Source process of the September 12, 2007 M_W 8.4 Southern Sumatra earthquake from tsunami tide gauge record inversion

3

4 Stefano Lorito, Fabrizio Romano, Alessio Piatanesi and Enzo Boschi

5

6 Istituto Nazionale di Geofisica e Vulcanologia, Via di Vigna Murata 605, 00143 Rome, Italy
7

8 Abstract

9 We infer the slip distribution and average rupture velocity of the magnitude M_w 8.4 September 12, 10 2007, Southern Sumatra earthquake from available tide-gauge records of the ensuing tsunami. We 11 select 9 waveforms recorded along the west coast of Sumatra and in the Indian Ocean. We assume 12 the fault plane and the slip direction to be consistent with both the geometry of the subducting plate 13 and the early focal mechanism solutions. Slip distribution and rupture velocity are determined 14 simultaneously by means of a non linear inversion method. We find high slip values (~10 m) into a 15 patch 100 km long and 50 km large, between 20 and 30 km of depth, about 100 km north-west from 16 the epicenter. Our estimate of rupture velocity is of 2.1±0.4 km/sec. The relatively large depth of 17 the main slip patch is the likely explanation for the small observed tsunami.

- 18
- 19
- 20
- 21
- 22
- 23
- 23
- 24
- 25

26 **1. Introduction**

On September 12, 2007 at 11:10:26 UTC an earthquake of magnitude M_W 8.4 occurred off the 27 28 west coast of Sumatra about 130 km SW of Bengkulu. The epicenter was localized at 4.517°S and 29 101.382°E, between the Sunda trench and Bengkulu (Figure 1). The induced sea-floor displacement 30 generated a moderate tsunami that nevertheless propagated through the Indian Ocean and was 31 recorded for example also by the tide-gauge at Salalah, Oman. Apart from minor aftershocks, it was followed, 12 hours later, by another earthquake of magnitude M_W 7.9 near the Sumatra coast, 185 32 33 km SSE of Padang (Figure 1). Both earthquakes caused in total 25 fatalities and 161 people were 34 injured [ref. USGS]. The seismic sequence continued on the next two days, with the biggest event 35 of magnitude M_W 7.1 happening on September 13. This sequence took place in the same zone 36 where the historical earthquakes of 1797 and 1833 also generated significant tsunamis [Nalbant et 37 al., 2005].

38 This is the fourth very large earthquake to occur on the Sunda megathrust and generating a 39 significant tsunami in less than three years (Figure 1). We recall the huge Sumatra-Andaman 40 earthquake and tsunami of December 26, 2004 with a magnitude M_W 9.2 and a rupture extent of 41 almost 1,300 km, that caused widespread victims and destruction on the Indian Ocean coasts. The 42 Sumatra-Andaman 2004 event was followed later on by the M_W 8.7 earthquake and tsunami of 43 Simeulue-Nias (March 28, 2005), generated along the Sunda trench on the stretch just contiguous to 44 the Southern end of the Sumatra-Andaman 2004 rupture zone. The imminence of the Nias 45 earthquake was predicted as a consequence of the coseismic stress induced by the slip distribution of the Sumatra-Andaman earthquake [McCloskey et al., 2005]. The rupture zone of the Simeulue-46 47 Nias earthquake has also a significant overlap with that of the historical 1861 earthquake and 48 tsunami [Nalbant et al., 2005]. The next destructive tsunami earthquake was the M_W 7.7 Java event 49 (July 17, 2006), with a rupture zone displaced southward with respect to the one of the Simeulue-50 Nias event. It generated an abnormally large tsunami with respect to what expected by its seismically radiated energy and it has been then catalogued as a "tsunami earthquake" [*Ammon et al.*, 2006; *Fuji and Satake*, 2006].

The inversion of tsunami waveforms is an important tool for characterizing the seismic source of off-shore earthquakes. Recently, such inversions have been performed by *Piatanesi and Lorito* (2007) and by *Fuji and Satake* (2007) to characterize the kinematic rupture of the 2004 Sumatra-Andaman earthquake.

A better understanding of the rupture process of tsunamigenic earthquakes originating on the Sunda megathrust is in turn a key issue for evaluating the possible consequences of future events both for the risk mitigation and the warning strategies design [*Borrero et al.*, 2006; *Geist et al.*, 2007; *McCloskey et al.*, 2007a; *McCloskey et al.*, 2007b].

Here we perform the inversion of the waveforms recorded by 9 tide-gauge stations distributed in the Indian Ocean both in the near and in the far field with respect to the source zone. Our goal is to retrieve the slip distribution and the average rupture velocity of the September 12, 2007 earthquake.

64

65 **2. Sea-level Data**

The tsunami waves generated by the September 12, 2007 earthquake were recorded by tide-gauge stations distributed in the Indian Ocean in the shallow waters of harbors and coastal sites. The data were available for download in near real time at the website of the University of Hawaii Sea Level Center (UHSLC; <u>http://ilikai.soest.hawaii.edu/RSL/</u>). Most of these stations are operated by the Global Sea Level Observing System (GLOSS; <u>http://www.gloss-sealevel.org/</u>).

71 The tsunami was also recorded by the DART buoy 23401 in the deep ocean northwest of Sumatra. 72 This buoy is owned and operated by the Thailand Meteorological Department (TMD) in 73 conjunction with National Disaster Warning Center of the Kingdom of Thailand. Data were 74 available in real-time at the National Data Buoy (NDBC) Center website 75 (http://www.ndbc.noaa.gov/dart.shtml), maintained by the U.S. National Oceanic and Atmospheric 76 Administration (NOAA).

Both the UHSLC and the DART 23401 records of this tsunami have a sampling rate of one minute. The positions of the stations we choose for the inversion are plotted on the map of Figure 1. Before using these data in the inversion, we remove tidal components to extract the tsunami signal and we select only the first cycles of the waveforms that are less sensitive to local bathymetry than later arrivals. We use an even narrow time window for Padang and Sibolga stations since they clearly show a resonant character in the later phases.

83

84 **3. Seismic Source Parameters**

85 To define the dimension of the causative fault, we use the spatial distribution of the aftershocks occurred during 12 hours after the mainshock, that is available at the National Earthquake 86 87 Information website Center of the U.S. Geological Survey (USGS; 88 http://neic.usgs.gov/neis/epic/epic.html). We choose a region large enough to contain all the 89 aftershocks, and then we end up with a length of 350 km and a width of 200 km (Figure 2).

The strike of the source is 323° roughly parallel to the Sunda trench [Bird, 2003]. The dip is fixed at 90 91 12°, using the quick moment tensor solution of the Global CMT project. We adopt a slip direction 92 (rake) of 105°, basing both on the focal mechanism and on the finite fault model calculated by C. Ji 93 according algorithm described in Ji al. to the et [2002], and available at 94 http://www.geol.ucsb.edu/faculty/ji/big earthquakes/2007/09/sumatra seismic.html/.

We split the source region into 28 square subfaults of dimension 50x50 km (see Table 1 of the Online Supplementary Material). The slip amount on each subfault is to be determined as a result of the inversion, along with the average rupture velocity.

98

99 4. Tsunami Modeling and Bathymetric Dataset

00 For each of the subfaults we calculate the corresponding marigrams at the coordinates of the tide-

01 gauges, which are the Green's functions we will use for the inversion.

02 The initial seawater elevation is assumed to be equal to the coseismic vertical displacement of the 03 sea bottom corresponding to an assumed "unitary" slip of 3 meters [Piatanesi and Lorito, 2007], 04 and computed through the Okada's analytical formulas [Okada, 1992], while the initial velocity 05 field is assumed to be identically zero. The boundary conditions are pure wave reflection at the 06 solid boundary (coastlines) and full wave transmission at the open boundary (open sea). The 07 tsunami wave propagation from the initial field to the tide-gauges is calculated by solving the non 08 linear shallow water equations, including Coriolis force and bottom friction, with a finite 09 differences scheme on a staggered grid. More detailed description of the equations as well as of the 10 numerical method can be found in Lorito et al. [2008], Piatanesi and Lorito [2007] and Mader [2001]. 11

12 The computational domain is shown in Figure 1. We choose a grid resolution for tsunami propagation of 1 arc-minute. The bathymetry grid is obtained by merging different bathymetric 13 14 datasets [e.g. Geist et al., 2007; Fujii and Satake, 2007]. We use as a background the 1 arc-min GEBCO bathymetry [British Oceanographic Data Center, 2003], version 1.02, available at the 15 16 British Oceanographic Data Center website (http://www.bodc.ac.uk/data/online delivery/gebco/). 17 To improve the bathymetry in shallow waters, particularly along the coast of Sumatra and around 18 some of the tide-gauges, we digitize, where available to us, 9 nautical charts (United Kingdom 19 *Hydrographic Office*, 2005; see Figure 1). We then remove the shallow water points from GEBCO 20 in correspondence of the digitized dataset and interpolate both on local 0.5 arc-min subgrids, before 21 resampling to 1 arc-min and merging to the whole domain.

22

23 **5. Inversion**

We use a non linear inversion method based on the simulated annealing technique to simultaneously infer both slip distribution and average rupture velocity, with a L1-L2 hybrid norm as cost function. The details can be found in *Piatanesi and Lorito* [2007] and in *Lorito et al.* [2008], and in the references therein. The average rupture velocity is assumed to be the uniform velocity of a circular front propagating out from the hypocenter on the fault plane. We consequently add the appropriate delay to the Green's function corresponding to each subfault, according to their distance along the rupture path.

The resolving power of the inversion setup (azimuthal coverage, sampling rate, fault 31 32 parametrization, etc.) is tested by means of a checkerboard experiment, with target slip values of 33 alternatively 2 and 6 meters on adjacent subfaults. We first tune the subfaults size by means of 34 several checkerboard experiments, starting with larger sizes and ending up with 50 by 50 km. We 35 moreover test for different rupture velocities. The synthetic waveforms generated with the 36 checkerboard slip distribution are corrupted with Gaussian noise, with a variance that is 20% of the 37 clean time series variance. We let the slip range between 0 and 15 meters, at 1 meter steps, whilst 38 the velocity ranges between 0.5 and 3.5 km/sec, at 0.5 km/sec steps.

39 The target slip distribution, i.e. the checkerboard pattern, is reproduced fairly well by the best model 40 (Figure 2, and Table 1 of the Online Supplementary Material), with a root mean square of the 41 differences between target and inverted values of 0.8 meters. Conversely, the target rupture velocity 42 of 2.5 km/sec is not inferred exactly, as our best model estimation is 2 km/sec. Following Piatanesi 43 and Lorito [2007], we estimate the uncertainty of each inverted parameters through an appraisal of 44 the ensemble of the models explored during the search stage (see Table 1 of the Online 45 Supplementary Material). In particular, the marginal distribution of the explored velocity values 46 shows quite a broad peak ranging between 2 and 2.5 km/sec (see inset of Fig. 2). The average 47 model estimation of the rupture velocity is 2.2±0.3 km/sec, that is consistent with the target velocity 48 of 2.5 km/sec. Later, in the real case inversion, we will then assume the average model value, in 49 place of the best model, as our estimate of the rupture velocity.

50 The checkerboard experiment results indicate that the dataset has the capability of resolving the 51 main features of the rupture kinematics, with a good resolution for the slip and a relatively worst 52 resolution for the velocity. 53 To retrieve the rupture features of the September 12, 2007 earthquake, we adopt the same subfaults 54 geometry and parameter ranges as in the checkerboard experiments. Moreover we adjust of a few minutes the arrival times of the Green's functions at the stations of Cocos, Sibolga, Colombo, 55 56 Diego Garcia and Pointe La Rue, at which we observed systematic differences between recorded 57 and simulated phases. Arcas and Titov [2006] discussed the difficulty in reproducing coastal in 58 comparison to offshore propagation, due to the poor bathymetry knowledge along with the 59 contamination from unmodeled coastal processes. We actually use the GEBCO bathymetry only at 60 some of the stations and did not simulate inundation, likely leading to travel times inaccuracy. An 61 adjustment of travel times has been performed also by Fuji and Satake [2006], who observed discrepancies at the Cocos station while studying the 2006 Java tsunami. In the present case, 62 63 however, we verified that the inverted rupture velocity is only slightly dependent on such arrival 64 time adjustments.

65 The slip distribution of the best model we find is shown in Figure 3. According to our results, the rupture propagated with a velocity of 2.1±0.4 km/sec, with a relatively low slip (2 to 3 meters) 66 67 around the hypocentral zone. The rupture then propagated to the North-West featuring the highest slip concentration (up to 12 meters) at about 3-3.5°S and 101°E, at a depth ranging between 20 to 68 69 30 km. We notice that this main patch is surrounded by most of the aftershocks. We also plot the 70 resulting coseismic vertical displacement, to be compared with the geodetic data when available. 71 The whole set of results, best model and average model with associated errors is reported in Table 1 72 in the online supplementary material. The best model slip values always fall well inside the error 73 bars. Conversely, the best model velocity lies at the upper edge of the error bar, confirming the best 74 model is an extreme one in this context and as velocity is concerned.

The match between the recorded and inverted waveforms is generally good (Figure 4). In some of the cases, as those of Padang (the nearest station to the source) and the DART buoy (the most reliable data) is excellent. The worst case is Diego Garcia, with at least the period well reproduced, while missing its amplitude. Overall, we satisfactorily reproduce the main features of the September
12, 2007 tsunami wave amplitudes and periods, and, in some cases, the arrival times.

80

81 6. Conclusions

We find that the source of the September 12, 2007 Southern Sumatra earthquake has been characterized by its highest slip values (~10 m) concentrated into a patch 100 km long and 50 km large, located between 20 and 30 km of depth, about 100 km north-west from the epicenter. The occurrence of such a slip amount has been suggested by *Nalbant et al.* [2005], who indicated that the greatest current seismic threat from the Sunda megathrust may came from a section overlapped with the source of the September 12, 2007 earthquake, with a slip as great as in 1833: that is, up to 10 meters.

The slip release has been very low or even absent at depths lower than 10-15 km. A shallower slip patch of about 2-3 meters occurred only around the epicentral latitudes.

91 These results are in fair agreement, at least as regard the localization of the main slip patches, with 92 those of Chen Ji

93 (http://www.geol.ucsb.edu/faculty/ji/big_earthquakes/2007/09/sumatra_seismic.html/), and in a

94 lesser extent with those of Yuji Yagi (http://www.geo.tsukuba.ac.jp/press HP/yagi/EQ/20070912/).

95 Nevertheless, the above teleseismic inversions infer a much lower slip amount than our inversion of96 tsunami waveforms.

97 Our best model features a seismic moment of 4.8×10^{21} N·m, if we use a shear modulus μ =6.0 × 98 10^{10} N/m² [*Geist and Bilek*, 2001], corresponding to a magnitude M_W 8.39 earthquake. This result is 99 consistent with the USGS estimation of a M_W 8.4 earthquake magnitude.


The depth of the earthquake is an important factor in controlling the tsunami amplitude especially in the near field. On one hand, slip at depth produces relatively small vertical displacement of the sea bottom. On the other hand, high slip at intermediate depths on the megathrust produces maximum sea floor displacements in shallow waters thus generating tsunamis with relatively small potential

04	energy. The absence of significant slip at shallow depths is then a likely explanation for the
05	generation of a relatively moderate tsunami. As a comparison, the tsunami generated by the smaller
06	and shallower Java 2006 $M_{\rm W}$ 7.7 earthquake was by far more destructive, and it has been then
07	catalogued as a "tsunami earthquake" [Fuji and Satake, 2006].
08	
09	Acknowledgments. We gratefully acknowledge the contribution of Alessio Mautone, at the INGV
10	SISMOS laboratory, who scanned the nautical charts we used in this work.
11	Some figures have been produced with Generic Mapping Tools software (Wessel and Smith, 1998).
12	
13	References
14	Ammon, C. J., H. Kanamori, T. Lay and A. A. Velasco (2006). The 17 July 2006 Java tsunami
15	earthquake, Geophys. Res. Lett., 33, L24308, doi:10.1029/2006GL028005.
16	Arcas, D., and V. V. Titov (2006), Sumatra tsunami: lessons from modeling, Surv. Geophys., 27,
17	679-705, doi:10.1007/s10712-006-9012-5.
18	Bird, P. (2003), An updated digital model of plate boundaries, Geochem. Geophys. Geosystems, 4,
19	1027, doi:10.1029/2001GC000252.
20	Borrero, J.C., K. Sieh, M. Chlieh, and C. E. Synolakis (2006), Tsunami inundation modeling for
21	western Sumatra, Proc. Nat. Acad. Sci., 103, 19673-19677.
22	British Oceanographic Data Center (2003). The Centenary Edition of the GEBCO Digital Atlas
23	[CD-ROM], Liverpool, UK.
24	Fujii Y., and K. Satake (2006), Source of the July 2006 West Java tsunami estimated from tide
25	gauge records, Geophys. Res. Lett., 33, L24317, doi:10.1029/2006GL028049.
26	Fujii Y., and K. Satake (2007), Tsunami Source of the 2004 Sumatra-Andaman Earthquake
27	Inferred from Tide Gauge and Satellite Data, Bull. Seismol. Soc. Am., 97, S192-S207,
28	doi:10.1785/0120050613.

- Geist, E.L., and S. L. Bilek (2001), Effect of depth-dependent shear modulus on tsunami generation
 along subduction zones, *Geophys. Res. Lett.*, 28, 1315-1318.
- Geist, E.L., V.V. Titov, D. Arcas, F. F. Pollitz, and S. L. Bilek (2007), Implications of the 26
 December Sumatra-Andaman earthquake on tsunami forecast and assessment models for
 great subduction-zone earthquakes, *Bull. Seismol. Soc. Am.*, *97*, S249-S270, doi:
 10.1785/0120050619.
- Ji, C., D.J. Wald, and D.V. Helmberger (2002), Source description of the 1999 Hector Mine,
 California earthquake; Part I: Wavelet domain inversion theory and resolution analysis,
 Bull. Seism. Soc. Am., *92*, 1192-1207.
- Lorito, S., A. Piatanesi, and A. Lomax (2008), Rupture Process of the 18 April 1906 California
 Earthquake from Near-Field Tsunami Waveform Inversion, *Bull. Seismol. Soc. Am.*, in
 press.
- 41 Mader, C. L. (2001). *Numerical modeling of water waves*, Los Alamos series in Basic and Applied
 42 Sciences, 206 p.
- McCloskey J., S. S. Nalbant, and S. Steacy (2005), Indonesian earthquake Earthquake risk from coseismic stress, *Nature*, 434, 291 291.
- McCloskey, J., A. Antonioli, A. Piatanesi, K. Sieh, S. Steacy, S.S. Nalbant, M. Cocco, C. Giunchi,
 J.D. Huang, and P. Dunlop (2007a), Near-field propagation of tsunamis from megathrust
 earthquakes, *Geophys. Res. Lett.*, *34*, L14316, doi:10.1029/2007GL030494.
- McCloskey, J., A. Antonioli, A. Piatanesi, K. Sieh, S. Steacy, S.S. Nalbant, M. Cocco, C. Giunchi,
 J.D. Huang, and P. Dunlop (2007b), Tsunami Threat in the Indian Ocean from a Future
 Megathrust Earthquake West of Sumatra, *Earth Planet. Sci. Lett.*, in press.
- Nalbant S. S., S. Steacy, K. Sieh, D. Natawidjaja, and J. McCloskey (2005), Seismology:
 Earthquake risk on the Sunda trench, *Nature*, 435, 756-757, doi:10.1038/nature435756a.
- 53 Okada, Y. (1992), Internal deformation due to shear and tensile faults in a half-space, *Bull. Seismol.*
- 54 Soc. Am., 82, 1018-1040.

- Piatanesi, A., and S. Lorito (2007), Rupture process of the 2004 Sumatra-Andaman earthquake
 from tsunami waveform inversion, *Bull. Seismol. Soc. Am.*, *97*, 223-231,
 doi:10.1785/0120050627.
- United Kingdom Hydrographic Office (2005). Catalogue of Admiralty Charts and Publications,
 2005 Edition, Taunton, Somerset, United Kingdom.
- Wessel, P., and W. H. F. Smith (1998), New, improved version of the Generic Mapping Tools
 Released, EOS Trans. AGU, 79, 579.

62



63

Figure 1. Epicenter and focal mechanism of the M_W 8.4 earthquake of 12 September 2007, along with the epicentral positions and focal mechanisms of the major recent tsunamigenic earthquakes on the Sunda trench. The triangles indicate the positions of the tide-gauge stations and of the DART buoy 23401. The bathymetry used for the simulation is represented by the colorscale. The rectangles are the limits of the nautical charts digitized to construct the bathymetric dataset.




Figure 2. Slip distribution of the best model resulting from the checkerboard test: the rectangles represent the projection of the subfaults to the Earth's surface. The black star indicates the epicenter position. The inset shows the marginal distribution of the rupture velocity; the blue and green vertical solid lines represent the best and average model value respectively.




Figure 3. Slip distribution of the best model resulting from the September 12, 2007 Sumatra event;
rectangles represent the projection of the subfaults to Earth's surface. The black star indicates the
epicenter of the mainshock and the green circles are the epicenter of the aftershocks occurred 12
hours after the main event. Solid and dashed contour lines represent the positive and negative
vertical displacement respectively.




Figure 4. Comparison between the observed time-shifted records (black solid lines) and computed
waveforms using the inverted best model (red solid lines). Grey dashed lines are the original
observed records.

92