

# Reynolds-stress and triple-product models applied to flows with rotation and curvature

Michael E. Olsen \*

NASA Ames Research Center

Moffett Field, CA 94035




Figure 1: Spinning Cylinder Flow Predictions for Various Turbulence Models,  $X=-4.72R$

Predictions for Reynolds-stress and triple product turbulence models are compared for flows with significant rotational effects. One of the turbulent flows is the spinning cylinder flow<sup>1-3</sup> when a fully developed essentially flat plate flowfield encounters a step change in the surface speed. This flowfield configuration introduces a destabilizing, turbulence enhancing combination of curvature and rotation. Comparison of predictions for the two components of velocity  $4.72R$  upstream of the end of the spinning section are shown in Figure 1.

A second flowfield that will be investigated is the alter ego of this flowfield, the rotating pipe,<sup>4-7</sup> which subjects an essentially fully developed pipe( $x=200R$ ) flowfield to a rotating section of pipe. The flow in the

\*Research Scientist, NASA Ames Research Center, Associate Fellow AIAA




Figure 2: Rotating Pipe Flow Predictions for Various Turbulence Models

rotating wall section is inherently stabilizing, and lowers the turbulent intensity as the flow progresses down the rotating section.

In figure 2a, the predictions for the wall static pressure from the Spalart-Almaras turbulence model, the Menter SST model, and three Lag Reynolds-stress models<sup>8</sup> are compared over the rotating section of the pipe. The turbulence models give different predictions for the axial skin friction in this section of the pipe, and hence predict different wall pressure distributions. The axial velocity distribution at the exit plane of the pipe (100 radii downstream of the rotation start) shown in figure 2b show similar differences.

The final paper will have comparisons for these models and the new triple product model<sup>9</sup> for at least these flowfields.

## References

<sup>1</sup>Bissonnette, L. R. and Mellor, G. L., “Experiments on the behaviour of an axisymmetric turbulent boundary layer with a sudden circumferential strain,” *Journal of Fluid Mechanics*, Vol. 63, 4 1974, pp. 369–413.

<sup>2</sup>DRIVER, D. M. and HEBBAR, S. K., “Experimental study of a three-dimensional, shear-driven, turbulent boundary layer,” *AIAA Journal*, Vol. 25, No. 1, Jan 1987, pp. 35–42.

<sup>3</sup>Higuchi, H. and Rubesin, M. W., “Behavior of a Turbulent Boundary Layer Subjected to Sudden Transverse Strain,” *AIAA Journal*, Vol. 17, No. 9, Sep 1979, pp. 931–941.

<sup>4</sup>Zaets, P., Onufriev, A., Safarov, N., and Safarov, R., “Experimental study of the behavior of the energy spectrum in a turbulent flow in a tube rotating relative to its longitudinal axis,” *Journal of Applied Mechanics and Technical Physics*, Vol. 33, No. 1, 1992, pp. 31–35.

<sup>5</sup>Kurbatskii, A. and Poroseva, S., “Modeling turbulent diffusion in a rotating cylindrical pipe flow,” *International Journal of Heat and Fluid Flow*, Vol. 20, No. 3, 1999, pp. 341 – 348.

<sup>6</sup>Reich, G. and Beer, H., “Fluid flow and heat transfer in an axially rotating pipeI. Effect of rotation on turbulent pipe flow,” *International Journal of Heat and Mass Transfer*, Vol. 32, No. 3, 1989, pp. 551 – 562.

<sup>7</sup>NISHIBORI, K., KIKUYAMA, K., and MURAKAMI, M., “Laminarization of Turbulent Flow in the Inlet Region of an Axially Rotating Pipe : Fluids Engineering,” *JSME international journal*, Vol. 30, No. 260, 1987, pp. 255–262.

<sup>8</sup>Olsen, M. E. , Lillard, R. P., and Murman S. M., “Separation Prediction of Large Separations with Reynolds Stress Models,” AIAA Paper 2013-2720.

<sup>9</sup>Olsen, M. E., “Prediction of Separation with a Third-Order-Moment Model,” AIAA Paper 2015-1968.