

5<sup>th</sup> International Association for the Advancement of Space Safety Conference  
Versailles, FRANCE  
October 17-19, 2011

# Human Factors Throughout the Life Cycle: Lessons Learned from the Shuttle Program

## Human Factors in Ground Processing



Barbara G. Kanki, PhD.  
NASA Ames Research Center  
Moffett Field, California USA  
[barbara.g.kanki@nasa.gov](mailto:barbara.g.kanki@nasa.gov)





# Agenda

## Human Factors in Ground Processing

- Introduction
  - Managing risk in human systems
  - Contributing risks: design, environment, process
- Example: STS-93 wire anomaly
  - Design risks
  - Environment risks
  - Process risks
  - Human systems issues
- Summary



# Managing Risk in Human Systems

- HUMAN SYSTEMS

- Individual / Teams
  - Skills & knowledge
  - Leadership
  - Team complement
  - Work practices
- Organizations
  - Training
  - Controls
  - Resources
  - Workforce

- DESIGN RISK

- Hardware / Software

- ENVIRONMENT RISK



- Workplace / Conditions / Hazards

- PROCESS RISK

- Procedures / Policies / Resources

Focus on the human interfaces

# Managing Risk in Human Systems



- DESIGN
  - Is damage visible?
  - Is there access to the work area?
- ENVIRONMENT
  - Is there adequate space, lighting?
  - Is PPE required?
- PROCESS
  - Are resources, controls adequate?
  - Are work procedures usable, up-to-date?
  - Do teams communicate/coordinate appropriately?





# STS-93 JULY 23, 1999

- Five seconds after lift-off, one of two redundant main engine controllers on two of the three engines shut down due to power fluctuation (later found to be due to wire arcing).
- **OUTCOME:** The redundant controllers on those two engines -- center and right main engines -- functioned normally allowing them to fully support Columbia's climb to orbit





An orbiter has more than 300 miles of wires such as these shown in the cable tray.




A damaged wire found during wiring inspections in Columbia's payload bay following STS-93, caused a short circuit in two separate main engine controllers on launch.



# Wiring In-Flight Anomaly: Basic Findings

- Inspection revealed a single 14 ga. polyimide wire had arced to a burred screw head; located in the aft left-hand mid-body bay #11 lower wire tray.
- Wiring in the mid-body payload bay normally covered; records indicate covers last removed during Orbiter Maintenance Down Period (OMDP) 4 years earlier in the Palmdale depot facility.





# Wiring In-Flight Anomaly: Root Cause

- Root cause
  - Work-induced collateral damage
  - No evidence of generic chafing exists (not simply fair wear-and-tear)
  - Wire protection specification applied inconsistently
- Therefore, assessments focused on maintenance practices.





# Wiring In-Flight Anomaly: Assessments

- Review the Space Shuttle systems and **maintenance practices**... look at NASA practices, Shuttle anomalies, and civilian and military experience. (NASA)
- Identify strengths and weaknesses in **shuttle processing**, compare shuttle processing to commercial aviation best practices, make suggestions to reduce Ground-Processing-Induced In-Flight Anomaly (**GPI-IFA**) risk (USA)

[http://www.hq.nasa.gov/osf/shuttle\\_assess.html](http://www.hq.nasa.gov/osf/shuttle_assess.html)



# HUMAN SYSTEM Issues

- **INDIVIDUAL RISKS:** Ground personnel expected to perform “error-free” and in compliance with procedures
  - Not aware of the in-flight consequences of ground-processing-induced “errors”
  - Downsized workforce under strain
- **TEAM-LEVEL RISKS:** KSC team and Palmdale processing teams have different standards
  - Wire inspection criteria need redefinition



# TECHNICAL Issues: Wiring System

- **DESIGN RISKS**

- Maximum feasible separation of redundant systems (e.g., redundancy of circuits compromised by placement in same wire bundle)
- Identification of single point failures
- Over time and modifications, additional wire protection for critical systems (e.g., wire tray covers become hard to close)

# TECHNICAL Issues: Wiring System



## ● WORK ENVIRONMENT RISKS

- Extensive wiring inspection, repair
- High traffic area?
- Access to work area?
- Damage visible?





# TECHNICAL Issues: Wiring System

## ● PROCESS RISKS

- Managed through certification, skill, procedural control, inspection, teaming and continuous reinforcement of safety awareness
- Little emphasis on error reporting, management, and understanding of why workmanship errors occur
- Line employees should be aware of relationship between workmanship/test errors and GPI-IFAs



# Summary

- Risk Management in Human Systems applies to:
  - Individuals
  - Teams
  - Organizations
- Risk Contributors to Human Systems are:
  - Design risks
  - Work Environment risks
  - Process risks



# Summary

- Apply Lessons Learned to future programs
  - Maintain a realistic attitude toward risky operations
  - Develop a better understanding of the risk of Ground-Processing-Induced In-Flight Anomalies
  - Expand corrective actions beyond specific, technical fixes
  - Fit solutions to the risks: design risks are not well-solved by process solutions



***Thank You***