View

citation

and

similar

papers

a

clo

4

34,

env

om

od (

r to of . Ę

as

lob

o:// 03.

es

ET

AOD

(OMI vs

The colo

of 0.02 A

color. Th

E

150000341 2019-08-31T14:23:17+00:00Z



Assessment of 10 Year Record of Aerosol Optical Der From OMI UV Observations

Changwoo Ahn^{1*}, Omar Torres², and Hiren Jethva³

1. Science Systems & Applications Inc., Lanham, MD USA (*Changwoo.Ahn@ssaihq.com) 2. NASA Goddard Space Flight Center Code 614, Greenbelt, MD USA 3. Universities Space Research Association / GESTAR, Greenbelt, MD USA

Background

The Ozone Monitoring Instrument (OMI) onboard the EOS-Aura satellite provides information on aerosol optical properties by making use of the large sensitivity to aerosol absorption in the near-ultraviolet (UV) spectral region. Another important advantage of using near UV observations for aerosol characterization is the low surface albedo of all terrestrial surfaces in this spectral region that reduces retrieval errors associated with land surface reflectance characterization. In spite of the 13 × 24 km² coarse sensor footprint, the OMI near UV aerosol algorithm (OMAERUV) retrieves aerosol optical depth (AOD) and single-scattering albedo under cloud-free conditions from radiance measurements at 354 and 388 nm. We present validation results of OMI AOD against space and time collocated Aerosol Robotic Network measured AOD values over multiple stations representing major aerosol episodes and regimes. OMAERUV's performance is also evaluated with respect to those of the Aqua-MODIS Deep Blue and Terra-MISR AOD algorithms over arid and semi-arid regions in Northern Africa. The outcome of the evaluation analysis indicates that in spite of the "row anomaly" problem, affecting the sensor since mid-2007, the long-term aerosol record shows remarkable sensor stability.

Reference: "Assessment of OMI near-UV Aerosol Optical Depth over Land", Changwoo Ahn, Omar Torres, and Hiren Jethva, Journal of Geophysical Research - Atmospheres, 10.1002/2013JD020188.

	Information o	f AOD Data Sets
Sensor Name	Version No.	Meaning of AOD Quality Assurance (QA) Flags
OMI-NASA (OMAERUV)	version 1.4.2	QA Flag 0 (= most reliable retrievals)
AERONET	version 2.0	Level 2.0 (= cloud screened and calibrated)
Aqua/MODIS Deep Blue	collection 5.1	QA Flag 3 (= very good confidence)
Terra/MISR	version 22	QA Flags 0 and 1 (= successful aerosol mixtures)
OMI-KNMI (OMAERO)	version 1.2.3.1	No QA Flags

AOD Collocation Method

• Within a radius of 40 km and ± 10 min window of the OMI overpass at 44 AERONET sites globally distributed over lands.

• Discard large standard deviations of OMI (> 0.3) daily matchups roughly corresponding to 3 % extreme outliers out of total collocated pairs at 44 sites over 4 years (2005 - 2008).

• The same collocation rules are applied to other data sets (i.e., MODIS, MISR, and KNMI).



Global locations of the selected 44 AERONET sites for comparisons with OMI AOD. Colors indicate the percent (O) of daily OMI-matched AOD values falling within the uncertainty envelope of ± 30% or

Green circle: $Q \ge 70\%$

Red circle: Q < 50%

0.1 AOD

Blue circle: $60\% \le Q < 70\%$

Pink circle: $50\% \le Q \le 60\%$



• N : Total number of daily match-ups for 2005 - 2008

Q = Percent of match-ups within ± 30 % or 0.1 AOD uncertainty limits.

• RMSE = SQRT[SUM (Y - LinearFitted Y)^2 / N]. Y is the OMI observation, X is the AERONET measurement

· y-intercept and slope from a linear fit.

ρ = Correlation Coefficient.







Sept15 - 18, 2014, Aura Science Team Meeting			
Conclusions			
ble to retrieve reliable scattering aerosol optical depths ud screening information is available.			
sites is in good agreement with AERONET AOD, showing RMSE= 0.16, $\rho = 0.81$, and the percent of OMI AOD values elope of \pm 30 % or 0.1 AOD is 64.93 %.			
parable to the MODIS Deep Blue and MISR, with relatively quality AOD over dust and biomass dominant sites.			
be associated with the remaining algorithm issues such as the surface albedo, aerosol models, and/or inadequate flagging urance (QA).			
al aerosol record is publicly available at the NASA data disc.sci.gsfc.nasa.gov/Aura/data_ shtml).			
)	Time Series		
	10) 10) 10) 10) 10) 10) 10) 10)		



44 AERONET Sites (2005 - 2008)



ents the number of pairs for each bin with the interval the minimum number of pairs (1.0) is shown in gray number of pairs between 50 and 110 is shown in pink.

ACKNOWLEDGEMENTS

- ught centers for providing AOD data from OMI 5
- ura/data-holdings/OMI/omaeruv v003.shtml/), MODIS you v/data/search.html), and MISR
- ĝ ODOCS/misr/table_misr.html) sensors. We also thank the
- ors for theirs efforts in establishing and maintaining the sites that ellite AOD values in this intercomparison study. This work was CORE NASA.