Abstract Submittal Form JANNAF Liquid Propulsion Subcommittee and Advanced Materials Panel Technical Interchange Meeting 3 – 5 September 2014 3 – 5 September 2014			
Abstract Due Date: Wednesday, June 4, 2013			
Title: Cleaning Process Development for Metallic Additively Manufactured Parts			
Session Area: 1 2 3 4 5 6 7 8 9			
Sponsoring organization if SBIR-funded:			
Primary Author (this author will receive all correspondence regarding participation in this program)			
Name: Dr. Terri L. Tramel			
Organization: NASA/MSFC/EM50			
Address: Marshall Space Flight Center, EM50,	Bldg 4711		
City: Huntsville	State: AL		ZIP Code: 35812
Phone: 256-544-6048	Fax:		Email: Terri.L.Tramel@nasa.gov
2nd Author			
Name: Mr. Roger Welker			
Organization: NASA/MSFC/EM50/Jacobs			
Address: Marshall Space Flight Center, EM50, Bldg 4711			
City: Huntsville State: AL			ZIP Code: 35812
Phone: 256-544-2787	Fax:		Email: Roger.W.Welker@nasa.gov
3rd Author			
Name: Mrs. Niki Lowery			
Organization: NASA/MSFC/EM50/Jacobs			
Address: Marshall Space Flight Center, EM50, Bldg 4711			
^{City:} Huntsville	State: AL		ZIP Code: 35812
Phone: 256-544-9596	Fax:		Email: Niki.M.Lowery@nasa.gov
4 th Author			
Name: Mr. Mark Mitchell			
Organization: NASA/MSFC/EM50			
Address: Marshall Space Flight Center, EM50, Bldg 4711			
City: Huntsville	State: AL		ZIP Code: 35811
Phone: 256-544-5860	Fax:		Email: Mark.A.Mitchell@nasa.gov
Approval			
Approved by Management		Placeholder	

Abstract Submittal Form

JANNAF Liquid Propulsion Subcommittee and Advanced Materials Panel Technical Interchange Meeting 3 – 5 September 2014

Abstract Due Date: Wednesday, June 4, 2013

Unclassified Abstract (250 - 300 words; do not include figures or tables)

Additive Manufacturing of metallic components for aerospace applications offers many advantages over traditional manufacturing techniques. As a new technology, many aspects of its widespread utilization remain open to investigation. Among these are the cleaning processes that can be used for post finishing of parts and measurements to verify effectiveness of the cleaning processes.

Many cleaning and drying processes and measurement methods that have been used for parts manufactured using conventional techniques are candidates that may be considered for cleaning and verification of additively manufactured parts. Among these are vapor degreasing, ultrasonic immersion and spray cleaning, followed by hot air drying, vacuum baking and solvent displacement drying. Differences in porosity, density, and surface finish of additively manufactured versus conventionally manufactured parts may introduce new considerations in the selection of cleaning and drying processes or the method used to verify their effectiveness.

This presentation will review the relative strengths and weaknesses of different candidate cleaning and drying processes as they may apply to additively manufactured metal parts for aerospace applications. An ultrasonic cleaning technique for exploring the cleanability of parts will be presented along with an example using additively manufactured Inconel 718 test specimens to illustrate its use. The data analysis shows that this ultrasonic cleaning approach results in a well-behaved ultrasonic cleaning/extraction behavior. That is, it does not show signs of accelerated cavitation erosion of the base material, which was later confirmed by neutron imaging. In addition, the analysis indicated that complete cleaning would be achieved by ultrasonic immersion cleaning at approximately 5 minutes, which was verified by subsequent cleaning of additional parts.

> By submitting an abstract, you agree to complete a final paper/presentation for publication and to attend the meeting to present this information.

- \succ Submit abstracts electronically; submittal instructions are found in the call for papers.
- > Direct questions to Kathleen Biglari, by phone at 410.992.7300 x 208, or email to <u>kbiglari@cpiac.jhu.edu</u>.