

NASA/TP—2013-217734



# Alternate-Fueled Combustor-Sector Emissions

*Nikita T. Saxena  
Tufts University, Medford, Massachusetts*

*Anna E. Thomas  
Georgia Institute of Technology, Atlanta, Georgia*

*Dale T. Shouse and Craig Neuroth  
Air Force Research Laboratory, Wright-Patterson Air Force Base, Wright-Patterson AFB, Ohio*

*Robert C. Hendricks  
Glenn Research Center, Cleveland, Ohio*

*Amy Lynch, Charles W. Frayne, Jeffrey S. Stutrud, Edwin Corporan, and Terry Hankins  
Air Force Research Laboratory, Wright-Patterson Air Force Base, Wright-Patterson AFB, Ohio*

## NASA STI Program . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) program plays a key part in helping NASA maintain this important role.

The NASA STI Program operates under the auspices of the Agency Chief Information Officer. It collects, organizes, provides for archiving, and disseminates NASA's STI. The NASA STI program provides access to the NASA Aeronautics and Space Database and its public interface, the NASA Technical Reports Server, thus providing one of the largest collections of aeronautical and space science STI in the world. Results are published in both non-NASA channels and by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services also include creating custom thesauri, building customized databases, organizing and publishing research results.

For more information about the NASA STI program, see the following:

- Access the NASA STI program home page at <http://www.sti.nasa.gov>
- E-mail your question to [help@sti.nasa.gov](mailto:help@sti.nasa.gov)
- Fax your question to the NASA STI Information Desk at 443-757-5803
- Phone the NASA STI Information Desk at 443-757-5802
- Write to:  
STI Information Desk  
NASA Center for AeroSpace Information  
7115 Standard Drive  
Hanover, MD 21076-1320



# Alternate-Fueled Combustor-Sector Emissions

*Nikita T. Saxena  
Tufts University, Medford, Massachusetts*

*Anna E. Thomas  
Georgia Institute of Technology, Atlanta, Georgia*

*Dale T. Shouse and Craig Neuroth  
Air Force Research Laboratory, Wright-Patterson Air Force Base, Wright-Patterson AFB, Ohio*

*Robert C. Hendricks  
Glenn Research Center, Cleveland, Ohio*

*Amy Lynch, Charles W. Frayne, Jeffrey S. Stutrud, Edwin Corporan, and Terry Hankins  
Air Force Research Laboratory, Wright-Patterson Air Force Base, Wright-Patterson AFB, Ohio*

Prepared for the  
14th International Symposium on Transport Phenomena and Dynamics of Rotating Machinery  
(ISROMAC-14)  
sponsored by the Fluid Systems Technology (FST) of Technische Universitat Darmstadt  
Honolulu, HI, February 27–March 2, 2012

National Aeronautics and  
Space Administration

Glenn Research Center  
Cleveland, Ohio 44135

## Acknowledgments

The authors would like to thank the NASA GRC technical editing and publishing staff for their diligent efforts in completing our paper.

This work was sponsored by the Fundamental Aeronautics Program  
at the NASA Glenn Research Center.

*Level of Review:* This material has been technically reviewed by expert reviewer(s).

Available from

NASA Center for Aerospace Information  
7115 Standard Drive  
Hanover, MD 21076-1320

National Technical Information Service  
5301 Shawnee Road  
Alexandria, VA 22312

Available electronically at <http://www.sti.nasa.gov>

# Alternate-Fueled Combustor-Sector Emissions

Nikita T. Saxena  
Tufts University  
Medford, Massachusetts 02155

Anna E. Thomas  
Georgia Institute of Technology  
Atlanta, Georgia 30332

Dale T. Shouse and Craig Neuroth  
Air Force Research Laboratory  
Wright-Patterson Air Force Base  
Wright-Patterson AFB, Ohio 45433

Robert C. Hendricks  
National Aeronautics and Space Administration  
Glenn Research Center  
Cleveland, Ohio 44135

Amy Lynch, Charles W. Frayne, Jeffrey S. Stutrud, Edwin Corporan, and Terry Hankins  
Air Force Research Laboratory  
Wright-Patterson Air Force Base  
Wright-Patterson AFB, Ohio 45433

## Summary

In order to meet rapidly growing demand for fuel, as well as address environmental concerns, the aviation industry has been testing alternate fuels for performance and technical usability in commercial and military aircraft. In order to make alternate fuels (and blends) a viable option for aviation, the fuel must be able to perform at a similar or higher level than traditional petroleum fuel. They also attempt to curb harmful emissions, and therefore a truly effective alternate fuel would emit at or under the level of currently used fuel. This report analyzes data from gaseous and particulate emissions of an aircraft combustor sector. The data were evaluated at various inlet conditions, including variation in pressure and temperature, fuel:air ratios, and percent composition of alternate fuel. Traditional JP-8+100 data were taken as a baseline, and blends of JP-8+100 with synthetic-paraffinic-kerosene (SPK) fuel (Fischer-Tropsch (FT)) were used for comparison. Gaseous and particulate emissions, as well as flame luminosity, were assessed for differences between FT composition of 0, 50, and 100 percent. The data show that SPK fuel (an FT-derived fuel) had slightly lower harmful gaseous emissions, and smoke number information corroborated the hypothesis that SPK-FT fuels are cleaner burning fuels.

## Introduction

Currently, alternate aviation fuels must satisfy MIL-DTL-83133F(2008) (military) or ASTM D 7566-Annex(2011) (commercial) standards and are termed “drop-in” fuel replacements. Fuel blends of up to 50 percent alternative fuel

blended with petroleum (JP-8), which have become a practical alternative, are individually certified on the market. In order for a fuel alternate to be truly effective, it must have a sustainable supply and cause little environmental harm. Combustor emissions are of great relevance in alternate fuel considerations for both combustor efficiency as well as environmental and human health. The life cycle analysis (LCA) of fuel feedstocks carries a great effect on the usability of the fuel in aviation and is directly related to the combustor emissions data. The LCA estimates the impact of the greenhouse gas emissions for the entire fuel process, from production to distribution to usage, and can determine the true efficacy of using alternate fuel blends (Ref. 1). The testing discussed in this study represents only the emissions created when the fuel is in use. Because alternative fuels from multiple feedstocks are still being explored, fuel-flexible engine combustors are the primary targets for these tests, as they will be used for most of the fueling with alternate fuels in the near future.

The emissions trending described in this paper proves some expected trends while highlighting differences for further observation. Data were taken from “Combustor A,” a proprietary-geometry three-cup combustor sector representative of current engine combustor technology (details withheld because of proprietary concerns). Both the gaseous and particulate sampling probes were placed at the nozzle exit plane. The probes were specially built for the cell facility at Wright-Patterson Air Force Base. The facility has two identical fueling systems in place: one for the JP-8+100 (herein referred to as “JP-8”) fueling purposes and one for the Fischer-Tropsch (FT) fuel. The fuel is blended on line to achieve the desired blend. Further details regarding the facility, errors, postprocessing

parameters, and so forth, are available in Reference 2. This report provides a full analysis of the data set introduced in that paper.

Generally, the FT fuel is expected to be a cleaner burning fuel than the JP-8 fuel, and the blend falls somewhere between the two. The blend data appear to lean closer to the JP-8 emissions count rather than the FT emissions, allowing us to conclude that JP-8 is the dominating fuel in the blend, which is of potential importance when determining carbon credits or other emissions implications. This is corroborated by observations in performance data sets for these tests.

## Combustor Parameters and Collection of Data

Data from Combustor A emissions were assessed for the following variables:

- (1) Inlet pressure ( $P$ ) and temperature ( $T$ ): 75 psia (0.52 MPa) and 500 °F (533 K), 125 psia (0.86 MPa) and 625 °F (603 K), 175 psia (1.21 MPa) and 725 °F (658 K), and 225 psia (1.55 MPa) and 790 °F (694 K)
- (2) Combustor pressure drop ( $\Delta P$ ): 3, 4, and 5 percent
- (3) Fuel blends: 100 percent JP-8, 50:50 JP-8:FT, and 100 percent FT ( $\pm 5$  percent)
- (4) Fuel:air ratio ( $F/A$ ): 0.010, 0.015, 0.020, and 0.025

Data were collected for the following emissions: NO (ppm), NO<sub>2</sub> (ppm), NO<sub>x</sub> (ppm), CO (ppm), CO<sub>2</sub> (percent), O<sub>2</sub> (percent), and total hydrocarbon (THC) (ppm). Photodiode output voltage was also taken, and both still and high-speed photography were used and can be correlated with this luminosity data.

Data such as smoke number information and particulate emissions are analyzed, in part, because of an incomplete data set. Data from collaborative testing sites are summarized in relevance to the paper to illustrate uniformity of the results.

## Gaseous Emissions

Emissions such as nitrogen and carbon oxides are important to military and civil aviation. The emissions data collected in this study are listed below.

(1) NO emissions: Nitric oxide (NO) emissions (with molecular atomic dimension 0.115 nm), measured in ppm, show uniform results for all pressure levels. There is a monotone decrease as the change in percentage combustor pressure drop ( $\% \Delta P$ ) increases and a monotone increase as  $F/A$  increases.

(2) NO<sub>2</sub> emissions: Nitrogen dioxide (NO<sub>2</sub>) emissions, measured in ppm, (0.221 nm) follow a monotone increase with  $F/A$ . There is little change as  $\% \Delta P$  increases. The FT fuel trends show greater NO<sub>2</sub> emissions than the JP-8 fuel. Unlike other emissions data, the 50:50 blend trends towards the FT fuel data rather than the JP-8 data.




Figure 1.—NO<sub>x</sub> emissions (ppm) for combustor inlet pressure of 75 psia (0.52 MPa) at 5 percent combustor pressure drop  $\Delta P$  at varied fuel:air ratio  $F/A$ . Fischer-Tropsch (FT) fuel emissions are marginally smaller than both JP-8 and 50:50 blend emissions.

(3) NO<sub>x</sub> emissions: Nitrogen oxide (NO<sub>x</sub>) emissions (ppm) were taken as a combination of NO (ppm) and NO<sub>2</sub> (ppm) data. Because NO emissions were greater, the NO trends are dominant in the NO<sub>x</sub> emissions data. Therefore, the emissions show a monotone decrease as  $\% \Delta P$  increases, and a monotone increase with  $F/A$  (Fig. 1), similar to the NO emissions. NO<sub>x</sub> emissions also increase with absolute pressure. Emissions from the 100-percent FT blend do tend to be lower than those of the JP-8 fuel, but the difference is too small to be conclusive.

(4) CO<sub>2</sub> emissions: The percent of carbon dioxide (CO<sub>2</sub>) emissions (0.116 nm) did not show a significant difference between fuels or  $\% \Delta P$ , and maintained a monotone increase with  $F/A$ .

(5) CO emissions: Carbon monoxide (CO) emissions (ppm) (0.113 nm) showed significant increases with  $F/A$ . In the 75-psia (0.52-MPa) pressure combustor, the only pressure for which the  $F/A$  data go up to 0.025, the CO concentration doubled from  $F/A$  of 0.020 to 0.025 (Fig. 2).

The FT and 50:50 fuels showed a more pronounced jump with the increasing  $F/A$  (0.020 to 0.025) than the JP-8. CO emissions also showed a drastic decrease as absolute pressure increased.

Figure 3 shows overall trends in CO emissions differences between the JP-8, the 50:50 blend, and FT fuels. A greater difference is apparent at higher  $F/A$  values. The 100-percent FT and 50:50 fuels generally emit less to similar amounts than JP-8 over the range of ( $\Delta P$ ) yet at higher  $F/A$  and lower inlet pressures ( $P$ ), emit higher amounts with increasing ( $\Delta P$ ). The differences in CO become less significant at higher  $P$  and lower  $F/A$ .




Figure 2.—CO emissions (ppm) for combustor inlet pressure of 75 psia (0.52 MPa) at 5 percent combustor pressure drop  $\Delta P$  at varied fuel:air ratio  $F/A$ . The large jump from lower  $F/A$  values to  $F/A = 0.025$  is clearly demonstrated.




Figure 3.—Fuel:air ratios  $F/A$  versus inlet pressures at 3, 4, and 5 percent combustor pressure drop  $\Delta P$  for differences in CO emissions (ppm) relative to JP-8 ( $CO_{\text{fuel blend}} - CO_{\text{JP-8}}$ ) in combustion of alternative fuels. Pressure and  $F/A$  combinations that increase differences are shown by warmer colors. (a) 100 percent Fischer-Tropsch (FT) fuel ( $CO_{\text{FT}} - CO_{\text{JP-8}}$ ). (b) 50:50 fuel blend of FT with JP-8 ( $CO_{\text{50:50}} - CO_{\text{JP-8}}$ ).




Figure 4.—Total hydrocarbon (THC) emission (ppm) variation with percent of Fischer-Tropsch (FT) fueling and fuel:air ratio  $F/A$  for combustor inlet pressure of 75 psia (0.52 MPa) at 5 percent  $\Delta P$ . Trending for THC emissions is inconclusive, but large emissions increase is again apparent as  $F/A$  approaches 0.025.

TABLE I.—COMBUSTOR EFFICIENCY DATA SUMMARY AT 75 psia (0.52 MPa)

|                             | Combustor pressure drop, $\Delta P$ |       |                       |       |                       |       |
|-----------------------------|-------------------------------------|-------|-----------------------|-------|-----------------------|-------|
|                             | 3 percent                           |       | 4 percent             |       | 5 percent             |       |
|                             | Fuel:air ratio, $F/A$               |       | Fuel:air ratio, $F/A$ |       | Fuel:air ratio, $F/A$ |       |
|                             | 0.010 to 0.020                      | 0.025 | 0.010 to 0.020        | 0.025 | 0.010 to 0.020        | 0.025 |
| Fuels                       |                                     |       |                       |       |                       |       |
| JP-8                        | 99.61                               | 99.32 | 99.56                 | 99.10 | 99.46                 | 99.20 |
| 50:50 blend                 | 99.65                               | 99.24 | 99.56                 | 99.09 | 99.46                 | 98.90 |
| Fischer-Tropsch (FT)        | 99.66                               | 99.20 | 99.58                 | 98.96 | 99.48                 | 98.87 |
| Average efficiency, percent | 99.64                               | 99.25 | 99.56                 | 99.05 | 99.47                 | 98.99 |
| Standard deviation          | 0.024                               | 0.058 | 0.011                 | 0.080 | 0.013                 | 0.181 |

(6)  $O_2$  emissions: The percent of oxygen ( $O_2$ ) emissions (0.116 nm) did not show a significant difference between fuels or  $\% \Delta P$ , and maintained a monotone increase with  $F/A$ .

(7) THC emissions: Total hydrocarbon (THC) emissions do not show trends directly related to  $F/A$ , fuel type, or  $\% \Delta P$  for  $F/A < 0.025$ . For the 75 psia (0.52 MPa) pressure data, there is again a significant increase in THC concentration, particularly for FT and 50:50 fuels relative to JP-8, from  $F/A$  of 0.020 to 0.025 (Fig. 4). The smoke number data are not available for this  $F/A$  of 0.025.

It is possible that a  $F/A$  of 0.025 represents the combustor efficiency drop-off ratio as the amount of uncombusted fuel rises significantly because of the fuel itself or combustor configuration (e.g., poor atomization,  $F/A$ , reactant-product mixing, or decreased heat content), contributing to higher emissions as shown in CO and THC data (Figs. 2 and 4).

The data taken at the combustors show that in the 75 psia (0.52 MPa) data, the combustor efficiency at  $F/A = 0.025$  is

slightly lower than the rest (Table I). At 3 percent  $\Delta P$ , the efficiency of all fuel blends averages to 99.64 percent with a standard deviation of 0.024 for  $F/A$  of 0.010, 0.015, and 0.020. However, at 0.025, the average efficiency is 99.25 percent with a standard deviation of 0.058. Similar trends are shown at 4 percent  $\Delta P$ , with averages and standard deviations of 99.56 and 0.011 along with 99.05 and 0.080, respectively, as well as 5 percent  $\Delta P$  with averages and standard deviations of 99.47 and 0.013 along with 98.99 and 0.181, respectively.

The efficiency difference between the first three  $F/A$  values and the fourth is much more significant than between the various types of fuel, as shown by the standard deviation. The data at 5 percent  $\Delta P$  and  $F/A = 0.025$  ratio is the one exception, as the difference between fuel blends is definite. The efficiency difference between fuel blends is more pronounced at higher  $\% \Delta P$  and  $F/A$ . The combustor efficiency for all three blends decreases as  $\Delta P$  increases, but for all  $F/A$  values before 0.025, the efficiency differences between the blends are insignificant.



## Smoke and Photodiode Numbers

The smoke number measurements were taken by filtering an exhaust sample and comparing the change in reflectance. The smoke data and the THC emissions (ppm) are expected to be somewhat correlated. The smoke number data from this testing run are partially incomplete, but the data obtained show some definite trends. Smoke number decreases as 100 percent FT fueling is approached, with more distinct decreases at higher  $F/A$ . Figure 5 illustrates this with the available smoke number data.

The change in flame photodiode luminosity is related to all variables tested. It increases with  $F/A$  and decreases steadily

with increasing  $\% \Delta P$  and  $\% FT$  composition (Fig. 6). The decreased luminosity of the 50:50 blend and the FT fuel show that they are cleaner burning fuels than JP-8 (Fig. 7). The luminosity indicates carbon presence in the flames, and therefore the potential for carbon deposits within or coming through the engine to be released into the environment. The decrease in luminosity as the fuel blend approaches full FT fuel implies that the radiative heat loss is also decreasing as would liner temperature. This decrease occurs across increasing  $\% \Delta P$  and decreased  $F/A$  as well, signifying lower heat losses, cleaner burning, and a higher exit temperature from the combustor of the engine.




Figure 5.—Smoke number variation with percent Fischer-Tropsch (FT) fueling for combustor inlet pressure of 175 psia (1.21 MPa) at 5 percent combustor pressure drop  $\Delta P$  at varied fuel:air ratio  $F/A$ . Lower smoke number indicates that FT fuels are cleaner burning than JP-8 fuels, especially at higher  $F/A$ .




Figure 6.—Variation in photodiode voltage output with fuel blending at various fuel:air ratios  $F/A$ , for combustor inlet pressure 75 psia (0.52 MPa) at 5 percent combustor pressure drop  $\Delta P$ . The decrease in luminosity as percentage of Fischer-Tropsch (FT) fuel approaches 100 is demonstrated.



Figure 7.—Digital camera photographs showing flame changes with changes in fuel blend at fuel:air ratio  $F/A = 0.020$ . JP-8 fuel is visibly more luminous.

## Particulate Emissions

The particulate emissions of any fuel are of utmost concern for both environmental and human health (Ref. 3). Like the gaseous emissions, they relate to engine temperature and pressure,  $\% \Delta P$ ,  $F/A$ , and fuel composition. The data available from this study do demonstrate the clear reduction in particulate emissions from FT fuel at all pressures and  $F/A$  values (Fig. 8). Because the particulate emission size-distribution data available from this particular study was not enough to

make definite conclusions, the effects of particulates will be left for another report. A figure of particulate sample size distributions has been included (Fig. 9) to illustrate again the significant difference between pure FT fuel and the blend and JP-8. The total number of particulates is visibly smaller, as is the peak size of the particles. This indicates the need for further studies into the size-related particle health effects. There are many analyses underway to characterize and compare particulate emissions for alternate fuels (e.g., alternative fuels testing on a C-17 aircraft (Ref. 4)).




Figure 8.—Particulate emissions number index  $E/n$  variations with test pressure and fuel:air ratio  $F/A$  for JP-8, Fischer-Tropsch (FT), and 50:50 blend fueling (Ref. 1). (Test data set is incomplete at 75 and 225 psia (0.52 and 1.55 MPa) for  $F/A = 0.015$  and at 225 psia for  $F/A = 0.025$ .)




Figure 9.—Alternate fueling particle size distribution from emissions data of JP-8, Fischer-Tropsch (FT), and 50:50 blend fuels for combustor pressure at 75 psia (0.52 MPa) and fuel:air ratio  $F/A = 0.025$  (Ref. 2).

The effect of these particulate emissions on human health has been concluded by a number of researchers (Ref. 5), and the U.S. Environmental Protection Agency has launched a program involving multiple research centers to further investigate the hazards. The hazards include distress in respiratory and cardiovascular function—contributing to the development or worsening of common distresses such as asthma, chronic obstructive pulmonary disorder, angina pectoris, myocardial infarction (heart attack), and more. The possibility and problems associated with particles moving into the blood stream and being transported to other vital organs is also being considered (Ref. 6).

## Engine Emissions Testing

Further testing that provides other insight into particulate emissions for both small and large engines has been done in collaboration with a large group of organizations, including government agencies, private industries, and educational institutions.

Testing run by General Electric (GE) showed that for alternate fuels, the emissions level of the regulated emissions (NO<sub>x</sub>, CO, hydrocarbons, and smoke number) were within the limits set for traditional fuels. The GE study observed power levels starting from idle through to takeoff, capturing a full performance that the data in this report does not span. This study corroborates our results, presenting alternative fuel emissions and indicating that similar trends occur all through the flying process, offering further insight for true LCA (Ref. 7).

A small-engine test with similar fuel parameters to ours was conducted with a Pratt & Whitney small turbine engine, with 100 percent FT fuel and JP-8 as well as a 50:50 blend. The trends observed in this test were similar: small reductions in NO<sub>x</sub> emissions as the SPK-FT fuel percentage increased, especially at higher power. The smoke number data was more conclusive, with the FT fuels having significantly lower smoke measurements than the JP-8 fuel (Ref. 8).

Larger engine tests, such as those conducted in the Alternate Aviation Fuel Experiment (AAFEX) study (Refs. 9 and 10), point in the same direction with regards to emissions trends. The C-17 test also tested both gaseous and particulate emissions data with similar results (Ref. 4).

## Emissions Implications

The European Union has recently moved to implement a carbon emissions tax on airlines flying in and out of its airspace, an act that has enraged officials in foreign countries such as the United States and China. America's aviation industry contributes approximately 2 percent of greenhouse gas emissions, and a law requiring payment per metric ton of carbon emission could place an overwhelming burden on an industry having hard times at present (Ref. 11). In order to maintain current flight profit and availability as well as market

competitiveness, it is necessary for countries to move towards alternate fuels such as those proposed in this report.

## Concluding Remarks

Gathering preliminary data is essential for establishing baseline information to compare performance and emissions data for alternate-fuel-flexible combustor-sector systems. Observing pure synthetic-paraffinic-kerosene (SPK) fuel (Fischer-Tropsch (FT)) and blended fuel with respect to JP-8+100 fuels can lead to the future development of new, efficient, and effective combustor systems for these up-and-coming types of fuel. Fuel-flexible systems are the near-term goal for the industry, and analysis of combustor performance is necessary for utilization of alternative fuels. The data from Combustor A summarized in this report provide analysis and comparison based on a variety of engine variables.

Inlet temperature and pressure, fuel-to-air ratio ( $F/A$ ), combustor pressure drops, and fuel blends were the parameters varied for this study.

Generally, the gaseous emissions varied more based on  $F/A$  than the fuel blend used. This report indicates that both 100 percent FT and the 50:50 blend emit at or under currently acceptable rates. Although the differences were not enormous, FT fuel did have generally lower NO<sub>x</sub> emissions, one of the primary regulated emissions species today. However, at higher  $F/A$ , the combustor efficiency drops and emissions increase more with FT fuel blends than with JP-8.

The smoke number differences were very distinct and point to the fact that, as hoped, SPK fuels are cleaner burning than JP-8 fuels, and the 50:50 blend is an intermediate step towards environmentally friendly fuel. It is important to note that a 50:50 blend does not directly correlate to a 50 percent reduction in smoke or emissions, which has implications towards the effectiveness of using a blend as an economic substitute.

Multiple studies and data sets show that SPK fuel and fuel blends do not have a significant negative impact on the performance of combustor sector systems, and that emissions produced certainly do not exceed the current limitations on traditional fuel. Taking into account the life cycle analysis and emissions reduction for alternate fueling, these SPK fuels are a promising near-term alternative for jet fuels.

Glenn Research Center  
National Aeronautics and Space Administration  
Cleveland, Ohio, September 23, 2013

## References

1. Stratton, Russell W.; Wong, Hsin Min; and Hileman, James I. Life Cycle Greenhouse Gas Emissions from Alternate Jet Fuels. Partnership for Air Transportation Noise and Emissions Reduction, PARTNER Project 28 Report, Version 1.2, 2010. <http://web.mit.edu/aeroastro/partner/reports/proj28/partner-proj28-2010-001.pdf> Accessed Sept. 23, 2012.

2. Shouse, D.T., et al.: Alternate-Fueled Combustor-Sector Performance: Part A: Combustor Performance: Part B: Combustor Emissions. ISROMAC13–2010–49, 2010.  
[http://ntrs.nasa.gov/archive/nasa/casi.ntrs.nasa.gov/20100017413\\_2010018362.pdf](http://ntrs.nasa.gov/archive/nasa/casi.ntrs.nasa.gov/20100017413_2010018362.pdf) Accessed Sept. 24, 2012.
3. Hendricks, Robert C.; and Bushnell, Dennis: Particulate Emissions Hazards Associated with Fueling Heat Engines. *Int. J. Rotating Mach.*, vol. 2011, no. 415296, 2011.  
<http://www.hindawi.com/journals/ijrm/2011/415296/> Accessed March 28, 2013.
4. Corporan, Edwin, et al.: Alternative Fuels Tests on a C–17 Aircraft: Emissions Characteristics. Air Force Research Laboratory, Interim Report, 2010.
5. Environmental Protection Agency: EPA Finds Greenhouse Gases Pose Threat to Public Health, Welfare/Proposed Finding Comes in Response to 2007 Supreme Court Ruling. News Release, 2009.  
<http://yosemite.epa.gov/opa/admpress.nsf/0/0EF7DF675805295D8525759B00566924> Accessed Jan. 22, 2013.
6. Lippmann, Morton, et al.: The U.S. Environmental Protection Agency Particulate Matter Health Effects Research Centers Program: A Midcourse Report of Status, Progress, and Plans. *Environ. Health Perspect.*, no. 111, no. 8, 2003.
7. Kinder, James D.; and Rahmes, Timothy: Evaluation of Bio-Derived Synthetic Paraffinic Kerosenes (Bio-SPK). Sustainable Biofuels Research & Technology Program document, The Boeing Company, Seattle, WA, 2009.  
[http://www.boeing.com/aboutus/govt\\_ops/reports\\_white\\_papers/pas\\_biofuel\\_exec\\_summary.pdf](http://www.boeing.com/aboutus/govt_ops/reports_white_papers/pas_biofuel_exec_summary.pdf) Accessed Sept. 24, 2012.
8. Rahmes, T.F., et al.: Sustainable Bio-Derived Synthetic Paraffinic Kerosene (Bio-SPK) Jet Fuel Flights and Engine Tests Program Results. AIAA 2009–7002, 2009.
9. Bulzan, D., et al.: Gaseous and Particulate Emissions Results of the NASA Alternative Aviation Fuel Experiment (AAFEX), GT2010–23524, 2010.
10. Anderson, B.E., et al.: Alternative Aviation Fuel Experiment (AAFEX). NASA/TM—2011-217059, 2011.  
[http://ntrs.nasa.gov/archive/nasa/casi.ntrs.nasa.gov/20110007202\\_2011007929.pdf](http://ntrs.nasa.gov/archive/nasa/casi.ntrs.nasa.gov/20110007202_2011007929.pdf) <http://ntrs.nasa.gov/search.jsp>
11. CleanBiz: Trade War Looms Over EU’s Airline Carbon Tax. CleanBiz Asia, 2011.  
<http://www.cleanbiz.asia/story/trade-war-looms-over-eu%E2%80%99s-airline-carbon-tax>.

| REPORT DOCUMENTATION PAGE   |                         |  | Form Approved<br>OMB No. 0704-0188                                    |                                     |  |
|---|-------------------------|--|---|-------------------------------------|--|
| <p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</p>  |                         |  |   |                                     |  |
| <b>1. REPORT DATE (DD-MM-YYYY)</b><br>01-09-2013  |                         | <b>2. REPORT TYPE</b><br>Technical Paper |   | <b>3. DATES COVERED (From - To)</b> |  |
| <b>4. TITLE AND SUBTITLE</b><br>Alternate-Fueled Combustor-Sector Emissions   |                         |  | <b>5a. CONTRACT NUMBER</b>  |                                     |  |
|   |                         |  | <b>5b. GRANT NUMBER</b>   |                                     |  |
|   |                         |  | <b>5c. PROGRAM ELEMENT NUMBER</b>                                     |                                     |  |
| <b>6. AUTHOR(S)</b><br>Saxena, Nikita, T.; Thomas, Anna, E.; Shouse, Dale, T.; Neuroth, Craig; Hendricks, Robert, C.; Lynch, Amy; Frayne, Charles, W.; Stutrud, Jeffrey, S.; Corporan, Edwin; Hankins, Terry  |                         |  | <b>5d. PROJECT NUMBER</b>   |                                     |  |
|   |                         |  | <b>5e. TASK NUMBER</b>  |                                     |  |
|   |                         |  | <b>5f. WORK UNIT NUMBER</b><br>WBS 561581.02.08.03.16.03              |                                     |  |
| <b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b><br>National Aeronautics and Space Administration<br>John H. Glenn Research Center at Lewis Field<br>Cleveland, Ohio 44135-3191  |                         |  | <b>8. PERFORMING ORGANIZATION REPORT NUMBER</b><br>E-17901-1          |                                     |  |
| <b>9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b><br>National Aeronautics and Space Administration<br>Washington, DC 20546-0001  |                         |  | <b>10. SPONSORING/MONITOR'S ACRONYM(S)</b><br>NASA                    |                                     |  |
|   |                         |  | <b>11. SPONSORING/MONITORING REPORT NUMBER</b><br>NASA/TP-2013-217734 |                                     |  |
| <b>12. DISTRIBUTION/AVAILABILITY STATEMENT</b><br>Unclassified-Unlimited<br>Subject Categories: 07, 44, 45, and 05<br>Available electronically at <a href="http://www.sti.nasa.gov">http://www.sti.nasa.gov</a><br>This publication is available from the NASA Center for AeroSpace Information, 443-757-5802   |                         |  |   |                                     |  |
| <b>13. SUPPLEMENTARY NOTES</b>  |                         |  |   |                                     |  |
| <b>14. ABSTRACT</b><br>In order to meet rapidly growing demand for fuel, as well as address environmental concerns, the aviation industry has been testing alternate fuels for performance and technical usability in commercial and military aircraft. In order to make alternate fuels (and blends) a viable option for aviation, the fuel must be able to perform at a similar or higher level than traditional petroleum fuel. They also attempt to curb harmful emissions, and therefore a truly effective alternate fuel would emit at or under the level of currently used fuel. This report analyzes data from gaseous and particulate emissions of an aircraft combustor sector. The data were evaluated at various inlet conditions, including variation in pressure and temperature, fuel-to-air ratios, and percent composition of alternate fuel. Traditional JP-8+100 data were taken as a baseline, and blends of JP-8+100 with synthetic-paraffinic-kerosene (SPK) fuel (Fischer-Tropsch (FT)) were used for comparison. Gaseous and particulate emissions, as well as flame luminosity, were assessed for differences between FT composition of 0, 50, and 100 percent. The data show that SPK fuel (an FT-derived fuel) had slightly lower harmful gaseous emissions, and smoke number information corroborated the hypothesis that SPK-FT fuels are cleaner burning fuels. |                         |  |   |                                     |  |
| <b>15. SUBJECT TERMS</b><br>Green aviation; Fueling; Energy; Particulates; Pollution control; Air pollution; Combustion product; Combustor design   |                         |  |   |                                     |  |
| <b>16. SECURITY CLASSIFICATION OF:</b>  |                         |  | <b>17. LIMITATION OF ABSTRACT</b>                                     | <b>18. NUMBER OF PAGES</b><br>16    | <b>19a. NAME OF RESPONSIBLE PERSON</b><br>STI Help Desk (email: <a href="mailto:help@sti.nasa.gov">help@sti.nasa.gov</a> ) |
| <b>a. REPORT</b><br>U   | <b>b. ABSTRACT</b><br>U | <b>c. THIS PAGE</b><br>U                 |   |                                     | <b>19b. TELEPHONE NUMBER (include area code)</b><br>443-757-5802   |



