

NASA-CR-195115

NASA CONTRACTOR REPORT

IN-05CR  
3844  
10P

# ADVANCED VEHICLE CONCEPTS SYSTEMS AND DESIGN ANALYSIS STUDIES

Mark H. Waters  
and  
Loc C. Huynh

Eloret Institute  
3788 Fabian Way  
Palo Alto, CA 94303

Prepared for

Ames Research Center  
under Cooperative Agreement NCC2-746



National Aeronautics and  
Space Administration

Ames Research Center  
Moffett Field, California 94035

(NASA-CR-195115) ADVANCED VEHICLE  
CONCEPTS SYSTEMS AND DESIGN  
ANALYSIS STUDIES Final Technical  
Report, 1 Apr. 1992 - 31 Jan. 1994  
(Eloret Corp.) 10 p

N94-29721

Unclass

G3/05 0003844

NASA CONTRACTOR REPORT

# ADVANCED VEHICLE CONCEPTS SYSTEMS AND DESIGN ANALYSIS STUDIES

Mark H. Waters  
and  
Loc. C. Huynh

CONTRACT NAS2-

**NASA**

1. Report No.	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle ADVANCED VEHICLE CONCEPTS SYSTEMS ANA DESIGN ANALYSIS STUDIES		5. Report Date 20 April, 1994	6. Performing Organization Code
		8. Performing Organization Report No.	
7. Author(s) Mark H. Waters and Loc C. Huynh		10. Work Unit No.	
9. Performing Organization Name and Address Eloret Institute 3788 Fabian Way Palo Alto, CA 94303		11. Contract or Grant No. NCC2-746	
		13. Type of Report and Period Covered	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administr. Washington, D.C. 20456		14. Sponsoring Agency Code	
		15. Supplementary Notes Point of Contact: Mr. Mark H. Waters c/o 237-11 NASA Ames Research Center, Moffett Field, CA 94035	
16. Abstract  The work conducted by ELORET Institute under this Cooperative Agreement includes the modeling of hypersonic propulsion systems, and the evaluation of hypersonic vehicles in general and most recently hypersonic waverider vehicles. This work in hypersonics was applied to the design of a two-stage to orbit launch vehicle which was included in the <i>NASA Access to Space Project</i> . Additional research regarded the Oblique All-Wing (OAW) Project at NASA Ames and included detailed configuration studies of OAW transport aircraft. Finally, work on the modeling of subsonic and supersonic turbofan engines was conducted under this research program.			
17. Key Words (Suggested by Author(s)) hypersonic propulsion systems hypersonic waverider vehicles supersonic turbofan engines oblique all-wing transport		18. Distribution Statement  unclassified, unlimited	
19. Security Classif. (of this report) unclassified	20. Security Classif. (of this page) unclassified	21. No. of Pages	22. Price*

# **Advanced Vehicle Concepts Systems and Design Analysis Studies**

**Final Technical Report  
for  
Cooperative Agreement NCC2-746**

for the period  
April 1, 1992 - January 31, 1994

Submitted to

National Aeronautics and Space Administration  
Ames Research Center  
Moffett Field, California 94035

Systems Analysis Branch  
George H. Kidwell, Chief and Technical Officer

Prepared by

ELORET INSTITUTE  
3788 Fabian Way  
Palo Alto, CA 94303  
Phone: (415) 493-4710  
Telefax: (415) 424-9876  
K. Heinemann, President and Grant Administrator  
Mark H. Waters, Principal Investigator  
Loc C. Huynh, Co-Principal Investigator

20 April, 1994

## ABSTRACT

The objective for this research program was to develop more sophisticated analysis tools to model the aerodynamic, propulsion, and structural characteristics of vehicles and the dynamics of vehicles in flight. The work conducted by ELORET Institute under this Cooperative Agreement includes the modeling of hypersonic propulsion systems, and the evaluation of hypersonic vehicles in general and most recently hypersonic waverider vehicles. This work in hypersonics was applied to the design of a two-stage to orbit launch vehicle which was included in the *NASA Access to Space Project*. Additional research regarded the Oblique All-Wing (OAW) Project at NASA Ames and included detailed configuration studies of OAW transport aircraft. Finally, work on the modeling of subsonic and supersonic turbofan engines was conducted under this research program.

## INTRODUCTION

This research activity has been conducted at the Systems Analysis Branch at NASA Ames Research Center and involves the preliminary design and mission evaluation of advanced vehicle concepts. An advanced vehicle can be any aircraft or spacecraft being proposed within or without NASA. The objective of the work is to conduct vehicle design and mission studies in enough depth so that meaningful comparisons between concepts can be

made and conclusions can be drawn regarding the technical and/or economic viability of a given concept. Typically, several different vehicle concepts may be proposed for a given mission requirement, and a study will emphasize a comparison between concepts.

The objective for this research program was to conduct a major effort in the development of more sophisticated analysis tools to model the aerodynamic, propulsion, and structural characteristics of the vehicles and dynamics of the vehicles in flight. The work conducted by ELORET Institute under this Research Task included the following major topics:

- ◆ Hypersonic Propulsion Modeling
- ◆ Evaluation of a Hypersonic Waverider Vehicle
- ◆ Evaluation of Vehicle Concepts for the NASA Access to Space Project
- ◆ Oblique All-Wing (OAW) Transport Aircraft
- ◆ Turbofan Engine Modeling
- ◆ Propulsion Systems for High Flier Unmanned Aircraft Designs

The following sections report on each of these research topics.

## HYPERSONIC PROPULSION MODELING

The development of analytical tools for hypersonic vehicle analysis is a major effort in the Systems Analysis Branch. Work under this Research Task has specifically supported the development of a "Nose-To-Tail" (NTT) propulsion system model for hypersonic

aircraft. Such a program is made difficult because the propulsion system actually involves the aircraft design as well because the vehicle forebody serves as a compression surface for the propulsion system inlet, and the vehicle afterbody serves as an expansion surface for the propulsion system nozzle. Coupled with this is the need to use real gas effects throughout the analysis to account for the reactive properties of air and fuel-air mixtures at high temperature.

Specifically in this Task, programs have been written for the analysis of the vehicle forebody shock field and engine inlet, the engine combustor, and the engine nozzle and vehicle afterbody which serves as the expansion surface for the engine exhaust gas. A graphics program displays a flow path elevation of the complete propulsion system with the associated shock field geometry for each component.

#### HYPERSONIC WAVERIDER VEHICLE

Under this Research Task, on-going work has supported the design and evaluation of a broad range of vehicle designs and requirements (1,2,3). Most recently, the work has concentrated on an optimized Mach 6 hydrocarbon fuel waverider vehicle. Waveriders are a class of hypersonic vehicles designed to take full advantage of the bow shock generated by the vehicle shape to generate lift at hypersonic speeds. The aerodynamic

shape of such a vehicle is extremely important for good aerodynamic performance, but if other major considerations such as structural weight and propulsion system integration are ignored, a completely impractical vehicle will result.

This Research Task has been part of a specific project to optimize a hydrocarbon fueled waverider designed for Mach 6. A complete synthesis of the vehicle included all aspects of the design and practical constraints. As a result of this analytical project, a waverider vehicle has been defined, and a wind tunnel program is planned to evaluate the low speed characteristics of such a vehicle.

#### SUPPORT FOR ACCESS TO SPACE PROJECT

An agency wide project to evaluate future candidate launch vehicles to replace the space shuttle took place throughout much of 1993. The Systems Analysis Branch supported the work on this project being done at the NASA Ames Research Center, and in particular work under this Research Program was conducted to model a two stage to orbit (TSTO) launch vehicles. The design has a first stage having airbreathing propulsion and a rocket powered second stage. The airbreathing propulsion is a combination of turbofan engines and ramjets fueled with liquid hydrogen. Takeoff and landing are both horizontal, and the best staging Mach number is approximately 5. The results of this work are very promising, and they were included in the final report presented to NASA Headquarters.



## OBLIQUE ALL-WING (OAW) TRANSPORT AIRCRAFT

The OAW program is in its second year with an ultimate goal of a test in the 9'x7' supersonic wind tunnel in May, 1994. The Eloret Institute Principal Investigator of this Research Program has acted as the Co-Leader of this project from its inception at NASA Ames in June, 1992. The work involves approximately 10 people from four different divisions at NASA Ames and contracts with both Boeing Commercial Airplane Company and Douglas Aircraft Company.

The specific work within the Systems Analysis Branch involves the definition and evaluation of a reasonable configuration that would serve as a commercial transport aircraft to carry 450-500 passengers over long range (nominally 5000 N.Mi.) at a flight Mach number of 1.6. The wind tunnel model to be built will be based on this configuration.

The definition and evaluation of the OAW aircraft configuration involves all aspects of airplane design -- structures, weights, propulsion, aerodynamics, and airline economics. Numerous CFD programs are being used to design the wing aerodynamic shape of the wing, and the resulting aerodynamic performance along with the other aspects of the design are modeled in the ACSYNT aircraft synthesis program to simulate the complete

aircraft design and mission performance. Two AIAA conference papers(4,5) have been prepared and were presented in August, 1992. These papers have proven to be a valuable interim step in the definition of an OAW transport aircraft.

## TURBOFAN ENGINE MODELING

The long term requirement for this Research Task is to provide propulsion system modeling. To that end there is a major and on-going effort to model subsonic and supersonic turbofan engines for use in the aircraft synthesis programs used in the Branch.

The most direct approach is to use a cycle analysis program developed by an engine manufacturer to produce the basic data. These data for thrust, airflow, and fuel flow are then modeled in a generalized form and integrated in to the synthesis programs. The advantage of this general form is that the data can be scaled to different rated thrust sizes, and the models are sensitive to changes in engine pressure recovery and non-standard day atmospheric conditions.

Most recently, there was a major effort within this research program to have the capability of a basic cycle analysis program within the Branch. The long range goal is to include engine cycle parameters such as compression ratio, turbine inlet temperature, and bypass ratio as parameters in large scale aircraft optimization problems.

The approach being taken is two-fold. First the well known cycle program NEP is being used. This is the NASA Engine Program developed at NASA Lewis Research Center. This program requires the use of fan, compressor, and turbine maps, and separate programs developed by the General Electric Company for NASA Lewis are used for this purpose. Second, a design point program is being written as part of the Research Task. This program computes the detailed turbine cooling requirements of the engine, the geometric flow path through the engine, and the engine weight. The flowpath is used to estimate the weight of each engine component, but it is also important because key data required for input to the turbine map program are generated.

#### PROPULSION SYSTEMS FOR HIGH FLYER AIRCRAFT DESIGNS

The development of unmanned, high altitude aircraft is an on-going project within the Systems Analysis Branch. These aircraft are referred to as "Platforms", and the objective is to have a means for high altitude atmospheric sampling. The evaluation and modeling of propulsion systems for these high altitude platforms was part of this research program, and most recently the J75-P-13 turbojet engine has been modeled to study the effect of low Reynolds numbers on turbojet engine performance. This is the engine currently used in the U2C high altitude aircraft, and it is rated up to 75000 feet.

## REFERENCES

1. Molvik, G.(MCAT), Bowles, J (NASA Ames), Huynh, L.(Eloret Institute), "Hydrocarbon Scramjet with Augmented Preburning", AIAA paper 92-3425.
2. Molvik, G.(MCAT), Bowles, J (NASA Ames), Huynh, L.(Eloret Institute), "Analysis of a Hypersonic Research Vehicle with a Hydrocarbon Scramjet Engine", AIAA paper 93-0509.
3. Molvik, G.(MCAT), Bowles, J.(NASA Ames), Huynh, L.(Eloret Institute), "A Hypersonic Research Vehicle with Hydrocarbon Scramjet Propulsion: Design and Analysis", AIAA paper 93-5097, Munich Germany, November, 1993.
4. Waters, M. (Eloret Inst.), Ardema, M. (NASA Ames), Roberts, C. (Sterling Software), Kroo, I. (Stanford Univ.), "Structural and Aerodynamic Considerations for an Oblique All-Wing Aircraft", AIAA paper 92-4220, Hilton Head, SC, August, 1992.
5. Galloway, T., Gelhausen, P., Moore, M. (NASA Ames), Waters, M. (Eloret Inst.), "Oblique Wing Supersonic Transport Concepts", AIAA paper 92-4230, Hilton Head, SC, August, 1992.