



National Aeronautics and  
Space Administration

Lyndon B. Johnson Space Center  
Houston, Texas 77058

DMS-DR-2547  
NASA-CR-167,697

VOLUME 2 OF 2

RESULTS OF THE SPACE SHUTTLE VEHICLE ASCENT AIR  
DATA SYSTEM PROBE CALIBRATION TEST USING A 0.07-  
SCALE EXTERNAL TANK FOREBODY MODEL (68T) IN THE  
AEDC 16-FOOT TRANSONIC WIND TUNNEL (IA-310)

# SPACE SHUTTLE AEROTHERMODYNAMIC DATA REPORT

CRAIGEN-167670 - RESULTS OF THE SPACE  
SHUTTLE VEHICLE ASCENT AIR DATA SYSTEM PROBE  
CALIBRATION TEST USING A 0.07-SCALE EXTERNAL  
TANK FOREBODY MODEL (68T) IN THE AEDC  
16-FOOT TRANSONIC WIND TUNNEL (IA-310)


CR-167674

and 1-5  
63/15 09-2000

Data ManAGEMENT SERVICES

MICHoud ENGINEERING OFFICE

CHRYSLER  
TECHNOLOGIES  
AIRBORNE SYSTEMS



November 1991

DMS-DR-2547  
NASA-CR-167,697

VOLUME 2 OF 2

RESULTS OF THE SPACE SHUTTLE VEHICLE  
ASCENT AIR DATA SYSTEM PROBE CALIBRATION TEST  
USING A 0.07-SCALE EXTERNAL TANK FOREBODY MODEL (68T)  
IN THE AEDC 16-FOOT TRANSONIC WIND TUNNEL  
(IA-310)

by

J.G.R. COLLETTE  
ROCKWELL INTERNATIONAL  
SPACE TRANSPORTATION SYSTEMS DIVISION

Prepared under NASA Contract Number NAS9-17840

by

DATA MANAGEMENT SERVICES  
CHRYSLER TECHNOLOGIES AIRBORNE SYSTEMS  
MICHoud ENGINEERING OFFICE  
NEW ORLEANS, LOUISIANA 70189

for

NAVIGATION, CONTROL & AERONAUTICS DIVISION

JOHNSON SPACE CENTER  
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION  
HOUSTON, TEXAS

WIND TUNNEL TEST SPECIFICS:

TEST NUMBER: TF-783  
NASA SERIES NUMBER: IA-310  
MODEL NUMBER: 68-T  
TEST DATES: Sept. 28, 1989 thru October 1, 1989  
OCCUPANCY HOURS: 64 (44 Air-On Hours)

FACILITY COORDINATOR:

Earl A. Price, Jr. - MS 600  
Arnold Engineering Development Center  
Propulsion Wind Tunnel Facility  
Arnold Air Force Station, TN 37389

Telephone: (615) 454-6675

PROJECT ENGINEERS:

D. E. Reichenau - MS 600

J.G.R. Collette - AE21  
C.L. Berthold - AE21  
A.A. Reinberger - AE21

AEDC  
Propulsion WT Facility  
Arnold AF Station, TN 37389

Rockwell International  
STSD Division  
12214 Lakewood Blvd.  
Downey, CA 90241

Phone: (615) 454-6672

Phone: (213) 922-5352

DATA MANAGEMENT SERVICES:

Approved: J. L. Glynn  
J. L. Glynn, Manager  
Data Management Services

Concurrence: D.E. Poucher  
D.E. Poucher, Mgr.  
CTAS Michoud Engrg. Office

RESULTS OF THE SPACE SHUTTLE VEHICLE  
ASCENT AIR DATA SYSTEM PROBE CALIBRATION TEST  
USING A 0.07-SCALE SCALE EXTERNAL TANK FOREBODY MODEL (68T)  
IN THE AEDC 16-FOOT TRANSONIC WIND TUNNEL  
(IA-310)

by

J.G.R. COLLETTE  
ROCKWELL INTERNATIONAL  
SPACE TRANSPORTATION SYSTEMS DIVISION

ABSTRACT

A recalibration of the Space Shuttle Vehicle Ascent Air Data System probe was conducted in the AEDC transonic wind tunnel. The purpose was to improve on the accuracy of the previous calibration in order to reduce the existing uncertainties in the system.

A probe tip attached to a 0.07-scale External Tank Forebody model was tested at angles of attack of -8 to +4 degrees and sideslip angles of -4 to +4 degrees. High precision instrumentation was used to acquire pressure data at discrete Mach numbers ranging from 0.6 to 1.55. Pressure coefficient uncertainties were estimated at less than 0.0020.

**(This page intentionally left blank)**

## TABLE OF CONTENTS

	<u>PAGE</u>
ABSTRACT	iii
INDEX OF MODEL FIGURES	2
INDEX OF DATA FIGURES	3
INTRODUCTION	4
NOMENCLATURE	5
CONFIGURATIONS INVESTIGATED	8
INSTRUMENTATION	9
TEST FACILITY DESCRIPTION	12
TEST PROCEDURES	13
DATA REDUCTION	16
REMARKS	18
REFERENCES	21
TABLES	
I TEST CONDITIONS	22
II DATASET/RUN NUMBER COLLATION SUMMARY	23
III PROBE DIMENSIONAL DATA	36
IV PRESSURE TAP LOCATIONS	37
V ESP ORIFICE ASSIGNMENTS	38
FIGURES	
MODEL	39
DATA (VOLUME 1)	51
APPENDIX	
TABULATED SOURCE DATA -	Volume 1 R&S Datasets Pages 1 thru 420
-	Volume 2 T,U, & V Datasets Pages 421 thru 1050

PRECEDING PAGE BLANK NOT FILMED

## INDEX OF MODEL FIGURES

<u>FIGURE</u>	<u>TITLE</u>	<u>PAGE</u>
1a.	MODEL PROFILE LINES	39
b.	MODEL FRONT VIEW	40
c.	AADS PROBE AND CONE	41
d.	AADS PROBE AND CONE (PHOTO)	42
2.	MODEL INSTALLATION	43
3.	PRESSURE INSTRUMENTATION LOCATION	44
4.	PRESSURE INSTRUMENTATION SYSTEM SCHEMATIC	45
5.	INSTRUMENTATION ARRANGEMENT - #1 CONTAINER	46
6.	INSTRUMENTATION ARRANGEMENT - #2 CONTAINER	47
7.	SHOCK WAVE SHADOWGRAPH (MACH 1.475)	48
8a.	MEASUREMENT UNCERTAINTIES - PROBE PRESSURE COEFFICIENTS	49
b.	MEASUREMENT UNCERTAINTIES - TOTAL PRESSURE COEFFICIENTS	50

INDEX OF DATA FIGURES

	TITLE	SCHEDULE	PAGE
FIG. 1	AADS PROBE CALIBRATION - TEST SERIES 4	A	1-132
FIG. 2	AADS PROBE CALIBRATION - TEST SERIES 4 - MACH EFFECTS	B	133-160

PLOTTED COEFFICIENT SCHEDULES:

SCHEDULE A

CPU VS ALPHA  
 CPB VS ALPHA  
 CPL VS ALPHA  
 CPR VS ALPHA  
 CPM VS ALPHA  
 CPTD VS ALPHA  
 CPAQ VS ALPHA  
 CPALPH VS ALPHA  
 DPACAL VS ALPHA  
 CPBQ VS ALPHA  
 CPBETA VS ALPHA  
 DPBCAL VS ALPHA

CPU VS MACH  
 CPB VS MACH  
 CPL VS MACH  
 CPR VS MACH  
 CPM VS MACH  
 CPTD VS ALPHA  
 CPAQ VS MACH  
 CPALPH VS MACH  
 DPACAL VS MACH  
 CPBQ VS MACH  
 CPBETA VS MACH  
 DPBCAL VS MACH

## INTRODUCTION

The present uncertainties in certain post-flight aerodynamic analyses are due largely to uncertainties in angles of attack and sideslip information obtained from the Ascent Air Data System during flight. Of the elements used to compute these uncertainties, the largest contributor is the probe data from an earlier wind tunnel test (IA-132). The objective of the present test was to obtain a more accurate calibration of the AADS probe in order to reduce the existing uncertainties in the system.

A nose probe attached to a 0.07-scale External Tank Forebody model was tested at angles of attack of -8 to +4 degrees and sideslip angles of -4 to +4 degrees. Following the acquisition of data to determine the tunnel flow angularities and installation misalignment/asymmetries, probe calibration data was obtained at eleven discrete Mach numbers from 0.6 to 1.55 with a constant Reynolds Number of 2.5 million per foot.

The focus on accuracy which prevailed during both the preparation and the conduct of the test resulted in high quality data which showed remarkable repeatability. Current analyses show differential pressure coefficient uncertainties below 0.0015 and pointing accuracies translating into alpha/beta deviations of less than 0.052 degree.

## NOMENCLATURE

<u>Symbol</u>	<u>Mnemonic</u>	<u>Description</u>
$C_{P_a}$	CPALPH	Probe pitch differential pressure coefficient normalized to $P_{TT}$
$C_{P_{aQ}}$	CPAQ	Probe pitch differential pressure coefficient normalized to Q
$C_{P_s}$	CPBETA	Probe yaw differential pressure coefficient normalized to $P_{TT}$
$C_{P_{sQ}}$	CPBQ	Probe yaw differential pressure coefficient normalized to Q
$C_{P_M}$	CPM	Mach parameter pressure coefficient normalized to $P_{TT}$
$C_{P_{TT}}$	CPTD	Coefficient of total pressure drop across the shock, normalized to $P_{TT}$
$C_p$	CPX	Gauge/absolute pressure coefficient
DPA1	DPA1	Redundant probe differential pressure in pitch, psid
DPA2	DPA2	Redundant probe differential pressure in pitch, psid
DPA	DPA	Probe differential pressure in pitch (average of DPA1 and DPA2), psid
$\Delta P_a$	DPACAL	Probe pitch differential pressure calculated from absolute measurements, psia
DPB1	DPB1	Redundant probe differential pressure in yaw, psid
DPB2	DPB2	Redundant probe differential pressure in yaw, psid
DPB	DPB	Probe differential pressure in yaw (average of DPB1 and DPB2), psid
$\Delta P_s$	DPBCAL	Probe yaw differential pressure calculated from absolute measurements, psia
$F_x$	FA	Axial force, lb

## NOMENCLATURE

<u>Symbol</u>	<u>Mnemonic</u>	<u>Description</u>
$F_y$	FY	Side force, lb
$F_n$	FN	Normal force, lb
M	MACH	Mach number
MPROBE	MPROBE	Probe Mach number
$M_x$	MX	Rolling moment, in-lb
$M_y$	MY	Pitching moment, in-lb
$M_z$	MZ	Yawing moment, in-lb
$P_{ATM}$	PATM	Atmospheric reference pressure, psfa
$P_U$	PU	Probe upper port static pressure, psia
$P_B$	PB	Probe bottom port static pressure, psia
$P_R$	PR	Probe right port static pressure, psia
$P_L$	PL	Probe left port static pressure, psia
$P_c$	PC	Plenum chamber static pressure, psfa
$P_{C_i}$	PC1,...	Cone surface static pressure, psia (i=1 to 12)
$P_{O_i}$	PO1,...	Ogive surface static pressure, psia (i=1 to 4)
$P_{REF}$	PREF	Reference pressure
$P_T$	PT	Freestream total pressure, psfa
$P_{TT}$	PTTF	Probe total pressure, psfa
$P_{TT2}$	PT2F	Isentropic flow pressure behind normal shock, psfa
$P_X$	PX	Static gauge pressure measurement, psia

## NOMENCLATURE

<u>Symbol</u>	<u>Mnemonic</u>	<u>Description</u>
$P_\infty$	P	Freestream static pressure, psfa
$\Delta P_\alpha$	DPA	Probe differential pressure in pitch, psid
$\Delta P_\gamma$	DPB	Probe differential pressure in yaw, psid
q	Q(PSF)	Freestream dynamic pressure, psfa
Re	RN/L	Freestream Reynolds Number 1/ft
SH	SH	Freestream Specific Humidity, lb/lb
T	T	Static temperature, deg Rankine
TT	TT	Freestream stagnation temperature, deg F
$X_T$	XT	External Tank longitudinal station, in
$\alpha$	ALPHA	Model angle of attack, degree
$\alpha_{FA}$	AFA	Flow angle correction for angle of attack, degree
$\alpha_i, \theta_i$	ALPHI	Sting pitch angle, degree
$\beta$	BETA	Model sideslip angle, degree
$\phi_i$	PHI	Sting roll angle, degree
$\psi_{FA}$	YFA	Flow angle correction for yaw angle, degree

## CONFIGURATIONS INVESTIGATED

The model used for this test was a 0.07-scale simulation of the External Tank Forebody designated Model 68-T. The ET lines are duplicated from the nose to station  $X_T = 819.63$  with the ogive section extending from the nose cone to  $X_T = 760.35$ . Between these two stations, the model is a plain cylinder. Aft of station 819.63, the cylindrical cross-section tapers slightly to  $X_T = 1118.56$ . A 26-inch tangent ogive fairing was added aft of station 1119.67 to minimize the turbulence at the aft end of the model. The model lines are shown in Figures 1a through 1d.

The  $\text{GO}_2$  vent line and the electrical tray are simulated from the cable fairing at the cone/ogive interface to the cylindrical section at  $X_T = 760.35$ . These protuberances together with their support and the cable fairing are removable for testing "without fairing".

The AADS probe consists of a total pressure (pitot) port at the tip of the spike and four static pressure ports oriented 90 degrees apart, all located on the 30-degree conical surface of the spike.

A new probe tip with 0.007-inch nominal diameter static pressure ports was fabricated and affixed to the existing LA probe for this test; the pitot port was kept at 0.010 inch. The SCHMIEDE probe (0.010-inch ports) which had been used in the previous test was held as a back-up. Some key test probe measurements are shown in Table III. The position reference for the probe is the attach pin-hole located at the 180-degree radial.

The prime attitude reference for the model is the balance sleeve. Because this sleeve is not easily accessible when the model is assembled on the support sting/balance, provisions are made to mount four removable leveling plates at right angles to each other on the model to serve as external references for alignment purposes.

## INSTRUMENTATION

The model angles of attack and sideslip were provided by a sector-mounted mechanism generating equivalent pitch/roll angle combinations which were appropriately corrected for structural deflections and misalignments.

A secondary source of attitude measurements was supplied by two Shaevitz high-accuracy inclinometers located at the forward end of the balance sleeve inside the model. One was placed in a zero-degree position for pitch angle measurements at zero roll angle, the other in a 90-degree position for yaw angles at  $\alpha = 0$ .

Force and moment data were obtained from the four-inch TASK six-component balance on which the model was mounted. The moment reference center was located 29.97 inches aft of the probe tip at  $X_T = 755.375$ . These data were used to compute the sting/model aero load deflections which were fed back to the support control system to adjust the sector angles.

The model was instrumented to measure a total of 25 pressures: one total (pitot) pressure, four differential and 20 static gauge pressures. The pressure measuring instruments were housed in temperature controlled containers located inside the model.

1. The pitot pressure port was connected to a high-precision SETRA transducer. A blocking valve was installed in the pressure line to the transducer, allowing the application of the reference pressure to both sides of the SETRA (see Figure 4), thus providing the capability for on-line re-zeroing of the SETRA and/or the monitoring of zero shifts.
2. Dual measurements of the "Bottom-minus-Upper" and "Right-minus-Left" differential pressures on the probe were effected by an Electronically Scanned Pressure module (ESP-16BP) containing differential transducers. The average of the respective dual measurements was used to calculate the relevant coefficients. In addition, each of the four probe ports was connected to an ESP-48 unit to measure the individual gauge pressures.

3. The 39-degree cone was instrumented with twelve surface pressure taps distributed around the cone in four rows of three taps aligned with the ports on the probe. Four additional pressure taps, in line with those on the cone, were located on the ogive surface. Each of these taps was connected to two gauge pressure transducers on the 48-port ESP unit. However, only one of the two pressure measurements was used in the data reduction. Both ESP modules were capped with 0.063-inch O.D. pressure tubes.

The location of the pressure taps is depicted in Figure 3 and their coordinates are tabulated in Table IV. The ESP orifice assignments which also identify the pressure and coefficient denominations in the final data package, are listed in Table V.

4. The reference pressure system incorporated a tracking controller to set the reference pressure relative to tunnel total or plenum pressure. At each Mach number, the reference pressure was adjusted to maintain the pitot 15-psid SETRA operating below 1/4 full-scale and the ESP's within  $\pm 2.5$  psid to take advantage of the higher accuracies obtainable in the lower pressure ranges. In addition, a blocking valve, downstream of the tracking controller, was used to keep the reference pressure constant during the data acquisition process. The reference itself was measured by a highly accurate SONIX pressure transducer with a redundant measurement provided by another SETRA unit.
5. A control "verification" pressure was applied to all unused ports on the ESP modules to keep those transducers from overranging.

As with the pointing system, the entire pressure measuring system was designed to maximize accuracy, including the special selection of the best instruments among the many that were calibrated prior to the test. A schematic of the pressure instrumentation system is shown in Figure 4.

To eliminate the effect of temperature changes on the sensitivity of the pressure measuring instruments, particularly the ESP's, two remote controllers were employed to maintain the temperature in the instrumentation containers at constant values. The smaller container (#1) was held at 110 degrees F and #2 container at 100 degrees F throughout the test while the model internal temperature ranged from 84 to 93 degrees F.

One set of two thermocouples was installed in each container, next to the ESP modules. One iron-constantan instrument was used as a feedback to the remote heater controller unit, the other (copper-constantan) to monitor and record the module temperature. One additional thermocouple was installed in the model cavity to monitor and record its internal temperature.

Shadowgraph video and still photographs showing the flow patterns near the spike were taken at test conditions  $\geq$  Mach 1.40. These showed the bow shock attaching to the probe near Mach 1.48. A shadowgraph picture taken at Mach 1.475 is shown in Figure 7.

## TEST FACILITY DESCRIPTION

The AEDC 16-foot Transonic wind tunnel is a variable density, continuous flow tunnel capable of being operated at Mach numbers from 0.6 to 1.6 and stagnation pressures of 120 to 4,000 psfa. The maximum attainable Mach number can vary slightly depending on the tunnel pressure ratio requirements for a particular installation and on ambient atmospheric conditions. The maximum stagnation pressure attainable for a given Mach number is a function of the electrical power available. The tunnel stagnation temperature can be varied from approximately 60 to 160 degrees Fahrenheit.

The 16 feet square by 40 feet long test section is enclosed by 60-degree inclined-hole perforated walls of six percent porosity to effect a measure of boundary layer control.

The tunnel employs SONIX transducers to effect dual measurements of the total pressure and of the plenum chamber static pressure. Atmospheric pressure is measured by a RUSKA transducer.

## TEST PROCEDURES

### Installation

The model was mounted on a balance attached to a 7-inch diameter sting in the High-Angle Automated Sting (HAAS) Cart. The rather large sting was selected to provide high support system rigidity to minimize model oscillations. The probe tip was located near the center of rotation of the sector, reducing the total linear displacement to approximately six inches from the tunnel centerline at maximum deflection. A sketch of the installation is shown in Figure 2.

The 48-port ESP unit was placed in the #1 instrumentation container and the ESP-16BP module was positioned in the #2 container together with the pitot pressure measuring SETRA transducer and its control valve (see Figures 5 and 6). The original soft isolation mounts were removed from the container frames and the ESP units were placed on thin plastic foam pads attached to support brackets which were hard-mounted to the inner frames.

### Calibrations and Pretest Checks

#### 1. Prior to installation

The output of the balance gauges were calibrated in the lab by AEDC.

A number of pressure transducers were calibrated using high precision equipment referable to an NBS standard. The most accurate instruments were selected for installation in the model and the plenum chamber.

#### 2. In-Cart

The individual pressure lines were leak-checked and the thermocouples were tested for continuity and response.

The relative alignment of the external leveling plates was checked against the outer balance sleeve using a digital inclinometer (DINC). The angles measured were within the 0.05 degree accuracy requirement.

The Shaevitz instruments installed in the model were calibrated using the sector angles as reference. Also, the sector angles were checked against the top and RHS leveling plates.

A balance load test was performed and the sting/model structural deflections under load were calibrated to obtain the balance constants.

The instrumentation was connected to a computer and a tunnel emulation test was carried out to check all instrumentation throughputs, the data reduction program, and the data printouts.

### 3. In-Tunnel

Check-loading of the balance through the data acquisition system was performed and the sting/model deflections checked out.

A leak check and a qualitative "end-to-end" checkout of the pressure transducers through the data system system were carried out.

The sector angles and the Shaevitz outputs were verified.

#### Test Conditions

The test was conducted at Mach numbers ranging from 0.6 to 1.55 at total pressures of 1198 to 2040 psfa. The stagnation temperature was held constant at 100 degrees F throughout. The test conditions are listed in Table I.

#### Test Procedure

Two model configurations "without fairing" and "with fairing" were tested. All protuberances were removed and recesses filled in to test "without fairing".

Pressure data were acquired in five distinct test series, each of which is described by its specific purpose:

TEST SERIES

1. Flow Angularity and Model Asymmetry
2. Port Misorientation Effects
3. Fairing-off Data Base
4. Probe Calibration
5. Repeat Runs

A secondary purpose of Test Series 1 was to evaluate a possible requirement for additional test Mach numbers.

The model was configured "without fairing" for the first three series. The test parameters are shown in the Run Schedule (Table II). A grid map of the angles tested in each series is appended to the Run Schedule in the same table.

Before acquiring any data, a "dust blow" run was made to determine the amount of particle contamination in the airstream. No "hits" were registered on the contamination disk during the half-hour run at Mach 0.6.

The pitch-pause mode of operation was used with sufficient time allowed between data points ( $\sim 10$  seconds) for the model pressures to stabilize. Yaw angles were obtained from model pitch-roll angle combinations. The required pitch and roll angles were iterated to include the sting-balance angular deflection corrections in order to produce settings equivalent to the nominal angles of attack and sideslip angles within a tolerance of  $\pm 0.05$  degrees. After the desired condition and attitude were achieved, all tolerances were checked and data acquired. If the checks signaled an out-of-tolerance condition, the model instrumentation was recalibrated/rezeroed on-line before proceeding.

All negative angles of attack were produced by inverting the model and pitching the nose up above the centerline of the tunnel, in effect keeping the probe in the same section of the tunnel throughout the test.

## DATA REDUCTION

Standard AEDC methods and equations were used to compute all tunnel conditions. All local static pressures were reduced to the standard coefficient form:

$$c_{p_x} = \frac{p_x * 144 + p_{ref} - p_\infty}{q}$$

The probe pressure differentials were reduced as follows:

$$c_{p_\alpha} = \frac{\Delta p_\alpha}{p_{tt}}$$

$$c_{p_{\alpha q}} = \frac{\Delta p_\alpha}{q}$$

$$c_{p_\beta} = \frac{\Delta p_\beta}{p_{tt}}$$

$$c_{p_{\beta q}} = \frac{\Delta p_\beta}{q}$$

$$\text{where } \Delta p_\alpha = p_\beta - p_u$$

$$\text{and } \Delta p_\beta = p_r - p_l$$

These values were calculated for the gauge pressure differences as well as for the differential transducer outputs. Similar pressure difference coefficients were generated for the cone and ogive pressures.

The following ratios were also calculated.

$$c_{p_m} = \frac{p_{tt}}{p_\infty}$$

$$c_{p_t} = \frac{p_{tt} - p_{t2}}{p_{tt}}$$

$$\text{where } p_{t2} = \left( \frac{6M^2}{M^2 + 5} \right)^{3.5} \left( \frac{6}{7M^2 - 1} \right)^{2.5} * p_t$$

### Uncertainties

Combinations of systematic and random errors in the basic wind tunnel parameters were estimated from the calibration and from the repeatability of the measurements during tunnel calibrations by the facility. Uncertainties of the instrumentation systems were estimated from repeat calibrations against secondary standards traceable to National Institute of Standards & Technology equipment.

The wind tunnel parameter uncertainties were first calculated through perturbation of the independent variables  $P_T$  and  $P_C$ , including error estimates related to the Mach number calibrations. The results were then combined with the uncertainties in the instrumentation systems, using the Taylor series method of error propagation to determine the uncertainties of the pressure coefficients and pressure ratios.

The uncertainties for the coefficients shown in Figure 8 were obtained for the maximum/minimum value of the respective coefficients at each Mach number during the probe calibration phase of the test (Test Series 4).

## REMARKS

1. Initially, the following operating tolerances were set for the instrumentation:

Mach Number	$\pm 0.003$
$P_T$ (Sonix)	$\pm 3$ psf
ESPs	0.3 - 0.5 psf
$P_{TT}$ (Setra)	0.08 psf

Early in the test it became obvious that the last two tolerances were much too tight. The ESPs were therefore relaxed to 0.3 - 0.8 psf and the pitot measurement SETRA to 0.12 psf.  $P_T$  and Mach number were generally held well within their tolerance levels.

2. The Schaevitz instruments performed their function very well in the pretest phase and early in the test. However, their performance soon deteriorated and no action was taken to repair or replace these back-up instruments. The data values of ALPSH and BETASH should be disregarded.
3. During the first Test Series, the rated axial load on the balance was exceeded at Mach 1.1 ( $q = 705$  psf), and the Reynolds Number was lowered to 3.0 E06/ft. The axial force component due to the model weight caused the balance limit to be exceeded again at  $\alpha = +4$  degrees at Mach 1.25. Therefore,  $\alpha$  was limited to -8 to +4 degrees for runs 1159, 1161-1163, after which the Reynolds Number was lowered to a constant 2.5 E06/ft for the remainder of the test.
4. A comparison of the data from runs 1159-1163 ( $Re = 3.0$  E06) with runs 1165-1169 ( $Re = 2.5$  E06) at the same Mach number showed no discernible difference between the two sets. Another data comparison between Reynolds Number 3.9 E06 (runs 1118-1121) and 2.5 E06 (runs 1221-1224) yielded similar results. Therefore, the test runs planned for the evaluation of Reynolds number effect were eliminated.

5. Following Test Series 1, Mach numbers 1.475 and 1.525 were added to the nine baseline Mach numbers.
6. The asymmetry of the alpha/beta matrix in Test Series 4 is the result of a compromise from budgeted Air-On Hours (AOH) consideration. Since there was insufficient time to complete the original test matrix, the angles of attack -8.5, -7.5, +1.5, +2.5 degrees and sideslip angles  $\pm$ 3.5, and  $\pm$ 4.5 degrees were eliminated. Further the one quarter degree grid was restricted to an alpha = -4  $\pm$ 1 degrees and beta =  $\pm$ 1 degree envelope, and tested at Mach 1.25 only.

The net result was the elimination of some 1930 data points equivalent to more than 6-1/2 AOH. The consensus of opinion was that the resulting reduced matrix would still provide a sufficient number of data points to generate the required probe calibration functions within the stipulated accuracy.

7. For Test Series 2 through 5, the flow angularity corrections are included with other corrections in the terms Alpha (Sting + Deflection) and Beta (Sting + Deflection) referred to as ALPSPD and BETASPD, respectively, in the data tabulations. Model and sting asymmetries (misalignments) derived from Test Series 1 are added separately to those terms to yield the ALPSPDC and BETASPDC values. Therefore, flow angularity cannot be removed directly from the ALPSPD and BETASPD terms. Asymmetries, however, can be subtracted from ALPSPDC and BETASPDC. ALPSPDC and BETASPDC are labeled ALPHA and BETA, respectively, in the plotted and tabulated data of this report.

8. A correction was applied to certain data to compensate for condensation in the tunnel free stream. The following corrections based on the specific humidity (SH), apply only to Mach number  $\geq 1.475$  and to the corresponding values of total pressure ( $P_T$ ), and dynamic pressure ( $Q$ ). The values of CPAQ, CPBQ, and  $P_{T2}$  have been modified to reflect the corrected wind tunnel parameters.

$$\frac{M_{corr}}{M_{ind}} = (3.02365 - 1436.80 \cdot SH) - (2.6184 - 1867.65 \cdot SH) \cdot M_{ind} + (0.848 - 609.128 \cdot SH) \cdot M_{ind}^2$$

$$\frac{P_T_{corr}}{P_T_{ind}} = (4.90395 - 2820.58 \cdot SH) - (5.0448 - 3670.70 \cdot SH) \cdot M_{ind} + (1.632 - 1199.16 \cdot SH) \cdot M_{ind}^2$$

$$Q_{corr} = 0.7 \cdot P_\infty \cdot M_{corr}^2$$

$$P_{T2corr} = \left( \frac{6 \cdot M_{corr}^2}{M_{corr}^2 + 5} \right)^{3.5} \left( \frac{6}{7 \cdot M_{corr}^2 - 1} \right)^{2.5} * P_T_{corr}$$

## **REFERENCES**

1. STS88-0955, "Pretest Information for the Space Shuttle Ascent Air Data System Calibration Test IA-310 in the AEDC 16-foot Transonic Wind Tunnel Model 68-T," by J.G.R. Collette, dated November 1988.
2. DMS-DR-2449, NASA-CR 160,497, "Results of Shuttle Transportation System Ascent Air Data System Calibration Test Using the 0.07-Scale External Oxygen Hydrogen Tank Forebody Model (68-T) in the AEDC 16-foot Transonic Wind Tunnel (IA132)," by R.R. Burrows and W.R. Carlson, dated January 1981.

TABLE I - TEST CONDITIONS

MACH NO.	TT (deg F)	PT (psfa)	P (psfa)	Q (psfa)	Re (E06/ft)
<b>TEST SERIES 1</b>					
0.60	100	2040	1599	404	3.2
0.80		2018	1323	593	3.7
0.90		1984	1172	665	3.9
0.92		1971	1140	676	
0.95		1948	1089	689	
0.98		1920	1038	698	↓
1.05		1842	917	708	3.8
1.10		1447	678	574	3.0
1.15		1440	633	586	
1.25		1438	555	607	↓
		1198	462	506	2.5
1.30		1202	434	513	
1.35		1207	407	519	
1.40		1216	382	524	
1.45		1226	359	528	
1.475		1232	348	530	
1.50		1239	338	532	
1.525		1246	327	533	
1.55		1254	318	534	↓
<b>TEST SERIES 2-5</b>					
0.60		1597	1252	316	2.5
0.80		1341	880	394	
0.90		1273	753	427	
1.10		1206	565	479	
1.25		1198	462	506	
1.40		1216	382	524	
1.45		1226	359	528	
1.475		1232	348	530	
1.50		1239	338	532	
1.525		1246	327	533	
1.55		1254	318	534	↓

TABLE II – AADS PROBE CALIBRATION TEST (IA310) RUN SCHEDULE  
TEST SERIES 1

1 of 13

TEST: IA310 (AEDC 16TF - 783)		DATA SET/RUN NUMBER COLLIMATION SUMMARY										DATE: SEPT. 1989	
DATA SET IDENTIFIER	CONFIGURATION	SCHED.	PARAMETERS	0.6	0.8	0.9	0.92	0.95	0.98	1.05	1.10	1.15	1.25
		alpha	beta	PHI									
RCM001	FLOW ANGULARITIES &	A	0	0									1147*
RCM002	MODEL/STRING ASYMM. &	A	0	0									1148
RCM003	MISALIGNMENT	A	0	0									1149
RCM004	(FAIRING OFF)	A	0	0									T
RCM005		A	0	180									B
RCM006		0	D	90									S
RCM007		0	D	-90									T
RCM008		F	0	0									R
RCM009		G	0	180									U
RCM010		0	E	90									N
RCM011		0	E	-90									M
RCM012		0	E	-90									B
													B
													R
													S

alpha or beta  
SCHEDULES  
\* INCOMPLETE DATA

A: ALPHA = -8 TO +8 DEG. IN 1 DEG. INCREM.  
F: ALPHA = -4, 0 DEG. G: ALPHA = 0,+4 DEG.  
E: BETA = -2,+2 DEG.

TABLE II - AADS PROBE CALIBRATION TEST (IA310) RUN SCHEDULE  
TEST SERIES 1 CONT'D.

alpha or beta

A: ALPHA = -8 TO +8 DEG. IN 1 DEG. INCREM.  
 B: AL PHA = -4 TO 0 DEG  
 C: AL PHA = 0 TO +4 DEG  
 D: BETA = -4 TO +4 DEG. IN 1 DEG. INCREM.  
 E: BETA = -2 TO +2 DEG

## TEST SERIES 1




TABLE II – AADS PROBE CALIBRATION TEST (IA310) RUN SCHEDULE  
TEST SERIES 2

alpha or beta  
SCHEDULES

**B: PHI = -2 TO +2 DEG. IN 0.25 DEG INCREM.**

## TEST SERIES 2





TABLE II – AADS PROBE CALIBRATION TEST (IA310) RUN SCHEDULE  
TEST SERIES 3

TEST: IA310 (AEDC 16TF - 783)		DATA SET/RUN NUMBER COLLATION SUMMARY										DATE: SEPT. 1989				
DATA SET IDENTIFIER	CONFIGURATION	SCHED.		PARAMETERS		MACH NUMBERS										
		alpha	beta	PHI		0.60	0.80	0.90	1.10	1.25	1.40	1.45	1.475	1.50	1.525	1.55
RCM030	FAIRING – OFF DATABASE	C	-4	180		1351	1341	1329	1320	1365	1376	1388	1433	1400	1421	1410*
RCM031		C	-4	180												1423
RCM032		C	-3	180		1352	1342	1330	1321	1366	1377	1389	1434	1401	1424	1412
RCM033		C	-2	180		1353	1343	1331	1322	1367	1378	1390	1435	1402	1425	1413
RCM034		C	-1	180		1354	1344	1332	1323	1368	1380	1391	1436	1403	1426	1414
RCM035		C	0	180		1355	1345	1333*	1324	1370	1381	1392	1437	1404	1427	1416
RCM036		C	0	180					1335							T
RCM037		C	+1	180		1357	1346	1336	1325	1371	1382	1394	1438	1405	1428	1417
RCM038		C	+2	180		1358	1347	1337	1326	1372	1383	1395	1439	1406	1429	1418
RCM039		C	+3	180		1359	1348	1338	1327	1373	1384	1397	1440	1407	1430	1420
RCM040		C	+4	180		1360	1349	1339	1328	1374	1385	1398	1441	1408	1431	1419
																N
																U
																M
																B
																R
																S

alpha or beta  
SCHEDULES  
\* INCOMPLETE DATA

C: ALPHA = -8 to +2 DEG. in 1 DEG. INCREMENTS

## TEST SERIES 3




TABLE II – AADS PROBE CALIBRATION TEST (IA310) RUN SCHEDULE  
TEST SERIES 4

TEST: IA310 (AEDC 16TF - 783)		DATA SET/RUN NUMBER COLLATION SUMMARY				DATE: SEPT. 1989	
DATA SET	IDENTIFIER	CONFIGURATION	SCHD.	PARAMETERS	MACHIN NUMBERS		
			alpha <sup>b1a</sup>	beta <sup>b1a</sup>	PHI		
	RCM041	PROBE CALIBRATION	C	-4	180	0.60	0.80
			A1	-4	180	1670	1746
	RCM042					1659	1738
	RCM043		A	-3	180	1568	1458
	RCM044		A	-2.5	180	1491	1475
	RCM045		A	-2	180	1515	1531
	RCM046		A	-1.5	180	1492	1476
	RCM047		A	-1	180	1460	1493
	RCM048		A	-0.5	180	1477	1517
	RCM049		A	0	180	1461	1495
	RCM050		A	0.5	180	1478	1518
	RCM051		A	1	180	1462	1496
	RCM052		A	1.5	180	1463	1497
	RCM053		A	2	180	1480	1520
	RCM054		A	2.5	180	1464	1498
	RCM055		A1	3	180	1499	1484
	RCM056		A1	4	180	1465	1499
	RCM057		C	4	180	1466	1500
	RCM058		D	8	180	1485	1523
	RCM059		+2	D	180	1501	1486
						1521	1537
						1553	1637
						1635	1551
						1586	1635
						1602	1617
						1618	B
						1636	S
						1587	T
						1603	R
						1619	N
						1604	U
						1589	1620
						1605	1621
						1590	1606
						1640	1556
						1538	1554
						1638	1536
						1554	1497
						1591	1607
						1622	1592
						1642	1557
						1608	1623
						1623	1593
						1609	1624
						1593	1609
						1643	1558
						1540	1524
						1539	1467
						1523	1466
						1557	1466
						1537	1463
						1555	1465
						1639	1464
						1590	1464
						1621	1464
						1606	1464
						1591	1464
						1640	1464
						1556	1464
						1538	1465
						1554	1465
						1599	1466
						1605	1466
						1620	1467
						1621	1468
						1622	1469
						1623	1470
						1624	1471
						1625	1472
						1626	1473
						1627	1474
						1628	1475
						1629	1476
						1630	1477
						1631	1478
						1632	1479
						1633	1480
						1634	1481
						1635	1482
						1636	1483
						1637	1484
						1638	1485
						1639	1486
						1640	1487
						1641	1488
						1642	1489
						1643	1490
						1644	1491
						1645	1492
						1646	1493
						1647	1494
						1648	1495
						1649	1496
						1650	1497
						1651	1498
						1652	1499
						1653	1500
						1654	1501
						1655	1502
						1656	1503
						1657	1504
						1658	1505
						1659	1506
						1660	1507
						1661	1508
						1662	1509
						1663	1510
						1664	1511
						1665	1512
						1666	1513
						1667	1514
						1668	1515
						1669	1516
						1670	1517
						1671	1518
						1672	1519
						1673	1520
						1674	1521
						1675	1522
						1676	1523
						1677	1524
						1678	1525
						1679	1526
						1680	1527
						1681	1528
						1682	1529
						1683	1530
						1684	1531
						1685	1532
						1686	1533
						1687	1534
						1688	1535
						1689	1536
						1690	1537
						1691	1538
						1692	1539
						1693	1540
						1694	1541
						1695	1542
						1696	1543
						1697	1544
						1698	1545
						1699	1546
						1700	1547
						1701	1548
						1702	1549
						1703	1550
						1704	1551
						1705	1552
						1706	1553
						1707	1554
						1708	1555
						1709	1556
						1710	1557
						1711	1558
						1712	1559
						1713	1560
						1714	1561
						1715	1562
						1716	1563
						1717	1564
						1718	1565
						1719	1566
						1720	1567
						1721	1568
						1722	1569
						1723	1570
						1724	1571
						1725	1572
						1726	1573
						1727	1574
						1728	1575
						1729	1576
						1730	1577
						1731	1578
						1732	1579
						1733	1580
						1734	1581
						1735	1582
						1736	1583
						1737	1584
						1738	1585
						1739	1586
						1740	1587
						1741	1588
						1742	1589
						1743	1590
						1744	1591
						1745	1592
						1746	1593
						1747	1594
						1748	1595
						1749	1596
						1750	1597
						1751	1598
						1752	1599
						1753	1600
						1754	1601
						1755	1602
						1756	1603
						1757	1604
						1758	1605
						1759	1606
						1760	1607
						1761	1608
						1762	1609
						1763	1610
						1764	1611
						1765	1612
						1766	1613
						1767	1614
						1768	1615
						1769	1616
						1770	1617
						1771	1618
						1772	1619
						1773	1620
						1774	1621
						1775	1622
						1776	1623
						1777	1624
						1778	1625
						1779	1626
						1780	1627
						1781	1628
						1782	1629
						1783	1630
		</td					

TEST ((A310) BIN SCHED II E

TEST SERIES 4 (CONT'D.)


TEST: IA310 (AEDC 16TF-783)		DATA SET/RUN NUMBER/COLLATION SUMMARY												DATE: SEPT. 1989									
DATA SET IDENTIFIER	CONFIGURATION	SCHED.		PARAMETERS				MACH NUMBERS						T	B	S	T	U	N	M	B	R	S
		alpha	beta	phi	psi	theta	phi	psi	theta	0.60	0.80	0.90	1.10	1.25	1.40	1.45	1.475	1.50	1.525	1.55			
RCM060	PROBE CALIBRATION	X	-1	180														1729					
RCM061		X	-.75	180														1730					
RCM062		X	-.5	180														1731					
RCM063		X	-.25	180														1732					
RCM064		X	0	180														1733					
RCM065		X	.25	180														1734					
RCM066		X	.50	180														1735					
RCM067		X	.75	180														1736					
RCM068		X	1	180														1737					

SCHEDULLES

X; ALPHA = -5 TO -3 DEG. IN 0.25 DEG. INCREMENTS

1A319WK3

## TEST SERIES 4




TEST: A310 (AEDC 16TF-783)      DATA SET/BUN NUMBER COLLATION SUMMARY      DATE: SEPT. 1989

## **alpha or beta SCHEDULES**

C: ALPHA = -8 TO +2 DEG. IN 1 DEG. INCREMENTS  
D: BETA = -4 TO +4 DEG. IN 1 DEG. INCREMENTS

## TEST SERIES 5



**TABLE II CONCLUDED  
IA310 (AEDC 16TF-783)  
COEFFICIENT SCHEDULES**

TABLE III PROBE DIMENSIONAL CHECK

PRESSURE PORT	RADIAL (deg)	DISTANCE TO TIP	ORIENTATION (deg)	CIRCUMFERENTIAL DISPLACEMENT
BOTTOM	000	.0820( $\pm .0004$ ) IN	357 46.2°( $\pm 10.8'$ )	-.0019 IN
UPPER	180	.0820( $\pm .0001$ ) IN	180 15.9°( $\pm 12.4'$ )	.0002 IN
RIGHT	090	.0819( $\pm .0003$ ) IN	090 34.5°( $\pm 7.0'$ )	.0005 IN
LEFT	270	.0819( $\pm .0001$ ) IN	268 26.3°( $\pm 8.9'$ )	-.0013 IN

TABLE IV - MODEL 68-T PRESSURE TAP LOCATIONS

TAP ID	RADIAL (DEG)	$X_T$ (IN)		LOCATION
		FULL SCALE	MODEL SCALE	
PTT	TIP	327.22	22.905	AADS PROBE
PB	0	328.37	22.986	
PU	180			
PR	90			
PL	270			
PC1	0	346.00	24.220	NOSE CONE
PC2		356.00	24.920	
PC3		366.00	25.620	
PC4	180	346.00	24.220	
PC5		356.00	24.920	
PC6		366.00	25.620	
PC7	90	346.00	24.220	
PC8		356.00	24.920	
PC9		366.00	25.620	
PC10	270	346.00	24.220	
PC11		356.00	24.920	
PC12		366.00	25.620	
PO1	0	430.00	30.10	OGIVE SURFACE
PO2	180			
PO3	90			
PO4	270			

TABLE V – ESP ORIFICE ASSIGNMENT

ESP-48 MODULE (+2.5 psid)

PORT	TAP ID	PORT	TAP ID
		2.5	VERIF P
01	VERIF P	26	
02	PU	27	
03	PB	28	
04	VERIF P	29	
05	PL	30	
06	PC 1	31	↓
07	PC 2	32	VERIF P
08	PC 3	33	PC 1
09	PC 4	34	PC 2
10	PC 5	35	PC 3
11	PC 6	36	PC 4
12	PC 7	37	PC 5
13	PC 8	38	PC 6
14	PC 9	39	PC 7
15	PC10	40	PC 8
16	PC11	41	PC 9
17	PC12	42	PC10
18	PO 1	43	PC11
19	PO 2	44	PC12
20	PO 3	45	PO 1
21	PO 4	46	PO 2
22	VERIF P	47	PO 3
23	VERIF P	48	PO 4
24	PR		

ESP-16BP MODULE (+2.5 psid)

PORT	TAP ID	PORT	TAP ID
		01 P	VERIF P
		02 P	
		03 P	↓
		04 P	PB
		05 P	VERIF P
		06 P	PB
		07 P	PR
		08 P	PR




Figure 1a. Model Profile Lines




Figure 1b. Model Front View





Figure 1c. AADS Probe and Cone



ORIGINAL PAGE IS  
OF POOR QUALITY

Figure 1d. AADS Probe & Cone




Figure 2. Model Installation




Figure 3. Pressure Instrumentation Location





Figure 4. Pressure Instrumentation System Schematic




Figure 5. Instrumentation Arrangement - #1 Container

ORIGINAL PAGE  
BLACK AND WHITE PHOTOGRAPH

Figure 6. Instrumentation Arrangement - #2 Container



ORIGINAL PAGE  
BLACK AND WHITE - HOTOGRAPH



DS 7150 1277 002 000

Figure 7. Shock Wave Shadowgraph (Mach 1.475)

ORIGINAL PAGE  
BLACK AND WHITE PHOTOGRAPH




Figure 8a. Measurement Uncertainties - Probe Pressure Coefficients

## **BASED ON MAXIMUM CPM CONDITIONS**




Figure 8b. Measurement Uncertainties - Total Pressure Coefficients

**APPENDIX**  
**TABULATED SOURCE DATA**



## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 421  
PRECEDING PAGE BLANK NOT FILMED

(TCM001) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1102/ 0	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	.000	PHI	=	.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPHI	CPME	CPMT	CPTD	
.599	.8 .006	-.01407	-.04533	-.33374	-.06710	-.00889	-.00179	.57160	1.24800	-.02102		
.599	.6 .998	-.01475	-.04507	-.29058	-.05820	-.00885	-.00177	.57864	1.25466	-.01595		
.600	.6 .001	-.01554	-.04481	-.24678	-.04929	-.00812	-.00162	.58428	1.26007	-.01192		
.599	.4 .998	-.01569	-.04448	-.20534	-.04083	-.00644	-.00128	.58907	1.26471	-.00802		
.599	.3 .995	-.01603	-.04418	-.16196	-.03208	-.00518	-.00103	.59277	1.26834	-.00493		
.600	.3 .002	-.01888	-.00436	-.11925	-.02363	-.00576	-.00114	.59568	1.27120	-.00323		
.600	.1 .999	-.01842	-.00401	-.07675	-.01517	-.00673	-.00133	.59770	1.27321	-.00145		
.600	.995	-.01803	-.00429	-.03607	-.03607	-.00713	-.00131	.59903	1.27454	-.00072		
.600	.009	-.01842	-.00338	-.00371	-.00073	-.00779	-.00154	.59950	1.27500	-.00019		
.600	.1 .003	-.01833	-.00307	.04504	.00890	-.00724	-.00143	.59962	1.27512	-.00036		
.600	.2 .001	-.01843	-.00275	.08702	.01722	-.00606	-.00120	.60001	1.27552	-.00036		
.600	.3 .011	-.02067	-.04197	.12947	.02563	-.00414	-.00082	.59967	1.27517	-.00065		
.600	.4 .005	-.01873	-.00210	.17308	.03422	-.00412	-.00081	.59908	1.27459	-.00070		
.600	.4 .999	-.02193	-.04125	.21416	.04241	-.00439	-.00087	.59814	1.27364	-.00167		
.600	.6 .003	-.02297	-.04084	.25661	.05094	-.00467	-.00093	.59598	1.27151	-.00350		
.600	.6 .998	-.02344	-.04046	.29912	.05939	-.00401	-.00080	.59210	1.26768	-.00588		
.600	.7 .996	-.02366	-.04012	.33954	.06767	-.00338	-.00067	.58781	1.26348	-.00935		
	GRADIENT	-.00043	.00104	.04174	.00827	.00019	.00004	.000080	.000079	.000054		

RUN NO. 1109/ 0 RN/L = 3.76 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1109/ 0	RN/L =	3.76	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	.000	PHI	=	.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPHI	CPME	CPMT	CPTD	
.800	-.8 .000	-.02254	-.00648	-.31962	-.09656	-.00791	-.00239	.77175	1.48275	-.02799		
.800	-.6 .987	-.02225	-.00604	-.27807	-.08343	-.00761	-.00228	.77866	1.49271	-.02104		
.800	-.5 .995	-.02207	-.00564	-.23780	-.07097	-.00635	-.00190	.78465	1.50146	-.01535		
.800	-.4 .981	-.02177	-.00523	-.19632	-.05833	-.00457	-.00136	.78954	1.50867	-.01060		
.800	-.3 .994	-.02133	-.00483	-.15499	-.04586	-.00358	-.00106	.79302	1.51385	-.00687		
.800	-.2 .997	-.02138	-.00446	-.11534	-.03401	-.00405	-.00119	.79590	1.51815	-.00374		
.800	-.1 .993	-.02072	-.00408	-.07437	-.02189	-.00484	-.00143	.79743	1.52043	-.00211		
.800	-.989	-.02070	-.00372	-.03479	-.01023	-.00579	-.00170	.79937	1.52339	-.00064		
.800	.014	-.02019	-.00337	-.00424	-.00125	-.00581	-.00171	.79930	1.52328	-.00043		
.800	1 .003	-.02001	-.00304	-.04388	-.01290	-.00453	-.00133	.79921	1.52315	-.00066		
.800	2 .006	-.02013	-.00269	-.08375	-.02463	-.00351	-.00103	.79961	1.52375	-.00044		
.800	3 .005	-.01995	-.00236	-.12478	-.03667	-.00218	-.00064	.79918	1.52310	-.00049		
.799	4 .004	-.01981	-.00204	-.16608	-.04876	-.00208	-.00061	.79835	1.52185	-.00054		
.800	5 .003	-.01962	-.00172	-.20590	-.06063	-.00192	-.00056	.79734	1.52033	-.00235		
.800	6 .002	-.01929	-.00142	-.24594	-.07262	-.00154	-.00045	.79597	1.51827	-.00429		
.800	7 .012	-.01903	-.00113	-.28690	-.08485	-.00084	-.00025	.79260	1.51322	-.00693		
.800	8 .001	-.01928	-.00078	-.32603	-.09691	-.00090	-.00027	.78888	1.50770	-.01116		
	GRADIENT	-.00022	.00035	.04009	.01183	.00022	.00006	.00089	.00133	.00095		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 422

(TCM001) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1118/ 0	RN/L =	3.89	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	.000	PHI	=	.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD		
.900	-8.002	-.02334	-.00657	-.30626	-.10572	-.00772	-.00266	.87196	1.64122	-.03011		
.900	-6.993	-.02291	-.00611	-.26674	-.09147	-.00733	-.00251	.87928	1.65404	-.02271		
.900	-5.994	-.02294	-.00571	-.22795	-.07769	-.00617	-.00210	.88524	1.66461	-.01632		
.900	-4.990	-.02223	-.00526	-.18867	-.06395	-.00448	-.00152	.88966	1.67252	-.01117		
.900	-3.991	-.02201	-.00486	-.14862	-.05018	-.00351	-.00118	.89357	1.67958	-.00705		
.900	-2.976	-.02194	-.00448	-.10969	-.03691	-.00397	-.00133	.89592	1.68385	-.00402		
.900	-1.994	-.02147	-.00410	-.07136	-.02399	-.00493	-.00166	.89805	1.68773	-.00243		
.900	- .999	-.02146	-.00374	-.03344	-.01122	-.00575	-.00193	.89901	1.68950	-.00086		
.900	.020	-.02124	-.00337	-.00420	.00141	-.00554	-.00186	.89919	1.68982	-.00065		
.900	1.003	-.02156	-.04262	-.04224	.01416	-.00417	-.00140	.89905	1.68957	-.00062		
.900	2.007	-.02072	-.00267	-.08112	.02721	-.00322	-.00108	.89915	1.68975	-.00069		
.900	3.011	-.02295	-.04186	-.11949	.04008	-.00234	-.00079	.89914	1.68973	-.00068		
.900	4.007	-.02329	-.04150	-.15880	.05326	-.00227	-.00076	.89916	1.68976	-.00071		
.899	5.006	-.02039	-.00166	.19722	.06621	-.00223	-.00075	.89759	1.68689	-.00200		
.899	6.007	-.01956	-.00141	.23596	.07933	-.00164	-.00055	.89536	1.68284	-.00400		
.900	7.002	-.02464	-.04036	.27453	.09266	-.00138	-.00047	.89304	1.67863	-.00715		
.900	8.008	-.02512	-.03996	.31217	.10587	-.00144	-.00049	.88939	1.67204	-.01157		
	GRADIENT	-.00006	-.00419	.03842	.01294	.00021	.00007	.000159	.000098	.00007		

	RUN NO.	1147/ 0	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	.000	PHI	=	.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD		
1.099	-7.994	-.02904	-.00735	-.27584	-.11290	-.00434	-.00177	1.0736	2.06610	-.03122		
1.100	-6.977	-.02928	-.00686	-.23993	-.09747	-.00406	-.00165	1.08129	2.08519	-.02296		
1.100	-5.998	-.03274	-.00671	-.20584	-.08309	-.00322	-.00130	1.08669	2.09883	-.01637		
1.100	-4.975	-.03061	-.04569	-.17066	-.06934	-.00193	-.00079	1.08080	2.08394	-.02326		
1.100	-3.975	-.03289	-.00558	-.13446	-.05376	-.00135	-.00054	1.09427	2.11813	-.00689		
	GRADIENT	-.00229	.04012	.03621	.01558	.00058	.00025	.01348	.03420	.01638		

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

IAA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

## PARAMETRIC DATA

RUN NO.	1159/ 0	RN/L =	2 . 99	GRADIENT INTERVAL =	- 5 . 00/	5 . 00	
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBEA	CPTD
- 7 . 997	- .01784	- .00584	- .28164	- .12435	- .00568	- .00251	- .03226
- 6 . 250	- .01234	- .04475	- .24536	- .10756	- .00544	- .00239	- .02476
- 5 . 985	- .01598	- .00503	- .20977	- .09134	- .00433	- .00188	- .01793
- 4 . 990	- .01355	- .00455	- .17459	- .07564	- .00291	- .00126	- .01272
- 3 . 978	- .01350	- .00431	- .13705	- .05908	- .00224	- .00097	- .00797
- 2 . 987	- .01482	- .04379	- .10138	- .04358	- .00269	- .00116	- .00480
- 1 . 250	- 1 . 988	- .01732	- .00397	- .06566	- .02816	- .00340	- .00283
- 1 . 250	- .985	- .01547	- .00365	- .02999	- .01285	- .00380	- .00172
- 1 . 250	- .029	- .01618	- .00338	- .00445	- .00191	- .00315	- .00111
- 1 . 250	1 . 019	- .01727	- .04269	.03998	.01711	- .00217	- .00063
- 1 . 250	2 . 017	- .01773	- .00277	.07512	.03215	- .00157	- .00066
- 1 . 251	3 . 012	- .02060	- .04198	.11020	.04721	- .00158	- .00120
- 1 . 250	3 . 971	- .01880	- .00212	.14543	.06233	- .00161	- .00195
GRADIENT	- .00068	- .00093	.03550	.01528	.00016	.00007	.00279

4 OCT 91

SYNTHETIC DATA

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 424  
( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1103/ 0	RN/L =	3.20	GRADIENT INTERVAL	= -5.00/ 5.00	BETA = .000 PHI = .000	CPTD
<b>MACH</b>			<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBE</b>
5.99	- 8.006	- .01388	- .04530	- .33340	- .06708	- .00880	- .00177	.57151 1.24793 -.02121
5.99	- 6.994	- .01911	- .00570	- .29077	- .05826	- .00839	- .00168	.57828 1.25432 -.01623
5.99	- 5.996	- .01920	- .00538	- .24774	- .04945	- .00743	- .00148	.58459 1.26036 -.01160
5.99	- 4.999	- .01897	- .00502	- .20539	- .04083	- .00585	- .00116	.58878 1.26443 -.00813
5.99	- 4.000	- .01855	- .00466	- .16252	- .03221	- .00447	- .00088	.59296 1.26852 -.00492
6.00	- 3.003	- .01851	- .00434	- .12001	- .02378	- .00510	- .00101	.59575 1.27128 -.00326
6.00	- 1.999	- .01741	- .04360	- .07660	- .01515	- .00633	- .00125	.59794 1.27345 -.00149
6.00	- 1.000	- .01850	- .00370	- .03593	- .00710	- .00644	- .00127	.59915 1.27465 -.00053
6.00	.014	- .01845	- .04298	- .00415	.00082	- .00727	- .00144	.59942 1.27493 -.00050
6.00	1.002	- .01931	- .04265	- .04509	.00892	- .00685	- .00136	.59988 1.27539 -.00035
6.01	2.001	- .01996	- .04232	- .08679	.01719	- .00567	- .00112	.60016 1.27567 -.00042
6.01	3.005	- .02072	- .04197	- .12981	.02571	- .00457	- .00091	.60004 1.27555 -.00054
6.01	4.010	- .02121	- .04162	- .17313	.03432	- .00418	- .00083	.59943 1.27494 -.00113
6.01	5.004	- .01821	- .00183	- .21378	.04237	- .00421	- .00084	.59826 1.27377 -.00181
6.00	6.003	- .02222	- .04091	- .25660	.05087	- .00390	- .00077	.59564 1.27116 -.00343
5.99	6.997	- .01829	- .00120	- .29921	.05931	- .00347	- .00069	.59201 1.26758 -.00557
6.00	7.997	- .02371	- .04012	- .33913	.06759	- .00311	- .00062	.58760 1.26328 -.00946
	GRADIENT	- .00029	- .00495	.04173	.00828	.00005	.00001	.00104 .00007
	RUN NO.	1111/ 0	RN/L =	3.76	GRADIENT INTERVAL	= -5.00/ 5.00	BETA = .000 PHI = .000	CPTD
<b>MACH</b>			<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBE</b>
.800	- 8.005	- .01600	- .04556	- .31922	- .09642	- .00642	- .00194	.77160 1.48253 -.02827
.800	- 6.986	- .02105	- .00590	- .27793	- .08342	- .00642	- .00193	.77833 1.49223 -.02140
.800	- 5.995	- .02079	- .00551	- .23791	- .07097	- .00542	- .00162	.78438 1.50107 -.01529
.800	- 5.003	- .02051	- .00513	- .19683	- .05846	- .00386	- .00115	.78911 1.50803 -.01071
.800	- 3.989	- .02060	- .00478	- .15488	- .04580	- .00311	- .00092	.79298 1.51380 -.00665
.800	- 2.997	- .02065	- .00443	- .11497	- .03391	- .00354	- .00104	.79615 1.51854 -.00375
.800	- 1.999	- .01879	- .04364	- .07454	- .02195	- .00463	- .00136	.79785 1.52109 -.00198
.800	- .989	- .01937	- .04331	- .03471	- .01021	- .00531	- .00156	.79926 1.52326 -.00075
.800	.025	- .01958	- .00337	- .00452	.00133	- .00548	- .00161	.79954 1.52365 -.00043
.799	1.008	- .01962	- .00304	- .04397	.01292	- .00480	- .00141	.79882 1.52255 -.00053
.799	2.007	- .01958	- .00271	- .08445	.02481	- .00345	- .00101	.79900 1.52283 -.00043
.800	3.005	- .01961	- .00238	- .12442	.03657	- .00264	- .00078	.79928 1.52326 -.00048
.800	4.020	- .02262	- .04153	- .16615	.04887	- .00257	- .00075	.79872 1.52241 -.00105
.800	5.003	- .01968	- .00171	- .20607	.06064	- .00245	- .00072	.79748 1.52055 -.00204
.799	6.018	- .02326	- .04082	- .24666	.07272	- .00239	- .00071	.79532 1.51729 -.00404
.799	7.002	- .01891	- .00115	- .28689	.08485	- .00198	- .00059	.79143 1.51148 -.00766
.800	7.995	- .02440	- .04005	- .32571	.09683	- .00174	- .00052	.78865 1.50735 -.01139
	GRADIENT	- .00011	- .03995	.03995	.01177	.00013	.00004	.00057 .00059

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 425

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( TCMOC2 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1148/ O	RN/L = 3.00	GRADIENT INTERVAL = -5.00/ 5.00	BETA = .000	PHI = .000	CPTD = .000
1.099	-8.010	-0.02222	.04640	.27641	-.11313	-.00440	-.00180	1.07327
1.100	-6.971	-.02928	-.00686	-.23959	-.09731	-.00413	-.00168	2.08159
1.100	-5.993	-.03189	-.00662	-.20578	-.08304	-.00330	-.00133	1.08646
1.100	-4.996	-.03368	-.00622	-.17117	-.06875	-.00206	-.00083	1.09094
1.100	-3.973	-.03108	-.00546	-.13455	-.05380	-.00139	-.00056	1.09406
1.100	-2.982	-.00271	-.04320	-.09941	-.03964	-.0043	-.00017	1.09668
1.100	-2.001	-.00703	-.00364	-.06414	-.02551	-.00185	-.00073	1.09833
1.100	-.979	-.02802	-.00383	-.02938	-.01167	-.00164	-.00065	1.09943
1.100	.003	-.01360	-.00339	-.00270	-.00107	-.00149	-.00059	1.09975
1.100	1.004	-.02436	-.00295	.03730	.01481	-.00080	-.00032	1.09993
1.099	2.015	-.01541	-.00286	.07196	.02858	.00003	.00001	1.09917
1.100	3.022	-.01094	-.00284	.10683	.04242	.00017	.00007	1.09950
1.099	4.009	-.02767	-.00148	.14239	.05657	-.00022	-.00009	1.09876
1.100	5.026	-.02871	-.00091	.17835	.07095	.00021	.00008	1.09831
1.100	6.005	-.02670	-.00665	.21258	.08473	.00086	.00034	1.09629
1.100	7.008	-.02251	-.00071	.24730	.09891	.00113	.00045	1.09382
1.099	8.009	-.02325	-.04020	.28017	.11252	.00132	.00053	1.08982
	GRADIENT	.00057	.00161	.03458	.01380	.00020	.00008	.00076

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( TCW003 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1108/ 0	RN/L =	3.20	GRADIENT INTERVAL	= -5.00/ 5.00	BETA	= .000	PHI	= .000
								CPAQ	CPALPH	CPBQ	CPBETA
.599	-8.006	-0.02013	-.00619	-.33301	-.06710	-.01036	-.00209	.57190	1.24828	-.02137	
.600	-6.993	-0.02011	-.00582	-.29032	-.05823	-.01034	-.00207	.57856	1.25459	-.01631	
.600	-5.996	-0.01999	-.00546	-.24789	-.04953	-.00874	-.00175	.58465	1.26043	-.01183	
.599	-5.004	-0.01990	-.00510	-.20609	-.04095	-.00733	-.00146	.58931	1.26495	-.00774	
.600	-3.995	-0.01952	-.00472	-.16170	-.03208	-.00621	-.00123	.59312	1.26868	-.00511	
.600	-2.997	-0.01729	-.00439	-.11933	-.02366	-.00588	-.00117	.59605	1.27158	-.00319	
.600	-2.004	-0.01902	-.00403	-.07723	-.01528	-.00655	-.00130	.59794	1.27345	-.00148	
.600	-1.000	-0.01907	-.00371	-.03631	-.00717	-.00681	-.00134	.59913	1.27463	-.00045	
.600	.009	-0.01892	-.00338	-.00365	-.00072	-.00790	-.00156	.59981	1.27532	-.00027	
.601	1.002	-0.01870	-.00306	-.04479	-.00887	-.00703	-.00139	.60005	1.27556	-.00054	
.601	2.001	-0.01889	-.00273	-.08654	-.01713	-.00564	-.00112	.60011	1.27562	-.00033	
.601	3.000	-0.01865	-.00244	-.12990	-.02571	-.00435	-.00086	.59995	1.27546	-.00045	
.601	4.005	-0.01880	-.00209	-.17297	-.03425	-.00404	-.00080	.59956	1.27506	-.00082	
.601	5.004	-0.01844	-.00181	-.21436	-.04250	-.00387	-.00077	.59833	1.27384	-.00185	
.601	6.008	-0.01799	-.00154	-.25648	-.05095	-.00346	-.00069	.59610	1.27162	-.00362	
.600	6.997	-0.01839	-.00119	-.29900	-.05946	-.00295	-.00059	.59255	1.26812	-.00598	
.600	8.002	-0.01829	-.00089	-.34030	-.06778	-.00209	-.00042	.58770	1.26338	-.00926	
	GRADIENT		.00001	.00230	.04158	.00824	.00025	.00005	.00071	.00046	
MACH	ALPHA	RUN NO.	1112/ 0	RN/L =	3.75	GRADIENT INTERVAL	= -5.00/ 5.00	BETA	= .000	PHI	= .000
								CPAQ	CPALPH	CPBQ	CPBETA
.800	-8.005	-0.02271	-.00650	-.31950	-.09653	-.00779	-.00235	.77105	1.48175	-.02845	
.800	-6.992	-0.02243	-.00607	-.27799	-.08433	-.00718	-.00216	.77885	1.49299	-.02105	
.800	-5.995	-0.02183	-.00562	-.23811	-.07104	-.00625	-.00186	.78448	1.50121	-.01533	
.800	-4.982	-0.01836	-.04468	-.19653	-.05836	-.00455	-.00135	.78959	1.50875	-.01034	
.800	-3.983	-0.02145	-.00483	-.15442	-.04566	-.00331	-.00098	.79290	1.51367	-.00670	
.799	-2.996	-0.02079	-.00444	-.11456	-.03377	-.00376	-.00111	.79538	1.51738	-.00400	
.800	-1.993	-0.02077	-.00408	-.07406	-.02179	-.00466	-.00137	.79781	1.52103	-.00181	
.800	-1.000	-0.02054	-.00372	-.03477	-.01023	-.00548	-.00161	.79895	1.52275	-.00115	
.800	0.15	-0.02049	-.00429	-.00419	-.00123	-.00551	-.00162	.79966	1.52383	-.00063	
.800	1.013	-0.02078	-.04263	-.04432	-.01303	-.00438	-.00129	.79904	1.52288	-.00060	
.800	2.006	-0.02139	-.04227	-.08393	-.02467	-.00319	-.00094	.79962	1.52376	-.00019	
.799	3.004	-0.01968	-.00238	-.12441	-.03655	-.00192	-.00056	.79878	1.52249	-.00062	
.800	4.010	-0.01969	-.00204	-.16579	-.04876	-.00178	-.00052	.79873	1.52241	-.00109	
.800	5.003	-0.01919	-.00176	-.20567	-.06053	-.00159	-.00047	.79771	1.52089	-.00191	
.800	6.002	-0.01967	-.00138	-.24591	-.07251	-.00148	-.00044	.79560	1.51771	-.00396	
.800	7.012	-0.01859	-.00118	-.28687	-.08489	-.00086	-.00025	.79216	1.51256	-.00741	
.800	8.000	-0.01905	-.00081	-.32593	-.09682	-.00069	-.00021	.78795	1.50632	-.01147	
	GRADIENT		.00001	.00034	.04002	.01181	.00023	.00007	.00135	.00090	

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( TCM003 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1149/ O	RN/L =	3.00	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
1.099	-7.994	-.02080	-.04620	-.27606	-.11300	-.00434	-.001178	1.07360	2.06596					
1.100	-6.988	-.02560	-.04631	-.24035	-.09763	-.00411	-.00167	1.08128	2.08516					
1.100	-5.988	-.03152	-.00658	-.20567	-.08303	-.00327	-.00132	1.08667	2.09876					
1.100	-4.990	-.03016	-.04566	-.17125	-.06875	-.00211	-.00085	1.09076	2.10915					
1.100	-3.991	-.03111	-.04516	-.13491	-.05397	-.00137	-.00055	1.09419	2.11793					
1.100	-2.980	-.03066	-.00491	-.09928	-.03957	-.00175	-.00070	1.09640	2.12358					
1.100	-1.980	-.00680	-.00364	-.06354	-.02527	-.00147	-.00058	1.09823	2.12827					
1.100	-.993	-.02376	-.00377	-.03003	-.01194	-.00164	-.00065	1.09914	2.13062					
1.099	.021	-.01222	-.00339	.00340	.00135	-.00126	-.00050	1.09907	2.13046					
1.100	.990	-.01733	-.00309	.03674	.01459	-.00085	-.00034	1.09972	2.13212					
1.100	2.010	-.01578	-.00285	.07153	.02841	-.0007	-.00003	1.09936	2.13119					
1.100	3.016	-.02193	-.00225	.10665	.04235	.00052	.00021	1.09932	2.13110					
1.100	4.019	-.00944	-.04246	.14277	.05672	.00079	.00031	1.09895	2.13014					
1.100	5.014	-.01294	-.04205	.17784	.07072	.00122	.00048	1.09823	2.12830					
1.099	6.010	-.02642	-.00067	.21285	.08481	.00096	.00038	1.09644	2.12367					
1.100	7.007	-.02340	-.00060	.24710	.09881	.00112	.00045	1.09381	2.11695					
1.099	8.004	-.02222	-.04035	.28016	.11249	.00137	.00055	1.08964	2.10631					
	GRADIENT	.00185	.00207	.03458	.01380	.00030	.00012	.00078	.00200					

PARAMETRIC DATA

RUN NO.	RN/L =		GRADIENT INTERVAL =		5.00 /	
	1116 /	O	3.76	5.00	CPTD	CPM
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
.800	- .8 .006	-.02088	-.00626	-.31931	-.09654	-.00620
.800	- 6 .987	-.02122	-.00593	-.27808	-.08346	-.00631
.800	- 5 .995	-.02091	-.00553	-.23804	-.07104	-.00544
.800	- 4 .992	-.02057	-.00513	-.19685	-.05842	-.00367
.800	- 3 .994	-.02021	-.00475	-.15498	-.04585	-.00280
.800	- 2 .997	-.02025	-.00441	-.11521	-.03398	-.00343
.800	- 1 .988	-.01997	-.00405	-.07381	-.02173	-.00469
.800	- .984	-.01913	-.004330	-.03446	-.01014	-.00528
.800	- .014	-.01967	-.003337	-.01967	-.00123	-.00117
.800	1 .008	-.01946	-.00304	-.01946	-.001294	-.00467
.800	2 .017	-.02086	-.004229	-.02486	-.00344	-.00101
.800	3 .016	-.01981	-.00237	-.12507	-.03676	-.00268
.800	4 .004	-.01963	-.00205	-.16571	-.04871	-.00270
.800	5 .003	-.02304	-.04117	-.20556	-.06051	-.00294
.800	6 .002	-.02342	-.04081	-.24595	-.07254	-.00263
.799	7 .001	-.01895	-.00114	-.28674	-.08480	-.00221
.800	8 .000	-.01944	-.00075	-.32616	-.09690	-.00216
				-.00062	-.01182	-.00002
				.00006	.04007	.00090
					.00005	.00091

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM0005) ( 04 OCT 91 )

#### METRIC DATA

PARAMETRIC DATA

RUN NO.	1105 / O	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/	5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPTD
7.999	.01323	-179.996940	.33274	.06627	.01048	.00909
7.002	.00784	179.99140	.29152	.05790	.01049	.00549
5.999	.00812	179.99150	.24901	.04936	.00929	.00325
4.996	.00796	179.99170	.20670	.04092	.00734	.00169
3.998	.00768	179.99190	.16417	.03249	.00569	.00102
3.001	.00769	179.99200	.12228	.02415	.00594	.00118
1.997	.00787	179.99210	.07915	.01567	.00629	.00047
.993	.00808	179.99230	.03730	.00738	.00687	.00041
.011	.00817	179.99240	-.00299	-.00059	.00731	.00145
-1.004	.00840	179.99250	-.04412	-.00872	.00755	.00149
-2.003	.00833	179.99270	-.08486	-.01681	.00581	.00170
-3.002	.00833	179.99280	-.12738	-.02529	.00506	.00101
-4.007	.00852	179.99300	-.17084	-.03401	.00505	.00100
-5.005	.00813	179.99310	-.21209	-.04226	.00511	.00102
-6.999	.00829	179.99320	-.25442	-.05090	.00580	.00116
-6.999	.00804	179.99330	-.29726	-.05796	.00493	.00099
-7.998	.00808	179.99340	-.33899	-.06834	.00449	.00091
.599	00000	00000	00000	00000	00000	00000
GRADIENT	00000	00000	00000	00000	00000	00000

BIN NO 1115 / 0 BN/1 = 3.75 GRADIENT INTERVAL = -5.00/-5.00

	CH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBETA	CPBQ	CPD	CPM	CPTD
.800	7.997	.00763	179.	99130	.31984	.09503	.00722	.00214	.79004	1.50942	-.01032
.800	6.994	.01332	-179.	96920	.27883	.08249	.00723	.00214	.79339	1.51440	-.00658
.800	5.997	.00776	179.	99160	.23898	.07051	.00622	.00183	.79651	1.51907	-.00366
.800	4.984	.01125	-179.	96870	.19858	.05848	.00450	.00133	.79832	1.52181	-.00183
.800	3.997	.00782	179.	99190	.15767	.04639	.00353	.00104	.79918	1.52310	-.00088
.800	2.994	.00829	179.	99200	.11699	.03438	.00380	.00112	.79934	1.52334	-.00040
.800	1.996	.00864	179.	99210	.07675	.02256	.00477	.00140	.79938	1.52340	-.00047
.800	.997	.00891	179.	99220	.03634	.01068	.00553	.00163	.79946	1.52352	-.00046
.800	-.017	.00877	179.	99240	-.00250	-.00073	-.00571	.00168	.79936	1.52338	-.00053
.800	-.1.005	.00875	179.	99260	-.04228	-.01244	-.00481	.00141	.79837	1.52188	-.0135
.800	-2.004	.00866	179.	99270	-.08186	-.02409	-.00383	.00113	.79704	1.51987	-.0229
.800	-3.002	.00856	179.	99280	-.12237	-.03610	-.00299	.00088	.79540	1.51741	-.00424
.800	-4.006	.00851	179.	99300	-.16297	-.04822	-.00309	.00091	.79238	1.51289	-.00722
.800	-5.010	.00818	179.	99310	-.20347	-.06044	-.00345	.00103	.78837	1.50694	-.01122
.799	-5.998	.00842	179.	99320	-.24419	-.07284	-.00322	.00096	.78300	1.49903	-.01613
.800	-7.009	.00779	179.	99330	-.28525	-.08576	-.00251	.00075	.77756	1.49111	-.0257
.800	-8.002	.00792	179.	99340	-.32461	-.09818	-.00270	.00082	.77022	1.48057	-.02940
GRADIENT		.00000			.00000		.00000		.00000		.00000

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( TCM005 ) ( 04 OCT 91 )

#### PARAMETRIC DATA

RUN NO. 1150/0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 431  
DATE 04 OCT 91 (TCM005) (04 OCT 91)

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

## PARAMETRIC DATA

	RUN NO.	1161/ 0	RN/L =	2.99	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA					CPTD
1.250	7.989	.00517	179.99160	.28230	.12212	.00694	.00300	1.24032	2.52727			.01132
1.250	6.983	.00606	179.99160	.24647	.10619	.00658	.00284	1.24424	2.53917			-.00705
1.249	5.992	.00539	179.99180	.21121	.09071	.00539	.00232	1.24593	2.54432			-.00417
1.250	4.988	.00302	179.99210	.17602	.07546	.00399	.00171	1.24800	2.55065			-.00215
1.250	3.993	.00193	179.99220	.13900	.05953	.00313	.00134	1.24867	2.55267			-.00128
1.250	2.981	.00479	179.99210	.10250	.04389	.00348	.00149	1.24939	2.55489			-.00092
1.250	1.992	.00736	179.99210	.06667	.02856	.00412	.00176	1.24882	2.55316			-.00133
1.250	.988	.00598	179.99230	.03135	.01343	.00438	.00188	1.24911	2.55403			-.00134
1.250	-.014	.00724	179.99240	-.00328	-.00140	.00373	.00160	1.24906	2.55387			-.00122
1.250	1.015	.00584	179.99250	-.03889	-.01665	.00272	.00117	1.24904	2.55381			-.00104
1.250	-2.013	.00747	179.99260	-.07363	-.03158	.00223	.00096	1.24748	2.54907			-.00270
1.250	-3.008	.00869	179.99280	-.10868	-.04675	.00249	.00107	1.24563	2.54341			-.00548
	GRADIENT	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000			.00000

## PARAMETRIC DATA

	RUN NO.	1106/ 0	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	=	.000	PHI	=	90.000
MACH	BETA	ALPHA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA					CPTD
.599	-3.996	.02141	90.01819	.00807	.00160	-.16271	-.03216	.59573	1.27126			-.00268
.600	-2.990	.02088	90.01817	.00843	.00167	-.12010	-.02374	.59789	1.27341			-.00141
.599	-1.995	.02042	90.01814	.00876	.00173	-.07850	-.01549	.59874	1.27425			-.00042
.600	-.996	.01967	90.01814	.00818	.00162	-.03790	-.00749	.59919	1.27470			-.00051
.600	.010	.01911	90.01813	.00829	.00164	.00382	.00076	.59958	1.27509			-.00047
.600	1.007	.01849	90.01813	.00672	.00133	.04583	.00905	.59945	1.27495			-.00031
.600	1.997	.01825	90.01813	.00667	.00132	.08701	.01723	.59929	1.27479			-.00093
.601	2.992	.01779	90.01814	.00598	.00119	.12899	.02557	.59871	1.27422			-.00154
.601	3.989	.01677	90.01816	.00714	.00142	.17187	.03415	.59724	1.27276			-.00302
	GRADIENT	-.00056	-.00000	-.00000	-.00000	.04176	.00827	.00017	.00016			-.00004

## PARAMETRIC DATA

	RUN NO.	1106/ 0	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/ 5.00	BETA					CPM
MACH	BETA	ALPHA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA					CPTD
.599	-3.996	.02141	90.01819	.00807	.00160	-.16271	-.03216	.59573	1.27126			-.00268
.600	-2.990	.02088	90.01817	.00843	.00167	-.12010	-.02374	.59789	1.27341			-.00141
.599	-1.995	.02042	90.01814	.00876	.00173	-.07850	-.01549	.59874	1.27425			-.00042
.600	-.996	.01967	90.01814	.00818	.00162	-.03790	-.00749	.59919	1.27470			-.00051
.600	.010	.01911	90.01813	.00829	.00164	.00382	.00076	.59958	1.27509			-.00047
.600	1.007	.01849	90.01813	.00672	.00133	.04583	.00905	.59945	1.27495			-.00031
.600	1.997	.01825	90.01813	.00667	.00132	.08701	.01723	.59929	1.27479			-.00093
.601	2.992	.01779	90.01814	.00598	.00119	.12899	.02557	.59871	1.27422			-.00154
.601	3.989	.01677	90.01816	.00714	.00142	.17187	.03415	.59724	1.27276			-.00302
	GRADIENT	-.00056	-.00000	-.00000	-.00000	.04176	.00827	.00017	.00016			-.00004

## PARAMETRIC DATA

	RUN NO.	1106/ 0	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA					CPM
MACH	BETA	ALPHA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA					CPTD
.599	-3.996	.02141	90.01819	.00807	.00160	-.16271	-.03216	.59573	1.27126			-.00268
.600	-2.990	.02088	90.01817	.00843	.00167	-.12010	-.02374	.59789	1.27341			-.00141
.599	-1.995	.02042	90.01814	.00876	.00173	-.07850	-.01549	.59874	1.27425			-.00042
.600	-.996	.01967	90.01814	.00818	.00162	-.03790	-.00749	.59919	1.27470			-.00051
.600	.010	.01911	90.01813	.00829	.00164	.00382	.00076	.59958	1.27509			-.00047
.600	1.007	.01849	90.01813	.00672	.00133	.04583	.00905	.59945	1.27495			-.00031
.600	1.997	.01825	90.01813	.00667	.00132	.08701	.01723	.59929	1.27479			-.00093
.601	2.992	.01779	90.01814	.00598	.00119	.12899	.02557	.59871	1.27422			-.00154
.601	3.989	.01677	90.01816	.00714	.00142	.17187	.03415	.59724	1.27276			-.00302
	GRADIENT	-.00056	-.00000	-.00000	-.00000	.04176	.00827	.00017	.00016			-.00004

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 432

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM006) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1113/ 0	RN/L =	3.75	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	= .000	PHI	= 90.000
								CPALPH	CPBQ	CPBETA	CPTD
								CPAQ			
.800	-3.992	.02234	90.01820	.00602	.00177	-1563.1	-.04609	.79585	1.51808	-.00379	
.800	-2.987	.02174	90.01817	.00645	.00190	-1154.3	-.03398	.79803	1.52136	-.00186	
.800	-1.977	.02090	90.01816	.00666	.00196	-07500	-.02205	.79909	1.52296	-.00074	
.800	-.989	.02037	90.01814	.00691	.00203	-.03606	-.01061	.79934	1.52335	-.00083	
.800	.016	.01960	90.01813	.00620	.00182	.00347	.00102	.79917	1.52309	-.00058	
.799	1.001	.01913	90.01813	.00515	.00151	.04382	.01287	.79861	1.52225	-.00066	
.800	2.003	.01824	90.01813	.00455	.00134	.08477	.02492	.79869	1.52237	-.00080	
.800	3.002	.01735	90.01813	.00394	.00116	.12488	.03674	.79779	1.52100	-.00172	
.800	3.990	.01668	90.01814	.00478	.00141	.16574	.04884	.79657	1.51916	-.00314	
	GRADIENT	-.00071	-.00001	-.00031	-.00009	.04025	.01185	.00001	.00002	.00005	

MACH	BETA	RUN NO.	11120/ 0	RN/L =	3.89	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	= .000	PHI	= 90.000
								CPALPH	CPBQ	CPBETA	CPTD
								CPAQ			
.900	-3.986	.02314	90.01820	.00606	.00204	-1496.3	-.05035	.89651	1.68492	-.00377	
.900	-2.981	.02268	90.01817	.00679	.00228	-1111.8	-.03734	.89840	1.68838	-.00183	
.900	-1.982	.02190	90.01816	.00709	.00238	-.07275	-.02440	.89910	1.68966	-.00082	
.900	-.983	.02126	90.01814	.00703	.00236	-.03442	-.01154	.89906	1.68958	-.00054	
.900	.012	.02055	90.01813	.00652	.00219	.00370	.00124	.89919	1.68981	-.00054	
.899	1.002	.01995	90.01813	.00531	.00178	.04221	.01415	.89899	1.68946	-.00054	
.899	1.998	.01931	90.01813	.00455	.00153	.08110	.02719	.89873	1.68898	-.00075	
.900	3.003	.01823	90.01813	.00460	.00154	.11915	.04001	.89820	1.68801	-.00179	
.900	3.993	.01708	90.01814	.00519	.00174	.15869	.05336	.89679	1.68544	-.00328	
	GRADIENT	-.00074	-.00001	-.00028	-.00009	.03860	.01297	-.00000	.00001	.00004	

CPTD

MACH	BETA	RUN NO.	11151/ 0	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	= .000	PHI	= 90.000
								CPALPH	CPBQ	CPBETA	CPTD
								CPAQ			
1.100	-3.983	.00660	90.01820	.00220	.00088	-1356.1	-.05402	1.09710	2.12537	-.00325	
1.100	-2.982	.00729	90.01817	.00250	.00099	-.10055	-.04000	1.09826	2.12838	-.00184	
1.100	-1.980	.00826	90.01816	.00310	.00123	-.06524	-.02593	1.09935	2.13118	-.00075	
1.100	-.995	.01167	90.01814	.00290	.00115	-.03086	-.01226	1.09955	2.13167	-.00019	
1.100	.021	.01305	90.01813	.00192	.00076	.00387	.00154	1.09986	2.13248	-.00027	
1.100	1.005	.02379	90.01813	.00141	.00056	.03838	.01525	1.09972	2.13213	-.00031	
1.100	2.016	.01716	90.01813	.00133	.00053	.07253	.02881	1.09915	2.13065	-.00050	
1.100	3.005	.01626	90.01813	.00144	.00057	.10623	.04224	1.09851	2.12900	-.00144	
1.100	4.001	.02292	90.01814	.00302	.00120	.14220	.05664	1.09683	2.12469	-.00324	
	GRADIENT	.00204	-.00001	-.00008	-.00003	.03467	.01380	-.00002	.00001	.00003	

MACH	BETA	RUN NO.	11151/ 0	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	= .000	PHI	= 90.000
								CPALPH	CPBQ	CPBETA	CPTD
								CPAQ			
1.100	-3.983	.00660	90.01820	.00220	.00088	-1356.1	-.05402	1.09710	2.12537	-.00325	
1.100	-2.982	.00729	90.01817	.00250	.00099	-.10055	-.04000	1.09826	2.12838	-.00184	
1.100	-1.980	.00826	90.01816	.00310	.00123	-.06524	-.02593	1.09935	2.13118	-.00075	
1.100	-.995	.01167	90.01814	.00290	.00115	-.03086	-.01226	1.09955	2.13167	-.00019	
1.100	.021	.01305	90.01813	.00192	.00076	.00387	.00154	1.09986	2.13248	-.00027	
1.100	1.005	.02379	90.01813	.00141	.00056	.03838	.01525	1.09972	2.13213	-.00031	
1.100	2.016	.01716	90.01813	.00133	.00053	.07253	.02881	1.09915	2.13065	-.00050	
1.100	3.005	.01626	90.01813	.00144	.00057	.10623	.04224	1.09851	2.12900	-.00144	
1.100	4.001	.02292	90.01814	.00302	.00120	.14220	.05664	1.09683	2.12469	-.00324	
	GRADIENT	.00204	-.00001	-.00008	-.00003	.03467	.01380	-.00002	.00001	.00003	

MACH	BETA	RUN NO.	11151/ 0	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	= .000	PHI	= 90.000
								CPALPH	CPBQ	CPBETA	CPTD
								CPAQ			
1.100	-3.983	.00660	90.01820	.00220	.00088	-1356.1	-.05402	1.09710	2.12537	-.00325	
1.100	-2.982	.00729	90.01817	.00250	.00099	-.10055	-.04000	1.09826	2.12838	-.00184	
1.100	-1.980	.00826	90.01816	.00310	.00123	-.06524	-.02593	1.09935	2.13118	-.00075	
1.100	-.995	.01167	90.01814	.00290	.00115	-.03086	-.01226	1.09955	2.13167	-.00019	
1.100	.021	.01305	90.01813	.00192	.00076	.00387	.00154	1.09986	2.13248	-.00027	
1.100	1.005	.02379	90.01813	.00141	.00056	.03838	.01525	1.09972	2.13213	-.00031	
1.100	2.016	.01716	90.01813	.00133	.00053	.07253	.02881	1.09915	2.13065	-.00050	
1.100	3.005	.01626	90.01813	.00144	.00057	.10623	.04224	1.09851	2.12900	-.00144	
1.100	4.001	.02292	90.01814	.00302	.00120	.14220	.05664	1.09683	2.12469	-.00324	
	GRADIENT	.00204	-.00001	-.00008	-.00003	.03467	.01380	-.00002	.00001	.00003	

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM006) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1162/ O	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.250	-3.987	.01507	90.01820	.00429	.00184	-.13787	-.05923	1.24639	2.54573	-.00433
1.250	-2.967	.01950	90.01817	.00462	.00198	-.10159	-.04356	1.24842	2.55193	-.00215
1.250	-1.988	.01834	90.01816	.00504	.00216	-.06628	-.02840	1.24842	2.55192	-.00181
1.250	-.984	.01727	90.01814	.00500	.00214	-.03062	-.01312	1.24862	2.55253	-.00151
1.250	.027	.01667	90.01813	.00392	.00168	.00475	.00204	1.24902	2.55377	-.00085
1.250	1.007	.01555	90.01813	.00277	.00118	.04011	.01717	1.24914	2.55411	-.00074
1.250	2.002	.01521	90.01813	.00245	.00105	.07556	.03235	1.24869	2.55274	-.00100
1.250	3.003	.01650	90.01813	.00311	.00133	.11036	.04732	1.24759	2.54940	-.00244
GRADIENT	-.000024	-.00001	-.000032	-.000014	-.000032	.03555	.00015	.000045	.000027	.000027

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF (TCM007) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1107/ O	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.599	4.032	-.01120	-89.98788	-.00397	-.00078	.16315	.03224	.59622	1.27174	-.00229
.600	3.022	-.01074	-89.98790	-.00455	-.00090	.12075	.02389	.59818	1.27369	-.00139
.600	1.999	-.01043	-89.98792	-.00617	-.00122	.07829	.01548	.59899	1.27450	-.00081
.600	1.003	-.00986	-89.98793	-.00711	-.00140	.03727	.00737	.59903	1.27453	-.00069
.600	-.010	-.00936	-89.98793	-.00684	-.00135	.00366	-.00072	.59931	1.27482	-.00046
.600	-1.008	-.00976	-89.98793	-.00578	-.00114	.04522	-.00895	.59951	1.27501	-.00075
.601	-2.016	-.00899	-89.98793	-.00436	-.00086	.08627	-.01710	.59927	1.27478	-.00117
.601	-3.016	-.00866	-89.98792	-.00299	-.00059	.12863	-.02550	.59815	1.27366	-.00191
.601	-4.033	-.00037	-89.98790	-.00250	-.00005	.17179	-.03411	.59625	1.27177	-.00344
GRADIENT	-.000037	.00000	-.000025	-.000005	-.04137	.00819	-.000002	-.000002	-.000002	.00011

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF (TCM007) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1114/ O	RN/L =	3.75	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.800	4.024	-.01262	-89.98788	-.00176	-.00052	.15723	.04636	.79704	1.51987	-.00302
.800	3.019	-.01190	-89.98790	-.00287	-.00084	.11682	.03438	.79829	1.52176	-.00160
.800	1.997	-.01136	-89.98792	-.00420	-.00124	.07644	.02248	.79921	1.52314	-.00080
.800	1.001	-.01093	-89.98793	-.00497	-.00146	.03625	.01066	.79917	1.52308	-.00060
.800	-.016	-.01071	-89.98793	-.00461	-.00135	.00322	-.00095	.79930	1.52328	-.00053
.800	-1.009	-.01025	-89.98793	-.00360	-.00106	.04348	-.01278	.79887	1.52263	-.00075
.799	-2.016	-.00956	-89.98793	-.00190	-.00056	.08368	-.02460	.79836	1.52187	-.00103
.800	-3.022	-.00917	-89.98792	-.00100	-.00029	.12378	-.03648	.79757	1.52066	-.00256
.800	-4.020	-.00883	-89.98792	-.00098	-.00029	.16491	-.04865	.79582	1.51805	-.00397
GRADIENT	-.00046	.00000	-.00024	-.00007	.03995	.01177	.00015	.000022	.00012	.00012

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( TCM007 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1121/ O	RN/L =	3.89	GRADIENT	INTERVAL =	-5.00/ 5.00	ALPHA	= .000	PHI	= -90.000	PARAMETRIC DATA				
													CPTD	CPM	MPROBE	CPTD	
.900	4.024		.01415	-89.98788	-.00178	CPAQ	CPALPH	CPBQ	CPBETA	.05077	.89710	1.68601	-.00304				
.900	3.019		.01345	-89.98790	-.00304		-.00102	-.11237	.03772	.89859	1.68871	-.00141					
.900	1.997		.01283	-89.98792	-.00441		-.00148	.07376	.02474	.89997	1.68941	-.00072					
.900	.996		.01248	-89.98793	-.00523		-.00176	.03510	.01178	.89924	1.68990	-.00080					
.900	.017		.01196	-89.98793	-.00467		-.00157	-.00303	-.00102	.89952	1.69044	-.00048					
.900	-.1.009		.01126	-89.98793	-.00313		-.00105	-.04160	-.01395	.89915	1.68974	-.00057					
.900	-.2.027		.01034	-89.98793	-.00174		-.00058	-.08086	-.02712	.89863	1.68880	-.00106					
.900	-.3.018		.01061	-89.98792	-.00107		-.00036	-.11861	-.03983	.89755	1.68683	-.00215					
.900	-.4.023		.00984	-89.98792	-.00094		-.00031	-.15760	-.05302	.89563	1.68332	-.00414					
.899	GRADIENT		-.00053	.00000	-.00028		-.00009	.03833	.01288	.00016	.00029	.00012					
MACH	BETA	RUN NO.	1152/ O	RN/L =	3.00	GRADIENT	INTERVAL =	-5.00/ 5.00						CPTD	CPM	MPROBE	CPTD
1.100	4.020		.00444	-89.98788	.00111	CPAQ	CPALPH	CPBQ	CPBETA	.05454	1.09768	2.12687	-.00265				
1.100	2.996		.00071	-89.98790	-.00011		-.00044	1.0119	.04023	1.09875	2.12962	-.00118					
1.100	1.984		.00244	-89.98792	-.00132		-.00052	.06593	.02619	1.09938	2.13125	-.00039					
1.100	.996		.00622	-89.98793	-.00296		-.00117	.03165	.01257	1.09994	2.13271	-.00014					
1.100	-.016		.00564	-89.98793	-.00178		-.00071	-.00291	-.00116	1.09975	2.13221	-.00017					
1.100	-.1.001		.01222	-89.98793	-.00049		-.00020	-.03669	-.01457	1.09961	2.13185	-.00032					
1.099	-.2.017		.00755	-89.98793	.00085		-.00034	-.07081	-.02813	1.09851	2.12900	-.00078					
1.100	-.3.025		.00228	-89.98792	.00085		-.00034	-.10504	-.04178	1.09803	2.12778	-.00190					
1.099	-.4.035		.00393	-89.98790	-.00072		-.00029	-.14112	-.05624	1.09620	2.12308	-.00384					
	GRADIENT		.00061	.00000	-.00013		-.00005	.03439	.01368	.00017	.00043	.00013					
MACH	BETA	RUN NO.	1163/ O	RN/L =	3.00	GRADIENT	INTERVAL =	-5.00/ 5.00						CPTD	CPM	MPROBE	CPTD
1.250	4.024		.00443	-89.98788	-.00133	CPAQ	CPALPH	CPBQ	CPBETA	.05937	1.24667	2.54660	-.00365				
1.250	2.996		.00671	-89.98790	-.00234		-.00100	.10286	.04409	1.24826	2.5145	-.00202					
1.250	1.998		.00844	-89.98792	-.00359		-.00154	.06763	.02898	1.24875	2.55292	-.00165					
1.250	.993		.00774	-89.98793	-.00416		-.00178	.03185	.01364	1.24878	2.55301	-.00126					
1.250	-.018		.00791	-89.98793	-.00325		-.00139	-.00325	-.00139	1.24875	2.55292	-.00092					
1.250	-.1.013		.00760	-89.98793	-.00184		-.00079	-.03906	-.01672	1.24966	2.55572	-.00075					
1.249	-.2.031		.00817	-89.98793	-.00100		-.00043	-.07483	-.03205	1.24827	2.55146	-.00135					
1.250	-.3.021		.00955	-89.98792	-.00098		-.00042	-.10934	-.04691	1.24712	2.54796	-.00303					
	GRADIENT		.00048	.00000	-.00018		-.00008	.03532	.01515	.00007	.00021	.00013					

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM008) ( 04 OCT 91 )

卷之三

PARAMERIC DATA

RUN NO.		1123/ O		RN/L = 3.89		GRADIENT INTERVAL = -5.00/ 5.00		CPD	
MACH .920 .920	ALPHA .010 GRADIENT	BETA -.02133 -.02310 .00044	PHI -.003337 -.00495 .00039	CPAQ .00393 -.14888 .03783	CPALPH .00135 -.05137 .01305	CPBQ -.00537 -.00344 -.00048	CPBETA -.00184 -.00119 -.00016	M PROBE .91934 .91317 .00153	CPTD -.00063 -.00712 .00161
	ALPHA .010 GRADIENT	BETA -.02229 -.02376 .00036	PHI -.04297 -.00499 .00940	CPAQ -.00371 -.14656 .03719	CPALPH .00131 -.05215 .01323	CPBQ -.00540 -.00369 -.00042	CPBETA -.00191 -.00131 -.00015	M PROBE .94940 .94299 .00159	CPTD -.00050 -.00727 .00167
	ALPHA .950 .949	BETA -.01871 -.02339 .00116	PHI -.00338 -.00496 .00039	CPAQ .00315 -.14452 .03653	CPALPH .00114 -.05289 .01337	CPBQ -.00463 -.00306 -.00039	CPBETA -.00168 -.00112 -.00014	M PROBE .97948 .97350 .00148	CPTD -.00039 -.00710 .00166
RUN NO.		1134/ O		RN/L = 3.86		GRADIENT INTERVAL = -5.00/ 5.00		CPD	
MACH .980 .980	ALPHA .008 GRADIENT	BETA -.01871 -.02339 .00116	PHI -.00338 -.00496 .00039	CPAQ .00315 -.14452 .03653	CPALPH .00114 -.05289 .01337	CPBQ -.00463 -.00306 -.00039	CPBETA -.00168 -.00112 -.00014	M PROBE .94845 .83582 .00313	CPTD -.00039 -.00710 .00166
	ALPHA .029 GRADIENT	BETA -.02206 -.03575 .00337	PHI -.003337 -.00579 .00060	CPAQ .00196 -.14172 .03540	CPALPH .00076 -.05487 .01370	CPBQ -.00385 -.00273 -.00028	CPBETA -.00148 -.00106 -.00010	M PROBE .94933 .94359 .00141	CPTD -.00073 -.00759 .00169
	ALPHA .050 GRADIENT	BETA -.01771 -.02253 .00119	PHI -.003338 -.00493 .00038	CPAQ .00323 -.13664 .03453	CPALPH .00132 -.05623 .01421	CPBQ -.00290 -.00216 -.00018	CPBETA -.00118 -.00089 -.00007	M PROBE .14944 .14393 .00136	CPTD -.00060 -.00730 .00165

## PARAMETRIC DATA

RUN NO. 1124/ O RN/L = 3.89 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAO	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.920	.007	.01009	179.99240	.00301	.00103	.00569	.00195	.91934	1.72743	-.00050
.920	4.032	.01028	179.99170	.15028	.05154	.00423	.00145	.91917	1.72710	-.00074
	GRADIENT	.00005	-.00017	.03795	.01301	-.00036	-.00012	-.00004	-.00008	-.00006

RUN NO. 1129/ O RN/L = 3.88 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.950	.013	.01043	179.99240	.00293	-.00104	.00553	.00195	.94921	1.78585	-.00042
.950	4.038	.01061	179.99170	.14844	.05248	.00444	.00157	.94885	1.78512	-.00077
	GRADIENT	.00005	-.00017	.03737	.01321	-.00027	-.00009	-.00009	-.00018	-.00009

RUN NO. 1135/ O RN/L = 3.86 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.980	.011	.00817	179.99240	-.00286	-.00104	.00522	.00190	.97944	1.84838	-.00045
.980	4.047	.00869	179.99180	.14657	.05329	.00381	.00139	.97910	1.84766	-.00059
	GRADIENT	.00013	-.00015	.03682	.01339	-.00035	-.00013	-.00008	-.00018	-.00004

RUN NO. 1140/ O RN/L = 3.77 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.050	.004	.00883	179.99240	-.00462	-.00178	.00459	.00176	1.04903	2.00594	-.00082
1.050	4.044	.02835	179.99050	.13954	.05366	.00462	.00178	1.04892	2.00567	-.00098
	GRADIENT	.00482	-.00047	.03561	.01370	-.00001	.00000	-.00003	-.00007	-.00004

RUN NO. 1155/ O RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.150	.014	.00822	179.99240	-.00314	-.00128	.00346	.00141	1.14963	2.26507	-.00050
1.150	4.042	.01035	179.99170	.13801	.05642	.00347	.00142	1.14965	2.26513	-.00062
	GRADIENT	.00053	-.00017	.03480	.01423	-.00000	.00000	-.00000	-.00001	-.00003

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM010) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1125/ 0	RN/L =	3.88	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
.920	.1.990		ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	.02741	MPROBE	CPTD
	.01976	90.01813	.00426	.00146	.07994	.07282	-.02498	.91876	1.72632	-.00088	
.920	-.2.017	.02285	90.01816	.00686	.00235	-.03812	.01307	.91920	1.72717	-.00095	
	-.00077	-.00001	-.00065	-.00022	.03812	-.00011		-.00011	-.00021	.00002	
MACH	BETA	RUN NO.	1130/ 0	RN/L =	3.88	GRADIENT INTERVAL =	-5.00/ 5.00				
.950	.1.943		ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	.02737	MPROBE	CPTD
	.01922	90.01811	.00388	.00137	.07737	.07233	-.02558	.94906	1.78554	-.00090	
.950	-.2.024	.02335	90.01816	.00681	.00241	-.03774	.01335	.94882	1.78507	-.0101	
	-.00104	-.00001	-.00074	-.00026	.03774	-.00006		-.00006	.00012	.00003	
MACH	BETA	RUN NO.	1136/ 0	RN/L =	3.86	GRADIENT INTERVAL =	-5.00/ 5.00				
.980	.1.988		ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	.02816	MPROBE	CPTD
	.01756	90.01813	.00349	.00127	.07744	.07092	-.02581	.97895	1.84734	-.00071	
.980	-.2.024	.02186	90.01816	.00630	.00229	-.03698	.01345	.97913	1.84772	-.00106	
	-.00107	-.00001	-.00070	-.00025	.03698	-.00004		-.00004	.00009	.00009	
MACH	BETA	RUN NO.	1141/ 0	RN/L =	3.77	GRADIENT INTERVAL =	-5.00/ 5.00				
.980	.1.989		ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	.02816	MPROBE	CPTD
	.02164	90.01813	.00080	.00031	.07433	.06834	-.02630	1.04885	2.00550	-.00106	
.980	-.2.021	.02805	90.01816	.00343	.00132	-.00025	.03558	1.04884	2.00547	-.00130	
	-.00160	-.00001	-.00065	-.00025	.03558	-.00000		-.00000	.00001	.00006	
MACH	BETA	RUN NO.	1156/ 0	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00				
1.050	.1.989		ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	.02951	MPROBE	CPTD
	.02164	90.01813	.00249	.00102	.07219	.06627	-.02709	1.14878	2.26273	-.00095	
1.050	-.2.021	.02805	90.01816	.00500	.00204	-.00026	.03453	.01412	1.14919	2.26386	-.00066
	-.00160	-.00001	-.00063	-.00026	.03453	-.00010		-.00010	.00028	-.00007	

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM011) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	GRADIENT	RUN NO.	1126/ 0	RN/L =	3.88	GRADIENT	INTERVAL =	-5.00/	5.00	ALPHA	=	.000	PHI	=	-90.000
				ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD				
.920	-2.004	GRADIENT	- .01133	-89.98793	- .00219	- .00075	- .07962	- .02731	.91880	1.72640	- .00106					
			- .01361	-89.98792	- .00487	- .00167	.07404	.02539	.91921	1.72717	- .00067					
			- .00056	.00000	- .00066	- .00023	.03802	.01304	.00010	.00019	.00010	.00010				
.920	2.037	GRADIENT	RUN NO.	1131/ 0	RN/L =	3.88	GRADIENT	INTERVAL =	-5.00/	5.00						
			BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD				
			- .01179	-89.98793	- .00207	- .00073	- .07820	- .02767	.94870	1.78483	- .00121					
.950	-2.043	GRADIENT	- .01394	-89.98792	- .00475	- .00168	- .07337	- .02595	.94913	1.78569	- .00084					
			- .00053	.00000	- .00066	- .00023	.03748	.01326	.00011	.00021	.00011	.00009	.00009	.00009	.00009	.00009
			RUN NO.	1137/ 0	RN/L =	3.86	GRADIENT	INTERVAL =	-5.00/	5.00						
.950	2.043	GRADIENT	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD				
			- .01075	-89.98793	- .00184	- .00067	- .07656	- .02786	.97905	1.84755	- .00116					
			- .01342	-89.98792	- .00462	- .00168	- .07221	- .02627	.97936	1.84820	- .00073					
.980	-2.039	GRADIENT	- .00066	.00000	- .00069	- .00025	.03681	.01339	.00008	.00016	.00016	.00011	.00011	.00011	.00011	.00011
			RUN NO.	1142/ 0	RN/L =	3.77	GRADIENT	INTERVAL =	-5.00/	5.00						
			BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD				
.980	2.039	GRADIENT	- .01651	-89.98793	- .00369	- .00142	- .07322	- .02817	1.04836	2.00433	- .00153					
			- .01666	-89.98792	- .00621	- .00239	.06966	.02680	1.04904	2.00596	- .00112					
			- .00004	.00000	- .00062	- .00024	.03538	.01361	.00017	.00040	.00040	.00010	.00010	.00010	.00010	.00010
1.050	-2.002	GRADIENT	RUN NO.	1157/ 0	RN/L =	3.00	GRADIENT	INTERVAL =	-5.00/	5.00						
			BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD				
			- .00841	-89.98793	- .00076	- .00031	- .07127	- .02915	1.14871	2.26253	- .00129					
1.150	2.023	GRADIENT	- .00897	-89.98792	- .00320	- .00131	.06709	.02743	1.14963	2.26506	- .00066					
			- .00014	.00000	- .00061	- .00025	.03431	.01403	.00023	.00033	.00033	.00016	.00016	.00016	.00016	.00016

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 439

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM012) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1132/ O	RN/L =	3.88	GRADIENT INTERVAL	=	-5.00/ 5.00	ALPHA	=	.000	PHI	=	-90.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	CPH	=	
.950	-2.000	-.01191	-89.98793	-.00201	-.00071	-.07800	-.02760	.94905	1.78554	-.00105			
.950	2.038	-.01397	-89.98792	-.00494	-.00175	.07334	.02594	.94926	1.78596	-.00077			
	GRADIENT	.000051	.00000	-.00073	-.00026	.03748	.01326	.00005	.00010	.00007			

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM013) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1221/ O	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/ 5.00	BETA	=	.000	PHI	=	.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	CPH	=	
.899	-8.002	-.02002	-.00616	-.30437	-.10487	-.00745	-.00257	.87336	1.64366	-.02838			
.900	-6.995	-.01946	-.00574	-.26470	-.09065	-.00708	-.00242	.88039	1.65599	-.02141			
.900	-5.993	-.01907	-.00535	-.22668	-.07718	-.00578	-.00197	.88568	1.66540	-.01560			
.900	-4.991	-.01893	-.00501	-.18882	-.06398	-.00450	-.00153	.89022	1.67354	-.01068			
.900	-3.993	-.01935	-.00471	-.14903	-.05030	-.00388	-.00131	.89341	1.67929	-.00698			
.900	-2.991	-.01916	-.00436	-.10995	-.03700	-.00403	-.00136	.89608	1.68415	-.00401			
.900	-1.995	-.01905	-.00403	-.07049	-.02369	-.00158	-.00174	.89801	1.68766	-.00222			
.900	- .992	-.01893	-.00370	-.03295	-.01106	-.00552	-.00185	.89891	1.68930	-.00114			
.900	.021	-.01870	-.00337	-.00236	-.00079	-.00491	-.00165	.89923	1.68990	-.00083			
.900	1.007	-.01847	-.00306	-.03956	.01327	-.00383	-.00128	.89895	1.68938	-.00081			
.900	2.009	-.01807	-.00276	-.07812	.02620	-.00275	-.00092	.89901	1.68948	-.00076			
.900	3.012	-.01840	-.00244	-.11300	.03791	-.00257	-.00086	.89918	1.68981	-.00076			
.900	4.010	-.01803	-.00215	-.15450	.05184	-.00299	-.00100	.89885	1.68920	-.00103			
.900	5.008	-.02123	-.04132	-.19378	.06507	-.00294	-.00099	.89789	1.68744	-.00198			
.900	6.007	-.02188	-.04096	-.23269	.07825	-.00252	-.00085	.89613	1.68424	-.00365			
.900	7.006	-.01788	-.00126	-.27066	.09134	-.00250	-.00084	.89354	1.67953	-.00681			
.900	7.999	-.01839	-.00088	.30901	.10469	-.00266	-.00090	.88971	1.67261	-.01089			
	GRADIENT	.00013	.00032	.03774	.01271	.00021	.00007	.00082	.00150	.00092			

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 440

(TCM013) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1165/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA	= .000	PHI	= .000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBE
1.249	-7.994	-.01564	-.00556	-.28113	-.12407	-.00488	-.00215
1.249	-6.987	-.01602	-.00532	-.24505	-.10738	-.00465	-.00204
1.250	-5.992	-.01534	-.00497	-.20974	-.09134	-.00385	-.00168
1.249	-4.992	-.01297	-.00451	-.17459	-.07561	-.00270	-.00117
1.250	-3.996	-.01381	-.00434	-.13764	-.05937	-.00221	-.00095
1.250	-2.995	-.01675	-.00424	-.10123	-.04350	-.00259	-.00111
1.250	-1.995	-.01586	-.00393	-.06503	-.02789	-.00335	-.00144
1.250	-.991	-.01554	-.00365	-.02997	-.01285	-.00376	-.00161
1.250	.024	-.01537	-.00338	-.00386	-.00165	-.00329	-.00141
1.250	1.010	-.01553	-.00312	-.03876	-.01659	-.00263	-.00112
1.250	2.004	-.01799	-.004239	-.07378	-.03158	-.00209	-.00089
1.250	3.014	-.01800	-.00246	-.10961	-.04694	-.00200	-.00086
1.250	4.011	-.01860	-.00211	-.14662	-.06282	-.00228	-.00098
1.250	5.023	-.02154	-.004129	-.18274	-.07835	-.00170	-.00073
1.249	6.004	-.01701	-.00165	-.21931	-.09410	-.00122	-.00052
1.249	7.008	-.01764	-.00129	-.25438	-.10956	-.00137	-.00059
1.249	8.005	-.01751	-.00101	-.28834	-.12471	-.00122	-.00053
	GRADIENT			-.00092	-.03538	-.01522	-.00006
RUN NO.	1185/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA	= .000	PHI	= .000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBE
1.400	-8.002	-.02353	-.00663	-.31284	-.14540	-.00609	-.00283
1.400	-6.991	-.02101	-.00591	-.27428	-.12640	-.00613	-.00237
1.400	-5.996	-.02025	-.00547	-.23516	-.10766	-.00391	-.00179
1.400	-5.000	-.02195	-.00526	-.19514	-.08891	-.00310	-.00141
1.400	-3.994	-.02223	-.00490	-.15346	-.06964	-.00250	-.00113
1.400	-2.994	-.02125	-.00446	-.11319	-.05116	-.00289	-.00130
1.400	-1.993	-.02019	-.00407	-.07370	-.03326	-.00379	-.00171
1.400	-.995	-.01826	-.00369	-.03464	-.01562	-.00389	-.00175
1.400	.024	-.01743	-.00338	-.00346	-.00156	-.00315	-.00142
1.400	1.005	-.01822	-.00307	-.04133	-.01860	-.00248	-.00112
1.400	2.006	-.01832	-.00275	-.08026	-.03616	-.00220	-.00099
1.400	3.021	-.01859	-.00242	-.12041	-.05424	-.00240	-.00108
1.400	4.018	-.01665	-.00225	-.162297	-.07338	-.00236	-.00106
1.400	5.009	-.01678	-.00196	-.20234	-.09121	-.00172	-.00078
1.400	6.017	-.01759	-.00159	-.24203	-.10924	-.00161	-.00073
1.400	7.009	-.01772	-.00128	-.28119	-.12723	-.00195	-.00088
1.399	8.011	-.01850	-.00087	-.31809	-.14450	-.00135	-.00061
	GRADIENT			-.00057	-.0033	-.01766	-.00011

RUN NO.	1185/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA	= .000	PHI	= .000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBE
1.400	-8.002	-.02353	-.00663	-.31284	-.14540	-.00609	-.00283
1.400	-6.991	-.02101	-.00591	-.27428	-.12640	-.00613	-.00237
1.400	-5.996	-.02025	-.00547	-.23516	-.10766	-.00391	-.00179
1.400	-5.000	-.02195	-.00526	-.19514	-.08891	-.00310	-.00141
1.400	-3.994	-.02223	-.00490	-.15346	-.06964	-.00250	-.00113
1.400	-2.994	-.02125	-.00446	-.11319	-.05116	-.00289	-.00130
1.400	-1.993	-.02019	-.00407	-.07370	-.03326	-.00379	-.00171
1.400	-.995	-.01826	-.00369	-.03464	-.01562	-.00389	-.00175
1.400	.024	-.01743	-.00338	-.00346	-.00156	-.00315	-.00142
1.400	1.005	-.01822	-.00307	-.04133	-.01860	-.00248	-.00112
1.400	2.006	-.01832	-.00275	-.08026	-.03616	-.00220	-.00099
1.400	3.021	-.01859	-.00242	-.12041	-.05424	-.00240	-.00108
1.400	4.018	-.01665	-.00225	-.162297	-.07338	-.00236	-.00106
1.400	5.009	-.01678	-.00196	-.20234	-.09121	-.00172	-.00078
1.400	6.017	-.01759	-.00159	-.24203	-.10924	-.00161	-.00073
1.400	7.009	-.01772	-.00128	-.28119	-.12723	-.00195	-.00088
1.399	8.011	-.01850	-.00087	-.31809	-.14450	-.00135	-.00061
	GRADIENT			-.00057	-.0033	-.01766	-.00011

RUN NO.	1185/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA	= .000	PHI	= .000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBE
1.400	-8.002	-.02353	-.00663	-.31284	-.14540	-.00609	-.00283
1.400	-6.991	-.02101	-.00591	-.27428	-.12640	-.00613	-.00237
1.400	-5.996	-.02025	-.00547	-.23516	-.10766	-.00391	-.00179
1.400	-5.000	-.02195	-.00526	-.19514	-.08891	-.00310	-.00141
1.400	-3.994	-.02223	-.00490	-.15346	-.06964	-.00250	-.00113
1.400	-2.994	-.02125	-.00446	-.11319	-.05116	-.00289	-.00130
1.400	-1.993	-.02019	-.00407	-.07370	-.03326	-.00379	-.00171
1.400	-.995	-.01826	-.00369	-.03464	-.01562	-.00389	-.00175
1.400	.024	-.01743	-.00338	-.00346	-.00156	-.00315	-.00142
1.400	1.005	-.01822	-.00307	-.04133	-.01860	-.00248	-.00112
1.400	2.006	-.01832	-.00275	-.08026	-.03616	-.00220	-.00099
1.400	3.021	-.01859	-.00242	-.12041	-.05424	-.00240	-.00108
1.400	4.018	-.01665	-.00225	-.162297	-.07338	-.00236	-.00106
1.400	5.009	-.01678	-.00196	-.20234	-.09121	-.00172	-.00078
1.400	6.017	-.01759	-.00159	-.24203	-.10924	-.00161	-.00073
1.400	7.009	-.01772	-.00128	-.28119	-.12723	-.00195	-.00088
1.399	8.011	-.01850	-.00087	-.31809	-.14450	-.00135	-.00061
	GRADIENT			-.00057	-.0033	-.01766	-.00011

RUN NO.	1185/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA	= .000	PHI	= .000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBE
1.400	-8.002	-.02353	-.00663	-.31284	-.14540	-.00609	-.00283
1.400	-6.991	-.02101	-.00591	-.27428	-.12640	-.00613	-.00237
1.400	-5.996	-.02025	-.00547	-.23516	-.10766	-.00391	-.00179
1.400	-5.000	-.02195	-.00526	-.19514	-.08891	-.00310	-.00141
1.400	-3.994	-.02223	-.00490	-.15346	-.06964	-.00250	-.00113
1.400	-2.994	-.02125	-.00446	-.11319	-.05116	-.00289	-.00130
1.400	-1.993	-.02019	-.00407	-.07370	-.03326	-.00379	-.00171
1.400	-.995	-.01826	-.00369	-.03464	-.01562	-.00389	-.00175
1.400	.024	-.01743	-.00338	-.00346	-.00156	-.00315	-.00142
1.400	1.005	-.01822	-.00307	-.04133	-.01860	-.00248	-.00112
1.400	2.006	-.01832	-.00275	-.08026	-.03616	-.00220	-.00099
1.400	3.021	-.01859	-.00242	-.12041	-.05424	-.00240	-.00108
1.400	4.018	-.01665	-.00225	-.162297	-.07338	-.00236	-.00106
1.400	5.009	-.01678	-.00196	-.20234	-.09121	-.00172	-.00078
1.400	6.017	-.01759	-.00159	-.24203	-.10924	-.00161	-.00073
1.400	7.009	-.01772	-.00128	-.28119	-.12723	-.00195	-.00088
1.399	8.011	-.01850	-.00087	-.31809	-.14450	-.00135	-.00061
	GRADIENT			-.00057	-.0033	-.01766	-.00011

RUN NO.	1185/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA	= .000	PHI	= .000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBE
1.400	-8.002	-.02353	-.00663	-.31284	-.14540	-.00609	-.00283
1.400	-6.991	-.02101	-.00591	-.27428	-.12640	-.00613	-.00237
1.400	-5.996	-.02025	-.00547	-.23516	-.10766	-.00391	-.00179
1.400	-5.000	-.02195	-.00526	-.19514	-.08891	-.00310	-.00141
1.400	-3.994	-.02223	-.00490	-.15346	-.06964	-.00250	-.00113
1.400	-2.994	-.02125	-.00446	-.11319	-.05116	-.0	

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM013) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1203/ O	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	.000
	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPBE	CPMI			CPTD		
MACH	-8.005	-.02062	-.00624	-.32586	-.15395	-.01080	-.00510	1.41888	3.11583			-.03609		
1.450	-7.000	-.02031	-.00583	-.28405	-.13330	-.01061	-.00498	1.42391	3.13373			-.02933		
1.449	-6.005	-.02001	-.00545	-.24296	-.11332	-.00914	-.00426	1.42935	3.15318			-.02305		
1.450	-5.000	-.01881	-.00500	-.20421	-.09462	-.00775	-.00359	1.43572	3.17605			-.01618		
1.450	-3.999	-.01850	-.00465	-.16087	-.07424	-.00705	-.00325	1.43880	3.18716			-.01222		
1.450	-3.000	-.01872	-.00434	-.11948	-.05498	-.00699	-.00322	1.44142	3.19662			-.00928		
1.450	-2.006	-.01832	-.00401	-.07925	-.03630	-.00696	-.00319	1.44555	3.21159			-.00460		
1.450	-1.002	-.01814	-.00369	-.03666	-.01674	-.00660	-.00301	1.44944	3.22574			-.00102		
1.451	.003	-.01782	-.00338	-.00407	-.00186	-.00533	-.00243	1.45132	3.23256			.00052		
1.450	1.006	-.01842	-.00306	.04653	.02116	-.00442	-.00201	1.45192	3.23477			.00246		
1.450	2.001	-.01828	-.00276	.08636	.03945	-.00334	-.00153	1.44867	3.22291			-.00178		
1.451	2.996	-.01637	-.03711	-.12779	.05838	-.00340	-.00155	1.44901	3.22415			-.00177		
1.449	4.002	-.01888	-.00210	-.17317	.07900	-.00340	-.00155	1.44883	3.22352			-.00067		
1.451	4.994	-.01774	-.00188	.21390	.09784	-.00186	-.00085	1.44805	3.22066			-.00296		
1.450	6.001	-.01790	-.00156	.25472	.11672	-.00142	-.00065	1.44586	3.21272			-.00492		
1.450	6.988	-.01793	-.00126	.29599	.13584	-.00190	-.00087	1.44387	3.20549			-.00661		
1.449	7.995	-.01779	-.00098	.33458	.15411	-.00117	-.00054	1.44015	3.19203			-.01034		
GRADIENT	.00010	.00139	.04167	.01914	.0058	.00027	.00121	.00439	.00131			.00131		

RUN NO. 1276/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1276/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	.000
	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPBE	CPMI			CPTD		
MACH	-8.000	-.01936	-.00606	-.34614	-.16391	-.00925	-.00438	1.44562	3.21183			-.03390		
1.474	-6.979	-.01933	-.00571	-.30285	-.14232	-.00814	-.00383	1.45167	3.23385			-.02616		
1.474	-5.995	-.01902	-.00535	-.25996	-.12148	-.00676	-.00316	1.45711	3.25373			-.02038		
1.474	-4.994	-.01770	-.00490	-.21564	-.10032	-.00560	-.00261	1.46076	3.26709			-.01582		
1.474	-3.994	-.01768	-.00460	-.16911	-.07829	-.00499	-.00231	1.46506	3.28291			-.01105		
1.474	-2.994	-.01798	-.00430	-.12316	-.05697	-.00526	-.00243	1.46585	3.28581			-.01023		
1.474	-1.979	-.01784	-.00399	-.07940	-.03676	-.00621	-.00288	1.46558	3.28483			-.01093		
1.473	-.991	-.01751	-.00368	-.03747	-.01730	-.00690	-.00318	1.46744	3.29168			-.00812		
1.473	.014	-.01704	-.00338	.00444	.00205	-.00610	-.00281	1.46865	3.29614			-.00687		
1.473	1.011	-.01712	-.00309	.04734	.02181	-.00542	-.00250	1.46898	3.29737			-.00649		
1.473	2.005	-.01769	-.00278	.08997	.04143	-.00444	-.00205	1.46956	3.29951			-.00565		
1.474	3.010	-.01714	-.00251	.13346	.06140	-.00440	-.00202	1.47085	3.30428			-.00470		
1.474	4.022	-.01712	-.00221	.17866	.08217	-.00404	-.00186	1.47134	3.30610			-.00453		
1.473	5.008	-.02134	-.04131	.22350	.10266	-.00287	-.00132	1.47181	3.30782			-.00327		
1.473	6.004	-.01830	-.00152	.26720	.12273	-.00234	-.00108	1.47155	3.30687			-.00340		
1.473	7.012	-.02362	-.04045	.30979	.14239	-.00214	-.00098	1.47086	3.30430			-.00418		
1.473	8.008	-.01853	-.00087	.35017	.16146	-.00123	-.00057	1.46853	3.29571			-.00713		
GRADIENT	.00008	.00030	.04332	.0003	.02003	.00015	.00007	.00100	.00370			.00111		

## PARAMETRIC DATA

	RUN NO.	1238/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	.000	PHI =	= .000
<b>ALPHA</b>											
MACH	1.495	-7.999	-0.01725	-.00578	-.35953	-17060	-.00718	-.00341	1.46891	3.29712	-.03497
	1.495	-6.988	-0.01837	-.00560	-.31668	-14912	-.00725	-.00342	1.47578	3.32254	-.02705
	1.495	-5.993	-0.01703	-.00515	-.27398	-12815	-.00601	-.00281	1.48203	3.34581	-.02012
	1.495	-4.993	-0.01381	-.04432	-.22877	-10647	-.00537	-.00250	1.48646	3.36234	-.01491
	1.495	-3.987	-0.01723	-.00456	-.18141	-.08420	-.00617	-.00240	1.48911	3.37229	-.01218
	1.495	-2.993	-0.01577	-.04384	-.13600	-.06294	-.00609	-.00282	1.49187	3.38265	-.00923
	1.495	-1.994	-0.01561	-.04354	-.08974	-.04142	-.00657	-.00303	1.49398	3.39059	-.00672
	1.495	-0.998	-0.01599	-.04326	-.04172	-.01925	-.00690	-.00318	1.49427	3.39167	-.00623
	1.495	.015	-0.01536	-.00338	-.00485	-.00224	-.00594	-.00274	1.49403	3.39075	-.00638
	1.496	1.008	-0.01531	-.00312	-.05156	.02381	-.00486	-.00225	1.49400	3.39066	-.00695
	1.495	2.005	-0.01723	-.00279	-.09632	.04440	-.00517	-.00238	1.49524	3.39531	-.00522
	1.495	3.010	-0.01808	-.00246	-.14050	.06467	-.00487	-.00224	1.49648	3.39999	-.00383
	1.495	4.011	-0.01844	-.00212	-.18821	.08664	-.00414	-.00191	1.49665	3.40063	-.00365
	1.495	5.007	-0.02129	-.04132	-.23380	.10765	-.00285	-.00131	1.49649	3.40003	-.00377
	1.495	6.015	-0.02120	-.04103	-.27943	.12858	-.00222	-.00102	1.49684	3.40136	-.00309
	1.496	7.007	-0.01722	-.00134	-.32217	.14838	-.00206	-.00095	1.49667	3.40069	-.00396
	1.496	8.008	-0.02206	-.04036	-.35982	.16623	-.00075	-.00035	1.49356	3.38900	-.00714
	GRADIENT		-.00032	-.00462	-.04628	.02141	.00014	.00007	.00364	.00108	.00097
<b>ALPHA</b>											
MACH	1.520	-7.999	-.02155	-.00636	-.43801	-.20587	-.00879	-.00413	1.50735	3.44111	-.01918
	1.520	-6.993	-.02155	-.00598	-.37793	-.17667	-.00954	-.00446	1.51252	3.46082	-.01363
	1.520	-5.993	-.02061	-.00551	-.30375	-.14170	-.00820	-.00383	1.51425	3.46741	-.01161
	1.520	-4.999	-.02029	-.00512	-.24023	-.11163	-.00909	-.00423	1.51774	3.48075	-.00800
	1.520	-3.982	-.02055	-.00478	-.17520	-.08136	-.00943	-.00438	1.51854	3.48384	-.00737
	1.520	-2.994	-.02041	-.00442	-.11074	-.05143	-.00767	-.00356	1.51877	3.48472	-.00734
	1.520	-1.995	-.01998	-.00406	-.05392	-.02503	-.00501	-.00233	1.51876	3.48465	-.00700
	1.520	-0.986	-.01939	-.00370	-.02342	-.01086	-.00391	-.00182	1.51967	3.48817	-.00572
	1.520	.014	-.01917	-.00337	-.00400	-.00185	-.00407	-.00189	1.52070	3.49209	-.00479
	1.520	1.011	-.01931	-.00304	-.03136	-.01454	-.00189	-.00087	1.52030	3.49058	-.00518
	1.520	2.005	-.01938	-.00272	-.07323	-.03402	-.00243	-.00113	1.51845	3.48347	-.00732
	1.520	3.005	-.01943	-.00238	-.13675	.06342	-.00488	-.00227	1.51917	3.48624	-.00588
	1.521	4.006	-.01971	-.00204	-.19761	.09168	-.00519	-.00241	1.51970	3.48827	-.00625
	1.520	5.018	-.01925	-.00174	-.26494	.12315	-.00607	-.00282	1.51696	3.47778	-.00832
	1.520	6.004	-.01903	-.00144	-.32942	.15279	-.00683	-.00317	1.51909	3.48593	-.00617
	1.520	7.006	-.01940	-.00108	-.38189	.17687	-.00543	-.00251	1.52082	3.49257	-.00467
	1.520	7.997	-.01937	-.00075	-.43253	.19991	-.00227	-.00105	1.52278	3.50009	-.00256
	GRADIENT		-.00012	.00034	-.04442	.02062	.00062	.00029	.00016	.00020	.00091

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM013) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1251 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPI	CPTD
1.543	-8.002	-.02072	-.00625	-.38522	-.18278	-.00932	-.00442	1.52610	3.51285	-.02611
1.543	-7.003	-.01577	-.04518	-.32930	-.15582	-.00817	-.00386	1.52845	3.52191	-.02339
1.543	-5.992	-.01635	-.04488	-.27645	-.13053	-.00555	-.00262	1.53110	3.53215	-.02107
1.544	-4.982	-.01714	-.04459	-.22153	-.10434	-.00487	-.00229	1.53402	3.54347	-.01797
1.544	-3.992	-.02124	-.00483	-.16142	-.07592	-.00257	-.00121	1.53473	3.54622	-.01652
1.544	-2.993	-.02086	-.00445	-.11185	-.05254	-.00266	-.00125	1.53635	3.55249	-.01517
1.544	-1.988	-.02049	-.00407	-.06680	-.03138	-.00488	-.00229	1.53682	3.56431	-.01506
1.544	-.990	-.01988	-.00371	-.02678	-.01260	-.00588	-.00277	1.53453	3.54544	-.01683
1.544	.015	-.01972	-.00337	-.00465	-.00219	-.00558	-.00263	1.53349	3.54140	-.01802
1.544	1.011	-.02070	-.04263	-.03575	-.01684	-.00366	-.00173	1.53351	3.54148	-.01827
1.543	2.011	-.01920	-.00272	-.07292	-.03433	-.00220	-.00104	1.53354	3.54158	-.01795
1.543	3.010	-.01920	-.00240	-.11562	-.05436	-.0017	-.0008	1.53435	3.54473	-.01680
1.543	4.006	-.01956	-.00205	-.17135	.08057	-.00103	-.00049	1.53427	3.54443	-.01687
1.543	5.012	-.01850	-.00181	-.23194	.10909	-.00146	-.00069	1.53460	3.54570	-.01691
1.543	6.009	-.01906	-.00144	-.28518	.13387	-.00083	-.00039	1.53625	3.55211	-.01488
1.543	7.005	-.01878	-.00115	-.33740	.15850	-.00353	-.00166	1.53575	3.55016	-.01561
1.543	8.012	-.02426	-.04005	-.39939	.18762	-.00685	-.00322	1.53557	3.54946	-.01559
GRADIENT	.00000	.00177	.04085	.01922	.0048	.00022	-.00015	-.000060	-.00010	

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM014) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1268/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD	MPROBE	CPM	CPTD	MPROBE	CPM	CPTD
.899	-8.003	-.02007	-.00617	-.30366	-.10477	-.00661	-.00228	.87208	1.64144	-.02977	.02249	1.65484	-.02249	.02245
.900	-6.980	-.01957	-.00574	-.26433	-.09065	-.00652	-.00224	.87974	1.66398	-.01619	.01619	1.66398	-.01619	.01619
.900	-5.993	-.01919	-.00537	-.22638	-.07710	-.00524	-.00178	.88489	1.6894	-.01144	.01144	1.67208	-.01144	.01144
.900	-4.992	-.01903	-.00502	-.18847	-.06390	-.00406	-.00138	.8894	1.67222	-.00540	.00540	1.68222	-.00540	.00540
.900	-3.988	-.01926	-.00470	-.14875	-.05014	-.00358	-.00121	.89502	1.68243	-.00514	.00514	1.68243	-.00514	.00514
.900	-2.991	-.01908	-.00436	-.10929	-.03682	-.00350	-.00118	.89514	1.68650	-.00237	.00237	1.68650	-.00237	.00237
.900	-1.995	-.01900	-.00403	-.07009	-.02354	-.00467	-.00157	.89737	1.68917	-.00124	.00124	1.68917	-.00124	.00124
.900	- .997	-.01892	-.00370	-.03222	-.01082	-.00502	-.00168	.89883	1.68946	-.00075	.00075	1.68946	-.00075	.00075
.900	.015	-.01876	-.00337	.00288	.00097	-.00475	-.00159	.89899	1.68946	-.00075	.00075	1.68946	-.00075	.00075
.900	1.007	-.01875	-.00306	.00407	.01344	-.00377	-.00126	.89896	1.68944	-.00076	.00076	1.68944	-.00076	.00076
.900	2.004	-.01879	-.00274	.07896	.02650	-.00261	-.00087	.89898	1.68944	-.00101	.00101	1.68944	-.00101	.00101
.900	3.006	-.01880	-.00242	.11768	.03948	-.00197	-.00066	.89893	1.68935	-.00093	.00093	1.68935	-.00093	.00093
.900	4.010	-.01867	-.00211	.15701	.05270	-.00240	-.00081	.89857	1.68868	-.00136	.00136	1.68868	-.00136	.00136
.900	5.008	-.01846	-.00181	.19574	.06574	-.00260	-.00087	.89768	1.68707	-.00219	.00219	1.68707	-.00219	.00219
.900	6.001	-.01836	-.00151	.23426	.07880	-.00206	-.00069	.89610	1.68417	-.00383	.00383	1.68417	-.00383	.00383
.900	7.005	-.02322	-.04050	.27278	.09197	-.00206	-.00069	.89388	1.68014	-.00619	.00619	1.68014	-.00619	.00619
.900	8.009	-.02399	-.04008	.30933	.10472	-.00221	-.00075	.88998	1.67310	-.01039	.01039	1.67310	-.01039	.01039
		GRADIENT	.00005	.00032	.03807	.01283	.00020	.00007	.00081	.00012	.000090	.000090	.000090	.000090

	RUN NO.	1264/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD	MPROBE	CPM	CPTD	MPROBE	CPM	CPTD
1.250	-7.999	-.01757	-.00582	-.28107	-.12412	-.00336	-.00237	1.22294	2.47503	-.03245	.02480	2.49522	-.03245	.02480
1.250	-6.982	-.01762	-.00551	-.24469	-.10727	-.00493	-.00216	1.22969	2.49522	-.03245	.02480	2.49522	-.03245	.02480
1.250	-5.996	-.01745	-.00519	-.20950	-.09130	-.00387	-.00169	1.23467	2.51018	-.01868	.01868	2.51018	-.01868	.01868
1.250	-4.981	-.01453	-.00464	-.17424	-.07549	-.00280	-.00121	1.23899	2.52324	-.01289	.01289	2.52324	-.01289	.01289
1.250	-3.991	-.01137	-.04386	-.13742	-.05930	-.00221	-.00095	1.24239	2.53354	-.00885	.00885	2.53354	-.00885	.00885
1.250	-2.990	-.01717	-.00426	-.10106	-.04346	-.00267	-.00115	1.24567	2.54354	-.00522	.00522	2.54354	-.00522	.00522
1.250	-1.990	-.01742	-.00398	-.06504	-.02793	-.00348	-.00150	1.24716	2.54809	-.00363	.00363	2.54809	-.00363	.00363
1.250	- .996	-.01649	-.00367	-.02959	-.01269	-.00388	-.00166	1.24745	2.54897	-.00259	.00259	2.54897	-.00259	.00259
1.250	.014	-.01680	-.00338	-.00400	-.00171	-.00329	-.00141	1.24854	2.55229	-.00184	.00184	2.55229	-.00184	.00184
1.250	1.010	-.01734	-.00308	-.03891	-.01667	-.00244	-.00104	1.24888	2.55332	-.00132	.00132	2.55332	-.00132	.00132
1.250	2.008	-.01833	-.00275	-.07449	-.03192	-.00185	-.00079	1.24848	2.55210	-.00165	.00165	2.55210	-.00165	.00165
1.250	3.025	-.01914	-.00239	-.11011	-.04720	-.00178	-.00076	1.24786	2.56020	-.00216	.00216	2.56020	-.00216	.00216
1.250	4.011	-.02324	-.04148	-.14650	-.06281	-.00184	-.00079	1.24768	2.54965	-.00242	.00242	2.54965	-.00242	.00242
1.250	5.017	-.01992	-.00168	-.18272	-.07837	-.00135	-.00058	1.24723	2.54831	-.00283	.00283	2.54831	-.00283	.00283
1.250	6.009	-.01860	-.00149	-.21973	-.09430	-.00088	-.00038	1.24696	2.54747	-.00335	.00335	2.54747	-.00335	.00335
1.250	7.007	-.01861	-.00117	-.25486	-.10968	-.00106	-.00046	1.24471	2.54060	-.00609	.00609	2.54060	-.00609	.00609
1.250	8.004	-.02432	-.04005	-.28835	-.12466	-.00080	-.00035	1.24113	2.52972	-.01062	.01062	2.52972	-.01062	.01062
		GRADIENT	-.00084	-.00018	.03540	.01524	.00012	.00005	.00083	.00012	.000090	.000090	.000090	.000090

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM014) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1258/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
ALPHA		BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
MACH										
1.400	-7.996	-.02247	-.00648	-.31124	-.14460	-.00454	-.00211	1.37202	2.95241	-.03261
1.400	-6.985	-.02120	-.00593	-.27278	-.12575	-.00364	-.00114	1.37892	2.97611	-.02454
1.400	-5.990	-.02127	-.00557	-.23411	-.10722	-.00248	-.00087	1.38459	2.99565	-.01784
1.400	-4.989	-.01860	-.04471	-.19425	-.08853	-.00191	-.00067	1.38911	3.01128	-.01285
1.399	-3.988	-.02194	-.00487	-.15307	-.06947	-.00148	-.00067	1.39140	3.01925	-.00891
1.400	-2.988	-.02090	-.00445	-.11281	-.05101	-.00221	-.00100	1.39561	3.03391	-.00504
1.400	-1.988	-.02019	-.00406	-.07322	-.03305	-.00327	-.00147	1.39722	3.03952	-.00327
1.399	-.990	-.01828	-.00369	-.03405	-.01535	-.00352	-.00159	1.39745	3.04032	-.00229
1.400	.018	-.01745	-.00338	-.00336	-.01515	-.00276	-.00125	1.39928	3.04673	-.00084
1.400	1.004	-.01802	-.00307	-.04173	-.01879	-.00200	-.00090	1.39886	3.04526	-.00094
1.400	2.005	-.01836	-.00275	-.08056	-.03631	-.00177	-.00080	1.39829	3.04328	-.00173
1.400	3.005	-.01860	-.00243	-.11976	-.05399	-.00198	-.00089	1.39819	3.04292	-.00190
1.400	4.023	-.01647	-.00226	-.16242	-.07317	-.00193	-.00087	1.39888	3.04533	-.00121
1.400	5.009	-.01676	-.00196	-.20163	-.09094	-.00140	-.00063	1.39793	3.04200	-.00244
1.400	6.011	-.01792	-.00156	-.24087	-.10876	-.00152	-.00069	1.39689	3.03836	-.00354
1.400	7.013	-.02297	-.04053	-.28009	-.12668	-.00200	-.00090	1.39582	3.03464	-.00510
1.400	8.005	-.01831	-.00090	-.31646	-.14363	-.00152	-.00069	1.39196	3.02117	-.00878
GRADIENT		.00038	.00249	.03920	.01775	.0002	.00001	.00094	.00329	.00108

RUN NO. 1226/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1226/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
ALPHA		BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
MACH										
1.450	-8.000	-.02045	-.00621	-.32427	-.15329	-.01064	-.00503	1.41808	3.11297	-.03677
1.451	-6.989	-.01976	-.00576	-.28261	-.13261	-.01033	-.00485	1.42534	3.13884	-.02896
1.450	-5.994	-.01990	-.00543	-.24302	-.11329	-.00859	-.00401	1.43017	3.15611	-.02241
1.450	-4.994	-.01877	-.00499	-.20317	-.09411	-.00764	-.00354	1.43612	3.17748	-.01588
1.450	-3.994	-.01842	-.00464	-.16040	-.07403	-.00717	-.00331	1.43910	3.18825	-.01220
1.450	-2.994	-.01856	-.00433	-.11990	-.0513	-.00720	-.00331	1.44117	3.19932	-.00845
1.450	-1.995	-.01673	-.04353	-.07893	-.03612	-.00739	-.00338	1.44677	3.21604	-.00366
1.450	-.986	-.01784	-.00368	-.03649	-.01667	-.00727	-.00332	1.44811	3.22089	-.00190
1.450	.024	-.01815	-.04297	-.00369	-.00168	-.00548	-.00250	1.45033	3.22895	-.00055
1.450	1.006	-.01757	-.00308	-.04600	-.02096	-.00409	-.00186	1.45054	3.22975	-.00074
1.450	2.010	-.01953	-.04234	-.08598	-.03933	-.00337	-.00154	1.44684	3.21626	-.00321
1.450	3.011	-.01891	-.00241	-.02731	-.05823	-.00363	-.00166	1.44773	3.21951	-.00303
1.450	4.012	-.01923	-.00207	-.17165	-.07843	-.00370	-.00169	1.44796	3.22035	-.00211
1.451	5.009	-.02186	-.04127	-.21263	-.09737	-.00256	-.00117	1.44687	3.21639	-.00412
1.450	6.011	-.01832	-.00151	-.25420	-.11635	-.00249	-.00114	1.44618	3.21387	-.00396
1.450	7.008	-.02306	-.04052	-.29523	-.13531	-.00340	-.00156	1.44531	3.21072	-.00520
1.450	8.004	-.02358	-.04015	-.33420	-.15364	-.00158	-.00073	1.44253	3.20064	-.00829
GRADIENT			-.00040	-.00009	-.04137	.01902	.00055	.00026	.00124	.00139

## PARAMETRIC DATA

	RUN NO.	1222/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	.000	PHI	=	180 .000
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
MACH	7.994	.00810	179.99120	.30390	.10292	.00717	.00243	.88998	1.67310					
.900	6.993	.00838	179.99130	.26589	.08970	.00684	.00231	.89405	1.68045					
.900	5.980	.00849	179.99150	.22548	.07583	.00585	.00197	.89665	1.68518					
.900	4.994	.00719	179.99180	.18933	.06357	.00406	.00136	.89827	1.68814					
.900	3.996	.00493	179.99230	.14923	.05006	.00374	.00125	.89895	1.68938					
.900	2.995	.00572	179.99240	.11042	.03706	.00420	.00141	.89970	1.69075					
.900	1.993	.00766	179.99210	.07136	.02394	.00433	.00145	.89917	1.68978					
.900	.990	.00782	179.99230	.03244	.01088	.00455	.00153	.89920	1.68985					
.900	-.028	.00806	179.99240	-.00417	-.00140	.00449	.00151	.89895	1.68938					
.900	-1.009	.00813	179.99250	-.03982	-.01336	.00285	.00096	.89859	1.68873					
.900	-2.006	.00947	1.95310	-.07796	-.02618	.00259	.00087	.89734	1.68645					
.900	-3.009	.00817	1.99280	-.11678	-.03931	.00294	.00099	.89547	1.68303					
.900	-4.012	.01098	179.95340	-.15618	-.05273	.00324	.00109	.89281	1.67821					
.900	-5.016	.00867	179.99310	-.19484	-.06603	.00315	.00107	.88902	1.67138					
.900	-6.009	.00877	179.99330	-.23259	-.07927	.00258	.00088	.88486	1.66393					
.900	-7.007	.01333	179.95410	-.27103	-.09286	.00234	.00080	.87898	1.65352					
.900	-8.006	.00813	179.99340	-.30779	-.10617	.00251	.00087	.87246	1.64209					
	GRADIENT			.00000	.00000	.00000	.00000	.00000	.00000					

	RUN NO.	1166/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	.000	PHI	=	180 .000
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
MACH	7.992	.00515	179.99160	.28131	.12168	.00687	.00297	.1.24057	2.52804					
1.250	6.991	.00569	179.99170	.24588	.10592	.00637	.00274	.1.24438	2.53959					
1.250	5.990	.00521	179.99180	.21050	.09041	.00525	.00226	.1.24671	2.54671					
1.250	5.001	.00252	179.99210	.17579	.07536	.00399	.00171	.1.24846	2.55206					
1.250	3.995	.00222	179.99220	.13863	.05937	.00335	.00143	.1.24869	2.55274					
1.250	2.979	.00419	179.99220	.10188	.04361	.00361	.00154	.1.24950	2.55524					
1.250	1.994	.00652	179.99220	.06558	.02808	.00402	.00172	.1.24902	2.55375					
1.250	.984	.00628	179.99230	.02975	.01274	.00434	.00186	.1.24882	2.55315					
1.250	-.009	.00712	179.99240	-.00363	-.00155	.00378	.00162	.1.24917	2.55423					
1.250	-.1.011	.00625	179.99250	-.03846	-.01647	.00298	.00128	.1.24878	2.55301					
1.250	-.2.010	.00738	179.99260	-.07294	-.03128	.00251	.00108	.1.24742	2.54888					
1.250	-.3.005	.00773	179.99280	-.10831	-.04658	.00259	.00111	.1.24533	2.54250					
1.250	-.4.012	.00925	179.99300	-.14559	-.06284	.00283	.00122	.1.24181	2.53178					
1.250	-.5.008	.00752	179.99300	-.18147	-.07865	.00219	.00095	.1.23873	2.52244					
1.250	-.6.005	.00868	179.99330	-.21849	-.09511	.00165	.00072	.1.23489	2.51083					
1.250	-.7.008	.00865	179.99340	-.25347	-.11111	.00176	.00077	.1.22900	2.49314					
1.250	-.8.021	.00829	179.99350	-.28804	-.12730	.00146	.00065	.1.22243	2.47352					
	GRADIENT			.00000	.00000	.00000	.00000	.00000	.00000					



1A310 (AEDC 161F-783) ELOW ANGULARITIES-FAIR OFF

(TCM015) ( 04 OCT 91 )

卷之三

PARAMETRIC DATA

RUN NO.	1278/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00
ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPTD
. 7.996	. 00599	179 99150	.34677	.15979	.01017	.00697
. 7.996	. 00613	179 99160	.30461	.14016	.00913	.00555
. 6.996	. 00694	179 99170	.26072	.11985	.00768	.00459
. 5.986	. 00603	179 99180	.21650	.09949	.00602	.00434
. 4.996	. 00615	179 99200	.16907	.07768	.00519	.00413
. 3.985	. 00640	179 99210	.12359	.05695	.00560	.00674
. 2.996	. 00649	179 99220	.08003	.03699	.00661	.00306
. 1.992	. 00646	179 99230	.03752	.01729	.00677	.00312
. 1.983	. 00675	179 99240	.00350	.00161	.00624	.00288
. -0.017	. 00634	179 99250	.04677	.02155	.00515	.00237
. -1.014	. 00639	179 99260	.08971	.04134	.00418	.00192
. -2.008	. 00620	179 99270	.-13309	.-06140	.00448	.00207
. -3.008	. 00538	179 99270	.-17705	.-08213	.00432	.00201
. -4.009	. 00557	179 99280	.-22206	.-10304	.00330	.00153
. -5.005	. 00563	179 99300	.-26565	.-12406	.00291	.00136
. -6.012	. 00749	179 99320	.-30812	.-14474	.00280	.00131
. -7.009	. 00634	179 99320	.-34875	.-16515	.00189	.00089
. -8.005	. 00000	179 99320	.00000	.00000	.00000	.00000
GRADIENT						

RUN NO.: 1241 / O RN/L = 2.49 GRADIENT INTERVAL = -5.00 / 5.00

## PARAMETRIC DATA

DIN DIN	1000/ 0	RN/1 - 2 50	GRADIENT INTERVAL	= - E 00/ E 00
			BETA	= .000 PHI = 180.000

BURN NO.: 1253/8 BN/L = 2.50 GRADIENT INTERVAL = -5.00/

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM016) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD
.900	7.989	.00754	179.99130	.30371	.10281	.00719	.00244	.89045
.900	6.987	.00826	179.99130	.26585	.08959	.00710	.00239	.89415
.900	5.990	.00792	179.99150	.22793	.07665	.00605	.00204	.89707
.900	4.994	.00797	179.99170	.18993	.06379	.00474	.00159	.89826
.900	3.996	.00774	179.99190	.14987	.05032	.00425	.00143	.89922
.900	2.984	.00761	179.99200	.11072	.03715	.00433	.00145	.89914
.900	1.992	.00778	179.99210	.07206	.02418	.00467	.00157	.89927
.899	.995	.00765	179.99230	.03319	.01113	.00466	.00156	.89866
.900	-.012	.00783	179.99240	-.00316	-.00106	.00462	.00155	.89918
.900	-.1.004	.00782	179.99250	-.03935	-.01321	.00312	.00105	.89825
.900	-.2.012	.00787	179.99270	-.07734	-.02598	.00262	.00088	.89711
.900	-.3.003	.00766	179.99280	-.11582	-.03902	.00271	.00091	.89558
.900	-.4.007	.00783	179.99290	-.15539	-.05251	.00296	.00100	.89261
.899	-.5.010	.00866	179.99310	-.19438	-.06585	.00268	.00091	.88796
.900	-.6.004	.00814	179.99320	-.23207	-.07910	.00210	.00071	.88381
.900	-.7.003	.00803	179.99330	-.27042	-.09276	.00198	.00068	.87730
.900	-.8.006	.00774	179.99340	-.30799	-.10637	.00198	.00068	.87142
		.00000	.00000	.00000	.00000	.00000	.00000	.00000
		GRADIENT						

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD
1.249	7.990	.00436	179.99170	.28156	.12166	.00662	.00286	.2.52873
1.250	6.984	.00476	179.99180	.24589	.10586	.00618	.00266	.2.54112
1.250	5.994	.00462	179.99190	.21061	.09046	.00517	.00222	.2.54634
1.250	4.989	.00198	179.99220	.17560	.07530	.00397	.00170	.2.54755
1.250	3.989	.00213	179.99220	.13847	.05933	.00322	.00138	.2.54858
1.250	2.993	.00534	179.99210	.10245	.04389	.00347	.00149	.2.54777
1.249	1.993	.00618	179.99220	.06607	.02831	.00384	.00164	.2.55032
1.250	.994	.00590	179.99230	.03003	.01287	.00413	.00177	.2.55059
1.250	-.015	.00621	179.99240	-.00349	-.00150	.00340	.00146	.2.55215
1.250	-1.007	.00558	179.99250	-.03810	-.01633	.00231	.00099	.2.55198
1.249	-2.011	.00652	179.99260	-.07330	-.03146	.00189	.00081	.2.54647
1.250	-3.017	.00752	179.99280	-.10853	-.04671	.00211	.00091	.2.54496
1.250	-4.008	.00909	179.99300	-.14544	-.06282	.00231	.00100	.2.53146
1.250	-5.009	.00595	179.99290	-.18159	-.07875	.00190	.00082	.2.52000
1.250	-6.006	.00655	179.99300	-.21820	-.09504	.00164	.00072	.2.51008
1.250	-7.009	.00710	179.99320	-.25336	-.11115	.00167	.00073	.2.49254
1.250	-8.017	.00778	179.99340	-.28782	-.12725	.00148	.00065	.2.47300
		GRADIENT						.00000

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM016) ( 04 OCT 91 )

卷之三

## PARAMETRIC DATA

RUN NO. 12278 BN/L = 2.50 GRADIENT INTERVAL = -5.00

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 452

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM017) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1223/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.900	-3.988	.02123	90.01819	.00499	.00168	-.14905	-.05010	.89660	1.68509	-.00320						
.900	-2.989	.02026	90.01817	.00509	.00171	-.11041	-.03708	.89810	1.68782	-.00200						
.899	-1.985	.01956	90.01814	.00520	.00175	-.07148	-.02397	.89852	1.68860	-.0104						
.900	- .993	.01929	90.01814	.00525	.00176	-.03360	-.01127	.89921	1.68986	-.00088						
.900	.017	.01857	90.01813	.00383	.00129	.00345	.00116	.89909	1.68964	-.00079						
.900	1.006	.01826	90.01813	.00352	.00118	.04141	.01389	.89887	1.68923	-.00099						
.900	2.005	.01774	90.01813	.00312	.00105	.07896	.02650	.89838	1.68833	-.00150						
.900	2.998	.01681	90.01814	.00335	.00113	.11729	.03939	.89735	1.68646	-.00237						
.900	3.995	.01603	90.01816	.00451	.00152	.15651	.05269	.89580	1.68364	-.00434						
.900	GRADIENT	-.00060	-.00000	-.00022	-.00007	.03810	.01281	-.00010	-.00018	-.00011						
MACH	BETA	RUN NO.	1168/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.250	-3.985	.01563	90.01820	.00450	.00193	-.13795	-.05925	1.24613	2.54493	-.00424						
1.250	-2.970	.02088	90.01817	.00477	.00205	-.10108	-.04337	1.24797	2.55055	-.00215						
1.250	-1.980	.01787	90.01814	.00503	.00216	-.06525	-.02737	1.24856	2.55234	-.00188						
1.250	-.992	.01702	90.01814	.00493	.00211	-.03049	-.01306	1.24840	2.55186	-.00148						
1.250	.016	.01757	90.01813	.00354	.00151	.00408	.00175	1.24899	2.55367	-.00110						
1.249	1.014	.01681	90.01813	.00256	.00109	.04010	.01716	1.24887	2.55331	-.00056						
1.250	2.004	.01658	90.01813	.00264	.00113	.07448	.03190	1.24893	2.55350	-.00125						
1.250	3.010	.01743	90.01814	.00324	.00139	.10985	.04709	1.24777	2.54992	-.00222						
1.250	3.995	.01808	90.01814	.00415	.00178	.14666	.06298	1.24624	2.54527	-.00399						
1.250	GRADIENT	-.00006	-.00001	-.00022	-.00009	.03545	.01521	.00002	.00006	.00005						
MACH	BETA	RUN NO.	1187/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.400	-3.988	.02441	90.01819	.00445	.00201	-.15409	-.06961	1.39607	3.03552	-.00409						
1.400	-2.991	.02356	90.01817	.00471	.00212	-.11403	-.05140	1.39850	3.04399	-.00176						
1.400	-1.984	.02215	90.01814	.00519	.00234	-.07410	-.03340	1.39864	3.04449	-.00161						
1.400	-.986	.01980	90.01814	.00473	.00213	-.03487	-.01571	1.39869	3.04466	-.00147						
1.400	.008	.01844	90.01813	.00301	.00136	.00320	.00144	1.40010	3.04959	-.00005						
1.400	1.004	.01869	90.01813	.00209	.00094	.04328	.01947	1.39965	3.04800	-.00013						
1.400	2.000	.01817	90.01813	.00273	.00123	.08176	.03686	1.39792	3.04195	-.00200						
1.400	3.006	.01766	90.01814	.00422	.00190	.12105	.05459	1.39800	3.04224	-.00230						
1.400	3.996	.01549	90.01814	.00473	.00214	.16252	.07337	1.39672	3.03779	-.00348						
1.400	GRADIENT	-.00104	-.00001	-.00013	-.00006	.03943	.01779	.00001	.00004	.00002						

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM017) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1201/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000	
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD	
1.450	-3.993	.02022	90.01819	.00948	.00436	-16158	-.07423	1.44312	3.20277	
1.449	-2.997	.01966	90.01817	.00916	.00420	-12053	-.05529	1.44396	3.20581	
1.450	-1.996	.01930	90.01814	.00904	.00413	-.07991	-.03654	1.44762	3.21909	
1.450	-1.003	.01883	90.01814	.00806	.00368	-.03762	-.01716	1.44919	3.22483	
1.450	.005	.01817	90.01813	.00608	.00277	.00366	.00167	1.45063	3.23005	
1.450	1.004	.01763	90.01813	.00473	.00215	.04732	.02153	1.45173	3.23408	
1.450	1.990	.01710	90.01813	.00439	.00201	.08744	.03996	1.44806	3.22071	
1.450	2.986	.01718	90.01814	.00542	.00248	.02836	.05873	1.44652	3.21510	
1.450	3.986	.01647	90.01814	.00630	.00288	.17356	.07937	1.44729	3.21792	
GRADIENT		-.00047	-.00001	-.00061	-.00028	.04189	.01918	.00047	.00169	.00052

RUN NO.	1280/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000	
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD	
1.473	-3.982	.01906	90.01819	.00671	.00309	-16929	-.07803	1.46856	3.29581	
1.473	-2.990	.01878	90.01817	.00686	.00316	-12379	-.05709	1.46800	3.29373	
1.473	-1.990	.01827	90.01814	.00748	.00346	-.08059	-.03726	1.46573	3.28539	
1.473	-.986	.01759	90.01814	.00783	.00361	-.03765	-.01736	1.46798	3.29368	
1.473	.017	.01724	90.01813	.00664	.00306	.00450	.00207	1.46892	3.29714	
1.473	1.010	.01608	90.01813	.00571	.00263	.04877	.02248	1.46848	3.29554	
1.473	2.000	.01629	90.01813	.00566	.00261	.09197	.04239	1.46884	3.29687	
1.473	3.001	.01505	90.01814	.00659	.00303	.13513	.06215	1.47003	3.30149	
1.473	3.991	.01388	90.01814	.00682	.00315	.17937	.08274	1.46803	3.29386	
GRADIENT		-.00062	-.00001	-.00010	-.00005	.04350	.02005	.00018	.00067	.00022

RUN NO.	1242/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000	
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD	
1.496	-3.987	.01919	90.01819	.00661	.00305	-18003	-.08324	1.49284	3.38627	
1.496	-2.990	.01891	90.01817	.00684	.00316	-13557	-.06263	1.49372	3.38960	
1.496	-1.985	.01779	90.01814	.00725	.00334	-.08993	-.04148	1.49515	3.39498	
1.496	-.989	.01791	90.01814	.00713	.00329	-.04160	-.01919	1.49526	3.39540	
1.496	.016	.01560	90.01813	.00564	.00260	.00525	.00242	1.49411	3.39108	
1.496	1.017	.01518	90.01813	.00488	.00225	.05299	.02447	1.49406	3.39088	
1.496	2.000	.01585	90.01813	.00470	.00217	.09866	.04553	1.49452	3.39260	
1.496	2.995	.01595	90.01814	.00576	.00265	.14369	.06625	1.49528	3.39546	
1.496	4.001	.01577	90.01814	.00603	.00278	.19107	.08816	1.49482	3.39374	
GRADIENT		-.00049	-.00001	-.00022	-.00010	.04666	.02154	.00017	.00064	.00016

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM017) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA = .000	PHI = 90.000
1.520	-3.987	.02267	90.01819	.00904	.00419	-.17924	-.08310	1.51959	3.48786	-.00572			
1.520	-2.985	.02148	90.01817	.00428	.00199	-.11429	-.05304	1.51861	3.48412	-.00682			
1.520	-1.990	.02064	90.01814	-.00149	-.00069	-.05012	-.02323	1.52028	3.49051	-.00541			
1.520	-.992	.01955	90.01814	.00065	.00030	-.02015	-.00935	1.51954	3.48764	-.00610			
1.520	.015	.01908	90.01813	.00136	.00063	.00595	.00276	1.51977	3.48854	-.00575			
1.520	1.004	.01840	90.01813	.00024	.00011	.03145	.01457	1.51980	3.48868	-.00544			
1.520	2.006	.01783	90.01813	.00275	.00128	.08145	.03782	1.51794	3.48153	-.00738			
1.520	3.001	.01743	90.01814	.00634	.00294	.13906	.06457	1.51829	3.48285	-.00744			
1.520	3.996	.01670	90.01814	.00656	.00305	.20198	.09380	1.51761	3.48025	-.00769			
	GRADIENT	-.00071	-.00001	.00007	.00003	.04341	.02015	-.00022	-.00085	-.00022			
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA = .000	PHI = 90.000
1.544	-3.987	.02297	90.01819	.00190	.00089	-.16163	-.07591	1.53606	3.55136	-.01537			
1.544	-2.979	.02163	90.01817	.00157	.00074	-.11157	-.05234	1.53734	3.55634	-.01413			
1.544	-1.989	.02094	90.01814	.00244	.00114	.06593	-.03095	1.53675	3.55404	-.01479			
1.543	-.991	.01998	90.01814	.00323	.00152	-.02521	-.01186	1.53458	3.54563	-.01693			
1.544	.017	.01966	90.01813	.00204	.00096	.00689	.00325	1.53342	3.54111	-.01884			
1.543	1.010	.01822	90.01813	.00029	.00013	.03887	.01831	1.53293	3.53922	-.01885			
1.544	2.000	.01769	90.01813	-.00176	-.00083	.07624	.03588	1.53406	3.54362	-.01774			
1.543	3.001	.01774	90.01814	-.00270	-.00127	.11788	.05547	1.53392	3.54306	-.01761			
1.543	3.995	.01618	90.01814	-.00134	-.00063	.16529	.07781	1.53345	3.54125	-.01830			
	GRADIENT	-.00079	-.00001	-.00062	-.00002	.03917	.01842	-.00046	-.00180	-.00050			

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM018) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1272 / O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000	
MACH	BETA	ALPHA	PHI	CPOQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
.900	-3.989	.02043	90.01819	.00535	.00180	-.14926	-.05020	.89673	1.68532	-.00340	
.900	-2.989	.01984	90.01817	.00554	.00186	-.11064	-.03716	.89791	1.68748	-.00202	
.900	-1.985	.01962	90.01814	.00572	.00192	-.07124	-.02392	.89923	1.68989	-.00113	
.900	-.993	.01897	90.01814	.00569	.00191	-.03402	-.01141	.89930	1.69002	-.00078	
.900	.016	.01844	90.01813	.00442	.00148	.00306	.00103	.89921	1.68985	-.00063	
.900	.899	1.005	.01758	90.01813	.00392	.00132	.04121	.01382	.89869	1.68891	-.00076
.900	2.005	.01709	90.01813	.00366	.00123	.07876	.02644	.89883	1.68917	-.00133	
.900	2.998	.01664	90.01814	.00397	.00133	.11705	.03932	.89764	1.68699	-.00226	
.900	4.000	.01562	90.01816	.00532	.00179	.15650	.05267	.89613	1.68424	-.00408	
GRADIENT		-.00059	-.00000	-.00018	-.00006	.03809	.01280	-.00008	-.00014	-.00006	

RUN NO. 1266 / O RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1266 / O	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	5.00
MACH	BETA	ALPHA	PHI	CPOQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.250	-3.985	.01574	90.01820	.00433	.00186	-.13797	-.05930	1.24570	2.54362	-.00478
1.250	-2.987	.01897	90.01817	.00453	.00194	-.10165	-.04358	1.24799	2.55062	-.00229
1.250	-1.986	.01726	90.01814	.00496	.00213	-.06586	-.02824	1.24791	2.55035	-.00233
1.250	-.981	.01710	90.01814	.00495	.00212	-.03022	-.01296	1.24809	2.55092	-.00223
1.250	.015	.01624	90.01813	.00380	.00163	.00412	.00177	1.24772	2.54978	-.00215
1.250	.008	.01566	90.01813	.00303	.00130	.03982	.01706	1.24849	2.55213	-.00150
1.250	2.003	.01572	90.01813	.00303	.00130	.07492	.03211	1.24803	2.55075	-.00208
1.250	2.999	.01645	90.01814	.00342	.00147	.10967	.04708	1.24688	2.54721	-.00351
1.250	4.000	.01680	90.01814	.00442	.00190	.14643	.06301	1.24498	2.54144	-.00587
GRADIENT		-.00013	-.00001	-.00015	-.00006	.03547	.01523	-.00009	-.00028	-.00011

	RUN NO.	1261 / O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	5.00
MACH	BETA	ALPHA	PHI	CPOQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.400	-3.988	.02348	90.01819	.00409	.00185	-.15411	-.06966	1.39661	3.03633	-.00456
1.400	-2.980	.02230	90.01817	.00436	.00197	-.11404	-.05142	1.39760	3.04085	-.00218
1.400	-.984	.02113	90.01814	.00505	.00228	-.07441	-.03355	1.39831	3.04333	-.00215
1.400	.019	.0186	90.01814	.00472	.00213	-.03524	-.01588	1.39846	3.04386	-.00177
1.400	.019	.01744	90.01813	.00326	.00147	-.00339	.00153	1.39955	3.04766	-.00094
1.400	1.008	.01771	90.01813	.00259	.00117	.04324	.01948	1.39879	3.04502	-.00112
1.400	2.000	.01710	90.01813	.00313	.00141	.08173	.03686	1.39761	3.04089	-.00249
1.400	3.001	.01555	90.01814	.00419	.00189	.12020	.05428	1.39699	3.03873	-.00363
1.400	4.001	.01486	90.01814	.00495	.00224	.16197	.07323	1.39558	3.03380	-.00484
GRADIENT		-.00106	-.00001	-.00005	-.00002	.03939	.01779	-.00010	-.00034	-.00009

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 456

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM018) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.449	-3.987	.01990	90.01819	.00880	.00404	-.16138	-.07414	1.44275	3.20145	-.00763
1.450	-2.980	.01946	90.01817	.00862	.00395	-.12058	-.05529	1.44466	3.20837	-.00567
1.450	-1.985	.01898	90.01814	.00861	.00393	-.07976	-.03646	1.44753	3.21878	-.00266
1.450	-.992	.01857	90.01814	.00793	.00362	-.03740	-.01707	1.44873	3.22314	-.00092
1.450	.016	.01773	90.01813	.00585	.00267	.00382	.00174	1.44951	3.22597	-.00024
1.450	1.009	.01717	90.01813	.00461	.00210	.04704	.02142	1.45126	3.23234	.00133
1.450	2.006	.01649	90.01813	.00462	.00211	.08748	.04003	1.44730	3.21794	-.00341
1.450	2.996	.01693	90.01814	.00551	.00252	.12859	.05887	1.44638	3.21462	-.00405
1.450	3.997	.01442	90.01814	.00612	.00280	.17291	.07923	1.44533	3.21079	-.00498
	GRADIENT	-.00060	-.00001	-.00052	-.00024	.04183	.01917	.00029	.00107	.00027

(TCM019) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.900	4.025	-.01137	-89.98788	-.00256	-.00086	1.4913	.05020	.89625	1.68445	-.00405
.900	3.016	-.01107	-89.98790	-.00348	-.00117	1.1067	.03717	.89756	1.68683	-.00232
.900	2.005	-.01059	-89.98792	-.00443	-.00149	.07195	.02415	.89881	1.68913	-.00131
.900	1.000	-.01016	-89.98793	-.00551	-.00185	.03396	.01140	.89914	1.68974	-.00085
.900	-.016	-.00973	-89.98793	-.00527	-.00177	-.00325	-.00109	.89909	1.68964	-.00067
.900	-.1.012	-.00938	-89.98793	-.00341	-.00114	-.04073	-.01366	.89893	1.68935	-.00082
.900	-.2.013	-.00884	-89.98793	-.00234	-.00079	-.07873	-.02643	.89874	1.68900	-.00131
.900	-.3.023	-.00835	-89.98792	-.00230	-.00077	-.11715	-.03934	.89774	1.68718	-.00209
.900	-.4.039	-.00801	-89.98790	-.00279	-.00094	-.15628	-.05259	.89635	1.68464	-.00389
	GRADIENT	-.00043	.00000	-.00015	-.00005	.03776	.01269	-.00001	-.00002	-.000002

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM019) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	RUN NO. 1169/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
		ALPHA	PHI												
1.250	4.023	.00472	-89.98788	-.00167	-.00072	-13920	.05974	1.24702	2.54766	-.00338					
1.250	3.010	-.00598	-89.98790	-.00263	-.00113	10282	.04406	1.24837	2.55177	.00185					
1.250	2.001	-.00777	-89.98792	-.00371	-.00159	.06675	.02860	1.24865	2.55263	.00149					
1.250	.995	-.00712	-89.98793	-.00465	-.00199	.03145	.01347	1.24853	2.55227	.00134					
1.250	-.013	-.00721	-89.98793	-.00364	-.00156	-.00330	-.00141	1.24913	2.55410	.00086					
1.250	-1.009	-.00657	-89.98793	-.00217	-.00093	.03868	-.01655	1.24928	2.55454	.00052					
1.250	-2.027	-.00788	-89.98793	-.00140	-.00060	-.07393	-.03167	1.24858	2.55240	.00143					
1.250	-3.024	-.00878	-89.98792	-.00137	-.00059	-.10863	-.04659	1.24738	2.54875	.00264					
1.250	-4.043	-.00725	-89.98790	-.00137	-.00059	-.14543	-.06253	1.24602	2.54461	-.00500					
GRADIENT		.00030	.00000	-.00020	-.00009	.03516	.01509	.00011	.00032	.00013					

MACH	BETA	RUN NO. 1188/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
		ALPHA	PHI												
1.400	4.025	-.01235	-89.98788	-.00156	-.00070	.15539	.07015	1.39708	3.03905	.00335					
1.400	3.024	-.01154	-89.98790	-.00214	-.00097	.11549	.05203	1.39840	3.04365	.00139					
1.399	2.004	-.01003	-89.98792	-.00399	-.00180	.07573	.03412	1.39812	3.04265	.00152					
1.399	.998	-.00824	-89.98793	-.00467	-.00210	.03603	.01623	1.39844	3.04380	.00111					
1.400	-.019	-.00742	-89.98793	-.00348	-.00157	-.00335	-.00151	1.39956	3.04770	.00019					
1.400	-1.004	-.00820	-89.98793	-.00220	-.00099	-.0192	-.01886	.139935	3.04697	.00020					
1.400	-2.024	-.00805	-89.98793	-.00175	-.00079	-.08100	-.03653	1.39790	3.04190	.00222					
1.400	-3.015	-.00750	-89.98792	-.00193	-.00087	-.11947	-.05391	1.39725	3.03960	.00294					
1.400	-4.035	-.00579	-89.98790	-.00196	-.00089	-.16127	-.07287	1.39618	3.03588	.00425					
GRADIENT		-.00070	.00000	-.00010	-.00004	.03911	.01765	.00011	.00038	.00014					

MACH	BETA	RUN NO. 1202/ 0		RN/L = 2.49	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
		ALPHA	PHI												
1.450	4.030	-.00921	-89.98788	-.00565	-.00260	.16314	.07493	1.44361	3.20456	-.00732					
1.450	3.019	-.00933	-89.98790	-.00617	-.00283	.12191	.05591	1.44446	3.20765	-.00588					
1.450	2.011	-.00928	-89.98792	-.00711	-.00325	.08135	.03719	1.44731	3.21798	-.00273					
1.450	1.005	-.00907	-89.98793	-.00691	-.00315	.03880	.01771	1.44953	3.22606	-.00073					
1.451	-.003	-.00840	-89.98793	-.00521	-.00238	-.00294	-.00134	1.45092	3.23111	.00040					
1.450	-1.001	-.00794	-89.98793	-.00376	-.00171	-.04570	-.02080	1.45172	3.23404	.00180					
1.450	-2.009	-.00827	-89.98793	-.00262	-.00120	-.08631	-.03946	1.44723	3.21771	-.00282					
1.450	-3.011	-.00679	-89.98792	-.00259	-.00118	-.12704	-.05814	1.44711	3.21724	-.00358					
1.450	-4.025	-.00705	-89.98790	-.00254	-.00116	-.17158	-.07856	1.44656	3.21526	-.00407					
GRADIENT		-.00032	.00000	-.00058	-.00027	.04151	.01902	.00036	.00037	.00131					

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 458

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM19) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1281/0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.473	4.024	-0.00935	-89.98788	-0.00294	-.00136	.17150	.07907	1.46848	3.29553	-.00762
1.473	3.007	-0.00958	-89.98790	-0.00373	-.00172	.12549	.05786	1.46802	3.29384	-.00766
1.473	2.004	-0.00895	-89.98792	-0.00538	-.00248	.08193	.03786	1.46601	3.28640	-.00977
1.473	.993	-0.00913	-89.98793	-0.00651	-.00300	.03867	.01784	1.46808	3.29404	-.00762
1.473	.010	-0.00787	-89.98793	-0.00574	-.00265	.00369	-.00170	1.46904	3.29760	-.00670
1.473	-1.012	-0.00830	-89.98793	-0.00453	-.00209	.04740	-.02184	1.46889	3.29703	-.00670
1.474	-2.014	-0.00814	-89.98793	-0.00364	-.00168	.09048	-.04168	1.46965	3.29985	-.00614
1.473	-3.021	-0.00697	-89.98792	-0.00352	-.00162	.13351	-.06146	1.46938	3.29882	-.00582
1.474	-4.040	-0.00721	-89.98790	-0.00302	-.00139	.17750	-.08185	1.46889	3.29705	-.00740
	GRADIENT	-0.00031	.00000	-.000010	-.00004	.04313	.01988	-.000023	-.00084	-.00024

RUN NO. 1243/0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.496	4.023	-0.00829	-89.98788	-0.00438	-.00203	.18281	.08449	1.49347	3.38866	-.00757
1.496	3.012	-0.00786	-89.98790	-0.00546	-.00253	.13754	.06361	1.49294	3.38667	-.00814
1.495	1.999	-0.00786	-89.98792	-0.00722	-.00333	.09107	.04199	1.49507	3.39466	-.00521
1.496	.996	-0.00756	-89.98793	-0.00735	-.00339	.04228	.01952	1.49453	3.39265	-.00627
1.496	.027	-0.00631	-89.98793	-0.00634	-.00292	.00532	-.00246	1.49485	3.39386	-.00558
1.496	-1.013	-0.00594	-89.98793	-0.00531	-.00245	.05181	-.02394	1.49367	3.38941	-.00699
1.496	-2.024	-0.00798	-89.98793	-0.00493	-.00228	.09797	-.04519	1.49532	3.39559	-.00515
1.496	-3.020	-0.00793	-89.98792	-0.00441	-.00203	.14177	-.06536	1.49546	3.39617	-.00460
1.496	-4.039	-0.00856	-89.98790	-0.00346	-.00160	.18788	-.08668	1.49533	3.39565	-.00530
	GRADIENT	-.00000	.00000	-.00022	-.00010	.04624	.02135	-.00024	-.00091	-.00032

RUN NO. 1289/0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.520	4.024	-0.1202	-89.98788	-0.0682	-.00317	.17035	.07909	1.51863	3.48417	-.00717
1.520	3.023	-0.1114	-89.98790	-0.0579	-.00269	.10966	.05092	1.51826	3.48276	-.00730
1.520	1.988	-0.1073	-89.98792	-0.0695	-.00322	.04566	.02117	1.51954	3.48765	-.00576
1.520	.994	-0.1044	-89.98793	-0.0607	-.00281	.01897	.00880	1.51952	3.48760	-.00619
1.520	.015	-0.00950	-89.98793	-0.0614	-.00285	.00659	-.00306	1.51957	3.48779	-.00595
1.520	-1.006	-0.00991	-89.98793	-0.0680	-.00315	.03408	-.01580	1.51946	3.48737	-.00594
1.520	-2.014	-0.00996	-89.98793	-0.0683	-.00317	.08694	-.04035	1.51929	3.48669	-.00679
1.519	-3.016	-0.00955	-89.98792	-0.00570	-.00265	.14637	-.06795	1.51791	3.48143	-.00717
1.520	-4.040	-0.00956	-89.98790	-0.00442	-.00206	.20791	-.09659	1.51813	3.48227	-.00782
	GRADIENT	-.000028	.00000	-.00016	-.00007	.04307	.02000	-.00006	.000023	.00007

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( TCMD19 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1256/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.543	4.023	-.01225	-89.98788	-.00485	-.00228	.15279	.07168	1.53671	3.55387	-.01447
1.544	3.016	-.01152	-89.98790	-.00639	-.00300	.10837	.05083	1.53749	3.55692	-.01400
1.543	2.004	-.01110	-89.98792	-.00731	-.00343	.06425	.03015	1.53635	3.55250	-.01459
1.543	.993	-.01058	-89.98793	-.00823	-.00387	.02427	.01142	1.53386	3.54284	-.01720
1.544	.016	-.01017	-89.98793	-.00734	-.00346	-.00793	-.00374	1.53297	3.53940	-.01879
1.544	-1.012	-.00994	-89.98793	-.00522	-.00246	-.03956	-.01865	1.53305	3.53969	-.01885
1.544	-2.025	-.00942	-89.98793	-.00357	-.00168	-.07884	-.03715	1.53341	3.54110	-.01851
1.544	-3.021	-.00887	-89.98792	-.00208	-.00098	-.12345	-.05815	1.53362	3.54190	-.01817
1.544	-4.040	-.00916	-89.98790	-.00071	-.00033	-.18374	-.08653	1.53357	3.54171	-.01812
GRADIENT		-.00040	.00000	-.00075	-.00035	.03958	.01861	.00051	.00198	.00061

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( TCMD20 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1273/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.900	4.025	-.01155	-89.98788	-.00197	-.00066	.14948	.05029	.89636	1.68466	-.00372
.900	3.016	-.01143	-89.98790	-.00292	-.00098	.11077	.03720	.89796	1.68758	-.00205
.900	1.999	-.01097	-89.98792	-.00399	-.00134	.07186	.02411	.89877	1.68905	-.00114
.900	.995	-.01076	-89.98793	-.00496	-.00166	.03406	.01143	.89943	1.69027	-.00083
.900	-.022	-.01008	-89.98793	-.00491	-.00165	-.00335	-.00112	.89911	1.68967	-.00056
.900	-1.012	-.00963	-89.98793	-.00296	-.00099	-.04079	-.01368	.89922	1.68988	-.00072
.900	-2.018	-.00911	-89.98793	-.00234	-.00079	-.07866	-.02638	.89868	1.68889	-.00099
.900	-3.018	-.00892	-89.98792	-.00194	-.00065	-.11692	-.03927	.89794	1.68754	-.00209
.899	-4.039	-.00840	-89.98790	-.00228	-.00077	-.15639	-.05258	.89597	1.68395	-.00368
GRADIENT		-.00041	.00000	-.00011	-.00004	.03779	.01270	.00003	.00006	-.00001

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM020) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1267/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/ 5.00	ALPHA	= .000	PHI	= -90.000	PARAMETRIC DATA				
													CPTD	CPBQ	CPBETA	MPROBE	CPM
1.249	4.020	- .00637	-89.98788	- .00138	CPAQ	CPALPH	CPBQ	.05954	1.24549	2.54299	- .00466						
1.250	3.018	- .00795	-89.98790	- .00228			.00059	.10249	.04397	2.54967	- .00296						
1.250	1.999	- .00886	-89.98792	- .00310			.00098	.06663	.02857	2.55169	- .00223						
1.250	.993	- .00848	-89.98793	- .00396			.00133	.00170	.01320	2.55049	- .00215						
1.250	.993	- .015	-89.98793	- .00312			.00134	.00361	.01155	2.54795	- .00219						
1.249	-1.016	- .00697	-89.98793	- .00202			.00087	.00087	.03917	2.54849	- .00116						
1.250	-2.017	- .00861	-89.98793	- .00138			.00059	.07419	.03181	2.54982	- .00237						
1.250	-3.025	- .00914	-89.98792	- .00133			.00057	.00057	.01912	2.54808	- .00327						
1.250	-4.044	- .00883	-89.98790	- .00146			.00063	.00063	.04683	2.54716	- .00586						
	GRADIENT	.00019	.00000	- .00013			.00006	.03516	.01510	.00009	.00008						
MACH	BETA	RUN NO.	1262/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/ 5.00									
1.400	4.019	- .01305	-89.98788	- .00060	CPAQ	CPALPH	CPBQ	.06998	1.39585	3.03475	- .00454						
1.400	3.006	- .01232	-89.98790	- .00129			.00027	.00027	.01148	1.39781	3.04158	- .00249					
1.400	1.998	- .01000	-89.98792	- .00271			.00122	.00122	.07560	1.39410	3.02463	- .00237					
1.400	.997	- .00860	-89.98793	- .00356			.00160	.00160	.03611	1.39628	3.04311	- .00208					
1.400	.020	- .00810	-89.98793	- .00262			.00118	.00118	.00296	1.39013	3.04435	- .00113					
1.400	-1.014	- .00863	-89.98793	- .00166			.00075	.00075	.04214	.01898	1.39908	- .00091					
1.400	-2.020	- .00891	-89.98793	- .00110			.00050	.00050	.08071	.03641	1.39772	- .00269					
1.400	-3.021	- .00739	-89.98792	- .00150			.00068	.00068	.11940	.05389	1.39720	- .00312					
1.400	-4.041	- .00549	-89.98790	- .00158			.00071	.00071	.16118	.07286	1.39545	- .00483					
	GRADIENT	- .00078	.00000	- .00001			.00000	.03905	.01764	.00006	.00004						
MACH	BETA	RUN NO.	1231/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/ 5.00									
1.450	4.014	- .01042	-89.98788	- .00631	CPAQ	CPALPH	CPBQ	.07488	1.44244	3.20034	- .00837						
1.450	3.013	- .00977	-89.98790	- .00655			.00030	.00030	.12235	.05614	1.44416	- .00632					
1.450	1.994	- .00972	-89.98792	- .00743			.00340	.00340	.08106	.03707	1.44741	- .00284					
1.450	.999	- .00954	-89.98793	- .00754			.00344	.00344	.03858	.01761	1.44908	- .00096					
1.450	.025	- .00919	-89.98793	- .00593			.00271	.00271	.00351	.00160	1.45089	- .0026					
1.450	-1.012	- .00858	-89.98793	- .00448			.00204	.00204	.04619	.02104	1.45076	- .00113					
1.450	-2.015	- .00909	-89.98793	- .00355			.00163	.00163	.08648	.03956	1.44791	- .00300					
1.450	-3.027	- .00898	-89.98792	- .00367			.00168	.00168	.12793	.05856	1.44669	- .00388					
1.450	-4.057	- .00985	-89.98790	- .00372			.00170	.00170	.17271	.07906	1.44629	- .00403					
	GRADIENT	- .00011	.00000	- .00049			.00003	.04158	.01906	.00042	.00044	- .00154					

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 461

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM021) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	11171/ O	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= .000	PHI	= .000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.300	.012	-.01780	-.00338	.00348	.00152	-.00400	-.00175	1.29590	2.70045	-.00457
1.300	-4.013	-.01557	-.00446	-.14099	-.06209	-.00345	-.00152	1.29100	2.68481	-.01025
GRADIENT		-.00055	.00027	.03589	.01580	-.00013	-.00006	.00122	.00388	.00141

RUN NO. 11175/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	11175/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= .000	PHI	= .000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.350	.017	-.01887	-.00337	.00458	.00204	-.00343	-.00152	1.34703	2.86783	-.00361
1.350	-4.028	-.01648	-.04421	-.14703	-.06578	-.00273	-.00122	1.34180	2.85039	-.00928
GRADIENT		-.00059	.01010	.03749	.01677	-.00017	-.00008	.00129	.00431	.00140

RUN NO. 12333/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	12333/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= .000	PHI	= .000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.470	.010	-.01693	-.00338	.00342	.00157	-.00562	-.00258	1.46782	3.29307	-.00785
1.470	-4.025	-.01757	-.00460	-.17124	-.07898	-.00419	-.00193	1.46434	3.28027	-.01200
GRADIENT		-.00016	.00030	.04329	.01997	-.00036	-.00016	.00086	.00317	.00103

RUN NO. 1245/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1245/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= .000	PHI	= .000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.519	.009	-.01828	-.00338	.00335	.00155	-.00365	-.00169	1.51923	3.48647	-.00629
1.519	-4.019	-.02043	-.00479	-.17917	-.08334	-.00839	-.00390	1.51533	3.47155	-.00985
GRADIENT		-.00053	.00035	.04531	.02107	-.00118	-.00055	.00097	.00371	.00088

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM022) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	11172/ O	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= .000	PHI	= 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.300	-.015	.00815	179.99240	-.00463	-.00203	.00462	.00203	1.29598	2.70071	-.00478
1.300	4.027	.00466	179.99210	-.14214	.06218	-.00449	.00197	1.29660	2.70269	-.00364
GRADIENT		-.00086	-.00007	.03631	.01589	-.00003	-.00001	.00015	.00049	.00028

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 462

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(TCM022) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	RN/L	= 2.50	GRADIENT INTERVAL	= -5.00/ 5.00	BETA = .000	PHI = 180.000	CP TD
1.350	-.014	.00915	179.99240	- .00468	- .00208	.00407	.00181	1.34662	2.86647	-.00347
		.00789	179.99180	.14742	.06548	.00390	.00173	1.34819	2.87174	-.00194
		-.00031	-.00015	.03776	.01677	-.00004	-.00002	.00039	.00131	.00038

MACH	ALPHA	BETA	PHI	RN/L	= 2.50	GRADIENT INTERVAL	= -5.00/ 5.00	BETA = .000	PHI = 180.000	CP TD
1.470	-.017	.00658	179.99240	- .00434	-.00199	.00601	.00276	1.46835	3.29503	-.00773
		.00644	179.99190	.17079	.07824	.00571	.00261	1.47044	3.30275	-.00517
		-.00003	-.00012	.04330	.01984	-.00007	-.00004	.00052	.00191	.00063

MACH	ALPHA	BETA	PHI	RN/L	= 2.50	GRADIENT INTERVAL	= -5.00/ 5.00	BETA = .000	PHI = 180.000	CP TD
1.519	-.016	.00783	179.99240	- .00929	-.00431	.00253	.00117	1.51908	3.48589	-.00644
		.00763	179.99190	.17129	.07942	.00764	.00354	1.51847	3.48357	-.00686
		-.00005	-.00012	.04472	.02073	.00126	.00059	-.00015	-.00057	-.00010

MACH	ALPHA	BETA	PHI	RN/L	= 2.50	GRADIENT INTERVAL	= -5.00/ 5.00	BETA = .000	PHI = 180.000	CP TD
1.520	-.016	.00859	179.99240	- .00946	-.00439	.00256	.00119	1.51885	3.48500	-.00669
		.00808	179.99180	.17150	.07951	.00721	.00334	1.51978	3.48857	-.00653
		-.00013	-.00015	.04481	.02077	.00115	.00053	.00023	.00088	.00004

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 463

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( TCM024 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1173/ 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.300	1.999	.01756	90.01813	.00369	.00161	.07569	.0312	1.29626	2.70159	-.00388
1.299	-2.029	.01833	90.01816	.00581	.00254	.06781	-.02966	1.29574	2.69994	-.00359

GRADIENT



IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(TCM026) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1293/ O	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA = .000	BETA = .000	CPALPH = .000	CPBQ = .000	CPALPH = .000	CPBQ = .000	CPALPH = .000	CPBQ = .000
MACH	PHI	ALPHA	BETA	CPAQ	CPALPH	CPBQ	CPALPH	CPBQ	CPALPH	CPBQ	CPALPH	CPBQ
.599	-1.983	-.01950	-.15943	-.00283	-.00056	-.00657	-.00130	.59899	1.27450	-.00022	1.27450	-.00011
.599	-1.746	-.01858	-.15953	-.00211	-.00042	-.00662	-.00130	.59914	1.27465	-.00075	1.27465	-.00021
.600	-1.508	-.01812	-.15969	-.00260	-.00051	-.00687	-.00136	.59918	1.27469	-.00060	1.27469	-.00021
.599	-1.271	-.01712	-.15972	-.00204	-.00040	-.00711	-.00140	.59981	1.27432	-.00052	1.27432	-.00021
.600	-.993	-.01643	-.15969	-.00212	-.00042	-.00686	-.00136	.59923	1.27473	-.00052	1.27473	-.00021
.600	-.716	-.01068	-.15981	-.00228	-.00045	-.00696	-.00138	.59961	1.27511	-.00053	1.27511	-.00021
.600	-.479	-.00989	-.15972	-.00205	-.00040	-.00662	-.00131	.59883	1.27434	-.00054	1.27434	-.00021
.600	-.241	-.01480	-.15976	-.00244	-.00048	-.00687	-.00136	.59918	1.27469	-.00062	1.27469	-.00021
.599	-.003	-.01389	-.15990	-.00205	-.00040	-.00694	-.00137	.59854	1.27405	-.00054	1.27405	-.00021
.600	.234	-.01335	-.16033	-.00190	-.00038	-.00676	-.00134	.59908	1.27458	-.00054	1.27458	-.00021
.599	.472	-.01278	-.15994	-.00184	-.00036	-.00685	-.00135	.59888	1.27439	-.00002	1.27439	-.00021
.600	.749	-.00678	-.15974	-.00215	-.00042	-.00685	-.00135	.59910	1.27460	-.00033	1.27460	-.00021
.599	.987	-.01128	-.16028	-.00227	-.00045	-.00689	-.00136	.59877	1.27427	-.00023	1.27427	-.00021
.600	1.224	-.01050	-.16034	-.00234	-.00046	-.00713	-.00141	.59900	1.27451	-.00054	1.27451	-.00021
.600	1.501	-.00939	-.16027	-.00223	-.00044	-.00696	-.00137	.59905	1.27456	-.00038	1.27456	-.00021
.599	1.739	-.00877	-.16047	-.00195	-.00038	-.00708	-.00140	.59917	1.27468	-.00018	1.27468	-.00021
.599	1.977	-.00824	-.16019	-.00162	-.00032	-.00661	-.00130	.59899	1.27450	-.00008	1.27450	-.00021
	GRADIENT	.00270	-.00022	.00012	.00002	-.00004	-.00001	-.00003	-.00003	-.00003	-.00003	-.00004

RUN NO. 1298/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1298/ O	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA = .000	BETA = .000	CPALPH = .000	CPBQ = .000	CPALPH = .000	CPBQ = .000	CPALPH = .000	CPBQ = .000
MACH	PHI	ALPHA	BETA	CPAQ	CPALPH	CPBQ	CPALPH	CPBQ	CPALPH	CPBQ	CPALPH	CPBQ
.900	-2.023	-.02078	-.12637	-.00168	-.00056	-.00501	-.00168	.89921	1.68986	-.00055	1.68986	-.00055
.900	-1.746	-.01476	-.12658	-.00166	-.00056	-.00504	-.00169	.89928	1.68998	-.00057	1.68998	-.00057
.900	-1.508	-.01952	-.12678	-.00167	-.00056	-.00497	-.00167	.89919	1.68982	-.00070	1.68982	-.00070
.900	-1.271	-.01391	-.12667	-.00164	-.00055	-.00496	-.00166	.89919	1.68981	-.00061	1.68981	-.00061
.900	-.993	-.01866	-.12695	-.00163	-.00055	-.00497	-.00167	.89945	1.69030	-.00061	1.69030	-.00061
.900	-.756	-.01274	-.12686	-.00155	-.00052	-.00502	-.00168	.89946	1.69032	-.00049	1.69032	-.00049
.900	-.518	-.01218	-.12706	-.00161	-.00054	-.00510	-.00171	.89930	1.69002	-.00076	1.69002	-.00076
.900	-.241	-.01162	-.12679	-.00156	-.00052	-.00503	-.00169	.89961	1.69059	-.00051	1.69059	-.00051
.900	-.003	-.01132	-.12723	-.00156	-.00052	-.00521	-.00175	.89922	1.68987	-.00065	1.68987	-.00065
.900	.234	-.01589	-.12728	-.00146	-.00049	-.00502	-.00168	.89902	1.68951	-.00064	1.68951	-.00064
.900	.472	-.01009	-.12720	-.00147	-.00049	-.00493	-.00165	.89948	1.69036	-.00051	1.69036	-.00051
.900	.709	-.01477	-.12688	-.00142	-.00048	-.00510	-.00171	.89934	1.69010	-.00060	1.69010	-.00060
.900	.987	-.00910	-.12724	-.00145	-.00049	-.00513	-.00172	.89932	1.69005	-.00053	1.69005	-.00053
.900	1.224	-.00847	-.12734	-.00136	-.00045	-.00512	-.00172	.89944	1.69029	-.00062	1.69029	-.00062
.900	1.462	-.01323	-.12743	-.00143	-.00048	-.00508	-.00171	.89941	1.69023	-.00064	1.69023	-.00064
.900	1.739	-.00745	-.12720	-.00139	-.00047	-.00516	-.00173	.89954	1.69045	-.00056	1.69045	-.00056
.900	1.977	-.00685	-.12735	-.00134	-.00045	-.00504	-.00169	.89928	1.68998	-.00065	1.68998	-.00065
	GRADIENT	.00257	-.00021	.00009	-.00003	-.00001	-.00003	-.00007	-.00007	-.00007	-.00007	-.00007

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 466

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(TCM026) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1304/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	BETA =	.000	CPTD
PHI	1.250	-1.983	-0.01652	-1.0184	-0.00107	-0.00046	-0.00352	-0.00151	1.24872	2.55286	-0.00139
MACH	1.250	-1.746	-0.01618	-1.0148	-0.00084	-0.00036	-0.00358	-0.00153	1.24867	2.55269	-0.00159
PHI	1.249	-1.508	-0.01592	-1.0147	-0.00071	-0.00031	-0.00359	-0.00154	1.24838	2.55182	-0.00133
MACH	1.250	-1.231	-0.01526	-1.0168	-0.00069	-0.00029	-0.00359	-0.00154	1.24862	2.55254	-0.00134
PHI	1.250	-1.250	-0.01514	-1.0123	-0.00059	-0.00025	-0.00356	-0.00153	1.24865	2.55262	-0.00143
MACH	1.249	-1.756	-0.01456	-1.0149	-0.00062	-0.00027	-0.00360	-0.00154	1.24848	2.55211	-0.00119
PHI	1.250	-5.18	-0.01391	-1.0140	-0.00058	-0.00025	-0.00357	-0.00153	1.24854	2.55229	-0.00145
MACH	1.250	-2.41	-0.01371	-1.0156	-0.00041	-0.00017	-0.00355	-0.00152	1.24856	2.55237	-0.00163
PHI	1.250	-0.003	-0.01300	-1.0198	-0.00038	-0.00016	-0.00361	-0.00155	1.24880	2.55308	-0.00132
MACH	1.250	.234	-0.01232	-1.0177	-0.00040	-0.00017	-0.00363	-0.00156	1.24886	2.55328	-0.00143
PHI	1.250	.472	-0.01273	-1.0209	-0.00040	-0.00017	-0.00353	-0.00151	1.24900	2.55369	-0.00137
MACH	1.250	.709	-0.01203	-1.0164	-0.00031	-0.00013	-0.00356	-0.00152	1.24893	2.55347	-0.00140
PHI	1.250	.987	-0.01094	-1.0164	-0.00030	-0.00013	-0.00353	-0.00151	1.24879	2.55305	-0.00140
MACH	1.250	1.224	-0.01145	-1.0156	-0.00029	-0.00013	-0.00354	-0.00152	1.24859	2.55245	-0.00138
PHI	1.250	1.501	-0.01024	-1.0171	-0.00025	-0.00011	-0.00358	-0.00153	1.24845	2.55202	-0.00135
MACH	1.250	1.739	-0.00988	-1.0191	-0.00031	-0.00013	-0.00357	-0.00153	1.24859	2.55244	-0.00142
PHI	1.250	1.977	-0.00925	-1.0187	-0.00029	-0.00012	-0.00361	-0.00155	1.24885	2.55324	-0.00138
MACH	1.250	GRADIENT	.00181	.00008	.00017	.00007	.00000	.00000	.00004	.00001	.00001

	RUN NO.	1310/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	BETA =	.000	CPTD
PHI	1.400	-2.023	-0.1846	-0.9477	-0.00067	-0.00030	-0.00363	-0.00164	1.39965	3.04801	-0.00043
MACH	1.400	-1.746	-0.1345	-0.9557	-0.00031	-0.00014	-0.00365	-0.00164	1.39946	3.04666	-0.00049
PHI	1.400	-1.508	-0.1322	-0.9542	-0.00036	-0.00016	-0.00359	-0.00161	1.39965	3.04802	-0.00057
MACH	1.400	-1.231	-0.1749	-0.9518	-0.00031	-0.00014	-0.00364	-0.00164	1.39965	3.04803	-0.00046
PHI	1.400	-0.993	-0.1190	-0.9500	-0.00031	-0.00014	-0.00359	-0.00162	1.39970	3.04817	-0.00041
MACH	1.400	-0.756	-0.1121	-0.9554	-0.00027	-0.00012	-0.00357	-0.00160	1.39964	3.04796	-0.00028
PHI	1.400	-0.518	-0.1104	-0.9536	-0.00026	-0.00012	-0.00357	-0.00161	1.39941	3.04717	-0.00039
MACH	1.400	-2.41	-0.1082	-0.9536	-0.00027	-0.00012	-0.00363	-0.00163	1.39972	3.04825	-0.00027
PHI	1.400	-0.003	-0.1075	-0.9530	-0.00021	-0.00009	-0.00359	-0.00162	1.39960	3.04785	-0.00037
MACH	1.400	-2.34	-0.1494	-0.9539	-0.00017	-0.00008	-0.00362	-0.00163	1.39915	3.04629	-0.00054
PHI	1.399	-4.72	-0.0989	-0.9518	-0.00022	-0.00010	-0.00354	-0.00159	1.39921	3.04648	-0.00031
MACH	1.400	-709	-0.0958	-0.9517	-0.00015	-0.00007	-0.00352	-0.00159	1.39940	3.04715	-0.00042
PHI	1.400	.987	-0.0846	-0.9542	-0.00015	-0.00007	-0.00363	-0.00164	1.39955	3.04767	-0.00051
MACH	1.400	1.224	-0.1355	-0.9528	-0.00016	-0.00007	-0.00349	-0.00157	1.39917	3.04631	-0.00050
PHI	1.400	1.462	-0.1316	-0.9554	-0.00020	-0.00009	-0.00354	-0.00159	1.39944	3.04727	-0.00050
MACH	1.400	1.739	-0.1287	-0.9568	-0.00010	-0.00004	-0.00357	-0.00160	1.39945	3.04733	-0.00040
PHI	1.399	1.977	-0.0689	-0.9539	-0.00016	-0.00007	-0.00360	-0.00162	1.39893	3.04550	-0.00053
MACH	1.399	GRADIENT	.00132	.00008	.00007	.00002	.00000	.00001	.00001	.00001	.00001

LA310 (AFDC 161F-783) PORT MUSOBENT-FAIRING QEE

卷之三

PARAMETRIC DATA

RUN NO.	1315/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00
MACH	PHI	ALPHA	BETA	CPAQ	CPALPH	CPBQ
1.545	-2.023	-.01785	-.13574	-.00045	-.00021	-.00494
1.545	-1.746	-.01723	-.13557	-.00038	-.00018	-.00499
1.545	-1.469	-.01646	-.13549	-.00023	-.00011	-.00490
1.545	-1.271	-.01584	-.13558	-.00014	-.00007	-.00518
1.544	-.993	-.01533	-.13569	-.00003	-.00001	-.00504
1.544	-.716	-.01468	-.13583	-.00005	-.00003	-.00500
1.544	-.479	-.01444	-.13582	-.00015	-.00007	-.00513
1.544	-.241	-.01369	-.13580	-.00010	-.00005	-.00516
1.544	-.003	-.01314	-.13594	-.00016	-.00007	-.00517
1.544	.234	-.01278	-.13606	-.00016	-.00007	-.00525
1.544	.511	-.01187	-.13625	-.00014	-.00007	-.00533
1.544	.749	-.01120	-.13577	-.00019	-.00009	-.00529
1.544	.987	-.01082	-.13596	-.00029	-.00014	-.00508
1.544	1.264	-.01037	-.13622	-.00034	-.00016	-.00515
1.544	1.462	-.00983	-.13614	-.00045	-.00021	-.00491
1.544	1.739	-.00921	-.13632	-.00046	-.00022	-.00501
1.544	1.977	-.00870	-.13620	-.00048	-.00022	-.00517
GRADIENT	.00228	-.00018	-.00022	-.00010	-.00003	-.00002
CPTD						
CPM						
MPROBE						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
CPOAQ						
CPAQB						
CPBTA						
CPBQ						
CPALPH						
					</	

## IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(TCM027) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1294/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	PARAMETRIC DATA		
						ALPHA	= -8.000	BETA
MACH	PHI							
.599	-2.006	-8.02527	.12048	-.33736	-.06795	.00198	.57103	1.24747
.599	-1.731	-8.02549	.08211	-.33665	-.06783	.00077	.57112	1.24755
.600	-1.496	-8.02588	.04864	-.33591	-.06779	-.00095	.57139	1.24780
.599	-1.222	-8.02604	.01006	-.33659	-.06779	-.00253	.57108	1.24752
.599	-986	-8.02607	.02288	-.33697	-.06780	-.00396	.57073	1.24719
.599	-751	-8.02605	.05626	-.33659	-.06784	-.00567	.57120	1.24763
.599	-477	-8.02557	.09447	-.33673	-.06784	-.00654	.57090	1.24735
.599	-241	-8.02532	.12786	-.33733	-.06794	-.00843	.57149	1.24791
.600	.006	-8.02475	.16086	-.33681	-.06804	-.00960	.57203	1.24841
.600	.229	-8.02409	.19434	-.33724	-.06803	-.01160	.57222	1.24859
.599	.504	-8.01775	.23263	-.33801	-.06813	-.01248	.57128	1.24770
.600	.739	-8.01699	.26558	-.33727	-.06804	-.01407	.57192	1.24831
.599	.974	-8.02099	.29903	-.33781	-.06808	-.01580	.57166	1.24806
.599	1.210	-8.01961	.33195	-.33784	-.06808	-.01734	.57128	1.24771
.599	1.445	-8.01798	.36491	-.33826	-.06816	-.01829	.57159	1.24799
.599	1.719	-8.01655	.40405	-.33842	-.06820	-.02067	.57176	1.24816
.599	1.955	-8.00942	.43675	-.33774	-.06808	-.02201	.57135	1.24777
	GRADIENT	.00332	.14073	-.00043	-.00010	-.00605	.00122	.00007
							.00017	.00016

RUN NO.	1300/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	PARAMETRIC DATA		
						ALPHA	= -8.000	BETA
MACH	PHI							
.900	1.967	-8.01720	.14726	-.30871	-.10659	.00313	.00108	.87179
.900	1.732	-8.02332	.11427	-.30922	-.10674	.00189	.00065	.87169
.900	1.496	-8.02369	.08112	-.30950	-.10682	.00094	.00032	.87184
.900	1.261	-8.02389	.04836	-.30947	-.10691	-.00018	.00006	.87179
.900	.987	-8.02405	.02411	-.30982	-.10701	-.00192	.00066	.87173
.900	.751	-8.02397	.05679	-.30993	-.10708	-.00337	.00116	.87187
.900	.516	-8.02394	.09550	-.30990	-.10702	-.00472	.00163	.87164
.900	.241	-8.02390	.081792	-.30985	-.10704	-.00595	.00206	.87177
.900	.006	-8.01792	.12870	-.30998	-.10708	-.00746	.00258	.87201
.900	.229	-8.02273	.16168	-.30993	-.10708	-.00865	.00299	.87182
.900	.504	-8.02211	.19989	-.30996	-.10705	-.00994	.00343	.87188
.900	.739	-8.02092	.23332	-.31003	-.10705	-.01139	.00393	.87156
.900	.974	-8.01992	.26692	-.30998	-.10707	-.01296	.00448	.87206
.900	1.210	-8.01869	.29441	-.30989	-.10701	-.01394	.00481	.87169
.900	1.445	-8.01776	.33247	-.30977	-.10701	-.01519	.00525	.87223
.900	1.719	-8.01598	.37144	-.30990	-.10700	-.01702	.00588	.87173
.900	1.955	-8.01427	.40338	-.30989	-.10701	-.01744	.00602	.87183
	GRADIENT	.00166	.14061	-.00022	-.00007	-.00542	-.00187	.00003
							.00007	.00006

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(TCM027) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO. 13111 / 0 RN/L = 2.50 GRADIENT INTERVAL = - 5.00/ 5.00

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

PAGE 470

(TCM027) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1316/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-8.000	BETA =	.000
PHI	ALPHA	BETA	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD	CPM	
1.543	-1.967	-8.01472	-13851	-.39748	-.18805	.00356	.00169	1.52898	3.52397	
1.544	-1.732	-8.02599	-10526	-.39738	-.18812	.00187	.00088	1.52953	3.52608	-0.02286
1.543	-1.497	-8.02630	.07240	-.39615	-.18796	.00002	.00001	1.52629	3.51360	-0.02539
1.544	-1.222	-8.02114	.03442	-.39620	-.18784	-.00074	-.00035	1.52784	3.51958	-0.02449
1.544	-987	-8.02109	.0022	-.39731	-.18834	-.00321	-.00152	1.52854	3.52226	-0.02428
1.543	-751	-8.02642	.03245	-.39778	-.18863	.00461	.00218	1.52645	3.51421	-0.02496
1.544	-477	-8.02627	.07062	-.39738	-.18850	-.00627	-.00297	1.52736	3.51773	-0.02507
1.543	-242	-8.02097	-.10411	-.39610	-.18794	-.00868	-.00412	1.52617	3.51314	-0.02524
1.545	-.006	-8.02032	-.13758	-.39796	-.18880	-.01026	-.00487	1.52826	3.52120	-0.02478
1.544	.229	-8.01979	-.17048	-.39653	-.18825	-.01209	-.00574	1.52661	3.51482	-0.02559
1.544	.464	-8.01913	-.20345	-.39617	-.18812	-.01384	-.00657	1.52668	3.51511	-0.02583
1.544	.739	-8.01806	-.24197	-.39686	-.18838	-.01558	-.00740	1.52696	3.51617	-0.02547
1.544	.974	-8.01671	-.27513	-.39546	-.18776	-.01721	-.00817	1.52609	3.51283	-0.02588
1.543	1.209	-8.01575	-.30821	-.39577	-.18789	-.01928	-.00915	1.52563	3.51105	-0.02623
1.544	1.445	-8.01451	-.34101	-.39545	-.18766	-.02075	-.00984	1.52656	3.51464	-0.02578
1.543	1.719	-8.01269	-.38002	-.39594	-.18790	-.02293	-.01088	1.52639	3.51399	-0.02586
1.544	1.994	-8.01076	-.41796	-.39551	-.18770	-.02434	-.01155	1.52654	3.51455	-0.02589
	GRADIENT	.00280	.00044	.00009	-.14060	-.00019	-.00341	-.00060	-.00030	-.00069

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

OCT 91

BUN NO.: 1301/0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/-5.00

## IA310 (AEDC 16TF-783) TABULATED DATA

IAA310 (AEADC 16TF-783) PORT MISORIENT-FAIRING OFF

PAGE 472

( TCM028 ) ( 04 OCT 91 )

RUN NO.	1307/ O	RN/L =	2 . 50	GRADIENT INTERVAL	=	- 5 . 00 /	5 . 00
MACH	PHI	ALPHA	BETA	CPAQ	CPALPH	CPBQ	CPTD
1 . 250	.04215	-.02006	-.00132	-.00057	-.06121	1 . 24563	.00502
1 . 250	.02240	-.02032	-.00013	-.00006	-.06133	1 . 24604	-.00491
1 . 249	.00570	-.02051	.000042	.00018	-.06130	1 . 24569	.00448
1 . 250	.01079	-.02012	.00059	.00025	-.06128	1 . 24586	-.00458
1 . 249	.03061	-.02025	.00145	.00062	-.06128	1 . 24563	-.00454
1 . 250	.04712	-.02060	.00213	.00091	-.06129	1 . 24603	-.00445
1 . 250	.06742	-.01967	.00280	.00120	-.06125	1 . 24632	-.00457
1 . 250	.08361	-.02595	.00356	.00153	-.06126	1 . 24575	-.00457
1 . 250	.10036	-.01506	.00412	.00177	-.06124	1 . 24606	-.00437
1 . 250	.11922	-.01774	.00447	.00192	-.06123	1 . 24658	-.00450
1 . 250	.13675	-.02266	.00550	.00236	-.06121	1 . 24610	-.00441
1 . 250	.15317	-.01734	.00624	.00268	-.06115	1 . 24626	-.00444
1 . 250	.16991	-.02177	.00658	.00283	-.06112	1 . 24600	-.00463
1 . 250	.18927	-.02086	.00726	.00312	-.06110	1 . 24650	-.00430
1 . 250	.20645	-.02037	.00810	.00348	-.06105	1 . 24641	-.00440
1 . 250	.22321	-.01383	.00872	.00375	-.06103	1 . 24602	-.00466
1 . 250	.24184	-.01312	.00903	.00388	-.06099	1 . 24643	-.00421
1 . 250	.00000	.00000	.00000	.00000	.00000	.00000	.00000
GRADIENT							

RUN NO	13112/8	BN/L =	2.49	GRADIENT INTERVAL	= -5.00/-5.00
--------	---------	--------	------	-------------------	---------------



	RUN NO.	1302/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00			
MACH	PHI	ALPHA	BETA	CPOA	CPALPH	CPBQ	CPBETA	CPBE	CPBM	CPTD
.900	88.026	.26248	3.97661	.00980	.00330	.15174	.05103	.89635	1.68464	.00353
.900	88.264	.24574	3.97248	.00841	.00283	.15183	.05108	.89660	1.68509	.00364
.900	88.502	.22930	3.97357	.00771	.00259	.15198	.05111	.89642	1.68476	.00351
.900	88.780	.20972	3.97453	.00743	.00250	.15194	.05111	.89672	1.68531	.00351
.900	89.018	.19332	3.98064	.00640	.00215	.15198	.05111	.89634	1.68461	.00360
.900	89.256	.17681	3.97613	.00596	.00201	.15209	.05115	.89662	1.68513	.00342
.900	89.534	.15754	3.98233	.00511	.00172	.15210	.05116	.89644	1.68480	.00361
.900	89.772	.14093	3.97812	.00444	.00149	.15208	.05116	.89659	1.68507	.00360
.900	90.011	.12459	3.95570	.00379	.00128	.15205	.05117	.89672	1.68530	.00365
.900	90.249	.10787	3.98271	.00344	.00116	.15214	.05117	.89626	1.68446	.00366
.900	90.487	.09128	3.98339	.00261	.00088	.15202	.05114	.89656	1.68502	.00361
.900	90.765	.07231	3.98406	.00164	.00055	.15200	.05113	.89625	1.68444	.00376
.900	91.043	.05279	3.97922	.00148	.00050	.15207	.05116	.89647	1.68485	.00371
.900	91.281	.03624	3.97950	.00086	.00029	.15213	.05118	.89626	1.68447	.00375
.900	91.519	.01973	3.98484	.00024	.00008	.15209	.05118	.89659	1.68508	.00376
.900	91.757	.00357	3.97973	.00086	.00029	.15216	.05120	.89658	1.68505	.00373
.900	92.035	.01617	3.97950	.00110	.00037	.15202	.05116	.89636	1.68465	.00389
.900				.00000	.00000			.00000	.00000	.00000
				.00000	.00000					

RUN NO. 1313/0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/-5.00

DATE 04 OCT 91

## IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(TCM029) (04 OCT 91)

## PARAMETRIC DATA

MACH	PHI	RUN NO.	1318/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	=	.000	BETA	=	4.000
1.543	88.025	27030	3.95282	CPAQ	.00616	CPALPH	.07527	CPBQ	1.52595	1.52595	CPTD	.02651	
1.543	88.263	25414	3.97519	.00385	.00183	.07586	.07586	.05292	1.52573	3.51144	.02657		
1.543	88.502	23764	3.97093	.00340	.00161	.07602	.07602	.05271	1.52638	3.51396	.02634		
1.543	88.740	22188	3.97724	.00296	.00141	.07592	.07592	.04405	1.52572	3.51139	.02650		
1.543	89.018	20165	3.97291	.00189	.00090	.07595	.07595	.02054	1.52563	3.51104	.02676		
1.544	89.256	18537	3.97404	.00113	.00054	.07603	.07603	.01610	1.52611	3.51292	.02678		
1.543	89.494	16934	3.97968	.00064	.00030	.07608	.07608	.01622	1.52567	3.51122	.02687		
1.543	89.772	14967	3.98109	-.00030	-.00014	.07594	.07594	.01014	1.52527	3.50967	.02694		
1.544	90.010	13279	3.95013	-.00061	-.00029	.07605	.07605	.01021	1.52644	3.51417	.02647		
1.543	90.288	11394	3.98056	-.00113	-.00054	.07592	.07592	.00546	1.52562	3.51103	.02682		
1.543	90.526	09676	3.98127	-.00178	-.00085	.07596	.07596	.00602	1.52617	3.51315	.02660		
1.544	90.764	08042	3.98184	-.00290	-.00138	.07590	.07590	.00138	1.52593	3.51223	.02704		
1.543	91.042	06095	3.98214	-.00334	-.00159	.07592	.07592	.00159	1.52564	3.51109	.02715		
1.543	91.280	04433	3.98239	-.00349	-.00166	.07585	.07585	.00166	1.52564	3.51110	.02676		
1.543	91.519	02799	3.98243	-.00512	-.00243	.07577	.07577	.00243	1.52571	3.51136	.02691		
1.543	91.757	01234	3.98266	-.00500	-.00237	.07585	.07585	.00237	1.52532	3.50987	.02690		
1.543	92.035	-00757	3.98263	-.00573	-.00272	.07587	.07587	.00272	1.52541	3.51020	.02700		
GRADIENT													
													.00000

MACH	ALPHA	BETA	PHI	RUN NO.	1351/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-4.000	PHI	=	180.000
5.98	-8.099	-3.75415	-154.47550	134901	-.0703	CPALPH	-.0717	CPBQ	-.03368	CPBETA	-.03368	.56651	1.24326	.02446	
6.00	-7.097	-3.74959	-151.38710	30430	-.06122	-.06122	-.06122	-.06122	-.03312	-.03312	.57439	1.25062	.01952		
5.99	-6.117	-3.76281	-147.50810	.26321	-.05271	-.05271	-.05271	-.05271	-.03291	-.03291	.57968	1.25566	.01529		
6.00	-5.142	-3.77434	-142.67870	.22040	-.04405	-.04405	-.04405	-.04405	-.03261	-.03261	.58476	1.26053	.01182		
6.00	-4.164	-3.78753	-136.50310	.17802	-.03547	-.03547	-.03547	-.03547	-.03219	-.03219	.58845	1.26411	.00889		
6.01	-3.198	-3.81922	-128.54730	.13634	-.02717	-.02717	-.02717	-.02717	-.03204	-.03204	.59204	1.26762	.00681		
6.01	-2.235	-3.85592	-118.49470	.09456	-.01881	-.01881	-.01881	-.01881	-.03220	-.03220	.59423	1.26978	.00504		
6.00	-1.264	-3.91403	-106.10850	.05132	-.01018	-.01018	-.01018	-.01018	-.03246	-.03246	.59571	1.27124	.00350		
6.01	-2.275	-3.98738	-92.02144	.00835	-.00166	-.00166	-.00166	-.00166	-.03301	-.03301	.59697	1.27248	.00312		
6.00	.716	-4.06529	-78.05354	.03343	-.00663	-.00663	-.00663	-.00663	-.03329	-.03329	.59645	1.27197	.00288		
6.00	1.739	-4.12861	-65.27127	.07750	.01534	-.17063	-.17063	-.17063	-.03377	-.03377	.59687	1.27239	.00231		
												.00133	.00133	.00107	

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM030) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.800	-8.063	-3.82245	-154.23800	-.33122	-.10064	-.16316	-.04958	.76657	1.47537	.03346
.799	-7.056	-3.82256	-151.07010	-.29023	-.08745	-.16028	-.04830	.77280	1.48425	.02631
.800	-6.067	-3.83122	-147.15070	-.24980	-.07494	-.15903	-.04771	.77880	1.49291	.02092
.800	-5.088	-3.83882	-142.28120	-.20920	-.06248	-.15780	-.04713	.78406	1.50059	.01597
.800	-4.103	-3.84903	-136.02570	-.16809	-.04999	-.15636	-.04650	.78811	1.50655	.01187
.800	-3.132	-3.87201	-128.02980	-.12835	-.03808	-.15540	-.04611	.79138	1.51140	.00895
.800	-2.158	-3.89493	-117.89720	-.08746	-.02587	-.15628	-.04623	.79358	1.51469	.00642
.800	-1.185	-3.93797	-105.51080	-.04651	-.01374	-.15736	-.04649	.79551	1.51758	.00480
.800	-1.188	-3.99598	-91.34415	-.00608	-.00180	-.15912	-.04695	.79616	1.51855	.00388
.800	.802	-4.05380	-77.41586	-.03475	-.01025	-.15998	-.04717	.79655	1.51914	.00338
.800	1.818	-4.10107	-64.71310	-.07667	-.02260	-.16234	-.04786	.79651	1.51907	.00336
	GRADIENT	-.04427	12.38597	.04137	.01226	-.00109	-.00025	.00138	.00206	.00142

RUN NO. 1329/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.900	-8.058	-3.80518	-154.27670	-.31638	-.1095	-.15534	-.05389	.86789	1.63416	.03488
.900	-7.048	-3.80408	-151.10880	-.27659	-.09527	-.15261	-.05257	.87428	1.64526	.02774
.899	-6.066	-3.81642	-147.19000	-.23800	-.08148	-.15259	-.05224	.87928	1.65405	.02186
.900	-5.081	-3.81971	-142.32010	-.19906	-.06784	-.15124	-.05155	.88463	1.66352	.01667
.900	-4.105	-3.83495	-136.06520	-.16002	-.04522	-.14959	-.05078	.88877	1.67093	.01234
.900	-3.133	-3.85041	-128.10870	-.12219	-.04132	-.14831	-.05015	.89166	1.67614	.00887
.900	-2.163	-3.88395	-117.93710	-.08364	-.02823	-.14883	-.05023	.89414	1.68062	.00657
.900	-1.192	-3.92722	-105.55070	-.04472	-.01506	-.14983	-.05046	.89542	1.68295	.00477
.900	-1.197	-3.98167	-91.38419	-.00577	-.00194	-.15179	-.05107	.89647	1.68486	.00369
.900	.789	-4.04253	-77.45616	-.03312	-.01114	-.15291	-.05142	.89694	1.68571	.00325
.900	1.806	-4.09838	-64.75342	-.07355	-.02472	-.15506	-.05212	.89664	1.68517	.00318
	GRADIENT	-.04624	12.41484	.03954	.01337	-.00104	-.00027	.00132	.00239	.00151

RUN NO. 1320/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.098	-8.001	-3.93643	-153.80230	-.28462	-.11692	-.14440	-.05932	.1.06876	2.05394	.03576
1.099	-6.974	-3.93075	-150.55380	-.24759	-.10108	-.14256	-.05820	.1.07557	2.07086	.02867
1.100	-5.985	-3.93047	-146.59370	-.21298	-.08649	-.14117	-.05732	.1.08185	2.08660	.02243
1.100	-4.996	-3.93218	-141.60430	-.17741	-.07163	-.14051	-.05673	.1.08644	2.09818	.01667
1.101	-4.007	-3.93479	-135.26900	-.14134	-.05686	-.13858	-.05575	.1.09014	2.10757	.01272
1.101	-3.022	-3.94138	-127.15320	-.10648	-.04269	-.13724	-.05503	.1.09279	2.11433	.00937
1.100	-2.040	-3.95194	-116.90140	-.07146	-.02857	-.13676	-.05468	.1.09466	2.11912	.00664
1.100	-1.036	-3.97021	-104.39540	-.03495	-.01394	-.13650	-.05447	.1.09605	2.12267	.00476
1.100	-.075	-3.99106	-90.50635	-.0103	-.00041	-.13722	-.05471	.1.09682	2.12467	.00389
1.100	.932	-4.01633	-76.30061	-.03466	-.01381	-.13688	-.05453	.1.09748	2.12635	.00309
1.100	1.936	-4.03897	-63.71753	-.07117	-.02835	-.13803	-.05498	.1.09708	2.12533	.00322
	GRADIENT	-.01593	11.58902	.03579	.01438	-.00031	-.00024	.00150	.00383	.00193

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 478  
( TCM030 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1365/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	-4.000	PHI	=	180.000
	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD				
MACH	1.249	-8.047	-154.07970	-29454	-13075	-14710	-06530	1.21852	2.46189	-0.03791			
	1.250	-7.037	-150.91140	-25772	-11358	-14330	-06315	1.22506	2.48135	-0.03023			
	1.250	-6.046	-146.99180	-22175	-09710	-14360	-06288	1.23062	2.49801	-0.02355			
	1.250	-5.062	-142.08240	-18645	-08120	-14226	-06195	1.23487	2.51080	-0.01805			
	1.250	-4.083	-135.82710	-14934	-06474	-14041	-06087	1.23931	2.52421	-0.01328			
	1.250	-3.106	-127.79100	-11310	-04889	-13955	-06032	1.24127	2.53015	-0.01045			
	1.250	-2.129	-117.57920	-07756	-03344	-13939	-06010	1.24307	2.53561	-0.00804			
	1.250	-1.148	-105.15270	-04179	-01800	-14002	-06029	1.24449	2.53993	-0.00658			
	1.250	-0.153	-91.02554	-00491	-00211	-14165	-06090	1.24571	2.54365	-0.00505			
	1.250	.842	-4.05151	-77.09720	-03102	-01333	-14221	-06110	1.24588	2.54417	-0.00452		
	1.250	1.853	-4.08848	-64.43430	-06855	-02946	-14370	-06174	1.24639	2.54573	-0.00440		
	GRADIENT	-0.3710	12.36312	.03665	.01583	.00063	.00018	.00119	.00363	.00150	.00177		

RUN NO. 1376/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1376/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA		CPALPH	CPBQ	CPBETA	MPROBE	CPTD
	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
MACH	1.400	-8.008	-153.72450	-32089	-15008	-16317	-07632	1.36593	2.9164	-0.03959				
	1.400	-7.026	-150.83230	-28367	-13160	-15785	-07323	1.37347	2.95740	-0.03106				
	1.400	-6.038	-146.95200	-24507	-11290	-15728	-07246	1.37971	2.97882	-0.02384				
	1.400	-5.051	-142.00290	-20487	-09390	-15658	-07177	1.38383	2.99303	-0.01868				
	1.400	-4.068	-135.74730	-16450	-07507	-15539	-07092	1.38761	3.00611	-0.01429				
	1.400	-3.089	-127.71120	-12476	-05674	-15520	-07058	1.39088	3.01744	-0.01073				
	1.400	-2.113	-117.49950	-08560	-03881	-15536	-07044	1.39380	3.02758	-0.00758				
	1.400	-1.135	-105.11250	-04564	-02065	-15591	-07053	1.39503	3.03190	-0.00548				
	1.400	-0.134	-90.94566	-00475	-00215	-15786	-07134	1.39585	3.03475	-0.00438				
	1.400	.856	-4.04867	-77.01733	-03561	-01608	-15852	-07160	1.39611	3.03564	-0.00397			
	1.400	1.871	-4.08645	-64.35434	-07743	-03496	-16031	-07238	1.39670	3.03770	-0.00350			
	GRADIENT	-0.3508	12.36185	.04072	.01851	.00087	.00027	.00143	.00499	.00177				

RUN NO. 1388/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1388/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA		CPALPH	CPBQ	CPBETA	MPROBE	CPTD
	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
MACH	1.449	-8.093	-154.43560	-34151	-16196	-16673	-07908	1.41459	3.10060	-0.04028				
	1.450	-7.082	-151.26800	-29880	-14066	-16353	-07698	1.42176	3.12606	-0.03244				
	1.450	-6.101	-147.38900	-25875	-12098	-16389	-07663	1.42779	3.14761	-0.02539				
	1.450	-5.120	-142.51960	-21687	-10092	-16303	-07587	1.43205	3.16288	-0.02058				
	1.450	-4.148	-136.34400	-17499	-08108	-16160	-07487	1.43566	3.17586	-0.01616				
	1.450	-3.177	-128.34840	-13398	-06183	-16210	-07481	1.43932	3.18906	-0.01213				
	1.450	-2.212	-118.21660	-09367	-04305	-16382	-07530	1.44253	3.20067	-0.00813				
	1.450	-1.242	-105.87010	-05169	-02370	-16527	-07579	1.44555	3.21157	-0.00555				
	1.450	-246	-91.74319	-00851	-00390	-16791	-07689	1.44676	3.21598	-0.00416				
	1.450	.742	-77.8.1483	-03440	-01574	-16958	-07761	1.44660	3.21540	-0.00375				
	1.450	1.764	-65.07208	-07917	.03623	-17190	-07867	1.44645	3.21484	-0.00375				
	GRADIENT	-0.5764	12.40073	.04301	.01983	.00181	.00068	.00185	.00669	.00210	.00177			

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM030) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1433/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	PARAMETRIC DATA	
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
1.471	-8.080	-3.78596	-154.35660	-35294	-16692	-17500	.08276	1.44283	3.20175
1.471	-7.070	-3.78521	-151.18870	-31111	-14698	-17226	.08138	1.44350	3.20415
1.471	-6.089	-3.79503	-147.30940	-27012	-12759	-17296	.08170	1.44365	3.20469
1.471	-5.106	-3.80326	-142.43990	-22509	-10490	-17115	.07976	1.45574	3.24869
1.470	-4.134	-3.82127	-136.22500	-18158	-08422	-16936	.07854	1.45942	3.26218
1.471	-3.162	-3.84011	-128.26850	-13897	-06426	-16836	.07785	1.46309	3.27568
1.470	-2.193	-3.88347	-118.09710	-09542	-04399	-16955	.07816	1.46520	3.28340
1.471	-1.225	-105.93071	-105.79000	-05267	-02425	-17018	.07834	1.46647	3.28809
1.470	-2.227	-3.99283	-91.62338	-00841	-00387	-17253	.07935	1.46728	3.29107
1.470	.765	-4.06610	-77.69502	.03586	.01647	-17498	.08038	1.46837	3.29513
1.470	1.785	-4.11787	-64.95248	.08180	.03755	-17773	.08160	1.46852	3.29567
GRADIENT	-.05268	12.38849	.04449	.02056	.00150	-.00056	.00144	.00532	.00166
RUN NO.		1400/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	PARAMETRIC DATA	
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
1.495	-8.080	-3.80059	-154.31740	-36300	-17305	-18131	.08644	1.46523	3.28353
1.495	-7.064	-3.79723	-151.14910	-32013	-15152	-17882	.08464	1.47114	3.30755
1.496	-6.080	-3.81015	-147.23020	-28051	-13187	-18154	.08534	1.47785	3.33023
1.495	-5.097	-3.81632	-142.36050	-23682	-11070	-18304	.08556	1.48239	3.34713
1.495	-4.121	-3.82877	-136.14510	-19118	-08902	-18219	.08483	1.48605	3.36082
1.495	-3.152	-3.85570	-128.14940	-14534	-06745	-18171	.08433	1.48885	3.37130
1.495	-2.183	-3.88925	-118.01730	-10107	-04678	-18228	.08437	1.49171	3.38203
1.496	-1.209	-3.93617	-105.63080	-05594	-02584	-18386	.08493	1.49369	3.38947
1.496	-.214	-3.99923	-91.50385	-00917	-00423	-18512	-.08542	1.49465	3.39311
1.496	.780	-4.06374	-77.53581	.03805	.01755	-18679	-.08612	1.49563	3.39678
1.495	1.800	-4.11757	-64.83281	.08619	.03972	-18784	-.08656	1.49560	3.39669
GRADIENT	-.05052	12.38791	.04677	.02170	-.00109	-.00036	.00163	.00613	.00177
RUN NO.		1421/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	PARAMETRIC DATA	
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
1.517	-8.074	-3.80132	-154.27730	-40408	-19352	-19784	-.09474	1.48663	3.36299
1.521	-7.062	-3.80034	-151.10940	-37957	-18174	-20899	-.10007	1.49184	3.38254
1.520	-6.081	-3.80878	-147.23010	-32926	-15754	-20903	-.10001	1.49087	3.37889
1.518	-5.103	-3.81869	-142.36070	-27729	-13257	-20664	-.09879	1.49008	3.37592
1.519	-4.122	-3.82800	-136.14510	-22622	-10563	-20851	-.09736	1.51178	3.45797
1.529	-3.154	-3.85533	-128.14940	-17289	-08189	-20867	-.09884	1.51144	3.45668
1.519	-2.182	-3.89088	-117.97770	-12177	-05689	-21125	-.09869	1.51111	3.45544
1.518	-1.207	-3.93225	-105.59100	-06777	-.03166	-21189	-.09900	1.51061	3.45353
1.518	-.213	-4.00012	-91.46117	-.01302	-.00608	-21242	-.09925	1.51049	3.45308
1.518	.779	-4.06468	-77.53580	.04133	.01931	-21840	-.10205	1.51057	3.45340
1.519	1.799	-4.11857	-64.83276	.09834	.04594	-22301	-.10419	1.51101	3.45505
GRADIENT	-.05076	12.38636	.05475	.02565	-.00233	-.00100	-.00017	-.00064	-.00014

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 480  
(TCM030) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.543	-8.078	-3.79860	-154.31170	-.41900	-.19923	-.20102	-.09558	1.52410	3.50517	-.02861
1.543	-7.069	-3.80553	-151.11000	-.35027	-.16616	-.19457	-.09230	1.52606	3.51272	-.02625
1.543	-5.101	-3.81837	-142.36070	-.24810	-.11726	-.18821	-.08896	1.52928	3.52512	-.02267
GRADIENT		.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

RUN NO.	1410/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -4.000	PHI	= 180.000	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.517	-8.074	-3.80024	-154.27720	-.40010	-.19230	-.19574	-.09408	1.48415	3.35372	-.04653
1.517	-7.066	-3.80216	-151.10960	-.36545	-.17540	-.19937	-.09568	1.48501	3.35703	-.04501
1.516	-6.081	-3.80794	-147.23000	-.32099	-.15416	-.20261	-.09731	1.48319	3.35013	-.04666
1.516	-5.103	-3.81812	-142.36070	-.27315	-.13115	-.20351	-.09772	1.48354	3.35144	-.04643
1.516	-4.124	-3.83379	-136.10570	-.22266	-.10687	-.20431	-.09806	1.48433	3.35439	-.04606
1.517	-3.155	-3.85451	-128.14940	-.17008	-.08162	-.20628	-.09899	1.48454	3.35519	-.04594
1.516	-2.182	-3.89069	-117.97760	-.11866	-.05695	-.21007	-.10082	1.48423	3.35402	-.04621
1.516	-1.210	-3.93659	-105.63090	-.06558	-.03148	-.21468	-.10305	1.48377	3.35228	-.04657
1.517	-2.11	-4.00099	-91.46417	-.01011	-.00475	-.21781	-.10229	1.50487	3.43170	-.02375
1.516	.780	-4.05926	-77.53587	.04550	.02136	-.21939	-.10299	1.50364	3.42707	-.02368
1.516	1.798	-4.11342	-64.83293	.09909	.04653	-.21627	-.10154	1.50302	3.42472	-.02402
GRADIENT		-0.04923	12.37846	.05451	.02602	-.00252	-.00072	.00417	.01569	.00483

RUN NO.	1411/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -4.000	PHI	= 180.000	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.542	-8.071	-3.80191	-154.27740	-.41451	-.19707	-.20084	-.09549	1.52347	3.50276	-.02918
1.543	-7.065	-3.80262	-151.10970	-.34907	-.16552	-.19395	-.09197	1.52606	3.51270	-.02651
1.542	-6.079	-3.80855	-147.23000	-.29966	-.14193	-.19091	-.09042	1.52676	3.51541	-.02555
1.542	-5.097	-3.81517	-142.36040	-.24799	-.11718	-.18937	-.08948	1.52822	3.52106	-.02320
1.543	-4.125	-3.83137	-136.14530	-.19432	-.09180	-.18646	-.08809	1.52949	3.52593	-.02286
1.542	-3.153	-3.85461	-128.14940	-.14365	-.06782	-.18310	-.08645	1.52989	3.52749	-.02224
1.542	-2.182	-3.88421	-118.01710	-.09612	-.04534	-.17774	-.08384	1.53050	3.52986	-.02135
1.542	-1.210	-3.93594	-105.63080	-.05134	-.02420	-.17109	-.08066	1.53120	3.53255	-.02064
1.542	-2.113	-3.99905	-91.50385	-.00807	-.03380	-.16985	-.08003	1.53160	3.53410	-.02008
1.543	.781	-4.06325	-77.53583	.03636	.01713	-.17578	-.08282	1.53184	3.53503	-.02002
1.543	1.797	-4.11890	-64.87250	.08691	.04094	-.18480	-.08704	1.53259	3.53792	-.01964
GRADIENT		-.05058	12.37958	.04679	.02208	-.00097	.00052	.00200	.00056	.00056

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

( TCM032 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1352/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -3.000	PHI	= 180.000
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD	CPM	CPM
.599	-8.031	-2.79357	-160.07840	-34159	-06895	-12698	-02563	.56949	1.24603	-.02320
.600	-7.070	-2.74075	-157.94740	-30096	-06048	-12170	-02446	.57593	1.25209	-.01834
.600	-6.088	-2.74655	-154.70960	-25907	-05192	-12077	-02420	.58214	1.25801	-.01402
.600	-5.106	-2.75394	-150.48110	-21613	-04312	-11903	-02375	.58734	1.26302	-.00984
.601	-4.134	-2.76446	-144.82690	-17440	-03480	-11848	-02364	.59105	1.26665	-.00770
.601	-3.169	-2.78715	-136.99520	-13326	-02652	-11845	-02357	.59404	1.26959	-.00525
.601	-2.214	-2.82661	-126.07700	-09171	-01822	-11887	-02362	.59613	1.27165	-.00364
.601	-1.261	-2.88467	-111.28230	-05059	-01004	-11990	-02381	.59802	1.27353	-.00237
.601	-.285	-2.98352	-92.88884	-00954	-00189	-12309	-02443	.59849	1.27400	-.00200
.600	.713	-3.08505	-74.41705	.03226	.00639	-12656	-02506	.59881	1.27432	-.00121
.601	1.751	-3.16663	-58.67409	.07711	.01529	-12970	-02572	.59891	1.27442	-.00153
	GRADIENT	-.07180	15.25764	.04270	.00850	-.00199	-.00037	.00129	.00128	.00103

	RUN NO.	1342/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -3.000	PHI	= 180.000
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD	CPM	CPM
.799	-8.047	-2.86094	-159.96150	-32783	-09924	-12371	-03745	.76817	1.47764	-.03096
.800	-7.036	-2.81585	-157.63110	-28647	-08621	-11996	-03610	.77516	1.48765	-.02436
.800	-6.046	-2.81720	-154.35300	-24684	-07392	-11745	-03517	.78188	1.49739	-.01838
.800	-5.059	-2.82375	-150.04480	-20584	-06129	-11629	-03463	.78633	1.50392	-.01344
.800	-4.081	-2.83092	-144.31090	-16524	-04905	-11524	-03420	.79051	1.51011	-.00964
.800	-3.109	-2.84635	-136.39950	-12561	-03719	-11533	-03414	.79359	1.51470	-.00676
.800	-2.144	-2.86982	-125.40150	-08581	-02533	-11486	-03390	.79551	1.51758	-.00439
.800	-1.182	-2.91763	-110.44810	-04568	-01347	-11571	-03411	.79699	1.51979	-.00306
.800	-.200	-2.98914	-92.01471	-00584	-00172	-11814	-03479	.79790	1.52117	-.00203
.800	.797	-3.06922	-73.58255	.03360	.00990	-12019	-03540	.79849	1.52205	-.00178
.800	1.824	-3.12707	-57.99852	.07613	.02241	-12267	-03611	.79811	1.52149	-.00175
	GRADIENT	-.05301	15.22813	.04086	.01209	-.00129	-.00033	.00127	.00190	.00130

	RUN NO.	1330/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -3.000	PHI	= 180.000
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD	CPM	CPM
.900	-8.078	-2.84556	-160.08070	-31395	-10863	-11788	-04079	.86986	1.63757	-.03246
.900	-7.025	-2.79742	-157.66980	-27363	-09401	-11301	-03883	.87636	1.64889	-.02527
.899	-6.037	-2.79972	-154.39180	-23555	-08044	-11215	-03830	.88173	1.65837	-.01927
.900	-5.053	-2.80749	-150.08390	-19647	-06677	-11076	-03764	.88696	1.66766	-.01394
.900	-4.082	-2.81916	-144.35040	-15757	-05338	-10972	-03717	.89078	1.67454	-.01024
.900	-3.110	-2.83347	-136.43900	-11995	-04051	-10953	-03699	.89376	1.67992	-.00706
.900	-2.146	-2.85580	-125.44110	-08137	-02741	-10960	-03692	.89598	1.68397	-.00455
.900	-1.188	-2.90270	-110.52750	-04381	-01474	-11003	-03701	.89746	1.68665	-.00303
.900	-.208	-2.98169	-92.05467	-00541	-00182	-11238	-03777	.89804	1.68764	-.00230
.900	.783	-3.06109	-73.66231	.03217	.01080	-11467	-03850	.89826	1.68826	-.00170
.899	1.810	-3.12306	-58.03871	.07259	.02434	-11723	-03931	.89772	1.68713	-.00144
	GRADIENT	-.05457	15.26038	.03907	.01319	-.00130	-.00038	.00116	.00211	.00143

## PARAMETRIC DATA

	RUN NO.	1321/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	-3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPI	CPTD	
1.099	-8.036	-2.97406	-159.64690	-28284	-11605	-11068	-04541	1.07165	2.06110	-03372	
1.100	-6.965	-2.93018	-157.07640	-24570	-10012	-10619	-04327	1.07895	2.07932	-02600	
1.100	-5.978	-2.92977	-153.71840	-21119	-08555	-10512	-04258	1.08408	2.09220	-01987	
1.101	-4.983	-2.92963	-149.29040	-17549	-07073	-10418	-04199	1.08865	2.10379	-01449	
1.100	-3.997	-2.93475	-143.39750	-14002	-05618	-10287	-04128	1.09177	2.11173	-01028	
1.100	-3.011	-2.93239	-135.36640	-10548	-04218	-10200	-04078	1.09426	2.11810	-00691	
1.100	-2.033	-2.94172	-124.16980	-06993	-02790	-10098	-04029	1.09635	2.12347	-00457	
1.100	-1.052	-2.95445	-109.05750	-03461	-01378	-10054	-04005	1.09760	2.12666	-00297	
1.099	-0.054	-2.98790	-90.58440	-00012	-00005	-10105	-04020	1.09771	2.12694	-00209	
1.100	.925	-3.02227	-72.43008	-03315	.01318	-10158	-04039	1.09862	2.12929	-00145	
1.100	1.921	-3.05772	-57.04480	-06928	.02755	-10278	-04087	1.09856	2.12913	-00142	
	GRADIENT	-0.1829	13.89322	.03540	.01419	.00024	.00017	.00139	.00356	.00183	

RUN NO. 1366/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1366/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	-3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPI	CPTD	
1.250	-8.037	-2.84773	-160.11760	-29138	-12906	-10790	-04779	1.22140	2.47045	-03527	
1.250	-7.016	-2.85175	-157.43320	-25548	-11232	-10641	-04678	1.22685	2.48670	-02784	
1.250	-6.028	-2.85129	-154.15500	-21994	-09602	-10623	-04638	1.23276	2.50441	-02063	
1.250	-5.043	-2.85568	-149.84670	-18354	-07969	-10471	-04546	1.23744	2.51853	-01495	
1.250	-4.065	-2.86616	-144.03340	-14690	-06359	-10299	-04458	1.23983	2.52577	-01204	
1.250	-3.086	-2.87334	-136.12160	-11160	-04817	-10240	-04419	1.24308	2.53565	-00874	
1.250	-2.115	-2.89434	-125.04420	-07612	-03275	-10215	-04394	1.24521	2.54212	-00569	
1.250	-1.149	-2.93569	-110.05100	-04069	-01748	-10241	-04399	1.24675	2.54682	-00410	
1.250	-1.160	-2.99506	-91.57785	-00481	-00207	-10444	-04482	1.24719	2.54818	-00319	
1.250	.833	-3.06512	-73.22490	-03038	-01303	-10592	-04543	1.24780	2.55004	-00257	
1.250	1.859	-3.11563	-57.68053	-06739	-02890	-10827	-04644	1.24788	2.55026	-00265	
	GRADIENT	-0.4479	15.18610	.03621	.01562	.00092	.00033	.00129	.00392	.00156	

RUN NO. 1377/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1377/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	-3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPI	CPTD	
1.400	-8.024	-2.86419	-160.03860	-31969	-14915	-11848	-05528	1.36830	2.93972	-03697	
1.400	-7.012	-2.85872	-157.43310	-28143	-13021	-11668	-05398	1.37610	2.96642	-02819	
1.400	-6.022	-2.86229	-154.11530	-24267	-11153	-11562	-05313	1.38193	2.98645	-02132	
1.400	-5.035	-2.86913	-149.76740	-20176	-09227	-11530	-05273	1.38632	3.00161	-01630	
1.400	-4.052	-2.87465	-143.99360	-16271	-07410	-11454	-05216	1.38990	3.01402	-01202	
1.400	-3.074	-2.88562	-136.04230	-12296	-05576	-11432	-05184	1.39288	3.02441	-00794	
1.400	-2.101	-2.90435	-124.92500	-08376	-03789	-11352	-05135	1.39488	3.03135	-00549	
1.400	-1.133	-2.93580	-109.93160	-04407	-01990	-11360	-05132	1.39640	3.03666	-00397	
1.400	-1.146	-2.99563	-91.45856	-00460	-00208	-11575	-05224	1.39755	3.04066	-00307	
1.400	.846	-3.05551	-73.10570	-03464	-01562	-11747	-05298	1.39740	3.04017	-00250	
1.400	1.876	-3.10554	-57.52173	-07605	-03429	-12045	-05431	1.39768	3.04113	-00213	
	GRADIENT	-0.0408	15.19429	.04027	.01827	.00096	.00035	.00127	.00442	.00155	

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM032) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1389/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	CPROBE	CPTD		
1.450	-8.066	-2.75756	-160.43320	-33789	-15982	-12215	-0.5778	1.41771	3.11165	-0.3731		
1.451	-7.052	-2.75815	-157.82840	-29611	-13906	-12114	-0.5689	1.42458	3.13614	-0.2983		
1.450	-6.070	-2.76092	-154.59040	-25679	-11975	-11900	-0.5549	1.43008	3.15581	-0.2275		
1.450	-5.086	-2.76825	-150.32220	-21337	-09908	-11916	-0.5534	1.430416	3.17045	-0.1838		
1.450	-4.118	-2.78078	-144.62840	-17309	-08000	-11919	-0.5509	1.43804	3.18443	-0.1365		
1.449	-3.146	-2.80053	-136.75700	-13361	-06143	-11919	-0.5480	1.44192	3.19843	-0.0846		
1.450	-2.194	-2.83566	-125.83870	-09210	-04224	-11871	-0.5444	1.44502	3.20965	-0.0571		
1.450	-1.241	-2.89913	-110.96550	-05051	-02314	-11957	-0.5479	1.44561	3.21181	-0.0492		
1.450	-0.259	-2.98959	-92.53172	-00842	-00385	-12262	-0.5615	1.44596	3.21309	-0.0432		
1.450	.741	-3.08992	-74.09941	.03338	.01527	-12591	-0.5760	1.44692	3.21658	-0.0332		
1.450	1.777	-3.16491	-58.43565	.07771	.03551	-13011	-0.5945	1.44831	3.22162	-0.0204		
GRADIENT		-0.06896	15.24699	.04272	.01965	.00184	-.00075	.00152	.00551	.00169		

RUN NO. 1434/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1434/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA		CPALPH	CPBQ	CPBETA	CPM
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	CPROBE	CPTD		
1.470	-8.056	-2.77818	-160.35430	-35015	-16596	-12885	-0.6107	1.44028	3.19252	-0.3912		
1.471	-7.049	-2.77384	-157.78890	-30964	-14548	-12664	-0.5950	1.44859	3.22264	-0.2993		
1.471	-6.062	-2.78458	-154.47180	-26715	-12470	-12540	-0.5853	1.45467	3.24478	-0.2311		
1.471	-5.079	-2.78690	-150.24300	-22319	-10371	-12379	-0.5752	1.45815	3.25752	-0.1871		
1.471	-4.102	-2.79928	-144.50940	-17977	-08320	-12334	-0.5709	1.46211	3.27206	-0.1468		
1.470	-3.136	-2.81642	-136.67760	-13686	-06312	-12242	-0.5646	1.46482	3.28203	-0.1142		
1.470	-2.174	-2.84847	-125.67980	-09387	-04321	-12298	-0.5661	1.46632	3.28754	-0.0971		
1.470	-1.219	-2.90617	-110.80590	-05191	-02385	-12471	-0.5730	1.46773	3.29274	-0.0780		
1.471	-0.238	-2.98934	-92.37259	-00847	-00389	-12822	-0.5886	1.46902	3.29752	-0.0635		
1.471	.757	-3.07866	-73.98003	.03510	.01611	-13182	-0.6049	1.46973	3.30012	-0.0590		
1.471	1.796	-3.15174	-58.21673	.08090	.03713	-13466	-0.6181	1.46978	3.30031	-0.0605		
GRADIENT		-0.06296	15.23836	.04418	.02038	-.0012	-.00090	.00129	.00476	.00146		

RUN NO. 1401/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1401/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA		CPALPH	CPBQ	CPBETA	CPM
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	CPROBE	CPTD		
1.496	-8.059	-2.78754	-160.35450	-36055	-17104	-13343	-0.6330	1.46982	3.30046	-0.3441		
1.496	-7.038	-2.78898	-157.70980	-31918	-15135	-13276	-0.6295	1.47039	3.30258	-0.3376		
1.495	-6.053	-2.79408	-154.43200	-27955	-13257	-13272	-0.6294	1.47002	3.30120	-0.3386		
1.496	-5.073	-2.80035	-150.16380	-23445	-10940	-13188	-0.6154	1.48483	3.35626	-0.1725		
1.495	-4.096	-2.80962	-144.42990	-18953	-08807	-13223	-0.6144	1.48793	3.36787	-0.1317		
1.495	-3.128	-2.82691	-136.55840	-14598	-06758	-13110	-0.6069	1.49146	3.38108	-0.0937		
1.495	-2.164	-2.85680	-125.56060	-10090	-04661	-13147	-0.6073	1.49325	3.38781	-0.0731		
1.495	-1.205	-2.91296	-110.60740	-05630	-02597	-13302	-0.6136	1.49457	3.39278	-0.0605		
1.496	-0.224	-2.99110	-92.21365	-00988	-00456	-13676	-0.6306	1.49553	3.39639	-0.0528		
1.495	.773	-3.08068	-73.82103	.03638	.01676	-14004	-0.6452	1.49577	3.39733	-0.0463		
1.496	1.807	-3.14584	-58.15747	.08528	.03930	-14290	-0.6585	1.49596	3.39803	-0.0463		
GRADIENT		-0.06024	15.22785	.04664	.02160	-.00202	-.00085	.00127	.00477	.00135		

RUN NO. 1401/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

## PARAMETRIC DATA

	RUN NO.	1424/ O	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/ 5.00	BETA	=	-3.000	PHI	=	180.000
<b>MACH</b>													CPTD
<b>ALPHA</b>													
-8.053	-2.78820	-160.31450	-	.39737	-	.19041	-	.14444	-	.06921	1.48447	3.35489	- .04536
-7.041	-2.79338	-157.67030	-	.36357	-	.17429	-	.14653	-	.07024	1.48534	3.35814	- .04533
-6.059	-2.79402	-154.43200	-	.32146	-	.15406	-	.14844	-	.07114	1.48494	3.35665	- .04539
-5.074	-2.79894	-150.16360	-	.27236	-	.13050	-	.14840	-	.07111	1.48464	3.35554	- .04523
-4.101	-2.81171	-144.43010	-	.22016	-	.10549	-	.14906	-	.07143	1.48519	3.35761	- .04518
-3.123	-2.82532	-136.51860	-	.17317	-	.08298	-	.15568	-	.07460	1.48556	3.35898	- .04516
-2.166	-2.85631	-125.56060	-	.12127	-	.05813	-	.15916	-	.07629	1.48521	3.35768	- .04548
-1.207	-2.91295	-110.60740	-	.06691	-	.03208	-	.15916	-	.07630	1.48310	3.34980	- .04587
-2.224	-2.99173	-92.17403	-	.01215	-	.00582	-	.16165	-	.07749	1.48367	3.35192	- .04566
-1.773	-3.08136	-73.78139	-	.04241	-	.02034	-	.16457	-	.07891	1.48407	3.35341	- .04568
-3.14691	-3.14691	-58.11777	-	.10112	-	.04849	-	.16911	-	.08110	1.48374	3.35216	- .04584
1.808	-	-	-	.05478	-	.02625	-	.00293	-	.00141	-	.00032	- .000120
<b>GRADIENT</b>	-	.06030	15.22640	-									

RUN NO. 1412/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1412/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/ 5.00	BETA	=	-3.000	PHI	=	180.000
<b>MACH</b>													CPTD
<b>ALPHA</b>													
-8.056	-2.79076	-160.31480	-	.40478	-	.19218	-	.14612	-	.06938	1.52492	3.50834	- .02810
-7.042	-2.78963	-157.70980	-	.34457	-	.16329	-	.14175	-	.06718	1.52647	3.51428	- .02647
-6.057	-2.79471	-154.43210	-	.29662	-	.14030	-	.13905	-	.06577	1.52780	3.51944	- .02442
-5.077	-2.80175	-150.16390	-	.24409	-	.11534	-	.13700	-	.06474	1.52927	3.52508	- .02329
-4.095	-2.80961	-144.42990	-	.19053	-	.08998	-	.13561	-	.06405	1.52950	3.52600	- .02281
-3.126	-2.82850	-136.51880	-	.13629	-	.06430	-	.1295	-	.06037	1.53060	3.53024	- .02167
-2.163	-2.85796	-125.52100	-	.08732	-	.04116	-	.11788	-	.05556	1.53142	3.53341	- .02067
-1.207	-2.91223	-110.64700	-	.04620	-	.02177	-	.11343	-	.05344	1.53172	3.53455	- .02011
-2.222	-2.99674	-92.17404	-	.00763	-	.00360	-	.11405	-	.05372	1.53173	3.53458	- .01996
-1.773	-3.08093	-73.82103	-	.02999	-	.01413	-	.11783	-	.05549	1.53236	3.53705	- .01971
1.807	-3.14641	-58.15746	-	.07456	-	.03509	-	.12508	-	.05887	1.53214	3.53619	- .01952
<b>GRADIENT</b>	-	.06038	15.22831	-	.04397	-	.02074	-	.00199	-	.00097	.00043	.00053

RUN NO. 1412/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00



## PARAMETRIC DATA

	RUN NO.	1322/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	-2.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBQ	CPALPH	CPBQ	CPBETA	CPBQ	CPTD
1.099	-8.010	-1.98619	-165.96690	-.28003	-.11470	-.07436	-.03046	1.07318	2.06490	.03189			
1.098	-6.958	-1.92474	-164.35620	-.24393	-.09924	-.07025	-.02858	1.07997	2.08186	.02444			
1.100	-5.968	-1.92856	-161.83870	-.20912	-.08455	-.07008	-.02833	1.08545	2.09569	.01797			
1.101	-4.969	-1.92999	-158.44850	-.17352	-.06981	-.06892	-.02773	1.09044	2.10734	.01273			
1.100	-3.981	-1.92893	-153.75040	-.13879	-.05561	-.06705	-.02686	1.09320	2.11539	.00871			
1.100	-2.981	-1.94097	-146.71520	-.10273	-.04104	-.06721	-.02685	1.09554	2.12136	.00571			
1.100	-2.024	-1.91594	-135.99630	-.06791	-.02706	-.06531	-.02602	1.09742	2.12621	.00323			
1.100	-1.048	-1.93512	-117.95690	-.03414	-.01358	-.06502	-.02587	1.09844	2.12883	.00186			
1.100	-.086	-1.97574	-91.65268	-.00129	-.00051	-.06630	-.02635	1.09870	2.12951	.00111			
1.100	.902	-2.03822	-65.15492	.03244	.01289	-.06702	-.02663	1.09927	2.13096	-.00066			
1.100	1.929	-2.07813	-46.05624	.06796	.02700	-.06828	-.02713	1.09905	2.13039	-.00072			
1.100	GRADIENT	-.02077	17.15729	.03502	.01403	.00009	.00008	.00112	.00323	.00169			

RUN NO. 1367/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1367/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	-2.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBQ	CPALPH	CPBQ	CPBETA	CPBQ	CPTD
1.249	-8.019	-1.83968	-166.63510	-.28870	-.12761	-.07013	-.03100	1.22174	2.47147	.03357			
1.250	-6.997	-1.84489	-164.71260	-.25325	-.11116	-.06983	-.03065	1.22905	2.49329	.02590			
1.250	-6.005	-1.84461	-162.31430	-.21749	-.09477	-.06974	-.03039	1.23460	2.50997	.01863			
1.250	-5.012	-1.84456	-159.04330	-.18044	-.07829	-.06753	-.02930	1.23874	2.52246	.01404			
1.250	-4.030	-1.84656	-154.46450	-.14500	-.06269	-.06608	-.02857	1.24131	2.53028	.01058			
1.250	-3.054	-1.85378	-147.62720	-.10893	-.04692	-.06574	-.02832	1.24447	2.53987	.00679			
1.250	-2.087	-1.86963	-136.75070	-.07355	-.03159	-.06544	-.02811	1.24615	2.54501	.00431			
1.250	-1.140	-1.90281	-119.10740	-.03945	-.01692	-.06636	-.02846	1.24731	2.54855	.00265			
1.250	-1.178	-1.98651	-92.92181	-.00523	-.00224	-.06905	-.02959	1.24814	2.55106	.00184			
1.250	.822	-2.09170	-66.26512	.03003	.01287	-.07188	-.03080	1.24844	2.55199	-.00162			
1.250	1.875	-2.15027	-46.92819	.06701	.02870	-.07359	-.03152	1.24831	2.55159	-.00145			
1.250	-.05509	19.35251	.03588	.01545	-.00141	-.00056	.00112					.00342	.00146

RUN NO. 1378/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1378/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	-2.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBQ	CPALPH	CPBQ	CPBETA	CPBQ	CPTD
1.400	-8.013	-1.85800	-166.55640	-.31775	-.14798	-.07622	-.03550	1.36997	2.94541	.03508			
1.400	-6.993	-1.85777	-164.67320	-.27938	-.12902	-.07552	-.03488	1.37712	2.96989	.02642			
1.400	-6.001	-1.85652	-162.27470	-.23957	-.10993	-.07519	-.03450	1.38314	2.99065	.01976			
1.400	-5.010	-1.86262	-158.96450	-.19937	-.09103	-.07451	-.03402	1.38753	3.00581	.01463			
1.400	-4.026	-1.86514	-154.38560	-.16078	-.07308	-.07420	-.03373	1.39147	3.01948	.01018			
1.400	-3.042	-1.86254	-147.54780	-.11992	-.05430	-.07321	-.03315	1.39465	3.03054	.00633			
1.400	-2.080	-1.87774	-136.67130	-.08050	-.03639	-.07256	-.03280	1.39592	3.03497	.00470			
1.400	-1.127	-1.91072	-118.90910	-.04256	-.01922	-.07352	-.03319	1.39733	3.03990	.00338			
1.400	-.162	-1.98862	-92.64429	-.00462	-.00209	-.07646	-.03449	1.39778	3.04149	.00249			
1.400	.834	-2.08201	-66.06689	.03433	.01548	-.07966	-.03591	1.39798	3.04217	.00208			
1.400	1.888	-2.13834	-46.73003	.07492	-.08184	-.03689	-.03981	1.39815	3.04276	.00189			
1.400	.05008	19.35183	.03981	.01803	-.00145	-.00061	.00362					.00362	.00129

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM033) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPME	CPTD
1.449	-8.038	-1.74815	-166.95020	-33442	-15795	-07447	-03659	1.41824	3.11355
1.450	-7.021	-1.74933	-165.10720	-29380	-13772	-07755	-03635	1.42541	3.13908
1.450	-6.034	-1.74855	-162.78870	-25319	-11795	-07640	-03559	1.43065	3.15783
1.450	-5.045	-1.75090	-159.59760	-21116	-09786	-07601	-03523	1.43508	3.17375
1.450	-4.069	-1.75795	-155.09850	-17219	-07934	-07496	-03454	1.44074	3.19417
1.450	-3.100	-1.76759	-148.42020	-12971	-05956	-07452	-03422	1.44392	3.20569
1.451	-2.149	-1.79113	-137.78170	-08812	-04041	-07438	-03411	1.44591	3.21289
1.449	-1.218	-1.84899	-120.29710	-04860	-02226	-07635	-03497	1.44550	3.21141
1.450	-2.273	-1.97296	-94.27011	-00887	-00406	-08102	-03706	1.44703	3.21697
1.450	.733	-2.12754	-67.49452	-02866	-01503	-08601	-03935	1.44738	3.21823
1.450	-2.21502	-47.91945	-07684	-03514	-08884	-04063	1.44657	3.21529	-00333
1.449	1.801	-0.8401	19.43625	.04240	.01948	.00264	-.00116	.00093	.00338
GRADIENT									.00117

RUN NO. 1435/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPME	CPTD
1.471	-8.037	-1.76521	-166.91100	-34828	-16479	-08269	-.03913	1.44288	3.20189
1.471	-7.015	-1.76376	-165.06770	-30759	-14423	-08134	-.03814	1.45075	3.23050
1.471	-6.025	-1.77054	-162.67000	-26368	-12297	-08138	-.03795	1.45572	3.24862
1.471	-5.040	-1.77381	-159.47900	-22017	-10220	-08002	-.03715	1.45966	3.26307
1.471	-4.062	-1.78102	-154.98000	-17767	-08214	-07782	-.03597	1.46371	3.27795
1.471	-3.093	-1.78677	-148.30140	-13437	-06198	-07655	-.03531	1.46511	3.28307
1.471	-2.138	-1.81062	-137.58350	-09156	-04212	-0695	-.03540	1.46810	3.29411
1.471	-1.202	-1.85726	-120.13840	-05033	-02314	-07903	-.03634	1.46833	3.29495
1.471	-253	-1.97335	-94.03210	-00913	-.00420	-08393	-.03858	1.46857	3.29585
1.471	.750	-2.11366	-67.25661	.03448	.01584	-08976	-.04122	1.46921	3.29823
1.471	1.818	-2.19927	-47.72124	.08101	.03715	-09333	-.04280	1.47042	3.30268
GRADIENT				.04396	.02026	-.00295	-.00131	.00106	.00390

RUN NO. 1402/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPME	CPTD
1.495	-8.029	-1.77774	-166.87160	-35885	-17039	-08577	-.04072	1.46886	3.29693
1.495	-7.011	-1.78130	-164.98880	-31894	-15142	-08664	-.04113	1.46895	3.29726
1.495	-6.021	-1.78624	-162.59100	-27730	-12987	-08536	-.04050	1.48129	3.34304
1.496	-5.036	-1.78734	-159.39980	-23176	-10798	-08544	-.03998	1.48618	3.36133
1.496	-4.058	-1.79340	-154.86090	-18889	-08762	-08377	-.03886	1.48993	3.37537
1.496	-3.086	-1.79990	-148.14270	-14419	-06670	-08331	-.03854	1.49239	3.38460
1.496	-2.125	-1.81789	-137.42480	-09835	-04544	-08368	-.03867	1.49381	3.38992
1.496	-1.191	-1.87116	-119.90060	-05530	-.02555	-08614	-.03980	1.49391	3.39031
1.496	-.239	-1.97602	-93.8382	-.01071	-.03495	-.09198	-.04252	1.49310	3.38726
1.496	.762	-2.10992	-67.09793	.03636	.01681	-.09643	-.04457	1.49313	3.37339
1.495	1.829	-2.19056	-47.56258	.08551	.03950	-.09860	-.04555	1.49352	3.38885
GRADIENT				.04669	.02162	-.00291	-.00132	.00042	.00158

RUN NO. 1402/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

PAGE 488  
OCT 91

(TCM033) ( 04 OCT 91 )

GRADIENT INTERVAL = -5.00/-5.00

	MACH	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBE	CPTD
1.542	-8.032	-1.78212	-166.83200	-0.39790	-18882	-0.9403	3.50952	-0.02759
1.542	-7.010	-1.77971	-164.98860	-0.34197	-16201	-0.9172	3.51417	-0.02625
1.542	-6.026	-1.78618	-162.59100	-0.28897	-13659	-0.9094	3.52226	-0.02396
1.542	-5.037	-1.78568	-159.39960	-0.23644	-11166	-0.8931	3.52544	-0.02308
1.542	-4.058	-1.79278	-154.86090	-0.18287	-08628	-0.8527	3.52757	-0.02225
1.542	-3.085	-1.80224	-148.10310	-0.12426	-05857	-0.7562	3.53081	-0.02129
1.542	-2.130	-1.82127	-137.42490	-0.07984	-03763	-0.7014	3.53182	-0.02118
1.542	-1.192	-1.87099	-119.90060	-0.04466	-02106	-0.6986	3.53000	-0.02177
1.542	-2.238	-1.97636	-93.75461	-0.00950	-00448	-0.7333	3.52863	-0.02133
1.542	-765	-2.10955	-67.01868	-0.02752	-01297	-0.7692	3.53130	-0.02082
1.542	1.828	-2.19122	-47.56256	-0.06797	-03200	-0.7960	3.53463	-0.01981
1.542	-	-	-0.07237	-0.04131	-0.01947	-0.00038	.000019	.000083

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

( TCM034 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.600	-8.002	-7.2538	-173.90840	-339575	-.06773	-.03332	-.00672	.57153	1.24794	-.02184
.599	-6.991	-7.2539	-173.02660	-29454	-.05902	-.03436	-.00688	.57843	1.25446	-.01618
.600	-6.001	-7.2675	-171.86710	-25184	-.05031	-.03230	-.00645	.58432	1.26010	-.01196
.600	-5.008	-7.2657	-170.27060	-20892	-.04163	-.03137	-.00625	.58944	1.26508	-.00831
.600	-4.023	-7.2752	-167.92010	-16841	-.03351	-.03208	-.00638	.59302	1.26858	-.00583
.600	-3.040	-7.2874	-164.14090	-12581	-.02497	-.03146	-.00624	.59640	1.27192	-.00319
.601	-2.078	-7.3506	-157.18900	-84448	-.01675	-.02993	-.00593	.59818	1.27369	-.00185
.600	-1.158	-7.5718	-141.59830	-04637	-.00918	-.02982	-.00590	.59933	1.27484	-.00085
.601	-2.265	-9.6005	-97.78949	-0987	-.00196	-.02820	-.00756	.59982	1.27533	-.00063
.600	.783	-1.19301	-50.51779	.03229	.00639	-.04749	-.00940	.59997	1.27548	-.00038
.601	1.859	-1.26495	-30.07860	.07774	.01540	-.05004	-.00991	.60008	1.27558	-.00052
	GRADIENT	-1.10244	25.88758	.04166	.00827	-.00350	-.00069	.00110	.00083	

RUN NO. 1344 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.800	-7.965	-85701	-173.23910	-31951	-.09654	-.03799	-.01148	.77117	1.48192	-.02841
.800	-6.981	-80435	-172.71110	-28127	-.08449	-.03534	-.01062	.77780	1.49146	-.02207
.800	-5.989	-80404	-171.51140	-24070	-.07188	-.03337	-.00997	.78437	1.50105	-.01576
.800	-4.995	-80461	-169.83530	-20056	-.05962	-.03223	-.00958	.78886	1.50767	-.01118
.800	-4.002	-80812	-167.32580	-16048	-.04754	-.03230	-.00957	.79294	1.51373	-.00736
.801	-3.015	-80672	-163.38760	-11938	-.0328	-.03281	-.00970	.79583	1.51806	-.00470
.800	-2.045	-81000	-156.11820	-8001	-.02359	-.03181	-.00938	.79772	1.52090	-.00266
.800	-1.108	-82291	-139.85420	-04271	-.01257	-.03130	-.00921	.79848	1.52204	-.00144
.800	-.186	-98222	-95.33426	-00672	-.00198	-.03814	-.01122	.79912	1.52301	-.00092
.800	.847	-1.14220	-48.81480	.03402	.01001	-.04415	-.01298	.79919	1.52312	-.00076
.800	1.903	-1.19658	-29.00945	.07626	.02241	-.04497	-.01322	.79887	1.52263	-.00070
	GRADIENT	-.06057	21.97018	.04009	.01187	-.00200	-.00057	.00136	.00204	

RUN NO. 1332 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.900	-7.989	-.84140	-173.31810	-30679	-.10589	-.03603	-.01243	.87273	1.64257	-.02963
.900	-6.968	-.79477	-172.71080	-26837	-.09201	-.03361	-.01152	.87882	1.65323	-.02282
.900	-5.973	-.79337	-171.51100	-22974	-.07832	-.03193	-.01089	.88451	1.66332	-.01685
.900	-4.982	-.79052	-169.87460	-19128	-.06487	-.03061	-.01038	.88932	1.67192	-.01161
.900	-3.996	-.79327	-167.40480	-15259	-.05156	-.03107	-.01050	.89302	1.67860	-.00774
.900	-3.007	-.79211	-163.46670	-11363	-.03827	-.03079	-.01037	.89573	1.68351	-.00466
.900	-2.037	-.79278	-156.23690	-07580	-.02547	-.03002	-.01009	.89752	1.68677	-.00253
.900	-1.111	-.80898	-140.05230	-04033	-.01354	-.02981	-.01001	.89885	1.68919	-.00144
.900	-.199	-.97255	-95.75204	-00634	-.0213	-.03616	-.01213	.89921	1.6987	-.00078
.900	.834	-1.14481	-49.01292	.03251	.01091	-.04211	-.01413	.89928	1.69999	-.00071
.900	1.889	-1.20314	-29.16798	.07227	.02424	-.04295	-.01440	.89943	1.69027	-.00052
	GRADIENT	-.06389	22.03183	.03833	.01295	-.00063	-.00193	.00139	.00253	



(TCM034) ( 04 OCT 91 )

(TCM034) ( 04 OCT 91 )

(TCM034) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1391/ O	RN/L =	2.49	GRADIENT INTERVAL	= - 5.00 /	5 . 00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA
.450	- .8.006	- .73927	- 173.86910	- .33184	- .5663	- .03344
.450	- .6.983	- .74203	- 172.94760	- .29173	- .13667	- .03337
.450	- .5.986	- .74084	- 171.78780	- .25049	- .11662	- .03256
.450	- .5.002	- .74430	- 170.15190	- .20937	- .09693	- .03305
.450	- .4.015	- .74472	- 167.76170	- .16915	- .07783	- .03187
.449	- .3.031	- .74469	- 163.90300	- .12511	- .05744	- .03127
.450	- .2.068	- .75097	- 156.91130	- .08425	- .03860	- .03134
.450	- .1.145	- .77303	- 141.12270	- .04723	- .02156	- .03258
.450	- .2.249	- .96932	- 97.31430	- .00877	- .00399	- .04047
.450	.798	- .1.18219	- 50.12177	.03554	.01622	.04856
.450	.1.868	- .1.25603	- 29.95969	.07883	.03605	.04930
GRADIENT	.09677	25.87751	.04205	.01930	.00354	.00130
AACH	CPTD	CPM	M PROBE	CPBTA	CPBQ	CPALPH
.450	-.03527	.00138	.00472	.3.11676	1.41915	.03344
.450	-.02735	.00117	.00290	.3.14310	1.42653	.01578
.450	-.02117	.00169	.00160	.3.15978	1.43119	.01563
.450	-.01542	.00054	.00110	.3.17822	1.43632	.01516
.450	-.00913	.00054	.00054	.3.19877	1.44201	.01466
.450	-.00705	.00054	.00054	.3.20274	1.44311	.01436
.450	-.00492	.00088	.00088	.3.21188	1.44563	.01334
.450	-.00088	.00169	.00169	.3.22540	1.44935	.01487
.450	-.00088	.00054	.00054	.3.23418	1.45176	.01842
.450	-.00088	.00054	.00054	.3.22565	1.44942	.02215
.450	-.00088	.00054	.00054	.3.21967	1.44778	.02254

BURN NO 1436 / Q BN/1 = 2 49 GRADIENT INTERVAL = -5 00/ 5 00

	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
AACH	.471	-.8 .006	-.76161	-173 .79050	-.34637	-.16372	-.03585	1.44362	3.20460	-.03575
	.471	-6 .978	-.76766	-172 .82930	-.30507	-.14291	-.03626	-.01699	1.45121	-.02659
	.471	5 .986	-.76433	-171 .66930	-.26121	-.12172	-.03530	-.01645	1.45631	-.02116
	.471	4 .996	-.76642	-170 .03330	-.21781	-.10102	-.03432	-.01592	1.46014	-.01643
	.471	4 .009	-.76638	-167 .64290	-.17406	-.08046	-.03281	-.01517	1.46392	-.01288
	.471	3 .025	-.76545	-163 .78410	-.13030	-.06002	-.03253	-.01499	1.46639	-.00949
	.471	2 .059	-.77157	-156 .63370	-.08773	-.04037	-.03196	-.01471	1.46723	-.00847
	.470	-1 .132	-.78985	-140 .68660	-.04781	-.02199	-.03249	-.01495	1.46715	-.00807
	.471	-.228	-.97821	-96 .68069	-.00875	-.00402	-.04053	-.01863	1.46858	-.00723
	.471	.818	-1 .17248	-49 .72563	.03656	.01680	-.04934	-.02268	1.46881	-.00715
	.471	1 .885	-1 .23570	-29 .60333	.08254	.03789	-.05176	-.02376	1.46972	-.00601
GRADIENT		-.07336		21 .96157	.04362	-.02015	-.00282	-.00127	.00442	.001133

RUN No. 1403/0 RN/L = 2.49 GRADIENT INTERVAL = -5.00 / 5.00

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM034) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1426/ 0	RN/L =	2.49	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	-1.000	PHI	=	180.000
<b>MACH</b>														
ALPHA														
1.517	-8.000	-.777008	-173.71130	.40852	CPAQ	CPAL PH	CPBQ	CPBETA	MPROBE	CPTD				
1.517	-6.983	-.77801	-172.78970	.37047		-.19198	-.04176	-.01962	1.50344	3.42630	-.02426			
1.517	-5.985	-.77845	-171.59010	.31949		-.17410	-.04360	-.02049	1.50351	3.42656	-.02402			
1.517	-4.996	-.77695	-169.95380	.26832		-.15013	-.04345	-.02042	1.50346	3.42638	-.02392			
1.517	-4.008	-.77979	-167.18400	.22023		-.12610	-.04169	-.01959	1.50382	3.42772	-.02390			
1.516	-3.022	-.78220	-163.54610	.16145		-.10354	-.04250	-.01998	1.50360	3.42691	-.02426			
1.517	-2.055	-.78525	-156.39570	.10869		-.07589	-.04257	-.02001	1.50276	3.42371	-.02430			
1.517	-1.125	-.80193	-140.32390	.05782		-.05109	-.04244	-.01995	1.50360	3.42691	-.02396			
1.516	-.215	-.98225	-96.16591	.01456		-.02717	-.03944	-.01853	1.50373	3.42739	-.02387			
1.516	.830	-.1.16561	-49.36917	.04224		-.00685	-.04219	-.01984	1.50223	3.42171	-.02478			
1.517	1.895	-.1.22318	-29.32610	.09933		-.01986	-.05329	-.02505	1.50265	3.42332	-.02429			
GRADIENT	-.06951		21.96694	.05353		.02516	-.04670	-.05949	1.50364	3.42705	-.02403			
							-.00216	-.00102		-.00009				
<b>MACH</b>														
ALPHA														
1.542	-8.004	-.77893	-173.71160	.39492	CPAQ	CPAL PH	CPBQ	CPBETA	MPROBE	CPTD				
1.542	-6.982	-.77892	-172.78980	.33959		-.18723	-.04175	-.01979	1.51121	3.51256	-.02701			
1.542	-5.990	-.77521	-171.62970	.28073		-.16074	-.03965	-.01877	1.51657	3.51657	-.02535			
1.542	-4.995	-.78049	-169.91420	.22677		-.13268	-.03965	-.01877	1.52706	3.52314	-.02328			
1.542	-4.008	-.77824	-167.52370	.17067		-.10715	-.03957	-.01870	1.52876	3.52584	-.02293			
1.543	-3.022	-.77862	-163.62540	.11649		-.08057	-.03634	-.01715	1.52982	3.52722	-.02190			
1.542	-2.055	-.78505	-156.43540	.07716		-.05494	-.03157	-.01489	1.53146	3.53355	-.02091			
1.542	-1.125	-.80176	-140.36950	.04245		-.03641	-.03022	-.01426	1.53006	3.52815	-.02178			
1.543	-.215	-.98193	-96.20552	.00927		-.02003	-.02926	-.01381	1.53052	3.52992	-.02135			
1.543	.829	-.1.16550	-49.40878	.02831		-.00437	-.03542	-.01671	1.53083	3.53111	-.02092			
1.554	1.896	-.1.22128	-29.28653	.06693		-.01335	-.04041	-.01906	1.53126	3.53278	-.02075			
GRADIENT	-.06925		21.96397	.04165		-.02022	-.04170	-.01995	1.53122	3.53262	-.02063			
						-.00057	-.00029	-.00029		.00085	.00027			

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

( TCM035 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RUN NO. 1355/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
		BETA	PHI												
.599	-7.963	.28604	178.93230	-.33249	-.06693	.01048	.00211	.57123	1.24766	-.02150					
.600	-6.956	.28609	178.77250	-.29082	-.05839	.01069	.00215	.57820	1.25424	-.01678					
.600	-5.955	.28131	178.61260	-.24856	-.04970	.01073	.00214	.58481	1.26058	-.01188					
.600	-4.953	.28145	178.33410	-.20653	-.04115	.01068	.00213	.58953	1.26517	-.00826					
.601	-3.951	.28274	177.89720	-.16508	-.03286	.01025	.00204	.59388	1.26943	-.00542					
.600	-2.948	.27921	177.26200	-.12247	-.02430	.01036	.00205	.59626	1.27178	-.00324					
.601	-1.942	.27778	175.91380	-.07903	-.01568	.01086	.00215	.59846	1.27397	-.00185					
.601	-.922	.26963	172.0960	-.03614	-.00716	.01073	.00213	.59940	1.27490	-.00102					
.600	.192	-.06618	103.32380	-.00687	-.00136	-.00233	-.00046	.59920	1.27471	-.00048					
.600	.869	-.17438	-.08211	-.03342	-.00661	-.00670	-.00133	.59947	1.27498	-.00043					
.600	2.006	-.28588	-.3.24762	-.08254	-.01632	-.00944	-.00187	.59945	1.27495	-.00048					
	GRADIENT	-.08719	-28.24187	.04141	.00823	.00315	-.00062	.00129	.00128	.00107					

RUN NO. 1345/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	RUN NO. 1345/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
		BETA	PHI												
.800	-7.968	.20124	179.24610	-.31883	-.09634	.00724	.00219	.77118	1.48193	-.02843					
.800	-6.952	.20224	179.12650	-.27762	-.08336	.00736	.00221	.77846	1.49243	-.02149					
.800	-5.951	.20404	178.96730	-.23746	-.07087	.00740	.00221	.78381	1.50022	-.01584					
.800	-4.950	.20310	178.76830	-.19838	-.05896	.00804	.00239	.78921	1.50818	-.01091					
.800	-3.955	.20093	178.49010	-.15828	-.04688	.00787	.00233	.79289	1.51366	-.00733					
.800	-2.948	.20121	177.97420	-.11707	-.03458	.00748	.00221	.79607	1.51841	-.00431					
.800	-1.946	.19906	177.02250	-.07624	-.02246	.00717	.00211	.79796	1.52125	-.00219					
.800	-.933	.19301	174.28810	-.03574	-.01052	.00732	.00215	.79902	1.52286	-.00112					
.800	.019	-.13591	15.12493	-.00024	.00007	-.00556	-.00164	.79925	1.52321	-.00074					
.800	1.009	-.17075	-2.18056	-.03839	.01129	-.00615	-.00181	.79899	1.52282	-.00070					
.799	2.003	-.20604	-2.09988	-.07933	.02331	-.00581	-.00171	.79897	1.52279	-.00048					
	GRADIENT	-.06856	-31.78292	.03980	.01178	-.00246	-.00073	.00132	.00197	.00142					

RUN NO. 1333/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	RUN NO. 1333/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
		BETA	PHI												
.900	-7.958	.21413	179.20690	-.30466	-.10518	.00772	.00267	.87220	1.64165	-.03002					
.900	-6.932	.21469	179.08720	-.26518	-.09093	.00743	.00255	.88700	1.65355	-.02282					
.900	-5.938	.21555	178.92790	-.22717	-.07738	.00778	.00265	.88421	1.66277	-.01663					
.900	-4.939	.21432	178.72890	-.18919	-.06415	.00822	.00279	.88934	1.67195	-.01154					
.900	-3.940	.21363	178.41100	-.15077	-.05093	.00802	.00271	.89318	1.67887	-.00750					
.900	-2.935	.21198	177.89510	-.11133	-.03747	.00768	.00259	.89580	1.68363	-.00431					
.900	-1.929	.21075	176.86410	-.07221	-.02427	.00678	.00228	.89804	1.68772	-.00228					
.900	-.918	.20380	173.97120	-.03364	-.01129	.00744	.00250	.89888	1.68925	-.00109					
	GRADIENT	-.00238	-1.10139	.03876	.01317	-.00028	-.00010	.00132	.00138	.000238	.000432	.000260			

## PARAMETRIC DATA

	RUN NO.	1324/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD				
1.100	-7.946	.03990	179.95260	-.27498	-.11252	.00052	.00021	1.07463	2.06852	-.03065			
1.100	-6.933	.07825	179.67800	-.24082	-.09786	.00208	.00085	1.08107	2.08464	-.02323			
1.100	-5.936	.07526	179.67760	-.20639	-.08335	.00189	.00076	1.08612	2.09737	-.01695			
1.100	-4.941	.07339	179.63760	-.17179	-.06904	.00229	.00092	1.09065	2.10888	-.01180			
1.100	-3.935	.07135	179.55780	-.13626	-.05452	.00276	.00110	1.09344	2.11599	-.00773			
1.100	-2.935	.05880	179.39840	-.09998	-.03990	.00199	.00079	1.09664	2.12420	-.00456			
1.100	-1.940	.06592	178.92300	-.06504	-.02589	.00183	.00073	1.09809	2.12794	-.00225			
1.100	-936	.07204	177.89280	-.03143	-.01249	.00226	.00090	1.09898	2.13021	-.00095			
1.100	.059	.00484	119.99410	.00097	.00038	.00150	.00059	1.09925	2.13092	-.00040			
1.100	.985	-.07623	-.04232	.03295	-.01309	-.00044	-.00017	1.09946	2.13147	-.00065			
1.100	.007	-.08021	-.23965	.06821	.02710	.00024	.00009	1.09977	2.13225	-.00049			
1.100	GRADIENT	-.02355	-.27.92565	.03440	.01376	-.00038	-.00015	.00124	.00317	.00155			

	RUN NO.	1370/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	5.00
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD				
1.250	-7.973	.16830	179.36380	-.28398	-.12540	.00408	.00180	1.22298	2.47514	-.03239			
1.250	-6.948	.17154	179.24450	-.24838	-.10888	.00573	.00251	1.22956	2.49481	-.02476			
1.250	-5.950	.16656	179.16430	-.21328	-.09285	.00460	.00200	1.23524	2.51190	-.01770			
1.250	-4.947	.16969	178.96570	-.17660	-.07656	.00557	.00241	1.23919	2.52383	-.01335			
1.250	-3.951	.16781	178.72720	-.14061	-.06072	.00645	.00279	1.24266	2.53438	-.00931			
1.250	-2.948	.16624	178.33030	-.10348	-.04451	.00545	.00235	1.24520	2.54211	-.00555			
1.250	-1.946	.16375	177.49760	-.06834	-.02932	.00513	.00220	1.24766	2.54959	-.00287			
1.250	-.941	.16028	175.15950	-.03280	-.01405	.00565	.00242	1.24882	2.55332	-.00140			
1.250	-.074	-.06143	-.51.07858	-.00268	-.00115	-.00130	-.00056	1.24872	2.55285	-.00156			
1.250	.987	-.19767	-.4.83343	.03468	.01485	-.00537	-.00230	1.24893	2.55348	-.00093			
1.249	2.026	-.17631	-.1.74371	.07138	.03056	-.00369	-.00158	1.24857	2.55237	-.00104			
1.249	GRADIENT	-.05910	-.34.19582	.03549	.01531	-.00172	-.00074	.00131	.00399	.00170			

MACH ALPHA BETA PHI CPAQ CPALPH CPBQ CPBETA MPROBE CPTD

	RUN NO.	1381/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	5.00
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD				
1.400	-7.977	.14945	179.44230	-.31353	-.14579	.00568	.00264	1.37168	2.95126	-.03338			
1.400	-6.948	.15342	179.32300	-.27478	-.12679	.00753	.00347	1.37804	2.97306	-.02556			
1.400	-5.951	.15323	179.20350	-.23544	-.10800	.00646	.00296	1.38318	2.99285	-.01935			
1.400	-4.954	.15245	179.04440	-.19676	-.08970	.00667	.00304	1.38810	3.00781	-.01329			
1.400	-3.952	.15241	178.80610	-.15670	-.07112	.00735	.00334	1.39228	3.02231	-.00872			
1.400	-2.954	.15197	178.44900	-.11448	-.05181	.00682	.00309	1.39533	3.03294	-.00583			
1.400	-1.948	.15019	177.73520	-.07549	-.03410	.00563	.00254	1.39725	3.03962	-.00375			
1.400	-.948	.14780	175.59520	-.03656	-.01646	.00587	.00264	1.39898	3.04567	-.00083			
1.400	.055	-.09971	25.06580	.00210	.00094	-.00276	-.00124	1.39928	3.04670	-.00072			
1.399	1.005	-.14371	-.2.02219	.03888	.01750	-.00402	-.00181	1.39929	3.04676	-.00023			
1.400	2.022	-.15950	-.1.42703	.07837	.03532	-.00410	-.00185	1.39823	3.04305	-.00171			
1.400	GRADIENT	-.05278	-.31.39032	.03937	.01786	-.00192	-.00087	.00143	.00499	.00170			

PARAMETRIC DATA

$B_E | A = \frac{.000}{.000} P_{H1} = \frac{.000}{.000}$

180.000

	ACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPM	CPTD
.450	-7.974	.26592	179.01060	.32917	.15528	.00951	.00448	.1.42015	.3.12034	-.03453
.450	-6.945	.26793	178.85110	.28920	.13546	.01049	.00491	.1.42630	.3.14226	-.02726
.450	-5.947	.26413	178.69130	.24785	.11541	.00921	.00429	.1.43197	.3.16257	-.02107
.450	-4.949	.26440	178.41290	.20753	.09605	.01052	.00487	.1.43615	.3.17759	-.01521
.450	-3.946	.26668	178.01580	.16643	.07658	.01132	.00521	.1.44218	.3.19939	-.00904
.450	-2.942	.26477	177.38070	.12160	.05583	.01023	.00470	.1.44341	.3.20384	-.00699
.450	-1.938	.26213	176.11180	.08024	.03674	.00991	.00454	.1.44638	.3.21462	-.00423
.450	-.920	.25405	172.50560	.03883	.01768	.01081	.00492	.1.45134	.3.23265	-.00136
.450	-.095	-.16525	-.00344	-.00369	-.00168	-.00598	-.00273	1.44990	.3.22741	-.00047
.450	.993	-.28778	-.5.98163	.04216	.01917	-.00134	-.00425	.1.45116	.3.23198	-.00159
.450	2.018	-.27443	-.3.08924	.08312	.03801	-.00815	-.00373	1.44659	.3.23153	-.00306
.449	GRADIENT	-.09258	-.32.50265	.04184	.01926	-.00336	-.00154	.00172	.00622	.00197

RUN NO	1437/0	PN/1	3.19	GRADIENT INTERVAL	-5°/00'	5°/00'
--------	--------	------	------	-------------------	---------	--------

GRADIENT INTERVAL = -6 00/-5 00

GRADIENT	-2.43	-1.04	0	1.04	2.43	GRADIENT	-	J.00/	J.00/	CPM	CPTD	
RUN NO.						INTERVAL	-			MPROBE	CPBQ	CPALPH
ALPHA	BETA	PHI	CPAQ	CPAQ	CALPH	CPBQ	CPALPH	CPBQ	CPALPH	CPBQ	CPALPH	CPALPH
- .496	- .973	.23026	.179	.128	.10	.35579	-	.16846	-	.147177	-	.30767
- .496	- .944	.23506	.178	.969	.10	.31626	-	.14978	-	.00411	-	.30781
- .496	- .944	.22948	.178	.4890	-	.27303	-	.10630	-	.00377	-	.34639
- .496	- .944	.23460	.178	.57100	-	.22833	-	.08559	-	.00441	-	.48219
- .496	- .944	.22934	.178	.29240	-	.18383	-	.06363	-	.00441	-	.48723
- .496	- .944	.22759	.177	.73680	-	.13670	-	.04336	-	.00468	-	.36528
- .496	- .944	.22591	.176	.62650	-	.09156	-	.02146	-	.00461	-	.36278
- .496	- .935	.21953	.173	.45620	-	.04519	-	.02104	-	.00480	-	.36441
- .496	- .063	.10550	-112	.67150	-	.00439	-	.00204	-	.00507	-	.48707
- .496	- .124	.12033	-179	.45080	-	.05047	-	.00235	-	.00574	-	.36465
- .496	- .030	.23519	-176	.39217	-	.09299	-	.04336	-	.00267	-	.36082
- .01079	-6.1	.21721		.04608	-		-	.01294	-	.00393	-	.35917
GRADIENT	-				-		-	.00603	-	.1.48561	-	.1595
					-		-	.00003	-	.1.48584	-	.16067
					-		-	.00006	-	.00003	-	.00023
					-		-		-	.000087	-	

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAO	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.517	-7.973	.22813	179.16780	-.41044	-.19300	.01034	.00486	1.50375	3.42746	-.02414
1.517	-6.944	.23247	179.00870	-.37166	-.17477	.01192	.00561	1.50384	3.42782	-.02421
1.517	-5.948	.22751	178.88850	-.31860	-.14986	.01091	.00513	1.50326	3.42563	-.02458
1.518	-4.950	.23355	178.61060	-.27008	-.12705	.01262	.00594	1.50374	3.42741	-.02437
1.517	-3.948	.22840	178.33210	-.21795	-.10251	.01338	.00629	1.50298	3.42456	-.02436
1.518	-2.945	.22814	177.77650	-.15757	-.07411	.01103	.00519	1.50388	3.42797	-.02412
1.517	-1.942	.22664	176.66620	-.10215	-.04808	.00990	.00466	1.50221	3.42164	-.02505
1.517	-.928	.21937	173.57510	-.03796	-.01786	.00524	.00246	1.50212	3.42128	-.02476
1.517	-.115	-.06436	-.49.49515	-.00347	-.00163	-.00584	-.00275	1.50341	3.42618	-.02422
1.517	.978	-.25600	-.6.33198	-.02945	-.01386	-.00466	-.00304	1.50263	3.42321	-.02504
1.517	2.017	-.23783	-.2.53514	-.09964	-.04689	-.00710	-.00334	1.50292	3.42432	-.02470
GRADIENT		-.07919	-.34.17506	.05250	.02470	-.00350	-.00165	-.00011	-.000042	-.000007

RUN NO. 1416/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAO	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.543	-7.971	.24906	179.01080	-.39271	-.18590	.01841	.00871	1.52758	3.51857	-.02471
1.543	-6.949	.23123	179.00850	-.33820	-.16015	.01419	.00672	1.52751	3.51829	-.02497
1.543	-5.946	.23060	178.84900	-.27412	-.12978	.01201	.00569	1.52775	3.51922	-.02487
1.543	-4.944	.23140	178.61040	-.21983	-.10411	.00771	.00365	1.52742	3.51796	-.02511
1.543	-3.948	.23036	178.29250	-.16317	-.07725	.00870	.00412	1.52764	3.51881	-.02491
1.543	-2.945	.22844	177.73680	-.11420	-.05407	.00655	.00310	1.52731	3.51751	-.02509
1.543	-1.942	.22742	176.62650	-.07436	-.03521	.00680	.00322	1.52788	3.51972	-.02500
1.543	-.927	.22001	173.49590	-.03603	-.01706	.00768	.00363	1.52767	3.51891	-.02489
1.543	-.116	-.11317	-.17.38718	-.00234	-.00111	-.00570	-.00270	1.52684	3.51574	-.02540
1.543	1.001	-.25443	-.6.10037	-.03210	-.01521	-.00718	-.00340	1.52789	3.51978	-.02500
1.542	2.012	-.23517	-.2.49561	-.06966	-.03299	-.00516	-.00244	1.52694	3.51609	-.02521
GRADIENT		-.08049	-.33.09517	.04071	.01928	-.00245	-.00116	-.00017	-.00004	-.000002

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

( TCM036 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1335/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	180.000
.900	.7. 958	.21346	179.20680	-	.30511	-	.10532	.0606	.00209	.87234		1.64188		.02988	
.900	.6. 937	.21947	179.04790	-	.26567	-	.09106	.0638	.00219	.87880		1.65319		.02273	
.900	.5. 938	.21542	178.92790	-	.22719	-	.07739	.0761	.00259	.88460		1.66347		.01642	
.900	.4. 934	.21762	178.68940	-	.18930	-	.06418	.0772	.00262	.88915		1.67161		.01158	
.900	.3. 935	.21327	178.41100	-	.15099	-	.05100	.0812	.00274	.89327		1.67904		.00741	
.900	.2. 935	.21203	177.89510	-	.11124	-	.03747	.0693	.00234	.89595		1.68391		.00452	
.900	.1. 929	.21080	176.86410	-	.07231	-	.02428	.0662	.00222	.89746		1.68666		.00226	
.900	.- .918	.20389	173.97120	-	.03376	-	.01133	.0715	.00240	.89926		1.68995		.00109	
.900	.038	.- 13904	3.32316	-	.00038	-	.00013	.0488	-	.00164		.89902		.00070	
.900	.980	.- 233372	-5.50652	-	.03567	-	.01197	.0768	-	.00164		.89919		.00068	
.900	.2. 008	.- 22127	-2.33733	-	.07568	-	.02537	.0562	-	.00188		.89904		.00052	
.900	.GRADIENT	.- 07624	-32.50094	-	.03805	-	.01285	.0248	-	.00084		.00133		.00149	

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

MACH	ALPHA	RUN NO.	1357/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	1.000	PHI	=	180.000
.599	.7. 940	1.27106	171.94890	-	.33127	-	.06676	.05225	.01053	.57083		1.24728		.02201	
.600	.6. 915	1.26339	170.82920	-	.28967	-	.05815	.05283	.01061	.57817		1.25421		.01677	
.599	.5. 911	1.26235	169.31410	-	.24697	-	.04931	.05321	.01062	.58325		1.25907		.01245	
.600	.4. 906	1.25849	167.24440	-	.20343	-	.04057	.05247	.01046	.58946		1.26509		.00848	
.600	.3. 889	1.25227	164.18450	-	.16256	-	.03230	.05197	.01033	.59279		1.26835		.00566	
.600	.2. 869	1.24329	159.26330	-	.11898	-	.02358	.05142	.01019	.59569		1.27122		.00337	
.601	.1. 831	1.21326	150.42160	-	.07485	-	.01483	.04980	.00987	.59834		1.27405		.00156	
.601	.- .777	1.13565	131.08730	-	.03079	-	.00610	.04633	.00919	.59971		1.27522		.00097	
.601	.297	.- 94781	82.84685	-	.01114	-	.00221	.03921	.00777	.59974		1.27525		.00075	
.600	.1. 188	.- 77297	40.30490	-	.04829	-	.00955	.03181	.00629	.59986		1.27537		.00035	
.600	.2. 118	.- 74164	23.82216	-	.08743	-	.01729	.03213	.00636	.59967		1.27518		.00044	
.600	.- .08164	.- 21.89490	.04142	-	.00823	-	.00332	.00067	-	.00142		.00141		.00108	

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1335/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	180.000
.599	.7. 940	1.27106	171.94890	-	.33127	-	.06676	.05225	.01053	.57083		1.24728		.02201	
.600	.6. 915	1.26339	170.82920	-	.28967	-	.05815	.05283	.01061	.57817		1.25421		.01677	
.599	.5. 911	1.26235	169.31410	-	.24697	-	.04931	.05321	.01062	.58325		1.25907		.01245	
.600	.4. 906	1.25849	167.24440	-	.20343	-	.04057	.05247	.01046	.58946		1.26509		.00848	
.600	.3. 889	1.25227	164.18450	-	.16256	-	.03230	.05197	.01033	.59279		1.26835		.00566	
.600	.2. 869	1.24329	159.26330	-	.11898	-	.02358	.05142	.01019	.59569		1.27122		.00337	
.601	.1. 831	1.21326	150.42160	-	.07485	-	.01483	.04980	.00987	.59834		1.27405		.00156	
.601	.- .777	1.13565	131.08730	-	.03079	-	.00610	.04633	.00919	.59971		1.27522		.00097	
.601	.297	.- 94781	82.84685	-	.01114	-	.00221	.03921	.00777	.59974		1.27525		.00075	
.600	.1. 188	.- 77297	40.30490	-	.04829	-	.00955	.03181	.00629	.59986		1.27537		.00035	
.600	.2. 118	.- 74164	23.82216	-	.08743	-	.01729	.03213	.00636	.59967		1.27518		.00044	
.600	.- .08164	.- 21.89490	.04142	-	.00823	-	.00332	.00067	-	.00142		.00141		.00108	

## PARAMETRIC DATA

## PARAMETRIC DATA

	RUN NO.	1346/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA	= 1.000	PHI	= 180.000
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD
.800	-7.940	1.18515	172.26270	-31670	.09568	.04908	.01483	.02868
.800	-6.922	1.18400	171.14380	-27684	.08318	.04784	.01437	.02222
.800	-5.920	1.18482	169.66880	-23608	.07054	.04786	.01430	.01638
.800	-4.914	1.17936	167.67860	-19582	.05819	.04814	.01430	.01119
.800	-3.906	1.17683	164.69840	-15548	.04606	.04720	.01398	.00757
.800	-2.889	1.16622	159.97550	-11447	.03381	.04573	.01351	.00451
.801	-1.867	1.14654	151.33240	-07332	.02162	.04459	.01315	.00243
.800	-834	1.08686	132.51350	-03199	.00941	.04288	.01261	.00109
.800	.218	.95793	85.14476	.00764	.00225	.03881	.01142	.00078
.800	1.129	.83570	42.16666	.04371	.01285	.03404	.01001	.00060
.800	2.084	.81558	24.89116	.08216	.02415	.03428	.01008	.00072
	GRADIENT	- .05823	-21.87592	.03963	.01173	- .00219	- .00066	.00138
	RUN NO.	1336/ 0	RN/L = 2.49	GRADIENT INTERVAL = -5.00/ 5.00				
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD
.900	-7.943	1.20397	172.18430	-30307	.10468	.04629	.01599	.03030
.900	-6.915	1.20046	171.06520	-26491	.09088	.04633	.01589	.02363
.900	-5.910	1.19913	169.58990	-22607	.07711	.04664	.01591	.01751
.900	-4.905	1.19258	167.59960	-18730	.06354	.04604	.01562	.01188
.900	-3.894	1.18690	164.61920	-14853	.05020	.04529	.01531	.00789
.901	-2.879	1.17645	159.85670	-10923	.03681	.04406	.01485	.00468
.900	-1.852	1.15363	151.17390	-07003	.02354	.04264	.01433	.00233
.900	-.819	1.09155	132.19650	-03045	.01022	.04113	.01380	.00125
.900	.231	.95391	84.74855	.00720	.00242	.03709	.01244	.00072
.900	1.141	.82854	41.92894	.04146	.01391	.03270	.01097	.00067
.900	2.095	.80784	24.77228	.07835	.02627	.03283	.01101	.00073
	GRADIENT	- .06148	-21.88681	.03783	.01278	- .00210	- .00073	.00130
	RUN NO.	1325/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00				
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD
1.100	-7.949	1.05600	172.73370	-27445	-.11238	.03727	.01526	.06675
1.100	-6.926	1.05748	171.69510	-23966	-.09751	.03727	.01516	.03137
1.100	-5.948	1.05834	170.37950	-20604	-.08326	.03654	.01476	.0438
1.100	-4.924	1.05057	168.50820	-.17017	-.06845	.03683	.01481	.01769
1.100	-3.925	1.03154	165.76520	-.13524	-.05414	.03667	.01468	.01265
1.100	-2.919	1.04004	161.00380	-.09962	-.03976	.03551	.01417	.00811
1.100	-1.912	1.03087	152.79730	-.06479	-.02580	.03442	.01370	.00259
1.100	-.917	.99745	134.92970	-.03069	-.01220	.03379	.01344	.00124
1.100	.089	.96293	89.30457	.00175	.00069	.03399	.01351	.00070
1.100	1.052	.92558	44.46443	.03453	.01372	.03306	.01314	.00047
1.100	2.026	.91883	26.35649	.06852	.02722	.03352	.01332	.00058
	GRADIENT	- .02052	-21.91385	.03421	.01369	- .00056	- .00025	.00164

	RUN NO.	1325/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA	= 1.000	PHI	= 180.000
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD
1.100	-7.949	1.05600	172.73370	-27445	-.11238	.03727	.01526	.06675
1.100	-6.926	1.05748	171.69510	-23966	-.09751	.03727	.01516	.03137
1.100	-5.948	1.05834	170.37950	-20604	-.08326	.03654	.01476	.0438
1.100	-4.924	1.05057	168.50820	-.17017	-.06845	.03683	.01481	.01769
1.100	-3.925	1.03154	165.76520	-.13524	-.05414	.03667	.01468	.01265
1.100	-2.919	1.04004	161.00380	-.09962	-.03976	.03551	.01417	.00811
1.100	-1.912	1.03087	152.79730	-.06479	-.02580	.03442	.01370	.00259
1.100	-.917	.99745	134.92970	-.03069	-.01220	.03379	.01344	.00124
1.100	.089	.96293	89.30457	.00175	.00069	.03399	.01351	.00070
1.100	1.052	.92558	44.46443	.03453	.01372	.03306	.01314	.00047
1.100	2.026	.91883	26.35649	.06852	.02722	.03352	.01332	.00058
	GRADIENT	- .02052	-21.91385	.03421	.01369	- .00056	- .00025	.00164

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

( TCM037 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1371/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	1.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA					CPTD
1.250	-7.949	1.15125	172.38030	-2.28248	-12483	.04114	.01818	1.22268	2.47426	-.033309		
1.250	-6.928	1.15274	171.26180	-2.24697	-.10835	.04184	.01836	1.22881	2.49256	-.02564		
1.250	-5.920	1.14986	169.82630	-2.21167	-.09220	.04123	.01796	1.23474	2.51039	-.01830		
1.250	-4.923	1.14774	167.83640	-1.7457	-.07569	.04112	.01783	1.23863	2.52214	-.01363		
1.250	-3.909	1.14866	164.85650	-1.13838	-.05975	.04134	.01785	1.24193	2.53215	-.00940		
1.250	-2.895	1.13588	160.21290	-1.0170	-.04375	.03988	.01716	1.24474	2.54069	-.00579		
1.250	-1.882	1.11750	151.72840	-0.66601	-.02833	.03870	.01661	1.24725	2.54834	-.00336		
1.250	-860	1.06518	133.10770	-0.03024	-.01296	.03774	.01617	1.24860	2.55247	-.00149		
1.250	.186	.97166	86.01637	.00572	.00245	.03549	.01520	1.24916	2.55420	-.00090		
1.250	1.122	.86312	42.52313	.03872	.01658	.03220	.01379	1.24897	2.55362	-.00097		
1.250	2.079	.84092	25.12872	.07264	.03111	.03153	.01350	1.24894	2.55353	-.00117		
GRADIENT		-.04868	-21.87242	.03522	.01520	-.00150	-.00067	.00145	.00442	.00174		

RUN NO. 1382/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1382/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA		CPBQ	CPALPH	CPBETA	CPM
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA					CPTD
1.399	-7.955	1.13944	172.41970	-.31179	-.14509	.04680	.02178	1.37015	2.94604	-.03438		
1.400	-6.930	1.13504	171.34040	-.27351	-.12628	.04702	.02171	1.37753	2.97132	-.02613		
1.400	-5.923	1.13285	169.90500	-.23374	-.10725	.04639	.02129	1.38345	2.99171	-.01966		
1.400	-4.921	1.13203	167.91520	-.19438	-.08869	.04605	.02101	1.38759	3.00603	-.01408		
1.400	-3.914	1.12921	165.01460	-.15432	-.07007	.04617	.02096	1.39234	3.02253	-.00907		
1.400	-2.905	1.12288	160.37130	-.11270	-.05099	.04417	.01998	1.39467	3.03064	-.00569		
1.400	-1.890	1.10538	151.92650	-.07297	-.03296	.04262	.01925	1.39621	3.03600	-.00402		
1.400	-.870	1.05883	133.42460	-.03410	-.01537	.04205	.01895	1.39912	3.04617	-.00152		
1.400	.172	.97296	86.49178	.00558	.00251	.03954	.01779	1.39928	3.04671	-.00034		
1.400	1.117	.87336	42.72119	.04265	.01921	.03617	.01629	1.39891	3.04544	-.00087		
1.400	2.073	.85769	25.40585	.07987	.03600	.03495	.01575	1.39816	3.04281	-.00192		
GRADIENT		-.04372	-21.87064	.03910	.01775	-.00168	-.00079	.00147	.00513	.00172		

RUN NO. 1394/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1394/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA		CPBQ	CPALPH	CPBETA	CPM
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA					CPTD
1.450	-7.943	1.25102	172.02730	-.32785	-.15482	.05181	.02447	1.41918	3.11690	-.03566		
1.450	-6.906	1.24781	170.88220	-.28794	-.13493	.05303	.02485	1.42629	3.14224	-.02766		
1.450	-5.901	1.24701	169.35320	-.24593	-.11453	.05179	.02412	1.43169	3.16159	-.02129		
1.450	-4.896	1.24236	167.28350	-.20465	-.09479	.05165	.02392	1.43567	3.17589	-.01587		
1.450	-3.882	1.23952	164.22390	-.16352	-.07525	.05259	.02420	1.44147	3.19680	-.00936		
1.450	-2.864	1.22882	159.34230	-.11865	-.05446	.05029	.02308	1.44398	3.20590	-.00667		
1.450	-1.834	1.20066	150.50070	-.07585	-.03476	.04854	.02224	1.44539	3.21102	-.00503		
1.450	-.781	1.12349	131.66660	-.03392	-.01248	.04784	.02183	1.44909	3.24446	-.00096		
1.450	.281	.94559	83.32231	.01013	.00461	.04190	.01907	1.45173	3.23406	-.00203		
1.450	1.175	.78970	40.89900	.04833	.02204	.03575	.01630	1.44996	3.22760	-.00015		
1.450	2.113	.74902	23.90144	.08586	.03927	.03355	.01534	1.44708	3.21715	-.00313		
GRADIENT		-.07781	-21.91663	.04151	.01911	-.00278	-.00131	.00178	.00645	.00197		

## PARAMETRIC DATA

	RUN NO.	1438/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	1.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA						CPTD
1.471	-7.882	1.24254	171.94760	.34010	.16076	.05440	.02571	1.44369	3.20483				.03569
1.471	-6.913	1.22770	170.94690	.30132	.14123	.05440	.02550	1.45147	3.23311				.02694
1.471	-5.908	1.22837	169.43210	.25683	.11973	.05439	.02535	1.45593	3.24940				.02150
1.471	-4.903	1.22203	167.40200	.21287	.09874	.05387	.02499	1.46098	3.26759				.01638
1.471	-3.888	1.21490	164.38180	.16889	.07805	.05370	.02481	1.46363	3.27763				.01273
1.471	-2.871	1.20813	159.50050	.12396	.05708	.05321	.02450	1.46637	3.28773				.00929
1.471	-1.843	1.18276	150.73830	.07906	.03636	.05164	.02375	1.46817	3.29438				.00800
1.471	-800	1.11363	131.56280	.03405	.01565	.04926	.02264	1.46819	3.29446				.00770
1.471	.260	.95450	83.83734	.01142	.00525	.04265	.01960	1.46842	3.29529				.00745
1.471	1.159	.80849	41.41397	.04947	.02274	.03646	.01676	1.46873	3.29646				.00713
1.471	2.104	.76734	24.0938	.08993	.04128	.03436	.01577	1.46958	3.29959				.00581
GRADIENT				.04323	.01997	-.00302	-.00142	.00110	.00404				.00128

RUN NO. 1405/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1405/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA		CPALPH	CPBQ	CPBETA		CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA							CPTD
1.496	-7.947	1.21466	172.14480	.35464	.16835	.05291	.02511	1.46971	3.30005					.03438
1.496	-6.916	1.21119	171.02560	.31479	.14942	.05501	.02611	1.46982	3.30046					.03428
1.496	-5.906	1.21236	169.51090	.27112	.12709	.05501	.02579	1.48113	3.34245					.02142
1.496	-4.902	1.20906	167.48110	.22574	.10581	.05490	.02573	1.48091	3.34163					.02139
1.496	-3.892	1.20503	164.46110	.18048	.08460	.05643	.02645	1.48071	3.34088					.02155
1.496	-2.878	1.19276	159.69850	.13320	.06219	.05534	.02583	1.48424	3.35406					.01751
1.496	-1.852	1.17058	150.93640	.08690	.04015	.05462	.02524	1.49374	3.38967					.00697
1.496	-.814	1.10646	131.87070	.03961	.01830	.05308	.02453	1.49384	3.39003					.00691
1.496	.247	.95465	84.15433	.01047	.00484	.04685	.02164	1.49398	3.39058					.00674
1.496	1.157	.81511	41.29512	.05357	.02477	.04100	.01896	1.49313	3.38739					.00748
1.496	2.104	.78360	24.29726	.09576	.04426	.03812	.01762	1.49364	3.38929					.00725
GRADIENT				.04603	.02149	-.00260	-.00126	.00215	.00803					.00240

RUN NO. 1428/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1428/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA		CPALPH	CPBQ	CPBETA		CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA							CPTD
1.517	-7.947	1.21737	172.14510	.41192	.19453	.06325	.02987	1.49947	3.41128					.02830
1.517	-6.916	1.21351	171.02590	.37152	.17545	.06501	.03070	1.50032	3.41448					.02811
1.517	-5.913	1.21153	169.55060	.31723	.14980	.06515	.03076	1.49954	3.41154					.02813
1.517	-4.902	1.21111	167.48120	.26812	.12661	.06597	.03115	1.50067	3.41580					.02782
1.517	-3.893	1.20432	164.50070	.21377	.10098	.06875	.03248	1.50010	3.41367					.02825
1.517	-2.908	1.20356	159.73870	.15402	.07278	.06358	.03004	1.49939	3.41099					.02861
1.517	-1.853	1.17024	151.01560	.09848	.04651	.05926	.02799	1.50022	3.41410					.02799
1.517	-.808	1.10243	131.91930	.04194	.01981	.04941	.02333	1.50060	3.41553					.02787
1.517	.246	.95896	84.43156	.00230	.00109	.03058	.01445	1.49979	3.41246					.02854
1.517	1.157	.81426	41.45361	.04689	.02216	.03750	.01772	1.50006	3.41350					.02822
1.517	2.102	.77704	24.21822	.10014	.04731	.04184	.01977	1.50001	3.41332					.02813
GRADIENT				.02455	-.00516	-.00244	-.00044	.00004	-.00002					.00002

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 501

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM037) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.543	-7.946	1.21118	172.18430	-.39214	-.18595	.06319	.02996	1.52624	3.51340
1.543	-6.915	1.21193	171.02570	-.33371	-.15825	.06273	.02975	1.52613	3.51298
1.543	-5.911	1.21474	169.51110	-.27278	-.12935	.05850	.02774	1.52631	3.51366
1.542	-4.907	1.20977	167.48110	-.21577	-.10229	.05388	.02554	1.52618	3.51318
1.554	-3.893	1.20200	164.50060	-.15869	-.07634	.04963	.02388	1.52619	3.51320
1.554	-2.878	1.19374	159.69850	-.11221	-.05398	.04271	.02055	1.52601	3.51252
1.554	-1.847	1.16830	150.97590	-.07100	-.03415	.04023	.01935	1.52641	3.51406
1.543	-.811	1.10641	131.87970	-.03362	-.01594	.03852	.01827	1.52618	3.51317
1.543	.246	.95863	84.43156	.00416	.00197	.03507	.01663	1.52580	3.51169
1.554	1.160	.81873	41.49315	.03574	.01720	.03114	.01498	1.52634	3.51379
1.554	2.101	.77739	24.21820	.07100	.03416	.03128	.01505	1.52583	3.51181
GRADIENT	-.06713	-21.90051	.03975	.01900	-.00325	-.00155	-.00003	-.00012	-.00004

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM038) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
.599	-7.904	2.26063	165.12480	-.333225	-.06693	.09760	.01966	.56962	1.24615
.599	-6.881	2.25302	163.08540	-.28875	-.05796	.0644	.01936	.57685	1.25296
.600	-5.867	2.24439	160.45220	-.24529	-.04910	.09587	.01919	.58284	1.25868
.600	-4.858	2.24014	156.86910	-.20230	-.04030	.09448	.01882	.58773	1.26341
.600	-3.840	2.22685	151.86020	-.16105	-.03201	.09405	.01869	.59149	1.26708
.600	-2.811	2.20299	144.39610	-.11760	-.02336	.09230	.01833	.59504	1.27058
.601	-1.776	2.15788	132.73500	-.07289	-.01446	.08904	.01767	.59744	1.27295
.601	-.745	2.07744	114.06590	-.02994	-.00594	.08563	.01698	.59906	1.27457
.600	.265	1.95506	87.35843	.01024	.00203	.08077	.01599	.59910	1.27461
.600	1.223	1.85951	61.28371	.04967	.00981	.07774	.01536	.59909	1.27460
.600	2.191	1.78931	42.85181	.08990	.01777	.07578	.01498	.59899	1.27449
GRADIENT	-.06832	-16.92133	.04152	.00825	-.00295	-.00060	-.00015	.00153	.00120

## PARAMETRIC DATA

	RUN NO.	1347 / O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD
.800	-7.919	2.18161	165.39970	-.31700	.09596	.09068	.02745	.76923
.800	-6.895	2.17272	163.40010	-.27633	.08318	.09038	.02721	.77624
.800	-5.889	2.17225	160.76800	-.23609	.07061	.08893	.02660	.78220
.800	-4.881	2.16562	157.26430	-.19469	.05794	.08791	.02616	.78741
.800	-3.865	2.15252	152.33490	-.15425	.04577	.08731	.02591	.79211
.800	-2.851	2.13575	144.99040	-.11343	.03352	.08606	.02543	.79489
.800	-1.828	2.10295	133.44880	-.07247	.02136	.08323	.02454	.79700
.800	-.810	2.04021	114.97830	-.03211	.00946	.08070	.02377	.79843
.800	.191	1.95569	88.35043	.00636	.00187	.07785	.02291	.79886
.800	1.155	1.89509	62.23575	.04441	.01306	.07623	.02242	.79882
.800	2.140	1.83716	43.44679	.08399	.02468	.07496	.02203	.79852
.799	GRADIENT	.04956	-16.97850	.03962	.01174	-.00205	-.00065	.00148

RUN NO. 1337 / O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1337 / O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD
.900	-7.896	2.24720	164.96770	-.30199	-.10442	.09007	.03114	.87071
.900	-6.892	2.19005	163.32150	-.26455	-.09085	.08611	.02957	.87683
.900	-5.884	2.18267	160.72850	-.22584	-.07708	.08525	.02909	.88261
.900	-4.866	2.17520	157.18500	-.18628	-.06328	.08426	.02863	.88786
.900	-3.856	2.16575	152.21620	-.14774	-.04998	.08357	.02827	.89183
.900	-2.837	2.14673	144.83180	-.10826	-.03650	.08208	.02767	.89507
.900	-1.812	2.10747	133.29000	-.06900	-.02321	.07961	.02677	.89726
.900	-.794	2.04291	114.74040	-.03051	-.01025	.07722	.02593	.89840
.900	.206	1.95536	88.11246	.00623	.00209	.07452	.02501	.89891
.900	1.169	1.88829	61.99783	.04277	.01435	.07288	.02446	.89924
.900	2.144	1.83032	43.44672	.07999	.02683	.07147	.02398	.89931
.900	GRADIENT	-.05254	-16.98892	.03792	.01282	-.00199	-.00072	.00154

RUN NO. 1326 / O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1326 / O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD
1.099	-7.940	2.05302	165.87120	-.27453	-.11256	.07401	.03035	.1.07278
1.100	-6.917	2.04965	163.91240	-.24007	-.09778	.07331	.02986	.1.07900
1.101	-5.915	2.04933	161.39980	-.20542	-.08316	.07215	.02921	.1.08495
1.100	-4.909	2.04093	158.01540	-.17029	-.06857	.07139	.02875	.1.08900
1.100	-3.914	2.03424	153.24540	-.13548	-.05429	.07108	.02848	.1.09269
1.100	-2.910	2.01747	146.09930	-.09994	-.03991	.06994	.02793	.1.09564
1.100	-1.907	2.00322	134.75690	-.06518	-.02597	.06818	.02716	.1.09779
1.100	-.921	1.97667	116.64410	-.03117	-.01240	.06724	.02675	.1.09870
1.100	.066	1.95670	90.17535	.00109	.00043	.06721	.02673	.1.09942
1.100	1.035	1.95147	63.94147	.03440	.01368	.06778	.02694	.1.09912
1.100	2.039	1.94046	45.11168	.06897	.02741	.06815	.02708	.1.09901
		-.01592	-17.06296	.03435	.01376	-.00058	-.00028	.00138

RUN NO. 1326 / O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM038) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1372/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPM	CPTD
1.249	-7.933	2.14780	165.51740	-28238	-12499	.07904	.03499	1.22068	2.46830	-.03498
1.250	-6.901	2.14562	163.47890	-24685	-.10847	.07903	.03472	1.22717	2.48765	-.02731
1.250	-5.895	2.14015	160.88600	21146	-.09225	.07794	.03400	1.23357	2.50688	-.01981
1.251	-4.885	2.13631	157.38270	-17406	-.07558	.07685	.03337	1.23842	2.52152	-.01478
1.250	-3.881	2.12782	152.49340	-13791	-.05962	.07647	.03306	1.24093	2.52913	-.01071
1.251	-2.865	2.10981	145.18850	-10116	-.04359	.07534	.03246	1.24485	2.54104	-.00692
1.250	-1.850	2.07878	133.76600	-6503	-.02793	.07306	.03138	1.24633	2.54553	-.00411
1.250	-.841	2.03106	115.33550	-2988	-.01281	.07153	.03067	1.24759	2.54940	-.00247
1.250	.160	1.96011	88.74720	.00456	.00196	.07020	.03008	1.24822	2.55130	-.00183
1.249	1.132	1.91878	62.63231	.03878	.01661	.06930	.02968	1.24868	2.55091	-.00157
1.250	2.124	1.86699	43.80339	.07399	.03171	.06742	.02889	1.24826	2.55142	-.00174
GRADIENT		-.04065	-16.98076	.03529	.01525	-.00141	-.00067	.00138	.00420	.00183

	RUN NO.	1383/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPM	CPTD
1.400	-7.936	2.13039	165.59610	-31119	-.14506	.08930	.04163	1.36894	2.94190	-.03611
1.400	-6.910	2.12965	163.55770	-27296	-.12623	.08831	.04084	1.37645	2.96761	-.02772
1.400	-5.900	2.12498	160.96500	-23359	-.10730	.08716	.04004	1.38194	2.98651	-.02091
1.400	-4.897	2.12238	157.46170	-19352	-.08840	.08565	.03913	1.38661	3.00262	-.01532
1.400	-3.883	2.11214	152.57240	-15403	-.07003	.08541	.03883	1.39105	3.01802	-.01045
1.400	-2.875	2.09699	145.30730	-11217	-.05080	.08423	.03815	1.39431	3.02938	-.00660
1.400	-1.860	2.07010	133.88500	-7162	-.03237	.08126	.03672	1.39580	3.03455	-.00444
1.400	-.854	2.02591	115.53380	-3314	-.01496	.07943	.03585	1.39702	3.03884	-.00312
1.400	.146	1.96179	88.98523	.00499	.00225	.07802	.03518	1.39814	3.04274	-.00226
1.399	1.119	1.92655	62.83060	.04263	.01922	.07722	.03481	1.39743	3.04025	-.00219
1.400	2.113	1.87936	44.00159	.08144	.03671	.07502	.03382	1.39846	3.04386	-.00179
GRADIENT		-.03654	-16.97136	.03919	-.01781	-.00161	-.00080	.00152	.00529	.00179

	RUN NO.	1395/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPM	CPTD
1.449	-7.907	2.23943	165.20300	-32670	-.15448	.09684	.04579	1.41730	3.11021	-.03720
1.449	-6.875	2.24120	163.08490	-28634	-.13437	.09636	.04522	1.42368	3.13291	-.02937
1.450	-5.863	2.22806	160.49130	-24513	-.11432	.09453	.04409	1.42961	3.15409	-.02294
1.450	-4.848	2.22240	156.86850	-20250	-.09392	.09314	.04320	1.43546	3.17513	-.01709
1.450	-3.831	2.20999	151.85970	-16174	-.07456	.09343	.04307	1.44071	3.19406	-.01094
1.450	-2.807	2.18973	144.39590	-11713	-.05377	.09200	.04223	1.44450	3.20776	-.00672
1.450	-1.777	2.14427	132.77460	-7353	-.03372	.08873	.04069	1.44477	3.20876	-.00582
1.450	-.748	2.06542	114.06600	-3194	-.01463	.08602	.03939	1.44590	3.21285	-.00439
1.450	.258	1.95410	87.35870	.0899	.00411	.08262	.03779	1.44732	3.21800	-.00309
1.450	1.219	1.86965	61.32343	.04835	.02211	.07990	.03654	1.44710	3.21720	-.00344
1.449	2.188	1.78887	42.77289	.08879	.04062	.07618	.03485	1.44640	3.21468	-.00140
GRADIENT		-.06515	-16.96911	.04143	-.01910	-.00256	-.00125	.00140	.00507	.00175

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM038) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1439/ O		RN/L = 2.49		GRADIENT INTERVAL = -5.00/ 5.00		BETA = 2.000		PHI = 180.000	
		BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBQ	CPBETA	CPBQ	CPBETA
MACH	ALPHA	2.22339	165.24230	.34075	.16137	.0923	.04699	1.44201	3.19877	.03785	CPTD
1.471	-7.914	2.21878	163.16350	.30013	.14081	.0894	.04642	1.45010	3.22811	.02846	
1.471	-6.874	2.21453	160.53090	.25587	.11940	.0814	.04580	1.45519	3.24670	.02256	
1.471	-5.871	2.20491	156.98720	.21187	.09836	.0637	.04474	1.45939	3.26208	.01765	
1.471	-4.859	2.19372	151.97860	.16760	.07744	.0637	.04453	1.46328	3.27635	.01300	
1.471	-3.845	2.17372	144.55450	.12165	.05606	.0929	.04391	1.46600	3.28637	.01022	
1.471	-2.823	2.13508	132.89370	.07716	.03546	.09337	.04290	1.46837	3.29513	.00747	
1.471	-1.794	2.05596	114.30410	.03306	.01519	.08983	.04126	1.46852	3.29566	.00707	
1.471	-.767	1.95972	87.63644	.00971	.00446	.08569	.03936	1.46863	3.29605	.00717	
1.471	.237	1.87997	61.60106	.05064	.02324	.08314	.03815	1.46981	3.30043	.00591	
1.471	1.199	1.80802	42.97096	.09247	.04241	.07965	.03653	1.47021	3.30189	.00536	
1.471	2.176	1.80973	-16.96262	.04323	.01997	-.00254	-.00123	.00138	.00508	.00155	
RUN NO.		1406/ O		RN/L = 2.49		GRADIENT INTERVAL = -5.00/ 5.00		BETA = 2.000		PHI = 180.000	
		BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBQ	CPBETA	CPBQ	CPBETA
MACH	ALPHA	2.21002	165.28150	.35291	.16779	.0963	.04737	1.46847	3.29547	.03596	CPTD
1.496	-7.918	2.20375	163.24240	.31224	.14841	.10193	.04845	1.46890	3.29707	.03562	
1.496	-6.885	2.19967	160.60980	.26989	.12648	.10120	.04743	1.48119	3.34267	.02116	
1.496	-5.877	2.19087	157.06630	.22328	.10463	.10000	.04686	1.48119	3.34266	.02107	
1.496	-4.860	2.18137	152.09750	.17806	.08343	.10022	.04696	1.48120	3.34272	.02108	
1.496	-3.851	2.15886	144.71290	.13011	.06017	.10009	.04629	1.49286	3.38637	.00783	
1.496	-2.829	2.12108	133.09190	.08376	.03869	.09859	.04553	1.49412	3.39110	.00649	
1.496	-1.803	2.05135	114.50240	.03711	.01714	.09637	.04450	1.49403	3.39076	.00635	
1.496	-.781	2.06204	87.87442	.00886	.00409	.09305	.04298	1.49443	3.39226	.00647	
1.496	.222	1.88833	61.79938	.05352	.02472	.09004	.04159	1.49393	3.39037	.00644	
1.496	1.186	1.81991	43.12949	.09760	.04507	.08613	.03978	1.49425	3.39159	.00640	
1.496	2.167	1.05574	-16.97437	.04574	.02133	-.00202	-.00103	.00190	.00711	.00214	
RUN NO.		1429/ O		RN/L = 2.49		GRADIENT INTERVAL = -5.00/ 5.00		BETA = 2.000		PHI = 180.000	
		BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBQ	CPBETA	CPBQ	CPBETA
MACH	ALPHA	1.623	165.32100	.40704	.19237	.11747	.05552	1.49937	3.41091	.02847	CPTD
1.518	-7.914	2.20532	163.24260	.36911	.17441	.11927	.05635	1.50026	3.41425	.02812	
1.518	-6.885	2.20175	160.61010	.31588	.14926	.11969	.05656	1.50040	3.41479	.02806	
1.518	-5.877	2.18926	157.10590	.26388	.12481	.11849	.05605	1.49917	3.41015	.02877	
1.518	-4.862	2.18306	152.09760	.21039	.09949	.12162	.05752	1.49922	3.41034	.02861	
1.518	-3.851	2.15874	144.75260	.15039	.07111	.11678	.05522	1.50045	3.41497	.02820	
1.518	-2.830	2.12161	133.13160	.09724	.04597	.10991	.05196	1.49995	3.41309	.02818	
1.518	-1.803	2.05717	114.54210	.04308	.02038	.10129	.04792	1.49804	3.40587	.02911	
1.518	-.783	1.95730	87.87444	.00641	.00303	.09410	.04449	1.49877	3.40862	.02883	
1.518	.224	1.88431	61.83908	.05281	.02495	.09421	.04452	1.49971	3.41218	.02831	
1.518	1.185	1.81558	43.12965	.10610	.05015	.09524	.04502	1.49957	3.41165	.02859	
1.518	2.165	.05640	-16.97750	.05241	.02478	-.00446	-.00211	.00002	.00008	.00000	

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM038) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.543	-7.916	2.21208	165.28180	-39205	-18563	-11584	.05485	1.52790	3.51980	-.02467
1.542	-6.884	2.20450	163.24250	-33214	-15727	-11155	.05282	1.52716	3.51695	-.02488
1.543	-5.876	2.20035	160.60990	-27615	-13075	-10881	.05152	1.52764	3.51880	-.02472
1.543	-4.865	2.19329	157.06650	-21851	-10347	-10086	.04776	1.52792	3.51988	-.02462
1.543	-3.851	2.18168	152.09750	-16558	-07846	-09305	.04409	1.52758	3.51859	-.02487
1.543	-2.829	2.15959	144.71300	-11684	-05537	.08469	.04013	1.52770	3.51902	-.02473
1.543	-1.804	2.12085	133.13150	-07425	-03519	.07754	.03675	1.52720	3.51711	-.02486
1.543	-.780	2.05229	114.50240	-03518	-01666	.07445	.03527	1.52746	3.51812	-.02477
1.543	.223	1.95702	87.87444	.00116	.00055	.07169	.03396	1.52739	3.51784	-.02482
1.543	1.187	1.88884	61.83899	.03659	.01733	.07129	.03377	1.52754	3.51842	-.02489
1.542	2.165	1.81583	43.12964	.07475	.03542	.07158	.03392	1.52666	3.51503	-.02513
	GRADIENT	-.05643	-16.96577	.04089	.01937	-.00422	-.00200	-.00011	-.00044	-.00004

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM039) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.600	-7.870	3.24587	158.69650	-33086	-.06694	.14084	.02849	.56834	1.24496	-.02441
.600	-6.847	3.24028	155.89610	-28791	-.05794	.13985	.02815	.57511	1.25131	-.01918
.600	-5.836	3.22751	152.42260	-24483	-.04907	.13902	.02787	.58113	1.25704	-.01466
.601	-4.820	3.21729	147.84070	-20009	-.04003	.13745	.02750	.58676	1.26246	-.01087
.601	-3.798	3.19584	141.75380	-15832	-.03161	.13520	.02700	.59112	1.26672	-.00780
.601	-2.772	3.16450	133.41010	-11616	-.02310	.13394	.02663	.59422	1.26977	-.00497
.600	-1.746	3.11798	121.89900	-.07323	-.01453	.13044	.02588	.59640	1.27192	-.00315
.601	-.728	3.04728	106.54740	-.03017	-.00598	.12713	.02521	.59801	1.27352	-.00209
.601	.283	2.96712	87.90909	.01076	.00214	.12330	.02448	.59845	1.27396	-.00210
.601	1.256	2.89045	69.74646	.05061	.01004	.12101	.02400	.59893	1.27443	-.00160
.601	2.230	2.83468	54.63287	.09202	.01824	.11991	.02376	.59861	1.27412	-.00157
	GRADIENT	-.05732	-13.71042	.04143	.00826	-.00270	-.00057	.00161	.00159	.00125

## PARAMETRIC DATA

	RUN NO.	1348/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA		CPTD			
.800	-7.894	3.17322	158.93270	-3.17178	-.09618	.13262	.04022		1.47582			
.800	-6.871	3.16558	156.17210	-.27591	-.08317	.13068	.03939		1.48570			
.800	-5.863	3.15900	152.69930	-.23585	-.07070	.12979	.03891		1.49465			
.800	-4.855	3.14850	148.19720	-.19387	-.05783	.12875	.03841		1.50319			
.800	-3.840	3.13313	142.15060	-.15301	-.04546	.12704	.03774		1.50934			
.800	-2.821	3.10603	133.88660	-.11308	-.03347	.12552	.03715		1.51441			
.800	-1.811	3.06982	122.53480	-.07210	-.02128	.12355	.03647		1.51800			
.800	-7.799	3.02249	107.18370	-.03220	-.00949	.12046	.03550		1.52022			
.800	.208	2.96561	88.58531	.00686	.00202	.11827	.03483		1.52120			
.800	1.184	2.91326	70.38281	.04587	.01350	.11687	.03440		1.52135			
.800	2.163	2.87405	55.22917	.08573	.02523	.11597	.03413		1.52133			
GRADIENT	-.04133	-13.74873	.03973	.01179	-.00196	-.00065	.00167		.00249			

RUN NO. 1338/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1338/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA		CPBQ	CPALPH	CPBETA	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA					
.900	-7.891	3.18554	158.89330	-.30274	-.10494	.12717	.04408		.86859			
.900	-6.864	3.17619	156.13250	-.26389	-.09083	.12469	.04292		.87492			
.900	-5.856	3.17340	152.62030	-.22568	-.07722	.12392	.04240		.88051			
.900	-4.840	3.15683	148.11760	-.18579	-.06322	.12313	.04190		.88587			
.900	-3.827	3.14063	142.07100	-.14635	-.04957	.12201	.04133		.89033			
.900	-2.811	3.11857	133.76760	-.10768	-.03636	.12039	.04065		.89385			
.900	-1.792	3.07562	122.33620	-.06859	-.02309	.11831	.03983		.89576			
.900	-.782	3.02609	106.98510	-.03023	-.01016	.11526	.03874		.89744			
.900	.223	2.96316	88.42636	.00704	.00236	.11320	.03802		.89760			
.900	1.198	2.91203	70.26349	.00439	.01491	.11170	.03750		.89830			
.900	2.177	2.86409	55.07037	.08233	.02764	.11080	.03720		.89818			
GRADIENT	-.04391	-13.75583	.03809	.01289	-.00193	-.00072			.00165			

RUN NO. 1327/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1327/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA		CPBQ	CPALPH	CPBETA	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA					
1.099	-7.937	3.04514	159.40490	-.27543	-.11321	.10891	.04476		1.07052			
1.100	6.912	3.04238	156.68500	-.23988	-.09794	.10840	.04426		1.07712			
1.100	-5.909	3.04013	153.29260	-.20587	-.08352	.10762	.04366		1.08278			
1.100	-4.904	3.03260	148.87030	-.17052	-.06878	.10687	.04311		1.08760			
1.100	-3.904	3.02058	142.98320	-.13529	-.05432	.10611	.04260		1.09138			
1.100	-2.917	2.99453	134.87830	-.10098	-.04040	.10464	.04186		1.09433			
1.100	-1.896	3.00786	123.29050	-.06513	-.02598	.10390	.04146		1.09624			
1.100	-.924	2.96669	108.37610	-.03135	-.01249	.10199	.04063		1.09775			
1.100	.079	2.96136	89.77826	.00177	.00070	.10160	.04043		1.09818			
1.100	1.067	2.95346	71.49614	.03558	.01415	.10212	.04062		1.09834			
1.100	2.057	2.94431	56.30206	.07041	.02800	.10251	.04077		1.09806			
GRADIENT	-.01309	-13.82970	.03451	.01385	-.00074				.00038			

## PARAMETRIC DATA

	RUN NO.	1373/ O	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
1.249	-7.914	159.05080	.28274	-12541	-11537	.05117	1.21878	2.46266	.03721					
1.250	-6.882	156.25100	.24571	-10825	.11571	.05098	1.22525	2.48192	.02997					
1.250	-5.876	152.81790	.21092	-.09226	.11464	.05014	1.23158	2.50087	.02244					
1.250	-4.869	148.31580	.17409	-.07568	.11335	.04928	1.23656	2.51587	.01624					
1.250	-3.858	142.26990	.13713	-.05940	.11143	.04827	1.23998	2.52624	.01241					
1.250	-2.845	134.08530	.10081	-.04351	.1069	.04777	1.24289	2.53506	.00880					
1.250	-1.834	122.65440	.06446	-.02773	.10891	.04686	1.24521	2.54214	.00579					
1.250	-.828	3.01265	.107.42205	-.02903	.01247	.10649	.04573	1.24669	.00381					
1.250	1.177	2.97004	.88.86374	.00559	.00240	.10485	.04498	1.24740	.00290					
1.250	1.157	2.93378	.70.70062	.04032	.01729	.10410	.04465	1.24773	.00274					
1.250	2.146	2.90188	.55.46727	.07572	.03248	.10375	.04450	1.24765	.00267					
GRADIENT	-.033323	-13.74155	.03549	.01535	-.00147	-.00072	-.000156	.00475	.00194					

RUN NO. 1384/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1384/ O	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
1.400	-7.924	159.12990	-.31126	-.14552	.12827	.05997	1.36645	2.93341	-.03914					
1.400	-6.889	156.32990	-.27228	-.12622	.12805	.05936	1.37417	2.95977	-.03024					
1.400	-5.884	152.89690	-.23321	-.10734	.12719	.05854	1.38040	2.98119	-.02293					
1.400	-4.877	148.39500	-.19287	-.08829	.12534	.05737	1.38484	2.99650	-.01739					
1.400	-3.871	142.38860	-.15291	-.06965	.12465	.05677	1.38953	3.01274	-.01224					
1.400	-2.858	134.12530	-.11262	-.05107	.12318	.05585	1.39370	3.02725	-.00765					
1.400	-1.846	122.77370	-.07181	-.03249	.12120	.05483	1.39552	3.03360	-.00541					
1.400	-.842	107.54190	-.03211	-.01450	.11822	.05339	1.39712	3.03917	-.00366					
1.400	.162	2.97615	.89.02272	.00675	.00305	.11691	.05275	1.39757	3.04075	-.00281				
1.399	1.144	2.93864	.70.81995	.04496	.02027	.11594	.05229	1.39737	3.04005	-.00238				
1.400	2.136	2.90943	.55.54681	.08430	.03801	.11582	.05223	1.39798	3.04218	-.00220				
GRADIENT	-.02983	-13.74271	.03951	.01798	-.00157	-.00082	-.000152	.00598	.00204					

RUN NO. 1397/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1397/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
1.449	-7.881	158.73580	-.32700	-.15499	.13873	.06576	1.41471	3.10102	-.03977					
1.452	-6.841	155.89540	-.28595	-.13460	.13776	.06484	1.42874	3.13350	-.03191					
1.450	-5.831	152.42210	-.24430	-.11417	.13706	.06406	1.42874	3.15098	-.02487					
1.450	-4.816	147.84020	-.20136	-.09357	.13437	.06244	1.43358	3.16836	-.01904					
1.450	-3.797	133.175350	-.15954	-.07380	.13384	.06191	1.43756	3.18269	-.01438					
1.450	-2.771	133.37040	-.11718	-.05386	.13334	.06129	1.44296	3.20221	-.00811					
1.450	-1.750	121.85950	-.07375	-.03380	.13065	.05988	1.44482	3.20893	-.00534					
1.450	-.735	106.50810	-.03100	-.01420	.12684	.05810	1.44602	3.21327	-.00451					
1.450	.274	87.94916	.01030	.00472	.12380	.05668	1.44656	3.21525	-.00405					
1.450	1.248	69.78650	.05075	.02322	.12194	.05580	1.44651	3.21506	-.00360					
1.449	2.224	54.67285	.09195	.04202	.12171	.05563	1.44728	3.21787	-.00246					
GRADIENT	-.05432	-13.72689	.04170	.01925	-.00213	-.000111	-.00111	.00181	.00655	.00217				

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
RUN NO.	1440/ 0	RN/L =	2.49	GRADIENT	INTERVAL	= -5.00/	5.00		
1.471	-7.885	3.21516	158.77510	-33982	-16127	-14316	.06794	1.43951	3.18974
1.471	-6.853	3.20767	155.97450	-29837	-14037	-14290	.06723	1.44796	3.22033
1.471	-5.839	3.19464	152.50110	-25547	-11933	-14140	.06604	1.45411	3.24273
1.471	-4.824	3.18519	147.91950	-21078	-.09800	-14008	.06513	1.45833	3.25819
1.471	-3.813	3.16553	141.87270	-16614	-.07690	-13921	.06443	1.46213	3.27211
1.471	-2.791	3.13945	133.52930	-12067	-.05566	-13764	.06349	1.46553	3.28464
1.471	-1.767	3.09646	122.01850	-07650	-.03521	-13544	.06234	1.46738	3.29146
1.471	-.755	3.03759	106.70690	-.03216	-.01477	-13286	.06101	1.46892	3.29716
1.470	.256	2.96506	88.06868	.01132	.00519	-12958	.05946	1.46926	3.29840
1.471	1.229	2.90484	69.94550	.05321	.02440	-12723	.05835	1.46993	3.30088
1.471	2.209	2.85516	54.79199	.09504	.04359	-12544	.05754	1.46993	3.30087
GRADIENT	-.04955	-13.73449	.04348	.02011	-.00223	-.00115	.00158	.00580	.00181

RUN NO. 1407/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
RUN NO.	1407/ 0	RN/L =	2.49	GRADIENT	INTERVAL	= -5.00/	5.00		
1.496	-7.892	3.19719	158.85380	-.35184	-.16754	-14543	.06925	1.46671	3.28900
1.496	-6.856	3.18916	156.05320	-.30952	-.14720	-14665	.06974	1.46251	3.29466
1.496	-5.845	3.18436	152.54080	-.26789	-.12569	-14839	.06962	1.48031	3.33938
1.496	-4.833	3.17332	147.99880	-.22215	-.10368	-14648	.06836	1.48503	3.35699
1.496	-3.821	3.15685	141.95220	-.17578	-.08206	-14508	.06773	1.48461	3.35544
1.496	-2.798	3.12736	133.64840	-.12950	-.06045	-14545	.06789	1.48477	3.35602
1.495	-1.781	3.08934	122.17740	-.08247	-.03849	-14359	.06701	1.48433	3.35438
1.496	-.768	3.03495	106.82620	-.03517	-.01642	-14116	.06590	1.48482	3.35623
1.496	.241	2.96694	88.22766	.01061	.00495	-13879	.06480	1.48475	3.35595
1.496	1.216	2.91124	70.10442	.05565	.02598	-13640	.06369	1.48456	3.35524
1.496	2.194	2.86077	54.95099	.10035	.04685	-13460	.06284	1.48450	3.35504
GRADIENT	-.04671	-13.73804	.04594	.02145	-.00176	-.00082	-.00004	-.00003	-.00015

RUN NO. 1430/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
RUN NO.	1430/ 0	RN/L =	2.49	GRADIENT	INTERVAL	= -5.00/	5.00		
1.517	-7.894	3.19424	158.89340	-.40358	-.19092	-16814	.07954	1.49832	3.40691
1.518	-6.856	3.19149	156.05350	-.36462	-.17245	-17226	.08147	1.49929	3.41058
1.518	-5.846	3.18206	152.58050	-.31594	-.14935	-17201	.08131	1.49946	3.41124
1.518	-4.834	3.17165	148.03850	-.26002	-.12294	-17160	.08114	1.49912	3.40994
1.518	-3.816	3.15519	141.95210	-.20743	-.09810	-17381	.08220	1.49949	3.41135
1.518	-2.798	3.12867	133.64850	-.15017	-.07104	-17198	.08136	1.49893	3.40922
1.518	-1.780	3.09069	122.17750	-.09349	-.04420	-16377	.07742	1.50022	3.41411
1.517	-.767	3.03054	106.86580	-.04117	-.01946	-15427	.07291	1.49935	3.41082
1.518	.238	2.96256	88.30699	.00839	.00397	-15139	.07157	1.49989	3.41286
1.517	1.216	2.90641	70.10452	.05845	.02764	-14802	.07000	1.49836	3.40708
1.517	2.194	2.86198	54.99062	.11153	.05274	-14978	.07083	1.49792	3.40544
GRADIENT	-.04695	-13.73852	.05278	.02496	-.00418	-.00198	-.00014	-.00003	-.00006

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 509

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM039) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1420/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPALPH	CPBQ	CPBETA	CPALPH	CPTD
1.543	-7.891	3.19840	158.85390	-3.9889	-18907	.16719	.07925	1.52662	3.51487	-	.02550	
1.543	-6.859	3.19228	156.05350	-3.3517	.15880	.16044	.07601	1.52725	3.51729	-	.02500	
1.543	-5.844	3.18477	152.54090	-28173	-1.3344	.15936	.07548	1.52764	3.51879	-	.02468	
1.543	-4.834	3.17048	148.03830	-22303	-.10564	.15039	.07124	1.52766	3.51886	-	.02468	
1.543	-3.820	3.15665	141.95220	-17105	-.08104	.14020	.06642	1.52755	3.51844	-	.02482	
1.543	-2.798	3.12714	133.64840	-12170	-.05765	.12918	.06119	1.52753	3.51840	-	.02470	
1.543	-1.780	3.08959	122.17740	-.07736	.03665	.12061	.05714	1.52745	3.51809	-	.02492	
1.543	-767	3.03533	106.82620	-0.3726	-.01765	.11530	.05463	1.52759	3.51860	-	.02492	
1.543	.240	2.96733	88.26733	.00099	.00047	.11239	.05325	1.52728	3.51742	-	.02498	
1.543	1.215	2.90612	70.10452	.03858	.01828	.11288	.05349	1.52746	3.51812	-	.02512	
1.543	2.193	2.86166	54.99063	.07932	.03757	.11556	.05474	1.52779	3.51939	-	.02464	
GRADIENT				.04230	.02004	-.00518	-.00245	-.00000	-.00000	-	.00002	

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(TCM040) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1360/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	4.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPALPH	CPBQ	CPBETA	CPALPH	CPTD
.599	-7.846	4.23771	152.74410	-.33134	-.06707	.18379	.03720	.03659	.57233	1.24193	1.24193	-.02644
.600	-6.821	4.22102	149.45900	-.28646	-.05779	.18139	.03630	.03630	.57828	1.24869	1.24869	-.02137
.600	-5.807	4.21049	145.38300	-.24345	-.04891	.18067	.03583	.03583	.58347	1.25432	1.25432	-.01688
.600	-4.791	4.19419	140.27750	-.20033	-.04007	.17912	.03517	.03517	.58816	1.25929	1.25929	-.01274
.600	-3.770	4.16931	133.78590	-.15699	-.03132	.17630	.03517	.03517	.58816	1.26382	1.26382	-.00939
.601	-2.748	4.13489	125.51270	-.11453	-.02281	.17450	.03475	.03475	.59207	1.26765	1.26765	-.00663
.601	-1.729	4.08650	115.10170	-.07217	-.01436	.17092	.03400	.03400	.59415	1.26970	1.26970	-.00514
.600	-7.17	4.03335	102.47360	-.03014	-.00598	.16913	.03357	.03357	.59605	1.27157	1.27157	-.00347
.600	.292	3.96908	88.30133	.01121	.00222	.16701	.03309	.03309	.59673	1.27225	1.27225	-.00260
.600	1.274	3.90964	74.40704	.05237	.01038	.16448	.03261	.03261	.59699	1.27251	1.27251	-.00265
.601	2.252	3.85647	61.97815	.09385	.01864	.16229	.03223	.03223	.59703	1.27254	1.27254	-.00301
GRADIENT				-.04164	.00830	-.00238	-.00051	-.00000	.00180	.00180	.00180	.00137

## PARAMETRIC DATA

RUN NO.	1349/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	4.000	PHI	=	180.000
<b>MACH</b>	<b>ALPHA</b>	<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBETA</b>	<b>CPM</b>	<b>MPROBE</b>	<b>CPM</b>	<b>CPTD</b>	
.800	-7.878	4.15928	153.02010	-.31656	-.09628	.17457	.05309	.76365	1.47125	.03558		
.799	-6.856	4.14817	149.73580	-.27536	-.08316	.17147	.05179	.77044	1.48088	.02865		
.800	-5.842	4.14164	145.66040	-.23556	-.07074	.17062	.05124	.77711	1.49046	.02237		
.800	-4.833	4.12929	140.59520	-.19410	-.05802	.16855	.05038	.78267	1.49856	.01716		
.800	-3.822	4.10855	134.18370	-.15267	-.04543	.16690	.04966	.78766	1.50588	.01231		
.800	-2.809	4.08473	125.95100	-.11148	-.03307	.16531	.04904	.79140	1.51143	.00888		
.800	-1.795	4.05244	115.54060	-.07176	-.02122	.16314	.04824	.79351	1.51459	.00633		
.800	-.792	4.01214	102.99240	-.03119	-.00921	.16122	.04759	.79528	1.51723	.00459		
.800	.216	3.97119	88.82018	.00862	.00254	.15948	.04701	.79600	1.51831	.00356		
.800	1.200	3.93057	74.92563	.04755	.01403	.15767	.04650	.79650	1.51906	.00349		
.800	2.182	3.88998	62.45668	.08781	.02588	.15679	.04621	.79617	1.51856	.00337		
	<b>GRADIENT</b>	<b>-.03493</b>	<b>-11.46822</b>	<b>.04005</b>	<b>.01190</b>	<b>-.00175</b>	<b>-.00061</b>	<b>.00183</b>	<b>.00273</b>	<b>.00188</b>		

RUN NO.	1339/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	4.000	PHI	=	180.000
<b>MACH</b>	<b>ALPHA</b>	<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBETA</b>	<b>CPM</b>	<b>MPROBE</b>	<b>CPM</b>	<b>CPTD</b>	
.900	-7.870	4.16930	152.98040	-.30296	-.10534	.16653	.05790	.86534	1.62978	-.03745		
.899	-6.842	4.16110	149.65650	-.26308	-.09078	.16452	.05677	.87184	1.64101	-.02998		
.900	-5.832	4.14977	145.62500	-.22500	-.07719	.16356	.05611	.87786	1.65153	.02370		
.900	-4.818	4.13752	140.51550	-.18591	-.06343	.16172	.05517	.88325	1.66106	.01794		
.900	-3.806	4.11896	134.06440	-.14604	-.04959	.15971	.05424	.88796	1.66948	.01300		
.900	-2.795	4.09411	125.83170	-.10672	-.03612	.15838	.05360	.89148	1.67581	.00937		
.900	-1.780	4.05740	115.42110	-.06823	-.02303	.15626	.05274	.89420	1.68072	.00655		
.900	-.774	4.01781	102.83320	-.02956	-.00996	.15439	.05200	.89553	1.68155	.00480		
.900	.234	3.96661	88.66095	.00857	.00288	.15276	.05138	.89621	1.68438	.00376		
.900	1.214	3.92308	74.80620	.04602	.01548	.15116	.05083	.89676	1.68539	.00331		
.900	2.199	3.88474	62.33716	.08444	.02839	.15008	.05046	.89672	1.68532	.00325		
	<b>GRADIENT</b>	<b>-.03759</b>	<b>-11.47068</b>	<b>.03840</b>	<b>.01303</b>	<b>-.00170</b>	<b>-.00068</b>	<b>.00183</b>	<b>.00330</b>	<b>.00202</b>		

RUN NO.	1328/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	4.000	PHI	=	180.000
<b>MACH</b>	<b>ALPHA</b>	<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBETA</b>	<b>CPM</b>	<b>MPROBE</b>	<b>CPM</b>	<b>CPTD</b>	
1.099	-7.928	4.04299	153.41480	-.27604	-.11383	.14476	.05969	.106759	2.05107	-.03887		
1.100	-6.901	4.03211	150.17070	-.23978	-.09817	.14398	.05895	.107470	2.06870	-.03094		
1.100	-5.904	4.03282	146.17610	-.20565	-.08366	.14365	.05844	.108018	2.08240	-.02431		
1.100	-4.898	4.01806	141.23030	-.17032	-.06890	.14277	.05775	.108532	2.09534	-.01834		
1.101	-3.898	4.01237	134.85990	-.13554	-.05456	.14067	.05663	.108952	2.10600	-.01338		
1.100	-2.902	4.00000	126.74720	-.10031	-.04021	.14045	.05630	.109231	2.11310	-.00941		
1.100	-1.906	3.98505	116.45690	-.06590	-.02634	.13913	.05561	.109419	2.11792	-.00673		
1.100	-.926	3.97120	103.94910	-.03079	-.01229	.13820	.05515	.109598	2.12250	-.00482		
1.100	.093	3.96320	89.57890	.00342	.00136	.13768	.05487	.109672	2.12441	-.00371		
1.100	1.092	3.95126	75.68425	.03796	.01512	.13748	.05477	.109685	2.12474	-.00333		
1.100	2.068	3.94323	63.37335	.07249	.02889	.13747	.05479	.109692	2.12492	-.00405		
	<b>GRADIENT</b>	<b>-.01140</b>	<b>-11.53209</b>	<b>.03482</b>	<b>.01400</b>	<b>-.00074</b>	<b>-.00042</b>	<b>.00159</b>	<b>.00205</b>			

## PARAMETRIC DATA

	RUN NO.	1374/ O	RN/L =	2.49	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	4.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD					
1.249	-7.898	4.13053	153.09890	-28328	-12612	.15260	.06794	1.21600	2.45443					
1.250	-6.866	4.12580	149.77550	-24544	-10841	.15152	.06693	1.22273	2.47441					
1.250	-5.859	4.11894	145.74000	-21007	-.09216	.15125	.06636	1.22881	2.49255					
1.250	-4.849	4.10289	140.71440	-17475	-.07618	.14954	.06519	1.23391	2.50789					
1.250	-3.843	4.08750	134.30330	-13740	-.05960	.14744	.06395	1.23838	2.52140					
1.250	-2.837	4.07222	126.07110	-10042	-.04344	.14610	.06319	1.24083	2.52880					
1.250	-1.821	4.04253	115.66080	-06468	-.02789	.14448	.06230	1.24333	2.53640					
1.250	-.820	4.01060	103.15230	-02859	-.01231	.14298	.06155	1.24518	2.54203					
1.250	.186	3.97102	89.01981	.00680	.00292	.14168	.06090	1.24597	2.54443					
1.250	1.168	3.93930	75.16487	.0176	.01795	.14075	.06048	1.24613	2.54493					
1.249	2.159	3.91961	62.65546	.07729	.03321	.14012	.06020	1.24552	2.54308					
GRADIENT		-.02802	-11.46787	.03585	.01554	-.00136	-.00071	.00163	.00496					

RUN NO. 1385/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1398/ O	RN/L =	2.49	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	4.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD					
1.400	-7.865	4.16518	152.78420	-30833	-.14463	.17247	.08090	1.36373	2.92419					
1.400	-6.874	4.11035	149.85460	-27145	-.12622	.16868	.07843	1.37127	2.94986					
1.400	-5.869	4.10493	145.81930	-23222	-.10721	.16798	.07755	1.37718	2.97353					
1.400	-4.857	4.09247	140.75420	-19281	-.08844	.16598	.07613	1.38312	2.99055					
1.400	-3.856	4.07637	134.38290	-15275	-.06975	.16363	.07472	1.38718	3.00462					
1.400	-2.846	4.05951	126.15060	-11189	-.05087	.16318	.07418	1.39109	3.01817					
1.400	-1.837	4.03555	115.78030	-.07204	-.03266	.16163	.07327	1.39362	3.02698					
1.400	-.834	4.00304	103.23200	-03167	-.01432	.15966	.07221	1.39522	3.03528					
1.400	.171	3.97728	89.09975	.00782	.00353	.15829	.07152	1.39596	3.03511					
1.400	1.156	3.94903	75.24466	.04666	.02108	.15744	.07111	1.39674	3.03785					
1.400	2.146	3.91924	62.73553	.08612	.03889	.15662	.07073	1.39678	3.03800					
GRADIENT		-.02529	-11.47225	.03981	.01815	-.00134	-.00077	.00190	.00660					

RUN NO. 1398/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1398/ O	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	4.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD					
1.450	-7.810	4.26831	152.38880	-.32529	-.15471	.18305	.08706	1.41290	3.09464					
1.450	-6.817	4.20584	149.45830	-28395	-.13400	.17956	.08474	1.42017	3.12040					
1.450	-5.805	4.19619	145.38260	-24314	-.11394	.17933	.08403	1.42646	3.14283					
1.449	-4.787	4.17684	140.27690	-.20132	-.09377	.17670	.08207	1.43049	3.15726					
1.450	-3.768	4.15206	133.78560	-.15867	-.07357	.17400	.08067	1.43507	3.17372					
1.450	-2.754	4.12430	125.51290	-.11592	-.05350	.17372	.08017	1.43984	3.19093					
1.450	-1.733	4.08374	115.02280	-.07393	-.03397	.17296	.07948	1.44281	3.20166					
1.450	-.722	4.03187	102.43450	-.03086	-.01415	.17071	.07825	1.44550	3.21139					
1.450	.286	3.96771	88.26221	.01183	.00542	.16872	.07726	1.44662	3.21546					
1.450	1.268	3.91118	74.40756	.05285	.02419	.16670	.07629	1.44688	3.21642					
1.450	2.247	3.86424	62.01816	.03934	.04301	.16554	.07578	1.44631	3.21433					
GRADIENT		-.04626	-11.45301	.04200	.01943	-.00156	-.00092	.00226	.00826					

RUN NO. 1398/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

## PARAMETRIC DATA

RUN NO. 1441/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00  
 BETA PHI CPAQ CPALPH CPBQ CPBETA CPM PROBE CPTD

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	PROBE	CPTD
1.471	-7.862	4.19912	152.86190	-339598	-16181	.18605	.08865	1.43691	3.18036	-.04425
1.471	-6.828	4.19230	149.49810	-29627	-13992	.18610	.08789	1.44431	3.20708	-.03508
1.471	-5.815	4.17750	145.46180	-25492	-11934	.18683	.08747	1.45237	3.23642	-.02607
1.471	-4.801	4.16321	140.35660	-21021	-9794	.18328	.08539	1.45593	3.24940	-.02127
1.470	-3.784	4.14108	133.86550	-16608	-07700	.18148	.08414	1.45955	3.26266	-.01669
1.470	-2.768	4.11186	125.59280	-12117	-05597	.18060	.08342	1.46340	3.27679	-.01285
1.471	-1.753	4.07194	115.18210	-07715	-03554	.17848	.08222	1.46601	3.28640	-.01004
1.471	-.743	4.02588	102.55430	-03203	-01473	.17627	.08108	1.46748	3.29182	-.00847
1.471	.266	3.97169	88.38202	-01201	00552	.17362	.07980	1.46819	3.29446	-.00739
1.471	1.245	3.92145	74.56694	.05428	.02494	.17173	.07889	1.46955	3.29726	-.00692
1.471	2.231	3.87698	62.09795	.09686	.04447	.17041	.07823	1.46932	3.29864	-.00615
GRADIENT	-.04221	-11.45688	.04375	.02026	-.00192	-.00105	.00186	.00683	.00205	

RUN NO. 1408/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00  
 BETA PHI CPAQ CPALPH CPBQ CPBETA CPM PROBE CPTD

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	PROBE	CPTD
1.496	-7.869	4.18681	152.90150	-35173	-.16804	.19051	.09102	1.46378	3.27819	-.04111
1.496	-6.830	4.17865	149.53760	-30650	-.14531	.19219	.09112	1.47111	3.30526	-.03300
1.496	-5.823	4.16684	145.50160	-.26585	-.12513	.19273	.09071	1.47755	3.32911	-.02534
1.496	-4.809	4.15452	140.39660	-.22175	-.10369	.19199	.08977	1.48311	3.34983	-.01871
1.496	-3.798	4.13581	133.94540	-.17537	-.08165	.18996	.08844	1.48721	3.36515	-.01430
1.496	-2.781	4.10325	125.71220	-.12818	-.05947	.18936	.08785	1.48986	3.37510	-.01072
1.496	-1.766	4.06680	115.30170	-.08242	-.03813	.18843	.08718	1.49305	3.38709	-.00783
1.496	-.758	4.01793	102.71350	-.03514	-.01623	.18751	.08657	1.49458	3.39284	-.00582
1.496	.250	3.97347	88.54131	.01155	.00533	.18577	.08568	1.49618	3.39885	-.00467
1.496	1.232	3.92638	74.68648	.05700	.02628	.18416	.08490	1.49618	3.39887	-.00426
1.496	2.219	3.88489	62.21739	.10190	.04695	.18181	.08378	1.49595	3.39800	-.00399
GRADIENT	-.03992	-11.45147	.04611	.02144	-.00132	-.00079	-.00079	.00184	.00692	.00206

RUN NO. 1431/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00  
 BETA PHI CPAQ CPALPH CPBQ CPBETA CPM PROBE CPTD

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	PROBE	CPTD
1.518	-7.867	4.18993	152.90190	-.39525	-.18860	.21857	.10429	1.49108	3.37967	-.03805
1.518	-6.837	4.17833	149.57750	-.35913	-.16985	.22336	.10563	1.49901	3.40954	-.02890
1.518	-5.826	4.17210	145.50210	-.31182	-.14743	.22728	.10746	1.49538	3.41269	-.02844
1.517	-4.811	4.15333	140.43630	-.25948	-.12271	.22472	.10627	1.49838	3.40717	-.02883
1.518	-3.796	4.13113	133.98490	-.20390	-.09647	.22205	.10506	1.49841	3.40727	-.02922
1.518	-2.779	4.10509	125.71230	-.15131	-.07157	.22364	.10579	1.49933	3.41074	-.02890
1.518	-.765	4.06800	115.30170	-.09558	-.04520	.22073	.10439	1.49930	3.41061	-.02864
1.518	.757	4.02405	102.71360	-.04072	-.01926	.21490	.10163	1.49947	3.41127	-.02863
1.518	.249	3.97387	88.58101	.01224	.00579	.21125	.09995	1.49897	3.40938	-.02915
1.517	1.230	3.92206	74.72627	.06382	.03020	.20903	.09891	1.49891	3.40601	-.02939
1.518	2.215	3.88091	62.25726	.11770	.05566	.21062	.09961	1.49961	3.41181	-.02866
GRADIENT	-.04013	-11.45415	.05360	.02535	-.00245	-.00116	.00007	.00027	.00000	

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

( TCM040 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1419/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.543	-7.866	4.18854	152.90170	.40682	.19288	.22506	.10670	1.52688	3.51588	-.02579
1.543	-6.836	4.17758	149.57740	-.34053	-.16146	.21236	.10069	1.52721	3.51716	-.02581
1.543	-5.825	4.17102	145.50200	-.28400	-.13465	.20836	.09879	1.52677	3.51545	-.02584
1.543	-4.811	4.15192	140.43620	-.22991	-.10902	.20077	.09520	1.52660	3.51478	-.02602
1.543	-3.796	4.12977	133.98480	-.17839	-.08460	.19040	.09029	1.52700	3.51635	-.02604
1.543	-2.781	4.10328	125.71220	-.12996	-.06162	.18083	.08574	1.52620	3.51323	-.02615
1.543	-1.766	4.06669	115.30170	-.08417	-.03991	.17025	.08073	1.52599	3.51245	-.02623
1.554	-7.758	4.02351	102.71360	-.03849	-.01851	.16042	.07715	1.52660	3.51479	-.02598
1.554	-248	3.96853	88.58102	.00286	.00138	.15730	.07566	1.52624	3.51339	-.02619
1.554	1.230	3.92179	74.72627	.04379	.02106	.15857	.07626	1.52614	3.51303	-.02612
1.543	2.214	3.88142	62.25725	.08927	.04233	.1605	.07874	1.52627	3.51351	-.02621
GRADIENT	-.04003	-11.45540	.04490	.02131	-.00574	-.00261	-.00007	-.000027	-.000002	-.0000027

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM041 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1670/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.600	-8.125	-3.74672	-154.59490	-.35773	-.07252	-.16527	-.03250	.56519	1.24204	-.02674
.600	-7.121	-3.75017	-151.46730	-.31424	-.06331	-.16307	-.03285	.57270	1.24904	-.02085
.600	-6.140	-3.75474	-147.66710	-.27234	-.05472	-.16125	-.03240	.57865	1.25467	-.01671
.601	-5.164	-3.77042	-142.83790	-.22914	-.04592	-.15966	-.03200	.58413	1.25992	-.01283
.600	-4.188	-3.78469	-136.70190	-.18731	-.03737	-.15766	-.03145	.58823	1.26389	-.00932
.600	-3.220	-3.81444	-128.78560	-.14615	-.02911	-.15659	-.03119	.59127	1.26686	-.00713
.601	-2.253	-3.85192	-118.73280	-.10410	-.02074	-.15706	-.03130	.59417	1.26972	-.00551
.601	-1.284	-3.91315	-106.38630	-.06173	-.01226	-.15808	-.03140	.59560	1.27112	-.00393
.600	-291	-3.98120	-92.25951	-.01918	-.00380	-.15953	-.03164	.59650	1.27202	-.00300
.600	.704	-4.06259	-78.21233	.02308	.00457	-.16090	-.03184	.59607	1.27159	-.00272
.600	1.729	-4.12782	-65.39041	.06613	.01310	-.16264	-.03221	.59605	1.27158	-.00289
GRADIENT	-.06012	12.40045	.04295	.00855	-.00095	-.00014	-.00007	.00128	.00126	.00111

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

## PARAMETRIC DATA

	RUN NO.	1746/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-4.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA					CPTD
.800	-8.087	-3.82025	-154.31790	-.34048	-.10367	-.16105	-.04904					-.03630
.799	-7.081	-3.81802	-151.18970	-.29943	-.09036	-.15740	-.04750					-.02851
.800	-6.094	-3.82595	-147.31000	-.25840	-.07765	-.15673	-.04710					-.02268
.799	-5.110	-3.83456	-142.44030	-.21801	-.06511	-.15490	-.04626					-.01719
.800	-4.133	-3.84666	-126.26450	-.17742	-.05284	-.15215	-.04531					-.01294
.800	-3.154	-3.86766	-128.26810	-.13755	-.04080	-.15150	-.04494					-.00953
.800	-2.179	-3.89581	-118.13560	-.09721	-.02878	-.15106	-.04473					-.00701
.800	-1.201	-3.93358	-105.74880	-.05655	-.01671	-.15184	-.04487					-.00528
.800	-2.204	-3.99044	-91.58217	-.01567	-.00463	-.15239	-.04500					-.00433
.800	.789	-4.04626	-77.57468	.02525	.00744	-.15411	-.04543					-.00370
.799	1.806	-4.09543	-64.83240	.06626	.01953	-.15486	-.04564					-.00379
	GRADIENT	- .04333	12.36999	.04112	.01220	-.00053	-.00008					.00151
							.00141					

RUN NO. 1659/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1659/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA					CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA					CPM
.900	-8.098	-3.80426	-154.39700	-.32621	-.11344	-.15278	-.05313					-.03744
.900	-7.081	-3.80951	-151.18960	-.28574	-.09865	-.15406	-.05318					-.03003
.900	-6.098	-3.81414	-147.34960	-.24717	-.08479	-.15209	-.05218					-.02345
.900	-5.113	-3.82176	-142.47980	-.20867	-.07121	-.14934	-.05097					-.01834
.900	-4.135	-3.83296	-136.30400	-.16980	-.05771	-.14699	-.04996					-.01360
.900	-3.165	-3.85906	-128.34780	-.13175	-.04461	-.14570	-.04933					-.01006
.900	-2.186	-3.88371	-118.21510	-.09367	-.03164	-.14563	-.04920					-.00744
.900	-1.213	-3.92351	-105.82870	-.05462	-.01842	-.14590	-.04920					-.00565
.900	-2.216	-3.99200	-91.66200	-.01539	-.00518	-.14646	-.04932					-.00449
.900	.777	-4.05102	-77.65448	.02323	.00782	-.14800	-.04982					-.00419
.900	1.798	-4.10274	-64.87242	.06336	.02133	-.14949	-.05032					-.00405
	GRADIENT	- .04711	12.38172	.03933	.01332	-.00047	-.00008					.00252
							.00140					

RUN NO. 1738/ O RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1738/ O	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA					CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA					CPM
1.098	-7.989	-3.97317	-153.56660	-.29060	-.11977	-.14550	-.05997					-.04942
1.100	-7.016	-3.93378	-150.67430	-.25624	-.10500	-.13965	-.05722					-.03881
1.101	-6.023	-3.93197	-146.75380	-.22116	-.09006	-.13900	-.05661					-.03186
1.101	-5.030	-3.93330	-141.80380	-.18599	-.07529	-.13735	-.05560					-.02496
1.101	-4.040	-3.94070	-135.46850	-.14998	-.06044	-.13542	-.05457					-.01887
1.100	-3.049	-3.94300	-127.39180	-.11520	-.04624	-.13361	-.05363					-.01432
1.100	-2.064	-3.95883	-117.13990	-.08009	-.03205	-.13278	-.05313					-.01039
1.100	-1.072	-3.97297	-104.63360	-.04435	-.01772	-.13193	-.05220					-.00752
1.100	-.052	-4.00101	-90.46666	-.00794	-.00317	-.13179	-.05258					-.00585
1.100	.922	-4.02021	-76.73708	.02613	.01042	-.13176	-.05254					-.00462
1.100	1.931	-4.04323	-64.28089	.06208	.02475	-.13178	-.05255					-.00414
	GRADIENT	- .01810	12.28089	.03556	.01427	-.00056	.00031					.00164
							.00123					

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM041 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1722/ O	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	-4.000	PHI	=	180.000
<b>MACH</b>	<b>ALPHA</b>		<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBETA</b>	<b>MPROBE</b>	<b>CPTD</b>				
1.249	-8.032	-3.88739	-153.88320	-30031	-13368	-14660	-06526	-1.21624	2.45515	-0.04075				
1.250	-7.062	-3.84380	-151.07040	-26559	-11741	-14061	-06216	-1.22217	2.47272	-0.03355				
1.250	-6.074	-3.85499	-147.15120	-22976	-10085	-14015	-06151	-1.22887	2.49276	-0.02592				
1.250	-5.084	-3.85558	-142.28080	-19400	-08461	-13852	-06041	-1.23438	2.50931	-0.01935				
1.249	-4.101	-3.86797	-136.02550	-15654	-06797	-13684	-05942	-1.23679	2.51657	-0.01523				
1.250	-3.120	-3.88470	-127.98930	-12083	-05231	-13486	-05838	-1.24031	2.52724	-0.01192				
1.250	-2.142	-3.91537	-117.85700	-08530	-03683	-13441	-05803	-1.24222	2.53303	-0.00923				
1.250	-1.167	-3.93889	-105.50960	-04936	-02126	-13431	-05786	-1.24401	2.53847	-0.00705				
1.250	-1.160	-3.99347	-91.26358	-01313	-00565	-13480	-05802	-1.24491	2.54122	-0.00608				
1.250	.832	-4.04531	-77.29570	.02298	.00988	-13581	-05841	-1.24547	2.54294	-0.00543				
1.250	1.844	-4.08287	-64.59328	.05985	.02574	-13661	-05876	-1.24528	2.54233	-0.00550				
<b>GRADIENT</b>		-0.03770	12.35328	.03640	.01575	.00006	.00007	.00138	.00421	.00163				

RUN NO. 1711/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1711/ O	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA		CPALPH	CPBQ	CPBETA	MPROBE	CPTD
<b>MACH</b>	<b>ALPHA</b>		<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBETA</b>	<b>MPROBE</b>	<b>CPTD</b>					
1.400	-8.024	-3.89996	-153.84360	-32886	-15433	-15983	-07501	-1.36393	2.92484	-0.04288					
1.400	-7.050	-3.86053	-150.99130	-29175	-13584	-15485	-07210	-1.37017	2.94609	-0.03481					
1.400	-6.066	-3.86589	-147.11140	-25364	-11726	-15318	-07082	-1.37661	2.96816	-0.02746					
1.400	-5.073	-3.86907	-142.20140	-21328	-09800	-15185	-06977	-1.38170	2.98568	-0.02118					
1.400	-4.090	-3.87964	-135.94590	-17335	-07931	-14982	-06855	-1.38598	3.00046	-0.01676					
1.400	-3.110	-3.89896	-127.94960	-13370	-06090	-14945	-06807	-1.38926	3.01182	-0.01235					
1.400	-2.131	-3.91415	-117.81670	-09473	-04300	-14864	-06747	-1.39240	3.02270	-0.00884					
1.400	-1.150	-3.94934	-105.35050	-05525	-02502	-14834	-06718	-1.39392	3.02803	-0.00657					
1.400	-1.151	-3.99203	-91.18372	-01492	-00675	-14862	-06724	-1.39503	3.03189	-0.00551					
1.399	.842	-4.04140	-77.21585	.02455	.01110	-14943	-06757	-1.39497	3.03168	-0.00510					
1.400	1.857	-4.07575	-64.47380	.06583	.02976	-15087	-06820	-1.39574	3.03434	-0.00468					
<b>GRADIENT</b>		-0.03434	12.35921	.04018	.01830	.00011	.00008	.000156	.00542	.00195					

RUN NO. 1704/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1704/ O	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	CPALPH	CPBQ	CPBETA	MPROBE	CPTD	
<b>MACH</b>	<b>ALPHA</b>		<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBETA</b>	<b>MPROBE</b>	<b>CPTD</b>					
1.450	-8.114	-3.75819	-154.55510	-35258	-16794	-16292	-07760	-1.41161	3.09007	-0.04462					
1.450	-7.110	-3.75991	-151.42730	-30934	-14624	-15964	-07547	-1.41771	3.1166	-0.03691					
1.450	-6.125	-3.77207	-147.54810	-26931	-12644	-15887	-07459	-1.42446	3.13571	-0.02958					
1.450	-5.141	-3.77850	-142.71810	-22727	-10606	-15797	-07372	-1.42958	3.15402	-0.02345					
1.449	-4.168	-3.79557	-136.54270	-18559	-08623	-15567	-07233	-1.43232	3.16384	-0.01923					
1.450	-3.200	-3.82564	-128.58670	-14480	-06695	-15591	-07208	-1.43793	3.18402	-0.01396					
1.450	-2.227	-3.86056	-118.49420	-10457	-10457	-15633	-07196	-1.44153	3.19704	-0.00949					
1.450	-1.261	-3.91647	-106.18740	-06285	-02885	-15689	-07203	-1.44434	3.20721	-0.00681					
1.450	-.261	-3.98796	-91.98123	-01982	-00909	-15788	-07241	-1.44451	3.20780	-0.00591					
1.450	.731	-4.06436	-78.01329	.02174	.00996	-16044	-07353	-1.44500	3.20959	-0.00519					
1.450	1.752	-4.12326	-65.23111	.06594	.03022	-16135	-07396	-1.44543	3.21116	-0.00525					
<b>GRADIENT</b>		-0.05762	12.38962	.04250	.01966	-.00101	-.00030	-.000204	.00736	.00228					

RUN NO. 1704/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 516  
 ( TCM041 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1697/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-4.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD	
1.470	-8.064	-3.82181	-154.12080	-360888	-17174	-17175	-08173	1.43669	3.17955	-04408	
1.470	-7.098	-3.77770	-151.34790	-32013	-15129	-16557	-07825	1.44272	3.20133	.03690	
1.470	-6.113	-3.78765	-147.46850	-27950	-13106	-16551	-07761	1.44996	3.22764	.02869	
1.470	-5.125	-3.79616	-142.59880	-23483	-10949	-16292	-07596	1.45513	3.24649	.02281	
1.470	-4.151	-3.81075	-136.42330	-19137	-08886	-16034	-07445	1.45837	3.25835	.01878	
1.470	-3.181	-3.83897	-128.46730	-14869	-06880	-15903	-07359	1.46139	3.26940	.01529	
1.470	-2.211	-3.87395	-118.37480	-10601	-04893	-15882	-07330	1.46389	3.27861	.01259	
1.470	-1.236	-3.92221	-105.98830	-06450	-02970	-15900	-07323	1.46517	3.28330	.01063	
1.470	-0.243	-3.98671	-91.86143	-02101	-00966	-15988	-07353	1.46632	3.28756	.00923	
1.484	.752	-4.05835	-77.85388	.02150	.01008	-15917	-07461	1.46725	3.29098	.00869	
1.485	1.772	-4.11226	-65.07176	.06398	.02997	-16009	-07501	1.46778	3.29295	.00826	
GRADIENT	- .05280	12.38852	.04316	.02005	.00002	- .00014	- .00014	.00563	.00174	.00174	

RUN NO. 1667/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1667/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA		CPALPH	CPBQ	CPBETA	CPBE	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD		
1.497	-8.059	-3.83235	-154.08100	-36617	-17698	-17386	-08403	1.45471	3.24495	-.05191		
1.496	-7.089	-3.79355	-151.26880	-32674	-15692	-16799	-08068	1.45987	3.26382	.04538		
1.497	-6.107	-3.79745	-147.42860	-28762	-13724	-16793	-07973	1.46593	3.28631	.03858		
1.497	-5.117	-3.80832	-142.51930	-24504	-11168	-16686	-07912	1.47221	3.30932	.03190		
1.497	-4.146	-3.82503	-136.34390	-20149	-09516	-16622	-07850	1.47562	3.32197	.02787		
1.497	-3.169	-3.84930	-128.34790	-15780	-07427	-16639	-07831	1.47822	3.33161	.02446		
1.497	-2.198	-3.88171	-118.25530	-11324	-05314	-16680	-07828	1.48080	3.34121	.02149		
1.497	-1.226	-3.93134	-105.90690	-06900	-03299	-16826	-07874	1.48327	3.35043	.01867		
1.497	-0.228	-3.98851	-91.74188	-02372	-01108	-16963	-07928	1.48448	3.35495	.01734		
1.497	.765	-4.05058	-77.73441	.02200	.01028	-17142	-08007	1.48496	3.35674	.01683		
1.496	1.790	-4.11101	-64.95212	.06900	.03224	-17224	-08048	1.48414	3.35370	.01728		
GRADIENT	- .04951	12.37283	.04559	.02146	.00112	- .00038	- .00038	.00154	.00174	.00174		

RUN NO. 1685/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1685/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA		CPALPH	CPBQ	CPBETA	CPBE	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD		
1.519	8.051	-3.83210	-154.08090	-38715	-18727	-18500	-08949	1.48072	3.34092	-.04975		
1.520	-7.087	-3.79553	-151.26900	-35266	-16936	-17927	-08609	1.48764	3.36678	.04213		
1.520	-6.104	-3.79965	-147.42890	-31310	-14930	-18265	-08709	1.49465	3.39308	.03463		
1.520	-5.121	-3.81002	-142.55940	-27072	-12825	-18505	-08767	1.50034	3.41457	.02796		
1.520	-4.141	-3.82334	-136.34380	-22410	-10573	-18562	-08758	1.50397	3.42830	.02377		
1.520	-3.173	-3.84609	-128.42720	-17758	-08360	-18877	-08877	1.50586	3.43549	.02155		
1.520	-2.196	-3.87733	-118.25520	-12926	-06077	-19409	-09125	1.50706	3.44004	.02016		
1.520	-1.222	-3.92707	-105.86880	-07889	-03705	-19788	-09292	1.50789	3.44317	.01898		
1.520	-0.228	-3.98824	-91.74188	-02466	-01157	-20241	-09500	1.50832	3.44483	.01848		
1.520	.766	-4.05591	-77.73433	.02832	.01329	-19990	-09382	1.50850	3.44549	.01840		
1.520	1.787	-4.10618	-64.95227	.08026	.03768	-19744	-09270	1.50825	3.44457	.01863		
GRADIENT	- .04996	12.38791	.05175	.02437	.00238	- .00105	- .00105	.00074	.00074	.00074		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM041) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.541	-8.058	-3.83100	-154.08080	-43876	-20910	-20826	-09925	1.51950	3.48752	-03199
1.541	-7.089	-3.79225	-151.26860	-38456	-18278	-20367	-09681	1.52237	3.49853	-02918
1.545	-6.103	-3.80068	-147.38900	-31295	-14852	-19888	-09439	1.52823	3.52109	-02682
1.543	-5.123	-3.80720	-142.55910	-25351	-11997	-19351	-09158	1.52786	3.51964	-02437
1.544	-4.146	-3.82403	-136.34390	-19150	-09058	-19094	-09032	1.52999	3.52787	-02365
1.544	-3.166	-3.84382	-128.34760	-14398	-06813	-18678	-08839	1.52908	3.52435	-02410
1.543	-2.198	-3.88064	-118.25530	-09532	-04509	-18261	-08639	1.52911	3.52448	-02380
1.542	-1.222	-3.92669	-105.86880	-04940	-02335	-17462	-08255	1.52849	3.52207	-02328
1.543	-2.229	-3.99309	-91.74190	-00617	-00291	-16554	-07820	1.52942	3.52566	-02257
1.543	.766	-4.0557	-77.73433	-03451	-01631	-16474	-07784	1.52959	3.52631	-02260
1.543	1.788	-4.11080	-64.95212	-08422	-03978	-17833	-08424	1.53002	3.52797	-02239
GRADIENT	-0.05057	12.37730	.04606	.02178	.00356	.00171	.00005	.000020	.000029	.00140

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
5.99	-7.140	-3.75942	-151.46850	-31422	-06331	-16326	-03289	.57148	1.24790	-02159
5.99	-6.144	-3.75684	-147.66740	-27236	-05457	-16201	-03246	.57773	1.25380	-01656
6.00	-5.169	-3.77265	-142.83810	-22896	-04575	-16008	-03199	.58388	1.25968	-01228
6.00	-4.196	-3.79080	-136.70240	-18643	-03718	-15766	-03144	.58738	1.26307	-00976
6.00	-3.224	-3.81781	-128.78580	-14602	-02909	-15677	-03123	.59088	1.26648	-00738
6.01	-2.256	-3.85566	-118.73300	-10350	-02059	-15718	-03127	.59362	1.26917	-00544
6.00	-1.286	-3.91751	-106.38640	-06159	-01223	-15819	-03140	.59490	1.27043	-00416
6.00	-2.291	-3.99092	-92.25957	-01915	-00380	-15923	-03157	.59588	1.27141	-00328
6.00	.705	-4.06726	-78.21227	-02282	-00452	-16134	-03199	.59665	1.27216	-00286
GRADIENT	-0.05735	12.09674	.04285	.00854	.00078	.00011	.00012	.00182	.00179	.00140

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
5.99	-7.140	-3.75942	-151.46850	-31422	-06331	-16326	-03289	.57148	1.24790	-02159
5.99	-6.144	-3.75684	-147.66740	-27236	-05457	-16201	-03246	.57773	1.25380	-01656
6.00	-5.169	-3.77265	-142.83810	-22896	-04575	-16008	-03199	.58388	1.25968	-01228
6.00	-4.196	-3.79080	-136.70240	-18643	-03718	-15766	-03144	.58738	1.26307	-00976
6.00	-3.224	-3.81781	-128.78580	-14602	-02909	-15677	-03123	.59088	1.26648	-00738
6.01	-2.256	-3.85566	-118.73300	-10350	-02059	-15718	-03127	.59362	1.26917	-00544
6.00	-1.286	-3.91751	-106.38640	-06159	-01223	-15819	-03140	.59490	1.27043	-00416
6.00	-2.291	-3.99092	-92.25957	-01915	-00380	-15923	-03157	.59588	1.27141	-00328
6.00	.705	-4.06726	-78.21227	-02282	-00452	-16134	-03199	.59665	1.27216	-00286
GRADIENT	-0.05735	12.09674	.04285	.00854	.00078	.00011	.00012	.00182	.00179	.00140

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
5.99	-7.140	-3.75942	-151.46850	-31422	-06331	-16326	-03289	.57148	1.24790	-02159
5.99	-6.144	-3.75684	-147.66740	-27236	-05457	-16201	-03246	.57773	1.25380	-01656
6.00	-5.169	-3.77265	-142.83810	-22896	-04575	-16008	-03199	.58388	1.25968	-01228
6.00	-4.196	-3.79080	-136.70240	-18643	-03718	-15766	-03144	.58738	1.26307	-00976
6.00	-3.224	-3.81781	-128.78580	-14602	-02909	-15677	-03123	.59088	1.26648	-00738
6.01	-2.256	-3.85566	-118.73300	-10350	-02059	-15718	-03127	.59362	1.26917	-00544
6.00	-1.286	-3.91751	-106.38640	-06159	-01223	-15819	-03140	.59490	1.27043	-00416
6.00	-2.291	-3.99092	-92.25957	-01915	-00380	-15923	-03157	.59588	1.27141	-00328
6.00	.705	-4.06726	-78.21227	-02282	-00452	-16134	-03199	.59665	1.27216	-00286
GRADIENT	-0.05735	12.09674	.04285	.00854	.00078	.00011	.00012	.00182	.00179	.00140

## PARAMETRIC DATA

	RUN NO.	1458/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -4.000	PHI	= 180.000	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPM	CPTD
.800	-7.105	-3.83063	-151.19130	-.30036	-.09087	-.15778	-.04773	-.77026	1.48062	-.02945	
.800	-6.098	-3.82830	-147.31030	-.25868	-.07779	-.15694	-.04720	-.77627	1.48924	-.02345	
.800	-5.112	-3.83064	-142.47980	-.21821	-.06535	-.15435	-.04623	-.78162	1.49701	-.01857	
.800	-4.133	-3.84632	-136.26450	-.17760	-.05292	-.15241	-.04542	-.78526	1.50236	-.01434	
.800	-3.157	-3.87126	-128.26830	-.13753	-.04087	-.15111	-.04491	-.78879	1.50756	-.01114	
.800	-2.183	-3.89858	-118.17540	-.09766	-.02894	-.15154	-.04491	-.79102	1.51087	-.00869	
.800	-1.206	-3.94275	-105.78870	-.05682	-.01683	-.15190	-.04498	-.79308	1.51394	-.00715	
.800	-2.203	-3.99552	-91.58220	-.01538	-.00455	-.15247	-.04509	-.79398	1.51528	-.00605	
.800	.788	-4.05160	-77.61429	.02494	.00738	-.15284	-.04549	-.79423	1.51565	-.00592	
GRADIENT		-.04194	12.07569	.04123	.01227	-.0034	-.00003	.00181	.00269	.00171	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPM	CPTD
.900	-7.109	-3.81276	-151.27010	-.29403	-.10158	-.15095	-.05215	-.87140	1.64025	-.03084	
.899	-6.098	-3.81402	-147.34960	-.25467	-.08745	-.14980	-.05144	-.87634	1.64887	-.02501	
.900	-5.117	-3.82521	-142.48010	-.21603	-.07386	-.14778	-.05052	-.88227	1.65933	-.01953	
.900	-4.137	-3.83943	-136.26460	-.17700	-.06024	-.14573	-.04959	-.88614	1.66622	-.01509	
.900	-3.162	-3.86155	-128.30820	-.13887	-.04712	-.14466	-.04908	-.88954	1.67231	-.01171	
.901	-2.191	-3.89295	-118.21550	-.10051	-.03402	-.14459	-.04893	-.89237	1.67742	-.00885	
.900	-1.210	-3.93354	-105.78900	-.06132	-.02071	-.14512	-.04902	-.89353	1.67952	-.00726	
.900	-2.216	-3.99200	-91.66200	-.02185	-.00738	-.14562	-.04915	-.89468	1.68160	-.00623	
.900	.781	-4.05569	-77.61472	.01705	.00575	-.14728	-.04966	-.89446	1.68120	-.00595	
GRADIENT		-.04403	12.08592	.03954	.01344	-.00002	-.00002	.00169	.00304	.00185	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPM	CPTD
1.100	-7.044	-3.93653	-150.75480	-.25758	-.10557	-.14012	-.05743	1.07332	2.06526	-.03232	
1.100	-6.022	-3.93170	-146.75370	-.22207	-.09047	-.13834	-.05636	1.07897	2.07937	-.02583	
1.100	-5.034	-3.93611	-141.80400	-.18665	-.07563	-.13687	-.05546	1.08378	2.09147	-.02014	
1.100	-4.040	-3.94019	-135.46850	-.15085	-.06085	-.13515	-.05452	1.08689	2.09931	-.01581	
1.100	-3.053	-3.95063	-127.39230	-.11552	-.04644	-.13383	-.05380	1.09010	2.10746	-.01222	
1.100	-2.063	-3.95799	-117.13990	-.08055	-.03229	-.13313	-.05336	1.09234	2.11319	-.00929	
1.100	-1.075	-3.97870	-104.63370	-.04502	-.01801	-.13235	-.05295	1.09374	2.11678	-.00744	
1.100	-0.072	-4.00672	-90.46667	-.00894	-.00357	-.13202	-.05275	1.09422	2.11799	-.00648	
1.100	.919	-4.03264	-76.49878	.02548	.01018	-.13227	-.05285	1.09477	2.11940	-.00617	
GRADIENT		.01876	12.04213	.03562	.01434	-.00059	-.00034	.00153	.00390	.00194	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCMO42) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1515/ 0		RN/L = 2.49		GRADIENT INTERVAL = -5.00/ 5.00		BETA = -4.000		PHI = 180.000	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPD	CPTD
1.250	-7.088	-3.85260	-151.11150	-26695	-11797	-14123	-06241	1.22269	2.47428	-0.03308	
1.250	-6.074	-3.85544	-147.15120	-23061	-10130	-13959	-06132	1.22802	2.49019	-0.02685	
1.250	-5.081	-3.85951	-142.24130	-19482	-08504	-13835	-06039	1.23315	2.50561	-0.02039	
1.250	-4.102	-3.86815	-136.02550	-15773	-06856	-13652	-05933	1.23714	2.51765	-0.01588	
1.250	-3.123	-3.88899	-127.98950	-12131	-05256	-13477	-05840	1.23951	2.52480	-0.01282	
1.250	-2.146	-3.91176	-117.85690	-08605	-03719	-13451	-05813	1.24141	2.53059	-0.01025	
1.250	-1.160	-3.95393	-105.43050	-04967	-02143	-13448	-05803	1.24289	2.53507	-0.00868	
1.251	-1.168	-3.99362	-91.38260	-01343	-00579	-13483	-05812	1.24449	2.53995	-0.00736	
1.252	.828	-4.04582	-77.33537	.02296	.00990	-13609	-05866	1.24630	2.54546	-0.00684	
GRADIENT	-.03609	12.05368	.03662	.01589	.00006	.00012	.00180	.00548	.00183		
RUN NO.		1531/ 0		RN/L = 2.50		GRADIENT INTERVAL = -5.00/ 5.00		BETA = -4.000		PHI = 180.000	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPD	CPTD
1.400	-7.077	-3.86858	-151.03240	-29524	-13731	-15093	-07019	1.37118	2.94955	-0.03368	
1.400	-6.066	-3.86569	-147.11140	-25617	-11832	-14918	-06891	1.37724	2.97032	-0.02655	
1.400	-5.077	-3.87191	-142.20160	-21543	-09893	-14852	-06821	1.38248	2.98834	-0.02060	
1.400	-4.093	-3.88353	-135.94620	-17540	-08016	-14653	-06697	1.38670	3.00296	-0.01565	
1.400	-3.113	-3.90303	-127.94980	-13555	-06171	-14615	-06653	1.38981	3.01372	-0.01177	
1.400	-2.131	-3.92024	-117.77220	-09646	-04377	-14568	-06611	1.39225	3.02221	-0.00860	
1.400	-1.150	-3.95485	-105.35060	-05675	-02570	-14555	-06592	1.39455	3.03021	-0.00649	
1.400	-.152	-3.99712	-91.18373	-01584	-00717	-14599	-06605	1.39520	3.03248	-0.00556	
1.400	.841	-4.04139	-77.21585	.02398	.01085	-14744	-06668	1.39535	3.03300	-0.00518	
GRADIENT	-.03205	12.06209	.04042	.01844	.00012	.00009	.00179	.00620	.00211		
RUN NO.		1549/ 0		RN/L = 2.49		GRADIENT INTERVAL = -5.00/ 5.00		BETA = -4.000		PHI = 180.000	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPD	CPTD
1.450	-7.130	-3.77029	-151.42860	-31072	-14653	-15982	-07537	1.41982	3.11915	-0.03433	
1.450	-6.125	-3.77155	-147.54800	-27008	-12655	-15687	-07350	1.42575	3.14030	-0.02768	
1.451	-5.143	-3.78458	-142.67880	-22875	-10661	-15594	-07268	1.43129	3.16015	-0.02202	
1.450	-4.169	-3.79538	-136.54270	-18631	-08648	-15461	-07176	1.43412	3.17029	-0.01801	
1.449	-3.200	-3.82539	-128.58670	-14569	-06731	-15444	-07135	1.43772	3.18327	-0.01336	
1.450	-2.233	-3.86336	-118.49440	-10544	-04854	-15556	-07162	1.44093	3.19484	-0.00978	
1.450	-1.257	-3.92326	-106.10810	-06348	-02916	-15580	-07156	1.44377	3.20514	-0.00730	
1.451	-.263	-3.99305	-91.98125	-02032	-00932	-15711	-07209	1.44525	3.21050	-0.00610	
1.450	.730	-4.06424	-78.01331	.02122	.00973	-15988	-07331	1.44486	3.20907	-0.00567	
GRADIENT	-.05568	12.10782	.04246	.01967	.00101	.00029	.000230	.00832	.00250		

THE JOURNAL OF CLIMATE VOL. 15, NO. 10, OCTOBER 2002

PAGE 520

(TGM042) ( 04 OCT 91 )

## PARAMETRIC DATA

			CPTD	CPM	MPROBE	CPBETA	CPALPH	CPBQ	CPCPAQ	BETA	PHI	ALPHA	MACH
1.469	-7.127	-3.79118	-15.1	-34.960	-3.1839	-15.142	-16.387	-0.07794	1.43557	3.19551	-0.4452		
1.470	-6.117	-3.78916	-14.7	-46.870	-2.7975	-13.042	-16.125	-0.07625	1.44125	3.19673	-0.3844		
1.470	-5.134	-3.80142	-14.2	-59.930	-2.3413	-11.006	-16.046	-0.07543	1.44683	3.21623	-0.3231		
1.470	-4.160	-3.81687	-13.6	-42.370	-1.9194	-0.8973	-1.5878	-0.07422	1.45206	3.23527	-0.2657		
1.470	-3.186	-3.84154	-12.8	-46.740	-1.4830	-0.6917	-1.5697	-0.07321	1.45304	3.23886	-0.2431		
1.469	-2.213	-3.87861	-11.8	-33.530	-1.0602	-0.4935	-1.5696	-0.07306	1.45583	3.24901	-0.2026		
1.469	-1.239	-3.92653	-10.5	-98.840	-0.6353	-0.2952	-1.5678	-0.07284	1.45700	3.25333	-0.2024		
1.470	-2.244	-3.99720	-9.1	-86.148	-0.2105	-0.1005	-1.5800	-0.07331	1.45848	3.25873	-0.1879		
1.469	-2.755	-4.06278	-7.7	-8.1412	-0.2053	-0.0952	-1.6023	-0.07431	1.45779	3.25589	-0.1857		
GRADIENT		-0.05080	12.08517	-0.04319	-0.02017	-0.00030	-0.0002	-0.0002		.00485	.00133	.00170	

RUN NO.	1584/ O	RN/L =	2.50	GRADIENT INTERVAL	= -5.00/	5.00
LPHA	BETA	PHI	CPAQ	CPALPH	CPBO	CPBETA
-3.80090	-151.30970	-33189	-15837	-16985	-08105	1.45933
-3.80264	-147.42920	-29158	-13838	-16777	-07962	1.46476
-3.81481	-142.51990	-24749	-11686	-16776	-07921	1.46944
-3.82887	-136.34420	-20505	-09637	-16823	-07906	1.47330
-3.84648	-128.38750	-16124	-07554	-16830	-07885	1.47606
-3.88477	-118.25550	-11666	-05449	-16981	-07931	1.47955
-3.93617	-105.90870	-07232	-03372	-17142	-07992	1.48025
-3.99838	-91.74193	-02587	-01207	-17369	-08106	1.47934
-4.06061	-77.73427	.02024	.00945	-17567	-08199	1.47931
DIENT	.04847	12.08137	.04585	.02152	.00160	.00064
CPTD						.00437
CPM						.00118
MPROBE						.00139

RUN NO.	1600/ O	RN/L =	2.49	GRADIENT INTERVAL	=	-5.00/	5.00
BETA	PHI	CPOQ	CPALPH	CPBQ	CPBETA	M PROBE	CPTD
7. 115	-3.79917	-15.1	30950	-17687	-18715	1.48858	3.37030
6. 108	-3.80294	-147	38930	-15577	-19109	1.49524	3.39533
5. 125	-3.81337	-142	5.1980	-13291	-19163	1.50056	3.41539
4. 151	-3.82759	-136	3.4410	-10891	-18949	1.50367	3.42715
3. 176	-3.84968	-128	38760	-08558	-19063	1.50455	3.43052
2. 202	-3.88465	-118	25540	-06312	-19751	1.50513	3.43269
1. 223	-3.93208	-105	82920	-07997	-03745	-20093	-09410
-2.228	-4.70861	-91	70224	-02690	-01259	-20464	-05075
.769	-4.06018	-77	69456	.02690	.01259	-20417	-05954
DENT	-04818	12	08279	05268	02476	-00345	-00152
						.00072	.00092

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBEA	CPM	CPTD
1.517	-7.115	-3.79917	-151.30950	-37000	-17687	-18715	-08946	1.37030	-0.04118
1.517	-6.108	-3.80294	-147.38930	-32820	-15577	-19109	-09070	3.39533	-0.03362
1.517	-5.125	-3.81337	-142.51980	-28191	-13291	-16163	-09035	1.41539	-0.02684
1.517	-4.151	-3.82759	-136.34410	-23167	-10891	-18949	-08908	1.50367	-0.02381
1.517	-3.176	-3.84968	-128.38760	-18220	-08558	-19063	-08954	3.43052	-0.02298
1.517	-2.202	-3.88465	-118.25540	-13449	-06312	-19751	-09269	1.50513	-0.02211
1.516	-1.223	-3.93208	-105.82920	-07997	-03745	-20093	-09410	3.43269	-0.02055
1.517	-228	-3.99861	-91.70224	-02690	-01259	-20464	-09575	1.50743	-0.01961
1.516	-7.69	-4.06018	-77.69456	-020417	-01259	-20417	-09554	1.50676	-0.01979
GRADIENT	-	-0.04818	-12.82779	-0.02476	-0.02476	-0.02476	-0.00152	0.00072	-0.0092

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM042) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1615/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-4.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPM	CPTD		
1.541	-7.114	-3.80067	-151.30970	-37494	-17743	-20204	-09561	1.52573	3.51144	.02662		
1.541	-6.114	-3.80263	-147.42920	-31365	-14808	-19634	-09270	1.52790	3.51981	.02425		
1.540	-5.124	-3.81444	-142.51990	-25333	-11930	-19046	-08970	1.52967	3.52663	.02176		
1.541	-4.146	-3.82443	-136.34390	-19555	-09205	-18474	-08696	1.53088	3.53130	.02118		
1.541	-3.176	-3.85016	-128.38770	-14639	-06893	-18309	-08620	1.53062	3.53029	.02135		
1.541	-2.201	-3.88475	-118.25550	-9779	-04603	-17952	-08450	1.53098	3.53168	.02107		
1.541	-1.228	-3.93549	-105.90870	-5238	-02464	-17198	-08091	1.53167	3.53438	.02042		
1.541	-1.228	-3.99814	-91.74193	-0982	-00462	-16287	-07658	1.53189	3.53520	.02002		
1.541	.767	-4.06033	-77.73427	.03100	.01458	-16361	-07693	1.53175	3.53468	.01997		
GRADIENT		-0.04874	12.08674	.04617	.02173	.00506	.00240	.00026	.00100	.00031		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM043) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1569/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPM	CPTD		
.600	-7.115	-2.74184	-158.06760	-31141	-06265	-11884	-02391	.57429	1.25054	.01957		
.600	-6.613	-2.74257	-156.54740	-28958	-05818	-11783	-02367	.57727	1.25336	.01747		
.600	-6.121	-2.74755	-154.82950	-26826	-05372	-11701	-02343	.58104	1.25695	.01447		
.600	-5.631	-2.74712	-152.91320	-24673	-04931	-11506	-02299	.58326	1.25909	.01267		
.599	-5.136	-2.75227	-150.64040	-22566	-04501	-11494	-02293	.58536	1.26111	.01096		
.600	-4.649	-2.75707	-148.05090	-20462	-04077	-11408	-02273	.58782	1.26350	.00927		
.600	-4.162	-2.76838	-144.98630	-18382	-03656	-11371	-02262	.58934	1.26498	.00796		
.599	-3.679	-2.77611	-141.44650	-16352	-03247	-11447	-02273	.59091	1.26652	.00661		
.600	-3.193	-2.79057	-137.19410	-14330	-02843	-11449	-02272	.59286	1.26843	.00530		
.600	-2.714	-2.80661	-132.22950	-12263	-02431	-11421	-02264	.59369	1.26924	.00458		
.600	-2.236	-2.82833	-126.35490	-10184	-02021	-11393	-02262	.59529	1.27082	.00393		
.600	-1.754	-2.85440	-119.41200	-08020	-01592	-11429	-02268	.59638	1.27190	.00321		
.600	-1.276	-2.89442	-111.48080	-06015	-01190	-11478	-02271	.5973	1.27225	.00232		
.599	-0.790	-2.93604	-102.60030	-03852	-00762	-11605	-02295	.59637	1.27189	.00240		
.601	-0.308	-2.99139	-93.32489	-01861	-00369	-11656	-02312	.59806	1.27357	.00204		
.600	.204	-3.04056	-83.57410	-00216	.00043	-11831	-02342	.59763	1.27314	.00184		
.600	.715	-3.08445	-74.37741	.02310	.00457	-11996	-02375	.59762	1.27313	.00197		
GRADIENT		-0.06189	14.01434	.04272	.00850	-00095	-.00016	.00187	.00184	.00136		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 522

( TCMO43 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1459/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000	PARAMETRIC DATA			
							BETA	-3.000	PHI	180.000	CPM	CPTD		
MACH	ALPHA						CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD		
.800	-7.080	-2.81668	-157.75130	-.29662	-.08948	-.11608	-.03502	-.77257	1.48393	-.02690				
.800	-6.581	-2.81556	-156.23090	-.27623	-.08307	-.11558	-.03476	-.77608	1.48898	-.02354				
.800	-6.086	-2.81620	-154.51260	-.25578	-.07674	-.11488	-.03447	-.77916	1.49344	-.02074				
.800	-5.589	-2.81968	-152.51700	-.23572	-.07050	-.11375	-.03402	-.78185	1.49736	-.01786				
.800	-5.093	-2.82571	-150.20440	-.21536	-.06428	-.11244	-.03356	-.78418	1.50077	-.01568				
.800	-4.602	-2.82467	-147.61450	-.19469	-.05799	-.11114	-.03310	-.78645	1.50410	-.01347				
.800	-4.115	-2.83564	-144.51020	-.17502	-.05205	-.11109	-.03304	-.78832	1.50687	-.01170				
.800	-3.628	-2.84516	-140.89100	-.15517	-.04607	-.11086	-.03291	-.79012	1.50953	-.00995				
.800	-3.141	-2.84961	-136.67780	-.13511	-.04005	-.11085	-.03286	-.79143	1.51148	-.00856				
.800	-2.652	-2.86369	-131.59410	-.11525	-.03412	-.11067	-.03276	-.79256	1.51316	-.00733				
.800	-2.172	-2.88132	-125.67970	-.09497	-.02808	-.11073	-.03274	-.79357	1.51467	-.00630				
.800	-1.683	-2.89783	-118.69700	-.07466	-.02205	-.11095	-.03278	-.79452	1.51609	-.00531				
.800	-1.198	-2.92788	-110.68620	-.05455	-.01611	-.11086	-.03274	-.79512	1.51700	-.00482				
.800	-709	-2.95631	-101.80550	-.03449	-.01018	-.11131	-.03287	-.79588	1.51813	-.00434				
.800	-223	-2.99839	-92.49040	-.01537	-.00453	-.11184	-.03300	-.79596	1.51826	-.00395				
.800	.286	-3.02858	-82.77925	-.00493	-.00145	-.11313	-.03336	-.79627	1.51871	-.00359				
.800	.796	-3.07008	-73.62218	-.02523	-.00744	-.11374	-.03353	-.79599	1.51830	-.00364				
	GRADIENT	-.04476	13.97164	.04092	.01217	-.00041	-.00006	.00177	.00264	.00180				
RUN NO.	1492/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/ 5.00								
MACH	ALPHA						CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD		
.900	-7.086	-2.79991	-157.83020	-.29076	-.10018	-.11150	-.03842	-.87427	1.64525	-.02789				
.899	-6.578	-2.80133	-156.27101	-.27107	-.09305	-.1098	-.03810	-.87662	1.64937	-.02469				
.900	-6.086	-2.80784	-154.51250	-.25228	-.08640	-.10931	-.03744	-.87991	1.65516	-.02171				
.900	-5.594	-2.80900	-152.55650	-.23233	-.07939	-.10844	-.03706	-.88297	1.66057	-.01892				
.900	-5.099	-2.81115	-150.28360	-.21284	-.07250	-.10771	-.03669	-.88451	1.66332	-.01644				
.900	-4.605	-2.81367	-147.65410	-.19348	-.06581	-.10686	-.03635	-.88721	1.66812	-.01423				
.900	-4.123	-2.82414	-144.58950	-.17422	-.05911	-.10649	-.03613	-.88895	1.67124	-.01204				
.900	-3.634	-2.82858	-141.00980	-.15565	-.05271	-.10564	-.03578	-.89027	1.67363	-.01040				
.900	-3.146	-2.84110	-136.71760	-.13632	-.04611	-.10557	-.03571	-.89205	1.67684	-.00880				
.900	-2.659	-2.85287	-131.67340	-.11759	-.03912	-.10547	-.03563	-.89295	1.67845	-.00766				
.900	-2.174	-2.86828	-125.71930	-.09791	-.03303	-.10550	-.03559	-.89393	1.68024	-.00651				
.900	-1.693	-2.89232	-118.77660	-.07842	-.02644	-.10568	-.03563	-.89489	1.68198	-.00561				
.900	-1.209	-2.92324	-110.76580	-.05936	-.02000	-.10565	-.03559	-.89568	1.68342	-.00475				
.900	-721	-2.95281	-101.88510	-.03979	-.01339	-.10638	-.03580	-.89569	1.68343	-.00423				
.900	-237	-2.99087	-92.60963	-.02134	-.00718	-.10671	-.03590	-.89614	1.68425	-.00389				
.900	.275	-3.03374	-82.85886	-.00200	-.00067	-.10816	-.03639	-.89602	1.68403	-.00396				
.900	.785	-3.07232	-73.70181	-.01743	-.00586	-.10881	-.03661	-.89635	1.68463	-.00384				
	GRADIENT	-.04777	13.98880	.03930	.01334	-.00035	-.00005	.00166	.00301	.00190				

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM043) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1476/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -3.000	PHI	= 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD	CPME	CPTD
1.100	-7.037	-2.93595	-157.23720	-2.25534	-1.10431	-1.0413	-0.4254	1.07585	2.07157	-0.2903
1.100	-6.520	-2.93099	-155.63640	-2.23746	-1.09674	-1.0348	-0.4216	2.0784	2.0784	-0.2593
1.100	-6.029	-2.93237	-153.87840	-2.22008	-0.8940	-1.0259	-0.4167	1.08132	2.08526	-0.2285
1.100	-5.526	-2.93110	-151.84250	-2.20226	-0.8192	-1.0179	-0.4123	1.08396	2.09190	-0.1982
1.100	-5.034	-2.93687	-149.49030	-1.8444	-0.7452	-1.0112	-0.4086	1.08576	2.09645	-0.1737
1.102	-4.532	-2.93657	-146.78110	-1.6724	-0.6746	-0.9995	-0.4032	1.09002	2.10728	-0.1457
1.101	-4.038	-2.94057	-143.63660	-1.4955	-0.6021	-0.9970	-0.4014	1.09038	2.10820	-0.1311
1.100	-3.545	-2.94160	-139.97730	-1.3206	-0.5304	-0.9099	-0.3979	1.09104	2.10987	-0.1113
1.100	-3.037	-2.95479	-135.64570	-1.1427	-0.4581	-0.9854	-0.3950	1.09207	2.11248	-0.0956
1.100	-2.557	-2.94876	-130.75970	-0.9669	-0.3871	-0.9804	-0.3925	1.09333	2.11572	-0.0814
1.100	-2.062	-2.95143	-124.72580	-0.7859	-0.3142	-0.9763	-0.3904	1.09460	2.11896	-0.0675
1.100	-1.566	-2.95807	-117.66360	-0.6104	-0.2438	-0.9688	-0.3870	1.09500	2.11998	-0.0592
1.099	-1.079	-2.97279	-109.65260	-0.4339	-0.1732	-0.9621	-0.3839	1.09511	2.12027	-0.0518
1.100	-581	-2.98359	-100.69240	-0.2578	-0.1028	-0.9607	-0.3831	1.09606	2.12271	-0.0444
1.100	-0.94	-3.00331	-91.37717	-0.0884	-0.0352	-0.9609	-0.3831	1.09609	2.12279	-0.0418
1.100	.416	-3.01857	-81.70569	.00840	.00335	-0.9638	-0.3842	1.09642	2.12440	-0.0379
1.100	.920	-3.03462	-72.58844	.02581	.01029	-0.9646	-0.3846	1.09666	2.12426	-0.0394
GRADIENT	-0.1723	13.85592	.03555	.01430	.00076	.00039	.00135	.00345	.000201	
RUN NO.		1516/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -3.000	PHI	= 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD	CPME	CPTD
1.250	-7.066	-2.84477	-157.63250	-2.26422	-1.11646	-1.03110	-0.4544	1.22526	2.48195	-0.3030
1.251	-6.560	-2.84512	-156.07230	-2.24626	-1.10813	-1.0245	-0.4499	1.22919	2.49370	-0.2616
1.250	-6.061	-2.84618	-154.31410	-2.22821	-0.9987	-1.0294	-0.4505	1.23124	2.49986	-0.2293
1.250	-5.570	-2.85004	-152.31860	-2.21013	-0.9168	-1.0195	-0.4448	1.23378	2.50750	-0.1981
1.250	-5.073	-2.84816	-150.04530	-1.9228	-0.8365	-1.0060	-0.4377	1.23608	2.51445	-0.1691
1.250	-4.583	-2.85602	-147.37650	-1.7304	-0.7512	-1.0014	-0.4347	1.23767	2.51923	-0.1485
1.250	-4.095	-2.85981	-144.31150	-1.5518	-0.6727	-0.9899	-0.4291	1.23861	2.52208	-0.1349
1.250	-3.601	-2.87334	-140.65290	-1.3715	-0.5934	-0.9881	-0.4275	1.24047	2.52772	-0.1149
1.250	-3.110	-2.87354	-136.43950	-1.1967	-0.5170	-0.9812	-0.4239	1.24134	2.53035	-0.1001
1.250	-2.627	-2.87990	-131.39510	-1.0174	-0.4388	-0.9824	-0.4238	1.24289	2.53508	-0.0840
1.250	-2.138	-2.89083	-125.40120	-0.8389	-0.3614	-0.9757	-0.4203	1.24402	2.53852	-0.0708
1.250	-1.654	-2.91557	-118.37920	-0.6600	-0.2841	-0.9751	-0.4197	1.24429	2.53931	-0.0633
1.250	-1.167	-2.93454	-110.40790	-0.4820	-0.2073	-0.9757	-0.4196	1.24542	2.54277	-0.0541
1.250	-673	-2.96356	-101.40830	-0.3016	-0.1296	-0.9793	-0.4210	1.24560	2.54331	-0.0501
1.250	-189	-2.99351	-92.13277	-0.1286	-0.0553	-0.9841	-0.4229	1.24622	2.54520	-0.0453
1.250	.322	-3.02867	-82.38200	.00511	.00220	-0.9927	-0.4266	1.24619	2.54513	-0.0452
1.250	.832	-3.06012	-73.26462	.02303	.00989	-0.9977	-0.4287	1.24591	2.54427	-0.0451
GRADIENT	-0.3745	13.96559	.036333	.01574	.00005	.00011	.00163	.00494	.00198	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 524  
 (TCM043) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1532/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -3.000	PHI	= 180.000	CPTD
MACH	ALPHA	BETA	PHI	CPAO	CPALPH	CPBQ	CPBETA	MPROBE	CPM		
1.400	-7.064	-2.85860	-157.59320	-.29244	-.13563	-.10876	-.05044	1.37397	2.95910	-.03069	
1.400	-6.554	-2.85706	-156.03280	-.27313	-.12625	-.10794	-.04989	1.37676	2.96866	-.02725	
1.400	-6.059	-2.85972	-154.27480	-.25387	-.11693	-.10734	-.04944	1.37921	2.97707	-.02372	
1.400	-5.563	-2.86036	-152.27890	-.23329	-.10714	-.10663	-.04897	1.38232	2.98779	-.02069	
1.400	-5.068	-2.86480	-149.96630	-.21273	-.09745	-.10674	-.04889	1.38433	2.99474	-.01809	
1.400	-4.578	-2.87363	-147.29750	-.19300	-.08821	-.10598	-.04844	1.38624	3.00136	-.01583	
1.400	-4.085	-2.87457	-144.23230	-.17349	-.07905	-.10609	-.04834	1.38854	3.00931	-.01278	
1.399	-3.594	-2.87954	-140.61290	-.15399	-.07002	-.10547	-.04796	1.39013	3.01485	-.01071	
1.400	-3.103	-2.88628	-136.32040	-.13357	-.06066	-.10506	-.04771	1.39220	3.02200	-.00919	
1.400	-2.616	-2.89679	-131.23660	-.11393	-.05164	-.10450	-.04737	1.39335	3.02604	-.00748	
1.400	-2.126	-2.90600	-125.24260	-.09396	-.04255	-.10421	-.04720	1.39434	3.02947	-.00656	
1.399	-1.639	-2.92422	-118.22030	-.07418	-.03356	-.10406	-.04707	1.39427	3.02923	-.00557	
1.399	-1.150	-2.94092	-110.20930	-.05507	-.02489	-.10349	-.04678	1.39525	3.03264	-.00474	
1.400	-660	-2.96606	-101.28900	-.03465	-.01566	-.10383	-.04692	1.39614	3.03575	-.00436	
1.400	-174	-2.99439	-91.97385	-.01513	-.00684	-.10455	-.04724	1.39627	3.03619	-.00424	
1.400	.336	-3.02692	-82.26266	.00431	.00195	-.10594	-.04786	1.39632	3.03638	-.00396	
1.400	.843	-3.05119	-73.14540	.02400	.01084	-.10625	-.04798	1.39661	3.03741	-.00373	
	GRADIENT	- .03334	13.95554	.04023	.01833	.00010	.00014	.00180	.00624	.00207	
	RUN NO.	1550/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM		
1.449	-7.106	-2.75265	-158.02790	-.30802	-.14492	-.11446	-.05385	1.42170	3.12584	-.03197	
1.450	-6.598	-2.75530	-156.46790	-.27442	-.13481	-.11478	-.05383	1.42547	3.13932	-.02856	
1.450	-6.106	-2.75809	-154.74980	-.26769	-.12510	-.11298	-.05280	1.42797	3.14825	-.02499	
1.449	-5.614	-2.76052	-152.79400	-.24660	-.11487	-.11243	-.05237	1.43042	3.15700	-.02173	
1.450	-5.123	-2.76651	-150.52130	-.22445	-.10440	-.11281	-.05247	1.43261	3.16489	-.02007	
1.449	-4.630	-2.77012	-147.89190	-.20432	-.09482	-.11201	-.05198	1.43372	3.16885	-.01793	
1.450	-4.150	-2.77929	-144.86700	-.18458	-.08545	-.11163	-.05168	1.43664	3.17937	-.01531	
1.450	-3.665	-2.78958	-141.28770	-.16496	-.07612	-.11211	-.05173	1.43912	3.18831	-.01206	
1.450	-3.178	-2.80438	-136.99560	-.14442	-.06650	-.11168	-.05143	1.44129	3.19615	-.00987	
1.450	-2.698	-2.82219	-132.03120	-.12372	-.05691	-.11139	-.05124	1.44215	3.19927	-.00886	
1.450	-2.219	-2.83605	-126.15630	-.10258	-.04712	-.11122	-.05109	1.44409	3.20628	-.00727	
1.450	-1.734	-2.86421	-119.17390	-.08188	-.03759	-.11162	-.05124	1.44411	3.20638	-.00667	
1.450	-1.255	-2.89925	-111.24250	-.06180	-.02835	-.11146	-.05113	1.44477	3.20875	-.00597	
1.450	-772	-2.94049	-102.40170	-.04072	-.01868	-.11228	-.05105	1.44507	3.20985	-.00587	
1.450	-288	-2.99225	-93.08665	-.02053	-.00942	-.11344	-.05203	1.44472	3.20859	-.00599	
1.451	.225	-3.03838	-83.29622	.00065	.00030	-.11538	-.05288	1.44605	3.21341	-.00507	
1.450	.732	-3.08107	-74.17880	.02119	.00971	-.11675	-.05351	1.44537	3.21092	-.00511	
	GRADIENT	- .05850	14.01759	.04237	.01961	-.00072	-.00022	.00200	.00725	.00219	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 525  
( TCM043 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.		1634/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	CPTD			
1.469	-7.100	-2.77543	-157.90920	.31466	.14918	-.11900	-.05642	1.43853	3.18617	-.04186		
1.469	-6.593	-2.77302	-156.38860	.29375	.13888	-.11652	-.05509	1.44128	3.19614	-.03890		
1.470	-6.099	-2.78030	-154.63110	.27344	.12889	-.11643	-.05488	1.44433	3.20716	-.03560		
1.469	-5.607	-2.78189	-152.67520	.25308	.11887	-.11628	-.05462	1.44663	3.21552	-.03203		
1.469	-5.111	-2.78416	-150.40220	.23160	.10846	-.11595	-.05430	1.44968	3.22660	-.02874		
1.469	-4.624	-2.78613	-147.81250	.20947	.09786	-.11470	-.05359	1.45134	3.23264	-.02643		
1.470	-4.135	-2.79818	-144.70830	.18725	.08748	-.11411	-.05331	1.45263	3.23736	-.02552		
1.470	-3.649	-2.80705	-141.12890	.16622	.07754	-.11368	-.05304	1.45400	3.24234	-.02410		
1.469	-3.165	-2.81668	-136.91600	.14515	.06762	-.11288	-.05258	1.45448	3.24411	-.02277		
1.469	-2.682	-2.83449	-131.87220	.12429	.05781	-.11198	-.05203	1.45562	3.24827	-.02127		
1.469	-2.199	-2.85002	-125.95770	.10323	.04794	-.11223	-.05212	1.45733	3.25455	-.01973		
1.469	-1.719	-2.87706	-119.01500	.08317	.03858	-.11232	-.05210	1.45841	3.25847	-.01857		
1.469	-1.235	-2.91144	-111.00430	.06270	.02906	-.11257	-.05217	1.45888	3.26022	-.01779		
1.470	-7.749	-2.94395	-102.16330	.04132	.01914	-.11336	-.05252	1.45974	3.26337	-.01717		
1.471	-2.267	-2.99202	-92.88791	.02142	.00992	-.11441	-.05298	1.46126	3.26894	-.01662		
1.469	.244	-3.04034	-83.17671	.00000	.00000	-.11650	-.05393	1.46028	3.26536	-.01651		
1.469	.756	-3.07884	-73.98003	.02092	.00968	-.11788	-.05454	1.46065	3.26669	-.01631		
GRADIENT	- .05461	14.00175	.04281	.01999	.00048	-.00012	.000186	.00681	.00204	.00141	.00167	
RUN NO.		1585/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	CPTD			
1.491	-7.089	-2.78685	-157.86960	.32993	.15748	-.12254	-.05849	1.45916	3.26123	-.04650		
1.491	-6.585	-2.79002	-156.30970	.31027	.14785	-.12155	-.05792	1.46070	3.26689	-.04475		
1.492	-6.093	-2.79223	-154.59160	.28797	.13693	-.12106	-.05756	1.46291	3.27498	-.04246		
1.491	-5.601	-2.79269	-152.63560	.26784	.12710	-.11996	-.05693	1.46446	3.28069	-.04029		
1.491	-5.108	-2.80062	-150.32320	.24694	.11687	-.12085	-.05720	1.46681	3.28934	-.03751		
1.491	-4.614	-2.80270	-147.69370	.22458	.10618	-.12049	-.05697	1.46763	3.29237	-.03651		
1.492	-4.132	-2.81313	-144.62920	.20436	.09644	-.12165	-.05741	1.47000	3.30112	-.03439		
1.491	-3.646	-2.82025	-141.04960	.18236	.08591	-.12186	-.05741	1.47093	3.30459	-.03281		
1.491	-3.156	-2.82741	-136.79680	.15998	.07527	-.12190	-.05735	1.47111	3.30745	-.03153		
1.491	-2.672	-2.84438	-131.79270	.13829	.06492	-.12209	-.05732	1.47361	3.31451	-.02927		
1.491	-2.191	-2.86277	-125.87840	.11577	.05429	-.12292	-.05765	1.47473	3.31866	-.02822		
1.491	-1.708	-2.88424	-118.93540	.09367	.04392	-.12394	-.05811	1.47526	3.32061	-.02766		
1.492	-1.224	-2.91648	-110.92470	.07168	.03359	-.12549	-.05880	1.47602	3.32343	-.02701		
1.491	-7.736	-2.95344	-102.04410	.04861	.02278	-.12729	-.05965	1.47585	3.32281	-.02709		
1.491	-2.252	-2.99393	-92.76862	.02590	.01214	-.12903	-.06048	1.47557	3.32178	-.02743		
1.491	.260	-3.03420	-83.01779	.00195	.00091	-.13140	-.06158	1.47526	3.32064	-.02733		
GRADIENT	.772	-3.07518	-73.82111	.02131	.00999	-.13246	-.06207	1.47566	3.32209	-.02715	.00141	.00094
	-.05078	13.98476	.04590	.02166	-.00221	-.00012	.000186	.00681	.00204	.00141	.00167	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 526  
 (TCM043) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1601/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.516	-7.094	-2.78722	-157.86960	-37248	-17722	-13770	-06552	1.49203	3.38325	-.03690
1.516	-6.586	-2.78832	-156.30950	-35073	-16618	-13892	-06582	1.49584	3.39756	-.03260
1.516	-6.094	-2.79002	-154.59140	-32829	-15517	-13760	-06504	1.49755	3.40403	-.03016
1.516	-5.600	-2.79530	-152.59590	-30391	-14328	-13860	-06534	1.50052	3.41525	-.02736
1.517	-5.109	-2.79955	-150.32310	-27843	-13092	-13712	-06447	1.50361	3.42694	-.02447
1.517	-4.619	-2.80449	-147.69380	-25287	-11879	-13642	-06408	1.50380	3.42767	-.02355
1.517	-4.132	-2.81175	-144.62910	-22877	-10742	-13717	-06441	1.50425	3.42936	-.02329
1.517	-3.646	-2.81967	-141.04950	-20761	-09741	-13945	-06543	1.50479	3.43140	-.02250
1.516	-3.155	-2.82732	-136.79680	-18368	-08611	-14052	-06588	1.50500	3.43221	-.02176
1.516	-2.672	-2.84319	-131.75290	-15771	-07383	-14329	-06708	1.50648	3.43784	-.02038
1.517	-2.189	-2.85785	-125.83850	-13061	-06109	-14418	-06743	1.50784	3.44301	-.01926
1.517	-1.706	-2.88480	-118.85610	-10326	-04826	-14618	-06832	1.50839	3.44510	-.01859
1.516	-1.222	-2.91726	-110.84540	-07676	-03585	-14644	-06839	1.50862	3.44597	-.01780
1.517	-0.736	-2.95329	-102.00450	-04973	-02320	-14713	-06863	1.51009	3.45154	-.01661
1.516	-0.252	-2.98854	-92.72896	-02387	-01113	-14949	-06971	1.50965	3.44989	-.01650
1.517	.260	-3.03961	-82.97815	.00355	.00166	-15007	-06998	1.51068	3.45379	-.01630
1.517	.772	-3.07508	-73.78148	.02971	.01385	-15069	-07028	1.51036	3.45260	-.01654
	GRADIENT	- .05087	13.98553	.05322	.02499	.00278	.00119	.00141	.00535	.00155
	RUN NO.	1616/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.541	-7.093	-2.78866	-157.86980	-36686	-17348	-14812	-07005	1.52651	3.51446	-.02579
1.541	-6.587	-2.78548	-156.34920	-30532	-15852	-14310	-06757	1.52783	3.51955	-.02427
1.541	-6.093	-2.79191	-154.59160	-30532	-14389	-14057	-06625	1.52977	3.52703	-.02233
1.541	-5.601	-2.79236	-152.63550	-27568	-12982	-13668	-06436	1.53104	3.53194	-.02145
1.541	-5.110	-2.79693	-150.36280	-24671	-11612	-13490	-06350	1.53112	3.53223	-.02105
1.542	-4.618	-2.80516	-147.69390	-21743	-10238	-13251	-06240	1.53123	3.53265	-.02140
1.541	-4.127	-2.80956	-144.62890	-19008	-08950	-13116	-06176	1.53042	3.52951	-.02151
1.541	-3.644	-2.82130	-141.04970	-16352	-07070	-12973	-06109	1.53048	3.52975	-.02102
1.541	-3.155	-2.82678	-136.83650	-13793	-06492	-12660	-05959	1.53088	3.53131	-.02030
1.541	-2.672	-2.84240	-131.79260	-11222	-05278	-12267	-05770	1.53144	3.53348	-.01920
1.541	-2.187	-2.85860	-125.83850	-08667	-04072	-11481	-05394	1.53263	3.53809	-.01923
1.541	-1.707	-2.88415	-118.89570	-06585	-03094	-10932	-05136	1.53210	3.53602	-.01846
1.541	-1.220	-2.91203	-110.88490	-04724	-02218	-10544	-04950	1.53312	3.53998	-.01854
1.541	-0.734	-2.95325	-102.00450	-02868	-01347	-10355	-04862	1.53307	3.53979	-.01854
1.541	-0.250	-2.98852	-92.72896	-01166	-00548	-10378	-04873	1.53329	3.54063	-.01854
1.541	.259	-3.03406	-83.01779	.00595	.00279	-10369	-04869	1.53287	3.53899	-.01863
1.541	.770	-3.07535	-73.86075	.02428	.01140	-10411	-04886	1.53350	3.54145	-.01811
	GRADIENT	- .05048	13.98419	.04479	.02109	.00654	.00311	.00059	.00228	.00072

## PARAMETRIC DATA

MACH	RUN NO.	1570/ 0		RN/L = 2.50		GRADIENT INTERVAL = -5.00/ 5.00		BETA = -2.500		PHI = 180.000	
		BETA	PHI	CPOAQ	CPALPH	CPBHQ	CPBETA	MPROBE	CPM	MPROBE	CPTD
.599	-7.098	-2.23601	-161.60680	-.30811	-.06189	-.09684	-.01945	.574577	1.25080	-.01905	
.599	-6.592	-2.23547	-160.28670	-.28733	-.05752	-.09707	-.01943	.57839	1.25442	-.01597	
.599	-6.103	-2.23740	-158.80850	-.26579	-.05319	-.09543	-.01910	.58112	1.25703	-.01430	
.599	-5.605	-2.23744	-157.09200	-.24484	-.04884	-.09396	-.01874	.58381	1.25962	-.01189	
.599	-5.117	-2.24131	-155.09850	-.22265	-.04439	-.09320	-.01858	.58616	1.26189	-.01040	
.599	-4.631	-2.24778	-152.74850	-.20224	-.04022	-.09236	-.01837	.58870	1.26435	-.00832	
.600	-4.147	-2.25585	-149.96270	-.18179	-.03617	-.09181	-.01827	.59019	1.26581	-.00752	
.600	-3.656	-2.26144	-146.62200	-.16168	-.03212	-.09024	-.01828	.59188	1.26746	-.00615	
.599	-3.174	-2.27350	-142.56880	-.14087	-.02792	-.09243	-.01832	.59303	1.26860	-.00492	
.600	-2.697	-2.28720	-137.68430	-.12039	-.02387	-.09208	-.01826	.59450	1.27004	-.00413	
.600	-2.219	-2.30720	-131.65200	-.09994	-.01978	-.09212	-.01823	.59568	1.27120	-.00299	
.600	-1.743	-2.33484	-124.27460	-.07856	-.01558	-.09251	-.01834	.59667	1.27219	-.00282	
.600	-1.267	-2.37379	-115.39420	-.05879	-.01164	-.09263	-.01833	.59718	1.27270	-.00209	
.599	-7.789	-2.42242	-105.12970	-.03859	-.00762	-.09387	-.01855	.59766	1.27318	-.00140	
.600	-.311	-2.48518	-94.07506	-.01899	-.00376	-.09528	-.01886	.59791	1.27342	-.00171	
.600	-.200	-2.54326	-82.38698	-.00174	-.00034	-.09754	-.01929	.59778	1.27329	-.00153	
.600	.717	-2.60471	-71.56949	.02288	.00452	-.0937	-.01964	.59762	1.27313	-.00157	
.600	.06610	-15.44498	.04233	.00841	-.00117	-.00021	.00174	.00172	.00132		
MACH	RUN NO.	1460/ 0		RN/L = 2.50		GRADIENT INTERVAL = -5.00/ 5.00		BETA = -2.500		PHI = 180.000	
		ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBHQ	CPBETA	MPROBE	CPM	CPTD
.800	-7.069	-2.31212	-161.29090	-.29475	-.08886	-.09538	-.02876	.77409	1.48610	-.02577	
.800	-6.563	-2.31393	-159.93110	-.27414	-.08238	-.09561	-.02873	.77747	1.49099	-.02244	
.800	-6.066	-2.30982	-158.45220	-.25421	-.07611	-.09492	-.02842	.77986	1.49446	-.01951	
.800	-5.573	-2.31307	-156.69630	-.23367	-.06985	-.09353	-.02796	.78290	1.49889	-.01701	
.800	-5.085	-2.31776	-154.66300	-.21339	-.06361	-.09246	-.02756	.78519	1.50224	-.01454	
.800	-4.594	-2.32230	-152.27300	-.19288	-.05742	-.09144	-.02722	.78747	1.50560	-.01262	
.800	-4.100	-2.32488	-149.44110	-.17328	-.05146	-.09011	-.02676	.78927	1.50827	-.01060	
.800	-3.613	-2.33144	-146.06680	-.15360	-.04554	-.08998	-.02668	.79092	1.51072	-.00891	
.800	-3.126	-2.33632	-142.01330	-.13334	-.03949	-.09018	-.02671	.79228	1.51274	-.00767	
.800	-2.638	-2.34961	-136.97010	-.11355	-.03359	-.09012	-.02666	.79370	1.51487	-.00632	
.800	-2.158	-2.36425	-130.89810	-.09348	-.02762	-.08964	-.02649	.79455	1.51614	-.00539	
.800	-1.675	-2.38293	-123.44120	-.07342	-.02168	-.08997	-.02656	.79541	1.51742	-.00454	
.800	-1.194	-2.40941	-114.52090	-.05378	-.01587	-.08978	-.02649	.79605	1.51838	-.00387	
.800	-.709	-2.44430	-104.17720	-.03415	-.01007	-.09060	-.02671	.79651	1.51908	-.00333	
.800	-.229	-2.49143	-93.12241	-.01522	-.00448	-.09136	-.02694	.79690	1.51966	-.00324	
.800	.283	-2.53796	-81.43430	.00467	.00138	-.09304	-.02742	.79693	1.51971	-.00298	
.800	.797	-2.57959	-70.65654	.02462	.00725	-.09395	-.02769	.79701	1.51982	-.00286	
.800	.40748	-15.40208	.04061	.01206	-.00047	-.00009	.00175	.00176	.00262		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM044 ) ( 04 OCT 91 )  
PAGE 528

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	BETA = -5.00 /	GRADIENT INTERVAL = -5.00 /	BETA = -2.500 /	GRADIENT INTERVAL = -5.00 /	PHI = 180.000
											RN/L = 1493 / 0	RN/L = 2.50	RN/L = 2.50	RN/L = 2.50	RN/L = 2.50
.900	-7.073	-2.29509	-161.36970	-28924	.09958	.09082	-.03127	.87545	1.64732	-.02680					
.900	-6.565	-2.29714	-160.00980	-26935	-.09240	-.09121	-.03129	.87809	1.65195	-.02356					
.899	-6.070	-2.29904	-158.49170	-25031	-.08557	-.09117	-.03083	.88032	1.65588	-.02055					
.900	-5.578	-2.29815	-156.77530	-23089	-.07877	.08887	-.03032	.88353	1.66156	-.01777					
.900	-5.088	-2.30294	-154.74210	-21141	-.07195	.08742	-.02975	.88601	1.66599	-.01521					
.900	-4.596	-2.30768	-152.35210	-19212	-.06523	.08660	-.02940	.88763	1.66889	-.01311					
.900	-4.106	-2.31248	-149.52630	-17312	-.05864	.08633	-.02925	.88944	1.67213	-.01098					
.900	-3.618	-2.31961	-146.14610	-15406	-.05214	.08600	-.02910	.89157	1.67596	-.00931					
.900	-3.129	-2.32698	-142.05300	-13481	-.04554	.08589	-.02902	.89281	1.67820	-.00777					
.900	-2.645	-2.33603	-137.08900	-11550	-.03898	.08572	-.02893	.89400	1.68036	-.00653					
.900	-2.163	-2.35237	-130.97740	-09635	-.03247	.08555	-.02883	.89463	1.68151	-.00554					
.900	-1.685	-2.37457	-123.56030	-07714	-.02599	.08563	-.02885	.89592	1.68386	-.00476					
.900	-1.202	-2.40267	-114.60040	-05833	-.01963	.08577	-.02886	.89627	1.68449	-.00384					
.900	-722	-2.44368	-104.29630	-03930	-.01322	.08656	-.02912	.89673	1.68532	-.00345					
.900	-241	-2.48774	-93.24155	-02141	-.00720	.08725	-.02934	.89709	1.68598	-.00312					
.900	-270	-2.53692	-81.55345	-00203	-.00068	.08886	-.02987	.89697	1.68576	-.00293					
.900	787	-2.58560	-70.73602	.01722	.00579	.08979	-.03018	.89710	1.68600	-.00284					
	GRADIENT	-.05083	15.42179	.03910	.01325	-.00051	-.00012	.00310	.00033	.00157					
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	RN/L = 1477 / 0	RN/L = 2.50	RN/L = 2.50	RN/L = 2.50	RN/L = 2.50
1.100	-7.032	-2.42965	-160.77670	-25394	-.10365	-.08606	-.03513	1.07650	2.07317	-.02817					
1.100	-6.521	-2.42875	-159.37670	-23632	-.09617	-.08527	-.03470	1.07952	2.08073	-.02487					
1.100	-6.020	-2.43233	-157.77900	-21831	-.08858	-.08548	-.03468	1.08226	2.08763	-.02170					
1.100	-5.523	-2.42711	-156.02240	-20111	-.08137	-.08396	-.03397	1.08476	2.09394	-.01873					
1.100	-5.026	-2.43393	-153.86990	-18327	-.07397	-.08310	-.03354	1.08681	2.09911	-.01621					
1.100	-4.534	-2.43507	-151.44000	-16594	-.06679	-.08202	-.03301	1.08841	2.10319	-.01377					
1.100	-4.035	-2.43631	-148.53460	-14823	-.05955	-.08170	-.03282	1.09045	2.10838	-.01165					
1.100	-3.535	-2.43454	-145.07460	-13103	-.05255	-.08078	-.03240	1.09188	2.11200	-.00993					
1.100	-3.035	-2.45291	-140.86310	-11269	-.04511	-.08105	-.03245	1.09310	2.11514	-.00819					
1.100	-2.549	-2.44117	-136.01750	-09516	-.03805	-.08026	-.03209	1.09412	2.11774	-.00693					
1.100	-2.058	-2.44333	-129.82610	-07754	-.03097	-.07940	-.03171	1.09483	2.11957	-.00591					
1.100	-1.566	-2.45250	-122.25020	-05974	-.02385	-.07911	-.03158	1.09613	2.12288	-.00493					
1.100	-1.077	-2.46569	-113.25060	-04251	-.01695	-.07852	-.03131	1.09630	2.12332	-.00430					
1.100	-583	-2.47822	-102.82740	-02537	-.01011	-.07836	-.03123	1.09679	2.12458	-.00359					
1.100	-0.99	-2.49909	-91.73286	-00869	-.00346	-.07844	-.03125	1.09697	2.12507	-.00334					
1.100	.414	-2.52064	-80.08441	-00856	-.00341	-.07887	-.03142	1.09737	2.12607	-.00308					
1.100	.921	-2.53977	-69.42570	-02570	-.01023	-.07900	-.03146	1.09725	2.12576	-.00302					
	GRADIENT	-.01822	15.27537	.03531	.01418	.00066	.00033	.00157	.00401	.00193					

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM044) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1517/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.500	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.250	-7.059	-2.34079	-161.17220	-26308	-11576	.08477	.03730	1.22603	2.48423	.02875
1.250	-6.549	-2.33972	-159.81200	-24485	-10736	.08455	.03708	1.22924	2.49386	.02508
1.250	-6.056	-2.34462	-158.25430	-22685	.09914	.08423	.03681	1.23205	2.50229	.02164
1.250	-5.559	-2.34474	-156.49810	-20872	.09092	.08389	.03654	1.23456	2.50985	.01836
1.250	-5.062	-2.34356	-154.46440	-19018	.08263	.08216	.03570	1.23689	2.51688	.01567
1.250	-4.571	-2.35021	-152.03490	-17181	.07454	.08105	.03517	1.23808	2.52047	.01429
1.250	-4.078	-2.35180	-149.20890	-15397	.06667	.08082	.03500	1.23949	2.52474	.01234
1.250	-3.587	-2.35558	-145.82850	-13615	.05884	.08015	.03464	1.24144	2.53065	.01033
1.250	-3.101	-2.36287	-141.77520	-11812	.05097	.07989	.03447	1.24237	2.53347	.00882
1.250	-2.615	-2.37354	-136.73190	-10038	.04324	.07938	.03420	1.24386	2.53801	.00717
1.250	-2.128	-2.38604	-130.58060	-08250	.03551	.07900	.03400	1.24499	2.54145	.00601
1.250	-1.645	-2.40148	-123.08400	-06467	.02781	.07916	.03404	1.24559	2.54328	.00528
1.250	-1.159	-2.42297	-114.12400	-04699	.02019	.07920	.03403	1.24604	2.54466	.00459
1.250	-679	-2.45910	-103.78030	-02974	.01277	.07985	.03428	1.24665	2.54653	.00370
1.250	-193	-2.48974	-92.68584	-01246	.00535	.08067	.03463	1.24646	2.54593	.00376
1.250	.318	-2.52938	-80.99777	.00515	.00221	.08192	.03516	1.24706	2.54779	.00346
1.249	.832	-2.56958	-70.22000	.02292	.00983	.08243	.03537	1.24655	2.54622	.00326
	GRADIENT	-.04010	15.40611	.03621	.01568	-.00020	-.00002	.00161	.00489	.00201
	RUN NO.	1533/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.400	-7.053	-2.35372	-161.13280	-29132	.13499	-.08821	-.04088	1.37431	2.96027	.02986
1.400	-6.544	-2.35208	-159.77260	-27175	.12545	-.08739	-.04034	1.37779	2.97720	.02598
1.400	-6.050	-2.35657	-158.21480	-25166	.11584	-.08676	-.03994	1.38017	2.98039	.02306
1.400	-5.553	-2.35555	-156.45850	-23136	.10614	-.08657	-.03972	1.38264	2.98893	.01968
1.400	-5.060	-2.35989	-154.38540	-21115	.09664	-.08625	-.03947	1.38471	2.99604	.01727
1.400	-4.564	-2.36251	-151.99530	-19204	.08765	-.08569	-.03911	1.38755	3.00588	.01440
1.400	-4.076	-2.36668	-149.16960	-17276	.07866	-.08608	-.03874	1.38961	3.01304	.01198
1.400	-3.582	-2.37393	-145.70990	-15277	.06943	-.08457	-.03843	1.39117	3.01846	.01006
1.400	-3.092	-2.37288	-141.65610	-13231	.06004	-.08439	-.03829	1.39255	3.02325	.00851
1.400	-2.605	-2.38286	-136.61280	-11264	.05102	-.08381	-.03796	1.39385	3.02777	.00674
1.400	-2.118	-2.39452	-130.42170	-09257	.04188	-.08337	-.03772	1.39482	3.03116	.00563
1.400	-1.634	-2.40964	-122.92520	-07210	.03261	-.08353	-.03778	1.39536	3.03302	.00528
1.400	-1.148	-2.42779	-113.96520	-05341	.02414	-.08348	-.03774	1.39624	3.03608	.00461
1.400	-.662	-2.46408	-103.54230	-03395	.01534	-.08383	-.03788	1.39570	3.03420	.00442
1.400	-.177	-2.49093	-92.44778	-01516	.00685	-.08497	-.03838	1.39640	3.03668	.00390
1.400	.333	-2.53255	-80.79930	.00450	.00203	-.08641	-.03903	1.39637	3.03657	.00387
1.400	.845	-2.56564	-70.06120	.02410	.01088	-.08699	-.03928	1.39712	3.03918	.00344
	GRADIENT	-.03684	15.40211	.04018	.01829	-.00018	-.00001	.00161	.00562	.00188

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

## PARAMETRIC DATA

	RUN NO.	1551/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -2.500	PHI	= 180.000	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPME	MPROBE	CPTD	
1.450	-7.083	-2.24473	-161.56680	-30626	-14389	-09269	-0.4355	1.42363	3.13273	-0.03040	
1.450	-6.580	-2.24938	-160.20740	-28599	-13399	-09263	-0.4340	1.42609	3.14152	-0.02753	
1.451	-6.087	-2.24766	-158.72880	-26556	-12402	-09170	-0.4282	1.42950	3.15372	-0.02406	
1.450	-5.596	-2.25359	-156.97310	-24365	-11344	-09212	-0.4289	1.43101	3.15913	-0.02120	
1.450	-5.106	-2.25938	-154.93990	-22297	-10366	-09031	-0.4199	1.43312	3.16671	-0.01951	
1.450	-4.616	-2.26215	-152.58960	-20293	-09407	-09021	-0.4182	1.43538	3.17484	-0.01663	
1.450	-4.127	-2.26623	-149.80360	-18412	-08508	-09012	-0.4164	1.43824	3.18514	-0.01339	
1.450	-3.640	-2.27518	-146.46320	-16337	-07533	-08972	-0.4137	1.44019	3.19219	-0.01121	
1.449	-3.158	-2.28446	-142.40990	-14253	-06557	-09033	-0.4156	1.44139	3.19653	-0.00906	
1.449	-2.676	-2.29683	-137.48580	-12155	-05585	-08917	-0.4157	1.44225	3.19961	-0.00790	
1.450	-2.202	-2.31169	-131.45360	-10047	-04614	-08884	-0.4080	1.44394	3.20574	-0.00711	
1.450	-1.726	-2.34594	-124.03660	-07998	-03672	-08910	-0.4091	1.44380	3.20524	-0.00688	
1.450	-1.249	-2.38484	-115.11650	-06004	-02755	-09005	-0.4132	1.44464	3.20829	-0.00627	
1.450	-0.769	-2.42811	-104.81240	-03998	-01834	-09123	-0.4184	1.44493	3.20935	-0.00585	
1.450	-0.291	-2.48658	-93.79736	-02020	-00926	-09263	-0.4249	1.44473	3.20860	-0.00597	
1.450	.220	-2.54617	-82.10925	.00073	.00034	.09464	.04338	.1.44489	3.20921	.00541	
1.450	.736	-2.60049	-71.29178	.02143	.00982	.09613	.04406	.1.44554	3.21154	.00518	
	GRADIENT	-0.06331	15.46705	.04236	.01958	.00097	.00037	.00165	.00596	.00185	
	RUN NO.	1635/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPME	MPROBE	CPTD	
1.470	-7.080	-2.26295	-161.48770	-31230	-14799	-05556	-0.4528	1.43998	3.19143	-0.04076	
1.469	-6.577	-2.26712	-160.61030	-29214	-12805	-09449	-0.465	1.44183	3.19812	-0.03797	
1.469	-6.086	-2.27192	-158.14300	-27192	-12801	-09134	-0.4441	1.44531	3.21071	-0.0409	
1.469	-5.591	-2.27509	-156.85440	-25145	-11799	-09409	-0.4415	1.44777	3.21966	-0.03077	
1.469	-5.097	-2.27760	-154.82100	-22939	-10730	-09356	-0.4377	1.45025	3.22866	-0.02766	
1.470	-4.609	-2.28328	-152.47090	-20692	-09664	-09267	-0.4328	1.45294	3.23847	-0.02578	
1.468	-4.120	-2.28621	-149.68480	-18626	-08692	-09122	-0.4257	1.45194	3.23483	-0.02505	
1.470	-3.632	-2.29396	-146.30460	-16491	-07689	-09108	-0.4247	1.45448	3.24410	-0.02328	
1.470	-3.150	-2.30164	-142.29100	-14310	-06663	-09034	-0.4207	1.45583	3.24905	-0.02176	
1.471	-2.670	-2.31691	-137.32720	-12261	-05699	-08996	-0.4181	1.45792	3.25667	-0.01979	
1.471	-2.185	-2.33245	-131.21550	-10174	-04723	-09001	-0.4178	1.45789	3.25657	-0.01879	
1.470	-1.710	-2.36119	-123.79860	-08109	-03762	-08964	-0.4159	1.45894	3.26042	-0.01813	
1.470	-1.232	-2.39152	-114.91800	-06145	-02852	-09023	-0.4187	1.45845	3.25863	-0.01827	
1.470	-0.748	-2.43309	-104.57430	-04119	-01911	-09168	-0.4254	1.45876	3.25976	-0.01805	
1.471	-0.271	-2.49227	-93.55919	-02145	-00995	-09335	-0.4331	1.45947	3.26237	-0.01797	
1.470	.242	-2.54252	-81.87105	.00037	.00017	.09569	.04437	.1.45913	3.26110	.01761	
1.484	.756	-2.59282	-71.09325	.02019	.00955	.09510	.04496	.1.45873	3.25966	.01730	
	GRADIENT	-0.05788	15.43899	.04249	.01984	.00065	.00031	.00130	.00476	.00159	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM044) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1586/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.500	PHI =	-180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
1.491	-7.079	-2.28295	-161.40920	-32912	-15729	-0.9894	-0.04729	1.45791	3.25664	-0.04772
1.492	-6.571	-2.28428	-160.04930	-30847	-14700	-0.9729	-0.04636	1.46106	3.26822	-0.04460
1.491	-6.082	-2.28375	-158.57080	-28632	-13616	-0.9755	-0.04639	1.46246	3.27332	-0.04265
1.491	-5.586	-2.28636	-156.81480	-26655	-12643	-0.9772	-0.04635	1.46468	3.28152	-0.03993
1.492	-5.091	-2.28859	-154.78140	-24518	-11612	-0.9747	-0.04616	1.46648	3.28816	-0.03795
1.492	-4.603	-2.29556	-152.39160	-22408	-10592	-0.9760	-0.04614	1.46814	3.29426	-0.03593
1.492	-4.111	-2.30195	-149.56590	-20242	-09551	-0.9709	-0.04581	1.47021	3.30190	-0.03400
1.491	-3.622	-2.30933	-146.18570	-18110	-08530	-0.9724	-0.04580	1.47133	3.30604	-0.03244
1.492	-3.141	-2.31518	-142.17200	-15916	-07483	-0.9806	-0.04610	1.47330	3.31335	-0.03033
1.492	-2.659	-2.32844	-137.20820	-13656	-06410	-0.9804	-0.04602	1.47459	3.31815	-0.02868
1.491	-2.175	-2.34135	-131.13610	-11531	-05411	-0.9900	-0.04646	1.47456	3.31801	-0.02844
1.491	-1.701	-2.36880	-123.71910	-09286	-04356	-1018	-0.04700	1.47470	3.31854	-0.02827
1.491	-1.219	-2.39840	-114.79890	-07096	-03328	-10207	-0.04787	1.47505	3.31985	-0.02798
1.492	-1.736	-2.43774	-104.45510	-04817	-02259	-10453	-0.04901	1.47579	3.32256	-0.02767
1.492	-1.256	-2.48889	-93.40036	-02557	-01199	-10660	-0.04991	1.47542	3.32121	-0.02782
1.492	.257	-2.54133	-81.71225	-00163	-00076	-10954	-0.05137	1.47519	3.32037	-0.02788
1.492	.772	-2.58808	-70.89484	.02185	.01025	-11075	-0.05194	1.47543	3.32122	-0.02788
GRADIENT	- .05395	15.42905	.04593	.02167	.00265	-.00118	.00120	.00446	.00138	
	RUN NO.	1602/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
1.516	-7.084	-2.28304	-161.40920	-37258	-17698	-1.1179	-0.05310	1.49261	3.38541	-0.03544
1.516	-6.572	-2.27856	-160.08860	-34918	-16534	-1.1158	-0.05283	1.49552	3.39638	-0.03222
1.517	-6.076	-2.28438	-158.53100	-32620	-15395	-1.1168	-0.05271	1.49968	3.41205	-0.02858
1.517	-5.580	-2.28692	-156.77500	-30210	-14223	-1.1134	-0.05242	1.50188	3.42041	-0.02603
1.516	-5.096	-2.28973	-154.78150	-27665	-13005	-1.0913	-0.05130	1.50295	3.42444	-0.02450
1.517	-4.604	-2.29408	-152.39150	-25100	-11798	-1.0783	-0.05069	1.50319	3.42535	-0.02393
1.517	-4.112	-2.29940	-149.56580	-22826	-10774	-1.0974	-0.05157	1.50425	3.42937	-0.02357
1.517	-3.624	-2.30666	-146.18560	-20549	-09647	-1.1155	-0.05237	1.50448	3.43025	-0.02259
1.517	-3.139	-2.31756	-142.09270	-18065	-08471	-1.1269	-0.05284	1.50559	3.43443	-0.02126
1.517	-2.660	-2.32827	-137.16850	-15392	-07201	-1.1405	-0.05336	1.50758	3.44200	-0.01905
1.517	-2.178	-2.34502	-131.09650	-12809	-05981	-1.1538	-0.05387	1.50935	3.44875	-0.01713
1.517	-1.698	-2.36381	-123.67930	-10140	-04735	-1.1668	-0.05448	1.50937	3.44883	-0.01718
1.517	-1.218	-2.39898	-114.71960	-07609	-03551	-1.1735	-0.05477	1.50949	3.44927	-0.01689
1.517	-.736	-2.44227	-104.41560	-05094	-02375	-1.1870	-0.05536	1.51030	3.45235	-0.01612
1.517	-.255	-2.48914	-93.36072	-02504	-01168	-1.2111	-0.05647	1.51055	3.45332	-0.01602
1.517	.257	-2.54132	-81.67264	.00132	.00062	-1.2332	-0.05747	1.51114	3.45556	-0.01585
1.516	.771	-2.58876	-70.89484	.02802	.01306	-1.2385	-0.05771	1.51038	3.45266	-0.01594
GRADIENT	- .05446	15.42836	.05263	.02472	.00293	-.00127	.00153	.00582	.00169	

PAGE 332  
# OCT 91 )

(TCM044) ( 04 OCT 91 )

PARAMETRIC DATA

RUN NO.	1617/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.500	PHI =	-180.000
ALPHA	BETA	PHI	CPO	CPALPH	CPBQ	CPBE	MPROBE	CPM	CPTD
MACH									
1.541	-7.079	-2.27770	-161.44850	-36246	-17148	-11915	-05637	3.51166	-02629
1.541	-6.570	-2.28413	-160.04930	.33074	-15609	-11543	-05448	3.52332	-02357
1.541	-6.076	-2.28147	-158.50760	-29969	-14121	-11330	-05339	3.52906	-02190
1.541	-5.581	-2.28401	-156.81460	-27068	-12751	-11132	-05244	3.52926	-02165
1.541	-5.091	-2.28842	-154.78140	-24187	-11393	-10942	-05154	3.52954	-02157
1.541	-4.603	-2.29502	-152.39160	-21301	-10035	-10788	-05082	3.52961	-02168
1.541	-4.115	-2.30354	-149.56610	-18555	-08741	-10587	-04988	3.52766	-02169
1.541	-3.624	-2.30557	-146.2530	-15796	-07440	-10279	-04841	3.52906	-02142
1.542	-3.136	-2.31140	-142.17180	-13120	-06173	-09779	-04601	1.53199	3.53559
1.542	-2.659	-2.32784	-137.20820	-10449	-04912	-09201	-04325	1.53280	3.53874
1.542	-2.175	-2.34010	-131.13600	-08254	-03878	-08714	-04094	1.53365	3.54204
1.541	-1.697	-2.37005	-123.63980	-06308	-02965	-08415	-03955	1.53271	3.53839
1.541	-1.218	-2.39840	-114.75920	-04553	-02142	-08258	-03884	1.53211	3.53605
1.542	-7.37	-2.44207	-104.45520	-02827	-01330	-08166	-03843	1.53226	3.53663
1.542	-2.54	-2.48111	-93.36072	-01239	-00583	-02827	-03899	1.53204	3.53578
1.542	-257	-2.54149	-81.71225	.00551	.00259	-08315	-03911	1.53274	3.53850
1.541	.771	-2.58860	-70.93446	.02253	.01059	-08262	-03884	1.53262	3.53803
GRADIENT	-0.5446	15.42619	.04349	.00446	.02048	.00250	.00527	.00043	.00166

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM045 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1571/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
.599	-7.078	-1.73062	-165.265610	-.30673	-.06149	-.07526	-.01509	.57514	1.25134	-.01823
.599	-6.577	-1.72564	-164.26540	-.28489	-.05708	-.07431	-.01489	.57869	1.25470	-.01602
.599	-6.082	-1.72791	-163.02700	-.26405	-.05269	-.07336	-.01464	.58225	1.25812	-.01293
.600	-5.586	-1.72895	-161.59010	-.24236	-.04839	-.07232	-.01444	.58472	1.26049	-.01159
.599	-5.096	-1.73104	-159.91540	-.22141	-.04406	-.07095	-.01412	.58693	1.26263	-.00951
.600	-4.607	-1.73442	-157.92360	-.20057	-.03991	-.07024	-.01397	.58972	1.26535	-.00779
.600	-4.121	-1.74144	-155.49590	-.18024	-.03583	-.07032	-.01398	.59118	1.26678	-.00670
.600	-3.632	-1.74886	-152.51320	-.15966	-.03169	-.07025	-.01394	.59246	1.26803	-.00558
.600	-3.149	-1.75440	-148.89670	-.13920	-.02760	-.06994	-.01387	.59423	1.26978	-.00431
.600	-2.668	-1.76466	-144.29000	-.11781	-.02337	-.06946	-.01378	.59589	1.27142	-.00345
.600	-2.194	-1.78235	-138.37690	-.09720	-.01926	-.06972	-.01381	.59652	1.27204	-.00277
.600	-1.723	-1.80804	-130.76200	-.07758	-.01537	-.06935	-.01374	.59745	1.27296	-.00214
.600	-1.258	-1.85145	-120.97120	-.05753	-.01139	-.07017	-.01390	.59800	1.27351	-.00175
.600	-788	-1.90326	-108.92620	-.03855	-.00762	-.07176	-.01418	.59791	1.27342	-.00133
.600	-317	-1.97205	-95.30020	-.01918	-.00380	-.07376	-.01460	.59863	1.27414	-.00124
.600	-194	-2.05130	-80.72488	-.00165	-.00033	-.07641	-.01511	.59839	1.27389	-.00122
.600	.719	-2.12437	-67.57410	.02227	.00440	-.07933	-.01569	.59823	1.27374	-.00128
GRADIENT		-.07064	17.10911	.04211	.00837	-.00139	-.00026	.00166	.00164	.00125
	RUN NO.	1461/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
.800	-7.059	-1.80353	-165.02980	-.29305	-.08824	-.07413	-.02232	.77511	1.48758	-.02465
.800	-6.553	-1.80461	-163.90990	-.27241	-.08181	-.07455	-.02239	.77837	1.49229	-.02163
.800	-6.054	-1.80685	-162.63160	-.25247	-.07554	-.07361	-.02203	.78087	1.49593	-.01864
.800	-5.558	-1.80907	-161.15490	-.23193	-.06923	-.07180	-.02143	.78347	1.49972	-.01611
.800	-5.065	-1.80645	-159.47990	-.21184	-.06311	-.07079	-.02109	.78617	1.50369	-.01374
.800	-4.575	-1.81290	-157.40880	-.19192	-.05704	-.07080	-.02104	.78800	1.50639	-.01167
.800	-4.084	-1.81711	-154.94110	-.17230	-.05115	-.07042	-.02091	.79012	1.50953	-.00993
.800	-3.596	-1.82019	-151.95830	-.15199	-.04505	-.06996	-.02074	.79189	1.51216	-.00824
.800	-3.105	-1.82459	-148.22260	-.13165	-.03895	-.06970	-.02062	.79303	1.51387	-.00685
.800	-2.618	-1.83044	-143.53650	-.11170	-.03300	-.06943	-.02051	.79429	1.51574	-.00554
.800	-2.140	-1.84440	-137.54410	-.09186	-.02713	-.06907	-.02040	.79528	1.51723	-.00475
.800	-1.664	-1.86552	-129.81030	-.07249	-.02139	-.06895	-.02034	.79597	1.51827	-.00394
.800	-1.187	-1.89326	-119.90050	-.05303	-.01564	-.06923	-.02042	.79675	1.51944	-.00337
.800	-709	-1.92875	-107.73660	-.03429	-.01010	-.07020	-.02069	.79694	1.51972	-.00286
.800	-234	-1.98354	-94.07101	-.01554	-.00458	-.07145	-.02105	.79751	1.52058	-.00253
.800	.278	-2.04179	-79.49565	.00395	.00116	-.07315	-.02155	.79749	1.52056	-.00238
.800	.798	-2.09695	-66.46375	.02437	-.00718	-.07469	-.02201	.79770	1.52087	-.00242
GRADIENT		-.05070	17.07142	.04041	.01199	-.00058	-.00014	.00173	.00259	.00171

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 534  
(TCM045) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1495/ O	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	-2.000	PHI	=	180.000
MACH									CPTD					
ALPHA									CPBQ					
	-7.060	-1.79135	-165.06920	-28133	.09676	-.07020	-.02414	.87585	1.64801					
	-6.552	-1.79246	-163.94930	-26171	.08971	-.07070	-.02423	.87907	1.65366	-.02264				
	-6.059	-1.79194	-162.71060	-24227	.08280	-.06967	-.02381	.88146	1.65789	-.01979				
	-5.561	-1.79410	-161.23390	-22265	.07591	-.06931	-.02363	.88450	1.66329	-.01692				
	-5.066	-1.79533	-159.51940	-20343	.06919	-.06774	-.02304	.88674	1.66729	-.01446				
	-4.581	-1.80009	-157.48790	-18428	.06255	-.06753	-.02292	.88877	1.67092	-.01237				
	-4.089	-1.80472	-155.02030	-16516	.05597	-.06707	-.02273	.89106	1.67505	-.01024				
	-3.595	-1.80566	-152.03730	-14614	.04944	-.06709	-.02270	.89214	1.67699	-.00887				
	-3.113	-1.81291	-148.34160	-12685	.04281	-.06551	-.02211	.89326	1.67903	-.00700				
	-2.624	-1.82105	-143.61590	-10741	.03623	-.06621	-.02233	.89467	1.68158	-.00596				
	-2.142	-1.83194	-137.62330	-08854	.02982	-.06652	-.02241	.89535	1.68281	-.00492				
	-1.669	-1.85145	-129.92910	-06978	.02348	-.06762	-.02275	.89612	1.68421	-.00400				
	-1.196	-1.88342	-120.05910	-05122	.01722	-.06876	-.02312	.89677	1.68540	-.00331				
	-720	-1.92631	-107.85570	-03301	.01109	-.06985	-.02347	.89689	1.68562	-.00277				
	-245	-1.98345	-94.19006	-01495	.00503	-.07089	-.02383	.89759	1.68690	-.00262				
	.267	-2.04498	-79.61469	.00364	.00122	-.07222	-.02427	.89755	1.68682	-.00243				
	.786	-2.09850	-66.58282	.02346	.00788	-.07307	-.02455	.89790	1.68747	-.00231				
GRADIENT		-0.05397	17.08917	.03886	.01317	-.00119	-.00036	.00161	.00291	.00184				
									CPTD					
									CPBQ					
MACH									CPALPH					
ALPHA										CPBQ				
	-7.027	-1.93003	-164.43690	-25292	.10341	-.06706	-.02742	.1.07881	2.07896					
	-6.516	-1.92877	-163.72690	-23502	.09565	-.06793	-.02765	.1.08108	2.08465					
	-6.017	-1.92913	-161.95850	-21704	.08797	-.06785	-.02750	.1.08335	2.09038					
	-5.516	-1.92780	-160.44180	-19969	.08071	-.06688	-.02703	.1.08536	2.09545					
	-5.025	-1.93127	-158.64790	-18211	.07341	-.06596	-.02659	.1.08776	2.10152					
	-4.523	-1.93350	-156.49700	-16489	.06633	-.06453	-.02596	.1.08949	2.10593					
	-4.021	-1.94621	-153.99030	-14715	.05907	-.06406	-.02572	.1.09097	2.10969					
	-3.531	-1.92978	-151.12570	-12984	.05201	-.06322	-.02532	.1.09210	2.11259					
	-3.035	-1.93258	-147.27090	-11163	.04466	-.06286	-.02514	.1.09398	2.11737					
	-2.542	-1.93273	-142.46560	-09385	.03748	-.06227	-.02487	.1.09464	2.11908					
	-2.052	-1.93755	-136.31440	-07636	.03048	-.06171	-.02464	.1.09579	2.12202					
	-1.560	-1.94669	-128.34270	-05903	.02352	-.06140	-.02447	.1.09635	2.12347					
	-1.075	-1.95695	-118.35360	-04166	.01660	-.06129	-.02442	.1.09689	2.12485					
	-1.000	-1.97162	-106.07090	-02534	.01009	-.06116	-.02436	.1.09744	2.12627					
	-1.000	-1.99713	-92.32605	-00848	.00337	-.06173	-.02457	.1.09765	2.12679					
	.405	-2.02171	-77.82996	.00803	.03220	-.06191	-.02465	.1.09782	2.12722					
	.915	-2.04641	-64.99631	.02522	.01004	-.06211	-.02472	.1.09786	2.12734					
GRADIENT		-0.01898	16.97772	.03511	.01409	.00048	.00024	.00154	.00395	.00191				

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM045) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1518/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.250	-7.049	-1.83571	-164.87160	-26185	-11511	-0.06555	-0.02886	1.22727	-0.02765
1.250	-6.539	-1.83441	-163.75150	-24350	-10668	-0.06548	-0.02872	1.22980	-0.02426
1.250	-6.042	-1.83477	-162.47290	-22546	-09845	-0.06493	-0.02859	1.23283	-0.02081
1.250	-5.546	-1.83980	-160.95680	-20716	-09015	-0.06493	-0.02826	1.23563	-0.01730
1.250	-5.047	-1.83806	-159.24200	-18855	-08188	-0.06333	-0.02750	1.23700	-0.01531
1.249	-4.558	-1.84410	-157.17090	-17025	-07381	-0.06317	-0.02738	1.23803	-0.01365
1.250	-4.063	-1.84606	-154.70310	-15307	-06621	-0.06197	-0.02680	1.24059	-0.01116
1.250	-3.575	-1.85115	-151.68070	-13518	-05839	-0.06152	-0.02657	1.24182	-0.00971
1.250	-3.082	-1.84985	-147.98460	-11680	-05036	-0.06109	-0.02634	1.24352	-0.00791
1.250	-2.598	-1.86042	-143.21930	-09874	-04251	-0.06102	-0.02627	1.24479	-0.00635
1.250	-2.112	-1.86601	-137.18700	-08079	-03473	-0.06101	-0.02623	1.24561	-0.00504
1.250	-1.636	-1.88595	-129.41360	-06368	-02735	-0.06087	-0.02614	1.24609	-0.00412
1.250	-1.157	-1.90526	-119.50380	-04629	-01987	-0.06151	-0.02641	1.24669	-0.00362
1.250	-0.678	-1.94350	-107.22120	-02957	-01269	-0.06226	-0.02671	1.24706	-0.00297
1.250	-0.201	-1.98972	-93.55554	-01276	-00547	-0.06337	-0.02719	1.24772	-0.00288
1.249	.313	-2.03967	-78.98018	.00489	.00210	-0.06491	-0.02783	1.24728	-0.00263
1.250	.830	-2.08287	-65.98795	.02290	.00982	-0.06561	-0.02814	1.24772	-0.00266
GRADIENT	-.04291	17.07617	.03604	.01559	.00053	-.00017	.00167	.00507	.00201

RUN NO.	1534/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.400	-7.044	-1.84950	-164.83230	-29013	-13433	-0.06705	-0.03105	1.37501	-0.02908
1.400	-6.539	-1.84851	-163.71220	-27042	-12472	-0.06702	-0.03091	1.37814	-0.02514
1.400	-6.036	-1.85159	-162.39400	-25000	-11496	-0.06707	-0.03084	1.38122	-0.02194
1.400	-5.541	-1.85210	-160.91730	-22979	-10542	-0.06639	-0.03046	1.38365	-0.01948
1.400	-5.046	-1.85630	-159.16320	-20988	-09599	-0.06583	-0.03011	1.38572	-0.01644
1.400	-4.554	-1.85473	-157.13130	-19108	-08714	-0.06514	-0.02970	1.38789	-0.01359
1.400	-4.058	-1.85913	-154.62390	-17164	-07812	-0.06459	-0.02940	1.39011	-0.01158
1.399	-3.570	-1.86225	-151.60140	-15140	-06874	-0.06434	-0.02921	1.39150	-0.00921
1.400	3.074	-1.86339	-147.82590	-13059	-05921	-0.06384	-0.02894	1.39314	-0.00403
1.400	-2.590	-1.87198	-143.06060	-11063	-05009	-0.06342	-0.02871	1.39413	-0.00392
1.400	-2.108	-1.88101	-137.02850	-03091	-04113	-0.06261	-0.02833	1.39574	-0.00337
1.400	-1.621	-1.89184	-129.17560	-07118	-03219	-0.06281	-0.02841	1.39533	-0.00516
1.400	-1.143	-1.91399	-119.22630	-05255	-02374	-0.06379	-0.02882	1.39658	-0.00403
1.400	-0.662	-1.94446	-106.94360	-03380	-01527	-0.06467	-0.02921	1.39653	-0.00371
1.400	-0.184	-1.99231	-93.23843	-01522	-00687	-0.06591	-0.02975	1.39703	-0.00384
1.400	.329	-2.03788	-78.70267	.00447	.00202	-0.06761	-0.03052	1.39710	-0.00329
1.400	.847	-2.08247	-65.74998	.02442	.01102	-0.06858	-0.03096	1.39727	-0.00328
GRADIENT	-.03996	17.07821	.04006	.01822	-.00059	.00021	.00164	.00570	.00183

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM045) (04 OCT 91)

PAGE 536

## PARAMETRIC DATA

	RUN NO.	1552/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-2.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBETA	CPBETA	CPBETA	CPBETA	CPTD
1.450	-7.072	-1.74103	-165.26630	-130471	-14307	-07039	-03305	1.42416	3.13464	-0.02976		
1.450	-6.564	-1.73846	-164.18600	-28446	-13316	-07054	-03302	1.42722	3.14556	-0.02657		
1.450	-6.068	-1.74346	-162.90790	-26357	-12299	-07102	-03314	1.42969	3.15439	-0.02335		
1.450	-5.576	-1.74390	-161.47100	-24228	-11277	-06979	-03248	1.43117	3.15971	-0.02097		
1.450	-5.085	-1.74811	-159.75670	-22104	-10268	-06984	-03245	1.43308	3.16657	-0.01891		
1.450	-4.596	-1.74973	-157.76480	-20232	-09364	-06892	-03190	1.43660	3.17922	-0.01512		
1.449	-4.104	-1.75641	-155.29740	-18264	-08431	-06834	-03154	1.43851	3.18612	-0.01248		
1.451	-3.615	-1.76125	-152.35440	-16199	-07462	-06772	-03120	1.44199	3.19868	-0.01007		
1.450	-3.130	-1.76740	-148.69830	-14085	-06475	-06744	-03101	1.44272	3.20134	-0.00825		
1.450	-2.651	-1.77599	-144.09160	-11898	-05467	-06742	-03098	1.44286	3.20182	-0.00774		
1.450	-2.180	-1.79662	-138.13900	-09842	-04519	-06718	-03085	1.44318	3.20300	-0.00721		
1.451	-1.705	-1.81743	-130.48440	-07867	-03611	-06755	-03101	1.44506	3.20983	-0.00648		
1.450	-1.239	-1.85405	-120.69360	-05937	-02723	-06869	-03150	1.44444	3.20757	-0.00588		
1.450	-767	-1.90630	-108.52980	-03991	-01829	-07044	-03228	1.44513	3.21007	-0.00521		
1.450	-297	-1.97926	-94.90388	-02023	-00927	-07254	-03324	1.44575	3.21229	-0.00487		
1.450	.217	-2.05404	-80.28891	.00066	.00030	-07532	-03449	1.44607	3.21348	-0.00443		
1.450	.738	-2.11961	-67.25696	.02171	.00995	-07696	-03526	1.44563	3.21188	-0.00478		
	GRADIENT	-.06726	17.13468	.04230	.01953	-.00149	-.00063	.00155	.00560	.00178		
	RUN NO.	1636/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-2.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBETA	CPBETA	CPBETA	CPBETA	CPTD
1.470	-7.065	-1.75897	-165.18710	-31051	-14720	-.07247	-.03435	1.44041	3.19299	-.04018		
1.470	-6.561	-1.76171	-164.06740	-29034	-13717	-.07245	-.03423	1.44241	3.20019	-.03691		
1.470	-6.061	-1.75976	-162.82860	-27033	-12722	-.07159	-.03369	1.44650	3.21503	-.03277		
1.469	-5.573	-1.76592	-161.35240	-24913	-11685	-.07229	-.03391	1.44844	3.22210	-.02955		
1.470	-5.082	-1.76881	-159.63800	-22661	-10606	-.07143	-.03343	1.45116	3.23200	-.02714		
1.470	-4.585	-1.77264	-157.60650	-20514	-.09589	-.07075	-.03307	1.45175	3.23415	-.02594		
1.470	-4.099	-1.77761	-155.17870	-18409	-.08590	-.06956	-.03246	1.45397	3.24224	-.02410		
1.470	-3.610	-1.77899	-152.23550	-16284	-.07586	-.06876	-.03203	1.45509	3.24633	-.02242		
1.470	-3.129	-1.78824	-148.53980	-14156	-.06582	-.06840	-.03181	1.45660	3.25185	-.02054		
1.469	-2.642	-1.79458	-143.89340	-12059	-.05596	-.06797	-.03154	1.45717	3.25393	-.01915		
1.470	-2.165	-1.81134	-137.90100	-.09946	-.04617	-.06772	-.03144	1.45841	3.25847	-.01886		
1.470	-1.692	-1.83465	-130.20680	-.08032	-.03729	-.06758	-.03138	1.45833	3.25818	-.01893		
1.470	-1.222	-1.86963	-120.37640	-.06120	-.02839	-.06913	-.03207	1.45923	3.26147	-.01825		
1.470	-748	-1.91745	-108.21260	-.04178	-.01938	-.07139	-.03310	1.45891	3.26033	-.01793		
1.470	-274	-1.98093	-94.58664	-.02175	-.01008	-.07355	-.03410	1.45946	3.26235	-.01767		
1.470	.237	-2.05034	-80.05089	-.00031	-.00014	-.07653	-.03548	1.45925	3.26155	-.01762		
1.469	.759	-2.11068	-66.97935	.02108	.00977	-.07817	-.03622	1.45940	3.26209	-.01724		
	GRADIENT	-.06164	17.11458	.04228	.01973	-.00143	-.00061	.00130	.00477	.00147		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM045) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPME	CPTD
1.492	-7.065	-1.77745	-165.10840	-32825	-15666	-07459	.03560	1.45963	3.26296
1.492	-6.558	-1.777388	-164.02800	-30599	-14576	-07445	.03547	1.46178	3.27084
1.492	-6.061	-1.77744	-162.74980	-28555	-13570	-07463	.03547	1.46368	3.27784
1.492	-5.569	-1.777656	-161.31280	-26557	-12585	-07387	.03501	1.46663	3.28869
1.491	-5.076	-1.78292	-159.55890	-24445	-11561	-07443	.03520	1.46731	3.29122
1.491	-4.586	-1.78611	-157.52730	-22302	-10530	-07438	.03512	1.46906	3.29766
1.491	-4.094	-1.78770	-155.09920	-20136	-09488	-07392	.03483	1.47086	3.30432
1.491	-3.601	-1.79665	-152.07710	-18017	-08473	-07339	.03451	1.47266	3.31097
1.491	-3.117	-1.79850	-148.42070	-15792	-07416	-07390	.03470	1.47392	3.31564
1.491	-2.637	-1.81240	-143.73500	-13549	-06357	-07420	.03482	1.47472	3.31863
1.492	-2.156	-1.82269	-137.78200	-11367	-05333	-07544	.03539	1.47519	3.32036
1.492	-1.682	-1.84400	-130.08780	-09211	-04321	-0696	.03610	1.47524	3.32054
1.492	-1.208	-1.87372	-120.21770	-07014	-03291	-07874	.03694	1.47538	3.32106
1.491	-7.736	-1.92319	-108.05400	-04825	-02264	-08129	.03814	1.47464	3.31830
1.492	-.260	-1.97814	-94.38832	-02516	-01181	-08366	.03926	1.47490	3.31927
1.492	.251	-2.04902	-79.85258	-00103	-00049	-08757	.04112	1.47459	3.31814
1.492	.775	-2.11066	-66.78099	.02288	.04200	-08942	.04200	1.47499	3.31961
GRADIENT	-.05816	17.09116	.04604	.02169	.00299	-.00138	.00087	.00093	.00093
RUN NO.	1603/ 0	RN/L =	2.49		GRADIENT	INTERVAL =	-5.00/ 5.00		
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPME	CPTD
1.516	-7.071	-1.77375	-165.14800	-36977	-17549	-08550	.04058	1.49336	3.38821
1.516	-6.562	-1.77451	-164.02810	-34662	-16387	-08517	.04026	1.49713	3.40245
1.516	-6.066	-1.77818	-162.74990	-32444	-15298	-08537	.04025	1.49956	3.41162
1.515	-5.568	-1.78023	-161.27330	-30041	-14129	-08534	.04014	1.50099	3.41703
1.515	-5.071	-1.78086	-159.55870	-27457	-12881	-08332	.03909	1.50323	3.42551
1.515	-4.585	-1.78603	-157.52730	-24898	-11664	-08175	.03830	1.50432	3.42965
1.515	-4.089	-1.78569	-155.09910	-22442	-10507	-08195	.03837	1.50504	3.43238
1.515	-3.602	-1.79452	-152.07700	-20199	-09448	-08350	.03906	1.50619	3.43672
1.515	-3.119	-1.80250	-148.38120	-17745	-08288	-08546	.03991	1.50728	3.44086
1.515	-2.633	-1.80725	-143.73470	-15103	-07042	-08634	.04026	1.50803	3.44372
1.515	-2.156	-1.82070	-137.78190	-12399	-05775	-08678	.04042	1.50925	3.44837
1.515	-1.685	-1.84812	-130.04830	-10894	-04602	-08830	.04107	1.51094	3.45479
1.515	-1.211	-1.87698	-120.21780	-07416	-03445	-08969	.04167	1.51161	3.45735
1.514	-.736	-1.92770	-108.01440	-04891	-02272	-09057	.04207	1.51120	3.45579
1.514	-.261	-1.98280	-94.38835	-02353	-01093	-09305	.04322	1.51097	3.45491
1.514	.251	-2.05365	-79.85257	.00231	.00107	.09616	.04466	1.51146	3.45678
1.515	.775	-2.11023	-66.78099	.02918	.01355	-.09784	.04544	1.51194	3.45862
GRADIENT	-.05919	17.10197	.05249	.02457	-.00297	.00131	.00150	.00093	.00093

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM045) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1618/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA = -2.000	PHI = 180.000	CPTD
<b>MACH</b>									
1.541	-7.064	-1.77790	-165.10850	-35786	CPAO	CPALPH	CPBQ	CPBTA	MPROBE
1.542	-6.556	-1.77881	-163.98860	-32544	-16911	-0.9340	-0.4414	1.52774	3.51919
1.541	-6.061	-1.77735	-162.74980	-29419	-15368	-0.8991	-0.4246	1.52876	3.52313
1.541	-5.567	-1.78079	-161.27330	-26615	-13854	-0.8704	-0.4099	1.53038	3.52939
1.541	-5.076	-1.78348	-159.55890	-23687	-12534	-0.8543	-0.4023	1.53097	3.53165
1.541	-4.580	-1.78481	-157.52720	-20902	-11160	-0.8459	-0.3986	1.53024	3.52883
1.541	-4.093	-1.78974	-155.09940	-18087	-09850	-0.8373	-0.3946	1.53035	3.52928
1.541	-3.602	-1.79355	-152.11660	-15167	-08517	-0.8038	-0.3785	1.53054	3.52999
1.541	-3.116	-1.79948	-148.42080	-12345	-07138	-0.7654	-0.3602	1.53091	3.53144
1.541	-2.638	-1.80952	-143.77450	-108.01430	-05803	-0.7147	-0.3360	1.53196	3.53550
1.541	-2.156	-1.82143	-137.78200	-102944	-04653	-0.6700	-0.3147	1.53269	3.53831
1.541	-1.682	-1.84357	-130.08780	-102944	-04653	-0.6436	-0.3025	1.53274	3.53850
1.542	-1.211	-1.87693	-120.21780	-102944	-03714	-0.6436	-0.3027	1.53152	3.53376
1.541	-0.734	-1.92292	-108.01430	-102944	-02930	-0.6435	-0.3027	1.53243	3.53732
1.542	-0.260	-1.98323	-94.38835	-102944	-02930	-0.6374	-0.2998	1.53157	3.53397
1.541	.252	-2.04863	-79.85258	-00449	-02201	-0.6382	-0.3002	1.53157	3.53397
1.542	.775	-2.11046	-66.78099	-01035	-04220	-0.6382	-0.3002	1.53245	3.53737
GRADIENT									
		- .05863	17.10636	.04220	.01987	.00319	.00151	.00027	.00103

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM046 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	BETA = -1.500	PHI = 180.000
											RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00
.599	-7.062	-1.22410	-169.16550	-30453	-.06108	-.05204	-.01044	.57579	1.25195	-.01797		
.599	-6.552	-1.22080	-168.36500	-28375	-.05674	-.05157	-.01031	.57949	1.25546	-.01505		
.600	-6.061	-1.22468	-167.40630	-26128	-.05226	-.05087	-.01018	.58281	1.25865	-.01317		
.600	-5.564	-1.22294	-166.32820	-24004	-.04800	-.04946	-.00989	.58574	1.26148	-.01137		
.600	-5.069	-1.22589	-165.01230	-21910	-.04372	-.04860	-.00970	.58776	1.26344	-.00968		
.600	-4.578	-1.22710	-163.45830	-19839	-.03951	-.04796	-.00955	.58969	1.26532	-.00807		
.600	-4.089	-1.23035	-161.54750	-17860	-.03551	-.04879	-.00970	.59141	1.26701	-.00659		
.600	-3.601	-1.23150	-159.20030	-15826	-.03141	-.04867	-.00966	.59386	1.26941	-.00477		
.600	-3.115	-1.23659	-156.17930	-13682	-.02710	-.04764	-.00944	.59461	1.27015	-.00385		
.600	-2.635	-1.24617	-152.20730	-11581	-.02293	-.04725	-.00935	.59560	1.27113	-.00310		
.600	-2.160	-1.25692	-146.92780	-09566	-.01896	-.04689	-.00929	.59721	1.27273	-.00241		
.599	-1.691	-1.27522	-139.58920	-07573	-.01496	-.04756	-.00939	.59716	1.27268	-.00161		
.600	-1.231	-1.30755	-129.28220	-05635	-.01114	-.04767	-.00943	.59839	1.27390	-.00123		
.600	-778	-1.36553	-115.01930	-03800	-.00751	-.04889	-.00967	.59796	1.27348	-.00136		
.600	-323	-1.46004	-97.39621	-01986	-.00393	-.05240	-.01035	.59866	1.27417	-.00084		
.600	.189	-1.56989	-78.03360	-00007	-.00001	-.05644	-.01117	.59867	1.27417	-.00121		
.600	.726	-1.655303	-61.55989	.02186	.00432	-.05952	-.01177	.59909	1.27460	-.00082		
	GRADIENT	-0.07488	18.99652	.04179	.00831	-.00170	-.00032	.00167	.00165	.00128		
RN NO.	1462/ 0	RN/L = 2.50										
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD		
.800	-7.047	-1.30253	-168.85000	-29119	-.08767	-.05195	-.01564	.77559	1.48826	-.02432		
.800	-6.538	-1.30131	-168.00970	-27096	-.08131	-.05237	-.01571	.77885	1.49298	-.02102		
.800	-6.044	-1.30175	-167.05070	-25077	-.07501	-.05173	-.01547	.78149	1.49683	-.01812		
.800	-5.543	-1.30016	-165.93270	-23022	-.06874	-.05041	-.01505	.78450	1.50123	-.01564		
.800	-5.050	-1.30355	-164.57700	-21042	-.06261	-.05023	-.01494	.78644	1.50409	-.01305		
.800	-4.560	-1.30520	-162.98340	-19036	-.05657	-.04953	-.01472	.78876	1.50751	-.01114		
.800	-4.061	-1.30442	-161.03240	-17046	-.05059	-.04935	-.01465	.79091	1.51071	-.00934		
.800	-3.571	-1.30911	-158.56630	-15025	-.04448	-.04936	-.01462	.79234	1.51284	-.00752		
.800	-3.084	-1.31379	-155.46590	-13042	-.03857	-.04913	-.01453	.79365	1.51479	-.00622		
.800	-2.598	-1.31844	-151.41430	-11026	-.03257	-.04844	-.01431	.79478	1.51648	-.00518		
.800	-2.115	-1.32572	-145.97620	-09056	-.02674	-.04813	-.01421	.79612	1.51849	-.00411		
.800	-1.639	-1.34113	-138.43950	-07143	-.02106	-.04781	-.01410	.79671	1.51938	-.00332		
.800	-1.172	-1.36631	-127.93460	-05258	-.01550	-.04779	-.01409	.79730	1.52026	-.00282		
.800	-707	-1.40681	-113.51350	-03418	-.01006	-.04895	-.01441	.79737	1.52037	-.00224		
.800	-240	-1.47307	-95.73209	-01627	-.00479	-.05084	-.01497	.79778	1.52099	-.00215		
.800	.271	-1.55502	-76.44870	.00288	.00085	-.05459	-.01607	.79810	1.52147	-.00192		
.800	.804	-1.62106	-60.17296	.02371	.00698	-.05592	-.01646	.79784	1.52108	-.00178		
	GRADIENT	-0.05443	18.99111	.04006	.01188	-.00091	-.00024	.00166	.00170	.00249		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 540  
( TCM046 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1496/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-1.500	PHI	=	180.000
CPTD												
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA					
.900	-7.048	-1.28562	-168.92880	-.27988	-.09617	-.05022	-.01726	.87650	1.64915	-.02528		
.900	-6.537	-1.28905	-168.04910	-.26020	-.08917	-.04932	-.01690	.87956	1.65454	-.02223		
.900	-6.041	-1.28930	-167.09000	-.24059	-.08216	-.04929	-.01683	.88236	1.65948	-.01891		
.900	-5.549	-1.29026	-165.97240	-.22122	-.07537	-.04864	-.01657	.88504	1.66425	-.01624		
.900	-5.050	-1.28872	-164.65610	-.20222	-.06871	-.04717	-.01603	.88721	1.66814	-.01371		
.900	-4.558	-1.29043	-163.06240	-.18306	-.06207	-.04663	-.01581	.88912	1.67155	-.01165		
.900	-4.063	-1.29151	-161.11160	-.16363	-.05542	-.04588	-.01554	.89138	1.67563	-.00984		
.900	-3.572	-1.29268	-158.64550	-.14441	-.04881	-.04647	-.01571	.89284	1.67827	-.00798		
.900	-3.081	-1.29683	-155.58460	-.12484	-.04214	-.04646	-.01568	.89424	1.68079	-.00655		
.900	-2.598	-1.30423	-151.53310	-.10600	-.03571	-.04615	-.01555	.89516	1.68247	-.00510		
.900	-2.120	-1.31442	-146.09510	-.08715	-.02933	-.04579	-.01541	.89577	1.68358	-.00416		
.900	-1.646	-1.32785	-138.63770	-.06863	-.02308	-.04580	-.01540	.89681	1.68547	-.00329		
.900	-1.179	-1.35416	-128.13270	-.05038	-.01693	-.04569	-.01536	.89723	1.68624	-.00287		
.900	-715	-1.39717	-113.67200	-.03250	-.01092	-.04672	-.01570	.89804	1.68771	-.00233		
.900	-252	-1.47111	-95.93025	-.01568	-.00527	-.04862	-.01633	.89791	1.68748	-.00202		
.900	.258	-1.55761	-76.68646	-.00257	-.00086	-.05192	-.01743	.89814	1.68789	-.00180		
.900	.790	-1.62297	-60.37114	-.02286	-.00767	-.05368	-.01802	.89807	1.68778	-.00168		
	GRADIENT	-.05775	19.01565	.03861	.01307	-.00107	-.00033	.00161	.00292	.00184		
CPTD												
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA					
1.099	-7.023	-1.42776	-168.25700	-.23209	-.10271	-.04885	-.01990	.07806	2.07707	-.02623		
1.099	-6.508	-1.42979	-167.33730	-.23397	-.09505	-.04945	-.02099	.08093	2.08427	-.02307		
1.100	-6.010	-1.42691	-166.33810	-.21644	-.08768	-.04834	-.01958	.08365	2.09113	-.02001		
1.100	-5.508	-1.42706	-165.14070	-.19890	-.08034	-.04802	-.01940	.08593	2.09689	-.01714		
1.100	-5.015	-1.42734	-163.74500	-.18149	-.07312	-.04720	-.01902	.08812	2.10245	-.01455		
1.100	-4.511	-1.44096	-162.07280	-.16385	-.06586	-.04701	-.01890	.08984	2.10683	-.01229		
1.100	-4.020	-1.42816	-160.20070	-.14610	-.05861	-.04666	-.01872	.09164	2.11140	-.01011		
1.100	-3.523	-1.42555	-157.69440	-.12830	-.05139	-.04586	-.01837	.09289	2.11460	-.00861		
1.100	-3.028	-1.42811	-154.43510	-.11032	-.04410	-.04495	-.01797	.09445	2.11859	-.00655		
1.100	-2.529	-1.42884	-150.18510	-.09254	-.03693	-.04477	-.01787	.09545	2.12114	-.00510		
1.099	-2.044	-1.43177	-144.54880	-.07520	-.02998	-.04436	-.01768	.09594	2.12239	-.00427		
1.100	-1.555	-1.43412	-136.77420	-.05826	-.02321	-.04388	-.01748	.09703	2.12520	-.00321		
1.100	-1.069	-1.44268	-125.95260	-.04132	-.01645	-.04376	-.01742	.09732	2.12594	-.00278		
1.100	-589	-1.45900	-111.21490	-.02496	-.00994	-.04410	-.01756	.09806	2.12786	-.00255		
1.100	-115	-1.49139	-93.43382	-.00904	-.00360	-.04454	-.01772	.09789	2.12741	-.00212		
1.100	.393	-1.53180	-74.30887	-.00731	-.00291	-.04538	-.01805	.09838	2.12867	-.00186		
1.100	.911	-1.56242	-58.31047	-.02495	-.00993	-.04559	-.01814	.09827	2.12840	-.00179		
	GRADIENT	-.02088	18.96308	.03486	.01398	.00031	.00016	.00152	.00389	.00188		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM046 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1519/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
1.250	-7.038	-1.33428	-168.69170	-26064	-11451	-04648	-02042	1.22767	2.48914	-.02703
1.250	-6.525	-1.33521	-167.81170	-24230	-10609	-04647	-02035	1.23042	2.49739	-.02357
1.250	-6.031	-1.33776	-166.81310	-22433	-09785	-04651	-02029	1.23339	2.50633	-.01977
1.250	-5.532	-1.33434	-165.69500	-20572	-08947	-04620	-02009	1.23559	2.51297	-.01685
1.250	-5.034	-1.33626	-164.33930	-18714	-08124	-04539	-01970	1.23729	2.51807	-.01493
1.250	-4.540	-1.33507	-162.74540	-16933	-07337	-04416	-01914	1.23921	2.52390	-.01294
1.250	-4.046	-1.33880	-160.75510	-15149	-06551	-04380	-01894	1.24107	2.52954	-.01088
1.250	-3.558	-1.34246	-158.28890	-13336	-05754	-04359	-01881	1.24241	2.53361	-.00874
1.250	-3.068	-1.34301	-155.18830	-11538	-04970	-04261	-01835	1.24392	2.53819	-.00698
1.250	-2.578	-1.34634	-151.09710	-09749	-04195	-04245	-01826	1.24523	2.54220	-.00579
1.250	-2.091	-1.35164	-145.57960	-07966	-03423	-04264	-01832	1.24592	2.54430	-.00461
1.249	-1.615	-1.36482	-138.00340	-06294	-02701	-04263	-01830	1.24657	2.54627	-.00347
1.250	-1.143	-1.38325	-127.41920	-04611	-01979	-04303	-01846	1.24745	2.54895	-.00305
1.250	-675	-1.41781	-112.87940	-02964	-01271	-04402	-01887	1.24811	2.55099	-.00222
1.250	-208	-1.47802	-95.05852	-01310	-00561	-04565	-01957	1.24812	2.55100	-.00228
1.250	.305	-1.54917	-75.77515	.00456	.00195	-04804	-02059	1.24806	2.55084	-.00201
1.250	.836	-1.60643	-59.57860	.02312	.00991	-04922	-02109	1.24816	2.55113	-.00182
GRADIENT	.04572	19.000815	.03583	.01549	.00085	.00032	.00166	.00505		
	RUN NO.	1535/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPM	CPTD
1.400	-7.035	-1.34791	-168.65240	-28918	-13377	-04600	-02128	1.37564	2.96483	-.02815
1.400	-6.521	-1.34775	-167.77230	-26892	-12398	-04671	-02153	1.37846	2.97451	-.02472
1.400	-6.028	-1.34577	-166.81310	-24882	-11434	-04598	-02113	1.38154	2.98512	-.02132
1.400	-5.528	-1.34704	-165.65560	-22863	-10477	-04550	-02085	1.38354	2.99201	-.01862
1.400	-5.029	-1.35179	-164.26020	-20896	-09548	-04588	-02096	1.38680	3.00329	-.01552
1.400	-4.534	-1.35330	-162.62670	-18972	-08650	-04533	-02067	1.38849	3.00914	-.01329
1.400	-4.047	-1.35337	-160.67590	-17013	-07735	-04459	-02027	1.39067	3.01671	-.01052
1.400	-3.554	-1.35441	-158.20960	-15008	-06812	-04355	-01977	1.39215	3.02185	-.00885
1.400	-3.057	-1.35541	-155.02960	-12925	-05856	-04301	-01949	1.39374	3.02740	-.00692
1.400	-2.570	-1.36083	-150.89880	-10874	-04923	-04261	-01929	1.39482	3.03115	-.00612
1.400	-2.084	-1.36297	-145.42100	-08916	-04033	-04276	-01934	1.39509	3.03208	-.00530
1.400	-1.602	-1.37081	-137.76530	-07064	-04301	-04207	-01943	1.39615	3.03579	-.00428
1.400	-1.134	-1.39653	-127.06260	-05233	-02363	-04389	-01982	1.39648	3.03692	-.00374
1.400	-.660	-1.42705	-112.44360	-03412	-01539	-04523	-02040	1.39749	3.04046	-.00250
1.400	-.191	-1.48317	-94.62277	-01556	-00702	-04690	-02115	1.39778	3.04146	-.00222
1.399	.320	-1.54755	-75.41856	.00415	.00187	-04905	-02211	1.39768	3.04111	-.00206
1.400	.847	-1.59561	-59.30128	.02455	.01107	-05048	-02277	1.39785	3.04173	-.00244
GRADIENT	.04171	19.02419	.03984	.01812	.00097	.00040	.00166	.00578		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 542  
(TCM046) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1553/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.450	-7.050	-1.23799	-169.08620	-.30305	-.14221	-.04939	-.02318	1.42456	.02916
1.450	-6.544	-1.23397	-168.28560	-.28305	-.13241	-.04845	-.02266	1.42681	.02605
1.450	-6.052	-1.23662	-167.32680	-.26183	-.12214	-.04852	-.02263	1.43019	.02299
1.450	-5.558	-1.24271	-166.16980	-.24036	-.11185	-.04875	-.02269	1.43219	.02056
1.450	-5.064	-1.24051	-164.89330	-.22000	-.10212	-.04827	-.02241	1.43376	.01811
1.450	-4.572	-1.24419	-163.29980	-.20139	-.09314	-.04743	-.02194	1.43775	.01425
1.450	-4.076	-1.24564	-161.38880	-.18091	-.08344	-.04729	-.02181	1.43969	.01154
1.450	-3.587	-1.24979	-159.00210	-.15971	-.07356	-.04676	-.02153	1.44173	.00993
1.450	-3.103	-1.25050	-156.02070	-.13827	-.06355	-.04541	-.02087	1.44287	.00802
1.450	-2.622	-1.25815	-152.04860	-.11674	-.05365	-.04490	-.02064	1.44269	.00798
1.450	-2.142	-1.26743	-146.68980	-.09674	-.04441	-.04555	-.02091	1.44366	.00692
1.450	-1.677	-1.28824	-139.31160	-.07750	-.03554	-.04590	-.02105	1.44476	.00578
1.450	-1.213	-1.31616	-128.92540	-.05922	-.02711	-.04750	-.02175	1.44637	.00421
1.450	-759	-1.37145	-114.58340	-.04023	-.01839	-.04983	-.02279	1.44738	.00285
1.450	-304	-1.45827	-96.92082	-.02103	-.00961	-.05271	-.02409	1.44799	.00223
1.450	.206	-1.56247	-77.59784	.00021	.00010	-.05639	-.02577	1.44838	.00220
1.450	.745	-1.64773	-61.16367	.02250	.01030	-.05841	-.02673	1.44677	.00359
GRADIENT		-0.07003	19.02112	.04212	.01944	-.00201	-.00087	.00678	.00215

RUN NO.	1637/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.469	-7.049	-1.25682	-169.00710	-.30972	-.14662	-.04942	-.02340	1.44012	.03955
1.470	-6.543	-1.25773	-168.16710	-.28940	-.13661	-.05010	-.02365	1.44327	.03646
1.469	-6.046	-1.25863	-167.20810	-.26920	-.12653	-.04954	-.02357	1.44625	.03219
1.470	-5.553	-1.26436	-166.09050	-.24778	-.11607	-.04885	-.02320	1.45060	.02848
1.470	-5.062	-1.26467	-164.73500	-.22522	-.10531	-.04885	-.02284	1.45171	.02667
1.470	-4.564	-1.26467	-163.18100	-.20340	-.09500	-.04876	-.02277	1.45263	.02545
1.469	-4.074	-1.26544	-161.27000	-.18232	-.08499	-.04793	-.02235	1.45390	.02357
1.469	-3.584	-1.26709	-158.88320	-.16106	-.07493	-.04631	-.02155	1.45542	.02161
1.470	-3.097	-1.27293	-155.78280	-.13951	-.06478	-.04618	-.02144	1.45846	.01944
1.470	-2.615	-1.28035	-151.77110	-.11809	-.05481	-.04517	-.02096	1.45861	.01896
1.469	-2.134	-1.28719	-146.41220	-.09805	-.04552	-.04555	-.02115	1.45719	.01945
1.469	-1.666	-1.30737	-138.95490	-.07933	-.03681	-.04623	-.02145	1.45799	.01880
1.470	-1.202	-1.33645	-128.52910	-.06079	-.02820	-.04738	-.02198	1.45926	.01803
1.469	-744	-1.38942	-114.14760	-.04171	-.01933	-.05011	-.02323	1.45913	.01758
1.470	-283	-1.47124	-96.48503	-.02215	-.0106	-.05343	-.02476	1.45951	.01737
1.470	.229	-1.56302	-77.20158	-.00050	-.00023	-.05725	-.02652	1.46028	.01705
1.469	.766	-1.64188	-60.84660	.02182	.01011	-.05916	-.02741	1.45931	.01723
GRADIENT		-0.06598	19.01842	.04211	.01963	-.000201	-.00090	.00443	.00140

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM046 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1588/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.492	-7.051	-168.96790	-32734	-15622	-05074
1.492	-6.544	-168.0830	-30491	-14521	-05070
1.492	-6.047	-167.12930	-28513	-13550	-05021
1.492	-5.549	-166.01150	-26414	-12519	-05152
1.492	-5.053	-164.65580	-24319	-11498	-05138
1.492	-4.560	-163.06210	-22165	-10458	-05123
1.491	-4.069	-161.15120	-19989	-09413	-05088
1.492	-3.579	-158.76430	-17871	-08402	-05003
1.492	-3.091	-155.66400	-15584	-07321	-04951
1.492	-2.605	-151.69170	-13407	-06298	-05022
1.492	-2.127	-146.25370	-11222	-05269	-05156
1.492	-1.658	-138.79640	-09073	-04262	-05306
1.492	-1.189	-130.33090	-06922	-03296	-05445
1.492	-0.729	-113.90980	-04761	-02240	-05674
1.492	-0.270	-96.24722	-02576	-01212	-06088
1.491	.244	-76.92422	-00122	-00057	-06559
1.492	.780	-60.60883	-02423	-01140	-06776
GRADIENT	.06176	19.00705	.04605	.02169	.00321

RUN NO.	1604/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.515	-7.051	-168.96780	-37137	-17611	-05809
1.515	-6.539	-168.12760	-34829	-16456	-05868
1.514	-6.041	-167.12910	-32475	-15303	-05984
1.514	-5.548	-166.01140	-30146	-14158	-05892
1.514	-5.057	-164.65590	-27420	-12850	-05728
1.514	-4.559	-163.06210	-24823	-11608	-05635
1.514	-4.069	-161.15110	-22279	-10412	-05730
1.514	-3.577	-158.72470	-19987	-09336	-05853
1.513	-3.091	-155.66390	-17423	-08127	-05984
1.515	-2.608	-151.65210	-14800	-06898	-05926
1.514	-2.126	-146.25360	-12054	-05604	-05936
1.514	-1.656	-138.75670	-09267	-04304	-05978
1.514	-1.192	-128.33090	-06837	-03176	-05977
1.514	-0.731	-113.90980	-04490	-02086	-06108
1.514	-0.269	-96.24721	-02193	-01019	-06450
1.514	.244	-76.92424	.00380	.00176	.06706
1.514	.777	-60.60890	.02919	.01355	.06937
GRADIENT	.06146	19.01325	.05284	.02469	.00205

RUN NO.	1588/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.492	-7.051	-168.96790	-32734	-15622	-05074
1.492	-6.544	-168.0830	-30491	-14521	-05070
1.492	-6.047	-167.12930	-28513	-13550	-05021
1.492	-5.549	-166.01150	-26414	-12519	-05152
1.492	-5.053	-164.65580	-24319	-11498	-05138
1.492	-4.560	-163.06210	-22165	-10458	-05123
1.491	-4.069	-161.15120	-19989	-09413	-05088
1.492	-3.579	-158.76430	-17871	-08402	-05003
1.492	-3.091	-155.66400	-15584	-07321	-04951
1.492	-2.605	-151.69170	-13407	-06298	-05022
1.492	-2.127	-146.25370	-11222	-05269	-05156
1.492	-1.658	-138.79640	-09073	-04262	-05306
1.492	-1.189	-130.33090	-06922	-03296	-05445
1.492	-0.729	-113.90980	-04761	-02240	-05674
1.492	-0.270	-96.24722	-02576	-01212	-06088
1.491	.244	-76.92422	-00122	-00057	-06559
1.492	.780	-60.60883	-02423	-01140	-06776
GRADIENT	.06176	19.00705	.04605	.02169	.00321

RUN NO.	1604/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.515	-7.051	-168.96780	-37137	-17611	-05809
1.515	-6.539	-168.12760	-34829	-16456	-05868
1.514	-6.041	-167.12910	-32475	-15303	-05984
1.514	-5.548	-166.01140	-30146	-14158	-05892
1.514	-5.057	-164.65590	-27420	-12850	-05728
1.514	-4.559	-163.06210	-24823	-11608	-05635
1.514	-4.069	-161.15110	-22279	-10412	-05730
1.514	-3.577	-158.72470	-19987	-09336	-05853
1.513	-3.091	-155.66390	-17423	-08127	-05984
1.515	-2.608	-151.65210	-14800	-06898	-05926
1.514	-2.126	-146.25360	-12054	-05604	-05936
1.514	-1.656	-138.75670	-09267	-04304	-05978
1.514	-1.192	-128.33090	-06837	-03176	-05977
1.514	-0.731	-113.90980	-04490	-02086	-06108
1.514	-0.269	-96.24721	-02193	-01019	-06450
1.514	.244	-76.92424	.00380	.00176	.06706
1.514	.777	-60.60890	.02919	.01355	.06937
GRADIENT	.06146	19.01325	.05284	.02469	.00205

RUN NO.	1588/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.492	-7.051	-168.96790	-32734	-15622	-05074
1.492	-6.544	-168.0830	-30491	-14521	-05070
1.492	-6.047	-167.12930	-28513	-13550	-05021
1.492	-5.549	-166.01150	-26414	-12519	-05152
1.492	-5.053	-164.65580	-24319	-11498	-05138
1.492	-4.560	-163.06210	-22165	-10458	-05123
1.491	-4.069	-161.15120	-19989	-09413	-05088
1.492	-3.579	-158.76430	-17871	-08402	-05003
1.492	-3.091	-155.66400	-15584	-07321	-04951
1.492	-2.605	-151.69170	-13407	-06298	-05022
1.492	-2.127	-146.25370	-11222	-05269	-05156
1.492	-1.658	-138.79640	-09073	-04262	-05306
1.492	-1.189	-130.33090	-06922	-03296	-05445
1.492	-0.729	-113.90980	-04761	-02240	-05674
1.492	-0.270	-96.24722	-02576	-01212	-06088
1.491	.244	-76.92422	-00122	-00057	-06559
1.492	.780	-60.60883	-02423	-01140	-06776
GRADIENT	.06176	19.00705	.04605	.02169	.00321

RUN NO.	1604/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.515	-7.051	-168.96780	-37137	-17611	-05809
1.515	-6.539	-168.12760	-34829	-16456	-05868
1.514	-6.041	-167.12910	-32475	-15303	-05984
1.514	-5.548	-166.01140	-30146	-14158	-05892
1.514	-5.057	-164.65590	-27420	-12850	-05728
1.514	-4.559	-163.06210	-24823	-11608	-05635
1.514	-4.069	-161.15110	-22279	-10412	-05730
1.514	-3.577	-158.72470	-19987	-09336	-05853
1.513	-3.091	-155.66390	-17423	-08127	-05984
1.515	-2.608	-151.65210	-14800	-06898	-05926
1.514	-2.126	-146.25360	-12054	-05604	-05936
1.514	-1.656	-138.75670	-09267	-04304	-05978
1.514	-1.192	-128.33090	-06837	-03176	-05977
1.514	-0.731	-113.90980	-04490	-02086	-06108
1.514	-0.269	-96.24721	-02193	-01019	-06450
1.514	.244	-76.92424	.00380	.00176	.06706
1.514	.777	-60.60890	.02919	.01355	.06937
GRADIENT	.06146	19.01325	.05284	.02469	.00205

RUN NO.	1588/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.492	-7.051	-168.96790	-32734	-15622	-05074
1.492	-6.544	-168.0830	-30491	-14521	-05070
1.492	-6.047	-167.12930	-28513	-13550	-05021
1.492	-5.549	-166.01150	-26414	-12519	-05152
1.492	-5.053	-164.65580	-24319	-11498	-05138
1.492	-4.560	-163.06210	-22165	-10458	-05123
1.491	-4.069	-161.15120	-19989	-09413	-05088
1.492	-3.579	-158.76430	-17871	-08402	-05003
1.492	-3.091	-155.66400	-15584	-07321	-04951
1.492	-2.605	-151.69170	-13407	-06298	-05022
1.492	-2.127	-146.25370	-11222	-05269	-05156
1.492	-1.658	-138.79640	-09073	-04262	-05306
1.492	-1.189	-130.33090	-06922	-03296	-05445
1.492	-0.729	-113.90980	-04761	-02240	-05674
1.492	-0.270	-96.24722	-02576	-01212	-06088
1.491	.244	-76.92422	.00380	.00176	.06706
1.492	.777	-60.60890	.02919	.01355	.06937
GRADIENT	.06146	19.01325	.05284	.02469	.00205

RUN NO.	1604/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.515	-7.051	-168.96780	-37137	-17611	-05809
1.515	-6.539	-168.12760	-34829	-16456	-05868
1.514	-6.041	-167.12910	-32475	-15303	-05984
1.514	-5.548	-166.01140	-30146	-14158	-05892
1.514	-5.057	-164.65590	-27420	-12850	-05728
1.514	-4.559	-163.06210	-24823	-11608	-05635
1.514	-4.069	-161.15110	-22279	-10412	-05730
1.514	-3.577	-158.72470	-19987	-09336	-05853
1.513	-3.091	-155.66390	-17423	-08127	-05984
1.515	-2.608	-151.65210	-14800	-06898	-05926
1.514	-2.126	-146.25360	-12054	-05604	-05936
1.514	-1.656	-138.75670	-09267	-04304	-05978
1.514	-1.192	-128.33090	-06837	-03176	-05977
1.514	-0.731	-113.90980	-04490	-02086	-06108
1.514	-0.269	-96.24721	-02193	-01019	-06450
1.514	.244	-76.92424	.00380	.00176	.06706
1.514	.777	-60.60890	.02919	.01355	.06937
GRADIENT	.06146	19.01325	.05284	.02469	.00205

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 544  
(TCM046) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1619/ O	RN/L =	2.49	GRADIENT	INTERVAL =	- 5.00 /	5.00	BETA	=	- 1.500	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAO	CPALPH	CPBQ	CPBETA	CPBE	CPTD					
1.542	-7.046	-1.26984	-168.96780	-.35246	-.16676	-.06180	-.03066	1.52784	3.51959					
1.543	-6.539	-1.27412	-168.08820	-.31979	-.15105	-.06140	-.02900	1.52960	3.52635					
1.542	-6.048	-1.27093	-167.16880	-.28968	-.13672	-.05989	-.02826	1.53006	3.52813					
1.542	-5.548	-1.27469	-166.01150	-.26039	-.12287	-.05960	-.02812	1.53007	3.52819					
1.542	-5.058	-1.27601	-164.69550	-.23246	-.10966	-.05942	-.02803	1.53028	3.52897					
1.542	-4.560	-1.27827	-163.10190	-.20434	-.09640	-.05868	-.02769	1.52960	3.52634					
1.541	-4.070	-1.27848	-161.19080	-.17495	-.08240	-.05634	-.02654	1.53076	3.53083					
1.542	-3.579	-1.28201	-158.76440	-.14448	-.06798	-.05250	-.02470	1.53207	3.53593					
1.541	-3.091	-1.28731	-155.66400	-.11750	-.05523	-.04801	-.02257	1.53271	3.53841					
1.541	-2.604	-1.29094	-151.65200	-.09562	-.04495	-.04544	-.02136	1.53240	3.53720					
1.541	-2.126	-1.30066	-146.25370	-.07776	-.03658	-.04501	-.02118	1.53192	3.53535					
1.541	-1.657	-1.31865	-138.79630	-.06173	-.02901	-.04541	-.02134	1.53243	3.53730					
1.541	-1.191	-1.34660	-128.33090	-.04481	-.02108	-.04462	-.02099	1.53144	3.53346					
1.541	-0.729	-1.39132	-113.90980	-.02851	-.01341	-.04491	-.02112	1.53141	3.53336					
1.541	-0.268	-1.46897	-96.24722	-.01290	-.00606	-.04686	-.02203	1.53191	3.53528					
1.541	.244	-1.56107	-76.96382	.00394	.00185	-.04889	-.02297	1.53260	3.53795					
1.541	.779	-1.63603	-60.64842	.02172	.01021	-.04990	-.02345	1.53212	3.53610					
	GRADIENT	-.06193	19.00676	.04104	.01934	.00161	.00077	.00026	.00097					

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM047 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.		RN/L =		GRADIENT INTERVAL =		BETA		= -1.000		PHI		= 180.000	
		1573/ 0	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBQ	CPBETA	MPROBE	CPM	CPTD		
.601	-7.040	-.71634	-173.14560	-.30142	-.06071	-.03035	-.00611	.57782	1.25387	-.01778					
.600	-6.534	-.71514	-172.62520	-.28114	-.05633	-.02957	-.00593	.58050	1.25643	-.01495					
.600	-6.039	-.71478	-172.02560	-.25978	-.05200	-.02821	-.00565	.58374	1.25954	-.01278					
.601	-5.542	-.72006	-171.26740	-.23827	-.04769	-.02719	-.00544	.58695	1.26265	-.01086					
.600	-5.046	-.71883	-170.42950	-.21759	-.04336	-.02766	-.00551	.58822	1.26388	-.00906					
.601	-4.554	-.72007	-169.39320	-.19732	-.03934	-.02736	-.00546	.59160	1.26719	-.00717					
.600	-4.061	-.72132	-168.11870	-.17676	-.03517	-.02713	-.00540	.59211	1.26769	-.00638					
.600	-3.565	-.72318	-166.48710	-.15695	-.03118	-.02728	-.00542	.59425	1.26980	-.00472					
.601	-3.079	-.72374	-164.41900	-.13495	-.02684	-.02647	-.00526	.59606	1.27158	-.00389					
.600	-2.593	-.72865	-161.55760	-.11421	-.02260	-.02602	-.00515	.59581	1.27134	-.00290					
.600	-2.111	-.73255	-157.58590	-.09439	-.01868	-.02545	-.00504	.59741	1.27293	-.00194					
.600	-1.635	-.74027	-151.59270	-.07369	-.01460	-.02478	-.00491	.59848	1.27399	-.00150					
.601	-1.184	-.76336	-142.07420	-.05485	-.01086	-.02470	-.00489	.59934	1.27485	-.00102					
.600	-1.750	-.81425	-126.14310	-.03715	-.00735	-.02549	-.00505	.59909	1.27460	-.00101					
.601	-.330	-.92595	-101.98610	-.02008	-.00398	-.03042	-.00602	.59914	1.27465	-.00107					
.600	.229	-.1.10144	-70.90875	-.00664	-.00013	-.03730	-.00738	.59906	1.27457	-.00081					
.600	.751	-.1.20112	-51.78479	-.02160	-.00428	-.04041	-.00800	.59943	1.27494	-.00076					
	GRADIENT	-.07866	21.11599	.04156	.00827	-.00182	-.00035	.00155	.00153						
MACH	ALPHA	RUN NO.		RN/L =		GRADIENT INTERVAL =		BETA		= -5.00/		5.00/		CPTD	
		1463/ 0	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBQ	CPBETA	MPROBE	CPM	CPTD		
.800	-7.034	-.79570	-172.83010	-.28947	-.08706	-.03079	-.00926	.77604	1.48893	-.02359					
.800	-6.520	-.79566	-172.26990	-.26914	-.08074	-.03026	-.00908	.77958	1.49405	-.02046					
.800	-6.027	-.79664	-171.63050	-.24921	-.07451	-.02932	-.00877	.78217	1.49783	-.01756					
.800	-5.527	-.80176	-170.83240	-.22865	-.06823	-.02902	-.00866	.78498	1.50194	-.01509					
.800	-5.033	-.79737	-169.99420	-.20913	-.06222	-.02833	-.00843	.78711	1.50507	-.01260					
.800	-4.537	-.80104	-168.87840	-.18917	-.05620	-.02847	-.00846	.78940	1.50846	-.01067					
.800	-4.040	-.79949	-167.56400	-.16906	-.05013	-.02899	-.00860	.79121	1.51115	-.00881					
.800	-3.545	-.80209	-165.85290	-.14899	-.04410	-.02854	-.00845	.79275	1.51345	-.00714					
.800	-3.053	-.80291	-163.66570	-.12863	-.03803	-.02845	-.00841	.79424	1.51567	-.00582					
.800	-2.562	-.80289	-160.72470	-.10864	-.03208	-.02796	-.00826	.79544	1.51748	-.00465					
.800	-2.078	-.80868	-156.51510	-.08916	-.02630	-.02731	-.00806	.79634	1.51883	-.00366					
.800	-1.602	-.81511	-150.32390	-.07018	-.02070	-.02661	-.00785	.79725	1.52020	-.00300					
.800	-1.135	-.82824	-140.44900	-.05155	-.01519	-.02678	-.00789	.79770	1.52087	-.00251					
.800	-689	-.86663	-124.08300	-.03385	-.00997	-.02715	-.00800	.79805	1.52139	-.00199					
.800	-253	-.95421	-99.57042	-.01736	-.00511	-.03054	-.00899	.79799	1.52131	-.00177					
.800	.258	-1.07781	-71.22481	-.00144	-.00042	-.03578	-.01053	.79821	1.52164	-.00161					
.800	.818	-1.15766	-50.16090	-.02369	-.00697	-.03801	-.01119	.79841	1.52194	-.00153					
	GRADIENT	-.05745	21.10140	.03981	.01180	-.00123	-.00035	.00165	.00247	.00167					

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 546  
 (TCM047) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1497/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= -1.000	PHI	= 180.000	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA				
.900	-7.028	-.78313	-172.86950	-.27828	-.09562	-.02949	-.01013	.87700	1.65003	-.02496	
.900	-6.518	-.78355	-172.30930	-.25862	-.08851	-.02958	-.01012	.87798	1.65492	-.02147	
.901	-6.023	-.78493	-171.66990	-.23899	-.08168	-.02899	-.00991	.88354	1.66158	-.01863	
.900	-5.527	-.78663	-170.91140	-.21997	-.07491	-.02802	-.00954	.88554	1.66515	-.01575	
.900	-5.031	-.78620	-170.0370	-.20104	-.06826	-.02749	-.00933	.88751	1.66867	-.01321	
.900	-4.534	-.78671	-168.95750	-.18185	-.06165	-.02711	-.00919	.88995	1.67306	-.01109	
.900	-4.040	-.78687	-167.64320	-.16235	-.05494	-.02710	-.00917	.89160	1.67603	-.00925	
.900	-3.545	-.78713	-165.97170	-.14278	-.04823	-.02683	-.00906	.89330	1.67909	-.00747	
.900	-3.052	-.78825	-163.78450	-.12314	-.04152	-.02679	-.00903	.89454	1.68135	-.00586	
.900	-2.564	-.79079	-160.84370	-.10423	-.03511	-.02628	-.00885	.89558	1.68323	-.00478	
.900	-2.081	-.79381	-156.71340	-.08568	-.02883	-.02585	-.00870	.89635	1.68464	-.00375	
.900	-1.604	-.80248	-150.48250	-.06747	-.02268	-.02522	-.00848	.89689	1.68562	-.00297	
.900	-1.142	-.81869	-140.64720	-.04926	-.01655	-.02549	-.00857	.89779	1.68726	-.00239	
.900	-6.97	-.85871	-124.32070	-.03242	-.01089	-.02602	-.00874	.89805	1.68773	-.00189	
.900	-264	-.95003	-99.84766	-.01660	-.00557	-.02931	-.00984	.89846	1.68848	-.00170	
.900	295	-1.08417	-69.08707	-.00361	-.00121	-.03439	-.01155	.89841	1.68839	-.00156	
.900	811	-1.16299	-50.24019	-.02294	-.00770	-.03652	-.01226	.89852	1.68859	-.00142	
	GRADIENT	-.06122	21.24805	.03836	.01298	-.00131	-.00042	.00158	.00286	.00178	
	RUN NO.	1480/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA				
1.100	-7.018	-.93012	-172.15820	-.25086	-.10219	-.03057	-.01245	.07877	2.07886	-.02586	
1.100	-6.500	-.92309	-171.59730	-.23305	-.09463	-.03050	-.01238	.08154	2.08581	-.02247	
1.100	-6.007	-.92719	-170.87840	-.21533	-.08716	-.03083	-.01248	.08419	2.09251	-.01923	
1.100	-5.504	-.92512	-170.07980	-.19790	-.07989	-.03028	-.01222	.08650	2.09834	-.01653	
1.100	-5.009	-.92869	-169.08290	-.18064	-.07272	-.02914	-.01173	.08850	2.10341	-.01383	
1.100	-4.502	-.93569	-167.96760	-.16299	-.06547	-.02975	-.01195	.09028	2.10794	-.01161	
1.100	-4.011	-.92954	-166.65300	-.14552	-.05834	-.02886	-.01157	.09180	2.11180	-.00973	
1.100	-3.512	-.92371	-164.90160	-.12752	-.05103	-.02812	-.01125	.09364	2.11650	-.00774	
1.100	-3.012	-.92339	-162.55540	-.10945	-.04372	-.02772	-.01107	.09437	2.11838	-.00627	
1.100	-2.518	-.92242	-159.37640	-.09195	-.03669	-.02741	-.01094	.09566	2.12168	-.00494	
1.100	-2.028	-.92392	-154.92880	-.07509	-.02994	-.02684	-.01070	.09703	2.12521	-.00386	
1.100	-1.542	-.92821	-148.22240	-.05825	-.02320	-.02638	-.01051	.09727	2.12581	-.00310	
1.100	-1.059	-.93054	-137.79330	-.04164	-.01657	-.02623	-.01044	.09761	2.12668	-.00239	
1.100	-5.88	-.94111	-120.75510	-.02542	-.01011	-.02619	-.01042	.09788	2.12738	-.00205	
1.100	-1.136	-.98161	-95.88741	-.01035	-.00412	-.02738	-.01089	.09837	2.12865	-.00184	
1.100	.432	-1.03144	-65.12708	-.00799	.00318	-.02919	-.01161	.09856	2.12915	-.00149	
1.100	.927	-1.08114	-47.26982	-.02452	-.00975	-.03015	-.01199	.09886	2.12991	-.00136	
	GRADIENT	-.02172	21.42504	.03458	.01386	.00006	.00005	.00151	.00387	.00184	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM047 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1520/ O	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = -1.000	PHI = 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.250	-7.027	-.83232	-172.63240	-.25987	-.11412	-.02784
1.250	-6.514	-.82975	-172.07200	-.24119	-.10551	-.02846
1.250	-6.016	-.83245	-171.39280	-.22339	-.09739	-.02738
1.250	-5.518	-.83276	-170.63420	-.20443	-.08893	-.02730
1.250	-5.019	-.83089	-169.75640	-.18619	-.08082	-.02623
1.250	-4.525	-.83287	-168.64060	-.16843	-.07295	-.02614
1.250	-4.029	-.83438	-167.28660	-.15077	-.06515	-.02524
1.250	-3.531	-.83072	-165.61490	-.13218	-.05701	-.02477
1.250	-3.040	-.83516	-163.34840	-.11387	-.04902	-.02496
1.250	-2.551	-.83618	-160.36790	-.09623	-.04137	-.02467
1.250	-2.063	-.83918	-156.11860	-.07878	-.03383	-.02463
1.250	-1.582	-.84294	-149.80840	-.06195	-.02659	-.02453
1.250	-1.113	-.85436	-139.77520	-.04538	-.01946	-.02463
1.250	-660	-.88323	-123.17170	-.02942	-.01261	-.02507
1.250	-222	-.95466	-98.58032	-.01404	-.00602	-.02718
1.250	.291	-1.07265	-70.23476	-.00351	-.00150	-.03117
1.250	.848	-1.14149	-49.44797	-.02316	-.00992	-.03302
	GRADIENT	-.04861	21.16299	.03565	.01541	-.00106
					-.00043	.00164

	RUN NO.	1536/ O	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = -1.000	PHI = 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.400	-7.024	-.84520	-172.59310	-.28816	-.13323	-.02504
1.400	-6.511	-.84710	-171.99310	-.26782	-.12342	-.02545
1.400	-6.014	-.84507	-171.35340	-.24773	-.11378	-.02562
1.400	-5.515	-.84831	-170.55520	-.22759	-.10427	-.02464
1.400	-5.021	-.85072	-169.63790	-.20832	-.09513	-.02457
1.400	-4.522	-.84839	-168.56150	-.18897	-.08611	-.02470
1.400	-4.027	-.84544	-167.24700	-.16909	-.07684	-.02364
1.400	-3.528	-.84622	-165.49600	-.14823	-.06725	-.02326
1.400	-3.032	-.84910	-163.18970	-.12720	-.05762	-.02312
1.400	-2.542	-.84816	-160.20920	-.10680	-.04834	-.02322
1.399	-2.054	-.85015	-155.92020	-.08796	-.03978	-.02269
1.400	-1.576	-.85572	-149.53080	-.06984	-.03154	-.02298
1.400	-1.106	-.86671	-139.37880	-.05172	-.02332	-.02358
1.400	-649	-.89489	-122.61710	-.03347	-.01508	-.02425
1.400	-203	-.96252	-97.78839	-.01606	-.00724	-.02632
1.400	.308	-1.06509	-69.60123	.00335	.00151	-.03041
1.400	.860	-1.12742	-48.97279	.02491	-.01123	-.03255
	GRADIENT	-.04447	21.23646	.03968	.01804	-.00127
					-.00055	.00178

## PARAMETRIC DATA

RUN NO.	1554/ O	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	-1.000	PHI	=	180.000
<b>MACH</b>	<b>BETA</b>	<b>PHI</b>	<b>CPAO</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBETA</b>	<b>CPM</b>	<b>MPROBE</b>	<b>CPTD</b>				
1.449	-7.037	-173.06640	-30202	-14174	-02637	-01237	1.42368	3.13292	-02946				
1.450	-6.525	-172.46690	-28142	-13160	-02724	-01274	1.42734	3.14599	-02563				
1.450	-6.029	-171.86710	-26025	-12144	-02698	-01259	1.42983	3.15489	-02332				
1.450	-5.532	-171.14830	-23930	-11129	-02717	-01264	1.43241	3.16414	-02002				
1.450	-5.035	-170.31040	-21930	-10173	-02648	-01228	1.43466	3.17224	-01737				
1.450	-4.542	-169.23460	-19983	-09236	-02606	-01205	1.43765	3.18302	-01373				
1.450	-4.048	-167.96010	-17912	-08259	-02537	-01170	1.43979	3.19074	-01134				
1.450	-3.554	-166.36800	-15774	-07261	-02487	-01145	1.44125	3.19600	-00961				
1.451	-3.066	-164.22060	-13557	-06232	-02474	-01137	1.44445	3.20761	-00783				
1.449	-2.580	-161.35920	-11442	-05256	-02451	-01126	1.44229	3.19979	-00777				
1.450	-2.099	-157.30480	-09489	-04356	-02425	-01113	1.44435	3.20723	-00661				
1.450	-1.622	-151.27540	-07643	-03500	-02461	-01127	1.44607	3.21348	-00430				
1.450	-1.166	-141.63810	-05834	-02667	-02559	-01170	1.44806	3.22069	-00242				
1.450	-735	-125.62810	-03945	-01799	-02677	-01221	1.44982	3.22712	-00007				
1.450	-314	-101.35250	-02176	-00992	-03058	-01394	1.45057	3.22984	.00043				
1.449	.246	-70.39394	-00165	-00075	-03679	-01677	1.44873	3.22316	-00011				
1.450	.770	-51.30952	-02317	.01058	.04018	.01834	1.44881	3.22342	-00126				
GRADIENT		-07452	21.18352	.04187	.01932	.00229	.00101	.00230	.00834	.00230	.00112	.00135	.00493

RUN NO.	1638/ O	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	-1.000	PHI	=	180.000
<b>MACH</b>	<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBETA</b>	<b>CPM</b>	<b>MPROBE</b>	<b>CPTD</b>				
1.470	-7.033	-172.98720	-30806	-14583	-02742	-01298	1.44070	3.19402	-03909				
1.471	-6.526	-172.38780	-28185	-13600	-02747	-01297	1.44487	3.20913	-03556				
1.470	-6.029	-171.74840	-26784	-12589	-02706	-01272	1.44766	3.21924	-03143				
1.471	-5.533	-171.02960	-24617	-11531	-02764	-01295	1.45101	3.23146	-02791				
1.470	-5.035	-170.15200	-22356	-10459	-02701	-01263	1.45114	3.23194	-02675				
1.470	-4.542	-169.11590	-20224	-09447	-02602	-01215	1.45330	3.23978	-02502				
1.470	-4.043	-167.84120	-18096	-08438	-02498	-01165	1.45438	3.24374	-02319				
1.469	-3.552	-166.16980	-15902	-07400	-02503	-01165	1.45546	3.24768	-02122				
1.470	-3.065	-164.02240	-13713	-06370	-02462	-01144	1.45788	3.25652	-01934				
1.470	-2.573	-161.12120	-11571	-05376	-02401	-01116	1.45789	3.25657	-01939				
1.470	-2.095	-157.03070	-09704	-04507	-02361	-01096	1.45810	3.25734	-01904				
1.470	-1.621	-150.91870	-07827	-03631	-02403	-01115	1.45905	3.26082	-01795				
1.471	-1.158	-141.20210	-05963	-02766	-02499	-01159	1.45997	3.26421	-01747				
1.470	-719	-125.03380	-04143	-01920	-02699	-01251	1.45998	3.26423	-01687				
1.470	-293	-100.63970	-02303	-01067	-03150	-01460	1.45979	3.26355	-01673				
1.471	.215	-72.29405	-00121	-00056	-03766	-01744	1.46100	3.26799	-01644				
1.484	.782	-51.07181	-02236	.01056	.03999	.01889	1.46016	3.26489	-01674				
GRADIENT		-06910	21.07949	.04191	.01956	.00240	.00112	.00135	.00493	.00149	.00112	.00135	.00493

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCMO47) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1589/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPTD	
1.492	-7.036	-76284	-172.94800	-32665	-15585	-02749	-01312	1.45990	3.26395	-04516
1.492	-6.524	-76833	-172.34840	-30407	-14482	-02805	-01336	1.46153	3.26993	-04328
1.492	-6.022	-76849	-171.70890	-28483	-13535	-02799	-01330	1.46361	3.27758	-04105
1.492	-5.531	-76715	-170.99010	-26390	-12510	-02722	-01290	1.46653	3.28833	-03826
1.492	-5.033	-77117	-170.07290	-24282	-11482	-02736	-01294	1.46860	3.29596	-03574
1.492	-4.534	-77331	-168.99690	-22073	-10414	-02678	-01264	1.47009	3.30147	-03353
1.493	-4.045	-77243	-167.72240	-19881	-09362	-02696	-01270	1.47283	3.31159	-03121
1.492	-3.550	-77149	-166.09060	-17670	-08305	-02646	-01243	1.47439	3.31740	-02925
1.492	-3.056	-77374	-163.90340	-15402	-07234	-02665	-01251	1.47459	3.31815	-02878
1.492	-2.573	-77875	-160.96270	-13217	-06206	-02656	-01247	1.47438	3.31737	-02857
1.492	-2.086	-78022	-156.87200	-11023	-05176	-02718	-01276	1.47493	3.31939	-02834
1.492	-1.615	-79077	-150.72040	-08927	-04195	-02824	-01327	1.47397	3.31581	-02912
1.492	-1.149	-80550	-140.92470	-06796	-03196	-02918	-01372	1.47380	3.31518	-03001
1.492	-7.111	-85067	-124.67730	-04724	-02223	-03111	-01464	1.47280	3.31151	-03060
1.492	-2.278	-94223	-100.24370	-02657	-01250	-03648	-01717	1.47288	3.31177	-03090
1.492	.231	-1.08432	-71.85846	-00170	-00080	-04332	-02039	1.47232	3.30973	-03134
1.492	.796	-1.17446	-50.71538	-02530	-01191	-04671	-02200	1.47198	3.30845	-03164
	GRADIENT	-.06550	21.10490	.04600	.02166	-.00342	-.00161	-.00004	-.00004	
	RUN NO.	1605/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPTD	
1.514	-7.040	-76835	-172.90860	-37124	-17592	-03215	-01523	1.49297	3.38676	-03570
1.515	-6.523	-76781	-172.34840	-34778	-16420	-03249	-01534	1.49700	3.40194	-03191
1.514	-6.027	-76906	-171.70900	-32472	-15289	-03282	-01545	1.49884	3.40890	-02930
1.514	-5.530	-76690	-170.99000	-29975	-14065	-03100	-01455	1.50123	3.41792	-02626
1.514	-5.033	-77073	-170.7290	-27165	-12707	-03023	-01414	1.50471	3.43112	-02279
1.514	-4.538	-77454	-168.99700	-24584	-11485	-03026	-01413	1.50506	3.43245	-02171
1.514	-4.044	-77377	-167.68260	-22156	-10355	-03114	-01456	1.50496	3.43205	-02207
1.514	-3.554	-77365	-166.05090	-19898	-09287	-03178	-01483	1.50673	3.43879	-02059
1.515	-3.060	-77348	-163.90340	-17135	-07986	-03222	-01502	1.50868	3.44618	-01895
1.514	-2.573	-77778	-160.96260	-14341	-06674	-03270	-01522	1.50921	3.44819	-01757
1.514	-2.084	-78086	-156.83230	-11639	-05407	-03252	-01511	1.51067	3.45376	-01575
1.514	-1.614	-79125	-150.68080	-0878	-04123	-03200	-01486	1.51126	3.45600	-01543
1.514	-1.153	-80770	-140.92470	-06486	-03014	-03249	-01510	1.50996	3.45107	-01629
1.514	-.709	-85050	-124.63770	-04330	-02013	-03522	-01638	1.50960	3.44967	-01659
1.514	-.281	-94563	-100.28330	-02262	-01052	-04042	-01880	1.50986	3.45066	-01633
1.514	.232	-1.08869	-71.85844	.00186	.00086	-.04693	-.02182	1.51030	3.45236	-01629
1.515	.799	-1.17875	-50.71532	.02848	.01323	-.04938	-.02294	1.51174	3.45783	-01537
	GRADIENT	-.06558	21.08189	.05246	.02450	-.00132	-.00111	-.00424	-.00123	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 550

(TCM047) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1620/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA = -1.000	PHI = 180 000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD
1.541	-7.035	-.76812	-172.90860	-.34950	-.16488	-.03804	-.01795	3.52135
1.541	-6.523	-.76811	-172.34840	-.31647	-.14914	-.03575	-.01685	3.52832
1.541	-6.027	-.76934	-171.70900	-.28553	-.13447	-.03432	-.01616	3.52999
1.541	-5.530	-.77161	-170.95060	-.25645	-.12077	-.03384	-.01593	3.52763
1.541	-5.038	-.77263	-170.07300	-.22871	-.10771	-.03432	-.01616	3.52980
1.540	-4.534	-.77177	-169.03660	-.20029	-.09430	-.03365	-.01585	3.52983
1.541	-4.040	-.77220	-167.72240	-.17002	-.08000	-.03150	-.01482	3.53067
1.541	-3.549	-.77193	-166.09060	-.13894	-.06532	-.02930	-.01378	3.53188
1.541	-3.056	-.77251	-163.94310	-.11357	-.05336	-.02672	-.01255	3.53291
1.541	-2.574	-.77793	-161.00240	-.09306	-.04373	-.02650	-.01245	3.53207
1.541	-2.090	-.78260	-156.87210	-.07718	-.03630	-.02632	-.01238	3.53171
1.541	-1.614	-.79065	-150.72040	-.05970	-.02810	-.02591	-.01219	3.53089
1.541	-1.149	-.80440	-140.96430	-.04313	-.02031	-.02575	-.01213	3.53046
1.542	-7.10	-.85005	-124.71690	-.02834	-.01333	-.02593	-.01220	3.53185
1.541	-.280	-.94620	-100.28330	-.01377	-.00648	-.02917	-.01372	3.53202
1.542	.231	-1.08355	-.71.89804	-.00320	-.00151	-.03289	-.01547	3.53503
1.541	.796	-1.17530	-.50.75499	.02137	.01005	-.03473	-.01634	3.53188
	GRADIENT	-.06542	21.11213	.04011	.01887	-.00012	-.00005	.00066
							-.00017	.00011

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM048) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1574/ O	RN/L =	2.50	GRADIENT	INTERVAL	=	-5.00/	5.00	BETA	=	- .500	PHI	=	180.000
<b>ALPHA</b>															
MACH	.600	-7.023	-177.16760	-30078	-06041	-00789	-	.57750	.1.25358	-	.01726				
	.599	-6.514	-176.96720	-27863	-05573	-00704	-	.58061	.1.25654	-	.01447				
	.599	-6.011	-176.68750	-25794	-05152	-00713	-	.58320	.1.25902	-	.01261				
	.600	-5.513	-176.36810	-23689	-04723	-00571	-	.58677	.1.26247	-	.01005				
	.601	-5.021	-176.04840	-21606	-04315	-00508	-	.58920	.1.26484	-	.00897				
	.600	-4.523	-175.60970	-19615	-03904	-00557	-	.59055	.1.26616	-	.00738				
	.600	-4.026	-175.05190	-17537	-03490	-00536	-	.59294	.1.26850	-	.00591				
	.600	-3.528	-174.33510	-15427	-03063	-00545	-	.59463	.1.27017	-	.00441				
	.600	-3.030	-173.41970	-13283	-02634	-00518	-	.59595	.1.27148	-	.00332				
	.601	-2.537	-172.10720	-11184	-02220	-00491	-	.59701	.1.27253	-	.00293				
	.600	-2.049	-170.27850	-9131	-01807	-00397	-	.59782	.1.27333	-	.00168				
	.601	-1.561	-167.29850	-7033	-01395	-00295	-	.59904	.1.27454	-	.00147				
	.601	-1.088	-161.81890	-5003	-00992	-00231	-	.59902	.1.27452	-	.00136				
	.600	-654	-23658	-149.67850	-03330	-00659	-	.59943	.1.27454	-	.00101				
	.600	-310	-32733	-117.14760	-02047	-00405	-	.59946	.1.27496	-	.00075				
	.601	-248	-66529	-57.37181	-00056	-00011	-	.60216	-	.00399	.59981	.1.27531	-	.00055	
	.601	.828	-75791	-34.24951	.02359	.00468	-	.60233	-	.00463	.59977	.1.27527	-	.00100	
		GRADIENT	-0.7991	23.04542	.04132	.00822	-	.00224	-	.00044	.00162	.00118			
	RUN NO.	1464/ O	RN/L =	2.49	GRADIENT	INTERVAL	=	-5.00/	5.00	BETA	=	- .500	PHI	=	180.000
<b>ALPHA</b>															
MACH	.800	-7.018	-176.81260	-28750	-08647	-01102	-	.77656	.1.483968	-	.02332				
	.800	-6.507	-176.57230	-26799	-08033	-00979	-	.77965	.1.494416	-	.02008				
	.800	-6.006	-176.29230	-24785	-07408	-00948	-	.78225	.1.49794	-	.01740				
	.800	-5.505	-175.97250	-22768	-06790	-00867	-	.78524	.1.50232	-	.01468				
	.800	-5.010	-175.57340	-20796	-06186	-00867	-	.78774	.1.50601	-	.01217				
	.800	-4.515	-175.09480	-18814	-05586	-00759	-	.78963	.1.50880	-	.01024				
	.800	-4.014	-174.45730	-16793	-04979	-00803	-	.79167	.1.51184	-	.00849				
	.800	-3.518	-29556	-173.70060	-14759	-04366	-00748	-	.79306	.1.51391	-	.00674			
	.800	-3.022	-29611	-172.66600	-12735	-03763	-00749	-	.79459	.1.51620	-	.00542			
	.800	-2.530	-29728	-171.23420	-10704	-03158	-00771	-	.79549	.1.51754	-	.00423			
	.800	-2.033	-29622	-169.16710	-08735	-02575	-00697	-	.79631	.1.51877	-	.00338			
	.800	-1.549	-29869	-165.83000	-06756	-01991	-00649	-	.79733	.1.52032	-	.00264			
	.800	-1.072	-29976	-159.83500	-04809	-01417	-00586	-	.79808	.1.52144	-	.00216			
	.800	-620	-30802	-146.50660	-03192	-00940	-00510	-	.79839	.1.52191	-	.00172			
	.802	-218	-44312	-105.90270	-01678	-00496	-01041	-	.79894	.1.52273	-	.00281			
	.800	.329	-63412	-53.53152	.00340	.00100	-01875	-	.80116	.1.52609	-	.00083			
	.800	.886	-69473	-31.91336	.02545	.00749	-02014	-	.79777	.1.52097	-	.00211			
		GRADIENT	-0.6156	23.80669	.03959	.01173	-00171	-	.00176	.00264		.00164			

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 552  
( TCM048 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1498/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	- .500	PHI	=	180.000
<b>MACH</b>							<b>CPTD</b>					
ALPHA							CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM
.900	-7.016	-.28159	-176.89150	-.27711	-.09514	-.01059						
.900	-6.503	-.28086	-176.65120	-.25733	-.08809	-.01005						
.900	-6.006	-.28110	-176.37130	-.23813	-.08124	-.00940						
.900	-5.504	-.28388	-176.01200	-.21878	-.07449	-.00809						
.900	-5.012	-.28480	-175.61300	-.19976	-.06783	-.00781						
.900	-4.510	-.28119	-175.17400	-.18077	-.06127	-.00698						
.900	-4.012	-.28122	-174.57620	-.16129	-.05456	-.00680						
.900	-3.520	-.28421	-173.78000	-.14154	-.04781	-.00702						
.900	-3.017	-.28239	-172.78490	-.12183	-.04106	-.00737						
.901	-2.524	-.28285	-171.39290	-.10266	-.03462	-.00650						
.900	-2.031	-.28198	-169.36560	-.08368	-.02816	-.00640						
.900	-1.547	-.28440	-166.06820	-.06469	-.02176	-.00584						
.900	-1.070	-.28532	-160.15230	-.04651	-.01562	-.00537						
.900	-623	-.29578	-146.98230	-.03034	-.01018	-.00516						
.900	-259	-.37602	-112.83140	-.01709	-.00574	-.00763						
.900	.313	-.64076	-54.36290	.00328	.00110	.01767						
.900	.881	-.69969	-31.87381	.02455	.00824	.01932						
	GRADIENT	-.06209	23.50734	.03813	.01290	-.00162						
						-.00054						
<b>MACH</b>							<b>CPTD</b>					
ALPHA							CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM
1. 100	-7.012	-.42327	-176.21950	-.25150	-.10243	-.01387						
1. 100	-6.497	-.42208	-175.89960	-.23366	-.09488	-.01320						
1. 100	-5.998	-.42286	-175.57950	-.21610	-.08747	-.01342						
1. 100	-5.499	-.42644	-175.14060	-.19886	-.08026	-.01252						
1. 100	-5.005	-.42374	-174.70150	-.18160	-.07312	-.01148						
1. 100	-4.500	-.43313	-174.10420	-.16414	-.06593	-.01196						
1. 100	-4.001	-.42291	-173.54560	-.14641	-.05870	-.01091						
1. 100	-3.506	-.42352	-172.66960	-.12838	-.05136	-.01040						
1. 100	-3.005	-.42313	-171.47580	-.11043	-.04411	-.01015						
1. 100	-2.509	-.42433	-169.76590	-.09280	-.03702	-.01012						
1. 100	-2.010	-.42191	-167.34140	-.07575	-.03019	-.01000						
1. 100	-1.518	-.41980	-163.44880	-.05873	-.02339	-.00995						
1. 100	-1.025	-.41788	-156.38340	-.04208	-.01675	-.00899						
1. 100	-571	-.43569	-141.27420	-.02675	-.01064	-.00891						
1. 100	-102	-.48970	-98.06369	-.01141	-.00454	-.01127						
1. 100	.440	-.56446	-47.75131	-.00619	-.0246	-.01324						
1. 100	.966	-.58034	-28.07283	-.02372	-.00943	-.01332						
	GRADIENT	-.02412	24.51356	.03436	.01377	-.00023						
						-.00008						

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM048) (04 OCT 91)

PARAMETRIC DATA									
RUN NO.		1521/0		RN/L = 2.50		GRADIENT INTERVAL = -5.00/ 5.00		BETA = - .500 PHI = 180.000	
MACH	ALPHA	BETA	PHI	CPOQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.250	-7.018	-.32970	-176.65430	-.25868	-.11354	-.00913	-.00401	1.22802	2.49020
1.250	-6.503	-.33068	-176.37420	-.24012	-.10501	-.00909	-.00397	1.23144	2.50046
1.250	-6.004	-.32827	-176.09410	-.22219	-.09687	-.00967	-.00422	1.23446	2.50954
1.250	-5.504	-.32988	-175.73470	-.20347	-.08848	-.00917	-.00399	1.23670	2.51630
1.250	-5.005	-.33241	-175.29600	-.18544	-.08047	-.00822	-.00357	1.23780	2.51964
1.250	-4.505	-.33064	-174.81730	-.16771	-.07262	-.00798	-.00346	1.23947	2.52468
1.250	-4.012	-.32987	-174.21950	-.14980	-.06471	-.00696	-.00300	1.24134	2.53036
1.250	-3.513	-.32960	-173.42310	-.13108	-.05650	-.00732	-.00315	1.24363	2.53733
1.250	-3.014	-.33009	-172.34860	-.11259	-.04846	-.00723	-.00311	1.24457	2.54017
1.250	-2.520	-.32947	-170.91680	-.09471	-.04071	-.00666	-.00286	1.24540	2.54271
1.250	-2.024	-.32858	-168.77030	-.07747	-.03327	-.00655	-.00281	1.24709	2.54788
1.250	-1.536	-.32933	-165.31410	-.06050	-.02595	-.00652	-.00280	1.24774	2.54984
1.250	-1.055	-.32681	-159.04140	-.04353	-.01866	-.00585	-.00251	1.24794	2.55045
1.250	-604	-.33652	-145.11900	-.02772	-.01188	-.00552	-.00236	1.24833	2.55167
1.249	-192	-.45768	-104.04190	-.01351	-.00579	-.00964	-.00413	1.24824	2.55137
1.250	.354	-.61536	-52.18546	.00531	.00228	-.01499	-.00642	1.24876	2.55296
1.250	.910	-.66519	-30.80473	.02463	.01055	-.01629	-.00698	1.24871	2.55282
	GRADIENT	-.05147	23.98317	.03545	.01531	-.00121	-.00051	.00164	.00500
RUN NO. 1537/0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00									
MACH	ALPHA	BETA	PHI	CPOQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.399	-7.017	-.34318	-176.61500	-.28667	-.13250	-.00581	-.00269	1.37601	2.96610
1.400	-6.496	-.34351	-176.33480	-.26640	-.12277	-.00551	-.00254	1.37869	2.97532
1.400	-5.997	-.34523	-176.01510	-.24674	-.11329	-.00485	-.00223	1.38219	2.98735
1.400	-5.497	-.34197	-175.69530	-.22653	-.10376	-.00482	-.00221	1.38450	2.99535
1.400	-5.009	-.34733	-175.25670	-.20765	-.09481	-.00451	-.00206	1.38711	3.00436
1.400	-4.505	-.34653	-174.73820	-.18791	-.08561	-.00386	-.00176	1.38937	3.01218
1.399	-4.011	-.34591	-174.10060	-.16808	-.07633	-.00379	-.00172	1.39131	3.01892
1.400	-3.512	-.34697	-173.26450	-.14665	-.06653	-.00306	-.00139	1.39307	3.02505
1.400	-3.013	-.34400	-172.22960	-.12571	-.05693	-.00310	-.00140	1.39396	3.02816
1.400	-2.518	-.34441	-170.71830	-.10553	-.04776	-.00307	-.00139	1.39510	3.0312
1.400	-2.022	-.34422	-168.49240	-.08678	-.03925	-.00312	-.00141	1.39544	3.03332
1.400	-1.530	-.34251	-164.99650	-.06841	-.03087	-.00313	-.00141	1.39771	3.04123
1.400	-1.053	-.34431	-158.56530	-.04961	-.02237	-.00282	-.00127	1.39868	3.04463
1.400	-595	-.34902	-144.40540	-.03166	-.01426	-.00260	-.00117	1.39880	3.04505
1.400	-177	-.46606	-102.93330	-.01536	-.00692	-.00680	-.00307	1.39842	3.04372
1.400	.373	-.61266	-51.43321	.00544	.00245	-.01244	-.00560	1.39905	3.04593
1.400	.918	-.64837	-30.17125	.02646	.01192	-.01383	-.00623	1.39916	3.04629
	GRADIENT	-.04710	24.09063	.03942	.01791	-.00151	-.00068	.00631	.00204

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 554

(TCM048) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1555/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.450	-7.016	-.22867	-177.08830	-.30064	-.14102	-.00518	-.00243	1.42519	3.13829	-.02865
1.450	-6.507	-.23392	-176.80880	-.28014	-.13096	-.00559	-.00261	1.42803	3.14846	-.02524
1.449	-6.008	-.23109	-176.56860	-.25919	-.12080	-.00616	-.00287	1.42977	3.15467	-.02232
1.450	-5.509	-.23207	-176.24910	-.23787	-.11062	-.00563	-.00262	1.43238	3.16403	.01991
1.450	-5.011	-.23132	-175.88980	-.21882	-.10149	-.00556	-.00258	1.43471	3.17242	-.01725
1.449	-4.518	-.23066	-175.45100	-.19901	-.09196	-.00435	-.00201	1.43676	3.17979	-.01371
1.450	-4.015	-.23163	-174.89320	-.17812	-.08212	-.00369	-.00170	1.43997	3.19138	.01110
1.449	-3.521	-.23342	-174.17650	-.15606	-.07181	-.00361	-.00166	1.44126	3.19606	.00922
1.450	-3.024	-.23387	-173.22140	-.13361	-.06142	-.00334	-.00153	1.44300	3.20234	.00812
1.449	-2.526	-.23179	-171.94840	-.11263	-.05173	-.00353	-.00162	1.44288	3.20189	-.00745
1.450	-2.038	-.23438	-170.00060	-.09299	-.04267	-.00328	-.00151	1.44423	3.20681	-.00635
1.450	-1.555	-.23424	-166.98100	-.07450	-.03409	-.00292	-.00134	1.44638	3.21459	-.00368
1.450	-1.082	-.23472	-161.42200	-.05501	-.02509	-.00264	-.00121	1.45018	3.22840	.00015
1.451	-.643	-.24850	-148.88540	-.03612	-.01646	-.00262	-.00119	1.45033	3.23080	.00035
1.450	-.299	-.34517	-115.68240	-.02136	-.00974	-.00526	-.00240	1.45005	3.22794	-.00001
1.450	.266	-.66054	-56.38206	.00206	.00094	-.01812	-.00826	1.45056	3.22982	.00073
1.451	.841	-.74421	-33.61598	.02566	.01170	-.02117	-.00965	1.45097	3.23130	.00035
GRADIENT		-.07563	23.21044	.04179	.01927	-.00234	-.00106	.00275	.00999	.00287

RUN NO. 1639/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.470	-7.019	-.25219	-176.96980	-.30680	-.14525	-.00628	-.00297	1.44075	3.19420	-.03901
1.470	-6.504	-.25183	-176.72960	-.28681	-.13531	-.00585	-.00276	1.44400	3.20596	-.03528
1.469	-6.005	-.25252	-176.44980	-.26653	-.12523	-.00560	-.00263	1.44707	3.21709	-.03122
1.470	-5.507	-.25252	-176.13020	-.24452	-.11451	-.00607	-.00284	1.45064	3.23008	-.02776
1.470	-5.013	-.25690	-175.73150	-.22232	-.10397	-.00557	-.00261	1.45231	3.23616	-.02626
1.470	-4.510	-.25468	-175.29260	-.20137	-.09401	-.00454	-.00212	1.45294	3.23848	-.02462
1.470	-4.017	-.25401	-174.73470	-.17956	-.08367	-.00381	-.00177	1.45528	3.24703	-.02255
1.470	-3.518	-.25257	-174.01780	-.15770	-.07334	-.00358	-.00167	1.45670	3.25223	-.02058
1.484	-3.020	-.25394	-173.02290	-.13264	-.06282	-.00277	-.00131	1.45798	3.25692	-.01921
1.470	-2.533	-.25341	-171.71030	-.11425	-.05309	-.00232	-.00108	1.45759	3.25547	-.01970
1.470	-2.040	-.25417	-169.72280	-.09506	-.04413	-.00252	-.00117	1.45853	3.25891	-.01871
1.470	-1.551	-.25527	-166.54440	-.07596	-.03522	-.00226	-.00105	1.45952	3.26256	-.01760
1.470	-1.075	-.25535	-160.82680	-.05667	-.02626	-.00190	-.00088	1.46019	3.26500	-.01684
1.470	-6.39	-.26917	-148.01310	-.03856	-.01786	-.00244	-.00113	1.46046	3.26599	-.01650
1.470	-2.258	-.42252	-108.27830	-.02201	-.01020	-.00985	-.00456	1.45971	3.26324	-.01672
1.470	.287	-.65457	-55.47147	-.00180	-.00083	-.00956	-.0006	1.46073	3.26698	-.01625
1.470	.864	-.72189	-32.54695	-.02607	-.02167	-.01004	-.0004	1.46028	3.26533	-.01640
GRADIENT		-.07257	23.64120	.04181	.01953	-.00268	-.00124	.00460	.00126	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM048) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1590/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	- 5.00 /	5.00	BETA	=	- .500	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPD	MPROBE	CPM	CPTD			
1.492	-7.017	-.26511	-176.93040	-.32563	-.15539	-.00502	-.00240	1.45984	3.26373	-.04536				
1.492	-6.508	-.26458	-176.69020	-.30319	-.14440	-.00544	-.00259	1.46218	3.27232	-.04307				
1.492	-6.004	-.26447	-176.41030	-.28431	-.13501	-.00498	-.00236	1.46495	3.28249	-.04007				
1.492	-5.511	-.26851	-176.05120	-.26311	-.12464	-.00466	-.00221	1.46709	3.29040	-.03752				
1.492	-5.012	-.26608	-175.69180	-.24188	-.11430	-.00371	-.00175	1.46872	3.29640	-.03508				
1.492	-4.514	-.26822	-175.21340	-.21940	-.10347	-.00400	-.00189	1.47073	3.30385	-.03296				
1.492	-4.016	-.26737	-174.65550	-.19732	-.09285	-.00342	-.00161	1.47309	3.31256	-.03058				
1.493	-3.523	-.26791	-173.89880	-.17482	-.08214	-.00293	-.00138	1.47477	3.31881	-.02892				
1.492	-3.024	-.26826	-172.90390	-.15202	-.07139	-.00307	-.00144	1.47472	3.31861	-.02846				
1.492	-2.531	-.26983	-171.51190	-.13027	-.06115	-.00360	-.00169	1.47492	3.31937	-.02821				
1.492	-2.039	-.26913	-169.52430	-.10812	-.05076	-.00342	-.00160	1.47481	3.31896	-.02837				
1.492	-1.549	-.26987	-166.30630	-.08630	-.04056	-.00352	-.00166	1.47377	3.31510	-.02941				
1.493	-1.078	-.27193	-160.50940	-.06522	-.03067	-.00383	-.00180	1.47396	3.31578	-.02996				
1.492	-6.629	-.28218	-147.45810	-.04490	-.02111	-.00440	-.00207	1.47383	3.31530	-.02961				
1.492	-.244	-.42999	-107.36770	-.02569	-.01208	-.01326	-.00623	1.47333	3.31346	-.02973				
1.492	.302	-.64757	-54.75883	.00268	-.00126	-.02285	-.01075	1.47259	3.31073	-.03076				
1.492	.872	-.71317	-32.38853	.02974	-.01401	-.02461	-.01159	1.47187	3.30804	-.03181				
GRADIENT		-.06885	23.68401	.04596	.02163	-.00347	-.00163	-.00007	-.000026					

	RUN NO.	1606/ 0	RN/L =	2.49	GRADIENT INTERVAL	=	- 5.00 /	5.00	BETA	=	- .500	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPD	MPROBE	CPM	CPTD			
1.515	-7.022	-.26624	-176.93060	-.37043	-.17535	-.00802	-.00380	1.49510	3.39480	-.03385				
1.515	-6.502	-.26485	-176.69020	-.34732	-.16394	-.00762	-.00360	1.49712	3.40242	-.03099				
1.514	-6.004	-.26480	-176.41030	-.32306	-.15205	-.00675	-.00318	1.49950	3.41138	-.02811				
1.515	-5.510	-.26822	-176.05120	-.29680	-.13925	-.00555	-.00260	1.50253	3.42284	-.02491				
1.515	-5.012	-.26589	-175.69180	-.26693	-.12645	-.00418	-.00196	1.50457	3.43059	-.02331				
1.515	-4.514	-.26695	-175.21330	-.24423	-.11425	-.00474	-.00222	1.50511	3.43264	-.02215				
1.515	-4.016	-.26829	-174.61570	-.22248	-.10399	-.00517	-.00242	1.50578	3.43515	-.02151				
1.514	-3.518	-.26643	-173.89870	-.19721	-.09204	-.00603	-.00281	1.50676	3.43888	-.02007				
1.515	-3.019	-.26992	-172.86420	-.16958	-.07899	-.00616	-.00287	1.50953	3.44943	-.01805				
1.514	-2.531	-.26801	-171.55160	-.14143	-.06577	-.00623	-.00290	1.50989	3.45079	-.01671				
1.514	-2.038	-.26925	-169.52430	-.11448	-.05317	-.00619	-.00287	1.51068	3.45379	-.01527				
1.514	-1.548	-.26854	-166.34600	-.08789	-.04082	-.00587	-.00272	1.51137	3.45642	-.01521				
1.514	-1.072	-.27051	-160.46970	-.06418	-.02983	-.00711	-.00331	1.51059	3.45345	-.01606				
1.514	-6.633	-.28181	-147.53740	-.04367	-.02029	-.00987	-.00459	1.51061	3.45355	-.01579				
1.514	-2.245	-.43392	-107.40730	-.02222	-.01032	-.02058	-.00956	1.51089	3.45460	-.01525				
1.514	.301	-.64777	-54.87759	.00797	.00370	-.03066	-.01425	1.51002	3.45129	-.01575				
1.514	.871	-.71394	-32.38852	.03393	.01578	-.03098	-.01440	1.51099	3.45156	-.01571				
GRADIENT		-.06918	23.67958	.05259	.02457	-.00462	-.00214	-.00095	-.00026					

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 556

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM048) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1621/ O	RN/L =	2.49	GRADIENT INTERVAL =	- 5.00/ 5.00	BETA =	- .500	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPM	CPTD
1.541	-7.017	-26564	-176.93050	-34578	-.16320	-.01111	-.00525	1.52873	3.52300	-.02353
1.541	-6.502	-26465	-176.69020	-.31166	-.14692	-.00957	-.00451	1.52957	3.52626	-.02228
1.541	-6.009	-26534	-176.41040	-.28143	-.13260	-.00966	-.00455	1.53044	3.52962	-.02168
1.542	-5.505	-26866	-176.05120	-.25237	-.11882	-.00953	-.00449	1.53143	3.53344	-.02095
1.542	-5.012	-27050	-175.65230	-.22359	-.10533	-.00915	-.00431	1.53110	3.53217	-.02153
1.541	-4.514	-26969	-175.21350	-.19504	-.09190	-.00992	-.00468	1.53018	3.52859	-.02179
1.542	-4.016	-26784	-174.65550	-.16533	-.07786	-.00874	-.00412	1.53117	3.53241	-.02116
1.541	-3.518	-26871	-173.89890	-.13559	-.06375	-.00743	-.00350	1.53242	3.53728	-.01956
1.542	-3.020	-26669	-172.94360	-.11132	-.05232	-.00718	-.00337	1.53304	3.53967	-.01894
1.541	-2.527	-26852	-171.55170	-.09192	-.04324	-.00802	-.00377	1.53166	3.53432	-.02008
1.541	-2.034	-26783	-169.56400	-.07507	-.03533	-.00832	-.00391	1.53096	3.53161	-.02052
1.542	-1.549	-26888	-166.34600	-.05747	-.02704	-.00731	-.00344	1.53195	3.53544	-.02025
1.541	-1.077	-27179	-160.50940	-.04074	-.01917	-.00691	-.00325	1.53196	3.53548	-.02013
1.541	-632	-28310	-147.49770	-.02641	-.01242	-.00611	-.00287	1.53166	3.53433	-.01986
1.541	-245	-43475	-107.40730	-.01361	-.00640	-.01247	-.00586	1.53212	3.53611	-.01961
1.542	.303	-64741	-54.79842	.00566	.00267	-.01895	-.00892	1.53203	3.53576	-.01971
1.542	.879	-71215	-32.11136	.02382	.01121	-.01995	-.00939	1.53241	3.53722	-.01974
GRADIENT		-06895	23.71303	.03918	.01845	-.00164	-.00077	.00018	.00071	.00022

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM049 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.		1575/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	180.000	CPTD
		ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM					
MACH	.599	.6. 997	.29695	178. 69400	- .29906	- .06002	.01296	.00260	.57706	1.25316					
	.600	-6. 488	.29875	178. 57460	- .27677	- .05545	.01348	.00270	.58068	1.25660					
	.599	-5. 990	.29486	178. 49450	- .25655	- .05119	.01475	.00294	.58332	1.25914					
	.600	-5. 492	.29676	178. 33550	- .23486	- .04692	.01605	.00321	.58675	1.26245					
	.600	-4. 994	.29617	178. 17630	- .21451	- .04280	.01595	.00318	.58876	1.26441					
	.600	-4. 490	.29574	177. 97760	- .19359	- .03857	.01590	.00317	.59105	1.26665					
	.600	-3. 991	.29783	177. 69970	- .17286	- .03435	.01611	.00320	.59252	1.26809					
	.600	-3. 487	.29474	177. 42160	- .15193	- .03016	.01575	.00313	.59397	1.26952					
	.600	-2. 987	.29566	176. 98520	- .13043	- .02588	.01547	.00307	.59574	1.27127					
	.600	-2. 482	.29350	176. 42980	- .10874	- .02157	.01546	.00307	.59670	1.27222					
	.601	-1. 976	.29291	175. 55760	- .08785	- .01743	.01618	.00321	.59825	1.27376					
	.600	-1. 468	.29037	174. 17040	- .06613	- .01308	.01721	.00340	.59819	1.27370					
	.600	-954	.28659	171. 43630	- .04457	- .00882	.01664	.00329	.59898	1.27449					
	.600	-420	.26930	164. 18700	- .02361	- .00467	.01738	.00344	.59906	1.27456					
	.600	-75	-17418	.86780	- .01271	- .00251	.01271	- .00146	.00029	.59951	1.27501				
	.600	-472	-25165	-9. 50680	.00803	.00159	- .00378	- .00075	.59966	1.27517					
	.600	-984	-28028	-6. 29842	.02920	.00578	.00413	- .00082	.59948	1.27499					
	.600	GRADIENT	-08900	-30. 49832	.04096	.00815	- .00304	- .00061	.00174	.00174	.00136				
RUN NO.		1465/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	5.00	CPTD
		ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM					
MACH	.800	-7. 003	.21322	179. 04800	- .28645	- .08607	.01128	.00339	.77649	1.48957					
	.800	-6. 492	.21335	178. 96820	- .26645	- .07987	.01069	.00320	.77987	1.49447					
	.800	-5. 986	.21267	178. 88850	- .24647	- .07370	.01126	.00337	.78282	1.49878					
	.800	-5. 491	.21437	178. 76920	- .22630	- .06747	.01253	.00374	.78568	1.50297					
	.800	-4. 991	.21415	178. 64990	- .20648	- .06145	.01291	.00384	.78801	1.50641					
	.800	-4. 490	.21461	178. 49100	- .18648	- .05536	.01285	.00382	.78969	1.50890					
	.800	-3. 990	.21539	178. 29250	- .16649	- .04934	.01270	.00376	.79174	1.51195					
	.800	-3. 489	.21489	178. 05420	- .14616	- .04324	.01242	.00367	.79334	1.51433					
	.800	-2. 988	.21299	177. 77640	- .12587	- .03721	.01230	.00364	.79485	1.51658					
	.800	-2. 487	.21430	177. 30060	- .10521	- .03106	.01280	.00378	.79595	1.51823					
	.800	-1. 980	.21262	176. 66620	- .08520	- .02511	.01304	.00384	.79646	1.51900					
	.800	-1. 477	.21100	175. 63570	- .06476	- .01908	.01352	.00398	.79744	1.52048					
	.800	-971	.20875	173. 61480	- .04453	- .01311	.01336	.00393	.79787	1.52113					
	.800	-451	.19832	168. 22700	- .02509	- .00739	.01437	.00423	.79839	1.52191					
	.800	.083	-11513	41. 93819	- .00453	- .00133	.00124	.00037	.79899	1.52281					
	.801	.489	-17306	-4. 67581	- .00963	- .00283	- .00035	- .00010	.79935	1.52336					
	.800	1. 006	-19536	-3. 5636	.02974	.00875	- .00068	- .00020	.79871	1.52239					
	.800	GRADIENT	-06311	-28. 30927	.03956	.01174	- .00202	- .00060	.00180	.00269	.00179				

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 558  
( TCM049 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1499/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= .000	PHI	= 180.000	
.900	-7.001	.22473	179.00860	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPTD			
.900	-6.487	.22925	178.88950	-.27538	-.09451	.00973	.00334	.87777	1.65139	-.02392		
.900	-5.985	.22759	178.80970	-.25593	-.08759	.01040	.00356	.88075	1.65664	-.02087		
.900	-5.483	.22840	178.69040	-.23681	-.08082	.01168	.00399	.88329	1.66113	-.01811		
.900	-4.991	.22718	178.57100	-.21732	-.07398	.01200	.00409	.88596	1.66589	-.01533		
.900	-4.489	.22741	178.41200	-.19836	-.06738	.01256	.00427	.88826	1.67002	-.01299		
.900	-3.986	.22763	178.21340	-.17943	-.06078	.01266	.00429	.89021	1.67351	-.01055		
.900	-3.489	.22628	177.97520	-.15986	-.05406	.01280	.00433	.89197	1.67668	-.00868		
.900	-2.981	.22713	177.61810	-.14007	-.04730	.01246	.00421	.89375	1.67992	-.00701		
.900	-2.478	.22531	177.18180	-.10091	-.03397	.01251	.00421	.89476	1.68175	-.00543		
.900	-1.980	.22476	176.50780	-.08177	-.02750	.01266	.00426	.89672	1.68388	-.00429		
.900	-1.475	.22478	175.35840	-.06210	-.02087	.01315	.00442	.89765	1.68530	-.00341		
.900	-966	.22156	173.21870	-.04268	-.01433	.01289	.00433	.89822	1.68700	-.00245		
.900	-448	.21111	167.47440	-.02409	-.00809	.01362	.00457	.89866	1.68884	-.00191		
.900	-048	.13979	26.80847	-.00613	-.00206	.0061	.00021	.89875	1.68901	-.00126		
.900	.481	-.18935	-5.82417	.00900	.00302	-.00079	-.00026	.89896	1.68940	-.00106		
.900	.997	-.21063	-4.04149	.02819	.00946	-.00102	-.00034	.89885	1.68920	-.00110		
	GRADIENT	-.06813	-29.10114	.03798	.01286	-.00210	-.00071	.00173	.00315	.00192		
MACH	ALPHA	RUN NO.	1484/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= .000	PHI	= 5.00	
1. 100	-7.006	.08456	179.67870	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPTD			
1. 100	-6.492	.08663	179.63910	-.25068	-.10209	.00435	.00177	1.07887	2.07912	-.02562		
1. 100	-5.995	.08705	179.59920	-.23266	-.09444	.00551	.00224	1.08190	2.08672	-.02212		
1. 100	-5.492	.08713	179.55930	-.21562	-.08723	.00504	.00204	1.08407	2.09220	-.01892		
1. 100	-4.992	.08539	179.51930	-.19809	-.07993	.00592	.00239	1.08680	2.09910	-.01612		
1. 100	-4.488	.08434	179.43970	-.16372	-.07287	.00635	.00255	1.08886	2.10432	-.01328		
1. 100	-3.995	.07877	179.32010	-.14574	-.06575	.00626	.00252	1.09080	2.10927	-.01125		
1. 100	-3.496	.08240	179.12180	-.12786	-.05115	.00640	.00674	.00270	1.09226	2.11299	-.00921	
1. 100	-2.997	.08810	178.92380	-.10959	-.04377	.00665	.00692	.00277	1.09388	2.11713	-.00735	
1. 100	-2.488	.08894	178.76520	-.09212	-.03674	.00708	.00666	.00266	1.09508	2.12020	-.00586	
1. 100	-1.998	.08772	178.56690	-.07501	-.02989	.00717	.00282	1.09606	2.12270	-.00439		
1. 100	-1.487	.08614	178.17050	-.05773	-.02298	.00765	.00304	.00304	1.09767	2.12686	-.00263	
1. 100	-989	.08516	177.45720	-.04085	-.01626	.00752	.00299	.00299	1.09841	2.12876	-.00203	
1. 100	-486	.08193	175.47610	-.02444	-.00972	.00818	.00325	.00325	1.09864	2.12933	-.00157	
1. 100	.001	.03328	159.94870	-.00829	-.00330	.00687	.00273	.00273	1.09883	2.12984	-.00130	
1. 100	.513	-.05394	1.30364	-.00824	-.00327	.00394	.00156	.00156	1.09901	2.13030	-.00090	
1. 100	1.014	-.06512	.03670	.02525	.01004	.00388	.00154	.00154	1.09934	2.13115	-.00084	
	GRADIENT	-.01962	-22.63144	.03437	.01379	-.00022	-.00009	.00009	.00430	.00168	.00203	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM049) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1522/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.250	-7.001	17721	179.24520	-25759	-11309	.00839	.00368	1.22846	2.49151	-.02629
1.250	-6.485	17954	179.16570	-23923	.10461	.00870	.00380	1.23137	2.50026	-.02226
1.250	-5.987	18028	179.08600	-22128	.09649	.00990	.00432	1.23380	2.50756	-.01937
1.250	-5.488	17921	179.00630	-20246	.08800	.00929	.00404	1.23645	2.51555	-.01615
1.250	-4.984	17986	178.88700	-18436	.08000	.01043	.00453	1.23786	2.51981	-.01445
1.250	-4.486	18002	178.72810	-16666	.07217	.01017	.00441	1.23963	2.52157	-.01237
1.250	-3.988	18045	178.52950	-14854	.06418	.01113	.00481	1.24183	2.53184	-.00991
1.250	-3.489	17951	178.33100	-12993	.05603	.01058	.00456	1.24277	2.53470	-.00816
1.250	-2.987	17841	178.05320	-11175	.04809	.01068	.00460	1.24457	2.54017	-.00606
1.250	-2.483	18083	177.61710	-9362	.04024	.01056	.00454	1.24601	2.54458	-.00470
1.250	-1.978	18038	177.06210	-7625	.03273	.01059	.00455	1.24703	2.54768	-.00337
1.250	-1.478	17930	176.19010	-5887	.02524	.01085	.00465	1.24745	2.54897	-.00262
1.250	-980	17624	174.40690	-4097	.01756	.01149	.00493	1.24803	2.55075	-.00216
1.249	-462	16954	169.65290	-02292	.00982	.01174	.00503	1.24812	2.55100	-.00161
1.250	-102	03761	107.87740	-00330	.00141	.00767	.00329	1.24803	2.55073	-.00218
1.250	.502	-13879	-2.65627	.00982	.00421	.00164	.00070	1.24857	2.55239	-.00167
1.250	1.009	-15984	-2.61614	.02771	.01186	.00154	.00066	1.24890	2.55340	-.00104
1.250	GRADIENT	-04621	-25.20443	.03539	.01531	-.00114	-.00050	.00175	.00534	.00213
	RUN NO.	1538/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.400	-7.005	16861	179.24500	-28507	.13179	.01594	.00737	1.37627	2.96699	-.02751
1.400	-6.490	16654	179.20490	-26513	.12213	.01625	.00748	1.37979	2.97907	-.02369
1.400	-5.987	16364	179.16480	-24554	.11273	.01544	.00709	1.38202	2.98676	-.02048
1.400	-5.487	16647	179.04560	-22533	.10321	.01576	.00722	1.38411	2.99399	-.01803
1.400	-4.989	16314	178.96580	-20637	.09422	.01607	.00734	1.38737	3.00528	-.01471
1.400	-4.485	16553	178.80700	-18689	.08512	.01651	.00752	1.38984	3.01384	-.01209
1.400	-3.993	16588	178.64810	-16673	.07577	.01689	.00768	1.39115	3.01839	-.01008
1.400	-3.489	16592	178.44970	-14549	.06598	.01689	.00766	1.39287	3.02435	-.00791
1.400	-2.987	16475	178.21160	-12439	.05636	.01645	.00745	1.39413	3.02875	-.00692
1.400	-2.484	16483	177.85460	-10436	.04722	.01613	.00730	1.39527	3.03270	-.00552
1.400	-1.981	16419	177.33930	-08547	.03865	.01595	.00721	1.39616	3.03582	-.00487
1.400	-1.483	16370	176.50690	-06665	.03007	.01609	.00726	1.39778	3.04149	-.00272
1.399	-979	16362	174.84270	-04666	.02104	.01641	.00740	1.39769	3.04115	-.00207
1.400	-468	15563	170.64320	-02695	.01215	.01683	.00758	1.39901	3.04577	-.00149
1.400	.091	04916	114.01500	-00539	.00243	.01279	.00576	1.39896	3.04562	-.00152
1.400	.501	-12563	-1.94349	.00972	.00438	.00634	.00285	1.39947	3.04739	-.00071
1.400	1.006	-14532	-2.10137	.02940	.01325	.00554	.00249	1.39911	3.04614	-.00117
		-04151	-24.85189	.03934	.01790	-.00143	-.00066	.00195	.00679	.00224

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 560

(TCM049) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1556/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPM	CPTD
1.450	-6.956	.23319	179.16620	.29735	.13937	.01507	.00706	1.42593	3.14094	-.02788
1.450	-6.487	.28070	178.69310	.27866	.13023	.01690	.00790	1.42771	3.14731	-.02506
1.450	-5.983	.28116	178.57360	.25748	.12006	.01643	.00766	1.43076	3.15822	-.02250
1.450	-5.484	.28057	178.45410	.23631	.10990	.01564	.00727	1.43261	3.16489	-.01998
1.450	-4.980	.28043	178.29500	.21745	.10081	.01622	.00752	1.43551	3.17531	-.01668
1.450	-4.481	.27627	178.13560	.19738	.09122	.01751	.00809	1.43808	3.18455	-.01360
1.451	-3.982	.27814	177.85770	.17581	.08105	.01752	.00808	1.44094	3.19488	-.01091
1.450	-3.483	.27604	177.57970	.15414	.07093	.01739	.00800	1.44224	3.19960	-.00909
1.450	-2.979	.27720	177.14330	.13190	.06065	.01756	.00807	1.44240	3.20017	-.00849
1.450	-2.475	.27807	176.54850	.11064	.05083	.01687	.00775	1.44351	3.20421	-.00755
1.449	-1.969	.27688	175.71590	.09083	.04166	.01719	.00789	1.44357	3.20442	-.00609
1.450	-1.466	.27554	174.36830	.07144	.03268	.01774	.00812	1.44743	3.21841	-.00324
1.450	-954	.27164	171.79280	.05028	.02293	.01824	.00832	1.45034	3.22899	.00010
1.449	-423	.25549	164.89990	.02726	.01243	.01795	.00818	1.44954	3.22607	.00011
1.450	-081	.16512	.00343	.01417	.00647	.00151	.00069	1.44856	3.22253	-.00131
1.450	.477	.23917	-.8.83363	.00772	.00352	.00001	.00000	1.45022	3.22855	.00061
1.451	-.445	.24513	-10.17999	.00675	.00307	-.00035	-.00016	1.45172	3.23403	.00105
1.450	.987	.26674	-.5.90245	.03002	.01368	-.00072	-.00033	1.45073	3.23042	.000060
GRADIENT		.09302	-33.65768	.04130	.01908	-.00303	-.00141	.00252	.00914	.00290
	RUN NO.	1640/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPM	CPTD
1.471	-6.954	.21442	179.24500	.30378	.14374	.01643	.00777	1.44219	3.19941	-.03821
1.485	-6.486	.25780	178.81130	.27982	.13461	.01605	.00772	1.44433	3.20717	-.03525
1.484	-5.987	.25994	178.69200	.25985	.12457	.01703	.00816	1.44708	3.21716	-.03163
1.471	-5.489	.25980	178.57250	.24308	.11387	.01658	.00777	1.45121	3.23217	-.02787
1.485	-4.985	.25766	178.45300	.21671	.10338	.01683	.00803	1.45195	3.23487	-.02659
1.470	-4.486	.25673	178.25420	.19977	.09327	.01743	.00814	1.45280	3.23797	-.02461
1.484	-3.982	.25753	178.01590	.17449	.08291	.01770	.00841	1.45492	3.24569	-.02249
1.470	-3.489	.25737	177.73800	.15626	.07267	.01837	.00854	1.45715	3.25385	-.02024
1.471	-2.980	.25599	177.38080	.13348	.06199	.01763	.00819	1.45872	3.25962	-.01904
1.470	-2.476	.25499	176.86520	.11227	.05216	.01801	.00837	1.45781	3.25627	-.01942
1.470	-1.976	.25547	176.07230	.09254	.04294	.01879	.00872	1.45863	3.25930	-.01826
1.485	-1.469	.25427	174.84360	.07124	.03369	.01875	.00887	1.45956	3.26270	-.01757
1.484	-.958	.25144	172.46620	.05100	.02409	.01925	.00910	1.46022	3.26511	-.01663
1.470	-4.438	.23788	166.24660	.03020	.01399	.01982	.00918	1.45967	3.26312	-.01677
1.470	-0.80	-.15499	.03617	.01125	.00521	.00143	.00066	1.46013	3.26478	-.01656
1.470	.487	-.22212	-7.96246	.01010	.00468	-.00077	-.00036	1.46026	3.26526	-.01643
1.470	.997	-.24321	-5.11055	.03108	.01439	-.00113	-.00052	1.46136	3.26932	-.01547
GRADIENT		-.07767	-30.43247	.04166	.01962	-.00278	-.00131	.00140	.00514	.00164

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PARAMETRIC DATA									
RUN NO.	1591/0	RN/L	=	2.50	GRADIENT	INTERVAL	=	-5.00/	5.00
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.492	-6.954	.20197	179.28430	-.32235	-.15353	.01923	.00916	1.46209	3.27197
1.492	-6.486	.24535	178.85060	-.30232	-.14381	.01910	.00908	1.46285	3.27480
1.492	-5.988	.24418	178.77080	-.28326	-.13437	.01963	.00931	1.46582	3.28572
1.492	-5.484	.24472	178.65140	-.26219	-.12409	.01966	.00930	1.46746	3.29177
1.492	-4.991	.24300	178.53190	-.24038	-.11356	.02027	.00958	1.46967	3.29992
1.493	-4.487	.24522	178.33330	-.21837	-.10293	.02045	.00964	1.47207	3.30880
1.493	-3.989	.23917	178.17400	-.19565	-.09201	.01992	.00937	1.47397	3.31581
1.493	-3.484	.24210	177.85660	-.17276	-.08111	.02113	.00992	1.47548	3.32145
1.493	-2.986	.24203	177.49950	-.14994	-.07038	.02089	.00980	1.47594	3.32313
1.492	-2.477	.24231	176.98390	-.12792	-.06002	.01996	.00936	1.47592	3.32306
1.493	-1.978	.24117	176.27020	-.10538	-.04943	.01998	.00937	1.47658	3.32552
1.492	-1.472	.24008	175.08120	-.08262	-.03880	.01998	.00938	1.47715	3.32020
1.493	-0.964	.23538	172.86220	-.06012	-.02824	.02079	.00977	1.47485	3.31908
1.492	-0.443	.22488	166.72190	-.03640	-.01709	.02110	.00990	1.47530	3.32075
1.492	-.090	.14593	-.00344	-.01443	-.00677	.02110	.00067	1.47595	3.32338
1.492	.492	.20795	-7.24971	.01214	.00570	-.00060	-.00028	1.47486	3.31913
1.493	.995	.22773	-4.75424	.03527	.01659	-.00102	-.00048	1.47387	3.31546
1.493	GRADIENT	.07310	-30.36930	.04597	.02166	-.00335	-.00158	.00048	.00057
RUN NO. 1607/0 RN/L = 2.49									
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.515	-7.006	.24531	178.93040	-.36820	-.17426	.02053	.00972	1.49491	3.39408
1.514	-6.491	.24504	178.85060	-.34505	-.16282	.02049	.00967	1.49712	3.40240
1.515	-5.987	.24382	178.77070	-.32165	-.15134	.02107	.00991	1.50056	3.41539
1.515	-5.483	.24432	178.65140	-.29533	-.13853	.02200	.01032	1.50330	3.42576
1.515	-4.990	.24218	178.53180	-.26868	-.12581	.02236	.01047	1.50450	3.43031
1.514	-4.492	.24121	178.37270	-.24325	-.11387	.02232	.01045	1.50437	3.42981
1.515	-3.983	.24189	178.13450	-.22049	-.10323	.02257	.01057	1.50501	3.43225
1.515	-3.484	.24216	177.85660	-.19609	-.09143	.02163	.01008	1.50810	3.44399
1.514	-2.986	.24188	177.49950	-.16711	-.07787	.02013	.00938	1.50792	3.44328
1.515	-2.483	.24250	176.98390	-.14023	-.06524	.02025	.00942	1.51063	3.45362
1.514	-1.978	.24241	176.23070	-.11233	-.05216	.01960	.00910	1.51164	3.45744
1.514	-1.471	.23946	175.08120	-.08528	-.03963	.01936	.00900	1.51087	3.45454
1.515	-.962	.23672	172.78300	-.06082	-.02828	.01989	.00925	1.51164	3.45744
1.514	-.448	.22687	166.84070	-.03500	-.01627	.01912	.00889	1.51071	3.45391
1.515	-.095	-.14713	-.00344	-.00409	-.00190	-.00646	-.00301	1.51071	3.45392
1.515	.493	.20787	-7.13090	.02010	.00935	-.00870	-.00405	1.51065	3.45369
1.515	1.001	.22773	-4.63542	.04296	.01998	-.00884	-.00411	1.51092	3.45472
1.515	GRADIENT	.07291	-30.35380	.05299	.02479	-.00510	-.00239	.00134	.00456

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 562

(TCM049) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1622/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPI	CPTD
1.542	-6.954	.20107	179.28420	-.337778	-.15958	.02026	.00957	1.52866	3.52273	-.02333
1.542	-6.491	.24522	178.85060	-.30770	-.14522	.01661	.00784	1.53003	3.52802	-.02222
1.542	-5.987	.24354	178.77070	-.27708	-.13068	.01693	.00799	1.53035	3.52927	-.02168
1.542	-5.489	.24375	178.65130	-.24704	-.11643	.01645	.00775	1.53043	3.52956	-.02176
1.541	-4.990	.24475	178.49230	-.21942	-.10343	.01554	.00733	1.52982	3.52720	-.02201
1.541	-4.487	.24206	178.33310	-.19133	-.09016	.01501	.00708	1.53033	3.52917	-.02173
1.541	-3.983	.24351	178.09480	-.16269	-.07659	.01424	.00670	1.53136	3.53317	-.02069
1.542	-3.485	.24115	177.85650	-.13450	-.06324	.01349	.00634	1.53259	3.53793	-.01950
1.541	-2.982	.24054	177.49940	-.11023	-.05180	.01154	.00542	1.53215	3.53622	-.01906
1.541	-2.478	.24128	176.98390	-.09082	-.04273	.00980	.00461	1.53136	3.53318	-.02035
1.541	-1.978	.24147	176.23060	-.07288	-.03429	.01015	.00478	1.53148	3.53363	-.02036
1.541	-1.472	.23976	175.04160	-.05501	-.02588	.00960	.00452	1.53127	3.53281	-.02024
1.541	-962	.23662	172.74330	-.03702	-.01741	.01057	.00497	1.53155	3.53391	-.02011
1.541	-441	.22542	166.60310	-.01984	-.00933	.01190	.00560	1.53208	3.53595	-.01969
1.541	.142	.03240	115.04450	.00093	.00044	.00720	.00338	1.53275	3.53853	-.01903
1.541	.478	-.20191	-6.61615	.01280	.00602	-.00393	-.00185	1.53266	3.53819	-.01927
1.542	.996	-.22318	-4.39786	.02778	.01306	-.00372	-.00175	1.53241	3.53722	-.01996
	GRADIENT	-.06426	-25.08703	.04031	.01899	-.00266	-.00125	.00033	.000127	.000031

## PARAMETRIC DATA

RUN NO.	1576/ 0	RN/L =	2.50	GRADIENT INTERVAL	= -5.00/ 5.00	BETA = .500		PHI = 180.000	
						CPBQ	CPALPH	CPBETA	CPALPH
MACH	ALPHA	BETA	PHI	CPAQ	-29829	.05986	.03453	.0693	.57703
.599	-6.980	.78675	174.72250	-	.05531	.03549	.00711	.58073	1.25666
.600	-6.468	.78469	174.32340	-27600	.05087	.03575	.00715	.58378	1.25958
.600	-5.967	.78123	173.88470	-25443	.04654	.03607	.00720	.58617	1.26189
.600	-5.464	.78109	173.32730	-23321	.04242	.03619	.00721	.58926	1.26490
.600	-4.966	.78271	172.65110	-21283	.03820	.03582	.00713	.59102	1.26662
.600	-4.462	.78081	171.85600	-19184	.03396	.03620	.00720	.59262	1.26819
.600	-3.951	.78137	170.82330	-17069	.02987	.03579	.00711	.59457	1.27011
.600	-3.448	.77779	169.59240	-15042	.02543	.03531	.00701	.59612	1.27165
.601	-2.937	.77626	167.88630	-12803	.01924	.03625	.00718	.59656	1.27207
.600	-2.431	.77322	165.58610	-10700	.01685	.03630	.00718	.59788	1.27339
.600	-1.912	.76448	162.25610	-08523	.01255	.03546	.00703	.59883	1.27434
.601	-1.392	.75512	156.90660	-06334	.00804	.03447	.00683	.59883	1.27433
.601	-855	.72571	147.51810	-04055	.00380	.03090	.00611	.59940	1.27490
.600	-299	.64718	127.99350	-01924	.00026	.02345	.00463	.59935	1.27486
.600	-254	.46175	80.82901	.00129	.00031	.01740	.00344	.59940	1.27491
.600	-670	.29209	37.77702	.01675	.00680	.01655	.00327	.59911	1.27462
.600	1.102	.25463	22.05223	.03442	.00814	.00296	-.00060	.00159	.00127
	GRADIENT	.07884	-22.45996	.04091					
RUN NO.	1466/ 0	RN/L =	2.49	GRADIENT INTERVAL	= -5.00/ 5.00	BETA = .500		PHI = 180.000	
						CPBQ	CPALPH	CPBETA	CPALPH
MACH	ALPHA	BETA	PHI	CPAQ	-28539	.08583	.03208	.00965	.77648
.800	-6.986	.70777	175.03710	-26494	.07948	.03247	.00974	.78000	1.49466
.800	-6.478	.70417	174.67770	-24497	.07326	.03282	.00982	.78249	1.49829
.800	-5.974	.70333	174.23930	-22476	.06704	.03277	.00977	.78570	1.50300
.800	-5.470	.70244	173.72160	-20500	.06098	.03300	.00982	.78768	1.50591
.800	-4.971	.70335	173.08520	-18487	.05491	.03288	.00977	.78996	1.50929
.800	-4.471	.70308	172.33000	-16498	.04892	.03266	.00968	.79201	1.51234
.800	-3.969	.70076	171.41620	-14450	.04275	.03210	.00950	.79339	1.51440
.800	-3.461	.69839	170.22510	-12411	.03667	.03187	.00942	.79479	1.51650
.800	-2.954	.69718	168.63800	-10338	.03052	.03188	.00941	.79605	1.51838
.800	-2.449	.69534	166.45680	-08338	.02459	.03186	.00940	.79683	1.51956
.800	-1.938	.69074	163.28550	-06251	.01841	.03142	.00926	.79751	1.52059
.800	-1.424	.68225	158.29260	-04131	.01216	.03148	.00927	.79810	1.52147
.800	-900	.66218	149.41910	-02115	.00622	.02982	.00878	.79865	1.52230
.800	-362	.60377	130.92410	-00089	.00026	.02525	.00743	.79866	1.52231
.800	-178	.49171	85.34410	.01555	.00457	.02034	.00598	.79895	1.52276
.800	.628	.35631	40.82677	.03319	.00976	.01937	.00570	.79894	1.52274
.800	1.084	.32969	23.95302	.03947	.01171	-.00196	-.00059	.00263	.00179
	GRADIENT	.05569	-22.16668						

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 564  
( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.		1500/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	.500	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD		
.900	-6.987	.71954	174.99780	-.27409	-.09409	.03089	.01060	.87732	1.65058	-.02433		
.900	-6.472	.71473	174.63830	-.25464	-.08718	.03071	.01052	.88062	1.65642	-.02116		
.900	-5.967	.71324	174.19980	-.23547	-.08036	.03029	.01034	.88331	1.66118	-.01810		
.900	-5.466	.71595	173.64270	-.21571	-.07345	.03146	.01071	.88616	1.66625	-.01533		
.900	-4.970	.71349	173.04570	-.19695	-.06689	.03100	.01053	.88838	1.67023	-.01282		
.900	-4.463	.71515	172.25090	-.17814	-.06036	.03133	.01061	.89044	1.67392	-.01056		
.900	-3.959	.71412	171.29750	-.15856	-.05363	.03130	.01059	.89206	1.67685	-.00873		
.900	-3.459	.71222	170.10640	-.13871	-.04684	.03103	.01048	.89370	1.67982	-.00701		
.900	-2.950	.71161	168.47970	-.11922	-.04017	.03088	.01041	.89453	1.68133	-.00550		
.900	-2.443	.70778	166.29850	-.09941	-.03347	.03075	.01035	.89569	1.68344	-.00446		
.900	-1.934	.70410	163.08760	-.07997	-.02689	.03081	.01036	.89666	1.68519	-.00339		
.900	-1.413	.69197	158.05490	-.06017	-.02022	.03033	.01019	.89767	1.68704	-.00249		
.900	-887	.66967	149.06260	-.03977	-.01336	.03029	.01017	.89836	1.68831	-.00177		
.900	-348	.60972	130.29050	-.02064	-.00693	.02853	.00957	.89849	1.68853	-.00138		
.900	-191	.48517	84.63120	-.00112	-.00038	.02392	.00802	.89882	1.68915	-.00077		
.900	-635	.34130	40.11385	-.01481	-.00497	.01910	.00641	.89878	1.68907	-.00113		
.900	1.081	.31872	23.87386	-.03117	-.01046	.01869	.00627	.89874	1.68899	-.00109		
GRADIENT		-.05972	-22.22026	.03785	.01282	-.00186	-.00065	.00167	.00303	.00189		
RUN NO.		1485/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA		.500	PHI	=	5.00
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD		
1. 100	-7. 003	.57532	175.70740	-.24947	-.09414	.02215	.00902	.07903	2.07952	-.02565		
1. 100	-6. 483	.57289	175.38790	-.23184	-.08686	.02239	.00906	.08436	2.08657	-.02237		
1. 100	-5. 988	.57379	174.98930	-.21468	-.07953	.02302	.00929	.08660	2.09860	-.01889		
1. 100	-5. 481	.57511	174.51160	-.19712	-.07247	.02313	.00931	.08906	2.10483	-.01344		
1. 100	-4. 986	.57511	173.95460	-.18005	-.06537	.02328	.00935	.09090	2.10952	-.01132		
1. 100	-4. 483	.56481	173.27790	-.16275	-.05811	.02345	.00940	.09232	2.11314	-.00926		
1. 100	-3. 989	.56883	172.32490	-.14498	-.05085	.02370	.00948	.09379	2.11690	-.00733		
1. 100	-3. 481	.57390	171.17400	-.12713	-.04351	.02387	.00953	.09503	2.10503	-.00572		
1. 100	-2. 976	.57351	169.74570	-.10896	-.03656	.02370	.00946	.09635	2.12347	-.00458		
1. 100	-2. 479	.57391	167.84220	-.09163	-.02966	.02365	.00942	.09710	2.12538	-.00337		
1. 100	-1. 976	.57141	165.10690	-.07444	-.02278	.02331	.00928	.09761	2.12669	-.00263		
1. 100	-1. 464	.56566	160.66860	-.05722	-.01587	.02356	.00937	.09822	2.12826	-.00201		
1. 100	-1. 968	.55663	152.90410	-.03987	-.00931	.02331	.00927	.09858	2.12920	-.00163		
1. 100	-1. 460	.52959	136.23070	-.02341	-.00659	.02301	.00915	.09889	2.12999	-.00127		
1. 100	.051	.50936	92.94836	-.00970	-.00386	.02190	.00870	.09890	2.13001	-.00092		
1. 100	.536	.44782	45.54016	-.00970	-.00108	.02167	.00861	.09896	2.13015	-.00101		
1. 100	1. 029	.45368	27.27953	-.03425	-.01375	-.00021	-.00010	.00162	.00414	.00202		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM050) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1523/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	= .500	PHI	= 180.000
CPTD										
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBHQ	CPBETA	MPROBE	CPM	CPTD
1.250	-6.991	-67133	175.23430	-0.25648	-11259	.02659	.01167	1.22829	2.49101	.02621
1.250	-6.174	.66885	174.87500	-0.23822	-10425	.02753	.01205	1.23114	2.49957	-.02297
1.250	-5.978	.67058	174.43680	-0.22044	-.09608	.02785	.01214	1.23401	2.50819	-.01897
1.250	-5.471	.66524	173.95850	-0.20156	-.08764	.02784	.01211	1.23682	2.51667	-.01630
1.250	-4.973	.66593	173.32200	-0.18320	-.07951	.02737	.01188	1.23785	2.51978	-.01459
1.250	-4.471	.66925	172.52730	-0.16580	-.07177	.02793	.01209	1.23966	2.52526	-.01204
1.250	-3.966	.66747	171.61360	-0.14736	-.06367	.02835	.01225	1.24189	2.53202	-.00994
1.250	-3.462	.66360	170.46210	-0.12896	-.05561	.02814	.01213	1.24346	2.53681	-.00802
1.250	-2.958	.66500	168.87520	-0.11047	-.04755	.02768	.01192	1.24480	2.54090	-.00629
1.250	-2.451	.66287	166.73370	-0.09251	-.03977	.02775	.01193	1.24591	2.54428	-.00491
1.250	-1.948	.66054	163.64180	-0.07512	-.03225	.02736	.01174	1.24662	2.54642	-.00371
1.250	-1.431	.64925	158.80730	-0.05720	-.02454	.02740	.01176	1.24758	2.54936	-.00293
1.250	-1.916	.63361	150.17150	-0.03888	-.01667	.02732	.01171	1.24843	2.55195	-.00197
1.250	-1.390	.58602	131.95380	-0.02070	-.00887	.02623	.01124	1.24866	2.55265	-.00165
1.250	.145	.49244	86.57196	-.00222	-.00995	.02336	.01001	1.24843	2.55196	-.00153
1.250	.609	.38523	41.89609	.01370	.00587	.02007	.00859	1.24927	2.55452	-.00109
1.250	1.071	.35940	24.58661	.02976	.01274	.01964	.00841	1.24896	2.55358	-.00104
1.250	GRADIENT	-.04613	-22.11739	.03526	.01525	-.00122	-.00055	.00179	.00545	.00216
CPTD										
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBHQ	CPBETA	MPROBE	CPM	CPTD
1.400	-6.992	.65288	175.31280	-0.28438	-13144	.03506	.01620	1.37684	2.96893	.02720
1.400	-6.480	.65672	174.91430	-0.26380	-12157	.03607	.01662	1.37961	2.97846	-.02414
1.400	-5.979	.65418	174.51550	-0.24410	-11208	.03547	.01629	1.38246	2.98828	-.02046
1.400	-5.471	.65453	173.99800	-0.22424	-10271	.03527	.01616	1.38478	2.99629	-.01788
1.400	-4.975	.64905	173.44050	-0.20537	-.09379	.03515	.01605	1.38655	3.00243	-.01508
1.400	-4.472	.65393	172.64590	-0.18569	-.08456	.03565	.01624	1.38961	3.01304	-.01208
1.400	-3.973	.65373	171.73230	-.16546	-.07518	.03578	.01626	1.39091	3.01756	-.00994
1.400	-3.464	.65066	170.58900	-.14449	-.06552	.03572	.01620	1.39284	3.02425	-.00788
1.400	-2.966	.65216	169.03360	-.12343	-.05593	.03535	.01602	1.39441	3.02970	-.00701
1.400	-2.460	.64863	166.97130	-.10328	-.04673	.03439	.01556	1.39447	3.02991	-.00580
1.400	-1.949	.64446	163.91900	-.08422	-.03806	.03434	.01552	1.39547	3.03342	-.00458
1.400	1.439	.63629	159.12410	-.06503	-.02935	.03467	.01565	1.39701	3.03877	-.00314
1.400	.921	.62137	150.48830	-.04473	-.02016	.03432	.01547	1.39789	3.04186	-.00188
1.399	.399	.57516	132.50820	-.02451	-.01105	.03298	.01487	1.39771	3.04122	-.00198
1.400	.130	.49570	87.76009	-.00427	-.00192	.03056	.01377	1.39883	3.04516	-.00133
1.400	.600	.39312	42.41104	-.01356	-.00611	.02693	.01213	1.39931	3.04683	-.00085
1.400	1.059	.37908	25.45787	-.03115	.01403	.02626	.01183	1.39916	3.04629	-.00114
1.400	GRADIENT	-.04175	-22.01445	.03918	.01783	-.00138	-.00066	.00679	.00222	.00222

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM050 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1557/ 0	RN/L =	2 . 50	GRADIENT INTERVAL =	- 5 . 00 /	5 . 00	BETA	=	.500	PHI	=	180 . 000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD	CPM	CPRE	CPTD	CPM
1 . 450	- 6 . 981	.77096	174 . 80140	-.29873	-.14013	.03724	.01747	1 . 42512	3 . 13806	-.02871			
1 . 450	- 6 . 463	.76994	174 . 40240	-.27796	-.12996	.03746	.01751	1 . 42766	3 . 14712	-.02545			
1 . 450	- 5 . 961	.76636	173 . 96360	-.25684	-.11980	.03625	.01691	1 . 42954	3 . 15387	-.02302			
1 . 450	- 5 . 458	.76630	173 . 40620	-.23538	-.10946	.03705	.01723	1 . 43292	3 . 16600	-.01985			
1 . 450	- 4 . 955	.76220	172 . 76940	-.21644	-.10038	.03701	.01716	1 . 43494	3 . 17324	-.01710			
1 . 450	- 4 . 450	.76432	171 . 93480	-.19624	-.09074	.03839	.01775	1 . 43756	3 . 18268	-.01406			
1 . 450	- 3 . 950	.76397	170 . 94180	-.17502	-.08072	.03806	.01755	1 . 44000	3 . 19149	-.01152			
1 . 450	- 3 . 448	.76223	169 . 67130	-.15348	-.07063	.03800	.01749	1 . 44171	3 . 19767	-.00924			
1 . 450	- 2 . 937	.75933	168 . 00490	-.13074	-.06009	.03737	.01718	1 . 44253	3 . 20066	-.00812			
1 . 450	- 2 . 426	.75606	165 . 70470	-.10944	-.05029	.03685	.01693	1 . 44293	3 . 20211	-.00779			
1 . 450	- 1 . 907	.75008	162 . 33520	-.08890	-.04079	.03676	.01687	1 . 44427	3 . 20693	-.00630			
1 . 450	- 1 . 390	.73902	157 . 06490	-.06897	-.03157	.03738	.01711	1 . 44647	3 . 21492	-.00397			
1 . 450	- .856	.71014	147 . 75570	-.04703	-.02146	.03662	.01671	1 . 44961	3 . 22634	-.00065			
1 . 450	- .307	.63592	128 . 31040	-.02402	-.01095	.03422	.01560	1 . 45004	3 . 22791	-.00044			
1 . 449	.240	.46258	81 . 30431	-.00189	-.00086	.02760	.01257	1 . 45005	3 . 22794	.00070			
1 . 450	.659	.30250	38 . 2 . 1269	.01588	.00723	.02239	.01020	1 . 45085	3 . 23087	.00108			
1 . 449	1 . 098	.26957	22 . 40862	.03425	.01561	.02141	.00976	1 . 44984	3 . 22717	.00047			
	GRADIENT	-.07446	-22 . 46603	.04132	.01909	-.00243	-.00116	.00257	.00930	.00299			
	RUN NO.	1642/ 0	RN/L =	2 . 49	GRADIENT INTERVAL =	- 5 . 00 /	5 . 00	BETA	=	.500	PHI	=	180 . 000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD	CPM	CPRE	CPTD	CPM
1 . 470	- 6 . 982	.74726	174 . 91960	-.30567	-.14474	.03753	.01777	1 . 44062	3 . 19374	-.03906			
1 . 470	- 6 . 469	.74672	174 . 52060	-.28445	-.13424	.03879	.01831	1 . 44452	3 . 20787	-.03535			
1 . 471	- 5 . 968	.74465	174 . 08200	-.26429	-.12429	.03767	.01771	1 . 44756	3 . 21890	-.03174			
1 . 470	- 5 . 465	.74498	173 . 52460	-.24237	-.11355	.03807	.01784	1 . 45031	3 . 22889	-.02793			
1 . 470	- 4 . 967	.74381	172 . 88800	-.22029	-.10304	.03743	.01751	1 . 45213	3 . 23551	-.02620			
1 . 471	- 4 . 458	.74348	172 . 09300	-.19901	-.09292	.03768	.01759	1 . 45394	3 . 24211	-.02430			
1 . 470	- 3 . 957	.74452	171 . 10000	-.17745	-.08268	.03803	.01772	1 . 45496	3 . 24587	-.02244			
1 . 470	- 3 . 451	.74135	169 . 86920	-.15530	-.07222	.03808	.01771	1 . 45622	3 . 25047	-.02052			
1 . 470	- 2 . 941	.73795	168 . 24230	-.13275	-.06164	.03773	.01752	1 . 45820	3 . 25773	-.01879			
1 . 470	- 2 . 436	.73646	165 . 98190	-.11077	-.05145	.03779	.01755	1 . 45799	3 . 25695	-.01905			
1 . 470	- 1 . 920	.73007	162 . 69160	-.09081	-.04215	.03833	.01779	1 . 45904	3 . 26079	-.01825			
1 . 470	- 1 . 399	.71978	157 . 50050	-.07029	-.03259	.03841	.01781	1 . 45933	3 . 26186	-.01733			
1 . 470	- .872	.69716	148 . 31020	-.04814	-.02230	.03827	.01773	1 . 45982	3 . 26364	-.01669			
1 . 470	- .328	.62862	129 . 14210	-.02507	-.01162	.03633	.01683	1 . 46053	3 . 26625	-.01640			
1 . 470	- .219	.47547	82 . 69051	-.00130	-.00060	.03029	.01403	1 . 46054	3 . 26628	-.01609			
1 . 470	.650	.33043	39 . 63847	.01683	.00780	.02339	.01083	1 . 46073	3 . 26699	-.01596			
1 . 470	1 . 096	.28896	22 . 84418	.03501	.01621	.02149	.00996	1 . 46065	3 . 26668	-.01608			
	GRADIENT	-.06749	-22 . 33308	.04203	.01961	-.00215	-.00102	.00491	.00134	.00157			

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM050) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1592/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000
CPTD										
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	
1.492	-6.987	.73494	174.95890	-323339	-15410	.04074	.01941	1.46210	3.27201	-.04319
1.493	-6.470	.73059	174.59930	-30078	-14307	.04034	.01919	1.46385	3.27845	-.04113
1.493	-5.968	.73372	174.12150	-28143	-13343	.04112	.01950	1.46674	3.28910	-.03773
1.492	-5.466	.73193	173.60370	-26030	-12311	.04246	.02008	1.46875	3.29652	-.03534
1.492	-4.964	.73165	172.96710	-23875	-11265	.04245	.02003	1.47096	3.30468	-.03287
1.493	-4.460	.72709	172.21150	-21673	-10203	.04225	.01989	1.47129	3.31229	-.03065
1.492	-3.960	.72940	171.21860	-19386	-9109	.04260	.02002	1.47437	3.31731	-.02873
1.493	-3.453	.72759	169.98790	-17084	-8013	.04303	.02018	1.47642	3.32491	-.02678
1.492	-2.949	.72520	168.36100	-14801	-6939	.04317	.02024	1.47635	3.32466	-.02637
1.492	-2.440	.72386	166.10060	-12517	-5866	.04247	.01990	1.47693	3.32681	-.02602
1.493	-1.925	.71637	162.88960	-10227	-4793	.04262	.01997	1.47725	3.32799	-.02596
1.492	-1.405	.70704	157.73810	-7941	-3725	.04202	.01971	1.47758	3.32267	-.02700
1.492	-.882	.68467	148.70620	-5547	-2604	.04188	.01966	1.47537	3.32100	-.02756
1.493	-.341	.62135	129.73610	-3013	-1614	.04045	.01899	1.47580	3.32262	-.02724
1.493	.206	.48077	83.52225	-00218	-1012	.03472	.01629	1.47595	3.32316	-.02699
1.492	.634	.34781	40.90587	-01888	-887	.02775	.01303	1.47516	3.32023	-.02779
1.493	1.089	.29991	23.08179	-03947	-1854	.02489	.01169	1.47561	3.32192	-.02807
	GRADIENT	-.06327	-22.26362	.04590	.02160	-.00236	-.00111	.00043	.00159	.00049
CPTD										
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	
1.515	-6.987	.73003	174.99820	-36637	-17346	.04606	.02181	1.49525	3.39535	-.03333
1.515	-6.470	.73459	174.55990	-34342	-16209	.04541	.02143	1.49754	3.40400	-.03014
1.515	-5.968	.73294	174.12140	-31982	-15047	.04660	.02193	1.50075	3.41612	-.02699
1.516	-5.466	.72974	173.60350	-29317	-13752	.04760	.02233	1.50403	3.42855	-.02380
1.515	-4.968	.72962	172.96690	-26739	-12523	.04703	.02202	1.50471	3.43111	-.02235
1.515	-4.465	.73073	172.17210	-24350	-11406	.04736	.02218	1.50410	3.42878	-.02265
1.515	-3.955	.72836	171.21850	-22109	-10345	.04818	.02254	1.50577	3.43512	-.02135
1.516	-3.454	.72697	169.98780	-19487	-9111	.04757	.02224	1.50709	3.44014	-.02023
1.514	-2.949	.72558	168.36110	-16631	-7759	.04557	.02126	1.50743	3.44145	-.01820
1.516	-2.440	.72410	166.10060	-13862	-6457	.04513	.02102	1.51032	3.45243	-.01658
1.515	-1.930	.71827	162.88960	-11129	-5179	.04488	.02089	1.51081	3.45430	-.01571
1.516	-1.407	.70561	157.77770	-8371	-3895	.04422	.02058	1.51107	3.45530	-.01549
1.516	-.878	.68165	148.66650	-5509	-2566	.04352	.02027	1.51064	3.45364	-.01633
1.516	-.340	.62135	129.65690	-2580	-1201	.04128	.01922	1.51061	3.45353	-.01589
1.515	.205	.47969	83.52225	-0642	-2980	.03388	.01576	1.51067	3.45375	-.01517
1.516	.644	.34023	39.95534	-0281	-1387	.0281	.01061	1.51187	3.45832	-.01530
1.516	1.094	.30081	23.08177	-0497	-2315	.01911	.00890	1.51102	3.45512	-.01587
	GRADIENT	-.06327	-22.29577	.05334	.02496	-.00397	-.00187	.00122	.00465	.00127



PAGE 569  
4 OCT 91

(TCM051) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO. 1577 / 0 RN/L = 2.50 GRADIE

	CPALPH	CPOAQ	PHI	BETA	ALPHA	RADIENT
	- .05953	- .29630	- 170.75150	1.28073	- 6.960	- .07238
	- .05515	- .27527	- 170.03340	1.28103	- 6.452	- .07238
	- .05371	- .25371	- 169.23600	1.27739	- 5.945	- .07238
	- .04640	- .23243	- 168.28030	1.27621	- 5.440	- .07238
	- .04221	- .21168	- 167.12670	1.27684	- 4.938	- .07238
	- .03805	- .19105	- 165.73530	1.27557	- 4.428	- .07238
	- .03378	- .16973	- 164.02710	1.27304	- 3.920	- .07238
	- .02952	- .14837	- 161.88320	1.26963	- 3.411	- .07238
	- .02515	- .12688	- 159.14520	1.26228	- 2.900	- .07238
	- .02081	- .10485	- 155.41730	1.25375	- 2.382	- .07238
	- .01642	- .08292	- 150.22430	1.24020	- 1.863	- .07238
	- .01209	- .06092	- 142.57620	1.21341	- 1.330	- .07238
	- .00774	- .03911	- 130.81060	1.17110	- .798	- .07238
	- .00344	- .01733	- 112.31380	1.09148	- .265	- .07238
	.00020	.00100	- 87.04517	.97595	.227	- .07238
	.00380	.01919	- 60.54665	.88059	.704	- .07238
	.00764	.03863	- 41.13643	.79664	1.185	- .07238
	.00818	.04109	- 19.24837	.07238		- .07238

RUN NO.: 1467 / 0 RN/L = 2.49 GRADI

	ALPHA	BETA	PHI	CPAQ	CPLAPH
-6.976	1.20259	171.06630	-28533	-.08574	
-6.457	1.20385	170.34830	-26458	-.07930	
-5.959	1.20004	169.59070	-24423	-.07303	
-5.453	1.19777	168.67480	-22402	-.06679	
-4.956	1.19943	167.56100	-20417	-.06076	
-4.451	1.19953	166.20950	-18397	-.05464	
-3.942	1.19580	164.58060	-16402	-.04862	
-3.439	1.19379	162.51620	-14358	-.04249	
-2.925	1.18601	159.85760	-12289	-.03630	
-2.415	1.18082	156.24870	-10222	-.03018	
-1.900	1.17071	151.21430	-80182	-.02413	
-1.383	1.15418	143.80420	-60105	-.01798	
-857	1.12073	132.31590	-04073	-.01200	
-339	1.06636	114.25510	-02026	-.00597	
151	.99029	89.22423	-.00177	-.00052	
636	.92006	62.60687	.01639	.00482	
1.136	.86405	42.91860	.03537	.01040	
RADIENT	-.05129	-19.13375	.03947	.01171	

5/5.00

TA	M PROBE	CPM	CPD
.63	.57758	1.25365	.01729
.41	.58065	1.25658	.01483
.51	.58404	1.25984	.01266
.43	.58606	1.26179	.01074
.41	.58858	1.26423	.00899
.35	.59074	1.26634	.00739
.38	.59241	1.26799	.00630
.29	.59417	1.26971	.00515
.13	.59500	1.27054	.00377
.03	.59689	1.27241	.00290
.95	.59731	1.27282	.00218
.75	.59868	1.27419	.00178
.41	.59901	1.27452	.00110
.69	.59955	1.27506	.00107
.84	.59978	1.27528	.00097
.30	.59954	1.27505	.00079
.75	.59939	1.27490	.00057
.57	.00176	.00174	.00132

0/ 5.00

	CPTD	CPM	PROBE	TA
.77580	1.48856			.02339
.77941	1.49381			.02022
.78256	1.49840			.01737
.78518	1.50224			.01463
.78756	1.50574			.01247
.78987	1.50916			.01025
.79142	1.51146			.00852
.79308	1.51394			.00688
.79456	1.51615			.00526
.79600	1.51831			.00417
.79670	1.51936			.00338
.79752	1.52060			.00244
.79840	1.52192			.00190
.79890	1.52268			.00157
.79906	1.52291			.00135
.79824	1.52169			.00102
.79870	1.52238			.00095
.00179	.00268			.00181

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 570  
(TCM051) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1501/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD	CPTD	
.900	-6.972	1.21375	171.02690	-.27356	.05049	.01734	.87710	1.65021	-.02469	-.02469	
.900	-6.451	1.21397	170.30890	-.25422	.08701	.01743	.88072	1.65659	-.02092	-.02092	
.900	-5.951	1.20968	169.55120	-.23462	.08015	.01724	.88346	1.66144	-.01847	-.01847	
.900	-5.448	1.21119	168.59580	-.21502	.07324	.01725	.88599	1.66595	-.01564	-.01564	
.900	-4.948	1.21147	167.48190	-.19585	.06654	.01726	.88773	1.66906	-.01343	-.01343	
.900	-4.442	1.21029	166.13030	-.17703	.05999	.01715	.89003	1.67319	-.01082	-.01082	
.900	-3.937	1.20664	164.50140	-.15750	.05322	.01715	.89241	1.67750	-.00810	-.00810	
.900	-3.426	1.20390	162.39730	-.13784	.04654	.01685	.89387	1.68012	-.00684	-.00684	
.900	-2.918	1.19970	159.69920	-.11805	.03981	.01667	.89470	1.68163	-.00583	-.00583	
.900	-2.406	1.19405	156.05070	-.09833	.03312	.01653	.89609	1.68417	-.00449	-.00449	
.900	-1.893	1.18446	150.97680	-.07841	.02639	.01649	.89627	1.68450	-.00403	-.00403	
.900	-1.371	1.16243	143.56650	-.05867	.01972	.01628	.89791	1.68748	-.00246	-.00246	
.900	-845	1.12919	131.99910	-.03939	.01323	.01709	.89820	1.68802	-.00179	-.00179	
.900	-325	1.06967	113.85890	-.01979	.00664	.01495	.89849	1.68855	-.00124	-.00124	
.900	.165	.98660	88.78844	-.00216	-.00073	.04297	.01442	.89854	1.68863	-.00129	-.00129
.900	.650	.91530	62.21065	.01552	.00521	.04124	.01384	.89911	1.68967	-.00096	-.00096
.900	1.140	.85734	42.87923	.03366	.01129	.03916	.01314	.89910	1.68965	-.00079	-.00079
	GRADIENT	-.05429	-19.15998	.03782	.01280	-.00181	-.00064	.00173	.00314	.00193	.00193
	RUN NO.	1486/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD	CPTD	
1.100	-6.998	1.07555	171.69740	-.24902	-.10142	.04064	.01655	1.07868	2.07864	2.02573	
1.100	-6.483	1.07390	171.05870	-.23140	-.09392	.04138	.01680	1.08158	2.08592	2.02222	
1.100	-5.978	1.07453	170.30150	-.21412	-.08662	.04114	.01664	1.08414	2.09236	2.01892	
1.100	-5.476	1.06908	169.46470	-.19651	-.07929	.04136	.01669	1.08669	2.09881	2.01612	
1.100	-4.980	1.05951	168.38970	-.17936	-.07219	.04128	.01661	1.08846	2.10331	2.01367	
1.100	-4.480	1.06944	166.99930	-.16208	-.06510	.04127	.01658	1.09072	2.10906	2.01136	
1.100	-3.977	1.07139	165.41050	-.14448	-.05789	.04122	.01652	1.09222	2.11288	2.00913	
1.100	-3.470	1.07115	163.42560	-.12674	-.05070	.04112	.01645	1.09380	2.11691	2.00746	
1.100	-2.971	1.06872	160.88640	-.10884	-.04348	.04073	.01627	1.09530	2.12075	2.00586	
1.100	-2.467	1.06613	157.51550	-.09109	-.03635	.04060	.01620	1.09600	2.12255	2.00479	
1.100	-1.967	1.06506	152.75890	-.07404	-.02951	.04022	.01603	1.09688	2.12480	2.00371	
1.100	-1.466	1.05713	145.82440	-.05702	-.02270	.04036	.01607	1.09763	2.12674	2.00275	
1.100	-954	1.04297	134.73240	-.04003	-.01593	.04048	.01611	1.09809	2.12793	2.00209	
1.100	-467	1.00703	117.58260	-.02383	-.00948	.03888	.01546	1.09857	2.12917	2.00156	
1.100	.024	.99790	92.19585	-.00731	-.00291	.03946	.01569	1.09844	2.12884	2.00135	
1.100	.526	.98089	65.30116	-.00911	-.00362	.03978	.01581	1.09901	2.13031	2.00114	
1.100	1.034	.97614	46.16710	-.02605	-.01035	.03982	.01583	1.09905	2.13041	2.00098	
	GRADIENT	-.01632	-19.02541	.03420	.01373	-.00034	-.00017	.00166	.00426	.00204	

## PARAMETRIC DATA

	RUN NO.	1524/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	1.000	PHI	=	180.000
CPTD														
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	MPROBE	CPM	CPBETA	CPALPH	CPBQ	CPTD
1.250	-6.979	1.16982	171.22400	-25592	-11237	.04596	.02018	1.22791	2.48986	2.96564	-.02776			
1.250	-6.462	1.16770	170.54550	-23739	-10387	.04667	.02042	1.23130	2.50005	2.97740	-.02282			
1.250	-5.961	1.16349	169.78790	-21970	-09579	.04572	.01993	1.23425	2.50892	2.98594	-.01916			
1.250	-5.457	1.16542	168.83250	-20110	-08743	.04586	.01994	1.23666	2.51619	2.99410	-.01626			
1.250	-4.952	1.16251	167.75810	-18253	-07919	.04582	.01988	1.23780	2.51965	2.99867	-.01436			
1.250	-4.456	1.16295	166.44640	-16469	-07135	.04638	.02009	1.23922	2.52392	2.99986	-.01279			
1.250	-3.950	1.16291	164.77810	-14654	-06333	.04645	.02007	1.24135	2.53040	2.99986	-.01023			
1.250	-3.440	1.15970	162.711360	-12823	-05529	.04574	.01972	1.24344	2.53675	2.99986	-.00787			
1.250	-2.933	1.15678	160.05530	-10975	-04726	.04514	.01944	1.24425	2.53921	2.99986	-.00661			
1.250	-2.428	1.15120	156.52580	-09172	-03945	.04462	.01919	1.24527	2.54232	2.99986	-.00543			
1.250	-1.912	1.14121	151.53110	-07402	-03179	.04440	.01907	1.24666	2.54654	2.99986	-.00394			
1.250	-1.403	1.12703	144.23990	-05622	-02412	.04446	.01907	1.24756	2.54929	2.99986	-.00280			
1.250	-885	1.10003	132.87060	-03817	-01637	.04373	.01875	1.24814	2.55106	2.99986	-.00235			
1.250	-369	1.05676	114.84940	-02031	-00870	.04246	.01819	1.24837	2.55176	2.99986	-.00168			
1.250	-116	.98915	89.93744	-00333	-00142	.04088	.01751	1.24867	2.55270	2.99986	-.00140			
1.250	.605	.93581	63.24080	.01348	.00577	.03995	.01711	1.24864	2.55260	2.99986	-.00124			
1.250	1.105	.89185	43.75076	.03092	.01324	.03872	.01658	1.24886	2.55326	2.99986	-.00121			
1.250	GRADIENT	-.04220	-19.14818	.03520	.01523	-.00119	-.00055	1.24882	.00553	.00553	.00219			
CPTD														
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	MPROBE	CPM	CPBETA	CPALPH	CPBQ	CPTD
1.400	-6.981	1.15129	171.30250	-28359	-13113	.05734	.02651	1.37588	2.96564	2.99986	-.02776			
1.400	-6.465	1.15027	170.62420	-26363	-12148	.05614	.02587	1.37930	2.97740	2.99986	-.02414			
1.400	-5.962	1.15282	169.82740	-24346	-11189	.05573	.02561	1.38178	2.98594	2.99986	-.02136			
1.400	-5.459	1.15124	168.91150	-22361	-10241	.05583	.02557	1.38414	2.99410	2.99986	-.01797			
1.400	-4.960	1.15074	167.83730	-20429	-09334	.05593	.02555	1.38675	3.00312	2.99986	-.01541			
1.400	-4.458	1.15033	166.52550	-18479	-08419	.05605	.02553	1.38922	3.01166	2.99986	-.01254			
1.400	-3.954	1.14691	164.93630	-16462	-07482	.05610	.02550	1.39124	3.01868	2.99986	-.01010			
1.400	-3.445	1.14429	162.87190	-14377	-06522	.05561	.02523	1.39254	3.02319	2.99986	-.00829			
1.400	-2.939	1.14070	160.25320	-12266	-05560	.05470	.02480	1.39420	3.02898	2.99986	-.00723			
1.400	-2.434	1.13932	156.68420	-10205	-04619	.05353	.02423	1.39505	3.03195	2.99986	-.00587			
1.400	-1.925	1.13102	151.76880	-08273	-03740	.05332	.02411	1.39586	3.03478	2.99986	-.00481			
1.400	-1.409	1.11453	144.51710	-06358	-02872	.05364	.02423	1.39650	3.03699	2.99986	-.00395			
1.400	-893	1.09184	133.18750	-04387	-01979	.05297	.02389	1.39741	3.04020	2.99986	-.00264			
1.400	-383	1.04853	115.32470	-02410	-01086	.05142	.02317	1.39837	3.04355	2.99986	-.00159			
1.399	104	.99067	90.33362	-00535	-00241	.04973	.02241	1.39785	3.04171	2.99986	-.00159			
1.400	.595	.94582	63.63699	.01325	.00597	.04867	.02192	1.39904	3.04586	2.99986	-.00109			
1.400	1.095	.90654	44.22607	.03277	.01476	.04750	.02140	1.39910	3.04609	2.99986	-.00133			
1.400	GRADIENT	-.03816	-19.10748	.03913	.01781	-.00140	-.00069	1.39910	.00190	.00553	.00225			

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 572 ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1558/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	1.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD		
1.450	-6.962	1.26451	170.83030	-.29773	-.13971	.05946	.02790	1.42484	3.13706	-.02906		
1.450	-6.444	1.26349	170.11210	-.27663	-.12934	.06006	.02808	1.42752	3.14662	-.02548		
1.450	-5.941	1.26036	169.31470	-.25567	-.11921	.05823	.02715	1.43023	3.15635	-.02255		
1.449	-5.435	1.26300	168.31960	-.23461	-.10915	.05776	.02687	1.43133	3.16026	-.02049		
1.449	-4.929	1.25859	167.20540	-.21463	-.09952	.05838	.02707	1.43450	3.17167	-.01706		
1.450	-4.430	1.25960	165.81420	-.19465	-.09000	.05903	.02729	1.43796	3.18415	-.01395		
1.451	-3.918	1.25283	164.14540	-.17339	-.07997	.05902	.02722	1.44100	3.19512	-.01123		
1.450	-3.408	1.25278	161.96210	-.15182	-.06989	.05894	.02713	1.44127	3.19610	-.00967		
1.448	-2.897	1.24793	159.18460	-.12902	-.05931	.05785	.02659	1.44082	3.19447	-.00856		
1.450	-2.380	1.23836	155.49640	-.10730	-.04932	.05658	.02600	1.44309	3.20268	-.00792		
1.450	-1.862	1.22461	150.34300	-.08678	-.03983	.05650	.02593	1.44371	3.20491	-.00666		
1.451	-1.337	1.20124	142.73470	-.06631	-.03037	.05654	.02590	1.44659	3.21537	-.00447		
1.450	-806	1.15776	131.00860	-.04487	-.02050	.05596	.02557	1.44796	3.22036	-.00217		
1.450	-276	1.08359	112.51190	-.02313	-.01055	.05328	.02430	1.44977	3.22692	-.00024		
1.450	.215	.97754	87.20370	-.00269	-.00123	.04986	.02272	1.45014	3.22827	.00032		
1.450	.693	.88791	60.74480	.01685	.00768	.04714	.02149	1.44970	3.22667	.00009		
1.450	1.173	.81799	41.77007	.03674	.01677	.04428	.02021	1.44880	3.22340	-.00101		
GRADIENT		.06757	-19.25820	.04117	.01902	-.00215	-.00105	.00872	.00241	.00276		

	RUN NO.	1643/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD					
1.470	-6.969	1.24578	170.90920	-.30426	-.14419	.06010	.02848	1.44029	3.19254	-.03946					
1.470	-6.446	1.24453	170.19100	-.28329	-.13373	.06067	.02864	1.44323	3.20319	-.03553					
1.470	-5.944	1.23836	169.43310	-.26289	-.12368	.05985	.02816	1.44685	3.21633	-.03191					
1.471	-5.444	1.24306	168.43820	-.24132	-.11309	.05948	.02787	1.45118	3.23207	-.02775					
1.470	-4.938	1.24044	167.32400	-.21916	-.10448	.05914	.02765	1.45174	3.23410	-.02623					
1.484	-4.435	1.23860	165.97240	-.19395	-.09234	.05840	.02780	1.45304	3.23886	-.02451					
1.470	-3.928	1.23463	164.30370	-.17622	-.08209	.05943	.02769	1.45514	3.24650	-.02222					
1.470	-3.420	1.23336	162.16000	-.15389	-.07156	.05892	.02740	1.45663	3.25198	-.02041					
1.470	-2.905	1.22721	159.42220	-.13126	-.06093	.05855	.02718	1.45829	3.25803	-.01865					
1.470	-2.394	1.22205	155.73410	-.10892	-.05058	.05779	.02684	1.45831	3.25810	-.01890					
1.469	-1.873	1.20732	150.62030	-.08842	-.04103	.05807	.02695	1.45777	3.25615	-.01844					
1.470	-1.354	1.18874	143.09130	-.06746	-.03128	.05814	.02696	1.45913	3.26114	-.01755					
1.470	-1.420	1.14613	131.44440	-.04561	-.02113	.05743	.02661	1.46040	3.26577	-.01643					
1.469	-299	1.08229	113.10620	-.02333	-.01081	.05502	.02549	1.45950	3.26247	-.01650					
1.471	194	.98587	87.87721	-.00249	-.00115	.05145	.02383	1.46116	3.26856	-.01607					
1.470	.675	.90017	61.33905	.01726	.00799	.04798	.02222	1.46068	3.26681	-.01589					
1.470	1.158	.82850	42.08707	.03747	.01736	.04487	.02078	1.46088	3.26755	-.01604					
GRADIENT		.06214	-19.22677	.04180	.01959	-.00196	-.00098	.00140	.00514	.00157					

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM051) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.493	-6.971	1.22889	170.98790	-.32151	-.15318	.06515	.03104	1.46277	3.27447	-.04258
1.493	-6.453	1.22987	170.26990	-.29906	-.14221	.06516	.03098	1.46421	3.27979	-.04062
1.493	-5.951	1.22798	169.47260	-.27994	-.13276	.06468	.03067	1.46684	3.28945	-.03778
1.493	-5.446	1.22819	168.51710	-.25880	-.12236	.06575	.03109	1.46924	3.29831	-.03482
1.493	-4.946	1.22710	167.40310	-.23739	-.11199	.06559	.03094	1.47133	3.30605	-.03257
1.493	-4.444	1.22370	166.09100	-.21525	-.10134	.06592	.03103	1.47303	3.31236	-.03051
1.493	-3.931	1.22303	164.38290	-.19239	-.09041	.06579	.03092	1.47500	3.31967	-.02832
1.492	-3.419	1.21781	162.27860	-.16859	-.07908	.06628	.03109	1.47591	3.32301	-.02675
1.493	-2.915	1.21602	159.54100	-.14556	-.06821	.06562	.03075	1.47771	3.32971	-.02566
1.492	-2.400	1.20834	155.89240	-.12327	-.05775	.06470	.03031	1.47704	3.32722	-.02554
1.493	-1.881	1.19424	150.81830	-.10032	-.04700	.06467	.03030	1.47740	3.32858	-.02531
1.493	-1.364	1.17720	143.32900	-.07714	-.03616	.06415	.03007	1.47689	3.32667	-.02596
1.492	-8.333	1.13738	131.72170	-.05280	-.02477	.06330	.02969	1.47609	3.32368	-.02677
1.493	-.310	1.07368	113.46270	-.02788	-.01309	.06129	.02876	1.47582	3.32271	-.02699
1.492	.179	.98418	88.27344	-.00426	-.00200	.05789	.02716	1.47614	3.32286	-.02662
1.492	.661	.90498	61.69563	.01862	.00874	.05430	.02548	1.47565	3.32208	-.02692
1.493	1.147	.84518	42.56235	.04166	.01954	.05135	.02409	1.47599	3.32332	-.02682
	GRADIENT	-.05853	-19.18898	.04567	.02149	-.00209	-.00100	.00045	.00167	.00060
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.516	-6.970	1.22932	170.98790	-.36490	-.17267	.07283	.03446	1.49622	3.39900	-.03259
1.516	-6.453	1.22956	170.26990	-.34028	-.16069	.07314	.03454	1.49783	3.40509	-.03039
1.516	-5.951	1.22757	169.47260	-.31853	-.14993	.07242	.03408	1.50155	3.41915	-.02685
1.516	-5.447	1.22434	168.55650	-.29193	-.13703	.07299	.03426	1.50310	3.42501	-.02424
1.515	-4.941	1.22626	167.40300	-.26510	-.12433	.07302	.03425	1.50372	3.42734	-.02340
1.516	-4.439	1.22244	166.09090	-.24219	-.11361	.07431	.03486	1.50397	3.42832	-.02356
1.516	-3.931	1.22253	164.38290	-.22037	-.10323	.07465	.03497	1.50530	3.43335	-.02194
1.515	-3.424	1.21967	162.27870	-.19396	-.09069	.07369	.03445	1.50632	3.43723	-.02008
1.515	-2.910	1.21481	159.54100	-.16581	-.07741	.07213	.03367	1.50805	3.44381	-.01838
1.516	-2.401	1.20889	155.89250	-.13666	-.06370	.07009	.03267	1.51009	3.45155	-.01666
1.516	-1.882	1.19437	150.81830	-.10899	-.05077	.06979	.03251	1.51055	3.45329	-.01602
1.516	-1.361	1.17436	143.32890	-.08084	-.03762	.06927	.03224	1.51137	3.45645	-.01505
1.516	-.834	1.13829	131.68210	-.05195	-.02419	.06690	.03115	1.51121	3.45582	-.01543
1.516	-.309	1.07407	113.38350	-.02242	-.01044	.06253	.02912	1.51044	3.45290	-.01590
1.516	-.180	.98338	88.27344	.00408	.00190	.05635	.02625	1.51053	3.45321	-.01591
1.515	.663	.90495	61.73526	.02875	.01339	.05140	.02393	1.51031	3.45239	-.01563
1.516	1.150	.84015	42.36435	.05252	.02444	.04739	.02205	1.51166	3.45753	-.01492
	GRADIENT	-.05880	-19.21018	.03328	.02495	-.00414	-.00198	.00129	.00492	.00145

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

AA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM051) ( 04 OCT 91 )

## PARAMETRIC DATA

B11N NO 162A / 0 BN/1 = 2 49

0 / 5 00

PACH

CPBETA MPB0BE CPM CPTO

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM052) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.599	-6.941	1.77915	166.82050	-29633	-.05942	.08003	.01605	.57627	1.25241	-.01763
.600	-6.433	1.77408	165.86230	-27496	-.05508	.07935	.01590	.58013	1.25609	-.01511
.600	-5.926	1.77445	164.70650	-25285	-.05054	.07865	.01572	.58298	1.25881	-.01289
.600	-5.420	1.77567	163.35270	-23128	-.04620	.07853	.01569	.58588	1.26161	-.01103
.600	-4.907	1.76935	161.80050	-20988	-.04184	.07775	.01550	.58787	1.26354	-.00936
.600	-4.404	1.76739	159.93180	-18970	-.03778	.07751	.01544	.59047	1.26608	-.00759
.600	-3.889	1.75918	157.66680	-16885	-.03359	.07779	.01547	.59182	1.26740	-.00649
.601	-3.379	1.75591	154.80810	-14784	-.02939	.07754	.01542	.59429	1.26983	-.00488
.600	-2.863	1.74484	151.23650	-12571	-.02495	.07650	.01518	.59508	1.27063	-.00403
.601	-2.344	1.73177	146.55610	-10380	-.02061	.07605	.01510	.59697	1.27249	-.00303
.600	-1.823	1.71372	140.37120	-8193	-.01624	.07496	.01486	.59734	1.27285	-.00235
.600	-1.298	1.68052	132.00860	-5994	-.01188	.07406	.01467	.59822	1.27373	-.00173
.601	-.771	1.63681	120.47850	-3820	-.00757	.07199	.01427	.59894	1.27445	-.00134
.601	-.250	1.56213	105.30540	-1750	-.00347	.06882	.01363	.59932	1.27483	-.00105
.600	-.243	1.48488	87.43948	-17173	-.0034	.06597	.01305	.59981	1.27432	-.00092
.600	.735	1.41078	68.93887	-2180	-.00432	.06387	.01264	.59945	1.27496	-.00079
.601	1.213	1.35336	53.80408	.04050	.00802	.06189	.01226	.59960	1.27511	-.00081
	GRADIENT	-.06637	-17.15455	.04117	.00819	-.00264	-.00054	.00179	.00177	.00135
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.800	-6.959	1.70076	167.13530	-28488	-.08570	.07408	.02229	.77557	1.48824	-.02398
.800	-6.448	1.70239	166.13810	-26406	-.07923	.07403	.02221	.77918	1.49347	-.02075
.800	-5.946	1.69785	165.06140	-24394	-.07294	.07388	.02209	.78206	1.49766	-.01766
.800	-5.437	1.69282	163.78670	-22351	-.06672	.07373	.02201	.78519	1.50225	-.01513
.800	-4.933	1.69329	162.23500	-20324	-.06050	.07372	.02195	.78721	1.50522	-.01278
.800	-4.430	1.69124	160.40620	-18331	-.05444	.07296	.02167	.78943	1.50851	-.01052
.800	-3.921	1.68647	158.18110	-16337	-.04843	.07270	.02155	.79113	1.51103	-.00875
.800	-3.413	1.68269	155.40180	-14289	-.04231	.07216	.02137	.79334	1.51432	-.00699
.800	2.904	1.67569	151.90970	-12229	-.03615	.07151	.02114	.79453	1.51610	-.00556
.800	2.388	1.66451	147.34840	-10148	-.02996	.07113	.02100	.79567	1.51782	-.00437
.800	1.878	1.65405	141.28270	-8104	-.02390	.07050	.02079	.79652	1.51910	-.00338
.800	1.353	1.62690	132.9940	-6010	-.01771	.06960	.02050	.79696	1.51976	-.00278
.800	-.837	1.59353	121.70720	-3986	-.01174	.06850	.02018	.79804	1.52138	-.00211
.800	-.326	1.54767	106.65330	-1986	-.00585	.06650	.01958	.79845	1.52199	-.00170
.800	.164	1.49463	88.94586	-.00119	-.00035	.06475	.01905	.79835	1.52185	-.00138
.800	.663	1.44039	70.36594	.01803	.00531	.06350	.01870	.79924	1.52319	-.00124
.800	1.151	1.40237	55.07236	.03679	.01082	.06261	.01842	.79851	1.52209	-.00121
	GRADIENT	-.04709	-17.13171	.03959	.01175	-.00184	-.00058	.00183	.00274	.00183

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 576  
(TCM052) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1502/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	1.500	PHI	=	180.000	
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD						
MACH	.900	-6.954	1.71150	167.09590	-.27347	-.09394	.07073	.02430	.87680	1.64967					
	.900	-6.441	1.71203	166.09850	-.25370	-.08688	.07076	.02423	.87973	1.65484					
	.900	-5.938	1.70644	165.02180	-.23425	-.07997	.07095	.02422	.88285	1.66036					
	.901	-5.429	1.70924	163.66820	-.21445	-.07308	.07062	.02407	.88589	1.66578					
	.900	-4.924	1.70476	162.15590	-.19527	-.06635	.07034	.02390	.88782	1.66922					
	.900	-4.420	1.70136	160.32690	-.17613	-.05973	.07015	.02379	.89010	1.67332					
	.900	-3.913	1.69963	158.06240	-.15685	-.05308	.06954	.02353	.89180	1.67638					
	.900	-3.403	1.69402	155.28300	-.13728	-.04636	.06923	.02338	.89341	1.67928					
	.900	-2.892	1.68459	151.79070	-.11742	-.03960	.06874	.02318	.89444	1.68116					
	.900	-2.379	1.67557	147.18990	-.09760	-.03285	.06816	.02294	.89561	1.68329					
	.898	-1.862	1.65905	141.12400	-.07807	-.02621	.06748	.02265	.89516	1.68247					
	.900	-1.343	1.63668	132.80130	-.05782	-.01941	.06665	.02237	.89797	1.68758					
	.900	-825	1.60049	121.46940	-.03832	-.01288	.06534	.02196	.89829	1.68817					
	.900	-313	1.55035	106.41550	-.01915	-.00643	.06379	.02142	.89842	1.68841					
	.900	-180	1.49263	88.62880	-.00124	-.00042	.06188	.02077	.89873	1.68899					
	.900	.676	1.43408	70.08849	-.01741	-.00584	.06048	.02029	.89881	1.68913					
	.900	1.160	1.38915	54.83467	-.03487	-.01170	.05963	.02001	.89904	1.68956					
		GRADIENT	-.05051	-17.15336	.03797	.01286	-.00181	-.00065	.00177	.00321	.00197				
	RUN NO.	1509/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00							
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD						
MACH	1.100	-6.984	1.58165	167.68770	-.24887	-.10138	.06103	.02486	.07817	2.07735					
	1.100	-6.474	1.57319	166.80890	-.23123	-.09391	.05943	.02414	.08125	2.08509					
	1.100	-5.973	1.56715	165.73200	-.21400	-.08663	.05923	.02397	.08386	2.09167					
	1.100	-5.473	1.56680	164.45770	-.19639	-.07929	.05895	.02380	.08658	2.09854					
	1.100	-4.973	1.57081	162.90640	-.17880	-.07200	.05956	.02398	.08881	2.10419					
	1.100	-4.472	1.56820	161.15700	-.16149	-.06487	.05922	.02379	.09039	2.10822					
	1.100	-3.964	1.56752	158.97200	-.14450	-.05793	.05895	.02363	.09189	2.11204					
	1.100	-3.465	1.56506	156.31190	-.12638	-.05057	.05869	.02348	.09391	2.11719					
	1.100	-2.962	1.56174	152.89930	-.10827	-.04324	.05851	.02337	.09491	2.11975					
	1.100	-2.462	1.55581	148.53650	-.09085	-.03626	.05794	.02312	.09627	2.12325					
	1.100	-1.957	1.55368	142.62970	-.07352	-.02930	.05744	.02289	.09679	2.12459					
	1.100	-1.446	1.54694	134.54510	-.05624	-.02240	.05741	.02286	.09778	2.12714					
	1.100	-949	1.53052	123.49100	-.03923	-.01561	.05699	.02268	.09795	2.12758					
	1.100	-448	1.50801	108.59580	-.02233	-.00888	.05662	.02251	.09821	2.12824					
	1.100	.039	1.49606	90.88864	-.00603	-.00240	.05652	.02247	.09878	2.12972					
	1.100	.545	1.47903	72.26904	-.01091	-.00434	.05668	.02254	.09912	2.13059					
	1.100	1.051	1.47384	56.93546	-.02819	-.01120	.05684	.02258	.09913	2.13060					
	1.100	GRADIENT	-.01702	-17.16249	.03441	.01381	-.00053	-.00026	.00431	.00209	.00168				

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM052 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1525 / O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	1.500	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
1.250	-6.965	1.66661	167.29300	-25549	-11223	.06483	.02848	1.22741	2.48839					
1.250	-6.447	1.66192	166.33480	-23729	-.10385	.06467	.02830	1.23059	2.49792					
1.250	-5.947	1.66269	165.21890	-21945	-.09571	.06452	.02814	1.23371	2.50730					
1.250	-5.444	1.66437	163.90500	-20084	-.08732	.06471	.02813	1.23587	2.51382					
1.250	-4.945	1.65948	162.43250	-18207	-.07903	.06395	.02776	1.23752	2.51880					
1.250	-4.439	1.66039	160.56410	-16440	-.07121	.06382	.02764	1.23912	2.52362					
1.250	-3.929	1.65215	158.37860	-14602	-.06310	.06388	.02760	1.24096	2.52921					
1.250	-3.424	1.65108	155.59950	-12782	-.05514	.06376	.02751	1.24292	2.53515					
1.250	-2.913	1.64518	152.10740	-10940	-.04712	.06302	.02714	1.24420	2.53906					
1.250	-2.406	1.63894	147.58600	-.09116	-.03920	.06246	.02686	1.24507	2.54169					
1.250	-1.892	1.62558	141.55990	-.07325	-.03146	.06170	.02651	1.24620	2.54515					
1.250	-1.379	1.60466	133.39570	-.05563	-.02388	.06141	.02636	1.24734	2.54861					
1.250	-865	1.57617	122.10360	-.03772	-.01618	.06059	.02598	1.24729	2.54847					
1.250	-357	1.53711	107.08940	-.01983	-.00850	.05978	.02562	1.24807	2.55087					
1.250	132	1.49315	89.38206	-.00279	-.00120	.05886	.02522	1.24844	2.55199					
1.250	632	1.45387	70.80208	-.01433	-.00614	.05805	.02487	1.24841	2.55190					
1.250	1.123	1.41891	55.46881	-.03139	-.01345	.05733	.02457	1.24888	2.55332					
	GRADIENT	-.03921	-17.15499	.03520	.01523	-.00115	-.00055	.00183	.00556					

	RUN NO.	1541 / O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	1.500	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
1.399	-6.974	1.65037	167.37170	-.28293	-.13087	.07783	.03600	1.37541	2.96402					
1.400	-6.450	1.64595	166.41370	-.26296	-.12124	.07693	.03547	1.37831	2.97399					
1.400	-5.950	1.64788	165.29790	-.24291	-.11163	.07649	.03515	1.38172	2.98574					
1.400	-5.448	1.64631	164.02350	-.22298	-.10217	.07600	.03483	1.38379	2.99290					
1.400	-4.948	1.64604	162.51160	-.20336	-.09294	.07588	.03468	1.38609	3.00084					
1.400	-4.438	1.64356	160.68270	-.18411	-.08390	.07576	.03452	1.38863	3.00964					
1.400	-3.932	1.64105	158.45780	-.16425	-.07468	.07553	.03434	1.39083	3.01726					
1.401	-3.429	1.63868	155.71830	-.14338	-.06509	.07518	.03413	1.39286	3.02432					
1.400	-2.924	1.63386	152.26600	-.12249	-.05549	.07447	.03373	1.39392	3.02802					
1.400	-2.409	1.62448	147.74440	-.10130	-.04586	.07363	.03333	1.39469	3.03068					
1.400	-1.901	1.61446	141.75800	-.08177	-.03699	.07294	.03299	1.39568	3.03413					
1.400	-1.394	1.59962	133.63360	-.06269	-.02833	.07220	.03262	1.39602	3.03533					
1.400	-878	1.57100	122.42070	-.04285	-.01935	.07190	.03247	1.39736	3.03999					
1.400	-371	1.53514	107.44620	-.02344	-.01057	.07086	.03196	1.39769	3.04116					
1.400	116	1.49580	89.73880	-.00459	-.00207	.06979	.03147	1.39801	3.04228					
1.400	618	1.45513	71.07959	-.01446	-.00652	.06923	.03121	1.39832	3.04338					
1.400	114	1.43263	55.74617	-.0346	-.01509	.06815	.03073	1.39783	3.04165					
	GRADIENT	-.03539	-17.15219	.03919	.01785	-.00132	-.00067	.00185	.00644					

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.450	-6.946	1.76234	166.89930	-29668	.13926	.08087	.03796	1.42485	3.13709	-.02938
1.450	-6.426	1.75899	165.90140	-27636	.12923	.08064	.03771	1.42719	3.14545	-.02570
1.450	-5.924	1.76045	164.74570	-25474	.11883	.08049	.03755	1.43024	3.15638	-.02299
1.450	-5.415	1.75585	163.43120	-23345	.10862	.0877	.03665	1.43202	3.16277	-.02048
1.450	-4.912	1.75324	161.87930	-21311	.09893	.07880	.03658	1.43400	3.16985	-.01812
1.450	-4.399	1.74800	160.01050	-19322	.08938	.07955	.03680	1.43710	3.18102	-.01458
1.450	-3.889	1.74437	157.70610	-17275	.07970	.07951	.03668	1.43990	3.19113	-.01173
1.450	-3.380	1.73880	154.88700	-15071	.06939	.07950	.03660	1.44126	3.19603	-.00976
1.449	-2.864	1.72951	151.31550	-12822	.05896	.07882	.03624	1.44140	3.19654	-.00866
1.450	-2.351	1.71917	146.67490	-10597	.04870	.07727	.03551	1.44264	3.20103	-.00803
1.450	-1.828	1.69975	140.49000	-80538	.03921	.07610	.03495	1.44349	3.20412	-.00723
1.450	-1.305	1.66874	132.12740	-60433	.02950	.07534	.03455	1.44441	3.20744	-.00588
1.449	-778	1.62425	120.59740	-04327	.01981	.07471	.03421	1.44533	3.21077	-.00444
1.450	-261	1.56012	105.38490	-02223	.01017	.07311	.03343	1.44725	3.21775	-.00296
1.450	-230	1.48562	87.59814	-00206	.00094	.07099	.03243	1.44848	3.22223	-.00169
1.450	-724	1.41591	69.09750	-01815	.00829	.06889	.03148	1.44783	3.21989	-.00220
1.450	1.200	1.35878	53.96269	.03750	.01715	.0672	.03052	1.44722	3.21766	-.00318
	GRADIENT	-0.06262	-17.18050	.04115	.01902	-.00202	-.00101	.00209	.00757	.00239
RUN NO.	1644/ 0	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.470	-6.949	1.74228	166.97800	-30295	.14355	.08273	.03920	1.43981	3.19081	-.03948
1.471	-6.430	1.74017	165.98030	-28197	.13325	.08222	.03885	1.44348	3.20410	-.03645
1.471	-5.929	1.73883	164.86420	-26209	.12333	.08190	.03854	1.44728	3.21786	-.03193
1.470	-5.425	1.73726	163.54990	-24052	.11280	.08112	.03805	1.44945	3.22577	-.02876
1.470	-4.917	1.73444	161.99800	-21822	.10213	.08048	.03766	1.45168	3.23390	-.02661
1.470	-4.411	1.72871	160.16880	-19682	.09192	.08022	.03747	1.45308	3.23899	-.02457
1.470	-3.902	1.72675	157.86450	-17483	.08151	.07987	.03724	1.45495	3.24581	-.02272
1.470	-3.393	1.72341	155.04560	-15281	.07110	.07986	.03716	1.45628	3.25070	-.02072
1.471	-2.874	1.71316	151.47400	-13029	.06051	.07953	.03693	1.45884	3.26005	-.01855
1.470	-2.359	1.69850	146.91260	-10752	.04990	.07833	.03636	1.45919	3.26135	-.01816
1.471	-1.842	1.68345	140.76740	-08646	.04013	.07758	.03600	1.45962	3.26291	-.01801
1.470	-1.320	1.65657	132.40490	-06549	.03037	.07733	.03587	1.45951	3.26251	-.01748
1.470	-798	1.61448	120.99370	-04394	.02037	.07643	.03543	1.46000	3.26431	-.01706
1.470	-282	1.55608	105.82090	-02232	.01034	.07469	.03461	1.45995	3.26411	-.01663
1.470	-210	1.48821	88.03418	-00193	.00090	.07241	.03354	1.46083	3.26735	-.01605
1.470	-705	1.42468	69.49388	-01843	.00854	.07001	.03243	1.46057	3.26640	-.01613
1.471	1.187	1.37626	54.31934	-03798	.01759	.06786	.03143	1.46141	3.26949	-.01589
	GRADIENT	-0.05744	-17.15738	.04198	.01959	-.00192	-.00095	.00523	.00143	.00160

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM052) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1594/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	1.500	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD						
1.493	-6.952	1.72613	167.05680	- .32081	- .15287	.08780	.04184	1.46246	3.27336					
1.493	-6.438	1.72563	166.05930	- .29818	- .14177	.08720	.04146	1.46433	3.28023					
1.493	-5.932	1.72314	164.94300	- .27740	- .13181	.08799	.04181	1.46507	3.28292					
1.493	-5.429	1.72242	163.62890	- .25791	- .12206	.08807	.04168	1.46872	3.29641					
1.493	-4.921	1.72013	162.07700	- .23534	- .11107	.08801	.04153	1.47163	3.30717					
1.493	-4.416	1.71574	160.24790	- .21316	- .10035	.08839	.04161	1.47313	3.31272					
1.493	-3.907	1.71265	157.98330	- .19045	- .08952	.08840	.04155	1.47530	3.32077					
1.493	-3.399	1.70988	155.16430	- .16732	- .07850	.08818	.04137	1.47617	3.32401					
1.493	-2.886	1.70098	151.63250	- .14390	- .06743	.08808	.04127	1.47718	3.32777					
1.493	-2.367	1.68705	147.03140	- .12106	- .05670	.08729	.04088	1.47799	3.33075					
1.493	-1.856	1.67564	140.92600	- .09813	- .04594	.08648	.04049	1.47812	3.33125					
1.493	-1.331	1.64716	132.60310	- .07502	- .03513	.08623	.04038	1.47786	3.33028					
1.493	-811	1.60759	121.23160	- .05142	- .02409	.08485	.03974	1.47779	3.33002					
1.492	-298	1.55806	106.09840	- .02690	- .01261	.08327	.03902	1.47685	3.32651					
1.492	-194	1.48996	88.31168	- .00371	- .00174	.08076	.03786	1.47659	3.32557					
1.493	.691	1.43061	69.73174	- .01939	- .00909	.07829	.03672	1.47687	3.32658					
1.493	1.173	1.38195	54.55721	- .04215	- .01975	.07626	.03572	1.47760	3.32930					
GRADIENT		-.05395	-17.16154	.04545	.02139	-.00186	-.00091	.00068	.00251					
	RUN NO.	1610/ 0	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00						
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD						
1.516	-6.957	1.72774	167.05700	- .36457	- .17263	.09956	.04714	1.49569	3.39703					
1.516	-6.438	1.72633	166.05940	- .34157	- .16119	.09834	.04641	1.49882	3.40882					
1.516	-5.933	1.72391	164.94310	- .31661	- .14928	.09861	.04649	1.49950	3.41138					
1.516	-5.429	1.72268	163.62890	- .29081	- .13656	.09871	.04635	1.50363	3.42701					
1.516	-4.921	1.72076	162.07710	- .26349	- .12358	.09877	.04632	1.50473	3.43119					
1.516	-4.415	1.71584	160.24790	- .23867	- .11208	.09933	.04665	1.50286	3.42410					
1.517	-3.908	1.71250	157.98330	- .21765	- .10208	.10038	.04708	1.50524	3.43313					
1.517	-3.400	1.71050	155.16440	- .19316	- .09037	.09931	.04646	1.50735	3.44113					
1.516	-2.882	1.69904	151.63240	- .16479	- .07697	.09724	.04542	1.50859	3.44585					
1.516	-2.372	1.68922	147.07110	- .13572	- .06330	.09496	.04429	1.50981	3.45051					
1.516	-1.852	1.67312	140.92600	- .10718	- .04995	.09346	.04355	1.51043	3.45285					
1.516	-1.332	1.64668	132.64270	- .07946	- .03702	.09277	.04322	1.51080	3.45427					
1.516	-811	1.60810	121.23160	- .05105	- .02377	.09100	.04237	1.51116	3.45563					
1.516	-296	1.55391	106.09840	- .02247	- .01046	.08736	.04067	1.51156	3.45715					
1.516	-195	1.49050	88.35129	- .00318	- .00148	.08292	.03861	1.51129	3.45612					
1.516	.689	1.42700	69.81104	- .02885	- .01343	.07978	.03715	1.51116	3.45562					
GRADIENT		1.173	1.38271	54.59680	.05290	.02462	.03604	1.51137	3.45645					
		-.05424	-17.15305	.05286	.02477	-.00372	-.00180	.00134	.00509					

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 580

( TCM052 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPIID
1.542	-6.952	1.72548	167.05670	.34251	-.16187	.09613	.04543	3.52249	-.02365
1.542	-6.433	1.72385	166.05910	-.30748	-.14507	.09271	.04374	3.52893	-.02195
1.542	-5.932	1.72298	164.94300	-.27634	-.13027	.09082	.04282	3.53103	-.02125
1.542	-5.429	1.72209	163.62880	-.24702	-.11644	.08858	.04176	3.53054	-.02128
1.542	-4.926	1.72161	162.07710	-.21865	-.10308	.08567	.04039	1.53018	3.52861
1.542	-4.416	1.71545	160.24790	-.19114	-.09009	.08328	.03925	1.53067	-.02124
1.542	-3.906	1.71496	157.94370	-.16479	-.07759	.08011	.03772	1.53147	3.53359
1.541	-3.400	1.71003	155.16430	-.13916	-.06549	.07565	.03560	1.53155	3.53390
1.542	-2.882	1.69871	151.63240	-.11429	-.05374	.07002	.03292	1.53259	3.53794
1.542	-2.367	1.68716	147.03140	-.08961	-.04212	.06426	.03021	1.53304	3.53966
1.541	-1.853	1.67199	140.92590	-.06990	-.03288	.06183	.02908	1.53170	3.53446
1.541	-1.332	1.64694	132.60310	-.05126	-.02411	.06067	.02853	1.53200	3.53562
1.541	-.811	1.60825	121.19200	-.03178	-.01494	.05851	.02752	1.53168	3.53440
1.541	-.296	1.55388	106.05870	-.01429	-.00672	.05617	.02641	1.53190	3.53525
1.541	-.195	1.49053	88.31166	.00248	.00117	.05413	.02544	1.53207	3.53590
1.541	.690	1.42672	69.77139	.01903	.00895	.05196	.02443	1.53180	3.53485
1.541	1.172	1.38297	54.59680	.03507	.01649	.05036	.02368	1.53184	3.53504
		GRADIENT	-.05430	-.17.15011	.04109	-.00600	-.00284	.00017	.00018

GRADIENT INTERVAL = -5.00/ 5.00

BETA = 1.500 PHI = 180.000

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM053) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1579/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	2.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD	CPM		
.600	-6.923	2.27637	163.00830	-29526	-05934	-10055	.02021	.57649	1.25262	-0.01803		
.599	-6.410	2.26759	161.81010	-27416	-05491	-10017	.02006	.57914	1.25514	-0.01565		
.599	-5.903	2.26678	160.37480	-25230	-05045	-10067	.02013	.58226	1.25812	-0.01341		
.599	-5.396	2.26253	158.74140	-23070	-04602	-10025	.02000	.58450	1.26028	-0.01152		
.600	-4.888	2.26103	156.79140	-20911	-04167	-10005	.01994	.58735	1.26304	-0.00960		
.600	-4.378	2.25487	154.52440	-18813	-03745	-09940	.01979	.58956	1.26519	-0.00801		
.600	-3.864	2.24662	151.78210	-16741	-03332	-09868	.01964	.59146	1.26705	-0.00683		
.600	-3.356	2.24139	148.44620	-14655	-02910	-09876	.01961	.59289	1.26845	-0.00547		
.600	-2.837	2.22844	144.31800	-12543	-02488	-09794	.01943	.59490	1.27044	-0.00399		
.600	-2.315	2.20948	139.16030	-10369	-02057	-09655	.01915	.59595	1.27148	-0.00339		
.600	-1.797	2.18727	132.65660	-08125	-01611	-09532	.01890	.59663	1.27215	-0.00285		
.600	-1.273	2.15124	124.37100	-05936	-01176	-09388	.01861	.59766	1.27317	-0.00213		
.600	-756	2.11223	113.98710	-03826	-00757	-09221	.01825	.59799	1.27350	-0.00156		
.600	-239	2.04868	101.46480	-01733	-00343	-08976	.01777	.59798	1.27349	-0.00169		
.600	-251	1.98864	87.83380	-00178	.00035	.08745	.01730	.59877	1.27427	-0.00100		
.600	-753	1.93169	73.64769	.02246	.00445	.08580	.01698	.59860	1.27411	-0.00129		
.600	1.235	1.87729	61.24371	.04213	.00833	.08418	.01664	.59920	1.27471	-0.00063		
.600	GRADIENT	-0.6217	-15.49627	.04115	.00819	-0.00267	-.00055	.00181	.00178	.00137		
	RUN NO.	1470/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00						
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD	CPM		
.800	-6.946	2.19894	163.32350	-28408	-08548	.09575	.02881	.77521	1.48771	-0.02432		
.800	-6.433	2.19221	162.12550	-26370	-.07912	.09421	.02827	.77810	1.49190	-0.02141		
.800	-5.930	2.19150	160.73010	-24360	-.07288	.09368	.02803	.78137	1.49665	-0.01828		
.800	-5.424	2.18637	159.13650	-22313	-.06663	.09332	.02787	.78430	1.50094	-0.01580		
.800	-4.919	2.19012	157.18690	-20239	-.06029	.09330	.02779	.78685	1.50470	-0.01324		
.800	-4.411	2.18358	154.95960	-18254	-.05420	.09330	.02770	.78847	1.50709	-0.01097		
.800	-3.907	2.18183	152.25750	-16238	-.04818	.09277	.02753	.79087	1.51065	-0.00926		
.800	-3.391	2.17314	148.96110	-14190	-.04200	.09249	.02738	.79244	1.51299	-0.00738		
.800	-2.882	2.16180	144.95200	-12165	-.03597	.09163	.02709	.79399	1.51530	-0.00604		
.800	-2.369	2.14953	139.87390	-10095	-.02984	.09074	.02682	.79550	1.51756	-0.00493		
.800	-1.855	2.13330	133.44980	-.08044	-.02374	.08967	.02647	.79644	1.51898	-0.00386		
.800	-1.340	2.10993	125.24380	-.05967	-.01759	.08882	.02618	.79689	1.51965	-0.00302		
.800	-826	2.07822	114.97890	-.03978	-.01172	.08772	.02585	.79798	1.52130	-0.00223		
.800	-319	2.04056	102.57570	-.01977	-.00582	.08658	.02549	.79810	1.52148	-0.00188		
.800	-174	1.99417	88.94470	-.00081	-.00024	.08517	.02507	.79861	1.52224	-0.00152		
.800	.677	1.95201	74.75851	.01841	.00542	.08419	.02478	.79843	1.52196	-0.00148		
.800	1.167	1.91904	62.27493	.03770	.01109	.08299	.02441	.79842	1.52196	-0.00122		
.800	GRADIENT	-0.4462	-15.49781	.03954	.01178	-.00178	-.00058	.00191	.00285	.00191		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM053 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	GRADIENT INTERVAL = -5.00/ 5.00		
											BETA = 2.000	PHI = 180.000	
.899	-6.941	2.20909	163.28390	-.27297	.09377	.09070	.03116	.87606	1.64839	-.02535			
.900	-6.424	2.20593	162.04650	-.25319	-.08676	.09033	.03095	.87958	1.65457	-.02217			
.900	-5.920	2.20334	160.65090	-.23397	-.07990	.09006	.03075	.88208	1.65900	-.01903			
.900	-5.411	2.20074	159.01770	-.21410	-.07296	.09017	.03073	.88496	1.66411	-.01642			
.900	-4.911	2.20098	157.10760	-.19458	-.06615	.08953	.03044	.88745	1.66856	-.01385			
.900	-4.400	2.19317	154.88030	-.17509	-.05938	.08947	.03034	.88958	1.67238	-.01142			
.900	-3.890	2.18674	152.17790	-.15581	-.05272	.08936	.03023	.89113	1.67518	-.00945			
.900	-3.382	2.18144	148.88170	-.13629	-.04604	.08885	.03001	.89263	1.67788	-.00780			
.900	-2.874	2.17304	144.83310	-.11662	-.03933	.08822	.02975	.89427	1.68085	-.00616			
.900	-2.354	2.15715	139.71530	-.09702	-.03268	.08699	.02930	.89538	1.68288	-.00493			
.900	-1.843	2.14131	133.29110	-.07734	-.02603	.08605	.02896	.89650	1.68491	-.00376			
.900	-1.326	2.11502	125.08510	-.05730	-.01926	.08520	.02864	.89716	1.68611	-.00289			
.900	-8.111	2.08038	114.78050	-.03814	-.01281	.08394	.02820	.89762	1.68695	-.00232			
.900	-303	2.03888	102.33770	-.01900	-.00638	.08257	.02774	.89817	1.68796	-.00199			
.900	-189	1.99377	88.70671	-.00117	-.00039	.08127	.02729	.89815	1.68792	-.00184			
.900	.691	1.94809	74.52052	-.01747	.00586	.08036	.02697	.89847	1.68850	-.00138			
.900	1.181	1.91271	62.07661	.03594	.01206	.07915	.02657	.89866	1.68885	-.00134			
	GRADIENT	-.04719	-15.51432	.03789	.01284	-.00183	-.00067	.00178	.00323	.00197			
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	GRADIENT INTERVAL = -5.00/ 5.00		
RUN NO.	1510/ 0	RN/L = 2.50	BETA = 2.50	PHI = 180.000									
1.099	-6.983	2.07219	163.87520	-.24828	-.10118	.07776	.03169	.07749	2.07565	-.02666			
1.100	-6.469	2.06876	162.67760	-.23091	-.09384	.07751	.03150	.08055	2.08358	-.02342			
1.100	-5.966	2.06721	161.32200	-.21362	-.08650	.07733	.03131	.08330	2.09026	-.01992			
1.100	-5.464	2.06572	159.72870	-.19620	-.07925	.07654	.03092	.08557	2.09597	-.01729			
1.100	-4.962	2.06653	157.85850	-.17854	-.07193	.07639	.03077	.08836	2.10305	-.01434			
1.100	-4.465	2.06769	155.67160	-.16110	-.06476	.07644	.03072	.09010	2.10748	-.01213			
1.100	-3.960	2.06380	153.04880	-.14370	-.05764	.07639	.03064	.09141	2.11081	-.01020			
1.100	-3.455	2.05691	149.87160	-.12606	-.05047	.07628	.03054	.09311	2.11514	-.00819			
1.100	-2.954	2.05534	145.90290	-.10813	-.04321	.07581	.03030	.09457	2.11890	-.00636			
1.100	-2.451	2.05296	140.90460	-.09066	-.03617	.07524	.03002	.109574	2.12189	-.00490			
1.100	-1.947	2.04627	134.67900	-.07319	-.02919	.07478	.02982	.109695	2.12499	-.00413			
1.100	-1.446	2.03455	126.71120	-.05576	-.02221	.07423	.02957	.109754	2.12651	-.00305			
1.100	-940	2.01342	116.52580	-.03865	-.01539	.07385	.02940	.109822	2.12827	-.00239			
1.100	-445	2.00255	104.20230	-.02180	-.00867	.07353	.02925	.109805	2.12782	-.00199			
1.100	.045	2.00009	90.57158	-.00542	-.00215	.07358	.02926	.109841	2.12874	-.00144			
1.100	.556	1.98853	76.34561	.01156	.00460	.07381	.02936	.109920	2.13079	-.00135			
1.100	1.060	1.97407	63.74290	.02893	.01150	.07357	.02924	.109873	2.12957	-.00106			
	GRADIENT	-.01610	-15.55806	.03447	.01384	-.00060	-.00030	.00175	.00448	.00216			

## PARAMETRIC DATA

	RUN NO.	1526/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/ 5.00	BETA	=	2.000	PHI	=	180.000
<b>MACH</b>	<b>ALPHA</b>	<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBETA</b>	<b>MPROBE</b>	<b>CPM</b>	<b>CPTD</b>			
1.250	-6.957	2.16334	163.48100	-25488	-11204	.08338	.03665	1.22705	2.48729	-.02767			
1.250	-6.440	2.15728	162.28310	-23683	-10374	.03648	.03648	1.22997	2.49605	-.02404			
1.250	-5.934	2.16013	160.84830	-21889	-.09554	.08334	.03638	1.23326	2.50593	-.02028			
1.250	-5.430	2.15662	159.25470	-20105	-.08748	.08208	.03571	1.23552	2.51275	-.01720			
1.250	-4.925	2.15653	157.34470	-18182	-.07894	.08204	.03562	1.23733	2.51821	-.01503			
1.250	-4.420	2.15166	155.11760	-16377	-.07096	.08134	.03524	1.23873	2.52244	-.01306			
1.250	-3.916	2.14671	152.45500	-14564	-.06299	.08149	.03525	1.24089	2.52899	-.01100			
1.250	-3.403	2.14124	149.58800	-12729	-.05496	.08147	.03518	1.24240	2.53357	-.00932			
1.250	-2.896	2.13326	145.15000	-10894	-.04694	.08092	.03487	1.24340	2.53663	-.00742			
1.250	-2.387	2.12372	140.11180	-09095	-.03913	.07991	.03438	1.24492	2.54126	-.00591			
1.250	-1.874	2.10927	133.68770	-07290	-.03133	.07901	.03395	1.24577	2.54382	-.00463			
1.250	-1.365	2.09030	125.56110	-05498	-.02361	.07838	.03366	1.24656	2.54626	-.00401			
1.250	-853	2.06234	115.29630	-03717	-.01595	.07760	.03330	1.24724	2.54833	-.00311			
1.250	-349	2.03452	102.93290	-01961	-.00841	.07702	.03302	1.24783	2.55014	-.00236			
1.250	-139	2.00026	89.38113	-00250	-.00107	.07623	.03268	1.24815	2.55110	-.00219			
1.250	.644	1.99549	75.15524	-01458	-.00625	.07570	.03245	1.24768	2.54965	-.00221			
1.250	1.138	1.93371	62.63202	-03222	-.01381	.07491	.03210	1.24799	2.55062	-.00187			
1.250	GRADIENT	-.03628	-15.53084	.03527	.01527	-.00123	-.00060	.00177	.00540	.00217			
	RUN NO.	1543/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/ 5.00						
<b>MACH</b>	<b>ALPHA</b>	<b>BETA</b>	<b>PHI</b>	<b>CPAQ</b>	<b>CPALPH</b>	<b>CPBQ</b>	<b>CPBETA</b>	<b>MPROBE</b>	<b>CPM</b>	<b>CPTD</b>			
1.400	-6.961	2.14716	163.55980	-28232	-13072	.09477	.04388	1.37461	2.96129	-.02915			
1.400	-6.443	2.14577	162.32260	-26298	-12134	.09385	.04330	1.37817	2.97351	-.02542			
1.400	-5.938	2.14496	160.92720	-24288	-11171	.09317	.04285	1.38128	2.98423	-.02212			
1.400	-5.435	2.14201	159.33380	-22271	-10214	.09224	.04230	1.38314	2.90655	-.01933			
1.400	-4.931	2.13928	157.46320	-20289	-09278	.09194	.04205	1.38586	3.00003	-.01636			
1.400	-4.431	2.13808	155.23640	-18355	-.08371	.09187	.04190	1.38818	3.00807	-.01364			
1.400	-3.920	2.13543	152.53430	-16368	-.07449	.09189	.04182	1.38994	3.01416	-.01143			
1.400	-3.416	2.12893	149.31740	-14315	-.06499	.09204	.04179	1.39208	3.02160	-.00905			
1.400	-2.903	2.12165	145.26890	-12231	-.05543	.09088	.04119	1.39372	3.02732	-.00718			
1.400	-2.397	2.11223	140.27040	-10163	-.04602	.08967	.04061	1.39408	3.02856	-.00648			
1.400	-1.890	2.10203	133.88600	-08177	-.03699	.08851	.04004	1.39489	3.03138	-.00540			
1.400	-1.377	2.08220	125.75940	-06190	-.02799	.08751	.03957	1.39610	3.03561	-.00483			
1.400	-1.867	2.05684	115.53430	-04248	-.01920	.08669	.03917	1.39663	3.03747	-.00419			
1.400	-1.364	2.03244	103.17090	-02279	-.01029	.08598	.03882	1.39679	3.03803	-.00339			
1.400	-1.27	1.99650	89.57956	-.00402	-.00181	.08522	.03846	1.39710	3.03910	-.00317			
1.400	.630	1.97006	75.39325	.01486	.00671	.08462	.03820	1.39728	3.03972	-.00333			
1.400	1.128	1.94552	62.83025	.03415	.01541	.08379	.03780	1.39720	3.03945	-.00273			
1.400	GRADIENT	-.03262	-15.52715	.03924	.01788	-.00153	-.00077	.00178	.00621	.00208			

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 584

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM053) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1560/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = 2.000	PHI = 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.450	-6.926	2.25709	163.08690	.29570	.13883	.10147
1.450	-6.412	2.25327	161.84930	.27540	.12888	.10170
1.450	-5.899	2.25052	160.41390	.25474	.11885	.10040
1.450	-5.393	2.24639	158.78050	.23299	.10848	.09688
1.450	-4.889	2.24702	156.83070	.21227	.09858	.09886
1.449	-4.381	2.24071	154.56370	.19255	.08910	.09970
1.450	-3.867	2.23381	151.82160	.17203	.07944	.10024
1.450	-3.354	2.22631	148.48550	.15012	.06916	.09888
1.450	-2.838	2.21192	144.39700	.12789	.05885	.09099
1.450	-2.321	2.19801	139.23960	.10593	.04867	.09778
1.450	-1.801	2.17370	132.73590	.08442	.03878	.09589
1.450	-1.283	2.14448	124.45050	.06332	.02907	.09483
1.449	-7.763	2.09993	114.06650	.04231	.01940	.09352
1.451	-2.252	2.04648	101.58390	.02172	.00995	.09214
1.450	.240	1.98885	87.95296	.00189	-.00086	.09043
1.449	.738	1.93005	73.80650	.0813	.00831	.08887
1.450	1.223	1.88474	61.40239	.03790	.01736	.08711
	GRADIENT	-.05915	-15.51060	.04114	.01903	-.00215
	RUN NO.	1645/ 0	RN/L = 2.49	GRADIENT INTERVAL = -5.00/ 5.00		

RUN NO. 1645/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1560/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = 2.000	PHI = 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.470	-6.935	2.23906	163.16590	.30193	.14318	.10340
1.470	-6.417	2.23461	161.92830	.28147	.13299	.10359
1.470	-5.911	2.23096	160.53260	.26095	.12289	.10322
1.471	-5.403	2.23228	158.85990	.24000	.11259	.10299
1.470	-4.897	2.22791	156.94940	.21779	.10192	.10157
1.484	-4.389	2.22313	154.68260	.19239	.09164	.09922
1.485	-3.881	2.21663	151.98010	.17081	.08123	.09942
1.484	-3.365	2.20889	148.64400	.14916	.07079	.0906
1.484	-2.855	2.19732	144.59540	.12693	.06013	.08865
1.470	-2.336	2.18057	139.47750	.10741	.04983	.0909
1.484	-1.821	2.16369	132.97400	.08381	.03965	.09539
1.471	-1.304	2.13697	124.72820	.06407	.02972	.09662
1.470	-.785	2.09652	114.38390	.04301	.01994	.09563
1.469	-.274	2.04878	101.90130	.02189	.01014	.09397
1.470	.219	1.99580	88.27032	.00158	.00073	.09226
1.470	.719	1.94242	74.12378	.01863	.00863	.09065
1.470	1.206	1.89515	61.64040	.03858	.01787	.08865
	GRADIENT	-.05376	-15.51418	.04154	.01962	-.00185
	RUN NO.	1645/ 0	RN/L = 2.49	GRADIENT INTERVAL = -5.00/ 5.00		

	RUN NO.	1560/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = 2.000	PHI = 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.470	-6.935	2.23906	163.16590	.30193	.14318	.10340
1.470	-6.417	2.23461	161.92830	.28147	.13299	.10359
1.470	-5.911	2.23096	160.53260	.26095	.12289	.10322
1.471	-5.403	2.23228	158.85990	.24000	.11259	.10299
1.470	-4.897	2.22791	156.94940	.21779	.10192	.10157
1.484	-4.389	2.22313	154.68260	.19239	.09164	.09922
1.485	-3.881	2.21663	151.98010	.17081	.08123	.09942
1.484	-3.365	2.20889	148.64400	.14916	.07079	.0906
1.484	-2.855	2.19732	144.59540	.12693	.06013	.08865
1.470	-2.336	2.18057	139.47750	.10741	.04983	.0909
1.484	-1.821	2.16369	132.97400	.08381	.03965	.09539
1.471	-1.304	2.13697	124.72820	.06407	.02972	.09662
1.470	-.785	2.09652	114.38390	.04301	.01994	.09563
1.469	-.274	2.04878	101.90130	.02189	.01014	.09397
1.470	.219	1.99580	88.27032	.00158	.00073	.09226
1.470	.719	1.94242	74.12378	.01863	.00863	.09065
1.470	1.206	1.89515	61.64040	.03858	.01787	.08865
	GRADIENT	-.05376	-15.51418	.04154	.01962	-.00185
	RUN NO.	1645/ 0	RN/L = 2.49	GRADIENT INTERVAL = -5.00/ 5.00		

	RUN NO.	1560/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = 2.000	PHI = 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.470	-6.935	2.23906	163.16590	.30193	.14318	.10340
1.470	-6.417	2.23461	161.92830	.28147	.13299	.10359
1.470	-5.911	2.23096	160.53260	.26095	.12289	.10322
1.471	-5.403	2.23228	158.85990	.24000	.11259	.10299
1.470	-4.897	2.22791	156.94940	.21779	.10192	.10157
1.484	-4.389	2.22313	154.68260	.19239	.09164	.09922
1.485	-3.881	2.21663	151.98010	.17081	.08123	.09942
1.484	-3.365	2.20889	148.64400	.14916	.07079	.0906
1.484	-2.855	2.19732	144.59540	.12693	.06013	.08865
1.470	-2.336	2.18057	139.47750	.10741	.04983	.0909
1.484	-1.821	2.16369	132.97400	.08381	.03965	.09539
1.471	-1.304	2.13697	124.72820	.06407	.02972	.09662
1.470	-.785	2.09652	114.38390	.04301	.01994	.09563
1.469	-.274	2.04878	101.90130	.02189	.01014	.09397
1.470	.219	1.99580	88.27032	.00158	.00073	.09226
1.470	.719	1.94242	74.12378	.01863	.00863	.09065
1.470	1.206	1.89515	61.64040	.03858	.01787	.08865
	GRADIENT	-.05376	-15.51418	.04154	.01962	-.00185
	RUN NO.	1645/ 0	RN/L = 2.49	GRADIENT INTERVAL = -5.00/ 5.00		

	RUN NO.	1560/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = 2.000	PHI = 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.470	-6.935	2.23906	163.16590	.30193	.14318	.10340
1.470	-6.417	2.23461	161.92830	.28147	.13299	.10359
1.470	-5.911	2.23096	160.53260	.26095	.12289	.10322
1.471	-5.403	2.23228	158.85990	.24000	.11259	.10299
1.470	-4.897	2.22791	156.94940	.21779	.10192	.10157
1.484	-4.389	2.22313	154.68260	.19239	.09164	.09922
1.485	-3.881	2.21663	151.98010	.17081	.08123	.09942
1.484	-3.365	2.20889	148.64400	.14916	.07079	.0906
1.484	-2.855	2.19732	144.59540	.12693	.06013	.08865
1.470	-2.336	2.18057	139.47750	.10741	.04983	.0909
1.484	-1.821	2.16369	132.97400	.08381	.03965	.09539
1.471	-1.304	2.13697	124.72820	.06407	.02972	.09662
1.470	-.785	2.09652	114.38390	.04301	.01994	.09563
1.469	-.274	2.04878	101.90130	.02189	.01014	.09397
1.470	.219	1.99580	88.27032	.00158	.00073	.09226
1.470	.719	1.94242	74.12378	.01863	.00863	.09065
1.470	1.206	1.89515	61.64040	.03858	.01787	.08865
	GRADIENT	-.05376	-15.51418	.04154	.01962	-.00185
	RUN NO.	1645/ 0	RN/L = 2.49	GRADIENT INTERVAL = -5.00/ 5.00		

	RUN NO.	1560/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = 2.000	PHI = 180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ
1.470	-6.935	2.23906	163.16590	.30193	.14318	.10340
1.470	-6.417	2.23461	161.92830	.28147	.13299	.10359
1.470	-5.911	2.23096	160.53260	.26095	.12289	.10322
1.471	-5.403	2.23228	158.85990	.24000	.11259	.10299
1.470	-4.897	2.22791	156.94940	.21779	.10192	.10157
1.484	-4.389	2.22313	154.68260	.19239	.09164	.09922
1.485	-3.881	2.21663	151.98010	.17081	.08123</td	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 585  
 ( TCM053 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1595/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	2.000	PHI	=	180 000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD			
1.493	-6.939	2.22314	163.24480	-31942	-15226	-11025	.05256	1.46192	3.2135	.04308		
1.493	-6.426	2.22087	162.00740	-29729	-14133	-10976	.05218	1.46518	3.28336	-.04007		
1.493	-5.914	2.21976	160.57210	-27678	-13134	-10984	.05212	1.46620	3.28712	-.03816		
1.493	-5.410	2.21376	158.97830	-25667	-12138	-11029	.05216	1.46953	3.29939	-.03466		
1.493	-4.904	2.21097	157.06800	-23453	-11067	-11028	.05204	1.47116	3.30541	-.03253		
1.493	-4.395	2.20708	154.80120	-21217	-09991	-11097	.05225	1.47372	3.31491	-.03001		
1.493	-3.887	2.20478	152.05930	-18915	-08891	-11100	.05217	1.47510	3.32000	-.02841		
1.493	-3.373	2.19525	148.76290	-16587	-07786	-11088	.05205	1.47624	3.32425	-.02678		
1.493	-2.863	2.18492	144.71420	-14230	-06671	-11031	.05171	1.47708	3.32739	-.02553		
1.493	-2.350	2.17330	139.59660	-11897	-05577	-10917	.05118	1.47712	3.32751	-.02548		
1.493	-1.832	2.15328	133.13260	-09627	-04509	-10853	.05083	1.47836	3.33215	-.02430		
1.493	-1.314	2.12414	124.92640	-07282	-03410	-10775	.05046	1.47848	3.33258	-.02414		
1.493	-797	2.08650	114.58220	-04972	-02328	-10636	.04979	1.47863	3.33150	-.02400		
1.493	-289	2.04099	102.13930	-02610	-01222	-10529	.04932	1.47819	3.33150	-.02439		
1.493	-202	1.99749	88.50832	-00926	-0140	-10325	.04834	1.47856	3.33288	-.02398		
1.493	.705	1.94121	74.28258	-02023	.00947	-10113	.04733	1.47878	3.33370	-.02384		
1.493	1.192	1.90395	61.87831	.04303	.02013	.09974	.04665	1.47919	3.33524	-.02340		
GRADIENT		-.05064	-15.51633	.04547	.02140	-.00182	-.00091	.00105	.00391	.00124	.00158	

	RUN NO.	1611/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA		CPBQ	CPBETA	MPROBE	CPTD
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM			
1.516	-6.939	2.22410	163.24490	-36433	-17277	-12453	.05906	1.49500	3.39440	.03390		
1.516	-6.422	2.21955	162.00720	-34033	-16084	-12331	.05828	1.49701	3.40201	-.03051		
1.516	-5.914	2.22045	160.57220	-31785	-14970	-12400	.05840	1.50104	3.41720	-.02684		
1.516	-5.410	2.21446	158.97840	-29020	-13638	-12412	.05833	1.50312	3.42510	-.02452		
1.516	-4.897	2.21283	157.02840	-26243	-12317	-12277	.05762	1.50400	3.42841	-.02327		
1.516	-4.396	2.20761	154.80120	-23622	-11087	-12352	.05798	1.50381	3.42770	-.02338		
1.516	-3.887	2.20529	152.05940	-21511	-10088	-12532	.05877	1.50499	3.43218	-.02253		
1.516	-3.378	2.19899	148.76310	-19053	-08926	-12600	.05903	1.50597	3.43591	-.02140		
1.516	-2.863	2.18583	144.71430	-16386	-07660	-12387	.05791	1.50767	3.44237	-.01923		
1.516	-2.346	2.17070	139.59650	-13548	-06325	-12086	.05642	1.50881	3.44668	-.01784		
1.516	-1.834	2.15267	133.17220	-10670	-04977	-11835	.05520	1.51033	3.45247	-.01667		
1.516	-1.314	2.12461	124.92640	-07858	-03664	-11600	.05409	1.51030	3.45237	-.01631		
1.516	-.799	2.09154	114.58230	-05134	-02393	-11536	.05377	1.51076	3.45410	-.01602		
1.516	-.288	2.04171	102.13930	-02390	-01114	-11221	.05228	1.51073	3.45399	-.01566		
1.516	.203	1.99752	88.50832	.00235	.00109	.0999	.05117	1.51222	3.45967	-.01405		
1.517	.704	1.94218	74.32220	.02696	.01256	.10704	.04985	1.51162	3.45739	-.01502		
1.516	1.195	1.90863	61.87822	.05130	.02390	.10489	.04887	1.51056	3.45334	-.01561		
GRADIENT		-.05044	-15.51602	.05224	.02449	-.00338	-.00166	.00139	.00158	.001530	.00158	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 586  
( TCM053 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1626/ 0	RN/L =	2.49	GRADIENT INTERVAL =	- 5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD	CPTD
1.542	-6.938	2.22244	163.24470	.34605	-.16336	.12149	.05735	1.52892	3.52373	-.02392
1.541	-6.426	2.22044	162.00730	.31020	-.14622	.11797	.05561	1.52950	3.52598	-.02255
1.540	-5.921	2.21713	160.61170	.27826	-.13103	.11523	.05426	1.52974	3.52692	-.02161
1.541	-5.410	2.21305	158.97830	.24722	-.11634	.11244	.05291	1.53114	3.53230	-.02063
1.542	-4.902	2.21394	157.02850	.21918	-.10322	.10889	.05128	1.53128	3.53287	-.02062
1.542	-4.395	2.20669	154.80120	.19214	-.09053	.10558	.04975	1.53077	3.53089	-.02108
1.542	-3.887	2.20473	152.05930	.16547	-.07796	.10148	.04781	1.53135	3.53311	-.02085
1.542	-3.373	2.19511	148.76280	.14108	-.06644	.09787	.04609	1.53128	3.53285	-.02041
1.542	-2.863	2.18456	144.71420	.11676	-.05493	.09214	.04335	1.53237	3.53707	-.01936
1.542	-2.350	2.17256	139.59650	.09238	-.04345	.08617	.04052	1.53292	3.53919	-.01881
1.542	-1.828	2.15038	133.09280	.06967	-.03278	.08018	.03773	1.53236	3.53702	-.01929
1.542	-1.314	2.12486	124.88680	.05027	-.02368	.07764	.03657	1.53127	3.53283	-.02023
1.542	-.796	2.08701	114.54260	.03204	-.01509	.07602	.03580	1.53154	3.53385	-.01992
1.542	-.288	2.04675	102.09970	.01411	-.00664	.07399	.03483	1.53172	3.53453	-.01963
1.542	.204	1.99747	88.46867	.00240	.00113	.07209	.03393	1.53207	3.53589	.01958
1.542	.705	1.94279	74.32219	.02005	.00943	.07041	.03314	1.53195	3.53545	.01976
1.542	1.194	1.90318	61.83870	.03678	.01731	.06859	.03228	1.53284	3.53887	.01949
	GRADIENT	-.05054	-15.51673	.04159	.01959	-.00698	-.00020	.00017	.00067	.00020

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM054 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1580/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.500	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CP447	MPROBE	CPTD
.600	-6.906	2.77097	159.35450	-29489	-05929	-12173	-02447	.57847	1.25201	-.01852
.599	-6.393	2.76290	157.91650	-27332	-05474	-12222	-02448	.57847	1.25450	-.01604
.599	-5.888	2.76220	156.24160	-25250	-05050	-12177	-02436	.58158	1.25747	-.01389
.600	-5.376	2.75692	154.32870	-23017	-04600	-12111	-02420	.58418	1.25997	-.01213
.599	-4.867	2.75300	152.09920	-20860	-04152	-12163	-02421	.58627	1.26199	-.00996
.600	-4.359	2.74727	149.51330	-18711	-03732	-12074	-02408	.58914	1.26479	-.00872
.600	-3.844	2.73634	146.45200	-16635	-03307	-12056	-02397	.59053	1.26614	-.00713
.600	-3.328	2.72393	142.79690	-14528	-02890	-11947	-02376	.59291	1.26848	-.00584
.600	-2.814	2.71260	138.38960	-12390	-02460	-11867	-02357	.59393	1.26948	-.00483
.600	-2.295	2.68740	133.11090	-10235	-02028	-11753	-02329	.59504	1.27057	-.00368
.600	-1.781	2.66728	126.64480	-08011	-01588	-11615	-02303	.59636	1.27188	-.00298
.600	-1.259	2.63255	118.83220	-05882	-01166	-11449	-02269	.59735	1.27286	-.00229
.601	-.743	2.58857	109.63380	-03740	-00742	-11224	-02227	.59813	1.27364	-.00217
.600	-.235	2.54320	99.16849	-01702	-00337	-11065	-02190	.59816	1.27366	-.00147
.600	.258	2.49202	88.10928	-00256	-00051	-10864	-02152	.59865	1.27416	-.00139
.600	.760	2.44180	76.69319	-02270	-00449	-10724	-02121	.59822	1.27373	-.00130
.600	1.250	2.39810	66.26723	-04229	-00836	-10589	-02094	.59862	1.27413	-.00107
	GRADIENT	.05872	-14.09777	.04113	.00818	-.00270	-.00056	.00192	.00189	.00143

	RUN NO.	1471/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.500	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CP446	MPROBE	CPTD
.800	-6.935	2.69457	159.67000	-28345	-08543	-11483	-03461	.77466	1.48693	-.02531
.800	-6.421	2.68868	158.23230	-26347	-.07912	-11417	-03429	.77768	1.49129	-.02202
.800	-5.912	2.68415	156.59680	-24312	-.07285	-11417	-.03421	.78101	1.49613	-.01915
.800	-5.407	2.67992	154.72390	-22269	-.06649	-11406	-.03405	.78330	1.49948	-.01631
.800	-4.902	2.68131	152.49490	-20199	-.06018	-11406	-.03398	.78583	1.50320	-.01395
.801	-4.395	2.67548	149.94880	-18110	-.05390	-11348	-.03377	.78872	1.50746	-.01175
.800	-3.886	2.66865	146.92760	-16099	-.04779	-11320	-.03360	.79016	1.50959	-.00986
.800	-3.379	2.65889	143.35200	-14095	-.04177	-11240	-.03331	.79179	1.51201	-.00820
.800	-2.896	2.67542	138.98590	-12113	-.03584	-11180	-.03308	.79356	1.51466	-.00657
.800	-2.354	2.63657	133.70640	-10042	-.02967	-11086	-.03276	.79466	1.51630	-.00535
.800	-1.841	2.61775	127.31970	-07974	-.02355	-10987	-.03245	.79606	1.51840	-.00429
.800	-1.332	2.59856	119.62640	-05951	-.01754	-10863	-.03202	.79620	1.51862	-.00338
.800	-.819	2.56671	110.46790	-03954	-.01165	-10722	-.03159	.79712	1.52000	-.00269
.800	-.312	2.52985	100.04230	-01966	-.00579	-10597	-.03122	.79801	1.52134	-.00219
.800	.177	2.49910	89.06236	-.00028	-.00008	-10502	-.03092	.79815	1.52155	-.00177
.800	.686	2.46427	77.56686	.01896	.00558	-10433	-.03071	.79808	1.52144	-.00173
.800	1.179	2.43555	67.14059	.03856	.01135	-10324	-.03038	.79814	1.52153	-.00164
	GRADIENT	-.04161	-14.11313	.03950	.01174	-.00188	-.00062	.00195	.00291	.00199

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM054 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1505/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00		BETA = 2.500	PHI = 180.000					
					BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPM	MPROBE	CPTD
MACH	ALPHA												
.897	-6.924	2.70253	159.63020	-2.27285	-.09364	-.11038	.03788	.87282	1.64272	-.02669			
.901	-6.413	2.70223	158.15320	-.25331	-.08691	-.11006	.03776	.87965	1.65470	-.02276			
.900	-5.901	2.69596	156.51750	-.23382	-.07997	-.10926	.03737	.88171	1.65834	-.02004			
.900	-5.397	2.69587	154.60520	-.21428	-.07304	-.10919	.03722	.88367	1.66180	-.01725			
.899	-4.892	2.69216	152.41560	-.19433	-.06607	-.10912	.03710	.88574	1.66551	-.01480			
.900	-4.384	2.68465	149.86940	-.17441	-.05920	-.10893	.03697	.88869	1.67078	-.01237			
.900	-3.879	2.67899	146.84830	-.15497	-.05248	-.10886	.03686	.89082	1.67461	-.01002			
.901	-3.364	2.66658	143.23280	-.13562	-.04588	-.10814	.03658	.89344	1.67935	-.00806			
.900	-2.856	2.65994	138.86560	-.11626	-.03926	-.10722	.03621	.89407	1.68050	-.00691			
.899	-2.344	2.64610	133.58740	-.09652	-.03251	-.10637	.03583	.89422	1.68075	-.00552			
.900	-1.830	2.62488	127.20050	-.07656	-.02578	-.10527	.03545	.89595	1.68391	-.00444			
.900	-1.314	2.60033	119.42790	-.05720	-.01925	-.10407	.03502	.89683	1.68561	-.00363			
.900	-805	2.56890	110.30910	-.03784	-.01272	-.10283	.03457	.89749	1.68672	-.00274			
.900	-296	2.52903	99.84380	-.01906	-.00640	-.10161	.03413	.89759	1.68689	-.00223			
.900	.193	2.50042	88.86386	-.00067	-.00023	-.10044	.03373	.89808	1.68778	-.00197			
.900	.699	2.45782	77.40805	-.01779	-.00597	-.09953	.03343	.89858	1.68870	-.00172			
.900	1.191	2.42702	66.98186	-.03644	-.01224	-.09859	.03311	.89865	1.68883	-.00158			
GRADIENT		-.04404	-14.12494	.03792	.01285	-.00189	-.00071	.00071	.00348	.00208			
RUN NO.	1511/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00								
MACH	ALPHA				BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPM	MPROBE	CPTD
1.099	-6.976	2.56995	160.18240	-.24827	-.10126	-.09540	.03891	1.07664	2.07353	-.02758			
1.100	-6.465	2.56947	158.74530	-.23076	-.09387	-.09491	.03861	1.08025	2.08257	-.02430			
1.100	-5.962	2.56610	157.14980	-.21359	-.08659	-.09480	.03843	1.08841	2.08841	-.02101			
1.100	-5.457	2.56513	155.27730	-.19608	-.07927	-.09447	.03819	1.08528	2.09526	-.01793			
1.100	-4.961	2.56425	153.16750	-.17809	-.07177	-.09485	.03822	1.08756	2.10101	-.01492			
1.100	-4.461	2.56367	150.66160	-.16081	-.06464	-.09417	.03785	1.08946	2.10586	-.01235			
1.100	-3.954	2.56155	147.68050	-.14325	-.05750	-.09422	.03782	1.09124	2.11039	-.01068			
1.100	-3.449	2.55664	144.14490	-.12576	-.05038	-.09413	.03771	1.09245	2.11347	-.00886			
1.100	-2.948	2.54914	139.89670	-.10815	-.04325	-.09354	.03741	1.09397	2.11736	-.00718			
1.100	-2.443	2.54654	134.73810	-.09045	-.03613	-.09305	.03717	1.09523	2.12057	-.00587			
1.100	-1.943	2.54428	128.47090	-.07278	-.02903	-.09241	.03686	1.09639	2.12355	-.00436			
1.100	-1.441	2.52890	120.85710	-.05556	-.02214	-.09180	.03658	1.09687	2.12479	-.00364			
1.100	-939	2.51868	111.81800	-.03830	-.01525	-.09092	.03621	1.09756	2.12656	-.00282			
1.100	-442	2.50803	101.39270	-.02112	-.00841	-.09076	.03611	1.09795	2.12756	-.00217			
1.100	.050	2.50026	90.41289	-.00457	-.00182	-.09038	.03596	1.09822	2.12827	-.00195			
1.100	.562	2.49134	78.91727	-.01197	-.00476	-.09075	.03610	1.09856	2.12915	-.00166			
1.100	1.063	2.48549	68.49074	-.02919	-.01161	-.09057	.03602	1.09835	2.12860	-.00167			
GRADIENT		-.01427	-14.16811	.03451	.01386	-.00082	-.00041	.00041	.00458	.00218			

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM054) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1527/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA =	2.500	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPD	CPMB	CPM	CPTD		
1.250	-6.945	2.65777	159.82750	-254.18	-11185	10220	.04497	1.22596	2.48405	-02882			
1.250	-6.431	2.65829	158.35060	-23659	-10374	10126	.04440	1.22907	2.49334	-.02511			
1.250	-5.924	2.65547	156.71530	-21895	-.09566	10069	.04399	1.23248	2.50357	-.02128			
1.250	-5.417	2.65095	154.84240	-20098	-.08753	10035	.04370	1.23498	2.51111	-.01811			
1.249	-4.916	2.65071	152.65300	-18211	-.07910	09991	.04339	1.23664	2.51613	-.01550			
1.250	-4.408	2.64439	150.10700	-16343	-.07085	09945	.04312	1.23842	2.51152	-.01359			
1.250	-3.898	2.63826	147.08580	-14501	-.06278	09952	.04308	1.24005	2.52644	-.01198			
1.250	-3.391	2.63397	143.47090	-12685	-.05481	09943	.04296	1.24158	2.53108	-.01006			
1.250	-2.882	2.62341	139.14310	-10880	-.04692	09901	.04270	1.24324	2.53614	-.00811			
1.250	-2.372	2.61124	133.90480	-09067	-.03905	09793	.04217	1.24482	2.54095	-.00659			
1.250	-1.868	2.59984	127.55800	-07236	-.03114	09683	.04167	1.24533	2.54250	-.00581			
1.250	-1.356	2.57863	119.86470	-05467	-.02349	09592	.04121	1.24625	2.54531	-.00435			
1.250	-.848	2.55425	110.74600	-03670	-.01575	09497	.04077	1.24680	2.54697	-.00358			
1.250	-.343	2.52680	100.32050	-.01918	-.00823	09423	.04043	1.24740	2.54882	-.00307			
1.250	.146	2.49596	89.34056	-.00227	-.00097	09339	.04006	1.24765	2.54956	-.00280			
1.250	.654	2.46684	77.84506	.01520	.00652	09310	.03993	1.24727	2.54841	-.00272			
1.250	1.149	2.44374	67.41876	.03287	.01409	09233	.03959	1.24760	2.54942	-.00242			
	GRADIENT			.03536	.01532	-.00138	-.00069			.00550			
	RUN NO.	1544/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00					
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPD	CPMB	CPM	CPTD		
1.400	-6.953	2.64683	159.86710	-28211	-.13070	11383	.05274	1.37418	2.95981	-.02979			
1.400	-6.436	2.64206	158.42940	-26227	-.12113	11364	.05249	1.37725	2.97036	-.02647			
1.400	-5.929	2.63973	156.79420	-24258	-.11163	11290	.05195	1.38029	2.98809	-.02278			
1.400	-5.422	2.63603	154.92140	-22237	-.10203	11202	.05140	1.38240	2.98809	-.01991			
1.400	-4.918	2.63421	152.73190	-20234	-.09260	11133	.05095	1.38529	2.99806	-.01711			
1.400	-4.416	2.62871	150.22570	-18299	-.08352	11157	.05092	1.38739	3.00533	-.01437			
1.400	-3.911	2.62585	147.20480	-16268	-.07410	11201	.05102	1.38918	3.01155	-.01236			
1.400	-3.406	2.62092	143.62950	-14254	-.06476	11112	.05049	1.39168	3.02020	-.00973			
1.400	-2.893	2.60994	139.30170	-12206	-.05537	11066	.05020	1.39292	3.02453	-.00819			
1.400	-2.387	2.60389	134.06360	-.10161	-.04603	10947	.04959	1.39430	3.02932	-.00671			
1.400	-1.880	2.59185	127.71680	-.08145	-.03685	10834	.04901	1.39507	3.03201	-.00550			
1.400	-.366	2.56866	120.02340	-.06136	-.02774	10669	.04824	1.39564	3.03403	-.00491			
1.400	-.863	2.55042	110.94450	-.04159	-.01879	10546	.04765	1.39581	3.03459	-.00432			
1.400	-.359	2.52544	100.55860	-.02203	-.00995	10488	.04738	1.39624	3.03611	-.00407			
1.399	-.132	2.49784	89.53908	-.00316	-.00143	10381	.04686	1.39651	3.03703	-.00343			
1.400	.639	2.47103	78.04355	.01569	.00708	10330	.04663	1.39682	3.03812	-.00333			
1.400	1.134	2.45088	67.61723	.03935	.01517	10261	.04633	1.39722	3.03950	-.00343			
	GRADIENT				.03087	-.14.14902	-.0179	-.00018	.00184	.00639	.00217		



## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM054 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1596/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA A	=	2.500	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
1.492	-6.926	2.72324	159.59100	-31797	-15165	13330	.06358	1.46133	3.26919					
1.493	-6.404	2.71319	158.11360	-29667	-14112	13233	.06295	1.46449	3.28082	-.04041				
1.493	-5.902	2.70978	156.47830	-27492	-13055	13186	.06261	1.46580	3.28562	-.03846				
1.493	-5.392	2.70690	154.56560	-25495	-12068	13207	.06299	1.46833	3.29496	-.03532				
1.493	-4.888	2.70766	152.33660	-23304	-11003	13318	.06288	1.47119	3.30553	-.03267				
1.493	-4.378	2.69876	149.79030	-21073	-09930	13381	.06305	1.47289	3.31184	-.03056				
1.493	-3.865	2.69126	146.72930	-18805	-08846	13381	.06295	1.47407	3.31619	-.02890				
1.493	-3.357	2.68302	143.11410	-16491	-07742	13340	.06263	1.47603	3.32356	-.02708				
1.493	-2.844	2.67068	138.74650	-14105	-06614	13245	.06211	1.47717	3.32772	-.02565				
1.493	-2.331	2.65402	133.46820	-11758	-05508	13197	.06183	1.47819	3.33151	-.02462				
1.493	-1.818	2.63528	127.04180	-09442	-04416	13073	.06114	1.47911	3.33493	-.02294				
1.493	-1.301	2.60807	119.26910	-07139	-03338	12967	.06062	1.47984	3.33762	-.02252				
1.493	-789	2.57412	110.11060	-04800	-02245	12827	.06000	1.47925	3.33543	-.02312				
1.493	-283	2.53556	99.68494	-02485	-01163	12680	.05937	1.47815	3.33134	-.02438				
1.493	-208	2.49848	88.66534	-00211	-00098	12560	.05874	1.47895	3.33435	-.02327				
1.493	-716	2.45733	77.16988	-02079	.00972	12382	.05792	1.47964	3.33690	-.02295				
1.493	1.208	2.42383	66.78331	.04371	.02044	12214	.05712	1.47967	3.33700	-.02277				
GRADIENT	-0.04701	-14.12142	.04546	.02141	-00193	-0.00099	.00126	.00466	.00146	.00146				
	RUN NO.	1612/ 0	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00	BETA A	=	2.500	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD					
1.517	-6.923	2.71677	159.59100	-36215	-17197	15043	.07144	1.49431	3.39183	-.03475				
1.517	-6.409	2.71529	158.11380	-33985	-16070	15009	.07097	1.49800	3.40573	-.03045				
1.516	-5.899	2.71477	156.43890	-31677	-14934	15005	.07074	1.50013	3.41377	-.02750				
1.516	-5.391	2.70764	154.56570	-28901	-13597	15016	.07065	1.50179	3.42005	-.02539				
1.516	-4.890	2.70478	152.37610	-26162	-12289	14974	.07034	1.50358	3.42684	-.02391				
1.517	-4.378	2.69936	149.79040	-23527	-11052	14902	.07000	1.50403	3.42854	-.02366				
1.517	-3.870	2.69487	146.72950	-21222	-09965	15039	.07062	1.50413	3.42891	-.02329				
1.516	-3.357	2.68354	143.11420	-18855	-08843	15170	.07115	1.50505	3.43240	-.02205				
1.517	-2.844	2.67158	138.74660	-16282	-07620	15097	.07066	1.50702	3.43986	-.01997				
1.516	-2.331	2.65466	133.46830	-13522	-06318	14860	.06943	1.50843	3.44523	-.01835				
1.516	-1.814	2.63201	127.04170	-10711	-04999	14579	.06804	1.50947	3.44918	-.01714				
1.517	-1.300	2.60869	119.26910	-07961	-03713	14215	.06630	1.51026	3.45221	-.01652				
1.516	-788	2.57463	110.11060	-05221	-02434	13874	.06468	1.51019	3.45194	-.01611				
1.517	-282	2.53593	99.68494	-02586	-01206	13712	.06391	1.51089	3.45459	-.01579				
1.516	209	2.49357	88.66536	-00068	-00032	13503	.06293	1.51059	3.45346	-.01571				
1.517	.714	2.45324	77.20956	.02449	.01141	13355	.06223	1.51142	3.45662	-.01546				
1.517	2.42402	66.78331	.04962	.02312	.01324	.06162	.1.51112	3.45548	-.01547					
GRADIENT	-0.04742	-14.11550	.05151	.02418	-00343	-.00171	.00144	.00162	.00146	.00146				

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16IE-783) PROBE CALIBRATION

הנִזְקָנָה בְּבֵית־הַמִּלְחָמָה

PAGE 592

卷之三

PARAMETRIC DATA

	MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	NPROBE	CPTD
1.541	-6.920	2.72005	159.55140	-34740	-16417	-14742	.06967	1.52744	3.51802	-0.02469	
1.541	-6.406	2.71867	158.07430	-31334	-14779	-14331	.06759	1.52961	3.52641	-0.0269	
1.541	-5.899	2.71341	156.43880	-28167	-13268	-14012	.06601	1.52992	3.52761	-0.02150	
1.541	-5.391	2.70651	154.56560	-25081	-11804	-13660	.06429	1.53216	3.53624	-0.02051	
1.541	-4.888	2.70705	152.33650	-22146	-10428	-13337	.06280	1.53065	3.53042	-0.02117	
1.541	-4.377	2.70085	149.75070	-19374	-09121	-12978	.06109	1.53090	3.53138	-0.02087	
1.541	-3.865	2.69051	146.72920	-16748	-07886	-12517	.05894	1.53093	3.53151	-0.02107	
1.541	-3.358	2.68179	143.11410	-14201	-06680	-12021	.05655	1.53158	3.53403	-0.02020	
1.541	-2.843	2.67132	138.70690	-11868	-05759	-11527	.05418	1.53253	3.53767	-0.01935	
1.541	-2.329	2.65499	133.42860	-09560	-04491	-10939	.05139	1.53331	3.54070	-0.01871	
1.541	-1.818	2.63495	127.04180	-07186	-03376	-10282	.04830	1.53269	3.53829	-0.01892	
1.541	-1.301	2.60782	119.26910	-05072	-02383	.09712	.04564	1.53272	3.53841	-0.01915	
1.541	-0.790	2.57399	110.11060	-03167	-01489	.09347	.04394	1.53221	3.53643	-0.01942	
1.541	-0.282	2.53611	99.64529	-01343	-00631	.09147	.04299	1.53222	3.53648	-0.01930	
1.541	-0.210	2.49338	88.62573	-00344	-00162	.08943	.04204	1.53222	3.53650	-0.01960	
1.541	-0.713	2.45296	77.20956	.02048	-00963	.08822	.04148	1.53220	3.53778	-0.01962	
1.541	1.205	2.41943	66.78340	.03807	.01789	.08620	.04051	1.53245	3.53737	-0.01910	
GRADIENT	-0.04777	-	-14.12259	-0.04228	-0.01990	-0.00838	-0.00027	-	.00104	-	.00029

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 593

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM055) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1581/ O	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/ 5.00	BETA	=	3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPBE	CPBM	CPTD			
.600	-6.892	3.26653	155.85930	-.29445	-.05927	.14318	.02882	.57457	1.25080	-.01953			
.599	-6.376	3.25822	154.22100	-.27314	-.05482	.14266	.02863	.57719	1.25328	-.01728			
.600	-5.870	3.25093	152.38510	-.25139	-.05036	.14266	.02858	.57993	1.25589	-.01523			
.600	-5.357	3.24750	150.23260	-.22895	-.04581	.14245	.02850	.58361	1.25942	-.01276			
.600	-4.847	3.23982	147.80280	-.20790	-.04146	.14216	.02835	.58503	1.26080	-.01114			
.600	-4.334	3.23153	144.97700	-.18563	-.03697	.14208	.02830	.58759	1.26327	-.00931			
.600	-3.827	3.22405	141.71600	-.16502	-.03286	.14036	.02795	.59001	1.26563	-.00782			
.600	-3.307	3.20853	137.86040	-.14481	-.02877	.14054	.02792	.59096	1.26656	-.00672			
.600	-2.794	3.19315	133.37180	-.12330	-.02451	.13971	.02777	.59343	1.26898	-.00533			
.600	-2.279	3.17171	128.27910	-.10174	-.02020	.13848	.02750	.59474	1.27028	-.00433			
.600	-1.762	3.14481	121.89980	-.07984	-.01586	.13666	.02714	.59551	1.27104	-.00389			
.600	-1.250	3.11665	114.71880	-.05922	-.01173	.13500	.02674	.59629	1.27181	-.00284			
.600	-737	3.08271	106.54780	-.03735	-.00740	.13390	.02654	.59710	1.27261	-.00245			
.600	-232	3.04250	97.62459	-.01657	-.00328	.13185	.02612	.59743	1.27295	-.00217			
.600	.262	2.99568	88.34517	.00292	.00058	.13021	.02579	.59763	1.27314	-.00197			
.600	.766	2.94996	78.78821	.02384	.00472	.12897	.02554	.59796	1.27347	-.00176			
.600	1.258	2.91289	69.86497	.04332	.00858	.12740	.02523	.59814	1.27365	-.00163			
	GRADIENT	-.05438	-12.90666	.04120	.00820	-.00254	-.00054	.00204	.00201	.00150			

	RUN NO.	1472/ O	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/ 5.00	BETA	=	3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPOAQ	CPALPH	CPBQ	CPBETA	CPBE	CPBM	CPTD			
.800	-6.927	3.19132	156.17520	-.28298	-.08531	.13553	.04086	.77336	1.48506	-.02620			
.800	-6.405	3.18290	154.53690	-.26335	-.07916	.13438	.04039	.77683	1.49006	-.02291			
.800	-5.903	3.18035	152.70160	-.24318	-.07290	.13452	.04033	.77979	1.49435	-.02004			
.800	-5.395	3.17191	150.62830	-.22231	-.06648	.13411	.04010	.78266	1.49855	-.01732			
.800	-4.889	3.17012	148.19900	-.20165	-.06016	.13402	.03999	.78531	1.50243	-.01480			
.800	-4.380	3.16808	145.37370	-.18048	-.05367	.13376	.03978	.78705	1.50499	-.01246			
.800	-3.871	3.15856	142.15230	-.16059	-.04770	.13299	.03950	.78946	1.50856	-.01054			
.800	-3.364	3.14951	138.37670	-.14044	-.04163	.13235	.03923	.79098	1.51081	-.00880			
.800	-2.854	3.13773	133.92790	-.12048	-.03567	.13186	.03904	.79280	1.51352	-.00725			
.800	-2.345	3.12523	128.68730	-.09981	-.02950	.13104	.03873	.79383	1.51507	-.00594			
.800	-1.832	3.10515	122.53590	-.07950	-.02348	.13005	.03841	.79511	1.51698	-.00490			
.800	-1.323	3.08561	115.39470	-.05934	-.01751	.12898	.03805	.79598	1.51828	-.00395			
.800	-812	3.05657	107.26350	-.03900	-.01150	.12783	.03769	.79670	1.51936	-.00325			
.800	-308	3.02794	98.34045	-.01956	-.00576	.12679	.03735	.79731	1.52028	-.00257			
.800	181	2.99931	89.14038	-.00001	-.00000	.12563	.03701	.79767	1.52082	-.00234			
.800	689	2.97205	79.54356	.01969	.00580	.12458	.03669	.79792	1.52120	-.00210			
.800	1.185	2.94205	70.58055	.03924	.01155	.12396	.03649	.79774	1.52093	-.00197			
	GRADIENT	-.03846	-12.92658	.03960	.01176	-.000176	-.00060	.00207	.00309	.00206			

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 594  
( TCM055 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1506/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/ 5.00	BETA	=	3.000	PHI	=	180.000
									CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
.899	-6.916	3.19886	156.13530	-.27179	-.09355	.12957	.04460	.87429	1.64528	-.02734				
.900	-6.396	3.19609	154.45770	-.25229	-.08664	.12981	.04458	.87761	1.65110	-.02434				
.900	-5.892	3.19184	152.62220	-.23355	-.07993	.12895	.04413	.88039	1.65600	-.02108				
.900	-5.389	3.19063	150.50980	-.21348	-.07286	.12923	.04411	.88319	1.66096	-.01818				
.900	-4.879	3.18097	148.11960	-.19384	-.06602	.12859	.04379	.88596	1.66589	-.01555				
.900	-4.369	3.17747	145.29430	-.17375	-.05904	.12799	.04349	.88823	1.66995	-.01315				
.900	-3.863	3.16912	142.07290	-.15458	-.05239	.12756	.04323	.88965	1.67251	-.01107				
.900	-3.353	3.16047	138.25760	-.13495	-.04565	.12692	.04293	.89157	1.67596	-.00909				
.900	-2.841	3.14640	133.80870	-.11571	-.03908	.12622	.04263	.89291	1.67839	-.00756				
.900	-2.331	3.13136	128.56810	-.09590	-.03235	.12544	.04231	.89430	1.68091	-.00618				
.900	-1.818	3.11421	122.37710	-.07631	-.02572	.12431	.04189	.89551	1.68311	-.00505				
.900	-1.308	3.08601	115.27540	-.05688	-.01915	.12327	.04150	.89606	1.68410	-.00426				
.900	-.801	3.06410	107.14430	-.03749	-.01261	.12212	.04109	.89693	1.68569	-.00352				
.900	-.294	3.03316	98.18152	-.01864	-.00627	.12103	.04069	.89768	1.68707	-.00271				
.900	.197	2.99680	88.98140	-.00011	-.00004	.12007	.04034	.89766	1.68703	-.00236				
.900	.703	2.96190	79.38472	-.01852	-.00622	.11911	.04002	.89814	1.68790	-.00213				
.900	1.196	2.93102	70.46143	-.03748	-.01259	.11836	.03975	.89793	1.68752	-.00204				
	GRADIENT	-.04175	-12.92911	.03803	.01291	-.00177	-.00069	.00197	-.00077	-.00041				
MACH	ALPHA	RUN NO.	1512/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/ 5.00	BETA	=	3.000	PHI	=	5.00
									CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.099	-6.970	3.07074	156.64850	-.24749	-.10102	.11363	.04638	1.07581	2.07147	-.02846				
1.099	-6.460	3.06535	155.05160	-.23055	-.09384	.11297	.04598	1.0780	2.07894	-.02527				
1.100	-5.957	3.06668	153.21570	-.21365	-.08673	.11214	.04552	1.08175	2.08635	-.02221				
1.100	-5.457	3.06700	151.14320	-.19601	-.07931	.11199	.04531	1.08467	2.09371	-.01882				
1.100	-4.955	3.06273	148.79340	-.17853	-.07203	.11180	.04511	1.08688	2.09930	-.01603				
1.100	-4.453	3.05679	146.08710	-.16028	-.06451	.11173	.04497	1.08898	2.10463	-.01343				
1.100	-3.953	3.06100	142.86670	-.14290	-.05738	.11177	.04488	1.09015	2.10761	-.01145				
1.100	-3.447	3.05178	139.17060	-.12572	-.05040	.11133	.04463	1.09223	2.11291	-.00948				
1.100	-2.945	3.05140	134.76210	-.10811	-.04326	.11084	.04436	1.09352	2.11620	-.00776				
1.100	-2.439	3.04347	129.60110	-.08997	-.03596	.11077	.04427	1.09441	2.11849	-.00649				
1.100	-1.939	3.03428	123.56920	-.07284	-.02908	.11014	.04397	1.09609	2.12279	-.00510				
1.100	-1.436	3.02296	116.46800	-.05546	-.02212	.10912	.04352	1.09640	2.12357	-.00430				
1.100	-0.934	3.01749	108.37690	-.03786	-.01509	.10870	.04332	1.09724	2.12574	-.00344				
1.100	-.441	3.01203	99.49379	-.02106	-.00839	.10823	.04310	1.09751	2.12644	-.00289				
1.100	.057	3.00234	90.29376	-.00398	-.00159	.10817	.04306	1.09801	2.12773	-.00244				
1.100	.567	2.99693	80.69685	-.01276	-.00508	.10805	.04300	1.09805	2.12783	-.00221				
1.100	1.063	2.98374	71.81290	-.02992	-.01190	.10809	.04301	1.09807	2.12788	-.00202				
	GRADIENT	-.01331	-12.96612	.03462	.01392	-.00077	-.00041							

PAGE 595 ( TCM055 ) ( 04 OCT 91 )

RUN NO.		1528/ O		RN/L = 2.50		GRADIENT		INTERVAL = -5.00/ 5.00		CPM		CPTD	
BETA	PHI	CPAQ	CPALPH	CPBQ	CPBT	CPALPH	CPBQ	CPBT	CPM	CPM	CPTD		
ALPHA													
-6.939	3.15910	156.29340	-25423	-11198	.05261	1.22510	2.48146	-.02982					
.250													
-6.420	3.15290	154.65540	-23620	-10369	.05232	1.22819	2.49071	-.02625					
.250													
-5.915	3.14989	152.82000	-21850	-.09559	.05202	1.23131	2.50005	-.02265					
.250													
-5.409	3.14302	150.74690	-20070	-.08749	.05182	1.23381	2.50759	-.01917					
.250													
-4.902	3.14044	148.311760	-18216	-.07922	.05142	1.23616	2.51466	-.01667					
.250													
-4.394	3.13488	145.53190	-16333	-.07083	.05091	1.23819	2.52081	-.01393					
.250													
-3.887	3.13025	142.257110	-14447	-.06258	.05069	1.23940	2.52447	-.01268					
.250													
-3.383	3.12395	138.49570	-12656	-.05475	.05042	1.24081	2.52876	-.01127					
.250													
-2.875	3.11599	134.04720	-10841	-.04681	.05017	1.24255	2.53405	-.00920					
.250													
-2.361	3.09974	128.80650	-.09028	-.03890	.04989	1.24365	2.53737	-.00726					
.250													
-1.858	3.08657	122.73470	-.07215	-.03106	.04946	1.24499	2.54147	-.00623					
.250													
-1.350	3.06805	115.63330	-.05442	-.02341	.04833	1.24554	2.54314	-.00539					
.250													
-843	3.04700	107.50230	-.03631	-.01560	.04842	1.24612	2.54490	-.00442					
.250													
-340	3.02720	98.57930	-.01839	-.00811	.04797	1.24660	2.54638	-.00411					
.250													
.150	3.00348	89.37917	-.00182	-.00078	.04772	1.24715	2.54805	-.00345					
.250													
.659	2.97573	79.78238	.01577	.00676	.04741	1.24722	2.54825	-.00303					
.250													
1.155	2.95153	70.85893	.03338	.01432	.04715	1.24712	2.54798	-.00326					
.250													
GRADIENT	-.03147	-11.94500	.03548	.01538	-.00143	-.00073	.00183	.00557	.00223				
RUN NO.		1545/ O		RN/L = 2.50		GRADIENT		INTERVAL = -5.00/ 5.00		CPM		CPTD	
BETA	PHI	CPAQ	CPALPH	CPBQ	CPBT	CPALPH	CPBQ	CPBT	CPM	CPM	CPTD		
ALPHA													
-6.942	3.14687	156.33280	-.28147	-.13052	.13448	.06236	1.37345	2.95733	-.03071				
.400													
-6.424	3.14081	154.69480	-.26159	-.12095	.13417	.06203	1.37639	2.96741	-.02757				
.400													
-5.921	3.13451	152.89900	-.24208	-.11152	.13324	.06137	1.37962	2.97852	-.02377				
.400													
-5.413	3.13253	150.78650	-.22216	-.10204	.13249	.06086	1.38188	2.98630	-.02089				
.400													
-4.913	3.13020	148.39710	-.20196	-.09254	.13175	.06037	1.38389	2.99323	-.01845				
.400													
-4.405	3.12589	145.61140	-.18199	-.08313	.13116	.05991	1.38668	3.00286	-.01528				
.400													
-3.900	3.11987	142.39030	-.16230	-.07399	.13100	.05972	1.38866	3.00972	-.01314				
.400													
-3.392	3.11173	138.61470	-.14238	-.06475	.13076	.05946	1.39096	3.01772	-.01063				
.400													
-2.885	3.10528	134.16630	-.12186	-.05531	.13035	.05917	1.39138	3.01918	-.00906				
.400													
-2.377	3.09408	128.96550	-.10120	-.04588	.12969	.05880	1.39378	3.02755	-.00753				
.400													
-1.869	3.07984	122.85400	-.08116	-.03674	.12827	.05806	1.39419	3.02895	-.00610				
.400													
-1.363	3.06317	115.75260	-.06113	-.02765	.12710	.05749	1.39501	3.03180	-.00534				
.400													
-1.399	3.04405	107.66130	-.04099	-.01852	.12591	.05690	1.39546	3.03338	-.00450				
.400													
-1.353	3.02144	98.73827	-.02150	-.00971	.12493	.05644	1.39635	3.03650	-.00414				
.400													
-1.35	2.99341	89.53821	-.00228	-.00103	.12378	.05592	1.39627	3.03619	-.00407				
.400													
.643	2.97899	74.94138	-.01701	-.00768	.12331	.05567	1.39688	3.03832	-.00338				
.400													
1.141	2.95654	70.97824	-.03627	-.01637	.12278	.05542	1.39670	3.03771	-.00333				
.400													
GRADIENT	-.02917	-12.94431	.01803	.01649	-.00164	.00088	.00200	.00696	.00237				

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 596  
 ( TCM055 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1562/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	3.000	PHI =	180.000
<b>MACH</b>										
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
1.450	-6.892	3.242287	155.93740	-.29435	.13849	.14352	.06753	1.42281	3.12980	-.03177
1.449	-6.374	3.240003	154.25990	-.27396	.12843	.14358	.06731	1.42462	3.13628	-.02832
1.450	-5.866	3.237334	152.38470	-.25366	.11854	.14314	.06689	1.42874	3.15098	-.02479
1.450	-5.361	3.232355	150.27190	-.23222	.10823	.14208	.06622	1.43042	3.15700	-.02221
1.450	-4.847	3.222273	147.84190	-.21073	.09797	.14080	.06546	1.43248	3.16439	-.01969
1.450	-4.339	3.217667	145.01650	-.18974	.08803	.14042	.06515	1.43477	3.17266	-.01751
1.450	-3.829	3.207337	141.75530	-.16965	.07850	.14044	.06499	1.43724	3.18154	-.01478
1.450	-3.316	3.19345	137.93970	-.14870	.06862	.14040	.06479	1.43918	3.18855	-.01206
1.450	-2.801	3.17586	133.45090	-.12699	.05852	.13984	.06444	1.44103	3.19521	-.01059
1.450	-2.284	3.15817	128.13080	-.10499	.0428	.13919	.06401	1.44239	3.20014	-.00856
1.449	-1.772	3.13816	121.93980	-.08405	.03861	.13783	.06332	1.44263	3.20102	-.00766
1.450	-1.261	3.10798	114.79840	-.06266	.02876	.13572	.06229	1.44414	3.20647	-.00657
1.450	-751	3.07313	106.66710	-.04097	.01879	.13410	.06150	1.44477	3.20878	-.00585
1.449	-241	3.03384	97.66464	-.02052	.00941	.13249	.06076	1.44411	3.20636	-.00601
1.449	-250	2.99374	88.42491	-.00018	.00008	.13101	.06005	1.44476	3.20873	-.00530
1.450	.757	2.95534	78.82820	-.02012	.00922	.12990	.05953	1.44534	3.21083	-.00508
1.450	1.246	2.91736	69.98433	-.04027	.01845	.12888	.05904	1.44583	3.21259	-.00469
1.450	GRADIENT	-.05099	-12.92301	.04134	.01915	-.00216	-.00114	.000202	.000237	.000223
	RUN NO.	1647/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
<b>MACH</b>										
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
1.470	-6.903	3.22609	156.01670	-.30061	.14276	.14651	.06958	1.43838	3.18564	-.04174
1.484	-6.386	3.22383	154.33920	-.27465	.13256	.14383	.06942	1.44129	3.19617	-.03863
1.471	-5.881	3.21896	152.50360	-.25907	.12228	.14666	.06922	1.44444	3.20757	-.03552
1.471	-5.369	3.21685	150.35130	-.23822	.11199	.14656	.06890	1.44805	3.22065	-.03140
1.470	-4.862	3.20719	147.96110	-.21701	.10167	.14565	.06824	1.45001	3.22781	-.02804
1.471	-4.350	3.20087	145.13560	-.19462	.09102	.14363	.06717	1.45251	3.23689	-.02558
1.470	-3.845	3.19522	141.87470	-.17293	.08077	.14277	.06668	1.45347	3.24043	-.02433
1.470	-3.331	3.17697	138.09850	-.15125	.07053	.14210	.06626	1.45446	3.24402	-.02268
1.471	-2.817	3.16732	133.57040	-.12915	.06100	.14169	.06594	1.45692	3.25302	-.02057
1.471	-2.306	3.14794	128.32960	-.10683	.04966	.14073	.06543	1.45794	3.25676	-.01941
1.470	-1.791	3.12623	122.13850	-.08537	.03961	.13917	.06458	1.45889	3.26024	-.01767
1.471	-1.281	3.10515	114.95760	-.06390	.02962	.13777	.06385	1.46051	3.26617	-.01630
1.471	-1.769	3.06798	106.82620	-.04194	.01943	.13610	.06307	1.46091	3.26764	-.01602
1.471	-263	3.03640	97.86349	-.02098	.00972	.13397	.06205	1.46115	3.26853	-.01564
1.470	.228	2.99986	88.66338	-.00047	.00022	.13264	.06140	1.46131	3.26911	-.01516
1.471	.734	2.95997	79.06667	.01980	.00916	.13196	.06105	1.46206	3.27187	-.01454
1.470	1.228	2.92903	70.14331	.04018	.01859	.13112	.06066	1.46207	3.27192	-.01449
1.470	.04659	-12.92507	.04227	.01975	-.00243	-.00126	-.00023	.000721	.000197	.000223

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM055) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1597 / O	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPME	CPTD					
1.493	-6.910	3.21039	156.09570	-.31655	-.15111	.15568	.07432	1.46151	3.26985					
1.493	-6.393	3.20890	154.41830	-.29604	-.14087	.15504	.07377	1.46406	3.27924					
1.493	-5.886	3.20775	152.54320	-.27367	-.12993	.15504	.07361	1.46559	3.28485					
1.493	-5.381	3.20490	150.43060	-.25283	-.11976	.15565	.07373	1.46775	3.29282					
1.493	-4.868	3.19676	148.00080	-.23152	-.10933	.15636	.07384	1.47076	3.30396					
1.493	-4.363	3.19104	145.21510	-.20925	-.09863	.15590	.07348	1.47218	3.30919					
1.493	-3.856	3.18056	141.99360	-.18714	-.08804	.15618	.07348	1.47476	3.31875					
1.493	-3.344	3.16997	138.17810	-.16457	-.07332	.15605	.07331	1.47559	3.32184					
1.493	-2.830	3.15554	133.68950	-.14010	-.06577	.15495	.07274	1.47641	3.32488					
1.493	-2.316	3.13968	128.40910	-.11659	-.05464	.15430	.07232	1.47741	3.32862					
1.493	-1.804	3.11871	122.25770	-.09327	-.04367	.15306	.07167	1.47856	3.33287					
1.493	-1.292	3.09429	115.07680	-.07029	-.03289	.15186	.07106	1.47897	3.33441					
1.493	-784	3.06953	106.94570	-.04662	-.02180	.15086	.07054	1.47957	3.33665					
1.493	-279	3.03478	98.02251	-.02385	-.01115	.14917	.06973	1.47994	3.33801					
1.493	.214	3.00070	88.78273	-.00103	-.00048	.14793	.06915	1.47967	3.33700					
1.493	.720	2.96356	79.22566	-.02174	.01016	.14618	.06834	1.48007	3.33848					
1.493	1.213	2.93000	70.30237	.04476	.02092	.14497	.06777	1.47992	3.33793					
1.493	GRADIENT	-0.04407	-12.92399	.04555	.02145	-.00196	-.00104	.00146	.00543					
	RUN NO.	1613 / O	RN/L =	2.49	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPME	CPTD					
1.516	-6.909	3.21078	156.09570	-.35895	-.17064	.17582	.08358	1.49273	3.38586					
1.517	-6.393	3.20935	154.41840	-.33784	-.15992	.17592	.08327	1.49688	3.40149					
1.517	-5.885	3.20846	152.54330	-.31376	-.14808	.17670	.08339	1.49942	3.41110					
1.516	-5.383	3.20194	150.47020	-.28831	-.13572	.17693	.08328	1.50173	3.41982					
1.516	-4.870	3.19434	148.04040	-.26119	-.12271	.17553	.08247	1.50324	3.42556					
1.517	-4.359	3.18888	145.21490	-.23371	-.10970	.17463	.08197	1.50441	3.42998					
1.516	-3.855	3.17835	141.99340	-.20943	-.09830	.17402	.08168	1.50427	3.42946					
1.517	-3.344	3.17118	138.17820	-.18676	-.08762	.17558	.08237	1.50535	3.43353					
1.516	-2.829	3.15660	133.68950	-.16152	-.07571	.17659	.08277	1.50556	3.43434					
1.517	-2.315	3.14071	128.40920	-.13421	-.06281	.17539	.08209	1.50735	3.44114					
1.516	-1.806	3.11813	122.29740	-.10740	-.05020	.17281	.08078	1.50764	3.44224					
1.517	-1.293	3.09425	115.11640	-.08063	-.03764	.17036	.07954	1.50963	3.44979					
1.517	-.785	3.06965	106.98540	-.05360	-.02501	.16812	.07844	1.51046	3.45296					
1.517	-.278	3.03554	98.02251	-.02721	-.01269	.16506	.07697	1.51068	3.45379					
1.517	.215	2.99594	88.78275	-.00170	-.00079	.16375	.07627	1.51143	3.45665					
1.516	.720	2.96378	79.22566	.02384	.01110	.16272	.07580	1.51073	3.45399					
1.516	1.214	2.93013	70.30235	.05026	.02345	.16280	.07596	1.50958	3.44961					
1.516	0.4394	-12.92765	.05121	.02403	-.00249	-.00129	-.00137	.001170	.00520					

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM055) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1628/ O	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	3.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD	MPROBE	CPM	CPM	CPM	CPM	CPTD
1.541	-6.907	3.21425	156.05620	-35281	-16673	-17398	.08222	1.52763	3.51877	-0.2461				
1.542	-6.393	3.20822	154.41820	-31634	-14941	-16892	.07978	1.52892	3.52373	-0.2332				
1.542	-5.885	3.20718	152.54320	-28405	-13403	-16537	.07803	1.52957	3.52624	-0.2233				
1.542	-5.377	3.20166	150.43030	-25341	-11936	-16182	.07622	1.53176	3.53469	-0.2041				
1.542	-4.872	3.19919	148.00100	-22416	-10549	-15827	.07449	1.53195	3.53544	-0.2025				
1.542	-4.359	3.18727	145.21480	-19642	-09252	-15343	.07227	1.53117	3.53245	-0.2061				
1.542	-3.854	3.18269	141.95390	-17064	-08031	-14904	.07015	1.53175	3.53466	-0.2040				
1.541	-3.342	3.17158	138.13850	-14445	-06799	-14346	.06752	1.53138	3.53322	-0.2051				
1.541	-2.828	3.15687	133.64990	-11997	-05644	-13853	.06517	1.53186	3.53509	-0.2003				
1.542	-2.316	3.13952	128.40910	-09684	-04556	-13400	.06304	1.53229	3.53677	-0.1951				
1.542	-1.804	3.11832	122.25770	-07366	-03464	-12819	.06029	1.53282	3.53884	-0.1906				
1.542	-1.294	3.09905	115.07690	-05177	-02434	-12186	.05729	1.53284	3.53888	-0.1876				
1.542	-7.785	3.06380	106.98530	-03095	-01455	-11619	.05461	1.53311	3.53992	-0.1851				
1.542	-0.279	3.03501	98.02251	-01215	-00571	-11245	.05282	1.53380	3.54260	-0.1762				
1.542	.213	3.00076	88.78273	.00532	.00250	.10974	.05159	1.53338	3.54100	-0.1819				
1.542	.721	2.96330	79.18600	.02377	.01117	.10850	.05099	1.53398	3.54328	-0.1798				
1.542	1.214	2.92935	70.26273	.04302	.02022	.10740	.05047	1.53366	3.54208	-0.1807				
GRADIENT		-0.04432	-12.92421	.04356	.02050	-.00906	-.00428	.00045	.00172	.00051				

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

	RUN NO.	1582/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00	BETA	=	4.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPTD	MPROBE	CPM	CPM	CPM	CPM	CPTD
5.99	-6.858	4.24949	149.42250	-29281	-.05896	18600	.03746	.57176	1.24816	-.02128				
6.00	-5.832	4.22800	145.38480	-24992	-.05016	18533	.03719	.57766	1.25373	-.01700				
5.99	-4.815	4.21418	140.27920	-20749	-.04145	18450	.03686	.58322	1.25905	-.01260				
6.00	-3.790	4.19202	133.78740	-.16363	-.03264	18218	.03634	.58774	1.26342	-.00956				
6.00	-2.771	4.16277	125.55390	-.12133	-.02414	18025	.03586	.59080	1.26641	-.00715				
6.00	-1.750	4.11176	115.22160	-.07930	-.01575	17817	.03539	.59385	1.26940	-.00494				
6.01	-.733	4.05734	102.63280	-.03728	-.00742	17503	.03482	.59544	1.27097	-.00437				
6.00	.280	3.99131	88.49973	.00484	.00096	17291	.03429	.59597	1.27149	-.00328				
6.00	1.262	3.93608	74.68442	.04508	.00894	17128	.03395	.59634	1.27186	-.00295				
GRADIENT		-.04718	-10.91513	.04149	.00827	-.00223	-.00049	.00213	.00209	.00156				

(TCM056) (04 OCT 91)

## PARAMETRIC DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM056 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RUN NO. 1473/ 0			RN/L = 2.49			GRADIENT INTERVAL = -5.00/ 5.00			BETA	PHI	= 4.000	PROBE	CPM
		BETA	PHI	CPAQ	CPALPH	CPBQ	CPALPH	CPBQ	CPALPH	CPBQ					CPTD
.800	-6.904	4.17736	149.73940	-.28170	-.08516	.17733	.05361	.77095	1.48160	-.02876					
.800	-5.875	4.16506	145.66280	-.24186	-.07269	.17607	.05292	.7703	1.49035	-.02275					
.800	-4.859	4.15261	140.59720	-.20121	-.06014	.17497	.05229	.78246	1.49824	-.01721					
.800	-3.846	4.13470	134.18550	-.15966	-.04754	.17280	.05146	.78735	1.50543	-.01281					
.800	-2.835	4.11042	126.03180	-.11891	-.03529	.17147	.05089	.79093	1.51074	-.00931					
.800	-1.818	4.08163	115.66070	-.07922	-.02343	.16998	.05026	.79289	1.51365	-.00668					
.800	- .812	4.04518	103.19130	-.03838	-.01134	.16801	.04963	.79518	1.51707	-.00496					
.800	.202	3.99852	89.05830	-.00127	.00037	.16624	.04908	.79611	1.51848	-.00410					
.799	1.188	3.95684	75.20305	.04047	.01192	.16523	.04868	.79592	1.51819	-.00342					
GRADIENT		-.03272	-10.94020	.03990	.01189	-.00162	-.00060	.00220	.00327	.00224					
MACH	ALPHA	RUN NO. 1507/ 0			RN/L = 2.50			GRADIENT INTERVAL = -5.00/ 5.00			BETA	PHI	CPM	PROBE	CPTD
.900	-6.891	4.18953	149.65990	-.27030	-.09333	.17023	.05877	.87188	1.64109	.03025					
.900	-5.863	4.17680	145.58340	-.23231	-.07972	.16882	.05793	.87783	1.65149	-.02387					
.900	-4.846	4.16069	140.51750	-.19349	-.06604	.16723	.05708	.88330	1.66115	-.01812					
.900	-3.833	4.14211	134.10570	-.15365	-.05217	.16574	.05628	.88746	1.66858	-.01324					
.900	-2.821	4.12014	125.91250	-.11422	-.03867	.16448	.05568	.89118	1.67526	-.00969					
.900	-1.801	4.08190	115.54110	-.07590	-.02562	.16270	.05492	.89347	1.67941	-.00694					
.900	- .793	4.04097	103.03200	-.03687	-.01243	.16122	.05434	.89547	1.68304	-.00513					
.900	.217	3.99411	88.93874	.00111	.00037	.15918	.05357	.89598	1.68396	-.00410					
.900	1.202	3.94918	75.08360	.03893	.01310	.15836	.05328	.89654	1.68498	-.00368					
GRADIENT		-.03570	-10.94315	.03835	.01304	-.00152	-.00064	.00216	.00390	.00234					
MACH	ALPHA	RUN NO. 1513/ 0			RN/L = 2.50			GRADIENT INTERVAL = -5.00/ 5.00			BETA	PHI	CPM	PROBE	CPTD
1.099	-6.963	4.06395	150.17460	-.24668	-.10098	.14990	.06137	1.07370	2.06620	-.03131					
1.100	-5.943	4.05362	146.17820	-.21262	-.08654	.14858	.06048	1.08011	2.08223	-.02474					
1.100	-4.938	4.05366	141.15370	-.17820	-.07212	.14739	.05965	1.08464	2.09362	-.01900					
1.100	-3.933	4.04638	134.82240	-.14252	-.05739	.14633	.05892	1.08863	2.10373	-.01394					
1.100	-2.944	4.02605	126.74860	-.10771	-.04321	.14536	.05831	1.09187	2.11199	-.01010					
1.100	-1.930	4.02363	116.33910	-.07314	-.02926	.14513	.05805	1.09385	2.11704	-.00735					
1.100	-.922	4.01772	103.87050	-.03713	-.01482	.14440	.05765	1.09539	2.12100	-.00537					
1.100	.079	4.00208	89.93613	-.00246	-.00098	.14385	.05735	1.09649	2.12380	-.00399					
1.100	1.069	3.99352	76.12022	.03136	.01250	.14382	.05730	1.09657	2.12402	-.00359					
GRADIENT		-.00988	-10.96429	.03489	.01408	-.00059	-.00039	.00196	.00500	.00252					

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 600  
(TCM056) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1529/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	4.000	PHI	=	180.000	
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD					
MACH	4.15057	149.81850	.25298	-.11178	.15737	.06953	1.22244	2.47356	.03305						
1.250	-6.921	4.13643	145.74180	-.21754	.15631	.06859	1.22860	2.49194	.02586						
1.250	-5.887	4.12155	140.71600	-.18153	.15513	.06766	1.23419	2.50873	.01949						
1.250	-4.877	4.10816	134.26490	-.14470	.15303	.06642	1.23826	2.52102	.01453						
1.250	-3.862	4.09302	126.07210	-.10772	.15159	.06559	1.24004	2.52642	.01151						
1.250	-2.853	4.06620	115.78070	-.07202	.15030	.06488	1.24283	2.53488	.00894						
1.250	-1.843	4.03350	103.31150	-.03595	.14924	.06426	1.24457	2.54020	.00653						
1.250	-.837	3.99799	89.21825	-.00005	.14807	.06370	1.24484	2.54100	.00574						
1.250	-.174	3.96431	75.40262	.03473	.14194	.06339	1.24539	2.54268	.00530						
1.250	1.160	-.02664	-10.94761	.03582	.01557	-.00126	-.00070	.00182	.00552	.00231					
	RUN NO.	1546/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00							
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD					
MACH	4.13482	149.89760	.28036	-.13050	.17452	.08123	1.37042	2.94694	.03453						
1.400	-6.928	4.12286	145.82120	-.24103	.11138	.17446	.08061	2.96852	.02701						
1.400	-5.895	4.11271	140.75590	-.20113	.09238	.17222	.08016	2.98692	.02082						
1.400	-4.882	4.09459	134.38410	-.16110	.07365	.17038	.07790	1.38615	.01610						
1.400	-3.875	4.08467	126.15190	-.12110	.05511	.17014	.07743	1.39001	3.01443	.01145					
1.400	-2.864	4.05479	115.90010	-.08125	.03686	.16869	.07653	1.39290	3.02447	.00828					
1.400	-1.855	4.02972	103.43110	-.04062	.01840	.16697	.07563	1.39421	3.02902	.00669					
1.400	-.853	3.99795	89.33786	-.00060	.00027	.16563	.07490	1.39556	3.03373	.00510					
1.400	-.157	3.97251	75.48241	.03786	.01712	.16467	.07444	1.39647	3.03690	.00463					
1.400	1.146	-.02375	-10.95767	.03972	.01818	-.00125	-.00077	.00235	.00817	.00268					
	RUN NO.	1563/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00							
	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD					
MACH	4.23005	149.50120	.29277	-.13806	.18683	.08810	1.41951	3.11807	.03436						
1.450	-6.869	4.21365	145.38440	-.25176	.11800	.18623	.08729	1.42526	.02804						
1.450	-5.830	4.19999	140.27890	-.20995	.09780	.18344	.08545	1.43066	.02168						
1.450	-4.814	4.17772	133.78730	-.16769	.07783	.18022	.08365	1.43389	3.15787	.01800					
1.450	-3.794	4.14619	125.55380	-.12525	.05789	.18040	.08337	1.43852	3.18615	.01350					
1.450	-2.776	4.10800	115.14270	-.08358	.03849	.17936	.08259	1.44150	3.19692	.00983					
1.450	-1.752	4.05450	102.59360	-.04050	.01860	.17698	.08128	1.44329	3.20340	.00730					
1.450	-.738	3.98858	88.50029	-.00150	.00069	.17509	.08034	1.44420	3.20669	.00638					
1.450	.272	3.93746	74.72466	.04214	.01932	.17324	.07944	1.44537	3.21095	.00560					
1.450	1.252	-.04429	-10.92698	.04157	.01931	-.00156	-.00094	.00245	.00886	.00274					

PAGE 601  
 IA310 (AEDC 16TF-783) PROBE CALIBRATION  
 (TCM056) (04 OCT 91)

PARAMETRIC DATA									
RUN NO.		RN/L =		GRADIENT INTERVAL =		BETA =		PHI =	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM
1.470	-6.879	4.21094	149.58040	-30047	-14300	19030	.09056	1.43652	3.17895
1.471	-5.845	4.20001	145.46410	-25743	-12182	19013	.08997	1.44217	3.19935
1.471	-4.825	4.18551	140.35850	-21539	-10129	18814	.08847	1.44771	3.21942
1.484	-3.808	4.16357	133.90680	-16955	-08081	18220	.08684	1.45217	3.23567
1.470	-2.795	4.13864	125.67360	-12861	-05994	18340	.08548	1.45534	3.24724
1.470	-1.774	4.09765	115.30210	-08559	-03980	18152	.08441	1.45721	3.25409
1.470	-.761	4.04956	102.75310	-04219	-01956	17957	.08328	1.45876	3.25975
1.470	.249	3.99444	88.65981	.00054	.00025	17729	.08210	1.46048	3.26606
1.470	1.237	3.94701	74.80463	.04139	.01916	17586	.08140	1.46104	3.26811
GRADIENT	-.04031	-10.93783	.04224	.01990	-.00178	-.00116	.00212	.00775	.00247
RUN NO.		RN/L =		GRADIENT INTERVAL =		BETA =		PHI =	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM
1.493	-6.884	4.20034	149.62010	-31433	-15039	19894	.09518	1.45914	3.26115
1.493	-5.854	4.18525	145.54340	-27241	-12953	20030	.09524	1.46474	3.28173
1.493	-4.840	4.17575	140.43820	-22832	-10809	19895	.09419	1.46860	3.29596
1.493	-3.819	4.15193	133.98630	-18550	-08741	19954	.09403	1.47309	3.31258
1.493	-2.807	4.13026	125.75330	-13908	-06534	19936	.09366	1.47580	3.32262
1.493	-1.787	4.09201	115.38190	-09292	-04356	19729	.09249	1.47769	3.32964
1.493	-.776	4.04661	102.87270	-04958	-02152	19528	.09140	1.47864	3.33138
1.493	.235	3.99521	88.77942	.00056	.00026	19285	.09023	1.47896	3.33436
1.493	1.224	3.95112	74.92418	.04523	.02116	19100	.08933	1.47960	3.33676
GRADIENT	-.03779	-10.93195	.04539	.02142	-.00146	-.00086	.00168	.00624	.00200
RUN NO.		RN/L =		GRADIENT INTERVAL =		BETA =		PHI =	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM
1.516	-6.883	4.20008	149.62010	-35361	-16875	22456	.10716	1.48912	3.37232
1.516	-5.854	4.18588	145.54340	-30958	-14655	22748	.10769	1.49630	3.39931
1.517	-4.835	4.17332	140.43800	-26048	-12272	22587	.10641	1.50130	3.41821
1.516	-3.821	4.15747	133.98660	-20757	-09738	22321	.10472	1.50462	3.43077
1.517	-2.808	4.12953	125.79300	-15560	-07297	22171	.10398	1.50540	3.43372
1.516	-1.787	4.09169	115.42160	-10655	-04994	22355	.10478	1.50563	3.43459
1.517	-.777	4.04643	102.91240	-05451	-02551	22262	.10420	1.50739	3.44130
1.516	.234	3.99584	88.81911	.00103	-.00048	22081	.10330	1.50715	3.44039
1.517	1.222	3.95235	74.96390	.05037	.02356	21915	.10250	1.50773	3.44257
GRADIENT	-.03775	-10.93241	.05110	.02402	-.00085	-.00051	.00093	.00353	.00108

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 602

(TCM056) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.542	-6.883	4.19924	149.62000	-.35766	-.16925	.22646	.10716	1.52691	3.51597	-.02532
1.541	-5.851	4.18868	145.50380	-.29012	-.13685	.21729	.10250	1.52941	3.52564	-.02266
1.541	-4.835	4.17156	140.43780	-.22979	-.10813	.20750	.09764	1.53159	3.53407	-.02019
1.541	-3.823	4.15476	133.98650	-.17641	-.08298	.19798	.09313	1.53194	3.53539	-.01991
1.541	-2.806	4.13013	125.75330	-.12528	-.05897	.18734	.08818	1.53137	3.53322	-.02051
1.542	-1.788	4.09666	115.38210	-.07802	-.03670	.17779	.08364	1.53201	3.53570	-.01996
1.541	-.777	4.05158	102.87280	-.03231	-.01519	.17065	.08023	1.53265	3.53817	-.01929
1.541	.238	4.00059	88.73972	-.01179	.00554	.16500	.07754	1.53273	3.53846	-.01894
1.541	1.221	3.95213	74.96390	.05430	.02552	.16232	.07628	1.53240	3.53718	-.01900
GRADIENT		-.03689	-10.93480	.04667	.02196	-.00771	-.00365	.000199	.00072	.00024

IA310 (AEDC 16TF-783) PROBE CALIBRATION

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.599	-7.870	4.25640	152.70660	-.33570	-.06805	.18710	.03792	.56412	1.24106	-.02733
.599	-6.844	4.24066	149.42140	-.29292	-.05895	.18597	.03743	.57101	1.24746	-.02159
.600	-5.828	4.22444	145.38450	-.25008	-.05024	.18513	.03719	.57779	1.25385	-.01718
.600	-4.806	4.20658	140.27850	-.20685	-.04137	.18397	.03679	.58289	1.25873	-.01306
.600	-3.789	4.18516	133.82680	-.16318	-.03256	.18124	.03616	.58781	1.26349	-.00961
.601	-2.768	4.15818	125.55370	-.12094	-.02411	.17971	.03583	.59093	1.26653	-.00756
.601	-1.750	4.11105	115.22160	-.07918	-.01576	.17749	.03532	.59420	1.26975	-.00519
.601	-.736	4.05594	102.67250	-.03697	-.00734	.17529	.03482	.59620	1.27173	-.00356
.601	.277	3.99078	88.53943	-.00422	-.00084	.17249	.03425	.59691	1.27243	-.00304
.600	1.258	3.93134	74.72423	-.04463	-.00884	.17149	.03398	.59692	1.27244	-.00254
.600	2.239	3.87647	62.25543	.08605	.01705	.16946	.03358	.59700	1.27251	-.00250
GRADIENT		-.04880	-11.38720	.04140	.00825	-.00206	-.00046	.00195	.00191	.00147

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM057 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1748/ O	RN/L =	2.51	GRADIENT	INTERVAL	=	-5.00/	5.00	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.800	-7.906	4.18081	152.98310	- .32334	- .09848	.1726	.05399	.76215	1.46914	.03709
.800	-6.883	4.17124	149.69870	- .28120	- .08504	.17595	.05321	.76990	1.48010	.02953
.799	-5.871	4.16169	145.66250	- .24188	- .07265	.17572	.05278	.77589	1.48870	.02318
.800	-4.856	4.14890	140.59690	- .20096	- .06013	.17444	.05220	.78215	1.49779	.01788
.800	-3.843	4.13073	134.18520	- .15976	- .04759	.17257	.05141	.78691	1.50478	.01322
.800	-2.830	4.10788	125.99190	- .11884	- .03526	.17123	.05080	.79042	1.50999	.00950
.800	-1.817	4.07677	115.66060	- .07896	- .02338	.16943	.05016	.79344	1.51448	.00685
.800	- .808	4.03550	103.15150	- .03832	- .01132	.16811	.04966	.79510	1.51696	.00497
.800	- .201	3.99314	89.05832	- .00124	.00037	.16596	.04898	.79630	1.51876	.00391
.800	1.186	3.95161	75.20316	.04001	.01179	.16512	.04866	.79655	1.51913	.00318
.800	2.172	3.91406	62.73386	.07971	.02349	.16401	.04833	.79635	1.51884	.00326
	GRADIENT	- .03462	- 11.40125	.03984	.01186	- .00151	- .00055	.00198	.00294	.00203

RUN NO. 1661/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1661/ O	RN/L =	2.50	GRADIENT	INTERVAL	=	-5.00/	5.00	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
.900	-7.899	4.19088	152.94330	- .30892	- .10757	.17057	.05940	.86428	1.62796	.03882
.900	-6.870	4.18358	149.61920	- .26908	- .09300	.16956	.05860	.87098	1.63951	.03129
.900	-5.859	4.17404	145.58310	- .23149	- .07945	.16888	.05797	.87718	1.65035	.02432
.900	-4.845	4.16041	140.51740	- .19253	- .06572	.16729	.05711	.88221	1.65923	.01879
.900	-3.830	4.13857	134.10550	- .15281	- .05191	.16578	.05631	.88705	1.66784	.01366
.900	-2.815	4.11785	125.87260	- .11359	- .03846	.16441	.05566	.89102	1.67497	.00980
.900	-1.801	4.08214	115.54110	- .07522	- .02541	.16265	.05494	.89375	1.67992	.00718
.900	- .791	4.03597	103.03190	- .03641	- .01227	.16110	.05428	.89528	1.68268	.00507
.900	- .217	3.99413	88.93874	.00159	.00054	.15915	.05358	.89630	1.68455	.00417
.900	1.202	3.94896	75.08360	.03864	.01300	.15805	.05316	.89670	1.68527	.00346
.899	2.188	3.90872	62.61433	.07675	.02579	.15702	.05276	.89626	1.68447	.00316
	GRADIENT	- .03699	- 11.39895	.03819	.01296	- .00151	- .00063	.00195	.00350	.00213

RUN NO. 1740/ O RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1740/ O	RN/L =	2.51	GRADIENT	INTERVAL	=	-5.00/	5.00	
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.098	-7.920	4.10813	153.02310	- .28060	- .11580	.15120	.06240	.1.06564	2.04627	.04023
1.100	-6.942	4.05927	150.13400	- .24577	- .10082	.14906	.06115	.1.07310	2.06472	.03295
1.101	-5.939	4.05172	146.17800	- .21214	- .08647	.14885	.06067	.1.07976	2.08133	.02585
1.101	-4.931	4.04692	141.15310	- .17749	- .07191	.14771	.05984	.1.08483	2.09410	.01963
1.101	-3.931	4.04161	134.82210	- .14213	- .05729	.14650	.05905	.1.08858	2.10362	.01463
1.100	-2.939	4.02353	126.74840	- .10733	- .04308	.14566	.05847	.1.09157	2.11122	.01061
1.100	-1.922	4.02148	116.29930	- .07298	- .02921	.14509	.05806	.1.09385	2.11704	.00767
1.100	- .925	4.00596	103.91000	- .03733	- .01491	.14448	.05770	.1.09553	2.12136	.00560
1.100	-.080	3.99810	89.93614	- .00267	- .00106	.14426	.05751	.1.09616	2.12296	.00410
1.100	1.066	3.98393	76.12041	.03064	.01221	.14385	.05733	.1.09687	2.12479	.00366
1.100	2.063	3.97495	63.61060	.06554	.02612	.14412	.05743	.1.09703	2.12521	.00351
	GRADIENT	- .01052	- 11.41795	.03470	.01398	- .00051	- .00034	.00170	.00433	.00225

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM057) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1724/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	BETA	PHI	CPAQ	CPALPH	CPBQ	CPALPH	CPBETA	CPBETA	CPBM	CPTD
MACH	ALPHA	4.14758	153.10130	-28951	-12907	.15757	.07025	1.21437	2.44962	-.04259
1.249	-7.925	4.14256	149.77750	-25218	-.11157	.15728	.06958	1.22154	2.47088	-.03435
1.250	-6.894	4.14256	145.74160	-21701	-.09531	.15672	.06883	1.22764	2.48906	-.02678
1.250	-5.883	4.13406	140.71570	-18126	-.07910	.15554	.06788	1.23358	2.50690	-.02007
1.250	-4.873	4.11884	140.71570	-14412	-.06259	.15329	.06658	1.23776	2.51952	-.01512
1.250	-3.862	4.10884	134.26500	-10731	-.04643	.15191	.06573	1.24041	2.52755	-.01154
1.250	-2.850	4.08879	126.07190	-07177	-.03097	.15072	.06504	1.24275	2.53466	-.00874
1.250	-1.841	4.06222	115.78060	-03575	-.01540	.14938	.06433	1.24442	2.53973	-.00663
1.250	-8.36	4.02876	103.31140	-00009	-.00004	.14808	.06368	1.24554	2.54313	-.00531
1.250	.173	3.99293	89.21826	03432	.01475	.14722	.06329	1.24603	2.54463	-.00488
1.250	1.158	3.95994	75.40271	06954	.02989	.14660	.06300	1.24589	2.54422	-.00470
1.250	2.153	3.92881	62.89348	03563	.01546	-.00125	-.00068	.00172	.00521	.00213
GRADIENT		-.02839	-11.40094							

RUN NO. 1716/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	BETA	PHI	CPAQ	CPALPH	CPBQ	CPALPH	CPBETA	CPBETA	CPBM	CPTD
MACH	ALPHA	4.13265	149.89730	-27829	-.12965	.17391	.08102	1.37020	2.94619	-.03533
1.400	-6.923	4.12327	145.82120	-23960	-.11082	.17367	.08032	1.37591	2.96576	-.02794
1.400	-5.895	4.10988	140.75570	-19985	-.09187	.17198	.07906	1.38169	2.98563	-.02158
1.400	-4.878	4.09794	134.34450	-16052	-.07341	.16984	.07767	1.38613	3.00096	-.01630
1.400	-3.872	4.07845	126.19130	-12072	-.05494	.16930	.07705	1.38962	3.01307	-.01156
1.400	-2.865	4.05645	115.86040	-08142	-.03693	.16825	.07632	1.39292	3.02453	-.00813
1.400	-1.852	4.02503	103.43100	-.04110	-.01860	.16666	.07543	1.39423	3.02909	-.00607
1.399	-.851	4.02503	89.33786	-.00159	-.00072	.16542	.07476	1.39582	3.03462	-.00453
1.400	1.157	3.99823	75.43470	036379	.01643	.16461	.07434	1.39662	3.03744	-.00369
1.400	1.145	3.96750	63.01294	07579	.03423	.16412	.07412	1.39719	3.03940	-.00364
1.400	2.133	3.93760	50.00000	0.3932	.01796	-.00112	-.00070	.00215	.00746	.00252
GRADIENT		-.02528	-11.41113							

RUN NO. 1706/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	BETA	PHI	CPAQ	CPALPH	CPBQ	CPALPH	CPBETA	CPBETA	CPBM	CPTD
MACH	ALPHA	4.28198	152.51090	-33578	-.16006	.19145	.09126	1.41053	3.08624	-.04551
1.450	-7.874	4.22653	149.42080	-29310	-.13880	.18645	.08829	1.41634	3.10681	-.03863
1.450	-6.841	4.21435	145.38440	-25240	-.11863	.18649	.08765	1.42404	3.13419	-.03062
1.451	-5.831	4.19739	140.27870	-.21100	-.09853	.18422	.08602	1.42879	3.15118	-.02411
1.450	-4.811	4.17443	133.78710	-.16907	-.07854	.18168	.08440	1.43384	3.16929	-.01874
1.450	-3.790	4.14279	125.55360	-.12675	-.05858	.18213	.08418	1.43756	3.18270	-.01375
1.450	-2.773	4.10373	115.14260	-.08509	-.03914	.18152	.08350	1.44256	3.20076	-.00883
1.450	-1.750	4.04959	102.63330	-.04203	-.01923	.17940	.08230	1.44434	3.20721	-.00619
1.450	-.740	3.98396	88.50031	00051	-.00024	.17713	.08116	1.44512	3.21005	-.00496
1.450	.272	3.93214	74.68506	04066	.01862	.17553	.08036	1.44696	3.21670	-.00395
1.450	1.254	3.88722	62.25562	0.8223	.03764	.17476	.07999	1.44711	3.21727	-.00373
1.450	2.240	3.88722	50.00000	0.4162	.01930	-.00135	-.00086	.00258	.00932	.00291
GRADIENT		-.04616	-11.38634							

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM057) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1699/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
CPTD										
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.469	-7.887	4.25398	152.62900	-34758	-16549	-19552	.09309	1.43469	3.17234	-.04616
1.469	-6.855	4.20863	149.50010	-30471	-14401	-19192	.09071	1.44135	3.19639	-.03844
1.470	-5.841	4.19646	145.46380	-26359	-12349	-19310	.09047	1.44978	3.22695	-.02924
1.469	-4.822	4.18117	140.35820	-21933	-10212	-18954	.08825	1.45464	3.24469	-.02290
1.469	-3.808	4.16221	133.90670	-17533	-08131	-18715	.08679	1.45827	3.25797	-.01887
1.469	-2.789	4.12911	125.67310	-13123	-06063	-18559	.08575	1.46159	3.27014	-.01506
1.469	-1.769	4.09344	115.26220	-08824	-04065	-18452	.08500	1.46427	3.28001	-.01199
1.469	-761	4.04852	102.75310	-04439	-02039	-18234	.08377	1.46689	3.28965	-.00929
1.469	-249	3.98844	88.65982	-00101	-00046	-18034	.08273	1.46780	3.29300	-.00796
1.469	1.232	3.944203	74.84445	.04017	.01842	-17910	.08212	1.46867	3.29624	-.00740
1.469	2.221	3.89549	62.37534	.08238	.03777	-17823	.08171	1.46830	3.29485	-.00724
1.469	GRADIENT	-0.04213	-11.39398	.04283	.01984	-0.0162	-.00094	.00200	.00735	.00226
CPTD										
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.497	-7.845	4.25233	152.46960	-35156	-16939	-19907	.09592	1.45709	3.25366	-.04870
1.497	-6.858	4.19489	149.53950	-31107	-14901	-19639	.09408	1.46287	3.27486	-.04257
1.497	-5.849	4.18529	145.50350	-27075	-12869	-19810	.09415	1.46966	3.29988	-.03435
1.497	-4.833	4.16829	140.43760	-22753	-10744	-19726	.09315	1.47594	3.32314	-.02766
1.497	-3.821	4.15075	133.98620	-18279	-08617	-19548	.09215	1.47717	3.32771	-.02599
1.497	-2.796	4.12391	125.71330	-13691	-06455	-19466	.09177	1.47691	3.32673	-.02611
1.497	-1.783	4.08769	115.38180	-09261	-04355	-19355	.09103	1.47921	3.33529	-.02360
1.496	-774	4.04097	102.87260	-04652	-02166	-19206	.08943	1.48714	3.36492	-.01370
1.497	.235	3.98963	88.77943	-.00075	-.00035	-18985	.08826	1.48928	3.37291	-.01194
1.496	1.217	3.94157	74.96413	.04248	.01974	-18811	.08739	1.48946	3.37359	-.01139
1.497	2.207	3.90343	62.49478	.08672	.04030	-18618	.08652	1.48956	3.37397	-.01162
1.497	GRADIENT	-0.03958	-11.39100	.04470	.02103	-.00154	-.00097	.00239	.00891	.00281
CPTD										
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.521	-7.847	4.24447	152.50860	-37264	-18045	-21117	.10226	1.48103	3.34208	-.05027
1.520	-6.866	4.19827	149.53990	-33587	-16131	-21184	.10174	1.48816	3.36871	-.04163
1.521	-5.849	4.18359	145.50330	-29581	-14095	-21601	.10293	1.49573	3.39718	-.03334
1.520	-4.830	4.17038	140.39790	-25168	-11910	-21727	.10282	1.50140	3.41859	-.02631
1.521	-3.814	4.15016	133.94640	-20354	-09596	-21704	.10233	1.50510	3.43259	-.02234
1.521	-2.803	4.12581	125.75310	-15590	-07337	-21703	.10214	1.50695	3.43960	-.02038
1.521	-1.785	4.08687	115.38180	-10767	-05059	-21960	.10319	1.50852	3.44557	-.01873
1.520	-777	4.04067	102.87260	-05648	-02651	-22024	.10339	1.50833	3.44486	-.01795
1.520	.237	3.98957	88.70003	-.00395	-.00185	-21915	.10278	1.50943	3.44904	-.01699
1.520	1.220	3.94106	74.88470	.04664	.02186	-21781	.10211	1.51016	3.45182	-.01660
1.520	2.207	3.90374	62.45505	.09634	.04518	-21392	.10031	1.50982	3.45053	-.01689
1.520	GRADIENT	-0.03980	-11.40129	.04960	.02339	-.00015	-.00019	.00108	.00412	.00125

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 606

IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM057 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1680/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	4.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD		
1.541	-7.888	4.24839	152.62940	.42734	.20341	.24431	.11629	1.52048	3.49128	-.03039		
1.543	-6.862	4.19379	149.57940	.36693	.17446	.22660	.10773	1.52417	3.50543	-.02878		
1.542	-5.847	4.18585	145.50350	.30003	.14223	.22055	.10455	1.52518	3.50932	-.02606		
1.545	-4.831	4.16867	140.43760	.23737	.11230	.20735	.09810	1.53081	3.53104	-.02339		
1.544	-3.819	4.15155	133.98630	.18419	.08713	.19756	.09345	1.52971	3.52680	-.02345		
1.543	-2.800	4.12160	125.75290	.13014	.06154	.18821	.08900	1.52927	3.52509	-.02297		
1.543	-1.781	4.08846	115.34210	.08512	.04024	.17988	.08503	1.52966	3.52659	-.02251		
1.543	-7.775	4.04624	102.87270	.03834	.01812	.17352	.08199	1.52947	3.52587	-.02201		
1.543	.234	3.99473	88.77942	.00756	.00357	.16879	.07972	1.53053	3.52996	-.02144		
1.543	1.217	3.94165	74.96413	.04986	.02355	.16731	.07900	1.53043	3.52956	-.02126		
1.543	2.207	3.90359	62.49478	.09425	.04451	.16783	.07926	1.53084	3.53113	-.02129		
GRADIENT		- .03933	- 11.39554	.04674	.02210	- .00584	- .00278	.00009	.000033	.000019		

IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM058 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1673/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	=	-8.000	PHI	=	180.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD		
.600	-3.745	-8.12003	-154.59460	.35668	.07236	.16561	-.03360	.56548	1.24230	-.02675		
.600	-2.728	-8.09194	-160.63090	.35172	.07118	.12151	-.02459	.56774	1.24441	-.02483		
.600	-1.724	-8.06150	-167.10840	.34789	.07030	.07644	-.01545	.56927	1.24583	-.02359		
.600	-.718	-8.02806	-173.98750	.34305	.06931	.03141	-.00635	.57009	1.24660	-.02307		
.600	-.289	-7.99048	.81574	.34258	.06924	.01034	-.00209	.57101	1.24745	-.02261		
.600	-.737	-8.02855	-.6.43835	.34232	.06918	.03221	.00651	.57009	1.24659	-.02313		
.600	1.747	-8.06365	-13.33591	.34443	.06968	.07800	.01578	.56903	1.24561	-.02400		
.600	2.757	-8.08929	-19.83659	.34631	.07019	.12270	.02487	.56699	1.24371	-.02566		
.600	3.771	-8.12001	-25.82115	.34791	.07070	.16814	.03417	.56381	1.24077	-.02812		
GRADIENT			- .00039	.24.46570	.00105	.00019	.04442	.00901	-.000019	.000018		

## PARAMETRIC DATA

RUN NO.		1749 / O		RN/L =	2.51	GRADIENT	INTERVAL	=	-5.00/	5.00	CPMD
BETA	ACH	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
.800	-3.820	-8.08718	-154.31800	-34026	-10359	-16141	-04914	-76340	1.47089	-.03617	
.800	-2.803	-8.06085	-160.35460	-33530	-10184	-11920	-03620	-76595	1.47450	-.03364	
.801	-1.801	-8.04366	-166.83270	-32992	-10014	-07515	-02281	-76908	1.47894	-.03152	
.800	-.790	-8.01912	-173.75140	-32787	-09940	-03285	-00996	-76942	1.47942	-.03081	
.800	-.211	-7.99638	.54110	-32754	-0916	-00742	-00225	-76907	1.47892	-.03048	
.800	-.832	-8.02277	-6.83057	-32716	-0913	.03495	.01059	-76825	1.47776	-.03129	
.800	1.835	-8.04341	-13.68938	-32894	-0976	-07856	-02383	-76669	1.47555	-.03262	
.800	2.841	-8.06651	-20.15115	-33081	-10048	-12079	-03669	-76466	1.47268	-.03446	
.799	3.845	-8.08251	-26.09766	-33134	-10099	.16355	.04985	-76197	1.46888	-.03749	
.800	GRADIENT	-.00022	24.07102	.00091	.00027	.04240	.01290	-.00028	-.000040	-.00019	
RUN NO.		1662 / O		RN/L =	2.50	GRADIENT	INTERVAL	=	-5.00/	5.00	CPMD
BETA	ACH	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
.900	-3.810	-8.09521	-154.35770	-32631	-11348	-15246	-05302	.86525	1.62962	-.03762	
.900	-2.784	-8.06354	-160.43320	-32098	-11135	-11311	-03924	.86719	1.63297	-.03525	
.900	-1.783	-8.04670	-166.91140	-31720	-10987	-07183	-02488	.86928	1.63657	-.03333	
.900	-.778	-8.02089	-173.79060	-31378	-10857	-03072	-01063	.87069	1.63902	-.03199	
.900	-.229	-7.98458	.61951	-31432	-10875	-00736	-00255	.87034	1.63840	-.03218	
.900	-.808	-8.02472	-6.71301	-31364	-10856	.03373	.01167	.86950	1.63695	-.03286	
.900	1.812	-8.04873	-13.57169	-31495	-10912	.07524	.02620	.86827	1.63483	-.03402	
.900	2.821	-8.06891	-20.07291	-31628	-10983	.11569	.04017	.86676	1.63223	-.03602	
.900	3.820	-8.09054	-25.97997	-31746	-11051	.15676	.05457	.86377	1.62710	-.03890	
.900	GRADIENT	-.00033	24.18089	.00096	.00032	.04066	.01413	-.00019	-.000033	-.00018	
RUN NO.		1741 / O		RN/L =	2.51	GRADIENT	INTERVAL	=	-5.00/	5.00	CPMD
BETA	ACH	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
.999	-3.936	-8.03657	-153.92270	-29287	-12082	-14272	-05888	1.06671	2.04890	-.03953	
.999	-2.917	-8.02176	-159.95980	-28879	-11891	-10657	-04388	1.07016	2.05741	-.03675	
.999	-1.913	-8.01587	-166.43790	-28652	-11774	-06993	-02874	1.07180	2.06148	-.03471	
.999	-.911	-8.00806	-173.27770	-28399	-11661	-03245	-01333	1.07327	2.06513	-.03358	
.999	-.087	-7.98241	.18960	-28427	-11666	-00197	-00081	1.07108	2.05969	-.03413	
.999	-.963	-8.00880	-7.22119	-28376	-11653	.03589	.01474	1.07109	2.05973	-.03459	
.999	1.957	-8.01215	-14.04171	-28438	-11697	.07318	.03010	1.07045	2.05913	-.03595	
.999	2.958	-8.02534	-20.54465	-28518	-11748	.10955	.04513	1.06800	2.05209	-.03801	
.999	3.965	-8.02902	-26.53169	-28511	-11784	.14633	.06048	1.06645	2.04825	-.04093	
.999	GRADIENT	-.00039	23.46630	.00079	.00030	.03669	-.00018	-.000052	-.00021	-.00022	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 608

( TCM058 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.249	-3.888	-8.03195	-153.88320	-29997	-13350	-14701	-06543	1.21608	2.45468	-0.04065
1.250	-2.831	-8.05415	-160.27580	-29800	-13240	-10698	-04753	1.21831	2.46128	-0.3866
1.250	-1.820	-8.03388	-166.79290	-29505	-13087	-06868	-03046	1.21975	2.46555	-0.3688
1.250	-8.21	-8.01967	-173.63290	-29262	-12961	-03039	-01346	1.22070	2.46836	-0.3548
1.250	-178	-7.98213	-46341	-29116	-12898	-00530	-00235	1.22044	2.46760	-0.3570
1.250	.872	-8.01973	-6.94731	-29128	-12917	-03340	.01481	1.21997	2.46621	-0.3663
1.249	1.869	-8.03884	-13.76713	-29198	-12964	.07180	.03188	1.21826	2.46111	-0.3816
1.250	2.876	-8.05425	-20.26881	-29308	-13039	.10894	.04847	1.21679	2.45676	-0.04015
1.250	3.887	-8.07186	-26.25471	-29349	-13099	.14708	.06564	1.21431	2.44942	-0.04342
	GRADIENT	-.00318	23.78773	.00083	.00033	.03785	.01685	-.00027	-.00081	-.00034
RUN NO.	1725/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00			
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.400	-3.903	-8.02887	-153.84410	-32892	-15428	-15986	-07498	1.36362	2.92378	-0.4254
1.400	-2.844	-8.04759	-160.23640	-32741	-15322	-11604	-05430	1.36586	2.93141	-0.4007
1.399	-1.841	-8.03320	-166.71450	-32505	-15180	-07366	-03440	1.36706	2.93551	-0.3805
1.400	-.835	-8.01207	-173.59370	-32248	-15044	-03228	-01506	1.36830	2.93973	-0.3692
1.400	-.159	-7.99259	.34513	-32192	-15011	-00212	-00099	1.36895	2.94194	-0.3638
1.400	.885	-8.01789	-7.02647	-32244	-15044	.03947	.01842	1.36864	2.94089	-0.3690
1.400	1.888	-8.03352	-13.88564	-32278	-15084	.08156	.03811	1.36716	2.93582	-0.3863
1.400	2.883	-8.04470	-20.30904	-32387	-15163	.12301	.05759	1.36543	2.92996	-0.4055
1.400	3.894	-8.06613	-26.29498	-32395	-15219	.16549	.07775	1.36241	2.91970	-0.4414
	GRADIENT	-.00269	23.74498	.00061	.00026	.04171	.01955	-.00010	-.00035	-.00016
RUN NO.	1717/ O	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00			
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.400	-3.903	-8.02887	-153.84410	-32892	-15428	-15986	-07498	1.36362	2.92378	-0.4254
1.400	-2.844	-8.04759	-160.23640	-32741	-15322	-11604	-05430	1.36586	2.93141	-0.4007
1.399	-1.841	-8.03320	-166.71450	-32505	-15180	-07366	-03440	1.36706	2.93551	-0.3805
1.400	-.835	-8.01207	-173.59370	-32248	-15044	-03228	-01506	1.36830	2.93973	-0.3692
1.400	-.159	-7.99259	.34513	-32192	-15011	-00212	-00099	1.36895	2.94194	-0.3638
1.400	.885	-8.01789	-7.02647	-32244	-15044	.03947	.01842	1.36864	2.94089	-0.3690
1.400	1.888	-8.03352	-13.88564	-32278	-15084	.08156	.03811	1.36716	2.93582	-0.3863
1.400	2.883	-8.04470	-20.30904	-32387	-15163	.12301	.05759	1.36543	2.92996	-0.4055
1.400	3.894	-8.06613	-26.29498	-32395	-15219	.16549	.07775	1.36241	2.91970	-0.4414
	GRADIENT	-.00269	23.74498	.00061	.00026	.04171	.01955	-.00010	-.00035	-.00016
RUN NO.	1707/ O	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00			
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.450	-3.759	-8.11366	-154.55510	-35169	-16477	-16473	-07844	1.41159	3.09000	-0.4438
1.450	-2.736	-8.08449	-160.63080	-34780	-16510	-12023	-05707	1.41400	3.09851	-0.4118
1.450	-1.725	-8.05799	-167.14760	-34453	-16335	-07512	-03562	1.41589	3.10521	-0.3972
1.449	-.724	-8.02725	-173.98740	-34078	-16143	-03117	-01477	1.41562	3.10425	-0.3908
1.450	-.271	-7.98415	.73730	-33855	-16060	-00885	-00420	1.41532	3.10320	-0.4036
1.450	.768	-8.03004	-6.59509	-34005	-16147	.03486	.01655	1.41371	3.09748	-0.4151
1.450	1.777	-8.05844	-13.49298	-34080	-16206	.07949	.03780	1.41268	3.09385	-0.4296
1.450	2.768	-8.08418	-19.87639	-34136	-16275	.12232	.05832	1.41093	3.08767	-0.4557
1.450	3.794	-8.11296	-25.93954	-34112	-16326	.16694	.07989	1.40701	3.07386	-0.4970
	GRADIENT	-.00042	24.38586	.00124	.00047	.04398	.02096	-.0006	-.00231	-.00079

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM058 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1700/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00					
	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	CPTD				
MACH	1.469	-3.779	-8.10153	-154.47600	-36180	-17220	-17034	1.43534	3.17467	-0.04520			
	1.469	-2.756	-8.07479	-160.55180	-35809	-16998	-12465	.05917	1.43796	3.18414	-0.04229		
	1.470	-1.751	-8.05006	-167.02940	-35566	-16852	-07843	.03716	1.43993	3.19124	-0.04030		
	1.470	-1.739	-8.02354	-173.94780	-35365	-16738	-03296	.01560	1.44075	3.19421	-0.03916		
	1.469	-1.254	-7.98963	-698.3	-35796	-16944	-06556	.00310	1.44027	3.19246	-0.03924		
	1.469	.796	-8.02680	-6.71268	-35951	-17048	.03912	.01855	1.43888	3.18745	-0.04107		
	1.470	1.798	-8.05319	-13.57155	-35954	-17080	.08559	.04066	1.43793	3.18403	-0.04289		
	1.470	2.797	-8.07956	-19.99408	-35945	-17120	.13138	.06257	1.43528	3.17446	-0.04562		
	1.470	3.814	-8.10294	-26.01857	-35909	-17158	.17682	.08449	1.43234	3.16391	-0.04911		
GRADIENT			- .00085	24.25892	.00010	.00015	.04591	.02186	- .00047	-.00170	-.00060		
	RUN NO.	1693/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00					
	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	CPTD				
MACH	1.498	-3.792	-8.10099	-154.43660	-36764	-17748	-17184	.08296	1.45676	3.25244	-0.05087		
	1.497	-2.773	-8.06897	-160.47290	-36426	-17561	-12452	.06003	1.45745	3.25497	-0.04958		
	1.497	-1.764	-8.04736	-166.99000	-36175	-17412	-07897	.03801	1.45831	3.25810	-0.04797		
	1.496	-1.758	-8.02195	-173.86920	-35983	-17299	-03276	.01575	1.45894	3.26042	-0.04687		
	1.494	-1.240	-7.98175	.65907	-35915	-17287	-00658	.00317	1.45510	3.24637	-0.04893		
	1.495	.813	-8.02710	-6.79119	-36188	-17437	.03948	.01902	1.45546	3.24766	-0.04998		
	1.496	1.807	-8.05336	-13.57139	-36207	-17474	.08628	.04164	1.45507	3.24627	-0.05154		
	1.495	2.811	-8.07690	-20.03319	-36246	-17516	.13191	.06375	1.45303	3.23880	-0.05321		
	1.496	3.820	-8.09653	-26.01884	-36204	-17548	.17771	.08614	1.45103	3.23150	-0.05647		
GRADIENT			- .00071	24.21758	.00045	.00012	.04595	.02220	-.00081	-.000297	-.00078		
	RUN NO.	1688/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00					
	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPM	CPTD				
MACH	1.521	-3.835	-8.05563	-154.08130	-38444	-18607	-18400	.08906	1.48156	3.34406	-0.04956		
	1.521	-2.770	-8.06852	-160.51250	-38731	-18709	-13220	.06386	1.48325	3.35034	-0.04745		
	1.520	-1.767	-8.04503	-166.99040	-38757	-18677	.08245	.03973	1.48514	3.35742	-0.04503		
	1.520	-1.756	-8.02599	-173.90900	-38789	-18665	-03343	.01608	1.48633	3.36188	-0.04350		
	1.520	-1.234	-7.98188	.61990	-40419	-19388	-00689	.00330	1.48915	3.37243	-0.03989		
	1.521	.803	-8.02817	-6.71273	-40530	-19453	-04376	.02100	1.48960	3.37413	-0.04030		
	1.521	1.812	-8.05201	-13.61065	-40632	-19522	.09635	.04629	1.48858	3.37030	-0.04135		
	1.520	2.823	-8.07235	-20.11159	-40285	-19394	.14724	.07088	1.48610	3.36101	-0.04359		
	1.520	3.821	-8.09557	-26.01869	-40016	-19331	.19659	.09497	1.48299	3.34940	-0.04719		
GRADIENT			- .00367	24.08367	.00283	.00128	.04981	.02405	.00041	.00153	.00053		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 610

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM058) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1681/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	=	-8.000	PHI	=	180.000
1.543	-3.791	-8.10001	-154.43640	.44106	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD		
1.545	-2.772	-8.06755	-160.47270	.43336		.20660	.15585	.07430	1.52343	3.50259	.03110		
1.544	-1.765	-8.05076	-166.99010	.43004		.20494	.10222	.04871	1.52293	3.50067	.03086		
1.543	-758	-8.02031	-173.86920	.42662		.20322	.04683	.02231	1.52250	3.49903	.03049		
1.542	-236	-7.99566	-6.1957	.41073		.19552	.01085	.00516	1.52201	3.49712	.02994		
1.544	.806	-8.02594	-6.75226	.41424		.19719	.03984	.01896	1.52423	3.50567	.02959		
1.543	1.817	-8.05424	-13.65002	.41492		.19756	.09666	.04603	1.52239	3.49860	.03012		
1.543	2.816	-8.07807	-20.07256	.42315		.20155	.19243	.07260	1.52263	3.49953	.03032		
1.544	3.829	-8.10156	-26.05771	.43199		.20590	.21267	.10136	1.52284	3.50034	.03084		
GRADIENT		-.001116	24.18412	.00184		.00090	.05530	.02635	.00002	.00008	.00010		

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM059) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1676/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	=	2.000	PHI	=	180.000
.600	-4.121	1.74561	-65.15240	.06654	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD		
.600	-3.141	1.74456	-58.55591	.06545		.01297	.12142	.02405	.59794	1.27155	.00317		
.600	-2.191	1.76882	-47.92062	.06542		.01294	.08125	.01607	.59874	1.27345	.00188		
.600	-1.256	1.85255	-29.96002	.06679		.01320	.04240	.00838	.59895	1.27425	.00101		
.600	-.303	1.97733	-3.76217	.07101		.01403	.00351	.00069	.59955	1.27445	.00076		
.600	.734	2.12167	23.62424	.07763		.01536	.03750	.00742	.59947	1.27506	.00035		
.600	1.785	2.19577	42.73302	.08129		.01607	.08197	.01621	.59945	1.27497	.00058		
.600	2.833	2.25106	54.35518	.08542		.01688	.12671	.02504	.59860	1.27410	.00092		
.600	3.873	2.26572	61.93774	.08682		.01721	.16904	.03351	.59705	1.27256	.00254		
GRADIENT		.07893	18.07253	.00308		.00061	.04140	.00820	.00012	.00012	.00010		



## PARAMETRIC DATA

	RUN NO.	1728/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	2.000	PHI =	180.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.250	-4.076	1.84818	-64.51407	.06021	.02589	-.13633	-.05861	1.24526	2.54228	-.00519
1.250	-3.075	1.83387	-57.68184	.05846	.02510	-.10088	-.04331	1.24682	2.54705	-.00370
1.250	-2.107	1.85138	-46.65216	.05789	.02482	-.06605	-.02832	1.24804	2.55077	-.00235
1.250	-1.162	1.89874	-28.69298	.05853	.02509	-.03326	-.01426	1.24871	2.55282	-.00187
1.250	-1.197	1.99090	-2.29776	.06122	.02623	-.00900	.00039	1.24839	2.55185	-.00164
1.250	.834	2.08143	24.93080	.06436	.02758	.03631	.01556	1.24860	2.55249	-.00160
1.250	1.866	2.13260	43.68449	.06674	.02860	.07261	.03111	1.24831	2.55159	-.00176
1.250	2.910	2.16347	55.34793	.06869	.02947	.10995	.04717	1.24768	2.54967	-.00293
1.250	3.938	2.17102	62.73427	.07062	.03034	.14675	.06305	1.24608	2.54477	-.00446
GRADIENT		.05046	18.04505	.00161	.00069	.03522	.01513	.00010	.00030	.00010
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.400	-4.068	1.86030	-64.39462	.06636	.03000	-.15012	-.06786	1.39626	3.03618	-.00457
1.400	-3.065	1.84968	-57.52306	.06402	.02889	-.10994	-.04961	1.39734	3.03992	-.00296
1.400	-2.100	1.86643	-46.49348	.06284	.02834	-.07114	-.03208	1.39740	3.04014	-.00249
1.400	-1.151	1.91734	-28.41565	.06405	.02888	-.03520	-.01587	1.39755	3.04100	-.00218
1.400	-1.177	1.99299	-1.94157	.06637	.02992	.02227	.00102	1.39770	3.04121	-.00209
1.400	.855	2.06743	25.36632	.06881	.03103	.04195	.01892	1.39837	3.04355	-.00209
1.400	1.884	2.11641	44.00143	.07096	.03200	.08144	.03673	1.39806	3.04247	-.00218
1.400	2.919	2.14948	55.46710	.07457	.03362	.12260	.05528	1.39777	3.04146	-.00217
1.400	3.945	2.15338	62.81404	.07680	.03467	.16400	.07404	1.39686	3.03827	-.00334
GRADIENT		.04538	18.04313	.00158	.00071	.03896	.01758	.00009	.00033	.00013
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.450	-4.110	1.75641	-65.11240	.06599	.03024	-.16145	-.07399	1.44506	3.20980	-.00516
1.449	-3.124	1.75282	-58.43692	.06449	.02951	-.11910	-.05450	1.44554	3.21153	-.00380
1.450	-2.172	1.77761	-47.68297	.06370	.02916	-.07851	-.03594	1.44673	3.21588	-.00398
1.449	-1.245	1.85537	-29.84119	.06573	.03007	-.04016	-.01837	1.44621	3.21399	-.00359
1.449	-1.287	1.97876	-3.52468	.07000	.03201	-.00010	-.00004	1.44659	3.21536	-.00322
1.450	.743	2.11382	23.74310	.07424	.03397	.04185	.01915	1.44701	3.21689	-.00347
1.450	1.791	2.19316	42.73315	.07731	.03537	.08482	.03881	1.44714	3.21734	-.00337
1.450	2.852	2.24275	54.55333	.08151	.03726	.12947	.05919	1.44780	3.21977	-.00257
1.449	3.891	2.25538	62.09659	.08339	.03816	.17375	.07952	1.44595	3.21304	-.00389
GRADIENT		.07610	18.07068	.00263	.00120	.01908	.01969	.00020	.00072	.00017

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM059) (04 OCT 91)

## PARAMETRIC DATA

		RUN NO. 1703/ O		RN/L = 2.50		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = 2.000		PHI = 180.000	
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
1.484	-4.105	1.77615	-64.99263	.06564	.03075	-.16059	-.07522	1.46768	3.29257	-.00798	
1.470	-3.111	1.77112	-58.27800	.06524	.02995	-.12060	-.05537	1.46816	3.29433	-.00741	
1.470	-2.157	1.79301	-47.48477	.06461	.02963	-.08015	-.03676	1.46939	3.29888	-.00645	
1.470	-1.226	1.87175	-29.52440	.06684	.03067	-.04059	-.01863	1.46905	3.29763	-.00693	
1.485	-.265	1.98507	-3.20808	.06916	.03237	.00026	.00012	1.46868	3.29625	-.00721	
1.471	.759	2.10586	23.90147	.07525	.03452	.04273	.01960	1.46959	3.29963	-.00654	
1.470	1.813	2.17878	43.01044	.07884	.03614	.08754	.04012	1.46929	3.29849	-.00584	
1.470	2.863	2.22477	54.71230	.08177	.03749	.13191	.06049	1.46949	3.29926	-.00618	
1.484	3.899	2.23641	62.21628	.08200	.03835	.17434	.08155	1.46903	3.29754	-.00654	
GRADIENT		.07026	18.06508	.00255	.00117	.04203	.01949	.00016	.00059	.00018	
		RUN NO. 1696/ O		RN/L = 2.50		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = 2.000		PHI = 180.000	
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
1.495	-4.100	1.78805	-64.91277	.06906	.03209	-.17205	-.07995	1.48742	3.36594	-.01357	
1.495	-3.103	1.78602	-58.07951	.06817	.03167	-.12863	-.05976	1.48794	3.36790	-.01321	
1.495	-2.146	1.80699	-47.24693	.06780	.03149	-.08591	-.03990	1.48860	3.37037	-.01279	
1.494	-1.213	1.87447	-29.36604	.07054	.03271	-.04444	-.02061	1.48835	3.36945	-.01293	
1.494	-.258	1.98648	-3.16846	.07543	.03499	-.00204	-.00095	1.48788	3.36767	-.01318	
1.495	.779	2.10499	24.21814	.07999	.03715	.04051	.02090	1.48860	3.37037	-.01274	
1.495	1.819	2.16748	43.12953	.08340	.03871	.09133	.04239	1.48891	3.37152	-.01214	
1.495	2.874	2.21146	54.87112	.08670	.04020	.13896	.06444	1.48975	3.37469	-.01126	
1.495	3.907	2.22260	62.33572	.08843	.04105	.18617	.08644	1.48888	3.37141	-.01242	
GRADIENT		.06620	18.05977	.00291	.00134	.04475	.02078	.00020	.00076	.00020	
		RUN NO. 1691/ O		RN/L = 2.50		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = 2.000		PHI = 180.000	
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
1.521	-4.099	1.79045	-64.87312	.08082	.03794	-.19526	-.09167	1.50912	3.44786	-.01751	
1.521	-3.103	1.78602	-58.11914	.08202	.03848	-.15297	-.07177	1.50959	3.44965	-.01697	
1.521	-2.151	1.80947	-47.32605	.08319	.03904	-.10305	-.04836	1.50953	3.44941	-.01714	
1.521	-1.215	1.88008	-29.40562	.08516	.03997	-.05292	-.02483	1.50966	3.44993	-.01712	
1.521	-.256	1.98731	-3.20814	.09028	.04236	-.00580	-.00272	1.50975	3.45027	-.01691	
1.521	.778	2.10028	24.17853	.09621	.04516	.04631	.02174	1.50937	3.44881	-.01726	
1.521	1.826	2.16238	43.24823	.09963	.04675	.10473	.04914	1.50958	3.44960	-.01696	
1.521	2.875	2.21115	54.83141	.09965	.04672	.16113	.07555	1.51055	3.45330	-.01614	
1.521	3.907	2.22218	62.29599	.09859	.04623	.21232	.09957	1.51008	3.45151	-.01631	
GRADIENT		.06556	18.05595	.00280	.00131	.05155	.02419	.00011	.00042	.00013	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM059 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1684/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	2.000	PHI =	180.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPII	CPTD
1.544	-4.099	1.78994	-64.87312	.09110	.04304	-.17598	-.08316	1.53059	3.53020	-.02142
1.544	-3.108	1.78765	-58.11899	.06713	.03168	-.10593	-.04999	1.53205	3.53585	-.02015
1.544	-2.147	1.80590	-47.28653	.05733	.02705	-.06345	-.02994	1.53182	3.53495	-.02004
1.543	-1.209	1.88353	-29.16808	.05533	.02615	-.03208	-.01516	1.53009	3.52824	-.02181
1.543	-250	1.98764	-2.97059	.05854	.02767	-.00312	-.00147	1.53003	3.52802	-.02182
1.543	.782	2.10382	24.29729	.06223	.02950	.03003	.01420	1.52987	3.52741	-.02199
1.544	1.820	2.18092	42.97087	.06863	.03237	.06591	.03109	1.53222	3.53649	-.01962
1.543	2.879	2.21468	54.87094	.08298	.03914	.11177	.05272	1.53194	3.53539	-.01967
1.544	3.907	2.22294	62.33572	.09292	.04386	.16742	.07904	1.53179	3.53483	-.02043
GRADIENT		.06646	18.04587	.00150	.00070	.03918	.01850	.00009	.00034	.00011

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM060 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1729/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPII	CPTD
1.250	-5.036	.83279	-169.75660	-.18669	-.08107	-.02664	-.01157	1.23735	2.51827	-.01520
1.250	-4.776	.83052	-169.23810	-.17698	-.07676	-.02673	-.01159	1.23826	2.52103	-.01396
1.250	-4.525	.82977	-168.68020	-.16831	-.07293	-.02589	-.01122	1.23915	2.52373	-.01299
1.249	-4.279	.83549	-168.00340	-.15961	-.06907	-.02607	-.01128	1.23968	2.52534	-.01180
1.250	-4.029	.83426	-167.28660	-.15022	-.06497	-.02540	-.01099	1.24112	2.52968	-.01095
1.250	-3.788	.83524	-166.49060	-.14141	-.06108	-.02560	-.01106	1.24165	2.53129	-.00977
1.250	-3.537	.83262	-165.61500	-.13205	-.05696	-.02558	-.01103	1.24287	2.53501	-.00844
1.250	-3.289	.83318	-164.58090	-.12294	-.05298	-.02545	-.01097	1.24385	2.53801	-.00741
1.250	-3.041	.83537	-163.34840	-.11366	-.04895	-.02544	-.01096	1.24377	2.53774	-.00700
GRADIENT		.000208	3.35114	.036662	.01609	.00060	.00031	.00347	.01053	.00422

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM061 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1730/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	
	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
MACH	ALPHA								
1.250	-5.032	-58175	-172.52590	-.18603	-.08078	-.01710	-.00742	1.23756	2.51892
1.250	-4.767	-58237	-172.12720	-.17645	-.07651	-.01749	-.00759	1.23822	2.52090
1.250	-4.519	-58101	-171.72850	-.16786	-.07274	-.01701	-.00737	1.23955	2.52492
1.250	-4.271	-58182	-171.25040	-.15880	-.06873	-.01694	-.00733	1.24021	2.52694
1.250	-4.022	-58355	-170.69290	-.14981	-.06478	-.01631	-.00705	1.24126	2.53013
1.250	-3.774	-58341	-170.09570	-.14052	-.06067	-.01602	-.00692	1.24202	2.53241
1.250	-3.525	-58063	-169.45870	-.13126	-.05662	-.01635	-.00705	1.24292	2.53517
1.250	-3.276	-58210	-168.66310	-.12231	-.05272	-.01621	-.00699	1.24370	2.53754
1.250	-3.027	-58106	-167.78790	-.11289	-.04862	-.01599	-.00689	1.24442	2.53971
GRADIENT	.00036	2.47476	.03661	.01608	.00079	.00037	.00350	.01062	.00420

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM062 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1731/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	
	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
MACH	ALPHA								
1.250	-5.016	-32977	-175.33560	-.18537	-.08047	-.00875	-.00380	1.23724	2.51793
1.250	-4.758	-32940	-175.09630	-.17581	-.07623	-.00839	-.00364	1.23851	2.52177
1.250	-4.511	-33145	-174.81740	-.16714	-.07241	-.00766	-.00332	1.23950	2.52480
1.250	-4.259	-32943	-174.53820	-.15829	-.06848	-.00792	-.00343	1.24029	2.52716
1.250	-4.007	-32903	-174.21940	-.14884	-.06433	-.00768	-.00332	1.24125	2.53009
1.250	-3.760	-33070	-173.82130	-.14001	-.06045	-.00747	-.00323	1.24202	2.53243
1.250	-3.513	-33185	-173.38340	-.13089	-.05645	-.00701	-.00302	1.24288	2.53504
1.250	-3.261	-33107	-172.90570	-.12146	-.05234	-.00700	-.00302	1.24367	2.53744
1.250	-3.019	-33159	-172.34870	-.11221	-.04830	-.00691	-.00297	1.24414	2.53886
GRADIENT	.00107	1.56134	.03657	.01606	.00080	.00036	.00329	.00999	.00418

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 616

IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM063 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1732/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.250	PHI =	180.000
	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
<b>MACH</b>	<b>ALPHA</b>									
1.250	-5.009	-.07712	-178.18600	-.18487	-.08025	.00036	.00016	2.51842	-.01482	
1.250	-4.752	-.07960	-178.06650	-.17523	-.07598	.00074	.00032	2.52244	-.01362	
1.250	-4.500	-.07879	-177.98660	-.16655	-.07212	.00092	.00040	2.52515	-.01237	
1.249	-4.249	-.07926	-177.86710	-.15752	-.06813	.00118	.00051	2.52611	-.01136	
1.250	-4.002	-.07969	-177.74750	-.14828	-.06408	.00131	.00057	2.53024	-.01022	
1.250	-3.751	-.08139	-177.58830	-.13917	-.06009	.00154	.00066	2.53358	-.00926	
1.250	-3.500	-.07860	-177.46860	-.13025	-.05616	.00142	.00061	2.53490	-.00809	
1.250	-3.254	-.07920	-177.26950	-.12086	-.05207	.00141	.00061	2.53793	-.00718	
1.250	-3.003	-.07797	-177.07030	-.11170	-.04809	.00145	.00063	2.54035	-.00634	
GRADIENT	.00046	.56799	.03643	.01600	.00040	.00017	.00344	.01044	.00418	

IA310 (AEDC 16TF-783) PROBE CALIBRATION

( TCM064 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1733/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
<b>MACH</b>	<b>ALPHA</b>									
1.250	-5.001	.16235	179.08430	-.18418	-.07994	.00887	.00385	2.51792	-.01482	
1.250	-4.738	.16065	179.04450	-.17470	-.07573	.00975	.00423	2.52158	-.01354	
1.250	-4.492	.15779	179.00450	-.16621	-.07199	.00948	.00411	2.52525	-.01244	
1.250	-4.240	.16121	178.88560	-.15690	-.06787	.01004	.00434	2.52739	-.01130	
1.250	-3.993	.16160	178.80620	-.14797	-.06394	.00997	.00431	2.53102	-.01008	
1.250	-3.737	.16087	178.72680	-.13864	-.05985	.00995	.00430	2.53406	-.00914	
1.250	-3.490	.15989	178.64730	-.12932	-.05577	.01035	.00446	2.53649	-.00809	
1.250	-3.239	.16044	178.52830	-.12017	-.05177	.01023	.00441	2.53685	-.00724	
1.249	-2.988	.16215	178.36980	-.11113	-.04783	.01009	.00434	2.53931	-.00624	
GRADIENT	.00091	-.37576	.03649	.01602	.00033	.00013	.00333	.01010	.00417	

PAGE 617  
 (TCM065) (04 OCT 91)

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	PARAMETRIC DATA	
										BETA = .250	PHI = 180.000
1.249	-4.991	.42265	176.12430	-.18363	-.07970	.01814	.00787	1.23713	2.51760	CPTD	.01487
1.250	-4.732	.41525	175.96470	-.17401	-.07545	.01856	.00805	1.23828	2.52109		-.01371
1.250	-4.485	.41907	175.68680	-.16523	-.07156	.01906	.00826	1.23956	2.52497		-.01248
1.250	-4.232	.42052	175.40880	-.15621	-.06759	.01928	.00834	1.24044	2.52763		-.01144
1.250	-3.979	.42195	175.09120	-.14708	-.06355	.01945	.00840	1.24127	2.53014		-.01016
1.250	-3.732	.41869	174.81300	-.13792	-.05954	.01916	.00827	1.24214	2.53279		-.00916
1.250	-3.479	.42003	174.41620	-.12870	-.05550	.01906	.00822	1.24331	2.53635		-.00800
1.250	-3.226	.41766	174.01920	-.11957	-.05153	.01874	.00808	1.24350	2.53692		-.00746
1.250	-2.977	.41909	173.50360	-.11041	-.04752	.01865	.00803	1.24451	2.53999		-.00624
GRADIENT		-.00047	-1.28936	.03629	.01595	.00017	.00004	.00360	.01094		.00428

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	PARAMETRIC DATA	
										BETA = .500	PHI = 180.000
1.250	-4.984	.67061	173.28270	-.18292	-.07942	.02725	.01183	1.23790	2.51995	CPTD	-.01485
1.250	-4.725	.66623	172.96420	-.17339	-.07517	.02734	.01185	1.23826	2.52104		-.01361
1.250	-4.471	.66622	172.56680	-.16461	-.07130	.02768	.01199	1.23928	2.52412		-.01267
1.250	-4.221	.66954	172.09030	-.15556	-.06730	.02792	.01208	1.24021	2.52693		-.01140
1.250	-3.972	.66809	171.61360	-.14663	-.06336	.02832	.01224	1.24110	2.52964		-.01025
1.250	-3.717	.66682	171.05770	-.13743	-.05932	.02844	.01228	1.24197	2.53227		-.00918
1.250	-3.466	.66681	170.42260	-.12826	-.05531	.02843	.01226	1.24309	2.53569		-.00810
1.250	-3.210	.66521	169.70830	-.11895	-.05125	.02767	.01192	1.24404	2.53855		-.00721
1.250	-2.963	.66603	168.87530	-.10982	-.04728	.02750	.01184	1.24441	2.53968		-.00644
GRADIENT		-.00152	-2.16077	.03610	.01587	.00027	.00006	.00348	.01056		.00424

( TCM066 ) ( 04 OCT 91 )

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 618

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM067) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.250	-4.976	.91977	170.48090	-.18257	-.07924	.03648	.01583	1.23744	2.51855
1.250	-4.715	.91643	170.00360	-.17287	-.07497	.03656	.01585	1.23856	2.52193
1.250	-4.464	.91694	169.44720	-.16434	-.07117	.03717	.01610	1.23932	2.52424
1.250	-4.212	.91582	168.85120	-.15507	-.06709	.03701	.01601	1.24052	2.52788
1.250	-3.960	.91478	168.17590	-.14600	-.06311	.03691	.01596	1.24130	2.53024
1.250	-3.708	.91480	167.38190	-.13710	-.05919	.03721	.01607	1.24231	2.53329
1.250	-3.453	.91399	166.50870	-.12781	-.05511	.03679	.01587	1.24294	2.53521
1.250	-3.203	.91356	165.51660	-.11867	-.05113	.03663	.01578	1.24395	2.53829
1.250	-2.947	.91187	164.36610	-.10947	-.04711	.03640	.01566	1.24431	2.53939
GRADIENT	-.00311	-2.98179	.03597	.01581	-.00004	-.00009	.00347	.01053	.00424

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(TCM068) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.250	-4.968	1.16575	167.75840	-.18223	-.07912	.04577	.01987	1.23730	2.51812
1.250	-4.705	1.16396	167.12210	-.17270	-.07489	.04572	.01983	1.23833	2.52122
1.250	-4.455	1.16588	166.40690	-.16393	-.07102	.04591	.01989	1.23935	2.52432
1.250	-4.206	1.16416	165.65190	-.15473	-.06696	.04587	.01985	1.24022	2.52696
1.250	-3.950	1.16221	164.77810	-.14563	-.06296	.04591	.01985	1.24127	2.53015
1.250	-3.694	1.15954	163.82500	-.13659	-.05897	.04579	.01977	1.24176	2.53164
1.250	-3.440	1.16002	162.71370	-.12758	-.05502	.04563	.01968	1.24263	2.53427
1.250	-3.190	1.15912	161.48350	-.11853	-.05108	.04548	.01960	1.24400	2.53844
1.250	-2.938	1.15875	160.05540	-.10916	-.04700	.04506	.01940	1.24474	2.54070
GRADIENT	-.00388	-3.74388	.03589	.01578	-.00028	-.00020	.00361	.01095	.00429

IA310 (AEDC 16TF-783) REPEAT RUNS

RUN NO.	1671/ O	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00
ALPHA	BETA	PHI	CPAQ	CPALPH	CPBHQ	CPBETA	CPTD
.599	.999	.28034	.178 .97150	.33883	.06835	.01169	.02248
.599	.982	.27633	.178 .85120	.29843	.05989	.01359	.01734
.600	.975	.27709	.178 .65200	.25550	.05112	.01422	.01251
.600	.979	.27421	.178 .41300	.21407	.04273	.01460	.00907
.600	.977	.27437	.178 .01570	.17263	.03433	.01519	.00599
.600	.974	.27530	.177 .34120	.13043	.02588	.01474	.00347
.600	.968	.27206	.176 .11190	.08776	.01738	.01614	.00170
.601	.949	.26529	.172 .54530	.04431	.00877	.01638	.00143
.600	.078	.-17377	.- .04303	.01270	.00251	.00133	.00026
.600	.971	.-28995	.- .68527	.02873	.00568	.00100	.00064
.600	1.989	.-29553	.-3 .52467	.07157	.01416	.00331	.00051
.600	.09744	.-32 .58343	.-32 .04090	.00814	.00327	.00065	.00144
GADIENT							

PIN NO 1747/2 RN/1 = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	MACH	ALPHA	BETA	PHI	CPAQ	CPBQ	CPALPH	CPBETA	CPM	MPROBE	CPTD
.800	-7.999	.19622	.179.	.28540	-.32582	-.09865	.01016	.00308	.76899	.47881	-.03056
.800	-6.978	.19303	.179.	.20520	-.28602	-.08608	.00907	.00273	.77671	.48989	-.02346
.800	-5.977	.19519	.179.	.04600	-.24567	-.07337	.01095	.00327	.78251	.49832	-.01689
.800	-4.976	.19245	.178.	.88670	-.20600	-.06130	.01079	.00321	.78807	.50650	-.01208
.800	-3.981	.19540	.178.	.56910	-.16611	-.04924	.01149	.00340	.79252	.51311	-.00791
.800	-2.974	.19340	.178.	.13250	-.12501	-.03694	.01158	.00342	.79548	.51752	-.00484
.801	-1.972	.19112	.177.	.261010	-.08457	-.02496	.01209	.00357	.79810	.52147	-.00276
.800	-965	.18831	.174.	.68420	-.04421	-.01302	.01259	.00371	.79913	.52303	-.00134
.800	-147	-.00052	.120.	.62770	-.00195	-.00612	.00180	.00068	.79952	.52362	-.00068
.800	.988	-.20428	-.4.	.12070	.02908	.00855	-.00152	-.00045	.79904	.52289	-.00078
.800	1.998	-.21468	-.2.	.33733	.06952	.02044	-.00030	-.00009	.79893	.52273	-.00076
GRADIENT	-.06436	-.06436	-.27.	.83772	.03944	-.01169	-.00188	-.00056	.00146	.00218	.00154

RUN NO. 1669/8 BN/H = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	MACH	ALPHA	BETA	PHI	CPAQ	CPBQ	CPALPH	CPBEA	CPM	CPTD
.900	-8.000	.20873	179.24620	.31152	.10773	.00897	.00310	.87058	1.63883	-.03181
.899	-6.979	.20977	179.12660	.27305	.09372	.01051	.00361	.87687	1.64980	-.02450
.900	-5.970	.20683	179.00670	.23561	.08036	.01102	.00376	.88328	1.66112	-.01780
.900	-4.971	.20618	178.80770	.19722	.06597	.01103	.00374	.88851	1.67046	-.01267
.900	-3.977	.20790	178.49010	.15878	.05369	.01206	.00408	.89218	1.67707	-.00859
.900	-2.966	.20575	178.01370	.11953	.04027	.01161	.00391	.89575	1.68354	-.00476
.900	-1.966	.20612	177.02250	.08089	.02719	.01175	.00395	.89717	1.68613	-.00290
.900	-.955	.20095	174.32770	.04224	.01419	.01210	.00406	.89897	1.68942	-.00136
.900	-.086	.-14121	-.04303	-.01140	-.00382	-.00041	-.00014	.89929	1.69000	-.00089
.900	.994	.-22574	-.49521	-.02769	-.00929	-.00181	-.00061	.89907	1.68960	-.00095
.900	2.003	.-22886	-.2.53519	.06634	.02226	-.00036	-.00012	.88969	1.68892	-.00111
.900	GRADIENT	.07469	.-32.43895	.03769	.01274	-.00217	-.00074	.00142	.00257	.00159

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 620  
( TCM069 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.099	-8.003	.06679	179.83640	-.28275	-.11599	.00324	.00133	1.07171	2.06127
1.101	-6.975	.06991	179.79670	-.24747	-.10081	.00459	.00187	2.08169	-.02537
1.101	-5.975	.06606	179.79620	-.21369	-.08648	.00455	.00184	2.09543	-.01868
1.100	-4.978	.06443	179.75610	-.17921	-.07210	.00544	.00219	1.08929	2.10541
1.100	-3.968	.05565	179.67590	-.14365	-.05754	.00576	.00231	1.09303	-.00866
1.100	-2.977	.06656	179.31940	-.10806	-.04314	.00608	.00243	1.09596	-.00523
1.100	-1.970	.07030	179.04210	-.07303	-.02909	.00632	.00252	1.09802	2.12776
1.100	-.971	.06638	178.44750	-.03915	-.01557	.00695	.00277	1.09887	-.00275
1.100	.041	.01745	166.24620	-.00591	-.00235	.00626	.00249	1.09898	2.12993
1.100	1.007	-.08240	-.83435	.02580	.01026	.00346	.00138	1.09938	-.00149
1.100	2.014	-.09837	-.59563	.06010	.02388	.00338	.00134	1.09913	-.00097
GRADIENT		-.02357	-26.20811	.03413	.01367	-.00629	-.00012	.00132	-.00075
								.00338	-.00080
									.00167

RUN NO. 1739/ 0 RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.250	-7.999	.15655	179.48220	-.29102	-.12888	.00752	.00333	1.22081	2.46868
1.250	-6.974	.16262	179.36310	-.25599	-.11251	.00888	.00390	2.2797	-.03533
1.250	-5.971	.16374	179.24370	-.22039	-.09611	.00886	.00387	1.23381	-.02725
1.250	-4.969	.15782	179.12370	-.18369	-.07975	.00962	.00418	1.23808	-.01942
1.250	-3.973	.15626	178.88520	-.14789	-.06393	.00958	.00414	1.24153	-.01475
1.250	-2.972	.15763	178.44890	-.11148	-.04799	.00977	.00421	1.24453	-.01045
1.250	-1.970	.16071	177.61640	-.07605	-.03265	.01014	.00435	1.24690	-.00635
1.250	-.960	.15682	175.47640	-.04080	-.01749	.01071	.00459	1.24837	-.00355
1.250	-.118	.02057	132.50560	-.00299	-.00128	.00694	.00298	1.24809	-.00185
1.250	.996	-.16974	-.3.21007	.02679	.01147	.00096	.00041	1.24873	-.00217
1.250	2.008	-.18309	-.1.90197	.06206	.02660	.00129	.00055	1.24886	-.00108
GRADIENT		-.05254	-27.41766	.03519	.01521	-.00129	-.00056	.00147	-.00162
									.00449

RUN NO. 1723/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD
1.400	-7.997	.14633	179.48180	-.32045	-.14948	.01052	.00491	1.36866	2.94096
1.400	-6.974	.15321	179.36290	-.28247	-.13071	.01122	.00519	1.37585	-.03672
1.400	-5.972	.14665	179.32230	-.24375	-.11202	.01110	.00510	1.38198	-.02842
1.400	-4.974	.14170	179.20250	-.20479	-.09357	.01038	.00474	1.38654	-.02127
1.400	-3.973	.14329	178.96430	-.16560	-.07527	.01184	.00538	1.39133	-.01548
1.400	-2.972	.14545	178.56760	-.12350	-.05595	.01150	.00521	1.39394	-.01012
1.400	-1.972	.14470	177.89360	-.08466	-.03826	.01095	.00495	1.39618	-.00692
1.400	-.966	.14181	175.99140	-.04618	-.02081	.01152	.00519	1.39897	-.00448
1.400	-.111	.02188	135.47630	-.00516	-.00232	.00783	.00353	1.39839	-.00143
1.400	.998	-.15950	-.2.93286	.02845	.01281	.00233	.00105	1.39909	-.00113
GRADIENT		-.16774	-.1.66449	.06727	.03033	-.00271	-.00122	1.39800	-.00426
		-.04803	-27.27467	.03888	.01768	-.00132	-.00064	.00161	-.00192

## IA310 (AEDC 16TF-783) REPEAT RUNS

(TCM069) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.450	-7.994	.25818	179.08950	-33885	-16051	.01424	.00674	1.41630	3.10666	-.03888
1.450	-6.971	.26157	178.93020	-29927	-.14068	.01435	.00674	1.42347	3.13216	-.03088
1.450	-5.968	.26044	178.77060	-25783	-.12037	.01490	.00696	1.42863	3.15058	-.02403
1.450	-4.971	.25945	178.53170	-21807	-.10115	.01534	.00711	1.43509	3.17380	-.01725
1.450	-3.968	.25539	178.17390	-17672	-.08143	.01637	.00754	1.44066	3.19390	-.01057
1.450	-2.965	.25787	177.49940	-13235	-.06082	.01591	.00731	1.44308	3.20265	-.00780
1.450	-1.961	.25558	176.30980	-91123	-.04182	.01600	.00733	1.44539	3.21103	-.00526
1.450	-.944	.25056	172.90180	-.05040	-.02297	.01730	.00788	1.45113	3.23188	-.00078
1.449	-.091	-.16532	-.00344	-.01401	-.00640	.00201	.00092	1.44802	3.22055	-.00160
1.450	.974	-.27636	-6.57559	.02961	.01348	-.00088	-.00040	1.45103	3.23151	.00131
1.450	2.001	-.28047	-3.28716	.07076	.03236	.00045	.00021	1.44774	3.21956	-.00281
GRADIENT		.09208	-32.56052	.04148	.01914	-.00275	-.00127	.00194	.00703	.00223
RUN NO.	1698/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00			

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.471	-7.998	.23648	179.16800	-35080	-.16639	.01366	.00648	1.44101	3.19516	-.03908
1.471	-6.970	.23732	179.04830	-31049	-.14592	.01379	.00648	1.44915	3.22466	-.02956
1.472	-5.972	.23744	178.88880	-.26592	-.12430	.01394	.00651	1.45425	3.24324	-.02394
1.471	-4.970	.23741	178.65010	-.22310	-.10373	.01545	.00718	1.45864	3.25932	-.01859
1.471	-3.973	.23313	178.33190	-.18016	-.08334	.01588	.00735	1.46220	3.27239	-.01372
1.471	-2.970	.23498	177.73680	-.13562	-.06258	.01662	.00736	1.46514	3.28321	-.01098
1.471	-1.962	.23374	176.62650	-.09317	-.04294	.01630	.00751	1.46607	3.28663	-.00978
1.470	-.947	.23128	173.45630	-.05089	-.02341	.01734	.00798	1.46643	3.28797	-.00977
1.469	.149	-.13809	87.20670	-.00494	-.00227	.00267	.00123	1.46681	3.28936	-.00890
1.469	.980	-.24703	-5.42734	.02859	.01313	-.00027	.00012	1.46689	3.28966	-.00889
1.469	2.007	-.25983	-3.01013	.07089	.03251	.00085	.00039	1.46774	3.29279	-.00784
GRADIENT		-.08331	-29.19633	.04211	.01949	-.00263	-.00122	.00110	.00406	.00126
RUN NO.	1668/ 0	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00			

MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.496	-7.999	.22343	179.20720	-.35952	-.17300	.01398	.00673	1.45814	3.25748	-.04760
1.497	-6.971	.22515	179.08760	-.32032	-.15286	.01702	.00812	1.46604	3.28653	-.03887
1.497	-5.968	.22227	178.96770	-.27940	-.13250	.01724	.00818	1.47167	3.30733	-.03242
1.496	-4.966	.22349	178.72910	-.23650	-.11157	.01731	.00817	1.47585	3.32282	-.02708
1.497	-3.969	.22082	178.41100	-.19273	-.09043	.01809	.00849	1.48079	3.34118	-.02149
1.497	-2.967	.22142	177.85550	-.14622	-.06843	.01858	.00870	1.48318	3.35011	-.01885
1.497	-1.965	.22011	176.82450	-.10181	-.04763	.01789	.00837	1.48394	3.35292	-.01828
1.497	-.953	.21524	173.89200	-.05759	-.02695	.01878	.00879	1.48343	3.31502	-.01878
1.497	-.161	-.08155	99.40356	-.00457	-.00214	.00728	.00340	1.48488	3.35645	-.01700
1.496	.878	-.12950	1.14538	.02812	.01314	.00393	.00183	1.48388	3.35221	-.01773
1.496	1.999	-.24303	-2.73309	.07644	.03569	-.00116	-.00054	1.48508	3.35720	-.01653
GRADIENT		-.07099	-28.40020	.04514	.02121	-.00278	-.00131	.00118	.00381	.00102
RUN NO.	1668/ 0	RN/L =	2.49	GRADIENT	INTERVAL =	-5.00/	5.00			

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 622

( TCM069 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1686/ 0	RN/L =	2.50	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD					
1.520	-7.997	.22510	179.16740	-.38869	-.18688	.01607	.00772	1.48675	3.36344					
1.520	-6.969	.22623	179.04780	-.35315	-.16834	.01765	.00841	1.49446	3.39237					
1.520	-5.968	.22276	178.92790	-.31278	-.14795	.01708	.00808	1.50132	3.41826					
1.520	-4.966	.22174	178.72890	-.26808	-.12633	.01649	.00777	1.50461	3.43073					
1.520	-3.970	.21867	178.41090	-.22382	-.10518	.01753	.00824	1.50761	3.44210					
1.520	-2.967	.22154	177.81580	-.17042	-.08001	.01706	.00801	1.50821	3.44440					
1.520	-1.965	.22194	176.74530	-.11293	-.05301	.01439	.00676	1.50819	3.44432					
1.520	-952	.21520	173.89200	-.05172	-.02426	.00987	.00463	1.50923	3.44828					
1.520	.163	.07679	101.62110	-.00016	-.00008	.00286	.00134	1.50991	3.45088					
1.520	.984	-.23155	-4.91260	.02633	.01234	-.00263	-.00123	1.51004	3.45135					
1.520	2.000	-.24252	-2.77273	.08155	.03825	-.00817	-.00383	1.50905	3.44758					
GRADIENT		-.07611	-28.62250	.05091	.02395	-.00381	-.00179	.00059	.000225					

RUN NO. 1679/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1679/ 0	RN/L =	2.49	GRADIENT INTERVAL	=	-5.00/	5.00	BETA	=	.000	PHI	=	180.000
MACH	ALPHA	BETA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBE	CPTD					
1.545	-7.992	.22464	179.20740	-.42343	-.20153	.01509	.00718	1.52612	3.51293					
1.542	-6.974	.22505	179.08760	-.35606	-.16878	.01598	.00757	1.52587	3.51197					
1.543	-5.972	.22220	178.96770	-.28270	-.13389	.01053	.00499	1.52822	3.52104					
1.543	-4.971	.21958	178.76850	-.22064	-.10444	.00565	.00267	1.52868	3.52280					
1.543	-3.969	.22097	178.41100	-.16619	-.07858	.00795	.00376	1.52954	3.52612					
1.542	-2.968	.22104	177.85540	-.11188	-.05280	.00844	.00399	1.52995	3.52770					
1.542	-1.960	.21936	176.82450	-.07126	-.03368	.00653	.00309	1.52865	3.52270					
1.543	-.952	.21464	173.89200	-.03900	-.01845	.00951	.00450	1.52910	3.52443					
1.543	.164	-.07019	101.77940	.00111	.00053	.00668	.00315	1.52933	3.52531					
1.543	.983	-.23139	-4.87300	.02861	.01353	-.00369	-.00175	1.52880	3.52329					
1.543	1.994	-.24278	-2.73310	.05632	.02661	-.00321	-.00151	1.52949	3.52594					
GRADIENT		-.07576	-28.60898	.03916	.01852	-.00144	-.00068	.00001	.00003					

IA310 (AEDC 16TF-783) REPEAT RUNS

( TCM070 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1674/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	
			ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA
.601	-3.798	-4.19741	-136.66310	-	18732	-.03144	-.03147	.58823
.601	-2.772	-4.15446	-144.90700	-	18333	-.03658	-.02281	.59017
.601	-1.749	-4.10699	-155.33730	-	18018	-.03588	-.01407	.59198
.601	-.732	-4.05306	-167.96020	-	17616	-.03508	-.00772	.59261
.601	-.290	-3.98572	1.65364	-	17325	-.03451	-.00580	.59308
.600	.738	-4.06243	-12.64494	-	17550	-.03491	.03658	.00728
.600	1.758	-4.11453	-25.23834	-	17848	-.03549	.08018	.01595
.600	2.783	-4.15551	-35.61243	-	17951	-.03580	.12464	.02486
.600	3.824	-4.18861	-43.92581	-	18095	-.03615	.16780	.03353
GRADIENT	-.00055	18.83114	.00070	.00014	.04283	.00855	-.00017	.00007

MACH	BETA	RUN NO.	1750/ 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	
			ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA
.799	-3.857	-4.13863	-136.22540	-	17692	-.05257	-.15320	.04552
.800	-2.832	-4.10525	-144.47010	-	17368	-.05157	-.11152	.03311
.800	-1.818	-4.07292	-154.86160	-	17117	-.05080	-.07021	.02084
.800	-.810	-4.03324	-167.40550	-	16834	-.04990	-.02923	.00866
.800	-.212	-3.98960	1.10047	-	16568	-.04909	-.00267	.00079
.800	.826	-4.04458	-13.35616	-	16633	-.04930	.03861	.01144
.800	1.837	-4.08102	-25.83157	-	16850	-.05000	.07975	.02366
.800	2.848	-4.10886	-36.08810	-	17031	-.05059	.12123	.03601
.800	3.869	-4.13494	-44.24481	-	17164	-.05111	.16218	.04829
GRADIENT	-.00073	18.63700	.00066	.00019	.04090	.01216	.00002	.00003

MACH	BETA	RUN NO.	1663/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	
			ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA
.899	-3.844	-4.14681	-136.30480	-	17038	-.05784	-.14646	-.04972
.900	-2.815	-4.11075	-144.58880	-	16662	-.05651	-.10615	-.03600
.900	-1.803	-4.07821	-154.98040	-	16434	-.05566	-.06688	-.02265
.900	-.791	-4.03393	-167.56390	-	16155	-.05461	-.02743	-.00927
.900	-.227	-3.98438	1.21901	-	15874	-.05366	-.00247	-.00083
.900	.813	-4.04362	-13.2723	-	16018	-.05417	-.03679	.01244
.900	1.818	-4.08655	-25.67358	-	16188	-.05481	.07617	.02579
.900	2.839	-4.11995	-36.00870	-	16340	-.05537	.11655	.03949
.900	3.865	-4.14011	-44.24448	-	16465	-.05595	.15571	.05291
GRADIENT	-.00087	18.66681	.00067	.00022	.03930	.01334	-.00011	.00008

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 624

( TCM070 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1742/ 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPTD	CPM
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBET	CPBQ	CPBET	CPROBE	CPTD	CPM
1.100	-3.945	-4.05146	-135.50860	-.15025	-.06050	-.13600	-.05476	.08821	2.10267	-.01408			
1.100	-2.928	-4.02818	-143.67550	-.14813	-.05951	-.09991	-.04014	.09062	2.10880	-.01158			
1.099	-1.929	-4.01582	-153.94940	-.14648	-.05874	-.06478	-.02597	.09113	2.11010	-.01009			
1.100	- .941	-3.99808	-166.45470	-.14467	-.05796	-.02970	-.01190	.09255	2.11372	-.00896			
1.100	-.084	-3.98909	-139.032	-.14110	-.05773	-.00223	.00089	.09296	2.11476	-.00873			
1.100	.958	-4.01094	-14.18525	-.14390	-.05766	.03865	.01548	.09227	2.11300	-.00911			
1.100	1.961	-4.02216	-26.78099	-.14467	-.05802	.07435	.02982	.09149	2.11101	-.01005			
1.100	2.955	-4.03578	-36.84125	-.14529	-.05836	.10948	.04398	.08988	2.10692	-.01180			
1.100	3.979	-4.04450	-45.11850	-.14605	-.05883	.14531	.05853	.08774	2.10149	-.01449			
GRADIENT	-.00039	18.18935	.00050	.00020	.03558	.01431	-.00007	-.00017	-.00005				
RUN NO.	1726/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPTD	CPM
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBET	CPBQ	CPBET	CPROBE	CPTD	CPM
1.250	-3.880	-4.11910	-136.06620	-.15693	-.06812	-.13746	-.05967	.123741	2.51846	-.01488			
1.250	-2.850	-4.08185	-144.31080	-.15383	-.06667	-.09954	-.04314	.23893	2.52306	-.01314			
1.250	-1.844	-4.05905	-154.70300	-.15189	-.06574	-.06307	-.02730	.24031	2.52724	-.01175			
1.250	-.837	-4.02813	-167.24690	-.15004	-.06487	-.02647	-.01144	.24116	2.52982	-.01065			
1.250	-.177	-3.99397	.86354	-.14780	-.06384	-.0019	.00008	.24151	2.53089	-.00986			
1.250	.878	-4.03929	-13.83013	-.14854	-.06419	.03677	.01589	.24105	2.52950	-.01028			
1.250	1.874	-4.06178	-26.14798	-.14974	-.06478	.07266	.03143	.24019	2.52686	-.01138			
1.249	2.908	-4.08897	-36.56227	-.15116	-.06550	.11012	.04772	.23861	2.52209	-.01314			
1.249	3.911	-4.11015	-44.56172	-.15222	-.06616	.14585	.06339	.23607	2.51441	-.01616			
GRADIENT	-.00025	18.45098	.00055	.00024	.03640	.01579	-.00012	-.00008	-.000037				
RUN NO.	1718/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA	CPAQ	CPALPH	CPBQ	CPBETA	CPROBE	CPTD	CPM
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	CPBET	CPBQ	CPBET	CPROBE	CPTD	CPM
1.400	-3.892	-4.10763	-135.98660	-.17344	-.07926	-.15060	-.06882	.38592	3.00026	.01580			
1.400	-2.866	-4.07165	-144.23170	-.17143	-.07816	-.11006	-.05018	.38881	3.01027	.01327			
1.400	-1.858	-4.05314	-154.62380	-.16957	-.07716	-.06933	-.03154	.39028	3.01535	.01123			
1.400	-.851	-4.02571	-167.16780	-.16752	-.07616	-.02906	-.01321	.39142	3.01930	.01034			
1.400	-.163	-3.98864	.74491	-.16487	-.07490	.00195	.00088	.39148	3.01952	.00976			
1.400	.886	-4.03127	-13.86979	-.16544	-.07520	.04320	.01964	.39103	3.01794	.01024			
1.400	1.894	-4.05191	-26.34573	-.16618	-.07561	.08346	.03797	.39027	3.01530	.01120			
1.399	2.898	-4.08131	-36.48412	-.16743	-.07627	.12380	.05639	.38861	3.00956	.01258			
1.400	3.926	-4.10116	-44.68069	-.16862	-.07698	.16456	.07513	.38712	3.00438	.01473			
GRADIENT	-.00031	18.41451	.00068	.00032	.04047	.01846	.00006	.00011					

1A310 (AEDC 1611F-7883) REPEAT RUNS

1A310 (AEDEC 1611F-783) REPEAT RUNS

## PARAMETRIC DATA

RUN NO.		1708 / O		RN/L = 2.50		GRADIENT INTERVAL = -5.00/ 5.00		CPTD	
BETA	MACH	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM
.450	-3.810	-4.18364	-136.54380	-.18549	-.08614	-.15642	-.07264	1.43331	3.16740
.450	-2.773	-4.14115	-14.86660	-.18386	-.08511	-.11271	-.05217	1.43669	3.17955
.450	-1.757	-4.09818	-155.29740	-.18259	-.08428	-.07016	-.03238	1.43942	3.18941
.450	-7.40	-4.04281	-167.9.2040	-.18013	-.08302	-.02694	-.01242	1.44076	3.19425
.450	-2.76	-3.98587	1.57468	-.17420	-.08054	-.00391	-.00181	1.43718	3.18132
.450	.759	-4.05955	-12.84254	-.17663	-.08168	.03838	.01775	1.43733	3.18185
.450	1.776	-4.10715	-25.39664	-.17941	-.08303	.08135	.03765	1.43630	3.17815
.450	2.820	-4.14438	-35.96814	-.18153	-.08418	.12544	.05817	1.43417	3.17047
.449	3.841	-4.17664	-44.08456	-.18187	-.08465	.16689	.07767	1.43196	3.16254
.450	GRADIENT	-.00089	18.72298	.00051	.00020	.04244	.01970	-.00039	-.00042
RUN NO.		1701 / O		RN/L = 2.50		GRADIENT INTERVAL = -5.00/ 5.00		CPTD	
BETA	MACH	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM
.469	-3.822	-4.16994	-136.46400	-.19095	-.08858	-.16081	-.07460	1.45843	3.25855
.469	-2.791	-4.12672	-14.74760	-.18832	-.08717	-.11633	-.05308	1.46018	3.26497
.469	-1.772	-4.08929	-155.21810	-.18598	-.08599	-.07154	-.03308	1.46183	3.27103
.470	-7.61	-4.04219	-167.80170	-.18319	-.08461	-.02766	-.01277	1.46247	3.27339
.470	-2.53	-3.98656	1.37699	-.18268	-.08439	-.00066	-.00030	1.46225	3.27257
.470	.800	-4.05087	-13.27711	-.18419	-.08511	.04388	.02028	1.46199	3.27161
.470	1.821	-4.09833	-25.83107	-.18686	-.08642	.08863	.04099	1.46129	3.26906
.470	2.820	-4.13058	-35.92935	-.18896	-.08750	.13366	.06189	1.45975	3.26340
.469	3.850	-4.15944	-44.16451	-.19145	-.08886	.17819	.08271	1.45821	3.25774
.470	GRADIENT	-.00042	18.71448	-.00014	-.00007	.04437	.02056	-.00007	-.00007
RUN NO.		1694 / O		RN/L = 2.50		GRADIENT INTERVAL = -5.00/ 5.00		CPTD	
BETA	MACH	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM
.495	-3.837	-4.16375	-136.38460	-.19901	-.09370	-.16640	-.07835	1.47584	3.32279
.495	-2.802	-4.11971	-144.66810	-.19733	-.09270	-.12087	-.05679	1.47795	3.33060
.495	-1.786	-4.08323	-155.09920	-.19606	-.09189	-.07433	-.03483	1.48018	3.33889
.495	-7.78	-4.03914	-167.64310	-.19359	-.09078	-.02853	-.01338	1.47987	3.33775
.495	.240	-3.97896	1.29800	-.18748	-.08786	-.00268	-.00126	1.48042	3.33980
.495	.799	-4.04813	-13.15859	-.18946	-.08879	.04304	.02017	1.48037	3.33962
.495	1.817	-4.08534	-25.75249	-.19140	-.08969	.08918	.04179	1.48087	3.34076
.495	2.838	-4.12662	-36.04787	-.19338	-.09072	.13571	.06366	1.47897	3.33441
.495	3.869	-4.15193	-44.28320	-.19525	-.09172	.18123	.08513	1.47617	3.32401
.495	GRADIENT	-.00025	18.63989	.00067	.00014	.04526	.02126	-.00009	.000035

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

1A310 (AEDC 16TE-783) REPEAT BIINS

(TCM070) ( 04 OCT 91 )

卷之三

RUN NO. 1689/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	ACh	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	M PROBE	CPM	CPTD
- .521	- 3.833	- 4.16107	- 136.42420	- 2215.9	- 10456	- 18462	- .08712	1.50442	3.43001	-.02302	
- .521	- 2.804	- 4.11965	- 144.66830	- 2218.3	- 10452	- 13561	- .06390	1.50576	3.43510	-.02155	
- .521	- 1.786	- 4.08398	- 155.09920	- 2236.6	- 10524	- 108765	- .04124	1.50699	3.43975	-.02020	
- .520	- .775	- 4.03482	- 167.68270	- 2234.4	- 10505	- 03689	- .01734	1.50762	3.44214	-.01938	
- .520	- .241	- 3.98661	- 1.33766	- 2136.1	- 10041	- 00217	- .00102	1.50779	3.44280	-.01921	
.520	.809	- 4.05426	- 13.27696	- 21835	- 10262	.04975	.02338	1.50790	3.44324	.01900	
.520	1.827	- 4.08867	- 25.83122	- 22227	- 10451	- 10519	.04946	1.50700	3.43980	.01951	
.520	2.854	- 4.12526	- 36.16602	- 22521	- 10599	- 15900	.07483	1.50628	3.43708	.02039	
.520	3.870	- 4.14658	- 44.28317	- 22646	- 10671	- 21049	.09918	1.50537	3.43361	.02154	
GRADIENT		-.000021	18.61910		-.00045	-.00019	.02443		.00036	.00009	

	RUN NO.	1682/ O	RN/L =	2.49	GRADIENT INTERVAL	= -5.00/	5.00
BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MIPROBE
.543	-3.836	-4. 16413	-136. 38460	- 19177	-.09079	-.0893	1. 52821
.543	-2.801	-4. 12026	-144. 66810	- 18502	-.08760	-.06536	3. 52240
.543	-1.788	-4. 08256	-155. 05950	- 17796	-.08425	-.08809	1. 52857
.544	-.776	-4. 03985	-167. 68280	- 17052	-.08067	-.03998	3. 52628
.543	-.240	-3. 98971	-1. 29799	- 15579	-.07347	-.00591	1. 52958
.543	.797	-4. 04877	-13. 15870	- 16080	-.07579	.03552	1. 53196
.544	1.818	-4. 09067	-25. 75243	- 17037	-.08031	.08092	1. 53258
.543	2.831	-4. 12581	-35. 96898	- 18020	-.08499	.12840	3. 53787
.544	3.870	-4. 15112	-44. 28317	- 19030	-.08989	.18028	1. 53347
GRADIENT				.00066	.00036	.04764	.00054
						.02252	.00029

## IA310 (AEDC 16TF-783) REPEAT RUNS

## PARAMETRIC DATA

MACH	BETA	RUN NO. 1675/0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA	PHI	CPA0	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
		ALPHA	PHI											
.601	-3.993	-.27212	-91.98181	-.01861	-.00370	-.15868	-.03153	.59684	1.27236	-.00326				
.600	-2.974	-.27187	-92.65096	-.01806	-.00358	-.11596	-.02296	.59817	1.27368	-.00161				
.601	-1.969	-.27134	-93.99310	-.01779	-.00353	-.07299	-.01447	.59931	1.27482	-.00115				
.601	-.950	-.26340	-97.78944	-.01814	-.00359	-.03030	-.00600	.59947	1.27498	-.00093				
.600	-.173	-.08255	-.04303	-.01227	-.00243	-.00122	-.00024	.59943	1.27494	-.00056				
.601	.831	.38920	76.15369	.00721	.00143	.03967	.00785	.59981	1.27531	-.00062				
.601	1.996	.31350	86.09024	.00467	.00093	.08795	.01742	.59933	1.27484	-.00104				
.600	3.003	.29627	87.71065	.00505	.00100	.13081	.02589	.599812	1.27363	-.00154				
.601	4.011	.29447	88.30115	.00572	.00114	.17358	.03445	.59661	1.27213	-.00307				
	GRADIENT	.09629	29.85448	.00395	.00078	.04126	.00818	-.00002	-.00002					
MACH	BETA	RUN NO. 1751/0		RN/L = 2.51	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA	PHI	CPA0	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
		ALPHA	PHI											
.799	-3.996	-.19053	-91.38377	-.01474	-.00435	-.15220	-.04486	-.79486	1.51660	-.00427				
.800	-2.975	-.19212	-91.89575	-.01452	-.00428	-.11073	-.03265	.79737	1.52037	-.00284				
.800	-1.973	-.19181	-92.84312	-.01395	-.00411	-.07058	-.02078	.79849	1.52205	-.00165				
.800	-.960	-.18730	-95.57173	-.01494	-.00440	-.03106	-.00915	.79933	1.52332	-.00112				
.800	.100	.12680	-177.74150	-.00339	-.00100	.01090	.00321	.79913	1.52303	-.00082				
.800	.982	-.17858	-85.27518	-.01512	-.00445	.04136	.01269	.79886	1.52262	-.00093				
.800	2.008	-.18966	-87.33067	-.01400	-.00412	.08464	.02491	.79866	1.52232	-.00128				
.800	3.009	-.19013	-88.19888	-.01238	-.00365	.12583	.03706	.79766	1.52082	-.00220				
.800	4.014	-.19415	-88.59196	-.01147	-.00338	.16111	.04900	.79578	1.51799	-.00402				
	GRADIENT	.00048	.61023	.00034	.00010	.03953	.01165	.00008	.00012					
MACH	BETA	RUN NO. 1664/0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA	PHI	CPA0	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
		ALPHA	PHI											
.900	-3.998	-.20566	-91.50331	-.01460	-.00491	-.14578	-.04906	.89563	1.68331	-.00428				
.900	-2.967	-.20501	-92.01498	-.01417	-.00476	-.10581	-.03557	.89754	1.68681	-.00269				
.900	-1.967	-.20511	-93.04135	-.01357	-.00456	-.06758	-.02269	.89809	1.68781	-.00186				
.900	-.957	-.19942	-95.92815	-.01432	-.00480	-.02954	-.00991	.89870	1.68892	-.00128				
.900	-.141	-.09065	-.04304	-.01151	-.00386	-.0066	.00022	.89866	1.68885	-.00119				
.900	.859	.33135	78.01566	.00368	.00123	.03849	.01291	.89914	1.68972	-.00091				
.899	2.010	.24478	87.12164	.00089	.00030	.08175	.02742	.89808	1.68779	-.00128				
.900	3.016	.23031	88.34686	.00128	.00043	.12028	.04040	.89761	1.68692	-.00231				
.900	4.020	.22855	88.77986	.00204	.00069	.15966	.05372	.89621	1.68437	-.00382				
	GRADIENT	.07429	29.83333	.00266	.00089	.03792	.01275	.00004	.00008					

## IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 628  
( TCM071 ) ( 04 OCT 91 )

## PARAMETRIC DATA

		RUN NO.	1743/ O	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	180.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
1.100	-3.997	-.06197	-90.30794	-.00824	-.00329	-.13159	-.05249	1.09598	2.12251	-.00460	
1.100	-2.974	-.04579	-90.46548	-.00738	-.00294	-.09525	-.03792	1.09750	2.12639	-.00271	
1.100	-1.972	-.06509	-91.17741	-.00725	-.00288	-.06086	-.02421	1.09884	2.12986	-.00157	
1.100	-.972	-.07143	-92.24513	-.00865	-.00344	-.02732	-.01086	1.09946	2.13145	-.00087	
1.100	.014	-.02009	-108.83110	-.00830	-.00330	-.00617	-.00245	1.09916	2.13068	-.00074	
1.100	1.022	-.11158	-85.55331	-.01111	-.00442	-.03926	-.01560	1.09927	2.13096	-.00084	
1.100	2.022	-.05187	-89.27365	-.00795	-.00316	-.07436	-.02957	1.09896	2.13016	-.00119	
1.100	3.027	-.06264	-89.27243	-.00706	-.00281	-.00995	-.04374	1.09806	2.12785	-.00202	
1.100	4.021	-.06196	-89.42972	-.00550	-.00219	-.14525	-.05791	1.09619	2.12306	-.00423	
	GRADIENT	-.00107	.29475	.00013	.00005	.03430	.01366	.00004	.00011	.00007	
		RUN NO.	1727/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	180.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
1.250	-3.998	-.15493	-91.14455	-.01210	-.00521	-.13492	-.05806	1.24514	2.54192	-.00588	
1.250	-2.968	-.16591	-91.69669	-.01197	-.00514	-.09789	-.04204	1.24648	2.54599	-.00391	
1.250	-1.968	-.16042	-92.36723	-.01155	-.00495	-.06338	-.02718	1.24816	2.55115	-.00245	
1.250	-.964	-.15603	-94.54210	-.01224	-.00524	-.02778	-.01190	1.24821	2.55127	-.00161	
1.250	.099	.02879	-149.63650	-.00664	-.00285	-.01000	-.00428	1.24800	2.55065	-.00211	
1.250	1.046	-.29449	-78.66402	-.01783	-.00765	-.04156	-.01782	1.24812	2.55099	-.00229	
1.250	2.021	-.13433	-88.36101	-.01145	-.00491	-.07634	-.03274	1.24793	2.55045	-.00244	
1.250	3.018	-.16146	-88.39792	-.01126	-.00483	-.11243	-.04823	1.24733	2.54861	-.00287	
1.250	4.018	-.15784	-88.83121	-.01017	-.00437	-.14861	-.06389	1.24554	2.54315	-.00506	
	GRADIENT	-.00124	.65427	.00008	.00003	.03523	.01513	.00006	.00019	.00010	
		RUN NO.	1719/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	180.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD	
1.400	-4.003	-.14267	-91.06471	-.01403	-.00634	-.14875	-.06728	1.39551	3.03354	-.00516	
1.400	-2.974	-.14593	-91.45850	-.01334	-.00603	-.10694	-.04830	1.39678	3.03799	-.00384	
1.400	1.969	-.14427	-92.12933	-.01318	-.00595	-.06887	-.03108	1.39758	3.04079	-.00300	
1.400	-.964	-.14236	-94.14609	-.01317	-.00593	-.03016	-.01358	1.39934	3.04694	-.00078	
1.400	.092	.02419	-146.10770	-.00792	-.00357	-.01090	-.00491	1.39866	3.04457	-.00114	
1.400	1.046	-.27282	-79.41634	-.01915	-.00863	-.04759	-.02145	1.39832	3.04337	-.00194	
1.400	2.020	-.12243	-88.55933	-.01242	-.00560	-.08570	-.03864	1.39791	3.04195	-.00212	
1.400	3.018	-.14558	-88.59653	-.01164	-.00525	-.12545	-.05657	1.39793	3.04199	-.00223	
1.400	4.023	-.14745	-88.95074	-.01045	-.00472	-.16562	-.07482	1.39594	3.03505	-.00421	
	GRADIENT	-.00161	.59325	.00025	.00011	.03898	.01760	.00008	.00029	.00016	

## IA310 (AEDC 16TF-783) REPEAT RUNS

(TCM071) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1709/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00						
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD			
1.450	-3.994	-2.5646	-91.90189	-.01903	-.00873	-.15800	-.07245	1.44504	3.20973	.00571		
1.450	-2.963	-.25941	-92.57124	-.01870	-.00857	-.11312	-.05184	1.44542	3.21112	.00512		
1.450	-1.954	-.25473	-93.75513	-.01840	-.00842	-.07233	-.03311	1.44661	3.21544	.00402		
1.450	- .942	-.24938	-97.35379	-.01904	-.00867	-.03139	-.01430	1.45067	3.23021	.00088		
1.449	-1.65	-.09141	-.04304	-.01421	-.00649	.00224	.00102	1.44764	3.21917	.00144		
1.450	.966	.29022	82.84689	.00000	.00000	.05044	.02297	1.45067	3.23022	.00107		
1.451	2.005	.28802	86.60562	-.00023	-.00011	.09239	.04227	1.44797	3.22038	.00309		
1.450	3.013	.28021	87.86964	.00008	.00003	.13291	.06085	1.44610	3.21359	.00412		
1.450	4.015	.2813	88.38107	.00162	.00074	.17817	.08163	1.44587	3.21276	.00480		
GRADIENT		.09011	30.01564	.00325	.00149	.04171	.01911	.00013	.00049	.00014		
	RUN NO.	1702/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00						
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD			
1.470	-3.992	-.23428	-91.74242	-.01961	-.00902	-.15975	-.07344	1.46696	3.28991	.00896		
1.470	-2.968	-.23711	-92.37250	-.01991	-.00914	-.11578	-.05316	1.46847	3.29546	.00771		
1.470	-1.960	-.23539	-93.51715	-.01945	-.00894	-.07334	-.03369	1.46791	3.29341	.00826		
1.470	- .946	-.22804	-96.83891	-.01988	-.00913	-.03053	-.01403	1.46735	3.29135	.00869		
1.470	-1.53	-.07538	-.00343	-.01524	-.00700	.00247	.00114	1.46749	3.29187	.00826		
1.470	.969	.27016	83.32239	-.00103	-.00047	.05049	.02320	1.46729	3.29111	.00842		
1.470	2.006	.26656	86.88338	-.00101	-.00046	.09388	.04310	1.46872	3.29640	.00753		
1.470	3.013	.25964	88.02882	-.00032	-.00014	.13646	.06259	1.46886	3.29693	.00662		
1.470	4.015	.25795	88.54063	-.00019	.00009	.18086	.08305	1.46810	3.29412	.00769		
GRADIENT		.08283	30.01725	.00324	.00149	.04237	.01946	.00012	.00046	.00017		
	RUN NO.	1695/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00						
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPTD			
1.494	-3.993	-.21908	-91.58318	-.02195	-.01020	-.16932	-.07865	1.48674	3.36342	.01493		
1.495	-2.965	-.21942	-92.13426	-.02195	-.01021	-.12210	-.05681	1.48684	3.36376	.01519		
1.495	-1.964	-.21800	-93.20006	-.02175	-.01012	-.07914	-.03682	1.48629	3.36174	.01521		
1.495	- .951	-.21336	-96.32414	-.02213	-.01029	-.03441	-.01600	1.48685	3.36379	.01487		
1.495	-1.46	-.09018	-.00344	-.01487	-.00691	.00192	.00089	1.48742	3.36595	.01421		
1.495	.974	.25536	83.83739	-.00052	-.00024	.05415	.02545	1.48737	3.36576	.01405		
1.495	2.008	.24942	87.16101	-.00098	-.00046	.09947	.04622	1.48775	3.36720	.01361		
1.495	3.014	.24560	88.18785	-.00009	.00004	.14388	.06682	1.48816	3.36871	.01314		
1.495	4.021	.24114	88.69992	.00040	.00018	.19124	.08883	1.48837	3.36952	.01314		
GRADIENT		.07746	29.9926	.00365	.00170	.04488	.02085	.00023	.00087	.00017		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 630

IA310 (AEDC 16TF-783) REPEAT RUNS

(TCM071) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1690/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	180.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.521	-3.999	-.21975	-91.62289	-.02258	-.01060	-.20156	-.09460	1.50940	3.44895	-.01752
1.520	-2.965	-.22075	-92.21355	-.02292	-.01076	-.15273	-.07171	1.50859	3.44584	-.01790
1.521	-1.963	-.22075	-93.31885	-.01959	-.00920	-.09880	-.04638	1.50948	3.44922	-.01766
1.521	- .950	-.21432	-96.44292	-.01152	-.00540	-.02833	-.01328	1.51025	3.45218	-.01639
1.520	- .145	-.09510	-.04304	-.00412	-.00193	-.00101	-.00047	1.50979	3.45042	-.01644
1.521	.973	.25435	83.79779	.00567	.00266	.04855	.02277	1.51000	3.45123	-.01642
1.521	2.008	.24964	87.08176	.00162	.00076	.10984	.05156	1.50962	3.44978	-.01725
1.521	3.015	.24392	88.14816	.00093	-.00043	.16726	.07850	1.50946	3.44915	-.01719
1.520	4.021	.24306	88.62054	-.00201	-.00094	.21955	.10298	1.50974	3.45022	-.01664
GRADIENT		.07768	29.98507	.00345	.00162	.05242	.02460	.00007	.00025	.00011
	RUN NO.	1683/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	180.000
MACH	BETA	ALPHA	PHI	CPAQ	CPALPH	CPBQ	CPBETA	MPROBE	CPM	CPTD
1.544	-3.994	-.21708	-91.58318	-.00189	-.00689	-.16657	-.07869	1.53077	3.53090	-.02158
1.544	-2.970	-.22084	-92.17393	-.00663	-.00313	-.10253	-.04839	1.53177	3.53476	-.02039
1.543	-1.963	-.21940	-93.23965	-.00886	-.00419	-.06424	-.03038	1.52945	3.52577	-.02279
1.544	- .955	-.21538	-96.36375	-.01080	-.00511	-.03127	-.01479	1.52961	3.52641	-.02263
1.544	.100	-.07598	-108.71220	-.00978	-.00462	-.0074	-.00035	1.53021	3.52872	-.02182
1.544	.984	-.28397	-80.36604	-.01390	-.00656	.02776	.01310	1.53192	3.53535	-.01989
1.544	2.015	-.20416	-87.33014	-.01156	-.00544	.06857	.03228	1.53415	3.54399	-.01767
1.544	3.013	-.22164	-87.88103	-.01003	-.00472	.10788	.05080	1.53373	3.54232	-.01782
1.543	4.013	-.22423	-88.39255	-.00782	-.00368	.15795	.07437	1.53357	3.54171	-.01778
GRADIENT		-.00094	.86138	-.00071	-.00033	.03766	.01776	.00048	.00185	.00060

RUN NO.		1102/ O	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000	PARAMETRIC DATA
MACH	ALPHA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPBF	PTTF
.599	-8.006	- .92921	- .93139	- .93036	- .93087	- .02424	- .02488	- .02473	- .02480	1997.61800	2039.60000
.599	-6.998	- .80968	- .81207	- .81093	- .81150	- .02464	- .02475	- .02468	- .02472	2007.79300	2039.81000
.599	-6.001	- .68925	- .69069	- .68994	- .69032	- .02209	- .02289	- .02251	- .02270	2016.92101	2040.96001
.599	-4.998	- .57305	- .57447	- .57348	- .57398	- .01744	- .01812	- .01786	- .01799	2024.47099	2040.71001
.599	-3.995	- .45092	- .45299	- .45180	- .45239	- .01433	- .01459	- .01433	- .01446	2030.62300	2040.63000
.599	-3.002	- .33231	- .33436	- .33340	- .33388	- .01572	- .01620	- .01605	- .01612	2035.00800	2041.59000
.600	-1.999	- .21422	- .21523	- .21412	- .21468	- .01824	- .01885	- .01880	- .01886	2038.01801	2040.97000
.600	- .995	- .09981	- .10156	- .10043	- .10099	- .02022	- .02053	- .02040	- .02046	2039.71899	2041.17999
.600	- .009	- .01234	- .00985	- .01094	- .01039	- .02144	- .02188	- .02173	- .02181	2040.28400	2040.67000
.600	1.003	- .12754	- .12569	- .12659	- .12614	- .02009	- .02022	- .02036	- .02029	2040.11200	2040.85001
.600	2.001	- .24561	- .24342	- .24443	- .24392	- .01669	- .01693	- .01704	- .01698	2039.88901	2040.62000
.600	3.011	- .36525	- .36262	- .36333	- .36298	- .01118	- .01163	- .01157	- .01160	2039.51601	2040.84000
.600	4.005	- .48596	- .48396	- .48488	- .48442	- .01120	- .01138	- .01168	- .01153	2038.61400	2040.03900
.600	4.999	- .60159	- .59948	- .60021	- .59984	- .01200	- .01239	- .01229	- .01239	2036.65199	2040.05000
.600	6.003	- .72073	- .71874	- .71961	- .71918	- .01333	- .01306	- .01314	- .01310	2033.17500	2040.30000
.600	6.998	- .83792	- .83587	- .83693	- .83640	- .01160	- .01107	- .01133	- .01120	2027.99800	2039.92999
.600	7.996	- .95242	- .94960	- .95053	- .95007	- .00886	- .00937	- .00954	- .00946	2021.59599	2040.50000
GRADIENT		.11689	.11682	.11679	.11681	.00052	.00055	.00050	.00052	1.00495	-.08126
RUN NO.		1109/ O	RN/L =	3.76	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000	PARAMETRIC DATA
MACH	ALPHA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPBF	PTTF
.800	-8.000	-1.31676	-1.31756	-1.31707	-1.31732	- .03198	- .03289	- .03233	- .03261	1964.55499	2019.55000
.800	-6.987	-1.14284	-1.14483	-1.14415	-1.14449	- .03078	- .03159	- .03108	- .03134	1975.44701	2017.20200
.800	-5.995	- .97868	- .97931	- .97878	- .97905	- .02573	- .02646	- .02584	- .02615	1986.39500	2016.89000
.800	-4.981	- .80680	- .80905	- .80808	- .80856	- .01888	- .01897	- .01865	- .01881	1996.19200	2017.35001
.800	-3.994	- .63752	- .63880	- .63784	- .63832	- .01490	- .01492	- .01454	- .01473	2004.38800	2018.14999
.800	-2.997	- .47424	- .47536	- .47435	- .47485	- .01663	- .01674	- .01662	- .01668	2010.64999	2018.17999
.800	-1.993	- .30550	- .30664	- .30566	- .30615	- .01918	- .02011	- .01977	- .01994	2014.28799	2018.53000
.800	- .989	- .14225	- .14369	- .14285	- .14327	- .02361	- .02389	- .02381	- .02385	2016.40401	2017.69000
.800	- .014	- .01892	- .01700	- .01790	- .01745	- .02333	- .02396	- .02385	- .02391	2016.75999	2017.62000
.800	-1.003	- .18164	- .18045	- .18106	- .18076	- .01855	- .01867	- .01868	- .01867	2017.21700	2018.55000
.800	-2.006	- .34573	- .34469	- .34541	- .34505	- .01416	- .01440	- .01456	- .01448	2017.51601	2018.41000
.800	-3.005	- .51308	- .51401	- .51354	- .51308	- .00889	- .00900	- .00898	- .00898	2016.56100	2017.55000
.800	-4.004	- .68284	- .68240	- .68158	- .68199	- .00896	- .00849	- .00859	- .00854	2014.19701	2015.28999
.800	-5.003	- .84794	- .84687	- .84755	- .84721	- .00791	- .00783	- .00796	- .00789	2012.23500	2016.96001
.800	-6.002	- 1.01425	- 1.01405	- 1.01460	- 1.01432	- .00563	- .00624	- .00643	- .00633	2011.24899	2019.87000
.800	-7.012	- 1.18249	- 1.18176	- 1.18224	- 1.18200	- .00278	- .00338	- .00358	- .00348	2005.97200	2019.88000
.800	-8.001	- 1.34282	- 1.34281	- 1.34377	- 1.34329	- .00380	- .00353	- .00387	- .00371	1996.10400	2018.38000
GRADIENT		.16492	.16498	.16496	.16497	.00088	.00092	.00087	.00089	1.76276	-.13117

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 632

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM001) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-8.002	-1.41289	-1.41437	-1.41392	-1.41415	-0.03481	-0.03590	-0.03539	-0.03564	1926.19099	1984.19000
.900	-6.993	-1.23042	-1.23284	-1.23186	-1.23235	-0.03382	-0.03404	-0.03364	-0.03384	1940.07899	1984.14000
.900	-5.994	-1.05163	-1.05363	-1.05283	-1.05323	-0.02768	-0.02868	-0.02838	-0.02853	1952.20599	1984.07001
.900	-4.990	-8.6948	-8.7168	-8.7095	-8.7131	-0.02045	-0.02085	-0.02052	-0.02068	1961.84801	1983.75999
.900	-3.991	-6.8462	-6.8462	-6.84693	-6.84652	-0.01556	-0.01610	-0.01620	-0.01631	1970.12500	1984.02000
.900	-2.976	-5.0434	-5.0672	-5.0599	-5.0635	-0.01773	-0.01832	-0.01831	-0.01831	1975.71400	1983.66000
.900	-1.994	-3.2787	-3.3024	-3.2935	-3.2979	-0.02269	-0.02288	-0.02273	-0.02281	1979.71700	1984.52000
.900	-999	-15221	-15473	-15410	-15441	-0.02631	-0.02653	-0.02655	-0.02654	1981.99899	1983.70000
.900	-020	-02139	-01903	-01973	-01938	-0.02586	-0.02555	-0.02563	-0.02559	1982.75000	1984.03999
.900	1.003	-1.9797	-1.9461	-1.9545	-1.9503	-0.01937	-0.01914	-0.01939	-0.01926	1982.97200	1984.20000
.900	2.007	-3.7676	-3.7422	-3.7505	-3.7464	-0.01473	-0.01471	-0.01501	-0.01486	1982.87700	1984.24001
.900	3.011	-5.5421	-5.5154	-5.5219	-5.5187	-0.01030	-0.01030	-0.01077	-0.01086	1982.97501	1984.32001
.900	4.007	-7.3547	-7.3282	-7.3357	-7.3319	-0.01005	-0.01005	-0.01033	-0.01049	1982.19501	1983.60001
.899	5.006	-9.1295	-9.1012	-9.1078	-9.1045	-0.00987	-0.01006	-0.01055	-0.01030	1980.21800	1984.17999
.899	6.007	-1.09125	-1.08844	-1.08910	-1.08877	-0.00759	-0.00737	-0.00780	-0.00759	1976.21600	1984.12000
.900	7.002	-1.26979	-1.26702	-1.26774	-1.26738	-0.00656	-0.00610	-0.00667	-0.00639	1969.66800	1983.75999
.900	8.008	-1.44365	-1.44158	-1.44205	-1.44182	-0.00629	-0.00639	-0.00691	-0.00665	1961.14799	1983.83000
	GRADIENT	.17751	.17744	.17744	.17744	.00095	.00095	.00093	.00096	1.93692	.01779

RUN NO.	RN/L = 0	RN/L = 3.00	RN/L = 3.89	RN/L = 4.00	RN/L = 4.81	RN/L = 5.00	RN/L = 5.89	RN/L = 6.00	RN/L = 6.81	RN/L = 7.00	RN/L = 7.89
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.099	-7.994	-1.09751	-1.09952	-1.09839	-1.09896	-0.01611	-0.01753	-0.01702	-0.01727	1401.66499	1445.42599
1.100	-6.977	-9.5594	-9.5740	-9.5630	-9.5625	-0.01520	-0.01639	-0.01599	-0.01619	1413.55299	1446.00999
1.100	-5.998	-8.1808	-8.2094	-8.1984	-8.2039	-0.01312	-0.01349	-0.01253	-0.01282	1421.77000	1445.05099
1.100	-4.975	-6.7801	-6.8068	-6.7961	-6.8014	-0.00414	-0.00788	-0.00754	-0.00771	1412.43500	1445.29100
1.100	-3.975	-5.33387	-5.3650	-5.3529	-5.3590	-0.00434	-0.00547	-0.00530	-0.00539	1435.35400	1445.24001
	GRADIENT	.14417	.14421	.14434	.14428	.00020	.00241	.00224	.00232	.002375	-.05105

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM001) (04 Oct 91)

## PARAMETRIC DATA

RUN NO.: 11159 / O RN/L = 2.99 GRADIENT INTERVAL = -5.00/ 5.00

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 634

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM002) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.599	-8.006	-.92886	-.93002	-.93058	-.02380	-.02473	-.02439	-.02456	1997.78600	2040.16000
.599	-6.994	-.81044	-.81175	-.81129	-.02341	-.02368	-.02321	-.02344	2007.84599	2040.44000
.599	-5.996	-.69144	-.69302	-.69249	-.02048	-.02089	-.02062	-.02076	2016.66200	2040.05000
.599	-4.993	-.57298	-.57428	-.57326	-.01561	-.01641	-.01626	-.01634	2023.70799	2040.17000
.599	-4.000	-.45260	-.45447	-.45339	-.01181	-.01264	-.01230	-.01247	2029.63400	2039.63000
.600	-3.003	-.33453	-.33639	-.33534	-.01370	-.01438	-.01420	-.01429	2033.68700	2040.31000
.600	-1.999	-.21332	-.21482	-.21369	-.01717	-.01769	-.01774	-.01771	2036.61900	2039.64999
.600	-1.000	-.09910	-.10102	-.0997	-.01744	-.01808	-.01793	-.01800	2038.31100	2039.39999
.600	.014	0.1372	0.1095	0.1227	0.01161	0.01968	0.02036	0.02035	2038.78799	2039.80000
.600	1.002	1.2755	1.2588	1.2628	1.01911	1.01924	1.01920	1.01920	2038.89500	2039.60001
.601	2.001	2.4539	2.4282	2.4384	2.24333	2.01590	2.01592	2.01591	2038.91100	2039.75999
.601	3.005	3.6609	3.6357	3.6440	3.36398	3.01245	3.01273	3.01291	2038.76401	2039.86000
.601	4.010	4.8738	4.8515	4.8625	4.48570	4.01119	4.01168	4.01173	2037.97301	2040.27000
.601	5.004	6.0154	5.9870	5.9971	5.59921	5.01153	5.01173	5.01173	2036.28000	2039.97000
.600	6.003	7.1975	7.1777	7.1865	7.1821	6.01074	6.01084	6.01098	2032.97301	2039.94000
.599	6.997	8.3666	8.3488	8.3574	8.3531	7.00960	7.00952	7.00986	2027.94000	2039.23000
.600	7.997	9.5142	9.4821	9.4920	9.4870	8.00814	8.00847	8.00892	2021.28300	2040.39999
	GRADIENT	1.1691	1.1681	1.1679	.11680	.00011	.00012	.00015	1.36652	.00009
	RUN NO.	1103/ 0	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/ 5.00				
	RUN NO.	1111/ 0	RN/L =	3.76	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.800	-8.005	-1.31507	-1.31449	-1.31478	-.02553	-.02663	-.02629	-.02646	1962.36000	2017.83000
.800	-6.986	-1.14261	-1.14479	-1.14463	-.02545	-.02665	-.02625	-.02645	1975.95799	2018.25000
.800	-5.995	-.97831	-.97968	-.97931	-.02081	-.02246	-.02216	-.02231	1987.52800	2017.92000
.800	-5.003	-.80882	-.81109	-.81023	-.81066	-.01514	-.01603	-.01577	1996.92200	2018.31000
.800	-3.989	-.63665	-.63809	-.63725	-.63767	-.01199	-.01292	-.01270	2004.87900	2018.22000
.800	-2.997	-.47241	-.47381	-.47306	-.47344	-.01345	-.01464	-.01449	2010.26601	2017.80000
.800	-1.999	-.30580	-.30741	-.30655	-.30698	-.01798	-.01912	-.01902	2014.22099	2018.21001
.800	-1.989	-.14341	-.14247	-.14294	-.14247	-.02106	-.02188	-.02185	2016.09100	2017.61000
.800	.025	.01959	.01913	.01863	.01814	-.02172	-.02251	-.02262	2017.04201	2017.89999
.799	1.008	1.18204	1.18072	1.18119	1.18095	1.01891	1.01959	1.01989	2017.04900	2018.12000
.799	2.007	.34850	.34721	.34792	.34756	-.01329	-.01414	-.01429	2017.34700	2018.21001
.800	3.005	.51305	.51181	.51283	.51232	-.01053	-.01078	-.01098	2017.20900	2018.17999
.800	4.020	.68527	.68382	.68455	.68418	-.01048	-.01045	-.01067	2016.15300	2018.28000
.800	5.003	.84891	.84787	.84867	.84827	-.00969	-.00987	-.01027	2014.19901	2018.30000
.799	6.018	1.01506	1.01455	1.01528	1.01492	-.00945	-.00966	-.01003	2009.83000	2017.94000
.799	7.002	1.18101	1.18090	1.18045	1.18090	-.00732	-.00792	-.00838	2003.28400	2018.62000
.800	7.995	1.34161	1.34228	1.34171	1.34228	-.00690	-.00694	-.00742	2017.1995	2017.96001
	GRADIENT	.16447	.16450	.16449	.16450	.00044	.00056	.00050	.00053	.021773

卷之三

	RUN NO.	1148 / O	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/	5.00
ALPHA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2
-8.010	-1.09944	-1.10167	-1.10060	-1.10114	-0.1637	-0.01775	-0.1736
-6.971	-9.5328	-9.5605	-9.5474	-9.5539	-0.1557	-0.01664	-0.162
-5.993	-8.1803	-8.2068	-8.1946	-8.2007	-0.1276	-0.01341	-0.1283
-4.996	-6.8024	-6.8302	-6.8171	-6.8236	-0.0750	-0.00838	-0.0080
-3.973	-5.3415	-5.3686	-5.3572	-5.3629	-0.0441	-0.00575	-0.00533
-2.982	-3.9458	-3.9696	-3.9564	-3.9630	-0.0072	-0.00185	-0.00156
-2.001	-2.5346	-2.5621	-2.5494	-2.5557	-0.0677	-0.00745	-0.0072
-979	-1.1445	-1.1765	-1.1653	-1.1709	-0.0564	-0.00667	-0.0064
.003	.01254	.01012	.01141	.01076	-0.0496	-0.00605	-0.0058
1.004	1.0088	1.00815	1.0019	1.00867	-0.0282	-0.00319	-0.00311
.099	2.015	2.08921	2.08613	2.08738	.00121	.00006	.00011
3.022	4.22687	4.22514	4.22625	4.22570	.00137	.00073	.00066
4.009	.56931	.56690	.56785	.56737	.00005	.00091	.0008
5.026	7.12335	7.1049	7.1136	7.1092	.00155	.00088	.00077
6.005	.84812	.84677	.84773	.84725	.00378	.00352	.00333
7.008	.98730	.98510	.98630	.98570	.00503	.00462	.00433
8.009	1.11763	1.11610	1.11685	1.11648	.00618	.00543	.00505
GRADIENT	13778	13782	13780	13781	.00079	.00082	.0007

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 636

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM003) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1108/ O	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000	P12F
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PTFF	
.599	ALPHA	-.92967	-.93136	-.93029	-.93082	-.02887	-.02922	-.02869	1997.44501	2040.13000	
-8.006		-.81067	-.81237	-.81141	-.81189	-.02915	-.02912	-.02871	2007.84500	2040.60001	
-6.993		-.69301	-.69415	-.69328	-.69372	-.02396	-.02469	-.02423	2016.71800	2040.57001	
-5.996		-.57537	-.57611	-.57508	-.57560	-.01997	-.02059	-.02033	2023.99300	2039.64999	
-5.004		-.45115	-.45283	-.45178	-.45231	-.01737	-.01747	-.01728	2030.07700	2040.46001	
-3.995		-.33297	-.33470	-.33373	-.33422	-.01608	-.01657	-.01638	2034.18100	2040.66000	
-2.997		-.21599	-.21652	-.21566	-.21609	-.01778	-.01835	-.01830	2037.13699	2040.16000	
-2.004		-.10090	-.10201	-.10105	-.10153	-.01886	-.01909	-.01898	2038.76100	2039.67000	
-1.000		-.009	-.01143	-.00975	-.01069	-.01022	-.02158	-.02213	2039.42999	2039.98000	
.600		1.002	1.2644	1.2521	1.2606	1.2564	1.2635	1.2671	2039.33600	2040.44000	
.601		2.001	2.4361	2.4208	2.4298	2.4253	2.4251	2.4277	2039.29500	2039.96001	
.601		3.000	3.6586	3.6366	3.6456	3.6411	3.6497	3.6521	2039.29100	2040.21001	
.601		4.005	4.8585	4.8451	4.8543	4.8497	4.8510	4.8529	2039.74001	2040.41000	
.601		5.004	6.0215	6.0074	6.0170	6.0122	6.0184	6.0180	2036.90601	2040.67000	
.601		6.008	7.2013	7.1911	7.1974	7.1942	7.1967	7.1980	2033.36099	2040.72000	
.600		6.997	8.38822	8.3712	8.3781	8.3747	8.3853	8.3814	2028.26500	2040.39000	
.600		8.002	9.5307	9.5109	9.5190	9.5150	9.5067	9.5057	2021.44000	2040.16000	
	GRADIENT	1.1651	1.1647	1.1646	1.1647	.00070	.00071	.00069	.91423	-.01964	

	RUN NO.	1112/ O	RN/L =	3.75	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000	P12F
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PTFF	
.800	ALPHA	-1.31372	-1.31572	-1.31503	-1.31538	-.03084	-.03235	-.03177	1962.21600	2018.05000	
-8.005		-1.14239	-1.14516	-1.14468	-1.14492	-.02866	-.02976	-.02939	1976.17700	2017.78000	
-6.992		-9.78480	-.98097	-.98015	-.98056	-.02468	-.02592	-.02554	1987.51900	2017.98000	
-5.995		-.80685	-.80963	-.80891	-.80927	-.01817	-.01891	-.01860	1995.97701	2017.62000	
-4.982		-.63337	-.63619	-.63525	-.63572	-.01291	-.01380	-.01349	2004.76401	2018.19000	
-3.983		-.2.996	-.46891	-.47196	-.47090	-.01454	-.01554	-.01540	2010.02901	2018.06000	
.799		-1.993	-.30285	-.30532	-.30436	-.30484	-.30417	-.30417	2014.16100	2017.80000	
-1.000		-1.000	-.14088	-.14378	-.14270	-.14324	-.02206	-.02259	2015.93900	2018.25999	
.800		.01861	-.01676	-.01774	-.01725	-.01725	-.02206	-.02270	2016.97800	2018.24001	
.800		1.013	1.8454	1.8222	1.8271	1.8247	1.8276	1.8191	2018.01803	2016.96400	
.800		2.006	3.4610	3.4509	3.4592	3.4550	3.4525	3.4505	2017.01311	2017.17000	
.799		3.004	5.1271	5.1148	5.1237	5.1193	5.0692	5.0782	2016.75500	2018.00999	
.800		4.010	6.8346	6.8224	6.8327	6.8275	6.0666	6.0728	2016.12199	2018.32001	
.800		5.003	8.4708	8.4623	8.4717	8.4670	8.0628	8.0636	2014.28999	2018.14000	
.800		6.002	1.01276	1.01182	1.01269	1.01226	1.00538	1.00579	2010.14101	2018.11000	
.800		7.012	1.18165	1.18059	1.18099	1.18036	1.00330	1.00376	2003.40900	2018.25000	
.800		8.000	1.34144	1.34097	1.34213	1.34155	1.00230	1.00248	1995.35600	2018.24001	
	GRADIENT	.16455	.16478	.16477	.16477	.00099	.00099	.00099	.000996	1.82440	

.01929

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 637

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM003) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	RUN NO.	1149/ O	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000	PT2F
ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF			
1.099	-1.09792	-1.10034	-1.09926	-1.09980	-0.1625	-0.1755	-0.1705	-0.1730	1401.55099	1445.37399	
-7.994	-6.988	-6.95603	-9.5869	-9.5829	-0.01571	-0.01655	-0.01619	-0.01637	1413.43500	1445.76601	
1.100	-5.988	-8.1768	-8.2049	-8.1937	-0.1300	-0.1323	-0.1288	-0.1305	1421.94600	1445.41499	
-5.100	-4.990	-6.8028	-6.8291	-6.8184	-0.0794	-0.0856	-0.0826	-0.0841	1429.16499	1445.00101	
1.100	-3.991	-5.35666	-5.3850	-5.3732	-0.00482	-0.00561	-0.00532	-0.00546	1435.28799	1445.67999	
-2.980	-2.9415	-3.9617	-3.9499	-3.9558	-0.00638	-0.00712	-0.00679	-0.00695	1439.56100	1445.12300	
-1.980	-1.980	-2.5125	-2.5380	-2.5262	-0.25321	-0.00510	-0.00586	-0.00584	1442.77800	1445.31100	
-1.100	-0.993	-1.1727	-1.2036	-1.1907	-0.11971	-0.00632	-0.00658	-0.00654	1444.34200	1445.64900	
-1.100	-0.021	-0.1519	-0.1295	-0.1411	-0.01353	-0.00468	-0.00503	-0.00501	1444.92599	1445.19901	
-1.100	.990	.14844	.14586	.14705	.14645	-0.00299	-0.00341	-0.00337	1445.12100	1445.52000	
1.100	2.010	2.28699	2.28450	2.28561	.28505	.00024	-0.00019	-0.00035	-0.00027	1445.05600	1445.36600
1.100	3.016	4.2596	4.2446	4.2555	.42500	.00215	.00252	.00200	.00207	1444.99100	1445.36600
1.100	4.019	5.7089	5.6846	5.6951	.56898	.00306	.00319	.00314	.00319	1444.40300	1445.47501
1.100	5.014	7.1012	7.0823	7.0924	.70873	.00493	.00490	.00480	.00485	1443.02699	1445.44200
1.099	6.010	8.4901	8.4751	8.4846	.84798	.00387	.00401	.00360	.00381	1439.79500	1445.09000
1.100	7.007	.98647	.98420	.98551	.98485	.00495	.00459	.00437	.00448	1435.24500	1445.50800
1.099	8.004	1.11742	1.11586	1.11658	1.11622	.00580	.00567	.00527	.00547	1428.91901	1445.46300
		GRADIENT			.13780	.00116	.00118	.00121	.00121	1.45534	.02086

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 638

(UCM004) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	RN/L	BETA	GRADIENT INTERVAL = -5.00/ 5.00	PI1F
.800	-8.006	-1.31228	-1.31577	-1.31542	-0.02528
.800	-6.987	-1.14240	-1.14556	-1.14520	-0.02584
.800	-5.995	-97700	• -98070	-98035	-0.02240
.800	-4.992	-80719	-81078	-81027	-0.02256
.800	-3.994	-63617	-63879	-63832	-0.02473
.800	-2.997	-47225	-47494	-47444	-0.02485
.800	-1.988	-30201	-30451	-30396	-0.02617
.800	-0.984	-14022	-14260	-14139	-0.02619
.800	.014	0.1990	0.16663	0.1771	-0.02654
.800	1.008	.18259	.18099	.18167	-0.02660
.800	2.017	.35009	.34773	.34862	-0.02690
.800	3.016	.51631	.51437	.51549	-0.02720
.800	4.004	.68358	.68152	.68266	-0.02740
.800	5.003	.84717	.84582	.84626	-0.02754
.800	6.002	1.01302	1.01201	1.01296	-0.02755
.799	7.001	1.17943	1.17939	1.18031	-0.02756
.800	8.000	1.34295	1.34208	1.34336	-0.02757
	GRADIENT	.16482	.16495	.16495	-0.02758
				.00013	.00019
				.00023	.00023
				1.83078	.00282

PARAMETRIC DATA										
RUN NO.	1105/ 0	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	.000	PHI =	= 180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.600	7.999	.93049	.93118	.93084	.02999	.02941	.02924	.02932	2022.56400	2040.95000
.600	93218	.81688	.81561	.81633	.01597	.03006	.02940	.02932	2029.53300	2040.67000
.600	5.002									
.600	5.999	69836	.69706	.69769	.69737	.02680	.02506	.02595	2026.000	2034.35300
.600	5.999	57988	.57863	.57948	.57906	.01718	.02052	.02055	2037.50400	2040.94000
.600	4.996									
.600	4.996	46142	.45969	.46044	.46006	.01706	.01591	.01594	2038.92700	2041.00999
.600	3.998									
.600	3.001	34351	.34157	.34243	.34200	.01743	.01661	.01662	2039.55800	2039.92999
.600	1.997	22319	.22144	.22235	.22189	.01863	.01760	.01764	2039.56400	2040.52000
.601	.993									
.600	.00766	.00880	-.00797	-.00839	-.01210	.02034	.02061	.02047	2039.10001	2040.14999
.600	-.011									
.600	-.004	12312	-.12392	-.12290	-.12341	.02166	.02131	.02112	2038.17799	2039.81000
.600	-.2.003	23763	-.23822	-.23721	-.23771	.01747	.01612	.01628	2036.34900	2039.81000
.600	-.3.002	35616	-.35765	-.35654	-.35709	.01518	.01408	.01432	2033.03500	2040.08000
.601	-.4.007	47803	-.47942	-.47861	-.47901	.01540	.01402	.01429	2028.34300	2039.97000
.600	-.5.005	59358	-.59413	-.59302	-.59357	.01538	.01405	.01458	2022.42599	2039.74001
.600	-.5.999	71180	-.71275	-.71160	-.71217	.01710	.01595	.01649	2014.88800	2039.64999
.600	-.6.999	83112	-.83278	-.83183	-.83231	.01480	.01359	.01402	2005.60699	2040.13000
.600	-.7.998	94577	-.94555	-.94655	-.94705	.01351	.01223	.01286	2005.59599	2039.89999
.599	GRADIENT	.00000				.00000	.00000	.00000		
RUN NO.	1115/ 0	RN/L =	3.75	GRADIENT INTERVAL =	-5.00/	5.00				
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.800	7.997	1.31821	1.31717	1.31841	1.31779	.03133	.02991	.02957	1996.81779	2017.42000
.800	6.994	1.14887	1.14753	1.14891	1.14822	.03094	.02960	.02979	2004.44501	2017.63000
.800	5.997	98521	.98396	.98530	.98463	.02656	.02578	.02544	2010.73801	2018.10001
.800	4.984	81953	.81757	.81857	.81807	.01911	.01876	.01856	2014.25000	2017.94000
.800	3.997	65109	.64890	.65002	.64946	.01563	.01469	.01453	2016.22000	2017.99001
.800	2.994	48300	.48119	.48212	.48166	.01660	.01568	.01563	2017.19099	2017.99001
.800	1.996	31759	.31549	.31654	.31602	.02046	.01964	.01964	2016.99600	2017.95000
.800	.997	15072	.14911	.15018	.14964	.02381	.02282	.02272	2017.14999	2018.08000
.800	-.017	00846	-.01086	-.00970	-.01028	.02352	.02351	.02351	2016.82001	2017.88000
.800	-.005	17234	-.17462	-.17357	-.17410	.02093	.01978	.01980	2015.70700	2018.42000
.799	-.004	33498	-.33742	-.33633	-.33687	.01695	.01559	.01575	2013.81799	2018.42999
.799	-.002	50181	-.50427	-.50322	-.50375	.01354	.01196	.01261	2009.43500	2017.96001
.800	-.006	66881	-.67124	-.67030	-.67077	.01364	.01253	.01271	2003.32300	2017.78000
.800	-.010	83500	-.83810	-.83760	-.83710	.01602	.01405	.01421	1995.57401	2017.97000
.799	-.008	00178	-.00504	-.00419	-.00418	.01307	.01326	.01345	1985.96700	2018.00000
.800	-.009	17268	-.17590	-.17483	-.17537	.01134	.00967	.01100	1973.51500	2018.05000
.800	-.002	33365	-.33621	-.33683	-.33652	.01239	.01047	.01180	1960.22200	2017.85001
.800	GRADIENT	.00000				.00000	.00000	.00000		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGLES-FAIR OFF

HICM005 ( 01 OCT 81 )

## PARAMETRIC DATA

DPB	PTTF	PT2F
.02288	1430 .23599	1446 .1550
.02066	1436 .31200	1445 .7879
.01699	1440 .67000	1445 .4480
.01231	1443 .31700	1445 .1480
.01004	1444 .82600	1445 .4830
.01135	1445 .12500	1445 .5870
.00781	1445 .09801	1445 .3300
.00884	1445 .59500	1445 .3690
.00815	1445 .14500	1445 .3710
.00665	1444 .13200	1445 .1890
.00264	1442 .33299	1445 .5640
.00214	1439 .20200	1445 .4600
.00500	1434 .57800	1445 .3660
.00573	1428 .62199	1445 .4500
.00074	1420 .75000	1445 .5110
.00019	1411 .77699	1445 .4610
.00095	1400 .80000	1445 .5440

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 641  
IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF (UCM005) ( 04 OCT 91 )

		PARAMETRIC DATA								
		RN/L =	2.99	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	DPA CAL	DPA1	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.250	7.989	1.19318	1.18974	1.19070	.03000	.02925	.02928	.02927	1403.48399	1419.37199
1.250	6.983	1.04201	1.03904	1.04009	.03956	.02867	.02774	.02776	1409.75700	1419.69299
1.250	5.992	.89362	.89015	.89086	.02357	.02269	.02277	.02273	1413.69000	1419.57899
1.249	5.992	.89362	.89015	.89050	.01754	.01686	.01680	.01683	1416.46600	1419.51401
1.250	4.988	.74539	.74172	.74222	.01381	.01314	.01322	.01318	1417.74300	1419.56400
1.250	3.993	.58879	.58555	.58614	.01322	.01314	.01467	.01471	1418.28101	1419.58200
1.250	2.981	.43526	.43160	.43295	.01511	.01462	.01750	.01737	1417.85400	1419.73500
1.250	1.992	.28408	.28056	.28185	.01762	.01724	.01849	.01835	1417.52800	1419.42999
1.250	.988	.13467	.13158	.13284	.01880	.01863	.01571	.01571	1417.67200	1419.40100
1.250	-.014	-.01169	-.01459	-.01304	.01620	.01551	.01183	.01149	1417.89400	1419.37399
1.250	-.1.015	-.16192	-.16466	-.16326	.01223	.01114	.00939	.01001	1415.41701	1419.23700
1.250	-.2.013	-.30854	-.31103	-.31039	.00940	.00877	.01051	.01116	1411.98500	1419.72200
1.250	-.3.008	-.45631	-.45908	-.45839	.01095	.00987	.00000	.00000	.00000	.00000
	GRADIENT	.00000	.00000	.00000	.00000	.00000				

		PARAMETRIC DATA								
		RN/L =	3.20	GRADIENT INTERVAL =	-5.00/	5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	DPA CAL	DPA1	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.599	-3.996	.02360	.02218	.02288	.02253	.45347	.45431	.45435	2034.07500	2039.53000
.600	-2.990	.02489	.02311	.02401	.02356	.33588	.33579	.33583	2036.74899	2039.62000
.599	-1.995	.02594	.02394	.02496	.02445	.21938	.21922	.21916	2038.10001	2038.95000
.600	-.996	.02453	.02249	.02326	.02287	.10531	.10602	.10601	2038.61099	2039.64999
.600	.010	.02457	.02277	.02364	.02321	.01135	.01027	.01113	.01070	.01070
.600	1.007	.02037	.01836	.01925	.01881	.12868	.12804	.12830	12817.63699	2039.25999
.600	1.997	.02017	.01818	.01919	.01868	.24578	.24371	.24399	2038.25000	2040.14999
.601	2.992	.01765	.01627	.01727	.01677	.36309	.36150	.36184	.36167	.36167
.601	3.989	.02116	.01955	.02055	.02005	.48308	.48229	.48279	.48254	.48254
	GRADIENT	-.00079	-.00078	-.00075	-.00077	.11704	.11688	.11695	.11692	.11692

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 642

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM006) ( 04 OCT 91 )

## PARAMETRIC DATA

		PARAMETRIC DATA									
		RUN NO.	1113/ 0	RN/L =	3.75	GRADIENT INTERVAL = -5.00/ 5.00			ALPHA =	.000	PHI =
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.800	-3.992	.02731	.02434	.02522	.02478	.64185	.64340	.64374	.64357	2010.76500	2018.39000
.800	-2.987	.02916	.02602	.02707	.02654	.47378	.47523	.47544	.47533	2014.12700	2017.87000
.800	-1.977	.02875	.02686	.02796	.02741	.30704	.30864	.30890	.30877	2016.02600	2017.52000
.800	- .989	.02987	.02798	.02893	.02845	.14718	.14854	.14863	.14859	2016.57401	2018.24001
.800	.016	.02712	.02498	.02606	.02552	.01592	.01427	.01431	.01429	2016.82500	2017.99001
.799	1.001	.02263	.02073	.02161	.02117	.18108	.18026	.18035	.18030	2016.69099	2018.02000
.800	2.003	.02158	.01828	.01916	.01872	.34903	.34883	.34887	.34885	2016.19701	2017.20001
.800	3.002	.01889	.01580	.01666	.01623	.51475	.51385	.51412	.51398	2014.57600	2018.03999
.800	3.990	.02151	.01923	.02013	.01968	.68176	.68221	.68242	.68232	2011.54700	2017.86000
GRADIENT		-.00126	-.00126	-.00128	-.00127	.16544	.16566	.16573	.16570	.08393	-.02068
		RUN NO.	1120/ 0	RN/L =	3.89	GRADIENT INTERVAL = -5.00/ 5.00			ALPHA =	.000	PHI =
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-3.986	.03075	.02757	.02842	.02799	.69074	.69097	.69135	.69116	1976.72200	1984.17000
.900	-2.981	.03431	.03089	.03188	.03139	.51336	.51337	.51381	.51359	1980.40800	1984.03000
.900	-1.982	.03551	.03235	.03311	.03273	.33533	.33579	.33597	.33588	1981.91100	1983.53999
.900	- .983	.03536	.03203	.03287	.03245	.15854	.15886	.15897	.15891	1982.77100	1983.85001
.900	.012	.03274	.02963	.03055	.03009	.01777	.01708	.01705	.01707	1983.06000	1984.13000
.899	1.002	.02741	.02406	.02493	.02450	.19628	.19477	.19493	.19485	1983.14700	1984.21001
.899	1.998	.02408	.02058	.02146	.02102	.37596	.37417	.37449	.37433	1982.33099	1983.81000
.900	3.003	.02425	.02085	.02165	.02125	.55161	.55035	.55028	.55031	1980.64600	1984.19000
.900	3.993	.02656	.02354	.02439	.02396	.73396	.73261	.73305	.73283	1977.50700	1984.00000
GRADIENT		-.00130	-.00130	-.00130	-.00130	.17841	.17820	.17830	.17825	.08555	.01167
		RUN NO.	1151/ 0	RN/L =	3.00	GRADIENT INTERVAL = -5.00/ 5.00			ALPHA =	.000	PHI =
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.100	-3.983	.01144	.00816	.00938	.00877	.53965	.54048	.54042	.54045	1440.62000	1445.30499
1.100	-2.982	.01274	.00928	.01063	.00995	.40024	.40083	.40074	.40079	1442.80200	1445.45599
1.100	-1.980	.01406	.01166	.01302	.01234	.25901	.26000	.26016	.26008	1444.42200	1445.50700
1.100	- .995	.01322	.01093	.01217	.01155	.12251	.12306	.12294	.12300	1445.08099	1445.35800
1.100	.021	.00945	.00699	.00835	.00767	.01652	.01530	.01555	.01542	1445.25600	1445.64400
1.100	1.005	.00746	.00493	.00633	.00563	.15417	.15282	.15318	.15300	1444.96300	1445.41000
1.100	2.016	.00744	.00474	.00585	.00530	.28921	.28876	.28897	.28901	1444.54201	1445.26401
1.100	3.005	.00858	.00509	.00642	.00576	.42441	.42320	.42368	.42344	1443.58299	1445.65800
1.100	4.001	.01461	.01136	.01275	.01205	.56648	.56772	.56693	.56671	1440.87601	1445.54700
GRADIENT		-.00031	-.00033	-.00032	-.00033	.13818	.13813	.13820	.13817	.05861	.01905

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

(UCM006) ( 04 OCT 91 )

PAGE 643

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

## PARAMETRIC DATA

	RUN NO.	1162/ 0	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.250	-3.987	.02073	.01738	.01877	.01808	.058159	.58135	.58134	1413.25400	1419.37500
1.250	-2.967	.02260	.01879	.02020	.01950	.42851	.42836	.42842	1416.33800	1419.38499
1.250	-1.988	.02424	.02052	.02201	.02127	.28004	.27955	.27946	1416.84200	1419.39999
1.250	-1.984	.02400	.02040	.02179	.02109	.12916	.12925	.12911	1417.33600	1419.47000
1.250	.027	.01955	.01586	.01718	.01652	.02072	.01989	.02019	.02004	1417.90700
1.250	1.007	.01471	.01089	.01246	.01167	.16962	.16897	.16935	.16916	1418.66701
1.250	2.002	.01343	.00961	.01107	.01034	.31937	.31816	.31881	.31849	1417.63800
1.250	3.003	.01234	.01618	.01385	.01310	.46545	.46506	.46532	.46500	1419.52699
1.250	4.023	GRADIENT	-.00132	-.00135	-.00137	.15003	.14985	.14993	.14989	-.00009

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

## PARAMETRIC DATA

	RUN NO.	1107/ 0	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
4.032	-0.032	-.01094	-.01143	-.01072	-.01108	.45620	.45527	.45608	.45568	2035.40500
3.022	-0.022	-.01252	-.01314	-.01231	-.01272	.33910	.33784	.33818	.33801	2037.61099
1.999	-1.999	-.01675	-.01771	-.01681	-.01726	.22043	.21999	.21938	.21918	2038.68800
1.003	-1.003	-.01927	-.02035	-.01943	-.01989	.10441	.10424	.10441	.10433	2039.07401
1.010	-0.010	-.01857	-.01964	-.01864	-.01914	.00977	.01031	.01017	.01024	2039.20500
1.008	-1.008	-.01546	-.01673	-.01568	-.01620	.12584	.12680	.12670	.12675	2038.89799
2.016	-2.016	-.01182	-.01266	-.01182	-.01224	.24243	.24204	.24192	.24198	2040.15100
3.016	-3.016	-.00836	-.00883	-.00794	-.00838	.36077	.36058	.36060	.36059	2036.36900
4.033	-4.033	-.00686	-.00745	-.00658	-.00702	.48122	.48170	.48177	.48173	2033.51700
GRADIENT	-.00070	-.00070	-.00072	-.00071	-.00071	.11595	.11580	.11588	.11584	.20671

	RUN NO.	1114/ 0	RN/L =	3.75	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
4.024	-0.024	-.00602	-.00781	-.00673	-.00727	.64742	.64750	.64790	.64770	2012.04700
3.019	-0.019	-.01010	-.01223	-.01140	-.01181	.48144	.48095	.48124	.48109	2014.83400
1.997	-1.997	-.01602	-.01785	-.01678	-.01732	.31470	.31474	.31492	.31483	2016.31000
1.001	-1.001	-.01983	-.02093	-.02002	-.02047	.15084	.14919	.14931	.14925	2016.73399
1.016	-0.016	-.01833	-.01942	-.01853	-.01897	.01258	.01330	.01325	.01327	2016.83400
1.009	-1.009	-.01442	-.01529	-.01438	-.01484	.17798	.17901	.17897	.17899	2016.56799
2.016	-2.016	-.00631	-.00732	-.00734	-.00783	.34281	.34433	.34440	.34436	2015.97301
3.022	-3.022	-.00203	-.00426	-.00398	-.00412	.50861	.50992	.51022	.51007	2013.47200
4.020	-4.020	-.00205	-.00411	-.00398	-.00404	.67729	.67875	.67933	.67904	2009.99500
GRADIENT	-.00107	-.00105	-.00096	-.00096	-.00100	.16430	.16448	.16458	.16453	.21634

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM007) ( 04 OCT 91 )

## PARAMETRIC DATA

		PARAMETRIC DATA									
		RN/L =	3.89	GRADIENT INTERVAL = -5.00/ 5.00			ALPHA = .000			PHI = -90.000	
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	4.024	- .00681	- .00871	- .00775	- .00823	.69868	.69714	.69765	.69740	.9778 .09801	.984 .11000
.900	3.019	- .01205	- .01440	- .01365	- .01402	.52011	.51864	.51908	.51886	.1980 .83000	.1983 .62000
.900	1.997	- .01824	- .02079	- .01990	- .02034	.34148	.34037	.34064	.34050	.1982 .27100	.1983 .70000
.900	.996	- .02235	- .02462	- .02372	- .02417	.16257	.16206	.16221	.16213	.1982 .61800	.1984 .20000
.900	.017	- .01996	- .02199	- .02112	- .02156	.01424	.01402	.01398	.01402	.1983 .07401	.1984 .02000
.900	-1.009	- .01269	- .01482	- .01404	- .01443	.19224	.19203	.19214	.19208	.1982 .89301	.1984 .03000
.900	-2.027	- .00623	- .00845	- .00761	- .00803	.37305	.37329	.37335	.37332	.1982 .00500	.1984 .10001
.900	-3.018	- .00273	- .00503	- .00481	- .00492	.54776	.54745	.54768	.54757	.1979 .74400	.1984 .00999
.899	-4.023	- .00248	- .00437	- .00427	- .00432	.72755	.72738	.72763	.72750	.1975 .83099	.1984 .02000
GRADIENT		- .00130	- .00132	- .00123	- .00128	.17717	.17693	.17702	.17698	.20676	.02388
RN/L =	3.00	GRADIENT INTERVAL = -5.00/ 5.00									
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.100	4.020	.00658	.00412	.00473	.00443	.54675	.54594	.54605	.54600	.1441 .46700	.1445 .29100
1.100	2.996	- .00160	- .00076	- .00012	- .00044	.40366	.40295	.40362	.40328	.1443 .67200	.1445 .37100
1.100	1.984	- .00360	- .00579	- .00470	- .00525	.26253	.26202	.26301	.26277	.1444 .83600	.1445 .39799
1.100	.996	- .01074	- .01246	- .01112	- .01179	.12714	.12602	.12634	.12618	.1445 .18201	.1445 .38499
1.100	-.016	- .00622	- .00780	- .00638	- .00709	.01137	.01170	.01149	.01160	.1445 .26900	.1445 .52100
1.100	-1.001	- .00084	- .00229	- .00165	- .00197	.14606	.14628	.14619	.14623	.1444 .96300	.1445 .42200
1.099	-2.017	.00443	.00299	.00375	.00337	.28092	.28219	.28202	.28210	.1444 .23300	.1445 .35500
1.100	-3.025	.00545	.00314	.00363	.00338	.41817	.41866	.41864	.41865	.1442 .86099	.1445 .60500
1.099	-4.035	.00464	.00258	.00313	.00285	.56182	.56233	.56226	.56229	.1439 .85500	.1445 .38499
GRADIENT		- .00049	- .00055	- .00052	- .00053	.13705	.13701	.13706	.13704	.17085	.01709
RN/L =	3.00	GRADIENT INTERVAL = -5.00/ 5.00									
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.250	4.024	- .00629	- .00494	- .00561	- .00561	.58870	.58742	.58807	.58775	.1414 .56500	.1419 .72600
1.250	2.996	- .00783	- .01059	- .00916	- .00988	.43443	.43354	.43408	.43381	.1416 .80800	.1419 .67000
1.250	1.998	- .01314	- .01580	- .01449	- .01515	.28624	.28502	.28545	.28523	.1417 .26900	.1419 .60100
1.250	.993	- .01540	- .01826	- .01683	- .01754	.13421	.13401	.13447	.13424	.1417 .27901	.1419 .06300
1.250	-.018	- .01178	- .01447	- .01296	- .01372	.01379	.01386	.01353	.01370	.1418 .04201	.1419 .35001
1.250	-1.013	- .00552	- .00848	- .00701	- .00775	.16499	.16496	.16455	.16476	.1418 .63699	.1419 .70300
1.249	-2.031	- .00456	- .00388	- .00422	- .00422	.31540	.31542	.31537	.31540	.1417 .25900	.1419 .17500
1.250	-3.021	- .00173	- .00440	- .00411	- .00411	.46015	.46110	.46097	.46104	.1415 .27499	.1419 .56300
GRADIENT		- .00086	- .00082	- .00071	- .00071	.14903	.14891	.14898	.14895	.14412	.03592

I A 310 (AEDC 16TE-783) FLOW ANGULARITIES-FAIR OFF

(UCM008) ( 04 OCT 91 )

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 646  
(UCM009) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1124/ 0	RN/L =	3.89	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
.920	-.007	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	.02683	PTTF	PT2F
.920	4.032	-.01015	-.01644	-.01182	-.01413	.02791	.02657	.02670	1970.26700	1971.25000	
.920	GRADIENT	.70864	.70301	.70672	.70486	.02014	.01989	.01978	.01984	1969.50101	1970.96001
		.17795	.17811	.17789	.17800	-.00192	-.00165	-.00175	-.00170	-.18963	-.07179
MACH	ALPHA	RUN NO.	1129/ 0	RN/L =	3.88	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
.950	-.013	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	.02658	PTTF	PT2F
.950	4.038	-.01062	-.01624	-.01175	-.01400	.02783	.02627	.02642	1946.96100	1947.77000	
.950	GRADIENT	.71207	.70773	.71123	.70948	.02268	.02124	.02123	1946.67799	1948.17999	
		.17841	.17872	.17848	.17860	-.00127	-.00124	-.00132	-.00128	-.06985	.10122
MACH	ALPHA	RUN NO.	1135/ 0	RN/L =	3.86	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
.980	-.011	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	.02555	PTTF	PT2F
.980	4.047	-.00981	-.01596	-.01180	-.01388	.02611	.02504	.02529	1919.24500	1920.10001	
.980	GRADIENT	.71479	.70827	.71173	.71000	.01869	.01842	.01847	1918.66701	1919.80000	
		.17853	.17843	.17826	.17835	-.00183	-.00163	-.00173	-.00168	-.14240	-.07392
MACH	ALPHA	RUN NO.	1140/ 0	RN/L =	3.77	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
1.050	-.004	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	.02260	PTTF	PT2F
1.050	4.044	-.00807	-.03792	-.00751	-.02272	.02346	.02249	.02254	1840.25200	1841.76199	
1.050	GRADIENT	.69869	.67387	.69748	.68568	.02367	.02287	.02271	1839.88901	1841.69000	
		.17459	.17583	.17415	.17499	.00005	.00009	.00004	.00004	-.08967	-.01780
MACH	ALPHA	RUN NO.	1155/ 0	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
1.150	-.014	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	.01411	PTTF	PT2F
1.150	4.042	-.01169	-.01324	-.01230	-.01277	.01573	.01406	.01408	1434.26601	1434.98801	
1.150	GRADIENT	.56415	.56172	.56263	.56217	.01568	.01422	.01415	1434.85001	1435.74600	
		.14199	.14177	.14177	.14177	-.00001	-.00004	-.00002	-.00002	.14400	.18690

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 647

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCMO10) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1125/ 0 RN/L = 3.88 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.920	1.990	.02401	.01762	.01998	.37608	.37462	.37507	.37485	1969.31700	1971.06000
.920	-2.017	.03669	.02989	.03219	-.34165	-.34166	-.34159	1968.95300	1970.83000	
	GRADIENT	-.00316	-.00306	-.00305	.17910	.17874	.17882	.17878	.09084	.05740

RUN NO. 1130/ 0 RN/L = 3.88 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.950	1.943	.02283	.01640	.01856	.37043	.36978	.36996	.36987	1946.17700	1947.92000
.950	-2.024	.03679	.03027	.03257	-.34503	-.34593	-.34562	-.34577	1946.21400	1948.17000
	GRADIENT	-.00352	-.00357	-.00353	.18039	.18045	.18041	.18043	-.00933	-.06303

RUN NO. 1136/ 0 RN/L = 3.86 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.980	1.988	.02260	.01463	.01692	.37577	.37479	.37546	.37512	1918.44400	1919.81000
.980	-2.024	.03569	.02818	.03053	-.34390	-.34404	-.34355	-.34380	1918.25000	1920.28999
	GRADIENT	-.00326	-.00338	-.00340	.17936	.17915	.17920	.17917	.04835	-.11962

RUN NO. 1141/ 0 RN/L = 3.77 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.050	1.989	.01961	-.01052	.01840	.00394	.36575	.36518	.36529	1839.80299	1841.75200
1.050	-2.021	.03245	.00236	.03134	.01685	-.33567	-.33571	-.33590	1839.39301	1841.78600
	GRADIENT	-.00320	-.00321	-.00323	-.00322	.17491	.17483	.17485	.10224	-.00848

RUN NO. 1156/ 0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.150	1.992	.01198	.00950	.01012	.29397	.29365	.29406	.29386	1433.89400	1435.25000
1.150	-2.018	.02224	.01977	.02092	.02034	-.26855	-.26974	-.26976	.26975	1434.04401
	GRADIENT	-.00256	-.00256	-.00254	-.00255	.14029	.14051	.14062	-.03741	.06634

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 648

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM011) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1126/ 0	RN/L =	3.88	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
.920	-2.004 2.037 GRADIENT	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
		-.00652	-.01268	-.00783	-.01026	-.37290	-.37346	-.37335	-.37340	1968.77699	1970.86000
		-.01908	-.02532	-.02037	-.02285	.34793	.34695	.34749	.34722	1969.39900	1970.72000
		-.00311	-.00313	-.00310	-.00312	.17834	.17824	.17835	.17830	.15390	-.03464
.950	-2.001 2.043 GRADIENT	RUN NO.	1131/ 0	RN/L =	3.88	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
		DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
		-.00664	-.01222	-.00761	-.00991	-.37340	-.37391	-.37375	-.37383	1945.66200	1948.00999
		-.01926	-.02491	-.02054	-.02273	.35159	.35051	.35102	.35076	1946.32100	1947.95000
.980	-2.002 2.039 GRADIENT	RUN NO.	1137/ 0	RN/L =	3.86	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
		DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
		-.00389	-.01130	-.00654	-.00892	-.37124	-.37120	-.37087	-.37103	1917.75200	1919.98000
		-.01733	-.02476	-.02000	-.02238	.34980	.34956	.35034	.34995	1918.48801	1919.89000
1.050	-2.002 2.037 GRADIENT	RUN NO.	1142/ 0	RN/L =	3.77	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
		DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
		-.00292	-.03238	-.00390	-.01814	-.36012	-.35970	-.35999	-.35984	1839.28500	1842.10100
		-.01565	-.04515	-.01585	-.03050	.34270	.34227	.34247	.34237	1839.70399	1841.75800
1.150	-2.009 2.023 GRADIENT	RUN NO.	1157/ 0	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
		DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
		-.00163	-.00325	-.00295	-.00310	-.28892	-.29024	-.29025	-.29024	1433.75800	1435.60899
		-.01219	-.01369	-.01239	-.01304	.27358	.27305	.27333	.27319	1434.14400	1435.09700

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 649  
 IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF  
 (UCMO12) ( 04 OCT 91 )

MACH	BETA	GRADIENT	RUN NO.	1132/ 0	RN/L =	3.88	GRADIENT INTERVAL	= -5.00/ 5.00	ALPHA	= .000	PHI	= -90.000
			DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
.950	-2.000	.00619	-.01194	-.00727	-.00960	-.32555	-.37293	-.37286	-.37290	1945.81000	1947.86000	
.950	2.038	.02026	-.02597	-.02129	-.02363	.35140	.35042	.35078	.35060	1946.25301	1947.75000	
.950	.00348	-.00347	-.00347	-.00347	-.00347	.17927	.17912	.17919	.17915	.10970	.02724	

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

MACH	ALPHA	GRADIENT	RUN NO.	1221/ 0	RN/L =	2.50	GRADIENT INTERVAL	= -5.00/ 5.00	BETA	= .000	PHI	= .000
			DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
.899	-8.002	-.90057	-.90240	-.90055	-.90148	-.02394	-.02229	-.02181	-.02205	1237.86700	1273.00000	
.900	-6.995	-.78423	-.78555	-.78375	-.78465	-.02278	-.02121	-.02076	-.02098	1246.44800	1273.14000	
.900	-5.993	-.67112	-.67306	-.67081	-.67194	-.01881	-.01741	-.01688	-.01715	1253.61200	1273.17000	
.900	-4.991	-.55789	-.56084	-.55843	-.55964	-.01424	-.01352	-.01316	-.01334	1259.57201	1273.02000	
.900	-3.993	-.44051	-.44286	-.44045	-.44166	-.01227	-.01171	-.01131	-.01151	1264.32100	1273.14999	
.900	-2.991	-.32500	-.32696	-.32451	-.32573	-.01308	-.01220	-.01169	-.01195	1267.80000	1272.89000	
.900	-1.995	-.20839	-.21016	-.20775	-.20895	-.01661	-.01540	-.01529	-.01535	1270.28400	1273.11000	
.900	-.992	-.09804	-.09894	-.09636	-.09765	-.01784	-.01650	-.01624	-.01637	1271.52299	1272.97000	
.900	.021	.00861	.00505	.00895	.00700	-.01630	-.01461	-.01449	-.01455	1271.87199	1272.92999	
.900	1.007	-.11914	.11595	.11843	.11719	-.01269	-.01138	-.01129	-.01133	1271.83701	1272.87000	
.900	2.009	.23557	.23205	.23079	.23142	-.00967	-.00813	-.00816	-.00815	1271.91701	1272.88000	
.900	3.012	.34976	.34655	.32321	.33488	-.00867	-.00765	-.00758	-.00762	1272.13800	1273.10001	
.900	4.010	.46642	.46300	.45256	.45778	-.00992	-.00886	-.00883	-.00885	1271.68100	1272.99001	
.900	5.008	.58038	.57819	.57412	.57005	-.00998	-.00875	-.00866	-.00871	1270.48000	1273.00000	
.900	6.007	.69432	.68588	.68915	.68588	-.00959	-.00749	-.00743	-.00746	1268.27699	1272.89999	
.900	7.006	.80726	.80451	.79974	.80213	-.00948	-.00732	-.00747	-.00740	1264.63301	1273.25000	
.900	7.999	.91261	.91899	.91580	.91184	-.01022	-.00780	-.00797	-.00789	1259.65700	1273.38000	
.900	GRADIENT	.11294	.11279	.11090	.11184	.00057	.00063	.00058	.00061	1.14683	-.00867	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 650  
(UCM013) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1165/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	- .98720	-.98792	-.98692	-.98742	-.01691	-.01736	-.01692	-.01714	1146 .06300	1182 .67599
-7.994	- .85992	-.86124	-.86007	-.86066	-.01550	-.01659	-.01609	-.01634	1154 .12801	1182 .52000
-6.987	- .73585	-.73723	-.73608	-.73665	-.01271	-.01371	-.01337	-.01354	1161 .35201	1182 .36400
-5.992	- .61286	-.61365	-.61256	-.61311	-.00897	-.00965	-.00930	-.00948	1167 .62399	1182 .41600
-4.992	- .48248	-.48413	-.48290	-.48351	-.00664	-.00785	-.00768	-.00777	1172 .80000	1182 .53000
-3.996	- .35445	-.35620	-.35496	-.35558	-.00876	-.00919	-.00898	-.00908	1177 .17799	1182 .35500
-2.995	- .22786	-.22905	-.22771	-.22838	-.01110	-.01183	-.01170	-.01176	1179 .11099	1182 .36099
-1.995	- .10414	-.10588	-.10472	-.10530	-.01298	-.01329	-.01312	-.01320	1180 .28400	1182 .42700
-1.250	.024	.01541	.01295	.01416	.01355	.01145	.01156	.01156	.01156	.01156
1.010	.1250	.13772	.13559	.13671	.13615	.00914	.00924	.00922	.00923	.00923
1.250	2.004	.26115	.25844	.25990	.25917	.00662	.00725	.00741	.00733	.00733
1.250	3.014	.38736	.38463	.38558	.38510	.00622	.00702	.00705	.00703	.00703
1.250	4.011	.51669	.51457	.51564	.51511	.00752	.00793	.00810	.00802	.00802
1.250	5.023	.64320	.64133	.64240	.64186	.00551	.00586	.00611	.00599	.00599
1.249	6.004	.77256	.76980	.77099	.77039	.00375	.00416	.00438	.00427	.00427
1.249	7.008	.89497	.89341	.89382	.89361	.00448	.00470	.00489	.00480	.00480
1.249	8.005	1.01389	1.01202	1.01302	1.01252	.00430	.00422	.00434	.00428	.00428
GRADIENT	.12445	.12428	.12427	.12428	.12428	.00021	.00024	.00019	.00022	.00022

	RN/L =	1185/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.13759	-.1.13994	-1.13811	-1.13903	-.02079	-.02244	-.02190	-.02217	1128 .02100	1165 .35600
-8.002	-6.991	-.99442	-.99954	-.99780	-.01737	-.01899	-.01838	-.01869	1137 .72600	1165 .30099
-6.991	-5.996	-.85238	-.85699	-.85509	-.01479	-.01460	-.01390	-.01425	1145 .02699	1165 .09599
-5.000	-5.000	-.70610	-.71171	-.70919	-.01194	-.01159	-.01101	-.01130	1150 .60699	1165 .32001
-3.994	-2.994	-.55637	-.55973	-.55784	-.01001	-.00936	-.00882	-.00909	1155 .51401	1165 .34200
-1.400	-1.993	-.41023	-.41309	-.41088	-.01134	-.01066	-.01035	-.01050	1159 .53999	1164 .87601
1.400	- .995	-.26399	-.26931	-.26737	-.01400	-.01411	-.01347	-.01379	1161 .87199	1165 .34900
1.400	0.24	.01772	.01156	.01250	-.12717	-.12611	-.01406	-.01394	1162 .99899	1165 .03101
1.400	1.005	.15412	.14930	.15169	.15049	-.00919	-.00914	-.01136	-.01145	1164 .94099
1.400	2.006	.29519	.29110	.29336	.29223	-.00930	-.00812	-.00789	-.00800	1163 .62199
1.400	3.021	.44223	.43747	.43936	.43841	-.01012	-.00880	-.00869	-.00875	1163 .93700
1.400	4.018	.59793	.59224	.59436	.59330	-.00974	-.00860	-.00856	-.00858	1164 .27600
1.400	5.009	.74165	.73564	.73789	.73676	-.00734	-.00620	-.00634	-.00627	1163 .13200
1.400	6.017	.88415	.87965	.88235	.88100	-.00551	-.00586	-.00586	-.00705	1161 .34300
1.400	7.009	1.02625	1.02287	1.02389	1.02491	-.00621	-.00482	-.00500	-.00491	1158 .86900
8.011	1.399	1.16100	1.15701	1.15863	1.15782	-.00391	-.00432	-.00037	-.00491	1153 .81599
GRADIENT	.14260	.14239	.14241	.14240	.14240	.00043	.00032	.00040	.00040	.000305

GRADIENT		INTERVAL = -5.00/ 5.00		PT2F	
RUN NO.	1203/ 0	RN/L =	2.49	RN/L =	2.49
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL
1.450	-1.19464	-1.19612	-1.19458	-1.19535	-0.3996
-8.005	-1.03989	-1.04287	-1.04128	-1.04208	-0.3970
-7.000	-0.88825	-0.89177	-0.89056	-0.89117	-0.4055
-6.005	-0.74732	-0.75008	-0.74820	-0.74914	-0.3513
-5.000	-0.58754	-0.59085	-0.58885	-0.58985	-0.3377
-3.999	-0.43797	-0.43914	-0.43727	-0.43821	-0.2756
-3.000	-0.28905	-0.29183	-0.28960	-0.29072	-0.2607
-2.006	-0.13277	-0.13553	-0.13345	-0.13449	-0.2541
-1.002	-0.01391	-0.01698	-0.01597	-0.01494	-0.2535
1.450	0.003	0.006	0.006	0.006	-0.03927
1.450	1.006	1.0246	1.0246	1.0246	-0.03867
1.450	2.001	3.1681	3.1572	3.1769	-0.03894
1.450	2.996	4.002	4.449	4.449	-0.03352
1.450	4.994	7.8570	7.8383	7.8567	-0.02819
1.450	6.001	9.3348	9.3337	9.3526	-0.02870
1.450	6.988	1.08475	1.08642	1.08559	-0.02756
1.449	7.995	1.22820	1.22598	1.22827	-0.02564
GRADIENT	.15280	.15284	.15284	.15284	-0.02552
RUN NO.	1276/ 0	RN/L =	2.50	GRADIENT	INTERVAL = -5.00/ 5.00
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL
1.474	-8.000	-1.27259	-1.27215	-1.27170	-0.3564
1.473	-6.979	-1.11513	-1.11346	-1.11275	-0.3425
1.474	-5.995	-0.95663	-0.95593	-0.95521	-0.3016
1.474	-4.995	-0.79316	-0.79355	-0.79248	-0.2497
1.474	-3.994	-0.62254	-0.62236	-0.62048	-0.2061
1.474	-2.994	-0.45348	-0.45515	-0.45267	-0.2468
1.474	-1.979	-0.29320	-0.29324	-0.29180	-0.2468
1.474	-0.991	-0.13961	-0.13853	-0.13687	-0.2058
1.473	0.014	0.16223	0.16223	0.16333	-0.2044
1.473	1.011	1.17357	1.17287	1.17509	-0.2044
1.473	2.005	3.30005	3.29993	3.3150	-0.2044
1.474	3.010	4.49123	4.48985	4.49150	-0.2044
1.474	4.022	6.55522	6.55581	6.57335	-0.2044
1.473	5.008	8.2023	8.2107	8.2119	-0.2044
1.473	6.004	9.8055	9.8140	9.8115	-0.2044
1.473	7.012	1.13805	1.13617	1.13743	-0.2044
1.473	8.008	1.28395	1.28537	1.28466	-0.2044
GRADIENT	.15922	.15922	.15922	.15922	-0.00556
RUN NO.	1203/ 0	RN/L =	2.49	GRADIENT	INTERVAL = -5.00/ 5.00
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL
1.450	-1.19464	-1.19612	-1.19458	-1.19535	-0.3996
-8.005	-1.03989	-1.04287	-1.04128	-1.04208	-0.3970
-7.000	-0.88825	-0.89177	-0.89056	-0.89117	-0.4055
-6.005	-0.74732	-0.75008	-0.74820	-0.74914	-0.3513
-5.000	-0.58754	-0.59085	-0.58885	-0.58985	-0.3377
-3.999	-0.43797	-0.43914	-0.43727	-0.43821	-0.2756
-3.000	-0.28905	-0.29183	-0.28960	-0.29072	-0.2607
-2.006	-0.13277	-0.13553	-0.13345	-0.13449	-0.2541
-1.002	-0.01391	-0.01698	-0.01597	-0.01494	-0.2535
1.450	0.003	0.006	0.006	0.006	-0.03927
1.450	1.006	1.0246	1.0246	1.0246	-0.03867
1.450	2.001	3.1681	3.1572	3.1769	-0.03894
1.450	2.996	4.002	4.449	4.449	-0.03352
1.450	4.994	7.8570	7.8383	7.8567	-0.02819
1.450	6.001	9.3348	9.3337	9.3526	-0.02870
1.450	6.988	1.08475	1.08642	1.08559	-0.02756
1.449	7.995	1.22820	1.22598	1.22827	-0.02564
GRADIENT	.15280	.15284	.15284	.15284	-0.02552
RUN NO.	1276/ 0	RN/L =	2.50	GRADIENT	INTERVAL = -5.00/ 5.00
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL
1.474	-8.000	-1.27259	-1.27215	-1.27170	-0.3564
1.473	-6.979	-1.11513	-1.11346	-1.11275	-0.3425
1.474	-5.995	-0.95663	-0.95593	-0.95521	-0.3016
1.474	-4.995	-0.79316	-0.79355	-0.79248	-0.2497
1.474	-3.994	-0.62254	-0.62236	-0.62048	-0.2061
1.474	-2.994	-0.45348	-0.45515	-0.45267	-0.2468
1.474	-1.979	-0.29320	-0.29324	-0.29180	-0.2468
1.474	-0.991	-0.13961	-0.13853	-0.13687	-0.2058
1.473	0.014	0.16223	0.16223	0.16333	-0.2044
1.473	1.011	1.17357	1.17287	1.17509	-0.2044
1.473	2.005	3.30005	3.29993	3.3150	-0.2044
1.474	3.010	4.49123	4.48985	4.49150	-0.2044
1.474	4.022	6.55522	6.55581	6.57335	-0.2044
1.473	5.008	8.2023	8.2107	8.2119	-0.2044
1.473	6.004	9.8055	9.8140	9.8115	-0.2044
1.473	7.012	1.13805	1.13617	1.13743	-0.2044
1.473	8.008	1.28395	1.28537	1.28466	-0.2044
GRADIENT	.15937	.15922	.15922	.15922	-0.00556

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 652

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM013) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1238/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.495	-7.999	-1.31495	-1.31670	-1.31567	-1.31618	-0.26753	-0.2604	-.02629	1110.99500	1143.79764
1.495	-6.988	-1.15966	-1.16023	-1.15897	-1.15960	-0.2672	-0.2678	-.02634	1119.75400	1144.06808
1.495	-5.993	-1.00336	-1.00477	-1.00344	-1.00410	-0.2210	-0.2218	-.02201	1128.27100	1144.99582
1.495	-4.993	-84074	-83996	-83862	-83929	-0.1990	-0.1993	-.01970	1135.15199	1146.22029
1.495	-3.987	-66650	-66677	-66505	-66591	-0.1901	-0.1916	-.01882	1138.79700	1146.77905
1.495	-2.993	-50110	-50029	-49873	-49951	-0.2265	-0.2236	-.02236	1142.91200	1147.46426
1.495	-1.994	-33042	-33035	-32876	-32956	-0.2464	-0.2424	-.02403	1145.69701	1147.36450
1.495	- .998	-15401	-15381	-15211	-15296	-0.2583	-0.2536	-.02522	1144.29601	1145.42557
1.495	.015	01836	01685	01869	01777	-0.2208	-0.2168	-.02184	1142.51100	1143.79080
1.496	1.008	18881	18848	18902	18930	-0.1833	-0.1792	-.01779	1145.02800	1147.01122
1.496	2.005	35349	35293	35362	35327	-0.1973	-0.1894	-.01895	1145.81700	1145.83060
1.496	3.010	51541	51385	51546	51465	-0.1810	-0.1781	-.01783	1145.91800	1144.39839
1.496	4.011	68946	68934	69090	69012	-0.1556	-0.1509	-.01519	1146.98900	1145.49629
1.496	5.007	85942	85822	85987	85905	-0.1130	-0.1039	-.01055	1149.08900	1147.86382
1.496	6.015	1.02698	1.02629	1.02782	1.02705	-0.0872	-0.0794	-.00838	1150.23700	1148.31958
1.496	7.007	1.18297	1.18305	1.18440	1.18373	-0.0790	-0.0745	-.00767	1148.77901	1147.74919
1.496	8.008	1.32128	1.32045	1.32186	1.32115	-0.0357	-0.0259	-.00291	1144.47501	1147.04655
GRADIENT	.16996	.16980	.16978	.16978	.16979	.00050	.00056	.00053	.00053	-.20646
	RUN NO.	1283/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.520	-7.999	-1.61262	-1.61184	-1.61097	-1.61140	-.03219	-.03270	-.03198	-.03234	1127.10100
1.520	-6.993	-1.38972	-1.38952	-1.38864	-1.38908	-.03532	-.03535	-.03476	-.03505	1132.24400
1.520	-5.993	-1.11963	-1.11887	-1.11765	-1.11826	-.03105	-.03040	-.03020	1136.44701	1141.97092
1.520	-4.999	-88558	-88534	-88447	-88491	-.03417	-.03363	-.03338	1141.52000	1144.86359
1.520	-3.982	-64504	-64442	-64296	-64369	-.03554	-.03484	-.03443	1139.26199	1141.49124
1.520	-2.994	-4.1048	-4.0820	-4.0659	-4.0740	-.02921	-.02833	-.02808	1140.75600	1142.95647
1.520	-1.995	-1.9931	-1.9967	-1.9788	-1.9824	-.01847	-.01846	-.01846	1143.37000	1145.34476
1.520	- .986	-0.88851	-0.8720	-0.8552	-0.8636	-.01399	-.01452	-.01434	1144.93201	1145.67206
1.520	.014	01376	01385	01562	01473	-.01500	-.01498	-.01499	1143.82001	1143.38771
1.520	1.011	1.1514	1.1439	1.1614	1.1526	-.00640	-.00694	-.00692	1141.81000	1141.80496
1.520	2.005	2.005	2.6993	.27084	.27016	-.00973	-.00900	-.00894	1143.68800	1146.15042
1.520	3.005	50431	50264	.50431	.50348	-.01916	-.01788	-.01798	1143.16299	1143.99481
1.520	4.006	72708	72516	.72696	.72606	-.02010	-.01900	-.01915	1140.37100	1141.49786
1.520	5.018	97444	97552	.97683	.97617	-.02355	-.02218	-.02255	1141.43201	1144.92365
1.520	6.004	1.21291	1.21185	1.21330	1.21258	-.02652	-.02488	-.02539	1142.78900	1143.75960
1.520	7.006	1.40525	1.40429	1.40546	1.40487	-.02085	-.01969	-.02024	1143.77299	1142.99352
1.520	7.997	1.59136	1.58950	1.59143	1.59046	-.00920	-.00814	-.00857	1145.66100	1142.48862
GRADIENT	.16371	.16340	.16345	.16342	.00226	.00231	.00228	.00228	.00226	-.04098

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 653  
(UCM013) ( 04 OCT 91 )

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

## PARAMETRIC DATA

	RUN NO.	1251/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-8.002	-1.41806	-1.41886	-1.41776	-1.41831	-0.3521	-0.3451	-0.3413	-1117.41499	1138.40051
1.543	-7.003	-1.21353	-1.21259	-1.21141	-1.21200	-0.3092	-0.3025	-0.2987	-0.3006	1120.06200
1.543	-5.992	-1.01623	-1.01644	-1.01516	-1.01580	-0.2162	-0.2053	-0.2027	-0.2040	1120.60899
1.544	-4.982	-8.1783	-8.1628	-8.1482	-8.1555	-0.1822	-0.1801	-0.1781	-0.1791	1125.49800
1.544	-3.992	-5.9628	-5.9539	-5.9385	-5.9462	-0.1058	-0.0948	-0.0944	-0.0946	1127.85600
1.544	-2.993	-4.1363	-4.1306	-4.1135	-4.1221	-0.0958	-0.0984	-0.0976	-0.0980	1129.77299
1.544	-1.988	-2.4733	-2.4685	-2.4524	-2.4604	-0.1970	-0.1794	-0.1801	-0.1797	1129.10800
1.544	-0.990	-10.121	-0.9928	-0.9768	-0.9848	-0.2321	-0.2161	-0.2167	-0.2164	1125.75900
1.544	.015	.01660	.01617	.01797	.01707	-0.2160	-0.2035	-0.2063	-0.2049	1122.66400
1.544	1.01	13.128	13.078	13.249	13.164	-0.1499	-0.1346	-0.1353	-0.1349	1125.86501
1.543	2.01	2.6799	2.6767	2.6927	2.6847	-0.0806	-0.0802	-0.0816	-0.0809	1126.10699
1.543	3.010	4.24442	4.2411	4.2606	4.2509	.00052	.00077	.00047	.00062	1125.98199
1.543	4.006	6.2843	6.2858	6.3019	6.2939	.00244	.00397	.00361	.00379	1124.82600
1.543	5.012	.85216	.85123	.85209	.85295	.00408	.00523	.00549	.00536	1124.81300
1.543	6.009	1.04800	1.04829	1.04897	1.04863	.00466	.00290	.00321	.00306	1128.01500
1.543	7.005	1.24109	1.24072	1.24281	1.24176	.01462	.01273	.01322	.01298	1128.17900
1.544	8.012	1.46977	1.47042	1.47197	1.47120	.02692	.02495	.02550	.02522	1129.16299
1.543	GRADIENT	.15050	.15032	.15034	.15033	.00174	.00172	.00175	-.30560	-.25719

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM014) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.899	-8.003	-.89827	-.90069	-.89917	-.89993	-.02119	-.01982	-.01934	1236.94901	1273.77000
.900	-6.980	-.78388	-.78518	-.78370	-.78444	-.02104	-.01958	-.01910	1246.09300	1274.12000
.900	-5.993	-.67026	-.67247	-.67064	-.67156	-.01624	-.01573	-.01534	1254.23900	1274.53999
.900	-4.992	-.55790	-.56052	-.55869	-.55960	-.01289	-.01224	-.01189	1261.03101	1275.46001
.900	-3.988	-.43971	-.44133	-.43948	-.44041	-.01197	-.01072	-.01047	1264.86700	1271.70000
.900	-2.991	-.32332	-.32431	-.32247	-.32339	-.01115	-.01054	-.01019	1264.66299	1271.16000
.900	-1.995	-.20821	-.20863	-.20682	-.20773	-.01542	-.01392	-.01374	1270.56799	1273.58000
.900	- .997	-.09695	-.09639	-.09475	-.09557	-.01641	-.01498	-.01478	1272.38499	1273.96001
.900	-.015	.00801	.00746	.00959	.00853	-.01565	-.01412	-.01402	1271.91901	1272.87000
.900	1.007	.11936	.11767	.11960	.11864	-.01285	-.0114	-.01116	1271.30800	1272.28000
.900	2.004	.23364	.23310	.23481	.23396	-.00930	-.00776	-.00769	1271.54601	1272.83000
.900	3.006	.34860	.34825	.34929	.34877	-.00696	-.00579	-.00590	1272.11099	1273.28999
.900	4.010	.46588	.46464	.46652	.46558	-.00839	-.00721	-.00704	1272.19099	1273.92000
.900	5.008	.57817	.57957	.58137	.58047	-.00923	-.00774	-.00771	1271.40900	1274.20000
.900	6.001	.69261	.69411	.69527	.69469	-.00747	-.00606	-.00616	1269.46500	1274.33000
.900	7.005	.80563	.80704	.80872	.80788	-.00843	-.00610	-.00608	1264.92400	1272.75000
.900	8.009	.91227	.91430	.91589	.91510	-.00851	-.00641	-.00666	1258.28700	1271.36000
	GRADIENT	.11278	.11289	.11286	.11287	.00057	.00062	.00059	.00060	.000371
	RUN NO.	1268/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.250	-7.999	-.98590	-.98772	-.98637	-.98704	-.01904	-.01903	-.01865	1145.15601	1182.32100
1.250	-6.982	-.85950	-.86050	-.85916	-.85983	-.01742	-.01763	-.01701	1154.18900	1182.81000
1.250	-5.996	-.73626	-.73670	-.73522	-.73596	-.01383	-.01379	-.01342	1160.74100	1182.42700
1.250	-4.981	-.61241	-.61290	-.61134	-.61212	-.01216	-.01001	-.00967	1167.63400	1182.68300
1.250	-3.991	-.48451	-.48341	-.48183	-.48262	-.00982	-.00785	-.00767	1171.97301	1182.34500
1.250	-2.990	-.35565	-.35420	-.35589	-.35504	-.01131	-.00953	-.00924	1176.47000	1182.60800
1.250	-1.990	-.22913	-.22948	-.22767	-.22858	-.01420	-.01227	-.01221	1178.57001	1182.84500
1.250	- .996	-.10497	-.10482	-.10304	-.10393	-.01590	-.01366	-.01357	1161.1179.56300	1182.62199
1.250	0.14	.01412	.01306	.01500	.01403	-.01154	-.01154	-.01157	.01155	.01401
1.250	1.010	.13677	.13575	.13755	.13665	-.01082	-.00858	-.00855	.00856	.00851
1.250	2.008	.26020	.26086	.26241	.26163	-.00847	-.00639	-.00657	.00648	.00640
1.250	3.025	.38709	.38591	.38769	.38680	-.00858	-.00613	-.00640	.00626	.00600
1.250	4.011	.51472	.51367	.51558	.51462	-.00872	-.00637	-.00655	.00646	.00620
1.250	5.017	.64097	.64066	.64249	.64158	-.00571	-.00464	-.00485	.00475	.00450
1.250	6.009	.77132	.77128	.77310	.77219	-.00362	-.00294	-.00321	.00308	.00280
1.250	7.007	.89349	.89387	.89612	.89499	-.00467	-.00361	-.00389	.00372	.00350
1.250	8.004	1.01152	1.01244	1.01331	1.01418	-.00386	-.00272	-.00289	.00281	.00260
	GRADIENT	.12447	.12435	.12437	.12436	.00040	.00045	.00038	.00042	.000373
	RUN NO.	1264/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM014) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1258/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000	PTTF
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	PT2F
ALPHA	-1.13259	-1.13318	-1.13199	-1.13259	-1.01752	-0.01682	-0.01626	-0.01654	-1.127	1.127	8.4801
1.400	-7.996	-6.985	-6.99164	-7.99259	-0.01356	-0.01346	-0.01303	-0.01325	1.135	1.135	8.5899
1.400	-5.990	-5.9912	-8.5242	-8.5111	-0.00953	-0.00931	-0.00875	-0.00903	1.143	1.143	9.8399
1.400	-4.989	-7.076	-7.0721	-7.0578	-0.00764	-0.00723	-0.00668	-0.00695	1.149	1.149	15.900
1.400	-3.988	-5.5746	-5.5752	-5.5595	-0.00765	-0.00548	-0.00528	-0.00538	1.154	1.154	0.4900
1.400	-2.988	-4.1207	-4.1110	-4.0953	-0.01004	-0.00822	-0.00782	-0.00802	1.158	1.158	2.4001
1.400	-1.988	-2.6713	-2.6716	-2.6555	-0.01459	-0.01202	-0.01174	-0.01188	1.160	1.160	4.4000
1.400	-1.399	-1.2466	-1.2300	-1.2383	-0.01492	-0.01229	-0.01260	-0.01279	1.161	1.161	4.4400
1.400	.018	.01230	.01127	.01320	.01224	.01229	.01017	.00995	.01006	.01006	1.163
1.400	1.004	1.5141	1.5080	1.527	.015178	.00963	.00734	.00720	.00727	.00727	1.163
1.400	2.005	2.9298	2.9209	2.9387	.29298	.00891	.00650	.00638	.00644	.00644	1.162
1.400	3.005	4.3584	4.3481	4.3638	.43560	.00960	.00723	.00720	.00721	.00721	1.161
1.400	4.023	5.9015	5.8992	5.9172	.59082	.00831	.00703	.00704	.00704	.00704	1.162
1.400	5.009	7.3295	7.3252	7.3445	.73448	.00588	.00502	.00517	.00510	.00510	1.162
1.400	6.011	8.7546	8.7544	8.7775	.87659	.00625	.00553	.00556	.00554	.00554	1.160
1.400	7.013	1.01731	1.01788	1.01959	1.01874	.00837	.00725	.00730	.00728	.00728	1.164
1.400	8.005	1.15029	1.15057	1.15203	1.15130	.00783	.00535	.00569	.00552	.00552	1.164
1.400	GRADIENT	.14270	.14257	.14261	.14259	.00002	.00009	.00004	.00007	.00007	.00731
	RUN NO.	1226/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	PTTF
ALPHA	-1.18881	-1.19044	-1.18890	-1.18967	-0.03844	-0.03945	-0.03865	-0.03753	-0.03789	-0.03905	1.117
1.450	-8.000	-6.989	-1.03391	-1.03720	-1.03573	-1.03646	-1.03725	-1.03179	-1.03137	-1.03151	1.125
1.451	-5.994	-4.994	-8.8846	-8.89190	-8.89076	-8.9133	-8.9133	-8.03166	-8.02784	-8.02801	1.132
1.450	-4.994	-3.994	-7.42229	-7.4579	-7.4405	-7.4492	-7.4492	-8.02819	-8.02653	-8.02631	1.139
1.450	-2.994	-2.994	-5.87333	-5.8939	-5.8750	-5.8845	-5.8845	-8.02762	-8.02655	-8.02610	1.144
1.450	-1.995	-1.995	-4.3942	-4.4066	-4.3881	-4.3974	-4.3974	-8.02799	-8.02629	-8.02642	1.148
1.450	-1.450	-1.450	-2.8769	-2.9049	-2.8859	-2.8954	-2.8954	-8.02864	-8.02724	-8.02712	1.154
1.450	-0.986	-0.986	-1.3201	-1.3473	-1.3286	-1.3380	-1.3380	-8.02852	-8.02680	-8.02653	1.155
1.450	-0.24	-0.1692	-0.1254	-0.1455	-0.1354	-0.12177	-0.12177	-8.02019	-8.01998	-8.02009	1.159
1.450	1.006	1.6850	1.6745	1.6997	1.6871	-0.1694	-0.1694	-8.01496	-8.01503	-8.01499	1.159
1.450	2.010	3.1525	3.1445	3.1634	3.1540	-0.1390	-0.1390	-8.01240	-8.01230	-8.01235	1.154
1.450	3.011	4.6847	4.6628	4.6814	4.6721	-0.1506	-0.1506	-8.01329	-8.01329	-8.01332	1.155
1.450	4.012	6.3093	6.2852	6.3024	6.2938	-0.1550	-0.1550	-8.01363	-8.01352	-8.01358	1.155
1.451	5.009	7.8232	7.7948	7.8119	7.8033	-0.1122	-0.1122	-8.00937	-8.00943	-8.00940	1.157
1.450	6.011	9.3223	9.3289	9.3289	9.3208	-0.0900	-0.0900	-8.00908	-8.00920	-8.00914	1.153
1.450	7.008	1.08304	1.08192	1.08375	1.08284	-0.1260	-0.1260	-8.01237	-8.01256	-8.01246	1.152
1.450	8.004	1.22638	1.22517	1.22721	1.22619	-0.0559	-0.0559	-8.00603	-8.00581	-8.00581	1.158
1.450	GRADIENT	.15165	.15174	.15175	.15174	.00196	.00196	.00200	.00202	.00202	.01860

PARAMETRIC DATA



PARAMETRIC DATA

RUN NO. 1241 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.0

	GRADIENT	MACH	ALPHA	DPCAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
7.991	1.495	1.32186	1.32236	1.322330	1.32282	1.32282	1.32282	0.3575	0.3516	0.3494	1147.774	1147.774	
6.990	1.496	1.16057	1.16052	1.16168	1.16110	1.16110	1.16110	0.3364	0.3295	0.3280	1143.51300	1144.20224	
5.991	1.495	1.00442	1.00509	1.00381	1.00445	1.00445	1.00445	0.2901	0.2828	0.2808	1143.68600	1143.929	
4.991	1.496	8.3563	8.3549	8.3691	8.3620	8.3620	8.3620	0.2356	0.2339	0.2339	1146.32300	1146.886	
3.990	1.496	6.5628	6.5638	6.5787	6.5713	6.5713	6.5713	0.2202	0.2146	0.2141	1146.30099	1147.267	
2.996	1.495	4.9130	4.8985	4.9132	4.9059	4.9059	4.9059	0.2390	0.2272	0.2265	1145.79300	1146.584	
1.987	1.496	3.2269	3.2287	3.22437	3.22362	3.22362	3.22362	0.2576	0.2487	0.2486	1146.03500	1146.255	
.996	1.495	1.5010	1.4915	1.5080	1.4997	1.4997	1.4997	0.2662	0.2557	0.2556	1145.15199	1145.973	
.023	1.495	-	0.2225	-	0.2052	-	0.2052	-	0.2127	-	0.2138	1143.99600	1145.774
-1.011	1.495	-	1.9266	-	1.9244	-	1.9074	-	1.9159	-	0.1864	1143.24300	1145.120
-2.012	1.495	-	3.6038	-	3.5922	-	3.5775	-	3.5848	-	0.1594	1142.42300	1145.102
-3.012	1.496	-	5.2538	-	5.2473	-	5.2329	-	5.2401	-	0.1488	1141.99300	1144.779
-4.013	1.495	-	6.9848	-	6.9775	-	6.9632	-	6.9703	-	0.1325	1139.88600	1145.204
-5.009	1.495	-	86141	-	86022	-	85899	-	85961	-	0.0917	1133.63699	1144.154
-6.011	1.496	-	1.02292	-	1.02407	-	1.02287	-	1.02347	-	0.0822	1130.70700	1146.345
-7.002	1.496	-	1.17940	-	1.17898	-	1.17789	-	1.17843	-	0.0839	1122.40800	1146.588
-8.009	1.496	-	1.32211	-	1.32259	-	1.32159	-	1.32209	-	0.0240	1115.39200	1147.321
			0.00000	-	0.00000	-	0.00000	-	0.00000	-	0.00000	0.00000	0.00000

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM015) ( 04 OCT 91 )

ANEMETRIC DATA

PARAMETRIC DATA

GRADIENT INTERVAL = -5 00/-5 00

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAPERS ON DATA

TABLE III. GRADIENT INTERVALS

	GRADIENT	DPB1	DPB2	PTTF	PT2F
ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB
.2249	.98687	.98807	.98974	.98891	.02341
.2250	.86270	.86277	.86460	.86369	.02306
.984					.02175
.2250	.73928	.73888	.74069	.73979	.02168
.994					.01922
.2250	.61614	.61606	.61777	.61692	.01817
.989					.01437
.2250	.48651	.48542	.48717	.48629	.01135
.988					.01056
.2250	.35946	.35925	.36038	.35981	.01126
.993					.01167
.2249	.23163	.23122	.23293	.23208	.01221
.993					.01218
.2250	.994	.10576	.10464	.10553	.01343
.2250					.01352
.015		.01312	.01141	.0116	.01442
.007		.13432	.13460	.13380	.01460
.2249		.25765	.25839	.25660	.01451
.017		.382239	.38215	.38043	.01451
.008		.511137	.511169	.50996	.01451
.009		.63758	.63866	.63704	.01451
.006		.76641	.76732	.7662	.01451
.009		.88859	.89021	.88932	.01451
.017		.1.00932	.1.01193	.1.01052	.01451
GRADIENT	.00000	.00000	.00000	.00000	.00000

## PARAMETRIC DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM016) ( 04 OCT 91 )

HISTORICAL METRIC DATA

	RUN NO.	1223/ O	RN/L =	2 . 50	GRADIENT INTERVAL =	- 5 . 00 /	5 . 00
BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2
.900	.01731	.01378	.01577	.01477	.44375	.44161	.44141
.900	.01752	.01407	.01609	.01508	.32988	.32727	.32727
.900	.01763	.01433	.01649	.01541	.21285	.21177	.21165
.900	.01729	.01459	.01653	.01556	.10140	.09974	.09945
.900	.01309	.01026	.01245	.01136	.01074	.01004	.01040
.900	.01281	.00932	.01156	.01044	.12255	.12254	.12282
.900	.006	.006	.00820	.00720	.23319	.23359	.23412
.900	.005	.01184	.00820	.01030	.00925	.23319	.23359
.900	.005	.01255	.00888	.01098	.00993	.34603	.34702
.900	.005	.01574	.01240	.01429	.01335	.46345	.46318
GRADIENT	.00062	.00065	.00064	.00065	.00065	.11308	.11283

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM017) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1201/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.450	-3.993	.03763	.03376	.03578	.03477	-.59302	-.59254	-.59272	-.59263	1158.36200
1.449	-2.997	.03650	.03255	.03467	.03361	-.44216	-.44191	-.44203	1151.34000	1158.41400
1.450	-1.996	.03619	.03196	.03435	.03315	-.29315	-.29316	-.29307	-.29312	1158.37000
1.450	-1.003	.03138	.02850	.03065	.02957	-.13844	-.13806	-.13792	-.13799	1158.41200
1.450	.005	.02442	.02123	.02335	.02229	.01481	.01322	.01364	.01343	1158.29300
1.450	1.004	.01968	.01623	.01848	.01735	.17398	.17333	.17373	.17353	1160.27299
1.450	1.990	.01893	.01509	.01711	.01610	.31973	.32053	.32077	.32065	1158.17799
1.450	2.986	.02292	.01886	.02091	.01989	.47070	.47049	.47121	.47085	1158.55600
1.450	3.986	.02593	.02199	.02425	.02312	.63610	.63636	.63687	.63662	1158.39400
GRADIENT		-.00224	-.00224	-.00224	-.00224	.15360	.15360	.15368	.15364	.59282 .00049

	RUN NO.	1280/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.473	-3.982	.02542	.02368	.02545	.02456	-.61936	-.62012	-.62022	-.62017	1144.36617
1.473	-2.990	.02598	.02429	.02598	.02514	-.45553	-.45343	-.45373	-.45358	1144.60005
1.473	-1.990	.02723	.02659	.02833	.02746	-.29684	-.29606	-.29605	-.29605	1144.24300
1.473	-.986	.02885	.02782	.02962	.02872	-.13904	-.13815	-.13814	-.13814	1145.63858
1.473	.017	.02436	.02355	.02515	.02435	.01779	.01645	.01651	.01648	1145.58900
1.473	1.010	.02121	.02011	.02175	.02093	.17929	.17883	.17897	.17890	1145.79712
1.473	2.000	.02077	.01992	.02169	.02080	.33713	.33793	.33820	.33807	1148.26323
1.473	3.001	.02409	.02333	.02502	.02418	.49552	.49587	.49626	.49606	1149.41100
1.473	3.991	.02571	.02414	.02596	.02505	.65894	.65810	.65876	.65843	1145.94299
GRADIENT		-.00042	-.00037	-.00037	-.00037	.15963	.15951	.15961	.15956	.50876 .28413

	RUN NO.	1242/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.496	-3.987	.02438	.02342	.02513	.02427	-.66082	-.66125	-.66154	-.66140	1144.14500
1.496	-2.990	.02519	.02427	.02602	.02515	-.50063	-.49845	-.49874	-.49860	1146.45000
1.496	-1.985	.02671	.02580	.02750	.02665	-.33132	-.33063	-.33056	-.33059	1147.78000
1.496	-.989	.02660	.02526	.02709	.02617	-.15371	-.15272	-.15264	-.15268	1145.91200
1.496	.016	.02118	.01987	.02149	.02068	.02007	.01917	.01933	.01925	1144.13200
1.496	1.017	.01835	.01716	.01874	.01795	.19503	.19468	.19491	.19479	1145.28551
1.496	2.000	.01726	.01646	.01807	.01727	.36305	.36288	.36235	.36261	1146.83900
1.496	2.995	.02124	.02031	.02199	.02115	.52899	.52742	.52807	.52775	1147.01700
1.496	4.001	.02219	.02121	.02314	.02217	.70313	.70243	.70303	.70273	1147.81000
GRADIENT		-.00080	-.00079	-.00079	-.00079	.17170	.17145	.17154	.17149	.24732 .02755

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 664

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM017) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.520	-3.987	.03414	.03248	.03414	.03331	-.66163	-.66048	-.66070	-.66059	1144.73199	1145.17578
1.520	-2.985	.01662	.01488	.01662	.01575	-.42210	-.42046	-.42057	-.42052	1141.61800	1143.28876
1.520	-1.990	-.00650	-.00554	-.00543	-.00549	-.18518	-.18430	-.18417	-.18423	1142.01700	1142.11697
1.520	-.992	.00204	.00192	.00288	.00240	-.07574	-.07431	-.07401	-.07416	1142.49699	1143.22028
1.520	.015	.00503	.00409	.00409	.00501	.02182	.02173	.02209	.02191	1143.83701	1144.322732
1.520	1.004	-.00043	.00085	.00089	.00087	.11565	.11555	.11587	.11571	1143.21500	1143.35368
1.520	2.006	.00998	.00923	.01098	.01011	.29865	.29932	.29982	.29957	1140.57201	1142.91370
1.520	3.001	.02396	.02237	.02425	.02331	.51153	.51084	.51140	.51112	1139.81900	1142.04536
1.520	3.996	.02489	.02320	.02500	.02410	.74226	.74147	.74230	.74189	1138.87900	1141.36711
GRADIENT	.00026	.00023	.00028	.00026	.00026	.15991	.15963	.15975	.15969	-.511719	-.28770
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.544	-3.987	.00686	.00612	.00788	.00700	-.59615	-.59544	-.59566	-.59555	1129.75900	1139.16669
1.544	-2.979	.00562	.00488	.00669	.00578	-.41226	-.41057	-.41077	-.41067	1129.93300	1137.92747
1.544	-1.989	.00798	.00814	.00891	.00897	-.24234	-.24242	-.24254	-.24248	1128.34300	1137.02879
1.544	-.991	.01172	.01101	.01278	.01189	-.09409	-.09269	-.09266	-.09267	1125.54100	1136.55981
1.544	.017	.00745	.00652	.00752	.00752	.02543	.02524	.02549	.02537	1124.47301	1137.44447
1.544	1.010	-.00057	.00100	.00111	.00106	.14343	.14299	.14323	.14311	1125.42000	1138.37132
1.544	2.000	-.00835	-.00648	-.00646	-.00647	.28049	.28047	.28081	.28064	1126.19901	1138.04631
1.544	3.001	-.01096	-.01080	-.00906	-.00993	.43226	.43261	.43296	.43279	1123.49800	1135.14342
1.544	3.995	-.00578	-.00508	-.00479	-.00494	.60664	.60724	.60724	.60694	1123.22501	1135.33475
GRADIENT	-.00243	-.00219	-.00237	-.00228	-.00237	.14422	.14402	.14412	.14407	-.83319	-.33133

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM018) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1272/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.900	-3.989	.01584	.01499	.01675	.01587	-.44496	-.44261	-.44239	1269.30901	1273.64000
.900	-2.989	.01619	.01565	.01722	.01643	-.32964	-.32807	-.32804	1271.37100	1273.94000
.900	-1.985	.01621	.01606	.01786	.01696	-.21275	-.21133	-.21132	1272.33800	1273.78000
.900	-.993	.01628	.01598	.01778	.01688	-.10326	-.10093	-.10086	1272.84399	1273.84000
.900	.016	.01246	.01221	.01402	.01311	.00841	.00899	.00917	1272.75999	1273.56000
.900	.899	1.005	.01103	.01074	.01250	.01162	.12176	.12197	12221.12221	1273.39999
.900	2.005	.01016	.00998	.01173	.01085	.01176	.23268	.23346	1271.81900	1273.50999
.900	2.998	.01194	.01085	.01267	.01176	.01576	.34625	.34673	1270.46800	1273.34000
.900	4.000	.01594	.01492	.01660	.01660	.01576	.46363	.46392	1267.87801	1273.05000
GRADIENT		.00050	-.00054	-.00053	-.00053	.00053	.11317	.11290	.11291	-.08448

	RUN NO.	1266/ 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.250	-3.985	.01557	.01433	.01609	.01521	-.48516	-.48467	-.48470	1177.01199	1182.64101
1.250	-2.987	.01632	.01497	.01686	.01591	-.35737	-.35715	-.35693	1179.64600	1182.34900
1.250	-1.986	.01765	.01643	.01840	.01741	-.23139	-.23122	-.23146	1179.69901	1182.44800
1.250	-.981	.01782	.01646	.01835	.01740	-.10734	-.10619	-.10616	1180.11200	1182.74600
1.250	.015	.01367	.01234	.01438	.01336	.01368	.01437	.01457	1179.92101	1182.46001
1.250	1.008	.01090	.00960	.01169	.01065	.13895	.13986	.13997	1181.17300	1182.93900
1.250	2.003	.01110	.00965	.01160	.01062	.26218	.26292	.26319	1179.53799	1181.99500
1.250	2.999	.01261	.01103	.01299	.01201	.38575	.38514	.38548	1178.59700	1182.74001
1.250	4.000	.01505	.01459	.01649	.01554	.51491	.51423	.51466	1175.75200	1182.65100
GRADIENT		.00055	-.00052	-.00050	-.00051	.00051	.12467	.12456	.12452	-.12405 .00838

	RUN NO.	1261/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.400	-3.988	.01395	.01396	.01489	.01489	-.56122	-.56058	-.56079	1159.01100	1164.29500
1.399	-2.980	.01586	.01495	.01679	.01587	-.41514	-.41467	-.41485	1161.61400	1164.14500
1.400	-1.984	.01848	.01748	.01925	.01837	-.27050	-.27058	-.27068	1163.44901	1163.94701
1.400	-.986	.01719	.01628	.01810	.01719	-.13014	-.12823	-.12816	1162.21700	1164.27100
1.400	.019	.01197	.01096	.01278	.01187	.01170	.01225	.01244	1162.91901	1164.01500
1.400	1.008	.00952	.00849	.01036	.00942	.15646	.15718	.15733	1163.19800	1164.50400
1.400	2.000	.01139	.01044	.01235	.01139	.29723	.29709	.29731	1161.00101	1163.88800
1.400	3.001	.01442	.01431	.01620	.01525	.43827	.43716	.43772	1160.46001	1164.67700
1.400	4.001	.01729	.01705	.01893	.01799	.58814	.58876	.58894	1158.11900	1163.72400
GRADIENT		-.00021	-.00019	-.00018	-.00019	.14333	.14323	.14332	-.11542 -.00961	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 666

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM018) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1228/ O	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA =	.000	PHI =	90.000
			DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.449	-3.987	.03430	.03129	.03331	.03230	.59192	.59212	.59217	.59215	.1150.14200
1.450	-2.980	.03348	.03059	.03264	.03162	.44201	.44240	.44218	.44229	.1152.00000
1.450	-1.985	.03328	.03064	.03249	.03157	.29135	.29257	.29254	.29256	.1155.38901
1.450	-.992	.03093	.02810	.03008	.02909	.13724	.13731	.13697	.13714	.1158.15601
1.450	.016	.02530	.02046	.02249	.02148	.01362	.01375	.01429	.01402	.1158.66499
1.450	1.009	.02077	.01597	.01782	.01689	.17278	.17231	.17266	.17249	.1159.50101
1.450	2.006	.01893	.01588	.01799	.01694	.32129	.32077	.32113	.32095	.1154.64000
1.450	2.996	.02218	.01915	.02128	.02021	.47321	.47125	.47176	.47150	.1153.33600
1.450	3.997	.02468	.02142	.02348	.02245	.63414	.63448	.63431	.63431	.1152.83800
GRADIENT	-.00186	-.00193	-.00192	-.00192	-.00192	.15347	.15342	.15347	.15345	.26350 -.04808

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM019) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1224/ O	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
			DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.900	4.025	-.00616	-.00797	-.00720	-.00759	.44181	.44170	.44222	.44196	.1267.88699
.900	3.016	-.00943	-.01136	-.00923	-.01030	.32685	.32766	.32809	.32788	.1270.07300
.900	2.005	-.01214	-.01412	-.01312	-.01239	.21313	.21344	.21329	.21329	.1273.02000
.900	1.000	-.01601	-.01743	-.01524	-.01633	.10048	.10049	.10083	.10066	.1272.08400
.900	-.016	-.01542	-.01659	-.01462	-.01561	.01076	.00970	.00956	.00963	.1272.23500
.900	-1.012	-.00990	-.01114	-.00908	-.01011	.12264	.12083	.12048	.12066	.1271.98300
.900	-2.013	-.00556	-.00721	-.00667	-.00694	.23348	.23319	.23333	.23333	.1271.44800
.900	-3.023	-.00532	-.00701	-.00663	-.00682	.34971	.34754	.34666	.34710	.1270.43300
.900	-.039	-.00709	-.00898	-.00754	-.00826	.46333	.46323	.46323	.46323	.1268.37700
GRADIENT	-.00046	-.00048	-.00039	-.00043	-.00043	.11214	.11189	.11189	.11189	-.01641

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 667

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM019) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1169/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.250	4.023	-.00537	-.00651	-.00523	-.00587	.48954	.48871	.48906	.48889	.1182.34100
1.250	3.010	-.00837	-.00989	-.00856	-.00923	.36295	.36103	.36122	.36120	.1182.61301
1.250	2.001	-.01208	-.01365	-.01245	-.01305	.23645	.23440	.23459	.23449	.1182.63800
1.250	.995	-.01520	-.01697	-.01572	-.01635	.11071	.11032	.11059	.11046	.1182.50000
1.250	.013	-.01181	-.01339	-.01217	-.01278	.01124	.01174	.01147	.01161	.1182.32800
1.250	-1.009	-.00658	-.00819	-.00702	-.00761	.13459	.13596	.13576	.13586	.1182.48100
1.250	-2.027	-.00349	-.00524	-.00462	-.00493	.25985	.25959	.25974	.25966	.1182.46001
1.250	-3.024	-.00351	-.00511	-.00452	-.00482	.38141	.38138	.38157	.38148	.1182.25200
1.250	-4.043	-.00437	-.00500	-.00463	-.00481	.51093	.51094	.51093	.51093	.1182.50101
GRADIENT		-.00073	-.00076	-.00064	-.00070	.12364	.12346	.12353	.12349	.16701 .01350

RUN NO. 1188/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1188/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.400	4.025	-.00166	-.00601	-.00535	-.00568	.56552	.56544	.56601	.56572	.1161.26601 .15401
1.400	3.024	-.00425	-.00861	-.00699	-.00780	.42210	.41994	.42066	.42030	.1163.24100 .86000
1.399	2.004	-.01030	-.01558	-.01345	-.01452	.27601	.27557	.27594	.27576	.1163.75200 .52200
1.399	.998	-.01294	-.01808	-.01593	-.01700	.13212	.13087	.13139	.13113	.1163.65800 .95000
1.400	.019	-.00864	-.01378	-.01159	-.01269	.01300	.01243	.01196	.01220	.1165.20000 .41901
1.400	-1.004	-.00373	-.00894	-.00710	-.00802	.15269	.15273	.15245	.15259	.1164.83701 .06799
1.400	-2.024	-.00159	-.00664	-.00612	-.00638	.29501	.29450	.29481	.29491	.1162.62500 .21100
1.400	-3.015	-.00283	-.00745	-.00663	-.00704	.43450	.43350	.43490	.43500	.1161.92500 .33900
1.400	-4.035	-.00310	-.00765	-.00661	-.00713	.58620	.58710	.58705	.58707	.1160.11700 .04800
GRADIENT		-.00041	-.00039	-.00032	-.00036	.14239	.14235	.14242	.14238	.15875 -.00852

RUN NO. 1202/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1202/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.450	4.030	-.01917	-.02174	-.01972	-.02073	.59797	.59824	.59876	.59850	.1150.15800 .1158.57201
1.450	3.019	-.02136	-.02367	-.02158	-.02262	.44653	.44702	.44745	.44723	.1151.92999 .1158.70399
1.450	2.011	-.02479	-.02713	-.02505	-.02609	.29797	.29811	.29852	.29831	.1155.04300 .20000
1.450	1.005	-.02378	-.02643	-.02428	-.02535	.14255	.14217	.14249	.14233	.1157.46400 .1158.31200
1.450	.003	-.01754	-.02007	-.01816	-.01912	.01103	.01088	.01067	.01078	.1158.63699 .1158.17200
1.450	-1.001	-.01224	-.01479	-.01279	-.01379	.16815	.16773	.16762	.16767	.1160.67500 .1158.58800
1.450	-2.009	-.00827	-.01063	-.00860	-.00962	.31738	.31659	.31664	.31661	.1155.25800 .1158.51900
1.450	-3.011	-.00809	-.01057	-.00841	-.00949	.46806	.46601	.46590	.46596	.1154.07700 .1158.21400
1.450	-4.025	-.00778	-.01037	-.00828	-.00932	.62915	.62998	.62931	.62923	.1153.40100 .1158.09500
GRADIENT		-.00215	-.00214	-.00215	-.00214	.15238	.15233	.15223	.15226	-.38234 -.04088

卷之三

PARAMETRIC DATA

		ALPHA = .000	PHI = .000	P T F
RUN NO.	1281 / 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	
BETA	DPACAL	DPA1	DPA	DPBCAL
4 .024	-0.1168	-0.01172	-0.00987	-0.01080
3 .007	-0.1433	-0.1460	-0.1280	-0.1370
2 .004	-0.02025	-0.02060	-0.1891	-0.1976
.993	-0.02455	-0.02472	-0.02310	-0.02391
.010	-0.02176	-0.02194	-0.02022	-0.02108
-1 .012	-0.01731	-0.01752	-0.01575	-0.01663
-2 .014	-0.01422	-0.01421	-0.01246	-0.01334
-3 .021	-0.01358	-0.01371	-0.01205	-0.01288
-4 .040	-0.01203	-0.01191	-0.01024	-0.01108
GRADIENT	.000333	.00036	.00035	.00035
RUN NO.	1243 / 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	
BETA	DPACAL	DPA1	DPA	DPBCAL
4 .023	-0.1697	-0.1688	-0.1522	-0.1605
3 .012	-0.02111	-0.02082	-0.01930	-0.02006
1 .999	-0.02754	-0.02732	-0.02571	-0.02651
.996	-0.02815	-0.02782	-0.02611	-0.02697
.027	-0.02427	-0.02408	-0.02250	-0.02329
-1 .013	-0.02078	-0.02030	-0.01876	-0.01953
-2 .024	-0.01970	-0.01905	-0.01720	-0.01813
-3 .020	-0.01773	-0.01695	-0.01539	-0.01617
-4 .039	-0.01424	-0.01355	-0.01184	-0.01270
GRADIENT	.00073	.00081	.00082	.00081
RUN NO.	1289 / 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	
BETA	DPACAL	DPA1	DPA	DPBCAL
4 .024	-0.02639	-0.02595	-0.02430	-0.02512
3 .023	-0.02279	-0.02220	-0.02048	-0.02134
1 .988	-0.02794	-0.02643	-0.02473	-0.02558
.994	-0.02425	-0.02308	-0.02154	-0.02231
.015	-0.02424	-0.02332	-0.02180	-0.02256
-1 .006	-0.02748	-0.02590	-0.02422	-0.02506
-2 .014	-0.02720	-0.02595	-0.02434	-0.02515
-3 .016	-0.02209	-0.02181	-0.02094	-0.02007
-4 .040	-0.01762	-0.01708	-0.01543	-0.01626
GRADIENT	.00059	.00058	.00058	.00058

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 669  
(UCMO19) (04 OCT 91)

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

## PARAMETRIC DATA

	RUN NO.	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	DPACAL	DPA1	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.543	4.023	-0.1950	-0.01881	-.01786	.56182	.56241	.56266	1130.08099	1138.34164
1.544	3.016	-0.02531	-0.02439	-.02350	.39810	.39818	.39843	1128.46899	1136.22232
1.543	2.004	-0.02940	-0.02767	-.02683	.23540	.23577	.23599	1126.46300	1135.02917
1.543	.993	-0.03272	-0.03106	-.03020	.08867	.08900	.08921	1123.67500	1135.32980
1.543	.016	-0.02950	-0.02778	-.02695	-.03102	-.02912	-.02918	1122.23000	1135.70035
1.544	1.012	-0.02172	-0.02001	-.01917	-.14635	-.14546	-.14534	1122.76401	1136.31039
1.544	2.025	-0.01576	-0.01390	-.01312	-.28998	-.28998	-.29008	1124.03101	1137.12093
1.544	3.021	-0.00804	-0.00819	-.00767	-.45628	-.45473	-.45482	1126.23399	1138.86134
1.544	-4.040	.00173	.00186	.00260	.67796	.67724	.67757	1127.30600	1139.80496
GRADIENT		.00289	-.00281	-.00274	.14578	.14570	.14577	.39110	-.31287

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

## PARAMETRIC DATA

	RUN NO.	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	DPACAL	DPA1	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.900	4.025	-.00648	-.00581	-.00586	-.00583	.44249	.44324	1268.69701	1273.42000
.900	3.016	-.01037	-.00953	-.00778	-.00865	.32720	.32844	1270.79500	1273.39999
.900	1.999	-.01439	-.01268	-.01099	-.01183	.21141	.21311	1271.99100	1273.44000
.900	.995	-.01702	-.01553	-.01389	-.01471	.10044	.10101	1272.45799	1273.50999
.900	-.022	-.01702	-.01544	-.01368	-.01456	-.01227	-.01001	1272.54100	1273.25999
.900	-1.012	-.01119	-.00955	-.00802	-.00878	-.12344	-.12077	1272.25900	1273.17999
.900	-2.018	-.00875	-.00697	-.00690	-.00694	-.23474	-.23306	1271.64101	1272.89999
.900	-3.018	-.00650	-.00578	-.00571	-.00575	-.34682	-.34612	1270.35100	1273.00000
.900	-4.039	-.00737	-.00684	-.00669	-.00676	-.46294	-.46313	1268.04300	1272.71001
.899	GRADIENT	-.00041	-.00040	-.00028	-.00034	.11196	.11198	.07966	.09020

(UCMO20) (04 OCT 91)

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 670

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM020) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1267/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000	
MACH	BETA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	
1.249	4.020	-.00616	-.00502	-.00483	.48677	.48638	.48669	.48654	1176.63200	1182.11700	
1.250	3.018	-.00919	-.00861	-.00800	.36029	.36031	.35993	.36012	1179.25101	1182.74400	
1.250	1.999	-.01214	-.01180	-.01089	.23324	.23400	.23418	.23409	1179.93401	1182.56700	
1.250	.993	-.01521	-.01476	-.01302	.01389	.10734	.10784	.10840	.10812	1179.43900	1181.97000
1.250	.015	-.01222	-.01189	-.01065	.01097	.01481	.01284	.01256	.01270	1180.57800	1183.16701
1.249	-1.016	-.00764	-.00718	-.00701	.00710	.13891	.13758	.13744	.13751	1180.56400	1181.93700
1.250	-2.017	-.00555	-.00500	-.00473	.00486	.26046	.26077	.26065	.26071	1180.20500	1183.00301
1.250	-3.025	-.00522	-.00480	-.00458	.00469	.38354	.38321	.38324	.38322	1178.32001	1182.17599
1.250	-4.044	-.00615	-.00537	-.00490	.00513	.51276	.51262	.51291	.51277	1175.93600	1182.82600
GRADIENT	- .00054	-.00051	-.00040	-.00046	.00046	.12351	.12348	.12351	.12349	.06481	-.03264

	RUN NO.	1262/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	PTTF	
MACH	BETA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	
1.400	4.019	-.00373	-.00224	-.00210	.00217	.56306	.56301	.56344	.56322	1159.03900	1164.29601
1.400	3.006	-.00638	-.00486	-.00451	.00469	.41827	.41741	.41777	.41759	1161.19800	1164.09399
1.400	1.998	-.01142	-.01077	-.00893	.00985	.27522	.27508	.27519	.27513	1161.89000	1164.64999
1.400	.997	-.01455	-.01384	-.01205	.01295	.13045	.13120	.13149	.13134	1161.72200	1164.13901
1.400	-.020	-.01137	-.01047	-.00859	.00953	.01259	.01081	.01071	.01076	1163.24400	.55901
1.400	-1.014	-.00712	-.00609	-.00599	.00604	.15436	.15326	.15326	.15326	1163.10801	.1164.08000
1.400	-2.020	-.00505	-.00412	-.00389	.00401	.29380	.29355	.29373	.29364	1161.19099	.1164.31200
1.400	-3.021	-.00710	-.00559	-.00532	.00546	.43458	.43417	.43420	.43419	1160.18300	.1163.80800
1.400	-4.041	-.00749	-.00574	-.00573	.00573	.58617	.58617	.58649	.58633	1158.74899	.1164.34801
GRADIENT	- .0005	-.00001	-.00008	-.00001	.00003	.14214	.14202	.14210	.14206	.07101	-.02281

	RUN NO.	1231/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	PTTF	
MACH	BETA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	
1.450	4.014	-.02323	-.0214	-.0213	.02313	.59648	.59710	.59759	.59735	1148.71100	1158.32600
1.450	3.013	-.02439	-.02500	-.02301	.02401	.45050	.44856	.44899	.44877	1151.18600	1158.46001
1.450	1.994	-.02550	-.02618	-.02831	.02724	.29727	.29707	.29745	.29726	1154.82700	.1158.10201
1.450	.999	-.02625	-.02859	-.02671	.02765	.14213	.14145	.14166	.14156	1157.57401	.1158.69000
1.450	-.025	-.02011	-.02270	-.02081	.02176	.01462	.01295	.01277	.01286	1158.28200	.1157.98500
1.450	-1.012	-.01488	-.01738	-.01643	.01643	.16902	.16910	.16980	.16945	1159.95500	.1158.64200
1.450	-2.015	-.01109	-.01397	-.01210	.01303	.31547	.31706	.31720	.31713	1154.42799	.1157.89600
1.450	-3.027	-.01312	-.01443	-.01346	.01346	.46963	.46920	.46951	.46936	1154.19000	.1158.66800
1.450	-4.057	-.01346	-.01469	-.01257	.01363	.63326	.63249	.63344	.63335	1153.55099	.1158.19600
GRADIENT	- .00187	-.00181	-.00181	-.00181	.00181	.15245	.15246	.15258	.15252	-.49527	.00606

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( UCMO21 ) ( 04 OCT 91 )  
PAGE 671

(UCM021) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH		ALPHA		GRADIENT		INTERVAL =		-5.00/		5.00	
RUN NO.	RN/L =	RN/L	O	RN/L	O	RN/L	O	RN/L	O	RN/L	O
MACH 1.300 1.300	GRADIENT	DPA1	DPA2	DPA	DPA1	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.012	.013	.01164	.01315	.01240	.01481	- .01440	- .01406	- .01423	1171.00101	1176.3569	
-.4	-.025	-.50263	-.50112	-.50188	-.01249	- .01265	- .01194	- .01229	1163.99001	1175.9230	
MACH 1.350 1.350	GRADIENT	DPA1	DPA2	DPA	DPA1	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.017	.028	.01536	.01766	.01651	.01211	- .01261	- .01207	- .01234	1165.92000	1170.1320	
-.4	-.028	-.52878	-.53041	-.52926	-.52983	- .00948	- .01019	- .00983	1159.89400	1170.6600	
MACH 1.350 1.350	GRADIENT	DPA1	DPA2	DPA	DPA1	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.017	.028	.01532	.01352	.01352	.13508	- .00065	- .00060	- .00064	- .00062	1.48992	-.1305
-.4	-.025	-.13494	-.13522	-.13522	.13508	- .00065	- .00060	- .00064	- .00062	1.48992	-.1305
MACH 1.470 1.470	GRADIENT	DPA1	DPA2	DPA	DPA1	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.010	.025	.01140	.01359	.01249	.02018	- .02066	- .02046	- .02056	1145.61000	1148.6854	
-.4	-.025	-.62691	-.62509	-.62600	-.01499	- .01545	- .01518	- .01532	1141.28101	1148.8201	
MACH 1.470 1.470	GRADIENT	DPA1	DPA2	DPA	DPA1	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.010	.025	.01140	.01359	.01249	.02018	- .02066	- .02046	- .02056	1145.61000	1148.6854	
-.4	-.025	-.62691	-.62509	-.62600	-.01499	- .01545	- .01518	- .01532	1141.28101	1148.8201	
MACH 1.470 1.470	GRADIENT	DPA1	DPA2	DPA	DPA1	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.010	.025	.01140	.01359	.01249	.02018	- .02066	- .02046	- .02056	1145.61000	1148.6854	
-.4	-.025	-.62691	-.62509	-.62600	-.01499	- .01545	- .01518	- .01532	1141.28101	1148.8201	

	MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPB CAL	DPB 1	DPB 2	PTTF	PT2F
1.519	.009	.01136	.01136	.01227	-.01330	-.01348	-.01327	-.01337	1139.52499	1139.7775
1.519	-4.019	-.65897	-.6584	-.65736	-.65810	-.03192	-.03102	-.03060	1137.14500	1141.56639
GRADIENT		16642	16639	16646	16643	.00462	.00435	.00433	.59085	-.4433

卷之三

HISTOGRAMMETRIC DATA

RUN NO.	1172/O	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA ±	.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTIF	PTF
1.300	.015	-.01596	-.01728	-.01573	-.01651	.01698	.01627	.01647	.0176.3899
1.300	4.027	.50788	.50553	.50681	.50617	.01632	.01587	.01601	.0176.4299
GRADIENT		1.2950	1.2924	1.2928	1.2931	- .00016	- .00010	- .00011	.010

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 672

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM022) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1176/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
1.350	.014	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-.015	-.01516	-.01728	-.01645	-.01686	.01540	.01444	.01491	.01468	1166.61099	1170.66400
1.350	4.015	.53179	.53028	.53180	.53104	.01477	.01393	.01415	.01404	1167.90900	1170.17700
	GRADIENT	.13578	.13593	.13610	.13602	-.00016	-.00013	-.00019	-.00016	.32222	-.12090

MACH	ALPHA	RUN NO.	1234/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
1.470	.017	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	4.028	-.01453	-.01688	-.01487	-.01588	.02388	.02182	.02215	.02199	1147.26900	1149.93648
1.470	GRADIENT	.62697	.62419	.62586	.62502	.02257	.02089	.02088	.02089	1150.31500	1150.06801
		.15861	.15850	.15842	.15846	-.00032	-.00023	-.00031	-.00027	.75312	.03252

MACH	ALPHA	RUN NO.	1246/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
1.519	.016	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	4.022	-.03623	-.03507	-.03312	-.03410	.01098	.00912	.00947	.00929	1140.37700	1140.71545
1.519	GRADIENT	.62895	.62812	.62979	.62895	.02765	.02812	.02797	.02804	1140.33299	1141.12039
		.16471	.16422	.16415	.16419	.00413	.00470	.00458	.00464	-.01089	.10027

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM023) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1249/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
1.519	.016	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	4.022	-.03673	-.03566	-.03381	-.03473	.01096	.00923	.00958	.00940	1139.98500	1140.57405
1.519	GRADIENT	.62970	.62893	.63066	.62980	.02644	.02648	.02648	.02646	1140.66299	1141.04407
		.16502	.16457	.16454	.16455	.00383	.00426	.00419	.00422	.16788	.11639

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 673

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM024) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1113/ 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
1.300	1.999	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-2.029	.01429	.01242	.01384	.01313	.27049	.26920	.26979	.26950	1171.66100	1176.20799
1.299	-2.029	.02196	.02003	.02144	.02074	.24134	.24207	.24182	.24194	1174.80701	1179.02901
		.00189	.00189	.00189	.00189	.12709	.12695	.12703	.12699	.78116	.70046

MACH	BETA	RUN NO.	11177/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
1.350	1.994	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-2.023	.01355	.01063	.01212	.01137	.28684	.28555	.28629	.28592	1168.25999	1170.71100
1.350	GRADIENT	.02097	.01813	.01953	.01883	.25492	.25437	.25440	.25439	1167.15100	1170.37500
		-.00185	-.00187	-.00185	-.00186	.13487	.13442	.13461	.13451	.27609	.08365

MACH	BETA	RUN NO.	1235/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
1.470	1.995	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-2.016	.02041	.01646	.01840	.01743	.33399	.33450	.33488	.33469	1149.17500	1151.61566
1.470	GRADIENT	.02744	.02353	.02562	.02457	.30048	.30008	.30012	.30010	1145.13901	1151.86835
		-.00175	-.00176	-.00180	-.00178	.15816	.15819	.15829	.15824	1.00609	.06299

MACH	BETA	RUN NO.	1247/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
1.519	1.995	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-2.016	.00939	.00807	.00983	.00895	.30479	.30464	.30496	.30480	1139.94200	1142.04900
1.519	GRADIENT	-.01119	-.01042	-.00855	-.00949	.19275	.19226	.19215	.19221	1140.34801	1140.87892
		.00513	.00461	.00458	.00460	.12403	.12387	.12392	.12390	-.10121	.29168

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM025) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	RUN NO.	1114/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
1.300	1.995	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-2.007	-.00707	-.00806	-.00668	-.00737	-.26448	-.26531	-.26510	-.26521	1170.95300	1175.98300
1.300	2.022	-.01673	-.01789	-.01633	-.01711	.24502	.24351	.24408	.24380	1171.69901	1176.21400
	GRADIENT	-.00240	-.00244	-.00239	-.00242	.12645	.12628	.12637	.12633	.18515	.05733

(UCM025) ( 04 OCT 91 )

## PARAMETRIC DATA

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 674

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(UCM025) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	GRADIENT	ALPHA = .000 PHI = -90.000									
			RN/L = 1178/0	DPA1	DPA2	DPA	DPRCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.350	-2.013	GRADIENT	- .00400	- .00586	- .00480	- .00533	- .28201	- .28185	- .28135	- .28160	1168.09200	1170.67000
	2.022		- .01259	- .01479	- .01350	- .01414	.25895	.25713	.25789	.25751	1167.35800	1170.41600
	1.350		- .00213	- .00221	- .00216	- .00218	.13409	.13360	.13366	.13363	-.18193	-.06296
MACH	BETA	GRADIENT	RN/L = 1236/0	DPA1	DPA2	DPA	DPRCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-2.009		- .01275	- .01607	- .01385	- .01496	- .33129	- .33074	- .33068	-.33071	1148.27901	1150.66812
	2.025		- .01911	- .02222	- .0209	- .02115	.30208	.30257	.30283	.30270	1141.91200	1149.05885
	1.471		- .00158	- .00152	- .00155	- .00154	.15699	.15698	.15703	.15701	-1.57821	-.39889
MACH	BETA	GRADIENT	RN/L = 1248/0	DPA1	DPA2	DPA	DPRCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-2.009		- .02485	- .02437	- .02261	- .02349	- .32983	- .33016	- .33007	-.33012	1139.96300	1141.91350
	2.031		- .02934	- .02787	- .02601	- .02694	.17328	.17368	.17405	.17386	1141.36700	1142.18593
	1.519		- .00111	- .00087	- .00084	- .00085	.12453	.12471	.12477	.12474	.34751	.06743

## IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

## PARAMETRIC DATA

	RUN NO.	1293/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	BETA =	.000	PTTF
MACH	PHI	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.599	-1.983	-.00385	-.00635	-.00603	-.00619	-.01524	-.01447	-.01426	-.01437	1596.40500	1596.75000
.599	-1.746	-.00208	-.00478	-.00445	-.00461	-.01519	-.01461	-.01432	-.01447	1596.38100	1596.56000
.600	-1.508	-.00329	-.00594	-.00547	-.00571	-.01557	-.01514	-.01499	-.01506	1596.21600	1597.41000
.599	-1.271	-.00185	-.00458	-.00434	-.00446	-.01597	-.01560	-.01549	-.01554	1596.34000	1596.67000
.600	- .993	-.00218	-.00480	-.00451	-.00466	-.01567	-.01518	-.01490	-.01504	1596.46300	1597.42000
.600	- .716	-.00248	-.00522	-.00479	-.00500	-.01620	-.01540	-.01512	-.01526	1596.37500	1597.21001
.600	- .479	-.00190	-.00460	-.00436	-.00448	-.01571	-.01461	-.01439	-.01450	1596.19600	1597.03999
.600	- .241	-.00278	-.00561	-.00509	-.00535	-.01606	-.01520	-.01490	-.01505	1596.22301	1597.08000
.599	- .003	-.00177	-.00456	-.00440	-.00448	-.01631	-.01529	-.01506	-.01517	1596.41000	1597.39999
.600	.234	-.00166	-.00434	-.00398	-.00416	-.01606	-.01494	-.01467	-.01480	1596.38300	1597.24001
.599	.472	-.00147	-.00391	-.00403	-.00403	-.01606	-.01514	-.01480	-.01497	1596.32800	1596.28999
.600	.749	-.00221	-.00487	-.00453	-.00470	-.01620	-.01516	-.01484	-.01500	1596.36501	1596.89000
.599	.987	-.00224	-.00481	-.00511	-.00496	-.01598	-.01525	-.01488	-.01497	1596.53500	1596.89999
.600	1.224	-.00219	-.00528	-.00496	-.00512	-.01651	-.01562	-.01559	-.01561	1596.45100	1597.31000
.600	1.501	-.00229	-.00504	-.00473	-.00488	-.01635	-.01540	-.01508	-.01524	1596.43401	1597.03999
.599	1.739	-.00159	-.00438	-.00413	-.00426	-.01669	-.01562	-.01534	-.01548	1596.49001	1596.77000
.599	1.977	-.00095	-.00360	-.00346	-.00353	-.01549	-.01452	-.01437	-.01444	1596.46300	1596.59000
	GRADIENT	.00033	.00028	.00025	.00027	.00022	.00009	-.00008	-.00009	.03717	-.03079

	RUN NO.	1298/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	BETA =	.000	PTTF
MACH	PHI	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-2.023	-.00451	-.00513	-.00473	-.00497	-.01654	-.01494	-.01475	-.01485	1272.20500	1272.89999
.900	-1.746	-.00437	-.00511	-.00492	-.00492	-.01669	-.01507	-.01478	-.01492	1272.20399	1272.92999
.900	-1.508	-.00424	-.00522	-.00466	-.00494	-.01627	-.01487	-.01460	-.01474	1272.26401	1273.16000
.900	-1.271	-.00438	-.00504	-.00466	-.00485	-.01651	-.01481	-.01456	-.01468	1272.29601	1273.07001
.900	- .993	-.00428	-.00504	-.00460	-.00482	-.01661	-.01481	-.01465	-.01473	1272.15000	1272.92999
.900	- .756	-.00430	-.00476	-.00445	-.00460	-.01668	-.01498	-.01475	-.01487	1272.29201	1272.92000
.900	- .518	-.00414	-.00502	-.00455	-.00479	-.01685	-.01525	-.01501	-.01513	1272.18100	1273.14999
.900	- .241	-.00426	-.00484	-.00438	-.00461	-.01642	-.01498	-.01482	-.01490	1272.25400	1272.89999
.900	- .003	-.00426	-.00480	-.00443	-.00461	-.01688	-.01549	-.01538	-.01543	1272.15601	1272.98000
.900	.234	-.00396	-.00456	-.00406	-.00431	-.01681	-.01498	-.01478	-.01488	1272.25999	1273.08000
.900	.472	-.00391	-.00452	-.00419	-.00435	-.01642	-.01476	-.01447	-.01462	1272.25200	1272.89999
.900	.709	-.00379	-.00447	-.00396	-.00421	-.01735	-.01527	-.01497	-.01512	1272.25600	1273.02000
.900	.987	-.00401	-.00445	-.00413	-.00429	-.01688	-.01534	-.01503	-.01518	1272.19501	1272.87000
.900	1.224	-.00364	-.00423	-.00381	-.00402	-.01710	-.01531	-.01506	-.01518	1272.24500	1273.03999
.900	1.462	-.00384	-.00449	-.00400	-.00425	-.01686	-.01518	-.01495	-.01506	1272.17101	1272.99001
.900	1.739	-.00362	-.00430	-.00393	-.00412	-.01734	-.01538	-.01518	-.01528	1272.28799	1273.00000
.900	1.977	-.00356	-.00410	-.00385	-.00397	-.01676	-.01511	-.01478	-.01495	1272.23700	1273.07001
	GRADIENT	.00022	.00026	.00025	.00026	.00015	-.00010	-.00009	-.00009	.00224	.00395

1A310 (AEDC 16TE-783) PORT MISOBIENT-FAIRING OEE

HICM026 ( 04 OCT 91 )

PARAMETRIC DATA

RUN NO.	1304/ 0	RN/L =	2 . 50	GRADIENT INTERVAL =	- 5.00 /	5 . 00	
PHI	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2
1 . 250	- 1 . 983	- .00250	- .00407	- .00346	- .00376	- .01426	- .01233
1 . 250	- 1 . 746	- .00138	- .00332	- .00259	- .00295	- .01450	- .01265
1 . 249	- 1 . 508	- .00090	- .00275	- .00227	- .00251	- .01429	- .01266
1 . 250	- 1 . 231	- .00076	- .00277	- .00205	- .00241	- .01436	- .01260
1 . 250	- 1 . 250	- .00055	- .00242	- .00171	- .00207	- .01448	- .01253
1 . 249	- .756	- .00046	- .00255	- .00180	- .00217	- .01459	- .01275
1 . 250	- .518	- .00074	- .00235	- .00173	- .00204	- .01451	- .01253
1 . 250	- .241	- .00022	- .00178	- .00107	- .00143	- .01453	- .01249
1 . 250	- .003	- .00012	- .00110	- .00099	- .00134	- .01457	- .01271
1 . 250	.234	.00019	.00178	.00105	.00142	.01457	.01275
1 . 250	.472	.00035	.00178	.00105	.00142	.01407	.01235
1 . 250	.709	.00042	.00139	.00077	.00108	.01439	.01251
1 . 250	.987	.00074	.00145	.00064	.00105	.01431	.01235
1 . 250	1 . 224	.00080	.00141	.00064	.00103	.01442	.01242
1 . 250	1 . 501	.00077	.00134	.00043	.00089	.01442	.01264
1 . 250	1 . 739	.00036	.00152	.00066	.00109	.01460	.01253
1 . 250	1 . 977	.00070	.00148	.00054	.00101	.01447	.01264
GRADIENT	000065	000056	000063	000060	000001	000000	000000

	MACH	RUN NO.	1310/ 0	RN/L =	2 .50	GRADIENT INTERVAL =	- 5.00/	5 .00
PHI			DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2
	-2 .023	.00404	-.00262	-.00229	-.00245	-.01466	-.01321	-.01322
	-1 .400	.00285	-.00132	-.00096	-.00114	-.01443	-.01318	-.01322
	-1 .400	.00295	-.00143	-.00118	-.00130	-.01443	-.01317	-.01299
	-1 .508	.00285	-.00130	-.00099	-.00114	-.01438	-.01328	-.01322
	-1 .231	.00282	-.00128	-.00094	-.00111	-.01444	-.01315	-.0130
	-1 .400	.00283	-.00101	-.00096	-.00099	-.01431	-.01308	-.01285
	-1 .400	.00246	-.00106	-.00084	-.00095	-.01449	-.01302	-.0129
	-1 .518	.00254	-.00110	-.00084	-.00097	-.01448	-.01328	-.01316
	-1 .400	.00235	-.00084	-.00069	-.00076	-.01427	-.01317	-.01299
	-1 .400	.003	.00235	-.00077	-.00049	-.00063	-.01437	-.01314
	-1 .400	.234	.00229	-.00077	-.00060	-.00079	-.01413	-.01304
	-1 .399	.472	.00235	-.00097	-.00060	-.00054	-.01403	-.01277
	-1 .400	.709	.00219	-.00071	-.00037	-.00054	-.01291	-.01300
	-1 .400	.987	.00209	-.00064	-.00043	-.00054	-.01410	-.01337
	-1 .400	.1 .224	.00233	-.00064	-.00054	-.00059	-.01419	-.01282
	-1 .400	.1 .462	.00226	-.00088	-.00060	-.00074	-.01417	-.01293
	-1 .400	.1 .739	.00186	-.00044	-.00026	-.00035	-.01438	-.01315
	-1 .399	.1 .977	.00225	-.00077	-.00041	-.00059	-.01441	-.01315
		.00033	.00031	.00030	.00031	.00008	.00005	.00005
		GRADIENT						

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 677

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(UCMO26) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1315/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	BETA =	.000	PT1F	PT2F
	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	PT1F	PT2F
MACH	PHI											
1.545	-2.023	-.00399	-.00174	-.00154	-.00164	-.01972	-.01818	-.01818	-.01818	-.01818	1138.37335	
1.545	-1.746	-.00376	-.00145	-.00135	-.00140	-.02004	-.01843	-.01839	-.01839	-.01839	1138.77806	
1.545	-1.469	-.00310	-.00091	-.00077	-.00084	-.01942	-.01803	-.01802	-.01802	-.01802	1138.33476	
1.545	-1.271	-.00302	-.00064	-.00039	-.00051	-.02069	-.01911	-.01902	-.01902	-.01902	1137.78508	
1.545	-0.993	-.00262	-.00025	-.0002	-.00011	-.01994	-.01858	-.01856	-.01856	-.01856	1137.73575	
1.544	-0.716	-.00231	-.00013	-.00028	-.00020	-.01985	-.01843	-.01835	-.01839	-.01839	1137.68033	
1.544	-0.479	-.00294	-.00069	-.00041	-.00055	-.02055	-.01882	-.01895	-.01889	-.01889	1138.07910	
1.544	-0.241	-.00209	-.00026	-.00051	-.00038	-.02050	-.01907	-.01891	-.01899	-.01899	1137.99348	
1.544	-0.003	-.00213	-.00043	-.00072	-.00058	-.02062	-.01907	-.01897	-.01902	-.01902	1137.47650	
1.544	.234	.00188	.00052	.00064	.00058	-.02111	-.01929	-.01932	-.01930	-.01930	1137.57005	
1.544	.511	.00190	.00041	.00062	.00051	-.02121	-.01973	-.01949	-.01961	-.01961	1137.38875	
1.544	.749	.00140	.00050	.00089	.00070	-.02109	-.01953	-.01942	-.01948	-.01948	1137.78914	
1.544	.987	.00145	.00087	.00128	.00108	-.01997	-.01878	-.01865	-.01871	-.01871	1137.90334	
1.544	1.264	.00129	.00109	.00143	.00126	-.02040	-.01905	-.01884	-.01894	-.01894	1137.73981	
1.544	1.462	.00047	.00136	.00194	.00165	-.01950	-.01818	-.01794	-.01806	-.01806	1137.54015	
1.544	1.739	.00051	.00140	.00196	.00168	-.01993	-.01854	-.01833	-.01843	-.01843	1137.34520	
1.544	1.977	.00048	.00140	.00211	.00176	-.02100	-.01902	-.01899	-.01901	-.01901	1137.50249	
	GRADIENT	.00084	.00086	.00074	.00080	-.00014	-.00015	-.00009	-.00012	-.00009	-.22479	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 678

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(UCM027) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA = -8.000						BETA = .000							
					DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	DPB1	DPB2	DPB	PTTF	
MACH	PHI	DPACAL																
.599	-2.006	-.73599	-.73851	-.73661	-.73756	-.73618	-.73521	.00331	.00408	.00458	.00433	1562.94701	1597.00000					
.599	-1.731	-.73475	-.73476	-.73471	-.73677	-.73471	-.73677	.00064	.00147	.00189	.00168	1562.91600	1596.98000					
.600	-1.496	-.73419	-.73421	-.73421	-.73677	-.73482	-.73482	.00336	.00053	.00237	.00209	1562.94299	1597.35001					
.599	-1.222	-.73461	-.73461	-.73690	-.73491	-.73579	-.73579	.00653	.00573	.00573	.00554	1562.95500	1596.89999					
.599	-0.986	-.751	-.73490	-.73736	-.73533	-.73634	-.73533	.00974	.00886	.00842	.00864	1562.96899	1596.88000					
.599	-0.477	-.73482	-.73731	-.73529	-.73630	-.73630	-.73529	.01345	.01345	.01271	.01208	.01240	1562.98100	1597.10001				
.599	-0.241	-.73589	-.73840	-.73649	-.73745	-.73649	-.73745	.01544	.01544	.01458	.01402	.01430	1563.00800	1597.22000				
.600	-0.006	-.73692	-.73948	-.73758	-.73853	-.73758	-.73853	.01924	.01867	.01818	.01842	1563.10100	1596.66000					
.600	.229	-.73692	-.73937	-.73743	-.73840	-.73743	-.73840	.02180	.02132	.02076	.02104	1563.04700	1597.25000					
.599	.504	-.73764	-.74046	-.73841	-.73943	-.73841	-.73943	.02626	.02570	.02511	.02540	1562.99600	1596.49001					
.600	.739	-.73699	-.73956	-.73762	-.73859	-.73762	-.73859	.03155	.03106	.02794	.02751	.02730	1562.97900	1597.02000				
.599	.974	-.73744	-.74002	-.73820	-.73911	-.73820	-.73911	.03510	.03477	.03106	.03056	.03106	1563.14301	1596.94000				
.599	1.210	-.73722	-.74002	-.73796	-.73899	-.73796	-.73899	.03858	.03818	.03437	.03457	1563.28999	1596.97000					
.599	1.445	-.73829	-.74090	-.73881	-.73986	-.73881	-.73986	.04047	.04030	.03767	.03792	1563.16200	1597.12000					
.599	1.719	-.73870	-.74127	-.73939	-.74033	-.73939	-.74033	.04590	.04544	.04030	.03973	.04001	1563.05400	1596.73000				
.599	1.955	-.73740	-.73996	-.73802	-.73899	-.73802	-.73899	.04898	.04842	.04499	.04521	1563.21500	1596.75000					
GRADIENT	.00102	-.00107	-.00107	-.00107	-.00107	-.00107	-.00107	.01309	.01324	.01324	.01324	.01324	1563.10699	1597.13000				
													.06556	.03859				

RUN NO.	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA = -8.000						BETA = .000							
					DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	DPB1	DPB2	DPB	PTTF	
MACH	PHI	DPACAL																
.900	-1.967	-.90976	-.92199	-.90720	-.91460	-.91572	-.90838	.00889	.00887	.00966	.00927	1235.59399	1273.06000					
.900	-1.732	-.91059	-.92306	-.92372	-.90900	-.91636	-.90973	.00483	.00490	.00633	.00561	1235.40199	1273.16000					
.900	-1.496	-.91121	-.91195	-.92446	-.90973	-.91709	-.91054	.00528	.00257	.00258	.00278	1235.30099	1273.05000					
.900	-1.261	-.91127	-.91273	-.92540	-.91054	-.91797	-.91116	.00805	.00577	.0062	.00052	1235.23300	1272.98000					
.900	-0.987	-.91315	-.92575	-.92575	-.91116	-.91846	-.91190	.01190	.01014	.00562	.00570	1235.27499	1273.00000					
.900	-0.751	-.91315	-.92538	-.91062	-.91800	-.91587	-.91086	.01190	.01190	.01190	.00982	1235.17700	1272.95000					
.900	-0.516	-.91288	-.91307	-.92560	-.91086	-.91962	-.91344	.01309	.01309	.01309	.01378	1235.26801	1272.89999					
.900	-0.241	-.91322	-.91344	-.92586	-.91114	-.91850	-.91120	.01321	.01321	.01321	.01781	1235.24699	1273.07001					
.900	-0.006	-.91281	-.91324	-.92600	-.91120	-.91860	-.91094	.02371	.02371	.02371	.02188	1235.22600	1272.81000					
.900	.229	-.91274	-.91274	-.92580	-.91094	-.91837	-.91094	.02764	.02764	.02764	.02547	1235.32600	1273.14999					
.900	.504	-.91312	-.92538	-.91097	-.91833	-.91962	-.91097	.03099	.02958	.02958	.02931	.02944	1235.39900	1272.94000				
.900	.739	-.91318	-.92569	-.92569	-.91859	-.91859	-.91859	.03513	.03387	.03387	.03359	1235.28799	1272.92999					
.900	.974	-.91332	-.91332	-.92595	-.91122	-.91967	-.91067	.04002	.03868	.03868	.03816	.03842	1235.38100	1272.91000				
.900	1.210	-.91281	-.91281	-.92547	-.91067	-.91807	-.91071	.04268	.04268	.04268	.04146	.04128	1235.40300	1273.00999				
.900	1.445	-.91274	-.91274	-.92554	-.91071	-.91812	-.91058	.04669	.04669	.04669	.04522	.04481	1235.45799	1272.95000				
.900	1.719	-.91255	-.91255	-.92538	-.91058	-.91798	-.91073	.05209	.05209	.05209	.05052	.05042	1235.44099	1272.92000				
.900	1.955	-.91293	-.91293	-.92558	-.91073	-.91816	-.90056	.05324	.05324	.05324	.05146	.05166	1235.51100	1273.03000				
GRADIENT	.00056	-.00062	-.00063	-.00062	-.00063	-.01609	-.01601	.01324	.01324	.01324	.01611	.01606	.02527	-.02624				

IA310 (AEDEC 16TE-783) PORT MISOBIENT-FAIRING QEF

(UCM027) ( 04 OCT 91 )

## METRIC DATA

	RUN NO.	1305 / O	RN/L =	2.50	GRADIENT INTERVAL =	- 5.00 / 5.00	ALPHA =	- 8.000	BETA =	.000
PHI	DPA CAL	DPA1	DPA2	DPA	DPBC AL	DPB1	DPB2	DPB	PITF	PT2F
-2 .006	-1 .00071	-1 .00467	-1 .00111	-1 .00289	.01361	.01412	.01389	.0145	.17300	.182 .70700
-1 .731	-1 .00197	-1 .00559	-1 .00230	-1 .00394	.00803	.00821	.00847	.0144	.95799	.182 .76100
-1 .496	-1 .00273	-1 .00616	-1 .00277	-1 .00446	.00381	.00488	.00533	.0144	.74300	.182 .49200
-1 .221	-1 .00260	-1 .00603	-1 .00269	-1 .00434	.00116	.00293	.00318	.00306	.144 .78300	.182 .48900
-1 .986	-1 .00205	-1 .00583	-1 .00239	-1 .00411	-.00595	-.00411	-.00373	-.00392	.144 .74600	.182 .21899
-1 .751	-1 .00256	-1 .00618	-1 .00284	-1 .00451	-.01036	-.00844	-.00812	-.00828	.144 .80000	.182 .62801
-1 .516	-1 .00288	-1 .00646	-1 .00288	-1 .00467	-.01477	-.01306	-.01284	-.01262	.144 .97400	.182 .68600
-1 .241	-1 .00242	-1 .00592	-1 .00256	-1 .00424	-.01914	-.01763	-.01739	-.01739	.144 .85600	.182 .57001
-1 .006	-1 .00302	-1 .00657	-1 .00307	-1 .00482	-.02375	-.02216	-.02216	-.02201	.144 .89000	.182 .41000
-1 .229	-1 .00283	-1 .00640	-1 .00307	-1 .00473	-.02825	-.02642	-.02603	-.02623	.145 .64000	.182 .45399
-1 .465	-1 .00265	-1 .00611	-1 .00273	-1 .00442	-.03112	-.02951	-.02938	-.02924	.144 .87199	.182 .82201
-1 .739	-1 .00295	-1 .00664	-1 .00344	-1 .00504	-.03639	-.03541	-.03521	-.03501	.145 .05701	.182 .82201
-1 .975	-1 .00296	-1 .00655	-1 .00335	-1 .00495	-.04134	-.04032	-.04005	-.04005	.144 .94200	.182 .56000
1 .210	-1 .00299	-1 .00653	-1 .00320	-1 .00487	-.04491	-.04363	-.04339	-.04351	.145 .01900	.182 .69400
1 .485	-1 .00261	-1 .00629	-1 .00277	-1 .00453	-.04805	-.04710	-.04685	-.04698	.144 .91499	.182 .33299
1 .720	-1 .00319	-1 .00699	-1 .00367	-1 .00533	-.05465	-.05346	-.05325	-.05325	.145 .12601	.182 .76500
1 .955	-1 .00337	-1 .00696	-1 .00386	-1 .00541	-.05700	-.05597	-.05573	-.05573	.145 .06401	.182 .70700
GRADIENT	- .00035	- .00040	- .00038	- .00038	-.01795	-.01789	-.01791	-.01791	.03861	.01518

BUN No. 1311/8 BN/ = 2.50 GRADIENT INTERVAL = -5.00/5

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

PAGE 680

(UCM027) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1316/0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	ALPHA =	-8.000	BETA =	= .000
MACH	PHI	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.543	-1.967	-1.46468	-1.46435	-1.46165	-1.46300	.01427	.01267	.01356	.01312	1120.31400	1138.00238
1.544	-1.732	-1.46527	-1.46488	-1.46212	-1.46350	.00781	.00655	.00719	.00687	1120.28400	1138.44499
1.543	-1.497	-1.45975	-1.46012	-1.45741	-1.45877	-.00054	-.00020	-.00036	-.00008	1117.56200	1138.51636
1.544	-1.222	-1.45959	-1.45907	-1.45628	-1.45767	-.00340	-.00303	-.00244	-.00273	1117.47501	1137.35884
1.544	.987	-1.46353	-1.46294	-1.46019	-1.46156	-.01246	-.01218	-.01144	-.01181	1117.49899	1137.10646
1.543	-.751	-1.46538	-1.46497	-1.46242	-1.46369	-.01775	-.01726	-.01665	-.01695	1117.38901	1137.76418
1.544	-.477	-1.46452	-1.46411	-1.46133	-1.46272	-.02380	-.02337	-.02278	-.02308	1117.39799	1137.89595
1.543	-.242	-1.45993	-1.45962	-1.45705	-1.45833	-.03268	-.03230	-.03165	-.03198	1117.38901	1138.36505
1.545	-.006	-1.46659	-1.46636	-1.46501	-1.46566	-.03840	-.03808	-.03742	-.03775	1117.36501	1137.80768
1.544	.229	-1.46118	-1.46093	-1.45825	-1.45959	-.04516	-.04480	-.04423	-.04451	1116.51500	1137.89767
1.544	.464	-1.46010	-1.45966	-1.45690	-1.45828	-.05123	-.05069	-.05096	-.05096	1116.29300	1137.86702
1.544	.739	-1.46182	-1.46173	-1.45904	-1.46039	-.05741	-.0570	-.05699	-.05735	1116.36000	1137.53113
1.544	.974	-1.45725	-1.45680	-1.45418	-1.45549	-.06402	-.06371	-.06300	-.06335	1116.25999	1137.87042
1.543	1.209	-1.45826	-1.45781	-1.45517	-1.45649	-.07154	-.07128	-.07064	-.07096	1116.24001	1137.86157
1.544	1.445	-1.45674	-1.45610	-1.45335	-1.45473	-.07651	-.07660	-.07603	-.07632	1116.25000	1137.29039
1.543	1.719	-1.45841	-1.45789	-1.45521	-1.45655	-.08497	-.08482	-.08391	-.08436	1116.25000	1137.35574
1.544	1.994	-1.45663	-1.45619	-1.45484	-1.45530	-.08988	-.08920	-.08954	-.08954	1116.15199	1137.21889
	GRADIENT	.00180	.00186	.00185	.00185	-.02659	-.02646	-.02646	-.02646	-.026303	-.16957



DATA SHEET

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEBC 16TE-783) PORT MISORIENT-FAIRING OFF

(UCM028) ( 04 OCT 91 )

## METRIC DATA

PARAMETRIC DATA

GRADIENT

## PARAMETRIC DATA

RUN NO.	1296 / 0	RN/L =	2 . 50	GRADIENT INTERVAL =	- 5.00 /	5 . 00
DPACAL	DPA1 .02583	DPA2 .02801	DPA .02692	DPBCAL	DPB1 .36086	DPB2 .36086
PHI	.02912	.02708	.02596	.36057	.36101	.36102
MACH	.600	.600	.600	.36137	.36119	.36083
	88 .023	88 .262	88 .500	.02238	.02221	.02209
	.01931	.01786	.01664	.01562	.01446	.01299
	.01460	.01460	.01315	.01315	.01228	.01137
	.01606	.01606	.01606	.01446	.01337	.01299
	.01461	.01461	.01461	.01461	.01461	.01461
	90 .485	90 .762	91 .040	.01132	.00974	.00878
	.00506	.00506	.00506	.00506	.00506	.00506
	.00350	.00350	.00350	.00350	.00350	.00350
	.00153	.00153	.00153	.00153	.00153	.00153
	.00048	.00048	.00048	.00048	.00048	.00048
	.00184	.00184	.00184	.00184	.00184	.00184
	.00135	.00135	.00135	.00135	.00135	.00135
	.00000	.00000	.00000	.00000	.00000	.00000
GRADIENT						

RUN NO. 1302 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/-5.0

## IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(UCM029) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1308/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	
PHI	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
MACH	.03254	.03202	.03400	.03301	.49506	.49374	.49386	.1177. 1182. 45000
	88.02	.02986	.02907	.03100	.49879	.49737	.49753	.1177. 1182. 58299
	88.26	.02733	.02692	.02863	.49897	.49750	.49765	.1177. 1182. 37900
	88.504	.02687	.02622	.02814	.49932	.49766	.49774	.1176. 90300 1182. 22400
	88.782	.02355	.02288	.02455	.49875	.49777	.49790	.1176. 85600 1182. 36301
	89.020							
	89.258	.02073	.02016	.02199	.49921	.49790	.49801	.1177. 11800 1182. 69200
	89.496	.01891	.01814	.02011	.49859	.49735	.49754	.1177. 08400 1182. 46899
	89.774	.01722	.01661	.01837	.49939	.49768	.49775	.1177. 01300 1182. 36900
	90.012	.01394	.01327	.01526	.49870	.49730	.49748	.1176. 92200 1182. 50200
	90.290	.01349	.01286	.01468	.01377	.49899	.49772	.1176. 97600 1182. 55200
	90.489	.01091	.01007	.01199	.01103	.49882	.49752	.49762
	90.766	.00738	.00680	.00857	.00768	.49869	.49744	.49766
	91.044	.00614	.00544	.00731	.00637	.49853	.49737	.49775
	91.243	.00319	.00267	.00451	.00359	.49871	.49724	.49773
	91.521	.00129	.00205	.00167	.00169	.49869	.49719	.49737
	91.759	-.00051	-.00037	-.00044	-.00116	.49838	.49657	.49673
	91.997	-.00228	-.00137	-.00126	.00000	.49856	.49706	.49694
GRADIENT	.00000					.00000	.00000	.00000

	RUN NO.	1313/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	
PHI	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
MACH	.04069	.03943	.04124	.04034	.57277	.57242	.57299	.57270 1160. 79800 1165. 222200
	.03680	.03566	.03748	.03657	.57663	.57626	.57700	.57663 1160. 79800 1165. 35899
	88.028	.03311	.03509	.03410	.57621	.57582	.57622	.57602 1160. 67400 1165. 10500
	88.266	.03387	.03479	.03378	.57643	.57602	.57659	.57630 1160. 64000 1165. 23300
	88.504	.02957	.02833	.03026	.02929	.57623	.57584	.57639
	88.742	.02674	.02569	.02769	.02669	.57641	.57604	.57654
	89.020	.02464	.02339	.02532	.02435	.57570	.57544	.57613
	89.259							
	89.497	.02218	.02102	.02288	.02195	.57644	.57589	.57644
	89.775	.01881	.01786	.01972	.01879	.57592	.57540	.57605
	90.013	.01727	.01908	.01817	.01817	.57599	.57562	.57620
	90.251	.01832	.01727	.01727	.01727	.57649	.57589	.57646
	90.489	.01462	.01356	.01545	.01450	.57570	.57547	.57588
	90.767	.01077	.00961	.01184	.01072	.57570	.57547	.57567
	91.045	.01009	.00899	.01085	.00992	.57581	.57520	.57546
	91.283	.00628	.00502	.00688	.00595	.57583	.57509	.57543
	91.521	.00343	.00243	.00389	.00345	.57584	.57540	.57573
	91.759	.00131	.00113	.00113	.00111	.57554	.57527	.57607
	91.998	.00090	.00000	.00000	.00000	.57561	.57520	.57557
GRADIENT	.00000					.00000	.00000	.00000

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 686

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(UCM029) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1318/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	BETA =	4.000	
MACH	PHI	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
1.543	88.025	.02209	.02372	.02265	.58537	.58291	.58324	.58308	1115.46300	1136.83591	
1.543	88.263	.01343	.01312	.01415	.58970	.58731	.58786	.58758	1115.44000	1136.88455	
1.544	88.502	.01172	.01149	.01249	.59103	.58859	.58900	.58880	1115.38300	1136.62184	
1.543	88.740	.01016	.00983	.01196	.01090	.59029	.58791	.58829	.58810	1115.42599	1136.79189
1.543	89.018	.00596	.00597	.00697	.59068	.58808	.58854	.58831	1115.37900	1137.09685	
1.544	89.256	.00346	.00322	.00513	.59120	.58968	.58900	.58884	1115.32201	1137.05026	
1.543	89.494	.00112	.00168	.00299	.00234	.59145	.58906	.58947	.58926	1115.33200	1137.13931
1.543	89.772	.00282	.00126	.00092	.00109	.59041	.58793	.58839	.58816	1115.25400	1137.14450
1.544	90.010	.00375	.00249	.00203	.00226	.59124	.58877	.58917	.58897	1115.27400	1136.54446
1.543	90.288	.00567	.00437	.00393	.00415	.59037	.58775	.58822	.58799	1115.24100	1136.88313
1.543	90.526	.00825	.00685	.00626	.00656	.59049	.58806	.58848	.58827	1115.22701	1136.58105
1.544	90.764	.01310	.01170	.00960	.01065	.59003	.58760	.58798	.58779	1115.20399	1136.98128
1.543	91.042	.01477	.01330	.01130	.01126	.01228	.59034	.58778	.58797	1115.14999	1137.18509
1.543	91.280	.01496	.01385	.01184	.01285	.58975	.58718	.58758	.58738	1115.16000	1136.77542
1.543	91.519	.02120	.01980	.01789	.01884	.58921	.58654	.58697	.58675	1115.10300	1136.86838
1.543	91.757	.02061	.01945	.01731	.01838	.58965	.58709	.58755	.58732	1115.07899	1136.84315
1.543	92.035	.02331	.02208	.02005	.02106	.59005	.58725	.58788	.58756	1115.11301	1137.02950
GRADIENT		.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	

	RUN NO.	1351/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000	
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
5.98	-8.099	-75924	-75943	-76087	-36642	-36446	-36440	-36443	1558.29601	1596.42000	
6.00	-7.097	-66399	-66437	-66579	-36262	-36015	-36034	-36024	1566.04900	1596.62000	
5.99	-6.117	-57428	-57708	-57565	-36000	-35940	-35948	-35944	1572.62601	1596.67000	
6.00	5.142	-48297	-48406	-48145	-35876	-35815	-35750	-35732	-35741	1578.13800	1596.78999
6.00	-4.164	-38948	-38856	-38987	-35401	-35435	-35336	-35385	1582.80099	1596.88000	
6.01	-3.198	-29865	-30047	-29934	-35307	-35331	-35252	-35292	1586.37100	1597.17999	
6.01	-2.235	-20722	-20861	-20759	-35556	-35585	-35502	-35543	1589.27699	1597.28999	
6.00	-1.264	-11353	-11147	-11250	-36039	-35863	-35879	-35871	1591.27200	1596.84000	
6.01	-0.275	-01888	-01923	-01833	-36691	-36497	-36518	-36507	1592.41800	1597.38000	
6.00	.716	07311	07256	07404	07330	06965	06806	06834	06820	1592.86200	1597.45000
6.00	1.739	16923	16877	16968	17060	17349	17372	17361	17361	1596.91901	1596.60001
GRADIENT		.09484	.09495	.09510	.09502	.00387	.00350	.00375	.00362	.008361	-.00855

	RUN NO.	1351/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000	
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
5.98	-8.099	-76232	-66437	-66579	-36262	-36015	-36034	-36024	1566.04900	1596.62000	
6.00	-7.097	-66399	-57428	-57708	-36000	-35940	-35948	-35944	1572.62601	1596.67000	
5.99	-6.117	-57428	-48297	-48406	-35876	-35815	-35750	-35732	-35741	1578.13800	1596.78999
6.00	5.142	-48297	-48406	-48145	-35876	-35815	-35750	-35732	-35741	1578.13800	1596.78999
6.00	-4.164	-38948	-39119	-38856	-35401	-35435	-35336	-35385	1582.80099	1596.88000	
6.01	-3.198	-29865	-30047	-29934	-35307	-35331	-35252	-35292	1586.37100	1597.17999	
6.01	-2.235	-20722	-20861	-20759	-35556	-35585	-35502	-35543	1589.27699	1597.28999	
6.00	-1.264	-11353	-11147	-11250	-36039	-35863	-35879	-35871	1591.27200	1596.84000	
6.01	-0.275	-01888	-01923	-01833	-36691	-36497	-36518	-36507	1592.41800	1597.38000	
6.00	.716	07311	07256	07404	07330	06965	06806	06834	06820	1592.86200	1597.45000
6.00	1.739	16923	16877	16968	17060	17349	17372	17361	17361	1596.91901	1596.60001
GRADIENT		.09484	.09495	.09510	.09502	.00387	.00350	.00375	.00362	.008361	-.00855

(UCM030)

(04 OCT 91)

PARAMETRIC DATA

PARAMETRIC DATA

PARAMETRIC DATA									
	RUN NO.	1341/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	-4.000 PHI = 180.000
MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB 1	DPB2	PTTF
.800	-8.063	-90720	-90922	-90639	-90781	-44785	-44700	-44718	1298.92400 1342.38000
.799	-7.056	-79355	-79549	-79282	-79416	-44026	-43887	-43859	1307.70700 1342.11000
.800	-6.067	-68368	-68563	-68267	-68420	-43853	-43577	-43558	1314.77100 1342.27000
.800	-5.088	-57251	-57436	-57189	-57313	-43491	-43233	-43228	1320.96800 1342.06000
.800	-4.103	-46038	-46169	-45911	-46040	-43094	-42829	-42825	1326.14101 1341.88000
.800	-3.132	-35247	-35294	-35068	-35181	-42779	-42599	-42597	1330.34500 1342.25000
.800	-2.158	-24013	-24064	-23846	-23955	-42967	-42794	-42805	1333.36501 1341.92999
.800	-1.185	-12968	-12842	-12647	-12745	-43300	-43118	-43123	1335.60500 1342.00999
.800	-1.188	-01756	-01911	-01756	-01667	-43773	-43593	-43583	1336.85699 1342.05000
.800	.802	-09491	-09438	-09599	-09518	-43974	-43820	-43813	-43817 1337.52901 1342.05000
.800	1.818	-20950	-20937	-21056	-20997	-44631	-44468	-44459	1337.57300 1342.07001
	GRADIENT	.11323	.11343	.11321	.11332	.00284	.00294	.00295	.001050
MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB 1	DPB2	PTTF
.900	-8.058	-93599	-93920	-93617	-93769	-46082	-46055	-46026	1230.26300 1273.17000
.900	-7.048	-8.1894	-8.2089	-8.1786	-8.1938	-45290	-45209	-45208	1238.44299 1272.80000
.899	-6.066	-70396	-70620	-70319	-70470	-45314	-45178	-45179	1245.44299 1272.67000
.899	-5.081	-58970	-59142	-58841	-58992	-45029	-44832	-44822	1251.11501 1272.99001
.900	-4.105	-47572	-47294	-47433	-47433	-44556	-44359	-44326	1257.53799 1273.06000
.900	-3.133	-36323	-36071	-36202	-36202	-44201	-43957	-43921	-43939 1261.64999 1272.84000
.900	-2.163	-24848	-24668	-24798	-24798	-44267	-44140	-44115	-44128 1264.96500 1273.27000
.900	-1.192	-13459	-13356	-13143	-13249	-44511	-44405	-44382	-44393 1266.92700 1272.97000
.900	-1.197	-01851	-01811	-01609	-01710	-45125	-44962	-44973	-44968 1268.01500 1272.70000
.900	.789	-0.9794	-0.9728	.09902	.09815	-45454	-45304	-45313	-45309 1268.76801 1272.89000
.900	1.806	-2.1678	-2.1726	-2.1846	-2.1786	-46062	-45920	-45937	-45929 1268.87199 1272.91000
	GRADIENT	.11711	.11732	.11706	.11719	.00287	.00299	.00309	.003340
MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB 1	DPB2	PTTF
1.098	-8.001	-94406	-94364	-94506	-94545	-47951	-47945	-47948	1163.96201 1205.59000
1.099	-6.974	-82255	-82382	-82098	-82240	-47476	-47355	-47353	-47354 1171.60600 1205.19000
1.099	-5.985	-70708	-70922	-70726	-70774	-47012	-46911	-46910	1178.36700 1204.79700
1.100	-4.996	-58966	-59061	-58786	-58924	-46879	-46666	-46667	-46667 1184.49500 1204.24001
1.100	-4.007	-47072	-47098	-46835	-46967	-46240	-46037	-46060	-46049 1189.37100 1204.49400
1.101	-3.022	-35420	-35511	-35267	-35389	-45851	-45604	-45623	-45614 1193.59900 1204.78700
1.101	-2.040	-23644	-23854	-23625	-23740	-45675	-45423	-45445	-45434 1196.58501 1204.53000
1.100	-1.036	-1591	-11719	-11499	-11609	-45599	-45339	-45356	-45348 1198.93100 1204.63699
1.100	-0.075	-00263	-00345	-00338	-00341	-45815	-45580	-45612	-45596 1200.16100 1204.83400
1.100	.932	-1567	-11440	-11588	-11514	-45702	-45490	-45472	-45472 1200.90500 1204.61501
1.100	1.936	-23542	-23586	-23701	-23644	-46081	-45881	-45858	-45858 1200.98300 1204.84500
	GRADIENT	.11905	.11898	.11876	.11890	.00102	.00107	.00104	.06120

IA310 (WEDC 16TE-782) FAIRING OFF DATABASE

ENCL C (AEC 150717Z JUN 19) TAKING OF DATABASE

(UCM030) ( 04 Oct 91 )

RUN NO.	1365/ 0	RN/L =	2.50	GRADIENT INTERVAL =	- 5.00/ 5.00	BETA =	- 4.000	PHI =	- 180.000	
MACH	DPA CAL	DPA 1	DPA 2	DPA	DPCAL	DPB 1	DPB 2	DPB	PTTF	PT2F
ALPHA	- 8 .047	- 1 .02997	- 1 .03928	- 1 .02997	- 1 .03462	- .51676	- .51673	- .51672	- 1182 .6622	- 1182 .6622
	- 8 .249	- .90162	- .90984	- .90060	- .90522	- .50491	- .50331	- .50336	- 1182 .4050	- 1182 .4050
	- 7 .037	- .77662	- .78332	- .77436	- .77884	- .50559	- .50439	- .50435	- 1182 .2630	- 1182 .2630
	- 6 .046	- .65167	- .65954	- .65076	- .65515	- .50138	- .49980	- .49994	- 1161 .89700	- 1182 .8719
	- 5 .062	- .52140	- .52909	- .52053	- .52481	- .49466	- .49340	- .49345	- 1167 .2740	- 1182 .2740
	- 4 .083	- .39405	- .40147	- .39298	- .39723	- .49097	- .49009	- .49015	- 1170 .2740	- 1182 .3040
	- 3 .106	- .26953	- .27637	- .26827	- .27232	- .48996	- .48936	- .48951	- 1170 .0580	- 1182 .0580
	- 2 .129	- .14539	- .15081	- .14280	- .14681	- .49270	- .49179	- .49192	- 1174 .75301	- 1182 .4880
	- 1 .148	- .01574	- .01512	- .01338	- .01725	- .49855	- .49746	- .49760	- 1176 .42500	- 1182 .3660
	- 1 .153	- .842	- .11235	- .10532	- .11258	- .10895	- .10466	- .10470	- 1177 .07001	- 1182 .3900
	- 1 .250	1 .853	.24448	.23724	.24448	.24086	.50555	.50470	.50488	.50488
GRADIENT	12872	12888	128863	12876	128863	12876	100219	100224	100222	100222

卷之三

JN NO. 1388 / O RN/L = 2.49 GRADIENT INTERVAL = -5.00/-5.00

	GRADIENT	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PITF	PT2F
AACH	ALPHA	-8.093	-1.25184	-1.25432	-1.25074	-1.25253	-1.61246	-6.61170	-6.61134	-6.61301
		-4.49	-7.082	-1.09504	-1.09797	-1.09439	-1.09618	-5.9976	-5.9985	-5.9995
		-4.50	-6.101	-9.4769	-9.5081	-9.4758	-9.4919	-6.0059	-6.0124	-6.0123
		-4.50	-5.120	-7.9493	-7.9712	-7.9396	-7.9554	-5.9804	-5.9802	-5.9803
		-4.50	-4.148	-6.4132	-6.4319	-6.4025	-6.4172	-5.9314	-5.9257	-5.9262
		-4.50	-3.177	-4.9144	-4.9258	-4.9012	-4.9135	-5.9440	-5.9442	-5.9445
		-4.50	-2.212	-3.4332	-3.4476	-3.4234	-3.4355	-6.0059	-6.0076	-6.0095
		-4.50	-1.242	-1.8961	-1.9060	-1.8853	-1.8956	-6.0588	-6.0603	-6.0620
		-4.50	-1.246	-0.3297	-0.3207	-0.3040	-0.3123	-6.1583	-6.1623	-6.1617
		-4.50	-1.742	-1.2951	-1.2557	-1.2678	-1.2618	-6.2203	-6.2205	-6.2200
		-4.50	1.764	-0.28957	-0.28987	-0.29079	-0.29033	-6.3041	-6.3020	-6.3049
		-4.50	1.5748	-1.5789	-1.5755	-1.5772	-0.0663	-0.0667	-0.0667	-0.0667

PARAMETRIC DATA									
RUN NO.					BETA = -4.000 PHI = 180.000				
RN/L = 2.49		GRADIENT INTERVAL = -5.00/ 5.00			RN/L = 2.49		GRADIENT INTERVAL = -5.00/ 5.00		
RN	L	DPA1	DPA2	DPA	DPA1	DPA2	DPA	DPB1	DPB2
1	471	DPACAL	-1.29423	-1.29034	-1.29229	-1.29034	-1.29229	-6.4079	-6.4068
2	471	ALPHA	-1.29137	-1.13613	-1.13798	-1.13613	-1.13798	-6.3007	-6.3010
3	471	GRADIENT	-1.13801	-1.13983	-1.13982	-1.13801	-1.13983	-6.3255	-6.3257
4	471	AACH	-8.080	-6.089	-9.8594	-9.8962	-9.8788	-6.3255	-6.3255
5	471	ALPHA	-7.070	-5.106	-8.2208	-8.2482	-8.2315	-6.2605	-6.2578
6	471	GRADIENT	-5.134	-6.6372	-6.6589	-6.6267	-6.6428	-6.1983	-6.1943
7	471	AACH	-3.162	-5.0993	-5.0991	-5.0707	-5.0709	-6.1567	-6.1607
8	471	ALPHA	-2.193	-3.4922	-3.5028	-3.4772	-3.4900	-6.1973	-6.2011
9	471	GRADIENT	-1.225	-1.9263	-1.9377	-1.9159	-1.9268	-6.2202	-6.2259
10	470	AACH	-2.227	-0.3082	-0.3174	-0.2982	-0.3078	-6.3046	-6.3137
11	470	ALPHA	-765	-1.3084	-1.3044	-1.3191	-1.3118	-6.3981	-6.4032
12	470	GRADIENT	1.785	-2.9649	-2.9863	-2.9979	-2.9921	-6.4969	-6.5036
13	470	AACH	1.800	-1.6293	-1.6258	-1.6276	-1.6276	-0.00552	-0.00544
14	470	ALPHA	1.800	-1.7167	-1.7175	-1.7143	-1.7159	-0.00553	-0.00549
15	470	GRADIENT	1.7167	-1.7175	-1.7143	-1.7159	-0.00553	-0.00552	-0.00549
16	471	AACH	1433/ 0	RN/L =	2.49	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	GRADIENT INTERVAL = -5.00/ 5.00
17	471	ALPHA	1400/ 0	RN/L =	2.49	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	GRADIENT INTERVAL = -5.00/ 5.00
18	471	GRADIENT	1421/ 0	RN/L =	2.50	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	GRADIENT INTERVAL = -5.00/ 5.00
19	471	AACH	DPACAL	DPA1	DPA2	DPA	DPA1	DPBCAL	DPB1
20	471	ALPHA	-8.080	-1.33225	-1.33438	-1.33009	-1.33224	-6.6571	-6.6514
21	471	GRADIENT	-7.064	-1.17458	-1.17624	-1.17215	-1.17419	-6.5834	-6.5348
22	495	AACH	-6.080	-1.02862	-1.03082	-1.02705	-1.02893	-6.5746	-6.5682
23	495	ALPHA	-5.097	-0.87055	-0.87050	-0.86701	-0.86875	-6.6146	-6.6101
24	495	GRADIENT	-4.121	-0.70223	-0.70303	-0.70136	-0.69968	-6.5607	-6.5540
25	495	AACH	-3.152	-0.53395	-0.53456	-0.53170	-0.53313	-6.5328	-6.5284
26	495	ALPHA	-2.183	-0.37194	-0.37212	-0.36938	-0.37075	-6.5861	-6.5798
27	495	GRADIENT	-1.209	-0.20626	-0.20653	-0.20400	-0.20526	-6.6433	-6.6359
28	496	AACH	-2.114	-0.03612	-0.03472	-0.03252	-0.03365	-6.7233	-6.7140
29	496	ALPHA	-780	-1.3960	-1.3871	-1.4061	-1.3966	-6.7815	-6.9329
30	496	GRADIENT	1.800	-0.31593	-0.31553	-0.31682	-0.31617	-6.8573	-6.9312
31	495	AACH	1.800	-1.7167	-1.7175	-1.7143	-1.7159	-0.00553	-0.00552
32	495	ALPHA	1.800	-1.7167	-1.7175	-1.7143	-1.7159	-0.00553	-0.00552
33	471	GRADIENT	1421/ 0	RN/L =	2.50	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	GRADIENT INTERVAL = -5.00/ 5.00
34	471	AACH	DPACAL	DPA1	DPA2	DPA	DPA1	DPBCAL	DPB1
35	471	ALPHA	-8.074	-1.48517	-1.48690	-1.48269	-1.48480	-7.2795	-7.2688
36	517	GRADIENT	-7.062	-1.39426	-1.39643	-1.39224	-1.39434	-7.6939	-7.6766
37	521	AACH	-6.081	-1.20874	-1.21072	-1.20674	-1.20873	-7.6763	-7.6732
38	520	ALPHA	-5.103	-1.01520	-1.01816	-1.01520	-1.01710	-7.5758	-7.5802
39	518	GRADIENT	-5.103	-0.83129	-0.82937	-0.82781	-0.82955	-7.6451	-7.6458
40	519	AACH	-4.122	-0.64479	-0.64442	-0.64393	-0.64311	-7.7707	-7.7611
41	519	ALPHA	-3.154	-0.44928	-0.44808	-0.44526	-0.44667	-7.7636	-7.7490
42	519	GRADIENT	-2.182	-0.24729	-0.24990	-0.25000	-0.24860	-7.7876	-7.7726
43	518	AACH	-1.207	-0.04980	-0.04672	-0.04880	-0.04776	-7.8052	-7.7912
44	518	ALPHA	-2.13	-0.4980	-0.4672	-0.4880	-0.4776	-7.80123	-7.77938
45	518	GRADIENT	-1.779	-0.15153	-0.15253	-0.15074	-0.15163	-0.80285	-0.80119
46	519	AACH	-1.779	-0.36023	-0.36051	-0.36093	-0.36072	-0.81915	-0.81784
47	519	ALPHA	1.799	-0.20120	-0.20167	-0.20144	-0.20144	-0.00798	-0.00783
48	519	GRADIENT	20167	-0.00783	-0.00778	-0.00783	-0.00783	-0.00780	-0.00780

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 690

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM030) ( 04 OCT 91 )

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.543	-8.078	-1.54016	-1.54234	-1.53834	-1.54034	-1.73849	-1.73911	-.73890	1113.34399	1136.68695
1.543	-7.069	-1.28728	-1.29001	-1.28592	-1.28797	-1.71491	-1.71569	-.71518	1116.18500	1136.98520
1.543	-5.101	-9.1112	-9.1372	-9.1008	-9.1190	-69203	-69177	-.69175	1119.81599	1136.52553
GRADIENT	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM031) ( 04 OCT 91 )

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.517	-8.074	-1.46501	-1.46767	-1.46362	-1.46565	-1.71831	-1.71733	-.71677	1097.52100	1138.81413
1.517	-7.066	-1.33762	-1.33886	-1.33473	-1.33679	-73077	-72931	-.72922	1097.50999	1137.25909
1.516	-6.081	-1.17615	-1.17692	-1.17292	-1.17492	-74267	-74167	-.74157	1097.49600	1138.24176
1.516	-5.103	-1.00013	-1.00158	-1.00013	-1.00158	-99979	-99979	-.74488	1097.72800	1138.18671
1.517	-4.124	-8.16118	-8.1620	-8.1307	-8.1464	-74850	-74752	-.74752	1097.67999	1137.63170
1.516	-3.155	-6.2291	-6.2384	-6.2054	-6.2219	-75573	-75456	-.75463	1097.71001	1137.43799
1.516	-2.182	-4.43631	-4.3549	-4.3273	-4.3411	-76940	-76850	-.76859	1097.68700	1137.59578
1.516	-1.210	-2.210	-2.4046	-2.4111	-2.3881	-73996	-78600	-.78564	1097.67300	1137.84906
1.517	-2.11	-0.37645	-0.3794	-0.3604	-0.3699	-03699	-79765	-.79673	1097.65800	1137.23770
1.516	.780	.16601	.16553	.16720	.16636	-80292	-80198	-.80220	1121.50000	1136.94785
1.516	1.798	.36147	.36190	.36281	.36236	-79194	-79066	-.79098	1121.46700	1137.21849
GRADIENT	.19957	.19961	.19922	.19941	.00913	.00913	.00912	-.00912	5.18480	-.09368

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.542	-8.071	-1.52362	-1.52513	-1.52094	-1.52304	-1.73756	-1.73800	-.73789	1112.88499	1136.25537
1.543	.7.065	-1.28204	-1.28410	-1.28016	-1.28213	-71270	-71276	-.71204	1115.46201	1135.81503
1.542	-6.079	-1.10274	-1.10274	-1.09902	-1.10088	-70167	-70170	-.70100	1113.93600	1136.11693
1.542	-5.097	-9.1023	-9.1264	-9.0906	-9.1085	-69572	-69558	-.69554	1119.35500	1135.98341
1.543	-4.125	-7.1479	-7.1544	-7.1194	-7.1369	-68538	-68482	-.68478	1119.48300	1135.71277
1.542	-3.153	-5.29117	-5.2911	-5.2621	-5.2766	-67225	-67250	-.67263	1120.32899	1135.88368
1.542	-2.182	-3.5438	-3.5437	-3.5176	-3.5307	-65354	-65282	-.65295	1121.39101	1135.94174
1.542	-1.210	-1.9014	-1.8976	-1.8740	-1.8858	-62943	-62841	-.62857	1122.03900	1135.94958
1.542	-2.113	-0.3197	-0.3055	-0.2869	-0.2962	-62559	-62371	-.62377	1122.43201	1135.71631
1.543	.781	.13352	.13281	.13432	.13357	-64664	-64565	-.64582	1122.85899	1136.12144
1.543	1.797	.31841	.31869	.31979	.31924	-67870	-67853	-.67900	1122.98300	1135.73705
GRADIENT	.17196	.17196	.17206	.17167	.17186	.00351	.00360	-.00353	.00356	.00356

.01139

(UCM032) ( 04 OCT 91 )

PARAMETRIC DATA

RUN NO.		RN/L = 0		GRADIENT INTERVAL = -5.00/ 5.00		BETA = -3.000		PHI = 180.000	
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.599	-8.031	-.74599	-.74882	-.74622	-.74752	-.27957	-.27784	1561.08701	1597.30000
.600	-7.070	-.65739	-.66015	-.65744	-.65879	-.26657	-.26624	1568.53400	1597.30000
.600	-6.088	-.56724	-.56922	-.56665	-.56794	-.26460	-.26494	1575.19800	1597.28000
.600	-5.106	-.47365	-.47469	-.47211	-.47340	-.26072	-.26051	1581.08600	1596.64999
.601	-4.134	-.38376	-.38435	-.38191	-.38313	-.26028	-.26045	1588.88200	1597.55000
.601	-3.169	-.29370	-.29185	-.29150	-.29260	-.26043	-.26019	1588.88200	1597.23000
.601	-2.214	-.20253	-.20012	-.20024	-.20139	-.26125	-.26121	1591.46201	1597.25999
.601	-1.261	-.11108	-.11108	-.11106	-.11113	-.26376	-.26350	1593.20200	1596.98000
.601	-0.285	-.02118	-.02184	-.02007	-.02095	-.27107	-.27056	1594.322401	1597.50999
.601	.713	.07066	.06994	.07154	.07074	-.27750	-.27752	1594.77499	1596.71001
.600	1.751	.16763	.16842	.17032	.16937	-.28529	-.28488	1594.94200	1597.38000
.601	GRADIENT	.09354	.09384	.09372	.09378	-.00440	-.004430	.1.58036	-.04678
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.799	-8.047	-.89613	-.89842	-.89579	-.89710	-.33863	-.33838	1301.76401	1342.07001
.800	-7.036	-.78444	-.78558	-.78299	-.78428	-.32946	-.32855	1310.06100	1341.98000
.800	-6.046	-.67601	-.67795	-.67520	-.67657	-.32377	-.32200	1317.95399	1342.17999
.800	-5.059	-.56280	-.56495	-.56227	-.56361	-.32052	-.31853	1324.8701	1341.88000
.800	-4.081	-.45277	-.45390	-.45153	-.45227	-.31746	-.31581	1329.09200	1341.89999
.800	-3.109	-.34386	-.34536	-.34308	-.34422	-.31743	-.31608	1332.93401	1341.94000
.800	-2.144	-.23619	-.23386	-.23610	-.23498	-.31557	-.31449	1335.93401	1341.80000
.800	-1.182	-.12710	-.12608	-.12420	-.12514	-.31747	-.31698	1337.94800	1342.03999
.800	-2.200	-.01838	-.01684	-.01513	-.01598	-.32417	-.32354	1339.12100	1341.84000
.800	-7.97	-.09107	-.09135	-.09278	-.09206	-.33002	-.32926	1339.70599	1342.09000
.800	1.824	.20779	.20795	.20902	.20848	-.33649	-.33584	1339.65800	1342.00000
.800	GRADIENT	.11174	.11206	.11184	.11195	-.00332	-.00349	.00355	.02333
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.900	-8.078	-.92868	-.93190	-.92858	-.93024	-.34909	-.34982	1233.16100	1273.19000
.900	-7.025	-.81015	-.81192	-.80894	-.81043	-.33457	-.33489	1241.41400	1272.78000
.899	-6.037	-.69761	-.69920	-.69613	-.69767	-.33234	-.33235	1248.92799	1273.00000
.900	-5.053	-.58208	-.58367	-.58055	-.58211	-.32960	-.32833	1255.45700	1272.96001
.900	-4.082	-.46745	-.46855	-.46576	-.46716	-.32663	-.32531	1260.24100	1273.14000
.900	-3.110	-.35630	-.35696	-.35436	-.35566	-.32591	-.32480	1264.24100	1273.17000
.900	-2.146	-.24233	-.24170	-.24004	-.24118	-.32618	-.32502	1267.14000	1272.89999
.900	-1.188	-.13185	-.13097	-.12876	-.12986	-.32711	-.32616	1269.00101	1272.85001
.900	-2.08	-.01823	-.01708	-.01500	-.01604	-.33409	-.33308	1273.00000	1273.12000
.900	7.83	.09444	.09624	.09534	.09505	-.33984	-.33980	1270.87199	1273.03000
.810	GRADIENT	.11574	.11590	.21435	.21416	-.34908	-.34739	1270.89500	1272.72000
.899	GRADIENT	.11574	.11590	.21435	.21416	-.00387	-.00379	1.75562	-.04837

DATE 04 OCT 91

IA31O (AEDC 16TF-783) TABULATED DATA

## IA31O (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 692

(UCM032) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1321/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	-3.000	PHI =	180.000	DPB	DPB2	PTTF	PT2F
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB2	PTTF	PT2F
1.099	-8.036	-93816	-94082	-93797	-93940	-37048	-36762	-36755	-36758	1165	63600	1204	94400
1.100	-6.965	-81641	-81792	-81517	-81654	-35341	-35340	-35244	-35292	1174	37399	1204	90601
1.100	-5.978	-70169	-70321	-70043	-70182	-34992	-34982	-34882	-34932	1181	25900	1204	73100
1.101	-4.983	-58330	-58459	-58189	-58324	-34618	-34642	-34605	-34623	1187	50200	1204	70599
1.100	-3.997	-46632	-46658	-46523	-46588	-34295	-34183	-34176	-34179	1192	36800	1204	62700
1.100	-3.011	-35007	-35163	-34910	-35037	-34024	-33873	-33886	-33880	1196	20599	1204	46800
1.100	-2.033	-23190	-23352	-23115	-23233	-33671	-33551	-33548	-33549	1199	16800	1204	65100
1.100	-1.052	-11483	-11399	-11399	-11498	-33527	-33394	-33416	-33405	1201	15900	1204	72501
1.099	-0.054	-00057	-00044	-00037	-00041	-33706	-33558	-33574	-33566	1202	32100	1204	83400
1.100	-0.925	-11077	-10935	-11086	-11010	-33879	-33732	-33741	-33737	1202	69701	1204	44299
1.100	1.921	-22897	-23064	-22967	-23015	-34241	-34136	-34146	-34141	1203	04601	1204	75400
GRADIENT		1.1760	.11777	.11746	.11761	.00070	.00083	.00078	.00080	.2	.18245	.00712	
RUN NO.	1366/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00									
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB2	PTTF	PT2F
1.250	-8.037	-1.01878	-1.02863	-1.01913	-1.02388	-3.8067	-3.7917	-3.7911	-3.7914	1142	4.1299	1182	70500
1.250	-7.016	-89386	-90215	-89291	-89753	-37537	-37390	-37373	-37381	1150	64900	1182	68401
1.250	-6.028	-76879	-77704	-76804	-77254	-37455	-37312	-37313	-37313	1158	45000	1182	
1.250	-5.043	-64097	-64897	-64010	-64453	-36828	-36774	-36766	-36770	1164	73599	1182	14799
1.250	-4.065	-51304	-52048	-51177	-51613	-36266	-36178	-36191	-36185	1168	72600	1182	79900
1.250	-3.086	-38980	-39643	-38798	-39221	-36074	-35986	-35985	-35985	1172	56500	1182	81300
1.250	-2.115	-26406	-26325	-27153	-26739	-35983	-35873	-35886	-35879	1175	73900	1182	42400
1.250	-1.149	-14080	-14693	-13898	-14295	-36067	-35972	-35978	-35978	1177	58299	1182	41600
1.250	-0.160	-01478	-02077	-01303	-01690	-36795	-36795	-36697	-36697	1178	59700	1182	35800
1.250	.833	-11040	-10304	-11046	-10675	-37347	-37202	-37202	-37216	1179	70200	1182	72900
1.250	1.859	-23954	-23329	-24033	-23681	-38131	-38036	-38057	-38047	1179	75200	1182	88200
GRADIENT		1.2724	.12737	.12710	.12723	.00326	.00321	.00321	.00323	.1	.81639	.00135	
RUN NO.	1377/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00									
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB2	PTTF	PT2F
1.400	-8.024	-1.16184	-1.16156	-1.16143	-1.16330	-4.3024	-4.3127	-4.3103	-4.3115	1123	1.1800	1164	64000
1.400	-7.012	-1.02278	-1.02212	-1.02212	-1.02395	-4.2438	-4.2464	-4.2438	-4.2451	1132	4.1100	1164	33600
1.400	-6.022	-88224	-88439	-88096	-88267	-4.2137	-4.2060	-4.2046	-4.2053	1139	68100	1163	98199
1.400	-5.035	-73405	-73557	-73237	-73397	-4.2003	-4.1959	-4.1930	-4.1945	1145	4.3201	1164	10201
1.400	-4.052	-59049	-59374	-59049	-59212	-4.1768	-4.1692	-4.1670	-4.1681	1150	69600	1164	53000
1.400	-3.074	-44700	-44863	-44599	-44731	-4.1590	-4.1598	-4.1598	-4.1590	1155	14999	1164	32300
1.400	-2.101	-30327	-30587	-30351	-30469	-4.1273	-4.1290	-4.1300	-4.1295	1157	98199	1164	33900
1.400	-1.133	-16236	-16142	-15910	-16026	-4.1279	-4.1321	-4.1313	-4.1317	1159	38300	1163	99001
1.400	-1.146	-01913	-01768	-01675	-01675	-4.2055	-4.2089	-4.2098	-4.2094	1160	25301	1163	81300
1.400	.846	-12613	-12518	-12602	-12602	-4.2682	-4.2723	-4.2743	-4.2733	1161	44200	1164	34200
1.400	1.876	-27670	-27609	-27673	-27673	-4.3831	-4.3831	-4.3831	-4.3828	1162	19099	1164	67200
GRADIENT		1.4621	.14668	.14639	.14653	.00337	.00346	.00346	.00348	.1	.78513	.00111	

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM032) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		RN/L = 1389/ 0		GRADIENT INTERVAL = -5.00/ 5.00		BETA = -3.000		PHI = 180.000	
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.450	-8.066	-1.23924	-1.24134	-1.23977	-4.4998	-4.4833	-4.4807	-4.4820	1117.08501
1.451	-7.052	-1.08542	-1.08820	-1.08652	-4.4672	-4.4482	-4.4422	-4.4452	1125.10100
1.450	-6.070	-94019	-94339	-94002	-94170	-43677	-43659	-43638	1158.66600
1.450	-5.086	-78185	-78428	-78104	-78266	-43687	-43725	-43697	1158.14600
1.450	-4.118	-63466	-63652	-63384	-63518	-43697	-43753	-43720	1158.35100
1.449	-3.146	-49123	-49140	-48871	-49005	-43675	-43725	-43707	1158.91100
1.450	-2.194	-33781	-33893	-33672	-33783	-43557	-43555	-43525	52901
1.450	-1.241	-18529	-18634	-18418	-18526	-43848	-43864	-43847	1158.33800
1.450	-259	-0.3126	-0.3169	-0.3004	-0.3087	-45040	-44956	-44973	1158.30701
1.450	-741	.12206	.12171	.12315	.12243	.46278	.46162	.46186	14200
1.450	1.777	.28224	.28465	.28554	.28509	.47808	.47724	.47742	1158.21800
GRADIENT	.15638	.15687	.15656	.15671	.00699	.00699	.00679	.00674	1.86309 -.06876
RUN NO.		RN/L = 1434/ 0		GRADIENT INTERVAL = -5.00/ 5.00		BETA = -3.000		PHI = 180.000	
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.470	-8.056	-1.28032	-1.28302	-1.27907	-1.28105	-47134	-47155	-47126	1111.53700
1.471	-7.049	-1.13278	-1.13480	-1.13107	-1.13294	-46330	-46338	-46330	1121.39000
1.471	-6.062	-97542	-97963	-97600	-97781	-45822	-45899	-45898	1129.65129
1.471	-5.079	-81565	-81848	-81510	-81679	-45253	-45303	-45306	1129.01132
1.471	-4.102	-65731	-65939	-65622	-65781	-45117	-45124	-45140	1149.97279
1.470	-3.136	-50175	-50183	-49908	-50045	-44796	-44764	-44768	1138.45200
1.470	-2.174	-34404	-34443	-34196	-34319	-45000	-44952	-44970	1149.05571
1.470	-1.219	-18910	-18864	-19103	-18984	-45668	-45601	-45620	1143.71600
1.471	-238	-0.3102	-0.3189	-0.3010	-0.3100	-46933	-46897	-46918	1149.30636
1.471	.757	.12802	.12772	.12920	.12846	.48259	.48230	.48249	1147.57600
1.471	1.796	.29357	.29545	.29671	.29608	.49357	.49265	.49297	1148.28101
GRADIENT	.16139	.16179	.16147	.16163	.00790	.00790	.00783	.00781	1.66754 .08830
RUN NO.		RN/L = 1401/ 0		GRADIENT INTERVAL = -5.00/ 5.00		BETA = -3.000		PHI = 180.000	
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.496	-8.059	-1.32339	-1.32556	-1.32119	-1.32337	-49186	-48989	-48959	1114.18500
1.496	-7.038	-1.17196	-1.17312	-1.16916	-1.17114	-48828	-48720	-48706	1114.26199
1.495	-6.053	-1.02528	-1.02773	-1.02376	-1.02575	-48847	-48709	-48686	1114.21899
1.496	-5.073	-86223	-86201	-85858	-86029	-48505	-48398	-48393	1146.30067
1.495	-4.096	-69669	-69697	-69370	-69533	-48652	-48519	-48501	1136.88800
1.495	-3.128	-53586	-53682	-53413	-53547	-48239	-48080	-48097	1140.95300
1.495	-2.164	-37130	-36891	-37030	-37030	-48433	-48247	-48248	1146.07800
1.495	-1.205	-20751	-20543	-20776	-20659	-48955	-48806	-48811	1145.42200
1.496	.224	.03855	.03729	.03521	.03625	.50314	.50168	.50176	1146.35066
1.495	.773	.13319	.13264	.13428	.13346	.51535	.51349	.51384	1145.78101
GRADIENT	1.807	.31283	.31228	.31353	.31290	.52386	.52579	.52477	1146.50000
	.17121	.17126	.17110	.17110	.00733	.00741	.00740	.00740	.0150910 -.01454

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 694  
(UCM032) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1424/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
1.515	-8.053	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.515	-1.45158	-1.45468	-1.45071	-1.45269	-1.45269	-1.52819	-1.52792	-1.52815	-1.52803	1098.60001	1136.98029
1.516	-7.041	-1.33000	-1.33167	-1.32749	-1.32998	-1.53664	-1.53569	-1.53602	-1.53586	1098.54201	1137.12665
1.516	-6.059	-1.17614	-1.17720	-1.17339	-1.17529	-1.54301	-1.54289	-1.54250	-1.54269	1098.51500	1136.95764
1.516	-5.074	-1.99662	-1.99734	-1.99385	-1.99559	-1.54305	-1.54262	-1.54235	-1.54248	1098.58200	1136.87198
1.516	-4.101	-1.80664	-1.80642	-1.80312	-1.80477	-1.54606	-1.54496	-1.54484	-1.54490	1098.53500	1136.74690
1.516	-3.123	-1.63379	-1.63156	-1.63306	-1.63288	-1.57028	-1.56924	-1.56900	-1.56912	1098.55499	1136.74428
1.516	-2.166	-1.44543	-1.44493	-1.44200	-1.44346	-1.58276	-1.58204	-1.58198	-1.58201	1098.48801	1137.06357
1.515	-1.207	-1.24518	-1.24591	-1.24347	-1.24469	-1.58256	-1.58206	-1.58211	-1.58208	1098.50800	1137.60591
1.515	-0.224	-0.4562	-0.4533	-0.4349	-0.4441	-1.59166	-1.59104	-1.59123	-1.59114	1098.45100	1137.39539
1.516	.773	.15451	.15429	.15594	.15512	-1.60264	-1.60186	-1.60203	-1.60194	1098.44099	1137.51666
1.516	1.808	.36866	.36940	.37040	.36990	-1.61954	-1.61854	-1.61866	-1.61860	1098.42700	1137.68703
1.515	GRADIENT	.20038	.20047	.20008	.20028	-1.01071	-1.01075	-1.01081	-1.01078	-0.01143	.17047

MACH	ALPHA	RUN NO.	1412/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
1.543	-8.056	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.543	-7.042	-1.48638	-1.48858	-1.48650	-1.48654	-1.53751	-1.53651	-1.53675	-1.53663	1113.86900	1135.64803
1.542	-6.057	-1.26489	-1.26695	-1.26291	-1.26493	-1.52111	-1.52042	-1.52034	-1.52038	1115.48100	1135.22896
1.542	-5.077	-1.08950	-1.09128	-1.08732	-1.08930	-1.51170	-1.51077	-1.51053	-1.51065	1118.04500	1135.73024
1.543	-4.095	-1.89534	-1.89795	-1.89451	-1.89623	-1.50401	-1.50305	-1.50300	-1.50302	1118.94200	1135.40582
1.542	-3.126	-1.70025	-1.70137	-1.69812	-1.69974	-1.49944	-1.49812	-1.49801	-1.49807	1119.78101	1135.74144
1.543	-2.163	-1.50170	-1.49917	-1.50191	-1.50054	-1.47107	-1.46983	-1.46997	-1.46990	1120.89000	1135.66127
1.542	-1.207	-1.32111	-1.32193	-1.31938	-1.32065	-1.43391	-1.43290	-1.43288	-1.43289	1121.89799	1135.61217
1.542	-0.222	-1.17012	-1.17078	-1.16952	-1.16965	-1.41816	-1.41637	-1.41661	-1.41649	1122.36800	1135.50699
1.542	.773	-0.2902	-0.2705	-0.2803	-0.2705	-1.42067	-1.41873	-1.41887	-1.41880	1122.61700	1135.62569
1.543	1.807	-1.0940	-1.1095	-1.1018	-1.1095	-1.43462	-1.43272	-1.43290	-1.43281	1123.18800	1135.87987
1.542	GRADIENT	.27308	.27439	.27373	.27308	-1.46043	-1.45912	-1.45936	-1.45924	1123.33299	1135.49855
1.5137		.16137	.16164	.16132	.16148	.00726	.00734	.00729	.00732	.58024	.01020

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

## PARAMETRIC DATA

	RUN NO.	1353/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	.74450	-.74182	-.74316	DPA	DPBCAL	DPB1	DPB2
.600	-8.033	-.74168	-.65044	-.65347	-.55923	-.56149	-46602	-.65206	-.17274	-.17146
.599	-7.035	-.65044	-.55923	-.56149	-.46602	-.46706	-.46444	-.56008	-.16969	-.16843
.600	-6.043	-.55923	-.56149	-.46706	-.37760	-.37764	-.37535	-.46575	-.16735	-.16596
.600	-5.061	-.46602	-.46706	-.37760	-.28550	-.28311	-.28315	-.28432	-.16488	-.16369
.600	-4.086	-.37760	-.28550	-.28311	-.19306	-.19523	-.19415	-.19336	-.16336	-.16221
.600	-3.118	-.28550	-.19306	-.19523	-.10674	-.10859	-.10767	-.02307	-.16675	-.16598
.600	-2.166	-.19306	-.10674	-.10859	-.02241	-.02307	-.02150	-.02228	-.17628	-.17530
.600	-1.241	-.10674	-.02241	-.02307	-.06806	-.06641	-.06791	-.06716	-.18911	-.18835
.600	-.298	-.02241	-.06806	-.06641	-.16468	-.16543	-.16703	-.09227	-.19613	-.19595
.600	.705	-.06806	-.16468	-.16543	-.09243	-.09216	-.09235	-.09235	-.00606	-.00609
GRADIENT										

	RUN NO.	1343/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPACAL	DPA1	.88739	-.88510	-.88624	DPA	DPBCAL	DPB1	DPB2
.800	-8.015	-.88584	-.77737	-.77864	-.66615	-.66680	-.55456	-.77725	-.22250	-.22146
.799	-7.008	-.77737	-.66615	-.66680	-.55689	-.55428	-.44632	-.66739	-.21290	-.21185
.800	-6.016	-.66615	-.55456	-.55689	-.44752	-.44507	-.34567	-.44630	-.21184	-.21046
.800	-5.030	-.55456	-.44632	-.44752	-.33747	-.33567	-.33567	-.44530	-.20490	-.20352
.800	-4.045	-.44632	-.33747	-.33567	-.22843	-.22632	-.22632	-.33638	-.20296	-.20189
.800	-3.070	-.33747	-.22843	-.22632	-.12415	-.12415	-.12415	-.33638	-.20195	-.20083
.801	-2.112	-.22843	-.12415	-.12415	-.01851	-.01706	-.01851	-.12219	-.20250	-.20101
.800	-1.170	-.12415	-.01851	-.01706	-.02029	-.08935	-.08980	-.01778	-.20406	-.20277
.800	-.214	-.02029	-.08935	-.08980	-.787	-.09047	-.20415	-.0991	-.21276	-.21268
.800	.787	-.09047	-.20415	-.20410	-.842	-.20515	-.11066	-.20465	-.22232	-.22235
GRADIENT									-.00512	-.00506

	RUN NO.	1331/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPACAL	DPA1	.91909	-.92103	-.91787	DPA	DPBCAL	DPB1	DPB2
.900	-8.041	-.91909	-.80283	-.80086	-.68873	-.68747	-.57203	-.80248	-.22782	-.22837
.900	-6.998	-.91909	-.69062	-.68873	-.57129	-.57275	-.46030	-.68905	-.21871	-.21832
.899	-6.007	-.69062	-.57203	-.57129	-.46156	-.45877	-.34658	-.67747	-.21494	-.21477
.900	-5.020	-.57203	-.46156	-.45877	-.34540	-.34479	-.34469	-.34469	-.21328	-.21198
.900	-4.043	-.46156	-.34540	-.34479	-.23472	-.23483	-.23217	-.23345	-.21494	-.21169
.900	-3.068	-.34540	-.23472	-.23483	-.12658	-.12450	-.12450	-.12554	-.20754	-.20885
.900	-2.108	-.12658	-.12450	-.12450	-.01708	-.01912	-.01708	-.01810	-.20814	-.20816
.900	-1.172	-.01708	-.01912	-.01912	-.02071	-.0223	-.02071	-.01913	-.21834	-.21834
.900	-.223	-.02071	-.0223	-.0223	-.09220	-.09188	-.09220	-.09188	-.22859	-.22870
.900	.775	-.09220	-.09188	-.09188	-.830	-.842	-.842	-.842	-.23764	-.23703
GRADIENT									-.00516	-.00522

	RUN NO.	1331/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPACAL	DPA1	.91945	-.91945	-.91787	DPA	DPBCAL	DPB1	DPB2
.900	-8.041	-.91945	-.80248	-.80086	-.68873	-.68747	-.57203	-.68905	-.22782	-.22837
.900	-6.998	-.91945	-.69062	-.68873	-.57129	-.57275	-.46030	-.68905	-.21871	-.21832
.899	-6.007	-.69062	-.57203	-.57129	-.46156	-.45877	-.34658	-.67747	-.21494	-.21477
.900	-5.020	-.57203	-.46156	-.45877	-.34540	-.34479	-.34469	-.34469	-.21328	-.21198
.900	-4.043	-.46156	-.34540	-.34479	-.23472	-.23483	-.23217	-.23345	-.20754	-.20885
.900	-3.068	-.34540	-.23472	-.23483	-.12658	-.12450	-.12450	-.12554	-.20677	-.20659
.900	-2.108	-.12658	-.12450	-.12450	-.01708	-.01912	-.01708	-.01810	-.20814	-.20816
.900	-1.172	-.01708	-.01912	-.01912	-.02071	-.0223	-.02071	-.01913	-.21834	-.21834
.900	-.223	-.02071	-.0223	-.0223	-.09220	-.09188	-.09220	-.09188	-.22859	-.22870
.900	.775	-.09220	-.09188	-.09188	-.830	-.842	-.842	-.842	-.23764	-.23703
GRADIENT									-.00516	-.00522

	RUN NO.	1331/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPACAL	DPA1	.91945	-.91945	-.91787	DPA	DPBCAL	DPB1	DPB2
.900	-8.041	-.91945	-.80248	-.80086	-.68873	-.68747	-.57203	-.68905	-.22782	-.22837
.900	-6.998	-.91945	-.69062	-.68873	-.57129	-.57275	-.46030	-.68905	-.21871	-.21832
.899	-6.007	-.69062	-.57203	-.57129	-.46156	-.45877	-.34658	-.67747	-.21494	-.21477
.900	-5.020	-.57203	-.46156	-.45877	-.34540	-.34479	-.34469	-.34469	-.21328	-.21198
.900	-4.043	-.46156	-.34540	-.34479	-.23472	-.23483	-.23217	-.23345	-.20754	-.20885
.900	-3.068	-.34540	-.23472	-.23483	-.12658	-.12450	-.12450	-.12554	-.20677	-.20659
.900	-2.108	-.12658	-.12450	-.12450	-.01708	-.01912	-.01708	-.01810	-.20814	-.20816
.900	-1.172	-.01708	-.01912	-.01912	-.02071	-.0223	-.02071	-.01913	-.21834	-.21834
.900	-.223	-.02071	-.0223	-.0223	-.09220	-.09188	-.09220	-.09188	-.22859	-.22870
.900	.775	-.09220	-.09188	-.09188	-.830	-.842	-.842	-.842	-.23764	-.23703
GRADIENT									-.00516	-.00522

	RUN NO.	1331/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPACAL	DPA1	.91945	-.91945	-.91787	DPA	DPBCAL	DPB1	DPB2
.900	-8.041	-.91945	-.80248	-.80086	-.68873	-.68747	-.57203	-.68905	-.22782	-.22837
.900	-6.998	-.91945	-.69062	-.68873	-.57129	-.57275	-.46030	-.68905	-.21871	-.21832
.899	-6.007	-.69062	-.57203	-.57129	-.46156	-.45877	-.34658	-.67747	-.21494	-.21477
.900	-5.020	-.57203	-.46156	-.45877	-.34540	-.34479	-.34469	-.34469	-.21328	-.21198
.900	-4.043	-.46156	-.34540	-.34479	-.23472	-.23483	-.23217	-.23345	-.20754	-.20885
.900	-3.068	-.34540	-.23472	-.23483	-.12658	-.12450	-.12450	-.12554	-.20677	-.20659
.900	-2.108	-.12658	-.12450	-.12450	-.01708	-.01912	-.01708	-.01810	-.20814	-.20816
.900	-1.172	-.01708	-.01912	-.01912	-.02071	-.0223	-.02071	-.01913	-.21834	-.21834
.900	-.223	-.02071	-.0223	-.0223	-.09220	-.09188	-.09220	-.09188	-.22859	-.22870
.900	.775	-.09220	-.09188	-.09188	-.830	-.842	-.842	-.842	-.23764	-.23703
GRADIENT									-.00516	-.00522

	RUN NO.	1331/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPACAL	DPA1	.91945	-.91945	-.91787	DPA	DPBCAL	DPB1	DPB2
.900	-8.041	-.91945	-.80248	-.80086	-.68873	-.68747	-.57203	-.68905	-.22782	-.22837
.900	-6.998	-.91945	-.69062	-.68873	-.57129	-.57275	-.46030	-.68905	-.21871	-.21832
.899	-6.007</									

(UCM033) ( 04 OCT 91 )

PARAMETRIC DATA

RUN NO.	1322/ O	RN/L =	2.50	GRADIENT INTERVAL = -5.00 / 5.00			BETA = -2.000	PHI = 180.000				
				DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F		
-1.1.099	-8.010	-.92912	-.93159	-.92869	-.93014	-.24776	-.24705	-.24695	1.167	.78600	1.205	.0260
-1.1.100	-6.958	-.80989	-.81186	-.80905	-.81045	-.23348	-.23351	-.23326	1.176	.02499	1.204	.7660
-1.1.100	-5.968	-.69473	-.69618	-.69340	-.69479	-.23284	-.23292	-.23272	1.183	.33299	1.204	.5970
-1.1.101	-4.969	-.57633	-.57811	-.57514	-.57662	-.22902	-.22914	-.22889	1.189	.44501	1.204	.5870
-1.1.100	-3.981	-.46213	-.46213	-.45980	-.46115	-.22277	-.22280	-.22278	1.194	.16299	1.204	.5700
-1.1.100	-2.981	-.34277	-.34110	-.34004	-.34141	-.22396	-.22342	-.22332	1.198	.05800	1.204	.8960
-1.1.100	-2.024	-.22519	-.22678	-.22446	-.22562	-.21799	-.21704	-.21694	1.200	.82201	1.204	.7020
-1.1.100	-1.048	-.11295	-.11445	-.11239	-.11342	-.21714	-.21602	-.21602	1.202	.57401	1.204	.8150
-1.1.100	-0.86	-.00429	-.00437	-.00417	-.00427	-.22162	-.22018	-.22022	1.203	.17900	1.204	.5200
-1.1.100	-0.902	-.10844	-.10689	-.10859	-.10774	-.22260	-.22260	-.22262	1.203	.80900	1.204	.60100
-1.1.100	1.929	.22550	.22521	.22624	.22574	-.222669	-.222800	-.222685	1.203	.69901	1.204	.57000
GRADIENT	1.1642	-.11653	-.11621	-.11637	-.00011	.00035	.00030	.00032	.2	.00313	.2	-.0117

卷之三

BIN NO 1378/0 BN/1 = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPACAL		DPA1		DPA2		DPBCAL		DPB1		DPB2		DPB		PTTF		PT2F	
		DPA1	DPA2	DPA1	DPA2	DPA1	DPA2	DPA1	DPA2	DPA1	DPA2	DPA1	DPA2	DPA1	DPA2	DPA1	DPA2	DPA1	DPA2
1.400	-8.013	-1.15489	-1.15815	-1.15432	-1.15623	-0.27572	-0.27762	-0.27709	-0.27736	1.125	1.4700	1.164	1.6130	-	-	-	-	-	-
1.400	-6.993	-1.01563	-1.01794	-1.01447	-1.01620	-0.27400	-0.27475	-0.27466	-0.27471	1.134	1.8401	1.164	1.5500	-	-	-	-	-	-
1.400	-6.001	-8.7126	-8.7290	-8.6957	-8.7124	-0.27349	-0.27358	-0.27332	-0.27345	1.141	2.5900	1.163	8.1300	-	-	-	-	-	-
1.400	-5.010	-7.2375	-7.2691	-7.2580	-7.2375	-0.27148	-0.27118	-0.27093	-0.27106	1.147	4.5000	1.164	2.4300	-	-	-	-	-	-
1.400	-4.026	-5.8368	-5.8656	-5.8376	-5.8656	-0.26922	-0.27014	-0.26999	-0.27006	1.152	9.6001	1.164	6.9400	-	-	-	-	-	-
1.400	-3.042	-4.3552	-4.3759	-4.3491	-4.3552	-0.26575	-0.26633	-0.26626	-0.26633	1.156	9.3299	1.164	5.1500	-	-	-	-	-	-
1.400	-2.080	-2.9315	-2.9404	-2.9146	-2.9315	-0.26349	-0.26407	-0.26372	-0.26390	1.158	4.6899	1.163	9.1700	-	-	-	-	-	-
1.400	-1.127	-1.15668	-1.15601	-1.15374	-1.15668	-0.26729	-0.26758	-0.26743	-0.26750	1.160	4.6100	1.164	3.8100	-	-	-	-	-	-
1.400	-0.162	-0.1933	-0.1779	-0.1585	-0.1933	-0.1682	-0.17772	-0.17823	-0.17822	1.161	7.2701	1.164	6.2000	-	-	-	-	-	-
1.400	-0.834	-1.2448	-1.2408	-1.2563	-1.2448	-1.2485	-1.28953	-1.28970	-1.28972	1.161	6.3699	1.164	5.0600	-	-	-	-	-	-
1.400	-1.888	-2.7220	-2.7304	-2.7183	-2.7220	-2.7243	-2.29704	-2.29766	-2.29759	1.161	6.2700	1.163	8.2500	-	-	-	-	-	-
1.410	-1.1410	-1.14160	-1.1407	-1.1402	-1.14160	-0.00532	-0.00524	-0.00527	-0.00527	1.141	4.1083	1.141	0.0777	-	-	-	-	-	-

## PARAMETRIC DATA

RUN NO. 1435 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	PCH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PPTF	PT2F
-8.037	-1.27385	-1.27673	-1.27482	-1.27290	-1.27482	-1.30290	-1.30246	-1.30268	-1.114	.00999	1.149 .99696
-7.015	-1.12517	-1.12781	-1.12592	-1.12403	-1.12592	-1.29774	-1.29760	-1.29774	-1.124	.15199	1.150 .06801
-6.025	-9.6275	-9.6671	-9.6531	-9.6331	-9.6501	-1.29649	-1.29775	-1.29783	-1.130	.00999	1.149 .82382
-5.040	-8.0473	-8.0749	-8.0580	-8.0410	-8.0580	-1.29147	-1.29295	-1.29280	-1.135	.32800	1.149 .90358
-4.062	-6.65048	-6.64875	-6.65024	-6.65173	-6.64875	-1.28325	-1.28489	-1.28480	-1.139	.98399	1.149 .77519
-3.093	-4.9307	-4.9328	-4.9190	-4.9052	-4.9052	-1.27988	-1.28030	-1.28025	-1.142	.83299	1.150 .25226
-2.138	-3.3643	-3.3390	-3.33517	-3.3390	-3.33643	-1.28130	-1.28166	-1.28170	-1.145	.83299	1.150 .07956
-1.202	-1.8356	-1.8527	-1.8422	-1.8317	-1.8356	-1.18422	-1.18422	-1.18422	-1.146	.25600	1.150 .06171
-0.471	-0.253	-0.3235	-0.3241	-0.3241	-0.32341	-1.30672	-1.30672	-1.30710	-1.30716	.57201	1.149 .78429
GRADIENT	16075	16104	16074	16083	16083	-0.1083	-0.1082	-0.1080	-0.1077	1.42769	.00518

RUN NO. 1402 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	PT2F	DPB	PPTF	DPB2	DPA	DPA1	DPACAL	DPBCAL	DPB1	DPACAL	DPA	DPA1	DPACAL	DPB1	DPB2	DPB	PPTF	PT2F	
ACH	-8.029	-1.31648	-1.31876	-1.31468	-1.31672	-1.31489	-3.1451	-3.1470	-1.112	-80901	1146	-31947	-8.029	-1.31648	-1.31876	-1.31468	-1.31672	-8.029	
	-7.011	-1.17094	-1.17209	-1.16814	-1.17011	-1.1807	-3.1765	-3.1786	-1.112	-79500	1146	-15175	-7.011	-1.17094	-1.17209	-1.16814	-1.17011	-7.011	
	-6.021	-1.01733	-1.01971	-1.01584	-1.01777	-1.1343	-3.1330	-3.1330	-1.128	-5.3300	1146	-61823	-6.021	-1.01733	-1.01971	-1.01584	-1.01777	-6.021	
	-5.036	-8.52563	-8.49116	-8.50866	-8.49116	-8.49116	-3.1376	-3.1358	-1.134	-67101	1146	-85043	-5.036	-8.52563	-8.49116	-8.50866	-8.49116	-5.036	
	-4.058	-6.9404	-6.9476	-6.9161	-6.9318	-6.9476	-3.0734	-3.0742	-1.139	-25101	1146	-45389	-4.058	-6.9404	-6.9476	-6.9161	-6.9318	-4.058	
	-3.086	-5.3013	-5.3077	-5.2781	-5.2929	-5.3069	-3.0564	-3.0580	-1.142	-6.3400	1146	-72836	-3.086	-5.3013	-5.3077	-5.2781	-5.2929	-3.086	
	-2.125	-3.66312	-3.62226	-3.59664	-3.6095	-3.6095	-3.0714	-3.0709	-1.143	-7.6601	1146	-4.7583	-2.125	-3.66312	-3.62226	-3.59664	-3.6095	-2.125	
	-1.191	-2.0420	-2.0408	-2.0178	-2.0293	-2.0178	-3.1606	-3.1619	-1.143	-8.0000	1146	-3.6731	-1.191	-2.0420	-2.0408	-2.0178	-2.0293	-1.191	
	-0.496	-2.239	-0.4077	-0.4036	-0.38828	-0.3932	-3.33778	-3.33777	-1.143	-9.2400	1147	-2.1349	-0.496	-2.239	-0.4077	-0.4036	-0.38828	-0.496	
	.762	-1.13337	-1.13337	-1.13268	-1.13432	-1.13350	-3.5445	-3.5367	-1.143	-8.3701	1147	-0.06535	.762	-1.13337	-1.13337	-1.13268	-1.13432	.762	
	1.829	.31353	.31353	.31436	.31436	.31375	-3.5592	-3.5350	-1.160	-3.6196	1143	-7.7000	1.829	.31353	.31353	.31436	.31436	1.829	
	4.95	CBADIENT	17150	17151	17118	17135	0.1088	0.1066	0.1066	0.1066	0.1066	0.1066	0.1066	4.95	CBADIENT	17150	17151	17118	4.95

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 698

(UCM033) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1425/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
MACH	ALPHA	-1.47558	-1.47861	-1.47447	-1.47654	-1.4074	-1.34160	-1.34109	-1098.35600	1137.57457
1.516	-8.029	-1.34788	-1.34969	-1.34544	-1.34757	-1.35704	-1.35635	-1.35527	-1098.29900	1136.92250
1.516	-7.011	-1.16599	-1.16724	-1.16348	-1.16536	-1.35036	-1.34992	-1.34870	-1098.29900	1136.81230
1.516	-6.023	-1.98225	-1.98328	-1.97926	-1.98127	-1.34790	-1.34780	-1.34664	-1098.26601	1136.78348
1.516	-5.038	-1.81469	-1.81406	-1.81160	-1.81314	-1.35703	-1.35672	-1.35600	-1098.27499	1137.14111
1.516	-4.059	-1.62633	-1.62677	-1.62363	-1.62520	-1.36602	-1.36511	-1.36497	-1098.21800	1137.78355
1.517	-3.086	-1.42686	-1.42395	-1.42540	-1.42540	-1.36055	-1.35948	-1.35938	-1098.24800	1137.85931
1.517	-2.130	-1.24334	-1.24383	-1.24153	-1.24268	-1.36708	-1.36639	-1.36650	-1098.21500	1137.47951
1.517	-1.191	-0.05123	-0.04937	-0.05030	-0.05030	-1.38145	-1.38072	-1.38074	-1098.20500	1138.02101
1.517	-0.239	.35747	.35836	.35852	.35844	-1.5021	-1.40506	-1.40389	-1098.12700	1137.96371
1.516	.766	.14976	.14940	.15103	.15021	-1.41533	-1.41449	-1.41470	-1098.13699	1137.31183
1.516	1.831	.19956	.19979	.19931	.19955	-0.10099	-0.01003	-0.01017	-.02348	.03594
GRADIENT										

RUN NO. 1413/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
MACH	ALPHA	-1.46113	-1.46330	-1.45921	-1.46125	-1.34494	-1.34557	-1.34502	-1114.38000	1135.64503
1.542	-8.032	-1.25624	-1.25744	-1.25360	-1.25552	-1.33600	-1.33690	-1.33657	-1115.92599	1135.40823
1.542	-7.010	-1.06105	-1.06339	-1.05873	-1.06106	-1.33311	-1.33403	-1.33379	-1118.62700	1135.54330
1.542	-6.026	-1.67274	-1.67675	-1.66614	-1.686780	-1.32822	-1.32787	-1.32774	-1119.16100	1135.05760
1.542	-5.037	-4.058	-4.058	-4.058	-4.058	-1.31438	-1.31303	-1.31290	-1120.25000	1135.17235
1.542	-3.085	-1.45798	-1.45743	-1.45475	-1.45609	-1.27750	-1.27760	-1.27754	-1121.31400	1135.15031
1.542	-2.130	-1.29345	-1.29430	-1.29176	-1.29303	-1.25825	-1.25745	-1.25735	-1121.35800	1135.02684
1.542	-1.192	-1.16506	-1.16542	-1.16279	-1.16393	-1.25645	-1.25645	-1.25634	-1120.87700	1135.17929
1.542	-0.238	-0.03577	-0.03724	-0.03397	-0.03487	-1.26917	-1.26928	-1.26927	-1121.28101	1135.48248
1.542	.765	.10095	.10021	.10179	.10100	-1.28252	-1.28230	-1.28236	-1121.57300	1135.10869
1.542	1.828	.24856	.25024	.24876	.24950	-1.29300	-1.29213	-1.29226	-1122.84000	1135.32014
GRADIENT		.15166	.15176	.15148	.15162	.00148	.00142	.00138	.00140	.02968

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM034) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1354 / 0		RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	-1.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PPTF	PT2F	
.600	.73360	-.73378	-.73519	-.07371	-.07307	-.07284	-.07296	1563.11400	1597.25000		
.599	.64218	-.64243	-.64386	-.07689	-.07528	-.07493	-.07510	1570.89700	1596.31000		
.600	.5053	-.55257	-.54996	-.07301	-.07086	-.07056	-.07071	1577.94000	1596.81000		
.600	.45819	-.45909	-.45786	-.07086	-.06885	-.06864	-.06875	1583.85201	1597.00999		
.600	.4.023	-.36998	-.37076	-.36832	-.36954	-.07159	-.07053	1588.18800	1597.44000		
.600	.3.040	-.27488	-.27719	-.27472	-.27596	-.07015	-.06905	1591.72900	1596.81000		
.601	.2.078	-.18641	-.18412	-.18430	-.18536	-.06678	-.06583	1593.95900	1596.91000		
.600	.1.158	-.10143	-.10271	-.10068	-.10169	-.06640	-.06541	1595.35899	1596.71001		
.601	.265	-.02190	-.02250	-.02084	-.02167	-.08517	-.08394	1596.00101	1597.00000		
.600	.783	.07053	.07003	.07160	.07082	-.10562	-.10417	1596.30701	1596.91000		
.601	1.859	.16879	.16982	.17148	.17065	-.11117	-.10982	1596.11200	1596.94000		
GRADIENT	.09109	.09149	.09132	.09141	.00772	-.00765	-.00770	1.27984	-.04451		
RUN NO.		1344 / 0		RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	-1.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PPTF	PT2F	
.800	.87462	-.87630	-.87357	-.87494	-.10652	-.10421	-.10386	1305.02901	1342.11000		
.800	.7076	-.77186	-.76935	-.77060	-.09872	-.09697	-.09667	1313.34900	1342.33000		
.800	.5989	-.65810	-.66083	-.65814	-.09273	-.09151	-.09136	1321.13200	1341.95000		
.800	.4995	-.54821	-.55073	-.54808	-.08964	-.08835	-.08823	1327.07600	1341.92000		
.800	.4.002	-.43965	-.44088	-.43857	-.43973	-.09087	-.08857	1332.08099	1341.88000		
.801	.3.015	-.32737	-.32844	-.32610	-.32727	-.09194	-.09005	1335.85300	1342.13000		
.800	.2.045	-.22037	-.22029	-.21830	-.21930	-.08926	-.08723	1338.49600	1342.06000		
.800	.1.108	-.11890	-.11785	-.11608	-.11697	-.08802	-.08581	1340.08501	1342.02000		
.800	.186	-.02059	-.01927	-.01753	-.01840	-.10629	-.10448	1340.82401	1342.06000		
.800	.847	.09271	.09245	.09391	.09318	-.12300	-.12091	1340.87700	1341.89999		
.800	1.903	.20825	.20821	.20928	.20874	-.12521	-.12303	1341.12601	1342.06000		
GRADIENT	.10956	.10993	.10971	.10982	.00552	-.00546	-.00549	1.93342	.01021		
RUN NO.		1332 / 0		RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	-1.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PPTF	PT2F	
.900	.90926	-.91084	-.90765	-.90925	-.10076	-.10697	-.10658	10677	1236.47501	1273.11000	
.900	.79654	-.79355	-.79505	-.7955	-.09626	-.09982	-.09932	1244.34801	1272.75000		
.900	.68075	-.68245	-.67952	-.68099	-.09162	-.09482	-.09448	1245.09399	1273.19000		
.900	.56630	-.56847	-.56539	-.56693	-.09324	-.09224	-.09054	1258.45599	1273.07001		
.900	.3.996	-.45294	-.45089	-.45236	-.33681	-.09272	-.09138	1263.32600	1273.11000		
.900	.3.007	-.33665	-.33811	-.33551	-.22335	-.22459	-.09083	1267.21201	1273.12000		
.900	.2.037	-.22602	-.22584	-.22335	-.11837	-.11956	-.08910	1269.75101	1272.96001		
.900	.1.111	-.12075	-.12189	-.12075	-.01982	-.01778	-.01980	1271.18500	1273.00999		
.900	.199	-.02146	-.02146	-.02146	-.09735	-.09539	-.09571	1272.08200	1273.08000		
.900	.834	.09539	.09539	.09539	.21314	.21479	.21416	12483	12484	12485	1273.31000
.900	1.889	.21314	.21352	.21352	.11336	.11349	.11361	1272.28700	1272.28700	1272.28700	1273.28700
GRADIENT	.11336	.11373	.11373	.11373	.00586	-.00570	-.00575	.00573	1.93533	.00076	

## PARAMETRIC DATA

	RUN NO.	1323/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-7.980	-.92106	-.92385	-.92106	-.92245	-.12519	-.12358	-.12320	-.12339	1168.90300	1204.93100
1.099	-6.950	-.80465	-.80671	-.80371	-.80521	-.11489	-.11371	-.11331	-.11351	1176.70500	1204.96201
1.100	-5.949	-.68859	-.69014	-.68720	-.68867	-.11394	-.11289	-.11265	-.11277	1184.47200	1204.62601
1.100	-4.954	-.57319	-.57458	-.57174	-.57316	-.10946	-.10863	-.10838	-.10851	1190.51801	1204.70000
1.100	-3.957	-.45546	-.45602	-.45328	-.45465	-.10977	-.10863	-.10832	-.10848	1195.22600	1204.56100
1.100	-2.963	-.33416	-.33618	-.33341	-.33480	-.10709	-.10649	-.10638	-.10643	1199.09801	1204.72000
1.100	-1.981	-.2016	-.22170	-.21941	-.22056	-.10290	-.10262	-.10253	-.10257	1201.78101	1204.77100
1.100	-1.020	-.11008	-.11162	-.10946	-.11054	-.10130	-.10081	-.10091	-.10086	1203.09100	1204.46201
1.100	-.051	-.0288	-.0286	-.00278	.00282	-.10958	-.10936	-.10927	-.10931	1203.99400	1204.74200
1.100	.940	.10869	.10744	.10906	.10825	-.11448	-.11439	-.11448	-.11443	1204.02400	1204.57600
1.100	1.963	.22383	.22350	.22481	.22415	-.11323	-.11293	-.11306	-.11300	1204.11099	1204.70799
1.100	1.1518	.11489	.11503	.11503	.11503	-.00067	-.00079	-.00085	-.00082	1.87808	-.00128

	RUN NO.	1368/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-7.998	-1.00375	-1.01356	-1.00407	-1.00882	-.11250	-.11158	-.11137	-.11147	1145.62900	1183.13300
1.250	-6.973	-.87934	-.88734	-.87801	-.88267	-.10973	-.11019	-.10991	-.11005	1153.99001	1182.55901
1.250	-5.978	-.75385	-.76198	-.75290	-.75744	-.11224	-.11178	-.11152	-.11165	1161.92300	1182.55800
1.250	-4.986	-.62384	-.63220	-.62314	-.62767	-.10768	-.10681	-.10664	-.10672	1166.63600	1182.29100
1.250	-3.995	-.49927	-.50664	-.49782	-.50223	-.10396	-.10328	-.10298	-.10313	1171.07600	1182.07700
1.250	-3.005	-.37052	-.37736	-.37314	-.36893	-.10609	-.10411	-.10407	-.10409	1175.82201	1182.74500
1.250	-2.031	-.24715	-.25034	-.24623	-.25446	-.10463	-.10283	-.10274	-.10279	1178.66000	1182.59300
1.250	-1.091	-.13131	-.13748	-.12964	-.13356	-.10600	-.10392	-.10384	-.10388	1180.22501	1182.20300
1.250	-153	-.01512	-.01370	-.01254	-.01370	-.13762	-.12226	-.12074	-.12077	1181.50800	1182.72600
1.250	.881	1.1417	1.0646	1.1416	1.11031	-.13680	-.13478	-.13492	-.13485	1181.53400	1182.65401
1.250	1.923	.24117	.23478	.24195	.23837	-.13952	-.13719	-.13754	-.13737	1181.03101	1182.21700
1.250	1.12529	.12546	.12521	.12534	.12532	-.00513	-.00513	-.00513	-.00517	2.08142	.00280
	RUN NO.	1380/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
	-7.995	-1.14801	-.15150	-1.14751	-1.14951	-.12443	-.12494	-.12437	-.12464	1125.85201	1164.29601
1.400	-6.970	-1.00778	-1.01129	-1.00749	-1.00939	-.12680	-.12679	-.12642	-.12660	1135.33299	1164.42900
1.400	-5.975	-.86370	-.86549	-.86206	-.86377	-.12199	-.12306	-.12265	-.12285	1142.59599	1164.30299
1.400	-4.984	-.72062	-.72286	-.71963	-.72124	-.12136	-.12157	-.12157	-.12182	1148.57201	1164.37500
1.400	-3.993	-.57473	-.57774	-.57475	-.57624	-.12193	-.12178	-.12172	-.12195	1153.61099	1163.83200
1.400	-3.001	-.42296	-.42568	-.42290	-.42429	-.11928	-.11904	-.11880	-.11892	1157.05701	1164.13200
1.400	-2.026	-.28318	-.28415	-.28164	-.28290	-.11923	-.11913	-.11880	-.11896	1159.60600	1164.49500
1.400	-1.080	-.15283	-.15186	-.14962	-.15074	-.12279	-.12266	-.12241	-.12254	1162.59599	1164.43500
1.400	-137	-.01724	-.01617	-.01404	-.01510	-.13947	-.13935	-.13935	-.13935	1163.16400	1163.92000
1.400	1.399	.891	.13128	.13062	.13232	-.13147	-.15581	-.15547	-.15555	1163.61000	1164.34399
1.400	1.934	.27521	.27457	.27590	.27524	-.15774	-.15768	-.15745	-.15756	1161.72600	1164.00600
	GRADIENT	1.4426	.14426	.14400	.14413	-.00593	-.00585	-.00590	-.00587	1.97583	-.00874

## PARAMETRIC DATA

	RUN NO.	1391/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.450	-8.006	-1.21726	-1.21940	-1.21579	-1.21759	-1.2253	-1.2297	-1.2239	-1119.38000	1158.85699
1.450	-6.983	-1.06735	-1.07235	-1.06787	-1.07011	-1.2309	-1.2260	-1.2220	-1127.50999	1158.34801
1.450	-5.986	-9.16446	-9.2041	-9.1715	-9.1878	-1.2048	-1.1955	-1.1927	-1194.1134	1158.48100
1.450	-5.002	-7.6657	-7.6940	-7.66335	-7.6788	-1.2199	-1.2149	-1.2101	-1194.74001	1158.32600
1.450	-4.015	-6.1955	-6.2187	-6.1883	-6.2035	-1.1902	-1.1708	-1.1669	-11688.70799	1158.18600
1.450	-3.031	-4.6014	-4.6022	-4.5761	-4.5891	-1.1701	-1.1485	-1.1456	-11470.51601	1158.62199
1.450	-2.068	-30885	-31014	-30787	-30900	-1.1561	-1.1493	-1.1492	-11493.1152	1158.30701
1.450	-1.145	-17291	-17418	-17226	-17322	-1.2000	-1.1959	-1.1940	-11950.1157	1158.18100
1.450	-2.49	-0.3231	-0.3308	-0.3130	-0.3219	-1.4909	-1.4843	-1.4846	-14844.1160	27901.32300
1.450	.798	1.3009	1.2967	1.3112	1.3040	-1.7831	-1.7828	-1.7803	-17815.1157	98100.60100
1.450	1.868	.28651	.28858	.28960	.28909	-1.8107	-1.8066	-1.8089	-18078.1154	69901.04900
GRADIENT	15390	.15438	.15406	.15422	.15426	-0.01264	-0.01297	-0.01304	-0.01300	1.56985 -.01679

RUN NO. 1436/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1436/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.471	-8.006	-1.26747	-1.26987	-1.26613	-1.26800	-1.13175	-1.13149	-1.13100	-13125.26601	1150.19846
1.471	-6.978	-1.11608	-1.11876	-1.11506	-1.11691	-1.3306	-1.3288	-1.3261	-13275.43500	1150.38759
1.471	-5.986	-95331	-95772	-95417	-95595	-1.3078	-1.2937	-1.2898	-12918.1130	95500.1149.84615
1.471	-4.996	-7.9568	-7.9872	-7.9514	-7.9693	-1.2719	-1.2571	-1.2545	-12558.1135	98300.61845
1.471	-4.009	-6.3754	-6.3890	-6.3564	-6.3727	-1.2000	-1.2017	-1.2007	-12012.1140	50500.1150.18811
1.471	-3.025	-4.7798	-4.7842	-4.7559	-4.7700	-1.1897	-1.1922	-1.1899	-11910.1144	3.4801.1150.22868
1.471	-2.059	-32163	-32241	-32000	-32120	-1.1728	-1.1705	-1.1697	-11701.1145	6.9200.1150.42264
1.470	-1.132	-17490	-17392	-17300	-17500	-1.1906	-1.1897	-1.1890	-11894.1146	0.1801.1150.22087
1.471	-2.28	-0.3185	-0.3303	-0.3100	-0.3202	-1.4814	-1.4829	-1.4828	-14829.1146	1.9600.1149.39540
1.471	.818	.13372	.13301	.13460	.13381	-1.8035	-1.8053	-1.8063	-18058.1146	.74699.1149.81128
1.471	1.885	.29969	.30155	.30265	.30210	-1.8900	-1.8947	-1.8941	-18944.1148	.14700.1149.96426
GRADIENT	15937	.15980	.15946	.15963	.15963	-0.01013	-0.01029	-0.01033	-0.01031	1.49768 -.02479

RUN NO. 1403/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1403/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.495	-8.005	-1.31270	-1.31509	-1.31077	-1.31293	-1.4482	-1.4459	-1.4413	-14436.1120	48000.1146.61328
1.495	-6.983	-1.16752	-1.16853	-1.16472	-1.16662	-1.4353	-1.4286	-1.4236	-14261.1116	94200.1146.23807
1.495	-5.985	-1.00774	-1.01004	-1.00621	-1.00813	-1.3932	-1.3827	-1.3808	-13818.1126	.29601.1146.47415
1.495	-4.995	-8.4674	-8.4688	-8.4325	-8.4499	-1.4109	-1.4021	-1.4004	-14013.1135	.20000.1146.27025
1.495	-4.007	-6.8438	-6.8522	-6.8176	-6.8349	-1.3678	-1.3533	-1.3528	-13531.1139	.60100.1146.34021
1.495	-3.027	-5.1535	-5.1595	-5.1286	-5.1440	-1.3211	-1.3129	-1.3124	-13127.1139	.52400.1146.71063
1.495	-2.055	-35317	-35372	-35099	-35235	-1.3364	-1.3271	-1.3253	-13262.1139	.49001.1146.88281
1.495	-1.125	-19738	-19752	-19509	-19631	-1.3680	-1.3624	-1.3595	-13610.1139	.42700.1146.45465
1.495	.215	.03811	.03803	.03595	.03699	-1.7009	-1.6843	-1.6847	-16845.1139	.35899.1146.33481
1.495	.831	.14502	.14448	.14618	.14533	-1.9598	-1.9508	-1.9505	-19506.1139	.21899.1146.89357
1.495	1.895	.32503	.32440	.32560	.32500	-2.0044	-1.9974	-1.9985	-19979.1139	.13100.1146.34988
GRADIENT	17042	.17006	.17040	.17023	.17023	-0.01014	-0.01017	-0.01020	-0.01018	.30598 -.02181

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 702  
 (UCM034) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1426/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB
1.517	-8.000	-1.49377	-1.49311	-1.49510	-1.49510	-1.5331	-1.5317	-1.5248	-1.5283
1.517	-6.983	-1.35648	-1.35368	-1.35578	-1.35578	-1.5941	-1.5973	-1.5941	-1.5957
1.517	-5.985	-1.16985	-1.17100	-1.16720	-1.16910	-1.5843	-1.5929	-1.5870	-1.5900
1.517	-4.996	-0.98293	-0.98383	-0.98007	-0.98195	-1.5292	-1.5282	-1.5233	-1.5258
1.517	-4.008	-0.80738	-0.80797	-0.80457	-0.80627	-1.5567	-1.5571	-1.5547	-1.5559
1.516	-3.022	-0.59231	-0.59243	-0.58951	-0.59097	-1.5711	-1.5596	-1.5567	-1.5581
1.517	-2.055	-0.39918	-0.39946	-0.39778	-0.39698	-1.5698	-1.5545	-1.5521	-1.5533
1.517	-1.125	-0.21209	-0.21276	-0.21034	-0.21155	-1.4570	-1.4439	-1.4422	-1.4430
1.516	-0.215	-0.05378	-0.05424	-0.05240	-0.05332	-1.5543	-1.5448	-1.5448	-1.5448
1.516	.830	-1.5419	-1.5377	-1.5547	-1.5462	-1.19567	-1.19512	-1.19506	-1.19506
1.517	1.895	-0.36398	-0.36299	-0.36420	-0.36360	-0.21856	-0.21777	-0.21775	-0.21775
GRADIENT	19612	.19612	.19575	.19594	.00797	.00788	.00795	.00792	.02428

RUN NO. 1414/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1414/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB
1.542	-8.004	-1.4975	-1.45195	-1.44781	-1.44988	-1.5403	-1.5359	-1.5293	-1.5326
1.542	-6.982	-1.24742	-1.24837	-1.24489	-1.24663	-1.4615	-1.4578	-1.4536	-1.4557
1.542	-5.990	-1.03066	-1.03307	-1.02931	-1.03119	-1.4667	-1.4578	-1.4551	-1.4564
1.542	-4.995	-0.83360	-0.83460	-0.83129	-0.83294	-1.4658	-1.4549	-1.4518	-1.4534
1.542	-4.008	-0.62778	-0.62530	-0.62530	-0.62691	-1.3502	-1.3361	-1.3332	-1.3347
1.543	-3.022	-0.42974	-0.42931	-0.42668	-0.42800	-1.1606	-1.1659	-1.1589	-1.1598
1.542	-2.055	-0.28393	-0.28464	-0.28224	-0.28344	-1.1154	-1.1154	-1.1094	-1.1103
1.542	-1.125	-0.15697	-0.15493	-0.15595	-0.15697	-1.0833	-1.0745	-1.0758	-1.0752
1.543	-0.215	-0.03638	-0.03509	-0.03407	-0.03305	-1.3026	-1.3076	-1.3001	-1.3013
1.543	.829	-0.10397	-0.10320	-0.10480	-0.10400	-1.4906	-1.4849	-1.4843	-1.4846
1.554	1.896	-0.24912	-0.24878	-0.25018	-0.24948	-1.5621	-1.5536	-1.5551	-1.5544
GRADIENT	15336	.15346	.15318	.15332	.00220	.00227	.00220	.00229	.02428

	RUN NO.	1414/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB
1.542	-8.004	-1.4975	-1.45195	-1.44781	-1.44988	-1.5403	-1.5359	-1.5293	-1.5326
1.542	-6.982	-1.24742	-1.24837	-1.24489	-1.24663	-1.4615	-1.4578	-1.4536	-1.4557
1.542	-5.990	-1.03066	-1.03307	-1.02931	-1.03119	-1.4667	-1.4578	-1.4551	-1.4564
1.542	-4.995	-0.83360	-0.83460	-0.83129	-0.83294	-1.4658	-1.4549	-1.4518	-1.4534
1.542	-4.008	-0.62778	-0.62530	-0.62530	-0.62691	-1.3502	-1.3361	-1.3332	-1.3347
1.543	-3.022	-0.42974	-0.42931	-0.42668	-0.42800	-1.1606	-1.1659	-1.1589	-1.1598
1.542	-2.055	-0.28393	-0.28464	-0.28224	-0.28344	-1.1154	-1.1154	-1.1094	-1.1103
1.542	-1.125	-0.15697	-0.15493	-0.15595	-0.15697	-1.0833	-1.0745	-1.0758	-1.0752
1.543	-0.215	-0.03638	-0.03509	-0.03407	-0.03305	-1.3026	-1.3076	-1.3001	-1.3013
1.543	.829	-0.10397	-0.10320	-0.10480	-0.10400	-1.4906	-1.4849	-1.4843	-1.4846
1.554	1.896	-0.24912	-0.24878	-0.25018	-0.24948	-1.5621	-1.5536	-1.5551	-1.5544
GRADIENT	15336	.15346	.15318	.15332	.00220	.00227	.00220	.00229	.02428

	RUN NO.	1414/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB
1.542	-8.004	-1.4975	-1.45195	-1.44781	-1.44988	-1.5403	-1.5359	-1.5293	-1.5326
1.542	-6.982	-1.24742	-1.24837	-1.24489	-1.24663	-1.4615	-1.4578	-1.4536	-1.4557
1.542	-5.990	-1.03066	-1.03307	-1.02931	-1.03119	-1.4667	-1.4578	-1.4551	-1.4564
1.542	-4.995	-0.83360	-0.83460	-0.83129	-0.83294	-1.4658	-1.4549	-1.4518	-1.4534
1.542	-4.008	-0.62778	-0.62530	-0.62530	-0.62691	-1.3502	-1.3361	-1.3332	-1.3347
1.543	-3.022	-0.42974	-0.42931	-0.42668	-0.42800	-1.1606	-1.1659	-1.1589	-1.1598
1.542	-2.055	-0.28393	-0.28464	-0.28224	-0.28344	-1.1154	-1.1154	-1.1094	-1.1103
1.542	-1.125	-0.15697	-0.15493	-0.15595	-0.15697	-1.0833	-1.0745	-1.0758	-1.0752
1.543	-0.215	-0.03638	-0.03509	-0.03407	-0.03305	-1.3026	-1.3076	-1.3001	-1.3013
1.543	.829	-0.10397	-0.10320	-0.10480	-0.10400	-1.4906	-1.4849	-1.4843	-1.4846
1.554	1.896	-0.24912	-0.24878	-0.25018	-0.24948	-1.5621	-1.5536	-1.5551	-1.5544
GRADIENT	15336	.15346	.15318	.15332	.00220	.00227	.00220	.00229	.02428

	RUN NO.	1414/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB
1.542	-8.004	-1.4975	-1.45195	-1.44781	-1.44988	-1.5403	-1.5359	-1.5293	-1.5326
1.542	-6.982	-1.24742	-1.24837	-1.24489	-1.24663	-1.4615	-1.4578	-1.4536	-1.4557
1.542	-5.990	-1.03066	-1.03307	-1.02931	-1.03119	-1.4667	-1.4578	-1.4551	-1.4564
1.542	-4.995	-0.83360	-0.83460	-0.83129	-0.83294	-1.4658	-1.4549	-1.4518	-1.4534
1.542	-4.008	-0.62778	-0.62530	-0.62530	-0.62691	-1.3502	-1.3361	-1.3332	-1.3347
1.543	-3.022	-0.42974	-0.42931	-0.42668	-0.42800	-1.1606	-1.1659	-1.1589	-1.1598
1.542	-2.055	-0.28393	-0.28464	-0.28224	-0.28344	-1.1154	-1.1154	-1.1094	-1.1103
1.542	-1.125	-0.15697	-0.15493	-0.15595	-0.15697	-1.0833	-1.0745	-1.0758	-1.0752
1.543	-0.215	-0.03638	-0.03509	-0.03407	-0.03305	-1.3026	-1.3076	-1.3001	-1.3013
1.543	.829	-0.10397	-0.10320	-0.10480	-0.10400	-1.4906	-1.4849	-1.4843	-1.4846
1.554	1.896	-0.24912	-0.24878	-0.25018	-0.24948	-1.5621	-1.5536	-1.5551	-1.5544
GRADIENT	15336	.15346	.15318	.15332	.00220	.00227	.00220	.00229	.02428

	RUN NO.	1414/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB
1.542	-8.004	-1.4975	-1.45195	-1.44781	-1.44988	-1.5403	-1.5359	-1.5293	-1.5326
1.542	-6.982	-1.24742	-1.24837	-1.24489	-1.24663	-1.4615	-1.4578	-1.4536	-1.4557
1.542	-5.990	-1.03066	-1.03307	-1.02931	-1.03119	-1.4667	-1.4578	-1.4551	-1.4564
1.542	-4.995	-0.83360	-0.83460	-0.83129	-0.83294	-1.4658	-1.4549	-1.4518	-1.4534
1.542	-4.008	-0.62778	-0.62530	-0.62530	-0.62691	-1.3502	-1.3361	-1.3332	-1.3347
1.543	-3.022	-0.42974	-0.42931	-0.42668	-0.42800	-1.1606	-1.1659	-1.1589	-1.1598
1.542	-2.055	-0.28393	-0.28464	-0.28224	-0.28344	-1.1154	-1.1154	-1.1094	-1.1103
1.542	-1.125	-0.15697	-0.15493	-0.15595	-0.15697	-1.0833	-1.0745	-1.0758	-1.0752
1.543	-0.215	-0.03638	-0.03509	-0.03407	-0.03305	-1.3026	-1.3076	-1.3001	-1.3013
1.543	.829	-0.10397	-0.10320	-0.10480	-0.				

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM035) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1355/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000	PTT2F
MACH	ALPHA	DPA1CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTFF	PTT2F
.599	-7.963	-72546	-72805	-72533	-72669	.02321	.02279	.02291	1563.52200	1597.14000	
.600	-6.956	-63597	-63839	-63705	-63705	.02276	.02332	.02353	1571.09300	1597.46001	
.600	-5.955	-54385	-54592	-54333	-54462	.02285	.02334	.02366	1578.02600	1596.78000	
.600	-4.953	-45308	-45398	-45129	-45264	.02259	.02323	.02359	1583.83701	1596.92000	
.601	-3.951	-36306	-36368	-36122	-36245	.02159	.02228	.02271	.02250	1588.36501	1596.97000
.600	-2.948	-26713	-26963	-26759	-26861	.02171	.02257	.02272	1591.81799	1596.97000	
.601	-1.942	-17308	-17457	-17257	-17357	.02453	.02374	.02396	1594.39400	1597.34000	
.601	-922	-07889	-08031	-07837	-07934	.02437	.02347	.02364	1595.77100	1597.39999	
.600	-192	-01656	-01419	-01592	-01506	-.00600	-.00513	-.00510	1596.11800	1596.89000	
.600	.869	.07317	.07245	.07402	.07323	-.01554	-.01472	-.01467	1596.32300	1597.00999	
.600	2.006	.17938	.17999	.18173	.18086	-.02196	-.02068	-.02069	1596.16901	1596.92999	
.600	GRADIENT	.09076	.09088	.09073	.09081	-.00693	-.00687	-.00693	-.00679	1.69480	-.00113
	RUN NO.	1345/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	ALPHA	DPA1CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTFF	PTT2F
.800	-7.968	-87298	-87458	-87180	-87319	.01895	.01965	.02000	.01983	1305.13901	1342.25000
.800	-6.952	-76086	-76201	-75915	-76058	.02036	.01996	.02037	.02016	1313.87300	1342.11000
.800	-5.951	-64873	-65150	-64876	-65013	.02038	.02014	.02041	.02027	1321.02100	1341.94000
.800	-4.950	-54227	-54489	-54222	-54355	.02225	.02182	.02226	.02204	1327.57700	1342.06000
.800	-3.955	-43355	-43490	-43252	-43371	.02166	.02146	.02168	.02157	1332.25900	1342.03000
.800	-2.948	-32090	-32197	-32082	-32082	.01992	.02031	.02071	.02051	1336.16499	1341.92999
.800	-1.946	-21004	-20988	-20785	-20886	.01835	.01948	.01978	.01963	1338.97701	1341.91000
.800	-.933	-09997	-09881	-09700	-09790	.01881	.01994	.02015	.02004	1340.43500	1341.92999
.800	.019	-.00083	.00061	.00072	.00067	-.01790	-.01520	-.01527	-.01524	1340.94200	1341.94000
.800	1.009	.10475	.10448	.10575	.10511	-.01938	-.01675	-.01691	-.01683	1341.07600	1342.00999
.799	2.003	.21640	.21664	.21752	.21708	-.01880	-.01586	-.01596	-.01591	1341.19000	1341.83000
	GRADIENT	.10878	.10919	.10889	.10904	-.00724	-.00670	-.00679	-.00674	1.86473	-.01996
	RUN NO.	1333/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	ALPHA	DPA1CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTFF	PTT2F
.900	-7.958	-90271	-90434	-90132	-90283	.02250	.02257	.02319	.02288	1236.07899	1273.19000
.900	-6.932	-78694	-78735	-78440	-78588	.02155	.02179	.02224	.02202	1244.56300	1272.97000
.900	-5.938	-67293	-67436	-67125	-67280	.02362	.02288	.02321	.02304	1252.04401	1272.86000
.900	-4.939	-56026	-56232	-55930	-56081	.02486	.02411	.02463	.02437	1258.80499	1273.33000
.900	-3.940	-44776	-44844	-44556	-44700	.02409	.02345	.02409	.02377	1263.86700	1273.34000
.900	-2.935	-33008	-33120	-32846	-32983	.02335	.02263	.02288	.02276	1267.46001	1272.92000
.900	-1.929	-21541	-21279	-21404	-20253	.01990	.02028	.02098	.0209	1270.14799	1273.03999
.900	-.918	-.10204	-.10081	-.09858	-.09969	.02124	.02195	.02213	.02204	1271.75000	1273.14000
	GRADIENT	.11427	.11481	.11481	.11491	-.00107	-.00078	-.00088	-.00083	3.19879	-.06756

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 704

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCMC35) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO. 1324/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.100	-7.946	-91216	-91495	-91195	-91345	.00024	.00158	.00189	.00174	1168.96500	1204.78999
1.100	-6.933	-79980	-80168	-79847	-80008	.00654	.00673	.00710	.00692	1177.25999	1204.61000
1.100	-5.936	-68533	-68694	-68422	-68558	.00603	.00589	.00669	.00629	1184.43401	1204.50600
1.100	-4.941	-57072	-57235	-56935	-57085	.00746	.00739	.00783	.00761	1190.59000	1204.64301
1.100	-3.935	-45281	-45396	-45142	-45269	.01047	.00901	.00934	.00917	1195.60001	1204.84200
1.100	-2.935	-33136	-33355	-33098	-33226	.00790	.00644	.00676	.00660	1199.25700	1204.72000
1.100	-1.940	-21554	-21720	-21497	-21608	.00707	.00558	.00658	.00608	1201.96700	1204.67500
1.100	-0.936	-10393	-10550	-10326	-10438	.00907	.00748	.00753	.00751	1203.46500	1204.60500
1.100	.059	00430	.00221	.00421	.00321	.00484	.00483	.00510	.00497	1203.97900	1204.46100
1.100	.985	-11007	-10869	-11028	-10949	-.00146	.00151	-.00140	-.00146	1204.08600	1204.87300
1.100	2.007	-22635	-22604	-22724	-22664	.00013	.00088	.00069	.00078	1204.10600	1204.69901
	GRADIENT	11432	11442	11419	11430	-.00141	-.00121	-.00129	-.00125	1.84027	-.00396

RUN NO. 1370/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.250	-7.973	-99592	-99444	-99592	-99768	.01590	.01399	.01468	.01434	1145.69600	1182.80499
1.250	-6.948	-87128	-87424	-87105	-87264	.02153	.01985	.02042	.02014	1154.07700	1182.64999
1.250	-5.950	-74886	-75071	-74758	-74915	.01769	.01595	.01649	.01617	1161.86200	1182.42500
1.250	-4.947	-61995	-62181	-62181	-62031	.01943	.01925	.01987	.01956	1166.70200	1182.27499
1.250	-3.951	-49556	-49532	-49253	-49392	.02247	.02241	.02294	.02268	1171.37700	1182.27901
1.250	-2.948	-36442	-36478	-36231	-36355	.01872	.01894	.01937	.01915	1176.18700	1182.70900
1.250	-1.946	-24040	-24116	-23905	-24010	.01738	.01775	.01832	.01803	1179.31700	1182.70200
1.250	.941	-11551	-11513	-11522	-11513	.01953	.01962	.02004	.01983	1180.66701	1182.31700
1.250	.074	-01039	-01036	-00846	-00941	.00647	.00471	-.00444	-.00457	1180.69901	1182.54500
1.250	.987	-12215	-12101	-12262	-12181	.02094	.01891	-.01882	-.01886	1181.40100	1182.50101
1.249	2.026	-24983	-25008	-25140	-25074	.01509	.01306	-.01290	-.01298	1181.49500	1182.72000
	GRADIENT	12468	12479	12455	12467	-.00637	-.00600	-.00608	-.00604	2.02936	.04043

RUN NO. 1381/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.400	-7.977	-1.13883	-1.14239	-1.13861	-1.14050	.02059	.02033	.02101	.02067	1126.51199	1164.11800
1.400	-6.948	-99859	-1.00110	-99743	-99927	.02792	.02702	.02772	.02737	1134.86700	1163.87601
1.400	-5.951	-85673	-85516	-85583	-85683	.02583	.02322	.02380	.02351	1142.43600	1164.54201
1.400	-4.954	-71522	-71407	-71570	-71570	.02622	.02395	.02454	.02424	1148.95900	1164.22600
1.400	-3.952	-56817	-57152	-56834	-56993	.02891	.02645	.02701	.02673	1153.96500	1164.02400
1.400	-2.954	-41555	-41770	-41636	-41636	.02498	.02459	.02505	.02482	1157.12300	1163.87300
1.400	-1.948	-27494	-27596	-27344	-27470	.02058	.02033	.02066	.02050	1160.07899	1164.43401
1.400	.948	-13406	-13483	-13191	-13299	.02138	.02119	-.02148	.02134	1163.21300	1164.18100
1.400	.055	00720	.00657	.00863	.00763	.01194	-.01010	-.00997	-.01003	1163.66000	1164.50000
1.399	1.005	-14129	-14058	-14227	-14143	.01636	.01469	-.01458	-.01463	1163.96201	1164.23399
1.400	2.022	-28486	-28562	-28496	-28430	.01662	-.01500	-.01479	-.01490	1161.76801	1163.76100
	GRADIENT	14295	14332	14304	14318	-.00760	-.00694	-.00702	-.00698	1.94493	-.00668

## PARAMETRIC DATA

	RUN NO.	1392/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.450	-7.974	-1.20688	-1.20909	-1.20546	-1.20727	.03625	.03457	.03515	.03486	.03486
1.450	-6.945	-1.05920	-1.06284	-1.05865	-1.06075	.03993	.03817	.03874	.03846	.03846
1.450	-5.947	-90656	-91059	-90735	-90897	.03423	.03356	.03403	.03379	.03379
1.449	-4.945	-75974	-76266	-75950	-76108	.03832	.03828	.03885	.03857	.03857
1.450	-3.946	-60932	-61187	-60903	-61045	.04099	.04133	.04174	.04153	.04153
1.450	-2.942	-44717	-44725	-44477	-44601	.03701	.03731	.03771	.03751	.03751
1.450	-1.938	-29432	-29553	-29334	-29443	.03569	.03621	.03653	.03637	.03637
1.450	-920	-14207	-14338	-14143	-14241	.03909	.03943	.03988	.03966	.03966
1.450	-0.95	-01349	-01439	-01267	-01353	.02430	.02202	.02187	.02195	.02195
1.450	.993	15446	15368	15517	15443	.03657	.03428	.03425	.03426	.03426
1.449	2.018	30273	30449	30547	30498	.03216	.02988	.02992	.02990	.02990
GRADIENT	.15312	.15360	.15330	.15345	.15345	.01267	.01229	.01237	.01233	.01233

	RUN NO.	1437/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.471	-7.972	-1.25827	-1.26129	-1.25751	-1.25940	.03145	.02925	.02992	.02959	.02959
1.471	-6.943	-1.10704	-1.10993	-1.10611	-1.10802	.03723	.03687	.03747	.03717	.03717
1.471	-5.951	-94538	-94974	-94625	-94799	.03826	.03780	.03825	.03802	.03802
1.471	-4.948	-78727	-79030	-78713	-78871	.03884	.03877	.03939	.03908	.03908
1.471	-3.946	-62852	-62975	-62675	-62825	.04090	.04067	.04111	.04089	.04089
1.471	-2.942	-46644	-46648	-46365	-46507	.04146	.04160	.04178	.04169	.04169
1.471	-1.944	-30400	-30528	-30283	-30405	.04064	.04085	.04113	.04099	.04099
1.471	-0.923	-14263	-14371	-14156	-14264	.04204	.04199	.04221	.04210	.04210
1.471	.078	-01250	-01323	-01143	-01233	.02525	.02352	.02340	.02346	.02346
1.471	1.009	.15658	.15782	.15936	.15859	.03564	.03364	.03376	.03370	.03370
1.471	2.019	.31329	.31503	.31609	.31556	.03347	.03167	.03167	.03167	.03167
GRADIENT	.15817	.15870	.15840	.15855	.15855	.01297	.01263	.01272	.01267	.01267

	RUN NO.	1404/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.496	-7.973	-1.30540	-1.30784	-1.30377	-1.30580	.02538	.02380	.02436	.02408	.02408
1.496	-6.944	-1.16149	-1.16293	-1.15885	-1.16089	.03314	.03164	.03211	.03188	.03188
1.496	-5.947	-1.00153	-1.00434	-1.00237	-1.00237	.03071	.02932	.02983	.02958	.02958
1.496	-4.949	-83977	-84018	-83650	-83834	.03589	.03457	.03493	.03475	.03475
1.496	-3.947	-67580	-67661	-67329	-67495	.03828	.03672	.03702	.03687	.03687
1.495	-2.944	-50253	-50327	-50022	-50174	.03760	.03610	.03653	.03631	.03631
1.496	-1.941	-33701	-33742	-33455	-33598	.03869	.03771	.03797	.03784	.03784
1.496	-0.935	-16753	-16708	-16463	-16585	.04113	.03990	.04001	.03995	.03995
1.496	.063	-01711	-01711	-01508	-01610	.02220	.02095	.02118	.02106	.02106
1.496	1.124	.18451	.18442	.18619	.18531	.03226	.03086	.03097	.03092	.03092
1.496	2.030	.34111	.34091	.34205	.34148	.04814	.04740	.04763	.04752	.04752
GRADIENT	.16935	.16925	.16900	.16917	.16900	.00023	.00020	.00022	.00022	.00022

## PARAMETRIC DATA

	RUN NO.	1427/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	-1.50128	-1.50454	-1.50039	-1.50246	.03895	.03749	.03825	.03787	1121.02000	1138.03149	
	-1.36107	-1.36256	-1.35864	-1.36060	.04492	.04332	.04395	.04364	1121.03400	1138.07907	
	-1.16717	-1.16855	-1.16478	-1.16667	.04168	.03952	.04038	.03995	1121.02000	1138.44084	
	-1.950	-1.98965	-1.99074	-1.98718	.048896	.04754	.04662	.04623	1120.93300	1138.31517	
	-3.948	-7.9864	-7.9988	-7.9612	.04935	.04877	.04921	.04899	1120.97600	1138.40346	
	-2.945	-5.7805	-5.7842	-5.7535	.057688	.04071	.04012	.04068	.04040	1120.91901	1138.13499
	-1.942	-3.7501	-3.77558	-3.7297	.037427	.03674	.03603	.03653	.03628	1120.88600	1139.24561
	-1.4019	-1.4019	-1.3996	-1.3810	.013903	.01829	.01898	.01937	.01918	1120.84200	1138.89798
	-1.115	-0.1499	-0.1365	-0.1175	.01270	.02189	.02149	.02127	.02138	1120.74100	1138.19295
	.978	.10794	.10701	.10875	.10788	.02470	.02374	.02362	.02368	1120.63000	1138.96718
	2.017	.36566	.36440	.36542	.36491	.02752	.02608	.02590	.02599	1120.59700	1138.59238
GRADIENT	19236	19243	19243	19223	.01320	.01320	.01279	.01283	-.05607	-.05719	

	RUN NO.	1416/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	-1.44287	-1.44472	-1.44055	-1.44263	.06839	.06732	.06791	.06762	1117.46300	1135.96257	
	-1.24369	-1.24431	-1.24073	-1.24252	.05283	.05178	.05248	.05213	1117.23399	1136.05180	
	-1.00718	-1.00882	-1.00510	-1.00696	.04491	.04385	.04441	.04413	1117.25400	1135.88820	
	-4.946	-8.0951	-8.0948	-8.0775	.02923	.02802	.02865	.02833	1117.23000	1136.21326	
	-3.948	-6.0081	-6.0094	-5.9938	.03243	.03177	.03216	.03196	1117.25999	1135.90446	
	-2.945	-4.2106	-4.2092	-4.1953	.02592	.02397	.02413	.02405	1117.22701	1136.04268	
	-1.942	-2.7428	-2.7445	-2.7196	.02626	.02481	.02512	.02497	1117.20300	1136.00371	
	.943	-1.3507	-1.3345	-1.3122	.02820	.02837	.02819	.02819	1117.12199	1135.67090	
	-1.16	-0.1045	-0.0950	-0.0769	.00860	.02253	.02109	.02078	.02093	1116.94099	1136.49419
	1.001	1.1752	1.1702	1.1890	.11796	.02812	.02648	.02631	.02639	1116.91701	1136.03189
	2.012	.25558	.25646	.25532	.25589	.01897	.01900	.01892	.01896	1116.91701	1136.05058
GRADIENT	1.4973	.14942	.14957	.14955	-.00935	-.00897	-.00903	-.00900	-.05802	.00437	

180 000

BIN NO 1335/ Q BN/L = 2.50 GRADIENT INTERVAL = -5.00 / 5.00

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-7.958	-.90353	-.90559	-.90409	.01766	.01823	.01795	.1236	.14500	.1273 .08000
.900	-6.937	-.78727	-.78829	-.78689	.01804	.01907	.01889	.1244	.41701	.1272 .70000
.900	-5.938	-.67293	-.67453	-.67144	.02265	.02232	.02276	.02254	.1252	.25000
.900	-4.934	-.56005	-.56252	-.55103	.02320	.02270	.02289	.02289	.68600	.1273 .25999
.900	-3.935	-.44795	-.44897	-.44761	.02450	.02407	.02420	.02407	.1263	.87801
.900	-2.935	-.32940	-.33103	-.32976	.02051	.02060	.02056	.02056	.1267	.42500
.900	-1.929	-.21512	-.21304	-.21418	.01963	.01948	.01976	.01962	.1270	.09900
.900	-.918	-.10118	-.10239	-.10009	.02075	.02111	.02129	.02120	.1271	.62000
.900	.038	-.00061	.00096	.00128	.00112	.01679	-.01452	-.01441	.1272	.30293
.900	.980	-.10586	.10492	.10652	.01659	.02271	-.02280	-.02276	.1272	.31300
.900	2.008	-.22372	.22352	.22479	.02495	.02495	-.02495	-.01665	.1272	.28399
	GRADIENT	1.1258	1.1262	1.1277	-.00783	-.00733	-.00736	1.85368	-.02823	

IA310 (AEEDC 16TF-783) FAIRING-OFF DATABASE

PARAMETRIC DATA											
RUN NO.	1357 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00 / 5.00	BETA	=	1.000	PHI	=	180.000
						DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2
MACH	ALPHA	DPACAL	- .72577	- .72313	- .72445	.11396	.11406	.11449	- .11427	1562.69099	1597.08000
.599	- .7.940	- .72306	- .63554	- .63294	- .63424	.11502	.11554	.11580	- .11567	1570.61800	1596.95000
.600	- 6.915	- .63250	- .54132	- .53876	- .54004	.11497	.11623	.11647	- .11635	1577.22099	1596.86000
.599	- 5.911	- .53953	- .44728	- .44484	- .44606	.11373	.11494	.11505	- .11583	40100.40100	1596.83000
.600	- 4.906	- .44634	- .35607	- .35735	- .35502	.11290	.11380	.11393	- .11386	1587.86800	1596.86000
.600	- 3.889	- .35607	- .25921	- .26171	- .25964	.11218	.11263	.11270	- .11266	1591.57300	1596.92999
.600	- 2.869	- .25921	- .1.831	- .16329	- .16510	.10856	.10925	.10925	- .10925	1594.15900	1596.64999
.601	- .777	- .06776	- .06856	- .06670	- .06763	.10115	.10180	.10178	- .10178	1597.63699	1597.17999
.601	- .297	- .02544	- .02372	- .02521	- .02447	.08530	.08605	.08610	- .08608	1596.20399	1597.39999
.600	- 1.188	- .10484	- .10525	- .10652	- .10588	.06893	.06971	.06976	- .06973	1596.16100	1596.72000
.600	- 2.118	- .18962	- .19108	- .19229	- .19168	.06990	.07048	.07043	- .07045	1596.30499	1597.00999
GRADIENT	.09056	.09088	.09056	.09070	.09079	- .00720	- .00725	- .00726	- .00726	1.74066	.0307

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 708

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM037) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.800	-7.940	-.86651	-.86834	-.86551	.86693	.13359	.13416	.13456	.13436	.1342 .16000
.800	-6.922	-.75837	-.75976	-.75689	.75832	.13053	.13081	.13126	.13103	.1341 .98000
.800	-5.920	-.64552	-.64820	-.64549	.64684	.13109	.13098	.13130	.13114	.1342 .03999
.800	-4.914	-.53534	-.53724	-.53502	.53613	.13186	.13164	.13195	.1326 .78799	.1341 .64000
.800	-3.906	-.42587	-.42723	-.42494	.42608	.12892	.12921	.12947	.12934	.1332 .0010001
.800	-2.889	-.31350	-.31474	-.31264	.31369	.12491	.12515	.12551	.12533	.1336 .14900
.801	-1.867	-.20172	-.20198	-.20007	.20103	.12177	.12208	.12241	.12224	.1338 .84599
.800	-8.34	-.08932	-.08850	-.08668	.08759	.11693	.11737	.11744	.11741	.1340 .28999
.800	-2.18	-.02046	-.02012	-.02175	.02094	.10541	.10635	.10630	.10633	.1340 .93800
.800	1.129	-.11948	-.11897	-.11967	.11967	.09167	.09325	.09315	.09320	.1341 .10600
.800	2.084	-.22433	-.22455	-.22534	.22495	.09310	.09378	.09392	.09385	.1341 .03900
	GRADIENT	.10837	.10864	.10845	.10855	-.00615	-.00597	-.00603	-.00600	.1342 .00999
										.00838

RUN NO.	1346/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	1.000	PHI =	180.000
---------	---------	--------	------	---------------------	--------	------	--------	-------	-------	---------

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-7.943	-.89777	-.89977	-.89673	.89826	.13657	.13692	.13748	.13720	.1235 .64500
.900	-6.915	-.78504	-.78634	-.78318	.78476	.13690	.13697	.13751	.13724	.1243 .44800
.900	-5.910	-.66965	-.67140	-.66832	.66986	.13798	.13801	.13841	.13821	.1251 .002000
.900	-4.905	-.55425	-.55652	-.55366	.55509	.13642	.13624	.13664	.13644	.1258 .07899
.900	-3.894	-.44043	-.44167	-.43902	.44035	.13450	.13410	.13445	.13427	.1263 .25101
.901	-2.879	-.32458	-.32522	-.32271	.32396	.13034	.13050	.13087	.13068	.1267 .25800
.900	-1.852	-.20889	-.20758	-.20644	.20758	.12590	.12628	.12650	.12639	.1269 .92200
.900	-.819	-.09236	-.09122	-.09024	.09024	.12157	.12168	.12207	.12187	.1271 .43300
.900	-2.31	-.02041	-.02047	-.02222	.02135	.10969	.10993	.10986	.10989	.1271 .91400
.900	1.141	-.12316	-.12202	-.12361	.12282	.09648	.09674	.09698	.09686	.1271 .84300
.900	2.095	-.23146	-.23145	-.23271	.23208	.09650	.09718	.09730	.09724	.1272 .04401
	GRADIENT	.11200	.11224	.11201	.11212	-.00632	-.00621	-.00626	-.00624	1.85763
										-.04718

RUN NO.	1336/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00
---------	---------	--------	------	---------------------	--------	------

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-7.943	-.89777	-.89977	-.89673	.89826	.13657	.13692	.13748	.13720	.1235 .64500
.900	-6.915	-.78504	-.78634	-.78318	.78476	.13690	.13697	.13751	.13724	.1243 .44800
.900	-5.910	-.66965	-.67140	-.66832	.66986	.13798	.13801	.13841	.13821	.1251 .002000
.900	-4.905	-.55425	-.55652	-.55366	.55509	.13642	.13624	.13664	.13644	.1258 .07899
.900	-3.894	-.44043	-.44167	-.43902	.44035	.13450	.13410	.13445	.13427	.1263 .25101
.901	-2.879	-.32458	-.32522	-.32271	.32396	.13034	.13050	.13087	.13068	.1267 .25800
.900	-1.852	-.20889	-.20758	-.20644	.20758	.12590	.12628	.12650	.12639	.1269 .92200
.900	-.819	-.09236	-.09122	-.09024	.09024	.12157	.12168	.12207	.12187	.1271 .43300
.900	-2.31	-.02041	-.02047	-.02222	.02135	.10969	.10993	.10986	.10989	.1271 .91400
.900	1.141	-.12316	-.12202	-.12361	.12282	.09648	.09674	.09698	.09686	.1271 .84300
.900	2.095	-.23146	-.23145	-.23271	.23208	.09650	.09718	.09730	.09724	.1272 .04401
	GRADIENT	.11200	.11224	.11201	.11212	-.00632	-.00621	-.00626	-.00624	1.85763
										-.04718

RUN NO.	1325/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00
---------	---------	--------	------	---------------------	--------	------

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.100	-7.949	-.91327	-.91015	-.91171	.91171	.12454	.12343	.12418	.12380	.1168 .26900
1.100	-6.926	-.79537	-.79490	-.79635	.79435	.12395	.12213	.12411	.12385	.1176 .02299
1.100	-5.948	-.68408	-.68286	-.68435	.68435	.12114	.12113	.12157	.12135	.1183 .65601
1.100	-4.924	-.56522	-.56696	-.56411	.56554	.12299	.12217	.12263	.12240	.1189 .68800
1.100	-3.925	-.45052	-.44983	-.44787	.44920	.12240	.12170	.12187	.12179	.1194 .80299
1.100	-2.919	-.33032	-.33236	-.32974	.33105	.11916	.11782	.11819	.11800	.1198 .99699
1.100	-1.912	-.21476	-.21652	-.21401	.21526	.11595	.11422	.11449	.11435	.1201 .55901
1.100	-.917	-.10300	-.10136	-.10093	.10197	.11401	.11209	.11246	.11228	.1203 .19099
1.100	.089	.00689	.00478	.00684	.00581	.11431	.11282	.11300	.11291	.1203 .92700
1.100	1.052	.11579	.11385	.11558	.11472	.11110	.10973	.10992	.10983	.1204 .00400
1.100	2.026	.22767	.22697	.22823	.22760	.11268	.11210	.11136	.11133	.1203 .99001
	GRADIENT	.11375	.11355	.11366	-.00174	-.00183	-.00187	-.00185	1.95090	-.000087

## PARAMETRIC DATA

	RUN NO.	1371/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000	
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	-.99045	-.99391	-.99034	-.99213	.14489	.14413	.14485	.14449	1144.48000	1182.35699	
1.250	-.86751	-.86945	-.86605	-.86775	.14830	.14669	.14733	.14701	1153.21100	1182.77400	
-6.928	-.74346	-.74540	-.74228	-.74384	.14528	.14457	.14518	.14487	1161.70900	1182.96700	
1.250	-.5.920	-.6.1247	-.6.1172	-.6.1316	.14482	.14415	.14470	.14443	1166.49899	1182.39700	
-4.923	-.6.1250	-.6.1247	-.6.1172	-.6.1316	.14482	.14415	.14470	.14443	1166.49899	1182.39700	
1.250	-.3.909	-.4.8732	-.4.8733	-.4.8593	.14557	.14488	.14550	.14519	1171.18401	1182.19701	
-2.895	-.35752	-.35797	-.35627	-.35712	.13986	.13982	.14029	.14006	1175.43600	1182.23900	
1.250	-.1.882	-.23219	-.23303	-.23188	.13562	.13580	.13607	.13594	1178.51300	1182.47501	
-1.860	-.10646	-.10732	-.10521	-.10626	.13216	.13247	.13276	.13261	1180.98100	1182.74400	
1.250	-.186	-.02057	-.01921	-.02095	.02008	.12426	.12447	.12483	.12465	1181.17900	1182.24001
1.122	1.122	1.13649	1.13531	1.13676	.13604	.11261	.11301	.11321	.11311	1181.48801	1182.63499
1.250	2.079	.25437	.25471	.25576	.25523	.11026	.11069	.11090	.11080	1181.41701	1182.80099
GRADIENT	.12373	.12383	.12360	.12372	.00540	-.00523	-.00529	-.00526	2.08869	.06210	

	RUN NO.	1382/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000	
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	-.1.3257	-.1.13614	-.1.13227	-.1.13420	.17109	.16992	.17060	.17026	1125.68500	1164.38699	
1.399	-.6.930	-.99398	-.99651	-.99468	.17180	.17063	.17136	.17099	1134.26100	1163.89500	
-6.930	-.85022	-.85221	-.84856	-.85039	.16933	.16846	.16912	.16879	1141.77299	1164.21600	
-5.923	-.4.921	-.70621	-.70551	-.70722	.16811	.16725	.16785	.16755	1148.33400	1164.50301	
-4.921	-.3.914	-.56993	-.56300	-.56004	.16851	.16767	.16834	.16801	1153.97800	1164.44000	
-3.914	-.2.905	-.40910	-.41115	-.40942	.16119	.16038	.16083	.16060	1157.27000	1163.85899	
-2.905	-.1.890	-.26534	-.266662	-.26423	.15577	.15482	.15519	.15500	1159.49100	1164.14900	
-1.890	-.870	-.12592	-.12296	-.12407	.15351	.15289	.15314	.15302	1162.64101	1164.40500	
-.870	-.172	.01927	.02132	.02029	.14449	.14362	.14391	.14376	1163.49400	1163.89200	
1.400	1.117	.15520	.15442	.15590	.15516	.13196	.13136	.13159	1163.30299	1164.31400	
1.400	2.073	.29064	.28996	.29126	.29061	.12752	.12695	.12737	.12716	1162.35201	1164.58200
GRADIENT	.14200	.14229	.14210	.14225	.00614	-.00614	-.00614	-.00612	1.98296	.00239	

	RUN NO.	1394/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000	
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	-.1.20424	-.1.20474	-.1.20097	-.1.20285	.18994	.18969	.19050	.19009	1118.75400	1158.65199	
1.450	-.6.906	-.1.05443	-.1.05821	-.1.05455	.19455	.19424	.19491	.19457	1127.35500	1158.53700	
-5.901	-.89972	-.90383	-.90051	-.90217	.19016	.18966	.19035	.19001	1134.29700	1158.44800	
-4.896	-.75000	-.75214	-.74905	-.75059	.18921	.18909	.18976	.18943	1140.31100	1158.40601	
-3.882	-.59885	-.60123	-.59833	-.59978	.19235	.19262	.19317	.19290	1147.72099	1158.46700	
-2.864	-.43612	-.43652	-.43386	-.43519	.18428	.18399	.18490	.18444	1150.73500	1158.41200	
-.834	-.27789	-.27795	-.27700	-.27818	.17792	.17767	.17833	.17800	1152.48199	1158.27499	
1.450	-.781	-.12405	-.12341	-.12441	.17563	.17524	.17568	.17546	1127.20799	1158.32200	
1.450	.281	.03634	.03798	.03716	.15412	.15358	.15375	.15366	1160.62199	1158.26100	
1.450	1.175	.17705	.17634	.17812	.17723	.13089	.13101	.13109	1157.95799	1158.12900	
1.450	2.113	.31278	.31445	.31545	.31495	.12233	.12293	.12320	.12306	1154.86700	1158.47701
GRADIENT	.15204	.15237	.15209	.15223	.01018	-.01014	-.01023	-.01018	2.23706	-.01942	

## PARAMETRIC DATA

RUN NO.		1438/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00			BETA =	1.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PPTF	PT2F
1.471	-7.882	-1.24418	-1.24463	-1.244335	-1.244499	.19923	.19881	.19943	.19912	1115.16000	1150.10518
1.471	-6.913	-1.10244	-1.10131	-1.10323	-1.10323	.19939	.19890	.19945	.19917	1124.86900	1150.26605
1.471	-5.908	-1.93762	-1.94208	-1.93854	-1.94031	.19891	.19894	.19930	.19912	1130.94901	1150.32173
1.471	-4.903	-1.77763	-1.78069	-1.77745	-1.77907	.19736	.19689	.19741	.19715	1136.22301	1149.77440
1.471	-3.888	-1.61791	-1.61793	-1.61644	-1.61793	.19641	.19616	.19676	.19646	1140.11000	1149.53970
1.471	-2.871	-1.45494	-1.45509	-1.45225	-1.45367	.19466	.19455	.19495	.19475	1144.45700	1149.97777
1.471	-1.843	-1.28905	-1.29066	-1.28807	-1.28936	.18885	.18891	.18914	.18903	1146.02200	1149.95706
1.471	-8.00	-1.12442	-1.12360	-1.12558	-1.12459	.18072	.18008	.18040	.18024	1146.18401	1149.73938
1.471	.260	.04337	.04090	.04272	.04181	.15668	.15596	.15624	.15610	1146.82201	1150.05962
1.471	1.159	.17904	.18005	.18207	.18106	.13392	.13328	.13362	.13345	1146.62399	1149.94026
1.471	2.104	.32662	.32848	.32963	.32906	.12656	.12569	.12578	.12573	1147.94400	1149.66922
1.471	GRADIENT	1.5788	.15835	.15807	.15821	-.01093	-.01102	-.01107	-.01104	1.44485	.01609
RUN NO.		1405/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00			BETA =	1.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PPTF	PT2F
1.496	-7.947	-1.30191	-1.30424	-1.30012	-1.30218	.19455	.19397	.19454	.19426	1113.85899	1146.96243
1.496	-6.916	-1.15637	-1.15786	-1.15362	-1.15574	.20253	.20157	.20234	.20195	1113.83600	1146.85594
1.496	-5.906	-1.94548	-1.99732	-1.99325	-1.99528	.20225	.20168	.20223	.20195	1127.74600	1146.69571
1.496	-4.902	-1.83017	-1.83046	-1.82674	-1.82860	.20167	.20119	.20182	.20151	1127.66901	1146.59869
1.496	-3.892	-1.66305	-1.66416	-1.66075	-1.66246	.20756	.20691	.20733	.20712	1127.61099	1146.62418
1.496	-2.878	-1.49068	-1.49068	-1.48770	-1.48919	.20362	.20296	.20348	.20322	1132.74200	1147.25587
1.496	-1.852	-1.31974	-1.32048	-1.31750	-1.31899	.20111	.20068	.20068	.20049	1143.04401	1146.68967
1.496	-8.14	-1.14647	-1.14432	-1.14539	-1.14507	.19507	.19461	.19506	.19484	1143.76700	1146.54037
1.496	.247	.03857	.03739	.03945	.03842	.17254	.17175	.17209	.17192	1143.89000	1146.40886
1.496	1.157	.19606	.19592	.19752	.19672	.15172	.15049	.15067	.15058	1143.83600	1147.17148
1.496	2.104	.35167	.35138	.35170	.35154	.14112	.13982	.14010	.13996	1143.71600	1146.77446
1.496	GRADIENT	1.6914	.16920	.16877	.16899	-.00943	-.00953	-.00958	-.00955	2.69443	.01401
RUN NO.		1428/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00			BETA =	1.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PPTF	PT2F
1.517	-7.947	-1.50782	-1.51114	-1.50670	-1.50892	.23216	.23127	.23214	.23170	1116.96201	1138.89478
1.517	-6.916	-1.36145	-1.36300	-1.35879	-1.36089	.23744	.23772	.23853	.23813	1116.97200	1138.71097
1.517	-5.913	-1.16246	-1.16396	-1.16002	-1.16199	.23928	.23814	.23911	.23863	1116.98199	1138.84438
1.517	-4.902	-1.98268	-1.98402	-1.97997	-1.98200	.24201	.24119	.24202	.24160	1116.90500	1138.47078
1.517	-3.893	-1.78436	-1.78496	-1.78158	-1.78327	.25286	.25164	.25220	.25192	1116.90500	1138.99974
1.517	-2.908	-1.56507	-1.56602	-1.56294	-1.56448	.23320	.23273	.23332	.23303	1116.89500	1139.40086
1.517	-1.853	-1.36210	-1.36206	-1.35938	-1.36072	.21724	.21681	.21732	.21707	1116.88499	1138.72177
1.517	.808	-.15461	-.15478	-.15250	-.15364	.18187	.18074	.18120	.18097	1116.81799	1138.59059
1.517	.246	.00777	.00741	.00946	.00843	.11226	.11188	.11226	.11207	1116.77400	1139.41757
1.517	1.157	.17153	.17081	.17286	.17184	.13837	.13726	.13756	.13741	1116.78400	1139.14392
1.517	2.102	.36781	.36626	.36754	.36690	.15403	.15325	.15338	.15331	1116.73000	1138.98862
1.517	GRADIENT	1.9061	.19026	.19061	.19044	-.01887	-.01894	-.01894	-.01890	-.02669	.05046

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 711

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM037) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1417/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	-1.44295	-1.44094	.23282	DPB1	23255	PTTFF	PT2F
1.543	-7.946	-1.44092	-1.44295	-1.43893	-1.44094	.23183	DPB2	.23219	1115.88901	1136.25792
1.543	-6.915	-1.22759	-1.22827	-1.22429	-1.22628	.23098	DPBCAL	.23017	1115.85600	1136.29724
1.543	-5.911	-1.00236	-1.00423	-1.00049	-1.00236	.21530	DPB1	.21496	1115.86600	1136.25497
1.542	-4.907	-7.93558	-7.9441	-7.9086	-7.9264	.19818	DPB2	.19792	1115.82201	1135.97372
1.554	-3.893	-5.9261	-5.9319	-5.8989	-5.9154	.18544	DPBCAL	.18550	1115.82201	1149.77284
1.554	-2.878	-4.20223	-4.1972	-4.1688	-4.1830	.16012	DPB1	.15903	1115.81200	1149.79994
1.554	-1.847	-2.65056	-2.6592	-2.6329	-2.6461	.15059	DPB2	.14967	1115.75500	1149.53284
1.543	-8.11	-1.25557	-1.2459	-1.2247	-1.2353	.14200	DPBCAL	.14155	1115.71100	1136.25536
1.543	.246	.01438	.01427	.01630	.01528	.12964	DPB1	.12876	1115.69099	1136.32574
1.554	1.160	.13305	.13242	.13405	.13233	.11666	DPB2	.11626	1115.60000	1149.62347
1.554	2.101	.26427	.26410	.26518	.26464	.11683	DPBCAL	.11657	1115.62399	1149.70070
GRADIENT	.14734	.14739	.14705	.14722	.14722	-.01198	DPB1	-.01198	-.03419	.45944

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM038) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1358/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	-72719	-72446	-.72583	DPB1	21333	PTTFF	PT2F
.599	-7.904	-6.3011	-6.3298	-.63025	-.63161	.21196	DPB2	.21320	1561.63200	1596.96001
.599	-6.881	-5.867	-5.3680	-.53862	-.53735	.21015	DPBCAL	.21096	1569.24800	1596.74001
.600	-4.858	-4.4287	-4.4406	-.44159	-.44282	.20860	DPB1	.21002	1576.07600	1597.03999
.600	-3.840	-3.5252	-3.5391	-.35150	-.35270	.20506	DPB2	.20680	1582.13200	1596.84000
.600	-2.811	-2.5686	-2.5910	-.25686	-.25799	.20481	DPBCAL	.20596	1586.71300	1597.00999
.601	-1.776	-.15971	-.16095	-.16095	-.16003	.20083	DPB1	.20252	1590.56500	1597.25000
.601	-.745	-.06591	-.06662	-.06484	-.06573	.19438	DPB2	.19547	1593.36400	1597.41000
.600	.265	.02335	.02170	.02246	.02323	.18673	DPBCAL	.18803	1594.80800	1597.00999
.600	1.223	1.0844	1.0808	1.0940	1.0874	.17652	DPB1	.17720	.17717	.17720
.600	2.191	.19477	.19637	.19742	.19689	.16971	DPB2	.17015	.17018	.17015
GRADIENT	.09072	.09103	.09083	.09093	-.00630	-.00642	DPBCAL	.16595	1595.85201	1596.92999
							DPB1	-.00647	1.88116	-.01123



## PARAMETRIC DATA

RUN NO. 1372 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
MACH	.99380	-.99028	-.99204	.27788	.27728	.27811	.27769	1.142 .92200	1.182 .90700
ALPHA	-7.933	-.86910	-.86564	-.86737	.27656	.27732	.27802	.27767	.27767
	-6.901	-.86730	-.74122	-.74286	.27387	.27357	.27401	.27379	.27379
	-5.895	-.74217	-.61110	-.61003	.26957	.27044	.27001	.1165 .08099	.1182 .30600
	-5.250	-.61110	-.61152	.26974	.26957	.27044	.27001	.1165 .08099	.1182 .30600
	-4.885	-.48396	-.48571	-.48430	.26831	.26874	.26853	.1169 .63600	.1182 .16400
	-3.881	-.48396	-.35667	-.35546	.26514	.26440	.26501	.26471 .1174 .32500	.1182 .45399
	-2.865	-.35536	-.22959	-.22840	.25698	.25630	.25694	.25662 .1177 .54500	.1182 .38499
	-1.850	-.22834	-.10600	-.10495	.25085	.25102	.25149	.25126 .1179 .59100	.1182 .50000
	-8.41	-.10563	-.01692	-.01603	.24655	.24647	.24680	.24663 .1180 .64200	.1182 .80800
	-1.250	-.01672	-.01515	-.01369	.24324	.24335	.24345	.24345 .1180 .97099	.1182 .82600
	.160	.13687	.13544	.13699	.23689	.23668	.23705	.23686 .1180 .74899	.1182 .80701
	1.249	.1332	.25998	.26048	.23689	.23668	.23705	.23686 .1180 .74899	.1182 .80701
	2.124	.25998	.12384	.12384	-.00494	-.00492	-.00499	-.00495 .2.23015	.09492
GRADIENT	12397	.12411	1.2398	1.2398					

RUN NO. 1383 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
MACH	.99404	-.1.13013	-1.13208	.32590	.32448	.32099	.32164	.32487 .1123 .78200	.1164 .36501
ALPHA	-1.13025	-.99496	-.99126	-.99311	.32156	.31579	.31677	.32132 .1132 .92400	.1164 .33000
	-6.910	-.99202	-.84966	-.84790	.31579	.31105	.31116	.31705 .1140 .37900	.1164 .22099
	-5.900	-.84966	-.85155	-.84793	.31107	.31064	.31034	.31116 .1146 .24400	.1163 .80701
	-4.897	-.70308	-.70528	-.70370	.31064	.30660	.30626	.31075 .1152 .34801	.1164 .38800
	-4.897	-.70308	-.56195	-.55886	.30660	.29573	.29530	.30651 .1156 .95000	.1164 .58400
	-3.883	-.55847	-.40730	-.40671	.29573	.28865	.28850	.29561 .1159 .14400	.1164 .29100
	-2.875	-.40730	-.26104	-.26054	.28865	.28913	.28881	.28881 .1160 .21899	.1163 .83400
	-1.860	-.26104	-.12168	-.12052	.28913	.28396	.28357	.28378 .1161 .46201	.1164 .08501
	-.854	-.12211	-.11937	-.11937	.28396	.28077	.28070	.28088 .1161 .77400	.1164 .31900
	1.400	.01785	.01712	.01815	.28077	.27260	.27290	.27295 .1162 .33501	.1164 .41100
	1.400	.01785	.15577	.15584	.29632	.29695	.29730	-.00582 .00582	-.00591 .00587
GRADIENT	14236	.14270	.14242	.14256					

RUN NO. 1395 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
MACH	1.9776	-.1.20032	-1.19647	-.1.19839	.35423	.35474	.35571	.35522 .1117 .06100	.1158 .61200
ALPHA	-7.907	-.05218	-.04870	-.05044	.35242	.35315	.35386	.35350 .1125 .73900	.1158 .80000
	-6.875	-.04840	-.89664	-.89926	.34639	.34661	.34718	.34679 .1132 .69400	.1158 .68201
	-5.863	-.90090	-.74122	-.74275	.34204	.34131	.34197	.34164 .1138 .78500	.1158 .24800
	-4.848	-.74188	-.59486	-.59335	.34332	.34241	.34305	.34273 .1145 .91701	.1158 .45599
	-3.831	-.59271	-.42831	-.42963	.33806	.33713	.33775	.33744 .1150 .52000	.1158 .24699
	-2.807	-.43071	-.43096	-.42831	.32548	.32514	.32565	.32539 .1151 .45100	.1158 .14700
	1.450	-.2.6925	-.27076	-.26855	.32548	.31538	.31574	.31556 .1153 .57700	.1158 .63600
	1.450	-.2.6925	-.11619	-.11718	.31584	.31538	.31574	.31556 .1153 .57700	.1158 .63600
	1.450	-.1679	-.03394	-.03300	.30276	.30299	.30326	.30312 .1155 .13600	.1158 .70200
	1.450	-.03206	-.17823	-.17731	.29267	.29329	.29298	.29298 .1154 .57500	.1158 .13000
	1.450	-.17639	-.32564	-.32564	.27951	.27937	.27937	.27937 .1154 .39700	.1158 .37199
	1.449	-.32336	-.32519	-.32509	-.00948	-.00942	-.00940	-.00940 .1.99973	-.01342
GRADIENT	15169	.15181	.15209	.15195					

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 714

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM038) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.471	-7.914	-1.24662	-1.24890	-1.24555	-1.24722	.36419	.36331	.36320	1112.95300	1149.99469
1.471	-6.874	-1.09690	-1.0994	-1.09629	-1.09811	.36355	.36214	.36199	1122.97400	1149.57213
1.471	-5.871	-1.93403	-1.93845	-1.93461	-1.93653	.36048	.35938	.35921	1129.50500	1149.94379
1.471	-4.859	-1.77374	-1.77352	-1.77673	-1.77513	.35373	.35248	.35257	1134.82300	1149.53438
1.471	-3.843	-1.61302	-1.61458	-1.61148	-1.61303	.35342	.35231	.35251	1139.91901	1149.34056
1.471	-2.823	-1.44601	-1.44646	-1.44379	-1.44513	.34931	.34831	.34865	1143.36900	1149.64380
1.471	-1.794	-1.28232	-1.28352	-1.28115	-1.28233	.34201	.34146	.34164	1146.67101	1149.73744
1.471	-1.767	-1.12057	-1.12209	-1.11984	-1.12097	.32882	.32839	.32863	1147.05400	1149.63411
1.471	.237	.03696	.03460	.03642	.03551	.31357	.31339	.31352	1147.12100	1149.66817
1.471	1.199	1.8274	1.8446	1.8602	1.8524	.30314	.30341	.30411	1147.90700	1149.27727
1.471	2.176	.33580	.33783	.33886	.33835	.29142	.29141	.29145	1148.96201	1149.72163
GRADIENT	.15777	.15831	.15801	.15816	.15816	-.00947	-.00928	-.00930	.1.78470	.01161

RUN NO. 1439/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.496	-7.918	-1.29553	-1.29827	-1.29406	-1.29617	.36673	.36596	.36589	.36593	1112.05000
1.496	-6.885	-1.14674	-1.14851	-1.14429	-1.14640	.37534	.37389	.37464	.37426	1112.33800
1.496	-5.877	-.99008	-.99266	-.98894	-.99080	.37256	.37119	.37188	.37154	1128.01900
1.496	-4.860	-.82125	-.82138	-.81781	-.81960	.36806	.36691	.36721	.36706	1127.98500
1.496	-3.851	-.65392	-.65523	-.65182	-.65353	.36866	.36753	.36813	.36783	1127.94200
1.496	-2.829	-.47850	-.47914	-.47782	-.47771	.36826	.36722	.36779	.36750	1143.22900
1.496	-1.803	-.30838	-.30902	-.30614	-.30758	.36254	.36227	.36178	.36203	1144.92200
1.496	-.781	-.13782	-.13742	-.13507	-.13624	.35416	.35357	.35399	.35378	1144.81100
1.496	.222	.03271	.03149	.03358	.03253	.34154	.34157	.34171	.34164	1144.71400
1.496	1.186	1.9590	1.9563	1.9730	1.9647	.33060	.33048	.33067	.33058	1144.64700
1.496	2.167	.35880	.35805	.35850	.35828	.31603	.31606	.31628	.31617	1144.59300
GRADIENT	16811	.16811	.16772	.16772	.16791	-.00758	-.00739	-.00743	-.00744	2.42792

RUN NO. 1406/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.496	-7.918	-1.29553	-1.29827	-1.29406	-1.29617	.36673	.36596	.36589	.36593	1112.05000
1.496	-6.885	-1.14674	-1.14851	-1.14429	-1.14640	.37534	.37389	.37464	.37426	1112.33800
1.496	-5.877	-.99008	-.99266	-.98894	-.99080	.37256	.37119	.37188	.37154	1146.81964
1.496	-4.860	-.82125	-.82138	-.81781	-.81960	.36806	.36691	.36721	.36706	1146.63100
1.496	-3.851	-.65392	-.65523	-.65182	-.65353	.36866	.36753	.36813	.36783	1127.94200
1.496	-2.829	-.47850	-.47914	-.47782	-.47771	.36826	.36722	.36779	.36750	1146.52422
1.496	-1.803	-.30838	-.30902	-.30614	-.30758	.36254	.36227	.36178	.36203	1144.92200
1.496	-.781	-.13782	-.13742	-.13507	-.13624	.35416	.35357	.35399	.35378	1144.81100
1.496	.222	.03271	.03149	.03358	.03253	.34154	.34157	.34171	.34164	1144.71400
1.496	1.186	1.9590	1.9563	1.9730	1.9647	.33060	.33048	.33067	.33058	1146.88390
1.496	2.167	.35880	.35805	.35850	.35828	.31603	.31606	.31628	.31617	1146.87140
GRADIENT	16811	.16811	.16772	.16772	.16791	-.00758	-.00739	-.00743	-.00744	2.42792

RUN NO. 1429/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.518	-7.914	-1.49009	-1.49365	-1.48965	-1.49165	.43123	.42997	.43099	.43048	1116.61000
1.518	-6.885	-1.35301	-1.35446	-1.35031	-1.35238	.43755	.43642	.43754	.43698	1116.60001
1.518	-5.877	-1.15797	-1.15946	-1.15546	-1.15737	.43808	.43817	.43855	.43803	1138.85132
1.518	-4.862	-1.96821	-1.96959	-1.96598	-1.96779	.43636	.43414	.43502	.43458	1116.59000
1.518	-3.851	-.77260	-.77312	-.76972	-.77142	.44790	.44559	.44633	.44596	1116.52299
1.519	-2.830	-.55163	-.55289	-.54981	-.55135	.42985	.42783	.42843	.42813	1116.53300
1.518	-1.803	-.35731	-.35740	-.35545	-.35643	.40500	.40258	.40317	.40288	1116.55600
1.517	-.783	-.15996	-.15921	-.15681	-.15801	.37393	.37121	.37179	.37150	1116.48900
1.517	.224	.02274	.02258	.02437	.02348	.34600	.34471	.34509	.34490	1116.45900
1.518	1.185	1.9351	1.9269	1.9425	1.9347	.34615	.34497	.34535	.34516	1116.42599
1.518	2.165	.38948	.38829	.38935	.38882	.35016	.34891	.34910	.34900	1116.41600
GRADIENT	19230	.19235	.19199	.19217	.19199	-.01653	-.01645	-.01636	-.01640	-.02334

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.518	-7.914	-1.49009	-1.49365	-1.48965	-1.49165	.43123	.42997	.43099	.43048	1116.61000
1.518	-6.885	-1.35301	-1.35446	-1.35031	-1.35238	.43755	.43642	.43754	.43698	1116.60001
1.518	-5.877	-1.15797	-1.15946	-1.15546	-1.15737	.43808	.43817	.43855	.43803	1138.85132
1.518	-4.862	-1.96821	-1.96959	-1.96598	-1.96779	.43636	.43414	.43502	.43458	1116.59000
1.518	-3.851	-.77260	-.77312	-.76972	-.77142	.44790	.44559	.44633	.44596	1116.52299
1.519	-2.830	-.55163	-.55289	-.54981	-.55135	.42985	.42783	.42843	.42813	1116.53300
1.518	-1.803	-.35731	-.35740	-.35545	-.35643	.40500	.40258	.40317	.40288	1116.55600
1.517	-.783	-.15996	-.15921	-.15681	-.15801	.37393	.37121	.37179	.37150	1116.48900
1.517	.224	.02274	.02258	.02437	.02348	.34600	.34471	.34509	.34490	1116.45900
1.518	1.185	1.9351	1.9269	1.9425	1.9347	.34615	.34497	.34535	.34516	1116.42599
1.518	2.165	.38948	.38829	.38935	.38882	.35016	.34891	.34910	.34900	1116.41600
GRADIENT	19230	.19235	.19199	.19217	.19199	-.01653	-.01645	-.01636	-.01640	-.02334

DATE 04 OCT 91

(UCM038) ( 04 OCT 91 )

PAGE 714

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 715

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM038) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1418/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTf	PT2F
1.543	-7.916	-1.44035	-1.44269	-1.43860	-1.44065	.42798	.42520	.4263	.42566	.4256
1.543	-6.884	-1.22164	-1.22259	-1.21844	-1.22051	.41211	.40956	.41030	.40993	.4117
1.542	-5.876	-1.01440	-1.01658	-1.01283	-1.01470	.40220	.39935	.40026	.39981	.53300
1.543	-4.865	-8.0413	-8.0474	-8.0120	-8.0297	.37022	.37102	.37062	.1117	.1136
1.543	-3.851	-6.0973	-6.1053	-6.0719	-6.0886	.34286	.34186	.34215	.1117	.1136
1.543	-2.829	-4.3128	-4.3109	-4.2820	-4.2964	.31159	.31116	.31170	.1117	.1136
1.543	-1.804	-2.7371	-2.7429	-2.7184	-2.7306	.28475	.28481	.28515	.1117	.1137
1.543	-780	-1.3154	-1.3034	-1.2828	-1.2931	.27357	.27359	.27367	.1117	.1136
1.543	.223	.00367	.00324	.00525	.00425	.26349	.26341	.26351	.1117	.1136
1.543	1.187	.13415	.13367	.13533	.13450	.26206	.26186	.26222	.1117	.1136
1.542	2.165	.27404	.27407	.27556	.27481	.26231	.26305	.26327	.1117	.1136
GRADIENT		.15047	.15047	.15016	.15032	-.01576	-.01549	-.01553	-.03011	.00966

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM039) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1359/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	3.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTf	PT2F
.600	-7.870	-.72306	-.72603	-.72343	-.72473	.30678	.30832	.30868	.30850	.1559
.600	-6.847	-.62907	-.63171	-.62903	-.63037	.30474	.30600	.30642	.30621	.1566
.600	-5.836	-.53587	-.53740	-.5315	-.53627	.30313	.30427	.30474	.30451	.1573
.601	-4.820	-.43930	-.44042	-.43791	-.43917	.30065	.30160	.30177	.30168	.1579
.601	-3.798	-.34692	-.34909	-.34679	-.34794	.29574	.29707	.29722	.29715	.1585
.601	-2.772	-.25407	-.25592	-.25378	-.25485	.29241	.29378	.29395	.29386	.1588
.600	-1.746	-.16034	-.16165	-.15957	-.16061	.28472	.28591	.28622	.28606	.1591
.601	-.728	-.06626	-.06702	-.06539	-.06621	.27775	.27891	.27913	.27902	.1593
.601	.283	.02449	.02284	.02447	.02365	.26946	.27113	.27110	.27111	.1594
.601	1.256	1.1123	1.11054	1.11184	1.1119	.26383	.26581	.26586	.26584	.1594
.601	2.230	.19980	.20144	.20255	.20199	.26129	.26318	.26321	.26320	.1594
GRADIENT		.09073	.09106	.09086	.09096	-.00603	-.00590	-.00592	-.00591	.2.04454

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 716  
(UCM039) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1348/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	3.000	PHI =	180.000	
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB2	PTTF	PT2F	
.800	-7.894	- .86781	- .86957	- .86827	.36320	.36320	.36288	.36304	1299.94800	1342.12000		
.800	-6.871	- .75479	- .75693	- .75559	.35704	.35763	.35812	.35787	1308.22400	1342.06000		
.800	-5.863	- .64545	- .64745	- .64613	.35402	.35540	.35575	.35557	1316.07001	1342.24001		
.800	-4.855	- .53082	- .53262	- .53012	.35156	.35266	.35314	.35290	1323.03700	1342.17000		
.800	-3.840	- .41930	- .42066	- .41814	.341940	.34706	.34802	.34838	1328.45500	1342.17999		
.800	-2.821	- .30993	- .31095	- .30860	.30977	.34266	.34373	.34401	1332.87801	1341.87000		
.800	-1.811	- .19827	- .19847	- .19748	.33699	.33828	.33851	.33840	1336.17999	1341.84000		
.800	- .799	- .08995	- .08889	- .08749	.08819	.32893	.32975	.33016	.32995	1338.23199	1341.94000	
.800	.208	.01784	.01795	.01964	.01879	.32276	.32378	.32400	.32389	1339.25000	1341.92999	
.800	1.184	.12620	.12507	.12611	.12559	.31858	.31992	.32008	.32000	1339.67599	1342.00999	
.800	2.163	.23433	.23424	.23526	.23475	.31645	.31746	.31762	.31754	1339.65300	1342.02000	
	GRADIENT	.10878	.10899	.10875	.10887	-.00541	-.00540	-.00542	-.00542	.2.30181	-.01948	

	RUN NO.	1338/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	3.000	PHI =	180.000	
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB2	PTTF	PT2F	
.900	-7.891	- .89593	- .89888	- .89734	.37787	.37648	.37742	.37695	1231.95000	1273.28000		
.900	-6.864	- .78145	- .78308	- .78163	.37000	.36908	.36960	.36934	1239.19800	1272.64999		
.900	-5.856	- .66799	- .67000	- .66714	.36857	.36707	.36680	.36709	1246.74600	1272.83000		
.900	-4.840	- .55069	- .55198	- .55058	.36393	.36499	.36477	.36488	1254.04800	1273.11000		
.900	-3.827	- .43388	- .43508	- .43375	.36097	.36183	.36139	.36161	1259.93600	1273.09000		
.900	-2.811	- .31994	- .32042	- .31920	.35537	.35673	.35706	.35689	1264.23500	1273.00000		
.900	-1.792	- .20403	- .20446	- .20324	.34947	.35047	.35066	.35057	1267.38300	1272.99001		
.900	- .782	- .09186	- .09045	- .08867	.34096	.34137	.34159	.34148	1269.17300	1272.63000		
.900	.223	.02041	.01990	.02179	.02085	.33454	.33520	.33548	.33534	1270.08000	1272.92999	
.900	1.198	.13118	.13082	.13227	.13155	.32972	.33090	.33106	.33098	1270.83200	1272.99001	
.900	2.177	.24336	.24320	.24459	.24390	.32755	.32813	.32837	.32825	1270.50999	1272.78000	
	GRADIENT	.11281	.11298	.11276	.11287	-.00572	-.00572	-.00572	-.00570	.2.24770	-.04022	

	RUN NO.	1327/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	3.000	PHI =	180.000	
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB2	PTTF	PT2F	
1.099	-7.937	- .91338	- .91655	- .91499	.36241	.36198	.36161	.36179	1163.82600	1205.05701		
1.100	-6.912	- .79656	- .79882	- .79722	.36142	.36035	.36014	.36024	1172.13100	1205.04401		
1.100	-5.909	- .68358	- .68569	- .68418	.35877	.35739	.35764	.35764	1179.61700	1204.85400		
1.100	-4.904	- .56633	- .56808	- .56660	.35491	.35537	.35510	.35510	1186.23300	1204.61400		
1.100	-3.904	- .45026	- .45092	- .44952	.35257	.35235	.35275	.35255	1191.75101	1204.61501		
1.100	-2.917	- .33495	- .33684	- .33555	.34691	.34745	.34772	.34772	1196.06000	1204.74300		
1.100	-1.896	- .21507	- .21760	- .21639	.34447	.34508	.34539	.34523	1199.18300	1204.75200		
1.100	- .924	- .10358	- .10530	- .10418	.33821	.33874	.33894	.33894	1201.25101	1204.86700		
1.100	.079	.00781	.00495	.00679	.00587	.33685	.33739	.33770	.33754	1202.32500	1204.80701	
1.100	1.067	.11905	.11736	.11819	.11902	.33821	.33914	.33935	.33925	1202.68100	1204.80200	
1.100	2.057	.23272	.23316	.23455	.23386	.33969	.34033	.34062	.34048	1202.50000	1204.66901	
	GRADIENT	.11468	.11477	.11455	.11466	-.00261	-.00245	-.00246	-.00246	.2.26875	-.01950	

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM039) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1373/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	
		DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
MACH	ALPHA	.99222	.99487	.99314	.40508	.40563	.40523	1140 31200 1182.74899
1.249	-7.914	-.86318	-.86514	-.86350	.40631	.40625	.40665	1148 .63000 1183.05000
1.250	-6.882	-.74071	-.74266	-.74101	.40253	.40236	.40275	1156 .61099 1182.56000
1.250	-5.876	-.61056	-.61292	-.61145	.39893	.39776	.39848	1163 .42599 1182.31500
1.250	-4.869	-.48112	-.48299	-.48163	.39280	.39107	.39139	1167 .66800 1182.16299
1.250	-3.858	-.35419	-.35532	-.35406	.39015	.38842	.38878	1171 .87300 1182.18401
1.250	-2.845	-.22631	-.22753	-.22645	.38389	.38228	.38260	1175 .76900 1182.57500
1.250	-1.834	-.10335	-.10293	-.10108	.37558	.37391	.37442	1178 .30901 1182.80000
1.250	-.828	.02051	.01868	.02057	.01962	.01948	.01930	1179 .05800 1182.47301
1.250	.177	.14260	.14084	.14246	.14165	.14070	.14055	1179 .46700 1182.69800
1.250	1.157	.26650	.26540	.26657	.26598	.26537	.26428	1179 .38600 1182.53200
1.250	2.146	.12469	.12479	.12456	.12468	.12457	.12456	.00515 2.31703 .06288
GRADIENT								

	RUN NO.	1384/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	
		DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
MACH	ALPHA	.98972	-.99268	-.99074	.46632	.46542	.46642	1120 .82201 1164.68600
1.400	-6.889	-.84782	-.84998	-.84823	.46219	.46218	.46304	1130 .34000 1164.51700
1.400	-5.884	-.70555	-.70312	-.69985	.45550	.45557	.45587	1137 .90900 1163.99600
1.400	-4.877	-.55476	-.55799	-.55476	.45298	.45325	.45354	1144 .16701 1164.06599
1.400	-3.871	-.41102	-.40885	-.40964	.44822	.44773	.44835	1155 .12900 1163.96100
1.400	-2.858	-.26038	-.26252	-.25998	.44275	.44068	.44120	1157 .99800 1164.26300
1.400	-1.846	-.11791	-.11572	-.11681	.43183	.42984	.43039	1160 .03400 1164.28500
1.400	-.842	-.02355	.02557	.02456	.42663	.42511	.42536	1161 .89300 1164.35300
1.400	.162	.16261	.16438	.16350	.42329	.42133	.42193	1161 .22301 1163.98900
1.399	1.144	.30687	.30724	.30661	.42249	.42105	.42150	1161 .49200 1164.05200
1.400	2.136	.14352	.14384	.14356	.14370	.00541	.00570	.00572 2.32571 -.01350
GRADIENT								

	RUN NO.	1397/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	
		DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
MACH	ALPHA	.04699	-.05040	-.04499	.50379	.50247	.50314	.50280 1130 .30701 1158 .41499
1.449	-7.881	-.04707	-.05022	-.04870	.50598	.50477	.50564	.50520 1121 .93800 1157 .74200
1.452	-6.841	-.89471	-.89792	-.89620	.49426	.49251	.49315	.49283 1136 .60600 1158 .24300
1.450	-5.831	-.73705	-.73999	-.73852	.49330	.49136	.49192	.49164 1143 .56599 1160 .01100
1.450	-4.816	-.58560	-.58755	-.58604	.49160	.48957	.49022	.48989 1150 .95399 1160 .29300
1.450	-3.797	-.43185	-.42920	-.43053	.47954	.47927	.47954	.47954 1153 .13699 1159 .29601
1.450	-2.771	-.27042	-.27182	-.27069	.47954	.46507	.46549	.46528 1153 .25500 1158 .46100
1.450	-1.750	-.11270	-.11373	-.11373	.46709	.45387	.45401	.45394 1153 .24500 1157 .92101
1.450	-.735	.03772	.03695	.03776	.45546	.44718	.44742	.44730 1154 .37399 1158 .52499
1.450	.274	.18530	.18679	.18616	.44897	.44629	.44651	.44651 1155 .91600 1158 .75800
1.449	1.224	.33514	.33689	.33775	.44809	.44629	.44674	.44674 -.00786 -.00792
GRADIENT		.15275	.15318	.15286	.15302	.00571	.00572	.00572 2.32571 -.01350

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 718

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM039) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.471	-7.885	-1.24216	-1.24479	-1.24134	-1.24307	.52478	.52323	.52412	.52367	1109.93700	1149.44637
1.471	-6.853	-1.09134	-1.09367	-1.0976	-1.09171	.52401	.52253	.52319	.52286	1119.94800	1149.55322
1.471	-5.839	-0.93220	-0.93664	-0.93301	-0.93482	.51974	.51705	.51774	.51739	1128.09200	1149.69687
1.471	-4.824	-0.76974	-0.77310	-0.76975	-0.77142	.51495	.51232	.51302	.51267	1133.46600	1149.88011
1.471	-3.813	-0.60795	-0.60952	-0.60627	-0.60790	.50965	.50914	.50960	.50937	1138.34700	1149.65514
1.471	-2.791	-0.4250	-0.4302	-0.44029	-0.44166	.50399	.50348	.50404	.50376	1142.63699	1149.86867
1.471	-1.767	-0.27983	-0.28126	-0.27880	-0.28003	.49611	.49562	.49592	.49577	1145.07300	1150.06223
1.471	-0.755	-0.11752	-0.11870	-0.11663	-0.11767	.48647	.48583	.48632	.48608	1147.25301	1149.54166
1.470	.256	.04115	.04044	.04236	.04140	.47431	.47375	.47402	.47389	1147.72301	1149.19890
1.471	1.229	.19202	.19390	.19538	.19464	.46588	.46520	.46571	.46546	1148.61000	1149.50450
1.471	2.209	.34586	.34773	.34765	.34769	.45914	.45866	.45918	.45892	1148.47600	1149.55237
GRADIENT											
RUN NO. 1440/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00											
RUN NO. 1407/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00											
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.496	-7.892	-1.29068	-1.29338	-1.28895	-1.29117	.53577	.53333	.53407	.53370	1109.77901	1146.37593
1.496	-6.856	-1.13565	-1.13793	-1.13387	-1.13590	.53989	.53761	.53878	.53820	1111.23300	1146.31993
1.496	-5.845	-0.98217	-0.98503	-0.98125	-0.98314	.54649	.54398	.54522	.54460	1126.35400	1146.34998
1.496	-4.833	-0.81700	-0.81734	-0.81378	-0.81556	.53965	.53715	.53835	.53775	1132.71700	1146.73354
1.496	-3.821	-0.64582	-0.64726	-0.64377	-0.64552	.53465	.53238	.53314	.53276	1132.71700	1147.10947
1.496	-2.798	-0.47620	-0.47699	-0.47393	-0.47546	.53592	.53368	.53432	.53400	1132.64999	1146.85968
1.495	-1.781	-0.30336	-0.30411	-0.30133	-0.30272	.52893	.52681	.52737	.52709	1132.59599	1146.79532
1.496	-0.768	-0.13021	-0.12804	-0.12912	-0.12804	.52024	.51804	.51845	.51825	1132.49600	1146.76369
1.496	.241	.03905	.03798	.03994	.03896	.51122	.50943	.50986	.50964	1132.52901	1146.97725
1.496	1.216	.20383	.20349	.20591	.20434	.50232	.50068	.50105	.50086	1132.38800	1146.97676
1.496	2.194	.36975	.36778	.36910	.36844	.49571	.49403	.49435	.49419	1132.38800	1146.88522
GRADIENT											
RUN NO. 1430/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00											
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.517	-7.894	-1.47893	-1.48212	-1.47788	-1.48000	.61776	.61602	.61720	.61661	1116.29500	1140.07521
1.518	-6.856	-1.33739	-1.33882	-1.33477	-1.33679	.63232	.63113	.63194	.63153	1116.26100	1139.63368
1.518	-5.846	-1.15816	-1.15985	-1.15584	-1.15784	.63158	.63002	.63073	.63038	1116.34801	1139.23157
1.518	-4.834	-0.95386	-0.95494	-0.95114	-0.95304	.62998	.62863	.62929	.62896	1116.26100	1139.40790
1.518	-3.816	-0.76130	-0.76209	-0.75885	-0.76047	.63848	.63692	.63754	.63723	1116.24699	1139.59082
1.518	-2.798	-0.55163	-0.55212	-0.54923	-0.55068	.63038	.63090	.63064	.63094	1116.21800	1139.89610
1.518	-1.780	-0.34256	-0.34388	-0.34134	-0.34261	.60121	.59980	.60053	.60017	1116.25101	1139.03156
1.517	-0.767	-0.15264	-0.15195	-0.14970	-0.15083	.56661	.56494	.56542	.56518	1116.25101	1138.89748
1.518	.238	.02999	.02980	.03170	.03075	.55624	.55445	.55509	.55477	1116.17400	1139.03357
1.517	1.216	.21446	.21356	.21495	.21425	.54410	.54212	.54307	.54259	1116.12000	1139.62953
1.517	2.194	.40953	.40824	.40933	.40879	.55071	.54875	.54921	.54898	1116.12000	1139.62434
GRADIENT											
RUN NO. 19365 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00											

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.517	-7.894	-1.47893	-1.48212	-1.47788	-1.48000	.61776	.61602	.61720	.61661	1116.29500	1140.07521
1.518	-6.856	-1.33739	-1.33882	-1.33477	-1.33679	.63232	.63113	.63194	.63153	1116.26100	1139.63368
1.518	-5.846	-1.15816	-1.15985	-1.15584	-1.15784	.63158	.63002	.63073	.63038	1116.34801	1139.23157
1.518	-4.834	-0.95386	-0.95494	-0.95114	-0.95304	.62998	.62863	.62929	.62896	1116.26100	1139.40790
1.518	-3.816	-0.76130	-0.76209	-0.75885	-0.76047	.63848	.63692	.63754	.63723	1116.24699	1139.59082
1.518	-2.798	-0.55163	-0.55212	-0.54923	-0.55068	.63038	.63090	.63064	.63094	1116.21800	1139.89610
1.518	-1.780	-0.34256	-0.34388	-0.34134	-0.34261	.60121	.59980	.60053	.60017	1116.25101	1139.03156
1.517	-0.767	-0.15264	-0.15195	-0.14970	-0.15083	.56661	.56494	.56542	.56518	1116.25101	1138.89748
1.518	.238	.02999	.02980	.03170	.03075	.55624	.55445	.55509	.55477	1116.17400	1139.03357
1.517	1.216	.21446	.21356	.21495	.21425	.54410	.54212	.54307	.54259	1116.12000	1139.62953
1.517	2.194	.40953	.40824	.40933	.40879	.55071	.54875	.54921	.54898	1116.12000	1139.62434
GRADIENT											
RUN NO. 19367 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00											

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.517	-0.1535	-0.1527	-0.1520	-0.1513	-0.1506	.00821	.00757	.00683	.00619	-.02070	-.01280

1A310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM039) ( 04 OCT 91 )

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM040) ( 04 Oct 91 )

5.00  
D/

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 720

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM040) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	RN/L =	1349/ 0	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000	
	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F		
.800	.86524	-.86515	-.86638	.47793	.47737	.47817	.47777	1295.85699	1341.97000		
.799	.75264	-.75479	-.75344	.46940	.46886	.46949	.46918	1304.64700	1342.03000		
.800	.64406	-.64342	-.64473	.46643	.46668	.46731	.46699	1312.40601	1341.77000		
.800	.53127	-.53286	-.53044	.46101	.46137	.46193	.46165	1319.49300	1342.13000		
.800	.41802	-.41943	-.41694	.41819	.41640	.45698	.45736	1325.63000	1341.95000		
.800	.30558	-.30667	-.30441	.30554	.45256	.45298	.45320	1330.39999	1342.22000		
.800	.19795	-.19738	-.19760	.19652	.44710	.44659	.44691	1333.50301	1341.94000		
.800	.08728	-.08630	-.08454	.08542	.44170	.44135	.44165	.44150	1335.84399	1341.97000	
.800	.02356	-.02278	-.02442	.02360	.43653	.43629	.43663	.43646	1337.03300	1341.78999	
.800	.1.200	-.13028	-.12959	.13094	.43228	.43178	.43202	.43190	1337.50400	1342.17000	
.800	.2.182	-.23993	-.23988	.24081	.42943	.42902	.42929	.42916	1337.43700	1341.95000	
	GRADIENT	.10959	.10979	.10957	.10968	-.00469	-.00484	-.00487	-.00485	2.46376	-.01697

MACH	ALPHA	RN/L =	1339/ 0	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000	
	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F		
.900	.89572	-.89920	-.89632	.89776	.49420	.49317	.49379	.49348	1227.27100	1273.23000	
.899	.7870	-.77882	-.78061	.77760	.48820	.48689	.48754	.48722	1235.89999	1272.95000	
.900	.5.832	-.66612	-.66803	.66496	.48489	.48413	.48485	.48457	1243.14400	1272.88000	
.900	.4.818	-.55092	-.55216	.54919	.455067	.47857	.47870	.47938	.47904	1250.24300	
.900	.3.806	-.43380	-.43400	.43143	.43272	.47284	.47295	.47352	.47323	1256.47000	
.900	.2.795	-.31684	-.31759	.31512	.31635	.46909	.46928	.46966	.46947	1261.25000	
.900	.1.780	-.20300	-.20352	.20108	.20230	.46288	.46301	.46352	.46326	1264.84300	
.900	.774	-.08962	-.08854	.08666	.08760	.45762	.45728	.45775	.45752	1266.89200	
.900	.234	-.02528	-.02440	.02639	.02539	.45244	.45247	.45251	.45249	1268.07800	
.900	1.214	-.13557	-.13714	.13635	.44713	.44785	.44785	.44786	.44786	1268.75000	
.900	2.199	-.24915	-.24952	.25075	.25014	.44378	.44442	.44471	.44457	1268.64799	
	GRADIENT	.11373	.11387	.11365	.11376	-.00507	-.00500	-.00508	-.00504	2.52929	.00675
MACH	ALPHA	RN/L =	1328/ 0	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000	
	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F		
1.099	.91563	-.91849	-.91539	.91694	.48252	.48040	.48134	.48087	1160.00200	1205.09399	
1.100	.79593	-.79807	-.79501	.79654	.48013	.47795	.47867	.47831	1168.44701	1204.59599	
1.100	.68251	-.68469	-.68166	.68317	.47884	.47688	.47754	.47721	1175.97600	1204.56300	
1.100	.565578	-.56738	-.56454	.56596	.47621	.47408	.47470	.47439	1182.92799	1204.62199	
1.101	.45186	-.44894	-.45040	.45040	.46822	.46707	.46783	.46745	1188.69000	1204.59500	
1.100	.3.908	-.33334	-.33449	.33194	.33321	.46628	.46688	.46658	.46658	1193.31500	
1.100	.2.906	-.21748	-.22012	.21766	.21889	.46237	.46184	.46212	.46212	1196.54500	
1.100	.926	-.10177	-.10342	.10119	.10230	.45912	.45890	.45936	.45936	1198.89600	
1.100	.093	-.01315	-.01042	.01231	.01136	.45714	.45720	.45744	.45732	1200.10500	
1.100	1.092	-.12558	-.12525	.12688	.12606	.45663	.45660	.45669	.45665	1200.67200	
1.100	2.068	-.23978	-.24021	.24156	.24089	.45684	.45686	.45685	.45685	1200.61501	
	GRADIENT	.11567	.11581	.11558	.11569	-.00272	-.00243	-.00253	-.00248	2.46739	.04253

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 721

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM040) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO. 1374/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
MACH	DPACAL	- .99723	- .99543	.53617	.53545	.53702	.53623	1136.56700	1183.11900
ALPHA	- .99432	- .86389	- .86043	.53210	.53174	.53277	.53226	1145.18700	1182.64600
	- .86194	- .73955	- .73633	.53135	.53090	.53174	.53132	1153.01100	1182.54201
	- .73807	- .61535	- .61227	.52569	.52480	.52573	.52527	1160.20900	1182.48100
	- .61236	- .48400	- .48104	.51844	.51740	.51811	.51775	1165.78400	1182.10100
	- .48212	- .35413	- .35157	.51501	.51290	.51384	.51337	1169.80200	1182.76500
	- .35168	- .22838	- .22611	.50887	.50726	.50801	.50763	1173.29201	1182.69099
	- .22742	- .10155	- .09938	.50345	.50203	.50271	.50237	1175.34100	1182.59000
	- .10182	- .02394	- .02302	.49869	.49745	.49786	.49766	1176.65700	1182.36301
	- .02394	- .14728	- .14587	.49551	.49403	.49459	.49431	1176.83800	1182.20700
	- .14728	- .27106	- .27184	.49307	.49187	.49235	.49211	1177.07001	1182.48801
	- .27205	- .12607	- .12577	.00472	- .00474	- .00481	- .00478	2.33116	- .00853
GRADIENT	1.2581								

RUN NO. 1385/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
MACH	DPACAL	- 1.12368	- 1.11982	- 1.12175	.62706	.62787	.62748	1116.86800	1164.40700
ALPHA	- 1.12078	- .98555	- .98960	- .98770	.61376	.61321	.61378	1126.84599	1164.55800
	- 6.874	- .84473	- .84667	- .84486	.61069	.61072	.61113	1134.77499	1164.21600
	- 5.869	- .55722	- .55408	- .55565	.59503	.59485	.59525	1147.20500	1164.21300
	- 4.857	- .40864	- .40609	- .40556	.59330	.59333	.59370	1152.46500	1164.38300
	- 3.856	- .26336	- .26099	- .26217	.58778	.58789	.58822	1156.09399	1164.67500
	- 2.846	- .11633	- .11403	- .11518	.58022	.58032	.58071	1157.97400	1164.08299
	- 1.837	- .02832	- .02739	- .02948	.02843	.02857	.02852	1158.91499	1163.91901
	- .834	- .16979	- .16862	- .17088	.16975	.17023	.17241	1159.74500	1164.16800
	- .171	- .31339	- .31272	- .31393	.31333	.31391	.31471	1160.06700	1164.35800
	1.156	- .14492	- .14466	- .14479	.14479	- .00495	- .00486	- .00490	- .00488
GRADIENT	1.4454								

RUN NO. 1398/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
MACH	DPACAL	- 1.19285	- 1.19166	- 1.19356	.67252	.67121	.67166	1110.94600	1158.77299
ALPHA	- 1.19545	- 1.04004	- 1.03954	- 1.04171	.65935	.65833	.65875	1119.45599	1158.48599
	- 6.817	- 5.805	- 8.9148	- 8.9054	.65793	.65744	.65786	1127.35201	1158.42999
	- 4.787	- 7.3770	- 7.3986	- 7.3840	.64845	.64772	.64810	1133.93300	1158.51801
	- 3.768	- .58140	- .58360	- .58041	.63669	.63793	.63822	1139.18401	1158.42700
	- 2.754	- .42452	- .42391	- .42519	.63667	.63749	.63723	1144.51199	1158.28300
	- 1.733	- .27100	- .27004	- .27119	.63392	.63422	.63447	1149.49400	1158.59300
	- 1.1549	- .722	- 1.1418	- 1.1318	.62521	.62585	.62597	1151.92300	1158.00800
	- .286	.04352	.04422	.04340	.61816	.61856	.61886	1153.50200	1158.30200
	1.268	.19304	.19322	.19446	.61071	.61122	.61142	1154.03600	1158.29900
	2.247	.34323	.34449	.34463	.60641	.60694	.60740	1153.70000	1158.34900
GRADIENT	1.5374								

GRADIENT

= 4.000

PHI = 180.000

= 4.000

PHI = 180.000

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TIE-783) FAIRING-OFF DATABASE

Ergonomics

PAGE 722

11CM010 ( 01 OCT 81 )

卷之三

## PARAMETRIC DATA

RUN NO.		1441 / O	RN/L =	2.49	GRADIENT INTERVAL =	- 5.00 /	5.00
ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBC AL	DPB 1	DPB 2
-7.862	-1.242423	-1.24466	-1.244119	-1.24293	.68062	.68135	.68098
-6.828	-1.08387	-1.08645	-1.08248	-1.08446	.68049	.68156	.68121
-5.815	-9.3037	-9.3471	-9.3113	-9.32292	.68262	.68334	.68374
-4.801	-7.6753	-7.7063	-7.6755	-7.6909	.67061	.67023	.67054
-3.784	-6.0904	-6.0679	-6.0597	-6.0751	.66353	.66347	.66384
-2.768	-4.4439	-4.4473	-4.4193	-4.4333	.66059	.66047	.66106
-1.753	-2.8356	-2.8193	-2.8102	-2.8229	.65256	.65267	.65306
-743	-1.1826	-1.1696	-1.1612	-1.1719	.64461	.64476	.64497
-266	-0.4361	-0.4307	-0.4477	-0.4392	.63457	.63506	.63520
-1.245	1.1979	1.1979	1.1979	1.19863	.62786	.62839	.62844
2.231	3.5238	3.5443	3.5474	3.5453	.62336	.62366	.62377
GRADIENT	15970	16025	15989	16007	.00693	.00704	.00698

MACH	ALPHA	GRADIENT INTERVAL = -5.00/ 5.00			PTTF	PT2F
		RN/L	RN/O	RN/L = 2.49		
1.518	-7.867	-1.44823	-1.45164	-1.44755	-1.44959	-1.44959
1.518	-6.837	-1.31701	-1.31874	-1.31464	-1.31669	-1.31669
1.518	-5.826	-1.14320	-1.14481	-1.14091	-1.14286	-1.14286
1.517	-4.811	-95192	-95304	-94939	-95121	-95121
1.518	-3.796	-74852	-74949	-74606	-74778	-74778
1.518	-2.779	-55600	-55637	-55325	-55481	-55481
1.518	-1.765	-35055	-35172	-34903	-35038	-35038
1.518	-0.757	-15109	-15040	-14816	-14928	-14928
1.518	.249	.04441	.04441	.04584	.04490	.04490
1.517	1.230	.23393	.23338	.23478	.23408	.23408
1.518	2.215	.43145	.43110	.43178	.43144	.43144
1.518	1.9631	.19672	.19661	.19651	.19651	.19651

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 723

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(UCM040) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1419/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000	
MACH	ALPHA	DPA CAL	DPA 1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F	
1.543	-7.866	-1.49551	-1.49732	-1.49296	-1.49514	.82969	.82651	.82773	.82712	.82649	
-6.836	-1.25246	-1.25340	-1.24969	-1.25154	.78178	.78002	.78098	.78050	.1116.18600	.1136.29189	
1.543	-5.825	-1.04329	-1.04570	-1.04187	-1.04379	.76688	.76533	.76627	.76580	.1116.23000	.1136.38573
1.543	-4.811	-844480	-84678	-84502	-84502	.74026	.73742	.73792	.1116.15300	.1136.43398	
1.543	-3.796	-65648	-65738	-65402	-65570	.70150	.69949	.70020	.69984	.1116.13300	.1136.42574
1.543	-2.781	-48040	-47916	-47610	-47763	.66701	.66418	.66498	.66458	.1116.14301	.1136.47157
1.543	-1.766	-31053	-31071	-30798	-30934	.62723	.62552	.62591	.62571	.1116.06500	.1136.52353
1.554	-758	-14560	-14467	-14220	-14344	.59968	.59757	.59825	.59791	.1116.05499	.1149.55789
1.554	.248	.00969	.00953	.01181	.01067	.58784	.58615	.58639	.58639	.1116.08900	.1149.82716
1.554	1.230	.16290	.16237	.16408	.16322	.59072	.59072	.59127	.59100	.1116.01199	.1149.66653
1.543	2.214	.32708	.32752	.32861	.32806	.61165	.61003	.61042	.61022	.1115.95799	.1136.34737
GRADIENT	.16512	.16531	.16498	.16514	.02035	-.02018	-.02025	-.02021	-.02535	1.41596	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM041) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1670/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	ALPHA	DPA CAL	DPA 1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.600	-8.125	-7.8541	-7.8399	-7.8263	-.78331	-.36547	-.36185	-.36192	-.36189	1555.40199
.600	-7.121	-6.8920	-6.8831	-6.8682	-.68757	-.36042	-.35697	-.35663	-.35680	1563.89900
.600	-6.140	-5.9847	-5.9765	-5.9610	-.59688	-.35458	-.35388	-.35293	-.35340	1570.65100
.601	-5.164	-5.0540	-5.0367	-5.0197	-.50282	-.35170	-.35085	-.35035	-.35035	1576.78400
.600	-4.188	-4.1216	-4.1125	-4.0967	-.41046	-.34632	-.34555	-.34544	-.34550	1581.76801
.600	-3.220	-3.2120	-3.2115	-3.1974	-.32045	-.34420	-.34335	-.34334	-.34334	1585.26199
.601	-2.253	-2.2941	-2.2965	-2.2793	-.22879	-.34600	-.34520	-.34516	-.34516	1588.18401
.601	-1.284	-1.3610	-1.3621	-1.3467	-.13544	-.34869	-.34706	-.34666	-.34666	1590.52499
.600	-2.91	-0.4286	-0.4126	-0.4282	-.04204	-.35212	-.35015	-.34931	-.34931	1591.75700
.600	.704	.05047	.04971	.05132	.05051	-.35251	-.35176	-.35214	-.35214	1592.60699
.600	1.729	.14491	.14405	.14562	.14484	-.35644	-.35594	-.35619	-.35619	1592.64101
GRADIENT	.09437	.09413	.09414	.09414	-.00234	-.00204	-.00197	-.00197	-.00197	.09359

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 724  
4 OCT 91

(UCM041) (04 OCT 91)

PARAMETRIC DATA

RUN NO.: 1659 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00 / 5.00

MACH	ALPHA	DPCAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PPTF	PT2F
.900	-.0.98	-96847	-96699	-96567	-96633	-45473	-45351	-45166	-45258	1226.64900	1272.57000
.900	-7.081	-84904	-84748	-84616	-84682	-44530	-44325	-44325	-45656	1236.16400	1273.12000
.900	-6.098	-73504	-73309	-73159	-73234	-44623	-45792	-44335	-45064	1243.68700	1272.85000
.900	-5.113	-62047	-61900	-61765	-61832	-44150	-44797	-43707	-44252	1250.28400	1273.21000
.900	-4.135	-50566	-50424	-50265	-50345	-43524	-44044	-43122	-43583	1256.22099	1273.30000
.900	-3.165	-39326	-39129	-38962	-39045	-43143	-43578	-42777	-43178	1260.28799	1272.97000
.900	-2.186	-27925	-27853	-27676	-27765	-43244	-43496	-42840	-43168	1263.56000	1272.96000
.900	-1.213	-16401	-16273	-16108	-16190	-43290	-43540	-42950	-43245	1265.69800	1272.85000
.900	-.216	-04742	-04641	-04811	-04561	-43432	-43664	-43135	-43399	1267.13100	1272.82000
.900	.777	.06871	.06797	.06972	.06884	.43884	.44152	.43554	.43853	1267.59399	1272.91000
.900	1.798	.18737	.18702	.18864	.18783	.44311	.44642	.43991	.44317	1268.30901	1273.45000
GRADIENT		.11698	.11660	.11660	.11660	.00147	.00138	.00162	.00138	1.96367	.00774

RUN No. 1738 / 0 RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

	MACH	UPACAL	UPA2	UPCAL	UPB	UPB2	P1-F
-1.1.098	-7.989	-9.6555	-9.6418	-9.6486	-4.8579	-4.8327	-4.8288
-1.1.100	-7.016	-8.5326	-8.5113	-8.5181	-4.6597	-4.6441	-4.6403
-1.1.101	-6.023	-7.3813	-7.3630	-7.3477	-4.6490	-4.6249	-4.6210
-1.1.101	-5.030	-6.1982	-6.1752	-6.1911	-4.5930	-4.5675	-4.5648
-1.1.101	-4.040	-5.0165	-4.9932	-4.9766	-4.9849	-4.5373	-4.5022
-1.1.100	-3.049	-3.8485	-3.8368	-3.8195	-3.8282	-4.4752	-4.4421
-1.1.100	-2.064	-2.6666	-2.6666	-2.6533	-2.6609	-4.4474	-4.4134
-1.1.100	-1.072	-1.4869	-1.4827	-1.4642	-1.4734	-4.4209	-4.3854
-1.1.100	-0.52	-0.2726	-0.2549	-0.2726	-0.2637	-4.4162	-4.3796
-1.1.100	.922	.08754	.08607	.08758	.08683	-4.4159	-4.3794
-1.1.100	1.931	-2.0684	-2.0546	-2.0708	-2.0627	-4.4110	-4.3801
GRADIENT						-0.0128	-0.0128
						-0.0129	-0.0129

## PARAMETRIC DATA

RUN NO. 1722/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
1.249	-8.032	-1.05803	-1.05561	-1.05428	-1.05494	-5.1803	-5.1515	-5.1479
1.250	-7.062	-9.3658	-9.3343	-9.3208	-9.3275	-4.9695	-4.9396	-4.9381
1.250	-6.074	-8.1156	-8.0799	-8.0665	-8.0732	-4.9650	-4.9259	-4.9244
1.250	-5.084	-6.8435	-6.8228	-6.8082	-6.8155	-4.8983	-4.8639	-4.8663
1.250	-4.101	-5.5133	-5.5052	-5.4885	-5.4969	-4.8396	-4.8032	-4.8053
1.250	-3.120	-4.2650	-4.2537	-4.2369	-4.2453	-4.7710	-4.7378	-4.7380
1.250	-2.142	-3.0115	-3.0053	-2.9883	-2.9968	-4.7448	-4.7227	-4.7219
1.250	-1.167	-1.7575	-1.7419	-1.7253	-1.7336	-4.7404	-4.7177	-4.7169
1.250	-1.160	-0.4848	-0.4695	-0.4528	-0.4612	-4.7587	-4.7360	-4.7357
1.250	-0.832	-0.8123	-0.7992	-0.8151	-0.8172	-4.7970	-4.7712	-4.7709
1.250	1.844	-2.1101	-2.0940	-2.1110	-2.1025	-4.8243	-4.7983	-4.7990
GRADIENT	1.2826	.12785	.12785	.12785	.12785	.00008	.00019	.00023

RUN NO. 1711/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
1.400	-8.024	-1.20096	-1.19766	-1.19626	-1.19696	-5.8508	-5.8114	-5.8173
1.400	-7.050	-1.06431	-1.06255	-1.06019	-1.06137	-5.6654	-5.6273	-5.6332
1.400	-6.066	-9.2481	-9.2363	-9.2200	-9.2282	-5.6038	-5.5670	-5.5733
1.400	-5.073	-7.7887	-7.7655	-7.7498	-7.7576	-5.5530	-5.5162	-5.5230
1.400	-4.090	-6.3319	-6.3165	-6.2980	-6.3072	-5.4944	-5.4436	-5.4512
1.400	-3.110	-4.8805	-4.8723	-4.8552	-4.8638	-5.4795	-5.4438	-5.4368
1.400	-2.131	-3.4548	-3.4553	-3.4356	-3.4455	-5.4476	-5.3997	-5.4130
1.400	-1.150	-2.0131	-2.0189	-2.0000	-2.0095	-5.4413	-5.3873	-5.4027
1.400	-0.151	-0.05575	-0.05527	-0.05329	-0.05428	-5.4493	-5.3983	-5.4147
1.399	.842	.09034	.08846	.09013	.08929	-5.4793	-5.4275	-5.4449
1.400	1.857	.24097	.23858	.24033	.23946	-5.5307	-5.4796	-5.4956
GRADIENT	1.4677	.14615	.14615	.14615	.14615	.00041	.00038	.00042

RUN NO. 1704/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
1.450	-8.114	-1.29611	-1.29395	-1.29286	-1.29340	-6.0047	-5.9712	-5.9817
1.450	-7.110	-1.13526	-1.13394	-1.13460	-1.13460	-5.8834	-5.8493	-5.8614
1.450	-6.125	-9.9045	-9.8858	-9.8732	-9.8755	-5.8559	-5.8209	-5.8352
1.450	-5.141	-8.3695	-8.3465	-8.3307	-8.3386	-5.8215	-5.7897	-5.8022
1.449	-4.168	-6.8210	-6.8159	-6.8012	-6.8085	-5.7403	-5.7047	-5.7166
1.450	-3.200	-5.3198	-5.3199	-5.3025	-5.3112	-5.7485	-5.7116	-5.7252
1.450	-2.227	-3.8527	-3.8428	-3.8261	-3.8344	-5.7634	-5.7257	-5.7392
1.450	-1.261	-2.3133	-2.2964	-2.3048	-2.3048	-5.7874	-5.7469	-5.7603
1.450	-0.261	-0.07426	-0.07356	-0.07186	-0.07271	-5.8241	-5.7840	-5.7979
1.450	.731	.08057	.08078	.08072	.07975	-5.9175	-5.8769	-5.8919
1.450	1.752	.24281	.24099	.24099	.24180	-5.9517	-5.9092	-5.9253
GRADIENT	1.5627	.15588	.15591	.15589	.15589	.00375	.00364	.00370

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 726

(UCM041) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1697/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.470	-1.32463	-1.32190	-1.32063	-1.32126	.63241	.62820	.62945	.1107 .86800	.1150 .55771
-8.064	-1.17487	-1.17207	-1.17008	-1.17108	.60830	.60500	.60636	.1114 .62100	.1149 .59956
1.470	-6.113	-1.02432	-1.02217	-1.02273	.60821	.60496	.60630	.1123 .71500	.1149 .84430
1.470	-5.125	-8.6192	-8.5820	-8.5889	.59869	.59518	.59655	.1129 .64600	.1149 .29852
1.470	-4.151	-7.0120	-7.0057	-6.9966	.58893	.58542	.58700	.1133 .77421	.1148 .91620
1.470	-3.181	-5.4462	-5.4275	-5.4355	.58393	.58061	.58212	.1137 .59399	.1148 .83006
1.470	-2.211	-3.8890	-3.8841	-3.8762	.58348	.57986	.58151	.1140 .79500	.1148 .99393
1.470	-1.236	-2.3597	-2.3502	-2.3581	.58414	.58048	.58214	.1143 .13699	.1149 .05380
1.470	-2.243	-0.7762	-0.7592	-0.7678	.58757	.58357	.58515	.1144 .43300	.1148 .75621
1.484	.752	.08186	.07977	.08016	.59652	.59416	.59336	.1145 .22900	.1167 .16272
1.485	1.772	.24450	.24283	.23844	.59986	.59577	.59667	.1145 .46400	.1166 .87315
GRADIENT	.15944	.15900	.15779	.15839	.00226	.00214	.00215	.1.94906	.3.28582

RUN NO. 1667/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.497	-1.35088	-1.34664	-1.34591	-1.34627	.64068	.63933	.63911	.63922 .1095	.63900 .41800
1.496	-7.089	-1.20546	-1.20073	-1.19980	.61848	.61734	.61684	.61709 .1101	.6147 .41901
1.497	-6.107	-1.06087	-1.05770	-1.05663	.610516	.61163	.61145	.61417 .1109	.6147 .34540
1.497	-5.117	-9.0599	-9.0134	-9.00442	.90088	.61579	.61361	.61333 .1116	.61347 .59300
1.497	-4.146	-7.4561	-7.4106	-7.3985	.74046	.61320	.61078	.61088 .1120	.64264 .50999
1.497	-3.169	-5.8235	-5.8055	-5.7931	.57993	.61374	.61160	.61150 .1124	.61150 .41800
1.497	-2.198	-4.1949	-4.1702	-4.1559	.41631	.61626	.61324	.61321 .1128	.61321 .4601
1.497	-1.226	-2.5593	-2.5436	-2.5281	.25359	.62088	.61844	.61840 .1130	.61840 .88300
1.497	-2.228	-0.9020	-0.8781	-0.8654	.08717	.62595	.62354	.62347 .1132	.62351 .55499
1.497	.765	.08035	.08023	.08147	.08085	.63298	.62981	.63018 .1133	.63000 .05901
1.496	1.790	.25397	.25288	.25424	.25356	.63572	.63275	.63313 .1132	.63294 .49800
GRADIENT	.16831	.16756	.16757	.16756	.000419	.000408	.000415	.00411 .2.08144	.01297 .0

RUN NO. 1685/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.519	-8.051	-1.42843	-1.42371	-1.42273	.42322	.68320	.67946	.68076 .1094	.68011 .34599
1.520	-7.087	-1.29996	-1.29643	-1.29551	-1.29597	.66212	.65827	.65933 .1101	.65880 .92999
1.520	-6.104	-1.15656	-1.15151	-1.15017	-1.15083	.67507	.67189	.67135 .1110	.67001 .00301
1.520	-5.121	-9.9829	-9.9538	-9.9418	.99478	.68474	.67926	.67999 .1116	.68071 .90401
1.520	-4.141	-8.2837	-8.2425	-8.2297	.82361	.68694	.68144	.68293 .1121	.68219 .69400
1.520	-3.173	-6.5599	-6.5323	-6.5184	.65254	.69292	.69773	.69444 .1124	.69368 .01601
1.520	-2.196	-4.7801	-4.7591	-4.7425	.47508	.71782	.71285	.71333 .1125	.71333 .70599
1.520	-1.222	-2.9182	-2.9073	-2.8911	.28992	.73181	.72625	.72806 .1126	.72716 .90199
1.520	.728	.09133	.08991	.09062	.09421	.74821	.74298	.74390 .1127	.74390 .61099
1.520	.766	.10409	.10335	.10487	.10411	.73883	.73378	.73478 .1127	.73478 .75900
GRADIENT	1.787	.29569	.29429	.29508	.29508	.73077	.72694	.72592 .1127	.72592 .59100
	.19108	.19017	.19020	.19019	.00879	.00879	.00872	.00879 .97662	.00879 .07931

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 727

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM041) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1678/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.541	-8.058	-1.61844	-1.61365	-1.61325	-1.61345	-7.6899	-7.6521	-7.6643	-7.6582	1111.10400
1.541	-7.089	-1.41968	-1.41403	-1.41300	-1.41351	-7.5199	-7.4801	-7.4927	-7.4864	1113.59000
1.545	-6.103	-1.15601	-1.15031	-1.14901	-1.14966	-7.3526	-7.2987	-7.3133	-7.3060	1114.63800
1.543	-5.123	-93436	-93194	-93055	-93124	-7.1463	-7.1043	-7.1126	-7.1084	1117.76900
1.544	-4.146	-7.0697	-7.0406	-7.0261	-7.0333	-7.0085	-7.0173	-7.0129	-7.0129	1118.06799
1.544	-3.166	-53266	-52941	-52794	-52868	-6.8943	-6.8506	-6.8661	-6.8584	1117.37199
1.543	-2.198	-35420	-35080	-34944	-35012	-6.7371	-6.6997	-6.7148	-6.7073	1118.06400
1.542	-1.222	-18361	-18246	-18050	-18148	-6.4340	-6.4063	-6.4229	-6.4146	1119.02400
1.543	-2.229	-02547	-02343	-02188	-02265	-6.1076	-6.0719	-6.0892	-6.0806	1119.64900
1.543	.766	.12652	.12608	.12754	.12681	.60890	.60441	.60623	.60532	1119.85100
1.543	1.788	.30901	.30870	.31006	.30938	.65842	.65425	.65602	.65513	1119.82700
GRADIENT		.16985	.16919	.16918	.16918	.01311	.01308	.01296	.01302	.42718 .13134

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM042) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1568/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
.599	-7.140	-68835	-68823	-68659	-68741	-36001	-35743	-35687	-35715	1563.45399
.599	-6.144	-59606	-59591	-59441	-59516	-35489	-35461	-35344	-35403	1570.56799
.600	-5.169	-50315	-50172	-50031	-50101	-35116	-35085	-34972	-35029	1576.96201
.600	-4.196	-40965	-40924	-40773	-40849	-34581	-34547	-34542	-34544	1571.98000
.600	-3.224	-32065	-32104	-31942	-32023	-34396	-34365	-34381	-34365	1585.37900
.601	-2.256	-22744	-22637	-22717	-22717	-34543	-34500	-34502	-34502	1588.85100
.600	-1.286	-13538	-13586	-13424	-13505	-34796	-34703	-34669	-34666	1590.68100
.600	-2.291	-04251	-04273	-04122	-04197	-35107	-34940	-34849	-34895	1591.69099
.600	.705	.05005	.04912	.05094	.05003	.35583	.35417	.35336	.35376	1592.27901
GRADIENT		.09409	.09391	.09395	.09393	.00212	.00164	.00164	.00172	.2.10431 -.10487

IA310 (AEDEC 16TE-783) PROBE CALIBRATION

(UCM042) ( 04 OCT 91 )

卷之三

	H	GRADIENT	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	P TTF	PTT
00	-7.109	-85081	-87592	.866666	-.87129	-.44874	-.44753	-.44705	-.44729	1235.12399	1273.21001	
99	-6.098	-73380	-.75898	.74947	-.75423	-.44582	-.44402	-.44331	-.44366	1242.01900	1273.08000	
00	-5.117	-.61978	-.64514	.63564	-.64039	-.44118	-.43841	-.43775	-.43808	1248.58200	1272.97000	
00	-4.137	-.50473	-.52929	.51999	-.50473	-.43503	-.43197	-.43190	-.43193	1254.16701	1273.09000	
00	-3.162	-.39270	-.41643	.40712	-.41178	-.43217	-.43291	-.42887	-.42894	1258.43900	1273.17000	
01	-2.191	-.27866	-.30268	.29335	-.29802	-.43099	-.42872	-.42869	-.42871	1261.61900	1272.78000	
00	-1.210	-.16324	-.18637	.17717	-.18177	-.43234	-.43018	-.43020	-.43019	1263.77100	1272.95000	
00	-.216	-.04748	-.06938	.06020	-.06479	-.43381	-.43170	-.43175	-.43179	1265.05000	1272.92999	
00	.781	.06955	.04594	.05513	.05053	-.43884	-.43647	-.43642	-.43645	1265.47600	1273.00000	
		11691	11723	11720	11722					.00094	.00096	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 729  
(UCM042) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1515/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	ALPHA	DPA/CAL	DPA1	.93852	.93636	.93744	DPA	DPA2	DPA	DPB2
1.250	-7.088	-.93614	-.81145	-.80931	-.81038	-.49604	DPBCAL	DPB1	DPB	PTTF
1.250	-6.074	-.81075	-.68408	-.68324	-.68436	-.49283	DPB	DPB2	DPB	PT2F
1.250	-5.081	-.68408	-.68548	-.55298	-.55412	-.48916	DPB	DPB1	DPB	PTTF
1.250	-4.102	-.55337	-.55526	-.42624	-.42624	-.48285	DPB	DPB2	DPB	PTTF
1.250	-3.123	-.42618	-.42729	-.30107	-.30219	-.47619	DPB	DPB1	DPB	PT2F
1.250	-2.146	-.30251	-.30331	-.17682	-.17352	-.47624	DPB	DPB2	DPB	PTTF
1.250	-1.160	-.17682	-.17547	-.04807	-.04633	-.47336	DPB	DPB1	DPB	PT2F
1.251	-1.168	-.04997	-.04807	-.08013	-.07990	-.47367	DPB	DPB2	DPB	PTTF
1.252	.828	.08013	.08141	.12873	.12858	-.48096	DPB	DPB1	DPB	PT2F
GRADIENT		.12817	.12873	.12866	.12866	-.47819	DPB	DPB2	DPB	PTTF
MACH	ALPHA	DPA/CAL	DPA1	.07567	.07287	.07274	DPA	DPA2	DPA	DPB2
1.400	-7.077	-.07567	-.93281	-.93057	-.93169	-.56233	DPBCAL	DPB1	DPB	PTTF
1.400	-6.066	-.92952	-.78366	-.78485	-.78382	-.52978	DPB	DPB2	DPB	PT2F
1.400	-5.077	-.78366	-.63791	-.63938	-.63884	-.55331	DPB	DPB1	DPB	PTTF
1.400	-4.093	-.63791	-.63943	-.49204	-.49316	-.54624	DPB	DPB2	DPB	PT2F
1.400	-3.113	-.49433	-.35050	-.34986	-.35088	-.54639	DPB	DPB1	DPB	PTTF
1.400	-2.131	-.35050	-.35190	-.20676	-.20546	-.51872	DPB	DPB2	DPB	PT2F
1.400	-1.150	-.20676	-.20747	-.05667	-.05760	-.54427	DPB	DPB1	DPB	PTTF
1.400	-1.152	-.05814	-.05854	-.08644	-.08725	-.51686	DPB	DPB2	DPB	PT2F
1.400	.841	.08644	.08653	.14694	.14715	-.54417	DPB	DPB1	DPB	PTTF
GRADIENT		.14694	.14715	.14696	.14705	-.51799	DPB	DPB2	DPB	PT2F
MACH	ALPHA	DPA/CAL	DPA1	.1549/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	DPB	PTTF
1.450	-7.130	-.13750	-.14065	-1.13887	-1.13976	-.58648	DPBCAL	DPB1	DPB	PT2F
1.450	-6.125	-.98952	-.99163	-.98973	-.99068	-.57439	DPB	DPB2	DPB	PTTF
1.451	-5.143	-.83856	-.84003	-.83806	-.83905	-.57232	DPB	DPB1	DPB	PT2F
1.450	-4.169	-.68172	-.68424	-.68223	-.68324	-.56734	DPB	DPB2	DPB	PTTF
1.449	-3.200	-.53265	-.53521	-.53303	-.53412	-.56671	DPB	DPB1	DPB	PT2F
1.450	-2.233	-.38581	-.38771	-.38587	-.38679	-.57124	DPB	DPB2	DPB	PTTF
1.450	-1.257	-.23362	-.23374	-.23180	-.23277	-.57139	DPB	DPB1	DPB	PT2F
1.451	-263	-.07666	-.07536	-.07374	-.07455	-.57725	DPB	DPB2	DPB	PTTF
1.450	.730	.07697	.07704	.07862	.07783	-.58766	DPB	DPB1	DPB	PT2F
GRADIENT		.15500	.15566	.15576	.15571	-.00392	DPB	DPB2	DPB	PTTF
						-.00371	DPB	DPB1	DPB	PT2F

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 730

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM042) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1633/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.469	-7.127	-1.16765	-1.16400	-1.16261	-1.16331	-1.60149	-59904	-59847	-59875	1106.29401 1148.58014
1.470	-6.117	-1.01006	-1.00819	-1.00645	-1.00732	-59101	-58926	-58870	-58898	1112.24600 1148.00766
1.470	-5.134	-1.85749	-1.85600	-1.85446	-1.85523	-58835	-58637	-58586	-58611	1118.93100 1148.04112
1.470	-4.160	-1.70347	-1.70188	-1.70007	-1.70097	-58183	-58001	-57971	-57986	1124.95300 1147.73962
1.469	-3.186	-1.54461	-1.54252	-1.54072	-1.54162	-57542	-57350	-57306	-57328	1127.60800 1148.04605
1.470	-2.213	-1.39003	-1.38808	-1.38635	-1.38721	-57540	-57348	-57310	-57329	1129.95599 1147.88101
1.469	-1.239	-1.23284	-1.23306	-1.23113	-1.23209	-57394	-57284	-57263	-57273	1132.31799 1148.24562
1.470	-2.44	-0.7922	-0.8009	-0.7807	-0.7908	-57916	-57719	-57693	-57706	1133.56100 1147.91550
1.469	.755	.07486	.07394	.07607	.07500	-58789	-58533	-58521	-58527	1134.17500 1148.26897
GRADIENT		15839	15771	15777	15774	-00118	-00109	-00114	-00111	1.92689 .07611

	RUN NO.	1584/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.491	-7.114	-1.21192	-1.20904	-1.20785	-1.20844	-62088	-61862	-61828	-61845	1098.76700 1138.58905
1.492	-6.115	-1.06612	-1.06383	-1.06160	-1.06272	-61421	-61158	-61131	-61145	1105.88901 1139.58745
1.492	-5.125	-1.90812	-1.90538	-1.90405	-1.90471	-61418	-61339	-61314	-61327	1114.83200 1142.97440
1.491	-4.150	-1.75210	-1.75010	-1.74869	-1.74940	-61595	-61487	-61480	-61483	1119.82800 1142.78709
1.491	-3.172	-1.59100	-1.58972	-1.58832	-1.58902	-61602	-61487	-61475	-61481	1122.82800 1142.26692
1.492	-2.203	-1.42970	-1.42675	-1.42529	-1.42602	-62130	-62006	-62011	-62008	1125.88499 1141.67528
1.491	-1.228	-1.26555	-1.26479	-1.26311	-1.26395	-62663	-62560	-62573	-62566	1127.36301 1141.33501
1.491	-2.28	-0.9556	-0.95608	-0.9369	-0.9438	-63516	-63354	-63377	-63366	1125.69299 1140.81860
1.491	.768	.07343	.07296	.07468	.07382	-64198	-64043	-64091	-64067	1125.24600 1140.40173
GRADIENT		16799	16750	16755	16753	-00561	-00551	-00562	-00557	1.07444 -.48285

	RUN NO.	1600/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.517	-7.115	-1.35596	-1.35200	-1.35122	-1.35161	-68385	-68621	-68349	-68367	1100.44200 1135.73912
1.517	-6.108	-1.20825	-1.20239	-1.20125	-1.20182	-70018	-70315	-69932	-69975	1111.00800 1138.43011
1.517	-5.125	-1.03647	-1.03133	-1.03133	-1.03196	-70510	-70191	-70109	-70150	1118.07899 1138.21376
1.517	-4.151	-1.85395	-1.84908	-1.84812	-1.84860	-69729	-69409	-69409	-69409	1122.02000 1138.81853
1.517	-3.176	-1.67189	-1.66865	-1.66703	-1.66784	-70116	-69884	-69863	-69874	1123.68201 1139.54364
1.517	-2.202	-1.49658	-1.49403	-1.49253	-1.49328	-72778	-72427	-72451	-72439	1125.42500 1140.31567
1.516	-1.223	-1.29517	-1.29399	-1.29244	-1.29322	-73663	-73934	-73673	-73668	1127.32300 1140.11081
1.517	-2.28	-0.9919	-0.9919	-0.9771	-0.9845	-75197	-74896	-74910	-74903	1126.42599 1138.06596
1.516	.769	.09793	.09752	.09908	.09830	-74890	-74592	-74606	-74599	1124.37700 1136.18233
GRADIENT		19387	19295	19302	19298	-0.1225	-0.1225	-0.1224	-0.1226	-.52123

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 731

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM042) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1615/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.37983	-1.37474	-1.37366	-1.37420	-1.74335	-1.74071	-1.74030	-1.74050	1133.81113	
1.541	-7.114	-1.15605	-1.15046	-1.14899	-1.14972	-1.72281	-1.71987	-1.71956	1133.95561	
1.541	-6.114	-5.124	-9.3193	-9.2958	-9.2874	-7.0039	-6.9846	-6.9803	1134.21667	
1.540	-4.146	-7.2067	-7.1786	-7.1630	-7.1708	-6.7937	-6.7752	-6.7734	1134.31038	
1.541	-3.176	-5.4178	-5.3783	-5.3610	-5.3696	-6.7366	-6.7167	-6.7144	1134.64079	
1.541	-2.201	-3.6348	-3.5946	-3.5794	-3.5870	-6.6075	-6.5866	-6.5838	1134.70178	
1.541	-1.228	-1.9495	-1.9316	-1.9120	-1.9218	-6.3349	-6.3094	-6.3106	1134.88518	
1.541	-0.228	-0.3894	-0.3691	-0.3517	-0.3604	-6.0066	-5.9783	-5.9776	1135.32828	
1.541	.767	-1.1344	-1.1285	-1.1476	-1.1381	-6.0325	-6.0054	-6.0054	1135.54410	
GRADIENT	.17003	.16937	.16933	.16937	.16934	.01824	.01845	.01839	.01842	.56594 .24493

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM043) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1569/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-68208	-68209	-68063	-68136	-26149	-26020	-25982	-26001	1566.11501	1596.75999
600	-6.613	-6.3533	-6.3503	-6.3350	-6.3427	-25962	-25826	-25808	1569.98399	1597.42000
600	-6.121	-5.8780	-5.8780	-5.8625	-5.8703	-25717	-25623	-25605	1573.69501	1596.46001
600	-5.631	-5.4157	-5.4073	-5.4073	-5.3926	-25229	-25203	-25162	1577.09399	1597.08000
599	-5.136	-4.9603	-4.9458	-4.9289	-4.9374	-25176	-25163	-25150	1579.73399	1597.05000
600	-4.649	-4.5029	-4.4879	-4.4716	-4.4797	-25020	-24987	-24964	1582.18900	1596.86000
600	-4.162	-4.0439	-4.0314	-4.0162	-4.0238	-24939	-24886	-24891	1584.69501	1597.31000
599	-3.679	-3.5889	-3.5806	-3.5725	-3.5766	-25075	-25055	-25022	1586.26601	1596.75000
600	-3.193	-3.1412	-3.1450	-3.1276	-3.1363	-25143	-25066	-25050	1588.29700	1596.71001
600	-2.714	-2.6874	-2.6906	-2.6762	-2.6834	-25051	-25002	-24981	1589.43600	1596.71001
600	-2.236	-2.2288	-2.22416	-2.2259	-2.2337	-25063	-24996	-24985	-24990	1591.16901
600	-1.754	-1.7604	-1.7677	-1.7509	-1.7593	-25138	-25082	-25063	-25072	1591.80299
600	-1.276	-1.3200	-1.3245	-1.3093	-1.3169	-25135	-25128	-25121	-25128	1593.19701
599	-0.790	-0.8459	-0.8518	-0.8339	-0.8429	-25384	-25487	-25401	-25393	1593.27000
601	-3.08	-0.4121	-0.4172	-0.4000	-0.4086	-25665	-25594	-25582	-25588	1594.01500
600	-204	.00578	.00385	.00562	.00473	-26030	-25925	-25920	-25922	1594.12601
600	.715	.05038	.04964	.05162	.05063	-26383	-26285	-26296	-26299	1594.10899
GRADIENT	.09392	.09346	.09355	.09350	.09355	.00226	.00217	.00216	.00216	.05528

(UCM043) ( 04 OCT 91 )

IA31O (AEDC 16TF-783) TABULATED DATA  
IA31O (AEDC 16TF-783) PROBE CALIBRATION  
(UCM043) ( 04 OCT 91 )  
PAGE 732

	RUN NO.	1459/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00		
ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
-7 .080	-81290	-81216	-81069	-81142	-31903	-31775	-31754	1305 .84801	1340 .9800
.800	-75737	-75662	-75507	-75585	-31751	-31639	-31625	1310 .27100	1341 .1100
-6 .086	-70038	-69944	-70016	-70023	-31623	-31455	-31446	1313 .85100	1341 .1000
.800	-64531	-64577	-64415	-64496	-31351	-31142	-31104	1317 .37700	1340 .91000
-5 .589	-59017	-58892	-58859	-58938	-30977	-30786	-30759	1320 .24500	1340 .95000
.800	-53361	-53205	-53283	-53205	-30629	-30426	-30406	1323 .12300	1340 .94000
-4 .602	-47937	-47987	-47844	-47915	-30600	-30426	-30400	1325 .66499	1341 .1700
.800	-42520	-42557	-42395	-42476	-30524	-30362	-30333	1327 .73300	1340 .94000
-3 .141	-37037	-37063	-36902	-36983	-30513	-30358	-30344	1329 .69400	1341 .08000
.800	-2 .652	-31485	-31161	-31464	-31540	-30447	-30271	1331 .20799	1340 .97000
-2 .172	-26091	-26076	-25900	-25988	-30433	-30307	-30294	1332 .56500	1340 .96000
.800	-1 .683	-20505	-20350	-20428	-30523	-30362	-30355	1333 .81000	1340 .89000
-1 .198	-15091	-15016	-14846	-14931	-30381	-30340	-30346	1334 .69600	1341 .13000
.800	-709	-9604	-09517	-09445	-30530	-30488	-30475	1335 .44800	1341 .25000
-2 .223	-04396	-04286	-04124	-04245	-30655	-30620	-30609	1335 .77600	1341 .05000
.800	-286	-01319	-01429	-01349	-31010	-30954	-30951	1336 .01401	1340 .81000
.800	-796	-06874	-06985	-06819	-31115	-31112	-31114	1336 .14101	1341 .00000
GRADIENT	-11186	-11200	-11202	-11201	-00076	-000108	-00110	2 .37851	- .00400

	GRADIENT	INTERVAL	=	-5.00/	5.00
RUN NO.	1492/ O	RN/L	=	2.50	GRADIENT INTERVAL = -5.00/ 5.00
ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBC AL
.900	.84170	.86660	.85695	.86178	.33105
.899	.78200	.80723	.79804	.80264	.33070
.898	.72709	.75222	.74299	.74760	.32904
.897	.66830	.69372	.68414	.68893	.32552
.896	.61007	.63522	.62584	.63053	.32377
.895	.55263	.57852	.56900	.57376	.32158
.894	.4123	.49593	.52102	.51161	.31906
.893	.3634	.44095	.46590	.46122	.31907
.892	.3146	.38489	.40871	.40401	.31907
.891	.26659	.32870	.35321	.34384	.31906
.890	.2174	.27069	.29477	.28555	.31906
.889	.1693	.21281	.23710	.22780	.31906
.888	.1209	.15803	.18053	.17136	.31906
.887	.721	.10015	.12237	.11334	.31906
.886	.237	.04559	.06773	.05870	.31906
.885	.275	.01322	.01050	.01050	.31906
GRADIENT	.07073	.04711	.05618	.05194	.31906
.900	.11604	.11654	.11645	.11649	.31906
PT2F					
DPB					
DPB1					
DPB2					
PTTF					

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 733  
 (UCM043) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1476/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00			BETA = -3.000	PHI = 180.000	
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	.84752	-.84910	-.84754	-.84832	-.34580	-.34640	-.34552	-.34596	1171.05299	1205.05000
1.100	-7.037	-7.8917	-7.8980	-7.8830	-.34354	-.34399	-.34371	-.34385	1174.50200	1204.95799
-6.520	-6.029	-7.3168	-7.3205	-7.3047	-.34071	-.34105	-.34068	-.34087	1177.90100	1204.81400
-6.029	-5.526	-6.7182	-6.7266	-6.7121	-.67193	-.33774	-.33825	-.33809	1181.03939	1204.49899
-5.526	-5.034	-6.1299	-6.1357	-6.1296	-.61276	-.33602	-.33588	-.33595	1184.01010	1204.66400
-5.034	-4.532	-5.5517	-5.5597	-5.5509	-.55420	-.33277	-.33178	-.33175	1184.84300	1202.10500
-4.532	-4.038	-4.9808	-4.9716	-4.9548	-.49632	-.33219	-.33101	-.33073	1186.99800	1202.56599
-4.038	-3.545	-4.3916	-4.3928	-4.3743	-.43835	-.33031	-.32904	-.32880	1190.20599	1203.44800
-3.545	-3.037	-3.8029	-3.8042	-3.7850	-.37951	-.32825	-.32738	-.32714	1192.90900	1204.31799
-3.037	-2.557	-3.2143	-3.2217	-3.2045	-.32131	-.32729	-.32577	-.32576	1195.16600	1204.89500
-2.557	-2.062	-2.6121	-2.6205	-2.6026	-.26116	-.32601	-.32442	-.32443	1196.78500	1204.85699
-2.062	-1.566	-2.0263	-2.0373	-2.0190	-.20282	-.32348	-.32191	-.32186	1197.78900	1204.87801
-1.566	-1.079	-1.4471	-1.4506	-1.4321	-.14413	-.32117	-.31963	-.31952	1198.65300	1204.86600
-1.079	-581	-0.8626	-0.8650	-0.8475	-.08562	-.32089	-.31908	-.31911	1199.31200	1204.63699
-581	-094	-0.2984	-0.3023	-0.2849	-.02936	-.32084	-.31912	-.31922	1199.72099	1204.73300
-094	.416	-0.2918	-0.2692	-0.2891	-.02791	-.32200	-.32005	-.32021	1199.95200	1204.50000
.416	.920	-0.8489	-0.8611	-0.8575	-.08651	-.32196	-.32045	-.32057	1200.16400	1204.88699
.920	GRADIENT	.11799	.11800	.11800	.11800	.00236	.00251	.00244	.00248	.41367
RUN NO.	1516/ 0	RN/L =	2.50	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00				
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	.92816	-.92966	-.92759	-.92863	-.36381	-.36243	-.36224	-.36234	1148.19901	1182.99400
1.250	-7.066	-6.560	-8.6558	-.86412	-.86514	-.36232	-.36007	-.35978	-.35993	1152.10400
-6.560	-6.061	-8.0167	-8.0257	-.80005	-.80131	-.36470	-.36146	-.36142	-.36144	1155.40601
-6.061	-5.570	-7.3836	-7.3932	-7.3728	-.73830	-.36165	-.35826	-.35810	1159.64799	1182.81800
-5.570	-5.073	-6.7526	-6.77670	-6.7455	-.67563	-.35660	-.35400	-.35298	1163.06000	1182.72900
-5.073	-4.583	-6.0665	-6.0886	-6.0557	-.60772	-.35451	-.35111	-.35169	1164.90700	1182.20100
-4.583	-4.095	-5.4641	-5.45430	-5.4430	-.45427	-.35057	-.34839	-.34726	1167.16800	1182.91100
-4.095	-3.601	-4.8152	-4.8278	-4.8050	-.48164	-.35022	-.34746	-.34653	1168.73199	1182.15601
-3.601	-2.50	-3.110	-4.2067	-4.2143	-.41935	-.42039	-.34746	-.34470	1170.97200	1182.68800
-2.50	-2.627	-3.5714	-3.5850	-3.5641	-.35746	-.34774	-.34517	-.34521	1172.93100	1182.77901
-2.627	-2.138	-2.9510	-2.9563	-2.9355	-.29459	-.34444	-.34267	-.34257	1173.72701	1182.03400
-2.138	-1.654	-2.3301	-2.3288	-2.3080	-.23184	-.34347	-.34254	-.34254	1175.22400	1182.66299
-1.654	-1.167	-1.7140	-1.7035	-1.6829	-.16932	-.34386	-.34285	-.34279	1176.26601	1182.63200
-1.167	1.250	-1.0855	-1.0692	-1.0496	-.10594	-.34486	-.34397	-.34401	1176.66901	1182.56900
1.250	-1.89	-0.4799	-0.4607	-0.4429	-.04518	-.34691	-.34572	-.34564	1177.03799	1182.37500
-1.89	.322	-0.1667	-0.1707	-0.1883	-.01795	-.35026	-.34907	-.34833	1177.10500	1182.42999
.322	1.250	.832	.07990	.08006	-.08173	-.35213	-.35084	-.35049	1177.36400	1182.67200
1.250	GRADIENT	.12703	.12768	.12756	.12762	.00055	.00023	.00012	.00017	2.31127

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 734

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM043) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1532/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.400	-7.064	-1.06192	-1.06490	-1.06218	-1.06354	-1.40823	-1.38270	-1.40840	-1.39555	-1.129.18700
-6.554	-9.9201	-9.9486	-9.9275	-9.9380	-9.9541	-1.40541	-1.37990	-1.40558	-1.39274	-1.133.53101
-6.059	-9.2127	-9.2440	-9.227	-9.2333	-9.40351	-1.37752	-1.40326	-1.39039	-1.137.13400	-1.164.42400
-5.563	-8.4852	-8.4989	-8.4763	-8.4876	-8.40086	-1.37504	-1.40087	-1.38796	-1.140.71899	-1.164.31700
-5.068	-7.7341	-7.7476	-7.7262	-7.77369	-7.40156	-1.37535	-1.40104	-1.38820	-1.143.29100	-1.163.97200
-4.578	-7.0160	-7.0348	-7.0128	-7.0238	-7.40101	-1.37292	-1.39850	-1.38571	-1.146.60600	-1.164.75301
-4.085	-6.3074	-6.3206	-6.2986	-6.3096	-6.40109	-1.37292	-1.39874	-1.38583	-1.149.41800	-1.164.10300
-3.594	-5.5962	-5.6096	-5.5868	-5.5982	-5.39898	-1.37058	-1.39631	-1.38344	-1.151.33299	-1.163.66701
-3.103	-4.8579	-4.8695	-4.8506	-4.8600	-4.39778	-1.36739	-1.39514	-1.38227	-1.153.80800	-1.164.41499
-2.616	-4.1493	-4.1558	-4.1433	-4.1445	-4.39544	-1.36731	-1.39301	-1.38016	-1.155.62199	-1.164.27200
-2.126	-3.4150	-3.4287	-3.4071	-3.4179	-3.39475	-1.36612	-1.39200	-1.37906	-1.156.57600	-1.164.16600
-1.639	-2.6990	-2.7077	-2.6890	-2.6984	-2.39434	-1.36559	-1.39142	-1.37851	-1.157.95300	-1.164.39900
-1.399	-2.0058	-2.0131	-1.9922	-2.0027	-1.39193	-1.36334	-1.38942	-1.37638	-1.158.65800	-1.164.14900
-1.150	-1.2713	-1.2697	-1.2507	-1.2602	-1.39305	-1.36466	-1.39069	-1.37768	-1.159.06500	-1.164.12100
-0.660	-0.5680	-0.5599	-0.5411	-0.5505	-0.39629	-1.3627	-1.39338	-1.38032	-1.159.28999	-1.164.20900
-0.174	-0.1560	-0.1471	-0.1666	-0.1569	-0.40071	-1.37241	-1.39337	-1.38537	-1.159.60300	-1.164.19901
1.400	.336	.08652	.08652	.08804	.08731	-1.40227	-1.37352	-1.39964	-1.38658	-1.160.14301
1.400	.843	.14639	.14639	.14629	.000030	.000040	.000031	.000036	.2.36906	-.00039
	GRADIENT									
	RUN NO.	1550/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.449	-7.106	-1.12891	-1.13063	-1.12880	-1.12971	-1.42122	-1.40002	-1.41957	-1.122.55701	-1.158.44600
1.450	-6.598	-1.05228	-1.05514	-1.05333	-1.05423	-1.42267	-1.42119	-1.42080	-1.42099	-1.126.12500
1.450	-6.106	-9.7998	-9.8313	-9.8094	-9.8204	-1.41626	-1.41461	-1.41430	-1.41445	-1.130.38400
1.449	-5.614	-9.0261	-9.0494	-9.0302	-9.0398	-1.41403	-1.41232	-1.41202	-1.41217	-1.133.25900
1.450	-5.123	-8.2263	-8.2425	-8.2236	-8.2331	-1.41556	-1.41388	-1.41374	-1.41381	-1.135.60699
1.449	-4.630	-7.4856	-7.5042	-7.4859	-7.4951	-1.41273	-1.41097	-1.41081	-1.41089	-1.138.24699
1.450	-4.150	-6.7552	-6.7806	-6.7601	-6.7703	-1.41020	-1.40937	-1.40937	-1.40948	-1.140.93100
1.450	-3.665	-6.0368	-6.0615	-6.0396	-6.0505	-1.41240	-1.41128	-1.41111	-1.41119	-1.144.61200
1.450	-3.178	-5.2802	-5.3049	-5.2842	-5.2946	-1.40976	-1.40956	-1.40933	-1.40944	-1.146.49001
1.450	-2.698	-4.5266	-4.5495	-4.5304	-4.5400	-1.40913	-1.40878	-1.40870	-1.40874	-1.148.69299
1.450	-2.219	-3.7585	-3.7724	-3.7533	-3.7629	-1.40833	-1.40797	-1.40795	-1.40796	-1.149.92200
1.450	-1.734	-3.0035	-3.0132	-2.9957	-3.0044	-1.40956	-1.40964	-1.40954	-1.40955	-1.151.06000
1.450	-1.255	-2.2689	-2.2766	-2.2574	-2.2670	-1.40921	-1.40877	-1.40894	-1.40885	-1.151.50700
1.450	-7.72	-1.5139	-1.5013	-1.4855	-1.4934	-1.41202	-1.41170	-1.41180	-1.41175	-1.151.27100
1.450	-2.88	-0.7739	-0.7609	-0.7453	-0.7531	-1.41629	-1.41616	-1.41610	-1.41613	-1.151.60400
1.451	.225	.00120	.00193	.00281	.00237	-1.42350	-1.42313	-1.42323	-1.42318	-1.152.35300
1.450	.732	.07693	.07853	.07773	.07817	-1.42875	-1.42831	-1.42824	-1.42824	-1.152.50800
	GRADIENT									
	RUN NO.	15476	RN/L =	1.5549	.15534	.00244	-.00260	-.00263	2.45887	-.02818

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM043) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
1.469	-7.100	-1.15256	-1.14948	-1.14865	-1.43564	-1.43472	-1.43410	-1108.72400 1147.47783
1.469	-6.593	-1.07620	-1.07317	-1.07233	-1.42667	-1.42566	-1.42504	-1111.84900 1147.44225
1.470	-6.099	-1.00098	-1.99744	-1.99899	-1.42638	-1.42533	-1.42470	-1115.24200 1147.37823
1.469	-5.607	-1.92645	-1.92489	-1.92320	-1.42615	-1.42483	-1.42429	-1119.35001 1147.76453
1.469	-5.111	-1.84782	-1.84642	-1.84473	-1.42557	-1.42359	-1.42308	-1122.67200 1147.59692
1.469	-4.624	-1.76761	-1.76552	-1.76377	-1.42078	-1.41891	-1.41848	-1125.12500 1147.52531
1.470	-4.135	-1.68632	-1.68488	-1.68304	-1.41991	-1.41701	-1.41663	-1125.90700 1147.94356
1.470	-3.649	-1.60932	-1.60818	-1.60624	-1.40721	-1.41853	-1.41546	-1127.60699 1148.07851
1.469	-3.165	-1.53269	-1.53144	-1.52940	-1.53042	-1.41572	-1.41266	-1129.58900 1148.62947
1.469	-2.682	-1.45749	-1.45515	-1.45316	-1.41237	-1.40897	-1.40851	-1131.16800 1148.5392
1.469	-2.199	-1.37952	-1.37800	-1.37616	-1.37708	-1.41308	-1.40985	-1132.58800 1148.14864
1.469	-1.719	-1.30518	-1.30479	-1.30293	-1.30386	-1.41369	-1.41043	-1134.11000 1148.33899
1.469	-1.235	-1.22988	-1.23010	-1.22808	-1.22909	-1.41457	-1.41108	-1135.19501 1148.51538
1.470	-1.749	-1.15212	-1.15196	-1.14993	-1.15095	-1.41743	-1.41440	-1135.62199 1148.23425
1.471	-1.267	-1.07839	-1.07923	-1.07726	-1.07825	-1.42124	-1.41814	-1136.07899 1148.03864
1.469	.244	-1.00911	-1.00025	-1.00021	-1.00002	-1.42879	-1.42566	-1136.38100 1148.14981
1.469	.756	.07642	.07541	.07737	.07639	-1.43380	-1.43070	-1136.58200 1147.92781
GRADIENT	.15686	.15637	.15629	.15633	.15633	-.00187	-.00177	-.00177 2.32007
								.02900

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
1.491	-7.089	-1.20688	-1.20409	-1.20349	-1.44974	-1.44710	-1.44686	-1100.50700 1140.65102
1.491	-6.585	-1.13499	-1.13231	-1.13185	-1.44607	-1.44362	-1.44323	-1102.35500 1140.69691
1.492	-6.093	-1.05350	-1.05146	-1.05087	-1.44459	-1.44196	-1.44159	-1105.11000 1141.04491
1.491	-5.601	-1.98071	-1.97825	-1.97675	-1.97750	-1.44128	-1.43801	-1107.51900 1141.21561
1.491	-5.108	-1.90416	-1.90162	-1.90018	-1.90090	-1.44440	-1.44112	-1110.05800 1140.81279
1.491	-4.614	-1.82316	-1.82028	-1.81897	-1.81963	-1.43300	-1.43991	-1111.52600 1141.22350
1.492	-4.132	-1.74879	-1.74661	-1.74591	-1.44745	-1.44423	-1.44383	-1113.79700 1141.21460
1.491	-3.646	-1.66707	-1.66444	-1.66527	-1.44813	-1.44472	-1.44439	-1115.07401 1140.77301
1.491	-3.156	-1.58590	-1.58485	-1.58331	-1.48408	-1.44836	-1.44495	-1117.39200 1141.70267
1.491	-2.672	-1.50840	-1.50372	-1.50452	-1.44893	-1.44547	-1.44538	-1119.07201 1140.89449
1.491	-2.191	-1.42585	-1.42314	-1.42155	-1.42235	-1.45200	-1.44836	-1120.17999 1140.86400
1.491	-1.708	-1.34454	-1.34278	-1.34117	-1.34197	-1.45606	-1.45243	-1121.22099 1141.54141
1.492	-1.224	-1.26303	-1.26237	-1.26087	-1.26162	-1.46114	-1.45788	-1121.62500 1141.17798
1.491	-1.736	-1.17825	-1.17850	-1.17736	-1.17623	-1.46748	-1.46439	-1121.28900 1140.96742
1.491	-1.252	-1.09524	-1.09374	-1.09453	-1.09405	-1.47095	-1.47101	-1121.38901 1141.36714
1.491	.260	.00770	.00673	.00710	.00710	-1.48317	-1.47958	-1.47972 1121.62500 1141.50122
GRADIENT	.772	.07847	.07692	.07780	.07780	-.48334	-.48357	-.00804 .48345 1121.65800 1141.32324
						-.00804	-.00804	-.00804 1.81945 .04099

## PARAMETRIC DATA

	RUN NO.	1601/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.36658	-1.36238	-1.36151	-1.36194	-1.36194	-1.36151	-1.36194	-1.36194	1106.63699	1136.94691
1.516	-7.094	-1.28817	-1.28252	-1.28148	-1.28200	-1.28148	-1.28200	-1.28148	1110.89101	1136.57768
1.516	-6.586	-1.20701	-1.20097	-1.19984	-1.20041	-1.19984	-1.20041	-1.19984	1114.00101	1137.08788
1.516	-6.094	-1.11798	-1.11325	-1.11231	-1.11278	-1.11231	-1.11278	-1.11231	1118.38901	1138.50980
1.517	-5.600	-1.02444	-1.02068	-1.01948	-1.02008	-1.01948	-1.02008	-1.01948	1121.97000	1139.00899
1.517	-5.109	-9.3046	-9.2686	-9.2686	-9.2628	-9.2686	-9.2628	-9.2686	1122.85400	1138.94528
1.517	-4.619	-8.4303	-8.3825	-8.3825	-8.3697	-8.3825	-8.3697	-8.3825	1122.80600	1138.42783
1.517	-4.132	-7.6467	-7.6008	-7.5886	-7.5947	-7.6008	-7.5886	-7.5947	1122.71600	1137.44493
1.517	-3.646	-6.7467	-6.7221	-6.7070	-6.7146	-6.7221	-6.7070	-6.7146	1122.86000	1136.77771
1.516	-3.155	-6.7526	-6.7526	-6.7526	-6.7536	-6.7526	-6.7536	-6.7526	1123.59900	1135.88556
1.516	-2.672	-5.7981	-5.7981	-5.7981	-5.7610	-5.7981	-5.7610	-5.7981	1124.28101	1135.34862
1.517	-2.189	-4.8131	-4.7764	-4.7764	-4.7623	-4.7764	-4.7623	-4.7764	1126.26300	1136.62648
1.517	-1.706	-3.8132	-3.7824	-3.7824	-3.7667	-3.7824	-3.7667	-3.7824	1128.55701	1138.08897
1.516	-1.222	-2.8302	-2.8170	-2.8170	-2.8094	-2.8170	-2.8094	-2.8170	1129.60500	1137.71519
1.516	-1.736	-1.8257	-1.8299	-1.8299	-1.8093	-1.8299	-1.8093	-1.8299	1129.21201	1137.16054
1.516	-2.522	-0.8877	-0.8803	-0.8656	-0.8729	-0.8877	-0.8656	-0.8729	1128.59700	1136.28415
1.517	.260	.01307	.01212	.01382	.01297	.01212	.01382	.01297	.55025	.55037
1.517	.772	.10803	.10766	.10934	.10850	.10766	.10934	.10850	.1127.74400	.1135.64705
GRADIENT	1.9574	.19473	.19484	.19479	.19474	.19484	.19479	.19474	.01007	.014369

	RUN NO.	1616/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.35201	-1.34697	-1.34573	-1.34635	-1.34573	-1.34697	-1.34573	-1.34697	1117.50000	1135.28098
1.541	-7.093	-1.23870	-1.23200	-1.23245	-1.23200	-1.23870	-1.23245	-1.23870	1119.54500	1135.58594
1.541	-6.587	-1.12125	-1.12676	-1.11998	-1.12061	-1.12125	-1.12676	-1.11998	1121.44000	1135.34811
1.541	-6.093	-1.01249	-1.01567	-1.01102	-1.01176	-1.01249	-1.01567	-1.01102	1122.24001	1135.15637
1.541	-5.601	-0.90836	-0.90577	-0.90424	-0.90500	-0.90836	-0.90577	-0.90424	1122.27400	1134.70836
1.541	-5.110	-0.81118	-0.79847	-0.79762	-0.79676	-0.81118	-0.79847	-0.79762	1121.85100	1134.64713
1.542	-4.618	-4.127	-6.9975	-6.9801	-6.9626	-4.127	-6.9975	-6.9801	1121.61900	1134.56398
1.541	-3.644	-6.0334	-6.0054	-5.9873	-5.9963	-3.644	-6.0334	-6.0054	1121.45500	1134.38939
1.541	-3.155	-5.0977	-5.0651	-5.0481	-5.0566	-3.155	-5.0977	-5.0651	1121.64600	1134.08499
1.541	-2.672	-4.1432	-4.1228	-4.1029	-4.1129	-2.672	-4.1432	-4.1228	1122.06300	1133.73839
1.541	-2.187	-3.1971	-3.1829	-3.1667	-3.1748	-2.187	-3.1971	-3.1829	1122.73900	1133.14717
1.541	-1.707	-2.4300	-2.4040	-2.4207	-2.4124	-1.707	-2.4300	-2.4040	1122.80901	1133.31122
1.541	-1.220	-1.7437	-1.7380	-1.7217	-1.7298	-1.220	-1.7437	-1.7380	1123.06799	1132.68849
1.541	-7.334	-1.0717	-1.0595	-1.0406	-1.0500	-7.334	-1.0717	-1.0595	1122.80299	1132.47604
1.541	-2.250	-0.4549	-0.4356	-0.4182	-0.4269	-2.250	-0.4549	-0.4356	1122.48100	1132.17139
1.541	.259	.02139	.02088	.02269	.02178	.259	.02139	.02088	.37955	.37984
1.541	.770	.08831	.08813	.08957	.08885	.770	.08831	.08813	.38091	.38093
GRADIENT	1.6478	.16424	.16424	.16424	.16424	.16478	.16424	.16424	.02418	.02414

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 737

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM044) ( 04 OCT 91 )

## PARAMETRIC DATA

	RN NO.	1570/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.500	PHI =	180.000	PTTFF
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB2	PTTFF
.599	-7.098	-.67444	-.67284	-.67364	-.21322	-.21192	-.21154	-.21173	1567.25101	1597.11000	
.599	-6.592	-.62838	-.62688	-.62762	-.21357	-.21223	-.21182	-.21203	1571.25600	1596.35001	
.599	-6.103	-.58334	-.58260	-.58093	-.21013	-.20899	-.20876	-.20888	1574.85500	1597.37000	
.599	-5.605	-.53573	-.53461	-.53517	-.20652	-.20552	-.20523	-.20538	1578.02299	1596.78999	
.599	-5.117	-.48930	-.48809	-.48649	-.48729	-.48441	-.48402	-.48397	1580.73599	1597.17000	
.599	-4.631	-.44432	-.44315	-.44150	-.44232	-.42037	-.42014	-.42021	1583.54401	1596.72000	
.600	-4.147	-.40034	-.39905	-.39741	-.39823	-.20207	-.20128	-.20111	1585.43100	1597.36000	
.600	-3.656	-.35523	-.35489	-.35328	-.35409	-.20252	-.20168	-.20156	1587.39999	1597.17000	
.600	-3.174	-.30837	-.30899	-.30727	-.30813	-.20324	-.20225	-.20217	1589.14900	1596.96001	
.600	-2.697	-.26372	-.26455	-.26283	-.26369	-.20265	-.20172	-.20168	1590.70399	1597.28000	
.600	-2.219	-.21805	-.21961	-.21744	-.21867	-.20234	-.20159	-.20155	1591.94299	1596.71001	
.600	-1.743	-.17243	-.17312	-.17148	-.17230	-.20354	-.20305	-.20274	1592.95700	1597.45000	
.600	-1.267	-.12922	-.12958	-.12796	-.12877	-.20359	-.20300	-.20278	1593.71600	1597.05000	
.599	-789	-.08450	-.08527	-.08354	-.08441	-.20613	-.20541	-.20523	1594.21600	1596.45000	
.600	-311	-.04212	-.04240	-.04086	-.04163	-.20932	-.20881	-.20884	1594.51600	1597.23000	
.600	.200	.00503	.00293	.00470	.00381	-.21434	-.21363	-.21358	1594.72301	1597.16000	
.600	.717	.04989	.04920	.05096	.05008	-.21795	-.21753	-.21755	1594.71899	1597.22000	
	GRADIENT	.09303	.09264	.09265	.00253	-.00256	-.00256	-.00258	2.10923	.01209	
	RN NO.	1460/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00					PTTFF
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB2	PTTFF
.800	-7.069	-.80833	-.80751	-.80624	-.80687	-.26229	-.26137	-.26084	-.26110	1307.51500	1341.21001
.800	-6.563	-.75117	-.74969	-.75043	-.75043	-.26290	-.26199	-.26148	-.26174	1311.66901	1341.10001
.800	-6.066	-.69540	-.69444	-.69582	-.69513	-.26089	-.25980	-.25933	-.25957	1315.11800	1340.78000
.800	-5.573	-.63888	-.64038	-.63883	-.63960	-.25807	-.25618	-.25582	-.25600	1318.64400	1341.08000
.800	-5.085	-.58326	-.58464	-.58304	-.58384	-.25485	-.25309	-.25287	-.25298	1321.70700	1340.92000
.800	-4.594	-.52792	-.52885	-.52733	-.52809	-.25212	-.25048	-.25025	-.25036	1324.42700	1341.14000
.800	-4.100	-.47425	-.47342	-.47342	-.47419	-.24668	-.24652	-.24650	-.24660	1326.88200	1340.95000
.800	-3.613	-.42043	-.42100	-.41957	-.42028	-.24742	-.24631	-.24611	-.24621	1329.01100	1340.85001
.800	-3.126	-.36543	-.36418	-.36494	-.36494	-.24835	-.24886	-.24680	-.24683	1330.81700	1341.03000
.800	-2.638	-.30995	-.31161	-.31002	-.31082	-.24761	-.24675	-.24661	-.24668	1332.61000	1341.03000
.800	-2.158	-.25653	-.25512	-.25584	-.25584	-.24677	-.24531	-.24532	-.24532	1333.77901	1340.97000
.800	-1.675	-.20158	-.20017	-.20094	-.20094	-.24633	-.24633	-.24618	-.24625	1334.98100	1341.03999
.800	-1.194	-.14790	-.14645	-.14718	-.14718	-.24673	-.24698	-.24573	-.24571	1335.82300	1340.99001
.800	-0.9416	-.09274	-.09345	-.09345	-.09345	-.24796	-.24781	-.24781	-.24789	1336.41000	1340.86000
.800	-0.229	-.04318	-.04245	-.04163	-.04163	-.25144	-.25015	-.25010	-.25012	1336.74899	1341.08000
.800	.283	.01268	.01195	.01363	.01279	-.25623	-.25466	-.25462	-.25464	1337.11099	1341.10001
.800	.797	.06738	.06821	.06737	.06737	-.25878	-.25715	-.25705	-.25710	1337.18500	1341.00999
	GRADIENT	.11099	.11113	.11115	.11115	-.00129	-.00129	-.00128	-.00128	.2.33268	.00450

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 738  
(UCM044) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1493/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.500	PHI =	180.000
DPACAL										
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-7.073	-.83723	-.86207	-.85287	-.85747	-.26978	-.26942	-.26908	-.26925	1240.01601
.900	-6.565	-.77713	-.80279	-.79333	-.79806	-.27162	-.27042	-.27005	-.27023	1243.69400
.899	-6.070	-.72066	-.74585	-.73657	-.74121	-.26851	-.26715	-.26689	-.26702	1247.38100
.900	-5.578	-.63326	-.68897	-.67937	-.68417	-.26466	-.26355	-.26310	-.26332	1250.71300
.900	-5.088	-.60520	-.63130	-.62177	-.62056	-.26056	-.25935	-.25879	-.25907	1253.87300
.900	-4.596	-.54795	-.57396	-.56452	-.56924	-.25849	-.25681	-.25641	-.25661	1256.67400
.900	-4.106	-.49220	-.51743	-.50800	-.51271	-.25788	-.25591	-.25548	-.25569	1258.95399
.900	-3.618	-.43592	-.46122	-.45204	-.45663	-.25711	-.25505	-.25477	-.25491	1261.19800
.900	-3.129	-.38060	-.40417	-.39469	-.39943	-.25712	-.25458	-.25440	-.25449	1262.97000
.900	-2.645	-.32271	-.34271	-.33771	-.34231	-.25645	-.25414	-.25397	-.25406	1264.71001
.900	-2.163	-.26569	-.29010	-.28086	-.28548	-.25476	-.25352	-.25341	-.25347	1266.06000
.900	-1.685	-.20908	-.23337	-.22411	-.22874	-.25553	-.25401	-.25380	-.25390	1267.11700
.900	-1.202	-.15473	-.17745	-.16814	-.17280	-.25546	-.25412	-.25404	-.25408	1267.85899
.900	-7.722	-.09859	-.12103	-.11190	-.11647	-.25792	-.25655	-.25647	-.25651	1268.64799
.900	-2.241	-.04571	-.06795	-.05896	-.06346	-.25997	-.25864	-.25847	-.25856	1268.99001
.900	-2.707	-.01349	-.01061	-.00600	-.00140	-.26486	-.26339	-.26312	-.26326	1269.26500
.900	.787	.07035	.04640	.05562	.05101	-.26762	-.26607	-.26598	-.26602	1269.46601
GRADIENT		.11542	.11589	.11583	.11586	-.00134	-.00148	-.00153	-.00150	.2.34759 .001119
RUN NO.		1477/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.100	-7.032	-.84258	-.84434	-.84263	-.84349	-.28521	-.28602	-.28570	-.28586	1171.79700
1.100	-6.521	-.78491	-.78593	-.78440	-.78516	-.28289	-.28352	-.28312	-.28332	1175.61301
1.100	-6.020	-.72568	-.72614	-.72456	-.72535	-.28381	-.28423	-.28381	-.28402	1179.19901
1.100	-5.523	-.66786	-.66913	-.66728	-.66820	-.27942	-.27913	-.27877	-.27895	1182.53500
1.100	-5.026	-.60858	-.60994	-.60803	-.60898	-.27690	-.27623	-.27604	-.27614	1185.57800
1.100	-4.534	-.55107	-.55204	-.55023	-.55113	-.27316	-.27246	-.27236	-.27241	1188.16100
1.100	-4.035	-.49160	-.49327	-.49160	-.49243	-.27221	-.27153	-.27132	-.27143	1190.75301
1.100	-3.535	-.43625	-.43617	-.43545	-.43536	-.27004	-.26848	-.26833	-.26841	1192.90300
1.100	-3.035	-.37513	-.37531	-.37345	-.37438	-.27096	-.26928	-.26928	-.26928	1194.98801
1.100	-2.549	-.31597	-.31708	-.31521	-.31614	-.26830	-.26674	-.26652	-.26663	1196.46201
1.100	-2.058	-.25855	-.25747	-.25661	-.25758	-.26531	-.26391	-.26362	-.26376	1197.72501
1.100	-1.566	-.19839	-.19951	-.19756	-.19854	-.26447	-.26305	-.26278	-.26291	1198.95399
1.100	-1.077	-.14159	-.14215	-.14032	-.14123	-.26265	-.26106	-.26069	-.26087	1199.65601
1.100	-583	-.08537	-.08523	-.08332	-.08427	-.26191	-.26051	-.26011	-.26031	1200.39200
1.100	-099	-.02906	-.02988	-.02787	-.02887	-.26220	-.26075	-.26041	-.26058	1200.79100
1.100	.414	.02997	.02738	.02951	.02844	-.26363	-.26217	-.26192	-.26204	1201.08000
1.100	.921	.08688	.08454	.08536	.08618	-.26425	-.26250	-.26232	-.26241	1201.08000
GRADIENT		.1762	.11730	.11727	.11728	.00219	.00207	.00222	.00221	.2.32195 .001119

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM044) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1517 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
MACH								
ALPHA								
-7.059	-.92512	-.92285	-.92398	-.29836	-.29782	-.29760	-.29771	1149.36301
-6.549	-.86109	-.85894	-.86002	-.29849	-.29714	-.29683	-.29698	1153.47099
-6.056	-.79752	-.79789	-.79682	-.29783	-.29601	-.29571	-.29586	1157.39101
-5.559	-.73422	-.73422	-.73186	-.29724	-.29473	-.29450	-.29462	1161.01801
-5.062	-.66716	-.66888	-.66661	-.29755	-.29101	-.28855	-.28849	1163.74800
-4.571	-.60276	-.60481	-.60372	-.28743	-.28490	-.28473	-.28482	1166.22400
-4.078	-.54000	-.54198	-.53971	-.28661	-.28397	-.28378	-.28388	1168.12801
-3.587	-.47930	-.47817	-.47701	-.28383	-.28159	-.28140	-.28149	1170.10899
-3.101	-.41512	-.41599	-.41374	-.28268	-.28062	-.28053	-.28058	1172.06700
-2.615	-.35236	-.35376	-.35159	-.28088	-.27892	-.27890	-.27891	1174.36501
-2.128	-.29067	-.29082	-.28877	-.28979	-.27939	-.27759	-.27741	1182.36501
-1.645	-.22850	-.22812	-.22612	-.22712	-.28008	-.27802	-.27805	1176.07800
-1.159	-.16735	-.16602	-.16428	-.16515	-.28020	-.27837	-.27836	1177.81400
-679	-.10679	-.10544	-.10344	-.10444	-.28234	-.28040	-.28044	1178.05901
1.250	-.193	-.04643	-.04471	-.04376	-.28526	-.28316	-.28338	1177.73700
1.250	.318	.01670	.01718	.01902	-.28985	-.28784	-.28785	1178.73399
1.249	.832	.07894	.07962	.08128	-.29167	-.28925	-.28937	1178.12900
GRADIENT		1.2661	.12726	.12715	-.00060	-.00066	-.00074	.1181.96600
								-.04771

RUN NO. 1533 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
MACH								
ALPHA								
-7.053	-1.05827	-1.06101	-1.05878	-1.05990	-.33334	-.30818	-.33372	
-6.544	-.98693	-.98895	-.98751	-.98854	-.33001	-.30506	-.33071	
-6.050	-.91385	-.91659	-.91459	-.91559	-.32762	-.30292	-.32838	
-5.553	-.84152	-.84263	-.84040	-.84151	-.32867	-.30204	-.32774	
-5.060	-.76767	-.76907	-.76700	-.76803	-.32752	-.30091	-.32655	
-4.564	-.69843	-.69983	-.69756	-.69869	-.32620	-.29886	-.32464	
-4.076	-.62827	-.62941	-.62710	-.62826	-.32394	-.29658	-.32220	
-3.582	-.55567	-.55704	-.55474	-.55589	-.32210	-.29484	-.32061	
-3.092	-.48122	-.48239	-.48024	-.48132	-.32159	-.29407	-.31992	
-2.605	-.41036	-.41088	-.40868	-.40978	-.31957	-.29201	-.31777	
-2.118	-.33637	-.33769	-.33548	-.33659	-.31796	-.29020	-.31609	
1.400	-.1.634	-.26219	-.26339	-.26236	-.31860	-.29098	-.31697	
1.400	-.1.448	-.19429	-.19324	-.19427	-.31843	-.29069	-.31657	
1.400	-.662	-.12442	-.12252	-.12347	-.31954	-.29190	-.31786	
1.400	-.177	-.05721	-.05608	-.05514	-.32363	-.29608	-.32212	
1.400	.333	.01596	.01546	.01638	-.32926	-.30133	-.32728	
1.400	.845	.08694	.08844	.08766	-.33109	-.30347	-.31649	
GRADIENT		.14622	.14610	.14616	-.00064	-.00072	-.00067	
								.2.15339 -.00277

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCMO44) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1551/0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PITF	PT2F
1.450	-7.083	-1.12419	-1.12226	-1.12322	-.34064	-.34026	-.33962	-.33994	1.124.07201	1.158.24400
-6.580	-1.04725	-1.04994	-1.04803	-1.04899	-.34077	-.34007	-.33947	-.33977	1.127.31700	1.158.35400
1.450	-6.087	-9.7250	-9.7546	-9.7316	-.33744	-.33664	-.33624	-.33644	1.131.31500	1.158.53300
-5.596	-8.9240	-8.9409	-8.9271	-8.9340	-.33868	-.33795	-.33759	-.33777	1.134.10899	1.158.15100
1.450	-5.106	-8.1751	-8.1913	-8.1712	-.33216	-.33152	-.33124	-.33138	1.136.53799	1.158.71300
1.450	-4.616	-7.4309	-7.4523	-7.4333	-.34428	-.33184	-.33101	-.33086	1.139.37000	1.158.31400
-4.127	-6.7387	-6.7642	-6.7442	-6.7542	-.33086	-.33079	-.33040	-.33060	1.143.21899	1.158.52499
1.450	-3.640	-5.9786	-6.0052	-5.9829	-.59940	-.32944	-.32890	-.32917	1.145.87300	1.158.71700
-3.158	-5.2147	-5.2383	-5.2194	-5.2288	-.33051	-.33148	-.33131	-.33139	1.148.34500	1.158.75400
1.449	-2.676	-4.4634	-4.4677	-4.4572	-.32621	-.32717	-.32683	-.32700	1.149.24200	1.158.32201
1.450	-2.202	-3.6924	-3.6941	-3.6747	-.32534	-.32591	-.32567	-.32579	1.149.92300	1.158.09700
-1.726	-2.9342	-2.9451	-2.9247	-2.9349	-.32641	-.32715	-.32679	-.32697	1.151.02800	1.158.94901
1.450	-1.249	-2.2004	-2.2115	-2.1926	-.22021	-.32973	-.33030	-.33025	1.150.99400	1.158.21100
-1.249	-7.69	-1.4866	-1.4752	-1.4660	-.14660	-.33362	-.33459	-.33450	1.151.19200	1.157.92599
1.450	-2.91	-0.7651	-0.7488	-0.7329	-.07408	-.33889	-.33987	-.33976	1.151.48500	1.158.36000
1.450	.220	.00229	.00195	.00195	-.00269	-.34705	-.34757	-.34716	1.152.33400	1.158.57300
1.450	.736	.07779	.07775	.07775	-.07859	-.35246	-.35292	-.35247	1.151.97501	1.157.94200
	GRADIENT	.15474	.15542	.15533	-.15537	-.00339	-.00358	-.00355	2.02879	-.07089

RUN NO. 1635/0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PITF	PT2F
1.470	-7.080	-1.14406	-1.14080	-1.13934	-.1.14007	-.34944	-.34793	-.34883	1.109.33900	1.147.28616
1.469	-6.577	-1.07000	-1.06839	-1.06534	-.1.06702	-.34546	-.34553	-.34513	1.113.00700	1.148.02013
1.469	-6.086	-9.9588	-9.9401	-9.9240	-.99321	-.34479	-.34421	-.34456	1.117.22900	1.148.02310
-5.591	-9.2108	-9.1946	-9.1782	-9.1864	-.91864	-.34412	-.34401	-.34346	1.121.10300	1.148.37094
1.469	-5.097	-8.4064	-8.3864	-8.3685	-.83774	-.34314	-.34202	-.34139	1.124.30400	1.148.06918
1.470	-4.609	-7.5846	-7.5656	-7.5472	-.75564	-.34006	-.33864	-.33840	1.125.90300	1.147.67125
1.468	-4.120	-6.8228	-6.8132	-6.7916	-.68024	-.33354	-.33345	-.33314	1.126.96800	1.148.13445
1.470	-3.632	-6.0459	-6.0355	-6.0155	-.60255	-.33518	-.33306	-.33250	1.128.41200	1.148.27751
1.470	-3.150	-5.2530	-5.2382	-5.2205	-.52293	-.33231	-.33032	-.32996	1.130.10201	1.148.43623
1.471	-2.670	-4.5139	-4.4894	-4.4706	-.44800	-.33071	-.32901	-.32844	1.132.05600	1.148.18036
1.470	-2.185	-3.7402	-3.7282	-3.7088	-.37185	-.33148	-.32924	-.32869	1.133.77400	1.148.74783
1.470	-1.710	-2.9770	-2.9738	-2.9556	-.29647	-.33017	-.32800	-.32745	1.134.69000	1.148.91394
1.470	-1.232	-2.2549	-2.2378	-2.2237	-.22471	-.33245	-.33012	-.32975	1.134.61301	1.149.20201
1.470	-7.48	-15.173	-15.159	-14.954	-.15057	-.33753	-.33537	-.33498	1.134.65700	1.148.94406
1.471	-2.71	-0.7847	-0.7934	-0.7746	-.07840	-.34371	-.34149	-.34103	1.134.56599	1.148.73593
1.470	.242	.00222	.00149	.00118	-.00134	-.35306	-.35032	-.34920	1.135.06000	1.148.80836
1.484	.756	.07554	.07423	.07636	-.07530	-.35749	-.35516	-.35402	1.135.77499	1.167.60747
	GRADIENT	.15536	.15526	.15531	-.00320	-.00305	-.00297	-.00301	1.84374	1.70971

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM044) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.		RN/L = 1586 / 0	GRADIENT INTERVAL = -5.00 / 5.00			BETA = -2.500			PHI = 180.000		
		DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
MACH	ALPHA	-1.20470	-1.20182	-1.20061	-1.20122	-1.20119	-1.20104	-1.20111	1099.68700	1141.32896	
1.491	-7.079	-1.12888	-1.12647	-1.12531	-1.12589	-1.12539	-1.12573	-1.12545	1102.92200	1141.22923	
-6.571	-6.571	-1.04557	-1.04429	-1.04429	-1.04493	-1.04559	-1.04535	-1.04561	1105.06200	1141.21019	
1.491	-6.082	-1.04757	-1.04720	-1.04736	-1.04726	-1.04726	-1.04726	-1.04726	1108.08600	1141.35332	
-5.586	-5.586	-1.04760	-1.04728	-1.04736	-1.04728	-1.04728	-1.04728	-1.04728	1110.13499	1141.66812	
1.491	-5.091	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1110.13499	1141.66812	
1.492	-5.091	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1111.81500	1141.21513	
1.492	-4.603	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1113.61600	1140.87954	
-4.111	-4.111	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1115.75600	1141.11734	
-3.622	-3.622	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1118.41000	1141.68948	
1.491	-3.141	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1119.74300	1141.30211	
1.492	-3.141	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1120.05600	1141.36385	
-2.659	-2.659	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1120.49200	1141.38094	
1.491	-2.175	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1120.99699	1141.58096	
-1.701	-1.701	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1120.90601	1141.13010	
-1.219	-1.219	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1120.55000	1140.98337	
1.491	-1.736	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1122.18401	1141.15974	
1.492	-1.736	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	-1.04846	1122.18401	1141.15974	
1.492	-0.256	-0.94500	-0.94500	-0.94500	-0.94500	-0.94500	-0.94500	-0.94500	1123.50000	1141.19699	
1.492	-0.257	-0.94537	-0.94637	-0.94609	-0.94595	-0.94595	-0.94595	-0.94595	1120.56000	1141.19699	
1.492	-0.772	-0.80442	-0.78899	-0.8064	-0.7976	-0.7976	-0.7976	-0.7976	1120.64999	1141.19699	
1.492	-0.772	-0.80442	-0.78899	-0.8064	-0.7976	-0.7976	-0.7976	-0.7976	1120.64999	1141.19699	
GRADIENT		1.6819	1.6764	1.6759	1.6759	1.6762	1.6762	1.6762	1.50983	- .00410	
RUN NO.		RN/L = 1602 / 0	GRADIENT INTERVAL = -5.00 / 5.00			BETA = -2.500			PHI = 180.000		
MACH	ALPHA	-1.36790	-1.36353	-1.36262	-1.36308	-1.41110	-1.40919	-1.40877	DPB2	PTTF	
1.516	-7.084	-1.28313	-1.27751	-1.27642	-1.27696	-1.41010	-1.40827	-1.40783	-1.40805	-1.40805	
1.516	-6.572	-1.20005	-1.19384	-1.19274	-1.19329	-1.41005	-1.40873	-1.40839	-1.40856	-1.40856	
1.517	-6.076	-1.1580	-1.11170	-1.10677	-1.10537	-1.10607	-1.40912	-1.40774	-1.40755	-1.40764	
1.517	-5.580	-1.04779	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.39952	-1.39976	
1.516	-5.096	-1.04779	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.39530	-1.39546	
1.517	-4.604	-1.04746	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.40270	-1.40256	
1.517	-4.112	-1.04259	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.40242	-1.40242	
1.517	-3.624	-1.04259	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.40219	-1.40219	
1.517	-3.139	-1.04259	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.40194	-1.40194	
1.517	-2.660	-1.04259	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.41357	-1.41357	
1.517	-2.178	-1.04259	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.41837	-1.41837	
1.517	-1.698	-1.04259	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.42199	-1.42199	
1.517	-1.218	-1.04259	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.42679	-1.42679	
1.517	-7.316	-1.04259	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.42962	-1.42962	
1.517	-2.555	-1.04259	-1.01779	-1.01409	-1.01277	-1.01343	-1.01061	-1.0001	-1.43462	-1.43462	
1.517	.257	.00387	.00404	.00564	.00484	.00484	.00484	.00484	.44340	.44340	
1.516	.771	.10203	.10173	.10340	.10256	.10256	.10256	.10256	.45140	.45140	
1.516	.19391	.19303	.19306	.19306	.19306	.19306	.19306	.19306	.45325	.45325	
GRADIENT									.01053	.01053	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 742

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM044) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1617 / 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.500	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.541	-7.079	-1.33409	-1.32903	-1.32776	-1.32839	-4.3797	-4.3712	-4.3623	-4.3668	-1115.51300
1.541	-6.570	-1.22023	-1.21419	-1.21302	-1.21360	-4.2510	-4.2379	-4.2330	-4.2354	-1119.57399
1.541	-6.076	-1.10541	-1.09996	-1.09860	-1.09928	-4.1712	-4.1591	-4.1527	-4.1559	-1120.99300
1.541	-5.581	-99667	-99346	-99200	-99273	-4.1003	-4.0851	-4.0802	-4.0826	-1121.09399
1.541	-5.091	-89042	-88748	-88658	-88703	-4.0252	-4.0158	-4.0100	-4.0129	-1121.11700
1.541	-4.603	-78462	-78172	-78026	-78099	-3.9577	-3.9696	-3.9530	-3.9553	-1120.72800
1.541	-4.115	-68414	-68108	-67943	-68026	-3.8982	-3.8833	-3.8796	-3.8814	-1120.63100
1.541	-3.624	-58301	-58009	-57820	-57914	-3.7997	-3.7698	-3.7673	-3.7685	-1120.90300
1.542	-3.136	-48429	-48175	-47989	-48082	-3.6156	-3.5847	-3.5826	-3.5837	-1121.69301
1.542	-2.659	-38618	-38373	-38205	-38289	-3.3805	-3.3732	-3.3700	-3.3716	-1122.56300
1.542	-2.175	-30525	-30335	-30148	-30241	-3.2039	-3.1945	-3.1909	-3.1927	-1122.99001
1.541	-1.697	-23331	-23207	-23030	-23119	-3.1017	-3.0846	-3.0833	-3.0839	-1122.86900
1.541	-1.218	-16918	-16791	-16608	-16700	-3.0497	-3.0307	-3.0269	-3.0288	-1122.80499
1.542	-7.37	-10723	-10462	-10292	-10377	-3.0064	-2.9993	-2.9959	-2.9976	-1123.35600
1.542	-2.254	-04869	-04630	-04477	-04553	-3.0571	-3.0459	-3.0439	-3.0449	-1124.66701
1.542	.257	.01860	.01926	.02124	.02025	-3.0695	-3.0565	-3.0547	-3.0556	-1125.04700
1.541	.771	.08236	.08191	.08357	.08274	-3.0427	-3.0360	-3.0332	-3.0346	-1125.08000
		GRADIENT	.15990	.15943	.01940	.01920	.01917	.01918	.01918	.01918

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCMO45) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F	BETA =	-2.000	PHI =	180.000		
											RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00		
.599	-7.078	- .67044	- .67040	- .66888	- .66964	- .16630	- .16442	- .16420	- .16431	- .1568.	1568.	16400	1596.	75000		
.599	-6.577	- .62374	- .62411	- .62235	- .62323	- .16480	- .16269	- .16242	- .16256	- .1572.	1572.	17101	1597.	35001		
.599	-6.082	- .57791	- .57733	- .57585	- .57659	- .16207	- .16035	- .16005	- .16020	- .1575.	1578.	92500	1596.	13000		
.600	-5.586	- .53261	- .53138	- .52974	- .53056	- .16039	- .15831	- .15826	- .15831	- .1578.	1578.	92500	1597.	22000		
.599	-5.096	- .48600	- .48474	- .48330	- .48402	- .15756	- .15516	- .15506	- .15511	- .1581.	1581.	85800	1596.	89999		
.600	-4.607	- .44071	- .43976	- .43817	- .43896	- .15662	- .15386	- .15359	- .15373	- .1584.	1584.	01401	1596.	36000		
.600	-4.121	- .39671	- .39551	- .39378	- .39465	- .15580	- .15406	- .15406	- .15396	- .1586.	1586.	18300	1596.	81000		
.600	-3.632	- .35071	- .35032	- .34865	- .34948	- .15532	- .15388	- .15366	- .15377	- .1588.	1588.	20500	1597.	07001		
.600	-3.149	- .30488	- .30554	- .30396	- .30475	- .15483	- .15317	- .15317	- .15312	- .1589.	1589.	91400	1596.	75999		
.600	-2.668	- .25824	- .25913	- .25749	- .25831	- .15352	- .15240	- .15219	- .15230	- .1591.	1591.	4501	1596.	92999		
.600	-2.194	- .21238	- .21387	- .21121	- .21300	- .15395	- .15275	- .15280	- .15277	- .1592.	1592.	55000	1596.	96001		
.600	-1.723	- .17011	- .17091	- .16920	- .17005	- .15341	- .15207	- .15198	- .15202	- .1593.	1593.	52100	1596.	92999		
.600	-1.258	- .12642	- .12696	- .12534	- .12615	- .15580	- .15392	- .15381	- .15387	- .1594.	1594.	47099	1597.	25999		
.600	-788	- .08488	- .08527	- .08348	- .08438	- .15917	- .15704	- .15708	- .15706	- .1594.	1594.	66901	1596.	78999		
.600	-317	- .04251	- .04286	- .04122	- .04204	- .16314	- .16172	- .16166	- .16169	- .1594.	1594.	95799	1596.	94000		
.600	.194	.00476	.00269	.00453	.00361	- .16870	- .16740	- .16741	- .16740	- .1595.	1595.	17599	1597.	12000		
.600	.719	.04989	.04787	.04787	.04878	- .17499	- .17356	- .17356	- .17378	- .1595.	1595.	21899	1597.	25999		
	GRADIENT	.09264	.09217	.09220	.09218	- .00294	- .00304	- .00312	- .00308	- .09445						
RUN NO.	1571/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00											
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F						
.800	-7.059	- .80333	- .80286	- .80127	- .80206	- .20444	- .20306	- .20271	- .20289	- .1308.	1308.	90100	1341.	16000		
.800	-6.553	- .74713	- .74651	- .74512	- .74582	- .20540	- .20421	- .20398	- .20410	- .1312.	1312.	73300	1341.	13000		
.800	-6.054	- .69061	- .69132	- .68974	- .69053	- .20259	- .20149	- .20116	- .20133	- .1316.	1316.	27299	1340.	81000		
.800	-5.558	- .63380	- .63350	- .63374	- .63445	- .19752	- .19654	- .19628	- .19641	- .1319.	1319.	62500	1340.	89000		
.800	-5.065	- .57902	- .57902	- .58049	- .57974	- .19552	- .19383	- .19363	- .19373	- .1322.	1322.	74100	1340.	91000		
.800	-4.575	- .52487	- .52577	- .52497	- .52497	- .19559	- .19383	- .19352	- .19367	- .1325.	1325.	29700	1340.	75999		
.800	-4.084	- .47192	- .47239	- .47168	- .47168	- .19406	- .19283	- .19273	- .19278	- .1327.	1327.	85201	1341.	03999		
.800	-3.596	- .41603	- .41683	- .41532	- .41607	- .19286	- .19157	- .19143	- .19150	- .1329.	1329.	94099	1340.	89999		
.800	-3.105	- .36038	- .36101	- .35950	- .36025	- .19214	- .19080	- .19066	- .19073	- .1331.	1331.	78101	1340.	89999		
.800	-2.618	- .30485	- .30641	- .30487	- .30564	- .19122	- .19001	- .18993	- .18997	- .1333.	1333.	52100	1340.	91000		
.800	-2.140	- .25219	- .25221	- .25146	- .25146	- .19008	- .18914	- .18900	- .18907	- .1334.	1334.	72301	1341.	07001		
	GRADIENT	.11044	.11044	.11044	.11044	- .19925	- .19838	- .19878	- .18868	- .18870	- .1335.	1335.	74300	1341.	00999	
						- .14651	- .14519	- .19070	- .18963	- .18945	- .1336.	1336.	59900	1341.	10001	
						- .09526	- .09312	- .19353	- .19208	- .19210	- .1337.	1337.	21700	1341.	03999	
						- .04142	- .04253	- .19712	- .19566	- .19546	- .19556	- .1337.	1337.	55901	1340.	94000
						- .01090	- .01000	- .20186	- .20012	- .20022	- .20017	- .1337.	1337.	74001	1340.	92000
						.278	.06967	.06672	.06752	.06752	.06752	- .20448	- .20450	1337.	1337.	99100
						.800	.798	.06697	.06591	.06591	.06591	- .00159	.00159	.00159	.00159	2.30195

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 744  
(UCM045) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	RUN NO.	1495/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000	PTTF
	DPA1	DPA1	.83475	DPA2	DPA	.83376	-20897	-20831	-20776	-20804	1240.85300	1273.22000
.900	-7.060	-83306	-.83276	-77640	-.77444	-.77542	-21102	-20960	-20933	-20946	1244.65100	1272.83000
.900	-6.552	-77476	-.71675	-.71877	-.71669	-.71773	-20714	-20657	-20621	-20639	1248.29500	1273.03999
.900	-6.059	-65870	-.66096	-.65891	-.65993	-.20646	-20566	-20522	-20544	-2051	1251.85800	1273.03999
.900	-5.561	-5.066	-60087	-.60182	-.60284	-.20194	-20087	-20059	-20073	-2054	1254.67300	1272.82001
.900	-4.581	-5.4433	-.54728	-.54532	-.54630	-.20190	-20027	-20012	-20020	-20257	1257.60100	1273.16000
.900	-4.089	-4.88669	-.49070	-.48864	-.48967	-.19993	-19988	-19783	-19886	-1259	85800	1272.75999
.900	-3.595	-4.3254	-.43433	-.43229	-.43331	-.19803	-20134	-19650	-19892	1261.96700	1273.16000	
.900	-3.113	-3.7529	-.37678	-.37475	-.37577	-.19530	-19422	-19392	-19407	1263.99800	1272.85001	
.900	-2.624	-3.1815	-.31932	-.31755	-.31843	-.19587	-19469	-19469	-19628	-1265	640000	1273.17999
.900	-2.142	-2.6201	-.26331	-.26144	-.26237	-.19494	-20087	-19340	-19714	-1266	85600	1273.09000
.900	-1.669	-2.0728	-.20773	-.20580	-.20677	-.19561	-20626	-19626	-20036	-1267	98100	1273.05000
.900	-1.196	-1.5309	-.15275	-.15078	-.15176	-.19581	-21176	-19570	-20373	-1268	80701	1273.00999
.900	-0.720	-0.9952	-.09861	-.09690	-.09775	-.19980	-21525	-19844	-20684	-1269	31700	1272.83000
.900	-0.245	-0.4629	-.04519	-.04346	-.04432	-.20318	-21827	-20190	-21009	-1269	71300	1273.03999
.900	.267	.01000	.00990	.01169	.01079	-.20931	-21995	-20802	-21398	-1269	87700	1272.96001
.900	.786	.06888	.06879	.07027	.06953	-.21330	-22099	-21215	-21657	-1270	14301	1273.08000
	GRADIENT	.11463	.11525	.11517	.11521	-.00197	-.00490	-.00209	-.00350	2.30780	-.00393	
MACH	ALPHA	RUN NO.	1478/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	DPB1	DPBCAL	DPB2	DPB	PTTF
	DPA1	DPA1	.84018	DPA2	DPA	.84098	-22306	-22320	-22274	-22297	1171.07800	1204.26100
1.102	-7.027	-83986	-.78179	-.78283	-.78134	-.78209	-22576	-22623	-22588	-22605	1177.92799	1205.16901
1.101	-6.516	-7.2227	-.72118	-.72056	-.72142	-.72062	-22561	-22543	-22552	-22552	1180.90401	1204.99699
1.100	-6.017	-6.6268	-.66447	-.66281	-.66338	-.66388	-22296	-22248	-22205	-22226	1183.88000	1204.66200
1.100	-5.516	-5.025	-.60472	-.60120	-.60588	-.60104	-21942	-21925	-21905	-21915	1186.46899	1204.86000
1.100	-4.523	-4.54754	-.54711	-.54794	-.54794	-.21476	-21457	-21432	-21444	-21444	1189.46899	1204.76601
1.100	-4.021	-4.89664	-.48977	-.48887	-.48887	-.21338	-21300	-21266	-21283	-21283	1191.80701	1204.72301
1.100	-3.531	-4.3168	-.43209	-.43040	-.43124	-.21113	-21011	-20984	-20987	-20987	1193.93300	1204.76700
1.100	-3.035	-3.7119	-.37183	-.36984	-.37083	-.21023	-20889	-20872	-20881	-20881	1195.79100	1204.55400
1.100	-2.542	-3.1125	-.31125	-.31170	-.31170	-.20845	-20688	-20674	-20681	-20681	1197.55701	1204.70200
1.100	-2.052	-2.5349	-.25349	-.25468	-.25376	-.20654	-20520	-20498	-20509	-20509	1198.78600	1204.99200
1.100	-1.560	-1.9574	-.19693	-.19510	-.19602	-.20524	-20394	-20383	-20389	-20389	1199.87399	1204.49200
1.100	-1.075	-1.3856	-.13933	-.13744	-.13838	-.20452	-20366	-20355	-20361	-20361	1200.69000	1204.76700
1.100	-5.58	-0.84499	-.08523	-.08314	-.08419	-.20420	-20317	-20315	-20316	-20316	1201.11301	1204.60100
1.100	-1.03	-0.2817	-.02716	-.02914	-.02815	-.20516	-20572	-20573	-20571	-20571	1201.47200	1204.53300
1.100	.405	.02806	-.02563	-.02669	-.02669	-.20659	-20629	-20631	-20630	-20630	1201.84500	1204.87000
1.100	.915	.08508	.08292	.08376	.08376	-.00159	.00159	.00159	.00161	.00161	1201.24762	1204.02253
	GRADIENT	1.1684	.11662	.11666	.11664							

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCMO45) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1518/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA										
1.250	-7.049	-.91981	-.92109	-.91898	-.92003	-.23289	-.23047	-.23067	1150.90500	1182.73000
-6.539	-.85591	-.85621	-.85413	-.85517	-.85333	-.23173	-.23012	-.23023	1154.32100	1182.32001
1.250	-6.042	-.79310	-.79347	-.79119	-.79233	-.23212	-.23031	-.23011	1158.86900	1182.98700
1.250	-5.546	-.72866	-.72868	-.72660	-.72764	-.23026	-.22826	-.22791	1162.28101	1182.39301
1.250	-5.047	-.66100	-.66330	-.66105	-.66217	-.22483	-.22256	-.22240	1164.49800	1182.32800
1.249	-4.558	-.59723	-.59914	-.59702	-.59808	-.22463	-.22205	-.22175	1166.88200	1182.81500
1.250	-4.063	-.53697	-.53858	-.53639	-.53749	-.21963	-.21770	-.21759	1168.97800	1182.02299
1.250	-3.575	-.47528	-.47585	-.47362	-.47474	-.21797	-.21615	-.21596	1170.87199	1182.24600
1.250	-3.082	-.41082	-.41145	-.40933	-.41039	-.21644	-.21461	-.21463	1173.38800	1182.66400
1.250	-2.598	-.34652	-.34801	-.34572	-.34687	-.21617	-.21445	-.21435	1174.99300	1182.45300
1.250	-2.112	-.28413	-.28483	-.28277	-.28380	-.21590	-.21439	-.21429	1176.56200	1182.49400
1.250	-1.636	-.22501	-.22467	-.22254	-.22361	-.21545	-.21384	-.21375	1177.34399	1182.19501
1.250	-1.157	-.16496	-.16363	-.16154	-.16258	-.21771	-.21618	-.21598	1178.28500	1182.55000
1.250	-678	-.10645	-.10485	-.10292	-.10389	-.22083	-.21878	-.21869	1179.25900	1182.76500
1.250	-201	-.04773	-.0476	-.04391	-.04483	-.22470	-.22274	-.22257	1179.25200	1182.65300
1.249	.313	.01578	.01619	.01817	.01718	-.22997	-.22786	-.22799	1179.17500	1182.27200
1.250	.830	.07945	.07960	.08132	.08046	-.23231	-.23044	-.23055	1179.41000	1182.55000
GRADIENT	.12607	.12664	.12656	.12660	.00181	-.00184	-.00189	-.00187	2.35790	.01891
	RUN NO.	1534/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA										
1.400	-7.044	-1.05368	-1.05640	-1.05449	-1.05545	-.25593	-.23119	-.25664	1131.38699	1164.28900
1.400	-6.539	-.98224	-.98514	-.98276	-.98395	-.25581	-.23106	-.25669	1136.04601	1164.60400
1.400	-6.036	-.90772	-.91049	-.90826	-.90938	-.25797	-.23119	-.25673	1139.10201	1164.09599
1.400	-5.541	-.83604	-.83709	-.83488	-.83599	-.25502	-.22874	-.25434	1141.94701	1164.19299
1.400	-5.046	-.76315	-.76452	-.76237	-.76344	-.25303	-.22658	-.25236	1145.33000	1164.16000
1.400	-4.554	-.69453	-.69595	-.69371	-.69483	-.25009	-.22999	-.24971	1148.24200	1163.84599
1.400	-4.058	-.62322	-.62573	-.62448	-.62452	-.24852	-.22214	-.24788	1151.04300	1164.36800
1.399	-3.570	-.55045	-.55186	-.54954	-.55070	-.24834	-.22121	-.24687	1153.64000	1164.26700
1.400	-3.074	-.47501	-.47392	-.471605	-.47499	-.24665	-.21938	-.24500	1155.18800	1164.07300
1.400	-2.590	-.40315	-.40362	-.40142	-.40252	-.24509	-.21790	-.24358	1157.12601	1164.51601
1.400	-2.108	-.330357	-.33174	-.32952	-.33063	-.24220	-.21472	-.24069	1157.52000	1163.75200
1.400	-1.621	-.25889	-.25994	-.25795	-.25895	-.24294	-.21562	-.24138	1158.31500	1164.29700
1.400	-1.143	-.19226	-.19063	-.19114	-.19114	-.24489	-.21920	-.24489	1159.40401	1164.07700
1.400	-662	-.12524	-.12400	-.12300	-.12300	-.24944	-.22238	-.24823	1159.94099	1164.49001
1.400	-184	-.05751	-.05632	-.05437	-.05535	-.25386	-.22669	-.25277	1160.33400	1164.12900
1.400	.329	.01606	.01529	.01720	.01624	-.26020	-.23305	-.25875	1160.13600	1163.95599
1.400	.847	.08797	.08809	.08965	.08887	-.26356	-.23667	-.26245	1160.79800	1164.60899
GRADIENT	.14539	.14575	.14563	.14563	.00213	-.00222	-.00214	-.00214	2.13731	.03646



## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM045) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1587 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000	P12F
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PTTF	PT2F
ALPHA	-7.065	-1.2086	-1.19894	-1.19779	-1.19837	-1.27349	-1.27250	-1.27211	-1.27231	1.101.53500	1.141.54807
	-6.558	-1.12068	-1.11835	-1.11720	-1.11777	-1.27300	-1.27211	-1.27185	-1.27198	1.104.25301	1.142.10712
	-6.061	-1.04369	-1.04252	-1.04308	-1.04308	-1.27394	-1.27279	-1.27248	-1.27263	1.106.87700	1.142.14062
	-5.569	-9.97298	-9.7038	-9.6896	-9.6967	-1.27094	-1.26981	-1.26966	-1.26973	1.109.47301	1.141.53705
	-5.076	-8.95333	-8.9256	-8.9168	-8.9212	-1.27296	-1.27173	-1.27155	-1.27164	1.111.20700	1.141.24036
	-4.586	-8.1674	-8.1460	-8.1327	-8.1394	-1.27264	-1.27144	-1.27149	-1.27146	1.113.12199	1.141.23132
	-4.094	-7.3740	-7.3566	-7.3430	-7.3498	-1.27131	-1.26994	-1.26972	-1.26983	1.115.53101	1.141.3804
	-3.601	-6.5985	-6.5874	-6.5701	-6.5787	-1.26921	-1.26809	-1.26787	-1.26798	1.118.06000	1.141.74245
	-3.117	-5.7751	-5.7751	-5.7668	-5.7755	-1.27091	-1.26988	-1.26987	-1.26987	1.119.83099	1.141.86382
	-2.637	-4.9887	-4.9545	-4.9407	-4.9476	-1.27245	-1.27094	-1.27099	-1.27096	1.120.67999	1.141.83238
	-2.156	-4.1890	-4.1595	-4.1427	-4.1511	-1.27659	-1.27542	-1.27560	-1.27551	1.120.87199	1.141.79042
	-1.682	-3.3894	-3.3722	-3.3566	-3.3644	-1.28248	-1.28112	-1.28106	-1.28109	1.121.09700	1.141.97769
	-1.208	-2.5753	-2.5703	-2.5533	-2.5618	-1.28876	-1.2859	-1.28759	-1.28759	1.121.10699	1.141.98766
	-1.736	-1.7717	-1.7710	-1.7535	-1.7623	-1.29845	-1.29693	-1.29690	-1.29692	1.121.02000	1.142.13191
	-1.260	-0.9290	-0.9262	-0.9119	-0.9191	-1.30708	-1.30556	-1.30564	-1.30560	1.120.79500	1.142.12797
	.251	.0432	.0386	.00378	.00378	-1.32174	-1.31987	-1.32019	-1.32003	1.120.74100	1.142.61107
	1.492	.08317	.08290	.08436	.08363	-1.32856	-1.32681	-1.32686	-1.32684	1.120.55000	1.142.60646
	.775	.16850	.16809	.16801	.16805	.01106	.01095	.01100	.01098	1.123.622405	
	GRADIENT										
	RUN NO.	1603 / 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PTTF	PT2F
ALPHA	-7.071	-1.35686	-1.35244	-1.35152	-1.35198	-1.31307	-1.31294	-1.31229	-1.31262	1.109.37300	1.137.08243
	-6.562	-1.27313	-1.26759	-1.26673	-1.26716	-1.31164	-1.31153	-1.31117	-1.31135	1.113.53500	1.136.86487
	-6.066	-1.19251	-1.18634	-1.18522	-1.18578	-1.31249	-1.31230	-1.31173	-1.31202	1.116.20300	1.136.59148
	-5.568	-1.10338	-1.09863	-1.09764	-1.09814	-1.31257	-1.31217	-1.31173	-1.31195	1.116.17900	1.136.95174
	-5.071	-1.00797	-1.00422	-1.00289	-1.00355	-1.30421	-1.30471	-1.30431	-1.30454	1.121.92000	1.136.81581
	-4.585	-9.91408	-9.1079	-9.0924	-9.1001	-1.29952	-1.29896	-1.29860	-1.29878	1.123.44200	1.136.82899
	-4.089	-8.2536	-8.2070	-8.1927	-8.1998	-1.30043	-1.29958	-1.29927	-1.29943	1.123.83501	1.136.42242
	-3.602	-7.4305	-7.3866	-7.3722	-7.3794	-1.30640	-1.30519	-1.30491	-1.30505	1.124.74899	1.136.23453
	-3.119	-6.5172	-6.4886	-6.4736	-6.4811	-1.31353	-1.31228	-1.31197	-1.31212	1.126.07300	1.135.95995
	-2.633	-5.5492	-5.5212	-5.5073	-5.5143	-1.31704	-1.31535	-1.31509	-1.31522	1.127.58400	1.135.72440
	-2.156	-4.5703	-4.5340	-4.5184	-4.5262	-1.31673	-1.31682	-1.31673	-1.31678	1.128.63600	1.135.49823
	1.515	-3.6531	-3.6194	-3.6044	-3.6114	-1.32314	-1.32246	-1.32217	-1.32231	1.130.05701	1.135.29291
	1.515	-2.7298	-2.7138	-2.6993	-2.7065	-1.32832	-1.32742	-1.32725	-1.32734	1.131.19901	1.135.22490
	1.514	-1.7967	-1.7960	-1.7744	-1.7852	-1.33129	-1.33058	-1.33048	-1.33053	1.131.23199	1.135.29453
	1.514	-0.8721	-0.8663	-0.8508	-0.8586	-1.34061	-1.33966	-1.33950	-1.33958	1.131.38699	1.135.29597
	1.514	.251	.00859	.00761	.00925	-1.35141	-1.35332	-1.35039	-1.35090	1.131.42101	1.135.10239
	1.515	.775	.10577	.10567	.10645	-1.35695	-1.35695	-1.35695	-1.35695	1.134.10800	1.134.75719
	GRADIENT	19274	19178	19183	19181	-0.01090	-0.01072	-0.01072	-0.01072	1.71371	-3.35453

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 748

(UCM045) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1618 / 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
MACH	ALPHA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.541	-7.064	-1.31669	-1.31189	-1.31058	-1.31123	-1.34273	-1.34257	-1.34189	-1.34223	1116.54100
1.541	-6.556	-1.20100	-1.19508	-1.19367	-1.19438	-1.33041	-1.33034	-1.32962	-1.32998	1119.14101
1.542	-6.061	-1.08511	-1.08052	-1.07907	-1.07980	-1.32003	-1.31970	-1.31920	-1.31945	1122.37000
1.541	-5.567	-9.7991	-9.7670	-9.7483	-9.7577	-1.31351	-1.31353	-1.31292	-1.31323	1121.03000
1.541	-5.076	-87238	-86919	-86770	-86844	-1.31013	-1.31051	-1.30978	-1.31014	1120.55000
1.541	-4.580	-76981	-76713	-76561	-76637	-1.30805	-1.30737	-1.30661	-1.30699	1120.41499
1.541	-4.093	-66703	-66396	-66231	-66313	-1.29622	-1.29498	-1.29443	-1.29471	1121.12399
1.541	-3.602	-55999	-55706	-55533	-55619	-1.28281	-1.28092	-1.28044	-1.28068	1121.99800
1.541	-3.116	-45611	-45366	-45178	-45272	-1.26359	-1.26241	-1.26178	-1.26209	1123.38901
1.541	-2.638	-36728	-36407	-36227	-36317	-1.24620	-1.24578	-1.24568	-1.24568	1124.04100
1.541	-2.156	-29196	-29080	-28890	-28985	-1.23689	-1.23620	-1.23591	-1.23605	1123.81900
1.541	-1.682	-23023	-22936	-22754	-22845	-1.23739	-1.23620	-1.23591	-1.23605	1122.86900
1.542	-1.211	-17137	-16885	-16693	-16789	-1.23502	-1.23394	-1.23367	-1.23381	1122.92599
1.541	-7.734	-11125	-10899	-10711	-10805	-1.23483	-1.23432	-1.23410	-1.23421	1123.27499
1.542	-2.60	-05009	-04800	-04630	-04715	-1.24053	-1.23946	-1.23918	-1.23932	1123.35201
1.541	.252	.01518	.01551	.01745	.01648	-1.24460	-1.24340	-1.24318	-1.24329	1123.55701
1.542	.775	.08021	.07992	.08164	.08078	-1.24564	-1.24474	-1.24467	-1.24470	1123.81599
	GRADIENT	.15522	.15473	.15477	.15475	.01174	.01171	.01166	.01166	.46402 .22224

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 749

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM046) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	RN/L = 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = -1.500	PHI = 180.000	PT2F
MACH	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
ALPHA	.66627	.66468	.66548	-.11592	-.11384	-.11373	1568.90300
.599	-6.6619	-6.61891	-6.1972	-.11458	-.11282	-.11264	1596.50000
-7.062	-6.2006	-6.2053	-5.7285	-.11137	-.11156	-.11139	1597.11000
-6.552	-6.061	-5.7349	-5.2742	-.11070	-.10864	-.10849	1597.49001
-6.00	-5.564	-5.2840	-5.2566	-.10707	-.10668	-.10655	1582.12199
-600	-5.069	-4.8212	-4.8120	-.10475	-.104038	-.10642	1597.42999
-600	-4.578	-4.3699	-4.3565	-.10413	-.103489	-.10527	1584.88300
-600	-4.089	-3.9316	-3.9204	-.10309	-.103121	-.10500	1597.67000
-3.601	-3.4786	-3.4746	-3.4572	-.10293	-.102557	-.10513	1586.62601
-3.115	-2.9966	-3.0022	-2.9853	-.10222	-.101922	-.10687	1597.09000
-2.635	-2.5298	-2.5427	-2.5258	-.10155	-.10155	-.10681	1596.37000
-600	-2.160	-2.0922	-2.1064	-.100976	-.100973	-.10658	1588.79601
-599	-1.691	-1.6562	-1.6640	-.10047	-.10063	-.10425	1596.66000
-1.231	-1.2360	-1.2429	-1.2256	-.10023	-.100599	-.10410	1596.72000
-600	-778	-0.83333	-0.8413	-.098322	-.098322	-.10326	1591.79100
-600	-323	-0.4356	-0.4430	-.094349	-.094349	-.10282	1593.16499
-600	.189	.00008	.00018	-.00013	-.00016	-.10399	1594.10100
.600	.726	.04872	.04699	.04882	.04791	-.10442	1594.69200
.600	GRADIENT	.09199	.09160	.09152	.09156	-.10438	1595.06200
	RUN NO.	1462/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		
MACH	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
ALPHA	.79840	.79799	.79646	-.79722	-.74169	-.14429	14207
-7.047	-7.4266	-7.4230	-7.4109	-.74552	-.74552	-.14319	14334
-6.538	-6.044	-6.8596	-6.8682	-.68601	-.14340	-.14138	14151
-6.04	-5.543	-6.2976	-6.3118	-.62977	-.63047	-.14163	1317.01900
-5.50	-5.050	-5.7627	-5.7457	-.57627	-.57486	-.13791	13805
-4.560	-5.2083	-5.2179	-5.2026	-.52103	-.52103	-.13755	13722
-4.061	-4.6665	-4.6756	-4.6596	-.46676	-.46676	-.13571	13539
-3.571	-4.1105	-4.1186	-4.1032	-.41109	-.41109	-.13705	13501
-3.084	-3.5617	-3.5619	-3.5619	-.35688	-.35688	-.13718	13494
-2.598	-3.0090	-3.0258	-3.0101	-.30101	-.30179	-.13631	13436
-2.115	-2.4870	-2.4886	-2.4715	-.24715	-.24800	-.13400	13251
-1.639	-1.9588	-1.9632	-1.9472	-.19552	-.19552	-.13302	13259
-1.172	-1.4523	-1.4471	-1.4316	-.14394	-.14394	-.13283	1337.14200
-800	-0.9485	-0.9276	-0.9416	-.09346	-.09346	-.13266	13385
-800	-0.240	-0.4583	-0.4525	-.04379	-.04452	-.14120	1337.67101
-800	.271	.0795	.0700	.00789	.00789	-.13916	1338.24500
.800	.804	.6499	.6405	.06485	.06485	-.15298	1338.46300
.800	GRADIENT	.10945	.10964	.10965	.10965	-.00255	1338.52299
	RUN NO.	1462/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		
MACH	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
ALPHA	.79840	.79799	.79646	-.79722	-.74169	-.14429	14207
.800	-7.047	-7.4266	-7.4230	-.74552	-.74552	-.14319	14334
-6.538	-6.044	-6.8596	-6.8682	-.68601	-.14340	-.14138	14151
-6.04	-5.543	-6.2976	-6.3118	-.62977	-.63047	-.14163	1317.01900
-5.50	-5.050	-5.7627	-5.7457	-.57627	-.57486	-.13791	13805
-4.560	-5.2083	-5.2179	-5.2026	-.52103	-.52103	-.13755	13722
-4.061	-4.6665	-4.6756	-4.6596	-.46676	-.46676	-.13571	13539
-3.571	-4.1105	-4.1186	-4.1032	-.41109	-.41109	-.13705	13501
-3.084	-3.5617	-3.5619	-3.5619	-.35688	-.35688	-.13631	13494
-2.598	-3.0090	-3.0258	-3.0101	-.30101	-.30179	-.13437	13436
-2.115	-2.4870	-2.4886	-2.4715	-.24715	-.24800	-.13400	13251
-1.639	-1.9588	-1.9632	-1.9472	-.19552	-.19552	-.13302	13259
-1.172	-1.4523	-1.4471	-1.4316	-.14394	-.14394	-.13283	1337.14200
-800	-0.9485	-0.9276	-0.9416	-.09346	-.09346	-.13266	13385
-800	-0.240	-0.4583	-0.4525	-.04379	-.04452	-.14120	1337.67101
-800	.271	.0795	.0700	.00789	.00789	-.13916	1338.24500
.800	.804	.6499	.6405	.06485	.06485	-.15298	1338.46300
.800	GRADIENT	.10945	.10964	.10965	.10965	-.00255	1338.52299

PAGE 749 (UCM046) (04 OCT 91)

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

(UCM046) (04 OCT 91)

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 750

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM046) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1496/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-7.048	-.82875	-.83051	-.82846	-.82949	-.15048	-.14904	-.14862	-.14883	124.1	98.801
-6.537	-.76991	-.77226	-.77023	-.77124	-.77124	-.14782	-.14643	-.14593	-.14618	124.5	48.700
-6.041	-.71153	-.71426	-.71151	-.71288	-.71288	-.14843	-.14619	-.14591	-.14605	124.9	45.799
-5.549	-.65396	-.65666	-.65443	-.65555	-.65555	-.14606	-.14418	-.14412	-.14415	125.2	55.400
-5.050	-.59694	-.60021	-.59809	-.59915	-.59915	-.14167	-.13985	-.13969	-.13977	125.5	69.400
-4.558	-.54060	-.54360	-.54142	-.54251	-.54251	-.13920	-.13812	-.13827	-.13820	125.8	51.199
-4.063	-.48418	-.48631	-.48405	-.48518	-.48518	-.13970	-.13340	-.13870	-.13605	126.0	59.100
-3.572	-.42723	-.42913	-.42710	-.42812	-.42812	-.13967	-.13775	-.13777	-.13776	126.3	0.1601
-3.081	-.36961	-.37123	-.36897	-.37010	-.37010	-.13762	-.13956	-.13590	-.13773	126.4	77.800
-2.598	-.31378	-.31508	-.31305	-.31406	-.31406	-.13766	-.13804	-.13543	-.13673	126.6	39.700
-2.120	-.25801	-.25920	-.25714	-.25817	-.25817	-.13632	-.13678	-.13450	-.13564	126.7	72.301
-1.646	-.20385	-.20432	-.20235	-.20334	-.20334	-.13711	-.13647	-.13495	-.13571	126.8	69.400
-1.179	-.15081	-.15016	-.14842	-.14929	-.14929	-.13755	-.13539	-.13538	-.13538	126.9	43.900
-0.900	-.09789	-.09716	-.09554	-.09635	-.09635	-.14109	-.13788	-.13906	-.13847	127.0	0.0600
-0.900	-.04841	-.04732	-.04558	-.04645	-.04645	-.14664	-.14351	-.14455	-.14403	127.0	33.900
.900	.00708	.00675	.00849	.00762	.00762	-.15538	-.15434	-.15336	-.15385	127.0	70.100
.900	.790	.790	.06694	.06851	.06773	-.16022	-.15984	-.15818	-.15901	127.0	71.800
	GRADIENT	1.1387	.11450	.11437	.11444	-.00320	-.00329	-.00302	-.00316	2.27512	-.03541

RUN NO. 1479/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.099	-7.023	-.83538	-.83803	-.83625	-.83714	-.16276	-.16244	-.16203	-.16223	117.3	72.000
1.100	-6.508	-.77657	-.77803	-.77637	-.77720	-.16544	-.16449	-.16405	-.16427	117.7	46.899
1.100	-6.010	-.71868	-.72000	-.71826	-.71913	-.16152	-.16081	-.16039	-.16060	118.1	0.9300
1.100	-5.508	-.65983	-.66176	-.65995	-.66086	-.16057	-.15972	-.15938	-.15955	118.4	49.100
1.100	-5.015	-.60201	-.60393	-.60218	-.60305	-.15806	-.15701	-.15666	-.15684	118.7	56.799
1.100	-4.511	-.54368	-.54528	-.54350	-.54439	-.15762	-.15637	-.15600	-.15618	119.0	20.799
1.100	-4.020	-.48636	-.48627	-.48543	-.48540	-.15601	-.15513	-.15490	-.15501	119.2	68.800
1.100	-3.523	-.42637	-.42721	-.42540	-.42631	-.15372	-.15261	-.15214	-.15238	119.4	53.500
1.100	-3.028	-.36686	-.36744	-.36556	-.36650	-.15064	-.14941	-.14926	-.14933	119.6	85.899
1.100	-2.529	-.30613	-.30831	-.30637	-.30734	-.14995	-.14883	-.14855	-.14869	119.8	36.900
1.099	-2.044	-.24901	-.25068	-.24875	-.24971	-.14787	-.14749	-.14713	-.14731	119.9	45.399
1.100	-1.555	-.19280	-.19450	-.19245	-.19348	-.14668	-.14581	-.14562	-.14571	120.0	63.901
1.100	-1.069	-.13737	-.13821	-.13624	-.13722	-.14663	-.14545	-.14523	-.14534	120.1	28.700
1.100	-.589	-.08322	-.08401	-.08188	-.08295	-.14660	-.14594	-.14650	-.14655	120.1	89.99
1.100	-.115	-.02958	-.03109	-.02898	-.03003	-.14914	-.14799	-.14795	-.14795	120.2	17.999
1.100	.393	.02625	.02329	.02525	.02427	-.15219	-.15087	-.15068	-.15077	120.2	52.600
1.100	.911	.08462	.08200	.08376	.08288	-.15298	-.15157	-.15133	-.15145	120.2	67.300
	GRADIENT	.11609	.11580	.11582	.11584	-.00107	-.00103	-.00105	-.00105	2.23021	-.00498

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 751  
 (UCM046) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		RN/L = 0	GRADIENT INTERVAL = -5.00/ 5.00		BETA = -1.500	PHI = 180.000	PTTF	
		DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
MACH	ALPHA	.91666	-.91436	-.91551	-16579	-16344	-16311	-16327
	-7.038	-.91512	-.85247	-.85013	-16561	-16344	-16311	-16327
1.250	-6.525	-.85200	-.85013	-.85130	-16575	-16346	-16333	-16339
1.250	-6.031	-.78909	-.78914	-.78806	-16476	-16231	-16216	-16224
1.250	-5.532	-.72329	-.72365	-.72249	-16214	-15950	-15932	-15941
1.250	-5.034	-.65633	-.65837	-.65608	-15766	-15524	-15500	-15512
1.250	-4.540	-.59375	-.59591	-.59473	-15322	-15667	-15401	-15379
1.250	-4.046	-.53214	-.53339	-.53104	-15533	-15314	-15304	-15309
1.250	-3.558	-.46898	-.46949	-.46718	-15018	-15210	-14968	-14964
1.250	-3.068	-.40550	-.40630	-.40406	-15420	-14910	-14914	-14912
1.250	-2.578	-.34196	-.34360	-.34139	-15425	-15150	-14990	-14972
1.250	-2.091	-.28028	-.28112	-.27989	-15224	-15224	-14985	-14970
1.250	-1.615	-.22251	-.22219	-.22114	-15226	-15127	-15127	-15123
1.249	-1.249	-.16412	-.16319	-.16092	-15380	-15119	-15119	-15119
1.250	-1.143	-.10675	-.10507	-.10313	-15728	-15465	-15459	-15454
1.250	-0.675	-.04502	-.04697	-.04502	-16278	-16039	-16031	-16035
1.250	-0.208	-.04895	-.04697	-.04502	-16278	-16879	-16875	-16875
1.250	.305	.01456	.01500	.01703	-17147	-16871	-16879	-16879
1.250	.836	.08005	.08032	.08207	-17507	-17254	-17325	-17289
1.250	1.2534	.12592	.12582	.12587	-0.00296	-0.00292	.00302	.00297
GRADIENT								
RUN NO.		RN/L = 0	GRADIENT INTERVAL = -5.00/ 5.00		BETA = -1.500	PHI = 180.000	PTTF	
		DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
MACH	ALPHA	1.04969	1.05258	1.05060	-1.05159	-1.05456	-1.05456	-1.05456
	-7.035	-.97676	-.97965	-.97729	-1.97847	-1.98351	-1.98351	-1.98272
1.400	-6.521	-.90512	-.90599	-.90379	-1.90489	-1.8093	-1.8093	-1.7997
1.400	-6.028	-.83258	-.83294	-.83088	-1.83191	-1.7930	-1.7930	-1.7837
1.400	-5.528	-.75958	-.76099	-.75874	-1.75986	-1.8046	-1.8046	-1.7964
1.400	-5.029	-.68995	-.69148	-.68934	-1.69041	-1.7867	-1.7867	-1.7781
1.400	-4.534	-.61980	-.61759	-.61870	-1.6176	-1.7616	-1.7616	-1.7521
1.400	-4.047	-.54508	-.54720	-.54493	-1.54606	-1.7253	-1.7253	-1.7153
1.400	-3.554	-.46999	-.47125	-.46908	-1.47017	-1.7005	-1.7005	-1.6929
1.400	-3.057	-.39606	-.39651	-.39446	-1.39548	-1.6901	-1.6901	-1.6778
1.400	-2.570	-.32425	-.32551	-.32322	-1.32437	-1.6992	-1.6992	-1.6839
1.400	-2.084	-.25677	-.25799	-.25576	-1.25688	-1.7065	-1.7065	-1.6929
1.400	-1.602	-.19152	-.19091	-.18930	-1.19041	-1.7372	-1.7372	-1.7291
1.400	-1.134	-.12629	-.12521	-.12308	-1.12414	-1.7876	-1.7876	-1.7749
1.400	-0.660	-.05762	-.05557	-.05659	-1.05761	-1.8422	-1.8422	-1.8348
1.400	-0.191	-.01462	-.01416	-.01604	-1.01510	-1.9227	-1.9227	-1.9140
1.400	1.399	.08883	.08858	.08997	-1.04495	-1.9737	-1.9737	-1.9663
1.400	.847	.14450	.14500	.14491	-1.00353	-1.00353	-1.00353	-1.00354
GRADIENT								

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 752  
(UCM046) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1553/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000
MACH	ALPHA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.450	-7.050	-1.11043	-1.11224	-1.11040	-1.11132	-1.18138	-1.18141	-1.18081	-1.12511	1158.14600
1.450	-6.544	-1.03603	-1.03899	-1.03696	-1.03798	-1.17776	-1.17795	-1.17736	-1.17765	1158.26401
1.450	-6.052	-95866	-96149	-95958	-96054	-1.17821	-1.17823	-1.17777	-1.17800	1158.51300
1.450	-5.558	-88104	-88252	-88054	-88153	-1.17876	-1.17903	-1.17857	-1.17880	1158.21100
1.450	-5.064	-80670	-80828	-80613	-80720	-1.17735	-1.17733	-1.17689	-1.17711	1158.85001
1.450	-4.572	-73742	-73969	-73781	-73875	-1.17428	-1.17390	-1.17405	-1.17398	1158.38699
1.450	-4.076	-66180	-66444	-66227	-66335	-1.17382	-1.17337	-1.17340	-1.17339	1158.07100
1.450	-3.587	-58465	-58697	-58484	-58591	-1.17211	-1.17136	-1.17170	-1.17153	1158.41600
1.450	-3.103	-50599	-50822	-50624	-50723	-1.16770	-1.16670	-1.16643	-1.16657	1158.50301
1.450	-2.622	-42689	-42920	-42717	-42818	-1.16550	-1.16483	-1.16455	-1.16469	1158.45200
1.450	-2.142	-35451	-35571	-35371	-35471	-1.16387	-1.16319	-1.16686	-1.16702	1158.01199
1.450	-1.677	-28431	-28524	-28335	-28429	-1.16249	-1.16219	-1.16858	-1.16839	1158.59399
1.450	-1.213	-21745	-21823	-21626	-21725	-1.17500	-1.17408	-1.17446	-1.17427	1153.74899
1.450	-759	-14843	-14844	-14664	-14754	-1.18286	-1.18294	-1.18261	-1.18278	1158.60899
1.450	-304	-70913	-07803	-07622	-07712	-1.19356	-1.19347	-1.19321	-1.19334	1155.83200
1.450	.206	-00051	.00072	.00083	.00078	-2.0698	-2.0686	-2.0670	-2.0678	1155.45200
1.450	.745	.08177	.08180	.08321	.08250	-2.1455	-2.1421	-2.1411	-2.1416	1153.77299
	GRADIENT	.15385	.15458	.15448	.15438	-0.00730	-0.00739	-0.00734	-0.00737	-2.40909 -0.04228

	RUN NO.	1637/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000
MACH	ALPHA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.469	-7.049	-1.13575	-1.13236	-1.13089	-1.13162	-1.18179	-1.18103	-1.18013	-1.18058	1111.38400
1.470	-6.543	-1.06034	-1.0618	-1.05734	-1.0564	-1.18364	-1.18341	-1.18267	-1.18304	1114.54100
1.469	-6.046	-98616	-98419	-98258	-98339	-1.18357	-1.18373	-1.18272	-1.18314	1119.12000
1.470	-5.553	-90733	-90568	-90424	-90496	-1.18179	-1.18125	-1.18059	-1.18092	1122.72400
1.470	-5.062	-82575	-82345	-82192	-82268	-1.17919	-1.17877	-1.17809	-1.17843	1124.89799
1.470	-4.564	-74614	-74396	-74224	-74310	-1.17900	-1.17846	-1.17783	-1.17815	1126.40900
1.469	-4.074	-66870	-66697	-66517	-66607	-1.17639	-1.17528	-1.17495	-1.17511	1128.50200
1.469	-3.584	-59022	-58926	-58724	-58825	-1.17086	-1.16947	-1.16883	-1.16915	1130.53101
1.470	-3.097	-51213	-51060	-50866	-50963	-1.17021	-1.16899	-1.16836	-1.16867	1132.80200
1.470	-2.615	-43230	-43037	-43134	-43230	-1.16637	-1.16530	-1.16468	-1.16499	1133.24899
1.469	-2.134	-36048	-35913	-35730	-35821	-1.16801	-1.16674	-1.16610	-1.16642	1133.19501
1.469	-1.666	-29103	-29086	-28879	-28983	-1.17035	-1.16910	-1.16868	-1.16889	1133.93401
1.470	-1.202	-22307	-22315	-22217	-22217	-1.17491	-1.17321	-1.17314	-1.17317	1134.56200
1.469	-1.744	-15394	-15341	-15142	-15241	-1.18419	-1.18334	-1.18287	-1.18311	1135.25400
1.470	-1.283	-08128	-08192	-07991	-08092	-1.19693	-1.19547	-1.19492	-1.19520	1135.32100
1.470	.229	-00282	-00198	-00169	-00183	-2.1094	-2.0934	-2.0898	-2.0916	1135.53700
1.469	.766	.07977	.07874	.08070	.08070	-2.1811	-2.1643	-2.1597	-2.1620	1135.73801
	GRADIENT	.15434	.15386	.15379	.15382	-0.00733	-0.00746	-0.00734	-0.00734	1.58170 .06670

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM046) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1588/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000	PT2F
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	-7.051	-1.19964	-1.19700	-1.19634	-1.18637	-1.18566	-1.18524	-1.18545	1102.3399	1142.65500	
1.492	-6.544	-1.11729	-1.11499	-1.1137	-1.18634	-1.18551	-1.18511	-1.18531	1105.07300	1142.60626	
1.492	-6.047	-1.04484	-1.04278	-1.04215	-1.18414	-1.18370	-1.18330	-1.18350	1107.54900	1142.72787	
1.492	-5.549	-96875	-96610	-96548	-1.18932	-1.18849	-1.18816	-1.18833	1110.50500	1142.71173	
1.492	-5.053	-89189	-88894	-88782	-1.18822	-1.18787	-1.18752	-1.18770	1112.57401	1142.14529	
1.492	-4.560	-81214	-80998	-80864	-1.18802	-1.18701	-1.18709	-1.18705	1114.33501	1141.54628	
1.492	-4.069	-73216	-73020	-72894	-1.18692	-1.18580	-1.18562	-1.18571	1116.10201	1141.29274	
1.492	-3.579	-65426	-65122	-65206	-1.18369	-1.18259	-1.18255	-1.18255	1117.58000	1140.78427	
1.492	-3.091	-51186	-56934	-56765	-1.18153	-1.18063	-1.18061	-1.18062	1118.16499	1140.47679	
1.492	-2.605	-49286	-48981	-48897	-1.18438	-1.18317	-1.18315	-1.18316	1118.05400	1140.27420	
1.492	-2.127	-41286	-40988	-40831	-1.18891	-1.18798	-1.18790	-1.18794	1117.96300	1139.74234	
1.492	-1.658	-33243	-33141	-32995	-1.19458	-1.19339	-1.19339	-1.19339	1117.20399	1139.47189	
1.492	-1.189	-25402	-25351	-25166	-1.19982	-1.19872	-1.19867	-1.19869	1117.02600	1140.82520	
1.492	-729	-17592	-17474	-17387	-1.20841	-1.20718	-1.20721	-1.20719	1117.92900	1141.77339	
1.492	-270	-10509	-9481	-9331	-0.9406	-1.22330	-1.22232	-1.22231	1117.48300	1141.78560	
1.491	.244	-00520	-00456	-00436	-0.0446	-1.24084	-1.23953	-1.23954	1117.45900	1142.01752	
1.491	.780	.08837	.08765	.08929	.08847	-1.24887	-1.24731	-1.24745	1117.75101	1141.74446	
GRADIENT	.16859	.16810	.16805	.16807	.01179	-0.01172	-0.01176	-.01174	.32380	.16884	
RUN NO.		1604/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000	PT2F
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	-7.051	-1.36006	-1.35532	-1.35432	-1.35482	-2.1195	-2.11221	-2.11160	-2.11191	1107.78000	1134.72505
1.515	-6.539	-1.27652	-1.27105	-1.27010	-1.27058	-2.1434	-2.11376	-2.11408	1111.82100	1134.77681	
1.515	-6.041	-1.19043	-1.18522	-1.18424	-1.18473	-2.1868	-2.1857	-2.1804	-2.1831	1114.82100	1134.92018
1.514	-5.548	-1.10428	-1.09871	-1.09977	-1.0924	-2.1555	-2.1508	-2.1462	-2.1485	1118.02200	1134.49677
1.514	-5.057	-1.00464	-1.00095	-1.00095	-1.00032	-2.0955	-2.0921	-2.0870	-2.0870	1121.00200	1134.88217
1.514	-4.559	-90980	-90577	-90450	-1.90513	-2.0561	-2.0565	-2.0530	-2.0547	1122.82700	1134.31015
1.514	-4.069	-81305	-81165	-81165	-1.81235	-2.0921	-2.0908	-2.0881	-2.0894	1123.50900	1134.35406
1.514	-3.577	-73293	-72957	-72791	-1.72874	-2.1376	-2.1363	-2.1318	-2.1340	1123.97900	1134.28128
1.513	-3.091	-63886	-63589	-63437	-63513	-2.1884	-2.1831	-2.1793	-2.1812	1125.30901	1134.22659
1.513	-2.608	-54377	-54049	-53901	-53975	-2.1614	-2.1628	-2.1595	-2.1611	1126.70000	1134.36789
1.513	-2.126	-44349	-44011	-43858	-43934	-2.1679	-2.1656	-2.1612	-2.1634	1128.87000	1133.96281
1.514	-1.656	-34089	-33845	-33765	-33765	-2.1788	-2.1759	-2.1770	-2.1782	1129.75301	1133.61572
1.514	-1.192	-25005	-24824	-24915	-24915	-2.1799	-2.1795	-2.1767	-2.1781	1129.71001	1133.82384
1.514	-731	-16441	-16292	-16366	-16366	-2.2295	-2.2264	-2.2265	-2.2264	1129.54201	1133.91045
1.514	-269	-08136	-08074	-07912	-07993	-2.3554	-2.3522	-2.3494	-2.3508	1129.47501	1133.93161
1.514	.244	.01411	.01291	.01478	.01385	-2.4503	-2.4448	-2.4434	-2.4441	1129.78700	1133.85179
1.514	.777	.10580	.10558	.10718	.10638	-2.5319	-2.5283	-2.5278	-2.5280	1130.33501	1133.75948
GRADIENT	.19362	.19262	.19265	.19268	.00749	-.00743	-.00743	-.00746	1.52137	-.12099	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

TA310 (AEDC 16TE-783) PROBE CALIBRATION

PAGE 754

11206

	RUN NO.	1619 / O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00 /	5.00
MACH	DPA CAL	DPA 1	DPA 2	DPA	DPB CAL	DPB 1	DPB 2
1.542	-7.046	-1.30045	-1.29596	-1.29469	-1.29532	-2.3900	-2.3849
1.543	-6.539	-1.18171	-1.17596	-1.17463	-1.17529	-22652	-22597
1.542	-6.048	-1.06934	-1.06597	-1.06327	-1.06462	-22091	-22038
1.542	-5.548	-9.6094	-9.5787	-9.5628	-9.5707	-22004	-21946
1.542	-5.058	-85795	-85508	-85342	-85425	-21914	-21864
1.542	-4.560	-75200	-75015	-75107	-75107	-21605	-21535
1.542	-4.070	-64656	-64338	-64168	-64253	-20799	-20724
1.542	-3.579	-53372	-53140	-52963	-53052	-19388	-19297
1.541	-3.091	-43595	-43244	-43069	-43156	-17800	-17652
1.541	-2.604	-35423	-35216	-35031	-35123	-16807	-16670
1.541	-2.126	-28477	-28449	-28462	-28556	-16593	-16550
1.541	-1.657	-22803	-22715	-22538	-22627	-16801	-16665
1.541	-1.191	-16783	-16524	-16341	-16433	-16492	-16380
1.541	-729	-10816	-10567	-10376	-10471	-16615	-16474
1.541	-268	-05044	-04831	-04645	-04738	-17340	-17220
1.541	-244	01392	01346	01545	01445	-17936	-17936
1.541	-779	07915	07874	08062	07968	-18461	-18306
GRADIENT	15137	15077	15080	15079	00584	00602	00590

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM047) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1573/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000	PT2F
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	PT2F
ALPHA	.601	-.66273	-.66252	-.66103	-.61177	-.06863	-.06683	-.06642	-.06663	1569.59801	1597.50999
	-7.040	-.61589	-.61614	-.61468	-.61541	-.06681	-.06491	-.06455	-.06473	1573.10100	1596.62000
	-6.534	-.57073	-.57021	-.56865	-.56943	-.06433	-.06201	-.06167	-.06184	1576.95000	1597.10001
	-6.039	-.52502	-.52393	-.52243	-.52318	-.06220	-.05985	-.05953	-.05969	1579.73801	1596.89999
	-5.542	-.47864	-.47731	-.47574	-.47653	-.06310	-.06076	-.06042	-.06059	1582.61301	1596.95000
	-5.046	-.43522	-.43388	-.43225	-.43307	-.06263	-.06014	-.05997	-.06005	1585.11900	1596.49001
	-4.554	-.29690	-.29731	-.29569	-.29650	-.06085	-.05828	-.05805	-.05817	1587.38901	1597.52000
	-4.061	-.25073	-.24912	-.24992	-.24978	-.05702	-.05684	-.05693	-.05672	1588.88699	1596.38000
	-3.565	-.20634	-.20755	-.20586	-.20671	-.05727	-.05581	-.05564	-.05435	1594.02299	1597.22000
	-3.079	-.16177	-.16249	-.16074	-.16161	-.05592	-.05446	-.05424	-.05420	1594.71700	1596.92999
	-2.593	-.12077	-.12120	-.11944	-.12032	-.05581	-.05426	-.05413	-.05420	1595.49500	1597.10000
	-2.111	-.08185	-.08234	-.08062	-.08148	-.05779	-.05590	-.05592	-.05594	1595.49500	1597.10000
	-1.635	-.04468	-.04492	-.04321	-.04406	-.06814	-.06674	-.06674	-.06674	1595.74599	1597.16000
	-1.184	-.00166	-.00118	-.00164	-.00141	-.08338	-.08176	-.08175	-.08176	1595.71400	1597.00000
	-1.184	-.04842	-.04653	-.04824	-.04739	-.09030	-.08854	-.08875	-.08865	1596.13600	1597.35001
	-0.750	-.09158	-.09120	-.09114	-.09117	-.00378	-.00396	-.00403	-.00400	2.01075	.06000
	GRADIENT										
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	PT2F
ALPHA	.800	-.79298	-.79264	-.79142	-.79203	-.08595	-.08448	-.08402	-.08425	1310.07899	1340.99001
	-7.034	-.73717	-.73747	-.73630	-.73689	-.08476	-.08316	-.08254	-.08285	1314.22301	1341.11000
	-6.520	-.68172	-.68269	-.68118	-.68194	-.08232	-.08040	-.08008	-.08024	1317.86700	1341.00999
	-6.027	-.62522	-.62672	-.62524	-.62598	-.08132	-.07963	-.07928	-.07945	1321.08400	1341.02000
	-5.527	-.57109	-.57280	-.57146	-.57213	-.07874	-.07764	-.07739	-.07751	1324.16701	1340.85001
	-5.033	-.51768	-.51860	-.51729	-.51795	-.07932	-.07806	-.07782	-.07794	1327.05901	1341.22000
	-4.537	-.46350	-.46269	-.46212	-.46281	-.08079	-.07949	-.07924	-.07937	1329.40300	1341.11000
	-4.040	-.40760	-.40848	-.40699	-.40773	-.07917	-.07823	-.07799	-.07811	1331.45799	1340.97000
	-3.545	-.35122	-.35294	-.35127	-.35211	-.07981	-.07795	-.07780	-.07787	1333.25500	1341.00999
	-3.053	-.29737	-.29820	-.29663	-.29742	-.07849	-.07669	-.07642	-.07655	1334.86000	1341.07001
	-2.562	-.24443	-.24324	-.24402	-.24402	-.07656	-.07485	-.07466	-.07475	1336.06500	1340.96001
	-2.078	-.19304	-.19247	-.19217	-.19217	-.07480	-.07293	-.07278	-.07286	1337.02200	1341.03000
	-1.602	-.14186	-.14043	-.14115	-.14115	-.07514	-.07333	-.07332	-.07332	1337.72000	1341.08000
	-1.135	-.09398	-.09335	-.09193	-.09193	-.07649	-.07437	-.07427	-.07432	1338.32201	1340.98000
	-0.689	-.04879	-.04831	-.04669	-.04750	-.08582	-.08376	-.08338	-.08357	1338.56900	1340.94000
	GRADIENT	.818	.06483	.06403	.06564	.06484	-.10599	-.10404	-.10404	1339.01801	1341.07001
										-.00337	-.02301
										-.00339	-.19769

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 756  
(UCM047) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1497/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-7.028	-.82414	-.82260	-.82501	-.08970	-.08766	-.08718	-.08742	124.2 .48599	1273.50000
.900	-6.518	-.76488	-.76703	-.76604	-.08940	-.08781	-.08742	-.08761	124.6 .23000	1272.99001
.901	-6.023	-.70717	-.71005	-.70902	-.08772	-.08618	-.08580	-.08599	125.0 .03200	1273.32001
.900	-5.527	-.65037	-.65296	-.65192	-.08475	-.08337	-.08272	-.08305	125.3 .24300	1272.98000
.900	-5.031	-.59329	-.59655	-.59441	-.08253	-.08163	-.08124	-.08143	125.6 .18600	1272.78000
.900	-4.534	-.53721	-.54009	-.53806	-.08142	-.08054	-.08021	-.08037	125.9 .09000	1273.06000
.900	-4.040	-.48221	-.48002	-.48022	-.08117	-.08050	-.08018	-.08034	126.1 .32700	1273.00000
.900	-3.545	-.42420	-.42235	-.42218	-.08039	-.07966	-.07939	-.07952	126.3 .41600	1272.85001
.900	-3.052	-.36429	-.36596	-.36382	-.08035	-.07953	-.07921	-.07937	126.5 .47099	1272.89000
.900	-2.564	-.30854	-.30999	-.30784	-.07983	-.07796	-.07779	-.07788	126.6 .96899	1273.03000
.900	-2.081	-.25410	-.25492	-.25387	-.07867	-.07666	-.07655	-.07660	126.8 .19800	1272.96001
.900	-1.604	-.20020	-.20079	-.19892	-.07641	-.07478	-.07463	-.07470	126.9 .14500	1272.91000
.900	-1.142	-.14735	-.14688	-.14509	-.07745	-.07564	-.07547	-.07555	127.0 .03799	1273.08000
.900	-697	-.09757	-.09687	-.09605	-.07902	-.07716	-.07702	-.07709	127.0 .56200	1272.96001
.900	-264	-.05104	-.04999	-.04839	-.04919	-.08912	-.08693	-.08679	127.0 .91800	1273.08000
.900	.295	.01028	.00976	.01164	.01070	-.10373	-.10188	-.10195	.10191 .24499	1273.00999
.900	.811	.06697	.06714	.06879	.06796	-.11027	-.10824	-.10819	.10822 .22301	1273.03000
	GRADIENT	.11312	.11366	.11370	.00413	-.00385	-.00391	-.00388	.2.25231	.0.1293

	RUN NO.	1480/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1. 100	-7.018	-.83126	-.83434	-.83255	-.83345	-.10329	-.10183	-.10131	1174.41200	1204.77901
1. 100	-6.500	-.77499	-.77333	-.77416	-.10285	-.10161	-.10103	-.10132	1178.11301	1204.58701
1. 100	-6.007	-.71452	-.71626	-.71531	-.10389	-.10275	-.10206	-.10241	1181.83099	1204.55499
1. 100	-5.504	-.65601	-.65842	-.65752	-.10139	-.10083	-.10039	-.10061	1185.12300	1204.71201
1. 100	-5.009	-.59890	-.60103	-.59897	-.60000	-.09831	-.09694	-.09679	1188.05499	1204.48100
1. 100	-4.502	-.54045	-.54242	-.54143	-.10002	-.09900	-.09868	-.09884	1190.83900	1204.66200
1. 100	-4.011	-.48403	-.48442	-.48248	-.48345	-.09754	-.09606	-.09571	1193.19099	1204.80299
1. 100	-3.512	-.42346	-.42457	-.42273	-.42365	-.09461	-.09352	-.09330	.1195.38400	1204.63600
1. 100	-3.012	-.36343	-.36245	-.36352	-.36245	-.09224	-.09270	-.09190	.1197.20799	1204.71100
1. 100	-2.518	-.30438	-.30651	-.30432	-.30542	-.09188	-.09120	-.09087	.1198.67200	1204.59500
1. 100	-2.028	-.24860	-.25050	-.24849	-.24950	-.08978	-.08910	-.08919	.1200.08299	1204.71899
1. 100	-1.542	-.19256	-.19455	-.19247	-.19351	-.08814	-.08775	-.08763	.1201.00000	1204.72200
1. 100	-1.059	-.13808	-.13930	-.13729	-.13830	-.08802	-.08725	-.08695	.1201.60400	1204.47200
1. 100	-588	-.08450	-.08545	-.08445	-.08789	-.08711	-.08689	-.08700	.1202.31000	1204.77200
1. 100	-136	-.03361	-.03332	-.03438	-.03438	-.09166	-.09113	-.09080	.1202.62199	1204.83800
1. 100	-432	.02850	.02543	.02654	.02654	-.09794	-.09719	-.09679	.1203.01100	1204.80299
1. 100	-927	.08332	.08049	.08244	.08147	-.10111	-.10028	-.10006	.10017 .1203.04100	1204.67700
	GRADIENT	.11511	.11486	.11487	.11488	-.00029	-.00022	-.00021	.2.19865	.0.1047

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM047) ( 04 OCT 91 )

IASIU (AEDC 181F-183) FRUITE CALIBRATION

## PARAMETRIC DATA

RUN NO.		RN/L	=	2.50	GRADIENT INTERVAL = -5.00/ 5.00			BETA	=	-1.000	PHI	=	180.000
DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PTF	PT2F			
MACH	ALPHA												
1.250	-7.027	-9.1304	-9.1436	-9.1205	-9.1320	-10.034	-0.9804	-0.9760	-11.52	3.2700	1182.9400		
1.250	-6.514	-8.4798	-8.4829	-8.4605	-8.4717	-10.250	-100.013	-0.9978	-11.56	1.6701	1182.3844		
1.250	-6.016	-7.8513	-7.8539	-7.8326	-7.8433	-0.9890	-0.9625	-0.9599	-11.59	6.4900	1181.8111		
1.250	-5.518	-7.1929	-7.1971	-7.1733	-7.1852	-0.9794	-0.9609	-0.9581	-11.63	4.3100	1183.0776		
1.250	-5.019	-6.65338	-6.65548	-6.65296	-6.65422	-0.9419	-0.9234	-0.9198	-11.65	6.7101	1182.6888		
1.250	-4.525	-5.9088	-5.9276	-5.9034	-5.9155	-0.9373	-0.9201	-0.9164	-11.67	6.4301	1182.3336		
1.250	-4.029	-5.2940	-5.3058	-5.2834	-5.2946	-0.9060	-0.8874	-0.8854	-11.70	2.2900	1182.2830		
1.250	-3.531	-4.6468	-4.6537	-4.6319	-4.6428	-0.986	-0.9717	-0.8686	-11.72	6.9099	1182.4386		
1.250	-3.040	-4.0040	-4.0110	-3.9881	-3.9995	-0.9036	-0.8772	-0.8761	-11.74	8.3000	1182.5488		
1.250	-2.551	-3.3745	-3.3905	-3.3692	-3.3798	-0.8941	-0.8675	-0.8658	-11.76	4.3800	1182.3822		
1.250	-2.063	-2.27694	-2.27776	-2.27557	-2.2766	-0.8946	-0.8662	-0.8636	-11.77	6.7101	1182.3910		
1.250	-1.582	-2.1906	-2.1976	-2.1661	-2.1768	-0.8916	-0.8624	-0.8613	-11.79	0.0720	1182.8177		
1.250	-1.113	-1.6140	-1.6046	-1.5847	-1.5947	-0.8950	-0.8653	-0.8656	-11.80	0.0460	1182.8677		
1.250	-0.660	-1.0601	-1.0434	-1.0232	-1.0333	-0.9095	-0.8810	-0.8800	-11.80	0.1130	1182.2940		
1.250	-0.222	-0.5182	-0.5032	-0.4935	-0.4910	-0.9541	-0.9549	-0.9545	-11.80	0.33800	1182.3966		
1.250	0.291	0.1108	0.1137	0.11330	0.11209	-10.946	-10.951	-10.951	-11.80	0.63000	1182.5877		
1.250	0.848	0.08023	0.08052	0.08218	0.08135	-1.1888	-1.1593	-1.1605	-11.80	0.63000	1182.5877		
GRADIENT	12475	12528	12517	12522	0.0385	-0.0368	-0.0373	-0.0373	2.38865	.0555			

GRADIENT INTERVAL = -5.00/-5.00

MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBC AL	DPB 1	DPB 2	DPB	PTTF	PTT
1.400	-7.024	-1.04598	-1.04889	-1.04668	-1.04779	-1.0630	-1.07842	-1.0369	-0.9106	1163.774	
1.400	-6.511	-9.72669	-9.7578	-9.7331	-9.7455	-10.778	-10.7990	-10.531	-0.9261	1164.5606	
1.400	-6.014	-9.0075	-9.0196	-8.9975	-9.0086	-10.729	-10.8043	-10.593	-0.9318	1163.8583	
1.400	-5.515	-8.2845	-8.2929	-8.2686	-8.2807	-10.393	-10.7690	-10.240	-0.8965	1164.5080	
1.400	-5.021	-7.5744	-7.5885	-7.5647	-7.5766	-10.391	-10.7659	-10.217	-0.8938	1164.0582	
1.400	-4.522	-6.8728	-6.8875	-6.8645	-6.8760	-10.414	-10.7707	-10.270	-0.8989	1164.5755	
1.400	-4.027	-6.1464	-6.1620	-6.1393	-6.1507	-10.973	-10.7321	-0.9881	-0.8601	1164.7100	1164.1511
1.400	-3.528	-5.3829	-5.4009	-5.3789	-5.3899	-0.9821	-0.9734	-0.9734	-0.8456	1154.1670	1163.6749
1.400	-3.032	-4.6261	-4.6392	-4.6161	-4.6277	-0.9728	-0.7124	-0.9696	-0.8410	1156.5320	1164.3486
1.400	-2.542	-3.8894	-3.8960	-3.8735	-3.8847	-0.9827	-0.7169	-0.9723	-0.8446	1157.2710	1164.1830
1.400	-2.054	-3.199	-3.2108	-3.1890	-3.1999	-0.9606	-0.6968	-0.9545	-0.8256	1158.4030	1164.4324
1.400	-1.576	-2.5399	-2.5509	-2.5302	-2.5406	-0.9798	-0.7069	-0.9648	-0.8359	1159.9850	1164.3084
1.400	-1.106	-1.8912	-1.8910	-1.8707	-1.8808	-1.0008	-0.7281	-0.9872	-0.8577	1161.1940	1163.9855
1.400	-0.649	-1.2385	-1.2277	-1.2072	-1.2174	-1.0268	-0.7524	-1.0117	-0.8821	1162.1820	1164.1366
1.400	-0.203	-0.6043	-0.5933	-0.5752	-0.5843	-1.1014	-0.8293	-1.0862	-0.9578	1162.7430	1164.6322
1.400	-0.308	-0.1170	-0.1126	-0.1312	-0.1209	-1.2509	-0.9759	-1.2352	-1.1054	1162.4980	1163.5322
1.400	.860	.08998	.0914	.09094	.0914	-1.3272	-1.0546	-1.3142	-1.1844	1162.4640	1164.4555
	GRADIENT	14397	14440	14427	14434	.00477	.00458	.00465	.00462	2.37469	.013

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 758  
 (UCM047) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1554/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.449	-7.037	-1.10765	-1.10934	-1.10754	-1.10844	-0.9769	-0.9711	-0.9644	-0.9677	1.126.10400
1.450	-6.525	-1.03007	-1.03273	-1.03080	-1.03176	-1.0053	-1.0011	-0.9960	-0.9986	1.128.99300
1.450	-6.029	-95337	-95618	-95405	-95511	-0.9900	-0.9930	-0.9872	-0.9901	1.132.53999
1.450	-5.532	-87728	-87780	-87674	-87772	-0.9985	-0.9996	-0.9939	-0.9967	1.135.65500
1.450	-5.035	-80396	-80572	-80356	-80464	-0.9788	-0.9740	-0.9689	-0.9714	1.139.02299
1.450	-4.542	-73160	-73381	-73195	-73288	-0.9671	-0.9578	-0.9538	-0.9558	1.142.65100
1.450	-4.048	-65522	-65800	-65587	-65693	-0.9409	-0.9320	-0.9291	-0.9305	1.145.35899
1.450	-3.554	-57778	-58005	-57784	-57894	-0.9233	-0.9148	-0.9108	-0.9128	1.148.14700
1.451	-3.066	-49620	-49820	-49622	-49721	-0.9158	-0.9095	-0.9054	-0.9074	1.148.85201
1.449	-2.580	-41822	-42040	-41841	-41941	-0.9121	-0.904	-0.8961	-0.8983	1.148.96600
1.450	-2.099	-34793	-34924	-34724	-34824	-0.8995	-0.8913	-0.8884	-0.8899	1.151.32800
1.450	-1.622	-28023	-28114	-27919	-28016	-0.8923	-0.8935	-0.8922	-0.8922	1.152.77100
1.450	-1.166	-21413	-21509	-21305	-21407	-0.9633	-0.9406	-0.9375	-0.9390	1.155.97301
1.450	-735	-14563	-14376	-14376	-14471	-1.0081	-0.9832	-0.9805	-0.9819	1.158.41400
1.450	-314	-08194	-08071	-07888	-07980	-1.1468	-1.1219	-1.1209	-1.1214	1.158.66299
1.449	.246	.00585	.00512	.00699	.00606	-1.3759	-1.3505	-1.3480	-1.3493	1.158.49100
1.450	.770	.08428	.08437	.08561	.08499	-1.4833	-1.4749	-1.4729	-1.4739	1.156.96001
	GRADIENT	.15303	.15363	.15358	.00866	-0.00838	-0.00842	-0.00840	3.07082	.00597
	RUN NO.	1638/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.470	-7.033	-1.12946	-1.12627	-1.12474	-1.12550	-1.0286	-1.0056	-0.9977	-1.0017	1.111.37000
1.471	-6.526	-1.05633	-1.05425	-1.05342	-1.05342	-1.0319	-1.0087	-0.9999	-1.0043	1.115.14499
1.470	-6.029	-98170	-98002	-97812	-97907	-1.0160	-1.0050	-0.9930	-0.9890	1.119.91600
1.471	-5.533	-90212	-90049	-89879	-89984	-1.0249	-1.0138	-1.0061	-1.0099	1.123.44000
1.470	-5.035	-82005	-81777	-81607	-81692	-1.0021	-0.9910	-0.9827	-0.9868	1.124.75400
1.470	-4.542	-74207	-73999	-73819	-73909	-0.9665	-0.9546	-0.9469	-0.9507	1.126.58701
1.470	-4.043	-66392	-66043	-66143	-66243	-0.9286	-0.9161	-0.9101	-0.9131	1.128.79500
1.469	-3.552	-58349	-58232	-58051	-58141	-0.9294	-0.9181	-0.9125	-0.9153	1.131.43800
1.470	-3.065	-50360	-50214	-50033	-50123	-0.9064	-0.9029	-0.8968	-0.8998	1.133.01700
1.470	-2.573	-42544	-42389	-42185	-42287	-0.8867	-0.8801	-0.8750	-0.8776	1.132.74899
1.470	-2.095	-35604	-35377	-35477	-35477	-0.8711	-0.8653	-0.8608	-0.8631	1.133.58800
1.470	-1.621	-28682	-28501	-28611	-28611	-0.8868	-0.8815	-0.8757	-0.8786	1.134.63901
1.471	-1.158	-21882	-21908	-21695	-21801	-0.9223	-0.9161	-0.9114	-0.9138	1.135.17700
1.470	-719	-15279	-15040	-15142	-15040	-0.9944	-0.9893	-0.9839	-0.9866	1.135.67101
1.470	-293	-08459	-08514	-08320	-08417	-1.1585	-1.1527	-1.1504	-1.1515	1.136.07401
1.471	.215	.00462	.00443	.00443	.00443	-1.3856	-1.3769	-1.3755	-1.3762	1.136.10800
1.484	.782	.08367	.08427	.08424	.08335	-1.4996	-1.4922	-1.4896	-1.4909	1.136.27600
	GRADIENT	.15337	.15337	.15337	.00888	-0.00897	-0.00906	-0.00901	1.66706	1.51657

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 759  
(UCM047) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1589/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-1.000	PHI	=	180.000
MACH	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F		
ALPHA	-1.19644	-1.19356	-1.19237	-1.19296	-1.10199	-1.10052	-1.10031	-1.10041	1102.28799	114.1	94653	
	-1.11111	-1.10958	-1.1034	-1.10392	-1.10264	-1.10225	-1.10244	-1.104.02100	114.1	77559		
	-1.04314	-1.04075	-1.04018	-1.0339	-1.10239	-1.10205	-1.10222	-1.106.66499	114.1	87981		
	-1.96670	-1.96499	-1.96369	-1.96434	-1.10116	-1.09965	-1.09926	-1.110.05800	114.2	40065		
	-1.89045	-1.88743	-1.88675	-1.88709	-1.10148	-1.10114	-1.09979	-1.112.51100	114.2	14957		
	-1.80907	-1.80554	-1.80622	-1.80919	-1.09795	-1.09771	-1.09783	-1.114.79500	114.2	05310		
	-1.72697	-1.72541	-1.72619	-1.09995	-1.09862	-1.09833	-1.09847	-1.116.94501	114.1	85199		
	-1.64735	-1.64596	-1.64439	-1.64517	-1.09842	-1.09669	-1.09650	-1.09660	1118.71600	114.1	44019	
	-1.56328	-1.56577	-1.56161	-1.56244	-1.09900	-1.09740	-1.09721	-1.09731	1119.64600	114.1	68890	
	-1.48629	-1.48347	-1.48191	-1.48269	-1.09915	-1.09707	-1.09691	-1.09699	1120.00200	114.1	92471	
	-1.40639	-1.40347	-1.40177	-1.40262	-1.10107	-1.09935	-1.09923	-1.09929	1120.19400	114.1	95667	
	-1.32796	-1.32695	-1.32523	-1.32609	-1.10586	-1.10317	-1.10311	-1.10314	1119.47501	114.2	08752	
	-1.24905	-1.24956	-1.24741	-1.24823	-1.10940	-1.10655	-1.10662	-1.10658	1118.44701	114.1	87595	
	-1.17165	-1.17455	-1.17165	-1.17255	-1.11634	-1.11364	-1.11361	-1.11363	1117.98700	114.2	02721	
	-1.09783	-1.09841	-1.09704	-1.09726	-1.13613	-1.13323	-1.13323	-1.13324	1117.62100	114.1	98232	
	-1.00635	-1.00756	-1.00605	-1.00620	-1.16004	-1.15814	-1.15828	-1.15821	1117.12601	114.1	91473	
	.09316	.09243	.09241	.09241	-1.17222	-1.17027	-1.17099	-1.17063	1116.85800	114.2	11665	
GRADIENT	.16805	.16848	.16805	.16798	.16801	.161265	.01243	.01249	.03118	.04936		

	RUN NO.	1605/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA	=	-1.000	PHI	=	180.000
MACH	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F		
ALPHA	-1.36016	-1.35318	-1.35366	-1.35385	-1.11757	-1.11687	-1.11687	-1.11722	1108.05099	1134	33553	
	-1.27462	-1.26916	-1.26797	-1.26856	-1.11908	-1.11883	-1.11820	-1.11851	1112.47200	1134	58662	
	-1.18605	-1.19118	-1.18605	-1.18550	-1.12091	-1.12015	-1.11947	-1.11981	1116.57100	1135	71974	
	-1.10040	-1.09575	-1.09446	-1.09511	-1.11409	-1.11353	-1.11297	-1.11325	1121.14999	1136	65463	
	-1.99679	-1.99322	-1.99185	-1.99254	-1.11095	-1.11063	-1.11024	-1.11043	1124.74100	1136	61333	
	-1.90116	-1.89691	-1.89563	-1.89627	-1.11105	-1.11054	-1.11006	-1.11030	1123.73300	1134	32092	
	-1.81307	-1.80710	-1.80782	-1.80732	-1.11374	-1.11370	-1.11340	-1.11355	1123.36400	1134	34715	
	-1.72632	-1.72475	-1.72553	-1.72553	-1.11576	-1.11609	-1.11568	-1.11589	1124.96300	1134	30823	
	-1.62876	-1.62588	-1.62429	-1.62509	-1.11833	-1.11775	-1.11732	-1.11753	1127.17000	1134	70361	
	-1.52746	-1.52408	-1.52245	-1.52327	-1.12051	-1.11945	-1.11921	-1.11933	1129.07401	1135	10460	
	-1.42908	-1.42394	-1.42477	-1.42477	-1.11958	-1.11883	-1.11855	-1.11869	1131.33501	1135	40706	
	-1.32705	-1.32491	-1.32325	-1.32408	-1.11759	-1.11686	-1.11674	-1.11680	1131.86301	1135	61313	
	-1.23778	-1.23687	-1.23687	-1.23687	-1.11962	-1.11876	-1.11852	-1.11864	1131.69501	1136	23242	
	-1.15907	-1.15736	-1.15736	-1.15736	-1.12960	-1.12877	-1.12860	-1.12868	1131.60400	1136	87892	
	-1.08381	-1.08177	-1.08269	-1.08269	-1.14862	-1.14776	-1.14774	-1.14775	1131.82899	1137	14720	
	.00683	.00595	.00765	.00680	-1.17233	-1.17131	-1.17176	-1.17153	1132.14200	1137	.03362	
GRADIENT	.799	.10358	.10326	.10412	-.18112	-.18046	-.18046	-.18049	1133.11900	1136	.96112	
	.19124	.19132	.19128	.19128	-.01154	-.01152	-.01152	-.01146	1.91702	.63813		

TARIO (REDDUC TION) - ROBB SHELDON

(UCM-047) ( 04 OCT 91 )  
PAGE 760

## PARAMETRIC DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 761  
 (UCM048) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1574/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- .500	PHI =	= 180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
ALPHA	.65947	-.65935	-.65752	-.65844	-.01893	-.01737	-.01716	1569.64200	1596.73000
.600	-7.023	-6.514	-6.0984	-6.0832	-.60915	-.01784	-.01551	1596.86099	1596.64000
.599	-6.011	-5.6569	-5.6516	-5.6433	-.01823	-.01578	-.01559	1577.21600	1597.10001
.599	-5.513	-5.2014	-5.1910	-5.1752	-.51831	-.01526	-.01243	1580.24500	1596.12000
.600	-5.021	-4.7631	-4.7519	-4.7350	-.47434	-.01395	-.01121	1583.14700	1597.35001
.601	-4.523	-4.3143	-4.3058	-4.2901	-.42979	-.01463	-.01238	1585.29401	1597.00000
.600	-4.026	-3.8673	-3.8559	-3.8387	-.38473	-.01425	-.01185	1587.58800	1596.97000
.600	-3.528	-3.3871	-3.3899	-3.3739	-.33819	-.01452	-.01198	1589.75700	1596.75999
.600	-3.030	-2.9138	-2.9189	-2.9024	-.29107	-.01397	-.01136	1591.03000	1596.32001
.601	-2.537	-2.4503	-2.4649	-2.4472	-.24560	-.01330	-.01088	1592.81000	1597.47000
.600	-2.049	-1.9935	-2.0082	-1.9909	-.19995	-.01153	-.00871	1593.46800	1596.14999
.601	-1.561	-1.5467	-1.5529	-1.5360	-.15445	-.00911	-.00643	1594.53900	1596.89000
.601	-1.088	-1.1025	-1.1068	-1.0903	-.10986	-.00673	-.00511	1595.26401	1597.44000
.600	-6.54	-0.7344	-0.7387	-0.7220	-.07304	-.00648	-.00480	1595.63000	1597.25000
.600	-310	-0.4523	-0.4571	-0.4408	-.04489	-.01438	-.01286	1597.5101	1596.95000
.601	.248	-0.0149	.00113	.00123	-.00123	-.04607	-.04419	1596.05000	1596.92999
.601	.828	.05252	.05096	.05275	.05185	-.05282	-.05123	1597.28200	1597.88000
	GRADIENT	.09063	.09055	.09059	-.00472	-.00491	-.00495	.1.98905	.1.11801

RUN NO.	1464/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- .500	PHI =	= 180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
ALPHA	.78746	-.78634	-.78695	-.73259	-.73328	-.03273	-.03034	1310.50999	1341.07001
.800	-7.018	-6.507	-7.3327	-7.3398	-.67734	-.02877	-.02694	1314.47000	1340.87000
.800	-6.006	-5.505	-6.7763	-6.7893	-.62240	-.02772	-.02619	1318.11501	1341.05000
.800	-5.010	-4.515	-6.2299	-6.2322	-.56806	-.02525	-.02391	1321.72501	1341.13000
.800	-4.014	-3.518	-4.0346	-4.0452	-.40303	-.02311	-.02358	1324.59599	1340.72000
.800	-3.022	-3.4762	-3.4935	-3.4781	-.34858	-.02115	-.02241	1327.26601	1340.86000
.800	-2.530	-2.9762	-2.9363	-2.9201	-.29282	-.02086	-.02065	1329.77800	1341.07001
.800	-2.033	-2.3940	-2.3974	-2.3817	-.23896	-.02095	-.01923	1331.81000	1340.78000
.800	-1.549	-1.8526	-1.8575	-1.8401	-.18488	-.01956	-.01781	1333.83200	1341.06000
.800	-1.072	-1.3245	-1.3092	-1.3169	-.1838	-.01609	-.01602	1338.83701	1341.22000
.800	-6.20	.08863	.08825	.08654	-.08740	-.01660	-.01406	1339.1341	140000
.802	-2.18	.04734	.04676	.04528	-.04602	-.03058	-.02845	1336.36800	1340.12000
.800	.329	.00933	.00847	.01010	-.00929	-.05348	-.05125	1339.83000	1338.72000
.800	.886	.06988	.06882	.07054	-.06968	-.05515	-.05517	1339.05000	1341.88000
	GRADIENT	.10816	.10833	.10835	-.00494	-.00467	-.00469	.2.08564	.0.08977

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 762  
 (UCM048) (04 OCT 91)

## PARAMETRIC DATA

		RUN NO.	1498/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- .500	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	.82013	-.82222	-.81999	-.82110	-.03379	-.03151	-.03125	-.03138	1242.82700	1273.22000	
.900	-7.016	-.76108	-.76364	-.76150	-.03207	-.03005	-.02950	-.02977	1246.60899	1273.00000	
.900	-6.503	-.70354	-.70642	-.70445	-.02974	-.02804	-.02763	-.02783	1250.34700	1272.92999	
.900	-6.006	-.64695	-.64954	-.64748	-.02533	-.02413	-.02384	-.02398	1253.73599	1273.17000	
.900	-5.504	-.58995	-.59315	-.59105	-.02431	-.02329	-.02302	-.02315	1256.98000	1273.12000	
.900	-5.012	-.53408	-.53665	-.53510	-.02159	-.02081	-.02059	-.02070	1259.45300	1273.06000	
.900	-4.510	-.47700	-.47912	-.47697	-.02131	-.02035	-.01996	-.02016	1261.59900	1272.70000	
.900	-4.012	-.41895	-.42069	-.41869	-.02154	-.02101	-.02061	-.02081	1264.11400	1273.14000	
.900	-3.520	-.36007	-.36155	-.35965	-.02340	-.02192	-.02171	-.02181	1264.71899	1270.91000	
.900	-3.017	-.30361	-.30518	-.30325	-.02067	-.01942	-.01927	-.01927	1265.50101	1271.59000	
.901	-2.524	-.24804	-.24883	-.24696	-.02019	-.01909	-.01882	-.01896	1267.82800	1272.17000	
.900	-2.031	-.19205	-.19297	-.19097	-.01950	-.01748	-.01716	-.01732	1270.12900	1274.05000	
.900	-1.547	-.13904	-.13870	-.13868	-.01786	-.01595	-.01585	-.01590	1270.39400	1272.73000	
.900	-1.070	-.09141	-.09065	-.08913	-.08989	-.01758	-.01538	-.01518	1271.37700	1272.88000	
.900	-623	-.05237	-.05146	-.04987	-.05066	-.02463	-.02271	-.02250	1271.74300	1273.50000	
.900	-259	-.00913	-.00891	-.01051	-.00971	-.05443	-.05234	-.05235	1270.68800	1272.41000	
.900	-313	-.07217	-.07200	-.07366	-.07283	-.05925	-.05739	-.05725	1272.46800	1274.58000	
.900	.881	GRADIENT	.11247	.11304	.11297	.11301	-.00506	-.00478	-.00483	-.00488	.2.38688
											.22980
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	.83319	-.83244	-.83864	-.83554	-.04748	-.04625	-.04589	-.04607	1174.63699	1204.78200	
1.00	-7.012	-.77336	-.77338	-.7733	-.04545	-.04408	-.04365	-.04387	1178.24699	1204.77400	
1.00	-6.497	-.71546	-.72069	-.71807	-.04555	-.04485	-.04436	-.04461	1182.14600	1204.96001	
1.00	-5.998	-.65770	-.66354	-.66062	-.04266	-.04176	-.04143	-.04160	1185.31599	1204.59599	
1.00	-5.499	-.60039	-.60336	-.60345	-.03844	-.03799	-.03799	-.03816	1188.35899	1204.92400	
1.00	-5.005	-.54154	-.54227	-.54824	-.04003	-.03993	-.03954	-.03973	1190.98599	1204.54300	
1.00	-4.500	-.48365	-.48935	-.48650	-.03650	-.03639	-.03609	-.03624	1193.39000	1204.84200	
1.00	-4.001	-.42337	-.42360	-.42647	-.03475	-.03467	-.03441	-.03454	1195.65700	1204.70100	
1.00	-3.506	-.36394	-.36516	-.36667	-.03392	-.03392	-.03353	-.03372	1197.54800	1204.60001	
1.00	-3.005	-.30520	-.30536	-.31107	-.03409	-.03372	-.03349	-.03360	1199.03200	1204.51801	
1.00	-2.509	-.24836	-.24880	-.25447	-.03382	-.03334	-.03308	-.03321	1200.40601	1204.62900	
1.00	-2.010	-.19255	-.19227	-.19509	-.03357	-.03314	-.03293	-.03304	1201.24200	1204.60100	
1.00	-1.518	-.13791	-.13692	-.13978	-.03020	-.02999	-.02974	-.02986	1202.05800	1204.64999	
1.00	-1.025	-.08604	-.09111	-.08888	-.03000	-.02974	-.02950	-.02961	1202.50400	1204.79500	
1.00	-571	-.03594	-.03511	-.04067	-.03789	-.03839	-.03754	-.03730	1202.95799	1204.63499	
1.00	-102	-.02337	-.01775	-.02056	-.04524	-.04401	-.04395	-.04398	1203.28999	1204.87000	
1.00	-440	-.02445	-.02445	-.01750	-.04545	-.04428	-.04423	-.04426	1203.27600	1204.63100	
1.00	.966	GRADIENT	.11413	.11416	.11415	-.00094	-.00074	-.00077	2.1913	.01469	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM048) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1521/ 0	RN/L =	2.50	GRADIENT INTERVAL =	- 5.00/ 5.00	BETA =	-.500	PHI =	180.000
MACH	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	-.90970	-.90751	-.90861	-.03465	-.03232	-.03178	-.03205	1152.37100	1182.56000	
1.250	-7.018	-8.4453	-8.4209	-.034331	-.03413	-.03215	-.03191	1156.40100	1182.24600	
1.250	-6.503	-8.4418	-7.8128	-.03570	-.03411	-.03385	-.03398	1160.44200	1182.50500	
1.250	-6.004	-7.8128	-7.7951	-.03379	-.03235	-.03209	-.03222	1163.42101	1182.47099	
1.250	-5.504	-7.1546	-7.1331	-.03379	-.03295	-.02905	-.02887	1165.69099	1182.56599	
1.250	-5.005	-6.5060	-6.5252	-.03072	-.02972	-.02813	-.02795	1168.20000	1182.62700	
1.250	-4.505	-5.8836	-5.9039	-.02972	-.02972	-.02459	-.02443	1170.85300	1182.57899	
1.250	-4.012	-5.2591	-5.2742	-.02639	-.02639	-.02427	-.02427	1173.45000	1182.36301	
1.250	-3.513	-4.6063	-4.6162	-.02748	-.02748	-.02592	-.02592	1174.84000	1182.19400	
1.250	-3.014	-3.9568	-3.9658	-.02797	-.02797	-.02552	-.02539	1176.49600	1182.30299	
1.250	-2.520	-3.3229	-3.3376	-.02606	-.02606	-.02351	-.02328	1178.74600	1183.14101	
1.250	-2.024	-2.7288	-2.7339	-.02551	-.02551	-.02313	-.02291	1179.03799	1181.98900	
1.250	-1.536	-2.1373	-2.1353	-.02560	-.02560	-.02298	-.02281	1179.42101	1182.09500	
1.250	-1.055	-1.5497	-1.5394	-.02356	-.02356	-.02050	-.02050	1179.42101	1182.09500	
1.250	-604	-.09967	-.09850	-.09742	-.09742	-.01944	-.01934	1180.82800	1183.16600	
1.249	-192	-.04994	-.04842	-.04744	-.04744	-.03387	-.03379	1180.38100	1182.06200	
1.250	.354	.01747	.01766	-.01969	-.01868	-.05267	-.05267	1181.33200	1182.85500	
1.250	.910	.08556	.08569	.08733	-.08651	-.05728	-.05728	1181.01900	1182.55299	
	GRADIENT	.12406	.12460	.12447	-.00447	-.00423	-.00423	.00426	2.32621	.01917
MACH	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	-.04040	-.04354	-.04117	-.04235	-.03594	-.00836	-.03392	1132.86000	1163.87399	
1.399	-7.017	-.96733	-.96827	-.96931	-.03531	-.00727	-.03282	1136.92400	1164.61000	
1.400	-6.496	-.89713	-.89846	-.89744	-.03273	-.00489	-.03043	1140.67599	1164.08299	
1.400	-5.997	-.82428	-.82530	-.82415	-.03163	-.00476	-.03034	1143.72301	1164.32401	
1.400	-5.497	-.75512	-.75651	-.75420	-.03052	-.00374	-.02905	1147.22600	1164.21100	
1.400	-5.009	-.68339	-.68485	-.68266	-.68376	-.00133	-.02679	1150.20599	1164.51401	
1.400	-4.505	-.61068	-.61246	-.61127	-.61127	-.00998	-.02662	1153.20799	1164.09500	
1.399	-4.011	-.53325	-.53461	-.53236	-.53349	-.00161	-.02388	1154.67700	1164.15700	
1.400	-3.512	-.45617	-.45736	-.45617	-.45727	-.00158	-.02412	1156.61501	1164.22800	
1.400	-3.013	-.38427	-.38488	-.38274	-.38381	-.00165	-.02397	1157.28999	1163.91499	
1.400	-2.518	-.31591	-.31686	-.31482	-.31584	-.00143	-.02416	1158.90199	1164.78500	
1.400	-2.022	-.24863	-.24991	-.24773	-.24882	-.00143	-.02420	1160.64900	1163.94099	
1.400	-1.530	-.18212	-.18178	-.17914	-.18046	-.00256	-.02403	1161.70300	1163.92700	
1.400	-1.053	-.11624	-.11729	-.11519	-.12031	-.00344	-.02237	1162.79201	1164.37100	
1.400	-595	-.05821	-.05680	-.05493	-.05587	-.01189	-.03760	1162.49300	1164.42599	
1.400	-177	-.01939	-.01874	-.02080	-.01977	-.05907	-.03232	1162.47301	1163.78999	
1.400	.373	.09576	.09538	.09722	.09630	-.06458	-.03736	1163.31300	1164.73199	
1.400	.918	.14304	.14343	.14337	.14340	-.00563	-.00545	.00548	2.35601	.01036

IA310 (AEDC 16TE-783) PROBE CALIBRATION

(UCM048) ( 04 OCT 91 )

PARAMETRIC DATA

	MACH	RUN NO.	1555/ O	RN/L =	2 . 50	GRADIENT INTERVAL =	- 5 . 00 /	5 . 00		
ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPA1	DPCAL	DPB1	DPB2		
-7 . 016	-1 . 10216	-1 . 10388	-1 . 10194	-1 . 10291	-.01911	-.01920	-.01882	-.01901	1126 . 24800	1158 . 5140
-6 . 507	-1 . 02555	-1 . 02844	-1 . 02638	-1 . 02741	-.02050	-.02084	-.02016	-.02050	1129 . 71899	1158 . 2290
-6 . 008	-1 . 94871	-1 . 95159	-1 . 94600	-1 . 95059	-.02442	-.02282	-.02233	-.02258	1133 . 18800	1158 . 4830
-5 . 509	-1 . 87216	-1 . 87360	-1 . 87160	-1 . 87260	-.02062	-.02088	-.02046	-.02067	1135 . 95300	1158 . 5720
-5 . 011	-1 . 80163	-1 . 80375	-1 . 80131	-1 . 80253	-.02057	-.02066	-.02011	-.02039	1138 . 68700	1158 . 3320
-4 . 518	-1 . 72877	-1 . 73074	-1 . 72891	-1 . 72982	-.01608	-.01620	-.01572	-.01596	1142 . 87300	1158 . 5410
-4 . 015	-1 . 65198	-1 . 65456	-1 . 65251	-1 . 65353	-.01429	-.01381	-.01327	-.01354	1146 . 05400	1158 . 7790
-3 . 521	-1 . 57088	-1 . 57339	-1 . 57129	-1 . 57234	-.01418	-.01348	-.01299	-.01323	1147 . 77699	1158 . 3630
-3 . 024	-1 . 488858	-1 . 49096	-1 . 48881	-1 . 48989	-.01492	-.01238	-.01208	-.01223	1148 . 55000	1157 . 8780
-2 . 526	-1 . 41249	-1 . 41400	-1 . 41200	-1 . 41300	-.01557	-.01302	-.01286	-.01294	1149 . 68201	1158 . 2500
-2 . 038	-1 . 34092	-1 . 34208	-1 . 34000	-1 . 34104	-.01429	-.01218	-.01189	-.01203	1150 . 97200	1158 . 2820
-1 . 555	-1 . 27324	-1 . 27431	-1 . 27331	-1 . 27331	-.01302	-.01092	-.01051	-.01071	1154 . 45399	1158 . 6970
-1 . 082	-1 . 20190	-1 . 20274	-1 . 20077	-1 . 20175	-.01208	-.00988	-.00952	-.00970	1157 . 95799	1158 . 1360
-1 . 451	-1 . 13345	-1 . 13339	-1 . 13154	-1 . 13246	-.01213	-.00977	-.00941	-.00959	1158 . 55901	1158 . 1550
-1 . 450	-1 . 08030	-1 . 07923	-1 . 07949	-1 . 07836	-.02171	-.01938	-.01919	-.01928	1158 . 67300	1158 . 6860
-1 . 450	-1 . 00730	-1 . 00660	-1 . 00849	-1 . 00754	-.06872	-.06654	-.06640	-.06647	1159 . 45200	1158 . 4140
-1 . 451	.09350	.09331	.09495	.09413	-.08004	-.07774	-.07758	-.07766	1158 . 92200	1158 . 5220
GRADIENT	.15325	.15328	.00892	.00854	-.00860	-.00857	-.00860	-.00857	3 . 28706	.0002

RUN NO. 1639 O RN/L = 2.49 GRADIENT INTERVAL = -5 00/-5 00

	MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PPTF	PT2F
-1.470	-7.019	-1.12210	-1.12066	-1.12138	-1.02548	-0.02336	-0.02295	11111.70900	1148.73777		
-1.470	-6.504	-1.05110	-1.04898	-1.04825	-0.02385	-0.02181	-0.02139	1115.61600	1148.62554		
-1.469	-6.005	-9.77114	-9.7516	-9.7325	-0.02303	-0.02086	-0.02045	1120.18500	1148.82339		
-1.470	-5.507	-8.9588	-8.9440	-8.9267	-0.02463	-0.02258	-0.02181	-0.02220	1123.69299	1148.43322	
-1.470	-5.013	-8.1336	-8.1157	-8.11256	-0.02146	-0.02073	-0.02001	-0.02037	1125.35800	1148.49011	
-1.470	-4.510	-7.3920	-7.3702	-7.3526	-0.01755	-0.01693	-0.01628	-0.01660	1127.56500	1148.94444	
-1.470	-4.017	-6.5884	-6.5729	-6.5539	-0.01430	-0.01426	-0.01359	-0.01392	1129.64799	1148.71941	
-1.470	-3.518	-5.7819	-5.7729	-5.7534	-0.01371	-0.01339	-0.01279	-0.01309	1131.62000	1148.5096	
-1.484	-3.020	-4.9674	-4.9532	-4.9326	-0.01079	-0.01059	-0.01008	-0.01033	1132.99699	1166.7428	
-1.470	-2.533	-4.2009	-4.1866	-4.1662	-0.00884	-0.00869	-0.00829	-0.00849	1132.83900	1148.7615	
-1.470	-2.040	-3.4880	-3.4651	-3.47755	-0.00958	-0.00946	-0.00896	-0.00921	1134.16299	1148.9380	
-1.470	-1.551	-2.7890	-2.7877	-2.7765	-0.00834	-0.00860	-0.00795	-0.00827	1135.14700	1170.7213	
-1.470	-1.075	-2.0776	-2.0806	-2.0609	-0.00726	-0.00723	-0.00666	-0.00694	1135.61700	1148.2842	
-1.470	-0.639	-1.4219	-1.3984	-1.4087	-0.00926	-0.00911	-0.00870	-0.00890	1135.89999	1148.2386	
-1.470	-0.258	-0.8305	-0.8146	-0.7946	-0.00846	-0.00864	-0.00824	-0.00860	1136.50400	1149.1730	
-1.470	-0.287	-0.06663	-0.0549	-0.0767	-0.00558	-0.007216	-0.007125	-0.007146	1136.33600	1148.3420	
-1.470	-0.864	-0.9557	-0.94630	-0.9528	-0.007948	-0.007938	-0.007904	-0.007921	1136.40401	1148.6441	
GRADIENT	-1.5367	-1.5318	-1.5320	-1.5316	-0.00973	-0.00976	-0.00981	-0.00978	1.57045	1.57045	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM048) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1590/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00				BETA = -.500	PHI = 180.000	
				DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
MACH	ALPHA									
1.492	-7.017	-1.19272	-1.1.19015	-1.18866	-1.18940	-0.02049	-0.01858	-0.01811	-0.01835	1102.21001 1142.08722
6.508	-6.508	-1.1089	-1.1.10823	-1.10702	-1.10762	-0.02110	-0.02013	-0.01960	-0.01986	1104.56200 1142.14900
6.004	-6.004	-1.04170	-1.1.03929	-1.03812	-1.03870	-0.01934	-0.01836	-0.01802	-0.01819	1107.86501 1142.17850
1.492	-5.511	-1.96386	-1.1.96176	-1.96042	-1.96109	-0.01809	-0.01710	-0.01690	-0.01700	1110.40800 1141.98349
1.492	-5.012	-1.88659	-1.1.88381	-1.88282	-1.88332	-0.01477	-0.01370	-0.01342	-0.01356	1112.82600 1141.83359
1.492	-4.514	-1.80400	-1.1.80220	-1.80039	-1.80130	-0.01602	-0.01476	-0.01445	-0.01461	1115.17799 1141.90475
1.492	-4.016	-1.72344	-1.1.72140	-1.72012	-1.72076	-0.01385	-0.01264	-0.01234	-0.01249	1117.82201 1141.96373
1.493	-3.523	-1.64082	-1.1.63949	-1.63790	-1.63869	-0.01264	-0.01079	-0.01064	-0.01071	1119.73300 1142.12210
1.492	-3.024	-1.55642	-1.1.55458	-1.55450	-1.55550	-0.01374	-0.01123	-0.01118	-0.01120	1120.50999 1144.41478
1.492	-2.531	-1.47670	-1.1.47589	-1.47589	-1.47589	-0.01324	-0.01303	-0.01313	-0.01313	1120.57700 1142.15002
1.492	-2.039	-1.39848	-1.1.39580	-1.39410	-1.39495	-0.01450	-0.01242	-0.01253	-0.01248	1120.34200 1142.05060
1.492	-1.549	-1.31701	-1.1.31614	-1.31438	-1.31526	-0.01536	-0.01291	-0.01284	-0.01287	1119.26700 1142.10855
1.493	-1.078	-1.23951	-1.1.23909	-1.23743	-1.23826	-0.01638	-0.01397	-0.01400	-0.01398	1118.51801 1141.98401
1.492	-629	-1.16590	-1.1.16487	-1.16307	-1.16397	-0.01862	-0.01602	-0.01609	-0.01605	1118.68600 1141.82526
1.492	-244	-0.9532	-1.1.09457	-0.9312	-0.9384	-0.05114	-0.04852	-0.04834	-0.04843	1118.68600 1141.96103
1.492	.302	-0.0964	-1.1.00893	-0.0971	-0.09583	-0.08583	-0.08344	-0.08343	-0.08344	1117.24400 1141.62479
1.492	.872	-1.0863	-1.1.10766	-1.0955	-1.0861	-0.09239	-0.08983	-0.08991	-0.08987	1117.27000 1141.87592
	GRADIENT	-1.16841	-1.1.16786	-1.16789	-1.16788	-0.01287	-0.01264	-0.01270	-0.01267	-.1.16682 -.05627
RUN NO.	1606/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00						
MACH	ALPHA									
1.515	-7.022	-1.35859	-1.1.35301	-1.35218	-1.35259	-0.03085	-0.02963	-0.02894	-0.02929	1110.76500 1135.69574
1.515	-6.502	-1.27373	-1.1.26824	-1.26713	-1.26769	-0.02832	-0.02806	-0.02754	-0.02780	1113.50000 1135.34416
1.514	-6.004	-1.18427	-1.1.17914	-1.17796	-1.17855	-0.02509	-0.02490	-0.02438	-0.02464	1116.14101 1134.80786
1.515	-5.510	-1.08720	-1.1.08257	-1.08120	-1.08189	-0.01997	-0.02051	-0.01996	-0.02023	1118.76100 1133.86279
1.515	-5.012	-0.98867	-1.1.98513	-0.98393	-0.98453	-0.01473	-0.01554	-0.01495	-0.01524	1121.17999 1134.39682
1.515	-4.514	-0.89619	-1.1.89083	-0.89169	-0.89126	-0.01683	-0.01755	-0.01701	-0.01728	1123.32001 1135.15643
1.515	-4.016	-0.81687	-1.1.81220	-0.81075	-0.81148	-0.01856	-0.01914	-0.01858	-0.01886	1123.64200 1134.77046
1.514	-3.518	-0.72358	-1.1.72014	-0.71862	-0.71938	-0.02211	-0.02219	-0.02177	-0.02198	1125.50000 1134.82928
1.515	-3.019	-0.62181	-1.1.61926	-0.61761	-0.61843	-0.02253	-0.02263	-0.02229	-0.02246	1127.39500 1134.30136
1.514	-2.531	-0.51203	-1.1.51654	-0.51496	-0.51575	-0.02260	-0.02287	-0.02257	-0.02272	1129.16200 1134.46657
1.514	-2.038	-0.42154	-1.1.41849	-0.41679	-0.41764	-0.02233	-0.02274	-0.02240	-0.02257	1131.19099 1135.01221
1.514	-1.514	-0.32326	-1.1.32148	-0.31979	-0.32063	-0.02127	-0.02146	-0.02134	-0.02140	1131.10001 1134.82928
1.514	-1.072	-0.23584	-1.1.23492	-0.23342	-0.23417	-0.02642	-0.02610	-0.02582	-0.02596	1130.32700 1135.06067
1.514	-633	-0.16032	-1.1.15845	-0.15939	-0.15949	-0.03649	-0.03624	-0.03585	-0.03604	1131.03300 1135.52704
1.514	-245	-0.08240	-1.1.08203	-0.08113	-0.07519	-0.07527	-0.07504	-0.07515	-0.07515	1131.95000 1135.95326
1.514	-301	-0.02925	-0.02821	-0.03004	-0.02912	-0.11336	-0.11213	-0.11194	-0.11204	1132.07401 1136.98343
1.514	.871	-0.12374	-1.1.12318	-0.12405	-0.12442	-0.11328	-0.11321	-0.11324	-0.11324	1132.33299 1137.29218
	GRADIENT	-1.19182	-1.1.19182	-1.19188	-0.1712	-0.01684	-0.01692	-0.01688	-0.01688	1.76022 .44101

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 766  
(UCM048) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.541	-7.017	-1.27504	-1.27031	-1.26903	-1.26967	-1.04237	-.04125	-.04037	-.04081	1120.29601	1135.80357
1.541	-6.502	-1.14935	-1.14475	-1.14335	-1.14405	-.03646	-.03548	-.03480	-.03514	1121.33800	1135.50909
1.541	-6.009	-1.03667	-1.03316	-1.03161	-1.03238	-.03695	-.03675	-.03510	-.03542	1121.17300	1134.65921
1.541	-5.505	-1.92865	-1.92526	-1.92354	-1.92440	-.03621	-.03531	-.03454	-.03492	1120.26601	1132.89539
1.542	-5.012	-1.82208	-1.81932	-1.81765	-1.81848	-.03497	-.03374	-.03323	-.03348	1118.93600	1132.17421
1.541	-4.514	-1.71869	-1.71522	-1.71352	-1.71437	-.03762	-.03672	-.03598	-.03635	1119.38600	1132.95854
1.542	-4.016	-1.61070	-1.60746	-1.60562	-1.60654	-.03253	-.03230	-.03183	-.03206	1121.78200	1134.69133
1.541	-3.518	-1.50130	-1.49877	-1.49697	-1.49787	-.02810	-.02747	-.02713	-.02730	1124.56000	1135.77815
1.542	-3.020	-1.41274	-1.40963	-1.40777	-1.40870	-.02785	-.02663	-.02610	-.02636	1124.97701	1135.54196
1.541	-2.527	-1.33968	-1.33832	-1.33638	-1.33735	-.02962	-.02963	-.02926	-.02945	1123.42101	1135.20645
1.541	-2.034	-1.27770	-1.27645	-1.27454	-1.27550	-.03073	-.03069	-.03036	-.03053	1122.87399	1135.23106
1.542	-1.549	-1.21397	-1.21175	-1.20990	-1.21082	-.02776	-.02707	-.02659	-.02683	1122.64200	1134.59030
1.541	-1.077	-1.15253	-1.15032	-1.14849	-1.14941	-.02712	-.02554	-.02511	-.02533	1122.45100	1134.22153
1.541	-6.32	-1.10018	-1.09768	-1.09596	-1.09682	-.02438	-.02254	-.02224	-.02239	1122.64600	1134.13026
1.541	-2.45	-0.5232	-0.5085	-0.4902	-0.4993	-.04784	-.04589	-.04560	-.04575	1123.44200	1134.61264
1.542	.303	.02013	.01983	.02179	.02081	-.07156	-.06981	-.06944	-.06963	1123.97900	1136.29500
1.542	.879	.08707	.08671	.08837	.08754	-.07337	-.07543	-.07327	-.07332	1124.06000	1136.43472
GRADIENT		.14429	.14370	.14370	.14370	-.00632	-.00601	-.00607	-.00604	.35576	.24948

## PARAMETRIC DATA

	RUN NO.	1575/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	.65537	-.655372	-.65372	-.65446	.02837	.02814	.02859	.02836	1570.12900	1597.39999
.599	-.6.997	-.60684	-.60515	-.60600	.02945	.02931	.02971	.02951	1573.86700	1597.14999
.600	-.6.488	-.56221	-.55918	-.56076	.03105	.03205	.03245	.03225	1577.35699	1596.75000
.599	-.5.990	-.51689	-.51573	-.51423	.03383	.03503	.03537	.03520	1580.39999	1597.08000
.600	-.5.492	-.47231	-.47123	-.46974	.03382	.03483	.03514	.03498	1582.89600	1597.21001
.600	-.4.994	-.42659	-.42551	-.42382	.03360	.03470	.03505	.03488	1585.43500	1597.07001
.600	-.4.490	-.38099	-.37955	-.37791	.03421	.03516	.03544	.03530	1587.72501	1596.98000
.600	-.3.991	-.33351	-.33377	-.33209	.03342	.03439	.03462	.03451	1589.48199	1597.02000
.600	-.3.487	-.28645	-.28680	-.28518	.03260	.03379	.03404	.03392	1591.22501	1596.89000
.600	-.2.987	-.23942	-.23782	-.23682	.03281	.03379	.03404	.03393	1592.83701	1597.53000
.600	-.2.482	-.19263	-.19368	-.19212	.03456	.03532	.03572	.03552	1593.82700	1597.03999
.601	-.1.976	-.14566	-.14403	-.14485	.03687	.03762	.03779	.03770	1594.39799	1596.62000
.600	-.1.488	-.09829	-.09858	-.09681	.03523	.03638	.03656	.03647	1595.35800	1596.89000
.600	-.954	-.05231	-.05258	-.05092	.03706	.03795	.03824	.03809	1595.49001	1596.84000
.600	-.420	-.02841	-.02870	-.02701	.00473	-.00323	-.00317	-.00320	1595.54200	1596.52000
.600	-.075	-.01852	-.01674	-.01762	.01004	-.00838	-.00821	-.00829	1596.10100	1597.06000
.600	.472	-.06391	-.06324	-.06404	.01100	-.00900	-.00911	-.00905	1596.00999	1597.11000
.600	.984	.09015	.08980	.08982	.08981	-.00675	-.00664	-.00669	-.00666	2.11536
	GRADIENT									-.043332

	RUN NO.	1465/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	.78393	-.78440	-.78301	-.78371	.02983	.03062	.03111	.03086	1311.14600	1341.25999
-.7.003	-.72927	-.73005	-.72866	-.72935	.02794	.02905	.02948	.02926	1314.90800	1341.17999
-.6.492	-.67437	-.67557	-.67411	-.67484	.03073	.03066	.03098	.03082	1318.62000	1341.28000
-.5.986	-.61908	-.62025	-.61862	-.61944	.03477	.03413	.03447	.03430	1321.96100	1340.91000
-.5.491	-.56425	-.56618	-.56452	-.56535	.03546	.0354	.03555	.03535	1324.83600	1340.99001
-.4.991	-.51026	-.51115	-.50963	-.51039	.03547	.03497	.03540	.03518	1327.48300	1341.03999
-.4.490	-.45639	-.45545	-.45496	-.45568	.03466	.03464	.03490	.03477	1329.99800	1340.95000
.800	-.3.990	-.3.489	-.3.998	-.3.9915	.03398	.03386	.03411	.03398	1331.99001	1340.83000
.800	-.2.988	-.3.4364	-.34082	-.34082	.03385	.03353	.03385	.03369	1333.96500	1341.14000
.800	-.2.487	-.2.8793	-.34540	-.34466	.03547	.03484	.03525	.03504	1335.38499	1341.00000
.800	-.1.980	-.2.3342	-.2.33307	-.2.33307	.03570	.03554	.03579	.03566	1336.76900	1341.02000
.800	-.1.477	-.1.7801	-.1.7647	-.1.7724	.03725	.03687	.03714	.03701	1337.67200	1341.00999
.800	-.971	-.1.2323	-.1.2094	-.1.2188	.03640	.03671	.03656	.03656	1338.31700	1341.11000
.800	-.451	-.06950	-.0687	-.06868	.03892	.03923	.03945	.03934	1338.97501	1341.07001
.800	.083	-.01316	-.01163	-.01239	.00110	.00326	.00353	.00340	1339.18201	1340.97000
.801	.489	.02642	.02556	.02637	-.00301	-.00096	-.00095	-.00095	1339.55800	1341.12000
.800	1.006	.08222	.08060	.08210	.08135	-.00395	-.00188	-.00188	.00186	1339.45399
	GRADIENT					-.00550	-.00554	-.00552	-.00552	2.37538

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 768  
 (UCM049) ( 04 OCT 91 )

## PARAMETRIC DATA

		RUN NO.	1499/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPBF	PTTF	PT2F
ALPHA	-7.001	-.81499	-.81496	-.81594	.02807	.02853	.02915	.02884	1243.26601	1273.00999	
.900	-6.487	-.75585	-.75638	-.75751	.03016	.03052	.03102	.03077	1245.42599	1271.42000	
.900	-5.985	-.69910	-.70197	-.70086	.033373	.03432	.03481	.03457	1248.71800	1271.33000	
.900	-5.483	-.64190	-.64451	-.64353	.03600	.03532	.03578	.03555	1252.66800	1271.87000	
.900	-4.991	-.58556	-.58881	-.58677	.03738	.03779	.03744	.03722	1256.14700	1272.47000	
.900	-4.489	-.53023	-.53273	-.53061	.03792	.03728	.03772	.03750	1259.55600	1272.85001	
.900	-3.986	-.47291	-.47482	-.47279	.03819	.03764	.03822	.03793	1262.17200	1273.13000	
.900	-3.489	-.41430	-.41632	-.41434	.03721	.03680	.03707	.03694	1264.45300	1273.32001	
.900	-2.981	-.35567	-.35817	-.35618	.035717	.03680	.03666	.03699	1266.17599	1273.05000	
.900	-2.478	-.29853	-.30011	-.29802	.03732	.03689	.03725	.03707	1267.69299	1273.13000	
.900	-1.980	-.24255	-.24332	-.24230	.03770	.03735	.03768	.03751	1268.79800	1273.12000	
.900	-1.475	-.18449	-.18525	-.18401	.03916	.03885	.03908	.03891	1269.79201	1272.89999	
.900	-966	-.12796	-.12736	-.12648	.03871	.03803	.03839	.03821	1270.58099	1273.09999	
.900	-448	-.07274	-.07224	-.07140	.04071	.04020	.04054	.04037	1271.16200	1272.96001	
.900	.048	-.02010	-.01901	-.01733	.01817	.00029	.00193	.00181	1271.24200	1272.85001	
.900	.481	-.02622	-.02578	-.02754	.02666	.00447	.00241	.00233	1271.58400	1272.92999	
.900	.997	.08349	.08283	.08424	.08354	.00467	.00308	.00303	1271.54700	1272.95000	
	GRADIENT	.11203	.11261	.11256	.00657	.00620	.00625	.00622	.0061800	.00845	
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPBF	PTTF	PT2F
ALPHA	-7.006	-.82984	-.83588	-.83286	.01466	.01413	.01479	.01446	1174.78300	1204.88300	
1.100	-6.492	-.76970	-.76995	-.77297	.01820	.01702	.01690	.01832	1178.62199	1204.69600	
1.100	-5.995	-.71326	-.71358	-.71619	.01702	.01650	.01696	.01673	1182.32700	1204.69901	
1.100	-5.492	-.65476	-.65523	-.65814	.02102	.01946	.01985	.01965	1185.61501	1204.72400	
1.100	-4.992	-.59821	-.59867	-.60147	.02209	.02078	.02138	.02108	1188.61400	1204.39500	
1.100	-4.488	-.54029	-.54115	-.54679	.02187	.02056	.02106	.02081	1191.37801	1204.78200	
1.100	-3.995	-.48083	-.48120	-.48415	.02355	.02213	.02263	.02238	1193.69200	1204.68900	
1.100	-3.496	-.42130	-.42183	-.42476	.02403	.02286	.02315	.02300	1195.88200	1204.66701	
1.100	-2.997	-.36208	-.36123	-.36409	.02327	.02187	.02235	.02211	1197.76300	1204.78600	
1.100	-2.488	-.30261	-.30315	-.30598	.02465	.02324	.02379	.02351	1199.33099	1204.59599	
1.100	-1.996	-.24587	-.24637	-.24919	.02497	.02357	.02405	.02381	1200.46001	1204.78799	
1.100	-1.487	-.18924	-.18895	-.19465	.02631	.02516	.02564	.02540	1201.65500	1204.82001	
1.100	-0.989	-.13374	-.13283	-.13572	.02577	.02483	.02515	.02499	1202.28000	1204.72301	
1.100	-0.486	-.07907	-.07840	-.08121	.02829	.02697	.02739	.02718	1202.94200	1204.82899	
1.100	.001	-.02574	-.02470	-.03041	.02755	.02367	.02273	.02281	1203.14900	1204.70900	
1.100	.513	.03142	.03012	.02461	.02737	.01374	.01301	.01307	1203.37500	1204.45399	
1.100	1.014	.08798	.08682	.08096	.08389	.01390	.01276	.01289	1203.67700	1204.68300	
	GRADIENT	.11412	.11416	.11417	.00077	-.00070	-.00075	-.00072	2.42337	.00823	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 769  
 (UCM049) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1522/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	.90450	-.90583	-.90373	-.90478	.02846	.02926	.02967	.02947	1152.03500	1182.32100
1.250	-7.001	-	-	-	.83983	.03035	.03026	.03054	1156.06500	1181.80400
-6.485	-84064	-.84097	-.83869	-.83983	.03464	.03454	.03480	.03505	1160.49899	1182.97900
1.250	-5.987	-77834	-.77876	-.77758	.03240	.03238	.03288	.03263	1163.72301	1182.52299
-5.488	-7.1153	-.71120	-.70969	-.71120	.03649	.03649	.03682	.03665	1165.57100	1182.41200
1.250	-5.488	-64671	-.64878	-.64756	.03534	.03534	.03549	.03600	1168.22400	1182.67900
-4.486	-58439	-.58673	-.58433	-.58553	.03875	.03885	.03934	.03909	1170.92999	1182.53200
1.250	-3.988	-52161	-.52304	-.52065	.03694	.03700	.03735	.03718	1173.03700	1182.61400
-3.489	-45664	-.45745	-.45533	-.45639	.03720	.03733	.03752	.03752	1175.64200	1182.77100
1.250	-2.987	-39273	-.39379	-.39140	.03957	.03772	.03697	.03720	1177.15401	1182.68900
-2.483	-32934	-.32999	-.32892	-.32892	.03558	.03700	.03740	.03740	1178.23900	1182.21201
1.250	-1.978	-26815	-.26884	-.26779	.03670	.03792	.03824	.03808	1178.68800	1181.78101
-1.478	-20806	-.20766	-.20664	-.20664	.03902	.04026	.04052	.04039	1180.35800	1182.91299
1.250	-980	-14629	-.14504	-.14291	.04048	.04108	.04136	.04122	1180.43500	1182.33200
-4.62	-8274	-.08146	-.07950	-.07950	.02681	.02561	.02706	.02694	1180.07600	1182.64400
1.249	-102	-0.1429	-.01263	-.01158	.00360	.00525	.00626	.00576	1181.18700	1183.15900
-502	.03373	-.03353	-.03552	-.03452	.00494	.00581	.00581	.00400	1181.28799	1182.51801
1.250	1.009	.09638	.09642	.09732	.00246	.00437	.00402	.00397	1182.50403	.02168
	GRADIENT	12385	12437	.12428						
	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00						
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.03508	-.1.03814	-.1.03595	-.1.03705	.04430	.04330	.04532	.05799	1133.15800	1164.32600
-7.005	-96248	-.96569	-.96356	-.96462	.04558	.04558	.04642	.05912	1137.38901	1164.33900
-6.490	-89289	-.89376	-.89207	-.89292	.04257	.04257	.04358	.05616	1140.57001	1163.93201
-5.987	-82002	-.82082	-.81851	-.81967	.04430	.04430	.04463	.05734	1143.65100	1164.27600
-5.487	-75047	-.75193	-.74969	-.75081	.04682	.04682	.04580	.05848	1147.45599	1164.33600
-4.989	-67933	-.68082	-.67862	-.67972	.04788	.04788	.04726	.06003	1149.55599	1163.85699
-4.485	-60608	-.60786	-.60552	-.60669	.04960	.04960	.048715	.06146	1152.93500	1164.55600
-3.993	-52884	-.53045	-.52810	-.52928	.04933	.04933	.04879	.06145	1155.18900	1164.32200
-3.489	-45267	-.45383	-.45154	-.45269	.04760	.04760	.04711	.05986	1156.62000	1164.62500
-2.987	-38010	-.38067	-.37848	-.37957	.04679	.04679	.04592	.05867	1157.57300	1163.95799
-2.484	-31068	-.31002	-.31205	-.31104	.04588	.04588	.04519	.05804	1158.84000	1164.48900
-1.981	-24237	-.24347	-.24134	-.24241	.04611	.04611	.04571	.05852	1160.74800	1163.90800
-1.483	-17159	-.16863	-.17079	-.16971	.04733	.04733	.04685	.05967	1161.69901	1164.10100
-1.399	-979	-.10034	-.09913	-.09705	.04909	.04909	.04844	.06123	1162.82100	1164.55299
-1.400	-468	-.02181	-.02058	-.01962	.03458	.03458	.03363	.04655	1162.64301	1164.40500
.091	.03512	-.03434	-.03640	-.03537	.01067	.03596	.01014	.02305	1163.38499	1164.21300
1.400	1.006	.10643	.10610	.10696	.00775	.03300	.00730	.02015	1162.87500	1164.23900
	GRADIENT	14276	14314	.14306	-.00526	-.00515	-.00522	-.00518	2.57106	.00216

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM049) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1556/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	.000	PHI =	180.000	
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F		
1.450	-6.956	-1.08989	-1.09148	-1.08969	.05707	.05485	.05570	.05527	1126.83299	1158.25000		
1.450	-6.487	-1.01991	-1.02289	-1.02093	.06154	.06240	.06197	1129.95700	1158.27400			
1.450	-5.983	-1.94310	-1.94586	-1.94380	.06179	.05997	.06059	.06028	1133.23900	1158.74100		
1.450	-5.484	-1.86626	-1.86776	-1.86581	.05865	.05703	.05768	.05736	1135.01000	1158.39000		
1.450	-4.980	-1.79636	-1.79881	-1.79654	.079767	.06100	.05918	.05986	1139.47400	1158.47800		
1.450	-4.481	-1.72302	-1.72507	-1.72296	.072402	.06557	.06386	.06459	1142.91400	1158.45399		
1.451	-3.982	-1.64353	-1.64597	-1.64382	.064490	.06404	.06399	.06457	.06428	1145.80200	1158.30200	
1.450	-3.483	-1.56387	-1.56637	-1.56416	.056527	.06359	.06348	.06403	.06376	1147.62601	1158.05299	
1.450	-2.979	-1.48257	-1.48495	-1.48285	.048390	.06396	.06419	.06464	.06441	1148.92599	1158.67599	
1.450	-2.475	-1.40642	-1.40687	-1.40487	.040587	.06120	.06158	.06220	.06189	1149.77901	1158.46500	
1.449	-1.969	-1.32269	-1.33201	-1.33295	.03233	.06275	.06330	.06303	.06303	1150.94501	1157.95799	
1.450	-1.466	-1.26202	-1.26123	-1.26219	.06431	.06490	.06535	.06512	.06512	1155.27800	1159.12100	
1.450	-954	-1.18460	-1.18554	-1.18321	.18437	.066606	.06662	.06718	.06690	.06690	1158.04201	1157.92200
1.449	-423	-1.10188	-1.10087	-1.09904	.09996	.06459	.06558	.06606	.06582	.06582	1158.33400	1158.20300
1.450	-081	-0.5387	-0.52778	-0.51113	.05196	.00379	.00507	.00598	.00553	.00553	1156.49001	1158.01100
1.450	.477	.02813	.02746	.02919	.02832	.00219	.00009	.00015	.00003	.00003	1158.80800	1158.09500
1.451	.445	.02453	.02391	.02559	.02475	.003330	.00135	.00119	.00127	.00127	1159.33501	1158.12000
1.450	.987	.10957	.10927	.11009	.11009	.00522	.00279	.00248	.00263	.00263	1158.90199	1158.20399
GRADIENT												
	RUN NO.	1640/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00					
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F		
1.471	-6.954	-1.11425	-1.11111	-1.10971	-1.11041	.05925	.05955	.06057	.06006	.06112	1148.59149	
1.485	-6.486	-1.04570	-1.04365	-1.04200	-1.04283	.05911	.05938	.06024	.05981	.06115	1166.79568	
1.484	-5.987	-9.7140	-9.6933	-9.6776	-9.6855	.06292	.06302	.06393	.06347	.06119	1167.03316	
1.471	-5.489	-8.9091	-8.8877	-8.8741	-8.8809	.05997	.06011	.06104	.06057	.06123	1123.05800	
1.485	-4.985	-8.1074	-8.0858	-8.0680	-8.0769	.06256	.06229	.06315	.06272	.06125	1125.06600	
1.470	-4.486	-7.33037	-7.3127	-7.2956	-7.3042	.06354	.06329	.06414	.06371	.06127	1127.73700	
1.484	-3.982	-6.5279	-6.5142	-6.4941	-6.5041	.06625	.06554	.06640	.06597	.06129	1167.10320	
1.470	-3.489	-5.7333	-5.7218	-5.7115	-5.7218	.06882	.06682	.06748	.06715	.06131	1148.63251	
1.471	-2.980	-4.9031	-4.8889	-4.8683	-4.8786	.06601	.06408	.06479	.06444	.06133	1133.29300	
1.470	-2.476	-4.1305	-4.1158	-4.1054	-4.1054	.06739	.06554	.06614	.06584	.0633	1149.17694	
1.470	-1.976	-3.3946	-3.3732	-3.33830	-3.33830	.06978	.06837	.06903	.06870	.06134	1148.88319	
1.485	-1.469	-2.6662	-2.6456	-2.6648	-2.6648	.07114	.06963	.07013	.06988	.06134	1166.86577	
1.484	-958	-1.9078	-1.8902	-1.9010	-1.9006	.07337	.07146	.07204	.07175	.06135	1135.91299	
1.470	-438	-1.1156	-1.1038	-1.1037	-1.1037	.07349	.07208	.07278	.07243	.06135	1148.78467	
1.470	-080	-0.4289	-0.4209	-0.4115	-0.4115	.00526	.00488	.00557	.00522	.0136	1136.27600	
1.470	.487	.03669	.03795	.03694	.00324	.00299	.00267	.00283	.00283	.0136	1149.20483	
1.470	.997	.11372	.11252	.11464	.11358	.00474	.00427	.00401	.00414	.0136	1148.33676	
GRADIENT												
	RUN NO.	15418	RN/L =	1.5371	.15372	.01032	.01021	.01029	.01025	.01025	.01025	

## PARAMETRIC DATA

	RUN NO.	1591/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.492	-6.954	-1.18113	-1.17831	-1.17702	-1.17767	.07031	.06994	.07056	.07025	1104.57300
1.492	-6.486	-1.10742	-1.10478	-1.10343	-1.10410	.06998	.06952	.06998	.06975	1105.60100
1.492	-5.988	-1.03734	-1.03501	-1.03372	-1.03436	.07234	.07146	.07191	.07169	1108.51401
1.492	-5.484	-9.6039	-9.5829	-9.5685	-9.5757	.07206	.07160	.07200	.07180	1111.23500
1.492	-4.991	-8.8174	-8.7910	-8.7761	-8.7835	.07416	.07387	.07428	.07408	1113.75400
1.492	-4.487	-8.0104	-7.9912	-7.9736	-7.9824	.07456	.07447	.07504	.07475	1116.77800
1.493	-3.989	-7.1763	-7.1568	-7.1435	-7.1502	.07293	.07261	.07299	.07280	1119.05200
1.493	-3.484	-6.3322	-6.3202	-6.3040	-6.3121	.07709	.07705	.07734	.07720	1120.63100
1.493	-2.986	-5.51116	-5.4877	-5.4710	-5.4794	.07639	.07615	.07652	.07633	1121.13100
1.492	-2.477	-4.7109	-4.6837	-4.6679	-4.6758	.07226	.07216	.07255	.07295	1121.88400
1.493	-1.978	-3.88840	-3.85889	-3.8428	-3.8508	.07246	.07288	.07312	.07300	1121.77299
1.492	-1.472	-3.30333	-3.30285	-3.30101	-3.30193	.07215	.07292	.07312	.07302	1120.59801
1.493	-9.64	-2.2100	-2.2059	-2.1874	-2.1966	.07511	.07597	.07598	.07598	1119.95900
1.492	-4.443	-1.3488	-1.3378	-1.3215	-1.3297	.07619	.07699	.07717	.07708	1120.68800
1.492	-0.090	-0.05447	-0.05356	-0.05190	-0.05273	.00301	.00512	.00536	.00524	1121.99200
1.492	.492	.04452	.04347	.04527	.04437	.00435	.00215	.00222	.00219	1120.26900
1.493	.995	.99701	.9918	.12809	.12974	.012892	.00607	.00370	.00373	1118.83400
	GRADIENT	.16851	.16798	.16802	.16800	.01266	.01219	.01228	.01224	.62136 .00738
	RUN NO.	1607/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.515	-7.006	-1.34963	-1.34561	-1.34467	-1.34514	.07502	.07536	.07464	.07500	1111.55800
1.514	-6.491	-1.26647	-1.26061	-1.25951	-1.26006	.07596	.07447	.07519	.07483	1114.39400
1.515	-5.987	-1.17973	-1.17458	-1.17335	-1.17397	.07775	.07657	.07725	.07691	1117.04800
1.515	-5.483	-1.08281	-1.07782	-1.07648	-1.07715	.08122	.07986	.08061	.08024	1119.71201
1.515	-4.990	-9.8365	-9.8044	-9.7882	-9.7963	.08205	.08118	.08191	.08154	1121.27100
1.514	-4.492	-8.91179	-8.8695	-8.8607	-8.8651	.08305	.08103	.08169	.08136	1121.07899
1.515	-3.983	-8.1104	-8.0655	-8.0507	-8.0581	.08432	.08220	.08277	.08248	1124.07893
1.515	-3.484	-7.1997	-7.1640	-7.1493	-7.1567	.08095	.08262	.07924	.07893	1127.10300
1.514	-2.986	-6.1369	-6.1111	-6.0966	-6.1039	.07536	.07321	.07385	.07353	1128.68100
1.515	-2.483	-5.1653	-5.1333	-5.1192	-5.1263	.07603	.07367	.07437	.07402	1131.41200
1.514	-1.978	-4.1425	-4.1097	-4.1017	-4.1017	.07274	.07137	.07176	.07157	1132.34300
1.514	-1.471	-3.1390	-3.1194	-3.1032	-3.1113	.07135	.07042	.07084	.07063	1130.66299
1.515	-96.2	-2.2285	-2.2113	-2.2192	-2.2192	.07348	.07239	.07278	.07258	1129.91400
1.514	-44.8	-1.2941	-1.2864	-1.2687	-1.2776	.07072	.06961	.06998	.06979	1130.85500
1.515	-0.95	-0.1623	-0.1576	-0.1413	-0.1495	.02351	.02380	.02347	.02364	1131.82300
1.515	.493	.07375	.07265	.07446	.07356	.03166	.03191	.03174	.03182	1132.82100
1.515	1.001	.15676	.15614	.15819	.15716	.03230	.03241	.03228	.03235	1132.72000
	GRADIENT	.19424	.19332	.19342	.19337	.01889	.01859	.01868	.01863	.89423 .45513



## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 773

(UCM050) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1576/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000	PTTF
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	PT2F
.599	-6.980	-.65320	-.65325	-.65180	-.65253	.07556	.07570	.07553	1569.81400	1597.00000	
.600	-6.468	-.60530	-.60366	-.60448	-.60737	.07754	.07790	.07772	1573.70700	1597.07001	
.600	-5.967	-.55882	-.55784	-.55642	-.55713	.07781	.07807	.07829	1577.24400	1596.91000	
.600	-5.464	-.51265	-.51156	-.50977	-.51066	.07773	.07875	.07919	1580.21001	1596.96001	
.600	-4.966	-.46855	-.46719	-.46637	-.46637	.07793	.07913	.07947	1582.99400	1596.46001	
.600	-4.462	-.42259	-.42148	-.42064	-.42064	.07726	.07844	.07865	1585.55600	1597.02000	
.600	-3.951	-.37664	-.37520	-.37355	-.37438	.07807	.07922	.07956	1587.53500	1597.14000	
.600	-3.448	-.33034	-.33060	-.32893	-.32976	.07723	.07831	.07863	1589.53700	1596.66000	
.601	-2.937	-.28163	-.28190	-.28020	-.28105	.07656	.07738	.07764	1591.32700	1597.05000	
.600	-2.431	-.23422	-.23518	-.23435	-.23435	.07816	.07937	.07943	1592.74699	1596.87000	
.600	-1.912	-.18596	-.18730	-.18567	-.18648	.07809	.07949	.07943	1593.65100	1595.92999	
.601	-1.392	-.13943	-.13976	-.13818	-.13897	.07703	.07772	.07788	1594.59100	1596.74001	
.601	-855	-.08929	-.08989	-.08822	-.08906	.07529	.07566	.07575	1595.18201	1597.59000	
.600	-.299	-.04272	-.04295	-.04137	-.04216	.06726	.06782	.06771	1595.54700	1596.47000	
.600	.254	.00390	.00203	.00363	.00283	.05016	.05131	.05134	1595.75900	1596.47000	
.600	.670	.03747	.03598	.03748	.03673	.03707	.03810	.03817	1596.01401	1597.20000	
.600	1.102	.07506	.07442	.07641	.07542	.03506	.03620	.03627	1596.16800	1597.23000	
.600	GRADIENT	.09010	.08969	.08969	.08969	-.00643	-.00648	-.00652	-.00650	2.05060	
RUN NO.	1466/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00						
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	PTTF
.800	-6.986	-.78109	-.78198	-.78062	-.78130	.08660	.08762	.08805	.08783	1310.84801	1341.41000
.800	-6.478	-.72554	-.72638	-.72498	-.72568	.08806	.08877	.08913	.08895	1314.75101	1341.32001
.800	-5.974	-.67032	-.67144	-.66995	-.67069	.08947	.08967	.09005	.08986	1318.39799	1341.37000
.800	-5.470	-.61501	-.61613	-.61469	-.61541	.08917	.08954	.08990	.08972	1321.81100	1340.97000
.800	-4.971	-.56015	-.56183	-.56035	-.56109	.09043	.09012	.09055	.09033	1324.87100	1341.07001
.800	-4.471	-.50572	-.50704	-.50546	-.50625	.08980	.08976	.09031	.09004	1327.52000	1341.14000
.800	-3.969	-.45158	-.45259	-.45105	-.45182	.08963	.08925	.08962	.08944	1330.03600	1341.09000
.800	-3.461	-.39539	-.39628	-.39475	-.39551	.08788	.08769	.08805	.08787	1332.14500	1340.96001
.800	-2.954	-.33968	-.34048	-.33901	-.33974	.08766	.08713	.08736	.08725	1333.98900	1341.00999
.800	-2.449	-.28281	-.28386	-.28223	-.28304	.08736	.08713	.08745	.08729	1335.51601	1341.03000
.800	-1.938	-.22856	-.22907	-.22741	-.22824	.08744	.08713	.08732	.08723	1336.62100	1340.98000
.800	-1.424	-.17201	-.17177	-.17036	-.17107	.08573	.08587	.08613	.08600	1337.81300	1341.05000
.800	-1.900	-.11411	-.11381	-.11222	-.11302	.08567	.08596	.08628	.08612	1338.46800	1340.85001
.800	-362	-.05881	-.05871	-.05705	-.05788	.08125	.08150	.08172	.08161	1339.07899	1340.95000
.800	178	-.00285	-.00237	-.00250	-.00244	.06843	.06897	.06921	.06909	1339.29700	1340.95000
.800	.628	.04276	.04172	.04338	.04255	.05516	.05565	.05567	.05567	1339.52400	1340.95000
.800	1.084	.09151	.09002	.09163	.09082	.05321	.05301	.05302	.05302	1339.70900	1340.98000
.800	GRADIENT	.10792	.10808	.10802	.10805	-.00545	-.00545	-.00545	-.00537	2.34903	-.02574

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM050) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1500/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.900	-6.987	-8.1124	-.81310	-.81115	-.81212	.09076	.09116	.09188	.09152	1242.94299
.900	-6.472	-7.53339	-.75589	-.75394	-.75492	.09023	.09079	.09132	.09105	1246.91299
.900	-5.967	-6.99599	-.69902	-.69685	-.69793	.08971	.08951	.09007	.08979	1250.99600
.900	-5.466	-6.3790	-.64063	-.63857	-.63960	.09297	.09295	.09360	.09328	1273.22000
.900	-4.970	-5.8150	-.58487	-.58272	-.58380	.09202	.09163	.09216	.09189	1256.84801
.900	-4.463	-5.2655	-.52894	-.52690	-.52792	.09298	.09264	.09302	.09283	1259.39700
.900	-3.959	-4.6882	-.47090	-.46891	-.46990	.09319	.09249	.09306	.09278	1261.83501
.900	-3.459	-4.1043	-.41224	-.41014	-.41119	.09210	.09176	.09218	.09197	1264.19600
.900	-2.950	-3.5282	-.35427	-.35217	-.35322	.09156	.09121	.09179	.09150	1266.16499
.900	-2.443	-2.9438	-.29594	-.29385	-.29489	.09170	.09099	.09145	.09122	1268.85800
.900	-1.934	-2.3751	-.23833	-.23624	-.23729	.09101	.09116	.09166	.09141	1270.55701
.900	-1.413	-1.7910	-.17969	-.17734	-.17852	.08968	.08979	.09018	.08998	1271.35001
.900	-887	-1.1928	-.11892	-.11696	-.11794	.08964	.08962	.09003	.08982	1271.60400
.900	-348	-0.6257	-.06208	-.06031	-.06120	.08421	.08436	.08484	.08460	1272.29601
.900	-191	-0.04440	-.00333	-.00333	-.00333	.07034	.07075	.07099	.07087	1272.10500
.900	.635	.04361	.04304	.04474	.04389	.05615	.05655	.05669	.05662	1271.93300
.900	.081	.09242	.09159	.09319	.09239	.05556	.05526	.05555	.05541	1272.14500
	GRADIENT	.11174	.11226	.11211	.11218	-.00562	-.00550	-.00554	-.00552	.2.51117
	RUN NO.	1485/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				.12975
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.100	-7.003	-8.2583	-.82600	-.83193	-.82897	.07365	.07324	.07394	.07359	1174.78101
1.100	-6.483	-7.6748	-.76765	-.77331	-.77048	.07620	.07582	.07649	.07615	1178.57600
1.100	-5.988	-7.0992	-.71052	-.71567	-.71310	.07440	.07407	.07470	.07439	1182.24800
1.100	-5.481	-6.5128	-.65195	-.65769	-.65482	.07724	.07620	.07674	.07647	1185.69000
1.100	-4.986	-5.9486	-.59535	-.60094	-.59814	.07800	.07655	.07715	.07685	1188.60201
1.100	-4.483	-5.3695	-.53792	-.54372	-.54082	.07837	.07708	.07763	.07735	1191.32899
1.100	-3.989	-4.7839	-.47884	-.48455	-.48170	.07903	.07768	.07814	.07791	1193.73700
1.100	-3.481	-4.1889	-.41945	-.42229	-.42229	.08001	.07852	.07892	.07872	1195.86400
1.100	-2.976	-3.5959	-.35900	-.36492	-.36196	.08024	.07900	.07959	.07929	1197.86501
1.100	-2.479	-3.0109	-.30168	-.30731	-.30449	.07929	.07845	.07907	.07876	1199.33299
1.100	-1.976	-2.4371	-.24438	-.25014	-.24726	.07953	.07832	.07881	.07856	1200.52800
1.100	-1.464	-1.8755	-.18731	-.19284	-.19007	.07861	.07719	.07767	.07743	1201.60300
1.100	-968	-1.3014	-.12961	-.13532	-.13247	.07931	.07807	.07845	.07826	1202.29800
1.100	-460	-0.7579	-.07497	-.08060	-.07779	.07768	.07728	.07765	.07746	1202.88901
1.100	.051	.01962	-.01909	-.02470	-.02190	.07738	.07624	.07666	.07645	1203.19200
1.100	.536	.03664	-.02931	-.03222	-.02401	.07257	.07293	.07275	.07255	1203.54700
1.100	1.029	.08849	-.08137	-.08426	-.07329	.07184	.07211	.07198	.07198	1203.60100
	GRADIENT	.11379	.11380	.11380	.11380	-.00069	-.00073	-.00071	-.00071	.00994

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM050) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1523/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	- .991	-.90166	-.89941	-.90053	.09247	.09309	.09364	.09336	1181.97301	
	- 6.250	-.90044	-.83841	-.83597	.09618	.09644	.09702	.09673	1182.95500	
	- 6.474	-.83803	-.77555	-.77326	.09744	.09804	.09755	.09785	1182.66200	
	- 5.978	-.77497	-.70915	-.70682	.09799	.09750	.09804	.09779	1182.25400	
	- 5.471	-.70817	-.64231	-.64223	.09437	.09597	.09594	.09614	1182.35699	
	- 4.973	-.64231	-.58356	-.58237	.09788	.09786	.09838	.09812	1182.44501	
	- 4.471	-.58138	-.51883	-.51765	.09990	.09940	.09980	.09960	1182.37900	
	- 3.966	-.51725	-.45341	-.45193	.09813	.09851	.09909	.09885	1182.05701	
	- 3.462	-.45341	-.38840	-.38914	.09643	.09704	.09748	.09726	1182.46201	
	- 2.958	-.38840	-.32613	-.32389	.09250	.09676	.09731	.09750	1182.59300	
	- 2.451	-.32613	-.26495	-.26273	.09558	.09595	.09621	.09608	1178.08400	
	- 1.948	-.26379	-.20211	-.19991	.09563	.09609	.09649	.09629	1179.33600	
	- 1.431	-.20231	-.13895	-.13765	.09529	.09583	.09610	.09596	1180.15700	
	- 9.16	-.13895	-.07495	-.07365	.09721	.09072	.09224	.09216	1182.42700	
	- .390	-.07495	-.00834	-.00834	.09727	.00781	.08204	.08210	1180.77499	
	1.45	-.00995	-.04759	-.04709	.04918	.04813	.06911	.07060	1181.22099	
	1.250	-.609	-.10389	-.10357	.10546	.10452	.06724	.06892	1181.01900	
	1.250	1.071	-.12392	-.12392	.12386	-.00454	-.00424	-.00430	-.00109	
	GRADIENT	1.2343								

	RUN NO.	1539/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	- 1.03212	-.03528	- 1.03313	- 1.03421	.11402	.11498	.11401	.12750	1133.02901	1163.84900
	- 6.992	-.95785	-.96108	-.95988	.11766	.11394	.11632	.13127	1137.06200	1164.50999
	- 6.480	-.88780	-.88862	-.88778	.11636	.14167	.11632	.12899	1140.58900	1163.92000
	- 5.979	-.81580	-.81666	-.81558	.11543	.14089	.11567	.12828	1143.46800	1163.91000
	- 5.471	-.74679	-.74830	-.74605	.14717	.11489	.14063	.12789	1147.19600	1164.50000
	- 4.975	-.67488	-.67668	-.67421	.16754	.16711	.14237	.12969	1150.18600	1164.08200
	- 4.472	-.60301	-.60073	-.60187	.11848	.11740	.13015	.13015	1152.86301	1164.32100
	- 3.973	-.52152	-.52679	-.52540	.11786	.14264	.11722	.12993	1155.14999	1164.25700
	- 3.464	-.45024	-.44807	-.44915	.11641	.14129	.11600	.12864	1156.32600	1164.43100
	- 2.966	-.37632	-.37691	-.37575	.11313	.13785	.11236	.12510	1157.75999	1164.47900
	- 2.460	-.30615	-.30731	-.30514	.13762	.11319	.13762	.12488	1158.57001	1163.87399
	- 1.949	-.23644	-.23774	-.23664	.11424	.13902	.11333	.12617	1160.98801	1164.63100
	- 1.439	-.16424	-.16365	-.16171	.16268	.11188	.13758	.12483	1161.93900	1164.12000
	- 1.400	-.09008	-.09107	-.08823	.08915	.10685	.13283	.10712	11998.1161.96600	1164.27100
	- 3.99	-.011745	-.01653	-.01450	.01552	.09818	.12395	.09832	11113.1162.35899	1163.90800
	- 1.30	-.04886	-.04832	-.05032	.04932	.08586	.11080	.08512	.09796.1163.11200	1164.10201
	.600	1.059	1.1297	1.11238	.11428	.08338	.10840	.08268	.09554.1162.93401	1164.25600
	1.400	GRADIENT	1.4223	1.4258	.14250	-.00506	-.00506	-.00503	2.51358	-.03772

## PARAMETRIC DATA

	RUN NO.	1557/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-6.981	-1.09456	-1.09670	-1.09471	-1.09571	.13676	.13623	.13697	.98300	.1158 .31200
	-6.463	-1.01751	-1.02054	-1.01840	-1.01947	.13847	.13703	.13775	.57800	.1158 .32600
	-5.961	-94029	-94352	-94145	-94249	.13263	.13461	.13342	.89000	.1158 .97301
	-5.458	-86235	-86415	-86217	-86316	.13739	.13555	.13620	.48000	.1158 .01900
	-4.955	-79199	-79445	-79250	-79348	.13555	.13539	.13596	.33501	.1157 .79900
	-4.450	-71859	-72098	-71872	-71985	.14099	.14050	.14117	.39999	.1158 .46500
	-3.950	-64031	-64324	-64108	-64216	.13968	.13926	.14001	.52400	.1158 .71899
	-3.448	-56159	-56409	-56198	-56303	.13937	.13910	.13968	.96600	.1158 .57201
	-2.937	-47805	-48035	-47816	-47926	.13719	.13667	.13729	.49001	.1157 .81400
	-2.426	-40187	-40259	-40039	-40149	.13511	.13491	.13544	.65601	.1158 .61501
	-1.907	-32589	-32707	-32507	-32607	.13459	.13449	.13518	.17000	.1158 .42599
	-1.390	-25272	-25410	-25195	-25303	.13636	.13694	.13736	.00200	.1158 .58200
	-856	-17310	-17343	-17146	-17245	.13356	.13402	.13458	.28300	.1158 .03799
	-307	-08980	-08893	-08727	-08810	.12477	.12525	.12579	.98599	.1158 .47900
	-240	-00756	-00696	-00687	-00691	.10048	.10088	.10150	.90900	.1158 .10201
	1.449	.659	.05798	.05736	.05914	.05825	.08120	.08236	.04100	.1158 .78500
	1.450	1.098	12521	12475	12640	.12558	.07726	.07831	.66400	.1158 .11700
	1.449	GRADIENT	15111	15163	15147	.15155	-.00914	-.00890	-.00894	-.01229
	RUN NO.	1642/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-6.982	-1.12214	-1.11807	-1.11703	-1.11755	.13727	.13684	.13759	.1111 .83299	.1149 .02139
	-6.469	-1.04303	-1.03994	-1.03878	-1.03936	.14181	.14144	.14203	.1114 .92999	.1148 .15781
	-5.968	-96983	-96728	-96616	-96672	.13789	.13737	.13818	.04201	.1149 .37340
	-5.465	-88925	-88637	-88583	-88610	.13976	.13885	.13953	.72000	.1148 .95085
	-4.967	-80880	-80578	-80464	-80521	.13789	.13651	.13714	.26199	.1148 .61964
	-4.458	-73107	-72835	-72725	-72780	.13849	.13750	.13809	.86900	.1149 .15532
	-3.957	-65135	-64930	-64804	-64867	.13987	.13878	.13925	.72600	.1148 .83565
	-3.451	-57037	-56853	-56714	-56783	.13903	.13968	.13947	.1132 .15000	.1149 .20787
	-1.470	2.941	48811	48616	48467	.13851	.13775	.13820	.00900	.1149 .17194
	-2.436	-40776	-40561	-40410	-40486	.13920	.13792	.13828	.04401	.1148 .57065
	-1.920	-33362	-33276	-33134	-33205	.14231	.13989	.14041	.46500	.1149 .05182
	-1.470	-1.399	-25819	-25762	-25619	.14273	.14029	.14052	.10400	.1148 .66896
	-1.470	-1.872	-17762	-17669	-17524	.14180	.13971	.14009	.07401	.1148 .88730
	-1.470	-328	-09223	-09117	-09170	.13467	.13266	.13307	.78000	.1149 .31381
	-1.470	-219	-00587	-00467	-00487	.11271	.11064	.11085	.73199	.1148 .96867
	-1.470	.650	.06119	.06076	.06235	.06156	.08727	.08536	.97800	.1149 .11609
	1.470	1.096	12777	12721	12872	.12797	.08027	.07844	.16001	.1148 .71933
	GRADIENT	15420	15367	15364	15366	-.00763	-.00784	-.00789	1.72721	.00904

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM050) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1592/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000	PITF
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PITF	PITF
1.492	-6.987	-1.18486	-1.18239	-1.18110	-1.18174	.14978	.14857	.14916	.1104 .26801	.1142 .38371	
1.492	-6.470	-1.10236	-1.10007	-1.09877	-1.09942	.14814	.14718	.14774	.1106 .53900	.1142 .65817	
1.493	-5.968	-1.03158	-1.02925	-1.02813	-1.02869	.15087	.14992	.15069	.15030 .16701	.1142 .65956	
1.493	-5.466	-1.95417	-1.95217	-1.95083	-1.95150	.15578	.15496	.15545	.15520 .19800	.1142 .74577	
1.492	-4.964	-1.87605	-1.87320	-1.87176	-1.87248	.15617	.15491	.15536	.15514 .29700	.1142 .42148	
1.493	-4.460	-1.79460	-1.79262	-1.79119	-1.79190	.15496	.15416	.15459	.15437 .60500	.1142 .23662	
1.492	-3.960	-1.71090	-1.70943	-1.70718	-1.70831	.15611	.15551	.15581	.15566 .1119 .72099	.1142 .26747	
1.493	-3.453	-1.62623	-1.62503	-1.62329	-1.62416	.15793	.15706	.15732	.15719 .1121 .67000	.1142 .08163	
1.492	-2.949	-1.54196	-1.54020	-1.54108	-1.54086	.15867	.15761	.15803	.15782 .1122 .87900	.1142 .91565	
1.492	-2.440	-1.46103	-1.45849	-1.45764	-1.45764	.15541	.15505	.15551	.15528 .1123 .40700	.1143 .02386	
1.493	-1.925	-1.37759	-1.37487	-1.37304	-1.37396	.15650	.15573	.15592	.15583 .1123 .50800	.1143 .00858	
1.492	-1.405	-1.29173	-1.29143	-1.28947	-1.29045	.15402	.15361	.15379	.15370 .1122 .75500	.1143 .50661	
1.492	-882	-1.20400	-1.20388	-1.20203	-1.20296	.15372	.15319	.15325	.15322 .1122 .31799	.1143 .76985	
1.493	-341	-1.11113	-1.11114	-1.10938	-1.11026	.14789	.14802	.14806	.14804 .1122 .85899	.1144 .01805	
1.493	-206	-1.00953	-1.00887	-1.00707	-1.00797	.12679	.12705	.12719	.12712 .1123 .42999	.1144 .45558	
1.492	.634	-1.06940	-1.06821	-1.07006	-1.06913	.10147	.10153	.10165	.10159 .1122 .89301	.1144 .63203	
1.493	1.089	-1.14502	-1.14364	-1.14534	-1.14449	.09062	.09106	.09119	.09112 .1122 .28799	.1144 .35463	
GRADIENT		.16833	.16774	.16776	.16775	-.00877	-.00853	-.00860	-.00856 .91368	.43486	
	RUN NO.	1608/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00					PITF
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PITF	PITF
1.515	-6.987	-1.34260	-1.33908	-1.33769	-1.33838	.16954	.16773	.16876	.1111 .05099	.1136 .14349	
1.515	-6.470	-1.26199	-1.25677	-1.25554	-1.25616	.16687	.16574	.16643	.16608 .1115 .96600	.1137 .73032	
1.515	-5.968	-1.17720	-1.17149	-1.17030	-1.17089	.17196	.17014	.17110	.17062 .1120 .52499	.1138 .66240	
1.516	-5.466	-1.07809	-1.07387	-1.07258	-1.07322	.17551	.17383	.17466	.17424 .1123 .82700	.1138 .45403	
1.515	-4.968	-9.8066	-9.77771	-9.7592	-9.7681	.17279	.17131	.17229	.17180 .1123 .22301	.1136 .25838	
1.515	-4.465	-8.9299	-8.88881	-8.88881	-8.88832	.17420	.17237	.17331	.17277 .1121 .50900	.1134 .80153	
1.515	-3.955	-8.11116	-8.06555	-8.05057	-8.05081	.17739	.17526	.17593	.17560 .1121 .71100	.1134 .58786	
1.516	-3.454	-7.1567	-7.1291	-7.1098	-7.1194	.17484	.17345	.17410	.17377 .1125 .23801	.1136 .14635	
1.514	-2.949	-6.1127	-6.0864	-6.0706	-6.0785	.16754	.16629	.16684	.16657 .1128 .12700	.1136 .97293	
1.516	-2.440	-5.1067	-5.0708	-5.0556	-5.0632	.16620	.16459	.16509	.16484 .1129 .15900	.1135 .92796	
1.515	-1.930	-4.1026	-4.0725	-4.0557	-4.0641	.16495	.16364	.16413	.16388 .1129 .90800	.1135 .71272	
1.516	-1.407	-3.0843	-3.0670	-3.0488	-3.0579	.16277	.16132	.16171	.16152 .1130 .36800	.1136 .02170	
1.516	-878	-2.0237	-2.0073	-2.0037	-2.0155	.16063	.15900	.15945	.15923 .1131 .05000	.1137 .66838	
1.516	-340	-0.9543	-0.9525	-0.9367	-0.9446	.15260	.15083	.15142	.15112 .1132 .39400	.1138 .54974	
1.515	-205	-0.2401	-0.2243	-0.2446	-0.2345	.12498	.12360	.12381	.12371 .1130 .37801	.1135 .68796	
1.516	.644	.10859	.10777	.10959	.10868	.08387	.08313	.08324	.08318 .1128 .56799	.1134 .17746	
1.516	1.094	.18002	.18023	.18270	.18146	.07053	.06963	.06985	.06974 .1128 .76601	.1134 .98589	
GRADIENT		.19551	.19463	.19474	.19469	-.01454	-.01454	-.01454	-.01448 .1.41878	.07145	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 778  
(UCM050) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1623/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	.500	PHI =	180.000		
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPBF	PTTF	PT2F		
1.542	-6.986	-1.25560	-1.24978	-1.24925	.15911	.15706	.15801	.15753	.1118	.05600	.1133	.64168	
1.541	-6.469	-1.12828	-1.12380	-1.1232	.15304	.15109	.15209	.15159	.1119	.56700	.1133	.62497	
1.542	-5.968	-1.01490	-1.01156	-1.01000	.15309	.15114	.15209	.15161	.1120	.06100	.1133	.52625	
1.541	-5.466	-0.90637	-0.90396	-0.90219	.149307	.14844	.14661	.14737	.14699	.1120	.26300	.1133	.77359
1.541	-4.968	-0.80102	-0.79873	-0.79664	.147968	.14155	.14000	.14082	.1119	.97400	.1133	.97736	
1.542	-4.465	-0.69909	-0.69615	-0.69434	.13901	.13750	.13826	.13788	.1120	.63300	.1134	.17073	
1.542	-3.954	-0.59837	-0.59369	-0.59463	.13391	.13222	.13299	.13260	.1121	.62100	.1134	.13147	
1.541	-3.453	-0.49950	-0.49700	-0.49520	.12443	.12323	.12416	.12369	.1123	.32401	.1134	.85925	
1.541	-2.950	-0.40430	-0.40250	-0.40340	.11172	.11055	.11111	.11083	.1124	.25400	.1135	.03079	
1.541	-2.440	-0.32897	-0.32784	-0.32617	.10301	.10127	.10180	.10154	.1123	.03500	.1135	.40541	
1.542	-1.925	-0.26471	-0.26366	-0.26183	.10274	.10103	.09908	.09936	.1123	.19299	.1135	.46388	
1.542	-1.412	-0.19586	-0.19406	-0.19195	.10195	.09774	.09680	.09730	.1123	.20700	.1135	.71095	
1.541	-0.882	-0.12812	-0.12619	-0.12420	.12520	.09567	.09488	.09515	.09502	.1123	.48500	.1136	.00725
1.542	-0.339	-0.05855	-0.05687	-0.05498	.05592	.08877	.08896	.08940	.08918	.1123	.92599	.1136	.03998
1.542	.206	.01349	.01262	.01487	.01375	.07362	.07378	.07422	.07400	.1124	.56400	.1136	.15866
1.541	.642	.06537	.06468	.06658	.06563	.05349	.05346	.05396	.05371	.1124	.39000	.1136	.19505
1.542	1.094	1.1524	1.1445	1.11630	1.11538	.04830	.04853	.04890	.04871	.1124	.07700	.1136	.02698
	GRADIENT	1.4809	1.4749	1.4751	.14750	.01472	-.01438	-.01447	-.01443	.59769	.39084		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 779

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM051) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1577 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000	PT2F
MACH	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB 1	DPB 2	DPB	PTTF	PTTF	PT2F
ALPHA	.65008	-.64976	-.64825	-.64901	.12630	.12654	.12698	.12676	.1570 .01700	.1597 .17000	
.600	-.6.960	-.60373	-.60349	-.60271	-.12427	-.12455	-.12493	-.12474	.1573 .68700	.1597 .03000	
.600	-.6.452	-.55767	-.55622	-.5553	-.12573	-.12584	-.12616	-.12600	.1576 .79800	.1596 .75999	
.600	-.5.945	-.51121	-.50994	-.50821	-.12528	-.12522	-.12556	-.12539	.1580 .05600	.1597 .02000	
.600	-.5.440	-.46624	-.46468	-.46308	-.12425	-.12517	-.12558	-.12538	.1582 .59500	.1596 .82001	
.600	-.4.938	-.4.428	-.41952	-.41809	-.12348	-.12482	-.12508	-.12495	.1585 .14799	.1596 .87000	
.600	-.4.428	-.3.920	-.37381	-.37319	-.12424	-.12528	-.12549	-.12539	.1587 .30701	.1597 .30000	
.600	-.3.920	-.3.411	-.32638	-.32675	-.12346	-.12451	-.12482	-.12467	.1589 .48700	.1597 .67000	
.601	-.2.900	-.2.7850	-.27862	-.27706	-.12173	-.12283	-.12314	-.12299	.1590 .77299	.1596 .77000	
.601	-.2.382	-.2.3037	-.23098	-.22927	-.12013	-.12159	-.12175	-.12195	.1592 .57700	.1597 .20000	
.600	-.1.863	-.1.8163	-.18281	-.18065	-.18173	-.12064	-.12100	-.12114	.1593 .56100	.1597 .03999	
.601	-.1.330	-.1.3444	-.13477	-.13294	-.13385	-.11862	-.11888	-.11902	.1594 .67900	.1597 .52000	
.600	-.798	-.08601	-.08652	-.08500	-.08576	-.11495	-.11525	-.11534	.1594 .98100	.1596 .73000	
.601	-.265	-.03865	-.03890	-.03724	-.03807	-.10694	-.10734	-.10740	.1595 .57600	.1597 .28999	
.601	.227	.00290	.00151	.00288	.00219	.00978	.00971	.00974	.1596 .00900	.1597 .56000	
.601	.704	.04189	.04132	.04248	.04210	.09132	.09197	.09205	.09201 .93201	.1597 .20000	
.600	1.185	.08423	.08399	.08532	.08465	.08510	.08585	.08586	.1595 .99899	.1596 .91000	
	GRADIENT	.09041	.09009	.09008	-.00604	-.00617	-.00622	-.00619	.2 .11509	.02519	
	RUN NO.	1467 / 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000	PT2F
MACH	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB 1	DPB 2	DPB	PTTF	PTTF	PT2F
ALPHA	.78005	-.78097	-.77961	-.78029	-.14155	-.14273	-.14314	-.14293	.1310 .53600	.1341 .19000	
.799	-.6.976	-.72412	-.72469	-.72332	-.72401	-.14392	-.14424	-.14400	.1314 .65401	.1341 .23000	
.800	-.6.457	-.66808	-.66937	-.66779	-.66858	-.14706	-.14717	-.14735	.1318 .24400	.1341 .14000	
.800	-.5.959	-.6.1273	-.61381	-.61230	-.61305	-.14489	-.14521	-.14501	.1321 .65300	.1340 .99001	
.800	-.5.453	-.58801	-.55975	-.55807	-.50368	-.14677	-.14688	-.14714	.1324 .54800	.1341 .06000	
.800	-.4.956	-.50325	-.50446	-.50290	-.44894	-.14451	-.14396	-.14419	.1327 .42000	.1341 .03000	
.800	-.4.451	-.44876	-.44968	-.44894	-.44894	-.14390	-.14379	-.14359	.1329 .76801	.1341 .10001	
.800	-.3.942	-.39271	-.39378	-.39216	-.39297	-.14289	-.14233	-.14267	.14250 .1331 .85600	.1341 .02000	
.800	-.3.439	-.3.3619	-.33706	-.33538	-.33622	-.14237	-.14175	-.14215	.14195 .1333 .84801	.1340 .86000	
.800	-.2.925	-.2.7953	-.28073	-.27898	-.27985	-.13905	-.13950	-.13989	.13969 .1335 .36600	.1340 .94000	
.800	-.2.415	-.2.2357	-.22478	-.22322	-.22400	-.13835	-.13899	-.13931	.13915 .1336 .68201	.1341 .20000	
.800	-.1.900	-.1.6807	-.1.6790	-.1.6622	-.1.6706	-.13818	-.13842	-.13832	.1337 .63901	.1340 .89999	
.800	-.1.383	-.1.1235	-.1.1258	-.1.1069	-.1.1152	-.13448	-.13497	-.13512	.1338 .34100	.1340 .89000	
.800	-.857	-.05662	-.05634	-.05466	-.05550	-.12850	-.12867	-.12880	.1338 .91800	.1341 .02000	
.800	-.339	-.00549	-.00489	-.00483	-.00486	-.12307	-.12310	-.12317	.1339 .31799	.1341 .13000	
.799	.636	.04569	.04400	.04560	.04480	-.11864	-.11884	-.11891	.1339 .58299	.1340 .95000	
.800	1.136	.09765	.09593	.09757	.09675	-.11202	-.11214	-.11224	.1339 .67000	.1340 .94000	
	GRADIENT	.10794	.10806	.10800	-.00517	-.00509	-.00507	-.00512	.2 .39548	-.01053	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 780

(UCMOS1) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1501/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000	
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	.81083	-.81283	-.81073	-.81178	.14925	.14949	.15017	.14983	.1244 .17900	.1274 .89999	
.900	-6.972	-7.5261	-7.5504	-7.5300	.15120	.15073	.15133	.15103	.1247 .96100	.1274 .07001	
.900	-6.451	-6.9322	-6.9595	-6.9390	.14970	.14920	.14976	.14948	.1248 .55600	.1271 .62000	
.900	-5.951	-6.3551	-6.3826	-6.3726	.15027	.14975	.15049	.15012	.1252 .91901	.1272 .50999	
.900	-5.448	-5.9756	-5.9817	-5.9795	.15043	.15033	.15099	.15066	.1256 .84500	.1273 .72000	
.900	-4.948	-5.2401	-5.2650	-5.2446	.15073	.14991	.15058	.15024	.1261 .38901	.1275 .03999	
.900	-4.442	-4.6553	-4.6761	-4.6557	.15071	.15015	.15054	.15034	.1262 .47400	.1272 .70000	
.900	-3.937	-4.0710	-4.0895	-4.0699	.14979	.14815	.14743	.14806	.1262 .44000	.1271 .07001	
.900	-3.426	-3.918	-3.9053	-3.8470	.14962	.14678	.14606	.14635	.1264 .59000	.1271 .96001	
.900	-2.406	-2.9108	-2.9258	-2.9158	.14517	.14527	.14578	.14552	.1267 .66701	.1273 .36000	
.900	-1.893	-2.3222	-2.3370	-2.3165	.14548	.14514	.14561	.14537	.1269 .59700	.1274 .71001	
.900	-1.371	-1.7491	-1.7512	-1.7333	.14343	.14355	.14361	.14378	.1272 .13600	.1275 .27000	
.900	-845	-1.1809	-1.1773	-1.1591	.141682	.13991	.13952	.13981	.1271 .98801	.1274 .25999	
.900	-325	-0.6010	-0.5944	-0.5782	.13863	.13323	.13312	.13324	.1271 .62900	.1273 .20000	
.900	-165	-0.0739	-0.0643	-0.0639	.12729	.12713	.12750	.12731	.1271 .30701	.1272 .95000	
.900	.650	.04635	.04517	.04685	.04601	.12203	.12205	.12237	.12221	.1271 .76300	.1272 .99001
.900	.140	.09978	.09888	.10055	.09971	.11601	.11591	.11612	.11602	.1271 .80701	.1272 .81000
	GRADIENT	.11175	.11203	.11211	.00541	.00533	.00533	.00540	.00536	.2 .41336	-.01800
	RUN NO.	1486/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
ALPHA	.82408	-.822716	-.83025	-.822716	.13505	.13466	.13534	.13500	.1174 .47600	.1204 .69400	
1.100	-6.998	-7.6542	-7.6569	-7.7163	.13866	.13788	.13707	.13747	.1178 .42399	.1204 .67500	
1.100	-6.483	-7.0747	-7.0825	-7.1405	.13697	.13634	.13664	.13664	.1182 .22900	.1204 .59900	
1.100	-5.978	-6.4916	-6.5008	-6.5561	.13821	.13705	.13773	.13739	.1185 .57700	.1204 .68900	
1.100	-5.476	-5.9214	-5.9288	-5.9859	.13787	.13687	.13735	.13711	.1188 .39600	.1204 .63499	
1.100	-4.980	-5.3495	-5.3543	-5.4154	.13794	.13680	.13743	.13712	.1191 .11600	.1204 .64400	
1.100	-4.480	-4.7665	-4.7701	-4.8267	.13820	.13667	.13711	.13689	.1193 .55400	.1204 .45399	
1.100	-3.977	-4.1816	-4.1820	-4.2105	.13756	.13638	.13687	.13663	.1195 .80493	.1204 .72701	
1.100	-3.470	-3.5908	-3.5852	-3.6166	.13647	.13501	.13569	.13535	.1197 .73900	.1204 .75999	
1.100	-2.971	-2.467	-2.9926	-2.9991	.13047	.13060	.13462	.13492	.1199 .21700	.1204 .96500	
1.100	-1.967	-2.4274	-2.4322	-2.4597	.13481	.13347	.13381	.13364	.1200 .30200	.1204 .75700	
1.100	-1.466	-1.8637	-1.8674	-1.9209	.13891	.13448	.13435	.13408	.1201 .37601	.1204 .67900	
1.100	-1.954	-1.3102	-1.3018	-1.3575	.13296	.13499	.13422	.13448	.1202 .13499	.1204 .65300	
1.100	-2.971	-0.7696	-0.7648	-0.8182	.12997	.12898	.12931	.12915	.1202 .73000	.1204 .61099	
1.100	-0.246	-0.2187	-0.2146	-0.2712	.13153	.13090	.13123	.13107	.1203 .22000	.1204 .83900	
1.100	.526	.03440	.03296	.02756	.03026	.13269	.13199	.13217	.1203 .43201	.1204 .80701	
1.100	1.034	.09092	.08932	.08376	.08654	.13285	.13214	.13228	.1203 .57600	.1204 .76100	
1.100	.11361	.11356	.11364	.11360	-.00121	-.00110	-.00112	-.00112	2 .44837	.02481	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM051) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1524/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	.979	-.89878	-.90008	-.89789	-.89899	.16122	.16104	.16182	.1151 .99100	.1182 .57201
-6.979	-.83481	-.83528	-.83291	-.83409	-.83378	.16372	.16428	.16400	.1156 .30099	.1182 .69099
-6.462	-.77257	-.77309	-.77072	-.77191	-.70639	.16043	.16083	.16063	.1160 .43201	.1182 .66701
-5.961	-.70658	-.70764	-.70513	-.70625	-.63968	.16103	.16082	.16133	.1163 .42101	.1182 .33600
-5.457	-.63981	-.64205	-.64087	-.64087	-.64087	.16102	.16060	.16118	.16089	.1165 .30200
-4.952	-.57759	-.57987	-.57739	-.57863	-.57863	.16285	.16270	.16320	.1167 .84399	.1182 .78700
-4.456	-.51470	-.51613	-.51386	-.51500	-.51500	.16242	.16294	.16352	.1171 .08800	.1183 .07001
-3.950	-.45051	-.45162	-.44921	-.45041	-.45041	.16004	.16040	.16090	.1173 .10699	.1182 .33600
-3.440	-.38558	-.38648	-.38426	-.38537	-.38537	.15812	.15826	.15874	.1174 .32600	.1182 .08600
-2.933	-.32336	-.32336	-.32121	-.32228	-.32228	.15638	.15660	.15696	.1176 .48599	.1182 .87199
-2.428	-.26003	-.26003	-.26135	-.26013	-.26013	.15555	.15585	.15624	.1178 .43300	.1183 .07500
-1.912	-.19856	-.19852	-.19644	-.19748	-.19748	.15571	.15594	.15642	.1179 .20599	.1182 .50900
-1.403	-.13604	-.13512	-.13302	-.13407	-.13407	.15346	.15347	.15377	.1179 .62199	.1182 .39799
-885	-.07342	-.07240	-.07026	-.07133	-.07133	.14860	.14896	.14929	.1180 .28101	.1182 .26300
-369	-.01400	-.01268	-.01068	-.01168	-.01168	.14312	.14344	.14369	.1180 .68401	.1182 .34100
-116	-.04675	-.04636	-.04835	-.04735	-.04735	.13988	.14028	.14050	.1181 .49300	.1182 .95900
-605	1.105	1.0787	1.0762	1.0864	1.0864	.13537	.13597	.13611	.13604 .1181 .39301	.1182 .82100
1.250	GRADIENT	.12319	.12367	.12360	.12364	-.00442	-.00442	-.00442	-.004417	.2 .58 180 .02848

	RUN NO.	1540/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.02953	-1.03284	-1.03063	-1.03173	-.95883	.19473	.22121	.19602	.1132 .99400	.1164 .44901
-6.981	-.95690	-.95996	-.95770	-.95770	-.88493	.19077	.21677	.19159	.1136 .55400	.1163 .99001
-6.465	-.88599	-.88692	-.88493	-.88592	-.81360	.18960	.21535	.19025	.1140 .15800	.1164 .51500
-5.962	-.81360	-.81434	-.81214	-.81324	-.74304	.18962	.21571	.19042	.20306 .1143 .52000	.1164 .07001
-5.459	-.74304	-.74442	-.74222	-.74332	-.67108	.18998	.21617	.19081	.20349 .1146 .77800	.1164 .44901
-4.960	-.67154	-.67340	-.67224	-.67224	-.59830	.19047	.21652	.19126	.20389 .1149 .83501	.1164 .25400
-4.458	-.59830	-.59974	-.59747	-.59869	-.52231	.19051	.21672	.19131	.20401 .1152 .25301	.1163 .88699
-3.954	-.52231	-.52396	-.52172	-.52284	-.44763	.18957	.21491	.18954	.20222 .1154 .39301	.1163 .96300
-3.445	-.44763	-.44537	-.44537	-.44650	-.44537	.18671	.21162	.18663	.19913 .1156 .43201	.1164 .79201
-2.939	-.37192	-.37246	-.37017	-.37131	-.30200	.18146	.20755	.18196	.19476 .1157 .57700	.1164 .37100
-2.434	-.30052	-.29974	-.29974	-.30087	-.29974	.18109	.20665	.18118	.19391 .1158 .33600	.1163 .90401
-1.925	-.23109	-.23238	-.23011	-.23124	-.23124	.18205	.20777	.18237	.19507 .1159 .39101	.1163 .96800
-1.400	-.16145	-.16062	-.15862	-.15962	-.08667	.17988	.20548	.17998	.19273 .1161 .50700	.1164 .57001
1.400	-.08942	-.08867	-.08667	-.08767	-.01945	.17410	.19975	.17431	.18703 .1162 .28300	.1164 .12601
1.399	-.02159	-.02036	-.01853	-.01935	-.01853	.16805	.19365	.16813	.18089 .1162 .45100	.1164 .30200
1.400	.04805	.04724	.04921	.04822	.04921	.16408	.19001	.16419	.17710 .1163 .24699	.1164 .51500
1.095	.11863	.11828	.12005	.11916	.14239	.15985	.18563	.15991	.17277 .1162 .32100	.1163 .86099
1.4201	.14239	.14239	.14239	.14239	-.00501	-.00512	-.00508	-.00508	.2 .57 182	-.00989

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 782  
 (UCM051) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1558/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000	PTTF
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.450	-6.962	-1.09107	-1.09329	-1.09142	-1.09236	.21766	.21774	.21857	.21815	1125.92700	1158.64500
1.450	-6.444	-1.01246	-1.01560	-1.01370	-1.01465	.21988	.21986	.22070	.22028	1129.64600	1158.42400
1.450	-5.941	-1.93608	-1.93869	-1.93649	-1.93759	.21308	.21316	.21392	.21354	1132.61200	1158.15401
1.450	-5.435	-1.85988	-1.86168	-1.85982	-1.86075	.21133	.21151	.21230	.21191	1135.62500	1158.88901
1.449	-4.929	-1.78536	-1.78795	-1.78574	-1.78685	.21329	.21363	.21439	.21401	1138.52400	1157.95100
1.450	-4.430	-1.71248	-1.71546	-1.71275	-1.71411	.21603	.21617	.21696	.21656	1142.57899	1158.51900
1.451	-3.918	-1.63439	-1.63704	-1.63487	-1.63595	.21596	.21615	.21681	.21648	1145.19901	1158.05800
1.450	-3.408	-1.55521	-1.55774	-1.55566	-1.55670	.21548	.21571	.21650	.21610	1147.00301	1158.09200
1.448	-2.897	-1.47182	-1.47438	-1.47223	-1.47331	.21186	.21190	.21250	.21220	1149.15199	1158.98399
1.450	-2.380	-1.39350	-1.39477	-1.39251	-1.39349	.20689	.20724	.20774	.20749	1148.98399	1158.08600
1.450	-1.862	-1.31783	-1.31934	-1.31733	-1.31834	.20640	.20704	.20750	.20727	1150.97900	1158.64301
1.451	-1.337	-1.24279	-1.24418	-1.24211	-1.24314	.20673	.20761	.20707	.20734	1152.71600	1157.86600
1.450	-806	-1.16502	-1.16554	-1.16368	-1.16461	.20459	.20499	.20556	.20528	1156.01801	1158.53000
1.450	-276	-0.86449	-0.8568	-0.83997	-0.8482	.19451	.19514	.19561	.19537	1157.77800	1158.06100
1.450	-215	-0.01139	-0.01076	-0.00899	-0.00988	.18191	.18243	.18336	.18289	1158.95300	1158.57899
1.450	.693	.06169	.06097	.06264	.06180	.17194	.17271	.17306	.17289	1158.45000	1158.34700
1.450	1.173	.13422	.13405	.13554	.13479	.16185	.16230	.16262	.16246	1157.52299	1158.69099
GRADIENT		.15047	.15104	.15090	.15097	-.00793	-.00785	-.00790	-.00788	3.19849	.04697
RUN NO.	1643/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00						
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.470	-6.969	-1.11718	-1.11355	-1.11246	-1.11301	.22004	.21944	.22025	.21984	1111.56799	1149.58067
1.470	-6.446	-1.03908	-1.03621	-1.03502	-1.03562	.22266	.22142	.22215	.22178	1115.61200	1148.93773
1.470	-5.944	-1.96221	-1.96458	-1.96117	-1.96169	.21936	.21857	.21930	.21894	1119.66100	1149.57219
1.471	-5.444	-1.88305	-1.88548	-1.88195	-1.88250	.21798	.21711	.21788	.21750	1123.71201	1148.99481
1.470	-4.938	-1.80403	-1.80157	-1.80009	-1.80083	.21659	.21572	.21648	.21610	1125.31400	1148.43817
1.484	-4.435	-1.72361	-1.72623	-1.72255	-1.72308	.21800	.21740	.21807	.21774	1127.66600	1167.35759
1.470	-3.928	-1.64655	-1.64467	-1.64338	-1.64403	.21744	.21694	.21747	.21720	1129.75800	1148.60939
1.470	-3.420	-1.56477	-1.56328	-1.56188	-1.56258	.21552	.21515	.21562	.21538	1132.07600	1148.94217
1.470	-2.905	-1.48354	-1.47933	-1.48000	-1.48050	.21391	.21450	.21433	.21412	1134.33701	1149.25298
1.470	-2.394	-1.40070	-1.39877	-1.39756	-1.39817	.21132	.21106	.21146	.21126	1133.59801	1148.76749
1.469	-1.873	-1.32490	-1.32388	-1.32256	-1.32322	.21205	.21252	.21250	.21228	1134.30000	1148.99287
1.470	-1.354	-1.24761	-1.24576	-1.24528	-1.24652	.21230	.21273	.21267	.21248	1134.88400	1148.56030
1.470	-822	-1.16752	-1.16606	-1.16679	-1.16679	.20995	.20976	.21026	.21001	1136.55400	1149.16786
1.469	-299	-1.08563	-1.08606	-1.0853	-1.08529	.20157	.20092	.20134	.20113	1136.37199	1149.04256
1.471	-194	-1.01075	-1.00977	-1.00842	-1.00909	.19009	.18797	.18844	.18820	1137.10100	1149.30350
1.470	.675	.06307	.06230	.06389	.06309	.17789	.17531	.17545	.17538	1136.82300	1148.78999
1.470	1.158	.13702	.13635	.13780	.13707	.16614	.16408	.16419	.16414	1137.19800	1149.52481
GRADIENT		.15353	.15357	.15355	.15355	-.00708	-.00733	-.00740	-.00737	1.77276	.89848

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM051) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	RN/L = 1593/ 0	RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = 1.000	PHI = 180.000	PTTF
	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
1.493	-1.18052	-1.17768	-1.17736	.23818	.23815	.23886	1106.48900 1144.34659
1.493	-1.09756	-1.09553	-1.09425	.23816	.23822	.23888	1108.70599 1144.49062
1.493	-1.02755	-1.02574	-1.02424	.23723	.23656	.23707	1111.77299 1144.52402
1.493	-95066	-94811	-94671	.24078	.24043	.24099	1114.39859 1144.39859
1.493	-87250	-86962	-86841	.23992	.23988	.24037	1117.41701 1144.33759
1.493	-4.444	-79055	-78893	.24167	.24114	.24159	1119.93700 1144.67177
1.493	-3.931	-70676	-70535	.24086	.24069	.24121	1122.24500 1144.77327
1.492	-3.419	-61887	-61821	.24280	.24253	.24289	1124.12601 1144.78015
1.493	-2.915	-53631	-53365	.24032	.24005	.24056	1125.24400 1144.67665
1.492	-2.400	-45489	-45209	.23674	.23674	.23698	1125.25800 1144.57185
1.493	-1.881	-37055	-36814	.23635	.23675	.23696	1125.16701 1144.39095
1.493	-1.364	-28354	-28321	.28237	.23491	.23455	1124.36099 1144.24869
1.492	-8333	-19423	-19406	.19229	.19317	.23170	1123.22200 1143.81926
1.493	-310	-10277	-10287	.10117	.10202	.22414	1124.22430 1143.76245
1.492	.179	.01702	.01649	.01470	.01559	.21130	.21174 1122.48300 1143.15646
1.492	.661	.06849	.06720	.06893	.06806	.19884	.19851 1122.01300 1143.01437
1.493	1.147	.15304	.15135	.15321	.15228	.18795	.18777 1121.91200 1142.78990
GRADIENT	.16777	.16718	.16725	.16721	.00770	.00768	.00775 -.00772 -.31277
	RN/L = 1609/ 0	RN/L = 2.49	GRADIENT INTERVAL = -5.00/ 5.00				
	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
1.516	-1.33668	-1.33127	-1.33004	.26633	.26516	.26602	1109.71100 1134.04962
1.516	-1.24882	-1.24288	-1.24253	.26744	.26664	.26750	1113.45000 1135.60667
1.516	-1.16972	-1.16490	-1.16370	.26541	.26427	.26511	1118.26401 1136.60063
1.516	-1.07022	-1.06704	-1.06472	.26746	.26606	.26690	1120.06500 1135.53868
1.515	-4.941	-97117	-96811	.26694	.26613	.26679	1120.36700 1134.90897
1.515	-4.439	-88957	-88512	.27250	.27114	.27170	1121.24001 1135.89218
1.516	-3.931	-81037	-80596	.27254	.27249	.27298	1123.12199 1136.21594
1.515	-3.424	-71295	-71011	.26883	.26907	.26966	1125.79900 1136.96872
1.515	-2.910	-60960	-60718	.26333	.26345	.26402	1127.94901 1137.24089
1.516	-2.401	-50416	-50057	.25737	.25601	.25661	1129.67300 1137.16661
1.516	-1.882	-40241	-39938	.25615	.25492	.25559	1130.68100 1137.43135
1.516	-1.361	-29764	-29466	.25419	.25322	.25370	1132.14900 1137.90741
1.516	.834	-19109	-19106	.19013	.24545	.24467	.24504 1131.93700 1138.07486
1.516	.309	.08305	.08295	.08117	.08206	.22872	.22906 1131.72200 1138.43991
1.516	.180	.01554	.01398	.01495	.20684	.20613	.20657 1132.05800 1138.75220
1.515	.663	.10610	.10446	.10529	.18899	.18817	.18821 1132.46500 1138.82274
1.516	1.150	.19070	.19142	.19232	.17459	.17373	.17355 1133.30099 1138.80432
GRADIENT	.19460	.19462	.19465	.19462	.01492	.01499	.01506 -.01503 2.12635 .59129



PARAMETRIC DATA									
RUN NO.	1578 / O	RN/L =	2.50	BETA =	1.500	PHI =	=	180.000	
ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
-6.941	-64882	-64832	-64687	-64759	-17447	-17478	-17502	1569.32700	1596.99001
-6.433	-60286	-60244	-60095	-60169	-17335	-17341	-17388	1572.95000	1596.72000
-5.926	-55401	-55408	-55251	-55330	-17189	-17186	-17233	1572.5100	1596.84000
-5.420	-50915	-50762	-50599	-50681	-17134	-17182	-17237	1579.63100	1597.06000
-4.907	-46206	-46052	-45900	-45976	-16975	-17014	-17050	1582.32800	1597.14000
-4.404	-41800	-41665	-41506	-41585	-16871	-16974	-17009	1584.99200	1597.03000
-3.889	-37177	-37087	-36932	-37010	-16921	-17040	-17059	1586.76199	1597.06000
-3.379	-32529	-32355	-32355	-32433	-16908	-17000	-17022	1589.06599	1596.82001
-2.863	-27625	-27643	-27484	-27563	-16717	-16757	-16787	1590.64500	1597.06000
-2.344	-22833	-22873	-22709	-22791	-16640	-16687	-16712	1592.14600	1596.97000
-1.823	-17977	-18073	-17870	-17972	-16391	-16430	-16456	1593.60600	1597.35001
-1.298	-13185	-13221	-13072	-13146	-16195	-16229	-16255	1594.00999	1596.77000
-601	-771	-84223	-84668	-8299	-08384	-15784	-15805	1594.83600	1596.98000
-601	-250	-03875	-03925	-03757	-03841	-15056	-15094	1595.35899	1597.03000
-600	-243	-00481	-00288	-00472	-00380	-14434	-14451	14456	1595.72900
-600	-735	-04747	-04697	-04867	-04782	-13962	-14009	14013	1595.81599
-600	-1.213	-08866	-08817	-08961	-08889	-13548	-13585	13583	1595.71500
.601	GRADIENT	.09062	.09024	.09026	.09025	-.00565	-.00575	-.00580	-.00577
RUN NO.	1468 / O	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00				5.00	
ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
-6.959	-77907	-78021	-77984	-77953	-20196	-20241	-20304	1309.87100	1341.28000
-6.448	-72271	-72360	-72225	-72293	-20193	-20245	-20291	1313.97501	1341.24001
-5.946	-66695	-66830	-66670	-66750	-20119	-20201	-20232	1317.73300	1341.00999
-5.437	-61137	-61283	-61147	-61215	-20078	-20164	-20226	1321.08800	1341.08000
-4.933	-55588	-55706	-55568	-55637	-20075	-20159	-20204	1324.18500	1341.11000
-4.430	-50155	-50238	-50110	-50174	-19852	-19949	-19991	1327.06100	1341.02000
-3.921	-44683	-44627	-44787	-44707	-19788	-19881	-19912	1329.72900	1340.95000
-3.413	-39198	-39177	-39047	-39132	-19710	-19746	-19776	1331.76601	1341.07001
-2.904	-33403	-33542	-33473	-33468	-19558	-19588	-19573	1333.48500	1340.89999
-2.388	-27761	-27848	-27699	-27773	-19375	-19452	-19483	1335.03999	1340.87000
-1.878	-22142	-22255	-22100	-22177	-19189	-19282	-19304	1336.39600	1340.92000
-1.353	-16574	-16525	-16359	-16442	-18929	-19028	-19054	1337.23599	1340.96001
-0.837	-1.1060	-1.0989	-1.0836	-1.0913	-18672	-18745	-18753	1338.23000	1341.05000
-0.326	-0.5571	-0.5355	-0.5438	-0.5438	-18197	-18214	-18206	1338.83099	1341.11000
-1.64	-0.0322	-0.0322	-0.0326	-0.0326	-17669	-17706	-17713	1339.07600	1340.92000
-0.63	-0.05036	-0.05036	-0.04939	-0.04939	-17348	-17382	-17407	1339.44200	1341.10001
1.151	-10160	-0.9976	-10156	-10066	-17079	-17137	-17121	1339.39500	1341.00999
GRADIENT	-10832	-10835	-10835	-10836	-.00492	-.00505	-.00503	2.42970	.00209

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 786  
(UCM052) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1502/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00			BETA =	1.500	PHI =	180.000
				DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PT2F
MACH	DPACAL									
.900	ALPHA	- .80890	- .81128	- .80940	- .81034	- .81034	.20886	.20932	.20983	.20957
-6.954		- .74998	- .75274	- .75058	- .75166	- .75166	.20883	.20936	.20991	.20964
-6.441		- .69219	- .69508	- .69294	- .69401	- .69401	.20957	.20992	.21047	.21020
-5.938		- .63455	- .63728	- .63491	- .63609	- .63609	.20879	.20917	.20978	.20947
-5.429		- .57749	- .57987	- .57782	- .57885	- .57885	.20778	.20819	.20882	.20850
-4.924		- .52076	- .52332	- .52125	- .52229	- .52229	.20709	.20773	.20834	.20804
-4.420		- .46386	- .46598	- .46399	- .46499	- .46499	.20546	.20587	.20642	.20615
-3.913		- .40589	- .40788	- .40583	- .40685	- .40685	.20413	.20488	.20548	.20518
-3.403		- .34760	- .34913	- .34690	- .34801	- .34801	.20298	.20353	.20395	.20374
-2.892		- .28868	- .29007	- .28812	- .29010	- .29010	.20131	.20165	.20216	.20191
-2.379		- .23039	- .23174	- .22994	- .23084	- .23084	.19852	.19922	.19983	.19953
-1.862		- .17213	- .17235	- .17046	- .17140	- .17140	.19688	.19741	.19775	.19758
-1.343		- .11473	- .11444	- .11270	- .11357	- .11357	.19273	.19341	.19391	.19366
-825		- .05783	- .05773	- .05579	- .05676	- .05676	.18824	.18886	.18920	.18903
-3.13		- .00465	- .00372	- .00361	- .00367	- .00367	.18280	.18296	.18383	.18340
-180		- .05188	- .05067	- .05251	- .05159	- .05159	.17898	.17907	.17931	.17919
-676		- .10340	- .10251	- .10419	- .10335	- .10335	.17628	.17666	.17681	.17674
-1.160		- .11220	- .11263	- .11249	- .11256	- .11256	-.00530	-.00535	-.00539	-.00537
GRADIENT										

RUN NO.	1509/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00			BETA =	1.500	PHI =	180.000
				DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PT2F
MACH	DPACAL									
1. 100	ALPHA	- .82524	- .82756	- .82551	- .82653	- .82653	.20271	.20254	.20283	.20268
-6. 984		- .76682	- .76920	- .76712	- .76816	- .76816	.19754	.19723	.19762	.19743
-6. 474		- .70954	- .71211	- .70952	- .71082	- .71082	.19661	.19657	.19686	.19672
-5. 973		- .65110	- .65364	- .65137	- .65251	- .65251	.19598	.19569	.19604	.19587
-5. 473		- .59290	- .59541	- .59287	- .59414	- .59414	.19772	.19781	.19800	.19791
-4. 973		- .53513	- .53735	- .53560	- .53648	- .53648	.19657	.19655	.19693	.19674
-4. 472		- .47914	- .48107	- .47902	- .48005	- .48005	.19564	.19571	.19596	.19583
-3. 964		- .41902	- .42093	- .41879	- .41986	- .41986	.19523	.19483	.19512	.19497
-3. 465		- .36005	- .36048	- .35875	- .35961	- .35961	.19423	.19443	.19443	.19433
-2. 962		- .30170	- .30299	- .30081	- .30190	- .30190	.19243	.19255	.19255	.19255
-2. 462		- .24380	- .24519	- .24323	- .24421	- .24421	.19068	.19076	.19088	.19082
-1. 957		- .18683	- .18791	- .18585	- .18688	- .18688	.19053	.19074	.19077	.19075
-1. 446		- .13164	- .13117	- .12946	- .13031	- .13031	.18911	.18932	.18930	.18931
-1. 000		- .448	- .07554	- .07512	- .07322	- .07322	.18747	.18763	.18816	.18804
-1. 000		- .039	- .02149	- .02093	- .01913	- .02003	.18769	.18771	.18784	.18777
-1. 000		- .545	- .03624	- .03533	- .03715	- .03624	.18806	.18840	.18833	.18836
1. 051		- .09362	- .09272	- .09450	- .09361	- .09361	.18844	.18879	.18872	.18876
GRADIENT		- .14396	- .14355	- .1428	- .1431	- .1431	-.00180	-.00174	-.00180	-.00177

PT2F

DPB

DPB2

DPB1

DPB

DPB2

PTTF

DPB

PTTF

DPB

DPB2

PTTF

DPB

PTTF

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM052) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.		1525/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.500	PHI =	180.000	PTTF
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	22781	1151.84700	1182.95000
ALPHA	.89739	-.89884	-.89663	-.89773	.22750	.22745	.22715	.22715	1155.76700	1182.56000	
-6.965	-	-	-	-	.22686	.22686	.22654	.22654	1159.29300	1181.96201	
-6.447	-.83406	-.83464	-.83242	-.83353	.22539	.22539	.22531	.22531	1162.68600	1181.85100	
-1.250	-	-	-	-	.22598	.22598	.22732	.22732	1162.68600	1181.85100	
-5.947	-.77107	-.77167	-.77050	-.77050	.22695	.22695	.22732	.22732	1162.68600	1181.85100	
-1.250	-	-	-	-	.22443	.22443	.22449	.22449	1165.67500	1182.87000	
-5.444	-.70442	-.70624	-.70376	-.70376	.22284	.22284	.22443	.22443	1167.98199	1182.78101	
-1.250	-	-	-	-	.22320	.22320	.22352	.22352	1170.17500	1182.24400	
-4.945	-.63842	-.64091	-.63857	-.63974	.22352	.22352	.22412	.22412	1172.39200	1182.33200	
-4.439	-	-	-	-	.22373	.22373	.22417	.22417	1174.49800	1182.56500	
-1.250	-.57644	-.57880	-.57736	-.57758	.22397	.22397	.22445	.22445	1176.07600	1182.43300	
-3.929	-.51223	-.51387	-.51159	-.51273	.22412	.22412	.22447	.22447	1176.64500	1182.64999	
-1.250	-	-	-	-	.22315	.22315	.22373	.22373	1178.56100	1182.60001	
-3.424	-.44912	-.45019	-.44769	-.44894	.22315	.22315	.22417	.22417	1179.08900	1182.23399	
-1.250	-	-	-	-	.22015	.22015	.22118	.22118	1180.26401	1182.74699	
-2.913	-.38431	-.38547	-.38319	-.38433	.22118	.22118	.22159	.22159	1180.55600	1182.64301	
-1.250	-	-	-	-	.21917	.21917	.21954	.21954	1180.91200	1182.77499	
-2.406	-.31928	-.32127	-.31907	-.32017	.21814	.21814	.21696	.21696	1182.64999	1182.64999	
-1.250	-	-	-	-	.21559	.21559	.21588	.21588	1182.23399	1182.23399	
-1.892	-.25814	-.25850	-.25615	-.25732	.21453	.21453	.21566	.21566	1182.64301	1182.64301	
-1.250	-	-	-	-	.21340	.21340	.21266	.21266	1183.00100	1184.30100	
-1.379	-.19624	-.19650	-.19440	-.19545	.21154	.21154	.21286	.21286	1184.50500	1185.80500	
-1.250	-	-	-	-	.20985	.20985	.21019	.21019	1185.00100	1186.30100	
-865	-.13416	-.13343	-.13150	-.13247	.20690	.20690	.20630	.20630	1186.60000	1187.90000	
-1.250	-	-	-	-	.20586	.20586	.20525	.20525	1187.20000	1188.50000	
-357	-.07173	-.07070	-.06861	-.06966	.20380	.20380	.20310	.20310	1188.60000	1189.90000	
-1.250	-	-	-	-	.20098	.20098	.20031	.20031	1189.91200	1190.21200	
132	-.01217	-.01079	-.00884	-.00981	.20130	.20130	.20164	.20164	1190.51314	.01300	
1.250	-.632	-.04926	-.04926	-.05139	.200403	.200403	.200402	.200402	1190.51314	.01300	
1.250	1.123	.10980	.10938	.11121	.12367	.12367	.12367	.12367	1190.51314	.01300	
1.250	GRADIENT	.12319	.12371	.12363							
RUN NO.		1541/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.500	PHI =	180.000	PTTF
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	28308	1132.35300	1164.23399
ALPHA	-.1.02674	-.1.03017	-.1.02804	-.1.02911	.27049	.29558	.27059	.27059	1136.10100	1164.31500	
-6.974	-.95441	-.95784	-.95529	-.95656	.26655	.29244	.26723	.26723	1143.00101	1164.55600	
-6.450	-.88409	-.88513	-.88273	-.88393	.26473	.29096	.26570	.26570	1143.00101	1164.50500	
-5.950	-.81088	-.81209	-.80991	-.81100	.26293	.28913	.26374	.26374	1145.79800	1163.89900	
-5.448	-.73898	-.74064	-.73837	-.73950	.26227	.28860	.26331	.26331	1149.74200	1164.52299	
-4.948	-.66908	-.67110	-.66987	-.66988	.26237	.28829	.26303	.26303	1151.85800	1164.00700	
-4.438	-.59693	-.59621	-.59740	-.59740	.26117	.28736	.26208	.26208	1154.15601	1164.36900	
-3.932	-.52059	-.52131	-.52286	-.52286	.25912	.28624	.26092	.26092	1156.43900	1164.27499	
-3.429	-.44560	-.44454	-.44666	-.44560	.25655	.28358	.25824	.25824	1157.06700	1164.11700	
-2.924	-.36873	-.36732	-.36693	-.36693	.25455	.28053	.25512	.25512	1158.20300	1164.20000	
-2.409	-.29864	-.29633	-.29748	-.29748	.25196	.27808	.25264	.25264	1158.90900	1163.90199	
-1.901	-.22734	-.22906	-.22690	-.22690	.24892	.27530	.24982	.24982	1160.28600	1164.35100	
-1.400	-.15476	-.15708	-.15592	-.15592	.24829	.27441	.24879	.24879	1161.51900	1164.28500	
1.400	-.08703	-.08623	-.08429	-.08526	.24448	.27057	.24498	.24498	1161.79100	1164.38200	
1.400	-.01769	-.01669	-.01568	-.01669	.24055	.26668	.24114	.24114	1162.24100	1164.38100	
1.400	.05228	.05162	.05358	.05260	.23827	.26467	.23905	.23905	1161.46899	1164.03101	
1.400	1.114	.12112	.12077	.12258	.12167	.23437	.26067	.23507	.24787	1161.46899	.01381
1.400	GRADIENT	.14250	.14258	.14254					.00483	.00483	.047555

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM052) ( 04 OCT 91 )

UN NO. 1559 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.0

DPRCAI  
DPRCII  
DPRCIII  
DPRCIV  
DPRCV

RUN NO. 1644 / O RN/L = 2.49 GRADIENT INTERVAL = -5.00 / 5.00

	GRADIENT	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ACH	ALPHA	-6.949	-1.11224	-1.10849	-1.10749	-1.03176	-1.03064	-1.03120	-30408	-30258	-1111.4644
-4.70	-6.430	-1.03475	-1.03475	-1.03475	-1.03475	-1.03475	-1.03475	-1.03475	-30226	-30289	-1149.4644
-4.71	-5.929	-9.61553	-9.59513	-9.5792	-9.55853	-9.53753	-9.51653	-9.49553	-30036	-30104	-1149.1183
-4.71	-5.425	-8.8199	-8.7995	-8.7883	-8.7793	-8.7683	-8.7573	-8.7463	-29919	-29986	-1149.1674
-4.70	-4.917	-8.0142	-7.9904	-7.9745	-7.9508	-7.9265	-7.8924	-7.8575	-29724	-29697	-1149.0092
-4.70	-4.411	-7.2267	-7.2027	-7.1916	-7.1916	-7.1791	-7.1671	-7.1551	-29404	-29471	-1125.4592
-4.70	-3.902	-6.4150	-6.3975	-6.3854	-6.3854	-6.3775	-6.3705	-6.3635	-29298	-29335	-1127.4570
-4.70	-3.393	-5.6133	-5.5968	-5.5832	-5.5832	-5.5755	-5.5675	-5.5590	-29172	-29230	-1129.8326
-4.71	-2.874	-4.8007	-4.7707	-4.7561	-4.7561	-4.7359	-4.7235	-4.7110	-29046	-29105	-1132.6522
-4.70	-2.359	-3.9563	-3.9381	-3.9235	-3.9235	-3.9038	-3.8935	-3.8810	-28543	-28615	-1133.6710
-4.71	-1.842	-3.1785	-3.1686	-3.1545	-3.1545	-3.1416	-3.1316	-3.1216	-28256	-28334	-1134.5190
-4.70	-1.320	-2.4044	-2.4014	-2.3861	-2.3861	-2.3738	-2.3618	-2.3518	-28173	-28235	-1134.8267
-4.70	-0.798	-1.6213	-1.6144	-1.5995	-1.5995	-1.5835	-1.5675	-1.5515	-27854	-27925	-1135.7879
-4.70	-0.282	-0.8206	-0.8243	-0.8206	-0.8206	-0.8165	-0.8125	-0.8087	-27213	-27302	-1136.5840
-4.70	-0.0812	-0.0663	-0.0663	-0.0663	-0.0663	-0.0616	-0.0616	-0.0616	-0.0699	-0.0707	-1136.5939
-2.10	-0.6714	-0.705	-0.705	-0.705	-0.705	-0.6739	-0.6739	-0.6739	-0.6739	-0.6739	-1136.5840
-4.70	1.187	1.3900	1.3816	1.3970	1.3970	1.3893	1.3893	1.3893	1.3550	1.3550	1149.1680
-4.71	1.5405	1.5353	1.5353	1.5353	1.5353	1.5353	1.5353	1.5353	1.00740	1.00699	1149.0178
									0.00702	1.00702	1149.0178

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM052) ( 04 OCT 91 )

METRIC DATA

PARAMETRIC DATA

RUN NO. 1610/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1625/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00
DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2
-1.26429	-1.25893	-1.25765	-1.25829	.35523	.35272	.35362
-1.13474	-1.13024	-1.12873	-1.12948	.34261	.34014	.34098
-1.01918	-1.01581	-1.01412	-1.01496	.33357	.33309	.33408
-.91062	-.90817	-.90657	-.90737	.32721	.32505	.32570
-.80651	-.80404	-.80225	-.80314	.31513	.31428	.31474
-.4.926	-.4.926	-.4.916	-.4.916	.30544	.30627	.30586
-.3.906	-.3.906	-.3.400	-.3.400	.30682	.30202	.29412
-.5.1456	-.5.1456	-.4.2306	-.4.2306	.29487	.60409	.60500
-.2.882	-.2.882	-.3.3184	-.3.3184	.29369	.60591	.60591
-.2.367	-.2.367	-.2.5820	-.2.5820	.27746	.51204	.51103
-.1.853	-.1.853	-.1.332	-.1.332	.27888	.18956	.18898
-.1.541	-.1.541	-.1.1958	-.1.1958	.25691	.11958	.11750
-.811	-.811	-.2.96	-.2.96	.25749	.41895	.41979
-.1.541	-.1.541	-.3.2901	-.3.2994	.23559	.42063	.42063
-.1.541	-.1.541	-.32901	-.32994	.23630	.42306	.42306
-.1.541	-.1.541	-.32901	-.32994	.23559	.42306	.42306
-.1.541	-.1.541	-.32901	-.32994	.23559	.42306	.42306
-.1.541	-.1.541	-.32901	-.32994	.23559	.42306	.42306
GRADIENTI	15138	15085	15087	.022213	.022116	.022114

## PARAMETRIC DATA

RUN NO.	1579/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000	PT2F	
										DPB1	DPB2
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.600	-6.923	-6.4781	-64714	-64571	-64642	-21904	-21992	-22036	-22014	1568.69701	1596.98000
.600	-6.410	-60072	-60030	-59885	-59958	-21815	-21888	-21926	-21907	1572.34399	1596.95000
.599	-5.903	-55131	-55275	-55131	-55203	-21921	-22010	-22042	-22026	1575.69000	1596.82001
.599	-5.396	-50537	-50537	-50381	-50459	-21818	-21906	-21947	-21927	1578.84700	1597.03999
.599	-4.888	-45979	-45845	-45705	-45775	-21800	-21886	-21915	-21901	1581.71201	1596.89999
.600	-4.378	-41349	-41283	-41123	-41203	-21668	-21753	-21788	-21771	1584.31900	1597.00999
.600	-3.864	-36860	-36792	-36623	-36707	-21521	-21614	-21661	-21638	1586.47900	1597.32001
.600	-3.356	-32169	-32183	-32021	-32102	-21512	-21619	-21648	-21633	1588.33600	1597.03000
.600	-2.837	-27525	-27555	-27390	-27473	-21344	-21442	-21463	-21452	1590.04900	1596.39000
.600	-2.315	-22778	-22816	-22656	-22736	-21054	-21152	-21189	-21171	1591.59300	1596.99001
.600	-1.797	-17842	-17842	-17702	-17817	-20788	-20889	-20914	-20902	1592.69800	1597.23000
.600	-1.273	-13076	-13100	-12942	-13021	-20482	-20589	-20601	-20595	1593.91701	1597.32001
.600	-756	-08434	-08459	-08303	-08381	-20083	-20196	-20203	-20199	1594.19600	1596.69000
.600	-2399	-03839	-03883	-03716	-03800	-19555	-19665	-19699	-19682	1594.93500	1597.63000
.600	.251	.00349	.00302	.00478	.00390	-19036	-19162	-19161	-19161	1595.29100	1596.89000
.600	.753	.04912	.04839	.05010	.04925	-18694	-18804	-18825	-18814	1595.23399	1597.28999
.600	1.235	.09214	.09146	.09230	.0914	-18345	-18408	-18476	-18442	1595.64700	1596.64999
.600	GRADIENT	.09038	.09012	.09015	.09014	-00583	-00581	-00581	-00581	2.18613	.01034
RUN NO.	1470/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	DPB1	DPB2
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.800	-6.946	-77806	-77781	-77662	-77722	-26116	-26168	-26222	-26195	1309.26401	1341.10001
.800	-6.433	-72254	-72218	-72084	-72151	-25756	-25748	-25805	-25776	1313.14301	1341.25999
.800	-5.930	-66608	-66727	-66565	-66646	-25584	-25613	-25649	-25631	1316.87399	1340.95000
.800	-5.424	-61012	-61160	-61029	-61095	-25448	-25536	-25568	-25552	1320.29300	1341.16000
.800	-4.919	-55352	-55488	-55323	-55408	-25461	-25525	-25561	-25543	1323.47000	1340.99001
.800	-4.411	-49900	-49991	-49839	-49915	-25469	-25546	-25529	-25512	1326.21800	1340.75999
.800	-3.907	-44646	-44529	-44392	-44460	-25342	-25383	-25417	-25400	1328.82001	1341.13000
.800	-3.391	-38846	-38906	-38746	-38826	-25221	-25297	-25318	-25307	1331.02299	1340.85001
.800	-2.882	-33236	-33374	-33224	-33299	-24991	-25065	-25098	-25082	1333.00800	1341.06000
.800	-2.369	-27662	-27730	-27571	-27650	-24769	-24838	-24870	-24854	1334.54900	1341.13000
.800	-1.855	-22111	-22108	-21944	-22026	-24492	-24541	-24566	-24554	1335.88901	1341.03999
.800	-1.340	-16468	-16412	-16252	-16332	-24263	-24298	-24316	-24307	1337.04700	1341.08000
.800	-826	-11057	-10963	-10819	-10891	-23936	-24007	-24023	-24015	1337.91701	1340.89999
.800	-319	-05575	-05490	-05329	-05410	-23621	-23691	-23702	-23696	1338.51801	1341.03000
.800	-174	-00332	-00224	-00220	-00222	-23256	-23299	-23328	-23314	1338.94099	1340.97000
.800	-677	-05049	.04956	.05120	.05038	-22959	-23037	-23048	-23042	1339.15900	1341.14000
.800	1.167	.10355	.10237	.10387	.10312	-22656	-22696	-22703	-22700	1339.22230	1340.86000
.800	GRADIENT	.10804	.10824	.10818	.10821	-00487	-00486	-00490	-00488	2.53460	.00705

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 792

(UCM053) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	2.000	PHI =	180.000
	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PT2F
.899	- .80810	- .81071	- .80876	- .80973	.26836	.26871	.26942	.26907 1243.55200
-6.941	- .74915	- .75180	- .74975	- .75077	.26731	.26752	.26817	.26785 1246.08099
-6.424	- .69118	- .69396	- .69169	- .69283	.26590	.26644	.26692	.26668 1248.72400
.900	- .63274	- .63537	- .63303	- .63420	.26626	.26677	.26744	.26710 1251.69400
-5.411	- .57510	- .57700	- .57551	- .57661	.26464	.26511	.26552	.26532 1275.12701
.900	- .4400	- .51779	- .51993	- .51785	.26440	.26489	.26542	.26515 1258.40401
-4.400	- .46041	- .46276	- .46054	- .46165	.26350	.26445	.26507	.26476 1261.01401
-3.890	- .40396	- .40496	- .40284	- .40390	.26212	.26303	.26359	.26331 1263.32800
-3.382	- .40498	- .344667	- .344665	- .34566	.26071	.26122	.26173	.26148 1265.44099
.900	-2.874	- .28698	- .28856	- .28660	.28758	.25741	.25762	.25785 1267.05299
-2.354	-1.843	- .22859	- .23023	- .22825	.22924	.25464	.25479	.25529 1268.38300
.900	-1.326	- .17084	- .17079	- .16876	.16978	.25191	.25241	.25245 1270.32300
-8.11	- .11419	- .11397	- .11203	- .11203	.11300	.24807	.24849	.24871 1271.02499
.900	- .303	- .05752	- .05713	- .05547	.05630	.24418	.24450	.24496 1270.50900
.900	.189	- .00357	- .00350	- .00343	.00347	.24014	.24078	.24097 1271.04900
.900	.691	.05207	.05089	.05264	.05177	.23736	.23796	.23834 1271.53999
.900	1.181	.10675	.10575	.10733	.10654	.23406	.23444	.23463 1271.71700
	GRADIENT	.11201	.11238	.11229	- .00536	- .00539	- .00542	- .00541 2.56727 .08658
	RN/L =	1510/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00			
	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PT2F
		- .82330	- .82561	- .82335	.82448	.25905	.25802	.25842
		- .76571	- .76821	- .76599	.76710	.25751	.25740	.25758
		- .70571	- .71056	- .70839	.70947	.25690	.25660	.25704
		- .65064	- .65298	- .65069	.65184	.25385	.25420	.25437
		- .59185	- .59425	- .59203	.59314	.25373	.25367	.25389
		- .53465	- .53606	- .53457	.53531	.25386	.25411	.25399
		-3.960	-4.7665	-4.7846	-4.7744	.25389	.25373	.25387
		-3.455	-4.1903	-4.1990	-4.1774	.25279	.25333	.25353
		-2.954	-3.5917	-3.5991	-3.5840	.25130	.25172	.25191
		-2.451	-3.0048	-3.0206	-3.0010	.24990	.24980	.24997
		-1.947	-2.4290	-2.4426	-2.4220	.24836	.24843	.24860
		-1.446	-1.8515	-1.8618	-1.8428	.24648	.24653	.24668
		-1.00	-1.2962	-1.2938	-1.2747	.24513	.24536	.24539
		-1.00	-0.7364	-0.7336	-0.7144	.24388	.24421	.24433
		-1.00	-0.1898	-0.1895	-0.1703	.24434	.24436	.24440
		.045	.03885	.03760	.03925	.24493	.24525	.24534
		1.060	.09617	.09525	.09688	.24402	.24430	.24440
		1.100	.11455	.11453	.11451	- .00201	- .00197	- .00200
		GRADIENT	.11429			- .00199	2.55771	-.00759

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM053) ( 04 Oct 91 )

PARAMETRIC DATA										
RUN NO.	1526/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	2.000	PHI =	180.000
ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
MACH	.89538	-.89641	-.89460	-.89550	.29226	.29329	.29297	1150.94400	1182.78500	
	-.83211	-.83314	-.83079	-.83196	.29152	.29214	.29253	1154.85400	1182.61900	
	-.76940	-.77010	-.76766	-.76888	.29206	.29238	.29314	.29276	1158.90401	1182.40500
	-.70517	-.70721	-.70475	-.70598	.28699	.28791	.28853	.28822	1162.16200	1182.14900
	-.63743	-.63997	-.63739	-.63868	.28692	.28796	.28842	.28819	.1165.00700	1182.51801
	-.57363	-.57639	-.57392	-.57516	.28433	.28535	.28599	.28567	1167.16600	1182.40601
	-.51140	-.51278	-.51031	-.51154	.28562	.28599	.28624	1169.44000	1182.30200	
	-.3.916	-.3.921	-.4.4597	-.44716	.28542	.28595	.28646	.28620	1171.50800	1182.42101
	-.3.403	-.3.403	-.44835	-.44597	.28263	.28338	.28450	.28423	1173.78200	1182.49100
	-.2.896	-.3.8264	-.38374	-.38152	.28055	.28132	.28045	.28065	1175.41800	.1182.36900
	-.2.387	-.3.1881	-.3.2055	-.3.1832	.27949	.27949	.28086	.27767	.1176.78500	.1182.23700
	-.1.874	-.2.5676	-.2.5709	-.2.5491	.27649	.27726	.27747	.27740	1178.10500	.1182.82500
	-.1.365	-.1.9397	-.1.9439	-.1.9319	.27433	.27534	.27545	.27540	1179.18900	.1182.85500
	-.853	-.1.3229	-.1.3167	-.1.2953	.27060	.27167	.27258	.27265	1179.32700	.1182.10800
	-.349	-.0.7107	-.0.6991	-.0.6784	.26932	.27033	.27061	.27047	1179.81799	.1182.40500
	-.1.39	-.0.1108	-.0.0971	-.0.0785	.26661	.26756	.26794	.26775	.1179.80800	.1182.42000
	.644	.0.4996	.0.5019	.0.5119	.26464	.26575	.26598	.26586	.1179.70500	.1182.90900
	1.138	.1.1263	.1.1225	.1.1415	.26187	.26308	.26320	.26320	1180.70500	.1182.56136
	1.250	.1.2337	.1.2393	.1.2387	-.00436	-.00436	-.00435	-.00432	.2.56136	-.03326
GRADIENT										
RUN NO.	1543/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00				
ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	FITF	FITF	
MACH	-1.02532	-1.02783	-1.02677	.34530	.34431	.34503	.34467	1131.10500	1164.07700	
	-.95541	-.95804	-.95597	-.95700	.34226	.34130	.34154	1135.75999	1164.63600	
	-.88222	-.88467	-.88247	-.88357	.33909	.33856	.33895	1138.94701	1164.14500	
	-.81003	-.81115	-.80904	-.81010	.33521	.33518	.33551	1142.11099	1164.18500	
	-.73805	-.73915	-.73717	-.73816	.33395	.33430	.33473	.33451	1145.65800	.1164.39900
	-.66760	-.66877	-.66648	-.66763	.33349	.33390	.33439	.33414	1148.40900	.1164.07300
	-.59530	-.59659	-.59441	-.59550	.33310	.33408	.33456	.33432	1151.26401	.1164.42101
	-.52114	-.52190	-.51975	-.52083	.33359	.33458	.33516	.33487	1153.98500	.1164.43100
	-.4.903	-.4.4373	-.4.4578	-.4.4475	.33023	.33075	.33049	.33049	1155.49200	.1163.78799
	2.397	-.37036	-.37066	-.36967	.32504	.32599	.32637	.32618	1156.73500	.1164.22900
	1.890	-.29846	-.29648	-.29747	.32102	.32183	.32217	.32200	1158.14200	.1164.39000
	1.377	-.22531	-.22610	-.22517	.31709	.31817	.31851	.31834	1158.46800	.1164.5901
	-.867	-.15365	-.15562	-.15459	.31438	.31531	.31563	.31547	1159.62000	.1164.47600
	-.364	-.08381	-.08487	-.08290	.31150	.31293	.31273	.31273	1160.14799	.1164.08200
	1.27	-.01620	-.01547	-.01462	.30882	.30979	.31009	.30994	1160.31599	.1163.99001
	6.30	-.05370	-.05318	-.05407	.30653	.30782	.30817	.30800	1160.89600	.1164.75700
	1.128	-.12358	-.12341	-.12421	.30469	.30473	.30477	.30473	1160.87300	.1164.04500
	1.4270	-.14253	-.14279	-.14274	-.00564	-.00555	-.00555	-.00555	-.0023784	-.00295

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 794

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM053) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1560/ 0	RN/L =	2.50	GRADIENT INTERVAL =	- 5.00/ 5.00	BETA =	2.000	PHI =	180.000	
DPACAL											
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
1.450	-6.926	-1.08314	-1.08528	-1.08336	.37147	.37160	.37256	.37208	1124.66800	1157.97000	
1.450	-6.412	-1.00787	-1.01131	-1.00923	.37243	.37257	.37355	.37306	1128.83400	1158.58299	
1.450	-5.899	-0.93270	-0.93511	-0.93294	.36740	.36778	.36851	.36814	1131.62601	1158.05200	
1.450	-5.393	-0.85411	-0.85582	-0.85381	.36434	.36572	.36573	.36572	1134.67900	1158.65401	
1.449	-4.889	-0.77795	-0.77981	-0.77763	.36127	.36276	.36258	.36267	1137.45700	1158.73500	
1.449	-4.381	-0.70382	-0.70681	-0.70458	.36059	.36371	.36543	.36542	1140.48000	1157.67799	
1.450	-3.867	-0.62984	-0.63226	-0.63005	.63116	.36831	.36740	.36776	1144.13200	1158.57800	
1.450	-3.354	-0.54837	-0.55167	-0.54949	.55058	.36657	.36641	.36622	.36631	1146.35899	1158.38100
1.450	-2.838	-0.46764	-0.47019	-0.46810	.46915	.36420	.36362	.36340	.36351	1147.93800	1158.57201
1.450	-2.321	-0.38735	-0.38958	-0.38748	.38853	.35897	.35843	.35881	.35862	1149.58299	1158.39600
1.450	-1.801	-0.30924	-0.31071	-0.30959	.30965	.35212	.35144	.35196	.35170	1149.73801	1158.20399
1.450	-1.283	-0.23197	-0.23328	-0.23137	.23233	.34819	.34760	.34824	.34792	1151.00700	1158.82201
1.449	-7.763	-0.15673	-0.15611	-0.15414	.15513	.34322	.34258	.34322	.34322	1151.72701	1158.12801
1.451	-0.252	-0.08141	-0.08069	-0.07867	.07968	.33851	.33785	.33826	.33806	1152.64301	1158.42000
1.450	.240	-0.00807	-0.00709	-0.00674	.00691	.33193	.33134	.33193	.33163	1153.20399	1158.28900
1.449	.738	.06645	.06575	.06729	.06652	.32652	.32572	.32631	.32602	1153.30499	1158.81700
1.450	1.223	.13857	.13823	.13981	.13902	.31994	.31958	.31995	.31977	1153.36200	1158.43700
GRADIENT											
	RUN NO.	1645/ 0	RN/L =	2.49	GRADIENT INTERVAL =	- 5.00/ 5.00					
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
1.470	-6.935	-1.10861	-1.10518	-1.10388	-1.10453	.38118	.37771	.37780	.37826	1110.83200	1149.56627
1.470	-6.417	-1.02915	-1.02917	-1.02817	.38145	.37813	.37908	.37781	1113.86900	1148.53436	
1.470	-5.911	-0.95742	-0.95503	-0.95386	.95445	.38053	.37790	.37753	1118.35699	1149.36375	
1.471	-5.403	-0.87990	-0.87798	-0.87691	.87744	.37932	.37616	.37693	.37655	1122.23000	1148.84988
1.470	-4.897	-0.79927	-0.79670	-0.79531	.79601	.37377	.37077	.37167	.37122	1124.62500	1148.62871
1.484	-4.389	-0.72013	-0.71745	-0.71621	.71683	.37175	.36929	.37008	.36968	1126.45300	1166.57428
1.485	-3.881	-0.63902	-0.63737	-0.63587	.63662	.37083	.37013	.37094	.37054	1128.60300	1166.84029
1.484	-3.365	-0.55662	-0.55522	-0.55592	.55545	.36980	.36883	.36956	.36919	1130.76199	1166.92859
1.484	-2.855	-0.47684	-0.47394	-0.47254	.47324	.36832	.36750	.36810	.36780	1133.32899	1167.53951
1.470	-2.336	-0.39527	-0.39341	-0.39192	.39267	.36199	.36240	.36209	.36224	1134.84100	1148.89999
1.484	-1.821	-0.31373	-0.31169	-0.31169	.31240	.35501	.35532	.35580	.35556	1134.62900	1167.21565
1.471	-1.304	-0.23530	-0.23337	-0.23337	.23420	.35255	.35298	.35345	.35321	1134.71001	1148.64755
1.470	-0.785	-0.15870	-0.15798	-0.15655	.15726	.34898	.34940	.34989	.34965	1135.97301	1149.02832
1.469	-0.274	-0.08036	-0.08076	-0.07929	.08003	.34302	.34332	.34371	.34352	1135.99600	1148.97960
1.470	-0.219	-0.00699	-0.00572	-0.00586	.00579	.33656	.33691	.33736	.33714	1136.08701	1148.38876
1.470	.719	.06735	.06889	.06889	.06812	.33086	.33123	.33153	.33153	1136.73599	1149.40207
1.470	1.206	.14145	.14029	.14182	.14105	.32431	.32403	.32430	.32417	1136.82600	1149.08327
GRADIENT											
	RUN NO.	15367	RN/L =	1.5363	.15365	-.00831	-.00780	-.00787	-.00783	1.88885	- 2.67377

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM053) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1595/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.493	-6.939	-1.17121	-1.16882	-1.16759	-1.16820	.40459	.40284	.40360	.1104 .81300	.1143 .28940
1.493	-6.426	-1.08981	-1.08796	-1.08652	-1.08724	.40210	.40103	.40179	.1107 .80299	.1143 .09132
1.493	-5.914	-1.01500	-1.01332	-1.01188	-1.01260	.40263	.40154	.40220	.1110 .23199	.1143 .65099
1.493	-5.410	-9.4151	-9.3941	-9.3791	-9.3866	.40392	.40306	.40362	.1113 .60201	.1143 .11507
1.493	-4.904	-8.6112	-8.5858	-8.5694	-8.5776	.40404	.40295	.40371	.1116 .12100	.1143 .30212
1.493	-4.395	-7.7798	-7.7665	-7.7498	-7.7582	.40657	.40552	.40601	.1118 .22800	.1142 .90750
1.493	-3.887	-6.93220	-6.92333	-6.9073	-6.9153	.40609	.40560	.40599	.1119 .97800	.1142 .74168
1.493	-3.373	-6.0763	-6.0727	-6.0560	-6.0643	.40604	.40518	.40560	.1121 .61099	.1142 .81451
1.493	-2.863	-5.2347	-5.2106	-5.1931	-5.2019	.40375	.40295	.40349	.1122 .90100	.1142 .69765
1.493	-2.350	-4.3861	-4.3635	-4.3460	-4.3548	.40049	.39933	.39991	.1124 .42300	.1144 .26031
1.493	-1.832	-3.5460	-3.5347	-3.5159	-3.5253	.39970	.39729	.39754	.1125 .85699	.1144 .56660
1.493	-1.314	-2.6756	-2.6753	-2.6576	-2.6664	.39694	.39431	.39477	.1126 .00101	.1144 .53885
1.493	-7.797	-1.8225	-1.8323	-1.8071	-1.8197	.39149	.38907	.38944	.1125 .67900	.1144 .00462
1.493	-2.289	-0.9602	-0.9632	-0.9470	-0.9551	.38778	.38520	.38552	.1125 .15500	.1143 .99414
1.493	.202	-0.1122	-0.1193	-0.0994	-0.1094	.37964	.37751	.37781	.1124 .97701	.1143 .30759
1.493	.705	.07450	.07294	.07498	.07396	.37201	.36967	.36982	.1124 .89700	.1142 .79517
1.493	1.192	.15809	.15621	.15825	.15723	.36627	.36480	.36411	.1124 .89999	.1142 .21631
1.493	1.6686	.16623	.16631	.16627	.16627	.00632	.00659	.00672	.00665	.01955
	RUN NO.	1611/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.516	-6.939	-1.34064	-1.33520	-1.33380	-1.33450	.45945	.45576	.45653	.45614	.1112 .24400
1.516	-6.422	-1.25319	-1.24762	-1.24702	-1.24732	.45513	.45149	.45241	.45195	.1116 .69901
1.516	-5.914	-1.17016	-1.16512	-1.16385	-1.16448	.45639	.45390	.45470	.45430	.1120 .14900
1.516	-5.410	-1.06720	-1.06392	-1.06147	-1.06270	.45666	.45427	.45481	.45454	.1122 .07401
1.516	-4.897	-9.6401	-9.6104	-9.5959	-9.6031	.45144	.44890	.44955	.44923	.1122 .70200
1.516	-4.396	-8.6939	-8.66467	-8.6320	-8.6393	.45371	.45145	.45209	.45177	.1122 .07401
1.516	-3.887	-7.9128	-7.8720	-7.8564	-7.8642	.45949	.45779	.45849	.45814	.1122 .53400
1.516	-3.378	-7.0024	-6.9751	-6.9584	-6.9667	.46178	.46033	.46114	.46074	.1123 .88800
1.516	-2.863	-6.0254	-5.9999	-5.9811	-5.99005	.45394	.45264	.45308	.45286	.1126 .17300
1.516	-2.346	-4.9973	-4.9613	-4.9462	-4.9538	.44322	.44159	.44229	.44194	.1127 .88600
1.516	-1.834	-3.9431	-3.9127	-3.8942	-3.9035	.43402	.43261	.43331	.43296	.1129 .46800
1.516	-1.314	-2.8960	-2.8667	-2.8762	-2.8762	.42592	.42435	.42457	.4130 .40900	.1138 .07527
1.516	-0.799	-1.8870	-1.8898	-1.8708	-1.8803	.42389	.42225	.42251	.1131 .54100	.1138 .84618
1.516	-0.288	-0.8888	-0.8883	-0.8761	-0.8761	.41253	.41104	.41165	.41135	.1132 .91499
1.516	.203	.00890	.00766	.00953	.00859	.40351	.40227	.40278	.40252	.1132 .70399
1.516	.704	.09828	.09779	.09946	.09862	.39130	.39226	.39177	.39154	.1131 .01401
1.516	1.195	.18690	.18674	.18870	.18772	.38363	.38486	.38404	.38384	.1130 .97000
	RUN NO.	19103	RN/L =	1.9106	GRADIENT INTERVAL =	-5.00/ 5.00				

PARAMETRIC DATA

BETA = 2 000 PHI = 180 000

RUN NO 1626/0 RN/ = 2 49 GRADIENT INTERVAL = -5 00/ 5 0

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM054) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.600	.906	-.646667	-.64622	-.644669	-.64545	.26548	.26619	.26666	.26643	1567.55299	1596.58000
.600	.393	-.59860	-.59824	-.59661	-.59743	.26626	.26699	.26729	.26714	1571.52299	1596.73000
.599	.888	-.55352	-.55306	-.55157	-.55231	.26514	.26619	.26651	.26635	1574.78101	1596.64999
.599	.376	-.50657	-.50480	-.50332	-.50406	.26409	.26505	.26542	.26523	1578.07899	1597.22000
.600	.867	-.45770	-.45657	-.45500	-.45578	.26472	.26558	.26593	.26575	1580.65601	1596.39999
.599	.359	-.41198	-.41112	-.40955	-.41033	.26471	.26454	.26503	.26478	1583.30600	1597.11000
.600	.844	-.36556	-.36501	-.36332	-.36417	.26375	.26381	.26404	.26392	1585.59000	1596.89999
.600	.328	-.31938	-.31944	-.31784	-.31864	.26186	.26193	.26212	.26202	1587.75000	1597.02000
.600	.814	-.27246	-.27238	-.27082	-.27160	.25883	.26010	.26018	.26014	1589.62700	1597.30000
.600	.295	-.24742	-.24483	-.22329	-.22406	.25617	.25724	.25736	.25730	1590.84599	1596.70000
.600	.781	-.17681	-.17631	-.17488	-.17560	.25333	.25444	.25477	.25461	1592.16901	1596.92000
.600	.259	-.12941	-.12976	-.12897	-.12818	.24990	.25090	.25111	.25101	1593.28799	1596.92999
.601	.743	-.08245	-.08289	-.08143	-.08216	.24538	.24646	.24663	.24655	1593.87801	1597.34000
.600	.235	-.03785	-.03807	-.03650	-.03728	.24151	.24239	.24250	.24245	1594.51700	1596.86000
.600	.258	.00481	.00481	.00561	.00561	.23745	.23819	.23838	.23827	1594.52699	1596.75000
.600	.760	.04965	.04879	.05066	.04972	.23398	.23486	.23500	.23493	1595.20900	1597.28000
.600	.250	.09240	.09179	.09350	.09264	.23077	.23192	.23201	.23196	1595.05099	1596.75000
GRADIENT		.09031	.09003	.09005	.09004	-.00597	-.00585	-.00588	-.00586	2.28922	.02360
RN NO.	1471/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	RN NO.	1471/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.800	.935	-.77695	-.77667	-.77549	-.77608	.31402	.31421	.31461	.31441	1308.13499	1341.24001
.800	.421	-.72134	-.72164	-.72039	-.72101	.31222	.31224	.31263	.31244	1312.23000	1341.12000
.800	.912	-.66558	-.66655	-.66495	-.66575	.31170	.31247	.31282	.31264	1315.90100	1341.10001
.800	.407	-.60817	-.60990	-.60848	-.60919	.31112	.31120	.31124	.31202	1319.37700	1340.89000
.800	.902	-.55357	-.55202	-.55197	-.55280	.31112	.31196	.31233	.31214	1322.67500	1341.13000
.801	.395	-.49627	-.49679	-.49546	-.49613	.30989	.31070	.31103	.31087	1325.57001	1341.14000
.800	.886	-.44078	-.44142	-.43997	-.44069	.30970	.30973	.31004	.30988	1327.95500	1341.05000
.800	.379	-.38582	-.38652	-.38513	-.38583	.30742	.30749	.30782	.30766	1330.18800	1341.09000
.800	.896	-.33070	-.33230	-.33096	-.33163	.30565	.30592	.30625	.30609	1332.32401	1341.08000
.800	.2354	-.27582	-.27402	-.27572	-.27487	.30336	.30336	.30354	.30345	1333.93300	1341.07001
.800	.841	-.21899	-.21918	-.21918	-.21838	.30022	.30071	.30108	.30090	1335.30600	1341.03000
.800	.332	-.16350	-.16207	-.16279	-.16279	.29662	.29697	.29731	.29714	1336.47800	1340.99001
.800	.819	-.10925	-.10893	-.10746	-.10820	.29322	.29356	.29393	.29339	1337.44800	1341.05000
.800	.312	-.05548	-.05466	-.05297	-.05382	.28963	.28999	.29025	.29012	1338.01601	1340.95000
.800	.177	-.00184	-.00077	-.00077	-.00077	.28689	.28732	.28745	.28738	1338.50600	1340.87000
.800	.686	.05177	.05107	.05271	.05189	.28506	.28535	.28564	.28549	1338.77100	1341.09000
.800	1.179	.10598	.10464	.10635	.10550	.28196	.28248	.28247	.28247	1338.84500	1341.03999
GRADIENT		.10797	.10813	.10814	.10814	-.00514	-.00516	-.00520	-.00518	2.61231	-.02245

DATE 04 OCT 91

IA31O (AEDC 16TF-783) TABULATED DATA

## IA31O (AEDC 16TF-783) PROBE CALIBRATION

PAGE 798  
(UCM054) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1505 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.500	PHI =	180.000
DPACAL										
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.897	-6.924	-.80555	-.80798	-.80591	-.80694	.32608	.32680	.32644	1240.95500	1274.08000
.901	-6.413	-.75019	-.75248	-.75035	-.75141	.32560	.32614	.32647	1244.98300	1273.32001
.900	-5.901	-.69115	-.69365	-.69144	-.69254	.32277	.32336	.32361	1247.03799	1272.03000
.900	-5.397	-.63535	-.63535	-.63324	-.63430	.32264	.32298	.32322	1250.56200	1272.13000
.899	-4.892	-.57464	-.57672	-.57448	-.57560	.32204	.32303	.32340	1254.59801	1273.17000
.900	-4.384	-.51640	-.51852	-.51618	-.51735	.32188	.32285	.32340	1258.46700	1274.03000
.900	-3.879	-.45884	-.46050	-.45840	-.45945	.32148	.32256	.32276	1260.76100	1273.39999
.901	-3.364	-.40280	-.40314	-.40108	-.40211	.31947	.32046	.32079	.32063	1262.13499
.900	-2.856	-.34443	-.34443	-.34336	-.34440	.31637	.31744	.31782	.31763	1263.09500
.899	-2.344	-.28570	-.28672	-.28461	-.28566	.31437	.31467	.31494	.31480	1265.27499
.900	-1.830	-.22685	-.22783	-.22593	-.22688	.31120	.31176	.31220	.31198	1267.26300
.900	-1.314	-.17117	-.17051	-.16863	-.16957	.30754	.30840	.30867	.30853	1268.50000
.900	-805	-.11389	-.11307	-.11118	-.11212	.30378	.30449	.30498	.30474	1269.37500
.900	-296	-.05827	-.05737	-.05555	-.05646	.30014	.30084	.30119	.30102	1270.13400
.900	-193	-.0355	-.00203	-.00195	-.00199	.29675	.29748	.29781	.29765	1270.54700
.900	.699	.05238	.05182	.05362	.05272	.29406	.29490	.29518	.29504	1270.86501
.900	1.191	.10763	.10714	.10889	.10802	.29116	.29211	.29234	.29223	1271.00999
GRADIENT		.12025	.11247	.11231	.11239	-.00555	-.00558	-.00560	-.00559	-.02454
RUN NO.		1511 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.500	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.899	-6.976	-.82313	-.82552	-.82341	-.82447	.31770	.31671	.31694	.31682	1172.46300
1.00	-6.465	-.76523	-.76780	-.76561	-.76670	.31611	.31509	.31558	.31534	1176.11501
1.00	-5.962	-.70790	-.71062	-.70845	-.70954	.31495	.31474	.31509	.31491	1179.95399
1.00	-5.457	-.65006	-.65250	-.65041	-.65146	.31384	.31368	.31401	.31384	1183.49100
1.00	-4.961	-.59039	-.59254	-.59047	-.59151	.31495	.31483	.31522	.31502	1186.80299
1.00	-4.461	-.53373	-.53494	-.53296	-.53395	.31241	.31257	.31280	.31269	1189.57001
1.00	-3.954	-.47695	-.47650	-.47482	-.47589	.31252	.31293	.31310	.31302	1191.88800
1.00	-3.449	-.41754	-.41880	-.41672	-.41776	.31218	.31262	.31274	.31268	1194.13499
1.00	-2.948	-.35928	-.36008	-.35847	-.35928	.31041	.31070	.31076	.31076	1196.12000
1.00	-2.443	-.30035	-.30156	-.29952	-.30054	.30886	.30913	.30923	.30918	1197.71899
1.00	-1.943	-.24078	-.24273	-.24175	-.24078	.30649	.30690	.30705	.30697	1199.32100
1.00	-1.441	-.18355	-.18456	-.18355	-.18457	.30509	.30484	.30507	.30496	1200.31900
1.00	-939	-.12857	-.12811	-.12633	-.12722	.30232	.30195	.30212	.30203	1201.23500
1.00	-442	-.07099	-.06934	-.07016	-.07016	.30160	.30135	.30158	.30147	1202.03101
1.00	.050	-.01636	-.01609	-.01520	-.01520	.30011	.30027	.30031	.30029	1202.51500
1.00	.562	.04003	.03896	.04058	.03977	.30137	.30150	.30147	.30149	1202.71700
1.00	1.063	.09710	.09606	.09786	.09696	.30074	.30089	.30087	.30088	1202.83099
1.00	1.1464	.11458	.11464	.11461	.11461	-.00265	-.00269	-.00273	-.00271	.05244

## PARAMETRIC DATA

	RUN NO.	1527/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	2.500	PHI =	180.000	PTTF
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	.35898	1149.42599	1182.55200	PT2F
ALPHA	-.89249	-.89374	-.89190	-.89282	-.35919	.35909	.35590	.35578	1153.89301	1182.87000		
	-.83146	-.83241	-.83015	-.83128	.35498	.35549	.35608	.35373	1157.91000	1182.55600		
	-.76933	-.77038	-.76802	-.76920	.35250	.35339	.35407	.35251	1161.49400	1182.53000		
	-.70530	-.70729	-.70479	-.70604	.35135	.35220	.35283	.35086	1164.32500	1182.36900		
	-.5.417	-.70530	-.70729	-.70479	.34977	.35056	.35117	.34926	1166.41701	1182.26700		
	-.4.916	-.63883	-.64080	-.63827	.34954	.34800	.34890	.34990	1168.51300	1182.51500		
	-.4.408	-.57255	-.57514	-.57272	.34793	.34932	.34814	.34908	1170.83099	1182.61301		
	-.3.898	-.50915	-.51061	-.50821	.34941	.34781	.34566	.34781	1173.04700	1182.55499		
	-.3.391	-.44505	-.44684	-.44448	.34823	.34721	.34753	.34809				
	-.2.882	-.38193	-.38345	-.38101	.34823	.34721	.34753	.34809				
	-.2.372	-.31856	-.31965	-.31731	.34848	.34325	.34378	.34419				
	-.1.868	-.25482	-.25544	-.25315	.34793	.34530	.34543	.34000				
	-.1.356	-.19288	-.19312	-.19106	.34793	.34530	.34543	.34057				
	-.848	-.13046	-.13004	-.12777	.34793	.34530	.34543	.34057				
	-.343	-.06942	-.06842	-.06739	.34793	.34530	.34543	.34057				
	-.146	-.00998	-.00734	-.00797	.34793	.34530	.34543	.34057				
	.654	.05239	.05246	.05338	.34793	.34530	.34543	.34057				
	1.149	.11555	.11456	.11634	.34793	.34530	.34543	.34057				
	1.250	.12428	.12413	.12420	.34793	.34530	.34543	.34057				
	GRADIENT	.12380										
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	.34961	1168.51300	1182.51500	PT2F
ALPHA	-.02416	-.02687	-.02484	-.02585	.41553	.41359	.41428	.41394	1130.22000	1163.88400		
	-.95210	-.95498	-.95293	-.95396	.41481	.41295	.41375	.41335	1134.06900	1164.09200		
	-.5.929	-.80666	-.88364	-.88172	.41226	.41056	.41105	.41081	1138.63699	1164.57500		
	-.5.422	-.80854	-.80752	-.80861	.40883	.40709	.40763	.40736	1141.20000	1163.92500		
	-.4.918	-.73522	-.73729	-.73612	.40497	.40472	.40543	.40503	1144.90500	1164.49899		
	-.4.416	-.66498	-.66658	-.66436	.40561	.40550	.40597	.40573	1147.42400	1163.91100		
	-.3.911	-.59193	-.59285	-.59105	.40754	.40731	.40784	.40758	1150.35001	1164.57001		
	-.3.406	-.51889	-.51742	-.51849	.40404	.40393	.40450	.40422	1152.88901	1164.10699		
	-.2.893	-.44409	-.44295	-.44397	.40230	.40216	.40282	.40249	1154.60201	1164.06200		
	-.2.387	-.37026	-.37075	-.36860	.39813	.39796	.39858	.39827	1156.57401	1164.33900		
	-.1.880	-.29587	-.29736	-.29532	.39388	.39387	.39444	.39416	1158.05200	1164.41600		
	1.400	-.1.366	-.2.2296	-.2.2218	.38777	.38830	.38804	.38804	1158.34700	1164.03900		
	1.400	-.863	-.15227	-.15123	.38313	.38311	.38385	.38348	1158.83800	1163.84801		
	1.400	-.359	-.08158	-.07918	.38134	.38147	.38195	.38165	1159.91299	1164.62801		
	1.399	-.132	-.01237	-.01148	.37722	.37732	.37777	.37755	1160.12801	1164.11000		
	1.400	.639	.05622	.05789	.37562	.37547	.37583	.37565	1160.00301	1163.86800		
	1.400	1.134	.12734	.12724	.37321	.37332	.37366	.37349	1160.81300	1164.78900		
	GRADIENT	.14296	.14320	.14316	.00629	.00628	.00628	.00626	2.48950	.00546		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 800

(UCMC54) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1561/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.500	PHI =	180.000
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.450	-6.907	-1.07974	-1.08205	-1.08001	-1.08103	.45017	.45023	.45097	.45060	.1124.12801
1.450	-6.392	-1.00430	-1.00727	-1.00547	-1.00637	.44968	.45001	.45082	.45041	.1127.32001
1.450	-5.882	-93151	-93393	-93185	-93289	.44730	.44778	.44856	.44817	.1131.41800
1.450	-5.371	-85145	-85354	-85141	-85248	.43969	.43997	.44091	.44044	.1133.80299
1.450	-4.869	-77247	-77247	-77209	-77319	.44055	.44092	.44186	.44139	.1136.38901
1.449	-4.360	-69869	-70143	-69931	-70037	.43994	.44026	.44121	.44074	.1139.57100
1.450	-3.846	-62445	-62714	-62483	-62598	.44295	.44282	.44358	.44320	.1142.73900
1.450	-3.331	-54576	-54928	-54722	-54825	.44240	.44216	.44298	.44257	.1145.60699
1.450	-2.816	-46615	-46897	-46679	-46788	.43962	.43796	.43895	.43846	.1147.43100
1.450	-2.304	-38625	-38868	-38660	-38764	.43547	.43372	.43460	.43416	.1149.42599
1.450	-1.784	-30728	-30863	-30664	-30763	.42986	.42808	.42891	.42850	.1150.10800
1.449	-1.267	-23007	-23148	-22949	-23048	.42121	.41955	.42032	.41993	.1150.60201
1.451	-755	-15418	-15356	-15170	-15263	.41581	.41409	.41484	.41447	.1151.53200
1.450	-246	-07929	-07860	-07674	-07767	.41065	.40908	.40970	.40939	.1151.85800
1.450	-245	-00595	-00456	-00457	-00457	.40453	.40355	.40394	.40375	.1151.95799
1.450	-749	-06898	-06828	-07019	-06923	.40056	.39913	.39979	.39946	.1152.69800
1.450	1.238	-14240	-14208	-14365	-14287	.39522	.39374	.39423	.39398	.1152.45300
	GRADIENT	-15039	-15099	-15082	-15091	-.000838	-.00867	-.00875	-.00875	-.001198
RUN NO.	1646/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.470	-6.918	-1.10657	-1.10288	-1.10181	-1.10235	.45996	.45653	.45711	.45682	.1110.17700
1.471	-6.398	-1.02690	-1.02643	-1.02597	-1.02643	.45966	.45631	.45692	.45661	.1113.20100
1.470	-5.895	-95331	-95117	-94981	-95049	.46022	.45664	.45715	.45690	.1116.89600
1.470	-5.385	-87801	-87606	-87505	-87556	.45681	.45359	.45407	.45383	.1120.98399
1.470	-4.881	-79707	-79570	-79459	-79514	.45289	.45105	.45157	.45131	.1124.55499
1.470	-4.369	-71594	-71411	-71209	-71310	.45031	.44866	.44918	.44892	.1126.13400
1.471	-3.862	-63526	-63361	-63236	-63299	.44839	.44658	.44707	.44683	.1127.73599
1.470	-3.347	-55730	-55507	-55383	-55445	.44691	.44599	.44660	.44629	.1130.75000
1.470	-2.830	-47717	-47432	-47282	-47357	.44348	.44256	.44339	.44297	.1132.65100
1.470	-2.320	-39519	-39291	-39141	-39216	.43858	.43774	.43843	.43809	.1134.16600
1.484	-1.804	-31315	-31113	-311258	-311186	.43292	.43206	.43259	.43233	.1135.25101
1.484	-1.291	-23393	-23315	-23237	-23315	.42501	.42450	.42516	.42483	.1136.04700
1.484	-777	-15549	-15409	-15478	-15478	.41928	.41851	.41898	.41875	.1135.92300
1.470	-267	-07846	-07875	-07711	-07793	.41310	.41285	.41336	.41311	.1135.82201
1.484	-225	-00419	-00375	-00398	-00386	.40911	.40881	.40913	.40897	.1136.05701
1.470	-728	-06929	-06875	-06950	-06946	.40433	.40397	.40433	.40415	.1136.67500
1.484	1.219	-14235	-14303	-14224	-14224	.39836	.39793	.39836	.39815	.1136.91000
	GRADIENT	-15389	-15384	-15387	-15387	-.00944	-.00920	-.00923	-.00921	-.00923

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

## PARAMETRIC DATA

	RUN NO.	1596 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.500	PHI =	180.000	PTTF
<b>MACH</b>											
ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPBF	DPBF	PT2F
-6.926	-1.16705	-1.16481	-1.16346	-1.16414	.48975	.48774	.48835	.48805	1105.38200	1144.54108	
-6.404	-1.08981	-1.08740	-1.08592	-1.08666	.48650	.48436	.48503	.48470	1108.82800	1144.90733	
-5.902	-1.00987	-1.00826	-1.00671	-1.00748	.48486	.48279	.48361	.48320	1111.31799	1145.50938	
-5.493	-9.3722	-9.3493	-9.3332	-9.3413	.48882	.48728	.48790	.48759	1114.64000	1145.38208	
-5.392	-8.85696	-8.5482	-8.5305	-8.5394	.48914	.48767	.48835	.48801	1117.52901	1145.35728	
-4.888	-7.74448	-7.7296	-7.7137	-7.7217	.49208	.49004	.49059	.49032	1119.79401	1145.32823	
-4.378	-6.9108	-6.8999	-6.8853	-6.8926	.49218	.49015	.49074	.49045	1121.97701	1145.73048	
-3.865	-6.0536	-6.0499	-6.0323	-6.0411	.49003	.48840	.48895	.48868	1123.65700	1145.09753	
-3.357	-5.2016	-5.1774	-5.1603	-5.1688	.48665	.48518	.48561	.48540	1125.29300	1145.47383	
-2.844	-4.33380	-4.3185	-4.3007	-4.3096	.48571	.48345	.48398	.48371	1126.60300	1145.66405	
-2.331	-3.4717	-3.4617	-3.4429	-3.4523	.47974	.47782	.47818	.47800	1125.74300	1142.96214	
-1.818	-2.6181	-2.6221	-2.6023	-2.6122	.47642	.47421	.47446	.47446	1126.99600	1143.68871	
-1.301	-1.7560	-1.7642	-1.7443	-1.7543	.47064	.46862	.46896	.46879	1125.12900	1142.44374	
-1.493	-0.9129	-0.9177	-0.9017	-0.9097	.46620	.46409	.46446	.46427	1126.03600	1144.54247	
-0.283	-0.0763	-0.0834	-0.0771	-0.0771	.46169	.45978	.46026	.46002	1127.67200	1144.93132	
-0.208	.07663	.07519	.07616	.07533	.45370	.45369	.45369	.45369	1128.00800	1145.25507	
.716	.16015	.15927	.16101	.16014	.44866	.44742	.44750	.44746	1128.10800	1145.15971	
1.493	1.208	.16659	.16660	.16660	-.00713	-.00711	-.00719	-.00715	1.45223	-.15787	
<b>GRADIENT</b>											
<b>MACH</b>											
ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPBF	DPBF	PT2F
-6.923	-1.33279	-1.32726	-1.32657	-1.32657	.55311	.55052	.55157	.55104	1110.78000	1138.89436	
-6.409	-1.24999	-1.24415	-1.24359	-1.24387	.55141	.54868	.54999	.54934	1114.57600	1137.97870	
-5.899	-1.16384	-1.15923	-1.15764	-1.15843	.55045	.54807	.54941	.54874	1116.98500	1137.17598	
-5.391	-1.06086	-1.05755	-1.05594	-1.05675	.55100	.54842	.54971	.54907	1119.14500	1137.04761	
-4.890	-0.96082	-0.95787	-0.95643	-0.95715	.54994	.54709	.54853	.54781	1121.55400	1137.59941	
-4.378	-0.86739	-0.86257	-0.86121	-0.86189	.54840	.54517	.54668	.54592	1122.99899	1139.03682	
-3.870	-0.78315	-0.77875	-0.77729	-0.77802	.55328	.55094	.55174	.55134	1124.28500	1139.90485	
-3.357	-0.69506	-0.69216	-0.69063	-0.69139	.55804	.55591	.55661	.55626	1125.86400	1140.17281	
-2.844	-0.59995	-0.59724	-0.59537	-0.59631	.55447	.55249	.55333	.55291	1126.81400	1138.79247	
-2.331	-0.49549	-0.49371	-0.49371	-0.49460	.54531	.54294	.54415	.54355	1127.27499	1137.35115	
-1.814	-0.39526	-0.39234	-0.39068	-0.39151	.53512	.53248	.53327	.53288	1127.73500	1136.53453	
-1.300	-0.29326	-0.29204	-0.29111	-0.29111	.52208	.51944	.52015	.51980	1128.88699	1136.95930	
-1.517	-0.788	-0.9171	-0.9007	-0.9102	.50972	.50728	.50785	.50757	1130.04300	1137.64180	
1.517	-2.844	-0.9603	-0.9380	-0.9467	.50412	.50167	.50208	.50187	1130.80200	1138.04865	
1.516	-2.331	-0.0282	-0.00257	-0.00248	.49645	.49424	.49471	.49447	1131.50800	1138.68596	
1.516	-1.209	.08920	.08885	.09060	.08972	.49131	.48951	.48932	1132.29401	1139.19214	
1.517	.714	.18168	.18080	.18293	.18187	.48499	.48493	.48471	1132.76401	1139.69131	
1.517	1.209	.18956	.18868	.18870	.18869	-.01262	-.01258	1.78532	-.00910		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 161E-783) PROBE CALIBRATION

1116061 01 OCT 81

PARAMETERIC DATA

	RUN NO.	1627 / O	R/N/L =	2 . 49	GRADIENT INTERVAL =	- 5 . 00 /	5 . 00
MACH	ALPHA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1
1.541	-6 . 920	-1 . 28021	-1 . 27531	-1 . 27397	-1 . 27464	.54406	.54091
1.541	-6 . 406	-1 . 15561	-1 . 15059	-1 . 14888	-1 . 14974	.52907	.52530
1.541	-5 . 899	-1 . 03819	-1 . 03468	-1 . 03316	-1 . 03392	.51746	.51435
1.541	-5 . 391	-1 . 92369	-1 . 92136	-1 . 91957	-1 . 92046	.50477	.50134
1.541	-4 . 888	-8 . 16553	-8 . 14048	-8 . 12327	-8 . 11323	.49290	.48929
1.541	-4 . 377	-7 . 15442	-7 . 12443	-7 . 10227	-7 . 1135	.47992	.47611
1.541	-3 . 865	-6 . 18552	-6 . 15831	-6 . 1400	-6 . 1490	.46272	.45916
1.541	-3 . 358	-5 . 22023	-5 . 25117	-5 . 2008	-5 . 2106	.44344	.44059
1.541	-2 . 843	-4 . 39115	-4 . 3600	-4 . 3403	-4 . 3501	.42495	.42218
1.541	-2 . 329	-3 . 52324	-3 . 5104	-3 . 4909	-3 . 5007	.40265	.40103
1.541	-1 . 818	-2 . 6433	-2 . 6519	-2 . 6234	-2 . 6334	.37991	.37639
1.541	-1 . 301	-1 . 18697	-1 . 18712	-1 . 18524	-1 . 18618	.35735	.35623
1.541	-790	-1 . 11769	-1 . 11735	-1 . 11538	-1 . 11636	.34318	.34310
1.541	-282	-0 . 05039	-0 . 04835	-0 . 05019	-0 . 04927	.33534	.33537
1.541	-210	-0 . 01230	-0 . 01162	-0 . 01361	-0 . 01261	.32784	.32761
1.541	-713	.07496	.07412	.07619	.07516	.32365	.32325
1.541	1 . 205	.13960	.13871	.14079	.13975	.31685	.31625
1.541	15521	.15518	.1551	.15519	.15519	.03144	.03073
GRADIENT	15592					.03081	.03077
						.29145	.29145
						.0400	.0400

## PARAMETRIC DATA

	RUN NO.	1581/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	3.000	PHI =	180.000	PT2F		
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F			
.600	.6 .892	-.64617	-.64556	-.64409	-.64483	.31340	.31355	.1566	.69501	.1597	.28999		
.599	-.6 .376	-.59884	-.59837	-.59765	-.59693	.31192	.31241	.31217	.1570	.02000	.1597	.14999	
.600	-.5 .870	-.55142	-.55109	-.54954	-.55031	.31119	.31201	.31229	.1573	.50999	.1597	.48000	
.600	-.5 .357	-.50329	-.50238	-.50090	-.50164	.31115	.31198	.31226	.1576	.86501	.1596	.99001	
.599	-.4 .847	-.45654	-.45563	-.45410	-.45487	.31092	.31114	.31103	.1579	.77699	.1597	.37000	
.600	-.4 .334	-.40795	-.40692	-.40549	-.40621	.31059	.31077	.31106	.1582	.11501	.1596	.84000	
.600	-.3 .827	-.36313	-.36237	-.36097	-.36167	.30754	.30750	.30774	.1584	.92300	.1597	.31000	
.600	-.3 .307	-.31730	-.31776	-.31618	-.31697	.30751	.30748	.30762	.1586	.46800	.1597	.13000	
.600	-.2 .794	-.27107	-.27098	-.26961	-.27029	.30587	.30611	.30643	.1588	.33501	.1596	.80000	
.600	-.2 .279	-.22371	-.22374	-.22306	-.22306	.30340	.30339	.30360	.1589	.95799	.1596	.84000	
.600	-.1 .762	-.17650	-.17596	-.17447	-.17522	.29900	.29981	.29990	.1591	.35400	.1597	.53999	
.600	-.1 .250	-.13041	-.13041	-.12899	-.12970	.29487	.29565	.29570	.1592	.16100	.1596	.67999	
.600	-.737	-.08227	-.08271	-.08104	-.08188	.29250	.29351	.29361	.1593	.04401	.1596	.95000	
.600	-.232	-.03798	-.03708	-.03556	-.03632	.28803	.28898	.28909	.1593	.71201	.1597	.17000	
.600	.262	.00645	.00569	.00713	.00641	.28426	.28531	.28551	.1594	.87000	.1597	.00999	
.600	.766	.05196	.05135	.05318	.05226	.28174	.28275	.28276	.1594	.40401	.1597	.21001	
.600	1.258	.09520	.09497	.09579	.09022	.27818	.27923	.27933	.1594	.23599	.1596	.83000	
	GRADIENT	.09043	.09019			.09020	-.00568	-.00546					
	RUN NO.	1472/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00							
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F			
.800	-.6 .927	-.77409	-.77361	-.77429	-.77444	.37061	.37105	.37083	.1306	.91200	.1341	.14999	
.800	-.6 .405	-.72110	-.72005	-.72072	-.72050	.36750	.36799	.36774	.1311	.06000	.1341	.09000	
.800	-.5 .903	-.66550	-.66639	-.66486	-.66563	.36823	.36792	.36851	.36821	.81799	.1341	.17000	
.800	-.5 .395	-.60820	-.60935	-.60775	-.60855	.36718	.36701	.36721	.36711	.19400	.1341	.02000	
.800	-.4 .889	-.55154	-.55136	-.55210	-.55120	.36682	.36690	.36700	.36679	.15050	.1341	.07001	
.800	-.4 .380	-.49494	-.49286	-.49363	-.49363	.36620	.36604	.36654	.36584	.42400	.1340	.92000	
.800	-.3 .871	-.43951	-.44022	-.43879	-.43951	.36423	.36423	.36372	.36398	.1326	.83900	.1340	.82001
.800	-.3 .364	-.38437	-.38349	-.38431	-.38431	.36219	.36242	.36192	.36217	.37700	.1341	.07001	
.800	-.2 .854	-.33026	-.33057	-.32978	-.32978	.36097	.36120	.36067	.36093	.32201	.1340	.98000	
.800	-.2 .345	-.27327	-.27386	-.27311	-.27311	.35788	.35848	.35862	.35855	.10800	.1341	.03000	
.800	-.1 .832	-.21677	-.21677	-.21760	-.21760	.35552	.35583	.35612	.35597	.1334	.52901	.1341	.07001
.800	-.1 .323	-.16320	-.16320	-.16240	-.16240	.35259	.35284	.35310	.35297	.1335	.73500	.1341	.00999
.800	-.812	-.10755	-.10592	-.10674	-.10674	.34899	.34968	.35002	.34985	.1336	.67200	.1341	.02000
.800	-.308	-.05433	-.05270	-.05351	-.05351	.34681	.34679	.34703	.34691	.1337	.39700	.1340	.83000
.800	.181	-.00108	-.00004	-.00011	-.00004	.34347	.34374	.34397	.34386	.1337	.85400	.1340	.98000
.800	.689	.05375	.05308	.05472	.05390	.34009	.34100	.34104	.34102	.1338	.33000	.1341	.14000
.800	1.185	.10784	.10648	.10823	.10736	.33840	.33903	.33925	.33914	.1338	.36400	.1341	.00000
	GRADIENT	.10841	.10836	.10839		-.00489	-.00487	-.00487					

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 804

(UCM055) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.899	-6.916	-.80342	-.80598	-.80375	-.80487	.38469	.38327	.38415	1238.97400	1272.85001
.900	-6.396	-.74650	-.74880	-.74663	-.74771	.38577	.38444	.38499	1242.80200	1273.05000
.900	-5.892	-.69021	-.69313	-.69086	-.69199	.38234	.38170	.38244	1246.73900	1273.02000
.900	-5.389	-.63160	-.63377	-.63166	-.63272	.38282	.38269	.38335	1250.42400	1273.16000
.900	-4.879	-.57359	-.57356	-.57356	-.57461	.38094	.38088	.38148	1253.41299	1272.89999
.900	-4.369	-.51481	-.51633	-.51403	-.51518	.37917	.37916	.37986	1256.60001	1273.13000
.900	-3.863	-.45744	-.45901	-.45700	-.45801	.37782	.37765	.37827	1258.95200	1272.89000
.900	-3.353	-.40050	-.40090	-.39892	-.39991	.37590	.37573	.37652	1261.50101	1272.97000
.900	-2.841	-.34257	-.34395	-.34176	-.34285	.37377	.37368	.37430	1263.32800	1272.88000
.900	-2.331	-.28411	-.28527	-.28313	-.28420	.37130	.37147	.37204	1265.10500	1272.92999
.900	-1.818	-.22645	-.22717	-.22524	-.22621	.36816	.36824	.36874	1266.59300	1272.99001
.900	-1.308	-.16940	-.16958	-.16754	-.16856	.36460	.36561	.36506	1267.62399	1273.03000
.900	-801	-.11303	-.11215	-.11012	-.11114	.36179	.36232	.36177	1268.72900	1273.19000
.900	-294	-.05714	-.05628	-.05424	-.05526	.35784	.35863	.35888	1269.46800	1272.91000
.900	-197	-.00102	-.00038	-.00026	-.00032	.35517	.35558	.35591	1269.91400	1272.91000
.900	-703	.05460	.05404	.05573	.05488	.35210	.35297	.35308	1270.25000	1272.95000
.900	1.196	.11094	.11033	.11179	.11106	.35012	.35058	.35087	1270.45100	1273.03999
	GRADIENT	.11246	.11265	.11273	.11281	-.000537	-.00521	-.00533	-.00527	.00608
	RUN NO.	1506/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00			
	RUN NO.	1512/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00			
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.099	-6.970	-.82274	-.82067	-.82171	.37947	.37695	.37758	.37726	1171.27800	1204.61000
1.099	-6.460	-.76679	-.76471	-.76575	.37721	.37507	.37538	.37522	1175.06400	1204.75301
1.100	-5.957	-.70818	-.71099	-.70879	.37435	.37235	.37288	.37261	1178.12000	1204.87700
1.100	-5.457	-.65228	-.65011	-.65120	.37330	.37184	.37230	.37207	1182.36301	1204.61099
1.100	-4.955	-.59166	-.59405	-.59206	.37171	.37113	.37165	.37139	1185.53999	1204.54401
1.100	-4.453	-.53204	-.53356	-.53134	.37172	.37091	.37142	.37116	1188.57300	1204.53500
1.100	-3.953	-.47537	-.47350	-.47460	.37149	.37100	.37139	.37120	1190.97099	1204.61000
1.100	-3.447	-.41772	-.41878	-.41654	.37056	.36970	.37004	.36987	1193.33200	1204.64301
1.100	-2.945	-.35909	-.35980	-.35910	.36887	.36806	.36831	.36819	1195.27699	1204.54900
1.100	-2.439	-.29831	-.29996	-.29783	.36889	.36856	.36778	.36797	1196.99001	1204.76401
1.100	-1.939	-.24169	-.24305	-.24104	.36205	.36589	.36632	.36564	1198.61200	1204.72301
1.100	-1.436	-.18449	-.18306	-.18424	.36247	.36289	.36207	.36248	1199.41800	1204.57600
1.100	-934	-.12660	-.12681	-.12475	.36094	.36148	.36082	.36115	1200.51601	1204.65199
1.100	-441	-.07070	-.07083	-.06908	.36996	.35935	.35978	.35957	1201.28900	1204.75900
1.100	057	-.01441	-.01223	-.01323	.35925	.35953	.35929	.35941	1201.82600	1204.75301
1.100	.567	.04270	.04152	.04238	.35870	.35898	.35896	.35897	1202.15800	1204.81799
1.100	1.063	.09938	.09857	.10022	.09940	.35860	.35911	.35905	1202.36000	1204.78500
	GRADIENT	.11484	.11503	.11497	.11500	-.00272	-.00247	-.00262	-.00255	.2.72910

## PARAMETRIC DATA

BETA = - 5.00/ 5.00

BUN No. 1545/8 BN/l = 2.58 GRADIENT INTERVAL = -5.88/5.00

	MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2
ALPHA	-6.942	-1.02151	-1.02462	-1.02240	-1.02351	.49070	.48864	.48936
.400	-6.424	-.94956	-.95255	-.95041	-.95148	.48948	.48842	.48842
.400	-5.921	-.87869	-.88165	-.87965	-.88065	.48632	.48632	.48760
.400	-5.413	-.80789	-.80900	-.80688	-.80794	.48212	.48112	.48212
.400	-4.913	-.73454	-.73593	-.73370	-.73482	.47969	.47896	.47971
.400	-4.405	-.66120	-.66304	-.66092	-.66198	.47740	.47679	.47736
.400	-3.900	-.59016	-.59149	-.58940	-.59044	.47672	.47629	.47687
.400	-3.392	-.51913	-.51914	-.51686	-.51800	.47551	.47547	.47596
.399	-2.885	-.44389	-.44407	-.44214	-.44311	.47416	.47370	.47426
.400	-2.377	-.36855	-.36928	-.36725	-.36827	.47179	.47169	.47219
.399	-1.869	-.29468	-.29618	-.29417	-.29517	.46629	.46614	.46687
.400	-1.363	-.22241	-.22342	-.22137	-.22239	.46228	.46210	.46265
.399	-857	-.14990	-.15005	-.14816	-.14910	.45807	.45774	.45825
.400	-353	-.07840	-.07921	-.07717	-.07819	.45413	.45425	.45438
.400	135	-.00971	-.00900	-.00757	-.00829	.45031	.45027	.45050
.400	643	.06173	.06102	.06272	.06187	.44827	.44844	.44844
.400	141	.13129	.13121	.13260	.13190	.44600	.44641	.44664
		GRADIENT	14352	14373	14367	.00608	.00594	.00602

OCT 91

(UCM055) (04 OCT 91)

DADAMETRIC DATA

RUN NO.	1562 / 0	RN/L =	2.50	GRADIENT INTERVAL =	- 5.00 /	5.00
MACH	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2
ALPHA	- 1.07875	- 1.08095	- 1.07907	- 1.08001	.52659	.52604
1.450	- 1.00325	- 1.00583	- 1.00382	- 1.00483	.52599	.52608
1.449	- .92837	- .93130	- .92905	- .93018	.52421	.52440
1.449	- .85118	- .85302	- .85096	- .85199	.52056	.52078
1.450	- .77205	- .77369	- .77164	- .77266	.51634	.51587
1.450	- .69422	- .69694	- .69482	- .69588	.51506	.51450
1.450	- .62350	- .62128	- .61980	- .62239	.51523	.51485
1.450	- .54272	- .54638	- .54412	- .54525	.51465	.51445
1.450	- .46403	- .46675	- .46474	- .46574	.51279	.51247
1.450	- .38375	- .38624	- .38413	- .38519	.51036	.51032
1.450	- .30785	- .30931	- .30732	- .30832	.50702	.50519
1.449	- .23029	- .23084	- .22891	- .22988	.49955	.49761
1.450	- .15147	- .15123	- .14921	- .15022	.49313	.49138
1.450	- .07611	- .07687	- .07447	- .07529	.48732	.48572
1.449	- .00176	- .00054	- .00066	- .00066	.48152	.48087
1.449	.07347	.07288	.07467	.07378	.47772	.47663
1.450	.14738	.14691	.14857	.14774	.47395	.47318
1.450	.15106	.15168	.15153	.15161	.00788	.00794
GRADIENT					.00791	.00791
						.05561

49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPACAL		DPA1		DPA2		DPBCAL		DPA		DPB1		DPB2		DPB		P11	
		DPA1	DPA2	P11	P12														
-6.903	-1.470	-1.10005	-1.09955	-1.09905	-1.09905	-1.02287	-1.02287	-1.02421	-1.02421	-1.02682	-1.02682	-1.03555	-1.03555	-1.03555	-1.03555	-1.03555	-1.03555	1.149	4.7725
-6.386	-1.484	-1.02421	-1.02354	-1.02287	-1.02287	-1.02421	-1.02421	-1.02682	-1.02682	-1.03555	-1.03555	-1.03555	-1.03555	-1.03555	-1.03555	-1.03555	-1.03555	1.166	7.9232
-5.881	-1.471	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	-1.09443	1.148	7.6324
-5.369	-1.471	-1.07137	-1.07076	-1.07137	-1.07076	-1.07137	-1.07076	-1.07293	-1.07293	-1.07293	-1.07293	-1.07293	-1.07293	-1.07293	-1.07293	-1.07293	-1.07293	1.148	5.5448
-4.862	-1.470	-1.09552	-1.09288	-1.09399	-1.09288	-1.09552	-1.09288	-1.12669	-1.12669	-1.12669	-1.12669	-1.12669	-1.12669	-1.12669	-1.12669	-1.12669	-1.12669	1.149	0.716
-4.350	-1.471	-1.071440	-1.071070	-1.071440	-1.071070	-1.071440	-1.071070	-1.071440	-1.071440	-1.071440	-1.071440	-1.071440	-1.071440	-1.071440	-1.071440	-1.071440	-1.071440	1.149	0.6433
-3.845	-1.470	-1.063474	-1.063179	-1.063474	-1.063179	-1.063474	-1.063179	-1.063474	-1.063474	-1.063474	-1.063474	-1.063474	-1.063474	-1.063474	-1.063474	-1.063474	-1.063474	1.149	1.3917
-3.331	-1.470	-1.055641	-1.055274	-1.055641	-1.055274	-1.055641	-1.055274	-1.055641	-1.055641	-1.055641	-1.055641	-1.055641	-1.055641	-1.055641	-1.055641	-1.055641	-1.055641	1.149	8.9501
-2.817	-1.471	-1.047564	-1.047224	-1.047564	-1.047224	-1.047564	-1.047224	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	1.148	9.4048
-2.306	-1.471	-1.047564	-1.047224	-1.047564	-1.047224	-1.047564	-1.047224	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	-1.047564	1.149	8.0744
-1.791	-1.470	-1.031371	-1.031221	-1.031371	-1.031221	-1.031371	-1.031221	-1.031371	-1.031371	-1.031371	-1.031371	-1.031371	-1.031371	-1.031371	-1.031371	-1.031371	-1.031371	1.149	3.5557
-1.281	-1.471	-1.023441	-1.023362	-1.023441	-1.023362	-1.023441	-1.023362	-1.023441	-1.023441	-1.023441	-1.023441	-1.023441	-1.023441	-1.023441	-1.023441	-1.023441	-1.023441	1.148	8.5559
-0.769	-1.471	-1.015422	-1.015268	-1.015422	-1.015268	-1.015422	-1.015268	-1.015422	-1.015422	-1.015422	-1.015422	-1.015422	-1.015422	-1.015422	-1.015422	-1.015422	-1.015422	1.149	6.926
0.263	-1.471	-1.007728	-1.007757	-1.007728	-1.007757	-1.007728	-1.007757	-1.007728	-1.007728	-1.007728	-1.007728	-1.007728	-1.007728	-1.007728	-1.007728	-1.007728	-1.007728	1.149	3.0552
0.228	-1.470	-1.000084	-1.001167	-1.000084	-1.001167	-1.000084	-1.001167	-1.000084	-1.000084	-1.000084	-1.000084	-1.000084	-1.000084	-1.000084	-1.000084	-1.000084	-1.000084	1.149	2.3079
0.734	-1.471	-1.007164	-1.007324	-1.007164	-1.007324	-1.007164	-1.007324	-1.007164	-1.007164	-1.007164	-1.007164	-1.007164	-1.007164	-1.007164	-1.007164	-1.007164	-1.007164	1.149	4.0288
1.228	-1.470	-1.014729	-1.014776	-1.014729	-1.014776	-1.014729	-1.014776	-1.014729	-1.014729	-1.014729	-1.014729	-1.014729	-1.014729	-1.014729	-1.014729	-1.014729	-1.014729	1.149	6.1338
1.5517	GRADIENT	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-1.015456	-0.00884	0.0462

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM055) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1597/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA A =	3.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.493	-6.910	-1.16270	-1.16047	-1.15971	.57135	.56991	.57079	.57035	1105.12000	1145.08565
1.493	-6.393	-1.08815	-1.08537	-1.08459	.56914	.56767	.56833	.56800	1108.70799	1145.18886
1.493	-5.886	-1.00497	-1.00337	-1.00258	.56913	.56765	.56831	.56798	1111.15700	1145.22351
1.493	-5.381	-9.2902	-9.2670	-9.2514	.57121	.56964	.57042	.57003	1113.30701	1144.80016
1.493	-4.868	-8.5056	-8.4803	-8.4650	.57314	.57185	.57255	.57220	1115.95100	1143.91989
1.493	-4.363	-7.6770	-7.6619	-7.6462	.57134	.56984	.57068	.57026	1117.53000	1143.43346
1.494	-3.856	-6.8572	-6.8501	-6.8324	.57126	.57066	.57096	.57096	1118.94099	1142.59163
1.493	-3.344	-6.0257	-6.0235	-6.0050	.57124	.56997	.57055	.57026	1120.15401	1142.27242
1.493	-2.830	-5.1658	-5.1401	-5.1216	.56723	.56853	.56770	.56747	1123.33200	1144.66731
1.493	-2.316	-4.3002	-4.2793	-4.2627	.56617	.56493	.56559	.56526	1125.57300	1145.15323
1.493	-1.804	-3.4361	-3.4260	-3.4081	.56169	.56056	.56098	.56077	1126.74800	1145.16322
1.493	-1.292	-2.5783	-2.5845	-2.5657	.55734	.55616	.55659	.55637	1127.42999	1145.20956
1.493	-784	-1.17102	-1.17161	-1.16973	.55207	.55281	.55260	.55233	1127.47701	1144.40800
1.493	-279	-0.8749	-0.8814	-0.8636	.54735	.54526	.54620	.54573	1127.06400	1143.55878
1.493	-214	-0.00330	-0.00397	-0.00357	.00377	.00424	.04044	.04131	.54087	1126.40601
1.493	.720	.07978	.07850	.08047	.07948	.53610	.53421	.53452	.53436	1126.02299
1.493	1.213	.16400	.16275	.16494	.16385	.53261	.53058	.53086	.53072	1127.75000
1.493	GRADIENT	.16719	.16661	.16661	.00701	-.00713	-.00716	-.00714	1.88574	-.03491

	RUN NO.	1613/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA A =	3.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.516	-6.909	-1.31919	-1.31446	-1.31322	-1.31384	.64514	.64302	.64407	.64354	1108.73399
1.517	-6.393	-1.24262	-1.23641	-1.23582	-1.23611	.64535	.64315	.64416	.64365	1113.05800
1.517	-5.885	-1.15277	-1.14813	-1.14647	-1.14730	.64852	.64556	.64668	.64612	1115.67799
1.516	-5.383	-1.05829	-1.05467	-1.05321	-1.05394	.64893	.64631	.64722	.64676	1118.26500
1.516	-4.870	-9.5869	-9.5538	-9.5382	-9.5460	.64379	.64112	.64198	.64155	1120.12400
1.517	-4.359	-8.5945	-8.5497	-8.5327	-8.5412	.63969	.63789	.63853	.63821	1121.22099
1.516	-3.852	-7.7047	-7.6622	-7.6460	-7.6541	.63794	.63572	.63627	.63600	1121.22099
1.517	-3.344	-6.8685	-6.8364	-6.8200	-6.8282	.64483	.64149	.64246	.64197	1122.23900
1.516	-2.829	-5.9425	-5.9186	-5.8999	-5.9093	.64902	.64569	.64644	.64607	1123.97600
1.517	-2.315	-4.9558	-4.9204	-4.9042	-4.9123	.64486	.64158	.64233	.64195	1126.12601
1.516	-1.806	-3.9715	-3.9446	-3.9244	-3.9330	.63498	.63260	.63310	.63285	1128.19901
1.517	-1.293	-2.9735	-2.9626	-2.9456	-2.9541	.62694	.62392	.62442	.62417	1130.02299
1.517	-785	-1.9798	-1.9740	-1.9650	-1.9622	.61862	.61596	.61666	.61631	1131.45799
1.517	-278	-1.0113	-1.0079	-0.9886	-0.9983	.60733	.60523	.60574	.60549	1132.76801
1.517	-215	-0.0637	-0.0629	-0.0613	-0.0621	.60142	.59964	.60011	.59988	1132.61000
1.516	-720	.08708	.08629	.08792	.08711	.59611	.59440	.59488	.59464	1129.68100
1.516	1.214	.18336	.18282	.18488	.18385	.59733	.59526	.59574	.59550	1128.97501
1.516	GRADIENT	.18804	.18717	.18714	.18715	-.00901	-.00895	-.00892	-.00892	.35899

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 808

(UCM055) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1628/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PT2F
1.541	-6.907	-1.29825	-1.29371	-1.29303	.64074	.63716	.63815	.63765 1116.77901 1133.64229
1.542	-6.393	-1.16703	-1.16154	-1.16083	.62266	.61929	.62039	.61984 1118.79500 1134.88611
1.542	-5.885	-1.04813	-1.04509	-1.04424	.61093	.60733	.60852	.60793 1121.94299 1137.01471
1.542	-5.377	-0.93433	-0.93229	-0.93133	.59743	.59429	.59511	.59470 1123.59900 1136.56615
1.542	-4.872	-0.82646	-0.82364	-0.82190	.82277	.58377	.58052	.58137 .58094 1123.08501 1135.23393
1.542	-4.359	-0.72414	-0.72180	-0.72097	.62097	.56585	.56277	.56318 1122.17799 1135.26883
1.542	-3.854	-0.62919	-0.62654	-0.62468	.62561	.54929	.54566	.54717 .54641 1121.67799 1133.92451
1.541	-3.342	-0.53434	-0.53031	-0.52854	.52943	.52913	.52536	.52621 .52578 1121.33200 1133.66478
1.541	-2.828	-0.44431	-0.44048	-0.43947	.43947	.51038	.50713	.50781 .50747 1121.27400 1133.06268
1.542	-2.316	-0.35819	-0.35555	-0.35418	.35486	.49326	.49066	.49135 .49100 1121.50000 1133.29672
1.542	-1.804	-0.27290	-0.27118	-0.26926	.27022	.47339	.46990	.47064 .47027 1123.28000 1134.60924
1.542	-1.294	-0.19270	-0.19119	-0.18909	.19014	.45099	.44727	.44756 .44756 1124.94000 1135.97102
1.542	-0.785	-0.11549	-0.11473	-0.11282	.11473	.42986	.42676	.42753 .42714 1126.25999 1137.04695
1.542	-0.279	-0.04567	-0.04370	-0.04462	.04462	.41464	.41257	.41293 .41293 1125.67900 1135.71362
1.542	-0.213	.02013	.01845	.02060	.01952	.40380	.40258	.40306 .40282 1124.41600 1135.17505
1.542	-0.721	.08812	.08627	.08822	.08725	.39932	.39787	.39856 .39821 1124.61800 1135.02028
1.542	1.214	.15680	.15686	.15900	.15793	.39506	.39396	.39457 .39426 1124.82300 1135.30170
GRADIENT	16058	.15979	.15982	.15985	.15982	.03347	.03309	.03313 .03313 1124.8070 1135.22717

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM056) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1582/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PT2F
.599	-6.858	-.64133	-.64093	-.63948	-.64020	.40620	.40551	.40683 .40667 1563.48500 1596.75999
.600	-5.832	-.54737	-.54781	-.54629	-.54705	.40599	.40549	.40586 .40568 1570.57300 1597.27000
.599	-4.815	-.45469	-.45449	-.45297	-.45373	.40419	.40326	.40364 .40345 1576.35001 1596.22000
.600	-3.790	-.35994	-.35922	-.35783	-.35853	.39993	.39902	.39929 .39915 1581.86900 1596.99001
.600	-2.771	-.26622	-.26654	-.26516	-.26585	.39536	.39466	.39526 .39496 1585.87500 1597.21001
.600	-1.750	-.17509	-.17454	-.17302	-.17378	.39131	.39029	.39067 .39048 1588.77400 1596.63000
.601	-0.733	-.08394	-.08269	-.08117	-.08193	.38478	.38456	.38477 .38467 1590.74200 1597.69000
.600	.280	.01072	.00978	.01143	.01060	.37959	.37893	.37910 .37902 1591.8070 1597.03000
.600	1.262	.09869	.09792	.09968	.09880	.37582	.37521	.37549 .37535 1592.08501 1596.78000
GRADIENT	0.0905	.09079	.09084	.09081	.09080	-.00480	-.00473	-.00475 .2.53684 .00475 1596.78000

## PARAMETRIC DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM056) (04 OCT 91)

## PARAMETRIC DATA

		RUN NO.	1473/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.800	-6.904	-.77101	-.77191	-.77026	-.77109	.48594	.48516	.48562	.48539	1303.82100	1341.32001
.800	-5.875	-.66169	-.66277	-.66121	-.66199	.48152	.48166	.48215	.48191	1311.34100	1341.17999
.800	-4.859	-.55021	-.55116	-.54985	-.55050	.47838	.47848	.47892	.47870	1318.23300	1340.92000
.800	-3.846	-.43724	-.43788	-.43644	-.43716	.47311	.47295	.47334	.47315	1324.08400	1341.05000
.800	-2.835	-.32571	-.32652	-.32465	-.32559	.47023	.46937	.46965	.46951	1328.58501	1340.96001
.800	-1.818	-.21655	-.21745	-.21589	-.21667	.46537	.46467	.46467	.46489	1331.92700	1340.83000
.800	-.812	-.10664	-.10585	-.10430	-.10507	.46066	.45971	.46013	.45992	1334.35400	1340.97000
.800	.202	.00415	.00262	.00431	.00347	.45611	.45518	.45522	.45520	1335.65100	1341.13000
.799	1.188	.11099	.10981	.11148	.11065	.45269	.45169	.45177	.45173	1336.21800	1340.78999
GRADIENT		.10918	.10915	.10920	.10918	-.00427	-.00444	-.00450	-.00447	2.93455	-.00768
		RUN NO.	1507/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-6.891	-.79846	-.80205	-.79964	-.80085	.50544	.50400	.50468	.50434	1235.69400	1273.07001
.900	-5.863	-.68677	-.68940	-.68724	-.68832	.50084	.49989	.50052	.50021	1243.32800	1273.00999
.900	-4.846	-.57236	-.57461	-.57227	-.57344	.49578	.49536	.49589	.49563	1250.38300	1273.03999
.900	-3.833	-.45616	-.45625	-.45411	-.45518	.49080	.49072	.49128	.49100	1256.31400	1272.95000
.900	-2.821	-.33809	-.33960	-.33754	-.33857	.48714	.48731	.48777	.48754	1260.83800	1273.06000
.900	-1.801	-.22486	-.22594	-.22385	-.22490	.48207	.48177	.48238	.48207	1264.08299	1272.86000
.900	-.793	-.11028	-.11021	-.10835	-.10928	.47840	.47759	.47820	.47790	1266.50101	1273.00000
.900	-.217	.00351	.00239	.00420	.00330	.47208	.47145	.47187	.47166	1267.88800	1273.00000
.900	1.202	.11495	.11449	.11625	.11537	.46906	.46952	.46929	.46929	1268.33400	1273.00000
GRADIENT		.11351	.11368	.11359	.11364	-.00441	-.00450	-.00451	-.00450	2.92699	.00349
		RUN NO.	1513/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.099	-6.963	-.81694	-.82034	-.81823	-.81929	.49983	.49768	.49805	.49786	1168.27400	1204.85100
1.100	-5.943	-.70484	-.70771	-.70545	-.70658	.49504	.49357	.49397	.49377	1175.70799	1204.78999
1.100	-4.938	-.59088	-.59315	-.59109	-.59212	.49114	.48955	.48997	.48976	1182.26801	1204.72600
1.100	-3.933	-.47457	-.47247	-.47350	-.47247	.48682	.48592	.48635	.48613	1188.04500	1204.61000
1.100	-2.944	-.35802	-.35874	-.35703	-.35789	.48374	.48285	.48314	.48299	1192.70399	1204.74600
1.100	-1.930	-.24404	-.24293	-.24194	-.24299	.48197	.48282	.48234	.48215	1195.98199	1204.77000
1.100	-.922	-.12431	-.12237	-.12234	-.12334	.48060	.47951	.47991	.47971	1198.32300	1204.76199
1.100	.079	-.00902	-.00881	-.00751	-.00816	.47849	.47759	.47799	.47779	1199.76300	1204.55400
1.100	1.069	.10401	.10333	.10501	.10417	.47819	.47761	.47775	.47768	1200.43500	1204.74300
GRADIENT		.11580	.11598	.11590	.11594	-.00209	-.00199	-.00202	-.00200	2.97728	-.00166

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 810

(UCM056) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1529/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000	DPB	PTTF	DPB	PT2F
MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB 1	DPB 2	DPB	PTTF	DPB	PT2F	PT2F
1.250	-6.921	-88751	-88987	-88797	-88892	.55318	.55251	.55342	.55297	1145.17900	1183.03101		
1.250	-5.887	-76335	-76522	-76291	-76406	.54905	.54854	.54950	.54902	1152.55800	1182.36200		
1.250	-4.877	-63727	-63896	-63641	-63769	.54456	.54431	.54557	.54494	1159.72099	1182.32899		
1.250	-3.862	-50767	-50945	-50712	-50828	.53789	.53698	.53812	.53755	1165.35400	1182.28600		
1.250	-2.853	-37895	-37961	-37717	-37839	.53326	.53218	.53288	.53253	1169.23000	1182.68700		
1.250	-1.843	-25307	-25432	-25193	-25313	.52898	.52796	.52864	.52830	1172.55499	1183.03300		
1.250	-837	-12732	-12824	-12518	-12625	.52485	.52380	.52427	.52403	1174.32500	1181.99600		
1.250	.174	.00073	.00038	.00002	.00018	.52034	.51963	.52011	.51987	1175.27901	1182.03000		
1.160	.12161	.12105	.12303	.12204	.121844	.51770	.51821	.51796	.51796	1176.69901	1182.93800		
GRADIENT	.12559	.12592	.12571	.12582	.12571	.00432	.00436	.00450	.00443	2.69314	.02186		
RUN NO.	1546/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000	DPB	PTTF	DPB	PT2F
MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB 1	DPB 2	DPB	PTTF	DPB	PT2F	PT2F
1.400	-6.928	-1.01811	-1.02121	-1.01924	-1.02022	.63357	.63481	.63530	.63505	1125.75999	1164.63300		
1.400	-5.895	-87459	-87767	-87580	-87673	.63457	.63434	.63480	.63457	1133.54300	1164.16299		
1.400	-4.882	-73151	-73271	-73045	-73158	.62624	.62623	.62664	.62643	1140.36200	1164.10899		
1.400	-3.875	-58613	-58726	-58508	-58617	.62004	.61951	.62036	.61994	1146.01500	1164.46300		
1.400	-2.864	-44129	-44164	-43951	-44057	.61940	.61858	.61944	.61944	1151.18700	1164.37100		
1.400	-1.855	-29512	-29660	-29440	-29550	.61345	.61319	.61390	.61354	1154.40199	1163.96001		
1.400	-.853	-14760	-14868	-14683	-14776	.60754	.60713	.60772	.60742	1156.52100	1164.25800		
1.400	.157	-.00207	-.00223	-.00217	-.00220	.60251	.60245	.60285	.60265	1158.55701	1164.46700		
1.146	.13705	.13695	.13848	.13772	.13848	.59879	.59869	.59916	.59893	1158.51300	1163.88300		
GRADIENT	.14445	.14461	.14437	.14447	.14437	.00459	.00455	.00455	.00457	3.01630	-.02767		
RUN NO.	1563/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000	DPB	PTTF	DPB	PT2F
MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB 1	DPB 2	DPB	PTTF	DPB	PT2F	PT2F
1.449	-6.869	-1.07543	-1.07223	-1.07285	-1.07414	.68545	.68490	.68600	.68545	1120.37399	1158.86800		
1.450	-5.830	-92170	-92444	-92342	-92342	.68379	.68255	.68355	.68305	1126.84700	1158.44299		
1.450	-4.814	-76914	-77130	-76901	-77015	.67245	.67243	.67337	.67290	1133.99200	1158.57899		
1.450	-3.794	-61260	-61625	-61402	-61513	.66068	.66067	.66148	.66107	1138.06700	1158.55299		
1.450	-2.776	-45771	-46039	-45833	-45936	.66103	.66113	.66120	.66162	1142.73599	1158.15900		
1.450	-1.752	-30526	-30773	-30572	-30672	.65745	.65782	.65855	.65818	1147.59700	1158.87900		
1.450	-.738	-14979	-14945	-14758	-14852	.64719	.64851	.64935	.64893	1149.68900	1158.08200		
1.450	.272	.00483	.00650	.00448	.00549	.64064	.64166	.64252	.64209	1150.83501	1158.17300		
1.450	1.252	.15511	.15371	.15544	.15457	.63459	.63536	.63566	.63551	1151.94299	1158.39700		
GRADIENT	.15212	.15254	.15245	.15250	.15250	-.00590	-.00570	-.00570	-.00574	3.04762	-.04887		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(LUCM056) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	4.000	PHI =	180.000	PTTF
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	PTTF
ALPHA	-1.10364	-1.10003	-1.09912	-1.09957	.69713	.69597	.69680	.69639	.1107.26900	.1150.02394	PT2F
-6.879	-.94349	-.94218	-.9410	-.94159	.69599	.69500	.69586	.69543	.1113.02699	.1149.31818	
-5.845	-.78936	-.78805	-.78694	-.78750	.68951	.68746	.68823	.68784	.1119.54401	.1148.81499	
-4.825	-.63521	-.63265	-.63138	-.63202	.68044	.67881	.67956	.67919	.1126.20500	.1167.15723	
-3.808	-.47380	-.47104	-.47104	-.47035	.67280	.67043	.67103	.67073	.1129.94400	.1149.24663	
-2.795	-.31504	-.31372	-.31372	-.31302	.665587	.663553	.66418	.66386	.1132.52100	.1149.28864	
1.470	-1.774	-.15490	-.15490	-.15417	.65828	.65595	.65653	.65624	.1134.75101	.1148.61703	
1.470	-.761	-.00251	-.00177	-.00197	.64981	.64739	.64804	.64772	.1136.11900	.1148.21515	
1.470	.249	.15053	.15056	.15209	.64502	.64271	.64319	.64295	.1137.39500	.1148.93748	
1.470	1.237	.15531	.15531	.15530	-.00739	-.00747	-.00751	-.00749	2.76172	-1.34714	
GRADIENT	15578										
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	PTTF
ALPHA	-1.15328	-1.15131	-1.14950	-1.15041	.73057	.72790	.72825	.72807	.1101.52600	.1143.99373	PT2F
-6.884	-.99840	-.99684	-.99762	-.99762	.73312	.73094	.73646	.73352	.1109.04800	.1144.69838	
-5.854	-.83875	-.83663	-.83514	-.83589	.72825	.72844	.72835	.72835	.1113.56300	.1144.34087	
-4.840	-.68111	-.68010	-.67839	-.67924	.73332	.73026	.73109	.73068	.1118.94800	.1144.50011	
-3.819	-.51266	-.51020	-.50838	-.50929	.73304	.72978	.73025	.73001	.1122.34100	.1144.50102	
-2.807	-.34181	-.34107	-.34011	-.34011	.72475	.72221	.72208	.72215	.1124.29300	.1144.07721	
1.493	-.776	-.16865	-.16912	-.16734	.71682	.71691	.71450	.71433	.1125.49899	.1143.56194	
1.493	.235	.00288	.00164	.00248	.00206	.00272	.00534	.00551	.1125.99600	.1143.59053	
1.493	1.224	.16525	.16442	.16639	.16540	.16085	.69829	.69842	.1125.86200	.1142.98732	
GRADIENT	16675	.16618	.16616	.16617	-.00556	-.00547	-.00552	-.00549	1.91460	-.24043	
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	PTTF
ALPHA	-1.29728	-1.29148	-1.29025	-1.29087	.82272	.81933	.82019	.81976	.1101.56500	.1135.17606	PT2F
1.516	-.1.13707	-.1.13207	-.1.13074	-.1.13140	.83407	.83081	.83190	.83135	.1111.69800	.1136.45023	
1.516	-.95750	-.95399	-.95245	-.95322	.82919	.82601	.82709	.82655	.1118.49400	.1137.81683	
1.517	-.76441	-.75991	-.75820	-.75905	.81887	.81588	.81659	.81624	.1122.44800	.1137.10617	
1.516	-.3.821	-.56980	-.56799	-.56889	.81342	.81092	.81062	.81062	.1122.64000	.1136.80907	
1.517	-2.808	-.57154	-.56980	-.56889	.82150	.81761	.81789	.81789	.1124.02699	.1137.61198	
1.516	-1.787	-.39310	-.39070	-.38953	.81867	.81473	.81521	.81497	.1126.24400	.1138.21785	
1.517	-.777	-.20110	-.20038	-.19870	.81292	.80892	.80944	.80918	.1128.02499	.1139.52982	
1.516	.234	-.00422	-.00392	-.00359	.80376	.80330	.80373	.80351	.1128.79700	.1140.03616	
1.517	1.222	.18390	.18369	.18571	.18470	.18075	-.00258	-.00274	-.00283	-.00278	.45553
GRADIENT	18773	.18700	.18695	.18697							

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 812

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM056) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PTF
1.542	-6.883	-1.31749	-1.31287	-1.31147	-1.31217	.83427	.83014	.83153	.83084	1116.43700	1134.71165
1.541	-5.851	-1.06837	-1.06516	-1.06265	-1.06391	.80004	.79624	.79743	.79684	1119.47099	1134.29720
1.541	-4.835	-1.84623	-1.84351	-1.84171	-1.84261	.76514	.76033	.76146	.76090	1122.14799	1134.22444
1.541	-3.823	-1.65000	-1.64784	-1.64599	-1.64691	.73004	.72580	.72626	.72603	1122.56500	1134.29015
1.541	-2.806	-1.46432	-1.46061	-1.45868	-1.45964	.69108	.68688	.68782	.68735	1122.42101	1134.86267
1.542	-1.788	-1.28996	-1.28728	-1.28520	-1.28624	.65614	.65188	.65267	.65228	1123.00200	1134.79655
1.541	-7.777	-1.12096	-1.11960	-1.11754	-1.11857	.62990	.62591	.62647	.62619	1123.95599	1134.93106
1.541	-2.388	.04259	.04226	.04425	.04326	.60838	.60510	.60565	.60538	1124.29201	1134.88832
1.541	1.221	.19878	.19828	.20022	.19925	.59826	.59544	.59589	.59566	1124.47400	1135.14801
GRADIENT		.17116	.17119	.17117	.17117	-.02845	-.02816	-.02824	-.02820	.42260	.14252

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM057) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PTF
.599	-7.870	-1.73635	-1.73510	-1.73389	-1.73449	.40910	.40914	.40959	.40936	1554.36501	1596.85001
.599	-6.844	-1.64154	-1.64061	-1.63911	-1.63986	.40624	.40605	.40642	.40623	1562.92900	1596.67000
.600	-5.828	-1.54945	-1.54856	-1.54683	-1.54769	.40645	.40534	.40556	.40545	1569.76199	1596.73000
.600	-4.806	-1.45477	-1.45342	-1.45205	-1.45274	.40397	.40255	.40276	.40266	1576.06599	1596.64999
.600	-3.789	-1.35912	-1.35799	-1.35728	-1.35764	.39814	.39703	.39739	.39721	1581.66200	1596.86000
.601	-2.768	-1.26604	-1.26643	-1.26552	-1.26552	.39553	.39431	.39474	.39453	1585.69600	1597.67999
.601	-1.750	-1.17527	-1.17465	-1.17311	-1.17388	.38993	.38971	.38977	.38974	1588.85001	1597.09000
.601	-736	-0.8161	-0.8190	-0.8036	-0.8113	.38495	.38463	.38483	.38473	1591.01199	1596.67000
.601	277	.00933	.00840	.01013	.00926	.37893	.37871	.37876	.37873	1592.23199	1597.08000
.600	1.258	.09771	.09695	.09869	.09782	.37605	.37581	.37602	.37592	1592.91701	1596.97000
.600	2.239	.18811	.18781	.18863	.18945	.37185	.37137	.37147	.37147	1592.96001	1596.94000
GRADIENT		.09095	.09067	.09075	.09071	-.00461	-.00444	-.00445	-.00445	.2.32338	.00444

## PARAMETRIC DATA

	RUN NO.	1748/ O	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.800	-.88741	-.88479	-.88389	-.88434	.48634	.48454	.48508	.48481	1293.06500	1341.03000
.800	-.77195	-.76999	-.76868	-.76934	.48288	.48109	.48169	.48139	1302.72900	1341.20000
.799	-.66365	-.66197	-.66049	-.66123	.48082	.48022	.48053	.48038	1310.54601	1340.92999
.800	-.55180	-.55092	-.54952	-.55022	.47789	.47746	.47775	.47761	1317.64600	1341.21001
.800	-.43843	-.43963	-.43682	-.43756	.47381	.47244	.47284	.47264	1323.94099	1341.45000
.800	-.32742	-.32605	-.32453	-.32529	.46985	.46855	.46885	.46870	1328.54300	1341.17000
.800	-.21809	-.21705	-.21547	-.21626	.46588	.46382	.46422	.46402	1332.08299	1341.21001
.800	-.10790	-.10571	-.10406	-.10488	.46171	.45998	.46028	.46013	1334.22200	1340.86000
.800	.00219	.00256	.00425	.00340	.45607	.45445	.45439	.45439	1335.79100	1341.00999
.800	1.186	.10889	.10871	.11015	.45311	.45169	.45153	.45161	1336.37500	1340.62000
.800	2.172	.21760	.21725	.21870	.44999	.44864	.44839	.44851	1336.29800	1340.64999
GRADIENT	.10927	.10906	.10907	.10907	-.00408	-.00417	-.00426	-.00421	2.57028	-.10530

	RUN NO.	1661/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-.91622	-.91594	-.91449	-.91522	.50641	.50500	.50569	.50535	1225.122900	1272.69000
.900	-.79914	-.79821	-.79661	-.79741	.50420	.50217	.50281	.50249	1234.69901	1273.33000
.900	-.68774	-.68641	-.68492	-.68567	.50179	.50003	.50042	.50022	1242.67599	1272.89999
.900	-.57102	-.57309	-.56942	-.57022	.49710	.49523	.49570	.49547	1249.37601	1272.85001
.900	-.4845	-.45355	-.45619	-.45201	.45278	.45196	.45145	.49122	1256.13400	1273.28999
.900	-.3.830	-.33751	-.33574	-.33662	.48792	.48706	.48740	.48723	1260.48300	1272.84000
.900	-.2.815	-.33803	-.22226	-.22306	.48332	.48213	.48251	.48232	1264.11700	1273.19000
.900	-.1.801	-.2.2417	-.22385	-.22416	.48207	.47720	.47760	.47740	1266.54201	1272.97000
.900	-.791	-.10858	-.10866	-.10790	.47807	.47120	.47158	.47171	1267.65700	1272.94000
.900	.217	.00549	.00383	.00562	.47260	.47260	.47185	.46842	1268.83300	1273.23000
.900	1.202	.11534	.11368	.11538	.46905	.46835	.46849	.46470	1268.37801	1272.39000
.899	2.188	.22751	.22638	.22791	.46532	.46462	.46478	-.00453	-.00453	-.00451
GRADIENT	.11371	.11311	.11311	.11311	-.00460	-.00448	-.00448	-.00451	2.61490	-.04038

	RUN NO.	1740/ O	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.098	-.93176	-.93223	-.93089	-.93156	.50358	.50158	.50233	.50196	1158.41901	1205.02499
1.100	-.81810	-.81792	-.81626	-.81709	.49816	.49515	.49600	.49557	1167.08600	1205.54500
1.101	-.70631	-.70466	-.70548	-.70548	.49718	.49464	.49540	.49502	1174.85800	1205.23000
1.101	-.59127	-.58921	-.59081	-.59002	.49340	.49068	.49135	.49101	1181.53200	1204.73100
1.101	-.47316	-.47316	-.47147	-.47231	.48806	.48648	.48717	.48682	1187.17799	1204.54401
1.100	-.3.931	-.35623	-.35797	-.35665	.48534	.48374	.48432	.48403	1192.05901	1204.70399
1.100	-.2.939	-.24282	-.24334	-.24162	.48351	.48166	.48243	.48204	1195.47501	1204.64000
1.100	-.1.922	-.12490	-.12320	-.12405	.48164	.47978	.48047	.48012	1198.18500	1204.89900
1.100	-.925	-.00808	-.00966	-.00887	.48070	.47885	.47930	.47908	1199.61000	1204.52299
1.100	-.080	-.0951	-.10273	-.10178	.47931	.47764	.47814	.47789	1200.33900	1204.72900
1.100	1.066	.10344	.10083	.10273	.47983	.47863	.47900	.47882	1200.53000	1204.74899
1.100	2.063	.21869	.21692	.21774	-.00184	-.00173	-.00177	-.00175	2.67006	.00909
GRADIENT	.11531	.11533	.11533	.11533	-.00184	-.00173	-.00177	-.00175	2.67006	.00909

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 814

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM057) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1724/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000	PTT F
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	.55335	1134.22600
1.249	-7.925	-1.01941	-1.01734	-1.01600	-1.01667	.55523	.55280	.55389	.55244	1143.28101	1182.53000
1.250	-6.894	-.88961	-.88626	-.88534	-.88580	.55438	.55202	.55286	.55029	1151.28101	1182.54700
1.250	-5.883	-.76588	-.76272	-.76125	-.76199	.55121	.54992	.55066	.54639	1159.17300	1182.43900
1.250	-4.873	-.63905	-.63757	-.63591	-.63674	.54841	.54574	.54704	.53855	1164.85999	1182.47600
1.250	-3.862	-.50836	-.50714	-.50554	-.50634	.54057	.53801	.53909	.53353	1168.74499	1182.26601
1.250	-2.850	-.37851	-.37767	-.37610	-.37688	.53602	.53325	.53381	.52948	1172.31200	1182.55901
1.250	-1.841	-.25382	-.25305	-.25119	-.25212	.53149	.52910	.52987	.52477	1174.75900	1182.54300
1.250	-836	-.12738	-.12641	-.12480	-.12561	.52728	.52439	.52515	.52025	1176.40500	1182.64700
1.250	-173	-.00129	-.00046	-.00017	-.00032	.52299	.52006	.52043	.51729	1176.99600	1182.74400
1.250	1.158	-.12208	-.11970	-.12145	-.12058	.51990	.51699	.51759	.51495	1176.96201	1182.49400
2.153	2.153	.24535	.24346	.24510	.24428	.51743	.51477	.51513	.00440	2.49946	.03384
GRADIENT		1.2568	1.2515	1.2515	1.2517	-.00431	-.00434	-.00446			
	RUN NO.	1716/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000	PTT F
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	.63270	1124.45700
1.400	-6.923	-1.01483	-1.01323	-1.01160	-1.01242	.63307	.63309	.63231	.63184	1132.72000	1164.36301
1.400	-5.895	-.87332	-.87263	-.87073	-.87168	.63201	.63229	.63138	.62583	1139.91800	1164.51700
1.400	-4.878	-.73001	-.72813	-.72635	-.72724	.62623	.62624	.62543	.61772	.61813	1146.03500
1.400	-3.872	-.58616	-.58518	-.58326	-.58422	.61846	.61854	.61620	.61541	.61581	1150.93900
1.400	-2.865	-.44103	-.44006	-.43819	-.43913	.61599	.61228	.61249	.61171	.61210	1154.92599
1.400	-1.852	-.29621	-.29522	-.29716	-.29619	.60648	.60667	.60571	.60619	.60745	1157.21001
1.400	-851	-.15029	-.15050	-.14952	-.14951	.00556	.00579	.00226	.60247	.60145	1159.46400
1.400	-157	-.00538	-.00602	-.00556	-.00556	.59860	.59927	.59817	.59872	.59713	1159.79900
1.400	1.145	-.13379	-.13137	-.13335	-.13236	.59700	.59767	.59658	.59713	.59658	1164.08299
1.400	2.133	.27738	.27477	.27675	.27576	-.00417	-.00408	-.00413	-.00410	2.82783	-.03883
	RUN NO.	1706/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000	PTT F
MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	.70225	1108.05800
1.450	-7.874	-1.23453	-1.23224	-1.23108	-1.23166	.70266	.70254	.70196	.68397	1115.50200	1158.59000
1.450	-6.841	-1.07898	-1.07592	-1.07448	-1.07520	.6815	.68423	.68370	.68389	1123.51801	1157.92101
1.450	-5.831	-.92789	-.92629	-.92487	-.92558	.68457	.68425	.68353	.67536	.67577	1131.27800
1.450	-4.811	-.77703	-.77327	-.77402	-.77407	.67612	.67618	.66666	.66597	.66634	1136.94099
1.450	-3.790	-.62121	-.62107	-.61914	-.62011	.66666	.66695	.66758	.66806	.66842	1142.81500
1.450	-2.773	-.46559	-.46581	-.46404	-.46493	.66695	.66653	.66636	.66586	.66556	1148.25600
1.450	-1.750	-.31289	-.31299	-.31126	-.31213	.66513	.66513	.66536	.66586	.66556	1148.39700
1.450	-740	-.15578	-.15326	-.15418	-.15418	.65690	.65852	.65752	.65802	.65752	1151.26900
1.450	.272	.00131	.00151	.00226	.00188	.65036	.65011	.64920	.64966	.65011	1158.41800
1.450	1.254	.15073	.14824	.15013	.14918	.64457	.64459	.64334	.64396	.64334	1153.94000
1.450	2.240	.30363	.30071	.30160	.30160	.63977	.64160	.64039	.64099	.64039	1153.92999
GRADIENT		1.5323	1.5266	1.5267	1.5267	-.00499	-.00499	-.00490	-.00493	2.26813	-.01522

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM057) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1699/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.27234	-1.26946	-1.26831	-1.26889	.71387	.71425	.71329	.71377	1104.10100	1147.57178
1.469	-1.11552	-1.11333	-1.11260	-1.11260	.70062	.70119	.70034	.70076	1112.50000	1147.76624
1.469	-1.96404	-1.96309	-1.96238	-1.96238	.70542	.70543	.70461	.70502	1122.21800	1147.51749
1.470	-1.80255	-1.80146	-1.79973	-1.80060	.69217	.69228	.69142	.69185	1128.93700	1147.39421
1.469	-1.64134	-1.64098	-1.63924	-1.64011	.68491	.68374	.68275	.68325	1133.64900	1147.58925
1.469	-2.789	-1.48157	-1.47996	-1.47913	.67874	.67810	.67706	.67758	1137.88200	1147.62585
1.469	-1.769	-1.32249	-1.32307	-1.32221	.67490	.67428	.67327	.67378	1141.47600	1147.76579
1.469	-1.62226	-1.62297	-1.61114	-1.6206	.66616	.66628	.66515	.66571	1144.37801	1147.56163
1.469	-1.249	-1.0360	-1.00381	-1.00353	.65846	.65878	.65782	.65830	1145.77499	1147.44421
1.469	1.232	1.4810	1.4576	1.4669	.65414	.65454	.65349	.65401	1146.76300	1147.74954
1.469	2.221	3.0066	2.99992	3.0169	.65119	.65146	.65013	.65079	1146.96500	1147.82903
GRADIENT	.15675	.15638	.15634	.15636	-.00603	-.00588	-.00593	-.00590	2.58520	.03649

RUN NO. 1692/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1692/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.29576	-1.29314	-1.29207	-1.29260	.73400	.73227	.73159	.73193	1098.84000	1148.36110
1.497	-6.858	-1.14674	-1.14396	-1.14342	.72412	.72255	.72120	.72187	1104.94099	1147.92815
1.497	-5.849	-.99818	-.99604	-.99539	.73066	.72898	.72756	.72827	1113.83400	1148.14915
1.497	-4.833	-.83986	-.83683	-.83567	.83625	.82749	.82564	.82439	1120.77499	1147.74382
1.497	-3.821	-.67386	-.67267	-.67111	.67189	.67078	.671923	.67188	.71856	.71822
1.497	-2.796	-.50440	-.50246	-.50325	.71771	.71622	.71476	.71545	1122.73700	1147.94665
1.497	-1.783	-.34120	-.33948	-.34034	.71300	.71182	.71079	.71131	1125.26601	1147.71074
1.496	-.774	-.17016	-.17097	-.17097	.70752	.70629	.70532	.70581	1136.45300	1147.91667
1.497	.235	-.00276	-.00274	-.00274	.69873	.69833	.69704	.69769	1138.32401	1147.74730
1.496	1.217	1.5728	1.5524	1.5608	.69225	.69175	.69062	.69118	1138.88499	1147.64430
1.497	2.207	3.1874	3.1943	3.1864	.68496	.68472	.68338	.68405	1138.55000	1147.54495
GRADIENT		1.6430	.16429	.16429	-.00594	-.00571	-.00569	-.00570	3.10921	-.03785

RUN NO. 1687/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1687/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.37127	-1.37035	-1.37081	-1.37081	.78004	.77727	.77640	.77683	1093.90199	1142.87930
1.521	-6.866	-1.23536	-1.23486	-1.23511	.78294	.77928	.77899	.77899	1102.56000	1142.51007
1.521	-5.849	-.90312	-.08862	-.08837	.79640	.79481	.79413	.79447	1111.50700	1142.63243
1.520	-4.830	-.92847	-.92598	-.92474	.80063	.79925	.79849	.79887	1118.78700	1142.36317
1.521	-3.814	-.75275	-.74925	-.74797	.79990	.79861	.79793	.79827	1123.33299	1142.65799
1.521	-2.803	-.57570	-.57275	-.57351	.80006	.79877	.79799	.79838	1125.56000	1142.83707
1.521	-1.785	-.39824	-.39689	-.39515	.80962	.80834	.80709	.80771	1127.17599	1142.61633
1.520	-.777	-.20903	-.20856	-.20690	.81264	.81073	.80944	.81008	1128.29500	1142.89255
1.520	.237	-.01601	-.01376	-.01454	.80862	.80666	.80528	.80597	1129.19200	1142.67247
1.520	1.220	1.7177	1.7049	1.7252	.80341	.80160	.80034	.80097	1129.52800	1142.47247
1.520	2.207	.35586	.35430	.35465	.78797	.78727	.78607	.78667	1129.27299	1142.54626
GRADIENT	.18307	.18238	.18239	.18239	-.00049	-.00049	-.00058	-.00054	1.37949	.00185

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 816

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM057) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1680/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.57676	-1.57072	-1.57048	.90111	.89788	.89777	.89783	1111.80600	1136.83643	
1.541	-7.888	-6.862	-1.35521	-1.34980	-1.34940	.83578	.83366	.83332	1113.82500	1137.08633
1.543	-1.543	-1.542	-1.10964	-1.10424	-1.10298	.81384	.81168	.81125	1117.33000	1137.66354
1.544	-5.847	-4.831	-8.7581	-8.7290	-8.7170	.76406	.76237	.76197	1118.48199	1135.83380
1.545	-3.819	-3.819	-6.8066	-6.7739	-6.7600	.72759	.72650	.72510	1118.42101	1135.79044
1.546	-2.800	-2.800	-4.8309	-4.7902	-4.7754	.69407	.69217	.69124	1119.15601	1136.32054
1.547	-1.781	-1.781	-3.1594	-3.1374	-3.1207	.66370	.66177	.66069	1119.83900	1136.56731
1.548	-7.755	-7.755	-14.406	-14.175	-14.023	.64053	.63873	.63737	.63805	.64500
1.549	-2.34	-2.34	0.2753	0.2692	0.2865	.02778	.62311	.62137	.62007	.62072
1.550	1.217	1.217	-1.8262	-1.8251	-1.8426	.61765	.61596	.61466	.61531	.61211
1.551	2.207	2.207	34675	34630	34664	.61931	.61790	.61655	.61723	.61211
GRADIENT	17245	17180	17179	17179	17180	-.02132	-.02132	-.02135	.50783	.21009

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM058) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1673/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-8.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
BETA	-3.745	-3.745	-7.8376	-7.8235	-7.78100	-.78168	-.36639	-.36298	-.36289	-.36293
.600	-2.728	-2.728	-7.7234	-7.7085	-7.6964	-.77024	-.26625	-.26595	-.26610	-.2658
.600	-1.724	-1.724	-7.6390	-7.6239	-7.6097	-.76168	-.16746	-.16726	-.16736	-.16709
.600	-7.18	-7.18	-7.5381	-7.5226	-7.5068	-.75147	-.06996	-.06893	-.06880	-.06866
.600	-2.89	-2.89	-7.5307	-7.5139	-7.5012	-.75076	-.02403	-.02269	-.02265	-.02261
.600	-73.7	-73.7	-7.5215	-7.5060	-7.4988	-.74916	-.07069	-.07036	-.07077	-.07057
.600	1.747	1.747	-7.5700	-7.5525	-7.5393	-.75459	-.17130	-.17071	-.17104	-.17088
600	2.757	2.757	-7.6119	-7.5966	-7.5828	-.75897	-.26783	-.26882	-.26901	-.26892
600	3.771	3.771	-7.6473	-7.6336	-7.6204	-.76270	-.36884	-.36836	-.36885	-.36861
GRADIENT	.00223	.00223	.00223	.00223	.00223	.00223	.09733	.09733	.09735	-.27222

(UCM058) (04 OCT 91)

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 817

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM058) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1749/ 0 RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.800	-3.820	- .93133	- .93172	- .93057	- .93114	- .44326	- .44176	- .44163	- .44170	1294.34000	1341.14999
.800	-2.803	- .92069	- .91806	- .91697	- .91751	- .32712	- .32628	- .32609	- .32618	1297.41100	1341.06000
.801	-1.801	- .90701	- .90455	- .90332	- .90393	- .20732	- .20601	- .20581	- .20591	1299.84900	1340.82001
.800	- .790	- .90095	- .89852	- .89738	- .89795	- .09252	- .09005	- .08989	- .08997	1300.90700	1340.99001
.800	- .211	- .89978	- .89743	- .89623	- .89683	- .02272	- .02037	- .02029	- .02033	1302.34100	1342.03999
.800	- .832	- .89883	- .89658	- .89516	- .89587	- .09486	- .09552	- .09588	- .09570	1301.42400	1342.14999
.800	1.835	- .90398	- .90132	- .90025	- .90078	- .21458	- .21493	- .21532	- .21512	1300.20599	1342.62000
.799	2.841	- .90890	- .90634	- .90509	- .90572	- .33102	- .33039	- .33100	- .33070	1297.94501	1342.67000
.800	3.845	- .91053	- .90808	- .90669	- .90739	- .44932	- .44775	- .44804	- .44790	1293.80299	1342.31000
	GRADIENT	.00243	.00242	.00245	.00244	.11642	.11605	.11609	.11607	-.00481	.24658

RUN NO. 1662/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.900	-3.810	- .96718	- .96726	- .96614	- .96670	- .45427	- .45176	- .45160	- .45168	1226.67300	1272.82001
.900	-2.784	- .95246	- .95156	- .95030	- .95093	- .33574	- .33537	- .33485	- .33511	1229.79300	1273.14999
.900	-1.783	- .94203	- .94087	- .93960	- .94023	- .21388	- .21309	- .21275	- .21292	1232.27200	1273.35001
.900	- .778	- .93123	- .93046	- .92903	- .92974	- .09265	- .09124	- .09084	- .09104	1233.18500	1272.63000
.900	- .229	- .93304	- .93212	- .93070	- .93141	- .02440	- .02194	- .02168	- .02181	1233.26100	1272.95000
.900	.808	- .93124	- .93026	- .92950	- .92950	.10014	.09970	.10021	.09995	1232.88800	1273.39999
.900	1.812	- .93465	- .93347	- .93210	- .93279	.22235	.22260	.22307	.22283	1230.97000	1272.85001
.900	2.821	- .93794	- .93764	- .93702	- .93702	.34259	.34250	.34296	.34273	1228.53400	1272.78000
.900	3.820	- .94060	- .94074	- .93941	- .94007	.46512	.46380	.46457	.46418	1225.00301	1272.66000
	GRADIENT	.00292	.00289	.00291	.00290	.12078	.12042	.12047	.12044	-.24950	-.03671

RUN NO. 1741/ 0 RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.099	-3.936	- .97337	- .97363	- .97210	- .97286	- .47631	- .47433	- .47387	- .47410	1159.52600	1205.35699
1.100	-2.917	- .96097	- .96058	- .95914	- .95986	- .35498	- .35353	- .35422	- .35422	1162.42799	1205.15100
1.100	-1.913	- .95301	- .95261	- .95117	- .95189	- .23260	- .23207	- .23234	- .23234	1164.22200	1204.63200
1.101	- .911	- .94488	- .94454	- .94293	- .94373	- .10885	- .10814	- .10754	- .10784	1165.39799	1204.53101
1.099	- .087	- .94470	- .94440	- .94293	- .94367	- .00840	- .00681	- .00625	- .00653	1164.78700	1204.53700
1.099	.963	- .94363	- .94303	- .94163	- .94233	.12019	.11881	.11955	.11918	1164.43100	1204.71001
1.100	1.957	- .94594	- .94552	- .94410	- .94481	.24359	.24270	.24355	.24313	1163.11099	1204.92400
1.099	2.958	- .94717	- .94607	- .94748	- .94678	.36522	.36372	.36366	.36369	1160.50400	1204.61400
1.100	3.965	- .94711	- .94626	- .94774	- .94700	.48775	.48655	.48605	.48605	1157.26900	1204.63600
	GRADIENT	.00275	.00268	.00269	.00269	.12233	.12189	.12187	.12188	-.30837	-.06358

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 818

(UCM058) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1725/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.249	-3.888	-1.05630	-1.05430	-1.05306	-1.05368	-5.1927	-5.1628	-5.1641	1136.56500	1182.77000
1.250	-2.831	-1.05040	-1.04727	-1.04593	-1.04660	-37745	-37592	-37572	1138.27800	1182.28200
1.250	-1.820	-1.03978	-1.03711	-1.03592	-1.03651	-24278	-24156	-24127	1140.49500	1182.55600
1.250	-821	-1.03141	-1.02849	-1.02723	-1.02786	-10843	-10703	-10675	1141.99300	1182.51500
1.250	-178	-1.02624	-1.02340	-1.02198	-1.02269	-02042	-01900	-01826	-01863	-1141.76401
1.250	.872	-1.02678	-1.02393	-1.02266	-1.02329	-11713	-11693	-11732	-1140.80099	-1182.59200
1.250	1.869	-1.02944	-1.02628	-1.02490	-1.02559	.25261	.25185	.25254	.25219	.1139.17799
1.250	1.249	2.876	-1.03298	-1.02999	-1.02851	.38504	.38215	.38259	.1136.70300	.1182.34500
1.250	3.887	-1.03361	-1.03159	-1.03037	-1.03097	.51621	.51711	.51666	.1133.40100	.1182.61301
GRADIENT	.00291	.00292	.00293	.00292	.00293	.13367	.13292	.13296	.37663	-.00380

RUN NO. 1717/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.400	-3.903	-1.20070	-1.19761	-1.19596	-1.19679	-58459	-58114	-58216	-58165	1117.05800
1.400	-2.844	-1.19334	-1.19146	-1.18987	-1.19067	-42467	-42154	-42242	-42198	1119.03000
1.400	-1.841	-1.18519	-1.18326	-1.18178	-1.18252	-26885	-26753	-26841	-26797	1121.77400
1.400	-.835	-1.17602	-1.17382	-1.17245	-1.17313	-11928	-11699	-11790	-11722	.89301.1164.34599
1.400	-.159	-1.17429	-1.17223	-1.17079	-1.17151	-01113	-.00730	-.00771	1123.78999	.1164.66901
1.400	.885	-1.17582	-1.17378	-1.17209	-1.17293	.14235	.14395	.14324	.14360	.1122.72900
1.400	1.888	-1.17743	-1.17524	-1.17384	-1.17454	.29700	.29711	.29643	.29677	.1121.25000
1.400	2.883	-1.18186	-1.17879	-1.17734	-1.17807	.44894	.44773	.44718	.44746	.1118.78799
1.400	3.894	-1.18186	-1.17916	-1.17762	-1.17839	.60218	.60177	.60198	.1114.98599	.1164.20399
GRADIENT	.00217	.00221	.00220	.00220	.00220	.15219	.15171	.15178	.15174	-.18595

RUN NO. 1707/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.450	-3.759	-1.29264	-1.29048	-1.28904	-1.28976	-60677	-60359	-60464	-60412	1109.01500
1.450	-2.736	-1.27950	-1.27670	-1.27535	-1.27603	-44425	-44068	-44155	-44111	1112.97900
1.450	-1.725	-1.26800	-1.26436	-1.2632	-1.26374	-27500	-27761	-27609	-27555	1114.07300
1.450	-.724	-1.25420	-1.24993	-1.24941	-1.24967	-11384	-11649	-11478	-11431	1114.71201
1.450	-.271	-1.24625	-1.24201	-1.24132	-1.24167	-03290	-03202	-03246	-03246	1113.29401
1.450	.768	-1.25210	-1.24788	-1.24726	-1.24757	.12768	.12818	.12762	.12790	.1112.57800
1.450	1.777	-1.25310	-1.25047	-1.24997	-1.25022	.29129	.29190	.29131	.29160	.1110.90900
1.450	2.768	-1.25478	-1.25259	-1.25134	-1.25196	.44861	.44906	.44817	.44861	.1107.72099
1.450	3.794	-1.25351	-1.25139	-1.25033	-1.25086	.61240	.61223	.61188	.61214	.1103.31599
GRADIENT	.00469	.00461	.00456	.00456	.00459	.16177	.16128	.16134	.16131	-.85799

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM058) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1700/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-8.000	PHI =	180.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.469	-3.779	-1.32508	-1.32231	-1.32093	-1.32162	-62501	-62180	-62269	-62225	1105.19600 1148.21672
1.469	-2.756	-1.31080	-1.30858	-1.30746	-1.30802	-45740	-45474	-45590	-45532	1108.08501 1148.11325
1.470	-1.751	-1.30243	-1.29997	-1.29883	-1.29940	-28733	-28606	-28705	-28655	1110.30200 1148.25621
1.470	-1.739	-1.29478	-1.29249	-1.29134	-1.29191	-12246	-11989	-12093	-12041	1111.43500 1148.16594
1.469	-1.254	-1.31073	-1.30849	-1.30710	-1.30779	-02676	-02349	-02444	-02396	1111.42101 1148.35963
1.469	.796	-1.31653	-1.31427	-1.31318	-1.31372	-14278	-14334	-14259	-14296	1109.67400 1148.56691
1.470	1.798	-1.31620	-1.31392	-1.31292	-1.31342	-31245	-31296	-31237	-31266	1107.35600 1148.04492
1.470	2.797	-1.31655	-1.31377	-1.31243	-1.31310	-48081	-48031	-47954	-47993	1104.50101 1148.14970
1.470	3.814	-1.31538	-1.31237	-1.31126	-1.31181	-64712	-64625	-64567	-64596	1100.92000 1148.19511
GRADIENT		-0.00040	-0.00035	-0.00037	-0.00036	.16823	.16769	.16776	.16773	-.65114 -.00158

	RUN NO.	1693/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-8.000	PHI =	180.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.498	-3.792	-1.35485	-1.35192	-1.35088	-1.35140	-63566	-63101	-63233	-63167	1096.44000 1147.79013
1.497	-2.773	-1.34147	-1.33879	-1.33762	-1.33821	-46076	-45686	-45803	-45745	1097.30400 1147.23509
1.497	-1.764	-1.33167	-1.32916	-1.32791	-1.32853	-29157	-28951	-29049	-29000	1098.74899 1146.97708
1.496	-.758	-1.32513	-1.32216	-1.32104	-1.32160	-12244	-11984	-12083	-12034	1100.13600 1147.17892
1.494	-.240	-1.32221	-1.31961	-1.31837	-1.31899	-02701	-02362	-02468	-02415	1098.68201 1147.66681
1.495	-.813	-1.33290	-1.33005	-1.32883	-1.32944	-14441	-14454	-14459	-14502	1097.86501 1147.76425
1.496	1.807	-1.33111	-1.33068	-1.32938	-1.33003	-31787	-31738	-31653	-31695	1096.05099 1147.45732
1.495	2.811	-1.33410	-1.33160	-1.33032	-1.33096	-48665	-48473	-48404	-48439	1094.17300 1147.19783
1.496	3.820	-1.33202	-1.32955	-1.32823	-1.32889	-65296	-65196	-65231	-65270	1090.46700 1146.60088
GRADIENT		.00184	.00179	.00182	.00180	.16954	.16875	.16883	.16879	-.73752 -.06508

	RUN NO.	1688/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-8.000	PHI =	180.000
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.521	-3.835	-1.41876	-1.41427	-1.41321	-1.41374	-67973	-67590	-67738	-67664	1094.10100 1142.48389
1.521	-2.770	-1.43008	-1.42524	-1.42420	-1.42472	-49021	-48576	-48686	-48631	1096.61099 1142.84561
1.520	-1.767	-1.43047	-1.42571	-1.42482	-1.42527	-30572	-30265	-30377	-30321	1098.89900 1142.55132
1.520	-.756	-1.43159	-1.42707	-1.42604	-1.42655	-12577	-12234	-12352	-12293	1100.58900 1142.67285
1.520	-.234	-1.49237	-1.48754	-1.48683	-1.48718	-02785	-02484	-02586	-02535	1104.57001 1143.20517
1.521	.803	-1.49639	-1.49161	-1.49099	-1.49130	-16138	-16141	-16062	-16101	1103.90199 1143.01251
1.521	1.812	-1.50076	-1.49597	-1.49502	-1.49550	-35589	-35504	-35418	-35461	1103.14301 1143.38101
1.520	2.823	-1.48737	-1.48255	-1.48181	-1.48218	-54417	-54181	-54165	-54173	1100.53600 1143.09613
1.520	3.821	-1.47751	-1.47268	-1.47185	-1.47226	-72383	-72275	-72329	-72309	1100.73300 1143.08263
GRADIENT		-.01054	-.01053	-.01055	-.01053	.18411	.18320	.18330	.18325	.57550 .08891

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 820

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM058) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1681/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-8.000	PHI =	180.000	
MACH	BETA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.543	-3.791	-1.62912	-1.62336	-1.62357	-1.62357	-77259	-76887	-77011	-76949	1111.86301	1138.09276
1.545	-2.772	-1.59901	-1.59182	-1.59187	-1.59187	-57505	-57189	-57306	-57247	1109.51401	1135.43391
1.544	-1.765	-1.58739	-1.58022	-1.57952	-1.57987	-37743	-37501	-37604	-37553	1110.07201	1135.76099
1.543	-1.758	-1.57502	-1.56793	-1.56747	-1.56770	-17372	-17146	-17271	-17208	1110.85100	1136.20688
1.542	-1.236	-1.51634	-1.51068	-1.51027	-1.51027	-04144	-03942	-04035	-03988	1112.32600	1137.15265
1.544	.806	-1.52982	-1.52384	-1.52316	-1.52350	-14673	-14689	-14614	-14652	1112.53101	1136.94943
1.543	1.817	-1.53212	-1.52599	-1.52521	-1.52560	-35689	-35583	-35500	-35542	1111.97301	1136.97073
1.543	2.816	-1.56218	-1.55621	-1.55547	-1.55584	-56301	-56069	-56021	-56045	1111.58400	1136.84470
1.544	3.829	-1.59500	-1.58832	-1.58795	-1.58814	-78498	-78196	-78172	-78184	1110.71001	1136.53670
GRADIENT	.00676	.00675	.00679	.00677	.00677	.20420	.20326	.20339	.20333	.11150	.01198

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM059) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1676/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	2.000	PHI =	180.000	
MACH	BETA	DPA CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
.600	-4.121	.14554	.14504	.14671	.14587	.35933	.35666	.35631	.35648	1592.43800	1597.48000
.600	-3.141	.14225	.14270	.14440	.14355	.26768	.26623	.26636	.26630	1594.15100	1597.14999
.600	-2.191	.14185	.14263	.14406	.14334	.17947	.17793	.17813	.17803	1595.35001	1596.96001
.600	-1.256	.14493	.14554	.14709	.14632	.09473	.09287	.09290	.09289	1595.88699	1597.10001
.600	-.303	.15402	.15472	.15639	.15555	.00955	.00752	.00784	.00768	1596.12199	1596.67999
.600	.734	.16861	.16913	.17128	.17021	.08135	.08218	.08225	.08221	1596.18900	1597.11000
.600	1.785	.17648	.17706	.17923	.17814	.17937	.17959	.17967	.17963	1595.96800	1596.82001
.600	2.833	.18523	.18619	.18782	.18701	.27650	.27735	.27741	.27738	1595.05099	1596.52000
.600	3.873	.18943	.18956	.19122	.19039	.37074	.37057	.37081	.37069	1593.06599	1597.12000
GRADIENT	.00668	.00673	.00677	.00675	.00675	.09102	.09074	.09075	.09075	.10221	-.05924

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM059) ( 04 OCT 91 )

## PARAMETRIC DATA

		RUN NO.		RN/L =		2.50		GRADIENT INTERVAL =		-5.00/ 5.00		ALPHA =		2.000		PHI =		180.000	
MACH	BETA	DPA1	DPA1	DPA2	DPA	DPA1	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F						
.799	-4.086	.18159	.18205	.18342	.18274	.42286	.42078	.42119	.42099	.7099	.74001								
.800	-3.097	.17852	.17808	.17920	.17914	.31398	.31292	.31315	.31304	.01900	.01900	1341.45000							
.800	-2.136	.17540	.17596	.17795	.17696	.20925	.20724	.20734	.20729	.60699	.60699	1341.52000							
.800	-1.188	.17856	.17929	.18144	.18036	.10767	.10531	.10554	.10543	.04700	.04700	1341.14000							
.800	-228	.18560	.18685	.18838	.18761	.00474	.00210	.00229	.00220	.94701	.94701	1341.03999							
.800	.795	.19829	.19829	.19931	.20092	.20012	.10463	.10553	.10572	.10563	.98000	.98000	1341.06000						
.800	1.840	.20627	.20653	.20810	.20732	.21837	.21930	.21922	.21926	.50400	.50400	1340.85001							
.800	2.888	.21442	.21444	.21588	.21516	.33470	.33539	.33514	.33526	.49600	.49600	1340.73000							
.800	3.918	.22079	.22112	.22255	.22184	.44707	.44735	.44707	.44716	.43700	.43700	1340.89999							
GRADIENT	.00581	.00582	.00582	.00576	.00579	.10849	.10819	.10821	.10820	.05719	.05719	-.04940							
		RUN NO.	1665/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00												
MACH	BETA	DPA1	DPA1	DPA2	DPA	DPA1	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F						
.900	-4.089	.18771	.18685	.18847	.18766	.44173	.43772	.43780	.43776	.00999	.00999	1273.16000							
.900	-3.100	.18507	.18409	.18569	.18489	.32847	.32557	.32583	.32570	.30000	.30000	1273.50000							
.900	-2.142	.18318	.18214	.18387	.18300	.21679	.21453	.21466	.21460	.20700	.20700	1273.17000							
.900	-1.199	.18710	.18710	.18525	.18701	.18613	.11104	.10880	.10882	.1271.70300	.70300	1273.12000							
.900	-.236	.19626	.19440	.19597	.19518	.00469	.00297	.00317	.00307	.86800	.86800	1273.03999							
.900	.798	.20738	.20559	.20734	.20646	.11068	.11050	.11068	.11059	.71600	.71600	1272.89000							
.900	1.841	.21525	.21385	.21554	.21470	.22708	.22779	.22783	.22781	.56900	.56900	1272.80000							
.900	2.881	.22372	.22239	.22403	.22321	.34622	.34677	.34677	.34675	.77200	.77200	1273.06000							
.900	3.911	.23080	.22988	.23163	.23076	.46338	.46274	.46295	.46285	.73399	.73399	1272.86000							
GRADIENT	.00625	.00622	.00622	.00623	.00623	.11274	.11222	.11226	.11224	.07594	.07594	-.05788							
		RUN NO.	1744/ 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00												
MACH	BETA	DPA1	DPA1	DPA2	DPA	DPA1	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F						
1.099	-4.031	.20639	.20459	.20635	.20547	.44035	.43690	.43662	.43676	.04401	.04401	1204.87300							
1.100	-3.023	.19989	.19791	.19960	.19875	.32336	.32115	.32114	.32115	.89200	.89200	1204.70300							
1.100	-2.051	.19599	.19335	.19505	.19420	.20844	.20713	.20704	.20709	.96700	.96700	1204.70399							
1.100	-1.082	.19652	.19368	.19543	.19456	.09906	.09749	.09736	.09743	.67200	.67200	1204.82899							
1.100	-.106	.19961	.19694	.19868	.19781	.01014	.00925	.00964	.00945	.80000	.80000	1204.74001							
1.100	.920	.20524	.20226	.20422	.20324	.12522	.12460	.12487	.12473	.76601	.76601	1204.82300							
1.100	1.944	.20746	.20529	.20701	.20615	.24109	.24067	.24114	.24091	.48801	.48801	1204.67000							
1.100	1.099	.21370	.21554	.21370	.21462	.36049	.35994	.35954	.35974	.64799	.64799	1204.68401							
1.100	2.966	.22193	.22078	.22193	.21993	.47740	.47786	.47786	.47763	.57899	.57899	1204.67900							
1.100	3.982	.22126	.22080	.22126	.21993	.47740	.47786	.47786	.47763	.11362	.11362	1204.01521							
GRADIENT	.00233	.00233	.00232	.00232	.00232	.11240	.11226	.11226	.11224	.08777	.08777	-.01521							

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM059) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO. 1728/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.250	-4.076	.21231	.21061	.21229	.21145	.48135	.47877	.47879	.47878	1176.29900	1182.40199
1.250	-3.075	.20577	.20445	.20629	.20537	.35602	.35485	.35394	.35439	1178.24699	1182.60500
1.250	-2.107	.20355	.20244	.20422	.20333	.23278	.23198	.23201	.23199	1179.59000	1182.36301
1.250	-1.162	.20575	.20480	.20652	.20566	.11874	.11680	.11691	.11685	1180.40601	1182.60800
1.250	-1.197	.21540	.21429	.21429	.21510	.00088	.00313	.00323	.00318	1180.81900	1182.75800
1.250	.834	.22631	.22526	.22687	.22606	.12719	.12736	.12771	.12753	1180.46001	1182.34399
1.250	1.866	.23520	.23348	.23533	.23440	.25497	.25479	.25521	.25500	1180.24899	1182.32001
1.250	2.910	.24210	.24049	.24225	.24137	.38838	.38613	.38660	.38637	1179.37500	1182.82800
1.250	3.938	.24919	.24714	.24899	.24807	.51773	.51533	.51561	.51547	1177.26900	1182.51601
GRADIENT	.00571	.00565	.00565	.00565	.00565	.12429	.12372	.12373	.12373	.13546	.01285

RUN NO. 1720/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.400	-4.068	.24319	.24046	.24249	.24148	.55095	.54546	.54709	.54628	1159.18900	1164.48900
1.400	-3.065	.23484	.23185	.23388	.23287	.40449	.39906	.40066	.39986	1160.59900	1164.03900
1.400	-2.100	.23029	.22761	.22952	.22856	.26137	.25810	.25932	.25871	1161.19400	1164.08800
1.400	-1.151	.23488	.23196	.23398	.23297	.13116	.12729	.12879	.12804	1161.73100	1164.26500
1.400	-1.177	.24346	.24049	.24240	.24144	.00788	.00885	.00768	.00782	1162.04700	1164.47400
1.400	.855	.25227	.24925	.25136	.25030	.15174	.15312	.15209	.15261	1161.67799	1164.10899
1.400	1.884	.26020	.25729	.25909	.25819	.29519	.29693	.29576	.29635	1161.98399	1164.52000
1.400	2.919	.27320	.27028	.27217	.27123	.44588	.44647	.44541	.44594	1161.69501	1164.21001
1.400	3.945	.28136	.27821	.28038	.27929	.59647	.59703	.59576	.59640	1160.00200	1163.87300
GRADIENT	.00579	.00575	.00575	.00575	.00575	.14233	.14233	.14167	.14173	.13018	-.02130

RUN NO. 1710/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.450	-4.110	.24369	.24110	.24285	.24198	.59552	.59116	.59281	.59198	1152.14400	1158.09399
1.449	-3.124	.23735	.23560	.23657	.23657	.43927	.43617	.43754	.43686	1154.37100	1158.75400
1.450	-2.172	.23440	.23269	.23469	.23369	.28953	.28719	.28886	.28802	1153.93401	1158.52600
1.449	-1.245	.24215	.24013	.24196	.24104	.15014	.14655	.14802	.14728	1154.24699	1158.39301
1.449	-287	.25671	.25591	.25751	.25671	.00372	.00033	.00104	.00036	1154.67300	1158.38499
1.450	.743	.27258	.27133	.27326	.27230	.15184	.15412	.15291	.15351	1154.30099	1158.30299
1.450	1.791	.28481	.28265	.28440	.28353	.31098	.31174	.31039	.31106	1154.21300	1158.10800
1.450	2.852	.30107	.29808	.30000	.29904	.47657	.47572	.47430	.47501	1155.64700	1158.61400
1.449	3.891	.30809	.30684	.30595	.30595	.63815	.63595	.63679	.63747	1154.40100	1158.89200
GRADIENT	.00975	.00965	.00964	.00964	.00964	.15333	.15291	.15294	.15293	.22321	.03194

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 823

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(LUCM059) (04 OCT 91)

## PARAMETRIC DATA

		RN NO.	1703/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	2.000	PHI =	180.000	PTTF	
MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	DPB	PTTF	
1.484	-4.105	.24548	.24548	.24467	.60180	.59767	.59950	.59859	.1145	.94800	.1167	.11589	
1.470	-3.111	.23937	.23755	.23846	.44517	.44006	.44161	.44084	.1146	.52901	.1148	.77704	
1.470	-2.157	.23774	.23532	.23616	.29607	.29216	.29378	.29297	.1147	.56000	.1148	.69630	
1.470	-1.226	.24593	.24340	.24433	.15054	.14759	.14918	.14838	.1147	.09000	.1148	.77380	
1.485	-.265	.25948	.25689	.25778	.00017	.00176	.00017	.00097	.1146	.67700	.1166	.89597	
1.471	.759	.277703	.27409	.27508	.15722	.15690	.15553	.15622	.1147	.45900	.1148	.69275	
1.470	1.813	.29013	.28719	.28916	.31803	.32067	.31926	.31997	.1148	.36600	.1148	.83116	
1.470	2.863	.30044	.29792	.29987	.48153	.48283	.48156	.48220	.1147	.92000	.1148	.75305	
1.484	3.899	.30527	.30483	.30652	.65003	.65051	.64933	.64992	.1147	.67400	.1167	.18317	
GRADIENT		.00936	.00939	.00940	.15573	.15521	.15528	.15524	.21781	.01880			
MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	DPB	PTTF	
1.495	-4.100	.25420	.25253	.25409	.63436	.63019	.63194	.63107	.1136	.63400	.1146	.07716	
1.495	-3.103	.25070	.24925	.25097	.25011	.47678	.47106	.47196	.1137	.22501	.1146	.32483	
1.495	-2.146	.24942	.24782	.24954	.24868	.31862	.31424	.31508	.1137	.23500	.1145	.84309	
1.494	-1.213	.25921	.25755	.25909	.25832	.16501	.16194	.16274	.1137	.09000	.1144	.45731	
1.494	-.258	.27707	.27545	.27726	.27635	.00888	.00674	.00818	.00746	.1137	.01500	.1144	.92178
1.495	.779	.29474	.29264	.29427	.29346	.16591	.16585	.16513	.1137	.49699	.1146	.12314	
1.495	1.819	.30760	.30520	.30686	.30603	.33414	.33587	.33510	.1138	.41400	.1146	.38834	
1.495	2.874	.31925	.31723	.31887	.31805	.50999	.51042	.50979	.1139	.15601	.1146	.12791	
1.495	3.907	.32483	.32360	.32532	.32446	.68398	.68379	.68313	.1138	.07800	.1146	.34996	
GRADIENT		.01071	.01068	.01069	.01069	.16484	.16414	.16421	.16417	.24063	.05815		
MACH	BETA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	DPB	DPB	DPB	PTTF	
1.521	-4.099	.29823	.29661	.29822	.29742	.72380	.71767	.71946	.71856	.1128	.77100	.1143	.26253
1.521	-3.103	.30173	.30112	.30258	.30185	.56724	.56200	.56396	.56298	.1129	.49001	.1143	.38091
1.521	-2.151	.30541	.30533	.30692	.30613	.38312	.37835	.38013	.37924	.1129	.14400	.1143	.24701
1.521	-1.215	.31275	.31258	.31406	.31332	.19608	.19388	.19552	.19470	.1128	.94200	.1142	.98817
1.521	-.256	.33154	.33134	.33212	.33212	.02401	.02048	.02220	.02134	.1129	.02299	.1142	.86571
1.521	.778	.35419	.35373	.35450	.35411	.17059	.17124	.16966	.17045	.1129	.21500	.1143	.46280
1.521	1.826	.36722	.36589	.36753	.36671	.38717	.38615	.38479	.38547	.1129	.57401	.1143	.49106
1.521	2.875	.36799	.36591	.36745	.36668	.59346	.59356	.59220	.59288	.1130	.07800	.1143	.05910
1.521	3.907	.36505	.36192	.36369	.36281	.78306	.78194	.78068	.78131	.1130	.00101	.1143	.24898
GRADIENT		.01052	.01030	.01030	.01030	.19062	.18966	.18975	.18971	.13228	-.00034		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 824

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM059) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1684/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	2.000	PHI =	180.000
MACH	BETA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.544	-4.099	.33497	.33434	.33575	.33505	.65050	.64635	.64816	.84700	1137.05458
1.544	-3.108	.24584	.24614	.24766	.24690	.39336	.38875	.39046	.25800	1136.99420
1.544	-2.147	.21132	.21017	.21157	.21087	.23510	.23255	.23421	.25299	1137.15039
1.544	-1.209	.20282	.20268	.20436	.20352	.12108	.11719	.11882	.63901	1137.18553
1.544	-2.250	.21483	.21455	.21599	.21527	.01423	.01061	.01234	.43401	1136.98732
1.544	.782	.23019	.22879	.23037	.22958	.11016	.11121	.10981	.78300	1137.59277
1.544	1.820	.25229	.25166	.25335	.25250	.24113	.24317	.24187	.32300	1137.48898
1.544	2.879	.30603	.30447	.30600	.30524	.41292	.41193	.41041	.08200	1137.31323
1.544	3.907	.34229	.34128	.34238	.34183	.61765	.61651	.61533	.17500	1137.28635
GRADIENT	.00566	.00553	.00552	.00553	.00553	.14480	.14409	.14416	.16339	.04929

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM060) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1729/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
1.250	-5.036	.65798	-.655675	-.65511	-.65593	.09534	.09389	.09331	.03200	1182.73900
1.250	-4.776	.62359	-.62263	-.62070	-.62166	.09564	.09415	.09364	.18700	1182.47099
1.250	-4.525	.59321	-.59215	-.59127	-.59127	.09296	.09119	.09069	.40601	1167.40601
1.249	-4.279	.56192	-.56134	-.55975	-.56054	.09349	.09177	.09133	.168	1168.65800
1.250	-4.029	.52945	-.52874	-.52705	-.52789	.09113	.08943	.08912	.97800	1182.79500
1.250	-3.788	.49832	-.49751	-.49595	-.49673	.09178	.09009	.08974	.08992	1171.13300
1.250	-3.537	.46524	-.46457	-.46293	-.46375	.09200	.09002	.08963	.35300	1182.24600
1.250	-3.289	.43313	-.43261	-.43099	-.43180	.09137	.08949	.08927	.56200	1182.26300
1.250	-3.041	.40118	-.40006	-.39846	-.39926	.09147	.08954	.08922	.44501	1182.66701
GRADIENT	.12880	.12874	.12860	.12867	.12867	.00197	.00204	.00211	.84789	.04647

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

(UCMO61) ( 04 OCT 91 )

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

## PARAMETRIC DATA

	RUN NO.	1730/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- .750	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-65587	-65445	-65282	-65364	-60130	-06306	-05979	-06008	1165.25301	1182.74001
1.250	-5.032	-6.2055	-6.1897	-6.1976	-0.6319	-0.6164	-0.6126	-0.6145	1166.47600	1182.53200
-4.767	-6.2182	-5.9057	-5.8982	-5.8982	-0.6185	-0.5998	-0.5956	-0.5977	1167.60400	1182.67101
1.250	-4.519	-5.5906	-5.5867	-5.5716	-0.6106	-0.5981	-0.5921	-0.5951	1168.89000	1182.67101
-4.271	-5.5906	-5.2825	-5.2723	-5.2551	-0.5903	-0.5755	-0.5708	-0.5732	1170.11301	1182.66200
1.250	-4.022	-4.9518	-4.9442	-4.9277	-0.5816	-0.5636	-0.5615	-0.5626	1171.49899	1182.46600
-3.774	-4.9518	-4.6190	-4.6026	-4.6108	-0.5927	-0.5769	-0.5719	-0.5744	1172.67500	1182.48199
1.250	-3.525	-4.6259	-4.3064	-4.2975	-0.5903	-0.5718	-0.5674	-0.5696	1173.81700	1182.70100
-3.276	-4.3144	-3.9847	-3.9757	-3.9570	-0.5790	-0.5629	-0.5609	-0.5619	1174.84801	1182.73801
1.250	-3.027	-3.9847	-3.2874	-1.2860	.00274	.00282	.00274	.00274	4.90353	.03950
GRADIENT	1.2874	1.2851	1.2869	1.2859						

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

## PARAMETRIC DATA

	RUN NO.	1731/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- .500	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-65317	-65196	-65043	-65120	-03152	-03098	-03049	-03073	1165.27699	1182.69099
1.250	-5.016	-6.1940	-6.1828	-6.1677	-0.3030	-0.2970	-0.2924	-0.2947	1166.52901	1182.43401
-4.758	-6.1940	-5.8933	-5.8804	-5.8722	-0.2866	-0.2718	-0.2668	-0.2693	1167.74800	1182.62900
1.250	-4.511	-5.5736	-5.5684	-5.5518	-0.2961	-0.2802	-0.2763	-0.2782	1169.14900	1182.50900
-4.259	-5.5736	-5.2445	-5.2356	-5.2207	-0.2858	-0.2731	-0.2666	-0.2698	1170.30000	1182.48199
1.250	-4.007	-4.9359	-4.9265	-4.9112	-0.2807	-0.2643	-0.2608	-0.2625	1171.65700	1182.67700
-3.760	-4.9359	-4.6111	-4.6055	-4.5900	-0.2977	-0.2622	-0.2481	-0.2463	1172.94400	1182.54401
1.250	-3.513	-4.2881	-4.2763	-4.2676	-0.2617	-0.2475	-0.2442	-0.2458	1174.05200	1182.78101
-3.261	-4.2881	-3.9604	-3.9490	-3.9329	-0.2645	-0.2451	-0.2401	-0.2426	1174.89101	1182.50900
1.250	-3.019	-3.9604	-3.2847	-1.2850	.00240	.00282	.00278	.00280	4.91782	.07601
GRADIENT	1.2847									

(UCMO61) ( 04 OCT 91 )

(UCMO62) ( 04 OCT 91 )

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 826

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM063) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1732/ 0	RN/L =	2 . 50	GRADIENT INTERVAL = -5 . 00/ 5 . 00	BETA =	- . 250	PHI =	180 . 000
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	P12F
ALPHA									
-5 . 009	- . 65127	- . 65015	- . 64868	- . 64942	. 00028	. 0094	. 00157		
-4 . 752	- . 61761	- . 61636	- . 61479	- . 61557	. 00162	. 00229	. 00288		
-4 . 500	- . 58724	- . 58575	- . 58418	- . 58496	. 00210	. 00306	. 00340		
-4 . 249	- . 55471	- . 55404	- . 55238	- . 55321	. 00295	. 00390	. 00439		
-4 . 002	- . 52251	- . 52159	- . 52096	- . 52083	. 00295	. 00435	. 00484		
-3 . 751	- . 49090	- . 48986	- . 48826	- . 48906	. 00493	. 00492	. 00587		
-3 . 500	- . 45897	- . 45819	- . 45660	- . 45739	. 00295	. 00459	. 00538		
-3 . 254	- . 42653	- . 42540	- . 42360	- . 42450	. 00265	. 00457	. 00534		
-3 . 003	- . 39443	- . 39326	- . 39152	- . 39239	. 00322	. 00466	. 00555		
GRADIENT	. 12801	. 12791	. 12802	. 12797	. 00076	. 00127	. 00154	. 00141	. 4 . 85221 . 00634

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM064) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1733/ 0	RN/L =	2 . 50	GRADIENT INTERVAL = -5 . 00/ 5 . 00	BETA =	. 000	PHI =	180 . 000
MACH	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF	P12F
ALPHA									
-5 . 001	- . 64920	- . 64779	- . 64622	- . 64701	. 03190	. 03083	. 03150		
-4 . 738	- . 61565	- . 61443	- . 61282	- . 61363	. 03451	. 03395	. 03453		
-4 . 492	- . 58588	- . 58452	- . 58313	- . 58383	. 03402	. 03298	. 03365		
-4 . 240	- . 55258	- . 55179	- . 55035	- . 55107	. 03609	. 03503	. 03552		
-3 . 993	- . 52154	- . 52058	- . 51891	- . 51975	. 03494	. 03463	. 03542		
-3 . 737	- . 48866	- . 48804	- . 48623	- . 48714	. 03446	. 03470	. 03524		
-3 . 490	- . 45602	- . 45523	- . 45338	- . 45431	. 03605	. 03603	. 03667		
-3 . 239	- . 42406	- . 42280	- . 42127	- . 42203	. 03540	. 03572	. 03615		
-2 . 988	- . 39233	- . 39121	- . 38942	- . 39031	. 03505	. 03516	. 03574		
GRADIENT	. 12818	. 12811	. 12827	. 12819	. 00048	. 00115	. 00120	. 00118	. 4 . 86207 . 03118

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM065) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1734/ 0	RN/L =	2 . 50	GRADIENT INTERVAL =	- 5 . 00/ 5 . 00	BETA =	. 250	PHI =	180 . 000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA										
-4 . 991	- . 64696	- . 64574	- . 64415	- . 64495	- . 6440	- . 64340	- . 64401	. 06371	1165 . 22701	1182 . 55400
-4 . 732	- . 61314	- . 61192	- . 61043	- . 61118	- . 60588	- . 60492	- . 60545	. 06519	1166 . 48900	1182 . 48199
-4 . 485	- . 58250	- . 58129	- . 57955	- . 58042	- . 66770	- . 66556	- . 66735	. 06695	1167 . 93300	1182 . 50600
-4 . 232	- . 55019	- . 54967	- . 54877	- . 54877	- . 67556	- . 6753	- . 67773	. 1169 . 20900	1182 . 58299	
-4 . 250	- . 51859	- . 51744	- . 51575	- . 51659	- . 6835	- . 6804	- . 6858	. 06831	1170 . 55200	1182 . 45100
-3 . 979	- . 48613	- . 48529	- . 48371	- . 48450	- . 6728	- . 6696	- . 6763	. 06729	1171 . 85201	1182 . 58299
-3 . 732	- . 45391	- . 45298	- . 45128	- . 45213	- . 6708	- . 6658	- . 6735	. 06696	1173 . 19600	1182 . 58600
-3 . 479	- . 42198	- . 42094	- . 41931	- . 42012	- . 6547	- . 6552	- . 6619	. 06585	1174 . 13600	1182 . 89600
-3 . 226	- . 38971	- . 38867	- . 38695	- . 38781	- . 6497	- . 6539	- . 6565	. 06552	1175 . 13400	1182 . 46100
-2 . 977	- . 12750	- . 12741	- . 12745	- . 12743	- . 00003	- . 00061	- . 00056	. 00059	5 . 0 . 1999	. 06830
GRADIENT										

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM066) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1735/ 0	RN/L =	2 . 50	GRADIENT INTERVAL =	- 5 . 00/ 5 . 00	BETA =	. 500	PHI =	180 . 000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA										
-4 . 984	- . 64470	- . 64347	- . 64178	- . 64262	- . 60897	- . 60662	- . 60546	. 09601	1165 . 20700	1182 . 50999
-4 . 725	- . 61072	- . 60982	- . 60812	- . 60812	- . 57739	- . 57825	- . 60572	. 09636	1166 . 61700	1182 . 49699
-4 . 471	- . 58007	- . 577910	- . 57739	- . 57739	- . 57739	- . 57739	- . 60689	. 09758	1167 . 79201	1182 . 58501
-4 . 221	- . 54782	- . 54716	- . 54563	- . 54639	- . 54639	- . 54639	- . 60824	. 09778	1169 . 16901	1182 . 49600
-3 . 972	- . 51680	- . 51575	- . 51421	- . 51421	- . 48273	- . 48273	- . 60022	. 09915	1170 . 44501	1182 . 43800
-3 . 717	- . 48448	- . 48354	- . 48191	- . 48191	- . 45047	- . 45047	- . 60035	. 09952	1171 . 78900	1182 . 54800
-3 . 466	- . 45227	- . 45132	- . 44962	- . 44962	- . 41792	- . 41792	- . 60007	. 09961	1172 . 86700	1182 . 36400
-3 . 210	- . 42013	- . 38866	- . 38490	- . 38578	- . 38578	- . 38578	- . 60762	. 09752	1174 . 16299	1182 . 62500
-2 . 963	- . 12673	- . 12679	- . 12684	- . 12681	- . 00084	- . 00084	- . 09634	. 09689	1175 . 01300	1182 . 57899
GRADIENT								. 00092	. 00093	. 01795

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM067) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1736/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.750	PHI =	= 180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.250	-4.976	- .64340	- .64037	- .64113	- .12804	- .12776	- .12846	- .12811	1165.16701	1182.27901
1.250	-4.715	- .60921	- .60650	- .60730	- .12884	- .12811	- .12874	- .12843	1166.50000	1182.54700
1.250	-4.464	- .57914	- .57632	- .57713	- .13108	- .13028	- .13081	- .13054	1167.67500	1182.26700
1.250	-4.212	- .54625	- .54561	- .54476	- .13057	- .12970	- .13034	- .13002	1169.17599	1182.55901
1.250	-3.960	- .51370	- .51212	- .51291	- .13001	- .12942	- .12995	- .12968	1170.39600	1182.56200
1.250	-3.708	- .48339	- .48251	- .48074	- .13094	- .13043	- .13103	- .13073	1171.70500	1182.54401
1.250	-3.453	- .45052	- .44968	- .44817	- .12971	- .12891	- .12956	- .12923	1172.94800	1182.46400
1.250	-3.203	- .41900	- .41770	- .41595	- .12919	- .12838	- .12898	- .12868	1173.94501	1182.41100
1.250	-2.947	- .38653	- .38537	- .38366	- .128451	- .12837	- .12749	- .12784	1175.21201	1182.57001
GRADIENT		.12637	.12628	.12635	.12632	.00000	.00000	.000015	.4.97958	.07482

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(UCM068) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1737/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	= 180.000
MACH	ALPHA	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.250	-4.968	- .64223	- .64087	- .63928	- .64008	- .16119	- .16046	- .16107	.16076	1164.89200
1.250	-4.705	- .60861	- .60742	- .60573	- .60658	- .16070	- .16022	- .16094	.16058	1166.30200
1.250	-4.455	- .57712	- .57663	- .57502	- .57583	- .16194	- .16097	- .16156	.16127	1167.55800
1.250	-4.206	- .54490	- .54436	- .54268	- .54352	- .16143	- .16088	- .16139	.16113	1168.85400
1.250	-3.950	- .51348	- .51243	- .51081	- .51162	- .16163	- .16095	- .16161	.16128	1170.10001
1.250	-3.694	- .48138	- .48048	- .47897	- .47972	- .16119	- .16046	- .16120	.16083	1171.37300
1.250	-3.440	- .44997	- .44890	- .44733	- .44811	- .16075	- .15995	- .16059	.16027	1172.76401
1.250	-3.190	- .41799	- .41637	- .41553	- .41522	- .16026	- .15940	- .16010	.15975	1173.86200
1.250	-2.938	- .38542	- .38434	- .38267	- .38351	- .15868	- .15801	- .15861	.15831	1175.08099
GRADIENT		.12607	.12601	.12602	.12601	.00092	.00097	.00095	.5.0239	.06172

## IA310 (AEDC 16TF-783) REPEAT RUNS

(UCM069) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1671/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.599	-7.999	-7.4352	-74204	-74064	-.74134	.02558	.02544	.02573	1561.97000	1596.97000
.599	-6.982	-65465	-65369	-65220	-.65295	.03003	.02960	.02986	1569.05000	1597.05000
.599	-5.975	-56136	-56053	-55904	-.55979	.03024	.03101	.03116	1577.00600	1596.73000
.600	-4.979	-47232	-47038	-46891	-.46964	.03082	.03198	.03206	1582.81700	1597.17999
.600	-3.977	-38111	-37933	-37776	-.37855	.03213	.03324	.03339	1587.62000	1597.13000
.600	-2.974	-28592	-28697	-28511	-.28604	.03133	.03225	.03238	1591.48199	1597.00999
.600	-1.968	-19225	-19316	-19165	-.19240	.03468	.03525	.03550	1594.04500	1596.75999
.601	-949	-09779	-09805	-09639	-.09722	.03663	.03585	.03604	1595.45500	1597.09000
.600	-078	-02830	-02861	-02782	-.02782	.00399	-.00286	.00295	1596.36501	1597.06000
.600	.971	.06339	.06216	.06384	.06300	-.01265	-.01096	-.01113	1596.23199	1597.25999
.600	1.989	.15587	.15616	.15778	.15695	-.00900	-.00714	-.00739	1596.28799	1597.11000
.600	GRADIENT	.08998	.08969	.08971	.08970	-.00723	-.00714	-.00720	-.00717	1.84583 .00746

	RUN NO.	1747/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	5.00
MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.800	-7.999	-89440	-89193	-89117	-.89155	.02700	.02767	.02794	1301.38499	1341.16000
.800	-6.978	-78679	-78401	-78282	-.78342	.02527	.02465	.02504	1310.58800	1341.34000
.800	-5.977	-67420	-67259	-67111	-.67185	.03028	.02982	.03006	1318.62900	1340.89999
.800	-4.976	-56563	-56488	-56340	-.56414	.02998	.02944	.02965	1325.29300	1341.30000
.800	-3.981	-45691	-45578	-45432	-.45505	.03191	.03134	.03158	1330.69099	1341.22000
.800	-2.974	-34286	-34310	-34160	-.34235	.03102	.03165	.03180	1334.61000	1341.07001
.801	-1.972	-23287	-23251	-23111	-.23181	.03232	.03298	.03328	1337.52200	1341.22000
.800	-965	-12384	-12184	-12031	-.12108	.03402	.03437	.03458	1339.19200	1340.99001
.800	-147	-00670	-00535	-00530	-.00532	.01591	.01672	.01679	1339.75301	1340.66000
.800	.988	.07885	.07885	.08028	.07956	-.00662	-.00405	-.00429	1339.89000	1340.92999
.800	1.998	.18891	.18936	.19099	.19018	-.00324	-.00060	-.00102	1340.00500	1341.02000
.800	GRADIENT	.10808	.10803	.10799	.10801	-.00555	-.00510	-.00518	-.00514	1.98183 -.05896

	RUN NO.	1660/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	5.00
MACH	ALPHA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB1	DPB2	PTTF	PT2F
.900	-8.000	-92574	-92360	-92215	-.92288	.02567	.02631	.02687	.02659	1233.53600
.899	-6.979	-81207	-80936	-80821	-.80879	.03029	.03092	.03137	.03115	1242.73199
.900	-5.970	-69975	-69856	-69716	-.69786	.03200	.03240	.03265	.03265	1250.47000
.900	-4.971	-58531	-58380	-5830	-.58455	.03305	.03242	.03294	.03268	1256.92599
.900	-3.977	-47240	-47154	-47000	-.47077	.03560	.03567	.03585	.03576	1262.52699
.900	-2.966	-35490	-35330	-35419	-.35446	.03432	.03447	.03440	.03440	1266.60400
.900	-1.966	-24142	-24052	-23878	-.23965	.03484	.03468	.03496	.03482	1269.12601
.900	-955	-12738	-12604	-12444	-.12524	.03608	.03574	.03587	.03587	1271.33600
.900	-086	-03576	-03468	-03286	-.03377	-.00050	.00112	.00120	.00120	1271.41400
.900	.994	.08236	.08130	.08273	.08202	-.00707	-.00533	-.00539	-.00536	1271.11800
.900	2.003	.19734	.19576	.19751	.19663	-.00259	-.00100	-.00112	-.00106	1272.12199
.900	GRADIENT	.11171	.11172	.11171	.11171	-.00675	-.00640	-.00647	-.00644	1.99347 -.00445

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 830

(UCM069) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
MACH	DPACAL	DPACAL	DPACAL	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.099	-.94055	-.93989	-.93917	.01053	.01038	.01117	.01077	1165.99500	1205.11900
-8.003	-.82510	-.82205	-.82276	.01498	.01484	.01565	.01524	1175.26900	1205.08000
-6.975	-.71228	-.71138	-.71026	.01470	.01477	.01548	.01513	1182.63901	1204.73100
-5.975	-.59722	-.59608	-.59534	.01904	.01778	.01838	.01808	1188.99001	1204.55200
-4.978	-.47841	-.47812	-.47643	.01985	.01875	.01955	.01915	1194.33099	1204.67000
-3.968	-.47841	-.47812	-.47727	.02063	.01994	.02049	.02022	1198.38000	1204.65401
-2.977	-.36096	-.35983	-.35828	.02175	.02074	.02129	.02101	1201.33400	1204.63300
-1.970	-.24347	-.24347	-.24188	.02356	.02284	.02338	.02311	1203.02699	1204.82201
-1.971	-.13158	-.13092	-.13010	.02112	.02061	.02099	.02080	1203.63499	1204.80200
-1.000	-.02074	-.02060	-.01965	.02112	.02061	.02099	.02080	1203.85800	1204.75500
1.000	.041	.01870	.01870	.01170	.01130	.01169	.01150	1203.78000	1204.74200
1.000	1.007	.08678	.08489	.08573	.01140	.01145	.01122	1203.78000	1204.74200
1.000	2.014	.20119	.19887	.20041	.19964	.00096	-.000100	-.00098	2.01218 .02852
	GRADIENT	1.13383	.113383	.11339	-.00108	-.00096	-.000100	-.00098	2.01218 .02852

RUN NO.	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
1.250	-7.999	-1.02292	-1.02155	-1.02224	.02600	.02604	.02678	.02641
1.250	-6.974	-.90307	-.90027	-.89879	.03188	.03081	.03161	.03121
1.250	-5.971	-.77700	-.77480	-.77442	.03145	.03083	.03143	.03113
1.250	-4.969	-.64768	-.64596	-.64456	.03440	.03346	.03410	.03378
1.250	-3.973	-.52155	-.52047	-.51876	.03359	.03342	.03389	.03365
1.250	-2.972	-.39345	-.39247	-.39077	.03373	.03404	.03464	.03434
1.250	-1.970	-.26780	-.26634	-.26713	.03484	.03536	.03589	.03563
1.250	-.960	-.14468	-.14415	-.14253	.03724	.03737	.03789	.03763
1.250	-.118	-.01134	-.00964	-.01049	.02366	.02427	.02450	.02439
1.250	.996	.09469	.09321	.09498	.00106	.00331	.00344	.00337
1.250	2.008	.21829	.21727	.21892	.00238	.00448	.00456	.00452
	GRADIENT	.12400	.12361	.12363	.12362	-.00491	-.00451	-.00459
RUN NO.	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	PTTF
1.400	-7.997	-1.16864	-.1.16625	-.1.16504	-.1.16565	.03658	.03865	.03785
1.400	-6.974	-1.03194	-1.02871	-1.02727	-1.02799	.03914	.04117	.04050
1.400	-5.972	-.89042	-.88704	-.88594	-.88649	.04006	.04071	.04036
1.400	-4.974	-.74864	-.74584	-.74419	-.74501	.03784	.03821	.03776
1.400	-3.973	-.60343	-.60309	-.60146	-.60228	.04290	.04352	.04306
1.400	-2.972	-.45112	-.44832	-.44924	-.44924	.04154	.04237	.04132
1.400	-.972	-.30830	-.30895	-.30699	-.30797	.03951	.04033	.03936
1.400	-.966	-.16953	-.16905	-.16693	-.16799	.04046	.04243	.04136
1.399	-.111	-.02013	-.01966	-.01789	-.01877	.02653	.02913	.02786
1.400	.998	.10515	.10256	.10444	.10350	.00636	.00907	.00788
1.400	2.020	.24655	.24377	.24457	.24472	.00872	.01049	.00923
	GRADIENT	.14204	.14140	.14143	.14142	-.00510	-.00478	-.00484

IA310 (AEDC 16TF-783) REPEAT RUNS

IA310 (AEDC 16TF-783) REPEAT RUNS

PARAMETRIC DATA										
RUN NO.	1705 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	.000	PHI =	180 . 000
MACH	DIPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.24728	-1.24304	-1.24243	-1.24273	.05157	.05260	.05182	.05221	1114.93330	1158.28400
	-1.10133	-1.09817	-1.09705	-1.09761	.05356	.05304	.05221	.05262	1123.49600	1158.19501
	-5.971	-5.968	-5.963	-5.9485	.05539	.05507	.05424	.05465	1131.22200	1158.40601
	-4.971	-4.971	-4.972	-4.94639	.05525	.05668	.05583	.05626	1138.58800	1158.22701
	-3.968	-3.968	-3.964	-3.94882	.05863	.06053	.05951	.06002	1146.08501	1158.19901
	-2.965	-2.965	-2.963	-3.98828	.05845	.05702	.05894	.05775	.05834	.05834
	-1.961	-1.961	-1.961	-3.33556	.05694	.05648	.05822	.05870	1152.38600	1158.44600
	-9.94	-9.94	-9.94	-1.85774	.06175	.06404	.06287	.06345	1159.01300	1158.11000
	-0.91	-0.91	-0.91	-0.05227	.05049	.05138	.00555	.00676	.00739	.00739
	-0.974	-0.974	-0.974	-1.07664	.10951	.10857	.00671	.00255	.00388	.00321
	2.001	2.001	2.001	.25880	.26044	.25962	.00177	.00245	.00088	.00166
GRADIENT	.15259	.15259	.15213	.15214	.15213	.15213	.01043	.01004	.01013	.04212
	RUN NO.	1698 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00			
MACH	DIPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.28717	-1.28503	-1.28379	-1.28441	.04877	.05039	.04961	.05000	1111.54300	1150.24953
	-1.13953	-1.13744	-1.13639	-1.13691	.04923	.05096	.05004	.05050	1121.99001	1150.38181
	-5.972	-5.972	-5.972	-5.97439	.097287	.097363	.05038	.05103	1127.98000	1150.19312
	-4.970	-4.970	-4.970	-8.19960	.81742	.81590	.05749	.05607	.05656	.05656
	-3.973	-3.973	-3.973	-6.6076	.66029	.65865	.05947	.05871	.05757	.05814
	-2.970	-2.970	-2.970	-4.99717	.49740	.49558	.06167	.06152	.0616	.06084
	-1.962	-1.962	-1.962	-3.4154	.34190	.34034	.34112	.06021	.06026	.05910
	-0.947	-0.947	-0.947	-1.8575	-1.8688	-1.8511	.18600	.06406	.06402	.06276
	-0.149	-0.149	-0.149	-0.01888	-0.01887	-0.01720	.01804	.01012	.01038	.00913
	.980	.980	.980	.10544	.10346	.10525	.10436	.00006	.00178	.00019
	2.007	2.007	2.007	.26061	.25799	.25956	.25878	.00219	.00393	.00230
GRADIENT	.15463	.15463	.15409	.15410	.15409	.15409	.00991	.00960	.00968	.00964
	RUN NO.	1668 / 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00			
MACH	DIPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
ALPHA	-1.322751	-1.32236	-1.32144	-1.32190	.05297	.05096	.05185	.05140	1100.31599	1148.40784
	-1.18306	-1.17829	-1.17730	-1.17779	.06387	.06229	.06285	.06257	1109.54601	1148.33621
	-5.968	-5.966	-5.966	-5.02803	-1.02679	-1.02739	.06484	.06309	.06339	.06339
	-4.966	-4.966	-4.966	-8.74553	-.86986	-.86879	.06344	.06480	.06364	.06364
	-3.969	-3.969	-3.969	-7.1257	-.70876	-.70713	.06627	.06737	.06666	.06647
	-2.967	-2.967	-2.967	-5.3925	-.53735	-.53600	.06940	.06802	.06838	.06820
	-1.965	-1.965	-1.965	-3.7755	-.37461	-.37304	.06675	.06550	.06591	.06570
	-0.953	-0.953	-0.953	-2.1230	-.21094	-.21162	.07020	.06886	.06912	.06899
	-0.1866	-0.1866	-0.1866	-0.1749	-.01609	-.01679	.02772	.02674	.02674	.02674
	-1.61	-1.61	-1.61	-1.0321	-.10402	-.10329	.01438	.01540	.01447	.01447
	.878	.878	.878	.28164	.28003	.28164	.28083	-.00510	-.00414	.00424
GRADIENT	1.999	1.999	1.999	.16586	.16586	.16584	.16584	-.01040	-.01019	.01023

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 832

IA310 (AEDC 16TF-783) REPEAT RUNS

(UCM069) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.520	-7.997	-1.43389	-1.42929	-1.42839	-1.42884	.05842	.05955	.05856	.05906	1101.00000	1142.22244
1.520	-6.969	-1.30249	-1.29835	-1.29736	-1.29786	.06390	.06530	.06440	.06485	1110.20900	1141.90816
1.520	-5.968	-1.15625	-1.15042	-1.14916	-1.14979	.06296	.06324	.06231	.06278	1119.07800	1142.21899
1.520	-4.966	-1.98955	-1.98580	-1.98455	-1.98250	.06148	.06108	.06009	.06059	1122.93201	1141.91878
1.520	-3.970	-1.82760	-1.82325	-1.82175	-1.82250	.06559	.06499	.06386	.06443	1126.04601	1141.78221
1.520	-2.967	-1.63032	-1.62717	-1.62566	-1.62641	.06227	.06331	.06214	.06272	1127.33299	1142.12306
1.520	-1.965	-1.41809	-1.41582	-1.41433	-1.41508	.05233	.05355	.05225	.05290	1127.61501	1142.12224
1.520	-0.952	-1.19112	-1.19091	-1.18936	-1.19014	.03560	.03689	.03567	.03628	1128.60300	1142.31921
1.520	-0.0117	-0.0071	-0.0047	-0.00059	-0.00934	.01119	.00986	.01053	.0129.25500	1141.99414	
1.520	.984	.09723	.09592	.09771	.09682	-.01250	-.00895	-.01038	-.00967	1129.74200	1142.40054
1.520	2.000	.29858	.29906	.30049	.29978	-.03327	-.02919	-.03086	-.03002	1128.64700	1142.24260
	GRADIENT	1.8786	1.8713	1.8711	1.8712	-.01461	-.01396	-.01404	-.01400	.77977	.06088

RUN NO. 1679/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.545	-7.992	-1.56301	-1.55680	-1.55607	-1.55643	.05487	.05584	.05510	.05547	1112.14999	1135.98326
1.545	-6.974	-1.31451	-1.30891	-1.30795	-1.30843	.05871	.05913	.05828	.05871	1116.32600	1136.43317
1.545	-5.972	-1.04371	-1.03942	-1.03809	-1.03876	.03894	.03923	.03815	.03869	1117.21001	1136.02274
1.545	-4.971	-1.81404	-1.81115	-1.80985	-1.81050	.02047	.02125	.02024	.02074	1117.53200	1135.75661
1.545	-3.969	-1.61385	-1.61092	-1.60947	-1.61019	.02939	.02975	.02863	.02919	1118.24800	1135.19360
1.545	-2.968	-1.41415	-1.41160	-1.41017	-1.41088	.03062	.03159	.03044	.03101	1120.54201	1135.76976
1.545	-1.960	-1.26334	-1.26245	-1.26091	-1.26168	.02463	.02498	.02332	.02397	1118.74800	1135.64491
1.545	-0.952	-1.14656	-1.14396	-1.14251	-1.14323	.03473	.03556	.03432	.03494	1118.05200	1135.44736
1.545	-0.0341	.00328	.00491	.00409	.00449	.02357	.02520	.02385	.02453	1119.80901	1136.21504
1.545	.983	.10518	.10429	.10596	.10512	-.01576	-.01273	-.01441	-.01357	1119.10001	1136.21790
1.545	1.994	.20654	.20616	.20785	.20701	-.01458	-.01103	-.01253	-.01178	1120.00700	1136.50880
	GRADIENT	1.4441	1.4383	1.4388	1.4386	-.00566	-.00523	-.00531	-.00527	.22405	.13736

IA310 (AEDC 16TF-783) REPEAT RUNS

(UCM070) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1674 / O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-4.000	PHI	=	180.000
MACH	DPA CAL	DPA1	DPA2	DPA	DPBC AL	DPB1	DPB2	DPB	PTTF	PT2F
BETA	-3.798	-.41344	-.41204	-.41053	-.41128	-.344654	-.34565	-.34566	1581.78000	1597.25000
.601	-2.772	-.40524	-.40327	-.40164	-.40246	-.25165	-.25097	-.25097	1584.23199	1597.25999
.601	-1.749	-.39774	-.39604	-.39442	-.39523	-.15656	-.15494	-.15492	1586.05901	1596.64999
.601	-.732	-.38929	-.38749	-.38590	-.38669	-.06331	-.06095	-.06076	1587.15700	1597.17999
.601	-.290	-.38326	-.38115	-.37968	-.38042	-.01536	-.01275	-.01274	1587.44600	1597.07001
.600	-.738	-.38751	-.38550	-.38404	-.38477	-.07924	-.08003	-.08036	1587.11000	1596.82001
.600	1.758	-.39335	-.39166	-.39004	-.39085	-.17546	-.17536	-.17560	1583.70001	1596.73000
.600	2.783	-.39636	-.39457	-.39308	-.39382	-.27294	-.27343	-.27346	1583.88200	1597.25999
.600	3.824	-.39862	-.39744	-.39611	-.39693	-.36922	-.36799	-.36808	1580.91299	1597.36000
GRADIENT	.00166	.00162	.00162	.00162	.00162	.09421	.09396	.09397	-.11075	.00576

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 834

(UCM070) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1742/ 0 RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.100	-3.945	-50203	-50015	-49830	-49922	-45514	-45198	-45177	-45188	1188.21899	1204.94400
1.100	-2.928	-49336	-49305	-49148	-49227	-33432	-33222	-33186	-33204	1191.15199	1204.94099
1.099	-1.929	-48728	-48736	-48582	-48659	-21692	-21541	-21494	-21518	1192.90199	1204.93600
1.100	-1.941	-4.8154	-4.8149	-4.7978	-4.8063	-0.0953	-0.09888	-0.09844	-0.09866	1194.04401	1204.73801
1.100	-0.84	-4.7977	-4.7961	-4.7811	-4.7886	.00830	.00713	.00766	.00740	1194.41701	1204.83900
1.100	.958	-4.7887	-4.7891	-4.7722	-4.7806	.12960	.12802	.12876	.12839	1193.99400	1204.86501
1.961	-1.961	-4.8114	-4.8146	-4.7976	-4.8061	.24666	.24727	.24734	.24700	1192.84500	1204.83400
1.100	2.955	-4.8535	-4.8347	-4.8174	-4.8261	.36440	.36379	.36355	.36367	1190.72900	1204.78000
3.979	-4.8742	-4.8588	-4.8429	-4.8508	-4.8395	.48224	.48296	.48260	.1187.37000	1204.57700	
GRADIENT	.00164	.00169	.00168	.00168	.00168	.11875	.11818	.11819	.11818	.08729	-.03454

RUN NO. 1726/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.250	-3.880	-52421	-55201	-55054	-55127	-48550	-48300	-48275	-48288	1165.27100	1182.61400
1.250	-2.850	-54172	-54113	-53950	-54031	-35291	-35019	-34905	-34962	1167.07401	1182.41200
1.250	-1.844	-53545	-53426	-53296	-53361	-22295	-22177	-22140	-22159	1168.83099	1182.56200
1.250	-1.837	-52898	-52782	-52630	-52706	-0.09482	-0.09318	-0.09278	-0.09298	1170.02600	1182.49100
1.250	-1.77	-52099	-51833	-51917	-51917	.00214	.00085	.00052	.00056	1171.00000	1182.55700
1.250	.878	-52347	-52251	-52100	-52175	.12970	.12891	.12943	.12917	1170.53000	1182.56700
1.250	1.874	-52778	-52666	-52525	-52596	.25524	.25486	.25555	.25520	1169.18600	1182.49300
1.249	2.908	-53276	-53166	-53006	-53086	.38833	.38640	.38708	.38674	1167.10400	1182.43600
3.911	-53621	-53520	-53427	-53474	-51462	.51199	.51272	.51235	.1163.94701	1182.75999	
GRADIENT	.00191	.00197	.00193	.00195	.00195	.12855	.12786	.12788	.12787	-.08205	.01030

RUN NO. 1718/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F
1.400	-3.892	-63282	-63178	-62987	-63082	-55185	-54703	-54842	-54773	1146.02000	1164.13000
1.400	-2.866	-62528	-62444	-62239	-62341	-40491	-39972	-40075	-40023	1148.50600	1163.74699
1.400	-1.858	-61803	-61773	-61583	-61678	-25565	-25161	-25270	-25215	1151.12500	1164.05200
1.400	-1.851	-61050	-61037	-60844	-60941	-10768	-10520	-10625	-10573	1152.21400	1164.12399
1.400	-1.613	-60062	-60058	-59866	-59962	.00674	.00746	.00669	.00708	1152.75101	1163.99699
1.400	.886	-60287	-60189	-60095	-60189	.15744	.15759	.15676	.15717	1152.53000	1164.33501
1.400	1.894	-60572	-60347	-60443	-60443	.30170	.30405	.30304	.30355	1151.16600	1164.06400
1.399	2.898	-61075	-60995	-60802	-60899	.44964	.45080	.45028	.45098	1149.77901	1164.24500
1.400	3.926	-61532	-61239	-61430	-61335	.59848	.59826	.59861	.5981	1147.29300	1164.19701
GRADIENT	.00247	.00247	.00246	.00246	.00246	.14777	.14717	.14722	.14720	.15307	.03447

RUN NO.	1708/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-4.000	PHI =	180.000
DPA CAL	DPA1	DPA	DPBCAL	DPB1	DPB2	DPB	DPBF	PTTF	PT2F
BETA	-3.810	-68108	-68028	-57306	-57429	-57367	1137.16800	1158.36400	
CH	-450	-68171	-67948	-57662	-57622	-57333	1140.187300	1158.18600	
	-2.773	-67570	-67337	-41587	-41277	-41333	1144.125801	1158.63901	
	-1.757	-67140	-67008	-66991	-65910	-25742	1144.65401	1158.632201	
	-740	-66196	-66158	-65985	-66071	-09829	1145.98801	1158.15564	
	-276	-64012	-63988	-63902	-61749	-01375	1142.47701	1158.63800	
	-759	-64911	-64687	-64772	-14026	-14020	1141.88600	1158.18800	
	1.776	-65923	-65887	-65712	-65799	-29787	1141.29835	1158.37500	
	2.820	-66728	-66688	-66510	-66599	-46074	1139.45976	1158.88300	
	3.841	-66838	-66793	-66619	-66706	-61187	1139.61171	1158.28700	
GRADIENT	.00188	.00186	.00186	.00187	.00186	.00186	.00186	.00186	.00186

RUN NO.	1701/ O	RN/L =	2.50	GRADIENT INTERVAL	= -5.00/	5.00
BETA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1
-3.822	.69900	-.69836	-.69693	-.69764	-.59047	-.58679
-2.791	.68912	-.68857	-.68700	-.68778	-.42410	-.42846
-1.772	.68105	-.68036	-.67862	-.67949	-.26409	-.26186
-.761	.67050	-.67012	-.66846	-.66929	-.10224	-.10054
-.253	.66845	-.66817	-.66654	-.66735	-.00303	-.00188
.800	.67430	-.67213	-.67288	-.67363	.15985	.16083
1.821	.68363	-.68342	-.68183	-.68262	.32190	.32427
2.820	.69182	-.69115	-.68949	-.69032	.48824	.48878
3.850	.70073	-.70026	-.69855	-.69940	.65127	.65144
GRADIENT	.00049	-.00051	-.00049	-.00050	.16254	.16205
					.16212	.16208
					-.09300	.00461
						PT2F
						1148.33192
						1134.13699
						1134.13699
						1148.33192

## IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 836  
 (UCM070) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1689/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-4.000	PHI =	180.000
MACH	BETA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.521	-3.833	- .81849	- .81578	- .81445	- .81511	- .68340	- .67835	- .67911	- .67911	PT2F
1.521	-2.804	- .82056	- .81661	- .81521	- .81591	- .50185	- .49804	- .49881	- .49881	
1.521	-1.786	- .82778	- .82314	- .82179	- .82247	- .32403	- .32175	- .32233	- .32233	
1.521	-1.520	- .775	- .82671	- .82236	- .82094	- .82165	- .13661	- .13500	- .13565	
1.520	- .241	- .79022	- .78681	- .78540	- .78611	- .01006	- .00734	- .00799	- .00799	
1.520	.809	- .80726	- .80384	- .80236	- .80310	- .18338	- .18337	- .18260	- .18299	
1.520	1.827	- .82162	- .81816	- .81675	- .81746	- .38908	- .38735	- .38643	- .38689	
1.520	2.854	- .83267	- .82906	- .82779	- .82842	- .58571	- .58543	- .58488	- .58488	
1.520	3.870	- .83754	- .83399	- .83253	- .83326	- .77716	- .77495	- .77452	- .77452	
GRADIENT	.00166	- .00167	- .00167	- .00167	- .00167	- .19162	- .19162	- .19072	- .19072	
								.05015	.05015	
								.24409	.24409	
								.19076	.19076	
MACH	BETA	DPA CAL	DPA 1	DPA 2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.543	-3.836	- .70884	- .70559	- .70406	- .70482	- .70196	- .69745	- .69880	- .69813	PT2F
1.543	-2.801	- .68390	- .68095	- .67950	- .68023	- .51011	- .50678	- .50752	- .50752	
1.543	-1.788	- .65716	- .65518	- .65387	- .65452	- .32514	- .32332	- .32469	- .32400	
1.544	-1.776	- .63086	- .62785	- .62641	- .62713	- .14945	- .14642	- .14767	- .14704	
1.544	- .240	- .57684	- .57395	- .57243	- .57319	- .02261	- .02115	- .02237	- .02176	
1.543	.797	- .59485	- .59202	- .59063	- .59132	- .13121	- .13118	- .13003	- .13061	
1.544	1.818	- .63050	- .62717	- .62598	- .62657	- .29839	- .29819	- .29703	- .29761	
1.543	2.831	- .66326	- .66177	- .66532	- .66252	- .47433	- .47258	- .47155	- .47206	
1.544	3.870	- .70343	- .70054	- .69917	- .69986	- .66345	- .66548	- .66254	- .66299	
GRADIENT	.00244	.00241	.00240	.00241	.00241	.17598	.17512	.17519	.17515	
								.67203	.67203	
								.03918	.03918	

## IA310 (AEDC 16TF-783) REPEAT RUNS

(UCM071) (04 OCT 91)

## PARAMETRIC DATA

		RN NO.	1675 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	180.000	
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
.601	-3.993	-.04172	-.04163	-.04013	-.04088	-.35137	-.34907	-.34815	-.34861	159.1 94.701	159.7 14000	
.600	-2.974	-.04050	-.04037	-.03880	-.03958	-.25529	-.25409	-.25412	159.3 84.200	159.6 39999		
.601	-1.969	-.04006	-.03991	-.03823	-.03907	-.16174	-.16020	-.16024	159.5 10.800	159.6 94000		
.601	-.950	-.04074	-.04063	-.03900	-.03981	-.06812	-.06648	-.06653	-.06650	159.5 73.599	159.7 22000	
.600	-.173	-.02781	-.02769	-.02609	-.02689	-.00395	-.00261	-.00274	-.00268	159.6 0.0400	159.6 89999	
.601	.831	.01656	.01497	.01666	.01582	.08644	.08708	.08703	.08706	159.6 15.800	159.7 14999	
.601	1.996	.01099	.00939	.01113	.01026	.19211	.19305	.19309	.19307	159.5 65.500	159.7 31000	
.600	3.003	.01177	.01011	.01203	.01107	.28597	.28664	.28676	.28670	159.4 65.700	159.7 12000	
.601	4.011	.01226	.01175	.01256	.01256	.38102	.38083	.38102	.38092	159.2 44.000	159.7 33000	
GRADIENT		.00886	.00865	.00868	.00866	.09080	.09057	.09055	.09055	.09185	.06049	
		RN NO.	1751 / 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	180.000	
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
.799	-3.996	-.04386	-.04113	-.03945	-.04029	-.41783	-.41582	-.41611	-.41596	1335.10300	1340.80000	
.800	-2.975	-.04350	-.04045	-.03906	-.03976	-.30316	-.30325	-.30320	1337.43300	1341.23000		
.800	-1.973	-.04152	-.03894	-.03746	-.03820	-.19524	-.19322	-.19327	1339.12601	1341.33000		
.800	-.960	-.04444	-.04170	-.04015	-.04093	-.08742	-.08519	-.08510	1339.93201	1341.42999		
.800	-.100	-.01220	-.01010	-.00849	-.00929	.02853	.02982	.02983	1340.14400	1341.24001		
.800	.982	-.04481	-.04207	-.04064	-.04136	.11688	.11795	.11817	.11806	1339.46600	1340.71001	
.800	2.008	-.04170	-.03912	-.03752	-.03832	.23076	.23157	.23164	.23160	1339.06300	1340.78000	
.800	3.009	-.03757	-.03461	-.03314	-.03388	.34422	.34423	.34426	.34426	1337.82001	1340.75999	
.800	4.014	-.03513	-.03220	-.03137	-.03137	.45447	.45532	.45446	.45446	1335.48300	1340.85001	
GRADIENT		.00091	.00092	.00092	.00092	.10842	.10813	.10816	.10814	.03838	-.04981	
		RN NO.	1664 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	180.000	
MACH	BETA	DPACAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF	PT2F	
.900	-3.998	-.04419	-.04417	-.04233	-.04325	-.43572	-.43183	-.43199	-.43191	1267.80800	1273.24001	
.900	-2.967	-.04314	-.04275	-.04120	-.04197	-.31651	-.31347	-.31352	-.31349	1269.22900	1272.64000	
.900	-1.967	-.04184	-.04102	-.03938	-.04020	-.20210	-.20024	-.20022	-.20022	1270.45700	1272.82001	
.900	-.957	-.04416	-.04314	-.04171	-.04243	-.09010	-.08753	-.08754	-.08754	1271.50500	1273.13000	
.900	-.141	-.03572	-.03496	-.03325	-.03410	-.00041	-.00200	-.00193	-.00197	1271.37300	1272.89000	
.900	.859	-.01144	-.00998	-.01181	-.01089	.11402	.11412	.11412	.11407	1271.93700	1273.10001	
.899	2.010	-.00345	-.00177	-.00348	-.00262	.24150	.24195	.24211	.24203	1271.07401	1272.70000	
.900	3.016	-.00456	-.00288	-.00470	-.00379	.35603	.35634	.35649	.35641	1270.28799	1273.22000	
.900	4.020	-.00665	-.00516	-.00694	-.00605	.47355	.47284	.47314	.47299	1268.00000	1272.85001	
GRADIENT		.00820	.00787	.00789	.00788	.11284	.11231	.11233	.11233	.08710	-.00182	

(UCM071) ( 04 OCT 91 )  
PAGE 838

PARAMETRIC DATA

## IA310 (AEDC 16TF-783) REPEAT RUNS

(UCM071) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		RN/L = 1709/ 0		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 180.000		PT2F	
		DPACAL		DPA1		DPA2		DPBCAL		DPB2	
MACH	BETA	-3.994	-.07127	-.07070	-.06895	-.06982	-.058288	-.58050	-.57974	1158.77499	
1.450	-2.963	-.06954	-.06956	-.06763	-.06859	-.41731	-.41416	-.41559	-.41488	1152.42000	
1.450	-1.954	-.06734	-.06842	-.06652	-.06747	-.26637	-.26460	-.26587	-.26523	1153.37399	
1.450	-1.942	-.06959	-.07072	-.06895	-.06984	-.11786	-.11445	-.11581	-.11513	1159.42999	
1.450	-1.949	-.05120	-.05308	-.05214	-.05120	.00632	.00879	.00766	.00822	1157.24300	
1.450	.965	-.00027	-.00016	-.00019	-.00002	.18408	.18536	.18463	.18499	1159.62801	
1.450	2.005	-.00061	-.00099	-.00071	-.00085	.33915	.33945	.33839	.33892	1158.29100	
1.451	3.013	.00048	.00013	.00042	.00028	.48884	.48805	.48695	.48750	1153.71700	
1.450	4.015	.00621	.00496	.00690	.00593	.65242	.65403	.65295	.65349	1158.32500	
GRADIENT	GRADIENT	.01210	.01199	.01195	.01185	.15341	.15304	.15300	.15300	.14475	-.01465
RUN NO.		RN/L = 1702/ 0		GRADIENT INTERVAL = -5.00/ 5.00		DPACAL		DPA1		DPA2	
MACH	BETA	-3.992	-.07285	-.07260	-.07075	-.07167	-.58681	-.58286	-.58463	.58375	1144.63400
1.470	-2.968	-.07429	-.07367	-.07184	-.07276	-.42681	-.42226	-.42390	-.42306	1146.04500	
1.470	-1.960	-.07262	-.07195	-.07021	-.07108	-.27073	-.26725	-.26869	-.26797	1145.39600	
1.470	-1.946	-.07430	-.07356	-.07171	-.07264	-.11315	-.11085	-.11228	-.11157	1148.44325	
1.470	-1.953	-.05702	-.05658	-.05479	-.05568	.00954	.00967	.00839	.00903	1145.57500	
1.470	.969	-.00375	-.00386	-.00363	-.00375	.18376	.18494	.18411	.18453	1145.40601	
1.470	2.006	-.00329	-.00386	-.00351	-.00368	.34134	.34368	.34255	.34311	1146.37100	
1.470	3.013	-.00107	-.00127	-.00103	-.00115	.49843	.49923	.49815	.49869	1147.40199	
1.470	4.015	.00070	.00056	.00081	.00069	.66139	.66161	.66047	.66104	1146.22701	
GRADIENT	GRADIENT	.01209	.01197	.01171	.01184	.15530	.15481	.15490	.15485	.21420	.03868
RUN NO.		RN/L = 1695/ 0		GRADIENT INTERVAL = -5.00/ 5.00		DPACAL		DPA1		DPA2	
MACH	BETA	-3.993	-.08028	-.08114	-.07953	-.08033	-.62289	-.61891	-.62037	.61964	1134.56300
1.494	-2.965	-.08048	-.08118	-.07970	-.08044	-.45198	-.44675	-.44833	-.44754	1134.47600	
1.495	-1.964	-.07995	-.08063	-.07891	-.07977	-.29316	-.28946	-.29096	-.29021	1134.87900	
1.495	-1.951	-.08123	-.08199	-.08030	-.08114	-.12791	-.12550	-.12681	-.12615	1135.04700	
1.495	-1.946	-.05450	-.05368	-.05540	-.05454	.00721	.00757	.00650	.00704	1135.77600	
1.495	.974	-.00187	-.00195	-.00188	-.00192	.20149	.20016	.20149	.20079	1136.27100	
1.495	2.008	-.00358	-.00368	-.00351	-.00359	.36449	.36578	.36372	.36475	1136.46201	
1.495	3.014	-.00057	-.00024	-.00042	-.00033	.52836	.52826	.52711	.52769	1137.10400	
1.495	4.021	.00153	.00140	.00151	.00146	.70304	.70189	.70086	.70138	1137.01300	
GRADIENT	GRADIENT	.01339	.01349	.01324	.01337	.16517	.16447	.16450	.16448	.36798	.18401

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 840

(UCM071) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1690/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	180.000
MACH	BETA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.521	-3.999	-.08487	-.08381	-.08220	-.08300	-.74541	-.7405	-.74185	-.74095	1127.81799
1.520	-2.965	-.08503	-.08518	-.08344	-.08431	-.56616	-.56107	-.56260	-.56184	1128.27901
1.521	-1.963	-.07391	-.07291	-.07124	-.07207	-.36646	-.36267	-.36423	-.36345	1128.43700
1.521	-.950	-.04402	-.04317	-.04154	-.04235	-.10422	-.10337	-.10500	-.10418	1129.64600
1.520	-.145	-.01660	-.01601	-.01432	-.01516	-.00634	-.00297	-.00446	-.00371	1129.94901
1.521	.973	.02176	.02002	.02168	.02085	.18127	.17933	.17795	.17864	1129.77499
1.521	2.008	.00603	.00516	.00675	.00595	.40621	.40474	.40345	.40409	1128.69000
1.521	3.015	-.00318	-.00335	-.00346	-.00341	.61706	.61609	.61489	.61549	1129.06000
1.520	4.021	-.00818	-.00767	-.00716	-.00741	.81046	.80874	.80722	.80798	1129.84599
GRADIENT	.01290	.01276	.01259	.01267	.01263	.19383	.19282	.19287	.19285	.18284
										.10699
MACH	BETA	DPA/CAL	DPA1	DPA2	DPA	DPBCAL	DPB1	DPB2	DPB	PTTF
1.544	-3.994	-.00881	-.00701	-.00690	-.00696	-.61579	-.61151	-.61312	-.61232	1120.51801
1.544	-2.970	-.02613	-.02509	-.02366	-.02437	-.38077	-.37620	-.37787	-.37704	1122.08701
1.543	-1.963	-.03560	-.03341	-.03173	-.03257	-.23773	-.23545	-.23705	-.23625	1119.74500
1.544	-.955	-.04262	-.04050	-.03891	-.03970	-.11783	-.11417	-.11581	-.11499	1119.74500
1.544	100	-.03867	-.03678	-.03600	-.03521	0.0007	0.00346	0.00198	0.00272	1120.82001
1.544	.984	-.05411	-.05183	-.05047	-.05115	.10216	.10284	.10146	.10215	1122.85899
1.544	2.015	-.04518	-.04328	-.04180	-.04254	.25193	.25296	.25159	.25227	1125.22099
1.544	3.013	-.03781	-.03770	-.03613	-.03691	.39792	.39765	.39630	.39697	1125.31200
1.543	4.013	-.03096	-.02953	-.02797	-.02875	.58162	.58048	.58105	.58125	1129.99
GRADIENT	-.00258	-.00266	-.00257	-.00261	-.00257	.13918	.13847	.13853	.13850	.111612

RUN NO.		1102 / O		RN/L =		3.20		GRADIENT INTERVAL =		- 5.00 /		5.00	
ALPHA		P	PT	Q(PSF)		T(R)	TT(F)	RN/L		PC	PREF	PATM	
- .006	1600	65100	2039, 60001	401.65190	521.57590	99.30000	1947.92999	3. 19181	161.4.09000	1947.92999	9. 15889	2058.20999	
- .998	1600	27000	2039, 81000	402.14090	521.52510	99.30000	1947.98000	3. 19377	161.3.72000	1947.98000	9. 15793	2058.20999	
- .001	1600	64101	2040, 96001	402.80400	521.47560	99.30000	1948.06000	3. 19716	161.4.11000	1948.06000	9. 15269	2058.20999	
- .998	1600	1323	2040, 71001	402.51420	521.50290	99.30000	1948.11000	3. 19589	161.4.20000	1948.11000	9. 15383	2058.17499	
- .995	1601	00400	2040, 63000	402.22850	521.62670	99.39999	1948.14000	3. 19405	161.4.46001	1948.14000	9. 15420	2058.20999	
- .002	1600	85001	2041.59000	403.16110	521.54250	99.39999	1948.22000	3. 19826	161.4.33000	1948.22000	9. 14983	2058.20999	
- 1.999	1600	69099	2040.77000	402.77080	521.52690	99.39999	1948.27000	3. 19631	161.4.16000	1948.27000	9. 15265	2058.20999	
- .995	1600	36099	2041.17999	403.21800	521.55100	99.39999	1948.34000	3. 19812	161.3.84000	1948.34000	9. 15169	2058.20999	
.009	1600	22099	2040.67000	402.90480	521.51100	99.39999	1948.35001	3. 19655	161.3.69000	1948.35001	9. 15401	2058.24500	
1.003	1599	93100	2040.85001	403.29270	521.51100	99.39999	1948.38000	3. 19811	161.3.41000	1948.38000	9. 15319	2058.24500	
2.001	1599	26601	2040.62000	403.64580	521.37230	99.30000	1948.46001	3. 19993	161.2.75000	1948.46001	9. 17125	2058.24500	
3.011	1599	40300	2040.84000	403.71800	521.36910	99.30000	1948.49001	3. 20038	161.2.89000	1948.49001	9. 18728	2058.24500	
4.005	1599	43100	2040.03999	403.72270	521.43020	99.30000	1948.53000	3. 19717	161.2.89999	1948.53000	9. 17389	2058.24500	
4.999	1599	07401	2040.05000	403.32320	521.48950	99.30000	1948.62000	3. 19754	161.2.55000	1948.62000	9. 20796	2058.24500	
6.003	1599	02800	2040.30000	403.57130	521.37350	99.30000	1948.64000	3. 19938	161.2.50999	1948.64000	9. 20681	2058.28000	
6.998	1599	76900	2039.92999	402.65280	521.46970	99.30000	1948.71001	3. 19573	161.3.23000	1948.71001	9. 20851	2058.24500	
7.996	1600	.02000	2040.50000	402.92600	521.45140	99.30000	1948.80000	3. 19721	161.3.49001	1948.80000	9. 18883	2058.28000	
GRADIENT	-	.20207	- .08126	.09740	-.01628	-.00364	-.00050	-.00031	-.00050	-.00499	.00455	.00636	
RUN NO.		1109 / O		RN/L =		3.76		GRADIENT INTERVAL =		- 5.00 /		5.00	
ALPHA		P	PT	Q(PSF)		T(R)	TT(F)	RN/L		PC	PREF	PATM	
- 8.000	1324	.93700	2019.55000	593.49440	496.25730	100.10000	1941.52000	3. 76225	1341.19000	1892.97000	5. 45236	2057.75500	
- 6.987	1323	.39500	2017.02000	592.67040	496.18140	100.00000	1942.92999	3. 75819	1339.50000	1892.92999	5. 41653	2057.79001	
- 5.995	1322	.97301	2016.89000	592.86130	496.23390	100.10000	1942.88000	3. 75768	1339.53000	1892.88000	5. 38502	2057.75500	
- 4.981	1323	.14700	2017.35001	593.08370	496.04270	99.89999	1943.10001	3. 76050	1339.71001	1892.89000	5. 36265	2057.75500	
- 3.994	1324	.03200	2018.14999	593.07350	496.17020	100.00000	1943.60001	3. 76048	1340.60001	1892.88000	5. 32895	2057.75500	
- 2.997	1324	.40601	2018.17999	592.84200	496.03080	99.80000	1943.97000	3. 76164	1340.97000	1892.92000	5. 27664	2057.75500	
- 1.993	1324	.81300	2018.53000	592.82350	496.31570	100.10000	1944.96001	3. 75938	1341.38000	1892.96001	5. 25497	2057.75500	
- .989	1323	.62500	2017.69000	593.00950	496.33620	100.20000	1945.90001	3. 75808	1340.19000	1892.99001	5. 21597	2057.75000	
.014	1323	.96001	2018.62000	592.73020	496.19970	100.00000	1946.52000	3. 75900	1340.52000	1893.00999	5. 18525	2057.72000	
1.003	1324	.36800	2018.55000	593.14060	496.35520	100.20000	1947.04000	3. 75937	1340.94000	1893.03000	5. 14206	2057.72000	
2.006	1324	.04800	2018.41000	593.25510	496.41940	100.30000	1947.56000	3. 75865	1340.62000	1893.06000	5. 09184	2057.75500	
3.005	1323	.98199	2017.55000	592.66380	496.56150	100.40000	1948.08000	3. 75530	1340.53999	1893.08000	5. 03390	2057.72000	
4.004	1323	.51601	2015.28999	591.30760	496.67070	100.40000	1948.30999	3. 74928	1340.03999	1893.07001	4. 9981	2057.68000	
5.003	1323	.54800	2016.96001	592.52270	496.55640	100.40000	1948.71001	3. 75429	1340.14000	1893.16000	4. 87810	2057.68000	
6.002	1324	.69901	2019.87000	593.89310	496.47530	100.40000	1949.23000	3. 76105	1341.28999	1893.25000	4. 83245	2057.68500	
7.012	1325	.62801	2019.88000	593.26880	496.57400	100.40000	1949.71001	3. 75943	1342.21001	1893.32001	4. 79414	2057.68500	
8.001	1323	.93700	2018.38000	593.30860	496.49830	100.40000	1950.50999	3. 75789	1340.34000	1893.34000	4. 76917	2057.64999	
GRADIENT		.00093	- 13117	-.09775	-.06256	-.06005	-.00092	-.00132	-.00132	-.00092	-.004018	.02396	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 842

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM001) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.900	-8.002	1173.63600	1984.19000	664.91240	482.12840	100.50000	3.89007	1190.92999	1643.41000	1.10852	2056.91501
.900	-6.993	1172.93201	1984.14000	665.29710	482.04930	100.50000	3.89085	1190.23000	1643.45000	1.10288	2056.88000
.900	-5.994	1172.77200	1984.07001	665.34420	482.03520	100.50000	3.89087	1190.07001	1643.50999	1.10575	2056.88000
.900	-4.990	1172.98801	1983.75999	665.00270	482.08200	100.50000	3.88974	1190.28000	1643.53999	1.10876	2056.88000
.900	-3.991	1172.98399	1984.02000	665.18360	482.06370	100.50000	3.89046	1190.28000	1643.55000	1.11145	2056.91501
.900	-2.976	1173.33200	1983.66000	664.72920	482.12960	100.50000	3.88902	1190.62000	1643.56000	1.11165	2056.91501
.900	-1.994	1173.00700	1984.52000	665.51390	482.03150	100.50000	3.89179	1190.31000	1643.63000	1.11117	2056.91501
.900	-.999	1173.13000	1983.70000	664.87700	482.10300	100.50000	3.88939	1190.42000	1643.66000	1.10313	2056.88000
.900	.020	1173.34700	1984.03999	664.98170	482.10470	100.50000	3.89004	1190.64000	1643.74001	1.09730	2056.88000
.900	1.003	1173.65601	1984.20000	664.90720	482.13010	100.50000	3.89007	1190.95000	1643.75999	1.10003	2056.91501
.900	2.007	1173.47400	1984.24001	665.04320	482.10600	100.50000	3.89042	1190.77000	1643.80000	1.10565	2056.91501
.900	3.011	1173.54300	1984.32001	665.05690	482.10840	100.50000	3.89055	1190.84000	1643.83000	1.10844	2056.88000
.900	4.007	1173.06100	1983.60001	664.84940	482.18800	100.60000	3.88831	1190.35001	1643.89000	1.12026	2056.88000
.899	5.006	1173.88800	1984.17999	664.75560	482.24460	100.60000	3.88881	1191.17999	1643.92999	1.11421	2056.91501
.899	6.007	1174.33299	1984.12000	664.45000	482.21510	100.50000	3.88897	1191.62000	1643.96001	1.11140	2056.91501
.900	7.002	1173.38100	1983.75999	664.76900	482.12840	100.50000	3.88923	1190.67000	1644.00000	1.10592	2056.88000
.900	8.008	1172.90601	1983.83000	665.09960	482.06760	100.50000	3.89004	1190.20000	1644.05000	1.10305	2056.88000
	GRADIENT	.04518	.01779	-.01468	.00878	.00546	-.00006	.04516	.04111	.00008	-.00149

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.099	-7.994	678.41060	1446.94000	573.70630	450.59770	99.80000	2.99951	691.03980	1316.02000	1.27966	2054.46500
1.100	-6.977	677.90190	1447.57001	574.27390	450.44480	99.80000	3.00120	690.53980	1316.07001	1.28577	2054.50000
1.100	-5.998	677.41190	1446.61000	573.90920	450.43730	99.80000	2.99922	690.03980	1316.08000	1.28662	2054.50000
1.100	-4.975	677.77000	1446.84000	573.90160	450.48490	99.80000	2.99958	690.39990	1281.32001	1.28976	2054.46500
1.100	-3.975	677.65040	1446.78999	573.91970	450.38600	99.70000	3.00023	690.27980	1275.05000	1.28646	2054.50000
	GRADIENT	-.11968	-.05007	.01807	-.09898	-.10002	.00064	-.12017	-.12138	-.00330	.03419

## PARAMETRIC DATA

GRADIENT INTERVAL = -5.00/ 5.00  
BETA = .000 PHI = .000

	GRADIENT	PATM	SH10+3	PREF	RN/L	PC	T(F)	T(R)	Q(PSF)	P	PT	ALPHA
CH												
-7.997	555.37550	1438.13000	607.21340	427.13920	100.90000	2.99487	567.95000	1154.17000	1.40597	2055.02499		
-6.985	555.24460	1438.25000	607.30270	427.10030	100.90000	2.99510	567.81980	1154.25000	1.42043	2055.06000		
-5.973	555.17920	1437.78000	607.07860	427.20190	101.00000	2.99343	567.75000	1154.35001	1.43562	2055.02499		
-4.990	555.25440	1438.25999	607.30570	427.17770	101.00000	2.99442	567.82980	1154.42999	1.37711	2055.06000		
-3.978	555.48880	1437.75000	606.99580	427.27250	101.00000	2.99341	568.05980	1154.49001	1.44678	2055.06000		
-2.987	555.29490	1438.20000	607.26640	427.19170	101.00000	2.99430	567.86990	1154.57001	1.44632	2055.06000		
-1.988	555.38840	1437.82001	607.05350	427.24460	101.00000	2.99354	567.96000	1154.64999	1.44671	2055.02499		
-.985	555.41800	1437.84000	607.05690	427.32540	101.10000	2.99288	567.99000	1154.70000	1.44297	2055.02499		
.029	555.26880	1437.80000	607.06930	427.29610	101.10000	2.99278	567.83980	1154.75000	1.43930	2055.06000		
1.019	555.26660	1438.02000	607.18140	427.27690	101.10000	2.99323	567.83980	1154.82001	1.44279	2055.09500		
2.017	555.52250	1438.09000	607.15990	427.40410	101.20000	2.99270	568.09990	1154.87000	1.45764	2055.06000		
3.012	554.80690	1438.14939	607.34770	427.24100	101.20000	2.99273	567.37990	1154.92000	1.47644	2055.06000		
3.971	555.07860	1437.87000	607.14650	427.32450	101.20000	2.99220	567.64990	1154.95000	1.47294	2055.06000		
	-0.03466	-	.00427	.00541	.01357	-.00021	.02734	-.03479	.05924	.00675	.00149	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 844

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM002) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PREF	SH10+3	PATM
.599	-8.006	1600.88200	2040.16000	401.93310	521.55660	99.30000	3.19331	1614.33000	1950.14999	9.24167 2058.17499
.599	-6.994	1600.74400	2040.44000	402.28200	521.52320	99.30000	3.19482	1614.20000	1950.22000	9.25753 2058.14001
.599	-5.996	1600.06100	2040.05000	402.51440	521.48800	99.30000	3.19533	1613.52000	1950.28999	9.25933 2058.14001
.599	-4.999	1600.48599	2040.17000	402.26660	521.51880	99.30000	3.19453	1613.94000	1950.34000	9.27596 2058.14001
.599	-4.000	1599.98899	2039.63000	402.21170	521.41970	99.20000	3.19460	1613.45000	1950.38000	9.27845 2058.14001
.600	-3.003	1599.71899	2040.31000	403.01290	521.34400	99.20000	3.19809	1613.19000	1950.42999	9.27531 2058.10501
.600	-1.999	1599.29700	2039.64999	402.80420	521.25950	99.09999	3.19750	1612.75999	1950.47000	9.26117 2058.10501
.600	-1.000	1599.11000	2039.39999	402.74800	521.26050	99.09999	3.19709	1612.57001	1950.48000	9.26233 2058.10501
.600	.014	1599.14101	2039.80000	403.05810	521.23410	99.09999	3.19855	1612.61000	1950.52000	9.26048 2058.14001
.600	1.002	1598.64700	2039.60001	403.29520	521.20260	99.09999	3.19925	1612.12000	1950.56000	9.26140 2058.10501
.601	2.001	1598.30800	2039.75999	403.70750	521.06620	99.00000	3.20161	1611.78999	1950.61000	9.26067 2058.10501
.601	3.005	1598.34599	2039.86000	403.76000	521.06250	99.00000	3.20189	1611.83000	1950.63000	9.26021 2058.10501
.601	4.010	1598.49001	2040.27000	403.98730	521.04590	99.00000	3.20306	1611.98000	1950.67999	9.25832 2058.10501
.601	5.004	1598.62900	2039.97000	403.62110	520.98730	98.89999	3.20221	1612.11000	1950.77000	9.25970 2058.07001
.600	6.003	1599.30099	2039.94000	403.04520	521.05220	98.89999	3.20009	1612.77000	1950.86000	9.25984 2058.07001
.599	6.997	1599.84500	2039.23000	402.83130	521.15480	98.89999	3.19569	1613.28999	1950.94000	9.26311 2058.07001
.600	7.997	1600.03200	2040.39999	402.17990	521.17990	99.00000	3.19897	1613.50000	1951.00999	9.27490 2058.07001
	GRADIENT	-.23310	.00009	.19119	-.05050	-.03088	.00092	-.22918	.03645	-.00219 -.00317
RUN NO.	1103/ O	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/	5.00				
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PREF	SH10+3	PATM
.800	-8.005	1323.65401	2017.83000	593.09400	496.41800	100.30000	3.75759	1340.22000	1892.12000	3.58242 2057.40500
.800	-6.986	1324.16100	2018.25000	593.05960	496.44290	100.30000	3.75796	1340.73000	1892.13000	3.64023 2057.40500
.800	-5.995	1324.07700	2017.92000	592.87330	496.45700	100.30000	3.75712	1340.64000	1892.13000	3.21817 2057.40500
.800	-5.003	1324.19000	2018.31000	593.08400	496.44190	100.30000	3.75809	1340.75999	1892.14000	3.13565 2057.37000
.800	-3.989	1324.40401	2018.22000	592.87230	496.47090	100.30000	3.75744	1340.97000	1892.16000	3.03430 2057.40500
.800	-2.997	1323.81599	2017.80000	592.961170	496.43750	100.30000	3.75721	1340.38000	1892.20000	2.88146 2057.37000
.800	-1.999	1324.19200	2018.21001	593.00850	496.44900	100.30000	3.75778	1340.75999	1892.22000	2.71512 2057.37000
.800	-.989	1323.53600	2017.61000	593.01120	496.42090	100.30000	3.75714	1340.10001	1892.24001	3.22622 2057.37000
.800	.025	1323.82401	2017.89999	593.02980	496.43140	100.40000	3.75750	1340.39000	1892.25000	3.06348 2057.37000
.799	1.008	1324.78000	2018.12000	592.54270	496.60690	100.40000	3.75561	1341.34000	1892.28999	2.91524 2057.33499
.799	2.007	1324.73801	2018.21001	592.63820	496.50760	100.30000	3.75682	1341.30000	1892.32001	2.74755 2057.33499
.800	3.005	1324.27400	2018.17999	592.93140	496.54860	100.40000	3.75669	1340.84000	1892.35001	2.40951 2057.33499
.800	4.020	1324.31300	2018.28000	592.97900	496.54570	100.40000	3.75692	1340.88000	1892.37000	2.76709 2057.29999
.800	5.003	1324.65601	2018.30000	592.76050	496.58110	100.40000	3.75637	1341.22000	1892.39999	2.80006 2057.29999
.799	6.018	1324.62100	2017.94000	592.51730	496.69120	100.50000	3.75448	1341.17999	1892.47000	2.79394 2057.29999
.799	7.002	1325.37700	2018.62000	592.50660	496.72440	100.50000	3.75520	1340.24001	1892.55000	2.74048 2057.26501
.800	7.995	1323.67200	2017.96001	593.17770	496.58810	100.50000	3.75623	1340.24001	1892.57001	2.80718 2057.26501
	GRADIENT	.05558	.03142	-.01448	.01556	.01332	-.00012	.05548	.02564	-.04534 -.01049

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

## PARAMETRIC DATA

RUN NO.	1148/ O	RN/L =	3.00	GRADIENT INTERVAL = -5.00/ 5.00	BETA = .000	PHI = .000	PATM
MACH	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
ALPHA	P	573.65750	450.56300	99.70000	3.00034	691.33980	SH10+3
-8.010	678.71020	1447.06000	573.65750	450.56300	99.70000	3.00153	1.27956
-6.971	677.74390	1447.38000	574.22610	450.35130	99.70000	3.00011	2054.57001
1.100	677.75070	1446.75999	573.86250	450.40770	99.70000	690.37990	1.27595
-5.993	677.51860	1446.92000	574.04760	450.34940	99.70000	3.00059	2054.57001
1.100	677.51860	1446.92000	574.04760	450.34940	99.70000	3.00055	1.27650
-4.996	677.51860	1446.92000	574.04760	450.34940	99.70000	690.51000	2054.50000
1.100	677.51860	1446.92000	574.04760	450.34940	99.70000	3.00055	1.28635
-3.973	677.87870	1446.98000	573.93990	450.41240	99.59999	3.00144	1.27546000
-2.982	677.72780	1447.03000	574.02880	450.29880	99.59999	3.00063	1.26635
1.100	677.74170	1446.67999	573.81960	450.33250	99.59999	690.36990	2054.53500
-2.001	677.70850	1446.94000	573.98390	450.30320	99.59999	3.00124	1.26995
1.100	677.70850	1446.94000	573.98390	450.30320	99.59999	690.33980	2054.53500
-979	677.79830	1446.99001	573.97780	450.31590	99.59999	3.00131	1.26972
.003	677.79830	1446.99001	573.97780	450.31590	99.59999	690.42990	2054.57001
1.100	677.79830	1446.99001	573.97780	450.31590	99.59999	3.00099	1.26968
1.004	677.60990	1446.81000	573.94730	450.29590	99.59999	690.24000	1.26984
2.015	678.17020	1446.92999	573.79570	450.39160	99.59999	3.00100	2054.57001
1.099	678.01050	1446.85001	573.81230	450.44900	99.70000	3.00019	1.28641
3.022	678.18040	1446.89999	573.77420	450.63790	99.89999	690.80980	1.26646
1.100	678.18040	1446.89999	573.77420	450.63790	99.89999	2.9983	2054.57001
4.009	677.87790	1447.06000	573.98710	450.64670	100.00000	2.99864	1.27624
5.026	677.87790	1447.06000	573.98710	450.64670	100.00000	690.51000	2054.60501
1.100	678.16750	1447.14000	573.91890	450.61400	99.89999	2.99938	1.27635
6.005	677.90800	1447.03999	573.96340	450.65430	100.00000	2.99858	2054.60501
7.008	678.21900	1447.03999	573.84030	450.87430	100.20000	2.99703	1.26305
8.009	678.05333	- .00692	- .02511	.01953	-.01092	-.00012	1.25323
1.099						.05310	.00020
GRADIENT						.05260	.00763

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 846

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM003) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	BETA = -5.00/ 5.00	PHI = .000	PREF	SH10+3	PATM
.599	-8.006	1600.15100	2040.13000	402.50780	521.58400	99.39999	3.19464	1613.61000	1947.69000	9.44954	2058.10501	
.600	-6.993	1600.40401	2040.60001	402.69480	521.57320	99.39999	3.19572	1613.87000	1947.73000	9.48235	2058.10501	
.600	-5.996	1600.02901	2040.57001	402.97750	521.54050	99.39999	3.19673	1613.50000	1947.78999	9.50005	2058.10501	
.599	-5.004	1600.06000	2039.64999	402.17900	521.61040	99.39999	3.19304	1613.50999	1947.80000	9.50440	2058.10501	
.600	-3.995	1600.14301	2040.46001	402.79150	521.55910	99.39999	3.19596	1613.61000	1947.83000	9.50057	2058.07001	
.600	-2.997	1599.73199	2040.66000	403.29640	521.50610	99.39999	3.19796	1613.21001	1947.83000	9.49962	2058.10501	
.600	-2.004	1599.70200	2040.16000	402.90660	521.54000	99.39999	3.19610	1613.17000	1947.86000	9.48443	2058.07001	
.600	-1.000	1599.49001	2039.67000	402.66330	521.55590	99.39999	3.19482	1612.95000	1947.87000	9.48674	2058.07001	
.600	-0.009	1599.15700	2039.98000	403.19630	521.50220	99.39999	3.19702	1612.63000	1947.89999	9.48528	2058.03500	
.601	1.002	1598.78101	2040.44000	403.89110	521.43630	99.39999	3.19993	1612.27000	1947.94000	9.46558	2058.03500	
.601	2.001	1598.67000	2039.96001	403.57960	521.45830	99.39999	3.19840	1612.14999	1948.00000	9.45034	2058.00000	
.601	3.000	1598.86800	2040.21001	403.62720	521.45850	99.39999	3.19787	1612.35001	1948.03000	9.39685	2057.96500	
.601	4.005	1598.93401	2040.41000	403.74050	521.45020	99.39999	3.19936	1612.42000	1948.05000	9.37853	2058.00000	
.601	5.004	1599.03000	2040.67000	403.88060	521.43990	99.39999	3.20009	1612.52000	1948.10001	9.35997	2057.96500	
.601	6.008	1599.03000	2040.72000	403.92310	521.43630	99.39999	3.20029	1612.52000	1948.12000	9.37709	2057.96500	
.600	6.997	1599.42300	2040.39000	403.32320	521.49710	99.39999	3.19783	1612.89999	1948.17000	9.37862	2057.96500	
.600	8.002	1600.02800	2040.16000	402.63330	521.47710	99.30000	3.19586	1613.49001	1948.24001	9.39708	2057.92999	
	GRADIENT	-.17001	-.01964	.12292	-.01440	-.00000	.00043	-.16766	.03050	-.01476	-.01459	
	RUN NO.	1112/ 0	RN/L =	3.75	GRADIENT INTERVAL = -5.00/ 5.00							
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	BETA = -5.00/ 5.00	PHI = .000	PREF	SH10+3	PATM
.800	-8.005	1324.25600	2018.05000	592.84740	496.82180	100.70000	3.75374	1340.82001	1803.56000	2.37518	2057.05499	
.800	-6.992	1323.63400	2017.78000	593.07030	496.77390	100.70000	3.75403	1340.20000	1803.60001	2.36411	2057.05499	
.800	-5.995	1323.94400	2017.98000	593.00760	496.79320	100.70000	3.75408	1340.50999	1803.61000	2.35820	2057.01999	
.800	-4.982	1323.59599	2017.62000	592.97750	496.7820	100.70000	3.75361	1340.16000	1803.62000	2.33603	2057.05499	
.800	-3.983	1324.43500	2018.19000	592.82890	496.83110	100.70000	3.75385	1341.00000	1803.64000	2.30741	2057.05499	
.799	-2.996	1324.67000	2018.06000	592.57320	496.86520	100.70000	3.75304	1341.23000	1803.66000	2.30201	2057.05499	
.800	-1.993	1324.20900	2017.80000	592.69380	496.83420	100.70000	3.75307	1340.77000	1803.69000	2.28571	2057.05499	
.800	-1.000	1323.87900	2018.25999	593.25930	496.76640	100.70000	3.75505	1340.45000	1803.72000	2.25235	2057.05499	
.800	.015	1323.62601	2018.24001	593.41600	496.74070	100.70000	3.75543	1340.20000	1803.75000	2.23071	2057.05499	
.800	1.013	1324.43600	2018.17000	592.81370	496.83250	100.70000	3.75378	1341.00000	1803.77000	2.23079	2057.05499	
.800	2.006	1323.76100	2017.47000	592.75490	496.80930	100.70000	3.75287	1340.32001	1803.80000	2.21545	2057.05499	
.799	3.004	1324.64000	2018.00999	592.55640	496.86570	100.70000	3.75294	1341.20000	1803.83000	2.20950	2057.09000	
.800	4.010	1324.29201	2018.32001	593.02270	496.71780	100.60000	3.75536	1340.86000	1803.87000	2.17732	2057.09000	
.800	5.003	1324.41600	2018.14000	592.80540	496.83250	100.70000	3.75373	1340.98000	1803.92000	2.18279	2057.09000	
.800	6.002	1324.45700	2018.11000	592.75490	496.83910	100.70000	3.75357	1341.02000	1803.94000	2.16703	2057.09000	
.800	7.012	1324.51500	2018.25000	592.81930	496.83540	100.70000	3.75389	1341.08000	1804.00000	2.15118	2057.09000	
.800	8.000	1324.65601	2018.24001	592.71560	496.85130	100.70000	3.75361	1341.22000	1804.05000	2.15119	2057.09000	
	GRADIENT	.02166	.01929	-.00041	-.00388	-.00046	.02171	.02760	.00007	-.01658	.00340	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 847

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM003) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	T(F)	RN/L	P/C	PREF	SH10+3	PATM
1.099	-7.994	678.40110	1446.89000	573.68090	450.84180	100.10000	2.99730	691.02980	1276.86000	1.23393	2054.78000
	-6.988	677.85470	1447.32001	574.14750	450.69970	100.10000	2.99854	690.49000	1276.94000	1.23357	2054.81500
1.100	-5.988	677.51760	1446.98000	574.08280	450.58540	100.00000	2.99862	690.14990	1277.00999	1.24030	2054.78000
1.100	-4.990	677.60300	1446.55000	573.79880	450.63990	100.00000	2.99760	690.23000	1277.10001	1.23744	2054.78000
1.100	-3.991	677.68530	1447.24001	574.16770	450.59420	100.00000	2.99914	690.31980	1277.17000	1.23042	2054.78000
1.100	-2.980	677.89230	1446.66000	573.74830	450.68510	100.00000	2.99771	690.51980	1277.24001	1.23735	2054.81500
1.100	-1.980	677.91040	1446.85001	573.85210	450.75220	100.10000	2.99744	690.53980	1277.33000	1.23719	2054.81500
1.100	-0.993	677.89500	1447.20000	574.06100	450.55710	99.89999	2.99965	690.52980	1277.38000	1.23689	2054.81500
.021	678.22270	1446.72000	573.65260	450.66190	99.89999	2.99839	690.84990	1277.46001	1.24052	2054.81500	
.990	677.78740	1447.07001	574.02860	450.54810	99.89999	2.99940	690.41990	1277.52000	1.24022	2054.81500	
2.010	678.05000	1446.89999	573.82570	450.53270	99.80000	2.99959	690.67990	1277.59000	1.23071	2054.81500	
3.016	678.05000	1446.89999	573.82570	450.69380	100.00000	2.99819	690.67990	1277.66000	1.22113	2054.81500	
4.019	678.07890	1447.00999	573.87840	450.52830	99.80000	2.99983	690.71000	1277.71001	1.22103	2054.81500	
5.014	678.01900	1446.98000	573.88450	450.68070	100.00000	2.99839	690.64990	1277.78000	1.21788	2054.85001	
6.010	677.97310	1446.62000	573.69310	450.62350	99.89999	2.99828	690.59990	1277.81000	1.23738	2054.85001	
7.007	677.97800	1447.05000	573.94140	450.58620	99.89999	2.99927	690.60990	1277.89999	1.23380	2054.81500	
8.004	678.40010	1446.98000	573.73390	450.67240	99.89999	2.99891	691.02980	1277.92999	1.23385	2054.81500	
1.099	GRADIENT	.04605	.01892	-.00719	-.00951	-.02058	.00017	.04616	.06860	-.00142	.00339

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 848

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM004) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q (PSF)	T (R)	TT (F)	RN/L	PC	PREF	SH10+3
.800	-8.006	1323.72099	2018.05000	593.21120	496.23240	100.10000	3.75987	1340.28999	1733.89000	1.26966 2056.84500
.800	-6.987	1324.13200	2018.17999	593.02760	496.26730	100.10000	3.75953	1340.70000	1733.89999	1.24413 2056.84500
.800	-5.995	1323.67500	2017.78000	593.04270	496.15800	100.06000	3.76000	1340.24001	1733.89000	1.24123 2056.81000
.800	-4.992	1323.82100	2017.49001	592.72880	496.19380	100.00000	3.75886	1340.38000	1733.92000	1.22888 2056.84500
.800	-3.994	1324.16000	2018.31000	593.10470	496.26120	100.10000	3.75987	1340.73000	1733.92000	1.22217 2056.81000
.800	-2.997	1324.45200	2018.42000	592.98830	496.28470	100.10000	3.75969	1341.02000	1733.91000	1.22210 2056.81000
.800	-1.988	1323.82401	2017.87000	593.00730	496.07890	99.89999	3.76087	1340.39000	1733.92999	1.21316 2056.81000
.800	- .984	1323.94800	2018.35001	593.27880	496.05830	99.89999	3.76210	1340.52000	1733.92000	1.20673 2056.81000
.800	.014	1323.90500	2017.92000	592.99020	496.26120	100.10000	3.75915	1340.47000	1733.94000	1.18270 2056.81000
.800	1.008	1324.21800	2017.92999	592.78470	496.20560	100.00000	3.75948	1340.78000	1733.96001	1.17968 2056.81000
.800	2.017	1324.04800	2017.78000	592.78880	496.19780	100.00000	3.75933	1340.61000	1733.98000	1.17378 2056.81000
.800	3.016	1324.41400	2018.24001	592.88040	496.29350	100.10000	3.75921	1340.98000	1734.02000	1.16756 2056.81000
.800	4.004	1324.36800	2017.98000	592.71920	496.30660	100.10000	3.75850	1340.92999	1734.03999	1.15293 2056.84500
.800	5.003	1324.52400	2018.28000	592.83500	496.30220	100.10000	3.75913	1341.09000	1734.06000	1.14397 2056.84500
.800	6.002	1324.09801	2017.82001	592.78440	496.28910	100.10000	3.75850	1340.66000	1734.11000	1.13841 2056.84500
.799	7.001	1324.73000	2018.03999	592.51710	496.34130	100.10000	3.75804	1341.28999	1734.14000	1.15584 2056.88000
.800	8.000	1324.25600	2018.00999	592.81740	496.38110	100.20000	3.75793	1340.82001	1734.17000	1.10112 2056.88000
	GRADIENT	.03517	.00282	-.02183	.00839	.00543	-.00010	.03487	.01356	-.00067 -.00001

1A310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM005) ( 04 Oct 91 )

PARAMETRIC DATA

$$\text{BETA} = \frac{1000}{180,000} \text{ PHI} = 0.005555555555555556 \text{ PHI}$$

$$\text{GRADIENT INTERVAL} = \frac{\text{BN/L}}{\text{PIN NO}} = \frac{3.20}{1105/0} = -5.00/5.00$$

	$Q(PSF)$	$T(R)$	$T(F)$	RN/L	PC	PREF	PAIM
$\Delta PMA$	P	PT					

$$\text{RUN NO } 1115 / \quad R_N/L = 3.75 \quad \text{GRADIENT INTERVAL} = -5.00 / \quad 5.00 /$$

卷之三

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FA18 OFF

OCT 6 1

## PARAMETRIC DATA

RUN NO. 1119/ 0 RN/L = 3.89 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO. 1150/ 0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 851

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM005) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.250	7.989	555.33740	1437.92999	607.12010	427.60500	101.50000	2.99024	567.90990	1156.10001	1.35974	2055.09500
1.250	6.983	555.20390	1438.33000	607.35210	427.5450	101.50000	2.99104	567.77980	1156.12000	1.35585	2055.09500
1.249	5.992	555.62520	1438.08000	607.13330	427.65550	101.50000	2.99058	568.20000	1156.12000	1.34212	2055.09500
1.250	4.988	555.33590	1438.09000	607.20170	427.59110	101.50000	2.99057	567.90990	1156.14000	1.33864	2055.09500
1.250	3.993	555.39550	1438.13000	607.20900	427.60080	101.50000	2.99066	567.97000	1156.14000	1.33860	2055.09500
1.250	2.981	555.12520	1438.23000	607.311880	427.45650	101.40000	2.99153	567.70000	1156.14000	1.33504	2055.06000
1.250	1.992	555.33350	1438.34000	607.322890	427.49320	101.40000	2.99178	567.90990	1156.14999	1.29403	2055.09500
1.250	.988	555.01660	1438.09000	607.27150	427.36840	101.30000	2.99193	567.58980	1156.16000	1.28421	2055.13000
1.250	-.014	555.10690	1438.03000	607.22120	427.39330	101.30000	2.99182	567.67990	1156.17000	1.31122	2055.13000
1.250	-.1.015	555.20750	1437.97000	607.16890	427.42070	101.30000	2.99171	567.77980	1156.19000	1.30449	2055.09500
1.250	-.2.013	555.26880	1437.80000	607.06930	427.44850	101.30000	2.99137	567.83980	1156.20000	1.29452	2055.09500
1.250	-.3.008	555.15360	1438.38000	607.38840	427.37400	101.30000	2.99254	567.73000	1156.23000	1.28729	2055.13000
	GRADIENT	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM006) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.599	-3.996	1600.05200	2039.53000	402.08400	521.61870	99.39999	3.19259	1613.50000	1946.11000	9.41744	2058.31500
.600	-2.990	1599.45000	2039.62000	402.65410	521.55590	99.39999	3.19474	1612.91000	1946.16000	9.41702	2058.31500
.599	-1.995	1599.45500	2038.95000	402.08640	521.60520	99.39999	3.19211	1612.89999	1946.20000	9.40274	2058.31500
.600	-.996	1599.28700	2039.64999	402.81250	521.53860	99.39999	3.19535	1612.75000	1946.24001	9.41688	2058.31500
.600	.010	1598.91901	2039.72000	403.17330	521.49900	99.39999	3.19672	1612.39000	1946.25999	9.39914	2058.31500
.600	1.007	1598.99100	2039.25999	402.72800	521.53930	99.39999	3.19471	1612.45000	1946.30000	9.41871	2058.31500
.600	1.997	1598.88901	2040.14999	403.55910	521.37160	99.30000	3.19921	1612.37000	1946.35001	9.41454	2058.31500
.601	2.992	1598.67500	2040.19000	403.76860	521.44210	99.39999	3.19928	1612.16000	1946.37000	9.44926	2058.31500
.601	3.989	1598.56099	2040.71001	404.30620	521.29930	99.30000	3.20240	1612.05000	1946.39999	9.46431	2058.31500
	GRADIENT	-.16303	.14084	.25204	-.03482	-.01001	.00111	-.15724	.03591	.00516	-.00000

C. 4

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 852  
(VCM006) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1113/ 0	RN/L =	3.75	GRADIENT INTERVAL =	-5.00/ 5.00	ALPPHA =	.000	PHI =	90.000	PREF	SH10+3	PATM
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
.800	-3.992	1324.54300	2018.39000	592.90380	496.91720	100.80000	3.75340	1341.11000	1804.42999	1.96588	2057	05499	
.800	-2.987	1323.89600	2017.87000	592.95920	496.79570	100.70000	3.75384	1340.46001	1804.42999	1.93304	2057	05499	
.800	-1.977	1323.75000	2017.52000	592.79910	496.89330	100.80000	3.75218	1340.31000	1804.48000	1.93811	2057	05499	
.800	- .989	1323.77800	2018.24001	593.31300	496.84570	100.80000	3.75431	1340.35001	1804.49001	1.92797	2057	05499	
.800	.016	1324.16600	2017.99001	592.86430	496.90480	100.80000	3.75286	1340.73000	1804.53999	1.92350	2057	05499	
.800	.001	1324.81200	2018.02000	592.44680	496.97220	100.80000	3.75180	1341.37000	1804.53999	1.90008	2057	05499	
.799	2.003	1324.38100	2017.82001	592.59180	496.93990	100.80000	3.75196	1340.94000	1804.55000	1.89562	2057	05499	
.800	3.002	1324.50800	2018.03999	592.66820	496.93800	100.80000	3.75240	1341.07001	1804.61000	1.87693	2057	05499	
.800	3.990	1324.11800	2017.86000	592.80080	496.99760	100.90000	3.75169	1340.67999	1804.64000	1.85878	2057	05499	
GRADIENT	.04050	.02068	-.04287	.01617	.01169	-.00024	.03980	.02624	-.01186	.000000			

	RUN NO.	1120/ 0	RN/L =	3.89	GRADIENT INTERVAL =	-5.00/ 5.00	ALPPHA =	.000	PHI =	90.000	PREF	SH10+3	PATM
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
.900	-3.986	1173.18300	1984.17000	665.16820	481.73240	100.10000	3.89420	1190.48000	1644.97000	1.09723	2056	81000	
.900	-2.981	1172.96400	1984.03000	665.20290	481.71630	100.10000	3.89410	1190.25999	1644.96001	1.09450	2056	81000	
.900	-1.982	1172.96100	1983.53999	664.86770	481.75000	100.10000	3.89276	1190.25000	1644.95000	1.09477	2056	77499	
.900	-.983	1173.53101	1983.85001	664.74170	481.79540	100.10000	3.89287	1190.82001	1644.97000	1.10022	2056	77499	
.900	.012	1173.53600	1984.13000	664.93090	481.77660	100.10000	3.89363	1190.83000	1644.99001	1.10006	2056	81000	
.899	1.002	1173.83701	1984.21001	664.80640	481.80640	100.10000	3.89345	1191.13000	1645.00999	1.10567	2056	77499	
.899	1.998	1173.68201	1983.81000	664.62380	481.81590	100.10000	3.89256	1190.97000	1645.00000	1.10873	2056	77499	
.900	3.003	1173.36501	1984.19000	665.07420	481.75220	100.10000	3.89402	1190.66000	1645.03000	1.11136	2056	73999	
.900	3.993	1173.28600	1984.00000	664.99050	481.75630	100.10000	3.89360	1190.58000	1645.05000	1.11431	2056	73999	
GRADIENT	.05620	.01167	-.02542	.00579	.00000	-.00004	.05598	.01120	.00255	-.00819			

	RUN NO.	1151/ 0	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	ALPPHA =	.000	PHI =	90.000	PREF	SH10+3	PATM
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.100	-3.983	677.82010	1446.85001	573.88770	450.81540	100.20000	2.99678	690.45000	1278.87000	1.20849	2055	09500	
1.100	-2.982	677.88820	1447.00000	573.94780	450.89580	100.30000	2.99640	690.51980	1278.89999	1.21469	2055	13000	
1.100	-1.980	677.75780	1447.06000	574.03440	450.86550	100.30000	2.99659	690.38990	1278.94000	1.20831	2055	09500	
1.100	-.995	677.90990	1446.89999	573.88130	450.98930	100.40000	2.99546	690.53980	1278.96001	1.21161	2055	13000	
1.100	.021	677.73580	1447.20000	574.12450	450.92940	100.40000	2.99623	690.36990	1279.00000	1.22087	2055	16501	
1.100	1.005	677.70830	1446.96001	573.99580	450.94560	100.40000	2.99569	690.33980	1279.00999	1.22746	2055	13000	
1.100	2.016	677.98120	1446.80000	573.79490	451.01170	100.40000	2.99520	690.60990	1279.06000	1.26655	2055	13000	
1.100	3.005	678.05640	1447.20000	573.99780	451.07080	100.50000	2.99538	690.68990	1279.11000	1.26620	2055	16501	
1.100	4.001	678.15840	1447.08000	573.88770	451.18140	100.60000	2.99436	690.78980	1279.16000	1.25646	2055	16501	
GRADIENT	.03509	.01772	-.00352	.03734	.04006	-.00026	.03520	.03473	.00800	.00760			

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 853

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM006) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1162/ O	RN/L =	3.00	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PARM
1.250	-3.987	555.14720	1437.99001	607.19210	427.10080	100.90000	2.99456	567.72000	1156.28999	1.16919 2055.13000
1.250	-2.967	555.00730	1438.03999	607.24800	427.06590	100.90000	2.99464	567.57980	1156.28000	1.16609 2055.13000
1.250	-1.988	555.20700	1438.00000	607.18430	427.03690	100.80000	2.99529	567.77980	1156.28000	1.16307 2055.16501
1.250	- .984	555.26640	1438.06000	607.20170	427.04490	100.80000	2.99542	567.83980	1156.27000	1.13590 2055.16501
1.250	.027	555.22020	1437.67000	607.01420	426.99170	100.70000	2.99532	567.78980	1156.27000	1.12730 2055.16501
1.250	1.007	555.44360	1438.28999	607.27930	426.91210	100.60000	2.99732	568.01980	1156.28999	1.15676 2055.16501
1.250	2.002	555.34080	1437.57001	606.93700	426.95040	100.60000	2.99584	567.90990	1156.27000	1.15734 2055.20001
1.250	3.003	555.45580	1438.07001	607.16530	426.85720	100.50000	2.99758	568.02980	1156.28999	1.00000 2055.20001
GRADIENT	.05354	-.01570	-.01966	-.01570	-.03235	-.05967	.00040	.05351	-.00024	-.09852 .01001

(VCM007) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1107/ O	RN/L =	3.20	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PARM
.599	4.032	1600.48801	2040.07001	402.18120	521.52640	99.30000	3.19413	1613.94000	1946.70000	9.46732 2058.28000
.600	3.022	1599.76700	2040.44000	403.08230	521.43210	99.30000	3.19773	1613.24001	1946.72000	9.44809 2058.28000
.600	1.999	1599.59700	2040.34000	403.13870	521.51710	99.39999	3.19712	1613.07001	1946.72000	9.44856 2058.24500
.600	1.003	1599.85800	2040.48000	403.04220	521.53100	99.39999	3.19688	1613.33000	1946.77000	9.43043 2058.28000
.600	-.010	1599.60100	2040.14999	402.97530	521.53120	99.39999	3.19636	1613.07001	1946.80000	9.43198 2058.24500
.600	-.1.008	1599.11700	2040.42000	403.59890	521.46660	99.39999	3.19886	1612.60001	1946.83000	9.43071 2058.28000
.601	-2.016	1598.83000	2040.53000	403.92700	521.43160	99.39999	3.20014	1612.32001	1946.89000	9.43020 2058.24500
.601	-3.016	1598.83600	2040.25000	403.68650	521.45260	99.39999	3.19903	1612.32001	1946.89000	9.39666 2058.24500
.601	-4.033	1598.96300	2040.52000	403.80980	521.4480	99.39999	3.19971	1612.45000	1946.92999	9.37802 2058.24500
GRADIENT	.18485	-.025568	-.17316	.00826	-.17316	-.01160	-.00057	.18125	-.03028	.00907 .00406

	RUN NO.	1114/ O	RN/L =	3.75	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	PREF	SH10+3 PARM
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PARM	
.800	4.024	1323.83000	2018.13000	593.19600	497.03640	101.00000	3.75216	1340.39999	1805.03999	1.71356 2057.09000	
.800	3.019	1324.01300	2018.06000	593.01980	496.97220	100.90000	3.75248	1340.58000	1805.07001	1.69677 2057.09000	
.800	1.997	1323.78300	2017.92999	593.07980	497.04540	101.00000	3.75164	1340.35001	1805.10001	1.69688 2057.09000	
.800	1.001	1324.11600	2017.94000	592.86080	497.08060	101.00000	3.75107	1340.67999	1805.12000	1.69687 2057.09000	
.800	-.016	1324.00500	2017.91000	592.91380	497.07080	101.00000	3.75118	1340.57001	1805.12000	1.68020 2057.09000	
.800	-.1.009	1324.39700	2018.08000	592.77390	497.10060	101.00000	3.75100	1340.96001	1805.19000	1.66352 2057.09000	
.799	-2.016	1324.67000	2018.03999	592.55810	497.13280	101.00000	3.75039	1341.23000	1805.20000	1.65124 2057.09000	
.800	-3.022	1324.07401	2018.62000	593.39230	497.02810	101.00000	3.75320	1340.64999	1805.22000	1.64668 2057.05499	
.800	-4.020	1324.06599	2017.98000	592.92500	497.07230	101.00000	3.75129	1340.63000	1805.24001	1.62289 2057.05499	
GRADIENT	-.05270	-.02383	.01819	-.00840	-.00498	-.00006	-.05250	-.02519	.01056	.00406	

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM007) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1121/ 0 RN/L = 3.89 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.900	4.024	1173.24400	1984.11000	665.09060	481.82980	100.20000	3.89305	1190.53999	1645.17000	1.11997	2056.73999
.900	3.019	1172.98000	1983.62000	664.91110	481.83280	100.20000	3.89206	1190.27000	1645.17999	1.11453	2056.73999
.900	1.997	1173.35201	1983.70000	664.74510	481.87080	100.20000	3.89179	1190.64000	1645.21001	1.11734	2056.73999
.900	.996	1173.21300	1984.20000	665.17140	481.81980	100.20000	3.89334	1190.50999	1645.22000	1.21204	2056.73999
.900	-.017	1173.11501	1984.02000	665.10570	481.82080	100.20000	3.89298	1190.41000	1645.24001	1.21125	2056.73999
.900	-.1.009	1173.48801	1984.03000	664.89090	481.86380	100.20000	3.89252	1190.78000	1645.25999	1.21833	2056.77499
.900	-2.027	1173.61800	1984.10001	664.86160	481.87430	100.20000	3.89254	1190.91000	1645.28000	1.22138	2056.77499
.900	-3.018	1173.64900	1984.00999	664.78120	481.97020	100.30000	3.89135	1190.94000	1645.27000	1.21834	2056.77499
.899	-4.023	1173.76900	1984.02000	664.71610	481.98360	100.30000	3.89122	1191.06000	1645.28999	1.22454	2056.77499
GRADIENT	-.08139	-.02388	-.03203	-.01784	-.01158	.00015	-.08116	-.01542	-.01565	-.00579	-.00538

RUN NO. 1152/ 0 RN/L = 3.00 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.100	4.020	677.74000	1446.84000	573.91330	451.20390	100.70000	2.99331	690.36990	1279.28000	1.20535	2055.23499
1.100	2.996	677.89970	1446.91000	573.89090	451.22780	100.70000	2.99339	690.52980	1279.30000	1.20215	2055.23499
1.100	1.984	677.92920	1446.94000	573.89670	451.15040	100.60000	2.99415	690.55980	1279.32001	1.19586	2055.23499
1.100	.996	677.62840	1446.94000	574.01560	450.93210	100.40000	2.99568	690.26000	1279.33000	1.19274	2055.23499
1.100	-.016	677.82740	1447.07001	574.01270	450.87790	100.30000	2.99559	690.46000	1279.35001	1.19263	2055.20001
1.100	-1.001	677.9860	1446.97000	573.96580	450.88130	100.30000	2.99637	690.42990	1279.38000	1.17722	2055.23499
1.099	-2.017	678.36160	1446.87000	573.68530	450.83590	100.10000	2.99727	690.99000	1279.39000	1.17731	2055.23499
1.100	-3.025	678.10740	1447.14000	573.94290	450.76370	100.10000	2.99801	690.74000	1279.42999	1.18636	2055.26999
1.099	-4.035	678.19040	1446.91000	573.77610	450.71950	100.00000	2.99815	690.81980	1279.45000	1.18965	2055.23499
GRADIENT	-.05746	-.01428	.01437	.06649	.09453	-.00067	-.05747	-.02090	.00270	-.00174	-.00538

RUN NO.	1163/ 0	RN/L	= 3.00	GRADIENT	INTERVAL	= -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.250	4.024	555.47340	1438.28999	607.27270	426.76610	100.40000	2.99873	568.04980	1156.28999	1.08607	2055.20001
1.250	2.996	555.29420	1438.28000	607.30690	426.72750	100.40000	2.99869	567.86990	1156.28000	1.0502	2055.20001
1.250	1.998	555.15480	1438.24001	607.31710	426.62430	100.30000	2.99930	567.73000	1156.27000	1.0504	2055.23499
1.250	.993	555.14060	1437.64000	607.01640	426.67190	100.10000	2.99807	567.71000	1156.28000	1.04715	2055.20001
1.250	-.018	555.45780	1437.87000	607.06350	426.56960	100.10000	2.99999	568.02980	1156.27000	1.02778	2055.23499
1.250	-1.013	555.08400	1438.38000	607.40380	426.44430	100.10000	3.00099	567.65990	1156.25999	1.03014	2055.23499
1.249	-2.031	555.46950	1437.67000	606.95950	426.51290	100.00000	3.00029	568.03980	1156.25999	1.04713	2055.23499
1.250	-3.021	555.45530	1438.11000	607.18550	426.39650	99.89999	3.00190	568.02980	1156.25999	1.04958	2055.23499
GRADIENT	-.01009	.04346	.02422	.05090	.07454	-.00044	-.00967	.00415	-.00538	-.00174	-.00538

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 855  
IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF (VCM008) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.920	.010	1140.	33000	1971.07001	675.49000	480.02690	101.60000	3.88673	1157.	1.27715	2056.
		-4.029	1140.	52400	1970.81000	675.20140	480.06840	101.60000	3.88580	1157.	1.27732
	GRADIENT			.06437	.07144		-.01027	.00000	.00023	1610.	2056.
									-.04703	64000	.67001
										-.02970	.00004
											.00001
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.950	.010	1090.	06000	1948.08000	688.42380	475.89790	102.10000	3.87941	1107.	1.06438	2056.
		-4.031	1090.	64200	1948.23000	688.20390	475.96000	102.10000	3.87917	1107.	1.06979
	GRADIENT				.05442		-.01537	.00000	.00006	.38000	.56500
									-.14354	1694.	.00000
										-.00248	.00000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.980	.008	1038.	25900	1919.92999	697.74630	471.11180	101.90000	3.86190	1055.	1.4901	2056.
		-4.035	1038.	52800	1920.09000	697.70920	471.21920	102.00000	3.86116	1055.	1.49893
	GRADIENT				.00918		-.02657	.02474	.00018	.75000	.49500
									-.06680	1548.	.00002
										.62000	.00000
										-.01980	.00000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.050	.029	917.	18900	1842.10001	707.76860	460.20510	102.00000	3.76868	933.	1.14029	2055.
		-4.030	917.	24830	1842.16000	707.77830	460.20920	102.00000	3.76878	933.	1.13733
	GRADIENT						-.001479	.00101	.00003	.99000	.89999
									-.01481	1517.	.00073
										-.01233	.00860
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.150	.012	633.	40840	1440.02000	586.32010	442.92720	100.40000	2.99654	646.	1.29588	2055.
		4.038	633.	36960	1439.91000	586.27170	442.85010	100.30000	2.99700	646.	1.29262
	GRADIENT				.02715		.01195	.01903	.00012	.01000	.13000
									-.00982	1231.	.00080
										19000	-.00001





DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 858

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM0111) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.920	-2.004	1140	39301	1970.86000	675.31130	480.22020	101.80000	3.88430	1157.72000	1611.72000	1.25165 2056.56500
.920	2.037	1140	24400	1970.72000	675.30250	480.21190	101.80000	3.88411	1157.57001	1611.77000	1.25174 2056.60001
	GRADIENT			.03464	-.03687	-.00218	-.00205	-.00005	-.03711	.01237	.00002 .00865
RUN NO.	1126/ 0	RN/L	=	3.88	GRADIENT	INTERVAL	=	-5.00/	5.00		
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.950	-2.001	1090	11200	1948.00999	688.34990	475.65500	101.80000	3.88186	1107.42999	1694.58000	1.00832 2056.49500
.950	2.043	1089	95200	1947.95000	688.39790	475.5470	101.70000	3.88277	1107.27000	1694.60001	.99798 2056.49500
	GRADIENT			.03957	-.01483	.01187	-.02480	.00023	-.03956	.00495	-.00256 .00000
RUN NO.	1131/ 0	RN/L	=	3.88	GRADIENT	INTERVAL	=	-5.00/	5.00		
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.980	-2.002	1037	99699	1919.98000	697.91480	471.07420	101.90000	3.86228	1055.22000	1549.00000	94652 2056.42499
.980	2.039	1038	02800	1919.89000	697.84030	471.08470	101.90000	3.86202	1055.25000	1549.03000	.93676 2056.42499
	GRADIENT			.00767	-.02227	.01843	-.02620	.00006	.00742	.00742	-.00241 .00000
RUN NO.	1142/ 0	RN/L	=	3.77	GRADIENT	INTERVAL	=	-5.00/	5.00		
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.050	-2.002	917	65720	1842.37000	707.72240	460.17090	101.90000	3.76988	934.39990	1518.49001	1.13720 2055.82999
1.050	2.037	917	11960	1842.03000	707.75730	460.20020	102.00000	3.76856	933.85990	1518.53999	1.13158 2055.82999
	GRADIENT			-.13311	-.08418	.00864	.00726	.02476	-.00033	.01237	-.00139 .00000
RUN NO.	1157/ 0	RN/L	=	3.00	GRADIENT	INTERVAL	=	-5.00/	5.00		
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.150	-2.009	633	69530	1440.36000	586.41210	442.55910	99.89999	3.00071	646.33980	1232.60001	1.29557 2055.09500
1.150	2.023	633	15970	1439.88000	586.32640	442.57350	100.00000	2.99910	645.79980	1232.64999	1.28929 2055.09500
	GRADIENT			-.13282	-.11903	-.02125	.00357	.02480	-.00040	-.13392	.01240 -.00156 -.00000

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 859

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO12) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	RN/L =	3.88	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	-90.000
MACH	BETA P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
.950	-2.000	1089.76199	1947.86000	688.44260	475.62210	101.80000	3.88185	1107.08000	.99031 2056.49500
.950	2.038	1089.75301	1947.75000	688.37480	475.62840	101.80000	3.88157	1107.07001	.99036 2056.49500
GRADIENT				.00156		-.00000	-.00007	-.00248	.00991 .00001

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO13) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
.899	-8.002	753.11450	1273.00000	426.50390	481.72410	100.00000	2.49845	763.11990	.87990 1.86257 2046.20500
.900	-6.995	752.68900	1273.14000	426.85330	481.63130	100.00000	2.49939	762.70000	.979.02980 1.84818 2046.24001
.900	-5.993	752.73900	1273.17000	426.84400	481.63720	100.00000	2.49941	762.75000	.979.13990 1.82472 2046.24001
.900	-4.991	752.64060	1273.02000	426.79980	481.63550	100.00000	2.49913	762.64990	.979.28980 1.81101 2046.24001
.900	-3.993	752.89060	1273.14999	426.74020	481.66700	100.00000	2.49916	762.89990	.979.36990 1.79242 2046.24001
.900	-2.991	752.78340	1272.89000	426.62520	481.67550	100.00000	2.49858	762.78980	.979.49000 1.76097 2046.24001
.900	-1.995	752.68970	1273.11000	426.83230	481.63480	100.00000	2.49931	762.70000	.979.58980 1.74273 2046.24001
.900	-.992	752.69170	1272.97000	426.73510	481.65010	100.00000	2.49892	762.72000	.979.72000 1.74739 2046.27499
.900	.021	752.63160	1272.92999	426.74290	481.64360	100.00000	2.49889	762.63990	.979.79980 1.73852 2046.27499
.900	1.007	752.84400	1272.87000	426.57540	481.68870	100.00000	2.49845	762.84990	.979.89990 1.73415 2046.31000
.900	2.009	752.84400	1272.88000	426.58230	481.68770	100.00000	2.49848	762.84990	.979.98000 1.72527 2046.31000
.900	3.012	752.83080	1273.10001	426.74120	481.66160	100.00000	2.49909	762.83980	.980.09990 1.72940 2046.31000
.900	4.010	752.83230	1272.99001	426.66500	481.67360	100.00000	2.49879	762.83980	.980.17990 1.72512 2046.31000
.900	5.008	752.90280	1273.00000	426.62990	481.68550	100.00000	2.49873	762.90990	.980.28980 1.71629 2046.31000
.900	6.007	753.02510	1272.89999	426.48850	481.71870	100.00000	2.49830	763.02980	.980.36990 1.70764 2046.31000
.900	7.006	752.96970	1273.25000	426.76170	481.67070	100.00000	2.49932	762.98000	.980.46000 1.70279 2046.34500
.900	7.999	753.10910	1273.38000	426.76810	481.68210	100.00000	2.49950	763.11990	.980.54980 1.67229 2046.34500
GRADIENT						.00315			-.00004 .01196 -.00865 .01017

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( VCMO13 ) ( 04 OCT 91 ) PAGE 860

## PARAMETRIC DATA

RUN NO.	1165 / 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA = .000	PHI = .000	PREF	SH10+3	PATM
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC		
1.249	-7.994	463.00120	1198.06000	505.77610	426.54170	100.00000	2.50026	473.12990	1058.30000
1.249	-6.987	462.84250	1197.92999	505.74510	426.36080	99.80000	2.50115	472.97000	1058.36000
1.250	-5.992	462.54390	1197.84000	505.76490	426.29150	99.80000	2.50093	472.66990	1058.42000
1.249	-4.992	462.81350	1197.82001	505.69580	426.36430	99.80000	2.50093	472.93990	1058.47000
1.250	-3.996	462.60280	1198.00999	505.63840	426.41910	100.00000	2.50011	472.73000	1058.50000
1.250	-2.995	462.44410	1197.86000	505.79690	426.33910	99.89999	2.50037	472.56980	1058.53999
1.250	-1.995	462.70390	1197.78999	505.70460	426.56710	100.10000	2.49909	472.82980	1058.59000
1.250	-0.991	462.41380	1197.95000	505.84910	426.47440	100.10000	2.49937	472.53980	1058.62000
1.250	.024	462.49340	1197.96001	505.83690	426.57060	100.20000	2.49882	472.61990	1058.64999
1.250	1.010	462.71240	1198.00999	505.81420	426.39450	99.89999	2.50071	472.83980	1058.67999
1.250	2.004	462.78150	1198.13000	505.85990	426.47680	100.00000	2.50038	472.90990	1058.72000
1.250	3.014	462.68090	1198.23000	505.93260	426.4020	100.00000	2.50057	472.80980	1058.75000
1.250	4.011	462.80080	1198.21001	505.89620	426.47390	100.00000	2.50054	472.92990	1058.80000
1.250	5.023	462.78250	1197.97000	505.77860	426.49340	100.00000	2.50005	472.90990	1058.85001
1.249	6.004	462.88110	1198.14000	505.84330	426.50200	100.00000	2.50041	473.00980	1058.86000
1.249	7.008	462.89090	1198.17000	505.85600	426.50150	100.00000	2.50047	473.01980	1058.89999
1.249	8.005	462.88380	1197.77000	505.65500	426.54030	100.00000	2.49966	473.00980	1058.92999
GRADIENT	.01344		.04281	.01874	.00753	.01093	.00002	.01377	.03585
RUN NO.	1185 / 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00					
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
1.400	-8.002	382.36130	1216.07001	524.28980	402.48780	100.50000	2.49813	392.07980	899.89990
1.400	-6.991	382.22290	1216.10001	524.30590	402.44340	100.50000	2.49808	391.93990	899.99000
1.400	-5.996	382.23440	1215.83000	524.18750	402.47240	100.50000	2.49760	391.95000	900.02980
1.400	-5.000	382.34180	1216.03999	524.27710	402.48490	100.50000	2.49806	392.05980	900.12990
1.400	-3.994	382.21240	1216.16000	524.33230	402.43460	100.50000	2.49818	391.92990	900.23000
1.400	-2.994	382.10670	1215.64000	524.10690	402.45190	100.50000	2.49716	391.81980	900.28980
1.400	-1.993	382.25220	1216.14000	524.32280	402.52030	100.60000	2.49758	391.97000	900.36990
1.400	-.995	382.10570	1215.84000	524.19430	402.50460	100.60000	2.49693	391.81980	900.41990
1.400	.024	382.12430	1216.03999	524.28170	402.49120	100.60000	2.49731	391.83980	900.48000
1.400	1.005	382.27200	1216.13000	524.31790	402.52710	100.60000	2.49758	391.99000	900.55980
1.400	2.006	382.30180	1216.13000	524.31740	402.53610	100.60000	2.49760	392.01980	900.63990
1.400	3.021	382.11400	1216.09000	524.30370	402.55520	100.70000	2.49680	391.82980	900.72000
1.400	4.018	382.02610	1215.89999	524.22240	402.54660	100.70000	2.49639	391.74000	900.78980
1.400	5.009	382.16310	1216.17999	524.34200	402.56150	100.70000	2.49700	391.87990	900.88990
1.400	6.017	382.15530	1215.80000	524.17580	402.59500	100.70000	2.49630	391.86990	900.95000
1.400	7.009	382.32100	1216.20000	524.34770	402.53520	100.60000	2.49774	392.03980	901.02980
1.399	8.011	382.32400	1215.73000	524.14180	402.58060	100.60000	2.49689	392.03980	901.11990
GRADIENT	-.00766		.00964	.00438	.01351	.02331	-.00013	.00770	.00180

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO13) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1203/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
ALPHA									
1.450	-8.005	358.84400	1226.14000	528.23410	394.81640	101.20000	2.49227	368.31980	976.58980
	-7.000	359.23780	1226.21001	528.28340	394.86330	101.10000	2.49336	368.72000	976.57980
	-6.005	359.14060	1225.98000	528.18260	394.92430	101.20000	2.49227	368.61990	976.56980
	-5.000	358.97190	1226.17000	528.25340	394.85400	101.20000	2.49244	368.45000	976.57980
	-3.999	358.97530	1225.53999	527.99150	394.84250	101.10000	2.49193	368.45000	976.57980
	-3.000	359.04250	1225.86000	528.12790	394.90450	101.20000	2.49196	368.51980	976.58980
	-2.006	359.11010	1226.13000	528.24370	394.90090	101.20000	2.49250	368.58980	976.59990
	-1.002	358.74540	1226.17000	528.24150	394.78270	101.20000	2.49223	368.22000	976.63990
	-1.450	.003	358.49850	1226.20000	528.14120	394.63180	101.10000	2.49264	367.97000
	1.450	1.006	358.98340	1225.89999	528.14180	101.10000	2.49257	368.46000	976.67990
	1.450	2.001	358.70750	1225.85001	528.10640	394.72970	101.10000	2.49222	368.17990
	1.451	2.996	358.56910	1225.95000	528.14090	394.67700	101.10000	2.49227	368.03980
	1.452	4.002	359.12160	1225.84000	528.12350	394.86080	101.10000	2.49260	368.59990
	1.449	4.994	358.63600	1226.34000	528.30660	394.66240	101.10000	2.49302	368.10990
	1.451	6.001	358.78520	1226.06000	528.19800	394.80520	101.20000	2.49207	368.25980
	1.450	6.988	359.00290	1225.91000	528.14670	394.81710	101.10000	2.49261	368.48000
	1.449	7.995	359.22020	1225.86000	528.13700	394.96040	101.20000	2.49213	368.70000
GRADIENT	-	.02801	.01351	.00416	-.01710	-.01001	.00006	-.02836	-.01793

RUN NO.	1276/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	5.00
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
ALPHA									
1.474	-8.000	347.85230	1229.94148	529.04414	390.63060	101.00000	2.49306	357.18990	937.16990
	-6.979	348.16720	1229.99370	529.09273	390.65920	100.90000	2.49404	357.50980	937.17990
	-5.995	347.98930	1230.08415	529.11367	390.45020	100.70000	2.49528	357.32980	937.16990
	-4.994	348.17600	1230.23581	529.19247	390.50460	100.70000	2.49558	357.51980	937.18990
	-3.994	348.14600	1230.11005	529.13754	390.48680	100.70000	2.49571	357.49000	937.18990
	-2.994	348.21310	1230.40605	529.26234	390.33740	100.50000	2.49758	357.55980	937.21000
	-1.979	348.01660	1230.28445	529.19624	390.21190	100.40000	2.49783	357.35990	937.23000
	-1.473	348.25420	1230.03238	529.11507	390.31250	100.40000	2.49761	357.59990	937.24000
	-0.14	348.27270	1230.36702	529.25321	390.22710	100.30000	2.49864	357.61990	937.24000
	1.011	348.31150	1230.30251	529.22929	390.15700	100.20000	2.49952	357.65990	937.25980
	1.473	2.005	348.38060	1230.52893	529.32818	390.11400	100.10000	2.50010	357.73000
	1.474	3.010	348.26070	1230.80014	529.42681	390.04220	100.10000	2.50062	357.60990
	1.474	4.022	348.04520	1230.28017	529.19637	389.91890	100.00000	2.50069	357.38990
	5.008	348.19560	1229.83008	529.02734	389.95340	99.89999	2.50038	357.53980	937.28980
	1.473	6.004	348.11940	1229.20575	528.76770	390.11620	100.10000	2.49818	357.46000
	7.012	347.93550	1228.39944	528.42327	389.97580	99.89999	2.49808	357.26980	937.28980
	8.008	347.65260	1228.13049	528.29081	389.99930	100.00000	2.49633	356.98000	937.29980
GRADIENT		.00821	.03770	.01586	-.05906	-.07993	.00660	.00867	.01021

SH10+3

PATM

SH10+3

PATM

SH10+3

PATM

SH10+3

PATM

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM013) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	P	PT	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	= .000
1.495	-7.999	336.95950	1228.07863	527.16111	386.42970	100.60000	2.49086	346.12990	947.51980	1.23720	2046.34500
1.495	-6.988	337.01780	1228.39268	527.29272	386.36080	100.50000	2.49188	346.18990	947.60990	1.23048	2046.34500
1.495	-5.993	337.21920	1229.46832	527.74320	386.39940	100.60000	2.49335	346.39990	947.65990	1.22940	2046.34500
1.495	-4.993	337.60740	1230.75288	528.29925	386.42750	100.60000	2.49569	346.79980	947.72000	1.21860	2046.34500
1.495	-3.987	337.69240	1231.44098	528.58221	386.38870	100.60000	2.49706	346.88990	947.76980	1.22109	2046.31000
1.495	-2.993	337.87520	1232.19720	528.90312	386.36740	100.60000	2.49881	347.07980	947.81980	1.22989	2046.34500
1.495	-1.994	337.90530	1232.02467	528.83898	386.38870	100.60000	2.49863	347.10990	947.84990	1.23327	2046.34500
1.495	-0.998	337.38430	1229.88734	527.92934	386.41260	100.60000	2.49432	346.56980	947.85990	1.23219	2046.34500
1.495	.015	336.95000	1228.07983	527.16073	386.43090	100.60000	2.49076	346.11990	947.88990	1.23399	2046.31000
1.496	1.008	337.70040	1231.75708	528.70846	386.35300	100.60000	2.49780	346.89990	947.91990	1.22713	2046.34500
1.495	2.005	337.47090	1230.35791	528.12559	386.47240	100.70000	2.49454	346.65990	947.97000	1.22853	2046.34500
1.495	3.010	337.03590	1228.83549	527.47106	386.47340	100.70000	2.49130	346.21000	947.97000	1.22365	2046.34500
1.495	4.011	337.28371	1230.09407	527.99976	386.47090	100.70000	2.49321	346.47000	948.00000	1.20346	2046.34500
1.495	5.007	337.96440	1232.65813	529.09703	386.47950	100.70000	2.49805	347.16990	948.04980	1.19164	2046.31000
1.495	6.015	338.16940	1233.06935	529.28477	386.52080	100.70000	2.49878	347.37990	948.08980	1.18507	2046.31000
1.496	7.007	337.80710	1232.67224	529.08394	386.49370	100.80000	2.49734	347.00980	948.10990	1.19160	2046.34500
1.496	8.008	337.70260	1231.80437	528.72775	386.46440	100.70000	2.49640	346.89990	948.13990	1.19556	2046.34500
GRADIENT	-.06397	-.21817	-.09413	.00860	.01272	-.00055	-.06614	-.02976	-.00086	-.00126	.00148

MACH	ALPHA	P	PT	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	RN/L	TT(F)	TT(F)	PREF
1.520	-7.999	327.53960	1238.03171	529.76688	382.39920	100.50000	2.49615	336.56980	950.68990	1.08952	2047.53500
1.520	-6.993	327.16110	1236.90628	529.36230	382.36230	100.50000	2.49397	336.17990	950.75980	1.09625	2047.53500
1.520	-5.993	327.75100	1238.89775	530.13497	382.37500	100.50000	2.49822	336.78980	950.82980	1.10318	2047.53500
1.520	-4.999	327.95210	1239.60735	530.44056	382.33790	100.50000	2.50046	337.00000	950.92990	1.13485	2047.53500
1.520	-3.982	327.01340	1236.39900	529.05345	382.23070	100.40000	2.49464	336.02980	950.99000	1.14073	2047.53500
1.520	-2.994	327.35990	1238.07626	529.75644	382.19920	100.40000	2.49789	336.38990	951.03980	1.13919	2047.53500
1.520	-1.995	328.11570	1240.57480	530.83984	382.25050	100.40000	2.50267	337.16990	951.09990	1.12508	2047.53500
1.520	-.986	328.23320	1240.90025	530.98406	382.28880	100.40000	2.50284	337.28980	951.14990	1.10431	2047.53500
1.520	.014	327.54590	1238.46643	529.93600	382.25950	100.40000	2.49816	336.57980	951.17990	1.11520	2047.53500
1.520	1.011	327.11600	1236.72868	529.19650	382.26610	100.40000	2.49472	336.12990	951.22000	1.11675	2047.53500
1.520	2.005	328.31860	1241.48247	531.22334	382.25440	100.40000	2.50415	337.37990	951.25000	1.11252	2047.53500
1.520	3.005	327.90720	1238.89427	530.15764	382.41410	100.50000	2.49867	336.95000	951.32980	1.11485	2047.57001
1.521	4.006	326.91580	1236.52893	529.08920	382.27690	100.50000	2.49372	335.92990	951.35990	1.12279	2047.53500
1.520	5.018	328.20680	1239.85962	530.57785	382.41480	100.50000	2.50094	337.25980	951.37990	1.12575	2047.53500
1.520	6.004	327.82860	1238.65390	530.05324	382.38530	100.50000	2.49862	336.86990	951.46000	1.13275	2047.53500
1.520	7.006	327.48780	1237.97224	529.73585	382.32500	100.50000	2.49717	336.51980	951.47000	1.13633	2047.53500
1.520	7.997	327.32350	1237.44991	529.50988	382.31910	100.50000	2.49603	336.34990	951.50980	1.13382	2047.53500
GRADIENT	-.01209	-.04390	-.01881	-.00622	.00423	-.00018	-.01266	-.00166	-.00265	-.00148	

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM013) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.543	-8.002	318.09350	1243.37097	530.17992	378.20870	100.20000	2.50082	326.96000	959.45000	1.25443	2046.06500
1.543	-7.003	318.02660	1242.92326	529.99781	378.222050	100.20000	2.50007	326.88990	959.50980	1.25814	2045.99500
1.544	-5.992	317.26030	1240.97990	529.11807	378.06030	100.10000	2.49641	326.09990	959.51980	1.25679	2046.03000
1.544	-4.982	317.62620	1243.43370	530.11642	378.03660	100.10000	2.49974	326.48000	899.32980	1.20637	2045.99500
1.544	-3.992	318.04490	1244.10387	530.45033	378.13230	100.10000	2.50121	326.90990	899.36990	1.19950	2045.99500
1.544	-2.993	318.02320	1244.80371	530.71099	378.06740	100.10000	2.50228	326.88990	899.43990	1.19569	2045.99500
1.544	-1.988	317.67330	1244.07091	530.36668	378.07710	100.20000	2.50003	326.52980	899.48000	1.19637	2045.99500
1.544	-.990	317.52320	1242.17928	529.62386	378.18700	100.20000	2.49675	326.36990	899.49000	1.20133	2045.96001
1.544	.015	317.01120	1240.15936	528.76225	378.11430	100.10000	2.49342	325.83980	899.51980	1.20640	2045.99500
1.544	1.011	317.90770	1243.61539	530.23727	378.14380	100.20000	2.50060	326.76980	899.62990	1.23799	2045.96001
1.543	2.011	317.96730	1243.32928	530.14090	378.18550	100.20000	2.50027	326.82980	899.66990	1.24151	2045.96001
1.543	3.010	317.64990	1241.58363	529.42079	378.15230	100.10000	2.49772	326.50000	899.67990	1.24971	2045.96001
1.543	4.006	317.35080	1240.46645	528.94218	378.15480	100.10000	2.49532	326.18990	899.70000	1.24435	2045.96001
1.543	5.012	317.23220	1240.74585	529.02503	378.09740	100.10000	2.49549	326.06980	899.72000	1.23761	2045.96001
1.543	6.009	317.56200	1241.83830	529.50006	378.12500	100.10000	2.49755	326.40990	899.73000	1.23013	2045.96001
1.544	7.005	317.78300	1242.99606	529.98060	378.10030	100.10000	2.49976	326.63990	899.76000	1.22899	2045.96001
1.543	8.012	318.12210	1244.04053	530.43907	378.13110	100.10000	2.50184	326.99000	899.76980	1.22479	2045.96001
GRADIENT		-.03239	-.33432	-.13272	.01165	-.00243	-.00046	-.03396	.04324	.00638	-.00488

DATE 04 OCT 91

## IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 864

(VCMO14) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1268/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	= .000	
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
ALPHA	-8.003	753.57710	1273.77000	426.75760	481.46730	99.70000	2.50168	763.58980	977.65990	.82508 2045 99500	
	-6.980	752.99800	1274.12000	427.34280	481.32370	99.70000	2.50340	763.01980	977.59990	.80265 2046 03000	
	-5.993	753.75780	1274.53999	427.17900	481.33110	99.59999	2.50414	763.77980	977.54980	.83589 2046 03000	
	-4.992	754.16850	1275.46001	427.56690	481.22070	99.50000	2.50670	764.20000	977.49000	.80620 2046 03000	
	-3.988	751.90330	1271.70000	426.33130	481.12700	99.39999	2.49994	761.89990	977.32980	.81080 2046 03000	
	-2.991	751.68920	1271.16000	426.08790	481.06010	99.30000	2.49932	761.67990	977.25980	.81178 2046 03000	
	-1.995	753.37790	1273.58000	426.47450	481.02100	99.20000	2.50432	763.38990	977.22000	.81181 2046 06500	
	-0.997	753.26220	1273.96001	427.07570	480.87280	99.09999	2.50609	763.27980	977.18990	.81601 2046 03000	
	.015	752.85420	1272.87000	426.56690	480.91600	99.09999	2.50364	762.85990	977.15990	.81894 2046 06500	
	.900	1.007	752.52000	1272.28000	426.36300	480.91870	99.09999	2.50246	762.51980	977.11990	.82380 2046 06500
	.900	2.004	752.64310	1272.83000	426.66750	480.88180	99.09999	2.50380	762.64990	977.08980	.82569 2046 06500
	.900	3.006	753.01980	1273.28999	426.75950	480.89090	99.09999	2.50457	763.02980	977.04980	.82765 2046 06500
	.900	4.010	753.36350	1273.92000	426.98780	480.89580	99.09999	2.50585	763.37990	977.02980	.82949 2046 06500
	.900	5.008	753.62180	1274.20000	427.02660	480.91260	99.09999	2.50628	763.63990	977.01980	.83839 2046 06500
	.900	6.001	753.76070	1274.33000	427.03320	480.92380	99.09999	2.50645	763.77980	976.99000	.88898 2046 06500
	.900	7.005	752.86600	1272.75000	426.47970	480.93120	99.09999	2.50329	762.86990	976.95000	.89100 2046 06500
	.900	8.009	752.06910	1271.36000	425.99900	480.93580	99.09999	2.50052	762.05980	976.92990	.88716 2046 10001
	.900	GRADIENT	.01423	.00371	-.00592	-.03431	.00024	.04243	.01417	-.04414	.00246 .00437

	RUN NO.	1264/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	= .000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
ALPHA	-7.999	462.68430	1197.75000	505.68850	426.18510	99.59999	2.50195	472.80980	903.66990	.95977 2045 47000
	-6.982	462.56050	1198.34000	505.01460	426.01640	99.50000	2.50372	472.68990	903.70000	.95412 2045 47000
	-5.996	462.41380	1197.95000	505.84910	426.01730	99.50000	2.50291	472.53980	903.76980	.93905 2045 47000
	-4.981	462.75150	1198.14000	505.87160	426.08690	99.50000	2.50334	472.87990	903.80980	.94145 2045 43500
	-3.991	462.58420	1197.81000	505.74100	426.07640	99.50000	2.50264	472.71000	903.84990	.94427 2045 43500
	-2.990	462.53220	1198.12000	505.90940	425.95510	99.39999	2.50386	472.65990	903.87990	.94402 2045 47000
	-1.990	462.53030	1198.39000	506.04660	425.92700	99.39999	2.50441	472.65990	903.92990	.94126 2045 47000
	-1.250	462.76200	1198.07001	505.83370	426.02050	99.39999	2.50379	472.88990	903.95000	.94662 2045 50500
	-1.250	462.26710	1197.53000	505.66850	425.94510	99.39999	2.50262	472.38990	903.99000	.92925 2045 50500
	0.14	462.45410	1197.85001	505.78960	426.03810	99.50000	2.50271	472.57980	904.03980	.92398 2045 47000
	1.010	462.52420	1197.84000	505.76930	426.05760	99.50000	2.50270	472.64990	904.08980	.91153 2045 50500
	1.250	462.50540	1198.14000	505.86940	426.08960	99.50000	2.50334	472.88990	904.11990	.91626 2045 50500
	1.250	462.71220	1198.07001	505.84470	426.08370	99.50000	2.50319	472.83980	904.13990	.90888 2045 50500
	1.250	462.58570	1197.58000	505.62400	426.10010	99.50000	2.50218	472.71000	904.16990	.93680 2045 50500
	1.250	462.85840	1198.55000	506.05590	426.07350	99.50000	2.50419	472.99000	904.21000	.90359 2045 50500
	1.250	462.68210	1197.66000	505.68210	426.07100	99.50000	2.50233	472.62990	904.23000	.89936 2045 50500
	1.250	462.69950	1198.44000	506.03490	426.04270	99.50000	2.50395	472.82980	904.26000	.90122 2045 50500
	1.250	462.69950	1198.44000	506.03490	426.04270	99.50000	2.50395	472.82980	904.26000	.00437 .00785
	GRADIENT	.00077	-.01137	-.00593	-.00593	-.00005	.00486	-.00005	.00068	.00068

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO14) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1258/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
ALPHA									
-7.996	382.00950	1215.39999	524.00390	402.30180	100.30000	2.49784	391.72000	859.96000	1.0824 2045.39999
1.400	381.65890	523.61720	402.28120	100.30000	2.49594	391.35990	860.01000	1.10611 2045.43500	
-6.985	381.88210	1215.17999	523.91020	402.28420	100.30000	2.49734	391.58980	860.03980	1.13838 2045.36501
-5.990	381.61770	1214.77000	523.73630	402.31520	100.40000	2.49581	391.31980	860.10990	1.12370 2045.39999
-4.989	382.23020	1214.86000	523.76290	402.49100	100.40000	2.49642	391.93990	860.12990	1.11170 2045.39999
-3.988	381.76540	1214.86000	523.77270	402.35110	100.40000	2.49608	391.47000	860.18990	1.09403 2045.39999
-2.988	381.78420	1215.05000	523.85520	402.33890	100.40000	2.49644	391.49000	860.24000	1.09094 2045.39999
-1.988	382.01340	1214.72000	523.76300	402.43900	100.40000	2.49600	391.72000	860.26980	1.08833 2045.36501
-0.990	381.85230	1215.17999	523.91090	402.27510	100.30000	2.49732	391.55980	860.27980	1.08501 2045.36501
-0.018	381.96260	1214.97000	523.81670	402.32840	100.30000	2.49702	391.66990	860.28980	1.08230 2045.36501
1.400	1.004	381.83520	1214.75999	523.72750	402.38160	100.40000	2.49595	391.53980	860.31980
1.400	2.005	381.83470	1214.85001	523.76680	402.30100	100.30000	2.49670	391.53980	860.34990
1.400	3.005	381.83370	1214.99001	523.82810	402.28760	100.30000	2.49696	391.53980	860.35990
1.400	4.023	381.78420	1215.03000	523.84670	402.26880	100.30000	2.49705	391.49000	860.37990
1.400	5.009	381.98900	1215.53000	524.06130	402.21140	100.20000	2.49865	391.70000	860.41990
1.400	6.011	381.60770	1214.81000	523.75390	402.16460	100.20000	2.49706	391.30980	860.42990
1.400	7.013	382.07060	1215.11000	523.87570	402.27560	100.20000	2.49795	391.77980	860.45000
1.400	8.005	-	-	.00436	-.00984	-.01213	.00009	-.00057	.02786 -.00467
GRADIENT	-.00063	.00992							

RUN NO.	1226/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	5.00
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
ALPHA									
-8.000	359.00100	1226.27000	528.29610	394.85380	101.20000	2.49265	368.48000	932.57980	1.84692 2046.76500
-6.989	358.56910	1225.89999	528.12010	394.75200	101.20000	2.49159	368.03980	932.64990	1.81933 2046.76500
-5.994	358.98320	1225.92000	528.14990	394.88040	101.20000	2.49202	368.46000	932.68990	1.81465 2046.73000
-4.994	358.70920	1225.52000	527.96950	394.76070	101.10000	2.49165	368.17990	932.74000	1.80135 2046.73000
-3.994	359.03080	1226.23000	528.28220	394.86690	101.10000	2.49260	368.50980	932.78980	1.80492 2046.73000
-2.994	359.03270	1225.85001	528.12330	394.83200	101.10000	2.49253	368.50980	932.83980	1.81011 2046.73000
-1.995	358.91280	1226.14999	528.24190	394.76680	101.10000	2.49295	368.38990	932.87990	1.80967 2046.76500
-0.986	358.89550	1225.70000	528.05370	394.80270	101.10000	2.49214	368.36990	932.91990	1.81033 2046.73000
-0.24	358.99190	1226.11000	528.22920	394.79520	101.10000	2.49295	368.47000	933.00000	1.79587 2046.73000
1.006	358.88500	1225.83000	528.10740	394.71700	101.00000	2.49295	368.35990	933.03980	1.77340 2046.76500
2.010	359.06130	1226.06000	528.21190	394.75120	101.00000	2.49352	368.53980	933.09990	1.75495 2046.73000
3.011	358.86080	1226.67000	528.45530	394.56180	100.90000	2.49500	368.33980	933.14990	1.74061 2046.73000
4.012	358.83720	1225.57001	527.99680	394.51460	100.70000	2.49423	368.30980	933.21000	1.73325 2046.73000
5.009	358.81150	1226.67999	528.45700	394.40450	100.70000	2.49616	368.28980	933.25000	1.72723 2046.73000
6.011	358.92550	1225.61000	528.01780	394.46850	100.60000	2.49498	368.39990	933.31980	1.72874 2046.76500
7.008	358.91380	1225.96001	528.16280	394.36210	100.50000	2.49618	368.38990	933.35990	1.73715 2046.76500
8.004	359.05980	1226.35001	528.33250	394.30180	100.40000	2.49760	368.53980	933.39990	1.73660 2046.76500
GRADIENT	.00072	.02441	.01017	-.02973	-.03935	.00028	.00085	.05215	-.00085 -.00001

1A310 (AEDC 16TE-783) ELOW ANGULI ABILITIES-FAIR QEE

(VCM015) ( 04 OCT 91 )

$$\text{GRADIENT INTERVAL} = -5.00$$

$$P \quad PT \quad Q(PSF) \quad T(R) \quad TT(F) \quad RN/L$$

REF ID: A1000000000000000000000000000000

IA310 (AEDC 16TE-783) FLOW ANGLES-FAIR OFF

1 OCT 91

## PARAMETRIC DATA

BURN NO 12001 0 BN/1 - 3 19 GRADIENT INTERVAL = -5 00/-5 00

## IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

( VCMO15 ) ( 04 OCT 91 ) PAGE 868

## PARAMETRIC DATA

MACH	ALPHA	P	PT	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000	PREF	SH10+3	PATM
1.473	7.996	347.56670	1227.01109	527.82777	390.02150	100.00000	2.49529	356.88990	937.58980	1.06030	2047.22000			
6.996	348.51270	1230.75662	529.42867	389.90840	99.89999	2.50352	357.86990	937.63990	1.06268	2047.25500				
5.986	348.41160	1231.07895	529.55002	389.96780	100.10000	2.50313	357.76980	937.70000	1.07077	2047.25500				
4.996	348.08810	1228.88155	528.63052	390.07100	100.10000	2.49883	357.42990	937.73000	1.06930	2047.25500				
3.985	347.22560	1226.02824	527.39410	389.91600	100.00000	2.49307	356.53980	937.75980	1.07235	2047.25500				
2.996	347.52250	1228.17325	528.29546	389.91600	100.00000	2.49699	356.84990	937.83980	1.04815	2047.25500				
1.992	348.28100	1230.08629	529.13738	390.05760	100.10000	2.50047	357.62990	937.84990	1.04935	2047.25500				
.983	348.58540	1229.92278	529.09576	390.21120	100.20000	2.50045	357.93990	937.91990	1.06905	2047.25500				
.017	348.34180	1229.41898	528.87043	390.04170	100.00000	2.50047	357.68990	937.93990	1.06666	2047.25500				
-1.014	347.95210	1228.47116	528.45232	389.99390	100.00000	2.49859	357.28980	937.98000	1.07025	2047.25500				
-2.008	347.67290	1227.15689	527.89489	390.01860	100.00000	2.49611	357.00000	938.00000	1.07422	2047.28999				
-3.008	347.48070	1226.12775	527.46010	390.04570	100.00000	2.49421	356.79980	938.02980	1.07795	2047.28999				
-4.009	347.70680	1228.08899	528.27489	389.92630	100.00000	2.49812	357.03980	938.05980	1.08186	2047.28999				
-5.005	347.94750	1227.17952	527.92731	390.08940	100.00000	2.49673	357.27980	938.13990	1.08559	2047.28999				
-6.012	347.34060	1226.88545	527.75645	389.95630	100.00000	2.49492	356.65990	938.16990	1.06037	2047.28999				
-7.009	347.44680	1227.27426	527.92382	389.95070	100.00000	2.49579	356.76980	938.18990	1.06283	2047.28999				
-8.005	348.02050	1228.73228	528.56457	390.00780	100.00000	2.49882	357.35990	938.20000	1.06162	2047.28999				
GRADIENT	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000			
MACH	ALPHA	P	PT	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000	PREF	SH10+3	PATM
1.495	7.991	338.02320	1232.46826	529.02871	386.56790	100.80000	2.49752	347.23000	947.33980	1.20432	2046.24001			
6.990	336.84060	1228.77672	527.42352	386.50440	100.80000	2.48999	346.00980	947.37990	1.20786	2046.24001				
5.991	336.89160	1228.33791	527.25591	386.55790	100.80000	2.48935	346.05980	947.40990	1.21146	2046.27499				
4.991	337.63400	1231.65573	528.65990	386.51440	100.80000	2.49566	346.82980	947.46000	1.20195	2046.24001				
3.990	337.78000	1232.02768	528.82542	386.53470	100.80000	2.49635	346.98000	947.48000	1.19847	2046.24001				
2.996	337.59640	1231.27443	528.50439	386.54150	100.80000	2.49487	346.78980	947.50980	1.19920	2046.24001				
1.987	337.42140	1231.00809	528.37789	386.51540	100.80000	2.49407	346.60990	947.54980	1.19320	2046.24001				
1.495	337.48270	1230.54538	528.20212	386.58350	100.80000	2.49323	346.66990	947.53980	1.19057	2046.24001				
.996	337.44460	1230.30850	528.10354	386.59690	100.80000	2.49269	346.62990	947.55980	1.18770	2046.24001				
.023	337.17210	1229.69571	527.82827	386.56030	100.80000	2.49137	346.34990	947.57980	1.18826	2046.24001				
1.495	-1.011	337.17210	1229.69571	527.82827	386.56030	100.80000	2.49120	346.38990	947.59990	1.18525	2046.24001			
1.495	-2.012	337.21190	1229.62579	527.80463	386.58500	100.80000	2.49084	346.04980	947.63990	1.18837	2046.27499			
1.496	-3.012	336.87790	1229.54350	527.73239	386.47390	100.80000	2.49094	346.38990	947.64990	1.18820	2046.27499			
1.495	-4.013	337.21120	1229.76947	527.86218	386.63600	100.90000	2.48868	346.07980	947.64990	1.18928	2046.27499			
1.495	-5.009	336.91140	1228.63087	527.37464	386.63870	100.90000	2.49360	346.53980	947.71000	1.18678	2046.27499			
1.496	-6.011	337.35210	1231.21167	528.52565	386.55080	100.90000	2.49417	346.73000	947.75000	1.19288	2046.27499			
1.496	-7.002	337.53780	1231.34511	528.84881	386.61450	100.90000	2.49570	347.00000	947.75000	1.19219	2046.24001			
1.496	-8.009	337.79980	1232.08177	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000			

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM015) ( 04 OCT 91 )

## PARAMETRIC DATA

$$\text{GRADIENT INTERVAL} = -5.00 / 5.00$$



AA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OEE

1 OCT 91

卷之三

卷之三

RUN NO.: 12277 O RN/L = 2.50 GRADIENT INTERVAL = -5 00/-5 00/

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 872  
(VCMO17) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1223/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000	PREF	SH10+3	PATM
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
.900	-3.988	753.06350	1273.03999	426.56180	482.14090	100.50000	2.49575	763.06980	982.61990	1.82490	2046.48500		
.900	-2.989	752.84940	1273.22000	426.81270	482.08230	100.50000	2.49652	762.85990	982.70000	1.79690	2046.48500		
.900	-1.985	753.05490	1272.92999	426.49120	482.15110	100.50000	2.49546	763.05980	982.75980	1.77903	2046.45000		
.899	- .993	752.74950	1273.16000	426.83110	482.07060	100.50000	2.49648	762.76000	982.85990	1.76511	2046.45000		
.900	.017	752.76290	1272.91000	426.65140	481.92800	100.30000	2.49694	762.76980	982.91990	1.76546	2046.45000		
.900	1.006	752.72460	1272.78000	426.58500	481.93480	100.30000	2.49663	762.73000	982.98000	1.77016	2046.48500		
.900	2.005	752.61650	1272.57001	426.50460	481.93800	100.30000	2.49620	762.61990	983.02980	1.77046	2046.45000		
.900	2.998	752.66990	1272.35001	426.32180	481.97140	100.30000	2.49553	762.66990	983.11990	1.77530	2046.45000		
.900	3.995	752.40920	1272.28000	426.42900	481.93140	100.30000	2.49567	762.40990	983.17990	1.77994	2046.45000		
GRADIENT		.06776	-.11272	-.03712	-.02896	-.03342	-.00003	-.06879	.06948	-.00429	-.00351		
RUN NO.		1168/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000	PREF	SH10+3	PATM
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.250	-3.985	462.64380	1197.84000	505.74320	426.24150	99.70000	2.50153	472.76980	1059.06000	933660	2054.98999		
1.250	-2.970	462.61330	1197.92000	505.79030	426.22530	99.70000	2.50169	472.74000	1059.13000	91147	2054.95499		
1.250	-1.980	462.50170	1198.21001	505.961170	426.16650	99.70000	2.50227	472.62990	1059.20000	91125	2054.98999		
1.250	- .992	462.68330	1197.89999	505.76490	426.24580	99.70000	2.50166	472.80980	1059.24001	90901	2054.98999		
1.250	.016	462.53340	1197.95000	505.82300	426.20120	99.70000	2.50175	472.65990	1059.28999	90897	2054.95499		
1.250	1.014	462.86300	1197.89000	505.72050	426.29390	99.70000	2.50166	472.99000	1059.36000	91149	2054.98999		
1.250	2.004	462.53270	1198.06000	505.87890	426.18990	99.70000	2.50197	472.65990	1059.38000	90151	2054.98999		
1.250	3.010	462.69340	1197.89999	505.76270	426.24830	99.70000	2.50166	472.81980	1059.41000	89187	2054.95499		
1.250	3.995	462.66430	1197.74001	505.68800	426.25710	99.70000	2.50133	472.78980	1059.44000	89199	2054.95499		
GRADIENT		.00943	-.01284	-.00857	.00378	-.00000	-.00002	-.00035	.04747	-.00425	-.00235		
RUN NO.		1187/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000	PREF	SH10+3	PATM
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.400	-3.988	382.36080	1216.14000	524.32060	402.69650	100.80000	2.49648	392.07980	902.49000	1.18061	2051.80499		
1.400	-2.991	382.09470	1215.98000	524.25590	402.55980	100.70000	2.49658	391.80980	902.52980	1.19020	2051.76999		
1.400	-1.984	382.03640	1215.83000	524.19140	402.55640	100.70000	2.49627	391.75000	902.57980	1.19351	2051.76999		
1.400	- .986	382.23120	1216.31000	524.39750	402.56980	100.70000	2.49729	391.95000	902.62990	1.19938	2051.76999		
1.400	.008	382.04520	1216.02000	524.27440	402.54100	100.70000	2.49662	391.75980	902.66990	1.20604	2051.76999		
1.400	1.004	382.16550	1215.74001	524.14970	402.53200	100.60000	2.49679	391.87990	902.70000	1.20952	2051.76999		
1.400	2.000	382.31230	1216.03000	524.27340	402.54880	100.60000	2.49743	392.02980	902.75000	1.20603	2051.76999		
1.400	3.006	382.15330	1216.12000	524.31590	402.49240	100.60000	2.49747	391.86990	902.77980	1.20594	2051.73499		
1.400	3.996	382.30150	1216.16000	524.33060	402.53320	100.60000	2.49766	392.01980	902.83980	1.20590	2051.73499		
GRADIENT		.00706	.00228	-.01518	-.02338	-.00015	.00715	.04274	.00307	-.00643			

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM017) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 90.000		PATM	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.450	-3.993	358.94360	1225.92999	528.15190	394.79660	101.10000	2.49259	368.41990	976.12990	1.31203	2052.64499
-2.997	359.14140	1225.82001	528.11620	394.86890	101.10000	2.49258	368.61990	976.13990	1.30870	2052.67999	
1.449	-1.996	358.80490	1226.07001	528.20290	394.74020	101.10000	2.49270	368.27980	976.15990	1.30500	2052.67999
1.450	-1.003	358.98290	1225.96001	528.16650	394.80620	101.10000	2.49268	368.46000	976.16990	1.29826	2052.67999
1.450	.005	358.76590	1226.00000	528.17190	394.73440	101.10000	2.49254	368.24000	976.20000	1.29822	2052.67999
1.450	1.004	358.93430	1225.82001	528.10570	394.80400	101.10000	2.49239	368.40990	976.24000	1.30870	2052.71500
1.450	1.990	358.80620	1225.81000	528.09500	394.76440	101.10000	2.49225	368.27980	976.24000	1.30527	2052.67999
1.450	2.986	359.11060	1226.03999	528.17910	394.83910	101.10000	2.49294	368.58980	976.25000	1.29818	2052.67999
1.450	3.986	358.91360	1226.00000	528.17940	394.78080	101.10000	2.49268	368.38980	976.28980	1.29481	2052.67999
GRADIENT	- .00436	.00467	.00172	-.00179	.00000	-.00000	.00000	-.00000	-.00000	-.00149	.00293
RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 90.000		PATM	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.473	-3.982	347.25540	1226.30675	527.51468	389.99240	100.00000	2.49361	356.56980	938.98000	1.05532	2047.39500
-2.990	347.34280	1226.53935	527.61691	389.99510	100.00000	2.49419	356.65990	939.14990	1.05790	2047.39500	
1.473	-1.990	348.28200	1229.75639	529.00340	390.00460	100.00000	2.50075	357.62990	939.24000	1.05796	2047.39500
1.473	-.986	347.92530	1228.21844	528.34850	390.03420	100.00000	2.49762	357.25980	939.33980	1.05650	2047.39500
1.473	.017	347.44970	1226.70955	527.69512	390.01050	100.00000	2.49467	356.76980	939.40990	1.06055	2047.36000
1.473	1.010	347.70140	1227.81825	528.16686	390.00590	100.00000	2.49656	357.02980	939.45000	1.05127	2047.39500
1.473	2.000	348.37720	1230.51646	529.31198	389.98000	100.00000	2.50191	357.73000	939.51980	1.04898	2047.39500
1.473	3.001	348.14940	1228.89316	528.64225	390.06150	100.00000	2.49871	357.49000	939.56980	1.04763	2047.39500
1.473	3.991	347.90330	1228.83807	528.59818	389.98290	100.00000	2.49845	357.24000	939.62990	1.04763	2047.39500
GRADIENT	.08313	.30561	.1324	.00141	-.00000	-.00000	.00057	.08585	.07569	-.00141	-.00001
RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 90.000		PATM	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.496	-3.987	337.87790	1232.47581	529.01485	386.63210	100.90000	2.49594	347.07980	947.80980	1.17331	2046.31000
-2.990	338.22610	1233.82538	529.59108	386.63090	100.90000	2.49853	347.43990	947.82980	1.16898	2046.31000	
1.496	-1.985	338.08110	1233.30074	529.36575	386.63430	100.90000	2.49740	347.28980	947.84990	1.16642	2046.31000
1.496	-.989	337.48950	1231.38039	528.53409	386.59590	100.90000	2.49376	346.67990	947.82980	1.17739	2046.27499
1.496	.016	337.39430	1230.54224	528.18994	386.55810	100.80000	2.49306	346.57980	947.82980	1.18746	2046.31000
1.496	1.017	338.04100	1233.16396	529.30704	386.53270	100.80000	2.49832	347.25000	947.83980	1.18805	2046.31000
1.496	2.000	338.04150	1233.00951	529.24591	386.47800	100.70000	2.49865	347.25000	947.84990	1.18820	2046.31000
1.496	2.995	337.80960	1232.12296	528.86678	386.41160	100.60000	2.49748	347.00980	947.85990	1.18905	2046.31000
1.496	4.001	338.21440	1233.87605	529.60957	386.31490	100.50000	2.50161	347.42990	947.87990	1.19047	2046.31000
GRADIENT	.00944	.02810	.01226	-.03844	-.05007	-.00044	.00044	.000997	.000306	.00058	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 874

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM017) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.520	-3.987	328.20480	1240.222391	530.718389	382.36940	100.50000	2.50179	337.25980	875.97000	1.13430	2047.60500
1.520	-2.985	327.66360	1238.18060	529.84420	382.366690	100.50000	2.49771	336.70000	875.98000	1.13615	2047.60500
1.520	-1.990	327.17800	1237.09509	529.34875	382.30470	100.50000	2.49519	336.20000	876.01000	1.13117	2047.57001
1.520	- .992	327.58450	1238.17929	529.83138	382.32400	100.50000	2.49793	336.61990	876.01980	1.14811	2047.60500
1.520	.015	327.88450	1239.39900	529.34944	382.33720	100.50000	2.49996	336.92990	876.04980	1.13206	2047.57001
1.520	1.004	327.69310	1238.23770	529.87111	382.37600	100.50000	2.49777	336.73000	876.09990	1.13313	2047.60500
1.520	2.006	327.60690	1237.71182	529.65369	382.39360	100.50000	2.49677	336.63990	876.10990	1.13361	2047.57001
1.520	3.001	327.26610	1236.88422	529.28086	382.33080	100.50000	2.49537	336.28980	876.12990	1.14930	2047.57001
1.520	3.996	327.24020	1235.94389	528.91355	382.40280	100.50000	2.49380	336.25980	876.12990	1.15321	2047.57001
GRADIENT	-.06817	-.32908	-.13739	.00426	-.00000	-.00060	-.07078	.02286	.00175	-.00410	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.544	-3.987	318.12040	1244.46027	530.59740	378.08500	100.10000	2.50271	326.99000	900.50000	1.23075	2045.82001
1.544	-2.979	317.72360	1243.17459	530.03596	378.05930	100.10000	2.5007	326.57980	900.53980	1.23200	2045.82001
1.544	-1.989	317.48220	1242.18021	529.61465	378.05830	100.10000	2.49820	326.32980	900.62990	1.23618	2045.78500
1.544	-.991	317.44510	1241.54124	529.36597	378.09740	100.10000	2.49716	326.28980	900.64990	1.24004	2045.82001
1.544	.017	317.54790	1242.70139	529.82309	378.00900	100.10000	2.49965	326.39990	900.68990	1.25505	2045.82001
1.544	1.010	317.98540	1243.47298	530.19740	378.08540	100.10000	2.50163	326.84990	900.73000	1.26083	2045.82001
1.544	2.000	317.81050	1243.23175	530.07371	377.99560	100.00000	2.50129	326.66990	900.76980	1.24805	2045.78500
1.544	3.001	317.09790	1239.92827	528.68990	378.03760	100.00000	2.49488	325.92990	900.78980	1.25134	2045.82001
1.544	3.995	317.18380	1240.09323	528.76803	378.01320	100.00000	2.49602	326.01980	900.81980	1.28070	2045.82001
GRADIENT	-.07396	-.38709	-.16047	-.00819	-.01503	-.00053	-.07670	.03992	.00505	-.00000	

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO 18) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1272/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00		ALPHA =	.000	PHI =	90.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
.900	-3.989	753.15620	1273.62000	426.90500	481.40650	99.70000	2.50183	763.16990	979.31980	.76436	2047.00999	
.900	-2.989	753.41380	1273.94000	426.97170	481.41920	99.70000	2.50236	763.42990	979.39990	.77897	2047.00999	
.900	-1.985	752.91210	1273.78000	427.16040	481.34470	99.70000	2.50258	762.92990	979.46000	.78981	2047.00999	
.900	-.993	753.15310	1273.84000	427.05790	481.38230	99.70000	2.50243	763.16990	979.52980	.80943	2047.00999	
.900	.016	753.17720	1273.56000	426.85160	481.41700	99.70000	2.50163	763.18990	979.57980	.81183	2047.00999	
.900	1.005	753.40090	1273.39999	426.60820	481.47510	99.70000	2.50090	763.40990	979.64990	.79438	2047.00999	
.899	2.005	752.92580	1273.50999	426.96660	481.37650	99.70000	2.50183	762.93990	979.67990	.79214	2046.97501	
.900	2.998	753.09990	1273.34000	426.74630	481.42650	99.70000	2.50113	763.10990	979.74000	.79008	2047.00999	
.900	4.000	752.79130	1273.05000	426.73070	481.40140	99.70000	2.50074	762.79980	979.77980	.79243	2047.00999	
GRADIENT		-.03552	-.08448	-.03690	-.0263	.00000	-.00018	-.03642	.05644	.00226	-.00116	

RUN NO.		1266/ 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/	5.00		ALPHA =	.000	PHI =	5.00
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
1.250	-3.985	462.73190	1198.10001	505.85570	425.78100	99.09999	2.50562	472.85990	904.68990	.91133	2045.67999	
1.250	-2.987	462.49440	1197.84000	505.77590	425.74490	99.09999	2.50506	472.61990	904.66990	.91401	2045.71500	
1.250	-1.986	462.56350	1197.92999	505.80640	425.75390	99.09999	2.50525	472.68990	904.68990	.90899	2045.67999	
1.250	-.981	462.62110	1198.25000	505.95580	425.73660	99.09999	2.50591	472.75000	904.70000	.91122	2045.67999	
1.250	.015	462.75320	1197.89000	505.74440	425.80790	99.09999	2.50519	472.87990	904.71000	.91397	2045.67999	
1.250	1.008	462.81960	1198.41000	505.99370	425.77270	99.09999	2.50626	472.95000	904.72000	.91109	2045.71500	
1.250	2.003	462.42700	1197.46001	505.59810	425.76590	99.09999	2.50427	472.54980	904.73000	.90688	2045.71500	
1.250	2.999	462.70120	1198.22000	505.82310	425.76070	99.09999	2.50586	472.82980	904.73000	.92119	2045.71500	
1.250	4.000	462.63180	1198.14000	505.89770	425.75070	99.09999	2.50569	472.75980	904.74000	.90883	2045.71500	
GRADIENT		.00246	.00871	.00387	-.00023	.00000	.00002	.00250	.00804	.00012	.00409	

RUN NO.		1261/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00		ALPHA =	.000	PHI =	5.00
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
1.400	-3.988	381.71410	1215.17999	523.91360	402.01810	100.00000	2.49900	391.41990	860.38990	.99844	2045.29500	
1.399	-2.980	382.00320	1214.78000	523.73270	402.14280	100.00000	2.49848	391.71000	860.43990	1.00146	2045.29500	
1.400	-.984	381.63720	1214.78999	523.74440	402.03200	100.00000	2.49823	391.33980	860.51000	.99876	2045.29500	
1.400	1.986	381.82350	1215.07001	523.86760	402.06150	100.00000	2.49888	391.52980	860.53980	.98252	2045.25999	
1.400	0.19	381.57710	1214.92000	523.80	402.00150	100.00000	2.49842	391.27980	860.56980	.97999	2045.29500	
1.400	1.008	382.00070	1215.24001	523.93410	402.09860	100.00000	2.49932	391.71000	860.57980	.97974	2045.29500	
1.400	2.000	381.79660	1214.60001	523.65820	402.09790	100.00000	2.49800	391.50000	860.59990	.98290	2045.25999	
1.400	3.001	381.88990	1215.53999	524.06760	402.03710	100.00000	2.49978	391.59990	860.62990	.98745	2045.25999	
1.400	4.001	381.73850	1214.42999	523.58520	402.09640	100.00000	2.49765	391.43990	860.63990	.98304	2045.25999	
GRADIENT		.00422	-.01557	-.00687	-.00275	.00000	-.00003	.00416	.02991	-.00231	-.00468	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 876

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO18) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	ALPHA =	PHI =	PREF	SH10+3	PATM
1.449	-3.987	359.25660	1226.39000	528.35940	394.21900	100.20000	2.49904	368.74000	934.11990	1.55410	2046.73000	
1.450	-2.980	359.06130	1226.06000	528.21190	394.25830	100.30000	2.49768	368.53980	934.12990	1.55856	2046.76500	
1.450	-1.985	358.95290	1226.05000	528.20210	394.22530	100.30000	2.49756	368.42990	934.15990	1.55857	2046.76500	
1.450	- .992	358.99460	1225.61000	528.02150	394.34940	100.40000	2.49623	368.47000	934.17990	1.55509	2046.76500	
1.450	.016	359.16750	1226.50000	528.40060	394.32180	100.40000	2.49796	368.64990	934.21000	1.55396	2046.76500	
1.450	1.009	358.71850	1225.59000	527.99900	394.26440	100.40000	2.49594	368.18990	934.24000	1.54707	2046.76500	
1.450	2.006	358.81350	1226.34000	528.31590	394.29570	100.50000	2.49675	368.28980	934.25000	1.54212	2046.76500	
1.450	2.996	358.77780	1225.61000	528.01030	394.35160	100.50000	2.49543	368.25000	934.28980	1.53904	2046.73000	
1.450	3.997	359.05100	1226.13000	528.24050	394.38960	100.50000	2.49611	368.52980	934.32980	1.53440	2046.73000	
GRADIENT	-.03723	-.03052	-.01460	.01701	.03676	-.00031	-.03795	.02606	-.00298	-.00175	.00157	.00000

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO19) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	ALPHA =	PHI =	PREF	SH10+3	PATM
.900	4.025	752.70120	1273.02000	426.76390	481.73240	100.10000	2.49847	762.71000	983.43990	1.74285	2046.48500	
.900	3.016	752.93290	1273.02000	426.62570	481.68870	100.00000	2.49874	762.93990	983.50980	1.73395	2046.48500	
.900	2.005	752.79880	1273.24001	426.85670	481.81250	100.20000	2.49837	762.80980	983.56980	1.72921	2046.48500	
.900	1.000	752.83010	1273.16000	426.78320	481.56880	99.89999	2.49984	762.83980	983.63990	1.72489	2046.48500	
.900	-.016	752.96190	1273.09000	426.65650	481.77270	100.10000	2.49832	762.97000	983.68990	1.72941	2046.48500	
.900	-1.012	752.94290	1273.02000	426.61990	481.77660	100.10000	2.49815	762.95000	983.74000	1.71626	2046.48500	
.900	-2.013	752.78030	1273.12000	426.78540	481.56400	99.89999	2.49979	762.78980	983.80980	1.72937	2046.48500	
.900	-3.023	752.99240	1273.09000	426.63840	481.60600	99.89999	2.49943	763.00000	983.86990	1.72941	2046.48500	
.900	-4.039	752.90840	1273.31000	426.83940	481.73900	100.10000	2.49899	762.91990	983.92990	1.72469	2046.48500	
GRADIENT	-.01795	-.01641	-.00057	.00842	.01154	-.00009	-.01807	-.00298	-.00175	.00157	.00000	.00000

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO19) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.		RN/L =		2.50		GRADIENT INTERVAL =		-5.00/ 5.00		ALPHA =		.000		PHI =		-90.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM						
1.250	4.023	462.52440	1197.82001	505.75900	426.21190	99.70000	2.50148	472.64990	105.9.55000	.89680	2054.98999						
1.250	3.010	462.59230	1198.11000	505.89140	426.20040	99.70000	2.50208	472.72000	105.9.57001	.89658	2054.95499						
1.250	2.001	462.61180	1198.13000	505.89700	426.12740	99.59999	2.50236	472.74000	105.9.58000	.89413	2054.98999						
1.250	.995	462.69310	1197.95000	505.78810	426.16700	99.59999	2.50205	472.81980	105.9.59000	.91890	2054.98999						
1.250	-.013	462.51440	1197.81000	505.75610	426.13430	99.59999	2.50205	472.63990	105.9.61000	.89925	2055.02499						
1.250	-1.009	462.65310	1197.94000	505.79170	426.15750	99.59999	2.50233	472.77980	105.9.63000	.89671	2054.98999						
1.250	-2.027	462.61330	1197.92999	505.79540	426.22440	99.70000	2.50172	472.74000	105.9.64999	.89428	2054.98999						
1.250	-3.024	462.63480	1197.69000	505.66920	426.33060	99.80000	2.50064	472.75980	105.9.66000	.90670	2055.02499						
1.250	-4.043	462.39330	1198.03999	505.89920	426.30760	99.89999	2.50073	472.51980	105.9.69000	.91138	2055.02499						
GRADIENT		.00720	.01302	.00502	-.01584	-.02152	.00015	.00732	-.01672	-.00111	-.00579						

RUN NO. 1188/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.		RN/L =		2.50		GRADIENT INTERVAL =		-5.00/ 5.00		ALPHA =		.000		PHI =		-0.00732	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM						
1.400	4.025	382.11450	1215.99001	524.25980	402.56490	100.70000	2.49662	391.82980	902.99000	1.19969	2051.70001						
1.400	3.024	382.18650	1215.56000	524.07030	402.62720	100.70000	2.49589	391.89990	903.04980	1.20330	2051.70001						
1.399	2.004	382.47920	1216.20000	524.34420	402.65480	100.70000	2.49727	392.20000	903.08980	1.20586	2051.70001						
1.399	.998	382.30490	1215.59000	524.08110	402.65990	100.70000	2.49603	392.01980	903.12990	1.20009	2051.70001						
1.400	-.019	382.32100	1216.17999	524.33890	402.60910	100.70000	2.49711	392.03980	903.15990	1.20588	2051.70001						
1.400	-1.004	382.29420	1215.75000	524.15140	402.64160	100.70000	2.49631	392.00980	903.20000	1.20951	2051.70001						
1.400	-2.024	382.20360	1216.00000	524.26250	402.59690	100.70000	2.49670	391.91990	903.24000	1.21890	2051.70001						
1.400	-3.015	382.26220	1216.12000	524.31370	402.59690	100.70000	2.49696	391.98000	903.27980	1.21878	2051.70001						
1.400	-4.035	382.13530	1215.84000	524.19380	402.58520	100.70000	2.49636	391.84990	903.31980	1.21262	2051.70001						
GRADIENT		.00413	-.01400	.00622	.00259	.00000	-.00002	.00049	-.03939	-.00221	.00000						

RUN NO. 1202/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.		RN/L =		2.49		GRADIENT INTERVAL =		-5.00/ 5.00		ALPHA =		.000		PHI =		-0.02785	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM						
1.450	4.030	358.91260	1226.24001	528.27930	394.75830	101.10000	2.49310	368.38990	976.36990	1.31861	2052.67999						
1.450	3.019	359.11960	1226.23000	528.28560	394.82420	101.10000	2.49328	368.59990	976.35990	1.31111	2052.71500						
1.450	2.011	358.93480	1225.72000	528.06420	394.81320	101.10000	2.49221	368.40990	976.37990	1.3081	2052.67999						
1.450	1.005	358.78540	1226.00999	528.17700	394.73950	101.10000	2.49258	368.25980	976.37990	1.30163	2052.71500						
1.451	-.003	358.58840	1226.00000	528.16280	394.67850	101.10000	2.49237	368.05980	976.40990	1.29822	2052.71500						
1.450	-1.001	358.89260	1226.28000	528.29490	394.74830	101.10000	2.49316	368.36990	976.42990	1.30477	2052.71500						
1.450	-2.009	359.03150	1226.06000	528.21040	394.81230	101.10000	2.49290	368.50980	976.46000	1.30501	2052.71500						
1.450	-3.011	358.71680	1225.94000	528.14450	394.79490	101.20000	2.49180	368.18990	976.49000	1.31202	2052.71500						
1.450	-4.025	358.62750	1225.77000	528.07450	394.81400	101.20000	2.49151	368.20000	976.51980	1.31569	2052.67999						
GRADIENT		.02733	.02988	.01381	-.00235	-.01159	.00015	.02785	-.01988	.00026	-.00115						

RUN NO.		RN/L =		2.49		GRADIENT INTERVAL =		-5.00/ 5.00		ALPHA =		.000		PHI =		-.01988	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM						
1.450	4.030	358.91260	1226.24001	528.27930	394.75830	101.10000	2.49328	368.38990	976.36990	1.31861	2052.67999						
1.450	3.019	359.11960	1226.23000	528.28560	394.82420	101.10000	2.49221	368.40990	976.35990	1.31111	2052.71500						
1.450	2.011	358.93480	1225.72000	528.06420	394.81320	101.10000	2.49258	368.25980	976.37990	1.3081	2052.67999						
1.450	1.005	358.78540	1226.00999	528.17700	394.73950	101.10000	2.49237	368.05980	976.40990	1.29822	2052.71500						
1.451	-.003	358.58840	1226.00000	528.16280	394.67850	101.10000	2.49316	368.36990	976.42990	1.30477	2052.71500						
1.450	-1.001	358.89260	1226.28000	528.29490	394.74830	101.10000	2.49290	368.50980	976.46000	1.30501	2052.71500						
1.450	-2.009	359.03150	1226.06000	528.21040	394.81230	101.10000	2.49180	368.18990	976.49000	1.31202	2052.71500						
1.450	-3.011	358.71680	1225.94000	528.14450	394.79490	101.20000	2.49151	368.20000	976.51980	1.31569	2052.67999						
1.450	-4.025	358.62750	1225.77000	528.07450	394.81400	101.20000	2.49151	368.20000	976.51980	1.31569	2052.67999						
GRADIENT		.02733	.02988	.01381	-.00235	-.01159	.00015	.02785	-.01988	.00026	-.00115						

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

PAGE 878

(VCMO 19) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1281/0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.473	4.024	348.03640	1229.21405	528.76035	389.93680	100.00000	2.50029	357.37990	939.80980	1.07805	2047.42999
1.473	3.007	348.41720	1230.13626	529.16830	390.00460	100.00000	2.50172	357.76980	939.83980	1.06322	2047.42999
1.473	2.004	348.41850	1229.93294	529.08596	390.02930	100.00000	2.50126	357.76980	939.86990	1.06062	2047.39500
1.473	.993	348.08810	1229.35019	528.82211	390.00220	100.00000	2.49941	357.42990	939.89990	1.04446	2047.39500
1.473	-.010	347.78690	1228.58417	528.48621	389.97730	100.00000	2.49772	357.11990	939.90990	1.04233	2047.42999
1.473	-1.012	347.66240	1227.92455	528.20776	390.07200	100.10000	2.49575	356.99000	939.93990	1.04015	2047.39500
1.474	-2.014	347.39890	1227.68738	528.08946	390.09890	100.20000	2.49408	356.72000	939.95000	1.02668	2047.39500
1.473	-3.021	347.39380	1226.40582	527.56825	390.18970	100.20000	2.49231	356.71000	939.98000	1.04420	2047.42999
1.474	-4.040	346.99930	1226.48361	527.56467	390.04220	100.20000	2.49229	356.30980	940.00980	1.04680	2047.42999
GRADIENT	.16033	.46401	.20180	.20180	-.01962	-.03145	.00130	.16556	-.02354	.00421	-.00001

RUN NO. 1243/0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.496	4.023	336.65600	1228.47318	527.28117	386.21190	100.40000	2.49132	345.81980	947.86990	1.19562	2046.31000
1.496	3.012	337.46850	1231.45026	528.55925	386.14580	100.30000	2.49788	346.65590	947.86990	1.19277	2046.31000
1.495	1.999	337.59810	1231.16341	528.46124	386.22560	100.30000	2.49731	346.78980	947.87990	1.18687	2046.31000
1.496	.996	337.48830	1231.63132	528.63313	386.15870	100.30000	2.49778	346.67990	947.86990	1.17714	2046.31000
1.496	-.027	337.96440	1232.93365	529.20644	386.13650	100.20000	2.50100	347.16990	947.87990	1.17287	2046.31000
1.496	-1.013	338.13770	1233.90837	529.61364	386.12380	100.20000	2.50253	347.34990	947.86990	1.15976	2046.31000
1.496	-2.024	337.69300	1232.34100	528.93980	386.12520	100.20000	2.49921	346.88990	947.87990	1.15516	2046.31000
1.496	-3.020	337.10600	1229.57391	527.77213	386.11130	100.10000	2.49442	346.27980	947.85990	1.15775	2046.31000
1.496	-4.039	337.16020	1230.62445	528.19452	386.03270	100.10000	2.49632	346.33980	947.86990	1.15674	2046.31000
GRADIENT	-.02952	-.02952	-.12681	-.05383	.01749	.03477	-.00030	-.03021	.00050	.00565	.00001

RUN NO. 1289/0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.520	4.024	327.90280	1239.64449	530.44752	382.38180	100.60000	2.49995	336.95000	873.06980	1.13779	2047.60500
1.520	3.023	328.25240	1240.53609	530.84694	382.42210	100.60000	2.50185	337.30980	873.22000	1.13699	2047.57001
1.520	1.988	327.95390	1239.14192	530.26166	382.44090	100.60000	2.49922	337.00000	873.37990	1.14125	2047.57001
1.520	.994	327.28440	1237.20227	529.40618	382.38060	100.60000	2.49526	336.30980	873.48000	1.14600	2047.57001
1.520	-.015	327.21800	1236.64008	529.17893	382.40840	100.60000	2.49423	336.24000	873.57980	1.14652	2047.57001
1.520	-1.006	328.31050	1240.53372	530.85445	382.42680	100.60000	2.50221	337.36990	873.65990	1.14897	2047.57001
1.520	-2.014	327.69780	1239.36908	530.30932	382.33180	100.60000	2.49934	336.74000	873.75000	1.14100	2047.57001
1.519	-3.016	327.40550	1236.41832	529.12243	382.49730	100.60000	2.49396	336.42990	873.79980	1.14376	2047.53500
1.520	-4.040	327.11010	1236.70808	529.18875	382.36890	100.60000	2.49416	336.12990	873.84990	1.14344	2047.53500
GRADIENT	.08634	.08634	.33731	.14389	-.00002	.00000	.00066	.08936	-.09575	-.00075	.00638

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 879

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO19) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup>	PATM
1.543	4.023	317.98610	1243.42867	530.18109	378.11160	100.10000	2.50114	326.84990	900.88990	1.24463	2045.82001
1.544	3.016	317.26000	1241.29514	529.23800	377.98660	100.00000	2.49713	326.09990	900.88990	1.24027	2045.78500
1.543	2.004	317.03010	1239.77226	528.63081	378.01540	99.89999	2.49455	325.91990	900.89990	1.22577	2045.78500
1.543	.993	317.16820	1240.10873	528.77295	378.17380	100.10000	2.49353	326.00000	900.89990	1.20647	2045.82001
1.544	-.016	317.06840	1240.78856	529.01238	377.95190	99.89999	2.49559	325.89990	900.89990	1.19952	2045.78500
1.544	-1.012	317.19290	1241.51582	529.30952	378.06670	100.10000	2.49576	326.02980	900.92990	1.19882	2045.78500
1.544	-2.025	317.42430	1242.39494	529.68616	378.05740	100.10000	2.49775	326.26980	900.91990	1.20738	2045.78500
1.544	-3.021	317.97510	1244.20837	530.47539	378.07350	100.10000	2.50178	326.83980	900.93990	1.21826	2045.78500
1.544	-4.040	318.29420	1245.16359	530.89613	377.88550	99.80000	2.50582	327.16990	900.97000	1.22688	2045.75000
GRADIENT		-.06725	-.36903	-.15235	.01105	.00831	-.00068	-.06987	-.00894	.00301	.00521

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO20) (04 OCT 91)

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup>	PATM
.900	4.025	753.08840	1273.42000	426.80810	481.41580	99.70000	2.50137	763.09990	979.95000	.80310	2047.00999
.900	3.016	753.02830	1273.39999	426.83010	481.40700	99.70000	2.50139	763.03980	980.00000	.80971	2047.00999
.900	1.999	753.07810	1273.44000	426.82790	481.41190	99.70000	2.50144	763.08980	980.01980	.82305	2047.04500
.900	.995	752.81520	1273.50999	427.03250	481.35620	99.70000	2.50197	762.82980	980.04980	.80964	2047.00999
.900	-.022	753.13090	1273.25999	426.67290	481.44090	99.70000	2.50087	763.13990	980.09990	.80320	2047.00999
.900	-1.012	752.86990	1273.17999	426.77290	481.31570	99.59999	2.50157	762.87990	980.11990	.79887	2047.00999
.900	-2.018	752.94460	1272.89999	426.53610	481.53170	99.80000	2.49955	762.95000	980.13990	.80123	2047.00999
.900	-3.018	752.78200	1273.00000	426.70190	481.49120	99.80000	2.50004	762.78980	980.15990	.80117	2047.00999
.899	-4.039	753.01760	1272.71001	426.36210	481.56570	99.80000	2.49894	763.01980	980.16990	.79917	2047.00999
GRADIENT		.02038	.09020	.04988	-.01741	-.01323	.00030	.02146	-.02765	.00158	.00115

## PARAMETRIC DATA

RUN NO. 1267/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.249	4.020	462.69580	1197.52000	505.56930	425.83030	99.09999	2.50443	472.81980	904.77980	.90683	2045.71500
1.250	3.018	462.51120	1198.28000	505.99510	425.70480	99.09999	2.50596	472.63990	904.77980	.90625	2045.75000
1.250	1.999	462.41260	1198.11000	505.93040	425.77220	99.20000	2.50501	472.53980	904.78980	.90638	2045.75000
1.250	.993	462.43730	1197.42999	505.58060	425.92410	99.30000	2.50303	472.55980	904.79980	.90444	2045.75000
1.250	-.015	462.94750	1198.63000	506.07690	426.01250	99.39999	2.50496	473.07980	904.82980	.90108	2045.75000
1.249	-1.016	462.57740	1197.35001	505.50930	426.04520	99.39999	2.50229	472.70000	904.84990	.90204	2045.78500
1.250	-2.017	462.85890	1198.47000	506.01510	426.08150	99.50000	2.50403	472.99000	904.85990	.89875	2045.78500
1.250	-3.025	462.43550	1197.66000	505.69750	426.05250	99.50000	2.50232	472.55980	904.88990	.90181	2045.78500
1.250	-4.044	462.86040	1198.27000	505.91380	426.17850	99.59999	2.50303	472.99000	904.88990	.90135	2045.82001
GRADIENT	-.02425	-.02947	-.00966	-.05256	-.06455	.00032	-.02453	-.01590	.00088	-.01042	

RUN NO. 1262/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.400	4.019	381.92260	1215.03000	523.84370	402.09500	100.00000	2.49888	391.62990	860.72000	.99053	2045.25999
1.400	3.006	381.77510	1214.88000	523.78120	401.99290	99.89999	2.49909	391.48000	860.73000	1.02115	2045.25999
1.400	1.998	381.87010	1215.52000	524.05910	402.03300	100.00000	2.49973	391.57980	860.75000	1.01713	2045.25999
1.400	.997	381.75490	1214.95000	523.81200	401.98020	99.89999	2.49920	391.46000	860.75000	1.01761	2045.25999
1.400	-.020	382.09940	1215.24001	523.93210	402.05640	99.89999	2.49999	391.80980	860.76000	1.01736	2045.29500
1.400	-1.014	381.81520	1214.83000	523.75850	402.15330	100.10000	2.49784	391.51980	860.76980	.98802	2045.29500
1.400	-2.020	381.81320	1215.13000	523.88960	401.98070	99.89999	2.49957	391.51980	860.78980	.97982	2045.29500
1.400	-3.021	381.70800	1214.56000	523.64260	402.14670	100.10000	2.49727	391.40990	860.78980	.98558	2045.29500
1.400	-4.041	382.00170	1215.03999	523.84640	402.18970	100.10000	2.49836	391.71000	860.79980	.99587	2045.29500
GRADIENT	-.00109	-.03003	-.01316	-.01655	-.01505	.00015	-.01655	-.00090	-.00091	.00323	-.00580

RUN NO. 1231/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.450	4.014	358.93410	1225.89000	528.13480	393.81180	99.70000	2.50084	368.40990	931.21000	1.37913	2046.55499
1.450	3.013	359.01220	1226.00000	528.18460	393.89650	99.80000	2.50051	368.49000	931.29980	1.37540	2046.59000
1.450	1.994	358.82670	1225.69000	528.04610	393.86670	99.80000	2.49979	368.29980	931.37990	1.37936	2046.59000
1.450	.999	359.00070	1226.32001	528.31710	393.86350	99.80000	2.50106	368.48000	931.43990	1.39315	2046.59000
1.450	-.025	358.49070	1225.84000	528.09110	393.811790	99.89999	2.49914	367.96000	931.50980	1.39735	2046.59000
1.450	-1.012	359.06050	1226.20000	528.27030	393.96360	99.89999	2.50031	368.53980	931.56980	1.38602	2046.55499
1.450	-2.015	358.50120	1225.71001	528.03780	393.83330	99.89999	2.49892	367.97000	931.61990	1.38295	2046.59000
1.450	-3.027	358.92160	1226.36000	528.32960	393.76460	99.70000	2.50166	368.39990	931.64990	1.37140	2046.55499
1.450	-4.057	358.88530	1225.75999	528.07840	394.01950	100.00000	2.49878	368.35990	931.75000	1.36848	2046.55499
GRADIENT	.01756	-.00777	-.00234	-.000778	-.001990	.00012	-.01990	-.00091	-.00090	.00232	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 881

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCMO21) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	.012	433.63130	1201.08000	512.79200	417.65580	99.09999	2.450504	443.65990	.95194 2055.09500
1.300	-.013	433.54540	1200.61000	512.57810	417.52930	98.89999	2.50527	443.56980	.96528 2055.09500

	RUN NO.	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.350	.017	406.55150	1206.67999	518.74630	410.43950	100.40000	2.49656	416.43990	1.11032 2054.98999
1.350	-.028	406.92530	1207.12000	518.91530	410.50440	100.40000	2.49759	416.81980	1.11884 2054.98999

	RUN NO.	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.470	.010	347.88550	1223.36691	526.36930	390.49930	100.70000	2.49360	357.22000	1.31990 2046.52000
1.470	-.025	347.92260	1223.51332	526.42257	390.25850	100.40000	2.49626	357.25980	1.33682 2046.52000

	RUN NO.	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.519	.009	326.84160	1234.15262	528.15855	382.07200	100.10000	2.49425	335.84990	.950.84990 1.21677 2046.31000
1.519	-.019	327.56130	1235.83386	528.92096	382.18160	100.10000	2.49765	336.58980	950.99000 1.20571 2046.31000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.17000	512.85400	417.31470	98.70000	2.50755	443.53980	1030.56000 .93400 2055.06000
1.300	-.027	433.70040	1201.14000	512.81010	417.44460	98.80000	2.50696	443.73000	1030.62000 .92144 2055.06000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.17000	512.85400	417.31470	98.70000	2.50755	443.53980	1030.56000 .93400 2055.06000
1.300	-.027	433.70040	1201.14000	512.81010	417.44460	98.80000	2.50696	443.73000	1030.62000 .92144 2055.06000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.17000	512.85400	417.31470	98.70000	2.50755	443.53980	1030.56000 .93400 2055.06000
1.300	-.027	433.70040	1201.14000	512.81010	417.44460	98.80000	2.50696	443.73000	1030.62000 .92144 2055.06000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.17000	512.85400	417.31470	98.70000	2.50755	443.53980	1030.56000 .93400 2055.06000
1.300	-.027	433.70040	1201.14000	512.81010	417.44460	98.80000	2.50696	443.73000	1030.62000 .92144 2055.06000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.17000	512.85400	417.31470	98.70000	2.50755	443.53980	1030.56000 .93400 2055.06000
1.300	-.027	433.70040	1201.14000	512.81010	417.44460	98.80000	2.50696	443.73000	1030.62000 .92144 2055.06000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.17000	512.85400	417.31470	98.70000	2.50755	443.53980	1030.56000 .93400 2055.06000
1.300	-.027	433.70040	1201.14000	512.81010	417.44460	98.80000	2.50696	443.73000	1030.62000 .92144 2055.06000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.17000	512.85400	417.31470	98.70000	2.50755	443.53980	1030.56000 .93400 2055.06000
1.300	-.027	433.70040	1201.14000	512.81010	417.44460	98.80000	2.50696	443.73000	1030.62000 .92144 2055.06000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.17000	512.85400	417.31470	98.70000	2.50755	443.53980	1030.56000 .93400 2055.06000
1.300	-.027	433.70040	1201.14000	512.81010	417.44460	98.80000	2.50696	443.73000	1030.62000 .92144 2055.06000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.17000	512.85400	417.31470	98.70000	2.50755	443.53980	1030.56000 .93400 2055.06000
1.300	-.027	433.70040	1201.14000	512.81010	417.44460	98.80000	2.50696	443.73000	1030.62000 .92144 2055.06000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.17000	512.85400	417.31470	98.70000	2.50755	443.53980	1030.56000 .93400 2055.06000
1.300	-.027	433.70040	1201.14000	512.81010	417.44460	98.80000	2.50696	443.73000	1030.62000 .92144 2055.06000

	RUN NO.	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.300	-.015	433.51120	1201.						

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 882

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM022) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1176/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	P PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.350	-.014	406.98510	1207.09000	518.89620	410.52440	100.40000	2.4957	416.87990	1003.18000	1.14603 2055.02499
1.350	.015	406.69040	1206.66000	518.72490	410.55470	100.50000	2.4960	416.57980	1003.20000	1.14643 2054.98999

RUN NO. 1234/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1234/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	P PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.470	-.017	348.18190	1224.78061	526.95940	389.94290	100.00000	2.5012	357.52980	939.77980	1.333888 2046.52000
1.470	.028	348.28980	1224.85306	526.99805	389.90210	99.89999	2.5020	357.63990	939.86990	1.333882 2046.52000

RUN NO. 1246/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1246/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	P PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.519	-.016	327.14110	1235.13116	528.58405	382.00660	100.00000	2.4970	336.15990	951.39990	1.22235 2046.27499
1.519	.022	327.34570	1235.46147	528.74327	381.97490	99.89999	2.4985	336.36990	951.49000	1.22824 2046.27499

RUN NO. 1249/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1249/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	P PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.519	-.016	327.11210	1234.96417	528.51514	382.07570	100.10000	2.4962	336.12990	950.83980	1.22871 2046.13499
1.520	.022	326.97140	1235.80991	528.82021	381.81420	99.89999	2.4987	335.99000	950.87990	1.22783 2046.17000

(VCM023) (04 OCT 91)

## PARAMETRIC DATA

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 883

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM024) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1173/ 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	P <sub>T</sub>	Q(PSF)	T(R)	TT(F)	RN/L	P <sub>C</sub>	PREF	SH10+3	PATM
1.300	1.999	433.69240	1200.88000	512.68550	417.54300	98.89999	2.50585	443.72000	1030.75999	.90675 2055.02499
1.299	-2.029	435.12300	1203.60001	513.77690	417.66580	98.89999	2.51167	445.17990	1030.88000	.87325 2055.02499

RUN NO. 1177/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1177/ 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	P <sub>T</sub>	Q(PSF)	T(R)	TT(F)	RN/L	P <sub>C</sub>	PREF	SH10+3	PATM
1.350	1.994	406.76560	1207.27000	518.99850	410.44360	100.40000	2.49779	416.65990	1003.35000	1.17050 2055.02499
1.350	-2.023	406.70870	1206.89000	518.82830	410.46440	100.40000	2.49704	416.59990	1003.35000	1.18337 2055.02499

RUN NO. 1235/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1235/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	P <sub>T</sub>	Q(PSF)	T(R)	TT(F)	RN/L	P <sub>C</sub>	PREF	SH10+3	PATM
1.470	1.995	348.76780	1226.49271	527.70529	390.04520	100.00000	2.50346	358.12990	940.13990	1.29976 2046.52000
1.470	-2.016	348.79640	1226.81020	527.83782	389.96750	99.89999	2.50442	358.15990	940.16990	1.29275 2046.52000

RUN NO. 1247/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1247/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	P <sub>T</sub>	Q(PSF)	T(R)	TT(F)	RN/L	P <sub>C</sub>	PREF	SH10+3	PATM
1.519	1.995	327.60550	1236.47505	529.17600	382.02030	100.00000	2.50036	336.63990	951.66990	1.24330 2046.24001
1.519	-2.016	327.22750	1235.26059	528.64835	382.06320	100.10000	2.49736	336.25000	951.74000	1.24773 2046.24001

RUN NO. 1174/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1174/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	P <sub>T</sub>	Q(PSF)	T(R)	TT(F)	RN/L	P <sub>C</sub>	PREF	SH10+3	PATM
1.300	-2.007	433.49490	1200.70000	512.62940	417.80540	99.30000	2.50306	443.51980	1030.96001	.78239 2055.06000
1.300	2.022	433.49270	1200.97000	512.76030	418.07690	99.70000	2.50123	443.51980	1031.00000	.77578 2055.06000

(VCM025) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1174/ 0	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	PHI =	90.000
MACH	BETA	P <sub>T</sub>	Q(PSF)	T(R)	TT(F)	RN/L	P <sub>C</sub>	PREF	SH10+3	PATM
1.300	-2.005	.06701	.03249	.06738	.09928	.00046	.00046	.00993	.00111	.00164 -.00000

(VCM025) ( 04 OCT 91 )

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 884

IA310 (AEDC 16TF-783) FLOW ANGULARITIES-FAIR OFF

(VCM025) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	RN/L =	GRADIENT INTERVAL =	-5.00/ 5.00
<b>MACH</b>	BETA	P	Q(PSF)	T(R) TT(F)
1.350	-2.013	406.83540	1207.17999	518.95090 410.47270
1.350	2.022	406.61870	1206.99001	518.88280 410.42870
GRADIENT		- .05371	- .04709	- .01688 - .01091

	RUN NO.	RN/L =	GRADIENT INTERVAL =	-5.00/ 5.00
--	---------	--------	---------------------	-------------

	RUN NO.	RN/L =	GRADIENT INTERVAL =	-5.00/ 5.00
<b>MACH</b>	BETA	P	Q(PSF)	T(R) TT(F)
1.471	-2.009	348.20610	1225.75934	527.36333 389.89790
1.471	2.025	347.56350	1224.20045	526.67567 389.82230
GRADIENT		- .15928	- .38640	- .17045 - .01874

	RUN NO.	RN/L =	GRADIENT INTERVAL =	-5.00/ 5.00
--	---------	--------	---------------------	-------------

	RUN NO.	RN/L =	GRADIENT INTERVAL =	-5.00/ 5.00
<b>MACH</b>	BETA	P	Q(PSF)	T(R) TT(F)
1.519	-2.009	327.44870	1236.47237	529.15070 381.90230
1.519	2.031	327.72310	1236.52814	529.21519 382.06030
GRADIENT		- .06792	- .01380	- .01596 - .03911

PARAMETRIC DATA

ALPHA = .000

PHI = -90.000

PATM SH10+3

RN/L 1.20208

PC 1003.45000

PREF 1.19590

RN/L 2055.02499

PC 1003.49000

PREF -.00153

RN/L 2055.02499

PC .00991

PREF -.00001

PATM SH10+3

RN/L 1.23821

PC 31980

PREF 1.24293

RN/L 2046.52000

PC 36990

PREF .00117

RN/L 2046.55499

PC .01242

PREF .00867



IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(VCM026) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1304/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	BETA =	.000	PREF	SH10+3	PATM
PHI	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC						
MACH	-1.983	462.59250	1198.06000	505.86600	426.35790	99.89999	2.50080	472.72000	853.26000	1.08592	2045.25999		
	1.250	-1.746	462.60080	1198.27000	505.97050	426.41500	100.00000	2.50064	472.73000	853.33980	1.09156	2045.25999	
	1.250	-1.508	462.68460	1197.67999	505.65310	426.49710	100.00000	2.49945	472.80980	853.41990	1.09210	2045.22501	
	1.249	-1.231	462.64310	1197.96001	505.80420	426.45780	100.00000	2.50001	472.76980	853.48000	1.11544	2045.25999	
	1.250	-0.993	462.57320	1197.64999	505.81420	426.44040	100.00000	2.49998	472.70000	853.53980	1.08312	2045.25999	
	1.249	-0.756	462.68480	1197.64999	505.63770	426.50020	100.00000	2.49939	472.80980	853.58980	1.08339	2045.25999	
	1.250	-0.518	462.60380	1197.88000	505.77220	426.45560	100.00000	2.49984	472.73000	853.62990	1.10366	2045.25999	
	1.250	-0.241	462.69970	1198.39999	506.01460	426.42770	100.00000	2.50092	472.82980	853.71000	1.07693	2045.22501	
	1.250	-0.003	462.53340	1197.92999	505.81270	426.43190	100.00000	2.49994	472.65990	853.75000	1.10066	2045.22501	
	1.250	-0.234	462.47310	1198.03000	505.87700	426.48190	100.10000	2.49955	472.59990	853.78980	1.09178	2045.22501	
	1.250	-0.472	462.42330	1198.03000	505.88770	426.46870	100.10000	2.49954	472.54980	853.81980	1.06293	2045.22501	
	1.250	-0.709	462.44340	1198.00999	505.87300	426.47610	100.10000	2.49950	472.56980	853.86990	1.05160	2045.22501	
	1.250	-0.987	462.55250	1198.07001	505.87960	426.49880	100.10000	2.49964	472.67990	853.91990	1.05155	2045.22501	
	1.250	-1.224	462.71140	1198.14999	505.88530	426.53250	100.10000	2.49982	472.83980	853.98000	1.05148	2045.22501	
	1.250	-1.501	462.76220	1198.00999	505.80320	426.56010	100.10000	2.49954	472.88990	854.01000	1.05160	2045.22501	
	1.250	-1.739	462.60350	1197.91000	505.78740	426.52860	100.10000	2.49932	472.73000	854.06980	1.04606	2045.22501	
	1.250	-1.977	462.53220	1198.10001	505.89900	426.49050	100.10000	2.49970	472.65990	854.08980	1.04029	2045.19000	
GRADIENT		- .00997	.02230	.01344	.02815	.02815	.04337	-.00021	-.00986	.20366	-.01515	-.01278	

	RUN NO.	1310/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	.000	BETA =	.000	PREF	SH10+3	PATM
PHI	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC						
MACH	-2.023	382.12400	1216.06000	524.29030	402.63280	100.80000	2.49616	391.83980	872.03980				
	-1.746	382.19530	1215.72000	524.14010	402.61470	100.70000	2.49618	391.90990	872.07980				
	-1.508	382.15190	1216.37000	524.42530	402.61210	100.80000	2.49674	391.86990	872.12990				
	-1.231	382.09450	1216.03000	524.27780	402.62700	100.80000	2.49608	391.80980	872.15990				
	-0.993	382.08500	1215.99001	524.26050	402.62770	100.80000	2.49600	391.79980	872.22000				
	-0.756	382.12550	1215.82001	524.18530	402.65600	100.80000	2.49572	391.83980	872.23000				
	-0.518	382.22390	1215.92000	524.22710	402.67630	100.80000	2.49598	391.9390	872.26000				
	-0.241	382.07620	1215.78999	524.17310	402.64400	100.80000	2.49563	391.78980	872.28980				
	-0.003	382.14450	1215.96001	524.24610	402.64840	100.80000	2.49599	391.85990	872.30980				
	-1.400	382.30270	1215.96001	524.24290	402.69630	100.80000	2.49611	392.01980	872.32980				
	-0.472	382.36250	1215.89999	524.21560	402.71970	100.80000	2.49604	392.07980	872.34990				
	-0.709	382.23340	1215.98000	524.25320	402.67330	100.80000	2.49609	391.95000	872.37990				
	-0.400	382.13400	1216.05000	524.28590	402.70870	100.90000	2.49556	391.84990	872.37990				
	-0.224	382.33200	1216.00000	524.26000	402.77320	100.90000	2.49561	392.04980	872.42990				
	-0.462	382.16430	1215.94000	524.23710	402.72830	100.90000	2.49538	391.87990	872.41990				
	-1.739	382.23320	1216.03999	524.27930	402.73950	100.90000	2.49561	391.95000	872.45000				
	-0.977	382.38280	1215.80000	524.17140	402.80740	100.90000	2.49528	392.09990	872.43990				
GRADIENT		.04535	-.01723	-.00842	.04155	.03654	-.00021	-.00021	-.00986	.20366	-.01515	-.01278	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 887

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(VCM026) (04 OCT 91)

## PARAMETRIC DATA

MACH	PHI	P	P <sub>T</sub>	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.545	-2.023	317.59010	1244.01532	530.333376	378.71070	101.00000	2.49281	326.43990	909.62990	1.10904	2045.19000
1.545	-1.746	317.67630	1244.49358	530.53069	378.69070	101.00000	2.49386	326.52980	909.67990	1.11445	2045.19000
1.545	-1.469	317.57960	1243.97163	530.31398	378.68730	101.00000	2.49317	326.42990	909.72000	1.12667	2045.22501
1.545	-1.271	317.42460	1243.37321	530.05862	378.73730	101.10000	2.49169	326.26980	909.79980	1.13908	2045.22501
1.544	-.993	317.58080	1243.08870	529.97974	378.78880	101.10000	2.49194	326.42990	909.83980	1.16041	2045.22501
1.544	-.716	317.46310	1243.16669	529.98729	378.73660	101.10000	2.49200	326.30980	909.84990	1.16336	2045.19000
1.544	-.479	317.61770	1243.54272	530.15757	378.81270	101.20000	2.49246	326.47000	909.87790	1.17217	2045.22501
1.544	-.241	317.65720	1243.36346	530.09721	378.83840	101.20000	2.49228	326.50980	909.89990	1.17541	2045.22501
1.544	-.003	317.53220	1242.77287	529.85061	378.84670	101.20000	2.49114	326.37990	909.93990	1.17596	2045.22501
1.544	.234	317.48220	1242.97681	529.91709	378.80300	101.20000	2.49158	326.32980	909.96000	1.18191	2045.22501
1.544	.511	317.53200	1242.64360	529.80117	378.84130	101.20000	2.49124	326.37990	909.98000	1.18842	2045.22501
1.544	.749	317.64820	1243.07509	529.98627	378.91580	101.30000	2.49143	326.50000	909.98000	1.18492	2045.22501
1.544	.987	317.69650	1243.17802	530.03461	378.92360	101.30000	2.49165	326.54980	910.01000	1.18483	2045.25999
1.544	1.264	317.73660	1242.88306	529.93002	378.95530	101.30000	2.49137	326.58980	910.02980	1.19131	2045.25999
1.544	1.462	317.62940	1242.73428	529.95344	378.93090	101.30000	2.49099	326.48000	910.04980	1.19144	2045.25999
1.544	1.739	317.45340	1242.68542	529.80165	378.87350	101.30000	2.49070	326.29980	910.04980	1.19147	2045.25999
1.544	1.977	317.41380	1242.97095	529.90294	378.91020	101.40000	2.49037	326.25980	910.04980	1.18500	2045.25999
GRADIENT	-.00413	-.322556	-.12463	.06432	.09362	-.00061	-.00432	-.10274	-.10274	.01976	.01655

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 888

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(VCM027) (04 OCT 91)

## PARAMETRIC DATA

MACH	PHI	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.599	-2.006	1252.899600	1597.00000	314.82760	522.27370	100.10000	2.49584	1262.64000	1300.87000	1.43909	2046.34500
.599	-1.731	1252.78400	1596.98000	314.90190	522.35550	100.20000	2.49552	1262.53000	1300.94000	1.42084	2046.31000
.599	-1.496	1252.55299	1597.35001	315.40220	522.29350	100.20000	2.49765	1262.31000	1301.00000	1.40966	2046.34500
.600	-1.222	1252.84700	1596.89999	314.78340	522.37060	100.20000	2.49503	1262.59000	1301.08000	1.39214	2046.34500
.599	-1.986	1253.19299	1596.88000	314.48240	522.41360	100.20000	2.49391	1262.92999	1301.16000	1.37797	2046.31000
.599	-751	1252.76100	1597.10001	315.02150	522.34160	100.20000	2.49606	1262.50999	1301.24001	1.36373	2046.31000
.599	-477	1253.06400	1597.22000	314.87450	522.45970	100.30000	2.49506	1262.81000	1301.30000	1.35318	2046.31000
.599	-241	1252.57800	1596.66000	314.80200	522.45430	100.30000	2.49432	1262.32001	1301.36000	1.33983	2046.34500
.600	-1.006	1252.02699	1597.25000	315.75000	522.33350	100.30000	2.49826	1262.78999	1301.44000	1.32906	2046.31000
.600	.229	1251.80901	1596.49001	315.29000	522.47170	100.40000	2.49538	1261.56000	1301.49001	1.32288	2046.31000
.599	.504	1252.68201	1597.02000	315.01950	522.52640	100.40000	2.49485	1262.42999	1301.53999	1.32584	2046.31000
.600	.739	1252.20599	1596.94000	315.34250	522.57030	100.50000	2.49538	1261.96001	1301.57001	1.33274	2046.31000
.599	.974	1252.57100	1596.97000	315.06810	522.61110	100.50000	2.49441	1262.32001	1301.64999	1.33271	2046.31000
.599	1.210	1252.82300	1597.12000	314.98850	522.72020	100.60000	2.49368	1262.57001	1301.69000	1.34634	2046.31000
.599	1.445	1252.45500	1596.73000	314.96240	522.80620	100.70000	2.49269	1262.20000	1301.75000	1.34667	2046.31000
.599	1.719	1252.41299	1596.75000	315.01320	522.89260	100.80000	2.49233	1262.16000	1301.81000	1.33976	2046.31000
.599	1.955	1252.72099	1597.13000	315.08030	522.80050	100.70000	2.49346	1262.47000	1301.87000	1.33258	2046.31000
GRADIENT	-.10302	-.03859	.05214	.14355	.16316	-.00077	-.002374	-.25108	-.00006	-.02374	-.00700
RUN NO.	1294 / 0	RN/L	=	2.49	GRADIENT INTERVAL	=	-5.00 /	5.00			
MACH	PHI	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.900	-1.967	752.98290	1273.06000	426.62350	482.29610	100.70000	2.49476	762.99000	977.37990	1.16725	2045.78500
.900	-1.732	752.95090	1273.16000	426.71090	482.27950	100.70000	2.49507	762.96000	977.49000	1.15793	2045.78500
.900	-1.496	752.77120	1273.05000	426.74240	482.34450	100.80000	2.49443	762.77980	977.58980	1.16110	2045.78500
.900	-1.261	752.76200	1272.98000	426.69970	482.26440	100.70000	2.49483	762.76980	977.68990	1.16732	2045.78500
.900	-.987	752.84230	1273.00000	426.66580	482.27690	100.70000	2.49478	762.84990	977.79980	1.16730	2045.75000
.900	-.751	752.67160	1272.95000	426.73290	482.25100	100.70000	2.49486	762.67990	977.86990	1.17044	2045.75000
.900	-.516	752.90410	1272.89999	426.56030	482.29910	100.70000	2.49442	762.90990	977.96000	1.16740	2045.78500
.900	-.241	752.79130	1273.07001	426.74460	482.26000	100.70000	2.49503	762.79980	978.03980	1.16416	2045.75000
.900	-.006	752.58300	1272.81000	426.68950	482.25000	100.70000	2.49459	762.58980	978.11990	1.15825	2045.75000
.900	.229	752.80000	1273.14999	426.79420	482.25290	100.70000	2.49524	762.80980	978.22000	1.15182	2045.75000
.900	.504	752.79300	1272.94000	426.65410	482.27440	100.70000	2.49468	762.79980	978.25980	1.15507	2045.75000
.900	.739	752.98440	1272.92999	426.53300	482.31050	100.70000	2.49440	762.99000	978.34990	1.16121	2045.75000
.900	.974	752.64230	1272.91000	426.72310	482.25000	100.70000	2.49479	762.64990	978.40990	1.16430	2045.71500
.900	1.210	752.95290	1273.00999	426.60690	482.29610	100.70000	2.49466	762.96000	978.47000	1.16421	2045.71500
.900	1.445	752.55080	1272.95000	426.80490	482.22900	100.70000	2.49502	762.55980	978.51980	1.16735	2045.71500
.900	1.719	752.94410	1272.92000	426.55030	482.39010	100.80000	2.49385	762.95000	978.56980	1.16429	2045.71500
.900	1.955	752.90230	1273.03000	426.65090	482.28470	100.70000	2.49478	762.90990	978.63990	1.15498	2045.71500
GRADIENT	-.01100	-.02624	-.01144	-.00168	-.00099	-.00006	-.01124	-.01124	-.01124	-.01109	-.02024

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

(VCM027) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1305/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-8.000	BETA =	.000	PREF		
										P	T(R)	RN/L
MACH	PHI	P	PT	Q(PSF)	T(R)	TT(F)				PC		
1.250	-2.006	462.67140	1198.19000	505.91460	426.51780	100.10000	2.49990	472.79980	854.21000			
1.250	-1.731	462.51120	1198.30000	506.00510	426.46460	100.10000	2.50010	472.63990	854.23000	1.04853	2045.	19000
1.250	-1.496	462.42310	1198.02000	505.88260	426.46970	100.10000	2.49952	472.54980	854.25000	1.04878	2045.	19000
1.250	-1.221	462.48320	1198.00000	505.85940	426.48750	100.10000	2.49949	472.60990	854.28980	1.07154	2045.	19000
1.250	-0.986	462.40530	1197.72000	505.73440	426.49560	100.10000	2.49891	472.52980	854.31980	1.07466	2045.	15500
1.250	-0.751	462.68190	1198.10001	505.86650	426.52980	100.10000	2.49971	472.80980	854.33980	1.07432	2045.	15500
1.250	-0.516	462.53150	1198.21001	505.95510	426.55250	100.20000	2.49933	472.65990	854.37990	1.07135	2045.	19000
1.250	-0.241	462.79220	1198.00000	505.79170	426.64530	100.20000	2.49894	472.91990	854.42990	1.06296	2045.	19000
1.250	-0.006	462.58370	1197.88000	505.77660	426.60250	100.20000	2.49867	472.71000	854.42990	1.04048	2045.	15500
1.250	.229	462.75240	1198.00000	505.80050	426.63480	100.20000	2.49893	472.87990	854.47000	1.03203	2045.	15500
1.250	.465	462.65310	1197.91000	505.77640	426.61770	100.20000	2.49874	472.77980	854.48000	1.03211	2045.	15500
1.250	.739	462.64040	1198.33000	505.99220	426.57150	100.20000	2.49959	472.76980	854.52980	1.02897	2045.	15500
1.250	.975	462.48290	1198.08000	505.89990	426.55570	100.20000	2.49906	472.60990	854.54980	1.03752	2045.	15500
1.250	1.210	462.59160	1198.20000	505.93700	426.57200	100.20000	2.49932	472.72000	854.55980	1.04021	2045.	15500
1.250	1.485	462.63430	1197.78000	505.71480	426.62600	100.20000	2.49847	472.75980	854.58980	1.03222	2045.	15500
1.250	1.720	462.66090	1198.25999	505.95210	426.58420	100.20000	2.49945	472.78980	854.59980	1.02904	2045.	15500
1.250	1.955	462.81130	1198.14999	505.86350	426.63500	100.20000	2.49924	472.93990	854.61990	1.02637	2045.	12000
1.250	GRADIENT	.04321	.00446	-.00721	.03589	.03275	-.00018	.04336	.10921	-.00887	-.01284	

RUN NO.	1311/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-8.000	BETA =	.000	PREF		
										P	T(R)	RN/L
MACH	PHI	P	PT	Q(PSF)	T(R)	TT(F)				PC		
1.399	-2.007	382.56050	12115.82001	524.17630	402.85890	100.90000	2.49545	392.27980	872.48000			
1.399	-1.732	382.27980	12116.48000	524.47090	402.78370	101.00000	2.49585	392.00000	872.49000	1.03284	2044.	91000
1.400	-1.497	382.01640	12115.87000	524.20920	402.76220	101.00000	2.49455	391.73000	872.48000	1.03613	2044.	91000
1.400	-1.261	382.24240	12116.14000	524.32300	402.80470	101.00000	2.49521	391.96000	872.49000	1.03590	2044.	94501
1.400	-.987	382.26220	12116.08000	524.29610	402.74460	100.90000	2.49570	391.98000	872.50000	1.03874	2044.	94501
1.399	-.752	382.30520	12115.57001	524.30520	402.80570	100.90000	2.49481	392.01980	872.50000	99543	2044.	94501
1.400	-.516	382.27150	12116.17999	524.33980	402.73780	100.90000	2.49589	391.99000	872.50000	99226	2044.	94501
1.400	-.242	382.12430	12116.00999	524.26860	402.78150	101.00000	2.49488	391.83980	872.50000	98973	2044.	94501
1.400	-.007	382.04470	12116.12000	524.31840	402.74710	101.00000	2.49503	391.75980	872.50000	98697	2044.	98000
1.400	.229	382.17290	12116.17999	524.34180	402.78000	101.00000	2.49523	391.88990	872.51980	98693	2044.	94501
1.400	.464	382.05440	12116.13000	524.32230	402.74900	101.00000	2.49505	391.76980	872.50000	98697	2044.	98000
1.400	.738	382.14450	12115.91000	524.22440	402.79710	101.00000	2.49472	391.85990	872.50000	98714	2044.	98000
1.400	.974	382.12500	12115.91000	524.22460	402.79100	101.00000	2.49470	391.83980	872.50000	1.00053	2044.	98000
1.400	1.209	382.26150	12116.22000	524.35770	402.80300	101.00000	2.49537	391.98000	872.50000	1.00027	2045.	01500
1.400	1.484	382.16480	12115.87000	524.20630	402.80690	101.00000	2.49466	391.87990	872.50000	97396	2044.	98000
1.400	1.719	382.27200	12116.12000	524.31370	402.81540	101.00000	2.49519	391.99000	872.51000	.97114	2044.	98000
1.400	1.994	382.09420	12116.09000	524.30400	402.76490	101.00000	2.49501	391.80980	872.50000	.96593	2045.	01500
1.400	.04192	.004438	.002880	-.00095	.01682	-.00012	-.04238	.00484	-.00484	-.01652	.02107	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

PAGE 890  
(VCM027) (04 OCT 91)

## PARAMETRIC DATA

MACH	PHI	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	P/C	PREF	SH10+3	P AIM
1.543	-1.967	317.91280	1243.03192	530.02013	379.08810	101.40000	2.49091	326.76980	910.06980	1.17883	2045.25999
1.543	-1.732	317.71360	1243.95049	530.32938	378.93310	101.40000	2.49229	326.56980	910.03980	1.18100	2045.29500
1.543	-1.497	318.06740	1243.57881	530.25656	379.08980	101.40000	2.49209	326.92990	910.03980	1.18139	2045.29500
1.544	-1.222	317.50290	1242.63878	529.79368	378.97090	101.40000	2.48992	326.34990	910.01980	1.18533	2045.25999
1.544	-.987	317.26780	1242.58514	529.72833	378.95650	101.50000	2.48904	326.10990	910.01000	1.18845	2045.25999
1.543	-.751	317.96260	1242.61510	529.87183	379.19360	101.50000	2.48999	326.81980	910.00000	1.19160	2045.29500
1.544	-.477	317.64750	1243.23309	530.04593	379.03250	101.50000	2.49057	326.50000	910.01000	1.18786	2045.29500
1.543	-.242	318.05930	1243.36803	530.17583	379.26540	101.60000	2.49007	326.91990	910.00000	1.16323	2045.29500
1.545	-.006	317.32470	1243.54070	530.10172	378.99680	101.60000	2.48940	326.16990	910.01000	1.15996	2045.29500
1.544	.229	317.65890	1243.22148	530.04506	379.14620	101.60000	2.48919	326.50980	910.00000	1.15727	2045.25999
1.544	.464	317.57030	1243.29565	530.05579	379.10030	101.60000	2.48936	326.41990	909.98000	1.16325	2045.25999
1.544	.739	317.49340	1242.90591	529.89394	379.17550	101.70000	2.48803	326.33980	909.98000	1.16361	2045.29500
1.544	.974	317.76680	1243.03587	529.99525	379.25590	101.70000	2.48865	326.61990	909.98000	1.16656	2045.25999
1.543	1.209	317.92210	1242.81171	529.93760	379.28030	101.70000	2.48940	326.77980	909.96000	1.20388	2045.25999
1.544	1.445	317.60010	1242.40610	529.72292	379.26220	101.80000	2.48790	326.45000	909.97000	1.21053	2045.25999
1.543	1.719	317.65890	1242.42322	529.74093	379.27690	101.80000	2.48808	326.50980	909.97000	1.21367	2045.29500
1.544	1.994	317.58030	1242.32276	529.68941	379.18190	101.70000	2.48859	326.42990	909.93990	1.22009	2045.25999
GRADIENT	-.03749	-.08243	-.19878	-.08243	.06855	.10651	-.00086	-.03872	-.02480	-.00312	.00601



PAPERS

$$\text{ALPHA} = .000 \quad \text{BETA} = -4.000$$

RUN NO. 1312 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00 / 5.00



## PARAMETRIC DATA

RUN NO.: 1296 / O RN/L = 2.50 GRADIENT INTERVAL = -5.00 / 5.00

RUN NO.: 1302 / O RN/L = 2.49 GRADIENT INTERVAL = -5.00 / 5.00



DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PORT MISORIENT-FAIRING OFF

PAGE 896

( VCMO29 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	PHI	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.543	88.025	317.59030	124.1.75069	529.47203	379.32370	101.90000	2.48734	326.43990	909.99000	1.25603	2045 12000
1.543	88.263	317.65890	124.1.72964	529.47686	379.41750	102.00000	2.48679	326.50980	910.00000	1.25606	2045 12000
1.544	88.502	317.41480	124.1.67282	529.40953	379.27760	101.90000	2.48684	326.25980	910.01000	1.24959	2045 15500
1.543	88.740	317.65940	124.1.59315	529.42956	379.42970	102.00000	2.48657	326.50980	910.01980	1.25620	2045 12000
1.543	89.018	317.67770	124.2.01619	529.58897	379.40720	102.00000	2.48713	326.52980	910.03980	1.24927	2045 15500
1.544	89.256	317.49120	124.2.19891	529.62265	379.32540	102.00000	2.48722	326.33980	910.04980	1.24906	2045 12000
1.543	89.494	317.64790	124.2.11916	529.62279	379.38330	102.00000	2.48735	326.50000	910.05980	1.25241	2045 12000
1.543	89.772	317.76590	124.1.96744	529.58707	379.43820	102.00000	2.48724	326.61990	910.04980	1.25258	2045 12000
1.544	90.010	317.36550	124.1.62527	529.38190	379.31880	102.00000	2.48636	326.21000	910.06980	1.25940	2045 12000
1.543	90.288	317.63890	124.1.75441	529.48243	379.39920	102.00000	2.48698	326.49000	910.06980	1.26256	2045 08501
1.543	90.526	317.44360	124.1.57367	529.37708	379.34200	102.00000	2.48653	326.28980	910.08980	1.26600	2045 12000
1.544	90.764	317.51980	124.2.05771	529.57331	379.31710	102.00000	2.48760	326.36990	910.09980	1.27208	2045 12000
1.543	91.042	317.60790	124.2.23930	529.65965	379.34990	102.00000	2.48767	326.46000	910.07980	1.25879	2045 12000
1.543	91.280	317.61010	124.1.63503	529.43176	379.40410	102.00000	2.48666	326.46000	910.08980	1.25942	2045 08501
1.543	91.519	317.57030	124.1.82527	529.49651	379.37330	102.00000	2.48693	326.41990	910.09990	1.25921	2045 12000
1.543	91.757	317.69820	124.1.61636	529.44176	379.43680	102.00000	2.48673	326.54980	910.10990	1.25944	2045 12000
1.543	92.035	317.67770	124.1.91705	529.55129	379.40720	102.00000	2.48713	326.52980	910.10990	1.25587	2045 12000
GRADIENT	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

( VCMO30 ) ( 04 OCT 91 )

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
598	-8.099	1253.39600	1596.42000	313.92920	522.10740	99.80000	2.49378	1263.12000	1300.25000	64999	
600	-7.097	1252.21300	1596.62000	315.06810	522.13450	100.00000	2.4996	1261.96001	1300.21001	.72362	2043 64999
599	6.117	1252.43500	1596.67000	314.92770	521.96970	99.80000	2.49763	1262.17999	1300.17000	.72165	2043 64999
600	-5.142	1251.96500	1596.78999	315.41380	521.99580	99.89999	2.49893	1261.72000	1300.14000	.71577	2043 61501
600	-4.164	1252.10600	1596.88000	315.37450	522.00420	99.89999	2.49886	1261.86000	1300.10001	.71573	2043 61501
601	-3.198	1251.45900	1597.17999	316.15650	522.08570	100.10000	2.50082	1261.23000	1300.11000	.70789	2043 61501
601	-2.235	1251.62000	1597.28999	316.11720	521.90800	99.89999	2.50191	1261.39000	1300.06000	.72137	2043 61501
600	-1.264	1251.12500	1596.84000	315.63180	522.15230	100.10000	2.49862	1261.50999	1300.03999	.72548	2043 58000
601	-2.75	1251.42500	1597.38000	316.35280	522.06300	100.10000	2.50170	1261.20000	1300.00999	.71164	2043 61501
600	.716	1252.27699	1597.45000	315.71310	521.87820	99.80000	2.50115	1262.03999	1299.95000	.71161	2043 58000
600	1.739	1251.90800	1596.60001	315.30100	521.91360	99.80000	2.49893	1261.66000	1299.94000	.71779	2043 58000
GRADIENT	.03133	-.00855	-.03290	-.01952	-.02580	.00002	.03068	-.03094	-.00014	-.00638	

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

( VCMO30 ) ( 04 OCT 91 )

PARAMETRIC DATA

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM030) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PREF	PATM
.800	-8.063	880.40480	1342.38000	394.67550	496.65700	100.60000	2.49835	890.31980	1046.89000
.799	-7.056	881.05520	1342.11000	394.03340	496.79030	100.60000	2.49638	890.96000	1046.94000
.800	-6.067	880.67870	1342.27000	394.40800	496.71260	100.60000	2.49753	890.58980	1046.95000
.800	-5.088	880.29830	1342.06000	394.51100	496.67360	100.60000	2.49757	890.21000	1047.00000
.800	-4.103	880.25070	1341.88000	394.41040	496.68480	100.60000	2.49711	890.15990	1047.00000
.800	-3.132	880.20460	1342.25000	394.71530	496.63840	100.60000	2.49831	890.11990	1047.03999
.800	-2.158	880.29030	1341.92999	394.42020	496.77470	100.70000	2.49662	890.20000	1047.07001
.800	-1.185	880.08720	1342.00999	394.61770	496.73340	100.70000	2.49722	890.00000	1047.06000
.800	-.188	880.34910	1342.05000	394.46900	496.77150	100.70000	2.49688	890.26000	1047.07001
.800	.802	880.45040	1342.05000	394.40000	496.78780	100.70000	2.49676	890.35990	1047.07001
.800	.818	880.52050	1342.07001	394.36740	496.79690	100.70000	2.49663	890.42990	1047.08000
.800	GRADIENT	.04954	.01050	-.02591	.02287	.01803	-.00016	.04918	.00430

RUN NO. 1329/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PREF	PATM
.900	-8.058	752.83980	1273.17000	426.78390	482.17210	100.60000	2.49582	762.84990	977.96000
.900	-7.048	752.73410	1272.80000	426.59250	482.19260	100.60000	2.49494	762.74000	977.43990
.899	-6.066	752.96800	1272.67000	426.36430	482.33570	100.70000	2.49371	762.97000	976.95000
.900	-5.081	752.69140	1272.99001	426.74880	482.25020	100.70000	2.49495	762.70000	977.71000
.900	-4.105	752.59960	1273.06000	426.85160	482.31200	100.80000	2.49468	762.60990	977.85990
.900	-3.133	752.71360	1272.84000	426.63260	482.27050	100.70000	2.49451	762.74000	977.13087
.900	-2.163	752.67720	1273.27000	426.94950	482.21750	100.70000	2.49573	762.68990	977.73000
.900	-1.192	752.80270	1272.97000	426.66920	482.27290	100.70000	2.49475	762.80980	977.71000
.900	-.197	752.59470	1272.70000	426.60720	482.26390	100.70000	2.49428	762.59990	977.68990
.900	.789	752.66260	1272.89000	426.69750	482.16990	100.60000	2.49529	762.66990	977.66990
.900	1.806	752.96480	1272.91000	426.53120	482.22290	100.60000	2.49494	762.97000	977.63990
.900	GRADIENT	.03325	-.03340	-.04271	-.01530	-.02905	-.00003	.03248	-.03046

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PREF	PATM
1.098	-8.001	566.69700	1206.81000	478.14920	450.39330	99.30000	2.50423	576.88990	862.51980
1.098	-6.974	565.75850	1206.45000	478.31200	450.21850	99.30000	2.50385	575.95000	862.53980
1.099	-5.985	564.72950	1206.10001	478.51510	450.02170	99.30000	2.50353	574.91990	862.54980
1.100	-4.996	564.53490	1205.53999	478.26610	450.03710	99.30000	2.50234	574.72000	862.59990
1.100	-4.007	564.33180	1205.81000	478.50340	449.96190	99.30000	2.50305	574.51980	862.63990
1.101	-3.022	564.52880	1206.10001	478.59420	449.97580	99.30000	2.50362	574.72000	862.66990
1.101	-2.040	564.66210	1205.83000	478.38480	450.03520	99.30000	2.50294	574.84990	862.70000
1.100	-1.036	564.82150	1205.92999	478.37990	450.06080	99.30000	2.50310	575.01000	862.73000
1.100	-.075	564.86940	1206.13000	478.47730	450.05030	99.30000	2.50353	575.05980	862.75000
1.100	.932	564.71710	1205.91000	478.38770	450.05150	99.30000	2.50307	574.96000	862.78980
1.100	1.936	565.07980	1206.13000	478.39400	450.09810	99.30000	2.50343	575.26980	862.79980
1.100	GRADIENT	.08664	.05797	-.00051	.01354	-.00009	.08705	.02911	.00379

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PREF	PATM
1.31435	SH10+3	1.30710	2044.73500	1.31435	2044.73500	1.31435	2044.73500	1.31435	2044.73500
1.38144	SH10+3	1.38144	2044.73500	1.38144	2044.73500	1.38144	2044.73500	1.38144	2044.73500
1.39195	SH10+3	1.39195	2044.73500	1.39195	2044.73500	1.39195	2044.73500	1.39195	2044.73500
1.38825	SH10+3	1.38825	2044.73500	1.38825	2044.73500	1.38825	2044.73500	1.38825	2044.73500
1.31087	SH10+3	1.31087	2044.73500	1.31087	2044.73500	1.31087	2044.73500	1.31087	2044.73500
1.29676	SH10+3	1.29676	2044.73500	1.29676	2044.73500	1.29676	2044.73500	1.29676	2044.73500
1.28015	SH10+3	1.28015	2044.66499	1.28015	2044.66499	1.28015	2044.66499	1.28015	2044.66499
1.27037	SH10+3	1.27037	2044.70000	1.27037	2044.70000	1.27037	2044.70000	1.27037	2044.70000
1.32116	SH10+3	1.32116	2044.66499	1.32116	2044.66499	1.32116	2044.66499	1.32116	2044.66499
1.31080	SH10+3	1.31080	2044.66499	1.31080	2044.66499	1.31080	2044.66499	1.31080	2044.66499
-.00855	SH10+3	-.00855	-.01016	-.00855	-.01016	-.00855	-.01016	-.00855	-.01016

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.249	-8.047	462.84160	1198.09000	505.82640	427.03000	100.70000	2.49619	472.97000	903.49000	1.15773	204.1.86501
1.250	-7.037	462.53390	1197.89000	505.79250	427.04570	100.80000	2.49516	472.65990	903.59990	1.16101	204.1.86501
1.250	-6.046	462.39500	1197.77000	505.76220	427.02120	100.80000	2.49490	472.51980	903.66990	1.16112	204.1.86501
1.250	-5.062	462.76000	1198.35001	505.97610	427.05830	100.80000	2.49612	472.88990	903.75000	1.16675	204.1.86501
1.250	-4.083	462.43090	1198.34000	506.04300	426.89650	100.70000	2.49665	472.55980	903.81980	1.16987	204.1.86501
1.250	-3.106	462.45460	1197.80000	505.76420	427.03390	100.80000	2.49496	472.57980	903.86990	1.16419	204.1.86501
1.250	-2.129	462.46660	1197.52000	505.61960	426.98930	100.70000	2.49498	472.58980	903.93990	1.16446	204.1.83000
1.250	-1.148	462.51320	1197.99001	505.84770	427.03000	100.80000	2.49536	472.63990	904.01000	1.16400	204.1.86501
1.250	-1.153	462.49410	1197.86000	505.78610	427.03810	100.80000	2.49509	472.61990	904.06980	1.16413	204.1.83000
1.250	.842	462.65380	1197.84000	505.74100	427.00610	100.70000	2.49566	472.77980	904.10990	1.16106	204.1.86501
1.250	1.853	462.53170	1198.17999	505.93990	427.01540	100.80000	2.49575	472.65990	904.14990	1.15149	204.1.83000
GRADIENT	.02627	-.00166	-.00658	.01256	.01256	.00721	-.00004	.02635	.05777	-.00223	-.00380

RUN NO. 1365/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.400	-8.008	382.07060	1215.10001	523.87130	402.42020	100.40000	2.49674	391.77980	920.70000	1.34831	204.1.75999
1.400	-7.026	381.93020	1215.41000	524.00980	402.42070	100.50000	2.49661	391.63990	920.72000	1.34091	204.1.75999
1.400	-6.038	381.68600	1214.92000	523.80030	402.39330	100.50000	2.49554	391.38990	920.75000	1.33092	204.1.79500
1.400	-5.051	381.76610	1214.74001	523.72000	402.50630	100.60000	2.49468	391.47000	920.76980	1.32414	204.1.75999
1.400	-4.068	381.81420	1214.96001	523.81520	402.50000	100.60000	2.49511	391.51980	920.79980	1.32042	204.1.75999
1.400	-3.089	381.81230	1215.31000	523.96830	402.46630	100.60000	2.49575	391.51980	920.81980	1.31657	204.1.72501
1.400	-2.113	381.74220	1214.44000	524.02660	402.43290	100.60000	2.49593	391.45000	920.81980	1.31298	204.1.72501
1.400	-1.135	381.87430	1214.87000	523.77490	402.52660	100.60000	2.49499	391.57980	920.81980	1.31014	204.1.72501
1.400	-.134	381.83670	1214.53000	523.62670	402.54760	100.60000	2.49434	391.53980	920.81980	1.30706	204.1.72501
1.400	.856	382.04150	1215.00999	523.83250	402.56370	100.60000	2.49537	391.75000	920.83980	1.30655	204.1.69000
1.400	1.871	382.03960	1215.31000	523.96390	402.60670	100.70000	2.49532	391.75000	920.84990	1.30279	204.1.72501
GRADIENT	.04449	-.01626	-.00799	.02279	.01091	-.00006	-.00006	.04492	.00688	-.00285	-.00629

RUN NO. 1376/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.449	-8.093	359.16060	1225.88000	528.14210	394.93990	101.20000	2.49211	368.63990	931.96000	1.24473	204.2.14500
1.450	-7.082	358.99150	1226.25000	528.28760	394.78220	101.10000	2.49320	368.47000	932.00980	1.26755	204.2.14500
1.450	-6.101	358.95240	1226.14999	528.24390	394.70870	101.00000	2.49358	368.42990	932.02980	1.24775	204.2.14500
1.450	-5.120	358.88330	1226.12000	528.22780	394.61940	100.90000	2.49405	368.35990	932.04980	1.27439	204.2.14500
1.450	-4.148	358.88550	1225.75000	528.07420	394.65410	100.90000	2.49340	368.35990	932.07980	1.27142	204.2.14500
1.450	-3.177	358.82590	1225.81000	528.09590	394.55960	100.80000	2.49405	368.29980	932.08980	1.27136	204.2.14500
1.450	-2.212	359.00290	1225.91000	528.14670	394.53540	100.70000	2.49499	368.48000	932.11990	1.28134	204.2.14500
1.450	-1.242	358.59910	1225.84000	528.09670	394.48540	100.80000	2.49389	368.06980	932.14990	1.27804	204.2.11000
1.450	-.246	358.83180	1226.61000	528.42900	394.41750	100.70000	2.49605	368.30980	932.15990	1.28061	204.2.11000
1.450	.742	358.92360	1226.67999	528.18430	394.43090	100.60000	2.49568	368.39990	932.17990	1.28461	204.2.11000
1.450	1.764	358.90500	1225.67999	528.04610	394.50560	100.60000	2.49508	368.37990	932.18990	1.28158	204.2.11000
GRADIENT	.00330	-.01333	-.01361	-.01333	-.03511	-.04720	-.04720	.00354	.00351	.00204	.00761

RUN NO. 1388/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.449	-8.093	359.16060	1225.88000	528.14210	394.93990	101.20000	2.49211	368.63990	931.96000	1.24473	204.2.2042
1.450	-7.082	358.99150	1226.25000	528.28760	394.78220	101.10000	2.49320	368.47000	932.00980	1.26755	204.2.2042
1.450	-6.101	358.95240	1226.14999	528.24390	394.70870	101.00000	2.49358	368.42990	932.02980	1.24775	204.2.2042
1.450	-5.120	358.88330	1226.12000	528.22780	394.61940	100.90000	2.49405	368.35990	932.04980	1.27439	204.2.2042
1.450	-4.148	358.88550	1225.75000	528.07420	394.65410	100.90000	2.49340	368.35990	932.07980	1.27142	204.2.2042
1.450	-3.177	358.82590	1225.81000	528.09590	394.55960	100.80000	2.49405	368.29980	932.08980	1.27136	204.2.2042
1.450	-2.212	359.00290	1225.91000	528.14670	394.53540	100.70000	2.49499	368.48000	932.11990	1.28134	204.2.2042
1.450	-1.242	358.59910	1225.84000	528.09670	394.48540	100.80000	2.49389	368.06980	932.14990	1.27804	204.2.11000
1.450	-.246	358.83180	1226.61000	528.42900	394.41750	100.70000	2.49605	368.30980	932.15990	1.28061	204.2.11000
1.450	.742	358.92360	1226.67999	528.18430	394.43090	100.60000	2.49568	368.39990	932.17990	1.28461	204.2.11000
1.450	1.764	358.90500	1225.67999	528.04610	394.50560	100.60000	2.49508	368.37990	932.18990	1.28158	204.2.11000
GRADIENT	.00330	-.01333	-.01361	-.01333	-.03511	-.04720	-.04720	.00354	.00351	.00204	.00761

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

( VCM030 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1433/ O	RN/L =	2.49	GRADIENT INTERVAL =	- 5.00/ 5.00	BETA =	- 4.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
ALPHA	-8.080	348.20650	1225.47728	527.24838	390.95240	101.30000	2.49167	357.54980	897.66990	1.24815 2043.12500
	-7.070	347.95170	1224.25491	526.72797	390.88700	101.30000	2.49109	357.28980	897.68990	1.30207 2043.12500
	-6.089	347.90360	1224.05914	526.64417	390.89500	101.30000	2.49059	357.24000	897.76000	1.29892 2043.12500
	-5.106	347.83470	1223.99501	526.61214	390.87210	101.30000	2.49054	357.16990	897.76000	1.30233 2043.12500
	-4.134	348.18800	1224.35240	526.78779	390.96290	101.30000	2.49134	357.52980	897.78980	1.29865 2043.12500
	-3.162	347.87380	1224.68336	526.89709	390.88010	101.30000	2.49066	357.21000	897.79980	1.26845 2043.09000
	-2.193	347.97170	1224.08620	526.66088	390.90330	101.30000	2.49092	357.30980	897.81980	1.30561 2043.09000
	-1.225	348.02000	1224.40657	526.79496	390.90160	101.30000	2.49130	357.35990	897.82980	1.29856 2043.09000
	-2.27	348.07890	1224.58183	526.87132	390.91700	101.30000	2.49143	357.41990	897.84990	1.29171 2043.09000
	.765	347.99170	1224.25250	526.73042	390.91260	101.30000	2.49109	357.32980	897.86990	1.29538 2043.05499
	1.785	348.14920	1224.27492	526.75282	390.96310	101.30000	2.49106	357.49000	897.86990	1.29538 2043.05499
GRADIENT	.00843	-.02175	-.00826	.00297	-.00000	.00000	.00857	.01488	.00109	-.01017

RUN NO. 1400/ O RN/L = 2.49 GRADIENT INTERVAL = - 5.00/ 5.00

	RUN NO.	1433/ O	RN/L =	2.49	GRADIENT INTERVAL =	- 5.00/ 5.00	BETA =	- 4.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
ALPHA	-8.080	337.61520	1231.23026	528.48862	386.52880	100.80000	2.49525	346.80980	944.68990	1.21495 2042.35500
	-7.064	337.38210	1230.52338	528.18108	386.50510	100.80000	2.49398	346.56980	944.74000	1.22197 2042.35500
	-6.080	337.38110	1230.58417	528.20461	386.48540	100.80000	2.49435	346.56980	944.75980	1.23148 2042.35500
	-5.097	337.61790	1230.64047	528.25546	386.65310	100.90000	2.49362	346.80980	944.76980	1.21555 2042.35500
	-4.121	337.57810	1230.70001	528.27477	386.62940	100.90000	2.49378	346.76980	944.78980	1.21865 2042.35500
	-3.152	337.59860	1230.51938	528.20541	386.65310	100.90000	2.49348	346.78980	944.79980	1.21884 2042.35500
	-2.183	337.41140	1230.61690	528.22152	386.58010	100.90000	2.49348	346.59990	944.79980	1.21871 2042.32001
	-1.209	337.44970	1230.94571	528.35733	386.57230	100.90000	2.49392	346.63990	944.81980	1.21206 2042.35500
	-2.14	337.57620	1231.32266	528.52288	386.58960	100.90000	2.49452	346.76980	944.82980	1.20540 2042.35500
	.780	337.44870	1231.26801	528.48416	386.55130	100.90000	2.49431	346.63990	944.82980	1.20544 2042.35500
	1.800	337.49020	1230.69266	528.26051	386.61400	100.90000	2.49342	346.67990	944.83980	1.20917 2042.35500
GRADIENT	-.01432	.07850	.02932	-.00861	-.00000	-.00000	-.01436	.00868	-.00248	-.00127

RUN NO. 1400/ O RN/L = 2.50 GRADIENT INTERVAL = - 5.00/ 5.00

	RUN NO.	1421/ O	RN/L =	2.50	GRADIENT INTERVAL =	- 5.00/ 5.00	BETA =	- 4.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
ALPHA	-8.074	328.53690	1235.97356	529.12392	382.26640	99.89999	2.50206	337.58980	954.05980	1.28326 2042.81000
	-7.062	326.62400	1236.37062	528.98301	381.60110	99.89999	2.50016	335.63990	954.00980	1.25951 2042.81000
	-6.081	326.98100	1235.32086	528.63322	381.81030	99.89999	2.49890	336.00000	953.99000	1.26721 2042.81000
	-5.103	327.26730	1234.07906	528.19797	382.08690	100.10000	2.49721	336.28980	954.01980	1.32218 2042.81000
	-4.122	327.04270	1233.76666	528.04260	382.03320	100.10000	2.49653	336.05980	953.99000	1.32591 2042.81000
	-3.154	327.13890	1233.34549	535.63716	381.95310	100.00000	2.49808	336.15990	954.00000	.00000 2042.81000
	-2.182	327.22710	1234.13557	528.21393	381.91330	99.89999	2.49881	336.25000	954.00000	1.33583 2042.81000
	-1.207	327.39280	1234.21140	528.26837	382.02290	100.00000	2.49869	336.41990	953.98000	1.34268 2042.81000
	-1.518	327.43240	1234.13658	528.24586	382.03880	100.00000	2.49869	336.46000	953.97000	1.34624 2042.77499
	.779	327.39260	1234.12691	528.26781	382.01420	100.00000	2.49886	336.41990	953.97000	1.34963 2042.77499
	1.519	327.22630	1234.10771	528.20351	382.03390	100.10000	2.49791	336.25000	953.97000	1.34971 2042.81000
GRADIENT	.04536	-1.34782	-.51468	.00910	.00384	.00020	.04669	-.00544	.00059	-.00380

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 900

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM030) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.543	-8.078	317.62890	124.1.47906	529.37554	378.57840	100.80000	2.49425	326.48000	959.21000	1.28594	2042.56500
1.543	-7.069	317.75510	124.1.74774	529.50144	378.53120	100.70000	2.49545	326.60990	959.42990	1.28568	2042.56500
1.543	-5.101	317.66800	124.1.18965	529.27348	378.52760	100.70000	2.49484	326.51980	899.46000	1.30298	2042.60001
GRADIENT		.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000	.00000

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM031) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1410/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.517	-8.074	327.25440	1232.27585	527.50146	382.49390	100.80000	2.49428	336.27980	911.50000	1.49776	2042.95000
1.517	-7.066	326.92900	1230.44621	526.74294	382.62990	100.90000	2.49428	335.93990	911.49000	1.48854	2042.95000
1.516	-6.081	327.59840	1231.04358	527.07769	382.76730	101.00000	2.49311	336.62990	911.60990	1.56962	2042.98500
1.516	-5.103	327.53960	1231.03636	527.06673	382.74220	101.00000	2.49313	336.56980	911.63990	1.57361	2042.98500
1.516	-4.124	327.23680	1230.60942	526.85612	382.73390	101.10000	2.49169	336.25980	911.65990	1.58212	2042.98500
1.517	-3.155	327.16850	1230.41487	526.77017	382.71730	101.10000	2.49148	336.18990	911.68990	1.59041	2042.98500
1.516	-2.182	327.27510	1230.51251	526.82522	382.79740	101.20000	2.49147	336.29980	911.70000	1.60244	2043.02000
1.516	-1.210	327.44070	1230.67468	526.91312	382.82370	101.20000	2.49223	336.47000	911.72000	1.61447	2043.02000
1.517	-.211	326.85230	1230.51266	526.62450	382.62450	101.20000	2.49153	335.86990	911.75000	1.62279	2043.02000
1.516	.780	327.24760	1229.62074	526.47592	382.83030	101.20000	2.49064	336.26980	911.76000	1.63229	2043.02000
1.516	1.798	327.46240	1229.74875	526.55796	382.88210	101.20000	2.49129	336.49000	911.76000	1.64043	2043.05499
GRADIENT		.01510	-.15167	-.05623	.01809	.01802	-.00010	.01540	.01774	.01010	.01014

RUN NO.	1423/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.517	-8.074	327.25440	1232.27585	527.50146	382.49390	100.80000	2.49428	336.27980	911.50000	1.49776	2042.95000
1.517	-7.066	326.92900	1230.44621	526.74294	382.62990	100.90000	2.49428	335.93990	911.49000	1.48854	2042.95000
1.516	-6.081	327.59840	1231.04358	527.07769	382.76730	101.00000	2.49311	336.62990	911.60990	1.56962	2042.98500
1.516	-5.103	327.53960	1231.03636	527.06673	382.74220	101.00000	2.49313	336.56980	911.63990	1.57361	2042.98500
1.516	-4.124	327.23680	1230.60942	526.85612	382.73390	101.10000	2.49169	336.25980	911.65990	1.58212	2042.98500
1.517	-3.155	327.16850	1230.41487	526.77017	382.71730	101.10000	2.49148	336.18990	911.68990	1.59041	2042.98500
1.516	-2.182	327.27510	1230.51251	526.82522	382.79740	101.20000	2.49147	336.29980	911.70000	1.60244	2043.02000
1.516	-1.210	327.44070	1230.67468	526.91312	382.82370	101.20000	2.49223	336.47000	911.72000	1.61447	2043.02000
1.517	-.211	326.85230	1230.51266	526.62450	382.62450	101.20000	2.49153	335.86990	911.75000	1.62279	2043.02000
1.516	.780	327.24760	1229.62074	526.47592	382.83030	101.20000	2.49064	336.26980	911.76000	1.63229	2043.02000
1.516	1.798	327.46240	1229.74875	526.55796	382.88210	101.20000	2.49129	336.49000	911.76000	1.64043	2043.05499
GRADIENT		.01510	-.15167	-.05623	.01809	.01802	-.00010	.01540	.01774	.01010	.01014

RUN NO.	1411/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.542	-8.071	317.71660	1240.72643	529.10567	378.53030	100.70000	2.49517	326.56980	899.54980	1.34446	2042.63499
1.542	-7.065	317.5080	1240.30243	528.91355	378.49540	100.70000	2.49453	326.39990	899.53980	1.35533	2042.60001
1.542	-6.079	317.72580	1240.51018	529.02458	378.51980	100.70000	2.49545	326.57980	899.56980	1.36914	2042.60001
1.542	-5.097	317.90330	1240.07713	528.89433	378.62060	100.70000	2.49492	326.75980	899.56980	1.36966	2042.60001
1.542	-4.125	317.50150	1240.21788	528.87163	378.46660	100.70000	2.49469	326.34990	899.56980	1.36944	2042.60001
1.542	-3.153	317.59910	1240.33774	528.93536	378.49020	100.70000	2.49501	326.45000	899.56980	1.36932	2042.63499
1.542	-2.182	317.68700	1240.30534	528.9390	378.51930	100.70000	2.49515	326.53980	899.58980	1.37289	2042.63499
1.542	-1.210	317.62870	1240.39543	528.96349	378.44240	100.60000	2.49547	326.48000	899.59990	1.35873	2042.63499
1.542	-.213	317.60060	1240.09053	528.84240	378.45950	100.60000	2.49492	326.45000	899.58980	1.35907	2042.63499
1.543	.781	317.63790	1240.63477	529.05534	378.42920	100.60000	2.49579	326.49000	899.57980	1.35498	2042.63499
1.543	1.797	317.41360	1240.37192	528.91373	378.36380	100.60000	2.49527	326.5980	899.56980	1.36223	2042.63499
GRADIENT		-.01018	.03045	.00967	-.01784	-.02168	-.00011	-.01046	.00067	-.00231	.00376

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM032) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1352/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.599	-8.031	1252.84900	1597.30000	315.11790	522.14670	100.00000	2.49772	1262.60001	1299.85001
.600	-7.070	1252.73700	1597.30000	315.20920	521.85380	99.70000	2.49976	1262.49001	1299.84000
.600	-6.088	1252.13800	1597.28000	315.68410	521.97070	99.89999	2.50033	1261.89999	1299.82001
.600	-5.106	1251.82600	1596.64999	315.41090	521.99240	99.89999	2.49880	1261.58000	1299.83000
.601	-4.134	1251.60400	1597.55000	316.34860	521.8180	99.89999	2.50297	1261.38000	1299.78999
.601	-3.169	1251.48900	1597.23000	316.17410	521.89790	99.89999	2.50206	1261.25999	1299.80000
.601	-2.214	1251.48900	1597.25999	316.19970	521.80200	99.80000	2.50275	1261.25999	1299.75999
.601	-1.261	1251.01601	1596.98000	316.35130	521.71710	99.80000	2.50306	1260.78999	1299.72000
.601	-.285	1251.43300	1597.50999	316.45560	521.67870	99.70000	2.50446	1261.21001	1299.70000
.600	.713	1251.46839	1596.71001	315.75340	521.75760	99.70000	2.50124	1261.23000	1299.67999
.601	.751	1251.50600	1597.38000	316.28590	521.69950	99.70000	2.50374	1261.28000	1299.67999
GRADIENT	-.01347	-.04678	-.02830	-.03462	-.04009	.00009	-.01420	-.02297	-.00307

RUN NO. 1342/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1342/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.799	-8.047	880.97510	1342.07001	394.05810	496.87010	100.70000	2.49583	890.87990	1047.11000
.800	-7.036	880.62280	1341.98000	394.23140	496.82300	100.70000	2.49618	890.52980	1047.11000
.800	-6.046	880.16550	1342.17999	394.69020	496.81670	100.80000	2.49703	890.07980	1047.11000
.800	-5.059	880.42260	1341.88000	394.29350	496.80130	100.70000	2.49623	890.32980	1047.13000
.800	-4.081	880.12920	1341.89999	394.50760	496.84060	100.80000	2.49624	890.03980	1047.13000
.800	-3.109	879.99730	1341.94000	394.62670	496.72630	100.70000	2.49717	889.90990	1047.11000
.800	-2.144	880.30220	1341.80000	394.31590	496.87890	100.80000	2.49563	890.21000	1047.12000
.800	-1.182	880.34940	1342.03999	394.46170	496.86110	100.80000	2.49628	890.26000	1047.12000
.800	-.200	880.32200	1341.84000	394.33200	496.78930	100.70000	2.49629	890.23000	1047.14999
.800	.797	880.19700	1342.09000	394.60230	496.74270	100.70000	2.49727	890.10990	1047.13000
.800	1.824	880.49120	1342.00000	394.33540	496.88820	100.80000	2.49590	890.39990	1047.14999
GRADIENT	.05479	.023333	-.01997	.00320	-.00355	-.00001	.05460	.00474	-.00823

RUN NO. 1330/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1330/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.900	-8.078	753.04130	1273.19000	426.67800	482.12060	100.50000	2.49619	763.04980	977.59990
.900	-7.025	752.87600	1272.78000	426.49490	482.13480	100.50000	2.49528	762.87990	977.58980
.899	-6.037	753.10450	1273.00000	426.50980	482.15280	100.50000	2.49558	763.10990	977.57980
.900	-5.053	752.81250	1272.96001	426.65600	482.10380	100.50000	2.49586	762.81980	977.55980
.900	-4.082	752.58860	1273.14000	426.91310	482.04320	100.50000	2.49664	762.59990	977.53980
.900	-3.110	752.55790	1273.17000	426.95190	481.94820	100.40000	2.49734	762.56980	977.50980
.900	-2.146	752.47090	1272.89999	426.81810	481.96170	100.40000	2.49671	762.48000	977.51980
.900	-1.188	752.38090	1272.85001	426.83740	481.95040	100.40000	2.49670	762.38990	977.50000
.900	-.208	752.64940	1273.12000	426.86300	481.97050	100.40000	2.49670	762.65990	977.49000
.900	.783	752.77120	1273.03000	426.72880	482.00240	100.40000	2.49668	762.77980	977.49000
.899	1.810	753.28960	1272.72000	426.20700	482.13090	100.40000	2.49515	763.28980	977.48000
GRADIENT	.09986	-.04837	-.09270	.01414	-.01089	-.00020	.09844	-.00907	-.00174

SH10+3 PATM

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 902  
( VCM032 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO. 1321/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.099	-8.036	565.54030	1206.21001	478.25850	450.27490	99.39999	2.50281	575.73000	862.84990	.87374	2045.12000
-6.965	564.78830	1206.21001	478.55590	450.10380	99.39999	2.50317	574.98000	862.88990	.86899	2045.15500	
1.100	-5.978	564.59990	1206.03999	478.53150	450.07890	99.39999	2.50287	574.78980	862.88990	.86911	2045.15500
1.101	-4.983	564.45970	1206.02000	478.57520	450.04910	99.39999	2.50289	574.64990	862.91990	.86676	2045.15500
-3.997	564.64110	1205.92299	478.45090	450.10010	99.39999	2.50260	574.82980	862.95000	.86619	2045.12000	
1.100	-3.011	564.75340	1205.75999	478.30790	450.14380	99.39999	2.50215	574.93990	862.96000	.83442	2045.12000
-2.033	564.72120	1205.95000	478.43120	450.11620	99.39999	2.50260	574.90990	863.00000	.82974	2045.12000	
1.100	-1.052	564.81050	1206.02000	478.43680	450.12920	99.39999	2.50272	575.00000	863.01000	.82742	2045.12000
1.099	-.054	565.28100	1206.11000	478.30300	450.22660	99.39999	2.50271	575.47000	863.02980	.82736	2045.12000
1.100	.925	564.833370	1205.73000	478.25880	450.16530	99.39999	2.50205	575.01980	863.06980	.82085	2045.12000
1.100	1.921	565.04100	1206.03999	478.35720	450.17940	99.39999	2.50266	575.23000	863.04980	.82064	2045.12000
GRADIENT		.08103	.00314	-.03015	.01812	.00000	-.00003	.02086	-.00806	-.00710	-.00297

RUN NO. 1366/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.250	-8.037	462.43160	1198.25999	506.00220	426.98100	100.80000	2.49589	472.55980	904.41990	1.10330	2041.83000
-7.016	462.72140	1198.14999	505.88330	426.99240	100.70000	2.49630	472.84990	904.46000	1.10636	2041.83000	
1.250	-6.028	462.60350	1197.92000	505.79250	427.06080	100.80000	2.49523	472.73000	904.50000	1.11846	2041.83000
1.250	-5.043	462.46580	1197.62000	505.67070	427.05520	100.80000	2.49460	472.58980	904.53980	1.12472	2041.83000
-4.065	462.72070	1198.28000	505.94920	426.97900	100.70000	2.49656	472.84990	904.59990	1.13314	2041.79500	
1.250	-3.086	462.43090	1198.38000	506.06350	426.89230	100.70000	2.49673	472.55980	904.60990	1.13304	2041.79500
1.250	-2.115	462.50390	1197.92000	505.81450	427.03470	100.80000	2.49521	472.62990	904.65990	1.13954	2041.79500
1.250	-1.149	462.37380	1197.95000	505.85790	426.92110	100.70000	2.49584	472.50000	904.68990	1.14865	2041.79500
1.250	-.160	462.52420	1197.84000	505.79630	426.97190	100.70000	2.49564	472.64990	904.73000	1.15182	2041.79500
1.250	.833	462.62110	1198.23000	505.94560	426.95780	100.70000	2.49645	472.75000	904.76000	1.15451	2041.79500
1.250	1.859	462.60010	1198.41000	506.04150	427.01000	100.80000	2.49622	472.73000	904.80980	1.14821	2041.79500
GRADIENT		.00168	.00120	.00022	.00591	.00736	-.00004	.00175	.03629	.00363	.00001

RUN NO. 1377/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.400	-8.024	382.04930	1215.38000	523.99440	402.67480	100.80000	2.49486	391.75980	920.86990	1.29246	2041.69000
1.400	-7.012	381.74340	1215.21001	523.92600	402.52690	100.70000	2.49492	391.45000	920.88990	1.29447	2041.69000
1.400	-6.022	381.61720	1214.85001	523.77120	402.52290	100.70000	2.49417	391.31980	920.86990	1.30329	2041.69000
1.400	-5.035	381.60620	1215.00999	523.84130	402.50440	100.70000	2.49446	391.30980	920.90990	1.30311	2041.69000
1.400	-4.052	381.78170	1215.42999	524.02150	402.58960	100.80000	2.49476	391.49000	920.89990	1.30266	2041.69000
1.400	-3.074	381.94240	1215.05000	523.85200	402.67380	100.80000	2.49418	391.64990	920.91990	1.30650	2041.69000
1.400	-2.101	382.02000	1215.03000	523.84230	402.69360	100.80000	2.49419	391.71000	920.92990	1.30653	2041.65500
1.400	-1.133	381.79590	1214.73000	523.71510	402.65990	100.80000	2.49349	391.50000	920.91990	1.29999	2041.65500
1.400	-1.146	381.57890	1214.66000	523.68870	402.60110	100.80000	2.49321	391.27980	920.95000	1.30006	2041.65500
1.400	.846	382.03170	1215.00999	523.83280	402.70430	100.80000	2.49418	391.74000	920.92990	1.29627	2041.69000
1.400	1.876	382.15800	1215.34000	523.97460	402.71140	100.80000	2.49487	391.86990	920.93990	1.29592	2041.69000
GRADIENT		.03256	-.02501	-.01161	-.01215	.00000	-.00002	.03277	.00579	-.00171	.00006

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM032) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1389/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- 3.000	PHI =	180.000
P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
MACH	ALPHA								
1.450	-8.066	359.00020	1226.42000	528.35860	394.27660	100.40000	2.49766	368.48000	932.24000
1.451	-7.052	358.75340	1226.50999	528.38330	394.19090	100.40000	2.49759	368.23000	932.25980
1.450	-6.070	358.82640	1225.75000	528.07130	394.28370	100.40000	2.49632	368.29980	932.28828
1.450	-5.086	358.76540	1226.08000	528.20530	394.16380	100.30000	2.49744	368.24000	932.30980
1.450	-4.118	359.02880	1226.59000	528.43070	394.27000	100.40000	2.49799	368.50980	932.31980
1.449	-3.146	359.18020	1225.94000	528.16820	394.37720	100.40000	2.49699	368.65990	932.31980
1.450	-2.194	358.84470	1225.99001	528.17190	394.26730	100.40000	2.49676	368.31980	932.34990
1.450	-1.241	358.87480	1225.92000	528.14430	394.28320	100.40000	2.49667	368.34990	932.34990
1.450	-0.259	358.89550	1225.67999	528.04540	394.31180	100.40000	2.49626	368.36990	932.36990
1.450	.741	358.88530	1225.78999	528.09080	394.36890	100.50000	2.49585	368.35990	932.37990
1.450	1.777	358.88280	1226.23000	528.27370	394.32760	100.50000	2.49662	368.35990	932.39990
GRADIENT	- .03535	- .06024	- .02684	.00739	.01839	- .00025	- .03616	.01391	.00218

RUN NO.	1434/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM

RUN NO.	1401/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- 3.000	PHI =	180.000
P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
MACH	ALPHA								
1.470	-8.056	348.16940	1224.46062	526.83089	390.91260	101.20000	2.49143	357.50980	897.89990
1.471	-7.049	347.97220	1224.60152	526.87151	390.83910	101.20000	2.49141	357.30980	897.90990
1.471	-6.062	347.99950	1225.066670	527.06326	390.81100	101.20000	2.49215	357.33980	897.93990
1.471	-5.079	348.14770	1224.86563	526.99299	390.86740	101.20000	2.49213	357.49000	897.91990
1.471	-4.102	347.93120	1224.72664	526.91857	390.79610	101.20000	2.49194	357.26980	897.93990
1.470	-3.136	347.89380	1223.86473	526.56429	390.82230	101.20000	2.49117	357.23000	897.96000
1.470	-2.174	347.89380	1223.66068	526.48141	390.82320	101.20000	2.49116	357.23000	897.92990
1.470	-1.219	348.09940	1224.03310	526.64959	390.86910	101.20000	2.49175	357.43990	897.92990
1.471	- .238	348.01220	1224.37912	526.78407	390.86740	101.20000	2.49116	357.34990	897.96000
1.471	.757	347.95110	1224.80714	526.95312	390.81910	101.20000	2.49165	357.28980	897.96000
1.471	1.796	347.89210	1224.91472	526.99215	390.78910	101.20000	2.49179	357.23000	897.92990
GRADIENT	.00390	.11692	.04799	.00043	-.00000	-.00000	.00002	.00041	-.00003

RUN NO.	1401/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- 3.000	PHI =	180.000
P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
MACH	ALPHA								
1.496	-8.059	337.58500	1231.38820	528.54814	386.77510	101.20000	2.49320	346.77980	944.82980
1.496	-7.038	337.39140	1231.00095	528.37207	386.7250	101.20000	2.49183	346.57980	944.83980
1.495	-6.053	337.51930	1230.96274	528.37165	386.88870	101.30000	2.49128	346.71000	944.82980
1.496	-5.073	337.39140	1231.07962	528.40277	386.90770	101.40000	2.49069	346.57980	944.83980
1.495	-4.096	337.56930	1230.74661	528.29230	386.99000	101.40000	2.49044	346.75980	944.81980
1.495	-3.128	337.45210	1230.56424	528.20601	386.96680	101.40000	2.49001	346.63390	944.81980
1.495	-2.164	337.70390	1231.16425	528.47379	386.97440	101.40000	2.49173	346.89990	944.81980
1.495	-1.205	337.60570	1230.93706	528.37181	386.94310	101.40000	2.49160	346.72980	944.81980
1.496	-.224	337.35230	1230.86638	528.31379	386.90010	101.40000	2.49054	346.53980	944.80980
1.495	.773	337.47070	1230.52907	528.19381	386.95340	101.40000	2.49041	346.65990	944.78980
1.496	1.807	337.40160	1230.98567	528.36640	386.92430	101.40000	2.49044	346.58980	944.78980
GRADIENT	-.02989	.01268	.00136	-.01081	.00000	-.00002	-.03036	-.00041	-.000380

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 904  
( VCM032 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1424/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
1.515	-8.053	327.46220	1229.40977	526.42738	382.87940	101.20000	2.49134	336.49000	911.83980
1.515	-7.041	327.12790	1230.02098	526.61365	382.74220	101.20000	2.49140	336.14990	911.84990
1.516	-6.059	327.26540	1229.61417	526.47697	382.79860	101.20000	2.49137	336.28980	911.88990
1.516	-5.074	327.39400	1229.33678	526.38841	382.86790	101.20000	2.49104	336.41990	911.88990
1.516	-4.101	327.17800	1229.41861	526.38818	382.78610	101.20000	2.49095	336.20000	911.90990
1.516	-3.123	327.05000	1229.56921	526.42728	382.79660	101.30000	2.49047	336.06980	911.92990
1.516	-2.166	327.15670	1229.89676	526.57072	382.80960	101.30000	2.49104	336.17990	911.92990
1.515	-1.207	327.93260	1229.73721	526.62377	383.09670	101.30000	2.49149	336.97000	911.95000
1.515	-0.224	327.70750	1229.70679	526.57838	383.03300	101.30000	2.49099	336.74000	911.96000
1.516	.773	327.55980	1230.05742	526.69264	382.96700	101.30000	2.49112	336.58980	911.95000
1.515	1.808	327.67700	1230.15903	526.74886	382.99830	101.30000	2.49142	336.71000	911.97000
GRADIENT	.11087	.10970	.05895	.04338	.04338	.01086	.00010	.11314	.00590 .00251

RUN NO. 1412/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1412/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
1.543	-8.056	317.49150	1240.13612	528.83855	378.31590	100.50000	2.49610	326.33980	899.55980
1.543	-7.042	317.41360	1239.62502	528.622970	378.29980	100.50000	2.49580	326.25980	899.55980
1.542	-6.057	317.67720	1240.00752	528.82451	378.37840	100.50000	2.49638	326.52980	899.56980
1.542	-5.077	317.42330	1239.87207	528.72565	378.30570	100.50000	2.49577	326.26980	899.55980
1.543	-4.095	317.57890	1240.15558	528.86194	378.33540	100.50000	2.49642	326.42990	899.55980
1.542	-3.126	317.51100	1240.12903	528.83916	378.32350	100.50000	2.49612	326.35990	899.55980
1.542	-2.163	317.51120	1240.05699	528.81223	378.33500	100.50000	2.49590	326.35990	899.55980
1.542	-1.207	317.54170	1239.86261	528.74535	378.36770	100.50000	2.49552	326.38990	899.55980
1.542	-0.222	317.61010	1239.94534	528.78976	378.38920	100.50000	2.49565	326.46000	899.53980
1.543	.773	317.54960	1240.39809	528.94832	378.32280	100.50000	2.49643	326.39990	899.53980
1.542	1.807	317.66770	1239.67979	528.69792	378.38480	100.50000	2.49619	326.51980	899.54980
GRADIENT	.01628	-.03678	-.01089	.00731	-.00000	-.00001	.01654	-.00328	.00130 .00760

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 905

(VCM033) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1353/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.600	-8.033	1252.79601	1597.41000	315.25370	521.85030	99.70000	2.50001	1262.55000	1299.61000	.73906	2043.47501
.599	-7.035	1252.86501	1596.53000	314.45730	521.84740	99.59999	2.49694	1262.60001	1299.59000	.73947	2043.47501
.600	-6.043	1251.92999	1597.00999	315.62740	521.78470	99.70000	2.50103	1261.69000	1299.56000	.73924	2043.47501
.600	-5.061	1252.13699	1597.33000	315.72680	521.77930	99.70000	2.50166	1261.89999	1299.52000	.73909	2043.47501
.600	-4.086	1252.17000	1596.70000	315.17020	521.74880	99.59999	2.49968	1261.92000	1299.50999	.73739	2043.47501
.600	-3.118	1251.85100	1596.92000	315.61690	521.78370	99.70000	2.50092	1261.61000	1299.50000	.73531	2043.44000
.600	-2.166	1251.73599	1597.07001	315.83720	521.75590	99.70000	2.50184	1261.50000	1299.46001	.73326	2043.44000
.600	-1.241	1252.00301	1596.92999	315.50050	521.80080	99.70000	2.50050	1261.75999	1299.44000	.73332	2043.44000
.600	-2.298	1251.44901	1596.72000	315.77880	521.75440	99.70000	2.50133	1261.21001	1299.41000	.73342	2043.44000
.600	.705	1251.47400	1596.46001	315.53930	521.78170	99.70000	2.50025	1261.23000	1299.38000	.72174	2043.40500
.600	1.775	1251.46600	1596.87000	315.89060	521.74240	99.70000	2.50187	1261.23000	1299.34000	.72351	2043.40500
GRADIENT	-.11606	-.02740	-.07217	-.01098	-.01098	-.00018	-.11484	-.02956	-.00254	-.01038	-.00255

RUN NO. 1343/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.800	-8.015	880.599810	1342.28000	394.47000	496.87600	100.80000	2.49656	890.51000	1047.16000	.83116	2044.24500
.799	-7.008	880.76560	1341.89000	394.06740	496.85550	100.70000	2.49565	890.66990	1047.16000	.83140	2044.28000
.800	-6.016	880.29710	1342.14000	394.57130	496.84230	100.80000	2.49667	890.21000	1047.14999	.83125	2044.24500
.800	-5.030	880.39260	1341.85001	394.29170	496.71090	100.60000	2.49677	890.29980	1047.14000	.83368	2044.24500
.800	-4.045	880.09570	1342.10001	394.67850	496.72530	100.70000	2.49748	890.01000	1047.14000	.84033	2044.24500
.800	-3.070	880.18070	1341.84000	394.42820	496.76660	100.70000	2.49654	890.08980	1047.14999	.85889	2044.24500
.801	-2.112	879.88530	1342.02000	394.76250	496.69970	100.70000	2.49761	889.79980	1047.16000	.85183	2044.24500
.800	-1.170	880.56300	1341.94000	394.24240	496.72900	100.60000	2.49674	890.47000	1047.16000	.85419	21001
.800	-2.14	880.31760	1342.12000	394.54220	496.84770	100.80000	2.49657	890.23000	1047.12000	.85177	2044.21001
.800	.787	880.53660	1341.70000	394.08280	496.83860	100.70000	2.49549	890.43990	1047.14000	.85898	2044.21001
.800	1.842	880.17700	1342.07001	394.60080	496.74150	100.70000	2.49725	890.08980	1047.16000	.85411	2044.21001
GRADIENT	.04983	-.00971	-.00971	-.01223	-.01223	-.00360	-.00014	.04918	.00006	-.00151	-.00766

RUN NO. 1331/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.900	-8.041	752.811180	1273.03000	426.70460	482.00980	100.40000	2.49662	762.81980	977.43990	1.22410	2044.56000
.900	-6.998	753.06320	1273.05000	426.56860	482.05370	100.40000	2.49635	763.06980	977.42990	1.21165	2044.56000
.899	-6.007	753.03660	1272.78999	426.40580	481.99100	100.30000	2.49625	763.03980	977.41990	1.21149	2044.56000
.900	-5.020	752.74150	1273.00000	426.72580	482.00020	100.40000	2.49663	762.75000	977.40990	1.19541	2044.56000
.900	-4.043	752.69950	1273.13000	426.84030	481.89230	100.30000	2.49762	762.71000	977.37990	1.19214	2044.56000
.900	-3.068	752.49110	1272.86000	426.77830	481.96970	100.40000	2.49658	762.50000	977.39990	1.19239	2044.59500
.900	-2.108	752.62350	1272.78999	426.65160	481.91530	100.30000	2.49679	762.62990	977.37990	1.18304	2044.56000
.900	-1.172	752.56660	1273.24001	426.99460	481.94240	100.40000	2.49752	762.57980	977.37990	1.17950	2044.56000
.900	-.223	752.83740	1272.63000	426.41460	482.05790	100.40000	2.49550	762.83980	977.37990	1.19892	2044.56000
.900	.775	752.76880	1273.22000	426.86080	481.98140	100.40000	2.49720	762.77980	977.34990	1.19836	2044.56000
.900	1.830	752.77220	1272.97000	426.68700	482.00900	100.40000	2.49651	762.77980	977.34990	1.19860	2044.56000
GRADIENT	.03607	.00304	-.01938	-.01938	-.01886	.01886	-.00012	.03581	-.000702	.00174	-.00255

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM033) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1322/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- 2.000	PHI =	180.000
ALPHA	P	Q(PSF )	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.099	-8.010	565.53980	1206.28999	478.30540	450.34690	99.50000	2.50241	.81152	2045 12000
	-6.958	564.89040	1206.06000	478.42850	450.22360	99.50000	2.50219	.80724	2045 12000
1.100	-5.968	564.65160	1205.89999	478.42970	450.26660	99.59999	2.50135	.574.83980	.79197 2045 12000
1.101	-4.969	564.43070	1205.89999	478.51660	450.1630	99.59999	2.50146	.574.61990	.78116 2045 12000
1.100	-3.981	564.51150	1205.88000	478.47310	450.23680	99.59999	2.50137	.574.70000	.78548 2045 .08501
1.100	-2.981	564.75850	1206.20000	478.56180	450.25900	99.59999	2.50199	.574.95000	.863.20000
1.100	-2.024	564.77080	1206.00000	478.44070	450.28320	99.59999	2.50153	.574.96000	.863.21000
1.100	-1.048	564.89990	1206.11000	478.45360	450.30080	99.59999	2.50172	.575.08980	.863.25000
1.100	-.086	565.00340	1205.80000	478.23220	450.35740	99.59999	2.50096	.575.18990	.863.25000
1.100	.902	564.91210	1205.89000	478.32080	450.32710	99.59999	2.50121	.575.20000	.863.26980
1.100	1.929	565.01290	1205.85001	478.25780	450.35420	99.59999	2.50107	.575.20000	.83205 2045 .08501
GRADIENT	.08426	-.01672	-.04299	.02098	-.00000	-.00008	.08387	.01930	.00830 -.00173

RUN NO.	1367/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- 2.000	PHI =	180.000
ALPHA	P	Q(PSF )	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.249	-8.019	463.06960	1198.27000	505.86770	427.07180	100.70000	2.49658	.904.99000	1.17305 2041 79500
1.250	-6.997	462.44040	1198.42999	506.08640	426.96580	100.80000	2.49624	.905.02980	1.17602 2041 79500
1.250	-6.005	462.44430	1197.85001	505.79200	427.02610	100.80000	2.49506	.905.05980	1.17972 2041 79500
1.250	-5.012	462.27370	1198.00000	505.90500	426.88960	100.70000	2.49593	.905.09990	1.18271 2041 79500
1.250	-4.030	462.50200	1198.17000	505.94140	427.00850	100.80000	2.49572	.905.62290	1.18254 2041 79999
1.250	-3.054	462.40380	1198.95000	505.85130	427.00510	100.80000	2.49526	.905.15990	1.18276 2041 79500
1.250	-2.087	462.60350	1197.87000	505.76710	426.98970	100.70000	2.49571	.905.73000	1.18599 2041 795999
1.250	-1.140	462.73340	1197.85001	505.72850	427.02610	100.70000	2.49569	.905.85990	1.18601 2041 79999
1.250	-.178	462.64380	1197.86000	505.75340	427.07760	100.80000	2.49511	.905.76980	1.18285 2041 75999
1.250	.822	462.75020	1198.32001	505.96290	427.05880	100.80000	2.49606	.905.87990	1.18239 2041 72501
1.250	1.875	462.82150	1198.07001	505.82060	427.10300	100.80000	2.49556	.905.34990	1.18264 2041 690000
GRADIENT	.06175	-.01605	-.00541	.01751	-.00374	.00002	.06207	.03396	-.00013 -.01288

RUN NO.	1378/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- 2.000	PHI =	180.000
ALPHA	P	Q(PSF )	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.400	-8.013	381.99950	1215.38000	523.99540	402.80350	101.00000	2.49364	.391.71000	920.95000
1.400	-6.993	381.89400	1214.87000	523.77440	402.82010	101.00000	2.49264	.391.59990	920.95000
1.400	-6.001	381.60860	1214.64000	523.67970	402.68380	101.00000	2.49260	.391.30980	920.97000
1.400	-5.010	381.74410	1215.09000	523.87380	402.75390	101.00000	2.49293	.391.45000	920.98000
1.400	-4.026	381.84010	1215.60001	524.09470	402.73460	101.00000	2.49393	.391.54980	920.98000
1.400	-3.042	381.72510	1214.99001	523.83030	402.75780	101.00000	2.49273	.391.42990	920.99000
1.400	-2.080	381.70700	1214.70000	523.70390	402.77980	101.00000	2.49219	.391.40990	920.98000
1.400	-1.127	381.74320	1215.27000	523.95240	402.73660	101.00000	2.49326	.391.45000	920.99000
1.400	-.162	381.96000	1215.42000	524.01370	402.85960	101.10000	2.49310	.391.66990	920.98000
1.400	.834	381.84450	1214.78000	523.73610	402.88550	101.10000	2.49185	.391.54980	920.99000
1.400	1.888	381.76730	1214.53999	523.63260	402.88500	101.10000	2.49135	.391.47090	920.98000
GRADIENT	.00969	-.10636	-.04670	.02869	.02185	-.00032	.00917	-.00002	-.00443 -.01151

## PARAMETRIC DATA

RUN NO.	1390/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
ALPHA	-8.038	359.26680	1226.31000	528.32640	394.58150	100.70000	2.49594	368.75000	932.43990
	-7.021	358.96260	1226.09000	528.21950	394.43580	100.60000	2.49586	368.43990	932.46000
	-6.034	358.98410	1225.75000	528.07930	394.61470	100.80000	2.49409	368.46000	932.47000
	-5.045	359.05250	1225.86000	528.12840	394.62600	100.80000	2.49435	368.52980	932.49000
	-4.069	358.89380	1226.05000	528.19920	394.55880	100.80000	2.49453	368.36990	932.52980
	-3.100	358.92210	1226.25999	528.28810	394.47480	100.70000	2.49552	368.39990	932.51980
	-2.149	358.47900	1226.20000	528.24020	394.34420	100.70000	2.49500	367.95000	932.53980
	-1.218	359.12110	1225.95000	528.16940	394.56880	100.70000	2.49517	368.59990	932.55980
	-2.273	358.90450	1226.89000	528.13330	394.57690	100.80000	2.49426	368.37990	932.54980
	.733	358.76490	1226.19000	528.15330	394.50540	100.80000	2.49466	368.24000	932.54980
	1.801	359.21970	1225.89999	528.04076	394.67480	100.80000	2.49458	368.70000	932.58980
GRADIENT			- .03299	- .01164	.02362	.01109	-.00009	.04120	.00926
									.00318 -.01404

RUN NO. 1435/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1435/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
ALPHA	-8.037	347.92210	1225.12453	527.08053	390.80860	101.20000	2.49163	357.25980	897.91990
	-7.015	347.98120	1225.16272	527.10111	390.82500	101.20000	2.49175	357.31980	897.95000
	-6.025	347.84370	1224.97256	527.01247	390.79080	101.20000	2.49141	357.17990	897.92990
	-5.040	347.93240	1224.98633	527.02487	390.81930	101.20000	2.49151	357.26980	897.93990
	-4.062	347.77390	1224.96918	527.00468	390.75020	101.20000	2.49169	357.10990	897.96000
	-3.093	347.90840	1225.29735	527.16512	390.85180	101.20000	2.49208	357.43990	897.91990
	-2.138	347.84330	1225.31674	527.15272	390.78150	101.20000	2.49159	357.17990	897.92990
	-1.202	347.88260	1225.25175	527.12884	390.79520	101.20000	2.49161	357.22000	897.95000
	-253	347.88380	1224.87215	526.97506	390.81370	101.20000	2.49127	357.22000	897.92990
	.750	347.97170	1225.06427	527.06056	390.83310	101.20000	2.49157	357.30980	897.93990
	1.818	348.03980	1225.13448	527.09443	390.83540	101.20000	2.49197	357.37990	897.89990
GRADIENT			- .01476	- .00409	.00093	.00000	-.00002	.02208	-.00525 -.00020
									.00134 -.00020

RUN NO. 1402/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1402/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
ALPHA	-8.029	337.52830	1230.97888	528.37783	386.94560	101.40000	2.49098	346.72000	944.73000
	-7.011	337.49100	1230.78572	528.29830	386.89990	101.30000	2.49085	346.67990	944.75000
	-6.021	337.57740	1231.34279	528.52904	386.95610	101.40000	2.49114	346.76980	944.73000
	-5.036	337.56640	1231.68089	528.66269	386.93020	101.40000	2.49155	346.75980	944.72000
	-4.058	337.51880	1231.17789	528.45696	386.87770	101.30000	2.49148	346.71000	944.73000
	-3.086	337.59740	1231.47539	528.58470	386.90450	101.30000	2.49155	346.78980	944.72000
	-1.125	337.40190	1231.33864	528.50716	386.85910	101.30000	2.49097	346.58980	944.71000
	-1.191	337.37330	1231.21854	528.45629	386.86500	101.30000	2.49065	346.55980	944.70000
	-239	337.71360	1232.02591	528.81680	386.90670	101.30000	2.49237	346.90990	944.70000
	1.496	337.677530	1231.77824	528.71404	386.98100	101.40000	2.49139	346.86990	944.67990
	1.829	337.50980	1230.92393	528.35497	386.96260	101.40000	2.49052	346.70000	944.67990
GRADIENT			- .01674	.00849	.01680	.01851	-.00007	.01616	-.00002 -.00013
									.000883 -.000515

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM033) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.516	-8.029	327.53050	1230.17493	526.73329	382.95730	101.30000	2.49108	336.55980	912.00000	1.62335	2043.05499
1.516	-7.011	327.10770	1229.75471	526.50857	382.78860	101.30000	2.49106	336.12990	912.01000	1.66962	2043.02000
1.516	-6.023	327.14790	1229.54832	526.43398	382.82670	101.30000	2.49065	336.16990	912.01000	1.66570	2043.05499
1.516	-5.038	327.17800	1229.47041	526.40780	382.85520	101.30000	2.49033	336.20000	912.01000	1.65742	2043.05499
1.516	-4.059	327.30520	1229.82770	526.56528	382.88890	101.30000	2.49066	336.32980	912.01980	1.64029	2043.05499
1.517	-3.086	327.07790	1231.01840	526.99041	382.77340	101.30000	2.49112	336.09990	912.02980	1.58558	2043.09000
1.517	-2.130	327.21660	1230.95848	526.98767	382.84790	101.30000	2.49077	336.24000	912.05980	1.56967	2043.09000
1.517	-1.191	327.18920	1230.44855	526.78555	382.88960	101.30000	2.48977	336.21000	912.05980	1.56634	2043.09000
1.517	-0.239	327.09790	1231.33301	527.11443	382.78880	101.30000	2.49098	336.11990	912.04980	1.55725	2043.09000
1.516	.766	327.67630	1230.55476	526.90222	382.97880	101.30000	2.49178	336.71000	912.03980	1.61876	2043.09000
1.516	1.831	327.26610	1230.11763	526.67059	382.88210	101.30000	2.49050	336.28980	912.04980	1.61519	2043.05499
GRADIENT		.03519	.00885	.008859	.01216	.00000	.00004	.03590	.00362	-.00061	-.00012

RUN NO. 1425 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.542	-8.032	317.53080	1240.07906	528.82443	378.33980	100.50000	2.49596	326.37990	899.50000	1.38020	2042.70500
1.542	-7.010	317.55000	1239.70511	528.68557	378.33590	100.50000	2.49619	326.39990	899.48000	1.41287	2042.74001
1.542	-6.026	317.58810	1239.85161	528.74759	378.32670	100.50000	2.49667	326.43990	899.48000	1.41996	2042.70500
1.542	-5.037	317.45290	1239.32098	528.52205	378.32100	100.50000	2.49571	326.29980	899.51000	1.42421	2042.74001
1.542	-4.058	317.57010	1239.33235	528.54833	378.41890	100.60000	2.49545	326.41990	899.49000	1.43152	2042.74001
1.542	-3.085	317.57980	1239.28723	528.53328	378.42140	100.60000	2.49548	326.42990	899.48000	1.43524	2042.74001
1.542	-2.130	317.50150	1239.21027	528.48869	378.39550	100.60000	2.49536	326.34990	899.49000	1.43900	2042.74001
1.542	-1.192	317.71680	1239.14575	528.50449	378.53980	100.70000	2.49499	326.56980	899.48000	1.44280	2042.70500
1.542	-0.238	317.76660	1239.52524	528.65940	378.57320	100.70000	2.49475	326.61990	899.48000	1.40589	2042.74001
1.542	.765	317.46310	1239.38254	528.54749	378.46900	100.70000	2.49435	326.30980	899.47000	1.41323	2042.74001
1.542	1.828	317.66870	1239.41772	528.59982	378.54320	100.70000	2.49455	326.51980	899.46000	1.40961	2042.70500
GRADIENT		.01178	.02793	.01292	.02350	.02185	-.00020	.01185	-.00445	-.00524	-.00390

RUN NO. 1413 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 909

(VCMO34) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1354/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.600	-8.002	1252.55499	1597.25000	315.31690	521.83670	99.70000	2.50011	1262.31000	1299.28999	.73515	2043.40500
.599	-6.991	1252.25000	1596.31000	314.77730	521.88790	99.70000	2.49735	1261.99001	1299.28000	.73360	2043.40500
.600	-6.001	1252.22900	1596.81000	315.21460	521.83890	99.70000	2.49936	1261.98000	1299.27000	.73337	2043.40500
.600	-5.008	1251.98100	1597.00999	315.58570	521.79080	99.70000	2.50088	1261.74001	1299.27000	.73131	2043.40500
.600	-4.023	1251.94099	1597.44000	315.97950	521.74580	99.70000	2.50267	1261.71001	1299.24001	.73111	2043.40500
.600	-3.040	1251.43700	1596.81000	315.86430	521.74460	99.70000	2.50172	1261.20000	1299.22000	.73140	2043.40500
.601	-2.078	1251.44501	1596.91000	315.94170	521.73610	99.70000	2.50209	1261.21001	1299.20000	.72741	2043.37000
.600	-1.158	1251.41800	1596.71001	315.79520	521.75170	99.70000	2.50139	1261.17999	1299.19000	.72358	2043.40500
.601	-2.265	1251.44299	1597.00000	316.01880	521.72750	99.70000	2.50245	1261.21001	1299.16000	.71761	2043.40500
.600	-783	1251.53600	1597.91000	315.86670	521.74710	99.70000	2.50181	1261.30000	1299.13000	.71765	2043.37000
.601	1.859	1251.28101	1596.94000	316.00330	521.71390	99.70000	2.50269	1261.05000	1299.07001	.72153	2043.37000
GRADIENT	-.06612	-.04451	.01674	-.00371	.00000	.00000	-.06596	-.02708	-.00240	-.00528	

RUN NO. 1344/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.800	-7.965	880.63110	1342.11000	394.32180	496.81050	100.70000	2.49656	890.53980	1047.14999	.85640	2044.21001
.800	-6.981	880.57710	1342.33000	394.52120	496.86720	100.80000	2.49675	890.49000	1047.14000	.87260	2044.21001
.800	-5.989	880.13870	1341.95000	394.53810	496.83670	100.80000	2.49638	890.04980	1047.13000	.85419	2044.21001
.800	-4.995	880.21950	1341.92000	394.46090	496.85300	100.80000	2.49614	890.12990	1047.13000	.85190	2044.17500
.800	-4.002	879.99800	1341.88000	394.58180	496.82150	100.80000	2.49641	889.90990	1047.13000	.84503	2044.17500
.801	-3.015	879.97440	1342.13000	394.78300	496.70240	100.70000	2.49779	889.88990	1047.14000	.86103	2044.17500
.800	-2.045	880.06640	1342.06000	394.66890	496.72490	100.70000	2.49741	889.98000	1047.13000	.85875	2044.17500
.800	-1.108	880.45070	1342.02000	394.37790	496.79100	100.70000	2.49661	890.35990	1047.14000	.85877	2044.17500
.800	-.186	880.37940	1342.06000	394.45610	496.86400	100.80000	2.49628	890.28980	1047.14000	.85875	2044.14000
.800	.847	880.35130	1341.89999	394.35640	496.87620	100.80000	2.49585	890.26000	1047.16000	.85885	2044.14000
.800	1.903	880.79320	1342.06000	394.17430	496.84200	100.70000	2.49612	890.70000	1047.14000	.86340	2044.14000
GRADIENT	.09019	.01021	-.05377	.00894	-.00509	-.00010	.08944	.00278	.00175	-.00640	

RUN NO. 1332/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.900	-7.989	752.77000	1273.11000	426.78420	481.90750	100.30000	2.49747	762.77980	977.31980	1.16720	2044.56000
.900	-6.968	752.67460	1272.75000	426.59370	482.01510	100.40000	2.49604	762.67990	977.29980	1.16754	2044.52499
.900	-5.973	752.76930	1273.19000	426.83980	481.98490	100.40000	2.49712	762.77980	977.31980	1.17332	2044.56000
.900	-4.982	752.70020	1273.07001	426.79860	481.98510	100.40000	2.49688	762.71000	977.29980	1.19219	2044.56000
.900	-3.996	752.60910	1273.11000	426.88010	481.96410	100.40000	2.49711	762.61990	977.29980	1.19847	2044.56000
.900	-3.007	752.71970	1273.12000	426.82130	481.98320	100.40000	2.49699	762.73000	977.28980	1.19846	2044.56000
.900	-2.037	752.77220	1272.96001	426.67990	482.01030	100.40000	2.49648	762.77980	977.30980	1.19861	2044.52499
.900	-1.111	752.53980	1273.00999	426.85250	481.96220	100.40000	2.49692	762.54980	977.29980	1.17660	2044.52499
.900	-.199	752.77050	1273.08000	426.76340	481.99680	100.40000	2.49681	762.77980	977.28980	1.20166	2044.56000
.900	.834	752.90840	1273.31000	426.83940	482.08330	100.50000	2.49669	762.91990	977.27980	1.17321	2044.56000
.900	1.889	752.71190	1273.95000	426.70900	482.08640	100.50000	2.49596	762.72000	977.25980	1.17044	2044.52499
GRADIENT	.01826	.00076	-.01036	.01602	.01482	-.00011	.01814	-.00482	-.00359	-.000308	

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 910  
(VCM034) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1323/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-1.000	PHI ≈ 180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC
1.099	-7.980	565.4	1020	1206.20000	478.30420	450.40750	99.59999	575.59990
1.099	-6.950	564.92820	1206.25999	478.52980	450.37180	99.70000	2.50146	575.11990
1.100	-5.949	564.66110	1205.92299	478.44310	450.34620	99.70000	2.50083	574.84990
1.100	-4.954	564.70070	1206.00000	478.46850	450.34770	99.70000	2.50098	574.88990
1.100	-3.957	564.70210	1205.86000	478.38650	450.36300	99.70000	2.50065	574.88990
1.100	-2.963	564.93090	1206.00999	478.38330	450.47970	99.80000	2.50031	575.11990
1.100	-1.981	565.01050	1206.06000	478.38060	450.49240	99.80000	2.50038	575.20000
1.100	-1.020	564.83350	1205.75000	478.27050	450.48510	99.80000	2.49975	575.01980
1.100	-0.051	564.95090	1206.03000	478.38700	450.48190	99.80000	2.50034	575.13990
1.100	.940	564.96290	1205.86000	478.28340	450.58350	99.89999	2.49936	575.14990
1.100	1.963	564.86080	1206.00000	478.40500	450.54520	99.89999	2.49973	575.04980
1.100	GRADIENT	.02795	-.00293	-.01277	.03009	.02909	-.00019	.02784

RUN NO. 1368/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1368/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-1.000	PHI ≈ 180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC
1.250	-7.998	462.91800	1198.60001	506.06840	427.07450	100.80000	2.49665	473.04980
1.250	-6.973	462.41260	1198.10001	505.92530	426.91600	100.70000	2.49615	472.53980
1.250	-5.978	462.37280	1198.11000	505.93920	426.98070	100.80000	2.49558	472.50000
1.250	-4.986	462.23510	1197.85001	505.83760	426.97070	100.80000	2.49504	472.35990
1.250	-3.995	462.16650	1197.63000	505.74100	426.97510	100.80000	2.49458	472.28980
1.250	-3.005	462.65110	1198.24001	505.94430	427.04080	100.80000	2.49588	472.77980
1.250	-2.031	462.64230	1198.07001	505.8610	427.05590	100.80000	2.49554	472.76980
1.250	-1.091	462.37550	1197.10001	505.73610	427.02220	100.80000	2.49477	472.50000
1.250	-.153	462.75120	1198.19000	505.89700	426.91990	100.60000	2.49697	472.87990
1.250	-.881	462.64160	1198.14000	505.89550	426.97240	100.70000	2.49626	472.76980
1.250	1.923	462.35520	1197.73000	505.75050	426.86230	100.60000	2.49598	472.48000
1.250	GRADIENT	.03902	.01413	-.00138	-.01423	-.03032	.00021	.03927

RUN NO. 1380/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1380/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-1.000	PHI ≈ 180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC
1.400	-7.995	381.92260	1215.03000	523.84370	402.95700	101.20000	2.49177	391.62990
1.400	-6.970	381.88180	1215.23000	523.93210	402.92600	101.20000	2.49210	391.58980
1.400	-5.975	381.92260	1215.03999	523.84810	402.95630	101.20000	2.49179	391.62990
1.400	-4.984	381.74320	1215.25999	523.94800	402.88130	101.20000	2.49205	391.45000
1.400	-3.993	381.73750	1214.57001	523.64620	402.94480	101.20000	2.49079	391.43990
1.400	-3.001	381.78490	1214.92000	523.79860	402.92600	101.20000	2.49147	391.49000
1.400	-2.026	382.20920	1215.08000	523.85960	403.03880	101.20000	2.49207	391.91990
1.400	-1.080	382.00100	1215.14999	523.89480	402.96950	101.20000	2.49204	391.71000
1.400	-.137	381.68730	1214.72000	523.71290	402.91550	101.20000	2.49103	391.38990
1.400	.891	382.19040	1214.89999	523.78150	403.05030	101.20000	2.49173	391.89990
1.400	1.934	381.93480	1214.64999	523.67750	402.99680	101.20000	2.49109	391.63990
1.400	GRADIENT	.03792	-.03843	-.01756	-.01508	-.00000	.03810	.01782

	RUN NO.	RN/L =	PC	PREF	PHI ≈ 180.000	PATM		
MACH	ALPHA	P	TT(F)	RN/L	PC	PREF		
1.400	-7.980	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	-6.950	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	-5.949	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	-4.954	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	-3.957	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	-2.963	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	-1.981	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	-1.020	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	-.051	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	.940	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	1.963	381.8369	2045.08501	.833636	2045.08501	.833636		
1.400	GRADIENT	-.00431	-.00431	-.00017	-.00017	-.00340	-.00017	-.00217

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.450	-8.006	359.14820	1226.41000	528.36210	394.67600	100.90000	2.49481	368.62990	932.61990	1.29438	204.1.97000
1.450	-6.983	358.72580	1226.11000	528.21560	394.57080	100.90000	2.49389	368.20000	932.61990	1.29811	204.1.97000
1.450	-5.986	359.03200	1226.00999	528.18970	394.67630	100.90000	2.49400	368.50980	932.64990	1.29480	204.1.93500
1.450	-5.002	358.92410	1225.89999	528.13840	394.72290	101.00000	2.49311	368.39990	932.67990	1.29833	204.1.93500
1.450	-4.015	358.79640	1225.83000	528.10280	394.68920	101.00000	2.49287	368.26980	932.65990	1.30182	204.1.93500
1.449	-3.031	359.22900	1226.02000	528.20390	394.80760	101.00000	2.49361	368.71000	932.67990	1.29820	204.1.93500
1.450	-2.068	358.86500	1225.92999	528.14790	394.70140	101.00000	2.49311	368.33980	932.67990	1.30172	204.1.89999
1.450	-1.145	358.76660	1225.85001	528.10960	394.67800	101.00000	2.49287	368.24000	932.71000	1.30523	204.1.89999
1.450	-2.49	358.75560	1226.05000	528.19210	394.65620	101.00000	2.49321	368.23000	932.70000	1.29817	204.1.86501
1.450	.798	358.91500	1226.21001	528.27100	394.78590	101.10000	2.49312	368.47000	932.72000	1.29800	204.1.86501
1.450	1.868	358.63870	1225.78999	528.07790	394.71360	101.10000	2.49205	368.10990	932.73000	1.29845	204.1.86501
GRADIENT	-.03891	.01303	-.00342	-.00030	-.01866	-.00012	-.03936	-.01145	-.00052	-.01409	-.00070

RUN NO. 1436/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.471	-8.006	348.02030	1225.30246	527.16177	390.83670	101.20000	2.49181	357.35990	897.89990	1.24830	204.3.02000
1.471	-6.978	348.19680	1225.38457	527.20945	390.88230	101.20000	2.49220	357.53980	897.88990	1.25148	204.3.02000
1.471	-5.986	347.90330	1224.93738	527.00330	390.81980	101.20000	2.49129	357.24000	897.89990	1.25514	204.2.98500
1.471	-4.996	347.94430	1224.58487	526.86316	390.86670	101.20000	2.49069	357.27980	897.88990	1.25552	204.2.98500
1.471	-4.009	347.85210	1225.45648	527.21023	390.76000	101.20000	2.49206	357.18990	897.90990	1.25135	204.2.95000
1.471	-3.025	348.05960	1225.30481	527.16633	390.84370	101.20000	2.49195	357.39990	897.88990	1.25154	204.2.98500
1.471	-2.059	348.13720	1225.49167	527.24755	390.85230	101.20000	2.49235	357.48000	897.88990	1.25136	204.2.98500
1.470	-1.132	348.26660	1225.08658	527.09337	390.92190	101.20000	2.49194	357.60990	897.87990	1.25829	204.2.98500
1.471	-.228	347.76760	1224.45648	526.79655	390.81350	101.20000	2.49044	357.09990	897.88990	1.25887	204.2.98500
1.471	.818	347.84350	1224.94920	527.00285	390.78710	101.20000	2.49148	357.17990	897.86990	1.26162	204.2.98500
1.471	1.885	347.91210	1225.08986	527.06560	390.80270	101.20000	2.49168	357.25000	897.85990	1.25823	204.2.98500
GRADIENT	-.01210	-.02187	-.00997	-.00414	-.00000	-.00001	-.01225	-.00518	-.000120	.00120	.00214

RUN NO. 1403/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.495	-8.005	337.63600	1231.27087	528.50740	386.90010	101.30000	2.49192	346.82980	944.63990	1.19920	204.2.14500
1.496	-6.983	337.38160	1231.02840	528.38197	386.83540	101.30000	2.49127	346.56980	944.62990	1.19941	204.2.14500
1.495	-5.985	337.67700	1231.03090	528.41738	386.95460	101.30000	2.49119	346.86990	944.60990	1.18702	204.2.14500
1.495	-4.995	337.52050	1230.91937	528.35523	386.98020	101.40000	2.49026	346.71000	944.60990	1.18710	204.2.11000
1.496	-4.007	337.39160	1231.15999	528.43498	386.91410	101.40000	2.49057	346.57980	944.60990	1.18684	204.2.14500
1.495	-3.027	337.62620	1231.41805	528.56464	386.89700	101.30000	2.49191	346.81980	944.59990	1.18972	204.2.11000
1.496	-2.056	337.52660	1231.77040	528.69336	386.83470	101.30000	2.49235	346.72000	944.59990	1.18626	204.2.11000
1.496	-1.125	337.37180	1231.34245	528.50515	386.90380	101.40000	2.49061	346.55980	944.56980	1.17741	204.2.11000
1.496	-.215	337.35330	1231.19545	528.4505	386.92020	101.40000	2.49017	346.53980	944.56980	1.17142	204.2.11000
1.496	.831	337.59670	1231.70737	528.67641	386.88720	101.30000	2.49187	346.78980	944.52980	1.17096	204.2.11000
1.496	1.895	337.50050	1231.05241	528.40486	386.89670	101.30000	2.49098	346.68990	944.50980	1.18387	204.2.11000
GRADIENT	-.00067	.03124	-.01229	-.00717	-.00103	-.00006	-.00070	-.01499	-.000070	-.00198	-.00213

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 912  
( VCM034 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1426/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- 1.000	PHI =	180.000
<b>MACH</b>	<b>P</b>	<b>PT</b>	<b>Q(PSF)</b>	<b>T(R)</b>	<b>TT(F)</b>	<b>RN/L</b>	<b>PC</b>	<b>PREF</b>	<b>SH10+3</b>	<b>PATM</b>
1.517	-8.000	327.30350	1230.98653	527.01314	382.84890	101.30000	2.49141	336.32980	912.06980	1.58968 2043.05499
-6.983	327.25610	1230.95325	526.99160	382.87260	101.30000	2.49060	336.27980	912.05980	1.56173 2043.05499	
1.517	-5.985	327.26660	1230.81790	526.93998	382.89360	101.30000	2.49028	336.28980	912.06980	1.55794 2043.02000
1.517	-4.996	327.13890	1230.97719	526.98308	382.84030	101.30000	2.49032	336.15990	912.06980	1.55376 2043.02000
-4.008	327.21530	1231.46375	527.182300	382.82300	101.30000	2.49123	336.24000	912.09990	1.55315 2043.02000	
1.516	-3.022	327.52050	1231.12135	527.09665	382.95390	101.30000	2.49107	336.54980	912.09990	1.55759 2043.02000
1.517	-2.055	327.19800	1231.04158	527.01670	382.86520	101.30000	2.49029	336.22000	912.10990	1.54581 2043.05499
-1.125	327.14920	1230.63852	526.85315	382.85890	101.30000	2.49005	336.16990	912.09990	1.56609 2043.05499	
1.517	-2.215	327.67580	1231.36476	527.21390	382.96970	101.30000	2.49195	336.71000	912.10990	1.56921 2043.05499
1.516	.830	327.51170	1231.11790	527.09323	382.97190	101.30000	2.49066	336.53980	912.11990	1.54183 2043.05499
1.516	1.895	327.14890	1231.25531	527.09128	382.84990	101.30000	2.49021	336.16990	912.11990	1.52988 2043.05499
1.517	GRADIENT	.02303	.00675	.00596	.0.01016	-.000000	-.00002	.02338	.00516	-.00214 .00638

RUN NO. 1414/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1414/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	- 1.000	PHI =	180.000
<b>MACH</b>	<b>P</b>	<b>PT</b>	<b>Q(PSF)</b>	<b>T(R)</b>	<b>TT(F)</b>	<b>RN/L</b>	<b>PC</b>	<b>PREF</b>	<b>SH10+3</b>	<b>PATM</b>
1.542	-8.004	317.57980	1239.64134	528.66721	378.55470	100.80000	2.49432	326.42990	899.47000	1.41295 2042.77499
-6.982	317.58010	1239.50563	528.61584	378.56690	100.80000	2.49409	326.42990	899.46000	1.41311 2042.77499	
1.542	-5.990	317.65820	1240.31683	528.93900	378.65770	100.90000	2.49366	326.50980	899.47000	1.36232 2042.77499
1.542	-4.995	317.47240	1240.37970	528.92753	378.59620	100.90000	2.49338	326.31980	899.47000	1.35524 2042.77499
1.543	-4.008	317.67870	1240.29909	528.93640	378.68530	100.90000	2.49330	326.52980	899.46000	1.34840 2042.77499
1.543	-3.022	317.45190	1240.75554	529.06632	378.63260	101.00000	2.49321	326.29980	899.46000	1.34786 2042.77499
1.542	-2.055	317.68750	1240.40326	528.97711	378.73270	101.00000	2.49316	326.53980	899.45000	1.35873 2042.74001
1.542	-1.125	317.66770	1240.61847	529.05562	378.72070	101.00000	2.49323	326.51980	899.43990	1.34804 2042.74001
1.543	-.215	317.65840	1240.71530	529.09073	378.73220	101.00000	2.49294	326.50980	899.45000	1.33068 2042.77499
1.543	.829	317.54100	1240.74872	529.08153	378.75540	101.10000	2.49226	326.38990	899.42990	1.33063 2042.77499
1.554	1.896	317.61910	1260.76811	536.73707	378.77930	101.10000	2.49241	326.47000	899.41990	0.00000 2042.81000
GRADIENT	.01133	1.81096	.69335	.02347	.0.02945	-.00016	-.01162	-.00666	-.00214	-.12031 .00517

1A310 (AEDC 16TE-783) EATING-OFF DATABASE

1A310 (AEDC 16TE-783) EATING-OFF DATABASE

1A310 (AEDC 16TE-783) EATING-OFF DATABASE

PARAMETRIC DATA

BETA =

	CH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
59.9	-7.963	1253.	16701	1597.14000	314.72220	521.91970	99.70000	2.49785	1262.91000	1299.06000	-71368	2043.3350
60.0	-6.956	1252.	62199	1597.46001	315.43850	521.82500	99.70000	2.50073	1262.38000	1299.03999	-71353	2043.3350
60.0	-5.955	1251.	82300	1596.78000	315.52200	521.88670	99.80000	2.49988	1261.58000	1299.02000	-71384	2043.3350
60.0	-4.953	1251.	88100	1596.92000	315.59180	521.78710	99.70000	2.50083	1261.64000	1299.02000	-71377	2043.3350
60.0	-3.951	1251.	24001	1596.97000	316.15970	521.79960	99.80000	2.50236	1261.09999	1298.98000	-70416	2043.30000
60.0	-2.948	1251.	64700	1596.97000	315.82670	521.84790	99.80000	2.50115	1261.41000	1298.94000	-70798	2043.30000
60.0	-1.942	1251.	51700	1597.34000	316.24370	521.79790	99.80000	2.50298	1261.28999	1298.92999	-70973	2043.30000
60.1	-922	1251.	67799	1597.39999	316.16190	521.81150	99.80000	2.50273	1261.45000	1298.92999	-71937	2043.26500
60.0	.192	1252.	14600	1596.89000	315.34990	521.82150	99.70000	2.49992	1261.89999	1298.27000	-69660	2043.1950
60.0	.869	1252.	04201	1597.00999	315.53610	521.79790	99.70000	2.50070	1261.80000	1298.24001	-70223	2043.1950
60.0	.206	1251.	94200	1596.92999	315.55050	521.79350	99.70000	2.50069	1261.70000	1298.22000	-70417	2043.1950
GRADIENT	.07357			.00113	-.05934	-.00025	-.00053	-.000016	.07242	-.13569	-.00123	-.0223

RUN NO. 1345 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	R/N/L	PC	PREF	SH10+3	PATM
-8.800	-7 .968	880 .69920	1342 .25000	394 .37890	496 .80660	100 .70000	2 .49686	890 .60990	1047 .16000	.86561	2044 .14000
-8.800	-6 .952	880 .35820	1342 .11000	394 .50760	496 .76660	100 .70000	2 .49705	890 .26980	1047 .16000	.86104	2044 .10500
-8.800	-5 .951	880 .55270	1341 .94000	394 .24930	496 .81590	100 .70000	2 .49618	890 .46000	1047 .12000	.85650	2044 .10500
-8.800	-4 .950	880 .24800	1342 .06000	394 .54520	496 .84280	100 .80000	2 .49652	890 .15990	1047 .16000	.85643	2044 .10500
-8.800	-3 .955	880 .15770	1342 .03000	394 .58450	496 .83130	100 .80000	2 .49659	890 .06980	1047 .14000	.85413	2044 .10500
-8.800	-2 .948	879 .97710	1341 .92999	394 .63310	496 .81270	100 .80000	2 .49660	889 .88990	1047 .14999	.84272	2044 .10500
-8.800	-1 .946	880 .17940	1341 .91000	394 .48070	496 .84770	100 .80000	2 .49618	890 .08980	1047 .14000	.84273	2044 .07001
-8.800	-.933	880 .20950	1341 .92999	394 .47510	496 .85030	100 .80000	2 .49619	890 .11990	1047 .12000	.84044	2044 .10500
-8.800	.919	880 .34030	1341 .94000	394 .939360	496 .78170	100 .70000	2 .49656	890 .25000	1047 .09000	.85834	2043 .96500
-8.800	1 .009	880 .65260	1342 .00999	394 .232290	496 .91330	100 .80000	2 .49565	890 .55980	1047 .09000	.86343	2043 .92999
-7.799	2 .003	880 .74630	1341 .83000	394 .03610	496 .94750	100 .80000	2 .49493	890 .64990	1047 .07001	.86355	2043 .96500
GRADIENT	.08461	-.01996	-.07233	.01259	-.00358	-.00019	.08351	-.01293	-.00168	-.02676	

RUN NO. 1333 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

CH	ALPHA	$\rho$	$\rho_1$	$\rho_{PSF}$	T(R)	T(F)	RN/L	PC	PREF	PATM	SH10+3
-7.900	-7.958	752.95040	1273.19000	426.73190	482.16090	100.60000	2.49553	762.96000	977.25980	1.14874	2044.52499
-6.900	-6.922	752.66160	1272.97000	426.75290	482.16090	100.60000	2.49551	762.66990	977.27980	1.14286	2044.52499
-5.900	-5.938	752.98540	1272.86000	426.48460	482.23220	100.60000	2.49478	762.99000	977.26980	1.13390	2044.52499
-4.900	-4.939	752.89790	1273.33000	426.85940	482.16530	100.60000	2.49618	762.90990	977.27980	1.13048	2044.52499
-3.900	-3.940	752.80740	1273.34000	426.92040	482.14770	100.60000	2.49632	762.81980	977.26980	1.12151	2044.49001
-2.900	-2.935	752.81300	1272.92000	426.62820	482.19410	100.60000	2.49517	762.81980	977.26980	1.11594	2044.49001
-1.900	-1.929	752.57960	1273.03999	426.82940	482.13840	100.60000	2.49580	762.85980	977.26980	1.10992	2044.52499
-0.900	-0.918	752.85030	1273.14000	426.75730	482.17720	100.60000	2.49572	762.85900	977.25980	1.11572	2044.49001
GRADIENT	-0.03205	-	-0.06756	-	0.02737	0.0145	-	0.00014	-	0.00408	0.00249

DATE 04 OCT 91

IA310 (AEDC 16TF~783) TABULATED DATA

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 914  
(VCM035) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	PREF	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC
1.100	-7.946	565.12080	1206.07001	478.34300	450.43600	99.70000	2.50094	575.30980	863.55980	.81167	2045.08501																												
1.100	-6.933	564.73170	1205.91000	478.40380	450.60600	100.00000	2.49900	574.91990	863.55980	.81178	2045.08501																												
1.100	-5.936	564.72270	1205.80000	478.34330	450.61570	100.00000	2.49876	574.90990	863.57980	.80963	2045.05000																												
1.100	-4.941	564.56050	1205.95000	478.49460	450.32100	99.70000	2.50093	574.75000	863.58980	.81175	2045.08501																												
1.100	-3.935	564.02980	1205.13000	478.41380	450.40890	99.70000	2.50112	575.22000	863.62990	.77033	2045.08501																												
1.100	-2.935	564.56980	1206.03000	478.53740	450.39530	99.80000	2.50052	574.76000	863.65990	.80726	2045.08501																												
1.100	-1.940	564.85110	1205.97000	478.39140	450.54610	99.89999	2.49967	575.03980	863.64990	.80508	2045.08501																												
1.100	-.936	564.95240	1205.89000	478.30490	450.49730	99.80000	2.50002	575.13990	863.66990	.80735	2045.08501																												
1.100	.059	565.00420	1205.74001	478.19700	450.68630	100.00000	2.49848	575.18990	863.67990	.79644	2045.05000																												
1.100	.985	564.90920	1206.17000	478.48490	450.61870	100.00000	2.49952	575.09990	863.72000	.79397	2045.05000																												
1.100	2.007	564.71040	1206.00000	478.46440	450.51100	99.89999	2.49980	574.89990	863.74000	.79409	2045.05000																												
	GRADIENT	.02244	-.00518	-.01188	.03859	.04087	-.00026	.02229	.01899	-.00042	-.00630																												

RUN NO.	1324/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	PREF	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC
MACH	ALPHA	P	PT	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	PREF	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC			
1.250	-7.973	462.88040	1198.24001	505.89400	426.94900	100.60000	2.49709	473.00980	903.83980	1.23700	2041.72501																										
1.250	-6.948	462.59180	1198.14999	505.91160	426.88210	100.60000	2.49887	472.72000	903.88990	1.23709	2041.72501																										
1.250	-5.950	462.54370	1197.91000	505.89300	426.89380	100.60000	2.49637	472.66990	903.95000	1.23734	2041.72501																										
1.250	-4.947	462.27510	1197.82001	505.81370	426.83200	100.60000	2.49615	472.39990	904.01980	1.23744	2041.72501																										
1.250	-3.951	462.19510	1197.85001	505.84640	426.80790	100.60000	2.49621	472.31980	904.05980	1.24069	2041.72501																										
1.250	-2.948	462.68140	1198.19000	505.91240	426.97780	100.70000	2.49637	472.80980	904.09990	1.24033	2041.75999																										
1.250	-1.946	462.55150	1198.22000	505.95580	426.94040	100.70000	2.49642	472.67990	904.13990	1.23702	2041.75999																										
1.250	-.941	462.40450	1197.83000	505.79030	426.94140	100.70000	2.49560	472.52980	904.17990	1.23415	2041.75999																										
1.250	-.074	462.50270	1198.06000	505.88550	426.94380	100.70000	2.49608	472.62990	904.37990	1.21446	2041.79500																										
1.250	.987	462.66280	1197.96001	505.79960	427.07250	100.80000	2.49531	472.78980	904.40990	1.20814	2041.79500																										
1.249	2.026	462.90090	1198.14000	505.83890	427.11690	100.80000	2.49571	473.02980	904.47000	1.20156	2041.75999																										
	GRADIENT	.07294	.02424	-.00370	.03883	.02895	-.00011	.07335	.06931	-.00592	.00833																										

RUN NO.	1381/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	PREF	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC
MACH	ALPHA	P	PT	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	PREF	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC	TT(F)	T(R)	Q(PSF)	RN/L	PC			
1.400	-7.977	381.70530	1214.96001	523.81740	402.97020	101.30000	2.49089	391.40990	920.39990	1.21350	2041.51500																										
1.400	-6.948	381.71730	1214.64000	523.67720	403.00420	101.30000	2.49032	391.41990	920.38990	1.21061	2041.51500																										
1.400	-5.951	381.72220	1215.49001	524.04880	402.92500	101.30000	2.49187	391.42990	920.39990	1.20976	2041.51500																										
1.400	-4.954	381.92270	1214.89000	523.78100	403.06350	101.30000	2.49097	391.70000	920.43990	1.20716	2041.51500																										
1.400	-3.952	381.81540	1214.75999	523.72780	403.02220	101.30000	2.49061	391.51980	920.43990	1.21692	2041.51500																										
1.400	-2.954	381.51860	1214.78000	523.74240	402.93090	101.30000	2.49042	391.22000	920.43990	1.21368	2041.51500																										
1.401	-1.948	381.65330	1215.39999	524.01100	402.91260	101.30000	2.49165	391.35990	920.43990	1.20665	2041.55000																										
1.400	-.948	381.92360	1214.88000	523.77830	403.04350	101.30000	2.49090	391.62990	920.45000	1.20717	2041.55000																										

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM035) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1392/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.450	-7.974	358.80570	1225.91000	528.13650	394.82540	101.20000	2.49183	368.27980	932.76980	1.30174 204.1 .83000
1.450	-6.945	358.85470	1225.99001	528.17240	394.83350	101.20000	2.49202	368.32980	932.77980	1.30852 204.1 .83000
1.450	-5.947	358.62870	1225.85001	528.10250	394.77540	101.20000	2.49156	368.46000	932.77980	1.31211 204.1 .83000
1.449	-4.945	359.07250	1225.78999	528.10030	394.92040	101.20000	2.49187	368.54980	932.78980	1.32256 204.1 .79500
1.450	-3.946	358.79540	1225.98000	528.16500	394.81590	101.20000	2.49194	368.26980	932.80980	1.32932 204.1 .79500
1.450	-2.942	359.08150	1225.97000	528.17550	394.97710	101.30000	2.49160	368.55980	932.83980	1.33633 204.1 .79500
1.450	-1.938	358.95070	1226.47000	528.37670	394.89010	101.30000	2.49236	368.42990	932.82980	1.33229 204.1 .79500
1.450	-9.20	358.80540	1225.99001	528.16990	394.88840	101.30000	2.49138	368.27980	932.84990	1.33631 204.1 .83000
1.450	-0.95	358.71660	1226.00999	528.17360	394.78830	101.20000	2.49192	368.18990	933.06980	1.36462 204.1 .89999
1.450	.993	358.9270	1225.96001	528.16700	394.80930	101.10000	2.49269	368.47000	933.07980	1.36826 204.1 .93500
1.449	2.018	359.34550	1226.38000	528.35940	394.88130	101.10000	2.49376	368.82980	933.08980	1.36779 204.1 .89999
GRADIENT		.02067	.04484	.01971	-.01025	-.01789	.00020	-.02121	.04970	.00718 .02132

RUN NO. 1437/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATE
1.471	-7.972	347.92210	1225.03325	527.04326	390.81150	101.20000	2.49158	357.25980	897.85990	1.25829 204.3 .05499
1.471	-6.943	347.87210	1225.41472	527.19437	390.77640	101.20000	2.49189	357.21000	897.84990	1.24816 204.3 .05499
1.471	-5.951	347.86350	1225.16141	527.09099	390.79710	101.20000	2.49143	357.20000	897.85990	1.24843 204.3 .02000
1.471	-4.948	347.87330	1225.20526	527.10966	390.80220	101.20000	2.49141	357.21000	897.83980	1.24515 204.3 .02000
1.471	-3.946	348.08910	1225.37518	527.19572	390.84580	101.20000	2.49188	357.42990	897.84990	1.24501 204.3 .05499
1.471	-2.942	348.11770	1225.61218	527.29603	390.84590	101.20000	2.49232	357.46000	897.82980	1.24477 204.3 .05499
1.471	-1.944	347.95260	1224.92561	527.00247	390.83760	101.20000	2.49130	357.28980	897.83980	1.25516 204.3 .05499
1.471	-.923	347.97340	1224.67258	526.90076	390.86230	101.20000	2.49098	357.30980	897.82980	1.25868 204.3 .05499
1.471	-.078	347.91530	1224.58430	526.86132	390.86280	101.20000	2.49056	357.25000	897.79980	1.25227 204.3 .05499
1.471	1.009	347.94260	1224.99588	527.02989	390.83350	101.20000	2.49131	357.27980	897.77980	1.25184 204.3 .05499
1.471	2.019	348.01030	1225.27768	527.15107	390.82980	101.20000	2.49187	357.34990	897.76000	1.25156 204.3 .02000
GRADIENT		-.00412	-.056608	-.02312	-.00170	-.000000	-.00006	-.000437	-.01211	-.00002 -.00002

RUN NO. 1404/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATE
1.496	-7.973	337.46120	1231.31944	528.50665	386.88570	101.30000	2.49090	346.64990	944.47000	1.16521 204.2 .11000
1.496	-6.944	337.42110	1231.49640	528.57200	386.85550	101.30000	2.49118	346.60990	944.45000	1.16503 204.2 .14500
1.496	-5.947	337.44970	1231.70358	528.65714	386.85080	101.30000	2.49148	346.63990	944.46000	1.16180 204.2 .11000
1.496	-4.949	337.45870	1231.84981	528.71610	386.83590	101.30000	2.49183	346.64990	944.43990	1.16470 204.2 .11000
1.496	-3.947	337.42940	1231.83543	528.70730	386.82710	101.30000	2.49178	346.61990	944.45000	1.16470 204.2 .14500
1.495	-2.944	337.65700	1231.37792	528.55382	386.93820	101.30000	2.49135	346.84990	944.43990	1.17129 204.2 .14500
1.496	-1.941	337.49020	1231.05954	528.40672	386.88820	101.30000	2.49107	346.67990	944.42990	1.18696 204.2 .14500
1.496	-.935	337.44020	1231.32298	528.50555	386.85110	101.30000	2.49141	346.62990	944.40990	1.18360 204.2 .14500
1.496	-.063	337.49070	1231.20786	528.46558	386.89720	101.30000	2.49090	346.67990	944.05980	1.17143 204.2 .21500
1.496	1.124	337.61650	1231.72060	528.68456	386.89720	101.30000	2.49183	346.80980	944.05980	1.16789 204.2 .21500
1.496	2.030	337.52690	1232.01520	528.79011	386.84400	101.30000	2.49218	346.72000	944.04980	1.16454 204.2 .21500
GRADIENT		.01053	.00479	.00320	.00294	.00000	.00002	.01073	-.01211	.00015 .01537

## PARAMETRIC DATA

RUN NO. 1427/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.517	-7.973	327.07010	1231.38066	527.12749	382.81640	101.30000	2.49025	336.08980	912.11990	1.52582 2043.05499
-6.944	327.04000	1231.48546	527.16379	382.79150	101.30000	2.49049	336.05980	912.09990	1.52957 2043.02000	
1.517	-5.948	327.24460	1231.75533	527.29995	382.83280	101.30000	2.49127	336.26980	912.11990	1.53116 2043.02000
1.517	-4.950	327.04960	1231.81119	527.29111	382.78590	101.30000	2.49067	336.06980	912.09990	1.51366 2043.02000
-3.948	327.33500	1231.59142	527.24892	382.740940	101.30000	2.49050	336.35990	912.10990	1.51012 2043.02000	
-2.945	326.99220	1231.62262	527.20875	382.79830	101.30000	2.49000	336.00980	912.11990	1.50235 2043.05499	
1.518	-1.942	327.58740	1232.48987	527.63541	382.93580	101.30000	2.49192	336.61990	912.11990	1.49373 2043.05499
1.517	-9.28	327.60890	1231.96669	527.43531	382.99050	101.30000	2.49105	336.63990	912.10990	1.49438 2043.05499
1.517	-1.15	327.11080	1231.56177	527.20322	382.85990	101.30000	2.48973	336.12990	912.10990	1.49099 2043.05499
1.517	.978	327.36230	1232.36458	527.55298	382.86940	101.30000	2.49147	336.38990	912.09990	1.49385 2043.05499
1.517	2.017	327.24630	1231.96808	527.38049	382.87010	101.30000	2.49057	336.26980	912.09990	1.49051 2043.05499
GRADIENT		.02391	.05273	.02397	.00783	-.00000	.00003	.02441	-.00109	-.00334 .00508

RUN NO. 1416/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.543	-7.971	317.59010	1240.46677	528.98377	379.11670	101.60000	2.48921	326.43990	899.65990	1.34473 2042.91499
-6.949	317.50500	1240.65067	529.04569	379.02370	101.50000	2.48998	326.39990	899.70000	1.34106 2042.91499	
1.543	-5.946	317.47240	1240.51520	528.97447	379.06620	101.60000	2.48924	326.31980	899.72000	1.34813 2042.88000
1.543	-4.944	317.57910	1240.84894	529.12578	379.08370	101.60000	2.48975	326.42990	899.73000	1.34085 2042.88000
-3.948	317.51120	1240.48657	528.97554	379.07790	101.60000	2.48933	326.35990	899.76000	1.35164 2042.88000	
1.543	-2.945	317.61870	1240.54483	529.01749	379.17330	101.70000	2.48905	326.47000	899.76000	1.35507 2042.91499
1.543	-1.942	317.41280	1240.76463	529.06229	379.16280	101.80000	2.48832	326.25980	899.76980	1.34438 2042.91499
1.543	-.927	317.46310	1240.20833	528.86114	379.14360	101.70000	2.48839	326.30980	899.78980	1.35892 2042.91499
1.543	-.116	317.69700	1241.10374	529.24535	379.20260	101.70000	2.48911	326.54980	899.80980	1.31661 2042.88000
1.543	1.001	317.32590	1240.92372	529.10688	379.09250	101.70000	2.48828	326.16990	899.81980	1.31336 2042.88000
1.542	2.012	317.65890	1240.50348	529.01046	379.14720	101.60000	2.48917	326.50980	899.81980	1.33779 2042.84500
GRADIENT		-.00159	.00870	.00313	.00693	.00485	-.00011	-.00183	.01319	-.00369 -.00417

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 917

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM036) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.900	-7.9358	752.88130	1273.08000	426.69750	481.50070	99.80000	2.50013	762.88990	977.46000	1.00824	2044.31500
.900	-6.937	752.73560	1272.76000	426.52320	481.42920	99.70000	2.49986	762.74000	977.47000	1.00315	2044.28000
.900	-5.938	752.79440	1272.81000	426.56370	481.51420	99.80000	2.49950	762.79980	977.50980	1.00307	2044.28000
.900	-4.934	752.97970	1273.25999	426.76270	481.49930	99.80000	2.50049	762.99000	977.52980	1.00271	2044.24500
.900	-3.935	752.73850	1273.24001	426.89260	481.54350	99.89999	2.50018	762.75000	977.54980	1.00273	2044.24500
.900	-2.935	752.66890	1273.14999	426.87210	481.45430	99.80000	2.50060	762.67990	977.56980	1.01089	2044.24500
.900	-1.929	753.02420	1272.97000	426.53710	481.53880	99.80000	2.49964	763.02980	977.58980	1.03567	2044.28000
.900	-918	752.45950	1273.00000	426.89360	481.51830	99.89999	2.49989	762.47000	977.59990	1.03842	2044.24500
.900	.038	753.06130	1273.19000	426.66600	482.21040	100.60000	2.49558	763.06980	977.77980	1.01357	2044.24500
.900	.980	752.93070	1273.17999	426.73740	482.27340	100.70000	2.49515	762.93990	977.78980	.99741	2044.24500
.900	.2008	753.03470	1272.95000	426.51710	482.31740	100.70000	2.49439	763.03980	977.79980	.96856	2044.24500
GRADIENT	.02317	-.02823	-.03317	.13924	.15333	-.00099	.02256	.04476	-.00301	-.00040	

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM037) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.599	-7.940	1252.87399	1597.08000	314.91240	521.89040	99.70000	2.49849	1262.62000	1300.58000	.67419	2043.12500
.600	-6.915	1252.27699	1596.95000	315.29270	521.83150	99.70000	2.49977	1262.03000	1300.58000	.67608	2043.12500
.599	-5.911	1252.68500	1596.86000	314.88230	521.88840	99.70000	2.49820	1262.42999	1300.60001	.67796	2043.09000
.600	-4.906	1251.60899	1596.83000	315.73970	521.76320	99.70000	2.50129	1261.37000	1300.60001	.68167	2043.12500
.600	-3.889	1251.91299	1596.86000	315.51560	521.79660	99.70000	2.50050	1261.67000	1300.60001	.70803	2043.09000
.600	-2.869	1252.00301	1596.92999	315.50050	521.80080	99.70000	2.50050	1261.75999	1300.61000	.70800	2043.09000
.601	-1.831	1251.25700	1596.64999	315.87720	521.73800	99.70000	2.50163	1261.02000	1300.61000	.71004	2043.12500
.601	-.777	1251.26700	1597.17999	316.31450	521.68970	99.70000	2.50367	1261.03999	1300.61000	.70789	2043.05499
.601	.297	1251.67799	1597.39999	316.16190	521.17830	99.70000	2.50330	1261.45000	1300.64000	.70588	2043.05499
.600	1.188	1251.53000	1596.72000	315.71190	521.76420	99.70000	2.50109	1261.28999	1300.63000	.71001	2043.05499
.600	2.118	1251.82899	1597.00999	315.71070	521.77270	99.70000	2.50133	1261.59000	1300.64000	.70796	2043.05499
GRADIENT	-.01680	.03076	.03962	-.00486	-.00000	-.00017	-.01592	.00611	-.00219	-.00993	

## PARAMETRIC DATA

	RUN NO.	1346/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	1.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.800	-7.940	880.89260	134.2.16000	394.18070	496.84740	100.70000	2.49624	890.79980	1047.10001
.800	-6.922	880.29960	134.1.98000	394.45090	496.77080	100.70000	2.49676	890.21000	1047.10001
.800	-5.920	880.22800	134.2.03999	394.54420	496.75290	100.70000	2.49707	890.13990	1047.11000
.800	-4.914	880.22440	134.1.64000	394.25070	496.88330	100.80000	2.49529	890.12990	1047.11000
.800	-3.906	880.16630	134.2.10001	394.63040	496.73660	100.70000	2.49736	890.07980	1047.10001
.800	-2.889	880.24630	134.2.17000	394.62790	496.83080	100.80000	2.49685	890.15990	1047.10001
.801	-1.867	879.89400	134.2.10001	394.81540	496.78150	100.80000	2.49727	889.80980	1047.11000
.800	-834	880.25270	134.1.75000	394.31270	496.87620	100.80000	2.49557	890.15990	1047.11000
.800	.218	880.26930	134.1.98000	394.47140	496.85470	100.80000	2.49624	890.17990	1047.12000
.800	1.129	880.54320	134.1.91000	394.23360	496.90620	100.80000	2.49554	890.45000	1047.12000
.800	2.084	880.63230	134.2.00999	394.24710	496.90990	100.80000	2.49568	890.53980	1047.12000
GRADIENT	.06045	.00838	-.03491	.01414	.00596	-.00012	.06002	.00271	.00035

RUN NO. 1336/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1336/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	1.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.900	-7.943	752.73020	127.3.09000	426.79440	482.24660	100.70000	2.49517	762.74000	977.79980
.900	-6.915	752.77420	127.2.83000	426.58960	482.28270	100.70000	2.49440	762.77980	977.80980
.900	-5.910	752.72270	127.2.91000	426.67530	482.26460	100.70000	2.49469	762.73000	977.83980
.900	-4.905	752.70070	127.3.03000	426.77080	482.33370	100.80000	2.49447	762.71000	977.82980
.900	-3.894	752.67820	127.3.22000	426.91480	482.30910	100.80000	2.49502	762.68990	977.82980
.901	-2.879	752.35620	127.3.19000	427.08570	482.25340	100.80000	2.49535	762.36990	977.83980
.900	-1.852	752.4.1090	127.2.88000	426.84030	482.29690	100.80000	2.49444	762.41990	978.171
.900	-.819	752.81150	127.3.02000	426.69780	482.35520	100.80000	2.49430	762.81980	978.161
.900	.231	752.70390	127.2.83000	426.63160	482.44210	100.90000	2.49334	762.71000	977.85990
.900	1.141	752.69560	127.2.70000	426.54710	482.45460	100.90000	2.49300	762.70000	977.88990
.900	2.095	753.04440	127.2.97000	426.52490	482.48930	100.90000	2.49328	763.04980	977.88990
GRADIENT	.04611	-.04718	-.05986	.02882	.01773	-.00029	.04507	.00920	.00098

RUN NO. 1325/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

PATM

	RUN NO.	1325/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	1.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
1.100	-7.949	565.26980	120.6.19000	478.35380	450.69870	100.00000	2.49939	575.46000	863.76980
1.100	-6.926	564.63010	120.6.00000	478.49610	450.41210	99.80000	2.50042	574.81980	863.79980
1.100	-5.948	564.99270	120.5.88000	478.28320	450.66870	100.00000	2.49881	575.17990	863.80980
1.100	-4.924	564.52930	120.6.05000	478.56490	450.46440	99.89999	2.50000	574.72000	863.82980
1.100	-3.925	564.85330	120.5.78000	478.28000	450.56690	99.89999	2.49923	575.03980	863.83980
1.100	-2.919	564.69950	120.6.11000	478.53300	450.57710	100.00000	2.49948	574.88990	863.86990
1.100	-1.912	564.73100	120.5.97000	478.43900	450.43820	99.80000	2.50031	574.91990	863.87990
1.100	-.917	564.67070	120.5.99001	478.47440	450.58350	100.00000	2.49922	574.85990	863.89990
1.100	.089	564.98070	120.6.06000	478.39260	450.48560	99.80000	2.50040	575.16990	863.92990
1.100	1.052	564.67220	120.5.86000	478.36250	450.61820	100.00000	2.49887	574.95000	863.93990
1.100	2.026	565.03170	120.5.97000	478.32010	450.74850	100.10000	2.49842	575.22000	863.96000
GRADIENT	.04598	-.00337	-.02013	.02154	.01775	-.00013	.04582	.00920	.01929

PATM

	RUN NO.	1325/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	1.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
1.100	-7.949	565.26980	120.6.19000	478.35380	450.69870	100.00000	2.49939	575.46000	863.76980
1.100	-6.926	564.63010	120.6.00000	478.49610	450.41210	99.80000	2.50042	574.81980	863.79980
1.100	-5.948	564.99270	120.5.88000	478.28320	450.66870	100.00000	2.49881	575.17990	863.80980
1.100	-4.924	564.52930	120.6.05000	478.56490	450.46440	99.89999	2.50000	574.72000	863.82980
1.100	-3.925	564.85330	120.5.78000	478.28000	450.56690	99.89999	2.49923	575.03980	863.83980
1.100	-2.919	564.69950	120.6.11000	478.53300	450.57710	100.00000	2.49948	574.88990	863.86990
1.100	-1.912	564.73100	120.5.97000	478.43900	450.43820	99.80000	2.50031	574.91990	863.87990
1.100	-.917	564.67070	120.5.99001	478.47440	450.58350	100.00000	2.49922	574.85990	863.89990
1.100	.089	564.98070	120.6.06000	478.39260	450.48560	99.80000	2.50040	575.16990	863.92990
1.100	1.052	564.67220	120.5.86000	478.36250	450.61820	100.00000	2.49887	574.95000	863.93990
1.100	2.026	565.03170	120.5.97000	478.32010	450.74850	100.10000	2.49842	575.22000	863.96000
GRADIENT	.04598	-.00337	-.02013	.02154	.01775	-.00013	.04582	.00920	.01929

PATM

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 919  
(VCM037) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1371/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
1.250	-7.949	462.55400	1197.83000	505.75760	426.98070	100.70000	2.49562	472.67990	904.63990	1.19551 204.1 79500
-6.928	462.66060	1198.27000	505.95730	427.04030	100.80000	2.49595	472.78980	904.66990	1.19507 204.1 79500	
-5.920	462.75930	1198.46001	506.03200	427.04690	100.80000	2.49634	472.88990	904.66990	1.19171 204.1 79500	
-4.923	462.50390	1197.89000	505.79910	427.03760	100.80000	2.49515	472.62990	904.68990	1.19228 204.1 79500	
-3.909	462.52540	1197.66000	505.67770	427.06670	100.80000	2.49469	472.64990	904.74000	1.19886 204.1 79500	
-2.895	462.64500	1197.67000	505.65650	427.17360	100.90000	2.49414	472.76980	904.76000	1.20203 204.1 79500	
-1.882	462.46310	1197.99001	505.85860	427.09300	100.90000	2.49476	472.58980	904.77980	1.20811 204.1 79500	
-1.250	462.68090	1198.23000	505.93260	427.12600	100.90000	2.49528	472.80980	904.82980	1.21107 204.1 79500	
-1.122	462.67190	1197.73000	505.73070	427.11450	100.90000	2.49453	472.56980	904.85990	1.20837 204.1 79500	
1.122	462.66060	1198.30000	505.87380	427.13570	101.90000	2.49503	472.77980	904.92990	1.20798 204.1 83000	
2.079	462.66060	1198.30000	505.97240	427.18970	101.90000	2.49483	472.78980	904.92990	1.21100 204.1 83000	
1.250	GRADIENT	.01691	.06507	.02927	.01493	.02244	.00000	.01739	.03349	.00236 .00785

RUN NO. 1382/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1382/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	5.00
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
1.399	-7.955	382.10080	1215.02000	523.83570	403.08370	101.30000	2.49129	391.80980	920.48000	1.20384 204.1 55000
-6.930	381.73710	1214.64999	523.68140	403.00900	101.30000	2.49035	391.43990	920.49000	1.21060 204.1 58501	
-5.923	381.64530	1215.13000	523.89310	402.93580	101.30000	2.49115	391.34990	920.51000	1.20373 204.1 58501	
-4.921	382.01050	1215.23000	523.92940	403.03660	101.30000	2.49161	391.72000	920.51980	1.19727 204.1 62000	
-3.914	381.79220	1215.31000	523.96870	402.96310	101.30000	2.49159	391.50000	920.51980	1.18770 204.1 58501	
-2.905	381.85640	1214.52000	523.62210	403.05740	101.30000	2.49200	391.55980	920.51980	1.18770 204.1 62000	
-1.890	381.91380	1214.85001	523.76510	403.04350	101.30000	2.49084	391.61990	920.49000	1.19131 204.1 58501	
-0.870	381.67330	1215.35001	523.98850	402.92360	101.30000	2.49158	391.37990	920.54980	1.19398 204.1 62000	
-1.172	381.88600	1214.53999	523.63010	403.06450	101.30000	2.49026	391.58980	920.52980	1.19161 204.1 62000	
1.117	381.98220	1215.00999	523.83400	403.04880	101.30000	2.49118	391.68990	920.53980	1.16922 204.1 58501	
1.400	2.073	381.99980	1215.34000	523.97780	403.02290	101.30000	2.49180	391.71000	920.52980	1.16891 204.1 62000
1.400	GRADIENT	.00833	-.00299	-.000145	-.000279	-.000000	.000000	.00839	.00309	-.00350 .00041

RUN NO. 1394/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1394/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	5.00
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
1.450	-7.943	358.93160	1226.33000	528.31760	394.68580	101.00000	2.49387	368.40990	933.06980	1.36785 204.1 86501
-6.906	358.77420	1226.32001	528.30540	394.56670	100.90000	2.49430	368.25000	933.06980	1.36428 204.1 86501	
-5.901	358.77470	1226.20000	528.25560	394.64840	101.00000	2.49350	368.25000	933.08980	1.36441 204.1 86501	
-4.896	359.05220	1225.89000	528.14090	394.69360	100.90000	2.49381	368.52980	933.08980	1.36476 204.1 86501	
-3.882	359.02220	1226.00000	528.18510	394.67410	100.90000	2.49397	368.50000	933.10990	1.36106 204.1 89999	
-2.864	358.94340	1226.00000	528.18120	394.64940	100.90000	2.49390	368.41990	933.09990	1.36821 204.1 89999	
-1.834	358.91460	1225.84000	528.11300	394.65500	100.90000	2.49359	368.38990	933.09990	1.38643 204.1 89999	
-1.450	358.88450	1225.92999	528.14890	394.63720	100.90000	2.49372	368.35990	933.08980	1.38270 204.1 86501	
-1.450	358.87500	1225.86000	528.11940	394.64060	100.90000	2.49359	368.34990	933.10990	1.36837 204.1 86501	
1.450	1.175	358.76710	1225.78000	528.08060	394.54370	100.80000	2.49394	368.24000	933.09990	1.38287 204.1 89999
1.450	2.113	358.97240	1226.06000	528.07500	394.58250	100.80000	2.49463	368.45000	933.09990	1.37894 204.1 86501
1.450	GRADIENT	-.02472	-.00326	-.00262	-.01727	-.01391	-.02508	-.00005	-.00049	-.00168

## PARAMETRIC DATA

RUN NO. 1438/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.471	-7.882	347.96220	1225.23270	527.12815	390.83520	101.20000	2.49142	357.29980	897.76000	1.24192 2043.02000
1.471	-6.913	347.92110	1225.49384	527.23090	390.79130	101.20000	2.49196	357.25980	897.76000	1.24486 2043.02000
1.471	-5.908	348.04910	1225.44255	527.22153	390.83330	101.20000	2.49208	357.38990	897.76000	1.24816 2043.02000
1.471	-4.903	347.72560	1225.01640	527.01981	390.75290	101.20000	2.49129	357.05980	897.76000	1.25503 2043.05499
1.471	-3.888	347.84570	1224.57527	526.05221	390.82860	101.20000	2.49071	357.17990	897.75000	1.25876 2043.05499
1.471	-2.871	348.09990	1224.92064	527.01224	390.87570	101.20000	2.49163	357.43990	897.73000	1.26170 2043.02000
1.471	-1.843	347.87160	1225.11989	527.07360	390.76900	101.20000	2.49203	357.21000	897.75000	1.26798 2043.05499
1.471	-.800	347.91240	1224.78177	526.94011	390.87790	101.30000	2.49098	357.25000	897.71000	1.27163 2043.05499
1.471	.260	348.01880	1225.11359	527.08412	390.87670	101.30000	2.49176	357.35990	897.71000	1.27458 2043.02000
1.471	1.159	347.83470	1225.13478	527.07802	390.87110	101.30000	2.49055	357.16990	897.67990	1.24200 2043.02000
1.471	2.104	347.90530	1224.69327	526.90404	390.92460	101.30000	2.49004	357.24000	897.68990	1.24892 2043.02000
GRADIENT			.01216	.00993	.00516	.01799	.01898	-.00012	.01231	-.00110 -.00496

RUN NO. 1405/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.496	-7.947	337.52780	1231.88025	528.73653	386.86550	101.30000	2.49178	346.72000	944.00000	1.15861 2042.25000
1.496	-6.916	337.47950	1231.78535	528.69395	386.86230	101.30000	2.49148	346.66990	944.00980	1.15567 2042.21500
1.496	-5.906	337.40110	1231.64746	528.62927	386.84370	101.30000	2.49126	346.58980	944.00980	1.15881 2042.21500
1.496	-4.902	337.46090	1231.44504	528.55617	386.88310	101.30000	2.49095	346.64990	944.00000	1.15902 2042.25000
1.496	-3.892	337.51950	1231.41548	528.55116	386.889230	101.30000	2.49121	346.71000	944.00980	1.16818 2042.21500
1.496	-2.878	337.72270	1232.07501	528.83731	386.89620	101.30000	2.49263	346.91990	944.00000	1.17062 2042.21500
1.496	-1.852	337.50900	1231.51959	528.59206	386.87450	101.30000	2.49147	346.70000	943.98000	1.17113 2042.21500
1.496	-.814	337.45070	1231.37514	528.67690	386.86790	101.30000	2.49116	346.63990	943.97000	1.17126 2042.21500
1.496	.247	337.37330	1231.27638	528.47882	386.86840	101.30000	2.49058	346.55980	943.96000	1.15917 2042.21500
1.496	1.157	337.67460	1232.01013	528.80568	386.889940	101.30000	2.49222	346.86990	943.93990	1.16153 2042.17999
1.496	2.104	337.44970	1231.70358	528.65714	386.85080	101.30000	2.49148	346.63990	943.91990	1.16180 2042.17999
GRADIENT			-.00514	.02534	.00943	-.00332	-.000000	.00002	-.00517	-.01225 -.00057

RUN NO. 1428/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.517	-7.947	327.43190	1232.17601	527.48958	382.91550	101.30000	2.49112	336.46000	9112.05980	1.49028 2043.05499
1.518	-6.916	327.12770	1232.28157	527.48390	382.80590	101.30000	2.49089	336.14990	9112.06980	1.48631 2043.02000
1.517	-5.913	327.41310	1232.12631	527.46693	382.92850	101.30000	2.49073	336.43990	9112.07980	1.47897 2043.02000
1.518	-4.902	326.98220	1232.11484	527.39735	382.79050	101.30000	2.49007	336.00000	9112.06980	1.47138 2043.02000
1.518	-3.893	327.18630	1232.62364	527.62541	382.82030	101.30000	2.49106	336.21000	9112.06980	1.46704 2043.02000
1.517	-2.908	327.44020	1232.88895	527.76634	382.88400	101.30000	2.49178	336.47000	9112.05980	1.46676 2043.02000
1.518	-.8153	327.13890	1232.28329	527.48615	382.83940	101.30000	2.49033	336.15990	9112.04980	1.46370 2043.05499
1.518	-.808	326.98220	1232.28557	527.46269	382.79490	101.30000	2.48999	336.00000	9112.04980	1.45620 2043.02000
1.518	.246	327.26390	1233.12628	527.83076	382.83130	101.30000	2.49144	336.28980	9112.03980	1.44411 2043.05499
1.518	1.157	327.16750	1232.85233	527.71051	382.90060	101.40000	2.49009	336.18990	9112.04980	1.43704 2043.05499
1.518	2.102	327.16850	1232.62868	527.62379	382.92110	101.40000	2.48971	336.18990	9112.02980	1.43731 2043.05499
GRADIENT			.00600	.06480	.02586	.01289	.01396	.00010	.00604	-.00520 -.00547

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM037) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
-7.94	317.60910	1240.87431	529.14125	378.97070	101.40000	2.49076	326.46000	899.79980	1.33050	2042.81000	
-6.915	317.63820	1240.89368	529.15489	378.97460	101.40000	2.49091	326.49000	899.79980	1.33392	2042.81000	
-5.911	317.57960	1240.90944	529.14880	378.88990	101.30000	2.49138	326.42990	899.80980	1.33046	2042.81000	
-4.907	317.61060	1240.45621	528.98427	378.94090	101.30000	2.49065	326.46000	899.79980	1.33096	2042.81000	
-3.893	317.60860	1260.92081	536.79248	378.89790	101.30000	2.49145	326.46000	899.79980	.00000	2042.81000	
-2.878	317.66770	1260.87785	536.78822	378.92160	101.30000	2.49147	326.51980	899.78980	.00000	2042.77499	
-1.847	317.51170	1260.70126	536.69133	378.81640	101.20000	2.49155	326.35990	899.79980	.00000	2042.77499	
-8.11	317.58010	1240.91040	529.15044	378.83620	101.20000	2.49171	326.42990	899.78980	1.32020	2042.77499	
.246	317.70800	1240.84227	529.14893	378.82420	101.10000	2.49226	326.55980	899.76980	1.31689	2042.81000	
1.160	317.49170	1260.86455	536.74906	378.72830	101.10000	2.49239	326.33980	899.77980	.00000	2042.81000	
2.101	317.67800	1260.71513	536.72882	378.80370	101.10000	2.49241	326.52980	899.76980	.00000	2042.77499	
1.554	GRADIENT	.00094	.67986	.25958	-.02461	-.03552	.00023	.00095	-.00450	-.00165	-.04460

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM038) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.599	-7.904	1253.16000	1596.96001	314.57640	521.84230	99.59999	2.49774	1262.89999	1300.63000	.70416	2043.05499
.599	-6.881	1252.43401	1596.74001	314.98750	521.77640	99.59999	2.49905	1262.17999	1300.62000	.70426	2043.05499
.600	-5.867	1252.16299	1597.03999	315.46170	521.71630	99.59999	2.50103	1261.92000	1300.63000	.70413	2043.02000
.600	-4.858	1252.26900	1596.84000	315.20650	521.74760	99.59999	2.49993	1262.02000	1300.64000	.70231	2043.05499
.600	-3.840	1252.25500	1597.00999	315.36080	521.73000	99.59999	2.50063	1262.00999	1300.62000	.70033	2043.02000
.600	-2.811	1251.84399	1597.25000	315.89990	521.65870	99.59999	2.50280	1261.61000	1300.61000	.69644	2043.05499
.601	-1.776	1251.70799	1597.41000	316.14530	521.62770	99.59999	2.50382	1261.48000	1300.62000	.68142	2043.05499
.601	-.745	1251.25000	1597.00999	316.18550	521.61010	99.59999	2.50363	1261.02000	1300.62000	.67974	2043.02000
.600	.265	1251.83501	1597.22000	315.88260	521.66040	99.59999	2.50271	1261.60001	1300.61000	.67597	2043.05499
.600	1.223	1252.14799	1596.78000	315.25540	521.73880	99.59999	2.50005	1261.89999	1300.62000	.67799	2043.02000
.600	2.191	1252.14500	1596.92999	315.38400	521.72440	99.59999	2.50065	1261.89999	1300.59000	.68348	2043.02000
GRADIENT	-.02381	-.01123	-.01015	-.00180	-.00165	-.00000	-.0003	-.02368	-.00411	-.00364	-.00328

卷之三

PAGE 922

(VCM038) ( 04 OCT 91 )

PARAMETRIC DATA

	RUN NO.	1347 / O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00 / 5.00	
ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC
ACH							
.800	-7.919	880.59180	1342.03000	394.28930	496.99000	100.90000	2.49524 .90.50000
.800	-6.895	880.45360	1342.46001	394.70140	496.22110	100.90000	2.49677 .90.36990
.800	-5.889	880.43920	1342.10001	394.44480	496.95800	100.90000	2.49573 .90.34990
.800	-4.881	880.39020	1342.02000	394.41920	496.95850	100.90000	2.49557 .90.29980
.801	-3.865	879.78440	1341.98000	394.80100	496.95360	101.00000	2.49595 .88.70000
.800	-2.851	880.21950	1341.95000	394.48340	496.93850	100.90000	2.49566 .89.12990
.800	-1.828	880.32060	1341.92999	394.39970	496.95680	100.90000	2.49542 .89.23000
.800	-810	880.18750	1342.05000	394.57890	496.83400	100.80000	2.49659 .89.09990
.800	-191	880.36790	1342.16000	394.53780	496.67430	100.60000	2.49775 .89.0.27980
.800	-1.155	880.50290	1341.89000	394.24610	496.72460	100.60000	2.49669 .89.0.40990
.799	2.140	880.95570	1341.95000	394.05000	496.68630	100.50000	2.49682 .89.0.76000
GRADIENT	0.8444	-	0.0208	-	0.04699	-	.06862 .00024
					0.58897	-	

	RUN NO.	1326 / 0	RN/L =	2 . 50	GRADIENT INTERVAL =	- 5 . 00 / 5 . 00	
ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC
.099	565.28980	1206.21001	478.35770	450.62060	99.89999	2.50001	575.48000
.940	564.86080	1206.02000	478.41670	450.70410	100.10000	2.49861	575.04988
.917	564.37040	1205.92999	478.55790	450.60210	100.10000	2.49864	574.55984
.915	564.66940	1206.10001	478.53880	450.49110	99.89999	2.50005	574.85999
.909	564.72140	1205.92000	478.41360	450.52200	99.89999	2.49962	574.90990
.914	564.64210	1205.83000	478.39260	450.59400	100.00000	2.49886	574.82988
.910	564.64210	1205.83000	478.39260	450.59400	100.00000	2.49886	574.82988
.907	564.64970	1206.05000	478.51730	450.65280	100.10000	2.49878	574.83988
.902	564.72120	1205.92999	478.41940	450.68190	100.10000	2.49847	574.90990
.900	564.57150	1205.88000	478.44950	450.65310	100.10000	2.49843	574.76000
.066	564.92040	1206.06000	478.41630	450.55250	99.89999	2.49984	575.10994
.035	565.01250	1205.91000	478.42940	450.20000	99.89999	2.00006	575.20000
.039	565.01250	1205.92000	478.42940	450.20000	99.89999	2.00006	575.20000

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM038) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1372/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00			BETA =	2.000	PHI =	180.000
ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
MACH											
-7.933	463.03960	1198.31000	505.89450	427.21240	100.90000	2.49549	473.16990	905.02980	1.20778	204.179500	
-6.901	462.88920	1198.39999	505.97310	427.16360	100.90000	2.49565	473.01980	905.07980	1.21090	204.179500	
-5.895	462.56250	1198.06000	505.87230	427.18820	101.00000	2.49433	472.68990	905.09990	1.21124	204.179500	
-4.885	462.05520	1197.92000	505.91240	427.06860	101.00000	2.49398	472.17990	905.11990	1.20818	204.183000	
-3.881	462.46580	1197.64000	505.68070	427.20560	101.00000	2.49347	472.58980	905.13990	1.21167	204.179500	
-2.865	462.14380	1198.06000	505.96390	427.07760	101.00000	2.49428	472.26980	905.15990	1.20804	204.183000	
-1.850	462.59400	1197.85001	505.75900	427.21800	101.00000	2.49391	472.72000	905.18990	1.20825	204.183000	
-1.250	462.69310	1197.95000	505.78810	427.23390	101.00000	2.49413	472.81980	905.22000	1.21136	204.183000	
-1.250	462.76050	1198.28000	505.94070	427.21800	101.00000	2.49481	472.88990	905.23000	1.20781	204.183000	
1.132	462.96040	1198.24001	505.87650	427.35110	101.10000	2.49416	473.08980	905.26980	1.20146	204.183000	
1.124	462.78050	1198.27000	505.93120	427.30050	101.10000	2.49420	472.90990	905.26980	1.20143	204.183000	
GRADIENT	.11290	.07369	.01267	.03307	.01417	.00008	.11374	.02420	-.00113	.00208	

RUN NO. 1383/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.		1383/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00			BETA =	2.000	PHI =	5.00
ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
MACH											
-7.936	381.99170	1215.07001	523.85990	403.04590	101.30000	2.49130	391.70000	920.55980	1.15988	204.158501	
-6.910	381.76340	1215.19000	523.91700	402.96580	101.30000	2.49135	391.47000	920.52980	1.15055	204.158501	
-5.900	381.84370	1214.99001	523.82790	403.00900	101.30000	2.49105	391.54980	920.55980	1.17547	204.158501	
-4.897	381.74780	1214.53000	523.62870	403.02370	101.30000	2.49014	391.45000	920.57980	1.18218	204.158501	
-3.883	381.82250	1215.22000	523.92900	402.98100	101.30000	2.49145	391.52980	920.56980	1.17837	204.158501	
-2.875	381.9040	1215.41000	524.01030	402.98930	101.30000	2.49186	391.61990	920.56980	1.18446	204.158501	
-1.860	381.98240	1214.98000	523.82080	403.05180	101.30000	2.49113	391.68990	920.57980	1.18488	204.155000	
-0.854	381.79710	1214.53000	523.62770	403.03860	101.30000	2.49018	391.50000	920.57980	1.18218	204.158501	
.146	381.71560	1214.91000	523.79540	402.97800	101.30000	2.49081	391.41990	920.57980	1.18181	204.158501	
1.119	382.13110	1214.91000	523.78690	403.10330	101.30000	2.49111	391.83980	920.58980	1.17555	204.158501	
1.399	381.86230	1215.22000	523.92820	402.99270	101.30000	2.49148	391.56980	920.57980	1.18150	204.158501	
2.113	.01864	.01565	.00645	.000412	-.000000	.00004	.01892	.00154	-.00035	.00040	

RUN NO. 1395/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.		1395/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00			BETA =	2.000	PHI =	5.00
ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
MACH											
-7.907	359.15990	1226.07001	528.22120	394.64040	100.80000	2.49482	368.63990	933.08980	1.38254	204.186501	
-6.875	359.32690	1226.17000	528.27120	394.68360	100.80000	2.49515	368.80980	933.09990	1.37882	204.186501	
-5.863	359.11960	1226.06000	528.27320	394.61600	100.80000	2.49501	368.59990	933.09990	1.37518	204.183000	
-4.848	358.65720	1226.03999	528.18290	394.41500	100.70000	2.49489	368.12990	933.10990	1.38258	204.186501	
-3.831	358.76490	1226.22000	528.26340	394.50270	100.80000	2.49471	368.24000	933.11990	1.38237	204.186501	
-2.807	358.66720	1226.03000	528.17940	394.48930	100.80000	2.49428	368.13990	933.11990	1.37177	204.186501	
-1.777	358.84620	1225.73000	528.06400	394.57320	100.80000	2.49393	368.31980	933.10990	1.37571	204.186501	
-1.450	359.05050	1226.20000	528.26980	394.5920	100.80000	2.49494	368.52980	933.11990	1.37518	204.189999	
-1.450	.258	358.96090	1226.37000	528.33570	394.48000	100.70000	2.49575	368.43990	933.09990	1.38583	204.186501
1.450	1.219	358.87600	1225.67999	528.04470	394.58720	100.80000	2.49387	368.34990	933.10990	1.39388	204.186501
1.449	2.188	359.10210	1225.80000	528.10600	394.64720	100.80000	2.49429	368.57980	933.09990	1.37923	204.183000
GRADIENT	.05626	-.03352	-.01104	.02405	.00469	-.00003	.05690	-.000200	.00089	-.00241	

## PARAMETRIC DATA

	RUN NO.	1439/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	
1.471	-7.914	347.93160	1225.11223	527.07676	390.87700	101.30000	2.49114	357.26980	897.66990	1.25821	2042.98500
-6.874	347.87330	1224.59180	526.85918	390.87080	101.30000	2.49083	357.21000	897.67990	1.27841	2042.98500	
-5.871	347.89280	1225.08110	527.06045	390.87260	101.30000	2.49094	357.23000	897.65990	1.25499	2043.02000	
-4.859	347.88380	1224.52998	526.83528	390.88600	101.30000	2.49062	357.22000	897.66990	1.27518	2042.98500	
-3.843	347.92410	1224.22495	526.71480	390.91630	101.30000	2.49033	357.25980	897.65990	1.28211	2042.98500	
-2.823	347.91210	1224.65096	526.88627	390.87260	101.30000	2.49108	357.25000	897.64990	1.28165	2042.98500	
-1.794	347.99000	1224.70091	526.91254	390.88210	101.30000	2.49146	357.32980	897.65990	1.28824	2043.02000	
-7.67	348.04980	1224.49986	526.83559	390.98460	101.40000	2.49067	357.38990	897.63990	1.29179	2042.98500	
-237	348.02880	1224.56755	526.86166	390.95340	101.40000	2.49111	357.36990	897.63990	1.30174	2042.95000	
1.471	1.199	347.80570	1224.25616	526.71722	390.94340	101.40000	2.48970	357.13990	897.59990	1.28206	2042.98500
2.176	347.97090	1224.69855	526.91039	390.88770	101.30000	2.49121	357.30980	897.59990	1.28161	2042.98500	
GRADIENT		.00528	.01052	.00462	.00593	.01077	.00000	.00554	-.00871	.00131	-.00168

RUN NO. 1406/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1406/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	
1.496	-7.918	337.55620	1232.24158	528.88364	386.84620	101.30000	2.49235	346.75000	943.88990	1.15524	2042.21500
-6.885	337.37130	1231.85431	528.70778	386.82320	101.30000	2.49143	346.55980	943.88990	1.15257	2042.21500	
-5.877	337.46040	1231.67603	528.64771	386.87040	101.30000	2.49119	346.64990	943.87990	1.15275	2042.25000	
-4.860	337.45140	1231.50096	528.57723	386.88330	101.30000	2.49088	346.63990	943.87990	1.15292	2042.25000	
-3.851	337.43190	1231.37283	528.52388	386.87960	101.30000	2.49080	346.61990	943.86990	1.15908	2042.25000	
-2.829	337.59690	1231.79491	528.71115	386.89260	101.30000	2.49177	346.78980	943.86990	1.16173	2042.25000	
-1.803	337.62550	1231.96353	528.78126	386.88230	101.30000	2.49218	346.81980	943.84990	1.16461	2042.25000	
1.496	-7.781	337.62720	1231.58794	528.63293	386.91770	101.30000	2.49152	346.81980	943.83980	1.16498	2042.25000
-2.22	337.44900	1231.85794	528.71849	386.83620	101.30000	2.49176	346.63990	943.80980	1.16165	2042.25000	
1.496	1.186	337.611770	1231.65356	528.65823	386.92160	101.30000	2.49137	346.80980	943.80980	1.15582	2042.28500
1.496	2.167	337.48000	1231.50591	528.58250	386.87500	101.30000	2.49125	346.66990	943.78980	1.16503	2042.25000
GRADIENT		.00828	.01532	.00711	.00020	-.00000	.00000	.00855	-.01327	.00082	.00206

RUN NO. 1429/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1429/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	
1.518	-7.914	327.36400	1232.77988	527.71172	382.97510	101.40000	2.49018	336.38990	912.01000	1.43776	2043.09000
-6.885	327.04100	1232.62759	527.60350	382.81370	101.30000	2.49008	336.05980	912.00000	1.42361	2043.09000	
-5.877	326.99220	1232.64598	527.60311	382.80000	101.30000	2.49096	336.00980	912.01000	1.42991	2043.09000	
-4.862	327.43120	1233.83881	528.13115	382.96510	101.40000	2.49088	336.46000	911.99000	1.38881	2043.09000	
-3.851	327.39310	1233.52260	528.00307	382.91210	101.30000	2.49089	336.41990	911.99000	1.38917	2043.12500	
-2.830	326.95210	1233.49297	527.92321	382.77170	101.30000	2.49020	335.97000	912.00000	1.38201	2043.12500	
1.518	-1.803	327.13960	1233.17909	527.83173	382.85550	101.30000	2.49004	336.15990	911.99000	1.38952	2043.12500
-7.83	327.81370	1233.80959	528.17823	383.03150	101.30000	2.49182	336.84990	911.99000	1.38890	2043.12500	
1.517	1.224	327.53980	1232.98225	527.81735	383.02250	101.40000	2.49062	336.56980	911.96000	1.43327	2043.12500
1.518	1.185	327.18870	1232.44646	527.55621	382.87650	101.30000	2.49001	336.21000	911.96000	1.43753	2043.16000
2.165	327.23610	1232.77791	527.69174	382.85790	101.30000	2.49073	336.25980	911.95000	1.44083	2043.19501	
GRADIENT		.00110	-.16166	-.06220	-.00019	-.00470	-.00003	-.00098	-.00649	.00895	.001069

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM038) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1418/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
1.543	-7.916	317.51120	1240.93353	529.14565	378.66550	101.00000	2.49304	326.35990	899.74000	1.32700 2042.77499
1.542	-6.884	317.75610	1240.85431	529.16250	378.68650	100.90000	2.49388	326.60990	899.73000	1.33054 2042.81000
1.543	-5.876	317.58010	1240.82565	529.11821	378.63180	100.90000	2.49354	326.42990	899.73000	1.32712 2042.77499
1.543	-4.865	317.49190	1240.98039	529.16031	378.60110	100.90000	2.49343	326.33980	899.73000	1.31671 2042.81000
1.543	-3.851	317.58910	1241.82230	529.49822	378.61940	100.90000	2.49385	326.43990	899.73000	1.27234 2042.81000
1.543	-2.829	317.55080	1241.84245	529.49946	378.62180	100.90000	2.49350	326.39990	899.73000	1.25919 2042.81000
1.543	-1.804	317.70750	1241.97144	529.57817	378.68310	100.90000	2.49357	326.55980	899.71000	1.24609 2042.84500
1.543	-7.780	317.61940	1241.30028	529.30633	378.65380	100.90000	2.49343	326.47000	899.72000	1.28946 2042.84500
1.543	.223	317.61960	1241.20068	529.26838	378.65820	100.90000	2.49335	326.47000	899.70000	1.29290 2042.81000
1.543	1.187	317.56050	1241.29814	529.29382	378.62430	100.90000	2.49353	326.40990	899.71000	1.29614 2042.81000
1.542	2.165	317.87350	1241.38814	529.38666	378.73100	100.90000	2.49396	326.73000	899.70000	1.29274 2042.81000
GRADIENT	.03118	-.02780	-.00473	.01198	-.00000	.00002	.03183	-.00462	.00110	.00005

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM039) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1359/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	3.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
.600	-7.870	1252.35300	1597.17999	315.42360	521.72580	99.59999	2.50100	1262.11000	1300.61000	.72337 2043.02000
.600	-6.847	1251.95799	1596.63000	315.28490	521.73020	99.59999	2.50003	1261.71001	1300.58000	.72558 2043.02000
.600	-5.836	1251.82500	1596.66000	315.41920	521.71170	99.59999	2.50055	1261.58000	1300.57001	.72556 2043.02000
.601	-4.820	1251.38200	1596.99001	316.05980	521.62790	99.59999	2.50316	1261.14999	1300.55000	.72541 2043.02000
.601	-3.798	1251.28200	1597.39000	316.47800	521.57860	99.59999	2.50501	1261.06000	1300.53999	.71938 2043.02000
.601	-2.772	1251.31500	1596.78000	315.93850	521.63960	99.59999	2.50254	1261.08000	1300.53999	.71577 2043.02000
.601	-1.746	1251.46800	1596.78000	315.81320	521.65770	99.59999	2.50208	1261.23000	1300.53999	.70998 2043.02000
.601	-.728	1251.31300	1596.89999	316.04130	521.62820	99.59999	2.50301	1261.08000	1300.53000	.70801 2043.02000
.601	.283	1251.75700	1598.03000	316.62650	521.57570	99.59999	2.50609	1261.53999	1300.53000	.70943 2042.98500
.601	1.256	1251.29601	1597.24001	316.34130	521.59420	99.59999	2.50439	1261.07001	1300.53999	.70978 2043.02000
.601	2.230	1251.72000	1597.35001	316.08540	521.63450	99.59999	2.50355	1261.49001	1300.52000	.70781 2043.02000
GRADIENT	.04251	.06658	-.02117	-.00115	.00000	.00013	.04314	-.00295	-.00228	-.00127

## PARAMETRIC DATA

RUN NO.	1348/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC
.800	-7.894	880.83280	1342.12000	394.19190	496.48730	100.30000	2.49852	890.74000
.800	-6.871	880.54100	1342.06000	394.34620	496.44680	100.30000	2.49886	890.45000
.800	-5.863	880.51780	1342.24001	394.49490	496.33520	100.20000	2.50002	890.42990
.800	-4.855	880.15550	1342.17000	394.68950	496.19580	100.10000	2.50103	890.06980
.800	-3.840	880.15550	1342.17999	394.69700	496.19460	100.10000	2.50106	890.06980
.800	-2.821	880.12990	1341.87000	394.48510	496.22310	100.10000	2.50116	890.03980
.800	-1.811	880.22120	1341.84000	394.40060	496.15260	100.00000	2.50049	890.12990
.800	-.799	880.29000	1341.94000	394.42770	496.06420	99.89999	2.50124	890.20000
.800	.208	880.39160	1341.92999	394.35160	496.25900	100.10000	2.49988	890.29980
.800	1.184	880.58180	1342.00999	394.28120	496.10400	99.89999	2.50093	890.49000
.800	2.163	880.58200	1342.02000	394.28880	496.19170	100.00000	2.50039	890.49000
GRADIENT	.07064	-.01948	-.06243	-.06243	-.00551	-.02137	-.00006	-.000334

RUN NO.	1338/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC
.900	-7.891	752.90890	1273.28000	426.81860	481.74240	100.10000	2.49891	762.91990
.900	-6.864	752.67600	1272.64999	426.52440	481.68190	100.00000	2.49807	762.67990
.900	-5.856	752.7420	1272.83000	426.58960	481.68040	100.00000	2.49843	762.77980
.900	-4.840	752.85110	1273.11000	426.73630	481.49190	99.80000	2.50025	762.85990
.900	-3.827	752.77050	1273.09000	426.77050	481.39330	99.70000	2.50088	762.77980
.900	-2.811	752.47970	1273.00000	426.88160	481.60820	100.00000	2.49928	762.49000
.900	-1.792	752.80200	1272.99001	426.68290	481.58200	99.89999	2.49941	762.80980
.900	-.782	752.49490	1272.63000	426.61840	481.56470	99.89999	2.49983	762.50000
.900	.223	752.90380	1272.92999	426.58110	481.60720	99.89999	2.49911	762.90990
.900	1.198	752.77200	1272.99001	426.70900	481.49050	99.80000	2.50003	762.77980
.900	2.177	752.68430	1272.78000	426.60860	481.49730	99.80000	2.49957	762.68990
GRADIENT	-.00236	-.04022	-.02625	-.00613	.00255	-.00012	-.000290	-.000353

RUN NO.	1327/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC
1.099	-7.937	565.42870	1206.33000	478.37260	450.72000	100.00000	2.49964	575.61990
1.099	-6.912	564.95730	1206.34000	478.56470	450.61160	100.00000	2.49988	575.14990
1.099	-5.909	564.69870	1206.16000	478.56200	450.65230	100.10000	2.49901	574.88990
1.099	-4.904	564.57100	1205.92000	478.47290	450.56840	100.00000	2.49910	574.76000
1.099	-3.904	564.61130	1205.92000	478.45700	450.65800	100.10000	2.49850	574.79980
1.099	-2.917	564.63960	1206.05000	478.52150	450.48950	99.89999	2.49995	574.82980
1.099	-1.896	564.81030	1206.05000	478.45410	450.52830	99.89999	2.49987	575.00000
1.099	-.924	564.74850	1206.17000	478.54810	450.66260	100.10000	2.49901	574.93990
1.099	.079	564.96000	1206.10001	478.42410	450.55710	99.89999	2.49992	575.14990
1.099	1.067	565.02030	1206.09000	478.39430	450.73320	100.10000	2.49870	575.21000
1.099	2.057	565.12230	1205.95000	478.27270	450.61010	99.89999	2.49949	575.30980
1.099	.08147	.01593	-.02290	-.01200	-.00602	-.00003	.08142	.01066

## PARAMETRIC DATA

RUN NO.	1373/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	3.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PADM
ALPHA	.04050	1198.13000	505.80300	427.45970	101.20000	2.49336	473.16990	905.40990	1.19521 2041.86501
-7.914	463.04050	1198.13000	506.06370	427.35400	101.20000	2.49417	472.92990	905.42990	1.19798 2041.86501
-6.882	462.79860	1198.53999	505.89990	427.31760	101.20000	2.49319	472.60990	905.45000	1.19844 2041.86501
-1.250	462.48290	1198.08000	505.77880	427.33130	101.20000	2.49266	472.55980	905.48000	1.20188 2041.86501
-5.876	462.43460	1197.82001	505.77080	427.28470	101.20000	2.49240	472.33980	905.49000	1.19881 2041.86501
-4.869	462.21610	1197.71001	505.94630	427.29690	101.20000	2.49243	472.38890	905.52980	1.20198 2041.89999
-3.858	462.21610	1197.71001	505.94630	427.32420	101.20000	2.49322	472.63990	905.52980	1.20161 2041.89999
-2.845	462.26560	1197.72000	505.76510	427.35110	101.20000	2.49365	472.81980	905.54980	1.20141 2041.89999
-1.834	462.51250	1198.09000	505.89840	427.35990	101.20000	2.49294	472.72000	905.55980	1.20175 2041.89999
-1.250	462.69070	1198.28999	505.96090	427.35010	101.20000	2.49308	472.71000	905.61990	1.20488 2041.93500
-828	462.59330	1197.95000	505.8980	427.32760	101.20000	2.49308	472.71000	905.61990	1.20488 2041.93500
-177	462.57150	1198.21001	505.94630	427.35010	101.20000	2.49308	472.71000	905.61990	1.20488 2041.93500
1.157	462.58280	1198.02000	505.84770	427.35010	101.20000	2.49308	472.71000	905.61990	1.20488 2041.93500
1.250	462.58280	1198.02000	505.01852	.00668	-.00000	.000012	.04784	.01943	.00040 .00788
GRADIENT	.04729	.05698							

RUN NO. 1384/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1384/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	3.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PADM
ALPHA	.08840	1215.41000	524.00660	403.04300	101.30000	2.49199	391.79980	920.58980	1.16884 2041.58501
-7.924	382.08840	1215.41000	523.97530	402.99410	101.30000	2.49171	391.60990	920.59990	1.16722 2041.58501
-6.889	381.90110	1215.33000	523.75220	402.98170	101.30000	2.49061	391.33990	920.60990	1.15705 2041.58501
-5.884	381.69650	1214.81000	523.81000	403.02440	101.30000	2.49069	391.53980	920.61990	1.15399 2041.62000
-4.877	381.83500	1214.80000	523.74490	403.02440	101.30000	2.49157	391.53980	920.62990	1.15353 2041.58501
-3.871	381.83200	1215.28000	523.95480	402.97800	101.30000	2.49160	391.27980	920.62990	1.14782 2041.58501
-2.858	381.57760	1214.85001	523.97200	402.94190	101.30000	2.49121	391.42990	920.60990	1.15983 2041.62000
-1.846	381.72410	1215.13000	523.89140	402.95970	101.30000	2.49128	391.33990	920.62990	1.15363 2041.62000
-0.842	381.69430	1215.17999	523.91410	402.94600	101.30000	2.49136	391.54980	920.60990	1.15058 2041.62000
.162	381.84280	1215.16000	523.90230	402.99270	101.30000	2.48984	391.67990	920.60990	1.14806 2041.65500
1.144	381.97490	1214.60001	523.65450	403.15720	101.40000	2.49068	391.50000	920.60990	1.14481 2041.65500
1.399	381.79540	1214.81000	523.75020	403.01150	101.30000	.00592	-.00007	.01417	-.00250 -.00106
2.136	381.01419	-.02764	-.01115						
GRADIENT	.01419	-.02764							
RUN NO.	1397/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	3.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PADM
ALPHA	.03820	1226.96001	528.61550	394.63840	100.70000	2.49743	369.12990	932.34990	1.39973 2041.93500
-7.881	359.63820	1226.96001	528.10000	394.16380	100.60000	2.49469	367.50980	932.38990	1.39726 2041.93500
-6.841	358.04660	1225.92000	528.25660	394.34740	100.60000	2.49583	368.18990	932.46000	1.38964 2041.93500
-5.831	358.71560	1226.21001	528.15380	394.37700	100.60000	2.49542	368.21000	932.50980	1.38629 2041.93500
-4.816	358.12250	1225.96001	528.95240	394.31620	100.50000	2.49981	368.79980	932.54980	1.38420 2041.97000
-3.797	359.30860	1227.81000	529.07080	394.39820	100.60000	2.49979	368.91990	932.57980	1.38028 2041.97000
-2.771	359.42530	1228.08000	528.53880	394.42190	100.50000	2.49809	368.83980	932.57980	1.38171 2042.00500
-1.750	359.35330	1226.81000	528.53880	394.34590	100.50000	2.49641	368.37990	932.62990	1.37889 2042.00500
-1.450	358.90330	1226.10001	528.22070	394.32350	100.50000	2.49529	368.14990	932.61990	1.37587 2042.00500
-1.274	358.67920	1225.58000	527.99290	394.39700	100.50000	2.49647	368.52980	932.63990	1.36458 2042.00500
-1.450	359.05150	1226.21001	528.28220	394.43460	100.50000	2.49690	368.70000	932.66990	1.36083 2042.03999
-1.449	359.21800	1226.21001	528.28220	394.43460	100.50000	.00592	-.00025	-.00835	-.002058 -.00344
2.224	359.18049	-.07546							
GRADIENT	-.00731	-.18049							

PREF

.00040

.00788

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

.00040

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

(VCM039) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	RN/L	=	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	3.000	PHI	=	180.000
1.471	-7.885	347.97120	1224.32179	526.75690	390.89330	101.30000	2.49111	357.30980	897.60990	1.29865	2042.	98500			PATM
1.471	-6.853	347.77440	1224.66463	526.88033	390.83110	101.30000	2.49089	357.10990	897.60990	1.27831	2042.	98500			
1.471	-5.839	347.88330	1224.75262	526.92577	390.87670	101.30000	2.49079	357.22000	897.58980	1.26837	2042.	98500			
1.471	-4.824	347.88260	1225.00377	527.02752	390.86470	101.30000	2.49102	357.22000	897.58980	1.26157	2042.	98500			
1.471	-3.813	347.89400	1224.68523	526.89964	390.96800	101.40000	2.48987	357.23000	897.59990	1.26191	2042.	95000			
1.471	-2.791	347.87260	1224.99809	527.02437	390.85620	101.30000	2.49111	357.21000	897.58980	1.26484	2042.	98500			
1.471	-1.767	347.90090	1225.23518	527.12400	390.84350	101.30000	2.49155	357.24000	897.56980	1.26459	2042.	95000			
1.471	-7.755	347.95190	1224.47154	526.81661	390.96020	101.40000	2.49043	357.28980	897.56980	1.28848	2042.	98500			
1.470	.256	347.96360	1223.99117	526.62194	390.93330	101.30000	2.49029	357.29980	897.56980	1.29233	2042.	98500			
1.471	1.229	347.97140	1224.40097	526.78905	390.96750	101.40000	2.49043	357.30980	897.54980	1.29189	2043.	02000			
1.471	2.209	347.93120	1224.50653	526.82868	390.93820	101.40000	2.49070	357.26980	897.54980	1.29510	2042.	98500			
1.471	0.1246	-.10295	-.04100	.01014	.00939	-.00004	.01265	-.00004	-.00699	.00581	.00452				

MACH	ALPHA	P	PT	RN/L	=	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	3.000	PHI	=	180.000
1.496	-7.892	337.42160	1231.17653	528.44485	386.93630	101.40000	2.49037	346.60990	943.75000	1.17758	2042.	28500			PATM
1.496	-6.856	337.28370	1231.25125	528.45791	386.81320	101.30000	2.49097	346.47000	943.75980	1.17749	2042.	28500			
1.496	-5.845	337.29390	1231.28250	528.47218	386.89180	101.40000	2.49027	346.48000	943.75980	1.17132	2042.	28500			
1.496	-4.833	337.42040	1231.67955	528.64499	386.90720	101.40000	2.49091	346.60990	943.74000	1.16486	2042.	28500			
1.496	-3.821	337.57590	1232.03273	528.80270	386.92800	101.40000	2.49166	346.76980	943.74000	1.16454	2042.	28500			
1.496	-2.798	337.49830	1231.76910	528.68908	386.92110	101.40000	2.49122	346.88900	943.74000	1.16783	2042.	28500			
1.496	-1.781	337.64750	1231.51382	528.60616	387.00950	101.40000	2.49064	346.83980	943.72000	1.15898	2042.	28500			
1.496	.768	337.43070	1231.70975	528.65746	386.92600	101.40000	2.49063	346.61990	943.72000	1.15271	2042.	32001			
1.496	.241	337.46900	1231.96671	528.76426	386.91530	101.40000	2.49112	346.65990	943.72000	1.15247	2042.	32001			
1.496	1.216	337.49880	1231.93301	528.75462	386.92850	101.40000	2.49108	346.68990	943.67990	1.15251	2042.	28500			
1.496	2.194	337.51880	1231.78218	528.69674	386.94510	101.40000	2.49092	346.71000	943.67990	1.15568	2042.	32001			
1.496	0.00002	-.00002	.01184	.00468	.00198	-.00000	-.00004	-.00000	-.000011	-.00922	-.000210				

MACH	ALPHA	P	PT	RN/L	=	2.49	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	3.000	PHI	=	180.000
1.517	-7.894	327.65650	1233.59018	528.06966	382.96850	101.30000	2.49182	336.68990	911.92990	1.41070	2043.	16000			PATM
1.517	-6.856	327.29350	1233.39922	527.94057	382.90940	101.40000	2.49088	336.31980	911.92990	1.42541	2043.	16000			
1.517	-5.846	327.25630	1232.86917	527.72977	382.94430	101.40000	2.48994	336.27980	911.95000	1.42603	2043.	16000			
1.517	-4.834	327.35550	1233.00056	527.79526	383.00020	101.40000	2.48963	336.37990	911.92990	1.40051	2043.	16000			
1.517	-3.816	327.21580	1233.43178	527.94061	382.83540	101.30000	2.49100	336.24000	911.95000	1.40720	2043.	16000			
1.517	-2.798	327.41140	1233.63155	528.04861	382.95310	101.40000	2.49095	336.43990	911.91990	1.40699	2043.	16000			
1.517	-1.780	326.95260	1232.95187	527.71501	382.77810	101.30000	2.49008	335.97000	911.91990	1.41496	2043.				
1.517	-.767	327.26730	1232.37839	527.54183	382.97800	101.40000	2.48939	336.28980	911.91990	1.43762	2043.	19501			
1.517	.238	327.04980	1232.83746	527.68681	382.79300	101.30000	2.49054	336.46980	911.90990	1.43704	2043.	19501			
1.517	1.216	327.58810	1233.03619	527.84517	383.02440	101.40000	2.49094	336.61990	911.88990	1.44057	2043.	19501			
1.517	2.194	327.74610	1232.83752	527.79200	383.10180	101.40000	2.49068	336.77980	911.88990	1.43714	2043.	19501			
1.517	0.4462	-.07227	-.02106	.01602	.00348	-.00006	.00006	.00006	.00459	.00559	-.000210				

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

( VCM039 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1420/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	3.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PARM
1.543	-7.891	317.71730	124.1.24956	529.30509	378.54860	100.70000	2.49483	326.56980	899.56980	1.29621 2042.88000
	-6.859	317.65820	124.1.39061	529.34711	378.52000	100.70000	2.49491	326.50980	899.55980	1.29271 2042.84500
	-5.844	317.57060	124.1.28456	529.29086	378.50290	100.70000	2.49454	326.41990	899.55980	1.28947 2042.84500
	-4.834	317.58010	124.1.35450	529.31838	378.50020	100.70000	2.49467	326.42990	899.54980	1.28940 2042.84500
	-3.820	317.59940	124.1.55516	529.39909	378.49830	100.70000	2.49486	326.45000	899.54980	1.28254 2042.84500
	-2.798	317.59060	124.1.36118	529.32426	378.51660	100.70000	2.49444	326.43990	899.53980	1.27942 2042.84500
	-1.780	317.60910	124.1.59544	529.41551	378.49800	100.70000	2.49494	326.46000	899.53980	1.28250 2042.84500
	-767	317.56010	124.1.58736	529.40340	378.47710	100.70000	2.49495	326.40990	899.52980	1.28582 2042.84500
	-240	317.64840	124.1.48146	529.38007	378.51760	100.70000	2.49488	326.50000	899.50000	1.28594 2042.88000
	1.215	317.57890	124.1.70442	529.45166	378.46870	100.70000	2.49526	326.42990	899.51000	1.28903 2042.84500
	2.193	317.45410	124.1.03630	529.17513	378.48410	100.70000	2.49399	326.29980	899.51000	1.28972 2042.88000
GRADIENT	-0.1004	-0.01286	-0.00672	-.00328	-.000000	-.000000	-.01029	-.00029	-.000720	.00068 .00413

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

## PARAMETRIC DATA

	RUN NO.	1360/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PARM
.599	-7.846	1252.56599	1596.73000	314.87080	521.79320	99.59999	2.49861	1262.31000	1300.50999	.70236 2043.02000
	-6.821	1252.22400	1597.06000	315.42870	521.72170	99.59999	2.50092	1261.98000	1300.49001	.70412 2043.02000
	-5.807	1252.03300	1596.96001	315.50150	521.70830	99.59999	2.50110	1261.78999	1300.48000	.69468 2043.02000
	-4.791	1252.06599	1596.81000	315.34790	521.72630	99.59999	2.50042	1261.82001	1300.42999	.69663 2043.02000
	-3.770	1251.89900	1597.03000	315.66940	521.68580	99.59999	2.50177	1261.66000	1300.42000	.69465 2043.02000
	-2.748	1251.29601	1596.72000	315.90380	521.64280	99.59999	2.50236	1261.06000	1300.42000	.69479 2043.02000
	-1.729	1251.78700	1597.56000	316.20730	521.62300	99.59999	2.50417	1261.56000	1300.41000	.69067 2043.02000
	-717	1251.48700	1596.87000	315.87380	521.65160	99.59999	2.50238	1261.25000	1300.39000	.69284 2043.05499
	.292	1251.70500	1596.62000	315.48460	521.70090	99.59999	2.50075	1261.46001	1300.38000	.69295 2043.05499
	1.274	1251.64700	1596.95000	315.80930	521.66330	99.59999	2.50221	1261.41000	1300.39000	.70607 2043.02000
	2.252	1251.61501	1597.53000	316.32280	521.60520	99.59999	2.50457	1261.39000	1300.36000	.70965 2043.05499
GRADIENT	-0.4151	.04271	.06998	-.00895	-.00000	-.00000	-.04009	-.000922	-.000169	.00455 .00169

## PARAMETRIC DATA

	RUN NO.	1360/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PARM
.599	-7.846	1252.56599	1596.73000	314.87080	521.79320	99.59999	2.49861	1262.31000	1300.50999	.70236 2043.02000
	-6.821	1252.22400	1597.06000	315.42870	521.72170	99.59999	2.50092	1261.98000	1300.49001	.70412 2043.02000
	-5.807	1252.03300	1596.96001	315.50150	521.70830	99.59999	2.50110	1261.78999	1300.48000	.69468 2043.02000
	-4.791	1252.06599	1596.81000	315.34790	521.72630	99.59999	2.50042	1261.82001	1300.42999	.69663 2043.02000
	-3.770	1251.89900	1597.03000	315.66940	521.68580	99.59999	2.50177	1261.66000	1300.42000	.69465 2043.02000
	-2.748	1251.29601	1596.72000	315.90380	521.64280	99.59999	2.50236	1261.06000	1300.42000	.69479 2043.02000
	-1.729	1251.78700	1597.56000	316.20730	521.62300	99.59999	2.50417	1261.56000	1300.41000	.69067 2043.02000
	-717	1251.48700	1596.87000	315.87380	521.65160	99.59999	2.50238	1261.25000	1300.39000	.69284 2043.05499
	.292	1251.70500	1596.62000	315.48460	521.70090	99.59999	2.50075	1261.46001	1300.38000	.69295 2043.05499
	1.274	1251.64700	1596.95000	315.80930	521.66330	99.59999	2.50221	1261.41000	1300.39000	.70607 2043.02000
	2.252	1251.61501	1597.53000	316.32280	521.60520	99.59999	2.50457	1261.39000	1300.36000	.70965 2043.05499
GRADIENT	-0.4151	.04271	.06998	-.00895	-.00000	-.00000	-.04009	-.000922	-.000169	.00455 .00169

## PARAMETRIC DATA

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 930  
( VCM040 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1349/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
.800	-7.878	880.78470	134.1.97000	394.11380	495.96340	99.70000	2.50160	890.68990	1046.98000	.81571 2043.89500
.799	-6.856	880.99580	1342.03000	394.01460	495.99100	99.70000	2.50141	890.89990	1046.97000	.81789 2043.89500
.800	-5.842	880.53540	1341.77000	394.13530	496.21040	100.00000	2.49991	890.43990	1046.97000	.81805 2043.89500
.800	-4.833	880.50950	1341.13000	394.14940	496.07960	99.89999	2.50143	890.41990	1046.97000	.82676 2043.89500
.800	-3.822	880.30000	1341.95000	394.42850	496.06490	99.89999	2.50125	890.21000	1046.96001	.81794 2043.89500
.800	-2.809	880.22530	1342.22000	394.67900	495.93580	99.80000	2.50278	890.13990	1046.96001	.81778 2043.89500
.800	-1.795	880.44170	1341.94000	394.32470	495.91140	99.70000	2.50212	890.34990	1046.94000	.82017 2043.92999
.800	-.792	880.45140	1341.97000	394.34060	495.99850	99.80000	2.50162	890.35990	1046.92999	.81571 2043.89500
.800	.216	880.60570	1341.78999	394.10210	495.95360	99.70000	2.50137	890.51000	1046.91000	.81804 2043.89500
.800	1.200	880.47830	1342.17000	394.47000	495.89310	99.70000	2.50275	890.38990	1046.91000	.81559 2043.89500
.800	2.182	880.72410	1341.95000	394.13907	496.04440	99.80000	2.50107	890.62990	1046.91000	.82911 2043.89500
GRADIENT	.04194	-.01697	-.04111	-.01156	-.02265	.00000	.04129	-.00986	.00000	-.00042

	RUN NO.	1339/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
.900	-7.870	753.03080	1273.23000	426.71190	481.51200	99.80000	2.50034	763.03980	977.78980	.99470 2044.21001
.899	-6.842	753.13530	1272.95000	426.45730	481.56130	99.80000	2.49944	763.13990	977.81980	.98430 2044.24500
.900	-5.832	752.88430	1272.88000	426.55830	481.52290	99.80000	2.49958	762.88990	977.80980	.98435 2044.21001
.900	-4.818	752.67580	1272.67000	426.53830	481.59350	99.89999	2.49870	762.67990	977.81980	.98188 2044.24500
.900	-3.806	752.61330	1272.81000	426.67160	481.48100	99.80000	2.49974	762.16990	977.79980	.98441 2044.24500
.900	-2.795	752.61990	1273.07001	426.84640	481.54000	99.89999	2.49887	762.62990	977.80980	.98421 2044.21001
.900	-1.780	752.55830	1273.13000	426.92410	481.60840	100.00000	2.49953	762.56980	977.80980	.98416 2044.21001
.900	-.774	752.69170	1272.97000	426.65010	481.65010	100.00000	2.49892	762.70000	977.80980	.98428 2044.21001
.900	.234	752.84470	1272.84000	426.55440	481.69210	100.00000	2.49837	762.84990	977.81980	.97649 2044.21001
.900	1.214	752.79270	1272.95000	426.66110	481.75680	100.10000	2.49816	762.79980	977.81980	.97903 2044.21001
.900	2.199	752.76490	1272.77000	426.55400	481.77120	100.10000	2.49770	762.76980	977.81980	.97917 2044.21001
GRADIENT	.02761	.00675	-.01179	.03698	.03795	-.00024	.02749	.00154	-.00082	-.000501

	RUN NO.	1328/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.099	-7.928	565.55880	1206.36000	478.33840	450.74630	100.00000	2.49964	575.75000	864.26980	.75131 2044.87500
1.100	-6.901	564.82200	1205.89000	478.35640	450.54810	99.89999	2.49950	575.01000	864.25000	.75160 2044.87500
1.100	-5.904	564.72220	1205.86000	478.37840	450.68970	100.10000	2.49831	574.90990	864.28980	.74336 2044.87500
1.100	-4.898	564.55100	1205.92999	478.48680	450.48220	99.89999	2.49972	574.74000	864.28980	.75365 2044.87500
1.100	-3.898	564.43090	1205.91000	478.52250	450.45680	99.89999	2.49973	574.61990	864.30980	.74951 2044.87500
1.100	-2.902	564.72240	1205.84000	478.36670	450.53080	99.89999	2.49943	574.90990	864.29980	.74132 2044.87500
1.100	-1.906	564.96240	1205.88000	478.29520	450.74220	100.10000	2.49824	575.14990	864.33980	.73721 2044.87500
1.100	-.926	564.85110	1205.97000	478.39140	450.62670	100.00000	2.49908	575.03980	864.33980	.73715 2044.87500
1.100	.093	564.91260	1205.85001	478.29740	450.57300	99.89999	2.49936	575.09990	864.33980	.74131 2044.84000
1.100	1.092	565.09230	1205.95000	478.28470	450.76440	100.10000	2.49834	575.27980	864.36990	.73717 2044.87500
1.100	2.068	565.01730	1206.35001	478.54690	450.70460	100.10000	2.49929	575.21000	864.37900	.74101 2044.87500
GRADIENT	.08406	.03884	-.01061	.03712	.02747	-.00011	.08428	.01256	-.00180	-.00127

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 931

(VCM040) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.249	-7.898	463.06790	1198.53999	506.00490	427.34890	101.10000	2.49479	473.20000	905.73000	1.20435	2041.97000
-6.866	462.81180	1198.08000	505.82790	427.32810	101.10000	2.49382	472.93990	905.75000	1.20482	2041.97000	
1.250	-5.859	462.58280	1198.03000	505.85280	427.27270	101.10000	2.49369	472.71000	905.77980	1.20167	2041.93500
1.250	-4.849	462.62330	1197.95000	505.80350	427.29150	101.10000	2.49353	472.75000	905.78980	1.20175	2041.97000
1.250	-3.843	462.35620	1197.60001	505.68430	427.18070	101.00000	2.49337	472.48000	905.78980	1.19892	2041.97000
1.250	-2.837	462.59080	1198.28000	505.97750	427.17330	101.00000	2.49478	472.72000	905.80980	1.19824	2041.93500
1.250	-1.821	462.58150	1198.20000	505.93920	427.17900	101.00000	2.49462	472.71000	905.83980	1.19832	2041.93500
1.250	-820	462.36250	1198.14999	505.96170	427.12620	101.00000	2.49449	472.49000	905.83980	1.20155	2041.93500
1.250	.186	462.44410	1197.87000	505.80200	427.17630	101.00000	2.49393	472.56980	905.87990	1.19547	2041.93500
1.250	1.168	462.42530	1197.70000	505.72270	427.1250	100.90000	2.49417	472.54980	905.85990	1.19247	2041.93500
1.249	2.159	462.85280	1197.89000	505.72270	427.20580	100.90000	2.49461	472.98000	905.88990	1.18912	2041.89999
GRADIENT	.01518	-.01407	-.01045	-.01174	-.02254	.00011	.01513	.01499	-.00149	-.00790	

RUN NO. 1385/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.400	-7.865	381.94170	1215.16000	523.90010	403.09420	101.40000	2.49084	391.64990	920.59990	1.17219	2041.69000
1.400	-6.874	382.00000	1215.31000	523.96460	403.02590	101.30000	2.49174	391.71000	920.59990	1.16894	2041.69000
1.400	-5.869	381.62520	1215.14000	523.89770	403.00070	101.40000	2.49057	391.32980	920.59990	1.17221	2041.72501
1.400	-4.857	381.69980	1214.48000	523.60790	403.01370	101.30000	2.49001	391.39990	920.62990	1.14817	2041.72501
1.400	-3.856	381.81420	1215.00000	523.83280	403.07100	101.40000	2.49045	391.51980	920.59990	1.14768	2041.72501
1.400	-2.846	381.84240	1215.20000	523.91990	402.98880	101.30000	2.49143	391.54980	920.61990	1.15054	2041.72501
1.400	-1.837	381.92940	1215.50999	524.05370	403.05740	101.40000	2.49147	391.63990	920.61990	1.14719	2041.75999
1.400	-.834	381.83500	1214.82001	523.75370	403.02250	101.30000	2.49073	391.53980	920.61990	1.16631	2041.75999
1.400	.171	381.833620	1214.61000	523.66190	403.04270	101.30000	2.49035	391.53980	920.61990	1.16341	2041.75999
1.400	1.156	381.76460	1214.98000	523.82520	403.05790	101.40000	2.49038	391.47000	920.60990	1.15689	2041.79500
1.400	2.146	381.85250	1215.16000	523.90210	403.06740	101.40000	2.49077	391.55980	920.62990	1.15672	2041.79500
GRADIENT	.00856	.02610	.01124	.00518	.00709	.00001	.00884	.000059	.000195	.01122	

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.450	-7.810	358.99020	1226.44000	528.36650	394.34200	100.50000	2.49709	368.47000	932.72000	1.36414	2042.07500
1.450	-6.817	358.75460	1226.27000	528.28370	394.28370	100.50000	2.49657	368.23000	932.73000	1.36433	2042.07500
1.450	-5.805	358.70560	1226.24001	528.26860	394.34130	100.60000	2.49588	368.17990	932.75980	1.36437	2042.11000
1.449	-4.787	359.15060	1225.95000	528.17090	394.50780	100.60000	2.49579	368.62990	932.76980	1.36112	2042.11000
1.450	-3.768	358.94310	1226.02000	528.18950	394.43630	100.60000	2.49572	368.41990	932.76980	1.35038	2042.11000
1.450	-2.754	358.67680	1226.07001	528.19630	394.41850	100.70000	2.49496	368.14990	932.78980	1.32923	2042.14500
1.450	-1.733	359.03100	1226.16000	528.25200	394.52150	100.70000	2.49545	368.50980	932.79980	1.32564	2042.11000
1.450	-.722	358.69870	1225.67999	528.03540	394.46120	100.70000	2.49429	368.16990	932.80980	1.32965	2042.14500
1.450	.286	358.73610	1226.03999	528.18700	394.43970	100.70000	2.49496	368.21000	932.80980	1.32577	2042.14500
1.450	1.268	358.79540	1225.98000	528.16500	394.53440	100.80000	2.49432	368.26980	932.83980	1.32584	2042.17999
1.450	2.247	358.92380	1225.92999	528.15090	394.57930	100.80000	2.49435	368.39990	932.83980	1.32241	2042.17999
GRADIENT	-.02960	-.01077	-.00601	-.01166	.02836	-.00022	-.03007	-.03007	.01159	.00475	.01033

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

PAGE 932

(VCMO40) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1441/ O	RN/L	=	2.49	GRADIENT INTERVAL =	-5.00/	5.00	
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
ALPHA		347.79350	1225.13557	390.82250	101.30000	2.49118	357.12990	897.51000
1.471	-7.862	347.79350	1225.14514	390.88840	101.30000	2.49148	357.34990	897.51980
1.471	-6.828	348.00980	1225.90608	390.90600	101.40000	2.49047	357.14990	897.51980
1.471	-5.815	347.81350	1224.93631	390.99445	101.40000	2.48996	357.33980	897.51000
1.471	-4.801	348.00240	1224.50392	391.00370	101.40000	2.49035	357.55980	897.51980
1.471	-3.784	348.21830	1224.12171	391.06490	101.40000	2.49074	357.40990	897.51980
1.470	-2.768	348.06930	1224.53180	390.98800	101.40000	2.49081	357.35990	897.51000
1.471	-1.753	348.01980	1224.65645	390.96580	101.40000	2.49138	357.31980	897.51980
1.471	-.743	347.98020	1224.66049	390.88260	101.30000	2.49037	357.27980	897.51000
1.471	.266	347.94360	1224.49005	390.92353	101.30000	2.49039	357.22900	897.51000
1.471	1.245	347.88280	1224.85948	390.96907	101.40000	2.49062	357.38990	897.50000
1.471	2.231	348.04980	1225.03909	390.98730	101.40000	.00005	-.02113	-.00163
GRADIENT	-.02093		.07923	.03053	-.01241	.00483		

RUN NO. 1408/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1431/ O	RN/L	=	2.49	GRADIENT INTERVAL =	-5.00/	5.00	
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
ALPHA		337.56760	1231.77090	528.69818	386.95830	101.40000	2.49103	346.75980
1.496	-7.869	337.56760	1231.47722	528.55032	386.89940	101.40000	2.49020	346.49000
1.496	-6.830	337.30400	1231.90285	528.73711	386.93680	101.40000	2.49057	346.63990
1.496	-5.823	337.45070	1231.65114	528.64298	386.97750	101.40000	2.49017	346.68990
1.496	-4.809	337.50100	1231.99771	528.78033	386.94480	101.40000	2.49078	346.68990
1.496	-3.798	337.49950	1231.08511	528.84476	387.02980	101.40000	2.49098	346.93990
1.496	-2.781	337.74510	1232.74068	529.09101	386.93090	101.40000	2.49204	346.82980
1.496	-1.766	337.63400	1232.74068	529.09101	386.93090	101.40000	2.49116	346.81980
1.496	-.758	337.62650	1232.4826	528.89486	386.97390	101.40000	2.49042	346.48000
1.496	.250	337.29350	1231.94322	528.73352	386.88350	101.40000	2.49042	346.62990
1.496	1.232	337.44120	1231.91873	528.74174	386.94090	101.40000	2.49013	346.78980
1.496	2.219	337.59960	1231.48569	528.58908	387.01780	101.40000	-.00005	-.01176
GRADIENT	-.01144		-.02856	-.01275	-.00164	-.00005		

RUN NO.	1431/ O	RN/L	=	2.49	GRADIENT INTERVAL =	-5.00/	5.00	
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
ALPHA		528.12428	382.96510	101.40000	2.49132	336.51980	911.87990	PATM
1.518	-7.867	327.48900	1233.79713	527.94512	382.97270	101.40000	2.49059	336.43990
1.518	-6.837	327.41210	1233.36475	527.77172	382.83640	101.30000	2.49002	336.10990
1.518	-5.826	327.09030	1233.04468	527.13528	383.08420	101.40000	2.49005	336.64990
1.518	-4.811	327.61990	1233.13528	528.11234	382.95630	101.30000	2.49154	336.61990
1.518	-3.796	327.58810	1233.72865	528.02079	382.92260	101.40000	2.49042	336.28980
1.518	-2.779	327.26490	1233.61932	527.86822	382.96360	101.40000	2.48965	336.28980
1.518	-1.765	327.26680	1233.22444	527.85291	382.93750	101.40000	2.48955	336.21000
1.518	-.757	327.18850	1233.21442	528.09909	382.94530	101.40000	2.49080	336.39990
1.518	.249	327.37210	1233.77890	528.12328	382.98630	101.30000	2.49171	336.72000
1.518	1.230	327.68630	1233.71768	527.83378	382.90970	101.40000	2.48963	336.14990
1.518	2.215	327.12920	1233.18977	527.00961	382.00114	-.01224	-.00003	-.03272
GRADIENT	-.03215							.00019

PATM

.00538

.00019

.00287

-.00043

-.00027

-.00016

-.00014

-.00013

-.00012

-.00011

-.00010

-.00009

-.00008

-.00007

-.00006

## IA310 (AEDC 16TF-783) FAIRING-OFF DATABASE

( VCM040 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1419/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4 . 000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
1.543	-7.866	317.48220	1241.14690	529.22186	378.53370	100.80000	2.49395	326.32980	899.66990
1.543	-6.836	317.35470	1241.26732	529.24292	378.47800	100.80000	2.49401	326.20000	899.65990
1.543	-5.825	317.52120	1241.18103	529.24181	378.54440	100.80000	2.49406	326.36990	899.66990
1.543	-4.811	317.56010	1241.19965	529.25622	378.61470	100.90000	2.49371	326.40990	899.65990
1.543	-3.796	317.41260	1241.38560	529.29821	378.47880	100.80000	2.49445	326.25980	899.63990
1.543	-2.781	317.69680	1241.07123	529.23338	378.59280	100.80000	2.49451	326.54980	899.64990
1.543	-1.766	317.74610	1241.08081	529.24579	378.61400	100.80000	2.49450	326.59990	899.63990
1.554	-758	317.53120	1260.71060	536.69828	378.48440	100.70000	2.49459	326.37990	899.62990
1.554	.248	317.66750	1260.91852	536.80334	378.58030	100.80000	2.49452	326.51980	899.62990
1.554	1.230	317.67820	1260.66441	536.70956	378.53810	100.70000	2.49472	326.52980	899.59990
1.543	2.214	317.61910	1240.99324	529.18926	378.50490	100.70000	2.49489	326.47000	899.59990
GRADIENT	.01712	2.07713	.79628	-.00755	-.02370	.00012	.01739	-.00699	-.14017 -.00168

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( VCM041 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1670/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4 . 000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
.600	-8.125	1252.29601	1596.99001	315.31050	521.64360	99.50000	2.50100	1262.05000	1301.22000
.600	-7.121	1252.08299	1596.50999	315.08230	521.75610	99.59999	2.49920	1261.83000	1301.22000
.600	-6.140	1251.84200	1596.89000	315.59960	521.78540	99.70000	2.50083	1261.60001	1301.22000
.601	-5.164	1251.49300	1597.02000	315.99410	521.82500	99.80000	2.50180	1261.25999	1301.24001
.600	-4.188	1251.50400	1596.50999	315.55710	521.96700	99.89999	2.49921	1261.25999	1301.22000
.600	-3.220	1251.33000	1596.56000	315.74170	521.84840	99.80000	2.50049	1261.09000	1301.22000
.601	-2.253	1250.81400	1596.94000	316.48340	521.75150	99.80000	2.50351	1260.59000	1301.22000
.601	-1.284	1251.27499	1596.77000	315.96340	521.82230	99.80000	2.50148	1261.03999	1301.21001
.600	-.291	1251.36099	1596.53000	315.69090	521.94820	99.89999	2.49972	1261.12000	1301.20000
.600	.704	1252.44901	1596.94000	315.14260	522.03960	99.89999	2.49807	1262.20000	1301.21001
.600	1.729	1252.49400	1597.25000	315.36690	521.82930	99.70000	2.50029	1262.25000	1301.21001
GRADIENT	.21033	.09359	-.09388	.00605	-.01101	-.00020	.20904	-.00253	-.16949 -.00382

( VCM041 ) ( 04 OCT 91 )

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM041) ( 04 OCT 91 )

PARAMETRIC DATA

GRADIENT INTERVAL = - 5.00 / 5.00

MACH	ALPHA	P	P <sub>T</sub>	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
.900	-8.098	752.51560	1272.57001	426.56470	481.48900	99.80000	2.49921	762.51980	979.31980	1.67335 2028.91499
.900	-7.081	753.01980	1273.28000	426.75270	481.41850	99.70000	2.50107	763.02980	979.42990	1.66813 2028.88000
.900	-6.098	752.68310	1272.85001	426.65750	481.40330	99.70000	2.50034	762.68990	979.52980	1.66441 2028.84500
.900	-5.113	753.05100	1273.21001	426.68600	481.34570	99.59999	2.50142	763.05980	979.60990	1.65966 2028.88000
.900	-4.135	752.69700	1273.30000	426.95850	481.18530	99.50000	2.50271	762.71000	979.66990	1.64679 2028.88000
.900	-3.165	752.6740	1272.97000	426.74710	481.30220	99.59999	2.50126	762.67990	979.74000	1.62615 2028.88000
.900	-2.186	752.51050	1272.96001	426.83590	481.27390	99.59999	2.50144	762.51980	979.81980	1.62617 2028.88000
.900	-1.213	752.42110	1272.85001	426.81320	481.35550	99.70000	2.50068	762.42990	979.90990	1.60963 2028.91499
.900	-2.16	752.58300	1272.82001	426.69650	481.138840	99.70000	2.50039	762.58980	980.00000	1.60139 2028.88000
.900	.777	752.72270	1272.91000	426.67530	481.49020	99.80000	2.499987	762.73000	980.05980	1.59715 2028.88000
.900	1.798	752.98710	1273.45000	426.88890	481.56620	99.89999	2.50043	763.00000	980.16990	1.60473 2028.88000
	GRADIENT	.03839	.00774	-.01753	.05911	.06152	-.00038	.03822	.08389	-.000753

RUN NO. - 17338 / Q RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 935

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCMO41) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1722/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA = -4.000	PHI = 180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L
1.249	-8.032	462.86110	1198.13000	505.84230	427.03120	100.70000
1.250	-7.062	462.64380	1197.82001	505.73290	427.00560	100.70000
1.250	-6.074	462.45190	1198.21001	505.97270	426.99150	100.80000
1.250	-5.084	462.26420	1197.97000	505.89210	426.89010	100.70000
1.249	-4.101	462.76420	1197.73000	505.66110	427.04640	100.70000
1.250	-3.120	462.41260	1198.10001	505.92530	426.91600	100.70000
1.250	-2.142	462.61210	1198.12000	505.89210	426.96660	100.70000
1.250	-1.167	462.51420	1197.84000	505.77150	426.96920	100.70000
1.250	-1.160	462.56200	1198.13000	505.90800	426.95240	100.70000
1.250	.832	462.51290	1198.03999	505.87300	426.87230	100.60000
1.250	1.844	462.62210	1198.09000	505.87450	426.89600	100.60000
GRADIENT	-.00980	.03501	.01987	-.01995	-.01810	.000118
RUN NO. 1711/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00			
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L
1.400	-8.024	381.84960	1215.64999	524.11650	402.44530	100.60000
1.400	-7.050	381.91260	1215.06000	523.85690	402.52030	100.60000
1.400	-6.066	381.79320	1215.17999	523.91210	402.47290	100.60000
1.400	-5.073	381.80520	1214.85001	523.76760	402.50780	100.60000
1.400	-4.090	381.64450	1215.24001	523.94120	402.35060	100.50000
1.400	-3.110	381.85330	1215.06000	523.85840	402.43040	100.50000
1.400	-2.131	381.71630	1214.82001	523.75610	402.41190	100.50000
1.400	-1.150	381.91480	1214.71001	523.70390	402.48220	100.50000
1.400	-.151	381.90310	1215.00000	523.83110	402.45120	100.50000
1.399	.842	382.14010	1215.05000	523.84810	402.51780	100.50000
1.400	1.857	381.85470	1214.83000	523.75760	402.45260	100.50000
GRADIENT	.04999	-.03838	-.01781	.01868	-.00000	-.000003
RUN NO. 1704/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00			
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L
1.450	-.8.114	358.90280	1226.17999	528.25370	394.40890	100.60000
1.450	-7.110	359.04200	1225.96001	528.16940	394.47270	100.60000
1.450	-6.125	358.83400	1226.19000	528.25440	394.38620	100.60000
1.450	-5.141	358.96090	1226.39000	528.34420	394.40770	100.60000
1.449	-4.168	359.35640	1226.14999	528.26440	394.55400	100.60000
1.450	-3.200	358.77590	1226.00000	528.17260	394.45580	100.70000
1.450	-2.227	358.82690	1225.64000	528.02540	394.50510	100.70000
1.450	-1.261	358.64870	1225.84000	528.09940	394.43070	100.70000
1.450	-.261	359.01250	1225.98000	528.17630	394.53200	100.70000
1.450	.731	359.07180	1225.94000	528.16260	394.55440	100.70000
1.450	1.752	358.77690	1225.78000	528.08110	394.47630	100.70000
GRADIENT	-.03446	-.03210	-.01510	-.00028	.01080	-.00015

RUN NO. 1704/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA = -4.000	PHI = 180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L
1.450	-.8.114	358.90280	1226.17999	528.25370	394.40890	100.60000
1.450	-7.110	359.04200	1225.96001	528.16940	394.47270	100.60000
1.450	-6.125	358.83400	1226.19000	528.25440	394.38620	100.60000
1.450	-5.141	358.96090	1226.39000	528.34420	394.40770	100.60000
1.449	-4.168	359.35640	1226.14999	528.26440	394.55400	100.60000
1.450	-3.200	358.77590	1226.00000	528.17260	394.45580	100.70000
1.450	-2.227	358.82690	1225.64000	528.02540	394.50510	100.70000
1.450	-1.261	358.64870	1225.84000	528.09940	394.43070	100.70000
1.450	-.261	359.01250	1225.98000	528.17630	394.53200	100.70000
1.450	.731	359.07180	1225.94000	528.16260	394.55440	100.70000
1.450	1.752	358.77690	1225.78000	528.08110	394.47630	100.70000
GRADIENT	-.03446	-.03210	-.01510	-.00028	.01080	-.00015
RUN NO. 1711/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00			
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L
1.400	-8.024	381.84960	1215.64999	524.11650	402.44530	100.60000
1.400	-7.050	381.91260	1215.06000	523.85690	402.52030	100.60000
1.400	-6.066	381.79320	1215.17999	523.91210	402.47290	100.60000
1.400	-5.073	381.80520	1214.85001	523.76760	402.50780	100.60000
1.400	-4.090	381.64450	1215.24001	523.94120	402.35060	100.50000
1.400	-3.110	381.85330	1215.06000	523.85840	402.43040	100.50000
1.400	-2.131	381.71630	1214.82001	523.75610	402.41190	100.50000
1.400	-1.150	381.91480	1214.71001	523.70390	402.48220	100.50000
1.400	-.151	381.90310	1215.00000	523.83110	402.45120	100.50000
1.399	.842	382.14010	1215.05000	523.84810	402.51780	100.50000
1.400	1.857	381.85470	1214.83000	523.75760	402.45260	100.50000
GRADIENT	.04999	-.03838	-.01781	.01868	-.00000	-.000003
RUN NO. 1722/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00			
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L
1.400	-8.032	462.86110	1198.13000	505.84230	427.03120	100.70000
1.400	-7.062	462.64380	1197.82001	505.73290	427.00560	100.70000
1.400	-6.074	462.45190	1198.21001	505.97270	426.99150	100.80000
1.400	-5.084	462.26420	1197.97000	505.89210	426.89010	100.70000
1.400	-4.101	462.76420	1197.73000	505.66110	427.04640	100.70000
1.400	-3.120	462.41260	1198.10001	505.92530	426.91600	100.70000
1.400	-2.142	462.61210	1198.12000	505.89210	426.96660	100.70000
1.400	-1.167	462.51420	1197.84000	505.77150	426.96920	100.70000
1.400	-1.160	462.56200	1198.13000	505.90800	426.95240	100.70000
1.400	.832	462.51290	1198.03999	505.87300	426.87230	100.60000
1.400	1.844	462.62210	1198.09000	505.87450	426.89600	100.60000
GRADIENT	-.00980	.03501	.01987	-.01995	-.01810	.000118
RUN NO. 1711/ 0		RN/L = 2.50	GRADIENT INTERVAL = -5.00/ 5.00			
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L
1.400	-8.024	381.84960	1215.64999	524.11650	402.44530	100.60000
1.400	-7.050	381.91260	1215.06000	523.85690	402.52030	100.60000
1.400	-6.066	381.79320	1215.17999	523.91210	402.47290	100.60000
1.400	-5.073	381.80520	1214.85001	523.76760	402.50780	100.60000
1.400	-4.090	381.64450	1215.24001	523.94120	402.35060	100.50000
1.400	-3.110	381.85330	1215.06000	523.85840	402.43040	100.50000
1.400	-2.131	381.71630	1214.82001	523.75610	402.41190	100.50000
1.400	-1.150	381.91480	1214.71001	523.70390	402.48220	100.50000
1.400	-.151	381.90310	1215.00000	523.83110	402.45120	100.50000
1.399	.842	382.14010	1215.05000	523.84810	402.51780	100.50000
1.400	1.857	381.85470	1214.83000	523.75760	402.45260	100.50000
GRADIENT	.04999	-.03838	-.01781	.01868	-.00000	-.000003

DATE 04 OCT 91

## IA310 (AEDC 16TF-783) TABULATED DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( PAGE 936 )

( VCM041 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO. 1697/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.470	-8.064	348.43530	1225.37740	527.22330	390.18680	100.30000	2.50058	357.78980	887.37990	1.33482	2030.24500
1.470	-7.098	348.17460	1224.32753	526.77459	390.19730	100.30000	2.49850	357.51980	887.37990	1.33595	2030.24500
1.470	-6.113	348.15360	1224.68347	526.91853	390.16360	100.30000	2.49900	357.50000	887.36990	1.33212	2030.28000
1.470	-5.125	347.95920	1224.13083	526.67712	390.15010	100.30000	2.49786	357.29980	887.38990	1.33271	2030.28000
1.470	-4.151	347.96140	1223.60631	526.46407	390.19340	100.30000	2.49705	357.29980	887.38990	1.33672	2030.28000
1.470	-3.181	347.95210	1223.49757	526.41871	390.20020	100.30000	2.49685	357.28980	887.40990	1.33684	2030.28000
1.470	-2.211	347.95090	1223.72220	526.50925	390.17920	100.30000	2.49725	357.28980	887.41990	1.33659	2030.28000
1.470	-1.236	348.16750	1223.58853	526.47256	390.25120	100.30000	2.49742	357.50980	887.40990	1.34366	2030.31500
1.470	-0.243	348.11040	1223.23900	526.32594	390.26460	100.30000	2.49676	357.45000	887.42990	1.34404	2030.31500
1.484	.752	347.99020	1248.79709	536.80439	390.19170	100.30000	2.49729	357.32980	887.41990	.00000	2030.31500
1.485	1.772	347.85350	1248.54031	536.68700	390.16700	100.30000	2.49678	357.18990	887.41990	.00000	2030.31500
GRADIENT	-.00355	4.54594	1.86528	-.00050	.00000	-.00000	-.00002	-.00362	.00433	-.24297	.00760

RUN NO. 1667/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.497	-8.059	337.57640	1233.61928	529.43311	386.45700	100.70000	2.49561	346.76980	945.61990	1.05535	2029.54500
1.496	-7.089	337.46340	1232.48955	528.97171	386.51900	100.70000	2.49360	346.64990	945.63990	1.05913	2029.54500
1.497	-6.107	337.52880	1233.63123	529.28877	386.52810	100.80000	2.49443	346.72000	945.64990	1.05844	2029.54500
1.497	-5.117	337.40890	1233.08440	529.41670	386.39430	100.70000	2.49557	346.59990	945.65990	1.05810	2029.54500
1.497	-4.146	337.30350	1233.22308	529.18797	386.40870	100.70000	2.49451	346.49000	945.67990	1.05857	2029.54500
1.497	-3.169	337.49980	1233.11383	529.22308	386.46920	100.70000	2.49481	346.68990	945.68990	1.06137	2029.54500
1.497	-2.198	337.61600	1233.49933	529.39051	386.54250	100.80000	2.49499	346.80980	945.68990	1.06105	2029.54500
1.497	-1.226	337.54830	1233.14853	529.24286	386.47460	100.70000	2.49507	346.74000	945.72000	1.06696	2029.54500
1.497	-0.228	337.57690	1233.28180	529.29917	386.53690	100.80000	2.49481	346.76980	945.73000	1.06966	2029.54500
1.497	.765	337.54790	1233.11964	529.23112	386.46460	100.70000	2.49526	346.74000	945.73000	1.07545	2029.54500
1.496	1.790	337.68650	1232.87825	529.15271	386.53030	100.70000	2.49503	346.87990	945.74000	1.07852	2029.54500
GRADIENT	.04356	-.03033	-.00676	.01262	-.00008	-.00008	.00008	.04442	.01086	.00350	-.00002

RUN NO. 1685/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.519	-8.051	327.55880	1236.99797	529.37025	382.32930	100.40000	2.49692	336.58980	911.99000	1.16741	2030.17500
1.520	-7.087	327.29520	1236.61679	529.18212	382.26860	100.40000	2.49607	336.31980	911.98000	1.17080	2030.17500
1.520	-6.104	327.13720	1236.96043	529.29039	382.18700	100.40000	2.49642	336.15990	911.99000	1.16739	2030.17500
1.520	-5.121	327.09960	1236.56711	529.13264	382.20950	100.40000	2.49571	336.11990	911.97000	1.16777	2030.10500
1.520	-4.141	327.18680	1236.74774	529.21597	382.21920	100.40000	2.49618	336.21000	911.99000	1.17066	2030.14000
1.520	-3.173	327.1770	1236.58144	529.15065	382.16310	100.30000	2.49449	336.20000	911.96000	1.17082	2030.14000
1.520	-2.196	327.23580	1236.79909	529.24321	382.23580	100.40000	2.49625	336.25980	911.97000	1.16756	2030.14000
1.520	-1.222	327.28560	1236.58247	529.16728	382.20430	100.30000	2.49652	336.30980	911.99000	1.16778	2030.10500
1.520	-0.228	327.33420	1236.70950	529.22415	382.227370	100.40000	2.49627	336.35990	911.96000	1.17072	2030.10500
1.520	.766	327.31420	1236.90257	529.29607	382.25730	100.40000	2.49643	336.33980	911.93990	1.16442	2030.07001
1.520	1.787	327.35300	1237.25038	529.43594	382.26340	100.40000	2.49661	336.37990	911.93990	1.14596	2030.07001
GRADIENT	.03146	.07517	.03394	.01300	.00731	.00004	.00004	.03216	-.00305	-.01395	-.00028

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM041) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1678/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATT
1.541	-8.058	318.59470	1241.40636	529.522805	379.24240	101.40000	2.49332	327.47000	911.67990	1.35078 2029.72000
1.541	-7.089	318.30270	1240.95020	529.30072	379.11280	101.30000	2.49282	327.16990	911.67990	1.35124 2029.72000
1.545	-6.103	316.56080	1241.05180	529.000793	378.50850	101.30000	2.49060	325.38990	911.72000	1.33703 2029.72000
1.543	-5.123	317.58060	1240.44066	528.97162	378.98540	101.40000	2.49026	326.42990	911.76000	1.34130 2029.72000
1.544	-4.146	316.92460	1240.52072	528.87743	378.67920	101.30000	2.49023	325.75980	911.78980	1.34112 2029.72000
1.544	-3.166	317.04370	1240.12224	528.74957	378.76150	101.30000	2.48961	325.87990	911.79980	1.33812 2029.72000
1.543	-2.198	317.22850	1240.49069	528.92362	378.79860	101.30000	2.49035	326.06980	911.81980	1.33430 2029.72000
1.542	-1.222	317.71800	1240.37093	528.97202	378.97240	101.30000	2.49090	326.56980	911.83980	1.34140 2029.75500
1.543	-0.229	317.57130	1240.33244	528.92957	378.92410	101.30000	2.49066	326.41990	911.85990	1.34142 2029.75500
1.543	.766	317.57010	1240.83047	529.11721	378.89360	101.30000	2.49123	326.41990	911.85990	1.33054 2029.75500
1.543	1.788	317.41410	1240.60220	529.00116	378.85400	101.30000	2.49076	326.25980	911.86990	1.33421 2029.75500
GRADIENT	.10292	.05447	.04022	.03281	-.00000	.00019	.10530	.01447	-.00104	.00758

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM042) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1568/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATT
.599	-7.140	1252.87100	1597.21001	315.02390	522.43770	100.30000	2.49559	1262.62000	1301.00999	1.00655 2034.69000
.599	-6.144	1252.64999	1596.57001	314.66700	522.47140	100.30000	2.49375	1262.39000	1301.07001	1.00431 2034.65500
.600	-5.169	1251.87300	1596.33000	315.10280	522.40110	100.30000	2.49513	1261.62000	1301.14999	.97067 2034.69000
.600	-4.196	1252.49100	1597.42000	315.51220	522.37280	100.30000	2.49754	1262.25000	1301.23000	.96745 2034.69000
.600	-3.224	1251.79700	1597.08000	315.79590	522.32200	100.30000	2.49828	1261.56000	1301.27000	.96511 2034.65500
.601	-2.256	1251.87900	1597.50000	316.08080	522.29250	100.30000	2.49967	1261.64999	1301.35001	.96232 2034.69000
.600	-1.286	1252.07700	1597.30000	315.75120	522.33470	100.30000	2.49831	1261.84000	1301.39999	.95990 2034.69000
.600	-.291	1251.91200	1596.92000	315.56690	522.35060	100.30000	2.49732	1261.67000	1301.47000	.95760 2034.69000
.600	.705	1251.62900	1596.84000	315.73170	522.32450	100.30000	2.49785	1261.39000	1301.52000	.95513 2034.69000
GRADIENT	-.11000	-.10487	.00207	-.00328	.00000	-.00008	-.11038	.06126	-.00253	.00305

## PARAMETRIC DATA

RUN NO.		1458/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
.800	-7.105	879.99680	1341.322001	394.16850	495.99390	99.80000	2.50046	889.89990	1045.84000	8.16490	2038.85500		
.800	-6.098	879.88920	1341.10001	394.07890	496.08860	99.89999	2.49941	889.78980	1046.00999	8.13406	2038.85500		
.800	-5.112	879.57470	1341.19000	394.35910	495.85110	99.70000	2.50139	889.48000	1046.13000	8.10144	2038.82001		
.800	-4.133	879.92260	1340.92000	393.92310	496.02440	99.80000	2.49938	889.81980	1046.25000	8.16737	2038.85500		
.800	-3.157	879.74850	1341.05000	394.13750	495.89380	99.70000	2.50066	889.64990	1046.36000	8.15045	2038.82001		
.800	-2.183	879.85210	1340.89000	393.94870	496.01610	99.80000	2.49941	889.75000	1046.44000	8.07130	2038.85500		
.800	-1.206	879.54590	1341.10001	394.31230	495.94460	99.80000	2.50059	889.45000	1046.53000	7.99061	2038.82001		
.800	-.203	879.66820	1341.00999	394.16240	495.97390	99.80000	2.50010	889.56980	1046.62000	7.84998	2038.82001		
.800	.788	879.73540	1341.27000	394.30960	495.95700	99.80000	2.50077	889.63990	1046.71001	7.77100	2038.82001		
GRADIENT	-.04287	.05351		.06875	-.00487	.00870	.00019	-.04160	.09203	-.08614	-.00611		
RUN NO.		1491/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
.900	-7.109	753.01070	1273.21001	426.71000	481.59640	99.89999	2.49974	763.01980	978.38990	2.67378	2036.75500		
.899	-6.098	753.25440	1273.08000	426.47560	481.65500	99.89999	2.49906	763.26000	978.50000	2.67406	2036.75500		
.900	-5.117	752.46000	1272.97000	426.87280	481.43580	99.80000	2.50039	762.47000	978.57980	2.66767	2036.75500		
.900	-4.137	752.70000	1273.09000	426.81230	481.46660	99.80000	2.50039	762.71000	978.68990	2.65424	2036.75500		
.900	-3.162	752.51730	1273.17000	426.92780	481.33840	99.70000	2.50143	762.52980	978.73000	2.60193	2036.72000		
.900	-2.191	752.12010	1272.78000	426.94460	481.39440	99.80000	2.50030	762.12990	978.81980	2.60274	2036.72000		
.900	-1.210	752.46020	1272.95000	426.85890	481.43800	99.80000	2.50032	762.47000	978.88990	2.59593	2036.72000		
.900	-.216	752.28930	1272.92999	426.94680	481.32280	99.70000	2.50107	762.29980	978.96000	2.57671	2036.75500		
.900	.781	752.72170	1273.00000	426.73780	481.39430	99.70000	2.50070	762.73000	979.04980	2.62824	2036.78999		
GRADIENT	-.00627	-.02880		-.01602	-.01058	-.01461	.00001	-.00670	.07440	-.00612	.00819		
RUN NO.		1475/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-4.000	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.100	-7.044	565.22780	1206.36000	478.46920	451.63720	101.20000	2.49282	575.41990	913.97000	1.78369	2038.33000		
1.100	-6.022	564.79030	1206.03999	478.45610	451.57150	101.20000	2.49229	574.98000	914.07980	1.79796	2038.33000		
1.100	-5.034	564.49340	1205.71001	478.38160	451.53910	101.20000	2.49168	574.67990	914.17990	1.79845	2038.33000		
1.100	-4.040	564.97000	1206.09000	478.41430	451.60720	101.20000	2.49232	575.15990	914.23000	1.80251	2038.33000		
1.100	-3.053	564.84810	1206.25000	478.55540	451.56230	101.20000	2.49275	575.03980	914.34990	1.80227	2038.33000		
1.100	-.2.063	564.91920	1206.17000	478.48100	451.58720	101.20000	2.49253	575.10990	914.40990	1.80239	2038.33000		
1.100	-1.075	564.93090	1206.02000	478.38920	451.60570	101.20000	2.49218	575.11990	914.48000	1.80261	2038.33000		
1.100	-.072	565.07320	1205.85001	478.23390	451.65650	101.20000	2.49173	575.26000	914.55980	1.80286	2038.29500		
1.100	.919	565.12720	1206.41000	478.53830	451.60890	101.20000	2.49298	575.31980	914.62990	1.80666	2038.33000		
GRADIENT	.04248	.00721		-.01259	-.00893	-.00000	-.00000	-.00000	.04241	.07771	.00066		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM042) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1515/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.250	-7.088	462.48560	1197.64000	505.67630	427.43920	101.30000	2.49171	472.60990	864.33980	1.64599	2035.84500
-6.074	462.59010	1198.39999	506.03860	427.38940	101.30000	2.49327	472.72000	864.36990	1.64920	2035.88000	
1.250	-5.081	462.50320	1197.99001	505.84990	427.33200	101.20000	2.49301	472.62990	864.39990	1.65832	2035.88000
1.250	-4.102	462.30400	1197.96001	505.87820	427.28250	101.20000	2.49293	472.42990	864.42990	1.66695	2035.88000
-3.123	462.51150	1198.25000	505.98000	427.23140	101.10000	2.49413	472.63990	864.42990	1.67518	2035.88000	
1.250	-2.146	462.43510	1197.72000	505.72800	427.18920	101.00000	2.49362	472.55980	864.46000	1.67592	2035.88000
1.250	-1.160	462.43330	1198.00000	505.87040	427.08400	100.90000	2.49478	472.55980	864.48000	1.67986	2035.88000
-1.168	462.19260	1198.20000	506.02420	427.00020	100.90000	2.49516	472.31980	864.48000	1.63250	2035.84500	
1.252	.828	461.01220	1197.33000	505.84010	426.70070	100.80000	2.49382	471.12990	864.49000	1.63369	2035.88000
GRADIENT	- .21580	- .08779	.00249	- .07822	- .0762	- .07822	.00025	- .21704	.01363	-.00844	-.00304

RUN NO. 1531/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.400	-7.077	381.93140	1215.24001	523.93550	402.00590	99.89999	2.49986	391.63990	880.63990	1.27906	2035.56500
-6.066	381.73630	1214.75999	523.72950	401.92270	99.89999	2.49884	391.43990	880.66990	1.27957	2035.56500	
1.400	-5.077	381.77320	1215.23000	523.93430	401.95920	99.89999	2.49973	391.48000	880.71000	1.28245	2035.60001
-4.093	381.72440	1215.10001	523.87840	402.10060	100.10000	2.49827	391.42990	880.70000	1.28253	2035.56500	
-3.113	381.85280	1215.14999	523.89770	402.13450	100.10000	2.49845	391.55980	880.73000	1.28592	2035.60001	
1.400	-2.131	381.94290	1214.95000	523.80830	402.18040	100.10000	2.49815	391.64990	880.75000	1.27937	2035.60001
-1.150	381.77320	1215.23000	523.93430	402.10300	100.10000	2.49854	391.48000	880.74000	1.28922	2035.56500	
-1.152	381.76510	1214.92999	523.80320	402.12890	100.10000	2.49799	391.47000	880.74000	1.28954	2035.60001	
1.400	.841	381.93160	1215.16000	523.90040	402.15720	100.10000	2.49853	391.63990	880.74000	1.28930	2035.56500
GRADIENT	.01747	-.00234	-.00139	.00547	-.00000	.00001	.01769	.00635	.000157	-.00104	

RUN NO. 1549/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.450	-7.130	359.10080	1226.03000	528.20170	394.62570	100.80000	2.49469	368.57980	892.10990	1.38259	2035.11000
-6.125	358.97270	1226.07001	528.21170	394.58180	100.80000	2.49464	368.45000	892.17990	1.39709	2035.14500	
-5.143	358.61770	1226.06000	528.18920	394.47120	100.80000	2.49429	368.08980	892.26980	1.39710	2035.14500	
1.450	-4.169	358.85600	1225.75000	528.07280	394.50420	100.70000	2.49456	368.32980	892.32980	1.39745	2035.17999
1.449	-3.200	358.96630	1225.36000	527.91600	394.57470	100.70000	2.49398	368.43990	892.39990	1.36893	2035.17999
1.450	-2.233	359.14970	1226.13000	528.24560	394.56130	100.70000	2.4951	368.62990	892.47000	1.37166	2035.17999
1.450	-1.257	358.68820	1225.73000	528.05570	394.52370	100.80000	2.49378	368.15990	892.51000	1.38293	2035.17999
1.451	-.263	358.68480	1226.46001	528.35910	394.38500	100.70000	2.49565	368.15990	892.53980	1.38210	2035.14500
1.450	.730	358.88530	1225.78999	528.09080	394.58010	100.80000	2.49407	368.35990	892.56980	1.39012	2035.17999
GRADIENT	-.03384	.09021	.03576	-.00662	.01749	-.00002	-.03384	.04834	.00043	-.00307	

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM042) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA = -4.000	PHI = 180.000	PARAMETRIC DATA						
										T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.469	-7.127	348.38330	1222.72699	526.13793	390.65700	100.80000	2.49490	357.73000	888.08980	1.39733	2032	97501				
1.470	-6.117	347.93210	1222.39276	525.96551	390.46900	100.70000	2.49452	357.26980	888.12990	1.39766	2032	94000				
1.470	-5.134	347.90210	1222.46837	525.99416	390.51540	100.80000	2.49415	357.24000	888.12990	1.40115	2032	94000				
1.470	-4.160	347.71560	1222.24210	525.88707	390.39870	100.70000	2.49431	357.04980	888.13990	1.40498	2032	97501				
1.469	-3.186	348.14970	1222.22964	525.95590	390.1704	100.70000	2.49441	357.49000	888.13990	1.39788	2032	97501				
1.470	-2.213	347.78470	1222.36684	525.94389	390.42260	100.70000	2.49434	357.11990	888.16990	1.39767	2032	97501				
1.469	-1.239	348.04930	1222.60202	526.06112	390.48830	100.70000	2.49499	357.38990	888.17990	1.39743	2033	00999				
1.470	-2.244	347.85400	1222.34450	525.93969	390.52370	100.80000	2.49365	357.18990	888.17990	1.39414	2033	00999				
1.469	.755	348.34590	1222.33948	525.97729	390.61060	100.70000	2.49478	357.68990	888.18990	1.39778	2032	97501				
GRADIENT	.07378	.03071	.01840	.03000	.00871	.00002	.07498	.00002	.07498	.001104	.001138	.00401				
MACH	ALPHA	P	PT	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00									
1.491	-7.114	336.85300	1220.92599	524.31414	386.14650	100.20000	2.49259	346.01980	896.78980	1.67456	2033	88499				
1.492	-6.115	336.97630	1222.18315	524.82746	386.02950	100.10000	2.49501	346.14990	896.78980	1.65606	2033	85001				
1.492	-5.125	337.92260	1225.87651	526.40610	386.00050	100.10000	2.50257	347.12990	896.82980	1.65950	2033	85000				
1.491	-4.150	337.97360	1225.55872	526.28426	386.05810	100.10000	2.50185	347.17990	896.81980	1.65159	2033	85001				
1.491	-3.172	337.93760	1224.98190	526.03983	386.11570	100.20000	2.50047	347.03980	896.82980	1.66490	2033	88499				
1.492	-2.203	337.43730	1224.59317	525.83943	385.96040	100.10000	2.49975	346.62990	896.82980	1.65701	2033	88499				
1.491	-1.228	337.61690	1223.92274	525.59317	386.08060	100.10000	2.49878	346.80980	896.82980	1.65794	2033	85001				
1.491	-.228	337.46140	1223.37195	525.35619	386.06620	100.10000	2.49791	346.64990	896.83980	1.66706	2033	88499				
1.491	.768	337.33570	1222.92755	525.16507	385.99540	100.00000	2.49761	346.51980	896.82980	1.66765	2033	88499				
GRADIENT	-.12019	-.54238	-.22946	-.00994	-.00994	-.00087	-.02331	-.00087	-.12460	.00231	.00256	.00405				
MACH	ALPHA	P	PT	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00									
1.517	-7.115	326.51170	1228.77863	526.03378	382.72680	101.10000	2.48630	335.50980	904.67990	1.52513	2033	57001				
1.517	-6.108	327.21630	1231.77332	527.30158	382.64230	101.00000	2.49257	336.24000	904.73000	1.51373	2033	57001				
1.517	-5.125	327.36550	1231.28349	527.13429	382.74290	101.00000	2.49179	336.38990	904.77980	1.51051	2033	60500				
1.517	-4.151	327.39160	1232.11636	527.46099	382.67190	101.00000	2.49334	336.41990	904.78980	1.51333	2033	60500				
1.517	-3.176	327.55470	1232.95613	527.81180	382.64750	101.00000	2.49505	336.58980	904.83980	1.51617	2033	60500				
1.517	-2.202	327.85550	1233.69592	528.14429	382.61110	100.90000	2.49733	336.89990	904.86990	1.51915	2033	60500				
1.516	-1.223	328.09110	1233.11989	527.95815	382.69210	100.90000	2.49758	337.13990	904.91990	1.55907	2033	57001				
1.517	-.228	327.31400	1231.13582	527.07078	382.59790	100.90000	2.49346	336.33980	904.92990	1.5647	2033	57001				
1.516	.769	326.96020	1228.87160	526.13933	382.74800	101.00000	2.48861	335.97000	904.92990	1.56835	2033	57001				
GRADIENT	-.07788	-.65051	-.26361	-.00916	-.00858	-.00083	-.008128	-.00083	-.08128	.002960	.01344	.00915				

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 941  
(VCM042) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup>	PATM
1.541	-7.114	317.62010	1237.26891	527.77395	378.66800	100.90000	2.49317	326.47000	909.52980	1.54793	2033.60500
1.541	-6.114	317.63890	1237.45538	527.84798	378.72560	101.00000	2.49291	326.49000	909.50000	1.54770	2033.60500
1.540	-5.124	317.86380	1237.53862	527.92164	378.79790	101.00000	2.49330	326.72000	909.47000	1.54764	2033.60500
1.541	-4.146	317.65670	1237.95079	528.03848	378.62010	100.90000	2.49437	326.50980	909.45000	1.54707	2033.60500
1.541	-3.176	317.77320	1238.28021	528.18570	378.70480	101.00000	2.49435	326.62990	909.43990	1.54275	2033.60500
1.541	-2.201	317.76290	1238.38271	528.22202	378.61910	100.90000	2.49522	326.61990	909.40990	1.54654	2033.60500
1.541	-1.228	317.75240	1238.66539	528.32714	378.60080	100.90000	2.49548	326.60990	909.38990	1.53834	2033.60500
1.541	-228	317.93680	1239.06873	528.51456	378.62500	100.90000	2.49647	326.79980	909.35990	1.54178	2033.60500
1.541	.767	318.04420	1239.24199	528.60054	378.72020	101.00000	2.49619	326.90990	909.33980	1.53766	2033.60500
GRADIENT	.07048	.07048	.26487	.11355	.00716	.00590	.00046	.07288	-.02360	.00169	.00000

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM043) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup>	PATM
.600	-7.115	1252.35201	1596.75999	315.07150	522.51120	100.40000	2.49482	1262.10001	1301.78999	.96023	2034.75999
.600	-6.613	1252.62300	1597.42000	315.40410	522.48190	100.40000	2.49558	1262.38000	1301.83000	.96491	2034.72501
.600	-6.121	1251.99300	1596.46001	315.11430	522.49630	100.40000	2.49472	1261.74001	1301.88000	.97059	2034.72501
.600	-5.631	1252.56900	1597.08000	315.16280	522.50710	100.40000	2.49542	1262.32001	1301.92000	.99348	2034.72501
.599	-5.136	1252.65100	1597.05000	315.07030	522.51980	100.40000	2.49506	1262.39999	1301.94000	.99612	2034.72501
.600	-4.649	1252.22800	1596.86000	315.25730	522.48710	100.40000	2.49558	1261.98000	1302.00999	.99624	2034.72501
.600	-4.162	1252.46499	1597.31000	312.20970	522.50680	100.40000	2.49758	1262.50000	1302.03000	.97008	2034.75999
.599	-3.679	1252.46400	1596.71000	314.97120	522.45260	100.40000	2.49444	1262.21001	1302.09000	.97042	2034.72501
.600	-3.193	1252.17999	1596.71001	315.17040	522.49540	100.40000	2.49513	1261.92999	1302.14000	.97044	2034.72501
.600	-2.714	1252.27200	1596.71001	315.09550	522.50630	100.40000	2.49486	1262.02000	1302.17000	.97001	2034.75999
.600	-2.236	1252.07401	1597.42000	315.85380	522.41650	100.40000	2.49821	1261.84000	1302.19000	.97031	2034.75999
.600	-1.754	1251.51500	1596.92000	315.89180	522.39650	100.40000	2.49793	1261.28000	1302.22000	.97033	2034.75999
.600	-1.276	1252.26801	1596.89000	315.24980	522.48900	100.40000	2.49557	1262.02000	1302.27000	.97020	2034.72501
.599	-.790	1252.67999	1597.10001	315.08790	522.51860	100.40000	2.49516	1262.42999	1302.31000	.97010	2034.72501
.601	-.308	1251.61000	1597.27000	316.10840	522.37520	100.40000	2.49901	1261.38000	1302.35001	.99349	2034.75999
.600	.204	1252.12300	1597.06000	315.51200	522.45580	100.40000	2.49667	1261.88000	1302.36000	.99599	2034.75999
.600	.715	1252.11800	1597.25000	315.67480	522.43750	100.40000	2.49742	1261.88000	1302.41000	.00151	.00246
GRADIENT	-.07808	.05528	.11048	-.01449	-.00000	-.00045	-.07575	.07472			

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.800	-7.080	879.99220	1340.98000	393.92020	496.11770	99.89999	2.49886	889.88990	1047.20000	7.77270	2038.85500
.800	-6.581	879.98000	1341.11000	394.02470	496.10210	99.89999	2.49928	889.87990	1047.28999	7.75653	2038.82001
.800	-6.086	879.74800	1341.10001	394.17500	496.06570	99.89999	2.49966	889.64990	1047.41000	7.74121	2038.85500
.800	-5.589	879.80100	1340.91000	393.99800	496.09450	99.89999	2.49999	889.70000	1047.50999	7.72697	2038.89000
.800	-5.093	879.71000	1340.95000	394.09100	495.98820	99.70000	2.50042	889.60990	1047.59000	7.63519	2038.85500
.800	-4.602	879.67940	1340.94000	394.10300	496.16040	100.00000	2.49872	889.57980	1047.67999	7.65044	2038.82001
.800	-4.115	879.74680	1341.17000	394.22750	496.05810	99.89999	2.49987	889.64990	1047.77000	7.57345	2038.85500
.800	-3.628	879.56860	1340.94000	394.17850	496.05370	99.89999	2.49949	889.47000	1047.89000	7.55971	2038.85500
.800	-3.141	879.72800	1341.08000	394.17360	496.15330	100.00000	2.49906	889.62990	1047.97000	7.51392	2038.82001
.800	-2.652	879.75000	1340.97000	394.07740	496.16850	100.00000	2.49869	889.64990	1048.03999	7.51454	2038.82001
.800	-2.172	879.77050	1340.96001	394.05620	496.17290	100.00000	2.49862	889.66990	1048.12000	7.45498	2038.82001
.800	-1.683	879.77100	1340.89000	394.00370	496.00290	99.80000	2.49956	889.66990	1048.19000	7.41094	2038.82001
.800	-1.198	879.82840	1341.13000	394.14260	495.98680	99.80000	2.50018	889.73000	1048.27000	7.36541	2038.82001
.800	-709	879.66460	1341.25000	394.34250	495.94780	99.80000	2.50084	889.56980	1048.35001	7.33542	2038.78500
.800	-223	879.80930	1341.05000	394.09620	496.16970	100.00000	2.49882	889.71000	1048.41000	7.33653	2038.78500
.800	.286	879.70170	1340.81000	393.99110	496.00020	99.80000	2.49944	889.59990	1048.48000	7.30863	2038.82001
.800	.796	880.02220	1341.00000	393.91430	496.03200	99.80000	2.49944	889.91990	1048.53999	7.23499	2038.82001
	GRADIENT	.03566	-.00408	-.02728	-.02049	-.03007	.00010	.03524	.15832	-.07079	-.00701

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.900	-7.086	752.88920	1273.24001	426.80270	481.22680	99.50000	2.50229	762.89990	979.43990	2.46940	2036.72000
.899	-6.578	753.11670	1272.83000	426.78550	481.31250	99.50000	2.50087	763.11990	979.51980	2.45792	2036.68500
.900	-6.086	752.81130	1273.07001	426.73240	481.23100	99.50000	2.50193	762.81980	979.57980	2.44523	2036.72000
.900	-5.594	752.46700	1273.17000	427.00560	481.07100	99.39999	2.50323	762.48000	979.65990	2.39072	2036.72000
.900	-5.099	752.94340	1272.97000	426.58500	481.09370	99.30000	2.50264	762.95000	979.73000	2.42719	2036.72000
.900	-4.605	752.63600	1273.35001	427.02910	480.99660	99.30000	2.50408	762.64990	979.80980	2.42646	2036.72000
.900	-4.123	752.60180	1272.92000	426.75420	481.12280	99.39999	2.50237	762.60990	979.84990	2.40317	2036.72000
.900	-3.634	752.79200	1273.00000	426.69580	481.14890	99.39999	2.50234	762.79980	979.95000	2.34369	2036.72000
.900	-3.146	752.43210	1272.81000	426.77950	481.18970	99.50000	2.50171	762.43990	980.01980	2.37948	2036.72000
.900	-2.659	752.72000	1273.09000	426.80030	481.29810	99.59999	2.50152	762.73000	980.06980	2.37301	2036.68500
.900	-2.174	752.78080	1273.09000	426.76440	481.39530	99.70000	2.50087	762.78980	980.13990	2.35528	2036.68500
.900	-1.693	752.66970	1273.08000	426.82350	481.46220	99.80000	2.50041	762.67990	980.22000	2.33768	2036.68500
.900	-1.209	752.61080	1272.98000	426.79000	481.46220	99.80000	2.50021	762.61990	980.29980	2.32037	2036.64999
.900	-721	752.95430	1272.91000	426.53740	481.53250	99.80000	2.49957	762.96000	980.37990	2.28015	2036.64999
.900	-237	752.88280	1272.98000	426.62790	481.59790	99.89999	2.49928	762.88990	980.43990	2.24596	2036.64999
.900	.275	752.96260	1273.03000	426.61470	481.60720	99.89999	2.49931	762.97000	980.48000	2.24024	2036.68500
.900	.785	752.83080	1273.11000	426.74830	481.57420	99.89999	2.49970	762.83980	980.53980	2.19551	2036.68500
	GRADIENT	.05868	-.01150	-.04285	.11537	.12017	-.00080	.05814	.14106	-.03845	-.01177

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM043) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.100	-7.037	565.29860	1206.33000	478.42410	451.65670	101.20000	2.49272	575.49000	914.88990	1.82540	2038.29500
1.100	-6.520	564.97830	1206.25000	478.50420	451.59200	101.20000	2.49269	575.16990	914.98000	1.83021	2038.29500
1.100	-6.029	564.86960	1206.11000	478.46560	451.50170	101.10000	2.49300	575.05980	915.01980	1.83983	2038.29500
1.100	-5.526	564.60250	1205.80000	478.39090	451.47390	101.10000	2.49241	574.78980	915.08980	1.84502	2038.25999
1.100	-5.034	564.81130	1205.96001	478.40140	451.50440	101.10000	2.49268	575.00000	915.13990	1.84951	2038.25999
1.102	-4.532	562.26200	1203.47000	477.95830	451.10720	101.00000	2.48876	572.42990	915.21000	1.85809	2038.29500
1.101	-4.038	563.03930	1203.89999	477.90260	451.23930	101.00000	2.48938	573.21000	915.25000	1.85743	2038.29500
1.100	-3.545	564.11280	1204.75000	477.97340	451.39380	101.00000	2.49082	574.28980	915.29980	1.86564	2038.25999
1.100	-3.037	564.69480	1205.61000	478.24390	451.43480	101.00000	2.49252	574.87990	915.34990	1.86908	2038.25999
1.100	-2.557	564.89890	1206.19000	478.50070	451.41920	101.00000	2.49375	575.08980	915.38990	1.87297	2038.25999
1.100	-2.062	564.79910	1206.16000	478.52250	451.31910	100.90000	2.49431	574.99000	915.42990	1.88262	2038.29500
1.100	-1.566	564.99950	1206.17000	478.44920	451.44460	101.00000	2.49365	575.18990	915.46000	1.88260	2038.25999
1.099	-1.079	565.33060	1206.14000	478.30100	451.36210	100.80000	2.49459	575.51980	915.72000	1.83978	2038.22501
1.100	-5.81	564.99220	1205.92000	478.30660	451.30830	100.80000	2.49425	575.17990	915.74000	1.84012	2038.22501
1.100	-.094	565.16160	1206.00999	478.29200	451.33740	100.80000	2.49437	575.34990	915.77980	1.84943	2038.22501
1.100	.416	564.84300	1205.78999	478.28830	451.28830	100.80000	2.49402	575.02980	915.80980	1.85926	2038.22501
1.100	.920	564.97920	1206.17999	478.46310	451.27780	100.80000	2.49485	575.16990	915.81980	1.86820	2038.25999
	GRADIENT	.39881	.40318	.07714	.00878	-.04874	.00102	.40222	.12772	-.00161	-.01117
RUN NO.	1476/ O	RN/L =	2.49	GRADIENT	INTERVAL	= -5.00/	5.00				
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.250	-7.066	462.61910	1198.53000	506.09810	426.92680	100.70000	2.49706	472.75000	864.55980	1.63205	2035.84500
1.251	-6.560	462.00540	1197.86000	505.89260	426.75680	100.60000	2.49620	472.12990	864.56980	1.62033	2035.84500
1.250	-6.061	462.18800	1197.42000	505.62990	426.77370	100.50000	2.49592	472.30980	864.57980	1.60422	2035.77499
1.250	-5.570	462.47240	1198.14999	505.93770	426.77440	100.50000	2.49744	472.59990	864.58980	1.60740	2035.77499
1.250	-5.073	462.55130	1198.25000	505.97120	426.78490	100.50000	2.49765	472.67990	864.60990	1.60311	2035.81000
1.250	-4.583	462.40550	1197.70000	505.72440	426.72630	100.40000	2.49710	472.52980	864.60990	1.59970	2035.77499
1.250	-4.095	462.77980	1198.39000	505.99220	426.67850	100.30000	2.49914	472.90990	864.61990	1.59051	2035.77499
1.250	-3.601	462.36600	1197.66000	505.71290	426.64380	100.30000	2.49760	472.49000	864.63990	1.59148	2035.84500
1.250	-3.110	462.77150	1198.14000	505.86720	426.70170	100.30000	2.49863	472.89990	864.62990	1.57851	2035.84500
1.250	-2.627	462.68090	1198.27000	505.95290	426.66480	100.30000	2.49888	472.80980	864.63990	1.56609	2035.84500
1.250	-2.138	462.36670	1197.52000	505.64160	426.65820	100.30000	2.49732	472.49000	864.62990	1.55491	2035.81000
1.250	-1.654	462.81150	1198.10001	505.83810	426.64010	100.20000	2.49914	472.93990	864.64990	1.52613	2035.81000
1.250	-1.167	462.59200	1198.13000	505.90140	426.57930	100.20000	2.49918	472.72000	864.64990	1.53007	2035.81000
1.250	-67.3	462.65230	1198.03999	505.84250	426.52810	100.10000	2.49959	472.77980	864.64990	1.52621	2035.81000
1.250	-18.9	462.45410	1197.88000	505.80490	426.49220	100.10000	2.49924	472.57980	864.64990	1.52245	2035.81000
1.250	.322	462.49370	1197.92999	505.82150	426.49760	100.10000	2.49935	472.61990	864.64990	1.50661	2035.77499
1.250	.832	462.75150	1198.13000	505.86650	426.54520	100.10000	2.49978	472.87990	864.63990	1.49853	2035.81000
	GRADIENT	.01027	.01277	.00419	-.04150	-.05630	.00036	.01041	.00581	-.01960	-.00104

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 944  
(VCM043) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1532/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-3.000	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC				
1.400	-7.064	381.59840	1214.69000	523.70170	401.95780	99.89999	2.49861	391.29980	880.75000	1.26956	2035.56500	
-6.554	381.83230	1215.25999	523.94600	402.04610	100.00000	2.49923	391.53980	880.76000	1.26896	2035.56500		
1.400	-6.059	381.96390	1214.75999	523.72490	401.98930	99.80000	2.49960	391.66990	880.76980	1.26948	2035.56500	
1.400	-5.563	381.79350	1215.14999	523.89890	401.90110	99.80000	2.50019	391.50000	880.76000	1.26907	2035.53000	
1.400	-5.068	381.76610	1214.73000	523.71580	402.07640	100.00000	2.49822	391.47000	880.77980	1.26283	2035.49500	
1.400	-4.578	382.02830	1215.53999	524.06470	394.96630	90.09999	2.56005	391.74000	880.76980	1.27537	2035.49500	
1.400	-4.085	381.95390	1214.75999	523.72510	402.12990	100.00000	2.49841	391.65990	880.76000	1.28294	2035.53000	
1.399	-3.594	381.88790	1214.25000	523.50320	402.01460	99.80000	2.49862	391.58980	880.76000	1.29027	2035.49500	
1.400	-3.103	381.80250	1215.27000	523.95120	401.89260	99.80000	2.50042	391.50980	880.75000	1.29599	2035.49500	
1.400	-2.616	381.89310	1215.02000	523.84010	401.94340	99.80000	2.50003	391.59990	880.75000	1.29968	2035.46001	
1.400	-2.126	381.77470	1214.97000	523.82060	402.05620	100.00000	2.49866	391.48000	880.73000	1.30316	2035.49500	
-1.639	382.25950	1214.92000	523.78860	402.20680	100.00000	2.49892	391.97000	880.73000	1.30321	2035.49500		
1.399	-1.150	382.06300	1214.74001	523.71410	402.23660	100.10000	2.49786	391.76980	880.73000	1.30340	2035.46001	
1.400	-660	381.80490	1214.89000	523.78490	402.07280	100.00000	2.49854	391.50980	880.70000	1.29640	2035.46001	
1.400	-174	381.82400	1214.99001	523.82840	402.06910	100.00000	2.49873	391.52980	880.68990	1.29971	2035.46001	
1.400	.336	381.90360	1214.92000	523.79610	402.02780	99.89999	2.49926	391.60990	880.70000	1.29978	2035.46001	
1.400	.843	381.95120	1215.23000	523.93070	402.01270	99.89999	2.49986	391.65990	880.66990	1.28245	2035.46001	
GRADIENT			-.00528	.00315	.00149	.56126	-.78390	-.00476	-.00535	-.001740	.00218	-.01021

	RUN NO.	1550/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	-3.000	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC				
1.449	-7.106	359.12130	1225.88000	528.14010	394.64580	100.80000	2.49445	368.59990	892.73000	1.39730	2035.17999	
1.450	-6.598	358.71630	1226.03999	528.18600	394.50390	100.80000	2.49435	368.18990	892.69800	1.38620	2035.17999	
1.450	-6.106	359.05080	1226.19000	528.26560	394.59520	100.80000	2.49493	368.52980	892.82980	1.40061	2035.17999	
1.449	-5.614	358.96680	1225.27000	527.87870	394.58300	100.70000	2.49382	368.43990	892.84990	1.40166	2035.21500	
1.450	-5.123	358.81450	1226.10001	528.21610	394.59960	100.90000	2.49395	368.28980	892.87990	1.40071	2035.17999	
1.449	-4.630	359.19900	1226.10001	528.23560	394.64990	100.80000	2.49491	368.67990	892.89990	1.40071	2035.17999	
1.450	-4.150	358.85420	1226.06000	528.20140	394.47510	100.70000	2.49511	368.32980	892.92990	1.42289	2035.21500	
1.450	-3.665	359.00270	1225.95000	528.16330	394.60210	100.80000	2.49446	368.48000	892.95000	1.43047	2035.25000	
1.450	-3.178	358.70970	1225.39000	527.9150	394.56150	100.80000	2.49320	368.17990	892.98000	1.40887	2035.21500	
1.450	-2.698	359.04910	1226.52000	528.40280	394.56420	100.80000	2.49551	368.52980	893.00000	1.42981	2035.17999	
1.450	-2.219	358.64700	1226.09000	528.20310	394.47750	100.80000	2.49437	368.11990	893.01980	1.42658	2035.17999	
1.450	-1.734	358.99050	1226.39999	528.34990	394.55690	100.80000	2.49524	368.47000	893.04980	1.42250	2035.17999	
1.450	-1.255	358.86430	1226.03000	528.18950	394.55130	100.80000	2.49447	368.33980	893.05980	1.41552	2035.21500	
1.450	-1.772	358.66870	1225.73000	528.05470	394.51170	100.80000	2.49376	368.13990	893.05980	1.41217	2035.17999	
1.450	-2.88	358.91280	1226.14999	528.24190	394.55570	100.80000	2.49473	368.38990	893.08980	1.39335	2035.21500	
1.451	.225	358.60820	1226.02000	528.17210	394.47170	100.80000	2.49421	368.07980	893.09990	1.39715	2035.21500	
1.450	.732	358.93360	1225.99001	528.17650	394.57670	100.80000	2.49447	368.40990	893.11990	1.39353	2035.17999	
GRADIENT		-.04434	.00250	-.00121	-.00961	-.00647	-.00008	-.04500	-.03984	-.00435	-.00232	

1A310 (AEDC 16TF-783) PROBE CALIBRATION

卷八

( VGM013 )

1A310 (AEDC 16TF-783) PROBE CALIBRATION

卷八

( VGM013 )

#### METRIC DATA

RUN NO. 1634 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00 / 5.00

		P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
ALPHA	AACH	P	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.469	- .7	100	347.98070	1221.62093	525.65473	390.54250	100.80000	2.49420	357.31980	888.26980	1.44576
.469	- .6	593	347.87230	1221.67984	525.67008	390.43160	100.70000	2.49480	357.21000	888.26980	1.44568
.470	- .6	099	347.73490	1221.72858	525.67869	390.39480	100.70000	2.49451	357.06980	888.26980	1.43825
.469	- .5	607	348.10890	1221.88538	525.77285	390.58620	100.80000	2.49428	357.45000	888.27980	1.43079
.469	- .5	111	347.94240	1221.82144	525.73338	390.48050	100.70000	2.49437	357.27980	888.30980	1.42356
.469	- .4	624	348.05180	1221.61965	525.65870	390.60500	100.80000	2.49351	357.38990	888.30980	1.42381
.470	- .4	135	347.78610	1222.45058	525.97770	390.52270	100.80000	2.49318	357.11990	888.31980	1.37628
.470	- .3	649	347.77540	1222.64548	526.05606	390.50100	100.80000	2.49351	357.10990	888.33980	1.37605
.469	- .3	165	348.19730	1222.97888	526.22602	390.61010	100.80000	2.49446	357.53980	888.33980	1.37573
.469	- .2	682	348.23730	1222.83630	526.17149	390.56670	100.70000	2.49484	357.57980	888.33980	1.37590
.469	- .2	199	348.00200	1222.51646	526.02244	390.57540	100.80000	2.49372	357.33980	888.33990	1.38330
.469	- .1	719	348.04980	1222.72865	526.11226	390.49580	100.70000	2.49485	357.38990	888.35990	1.38660
.469	- .1	235	348.19650	1222.82405	526.16312	390.59890	100.80000	2.49466	357.53980	888.36990	1.39007
.470	- .7	749	347.99070	1222.64410	526.07270	390.47780	100.70000	2.49477	357.32980	888.35990	1.39025
.471	- .2	67	347.53690	1222.82895	526.11166	390.31050	100.70000	2.49470	357.86990	888.37990	1.38998
.469	.244	348.01050	1222.50935	526.01973	390.55370	100.80000	2.49419	357.34990	888.37990	1.39754	
.469	.756	347.93140	1222.28455	525.92163	390.52290	100.80000	2.49421	357.26980	888.37990	1.41215	
GRADIENT	- .01493	.05442	.02097	- .01858	- .00707	- .00020	- .00020	- .01471	.01286	.00203	.0274

RUN NO. 1585 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00 / 5.00

## PARAMETRIC DATA

	RUN NO.	1601/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-3.000	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.516	-7.094	327.09330	1229.80354	526.52112	382.63110	100.90000	2.49114	336.10990	905.02980	1.57514	2033.57001		
1.516	-6.586	326.96730	1229.42776	526.35607	382.62160	100.90000	2.49037	335.98000	905.04980	1.57561	2033.57001		
1.516	-6.094	327.26000	1229.80402	526.54685	382.68850	100.90000	2.49132	336.27980	905.06980	1.57516	2033.60500		
1.516	-5.600	327.46900	1231.58334	527.26637	382.60570	100.90000	2.49449	336.50000	905.08980	1.56889	2033.60500		
1.517	-5.109	327.39750	1232.38297	527.56699	382.51950	100.90000	2.49558	336.42990	905.10990	1.55991	2033.60500		
1.517	-4.619	327.58540	1232.06458	527.47201	382.61820	100.90000	2.49514	336.61990	905.11990	1.55639	2033.60500		
1.517	-4.132	327.41020	1231.53712	527.24150	382.58420	100.90000	2.49445	336.43990	905.13990	1.57293	2033.60500		
1.517	-3.646	327.18900	1230.39970	526.76690	382.61040	100.90000	2.49227	336.21000	905.14990	1.57438	2033.64000		
1.516	-3.155	327.15330	1229.48915	526.40803	382.68020	100.90000	2.49067	336.16990	905.15990	1.57556	2033.64000		
1.516	-2.672	326.83280	1228.60210	526.01660	382.63890	100.90000	2.48901	335.83980	905.15990	1.58468	2033.64000		
1.517	-2.189	326.54030	1228.18723	525.81058	382.58060	100.90000	2.48789	335.53980	905.16990	1.58117	2033.64000		
1.517	-1.706	326.91750	1229.55789	526.39928	382.58740	100.90000	2.49064	335.92990	905.16990	1.57943	2033.67500		
1.516	-1.222	327.50050	1230.94379	527.02475	382.66360	100.90000	2.49363	336.52980	905.17990	1.57772	2033.71001		
1.517	-7.36	327.27540	1230.68179	526.88969	382.59890	100.90000	2.49314	336.29980	905.22000	1.58605	2033.67500		
1.516	-252	327.31790	1229.83841	526.56922	382.68410	100.90000	2.49185	336.33980	905.23000	1.59119	2033.67500		
1.517	.260	326.77100	1229.24637	526.25714	382.54880	100.90000	2.49025	335.77980	905.22000	1.59189	2033.71001		
1.517	.772	326.63620	1228.49854	525.94646	382.56450	100.90000	2.48893	335.63990	905.24000	1.59689	2033.78000		
GRADIENT		-.08875	-.355549	-.15113	-.00524	-.00000	-.00058	-.09165	-.02122	.00548	.02537		
	RUN NO.	1616/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =				PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.541	-7.093	317.98660	1238.93352	528.47301	378.72750	101.00000	2.49560	326.84990	909.28980	1.53805	2033.60500		
1.541	-6.587	318.09300	1239.23802	528.60780	378.73270	101.00000	2.49634	326.96000	909.26980	1.54159	2033.64000		
1.541	-6.093	317.95650	1239.07178	528.51962	378.63160	100.90000	2.49650	326.81980	909.25000	1.54178	2033.64000		
1.541	-5.601	317.74100	1239.97076	528.47992	378.62230	101.00000	2.49567	326.59990	909.21000	1.54173	2033.64000		
1.541	-5.110	317.72360	1238.44427	528.23750	378.66720	101.00000	2.49468	326.57980	909.21000	1.54645	2033.64000		
1.541	-4.618	317.56640	1238.56445	528.25372	378.60080	101.00000	2.49471	326.41990	909.18990	1.54627	2033.60500		
1.542	-4.127	317.78320	1238.15404	528.13943	378.71440	101.00000	2.49425	326.63990	909.15990	1.54684	2033.60500		
1.541	-3.644	317.71530	1237.98888	528.06433	378.70480	101.00000	2.49390	326.56980	909.12990	1.54703	2033.60500		
1.541	-3.155	317.62870	1237.65866	527.92339	378.70900	101.00000	2.49314	326.48000	909.11990	1.54351	2033.60500		
1.541	-2.672	317.55200	1237.25281	527.75483	378.72360	101.00000	2.49226	326.39990	909.09990	1.54010	2033.64000		
1.541	-2.187	317.32860	1236.68468	527.49809	378.68970	101.00000	2.49115	326.16990	909.06980	1.54470	2033.60500		
1.541	-1.707	317.53470	1236.65094	527.52418	378.77120	101.00000	2.49122	326.37990	909.03980	1.54086	2033.60500		
1.541	-1.220	317.25270	1236.11453	527.26851	378.71900	101.00000	2.49000	326.08980	909.02980	1.54149	2033.60500		
1.541	-1.734	317.19460	1235.88118	527.16969	378.71390	101.00000	2.48964	326.02980	909.00000	1.54570	2033.60500		
1.541	-2.250	317.02910	1235.65472	527.05219	378.68070	101.00000	2.48897	325.85990	908.98000	1.54203	2033.60500		
1.541	.259	316.98190	1235.55855	527.03992	378.73460	101.00000	2.48895	325.99000	908.98000	1.54218	2033.60500		
1.541	.770	316.98393	1235.23383	526.88393	378.70700	101.00000	2.48810	325.80980	908.93990	1.53865	2033.57001		
GRADIENT		-.14149	-.63553	-.26698	-.00911	.00000	-.00128	-.14698	-.04488	-.00107	-.00130		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( VCM044 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.		1570/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
.599	-7.098	1252.99500	1597.11000	314.83810	522.55520	100.40000	2.49427	1262.74001	1302.49001	.98825 2034.79500
.599	-6.592	1252.57401	1596.35001	314.54490	522.57590	100.40000	2.49256	1262.31000	1302.53000	.98612 2034.79500
.599	-6.103	1252.83701	1597.37000	315.18630	522.51200	100.40000	2.49575	1262.59000	1302.57001	.98290 2034.75999
.599	-5.605	1252.77800	1596.78999	314.74710	522.55930	100.40000	2.49366	1262.52000	1302.58000	.98067 2034.72501
.599	-5.117	1252.67900	1597.17000	315.14820	522.51200	100.40000	2.49544	1262.42999	1302.64000	.96506 2034.75999
.599	-4.631	1252.45399	1596.72000	314.95360	522.43410	100.30000	2.49492	1262.20000	1302.66000	.96533 2034.75999
.600	-4.147	1252.50200	1597.36000	315.45260	522.47310	100.40000	2.49671	1262.25999	1302.70000	.96749 2034.79500
.600	-3.656	1252.42500	1597.17000	315.35640	522.48170	100.40000	2.49620	1262.17999	1302.72000	.98302 2034.75999
.599	-3.174	1252.68300	1596.96001	314.96830	522.53200	100.40000	2.49461	1262.42999	1302.78999	.98574 2034.75999
.600	-2.697	1252.48399	1597.28000	315.40090	522.38500	100.30000	2.49702	1262.24001	1302.80000	.98814 2034.75051
.600	-2.219	1252.31200	1596.71001	315.06230	522.41800	100.30000	2.49531	1262.06000	1302.83000	.98850 2034.72501
.600	-1.743	1252.13499	1597.45000	315.82960	522.32760	100.30000	2.49872	1261.89999	1302.87000	.98804 2034.72501
.600	-1.267	1252.23399	1597.05000	315.41190	522.47000	100.40000	2.49630	1261.99001	1302.89000	.99089 2034.72501
.599	-7.89	1252.15601	1596.45000	314.97240	522.51680	100.40000	2.49420	1261.89999	1302.92000	.99387 2034.75999
.600	-.311	1252.13901	1597.23000	315.41110	522.34860	100.30000	2.49785	1261.89999	1302.94000	.99601 2034.72501
.600	.200	1252.44501	1597.16000	315.33130	522.39160	100.30000	2.49667	1262.00000	1302.99001	.99605 2034.72501
.600	.717	1252.59700	1597.22000	315.25760	522.40410	100.30000	2.49645	1262.35001	1303.02000	.99863 2034.72501
GRADIENT	-.03185	.01209	.03636	-.01380	-.00946	.00020	-.03116	.06567	.00552	-.00914
RUN NO.		1460/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
.800	-7.069	879.82670	1341.21001	394.20260	496.06690	99.89999	2.49985	889.73000	1048.89999	7.14761 2038.75000
.800	-6.563	879.722750	1341.10001	394.18870	496.23970	100.10000	2.49855	889.62990	1048.99001	7.09123 2038.78500
.800	-6.066	879.99540	1340.78000	393.77000	496.31690	100.10000	2.49710	889.88990	1049.08000	7.09295 2038.75000
.800	-5.573	879.744800	1341.08000	394.15990	496.06790	99.89999	2.49960	889.64990	1049.17999	7.04888 2038.78500
.800	-5.085	879.82130	1340.92000	393.99170	496.18530	100.00000	2.49841	889.72000	1049.22000	7.02155 2038.75000
.800	-4.594	879.66630	1341.14000	394.26000	496.13720	100.00000	2.49935	889.56980	1049.32001	6.99322 2038.78500
.800	-4.100	879.74020	1340.95000	394.06930	496.03030	99.89999	2.49927	889.62990	1049.39000	6.95139 2038.78500
.800	-3.613	879.72140	1340.85001	394.00810	496.17650	100.00000	2.49837	889.61990	1049.47000	6.93800 2038.75000
.800	-3.126	879.73850	1341.03000	394.12940	496.16040	100.00000	2.49889	889.63990	1049.53000	6.90929 2038.75000
.800	-2.638	879.68850	1341.03000	394.16360	496.15230	100.00000	2.49898	889.58980	1049.61000	6.86782 2038.75000
.800	-2.158	879.71950	1340.97000	394.09810	496.16360	100.00000	2.49874	889.61990	1049.67000	6.88193 2038.75000
.800	-1.675	879.76900	1341.03999	394.11620	496.16430	100.00000	2.49887	889.66990	1049.73000	6.84026 2038.71500
.800	-1.194	879.76980	1340.99001	394.07890	496.16970	100.00000	2.49871	889.66990	1049.80000	6.79943 2038.71500
.800	-.709	879.75170	1340.86000	393.99490	496.18040	100.00000	2.49835	889.64990	1049.85001	6.73212 2038.75000
.800	-.229	879.63700	1341.08000	394.23540	496.22730	100.00000	2.49865	889.53980	1049.92000	6.63689 2038.75000
.800	.283	879.84890	1341.10001	394.10620	496.25930	100.00000	2.49833	889.75000	1049.98000	6.59883 2038.71500
.800	.797	879.83010	1341.00999	394.05250	496.26590	100.00000	2.49809	889.73000	1050.02000	6.55754 2038.75000
GRADIENT	.01842	.00450	-.00920	.02586	-.00017	.01830	.13194	-.00831		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 948

(VCM044) (04 OCT 91)

## PARAMETRIC DATA

MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
ALPHA										
-7.073	752.74800	1273.25000	426.89360	481.63010	100.00000	2.49961	762.76000	980.82980	2.14609	2036.64999
.900	752.86250	1273.00000	426.65380	481.67820	100.00000	2.49878	762.86990	980.87990	2.17193	2036.68500
-6.565	753.30570	1273.02000	426.40380	481.84300	100.10000	2.49768	763.30980	980.93990	2.14648	2036.68500
-6.070	753.73240	1272.94000	426.68990	481.74680	100.10000	2.49821	762.74000	980.98000	2.14121	2036.64999
-5.578	752.63110	1272.95000	426.75710	481.81320	100.20000	2.49779	762.63990	981.04980	2.14660	2036.64999
-5.088	753.00150	1273.14999	426.67410	481.85940	100.20000	2.49786	763.01000	981.12990	2.13009	2036.64999
.900	752.90600	1272.78000	426.47680	481.88210	100.20000	2.49697	762.90990	981.15990	2.11999	2036.64999
-4.106	752.52080	1272.94000	426.81590	481.79420	100.20000	2.49791	762.52980	981.22000	2.10375	2036.64999
-3.618	752.57320	1272.78000	426.67480	481.90720	100.30000	2.49683	762.57980	981.27980	2.08814	2036.64999
-3.129	752.64140	1272.97000	426.76490	481.89920	100.30000	2.49726	762.64990	981.32980	2.07730	2036.64999
.900	752.93190	1273.07001	426.66040	481.94140	100.30000	2.49715	762.93990	981.37990	2.05106	2036.68500
-2.163	752.50760	1273.14999	426.96800	481.85520	100.30000	2.49793	762.51980	981.42990	2.04575	2036.64999
.900	752.66460	1272.73000	426.58590	482.01540	100.40000	2.49600	762.66990	981.50000	2.04126	2036.64999
-1.202	752.76150	1273.02000	426.72800	482.00170	100.40000	2.49666	762.76980	981.54980	2.04079	2036.61501
.900	752.67160	1272.95000	426.73290	481.99290	100.40000	2.49659	762.67990	981.58980	2.01524	2036.61501
-.241	752.93330	1272.98000	426.59790	482.03760	100.40000	2.49633	762.93990	981.62990	2.00501	2036.64999
.900	752.94210	1273.07001	426.65450	482.02930	100.40000	2.49656	762.95000	981.68990	1.99980	2036.64999
.900	GRADIENT	.00912	.01119	.00226	.03877	.04451	-.00024	.00923	.00680	-.002471
										-.00325
RUN NO.	1493/ 0	RN/L =	2.50	GRADIENT	INTERVAL =	-5.00/	5.00			
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
ALPHA										
-7.032	565.22070	1206.09000	478.31520	451.26200	100.70000	2.49511	575.40990	915.97000	1.92652	2038.22501
.521	564.99980	1206.14000	478.4160	451.28660	100.80000	2.49475	575.18990	915.99000	1.90686	2038.19000
-6.020	564.844990	1206.08000	478.45580	451.17850	100.70000	2.49526	575.03980	916.04980	1.88757	2038.19000
-5.523	564.74070	1205.99001	478.44680	451.16310	100.70000	2.49511	574.92990	916.05980	1.84001	2038.19000
-5.026	564.79960	1206.10001	478.48730	451.16480	100.70000	2.49533	574.99000	916.07980	1.81176	2038.19000
-4.534	564.93310	1205.81000	478.26650	451.22610	100.70000	2.49460	575.11990	916.10990	1.77081	2038.19000
-4.035	564.77150	1205.92000	478.39380	451.17750	100.70000	2.49493	574.96000	916.14990	1.73459	2038.19000
-3.535	564.82010	1206.05000	478.45020	451.17480	100.70000	2.49521	575.01000	916.14990	1.71222	2038.19000
-3.035	564.97020	1206.07001	478.40260	451.20680	100.70000	2.49518	575.15990	916.22000	1.69900	2038.15500
-2.549	564.97070	1206.03999	478.38480	451.21020	100.70000	2.49511	575.15990	916.25000	1.60515	2038.19000
-2.058	565.08060	1206.09000	478.37060	451.14940	100.60000	2.49576	575.26980	916.26980	1.60925	2038.22501
-1.566	564.77860	1206.17000	478.53640	451.07200	100.60000	2.49608	574.97000	916.28980	1.61150	2038.19000
-1.077	564.99000	1206.11000	478.41800	451.12670	100.60000	2.49550	575.17990	916.31980	1.64288	2038.19000
-1.000	565.00150	1205.99001	478.34370	451.06150	100.50000	2.49615	575.18990	916.34990	1.67302	2038.19000
-0.99	565.06050	1206.08000	478.37280	451.06540	100.50000	2.49632	575.25000	916.37990	1.74780	2038.22501
-0.914	564.93020	1206.07001	478.41820	451.03660	100.50000	2.49636	575.11990	916.39990	1.75231	2038.19000
-0.921	565.01120	1206.00000	478.34570	451.06270	100.50000	2.49617	575.20000	916.39990	1.75693	2038.19000
	GRADIENT	.02744	.02505	.00374	-.03456	-.04738	.00032	.02764	.005610	.00269

Q7

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM044) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1517/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.500	PHI =	180.000
P PT Q(PSF ) T(R) TT(F ) RN/L PC REF SH10+3 PATM										
MACH	ALPHA	P	PT	Q(PSF )	T(R)	TT(F )	RN/L	PC	REF	SH10+3 PATM
1.250	-7.059	462.66360	1197.85001	505.74390	426.39790	99.89999	2.50038	472.78980	864.64990	1.50671 2035 77499
-6.549	462.52390	1197.89000	505.79470	426.35720	99.89999	2.50044	472.64990	864.65990	1.54637 2035 81000	
1.250	-6.056	462.53340	1197.92999	505.81270	426.50810	100.10000	2.49935	472.65990	864.64990	1.47937 2035 77499
1.250	-5.559	462.58450	1197.80000	505.73580	426.38230	99.89999	2.50027	472.71000	864.64990	1.46417 2035 77499
1.250	-5.062	462.37720	1197.46001	505.60890	426.28610	99.80000	2.50014	472.50000	864.65990	1.44181 2035 77499
1.250	-4.571	462.70000	1198.39000	506.00950	426.42900	100.00000	2.50090	472.82980	864.64990	1.44069 2035 77499
1.250	-4.078	462.67260	1198.00000	505.81790	426.46140	100.00000	2.50010	472.79980	864.63990	1.42990 2035 74001
1.250	-3.587	462.37570	1197.70000	505.73100	426.26120	99.80000	2.50063	472.50000	864.63990	1.48352 2035 77499
1.250	-3.101	462.63380	1198.86000	505.75540	426.46530	100.00000	2.49981	472.75980	864.64990	1.47946 2035 74001
1.250	-2.615	462.71090	1198.25999	505.94140	426.44510	100.00000	2.50063	472.83980	864.62990	1.47511 2035 74001
1.250	-2.128	462.45410	1197.87000	505.79380	426.34080	99.89999	2.50039	472.57980	864.62990	1.46791 2035 81000
1.250	-1.645	462.42480	1197.78999	505.76560	426.41750	100.00000	2.49964	472.54980	864.62990	1.45656 2035 74001
1.250	-1.159	462.85720	1198.72000	506.14230	426.20830	99.70000	2.50336	472.99000	864.61990	1.44784 2035 74001
1.250	-679	462.61350	1197.88000	505.77000	426.22950	99.70000	2.50161	472.74000	864.62990	1.43754 2035 74001
1.250	-193	462.59570	1199.60001	505.63210	426.48190	100.00000	2.49927	472.72000	864.60990	1.43038 2035 74001
1.250	.318	462.65060	1198.32001	505.98490	426.34690	99.89999	2.50134	472.77980	864.59990	1.41834 2035 74001
1.249	.832	462.69700	1197.35001	505.48200	426.45780	99.89999	2.49937	472.81980	864.59990	1.41578 2035 74001
GRADIENT	.01159	-.05670	-.03131	-.00691	-.02068	.00001	.01127	-.00897	-.00754	-.00500
P PT Q(PSF ) T(R) TT(F ) RN/L PC REF SH10+3 PATM										
MACH	ALPHA	P	PT	Q(PSF )	T(R)	TT(F )	RN/L	PC	REF	SH10+3 PATM
1.400	-7.053	381.95120	1215.20000	523.91750	402.15940	100.10000	2.49861	391.65990	880.62990	1.27237 2035 42500
1.400	-6.544	381.77470	1215.00000	523.83370	402.12520	100.10000	2.49812	391.48000	880.62990	1.27258 2035 42500
1.400	-6.050	381.87230	1215.16000	523.90160	402.13940	100.10000	2.49848	391.57980	880.61990	1.26572 2035 39000
1.400	-5.553	381.98320	1214.85001	523.76390	402.20210	100.10000	2.49800	391.68990	880.61990	1.28963 2035 42500
1.400	-5.060	381.99290	1214.89999	523.78560	402.20020	100.10000	2.49810	391.70000	880.60990	1.28957 2035 39000
1.400	-4.564	381.86250	1215.16000	523.90190	402.13650	100.10000	2.49848	391.56980	880.61990	1.27421 2035 42500
1.400	-4.076	381.70730	1214.64999	523.68190	402.13790	100.10000	2.49743	391.40990	880.59990	1.27968 2035 39000
1.400	-3.582	381.96070	1215.30000	523.96120	402.15280	100.10000	2.49880	391.66990	880.57980	1.28237 2035 39000
1.400	-3.092	381.84370	1215.00999	523.83670	402.14500	100.10000	2.49819	391.54980	880.57980	1.29969 2035 35500
1.400	-2.605	381.99150	1215.08000	523.86430	402.03910	99.89999	2.49962	391.70000	880.56980	1.29961 2035 35500
1.400	-2.118	381.78760	1214.46001	523.59720	402.18020	100.10000	2.49714	391.49000	880.53980	1.30028 2035 39000
1.400	-1.634	381.96000	1215.39999	524.00490	402.14310	100.10000	2.49899	391.66990	880.52980	1.29977 2035 35500
1.400	-1.148	381.62700	1214.86000	523.77540	402.09400	100.10000	2.49776	391.32980	880.51980	1.28622 2035 35500
1.400	-.662	381.97390	1214.75000	523.72020	402.13700	100.00000	2.49841	391.67990	880.51980	1.28634 2035 35500
1.400	-.177	381.93240	1215.07001	523.86110	402.09420	100.00000	2.49896	391.63990	880.50000	1.30305 2035 35500
1.400	.333	381.91330	1214.91000	523.79130	402.10350	100.00000	2.49865	391.61990	880.50000	1.30666 2035 35500
1.400	.845	381.77370	1215.11000	523.88180	402.04270	100.00000	2.49891	391.48000	880.47000	1.30644 2035 39000
GRADIENT	.00284	-.00585	-.00264	-.01193	-.01858	.00010	.00287	-.02548	-.00468	-.00699

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 950  
( VCM044 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1551 / 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
1.450	-7.083	358.81570	1225.89000	528.12870	394.54880	100.80000	2.49418	368.28980	893.16990	1.40095
-6.580	358.84450	1226.00999	528.18020	394.54690	100.80000	2.49442	368.31980	893.18990	1.40082	
1.450	-6.087	358.72460	1226.36000	528.31960	394.47710	100.80000	2.49492	368.20000	893.18990	1.40408
1.451	-5.596	358.99460	1225.60001	528.01730	394.63180	100.80000	2.49384	368.47000	893.23000	1.41601
1.450	-5.106	358.90160	1226.44000	528.36180	394.52540	100.80000	2.49523	368.37990	893.24000	1.41874
1.450	-4.616	358.87480	1225.92299	528.14840	394.56370	100.80000	2.49431	368.34990	893.25000	1.38633
1.450	-4.127	358.92290	1226.17000	528.25070	394.55690	100.80000	2.49477	368.39990	893.26980	1.43022
1.450	-3.640	358.96090	1226.39000	528.34420	394.54860	100.80000	2.49519	368.43990	893.26980	1.38943
1.450	-3.158	359.24780	1226.17999	528.27150	394.72850	100.90000	2.49450	368.73000	893.28980	1.38604
1.449	-2.676	359.18160	1225.66000	528.05150	394.75540	100.90000	2.49353	368.65990	893.27980	1.38663
1.450	-2.202	358.70780	1225.78999	528.08150	394.59470	100.90000	2.49331	368.17990	893.28980	1.39012
1.450	-1.726	359.10790	1226.57001	528.42650	394.64870	100.90000	2.49505	368.58980	893.31980	1.39287
1.450	-1.249	358.75660	1225.89990	528.12990	394.59990	100.90000	2.49355	368.23000	893.31980	1.38999
1.450	-7.69	358.69920	1225.57001	527.98970	394.61210	100.90000	2.49291	368.16990	893.34990	1.39037
1.450	-2.91	358.87430	1225.99001	528.17330	394.62870	100.90000	2.49382	368.34990	893.33980	1.38263
1.450	.220	359.07100	1226.10001	528.22920	394.75070	101.00000	2.49360	368.54980	893.34990	1.38251
1.450	.736	358.69900	1225.59000	527.99800	394.61040	100.90000	2.49295	368.16990	893.35990	1.39035
GRADIENT	-.03482	-.06334	-.02812	.01323	.02604	-.00030	-.03567	.02074	-.00288	.00431
	RUN NO.	1635 / 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.500	PHI =	SH10+3
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.470	-7.080	347.59910	1221.73816	525.67207	390.38750	100.70000	2.49368	356.92990	888.37990	1.41636
1.469	-6.577	348.01950	1222.52295	525.94401	390.54220	100.80000	2.49448	357.35990	888.41990	1.41573
1.469	-6.086	347.96970	1222.37643	525.96187	390.58420	100.90000	2.49406	357.30980	888.40990	1.41928
1.469	-5.591	348.20510	1222.61768	526.07872	390.57640	100.80000	2.49516	357.54980	888.41990	1.41541
1.469	-5.097	348.22610	1222.18488	525.90399	390.61040	100.80000	2.49466	357.56980	888.42990	1.42317
1.470	-4.609	347.66550	1222.19788	525.86414	390.43680	100.80000	2.49395	357.00000	888.45000	1.41583
1.468	-4.120	348.38570	1222.11664	525.88963	390.70120	100.80000	2.49407	357.73000	888.43990	1.40520
1.470	-3.632	347.83540	1222.85844	526.14872	390.53830	100.80000	2.49323	357.16990	888.43990	1.35482
1.470	-3.150	347.82540	1223.08551	526.24062	390.53250	100.80000	2.49327	357.15990	888.45000	1.34417
1.470	-2.670	347.60960	1222.95071	526.16792	390.47310	100.80000	2.49286	356.93990	888.45000	1.34429
1.471	-2.185	348.14920	1223.18906	526.30878	390.61820	100.80000	2.49396	357.49000	888.46000	1.35102
1.470	-1.710	348.01950	1223.54475	526.44289	390.54220	100.80000	2.49448	357.35990	888.47000	1.35060
1.470	-1.232	348.18700	1223.77209	526.54965	390.60130	100.80000	2.49455	357.52980	888.46000	1.33657
1.470	-1.470	348.07960	1223.52621	526.44032	390.58230	100.80000	2.49414	357.41990	888.47000	1.34027
1.470	-7.48	348.94756	1223.54591	526.42343	390.47900	100.80000	2.49393	357.10990	888.48000	1.34020
1.471	-2.711	347.77420	1223.37109	526.37109	390.58520	100.80000	2.49395	357.39990	888.47000	1.34390
1.470	.242	348.06050	1223.35976	526.37109	390.69310	100.80000	2.49457	357.77980	888.48000	1.00000
1.484	.756	348.43380	1248.94756	536.91453	390.5796	100.80000	-.01401	.00015	.00734	-.02985
GRADIENT								.05910		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM044) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1586/0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	-2.500	PHI =	180.000
P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
ALPHA										
1.491	-7.079	337.67600	1223.84979	525.57053	386.03170	100.00000	2.49943	346.86990	896.86990	
1.492	-6.571	337.46900	1223.93689	525.58272	385.94900	100.00000	2.49948	346.65990	896.87990	
1.491	-6.082	337.59670	1223.77109	525.53104	385.99440	100.00000	2.49956	346.78980	896.86990	
1.491	-5.586	337.67480	1223.88550	525.58487	386.01000	100.00000	2.49984	346.86990	896.86990	
1.492	-5.091	337.61620	1224.38728	525.77689	385.9340	100.00000	2.49972	346.80980	896.86990	
1.492	-4.603	337.50070	1223.88133	525.56244	386.00660	100.00000	2.49862	346.68990	896.86990	
1.492	-4.111	337.26560	1223.66956	525.45126	385.94120	100.00000	2.49812	346.45000	896.88990	
1.491	-3.622	337.48970	1223.77970	525.51333	385.97800	100.00000	2.49908	346.67990	896.87990	
1.492	-3.141	337.54660	1224.49382	525.81256	385.95480	100.00000	2.49995	346.74000	896.87990	
1.492	-2.659	337.46070	1224.04657	525.62402	386.04710	100.10000	2.49826	346.64990	896.86990	
1.491	-2.175	337.56880	1224.01498	525.62391	386.08620	100.10000	2.49832	346.75980	896.87990	
1.491	-1.701	337.64620	1223.95447	525.60855	386.08740	100.10000	2.49887	346.83980	896.87990	
1.491	-1.219	337.66480	1224.21321	525.71381	386.07030	100.10000	2.49933	346.85990	896.87990	
1.492	-7.36	337.36160	1223.91496	525.56066	385.99610	100.10000	2.49801	346.54980	896.88990	
1.492	-.256	337.39230	1223.67694	525.46792	386.03390	100.10000	2.49801	346.57980	896.86990	
1.492	.257	337.48070	1223.82645	525.53901	386.06180	100.10000	2.49813	346.66990	896.87990	
1.492	.772	337.42090	1223.94359	525.57890	386.02510	100.10000	2.49839	346.60990	896.86990	
GRADIENT	.00090	-.00663	-.00245	.01402	.02299	-.00010	-.00010	-.00059	.00188	-.00910
RUN NO.		1602/0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	-2.500	PHI =	180.000
P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
ALPHA										
1.516	-7.084	327.61010	1230.36134	526.81582	382.67480	100.80000	2.49355	336.63990	905.26980	
1.516	-6.572	327.44530	1229.92250	526.62050	382.65770	100.80000	2.49262	336.47000	905.27980	
1.517	-6.076	327.11960	1230.45891	526.77956	382.50240	100.80000	2.49309	336.13990	905.26980	
1.517	-5.580	327.40010	1231.47679	527.21682	382.50730	100.80000	2.49513	336.42990	905.29980	
1.516	-5.096	327.68210	1232.11543	527.50671	382.55250	100.80000	2.49643	336.72000	905.29980	
1.517	-4.604	327.93220	1233.52086	528.09763	382.59570	100.80000	2.49797	337.03980	905.31980	
1.517	-4.112	327.77540	1233.97263	528.23988	382.47490	100.80000	2.49861	336.81980	905.31980	
1.517	-3.624	328.09860	1234.11818	528.34500	382.57840	100.80000	2.49911	337.14990	905.33980	
1.517	-3.139	328.24410	1234.71577	528.59872	382.59010	100.80000	2.49999	337.29980	905.32980	
1.517	-2.660	328.06030	1234.07005	528.32001	382.58470	100.80000	2.49869	337.10990	905.36990	
1.517	-2.178	327.11300	1230.34650	526.73289	382.64140	100.90000	2.49110	336.12990	905.35990	
1.517	-1.698	327.10300	1230.36657	526.73961	382.63090	100.90000	2.49122	336.11990	905.34990	
1.517	-1.218	327.50980	1231.53735	527.25597	382.65530	100.90000	2.49386	336.53980	905.34990	
1.517	-.736	327.52830	1231.65828	527.30647	382.56690	100.80000	2.49498	336.55980	905.34990	
1.517	-.255	327.49800	1231.65512	527.30069	382.54100	100.80000	2.49524	336.52980	905.35990	
1.517	.257	327.24370	1230.93649	526.98428	382.47020	100.80000	2.49465	336.26980	905.34990	
1.516	.771	327.57690	1230.82573	526.99193	382.57860	100.80000	2.49512	336.60990	905.34990	
GRADIENT	-.13494	-.29053	-.00245	-.00299	-.00010	-.00096	-.13947	-.00554	-.01653	-.00019

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 952  
( VCM044 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1617/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA = -2.500	PHI = 180.000	PARAMETRIC DATA								
								P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM					
1.541	-7.079	317.65990	1237.19394	527.75299	378.77250	101.00000	2.49218	326.50980	908.89990	1.53629	2033.60500					
1.541	-6.570	317.76250	1238.79779	528.37938	378.67630	101.00000	2.49482	326.61990	908.89990	1.52649	2033.60500					
1.541	-6.076	317.64670	1238.38524	528.20151	378.67720	101.00000	2.49389	326.50000	908.86990	1.52311	2033.57001					
1.541	-5.581	317.65750	1238.17535	528.12469	378.70510	101.00000	2.49344	326.50980	908.86990	1.51951	2033.57001					
1.541	-5.091	317.63820	1238.10475	528.09476	378.70460	101.00000	2.49330	326.49000	908.85990	1.51959	2033.57001					
1.541	-4.603	317.52170	1237.84538	527.97378	378.68650	101.00000	2.49273	326.36990	908.83980	1.51990	2033.57001					
1.541	-4.115	317.66940	1237.67633	527.93832	378.76440	101.00000	2.49241	326.51980	908.80980	1.51242	2033.57001					
1.541	-3.624	317.62060	1237.74698	527.95614	378.74610	101.00000	2.49237	326.47000	908.77980	1.50848	2033.57001					
1.542	-3.136	317.25980	1237.29597	527.71720	378.65840	101.00000	2.49121	326.09990	908.76980	1.50897	2033.57001					
1.542	-2.659	317.22170	1237.21465	527.67928	378.66800	101.00000	2.49073	326.05980	908.76000	1.49758	2033.53500					
1.542	-2.175	317.04590	1237.05223	527.58476	378.61470	101.00000	2.49035	325.87990	908.75000	1.50157	2033.53500					
1.542	-1.697	317.33890	1237.28059	527.72630	378.70360	101.00000	2.49097	326.17990	908.73000	1.49752	2033.57001					
1.541	-1.218	317.53100	1238.27676	528.13963	378.68290	101.00000	2.49287	326.37990	908.70000	1.49633	2033.53500					
1.542	-737	317.63480	1239.37547	528.57459	378.68380	101.10000	2.49435	326.49000	908.67990	1.49880	2033.53500					
1.542	-254	318.08130	1240.57510	529.11280	378.74540	101.10000	2.49669	326.95000	908.67990	1.48979	2033.57001					
1.542	.257	317.94460	1240.75687	529.15570	378.71170	101.10000	2.49626	326.80980	908.58980	1.46692	2033.57001					
1.541	.771	317.99610	1240.13394	528.93038	378.79050	101.10000	2.49516	326.85990	908.58980	1.46394	2033.53500					
GRADIENT		.10105	.62293	.25483	.00674	.02304	.00082	.10504	-.04385	-.00877	-.00384					

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM045) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1571/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
ALPHA	P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
.599	-7.078	1253.18500	1596.75000	314.37940	522.51810	100.30000	2.49286	1303.10001	.99893 2034.69000
.599	-6.577	1253.02100	1597.35001	315.01900	522.44260	100.30000	2.49569	1262.77000	.97775 2034.69000
.599	-6.082	1252.46700	1596.13000	314.44780	522.49050	100.30000	2.49259	1262.20000	.97592 2034.65500
.600	-5.586	1252.62700	1597.22000	315.23240	522.40770	100.30000	2.49636	1262.38000	.97269 2034.62000
.599	-5.096	1252.82700	1596.89999	314.79980	522.46140	100.30000	2.49452	1262.57001	.97032 2034.62000
.600	-4.607	1251.84200	1596.36000	315.15360	522.39450	100.30000	2.49534	1261.59000	.97321 2034.69000
.600	-4.121	1252.13800	1596.81000	315.28930	522.38790	100.30000	2.49622	1261.89000	.97038 2034.65500
.600	-3.632	1252.49800	1597.07001	315.12420	522.40650	100.30000	2.49616	1262.25000	.97022 2034.62000
.600	-3.149	1252.11800	1596.75999	315.26320	522.48340	100.40000	2.49551	1261.87000	.97041 2034.65500
.600	-2.668	1251.70799	1596.92999	315.74240	522.41870	100.40000	2.49740	1261.47000	.97287 2034.65500
.600	-2.194	1251.96201	1596.96001	315.55980	522.44600	100.40000	2.49676	1261.72000	.99880 2034.69000
.600	-1.723	1251.82001	1596.92999	315.65060	522.43190	100.40000	2.49706	1261.58000	1.00144 2034.72501
.600	-1.258	1252.02699	1597.25999	315.75850	522.51900	100.50000	2.49716	1261.78999	1.00651 2034.72501
.600	-78.8	1252.27100	1596.78999	315.16380	522.59200	100.50000	2.49461	1262.02000	1.01212 2034.72501
.600	-317	1251.78999	1596.94000	315.68410	522.52080	100.50000	2.49662	1261.55000	1.00937 2034.75999
.600	-194	1252.20200	1597.12000	315.49680	522.55300	100.50000	2.49610	1261.96001	1.00925 2034.79500
.600	.719	1252.39301	1597.25999	315.45870	522.56270	100.50000	2.49608	1262.14999	1.00651 2034.79500
GRADIENT	.02435	.09445	.05948	.03614	.04511	.00004	.02580	.05512	.00946 .02905

RUN NO. 1461/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.	1461/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
ALPHA	P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
.800	-7.059	879.88870	1341.16000	394.12380	496.34810	100.20000	2.49787	889.78980	1050.32001
.800	-6.553	879.67680	1341.13000	394.24580	496.31710	100.20000	2.49816	889.57980	1050.39000
.800	-6.054	879.90380	1340.81000	393.85420	496.47630	100.30000	2.49621	889.79980	1050.47000
.800	-5.558	879.91280	1340.89000	393.90750	496.46920	100.30000	2.49643	889.80980	1050.53000
.800	-5.065	879.65990	1340.91000	394.09420	496.42630	100.30000	2.49694	889.55980	1050.59000
.800	-4.575	879.78340	1340.75999	393.89920	496.46220	100.30000	2.49627	889.67990	1050.66000
.800	-4.084	879.64770	1341.03999	394.19850	496.41060	100.30000	2.49736	889.54980	1050.73000
.800	-3.596	879.49850	1340.89999	394.19680	496.40140	100.30000	2.49720	889.39990	1050.77000
.800	-3.105	879.72070	1340.89999	394.04540	496.43730	100.30000	2.49681	889.61990	1050.83000
.800	-2.618	879.78120	1340.91000	394.01150	496.44580	100.30000	2.49673	889.67990	1050.89000
.800	-2.140	879.70800	1341.07001	394.17990	496.41720	100.30000	2.49734	889.60990	1050.95000
.800	-1.664	879.77980	1341.00999	394.08690	496.43510	100.30000	2.49703	889.67990	1051.03000
.800	-1.187	879.66670	1341.10001	394.23000	496.40720	100.30000	2.49751	889.56980	1051.08000
.800	-709	879.91040	1341.03999	394.02000	496.36430	100.20000	2.49747	889.80980	1051.16000
.800	-234	879.63920	1340.94000	394.13040	496.33110	100.20000	2.49765	889.53980	1051.20000
.800	.278	879.77080	1340.92000	394.02610	496.35450	100.20000	2.49735	889.66990	1051.28000
.800	.798	879.75590	1341.23000	394.26560	496.31930	100.20000	2.49832	889.65990	1051.33000
GRADIENT	.01777	.04042	.01782	-.02186	-.02305	.00022	.01821	.12709	-.01185

RUN NO.	1461/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
ALPHA	P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
.800	-7.059	879.88870	1341.16000	394.12380	496.34810	100.20000	2.49787	889.78980	1050.32001
.800	-6.553	879.67680	1341.13000	394.24580	496.31710	100.20000	2.49816	889.57980	1050.39000
.800	-6.054	879.90380	1340.81000	393.85420	496.47630	100.30000	2.49621	889.79980	1050.47000
.800	-5.558	879.91280	1340.89000	393.90750	496.46920	100.30000	2.49643	889.80980	1050.53000
.800	-5.065	879.65990	1340.91000	394.09420	496.42630	100.30000	2.49694	889.55980	1050.59000
.800	-4.575	879.78340	1340.75999	393.89920	496.46220	100.30000	2.49627	889.67990	1050.66000
.800	-4.084	879.64770	1341.03999	394.19850	496.41060	100.30000	2.49736	889.54980	1050.73000
.800	-3.596	879.49850	1340.89999	394.19680	496.40140	100.30000	2.49720	889.39990	1050.77000
.800	-3.105	879.72070	1340.89999	394.04540	496.43730	100.30000	2.49681	889.61990	1050.83000
.800	-2.618	879.78120	1340.91000	394.01150	496.44580	100.30000	2.49673	889.67990	1050.89000
.800	-2.140	879.70800	1341.07001	394.17990	496.41720	100.30000	2.49734	889.60990	1050.95000
.800	-1.664	879.77980	1341.00999	394.08690	496.43510	100.30000	2.49703	889.67990	1051.03000
.800	-1.187	879.66670	1341.10001	394.23000	496.40720	100.30000	2.49751	889.56980	1051.08000
.800	-709	879.91040	1341.03999	394.02000	496.36430	100.20000	2.49747	889.80980	1051.16000
.800	-234	879.63920	1340.94000	394.13040	496.33110	100.20000	2.49765	889.53980	1051.20000
.800	.278	879.77080	1340.92000	394.02610	496.35450	100.20000	2.49735	889.66990	1051.28000
.800	.798	879.75590	1341.23000	394.26560	496.31930	100.20000	2.49832	889.65990	1051.33000
GRADIENT	.01777	.04042	.01782	-.02186	-.02305	.00022	.01821	.12709	-.01185

## PARAMETRIC DATA

RUN NO.	1495/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
ALPHA	.752	.93990	1273.22000	426.75880	481.49630	99.80000	2.50044	762.95000	1.82465 2036 58000
.900	-7.060	752.93990	1273.22000	426.65550	481.40190	99.70000	2.50031	762.66990	1.82055 2036 61501
.900	-6.552	752.63330	1272.83000	426.60570	481.60670	99.89999	2.49925	762.95000	1.82496 2036 58000
.900	-6.059	752.94340	1273.00000	426.81350	481.54710	99.89999	2.49976	762.64990	1.81098 2036 58000
.900	-5.561	752.64040	1273.03999	426.1272	481.46340	99.80000	2.49989	762.52980	1.81130 2036 61501
.900	-5.066	752.52220	1272.82001	426.73270	481.44780	99.80000	2.50067	762.64990	1.81081 2036 61501
.900	-4.581	752.63870	1273.16000	426.89700	481.39790	99.80000	2.50024	762.13990	1.80215 2036 61501
.900	-4.089	752.13010	1272.75999	426.92480	481.42580	99.80000	2.50082	762.52980	1.79699 2036 61501
.900	-3.595	752.51760	1273.16000	426.96900	481.51340	99.80000	2.49959	762.81980	1.79743 2036 58000
.900	-3.113	752.81420	1272.85001	426.57960	481.36130	99.70000	2.50129	762.65990	1.77768 2036 61501
.900	-2.624	752.64840	1273.17999	426.90480	481.41430	99.70000	2.50260	762.82980	1.76521 2036 61501
.900	-2.142	752.82080	1273.09000	426.74050	481.41430	99.70000	2.50065	762.86990	1.76527 2036 64999
.900	-1.669	752.86180	1273.05000	426.68850	481.41140	99.70000	2.50059	762.82980	1.75631 2036 64999
.900	-1.196	752.82200	1273.00999	426.68480	481.38210	99.59999	2.50041	763.02980	1.74758 2036 61501
.899	-720	753.02610	1272.83000	426.43950	481.29810	99.59999	2.50142	762.70000	1.74730 2036 64999
.900	-245	752.69040	1273.03999	426.78340	481.24490	99.50000	2.50161	762.82980	1.74294 2036 64999
.900	.267	752.82250	1272.96001	426.65010	481.20780	99.50000	2.50211	762.70000	1.73386 2036 64999
.900	.786	752.68990	1273.08000	426.81150	481.03915	-.04398	-.06073	.00025	.06878 .04837
GRADIENT	.06931	-.00393	-.00393	-.04398	-.03915	-.04398	-.06073	-.00025	-.01476 .00906

RUN NO.	1478/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
ALPHA	.563	.30080	1205.63000	478.80470	450.38990	100.10000	2.49845	573.49000	916.46000
.1.102	-7.027	564.79590	1207.33000	479.20410	450.54960	100.10000	2.50164	575.50000	916.50000
.1.101	-6.516	564.93580	1206.47000	478.64870	450.59280	100.00000	2.50019	575.12990	916.56980
.1.100	-6.017	564.98800	1206.28999	478.52340	450.54320	99.89999	2.50034	575.17990	916.58980
.1.100	-5.516	564.77120	1205.96001	478.41720	450.69020	100.10000	2.49852	574.96000	916.60990
.1.100	-5.025	564.81910	1206.16000	478.51460	450.43820	99.80000	2.50070	575.01000	916.67990
.1.100	-4.523	564.92040	1206.06000	478.41630	450.47190	99.80000	2.50043	575.10990	916.70000
.1.100	-4.021	564.15160	1206.00000	478.29000	450.69210	100.00000	2.49901	575.33980	916.71000
.1.100	-3.531	564.75220	1205.85001	478.36060	450.53660	99.89999	2.49944	574.93990	916.72000
.1.100	-3.035	565.13180	1205.98000	478.28640	450.68970	100.00000	2.49898	575.31980	916.74000
.1.100	-2.542	564.92310	1205.82001	478.27560	450.57860	99.89999	2.49929	575.10990	916.85990
.1.100	-2.052	564.92800	1206.28999	478.54710	450.52950	99.89999	2.50037	575.11990	916.76000
.1.100	-1.560	565.05420	1205.77000	478.19510	450.61380	99.89999	2.49911	575.24000	916.83980
.1.100	-1.075	565.07100	1206.05000	478.35110	450.58790	99.89999	2.49975	575.26000	916.84990
.1.100	-5.588	564.89230	1205.89000	478.32860	450.56420	99.89999	2.49946	575.07980	916.86990
.1.100	-1.103	564.92310	1205.82001	478.44730	450.47710	99.80000	2.50062	575.17990	916.90990
.1.100	-405	564.98950	1206.16000	478.31080	450.49630	99.80000	2.50004	575.13990	916.92990
.1.100	.915	564.95210	1205.89999	478.02367	450.08080	-.00138	-.00713	-.00002	.00778 .04860
GRADIENT	.08080	-.02367	-.01693	-.01693	-.00138	-.00002	-.00002	-.00002	-.04900 -.00254

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM045) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1518/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.250	-7.049	462.59130	1198.24001	505.95730	426.26320	99.80000	2.50175	472.72000	864.57980	1.41844	2035	77499	
-6.539	462.55440	1197.78999	505.73730	426.29930	99.80000	2.50083	472.67990	864.56980	1.41897	2035	77499		
1.250	-6.042	462.68920	1198.50000	506.06760	426.18630	99.70000	2.50089	472.81980	864.54980	1.39602	2035	77499	
1.250	-5.546	462.49390	1197.89000	506.80130	426.19700	99.70000	2.50162	472.61990	864.56980	1.40039	2035	77499	
1.250	-5.047	462.61430	1197.78000	505.71920	426.31590	99.80000	2.50082	472.74000	864.56980	1.40420	2035	77499	
1.249	-4.558	462.99020	1198.22000	505.85990	426.29390	99.70000	2.50235	473.11990	864.56980	1.40736	2035	77499	
1.250	-4.063	462.39700	1197.50000	505.62500	426.28710	99.80000	2.50022	472.51980	864.54980	1.41190	2035	77499	
1.250	-3.575	462.46480	1197.73000	505.72630	426.28170	99.80000	2.50070	472.58980	864.52980	1.41163	2035	81000	
1.250	-3.082	462.51200	1198.19000	505.94950	426.17110	99.70000	2.50223	472.63990	864.53894	2035	77499		
1.250	-2.598	462.4340	1197.97000	505.85280	426.17550	99.70000	2.50178	472.63990	864.51980	1.31812	2035	77499	
1.250	-2.112	462.60300	1197.97000	505.81790	426.14140	99.59999	2.50238	472.73000	864.51000	1.29071	2035	81000	
1.250	-1.636	462.64530	1197.62000	505.63130	426.18800	99.59999	2.50168	472.76980	864.51980	1.28091	2035	81000	
1.250	-1.157	462.68260	1198.00999	505.82080	426.23440	99.70000	2.50189	472.80980	864.51980	1.27039	2035	84500	
1.250	-678	462.86060	1198.20000	505.87790	426.26200	99.70000	2.50230	472.99000	864.51980	1.28029	2035	84500	
1.250	-201	462.50200	1198.17999	505.94650	426.16970	99.70000	2.50221	472.62990	864.48000	1.28031	2035	81000	
1.249	.313	462.70460	1197.69000	505.65360	426.27270	99.70000	2.50124	472.82980	864.47000	1.29101	2035	81000	
1.250	.830	462.55270	1198.05000	505.86940	426.19600	99.70000	2.50195	472.67990	864.47000	1.30431	2035	84500	
GRADIENT	.00488	.01997	.00902	-.00950	-.00950	-.01150	.00011	.00503	-.01694	-.02574	.01178		
	RUN NO.	1534/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00							
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM		
1.400	-7.044	381.88310	1215.05000	523.85330	401.93750	99.80000	2.50007	391.58980	880.42990	1.30995	2035	35500	
-6.539	382.06910	1215.32001	523.96780	401.96800	99.80000	2.50071	391.77980	880.41990	1.30621	2035	35500		
1.400	-6.036	381.73560	1214.91000	523.79520	402.05000	100.00000	2.49852	391.43990	880.41990	1.28278	2035	35500	
-5.541	381.61550	1215.12000	523.88920	401.85030	99.80000	2.50001	391.31980	880.40990	1.28256	2035	39000		
-5.046	381.83420	1214.92000	523.79740	402.07890	100.00000	2.49861	391.53980	880.39990	1.27940	2035	35500		
1.400	-4.554	381.84670	1214.50999	523.61790	402.12130	100.00000	2.49787	391.54980	880.38990	1.27983	2035	35500	
1.400	-4.058	381.80300	1215.21001	523.92500	402.04200	100.00000	2.49912	391.50980	880.38990	1.27909	2035	35500	
1.399	-3.570	382.05220	1214.89999	523.78440	402.14620	100.00000	2.49874	391.75980	880.37990	1.27605	2035	35500	
1.400	-3.074	381.84500	1214.80000	523.74490	401.94970	99.80000	2.49959	391.54980	880.34990	1.27279	2035	39000	
1.400	-2.590	382.05000	1215.22000	523.92430	402.11550	100.00000	2.49932	391.75980	880.33980	1.27235	2035	39000	
1.400	-2.108	381.47000	1214.66000	523.69090	401.99390	100.00000	2.49787	391.16990	880.32980	1.27294	2035	39000	
1.400	-1.621	381.91280	1215.03999	523.84840	402.09110	100.00000	2.49889	391.61990	880.31980	1.27254	2035	39000	
-1.143	381.72580	1214.89000	523.78660	402.04910	100.00000	2.49848	391.42990	880.29980	1.26935	2035	39000		
1.400	-6.62	381.92110	1215.28000	523.95310	401.92720	99.80000	2.50052	391.62990	880.29980	1.26894	2035	42500	
1.400	-1.184	381.83450	1214.88000	523.78000	402.08280	100.00000	2.49854	391.53980	880.28980	1.26936	2035	39000	
1.400	.329	381.73660	1214.73000	523.71630	401.92380	99.80000	2.49938	391.43990	880.26000	1.26951	2035	35500	
1.400	.847	381.88060	1215.46001	524.03270	402.04170	100.00000	2.49963	391.58980	880.25000	1.26541	2035	35500	
GRADIENT	-.01354	.05621	.02484	-.01863	-.01863	-.01288	.00117	-.01332	-.02542	-.00230	.00291		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 956  
(VCMO45) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1552/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000	PATM
ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.450	-7.072	358.79640	1225.80000	528.09060	394.69190	101.00000	2.49281	368.26980	893.38990	1.39375 2035.25000
-6.564	358.62890	1225.81000	528.08590	394.63840	101.00000	2.49267	368.09990	893.38990	1.39379 2035.25000	
1.450	-6.068	358.83470	1226.00000	528.17550	394.68550	101.00000	2.49320	368.30980	893.40990	1.40449 2035.25000
1.450	-5.576	358.88840	1225.17999	527.83720	394.77780	101.00000	2.49181	368.35990	893.43990	1.40912 2035.25000
-5.08	359.23580	1226.59000	528.44120	394.75730	101.00000	2.49462	368.72000	893.43990	1.45987 2035.25000	
1.450	-4.596	358.99170	1226.16000	528.25000	394.72020	101.00000	2.49363	368.47000	893.48000	1.45658 2035.28500
1.449	-4.104	359.15990	1226.07001	528.22120	394.78120	101.00000	2.49363	368.63990	893.47000	1.45669 2035.28500
-3.615	358.62480	1226.64000	528.43070	394.63110	101.10000	2.49353	368.09990	893.48000	1.45222 2035.28500	
-3.130	358.77760	1225.64999	528.02710	394.77030	101.10000	2.49194	368.25000	893.48000	1.44584 2035.25000	
1.450	-2.651	359.01270	1225.91000	528.14720	394.82030	101.10000	2.49262	368.49000	893.50000	1.44553 2035.25000
1.450	-2.180	359.06250	1225.84000	528.12060	394.84230	101.10000	2.49254	368.53980	893.51000	1.39370 2035.25000
1.451	-1.705	358.56710	1226.32001	528.29440	394.71290	101.20000	2.49232	368.03980	893.50000	1.40046 2035.25000
1.450	-1.239	358.93370	1225.75999	528.08370	394.89840	101.20000	2.49174	368.47000	893.51980	1.40477 2035.25000
1.450	-767	358.89600	1225.60001	528.01220	394.88260	101.20000	2.49137	368.36990	893.50000	1.40495 2035.25000
1.450	-297	359.00950	1226.53999	528.40890	394.83180	101.20000	2.49313	368.49000	893.51980	1.40755 2035.25000
1.450	.217	358.95190	1226.23000	528.27710	394.84200	101.20000	2.49253	368.42990	893.55980	1.42642 2035.25000
1.450	.738	358.90480	1225.85001	528.11670	394.86230	101.20000	2.49182	368.37990	893.53980	1.41943 2035.28500
GRADIENT	-.00093	-.02150	-.00899	.03036	.04071	-.00028	-.00104	.01378	-.00952	-.00407

RUN NO.	1636/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000	PATM
ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.470	-7.065	347.70580	1223.24156	526.29426	390.46610	100.80000	2.49368	357.03980	888.49000	1.35090 2032.62500
-6.561	348.10940	1223.23488	526.32399	390.59450	100.80000	2.49412	357.45000	888.49000	1.35443 2032.62500	
-6.061	347.87230	1223.35248	526.35254	390.57470	100.90000	2.49354	357.21000	888.49000	1.35427 2032.59000	
1.470	-5.573	348.26640	1223.32239	526.37239	390.70830	100.90000	2.49381	357.60990	888.49000	1.35435 2032.55499
1.469	-5.082	347.86430	1223.00900	526.21163	390.60380	100.90000	2.49292	357.20000	888.49000	1.35465 2032.55499
1.470	-4.585	348.05180	1222.82808	526.15346	390.67650	100.90000	2.49288	357.38990	888.50000	1.35836 2032.55499
1.470	-4.099	347.80470	1223.03294	526.21685	390.57570	100.90000	2.49303	357.13990	888.50000	1.35810 2032.55499
1.470	-3.610	348.00120	1223.14494	526.27899	390.63040	100.90000	2.49340	357.33980	888.51000	1.35800 2032.52000
1.470	-3.129	348.05050	1223.10211	526.26525	390.65090	100.90000	2.49336	357.38990	888.51000	1.35805 2032.55499
1.469	-2.642	348.37550	1222.59827	526.08528	390.75490	100.90000	2.49370	357.72000	888.51000	1.36860 2032.52000
1.470	-2.165	347.93140	1223.28343	526.32963	390.59450	100.90000	2.49358	357.26980	888.51000	1.35783 2032.52000
1.470	-1.692	347.94140	1223.21774	526.30366	390.59770	100.90000	2.49359	357.27980	888.51000	1.36139 2032.52000
1.470	-1.222	347.74510	1222.98036	526.19053	390.54830	100.90000	2.49313	357.07980	888.51000	1.36513 2032.48500
1.470	-7.48	348.02120	1222.86775	526.16752	390.64400	100.90000	2.49328	357.35990	888.51000	1.36880 2032.52000
1.470	-2.74	347.92160	1223.01427	526.21852	390.59130	100.90000	2.49357	357.25980	888.51980	1.37213 2032.52000
1.470	.237	348.03030	1222.93877	526.19650	390.63430	100.90000	2.49353	357.36990	888.52980	1.37223 2032.52000
1.469	.759	348.08030	1222.79753	526.14330	390.66410	100.90000	2.49332	357.41990	888.51000	1.37240 2032.48500
GRADIENT	-.00139	-.01609	-.00671	-.00375	-.00000	-.00006	-.00123	.00322	.00006	.00271

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM045) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.492	-7.065	337.58760	1224.25060	525.71880	386.07710	100.10000	2.49863	346.77980	896.86990	1.63258 2033.71001
-6.558	337.60570	1225.01071	526.02330	386.11910	100.20000	2.49868	346.79980	896.89990	1.60700 2033.74500	
-6.061	337.68430	1224.97150	526.01641	386.14310	100.20000	2.49881	346.87990	896.86990	1.61113 2033.64000	
-5.569	337.36040	1224.48401	525.78690	386.04320	100.20000	2.49831	346.54980	896.87990	1.63637 2033.71001	
-5.076	337.62820	1223.77762	525.53548	386.18430	100.20000	2.49760	346.81980	896.88990	1.64563 2033.71001	
-4.586	337.54930	1223.85106	525.55599	386.15140	100.20000	2.49765	346.74000	896.89990	1.64552 2033.67500	
-4.094	337.59740	1224.00806	525.62480	386.14110	100.20000	2.49820	346.78980	896.88990	1.65364 2033.67500	
-3.601	337.68410	1224.41745	525.79732	386.13940	100.20000	2.49888	346.87990	896.89990	1.64893 2033.67500	
-3.117	337.74240	1224.52301	525.84574	386.14330	100.20000	2.49923	346.93990	896.88990	1.65296 2033.71001	
-2.637	337.69410	1224.53146	525.84321	386.14430	100.20000	2.49985	346.88990	896.89990	1.64048 2033.74500	
-2.156	337.57570	1224.60188	525.85753	386.09860	100.20000	2.49885	346.76980	896.88990	1.64037 2033.71001	
-1.682	337.62450	1224.81007	525.94630	386.10210	100.20000	2.49915	346.81980	896.87990	1.63596 2033.71001	
-1.208	337.57470	1224.87786	525.96832	386.07320	100.20000	2.49933	346.76980	896.88990	1.64000 2033.67500	
-1.491	-7.736	337.83010	1224.80124	525.96629	386.15940	100.20000	2.49957	347.02980	896.86990	1.64427 2033.67500
-492	-260	337.66330	1224.97777	526.01780	386.10570	100.20000	2.49936	346.85990	896.87990	1.63161 2033.71001
.251	337.76150	1225.54337	526.25240	386.14060	100.20000	2.49942	346.96000	896.85990	1.59416 2033.67500	
1.492	.775	337.55420	1225.76331	526.31599	386.05150	100.20000	2.49959	346.75000	896.86990	1.59385 2033.67500
GRADIENT	.01080	.30064	.12060	-.12060	-.01071	-.000000	.00028	.01172	-.00636	-.00927 -.00105

RUN NO. 1587/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.516	-7.071	327.42110	1229.60542	526.49765	382.55220	100.80000	2.49444	336.45000	905.37990	1.68256 2033.74500
-6.562	327.27470	1229.47107	526.42372	382.51370	100.80000	2.49406	336.29980	905.40990	1.68272 2033.74500	
1.516	-6.066	327.17720	1229.19820	526.30327	382.49340	100.80000	2.49370	336.20000	905.38990	1.69160 2033.74500
-5.568	327.52950	1229.28922	526.39196	382.59550	100.80000	2.49445	336.55980	905.40990	1.70007 2033.71001	
-5.071	327.51950	1229.10812	526.32115	382.59110	100.80000	2.49445	336.54980	905.42990	1.71322 2033.74500	
-4.585	327.56790	1229.06923	526.31374	382.59420	100.80000	2.49476	336.59990	905.43990	1.72626 2033.74500	
1.515	-4.089	327.42160	1228.66487	526.12519	382.56270	100.80000	2.49424	336.45000	905.42990	1.73989 2033.78000
-3.602	327.27390	1228.57481	526.07888	382.49680	100.80000	2.49437	336.29980	905.47000	1.75756 2033.78000	
1.515	-3.119	327.26460	1228.19576	525.93230	382.50420	100.80000	2.49416	336.28980	905.45000	1.77584 2033.74500
-2.633	327.43240	1227.65855	525.74875	382.58670	100.80000	2.49387	336.46000	905.45000	1.79456 2033.74500	
1.515	-2.156	327.29520	1227.50073	525.66747	382.47340	100.70000	2.49428	336.31980	905.46000	1.80378 2033.74500
1.515	-1.68	327.09860	1227.44427	525.61707	382.39280	100.70000	2.49431	336.11990	905.47000	1.81743 2033.74500
1.515	-1.211	327.18730	1227.24091	525.55128	382.50390	100.80000	2.49358	336.21000	905.47000	1.82231 2033.74500
1.514	-.736	327.34420	1227.15237	525.54044	382.49150	100.70000	2.49431	336.36990	905.47000	1.82703 2033.71001
1.514	-.261	327.47190	1227.00227	525.50164	382.60500	100.80000	2.49382	336.50000	905.49000	1.83644 2033.74500
1.514	.251	327.30520	1226.92586	525.44751	382.54860	100.80000	2.49363	336.32980	905.49000	1.84112 2033.78000
1.515	.775	327.04080	1226.75029	525.34008	382.46730	100.80000	2.49316	336.05980	905.48000	1.84595 2033.78000
GRADIENT	-.04385	-.42499	-.17054	-.00849	-.00356	-.00020	-.04515	.00933	.02268	-.00020

RUN NO. 1603/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 958  
(VCM045) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1618/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-2.000	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.541	-7.064	317.27170	1237.05788	527.62996	378.78270	101.10000	2.48963	326.10990	908.54980	1.48638	2033.50000
1.542	-6.556	317.65550	1239.12794	528.48519	378.79130	101.20000	2.49316	326.50980	908.52980	1.49149	2033.50000
1.541	-6.061	318.00710	1239.07172	528.52959	378.89450	101.20000	2.49396	326.86990	908.50000	1.51074	2033.53500
1.541	-5.567	317.42380	1237.82184	527.94695	378.79420	101.20000	2.49129	326.26980	908.47000	1.51605	2033.53500
1.541	-5.076	317.54130	1237.79987	527.96057	378.83250	101.20000	2.49148	326.38990	908.46000	1.51996	2033.53500
1.541	-4.580	317.46290	1237.86537	527.97044	378.79880	101.20000	2.49150	326.30980	908.46000	1.51986	2033.53500
1.541	-4.093	317.60010	1237.76906	527.96017	378.85080	101.20000	2.49159	326.45000	908.42990	1.52388	2033.53500
1.541	-3.602	317.71680	1237.98145	528.06226	378.87840	101.20000	2.49198	326.56980	908.42990	1.51976	2033.53500
1.541	-3.116	317.74560	1238.03166	528.08672	378.87380	101.20000	2.49230	326.59990	908.40990	1.52746	2033.53500
1.541	-2.638	317.67750	1237.89406	528.02164	378.85640	101.20000	2.49209	326.52980	908.38990	1.53150	2033.53500
1.541	-2.156	317.59790	1238.29883	528.16021	378.73000	101.10000	2.49319	326.45000	908.36990	1.52709	2033.53500
1.541	-1.682	317.75420	1238.39066	528.22357	378.84470	101.20000	2.49292	326.60990	908.35990	1.52700	2033.53500
1.542	-1.211	317.45120	1238.41452	528.17635	378.74560	101.20000	2.49242	326.29980	908.34990	1.51917	2033.53500
1.541	-0.734	317.85110	1238.98125	528.46664	378.85250	101.20000	2.49353	326.71000	908.32980	1.50698	2033.50000
1.542	-0.260	317.56710	1238.94794	528.40003	378.75510	101.20000	2.49316	326.41990	908.33980	1.50697	2033.53500
1.541	.252	317.99800	1239.01360	528.50635	378.90700	101.20000	2.49365	326.85990	908.30980	1.50314	2033.50000
1.542	.775	317.71390	1239.09665	528.48368	378.79910	101.20000	2.49347	326.56980	908.29980	1.50298	2033.53500
GRADIENT	.03854	.03854	.27426	.11111	-.00485	.00071	.00040	.04014	-.02902	-.00435	-.00356

## IA310 (AFDC 16TF-783) PROBE CALIBRATION

(VCM046) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1572/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	-1.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PARM
.599	-7.062	1253.16800	1597.09000	314.67940	522.67090	100.50000	2.49310	1262.91000	1303.57001	.97277 2034.75999
.599	-6.552	1252.78400	1596.50000	314.49830	522.68040	100.50000	2.49195	1262.52000	1303.63000	.97057 2034.79500
.600	-6.061	1252.41600	1597.11000	315.31320	522.57930	100.50000	2.49542	1262.17000	1303.63000	.97020 2034.83000
.600	-5.564	1252.12399	1597.49001	315.87230	522.50900	100.50000	2.49777	1261.89000	1303.67999	.96741 2034.83000
.600	-5.069	1252.23700	1597.42999	315.72920	522.52810	100.50000	2.49720	1262.00000	1303.69000	.96745 2034.79500
.600	-4.578	1252.55701	1597.67000	315.66820	522.54390	100.50000	2.49718	1262.32001	1303.73000	.96986 2034.83000
.600	-4.089	1252.26401	1597.09000	315.42110	522.56320	100.50000	2.49580	1262.02000	1303.75999	.97021 2034.83000
.600	-3.601	1251.59801	1596.37000	315.36180	522.55100	100.50000	2.49497	1261.35001	1303.78000	.97578 2034.83000
.600	-3.115	1252.23199	1596.66000	315.08570	522.59960	100.50000	2.49422	1261.98000	1303.80000	.97047 2034.86501
.600	-2.635	1252.26100	1596.72000	315.11210	522.50420	100.40000	2.49493	1262.00999	1303.82001	.97043 2034.83000
.600	-2.160	1251.76801	1597.00999	315.76070	522.41820	100.40000	2.49753	1261.53000	1303.85001	.97282 2034.83000
.599	-1.691	1252.55701	1596.67000	314.82760	522.54420	100.40000	2.49385	1262.30000	1303.88000	.97559 2034.79500
.600	-1.231	1251.81599	1596.66000	315.422750	522.45680	100.40000	2.49602	1261.57001	1303.89999	.97560 2034.79500
.600	-7.78	1252.52499	1597.23000	315.32470	522.48780	100.40000	2.49613	1262.28000	1303.89999	.97782 2034.83000
.600	-3.223	1252.07899	1596.70000	315.24510	522.48440	100.40000	2.49540	1261.83000	1303.92999	.98850 2034.83000
.600	.189	1252.26500	1597.53999	315.79860	522.42800	100.40000	2.49812	1262.03000	1303.97000	.97250 2034.83000
.600	.726	1251.66299	1596.67000	315.56100	522.43750	100.40000	2.49652	1261.42000	1303.77000	.96791 2034.86501
GRADIENT	-.04197	-.01840	.01903	-.02522	-.02351	.00019	-.04169	.04660	.00010	.00052
RUN NO.		1462/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	-1.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PARM
.800	-7.047	879.83620	1341.27000	394.24070	496.41670	100.30000	2.49772	889.74000	1051.62000	6.15842 2038.64500
.800	-6.538	879.78780	1341.12000	394.16240	496.51340	100.40000	2.49678	889.68990	1051.67000	6.13424 2038.64500
.800	-6.044	879.87230	1340.88000	393.92750	496.55220	100.40000	2.49590	889.76980	1051.72000	6.09819 2038.64500
.800	-5.543	879.73390	1341.34000	394.36210	496.48140	100.40000	2.49754	889.63990	1051.78999	6.08375 2038.61000
.800	-5.050	880.11230	1341.03999	393.88260	496.57420	100.40000	2.49596	890.01000	1051.82001	6.04825 2038.61000
.800	-4.560	879.81860	1341.11000	394.13430	496.51930	100.40000	2.49670	889.72000	1051.87000	6.02347 2038.61000
.800	-4.061	879.46610	1341.03000	394.31470	496.47090	100.40000	2.49708	889.36990	1051.92999	6.02383 2038.57500
.800	-3.571	879.62260	1340.73000	393.98630	496.52780	100.40000	2.49589	889.51980	1051.99001	6.00082 2038.57500
.800	-3.084	879.70140	1340.86000	394.02930	496.52690	100.40000	2.49615	889.59990	1052.05000	5.95904 2038.57500
.800	-2.598	879.79830	1341.11000	394.14820	496.51610	100.40000	2.49673	889.70000	1052.10001	5.95792 2038.61000
.800	-2.115	879.65500	1341.23000	394.33450	496.48020	100.40000	2.49735	889.55980	1052.14000	5.99856 2038.61000
.800	-1.639	879.72800	1341.08000	394.17360	496.50810	100.40000	2.49676	889.62990	1052.20000	5.97180 2038.57500
.800	-1.172	879.54880	1340.91000	394.16970	496.49710	100.40000	2.49657	889.45000	1052.25999	5.94509 2038.61000
.800	-.707	879.83520	1340.67000	393.7940	496.56860	100.40000	2.49533	889.73000	1052.32001	5.93247 2038.61000
.800	-.240	879.84890	1341.12000	394.12130	496.52320	100.40000	2.49667	889.75000	1052.39000	5.90316 2038.57500
.800	.271	879.71870	1341.03999	394.15040	496.51070	100.40000	2.49666	889.61990	1052.44000	5.87633 2038.61000
.804	.804	879.98320	1340.89999	393.86690	496.56810	100.40000	2.49577	889.87790	1052.50000	5.78268 2038.61000
GRADIENT	.04107	-.00867	-.03434	.00756	-.00000	-.00010	.04057	.11747	-.03532	.00327

## PARAMETRIC DATA

	RUN NO.	1496/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	
.900	-7.048	753.10890	1273.39000	426.77510	481.25070	99.50000	2.50241	763.11990	979.03980	1.67228	2036.72000
.900	-6.537	752.76930	1273.17000	426.82590	481.12650	99.39999	2.50283	762.77980	979.07980	1.66827	2036.72000
.900	-6.041	752.92190	1273.08000	426.67360	481.16410	99.39999	2.50239	762.92990	979.11990	1.67268	2036.68500
.900	-5.549	752.62230	1272.89999	426.72830	481.12870	99.39999	2.50229	762.62990	979.15990	1.68586	2036.72000
.900	-5.050	752.75320	1272.91000	426.65720	481.32350	99.59999	2.50099	762.76000	979.21000	1.69018	2036.72000
.900	-4.558	752.90060	1273.17000	426.74800	481.40840	99.70000	2.50093	762.90990	979.24000	1.68550	2036.72000
.900	-4.063	752.30830	1273.00000	426.98340	481.40480	99.80000	2.50066	762.31980	979.26980	1.67279	2036.72000
.900	-3.572	752.56910	1273.09000	426.89010	481.44260	99.80000	2.50056	762.57980	979.30980	1.66409	2036.68500
.900	-3.081	752.48880	1273.06000	426.91720	481.51730	99.89999	2.50001	762.50000	979.35990	1.63865	2036.68500
.900	-2.598	752.70310	1272.86000	426.65260	481.57810	99.89999	2.49918	762.71000	979.39990	1.63049	2036.72000
.900	-2.120	752.9370	1273.00000	426.57590	481.61600	99.89999	2.49919	763.00000	979.45000	1.62193	2036.72000
.900	-1.646	752.72310	1272.87000	426.64750	481.75270	100.10000	2.49803	762.73000	979.48000	1.62210	2036.72000
.900	-1.179	752.82100	1273.08000	426.73340	481.57590	99.89999	2.49963	762.82980	979.51980	1.62601	2036.68500
.900	-7.715	752.50050	1272.96001	426.84180	481.61620	100.00000	2.49915	762.51000	979.54980	1.63878	2036.68500
.900	-2.252	752.80320	1272.91000	426.62720	481.67700	100.00000	2.49861	762.80980	979.57980	1.64730	2036.68500
.900	-258	752.83230	1272.99001	426.66500	481.75980	100.10000	2.49822	762.83980	979.63990	1.64296	2036.68500
.900	.790	752.89480	1272.85001	426.53150	481.87720	100.20000	2.49718	762.89990	979.68990	1.64314	2036.64999
	GRADIENT	.04689	-.03541	-.05222	.07707	.07516	-.00059	.04606	.08371	-.00634	-.00874

	RUN NO.	1479/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	
1.099	-7.023	565.08400	1205.78000	478.18900	450.53910	99.80000	2.49971	575.26980	917.01980	1.30621	2038.12000
1.100	-6.508	564.93190	1205.92000	478.33030	450.73100	100.10000	2.49835	575.11990	917.03980	1.29578	2038.12000
1.100	-6.010	564.81050	1206.02000	478.43680	450.61230	100.00000	2.49922	575.00000	917.06980	1.28208	2038.08501
1.100	-5.508	564.87990	1206.09000	478.45000	450.62060	100.00000	2.49935	575.06980	917.10990	1.23873	2038.12000
1.100	-5.015	564.84940	1206.14000	478.49120	450.68870	100.10000	2.49889	575.03980	917.12990	1.23541	2038.08501
1.100	-4.511	564.92940	1206.13000	478.45360	450.70800	100.10000	2.49883	575.11990	917.14990	1.22889	2038.08501
1.100	-4.020	564.88060	1206.03999	478.42040	451.27030	100.80000	2.49457	575.06980	917.48000	1.18736	2038.12000
1.100	-3.523	564.89970	1206.12000	478.45950	451.26590	100.80000	2.49475	575.08980	917.48000	1.19360	2038.08501
1.100	-3.028	564.93120	1205.99001	478.37130	451.28710	100.80000	2.49444	575.11990	917.51980	1.20008	2038.08501
1.100	-2.529	564.96390	1205.75999	478.22490	451.07740	100.50000	2.49564	575.14990	917.72000	1.14729	2037.91000
1.100	-2.044	565.14330	1205.85001	478.20610	451.10890	100.50000	2.49576	575.32980	917.73000	1.14416	2037.91000
1.100	-1.555	564.95390	1205.77000	478.23460	450.75200	100.10000	2.49799	575.13990	917.83980	1.07897	2037.84000
1.100	-1.069	565.06230	1205.91000	478.27290	450.76200	100.10000	2.49826	575.25000	917.84990	1.07884	2037.87500
1.100	-5.889	564.83790	1206.25999	478.56540	450.67330	100.10000	2.49917	575.02980	917.88990	1.07853	2037.87500
1.100	-1.115	565.09130	1206.00999	478.31980	450.75780	100.10000	2.49848	575.27980	917.86990	1.07587	2037.87500
1.100	.393	564.92040	1206.12000	478.41630	450.71340	100.10000	2.49867	575.10990	917.87990	1.07880	2037.87500
1.100	.911	564.99170	1205.96001	478.33010	450.65990	100.00000	2.49900	575.17990	917.87990	1.07880	2037.87500
	GRADIENT	.01444	-.00560	-.00897	-.12388	-.09586	-.00070	.01436	.11917	-.03087	-.05146

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM046) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1519/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATEM
1.250	-7.038	462.53370	1197.92000	505.80790	426.20430	99.70000	2.50168	472.65990	864.45000	1.36769 2035.88000
-6.525	462.69090	1198.24001	505.93550	426.21310	99.70000	2.50236	472.81980	864.46000	1.36733 2035.88000	
-6.031	462.70210	1198.08000	505.85210	426.15620	99.59999	2.50262	472.82980	864.46000	1.32157 2035.84500	
-5.532	462.72360	1197.83000	505.72050	426.18730	99.59999	2.50211	472.84990	864.46000	1.35706 2035.84500	
-5.034	462.64400	1197.81000	505.72780	426.16850	99.59999	2.50207	472.76980	864.43990	1.34997 2035.88000	
-4.540	462.46460	1197.81000	505.76710	426.12110	99.59999	2.50204	472.58980	864.42990	1.33937 2035.88000	
-4.046	462.47270	1198.10001	505.91240	426.09370	99.59999	2.50263	472.59990	864.43990	1.33202 2035.88000	
-3.558	462.60450	1197.75000	505.70610	426.08790	99.50000	2.50253	472.73000	864.43990	1.32542 2035.91499	
-3.068	462.55490	1197.71001	505.69650	426.07890	99.50000	2.50244	472.67990	864.41990	1.32197 2035.88000	
-2.578	462.47310	1198.02000	505.62000	426.02590	99.50000	2.50206	472.59990	864.41990	1.30434 2035.88000	
-2.091	462.76030	1198.30000	505.95070	426.14920	99.59999	2.50308	472.88990	864.40990	1.29376 2035.88000	
-1.615	462.95970	1198.34000	505.92720	426.19750	99.59999	2.50319	473.08980	864.41990	1.28352 2035.88000	
-1.143	462.68920	1198.49001	506.06250	426.11110	99.59999	2.50346	472.81980	864.39990	1.33158 2035.88000	
-0.675	462.43480	1197.78000	505.75830	426.11650	99.59999	2.50198	472.55980	864.38990	1.33588 2035.88000	
-2.208	462.41460	1197.82001	505.78320	426.18310	99.70000	2.50147	472.53980	864.40990	1.33584 2035.88000	
-1.250	462.71170	1198.14000	505.88040	426.22880	99.70000	2.50216	472.83980	864.38990	1.33548 2035.88000	
.305	462.66330	1197.91000	505.77440	426.31570	99.80000	2.50109	472.38980	864.39990	1.33574 2035.84500	
.836	GRADIENT	.02399	.02741	.00865	.03270	.03828	-.00017	.02422	-.00860	.00143 -.00464
RUN NO.	1535/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATEM
1.400	-7.035	381.81670	1214.58000	523.64890	402.03370	99.89999	2.49857	391.51980	880.18990	1.25634 2035.39000
1.400	-6.521	382.07930	1215.28999	523.95430	402.11770	100.00000	2.49947	391.78980	880.20000	1.25560 2035.42500
1.400	-6.028	381.76680	1214.66000	523.68510	402.08330	100.00000	2.49809	391.47000	880.20000	1.25294 2035.42500
1.400	-5.528	382.13840	1215.33000	523.97070	401.98780	99.80000	2.50077	391.84990	880.17990	1.25225 2035.39000
1.400	-5.029	381.56930	1214.58000	523.65410	401.88770	99.80000	2.49988	391.26980	880.15990	1.24972 2035.39000
1.400	-4.534	381.95970	1215.45000	524.02690	402.06640	100.00000	2.49967	391.66990	880.13990	1.25212 2035.39000
1.400	-4.047	381.80640	1214.62000	523.66670	401.95510	99.80000	2.49923	391.50980	880.14990	1.24638 2035.39000
1.400	-3.554	381.9050	1215.28999	523.95630	402.09080	100.00000	2.49940	391.70000	880.14990	1.24899 2035.39000
1.400	-3.057	381.92310	1214.96001	523.81320	402.10180	100.00000	2.49875	391.62990	880.11990	1.24933 2035.39000
1.400	-2.570	381.64750	1214.74001	523.72240	402.03980	100.00000	2.49815	391.34990	880.10990	1.24955 2035.39000
1.400	-2.084	381.9170	1215.07001	523.85990	401.96830	99.80000	2.50019	391.70000	880.09990	1.25252 2035.39000
1.400	-1.602	381.75710	1214.64000	523.67650	402.08200	100.00000	2.49804	391.46000	880.09990	1.25627 2035.39000
1.400	-1.134	382.03000	1215.25999	523.94210	402.10550	100.00000	2.49938	391.74000	880.04980	1.26896 2035.39000
1.400	-.660	382.05000	1215.21001	523.91990	402.04440	99.89999	2.49990	391.75980	880.04980	1.26901 2035.39000
1.400	-.191	381.84590	1214.64000	523.67480	402.18070	100.00000	2.49752	391.54980	880.04980	1.26626 2035.42500
1.399	.320	382.12960	1215.14000	523.88770	402.07500	99.89999	2.49983	391.83980	880.03980	1.25576 2035.39000
1.400	.847	381.70730	1214.64999	523.68190	401.99440	99.89999	2.49862	391.40990	880.02980	1.25295 2035.39000
GRADIENT	.0442	-.04574	-.02010	.00658	.00127	-.00009	-.00420	-.02473	-.00267	.001170

## PARAMETRIC DATA

	RUN NO.	1553/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.450	-7.050	358.83620	1225.74001	528.06740	394.92110	101.30000	2.49097	368.30980	893.55980	1.39747	2035.28500		
1.450	-6.544	359.04350	1225.71001	528.06540	394.98900	101.30000	2.49111	368.51980	893.55980	1.40483	2035.25000		
1.450	-6.052	358.81370	1226.25000	528.27830	394.93750	101.40000	2.49125	368.28980	893.57980	1.4054	2035.21500		
1.450	-5.558	358.75660	1225.89999	528.12990	394.88130	101.30000	2.49117	368.23000	893.59990	1.40461	2035.21500		
1.450	-5.064	359.17800	1226.37000	528.34690	394.97070	101.30000	2.49240	368.65990	893.59990	1.40407	2035.25000		
1.450	-4.572	358.77510	1226.12000	528.22240	394.93730	101.40000	2.49098	368.25000	893.63990	1.40069	2035.25000		
1.450	-4.076	358.84670	1225.63000	528.02220	395.00490	101.40000	2.49019	368.31980	893.62990	1.40860	2035.25000		
1.450	-3.587	358.69560	1226.23000	528.26390	394.90230	101.40000	2.49110	368.16990	893.64990	1.39691	2035.28500		
1.450	-3.103	358.94260	1226.12000	528.23100	394.99000	101.40000	2.49114	368.41990	893.65990	1.40069	2035.28500		
1.450	-2.622	359.01250	1225.99001	528.18040	395.02390	101.40000	2.49098	368.49000	893.64990	1.40451	2035.28500		
1.450	-2.142	358.85690	1225.53999	527.98540	395.01660	101.40000	2.49004	368.32980	893.64990	1.40502	2035.28500		
1.450	-1.677	359.00150	1226.19000	528.26290	395.00220	101.40000	2.49132	368.48000	893.65990	1.40428	2035.28500		
1.450	-1.213	358.91210	1226.28999	528.30000	394.96480	101.40000	2.49141	368.38990	893.68990	1.40416	2035.28500		
1.450	-0.759	358.90430	1225.92999	528.14990	394.92500	101.30000	2.49136	368.37990	893.66990	1.40458	2035.28500		
1.450	-0.304	358.90380	1226.03000	528.19170	394.91580	101.30000	2.49154	368.37790	893.68990	1.40814	2035.28500		
1.450	.206	358.62920	1225.73000	528.05270	394.85690	101.30000	2.49075	368.09900	893.67990	1.42328	2035.28500		
1.450	.745	358.75850	1225.50000	527.96360	394.84840	101.20000	2.49106	368.23000	893.67990	1.43474	2035.28500		
1.450	GRADIENT	-.00752	-.05005	-.02120	-.01996	-.03153	.00009	-.00788	.00984	.00445	.00510		
	RUN NO.	1637/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00					PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.469	-7.049	348.18700	1222.76405	526.13779	390.67110	100.90000	2.49396	357.52980	888.51000	1.39014	2032.48500		
1.470	-6.543	347.93120	1222.48917	526.11779	390.58620	100.90000	2.49374	357.26980	888.51000	1.39010	2032.52000		
1.469	-6.046	348.18850	1222.34576	526.02658	390.69680	100.90000	2.49347	357.52980	888.51980	1.39045	2032.45000		
1.470	-5.553	347.95810	1222.47928	525.91988	390.50830	100.90000	2.49283	356.92990	888.52980	1.39410	2032.41499		
1.470	-5.062	347.83400	1222.47928	525.99268	390.58060	100.90000	2.49315	357.16990	888.51980	1.39042	2032.45000		
1.470	-4.564	347.94140	1222.69684	526.09042	390.60230	100.90000	2.49351	357.27980	888.51980	1.38663	2032.45000		
1.469	-4.074	348.08980	1222.59557	526.06193	390.66060	100.90000	2.49346	357.42990	888.52980	1.38676	2032.41499		
1.469	-3.584	348.12040	1222.31465	525.94928	390.69040	100.90000	2.49311	357.46000	888.51000	1.39064	2032.41499		
1.470	-3.097	347.62700	1222.56429	526.01060	390.50420	100.90000	2.49312	356.96000	888.52980	1.39029	2032.34500		
1.470	-2.615	347.70650	1222.44463	525.96826	390.54790	100.90000	2.49286	357.03980	888.53980	1.38689	2032.34500		
1.470	-2.134	348.24710	1222.56448	526.06089	390.70950	100.90000	2.49366	357.58980	888.51980	1.39037	2032.34500		
1.469	-1.666	348.15800	1222.74083	526.12596	390.66990	100.90000	2.49377	357.50000	888.51980	1.38660	2032.34500		
1.469	-1.202	347.85300	1223.29147	526.32561	390.57400	100.90000	2.49341	357.18990	888.51000	1.35433	2032.34500		
1.470	-1.470	348.11870	1222.78490	526.14073	390.65920	100.90000	2.49369	357.46000	888.52980	1.38300	2032.34500		
1.469	-1.744	347.99120	1222.66245	526.08085	390.69800	101.00000	2.49277	357.32980	888.52980	1.38313	2032.34500		
1.470	-1.283	347.75490	1222.75215	526.09814	390.61740	101.00000	2.49261	357.08980	888.51000	1.37946	2032.31000		
1.470	.766	348.19730	1222.97888	526.22602	390.74950	101.00000	2.49327	357.53980	888.51000	1.37573	2032.31000		
1.469	GRADIENT	.01266	.07852	.03303	.01535	.01968	-.00006	.01297	-.00178	-.00274	-.02186		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM046) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1588/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.500	PHI =	180.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.492	-7.051	337.75120	1225.61597	526.28029	386.12480	100.20000	2.49965	346.95000	896.85990	1.59810 2033.67500
1.492	-6.544	337.64280	1225.66650	526.28803	386.08400	100.20000	2.49963	346.83980	896.87990	1.59803 2033.67500
1.492	-6.047	337.77050	1225.69649	526.31441	386.12380	100.20000	2.49981	346.97000	896.86990	1.59801 2033.64000
1.492	-5.549	337.64210	1225.81442	526.34685	386.07060	100.20000	2.49988	346.83980	896.86990	1.59783 2033.64000
1.492	-5.053	337.66460	1224.99956	526.02538	386.13380	100.20000	2.49884	346.85990	896.88990	1.61109 2033.64000
1.492	-4.560	337.39110	1224.46254	525.78074	386.07910	100.20000	2.49786	346.57980	896.86990	1.61194 2033.64000
1.491	-4.069	337.50500	1223.93475	525.58853	386.17410	100.20000	2.49723	346.74000	896.88990	1.62476 2033.67500
1.492	-3.579	337.20830	1223.59897	525.41637	386.16500	100.30000	2.49558	346.38990	896.88990	1.62107 2033.67500
1.492	-3.091	337.02370	1223.37108	525.30386	386.14750	100.30000	2.49455	346.20000	896.86990	1.60503 2033.67500
1.492	-2.605	337.02560	1223.08609	525.18530	386.18530	100.30000	2.49384	346.00000	896.85990	1.59730 2033.64000
1.492	-2.127	336.92920	1222.44955	524.92666	386.19310	100.30000	2.49298	346.09990	896.86990	1.61030 2033.64000
1.492	-1.658	336.79420	1222.21930	524.81931	386.19800	100.30000	2.49189	345.96000	896.84990	1.59033 2033.67500
1.492	-1.189	337.18040	1223.68600	525.44701	386.18900	100.30000	2.49492	346.35990	896.83980	1.59249 2033.67500
1.492	-0.729	337.47120	1224.69168	525.88064	386.20090	100.30000	2.49684	346.65990	896.86990	1.58718 2033.67500
1.492	-0.270	337.53980	1224.63297	525.86401	386.22340	100.30000	2.49692	346.73000	896.85990	1.59129 2033.67500
1.491	.244	337.75460	1224.72226	525.92411	386.26980	100.30000	2.49763	346.95000	896.86990	1.60333 2033.67500
1.492	.780	337.46000	1224.66353	525.86812	386.17070	100.30000	2.49734	346.64990	896.85990	1.60744 2033.67500
GRADIENT	.05347	.05347	.05347	.07638	.01857	.01463	.00015	.05488	-.00426	-.000370
	RUN NO.	1604/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.515	-7.051	327.02220	1226.72649	525.32271	382.48120	100.80000	2.49275	336.03980	905.50000	1.83219 2033.81500
1.515	-6.539	327.12960	1226.67181	525.32278	382.51100	100.80000	2.49301	336.14990	905.51000	1.84147 2033.78000
1.514	-6.041	327.34570	1226.61772	525.33392	382.59010	100.80000	2.49314	336.36990	905.51980	1.84159 2033.74500
1.514	-5.548	327.39480	1225.95786	525.08730	382.61080	100.80000	2.49312	336.41990	905.52980	1.88446 2033.78000
1.514	-5.057	327.29660	1226.62207	525.32285	382.57280	100.80000	2.49310	336.31980	905.51980	1.84158 2033.78000
1.514	-4.559	327.08010	1226.66802	525.08378	382.48020	100.80000	2.49321	336.09990	905.52980	1.89366 2033.78000
1.514	-4.069	327.21780	1225.96596	525.06440	382.60520	100.90000	2.49259	336.24000	905.53980	1.89384 2033.74500
1.514	-3.577	327.19850	1225.88551	525.03075	382.60570	100.90000	2.49243	336.22000	905.53980	1.89396 2033.74500
1.513	-3.091	327.44410	1225.51553	524.92411	382.69820	100.90000	2.49254	336.47000	905.55980	1.91355 2033.78000
1.515	-2.608	326.98290	1226.26590	525.14513	382.53440	100.90000	2.49214	336.00000	905.53980	1.86521 2033.81500
1.514	-2.126	327.17920	1225.45573	524.86192	382.60620	100.90000	2.49227	336.20000	905.55980	1.91837 2033.74500
1.514	-1.656	327.08280	1225.07574	524.69946	382.61350	100.90000	2.49140	336.09990	905.56980	1.91418 2033.71001
1.514	-1.192	327.17020	1225.26889	524.78854	382.61990	100.90000	2.49194	336.18990	905.55980	1.91866 2033.71001
1.514	-7.731	327.12060	1225.45113	524.85165	382.59280	100.90000	2.49208	336.13990	905.55980	1.91359 2033.74500
1.514	-2.269	327.20950	1225.37468	524.83441	382.63650	100.90000	2.49193	336.23000	905.55980	1.90897 2033.78000
1.514	.244	327.15110	1225.33052	524.80849	382.62670	100.90000	2.49167	336.16990	905.56980	1.90428 2033.78000
1.514	.777	327.03370	1225.33858	524.79355	382.59180	100.90000	2.49143	336.04980	905.57980	1.89951 2033.78000
GRADIENT	-.01608	-.015312	-.015312	-.016171	.01000	.00806	-.00026	-.01687	.00752	.00020

PARAMETRIC DATA

RUN No. 16119/0 BN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM047) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1573/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	PARAMETRIC DATA			
						BETA =	-1.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.601	-7.040	1251.79900	1597.50999	316.15600	522.37520	100.40000	2.49938	1261.57001	1304.03000
.600	-6.534	1252.03999	1596.62000	315.21000	522.39380	100.30000	2.49577	1261.78999	1304.03999
.600	-6.039	1252.00000	1597.10001	315.64620	522.34420	100.30000	2.49776	1261.75999	1304.06000
.601	-5.542	1251.13000	1596.89999	316.19090	522.25930	100.30000	2.49956	1260.89999	1304.06000
.600	-5.046	1252.18500	1596.95000	315.36790	522.38040	100.30000	2.49662	1261.94000	1304.08000
.601	-4.554	1250.89500	1596.49001	316.03960	522.36280	100.40000	2.49810	1260.66000	1304.10001
.600	-4.061	1252.19400	1597.52000	315.83980	522.42140	100.40000	2.49825	1261.96001	1304.12000
.600	-3.565	1251.29300	1596.38000	315.62060	522.32740	100.30000	2.49705	1261.05000	1304.14000
.601	-3.079	1251.21500	1597.22000	316.39040	522.23950	100.30000	2.50000	1260.99001	1304.16000
.600	-2.593	1252.47000	1596.92000	315.11799	522.50950	100.40000	2.49513	1262.22000	1304.17000
.600	-2.111	1251.77800	1596.50999	315.33200	522.46630	100.40000	2.49555	1261.53000	1304.21001
.600	-1.635	1251.54800	1596.85001	315.80660	522.31370	100.30000	2.49813	1261.31000	1304.24001
.601	-1.184	1250.90700	1596.34000	315.90280	522.28490	100.30000	2.49804	1260.67000	1304.25999
.600	-1.750	1251.76601	1597.11000	315.84670	522.40870	100.40000	2.49793	1261.53000	1304.30000
.601	-.330	1251.68300	1597.16000	315.95560	522.39400	100.40000	2.49836	1261.45000	1304.33000
.600	.229	1251.96100	1597.00000	315.59400	522.44210	100.40000	2.49692	1261.72000	1304.35001
.600	.751	1251.93300	1597.35001	315.91090	522.40620	100.40000	2.49836	1261.70000	1304.37000
GRADIENT	.07357	.06000	-.00991	.00842	.00568	-.00002	.07368	.05409	.00188
RUN NO.	1463/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	RN/L	PC	PREF	SH10+3 PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.800	-7.034	879.88090	1340.99001	394.00320	496.54200	100.40000	2.49622	889.77980	1052.74001
.800	-6.520	879.63700	1341.11000	394.25810	496.49000	100.40000	2.49702	889.53980	1052.82001
.800	-6.027	879.85060	1341.00999	394.03880	496.53520	100.40000	2.49634	889.75000	1052.87000
.800	-5.527	879.58760	1341.02000	394.22490	496.58030	100.50000	2.49626	889.49000	1052.92999
.800	-5.033	879.80250	1340.85001	393.95310	496.63310	100.50000	2.49536	889.70000	1052.99001
.800	-4.537	879.74610	1341.22000	394.26490	496.58470	100.50000	2.49658	889.64990	1053.06000
.800	-4.040	879.72750	1341.11000	394.19630	496.59330	100.50000	2.49620	889.62990	1053.12000
.800	-3.545	879.75000	1340.97000	394.07740	496.61180	100.50000	2.49582	889.64990	1053.16000
.800	-3.053	879.64840	1341.00999	394.17600	496.59110	100.50000	2.49612	889.54980	1053.21001
.800	-2.562	879.65750	1341.07001	394.21410	496.58620	100.50000	2.49629	889.55980	1053.27000
.800	-2.078	879.66920	1340.96001	394.12480	496.59990	100.50000	2.49593	889.56980	1053.30000
.800	-1.602	879.50630	1341.03000	394.28740	496.56620	100.50000	2.49643	889.40990	1053.35001
.800	-1.135	879.57640	1341.08000	394.27660	496.57230	100.50000	2.49646	889.48000	1053.41000
.800	-.689	879.66890	1340.98000	394.13960	496.59770	100.50000	2.49599	889.56980	1053.44000
.800	-.253	879.88160	1340.94000	393.96560	496.63620	100.50000	2.49550	889.77980	1053.52000
.800	.258	879.85110	1340.97000	394.00880	496.62820	100.50000	2.49564	889.75000	1053.57001
.800	.818	879.80910	1341.07001	394.11130	496.61080	100.50000	2.49602	889.71000	1053.60001
GRADIENT	.01699	-.02301	-.02857	.00520	.00000	-.00010	.01648	.10287	-.00894

## PARAMETRIC DATA

RUN NO.	1497/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PADM
MACH									
.900	-7.028	753.00680	1273.50000	426.91160	481.99460	100.40000	2.49766	763.01980	979.83980
.900	-6.518	753.04390	1272.99001	426.53880	482.05660	100.40000	2.49621	763.04980	979.88990
.901	-6.023	752.31400	1273.32001	427.20000	481.88750	100.40000	2.49807	762.32980	979.92990
.900	-5.527	752.63110	1272.98000	426.77780	481.98220	100.40000	2.49672	762.63990	979.95000
.900	-5.031	752.80520	1272.78000	426.53690	482.12180	100.50000	2.49537	762.80980	979.97000
.900	-4.534	752.56910	1273.06000	426.86940	482.04830	100.50000	2.49645	762.57980	980.01980
.900	-4.040	752.57030	1273.00000	426.82760	482.14110	100.60000	2.49571	762.57980	980.03980
.900	-3.545	752.44140	1272.85001	426.80130	482.13380	100.60000	2.49546	762.45000	980.07980
.900	-3.052	752.65260	1272.89000	426.70340	482.16800	100.60000	2.49530	762.65990	980.11990
.900	-2.564	752.70070	1273.03000	426.77080	482.07570	100.50000	2.49619	762.71000	980.13990
.900	-2.081	752.80250	1272.96001	426.66190	482.10180	100.50000	2.49587	762.80980	980.15990
.900	-1.604	752.92410	1272.91000	426.55520	482.04350	100.40000	2.49615	762.92990	980.20000
.900	-1.142	752.70200	1273.08000	426.79370	481.90160	100.30000	2.49746	762.73000	980.22000
.900	-697	752.82250	1272.96001	426.65010	481.84720	100.20000	2.49757	762.82980	980.24000
.900	-264	752.70000	1273.08000	426.80570	481.63990	100.00000	2.49921	762.71000	980.25980
.900	.295	752.80180	1273.00999	426.69680	481.57980	99.89999	2.49946	762.80980	980.29980
.900	.811	752.83180	1273.03000	426.69290	481.66940	100.00000	2.49890	762.83980	980.32980
GRADIENT	.05728	.01293	-.02515	-.10752	-.13548	.00074	.05703	.05751	-.01320 -.00940

RUN NO.	1480/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PADM
MACH									
1.100	-7.018	564.93020	1206.07001	478.41820	450.63430	100.00000	2.49928	575.11990	917.98000
1.100	-6.500	564.82230	1205.88000	478.35060	450.62390	100.00000	2.49889	575.01000	918.01980
1.100	-6.007	564.79220	1205.85001	478.34470	450.62620	100.00000	2.49884	574.98000	918.01000
1.100	-5.504	564.79050	1206.00999	478.43870	450.76980	100.20000	2.49804	574.98000	918.01000
1.100	-5.009	564.82320	1205.77000	478.28610	450.80270	100.20000	2.49747	575.01000	918.01980
1.100	-4.502	564.93160	1205.95000	478.34790	450.56670	99.89999	2.49958	575.11990	918.04980
1.100	-4.011	565.01050	1206.09000	478.39820	450.56980	99.89999	2.49987	575.20000	918.04980
1.100	-3.512	564.79150	1205.92999	478.39180	450.61740	100.00000	2.49902	574.98000	918.05980
1.100	-3.012	565.15190	1205.99001	478.28420	450.69310	100.00000	2.49899	575.33980	918.06980
1.100	-2.518	564.96240	1205.88000	478.29520	450.66190	100.00000	2.49883	575.14990	918.08980
1.100	-2.028	564.69020	1206.02000	478.48410	450.58470	100.00000	2.49927	574.87990	918.08980
1.100	-1.542	564.96090	1206.00999	478.37130	450.64750	100.00000	2.49913	575.14990	918.09990
1.100	-1.059	565.01390	1205.75000	478.19900	450.68750	100.00000	2.49850	575.20000	918.09990
1.100	-5.88	565.16110	1206.05000	478.31540	450.68900	100.00000	2.49912	575.34990	918.09990
1.100	-1.136	564.96950	1206.13000	478.43770	450.63670	100.00000	2.49940	575.15990	918.10990
1.100	-432	565.02030	1206.09000	478.39430	450.65260	100.00000	2.49928	575.21000	918.12990
1.100	.927	564.83110	1205.97000	478.39920	450.62230	100.00000	2.49909	575.01980	918.15990
GRADIENT	.00475	.01056	.00424	.01149	.01430	-.00006	.00488	.01765	-.00475 -.00397

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM047) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1520/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.250	-7.027	462.74950	1198.42999	506.01900	426.28540	99.80000	2.50216	472.87990	864.38990	1.32815 2035.84500
-6.514	462.49410	1197.88000	505.79610	426.27420	99.80000	2.50101	472.61990	864.39990	1.32876 2035.84500	
-6.016	462.19850	1197.32001	505.57710	426.25320	99.80000	2.49983	472.31980	864.38990	1.32589 2035.84500	
-5.518	462.69850	1198.60001	506.11620	426.25490	99.80000	2.50250	472.82980	864.40990	1.32447 2035.81000	
-5.019	462.50170	1198.22000	505.96660	426.24170	99.80000	2.50170	472.62990	864.39990	1.32489 2035.84500	
-4.525	462.51440	1197.82001	505.76120	426.28560	99.80000	2.50089	472.63990	864.38990	1.31838 2035.81000	
-4.029	462.61470	1197.73000	505.69380	426.39750	99.89999	2.50013	472.74000	864.38990	1.28079 2035.81000	
-3.531	462.56350	1197.92000	505.80130	426.36450	99.89999	2.50051	472.68990	864.39990	1.26045 2035.77499	
-3.040	462.74270	1197.99001	505.79760	426.40450	99.89999	2.50068	472.86990	864.38990	1.25042 2035.77499	
-2.551	462.58370	1197.85001	505.76120	426.45340	100.00000	2.49978	472.71000	864.41990	1.24729 2035.77499	
-2.063	462.68380	1197.83000	505.72920	426.32910	99.80000	2.50093	472.80980	864.40990	1.25340 2035.81000	
-1.582	462.69040	1198.31000	505.97090	426.43460	100.00000	2.50073	472.81980	864.39990	1.25336 2035.81000	
-1.113	462.74020	1198.35001	505.98050	426.44360	100.00000	2.50082	472.86990	864.39990	1.25397 2035.77499	
-660	462.51460	1197.77000	505.73580	426.51930	100.10000	2.49902	472.63990	864.39990	1.26054 2035.77499	
-222	462.67360	1197.84000	505.73660	426.40160	99.89999	2.50036	472.79980	864.38990	1.27012 2035.77499	
1.250	.291	462.75050	1198.25999	505.93260	426.37920	99.89999	2.50123	472.87990	864.37990	1.28047 2035.77499
1.250	.848	462.76220	1198.03000	505.81350	426.48190	100.00000	2.50017	472.87990	864.37990	1.27012 2035.77499
GRADIENT	.02968	.05422	.02098	.02123	.02487	-.00003	.03014	-.000207	-.00340	-.000433
	RUN NO.	1536/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.400	-7.024	381.78760	1214.46001	523.59720	402.03640	99.89999	2.49833	391.49000	879.95000	1.25646 2035.35500
1.400	-6.511	381.92070	1215.37000	523.99270	402.13400	100.10000	2.49890	391.62990	879.95000	1.24890 2035.35500
1.400	-6.014	381.76710	1214.58000	523.65010	402.16260	100.10000	2.49735	391.47000	879.95000	1.26632 2035.39000
1.400	-5.515	382.02030	1215.23000	523.92920	402.17720	100.10000	2.49872	391.73000	879.95000	1.26565 2035.39000
1.400	-5.021	381.87480	1214.75999	523.72680	402.03420	99.89999	2.49894	391.57980	879.93990	1.26948 2035.39000
1.400	-4.522	382.05960	1215.28999	523.95480	402.03980	99.89999	2.49905	391.76980	879.91990	1.26893 2035.39000
1.400	-4.027	381.80470	1214.52999	523.80250	401.99710	99.89999	2.49920	391.50980	879.91990	1.27988 2035.39000
1.400	-3.528	381.60960	1214.46001	523.60080	401.98290	99.89999	2.49820	391.30980	879.89990	1.24590 2035.39000
1.400	-3.032	381.93210	1215.09000	523.86990	402.02030	99.89999	2.49959	391.63990	879.87990	1.24609 2035.39000
1.400	-2.542	381.90380	1214.89999	523.78740	402.17330	100.10000	2.49803	391.60990	879.87990	1.24592 2035.39000
1.400	-2.054	382.11040	1215.07001	523.85740	402.21950	100.10000	2.49850	391.81980	879.86990	1.24603 2035.39000
1.400	-1.576	382.04170	1214.96001	523.81080	402.06570	99.89999	2.49943	391.75000	879.83980	1.24956 2035.39000
1.400	-1.106	381.78610	1214.73000	523.71530	402.15410	100.10000	2.49764	391.49000	879.83980	1.24942 2035.39000
1.400	-6.49	381.86430	1214.87000	523.77490	402.02080	99.89999	2.49914	391.56980	879.81980	1.24899 2035.39000
1.400	-2.203	382.15840	1215.28999	523.95260	402.06960	99.89999	2.50012	391.86990	879.80980	1.24677 2035.39000
1.400	.308	381.66040	1214.24001	523.50340	402.16260	100.10000	2.49665	391.35990	879.79980	1.24575 2035.39000
1.400	.860	381.93120	1215.23000	523.93120	402.00680	99.89999	2.49984	391.63990	879.79980	1.24575 2035.39000
GRADIENT	.00264	.01990	-.00879	.01113	-.01176	-.00010	-.00261	-.002520	-.000492	-.00008

## PARAMETRIC DATA

RUN NO. 1554/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.449	-7.037	359.44240	1226.70000	528.49760	394.88260	101.10000	2.49441	368.92990	893.68990
1.450	-6.525	358.86740	1225.42000	527.93600	394.81960	101.10000	2.49162	368.33980	893.68990
1.450	-6.029	358.97900	1226.69000	528.46970	394.66750	101.00000	2.49455	368.46000	893.71000
1.450	-5.532	358.91380	1225.99001	528.17550	394.71140	101.00000	2.49326	368.38990	893.70000
1.450	-5.035	359.05930	1226.42999	528.36570	394.71660	101.00000	2.49417	368.53980	893.71000
1.450	-4.542	358.98340	1225.87000	528.12890	394.74410	101.00000	2.49311	368.46000	893.71000
1.450	-4.048	358.96360	1225.89000	528.13650	394.73630	101.00000	2.49313	368.43990	893.73000
1.450	-3.554	359.24490	1226.75000	528.50830	394.67500	100.90000	2.49550	368.73000	893.73000
1.451	-3.066	358.16500	1225.95000	528.11960	394.40920	100.90000	2.49307	367.62990	893.73000
1.449	-2.580	359.07570	1225.19000	527.85080	394.76540	100.90000	2.49260	368.54980	893.71000
1.450	-2.099	358.97920	1226.67000	528.46140	394.52860	100.80000	2.49570	368.46000	893.72000
1.450	-1.622	358.73020	1225.28000	527.87080	394.57810	100.80000	2.49303	368.20000	893.72000
1.450	-1.166	358.92110	1226.50000	528.38790	394.52590	100.80000	2.49535	368.39990	893.73000
1.450	-735	358.96240	1226.10001	528.22360	394.57570	100.80000	2.49469	368.43990	893.72000
1.450	-314	358.73710	1225.86000	528.11230	394.52690	100.80000	2.49405	368.21000	893.70000
1.449	.246	359.42720	1225.83000	528.13480	394.74660	100.80000	2.49465	368.90990	893.73000
1.450	.770	358.92360	1226.02000	528.18820	394.57080	100.80000	2.49451	368.39990	893.71000
GRADIENT	.02372	- .01342	- .00436	- .00436	- .01984	- .04052	.00024	.02397	-.00144

RUN NO. 1638/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.470	-7.033	347.95310	1222.73091	526.10627	390.64040	100.90000	2.49286	357.28980	888.52980
1.471	-6.526	347.57590	1223.61929	526.45140	390.45140	100.90000	2.49376	356.90990	888.51000
1.470	-6.029	347.88210	1223.40251	526.37399	390.64310	101.00000	2.49304	357.22000	888.51000
1.471	-5.533	347.65670	1223.15964	526.25637	390.52100	100.90000	2.49302	356.99000	888.53980
1.470	-5.035	348.01250	1222.91940	526.18802	390.66140	100.90000	2.49289	357.34990	888.51000
1.470	-4.542	347.73580	1223.13770	526.25440	390.55540	100.90000	2.49293	357.06980	888.52980
1.470	-4.043	347.99170	1223.31192	526.34612	390.63650	100.90000	2.49321	357.32980	888.51980
1.469	-3.552	348.38400	1223.60609	526.49773	390.73970	100.90000	2.49406	357.73000	888.51000
1.470	-3.065	347.92290	1223.32286	526.34517	390.61250	100.90000	2.49318	357.25000	888.51000
1.470	-2.573	347.83520	1223.17241	526.27636	390.60350	100.90000	2.49272	357.16990	888.51000
1.470	-2.095	348.01030	1223.56857	526.45245	390.61890	100.90000	2.49368	357.34990	888.51000
1.470	-1.621	347.96190	1223.37662	526.37075	390.62060	100.90000	2.49330	357.29980	888.51980
1.471	-1.158	347.76420	1223.62262	526.45449	390.53810	100.90000	2.49346	357.09990	888.51980
1.470	-7.19	347.91360	1223.25079	526.31480	390.69190	101.00000	2.49233	357.25000	888.51000
1.470	-2.93	348.10990	1223.42255	526.40092	390.67160	100.90000	2.49339	357.45000	888.51000
1.471	.215	347.64700	1223.16812	526.25906	390.51680	100.90000	2.49302	356.98000	888.51000
1.484	.782	348.02930	1248.92120	536.85925	390.61130	100.90000	2.49396	357.36990	888.51000
GRADIENT	-.01517	2.11106	.86512	-.00546	.00360	.00002	-.01527	-.00199	-.11090

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM047) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1589/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
1.492	337.71580	1224.66577	525.89745	386.33670	100.40000	2.49678	346.90990	896.84990	1.59934	2033.67500	
-7.036	337.62870	1224.52179	525.82961	386.33230	100.40000	2.49622	346.81980	896.86990	1.59144	2033.67500	
1.492	-6.524	337.64670	1224.64867	525.88371	386.30350	100.40000	2.49691	346.83980	896.85990	1.60748	2033.67500
-6.022	337.64670	1224.64867	525.88371	386.21850	100.40000	2.49799	346.76980	896.85990	1.59830	2033.67500	
1.492	-5.531	337.57500	1225.45377	526.19587	386.23360	100.40000	2.49742	346.73000	896.85990	1.59870	2033.64000
-5.033	337.53710	1225.14484	526.06869	386.30180	100.40000	2.49708	346.85990	896.85990	1.59907	2033.64000	
1.492	-4.534	337.66600	1224.86896	525.97291	386.18460	100.40000	2.49648	346.47000	896.85990	1.58274	2033.67500
-4.045	337.28340	1225.00645	525.98385	386.20610	100.40000	2.49566	346.40990	896.84990	1.58741	2033.67500	
1.493	-3.550	337.22630	1224.19399	525.77349	386.24000	100.40000	2.49652	346.61990	896.83980	1.60343	2033.67500
1.492	-3.056	337.43090	1224.61755	525.91694	386.30270	100.40000	2.49670	346.80980	896.85990	1.59519	2033.67500
1.492	-2.573	337.61770	1224.74242	525.98164	386.24630	100.40000	2.49668	346.65990	896.84990	1.58685	2033.64000
1.492	-2.086	337.47000	1224.94804	525.98164	386.29370	100.40000	2.49687	346.80980	896.86990	1.58683	2033.67500
1.492	-1.615	337.61720	1224.97008	526.00746	386.19630	100.40000	2.49691	346.55980	896.84990	1.59895	2033.67500
-1.149	337.37110	1224.94403	525.96932	386.27320	100.40000	2.49718	346.79980	896.85990	1.60308	2033.67500	
1.492	-7.711	337.60640	1224.89812	525.97815	386.21920	100.40000	2.49719	346.65990	896.82980	1.60295	2033.71001
1.492	-2.278	337.46870	1224.98576	525.99720	386.24760	100.40000	2.49709	346.72000	896.83980	1.60723	2033.71001
1.492	.231	337.52810	1224.82684	525.94102	386.26100	100.40000	2.49720	346.76980	896.83980	1.59478	2033.74500
1.492	.796	337.57690	1225.05492	526.03687	.00086	- .00000	.00016	.02432	-.000327	.00209	.01281
GRADIENT	.02355	.04318	.01996								

RUN NO. 1605/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
1.514	327.17140	1225.99319	525.06602	382.64840	100.90000	2.49141	336.18990	905.56980	1.84712	2033.74500	
-6.523	327.01170	1226.52254	525.25588	382.53200	100.90000	2.49241	336.02980	905.58980	1.85550	2033.78000	
1.514	-6.027	327.54610	1227.51984	525.71650	382.60330	100.90000	2.49512	336.57980	905.58980	1.87270	2033.74500
-5.530	328.02150	1228.28633	526.08708	382.64790	100.90000	2.49789	337.06980	905.59990	1.90929	2033.74500	
-5.033	327.80620	1228.48341	526.13043	382.58150	100.90000	2.49752	336.84990	905.62990	1.89002	2033.74500	
1.514	-4.538	327.38500	1225.71909	524.99314	382.67850	100.90000	2.49246	336.40990	905.62990	1.89898	2033.74500
1.514	-4.044	327.31590	1225.83896	525.02917	382.64400	100.90000	2.49259	336.33980	905.62990	1.88978	2033.78000
1.514	-3.554	327.13890	1225.99516	525.06438	382.56910	100.90000	2.49267	336.15990	905.64990	1.89850	2033.81500
1.515	-3.060	327.07760	1226.63290	525.30386	382.49070	100.90000	2.49369	336.09990	905.63990	1.89750	2033.74500
1.514	-2.573	327.43970	1226.77095	525.41053	382.60300	100.90000	2.49432	336.47000	905.62990	1.89734	2033.78000
1.514	-2.084	327.56670	1227.04996	525.53745	382.62770	100.90000	2.49481	336.59990	905.63990	1.89221	2033.78000
1.514	-1.614	327.50630	1227.41560	525.67033	382.58060	100.90000	2.49525	336.52980	905.62990	1.88692	2033.78000
1.514	-1.153	327.92550	1227.79854	525.88228	382.73340	101.00000	2.49624	336.97000	905.62990	1.90529	2033.81500
1.514	-7.709	328.03250	1228.59003	526.20329	382.68070	100.90000	2.49736	337.07980	905.63990	1.86648	2033.81500
1.514	-2.281	328.00340	1229.00558	526.35867	382.67630	100.90000	2.49722	337.04980	905.62990	1.83350	2033.78000
1.514	.232	327.93290	1228.93039	526.32199	382.60960	100.90000	2.49795	336.98000	905.63990	1.87060	2033.78000
1.515	.799	327.69680	1229.10925	526.35603	382.58080	101.00000	2.49740	336.74000	905.60990	1.87028	2033.78000
GRADIENT	.15376	.72555	.30440	.00449	.00449	.00116	.00116	.0015927	-.000210	.00837	.00425

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 970  
(VCM047) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1620/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup>
ALPHA	317.15620	1235.13313	526.87756	378.86450	101.20000	2.48785	325.99000	908.01980	1.57437 2033.57001
-7.035	317.15620	1235.44617	526.95258	378.75810	101.20000	2.48802	325.75000	907.99000	1.56992 2033.53500
-6.523	316.92070	1235.35296	527.35296	378.85940	101.20000	2.48984	326.24000	907.98000	1.56498 2033.57001
-6.027	317.39750	1236.26802	527.74404	378.87920	101.20000	2.49167	326.52980	907.99000	1.56388 2033.53500
-5.530	317.67820	1237.16193	527.99182	378.89970	101.20000	2.49273	326.72000	907.98000	1.55923 2033.53500
-5.038	317.86250	1237.72461	527.82177	378.92480	101.20000	2.49395	326.67990	907.98000	1.55978 2033.53500
-4.534	317.82500	1237.29382	527.46012	378.88650	101.20000	2.49025	326.35990	907.95000	1.56075 2033.53500
-4.040	317.51440	1236.49178	527.47498	378.82740	101.20000	2.48991	326.16990	907.93990	1.55678 2033.53500
-3.549	317.32890	1236.04239	528.05828	378.78100	101.20000	2.49274	326.42990	907.93990	1.55087 2033.57001
-3.056	317.57790	1238.04239	527.34173	378.86690	101.20000	2.48947	326.21000	907.90990	1.55313 2033.57001
-2.574	317.36910	1236.25192	526.96842	378.83370	101.20000	2.48729	325.83980	907.87990	1.53839 2033.57001
-2.090	317.01050	1235.44113	528.35316	378.85910	101.20000	2.49363	326.74000	907.86990	1.53056 2033.57001
-1.614	317.88010	1236.66928	527.35268	378.86650	101.20000	2.48858	326.08980	907.84990	1.51788 2033.53500
-1.149	317.25290	1236.33588	528.55827	378.80080	101.20000	2.49382	326.61990	907.82980	1.50278 2033.53500
1.542	-7.10	317.76200	1239.26831	527.87594	378.84160	101.20000	2.49078	326.31980	907.81980 1.50862 2033.53500
1.541	-2.280	317.47410	1237.60898	528.39619	378.86400	101.30000	2.49247	326.50980	907.80980 1.50322 2033.53500
1.542	.231	317.65580	1238.89453	528.81942	378.89400	101.30000	2.49455	326.85990	907.80980 1.50594 2033.57001
1.541	.796	317.99460	1239.84430	.49200	-.00233	.01471	.00047	-.04292	-.03452 .01315 .00096

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM048) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1574/0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	- .500	PHI =	= 180.000
MACH	ALPHA	P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.600	-7.023	1252.12900	1596.73000	315.22900	522.48750	100.40000	2.49536	1261.88000	1304.41000	.98071	2034.79500
.599	-6.514	1252.53700	1596.64000	314.81880	522.54440	100.40000	2.49380	1262.28000	1304.42999	.98594	2034.79500
.599	-6.011	1252.73100	1597.10001	315.04640	522.52470	100.40000	2.49501	1262.48000	1304.46001	.98826	2034.75999
.600	-5.513	1251.70500	1596.12000	315.06470	522.49390	100.40000	2.49425	1261.45000	1304.50000	.99147	2034.72501
.601	-5.021	1251.65900	1597.35001	316.13550	522.37350	100.40000	2.49917	1261.42999	1304.48000	1.00911	2034.75999
.600	-4.523	1252.05200	1597.00000	315.51900	522.45310	100.40000	2.49664	1261.81000	1304.50999	.99615	2034.75999
.600	-4.026	1251.54500	1596.97000	315.90970	522.39550	100.40000	2.49804	1261.31000	1304.52000	1.00405	2034.79500
.600	-3.528	1251.61000	1596.75999	315.67970	522.42290	100.40000	2.49702	1261.37000	1304.53999	.99892	2034.83000
.600	-3.030	1251.32500	1596.32001	315.54420	522.42990	100.40000	2.49616	1261.08000	1304.57001	.98874	2034.72501
.601	-2.537	1251.68700	1597.47000	316.21340	522.36570	100.40000	2.49956	1261.46001	1304.57001	.98543	2034.75999
.600	-2.049	1251.42000	1596.14999	315.32350	522.45700	100.40000	2.49521	1261.17000	1304.59000	.98365	2034.75999
.601	-1.561	1251.06900	1596.89000	316.23240	522.34620	100.40000	2.49913	1260.84000	1304.62000	.98579	2034.79500
.601	-1.088	1251.65700	1597.44000	316.21260	522.36470	100.40000	2.49953	1261.42999	1304.64000	.98545	2034.79500
.600	-654	1251.92599	1597.25000	315.83330	522.41460	100.40000	2.49799	1261.69000	1304.67000	.98297	2034.75999
.600	-.310	1251.60699	1596.15000	315.84250	522.40450	100.40000	2.49777	1261.37000	1304.69000	.98575	2034.75999
.601	.248	1251.49500	1596.92999	315.91700	522.39330	100.40000	2.49803	1261.25999	1304.72000	.99097	2034.75999
.601	.828	1251.71899	1597.88000	316.53150	522.33110	100.40000	2.50106	1261.50000	1304.75000	.99298	2034.72501
GRADIENT	-.01279	.11801	.10967	-.01259	-.00000	-.00000	-.01025	.04550	-.00201	-.00650	-.00201
RUN NO.		1464/0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/	5.00				
MACH	ALPHA	P	PT	Q(PSSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.800	-7.018	879.72850	1341.07001	394.16630	496.77490	100.70000	2.49502	889.62990	1053.81000	5.18395	2038.53999
.800	-6.507	879.74150	1340.87000	394.00930	496.79830	100.70000	2.49439	889.63990	1053.84000	5.16058	2038.57500
.800	-6.006	879.95040	1341.05000	394.00000	496.81300	100.70000	2.49456	889.84990	1053.89000	5.11190	2038.57500
.800	-5.505	879.78810	1341.13000	394.16990	496.86690	100.80000	2.49452	889.68990	1053.94000	5.09966	2038.53999
.800	-5.010	879.54170	1340.72000	394.03420	496.87060	100.80000	2.49372	889.43990	1053.99001	5.06557	2038.53999
.800	-4.515	879.68090	1340.86000	394.04300	496.78960	100.70000	2.49446	889.57980	1053.03999	5.04140	2038.53999
.800	-4.014	879.57690	1341.07001	394.26930	496.83910	100.80000	2.49471	889.48000	1054.10000	4.99363	2038.50500
.800	-3.518	879.71260	1340.78000	393.96220	496.80320	100.70000	2.49417	889.60990	1054.14999	4.98303	2038.50500
.800	-3.022	879.71800	1341.06000	394.16550	496.77440	100.70000	2.49500	889.61990	1054.19000	4.99367	2038.53999
.800	-2.530	879.85230	1340.87000	393.93360	496.81620	100.70000	2.49419	889.75000	1054.23000	4.91312	2038.50500
.800	-2.033	879.93240	1340.92999	393.92360	496.82280	100.70000	2.49423	889.82980	1054.28999	4.92444	2038.53999
.800	-1.549	879.64040	1340.86000	394.07030	496.78300	100.70000	2.49454	889.53980	1054.33000	4.89017	2038.50500
.800	-1.072	879.64530	1341.22000	394.33370	496.65700	100.60000	2.49619	889.54980	1054.39000	4.88884	2038.50500
.800	-620	879.70680	1341.14000	394.23240	496.67550	100.60000	2.49584	889.60990	1054.46001	4.87768	2038.50500
.802	-2.118	877.61230	1340.12000	394.90090	496.35670	100.50000	2.49704	887.51980	1054.50999	4.77933	2038.53999
.800	.329	877.94700	1338.72000	393.63840	496.55910	100.50000	2.49221	887.82980	1054.67999	4.71732	2038.47000
.800	.886	880.391180	1341.88000	394.31420	496.61910	100.50000	2.49743	890.29980	1054.74001	4.57491	2038.47000
GRADIENT	-.15442	-.08977	-.03849	-.06056	-.06056	-.05093	-.15429	-.12498	-.00201	-.00650	-.00769

PAGE 972  
4 OCT 91 )

(VCM048) ( 04 OCT 91 )

IA310 (AEDC 16TF-783) PROBE CALIBRATION

## PARAMETRIC DATA

RUN NO.		1498/ O		RN/L =	2.50		GRADIENT INTERVAL =		-5.00/		5.00	
MACH		P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
ALPHA	-7.016	753.05080	1273.22000	426.69290	481.51660	99.80000	2.50029	763.05980	980.45000	1.49680	2036.58000	
.900	-6.503	752.75170	1273.00000	426.71970	481.59970	99.70000	2.50066	762.76000	980.47000	1.50095	2036.58000	
.900	-6.006	752.90380	1273.92999	426.58110	481.52100	99.80000	2.49969	762.90990	980.48000	1.50493	2036.61501	
.900	-5.504	752.74930	1273.17000	426.83790	481.46700	99.80000	2.50055	762.76000	980.50980	1.50075	2036.61501	
.900	-5.012	752.70950	1273.12000	426.82710	481.46510	99.80000	2.50046	762.72000	980.52980	1.49692	2036.61501	
.900	-4.510	752.555960	1273.06000	426.87550	481.35820	99.70000	2.50107	762.56980	980.54980	1.50088	2036.61501	
.900	-4.012	752.29220	1272.70000	426.78590	481.34810	99.70000	2.50044	762.29980	980.57980	1.48967	2036.58000	
.900	-3.520	752.45750	1273.14000	426.99100	481.33080	99.70000	2.50143	762.47000	980.60990	1.48915	2036.61501	
.900	-3.017	751.17850	1270.91000	426.21970	481.33790	99.70000	2.49699	761.16990	980.60990	1.49953	2036.58000	
.901	-2.524	751.14920	1271.59000	426.70430	481.17290	99.59999	2.49947	761.14990	980.61990	1.50262	2036.61501	
.900	-2.031	751.97730	1272.17000	426.61010	481.26170	99.59999	2.49998	761.98000	980.62990	1.50973	2036.64999	
.900	-1.547	752.95850	1274.05000	427.31810	481.23800	99.59999	2.50384	762.98000	980.67990	1.53905	2036.64999	
.900	-1.070	752.59420	1272.73000	426.62820	481.31400	99.59999	2.50070	762.59990	980.71000	1.57690	2036.64999	
.900	-623	752.65230	1272.88000	426.69650	481.30830	99.59999	2.50104	762.65990	980.81980	2.76187	2036.68500	
.900	-259	752.98660	1273.50000	426.92360	481.21660	99.50000	2.50288	763.00000	980.84990	3.02371	2036.68500	
.900	-313	752.45780	1272.41000	426.48950	481.23750	99.50000	2.50058	762.46000	980.86990	2.81105	2036.72000	
.900	.881	753.63650	1274.58000	427.27880	481.21850	99.50000	2.50498	763.65990	980.86990	2.91903	2036.72000	
.900	GRADIENT	2.1413	.22980	.03050	-.02238	-.04260	.00060	.21570	.06616	.32053	.02555	
RUN NO.		1483/ O		RN/L =	2.50		GRADIENT INTERVAL =		-5.00/		5.00	
MACH		P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
ALPHA	-7.012	564.99050	1206.07001	478.39450	450.80880	100.20000	2.49808	575.17990	911.41990	.98986	2037.77000	
.1.100	-6.497	564.83980	1206.07001	478.45390	450.77440	100.20000	2.49815	575.02980	911.47000	.98986	2037.77000	
.1.100	-5.998	565.00850	1206.25000	478.49220	450.79370	100.20000	2.49849	575.20000	911.53980	1.00314	2037.73500	
.1.100	-5.499	564.77170	1205.89000	478.37620	450.77810	100.20000	2.49777	574.96000	911.61990	1.00885	2037.73500	
.1.100	-5.005	564.90840	1206.22000	478.51420	450.77420	100.20000	2.49847	575.09990	911.63990	1.011129	2037.73500	
.1.100	-4.500	564.75220	1205.84000	478.35470	450.77910	100.20000	2.49767	574.93990	911.67990	1.00348	2037.73500	
.1.100	-4.001	564.86960	1206.14000	478.48320	450.77390	100.20000	2.49830	575.05980	911.70000	.97918	2037.73500	
.1.100	-3.506	564.97120	1205.99001	478.35550	450.81300	100.20000	2.49791	575.15990	911.75000	.97141	2037.73500	
.1.100	-3.005	564.90230	1205.89000	478.32470	450.80810	100.20000	2.49771	575.08980	911.76000	.97149	2037.70000	
.1.100	-2.509	564.98340	1205.80000	478.24020	450.83620	100.20000	2.49747	575.16990	911.79980	.99543	2037.70000	
.1.100	-2.010	564.84180	1205.92000	478.36600	450.79100	100.20000	2.49781	575.02980	911.82980	1.00341	2037.70000	
.1.100	-1.518	564.91210	1205.89000	478.32080	450.81030	100.20000	2.49771	575.09990	911.85990	1.01157	2037.73500	
.1.100	-1.025	564.92160	1205.94000	478.34620	450.80710	100.20000	2.49782	575.10990	911.86990	1.01699	2037.70000	
.1.100	-571	564.91020	1206.09000	478.43800	450.78830	100.20000	2.49817	575.08980	911.87990	1.01413	2037.70000	
.1.100	-102	564.96190	1205.92000	478.31840	450.88990	100.30000	2.49771	575.14990	911.92990	1.00612	2037.70000	
.1.100	.46	565.00950	1206.16000	478.43950	450.88430	100.30000	2.49770	575.20000	911.96000	1.00051	2037.70000	
.1.100	.966	564.90220	1205.92000	478.33420	450.88990	100.30000	2.49719	575.10990	911.98000	1.00071	2037.70000	
GRADIENT	.02114	.01370	-.00038	.01872	.01909	-.00009	.02124	.05487	.00489	-.00649		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCMO48) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1521/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-.500	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
ALPHA	-7.018	462.76250	1198.00000	505.79810	426.56130	100.10000	2.49952	472.88990	864.39990
	-6.503	462.47510	1197.73000	505.72440	426.51290	100.10000	2.49894	472.59990	864.39990
	-6.004	462.41310	1198.03999	505.89480	426.54130	100.20000	2.49957	472.53980	864.40990
	-5.504	462.35350	1198.02000	505.89790	426.45140	100.10000	2.49951	472.48000	864.39990
	-5.005	462.64260	1198.03999	505.84470	426.60180	100.20000	2.49900	472.76980	864.41990
	-4.505	462.71190	1198.09000	505.85500	426.61500	100.20000	2.49911	472.83980	864.40990
	-4.012	462.72240	1198.03000	505.82230	426.62380	100.20000	2.49899	472.84990	864.40990
	-3.513	462.47410	1197.86000	505.79030	426.57570	100.20000	2.49861	472.59990	864.41990
	-3.014	462.50540	1197.66000	505.68210	426.60420	100.20000	2.49821	472.62990	864.39990
	-2.520	462.69430	1197.73000	505.67630	426.64700	100.20000	2.49837	472.81980	864.40990
	-2.024	462.63820	1198.69000	506.17500	426.61080	100.30000	2.49973	472.76980	864.40990
	-1.536	462.39700	1197.46001	505.60450	426.67240	100.30000	2.49720	472.51980	864.39990
	-1.055	462.43630	1197.57001	505.65160	426.67140	100.30000	2.49743	472.55980	864.37790
	-604	462.76760	1198.67999	506.14160	426.72190	100.40000	2.49914	472.89990	864.40990
	-1.249	462.64620	1197.47000	505.55490	426.81320	100.40000	2.49666	472.76980	864.39990
	.354	462.73020	1198.34000	505.97750	426.74680	100.40000	2.49845	472.85990	864.40990
	.910	462.63260	1198.03000	505.84180	426.52420	100.40000	2.49780	472.75980	864.39990
GRADIENT	.00442	.02039	.00934	.03563	.04797	-.00024	.00457	-.000219	.00159
									.00125

RUN NO.	1537/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-.500	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
ALPHA	-7.017	381.93580	1214.48000	523.60280	402.07910	99.89999	2.49848	391.63990	879.72000
	-6.496	382.11890	1215.28999	523.95360	402.05760	99.89999	2.50009	391.82980	879.72000
	-5.997	381.83500	1214.82001	523.75370	402.01660	99.89999	2.49902	391.53980	879.71000
	-5.497	381.83300	1215.13000	523.88940	401.98680	99.89999	2.49959	391.53980	879.70000
	-5.009	381.85380	1214.97000	523.81880	402.00810	99.89999	2.49931	391.55980	879.71000
	-4.505	381.85130	1215.36000	523.98950	402.1430	100.10000	2.49883	391.55980	879.70000
	-4.011	381.99370	1214.70000	523.70680	402.1750	100.10000	2.49777	391.70000	879.67990
	-3.512	381.70530	1215.00999	523.83940	402.10330	100.10000	2.49809	391.40990	879.66990
	-3.013	381.95310	1214.92000	523.79520	402.18650	100.10000	2.49811	391.65990	879.65990
	-2.518	381.67720	1214.72000	523.71310	402.12230	100.10000	2.49754	391.37990	879.62990
	-2.022	382.05790	1215.56000	524.07300	402.15750	100.10000	2.49935	391.76980	879.62990
	-1.530	381.63750	1214.78000	523.74020	401.96090	99.89999	2.49881	391.33980	879.62990
	-1.053	381.55790	1214.82001	523.75900	401.93330	99.89999	2.49882	391.25980	879.60990
	-5.95	381.86250	1215.17000	523.90620	402.13550	100.10000	2.49850	391.56980	879.58980
	-1.177	381.93140	1215.19000	523.91360	402.08250	100.00000	2.49918	391.63990	879.55980
	.373	381.64840	1214.58000	523.65230	402.05520	100.00000	2.49786	391.34990	879.53980
	.918	381.87940	1215.62000	524.10280	402.09810	100.10000	2.49933	391.58980	879.53980
GRADIENT	-.01792	.02630	.01186	-.02026	-.01722	-.00014	-.01796	-.03013	-.00285

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 974  
(VCMO48) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1555/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-.500	PHI =	180.000	PREF	SH10+3	PATM
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC						
ALPHA													
1.450	-7.016	358.87330	1226.20000	528.26070	394.53860	100.80000	2.49478	368.34990	893.70000	1.44142	2035.35500		
	-6.507	358.81590	1225.87000	528.12060	394.48050	100.70000	2.49474	368.28980	893.71000	1.44181	2035.35500		
	-6.008	359.21020	1225.85001	528.13210	394.60600	100.70000	2.49507	368.68990	893.72000	1.44183	2035.39000		
	1.449												
	-5.509	359.02120	1226.14000	528.24320	394.52030	100.70000	2.49541	368.50000	893.73000	1.43399	2035.35500		
	1.450												
	-5.011	358.93380	1225.89999	528.1460	394.51460	100.70000	2.49490	368.40990	893.71000	1.43802	2035.35500		
	1.449												
	-4.518	359.41770	1225.74001	528.09670	394.68140	100.70000	2.49508	368.89990	893.73000	1.43821	2035.35500		
	-4.015	359.10910	1226.34000	528.33080	394.52930	100.70000	2.49584	368.58980	893.72000	1.44126	2035.35500		
	1.450												
	-3.521	359.12210	1225.77000	528.09450	394.58570	100.70000	2.49485	368.59990	893.73000	1.40844	2035.39000		
	1.449												
	-3.024	358.65990	1225.53999	527.97530	394.46170	100.70000	2.49401	368.12990	893.73000	1.40502	2035.35500		
	1.450												
	-2.526	359.06320	1226.67000	528.04980	394.57640	100.70000	2.49462	368.53980	893.72000	1.40855	2035.35500		
	1.449												
	-2.038	358.91460	1225.85001	528.11720	394.44290	100.60000	2.49539	368.38990	893.70000	1.41203	2035.39000		
	1.450												
	-1.555	359.12940	1226.21001	528.27780	394.47730	100.60000	2.49623	368.60990	893.68990	1.41161	2035.39000		
	1.450												
	-1.082	358.67800	1225.87000	528.11350	394.36670	100.60000	2.49520	368.14990	893.70000	1.41940	2035.35500		
	1.450												
	-643	358.59840	1225.97000	528.15090	394.26220	100.50000	2.49590	368.06980	893.73000	1.42300	2035.35500		
	1.450												
	-299	358.95120	1226.36000	528.33130	394.33720	100.50000	2.49692	368.42990	893.71000	1.42255	2035.35500		
	1.450												
	.266	358.92360	1226.02000	528.18820	394.35960	100.50000	2.49629	368.39990	893.68990	1.42666	2035.35500		
	1.450												
	.841	358.65530	1226.41000	528.33670	394.23950	100.50000	2.49672	368.12990	893.68990	1.44871	2035.39000		
	1.451												
	GRADIENT	-.09276	.08446	.03042	-.07115	-.04866	.00035	-.09366	-.00682	-.00015	.00145	.00624	.00115
	RUN NO.	1639/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00							
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC						
ALPHA													
1.470	-7.019	348.04050	1223.28317	526.33826	390.64310	100.90000	2.49344	357.37990	888.50000	1.35090	2032.20500		
	-6.504	347.98170	1223.24406	526.29414	390.63230	100.90000	2.49322	357.31980	888.51000	1.35096	2032.24001		
	-6.005	348.19820	1223.02298	526.33487	390.69900	100.90000	2.49350	357.53980	888.51000	1.35812	2032.24001		
	1.469												
	-5.507	347.88350	1223.74490	526.21898	390.60280	100.90000	2.49308	357.22000	888.49000	1.35438	2032.20500		
	1.470												
	-5.013	347.74490	1223.23892	526.29576	390.54300	100.90000	2.49323	357.07980	888.51000	1.35422	2032.20500		
	1.470												
	-4.510	348.17720	1223.42921	526.40805	390.73850	101.00000	2.49333	357.51980	888.50000	1.35422	2032.20500		
	1.470												
	-4.017	347.90190	1223.39529	526.37204	390.58060	100.90000	2.49364	357.24000	888.50000	1.35422	2032.20500		
	1.470												
	-3.518	347.95260	1223.05894	526.23975	390.69820	101.00000	2.49249	357.29880	888.49000	1.35461	2032.20500		
	1.484												
	-3.020	347.87450	1224.1248	526.33853	390.60963	100.9430	2.49280	357.21000	888.49000	0.00000	2032.24001		
	1.484												
	-2.533	347.98050	1223.37550	526.37106	390.67820	101.00000	2.49307	357.31980	888.50000	1.35426	2032.20500		
	1.470												
	-2.040	348.01880	1223.57800	526.45597	390.66600	101.00000	2.49358	357.35990	888.48000	1.35751	2032.20500		
	1.470												
	-1.551	347.93140	1223.36948	526.36457	390.66240	101.00000	2.49302	357.26980	888.49000	1.35426	2032.17000		
	1.470												
	-1.075	347.81540	1222.88734	526.15846	390.59250	100.90000	2.49279	357.14990	888.49000	1.35826	2032.17000		
	1.470												
	-6.39	347.79610	1222.84396	526.13891	390.66600	101.00000	2.49198	357.12990	888.47000	1.35483	2032.17000		
	1.470												
	-2.258	348.27490	1223.64500	526.50470	390.75710	101.00000	2.49368	357.61990	888.47000	1.35052	2032.13499		
	1.470												
	.287	347.82470	1222.95703	526.18762	390.65890	101.00000	2.49232	357.15990	888.47000	1.35818	2032.13499		
	1.470												
	.864	348.02100	1223.17499	526.29299	390.64040	100.90000	2.49335	357.35990	888.47000	1.35449	2032.13499		
	1.470												
	-.00929	-.94745	-.38942	-.94475	-.00020	-.00027	-.00007	-.00624	-.00624	-.000595	-.00145	.00115	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 975

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCMO48) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1590/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-.500	PHI =	180.000
P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF		SH10+3
ALPHA			386.31860	100.40000	2.49712	346.90990	896.83980	1.59909	PATM
1.492	-7.017	337.71510	1224.86296	525.97605	386.25590	100.40000	2.49708	896.83980	1.58662
1.492	-6.508	337.54760	1225.13193	526.06397	386.22310	100.40000	2.49711	896.84990	1.59456
1.492	-6.004	337.50760	1225.21689	526.09325	386.23100	100.40000	2.49697	896.83980	1.59485
1.492	-5.511	337.46920	1224.98688	525.99767	386.21300	100.40000	2.49640	896.83980	1.59128
1.492	-5.012	337.58890	1224.64679	525.87569	386.30760	100.40000	2.49661	896.83980	1.59107
1.492	-4.514	337.53910	1224.80049	525.93124	386.27710	100.40000	2.49683	896.63990	1.59083
1.492	-4.016	337.45000	1224.98064	525.99342	386.23100	100.40000	2.49715	896.57980	1.58642
1.493	-3.523	337.38990	1225.26686	526.09954	386.19090	100.40000	2.49764	896.82980	1.58628
1.492	-3.024	337.64480	1225.39653	526.18022	386.26440	100.40000	2.49706	896.73000	1.59070
1.492	-2.531	337.58690	1225.09061	526.05227	386.26680	100.40000	2.49714	896.75000	1.59487
1.492	-2.039	337.55760	1224.98415	526.00696	386.26100	100.40000	2.49698	896.82980	1.59487
1.492	-1.549	337.62650	1224.98972	526.01693	386.28340	100.40000	2.49698	896.82980	1.59487
1.493	-1.078	337.33130	1225.13860	526.04228	386.17700	100.40000	2.49640	896.61980	1.59061
1.492	-629	337.43140	1224.80684	525.92104	386.24630	100.40000	2.49657	896.61980	1.58703
1.492	-244	337.61820	1224.92260	525.93716	386.31010	100.40000	2.49589	896.81980	1.58707
1.492	.302	337.46220	1224.49365	525.80017	386.28490	100.40000	2.49630	896.64990	1.58744
1.492	.872	337.44140	1224.86674	525.94613	386.25590	100.40000	2.49620	896.62990	1.57983
GRADIENT	-.00843	-.06940	-.02866	.00520	-.00000	-.00000	-.00016	-.000901	-.00113

RUN NO.	1606/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-.500	PHI =	180.000
P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF		SH10+3
ALPHA			382.63210	101.00000	2.49261	336.22000	905.62990	1.78519	PATM
1.515	-7.022	327.19650	1227.90048	525.80742	382.70950	101.00000	2.49169	336.28980	905.60990
1.515	-6.502	327.26760	1227.31308	525.58921	382.73340	101.00000	2.49058	336.20000	905.62990
1.514	-6.004	327.18160	1226.65154	525.31978	382.63110	100.90000	2.48930	335.85990	905.62990
1.515	-5.510	326.85180	1225.69868	524.90058	382.50128	101.00000	2.49038	335.82980	905.62990
1.515	-5.012	326.81840	1226.50128	525.20818	382.59790	101.00000	2.49276	336.61990	1.80972
1.514	-4.514	327.24680	1227.12185	525.49440	382.60790	100.90000	2.49196	336.11990	1.82257
1.515	-4.016	327.10110	1226.42444	525.22240	382.59160	100.90000	2.49196	336.11990	1.84185
1.514	-3.518	327.28690	1226.47539	525.27088	382.70700	101.00000	2.49188	336.30980	905.64990
1.515	3.019	326.83570	1226.34697	525.15410	382.55100	101.00000	2.49141	335.84990	905.62990
1.514	-2.531	327.21830	1226.12546	525.12621	382.61570	100.90000	2.49239	336.24000	905.64990
1.514	-2.038	327.52120	1226.54045	525.33118	382.76340	101.00000	2.49259	336.54980	905.62990
1.514	-1.514	327.30420	1226.86836	525.31657	382.66280	101.00000	2.49241	336.26980	905.63990
1.514	-1.072	327.49900	1227.30026	525.42599	382.66550	101.00000	2.49280	336.32980	905.63990
1.514	-.633	327.66460	1227.70882	525.80473	382.73220	101.00000	2.49363	336.52980	905.63990
1.514	-.245	328.01540	1228.75677	526.26251	382.80100	101.00000	2.49427	336.70000	905.64990
1.514	.871	328.06370	1229.13966	526.41914	382.79520	101.00000	2.49564	337.05980	905.63990
GRADIENT	.16724	.42849	.19109	.03558	.00071	.01678	.000999	.17202	.00448

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 976

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCMO48) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1621/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-.500	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PAFM
ALPHA		317.99490	1239.68794	528.76037	378.89770	101.30000	2.49449	326.85990	907.76980	1.51382 2033.53500
1.541	-7.017	317.99490	1239.68794	528.59631	378.94210	101.30000	2.49366	326.85990	907.76980	1.51051 2033.53500
1.541	-6.502	317.99680	1239.25397	528.23649	378.88770	101.30000	2.49195	326.50000	907.74000	1.51142 2033.53500
1.541	-6.009	317.64700	1238.47571	527.44843	378.83400	101.30000	2.48825	325.87990	907.74000	1.51353 2033.53500
1.542	-5.505	317.04660	1236.69225	527.13161	378.80420	101.30000	2.48676	325.60990	907.72000	1.51437 2033.57001
1.542	-5.012	316.78470	1235.98520	527.42565	378.91410	101.30000	2.48820	326.06980	907.70000	1.51376 2033.57001
1.541	-4.514	317.23320	1236.53680	528.27924	378.84620	101.30000	2.49212	326.41990	907.71000	1.51121 2033.53500
1.542	-4.016	317.56810	1238.62799	528.77125	378.87450	101.30000	2.49432	326.77980	907.70000	1.50603 2033.53500
1.541	-3.518	317.91670	1239.75516	528.67078	378.86470	101.30000	2.49374	326.67990	907.67990	1.50245 2033.57001
1.542	-3.020	317.81980	1239.53825	528.47226	378.92260	101.30000	2.49296	326.72000	907.66990	1.50697 2033.53500
1.541	-2.527	317.86080	1238.99232	528.45774	378.97190	101.30000	2.49272	326.80980	907.65990	1.49943 2033.57001
1.541	-2.034	317.94970	1238.90997	528.23206	378.85110	101.30000	2.49180	326.38990	907.62990	1.50750 2033.57001
1.542	-1.549	317.53930	1238.51822	528.04543	378.86690	101.30000	2.49105	326.32980	907.63990	1.51191 2033.57001
1.541	-1.077	317.48190	1238.05423	527.94593	378.95360	101.30000	2.49064	326.49000	907.59990	1.51237 2033.57001
1.541	-632	317.64010	1237.71054	528.91650	378.91650	101.30000	2.49186	326.55980	907.58980	1.51546 2033.57001
1.541	-.245	317.70610	1238.32893	528.19230	378.98360	101.40000	2.49272	326.75000	907.58980	1.41556 2033.57001
1.542	.303	317.88960	1240.55069	529.06924	378.91890	101.40000	2.49309	326.63990	907.56980	1.41152 2033.57001
1.542	.879	317.78080	1240.90141	529.18164	378.91207	.01249	.01455	.00015	.03796	-.02754 .00478
GRADIENT		.03674	.31687							

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM049) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1575/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
MACH	.599	1252.93800	159.7.39999	315.12870	522.52120	100.40000	2.49556	1262.69000	1304.83000	.99067 2034.75999
	-6.997	1252.47600	159.7.14999	315.29790	522.48950	100.40000	2.49597	1262.23000	1304.84000	.98822 2034.72501
	-6.488	1252.72800	159.6.75000	314.75440	522.55690	100.40000	2.49366	1262.47000	1304.87000	.98847 2034.72501
	-5.990	1251.84801	159.7.08000	315.75420	522.42110	100.40000	2.49756	1261.61000	1304.89000	.98567 2034.72501
	-5.492	1251.88600	159.7.21001	315.83230	522.41360	100.40000	2.49796	1261.64999	1304.89999	.98819 2034.72501
	-4.994	1251.88600	159.7.21001	315.83230	522.41360	100.40000	2.49804	1261.44000	1304.92000	.99088 2034.65500
	-4.490	1251.67500	159.7.07001	315.88700	522.40160	100.40000	2.49853	1261.82001	1304.96001	.99093 2034.69000
	-3.991	1252.06300	159.6.98000	315.49370	522.45630	100.40000	2.49678	1261.78999	1304.97000	.99091 2034.62000
	-3.487	1252.03200	159.7.02000	315.55270	522.44870	100.40000	2.49676	1261.44000	1305.00000	.99360 2034.62000
	-2.987	1251.67900	159.6.89000	315.73270	522.51220	100.50000	2.49826	1261.78000	1305.00000	.99351 2034.58501
	-2.482	1252.01100	159.7.53000	315.99800	522.49190	100.50000	2.49853	1261.05000	1305.05000	.98855 2034.58501
	-1.976	1251.28000	159.7.03999	316.18600	522.45040	100.50000	2.49539	1261.53999	1305.05000	.97033 2034.62000
	-1.468	1251.78600	159.6.62000	315.41850	522.55000	100.50000	2.49652	1261.52000	1305.07001	.98582 2034.58501
	-954	1251.75999	159.6.89000	315.66630	522.52170	100.50000	2.49623	1261.55000	1305.10001	.98602 2034.72501
	-420	1251.79100	159.6.84000	315.59840	522.53030	100.50000	2.49617	1261.14999	1305.49001	.98828 2034.72501
	-075	1251.39200	159.6.52000	315.65750	522.51250	100.50000	2.49743	1261.44000	1305.50999	.98048 2034.72501
	.472	1251.67500	159.7.06000	315.87840	522.49580	100.60000	2.49673	1261.55000	1305.52000	.00162 .00300
	.984	1251.78600	159.7.11000	315.82980	522.59770	100.60000	2.49653	1261.0019	1304.452	.00162 .00300
	GRADIENT	-.04442	-.04332	-.00005	.02350					

	RUN NO.	1465/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
MACH	-7.003	880.222020	1341.25999	393.97240	496.65700	100.50000	2.49586	890.11990	1054.95000	4.39680 2038.50500
	-6.492	879.844770	1341.17999	394.16630	496.60520	100.50000	2.49628	889.75000	1054.95000	4.35561 2038.50500
	-5.986	879.79540	1341.28000	394.27590	496.58620	100.50000	2.49668	889.70000	1055.00000	4.20299 2038.50500
	-5.491	879.56880	1340.91000	394.15600	496.58890	100.50000	2.49596	889.47000	1055.05000	4.17429 2038.47000
	-4.991	879.46700	1340.99001	394.28470	496.65760	100.60000	2.49581	889.36990	1055.07001	4.14436 2038.47000
	-4.490	879.67900	1341.03999	394.11620	496.69600	100.60000	2.49542	889.66990	1055.13000	4.20375 2038.47000
	-3.990	879.65970	1340.95000	394.12430	496.68800	100.60000	2.49535	889.55980	1055.16000	4.12480 2038.47000
	-3.489	879.59060	1340.83000	394.08200	496.68950	100.60000	2.49511	889.49000	1055.17000	3.90492 2038.47000
	-2.988	879.58590	1341.14000	394.31490	496.65600	100.60000	2.49605	889.49000	1055.23000	3.76627 2038.47000
	-2.487	879.56760	1341.00000	394.22340	496.66770	100.60000	2.49566	889.47000	1055.24001	3.72174 2038.43500
	-1.980	880.03220	1341.02000	393.92260	496.74070	100.60000	2.49490	889.92990	1055.28000	3.79380 2038.43500
	-1.477	879.76950	1341.00999	394.09370	496.69950	100.60000	2.49534	889.66990	1055.31000	3.78474 2038.47000
	-.971	879.81860	1341.11000	394.13420	496.69680	100.60000	2.49555	889.72000	1055.35001	3.73934 2038.47000
	-.451	879.79910	1341.07001	394.11820	496.69780	100.60000	2.49546	889.70000	1055.37000	3.68597 2038.47000
	.083	879.41650	1340.97000	394.30400	496.64670	100.60000	2.49584	889.31980	1055.50999	3.52995 2038.43500
	.489	879.34400	1341.12000	394.46460	496.70780	100.70000	2.49585	889.25000	1055.55000	3.47045 2038.43500
	1.006	879.83350	1340.78999	393.88750	496.82150	100.70000	2.49398	889.73000	1055.58000	3.44624 2038.43500
	GRADIENT	.00431	-.00056	-.00333	.01131					-.11909 -.00538

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 978  
 (VCM049) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1499/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
.900	-7.001	752.86210	1273.00999	426.66060	481.33280	99.59999	2.50112	762.86990	980.99000	3.21565	2036	72000	
.900	-6.487	751.77610	1271.42000	426.21460	481.39210	99.70000	2.49761	761.76980	981.00000	3.30720	2036	72000	
.900	-5.985	751.72730	1271.33000	426.18190	481.47900	99.80000	2.49855	761.72000	981.00000	3.38066	2036	72000	
.900	-5.483	751.95140	1271.87000	426.41970	481.46170	99.80000	2.49803	761.95000	981.01980	3.46228	2036	72000	
.900	-4.991	752.17460	1272.47000	426.69900	481.43750	99.80000	2.49938	762.17990	981.03980	3.55414	2036	68500	
.900	-4.489	752.64280	1272.85001	426.68140	481.65430	100.00000	2.49866	762.64990	981.08980	3.64005	2036	68500	
.900	-3.986	752.78000	1273.13000	426.79200	481.64920	100.00000	2.49924	762.78980	981.11990	3.67457	2036	68500	
.900	-3.489	752.68680	1273.32001	426.97830	481.52540	99.89999	2.50046	762.70000	981.14990	3.70966	2036	72000	
.900	-2.981	752.89210	1273.05000	426.67070	481.67820	100.00000	2.4988	762.89990	981.15990	3.75545	2036	68500	
.900	-2.478	752.84060	1273.13000	426.75630	481.66020	100.00000	2.49917	762.84990	981.20000	3.80988	2036	68500	
.900	-1.980	752.86060	1273.12000	426.73730	481.66480	100.00000	2.49911	762.86990	981.23000	3.87460	2036	68500	
.900	-1.475	752.69240	1272.89999	426.68630	481.65800	100.00000	2.49873	762.70000	981.25000	3.92211	2036	68500	
.900	-1.966	752.69120	1273.00999	426.76270	481.81790	100.20000	2.49788	762.70000	981.29980	3.96912	2036	68500	
.900	-1.448	752.68190	1272.96001	426.73390	481.82150	100.20000	2.49775	762.68990	981.30980	4.04613	2036	68500	
.900	.048	752.65280	1272.85001	426.67750	481.91430	100.30000	2.49692	762.65990	981.38990	4.22444	2036	68500	
.900	.481	752.68210	1272.92999	426.71310	481.99710	100.40000	2.49652	762.68990	981.42990	4.29529	2036	68500	
.900	.997	752.75240	1272.95000	426.68510	482.00760	100.40000	2.49648	762.76000	981.46000	4.32603	2036	64999	
	GRADIENT	.02848	.00845	-.01112	.08070	.08880	-.00053	.02837	.06702	.12785	-.00348		
	RUN NO.	1484/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00							
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM		
1.100	-7.006	565.03960	1206.17000	478.43310	450.88990	100.30000	2.49771	575.23000	912.06980	.95306	2037	70000	
1.100	-6.492	564.82080	1205.99001	478.41480	450.85940	100.30000	2.49740	575.01000	912.07980	.95579	2037	70000	
1.100	-5.995	565.11180	1205.98000	478.29420	450.92680	100.30000	2.49724	575.29980	912.08980	.96098	2037	66499	
1.100	-5.492	564.82060	1206.02000	478.43240	450.85600	100.30000	2.49747	575.01000	912.11990	.96354	2037	66499	
1.100	-4.992	564.84450	1205.67999	478.22530	450.89770	100.30000	2.49668	575.02980	912.12990	.96642	2037	63000	
1.100	-4.488	564.82980	1206.08000	478.46360	450.85180	100.30000	2.49760	575.01980	912.13990	.96872	2037	66499	
1.100	-3.995	564.93140	1205.98000	478.36550	450.88550	100.30000	2.49732	575.11990	912.16990	1.01422	2037	66499	
1.100	-3.496	564.86130	1205.96001	478.38160	450.87180	100.30000	2.49731	575.04980	912.21000	1.01424	2037	66499	
1.100	-2.997	564.93020	1206.08000	478.42430	450.87480	100.30000	2.49755	575.11990	912.21000	1.01414	2037	63000	
1.100	-2.488	565.00240	1205.88000	478.27930	450.91240	100.30000	2.49706	575.18990	912.20000	1.01704	2037	63000	
1.100	-1.996	564.95020	1206.08000	478.41630	450.87920	100.30000	2.49754	575.13990	912.22000	1.01141	2037	63000	
1.100	-1.487	564.99000	1206.11000	478.41800	450.88500	100.30000	2.49759	575.17990	912.24000	1.00867	2037	63000	
1.100	-989	564.78050	1206.02000	478.44850	450.84690	100.30000	2.49748	574.97000	912.26000	1.00603	2037	63000	
1.100	-4.86	564.93970	1206.12000	478.44360	450.79200	100.20000	2.49822	575.12990	912.25000	1.00595	2037	63000	
1.100	.001	564.90110	1206.00000	478.38920	450.87650	100.30000	2.49738	575.08980	912.28980	1.00876	2037	59500	
1.100	.513	564.88380	1205.74001	478.24460	450.81980	100.20000	2.49738	575.06980	912.27980	.99548	2037	59500	
1.100	1.014	564.80100	1205.98000	478.41720	450.77540	100.20000	2.49797	574.99000	912.27980	.99529	2037	59500	
	GRADIENT	-.00209	.00843	.00574	-.01377	-.01539	.00011	-.00198	-.00258	-.00258	-.01038		

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 979  
(VCM049) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1522/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.250	-7.001	462.38450	1197.84000	505.79980	426.70650	100.40000	2.49738	472.50980	864.39990		1.23742	2035.77499	
-6.485	462.37840	1197.25999	505.50730	426.76390	100.40000	2.49620	472.50000	864.39990		1.23148	2035.77499		
1.250	-5.987	462.79910	1198.46001	506.02320	426.75270	100.40000	2.49870	472.92990	864.39990		1.23350	2035.77499	
-5.488	462.61280	1198.00000	505.83110	426.75050	100.40000	2.49774	472.74000	864.39990		1.23398	2035.77499		
1.250	-4.984	462.56370	1197.89000	505.78590	426.74880	100.40000	2.49751	472.68990	864.39990		1.23083	2035.77499	
-4.486	462.63160	1198.17000	505.91280	426.73800	100.40000	2.49809	472.75980	864.39990		1.23380	2035.77499		
1.250	-3.988	462.48290	1198.05000	505.88480	426.71120	100.40000	2.49782	472.60990	864.41990		1.23066	2035.77499	
-3.489	462.79200	1198.05000	505.81690	426.79250	100.40000	2.49786	472.91990	864.40990		1.23066	2035.77499		
1.250	-2.987	462.82080	1198.22000	505.89700	426.78270	100.40000	2.49821	472.95000	864.42990		1.23375	2035.77499	
1.250	-2.483	462.61130	1198.19000	505.92750	426.73070	100.40000	2.49812	472.74000	864.42990		1.22727	2035.77499	
1.250	-1.978	462.47530	1197.69000	505.70390	426.74560	100.40000	2.49709	472.59990	864.43990		1.23104	2035.77499	
1.250	-1.478	462.41850	1197.22000	505.47830	426.77860	100.40000	2.49613	472.53980	864.41990		1.22826	2035.77499	
1.250	-980	462.74950	1198.39999	506.00370	426.74560	100.40000	2.49857	472.87990	864.40990		1.22705	2035.81000	
-462	462.73410	1197.75000	505.67750	426.80790	100.40000	2.49724	472.85990	864.41990		1.22447	2035.77499		
1.250	-102	462.64180	1198.13000	505.89060	426.74490	100.40000	2.49801	472.76980	864.42990		1.22733	2035.77499	
1.250	.502	462.77760	1198.67000	506.13430	426.72560	100.40000	2.49912	472.90990	864.39990		1.23656	2035.77499	
1.250	1.009	462.63280	1197.99001	505.82150	426.75660	100.40000	2.49772	472.75980	864.39990		1.23726	2035.77499	
GRADIENT	.01380	.02055	.00740	.00153	-.000000	.00004	.01400	.00004	.000024	.000073			
	RUN NO.	1538/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00							
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.400	-7.005	381.92240	1215.07001	523.86130	402.16310	100.10000	2.49836	391.62990	879.48000		1.21661	2035.32001	
-6.490	381.79320	1215.17999	523.91210	401.97000	99.89999	2.49965	391.50000	879.48000		1.22296	2035.32001		
-5.987	381.87600	1214.60001	523.65650	402.04980	99.89999	2.49865	391.57980	879.47000		1.22354	2035.32001		
-5.487	381.98270	1214.96001	523.81200	402.04790	99.89999	2.49939	391.68990	879.46000		1.22967	2035.28500		
-4.989	381.81320	1215.16000	523.90280	402.12160	100.10000	2.49844	391.51980	879.47000		1.22622	2035.28500		
-4.485	381.55860	1214.73000	523.71970	401.94190	99.89999	2.49866	391.25980	879.45000		1.22018	2035.32001		
1.400	-3.993	381.97020	1215.33000	523.87470	402.15280	100.10000	2.49887	391.67990	879.43990		1.21635	2035.28500	
1.400	-3.489	381.96220	1215.03999	523.84740	402.03420	99.89999	2.49952	391.66990	879.40990		1.22310	2035.28500	
-2.987	381.88040	1215.48000	524.04150	401.96800	99.89999	2.50026	391.58980	879.42990		1.21620	2035.28500		
-2.484	381.69680	1214.75999	523.73020	402.12430	100.10000	2.49762	391.39990	879.40990		1.22015	2035.25000		
-1.981	381.72240	1215.42000	524.01830	402.06980	100.10000	2.49885	391.42990	879.39990		1.21626	2035.25000		
-1.483	381.63770	1214.74001	523.72290	402.07300	99.89999	2.49755	391.33980	879.35990		1.21694	2035.25000		
-1.399	381.93370	1214.73000	523.71120	402.07300	99.89999	2.49898	391.70000	879.36990		1.22018	2035.25000		
-4.68	381.78150	1215.46001	524.03470	401.94020	99.89999	2.50015	391.49000	879.34990		1.21944	2035.21500		
.091	381.74290	1215.30000	523.96530	401.94360	99.89999	2.49983	391.45000	879.33980		1.22608	2035.21500		
.501	381.76440	1215.03999	523.85130	402.11840	100.10000	2.49819	391.47000	879.30980		1.21986	2035.21500		
1.400	1.006	381.75420	1215.08000	523.86890	401.96780	99.89999	2.49944	391.46000	879.26980		1.21660	2035.21500	
GRADIENT	-.00676	.00789	.00358	-.01075	-.01113		-.00673	-.02903	-.00028	-.01653			

## PARAMETRIC DATA

RUN NO.	1556 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PATM
1.450	-6.956	358.75630	1225.95000	528.15060	394.31350	100.50000	2.49601	368.23000	893.67990
1.450	-6.487	359.02370	1225.74001	528.07710	394.41670	100.50000	2.49589	368.50000	893.67990
1.450	-5.983	358.82230	1226.55000	528.40360	394.20870	100.40000	2.49772	368.29980	893.66990
1.450	-5.484	358.84450	1226.06000	528.20090	394.26070	100.40000	2.49688	368.31980	893.67990
1.450	-4.980	358.85380	1226.17000	528.24730	394.25340	100.40000	2.49709	368.32980	893.68990
1.450	-4.481	358.89360	1226.10001	528.22000	394.27250	100.40000	2.49700	368.36990	893.66990
1.451	-3.982	358.63700	1226.13000	528.21950	394.18920	100.40000	2.49681	368.10990	893.66990
1.450	-3.483	358.67820	1225.75999	528.06760	394.23610	100.40000	2.49620	368.14990	893.67990
1.450	-2.979	359.02080	1226.28000	528.30150	394.22560	100.30000	2.49803	368.50000	893.66990
1.450	-2.475	358.83400	1226.17000	527.85160	394.44530	100.40000	2.49766	368.30980	893.64990
1.449	-1.969	359.17430	1225.17999	528.51440	394.22880	100.40000	2.49829	368.43990	893.63990
1.450	-1.466	358.95870	1226.80000	528.00760	394.23680	100.40000	2.49591	368.10990	893.64990
1.450	-0.954	358.63960	1225.62000	528.02880	394.29640	100.30000	2.49690	368.52980	893.63990
1.449	-0.423	359.05370	1225.62000	527.97800	393.96850	99.89999	2.49894	368.34990	893.24000
1.450	-.081	358.87670	1225.52000	528.00980	393.97730	99.89999	2.49911	368.39990	893.24000
1.450	.477	358.92580	1225.59000	528.16940	394.00830	100.20000	2.49768	367.95000	893.23000
1.451	.445	358.47970	1226.03000	528.12940	394.10400	100.20000	2.49770	368.22000	893.20000
1.450	.987	358.74660	1225.89999	528.07050	394.02972	-.02972	-.03745	-.05901	.00022
GRADIENT									

RUN NO.	1640 / 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PATM
1.471	-6.954	347.70510	1223.41760	526.36587	390.51930	100.90000	2.49340	357.03980	888.47000
1.485	-6.486	347.82450	1248.46394	536.65373	390.65160	101.00000	2.49246	357.15990	888.46000
1.484	-5.987	348.01120	1248.59575	536.72639	390.70870	101.00000	2.49271	357.34990	888.47000
1.471	-5.489	347.46190	1222.81987	526.10266	390.56320	101.00000	2.49154	356.78980	888.46000
1.485	-4.985	347.77470	1248.55545	536.68430	390.62300	101.00000	2.49265	357.10990	888.46000
1.470	-4.486	348.28490	1223.62680	526.49751	390.69240	100.90000	2.49425	357.62990	888.47000
1.484	-3.982	348.05030	1248.65193	536.75354	390.71780	101.00000	2.49282	357.38990	888.48000
1.470	-3.489	347.84500	1223.33441	526.34378	390.60400	100.90000	2.49279	357.17990	888.47000
1.471	-2.980	347.67600	1223.25978	526.29889	390.58760	101.00000	2.49262	357.00980	888.45000
1.470	-2.476	348.05830	1223.86555	526.57677	390.61350	100.90000	2.49413	357.39990	888.46000
1.470	-1.976	348.04050	1223.48209	526.41948	390.64310	100.90000	2.49344	357.37990	888.45000
1.485	-1.469	347.86350	1248.52011	536.68073	390.59080	100.90000	2.49317	357.20000	888.45000
1.484	-0.958	347.89400	1248.37547	536.62585	390.68750	101.00000	2.49228	357.23000	888.45000
1.470	-0.438	348.10080	1223.04607	526.24687	390.75490	101.00000	2.49248	357.43990	888.42990
1.470	-.080	348.04050	1223.56755	526.45489	390.71090	101.00000	2.49288	357.37990	888.40990
1.470	.487	348.12720	1223.83524	526.57018	390.70900	101.00000	2.49354	357.47000	888.38990
1.470	.997	347.76730	1223.00740	526.20406	390.66580	101.00000	2.49178	357.09990	888.38990
GRADIENT	.00140	-1.95074	-.00012	.01038	-.00012		.00012	-.00878	-.00934

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM049) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1591/0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.492	-6.954	337.58670	1225.16957	526.08295	386.25980	100.40000	2.49730	346.77980	896.75000	1.59060	2033.71001
1.492	-6.486	337.60890	1224.70819	525.90206	386.32030	100.40000	2.49630	346.79980	896.76980	1.58315	2033.71001
1.492	-5.988	337.37350	1224.61957	525.83974	386.24980	100.40000	2.49591	346.55980	896.76000	1.58325	2033.71001
1.492	-5.484	337.58030	1224.73026	525.90746	386.32620	100.40000	2.49598	346.76980	896.76000	1.57113	2033.71001
1.492	-4.991	337.50950	1225.42517	526.17525	386.26830	100.40000	2.49656	346.70000	896.76000	1.55043	2033.67500
1.493	-4.487	337.51760	1225.95140	526.38519	386.22900	100.40000	2.49737	346.71000	896.76000	1.54583	2033.67500
1.493	-3.989	337.48950	1225.61430	526.24854	386.25020	100.40000	2.49676	346.67990	896.75000	1.54625	2033.67500
1.493	-3.484	337.39260	1225.31032	526.11576	386.24510	100.40000	2.49614	346.57980	896.75000	1.54663	2033.67500
1.493	-2.986	337.37180	1225.63667	526.24377	386.21440	100.40000	2.49657	346.55980	896.77980	1.54229	2033.67500
1.492	-2.477	337.60570	1225.89651	526.37372	386.25780	100.40000	2.49747	346.79980	896.76000	1.54984	2033.71001
1.493	-1.978	337.32230	1225.62869	526.23453	386.19290	100.40000	2.49661	346.50980	896.75000	1.54621	2033.71001
1.492	-1.472	337.50930	1225.58655	526.23920	386.25930	100.40000	2.49673	346.70000	896.75000	1.54629	2033.71001
1.493	-964	337.43090	1225.44780	526.17484	386.24000	100.40000	2.49652	346.61990	896.75000	1.55039	2033.74500
1.492	-443	337.48050	1225.98329	525.99689	386.26420	100.40000	2.49643	346.66990	896.74000	1.54748	2033.74500
1.492	-.090	337.62650	1225.80756	526.34048	386.28420	100.40000	2.49712	346.81980	896.70000	1.54210	2033.74500
1.492	.492	337.51880	1225.68941	526.28124	386.25880	100.40000	2.49681	346.71000	896.68990	1.54224	2033.74500
1.493	.995	337.45950	1225.87440	526.34811	386.22780	100.40000	2.49696	346.64990	896.70000	1.53808	2033.74500
GRADIENT	.00560	.00418	.00230	.000161	-.000000	.00001	.00571	-.01107	-.00008	.01544	-.00008
RUN NO.		1607/0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.515	-7.006	327.49950	1228.46080	526.06892	382.70950	101.00000	2.49345	336.52980	905.64990	1.76661	2033.85001
1.514	-6.491	327.53120	1227.91443	525.86137	382.77540	101.00000	2.49244	336.55980	905.62990	1.76298	2033.85001
1.515	-5.987	327.06350	1227.33694	525.56744	382.67800	101.00000	2.49073	336.07980	905.62990	1.75491	2033.88499
1.515	-5.483	326.85060	1226.48643	525.20502	382.67530	101.00000	2.48916	335.85990	905.63990	1.76052	2033.88499
1.515	-4.990	326.87130	1226.06593	525.04510	382.70870	101.00000	2.48868	335.87990	905.61990	1.77000	2033.85001
1.514	-4.492	326.86380	1225.44327	524.80205	382.75630	101.00000	2.48772	335.86990	905.62990	1.77536	2033.85001
1.515	-3.983	327.50510	1228.97913	526.27293	382.61770	101.00000	2.49524	336.53980	905.63990	1.80162	2033.85001
1.515	-3.484	327.26640	1227.24707	525.56490	382.67920	101.00000	2.49225	336.28980	905.63990	1.81321	2033.85001
1.514	-2.986	327.79250	1228.09689	525.97330	382.78370	101.00000	2.49427	336.82980	905.63990	1.81203	2033.88499
1.515	-2.483	327.60160	1229.31401	526.41844	382.61470	101.00000	2.49603	336.63990	905.64990	1.80566	2033.88499
1.514	-1.978	327.50900	1227.84067	525.83163	382.70920	101.00000	2.49353	336.53980	905.63990	1.81237	2033.85001
1.514	-1.471	327.29790	1226.74272	525.37392	382.73540	101.00000	2.49143	336.31980	905.63990	1.81397	2033.88499
1.515	-.962	326.80660	1226.99762	525.39998	382.54910	101.00000	2.49122	335.81980	905.62990	1.80897	2033.88499
1.514	-.448	327.41310	1227.52179	525.69304	382.72290	101.00000	2.49254	336.43990	905.62990	1.79926	2033.85001
1.515	-.095	327.69240	1229.43285	526.47539	382.76860	101.00000	2.49450	336.73000	905.58980	1.75639	2033.92000
1.515	.493	328.00290	1230.26888	526.84549	382.80030	101.00000	2.49626	337.04980	905.57980	1.75523	2033.92000
1.515	1.001	327.87570	1230.14694	526.77943	382.83570	101.20000	2.49531	336.91990	905.57980	1.75388	2033.88499
GRADIENT	.11660	.50932	.21507	.01486	.02297	.00077	.12071	-.00819	-.00013	-.00439	-.00013

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 982

(VCM049) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1622/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	P/C	PREF	SH10 <sup>+3</sup>	PATM
1.542	-6.954	317.73580	1239.92535	528.80431	378.93700	101.30000	2.49171	326.58980	907.51000	1.40182 2033.57001
1.542	-6.491	317.62720	1240.10768	528.85271	378.87740	101.30000	2.49198	326.48000	907.52980	1.40519 2033.57001
1.542	-5.987	317.64770	1239.79625	528.73883	378.90260	101.30000	2.49167	326.50000	907.52980	1.41278 2033.57001
1.542	-5.489	317.58860	1238.69229	528.30750	378.87920	101.30000	2.49165	326.43990	907.48000	1.48822 2033.60500
1.542	-4.990	317.80370	1238.84999	528.40800	378.94210	101.30000	2.49216	326.65990	907.49000	1.48806 2033.57001
1.541	-4.487	317.70530	1238.74762	528.35018	378.89990	101.30000	2.49217	326.55980	907.50000	1.49959 2033.60500
1.541	-3.983	317.62770	1238.62995	528.29099	378.88280	101.30000	2.49189	326.48000	907.49000	1.49972 2033.60500
1.541	-3.485	317.56860	1238.63947	528.28378	378.85570	101.30000	2.49194	326.41990	907.48000	1.50352 2033.60500
1.541	-2.982	317.89230	1238.36826	528.24233	378.98950	101.30000	2.49194	326.75000	907.48000	1.50775 2033.60500
1.541	-2.478	317.74540	1238.37451	528.21661	378.93160	101.30000	2.49189	326.59990	907.47000	1.51156 2033.60500
1.541	-1.978	317.68650	1238.31633	528.18341	378.91060	101.30000	2.49182	326.53980	907.43990	1.51548 2033.60500
1.541	-1.472	317.76590	1237.99849	528.07802	378.96190	101.30000	2.49147	326.61990	907.46000	1.51975 2033.60500
1.541	-962	317.65840	1237.75725	527.96626	378.86740	101.20000	2.49174	326.50980	907.42990	1.52778 2033.60500
1.541	-441	317.62870	1237.95703	528.03670	378.84420	101.20000	2.49194	326.48000	907.39990	1.52365 2033.60500
1.541	.142	317.59910	1237.98163	528.03982	378.83150	101.20000	2.49195	326.45000	907.40990	1.52361 2033.60500
1.541	.478	317.46340	1237.68039	527.90105	378.81030	101.20000	2.49129	326.30980	907.35990	1.52396 2033.60500
1.542	.996	317.36450	1237.99530	528.00078	378.75240	101.20000	2.49161	326.21000	907.33980	1.51968 2033.60500
GRADIENT	-.04586	-.18263	-.07785	-.02219	-.02193	-.00009	-.04720	-.02478	.00565	.00230

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM050) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1576/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000
	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
MACH	ALPHA	1252.67200	1597.02000	315.01050	522.62040	100.50000	2.49423	1262.42000	1305.59000	1.01731 2034 69000
.599	-6.980	1252.29500	1597.07001	315.37890	522.56880	100.50000	2.49563	1262.05000	1305.62000	1.01727 2034 65500
.600	-6.468	1252.19701	1596.91000	315.32500	522.66530	100.60000	2.49473	1261.95000	1305.63000	.98060 2034 62000
.600	-5.967	1252.25600	1596.96001	315.31810	522.66770	100.60000	2.49474	1262.00999	1305.64000	.98057 2034 62000
.600	-5.464	1252.47400	1596.46001	315.53930	522.52810	100.50000	2.49569	1261.23000	1305.67000	1.01499 2034 62000
.600	-4.966	1251.81599	1597.14000	315.83060	522.50510	100.50000	2.49732	1261.58000	1305.71001	.98046 2034 62000
.600	-3.951	1251.49100	1596.66000	315.69380	522.51120	100.50000	2.49642	1261.25000	1305.73000	.97817 2034 62000
.600	-3.448	1251.39101	1597.05000	316.10300	522.46290	100.50000	2.49823	1261.16000	1305.74001	.97536 2034 58501
.601	-2.937	1251.50500	1596.47000	315.38230	522.56250	100.50000	2.49547	1261.84000	1305.75000	.97034 2034 58501
.601	-2.431	1252.08600	1596.87000	315.06810	522.58130	100.50000	2.49353	1261.25000	1305.78000	.96836 2034 58501
.600	-1.912	1251.50500	1595.92999	315.91260	522.48170	100.50000	2.49728	1261.07001	1305.78000	.96532 2034 58501
.601	-1.392	1251.30600	1596.74001	316.24150	522.45830	100.50000	2.49919	1261.55000	1305.80000	.96226 2034 62000
.601	-.855	1251.77600	1597.59000	315.52290	522.53050	100.50000	2.49564	1261.25999	1305.83000	.97315 2034 58501
.600	-.299	1251.50500	1596.47000	315.34790	522.56260	100.50000	2.49501	1261.47000	1305.84000	.98605 2034 58501
.600	.254	1251.18000	1596.47000	315.84030	522.59860	100.60000	2.49684	1261.63000	1305.86000	.99080 2034 62000
.600	.670	1251.86501	1597.20000	315.53270	522.64430	100.60000	2.4975	1262.03000	1305.88000	1.00653 2034 65500
.600	1.102	1252.27100	1597.23000	315.01308	.01362	.01156	-.00009	.04957	.03342	-.00210 .00022
GRADIENT	.04969	.03295								

	RUN NO.	1466/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000
	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
MACH	ALPHA	1341.41000	394.21530	496.78690	100.70000		2.49552	889.92990	1055.75999	3.32993 2038 .36501
.800	-6.986	880.02560	1341.32001	394.41550	496.73320	100.70000	2.49594	889.53980	1055.80000	3.28207 2038 .39999
.800	-6.478	879.63350	1341.37000	394.24710	496.77660	100.70000	2.49556	889.83980	1055.82001	3.21883 2038 .39999
.800	-5.974	879.93550	1341.97000	394.28340	496.82890	100.80000	2.4964	889.34990	1055.84000	3.17318 2038 .39999
.800	-5.470	879.44680	1340.07001	394.13180	496.87180	100.80000	2.49435	889.67930	1055.91000	3.13457 2038 .39999
.800	-4.971	879.77860	1341.14000	394.32860	496.83010	100.80000	2.49494	889.47000	1055.94000	3.09646 2038 .36501
.800	-4.471	879.56540	1341.14000	394.36670	496.81740	100.80000	2.49499	889.35990	1055.97000	3.05161 2038 .36501
.800	-3.969	879.45530	1341.09000	394.13870	496.77390	100.70000	2.49482	889.54980	1056.03000	3.01488 2038 .36501
.800	-3.461	879.64920	1340.96001	394.00810	496.97170	100.70000	2.49436	889.61990	1056.24001	2.85708 2038 .36501
.800	-2.954	879.64840	1341.00999	394.13790	496.85720	100.70000	2.49441	889.53980	1056.28000	2.80820 2038 .33000
.800	-2.449	879.56710	1341.03000	394.24610	496.75320	100.70000	2.49518	889.47000	1056.11000	2.95635 2038 .39999
.800	-1.938	879.60860	1340.98000	394.18120	496.76510	100.70000	2.49496	889.51000	1056.14000	2.93484 2038 .36501
.800	-1.424	879.79910	1341.05000	394.10300	496.78860	100.70000	2.49483	889.70000	1056.19000	2.89188 2038 .36501
.800	-.900	879.72140	1340.85001	394.00810	496.97170	100.70000	2.49436	889.61990	1056.24001	2.85708 2038 .36501
.800	-.362	879.63940	1340.95000	394.13790	496.77320	100.70000	2.49481	889.53980	1056.28000	2.80820 2038 .33000
.800	-.178	879.78050	1340.95000	394.04200	496.79610	100.70000	2.49456	889.67930	1056.33000	2.77391 2038 .33000
.800	.628	879.66970	1340.95000	394.11740	496.77830	100.70000	2.49476	889.56980	1056.39000	2.72655 2038 .36501
.800	1.084	879.80000	1340.98000	394.05080	496.79610	100.70000	2.49462	889.70000	1056.44000	2.71309 2038 .39999
GRADIENT	.02480	-.02574	-.03588	-.02480	-.02574	-.00952	-.01831	-.00002	.02416	-.08677

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 984  
( VCM050 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1500/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
.900	-6. 987	753.03150	1273.17999	426.67700	482.20610	100.60000	2.49560	763.03980	981.53980	4.53586
.900	-6. 472	752.77760	1273.30000	426.91040	482.14650	100.60000	2.49626	762.78980	981.57980	4.56781
.900	-5. 967	752.82890	1273.22000	426.82470	482.25070	100.70000	2.49539	762.83980	981.58980	4.61162
.900	-5. 466	752.58740	1273.22000	426.96870	482.20630	100.70000	2.49571	762.59990	981.60990	4.64450
.900	-4. 970	752.50050	1272.96001	426.84180	482.21850	100.70000	2.49511	762.51000	981.63990	4.70075
.900	-4. 463	752.36330	1272.69000	426.73800	482.13670	100.60000	2.49513	762.36990	981.66990	4.72405
.900	-3. 959	752.50170	1272.85001	426.76540	482.05860	100.50000	2.49596	762.51000	981.68990	4.77959
.900	-3. 459	752.57960	1273.06000	426.86330	481.96410	100.40000	2.49701	762.58980	981.70000	4.84697
.900	-2. 950	753.07250	1273.13000	426.61840	482.04660	100.40000	2.49656	763.07980	981.72000	4.92735
.900	-2. 443	753.72800	1274.52000	427.18310	481.93020	100.30000	2.50008	763.75000	981.75980	4.98022
.900	-1. 934	753.95480	1274.86000	427.28110	481.84890	100.20000	2.50129	763.98000	981.77980	5.01415
.900	-1. 413	753.59740	1274.50999	427.25440	481.73540	100.10000	2.50137	763.61990	981.79980	5.05104
.900	- .887	753.18310	1273.86000	427.05400	481.64380	100.00000	2.50071	763.20000	981.81980	5.10136
.900	- .348	753.49270	1274.05000	427.00020	481.59370	99.89999	2.50141	763.51000	981.83980	5.16082
.900	- .191	753.10330	1273.08000	426.56540	481.71340	100.00000	2.49869	763.10990	981.84990	5.26257
.900	.635	753.03860	1273.37000	426.80320	481.67040	100.00000	2.49956	763.04980	981.87990	5.31088
.900	1. 081	753.19750	1273.53000	426.81860	481.68210	100.00000	2.49979	763.21000	981.88990	5.33512
GRADIENT		.13726	.12975	.00748	-.09753	-.12621	.00090	.13804	-.04142	.10802
										.000000

	RUN NO.	1485/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
1. 100	-7. 003	564.92900	1206.21001	478.50050	450.77980	100.20000	2.49843	575.11990	912.36990	98442
1. 100	-6. 483	564.83790	1206.24001	478.55370	450.75590	100.20000	2.49854	575.02980	912.36990	98442
1. 100	-5. 988	564.88230	1205.87000	478.32100	450.80750	100.20000	2.49768	575.06980	912.37990	98706
1. 100	-5. 481	564.99120	1206.00999	478.35940	450.73490	100.10000	2.49853	575.17990	912.42990	99270
1. 100	-4. 986	564.70190	1205.87000	478.39230	450.668380	100.10000	2.49834	574.88990	912.41990	99270
1. 100	-4. 483	564.73930	1206.12000	478.52290	450.66580	100.10000	2.49890	574.92990	912.46000	99249
1. 100	-3. 989	564.91020	1206.09000	478.43800	450.70800	100.10000	2.49875	575.09990	912.45000	99252
1. 100	-3. 481	564.91210	1205.92000	478.33840	450.72660	100.10000	2.49836	575.02000	912.46000	98732
1. 100	-2. 976	565.01120	1206.00000	478.34570	450.74050	100.10000	2.49850	575.20000	912.48000	98725
1. 100	-2. 479	564.79930	1206.13000	478.50510	450.67850	100.10000	2.49889	574.99000	912.47000	98715
1. 100	-1. 976	564.85230	1205.86000	478.32690	450.71920	100.10000	2.49825	575.03980	912.49000	99271
1. 100	-1. 464	565.01100	1206.05000	478.37500	450.73510	100.10000	2.49861	575.20000	912.49000	99255
1. 100	- .968	564.92090	1206.00999	478.38720	450.63840	100.00000	2.49914	575.10990	912.48000	99258
1. 100	- .460	564.94970	1206.14000	478.45140	450.63110	100.00000	2.49943	575.13990	912.50000	99515
1. 100	.051	564.88090	1206.00999	478.40310	450.70970	100.10000	2.49858	575.06980	912.50000	96095
1. 100	.536	565.04200	1205.94000	478.29860	450.75420	100.10000	2.49834	575.23000	912.51980	96101
1. 100	1. 029	565.03030	1206.10001	478.39620	450.73410	100.10000	2.49872	575.22000	912.53980	97658
GRADIENT		.03835	.00827	-.01034	.00343	-.00548	.00003	.03835	.01485	-.00373

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM050) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1523/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000	
MACH	P	PT	Q (PSF)	T (R)	TT (F)	RN/L	PC	PREF	SH10+3 PATM		
ALPHA											
-6.991	462.37720	1197.45000	505.60380	426.74440	100.40000	2.49659	472.50000	864.41990	1.23455	2035.77499	
-6.474	462.63940	1198.48000	506.66840	426.70820	100.40000	2.49872	472.76980	864.42990	1.23348	2035.74001	
-5.978	462.74170	1198.12000	505.86350	426.77220	100.40000	2.49800	472.86990	864.40990	1.23059	2035.77499	
-5.471	462.73540	1197.81000	505.81740	426.67020	100.40000	2.49730	472.35990	864.43990	1.23418	2035.77499	
-4.973	462.48410	1197.85001	505.78320	426.73170	100.40000	2.49742	472.60990	864.41990	1.22761	2035.77499	
-4.471	462.70290	1197.96001	505.79100	426.77830	100.40000	2.49767	472.82980	864.41990	1.23076	2035.77499	
-3.966	462.37400	1197.91000	505.83760	426.69650	100.40000	2.49753	472.50000	864.42990	1.22755	2035.81000	
-3.462	462.41330	1197.99001	505.86940	426.69870	100.40000	2.49769	472.53980	864.42990	1.22422	2035.77499	
-2.958	462.51250	1198.11000	505.90870	426.71260	100.40000	2.49795	472.63990	864.41990	1.22735	2035.81000	
-2.451	462.56180	1198.17000	505.92820	426.71970	100.40000	2.49808	472.68990	864.42990	1.21757	2035.77499	
-1.948	462.64330	1197.91000	505.77860	426.67660	100.40000	2.49756	472.76980	864.41990	1.21783	2035.77499	
-1.431	462.60060	1198.31000	505.99070	426.71560	100.40000	2.49837	472.73000	864.42990	1.22066	2035.77499	
-9.116	462.45310	1198.00000	505.86600	426.70830	100.40000	2.49772	472.57980	864.40990	1.22097	2035.81000	
-390	462.45360	1197.94000	505.83520	426.71460	100.40000	2.49760	472.57980	864.39990	1.21780	2035.77499	
.145	462.69240	1198.03999	505.83400	426.67320	100.40000	2.49783	472.81980	864.38990	1.21770	2035.77499	
.609	462.40330	1198.03999	505.89700	426.69120	100.40000	2.49779	472.52980	864.39990	1.21770	2035.77499	
1.250	462.49490	1197.72000	505.71480	426.74780	100.40000	2.49715	472.61990	864.39990	1.21803	2035.77499	
1.250	GRADIENT	-.00117	-.00081	-.00015	-.00022	-.00000	-.00000	-.000120	-.000534	-.00207	
RUN NO.		1539/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000	
MACH	P	PT	Q (PSF)	T (R)	TT (F)	RN/L	PC	PREF	SH10+3 PATM		
ALPHA											
-6.992	381.62820	1214.67000	523.69210	402.11230	100.10000	2.49741	391.32980	879.25000	1.21058	2035.17999	
-6.480	381.76220	1215.42000	524.01760	401.93800	99.89999	2.50007	391.47000	879.22000	1.20663	2035.17999	
-5.979	381.68730	1214.72000	523.71290	401.98170	99.89999	2.49873	391.38990	879.22000	1.21053	2035.21500	
-5.471	381.62770	1214.75000	523.72730	402.10450	100.10000	2.49756	391.32980	879.21000	1.20411	2035.21500	
-4.975	382.03980	1215.17000	523.90160	402.20390	100.10000	2.49866	391.79980	879.21000	1.21008	2035.21500	
-4.472	381.73560	1214.89000	523.86440	402.12380	100.10000	2.49789	391.43990	879.21000	1.20716	2035.21500	
-3.973	382.05150	1214.97000	523.81490	402.13940	100.10000	2.49886	391.75980	879.21000	1.21028	2035.21500	
-3.464	381.96290	1214.95000	523.80810	402.04270	99.89999	2.49936	391.66990	879.16990	1.21030	2035.21500	
-2.966	381.66330	1215.39000	524.00630	402.05470	100.10000	2.49875	391.36990	879.16990	1.23249	2035.21500	
-2.460	382.11010	1215.13000	523.88380	402.21360	100.10000	2.49861	391.81980	879.15990	1.22301	2035.17999	
-1.949	381.93580	1214.48000	523.60280	402.22290	100.10000	2.49729	391.63990	879.12990	1.20437	2035.17999	
-1.439	382.05910	1215.36000	523.98540	402.17680	100.10000	2.49899	391.76980	879.12990	1.21632	2035.17999	
-1.400	.921	381.98360	1214.75999	523.72440	402.06710	99.89999	2.49902	391.68990	879.13990	1.20091	2035.17999
-1.400	.399	382.07180	1214.89000	523.77930	402.22490	100.10000	2.49814	391.77980	879.09990	1.20716	2035.21500
-1.400	.130	381.70700	1214.69000	523.69950	402.13400	100.10000	2.49751	391.40990	879.08980	1.21699	2035.17999
-1.400	.600	381.74540	1214.91000	523.79490	402.12480	100.10000	2.49793	391.45000	879.06980	1.22000	2035.17999
1.400	1.059	381.75390	1215.10001	523.87770	402.10940	100.10000	2.49829	391.46000	879.05980	1.20695	2035.17999
GRADIENT	-.02631	-.02923	-.01227	-.00049	-.00011	-.00011	-.02675	-.00008	-.00045	-.00045	

( VCM050 ) ( 04 OCT 91 )  
PAGE 986

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PARAMETRIC DATA

.500	PHI	=	180.000
------	-----	---	---------

BUN NO. 1557/8 RNL = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

	MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	R/N/L	PC	PREF	SH+3	PATM
1.1.450	-6.981	358.81520	1225.98000	528.16600	393.97730	100.00000	2.49910	368.28980	893.20000	1.44545	2035.35500	
1.1.450	-6.463	358.92410	1225.89999	528.13840	394.9570	100.20000	2.49787	368.39990	893.20000	1.44931	2035.32000	
1.1.450	-5.961	358.20680	1226.50999	528.40670	394.19240	100.00000	2.49921	368.68990	893.22000	1.45237	2035.32000	
1.1.450	-5.458	358.64890	1225.74001	528.05790	393.87670	99.89999	2.49911	368.11990	893.18990	1.45329	2035.35500	
1.1.450	-4.955	358.72970	1225.37000	527.90820	394.07690	100.10000	2.49735	368.20000	893.18990	1.45373	2035.39000	
1.1.450	-4.450	358.94290	1226.07001	528.21020	394.07960	100.10000	2.49878	368.41990	893.18990	1.44911	2035.35500	
1.1.450	-3.950	358.93120	1226.42000	528.35500	394.04370	100.10000	2.49938	368.40990	893.18990	1.44870	2035.35500	
1.1.450	-3.448	359.00150	1226.16000	528.25070	394.01930	100.00000	2.49959	368.48000	893.17990	1.44901	2035.35500	
1.1.450	-2.937	358.82860	1225.30000	528.44800	394.11450	100.10000	2.49731	368.29980	893.20000	1.45003	2035.32000	
1.1.450	-2.426	359.03100	1226.19000	528.26440	393.95530	99.89999	2.50027	368.50980	893.18990	1.41164	2035.32000	
1.1.450	-1.907	358.96320	1226.00000	528.18210	394.09230	100.10000	2.49868	368.43990	893.15990	1.41186	2035.32000	
1.1.450	-1.390	358.95190	1226.22000	528.27290	393.92770	99.89999	2.50025	368.42990	893.16990	1.41900	2035.35500	
1.1.450	-0.856	358.69820	1225.72000	528.05200	394.03490	100.10000	2.49793	368.16990	893.15990	1.43823	2035.35500	
1.1.450	-0.307	359.05180	1225.99001	528.18240	394.12110	100.10000	2.49874	368.52980	893.14990	1.41556	2035.35500	
1.1.449	-0.240	359.02470	1225.50999	527.98120	394.15670	100.10000	2.49787	368.50000	893.13990	1.40506	2035.35500	
1.1.450	-0.659	359.04960	1226.39999	528.35280	394.08280	100.10000	2.49946	368.52980	893.12990	1.40771	2035.35500	
1.1.449	1.098	359.03440	1225.52000	527.98610	394.01780	99.89999	2.49909	368.50980	893.12990	1.40872	2035.35500	
GRADIENT		0.2723	-0.00819	-0.00203	-0.00283	-0.00916	-0.00007	.02757	-.01128	-.00825	-.00012	

RUN NO.: 1642 / O RN/L = 2.49 GRADIENT INTERVAL = -5.00 / 5.00

	MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
-6	1.470	-.982	348.12820	1223.58353	526.46773	390.72630	101.00000	2.49321	357.47000	889.05980	2031.8900	
-6	1.471	-.469	347.56080	1222.96843	526.17095	390.60690	101.00000	2.49143	356.88990	889.09990	2031.8900	
-5	1.471	.968	347.95830	1224.23398	526.71880	390.61570	101.00000	2.49491	357.29980	889.13990	2031.8900	
-5	1.470	.02050	348.12233	59441	526.46354	390.70190	101.00000	2.49291	357.35990	889.18990	2031.8900	
-4	1.470	.967	347.78560	1223.37560	526.35503	390.58030	100.90000	2.49281	357.11990	889.22000	2031.8550	
-4	1.471	.458	347.88090	1224.01306	526.62257	390.62260	101.00000	2.49342	357.22000	889.24000	2031.8550	
-3	1.470	.957	348.05030	1223.40744	526.38992	390.71680	101.00000	2.49284	357.38990	889.25000	2031.8200	
-3	1.470	.451	348.30540	1223.66255	526.51462	390.78420	101.00000	2.49338	357.64990	889.26000	2031.8550	
-2	1.470	.941	348.09810	1223.81979	526.56134	390.70680	101.00000	2.49337	357.43990	889.29980	2031.8550	
-2	1.470	.436	347.88530	1223.20996	526.29674	390.70460	101.00000	2.49189	357.22000	889.30980	2031.8200	
-1	1.470	.920	347.91140	1223.84128	526.55544	390.64870	101.00000	2.49314	357.25000	889.31980	2031.8200	
-1	1.470	.399	347.99320	1223.23657	526.31585	390.66240	100.90000	2.49273	357.32980	889.31980	2031.8550	
-1	1.470	.872	348.10010	1223.42870	526.40295	390.74370	101.00000	2.49268	357.43990	889.34990	2031.8200	
-1	1.470	-.328	348.03830	1224.07118	526.65956	390.66940	101.00000	2.49365	357.37990	889.34990	2031.8200	
-1	1.470	.219	348.02100	1223.61845	526.47365	390.71190	101.00000	2.49272	357.35990	889.36990	2031.8200	
-1	1.470	.650	348.02030	1223.82050	526.55566	390.69900	101.00000	2.49296	357.35990	889.37990	2031.7850	
1	1.470	347.89430	1223.40358	526.37539	390.69580	101.00000	2.49212	357.23000	889.39990	2031.7850		
1	1.470	.096	347.00598	.00639	-.00311	.00793	.00536	-.00007	.00595	.02829	-.00158	.0097

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM050) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	BETA = 2.50	GRADIENT INTERVAL = -5.00/ 5.00	PREF	PC	PATM
1.492	-6.987	337.48950	1225.52194	526.21100	386.25290	100.40000	2.49671	346.67990	896.67990	1.55030	2033.74500	
1.493	-6.470	337.51860	1225.87338	526.35424	386.25340	100.40000	2.49691	346.71000	896.70000	1.53419	2033.74500	
1.493	-5.968	337.52860	1225.86443	526.35188	386.25760	100.40000	2.49690	346.72000	896.70000	1.53420	2033.74500	
1.492	-5.466	337.62550	1225.87866	526.36855	386.26610	100.40000	2.49746	346.81980	896.70000	1.54986	2033.71001	
1.492	-4.964	337.48970	1225.57494	526.23266	386.25390	100.40000	2.49669	346.67990	896.68990	1.54630	2033.71001	
1.493	-4.460	337.41110	1225.40282	526.15507	386.23170	100.40000	2.49653	346.59990	896.67990	1.55439	2033.71001	
1.492	-3.960	337.53930	1225.30579	526.13149	386.28340	100.40000	2.49649	346.73000	896.67990	1.55453	2033.71001	
1.493	-3.453	337.35300	1225.24989	526.08743	386.22610	100.40000	2.49621	346.53980	896.67990	1.55458	2033.71001	
1.492	-2.949	337.74290	1225.98759	526.42551	386.29570	100.40000	2.49777	346.93990	896.67990	1.54974	2033.71001	
1.492	-2.440	337.68290	1226.20471	526.50574	386.25020	100.40000	2.49819	346.87990	896.66990	1.55339	2033.71001	
1.493	-1.925	337.59370	1226.28134	526.52624	386.20780	100.40000	2.49834	346.78980	896.66990	1.55724	2033.71001	
1.492	-1.405	337.90720	1226.63232	526.70036	386.29220	100.40000	2.49904	347.10990	896.68990	1.54894	2033.71001	
1.492	-.882	337.94560	1226.95827	526.83503	386.28710	100.40000	2.49943	347.14990	896.68990	1.54068	2033.67500	
1.493	-.341	337.94430	1227.30612	526.97310	386.26070	100.40000	2.49992	347.14990	896.65990	1.53633	2033.67500	
1.493	.206	338.06100	1227.78899	527.17822	386.23220	100.40000	2.50055	347.26980	896.65990	1.52407	2033.71001	
1.492	.634	338.19700	1227.88655	527.23269	386.28740	100.40000	2.50128	347.40990	896.65990	1.53954	2033.71001	
1.493	1.089	337.84370	1227.88689	527.19304	386.17460	100.40000	2.50082	347.04980	896.65990	1.53559	2033.71001	
GRADIENT	.11393	.48241	.20489	-.00105	-.00000	.00086	-.11786	-.00412	-.00367	-.00194		

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	BETA = 2.49	GRADIENT INTERVAL = -5.00/ 5.00	PREF	PC	PATM
1.515	-6.987	327.22780	1228.49875	526.04060	382.81840	101.20000	2.49071	336.25000	905.57980	1.71403	2033.92000	
1.515	-6.470	327.83980	1230.02811	526.72563	382.89750	101.20000	2.49387	336.87990	905.58980	1.70766	2033.88499	
1.515	-5.968	328.01070	1231.15424	527.19004	382.82640	101.20000	2.49652	337.05980	905.57980	1.72771	2033.88499	
1.516	-5.466	327.78520	1231.12808	527.14621	382.81930	101.30000	2.49564	336.82980	905.58980	1.72771	2033.92000	
1.515	-4.968	327.36430	1228.6183	526.06183	382.91650	101.30000	2.49059	336.38990	905.58980	1.72704	2033.88499	
1.515	-4.465	327.08670	1226.75404	525.34294	382.97220	101.30000	2.48742	336.09990	905.58980	1.73384	2033.88499	
1.515	-3.955	326.54200	1225.66231	524.83777	382.88840	101.30000	2.48486	335.53980	905.58980	1.73095	2033.92000	
1.516	-3.454	327.09030	1228.66769	526.08491	382.83540	101.30000	2.49004	336.10990	905.58980	1.70516	2033.95500	
1.514	-2.949	327.80570	1228.98808	526.31584	383.07010	101.30000	2.49103	336.83980	905.58980	1.69199	2033.92000	
1.516	-2.440	327.06150	1228.39154	525.97462	382.83910	101.30000	2.48975	336.07980	905.57980	1.71415	2033.92000	
1.515	-1.930	327.10210	1228.03532	525.84239	382.88530	101.30000	2.48919	336.11990	905.58980	1.71466	2033.92000	
1.516	-1.407	327.14040	1228.42979	526.00059	382.87430	101.30000	2.48969	336.15990	905.57980	1.70550	2033.92000	
1.516	-.878	327.49540	1230.35374	526.80051	382.82350	101.30000	2.49335	336.52980	905.58980	1.70286	2033.95500	
1.516	-.340	327.89450	1231.13191	527.16260	382.88990	101.30000	2.49511	336.93990	905.58980	1.70183	2033.88499	
1.515	.205	327.29000	1227.77385	525.76820	383.05320	101.40000	2.48813	336.30980	905.58980	1.70645	2033.88499	
1.516	.644	326.33400	1226.76633	525.23260	382.77390	101.30000	2.48545	335.32980	905.55980	1.68633	2033.95500	
1.516	1.094	326.69380	1227.48749	525.56674	382.89580	101.40000	2.48658	335.70000	905.58980	1.68964	2033.92000	
GRADIENT	-.03004	.13790	.04876	-.00783	-.00105	-.00000	-.03040	-.00162	-.00040	-.000367	-.00288	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 988  
( VCM050 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.542	-6.986	317.22090	1237.55357	527.80754	378.78270	101.20000	2.48991	326.05980	907.30980	1.48955 2033.57001
1.542	-6.469	317.30910	1237.41154	527.77065	378.81640	101.20000	2.48996	326.14990	907.30980	1.49735 2033.57001
1.541	-5.968	317.17210	1237.44939	527.75864	378.76950	101.20000	2.48978	326.00980	907.29980	1.49347 2033.60500
1.542	-5.466	317.39700	1237.51195	527.82511	378.84370	101.20000	2.49014	326.24000	907.29980	1.49344 2033.64000
1.541	-4.968	317.45530	1237.73351	527.92079	378.84990	101.20000	2.49048	326.29980	907.27980	1.49837 2033.64000
1.541	-4.465	317.30660	1238.21471	528.07404	378.75420	101.20000	2.49112	326.14990	907.29980	1.48875 2033.60500
1.542	-3.954	317.36570	1238.07822	528.03357	378.78220	101.20000	2.49106	326.21000	907.27980	1.49273 2033.60500
1.542	-3.453	317.66700	1238.74254	528.34178	378.83470	101.20000	2.49242	326.51980	907.26980	1.48817 2033.60500
1.541	-2.950	317.80370	1238.81123	528.39313	378.87700	101.20000	2.49270	326.65990	907.26000	1.48811 2033.60500
1.541	-2.440	317.82180	1239.33641	528.59587	378.84180	101.20000	2.49351	326.67990	907.25000	1.48368 2033.60500
1.542	-1.925	317.76270	1239.50142	528.64758	378.81640	101.20000	2.49352	326.61990	907.24000	1.47592 2033.60500
1.542	-1.412	317.79100	1239.82513	528.77484	378.79760	101.20000	2.49410	326.64990	907.22000	1.47553 2033.60500
1.541	-882	318.06470	1239.89433	528.85283	378.88820	101.20000	2.49453	326.92990	907.23000	1.47550 2033.60500
1.542	-339	317.96610	1240.07352	528.90182	378.83740	101.20000	2.49472	326.82980	907.20000	1.47526 2033.60500
1.542	.206	317.98540	1240.22160	528.96138	378.83110	101.20000	2.49499	326.84990	907.20000	1.47508 2033.64000
1.541	.642	318.13230	1240.07928	528.93533	378.88550	101.20000	2.49511	327.00000	907.15990	1.48283 2033.64000
1.542	1.094	317.96560	1240.05476	528.89423	378.82350	101.20000	2.49498	326.82980	907.14990	1.48661 2033.60500
		GRADIENT	.11891	.41396	.17900	.00731	-.000000	.00079	.12291	-.02251 .00117

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 989

(VCM051) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1577 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.600	-6.960	1252.35400	1597.17000	315.41500	522.93950	100.90000	2.49357	1262.11000	1305.96001	.99867	2034.69000
.600	-6.452	1252.35600	1597.03000	315.29470	522.95290	100.90000	2.49302	1262.11000	1305.97000	.97281	2034.65500
.600	-5.945	1251.59000	1596.75999	315.69650	522.88670	100.90000	2.49424	1261.35001	1305.99001	.97041	2034.72501
.600	-5.440	1252.23500	1597.02000	315.38650	522.93950	100.90000	2.49334	1261.99001	1305.99001	.96770	2034.72501
.600	-4.938	1251.82201	1596.82001	315.55640	522.90890	100.90000	2.49379	1261.58000	1306.00999	.96527	2034.69000
.600	-4.428	1251.75000	1596.87000	315.65750	522.70900	100.70000	2.49533	1261.50999	1306.00999	.96270	2034.72501
.600	-3.920	1251.83299	1597.30000	315.95090	522.67870	100.70000	2.49676	1261.60001	1306.02000	.95737	2034.69000
.601	-3.411	1251.84599	1597.67000	316.25120	522.27270	100.30000	2.50043	1261.62000	1306.05000	.96222	2034.72501
.600	-2.900	1252.04700	1596.77000	315.33010	522.19410	100.10000	2.49474	1261.80000	1306.06000	.96022	2034.72501
.601	-2.382	1251.62199	1597.00000	316.04000	522.10100	100.00000	2.50098	1261.39000	1306.05000	.96759	2034.72501
.600	-1.863	1251.99100	1597.03999	315.60330	521.78910	99.70000	2.50097	1261.75000	1306.06000	.97024	2034.72501
.601	-1.330	1251.52400	1597.52000	316.38940	521.59520	99.59999	2.50480	1261.30000	1306.07001	.98800	2034.72501
.600	-.798	1251.43800	1596.73000	315.79570	521.47240	99.39999	2.50312	1261.20000	1306.07001	.99109	2034.72501
.601	-.265	1251.37601	1597.28999	316.31710	521.31930	99.30000	2.50606	1261.14999	1306.06000	.99074	2034.72501
.601	.227	1251.49300	1597.56000	316.44850	521.30810	99.30000	2.50677	1261.27000	1306.09000	.99580	2034.69000
.601	.704	1251.66200	1597.20000	316.00680	521.36180	99.30000	2.50486	1261.42999	1306.08000	.99865	2034.69000
.600	1.185	1251.86099	1596.91000	315.60030	521.50590	99.39999	2.50256	1261.62000	1306.08000	1.00146	2034.69000
.600	GRADIENT	-.04674	.02519	.05951	-.27139	-.28244	.00185	-.04554	.01192	.00768	-.00183

RUN NO. 1467 / 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.799	-6.976	880.40280	1341.19000	393.79610	496.87110	100.70000	2.49418	890.29980	1056.59000	2.60769	2038.39999
.800	-6.457	880.06910	1341.23000	394.05270	496.81300	100.70000	2.49490	889.97000	1056.61000	2.59476	2038.39999
.800	-5.959	879.76760	1341.14000	394.19140	496.77390	100.70000	2.49516	889.66990	1056.64000	2.48799	2038.39999
.800	-5.453	879.78980	1340.99001	394.06490	496.79350	100.70000	2.49466	889.68990	1056.69000	2.52554	2038.39999
.800	-4.956	879.66800	1341.06000	394.20000	496.85500	100.80000	2.49452	889.56980	1056.73000	2.49431	2038.36501
.800	-4.451	879.57760	1341.03000	394.23930	496.66630	100.60000	2.49574	889.48000	1056.78000	2.46975	2038.39999
.800	-3.942	879.78810	1341.10001	394.14750	496.87010	100.80000	2.49443	889.68900	1056.81000	2.45130	2038.39999
.800	-3.439	879.72880	1341.02000	394.12870	496.86890	100.80000	2.49429	889.62990	1056.85001	2.42721	2038.39999
.800	-2.925	879.76150	1340.86000	393.98800	496.80250	100.70000	2.49432	889.65990	1056.86000	2.40947	2038.39999
.800	-2.415	879.50780	1340.94000	394.21970	496.75320	100.70000	2.49501	889.40990	1056.89999	2.38547	2038.36501
.800	-1.900	879.76680	1341.20000	394.23630	496.85620	100.80000	2.49477	889.66990	1056.94000	2.34380	2038.39999
.800	-1.383	879.67990	1340.89999	394.07320	496.78520	100.70000	2.49459	889.57980	1056.99001	2.32687	2038.39999
.800	-.857	879.37740	1340.89000	394.27120	496.73730	100.70000	2.49509	889.27980	1057.02000	2.31531	2038.39999
.800	-.339	879.31520	1341.02000	394.41020	496.71360	100.70000	2.49560	889.22000	1057.06000	2.29210	2038.39999
.800	.151	879.44480	1341.13000	394.40330	496.72290	100.70000	2.49570	889.34990	1057.09000	2.33809	2038.39999
.799	.636	880.32590	1340.95000	393.67090	496.88400	100.70000	2.49359	890.22000	1057.12000	2.33259	2038.36501
.800	1.136	879.98240	1340.94000	393.89700	496.91850	100.80000	2.49360	889.87990	1057.14000	2.30370	2038.36501
.800	GRADIENT	.02525	-.01053	-.02499	.00320	-.00223	-.024483	-.00006	.02483	-.03167	-.00150

(VCMM051) ( 04 OCT 91 ) PAGE 990

PARAMETRIC DATA

BETA = -

	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
ALPHA	JACH									
-6.972	753.95460	1274.89999	427.30960	481.50020	99.80000	2.50371	763.98000	981.97000	5.20596	2036.64999
-6.451	753.33110	1274.07001	427.11010	481.38990	99.70000	2.50283	763.34990	981.99000	5.22116	2036.64999
-5.951	751.49150	1271.62000	426.52150	481.31840	99.70000	2.49853	761.49000	981.98000	5.12244	2036.61500
-5.448	752.07320	1273.50999	426.78690	481.32860	99.70000	2.50020	762.07980	982.00980	5.07095	2036.64999
-4.948	753.02340	1273.72000	427.05250	481.37160	99.70000	2.50227	763.03980	982.03980	5.00688	2036.64999
-4.442	753.88180	1275.03999	427.44900	481.38570	99.70000	2.50476	763.90990	982.04980	4.96647	2036.68500
-3.937	752.59470	1272.70000	426.60720	481.31740	99.59999	2.50062	762.59990	982.05980	5.03456	2036.72000
-3.426	751.39840	1271.07001	426.19920	481.18870	99.50000	2.49830	761.38990	982.05980	4.97039	2036.68500
-2.918	752.69600	1271.96001	426.45260	481.20260	99.50000	2.49995	762.00000	982.05980	4.86265	2036.64999
-2.406	752.12730	3.36000	427.00020	481.17850	99.50000	2.50287	762.71000	982.07980	4.77766	2036.64999
-1.893	753.69480	1274.71001	427.33330	481.21510	99.50000	2.50526	763.72000	982.12990	4.66105	2036.64999
-1.371	753.86840	1275.27000	427.64470	481.18650	99.50000	2.50657	763.89990	982.14990	4.59325	2036.68500
-0.845	753.54000	1274.25999	427.11650	481.23540	99.50000	2.50423	763.55980	982.16990	4.51053	2036.64999
-0.325	753.09130	1273.20000	426.65500	481.26810	99.50000	2.50192	763.17990	982.17990	4.19313	2036.61500
-0.165	752.86330	1272.95000	426.61910	481.16720	99.39999	2.50211	762.86990	982.15990	4.15407	2036.58000
-0.090	752.67140	1272.99001	426.76070	481.12790	99.39999	2.50247	762.67990	982.17990	4.14402	2036.61500
1.140	752.70390	1272.81000	426.61770	481.23930	99.50000	2.50135	762.71000	982.18990	4.13471	2036.61500
GRADIENT	0.02733	-0.01800	-0.02862	-0.02550	-0.03769	-0.00013	0.02688	-0.02684	-0.17337	-0.01399

RUN NO. 1486 / 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 991  
(VCM051) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1524/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
1.250	-6.979	462.67260	1198.03999	505.83810	426.68580	100.30000	2.49841	472.79980	864.38990
-6.462	462.51170	1198.22000	505.96460	426.62520	100.30000	2.49876	472.63990	864.39990	1.21430
1.250	-5.961	462.52170	1198.19000	505.94700	426.70700	100.40000	2.49811	472.64990	864.39990
1.250	-5.457	462.37450	1197.86000	505.81230	426.62570	100.30000	2.49801	472.50000	864.39990
1.250	-4.952	462.48660	1197.49001	505.60010	426.69290	100.30000	2.49727	472.60990	864.39990
1.250	-4.456	462.71070	1198.27000	505.94650	426.67260	100.30000	2.49889	472.83980	864.38990
1.250	-3.950	462.80830	1198.56000	506.07200	426.74490	100.40000	2.49890	472.93990	864.40990
1.250	-3.440	462.44430	1197.84000	505.78660	426.72220	100.40000	2.49739	472.56980	864.37990
1.250	-2.933	462.47630	1197.55000	505.63280	426.68410	100.30000	2.49739	472.59990	864.38990
1.250	-2.428	462.76000	1198.35001	505.97610	426.67750	100.30000	2.49906	472.88990	864.39990
1.250	-1.912	462.75850	1198.58000	506.09300	426.72970	100.40000	2.49894	472.88990	864.39990
1.250	-1.403	462.56300	1198.00000	505.84180	426.66110	100.30000	2.49832	472.68990	864.39990
1.250	-885	462.40410	1197.92000	505.83590	426.70360	100.40000	2.49755	472.52980	864.37990
1.250	-369	462.53490	1197.73000	505.71120	426.68120	100.30000	2.49777	472.65990	864.39990
1.250	.116	462.52440	1197.82001	505.75900	426.66920	100.30000	2.49795	472.64990	864.39990
1.250	.605	462.85910	1198.42000	505.99000	426.69650	100.30000	2.49921	472.99000	864.36990
1.250	1.105	462.70040	1198.31000	505.96870	426.66580	100.30000	2.49897	472.82980	864.36990
GRADIENT	.00859	.02943	.01301	-.00485	-.00540	.00009	.00881	-.000303	-.00995

RUN NO.	1540/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
1.400	-6.981	382.04080	1215.14000	523.88960	402.19190	100.10000	2.49857	391.75000	878.98000
1.400	-6.465	381.72660	1214.78000	523.73850	401.98780	99.89999	2.49887	391.42990	878.98000
1.400	-5.962	381.84160	1215.37000	523.99410	401.96660	99.89999	2.50003	391.54980	878.99000
1.400	-5.459	381.92430	1214.74001	523.71680	402.19480	100.10000	2.49776	391.62990	878.96000
1.400	-4.960	381.86180	1215.27000	523.95000	402.12570	100.10000	2.49868	391.56980	878.96000
1.400	-4.458	381.79390	1215.07001	523.86380	401.98070	99.89999	2.49945	391.50000	878.96000
1.400	-3.954	381.70750	1214.66000	523.68630	401.9340	99.89999	2.49864	391.40990	878.96000
1.400	-3.445	381.84590	1214.66000	523.68360	402.03520	99.89999	2.49874	391.54980	878.95000
1.400	-2.939	381.78980	1215.75999	524.16580	401.91410	99.89999	2.50071	391.50000	878.93990
1.400	-2.434	381.79300	1215.22000	523.92940	401.96610	99.89999	2.49972	391.50000	878.90990
1.400	-1.925	381.68730	1214.70000	523.70410	402.12720	100.10000	2.49751	391.38990	878.92990
1.400	-1.409	381.75630	1214.73000	523.71580	402.00150	99.89999	2.49880	391.46000	878.90990
1.400	-.893	382.04960	1215.28999	523.95510	402.10860	100.00000	2.49945	391.75980	878.90990
1.400	-.383	381.88430	1214.84000	523.76150	402.02950	99.89999	2.49910	391.58980	878.87990
1.399	.104	382.17090	1214.86000	523.76420	402.11380	99.89999	2.49934	391.87990	878.87990
1.400	.595	381.91090	1215.32001	523.97070	402.06420	100.00000	2.49940	391.61990	878.86990
1.400	1.095	381.57840	1214.72000	523.71510	402.09250	100.10000	2.49747	391.27980	878.84990
GRADIENT	.01473	-.02324	-.01048	-.01203	.01203	-.00008	.01476	-.01847	-.00860

MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.20691	2035	1.7999	1.20727	2035	1.7999	1.21309	2035	1.4500	1.22340	2035
1.20691	2035	1.7999	1.20727	2035	1.7999	1.21138	2035	1.4500	1.22611	2035
1.20691	2035	1.7999	1.20727	2035	1.7999	1.22307	2035	1.4500	1.22325	2035
1.20691	2035	1.7999	1.20727	2035	1.7999	1.16639	2035	1.4500	1.17579	2035
1.20691	2035	1.7999	1.20727	2035	1.7999	1.1761	2035	1.4500	1.16902	2035
1.20691	2035	1.7999	1.20727	2035	1.7999	1.16952	2035	1.4500	1.16952	2035

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 992  
(VCM051) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1558/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	
P	PT	Q(PSF)	T(R)	TT(F)		
ALPHA	358.91190	1226.34000	528.32080	394.04490	100.10000	
1.450	-6.962	359.00270	1225.96001	528.16750	394.03810	100.00000
1.450	-6.444	358.83620	1225.75000	528.07180	394.14580	100.20000
1.450	-5.941	359.34590	1226.27000	528.31370	394.04660	99.89999
1.449	-5.435	358.96630	1225.36000	527.91600	394.0180	100.00000
1.449	-4.929	358.83350	1226.24001	528.27510	393.95920	100.00000
1.450	-4.430	358.42090	1226.00000	528.15410	393.78120	99.89999
1.451	-3.918	358.87620	1225.63000	528.02370	394.02860	100.00000
1.450	-3.408	359.73170	1226.05000	528.24120	394.25830	100.00000
1.448	-2.897	358.75730	1225.73000	528.05930	393.98220	100.00000
1.450	-2.380	359.12960	1226.14000	528.24880	394.06130	100.00000
1.450	-1.862	358.50150	1225.67000	528.02100	393.90750	100.00000
1.451	-1.337	358.97220	1226.13000	528.23660	394.01290	100.00000
1.450	-806	358.78740	1225.67000	528.03590	393.99710	100.00000
1.450	-276	359.00150	1226.17000	528.25460	394.01830	100.00000
1.450	.215	359.02290	1225.84000	528.11870	394.12570	100.10000
1.450	.693	359.09990	1226.23000	528.28470	394.11400	100.10000
1.450	1.173	GRADIENT .02130	.04370	.01930	.01389	.01595

RUN NO.	1643/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00						
P	PT	Q(PSF)	T(R)	TT(F)							
ALPHA	526.76445	1224.30037	390.65500	100.90000	2.49419	357.51980	PC	PREF	SH10+3	PATM	
1.470	-6.969	526.41410	1223.45688	390.72170	100.90000	2.49266	357.48000	889.39990	889.39990	1.31553	2031.75000
1.470	-6.446	526.34752	1224.34752	390.70680	101.00000	2.49351	357.46000	889.42990	889.42990	1.31645	2031.75000
1.470	-5.944	526.60017	1223.99844	390.58590	101.00000	2.49265	357.00980	889.45000	889.45000	1.31579	2031.75000
1.471	-5.444	526.20029	1222.96109	390.63770	100.90000	2.49292	357.28980	889.43990	889.43990	1.35472	2031.71500
1.470	-4.938	526.88066	1248.85774	390.66850	100.90000	2.49387	357.50980	889.43990	889.43990	.00000	2031.71500
1.484	-4.435	526.16750	1223.15565	390.65140	100.90000	2.49294	357.32980	889.45000	889.45000	1.34411	2031.71500
1.470	-3.928	347.99270	1223.07867	526.28278	390.73240	101.00000	2.49303	357.46000	889.45000	1.34376	2031.71500
1.470	-3.420	348.11890	1223.48454	526.42659	390.71310	101.00000	2.49373	357.50980	889.46000	1.34335	2031.67999
1.470	-2.905	348.16630	1223.86215	526.58438	390.75270	100.90000	2.49338	357.26980	889.46000	1.34380	2031.64500
1.470	-2.394	347.93210	1223.43161	526.38970	390.60570	100.90000	2.49425	357.23000	889.47000	1.32919	2031.64500
1.470	-1.873	348.35600	1223.31891	526.37901	390.82670	101.00000	2.49293	357.70000	889.49000	1.34398	2031.67999
1.469	-1.354	348.00270	1223.07867	526.25234	390.66190	100.90000	2.49281	357.33980	889.47000	1.34420	2031.71500
1.470	-3.420	348.01980	1223.89171	526.58451	390.68630	101.00000	2.49320	357.35990	889.46000	1.32956	2031.71500
1.470	-2.905	348.31710	1223.42516	526.41885	390.75270	100.90000	2.49333	357.65990	889.48000	1.33354	2031.67999
1.469	-2.394	347.89010	1224.20657	526.70218	390.54420	100.90000	2.49425	357.23000	889.47000	1.32919	2031.64500
1.471	-1.94	347.99220	1223.40247	526.38264	390.64670	100.90000	2.49303	357.32980	889.46000	1.33352	2031.64500
1.470	.675	348.02810	1224.37152	526.78077	390.59300	100.90000	2.49431	357.36990	889.50000	1.31882	2031.64500
1.470	1.158	GRADIENT -.00487	.1.23793	-.50909	-.00789	-.00321	.00470	.00686	.00009	.06805	-.01091

RUN NO.	1643/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00						
P	PT	Q(PSF)	T(R)	TT(F)							
ALPHA	526.76445	1224.30037	390.65500	100.90000	2.49266	357.48000	PC	PREF	SH10+3	PATM	
1.470	-6.969	526.41410	1223.45688	390.72170	100.90000	2.49351	357.46000	889.42990	889.42990	1.31209	2031.75000
1.470	-5.944	526.34752	1224.34752	390.70680	101.00000	2.49265	357.00980	889.45000	889.45000	1.31579	2031.75000
1.471	-5.444	526.60017	1223.99844	390.58590	101.00000	2.49292	357.28980	889.43990	889.43990	1.35472	2031.71500
1.470	-4.938	526.20029	1222.96109	390.63770	100.90000	2.49387	357.50980	889.43990	889.43990	.00000	2031.71500
1.484	-4.435	526.88066	1248.85774	390.66850	100.90000	2.49294	357.32980	889.45000	889.45000	1.34411	2031.71500
1.470	-3.928	347.99270	1223.07867	526.28278	390.73240	101.00000	2.49303	357.46000	889.45000	1.34376	2031.71500
1.470	-3.420	348.01980	1223.89171	526.58451	390.68630	101.00000	2.49320	357.35990	889.46000	1.32956	2031.71500
1.470	-2.905	348.31710	1223.42516	526.41885	390.75270	100.90000	2.49333	357.65990	889.48000	1.33354	2031.67999
1.469	-2.394	347.93210	1224.20657	526.70218	390.54420	100.90000	2.49425	357.23000	889.47000	1.32919	2031.64500
1.471	-1.94	347.89010	1224.37152	526.38264	390.64670	100.90000	2.49303	357.32980	889.46000	1.33352	2031.64500
1.470	.675	347.99220	1223.40247	526.78077	390.59300	100.90000	2.49431	357.36990	889.50000	1.31882	2031.64500
1.470	1.158	GRADIENT -.00487	.1.23793	-.50909	-.00789	-.00321	.00470	.00686	.00009	.06805	-.01091

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM051) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1593/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	1.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATT
1.493	-6.971	337.91380	1227.79771	527.16441	386.22850	100.40000	2.50031	347.11990	896.64990	1.52016 2033.71001
1.493	-6.453	338.04150	1227.85895	527.20344	386.26590	100.40000	2.50054	347.25000	896.64990	1.52010 2033.67500
1.493	-5.951	337.98170	1227.97121	527.24129	386.23560	100.40000	2.50068	347.18990	896.65990	1.51996 2033.67500
1.493	-5.446	338.04100	1227.73157	527.15343	386.32930	100.50000	2.50085	347.25000	896.65990	1.53190 2033.64000
1.493	-4.946	337.99150	1227.70042	527.13512	386.30420	100.50000	2.50116	347.20000	896.65990	1.53975 2033.67500
1.493	-4.444	338.10840	1228.03925	527.28358	386.31840	100.50000	2.50075	347.31980	896.65990	1.53542 2033.71001
1.493	-3.931	338.05930	1228.23413	527.35471	386.30690	100.50000	2.50061	347.26980	896.64990	1.51964 2033.71001
1.492	-3.419	338.28540	1227.99660	527.28661	386.38160	100.50000	2.50085	347.50000	896.64990	1.53550 2033.67500
1.493	-2.915	337.94040	1228.23024	527.23024	386.24490	100.50000	2.50091	347.14990	896.65990	1.5316 2033.67500
1.492	-2.400	338.19780	1227.80161	527.19894	386.36990	100.50000	2.50043	347.40990	896.63990	1.53573 2033.64000
1.493	-1.881	338.03200	1227.73021	527.15112	386.34330	100.50000	2.49971	347.24000	896.64990	1.52026 2033.67500
1.493	-1.364	337.98340	1227.58498	527.08804	386.33450	100.50000	2.49952	347.18990	896.64990	1.52431 2033.67500
1.492	-8.833	337.94530	1227.02724	526.86196	386.34960	100.50000	2.49895	347.14990	896.61990	1.54059 2033.67500
1.493	-3.110	337.87820	1227.02065	526.85073	386.36160	100.50000	2.49823	347.07980	896.63990	1.51727 2033.64000
1.492	-1.79	337.70430	1226.36525	526.36245	386.36280	100.50000	2.49692	346.8990	896.61990	1.51806 2033.64000
1.492	.661	337.74460	1226.12318	526.47928	386.39820	100.50000	2.49654	346.93990	896.61990	1.51837 2033.64000
1.493	1.147	337.58790	1225.98071	526.40392	386.35820	100.50000	2.49614	346.77980	896.61990	1.51853 2033.67500
GRADIENT	-.07604	-.35355	-.14949	.01142	.00000	-.00078	-.00719	-.00709	-.00294	-.00758
RUN NO.		1609/ 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	1.000	PHI =	5.00
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATT
1.516	-6.970	326.48170	1226.40645	525.11607	382.90310	101.40000	2.48483	335.48000	905.54980	1.70395 2033.92000
1.516	-6.453	326.99580	1228.01053	525.81531	382.88480	101.30000	2.48839	336.00980	905.55980	1.68896 2033.92000
1.516	-5.951	327.05910	1229.35399	526.34628	382.78560	101.30000	2.49075	336.07980	905.56980	1.68710 2033.92000
1.516	-5.447	327.02560	1227.87746	525.76788	382.90700	101.30000	2.48819	336.03980	905.58980	1.68915 2033.88499
1.515	-4.941	326.89140	1227.14000	525.46172	382.99540	101.40000	2.48619	335.89990	905.58980	1.69016 2033.88499
1.516	-4.439	327.05270	1228.35025	525.95635	382.93070	101.40000	2.48865	336.06980	905.58980	1.69703 2033.88499
1.516	-3.931	327.12130	1228.72903	526.11256	382.94850	101.40000	2.48884	336.13990	905.58980	1.67526 2033.88499
1.515	-3.424	327.53120	1229.31050	526.39930	383.04860	101.40000	2.49005	336.55980	905.57980	1.66609 2033.95500
1.515	-2.910	327.52980	1229.70055	526.55035	383.01290	101.40000	2.49072	336.55980	905.57980	1.66556 2033.88499
1.516	-2.401	327.29440	1229.87711	526.58281	382.93260	101.40000	2.49045	336.31980	905.58980	1.65271 2033.88499
1.516	-1.882	327.42090	1230.10358	526.69060	382.95020	101.40000	2.49108	336.45000	905.58980	1.65660 2033.88499
1.516	-1.361	327.54660	1230.63124	526.91322	382.95700	101.40000	2.49191	336.55980	905.57980	1.64755 2033.92000
1.516	-.834	327.54540	1230.87206	527.00672	382.92940	101.40000	2.49242	336.57980	905.56980	1.65139 2033.95500
1.516	-.309	327.76030	1231.13434	527.14062	383.05370	101.50000	2.49240	336.79980	905.58980	1.64690 2033.92000
1.516	.180	327.82740	1231.50017	527.29357	383.03830	101.50000	2.49320	336.86990	905.58980	1.65058 2033.92000
1.515	.663	328.02390	1231.36426	527.26986	383.11280	101.50000	2.49328	337.06980	905.55980	1.65497 2033.88499
1.516	1.150	327.77730	1231.63457	527.33762	382.99800	101.50000	2.49358	336.81980	905.58980	1.65875 2033.88499
GRADIENT	.15011	.66338	.27972	.01243	.01935	.0104	.15540	-.00163	-.00225	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 994  
(VCM051) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1624/ O	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	1.000	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
1.542	-6.969	317.29790	1237.72881	527.88796	378.84640	101.30000	2.48999	326.13990	907.10990	1.50078 2033.60500
1.541	-6.453	317.59180	1237.60796	527.89822	378.95610	101.30000	2.49022	326.43990	907.10990	1.50481 2033.60500
1.541	-5.950	317.23000	1237.63191	527.83907	378.83620	101.30000	2.48965	326.06980	907.11990	1.49707 2033.60500
1.542	-5.446	317.37620	1237.86694	527.95528	378.80470	101.20000	2.49071	326.22000	907.11990	1.49299 2033.57001
1.542	-4.946	317.38650	1237.57759	527.84769	378.82370	101.20000	2.49043	326.23000	907.08980	1.50098 2033.57001
1.541	-4.438	317.36720	1237.51665	527.82110	378.82230	101.20000	2.49031	326.21000	907.08980	1.50105 2033.57001
1.541	-3.931	317.59080	1238.08275	528.07785	378.86670	101.20000	2.49122	326.43990	907.08980	1.48897 2033.57001
1.541	-3.425	317.62990	1238.10793	528.09499	378.87300	101.20000	2.49141	326.48000	907.07980	1.49274 2033.57001
1.541	-2.915	317.55080	1238.30911	528.15560	378.82710	101.20000	2.49166	326.39990	907.05980	1.49248 2033.53500
1.541	-2.401	317.64770	1238.66225	528.30770	378.84030	101.20000	2.49217	326.50000	907.04980	1.48448 2033.57001
1.542	-1.886	317.56910	1238.63121	528.28065	378.80490	101.20000	2.49222	326.41990	907.04980	1.49209 2033.53500
1.541	-1.364	317.80400	1238.72421	528.36071	378.88500	101.20000	2.49255	326.65990	907.04980	1.48822 2033.53500
1.541	-837	317.71530	1238.77856	528.36372	378.83840	101.20000	2.49274	326.56980	907.01980	1.49574 2033.53500
1.541	-309	317.78320	1238.97264	528.45016	378.85030	101.20000	2.49304	326.63990	907.00000	1.49171 2033.53500
1.542	.179	317.78200	1239.43709	528.62550	378.81880	101.20000	2.49363	326.63990	907.00000	1.48355 2033.57001
1.541	.660	318.03540	1239.80370	528.81268	378.87570	101.20000	2.49454	326.89990	906.98000	1.48315 2033.57001
1.541	1.149	318.02560	1239.84058	528.82479	378.94170	101.30000	2.49389	326.88990	906.97000	1.47932 2033.53500
GRADIENT	.09532	.09532	.36518	.15611	.00832	.00637	.00063	.09857	-.02091	-.00250 -.00378

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM052) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	1.500	PHI =	180.000
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
.599	-6.941	1253.04800	1596.99001	314.69360	521.91970	99.70000	2.49762	1262.78999	1306.11000
-6.433	1252.26100	1596.72000	315.11210	521.94430	99.80000	2.49834	1262.00999	1306.14000	
.600	-5.926	1252.37910	1596.84000	315.10690	522.04200	99.89999	2.49786	1262.14000	1306.14999
.600	-5.420	1252.07100	1597.06000	315.55370	521.98340	99.89999	2.49667	1261.83000	1306.17000
.600	-4.907	1252.29300	1597.14000	315.43900	521.90890	99.80000	2.49989	1262.05000	1306.17999
.600	-4.404	1251.89000	1597.03000	315.67770	521.96440	99.89999	2.50009	1261.64999	1306.19000
.600	-3.889	1251.98000	1597.06000	315.62840	521.97240	99.89999	2.49994	1261.74001	1306.17999
.601	-3.379	1251.39600	1596.82001	315.90600	521.92530	99.89999	2.50074	1261.16000	1306.20000
.600	-2.863	1251.85800	1597.06000	315.72850	522.05130	100.00000	2.49973	1261.62000	1306.20000
.601	-2.344	1251.21001	1596.97000	316.18460	521.79590	99.80000	2.50045	1260.98000	1306.19000
.600	-1.823	1251.99500	1597.35001	315.86040	522.04050	100.00000	2.50045	1261.75999	1306.24001
.600	-1.298	1251.44800	1596.77000	315.82150	521.84280	99.80000	2.50096	1261.21001	1306.24001
.601	-7.771	1251.39200	1596.98000	316.04320	522.00320	100.00000	2.50080	1261.16000	1306.25999
.601	-2.250	1251.43201	1597.03000	316.05270	522.00320	100.00000	2.50088	1261.20000	1306.28000
.600	.243	1252.22099	1597.19000	315.54030	521.98900	99.89999	2.49973	1261.98000	1306.28000
.600	.735	1251.66499	1597.08000	315.90430	522.11960	100.10000	2.49982	1261.42999	1306.30000
.601	1.213	1251.43201	1597.00000	316.02710	522.00610	100.00000	2.50076	1261.20000	1306.30000
GRADIENT	-.06318	.00214	.05359	.01715	.02667	.00004	-.06209	.02222	-.00683 -.01776
RUN NO.		RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		RN/L	PC	PREF	SH10+3 PATM
MACH	ALPHA	P	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
.800	-6.959	880.14890	1341.28000	394.03560	496.82060	100.70000	2.49490	890.04980	1057.94000
.800	-6.448	879.81640	1341.24001	394.23190	496.85990	100.80000	2.49480	889.72000	1057.98000
.800	-5.946	879.86060	1341.00999	394.03200	496.80270	100.70000	2.49460	889.76000	1058.00999
.800	-5.437	879.40480	1341.08000	394.39330	496.81030	100.80000	2.49505	889.30980	1058.03999
.800	-4.933	879.72750	1341.11000	394.19630	496.85940	100.80000	2.49457	889.62990	1058.08000
.800	-4.430	879.71920	1341.02000	394.13550	496.86740	100.80000	2.49431	889.61990	1058.10001
.800	-3.921	879.74020	1340.95000	394.06930	496.87820	100.80000	2.49406	889.63990	1058.14000
.800	-3.413	879.44530	1341.07001	394.35860	496.81790	100.80000	2.49495	889.34990	1058.17000
.800	-2.904	879.54930	1340.89999	394.16240	496.85280	100.80000	2.49425	889.45000	1058.21001
.800	-2.388	879.57960	1340.87000	394.11910	496.86080	100.80000	2.49410	889.48000	1058.22000
.800	-1.878	879.73050	1340.92000	394.05350	496.79130	100.70000	2.49456	889.62990	1058.30000
.800	-1.353	879.90160	1340.96001	393.96680	496.81470	100.70000	2.49437	889.79980	1058.30000
.800	-.837	879.61770	1341.05000	394.22660	496.58200	100.50000	2.49630	889.51980	1058.32001
.800	-.326	879.65670	1341.11000	394.24410	496.49320	100.40000	2.49698	889.55980	1058.35001
.800	-.164	879.90210	1340.92000	393.93680	496.37550	100.20000	2.49712	889.79980	1058.36000
.800	.663	879.36380	1341.10001	394.43580	496.18120	100.10000	2.49919	889.26980	1058.39000
.800	1.151	879.97170	1341.00999	393.95650	496.28860	100.10000	2.49784	889.86990	1058.41000
GRADIENT	.01538	.00209	-.00895	-.1233	-.12925	.00072	.01525	.05554	-.01782 .00981

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 996  
 (VCM052) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1502/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
.900	-6.954	752.94120	1273.14000	426.70310	481.50540	99.80000	2.50022	762.95000	982.25000	4.11391 2036.61501
.900	-6.441	752.82300	1272.95000	426.64310	481.50420	99.80000	2.49985	762.82980	982.27980	4.08510 2036.64999
.900	-5.938	752.66410	1272.78000	426.62080	481.66580	99.80000	2.49844	762.66990	982.30980	4.03702 2036.64999
.901	-5.429	752.38480	1273.28000	427.13040	481.38840	99.80000	2.50133	762.39990	982.32980	3.97780 2036.64999
.900	-4.924	752.62920	1273.10001	426.86130	481.71070	100.10000	2.49878	762.63990	982.33980	3.96884 2036.64999
.900	-4.420	752.45700	1273.17999	427.01860	481.75660	100.10000	2.49865	762.47000	982.37990	4.12363 2036.64999
.900	-3.913	752.45970	1272.98000	426.87990	481.60670	100.00000	2.49925	762.47000	982.36990	4.09479 2036.64999
.900	-3.403	752.56130	1272.92000	426.77810	481.63180	100.00000	2.49896	762.56980	982.40990	4.08520 2036.68500
.900	-2.892	752.80000	1273.14999	426.79420	481.73660	100.10000	2.49870	762.80980	982.43990	4.05222 2036.68500
.900	-2.379	752.82470	1272.82001	426.55250	481.777660	100.10000	2.49776	762.49980	982.43990	4.02724 2036.68500
.900	-1.862	753.92580	1272.63000	425.76590	482.08470	100.20000	2.49522	763.91990	982.47000	3.97985 2036.68500
.900	-1.343	753.53520	1273.89000	426.86500	481.96310	100.20000	2.49861	763.54980	982.53980	3.91904 2036.68500
.900	-825	752.23190	1272.67999	426.80910	481.85570	100.30000	2.49700	762.24000	982.52980	3.91338 2036.68500
.900	-313	752.70140	1272.99001	426.74270	481.99390	100.40000	2.49666	762.71000	982.55980	3.91243 2036.64999
.900	-180	752.68120	1272.99001	426.75490	481.99020	100.40000	2.49668	762.68990	982.55980	3.90304 2036.64999
.900	.676	752.76270	1272.94000	426.67210	482.09670	100.50000	2.49587	762.76980	982.59990	3.92199 2036.68500
.900	.160	752.69090	1273.02000	426.76980	482.07500	100.50000	2.49618	762.70000	982.59990	3.94062 2036.68500
	GRADIENT	.03010	-.01398	-.02750	.07472	.07868	-.00053	.02967	.04473	-.03088
										.00296

	RUN NO.	1509/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3
1.100	-6.984	565.13280	1205.89999	478.23930	450.61790	99.89999	2.49937	575.31980	911.59990	1.56020 2036.12500
1.100	-6.474	564.89140	1205.96001	478.36960	450.63700	100.00000	2.49904	575.07980	911.60990	1.55608 2036.12500
1.100	-5.973	564.90280	1205.84000	478.29540	450.65230	100.00000	2.49876	575.08980	911.61990	1.55220 2036.12500
1.100	-5.473	564.90900	1205.96001	478.44870	450.59130	100.00000	2.49914	574.87990	911.62990	1.55205 2036.12500
1.100	-4.973	564.69970	1206.06000	478.50340	450.42160	99.80000	2.50053	574.88990	911.64990	1.55192 2036.12500
1.100	-4.472	564.85160	1205.92000	478.36210	450.47120	99.80000	2.50014	575.03980	911.65990	1.55613 2036.09000
1.100	-3.964	565.01050	1206.09000	478.39820	450.48930	99.80000	2.50045	575.20000	911.66990	1.55188 2036.12500
1.100	-3.465	564.71190	1205.87000	478.38820	450.44480	99.80000	2.50009	574.89990	911.65990	1.54814 2036.09000
1.100	-2.962	564.94240	1205.87000	478.29710	450.65820	100.00000	2.49881	575.12990	911.67990	1.54011 2036.09000
1.100	-2.462	564.73930	1206.12000	478.52290	450.42430	99.80000	2.50065	574.92990	911.67990	1.54380 2036.09000
1.100	-1.957	564.97170	1205.95000	478.33230	450.49540	99.80000	2.50015	575.15990	911.68990	1.54803 2036.09000
1.100	-1.446	564.78980	1206.08000	478.47970	450.43990	99.80000	2.50053	574.98000	911.70000	1.54385 2036.09000
1.100	-1.949	565.03100	1206.03000	478.35550	450.50020	99.80000	2.50030	575.22000	911.68990	1.53991 2036.09000
1.100	-1.448	565.11300	1205.87000	478.22970	450.61670	99.80000	2.49931	575.29980	911.70000	1.54412 2036.09000
1.100	.039	564.94090	1206.03000	478.39110	450.56030	99.80000	2.49976	575.12990	911.70000	1.54392 2036.05499
1.100	.545	564.79860	1206.17999	478.53420	450.51200	99.80000	2.50017	574.99000	911.68990	1.53572 2036.05499
1.100	1.051	564.88430	1205.71001	478.22710	450.50100	99.80000	2.49964	575.06980	911.71000	1.52835 2036.05499
1.100	.02189	.021347	-.00834	-.01347	.00874	.00874	.00008	.02173	.00865	-.00315 -.00960

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM052) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	1.500	PHI =	180.000	
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM	
ALPHA										
-6.965	462.88920	1198.39999	505.97310	426.78250	100.40000	2.49859	473.01980	864.37990	1.22705 2035 70500	
-6.447	462.69260	1198.02000	505.82370	426.76930	100.40000	2.49779	472.81980	864.36990	1.21450 2035 67000	
-5.947	462.36720	1197.44000	505.60080	426.74270	100.40000	2.49657	472.49000	864.36990	1.22500 2035 70500	
-5.444	462.51810	1197.27000	505.48170	426.79980	100.40000	2.49624	472.63990	864.36990	1.20883 2035 70500	
-4.945	462.79000	1198.34000	505.96440	426.76250	100.40000	2.49845	472.91990	864.36990	1.19818 2035 70500	
-4.439	462.82060	1198.23000	505.90210	426.78170	100.40000	2.49823	472.95000	864.35990	1.20147 2035 70500	
-3.929	462.66480	1197.67000	505.65230	426.79790	100.40000	2.49707	472.78980	864.36990	1.19885 2035 70500	
-3.424	462.45460	1197.83000	505.77950	426.72610	100.40000	2.49737	472.57980	864.36990	1.20507 2035 70500	
-2.913	462.57250	1198.06000	505.87010	426.73360	100.40000	2.49786	472.70000	864.35990	1.20483 2035 67000	
-2.406	462.71340	1197.87000	505.74290	426.79000	100.40000	2.49749	472.83980	864.35990	1.20823 2035 67000	
-1.892	462.70170	1198.12000	505.87230	426.76170	100.40000	2.49799	472.82980	864.34990	1.21440 2035 67000	
-1.379	462.43240	1198.14000	505.94140	426.68850	100.40000	2.49800	472.55980	864.35990	1.21438 2035 67000	
-1.250	462.66500	1197.66000	505.64720	426.79880	100.40000	2.49705	472.78980	864.34990	1.21486 2035 67000	
-1.250	462.69090	1198.23000	505.93040	426.74760	100.40000	2.49822	472.81980	864.34990	1.22074 2035 67000	
-1.250	462.60180	1198.4030	505.90430	426.73230	100.40000	2.49802	472.73000	864.33980	1.22083 2035 70500	
.132	462.67140	1198.14999	505.89400	426.75050	100.40000	2.49805	472.79980	864.33980	1.22082 2035 67000	
1.250	462.50100	1198.32001	506.01760	426.68850	100.40000	2.49838	472.62990	864.35990	1.21742 2035 70500	
1.123	-0.02292	.02179	.01604	-.00826	-.00000	.00004	-.02283	-.00393	.00405 -.00308	
GRADIENT										
RUN NO.		RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	1.500	PHI =	5.00	
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM	
ALPHA										
-6.974	382.03250	1214.87000	523.77150	402.21510	100.10000	2.49807	391.74000	878.80980	1.16626 2035 14500	
-6.450	382.01200	1214.99001	523.82450	402.05370	99.89999	2.49946	391.72000	878.82980	1.17235 2035 11000	
-5.950	381.90090	1215.38000	523.99760	402.12720	100.10000	2.49891	391.60990	878.81980	1.17822 2035 11000	
-5.448	381.90430	1214.80000	523.74340	402.11130	100.00000	2.49845	391.60990	878.80980	1.17878 2035 11000	
-4.948	381.82640	1214.59000	523.65330	402.10770	100.00000	2.49800	391.52980	878.81980	1.17898 2035 11000	
-4.438	382.02030	1215.25000	523.93820	402.10350	100.00000	2.49935	391.73000	878.79980	1.17834 2035 14500	
-3.932	381.75610	1214.78000	523.73780	401.99660	99.89999	2.49889	391.46000	878.79980	1.17567 2035 14500	
-3.429	381.62430	1215.34000	523.98540	401.90410	99.89999	2.49982	391.32980	878.77980	1.17513 2035 11000	
-2.924	381.91280	1215.00999	523.83520	402.02200	99.89999	2.49943	391.61990	878.77980	1.19115 2035 11000	
-2.409	381.78520	1214.89999	523.78980	402.20950	100.20000	2.49735	391.49000	878.76980	1.17556 2035 11000	
-1.901	381.72460	1215.05000	523.85640	402.03370	100.00000	2.49877	391.42990	878.73000	1.17541 2035 11000	
1.400	-1.394	381.80640	1214.61000	523.66240	100.00000	2.49803	391.50980	878.73000	1.17584 2035 11000	
1.400	-.878	381.67410	1215.28000	523.95830	100.99660	2.49915	391.37990	878.73000	1.17519 2035 11000	
1.400	-.371	381.93260	1215.00999	523.83500	100.99990	2.49885	391.63990	878.72000	1.19115 2035 11000	
1.400	-.116	381.88230	1215.17000	523.90580	101.99780	99.89999	2.49970	391.58980	878.68990	1.19099 2035 11000
1.400	.618	381.89210	1215.16000	523.90110	102.07350	100.00000	2.49909	391.59990	878.66990	1.20051 2035 11000
1.400	1.114	381.85520	1214.74001	523.71830	102.0230	100.00000	2.49830	391.55980	878.66990	1.20412 2035 11000
GRADIENT	.00543	.01389	.00595	.00271	.00330	.00001	.00558	-.02506	.00367 -.00344	



## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM052) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1594/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.500	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.493	-6.952	337.11330	1224.65791	525.82302	386.27250	100.40000	2.49355	346.28980	896.60990	1.50473	2033.60500		
1.493	-6.438	336.95020	1223.90958	525.50680	386.22750	100.30000	2.49248	346.11990	896.60990	1.49799	2033.64000		
1.493	-5.932	337.37350	1225.70979	526.27161	386.11520	100.20000	2.49704	346.55980	896.58980	1.51113	2033.64000		
1.493	-5.429	338.20430	1228.88243	527.62891	386.10110	100.20000	2.50346	347.41990	896.58980	1.51113	2033.64000		
1.493	-4.921	338.04830	1228.91747	527.62437	386.07320	100.20000	2.50284	347.25980	896.61990	1.49195	2033.64000		
1.493	-4.416	338.00290	1227.72050	527.14417	386.13310	100.20000	2.50135	347.21000	896.59990	1.51641	2033.64000		
1.493	-3.907	337.70970	1227.70573	527.10414	386.06930	100.20000	2.50040	346.90990	896.59990	1.49340	2033.64000		
1.493	-3.399	337.77100	1226.84329	526.76833	386.13480	100.20000	2.49961	346.97000	896.58980	1.51748	2033.67500		
1.493	-2.886	337.73290	1226.52525	526.63695	386.15090	100.20000	2.49902	346.92990	896.58980	1.51787	2033.64000		
1.493	-2.367	337.49880	1226.19820	526.48068	386.10180	100.20000	2.49822	346.68990	896.57980	1.51825	2033.67500		
1.493	-1.856	337.38450	1225.38124	526.14279	386.13750	100.20000	2.49669	346.56980	896.56980	1.51926	2033.64000		
1.493	-1.331	337.35550	1225.20171	526.06735	386.14400	100.20000	2.49635	346.53980	896.54980	1.51948	2033.64000		
1.493	-8.811	337.09250	1224.67538	525.82850	386.10350	100.20000	2.49518	346.26980	896.55980	1.52011	2033.64000		
1.492	-2.298	337.19290	1224.20029	525.65144	386.17480	100.20000	2.49457	346.36990	896.54980	1.52459	2033.64000		
1.492	.194	337.16330	1224.24956	525.66684	386.16600	100.20000	2.49451	346.33980	896.53980	1.52065	2033.64000		
1.493	.691	337.41110	1226.08681	526.42593	386.09370	100.20000	2.49773	346.59990	896.55980	1.51067	2033.64000		
1.493	1.173	337.51950	1226.05797	526.42696	386.13260	100.20000	2.49779	346.71000	896.52980	1.51072	2033.64000		
GRADIENT	- .12402	- .559555	- .23673	.00661	- .00000	- .00000	-.00104	-.012861	-.01284	.00238	-.00154		
	RUN NO.	1610/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00							
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM		
1.516	-6.957	326.60840	1226.98163	525.35748	382.99710	101.50000	2.48471	335.60990	905.53980	1.67760	2033.88499		
1.516	-6.438	327.19730	1229.31955	526.35329	382.98410	101.50000	2.48943	336.22000	905.54980	1.67868	2033.88499		
1.516	-5.933	327.80810	1231.41982	527.25928	383.03910	101.50000	2.49304	336.84990	905.54980	1.65069	2033.88499		
1.516	-5.429	327.30320	1230.24426	526.72613	383.05000	101.60000	2.48969	336.32980	905.54980	1.64388	2033.88499		
1.516	-4.921	326.67550	1227.82265	525.69242	382.98880	101.50000	2.48538	335.67990	905.56980	1.64291	2033.88499		
1.516	-4.415	327.19190	1228.71259	526.11479	383.08690	101.50000	2.48745	336.21000	905.55980	1.64179	2033.88499		
1.516	-3.908	327.40750	1231.36507	527.17677	382.93310	101.50000	2.49200	336.43990	905.55980	1.62997	2033.85001		
1.517	-3.400	327.10860	1230.09348	526.63842	382.95000	101.50000	2.48941	336.12990	905.56980	1.62751	2033.85001		
1.516	-2.882	327.04300	1229.38594	526.35313	382.99660	101.50000	2.48803	336.05980	905.57980	1.62433	2033.85001		
1.516	-2.372	326.96610	1228.98677	526.18674	383.00610	101.50000	2.48726	335.98000	905.55980	1.62486	2033.81500		
1.516	-1.852	326.90940	1228.56262	526.01357	383.09840	101.60000	2.48578	335.91990	905.55980	1.62131	2033.81500		
1.516	-1.332	326.88920	1228.64603	526.04368	383.07840	101.60000	2.48600	335.89990	905.54980	1.62530	2033.81500		
1.516	-.811	326.93820	1228.70256	526.07239	383.02730	101.50000	2.48664	335.95000	905.55980	1.62112	2033.78000		
1.516	-.296	326.80100	1228.59663	526.01041	383.05250	101.60000	2.48583	335.80980	905.54980	1.62535	2033.81500		
1.516	.195	327.01490	1229.07054	526.22751	383.01540	101.50000	2.48746	336.02980	905.54980	1.62475	2033.81500		
1.516	.689	327.27660	1229.89313	526.58505	383.10520	101.60000	2.48844	336.29980	905.54980	1.61959	2033.81500		
1.516	1.173	327.39260	1230.32607	526.77139	383.10620	101.60000	2.48930	336.41990	905.54980	1.61903	2033.78000		
GRADIENT	.02027	.05727	.02522	.01682	.01613	-.00005	.02070	-.00347	-.00309	-.01471			

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1000

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM052) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	P	PT	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	1.500	PHI =	180.000
1.542	-6.952	317.77290	1240.47395	529.01875	378.90140	101.30000	2.49268	326.62990	906.96000	1.40120	2033.53500
1.542	-6.433	317.69480	1240.37904	528.96837	378.87740	101.30000	2.49252	326.54980	906.95000	1.40489	2033.53500
1.542	-5.932	317.64580	1240.21858	528.89765	378.85450	101.30000	2.49257	326.50000	906.95000	1.41954	2033.50000
1.542	-5.429	317.87060	1240.22353	528.94159	378.92850	101.30000	2.49293	326.73000	906.93990	1.42322	2033.50000
1.542	-4.926	317.96830	1240.19334	528.94958	378.95580	101.30000	2.49318	326.82980	906.93990	1.43057	2033.50000
1.542	-4.416	317.85080	1240.07417	528.88162	378.91480	101.30000	2.49303	326.71000	906.91990	1.43803	2033.53500
1.542	-3.906	317.74240	1239.57639	528.67092	378.85990	101.30000	2.49322	326.59990	906.91990	1.48337	2033.53500
1.541	-3.400	317.97780	1239.83006	528.81274	378.95120	101.30000	2.49334	326.83980	906.90990	1.46057	2033.53500
1.542	-2.882	317.95700	1240.11861	528.91753	378.91310	101.30000	2.49390	326.81980	906.90990	1.46395	2033.50000
1.542	-2.367	317.74290	1239.64330	528.69723	378.86960	101.30000	2.49305	326.59990	906.89990	1.47198	2033.50000
1.541	-1.853	317.87060	1238.86526	528.42568	378.92160	101.30000	2.49306	326.73000	906.90990	1.51868	2033.50000
1.541	-1.332	317.61790	1238.16658	528.11407	378.88380	101.30000	2.49179	326.47000	906.88990	1.52726	2033.50000
1.541	-8.11	317.65820	1237.70589	527.94621	378.92870	101.30000	2.49126	326.50980	906.87990	1.53564	2033.50000
1.541	-2.296	317.48410	1237.04709	527.66426	378.91500	101.30000	2.49015	326.32980	906.86990	1.54427	2033.46500
1.541	.195	317.27080	1236.41261	527.38491	378.89060	101.30000	2.48894	326.10990	906.85990	1.54896	2033.42999
1.541	.690	317.28100	1236.29085	527.34049	378.91060	101.30000	2.48864	326.11990	906.82980	1.54519	2033.46500
1.541	1.172	317.18480	1235.87967	527.16722	378.91330	101.30000	2.48784	326.01980	906.81980	1.54570	2033.46500
	GRADIENT	- .12499	- .77507	- .31725	- .00234	- .00000	- .00094	- .12939	- .01719	.02088	- .01283

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM053) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1579/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	ALPHA	P	PT	Q (PSF)	T (R)	TT (F)	RN/L	PC	PREF	SH10+3 PATM
.600	-6.923	1252.33800	1596.98000	3.15.26860	522.20900	100.10000	2.49742	1262.09000	1306.32000	.97284 2034.62000
.599	-6.410	1252.72400	1596.95000	3.14.92600	522.35130	100.20000	2.49558	1262.47000	1306.34000	.97029 2034.58501
.599	-5.903	1252.41200	1596.82001	3.15.07300	522.32620	100.20000	2.49601	1262.16000	1306.36000	.97037 2034.58501
.599	-5.396	1252.77299	1597.03999	3.14.96170	522.44190	100.30000	2.49522	1262.52000	1306.36000	.99351 2034.58501
.600	-4.888	1252.30901	1596.89999	3.15.22510	522.39970	100.30000	2.49606	1262.06000	1306.37000	.99621 2034.55000
.600	-4.378	1252.23500	1597.00999	3.15.37790	522.47390	100.40000	2.49614	1261.99001	1306.39000	.99614 2034.58501
.600	-3.864	1252.10600	1597.32001	3.15.74320	522.42970	100.40000	2.49773	1261.87000	1306.39999	.99857 2034.58501
.600	-3.356	1252.18401	1597.03000	3.15.43630	522.66110	100.40000	2.49637	1261.94000	1306.41000	.99613 2034.58501
.600	-2.837	1251.57700	1596.39000	3.15.39600	522.45340	100.40000	2.49568	1261.33000	1306.41000	.99653 2034.58501
.600	-2.315	1251.76801	1596.99001	3.15.74370	522.32690	100.30000	2.49802	1261.53000	1306.41000	.99616 2034.55000
.600	-1.797	1251.97701	1597.23000	3.15.77440	522.32930	100.30000	2.49833	1261.74001	1306.44000	.99601 2034.62000
.600	-1.273	1251.92400	1597.32001	3.15.89330	522.40800	100.40000	2.49827	1261.69000	1306.45000	.98552 2034.62000
.600	-756	1251.82500	1596.69000	3.15.44510	522.36180	100.30000	2.49668	1261.58000	1306.46001	.98851 2034.62000
.600	-239	1252.41600	1597.63000	3.15.75100	522.43750	100.40000	2.49802	1262.17999	1306.46001	1.00100 2034.62000
.600	.251	1251.92300	1596.89000	3.15.53230	522.35470	100.30000	2.49717	1261.67999	1306.48000	.99884 2034.58501
.600	.753	1252.03600	1597.28999	3.15.77590	522.33080	100.30000	2.49839	1261.80000	1306.49001	.99859 2034.58501
.600	1.235	1251.74999	1596.64999	3.15.45210	522.35960	100.30000	2.49667	1261.53000	1306.50000	.99899 2034.58501
GRADIENT	-.03816	-.01034	.04001	-.01547	-.01068	.00021	-.03737	.02023	.00018	-.00494
	RUN NO.	1470/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	ALPHA	P	PT	Q (PSF)	T (R)	TT (F)	RN/L	PC	PREF	SH10+3 PATM
.800	-6.946	880.05080	1341.10001	393.96900	496.20340	100.00000	2.49855	889.95000	1045.98000	1.70570 2038.43500
.800	-6.433	880.17940	1341.25999	394.00000	496.02980	99.80000	2.49995	890.07980	1046.03000	1.69247 2038.43500
.800	-5.930	879.88130	1340.95000	393.97310	496.01440	99.80000	2.49954	889.77980	1046.10001	1.68423 2038.43500
.800	-5.424	879.64620	1341.16000	394.28860	496.2050	100.10000	2.49887	889.54980	1046.16000	1.68397 2038.39999
.800	-4.919	879.55740	1340.99001	394.22290	496.13550	100.00000	2.49909	889.46000	1046.17999	1.68418 2038.43500
.800	-4.411	879.98560	1340.75999	393.76170	496.22880	100.00000	2.49793	889.87990	1046.24001	1.68017 2038.43500
.800	-3.907	879.63650	1341.13000	394.23720	496.13330	100.00000	2.49937	889.53980	1046.28899	1.69264 2038.39999
.800	-3.391	879.73190	1340.85001	394.00120	496.17820	100.00000	2.49836	889.62990	1046.31000	1.69299 2038.43500
.800	-2.882	879.69800	1341.06000	394.17920	496.15060	100.00000	2.49905	889.59990	1046.38000	1.69706 2038.43500
.800	-2.369	879.40410	1341.13000	394.43120	496.09590	100.00000	2.49979	889.30980	1046.41000	1.70567 2038.43500
.800	-1.855	879.46610	1341.03999	394.32230	496.11550	100.00000	2.49940	889.36990	1046.44000	1.71014 2038.43500
.800	-1.340	879.83910	1341.08000	394.09810	496.17140	100.00000	2.49886	889.74000	1046.49001	1.70138 2038.43500
.800	-.826	879.45830	1340.89999	394.22410	496.12890	100.00000	2.49900	889.35990	1046.52000	1.69293 2038.39999
.800	-.319	879.74880	1341.03000	394.12260	496.16190	100.00000	2.49887	889.64990	1046.55000	1.67126 2038.39999
.800	.174	879.58840	1340.97000	394.18750	496.14260	100.00000	2.49898	889.49000	1046.57001	1.64164 2038.43500
.800	.677	879.88870	1341.14000	394.10910	496.17290	100.00000	2.49896	889.78980	1046.62000	1.62469 2038.43500
.800	1.167	879.93330	1340.86000	393.87130	496.29830	100.00000	2.49746	889.82980	1046.64999	1.62086 2038.39999
GRADIENT	.01687	.00705	-.00622	-.00642	-.00005	.01680	.07469	-.00269	-.00109	-.00269



## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM053) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1526/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM		
-6.957	462.7	3070	1198.25999	505.93700	426.75490	100.40000	2.49828	472.85990	864.34990	1.22395	2035	67000	
1.250	-6.440	462.67190	1198.09000	505.86350	426.75680	100.40000	2.49793	472.79980	864.32980	1.22088	2035	67000	
1.250	-5.934	462.46390	1197.91000	505.81790	426.72020	100.40000	2.49754	472.58980	864.34990	1.22107	2035	67000	
1.250	-5.430	462.50560	1197.61000	505.65670	426.76200	100.40000	2.49693	472.62990	864.34990	1.21170	2035	67000	
1.250	-4.925	462.63280	1197.99001	505.82150	426.75660	100.40000	2.49772	472.75980	864.33980	1.21131	2035	67000	
1.250	-4.420	462.71360	1197.84000	505.72780	426.79320	100.40000	2.49742	472.83980	864.34990	1.20186	2035	67000	
1.250	-3.916	462.4460	1197.81000	505.77810	426.71750	100.40000	2.49733	472.53980	864.33980	1.20829	2035	67000	
1.250	-3.403	462.39360	1197.95000	505.85350	426.69780	100.40000	2.49761	472.51980	864.35990	1.21136	2035	70500	
1.250	-2.896	462.73290	1197.92999	505.76900	426.78910	100.40000	2.49761	472.85990	864.34990	1.21459	2035	70500	
1.250	-2.387	462.53420	1197.85001	505.77220	426.74490	100.40000	2.49742	472.65990	864.33980	1.21790	2035	63499	
1.250	-1.874	462.60500	1197.67999	505.67070	426.78100	100.40000	2.49709	472.73000	864.32980	1.21485	2035	67000	
1.250	-1.365	462.68040	1198.32001	505.97830	426.81180	100.50000	2.49781	472.80980	864.33980	1.21098	2035	67000	
1.250	-853	462.73020	1198.34000	505.97750	426.82300	100.50000	2.49786	472.85990	864.34990	1.21417	2035	67000	
1.250	-349	462.45610	1197.58000	505.65230	426.82810	100.50000	2.49628	472.57980	864.31980	1.21173	2035	67000	
1.250	.139	462.47390	1197.91000	505.81590	426.79910	100.50000	2.49695	472.5990	864.33980	1.20189	2035	67000	
1.250	.644	462.73340	1197.85001	505.72850	426.87380	100.50000	2.49686	472.85990	864.32980	1.21146	2035	67000	
1.250	1.138	462.90940	1198.35001	505.94340	426.86910	100.50000	2.49790	473.03980	864.31980	1.21095	2035	67000	
GRADIENT	.02511	.03020	.00981	.02093	.02280	-.00007	.02541	-.00372	.00042	-.00156			
RUN NO.		1543/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00							
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM		
-6.961	381.96410	1214.72000	523.70730	402.13670	100.00000	2.49834	391.66990	880.81980	1.18828	2035	14500		
-6.443	381.95970	1215.44000	524.02220	401.99560	99.89999	2.50025	391.66990	880.83980	1.18757	2035	11000		
-5.938	381.65580	1215.03000	523.84910	402.01460	100.00000	2.49868	391.35990	880.86990	1.18798	2035	11000		
-5.435	381.89360	1214.91000	523.79170	402.02590	99.89999	2.49923	391.59990	880.90990	1.18181	2035	14500		
-4.931	381.88210	1215.19000	523.91460	401.99580	99.89999	2.49973	391.58980	880.92990	1.18467	2035	14500		
-4.431	381.77540	1214.85001	523.76810	402.13960	100.10000	2.49785	391.48000	880.96000	1.18181	2035	14500		
-3.920	381.95140	1215.17000	523.90430	402.09600	100.00000	2.49916	391.65990	880.96000	1.18784	2035	11000		
-3.416	381.91160	1215.21001	523.92290	402.07470	100.00000	2.49920	391.61990	880.96000	1.18465	2035	11000		
-2.903	381.68850	1214.55000	523.63870	402.06980	100.00000	2.49783	391.38990	880.99000	1.18216	2035	11000		
-2.397	381.94310	1214.92999	523.79960	402.03880	99.89999	2.49931	391.64990	880.99000	1.18493	2035	11000		
-1.890	382.05100	1215.06000	523.85420	402.13090	100.00000	2.49903	391.75980	881.01980	1.18480	2035	14500		
-1.377	381.62650	1214.94000	523.81030	402.08620	100.10000	2.49790	391.32980	881.01000	1.18806	2035	14500		
-867	381.77220	1215.37000	523.99560	402.08940	100.10000	2.49879	391.48000	881.01980	1.18450	2035	14500		
-364	381.87480	1214.78999	523.73970	402.10330	100.00000	2.49841	391.57980	881.01000	1.18506	2035	11000		
-127	381.79590	1214.73000	523.71510	402.01340	99.89999	2.49883	391.50000	881.01000	1.18512	2035	14500		
.630	381.90890	1215.63000	524.10640	401.96240	99.89999	2.50056	391.61990	881.01980	1.18424	2035	11000		
1.400	1.128	381.93460	1214.70000	523.69900	402.05790	99.89999	2.49888	391.63990	881.02980	1.19146	2035	14500	
GRADIENT	.00100	-.00442	-.00198	-.00703	-.01077	-.0006	.00100	.01442	.00021	.00075			

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1004  
( VCM053 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1560/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.450	-6.926	358.599960	1225.72000	528.04710	394.07420	100.20000	2.49724	368.06980	892.96000	1.42701 2035.32001
1.450	-6.412	359.05100	1226.13000	528.24050	394.17820	100.20000	2.49839	368.52980	892.96000	1.42653 2035.32001
1.450	-5.899	358.90620	1225.55000	527.99190	394.18630	100.20000	2.49723	368.37990	892.92990	1.42721 2035.28500
1.450	-5.393	358.90210	1226.36000	528.32860	394.11040	100.20000	2.49866	368.37990	892.96000	1.42255 2035.32001
1.450	-4.889	359.19850	1226.20000	528.27710	394.24830	100.20000	2.49865	368.67790	892.95000	1.43018 2035.28500
1.450	-4.381	358.94850	1225.00999	527.76950	394.24900	100.20000	2.49632	368.41990	892.95000	1.43531 2035.28500
1.450	-3.867	358.82320	1226.33000	528.31230	394.08860	100.20000	2.49853	368.29980	892.93990	1.43003 2035.28500
1.450	-3.354	358.98320	1225.92000	528.14990	394.24680	100.30000	2.49736	368.46000	892.95000	1.43425 2035.28500
1.450	-2.838	359.00150	1226.16000	528.25070	394.23050	100.30000	2.49780	368.48000	892.95000	1.44147 2035.28500
1.450	-2.321	358.98320	1225.94000	528.15820	394.24490	100.30000	2.49740	368.46000	892.95000	1.44549 2035.32001
1.450	-1.801	358.64770	1225.99001	528.16160	394.13500	100.30000	2.49717	368.11990	892.97000	1.44543 2035.28500
1.450	-1.283	359.14840	1226.36000	528.34110	394.25830	100.30000	2.49829	368.62990	892.92990	1.42999 2035.25000
1.450	-1.763	359.11380	1225.46001	527.96510	394.33010	100.30000	2.49668	368.58980	892.90990	1.44606 2035.28500
1.450	-2.52	358.52730	1226.39000	528.32180	394.06050	100.30000	2.49776	368.00000	892.91990	1.45631 2035.25000
1.450	.240	358.99370	1225.78999	528.09620	394.26200	100.30000	2.49714	368.47000	892.90990	1.45702 2035.28500
1.449	.738	359.30690	1226.21001	528.28690	394.32180	100.30000	2.49818	368.78980	892.90990	1.45652 2035.28500
1.450	1.223	358.83420	1226.13000	528.22970	394.18070	100.30000	2.49759	368.30980	892.89990	1.44904 2035.21500
GRADIENT	-.00753	.04129	.01679	.00520	.01614	.00003	-.00744	-.00872	.00416	-.00640

	RUN NO.	1645/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.470	-6.935	348.06710	1224.38971	526.79185	390.66800	101.00000	2.49389	357.40990	889.47000	1.32686 2031.39999
1.470	-6.417	347.82640	1223.21889	526.29530	390.69040	101.00000	2.49174	357.15990	889.45000	1.32271 2031.39999
1.470	-5.911	348.03780	1224.14114	526.68700	390.59330	100.90000	2.49437	357.37990	889.47000	1.33321 2031.39999
1.471	-5.403	347.81370	1223.66251	526.47446	390.56320	100.90000	2.49334	357.14990	889.48000	1.34054 2031.39999
1.470	-4.897	347.91360	1223.26062	526.31896	390.69120	101.00000	2.49235	357.25000	889.49000	1.00000 2031.39999
1.484	-4.389	347.84590	1248.13490	536.52452	390.62500	100.90000	2.49239	357.17990	889.47000	.00000 2031.39999
1.485	-3.881	347.80420	1248.54660	536.68392	390.63530	101.00000	2.49263	357.13990	889.47000	.00000 2031.39999
1.484	-3.365	347.93260	1248.53391	536.69321	390.61570	100.90000	2.49319	357.26980	889.48000	.00000 2031.39999
1.484	-2.855	348.36470	1248.92535	536.89719	390.80860	101.00000	2.49334	357.71000	889.46000	.00000 2031.39999
1.470	-2.336	348.09860	1223.44699	526.40952	390.64720	100.90000	2.49378	357.43990	889.46000	1.35072 2031.33000
1.470	-1.821	348.18850	1248.66252	536.77318	390.76930	101.00000	2.49283	357.52980	889.45000	.00000 2031.36501
1.471	-1.304	347.65580	1223.54327	526.41270	390.57300	101.00000	2.49275	356.99000	889.42990	1.34363 2031.36501
1.470	-.785	347.98000	1223.74074	526.52003	390.59280	100.90000	2.49396	357.31980	889.45000	1.34346 2031.36501
1.469	-.274	348.28690	1223.36689	526.39326	390.72920	100.90000	2.49356	357.62990	889.43990	1.34392 2031.33000
1.470	-.219	347.84550	1223.00017	526.20676	390.68650	101.00000	2.49195	357.17990	889.42990	1.34427 2031.29500
1.470	.719	348.32400	1223.90930	526.61668	390.69780	100.90000	2.49443	357.66990	889.43990	1.33987 2031.29500
1.470	1.206	348.01030	1223.78580	526.54097	390.68680	101.00000	2.49312	357.34990	889.42990	1.33310 2031.33000
GRADIENT	.03213	-.3.72861	-1.52803	.00402	-.00113	.00014	.03291	-.00907	.00014	.01732

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1005

IA310 (AEDC 16TF-783) PROBE CALIBRATION

( VCM053 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.493	-6.939	337.72390	1226.522963	526.63848	386.15840	100.20000	2.49880	346.91990	896.51980	1.51016	2033.67500
1.493	-6.426	337.39940	1226.60854	526.63205	386.04810	100.20000	2.49851	346.58980	896.51980	1.50618	2033.64000
1.493	-5.914	337.75220	1227.00319	526.82953	386.21630	100.30000	2.49863	346.95000	896.52980	1.49427	2033.64000
1.493	-5.410	337.51780	1226.51205	526.60772	386.16550	100.30000	2.49886	346.71000	896.53980	1.50631	2033.71001
1.493	-4.904	337.66460	1226.61230	526.66435	386.20020	100.30000	2.49829	346.85990	896.53980	1.51004	2033.67500
1.493	-4.395	337.33280	1226.42488	526.55138	386.13890	100.30000	2.49700	346.51980	896.52980	1.48732	2033.67500
1.493	-3.887	337.34250	1226.18286	526.45658	386.14210	100.30000	2.49701	346.52980	896.50000	1.50287	2033.67500
1.493	-3.373	337.40260	1226.21773	526.47624	386.18680	100.30000	2.49661	346.58980	896.51980	1.48380	2033.67500
1.493	-2.863	337.47240	1225.97780	526.38877	386.22630	100.30000	2.49637	346.65990	896.50000	1.48789	2033.67500
1.493	-2.350	337.91720	1227.67305	526.11452	386.22750	100.30000	2.49964	347.11990	896.51000	1.48208	2033.74500
1.493	-1.832	337.87700	1228.14485	527.29736	386.19290	100.30000	2.50000	347.07980	896.50000	1.46645	2033.71001
1.493	-1.314	337.87700	1228.10573	527.28131	386.19650	100.30000	2.49993	347.07980	896.51000	1.46650	2033.74500
1.493	-7.797	337.72190	1227.52965	527.03441	386.19140	100.30000	2.49888	346.91990	896.49000	1.47093	2033.74500
1.493	-2.289	337.73240	1227.50339	527.02504	386.20800	100.30000	2.49864	346.92990	896.47000	1.46347	2033.74500
1.493	.202	337.53910	1226.56777	526.70636	386.20530	100.30000	2.49726	346.73000	896.46000	1.46809	2033.71001
1.493	.705	337.43190	1226.15842	526.45589	386.19090	100.30000	2.49674	346.61990	896.48000	1.49146	2033.74500
1.493	1.192	337.27710	1225.52060	526.18564	386.18580	100.30000	2.49570	346.46000	896.45000	1.49985	2033.71001
1.493	GRADIENT	.00491	.02181	.00912	.00421	-.00000	-.00004	.00489	-.01202	-.00316	.01137

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.516	-6.939	327.67040	1231.98705	527.45707	383.05250	101.60000	2.49244	336.71000	905.52980	1.61685	2033.78000
1.516	-6.422	328.24710	1232.57402	527.77151	383.20360	101.60000	2.49395	337.29980	905.54980	1.61208	2033.74500
1.516	-5.914	327.79710	1232.22636	527.56887	383.07470	101.60000	2.49298	336.83980	905.53980	1.61655	2033.74500
1.516	-5.410	327.60350	1231.67032	527.32363	383.06880	101.60000	2.49162	336.63990	905.54980	1.60910	2033.78000
1.516	-4.897	327.47000	1230.70735	526.93017	383.10400	101.60000	2.48994	336.50000	905.53980	1.61444	2033.78000
1.516	-4.396	327.35450	1230.03896	526.65271	383.1890	101.60000	2.48877	336.37990	905.54980	1.61940	2033.74500
1.516	-3.887	327.06180	1229.61224	526.44429	383.05100	101.60000	2.48784	336.07980	905.53980	1.62403	2033.74500
1.516	-3.378	327.10060	1229.86395	526.54729	383.05250	101.60000	2.48810	336.11990	905.54980	1.61550	2033.74500
1.516	-2.863	327.15040	1229.58569	526.44645	383.08940	101.60000	2.48778	336.16990	905.54980	1.61998	2033.78000
1.516	-2.346	327.23800	1229.80246	526.54364	383.10550	101.60000	2.48814	336.25980	905.54980	1.61560	2033.78000
1.516	-1.834	327.14770	1230.48763	526.79581	383.02880	101.60000	2.48891	336.16990	905.51980	1.60245	2033.78000
1.516	-1.314	327.43040	1231.00995	527.04128	383.08450	101.60000	2.49000	336.46000	905.51980	1.59775	2033.71001
1.516	-.799	327.59330	1231.91527	527.41756	383.05400	101.60000	2.49182	336.62990	905.51000	1.60064	2033.71001
1.516	-.288	328.00150	1232.92038	527.86868	383.10940	101.60000	2.49387	337.04980	905.53980	1.59533	2033.74500
1.516	-.203	327.40230	1230.83290	526.96754	383.10160	101.60000	2.48947	336.42990	905.52980	1.58990	2033.78000
1.516	.704	327.12960	1230.33289	526.73270	383.05790	101.60000	2.48822	336.14990	905.51980	1.58649	2033.78000
1.516	1.195	327.50050	1230.79652	526.96835	383.21240	101.70000	2.48881	336.52980	905.51000	1.58594	2033.78000
1.516	GRADIENT	.04569	.23807	.09912	.00640	.00640	.00027	.04718	-.00549	-.00635	.00104

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1006

(VCM053) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1626/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.000	PHI =	180.000
P	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PAFM
ALPHA	1.542	316.93950	1236.10443	527.20490	378.81130	101.30000	2.48784	325.76980	906.76980	1.54144 2033.42999
	-6.938	316.93950	1236.10443	527.20490	378.91500	101.30000	2.49174	326.53980	906.78980	1.53929 2033.42999
	-6.426	317.68680	1237.91125	528.02959	378.91500	101.30000	2.49536	327.25000	906.79980	1.54127 2033.42999
	1.541	318.37570	1239.53288	528.77254	379.00900	101.30000	2.49220	326.71000	906.76000	1.51885 2033.42999
	-5.921	318.37570	1239.53288	528.77254	378.99460	101.40000	2.48761	326.04980	906.76980	1.44833 2033.42999
	1.540	317.85130	1238.72697	528.37016	378.99460	101.40000	2.48640	325.84990	906.76980	1.44942 2033.39500
	-5.410	317.85130	1238.72697	527.80067	378.97310	101.40000	2.48690	325.76980	906.76000	1.44522 2033.39500
	1.541	317.21340	1237.53450	527.40936	378.92110	101.30000	2.48855	326.16990	906.74000	1.44068 2033.39500
	-4.902	317.02080	1236.59581	527.40936	378.86210	101.30000	2.48960	326.32980	906.74000	1.43592 2033.36000
	1.542	317.02080	1236.59581	527.54726	378.86210	101.30000	2.49203	326.54980	906.72000	1.41196 2033.36000
	-4.395	316.94140	1236.99956	527.54726	378.93600	101.30000	2.49362	326.80980	906.72000	1.41541 2033.32500
	1.542	316.94140	1236.99956	527.91193	378.93600	101.30000	2.49495	327.15990	906.72000	1.39243 2033.36000
	-3.887	317.33030	1237.77054	527.91193	378.98000	101.40000	2.49566	327.25980	906.67990	1.38841 2033.36000
	-3.373	317.33030	1237.77054	528.29313	378.98000	101.40000	2.49459	327.14990	906.65990	1.40361 2033.32500
	1.542	317.48390	1238.70171	528.77460	378.90360	101.30000	2.49241	326.74000	906.65990	1.41208 2033.32500
	-2.863	317.48390	1238.70171	529.13522	378.92380	101.30000	2.49022	326.66990	906.64990	1.42709 2033.28999
	1.542	317.69580	1239.86662	529.13522	379.03000	101.40000	2.49157	326.35990	906.62990	1.43083 2033.32500
	-2.350	317.69580	1239.86662	529.66925	379.03270	101.40000	.00116	.16542	-.02369	-.00633 - .01772
	1.542	317.94780	1240.69460	529.66925	378.99580	101.40000	2.49241	326.74000	906.65990	1.41208 2033.32500
	-1.828	318.28710	1241.93526	529.84116	378.98830	101.40000	2.49022	326.66990	906.64990	1.42709 2033.28999
	-1.314	318.38380	1242.34286	529.84116	379.04520	101.40000	2.49157	326.35990	906.62990	1.43083 2033.32500
	1.542	318.796	1242.34286	529.52735	378.99460	101.40000	.00116	.16542	-.02369	-.00633 - .01772
	-796	318.27810	1241.56583	529.52735	378.99460	101.40000	2.49241	326.74000	906.65990	1.41208 2033.32500
	1.542	318.27810	1241.56583	529.02215	378.99580	101.40000	2.49022	326.66990	906.64990	1.42709 2033.28999
	-288	317.88040	1240.43024	529.02215	378.98830	101.40000	2.49157	326.35990	906.62990	1.43083 2033.32500
	1.542	317.88040	1240.43024	528.85590	378.88670	101.40000	.00116	.16542	-.02369	-.00633 - .01772
	-204	317.81250	1240.02362	528.85590	378.88670	101.40000	2.49241	326.74000	906.65990	1.41208 2033.32500
	1.542	317.81250	1240.02362	528.90540	378.75336	101.40000	2.49022	326.66990	906.64990	1.42709 2033.28999
	1.194	317.50930	1239.90540	528.75336	378.75336	101.40000	2.49157	326.35990	906.62990	1.43083 2033.32500
	1.542	317.15971	.71265	.29980	.00997	.00116	.16542	-.02369	-.00633 - .01772	-.00633 - .01772

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1007

IA310 (AEDC 16TF-783) PROBE CALIBRATION

( VCM054 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.		RN/0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	2.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
.600	-6.906	1252.03000	1596.58000	315.18410	522.39650	100.30000	2.49564	1261.78000	1306.52000	.99641 2034.58501
.599	-6.393	1252.70799	1596.73000	314.75420	522.46310	100.30000	2.49421	1262.45000	1306.56000	.99370 2034.55000
.599	-5.888	1252.34399	1596.64999	314.98580	522.42720	100.30000	2.49498	1262.09000	1306.56000	.97561 2034.51500
.600	-5.376	1252.47501	1597.22000	315.35770	522.38960	100.30000	2.49681	1262.23000	1306.60001	.97013 2034.51500
.599	-4.867	1252.51199	1596.39999	314.63770	522.47070	100.30000	2.49351	1262.25000	1306.59000	.95791 2034.48000
.600	-4.359	1251.83701	1597.11000	315.78810	522.32400	100.30000	2.49828	1261.60001	1306.62000	.95245 2034.48000
.600	-3.844	1252.29800	1596.89999	315.23340	522.39840	100.30000	2.49609	1262.05000	1306.62000	.95257 2034.51500
.600	-3.328	1251.69600	1597.02000	315.82790	522.31540	100.30000	2.49835	1261.46001	1306.63000	.94748 2034.51500
.600	-2.814	1252.18800	1597.30000	315.65940	522.34790	100.30000	2.49797	1261.95000	1306.66000	.94233 2034.55000
.600	-2.295	1252.06900	1596.70000	315.25340	522.38990	100.30000	2.49594	1261.82001	1306.67000	.94268 2034.4501
.600	-1.781	1251.82001	1596.92000	315.64180	522.33960	100.30000	2.49759	1261.58000	1306.64999	.94255 2034.44501
.600	-1.259	1251.73900	1596.92999	315.71730	522.32910	100.30000	2.49787	1261.50000	1306.66000	.97801 2034.44501
.601	-7.433	1251.43600	1597.34000	316.30980	522.25460	100.30000	2.50037	1261.21001	1306.67999	.98033 2034.44501
.600	-235	1251.91299	1596.86000	315.51560	522.44950	100.40000	2.49651	1261.67000	1306.67999	.98321 2034.44501
.600	.258	1251.43800	1596.75000	315.81300	522.30980	100.30000	2.49807	1261.20000	1306.69000	.98847 2034.44501
.600	.760	1252.39200	1597.28000	315.47580	522.37430	100.30000	2.49729	1262.14999	1306.70000	.99075 2034.44501
.600	1.250	1251.87500	1596.75000	315.45460	522.45530	100.30000	2.49620	1261.63000	1306.71001	.99108 2034.34000
GRADIENT	-.06135	.02360	.07019	-.00054	.00963	.00022	-.05994	.01694	.00807	-.01839
RUN NO.	1471/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		RN/L	PC	PREF	PREF	SH10+3 PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
.800	-6.935	879.75590	1341.24001	394.27320	496.40700	100.30000	2.49777	889.65990	1046.80000	1.59564 2038.39999
.800	-6.421	879.92940	1341.12000	394.06640	496.4750	100.30000	2.49710	889.82980	1046.83000	1.60400 2038.39999
.800	-5.912	879.53590	1341.10001	394.31910	496.38620	100.30000	2.49774	889.43990	1046.84000	1.61642 2038.39999
.800	-5.407	879.89260	1340.89000	393.92110	496.54440	100.40000	2.49590	889.78980	1046.89000	1.62083 2038.36501
.800	-4.902	879.90890	1341.13000	394.08790	496.53170	100.40000	2.49659	889.80980	1046.92999	1.62054 2038.36501
.801	-4.395	879.34330	1341.14000	394.47970	496.43950	100.40000	2.49763	889.25000	1046.97000	1.62052 2038.36501
.800	-3.886	879.67770	1341.05000	394.18550	496.50290	100.40000	2.49676	889.57980	1046.97000	1.62480 2038.39999
.800	-3.379	879.74800	1341.09000	394.16750	496.51000	100.40000	2.49676	889.64999	1047.02000	1.62058 2038.39999
.800	-2.896	879.61690	1341.08000	394.24930	496.49000	100.40000	2.49696	889.51980	1047.03999	1.61644 2038.39999
.800	-2.354	879.72850	1341.07001	394.16630	496.50900	100.40000	2.49674	889.62990	1047.07001	1.5994 2038.39999
.800	-1.841	879.41600	1341.03000	394.34890	496.46290	100.40000	2.49717	889.31980	1047.10001	1.59179 2038.39999
.800	-1.332	880.06300	1340.99001	393.87940	496.57150	100.40000	2.49590	889.96000	1047.13000	1.57962 2038.39999
.800	-.819	879.90010	1341.05000	394.03420	496.53880	100.40000	2.49637	889.79980	1047.16000	1.57955 2038.36501
.800	-.312	879.49780	1340.95000	394.23410	496.57320	100.50000	2.49621	889.39990	1047.19000	1.57561 2038.39999
.800	-.177	879.70090	1340.87000	394.03660	496.61450	100.50000	2.49560	889.59990	1047.21001	1.5757† 2038.39999
.800	.686	879.93970	1341.09000	394.03710	496.62960	100.50000	2.49585	889.83980	1047.24001	1.56737 2038.39999
.800	1.179	879.93070	1341.03999	394.00610	496.63350	100.50000	2.49571	889.82980	1047.28000	1.54341 2038.39999
GRADIENT	.03624	-.02245	-.04128	.02545	.01943	-.00024	.03551	.05641	-.01248	-.00336

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1008  
(VCM054) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1505/0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.500	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	
.897	-6.924	755.42720	1274.08000	425.86740	482.20190	100.20000	2.49722	765.42990	979.61990	5.52299	2036.50999
.901	-6.413	752.39430	1273.32001	427.15210	481.73000	100.20000	2.49911	762.40990	979.64990	5.95317	2036.54500
.900	-5.901	751.97950	1272.03000	426.51290	481.79350	100.20000	2.49613	761.98000	979.68990	6.00035	2036.50999
.900	-5.397	752.53220	1272.13000	426.25270	481.97000	100.30000	2.49510	762.52980	979.72000	6.00035	2036.50999
.899	-4.892	753.28320	1273.17000	426.52000	481.9490	100.30000	2.49696	763.28980	979.75980	5.94009	2036.50999
.900	-4.384	753.22090	1274.03000	427.14840	481.89060	100.30000	2.49940	763.24000	979.79980	5.75961	2036.50999
.900	-3.879	752.86690	1273.39999	426.92600	481.98000	100.40000	2.49756	762.87990	979.80980	5.50024	2036.50999
.901	-3.364	751.56200	1272.31000	426.95310	481.85890	100.40000	2.49629	761.56980	979.83980	4.96551	2036.50999
.900	-2.856	751.61940	1271.82001	426.58280	481.92260	100.40000	2.49487	761.61990	979.85990	5.20646	2036.50999
.899	-2.344	752.80200	1272.25999	426.18120	482.09130	100.40000	2.49453	762.79980	979.88990	5.15603	2036.47501
.900	-1.830	752.57200	1272.89000	426.75120	482.06710	100.50000	2.49598	762.57980	979.92990	5.09331	2036.50999
.900	-1.314	752.57810	1273.14999	426.92630	482.04030	100.50000	2.49668	762.58980	979.92990	5.02094	2036.50999
.900	-805	752.57230	1272.86000	426.73050	482.15650	100.60000	2.49532	762.57980	979.96000	4.95167	2036.47501
.900	-296	752.94340	1272.97000	426.58500	482.21260	100.60000	2.49514	762.95000	979.98000	4.63443	2036.47501
.900	-193	752.79130	1273.05000	426.73070	482.17600	100.60000	2.49555	762.79980	979.99000	4.75631	2036.47501
.900	.699	752.56960	1273.05000	426.86250	482.22140	100.70000	2.49527	762.57980	980.03980	4.84701	2036.44000
.900	1.191	752.60010	1273.02000	426.82370	482.23050	100.70000	2.49515	762.60990	980.04980	5.29993	2036.44000
GRADIENT		-.01983	-.02454	-.00502	.05760	.06808	-.00043	-.02003	.04679	-.14116	-.01136
RUN NO.		1511/0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.500	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	
1.099	-6.976	565.44190	1206.06000	478.21020	450.59080	99.80000	2.50018	574.62990	911.79980	1.45412	2036.02000
	-6.465	564.74070	1205.99001	478.44680	450.35790	99.70000	2.50093	574.92990	911.79980	1.44658	2036.02000
	-5.962	565.00100	1206.03000	478.36720	450.41280	99.70000	2.50090	575.18990	911.79980	1.45040	2036.02000
	-5.457	564.84110	1206.00000	478.41320	450.37960	99.70000	2.50091	575.02980	911.80980	1.44308	2036.02000
	-4.961	564.87330	1205.80000	478.28370	450.40840	99.70000	2.50043	575.05980	911.82980	1.43963	2036.02000
	-4.461	564.88600	1205.53999	478.12740	450.43900	99.70000	2.49983	575.06980	911.80980	1.38739	2036.02000
	-3.954	564.77170	1205.91000	478.38770	450.45410	99.80000	2.50015	574.96000	911.80980	1.45040	2036.02000
	-3.449	565.01120	1206.00000	478.34570	450.41850	99.70000	2.50083	575.00000	911.83980	1.39096	2036.02000
	-2.948	564.91110	1206.00000	478.38530	450.39580	99.70000	2.50088	575.00000	911.80980	1.39821	2036.02000
	-2.443	564.81030	1206.03999	478.44820	450.36840	99.70000	2.50102	575.00000	911.82980	1.40579	2036.05499
	-1.943	564.77220	1205.84000	478.34690	450.38110	99.70000	2.50057	574.96000	911.81980	1.42042	2036.05499
	-1.441	564.91140	1205.98000	478.37350	450.39790	99.70000	2.50083	575.00000	911.80980	1.41679	2036.05499
	-1.939	564.87210	1205.91000	478.34810	450.39650	99.70000	2.50069	575.00000	911.81980	1.41678	2036.02000
	-4.442	564.98220	1205.92000	478.31050	450.42040	99.70000	2.50066	575.00000	911.6990	1.4202†	2036.05499
	-1.00	565.01950	1206.14999	478.42970	450.32370	99.59999	2.50175	575.21000	911.78980	1.42038	2036.05499
	.562	564.88090	1206.00999	478.40310	450.30710	99.59999	2.50150	575.06980	911.78980	1.42769	2036.05499
	1.063	565.07980	1206.13000	478.39400	450.33960	99.59999	2.50168	575.26980	911.76980	1.42027	2036.05499
	1.100	565.02340	.05269	.02142	-.01705	-.02079	.00023	.02393	-.00691	-.00077	.00686

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM054) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1527/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.500	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.250	-6.945	462.72240	1198.00000	505.80690	426.85550	100.50000	2.49716	472.84990	864.30980	1.21130	2035.67000		
-6.431	462.79000	1198.34000	505.96440	426.83860	100.50000	2.49787	472.91990	864.30980	1.21096	2035.63499			
1.250	-5.924	462.50270	1198.07001	505.89060	426.79050	100.50000	2.49728	472.62990	864.32980	1.21445	2035.67000		
1.250	-5.417	462.54300	1198.03000	505.86160	426.80520	100.50000	2.49720	472.66990	864.31980	1.21127	2035.67000		
1.249	-4.916	462.74390	1197.78999	505.69580	426.88260	100.50000	2.49674	472.86990	864.32980	1.21473	2035.63499		
1.250	-4.408	462.58470	1197.72000	505.69510	426.84770	100.50000	2.49658	472.71000	864.33980	1.20518	2035.63499		
-3.898	462.51290	1198.02000	505.86280	426.79810	100.50000	2.49718	472.63990	864.31980	1.19850	2035.63499			
1.250	-3.391	462.58230	1198.11000	505.89330	426.80740	100.50000	2.49737	472.71000	864.31980	1.20159	2035.63499		
1.250	-2.882	462.532270	1198.06000	505.87890	426.79930	100.50000	2.49726	472.65990	864.31980	1.20483	2035.63499		
1.250	-2.372	462.23540	1197.81000	505.81740	426.74630	100.50000	2.49672	472.55990	864.31980	1.20189	2035.67000		
1.250	-1.868	462.56010	1198.44000	506.06540	426.76810	100.50000	2.49804	472.68990	864.30980	1.20126	2035.67000		
-1.356	462.71020	1198.36000	505.99220	426.81570	100.50000	2.49790	472.83980	864.30980	1.20453	2035.63499			
1.250	-8.848	462.63260	1198.00000	505.82670	426.83180	100.50000	2.49715	472.75980	864.30980	1.20170	2035.67000		
1.250	-3.343	462.50340	1197.96001	505.83470	426.80180	100.50000	2.49706	472.62990	864.29980	1.20174	2035.67000		
1.250	.146	462.42480	1197.78000	505.76050	426.79930	100.50000	2.49668	472.54980	864.30980	1.23094	2035.63499		
1.250	.654	462.76270	1197.95000	505.77270	426.87110	100.50000	2.49707	472.88990	864.29980	1.23077	2035.63499		
1.250	1.149	462.69340	1197.89999	505.76270	426.93430	100.50000	2.49637	472.81980	864.28980	1.23408	2035.63499		
GRADIENT	.00721	.00921	.00311	.00589	.00648	-.00002	.00002	.00727	-.00610	.00400	.00148		
	RUN NO.	1544/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00							
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.400	-6.953	381.85640	1214.55000	523.63530	402.19240	100.10000	2.49736	391.55980	881.01000	1.16967	2035.14500		
-6.436	381.79520	1214.86000	523.77200	402.07280	100.00000	2.49847	391.50000	881.02980	1.17560	2035.14500			
-5.929	381.99000	1215.34000	523.97800	402.15770	100.10000	2.49890	391.70000	881.02980	1.16891	2035.17999			
-5.422	381.91550	1214.56000	523.63820	402.06540	99.89999	2.49861	391.61990	881.03980	1.17277	2035.17999			
-4.918	381.88130	1215.32001	523.97140	402.12700	100.10000	2.49878	391.58980	881.04980	1.17203	2035.21500			
-4.416	381.79650	1214.63000	523.67140	402.16670	100.10000	2.49746	391.50000	881.04980	1.16959	2035.17999			
-3.911	381.88000	1215.50000	523.80430	402.08300	100.00000	2.49949	391.68990	881.01980	1.17201	2035.17999			
-3.406	381.72560	1214.92299	523.80400	402.04520	100.00000	2.49855	391.42990	881.03980	1.16620	2035.17999			
-2.893	381.74550	1214.86000	523.77290	401.98580	99.89999	2.49903	391.45000	881.03980	1.16627	2035.21500			
-2.387	381.79320	1215.17999	523.91210	401.97000	99.89999	2.49965	391.50000	881.02980	1.17217	2035.17999			
-1.880	381.94170	1215.17000	523.90480	402.15940	100.10000	2.49855	391.64990	881.02980	1.16597	2035.17999			
-1.366	381.78560	1214.80000	523.74610	402.00370	99.89999	2.49895	391.49000	880.99000	1.16632	2035.21500			
-863	381.87650	1214.49001	523.60860	402.20410	100.10000	2.49727	391.57980	881.01000	1.16973	2035.17999			
-359	382.03910	1215.37000	523.99020	402.02610	99.89999	2.50018	391.75000	881.01000	1.18450	2035.17999			
-132	381.99370	1214.74001	523.71560	402.21560	100.10000	2.49781	391.70000	880.99000	1.17571	2035.17999			
1.399	.639	381.81670	1214.56000	523.64040	402.03560	99.89999	2.49854	391.51980	881.00000	1.18215	2035.17999		
1.400	1.134	381.90890	1215.67000	524.12400	401.95850	99.89999	2.50063	391.61990	880.97000	1.17794	2035.14500		
GRADIENT	.01647	-.00513	-.00256	-.00785	-.00015	-.01849	-.00111	.01663	-.01126	.00183	-.00495		

## PARAMETRIC DATA

	RUN NO.	1561/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.500	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.450	-6.907	359.04320	1225.75000	528.08200	394.28120	100.30000	2.49712	368.51980	892.88990	1.44949	2035.28500		
1.450	-6.392	359.08130	1226.00000	528.18820	394.27030	100.30000	2.49760	368.55980	892.88990	1.45298	2035.28500		
1.450	-5.882	358.97070	1226.42999	528.36130	394.19600	100.30000	2.49825	368.45000	892.88990	1.44869	2035.28500		
1.450	-5.371	358.78540	1226.03999	528.18970	394.17360	100.30000	2.49739	368.25980	892.88990	1.44537	2035.25000		
1.450	-4.869	358.833570	1225.84000	528.10890	394.20780	100.30000	2.49708	368.30980	892.88990	1.44939	2035.25000		
1.450	-4.360	359.266880	1225.98000	528.18920	394.33080	100.30000	2.49774	368.75000	892.87990	1.45300	2035.28500		
1.450	-3.846	358.82590	1225.85001	528.11280	394.20390	100.30000	2.49709	368.29980	892.88990	1.44937	2035.32001		
1.450	-3.331	358.86300	1226.27000	528.28930	394.17700	100.30000	2.49786	368.33980	892.86990	1.44510	2035.28500		
1.450	-2.816	358.85520	1225.86000	528.11840	394.21220	100.30000	2.49714	368.32980	892.87990	1.44559	2035.28500		
1.450	-2.304	358.97270	1226.03999	528.19920	394.23240	100.30000	2.49756	368.45000	892.85990	1.43411	21500		
1.450	-1.784	358.97270	1226.03000	528.19510	394.23340	100.30000	2.49755	368.45000	892.86990	1.43038	2035.32001		
1.449	-1.267	359.23000	1225.82001	528.12060	394.33350	100.30000	2.49742	368.71000	892.85990	1.43063	2035.28500		
1.449	-755	358.79200	1226.66000	528.44750	394.11890	100.30000	2.49848	368.26980	892.84990	1.42220	2035.25000		
1.451	-246	358.79470	1226.13000	528.22750	394.23880	100.40000	2.49696	368.26980	892.83980	1.41910	2035.28500		
1.450	-245	358.85550	1225.85001	528.11430	394.21310	100.30000	2.49712	368.32980	892.83980	1.40834	2035.28500		
1.450	.749	358.76510	1226.17999	528.24680	394.22490	100.40000	2.49702	368.24000	892.83980	1.41134	2035.32001		
1.450	1.238	358.62870	1225.82001	528.09010	394.21510	100.40000	2.49626	368.09990	892.82980	1.41946	2035.32001		
GRADIENT		- .03977	.02015	.006335	-.00376	.01501	-.00009	-.004022	-.00982	-.00711	.00483		

	RUN NO.	1646/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	2.49	PHI =	180.000	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC					
1.470	-6.918	348.46240	1224.19576	526.74548	390.75390	100.90000	2.49435	357.80980	889.41990	1.31908	2031.25999		
1.470	-6.398	347.87430	1223.89722	526.57602	390.67940	101.00000	2.49229	357.21000	889.41990	1.30580	2031.25999		
1.470	-5.895	348.10890	1223.75954	526.53794	390.72190	101.00000	2.49316	357.45000	889.41990	1.33314	2031.25999		
1.470	-5.385	347.91240	1223.60703	526.46043	390.67090	101.00000	2.49273	357.25000	889.40990	1.33328	2031.22501		
1.470	-4.881	348.08030	1223.48479	526.42389	390.66210	100.90000	2.49336	357.41990	889.41990	1.33687	2031.19000		
1.470	-4.369	347.93460	1222.98958	526.21037	390.65360	100.90000	2.49248	357.26980	889.41990	1.34084	2031.19000		
1.471	-3.862	347.56010	1223.05911	526.20786	390.52250	100.90000	2.49229	356.88990	889.40990	1.34071	2031.12000		
1.470	-3.347	348.10690	1223.90353	526.59581	390.68970	101.00000	2.49376	357.45000	889.39990	1.34329	2031.15500		
1.470	-2.830	347.87260	1223.61430	526.45964	390.65090	101.00000	2.49282	357.21000	889.41990	1.33670	2031.15500		
1.470	-2.320	348.11160	1223.18341	526.30453	390.77640	101.00000	2.49214	357.45000	889.38990	1.33378	2031.12000		
1.470	-1.804	348.12890	1248.73943	536.79696	390.73830	101.00000	2.49299	357.47000	889.39990	.00000	2031.12000		
1.484	-1.291	347.94310	1248.42014	536.64972	390.70140	101.00000	2.49236	357.27980	889.38990	.00000	2031.08501		
1.484	-1.777	348.22440	1249.31371	537.03712	390.71390	101.00000	2.49414	357.56980	889.39990	.00000	2031.08501		
1.484	-2.677	347.98290	1223.00197	526.21905	390.71970	101.00000	2.49230	357.31980	889.39990	1.35120	2031.08501		
1.484	-225	348.21680	1248.91736	536.87766	390.75290	101.00000	2.49334	357.55980	889.39990	.00000	2031.08501		
1.470	.728	348.00050	1223.40536	526.38462	390.68820	101.00000	2.49303	357.33980	889.37990	1.35075	2031.01500		
1.484	1.219	348.35670	1248.62254	536.77587	390.83760	101.00000	2.49273	357.70000	889.37990	.00000	2031.05000		
GRADIENT	.05140	3.56350	1.46773	.02464	.01621	.00002	.05239	.00566	-.00985	-.00711	.00483		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1011

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM054) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1596/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.492	-6.926	338.12060	1227.84262	527.20580	386.23610	100.30000	2.50098	347.32980	896.45000	1.51242 2033.71001
1.493	-6.404	337.97290	1228.51529	527.45535	386.18070	100.30000	2.50094	347.17990	896.47000	1.47352 2033.71001
1.493	-5.902	338.23680	1229.06683	527.70512	386.24120	100.30000	2.50174	347.45000	896.43990	1.45792 2033.71001
1.493	-5.392	338.28640	1228.83479	527.61871	386.26780	100.30000	2.50159	347.50000	896.47000	1.46567 2033.71001
1.493	-4.888	338.07910	1229.02760	527.67159	386.17530	100.30000	2.50183	347.28980	896.47000	1.46916 2033.64000
1.493	-4.378	338.11870	1228.94353	527.64270	386.19630	100.30000	2.50172	347.32980	896.45000	1.46927 2033.71001
1.493	-3.865	338.33350	1229.26981	527.79723	386.23880	100.30000	2.50250	347.54980	896.45000	1.46890 2033.71001
1.493	-3.357	338.08860	1228.65448	527.52463	386.17410	100.30000	2.50193	347.29980	896.45000	1.49609 2033.67500
1.493	-2.844	338.15720	1229.10437	527.71078	386.19460	100.30000	2.50204	347.36990	896.43990	1.46908 2033.67500
1.493	-2.331	338.16600	1229.36021	527.81307	386.17460	100.30000	2.50249	347.37990	896.43990	1.46877 2033.67500
1.493	-1.818	337.56100	1226.25032	526.50750	386.33330	100.40000	2.49570	346.75000	896.41990	1.46496 2033.67500
1.493	-1.301	337.66480	1227.15106	526.87728	386.27540	100.40000	2.49575	346.85990	896.42990	1.47138 2033.64000
1.493	-7.789	337.32690	1225.78250	526.29403	386.21700	100.30000	2.49547	346.50980	896.40990	1.47300 2033.64000
1.493	-2.283	338.01340	1227.96179	527.24062	386.21700	100.30000	2.50055	347.22000	896.40990	1.49312 2033.64000
1.493	.208	338.19820	1228.30209	527.39682	386.24270	100.30000	2.50142	347.40990	896.39990	1.49653 2033.60500
1.493	.716	338.04050	1228.92664	527.62632	386.17700	100.30000	2.50151	347.25000	896.39990	1.46553 2033.60500
1.493	1.208	338.06080	1228.77191	527.56815	386.19780	100.30000	2.50126	347.26980	896.39990	1.46572 2033.64000
GRADIENT	-.03751	-.17938	-.07566	.00359	.00112	-.00034	-.03892	-.01146	.00079	-.01245

RUN NO. 1612/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.517	-6.923	327.48660	1232.11156	527.47572	383.11010	101.70000	2.49064	336.51980	905.51000	1.56821 2033.74500
1.517	-6.409	327.26490	1231.07129	527.03931	383.12210	101.70000	2.48873	336.28980	905.51000	1.57352 2033.74500
1.516	-5.899	327.20040	1230.00150	526.61402	383.19630	101.70000	2.48684	336.22000	905.50000	1.57490 2033.74500
1.516	-5.391	327.23070	1229.78116	526.53259	383.22660	101.70000	2.48649	336.25000	905.51000	1.57519 2033.74500
1.516	-4.890	327.28520	1230.50520	526.82350	383.14820	101.70000	2.48839	336.30980	905.50000	1.59840 2033.74500
1.516	-4.378	327.54740	1232.24519	527.53661	383.11280	101.70000	2.49103	336.57980	905.50000	1.57204 2033.74500
1.517	-3.870	327.88430	1233.07532	527.90978	383.14990	101.70000	2.49290	336.92990	905.51000	1.57501 2033.71001
1.516	-3.357	328.01120	1233.30521	528.01842	383.17820	101.70000	2.49334	337.05980	905.51000	1.57074 2033.71001
1.517	-2.844	327.57540	1231.85907	527.39179	383.15820	101.70000	2.49041	336.60990	905.51980	1.57254 2033.71001
1.516	-2.331	327.19900	1230.25412	526.71253	383.16240	101.70000	2.48747	336.22000	905.51000	1.58258 2033.71001
1.516	-1.814	326.95780	1229.37794	526.33569	383.23710	101.80000	2.48492	335.97000	905.50000	1.57567 2033.71001
1.517	-1.300	327.00420	1229.92889	526.55637	383.12990	101.70000	2.48660	336.01980	905.51000	1.57896 2033.71001
1.516	-.788	327.36470	1230.46895	526.82040	383.26860	101.80000	2.48741	336.38990	905.49000	1.58233 2033.71001
1.517	-.282	327.33300	1231.08871	527.05615	383.13350	101.70000	2.48903	336.35990	905.51000	1.58151 2033.71001
1.516	.209	327.64450	1231.62331	527.31051	383.26100	101.80000	2.48968	336.67990	905.51000	1.58086 2033.71001
1.517	.714	327.57280	1232.43317	527.61359	383.09520	101.70000	2.49158	336.60990	905.49000	1.57980 2033.71001
1.517	1.209	327.81640	1232.85226	527.81313	383.14140	101.70000	2.49256	336.85990	905.49000	1.57929 2033.71001
GRADIENT	-.00371	-.00858	-.000397	-.00404	.00652	-.00006	-.00380	-.00183	-.0004	-.00418

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM054) ( 04 OCT 91 )

WCTDIC DATA

## PARAMETRIC DATA

BETA = -5.00/ 5.00

MACH	ALPHA	P	PT	Q((PSF))	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.541	-6.920	317.80350	1238.70436	528.35271	379.00610	101.40000	2.49161	326.65990	906.61990	1.49966	2033.2899
1.541	-6.406	317.67550	1238.82962	528.37572	378.94430	101.40000	2.49178	326.52980	906.61990	1.50331	2033.2555
1.541	-5.899	318.09550	1239.14420	528.57405	379.06490	101.40000	2.49279	326.96000	906.59990	1.50299	2033.2555
1.541	-5.391	317.52710	1239.19247	528.48403	378.84890	101.40000	2.49243	326.37990	906.62990	1.51050	2033.2555
1.541	-4.888	318.08300	1239.70129	528.78207	378.99510	101.40000	2.49401	326.95000	906.60990	1.51382	2033.2555
1.541	-4.377	318.03470	1239.53052	528.70806	378.99850	101.40000	2.49357	326.89990	906.60990	1.51018	2033.2555
1.541	-3.865	317.95630	1239.53696	528.69580	378.96480	101.40000	2.49359	326.81980	906.60990	1.51400	2033.2555
1.541	-3.358	317.82200	1238.71281	528.35899	378.98560	101.40000	2.49215	326.67990	906.61887	1.51887	2033.2555
1.541	-2.843	317.41550	1237.48225	527.81679	378.95650	101.40000	2.48951	326.25980	906.58980	1.51647	2033.2555
1.541	-2.329	317.02780	1236.26173	527.28181	378.92290	101.40000	2.48711	325.85990	906.57980	1.52179	2033.2555
1.541	-1.818	317.47490	1237.13947	527.69852	378.99240	101.40000	2.48930	326.31980	906.55980	1.52853	2033.2200
1.541	-1.301	317.89790	1239.24397	528.57330	378.95460	101.40000	2.49333	326.75980	906.54980	1.52596	2033.2200
1.541	-0.790	318.25680	1240.25722	529.02473	378.99630	101.40000	2.49535	327.12990	906.54980	1.52088	2033.2200
1.541	-0.282	317.90040	1238.65593	528.35197	379.01320	101.40000	2.49224	326.75980	906.54980	1.52282	2033.2555
1.541	-0.210	317.55100	1237.82082	527.97024	378.96920	101.40000	2.49033	326.39990	906.52980	1.51993	2033.2200
1.541	-0.713	317.67430	1238.88237	528.39528	378.91280	101.40000	2.49237	326.52980	906.52980	1.52249	2033.2200
1.541	1.205	318.01590	1239.32355	528.62635	379.00490	101.40000	2.49330	326.87990	906.50000	1.51428	2033.2200
GRADENT	-0.01127	-0.04371	-	-	-0.00171	-	-0.00006	-0.01163	-	-0.00613	-0.01770

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCMO55) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1581/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
.600	-6.892	1252.55400	1597.28999	315.35110	522.48580	100.40000	2.49628	1262.31000	1306.77000
.599	-6.376	1252.73000	1597.14999	315.08910	522.51980	100.40000	2.49521	1262.48000	1306.77000
.600	-5.870	1252.90601	1597.48000	315.22220	522.51000	100.40000	2.49597	1262.66000	1306.80000
.600	-5.357	1252.05200	1596.99001	315.51030	522.45410	100.40000	2.49605	1261.81000	1306.83000
.599	-4.847	1253.00000	1597.37000	315.05300	522.62480	100.50000	2.49470	1262.75000	1306.82001
.600	-4.334	1252.39101	1596.84000	315.10690	522.60180	100.50000	2.49444	1262.14000	1306.84000
.600	-3.827	1252.28000	1597.31000	315.59330	522.54440	100.50000	2.49661	1262.03999	1306.86000
.600	-3.307	1252.57800	1597.13000	315.19730	522.59690	100.50000	2.49502	1262.33000	1306.86000
.600	-2.794	1251.66000	1596.80000	315.67260	522.51830	100.50000	2.49646	1261.42000	1306.88000
.600	-2.279	1251.65900	1596.84000	315.70680	522.51440	100.50000	2.49662	1261.42000	1306.89000
.600	-1.762	1252.00999	1597.53999	316.00680	522.49100	100.50000	2.49830	1261.78000	1306.91000
.600	-1.250	1251.88600	1596.67999	315.38620	522.55640	100.50000	2.49532	1261.64000	1306.91000
.600	-.737	1251.78900	1596.95000	315.69240	522.51980	100.50000	2.49666	1261.55000	1306.92000
.600	-.232	1251.98801	1597.17000	315.71460	522.52290	100.50000	2.49693	1261.75000	1306.95000
.600	.262	1251.92000	1597.00999	315.63570	522.52980	100.50000	2.49651	1261.67999	1306.94000
.600	.766	1252.01801	1597.21001	315.72390	522.52270	100.50000	2.49700	1261.78000	1306.97000
.600	1.258	1251.70100	1596.83000	315.66460	522.52030	100.50000	2.49646	1261.46001	1306.97000
.600	GRADIENT	-.13373	-.02515	.08852	-.01358	.00000	.00030	-.113216	.02413

RUN NO. 1472/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
.800	-6.927	880.04000	1341.14999	394.01320	496.63940	100.50000	2.49585	889.93990	1047.39000
.800	-6.405	879.86910	1341.09000	394.08520	496.61820	100.50000	2.49597	889.76980	1047.44000
.800	-5.903	879.85820	1341.17000	394.15190	496.60820	100.50000	2.49623	889.76000	1047.47000
.800	-5.395	879.64840	1341.02000	394.18360	496.59010	100.50000	2.49615	889.54980	1047.52000
.800	-4.889	879.57690	1341.07001	394.26930	496.66190	100.60000	2.49586	889.48000	1047.53999
.800	-4.380	880.02340	1340.92000	393.85420	496.66110	100.50000	2.49518	889.91990	1047.57001
.800	-3.871	879.4030	1340.82001	394.10890	496.68260	100.60000	2.49517	889.43990	1047.60001
.800	-3.364	879.90990	1341.07001	394.04250	496.71560	100.60000	2.49527	889.80980	1047.62000
.800	-2.854	879.61820	1340.98000	394.17410	496.67820	100.60000	2.49551	889.51980	1047.64999
.800	-2.345	879.90040	1341.03000	394.01950	496.71830	100.60000	2.49516	889.79980	1047.69000
.800	-1.832	879.72850	1341.07001	394.16630	496.68630	100.60000	2.49559	889.62990	1047.70000
.800	-1.323	879.76950	1341.00999	394.09370	496.69950	100.60000	2.49534	889.66990	1047.73000
.800	-.812	879.75930	1341.02000	394.10820	496.69680	100.60000	2.49538	889.65990	1047.75999
.800	-.308	879.70140	1340.83000	394.00660	496.70750	100.60000	2.49491	889.59990	1047.78000
.800	-.181	879.68900	1340.98000	394.12620	496.68950	100.60000	2.49539	889.58980	1047.80000
.800	.689	879.78760	1341.14000	394.17750	496.68850	100.60000	2.49569	889.68990	1047.84000
.800	1.185	879.96140	1341.00000	393.95560	496.73140	100.60000	2.49496	889.85990	1047.84000
.800	GRADIENT	.01344	.00712	-.00390	-.00623	.000543	.01345	.05081	-.00963

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1014  
( VCM055 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1506/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	3.000	PHI =	180.000	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	
.899	-6.916	753.04570	1272.85001	426.44140	482.41650	100.80000	2.49352	763.04980	980.08980	4.82495	2036.44000
.900	-6.396	752.71070	1273.05000	426.77860	482.24730	100.70000	2.49509	762.72000	980.08980	4.48280	2036.44000
.900	-5.892	752.86210	1273.02000	426.66770	482.19240	100.60000	2.49538	762.86990	980.12990	4.40895	2036.44000
.900	-5.389	752.83010	1273.16000	426.78320	482.08520	100.50000	2.49638	762.83980	980.11990	3.98773	2036.44000
.900	-4.879	752.40010	1273.18999	426.86010	481.94850	100.40000	2.49681	762.40990	980.11990	3.87528	2036.44000
.900	-4.369	752.47780	1273.13000	426.97220	481.93800	100.40000	2.49733	762.49000	980.14990	3.85599	2036.47501
.900	-3.863	752.73320	1272.89000	426.65530	481.92460	100.30000	2.49692	762.74000	980.14990	3.90335	2036.47501
.900	-3.353	752.70140	1272.97000	426.72900	481.91020	100.30000	2.49718	762.71000	980.17990	4.20392	2036.44000
.900	-2.841	752.70290	1272.88000	426.66650	481.83400	100.20000	2.49751	762.71000	980.15990	4.27503	2036.47501
.900	-2.331	752.63160	1272.92999	426.74290	481.72950	100.10000	2.49831	762.63990	980.18990	4.12445	2036.44000
.900	-1.818	752.53000	1272.99001	426.84470	481.70460	100.10000	2.49861	762.53980	980.20000	4.14420	2036.47501
.900	-1.308	752.70070	1273.03000	426.77080	481.73140	100.10000	2.49850	762.71000	980.17890	4.14389	2036.44000
.900	-.801	752.64840	1273.19000	426.91190	481.70460	100.10000	2.49900	762.65990	980.22000	4.13347	2036.44000
.900	-.294	752.47070	1272.91000	426.82500	481.61620	100.00000	2.49905	762.48000	980.22000	4.09502	2036.40500
.900	.197	752.75320	1272.91000	426.65720	481.66800	100.00000	2.49868	762.76000	980.23000	4.03661	2036.44000
.900	.703	752.56100	1272.95000	426.79880	481.71440	100.10000	2.49846	762.56980	980.23000	3.96931	2036.44000
.900	1.196	752.85210	1273.03999	426.68750	481.75810	100.10000	2.49833	762.85990	980.23000	3.87485	2036.44000
	GRADIENT	.02669	.00608	-.01170	-.04808	-.06078	.00033	.02651	.01756	.00572	-.00532
	RUN NO.	1512/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00					
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.099	-6.970	565.43410	1205.87000	478.10280	450.44800	99.59999	2.50091	575.61990	911.78980	1.43548	2036.02000
1.099	-6.460	565.22140	1206.03000	478.28000	450.38260	99.59999	2.50138	575.40990	911.77980	1.43154	2036.02000
1.100	-5.957	564.95950	1206.17000	478.46510	450.30810	99.59999	2.50183	575.14990	911.78980	1.42391	2036.02000
1.100	-5.457	564.72140	1205.91000	478.40770	450.28150	99.59999	2.50134	574.90990	911.78980	1.41309	2036.02000
1.100	-4.955	564.73220	1205.84000	478.36280	450.29150	99.59999	2.50118	574.91990	911.80980	0.00000	2035.98500
1.100	-4.453	564.74240	1205.83000	478.35300	450.29490	99.59999	2.50115	574.92990	911.81980	1.37304	2036.02000
1.100	-3.953	565.08280	1205.89000	478.25340	450.36600	99.59999	2.50113	575.26980	911.79980	1.39839	2035.98500
1.100	-3.447	564.78120	1205.94000	478.40160	450.29200	99.59999	2.50138	574.97000	911.80980	1.39467	2035.98500
1.100	-2.945	564.82250	1205.95000	478.32710	450.31200	99.59999	2.50113	575.01000	911.83980	1.39479	2035.98500
1.100	-2.439	565.02080	1206.05000	478.37080	450.49580	99.80000	2.50036	575.21000	911.83980	1.39455	2035.98500
1.100	-1.939	564.63990	1206.03000	478.50980	450.33060	99.70000	2.50107	574.82980	911.84990	1.39457	2035.98500
1.100	-1.436	564.81230	1205.87000	478.34860	450.46750	99.80000	2.50004	575.00000	911.84990	1.39841	2035.98500
1.100	-0.934	564.75120	1205.95000	478.41940	450.44510	99.80000	2.50025	574.93990	911.83980	1.40199	2035.98500
1.100	-0.441	564.93070	1206.05000	478.40650	450.63650	100.00000	2.49923	575.11990	911.83980	1.40554	2035.98500
1.100	-.057	564.84030	1206.05000	478.44210	450.61570	100.00000	2.49927	575.02980	911.83980	1.40554	2035.98500
1.100	.567	564.97000	1206.11000	478.42580	450.63890	100.00000	2.49935	575.15990	911.86990	1.36912	2036.02000
1.100	1.063	565.05030	1206.07001	478.37060	450.58110	99.89999	2.49980	575.24000	911.86990	1.40921	2036.02000
	GRADIENT	.02376	.04150	.01471	.06271	.07666	-.00036	.02416	.00953	.09335	.00226

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM055) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	P/C	PREF	SH10+3	PATM
1.250	-6.939	462.89940	1198.36000	505.95070	426.94170	100.60000	2.49733	473.02980	864.28980	1.20134	2035.67000
-6.420	462.61330	1197.95000	505.80570	426.90800	100.60000	2.49646	472.74000	864.29980	1.20175	2035.67000	
1.250	-5.915	462.43460	1197.80000	505.76860	426.87620	100.60000	2.49613	472.55980	864.30980	1.20190	2035.67000
1.250	-5.409	462.52660	1197.50999	505.60160	426.92990	100.60000	2.49556	472.64990	864.29980	1.20220	2035.70500
1.250	-4.902	462.76810	1198.64000	506.12130	426.80250	100.50000	2.49847	472.89990	864.27980	1.20745	2035.67000
1.250	-4.394	462.50590	1197.59000	505.64650	426.84010	100.50000	2.49630	472.62990	864.27980	1.20851	2035.67000
1.250	-3.887	462.40600	1197.62000	505.68380	426.73460	100.40000	2.49694	472.52980	864.27980	1.21169	2035.70500
1.250	-3.383	462.64820	1198.66000	506.15770	426.69260	100.40000	2.49909	472.77980	864.28980	1.22354	2035.67000
1.250	-2.875	462.55980	1198.47000	506.08080	426.68850	100.40000	2.49869	472.68990	864.26000	1.22698	2035.70500
1.250	-2.361	462.58470	1197.72000	505.69510	426.69530	100.30000	2.49775	472.71000	864.25000	1.23100	2035.67000
1.250	-1.858	462.35420	1197.92000	505.84690	426.61430	100.30000	2.49813	472.48000	864.25000	1.22754	2035.70500
1.250	-1.350	462.48290	1198.00999	505.86450	426.56270	100.20000	2.49892	472.60990	864.24000	1.22745	2035.70500
1.250	-843	462.51490	1197.73000	505.71560	426.59960	100.20000	2.49835	472.63990	864.23000	1.20198	2035.67000
1.250	-340	462.55180	1198.19000	505.94070	426.56250	100.20000	2.49929	472.67990	864.20000	1.20470	2035.67000
1.250	-150	462.69870	1198.56000	506.09590	426.48750	100.10000	2.49965	472.88280	864.24000	1.20114	2035.70500
1.250	.659	462.60380	1197.86000	505.76220	426.53370	100.10000	2.49922	472.73000	864.18990	1.22112	2035.67000
1.250	1.155	462.49490	1197.74001	505.72510	426.51710	100.10000	2.49896	472.61990	864.18990	1.22124	2035.70500
1.250	GRADIENT	-.00509	-.03162	-.01490	-.05366	-.07287	.00036	-.00530	-.01619	-.00007	.00185
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	P/C	PREF	SH10+3	PATM
1.400	-6.942	381.82670	1214.53999	523.63130	402.11250	100.00000	2.49791	391.52980	880.95000	1.18531	2035.17999
1.400	-6.424	381.75560	1214.85001	523.76830	401.99000	99.89999	2.49902	391.46000	880.96000	1.18186	2035.17999
1.400	-5.921	381.79420	1215.02000	523.84200	402.20090	100.20000	2.49758	391.50000	880.95000	1.18484	2035.17999
1.400	-5.413	381.78610	1214.67999	523.69340	402.23070	100.20000	2.49695	391.49000	880.93990	1.18517	2035.14500
1.400	-4.913	381.99070	1215.21001	523.92110	402.24220	100.20000	2.49807	391.70000	880.93990	1.18465	2035.14500
1.400	-4.405	381.85400	1214.92999	523.80150	402.22750	100.20000	2.49746	391.55980	880.95000	1.18179	2035.14500
1.400	-3.900	381.82350	1215.08000	523.86770	401.98850	99.89999	2.49949	391.52980	880.96000	1.17851	2035.17999
1.400	-3.392	381.75390	1215.12000	523.88650	401.96390	99.89999	2.49951	391.46000	880.95000	1.17534	2035.14500
1.400	2.885	382.07400	1214.53999	523.62620	402.11500	99.89999	2.49869	391.77980	880.92990	1.17279	2035.14500
1.400	-2.377	381.76220	1215.42000	524.01760	402.15360	100.20000	2.49828	391.47000	880.92990	1.17194	2035.14500
1.400	1.399	381.98410	1214.69000	523.69380	402.21750	100.10000	2.49771	391.68990	880.92990	1.17576	2035.11000
1.400	-1.363	382.02120	1215.09000	523.86820	402.04710	99.89999	2.49966	391.73000	880.91990	1.17537	2035.14500
1.399	-.857	382.12110	1214.92999	523.79590	402.23610	100.10000	2.49825	391.82980	880.91990	1.16310	2035.11000
1.400	-353	381.71730	1214.64999	523.68160	402.14090	100.10000	2.49744	391.41990	880.91990	1.17893	2035.11000
1.400	135	382.01000	1215.33000	523.97340	402.02100	99.89999	2.50008	391.72000	880.91990	1.17514	2035.14500
1.400	.643	381.85450	1214.85001	523.76660	402.16330	100.10000	2.49791	391.55980	880.88990	1.17561	2035.14500
1.400	1.141	381.93430	1214.73000	523.71220	402.19870	100.10000	2.49775	391.63990	880.89990	1.17260	2035.14500
1.400	GRADIENT	.00713	-.03536	-.01560	.00234	-.00436	-.0003	-.00698	-.00894	-.00133	-.00348

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1016  
( VCM055 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1562 / 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	3.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
1.450	-6.892	358.79320	1226.42999	528.35210	394.21070	100.40000	2.49749	368.26980	892.81980
1.449	-6.374	359.22950	1225.92999	528.16650	394.32320	100.30000	2.49761	368.71000	892.81980
1.450	-5.866	358.60960	1225.72000	528.04760	394.14790	100.30000	2.49666	368.07980	892.81980
1.450	-5.361	359.05030	1226.28999	528.30710	394.23390	100.30000	2.49808	368.52980	892.80980
1.450	-4.847	358.88670	1225.52000	527.97850	394.25340	100.30000	2.49657	368.35990	892.82980
1.450	-4.339	358.78610	1225.89999	528.13130	394.18680	100.30000	2.49714	368.25980	892.78980
1.450	-3.829	358.84330	1226.27000	528.28810	394.17070	100.30000	2.49785	368.31980	892.79980
1.450	-3.316	358.87620	1225.63000	528.02370	394.23970	100.30000	2.49675	368.34990	892.79980
1.450	-2.801	358.66770	1225.89999	528.12520	394.22000	100.40000	2.49643	368.13990	892.80980
1.450	-2.284	359.00070	1226.31000	528.31300	394.28690	100.40000	2.49747	368.48000	892.78980
1.449	-1.772	359.20920	1226.07001	528.22360	394.30400	100.30000	2.49784	368.68990	892.79980
1.450	-1.261	358.95240	1226.14999	528.24390	394.21610	100.30000	2.49774	368.42990	892.78980
1.450	-7.751	358.76830	1225.53000	527.97680	394.21510	100.30000	2.49647	368.24000	892.76000
1.449	-24.1	359.19920	1226.08000	528.22730	394.29980	100.30000	2.49785	368.67990	892.76980
1.449	.250	359.15060	1225.96001	528.17500	394.29570	100.30000	2.49759	368.62990	892.76000
1.449	.757	358.89500	1225.77000	528.08300	394.23290	100.30000	2.49701	368.36990	892.76000
1.450	1.246	359.00050	1226.37000	528.33790	394.21090	100.30000	2.49817	368.48000	892.76000
1.450	GRADIENT	.03871	.03935	.01837	.00626	-.00322	.00012	.03950	-.00992

	RUN NO.	1647 / 0	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	3.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
1.470	-6.903	348.16670	1224.16879	526.70949	390.72170	101.00000	2.49358	357.50980	889.34990
1.484	-6.386	347.87430	1248.6681	536.63646	390.67680	101.00000	2.49234	357.21000	889.34990
1.471	-5.881	347.74410	1223.61314	526.44814	390.59590	101.00000	2.49295	357.07980	889.34990
1.471	-5.369	347.65650	1223.41624	526.36161	390.51540	100.90000	2.49312	356.99000	889.34990
1.470	-4.862	348.14790	1223.63257	526.48917	390.66480	100.90000	2.49379	357.49000	889.35990
1.471	-4.350	347.86430	1223.90575	526.57814	390.60570	100.90000	2.49289	357.20000	889.34990
1.470	-3.845	347.94260	1223.92998	526.59462	390.69310	101.00000	2.49252	357.27980	889.35990
1.470	-3.331	348.32400	1224.58339	526.89201	390.76560	101.00000	2.49387	357.66990	889.35990
1.471	-2.817	347.81540	1223.78575	526.52554	390.66410	101.00000	2.49216	357.14990	889.35990
1.471	-2.306	348.02810	1224.75827	526.93874	390.66260	101.00000	2.49371	357.36990	889.33980
1.470	-1.791	348.11040	1224.05904	526.66113	390.75510	101.00000	2.49254	357.45000	889.33980
1.471	-1.281	347.78760	1223.69768	526.48788	390.68700	101.00000	2.49153	357.11990	889.30980
1.471	-76.9	347.98000	1224.64983	526.89137	390.66260	101.00000	2.49337	357.31980	889.33980
1.471	-26.3	347.91280	1224.18689	526.69696	390.67720	101.00000	2.49261	357.25000	889.32980
1.470	.228	348.00200	1224.06322	526.65411	390.71850	101.00000	2.49246	357.33980	889.31980
1.471	.734	347.96170	1224.27176	526.73589	390.68580	101.00000	2.49280	357.29980	889.30980
1.470	1.228	348.04910	1224.47304	526.82483	390.69020	101.00000	2.49334	357.38990	889.30980
1.470	GRADIENT	-.01105	.07439	.02957	.00444	.01191	-.00008	-.01125	-.00386

	RUN NO.	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00	BETA =	3.000	PHI =	180.000	PREF	PC	RN/L	TT(F)	RN/L	PC	PREF	SH10+3	PATM
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM						
1.470	-6.903	348.16670	1224.16879	526.70949	390.72170	101.00000	2.49358	357.50980	889.34990	1.32246	2031.08501						
1.484	-6.386	347.87430	1248.6681	536.63646	390.67680	101.00000	2.49234	357.21000	889.34990	1.00000	2031.08501						
1.471	-5.881	347.74410	1223.61314	526.44814	390.59590	101.00000	2.49295	357.07980	889.34990	1.34357	2031.01500						
1.471	-5.369	347.65650	1223.41624	526.36161	390.51540	100.90000	2.49312	356.99000	889.34990	1.34378	2031.01500						
1.470	-4.862	348.14790	1223.63257	526.48917	390.66480	100.90000	2.49379	357.49000	889.35990	1.34016	2031.08501						
1.471	-4.350	347.86430	1223.90575	526.57814	390.60570	100.90000	2.49289	357.20000	889.34990	1.30579	2031.05000						
1.470	-3.845	347.94260	1223.92998	526.59462	390.69310	101.00000	2.49252	357.27980	889.35990	1.30915	2031.01500						
1.470	-3.331	348.32400	1224.58339	526.89201	390.76560	101.00000	2.49387	357.66990	889.35990	1.30512	2031.01500						
1.471	-2.817	347.81540	1223.78575	526.52554	390.66410	101.00000	2.49216	357.14990	889.35990	1.30928	2031.05000						
1.471	-2.306	348.02810	1224.75827	526.93874	390.66260	101.00000	2.49371	357.36990	889.33980	1.29818	2031.01500						
1.470	-1.791	348.11040	1224.05904	526.66113	390.75510	101.00000	2.49254	357.45000	889.33980	1.29895	2031.01500						
1.471	-1.281	347.78760	1223.69768	526.48788	390.68700	101.00000	2.49153	357.11990	889.30980	1.29595	2031.01500						
1.471	-76.9	347.98000	1224.64983	526.89137	390.66260	101.00000	2.49337	357.31980	889.33980	1.29495	2031.01500						
1.471	-26.3	347.91280	1224.18689	526.69696	390.67720	101.00000	2.49261	357.25000	889.32980	1.29879	2031.05000						
1.470	.228	348.00200	1224.06322	526.65411	390.71850	101.00000	2.49246	357.33980	889.31980	1.29893	2030.98000						
1.471	.734	347.96170	1224.27176	526.73589	390.68580	101.00000	2.49280	357.29980	889.30980	1.29870	2030.98000						
1.470	1.228	348.04910	1224.47304	526.82483	390.69020	101.00000	2.49334	357.38990	889.30980	1.30185	2030.98000						
1.470	GRADIENT	-.01105	.07439	.02957	.00444	.01191	-.00008	-.01125	-.00386	-.01173	-.00386						

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM055) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1597/0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	3.000	PHI =	180.000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.493	-6.910	337.97290	1228.76447	527.55434	386.17990	100.30000	2.50096	347.17990	896.38990	1.45825 2033.60500
1.493	-6.393	338.09910	1228.77068	527.57224	386.18900	100.30000	2.50172	347.30980	896.34990	1.48076 2033.60500
1.493	-5.886	338.26710	1228.63412	527.53619	386.26880	100.30000	2.50144	347.48000	896.37990	1.47342 2033.60500
1.493	-5.381	338.10180	1228.22449	527.35518	386.25050	100.30000	2.50056	347.30980	896.37990	1.47389 2033.60500
1.493	-4.868	337.76220	1227.36710	526.97447	386.21950	100.30000	2.49864	346.96000	896.36990	1.47113 2033.60500
1.493	-4.363	337.70530	1226.75038	526.72303	386.24560	100.30000	2.49773	346.89990	896.36990	1.47940 2033.60500
1.493	-3.856	337.15770	1226.17555	526.43154	386.19110	100.30000	2.49609	346.33980	896.36990	1.47627 2033.60500
1.493	-3.344	337.20950	1225.67227	526.23656	386.18770	100.30000	2.49516	346.38990	896.33980	1.47312 2033.60500
1.493	-2.830	337.85600	1228.30829	527.35938	386.16580	100.30000	2.50036	347.05980	896.35990	1.47000 2033.60500
1.493	-2.316	338.14990	1228.66464	527.53513	386.31200	100.40000	2.50046	347.35990	896.34990	1.46212 2033.60500
1.493	-1.804	338.07100	1228.76505	527.56592	386.21290	100.30000	2.50106	347.27980	896.34990	1.45826 2033.57001
1.493	-1.292	338.11940	1228.77692	527.57649	386.28050	100.40000	2.50084	347.32980	896.35990	1.46947 2033.57001
1.493	-7.844	337.90700	1227.89069	527.20013	386.28420	100.40000	2.49920	347.10990	896.33980	1.47427 2033.57001
1.493	-2.79	337.64550	1226.99086	526.81161	386.27810	100.40000	2.49738	346.83980	896.32980	1.47534 2033.57001
1.493	.214	337.50300	1226.25389	526.50784	386.30740	100.40000	2.49612	346.74000	896.30980	1.47599 2033.57001
1.493	.720	337.28610	1226.08223	526.40893	386.24510	100.40000	2.49535	346.47000	896.32980	1.47263 2033.57001
1.493	1.213	337.85860	1227.79005	527.15335	386.28810	100.40000	2.49877	347.05980	896.30980	1.46688 2033.53500
GRADIENT	.01595	.03125	.01425	.01775	.02165	-.00007	.01637	-.00933	-.00024	-.01025
RUN NO.		1613/0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00				
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.516	-6.909	327.46020	1231.08409	527.07410	383.17260	101.70000	2.48926	336.49000	905.48000	1.58556 2033.67500
1.517	-6.393	327.22680	1230.64711	526.86922	383.13650	101.70000	2.48817	336.25000	905.47000	1.58207 2033.67500
1.517	-5.885	327.07250	1229.90706	526.55891	383.14480	101.70000	2.48684	336.08980	905.47000	1.58704 2033.67500
1.516	-5.383	326.99540	1229.51770	526.39574	383.15330	101.70000	2.48609	336.00980	905.47000	1.58753 2033.67500
1.516	-4.870	327.01660	1229.25774	526.29813	383.12110	101.60000	2.48616	336.02980	905.47000	1.58386 2033.67500
1.517	-4.359	326.88890	1229.24174	526.27282	383.07300	101.60000	2.48610	335.89990	905.47000	1.58788 2033.64000
1.516	-3.852	326.93770	1229.24765	526.28208	383.08940	101.60000	2.48616	335.95000	905.47000	1.58788 2033.67500
1.517	-3.344	326.84720	1229.83102	526.49523	383.00560	101.60000	2.48706	335.85990	905.48000	1.58710 2033.64000
1.516	-2.829	327.27610	1230.51620	526.82566	383.09180	101.60000	2.48869	336.29980	905.47000	1.58627 2033.67500
1.517	-2.315	327.25420	1231.13715	527.06366	383.02830	101.60000	2.48973	336.27980	905.47000	1.58545 2033.60500
1.516	-1.806	327.75200	1231.66420	527.34322	383.14720	101.60000	2.49126	336.78980	905.46000	1.58887 2033.64000
1.517	-1.293	327.56270	1232.36250	527.58526	383.01930	101.60000	2.49225	336.59990	905.47000	1.58792 2033.60500
1.517	-7.85	327.67770	1233.09805	527.88774	382.99800	101.60000	2.49353	336.72000	905.46000	1.58296 2033.64000
1.517	-2.78	327.97880	1233.82631	528.21578	383.03610	101.60000	2.49509	337.02980	905.46000	1.58206 2033.64000
1.517	.215	327.66160	1232.16989	527.52589	383.07060	101.60000	2.49202	336.70000	905.47000	1.58819 2033.67500
1.516	.720	327.06590	1229.01877	526.21326	383.14920	101.60000	2.48601	336.07980	905.42990	1.59223 2033.64000
1.516	1.214	327.27660	1230.30127	526.74260	383.10620	101.60000	2.48842	336.29980	905.42990	1.59058 2033.67500
GRADIENT	.10709	.38378	.16511	.00113	-.00000	-.00000	.00079	-.000565	-.00047	-.00083

IA310 (AEDC 161FF-783) PROBE CALIBRATION

(VCM055) ( 04 OCT 91 )

PARAMETRIC DATA

RUN NO.	O	RN/L =	2.49	GRADIENT INTERVAL = -5.00/ 5.00							
				P	PT	Q(PSF )	T (R)	TT(F )	RN/L	PC	PREF
MACH											
1.1.541	-6 .907	3117.37790	1237.34473	527.75787	378.98710	101.40000		2.48864	326.22000	906.47000	SH10+3
1.1.542	-6 .393	3117.50270	1239.00281	528.41087	378.96480	101.40000	2.49004	326.34990	906.47000	1.43190	2033.2200
1.1.542	-5 .885	3118.17020	1241.23036	529.37901	379.002720	101.40000	2.49456	327.03980	906.46000	1.42938	2033.2550
1.1.542	-4 .872	3117.87770	1240.96387	529.22307	378.922770	101.40000	2.49368	326.74000	906.47000	1.42600	2033.2200
1.1.542	-4 .359	3117.66500	1239.29393	528.54964	378.91990	101.40000	2.49216	326.51980	906.46000	1.48749	2033.2200
1.1.542	-3 .854	3117.67750	1239.33022	528.56772	378.99240	101.40000	2.49088	326.52980	906.46000	1.43521	2033.2550
1.1.542	-3 .342	3117.36790	1237.39131	527.77394	378.97410	101.40000	2.48938	326.17990	906.42990	1.49305	2033.2200
1.1.542	-2 .828	3117.18410	1236.75432	527.49823	378.96580	101.40000	2.48875	326.21000	906.41990	1.49739	2033.2200
1.1.542	-2 .316	3117.09740	1237.21400	527.65696	378.97070	101.40000	2.48675	325.92990	906.41990	1.49814	2033.2200
1.1.542	-1 .294	3117.41530	1238.71330	528.28436	378.94970	101.40000	2.48964	326.25980	906.41990	1.44110	2033.2200
1.1.542	-1 .785	3118.15990	1241.29121	529.39991	378.98320	101.40000	2.49249	326.74000	906.39990	1.43957	2033.1850
1.1.542	-1 .279	3117.75510	1239.87915	528.79085	379.00070	101.40000	2.49484	327.02980	906.40990	1.43664	2033.1850
1.1.542	-1 .213	3117.54200	1239.37457	528.55975	378.98510	101.40000	2.49134	326.60990	906.39990	1.41270	2033.1850
1.1.542	-1 .71	3117.39480	1239.34389	528.51960	378.92110	101.40000	2.48996	326.38990	906.37990	1.40243	2033.1850
1.1.542	1 .214	3117.56030	1239.53470	528.62262	378.95780	101.40000	2.49062	326.24000	906.34990	1.41327	2033.1850
GRADIENT											
		0.29112	0.29437	-1.1720	-0.00245	-	-0.00018	-	-0.01493	-	
										-0.01382	-0.0098

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM056) ( 04 OCT 91 )

PARAMETRIC DATA

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1019

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM056) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1473/ O	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.800	-6.904	880.00710	1341.320001	394.16160	496.79350	100.70000	2.49528	889.90990	1047.96001
.810	-5.875	879.88770	1341.17999	394.13890	496.78910	100.70000	2.49507	889.78980	1047.99001
.820	-4.859	879.85210	1340.92000	393.97120	496.81080	100.70000	2.49434	889.75000	1048.03000
.800	-3.846	879.53660	1341.05000	394.28170	496.74610	100.70000	2.49530	889.43990	1048.07001
.800	-2.835	879.42700	1340.96001	394.28960	496.73800	100.70000	2.49522	889.32980	1048.07001
.800	-1.818	879.94380	1340.83000	393.84180	496.83520	100.70000	2.49391	889.83980	1048.12000
.800	-.812	879.55810	1340.97000	394.20780	496.75810	100.70000	2.49502	889.46000	1048.13000
.800	.202	879.59590	1341.13000	394.30050	496.74730	100.70000	2.49543	889.50000	1048.14999
.799	1.188	880.13670	1340.78999	393.68120	496.87060	100.70000	2.49344	890.02980	1048.17999
GRADIENT	.03881	-.00768	-.03212	.00709	-.00009	-.00009	.03834	.02370	.00054

RUN NO.	1507/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.900	-6.891	752.97220	1273.07001	426.63670	481.60450	99.89999	2.49941	762.98000	980.26980
.900	-5.863	752.85230	1273.00999	426.66670	481.67530	100.00000	2.49882	762.85990	980.27980
.900	-4.846	752.72090	1273.03999	426.76560	481.64790	100.00000	2.49907	762.73000	980.27980
.900	-3.833	752.92360	1272.95000	426.58300	481.69480	100.00000	2.49856	762.92990	980.29980
.900	-2.821	752.61990	1273.06000	426.83960	481.62720	100.00000	2.49926	762.62990	980.28980
.900	-1.801	752.69340	1272.86000	426.65840	481.57620	99.89999	2.49920	762.70000	980.30980
.900	-.793	752.50980	1273.00000	426.86350	481.44170	99.80000	2.50040	762.51980	980.30980
.900	.217	752.92160	1273.09000	426.68040	481.67920	100.00000	2.49895	762.92990	980.31980
.900	1.202	752.73140	1273.07000	426.73170	481.65430	100.00000	2.49895	762.74000	980.32980
GRADIENT	-.00297	.00349	.00414	-.00014	-.00707	-.00717	.00005	-.00287	-.00743

RUN NO.	1513/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
1.099	-6.963	565.42110	1206.12000	478.25320	450.74070	100.00000	2.49916	575.60990	911.90990
1.100	-5.943	564.63920	1206.10001	478.55080	450.56470	100.00000	2.49948	574.82980	911.91990
1.100	-4.938	564.70000	1206.03000	478.48610	450.66650	100.10000	2.49871	574.88990	911.92990
1.100	-3.933	564.73170	1205.91000	478.40380	450.68650	100.10000	2.49842	574.91990	911.92990
1.100	-2.944	564.73000	1206.05000	478.48580	450.75170	100.20000	2.49816	574.91990	911.91990
1.100	-1.930	564.93040	1206.06000	478.41240	450.79610	100.20000	2.49809	575.11990	911.93990
1.100	-.922	564.98050	1206.05000	478.38670	450.80880	100.20000	2.49804	575.16990	911.92990
1.100	.079	564.91260	1205.84000	478.29150	450.89620	100.30000	2.49701	575.09990	911.96000
1.100	1.069	565.17140	1206.02000	478.29370	450.93600	100.30000	2.49730	575.35990	911.96000
GRADIENT	.07220	-.00611	-.03213	.04577	.03561	-.00026	.00572	.07197	-.00001

## PARAMETRIC DATA

MACH	ALPHA	P	PT	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	4.000	PHI =	180.000
1.250	-6.921	462.96870	1198.47000	505.99120	426.41530	99.89999	2.50168	473.09990	864.15990	1.21726	2035	70500
1.250	-5.887	462.51420	1197.85001	505.77660	426.51100	100.10000	2.49918	472.63990	864.14990	1.21790	2035	70500
1.250	-4.877	462.27470	1197.88000	505.84420	426.29250	99.89999	2.50039	472.39990	864.15990	1.19546	2035	67000
1.250	-3.862	462.25490	1197.84000	505.82810	426.36770	100.00000	2.49972	472.37990	864.14990	1.19868	2035	70500
1.250	-2.853	462.80150	1198.13000	505.85570	426.48220	100.00000	2.50038	472.92990	864.12990	1.20157	2035	70500
1.250	-1.843	462.56880	1198.59000	506.13960	426.29790	99.89999	2.50188	472.70000	864.12990	1.20430	2035	67000
1.250	-.837	462.29710	1197.50000	505.64670	426.41330	100.00000	2.49903	472.41990	864.11990	1.21825	2035	70500
1.250	.174	462.52660	1197.47000	505.58130	426.47680	100.00000	2.49900	472.64990	864.09990	1.21506	2035	70500
1.250	1.160	462.77950	1198.42000	506.00730	426.37060	99.89999	2.50156	472.90990	864.10990	1.21732	2035	67000
GRADIENT	.05504	.00860	-.00768	.01365	.00005	.00002	.05527	-.00925	.00408	-.00002	.00245	.00371
MACH	ALPHA	P	PT	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	4.000	PHI =	180.000
1.400	-6.928	382.00950	12115.39999	524.00390	402.15800	100.10000	2.49902	391.72000	880.84990	1.16885	2035	14500
1.400	-5.895	381.85420	12114.91000	523.79270	402.08570	100.00000	2.49861	391.55980	880.83980	1.16932	2035	11000
1.400	-4.882	381.78520	12114.89000	523.78540	401.99490	99.89999	2.49912	391.49000	880.83980	1.16934	2035	11000
1.400	-3.875	381.87160	12115.28000	523.95410	402.12790	100.10000	2.49870	391.57980	880.84990	1.19089	2035	11000
1.400	-2.864	381.89230	12115.14999	523.89799	402.121830	100.20000	2.49789	391.59990	880.84990	1.18157	2035	11000
1.400	-1.855	381.68700	12114.77000	523.73490	402.04860	100.00000	2.49823	391.38990	880.83980	1.17881	2035	07500
1.400	-.853	381.81370	12115.06000	523.85910	402.05930	100.00000	2.49885	391.51980	880.80980	1.17853	2035	07500
1.400	.157	381.89160	12115.27000	523.94950	402.06330	100.00000	2.49929	391.59990	880.82980	1.17520	2035	11000
1.400	1.146	381.47880	12114.82001	523.76070	401.98140	100.00000	2.49817	391.17990	880.81980	1.17563	2035	14500
GRADIENT	-.03389	-.01128	-.00426	-.01165	-.00353	-.00002	-.03433	-.00499	-.00055	-.00245	.00245	.00371
MACH	ALPHA	P	PT	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA =	4.000	PHI =	180.000
1.449	-6.869	359.31640	1226.27000	528.31230	394.31910	100.30000	2.49829	368.79980	892.73000	1.44134	2035	25000
1.450	-5.830	359.03220	1225.96001	528.16890	394.25850	100.30000	2.49748	368.50980	892.72000	1.43795	2035	25000
1.450	-4.814	359.10060	1226.08000	528.22240	394.26900	100.30000	2.49775	368.57980	892.71000	1.43406	2035	21500
1.450	-3.794	359.07100	1226.07001	528.21680	394.26050	100.30000	2.49771	368.54980	892.72000	1.42660	2035	25000
1.450	-2.776	358.65770	1225.92000	528.13310	394.14450	100.30000	2.49705	368.12990	892.72000	1.42306	2035	25000
1.450	-1.752	358.96970	1226.60001	528.43190	394.18020	100.30000	2.49855	368.45000	892.71000	1.38557	2035	25000
1.450	-.738	358.89600	1225.60001	528.01220	394.24880	100.30000	2.49672	368.36990	892.72000	1.40128	2035	25000
1.450	.272	358.88550	1225.73000	528.06590	394.23360	100.30000	2.49694	368.35990	892.68990	1.40481	2035	25000
1.450	1.252	358.75510	1226.14999	528.23390	394.15410	100.30000	2.49755	368.23000	892.68990	1.40066	2035	25000
GRADIENT	-.04118	-.02804	-.01376	-.01034	-.00002	-.00009	-.04188	-.00424	-.00585	-.00245	.00245	.00371

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

( VCM056 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO. 1648/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.470	-6.879	348.31270	1224.77052	526.96697	390.73850	101.00000	2.49431	357.65990	889.29980	1.30828	2030.98000
1.471	-5.845	347.89180	1224.222517	526.71024	390.64890	101.00000	2.49300	357.23000	889.27980	1.30882	2030.91000
1.471	-4.825	347.74660	1223.682253	526.47812	390.64480	101.00000	2.49204	357.07980	889.27980	1.31276	2030.91000
1.484	-3.808	348.05980	1248.71689	536.78087	390.71460	101.00000	2.49295	357.39990	889.28980	.00000	2030.91000
1.470	-2.795	347.97090	1224.04823	526.64445	390.67970	101.00000	2.49298	357.30980	889.29980	1.31578	2030.91000
1.470	-1.774	348.03000	1224.04655	526.64835	390.69950	101.00000	2.49302	357.36990	889.28980	1.31579	2030.91000
1.470	-.761	348.11040	1223.04890	526.24857	390.75150	101.00000	2.49261	357.45000	889.26980	1.35464	2030.84000
1.470	.249	347.85570	1222.75331	526.10795	390.69430	101.00000	2.49187	357.18990	889.26000	1.35494	2030.84000
1.470	1.237	348.02880	1223.56749	526.45268	390.67650	101.00000	2.49345	357.36990	889.26000	1.35405	2030.87500
GRADIENT	.02045	-.1.88132	-.77051	-.00450	.00000	.00006	.02089	-.00526	.10143	-.01113	

RUN NO. 1598/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.493	-6.884	337.77220	1227.45941	527.01254	386.29980	100.40000	2.49790	346.97000	896.28980	1.45514	2033.57001
1.493	-5.854	337.94600	1228.25285	527.34772	386.36060	100.50000	2.49875	347.14990	896.31980	1.45514	2033.57001
1.493	-4.840	337.85690	1227.85158	527.17846	386.32350	100.50000	2.4980	347.05980	896.29980	1.48564	2033.57001
1.493	-3.819	337.78710	1228.15022	527.28847	386.27860	100.50000	2.49914	346.99000	896.30980	1.48148	2033.53500
1.493	-2.807	337.78760	1228.15163	527.28996	386.28390	100.50000	2.49904	346.99000	896.30980	1.47771	2033.53500
1.493	-1.787	337.66190	1227.69737	527.09455	386.28300	100.50000	2.49813	346.85990	896.27980	1.47825	2033.53500
1.493	-.776	337.66530	1226.97336	526.80668	386.35520	100.50000	2.49677	346.85990	896.30980	1.47536	2033.57001
1.493	.235	337.69530	1226.98003	526.81229	386.38110	100.50000	2.49650	346.88990	896.26980	1.46410	2033.53500
1.493	1.224	337.41240	1226.44827	526.56889	386.32320	100.50000	2.49551	346.9990	896.26980	1.47220	2033.57001
GRADIENT	-.05778	-.27254	-.11511	.00973	.00000	-.00061	-.06027	-.00600	-.00274	-.00121	

RUN NO. 1614/ O RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.516	-6.883	326.64940	1227.80966	525.68143	383.11960	101.60000	2.48340	335.64990	905.39990	1.58972	2033.57001
1.516	-5.854	327.03660	1229.16266	526.26435	383.13650	101.60000	2.48602	336.04980	905.41990	1.58398	2033.60500
1.517	-4.835	327.21610	1230.89920	526.96561	383.04200	101.60000	2.48918	336.24000	905.42990	1.58174	2033.60500
1.516	-3.821	327.17070	1229.93829	526.58591	383.10740	101.60000	2.48759	336.18990	905.41990	1.58701	2033.60500
1.517	-2.808	326.94580	1229.78510	526.49222	382.98070	101.50000	2.48758	335.96000	905.40990	1.58316	2033.60500
1.516	-1.787	327.26660	1230.54515	526.83560	383.09670	101.60000	2.48853	336.28980	905.41990	1.57820	2033.60500
1.517	-.777	327.27290	1231.40327	527.16913	382.95310	101.50000	2.49060	336.29980	905.41990	1.57709	2033.60500
1.516	.234	327.87700	1232.54843	527.70460	383.13180	101.60000	2.49250	336.91990	905.41990	1.57169	2033.60500
1.517	1.222	327.89380	1233.25200	527.98028	383.07450	101.60000	2.49372	336.93990	905.41990	1.57079	2033.60500
GRADIENT	.13311	.49016	.21016	.00419	-.00003	.00093	-.13757	-.00071	-.00246	.00001	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1022

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM056) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1629/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
1.542	-6.883	317.53320	1238.70651	528.30478	379.06960	101.50000	2.48898	326.37990	906.32980	1.43225 2033.14999
1.541	-5.851	317.52250	1238.11143	528.07526	379.04760	101.50000	2.48930	326.36990	906.33980	1.48513 2033.14999
1.541	-4.835	317.52270	1238.00491	528.03540	379.05200	101.50000	2.48922	326.36990	906.32980	1.48905 2033.14999
1.541	-3.823	317.52220	1238.10161	528.07162	379.03810	101.50000	2.48948	326.36990	906.30980	1.49273 2033.14999
1.541	-2.806	317.67680	1238.73425	528.34021	379.04150	101.50000	2.49063	326.52980	906.29980	1.48818 2033.11501
1.542	-1.788	317.61790	1238.71588	528.32211	379.01710	101.50000	2.49063	326.47000	906.30980	1.49199 2033.08000
1.541	-.777	317.66600	1238.84822	528.38058	379.01200	101.50000	2.49111	326.51980	906.28980	1.49946 2033.08000
1.541	.238	317.73510	1238.69412	528.33598	379.05030	101.50000	2.49092	326.58980	906.28980	1.49966 2033.08000
1.541	1.221	317.90090	1238.85419	528.42840	379.09470	101.50000	2.49138	326.75980	906.26980	1.49950 2033.08000
GRADIENT	.05463	.13598	.06177	.00429	-.00000	.00000	.00035	.05639	-.00813	-.01366

	RUN NO.	1672/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
.599	-7.870	1252.45200	1596.85001	315.06540	522.04810	99.89999	2.49771	1262.20000	1301.09000	8.64464 2030.21001
.599	-6.844	1252.89200	1596.67000	314.55250	522.39750	100.20000	2.49399	1262.63000	1301.09000	8.56287 2030.21001
.600	-5.828	1251.95599	1596.73000	315.37080	522.09370	100.00000	2.49815	1261.71001	1301.07001	8.46417 2030.17500
.600	-4.806	1252.11000	1596.64999	315.17750	522.11960	100.00000	2.49738	1261.86000	1301.06000	8.35111 2030.17500
.600	-3.789	1251.82201	1596.86000	315.59080	522.06540	100.00000	2.49906	1261.58000	1301.08000	8.23788 2030.21001
.601	-2.768	1251.99800	1597.67999	316.13530	522.01000	100.00000	2.50173	1261.77000	1301.05000	8.10718 2030.21001
.601	-1.750	1251.30901	1597.09000	316.20410	521.98320	100.00000	2.50148	1261.08000	1301.08000	7.95458 2030.21001
.601	-.736	1251.06400	1596.67000	316.05220	521.99290	100.00000	2.50057	1260.83000	1301.06000	7.7532 2030.21001
.601	.277	1251.33000	1597.08000	316.17900	521.98630	100.00000	2.50138	1261.10001	1301.07001	7.60676 2030.24500
.600	1.258	1251.86000	1596.97000	315.65140	521.96660	99.89999	2.49995	1261.62000	1301.05000	7.44577 2030.21001
.600	2.239	1251.82001	1596.94000	315.65920	521.96460	99.89999	2.49995	1261.58000	1301.06000	7.31605 2030.21001
GRADIENT	-.04918	.00444	.04403	-.01941	-.01409	-.00024	-.04834	-.00129	-.00129	-.15231 .00416

(VCM057) (04 OCT 91)

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM057) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1748/ 0	RN/L =	2.51	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	4.000	PHI =	180.000
	P	PT	Q (PSF)	T (R)	TT (F)	RN/L	PC	PREF	SH10+3	PATM
MACH	ALPHA									
.800	-7.906	880.15310	1341.03000	393.84770	495.34030	99.00000	2.50390	890.04980	1045.30000	5.93086 2029.54500
.800	-6.883	880.16040	1341.20000	393.96830	495.23510	98.89999	2.50498	890.05980	1045.28999	5.97126 2029.64999
.799	-5.871	880.32590	1340.92999	393.65600	495.29000	98.89999	2.50387	890.02200	1045.28000	6.01209 2029.72000
.800	-4.856	879.72580	1341.21001	394.27120	495.16410	98.89999	2.50579	889.62990	1045.52999	6.08434 2029.78999
.800	-3.843	879.82350	1341.45000	394.38280	495.15450	98.89999	2.50635	889.73000	1045.24001	6.23279 2029.86000
.800	-2.830	879.83760	1341.17000	394.16550	495.18630	98.89999	2.50547	889.74000	1045.24001	6.43885 2029.92999
.800	-1.817	879.56450	1341.21001	394.38090	495.04960	98.80000	2.50665	889.47000	1045.22000	6.79830 2030.03500
.800	-.808	879.53960	1340.86000	394.13890	495.08250	98.80000	2.50563	889.43990	1045.21001	7.25023 2030.10500
.800	-201	879.52710	1341.00999	394.25850	494.97580	98.70000	2.50669	889.42990	1045.20000	7.60455 2030.14000
.800	1.186	879.69480	1340.62000	393.85600	495.04390	98.70000	2.50521	889.58980	1045.17999	7.86787 2030.21001
.800	2.172	879.81540	1340.64999	393.79610	495.14890	98.80000	2.50451	889.71000	1045.17000	8.12077 2030.21001
.800	GRADIENT	-0.01175	-.10530	-.06991	-.01501	-.02731	-.00014	-.01327	-.01256	.31238 .06388

RUN NO. 1661/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.		1661/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	4.000	PHI =	5.00
	P	PT	Q (PSF)	T (R)	TT (F)	RN/L	PC	PREF	SH10+3	PATM
MACH	ALPHA									
.900	-7.899	752.55420	1272.69000	426.62400	481.91360	100.30000	2.49661	762.55980	982.56980	1.37423 2028.88000
.900	-6.870	753.08940	1273.33000	426.74540	481.94210	100.30000	2.49766	763.09990	982.59990	1.36282 2028.91499
.900	-5.859	752.97490	1272.89999	426.51830	481.96780	100.30000	2.49663	762.98000	982.64990	1.35617 2028.91499
.900	-4.845	752.98540	1272.85001	426.47750	482.06100	100.40000	2.49591	762.99000	982.70000	1.35269 2028.91499
.900	-3.830	753.15040	1273.28999	426.68160	482.04370	100.40000	2.49689	763.15990	982.74000	1.34165 2028.88000
.900	-2.815	752.54250	1272.84000	426.73340	481.89500	100.30000	2.49703	762.54980	982.78980	1.34197 2028.88000
.900	-1.801	752.48710	1273.19000	427.00760	481.93310	100.40000	2.49749	762.50000	982.82980	1.34176 2028.84500
.900	-.791	752.69170	1272.97000	426.73510	481.99440	100.40000	2.49662	762.70000	982.86990	1.34199 2028.88000
.900	.217	752.52080	1272.94000	426.81590	481.96630	100.40000	2.49676	762.52980	982.90990	1.33851 2028.91499
.900	1.202	752.89970	1273.23000	426.78980	482.00420	100.40000	2.49706	762.90990	982.95000	1.34523 2028.91499
.899	2.188	752.98190	1272.39000	426.16360	482.02420	100.30000	2.49523	762.98000	982.96000	1.33560 2028.88000
.899	GRADIENT	-.01396	-.04038	-.01942	-.00221	-.00469	-.00007	-.01444	-.03872	.000158 -.00079

RUN NO. 1740/ 0 RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.		1740/ 0	RN/L =	2.51	GRADIENT INTERVAL = -5.00/ 5.00		BETA =	4.000	PHI =	5.00
	P	PT	Q (PSF)	T (R)	TT (F)	RN/L	PC	PREF	SH10+3	PATM
MACH	ALPHA									
1.098	-7.920	566.11160	1206.25999	478.06130	449.91600	98.80000	2.50617	576.29980	911.92990	1.07277 2030.17500
1.098	-6.942	565.25240	1206.84000	478.73900	449.65920	98.80000	2.50791	575.45000	911.92990	1.06653 2030.17500
1.098	-5.939	564.47360	1206.56000	478.88350	449.43140	98.80000	2.50822	574.66990	911.90990	1.06678 2030.14000
1.098	-4.931	564.21850	1206.06000	478.69340	449.50710	98.80000	2.50620	574.40990	911.89990	1.06722 2030.14000
1.098	-3.931	564.35110	1205.86000	478.52490	449.47800	98.70000	2.50667	574.53980	911.86990	1.06454 2030.10500
1.098	-2.939	564.63010	1206.00999	478.50200	449.60600	98.80000	2.50630	574.81980	911.87990	1.06726 2030.10500
1.098	-1.922	564.69120	1205.94000	478.43730	449.62740	98.80000	2.50611	574.87990	911.86990	1.06447 2030.07001
1.098	-.925	564.81840	1206.20000	478.53810	449.62870	98.80000	2.50664	575.01000	911.85990	1.06424 2030.07001
1.098	.080	565.06370	1205.80000	478.20850	449.72710	98.80000	2.50561	575.25000	911.83980	1.06640 2030.07001
1.098	1.066	564.92090	1206.02000	478.39310	449.67110	98.80000	2.50618	575.10990	911.82980	1.09327 2030.03500
1.098	2.063	564.90060	1206.03999	478.41260	449.66430	98.80000	2.50624	575.08980	911.81980	1.08742 2030.03500
1.098	1.0784	.00340	-.04059	.02896	.00596	-.00008	.00596	.00008	.00008	.00443 -.01062

DATE 04 OCT 91

IA31O (AEDC 16TF-783) TABULATED DATA

IA31O (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1024

(VCM057) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1724/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PADM
1.249	-7.925	463.02220	1197.89000	505.68530	426.94580	100.50000	2.49698	473.14990	856.23000	1.02659 2030.66499
1.250	-6.894	462.70260	1198.00000	505.81130	426.85030	100.50000	2.49716	472.82980	856.25000	1.02374 2030.70000
1.250	-5.883	462.53610	1197.56000	505.62480	426.77490	100.40000	2.49683	472.65990	856.28980	1.02411 2030.70000
1.250	-4.873	462.39360	1197.97000	505.86380	426.69560	100.40000	2.49765	472.51980	856.28980	1.02401 2030.70000
1.250	-3.862	462.33350	1198.03000	505.90750	426.67360	100.40000	2.49776	472.46000	856.29980	1.02371 2030.66499
1.250	-2.850	462.41500	1197.77000	505.75780	426.72170	100.40000	2.49725	472.53980	856.31980	1.02393 2030.73500
1.250	-1.841	462.51250	1198.07001	505.88820	426.71680	100.40000	2.49787	472.63990	856.32980	1.02368 2030.73500
1.250	-836	462.55270	1198.03999	505.86450	426.73050	100.40000	2.49781	472.67990	856.35990	1.02095 2030.70000
1.250	-173	462.58180	1198.14999	505.91380	426.72710	100.40000	2.49804	472.71000	856.35990	1.01812 2030.73500
1.250	1.158	462.54130	1198.27000	505.98340	426.70410	100.40000	2.49828	472.66990	856.37990	1.01528 2030.73500
1.250	2.153	462.60300	1197.97000	505.81790	426.67460	100.30000	2.49826	472.73000	856.37990	1.01280 2030.77000
GRADIENT	.03614	.02742	.00597	.00045	-.00826	.00011	.03645	.01401	-.00142	.00955

RUN NO. 1716/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

	RUN NO.	1706/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PADM
1.400	-6.923	381.66530	1215.08000	523.87080	402.51560	100.70000	2.49643	391.36990	873.86990	1.15066 2031.01500
1.400	-5.895	381.93210	1215.11000	523.87870	402.59330	100.70000	2.49488	391.63990	873.86990	1.15369 2031.01500
1.400	-4.878	381.80180	1215.39999	524.00830	402.52640	100.70000	2.49531	391.50980	873.87990	1.15957 2031.05000
1.400	-3.872	381.88960	1215.59000	524.08940	402.53490	100.70000	2.49572	391.59990	873.84990	1.15939 2031.08501
1.400	-2.865	381.98270	1214.92000	523.79440	402.62650	100.70000	2.49457	391.68990	873.84990	1.16003 2031.08501
1.400	-1.852	381.85300	1215.10001	523.87570	402.57030	100.70000	2.49480	391.55980	873.83980	1.15677 2031.05000
1.399	-.851	382.03250	1214.87000	523.77150	402.64620	100.70000	2.49452	391.74000	873.83980	1.15699 2031.01500
1.397	157	382.07810	1215.45000	524.02440	402.60500	100.70000	2.49561	391.78980	873.80980	1.15031 2031.01500
1.400	1.145	381.83500	1214.82001	523.75370	402.59130	100.70000	2.49428	391.53980	873.80980	1.14785 2031.01500
1.400	2.133	381.68410	1215.22000	523.93160	402.50810	100.70000	2.49490	391.38990	873.79980	1.14747 2031.08501
GRADIENT	-.00732	-.04459	-.01938	.00202	-.00000	-.00009	-.00009	-.00766	-.01048	-.00203

	RUN NO.	1706/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PADM
1.450	-7.874	359.03170	1226.02000	528.19380	394.53440	100.70000	2.49520	368.50980	884.10990	1.30505 2030.45500
1.450	-6.841	359.05100	1226.14000	528.24490	394.52950	100.70000	2.49543	368.52980	884.12990	1.30492 2030.45500
1.451	-5.831	358.47140	1225.77000	528.06100	394.38130	100.70000	2.49424	367.93990	884.14990	1.30189 2030.45500
1.450	-4.811	359.00170	1226.14000	528.24220	394.51390	100.70000	2.49539	368.48000	884.14990	1.29466 2030.45500
1.450	-3.790	358.73630	1225.96001	528.15380	394.44730	100.70000	2.49482	368.21000	884.16990	1.28467 2030.45500
1.450	-2.773	359.07130	1226.03000	528.20020	394.54590	100.70000	2.49526	368.54980	884.20000	1.28459 2030.45500
1.450	-1.750	358.74510	1226.16000	528.23750	394.43160	100.70000	2.49518	368.22000	884.20000	1.28108 2030.45500
1.450	-.740	358.96310	1225.96001	528.16550	394.51830	100.70000	2.49503	368.43990	884.18990	1.28129 2030.42000
1.450	.272	359.09180	1225.87000	528.13450	394.49660	100.60000	2.49559	368.56980	884.21000	1.28476 2030.38499
1.450	1.254	358.734460	1226.31000	528.29910	394.34420	100.60000	2.49603	368.21000	884.24000	1.27755 2030.38499
1.450	2.240	358.66720	1226.00999	528.17090	394.35060	100.60000	2.49544	368.13990	884.23000	1.28123 2030.38499
GRADIENT	-.02422	.00176	-.00053	-.02020	-.01768	-.01768	-.00009	-.02457	.01099	-.00152

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1025

(VCM057) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1699/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.469	-7.887	348.04050	1221.69009	525.68787	390.15700	100.20000	2.49758	357.37990	887.51000	1.43467	2030.52499
1.469	-6.855	348.04910	1221.94727	525.79378	390.13620	100.20000	2.49803	357.38990	887.51000	1.43436	2030.56000
1.469	-5.841	347.76420	1221.89011	525.74747	390.04760	100.20000	2.49768	357.09990	887.51980	1.43440	2030.56000
1.470	-4.822	347.93360	1221.55362	525.62373	390.14720	100.20000	2.49699	357.26980	887.51980	1.42751	2030.56000
1.469	-3.808	347.96170	1221.79202	525.72319	390.12820	100.20000	2.49756	357.29980	887.52980	1.43088	2030.59500
1.469	-2.789	347.96170	1221.84224	525.74395	390.13010	100.20000	2.49753	357.29980	887.52980	1.42718	2030.63000
1.469	-1.769	348.01030	1221.98508	525.80607	390.13280	100.20000	2.49782	357.34990	887.52980	1.42701	2030.63000
1.469	-7.761	347.87280	1221.84239	525.73634	390.09420	100.20000	2.49757	357.21000	887.51000	1.43081	2030.59500
1.469	-2.49	347.94290	1221.61270	525.64862	390.13840	100.20000	2.49723	357.27980	887.52980	1.43109	2030.66499
1.469	1.232	347.90090	1222.07106	525.83164	390.07620	100.20000	2.49812	357.24000	887.51000	1.43420	2030.66499
2.221	348.10840	1221.97401	525.80913	390.15990	100.20000	2.49801	357.45000	887.51000	1.43068	2030.63000	
GRADIENT	.00848	.04139	.01751	.01751	.00221	-.00000	.00010	.00892	-.00221	.00064	.01076

RUN NO. 1692/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.497	-7.845	337.72410	1233.62323	529.45270	386.09770	100.10000	2.49925	346.91990	910.56980	1.05259	2030.24500
1.497	-6.858	337.40060	1233.37646	529.31543	386.00540	100.10000	2.49862	346.58980	910.58980	1.05554	2030.21001
1.497	-5.849	337.53810	1233.53345	529.39478	386.05030	100.10000	2.49878	346.73000	910.57980	1.04710	2030.24500
1.497	-4.833	337.26370	1233.27094	529.25716	385.97220	100.10000	2.49824	346.45000	910.59990	1.05283	2030.24500
1.497	-3.821	337.41060	1233.36865	529.31361	386.00950	100.10000	2.49861	346.59990	910.57980	1.05555	2030.28000
1.497	-2.796	337.48900	1233.30380	529.29726	386.03420	100.10000	2.49872	346.67990	910.57980	1.06120	2030.28000
1.497	-1.783	337.38210	1233.09254	529.20110	386.01710	100.10000	2.49826	346.56980	910.58980	1.06137	2030.28000
1.496	-.774	337.73610	1232.98711	529.14430	386.14430	100.10000	2.49845	346.92990	910.58980	1.06432	2030.28000
1.497	.235	337.49000	1233.02295	529.18576	386.05220	100.10000	2.49838	346.67990	910.57980	1.06706	2030.28000
1.496	1.217	337.58890	1232.76859	529.09713	386.10160	100.10000	2.49817	346.77980	910.56980	1.07294	2030.28000
1.497	2.207	337.45120	1232.78252	529.08591	386.05300	100.10000	2.49808	346.63990	910.56980	1.07291	2030.24500
GRADIENT	.03044	-.08706	-.03088	.01433	-.00000	-.00000	-.00005	.03078	-.000308	.00293	.000003

RUN NO. 1687/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.521	-7.847	327.31180	1238.02438	529.72861	382.34330	100.60000	2.49618	336.33980	911.67990	1.12440	2030.03500
1.520	-6.866	327.29470	1237.51614	529.53006	382.32280	100.50000	2.49574	336.31980	911.66990	1.11898	2030.03500
1.521	-5.849	327.18580	1237.82539	529.63262	382.26100	100.50000	2.49608	336.21000	911.67990	1.11575	2030.07001
1.520	-4.830	327.26640	1237.33968	529.45691	382.34060	100.50000	2.49519	336.28980	911.66990	1.11036	2030.07001
1.521	-3.814	327.25540	1237.77591	529.62361	382.30860	100.50000	2.49571	336.27980	911.67990	1.10124	2030.07001
1.521	-2.803	327.23540	1238.05756	529.72938	382.29150	100.50000	2.49588	336.25980	911.68990	1.08946	2030.10500
1.521	-1.785	327.13790	1237.86000	529.63712	382.27560	100.50000	2.49544	336.15990	911.65990	1.08963	2030.10500
1.520	-.777	327.53050	1237.77515	529.66637	382.41550	100.50000	2.49577	336.55980	911.66990	1.09262	2030.10500
1.520	.237	327.39360	1237.62698	529.58752	382.44600	100.60000	2.49485	336.41990	911.65990	1.09562	2030.07001
1.520	1.220	327.22680	1237.54524	529.53046	382.38400	100.60000	2.49476	336.25000	911.65990	1.10435	2030.10500
1.520	2.207	327.27540	1237.59081	529.55486	382.39700	100.60000	2.49488	336.29980	911.63990	1.10431	2030.10500
GRADIENT	.00941	-.00892	-.00199	.01628	.01772	-.00011	.00058	-.000461	-.00008	.00461	.00373

RUN NO. 1687/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.521	-7.847	327.31180	1238.02438	529.72861	382.34330	100.60000	2.49618	336.33980	911.67990	1.12440	2030.03500
1.520	-6.866	327.29470	1237.51614	529.53006	382.32280	100.50000	2.49574	336.31980	911.66990	1.11898	2030.03500
1.521	-5.849	327.18580	1237.82539	529.63262	382.26100	100.50000	2.49608	336.21000	911.67990	1.11575	2030.07001
1.520	-4.830	327.26640	1237.33968	529.45691	382.34060	100.50000	2.49519	336.28980	911.66990	1.11036	2030.07001
1.521	-3.814	327.25540	1237.77591	529.62361	382.30860	100.50000	2.49571	336.27980	911.67990	1.10124	2030.07001
1.521	-2.803	327.23540	1238.05756	529.72938	382.29150	100.50000	2.49588	336.25980	911.68990	1.08946	2030.10500
1.521	-1.785	327.13790	1237.86000	529.63712	382.27560	100.50000	2.49544	336.15990	911.65990	1.08963	2030.10500
1.520	-.777	327.53050	1237.77515	529.66637	382.41550	100.50000	2.49577	336.55980	911.66990	1.09262	2030.10500
1.520	.237	327.39360	1237.62698	529.58752	382.44600	100.60000	2.49485	336.41990	911.65990	1.09562	2030.07001
1.520	1.220	327.22680	1237.54524	529.53046	382.38400	100.60000	2.49476	336.25000	911.65990	1.10435	2030.10500
1.520	2.207	327.27540	1237.59081	529.55486	382.39700	100.60000	2.49488	336.29980	911.63990	1.10431	2030.10500
GRADIENT	.00941	-.00892	-.00199	.01628	.01772	-.00011	.00058	-.000461	-.00008	.00461	.00373

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1026

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM057) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1680 / 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
1.541	-7.888	318.45260	1240.59627	529.19595	379.04050	101.00000	2.49331	31980	912.07980
1.543	-6.862	317.74340	1241.91087	529.55986	378.67920	101.00000	2.49461	326.59990	912.04980
1.542	-5.847	318.38940	1241.89226	529.67484	378.90330	101.00000	2.49542	327.25980	912.05980
1.545	-4.831	316.75680	1241.40048	529.17812	378.38160	101.00000	2.49251	325.58980	912.06980
1.544	-3.819	317.12060	1240.84569	529.03851	378.54960	101.00000	2.49218	325.96000	912.10990
1.543	-2.800	317.48320	1241.13727	529.21887	378.68800	101.00000	2.49240	326.32980	912.13990
1.543	-1.781	317.54100	1241.42149	529.33694	378.69210	101.00000	2.49277	326.38990	912.14990
1.543	-7.75	317.83470	1241.69885	529.49822	378.79300	101.00000	2.49316	326.68990	912.14990
1.543	-23.4	317.64770	1241.94933	529.55754	378.63770	100.90000	2.49396	326.50000	912.14990
1.543	1.217	317.74610	1241.96338	529.58225	378.67970	100.90000	2.49393	326.59990	912.16990
1.543	2.207	317.56960	1242.08946	529.59622	378.61110	100.90000	2.49385	326.41990	912.17990
GRADIENT	.11404	.15522	.08077	.02629	-.01772	.00028	.11661	.01303	-.00892

(VCM058) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1673 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	-8.000	PHI =	180.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.600	-3.745	1252.19000	1597.21001	315.58250	522.26340	100.20000	2.49819	1261.95000	1301.05000
.600	-2.728	1252.22600	1596.97000	315.35130	522.10350	100.00000	2.49828	1261.98000	1301.03999
.600	-1.724	1252.26801	1596.92000	315.27540	522.11300	100.00000	2.49797	1262.02000	1301.06000
.600	-7.18	1252.34300	1597.19000	315.44020	522.09690	100.00000	2.49880	1262.10001	1301.03999
.600	-28.9	1251.64301	1596.66000	315.56880	521.96950	99.89999	2.49938	1261.39999	1301.07001
.600	-7.3	1252.07401	1596.92999	315.44240	522.08910	100.00000	2.49858	1261.83000	1301.10001
.600	1.747	1251.90401	1596.81000	315.48120	522.26660	100.20000	2.49748	1261.66000	1301.10001
.600	2.757	1251.89101	1596.92999	315.59230	522.25370	100.20000	2.49799	1261.64999	1301.09000
.600	3.771	1252.06799	1597.21001	315.68240	522.06230	100.00000	2.49969	1261.83000	1301.09000
GRADIENT	-.04118	-.00779	.02720	-.00064	.00380	.00007	-.04063	.00794	.00711

(VCM058) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.	1673 / 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	4.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.600	-3.745	1252.19000	1597.21001	315.58250	522.26340	100.20000	2.49819	1261.95000	1301.05000
.600	-2.728	1252.22600	1596.97000	315.35130	522.10350	100.00000	2.49828	1261.98000	1301.03999
.600	-1.724	1252.26801	1596.92000	315.27540	522.11300	100.00000	2.49797	1262.02000	1301.06000
.600	-7.18	1252.34300	1597.19000	315.44020	522.09690	100.00000	2.49880	1262.10001	1301.03999
.600	-28.9	1251.64301	1596.66000	315.56880	521.96950	99.89999	2.49938	1261.39999	1301.07001
.600	-7.3	1252.07401	1596.92999	315.44240	522.08910	100.00000	2.49858	1261.83000	1301.10001
.600	1.747	1251.90401	1596.81000	315.48120	522.26660	100.20000	2.49748	1261.66000	1301.10001
.600	2.757	1251.89101	1596.92999	315.59230	522.25370	100.20000	2.49799	1261.64999	1301.09000
.600	3.771	1252.06799	1597.21001	315.68240	522.06230	100.00000	2.49969	1261.83000	1301.09000
GRADIENT	-.04118	-.00779	.02720	-.00064	.00380	.00007	-.04063	.00794	.00711

## PARAMETRIC DATA

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1027

(VCM058) (04 OCT 91)

## PARAMETRIC DATA

		RUN NO.	1749/ O	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	- 8.000	PHI =	180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
.800	-3.820	879.96920	1341.14999	394.06130	495.03220	98.70000	2.50633	889.86990	1045.13000	7.77170	2030.49001	
.800	-2.803	879.90010	1341.06000	394.04200	495.03050	98.70000	2.50618	889.79980	1045.11000	7.46928	2030.52499	
.801	-1.801	878.90410	1340.82001	394.54130	494.89580	98.70000	2.50722	888.80980	1045.13000	7.19273	2030.52499	
.800	- .790	879.33570	1340.99001	394.37380	494.94730	98.70000	2.50697	889.24000	1045.08000	6.92337	2030.52499	
.800	- .211	880.60180	1342.03999	394.28980	495.04000	98.70000	2.50790	890.51000	1045.07001	6.73967	2030.56000	
.800	.832	880.67040	1342.14999	394.32450	494.95090	98.59999	2.50869	890.57980	1045.06000	6.83454	2030.56000	
.800	1.835	881.16820	1342.62000	394.33400	494.98120	98.59999	2.50923	891.07980	1045.05000	6.97054	2030.52499	
.799	2.841	881.34940	1342.67000	394.24780	495.00510	98.59999	2.50906	891.26000	1045.03999	7.11125	2030.49001	
.800	3.845	880.80960	1342.31000	394.34840	494.95630	98.59999	2.50893	890.72000	1045.03000	7.25678	2030.52499	
GRADIENT	.23348	.24658	.02372	-.00409	-.01762	.00043	.23503	-.01390	-.06331	.00106		
		RUN NO.	1662/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	- 8.000	PHI =	180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
.900	-3.810	752.73390	1272.82001	426.60670	481.93240	100.30000	2.49673	762.74000	983.13990	1.32124	2028.88000	
.900	-2.784	753.10250	1273.14999	426.61430	481.96390	100.30000	2.49715	763.10990	983.16990	0.00000	2028.88000	
.900	-1.783	752.95830	1273.35001	426.83720	481.91600	100.30000	2.49788	762.97000	983.23000	1.27977	2028.88000	
.900	- .778	752.39400	1272.63000	426.67850	481.89060	100.30000	2.49665	762.39990	983.26980	1.27379	2028.88000	
.900	- .229	752.72240	1272.95000	426.70310	481.91600	100.30000	2.49710	762.73000	983.48000	1.24696	2028.91499	
.900	.808	753.15920	1273.39999	426.75220	481.94730	100.30000	2.49776	763.16990	983.50980	1.24652	2028.84500	
.900	1.812	752.96510	1272.85001	426.48950	481.97140	100.30000	2.49651	762.97000	983.53980	1.25034	2028.84500	
.900	2.821	752.67410	1272.78000	426.61470	481.92550	100.30000	2.49670	762.67990	983.58990	1.25370	2028.91499	
.900	3.820	752.87700	1272.66000	426.41140	481.97580	100.30000	2.49610	762.87990	983.61990	1.27041	2028.98500	
GRADIENT	-.00010	-.03671	-.02520	.000394	-.000000	-.000010	-.000058	-.000058	-.07101	.00763		
		RUN NO.	1741/ O	RN/L =	2.51	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	- 8.000	PHI =	180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
1.099	-3.936	565.92700	1206.61000	478.33240	449.91750	98.89999	2.50648	576.11990	911.76000	1.07533	2029.96500	
1.100	-2.917	564.96630	1206.45000	478.61330	449.72290	98.89999	2.50655	575.18990	911.74000	1.07548	2029.96500	
1.100	-1.913	564.75170	1205.92999	478.40750	449.72270	98.89999	2.50547	574.93990	911.72000	1.07594	2029.96500	
1.101	- .911	564.32100	1205.85001	478.53080	449.63330	98.89999	2.50549	574.51000	911.72000	1.03638	2029.92999	
1.099	-.087	565.51510	1205.78999	478.02390	449.83080	98.80000	2.50537	575.70000	911.67990	1.03087	2029.96500	
1.099	.963	565.33230	1205.98000	478.20700	449.76880	98.80000	2.50590	575.51980	911.65990	1.03071	2029.96500	
1.100	1.957	565.12940	1206.21001	478.42110	449.69820	98.80000	2.50652	575.31980	911.64990	1.02775	2029.96500	
1.100	2.958	565.52420	1205.87000	478.06690	449.82420	98.80000	2.50555	575.71000	911.62990	1.02528	2029.96500	
1.100	3.965	565.00240	1205.92000	478.30250	449.70020	98.80000	2.50591	575.18990	911.61990	1.02800	2030.00000	
GRADIENT	-.00812	-.06479	-.03449	-.00850	-.01682	-.00005	-.00883	-.01850	-.00748	.00296		

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1028  
(VCM058) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1725/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.249	-3.888	463.02050	1198.16000	505.82280	426.84160	100.40000	2.49812	473.14990	856.41990	1.01537 2030.77000
1.250	-2.831	462.47490	1197.77000	505.74460	426.73730	100.40000	2.49725	472.59990	856.41990	1.01844 2030.80499
1.250	-1.820	462.57250	1198.05000	505.86500	426.65840	100.30000	2.49842	472.70000	856.41990	1.01820 2030.77000
1.250	- .821	462.65280	1197.98000	505.81230	426.68680	100.30000	2.49829	472.77980	856.43990	1.02101 2030.77000
1.250	- .178	462.70260	1197.98000	505.80130	426.70000	100.30000	2.49830	472.82980	856.48000	1.01826 2030.77000
1.250	.872	462.57250	1198.09000	505.88550	426.73050	100.40000	2.49792	472.70000	856.49000	1.01817 2030.77000
1.249	1.869	462.87180	1198.06000	505.80470	426.81250	100.40000	2.49789	473.00000	856.48000	1.01546 2030.73500
1.250	2.876	462.68410	1197.78000	505.70390	426.79150	100.40000	2.49730	472.80980	856.49000	1.01570 2030.73500
1.250	3.887	462.72190	1198.07001	505.84250	426.77200	100.40000	2.49789	472.84990	856.48000	1.01272 2030.70000
GRADIENT	-.00163	-.00388	-.00161	-.00387	-.00513	-.00004	-.00004	-.00166	.01064	-.00047 -.00981

RUN NO. 1717/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.400	-3.903	382.05960	1215.28999	523.95480	402.61450	100.70000	2.49530	391.76980	873.76000	1.14435 2031.08501
1.400	-2.844	382.73730	1214.62000	523.66820	402.58080	100.70000	2.49384	391.43990	873.75000	1.14499 2031.08501
1.399	-1.841	382.13990	1215.08000	523.86130	402.65870	100.70000	2.49498	391.84990	873.74000	1.14455 2031.15500
1.400	-.835	381.97190	1215.06000	523.85570	402.60990	100.70000	2.49482	391.67990	873.75000	1.14762 2031.12000
1.400	-.159	381.98930	1215.46001	524.03050	402.57710	100.70000	2.49556	391.70000	873.74000	1.14115 2031.12000
1.400	.885	381.76460	1214.97000	523.82060	402.55590	100.70000	2.49450	391.47000	873.72000	1.13555 2031.12000
1.400	1.888	381.92070	1215.37000	523.99270	402.56520	100.70000	2.49534	391.62990	873.72000	1.13518 2031.08501
1.400	2.883	381.84420	1214.91000	523.79300	402.58570	100.70000	2.49445	391.54980	873.71000	1.13561 2031.12000
1.400	3.894	381.83880	1214.94000	523.80520	402.59470	100.70000	2.49453	391.58980	873.66990	1.13256 2031.15500
GRADIENT	-.01774	-.00254	-.00075	-.00059	-.00000	-.00000	-.00002	-.01795	-.00959	-.00182 .00438

RUN NO. 1707/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.450	-3.759	358.90500	1225.80000	528.09590	394.44460	100.60000	2.49529	368.37990	884.26000	1.29843 2030.42000
1.450	-2.736	359.19800	1226.30000	528.31880	394.49050	100.60000	2.49645	368.67990	884.26000	1.29790 2030.38499
1.450	-1.725	358.77560	1226.03999	528.18920	394.31130	100.50000	2.49619	368.25000	884.27980	1.29477 2030.38499
1.449	-.724	359.09280	1225.67999	528.05540	394.44410	100.50000	2.49585	368.56980	884.27980	1.29175 2030.35001
1.450	-.271	358.75660	1225.92000	528.13820	394.31640	100.50000	2.49596	368.23000	884.33980	1.28471 2030.38499
1.450	.768	359.18850	1226.25000	528.29760	394.42160	100.50000	2.49695	368.66990	884.32980	1.28436 2030.42000
1.450	1.777	359.07060	1226.17999	528.26250	394.39110	100.50000	2.49671	368.54980	884.33980	1.28782 2030.38499
1.450	2.768	358.75630	1225.89000	528.12570	394.31910	100.50000	2.49591	368.23000	884.30980	1.28813 2030.38499
1.450	3.794	358.93530	1225.64999	528.03520	394.39750	100.50000	2.49565	368.40990	884.33980	1.28499 2030.38499
GRADIENT	-.00888	-.01978	-.00867	-.000990	-.01269	-.00003	-.00003	-.01119	-.00909	-.00184 -.00154

## IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1029  
( VCM058 ) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.469	-3.779	348.12890	1222.48286	526.01810	390.18360	100.20000	2.49770	357.47000	887.52980	1.39401	2030.70000
1.469	-2.756	348.00170	1222.46796	526.00195	390.08590	100.10000	2.49792	357.33980	887.52980	1.38690	2030.70000
1.470	-1.751	347.92210	1222.74283	526.10819	390.11010	100.20000	2.49762	357.25980	887.52980	1.38303	2030.66499
1.470	-1.739	347.95240	1222.58928	526.04793	390.06470	100.10000	2.49797	357.28980	887.51980	1.38321	2030.66499
1.469	-2.54	348.13960	1222.66801	526.09523	390.13180	100.10000	2.49803	357.48000	887.53980	1.37608	2030.73500
1.469	.796	348.13820	1222.95233	526.21069	390.10520	100.10000	2.49853	357.48000	887.53980	1.37575	2030.73500
1.470	1.798	347.78490	1222.59000	526.03395	390.00900	100.10000	2.49783	357.11990	887.53980	1.38318	2030.66499
1.470	2.797	347.93310	1222.58630	526.04519	390.06470	100.10000	2.49783	357.26980	887.53980	1.37967	2030.73500
1.470	3.814	347.96190	1222.61974	526.06118	390.06490	100.10000	2.49804	357.29980	887.51980	1.38317	2030.70000
GRADIENT	-.01864	.01639	.00523	-.01293	-.01065	.0003	-.01899	.00040	-.00125	.00273	.00273

RUN NO. 1693/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.498	-3.792	337.11300	1233.50378	529.33018	385.85350	100.10000	2.49939	346.29980	910.58980	1.08355	2030.21001
1.497	-2.773	337.11620	1232.72189	529.02157	385.91850	100.10000	2.49817	346.29980	910.57980	1.08998	2030.28000
1.497	-1.764	337.23610	1232.22620	528.83969	386.00150	100.10000	2.49747	346.41990	910.57980	1.09333	2030.24500
1.496	-.758	337.42210	1232.30176	528.89183	386.04980	100.10000	2.49793	346.60990	910.58980	1.09905	2030.28000
1.494	-.240	338.43430	1231.86435	528.83919	386.38920	100.10000	2.49893	347.63990	910.57980	1.13180	2030.21001
1.495	.813	338.04760	1232.42712	529.01607	386.25610	100.20000	2.49933	347.25000	910.56980	1.14311	2030.24500
1.496	1.807	337.63400	1232.45601	528.97800	386.10330	100.20000	2.49919	346.82980	910.56980	1.14902	2030.24500
1.495	2.811	337.83250	1231.87173	528.76935	386.20730	100.20000	2.49867	347.02980	910.53980	1.16170	2030.28000
1.496	3.820	337.44970	1231.46039	528.56070	386.08760	100.20000	2.49813	346.63990	910.52980	1.18038	2030.24500
GRADIENT	.08173	-.18237	-.06256	.03766	.01777	.0001	.08327	-.00720	.01342	.00222	.00222

RUN NO. 1688/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.521	-3.835	327.11720	1237.62218	529.55206	382.35620	100.60000	2.49491	336.20000	911.60990	1.10718	2030.10500
1.521	-2.770	327.31320	1237.97430	529.70937	382.37520	100.60000	2.49558	336.33980	911.59990	1.10397	2030.17500
1.520	-1.767	327.30490	1237.56216	529.54864	382.40580	100.60000	2.49494	336.32980	911.56980	1.10725	2030.14000
1.520	-.756	327.37330	1237.65269	529.59453	382.42500	100.60000	2.49509	336.39990	911.57980	1.10427	2030.17500
1.520	-.234	327.53000	1238.22395	529.83964	382.47310	100.60000	2.49537	336.55980	911.52980	1.06945	2030.17500
1.521	.803	327.16700	1238.39348	529.84843	382.34300	100.60000	2.49508	336.18990	911.50000	1.06082	2030.21001
1.521	1.812	327.31270	1238.74342	530.00668	382.36180	100.60000	2.49583	336.33980	911.48000	1.06053	2030.21001
1.520	2.823	327.44210	1238.17528	529.80708	382.51900	100.70000	2.49453	336.47000	911.46000	1.06666	2030.24500
1.520	3.821	327.44210	1238.15593	529.79959	382.52080	100.70000	2.49450	336.47000	911.41990	1.06668	2030.24500
GRADIENT	.02244	.02244	.00001	.04215	.01663	.01267	-.00006	.02288	-.02549	-.00710	.01687

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1030

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM058) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PREF	SH10+3	PATM
1.543	-3.791	317.89720	1243.18201	530.07004	378.59840	100.90000	2.49667	326.75980	912.16990	1.27756 2029.86000
1.545	-2.772	316.76980	1240.79616	528.95375	378.39970	100.90000	2.49158	325.59990	912.13990	1.28988 2029.89500
1.544	-1.765	317.10250	1240.822747	529.02891	378.58150	101.00000	2.49143	325.93990	912.15990	1.28989 2029.86000
1.543	-1.758	317.47410	1240.98253	529.15857	378.70310	101.00000	2.49204	326.31980	912.20000	1.28645 2029.86000
1.542	-1.236	318.06910	1241.57214	529.49416	378.92750	101.10000	2.49313	326.92990	912.23000	1.28590 2029.86000
1.544	.806	317.35230	1242.23647	529.60859	378.62110	101.10000	2.49332	326.20000	912.20000	1.28179 2029.82500
1.543	1.817	317.83400	1241.62099	529.46889	378.84060	101.10000	2.49294	326.68990	912.17990	1.28582 2029.82500
1.543	2.816	317.63820	1241.69827	529.46022	378.77390	101.10000	2.49267	326.49000	912.15990	1.27908 2029.82500
1.544	3.829	317.31540	1241.68022	529.39189	378.73390	101.20000	2.49158	326.15990	912.15990	1.27575 2029.86000
GRADIENT	.02436	-.01518	-.00106	.03630	.03716	-.00024	.02480	.00077	-.00093	-.00550

(VCM059) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PREF	SH10+3	PATM
.600	-4.121	1252.35699	1597.48000	315.67240	522.07150	100.00000	2.49988	1262.12000	1300.94000	4.95971 2030.28000
.600	-3.141	1251.83600	1597.14999	315.82280	522.04030	100.00000	2.50015	1261.60001	1300.94000	5.14276 2030.31500
.600	-2.191	1251.9200	1596.96001	315.53470	522.07670	100.00000	2.49894	1261.75000	1300.92999	5.14338 2030.35001
.600	-1.256	1252.21300	1597.10001	315.47170	522.08980	100.00000	2.49883	1261.97000	1300.92999	5.15333 2030.31500
.600	-.303	1251.80499	1596.67999	315.45290	522.08060	100.00000	2.49841	1261.56000	1300.92999	5.13390 2030.31500
.600	.734	1251.93800	1597.11000	315.70480	522.05620	100.00000	2.49969	1261.70000	1300.92999	5.14289 2030.31500
.600	1.785	1251.78200	1596.82001	315.58980	522.06470	100.00000	2.49902	1261.53999	1300.91000	5.14383 2030.31500
.600	2.833	1251.89999	1596.52000	315.24050	522.10670	100.00000	2.49750	1261.64999	1300.89999	5.14481 2030.28000
.600	3.873	1251.85699	1597.12000	315.78030	522.04540	100.00000	2.49997	1261.62000	1300.92999	5.14286 2030.24500
GRADIENT	-.04157	-.05924	-.01568	.00056	-.00000	-.00000	-.04218	-.00334	-.00198	-.00542

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1031

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM059) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1752/ O		RN/L =		2.50		GRADIENT INTERVAL =		-5.00/ 5.00		ALPHA =		2.000		PHI =		180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)		RN/L		PC		PREF		SH10+3		PATM			
.799	-4.086	880.02610	1340.74001	393.71920	495.17330	98.80000		2.50440		889.91990	1044.66000	6.45395	2029.82500						
.800	-3.097	879.91430	1341.45000	394.32080	495.16920	98.89999		2.50618		889.81980	1044.64000	6.38574	2029.82500						
.800	-2.136	880.04440	1341.52000	394.28420	495.18260	98.89999		2.50616		889.95000	1044.64999	6.37253	2029.82500						
.800	-1.188	879.92920	1341.14000	394.08130	495.20410	98.89999		2.50521		889.82980	1044.62000	6.34866	2029.82500						
.800	-.228	879.81960	1341.03999	394.08180	495.19700	98.89999		2.50511		889.72000	1044.62000	6.32354	2029.86000						
.795	.795	879.91990	1341.06000	394.02830	495.21120	98.89999		2.50499		889.81980	1044.62000	6.32345	2029.82500						
.800	1.840	879.93330	1340.85001	393.86380	495.23540	98.89999		2.50433		889.82980	1044.58000	6.32445	2029.86000						
.800	2.888	879.66280	1340.73000	393.95900	495.20460	98.89999		2.50444		889.55980	1044.58000	6.32502	2029.86000						
.800	3.918	879.91260	1340.89999	393.91500	495.31540	99.00000		2.50394		889.80980	1044.57001	6.33700	2029.86000						
GRADIENT		-.02397	-.04940	-.02025	.01321	.01338		-.00018		-.02449	-.01138	-.01271	.00525						
RUN NO.		1665/ O		RN/L =		2.50		GRADIENT INTERVAL =		-5.00/ 5.00		ALPHA =		2.000		PHI =		180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)		RN/L		PC		PREF		SH10+3		PATM			
.900	-4.089	753.09230	1273.16000	426.62360	481.96090	100.30000		2.49719		763.09990	984.63990	1.16716	2028.88000						
.900	-3.100	752.98660	1273.50000	426.92360	481.90500	100.30000		2.49826		763.00000	984.67990	1.15762	2028.84500						
.900	-2.142	752.59810	1273.17000	426.92770	481.86960	100.30000		2.49786		762.60990	984.67990	1.15486	2028.88000						
.900	-1.199	752.59890	1273.12000	426.89310	481.87520	100.30000		2.49772		762.60990	984.74000	1.15490	2028.88000						
.900	-.236	752.68040	1273.03999	426.78960	481.89870	100.30000		2.49740		762.68990	984.76980	1.15192	2028.88000						
.900	-.798	752.60210	1272.89000	426.73320	481.98660	100.40000		2.49652		762.60990	984.81980	1.14293	2028.91499						
.900	1.841	752.76440	1272.80000	426.57470	482.02610	100.40000		2.49606		762.76980	984.83980	1.14605	2028.88000						
.900	2.881	753.07350	1273.06000	426.56960	482.05440	100.40000		2.49636		763.07980	984.84990	1.14581	2028.88000						
.900	3.911	752.80400	1272.86000	426.59230	481.94070	100.30000		2.49674		762.80980	984.85990	1.14296	2028.88000						
GRADIENT		-.00822	-.05788	-.03488	.01333	.00997		-.00020		-.00897	-.02979	-.00269	.00228						
RUN NO.		1744/ O		RN/L =		2.51		GRADIENT INTERVAL =		-5.00/ 5.00		ALPHA =		2.000		PHI =		180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)		RN/L		PC		PREF		SH10+3		PATM			
1.099	-4.031	565.28050	1206.14999	478.32640	449.81960	98.89999		2.50573		575.47000	911.20000	9.1017	2029.75500						
1.100	-3.023	565.00150	1205.99001	478.34370	449.77320	98.89999		2.50549		575.18990	911.20000	9.1029	2029.72000						
1.100	-2.051	564.63010	1206.00999	478.50200	449.68650	98.89999		2.50571		574.81980	911.20000	9.1027	2029.68500						
1.100	-1.082	564.77930	1206.13000	478.51290	449.70780	98.89999		2.50592		574.97000	911.20000	9.1018	2029.68500						
1.100	-.106	564.97090	1206.03000	478.37920	449.76200	98.89999		2.50560		575.15990	911.15990	9.1026	2029.64999						
1.100	.920	565.06030	1206.11000	478.39010	449.77370	98.89999		2.50574		575.25000	911.15990	9.1267	2029.61501						
1.100	1.944	565.27270	1205.94000	478.20730	449.84010	98.89999		2.50525		575.46000	911.14990	9.1280	2029.58000						
1.100	2.966	564.98110	1205.97000	478.33980	449.77080	98.89999		2.50545		575.16990	911.14990	9.0784	2029.58000						
1.100	3.982	564.91140	1205.97000	478.36770	449.75460	98.89999		2.50549		575.09990	911.12990	9.0537	2029.50999						
GRADIENT		.00063	-.01577	-.00942	.01321	.00180		-.00004		-.00046	-.00952	-.00032	-.02802						



DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1033

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM059) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA =		PHI = 180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PATM
1.484	-4.105	348.04050	1248.68024	536.76436	390.15330	100.20000	2.49764	357.37990	887.39990
1.470	-3.111	348.03100	1223.34630	526.36304	390.15840	100.20000	2.49748	357.36990	887.40990
1.470	-2.157	347.86330	1223.40327	526.37317	390.09770	100.20000	2.49744	357.20000	887.39990
1.470	-1.226	347.85280	1223.51933	526.41907	390.08350	100.20000	2.49764	357.18990	887.39990
1.485	-2.65	347.87330	1248.55133	536.69401	390.10350	100.20000	2.49740	357.21000	887.38990
1.471	.759	347.75440	1223.50685	526.40620	390.05180	100.20000	2.49753	357.08980	887.39990
1.470	1.813	348.14920	1223.30260	526.35472	390.20190	100.20000	2.49750	357.49000	887.39990
1.470	2.863	347.93210	1223.41203	526.38192	390.1960	100.20000	2.49751	357.26980	887.38990
1.484	3.899	348.03980	1248.77374	536.80127	390.14330	100.20000	2.49783	357.37990	887.37990
GRADIENT		.00355	.02238	.00938	.00055	-.00000	.00002	.00365	-.00234
RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA =		PHI = 180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PATM
1.495	-4.100	337.68650	1230.46484	528.19402	386.25540	100.30000	2.49740	346.87990	910.29980
1.495	-3.103	337.66550	1230.83461	528.33821	386.22360	100.30000	2.49785	346.85990	910.31980
1.495	-2.146	337.42160	1230.43025	528.14872	386.17770	100.30000	2.49692	346.60990	910.32980
1.494	-1.213	337.47090	1228.43666	527.36325	386.19750	100.30000	2.49691	346.65990	910.31980
1.494	-.258	337.68550	1228.85045	527.55368	386.23730	100.30000	2.49774	346.87990	910.30980
1.495	.779	337.49930	1230.73654	528.27979	386.18530	100.30000	2.49735	346.68990	910.28980
1.495	1.819	337.65550	1230.93440	528.37630	386.21205	100.30000	2.49784	346.84990	910.29980
1.495	2.874	337.55860	1230.67780	528.26381	386.21050	100.30000	2.49730	346.75000	910.26980
1.495	3.907	337.56710	1230.97902	528.38405	386.18600	100.30000	2.49784	346.75980	910.29980
GRADIENT		-.00495	.08689	-.03393	-.00404	-.00000	.00004	-.00491	-.00403
RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA =		PHI = 180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PATM
1.521	-4.099	327.38280	1238.48723	529.91882	382.28390	100.40000	2.49645	336.40990	910.97000
1.521	-3.103	327.42160	1238.60907	529.97142	382.21800	100.30000	2.49730	336.45000	910.95000
1.521	-2.151	327.34370	1238.51274	529.92218	382.20340	100.30000	2.49698	336.36990	910.93990
1.521	-1.215	327.23660	1238.27301	529.81287	382.18430	100.30000	2.49653	336.25980	910.93990
1.521	-.256	327.22750	1238.10870	529.74834	382.26810	100.40000	2.49557	336.25000	910.91990
1.521	.778	327.42110	1238.72713	530.01688	382.27910	100.40000	2.49683	336.45000	910.90990
1.521	1.826	327.45070	1238.73126	530.02311	382.28910	100.40000	2.49687	336.48000	910.89990
1.521	2.875	327.24610	1238.36333	529.84949	382.25150	100.40000	2.49603	336.26980	910.89990
1.521	3.907	327.39330	1238.45488	529.90798	382.23320	100.30000	2.49679	336.41990	910.88990
GRADIENT		-.00114	.00093	.00019	.00271	.00321	-.00004	-.00121	-.00067

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) PROBE CALIBRATION

PAGE 1034

( VCM059 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1684/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	ALPHA =	2.000	PHI =	180.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PARM
1.544	-4.099	317.50290	1242.19118	529.62373	378.49540	100.70000	2.49415	326.34990	912.04980	1.211705 2030.03500
1.544	-3.108	317.39450	1242.24803	529.62398	378.51150	100.80000	2.49368	326.24000	912.04980	1.22332 2030.10500
1.544	-2.147	317.55100	1242.26607	529.66010	378.56470	100.80000	2.49390	326.39990	912.04980	1.22332 2030.14000
1.544	-1.209	317.61960	1242.222540	529.65788	378.58810	100.80000	2.49400	326.47000	912.01000	1.22656 2030.17500
1.543	-2.250	317.58130	1241.98669	529.56131	378.52810	100.70000	2.49415	326.42990	912.03980	1.22679 2030.14000
1.543	.782	317.73580	1242.66759	529.84771	378.53080	100.70000	2.49531	326.58980	912.01980	1.21977 2030.17500
1.544	1.820	317.63790	1242.64693	529.82121	378.49410	100.70000	2.49524	326.49000	912.03980	1.22295 2030.17500
1.543	2.879	317.66820	1242.34781	529.71371	378.46360	100.60000	2.49537	326.51980	912.00000	1.22326 2030.21001
1.544	3.907	317.46220	1242.58685	529.76580	378.37870	100.60000	2.49537	326.30980	912.00000	1.21665 2030.21001
GRADIENT	.01532	.05181	.02254	-.01380	-.02188	.00023	.01583	-.00600	-.00017	.01804

( VCM060 ) ( 04 OCT 91 )

## PARAMETRIC DATA

	RUN NO.	1729/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-1.000	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PARM
1.250	-5.036	462.63110	1198.24001	505.94870	426.65450	100.30000	2.49882	472.75980	856.63990	1.01804 2030.73500
1.250	-4.776	462.58330	1197.95000	505.81200	426.67160	100.30000	2.49822	472.71000	856.61990	1.01555 2030.70000
1.250	-4.525	462.57250	1198.06000	505.87010	426.65750	100.30000	2.49844	472.70000	856.62990	1.01000 2030.66499
1.249	-4.279	462.77320	1197.87000	505.73000	426.72970	100.30000	2.49808	472.89990	856.63990	1.00745 2030.66499
1.250	-4.029	462.50070	1198.34000	506.02780	426.61010	100.30000	2.49900	472.62990	856.64990	1.00164 2030.63000
1.250	-3.788	462.66240	1198.03999	505.84030	426.68330	100.30000	2.49841	472.78980	856.62990	1.00189 2030.63000
1.250	-3.537	462.46480	1197.73000	505.72630	426.66280	100.30000	2.49776	472.58980	856.63990	99946 2030.63000
1.250	-3.289	462.39500	1197.77000	505.76220	426.64010	100.30000	2.49783	472.51980	856.63990	1.00482 2030.59500
1.250	-3.041	462.79150	1198.11000	505.84770	426.71020	100.30000	2.49857	472.91990	856.64990	1.00454 2030.59500
GRADIENT	-.00953	-.05027	-.02328	-.00242	-.00001	-.00010	-.00991	.01138	-.00610	-.05766

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1035

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCMO61) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1730/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-.750	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
1.250	-5.032	462.60110	1198.25000	505.96020	426.64580	100.30000	2.49883	472.73000	856.64990	1.00442 2030.63000
1.250	-4.767	462.72270	1197.98000	505.79690	426.70530	100.30000	2.49830	472.84990	856.63990	1.00194 2030.63000
1.250	-4.519	462.43190	1198.22000	505.98190	426.68040	100.40000	2.49816	472.55980	856.65990	.99367 2030.63000
1.250	-4.271	462.57150	1198.17999	505.93120	426.64500	100.30000	2.49869	472.70000	856.66990	.99371 2030.63000
1.250	-4.022	462.47190	1198.20000	505.96310	426.69290	100.40000	2.49813	472.59990	856.64990	.99369 2030.63000
1.250	-3.774	462.60330	1197.94000	505.80270	426.67770	100.30000	2.49820	472.73000	856.65990	.99391 2030.63000
1.250	-3.525	462.56300	1197.97000	505.82670	426.74050	100.40000	2.49767	472.68990	856.65990	.99121 2030.59500
1.250	-3.276	462.58150	1198.21001	505.94430	426.64450	100.30000	2.49875	472.71000	856.65990	.99101 2030.59500
1.250	-3.027	462.59130	1198.25000	505.96240	426.64310	100.30000	2.49883	472.72000	856.64990	.99633 2030.59500
GRADIENT		-.00320	.04533	.02361	-.01655	-.01441	.00018	-.00282	.00216	-.02520

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCMO62) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1731/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	-.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3 PATM
1.250	-5.016	462.79130	1198.14000	505.86280	426.70700	100.30000	2.49863	472.91990	856.64990	1.00994 2030.59500
1.250	-4.758	462.58350	1197.91000	505.79200	426.67580	100.30000	2.49814	472.71000	856.65990	1.00741 2030.59500
1.250	-4.511	462.51200	1198.14999	505.92900	426.63230	100.30000	2.49862	472.63990	856.66990	1.00721 2030.63000
1.250	-4.259	462.63280	1197.98000	505.81640	426.68160	100.30000	2.49829	472.75980	856.65990	1.00465 2030.63000
1.250	-4.007	462.55320	1197.97000	505.82890	426.66160	100.30000	2.49826	472.67990	856.66990	1.00195 2030.66499
1.250	-3.760	462.66160	1198.16000	505.90140	426.67090	100.30000	2.49866	472.78980	856.64990	.99641 2030.63000
1.250	-3.513	462.69240	1198.00000	505.81350	426.69530	100.30000	2.49834	472.81980	856.65990	.99923 2030.63000
1.250	-3.261	462.69070	1198.27000	505.95070	426.66720	100.30000	2.49889	472.81980	856.65990	1.00170 2030.66499
1.250	-3.019	462.76270	1197.94000	505.76760	426.72000	100.30000	2.49822	472.88990	856.65990	.99928 2030.66499
GRADIENT		1.627	.05049	.00019	.02543	-.00002	.00012	.11702	-.00347	-.00509

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1036

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM063) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	P	PT	RN/L	=	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	.250	PHI	=	180.000
1.250	-5.009	462.74190	1198.10001	505.85350	426.69800	100.30000	2.49855	472.86990	856.64990	1.00997	2030.63000				
1.250	-4.752	462.48320	1197.98000	505.84910	426.64210	100.30000	2.49827	472.60990	856.64990	1.00736	2030.66499				
1.250	-4.500	462.51420	1197.85001	505.77660	426.63360	100.30000	2.49801	472.63390	856.63390	1.01018	2030.66499				
1.250	-4.249	462.86250	1197.92999	505.74070	426.74710	100.30000	2.49821	472.99000	856.64990	1.01284	2030.70000				
1.250	-4.002	462.58370	1197.88000	505.77660	426.67870	100.30000	2.49808	472.71000	856.64990	1.01288	2030.70000				
1.250	-3.751	462.57060	1198.34000	506.01250	426.62870	100.30000	2.49901	472.70000	856.64990	1.01522	2030.70000				
1.250	-3.500	462.67430	1197.75999	505.69580	426.71480	100.30000	2.49784	472.79980	856.64990	1.01298	2030.70000				
1.250	-3.254	462.55400	1197.84000	505.76270	426.67500	100.30000	2.49799	472.67990	856.63390	1.00747	2030.70000				
1.250	-3.003	462.56300	1198.00999	505.84690	426.66020	100.30000	2.49834	472.68990	856.63390	1.00733	2030.73500				
GRADIENT	.00886	.00466	.00070	.00886	.00173	-.00001	.00001	.00001	.00001	-.000336	-.00051	.00001	.00001	.00001	.03133

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM064) ( 04 OCT 91 )

## PARAMETRIC DATA

MACH	ALPHA	P	PT	RN/L	=	2.50	GRADIENT INTERVAL =	-5.00/	5.00	BETA	=	.000	PHI	=	180.000
1.250	-5.001	462.86080	1198.14999	505.85280	426.72440	100.30000	2.49866	472.99000	856.64990	1.00997	2030.77000				
1.250	-4.738	462.70260	1197.99001	505.80640	426.69900	100.30000	2.49832	472.82980	856.63390	1.00464	2030.77000				
1.250	-4.492	462.48390	1197.92000	505.81860	426.72460	100.40000	2.49756	472.60990	856.63390	1.03908	2030.77000				
1.250	-4.240	462.61350	1197.88000	505.77000	426.68650	100.30000	2.49808	472.74000	856.64990	1.0166	2030.77000				
1.250	-3.993	462.50370	1197.89999	505.80420	426.65580	100.30000	2.49811	472.62990	856.63390	1.03655	2030.77000				
1.250	-3.737	462.49170	1198.23000	505.97410	426.61890	100.30000	2.49878	472.61990	856.63390	1.03883	2030.77000				
1.250	-3.490	462.47290	1198.07001	505.89700	426.63010	100.30000	2.49845	472.59990	856.63390	1.03388	2030.80499				
1.250	-3.239	462.74340	1197.84000	505.72120	426.72490	100.30000	2.49802	472.86990	856.61990	1.03406	2030.80499				
1.250	-2.988	462.80250	1197.96001	505.76900	426.72830	100.30000	2.49827	472.92990	856.62990	1.03144	2030.80499				
GRADIENT	.07456	.01410	-.00942	-.00009	-.00009	-.02388	.00018	.00018	.00018	-.00965	-.02413	.02650	.02413	.02413	.02413

(VCM064) ( 04 OCT 91 )

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1037

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM065) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1734/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.250	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.249	-4.991	462.83230	1197.97000	505.76760	426.73510	100.30000	2.49829	472.96000	856.59990	.92389 2030.80499
1.250	-4.732	462.69310	1197.92999	505.77780	426.70240	100.30000	2.49819	472.81980	856.61990	.92643 2030.84000
1.250	-4.485	462.55300	1198.00000	505.84400	426.65840	100.30000	2.49832	472.67990	856.61990	.92889 2030.87500
1.250	-4.232	462.57230	1198.08000	505.88040	426.65550	100.30000	2.49848	472.70000	856.61990	.93135 2030.94501
1.250	-3.979	462.64330	1197.91000	505.77860	426.69140	100.30000	2.49815	472.76980	856.61990	.93401 2030.91000
1.250	-3.732	462.67240	1198.05000	505.84330	426.68480	100.30000	2.49843	472.79980	856.60990	.93390 2030.91000
1.250	-3.479	462.55250	1198.09000	505.88990	426.64920	100.30000	2.49850	472.67990	856.60990	.93640 2030.91000
1.250	-3.226	462.81980	1198.36000	505.96830	426.69210	100.30000	2.49909	472.95000	856.60990	.94128 2030.91000
1.250	-2.977	462.65330	1197.92000	505.78150	426.69310	100.30000	2.49817	472.77980	856.59990	.93908 2030.91000
GRADIENT	-.01584		.08203	.04525	-.01253	-.00002	.00017	-.01539	-.00412	.00815 .04347

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM066) (04 OCT 91)

## PARAMETRIC DATA

	RUN NO.	1735/ O	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.500	PHI =	180.000
MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10 <sup>+3</sup> PATM
1.250	-4.984	462.39310	1198.05000	505.90430	426.61130	100.30000	2.49840	472.51980	856.57980	1.01274 2030.91000
1.250	-4.725	462.75290	1197.92999	505.76460	426.64210	100.20000	2.49879	472.87990	856.57980	1.01557 2030.91000
1.250	-4.471	462.65230	1198.06000	505.85280	426.60230	100.20000	2.49904	472.77980	856.57980	1.01546 2030.91000
1.250	-4.221	462.68310	1197.95000	505.79030	426.62160	100.20000	2.49882	472.80980	856.57980	1.01829 2030.91000
1.250	-3.972	462.69340	1197.88000	505.75270	426.63130	100.20000	2.49868	472.81980	856.57980	1.01835 2030.91000
1.250	-3.717	462.74270	1197.99001	505.79760	426.63330	100.20000	2.49891	472.86990	856.57980	1.01552 2030.87500
1.250	-3.466	462.54390	1197.84000	505.76490	426.59620	100.20000	2.49858	472.66990	856.54980	.93660 2030.91000
1.250	-3.210	462.53220	1198.14000	505.91970	426.56250	100.20000	2.49919	472.65990	856.56980	.93130 2030.91000
1.250	-2.963	462.66210	1198.05000	505.84550	426.60600	100.20000	2.49902	472.78980	856.57980	.93137 2030.91000
GRADIENT	.01716		.01500	.00398	-.01727	-.02656	.00019	.01750	-.00614	-.04878 -.00250

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1038

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM067) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.250	-4.976	462.63480	1.197.72000	505.68430	426.63230	100.20000	2.49835	.472.75980	856.53980	.93416	2030.80499
1.250	-4.715	462.54270	1.198.05000	505.87160	426.57450	100.20000	2.49901	.472.66990	856.52980	.93898	2030.80499
1.250	-4.464	462.58470	1.197.72000	505.69510	426.61910	100.20000	2.49834	.472.71000	856.52980	.94690	2030.77000
1.250	-4.212	462.51250	1.198.07001	505.88820	426.56450	100.20000	2.49904	.472.63990	856.51980	.94919	2030.80499
1.250	-3.960	462.56250	1.198.06000	505.87230	426.57860	100.20000	2.49903	.472.68990	856.52980	.94407	2030.84000
1.250	-3.708	462.52290	1.198.05000	505.87600	426.56910	100.20000	2.49900	.472.64990	856.52980	.94664	2030.84000
1.250	-3.453	462.66330	1.197.92000	505.77930	426.61940	100.20000	2.49876	.472.78980	856.52980	.94674	2030.84000
1.250	-3.203	462.49390	1.197.91000	505.81150	426.57570	100.20000	2.49872	.472.61990	856.51980	.94931	2030.84000
1.250	-2.947	462.79220	1.198.00000	505.79170	426.64530	100.20000	2.49894	.472.91990	856.51000	.94412	2030.84000
GRADIENT	.04289	.07131	.02684	.00396	.00001	.00015	.04351	-.00038	.00448	.02758	

IA310 (AEDC 16TF-783) PROBE CALIBRATION

(VCM068) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.250	-4.968	462.60350	1.197.91000	505.78740	426.60470	100.20000	2.49873	.472.73000	856.50000	.94419	2030.91000
1.250	-4.705	462.59370	1.197.87000	505.76930	426.60620	100.20000	2.49865	.472.72000	856.50000	.94422	2030.91000
1.250	-4.455	462.52340	1.197.95000	505.82520	426.57960	100.20000	2.49880	.472.64990	856.48000	.94416	2030.91000
1.250	-4.206	462.55320	1.197.95000	505.81860	426.58740	100.20000	2.49880	.472.67990	856.50000	.94672	2030.91000
1.250	-3.950	462.46260	1.198.07001	505.89920	426.55130	100.20000	2.49904	.472.58980	856.47000	.94662	2030.91000
1.250	-3.694	462.69340	1.197.89000	505.75760	426.63040	100.20000	2.49870	.472.81980	856.50000	.94933	2030.91000
1.250	-3.440	462.76220	1.198.00999	505.80320	426.63620	100.20000	2.49895	.472.88990	856.48000	.94924	2030.91000
1.250	-3.190	462.43360	1.197.96001	505.84990	426.55490	100.20000	2.4981	.472.55980	856.47000	.94671	2030.87500
1.250	-2.938	462.50240	1.198.11000	505.91090	426.55760	100.20000	2.49913	.472.62990	856.48000	.94403	2030.91000
GRADIENT	-.01723	.07400	.04128	-.01216	-.00001	.00015	-.01689	-.01126	.00698	.00129	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 1039

(VCMO69) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1671/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.599	-7.999	1252.57100	1596.97000	315.06810	522.05130	99.89999	2.49783	1262.32001	1301.19000	8.23730	2030.03500
.599	-6.982	1252.66100	1597.05000	315.06200	522.05440	99.89999	2.49787	1262.41000	1301.17000	8.39745	2030.00000
.599	-5.975	1251.80400	1596.73000	315.49580	521.98220	99.89999	2.49918	1261.56000	1301.16000	8.61211	2030.03500
.600	-4.979	1251.75400	1597.17999	315.91460	521.93430	99.89999	2.50108	1261.52000	1301.16000	8.94663	2030.00000
.600	-3.977	1251.87700	1597.13000	315.77200	521.76710	99.70000	2.50166	1261.64000	1301.16000	9.26024	2030.03500
.600	-2.974	1251.72701	1597.00999	315.79390	521.85380	99.80000	2.50106	1261.49001	1301.16000	9.73095	2030.07001
.600	-1.968	1251.60100	1596.75999	315.68800	521.86210	99.80000	2.50047	1261.36000	1301.17000	9.95659	2030.07001
.601	-.949	1251.61400	1597.09000	315.95410	521.92600	99.89999	2.50115	1261.38000	1301.17000	10.18316	2030.07001
.600	-.078	1252.32500	1597.06000	315.34550	522.20020	100.10000	2.49777	1262.08000	1301.14000	8.98165	2030.21001
.600	.971	1251.95599	1597.25699	315.81670	522.13750	100.10000	2.49965	1261.72000	1301.14000	8.96333	2030.24500
.600	1.989	1251.81599	1597.11000	315.080490	522.04150	100.00000	2.50005	1261.58000	1301.13000	8.92990	2030.24500
.600	GRADIENT	.03042	.00746	.01867	.04402	-.04406	-.00031	.03012	-.00441	-.04140	.03809

RUN NO. 1747/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
-.800	-7.999	880.01950	1341.16000	394.03440	495.92580	99.70000	2.50051	889.91990	1045.49001	5.51982	2029.16000
.800	-6.978	879.65330	1341.34000	394.41700	495.75930	99.59999	2.50228	889.55980	1045.49001	5.54474	2029.16000
.800	-5.977	880.07420	1340.89999	393.80520	495.78490	99.50000	2.50077	889.97000	1045.47000	5.57237	2029.12500
.800	-4.976	879.71460	1341.30000	394.34570	495.68480	99.50000	2.50262	889.61990	1045.45000	5.34252	2029.09000
.800	-3.981	879.44340	1341.22000	394.47090	495.56080	99.39999	2.50344	889.34990	1045.44000	5.39280	2029.12500
.800	-2.974	879.46560	1341.07001	394.47470	495.49150	99.30000	2.50352	889.36990	1045.42999	5.43116	2029.12500
.801	-1.972	879.09960	1341.22000	394.70430	495.41670	99.30000	2.50463	889.01000	1045.42000	5.46854	2029.12500
.801	-.965	879.29490	1340.99001	394.40140	495.47270	99.30000	2.50358	889.20000	1045.41000	5.46948	2029.16000
.800	-.147	879.32010	1340.66000	394.13990	495.42290	99.20000	2.50311	889.22000	1045.39999	5.47084	2029.12500
.800	.988	879.83150	1340.92999	393.99240	495.29930	99.00000	2.50417	889.73000	1045.37000	5.79593	2029.23000
.800	1.998	880.00200	1341.02000	393.94310	495.31710	99.00000	2.50414	889.89990	1045.35001	5.82239	2029.30000
.800	GRADIENT	.04287	-.05896	-.07279	-.04783	-.04783	-.00014	.04156	-.01364	.06476	.02389

RUN NO. 1660/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.900	-8.000	752.69430	1272.78000	426.60280	481.58500	99.89999	2.49898	762.70000	980.52980	1.57684	2028.88000
.899	-6.979	753.26320	1273.17999	426.53910	481.64580	99.89999	2.49933	763.26980	980.58980	1.56822	2028.88000
.900	-5.970	752.78540	1272.73000	426.51420	481.77930	100.10000	2.49757	762.78980	980.66990	1.56878	2028.84500
.900	-4.971	752.44140	1272.85001	426.80130	481.70340	100.10000	2.49834	762.45000	980.71000	1.56863	2028.84500
.900	-3.977	752.81690	1273.37000	426.93510	481.62990	100.00000	2.49985	762.82980	980.76980	1.56394	2028.84500
.900	-2.966	752.34370	1272.64000	426.71530	481.79420	100.20000	2.49732	762.34990	980.84990	1.55276	2028.84500
.900	-.966	752.68380	1272.81000	426.62940	481.66600	100.00000	2.49849	762.68990	980.91990	1.54454	2028.88000
.900	-.955	752.52910	1273.07001	426.90040	481.60960	100.00000	2.49941	762.53980	980.98000	1.54024	2028.84500
.900	-.086	752.31450	1272.55000	426.67070	481.79860	100.20000	2.49711	762.31980	982.20000	1.40702	2028.91499
.900	.994	752.31790	1272.33000	426.51780	481.82300	100.20000	2.49651	762.31980	982.24000	1.40727	2028.88000
.900	2.003	753.21780	1273.53000	426.80640	481.85790	100.00000	2.49861	763.23000	982.26980	1.40594	2028.88000
.900	0.03313	-.00445	-.02277	-.02387	-.02277	-.02277	.02016	-.00017	.02380	.026690	.00702

IA310 (AEDC 16TE-783) REPEAT BIINS

IA310 (AEDC 16TE-783) REPEAT BIINS

( VCM068 ) ( M OCT 91 )

BUN NO 1739/ S BN/1 = 2.51 GRADIENT INTERVAL = -5 00/- 5 0

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	PATM
1.099	-8 .003	565 .66890	1206 .38000	478 .30660	449 .48070	98 .39999	2 .50900	.575 .85990	.912 .25000	.98961 .2030 .420
1.101	-6 .975	564 .57570	1206 .39999	478 .75020	449 .23020	98 .39999	2 .50957	.574 .76980	.912 .22000	.99494 .2030 .384
1.101	-5 .975	564 .38940	1206 .05000	478 .62040	449 .22510	98 .39999	2 .50885	.574 .57980	.912 .20000	1 .02238 .2030 .384
1.100	-4 .974	564 .73220	1205 .85001	478 .36870	449 .32420	98 .39999	2 .50823	.574 .91990	.912 .16990	1 .03638 .2030 .384
1.100	-3 .968	564 .71090	1205 .97000	478 .44680	449 .38720	98 .50000	2 .50793	.574 .89990	.912 .16990	1 .05875 .2030 .384
1.100	-2 .977	564 .62080	1205 .96001	478 .47660	449 .36770	98 .50000	2 .50795	.574 .80980	.912 .12990	1 .01697 .2030 .384
1.100	-1 .970	564 .60080	1205 .94000	478 .47290	449 .36550	98 .50000	2 .50791	.574 .78980	.912 .11990	1 .02247 .2030 .350
1.100	-.971	564 .81930	1206 .12000	478 .49120	449 .39580	98 .50000	2 .50822	.575 .01000	.912 .09990	1 .02783 .2030 .315
1.100	-.041	565 .03030	1206 .09000	478 .39060	449 .44700	98 .50000	2 .50805	.575 .22000	.912 .06980	1 .03339 .2030 .315
1.100	1 .007	564 .86040	1206 .05000	478 .43430	449 .49320	98 .59999	2 .50734	.575 .04980	.911 .98000	1 .05868 .2030 .315
1.100	2 .014	564 .99100	1206 .03000	478 .37110	449 .53240	98 .59999	2 .50734	.575 .17980	.911 .98000	1 .06154 .2030 .315
GRADIENT		04782	.02663	-.00340	.02625	-.00009	.04799	-.02893	.00274	-.00274

RUN NO. 1723/0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/

		P	PT	Q(PSF)	T(R)	T(F)	RN/L	PC	PREF	SH10+3	PATM
MACH	ALPHA										
1.250	-7 .999	462 .66280	1197 .98000	505 .0980	426 .91800	100 .60000	2 .49653	472 .78980	855 .93990	1 .04320	2030 .840
1.250	-6 .994	462 .63180	1198 .25000	506 .01270	426 .81130	100 .60000	2 .49704	472 .49000	856 .98000	1 .04296	2030 .804
1.250	-5 .971	462 .55370	1197 .89000	505 .78810	426 .89840	100 .60000	2 .49633	472 .67990	856 .00000	1 .04889	2030 .804
1.250	-4 .969	462 .26460	1197 .87000	505 .84130	426 .74800	100 .50000	2 .49684	472 .38990	856 .02980	1 .04610	2030 .804
1.250	-3 .973	462 .42240	1198 .14000	505 .94360	426 .76220	100 .50000	2 .49741	472 .54980	856 .02980	1 .03468	2030 .770
1.250	-2 .972	462 .65210	1198 .11000	505 .87820	426 .82570	100 .50000	2 .49738	472 .77980	856 .08980	1 .03471	2030 .804
1.250	-1 .970	462 .55350	1197 .92999	505 .80830	426 .81810	100 .50000	2 .49700	472 .67990	856 .09990	1 .03765	2030 .770
1.250	-.960	462 .56270	1198 .03000	505 .85720	426 .81030	100 .50000	2 .49721	472 .68990	856 .10990	1 .03478	2030 .735
1.250	.918	462 .58230	1198 .06000	505 .86790	426 .81250	100 .50000	2 .49727	472 .71000	856 .12990	1 .03475	2030 .735
1.250	.996	462 .69310	1197 .92000	505 .77290	426 .85600	100 .50000	2 .49700	472 .81980	856 .17990	1 .02656	2030 .700
1.250	.008	462 .49100	1198 .32001	506 .01980	426 .76200	100 .50000	2 .49779	472 .61990	856 .17990	1 .02622	2030 .700
GRADIENT	.03261	.02378		.00491	.00619	-.00000	.00005	.03288	.02296	-.00216	-.015

RUN NO. 1712/ O RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00/

	P	Q(PSF)	R(R)	S( $\perp$ )	T(L)	U( $\perp$ )	V(L)	W( $\perp$ )	X(L)	Y( $\perp$ )	Z(L)	PREF	SH10+3	PATM		
ALPHA	-7	.997	381.82450	1214.92999	523.80200	402.50590	100.60000	2.49506	391.52980	872.98000	1.25930	2030.735				
MACH	1.400	-1	.400	381.974	381.88010	1215.53000	524.46610	100.60000	2.49620	391.58980	872.96000	1.25204	2030.735			
	-6	.400	381.56860	1214.71001	523.71090	402.44970	100.60000	2.49447	391.26980	872.92990	1.24629	2030.770				
	-5	.400	381.974	381.88280	1215.08000	523.86650	402.50930	100.60000	2.49538	391.58980	872.89990	1.24262	2030.735			
	-4	.400	-3	.973	381.67700	1214.75999	523.73050	402.47780	100.60000	2.49464	391.37990	872.87990	1.24624	2030.700		
	-2	.972	381.82420	1214.97000	523.81960	402.50220	100.60000	2.49514	391.52980	872.95990	1.23291	2030.700				
	-1	.972	381.78390	1215.06300	523.85960	402.40970	100.50000	2.49586	391.49000	872.85990	1.22957	2030.700				
	-	.966	381.68530	1215.00999	523.83980	402.38480	100.50000	2.49570	391.38990	872.82980	1.23287	2030.700				
	.111	.399	382.11110	1214.92000	523.79170	402.52150	100.50000	2.49585	391.81980	872.80980	1.23623	2030.735				
	.998	381.90360	1214.92999	523.80030	402.45800	100.50000	2.49571	391.60990	872.74000	1.23622	2030.735					
	2.020	381.90360	1215.00999	523.84860	402.44730	100.50000	2.49591	391.60990	872.70000	1.22634	2030.700					
GRADIENT	0.2463	0.2463	0.0431	0.0138	-	0.0583	-	0.1787	0.0013	-	0.0179	0.006	0.2703			

## PARAMETRIC DATA

RUN NO.		1705/ 0		RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180. 000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
1.450	-7.994	358.88480	1225.88000	528.12820	394.50120	100.70000	2.49482	368.35990	88.3 92990	1.29153	2030.56000
1.450	-6.971	358.69730	1225.92999	528.13920	394.43770	100.70000	2.49473	368.16990	88.3 96000	1.28474	2030.52499
1.450	-5.968	359.05220	1225.89000	528.14090	394.55270	100.70000	2.49500	368.52980	88.3 96000	1.28474	2030.49001
1.450	-4.971	358.74660	1225.92999	528.14180	394.45310	100.70000	2.49478	368.22000	88.3 97000	1.29148	2030.56000
1.450	-3.968	358.83590	1225.81000	528.09670	394.42190	100.60000	2.49525	368.30980	88.4 01000	1.29161	2030.56000
1.450	-2.965	358.89400	1225.99001	528.17460	394.42360	100.60000	2.49562	368.36990	88.4 01000	1.29142	2030.52499
1.450	-1.961	358.88380	1226.10001	528.21970	394.41020	100.60000	2.49580	368.35990	88.4 02980	1.29130	2030.52499
1.450	-0.944	358.63870	1225.89000	528.11870	394.34620	100.60000	2.49518	368.08980	88.4 03980	1.29493	2030.52499
1.449	-.091	359.22800	1226.21001	528.28300	394.57860	100.70000	2.49573	368.71000	88.4 08980	1.31173	2030.52499
1.450	.974	358.87550	1225.75999	528.07790	394.50930	100.70000	2.49460	368.34990	88.4 09990	1.30876	2030.52499
1.450	2.001	358.86250	1226.36000	528.32670	394.45000	100.70000	2.49564	368.33980	88.4 09990	1.31157	2030.49001
GRADIENT	.01998	.03841	.01700	.00937	.00941	.00003	.02048	.01927	.00347	-.00804	

RUN NO. 1698/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

RUN NO.		1698/ 0		RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180. 000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
1.471	-7.998	347.88310	1225.50999	527.23538	390.17260	100.30000	2.49688	357.22000	88.7 46000	1.23201	2030.38499
1.471	-6.970	347.94120	1225.63254	527.28960	390.17500	100.30000	2.49725	357.27980	88.7 46000	1.23509	2030.38499
1.472	-5.972	347.79390	1225.52167	527.23180	390.13600	100.30000	2.49694	357.12990	88.7 47000	1.23518	2030.35001
1.471	-4.970	347.84420	1225.19762	527.10452	390.10790	100.20000	2.49711	357.17990	88.7 48000	1.23873	2030.38499
1.471	-3.973	348.18900	1225.1840	527.11840	390.29080	100.30000	2.49682	357.52980	88.7 48000	1.24203	2030.42000
1.471	-2.970	347.96220	1225.32312	527.16516	390.20530	100.30000	2.49683	357.29980	88.7 48000	1.23862	2030.45500
1.471	-1.962	348.05980	1225.44525	527.22355	390.15700	100.20000	2.49772	357.39990	88.7 48000	1.23851	2030.49001
1.470	-.947	347.97950	1223.32355	526.34942	390.10030	100.20000	2.49822	357.31980	88.7 48000	1.36828	2030.45500
1.469	.149	348.05050	1222.27794	525.92841	390.16380	100.20000	2.49752	357.38990	88.7 49000	1.40139	2030.42000
1.469	.980	348.00150	1221.54694	525.62608	390.15090	100.20000	2.49741	357.33980	88.7 50000	1.43849	2030.42000
1.469	2.007	348.09910	1221.67307	525.68501	390.16500	100.20000	2.49784	357.43990	88.7 50000	1.44203	2030.45500
GRADIENT	.01232	-.64350	-.26192	-.00577	-.00958	.00013	.01266	.00320	.03603	.00415	

RUN NO.		1668/ 0		RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00	BETA =	.000	PHI =	180. 000
MACH	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM	
1.496	-7.999	337.78120	1233.62502	529.46005	386.63160	100.90000	2.49523	346.98000	945.77980	1.07786	2029.54500
1.497	-6.971	337.60380	1233.72150	529.47593	386.55760	100.90000	2.49533	346.79980	945.76980	1.08058	2029.58000
1.497	-5.968	337.59350	1233.81566	529.51217	386.54520	100.90000	2.49549	346.78980	945.79980	1.08050	2029.58000
1.496	-4.966	337.67430	1233.31122	529.32223	386.68870	101.00000	2.49407	346.86990	945.78980	1.08097	2029.50999
1.497	-3.969	337.40330	1232.47920	528.96056	386.61230	100.90000	2.49281	346.58980	945.80980	1.07600	2029.58000
1.497	-2.967	337.09330	1231.49928	528.53400	386.66990	101.00000	2.49014	346.26980	945.79980	1.07401	2029.61501
1.497	-1.965	337.11080	1231.95682	528.71774	386.62920	101.00000	2.49104	346.28980	945.79980	1.07643	2029.61501
1.497	-.953	337.38210	1232.84052	529.10086	386.64040	101.00000	2.49283	346.56980	945.79980	1.07567	2029.61501
1.497	161	337.42160	1232.64491	529.02795	386.65970	101.00000	2.49276	346.60990	945.77980	1.08438	2029.61501
1.496	.878	337.56930	1232.48378	528.98197	386.78590	101.00000	2.49217	346.75980	945.81980	1.09027	2029.58000
1.496	1.999	337.51308	1232.57704	529.01521	386.6250	101.00000	2.49239	346.73000	945.78980	1.09305	2029.58000
GRADIENT	.01308	-.000908	-.00201	.01594	.02008	-.00006	.01343	-.00026	.000221	.000603	

## IA310 (AEDC 16TF-783) REPEAT RUNS

(VCM069) (04 OCT 91)

## PARAMETRIC DATA

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.520	-7.997	327.34330	1237.04378	529.35477	382.26270	100.40000	2.49555	336.36990	911.88990	1.15822	2030.03500
1.520	-6.969	327.266610	1236.68816	529.20583	382.26420	100.40000	2.49593	336.28980	911.85990	1.16158	2030.03500
1.520	-5.968	327.38280	1236.99091	529.34100	382.28120	100.40000	2.49650	336.40990	911.85990	1.15827	2030.00000
1.520	-4.966	327.31540	1236.64211	529.19462	382.28930	100.40000	2.49583	336.33980	911.84990	1.15860	2030.03500
1.520	-3.970	327.13890	1236.66246	529.17490	382.23050	100.40000	2.49561	336.15990	911.83980	1.15553	2030.03500
1.520	-2.967	327.29490	1236.96060	529.31509	382.32980	100.50000	2.49561	336.31980	911.84990	1.15224	2030.00000
1.520	-1.965	327.38350	1236.85083	529.28632	382.36650	100.50000	2.49558	336.40990	911.82980	1.15538	2030.00000
1.520	-0.952	327.29420	1237.24240	529.42353	382.31200	100.50000	2.49594	336.31980	911.80980	1.14596	2030.03500
1.520	-16.3	327.23680	1236.84645	529.26141	382.32790	100.50000	2.49520	336.25980	911.78980	1.14633	2030.00000
1.520	.984	327.33370	1237.31079	529.33103	382.33130	100.50000	2.49587	336.35990	911.74000	1.13693	2030.03500
1.520	2.000	327.37380	1237.03496	529.35567	382.37010	100.50000	2.49544	336.39990	911.72000	1.13719	2030.00000
GRADIENT	.01306	.01306	.07130	.02961	.01201	.01434	-.00003	.01343	-.01907	-.00320	-.00255

RUN NO. 1686/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	ALPHA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.545	-7.992	316.58760	1241.84787	529.31249	378.38480	101.20000	2.49248	325.41990	911.91990	1.33273	2029.75500
1.542	-6.974	317.86380	1240.79028	529.15784	378.93290	101.20000	2.49211	326.72000	911.92990	1.33063	2029.78999
1.543	-5.972	317.29570	1240.95078	529.11127	378.71850	101.20000	2.49171	326.13990	911.93990	1.33037	2029.75500
1.543	-4.971	317.22800	1240.65030	528.98394	378.72140	101.20000	2.49113	326.06980	911.96000	1.33069	2029.78999
1.543	-3.969	317.13260	1239.95296	528.70332	378.74490	101.20000	2.48993	325.97000	911.97000	1.33488	2029.75500
1.542	-2.968	317.64090	1240.11598	528.86085	378.84200	101.10000	2.49140	326.49000	911.98000	1.33477	2029.72000
1.542	-1.960	317.58250	1240.01111	528.81016	378.83080	101.10000	2.49115	326.42990	9112.00000	1.33488	2029.72000
1.543	-0.952	317.22920	1240.19489	528.81226	378.89530	101.10000	2.49114	326.06980	9112.01000	1.33807	2029.75500
1.543	-16.4	317.64840	1240.75888	529.10526	378.78760	101.10000	2.49249	326.50000	9112.01980	1.33407	2029.75500
1.543	.983	317.62890	1240.78937	529.11320	378.78270	101.10000	2.49243	326.48000	9112.04980	1.33060	2029.78999
1.543	1.994	317.64770	1241.19150	529.26938	378.76760	101.10000	2.49286	326.50000	9112.04980	1.31991	2029.78999
GRADIENT	.06084	.06084	.11991	.05694	.00245	-.01436	-.00333	.01375	.06255	-.00112	.00365

RUN NO. 1679/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

IA310 (AEDC 16TF-783) REPEAT RUNS

(VCM070) (04 OCT 91)

## PARAMETRIC DATA

RUN NO. 1674/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.601	-3.798	1251.50900	1597.25000	316.17430	522.08520	100.10000	2.50094	1261.28000	1301.03000	6.64267	2030.24500
.601	-2.772	1251.58000	1597.25999	316.12480	521.99950	100.00000	2.50134	1261.35001	1301.03000	6.56428	2030.17500
.601	-1.749	1251.26700	1596.64999	315.86890	521.92580	99.89999	2.50046	1261.03000	1301.00999	6.50214	2030.21001
.601	-.732	1251.53000	1597.17999	316.09810	522.00100	100.00000	2.50117	1261.30000	1301.00000	6.41041	2030.21001
.601	-.290	1251.30000	1597.07001	316.19510	521.98360	100.00000	2.50143	1261.07001	1301.02000	6.12437	2030.24500
.600	.738	1251.64000	1596.82001	315.70610	522.14090	100.10000	2.49888	1261.39999	1301.02000	6.01641	2030.24500
.600	1.758	1251.97701	1596.73000	315.35400	522.09620	100.00000	2.49809	1261.73000	1301.03000	5.92140	2030.24500
.600	2.783	1251.82401	1597.25999	315.92480	521.93510	99.89999	2.50118	1261.59000	1301.05000	5.83714	2030.24500
.600	3.824	1251.99400	1597.36000	315.86940	522.22580	100.20000	2.49936	1261.75999	1301.07001	5.73252	2030.28000
GRADIENT		.07628	.00576	-.05767	.01503	.00696	-.00024	.07519	.00504	-.00385	.00796

RUN NO. 1750/ 0 RN/L = 2.51 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.799	-3.857	880.28490	1340.35001	393.25460	494.99000	98.50000	2.50448	890.16990	1044.95000	7.62348	2030.45500
.800	-2.832	879.95190	1340.97000	393.93990	494.87110	98.50000	2.50697	889.84990	1044.92000	7.61992	2030.42000
.800	-1.818	880.07010	1341.82001	394.48880	494.80050	98.50000	2.50934	889.98000	1044.91000	7.58481	2030.42000
.800	-.810	880.53760	1342.28000	394.51120	494.82710	98.50000	2.50991	890.45000	1044.89999	7.53706	2030.38499
.800	-.212	879.64580	1341.14999	394.28120	494.80300	98.50000	2.50806	889.54980	1044.89999	7.36530	2030.31500
.800	.826	879.40060	1340.71001	394.12260	494.72120	98.39999	2.50774	889.29980	1044.87000	7.26554	2030.28000
.800	1.837	879.40990	1340.75000	394.14580	494.71850	98.39999	2.50784	889.30980	1044.84000	7.19311	2030.21001
.800	2.848	879.57350	1340.62000	393.93850	494.75850	98.39999	2.50716	889.47000	1044.85000	7.15080	2030.14000
.800	3.869	879.77250	1340.83000	393.95870	494.67970	98.30000	2.50802	889.66990	1044.83000	7.09268	2030.14000
GRADIENT		-.09524	-.04439	.03196	-.03250	-.02467	.00018	-.09499	-.01513	-.07989	-.04595

RUN NO. 1663/ 0 RN/L = 2.50 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
.899	-3.844	753.15450	1273.03000	426.50070	481.98660	100.30000	2.49675	763.15990	983.75000	1.28009	2028.91499
.900	-2.815	752.32100	1272.80000	426.83860	481.85890	100.30000	2.49721	762.32980	983.75980	1.27697	2028.91499
.900	-1.803	752.40670	1273.16000	427.03490	481.83570	100.30000	2.49808	762.41990	983.81980	1.26658	2028.88000
.900	-.791	752.67410	1272.78000	426.61470	481.92550	100.30000	2.49670	762.67990	983.85990	1.25041	2028.91499
.900	-.227	752.73880	1273.21001	426.87180	481.89110	100.30000	2.49779	762.75000	984.01980	1.24343	2028.91499
.900	.813	752.42360	1272.69000	426.70210	481.8960	100.30000	2.49678	762.42990	984.03980	1.23740	2028.91499
.900	1.818	752.60860	1273.14000	426.90110	481.87480	100.30000	2.49777	762.61990	984.08980	1.22400	2028.95000
.900	2.839	752.90530	1272.81000	426.49780	481.96460	100.30000	2.49648	762.90990	984.09990	1.20828	2028.95000
.900	3.865	752.95510	1272.86000	426.50240	481.96850	100.30000	2.49655	762.96000	984.15990	1.20187	2028.91499
GRADIENT		.01934	-.01494	-.02178	.00515	-.00000	-.00007	.01901	.05895	-.01088	.00423

IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 1044

(VCM070) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO. 1726 / O RN/L = 2.50 GRADIENT INTERVAL = -5.00 / 5.00

RN/L = 2.49 GRADIENT INTERVAL = -5.88/ 5.88

	CH	P	PT	Q(PSF)	T(R)	T(F)	RN/L	PC	PREF	SH10+3	PAIM
BETA	-3.892	381.97360	1214.78000	523.73340	402.63700	100.70000	2.49431	391.67990	873.59990	1.13271	2031.08501
	-2.866	381.52950	1214.61000	523.66800	402.51930	100.70000	2.49367	391.23000	873.59990	1.12685	2031.08501
	-1.858	381.75560	1214.84000	523.76420	402.56570	100.70000	2.49426	391.46000	873.59990	1.12964	2031.15500
	- .851	381.61600	1215.03000	523.84990	402.50560	100.70000	2.49450	391.31980	873.57980	1.12946	2031.12000
	- .163	381.76610	1214.75999	523.72880	402.50440	100.60000	2.49471	391.47000	873.57980	1.13575	2031.12000
	.886	381.89260	1215.10001	523.87500	402.51050	100.60000	2.49542	391.59990	873.55980	1.13543	2031.12000
	1.894	381.77540	1214.84000	523.76370	402.42800	100.50000	2.49546	391.48000	873.53980	1.14174	2031.15500
	2.898	382.04220	1214.88000	523.77590	402.50440	100.50000	2.49573	391.75000	873.52980	1.14474	2031.15500
	3.926	381.87380	1214.92460	523.80540	402.44800	100.50000	2.49571	391.57980	873.52980	1.15079	2031.12000
GRADIENT		0.22460	0.24663	0.22463	0.24663	0.11115	-	0.1855	-	0.0269	0.00609
		0.00226	0.02502	0.00226	0.02502	-	-	0.0991	-	0.00269	0.00609

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1045

IA310 (AEDC 16TF-783) REPEAT RUNS

(VCM070) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1708/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		ALPHA =	-4.000	PHI	$\pm$	180.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.450	-3.810	359.02270	1225.86000	528.12700	394.47580	100.60000	2.49551	368.50000	884.32980	1.29155	2030.38499
1.450	-2.773	358.81620	1225.81000	528.09550	394.41580	100.60000	2.49523	368.28980	884.33980	1.29161	2030.38499
1.450	-1.757	358.89210	1226.35001	528.32400	394.38990	100.60000	2.49625	368.36990	884.35990	1.28764	2030.38499
1.450	-7.740	358.76590	1226.03999	528.18870	394.33870	100.60000	2.49558	368.24000	884.34990	1.28120	2030.38499
1.450	-2.76	359.12010	1226.14000	528.24830	394.48070	100.60000	2.49609	368.59990	884.39990	1.29126	2030.45500
1.450	.759	358.87550	1225.75999	528.07790	394.43900	100.60000	2.49519	368.34990	884.37990	1.28488	2030.45500
1.450	1.776	359.05250	1225.85001	528.12430	394.48610	100.60000	2.49552	368.52980	884.38990	1.28817	2030.45500
1.449	2.820	359.32640	1226.28000	528.31690	394.53250	100.60000	2.49554	368.80980	884.37990	1.28433	2030.49001
1.450	3.841	358.82540	1225.94000	528.15010	394.40650	100.60000	2.49546	368.29980	884.37990	1.28131	2030.52499
GRADIENT		.01903	.00933	.00484	.00510	.00000	.00003	.01931	.00706	-.00109	.02164

RUN NO.		1701/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		ALPHA =	-4.000	PHI	$\pm$	180.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.469	-3.822	348.04980	1222.71883	526.10803	390.07860	100.10000	2.49841	357.38990	887.48000	1.38662	2030.66499
1.469	-2.791	347.99270	1222.25143	525.91338	390.09640	100.10000	2.49765	357.32980	887.48000	1.39070	2030.63000
1.470	-1.772	347.88260	1222.76793	526.11456	390.02510	100.10000	2.49823	357.22000	887.48000	1.38299	2030.63000
1.470	-.761	347.98140	1222.75858	526.11893	390.06490	100.10000	2.49818	357.31980	887.45000	1.37948	2030.66499
1.470	-.253	347.96170	1222.60094	526.05364	390.06030	100.10000	2.49812	357.29980	887.47000	1.38674	2030.63000
1.470	.800	347.98140	1222.60318	526.05569	390.13620	100.20000	2.49755	357.31980	887.47000	1.38674	2030.59500
1.470	1.821	347.95190	1222.58012	526.04351	390.12870	100.20000	2.49746	357.28980	887.46000	1.38676	2030.59500
1.469	2.820	348.11990	1222.63702	526.08102	390.19140	100.20000	2.49749	357.46000	887.45000	1.37964	2030.59500
1.470	3.850	347.91330	1222.65172	526.06936	390.12820	100.20000	2.49722	357.25000	887.46000	1.37606	2030.56000
GRADIENT		-.00072	.00703	.00283	.01340	.01765	-.00013	-.00079	-.00344	-.00113	-.01175

RUN NO.		1694/ 0	RN/L =	2.50	GRADIENT INTERVAL = -5.00/ 5.00		ALPHA =	-4.000	PHI	$\pm$	180.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.495	-.837	337.38480	1229.58562	527.81026	386.14580	100.20000	2.49654	346.56980	910.48000	1.24537	2030.24500
1.495	-2.802	337.37280	1229.94609	527.95094	386.09890	100.20000	2.49734	346.55980	910.49000	1.25147	2030.28000
1.495	-1.786	337.45120	1230.17976	528.05322	386.11840	100.20000	2.49755	346.63990	910.49000	1.24154	2030.24500
1.495	-.778	337.55660	1230.77925	528.30296	386.10400	100.20000	2.49861	346.75000	910.49000	1.23772	2030.24500
1.495	-.240	337.64480	1231.18439	528.47436	386.12480	100.20000	2.49887	346.83980	910.47000	1.21817	2030.28000
1.495	.799	337.54710	1230.80959	528.31433	386.17160	100.30000	2.49797	346.74000	910.41990	1.23447	2030.24500
1.495	1.817	337.43820	1230.68259	528.25074	386.12260	100.30000	2.49810	346.62990	910.43990	1.25071	2030.28000
1.495	2.838	337.54760	1230.01933	528.00089	386.18240	100.30000	2.49776	346.74000	910.40990	1.27763	2030.24500
1.494	3.869	337.60740	1227.90752	527.17020	386.21970	100.30000	2.49749	346.79980	910.38990	1.40067	2030.24500
GRADIENT		.02404	-.10507	-.03888	.01097	.01756	.00009	.02493	-.01354	.01307	-.00077

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 1046  
(VCM070) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO. 1689/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.521	-3.833	327.27540	1237.96227	529.69909	382.45800	100.70000	2.49442	336.29980	911.33980	1.08383	2030.31500
1.521	-2.804	327.24580	1237.86812	529.65767	382.45260	100.70000	2.49430	336.26980	911.35990	1.08677	2030.28000
1.521	-1.786	327.17800	1237.59079	529.54022	382.44650	100.70000	2.49390	336.20000	911.33980	1.09275	2030.28000
1.520	- .775	327.21750	1237.55737	529.53341	382.46340	100.70000	2.49388	336.24000	911.34990	1.09278	2030.28000
1.520	- .241	327.45870	1238.51207	529.93983	382.39230	100.60000	2.49637	336.49000	911.31980	1.09195	2030.28000
1.520	.809	327.28540	1237.80563	529.63945	382.40360	100.60000	2.49483	336.30980	911.26980	1.08683	2030.24500
1.520	1.827	327.44310	1237.66545	529.60998	382.47490	100.60000	2.49468	336.47000	911.26000	1.08412	2030.24500
1.520	2.854	327.47170	1237.89244	529.70238	382.46410	100.60000	2.49510	336.50000	911.24000	1.08392	2030.24500
1.520	3.870	327.49020	1238.27167	529.85226	382.44750	100.60000	2.49556	336.51980	911.21000	1.07505	2030.21001
GRADIENT	.03679	.02678	.01608	.00018	-.01712	.00016	.03756	-.01966	-.00119	-.01118	

RUN NO. 1682/ 0 RN/L = 2.49 GRADIENT INTERVAL = -5.00/ 5.00

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.543	-3.836	317.48490	1241.23175	529.25664	378.79660	101.10000	2.49103	326.32980	912.11990	1.25330	2029.86000
1.543	-2.801	317.56130	1241.59015	529.40549	378.78300	101.10000	2.49189	326.40990	912.12990	1.25946	2029.86000
1.543	-1.788	317.59840	1242.16013	529.62868	378.74560	101.10000	2.49289	326.45000	912.12990	1.25887	2029.82500
1.543	- .776	317.45210	1242.11456	529.58315	378.70260	101.10000	2.49256	326.29980	912.13990	1.25564	2029.78999
1.544	- .243	317.78300	1242.58205	529.82279	378.77320	101.10000	2.49382	326.63990	912.12990	1.25846	2029.82500
1.543	.797	317.55050	1241.99054	529.55573	378.75270	101.10000	2.49239	326.39990	912.09990	1.25253	2029.82500
1.544	1.818	317.56010	1242.11923	529.60638	378.81640	101.20000	2.49193	326.40990	912.09990	1.24915	2029.82500
1.543	2.831	317.66970	1241.56647	529.41766	378.90380	101.20000	2.49113	326.51980	912.09990	1.24973	2029.82500
1.544	3.870	317.45240	1242.08701	529.57336	378.78150	101.20000	2.49175	326.29980	912.08980	1.24917	2029.78999
GRADIENT	.00251	.05420	.02099	.00848	-.01605	.00003	.00269	-.00543	-.00121	-.00639	

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

PAGE 1047

IA310 (AEDC 16TF-783) REPEAT RUNS

(VCM071) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.601	-3.993	1251.17599	1597.14000	316.35520	521.96240	100.00000	2.50207	1260.95000	1301.02000
.601	-2.974	1251.36400	1596.39999	315.57960	522.05400	100.00000	2.49863	1261.12000	1301.00000
.601	-1.969	1251.24100	1596.94000	316.13380	521.98900	100.00000	2.50110	1261.00999	1300.99001
.601	-.950	1251.58099	1597.22000	316.09060	522.00320	100.00000	2.50118	1261.35001	1300.98000
.600	-.173	1251.83099	1596.89999	315.61670	522.06300	100.00000	2.49919	1261.59000	1300.98000
.601	.831	1251.58200	1597.14999	316.03080	522.01000	100.00000	2.50090	1261.35001	1301.00000
.601	1.996	1251.64999	1597.31000	316.10940	522.00320	100.00000	2.50132	1261.42000	1301.00000
.600	3.003	1252.06000	1597.12000	315.61380	522.06980	100.00000	2.49937	1261.82001	1301.00999
.601	4.011	1251.79201	1597.33000	316.01000	522.01810	100.00000	2.50098	1261.56000	1300.98000
GRADIENT	.03949	.06049	-.02253	.0502	-.00000	-.00000	-.00003	.08932	-.00150
RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.799	-3.996	880.32840	1340.80000	393.55810	494.77220	98.30000	2.50693	890.22000	1044.78000
.800	-2.975	879.67480	1341.23000	394.32080	494.62180	98.30000	2.50941	889.57980	1044.75999
.800	-1.973	879.81490	1341.33000	394.29930	494.63380	98.30000	2.50946	889.72000	1044.74001
.800	-.960	879.61160	1341.42999	394.51200	494.59060	98.30000	2.51013	889.51980	1044.74001
.800	-.100	879.91770	1341.24001	394.16330	494.74850	98.39999	2.50843	889.81980	1044.75000
.800	.982	879.71390	1340.71001	393.90970	494.94900	98.59999	2.50602	889.60990	1044.71001
.800	2.008	879.62160	1340.78000	394.02420	494.92680	98.59999	2.50640	889.51980	1044.71001
.800	3.009	879.67260	1340.75999	393.97460	495.02560	98.70000	2.50567	889.56980	1044.71001
.800	4.014	879.77200	1340.85001	393.97360	495.03220	98.70000	2.50577	889.66990	1044.69000
GRADIENT	-.04202	-.04981	-.00826	.05308	.06156	-.00043	-.04241	-.00999	-.03120
RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.900	-3.998	753.16160	1273.24001	426.64060	481.87890	100.20000	2.49789	763.16990	984.26980
.900	-2.967	752.14460	1272.64000	426.65530	481.81270	100.20000	2.49719	762.45000	984.27980
.900	-1.967	752.72390	1272.82001	426.61250	481.84420	100.20000	2.49732	762.73000	984.29980
.900	-.957	752.85080	1273.13000	426.75020	481.83400	100.20000	2.49800	762.85990	984.33980
.900	-.141	752.80350	1272.89000	426.61330	481.93750	100.30000	2.49683	762.80980	984.40990
.900	.859	752.75020	1273.10001	426.78930	481.90500	100.30000	2.49747	762.76000	984.47000
.899	2.010	753.09840	1272.70000	426.30710	482.01200	100.30000	2.49592	763.09990	984.48000
.900	3.016	753.02050	1273.22000	426.71090	481.94140	100.30000	2.49745	763.02980	984.50000
.900	4.020	752.80420	1272.85001	426.58540	481.94190	100.30000	2.49672	762.80980	984.52980
GRADIENT	.01601	-.00182	-.01079	.01734	.01649	-.00012	.01587	.03647	-.00188

RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.900	-3.998	753.16160	1273.24001	426.64060	481.87890	100.20000	2.49789	763.16990	984.26980
.900	-2.967	752.14460	1272.64000	426.65530	481.81270	100.20000	2.49719	762.45000	984.27980
.900	-1.967	752.72390	1272.82001	426.61250	481.84420	100.20000	2.49732	762.73000	984.29980
.900	-.957	752.85080	1273.13000	426.75020	481.83400	100.20000	2.49800	762.85990	984.33980
.900	-.141	752.80350	1272.89000	426.61330	481.93750	100.30000	2.49683	762.80980	984.40990
.900	.859	752.75020	1273.10001	426.78930	481.90500	100.30000	2.49747	762.76000	984.47000
.899	2.010	753.09840	1272.70000	426.30710	482.01200	100.30000	2.49592	763.09990	984.48000
.900	3.016	753.02050	1273.22000	426.71090	481.94140	100.30000	2.49745	763.02980	984.50000
.900	4.020	752.80420	1272.85001	426.58540	481.94190	100.30000	2.49672	762.80980	984.52980
GRADIENT	.01601	-.00182	-.01079	.01734	.01649	-.00012	.01587	.03647	-.00188

RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.900	-3.998	753.16160	1273.24001	426.64060	481.87890	100.20000	2.49789	763.16990	984.26980
.900	-2.967	752.14460	1272.64000	426.65530	481.81270	100.20000	2.49719	762.45000	984.27980
.900	-1.967	752.72390	1272.82001	426.61250	481.84420	100.20000	2.49732	762.73000	984.29980
.900	-.957	752.85080	1273.13000	426.75020	481.83400	100.20000	2.49800	762.85990	984.33980
.900	-.141	752.80350	1272.89000	426.61330	481.93750	100.30000	2.49683	762.80980	984.40990
.900	.859	752.75020	1273.10001	426.78930	481.90500	100.30000	2.49747	762.76000	984.47000
.899	2.010	753.09840	1272.70000	426.30710	482.01200	100.30000	2.49592	763.09990	984.48000
.900	3.016	753.02050	1273.22000	426.71090	481.94140	100.30000	2.49745	763.02980	984.50000
.900	4.020	752.80420	1272.85001	426.58540	481.94190	100.30000	2.49672	762.80980	984.52980
GRADIENT	.01601	-.00182	-.01079	.01734	.01649	-.00012	.01587	.03647	-.00188

RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.900	-3.998	753.16160	1273.24001	426.64060	481.87890	100.20000	2.49789	763.16990	984.26980
.900	-2.967	752.14460	1272.64000	426.65530	481.81270	100.20000	2.49719	762.45000	984.27980
.900	-1.967	752.72390	1272.82001	426.61250	481.84420	100.20000	2.49732	762.73000	984.29980
.900	-.957	752.85080	1273.13000	426.75020	481.83400	100.20000	2.49800	762.85990	984.33980
.900	-.141	752.80350	1272.89000	426.61330	481.93750	100.30000	2.49683	762.80980	984.40990
.900	.859	752.75020	1273.10001	426.78930	481.90500	100.30000	2.49747	762.76000	984.47000
.899	2.010	753.09840	1272.70000	426.30710	482.01200	100.30000	2.49592	763.09990	984.48000
.900	3.016	753.02050	1273.22000	426.71090	481.94140	100.30000	2.49745	763.02980	984.50000
.900	4.020	752.80420	1272.85001	426.58540	481.94190	100.30000	2.49672	762.80980	984.52980
GRADIENT	.01601	-.00182	-.01079	.01734	.01649	-.00012	.01587	.03647	-.00188

RUN NO.		RN/L =		GRADIENT INTERVAL = -5.00/ 5.00		ALPHA = .000		PHI = 180.000	
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF
.900	-3.998	753.16160	1273.24001	426.64060	481.87890	100.20000	2.49789	763.16990	984.26980
.900									

## PARAMETRIC DATA

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.100	-3.997	565.09890	1206.23000	478.44480	449.6980	98.89999	2.50600	575.28980	911.31980	.97121	2030.10500
1.100	-2.974	565.00170	1205.95000	478.32030	449.77760	98.89999	2.50540	575.18990	911.32980	.96360	2030.10500
1.100	-1.972	564.73070	1205.99001	478.45070	449.71140	98.89999	2.50562	574.91990	911.29980	.95579	2030.07001
1.100	-.972	564.60280	1205.77000	478.37330	449.70580	98.89999	2.50517	574.78980	911.31980	.94312	2030.03500
1.100	.014	564.97170	1205.95000	478.33230	449.71050	98.89999	2.50541	575.15990	911.29980	.93029	2030.03500
1.100	1.022	564.86080	1206.00000	478.47000	449.74000	98.89999	2.50558	575.04980	911.28980	.91276	2030.00000
1.100	2.022	564.84160	1205.92000	478.37180	449.74320	98.89999	2.50543	575.02980	911.26980	.90295	2030.00000
1.100	3.027	564.93310	1205.81000	478.26590	449.77690	98.89999	2.50511	575.11990	911.26980	.89814	2030.00000
1.100	4.021	565.12010	1206.14000	478.38400	449.78420	98.89999	2.50578	575.30980	911.24000	.90279	2029.89500
GRADIENT	.00585	-.01126	-.00888	.00254	-.00000	-.00000	.00003	.00570	-.00981	-.01009	-.02214
<hr/>											
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.250	-3.998	462.50270	1198.07001	505.89060	426.63820	100.30000	2.49845	472.62990	856.53980	1.00457	2030.73500
1.250	-2.968	462.67260	1198.03000	505.83330	426.68700	100.30000	2.49839	472.79980	856.53980	1.01003	2030.73500
1.250	-1.968	462.34400	1197.94000	505.85940	426.60960	100.30000	2.49817	472.47000	856.53980	1.01011	2030.70000
1.250	-.964	462.73320	1197.89000	505.74880	426.71700	100.30000	2.49812	472.85990	856.54980	1.00472	2030.70000
1.250	.099	462.64280	1198.00000	505.82450	426.68210	100.30000	2.49833	472.76980	856.54980	1.01006	2030.73500
1.250	1.046	462.53200	1198.13000	505.91460	426.63960	100.30000	2.49858	472.65990	856.57980	1.00995	2030.66499
1.250	2.021	462.59160	1198.20000	505.93700	426.64820	100.30000	2.49873	472.72000	856.57980	1.00717	2030.66499
1.250	3.018	462.69190	1198.07001	505.84910	426.68800	100.30000	2.49848	472.81980	856.58980	1.00728	2030.66499
1.250	4.018	462.69170	1198.11000	505.86940	426.68380	100.30000	2.49856	472.81980	856.57980	1.00996	2030.66499
GRADIENT	.01850	-.01722	-.00466	.00311	-.00000	-.00000	.00004	.01870	.00700	.00022	-.00988
<hr/>											
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.400	-4.003	381.72680	1214.74001	523.72090	402.42260	100.50000	2.49524	391.42990	873.47000	1.15405	2031.19000
1.400	-2.974	381.70610	1214.89999	523.79130	402.47310	100.60000	2.49492	391.40990	873.46000	1.15389	2031.19000
1.400	-1.969	381.79250	1215.30000	523.96440	402.46140	100.60000	2.49571	391.50000	873.45000	1.14739	2031.22501
1.400	-.964	381.69730	1214.71001	523.70850	402.41650	100.50000	2.49516	391.39990	873.46000	1.15101	2031.22501
1.400	.092	382.04030	1215.17999	523.90700	402.54740	100.60000	2.49568	391.75000	873.42990	1.13838	2031.19000
1.400	1.046	381.79440	1214.99001	523.82890	402.49120	100.60000	2.49515	391.50000	873.39990	1.12350	2031.15500
1.400	2.020	381.93260	1215.00999	523.83500	402.53100	100.60000	2.49529	391.63990	873.40990	1.12348	2031.15500
1.400	3.018	381.85400	1214.94000	523.80570	402.51390	100.60000	2.49510	391.55980	873.38990	1.12354	2031.15500
1.400	4.023	381.92460	1214.70000	523.69920	402.55790	100.60000	2.49472	391.62990	873.36990	1.12377	2031.19000
GRADIENT	.02703	-.00529	-.00287	.01466	.00836	-.00004	.02733	-.01250	-.00479	-.00523	

IA310 (AEDC 16TF-783) REPEAT RUNS

(VCM071) (04 OCT 91)

## PARAMETRIC DATA

RUN NO.		1709/ 0		RN/L =	2.50	GRADIENT INTERVAL =	- 5.00/ 5.00	ALPHA =	.000	PHI =	180.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.450	-3.994	358.97050	1226.46001	528.37380	394.40430	100.60000	2.49652	368.45000	884.39990	1.28414	2030.45500
1.450	-2.963	358.88450	1225.92000	528.14480	394.42700	100.60000	2.49548	368.35990	884.39990	1.29489	2030.52499
1.450	-1.954	358.69870	1225.67999	528.03540	394.39060	100.60000	2.49489	368.16990	884.37990	1.29174	2030.56000
1.450	- .942	358.93330	1226.00000	528.18040	394.43510	100.60000	2.49567	368.40990	884.38990	1.29141	2030.56000
1.449	- .165	359.48460	1226.17000	528.27910	394.59230	100.60000	2.49649	368.97000	884.41990	1.29463	2030.49001
1.450	.966	358.99320	1225.92000	528.15040	394.46120	100.60000	2.49559	368.47000	884.41990	1.27124	2030.56000
1.450	2.005	358.56760	1226.17999	528.23660	394.30370	100.60000	2.49564	368.03980	884.41990	1.27097	2030.59500
1.451	3.013	359.01220	1226.02000	528.19290	394.45800	100.60000	2.49578	368.49000	884.41990	1.26445	2030.63000
1.450	4.015	358.81520	1226.00000	528.17460	394.39790	100.60000	2.49556	368.28980	884.42990	1.25782	2030.66499
GRADIENT		-.00920	-.01105	-.00506	-.00186	-.00000	-.00003	-.000940	.00613	-.00435	.02075
RUN NO.		1702/ 0		RN/L =	2.50	GRADIENT INTERVAL =	- 5.00/ 5.00	ALPHA =	.000	PHI =	180.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.470	-3.992	347.92310	1222.93153	526.18564	390.13040	100.20000	2.49724	357.25980	887.42990	1.36171	2030.52499
1.470	-2.968	347.76490	1222.99265	526.19707	390.06620	100.20000	2.49733	357.09990	887.42990	1.36512	2030.52499
1.470	-1.960	347.78490	1222.93622	526.17628	390.07790	100.20000	2.49725	357.11990	887.41990	1.36519	2030.49001
1.470	-.946	347.89280	1223.02753	526.22186	390.10520	100.20000	2.49751	357.23000	887.42990	1.36510	2030.49001
1.470	-.153	348.00120	1222.99158	526.21584	390.14450	100.20000	2.49753	357.33980	887.42990	1.36515	2030.45500
1.470	.969	348.03080	1223.11931	526.27023	390.08520	100.10000	2.49814	357.36990	887.42990	1.35803	2030.45500
1.470	2.006	347.76420	1223.28256	526.31537	389.98170	100.10000	2.49821	357.09990	887.41990	1.35781	2030.45500
1.470	3.013	348.02120	1223.05930	526.24554	390.08760	100.10000	2.49803	357.35990	887.40990	1.35810	2030.45500
1.470	4.015	347.96170	1223.22643	526.30890	390.05860	100.10000	2.49816	357.29980	887.40990	1.35442	2030.45500
GRADIENT		.01664	.03631	.01616	-.00746	-.01678	.00014	.01697	-.00237	-.00121	-.00987
RUN NO.		1695/ 0		RN/L =	2.50	GRADIENT INTERVAL =	- 5.00/ 5.00	ALPHA =	.000	PHI =	180.000
MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.494	-3.993	337.32470	1227.51004	526.97905	386.17090	100.30000	2.49633	346.50980	910.37990	1.39393	2030.24500
1.495	-2.965	337.26420	1229.60669	527.80427	386.11910	100.30000	2.49687	346.45000	910.35990	1.28134	2030.24500
1.495	-1.964	337.58720	1230.14734	528.05645	386.20340	100.30000	2.49766	346.77980	910.35990	1.26434	2030.24500
1.495	-.951	337.43070	1229.85181	527.92043	386.16280	100.30000	2.49727	346.61990	910.35990	1.27449	2030.24500
1.495	-.146	337.43070	1229.98920	527.97506	386.16480	100.30000	2.49724	346.61990	910.34990	1.26448	2030.21001
1.495	.974	337.59670	1230.36923	528.14599	386.19580	100.30000	2.49787	346.78980	910.33980	1.25757	2030.21001
1.495	2.008	337.50950	1230.14047	528.04387	386.19680	100.30000	2.49721	346.70000	910.32980	1.25129	2030.21001
1.495	3.014	337.54830	1230.31392	528.11765	386.19870	100.30000	2.49746	346.74000	910.29980	1.24787	2030.24500
1.495	4.021	337.44040	1230.34001	528.11505	386.16430	100.30000	2.49731	346.62990	910.30980	1.24460	2030.24500
GRADIENT		.02214	.23289	.09493	.00388	-.00000	.00009	.02272	-.00906	-.01237	-.00167

DATE 04 OCT 91

IA310 (AEDC 16TF-783) TABULATED DATA

IA310 (AEDC 16TF-783) REPEAT RUNS

PAGE 1050  
( VCM071 ) ( 04 OCT 91 )

## PARAMETRIC DATA

RUN NO.	1690/ 0	RN/L =	2.50	GRADIENT INTERVAL =	-5.00/ 5.00
P	PT	Q(PSF)	T(R)	TT(F)	RN/L

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.521	.999	327.00390	1237.19324	529.35882	382.30470	100.50000	2.49387	336.01980	911.15990	1.07879	2030.17500
1.520	-2.965	327.43240	1237.97012	529.72676	382.38280	100.50000	2.49565	336.46000	911.14990	1.07815	2030.17500
1.520	-1.963	327.15720	1238.12604	529.74387	382.20510	100.40000	2.49623	336.17990	911.13990	1.07798	2030.14000
1.521	- .950	327.22730	1237.75748	529.61228	382.26270	100.40000	2.49567	336.25000	911.13990	1.07831	2030.10500
1.520	- .145	327.48140	1238.33446	529.87461	382.32810	100.40000	2.49636	336.50980	911.03980	1.05333	2030.03500
1.521	.973	327.35450	1238.19067	529.79966	382.22900	100.30000	2.49658	336.37990	911.00000	1.05444	2030.00000
1.521	2.008	327.17800	1238.14677	529.75498	382.17190	100.30000	2.49632	336.20000	910.99000	1.05546	2029.96500
1.521	3.015	327.34400	1238.43347	529.89207	382.27510	100.40000	2.49632	336.36990	910.99000	1.05244	2029.96500
1.520	4.021	327.47090	1238.49782	529.93570	382.24150	100.30000	2.49723	336.50000	910.97000	1.05519	2029.92999
GRADIENT	.02914	.02914	.11771	.05003	-.01143	-.02336	.00028	.02995	-.02789	-.00396	-.03438

RUN NO.	1683/ 0	RN/L =	2.49	GRADIENT INTERVAL =	-5.00/ 5.00
P	PT	Q(PSF)	T(R)	TT(F)	RN/L

MACH	BETA	P	PT	Q(PSF)	T(R)	TT(F)	RN/L	PC	PREF	SH10+3	PATM
1.544	.994	317.34640	1241.51575	529.33672	378.78150	101.20000	2.49092	326.18990	912.08980	1.25951	2029.78999
1.544	-2.970	317.44340	1241.922996	529.51207	378.79220	101.20000	2.49148	326.28980	912.07980	1.24933	2029.78999
1.543	-1.963	317.58910	1242.07237	529.59330	378.82200	101.20000	2.49205	326.43990	912.08980	1.25570	2029.78999
1.544	-.955	317.53100	1242.04816	529.57395	378.81690	101.20000	2.49169	326.37990	912.08980	1.24599	2029.82500
1.544	.100	317.62840	1242.73157	529.85149	378.63550	100.90000	2.49385	326.48000	912.08980	1.21021	2030.00000
1.544	.984	317.60910	1242.67970	529.82830	378.63750	100.90000	2.49366	326.46000	912.07980	1.20711	2030.00000
1.544	2.015	317.50150	1242.63904	529.79231	378.59910	100.90000	2.49355	326.34990	912.08980	1.21029	2030.03500
1.544	3.013	317.67700	1242.74750	529.86716	378.57930	100.80000	2.49462	326.52980	912.07980	1.21335	2030.07001
1.543	4.013	317.67850	1242.35777	529.71980	378.60990	100.80000	2.49404	326.52980	912.05980	1.21690	2030.07001
GRADIENT	.03240	.12715	.05448	-.03257	-.06182	-.00045	.03320	-.00216	-.00683	.04387	