

NASA Technical Memorandum 101458

# Adaptive Feed Array Compensation System for Reflector Antenna Surface Distortion

(NASA-TM-101458) ADAPTIVE FEED ARRAY  
COMPENSATION SYSTEM FOR REFLECTOR ANTENNA  
SURFACE DISTORTION (NASA) 7 P CSCI 20N

N89-17756

G3/32 Unclass  
0188945

Roberto J. Acosta and A. Zaman  
*Lewis Research Center*  
*Cleveland, Ohio*

Prepared for the  
1989 IEEE AP-S International Symposium and  
URSI Radio Science Meeting  
San Jose, California, June 26-30, 1989

**NASA**

**ORIGINAL PAGE IS  
OF POOR QUALITY**

## **ADAPTIVE FEED ARRAY COMPENSATION SYSTEM FOR REFLECTOR ANTENNA SURFACE DISTORTION**

**Roberto J. Acosta and A. Zaman  
National Aeronautics and Space Administration  
Lewis Research Center  
Cleveland, Ohio 44135**

### **INTRODUCTION**

The feasibility of a closed loop adaptive feed array system for compensating reflector surface deformations has been investigated. The performance characteristics (gain, sidelobe level, pointing, etc.) of large communication antenna systems degrade as the reflector surface distorts mainly due to thermal effects from a varying solar flux. The compensating systems described in this report can be used to maintain the design performance characteristics independent of thermal effects on the reflector surface. The proposed compensating system employ the concept of conjugate field matching to adjust the feed array complex excitation coefficients.

### **GENERALIZED ADAPTIVE COMPENSATION SYSTEM**

The feasibility of feed array compensation for reflector surface distortion has been extensively investigated [Refs. 1-6]. Basically there are two methods for obtaining the feed array complex excitation coefficients; namely the indirect conjugate field matching (ICFM) [Refs. 1-4] and the direct conjugate field matching (DCFM) [Refs. 5 and 6]. Graphical description of these two methods are presented in figures 1 and 2, respectively. These algorithms assume that the distorted reflector surface shape is known either in terms of a functional description or at discrete points. Some of the methods suggested to obtain the surface shape includes optical, photogrammetric, microwave holography, near-field measurement or other metrological techniques. For example, the near-field measurement technique [Ref.7] calculates the reflector surface shape from a measured near-field phase data. Figure 3 depicts a block diagram of a generalized adaptive compensation system, consisting of a detection and a compensation algorithm. The combination of these two algorithms provides a closed loop, on line control of the radiation performance of the antenna system in the presence solar radiation.

### **CONJUGATE FEED ARRAY**

Detecting the shape of a distorted reflector may be a difficult task in the spacecraft environment. The concept of conjugate feed array (figure 4) can be employed to compensate for the degraded antenna performance without requiring surface point measurements. A block diagram representation of the concept is presented in figure 5. This compensating system can be described as follows; a pilot signal sent from the ground terminal is received by the spacecraft antenna and is detected by the conjugate feed array. The conjugate feed array acquires the amplitude and phase information at each element location, and their conjugate value serves as the transmitting compensating excitations. This is essentially the concept of conjugate field matching. If dipole sources are used as array elements the system can potentially compensate for pointing error and directivity loss. To control the sidelobe level (to a limited extend), the feed element pattern is designed to provide a correct taper of illumination on the reflector. To demonstrate this concept a simulated distorted reflector case is presented with several element patterns.

## RESULTS

A simulated sinusoidal distortion (peak distortion of  $0.25\lambda$ ) was superimposed into an offset parabolic reflector configuration (figure 6). A hexagonal feed array of 37 elements (spacing =  $1\lambda$ ) was used in the simulation. Based on this configuration, numerical studies were conducted with different feed element patterns, and the results are shown in figures 7a-d. The array element pattern provided a limited control on the sidelobe level. In general the required undistorted sidelobe level is known and the corresponding feed element pattern can be selected accordingly. The most important feature of this compensating system is that it does not require the reflector surface shape to be known. The pilot signal from the ground need not be active all the time, since it is only needed at times when the distortions have changed appreciably. Above results indicate that the conjugate feed array concept will provide a closed loop adaptive control for the radiation performance of the antenna system. An experimental system prototype is being developed and will be used to verify the concept.

## REFERENCES

1. Rudge, A.W.; and Davies, D.E.N.: Electronically Controllable Primary Feed for Profile-Error Compensation of Large Parabolic Reflector. IEE Proc., vol. 117, no. 2, Feb. 1970, pp. 351-358.
2. Rahmat-Samii, Y.: A Generalized Reflector/Array Surface Compensation Algorithm for Gain and Sidelobe Control. 1987 IEEE International Symposium Digest Antennas and Propagation, vol. 2, IEEE, 1987, pp. 760-763.
3. Rahmat-Samii, Y.: Spacecraft Antenna Surface-Compensation Techniques. MSAT-X Quarterly (Jet Propulsion Laboratory), no. 9, Jan. 1987, pp. 2-6.
4. Cherrette, A.R.; et al.: Compensation of Reflector Antenna Surface Distortion Using an Array Feed. NASA TM-100286, 1988.
5. Acosta, R.J., et al.: Case Study of Active Array Feed Compensation with Sidelobe Control for Reflector Surface Distortion. NASA TM-100287, 1988.
6. Acosta, R.J.: Active Feed Array Compensation for Reflector Antenna Surface Distortions. NASA TM-100826, 1988.
7. Cherrette, A.R.; Lee, S.W.; and Acosta, R.J.: Detection of Reflector Surface Error From Near-Field Data: Effect of Edge Diffracted Field. NASA TM-89920, 1988.




FIGURE 1. - ILLUSTRATION OF INDIRECT CONJUGATE FIELD MATCHING (ICFM) TECHNIQUE.




FIGURE 2. - ILLUSTRATION OF DIRECT CONJUGATE FIELD MATCHING (DCFM) TECHNIQUE.




FIGURE 3. - BLOCK DIAGRAM OF A GENERALIZED ADAPTIVE COMPENSATION SYSTEM.




FIGURE 4. - TYPICAL CONJUGATE ARRAY ELEMENT.




FIGURE 5. - ILLUSTRATION OF THE CONJUGATE ARRAY FEED COMPENSATION SYSTEM.




FIGURE 6. - REFLECTOR GEOMETRY.




FIGURE 7. - COMPENSATED ANTENNA PATTERN.



# Report Documentation Page

1. Report No. NASA TM-101458	2. Government Accession No.	3. Recipient's Catalog No.	
4. Title and Subtitle Adaptive Feed Array Compensation System for Reflector Antenna Surface Distortion		5. Report Date	
		6. Performing Organization Code	
7. Author(s) Roberto J. Acosta and A. Zaman		8. Performing Organization Report No. E-4568	
		10. Work Unit No. 650-60-20	
9. Performing Organization Name and Address National Aeronautics and Space Administration Lewis Research Center Cleveland, Ohio 44135-3191		11. Contract or Grant No.	
		13. Type of Report and Period Covered Technical Memorandum	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, D.C. 20546-0001		14. Sponsoring Agency Code	
		15. Supplementary Notes Prepared for the 1989 IEEE AP-S International Symposium and URSI Radio Science Meeting, San Jose, California, June 26-30, 1989.	
16. Abstract <p>The feasibility of a closed loop adaptive feed array system for compensating reflector surface deformations has been investigated. The performance characteristics (gain, sidelobe level, pointing, etc.) of large communication antenna systems degrade as the reflector surface distorts mainly due to thermal effects from a varying solar flux. The compensating systems described in this report can be used to maintain the design performance characteristics independent of thermal effects on the reflector surface. The proposed compensating system employ the concept of conjugate field matching to adjust the feed array complex excitation coefficients.</p>			
17. Key Words (Suggested by Author(s)) Antenna surface distortion Antenna surface compensation Far-field analysis		18. Distribution Statement Unclassified - Unlimited Subject Category 32	
19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No of pages 6	22. Price* A02