

VON KARMAN INSTITUTE FOR FLUID DYNAMICS

111 11 5
N89-16834

LECTURE SERIES 1988-03

TRANSONIC COMPRESSORS

FEBRUARY 1 - 5, 1988

THE DESIGN AND DEVELOPMENT OF TRANSONIC
MULTISTAGE COMPRESSORS

C.L. Ball, R.J. Steinke, F.A. Newman
NASA-Lewis Research Center, Ohio, USA

Presentation
von Karman Institute for Fluid Dynamics
1987-1988 Lecture Series
Lecture 3-Transonic Compressors
February 1-5, 1988

THE DESIGN AND DEVELOPMENT OF
TRANSONIC MULTISTAGE COMPRESSORS

By
C. L. Ball
R. J. Steinke
and
F. A. Newman
National Aeronautics and Space Administration
Lewis Research Center
Cleveland, OH 44135
USA

ABSTRACT

The feasibility of operating multistage axial-flow compressors at transonic flow conditions was first demonstrated at the NACA Lewis Flight Propulsion Laboratory (now the NASA Lewis Research Center) during the early to mid fifties. This pioneering research provided a major breakthrough in technology and has contributed significantly to the high performance of present day turbine engines. Following the initial demonstrations, numerous organizations within governments, universities and industries worldwide have contributed to further enhancing the performance of the transonic compressors through their own research. NASA has and continues to play a key role in the development of technology in this critical area.

This paper presents a historical perspective on the development of the transonic multistage compressor. Changing trends in design and performance parameters are noted. These changes are related to advancements in compressor aerodynamics, computational fluid mechanics and other enabling technologies. The parameters normally given to the designer and those that need to be established during the design process are identified. Criteria and procedures used in the selection of these parameters are presented and discussed. Included are discussion on the selection of tip speed, aerodynamic loading, flowpath geometry, incidence and deviation angles, blade/vane geometry, blade/vane solidity, stage reaction, aerodynamic blockage, inlet flow per unit annulus area, stage/overall velocity ratio, and aerodynamic losses. Trends in these parameters both spanwise and axially through the machine are highlighted. The effects of flow mixing and methods for accounting for the mixing in the design process are discussed.

Brief discussions on the present day understanding and modeling capability of unsteady flow phenomena are presented which includes rotating stall, surge flutter and forced response. The influence of these unsteady phenomena on design parameter selections are highlighted.

The impact of the new and more demanding requirements being imposed on the propulsion system to meet advanced aircraft mission needs are noted. Examples of modern day high speed multistage compressors are presented. A case history of the design and development of a NASA Lewis Research Center high tip speed, high pressure ratio core compressor inlet stage group is highlighted.

OUTLINE

First, a historical perspective on the development of the transonic multistage compressor is provided. The impact of various technologies are highlighted. Present day design procedures are discussed. The parameters normally given to the designer and those that need to be established during the design process are identified. Criteria and procedures used in the selection of these parameters are presented. Ranges in the values for these parameters found in modern day transonic compressors are given. The affect of flow mixing and methods for accounting for it in the design process are discussed. Mechanical, aeroelastic and other considerations which must be taken into account during the design process are highlighted. And last, examples of modern day transonic compressors are presented along with lessons learned during their development.

OUTLINE

HISTORICAL PERSPECTIVE
TECHNOLOGY IMPACT
COMPRESSOR DESIGN PROCEDURE
DESIGN PARAMETERS
FLOW MIXING
MECHANICAL/AEROELASTIC CONSIDERATIO9NS
OTHER CONSIDERATIONS
EXAMPLES OF MODERN DAY TRANSONIC COMPRESSORS

HISTORICAL PERSPECTIVE

HISTORICAL PERSPECTIVE

A detailed review of the early research leading to the development of the transonic compressor is given in references 1-3. These papers summarize the transonic compressor research at the NASA Lewis and Langley Laboratories prior to 1960. Extensive reference lists are given with each paper.

As noted by Lieblein and Johnson in (ref. 1), the advent of supersonic flight in the late 1940's required that the turbojet engine be made lighter and more compact. For the compressor, this meant units of smaller diameter and fewer number of stages. Aerodynamically, the requirement was translated into a need for higher weight flow per unit frontal area and higher stage pressure ratio.

Compressor design theories at the time were generally based on the use of symmetrical velocity diagrams (50% reaction) and thick-nose blade profiles of approximately 10% maximum thickness ratio. These design practices were developed primarily from consideration of isolated-airfoil and two-dimensional low-speed concepts. As a result, serious limitations were imposed on the attainable specific weight flow and stage pressure ratio.

First, the use of thick blade profiles required that relative inlet Mach numbers be limited to about 0.70 to 0.75 to avoid serious loss penalties or possible choking of the flow. Second, the use of pre-rotation to maintain the rotor relative inlet mach number within the limiting values or to establish the symmetrical velocity diagrams restricted the maximum values of tip speed and inlet velocity (and consequently specific weight flow).

It was clear from the early research directed towards higher Mach number operation, that in order to achieve satisfactory performance goals, new blade shapes and improved design procedures needed to be developed. Highlights of the major accomplishments achieved prior to 1960 towards meeting these goals are summarized in the first three references. Included in these accomplishments was the development of a new blade loading parameter known as the D-factor (ref. 4), the development of a shock loss model (ref. 5), the demonstration of the double circular arc (DCA) blade shape, and the establishment of a data base involving single stage and multistage experiments which reflected on the desire to increase the reaction (reduce swirl leaving the stationary blade rows) and increase the blade solidity for the transonic stages.



The following figures present early subsonic compressors for comparison to early and modern day transonic multistage compressors to reflect on the progress to date for increasing the overall pressure ratio and reducing the required number of stages.

FIRST TURBOJET USING AXIAL-FLOW COMPRESSOR

Shown here is the first axial-flow compressor used in a turbojet engine. It is a German engine. The compressor had eight stages. It was designed for subsonic flow in all blade rows. The design pressure ratio and tip speed are not known.

FIRST TURBOJET USING AXIAL-FLOW COMPRESSOR


GERMAN JUMO 004



EARLY AMERICAN AXIAL TYPE TURBOJET

Shown here is an early American turbojet with a ten stage subsonic axial-flow compressor. This compressor was designed to produce a pressure ratio of 4.4 at a tip speed of 335 m/sec (1099 ft/sec). At this speed inlet guide vanes were needed to impart a swirl in the direction of rotation to keep the relative velocity to the rotor subsonic. It was designed by Westinghouse.

EARLY AMERICAN AXIAL TYPE TURBOJET WESTINGHOUSE J34




ORIGINAL PARTS
OF POOR QUALITY

FIRST AMERICAN TURBOPROP

Shown here is the first American turboprop engine. It was designed and built by General Electric. The burner cans are wrapped around the compressor as can be seen in the next figure.


FIRST AMERICAN TURBOPROP GENERAL ELECTRIC TG-100



CROSS-SECTION OF GENERAL ELECTRIC TG-100 TURBOPROP

Shown here is a cross-section of the TG-100 turboprop engine. One can note that in the early engine, the compressor component component tended to dominate much of the engine volume and provided the impetus to reduce the compressor diameter and length. The next figure shows a photograph of the compressor and gives its design parameters.

CROSS-SECTION OF GENERAL ELECTRIC TG-100 TURBOPROP




ORIGINAL PAGE IS
OF POOR QUALITY

COMPRESSOR ROTOR FOR GENERAL ELECTRIC TG-100

The TG-100 Compressor had 14 stages and produced a pressure ratio of 5.1 at a tip speed of 285 m/sec (935 ft/sec). As reflected in the design tip speed all compressor blade rows operated subsonically.

COMPRESSOR ROTOR FOR GENERAL ELECTRIC TG-100



STAGES - 14
PRESSURE RATIO - 5.1:1
TIP SPEED - 285 m/sec (935 ft/sec)


NACA EIGHT-STAGE AXIAL-FLOW TRANSONIC COMPRESSOR

Shown here is the NACA eight-stage axial-flow transonic compressor. It was designed for a pressure ratio of 10.3 and an inlet tip speed of 356 m/sec (1168 ft/sec) (ref. 6). It was this compressor that first demonstrated the feasibility of operating multistage axial-flow compressors at transonic conditions. The work was conducted at the NACA Lewis Flight Propulsion Laboratory (now NASA Lewis Research Center) during the early to mid fifties. This pioneering research provided a major breakthrough in technology for multistage compressor design and performance, and has contributed significantly to the high performance of present day turbine engines.

Following the initial demonstration, numerous organizations within governments, universities and industries worldwide have contributed to further enhancing the performance of the transonic compressors through their own research. NASA has and continues to play a key role in the development of technology in this critical area.

Only the first two stages of the NACA eight stage compressor operated with transonic flow. The last six stages operated subsonically. This was achieved through employing high reaction (non-symmetrical velocity diagrams) in the front two stages and 50% reaction (symmetrical diagrams) in the rear six stages.

NACA EIGHT-STAGE AXIAL FLOW TRANSONIC COMPRESSOR




STAGES - 8
PRESSURE RATIO - 10.3:1
TIP SPEED - 356 m/sec (1168 ft/sec)

ORIGINAL PAGE IS
OF POOR QUALITY

NACA EIGHT-STAGE AXIAL-FLOW TRANSONIC COMPRESSOR
OVERALL PERFORMANCE MAP

This figure shows the overall performance achieved with the NACA eight-stage compressor. One can note that the demonstrated pressure ratio was shy of the design value of 10.3 and the efficiency was on the order of 80% at maximum pressure ratio. However, the part speed performance was excellent. The lower than design pressure ratio at design speed was attributed to too large of boundary layer blockage assumed in the design process for the rear stages causing the rear stages to stall prematurely. Extensive research was conducted on this compressor (ref.7-12). It was this extensive data base that resulted in numerous transonic compressor designs for aircraft applications.

NACA EIGHT-STAGE AXIAL FLOW TRANSONIC COMPRESSOR
OVERALL PERFORMANCE MAP




ORIGINAL PAGE IS
OF POOR QUALITY

NACA FIVE-STAGE AXIAL-FLOW TRANSONIC COMPRESSOR

Shown here is a photograph of the NACA five-stage axial-flow transonic compressor. It was designed for a pressure ratio of 5 and its design tip speed was 335 m/sec (1100 ft/sec) (ref. 13). This design employed high reaction stages throughout. It did not employ an inlet-guide-vane and all stators were designed to turn the flow back to the axial direction. The design of this machine followed shortly the design of the NACA eight stage compressor.

NACA FIVE-STAGE AXIAL FLOW TRANSONIC COMPRESSOR




STAGES - 5
PRESSURE RATIO - 5.0:1
TIP SPEED - 335 m/sec (1100 ft/sec)

NACA FIVE-STAGE AXIAL FLOW TRANSONIC COMPRESSOR OVERALL PERFORMANCE MAP

The performance of the NACA five-stage compressor is shown here. A peak pressure ratio of 5.0 was attained at design speed at an efficiency of approximately 0.81. Peak efficiency on the map was 0.87. The performance achieved, though lacking at design speed, did demonstrate the feasibility of achieving satisfactory performance with all rotor blades operating transonically. Like the NACA eight stage compressor, the part speed performance was excellent. The performance data obtained on this machine was reported in references 14-17.

NACA FIVE-STAGE AXIAL FLOW TRANSONIC COMPRESSOR OVERALL PERFORMANCE MAP




ORIGINAL SOURCE OF POOR QUALITY

NASA ENERGY EFFICIENCY ENGINE CONFIGURATION PRATT & WHITNEY

The Energy Efficient Engine (E³) program was initiated in the late 1970's and extended over a period of approximately five years. The objective was to demonstrate significant reductions in fuel consumption for advanced high bypass ratio turbofan engines. Two contracts were awarded by NASA, one to Pratt & Whitney and one to General Electric, to: (1) design, build and test the components separately and (2) to test an integrated core low spool (ICLS). Shown here is a cross-section of the Pratt & Whitney engine with the compressor overall design values. The high compressor for this engine was designed for ten stages to produce a pressure ratio of 14 at a tip speed of 379 m/sec (1243 ft/sec) (ref. 18).

NASA
C-19-2743

NASA ENERGY EFFICIENT ENGINE CONFIGURATION PRATT & WHITNEY




H. P. COMPRESSOR
STAGES - 10
PRESSURE RATIO - 14:1
TIP SPEED - 379 m/sec (1243 ft/sec)

NASA ENERGY EFFICIENT ENGINE CONFIGURATION
GENERAL ELECTRIC

Shown here is the cross-section of the General Electric engine. The high compressor for this engine was designed to achieve a pressure ratio of 23 in 10 stages at a design inlet tip speed of 456 m/sec (1495 ft/sec)(ref. 19). The Energy Efficient Engine compressors reflect modern day technology and a very significant advance over the first transonic compressors, in terms of overall pressure ratios, tip speeds, and in number of stages required to achieve a given pressure ratio.

NASA
C-79-2745

NASA ENERGY EFFICIENT ENGINE CONFIGURATION
GENERAL ELECTRIC



H. P. COMPRESSOR

STAGES - 10

PRESSURE RATIO - 23:1


TIP SPEED - 456 m/sec (1495 ft/sec)

ORIGINAL PAGE IS
OF POOR QUALITY

NASA RESEARCH COMPRESSOR

Shown here is a NASA research compressor. It represents a modern day inlet stage group. It is designed to produce a pressure ratio of 4.45 in three stages at an inlet tip speed of 427 m/sec (1400 ft/sec) (ref. 20). To put the technology of this machine in perspective to other multistage compressors it would produce a pressure ratio of 9.27 in five stages and a pressure ratio of about 20 in eight stages maintaining stage loading levels.

The performance of the Energy Efficient Engine compressors and the NASA Research Compressor will be discussed in the section titled "Examples of Modern Day Transonic Compressors". Also, details about the design and development of these machines are given in the latter section.



TECHNOLOGY IMPACT

TECHNOLOGY IMPACT

In each of the areas listed below, examples of the major impacts that have resulted in the present level of technology of transonic multistage compressors will be noted.

TECHNOLOGY IMPACT

- AERODYNAMIC
- COMPUTATIONAL FLUID MECHANICS
- INSTRUMENTATION AND CONTROLS
- STRUCTURAL MECHANICS
- MATERIALS
- MECHANICAL COMPONENTS

AERODYNAMICS

In the area of aerodynamics, advanced blade shapes is high on the list of items having a very significant impact on performance of modern day transonic compressors. The range of blade shapes presently being used are listed. The airfoil series type blade shapes are still used for blade rows operating with subsonic flows. The DCA blade shape is used for high subsonic to low supersonic Mach numbers. The MCA blade shape is used extensively at the higher supersonic relative Mach numbers. The polynomial shape (ref. 21) allows more flexibility than the MCA shape and in fact can duplicate the DCA and MCA shapes through proper selection of the polynomial coefficient. The polynomial shape can also be used to approximate the various airfoil series as well as the controlled diffusion (CD) shapes. The CD shape is being employed with a high degree of success for moderate to high subsonic blade elements (ref. 22-28). The words "controlled diffusion" were coined to reflect a class of blade shapes that employ the concept of shaping the blade behind the point of peak suction surface velocity such that the diffusion rate and associated suction surface boundary layer results in minimum loss for the airfoil section. The supercritical blade shape referred to in some of the references is considered a special class of the CD shape where, in addition to controlling the diffusion rate behind the location of peak suction surface velocity, the forward portion of the blade is shaped to permit supercritical operation (a shock free supersonic pocket along the suction surface) at the higher subsonic Mach numbers. The benefit of CD blading has come not only in lower losses but also improved range.

In addition to blade shapes, the extensive data base that has been established to guide the selection of the design parameters must also rate high on the impact scale. Without it, the level of technology for the transonic compressor would not be what it is today.

AERODYNAMIC

O BLADE SHAPES

- AIRFOIL SERIES
- DOUBLE CIRCULAR ARC (DCA)
- MULTIPLE CIRCULAR ARC (MCA)
- POLYNOMIAL (ARBITRARY)
- CONTROLLED DIFFUSION (CD)

O EMPIRICAL DATA BASE

COMPUTATIONAL FLUID MECHANICS

The present design system, centered around the axisymmetric through-flow design code, still remains highly empirical in nature. Extensions of the empirical data base which supports the axisymmetric through-flow design codes have contributed the most to the present state of technology of transonic multistage compressors. However, this is rapidly changing. The computational methods, at the present time primarily used in an analysis mode, are now impacting the selection of design parameters in the design process. Potential flow and Euler codes, now being used routinely as analysis tools, are making their impact on the level of technology being demonstrated in the most recently designed machines. The application of viscous codes have been somewhat limited. However, they are now being employed in the design of the controlled diffusion (CD) blading.

COMPUTATIONAL FLUID MECHANICS

- AXISYMMETRIC DESIGN CODE
- POTENTIAL FLOW ANALYSIS CODES
- EULER ANALYSIS CODES
- VISCOUS ANALYSIS CODES

DESIGNING FOR
POOR QUALITY

FANS AND COMPRESSORS CONTROLLED DIFFUSION BLADES


The controlled diffusion blade shape is shown here, along with the blade surface Mach number distribution. A supersonic shock free pocket (supercritical flow region) exists along the blade suction surface. The flow range of the CD blade shape is compared to the conventional blade shape in the lower right part of the figure. The design of the CD blade shape requires extensive use of the internal flow codes. The benefits of this shape are indicated in the lower left corner.

NASA
C-82-5489

Lewis Research Center


NASA

FANS AND COMPRESSORS
CONTROLLED-DIFFUSION BLADES




SUCTION SURFACE

PRESSURE SURFACE



FLOW RANGE



- DESIGNED UTILIZING INTERNAL FLOW CODES
- ROUGHED EDGES FOR RESISTANT BLADES
- SHOCK FREE LOW LOSS DESIGN
- IMPROVED FLOW RANGE

LOSS COEFFICIENT

INSTRUMENTATION AND CONTROLS

The non-intrusive laser anemometry instrumentation has had a very significant technological impact in that the flow fields of transonic machines have now been well documented (ref. 29-32). Improved models have been developed and computational methods have been verified. The design of higher Mach number blading is now being guided by the verified Euler codes.

Also, the digital electronic controls have permitted more precise control of variable geometry for maximum performance over the speed range.

INSTRUMENTATION AND CONTROLS

NONINTRUSIVE LASER ANEMOMETRY

HOLOGRAPHY


DIGITAL ELECTRONIC CONTROLS

ADVANCED METHODS FOR COMPRESSOR FLOW RESEARCH

Shown here is a laser system used at NASA Lewis along with a comparison between measured and calculated Mach number contours. The three dimensionality of the shock structure has been well documented (ref. 31). Even the unsteadiness has been assessed (ref. 32).

NASA
C-81-1385

ADVANCED METHODS FOR COMPRESSOR FLOW RESEARCH



STRUCTURAL MECHANICS

As the tip speeds have increased the need for more reliable structural analysis codes were needed. The NASA Structural Analysis Code (NASTRAN) is now used extensively to not only calculate untwist and blade natural frequencies, but also to calculate camber. The blade coordinates are being adjusted to account for the camber in the design process. Significant improvements in the aeroelastic analysis codes have also been made. However, adequate modeling of stall flutter and of forced responses remains inadequate.

STRUCTURAL MECHANICS

NASA STRUCTURAL ANALYSIS CODE (NASTRAN)
AEROELASTIC CODES

MATERIALS

Without the advancement in high temperature high strength steels and the high strength lightweight titanium alloys desired high blade speeds could not be achieved. However, the rim and blade stresses can still impose limits on the aerodynamic design. This is particularly true for highly supersonic aircraft where the incoming air is at elevated temperatures.

MATERIALS

HIGH TEMPERATURE - HIGH STRENGTH STEELS

TITANIUM ALLOYS

MECHANICAL COMPONENTS

Improvements in the technology of bearings and seals has also permitted going to the higher rotative speeds. Without these improvements transonic operation would be limited.

MECHANICAL COMPONENTS

BEARINGS


SEALS

COMPRESSOR DESIGN PROCEDURE

DESIGN/ANALYSIS CODE HIERARCHY

The hierarchy of design and analysis codes are shown here. Moving from right to left results in increased complexity and more computer power required. Moving from left to right results in increasing empiricism and more extensive data bases. The present systems in general have as their basis the axisymmetric through-flow equations. A model for closing the inviscid form of the average-passage equation system is given in reference 33 and would bring the compressor design system a step closer to a fully viscous design system.

DESIGN/ANALYSIS CODE HIERARCHY




COMPRESSOR DESIGN PROCEDURE

As noted in the discussion of the previous figure, present design procedures tend to remain centered around the axisymmetric through-flow design type codes to provide the initial geometry and performance estimates. These codes require empirical input to establish such parameters as minimum loss incidence angle, flow deviation angle, viscous and shock losses and thus efficiency, and flow blockage allowances to name a few. An example of an axisymmetric design code is given in reference 21. The output from the axisymmetric code is input into the analysis codes as indicated in the block diagram reflecting the overall design procedure. Iterations are made between the two types of codes until a satisfactory aerodynamic design is established. The analysis codes range from two dimensional potential flow (ref. 34 and 35) and Euler codes (ref. 36) to three dimensional viscous codes (ref. 37) as appropriate and available. With convergence on the aerodynamic design iteration, iterations with the structural analysis codes are pursued along with the aeroelastic codes. With an acceptable overall design, input is provided to blade coordinate and off-design analysis codes.

As the technology advances in computational fluid mechanics and computers, the design system will move from the highly empirical system to a first principle system. Recent years have shown significant advancements towards meeting this goal.

COMPRESSOR DESIGN PROCEDURE



DESIGN PARAMETERS

DESIGN PARAMETERS

Parameters normally given to the designer and those selected during the design process are listed below. Many factors influence the values selected for these parameters such as engine type, flow size, application/mission, and the inter dependency between the various parameters for achieving satisfactory performance. Therefore it is difficult to reflect on typical ranges for the design parameters of modern day transonic compressors. However, it is felt some generalized comments may be helpful for some of the parameters, but caution is given in how they might be used in executing a design.

Overall pressure ratios in a single spool range from 14 to more than 20. Tip speeds range up to 457 m/sec (1500 ft/sec). The axial velocity is normally decreased somewhat through the machine to meet the low Mach number required at the burner inlet. Inlet hub/tip ratios go as low as .5. The flowpath is typically between a constant mean diameter and a constant tip diameter. The various blade/vane parameters are listed in the next figure.

DESIGN PARAMETERS

- GIVEN
 - WEIGHT FLOW
 - PRESSURE RATIO
 - ROTATIVE SPEED

- SELECTED DURING DESIGN PROCESS
 - TIP SPEED
 - WEIGHT FLOW PER UNIT ANNULUS AREA
 - VELOCITY RATIO
 - AERODYNAMIC LOADING (NUMBER OF STAGES)
 - INLET HUB/TIP RATIO
 - FLOWPATH GEOMETRY
 - BLADE/VANE GEOMETRY

BLADE/VANE GEOMETRY

Listed here are parameters which are directly related to the blade/vane geometry along with those parameters which influence the blade/vane geometry. Again, caution is given on the use of the generalized comments on the typical ranges for these parameters.

The blade/vane shapes used range from the airfoil series designated shapes to DCA for low transonic conditions and to MCA or tailored airfoils for blade elements operating above 1.2 relative inlet Mach numbers. In the highly transonic front stages the rotor tip solidity ranges from 1.2 to 1.5 and is reduced to about 1.0 in the subsonic rear stages. Aspect ratio for the rotors range from 2 to less than one in the rear stages. Stage reaction runs from moderate to high. Flow blockages allowances range from on the order of 4% in the front to 10 to 15% in the rear stages.

More insight into typical values for the design parameters can be gained by studying the example compressors presented at the end of this lecture.

Reference 38, even though it was initially published during 1956 and revised in 1965, remains an excellent reference today on the design of axial-flow compressors. The empirical data base has changed with technological advancement, but the basic design methods and considerations remain very much the same.

BLADE/VANE GEOMETRY

- AIRFOIL SHAPE
- SOLIDITY
- ASPECT RATIO (CHORD)
- THICKNESS DISTRIBUTION
- STAGE REACTION
- FLOW BLOCKAGE
- AERODYNAMIC LOSSES
- INCIDENCE ANGLE
- DEVIATION ANGLE



EFFECT OF ASPECT RATIO ON PERFORMANCE OF HIGH TIP SPEED CORE INLET STAGE

This figure reflects on the benefit of low aspect ratio type blading for achieving improved flow range in highly loaded high tip speed transonic compressor stages (ref. 39).

ORIGINAL FIGURES
OF POOR QUALITY

NASA
CR-81-12601

EFFECT OF ASPECT RATIO ON PERFORMANCE OF HIGH TIP SPEED CORE INLET STAGE



CD-81-12601


LARGE LOW SPEED COMPRESSOR RESEARCH ENDWALL FLOW FUNDAMENTAL EXPERIMENT

This figure shows the benefits that can be realized by shaping the blade in the endwall region to accommodate the endwall boundary layer. (ref. 40).

ORIGINAL PAGE IS
OF POOR QUALITY

NASA
CR-81-0193

LARGE LOW SPEED COMPRESSOR RESEARCH ENDWALL FLOW FUNDAMENTAL EXPERIMENTS




- PROVIDED UNDERSTANDING OF ENDWALL FLOWS
- IMPROVED BLADE SHAPE IN ENDWALL REGION TO ACCOMMODATE BOUNDARY LAYER
- RESULTED IN IMPROVED FLOW RANGE AND EFFICIENCY

CD 81-1259C

SELECTION PROCESS

As part of the selection process trade studies are often made to maximize the benefits of a new design in terms of some figure of merit such as return on investment, ROI or direct operating cost, DOC. The block diagram shown here reflects on this process. Examples of these types of studies are given in reference 41 and 42.

SELECTION PROCESS




FLOW MIXING

FLOW MIXING



The success of multistage compressor designs depends, in part on suitable modeling of the effects of radial mixing of the flow through the machine which tends to temper the gradient in flow parameters near the endwalls. Numerous reports and papers have treated various aspects of this phenomenon over the years. References 43-45 specifically address the mixing issue. NASA conducted a study in a two-stage fan where the endwall boundary layers were measured along with the radial distributions of other flow parameters (ref. 46). A photograph of the fan is shown below. The data obtained is presented in the next six figures. The first figure presents the overall performance of the fan and the remaining five figures show the radial distribution in flow parameters near the outer wall. In examining the data one can see that the gradients in flow parameters exiting the rotors are tempered on passing through the stators. This is an indication of the magnitude of the mixing that is taking place in this machine. A feature built into NASA axisymmetric through-flow design code (ref. 21) is the ability to smooth the temperature gradient coming out of the rotor on passing through the stator. Tempering the actual endwall loss gradients used in the design process is also employed.

TWO-STAGE FAN WITH LOW ASPECT RATIO HUBBLE-AGE ROTOR




OVERALL PERFORMANCE

TWO-STAGE, LOW-ASPECT-RATIO FAN




RADIAL DISTRIBUTIONS AT STATION 1

FIRST-STAGE ROTOR INLET




RADIAL DISTRIBUTIONS AT STATION 2

FIRST-STAGE ROTOR EXIT




RADIAL DISTRIBUTIONS AT STATION 3

FIRST-STAGE STATOR EXIT




RADIAL DISTRIBUTIONS AT STATION 4

SECOND-STAGE ROTOR EXIT



RADIAL DISTRIBUTIONS AT STATION 5

- SECOND-STAGE STATOR EXIT -



**MECHANICAL/AEROELASTIC
CONSIDERATIONS**

MECHANICAL/AEROELASTIC CONSIDERATIONS


A number of mechanical and aeroelastic consideration must be addressed in the design process. These are listed below. Blade untwist has been taken into account for many years by resetting blade elements so they untwist to the design setting at design speed. Only recently has uncambering been considered in the design process. The increased blade speeds coupled with low aspect ratio blades makes this an important consideration. The structural analysis codes like NASTRAN are employed in this process. Flutter is not a common problem encountered in advance relatively low aspect ratio blading, however, it must be considered in the design process to assure avoidance. Forced response can be a problem. Exit rim stresses may limit the exit diameter of the machine. Variable geometry must be incorporated in high pressure ratio machines to improve part speed performance. The trend is to use shrouded stators in at least the front variable rows. Methods for maintain tight clearances are of particular importance to achieving good efficiencies, particularly for the high hub/tip ratio rear stages.

MECHANICAL/AEROELASTIC CONSIDERATIONS

- BLADE UNTWIST/UNCAMBER
- FLUTTER
- FORCED RESPONCE
- RIM STRESS
- VARIABLE GEOMETRY
- CANTILEVERED/SHROUDED STATORS
- TIP CLEARANCE CONTROL

REGIONS OF COMPRESSOR FLUTTER

The performance map shown here reflects regions where flutter may be encountered. Subsonic/transonic flutter is the type most encountered in modern multistage designs and is the least understood.




FAN AND COMPRESSOR RESEARCH TRANSONIC FLUTTER

Shown here is a NASA Lewis research facility devoted to gaining an understanding of subsonic/transonic stall flutter.

NASA
CR-81-5324

FAN AND COMPRESSOR RESEARCH. TRANSONIC FLUTTER




FLUTTER CASCADE FACILITY




NINE-AIRFOIL TEST SECTION



MACH 0.8 STEADY FLOW



AIRFOIL DISPLACEMENT




FLOW OVER AIR AIRFOILS
OSCILLATING AT 400 HZ

CD-81-12599

PRIMARY ELEMENTS OF FORCED RESPONSE

This figure shows the primary elements of forced response. The forced response problem is triggered by nonaxisymmetric flows. The following figure list sources of these flows.

PRIMARY ELEMENTS OF FORCED VIBRATION



SOURCES OF NON-AXISYMMETRIC FLOWS

Of the various sources of non-axisymmetric flows listed the ones due to struts and blade/vane wakes are the most common ones considered in the design process.


SOURCES OF NON - AXISYMMETRIC FLOWS

- INLET DISTORTED FLOW FIELDS
 - PRESSURE
 - TEMPERATURE
- WAKE GENERATION AND TRANSPORT
 - STRUTS
 - BLADE/VANE WAKES
 - TIP VORTICES
 - ENDWALL BOUNDARY LAYERS
 - INSTRUMENTATION PROBES
- POTENTIAL FLOW FIELD DISTURBANCES
- ROTATING STALL CELLS
- SURGE
- BLEED PORTS

CAMPBELL DIAGRAM SHOWING FORCED EXCITATION POTENTIAL

This figure shows the commonly used diagram for identifying the potential for forced response. The lower order excitations are normally due to slots and avoidance of crossing one and two order excitations is common practice. The higher order excitations are due normally to rotor/stator interactions. However, in reality excitation can be noted throughout the map. This can be seen from the next figure.


CAMPBELL DIAGRAM SHOWING FORCED EXCITATION POTENTIALS



NASA THREE-STAGE RESEARCH COMPRESSOR

This data was recently taken by Fred Newman on the NASA three-stage research compressor shown earlier. The data indicated by the symbols reflect the range of excitations encountered. The data is now being analyzed to determine the aerodynamic damping involved in the various modes and to develop models and codes for predicting these modes during the design process. Present modeling is inadequate to establish the magnitude of these forced responses.

NASA THREE-STAGE RESEARCH COMPRESSOR THIRD STAGE ROTOR



OTHER CONSIDERATIONS

OTHER CONSIDERATIONS

Other considerations which the designer must address are listed below. Of all the items listed, the one which has received most attention recently is stall recoverability. Some of the basic modeling treating this area are presented in references 47-55. Structural loads encountered due to surge is treated in references 56 and 57.

OTHER CONSIDERATIONS

STALL MARGIN
INLET DISTORTION TOLERANCE
LOAD LINE
STALL RECOVERABILITY

STALL RECOVERY ISSUES/CONSIDERATIONS

Significant progress has been made in the modeling of this phenomena. However, additional work is needed to further address some of the issues listed below.

STALL RECOVERY ISSUES/CONSIDERATIONS

INLET/EXIT VOLUME/GEOMETRY
COMPRESSOR/BURNER INTERACTIONS
LUMPED VS STAGE-BY-STAGE COMPRESSOR MODEL
REVERSED FLOW CHARACTERISTICS
COMPRESSOR INERTANCE
HYSTERESIS
TRIGGERING MECHANISMS - INLET DISTORTIONS
FAN/LOW COMPRESSOR VS HIGH COMPRESSOR
SINGLE CELL VS MULTIPLE CELL/PART SPAN VS FULL SPAN
TURBOFAN VS TURBOJET VS TURBOSHAFT
SMALL ENGINES - AXIAL/CENT AND CENT/CENT


**EXAMPLES OF MODERN DAY
TRANSONIC COMPRESSORS**

**NASA ENERGY EFFICIENT ENGINE
CORE COMPRESSORS**

NASA/P&W ENERGY EFFICIENT ENGINE CORE COMPRESSOR

Shown here is a photograph of the P&W core compressor along with the overall design values given earlier.

NASA/P&W ENERGY EFFICIENT ENGINE CORE COMPRESSOR



STAGES - 10
PRESSURE RATIO - 14:1
TIP SPEED - 379 m/sec (1243 ft/sec)


NASA/P&W ENERGY EFFICIENT ENGINE CORE COMPRESSOR

Shown here is a cross-section of the P&W compressor. The compressor achieved its design pressure and an efficiency of 85.5% at design point conditions (ref. 18). This is considered excellent performance.

ORIGINAL PLANNED
OF POOR QUALITY

NASA/P&W ENERGY EFFICIENT ENGINE CORE COMPRESSOR

CROSS-SECTION




ADIABATIC EFFICIENCY OF 85.5%
DEMONSTRATED AT DESIGN POINT
CONDITIONS

NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR

Shown here is a photograph of the GE core compressor along with its design goals shown earlier.

ORIGINAL DESIGN
OF POWER PLANT

NASA/GE ENERGY EFFICIENT ENGINE
CORE COMPRESSOR




STAGES - 10
PRESSURE RATIO - 23:1
TIP SPEED - 456 m/sec (1495 ft/sec)

NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR CROSS-SECTION

Shown here is a cross-section of the GE core compressor. The next several figures reflect on various design features of this compressor. Detailed discussions of the design is given in reference 58. One can see the flow path geometry is between a constant mean diameter and a constant tip. Shrouded stators are employed in all stages. Active clearance control is incorporated within the casing over the rear stages. Also note that the compressor incorporates a variable IGV. It serves two purposes, one to maximize performance at off design conditions and two, to impart a swirl to reduce the rotor tip Mach number at the high design tip speed. The swirl imparted is not of the magnitude to reduce the reaction to 50% in the front stage.

NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR

CROSS--SECTION




NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR ASPECT RATIO

Shown here is the aspect ratio of the rotor and stator blading. Note the trends from front to rear. The aspect ratio of the rear stages is reduced, in part, to maintain acceptable blade and vane cords. Also, note the higher aspect ratio in the front stage stators. Stator aspect ratio can be higher in these stages compared to the rotor and maintain good efficiency with acceptable operating range at the highly transonic flow condition.

NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR

ASPECT RATIO




NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR
PITCH-LINE SOLIDITY

Shown here is the pitch-line solidities for the rotors and stators. Note the higher solidity for the front stage rotors as compared to the rear stages. The higher solidities are required on the front rotors because of the highly transonic flow conditions. The stator solidity is more or less constant except for the last stator where the solidity was increased significantly to reduce loading in this vane row.

NASA/GE ENERGY EFFICIENT ENGINE
CORE COMPRESSOR

PITCH-LINE SOLIDITY




NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR
PITCH-LINE MERIDIONAL MACH NUMBER

Shown here is the pitch-line meridional Mach number. Note the decrease from approximately 0.6 at the inlet to approximately 0.28 at the OGV exit. The high Mach number at the inlet reduces frontal area and enhances transonic operation. The lower Mach number at the exit reduces the amount of diffusion that has to take place between the compressor exit and the combustor inlet.

ORIGINAL DRAWING IS
OF POOR QUALITY

NASA/GE ENERGY EFFICIENT ENGINE
CORE COMPRESSOR

PITCH-LINE MERIDIONAL MACH NUMBER




NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR STATOR EXIT SWIRL ANGLE

Shown here is the stator exit swirl angle for the tip, pitch and hub sections. Note the high swirl leaving the tip section of the IGV and the low value at the hub. This reduced the rotor tip Mach number and limits the stator one inlet hub Mach number to approximated .85, considered a practical upper limit for achieving good stator performance. In general, the swirl is increased in the front stages with the limiting stator hub Mach number determining the rate of increase. The high swirl in the endwall regions compared to pitch values for the middle stages is incorporated due to considerations of the endwall boundary layer. Note a OGV is used to remove the remaining swirl leaving the last stator.

ORIGINAL PAGE IS
OF POOR QUALITY

NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR

STATOR EXIT SWIRL ANGLE



NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR CAFD FLOWPATH

Shown here is the flowpath from the axisymmetric through-flow design code (CAFD). Note the calculation station placed within the first four rotor blades. This was done to help in establishing the blade shape for these high Mach number blade rows. The modeling of the inlet and exit is also shown. This is done to assure the flow parameters entering and leaving the compressor are properly defined.

ORIGINAL IMAGE IS
OF POOR QUALITY

NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR

CAFD FLOWPATH




NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR
 PITCH-LINE DIFFUSION FACTOR

Shown here is the pitch-line D-factor. Note the increase in stator loading in the rear stages. This is due in part to the removal of a portion of the total swirl existing at the exit of stator five as the flow passes through stators six to nine. This is required to keep the swirl that needs to be removed on the tenth stator and OGV within practical limits. The lower diffusion factors in stator 6 and 7 is due in part to higher solidities in those stators. This resulted from consideration of compressor bleed requirements.

NASA/GE ENERGY EFFICIENT ENGINE
 CORE COMPRESSOR

PITCH-LINE DIFFUSION FACTOR




NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR
RADIAL DISTRIBUTION OF DIFFUSION FACTOR

Shown here is the radial distribution of diffusion factor for rotor 5 and stator 5. Note the increases in the endwall regions. This was required to obtain the desired radial pressure gradients.

NASA/GE ENERGY EFFICIENT ENGINE
CORE COMPRESSOR

RADIAL DISTRIBUTION OF DIFFUSION FACTOR




NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR HUB INLET MACH NUMBER

Note the tip Mach number for the first rotor. This Mach number would be higher if inlet swirl was not employed. Note the hub Mach number for stator one of approximately .85, considered the practical limit. The Mach number decreases through the machine due in part to increasing temperature and somewhat to decreasing axial velocity.

NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR

HUB INLET MACH NUMBER




NASA/GE ENERGY EFFICIENT ENGINE
CORE COMPRESSOR

STATOR SCHEDULE

Shown here is the schedule for the IGV and stators. Note the high degree of reset required at the part speed condition particularly in the IGV and stator one.

NASA/GE ENERGY EFFICIENT ENGINE
CORE COMPRESSOR

STATOR SCHEDULE




NASA/GE ENERGY EFFICIENT ENGINE CORE COMPRESSOR
OVERALL PERFORMANCE MAP

Shown here is the overall performance of the GE compressor (ref. 58). Design weight flow and pressure ratio were exceeded at design speed with a adiabatic efficiency of approximately 83%. This is considered excellent for such a high overall pressure ratio. Part speed efficiencies approach 85%. The program was a complete success and sets the standard for high pressure ratio cores.

NASA/GE ENERGY EFFICIENT ENGINE
CORE COMPRESSOR

OVERALL PERFORMANCE MAP



**NASA FIVE – STAGE RESEARCH
COMPRESSOR**

NASA FIVE-STAGE RESEARCH COMPRESSOR

In the late sixties/early seventies, NASA embarked on a program to further enhance the performance of transonic multistage compressors from that demonstrated in the NACA eight-stage and NACA five-stage compressors. Our first design was a seven-stage compressor having an overall pressure ratio of 9.27 and an inlet tip speed of 1200 ft./sec. A mechanical failure occurred early in the testing of this design. The decision was made to not rebuild which would have required complete replacement of the blades and vanes but to concentrate on a second more aggressive design. The second design was a five-stage compressor having the same overall pressure ratio of the seven-stage (9.27) but with an inlet tip speed of 1400 ft./sec. To put this compressor in perspective technology wise, the NACA five-stage had a design pressure ratio of 5.0 and an inlet tip speed of 1100 ft./sec. The NASA five-stage compressor was a very aggressive design for its time period and remains so today. A low aspect ratio version of the original design has demonstrated excellent performance (ref. 20). Many lessons were learned to get to this level of performance. The following figures tell the story.

NASA FIVE-STAGE RESEARCH COMPRESSOR
ORIGINAL DESIGN


Shown here is the flowpath and some of the design parameters for the original NASA five-stage design. Note the high overall design efficiency. The design efficiencies for the rear stages were particularly high. The efficiencies were based on a very limited amount of data considering the aerodynamic loading levels and blade/vane aspect ratios. However, the excellent part speed performance of the NACA five-stage and even more so the eight-stage compressor gave encouragement in being able to achieve this level of performance. The lower performance of these machines at their design speed was attributed much to stage matching problems. There was also a philosophy at the time to achieve good efficiency one must design optimistically. In retrospect, the design was too aggressive considering the data base that existed for selecting the design parameters consistent with the blade loading and highly transonic conditions. The direction at the time was to increase stage pressure ratio through increased aerodynamic blade/vane loading and blade speed, and at the same time increase the blade and vane aspect ratios to further reduce overall length. This turned out to be an unacceptable design philosophy for achieving good overall efficiencies and flow range. One might note the relatively low aspect ratios of the NACA eight and five-stage machines from the photographs shown earlier.

An IGV was incorporated into the design but did not impart a swirl at design setting to reduce the relative flow mach number entering the first rotor, and all stators turned the flow back to the axial direction, thus a high stage reaction design throughout like the NACA five-stage.

NASA FIVE - STAGE RESEARCH COMPRESSOR

ORIGINAL DESIGN

STAGE					
PRESSURE RATIO	1.60	1.73	1.67	1.51	1.32
EFFICIENCY	.86	.89	.90	.90	.92



OVERALL
PRESSURE RATIO 9.27
EFFICIENCY .87
WEIGHT FLOW 65.5 lb/sec

NASA FIVE-STAGE RESEARCH COMPRESSOR ORIGINAL DESIGN

The aerodynamic loading (stage pressure ratio) distribution was chosen purposely to unload the inlet and outlet stages in an attempt to enhance off-design operation. The idea was that the middle stages could sustain the higher loadings because they tend to remain near their design point at part speed (off-design) operation. The blade/vane aspect ratios chosen were considerably higher than those of the NACA eight and five-stage machines as noted earlier. Because of the high aspect ratio of the first rotor, a damper (part span shroud) was used to eliminate potential aeroelastic problems. Little data base existed for stages incorporating dampers. A blockage allowance of two percent at the inlet of the compressor and five percent at the exit was assumed in the design, and like that measured in the NACA five-stage. The NACA eight-stage incorporated a 20 percent blockage at the exit. A large overall axial velocity decrease of 0.7 was taken across the machine (nearly linear distribution) to reduce the amount of velocity diffusion between the compressor exit and combustor inlet. This further increased aerodynamic loading for a given overall pressure ratio. The aerodynamic loadings were much higher than for the NACA five-stage.

NASA FIVE - STAGE RESEARCH COMPRESSOR

ORIGINAL

ROTOR					
TIP RELATIVE MACH NO	1.56	1.23	1.09	1.00	0.93
TIP DIFFUSION FACTOR	.42	.52	.55	.51	.38
ASPECT RATIO	3.08	2.11	1.66	1.64	1.68
STATOR					
HUB MACH NO	0.69	0.66	0.59	0.50	0.39
HUB DIFFUSION FACTOR	.45	.62	.68	.66	.50
ASPECT RATIO	2.70	2.04	2.03	2.30	2.27

NASA FIVE-STAGE RESEARCH COMPRESSOR
ORIGINAL DESIGN


PHOTOGRAPH

Shown here is a photograph of the original NASA five-stage research compressor with one half of the casing removed. One can note the relatively high blade/vane aspect ratio and the damper incorporated into the first rotor design.

ORIGINAL PAGE IS
OF POOR QUALITY

NASA FIVE-STAGE RESEARCH COMPRESSOR
OFFICIAL

FIVE-STAGE HARDWARE




NASA FIVE-STAGE RESEARCH COMPRESSOR ORIGINAL DESIGN

FIVE-STAGE PERFORMANCE

Shown here is the overall performance obtained at design speed for the NASA five-stage compressor as originally designed. As can be seen, a pressure ratio of only five was demonstrated and the flow was well below design. The data indicated that the front stages remained in stall and the back stages in choked at the design speed. The use of the variable IGV and stators along with interstage bleed at the exit of rotors two, three and four was not sufficient to bring the front stage out of stall and the back out of choke. Insufficient flow range at all speeds made it difficult to characterize the individual stages. The decision was made to remove the back two stages and try to obtain more complete data on the front three.

NASA FIVE-STAGE RESEARCH COMPRESSOR ORIGINAL




NASA FIVE-STAGE RESEARCH COMPRESSOR
ORIGINAL DESIGN

THREE-STAGE PERFORMANCE

Shown here is the performance obtained for the front three stages of the original NASA five-stage compressor. Even though more flow range was obtained than for the full five stages, the performance remained well below design. The design pressure ratio for the front three stages was 4.6. The decision was then made to test the front stage alone (ref. 59).

NASA FIVE-STAGE RESEARCH COMPRESSOR
ORIGINAL




NASA FIVE-STAGE RESEARCH COMPRESSOR
ORIGINAL DESIGN

FIRST-STAGE PERFORMANCE

Shown here is the performance of the first stage of the original NASA five-stage compressor. Data is shown for a solid casing (circles) and with casing treatment (triangles). Significant improvements in range and efficiency were obtained with casing treatment. The stage was tested over a range of IGV and stator setting angles to include establishing its install characteristics for off-design stage matching studies (ref. 59). The next step was to establish the second and third stage performance.

NASA FIVE-STAGE RESEARCH COMPRESSOR
ORIGINAL




NASA FIVE-STAGE RESEARCH COMPRESSOR
ORIGINAL DESIGN

SECOND AND THIRD STAGE PERFORMANCE

Shown here is the performance obtained from the second and third stage of the original NASA five-stage compressor. Both pressure ratio and efficiency remained well below design.

NASA FIVE - STAGE RESEARCH COMPRESSOR
ORIGINAL

SECOND AND THIRD STAGE PERFORMANCE



NASA FIVE-STAGE RESEARCH COMPRESSOR
ORIGINAL DESIGN

In examining all of the data obtained on the original NASA five-stage design along with the data that had been obtained from single-stage studies, it was concluded that the original five-stage design was deficient in several respects. First, the aspect ratio of the blading tended to be too high for the aerodynamic loading. This was aggravated by the unloading of the front and rear stages which resulted in very highly loaded middle stages. New incidence angle, deviation angle and loss data obtained from the single stage program indicated a strong need for adjustments in these parameters. The blockage allowances for the rear stages were considered to be too low. The velocity decrease through the machine further aggravated the blade loading problem. With these and other factors taken into consideration, the decision was made to accept the performance of the first stage with casing treatment and the slightly lower flow associated with its peak efficiency point, and to redesign the second through the fifth stage to include changing the flowpath. Blade and vane chords were maintained. This was done to permit resetting and recambering the existing blading by the coining process. This was a compromised position since the blade/vane aspect ratio was maintained at the relative high level. However, to ease the loading problem, a new loading distribution was incorporated and the axial velocity was not reduced through the compressor. New incidence and deviation angles were incorporated into the modified design. The overall pressure ratio was reduced to compensate for the lower first stage pressure ratio. The overall efficiency was reduced through increased losses and flow blockage was increased.


NASA FIVE-STAGE RESEARCH COMPRESSOR
MODIFIED DESIGN

Shown here is the flowpath for the modified design along with overall and stage design parameters. One can note the adjustments in the outer wall flowpath. More contraction was taken across the rear rotors than for the stators to help in unloading the rotors. The demonstrated pressure ratio of the front stage was accepted as noted earlier, and the stage pressure distribution was changed in the other stages. Stage efficiencies and thus overall efficiency was reduced.

NASA FIVE-STAGE RESEARCH COMPRESSOR

MODIFIED

STAGE					
PRESSURE RATIO	1.52	1.64	1.60	1.51	1.43
EFFICIENCY	.85	.84	.85	.86	.87



OVERALL	
PRESSURE RATIO	8.60
EFFICIENCY	.82
WEIGHT FLOW	64.2 lb/sec

NASA FIVE-STAGE RESEARCH COMPRESSOR
MODIFIED DESIGN

Shown here are more details on the modified NASA five-stage compressor design. One can note the changes in loading in terms of \bar{D} -factor compared to the original design.

NASA FIVE - STAGE RESEARCH COMPRESSOR

MODIFIED

ROTOR					
TIP RELATIVE MACH NO	1.42	1.27	1.14	1.05	0.99
TIP DIFFUSION FACTOR	.38	.47	.50	.48	.46
ASPECT RATIO	3.61	1.93	1.44	1.33	1.25
STATOR					
HUB MACH NO	0.68	0.69	0.66	0.61	0.58
HUB DIFFUSION FACTOR	.35	.47	.47	.44	.41
ASPECT RATIO	2.54	1.82	1.71	1.80	1.62


ORIGINAL PAGE IS
OF POOR QUALITY

NASA FIVE-STAGE RESEARCH COMPRESSOR
MODIFIED DESIGN

Shown here is a photograph of the modified NASA Five-Stage Research Compressor with one half of the casing removed. One can note the inserts in the outer wall (casing) used to modify the flowpath geometry.

NASA FIVE-STAGE RESEARCH COMPRESSOR
MODIFIED

THREE-STAGE HARDWARE




NASA FIVE-STAGE RESEARCH COMPRESSOR MODIFIED DESIGN

THREE-STAGE PERFORMANCE

Shown here is the performance obtained on the front three stages of the modified NASA five-stage compressor. As can be seen, the design pressure ratio and weight flow was obtained at design speed. However, the overall efficiency was lower than design. This, in part, was attributed to the limits imposed by the recoining process, particularly near the blade/vane base regions. Also, there was evidence from other programs that the extended spacing between the blade rows for survey instrumentation was contributing to the lower efficiencies. In addition, the relatively high blade and vane aspect ratios even at the somewhat lower aerodynamic loadings of the modified design were likely contributing to the low efficiency and limited flow range.

With the performance of the first three stages of the modified five-stage compressor in hand along with even more single stage data available, a completely new design was pursued. Its design and performance is presented in the next several figures.

NASA FIVE-STAGE RESEARCH COMPRESSOR MODIFIED




**NASA FIVE-STAGE RESEARCH COMPRESSOR
LOW ASPECT RATIO DESIGN**

Shown here is the flowpath for the low aspect ratio NASA Five-Stage Compressor along with overall and stage design values. Note the contraction across each rotor and little contraction across the stators. This was done to keep the velocity ratio up across the rotors. Losses were assumed on the high side in favor of stage matching and performance at part speed.

NASA FIVE - STAGE RESEARCH COMPRESSOR

LOW ASPECT RATIO

STAGE					
PRESSURE RATIO	1.74	1.65	1.58	1.48	1.40
EFFICIENCY	.82	.85	.86	.87	.88



OVERALL

PRESSURE RATIO	9.27
EFFICIENCY	.80
WEIGHT FLOW	65.5 lb/sec

NASA FIVE-STAGE RESEARCH COMPRESSOR
LOW ASPECT RATIO DESIGN

Shown here are additional rotor and stator design parameters. Note the lower blade/vane aspect ratios.

NASA FIVE - STAGE RESEARCH COMPRESSOR

LOW ASPECT RATIO



ROTOR					
TIP RELATIVE MACH NO	1.41	1.22	1.07	0.99	0.93
TIP DIFFUSION FACTOR	.47	.52	.54	.53	.52
ASPECT RATIO	1.45	1.17	1.04	1.01	1.02
STATOR					
HUB MACH NO	0.84	0.72	0.66	0.59	0.54
HUB DIFFUSION FACTOR	.56	.54	.54	.53	.54
ASPECT RATIO	1.53	1.43	1.19	1.15	1.11

NASA FIVE-STAGE RESEARCH COMPRESSOR LOW ASPECT RATIO DESIGN

Shown here are the blockages and energy addition assumed for the low aspect ratio design. Note the blockage was increased from approximately four percent at the inlet to approximately 14 percent at the exit. The energy addition was slightly higher for the middle stages.

NASA FIVE-STAGE RESEARCH COMPRESSOR LOW ASPECT RATIO

DESIGN FACTORS




NASA FIVE-STAGE RESEARCH COMPRESSOR LOW ASPECT RATIO DESIGN

Shown here are the loss correlations used in the design. The shock loss used a simple correlation as a function of inlet relative Mach number. The profile losses were based on single stage results. The measured endwall losses were tempered somewhat to partly account for mixing effects.

NASA FIVE-STAGE RESEARCH COMPRESSOR LOW ASPECT RATIO

LOSS PARAMETER CORRELATIONS




NASA FIVE-STAGE RESEARCH COMPRESSOR
LOW ASPECT RATIO DESIGN

Shown here are the deviation angle adjustments to Carter's Rule used in the design to reflect observed endwall effects on this parameter.

NASA FIVE-STAGE RESEARCH COMPRESSOR
LOW ASPECT RATIO

DEVIATION ADJUSTMENTS TO CARTER'S RULE




NASA FIVE-STAGE RESEARCH COMPRESSOR
LOW ASPECT RATIO DESIGN

Shown here is a photograph of the first three-stages of NASA Five-Stage Research Compressor incorporating low aspect ratio rotors and stators. Note the blade rows are close coupled. Dampers are not required on the first rotor because of the low aspect ratio.

NASA FIVE-STAGE RESEARCH COMPRESSOR
LOW ASPECT RATIO

THREE STAGE HARDWARE




NASA FIVE-STAGE RESEARCH COMPRESSOR
LOW ASPECT RATIO DESIGN

THREE STAGE PERFORMANCE

Shown here is the performance of the first three stages of the low aspect ratio NASA Five-Stage Compressor. The data was obtained at design IGV and stator setting angles. Excellent part speed performance was obtained. Some falloff in efficiency occurred at design speed and was expected. This is because the design efficiency was established as mentioned earlier to favor part speed performance. It was anticipated that improvements in design speed performance could be achieved through rematching of the stages using variable geometry.

NASA FIVE - STAGE RESEARCH COMPRESSOR
LOW ASPECT RATIO

THREE STAGE PERFORMANCE



NASA FIVE-STAGE RESEARCH COMPRESSOR LOW ASPECT RATIO DESIGN

THREE STAGE PERFORMANCE


Shown here is the performance for the first three stages of the low aspect ratio NASA five-stage compressor: (1) with vanes scheduled to maximize performance at design speed and maintained at that setting at part speed and (2) for the vanes set for optimum performance (maximum efficiency at each speed). Note the severe falloff in efficiency at part speed when the vanes were maintained at the design speed optimum setting. Also note the improved performance at design speed for optimum setting compared to design. Performance with the vanes optimized for each speed is considered excellent. This compressor is now being used to study stage matching, install performance of highly loaded, high tip speed compressors and aeroelastic responses due to rotor stator interactions.

Obviously, the data base was not in place when we started such an aggressive design. However, we learned as much from the failures as we did from the successes along the way. Many lessons were learned in the process.


NASA FIVE-STAGE RESEARCH COMPRESSOR LOW ASPECT RATIO

THREE STAGE PERFORMANCE VANE SCHEDULE EFFECTS

DESIGN SPEED SCHEDULE



OPTIMUM SCHEDULE



SUMMARY

The design of modern day transonic multistage compressors is highly sophisticated and depends on an extensive empirical data base as well as the judicious judgment of the design engineer. As computational methods are developed and validated, the move towards a first principle system will occur. Advanced computational codes are now being used to analyze and guide transonic multistage designs.

Performance in terms of efficiency is considered to be approaching a physical maximum for large flow size machines. However, further increases in overall pressure ratio and a reduction in the number of stages required to achieve a given pressure ratio are anticipated.

Future advancements in the design of multistage transonic compressors will depend heavily on advanced computer technology, computational methods and more detailed internal flow measurements.

REFERENCES

1. Seymour Lieblein and I. A. Johnsen: Resume of Transonic-Compressor Research at NACA Lewis Laboratory. ASME Journal of Engineering for Power, Vol. 83, July 1961, p. 219.
2. R. O. Bullock: Critical High Lights in the Development of Transonic Compressor. ASME Journal of Engineering for Power, Vol. 83, July 1961, p. 243.
3. M. Savage, E. Boxer, and J. R. Erwin: Resume of Compressor Research at the NACA Langley Laboratory. ASME Journal of Engineering for Power, Vol. 83, July 1961, p. 269.
4. Seymour Lieblein, Francis C. Schwenk, and Robert L. Broderick: Diffusion Factor for Estimating Losses and Limiting Blade Loadings in Axial-Flow-Compressor Blade Elements. NACA RM E53D01, 1953.
5. G. R. Miller, G. W. Lewis, Jr., and M. J. Hartmann: Shock Losses in Transonic Compressor Blade Rows. ASME Journal of Engineering for Power, Vol. 83, July 1961, p. 235.
6. Charles H. Voit: Investigation of a High-Pressure-Ratio Eight-Stage Axial-Flow Research Compressor With Two Transonic Inlet Stages. I--Aerodynamic Design. NACA RM E53I24, 1953.
7. Richard P. Geyte, Ray E. Budinger, and Charles H. Voit: Investigation of a High-Pressure-Ratio Eight-Stage Axial-Flow Research Compressor With Two Transonic Inlet Stages. II--Preliminary Analysis of Over-All Performance. NACA RM E53J06, 1953.
8. Charles H. Voit and Richard P. Geyte: Investigation of a High-Pressure-Ratio Eight-Stage Axial-Flow Research Compressor With Two Transonic Inlet Stages. III--Individual Stage Performance Characteristics. NACA RM E54H17, 1954.
9. Richard P. Geyte and Charles H. Voit: Investigation of a High-Pressure-Ratio Eight-Stage Axial-Flow Research Compressor With Two Transonic Inlet Stages. IV--Modification of Aerodynamic Design and Prediction of Performance. NACA RM E55B28, 1955.
10. Raymond M. Standahar and Richard P. Geyte: Investigation of a High-Pressure-Ratio Eight-Stage Axial-Flow Research Compressor With Two Transonic Inlet Stages. V--Preliminary Analysis of Over-All Performance of Modified Compressor. NACA RM E55A03, 1955.
11. Gilbert K. Sievers, Richard P. Geyte, and James G. Lucas: Preliminary Analysis of Over-All Performance of an Eight-Stage Axial-Flow Research Compressor With Two Long-Chord Transonic Inlet Stages. NACA RM E57H14, 1958.

12. Raymond M. Standahar, Morgan P. Hanson, and Richard P. Gey: Investigation of a High-Pressure-Ratio Eight-Stage Axial-Flow Research Compressor With Two Transonic Inlet Stages. NACA RM E55I13, 1955.
13. Donald M. Sandercock, Karl Kovach, and Seymour Lieblein: Experimental Investigation of a Five-Stage Axial-Flow Research Compressor With Transonic Rotors in All Stages. I--Compressor Design, NACA RM E54F24, 1954.
14. Karl Kovach and Donald M. Sandercock: Experimental Investigation of a Five-Stage Axial-Flow Research Compressor With Transonic Rotors in All Stages. II--Compressor Over-All Performance. NACA RM E54G01, 1954.
15. Donald M. Sandercock and Karl Kovach: Experimental Investigation of a Five-Stage Axial-Flow Research Compressor With Transonic Rotors in All Stages. III--Interstage Data and Individual Stage Performance Characteristics. NACA RM E56G24, 1956.
16. Donald M. Sandercock: Experimental Investigation of a Five-Stage Axial-Flow Research Compressor With Transonic Rotors in All Stages. IV--Blade-Element Performance. NACA RM E57B12, 1957.
17. Karl Kovach and Donald M. Sandercock: Aerodynamic Design and Performance of Five-Stage Transonic Axial-Flow Compressor. ASME Journal of Engineering for Power, Vol. 83, July 1961, p. 303.
18. W. B. Gardner: Energy Efficient Engine (E³) Technology Status. AIAA Paper 82-1052, June 1982.
19. P. R. Holloway, G. L. Knight, C. C. Koch and S. J. Shaffer: Energy Efficient Engine High Pressure Compressor Detailed Design Report. NASA CR-165558, May 1982.
20. R. J. Steinke: Design of 9.271-Pressure-Ratio Five-Stage Core Compressor and Overall Performance for First Three Stages. NASA TP-2597, May 1986.
21. J. E. Crouse and W. T. Gorrell: Computer Program for Aerodynamic and Blading Design of Multistage Axial-Flow Compressors. NASA TP-1946, 1981.
22. H. E. Stephens: Application of Supercritical Airfoil Technology to the Compressor Cascades. AIAA Paper 78-1138, July 1978.
23. H. Rechter, P. Schimming, and H. Starcken: Design and Testing of Two Super-Critical Compressor Cascades. ASME Paper 79-CT-11, Mar. 1979.
24. D. R. Boldman, A. E. Buggele, and L. M. Shaw: Experimental Evaluation of Shockless Supercritical Airfoils in Cascade. AIAA Paper 83-003, Jan. 1983. (NASA TN-83045.)

25. J. F. Schmidt, T. F. Gelder, and L. F. Donovan: Redesign and Cascade Tests of a Supercritical Controlled Diffusion Stator Blade-Section. AIAA Paper 84-1207, June 1984. (NASA TM-83635.)
26. R. F. Behlke, J. D. Brooky, and E. Canal: Study of Controlled Diffusion Stator Blading. (PWA-5698-77, Pratt & Whitney Aircraft Group) NASA CR-167995, 1983.
27. R. F. Behlke: The Development of a Second Generation of Controlled Diffusion Airfoils for Multistage Compressors. Journal of Turbomachinery, Transactions of ASME, Vol. 108, No. 1, July 1986, pp. 32-41.
28. T. F. Gelder, J. F. Schmidt, K. N. Suder and M. D. Hathaway: Design and Performance of Controlled-Diffusion Stator Compared with Original Double-Circular-Arc Stator. SAE 871783, October 1987.
29. A. J. Strazisar: Investigation of Flow Phenomena in a Transonic Fan Rotor Using Laser Anemometry. Journal of Engineering for Gas Turbines and Power, Vol. 107, No. 2, Apr. 1985, pp. 427-435.
30. K. L. Suder, M. D. Hathaway, T. H. Okiishi, A. J. Strazisar, and J. J. Adamczyk: Measurements of the Unsteady Flow Field Within the Stator Row of a Transonic Axial Flow Fan. I - Measurement and Analysis Technique. ASME Paper 87-GT-226, June 1987. (NASA TM-88945.)
31. M. H. Pierzga and J. R. Wood: Investigation of the Three-Dimensional Flow Field Within a Transonic Fan Rotor: Experiment and Analysis. Journal of Engineering for Gas Turbines and Power, Vol. 107, No. 2, Apr. 1985, pp. 436-449.
32. M. D. Hathaway, K. L. Suder, T. H. Okiishi, A. J. Strazisar, and J. J. Adamczyk: Measurements of the Unsteady Flow Field Within the Stator Row of a Transonic Axial Flow Fan. II - Results and Discussion. ASME Paper 87-GT-227, June 1987. (NASA TM-88946.)
33. J. J. Adamczyk, R. A. Mulac and M. L. Celestina: A Model for Closing the Inviscid Form of the Average-Passage Equations. NASA TM-87199, June 1986.
34. T. Katsanis and W. D. McNally: Revised Fortran Program for Calculating Velocities and Streamlines on the Hub-Shroud Midchannel Stream Surface of an Axial-, Radial-, or Mixed-Flow Turbomachine or Annular Duct. I: Users Manual. NASA TN D-8430, 1977.
35. T. Katsanis: Fortran Program for Calculating Transonic Velocities on a Blade-to-Blade Stream Surface of a Turbomachine. NASA TN D-5427, 1969.
36. J. D. Denton: An Improved Time Marching Method for Turbomachinery Calculation. ASME Paper 82-GT-239, 1982.
37. R. V. Chima: Development of an Explicit Multigrid Algorithm for Quasi-Three-Dimensional Viscous Flows in Turbomachines. AIAA Paper 86-0032, Jan. 1986.

38. Irving A. Johnsen and Robert O. Bullock, eds.: Aerodynamic Design of Axial-Flow Compressors. NASA SP-36, 1965.
39. L. Reid and R. D. Moore: Experimental Study of Low Aspect Ratio Compressor Blading. ASME Paper No. 80-GT-6, December 1979.
40. D. C. Wisler: Core Compressor Exit Stage Study. NASA CR 165554, December 1981.
41. H. V. Marman and R. D. Marchant: Preliminary Compressor Design Study for an Advanced Multistage Axial Flow Compressor - Final Report. NASA CR 135091, September 1976.
42. D. C. Wisler, C. C. Koch and L. H. Smith, Jr.: Preliminary Design Study of Advanced Multistage Axial Flow Core Compressor. NASA CR 135133, February 1977.
43. G. G. Adkins, Jr. and L. H. Smith, Jr.: Spanwise Mixing in Axial-Flow Turbomachines. ASME Paper 81-GT-57, Mar. 1981.
44. D. Wisler, R. C. Bauer and T. H. Okiishi: Secondary Flow, Turbulent Diffusion, and Mixing in Axial-Flow Compressors. ASME Journal of Turbomachinery, Vol. 109, Oct. 1987.
45. S. J. Gallimore and N. A. Cumpsty: Spanwise Mixing in Multistage Axial Flow Compressors: Part I - Experimental Investigation. ASME Journal of Turbomachinery, Vol. 108, July 1986, pp. 2-4.
 S. J. Gallimore: Spanwise Mixing in Multistage Axial Flow Compressors: Part II - Throughflow Calculations Including Mixing. ASME Journal of Turbomachinery, Vol. 108, July 1986.
46. C. L. Ball, L. Reid and J. F. Schmidt: End-wall Boundary Layer Measurement on a Two-Stage Fan. NASA TM 83409.
47. E. M. Greitzer: Surge and Rotating Stall in Axial Flow Compressors - Part I: Theoretical Compression System Model. ASME Journal of Engineering for Power, Vol. 98, April 1976, pp. 190-198.
48. E. M. Greitzer: Surge and Rotating Stall in Axial Flow Compressors - Part II: Experimental Results and Comparison with Theory. ASME Journal of Engineering for Power, Vol. 98, April 1976, pp. 198-217.
49. I. J. Day, E. M. Greitzer and N. A. Cumpsty: Prediction of Compressor Performance in Rotating Stall. ASME Journal of Engineering for Power, Vol. 100, January 1978, pp. 1-14.
50. E. M. Greitzer: Review-Axial Compressor Stall Phenomena. ASME Journal of Fluids Engineering, Vol. 102, June 1980.
51. E. M. Greitzer: The Stability of Pumping Systems - The 1980 Freeman Sctiolar Lecture. ASME Journal of Fluids Engineering, Vol. 103, June 1981.

52. F. K. Moore: A Theory of Rotating Stall of Multistage Axial Compressors. NASA CR 3685, July 1983.
53. F. K. Moore: A Theory of Rotating Stall of Multistage Axial Compressors, Part I - Small Disturbances. ASME 83-GT-44 (Presented at the ASME 28th International Gas Turbine Conference and Exhibit, Phoenix, AZ, March 27-31, 1983.
54. F. K. Moore: A Theory of Rotating Stall of Multistage Axial Compressors, Part II - Finite Disturbances. ASME 83-GT-45 (Presented at the ASME 28th International Gas Turbine Conference and Exhibit, Phoenix, AZ, March 27-31, 1983.
55. F. K. Moore: A Theory of Rotating Stall of Multistage Axial Compressors, Part III - Limit Cycles. ASME 83-GT-46 (Presented at the ASME 28th International Gas Turbine Conference and Exhibit, Phoenix, AZ, March 27-31, 1983.
56. R. S. Mazzawy: Surge-Induced Structural Loads in Gas Turbines. ASME Journal of Engineering Power, Vol. 102, No. 1, January 1980.
57. M. D. Rudy: Transient Blade Response Due to Surge Induced Structural Loads. SAE Technical Paper 821438 (Presented at Aerospace Congress Exposition, Anaheim, CA) October 25-28, 1982.
58. W. M. Hosny, C. H. Lenhardt, H. T. Liu, R. C. Lovell and W. G. Steenken: Energy Efficient Engine (ICLS/IOC) High Pressure Compressor Report. NASA CR-174955, August 1985.
59. D. C. Urasek, R. J. Steinke and W. S. Cunnan: Stalled and Stall-Free Performance of Axial-Flow Compressor Stage with Three Inlet-Guide-Vane and Stator-Blade Settings. NASA TN D-8457, May 1977.