provided by NASA Technical Reports Serve

53518-CR 1rveying 20 P.

Department of Geodetic Science and Surveying

BASIC RESEARCH FOR THE GEODYNAMICS PROGRAM

Seventeenth Semiannual Status Report Research Grant No. NSG 5265 OSURF Project No. 711055

Period Covered: July - December, 1986

(NASA-CR-180137) EASIC RESEARCH FOR THE GEODYNAMICS PROGRAM Semiannual Status Report, Jul. - Dec. 1986 (Chio State Univ.) 20 p CSCL 08G

N87-17415

Unclas 43723

G3/46

Prepared for

NASA/Goddard Space Flight Center Greenbelt, Maryland 20771

> The Ohio State University Research Foundation Columbus, Ohio 43212

> > December, 1986

PREFACE

This project is under the supervision of Professor Ivan I. Mueller, Department of Geodetic Science and Surveying, The Ohio State University. The Science Advisor is Dr. David E. Smith, Code 921, Geodynamics Branch, and the Technical Officer through June 30, 1986, was Mr. Jean Welker, Code 903, Technology Applications Center. From July 1, 1986, the Technical Officer is Dr. Gilbert D. Mead, Code 601, Crustal Dynamics Project, Space and Earth Sciences Directorate. All addresses are at Goddard Space Flight Center, Greenbelt, Maryland 20771.

Because of the change in the contract administration, from now on the semiannual reports will cover the periods January-June and July-December, instead of October-March and April-September.

TABLE OF CONTENTS

			Page				
1.	CURR	ENT TECHNICAL OBJECTIVES	. 1				
2.	ACTIVITIES						
	2.1	Earth Rotation Parameter Determination from Different Space Geodetic Systems	. 2				
	2.2	Utilization of Range-Difference Observations in Geodynamics	. 3				
	2.3	An Algorithm for Crustal Deformation Analysis	. 5				
3.	PERS	ONNEL	. 12				
4.	TRAV	EL	. 12				
5.	REPO	RTS PUBLISHED TO DATE	. 14				

1. CURRENT TECHNICAL OBJECTIVES

1.	Intercomparison	of	Different	Space	Geodetic	Measurement	and	Computational
	Data							•

2.	Regional	Deformations	and	Relative	Plate	Motions	from	Robust	Estimation
----	----------	--------------	-----	----------	-------	---------	------	--------	------------

2. ACTIVITIES

2.1 Earth Rotation Parameter Determination from Different Space Geodetic Systems

This work has been nearly completed during this reporting period. After some further development of utility program software for analyzing final results, the main simulation experiments were performed, and results and conclusions compiled. Although awaiting final approval, the PhD dissertation [Archinal, 1987a] has been completed and describes the majority of the work and results of this study. Some additional work will probably be done, including performing simulation experiments using different orbital and observational weighting, and more normal observational data rates. It is planned that the just mentioned dissertation will be revised to reflect this additional work and published as [Archinal, 1987b].

During the latter part of the reporting period the results of the study were also presented at several meetings, as listed at the end of this report.

References

Archinal, Brent A. (1987a), Determination of Earth Rotation by the Combination of Data from Different Space Geodetic Systems, PhD dissertation, Ohio State Univ., Columbus, in preparation.

Archinal, Brent A. (1987b), "Determination of Earth Rotation by the Combination of Data from Different Space Geodetic Systems," Dept. of Geodetic Science and Surveying Rep., Ohio State Univ., Columbus, in preparation.

2.2 Utilization of Range-Difference Observations in Geodynamics

As anticipated in the 16th Semiannual Report, this study is close to being completed, and the final report is in preparation [Dedes, 1987]. For this reason, only a brief summary of the work accomplished in the last six months will be reported.

During this period the dynamic models employed by the GEOSPP software have been updated to be compatible with the MERIT Standards [Melbourne et GEOSPP is a software used to implement the Simultaneous Range-Difference (SRD) semidynamic mode method [Pavlis, 1982]. This method was anticipated to yield baseline estimates whose accuracy would be insensitive to the overall orbital accuracy and sensitive to the accuracy of the observations, especially if certain geometric configurations are fulfilled. This in fact has proven to be the case. For instance, baselines close to being parallel with their observed arcs have been estimated with an accuracy of 2 This accuracy not only represents one standard deviation but also reflects agreement when these baselines are compared corresponding ones as estimated by other computational centers using the range dynamic mode method [Tapley et al., 1985]. This accuracy was achieved, despite the fact that the input initial state vectors were in error by 150 meters and that the standard deviations of the adjusted ones were as large as 50 meters.

These results demonstrate the sensitivity of the SRD method to the accuracy of the observations as well as the insensitivity of this method to the overall orbital accuracy. Furthermore, these baseline estimates were obtained by using only eight Lageos passes. Realistically, eight Lageos passes may be observed in about a week. Therefore, this method is ideal for rapid baseline determination especially when mobile laser systems are moved into an area with the aim of spending the least possible time collecting data for baseline determination.

There still needs to be established how the relative orientation between the baselines and their observed arcs is related to the number of arcs necessary for convergence, when the baselines are estimated through the SRD method. This will be revealed by estimating baselines having different lengths and different orientation with their observed arcs. Furthermore, in the geometric mode method (16th Semiannual Status Report) tidal effects should be accounted for. Both of these tasks are expected to be completed by the end of this calendar year.

Presently the work is focused on finishing with these tasks and on preparing the final report which is expected to be ready within the next three months.

References

"Basic Research for the Geodynamics Program, April-September, 1986," 16th Semiannual Status Rep., Ohio State Univ. Research Foundation, RF 711055, Columbus.

Dedes, George C. (1987), "Baseline Estimation from Simultaneous Satellite Laser Tracking," Dept. of Geodetic Science and Surveying Rep., Ohio State Univ., Columbus, in preparation.

Melbourne, W. et al. (1983), "Project MERIT Standards, U.S. Naval Observatory Circular No. 167, Washington, D.C.

Pavlis, Erricos C. (1982), "On the Geodetic Applications of the Simultaneous Range-Differencing to Lageos," Dept. of Geodetic Science and Surveying Rep. 338, Ohio State Univ., Columbus.

Tapley, B.D., R.J. Eanes and B.E. Schutz (1985), "UT/CSR Analysis of Earth Rotation from Lageos SLR Data," Proc. of the International Conf. on Earth Rotation and the Terrestrial Reference Frame, Dept. of Geodetic Science and Surveying, Ohio State Univ., Columbus.

2.3 An Algorithm for Crustal Deformation Analysis

Sequential Model Discrimination

In the previous five Semiannual Reports (12 through 16), a general algorithm for the analysis of crustal movement measurements was proposed. In this report, a method based on the Bayesian philosophy and entropy measure of information is given for the elucidation of time-dependent models of crustal motions as part of the proposed algorithm. The method, which is due to Box and Hill (1967), is first reproduced; then the strategy of model discrimination and design of measurements is illustrated in an example for the case of crustal deformation models.

In the analysis of statistical decision theory two problems are generally distinguished. One is the problem of making the best decision on the basis of a given set of data, and the other is the problem of designing the best experiments in order to get information upon which a decision will be made. In this respect, model discrimination procedures of the proposed algorithm can be examined within the scope of these two problems.

Assume that geodetic surveys are performed at different epochs. The data indicate that crustal motions occurred during these time intervals and a set of concurring descriptive models are postulated either as a result of the displayed dislocation patterns of the network points and/or previous information. The question is how to use the data to select the best model and to design new optimal observations to facilitate model discrimination.

Since in general every decision is a result of some type of decision rule, it is necessary at this point to define a discrimination criterion.

Consider a complete set of events, E_i , i = 1, 2, ... m whose probabilities are $p_1, p_2, ..., p_m$ such that $\sum_{i=1}^{m} p_i = 1$. The expected information of the message on the occurrence of one of these events is defined as

$$I: = \sum_{i=1}^{m} p_i \ln \frac{1}{p_i}$$
 (1)

which is also known as the entropy of the distribution whose probabilities are p_i , i=1, 2, ... m (Shannon 1948). The least possible information occurs when $p_1 = p_2 ... p_m = 1/m$, which can be derived by maximizing the above equation subject to the constraint $\sum p_i = 1$. In this case the amount of information is small and the entropy as a measure of disorder is maximum. In other words, all events are equally likely. In situations where the probability of one event p_i is larger than the probability of other events p_j , $j \neq i$, the amount of information is considered to be large and entropy is small.

This concept can be applied to the discrimination of different competing models. Let there be a set of m competing models and the a priori probability of the i^{th} model being true is p_i . If the observations are performed and the a posteriori probability for the i^{th} model is computed, then the information gained by this experiment is specified, from (1) as

$$\Delta I(H,x) = -\sum_{i=1}^{m} p_{in-1} \ln p_{in-1} + \sum_{i=1}^{m} p_{in} \ln p_{in}$$
 (2)

The maximum of $\Delta I(H,x)$ is of interest in order to obtain the greatest amount of information out of the experiment. Now, using (2) and considering that there exists a finite number of models, the expected change in entropy (information) $E(\Delta I) = :\Delta J$ before and after the n^{th} observation is

$$\Delta J = \sum_{i=1}^{m} p_{i,n-1} \left\{ \sum_{k=1}^{m} p_{kn} \ln p_{kn} - \sum_{k=1}^{m} p_{kn-1} \ln p_{kn-1} \right\} \cdot p_{i}(y|x) dy_{n}$$
 (3)

where

$$\mathbf{p_{in}} = \frac{\mathbf{p_{in-1}} \ \mathbf{p_{i}(y|x)}}{\sum_{\ell=1}^{n} \mathbf{p_{\ell n-1}} \ \mathbf{p_{\ell}(y|x)}} \tag{4}$$

Substituting (4) into (3)

$$\Delta J = \sum_{i=1}^{m} p_{i,n-1} \int p_{i}(y|x) \ln \frac{p_{i}(y|x)}{\sum_{\ell=1}^{m} p_{\ell,n-1} p_{\ell}(y|x)} dy_{n}$$
(5)

Now an observation which maximizes (5) is considered the optimum one. Evaluation of (5) however is quite complicated, but an upper bound for this expression leads to a tractable form. Consider

$$\sum_{i=1}^{m} p_{jn-1} p_{i}(y|x) \ln \frac{p_{i}(y|x)}{p_{j}(y|x)} > p_{i}(y|x) \ln \frac{p_{i}(y|x)}{\sum_{\ell=1}^{m} p_{\ell n} p_{\ell}(y|x)}$$
(6)

which is a result of Corollary 3.1 of Kullback (1959). Substitution of (6) into (5) gives an upper bound ΔJ_u for ΔJ

$$\Delta J_{u} = \sum_{i=1}^{m} \sum_{j=1}^{m} p_{i,n-1} p_{j,n-1} \left[\int p_{i}(y|x) \ln \frac{p_{i}(y|x)}{p_{j}(y|x)} dy_{n} + \int p_{j}(y|x) \ln \frac{p_{j}(y|x)}{p_{i}(y|x)} dy_{n} \right]$$
(7)

Let now a group of competing models is given by

$$E(y^{(i)}) = A^{(i)}x^{(i)}, i = 1, 2, ... m$$
 (7a)

where $y^{(i)}$ is the m×l vector of observations for the ith model, $A^{(i)}$ is the nonstochastic n×u design matrix, and $x^{(i)}$ is the u×l unknown parameter vector for the ith model. u is not necessarily the same for all models. If the observations y_n are assumed to be distributed normally with mean $E(y_n)$ and

known variance σ^2 , the following relationships hold

$$p_{i}\left(y_{n}|E(y_{n}),\sigma\right) = \frac{1}{\sqrt{2\pi}} \exp\left\{-\frac{1}{2\sigma^{2}}\left[y_{n} - E(y_{n})\right]^{2}\right\}$$
(8)

$$p_{i}\left(\mathbb{E}(y_{n}) \mid \sigma\right) = \frac{1}{\sqrt{2\pi}} \exp\left\{-\frac{1}{\sqrt{2\pi} \sigma_{i}} \left[\mathbb{E}(y_{n}) - \hat{y}_{n}^{(i)}\right]^{2}\right\}$$
(9)

where $\hat{y}_{n}^{(i)}$ is the predicted value of y_{n} under model i using n-1 observations and its variance is σ_{i}^{2} which is given by

$$\sigma_{i}^{2} = \sigma^{2} a_{n}^{(i)} (A^{(i)}'A^{(i)})^{-1} a_{n}^{(i)}'$$
(10)

where $a_n^{(i)}$ is the row vector of $A^{(i)}$. From the definition of the probability density function of y_n under model i given σ and n-1 observations

$$p_{i}(y_{n}|\sigma) = \int p_{i}(y_{n}|E(y_{n}),\sigma) p_{i}(E(y_{n})|\sigma) d(E(y_{n}))$$
(11)

If (8) and (9) are substituted in (11) and integrated, then

$$p_{i}(y_{n}|\sigma) = \frac{1}{2\pi(\sigma^{2} + \sigma_{i}^{2})} \exp\left\{-\frac{1}{2(\sigma^{2} + \sigma_{i}^{2})} (y_{n} - \hat{y}_{n}^{(i)})^{2}\right\}$$
(12)

Substitution of (12) into (7) results in the following operational form of discrimination function

$$\Delta J_{u} = \frac{1}{2} \sum_{i=1}^{m} \sum_{j=1}^{m} p_{i n-1} p_{j n-1} \left\{ \frac{(\sigma_{i}^{2} - \sigma_{j}^{2})^{2}}{(\sigma^{2} + \sigma_{i}^{2})(\sigma^{2} + \sigma_{j}^{2})} + (\hat{y}_{n}^{(i)} - \hat{y}_{n}^{(j)}) \right\} .$$

$$\left\{ \frac{1}{(\sigma^{2} + \sigma_{i}^{2})} + \frac{1}{(\sigma^{2} + \sigma_{j}^{2})} \right\}$$
(13)

where $\hat{y}_{n}^{(i)}$ and $\hat{y}_{n}^{(j)}$ are the predicted observations for model i and j, σ_{i}^{2} and σ_{j}^{2} are the predicted variances obtained from (10) for these predicted observations and σ^{2} is the known a priori variance of the observations.

It is now possible to design sequential geodetic surveys to discriminate the descriptive models of deformations using this entropy measure of information. The scenario which is depicted in Fig. 1 is as follows.

First an initial network design for the area under consideration is constructed, for instance, using the D-optimal design criteria which is discussed in the 12th Semiannual Report. Geodetic surveys are then performed at two different epochs covering the whole network. This is followed by the estimation of deformation parameters from the differences of observed quantities. At this point, information provided by the current estimates and prior qualitative information are examined, and prior

probabilities are assigned to each model. If no preference is inferred from the existing information, each model is assigned equal probabilities p = 1/m, where m is the number of models. The next optimal observation (not necessarily the resurvey of the whole network) that gives the maximum expected discrimination among m rival models is sought in (13). Then the new optimal measurement(s) is performed and posterior probabilities for each model are computed using equation (4). Finally, the current standing of each model is examined. This procedure is repeated each time using posterior probabilities of previous observations as prior probabilities for the succeeding observations, until one model emerges from the others. The following numerical example illustrates the procedure.

Numerical Example

In the previous section, a method based on the entropy measure of information is presented as a possible candidate for the discrimination of several competing time-dependent models. In order to get a better feeling for the applicability of the method to the crustal deformation analysis, this section describes a numerical example.

Consider the case of a homogeneous deformation field. The following descriptive models are postulated as a result of prior experiments to represent possible network deformations,

$$model 2. dx = e_x x \Delta t (15)$$

where dx and dy are the displacement components of network points for the period Δt ; e_x and e_y are the extensional strains in X Y directions; e_{xy} is the shearing strain. If the baselines are observed at different epochs, then the baseline length ℓ_{ij} at epoch t is given by the following expression,

$$t_{ij}^2 = (x_j - x_i)^2 + (y_j - y_i)^2$$
 (17)

Linearizing this expression about the initial epoch to and considering equations (14), (15) and (16), results in the following mathematical models,

model 1:
$$\ell_{ijt} - \ell_{ijt_0} = \Delta t \ell_{ij} (\sin^2 \alpha_{ij} e_x + \cos^2 \alpha_{ij} e_y + \sin^2 2\alpha_{ij} e_{xy})$$
 (18)

model 2:
$$l_{ijt} - l_{ijt_0} = \Delta t l_{ij} \sin^2 \alpha_{ij} e_x$$
 (19)

model 3:
$$\ell_{ijt} - \ell_{ijt_0} = \Delta t \ell_{ij} \sin 2\alpha_{ij} e_{xy}$$
 (20)

where l_{ijt} and l_{ijt_0} are the observed baseline lengths at epochs t and t_0 respectively, and α_{ij} is the azimuth of the observed baseline i-j. In this

example, model 3 is chosen to be the correct model and the pseudo-

observations ℓ_{ijt} and ℓ_{ijt_0} are derived using this model. They are also contaminated with a noise from a normal distribution with mean zero and variance 1 mm. Shearing strain, e_{xy} , in the correct model 3 is 0.50 ppm and the time interval between observations is constant and equal to a month. The sequential model discrimination procedure can now be performed using the algorithm depicted in Fig. 1.

An initial design is set up for the measurement of deformation parameters (Fig. 2a). This is a D-optimal design of model 1, which was derived in the 12th Semiannual Report, with some additional observations. It is initially postulated that all three models are equally likely. In other words, prior probabilities for each model are 1/3. Part of the network is resurveyed a month later. This makes it possible to predict a new observation for the next month that maximizes the discrimination function ΔJ_u for each model and select the possible observation which gives the maximum discrimination. In this example three alternatives are possible: baselines which are in the north-east direction, baselines which are in the south-west direction, and baselines which are in the east-west direction. The predicted observation is then performed and posterior probabilities for each model are computed using the new observations and prior probabilities (4).

The rest of the experiment continues following this prediction and observation procedure until computed posterior probabilities indicate that one model is superior to the others (Figs. 2c, 2d and 2e). Fig. 2 shows that the correct model 3 is identified effectively with 14 baseline observations after six months.

As a comparison, null-hypothesis tests (H_0 : Model 3 is the same as model 1, H_0 : Model 3 is the same as model 2) are performed using the estimated parameters obtained by the least squares method at 5% and 1% significance levels. Neither hypothesis is rejected at the 1% significance level until $\Delta t = 5$ months (Fig. 2e). In the case of $\alpha = 0.05$, model 2 is rejected at $\Delta t = 5$. Model 2 is rejected at $\Delta t = 6$ months at both levels. However, the results were ambiguous in the sense that model 2 and model 3 were still likely candidates until the last measurement was performed. This problem is clearly eliminated by the proposed method due to the history of accumulated measurements and calculated posterior probabilities of each model.

REFERENCES

Box, G.E.P. and W.J. Hill (1967), "Discrimination Among Mechanistic Models," *Technometrics*, Vol. 9, No. 1, pp. 57-71.

Kullback, S. (1959), Information Theory and Statistics, John Wiley.

Shannon, C.E. (1948), "A Mathematical Theory of Communication," The Bell Syst. Tech. J., Vol. XXVII, No. 3, pp. 379-657.




Fig. 1 Sequential model discrimination.

--- INITIAL DESIGN PRIOR PREFERENCES AND OBSERVATIONS 1/3 a) 2 Model: POSTERIOR PROBABILITIES REPEATED OBSERVATIONS OBSERVATION PREDICTED ь) $\Delta t = 2$ 2 3 1 **c**) $\Delta t = 3$ 2 1 0.13 d) 2 3 1 1 t=4 ე.85 e) 3 2 $\Delta t=5$ 0.96 0.04 0.00 f) 2 3 **Δ**t=6

Fig. 2 Results of sequential experiment for the discrimination of three competing models.

3. PERSONNEL

Ivan I. Mueller, Project Supervisor, part time Brent Archinal, Graduate Research Associate, part time George Dedes, Graduate Research Associate, part time Stephen A. Hilla, Graduate Teaching Associate, without compensation Huseyin Baki Iz, Graduate Teaching Associate, without compensation Ziqing Wei, Visiting Researcher, without compensation

4. TRAVEL

Ivan I. Mueller, Ziqing Wei, Stephen Hilla
Austin, Texas
April 26 - May 2, 1986
To attend 4th International Geodetic Symposium on Satellite Positioning and to make presentations.

Ivan I. Mueller, Brent A. Archinal
Baltimore, Maryland May 20-23, 1986
To attend Annual Spring Meeting of the American Geophysical Union.
Mueller presented an invited paper. No project support.

Ivan I. Mueller
Toronto, Canada
June 1-9, 1986
To attend 18th International Congress of Surveyors. No project support.

Ivan I, Mueller
Toulouse, France
June 28 - July 11, 1986
To attend XXVI Plenary Meeting and associated activities of COSPAR and present an invited paper. No project support.

Ivan I. Mueller
Tallinn, USSR
September 7-12, 1986
Invited speaker at VI International Symposium on Recent Crustal
Movements. No project support.

Brent A. Archinal
Washington, D.C.
Discussions at U.S. Naval Observatory.
September 11-12, 1986
No project support.

Ivan I. Mueller, Brent A. Archinal, Huzeyin Baki Iz
Greenbelt, Maryland
October 14-16, 1986
To make presentations at 11th Crustal Dynamics Principal Investigators
Meeting at Goddard Space Flight Center. Project support only for Mueller.

Brent A. Archinal, George C. Dedes
Coolfront, West Virginia
To attend IAU/IAG Symposium on Earth Rotation and Reference Frames for Geodesy. Archinal presented paper. No project support.

Ivan I. Mueller

Mendoza, Argentina

October 24 - November 4, 1986

Invited speaker at 14th Meeting on Geophysics and Geodesy of the

Argentine Association of Geodesy and Geophysics. No project support.

Ivan I. Mueller
San Francisco
December 6-10, 1986
To attend Annual Fall Meeting of the American Geophysical Union.
No project support.

5. REPORTS PUBLISHED TO DATE

OSU Department of Geodetic Science Reports published

- 262 The Observability of the Celestial Pole and Its Nutations by Alfred Leick
 June, 1978
- 263 Earth Orientation from Lunar Laser Range-Differencing by Alfred Leick
 June, 1978
- 284 Estimability and Simple Dynamical Analyses of Range (Range-Rate and Range-Difference) Observations to Artificial Satellites by Boudewijn H.W. van Gelder December, 1978
- 289 Investigations on the Hierarchy of Reference Frames in Geodesy and Geodynamics
 by Erik W. Grafarend, Ivan I. Mueller, Haim B. Papo, Burghard Richter August, 1979
- 290 Error Analysis for a Spaceborne Laser Ranging System by Erricos C. Pavlis September, 1979
- 298 A VLBI Variance-Covariance Analysis Interactive Computer Program by Yehuda Bock
 May, 1980
- 299 Geodetic Positioning Using a Global Positioning System of Satellites by Patrick J. Fell June, 1980
- 302 Reference Coordinate Systems for Earth Dynamics: A Preview by Ivan I. Mueller August, 1980
- 320 Prediction of Earth Rotation and Polar Motion by Sheng-Yuan Zhu September, 1981
- 329 Reference Frame Requirements and the MERIT Campaign by Ivan I. Mueller, Sheng-Yuan Zhu and Yehuda Bock June, 1982
- 337 The Use of Baseline Measurements and Geophysical Models for the Estimation of Crustal Deformations and the Terrestrial Reference System by Yehuda Bock December, 1982

- 338 On the Geodetic Applications of Simultaneous Range-Differencing to Lageos by Erricos C. Pavlis
 December, 1982
- 340 A Comparison of Geodetic Doppler Satellite Receivers by Brent A. Archinal November, 1982 (partial support)
- 348 On the Time Delay Weight Matrix in VLBI Geodetic Parameter Estimation by Yehuda Bock
 July, 1983
- 351 Model Choice and Adjustment Techniques in the Presence of Prior Information by Burkhard Schaffrin September, 1983
- 370 Positioning with NAVSTAR, the Global Positioning System by Ziqing Wei October, 1986

Determination of Earth Rotation by the Combination of Data from Different Space Geodetic Systems by Brent A. Archinal January, 1987, in preparation

Publications and Presentations Since Mid-1985

Mueller, Ivan I., "Reference Coordinate Systems and Frames: Concepts and Realization," Bulletin Géodésique, 59, 2, 181-188, 1985

Wei, Ziqing, "GPS Positioning at The Ohio State University: Franklin County Results," *Positioning with GPS-1985*, Proc. of the 1st International Symp. on Precise Positioning with the Global Positioning System, Rockville, Maryland, April 15-19, 1985 (C.C. Goad, ed.) pp. 509-520, National Geodetic Information Center, NOAA, Rockville, MD 20852

Mueller, Ivan I., "Plans for a New Terrestrial Reference Frame: The MERIT/COTES Campaigns," 7th Annual Conference on the NASA Geodynamics Program, May 27-31, 1985, Baltimore, Maryland (invited)

Mueller, Ivan I., "IAG/COSPAR African Doppler Survey—Project ADOS," 7th Annual Conference on the NASA Geodynamics Program, May 27-31, 1985, Baltimore, Maryland

Mueller, Ivan I., "Terrestrial Reference Systems," NATO Workshop on Earth's Rotation: Solved and Unsolved Problems, Chateau de Bonas, Gers, France, June 11-13, 1985 (invited)

Mueller, Ivan I. and Ziqing Wei, "MERIT Main Campaign: Reference Frame Intercomparisons," Papers in Honor of Antal Tárczy-Hornoch 85, Geodetic and Geophysical Research Institute of the Hungarian Academy of Sciences, Sopron, 1985. Also, Proc. of the International Conference on Earth Rotation and the Terrestrial Reference Frame, July 31-August 3, 1985, Columbus, Ohio, Dept. of Geodetic Science and Surveying, Ohio State Univ., Columbus

Wilkins, G.A. and I.I. Mueller, "On the Rotation of the Earth and the Terrestrial Reference System, Joint Summary Report of the IAU/IUGG Working Groups MERIT and COTES, *Bulletin Géodésique*, 60, 1986. Also, Spring Meeting of AGU, Baltimore, May 19-23, 1986 (invited)

Mueller, Ivan I., "From 100 m to 100 mm in (About) 25 Years," keynote address, *Proc. 4th International Geodetic Symposium on Satellite Positioning*, Austin, Texas, April 28 - May 2, 1986

Wei, Ziqing, "GPS Network Adjustment Using Nondifferenced Carrier Phase Measurements," Proc. 4th International Geodetic Symposium on Satellite Positioning, Austin, Texas, April 28 - May 2, 1986

Wei, Ziqing, "Mathematical Models and Results Comparison for Various Relative Positioning Modes," *Proc.* 4th International Geodetic Symposium on Satellite Positioning, Austin, Texas, April 28 - May 2, 1986

Hilla, Stephen A., "Processing Cycle Slips in Nondifferenced Phase Data from the Macrometer V-1000 Receiver, Proc. 4th International Geodetic Symposium on Satellite Positioning, Austin, Texas, April 28 - May 2, 1986

Mueller, Ivan I. and Hyman Orlin, "Center for Mapping at The Ohio State University," Papers of Commission 2, XVIII International Congress of Surveyors, Toronto, June 1-11, 1986. Also, Argentine Geophysical and Geodetic Association, 14th Scientific Meeting on Geophysics and Geodesy, Mendoza, Argentina, October 27-31, 1986

Wilkins G.A. and I.I. Mueller, "Rotation of the Earth and the Terrestrial Reference System," *E&S, Transactions, the American Geophysical Union*, Vol. 67, No. 31, Aug. 5, 1986. Also, in *CSTG Bulletin*, No. 8, 1986

Mueller, Ivan I. and George A. Wilkins, "Earth Rotation and the Terrestrial Reference Frame, Applications of Space Techniques for Geodesy and Geodynamics (COSPAR Symp. 2, July 30, 1986), D. Reidel Publ. Also, 7th International Symp. on Recent Crustal Movements of the Earth, Tallinn, USSR, Sept. 8-13, 1986. Also at Pulkovo Observatory, Leningrad, USSR, Sept. 15, 1986

Archinal, Brent A., "Combination of Data from Different Space Geodetic Systems for the Determination of Earth Rotation Parameters," 11th Crustal Dynamics Principal Investigators Meeting, Greenbelt, Md., October 20-24, 1986. Also, Proc. of IAU/IAG Symp. No. 128, Earth Rotation and Reference Frames for Geodesy and Geodynamics, October 20-24, 1986, Coolfont, West Virginia, D. Reidel, 1987

Iz, Huseyin Baki, "An Algorithm for Crustal Deformation Analysis," 11th Crustal Dynamics Principal Investigators Meeting, Greenbelt, Md., October 20-24, 1986

Mueller, Ivan I., "Surveying with the Global Positioning System," Argentine Geophysical and Geodetic Association, 14th Scientific Meeting on Geophysics and Geodesy, Mendoza, Argentina, October 27-31, 1986

Mueller, Ivan I., "Terrestrial and Celestial Reference Frames: Concepts and Realization," Argentine Geophysical and Geodetic Association, 14th Scientific Meeting on Geophysics and Geodesy, Mendoza, Argentina, October 27-31, 1986