

Acronautical Engineering A Continuing Bibliography with Indexes NASA SP-7037(187) May 1985



National Aeronautics and Space Administration



ACCESSION NUMBER RANGES

Accession numbers cited in this Supplement fall within the following ranges.

STAR (N-10000 Series)	N85-15657 - N85-17931
IAA (A-10000 Series)	A85-19102 - A85-22566

۰

م. د

4

.

This bibliography was prepared by the NASA Scientific and Technical Information Facility operated for the National Aeronautics and Space Administration by PRC Government Information Systems.

SPECIAL NOTICE

FOREIGN TECHNOLOGY INDEX IN THIS ISSUE

Documents referred to in this bibliography whose country of intellectual origin is other than the United States are listed in the Foreign Technology Index (see page D-1).

A great deal of excellent scientific and technical work is done throughout the world. To the extent that U.S. researchers, engineers, and industry can utilize what is done in foreign countries, we save our resources. We can thus increase our country's productivity.

We are testing out this approach by helping readers bring foreign technology into focus. We would like to know whether it is useful, and how it might be improved.

Check below, tear out, fold, staple, and return this sheet.

Foreign Technology Index:

	Isn't useful, so should be discontinued.
--	--

Is useful, but other sources can be used.

] Is useful and should be continued.

Suggestions for improvements to future issues:

Name (optional)_____

Organization (optional)_____

:

National Aeronautics and Space Administration

Washington, D.C. 20546

Official Business Penalty for Private Use, \$300

FIRST CLASS MAIL



Postage and Fees Paid National Aeronautics a Space Administration NASA-451

National Aeronautics & Space Administration NASA Headquarters Mail Code NIT-2 Washington, D.C. 20546



AERONAUTICAL ENGINEERING

A CONTINUING BIBLIOGRAPHY WITH INDEXES

(Supplement 187)

A selection of annotated references to unclassified reports and journal articles that were introduced into the NASA scientific and technical information system and announced in April 1985 in

- Scientific and Technical Aerospace Reports (STAR)
- International Aerospace Abstracts (IAA).



This supplement is available as NTISUB/141/093 from the National Technical Information Service (NTIS), Springfield, Virginia 22161 at the price of **\$6.00** domestic; **\$12.00** foreign.

INTRODUCTION

Under the terms of an interagency agreement with the Federal Aviation Administration this publication has been prepared by the National Aeronautics and Space Administration for the joint use of both agencies and the scientific and technical community concerned with the field of aeronautical engineering. The first issue of this bibliography was published in September 1970 and the first supplement in January 1971.

This supplement to Aeronautical Engineering -- A Continuing Bibliography (NASA SP-7037) lists 725 reports, journal articles, and other documents originally announced in April 1985 in Scientific and Technical Aerospace Reports (STAR) or in International Aerospace Abstracts (IAA).

The coverage includes documents on the engineering and theoretical aspects of design, construction, evaluation, testing, operation, and performance of aircraft (including aircraft engines) and associated components, equipment, and systems. It also includes research and development in aerodynamics, aeronautics, and ground support equipment for aeronautical vehicles.

Each entry in the bibliography consists of a standard bibliographic citation accompanied in most cases by an abstract. The listing of the entries is arranged by the first nine *STAR* specific categories and the remaining *STAR* major categories. This arrangement offers the user the most advantageous breakdown for individual objectives. The citations include the original accession numbers from the respective announcement journals. The *IAA* items will precede the *STAR* items within each category.

Seven indexes -- subject, personal author, corporate source, foreign technology, contract number, report number, and accession number -- are included.

An annual cumulative index will be published.

AVAILABILITY OF CITED PUBLICATIONS

IAA ENTRIES (A85-10000 Series)

All publications abstracted in this Section are available from the Technical Information Service, American Institute of Aeronautics and Astronautics, Inc. (AIAA), as follows: Paper copies of accessions are available at \$8.50 per document. Microfiche⁽¹⁾ of documents announced in *IAA* are available at the rate of \$4.00 per microfiche on demand. Standing order microfiche are available at the rate of \$1.45 per microfiche for *IAA* source documents.

Minimum air-mail postage to foreign countries is \$2.50 and all foreign orders are shipped on payment of pro-forma invoices.

All inquiries and requests should be addressed to AIAA Technical Information Service. Please refer to the accession number when requesting publications.

STAR ENTRIES (N85-10000 Series)

One or more sources from which a document announced in *STAR* is available to the public is ordinarily given on the last line of the citation. The most commonly indicated sources and their acronyms or abbreviations are listed below. If the publication is available from a source other than those listed, the publisher and his address will be displayed on the availability line or in combination with the corporate source line.

Avail: NTIS. Sold by the National Technical Information Service. Prices for hard copy (HC) and microfiche (MF) are indicated by a price code preceded by the letters HC or MF in the *STAR* citation. Current values for the price codes are given in the tables on page viii.

Documents on microfiche are designated by a pound sign (#) following the accession number. The pound sign is used without regard to the source or quality of the microfiche.

Initially distributed microfiche under the NTIS SRIM (Selected Research in Microfiche) is available at greatly reduced unit prices. For this service and for information concerning subscription to NASA printed reports, consult the NTIS Subscription Section, Springfield, Va. 22161.

NOTE ON ORDERING DOCUMENTS: When ordering NASA publications (those followed by the * symbol), use the N accession number. NASA patent applications (only the specifications are offered) should be ordered by the US-Patent-Appl-SN number. Non-NASA publications (no asterisk) should be ordered by the AD, PB, or other *report* number shown on the last line of the citation, not by the N accession number. It is also advisable to cite the title and other bibliographic identification.

- Avail: SOD (or GPO). Sold by the Superintendent of Documents, U.S. Government Printing Office, in hard copy. The current price and order number are given following the availability line. (NTIS will fill microfiche requests, as indicated above, for those documents identified by a # symbol.)
- Avail: NASA Public Document Rooms. Documents so indicated may be examined at or purchased from the National Aeronautics and Space Administration, Public Document Room (Room 126), 600 Independence Ave., S.W., Washington, D.C. 20546, or public document rooms located at each of the NASA research centers, the NASA Space Technology Laboratories, and the NASA Pasadena Office at the Jet Propulsion Laboratory.

⁽¹⁾ A microfiche is a transparent sheet of film, 105 by 148 mm in size containing as many as 60 to 98 pages of information reduced to micro images (not to exceed 26.1 reduction).

- Avail: DOE Depository Libraries. Organizations in U.S. cities and abroad that maintain collections of Department of Energy reports, usually in microfiche form, are listed in *Energy Research Abstracts*. Services available from the DOE and its depositories are described in a booklet, *DOE Technical Information Center Its Functions and Services* (TID-4660), which may be obtained without charge from the DOE Technical Information Center.
- Avail: Univ. Microfilms. Documents so indicated are dissertations selected from *Dissertation Abstracts* and are sold by University Microfilms as xerographic copy (HC) and microfilm. All requests should cite the author and the Order Number as they appear in the citation.
- Avail: USGS. Originals of many reports from the U.S. Geological Survey, which may contain color illustrations, or otherwise may not have the quality of illustrations preserved in the microfiche or facsimile reproduction, may be examined by the public at the libraries of the USGS field offices whose addresses are listed in this introduction. The libraries may be queried concerning the availability of specific documents and the possible utilization of local copying services, such as color reproduction.
- Avail: HMSO. Publications of Her Majesty's Stationery Office are sold in the U.S. by Pendragon House, Inc. (PHI), Redwood City, California. The U.S. price (including a service and mailing charge) is given, or a conversion table may be obtained from PHI.
- Avail: BLL (formerly NLL): British Library Lending Division, Boston Spa, Wetherby, Yorkshire, England. Photocopies available from this organization at the price shown. (If none is given, inquiry should be addressed to the BLL.)
- Avail: Fachinformationszentrum, Karlsruhe. Sold by the Fachinformationszentrum Energie, Physik, Mathematik GMBH, Eggenstein Leopoldshafen, Federal Republic of Germany, at the price shown in deutschmarks (DM).
- Avail: Issuing Activity, or Corporate Author, or no indication of availability. Inquiries as to the availability of these documents should be addressed to the organization shown in the citation as the corporate author of the document.
- Avail: U.S. Patent and Trademark Office. Sold by Commissioner of Patents and Trademarks, U.S. Patent and Trademark Office, at the standard price of 50 cents each, postage free.
- Avail: ESDU. Pricing information on specific data, computer programs, and details on ESDU topic categories can be obtained from ESDU International Ltd. Requesters in North America should use the Virginia address while all other requesters should use the London address, both of which are on page vii.
- Other availabilities: If the publication is available from a source other than the above, the publisher and his address will be displayed entirely on the availability line or in combination with the corporate author line.

GENERAL AVAILABILITY

All publications abstracted in this bibliography are available to the public through the sources as indicated in the *STAR Entries* and *IAA Entries* sections. It is suggested that the bibliography user contact his own library or other local libraries prior to ordering any publication inasmuch as many of the documents have been widely distributed by the issuing agencies, especially NASA.

v

PUBLIC COLLECTIONS OF NASA DOCUMENTS

DOMESTIC: NASA and NASA-sponsored documents and a large number of aerospace publications are available to the public for reference purposes at the library maintained by the American Institute of Aeronautics and Astronautics, Technical Information Service, 555 West 57th Street, 12th Floor, New York, New York 10019.

EUROPEAN: An extensive collection of NASA and NASA-sponsored publications is maintained by the British Library Lending Division, Boston Spa, Wetherby, Yorkshire, England for public access. The British Library Lending Division also has available many of the non-NASA publications cited in *Star*. European requesters may purchase facsimile copy or microfiche of NASA and NASA-sponsored documents, those identified by both the symbols # and * from ESA - Information Retrieval Service European Space Agency, 8-10 rue Mario-Nikis, 75738 Paris CEDEX 15, France.

FEDERAL DEPOSITORY LIBRARY PROGRAM

In order to provide the general public with greater access to U.S. Government publications, Congress established the Federal Depository Library Program under the Government Printing Office (GPO), with 50 regional depositories responsible for permanent retention of material, inter-library loan, and reference services. Over 1,300 other depositories also exist. A list of the regional GPO libraries appears on the inside back cover.

;

ADDRESSES OF ORGANIZATIONS

American Institute of Aeronautics and Astronautics Technical Information Service 555 West 57th Street, 12th Floor New York, New York 10019

British Library Lending Division, Boston Spa, Wetherby, Yorkshire, England

Commissioner of Patents and Trademarks U.S. Patent and Trademark Office Washington, D.C. 20231

Department of Energy Technical Information Center P.O. Box 62 Oak Ridge, Tennessee 37830

ESA-Information Retrieval Service ESRIN Via Galileo Galilei 00044 Frascati (Rome) Italy

ESDU International, Ltd. 1495 Chain Bridge Road McLean, Virginia 22101

ESDU International, Ltd. 251-259 Regent Street London, W1R 7AD, England

Fachinformationszentrum Energie, Physik, Mathematik GMBH 7514 Eggenstein Leopoldshafen Federal Republic of Germany

Her Majesty's Stationery Office P.O. Box 569, S.E. 1 London, England

NASA Scientific and Technical Information Facility P.O. Box 8757 B.W.I. Airport, Maryland 21240 National Aeronautics and Space Administration Scientific and Technical Information Branch (NIT-1) Washington, D.C. 20546

National Technical Information Service 5285 Port Royal Road Springfield, Virginia 22161

Pendragon House, Inc. 899 Broadway Avenue Redwood City, California 94063

Superintendent of Documents U.S. Government Printing Office Washington, D.C. 20402

University Microfilms A Xerox Company 300 North Zeeb Road Ann Arbor, Michigan 48106

University Microfilms, Ltd. Tylers Green London, England

U.S. Geological Survey Library National Center – MS 950 12201 Sunrise Valley Drive Reston, Virginia 22092

U.S. Geological Survey Library 2255 North Gemini Drive Flagstaff, Arizona 86001

U.S. Geological Survey 345 Middlefield Road Menlo Park, California 94025

U.S. Geological Survey Library Box 25046 Denver Federal Center, MS 914 Denver, Colorado 80225

NTIS PRICE SCHEDULES

Schedule A

STANDARD PAPER COPY PRICE SCHEDULE

(Effective January 1, 1983)

Price Code	Page Range	North American	Foreign
C000		FTICO	Price
A01	Microfiche	\$ 4.50	\$ 9.00
A02	001-025	7.00	14.00
A03	026-050	8.50	17.00
A04	051-075	10.00	20.00
A05	07 6 -100	11.50	23.00
A06	101-125	13.00	26.00
A07	126-150	14.50	29.00
808	151-175	16.00	32.00
A09	176-200	17.50	35.00
A10	201-225	19.00	38.00
A11	226-250	20.50	41.00
A12	251-275	22.00	44.00
A13	276-300	23.50	47.00
A14	301-325	25.00	50.00
A15	326-350	26.50	53.00
A16	351-375	28.00	56.00
A17	376-400	29.50	59.00
A18	401-425	31.00	62.00
A19	426-450	32.50	65.00
A20	451-475	34.00	68.00
A21	476-500	35.50	71.00
A22	501-525	37.00	74.00
A23	526-550	38.50	77.00
A24	551-575	40.00	80.00
A25	576-600	41.50	83.00
A99	601-up	- 1	2

1/ Add \$1.50 for each additional 25 page increment or portion thereof for 601 pages up.

2/ Add \$3.00 for each additional 25 page increment or portion thereof for 601 pages and more.

Schedule E

EXCEPTION PRICE SCHEDULE

Paper Copy & Microfiche

Price	North American	Foreign
Code	Price	Price
E01	\$ 6.50	\$ 13.50
E02	7.50	15.50
E03	9.50	19.50
E04	11.50	23.50
E05	13.50	27.50
E06	15.50	31.50
E07	17.50	35.50
E08	19.50	39.50
E09	21.50	43.50
E10	23.50	47.50
E11	25.50	51.50
E12	28.50	57.50
E13	31.50	63.50
E14	34.50	69.50
E15	37.50	75.50
E16	40.50	81.50
E17	43.50	88.50
E18	46.50	93.50
E19	51.50	102.50
E20	61.50	123.50

E-99 - Write for quote

N01

.

45.00

35.00

TABLE OF CONTENTS

Page

Category 01	Aeronautics (General)	199
Category 02 Include surface	Aerodynamics s aerodynamics of bodies, combinations, wings, rotors, and control s; and internal flow in ducts and turbomachinery.	204
Category 03 Include	Air Transportation and Safety s passenger and cargo air transport operations; and aircraft accidents.	240
Category 04 Include (satellit	Aircraft Communications and Navigation s digital and voice communication with aircraft; air navigation systems e and ground based); and air traffic control.	244
Category 05 Include	Aircraft Design, Testing and Performance s aircraft simulation technology.	246
Category 06 Include	Aircraft Instrumentation s cockpit and cabin display devices; and flight instruments.	258
Category 07 Include engines	Aircraft Propulsion and Power s prime propulsion systems and systems components, e.g., gas turbine and compressors; and on-board auxiliary power plants for aircraft.	262
Category 08 Include	Aircraft Stability and Control s aircraft handling qualities; piloting; flight controls; and autopilots.	268
Category 09 Include wind tu	Research and Support Facilities (Air) s airports, hangars and runways; aircraft repair and overhaul facilities; nnels; shock tube facilities; and engine test blocks.	272
Category 10 Include facilities spaced and pe power.	Astronautics s astronautics (general); astrodynamics; ground support systems and s (space); launch vehicles and space vehicles; space transportation; raft communications, command and tracking; spacecraft design, testing formance; spacecraft instrumentation; and spacecraft propulsion and	279
Category 11 Include and pl propella	Chemistry and Materials s chemistry and materials (general); composite materials; inorganic nysical chemistry; metallic materials; nonmetallic materials; and ants and fuels.	280

Category 12 Engineering Includes engineering (general); communications; electronics and electrical engineering; fluid mechanics and heat transfer; instrumentation and photography; lasers and masers; mechanical engineering; quality assurance and reliability; and structural mechanics.	285
Category 13 Geosciences Includes geosciences (general); earth resources; energy production and conversion; environment pollution; geophysics; meteorology and climatology; and oceanography.	298
Category 14 Life Sciences Includes sciences (general); aerospace medicine; behavioral sciences; man/ system technology and life support; and planetary biology.	N.A.
Category 15 Mathematics and Computer Sciences Includes mathematical and computer sciences (general); computer operations and hardware; computer programming and software; computer systems; cybernetics; numerical analysis; statistics and probability; systems analysis; and theoretical mathematics.	300
Category 16 Physics Includes physics (general); acoustics; atomic and molecular physics; nuclear and high-energy physics; optics; plasma physics; solid-state physics; and thermodynamics and statistical physics.	303
Category 17 Social Sciences Includes social sciences (general); administration and management; documentation and information science; economics and cost analysis; law and political science; and urban technology and transportation.	307
Category 18 Space Sciences Includes space sciences (general); astronomy; astrophysics; lunar and planetary exploration; solar physics; and space radiation.	N.A .
Category 19 General	309
Subject Index	A- 1
Personal Author Index	B -1

Personal Author Index	D-1
Corporate Source Index	C-1
Foreign Technology Index	D-1
Contract Number Index	E-1
Report Number Index	F-1
Accession Number Index	G-1

.

TYPICAL CITATION AND ABSTRACT FROM STAR

NASA SPONSORED		
DOCUMENT		AVAILABLE ON MICROFICHE
NASA ACCESSION	> N85-10007*# Boeing Commercial Airplane Co., Seattle, Wash	— — —
NUMBER	> DEVELOPMENT AND APPLICATIONS OF ALGORITHMS FOR CALCULATING THE TRANSONIC FLOW ABOUT	CORPORATE SOURCE
	HARMONICALLY OSCILLATING WINGS	
	F. E. EHLERS, W. H. WEATHERILL, and E. L. YIP Oct. 1984	
	152 p rets	
AUTHORS	Contract NAS1-16297)	DATE
	(NASA-CH-1/2376; NAS 1.26:172376) Avail: NTIS HC A08/MF	
CONTRACT	A01 CSCL 01A ←	
OR GRANT-	A finite difference method to solve the unsteady transonic flow	
	about harmonically oscillating wings was investigated. The	SOUNCE
	procedure is based on separating the velocity potential into steady	
REPORT	and unsteady parts and linearizing the resulting unsteady differential	COSATI
NUMBER	equation for small disturbances. The differential equation for the	CODE
	unsteady velocity potential is linear with spatially varying coefficients	0052
	and with the time variable eliminated by assuming harmonic motion.	
	An alternating direction implicit procedure was investigated, and a	
	pilot program was developed for both two and three dimensional	
	wings. This program provides a relatively efficient relaxation solution	
	without previously encountered solution instability problems.	
	Pressure distributions for two rectangular wings are calculated.	
	Conjugate gradient techniques were developed for the asymmetric,	
	indefinite problem. The conjugate gradient procedure is evaluated	
	for applications to the unsteady transonic problem. Different	
	equations for the alternating direction procedure are derived using	
	a coordinate transformation for swept and tapered wing planforms.	
	Pressure distributions for swept untaped wings of vanishing	
	thickness are correlated with linear results for sween angles up	
	to 15 degreese	

TYPICAL CITATION AND ABSTRACT FROM IAA

		MICROFICHE
	► A85-18511*# Virginia Polytechnic Inst. and State Univ.	
AIAA ACCESSION	Blacksburg	
NUMBER	A VORTEX-LATTICE METHOD FOR GENERAL UNSTEADY	
AUTHORS	NAVEEH and L. WATSON (Virginia Polytophaia Institute and State -	
AUTHORS	Harren, and L. WATSON (Virginia Polytechnic institute and State	AUTHOR'S
P	University, Blacksburg, VA) Journal of Aircraft (ISSN 0021-8669),	AFFILIATION
	vol. 22, Jan. 1985, p. 43-49. rets	
TITLE OF	(Contract N00014-79-C-0103; NSG-1262)	
PERIODICAL	A general method of calculating unsteady, incompressible,	
	inviscid, three-dimensional flows around arbitrary planforms has	DATE
	been developed. The method is an extension of the vortex-lattice	
	technique. It is not limited by aspect ratio, camber, or angle of	
	attack as long as vortex breakdown does not occur above the	
	surface of the wing and separation occurs only along sharp edges	
	As the wing performs arbitrary manouvers, the position of the	
	As the wing performs arbitrary maneuvers, the position of the	
	wake and the distribution of circulation on the wing and in the	
	wake are obtained as functions of time. One desirable feature of	
	the present method is its ability to treat steady lifting flows very	
	efficiently. Several examples of steady and unsteady flows are	
	presented. These include rectangular wings, with and without flaps,	
	delta, and cropped delta wings. Author	

AERONAUTICAL ENGINEERING

A Continuing Bibliography (Suppl. 187)

MAY 1985

01

AERONAUTICS (GENERAL)

A35-19658*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

CALCULATION OF THE EXCHANGE RATIO FOR THE ADAPTIVE MANEUVERING LOGIC PROGRAM

F. NEUMAN and H. ERZBERGER (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p.

(AIAA PAPER 85-0311)

Improvements were made to the Adaptive Maneuvering Logic (AML) computer program, a computer-generated, air-to-air combat opponent. The primary improvement was incorporating a measure of performance, the exchange ratio, defined as the statistical measure of number of enemy kills divided by number of friendly losses. This measure was used to test a new modification of the AML's combat tactics. When the new version of the AML competed against the old version, the new version won with an exchange ratio of 1.4.

A85-19812

COMBAT AIRCRAFT: FLIGHT VEHICLES, POWER PLANTS, AND THEIR MAINTENANCE [BOEVAIA AVIATSIONNAIA TEKHNIKA: LETATEL'NYE APPARATY, SILOVYE USTANOVKI I IKH EKSPLUATATSIIA]

V. F. PAVLENKO, A. A. DIACHENKO, V. I. ZHULEV, B. K. KOLPAKOV, A. P. NAZAROV, and V. A. TIKHONRAVOV Moscow, Voennoe Izdatel'stvo, 1984, 320 p. In Russian. refs

The book covers the aerodynamics and flight dynamics of aircraft, the design of combat airplanes and helicopters, aircraft engines, and ground support services. Specific topics discussed include aircraft stability and control, flight characteristics of helicopters, the design of the airframe, take-off and landing gear, hydraulic and pneumatic systems, aircraft control systems, and fuel systems. The main design features, performance characteristics, and limitations of gas-turbine, turbojet, turboramjet, and bypass engines are examined. Attention is also given to maintenance and repair of aircraft, aircraft reliability, and aviation fuels and lubricants.

A85-20057

ADVANCED HELICOPTER TECHNOLOGY - INDUSTRY GIRDS FOR CHALLENGES OF EVOLVING OPERATIONAL NEEDS

Aviation Week and Space Technology (ISSN 0005-2175), vol. 122, Jan. 14, 1985, p. 40-43, 45, 46.

Military programs that are setting the pace of technology development for the helicopter industry are the 'JVX' joint services vertical lift aircraft and the U.S. Army's 'LHX' advanced scout/attack/utility helicopter. Much of the powerplant, drivetrain, airframe materials and structures, control system and avionics technologies developed to meet the requirements stipulated by these military programs will be applied to the design of commercial rotorcraft, which are expected to demand lower weights and costs and higher speeds and efficiencies than are currently available. Day/night, all-weather capabilities for commercial aircraft will also be predicated on military technology developments. Attention is given to multicompany development and construction arrangements, as well as to the requirements of NATO's European nations. O.C.

A85-20451

CURRENT PROBLEMS IN AVIATION SCIENCE AND TECHNOLOGY [AKTUAL'NYE PROBLEMY AVIATSIONNOI NAUKI I TEKHNIKI]

V. Z. PARTON, ED. Moscow, Izdatel'stvo Mashinostroenie, 1984, 280 p. In Russian. For individual items see A85-20452 to A85-20479.

Various aspects of aircraft structural design are examined. Particular attention is given to the use of plate and shell theory in determining the optimal parameters of aircraft structural elements; the mechanical properties and fracture processes of aircraft construction materials; the fatigue life of metals under multicycle loading; fabrication-related stresses and strains in reinforced plastics; and the properties of composite materials used in aircraft design. The application of CAD systems to aircraft design is considered in detail.

A85-20453

COMPUTERS AND PROGRESS IN AVIATION [EVM | PROGRESS AVIATSII]

S. M. BELOTSERKOVSKII IN: Current problems in aviation science and technology. Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 15-28. In Russian. refs

The impact of advanced computer technology on aviation is examined. Particular attention is given to the use of computers in the development of: active aircraft control; the anticipatory operation of mathematical models of aircraft; linear aeroelasticity and nonlinear aerodynamics calculations; and identification based on complete a priori information. Examples illustrating the numerical-experiment methodology are given. B.J.

A85-20455

TRAINING AND RESEARCH CAD SYSTEM OF THE MOSCOW AVIATION INSTITUTE AND EXPERIENCE IN ITS USE [UCHEBNO-ISSLEDOVATEL'SKAIA SAPR MOSKOVSKOGO AVIATSIONNOGO INSTITUTA I OPYT EE PRIMENENIIA]

I. T. BELIAKOV IN: Current problems in aviation science and technology . Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 37-44. In Russian.

The set of problems that were considered and solved in the development of the training and research CAD system of the Moscow Aviation Institute is described. Particular emphasis is placed on the development of a system nucleus which is an invariant software-informational subsystem of the CAD system, providing for the efficient operation of the problem-oriented subsystems. First results in the use of this CAD system in training processes are presented, and the use of this system for aircraft design is examined.

A85-20466

SOME PROBLEMS IN THE DEVELOPMENT OF CAD SYSTEMS [O NEKOTORYKH VOPROSAKH RAZRABOTKI SAPR]

I. IA. LANDAU and B. N. NAUMOV IN: Current problems in aviation science and technology Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 142-148. In Russian.

Various problems involved in the development of computer-aided design (CAD) systems are examined using a CAD system for the development of the digital components of minicomputers as an example. The architecture of the CAD system and the tasks it can perform are discussed. In particular, attention is given to the principal functions of the CAD data bank and the software of the technical design subsystem. V.L.

A85-21382

TOOLING PROBLEMS IN THE MANUFACTURE OF AH-64 COMPOSITES FLEXBEAM TAIL ROTOR

R. A. LOFLAND (Hughes Helicopters, Inc., Culver City, CA) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983. Washington, DC, American Helicopter Society, 1984, 4 p.

Initial manufacturing efforts for the AH-64 Apache helicopter's Composite Flexbeam Tail Rotor encountered unique tooling and fabrication problems associated with a design configuration that simultaneously required extreme flexibility and torsional strength at the flexbeam pitch-case juncture, where a high strength bond was required to allow blade pitch variation. The thermal expansion of silicon rubber was used as the basis of a process that would generate sufficient external bonding pressures at the juncture, as well as over most of the junction of the pitch cases. O.C.

A85-21394

FABRICATION AND ASSEMBLY OF COMPOSITE REAR FUSELAGE (CRF) TOOLING AND MANUFACTURING FOR THE UH-60 HELICOPTER

D. G. ORLINO (U.S. Army, Applied Technology Laboratory, Fort Eustis, VA) and G. JACARUSO (United Technologies Corp., Sikorsky Aircraft Div., Stratford, CT) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983 Washington, DC, American Helicopter Society, 1984, 15 p.

Advanced manufacturing methods have been used to reduce the parts count of a composite rear fuselage assembly for the UH-60 helicopter, which is 38 percent more economical to manufacture and 10 percent lighter than its metallic counterpart. In particular, the method employed to fabricate the steel shell molds for the composite structure proved to be less expensive than state-of-the-art fiberglass/epoxy molds. A practical size limit has been reached in molding the lower rear fuselage skin panels, due to tooling complexities. Precutting, preplying and preforming outside of the molds has proved to be a cost-effective way of handling the thousands of individual plies. The composite structure has passed both static testing to limit and ultimate loading tests. O.C.

A85-21456 DESIGN AND ADVANCED CONCEPTS OF AVIONICS/WEAPONS SYSTEM INTEGRATION; PROCEEDINGS OF THE SYMPOSIUM, LONDON, ENGLAND, APRIL 3, 4, 1984 Symposium sponsored by the Royal Aeronautical Society. London, Royal Aeronautical Society, 1984, 96 p. For individual items see A85-21457 to A85-21467.

Among the topics discussed are software design methods for advanced military avionics, a design methodology for integrated avionics, hardware design techniques, packaging and interconnection practices for avionics, integrated navigation systems, and aspects of the man-machine interface in military aircraft. Also covered are flight-critical phases of the man-machine interface; trends in both digital flight control and digital engine control system designs, and integrated avionics for helicopters.

A85-21680

ADVANCED TECHNOLOGY - THE KEY TO EUROPEAN COMPETITIVENESS

J. K. W. THOMAS (Airbus Industrie, Blagnac, Haute-Garonne, France) Aeronautical Society of South Africa and South African Institute of Aeronautical Engineers, Journal (ISSN 0250-3786), vol. 5, no. 1, 1984, p. 35-40.

Attention is given to the technology development aspects of the Airbus Industrie consortium's competitiveness as an airliner manufacturer. Efforts in novel technology integration have led to the refinement of the A300 aircraft into its A300-600, A310-300, and A320 variants by incorporating advanced cockpit display and control systems, lateral control improvements (through low speed aileron deletion), weight savings through structural innovations, center-of-gravity control management, fly-by-wire systems, load alleviation control features, and variable camber wing profile control. O.C.

A85-22226#

TRENDS IN CIVIL AIRCRAFT DESIGN

P. SMITH and A. STEPHENSON (British Aerospace, PLC, Aircraft Group, Hatfield, Herts., England) Aeronautical Society of India, Journal (ISSN 0001-9267), vol. 36, May 1984, p. 69-94.

Future trends in fixed-wing aircraft design are forecast in a 17-year timeframe, based on a statistical study of past developments. Among the aspects studied are: safety, environmental considerations, flexibility, fuel efficiency, economics and structures reliability and weight contribution. Furthermore, the benefits of the implementation of Al-Cu and Al-Zn alloys and fiber-reinforced composites are considered with respect to the strength and weight of wing structures. Finally, recent, as well as planned, advances in flight control systems, such as the digital Automatic Flight Control System and fly-by-wire controls, are reviewed.

N85-15658*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

TEMPERATURE DISTORTION GENERATOR FOR TURBOSHAFT ENGINE TESTING

G. A. KLANN, R. L. BARTH, and T. J. BIESIADNY Dec. 1984 34 p refs Presented at the SAE Aerospace Congr. and Exposition, Long Beach, Calif., 15-18 Oct. 1984

(NAŠA-TM-83748; USAAVSCOM-TR-84-C-12; E-2197; NAS

1.15:83748) Avail: NTIS HC A03/MF A01 CSCL 01B

The procedures and unique hardware used to conduct an experimental investigation into the response of а small-turboshaft-engine compression system to various hot gas ingestion patterns are presented. The temperature distortion generator described herein uses gaseous hydrogen to create both steady-state and time-variant, or transient, temperature distortion at the engine inlet. The range of transient temperature ramps produced by the distortion generator during the engine tests was from less than 111 deg K/sec (200 deg R/sec) to above 611 deg K/sec (1100 deg R/sec); instantaneous temperatures to 422 deg K (760 deg R) above ambient were generated. The distortion generator was used to document the maximum inlet temperatures and temperature rise rates that the compression system could tolerate before the onset of stall for various circumferential distortions as well as the compressor system response during stall. Author

N85-15659# Air Force Inst. of Tech., Wright-Patterson AFB, Ohio. School of Systems and Logistics.

UNITED STATES AIR FORCE AIRCRAFT MODIFICATION PROCESS: A SYSTEM DYNAMICS ANALYSIS M.S. Thesis

R. BAILEY and H. F. STALCUP Sep. 1984 232 p

(AD-A146954; AFIT/GSM/LSY/84S-2) Avail: NTIS HC A11/MF A01 CSCL 01C

A conceptual model of the Air Force aircraft modification process was developed and validated in this thesis. The model was designed using the system dynamics technology and is a tool to extend the knowledge and understanding of the decision and policy-makers within the modification process. Sources of

information used in the development of the model included both literature research and personal interviews. The personal interviews were conducted with Air Force, DOD, OMB, and Congressional people active in the aircraft modification process. Five key issues concerning the behavior of the system were identified and detailed. These issues were: the lack of a systems approach to modification management, the absence of a Class IV requirements approval process, the difficulties of management split between AFSC and AFLC, the priority ranking of modifications by the financial community, and the weaknesses of the process which are currently overcome by strong individuals. Five recommendations for change to the modification process were presented. The recommendations were to establish a requirements review, approval, and ranking process for Class IV modifications, encourage a systems approach to management, improve the credibility and understanding of the process, and encourage competition by several means. GRA

N85-15660# Air Force Inst. of Tech., Wright-Patterson AFB, Ohio. School of Systems and Logistics.

PERFORMANCE EVALUATION OF A-10 AIRCRAFT MAINTEANCE UNITS AND AIRCRAFT USING CONSTRAINED FACET ANALYSIS M.S. Thesis

V. J. GONNERMAN Sep. 1984 75 p

(AD-A146955; AFIT/GLM/LSM/84S-26) Avail: NTIS HC A04/MF A01 CSCL 15E

Performance evaluation is required to obtained important feedback on system efficiency for management decision making. For Air Force aircraft maintenance managers, performance evaluation is crucial for determining capability and evaluating unit efficiency and effectiveness. This thesis effort applied Constrained Facet Analysis (CFA), a linear fractional programming technique, to the performance evaluation of aircraft maintenance units (AMUs) and aircraft. Empirical data for three AMUs covering a five month period of time and simulated data for 28 aircraft was evaluated using the CFA and Data Envelopment Analysis (DEA) computer programs at the University of Texas. Results show that CFA and DEA can be used to evaluate relative efficiency of Air Force units. GRA

N85-15661# Naval Ship Research and Development Center, Bethesda, Md.

CIRCULATION CONTROL: A BIBLIOGRAPHY OF DTNSRDC RESEARCH AND SELECTED OUTSIDE REFERENCES: UPDATE Research and Development Report, Jan. 1969 - Dec. 1983 R. J. ENGLAR and C. A. APPLEGATE Sep. 1984 55 p

(AD-A146966; AERO-1291; DTNSRDC-84/052) Avail: NTIS HC A04/MF A01 CSCL 05B

This report is an update of a previously published bibliography (Report 77-0076) of formal reports, departmental reports, and technical papers by personnel of the Aviation and Surface Effects Dept., David W. Taylor Naval Ship Research and Development Center. Included are publications for the period of January 1969 through December 1983. The citations are arranged chronologically and represent the development of circulation control technology at the Center over the past several years. Selected outside references pertinent to circulation control are presented in the appendix. Originator - supplied keywords include: Circulation control aerodynamics, Blown flaps, Boundary layer control, Bluff airfoils, Critical Mach number, Elliptic airfoils, Finite wing, Helicopter Rotor, Helicopter Rotor Airfoil, High Advance Ratios, High-Lift Systems, Hover Performance, Jet Flaps, Subsonic Wind Tunnel, STOL Aircraft, Tangential Blowing, and V/STOL Aircraft. GRA

N85-15662#Air Force Inst. of Tech., Wright-Patterson AFB,
Ohio. School of Systems and Logistics.PARAMETRICESTIMATESOFPROPULSIONSYSTEM

PARAMETRIC ESTIMATES OF PROPULSION SYSTEM MAINTENANCE MANHOURS M.S. Thesis

T. J. SHARP Sep. 1984 97 p (AD-A147120; AFIT/GLM/LSM/84S-57) Avail: NTIS HC A05/MF A01 CSCL 01C

This thesis investigated the potential of using cost-estimating relationships (CERs) to estimate aircraft maintenance manhour requirements for propulsion systems. The performance specifications and physical parameters of a large sample of USAF turbine engines were used to develop CERs. These CERs could be applied early in the life cycle of an engine in acquisition in order to estimate future maintenance requirements and effect design configuration changes. The analysis was accomplished by the method of linear regression analysis of least squares. The CERs resulting from the regression were subjected to three tests to determine their predictive capability. A number of the CERs developed in the study displayed sufficient accuracy to be considered for application on acquisition programs. GRA

N85-15663# Air Force Inst. of Tech., Wright-Patterson AFB, Ohio. School of Systems and Logistics.

A Q-GERT NETWORK SIMULATION MODEL FOR EXAMINING PIPELINE TIME IN THE NAVY'S J-52 INTERMEDIATE LEVEL JET ENGINE REPAIR CYCLE M.S. Thesis

M. N. ROMERO Sep. 1984 152 p

(AD-A147269; AFIT/GLM/LSM/84S-56) Avail: NTIS HC A08/MF A01 CSCL 15E

Recent data suggest that the actual turnaround time (TAT) for the J-52 engine is almost four times the standard specified by the directive. One approach to investigating this excessive time in the pipeline is to examine the operation of the repair system, focussing attention on the utilization of resources. The objective of this project was, therefore, to develop a computer simulation model which replicates the J-52 intermediate level repair cycle, concentrating on repair crews, workstands, and test cells as the major resources employed. A hypothetical scenario based on contrived parameters was developed in order to convert the model to code and demonstrate its application on the computer. The results of a sample simulation show that excessive rapair backlogs and delays as well as inefficient resource utilization can, in fact, be identified in the output, thereby paving the way for management to experiment with different resource utilization schemes in order to achieve a lower TAT. GRA

N85-15664# Advisory Group for Aerospace Research and Development, Neuilly-Sur-Seine (France). OPERATIONAL LOADS DATA

Loughton, England Aug. 1984 303 p refs In ENGLISH and FRENCH Conf. held in Sienna, Italy, 2-6 Apr. 1984

(AGARD-CP-375; ISBN-92-835-0363-5) Avail: NTIS HC A14/MF A01

General principles followed in acquiring data on operational loads sustained by NATO aircraft, both fixed and rotary wing, in normal service were examined. Current and developing loads data acquisition programs were compared. The techniques used and data obtained from work on a variety of aircraft types were reported; microprocessor-based systems were seen as providing the essential technology for major advances in this field. Although the main emphasis was on fatigue loads, the acquisition of design loads data was also discussed, together with the validity of current data bases for loads calculations on high-agility designs representative of the next generation of combat aircraft.

N85-16731# Advisory Group for Aerospace Research and Development, Neuilly-Sur-Seine (France).

DESIGN FOR TACTICAL AVIONICS MAINTAINABILITY

Loughton, England Oct. 1984 281 p refs in ENGLISH and FRENCH Conf. held in Brussels, 7-10 May 1984

(AGARD-CP-361; ISBN-92-835-0366-10) Ávail: NTIS HC A13/MF A01

Advanced methods and tools to support design for avionic maintainability and testability are discussed. Both hardware and software design for maintainability issues and approaches are addressed.

N85-16732# Breguet-Aviation, Saint Cloud (France).

OBJECTIVES IN STUDYING THE MAINTAINABILITY OF AIRCRAFT SYSTEMS [OBJECTIFS D'ETUDE DE LA MAINTENABILITE DES SYSTEMES AVIONNES]

M. COURTOIS In AGARD Design for Tactical Avionics Maintainability 10 p Oct. 1984 refs In FRENCH Avail: NTIS HC A13/MF A01

Increased use of electronic equipment in combat aircraft results in an increased cost of avionics and of the total purchase price of aircraft. The maintenance of more numerous, more complex, and more costly electronic systems involves maintenance methods which are themselves both numerous and complex. Given the very important acquisition costs of future systems (supplies and replacements will be limited), the maintenance of electronic systems will be an essential function in assuring the maximum operational availability of aircraft. System costs must be reduced to allow for troubleshooting and the verification of aircraft equipment. Different levels of maintenance are analyzed using solutions developed for the Mirage aircraft. Specifications for the maintainability of all equipment, at all levels of maintenance must be established as a function of system architecture and the tests to be conducted. These specifications must be considered from the beginning of prototype equipment study. Transl. by A.R.H.

N85-16734# STTE, Paris (France).

THE EMBEDDED TEST (BIT): IMPACT ON THE TOTAL COST OF POSSESSION [TEST INTEGRE (BIT): IMPACT SUR LE COUT GLOBAL DE POSSESSION]

I. M. KERVELLA *In* AGARD Design for Tactical Avionics Maintainability 4 p Oct. 1984 refs In FRENCH Avail: NTIS HC A13/MF A01

The application of an embedded (built-in) test to digital systems is analyzed. Technical and operational aspects of such tests are discusserd and their characteristics as experienced by the French Air Force, are described. The total cost of having built-in tests comprises development, purchase, and operational costs. Results show that the cost of acquiring an embedded test is lightly increased, but is sharply diminished with respect to the cost of acquiring the on-line test formerly used. The cost of using the test should be likewise lower. By taking into consideration the observed operational results, the choice of the embedded test is shown to be satisfactory with respect to service rendered and cost. Transl. by A.R.H.

N85-16735# Aeritalia S.p.A., Torino (Italy). STUDY AND REALISATION OF A 3RD LEVEL MAINTENANCE CENTER BASED ON ATE SYSTEMS UTILIZATION

F. BOZZOLA *In* AGARD Design for Tactical Avionics Maintainability 7 p Oct. 1984

Avail: NTIS HC A13/MF A01

The development of the actual working program for the realisation of a 3rd level maintenance center for the avionics electronics modules of the MRCA Tornado aircraft is discussed. Starting from the initial requirement and from the primary goals of the program, and going through the different study and data collection phases, the adopted general criteria for the definition of the technical characteristics and quantities of the automatic test equipment to be used are described taking into account the testability problems shown by the different electronic boards to be maintained; problems connected with the boards available documentation are also measured. All the problems related to the management, installation, programming, interfacing, expandability and flexibility of the adopted automatic test equipment are discussed. In addition, using the actual maintenance problems faced during the activity development as a starting point, some general maintainability criteria that can be taken into account for similar future programs are outlined. Author

N85-16737# STTE, Paris (France).

ATE USER'S VIEW ON DESIGN FOR MAINTAINABILITY

J. M. G. B. MASCARENHAS *In* AGARD Design for Tactical Avionics Maintainability 16 p Oct. 1984 refs Avail: NTIS HC A13/MF A01

The main features of the Automatic Test Equipment (ATE) that PoAF is using are described. The hardware and software capabilities and limitations are emphasized. Techniques available for test program generation and validation are examined. Views on board design for maintainability (particularly with TE) are presented. B.W.

N85-16739# Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West Germany).

BUILT-IN-TEST FOR FIRST LINE TESTING

W. R. H. BEHM In AGARD Design for Tactical Avionics Maintainability 7 p Oct. 1984

Avail: NTIS HC A13/MF A01

Built-In-Test requirements were established more than a decade ago to give the maintenance personnel at flight line a help for diagnosis tasks. The prospect of new technology offered automatic, quick, accurate, effective and easy interpretable GO/NOGO information of Line Replaceable Units with built-in self test (BIT) facilities. Typical design goals were: (1) Detection and location of defects down to LRU level with 80% probability and a 90% confidence level at minimum time, and (2) Defective LRUs shall automatically be identified on a Central Maintenance Panel. Whereas the general line of requirements were followed through, some problems occured, which influenced the final results. These problems are briefly: (1) false alarm probability is higher than was expected; (2) BIT capabilities are less than specified; and (3) BIT is not totally independent of operators interpretation. On the basis of experience gathered during the development of BIT these problems and their reasons were analyzed. B.W.

N85-16740# National Aerospace Lab., Amsterdam (Netherlands). FUNCTIONAL BUILT-IN-TEST IN A PIPELINED IMAGE

FUNCTIONAL BUILT-IN-TEST IN A PIPELINED IMAGE PROCESSOR

H. A. VANINGEN SCHENAU, A. PLEIJSIER, and A. MONKEL *In* AGARD Design for Tactical Avionics Maintainability 8 p Oct. 1984

Avail: NTIS HC A13/MF A01

A method for built-in-test (BIT) is described which is applied to the test of function modules of a pipeline image processor. The built-in-test is used as a support tool during the early stages of development and for integration and maintenance. The test method takes advantage of the microprocessors used to interface and control the processor modules. Test programs are inserted in the microprocessor software to test the image processor functionally with a similar data and control flow as in real-time operation. The result is a number of test picture which can be interpreted in relation to the programmed functions of the image processing. Use is made of the 2-dimensional image formats to check the performance of the unit at one glance for several functions and parameter values.

N85-16743# AEG-Telefunken, Ulm (West Germany). MAINTAINABILITY: AN ILS EFFORT TO MANIPULATE LCC M. BOEHM *In* AGARD Design for Tactical Avionics Maintainability 15 p Oct. 1984 refs

Avail: NTIS HC A13/MF A01

The concept of maintainability is discussed. The importance of maintainability in controling the life cycle costs of avionics and radar equipment is evaluated. R.J.F.

N85-16745# LITEF, Freiburg (West Germany).

DOCUMENTATION AND SEPARATE TEST PROGRAM DEVELOPMENT IMPORTANT IS MOST FOR TEST/MAINTENANCE

B. GUSMANN and N. SANDNER In AGARD Design for Tactical Avionics Maintainability 11 p Oct. 1984 refs Avail: NTIS HC A13/MF A01

Well defined development phases with standardized documentations supported by computer based tools are important for test and maintenance. Systems for transport aircraft and military applications are discussed. Documentation is stressed throughout the life cycle and the independent testing. B.G.

N85-16752# Naval Electronic Systems Command, Washington, D. C.

A WEAPON SYSTEM DESIGN APPROACH TO DIAGNOSTICS G. W. NEUMANN (Giordano Associates, Inc., Arlington, Va.) and In AGARD Design for Tactical Avionics M. BATTAGLIA Maintainability 6 p Oct. 1984 refs

Avail: NTIS HC A13/MF A01

Providing a diagnostics capability for today's weapon systems requires a multifaceted combination of hardware, software, and personnel. The approach to providing this capability is fractionated among a number of different communities (e.g., testing, training, human engineering, publication writers). The result is reflected in the field, where the technician has been furnished a myriad of tools and documentation, which is confusing, complex and often contradictory. The result is lengthy repair times and a waste of manpower and dollars. The basic reason for this diagnostic deficiency is the lack of an integrated design approach to providing this capability and the inability to transition technological advancements to weapon systems acquisitions. Recent Department of Defense and U.S. industry efforts to solve this problem are discussed. R.S.F.

N85-16755# McDonnell Aircraft Co., St. Louis, Mo. AVIONICS FAULT TREE ANALYSIS AND ARTIFICAL INTELLIGENCE FOR FUTURE AIRCRAFT MAINTENANCE M. E. HARRIS and T. D. SNODGRASS In AGARD Design for

Tactical Avionics Maintainability 12 p Oct. 1984 refs Avail: NTIS HC A13/MF A01

The avionics fault tree analyzer (AFTA) was developed as an interim support tool for the Navy prior to attainment of total organic support capability, and as an alternate method of support to reduce life cycle/cost for F/A-18 foreign military sales. With the transformation of the AFTA concept from ground support equipment to avionics, a quantitative improvement in life cycle costs will be obtained through the application of artificial intelligence (AT) techniques. The AI is expected to see applications to practical problems in many disciplines; and one of which is the implementation of military fault diagnostic systems. A smart BIT was developed which will reduce false alarms, identify intermittent failures, and improve fault isolation to the lowest possible element by AI technique. Increasing density of computer memory, modularly designed avionic functions and the use of very large scale, and high speed integrated devices will allow future aircraft to fly with the AFTA function. Ramifications such as eliminating the need for intermediate avionic repair facilities, increased aircraft operational readiness, decrease in aircraft recurring costs, and a reduction in spares investment are discussed. The AFTA concept, life cycle cost advantages, and the implementation of artificial intelligence in future avionic designs relative to improved reliability and maintainability are summarized. E.A.K.

National Aeronautics and Space Administration. N85-16757*# Ames Research Center, Moffett Field, Calif.

MISSIONS AND VEHICLE CONCEPTS FOR MODERN, **PROPELLED, LIGHTER-THAN-AIR VEHICLES** M. D. ARDEMA Dec. 1984 48 p refs

(NASA-TM-86672; A-85077; NAS 1.15:86672) Avail: NTIS HC A03/MF A01 CSCL 01B

The results of studies conducted over the last 15 years to assess missions and vehicle concepts for modern, propelled, lighter-than-air vehicles (airships) were surveyed. Rigid and non-rigid airship concepts are considered. The use of airships for ocean patrol and surveillance is discussed along with vertical heavy lift airships. Military and civilian needs for high altitude platforms are addressed. RSE

N85-16758* National Aeronautics and Space Administration, Washington, D. C.

AERONAUTICAL **ENGINEERING:** A CONTINUING **BIBLIOGRAPHY WITH INDEXES (SUPPLEMENT 182)**

Jan. 1985 140 p

(NASA-SP-7037(182); NAS 1.21:7037(182)) Avail: NTIS HC \$6.00 CSCL 01A

This bibliography lists 475 reports, articles and other documents introduced into the NASA scientific and technical information system in December 1984. Author

N85-16759*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

COMPUTER SIZING OF FIGHTER AIRCRAFT

P. G. COEN and W. E. FOSS, JR. Jan. 1985 22 p Presented at 23rd AIAA Aerospace Sci. Meeting, Reno, Nev., 14-17 Jan. 1985

(NASA-TM-86351; NAS 1.15:86351) Avail: NTIS HC A02/MF A01 CSCL 01B

The computer sizing technique has been applied to a number of military mission profiles. Performance data can be determined for all segments of the selected profile, which typically include takeoff, climb, cruise, loiter, reserve and landing segments. Options are available for detailed calculation of combat performance and energy-maneuverability characteristics. Configuration changes, such as external fuel tank drop and weapon expenditure, can be included in the mission. In the sizing mode, aircraft gross weight, wing loading, and thrust-to-weight ratio are varied automatically to determine which combinations meet the design mission radius. The resulting performance data can be used to create a thumbprint plot. This plot is useful in determining the configuration size that best satisfies the mission and performance requirements. The sizing mode can also be used to perform parametric studies such as sensitivity of gross weight to alternate design conditions. Author

N85-16760# Federal Aviation Administration, Washington, D.C. Office of Management Systems.

FAA (FEDERAL AVIATION ADMINISTRATION) STATISTICAL HANDBOOK OF AVIATION, CALENDAR YEAR 1983 Annual Report

31 Dec. 1984 199 p (AD-A148171) Avail: NTIS HC A09/MF A01 CSCL 01B

This report presents statistical information pertaining to the Federal Aviation Administration, the National Airspace System, Airports, Airport Activity, U.S. Civil Air Carrier Fleet, U.S. Civil Air Carrier Operating Data, Airmen, General Aviation Aircraft, Aircraft Accidents, Aeronautical Production and Imports/Exports, and a Glossary of the terms used in this publication. Author (GRA)

N85-16761# Logistics Management Inst., Bethesda, Md. FORCE STOCK FUND THE AIR AND AIRCRAFT AVAILABILITY

C. H. HANKS Oct. 1984 63 p

(Contract MDA903-81-C-0166)

(AD-A148653; LMI-AF301-4) Avail: NTIS HC A04/MF A01 CSCL 15E

The methods and results of this work represent a first step in quantifying the relation between consumable parts and end-item readiness. This working note addresses the effect on aircraft availability rates if safety levels in the wholesale Air Force stock fund were to change. (Safety levels are the stock levels maintained to cover variations in demand.) The results are that as many as 150 additional aircraft, Air Force-wide, could become unavailable due to parts, if safety levels fell to the extent that wholesale fill rates dropped 5 points, from 85% to 80%. GRA

01 AERONAUTICS (GENERAL)

N85-16762# Air Force Systems Command, Wright-Patterson AFB, Ohio. Foreign Technology Div.

INTERNATIONAL AVIATION (SELECTED ARTICLES)

TONG, W. YE, Z. KEHAN, and Z. ZIQIAN 13 Nov. 1984 32 p Transl. into ENGLISH from Guoji Hang Kong (China), no. 254, Apr. 1984 p 13-19, 46-47

(AD-A148704; FTD-ID(RS)T-0969-84) Avail: NTIS HC A03/MF A01 CSCL 01A

Progress in international aerodynamic research is reported. The development of highly efficient supersonic and highly maneuverable fighter planes is predicted. The structure with forward swept wings has good maneuverability and low transonic drag. Transport aircrafts, V/STOL aircrafts, and fighter aircrafts were tested. Air jet propulsion technology and the development of target tracking display systems are described. E.A.K.

N85-16763# Joint Publications Research Service, Arlington, Va. USSR REPORT: TRANSPORTATION

15 Jan. 1985 193 p refs Transl. into ENGLISH from various Russian articles

(JPRS-UTR-85-001) Avail: NTIS HC A09/MF A01

Trends in the design of Soviet aircraft are explored as well as improvements in equipment for agricultural aircraft and in runway surfacing. An automated communication system for Aeroflot and a solution for the braking problems on theIL-76 aircraft are discussed.

N85-16764# Joint Publications Research Service, Arlington, Va. DIRECTOR ON INSTITUTE'S CIVIL AVIATION PROJECTS

R. SAKACH *In its* USSR Rept.: Transportation (JPRS-UTR-85-001) p 1-3 15 Jan. 1985 Transl. into ENGLISH from Vozdushnyy Transp. (Moscow), 30 Oct. 1984 p 2 Avail: NTIS HC A09/MF A01

Technologies being developed for the utilization of aircraft in land reclamation and in the use of reclaimed land for agriculture are discussed. The modernization and production of equipment for handling liquid and powered chemicals and biologicals for the An-2 and Ka-26 helicopter; the fitting of aircraft with accessories for cargo drop operations and transporting externally suspended materials; and systems for the aerial observation of crop conditions are needed to increase the nation's food supply. Capabilities of the Tu-134SKh (agricultural) aircraft for the nonphotographic mapping of the Earth's surface are described. A.R.H.

N85-16767# Joint Publications Research Service, Arlington, Va. INTERNATIONAL PROJECTS, OTHER WORK OF AEROPROYEKT INSTITUTE

V. BEREZIN *In its* USSR Rept.: Transportation (JPRS-UTR-85-001) p 9-11 15 Jan. 1985 Transl. into ENGLISH from Vozdushnyy Transp. (Moscow), 29 Sep. 1984 p 3 Avail: NTIS HC A09/MF A01

Soviet activities conducted towards implementing an agreement to cooperate in the development of international airports include working with: (1) Cuba to reconstruct the San Jose Marti International Airport; (2) Czechoslovakia to develop a device for evaluating runway surface braking conditions; (3) East Germany on a device for ground servicing of aircraft; (4) Canada on increasing aircraft safety and operational availability, modeling systems for a warning of ice formation, evaluating pavement uniformity, and designing a mobile air terminal; and (5) France on the design of construction methods, equipment, and operational techniques for aircraft. One result of this cooperation is the joint preparation of ICAO recommendations on fuel facility distribution and the development of devices for measuring the runway traction coefficient. A.R.H. **N85-16771#** Advisory Group for Aerospace Research and Development, Neuilly-Sur-Seine (France).

IMPROVEMENT OF AERODYNAMIC PERFORMANCE THROUGH BOUNDARY LAYER CONTROL AND HIGH LIFT SYSTEMS

Loughton (England) Aug. 1984 423 p refs In ENGLISH and FRENCH Conf. held in Brussels, 21-23 May 1984

(AGARD-CP-365; ISBN-92-835-0358-9) Avail: NTIS HC A18/MF A01

Theoretical and experimental developments are reported in the use of both traditional and non-traditional means of boundary layer control for external flow applications such as lift-augmentation, drag reduction and improved effectiveness of controls, and for internal flow applications such as air intakes and exit configurations. Techniques included shaping (geometry) suction and blowing transverse blowing; vortex generators; heating and cooling; and turbulent boundary layer manipulation. Boundary layer control on characteristics of wings and wing-body arrangements that involve flaps, slats and jets (blown flaps), and vortex flaps is covered.

N85-16797# Advisory Group for Aerospace Research and Development, Neuilly-Sur-Seine (France).

HELICOPTER GUIDANCE AND CONTROL SYSTEMS FOR BATTLEFIELD SUPPORT

Loughton, England Aug. 1984 284 p refs In ENGLISH and FRENCH Conf. held in Monterey, Calif., 8-11 May 1984

(AGARD-CP-359; ISBN-92-835-0365-1) Avail: NTIS HC A13/MF A01

Requirements and operational use of future helicopters; new methods of briefing helicopter crews and tactically setting up the mission systems before and during the flight, flight control, displays, communications, and navigation; sensors and weapon systems integration in overall cockpit design; and simulation and flight research are discussed.

N85-16798# Aerospace Engineering Test Establishment, Cold Lake (Alberta).

OPERATIONAL REQUIREMENTS VERSUS TECHNOLOGICAL CAPABILITIES

S. COYLE *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 9 p Aug. 1984 refs Avail: NTIS HC A13/MF A01

The lessons learned in the wartime use of helicopters, and the impact that modern technology can have on what have become common themes are discussed. Lessons learned, the constraints on helicopter operations, and the requirements of the battlefield helicopter are integrated to show where technology would better serve the operators. Performance monitoring, handling qualities and radio communications examples are presented, and a brief outline of how existing technology could be used to update an

02

Author

AERODYNAMICS

Includes aerodynamics of bodies, combinations, wings, rotors, and control surfaces; and internal flow in ducts and turbomachinery.

A85-19260#

COMPUTATION OF THREE-DIMENSIONAL FLOWS FOR APPLICATION TO TRANSONIC COMPRESSORS [EXPLOITATION DE CALCULS TRIDIMENSIONNELS DANS LES COMPRESSEURS TRANSSONIQUES]

L. MARRAFFA and A. LE MEUR (ONERA, Chatillon-sous-Bagneux, Hauts-de-Seine, France) ONERA, TP, no. 1984-146, 1984, 14 p. In French.

(ONERA, TP NO. 1984-146)

existing helicopter is made.

Features of three-dimensional models for transonic flow through an axial compressor are described. The finite difference code has been implemented in vector form on a computer. An artificial viscosity is employed to stabilize the calculations and an iterative method is used for a solution after definition of an initial field. Use of a supercomputer has sped the calculations by permitting entry of all grid coordinates and the flow coefficients into the computer memory. The validity of the numerical data is controlled by a governing equation of mass conservation in the flow and using the Euler theorem to detect temperature increases in different regions of the flow. Sample data generated for the pressures on the front and back of a blade oriented downward and the isobaric fields near the top of the channel are provided. It is noted that efforts are needed to structure the calculations so that the volume of data produced can be interpreted in the form of a simple map of the flowfield. M.S.K.

A85-19262#

A SENSOR FOR DETECTION OF UNSTEADY DISTORTION MAXIMA IN AIR INTAKES (DISPOSITIF DE DETECTION DES MAXIMA DE DISTORSION INSTATIONNAIRE DANS LES ENTREES D'AIR)

J. R. BION, B. SELLIER, J. F. OLLIVIER, and M. COMBET (ONERA, Chatillon-sous-Bagneux, Hauts-de-Seine, France) ONERA, TP, no. 1984-148, 1984, 29 p. In French. refs

(ONERA, TP NO. 1984-148)

The application of a pitot tube rake for recording unsteady air flow data in ONERA 1/4-scale wind tunnel trials with engine air intake ducts is described. Samples are taken at a 4 kHz rate for valid scaling. The sampling rate has driven the development of a 56 channel PCM system with programmable low pass filters capable of 20 Hz - 5 kHz rates. The PCM system is interfaced with a rapid acquisition system which can sample and filter the data over 64 channels at a peak 20 kHz rate, producing a pressure map every 64 msec. The time constraints for wind tunnel tests have spurred the development of 'gendarmes' to record only the passage of large perturbations. Up to six sensors placed far enough upstream of the rate are interconnected with a minicomputer which is programmed to respond to threshold turbulence levels to initiate and terminate recording of the rake data. The gendarmes are oriented horizontally to forestall production of a wake at the rake probes. MSK

A85-19263#

AERODYNAMIC STUDIES LINKED TO THE DEVELOPMENT OF DEPLOYABLE NOZZLES [ETUDES AERODYNAMIQUES LIEES AU DEVELOPPEMENT DES DIVERGENTS DEPLOYABLES]

A. VENABLES and G. LARUELLE (ONERA, Chatillon-sous-Bagneux, Hauts-de-Seine, France) ONERA, TP, no. 1984-149, 1984, 65 p. In French. refs (ONERA, TP NO. 1984-149)

The results of theoretical and experimental work carried out

for 5 yr by ONERA on possible configurations of deployable (some partially retractable) nozzle extensions to enhance upper stage ballistic missile thrust are reported. The discussion is limited to the aerodynamic features of the various designs. Attention is given to the beneficial and detrimental aspects of fluid, annufar, panel, mixed, and integrated extensions and a gas-deployable skirt. The deployables were examined for the performances during deployment, which would take place while the engine was already ignited. Their effects on the base drag of the missile stage were found amenable only to experimentation and not numerical modelling. Data from several Mach 5 wind tunnel tests using small rockets are discussed. M.S.K.

A85-19264#

A COMPARISON OF DIFFERENT THREE-DIMENSIONAL SINGULARITY METHODS FOR MODELLING INTERNAL FLOWS [COMPARAISON DE DIFFERENTES METHODES DE SINGULARITES POUR LE CALCUL DES ECOULEMENTS INTERNES EN TRIDIMENSIONNEL]

C. KIRRMANN (ONERA, Chatillon-sous-Bagneux, Hauts-de-Seine, France) ONERA, TP, no. 1984-150, 1984, 36 p. In French. refs

(ONERA, TP NO. 1984-150)

The capabilities of two singularly methods for modelling the interaction between an engine nacelle and a wing are compared. The classic method features Neumann constraints on the concealed surfaces of the panel sources. The lifting bodies are expressed as a skeleton of doublets with intensities fixed by an arbitrary distribution law and a Kutta-Joukowski condition. The second method supposes interior Dirichlet conditions and exterior Neumann limits with hidden closed surfaces of mixed doublet-source panels. The classic method is found to be sensitive to the grid density and the law of internal doublets selected. The Dirichlet scheme, however, is less grid-sensitive, allows regularization for the interior flow, and reduces parietal leakage. Several features of the REHBACH program, which incorporates the Dirichlet model, are discussed. M.S.K.

A85-19401#

AN IMPROVED VERSION OF THE LTRAN2 FOR HIGH FREQUENCY DOMAIN

J. NAKAMICHI (National Aerospace Laboratory, Chofu, Tokyo, Japan) Japan Society for Aeronautical and Space Sciences, Transactions (ISSN 0549-3811), vol. 27, Nov. 1984, p. 121-133. refs

In the present study, the NASA Ames code, LTRAN2 is improved in order that it may be employed to predict unsteady aerodynamic loads on an airfoil oscillating even in high frequency. The modified version presented here is based upon a two-dimensional full transonic small perturbation equation. The main modifications are obtained by adding appropriate higher order terms with respect to time, to the governing equation and to the boundary conditions. These modifications are carried out without any decrease in the accuracy of the solutions and without loss of the conservation property of the scheme. An alternating-direction-implicit finite difference algorithm is presented for the improvements. The results obtained demonstrate both the theoretical and practical feasibility of the present version for predicting the unsteady transonic aerodynamic loads on the two-dimensional airfoils in motions of high frequency, up to the reduced frequency, k = 0.8. Author

A85-19404#

COMPARATIVE STUDY OF VARIOUS QUADRATURES FOR SUBSONIC LIFTING SURFACE CHORDWISE INTEGRALS

S. ANDO (Nagoya University, Nagoya, Japan), D.-H. LEE (Ulsan Institute of Technology, Ulsan, Republic of Korea; Nagoya University, Nagoya, Japan), and K. ASAMI (Kawasaki Heavy Industries, Ltd., Gifu, Japan) Japan Society for Aeronautical and Space Sciences, Transactions (ISSN 0549-3811), vol. 27, Nov. 1984, p. 155-168. refs

Chordwise quadrature methods employed in numerical computations of unsteady subsonic lifting-surface problems are compared analytically by applying them to integrals containing kernel functions, one with a Cauchy-type singularity and one with a logarithmic singularity. The results are presented in graphs and tables and discussed. Although no single method satisfies all of the ideal requirements (wide applicability, rapid computation, and automatic achievement of a prescribed degree of accuracy), the method of Alway (1960) or a combination of Gaussian quadrature and the adaptive Newton-Cotes method of Ninomiya (1980) for different domains of the parameter Y are found to give the best results for the Cauchy-singularity case. A new method developed in an appendix to the present paper is shown to provide the best accuracy for the logarithmic-singularity integral.

A85-19405#

AN ANALYSIS OF THE FLOW PAST AN S-SHAPED ROTOR BY DISCRETE VORTEX MODEL

E. HATAYAMA, H. NAKATANI, and Y. MIYAI (Osaka Prefecture, University, Sakai, Japan) Japan Society for Aeronautical and Space Sciences, Transactions (ISSN 0549-3811), vol. 27, Nov. 1984, p. 169-183. refs

A discrete vortex model has been applied to various separated flow problems, but its application to rotating body problems has been limited to simple cases. In this study, the discrete vortex model together with the conformal mapping method has been applied to analyze the flow around a rotating S-shaped aerofoil having a comparatively complicated mapping function, as the first step to know the flow past the rotor of a windmill with a vertical axis. Numerical calculations are performed for three different types of S-shaped rotor at two tip speed ratios, then the vortex pattern, unsteady moment and forces are obtained. From the calculations, it has been found that the vortex pattern is remarkably influenced by the rotor shape, and that the variations of the moment and forces with the rotating angle show different tendencies with respect to the tip speed ratio. Author

A85-19406#

APPLICATION OF LASER INTERFEROMETRY TO DENSITY MEASUREMENTS IN FREE JETS

H. KOBAYASHI, T. NAKAGAWA, and M. NISHIDA (Kyoto University, Kyoto, Japan) Japan Society for Aeronautical and Space Sciences, Transactions (ISSN 0549-3811), vol. 27, Nov. 1984, p. 184-192. refs

Laser interferometry using Wollaston prisms has been applied to density measurements in freely expanding flows issuing from a sonic orifice. The radially resolved densities have been determined by means of the Abel inversion under the assumption of an axisymmetric flow. Thus determined densities have been compared with those predicted using the formula for a Mach number in the free jet proposed by Ashkenas and Sherman (1966). The comparison shows a fairly good agreement between the experimental and predicted results in the region surrounded by the barrel shock and Mach disk, except for the flow field near the orifice. Author

A85-19439#

THEORETICAL STUDY ON SUPERSONIC JET PLUMES

L. C. CHIEN, T. C. WANG, J. C. LIANG, and F. L. CHEN (Academia Sinica, Institute of Physics, Taipei, Republic of China) Chinese Society of Mechanical Engineers, Journal, vol. 4, Oct. 1983, p. 1-18. refs

The supersonic jet of rocket exhaust plumes under vaious altitudes are investigated by two numerical techniques. Method of characteristics, which the computational procedures are set up similar to the formation process of actual flow, was first employed to solve the plumes of two standard nozzles under various exhaust and ambient conditions. The results are compared with the existing solutions nicely. For an objectly comparison, the Lagrangian finite difference method which operates in the natural coordinates system was devoted to calculate the same jet plumes. It is found that the results obtained by different numerical techniques are in good agreement. Furthermore, the results are also found that they agree with physical phenomena as well.

A85-19451*# Bolt, Beranek, and Newman, Inc., Cambridge, Mass.

AN EXPERIMENTAL INVESTIGATION OF BLADE-VORTEX INTERACTION AT NORMAL INCIDENCE

A. R. AHMADI (Bolt Beranek and Newman, Inc., Cambridge, MA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 17 p. refs (Contract NAS2-11313)

(AIAA PAPER 85-0003)

An experimental investigation has been conducted for the blade-vortex interaction (BVI) of a rotor at normal incidence, where the vortex is generally parallel to the rotor axis. Tip Mach number, radial BVI station, and free stream velocity were varied during measurements of fluctuating-blade pressures, far field sound pressure levels and directivity, incident vortex velocity field, and blade-vortex interaction angles. The experimental setup is representative of the chopping of helicopter main rotor tip vortices by the tail rotor. This interaction is found to generate impulsive noise which radiates primarily ahead of the blade. O.C.

A85-19452#

INTERACTION OF A TURBULENT VORTEX WITH A LIFTING SURFACE

D. J. LEE and L. ROBERTS (Stanford University, Stanford, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs (AIAA PAPER 85-0004)

The impulsive noise due to blade-vortex-interaction is analyzed in the time domain for the extreme case when the blade cuts through the center of the vortex core with the assumptions of no distortion of the vortex path or of the vortex core. An analytical turbulent vortex core model, described in terms of the tip aerodynamic parameters, is used and its effects on the unsteady loading and maximum acoustic pressure during the interaction are determined. Author

A85-19454#

NUMERICAL SOLUTIONS OF VISCOUS TRANSONIC FLOW IN TURBOMACHINERY CASCADES

V. IYER and E. VON LAVANTE (Texas A&M University, College Station, TX) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985.

9 p. refs (AIAA PAPER 85-0007)

The present work is on the numerical solution of the Navier-Stokes equations for transonic flow in compressor cascades and other internal geometries. Two basic algorithms, the bidiagonal implicit algorithm and the approximate factorization implicit algorithm, are considered along with their modified versions. The results are compared to one another and also to inviscid results obtained by other investigators. Author

A85-19455#

AN EXPERIMENTAL INVESTIGATION OF STATOR/ROTOR INTERACTION INFLUENCE ON MULTISTAGE COMPRESSOR ROTOR FLOW

D. L. TWEEDT, T. H. OKIISHI (Iowa State University of Science and Technology, Ames, IA), and M. D. HATHAWAY (U.S. Army, Research and Technology Laboratories, Cleveland, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (Contract F49620-83-K-0023)

(AIAA PAPER 85-0009)

Time-averaged total-head measurements and warm air tracking observations for the second-stage rotor of a low-speed, two-stage, axial-flow compressor are presented and discussed. Some unusual aspects of the detailed distribution of total head in the rotor exit flow are explained in terms of first-stage stator/second-stage rotor viscous interaction. Author

A85-19460#

EULER SOLUTION OF AXISYMMETRIC FLOWS ABOUT BODIES OF REVOLUTION USING A MULTIGRID METHOD

C. J. WOAN (Rockwell International Corp., North American Aircraft Operations Div., Los Angeles, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. Research supported by the Rockwell International Independent Research and Development Program. refs

(AIAA PAPER 85-0017)

Jameson's airfoil Euler code FLO52MG, based on a new class of multistage time stepping schemes in conjunction with enthalpy damping, variable local time step, implicit residual averaging, and multigrid technique to produce a rapid convergence to steady-state, is modified for calculating axisymmetric flows about bodies of revolution. Comparisons of results for a sphere and three AGARD experimental-data-base configurations with exact solutions and test data show very good agreement. Gridding effect on numerical convergence is discussed. The usual airfoil-type mesh with grid points being clustered near the leading-edge often resulted in solution divergence although residuals may initially be reduced to within engineer tolerance. Extension of the modified program to inlet flows is straightforward. Author

A85-19461#

AERODYNAMICS OF AN AIRFOIL IN GROUND EFFECT WITH A JET ISSUING FROM ITS UNDERSURFACE

R. K. AGARWAL and J. E. DEESE (McDonnell Douglas Research Laboratories, St. Louis, MO) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs

(AIAA PAPER 85-0019)

Potential flow models employing the jet-flap theory are inadequate for simulating the flowfield around an airfoil in ground effect with a jet issuing from its undersurface. Euler equations serve as a better physical model because they do not require the assumption of an infinite open wake behind the jet with pressure equal to the free-stream pressure. Euler equations can also capture the vortex formation behind the jet and most of the airfoil/jet/ground-plane interaction, except the effect of entrainment. In this paper, airfoil/jet/ground-interaction flowfields are calculated by solving Euler equations on body-conforming curvilinear grids.

A85-19469#

CURRENT STATUS OF NUMERICAL SOLUTIONS OF THE NAVIER-STOKES EQUATIONS

R. W. MACCORMACK (Washington, University, Seattle, WA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 14 p. refs (Contract AF-AFOSR-83-0057)

(AIAA PAPER 85-0032)

Past and present limitations to the numerical solution of the compressible Navier-Stokes equations are examined. New procedures to accelerate convergence, including line Gauss-Seidel and Newton iteration, are described and tested. The calculation of viscous flow solutions at high Reynolds numbers in less than twenty time step iterations is demonstrated. Author

A85-19470*# Bari Univ. (Italy). AN INCREMENTAL BLOCK-LINE-GAUSS-SEIDEL METHOD FOR THE NAVIER-STOKES EQUATIONS

M. NAPOLITANO (Bari, Universita, Bari, Italy) and R. W. WALTERS (NASA, Langley Research Center, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. Research supported by the Ministero della Pubblica Istruzione. refs (Contract N00014-82-K-0184)

(AIAA PAPER 85-0033)

A block-line-Gauss-Seidel (LGS) method is developed for solving the incompressible and compressible Navier-Stokes equations in two dimensions. The method requires only one block-tridiagonal solution process per iteration and is consequently faster per step than the linearized block-ADI methods. Results are presented for both incompressible and compressible separated flows: in all cases the proposed block-LGS method is more efficient than the block-ADI methods. Furthermore, for high Reynolds number weakly separated incompressible flow in a channel, which proved to be an impossible task for a block-ADI method, solutions have been obtained very efficiently by the new scheme. Author A85-19472*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

A MULTISTAGE TIME-STÉPPING SCHEME FOR THE NAVIER-STOKES EQUATIONS

R. C. SWANSON (NASA, Langley Research Center, Theoretical Aerodynamics Branch, Hampton, VA) and E. TURKEL (Tel Aviv University, Tel Aviv, Israel) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 15 p. refs

(Contract NAS1-17070)

(AIAA PAPER 85-0035)

A class of explicit multistage time-stepping schemes is used to construct an algorithm for solving the compressible Navier-Stokes equations. Flexibility in treating arbitrary geometries is obtained with a finite-volume formulation. Numerical efficiency is achieved by employing techniques for accelerating convergence to steady state. Computer processing is enhanced through vectorization of the algorithm. The scheme is evaluated by solving laminar and turbulent flows over a flat plate and an NACA 0012 airfoil. Numerical results are compared with theoretical solutions or other numerical solutions and/or experimental data. Author

A85-19473#

CALCULATION OF COMPRESSIBLE POTENTIAL FLOW ABOUT MULTIELEMENT AIRFOILS USING A FINITE FIELD-PANEL APPROACH

N. D. HALSEY (Douglas Aircraft Co., Long Beach, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (Contract NSF MEA-80-18565)

(AIAA PAPER 85-0038)

A method for calculating the subsonic, compressible potential flow over general two-dimensional multielement airfoils has been developed. Such a method is needed for high-lift flows, even those with very low freestream Mach numbers, because local velocities become very large near the airfoil leading edges. The method uses the source field-panel approach which, at least for subcritical flows, may have significant computational advantages over the more common finite-difference approach. Unlike previous field-panel methods, this method employs efficient conformal mapping and fast Fourier transform algorithms in both the grid-generation and flow-solver parts of the calculations. Method development and results are described for two-element airfoil cases, while the broad features of the extension to cases with three or more airfoil elements are briefly outlined. Author

A85-19474#

AN EXPERIMENTAL INVESTIGATION OF AN AIRFOIL UNDERGOING LARGE AMPLITUDE PITCHING MOTIONS

J. M. WALKER, H. E. HELIN (USAF, Frank J. Seiler Research Laboratory, Colorado Springs, CO), and J. H. STRICKLAND (USAF, Frank J. Seiler Research Laboratory, Colorado Springs, CO; Texas Tech University, Lubbock, TX) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs

(Contract F49620-82-C-0035)

(AIAA PAPER 85-0039)

Flow-visualization and near-surface hot-wire experiments were performed in the USAF Academy Aeronautics Laboratory 2 x 3-ft subsonic wind tunnel on an airfoil undergoing large-amplitude pitching motions. The experiments were conducted using a 6-in. NACA 0015 airfoil at an airfoil Reynolds number of 45,000 by pitching from 0 to 60 deg at various constant angular-pitch rates. The two cases presented represent two different nondimensional pitching rates, alpha(+), equal to the ratio of the product of the pitch rate, and the chord to the freestream velocity. Data for the two cases where values of alpha(+) were equal to 0.2 and 0.6 show the dramatic effect of pitch rate on flow structure. Large-scale vortical structures are seen in both cases but appear in different form at higher angles of attack for the larger alpha(+) value. These structures are very energetic, producing reverse flow velocities near the airfoil surface of 1-2.5 times the freestream velocity. Author

National Aeronautics and Space Administration. A85-19475*# Langley Research Center, Hampton, Va. TURBULENT FLOW AROUND A WING-FUSELAGE TYPE

JUNCTURE

L. R. KUBENDRAN (NASA, Langley Research Center, Hampton, VA), H. M. MCMAHON, and J. E. HUBBARTT (Georgia Institute of Technology, Atlanta, GA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(Contract NAG1-40)

(AIAA PAPER 85-0040)

The flow over a 58-mm-thick uniform-thickness winglike body having a 1.5:1 elliptical leading edge and joined to a large flat plate (representing an aircraft fuselage) is characterized experimentally at freestream velocity 15 m/s, corresponding to Reynolds number 940,000/m, using hot-wire anemometry. The results are presented graphically, and it is found that the horseshoe vortex formed by the separation of the fuselage boundary layer ahead of the wing leading edge is effective in transporting turbulence and modifying the mean-flow characteristics and the turbulent-stress distribution. It is suggested that the slenderness ratio of the leading edge is the dominant factor affecting the strength and location of the vortex. T.K.

A85-19476#

THREE-DIMENSIONAL EFFECTS ON A PITCHING LIFTING SURFACE

M. GAD-EL-HAK (Flow Research Co., Kent, WA) and C.-M. HO (Southern California, University, Los Angeles, CA; Flow Research Co., Kent, WA) American Institute of Aeronautics and Astronautics. Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs

(Contract F49620-82-C-0020)

(AIAA PAPER 85-0041)

The low Reynolds number, time-dependent flow around two generic classes of wings is studied in a water towing tank. Delta and swept (including zero sweep) wings were sting-mounted to a four-bar mechanism which generated a large amplitude, harmonic pitching motion around the 1/4-chord location, at a reduced frequency that varied in the range of 0.2 to 3. Fluorescent dye-layers were placed in the weakly-stratified water channel prior to towing the wing. The horizontal dye sheets were excited using a vertical sheet of laser light. The dye marked the flow in the separation region around the wing, the wake region, and the potential flow away from the lifting surface. The complex, time-dependent flow field around the different wings can be mostly explained from the mutual induction between the leading edge separation vortex and the trailing edge shedding vortex. The reduced frequency, the shape of the leading edge, and the wing's planform play important roles in determining the flow patterns. Author

A85-19477# COMPUTATIONAL STUDY OF CIRCULATION CONTROL WITH SUCTION

R. HIMENO, K. KUWAHARA, and T. KAWAMURA (Tokyo, University, Tokyo, Japan) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs

(AIAA PAPER 85-0042)

The effects of circulation control by means of suction are studied computationally via a higher-order upwind scheme. Elliptic and oval airfoils with various thickness ratio are treated. Dependence on the various parameters is investigated. Because the suction position has a very important effect on lift/drag, special effort has been made to check its position. Also, dependence on the thickness ratio of the airfoil is shown. Author

A85-19478#

TURBULENCE STRUCTURE OF A THREE DIMENSIONAL IMPINGING JET IN A CROSS STREAM

M. V. SHAYESTEH, P. BRADSHAW (Imperial College of Science and Technology, London, England), and I. M. M. A. SHABAKA (Cairo University, Cairo, Egypt; Imperial College of Science and Technology, London, England) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. USAF-supported research. refs (A)AA PAPER 85-0044)

Extensive measurements have been made in turbulent jets which emerge from circular nozzles into a cross-stream, and then impinge on a flat surface perpendicular to the nozzle axis. Such flows are found in impingement-cooling applications and below a VTOL aircraft hovering in a headwind. Data were obtained with conventional hot-wire anemometers and, in regions of high turbulence intensity or reversed flow, with a pulsed-wire anemometer. Data include all components of mean velocity, and all Reynolds stresses and triple products of velocity fluctuations. The results show the presence of a pronounced trailing vortex system, and also the large effects of flow distortion on the turbulence structure parameters that determine the empirical constants in engineering models of turbulence. Author

A85-19479#

THE EFFECT OF PHASE-DIFFERENCE ON THE SPREADING RATE OF A LAMINAR CIRCULAR JET UNDER BI-MODAL EXCITATION

R. R. MANKBADI (Rutgers University, New Brunswick, NJ) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (AIAA PAPER 85-0045)

The role of initial phase difference between fundamental and subharmonic instability waves on the spreading rate of a circular jet under bi-modal excitation is investigated theoretically. For all Strouhal numbers considered, the initial growth rate of the subharmonic was found to be a maximum when the two waves are initially in-phase. The effect of the phase-difference on the subharmonic's peak is dependent on Strouhal number. The development of the momentum thickness along the jet is characterized by regions of step-wise growth. The momentum thickness first increases as the fundamental amplifies. This growth region is followed by a region where the decay of the fundamental and the growth of the subharmonic result in a constant momentum thickness. Once the fundamental has fully decayed, the momentum thickness grows again as a result of the subharmonic's amplification. The growth rate is dependent on the initial phase difference and is maximum when the subharmonic suffers maximum amplification. Author

A85-19480#

THE INTERACTION AND MERGING OF TWO TURBULENT LINE VORTICES

A. J. SMITS (Princeton University, Princeton, NJ) and R. P. KUMMER American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs (AIAA PAPER 85-0046)

An experimental investigation of the interaction and merging of two turbulent line vortices is described. The vortices were generated by two airfoils set at opposite angles of attack, and they were of opposite sign and equal strength. As the vortices proceed downstream they rotate around each other, and eventually they merge to produce a dominant, central vortex, with vestigial traces of the original vortices. Mean flow and turbulence measurements were made throughout the merging zone. The circulation profiles varied logarithmically with radius, for a considerable radial extent, at all stations. The turbulent shear stresses appeared to be simply related to the mean velocity gradients, and it seems that first-order turbulence models may be adequate to describe the merging process. Author

A85-19482*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

RESEARCH FACILITY IMPROVEMENTS VORTEX AND PRELIMINARY DENSITY STRATIFICATION EFFECTS ON **VORTEX WAKES**

D. R. SATRAN, G. T. HOLBROOK, G. C. GREENE (NASA, Langley Research Center, Hampton, VA), and D. NEUHART (NASA, Langley Research Center; Kentron International, Inc., Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 14 p. refs (AIAA PAPER 85-0050)

Recent modernization of NASA's Vortex Research Facility is described. The facility has a 300-ft test section, scheduled for a 300-ft extension, with constant test speeds of the model up to 100 ft/sec. The data acquisition hardware and software improvements included the installation of a 24-channel PCM system onboard the research vehicle, and a large dedicated 16-bit minicomputer. Flow visualization of the vortex wake in the test section is by particle seeding, and a thin sheet of argon laser light perpendicular to the line of flight; detailed flow field measurements are made with a laser velocimeter optics system. The improved experimental capabilities of the facility were used in a study of atmospheric stratification effects on wake vortex decay, showing that the effects of temperature gradient must be taken into account to avoid misleading conclusions in wake vortex research. L.T.

A85-19484#

A NOVEL EXPERIMENTAL FACILITY FOR CONDUCTING JET IMPINGEMENT STUDIES RELATED TO VTOL AIRCRAFT

K. R. SARIPALLI and J. C. KROUTIL (McDonnell Douglas Research Laboratories, St. Louis, MO) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985, 9 p. refs.

(AIAA PAPER 85-0052)

A novel experimental facility using water as the working medium has been designed and built to study multiple jet impingement flowfields, with specific application to vertical-take-off-and-landing (VTOL) aircraft. The components of this facility and the associated equipment are described in detail. An account is given of performance tests conducted on the facility which included diagnostic flow visualization and measurements. Flow-visualization studies conducted on a model VTOL aircraft to study the near-field exhaust flow patterns in ground effect are described. Author

A85-19487#

EXAMINING THE VALIDITY OF A COMBUSTOR FLOW MODEL WITH LDV

G. O. KRAEMER (Avco Corp., Lycoming Div., Stratford, CT) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs (AIAA PAPER 85-0055)

Laser Doppler velocimetry was used to map the flow field within a PLT-34 annular combustor liner at ambient conditions. This combustor design produces a primary zone flow field resembling a horseshoe shaped mean circulation path centered about the fuel injector. This combustor design was chosen because of the three-dimensionality of the flow field and its use in AVCO-Lycoming engines. Overall the combustor flow model, INTERN, was found to provide good qualitative and reasonable quantitative description of this complex flow field. However, the model underpredicts the fine detail of the high velocity jets and the rms velocity. In consideration of the coarseness of the grid used and approximate modeling of the combustor geometry, the overall agreement is considered good. Author A85-19489*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio. ACCELERATED CONVERGENCE FOR INCOMPRESSIBLE

FLOW CALCULATIONS

G. M. NEELY and R. W. CLAUS (NASA, Lewis Research Center, Cleveland, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. Previously announced in STAR as N85-10949. refs

(AIAA PAPER 85-0058)

Two improved algorithms which solve the steady-state Navier-Stokes equations, PISO and SIMPLER, are studied. Computations were carried out on progressively finer grids for the driven cavity and flow over a backward-facing step. The effects of relaxation factor, number of grid nodes and number of sweeps through the pressure equations are studied to evaluate the performance of the PISO and SIMPLER schemes. Results show that these improved schemes accelerate the convergence rate of the solution generally by a factor of two as compared to the SIMPLE method. Author

A85-19490*# Texas Technological Univ., Lubbock. FLOW VISUALIZATION OF LATERAL JET INJECTION INTO SWIRLING CROSSFLOW

G. B. FERRELL (Texas Tech University, Lubbock, TX; Oklahoma State University, Stillwater, OK), K. AOKI (Oklahoma State University, Stillwater, OK; Tokai University, Hiratsuka, Japan), and D. G. LILLEY (Oklahoma State University, Stillwater, OK) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs (Contract NAG3-159)

(AIAA PAPER 85-0059)

Flow visualization experiments have been conducted to characterize the time-mean flowfield of a deflected turbulent jet in a confining cylindrical crossflow. Jet-to-crossflow velocity ratios of 2, 4, and 6 were investigated, under crossflow inlet swirler vane angles of 0 (swirler removed), 45 and 70 degrees. Smoke, neutrally-buoyant helium-filled soap bubbles, and multi-spark flow visualization were employed to highlight interesting features of the deflected jet, as well as the trajectory and spread pattern of the jet. Gross flowfield characterization was obtained for a range of lateral jet-to-crossflow velocity ratios and a range of inlet swirl strengths in the main flow. The flow visualization results agree well with the measurements obtained elsewhere with the six-orientation single hot-wire method. Author

A85-19500#

THE DESIGN OF AIRFOILS AT LOW REYNOLDS NUMBERS

M. S. SELIG (Illinois, University, Urbana, IL) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan, 14-17, 1985, 11 p. refs (AIAA PAPER 85-0074)

This paper focuses on the design of airfoils at low Reynolds numbers (100,000-500,000), specifically those applicable to radio-controlled model sailplanes. Two common types of airfoil lift and drag hysteresis are illustrated and explained in terms of the behavior of the upper-surface transitional separation bubble which is commonly present at these low Reynolds numbers. The theoretical section characteristics of several airfoils predicted by the Eppler (1980) computer program for the design and analysis of low-speed airfoils were compared with the recent experimental data of Althaus (1980). Good correlation was found between the type of hysteresis and the general character of the pressure distribution. Also, the validity of the predicted section characteristics is discussed for this low Reynolds number regime. From the comparisons the desirable qualities of a low Reynolds number airfoil were determined. Based on this several airfoils for radio-controlled model sailplanes were subsequently designed and analyzed using the Eppler computer program. Author

A85-19501#

A COMPARISON OF FLIGHT TEST AND ANALYTICAL TECHNIQUES FOR BOUNDARY LAYER TRANSITION ON A SAILPLANE

K. MILLER (USAF, Edwards AFB, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(AIAA PAPER 85-0075)

Practical techniques for using pigmented oil and sublimating chemicals to reveal inflight boundary layer transition were developed and compared. Pigmented oil was found relatively simple to use and produced photographs with transition clearly defined at all but high angles of attack. Low temperatures increased the viscosity of the oil to the point that temperatures slightly below standard day resulted in no indication of transition. Temperature variations were a factor with the sublimation technique also. In general, the flight test results compared favorably with data from the Eppler-Somers airfoil analysis code. At angles of attack below eight degrees, the transition locations indicated by the pigmented oil are within 5 percent chord of the predicted locations. Practical procedures are recommended. Author

A85-19508*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

ON BOUNDARY LAYER TRANSITION IN HIGH-SUBSONIC AND TRANSONIC FLOW UNDER THE INFLUENCE OF ACOUSTIC DISTURBANCES AND FREE-STREAM TURBULENCE

S. V. MURTHY and F. W. STEINLE (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs

(AIAA PAPER 85-0082)

The existing data base which quantifies the roles played by the Mach number, turbulence level, and acoustic noise in the flow quality of wind tunnels is reviewed. Attention is given to the effects on end (ET) and beginning (BT) transitions in flows over a 10 deg cone in transonic channels. The Re of both ET and BT flows were significantly affected by the Mach number, acoustic noise level and the noise frequency content. A unit increment in the Mach number increased the Re beyond 3,000,000, while noise below the 1 percent level in the rms pressure coefficient did not alter the transition phenomenon. More data are required on the effects of turbulence, which was a significant factor, and in the settling chamber, test section, plenum and diffuser to trace the locations and magnitudes of the acoustic sources. M.S.K.

A85-19510*# United Technologies Research Center, East Hartford, Conn.

THREE-DIMENSIONAL INVISCID FLOW ANALYSIS OF TURBOFAN FORCED MIXERS

T. J. BARBER, G. L. MULLER, S. M. RAMSAY (United Technologies Research Center, East Hartford, CT), and E. M. MURMAN (MIT, Cambridge, MA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 14 p. refs

(Contract NAS3-23039)

(AIAA PAPER 85-0086)

A three-dimensional potential analysis has been formulated and applied to the inviscid flow over a turbofan forced mixer. The method uses a unique small disturbance formulation to analytically uncouple the circumferential flow from the radial and axial flow problem, thereby reducing the analysis to the solution of a series of axisymmetric problems. These equations are discretized using a flux volume formulation along a Cartesian grid. The method extends earlier applications of the Cartesian method to complex cambered geometries. The effects of power addition are also included within the potential formulation. Good agreement is obtained with an alternate small disturbance analysis for a symmetric mixer in a planar duct. In addition calculations showing pressure distributions and induced secondary vorticity fields are presented for practical turbofan mixer configurations, and where possible, comparison has been made with available experimental data. Author

A85-19511#

A QUASI-CONSERVATIVE LAMBDA FORMULATION

A. DADONE and V. MAGI (Bari, Universita, Bari, Italy) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. Research supported by the Ministero della Pubblica Istruzione and Consiglio Nazionale delle Ricerche, refs

(AIAA PAPER 85-0088)

A modified lambda formulation is demonstrated to be capable of simulating transonic inviscid flows. A technique for coupling the supersonic region with the subsonic region by means of a shock is defined. The method's ability to depict a shock is illustrated in terms of a simplified one-dimensional flow applied to three transonic nozzle flows. The technique is extended to nonisentropic oneand two-dimensional flows of a gas with a ratio of specific heats not equal to one. Solutions are obtained that are commensurate with solutions derived by exact methods, showing that the modified lambda method can model the forward movement of the shock.

M.S.K.

A85-19523#

FLOWS OVER LOW REYNOLDS NUMBER AIRFOILS COMPRESSIBLE NAVIER-STOKES NUMERICAL SOLUTIONS

A. P. KOTHARI and J. D. ANDERSON, JR. (Maryland, University, College Park, MD) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 15 p. refs

(Contract N00014-81-K-2037: N00014-84-K-0181) (AIAA PAPER 85-0107)

Laminar and transitional turbulent compressible two-dimensional viscous flows over Miley and Wortmann airfoils at Reynolds numbers 500-300,000 are investigated analytically. finite-difference implicit procedure is applied to solve the Navier-Stokes equations, and the results are compared presented graphically and compared with experimental data (Mueller, 1984): good agreement is obtained. Both laminar and turbulent flows with large separation are found to be unsteady, while the nonseparated flows are steady. TK.

A85-19524*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va. A THEORY FOR THE CORE OF A THREE-DIMENSIONAL

LEADING-EDGE VORTEX

J. M. LUCKRING (NASA, Langley Research Center, Transonic Aerodynamics Div., Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 15 p. refs

(AIAA PAPER 85-0108)

A theory is presented for the flow in the core of a separation-induced leading-edge vortex. The theory is based on matching inner and outer representations of the vortex. The inner representation models continuously distributed vorticity and includes an asymptotic viscous subcore. The outer representation models concentrated spiral sheets of vorticity and is fully three dimensional. A parameter is identified which closely tracks the vortex breakdown stability boundary for delta, arrow, and diamond Author winas.

A85-19526*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

A COMPARISON OF EULER AND NAVIER-STOKES SOLUTIONS FOR SUPERSONIC FLOW OVER A CONICAL DELTA WING

R. W. NEWSOME (NASA, Langley Research Center; USAF, Wright Aeronautical Laboratories, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs (AIAA PAPER 85-0111)

The flow around a thin elliptic cone at Mach number 2 and angle of attack 10 deg is simulated numerically, comparing the results obtained using a fine grid and the Navier-Stokes (NS) equations with those obtained using both coarse and fine grids and the Euler (E) equations. On the coarse grid, the E results are found to reproduce roughly the NS predictions of leading-edge separation and primary and secondary vortices on the leeward surface, but the E solution on the fine NS grid (showing no separation and a crossflow-shock-induced vorticity) reveals this agreement to be spurious. The fine-grid E prediction is shown to be a valid solution of the E equations, indicating their unsuitability as approximators of viscous flow. The imposition of a Kutta condition on the E computation is found to be ineffective in correcting this discrepancy. T.K.

A85-19531#

SOLUTION OF THE UNSTEADY EULER EQUATIONS FOR FIXED AND ROTOR WING CONFIGURATIONS

N. L. SANKAR, B. E. WAKE, and S. G. LEKOUDIS (Georgia Institute of Technology, Atlanta, GA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno. NV. Jan. 14-17, 1985. 11 p. Army-supported research. refs (AIAA PAPER 85-0120)

A solution procedure is described for the numerical solution of inviscid rotational flow past fixed and rotor wing configurations. This procedure solves the three-dimensional Euler equations in a body-fitted coordinate system and in strong conservation form. The derivatives along the spanwise direction are lagged by one time step, while all the other terms are treated in a fully implicit manner. This leads to a semi-implicit scheme that requires two block tridiagonal matrix inversions and one residual evaluation per point at every time step. This procedure also requires the flow variables to be stored at only one time level. A number of fixed wing and rotor wing calculations are presented to demonstrate the efficiency and accuracy of this procedure. Author

A85-19532#

THREE-DIMENSIONAL EULER SOLUTIONS WITH GRID EMBEDDING

T. J. BAKER, A. JAMESON (Princeton University, Princeton, NJ), and R. E. VERMELAND (McDonnell Aircraft Co., St. Louis, MO; Princeton University, Princeton, NJ) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs

(AIAA PAPER 85-0121)

An embedded mesh has been introduced into the three-dimensional Euler method for calculating flows over wing/body/tail combinations. The enriched mesh surrounds the tail and provides a reasonable resolution of the flow field there. Comparisons between theory and experiment are presented for the pressure distribution over the tail of the Boeing 747-200.

Author

A85-19533*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va. A COMPARISON OF FINITE VOLUME FLUX VECTOR

SPLITTINGS FOR THE EULER EQUATIONS

W. K. ANDERSON, J. L. THOMAS (NASA, Langley Research Center, Hampton, VA), and B. VAN LEER (Delft, Technische Hogeschool, Delft, Netherlands) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 16 p. refs

(AIAA PAPER 85-0122)

A comparison is made between the computational results of the Steger-Warming (1981) and van Leer (1982) flux splitting methods, which have been applied in generalized coordinates to quasi-one-dimensional transonic flow in a nozzle and two-dimensional subsonic, transonic, and supersonic flow over airfoils. The latter splitting method leads to higher convergence rates and a sharper representation of shocks in the transition region. The second-order accurate, one-sided-difference model is extended to a third-order, upwind-biased model with only small additional computational effort. O.C.

A85-19534*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va. NUMERICAL SOLUTION OF THE EULER EQUATIONS FOR

HIGH-SPEED, BLENDED WING-BODY CONFIGURATIONS

A. MOITRA (NASA, Langley Research Center; Systems and Applied Sciences Corp., Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs

(AIAA PAPER 85-0123)

Simulation of high-speed three-dimensional flow about blended wing-body combinations is investigated. A finite-volume explicit scheme with Runge-Kutta time integration is used to solve the compressible Euler equations in order to simulate the flow. The method, augmented by carefully chosen dissipative terms and convergence accelerators such as enthalpy damping and maximum local time-stepping, has been found to be very efficient in solving high-speed flows involving strong shocks. An analytic method for generating the body geometry and an algebraic method for quasi-three-dimensional grid generation are described. Results are presented for various blended wing-body configurations at different Mach numbers and angles of attack. Author

A85-19536#

SURFACE PRESSURE FLUCTUATIONS IN THREE-DIMENSIONAL SHOCK WAVE/TURBULENT **BOUNDARY LAYER INTERACTION**

D. K. M. TAN, S. M. BOGDONOFF (Princeton University, Princeton, American Institute of Aeronautics and NJ), and T. T. TRAN Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs (Contract F49620-81-K-0018)

(AIAA PAPER 85-0125)

Surface pressure fluctuations have been measured in a three-dimensional shock wave/turbulent bounday layer interaction. The shock wave was generated by a sharp-edged fin set perpendicular to the boundary layer at 10 deg to the flow direction. Tests were conducted at a nominal freestream Mach number of 3. The pressure fluctuations were found to be small in contrast to a two-dimensional compression ramp shock/boundary layer interaction with the same shock strength. This, however, does not suggest that the flow is steady. Cross-correlation analysis suggests some degree of unsteadiness in the shock structure. Contour plots of the space correlations and maxima in cross-correlations were computed. The contours showed the development of the spatial scales and decay rates of the pressure producing structures through the interaction. Author

A85-19538#

SOME THOUGHTS ON THE RANGE/TUNNEL TRANSITION CONTROVERSY

L. E. ERICSSON (Lockheed Missiles and Space Co., Inc., American Institute of Aeronautics and Sunnyvale, CA) Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs

(AIAA PAPER 85-0127)

The range/tunnel transition controversy is related to the observation that transition occurs earlier in the guiet range than in the noisy wind tunnel. Ericsson (1984) has shown that coupling between vehicle motion and boundary layer transition could provide an explanation for the early transition on the free flight model in a ballistic range. The present investigation is concerned with the existing data base for slender body transition to examine the validity of the concept presented by Ericsson. Local moving wall effects are discussed. According to recent flow visualization results, the spin-induced moving wall velocity generates vortices embedded in the boundary layer, and transition appears to occur through some form of vortex-burst. G.R.

-A85-19539#- - ------

NUMERICAL STUDY ON THE DYNAMIC STALL PROCESS OF A NACA 0012 AIRFOIL

K. ONO (Nihon University, Tokyo, Japan) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs (AIAA PAPER 85-0128)

The dynamic stall process is numerically simulated on a two-dimensional NACA 0012 airfoil oscillating in pitch at a high incidence angle in a subsonic flow. The formation of the leading-edge separation bubble, as well as its convection along the airfoil surface and shedding into the wake, plays an essential role. The Navier-Stokes equations are to be solved. The time-averaged compressible Navier-Stokes equations with the Baldwin-Lomax turbulence model are solved using the implicitly factored finite-difference algorithm constructed in a body-fitted coordinate system. The same scheme is applied to the laminar compressible Navier-Stokes equations. Qualitative agreement with experimental data is good. The laminar calculation is more promising because small-scale vortices are precisely trapped.

Author

A85-19540#

NUMERICAL SOLUTION OF UNSTEADY VISCOUS FLOW PAST **ROTOR SECTIONS**

N. L. SANKAR and W. TANG (Georgia Institute of Technology, Atlanta, GA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. Army-supported research. refs

(AIAA PAPER 85-0129)

A compressible Navier-Stokes solver has been developed for unsteady airfoil calculations frequently encountered in rotor applications. This procedure solves the unsteady, compressible Navier-Stokes equations on a body-fitted moving coordinate system in strong conservation form using an ADI procedure. This procedure is capable of treating embedded point and distributed vortices without excessive numerical diffusion, and can capture embedded shocks without overshoots. Numerical results are presented for the following cases to establish the usefulness of this procedure: (1) steady inviscid transonic flow over a NACA 0012 airfoil for a number of Mach numbers and angles of attack, (2) steady subsonic viscous flow past a NACA 0012 airfoil at 0.3 Mach number and 3 million Reynolds number, (3) inviscid transonic flow calculations involving vortex airfoil interaction, and (4) turbulent dynamic stall calculations for a NACA 0012 airfoil. In all cases presented, the results are compared with experimental and other published data. Author

A85-19541#

INTERRELATED EFFECTS OF PITCH RATE AND PIVOT POINT **ON AIRFOIL DYNAMIC STALL**

H. E. HELIN (U.S. Air Force Academy; USAF, Frank J. Seiler Research Laboratory, Colorado Springs, CO) and J. M. WALKER (USAF, Frank J. Seiler Research Laboratory, Colorado Springs, American Institute of Aeronautics and Astronautics, CO) Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (AIAA PAPER 85-0130)

Experimental investigations were performed to study energetic dynamic stall vortices and the associated unsteady aerodynamics generated by a pitching NACA 0015 airfoil. The model was pitched from 0 to 60 degrees at constant alpha rates of 460, 920, and 1380 deg/s about its quarter-chord, half-chord, and three quarter-chord positions. Smoke-wire visualization technique and near-surface hot-wires mounted in a staggered array on the airfoil surface were used. It is shown that, as the pitch rate is increased, the angle of attack at which dynamic stall occurs is also increased. Moving the pitch axis toward the trailing edge emulates some of the effects of the increased pitch rate; dynamic stall occurs at correspondingly higher angles of attack, and the large dynamic stall vortex has significant impact on the velocities over the airfoil surface. L.T.

CALCULATION OF VISCOUS NOZZLE FLOWS BY THE UNSTEADY METHOD OF CHARACTERISTICS

D. L. MARCUM and J. D. HOFFMAN (Purdue University, West Lafayette, IN) American Institute of Aeronautics and Astronautics. Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 14 p. refs

(AIAA PAPER 85-0131)

A numerical algorithm based on the unsteady two-dimensional method of characteristics is presented for calculating steady two-dimensional (planar) subsonic/transonic/supersonic viscous (laminar) nozzle flowfields. The Navier-Stokes equations for unsteady two-dimensional (planar) laminar flow are solved. The flowfield unit processes are based on a local network consisting of four bicharacteristics and the pathline. The algorithm is an explicit second-order accurate predictor-corrector procedure. An inverse marching method is employed, wherein the solution grid in physical space is prespecified. Steady flow solutions are obtained as the asymptotic solution in time. Results are presented for a small planar nozzle. The solution obtained by the present method agrees well with the solution obtained by McCormack's explicit method and with experimental data. Author

A85-19543#

THREE-DIMENSIONALITY IN UNSTEADY FLOW ABOUT A WING

J. N. ADLER and M. W. LUTTGES (Colorado, University, Boulder, CO) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs

(Contract AF-AFOSR-81-0037)

(AIAA PAPER 85-0132)

Serialized, phase locked, orthogonal view flow visualization was used to characterize the unsteady flow field generated by a finite NACA 0015 wing sinusoidally oscillating through angles of attack centered well beyond the static stall angle. Far inboard, toward the root of the wing, the flow field was dominated by a leading edge vortex similar in phase of initiation, size, and convection velocity to vortices observed in studies modeling an infinite wing. Spanwise smoke movements were associated with the leading edge vortex, indicating three-dimensionality of this nominally two-dimensional structure. Outboard flow was dominated by an unsteady wing tip vortex. An interactive interface region was identified between these well-defined flows. Elicited flow structures were very sensitive to pitching parameters. Visualizations provide evidence that wing tip circulation depended more on leading edge vortex development than on instantaneous angle of attack. These studies indicate the complexity of three-dimensional unsteady flows and the quantification that will be needed to fully characterize such flows. Author

A85-19556#

THE USE OF PANEL METHODS FOR THE DEVELOPMENT OF LOW-SUBSONIC WALL INTERFERENCE AND BLOCKAGE CORRECTIONS

K. G. BOWCUTT American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 18 p. refs

(AIAA PAPER 85-0159)

A method of adjusting two-dimensional wind tunnel data to correct for wall interference is described. The technique employs source and vortex panels and modified kernal functions to represent the model and a separated wake when one is present. Governing equations are defined for the potential flow and the source and vortex singularities which are distributed along the panels. Boundary conditions are imposed at all panel control points and the singularity strengths are calculated. Interferences is then quantified with an implicit wall model and viscous boundary layer effects are treated in terms of the laminar boundary layer, transition, the turbulent boundary layer, and a separated wake. Test runs for an airfoil and a blunt body were compared with experimental data, showing that the method yields accurate interference corrections, pressure distributions, and lift, drag and moment coefficients. M.S.K.

A85-19562*# United Technologies Research Center, East Hartford, Conn.

A PROCEDURE FOR THE CALCULATION OF SUPERSONIC FLOWS WITH STRONG VISCOUS-INVISCID INTERACTION

M. BARNETT (United Technologies Research Center, East Hartford, CT; Cincinnati, University, Cincinnati, OH) and R. T. DAVIS (Cincinnati, University, Cincinnati, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd,

Reno, NV, Jan. 14-17, 1985. 9 p. refs (Contract NGT-36-004-800; NCA2-OR-130-101;

N00014-76-C-0364)

(AIAA PAPER 85-0166)

The present paper is concerned with the calculation of strong viscous-inviscid interactions in two-dimensional laminar supersonic flows with and without separation. The equations solved are the so-called parabolized Navier-Stokes equations. The streamwise pressure gradient term is written as a combination of a forward and a backward difference to provide a path for upstream propagation of information. Global iteration is utilized to repeatedly update the pressure field from an initial guess until convergence is achieved. The numerical scheme employed is a new alternating direction explicit (ADE) procedure which is used as an alternative to the more difficult to program multigrid strategy to accelerate convergence. Results are presented for flows past two flat plate related bodies. Author

A85-19563#

NUMERICAL COMPUTATION OF VISCOUS FLOWFIELDS ABOUT MULTIPLE COMPONENT AIRFOILS

D. M. SCHUSTER and L. D. BIRCKELBAW (Lockheed-Georgia Co., Marietta, GA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(AIAA PAPER 85-0167)

A method has been developed which solves the time dependent, Reynolds averaged Navier-Stokes equations for compressible flows about multiple component airfoil systems. This method uses a grid patching scheme in conjunction with an Alternating Direction Implicit (ADI) finite difference method to numerically solve the subject equations. An algebraic turbulence model is used to predict turbulence characteristics of the flow. Several cases have been analyzed, and the correlation with experimental data for these cases is very encouraging. Author

A85-19565#

ANALYSIS OF CIRCULATION CONTROL AIRFOILS USING AN IMPLICIT NAVIER-STOKES SOLVER

G. D. SHREWSBURY (Lockheed-Georgia Co., Advanced Flight Sciences Dept., Marietta, GA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno. NV. Jan. 14-17, 1985. 8 p. refs

(AIAA PAPER 85-0171)

The compressible Reynolds time averaged Navier-Stokes equations were used to obtain solutions for both low speed and transonic flows about two-dimensional circulation control airfoils. The governing equations were written in conservation form for a body-fitted coordinate system and solved using an Alternating Direction Implicit (ADI) procedure. A modified algebraic eddy viscosity model was used to define the turbulent characteristics of the flow, including the wall jet flow over the Coanda surface at the trailing edge. Numerical results are compared to experimental data obtained for two circulation control airfoil geometries. Excellent agreement with the experimental results was obtained for both low speed and transonic flow tests. Author

A85-19567*# Purdue Univ., Lafayette, Ind.

THREE DIMENSIONAL AERODYNAMICS OF AN ANNULAR CASCADE IN A NON-UNIFORM INLET FLOW

S. R. MANWARING and S. FLEETER (Purdue University, West Lafayette, IN) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 18 p. NASA-supported research. refs

(AIAA PAPER 85-0174)

Three-dimensional viscous and inviscid numerical analyses are currently being developed to predict the complex flow through turbomachine blade passages. To be of value to the designer, these numerical solutions must be evaluated and subsequent refinements directed by correlating predicted flow fields with data obtained from experiments which model the fundamental three-dimensional flow phenomena inherent in blade rows. This paper describes a series of experiments to provide such data. In particular, the effect of a potential and a rotational inlet flow field on the detailed three-dimensional aerodynamic performance of an extensively instrumented cambered airfoil cascade has been determined at two levels of aerodynamic loading. Data presented quantify the pressure and suction surface static pressure chordwise distributions on the hub, mean, and tip streamlines; the velocity distribution in the cascade aft-passage region; and the cascade exit region flow field. Appropriate data are correlated with predictions. Author

A85-19568#

A NEW ITERATIVE MATRIX SOLUTION PROCEDURE FOR THREE-DIMENSIONAL PANEL METHODS

R. W. CLARK (Douglas Aircraft Co., Long Beach, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. Research sponsored by the McDonnell Douglas Independent Research and Development Program. refs

(AIAA PAPER 85-0176)

An iterative solution procedure is presented for the large set of linear simultaneous equations for the singularity strengths satisfying the boundary conditions in panel models of three-dimensional flows past bodies. Attention is focused on the Douglas panel method, which descibes the flow past the body in terms of a surface source singularity distribution and a normal velocity boundary condition. The acceleration of the solution convergence is achieved by defining a linear combination of earlier approximations after each iteration. The relaxation involves quantifying the residual vector after an iteration, and evaluating it in a simplified form. The process is performed independently from the iteration calculations and considers both the normal velocity and the Kutta condition residuals. Sample convergence histories are provided for a high lift wind and an inlet and compared with those of a Gauss-Seidel scheme. M.S.K.

A85-19569#

A STUDY OF COMPRESSIBLE TURBULENT FREE SHEAR LAYERS USING LASER DOPPLER VELOCIMETRY

H. L. PETRIE (U.S. Army, Missile Laboratory, Redstone Arsenal, AL), M. SAMIMY, and A. L. ADDY (Illinois, University, Urbana, IL) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs (Contract DAAG29-79-C-0184; DAAG29-83-K-0043)

(AIAA PAPER 85-0177)

An experimental investigation of two-dimensional planar turbulent free shear layers with supersonic freestream Mach numbers is discussed. Three backward facing step flow configurations were investigated in order to gain a detailed knowledge of the mean flow and turbulent field in developing free shear layers with and without an adjacent recirculating flow and a constant pressure separation. Two channel coincident laser Doppler velocimeter (LDV) measurements, surface static pressure measurements, schlieren flow visualization, and surface oil flow visualization were used to study these flows. Author

A85-19570#

SOME FEATURES OF TWO-DIMENSIONAL TURBULENT SEPARATED FLOWS

R. L. SIMPSON (Virginia Polytechnic Institute and State University, Blacksburg, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 19 p. refs

(AIAA PAPER 85-0178)

The characteristics of phenomena known to occur in two-dimensional separated flows are reviewed, along with causes for the separations. Attention is given to the experimentally observed features of separating and reattaching turbulent shear flows. The generating mechanisms can be adverse pressure gradients, sharp-edged bluff bodies, backward or forward facing steps, a fence or a rib. The effects of compressibility on separation are noted, and consideration is devoted to transonic, supersonic and stall-induced separated flows. It is shown that the maximum shearing stress is the appropriate scale for the flows, while the reattachment length is required for scaling the streamwise skin friction, upstream-downstream flow direction intermittancy, static pressure recovery, and mean square surface pressure fluctuations. M.S.K.

A85-19571*# Princeton Univ., N. J. STRUCTURE OF THE WALL PRESSURE FLUCTUATIONS IN A SHOCK-INDUCED SEPARATED TURBULENT FLOW

K. C. MUCK, S. M. BOGDONOFF (Princeton University, Princeton, NJ), and J.-P. DUSSAUGE (Aix-Marseille II, Universite, Marseille, France; Princeton, University, Princeton, NJ) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs (Contract N60921-83-C-0166; NAGW-240)

(AIAA PAPER 85-0179)

This paper presents the results of an experimental study of the unsteady nature of a shock wave/turbulent boundary layer interaction. The interaction was generated using an unswept compression ramp. The incoming freestream Mach number was 2.9 and the flow was separated at the corner. An array of flush mounted miniature high frequency pressure transducers was used to make multi-channel measurements of the fluctuating wall pressure within the interaction. From the present results, an overall picture of the instantaneous structure of the unsteady shock system (as inferred from the wall pressure signals) can be constructed. The flow ahead of the corner can be considered as composed of two regions, namely the 'intermittent' region where there is essentially a single leading shock which exhibits significant streamwise 'flapping' and spanwise 'rippling', and the separated region where the flow experiences continuous compression.

Author

A85-19572#

MEASUREMENTS OF SEPARATING BOUNDARY LAYER AND WAKE OF AN AIRFOIL USING LASER DOPPLER VELOCIMETRY

A. NAKAYAMA (Douglas Aircraft Co., Long Beach, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. Research sponsored by the McDonnell Douglas Independent Research and Development Program. refs

(AIAA PAPER 85-0181)

Mean-flow and turbulence measurements have been made in the boundary layer and the wake of a supercritical airfoil model at an angle of attack of 12 deg. The Reynolds number based on chord was 1.2 million and the Mach number was 0.1. The flow included a trailing-edge separation and a laser Doppler velocimeter was used to measure the fluctuating velocities that reverse the direction. Measurements include surface pressure distribution, mean velocity, turbulent stresses, and triple products. Details of these quantities are presented. Some higher-order statistics of turbulence are presented and discussed. Statistics involving the spanwise fluctuations were not obtained. Author

A85-19573#

COMPUTATION OF UNSTEADY SHOCK-INDUCED VORTEX SEPARATION

S. OBAYASHI, K. KUWAHARA, and H. KUBOTA (Tokyo, University, Tokyo, Japan) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(AIAA PAPER 85-0183)

Transonic flows around an NACA0012 airfoil were simulated by directly solving the full Navier-Stokes equations without any turbulence model. The implicit LU factored scheme was used with improved accuracy. The results of unsteady computations without any turbulence model show the clear dependence of the flow on the Reynolds number, and agree qualitatively with experimental observations even at Reynolds numbers over a million. Unsteady shock-induced vortex separation was observed at all the Reynolds numbers. To check the results against experiment, the improved scheme was coupled with the Baldwin-Lomax turbulence model, obtaining excellent agreement with experiment. Author

A85-19582#

SUBSONIC WING ROCK OF SLENDER DELTA WINGS

P. KONSTADINOPOULOS, D. T. MOOK, and A. H. NAYFEH (Virginia Polytechnic Institute and State University, Blacksburg, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs

(Contract N00014-75-C-0381; NR PROJECT 061-201) (AIAA PAPER 85-0198)

Experiments which have been conducted to investigate the self-excited motion of a flat delta wing, which is free to roll about an axis parallel to its midspan chord, are presently simulated numerically. The solution obtained on the basis of both an unsteady vortex lattice method for aerodynamic loads and an integration of the equation of motion by means of a prediction-correction scheme provides complete histories of the motions of the flowfield and the wing simultaneously, fully accounting for dynamic-aerodynamic interaction. It is found that at sufficiently high incidence, small disturbances introduced into the flowfield grow and induce wing rock. The simulation shows the influence of the experimental parameters, and provides an explanation for differences in the observations.

A85-19587#

UNSTEADY AERODYNAMICS OF AN AIRFOIL ENCOUNTERING A PASSING VORTEX

J. C. WU, N. L. SANKAR, and T. M. HSU (Georgia Institute of Technology, Atlanta, GA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs

(Contract AF-AFOSR-82-0108; DAAG29-82-K-0094)

(AIAA PAPER 85-0203)

The problem of vortex airfoil interaction is analyzed using three approaches: (1) incompressible flow calculations using conformal mapping techniques, (2) incompressible viscous flow calculations using the vorticity-stream function formulation, and (3) compressible inviscid transonic flow calculations using the Euler equations. In the incompressible flow calculations the aerodynamic loads experienced by the airfoil are decomposed into components associated with distinct physical processes using a generalized aerodynamic forces and moments theory. Numerical results are presented for a NACA 0012 airfoil at zero angle of attack encountering a vortex of strength -0.20 V c at zero and 0.8 Mach number and for a NACA 64A006 airfoil at a free stream Mach number of 0.85 and zero angle of attack encountering a vortex of strength -0.2 V c. Results are compared with available theoretical and experimental data. Author

A85-19588*# Stanford Univ., Calif. CIRCULATION CONTROL AIRFOILS - PAST, PRESENT, FUTURE

N. J. WOOD (Stanford University, Stanford, CA) and J. N. NIELSEN (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 22 p. refs (AIAA PAPER 85-0204)

This paper presents a review of circulation control technology, its history, status and areas for further research and development. A brief description of the basic performance characteristics of circulation control airfoils are presented together with a more detailed discussion of some of the more important aerodynamic parameters dependencies. The unique capability of the airfoils to develop high lift coefficients independent of incidence over a range of operating conditions is demonstrated. Consideration is also given to the various stall conditions that have been experimentally observed and to the various theoretical formulations that have been attempted to explain these phenomena. Author

A85-19589#

PREDICTION OF SUBSONIC/TRANSONIC SEPARATED FLOW ABOUT AIRFOILS

F. TAVERNA (Grumman Aerospace Corp., Bethpage, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs (AIAA PAPER 85-0205)

A computational method is presented for the analysis of subsonic and transonic flow about airfoils which might have substantial separation. The objective of this effort was to eliminate the past requirement of using different analysis codes depending on the flow conditions. The inviscid flow solver comes from the Korn-Garabedian airfoil analysis code. This has been combined with an inverse integral compressible turbulent boundary-layer method. Results at both subsonic and transonic speeds are compared to experimental data for a NACA 0012 airfoil. Future plans are discussed. Author

A85-19590*# Illinois Univ., Urbana. A CLASS OF AIRFOILS HAVING FINITE TRAILING EDGE PRESSURE GRADIENTS

A. I. ORMSBEE (Illinois, University, Urbana, IL) and M. D. MAUGHMER (Pennsylvania State University, University Park, PA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (Contract NAG1-76)

(AIAA PAPER 85-0206)

Some new developments relevant to the design of single-element airfoils using potential flow methods are presented. In particular, the ramifications of the unbounded trailing edge pressure gradients generally present in the potential flow solution for the flow over an airfoil are examined, and the conditions necessary to obtain a class of airfoils having finite trailing edge pressure gradients developed. The incorporation of these conditions into the inverse method of Eppler for the design of low-speed airfoils is discussed, and designs generated using the modified scheme are presented for consideration. A detailed viscous analysis of one of these airfoils demonstrates a significant reduction in the strong inviscid-viscid interactions generally present near the trailing edge. These reductions offer the possibility of improved airfoil performance, as well as the possibility of improved accuracy in the methods of airfoil design and analysis. Author

A85-19591*# Rensselaer Polytechnic Inst., Troy, N. Y. SUPERCRITICAL AIRFOIL DRAG REDUCTION BY PASSIVE SHOCK WAVE/BOUNDARY LAYER CONTROL IN THE MACH NUMBER RANGE .75 TO .90

H. T. NAGAMATSU (Rensselaer Polytechnic Institute, Troy, NY), R. V. FICARRA (Grumman Aerospace Corp., Bethpage, NY), and R. DYER American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(Contract NAG1-330)

(AIAA PAPER 85-0207)

Airfoils operating in the transonic region are subject to large increases in drag due to shock wave/boundary layer interactions. The concept of passive shock wave/boundary layer control seeks drag reduction by placing a thin cavity with a porous top surface at the airfoil chordwise position where a shock wave would normally occur. The higher pressure behind the shock wave circulates flow through the cavity to the lower pressure ahead of the shock wave. The effects from this circulation prevent boundary layer separation and reduce entropy increases through the shock wave. In this investigation this concept is studied at a freestream Mach number range of .75 and .90. The Mach number distributions over the model, the wake impact pressure surveys used to determine profile drag and schlieren photographs for 2.8 percent porosity and solid airfoil cases are presented and compared. Results indicate that the profile drag coefficient can be reduced by as much as 40 percent through the use of this passive drag control system.

Author

A85-19592#

A FOURIER TRANSFORM METHOD FOR CALCULATING VELOCITY PROFILES ON AIRFOILS

D. E. WILSON (Texas, University, Austin, TX) and W. J. TEDESCHI American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs

(AIAA PAPER 85-0208)

A new method has been developed for predicting the unsteady, inviscid, incompressible flow field around a two-dimensional airfoil inside a porous-wall wind tunnel. Using Fourier Transform techniques, the inviscid flow field is solved in a unique manner to yield an approximate closed form integral solution. The solution form is that of a Fredholm integral equation of the second kind and is evaluated using numerical quadrature. Comparisons with other theoretical methods and experimental data are then presented. Author

A85-19593*# Grumman Aerospace Corp., Bethpage, N.Y. PREDICTION OF HIMAT RPRV COMPONENT INTERFERENCE EFFECTS AT TRANSONIC SPEEDS

J. LAIOSA (Grumman Aerospace Corp., Bethpage, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs (Contract NAS2-11424)

(AIAA PAPER 85-0213)

Detailed surface flow field analyses of the NASA Highly Maneuverable Aircraft Technology Remotely Piloted Research Vehicle (HiMAT RPRV) are described. Computational predictions are provided by a nonlinear finite difference transonic wing-body code. Component interference effects are obtained through modifications in lifting surface twist and camber boundary conditions. Complex aircraft interactions created by wing-tip fins, landing gear, and lower surface wing actuator fairings are included. Lifting surface viscous flow effects are modeled using a two-dimensional 'strip' boundary layer method. Correlations with flight test data presented demonstrate the high degree of accuracy achieved for this realistic aircraft configuration. This methodology and approach appears to be generally applicable to other multisurface configurations.

National Aeronautics and Space Administration. A85-19611*# Langley Research Center, Hampton, Va.

APPLICATION OF AXISYMMETRIC ANALOGUE FOR CALCULATING HEATING IN THREE-DIMENSIONAL FLOWS

H. H. HAMILTON, K. J. WEILMUENSTER (NASA, Langley Research Center, Space Systems Div., Hampton, VA), and F. R. DEJARNETTE (North Carolina State University, Raleigh, NC) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 16 p. refs (AIAA PAPER 85-0245)

A rapid, approximate method has been developed for calculating the heating rates on three-dimensional vehicles such as the Space Shuttle Orbiter and other advanced reentry configurations. The based on the axisymmetric analogue method is for three-dimensional boundary layers. It uses information obtained from a three-dimensional inviscid flowfield solution, such as HALIS. to calculate inviscid surface streamlines along which approximate heating rates are calculated independent of what happens along other streamlines. Three-dimensional effects are included through the metric coefficient that describes the divergence or convergence of streamlines. Boundary-layer edge properties are obtained from the inviscid flowfield solution by interpolating in the inviscid flowfield at a distance equal to the boundary-layer thickness away from the wall. This accounts, approximately, for the variable boundary-layer edge entropy. Using this method, heating calculations can be made along a typical streamline in a few seconds. This method has been used to accurately predict heating rates for simple shapes such as a spherically blunted cone and more complex shapes such as the Shuttle Orbiter for a variety of wind-tunnel and flight conditions. A unique feature of the method is its ability to accurately predict heating rates on the Shuttle Orbiter wing. Author

A85-19614#

A SIMPLE ANALYTICAL METHOD FOR PREDICTING AXISYMMETRIC TURBULENT JET FLOWFIELDS IN Δ FREESTREAM

C.-W. CHU (Northrop Corp., Aircraft Div., Hawthorne, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs. (AIAA PAPER 85-0251)

A simple global analysis of the effect of freestream or composition on centerline flow property decays in a turbulent jet are presented. A simple correlation between velocity and total temperature decays in turbulent subsonic and perfectly expanded supersonic jets is derived. An analytic method for calculating the jet half radii for constant-pressure self-similar turbulent jets with and without a freestream is developed. Together, these analyses form a method for predicted axisymmetric turbulent flowfields of subsonic and perfectly expanded supersonic jets statically or in a freestream. An example of a turbulent jet flowfield is given showing excellent agreement with test data. C.D.

A85-19617*# Continuum Dynamics, Inc., Princeton, N. J. SCALING LAWS FOR TESTING OF HIGH LIFT AIRFOILS UNDER HEAVY RAINFALL

A. J. BILANIN (Continuum Dynamics, Inc., Princeton, NJ) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs (Contract NASA ORDER L-71488-B)

(AIAA PAPER 85-0257)

The results of studies regarding the effect of rainfall about aircraft are briefly reviewed. It is found that performance penalties on airfoils have been identified in subscale tests. For this reason, it is of great importance that scaling laws be dveloped to aid in the extrapolation of these data to fullscale. The present investigation represents an attempt to develop scaling laws for testing subscale airfoils under heavy rain conditions. Attention is given to rain statistics, airfoil operation in heavy rain, scaling laws, thermodynamics of condensation and/or evaporation, rainfall and airfoil scaling, aspects of splash back, film thickness, rivulets, and flap slot blockage. It is concluded that the extrapolation of airfoil

performance data taken at subscale under simulated heavy rain conditions to fullscale must be undertaken with caution. G.R.

A85-19621*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

NUMERICAL SOLUTION OF THE FULL-POTENTIAL EQUATION FOR ROTORS AND OBLIQUE WINGS USING A NEW WAKE MODEL

I.-C. CHANG (NASA, Ames Research Center, Moffett Field, CA) and C. TUNG (U.S. Army, Aeromechanics Laboratory, Moffett Field, American Institute of Aeronautics and Astronautics, CA) Aerospace Sciences Meeting, 23rd, Reno, NV, Jan, 14-17, 1985. 7 p. refs

(AIAA PAPER 85-0268)

A three-dimensional, full-potential, quasi-steady code TFAR1 is proposed for calculating the transonic flow past a lifting helicopter rotor blade and oblique wing. The TFAR1 uses a two-dimensional nonlinear wake-model that allows a jump in velocity potential to propagate with the local fluid flow in the wake. Rotor calculations were made for a single blade at an advance ratio of 0.3, a rotational tip Mach number of 0.7, and at 0-degree incidence. A 1/7-scale model of the Cobra Operational Load Survey (OLS) rotor blade is calculated, and the pressure distributions are compared to the measurements for azimuth angles 0, 30, 60, 90, 120, and 150 degrees at the 95 percent spanwise station of the OLS blade. Furthermore, an oblique wing with Korn airfoil was calculated at the high transonic free-stream Mach number of 0.9791, zero incidence, and yaw angle of 40 degrees. The TFAR1, coupled with a helicopter performance code CAMRAD (Johnson, 1981), provides a full-potential code for calculating the entire flow field for a multiple-bladed rotor in transonic lifting forward flight. L.T.

A85-19622#

COMPARISON BETWEEN THEORETICAL AND EXPERIMENTAL FLOW FIELDS OF AN AIRFOIL WITH DEFLECTED SPOILER

C. S. LEE and S. BODAPATI (Joint Institute for Aeronautics and Acoustics, Stanford, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. Research supported by the Boeing Co. refs (AIAA PAPER 85-0269)

A two-dimensional vortex tracing method is developed to simulate the unsteady flow field of an airfoil with deflected spoiler. The airfoil-spoiler geometry is represented by vortex panels and the wake is modeled by discrete point vortices with viscous cores. Average velocities are taken at the sharp edges to avoid singularities. Merging schemes are used to reduce the vortices in the wake. The surface pressure distributions, mean velocity profiles and turbulent stresses in the wake, and Strouhal number are calculated and compared with the experimental results for various angles of attack and spoiler deflection. The comparisons show that the vortex method describes this unsteady flow field reasonably Author well.

A85-19624#

AERODYNAMIC PREDICTION OF ELIPTICALLY-SHAPED MISSILE CONFIGURATIONS USING COMPONENT BUILD-UP METHODOLOGY

S. R. VUKELICH (McDonnell Douglas Astronautics Co., St. Louis, American Institute of Aeronautics and Astronautics, MO) Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(AIAA PAPER 85-0271)

Methods for the aerodynamic design of elliptically shaped cross section configurations using component build-up techniques are described. Since these techniques are primarily for use in the preliminary or conceptual design environments, they are easily applied and use methods which have been proven for conventional missile shapes. A new method for accounting for fin-body interference is developed, and its accuracy is compared to experiment. Also included are comparisons to experiment for elliptical cross section body alone, winged elliptical bodies, and elliptical bodies with multiple lifting surfaces. Although the methods are applicable to a wide range of preliminary design configurations, a few problem areas remain; these are identified. Author

National Aeronautics and Space Administration. A85-19628*# Langley Research Center, Hampton, Va:

SUBSONIC PRESSURE DISTRIBUTIONS NEAR A WING-FIN **ARROW-WING** JUNCTURE OŃ. A SUPERSONIC **CONFIGURATION WITH WING-MOUNTED VERTICAL FINS**

J. K. HUFFMAN and C. H. FOX, JR. (NASA, Langley Research Center, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs

(AIAA PAPER 85-0276)

A generic supersonic arrow-wing configuration has been extensively studied to develop a consistent experimental data base to aid in verifying analytical prediction methods. One of the wing configurations studied was a twisted and cambered wing with wing-mounted vertical fins and trailing-edge flaps. The pressure data obtained on that configuration was limited in the wing-fin juncture region, and no pressures were obtained on the fin itself. However, detailed data in the juncture region and on the fin are essential to check out the analytical prediction methods. Therefore, the model was modified to provide details of the juncture pressure field as well as pressures on the fin. The results of this experimental investigation showed that the addition of a fin helped improve the wing pressure distribution outboard of the fin. Deflection of the trailing-edge flap did not adversely affect this trend. The pressure distributions on the vertical fin were generally affected more by change in angle of attack than by flap deflection. The spanwise pressure distribution on the fin itself indicated a load reversal with angle of attack. Author

A85-19629#

EFFECTS OF COVERING CONFIGURATIONS ON ULTRALIGHT WING AERODYNAMICS

J. F. MARCHMAN, III and R. M. FRENCH (Virginia Polytechnic Institute and State University, Blacksburg, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p.

(AIAA PAPER 85-0277)

Wind tunnel tests were conducted to determine the influence of wing covering configuration and material flexibility on the aerodynamics of a typical ultralight aircraft wing design. Configurations examined included full surface covering, covering of only the upper wing surface and covering the upper surface plus partial covering of the lower surface. Covering materials included flexible and heat shrunk surfaces as well as a rigid metal surface. The results of the work show substantial differences in some of the configurations and should serve as a warning to the builder of ultralight aircraft to use extreme caution in modifying wing designs by such actions as substituting full surface covering for partial surface covering of the wing. Author

A85-19630#

AERODYNAMICS OF AN ASPECT RATIO 8 WING AT LOW **REYNOLDS NUMBERS**

J. F. MARCHMAN, III (Virginia Polytechnic Institute and State University, Blacksburg, VA) and A. A. ABTAHI American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p.

(AIAA PAPER 85-0278)

Wind tunnel tests were conducted on a three-dimensional wing of aspect ratio 8 at chord based Reynolds numbers between 70,000 and 300,000. Lift forces and pitching moments were measured using a strain gauge force balance and drag obtained through the strain gauge method and the momentum deficit method. The results of the two methods are compared. Two different flow visualization techniques were used to gain additional understanding of the flow phenomena occurring. The presence of a hysteresis loop in stall is demonstrated. Wingtip effects are found to be confined to the tip region and there is no significant influence on the laminar separation bubble due to the three-dimensionality of the flow.

Author

A85-19631*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

STUDY OF WINGLETS APPLIED TO BIPLANES

P. D. GALL (NASA, Langley Research Center, Hampton, VA) and H. C. SMITH (Pennsylvania State University, University Park, PA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs (AIAA PAPER 85-0279)

This paper examines, both theoretically and experimentally, the possibility of improving the aerodynamic characteristics of a biplane configuration by adding winglets. Theoretical calculations show good agreement with experiment in predicting inviscid drag due to lift. Theoretical and experimental results indicate that the addition of winglets to an optimized biplane configuration can increase the ideal efficiency factor by up to 13 percent, as well as increasing the lift-curve slope and maximum lift coefficient. A theoretical analysis comparing the biplane with an optimized winglet to an equivalent monoplane indicates that the biplane has the potential for a 6.4-percent increase in L/D(max), and 13-percent increase in C(L) to the 3/2-power/C(D), the classical endurance parameter. Author

A85-19632#

LINEARIZED POTENTIAL FLOW ANALYSIS OF COMPLEX AIRCRAFT CONFIGURATIONS BY HISSS, A HIGHER ORDER PANEL METHOD

L. FORNASIER (Messerschmitt-Boelkow-Blohm GmbH, Munich, West Germany) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(AIAA PAPER 85-0281)

Following the higher-order approach pioneered by the PANAIR method, a new panel method - called HISSS - is presently being developed at MBB for the calculation of sub/supersonic linearized potential flows about arbitrary three-dimensional configurations. In this investigation, published PANAIR results have been used to validate HISSS capabilities in the analysis of complex aircraft configurations. Comparison of surface pressures, forces and moments and flowfield characteristics - presented for two aircraft configurations demonstrates the effectiveness of the present method as an engineering tool for the computer aided aerodynamic design of aircraft configurations at subsonic and supersonic speeds. Author

A85-19633#

APPLICATION OF CONTINUOUS VORTICITY PANELS TO GENERAL UNSTEADY TWO-DIMENSIONAL LIFTING FLOWS M. J. KIM and D. T. MOOK (Virginia Polytechnic Institute and State University, Blacksburg, VA) American Institute of Aeronautics

and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs

(AIAA PAPER 85-0282)

Continuous vorticity panels are used to model general unsteady two-dimensional lifting flows. The geometry of the airfoil is approximated by a series of short straight segments having end points that lie on the actual surface. The no-penetration condition is imposed at the mid-point of each segment and at discrete times. The wake is simulated by a system of discrete vortex cores, which move at the local particle velocity. At each time step a new core is placed at the trailing edge and the condition of constant circulation around wing and wake is imposed. Because the system is over-determined, an optimization scheme is used to obtain simultaneously the unknown values of the surface velocity at the end points of the segments and the unknown value of the circulation around the core at the trailing edge. Comparisons are made with known exact solutions and wind tunnel data for one and two component airfoils in steady flow, and with other computed results and one experiment for unsteady flow. The present approach provides an attractive alternative to those developed earlier, being easy to formulate, easy to use, and very accurate. Author

A85-19634#

CALCULATION OF STEADY FLOW ABOUT PROPELLERS BY MEANS OF A SURFACE PANEL METHOD

J. L. HESS and W. O. VALAREZO (Douglas Aircraft Co., Long Beach, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. Navy-sponsored research. refs

(AIAA PAPER 85-0283)

A general method for making detailed calculations of flow about propellers with centerbodies has been constructed by adapting a surface panel method. Apparently this is the first method capable of obtaining reliable surface pressure distributions in the blade leading-edge region. New features of the program include input of an axisymmetric nonuniform onset flow, provision for blade symmetry, and generation of the helical wake, including a special far-wake approximation. Calculated blade pressure distributions and propeller efficiencies agree well with experimental data for the two propellers that have been considered. Several sample calculations have been included. Author

A85-19635#

OPTIMIZED DISCRETE-SINGULARITY REPRESENTATION OF **AXISYMMETRIC BODIES**

J. C. JANIKOWSKY (U.S. Naval Postgraduate School, Monterey, CA; U.S. Navy, Norfolk Naval Shipyard, Portsmouth, VA) and T. SARPKAYA (U.S. Naval Postgraduate School, Monterey, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (AIAA PAPER 85-0284)

A rational methodology has been developed whereby three-dimensional axial singularities may be used to represent the potential flow past an axisymmetric body of arbitrary profile at angles of attack. For this purpose the strength and position of the singularities along the axis of the body and the position and number of the control points on the surface of the body were optimized so as to minimize the normal velocity through the use of the method of least squares and the Automated Design Synthesis optimization technique. For flows at angle of attack, the axial and cross flow potentials have been superimposed to obtain the resulting three-dimensional velocity and pressure distributions. The results have shown that the use of two types of optimization in the determination of the strength and position of the singularities yields the desired body shape and the flow characteristics with excellent accuracy. A comprehensive computer code has been developed to enable one to calculate most of the practically significant body shapes. Author

A85-19641*# North Carolina State Univ., Raleigh. EULER CALCULATIONS FOR MULTIELEMENT AIRFOILS **USING CARTESIAN GRIDS**

D. K. CLARKE, H. A. HASSAN (North Carolina State University, Raleigh, NC), and M. D. SALAS (NASA, Langley Research Center, Theoretical Aerodynamics Branch, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (Contract NCC1-22)

(AIAA PAPER 85-0291)

A finite volume formulation for the Euler equations using Cartesian grids is presented and used to study complex two-dimensional configurations. The formulation extends methods developed for the potential equation to the Euler equations. Results using this approach for single element airfoils are shown to be competitive with and as accurate as other methods that employ mapped grids. Further, it is demonstrated that this method provides a simple and accurate procedure for solving flow problems involving multielement airfoils. Author

بالمستحج للترا التهيدا A85-19642*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

NUMERICAL SOLUTION OF THE TWO-DIMENSIONAL EULER EQUATIONS BY SECOND-ORDER UPWIND DIFFERENCE SCHEMES

J. Y. YANG (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs (AIAA PAPER 85-0292)

Two time-level, five-point explicit and implicit upwind difference schemes based on the characteristic flux difference splitting concept have been developed for the two-dimensional Euler equations. The method is conservative, second-order accurate in time and space, and general coordinate systems are used to treat complex geometries. Nonlinear flux limiters are employed to yield oscillation free sharp shock profiles. Upstream interpolation is used to yield a class of higher-order upwind schemes which closely mimic the locally one-dimensional method of characteristics (with fixed time intervals) through operator splitting. Numerical results have been obtained for a plane shock reflection and for flow over a circular arc in a channel. Characteristics of upwind TVD schemes, as applied to two-dimensional flows with embedded shocks are discussed. Author

A85-19643#

MULTIGRID SOLUTION OF THE EULER EQUATIONS USING IMPLICIT SCHEMES

A. JAMESON and S. YOON (Princeton University, Princeton, NJ) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs (AIAA PAPER 85-0293)

A multigrid method for implicit schemes of the approximate factorization type is described. The application of the method coupled with an Alternating Direction Implicit scheme to the solution of the Euler equations for transonic flow over an airfoil has resulted in very rapid convergence. The number of time steps required to reach a steady state is reduced by an order of magnitude by the introduction of multiple grids. Author

National Aeronautics and Space Administration. A85-19644*# Ames Research Center, Moffett Field, Calif.

RELAXATION APPROACH TO **PATCHED-GRID** CALCULATIONS WITH THE EULER EQUATIONS

M. M. RAI (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 19 p. refs (AIAA PAPER 85-0295)

A conservative zonal-boundary condition that was used with explicit integration schemes is extended to implicit, upwind, relaxation schemes; in particular to the Osher scheme. The rate of convergence was found to increase considerably with the use of the implicit, relaxation-zonal scheme when compared to the explicit scheme. The relaxation-zonal scheme has also been used in a time-accurate mode. Results demonstrating the time accuracy of the scheme and the feasibility of performing calculations in cases where some parts of the given system move relative to others (for example, rotor-stator configurations) are presented.

Author

A85-19648*# Princeton Univ., N. J.

THE DISTORTION OF A SUPERSONIC TURBULENT BOUNDARY LAYER BY BULK COMPRESSION AND SURFACE CURVATURE

A. J. SMITS (Princeton University, Princeton, NJ) and M. JAYARAM American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(Contract NAGW-240)

(AIAA PAPER 85-0299)

An experimental investigation is conducted of the effects of bulk compression and streamline curvature on a turbulent supersonic boundary layer whose incoming Mach number is 2.87. Two different, constant-radius curved wall models were used; the

total turning angle in both cases was fixed at 8 deg. While the amplification of the normal stress was approximately the same in both models, the amplification of the shear stress was greater in the one with delta(o)/R value 0.1 than in the model with a value of 0.02. The flow over the latter model appears to be especially complex. 00

A85-19649#

A NAVIER-STOKES INVESTIGATION OF A CIRCULATION CONTROL AIRFOIL

H. A. BERMAN (David W. Taylor Naval Ship Research and Development Center, Bethesda, MD) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(AIAA PAPER 85-0300)

A time-dependent, finite difference method is used in solving the complete, two-dimensional Reynolds-averaged Navier-Stokes equations for the turbulent flow about a circulation-control airfoil. The conditions simulated numerically are based on a transonic wind tunnel experiment, with the data points investigated corresponding to conditions immediately before stall. Numerical results obtained for the flow field over the aft 50 percent of the airfoil are in qualitative agreement with the experimental data, and furnish insights into the fluid dynamics of circulation control airfoils. O.C.

A85-19650*# Maryland Univ., College Park. A STUDY OF THE EFFECTS OF NUMERICAL DISSIPATION ON THE CALCULATION OF SUPERSONIC SEPARATED FLOWS

G. KURUVILA and J. D. ANDERSON, JR. (Maryland, University, College Park, MD) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985, 16 p. refs

(Contract NCC1-41)

(AIAA PAPER 85-0301)

An extensive investigation of the effect of numerical dissipation on the calculation of supersonic, separated flow over a rearward-facing step is carried out. The complete two-dimensional Navier-Stokes equations are solved by means of MacCormack's standard explicit, unsplit, time-dependent, finite difference method. A fourth-order numerical dissipation term is added explicitly. The magnitude of this term is progressively varied, and its consequences on the flowfield calculations are identified and studied. For a cold-wall, heat transfer case, numerical dissipation had a major effect on the results, particularly in the separated region. However, rather dramatically for an adiabatic wall case, numerical dissipation had virtually no effect on the results. The role of grid size on both the influence of numerical dissipation, and on the overall accuracy of the separated flow solutions is discussed. Author

A85-19651*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

SPECTRAL METHODS FOR MODELING SUPERSONIC CHEMICALLY REACTING FLOW FIELDS

J. P. DRUMMOND, T. A. ZANG (NASA, Langley Research Center, High-Speed Aerodynamics Div., Hampton, VA), and M. Y. HUSSAINI (NASA, Langley Research Center, Institute for Computer Applications in Science and Engineering, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs (AIAA PAPER 85-0302)

A partial implicit numerical algorithm has been developed for solving the equations describing chemically reacting supersonic flows. The algorithm employs a two-stage Runge-Kutta method for integrating the equations in time and a Chebyshev spectral method for integrating the equations in space. The accuracy and efficiency of the new technique have been assessed by comparison with an existing implicit finite-difference procedure for modeling chemically reacting flows. The comparison showed that the new procedure yielded equivalent accuracy on much coarser grids as compared to the finite-difference procedure with resultant significant gains in computational efficiency. Author

A85-19652#

CRITICAL LAYER CONCEPT RELATIVE TO HYPERSONIC **BOUNDARY LAYER STABILITY**

H. T. NAGAMATSU (Rensselaer Polytechnic Institute, Troy, NY) and R. E. SHEER, JR. (GE Research and Development Center, Schenectady, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (AIAA PAPER 85-0303)

At hypersonic Mach numbers, the critical layer height approaches the outer edge of laminar boundary layer and the phase velocity of the disturbance is subsonic relative to the free stream velocity. Small disturbances become amplified to form turbulent bursts in the transition region for subsonic to hypersonic laminar boundary layers. The Orr-Sommerfeld equation for the stability of the boundary layer is valid for hypersonic boundary layers. Wall cooling and favorable pressure gradient effects on the stability of the boundary layer become small at hypersonic Mach numbers because of the outward movement of the critical layer with Mach number. Author

A85-19653*# Grumman Aerospace Corp., Bethpage, N.Y. THE COMPUTATIONAL TREATMENT OF SUPERSONIC WAKE FLOWS IN INCOREL

M. J. SICLARI (Grumman Research and Development Center, Bethpage, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs

(Contract NAS1-16758)

(AIAA PAPER 85-0304)

Supersonic wake flows are computed in both conical and three-dimensional full potential flows by modeling the wake as a planar cut with a potential discontinuity. Continuity of pressure is satisfied exactly on the wake cut by computing the necessary potential jump at each wake cut grid point. In the conical wake problem, the jump in potential vanishes in the crossflow symmetry plane. Generally, good correlation is achieved for fully three-dimensional wake flows with the planar wake approximation. Matching pressures in the isolated wake flow leads to small variations in the spanwise jump in potential. On the other hand, a small variation in the jump in potential near the wing tip flow can lead to a significant loading in the wake flow if the pressures are not matched. V.L.

A85-19686*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

DETERMINATION OF RAREFIED-FLOW AERODYNAMICS OF THE SHUTTLE ORBITER FROM FLIGHT MEASUREMENTS ON STS-6 AND STS-7

R. C. BLANCHARD and G. M. BUCK (NASA, Langley Research Center, Space Systems Div., Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs

(AIAA PAPER 85-0347)

This report presents the flight data results from the High Resolution Accelerometer Package (HiRAP) experimment on the sixth and seventh Shuttle missions (i.e. STS-6 and STS-7). The data have been reduced to produce aerodynamic force coefficients, principally L/D in the rarefied flow regime. Also, a technique is used to extract approximate body-axis aerodynamic coefficients from the flight data. Comparisons of the rarefied transition flow aerodynamic behavior between the two sets of flight data indicate differences, primarily in the free-molecule flow coefficients; i.e. STS-7 shows a free-molecule flow behavior which correlates with diffuse surface reflection conditions, while STS-6 does not. The data have also been used to estimate the density profiles in the atmosphere. The atmospheric density is generated from 60 to 160 km from each flight. The density profiles produced have a primary wave structure and differences are observed between the two sets of flight data. A new rarefied transitional flow aerodynamic bridging formula has been generated from the flight data. Comparisons with the flight bridging formula and existing Monte Carlo and wind-tunnel data are made. Author
02 AERODYNAMICS

A85-19688#

REGARDING PARAMETRIC INVESTIGATIONS OF SLENDER CONE NOSE BLUNTNESS EFFECTS

L. E. ERICSSON (Lockheed Missiles and Space Co., Inc., Sunnyvale, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs

(AIAA PAPER 85-0349)

The well documented effect of nose bluntness on the hypersonic aerodynamics of slender cones is analyzed. It is shown that the combined effect of nose bluntness and semi-cone angle can be represented by a scaling parameter, and that the scaling concept can be extended to include the effects of moderate angles of attack. Using this generalized scaling concept it can be demonstrated that the approximation on which it is based introduces errors that are substantially smaller than the differences between tests in different wind tunnels. Thus, one can conclude that further parametric investigations of the effect of nose bluntness on hypersonic slender cone aerodynamics are not needed.

Author

A85-19689*# Vigyan Research Associates, Inc., Hampton, Va. AN ATTACHED FLOW DESIGN OF A NONINTERFERING LEADING EDGE EXTENSION TO A THICK DELTA WING

F. GHAFFARI (Vigyan Research Associates, Inc., Hampton, VA) and J. E. LAMAR (NASA, Langley Research Center, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(AIAA PAPER 85-0350)

The analytical procedure presented for leading edge extension (LEE) determination, in keeping with such design criteria as noninterference at the wing design point, is applied to thick delta wings. The LEE device thus defined is to be mounted on a wing along a dividing stream surface that is associated with an attached flow design lift coefficient greater than zero. The delta wing in question is of twisted and cambered type. It is demonstrated that span reductions for the candidate LEEs has the most detrimental effect on overall aerodynamic efficiency, irrespective of area or shape. O.C.

A85-19690#

PASSIVE CONTROL EFFECTS ON FLOW SEPARATION AROUND A PROTUBERANCE AT HIGH SUBSONIC SPEED F. L. SMITH (USAF, Weapons Laboratory, Kirtland AFB, NM), D. C. CHOU (New Mexico, University, Albuquerque, NM), and R. K. DE JONCKHEERE American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(AIAA PAPER 85-0351)

Unsteady surface pressure and oil flow data have been collected for several fairing configurations surrounding a blunt protuberance at high subsonic speed. The goal was to reduce the unsteadiness of the separated flow region around the blunt body by passive flow control techniques to enhance the optical propagation quality. Unsteady pressure data in the form of rms pressure fluctuations, power spectral density and cumulative power plots, and flow visualization data are presented for some turret/fairing configurations tested at Mach numbers of 0.55, 0.65, and 0.75. From the analysis of the unsteady pressure data and flow visualization from the oil flow photographs, it is evident the surface pressure fluctuation levels can be dramatically reduced through passive flow control. This suggests the unsteadiness in the separated wake and shear layer regions around the protuberance are also reduced, which means the optical transmission quality of the flow field is improved. Author

A85-19691#

THE INFLUENCE OF CAMBER VARIATION ON THE AERODYNAMICS OF CIVIL TRANSPORT AIRCRAFT

J. SZODRUCH (Messerschmitt-Boelkow-Blohm GmbH, Bremen, West Germany) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. Research supported by the Bundesministerium fuer Forschung und Technologie. refs

(AIAA PAPER 85-0353)

The paper discusses results of two research programs which are concerned with camber modifications on wings of existing aircraft configurations. The experimental investigations revealed improvements in buffet boundary, in lift-to-drag ratio and wing root bending moment. These results are used to formulate a new wing concept with variable camber during cruise flight. Author

A85-19692#

AFTERBODY DRAG REDUCTION BY VORTEX GENERATORS

W. CALARESE, W. P. CRISLER, and G. L. GUSTAFSON (USAF, Flight Dynamics Laboratory, Wright-Patterson AFB, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs (AIAA PAPER 85-0354)

An experimental investigation was performed on the effects of vortex generators on the total drag of a 1/72 scale model of a C-130 aircraft. Vortex generators energize low energy boundary layer flow and delay separation in regions of high adverse pressure gradients. The C-130 aircraft model was selected for the experiment because of its highly up-swept afterbody where the flow is characterized by very high adverse pressure gradients. Results show an appreciable drag reduction for some of the configurations tested. Author

A85-19696*# National Aeronautics and Space Administration. Lyndon B. Johnson Space Center, Houston, Tex.

A THREE-DIMENSIONAL NAVIER-STOKES/EULER CODE FOR BLUNT-BODY FLOW COMPUTATIONS

C. P. LI (NASA, Johnson Space Center, Houston, TX) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 21 p. refs (AIAA PAPER 85-0361)

The formulation computation method of an improved version the three-dimensional Navier-Stokes/Euler computation algorithm of Li (1981) for the numerical simulation of blunt-body reentry flows are discussed, and results for five sample problems are presented graphically. The vector notation of the coordinate systems is defined; the governing equations are presented in full; the Jacobian matrices and damping terms of the factorization technique (based on the alternating-direction implicit procedure of Beam and Warming, 1978) are explained; and the capabilities, limitations and proper use of the code are summarized. Examples presented include the equilibrium-flow problem for Shuttle-orbiter reentry at Mach 22 and angle of attack 40.8 deg and the perfect-gas problem of an aerobraking orbital-transfer vehicle with an ellipsoidal/60-deg cone and a toroidal sonic shoulder. The advantages of the improved code in terms of accuracy and computation time are indicated. T.K.

A85-19698#

A NAVIER-STOKES CALCULATION OF 3-D, TURBULENT FLOW NEAR A PROPELLER IN A SHEAR FLOW

D. H. PELLETIER (Virginia Polytechnic Institute and State University, Blacksburg, VA; Montreal, Universite, Montreal, Canada) and J. A. SCHETZ (Virginia Polytechnic Institute and State University, Blacksburg, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 14 p. Navy-supported research. refs (AIAA PAPER 85-0365)

A numerical procedure based on the primitive variable Navier-Stokes equations is applied to the simulation of the three-dimensional flow near a propeller in a shear flow. The Navier-Stokes equations are solved by a Penalty Finite Element Method. The propeller is modelled as an actuator disk, and the direct simulation of a given propeller is considered in detail. Turbulent transport is modeled by an integrated Turbulent Kinetic Energy equation. This approach results in a robust numerical algorithm. Detailed comparison with wind tunnel measurements shows good prediction of velocity and pressure. The high accuracy of the swirl prediction is a major improvement over previous analyses. Author

A85-19699*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

RECENT ADVANCES IN COMPUTATIONAL TRANSONIC AERODYNAMICS

J. C. SOUTH, JR. (NASA, Langley Research Center, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs

(AIAA PAPER 85-0366)

The near-term prospects are discussed for calculation of viscous transonic flow fields about realistic configurations at full-scale Reynolds numbers. Three basic algorithms are considered: The central-difference, three-factor ADI method; the central-difference, explicit, multistep Runge-Kutta method with multigrid acceleration; and the relaxation method for the upwind-differenced, flux-split equations. Each method has distinct advantages and disadvantages regarding stability, convergence rate, and vectorizability. It appears that computation times can be 15 to 60 hours on the latest super computers unless 3D algorithms are improved to perform as well as current 2D algorithms. Author

A85-19700*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

BREAKDOWN OF THE CONSERVATIVE POTENTIAL EQUATION

M. D. SALAS and C. R. GUMBERT (NASA, Langley Research Center, Transonic Aerodynamics Div., Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 15 p. refs (AIAA PAPER 85-0367)

The conservative full-potential equation is used to study transonic flow over five airfoil sections. The results of the study indicate that once shock waves are present in the flow, the qualitative approximation is different from that observed with the Euler equations. The difference in behavior of the potential eventually leads to multiple solutions. Author

A85-19701*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

THE NUMERICAL SIMULATION OF STEADY TRANSONIC ROTATIONAL FLOW USING Α DUAL POTENTIAL FORMULATION

N. M. CHADERJIAN and J. L. STEGER (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs (AIAA PAPER 85-0368)

A finite-difference method is presented that simulates steady transonic rotational flow of an inviscid fluid by representing the velocity field as the sum of scalar and vector potentials. This dual potential velocity decomposition extends the validity of the scalar (full) velocity potential to include vorticity. The inclusion of a vector potential also permits an alternate treatment of lift that does not require a circulation wake cut. This is accomplished by specifying the vector potential as a constant on the airfoil surface in order to satisfy a Kutta condition. The governing equations are solved as iteratively decoupled scalar equations using approximate factorization techniques, and the overall efficiency approaches that of the full potential equation. The governing equations are able to convect entropy and vorticity throughout the flow field and are equivalent to the Euler equations in continuous flow domains, however at shocks the Rankine-Hugoniot entropy jump must be supplied. An entropy correction method is presented and verified with transonic airfoil solutions of the Euler equations. Author

A85-19702#

SHOCK WAVES IN TRANSONIC CHANNEL FLOWS AT MODERATE REYNOLDS NUMBER

(USAF, MACE Wright Aeronautical Laboratories. Wright-Patterson AFB, OH) and T. C. ADAMSON, JR. (Michigan, University, Ann Arbor, MI) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985, 11 p. refs

(AIAA PAPER 85-0369)

The behavior of shock waves in transonic channel flow with varying Reynolds and Prandtl numbers is examined using analytical and numerical methods. It is shown that the location of the sonic line within the structure of a shock wave is independent of Reynolds number and is coincident with the location of the corresponding discontinuous wave in the limit as Reynolds number tends to infinity. Also, in a numerical solution, truncation errors and artificial viscosity produce a smeared shock wave which is similar to that found in a flow at moderate Reynolds number. Thus, this research lends support to the commonly accepted supposition that the position of the sonic line within the structure of a numerical shock wave can be adopted as the location of the corresponding shock wave in inviscid flow. Author

A85-19703#

VISCOUS/INVISCID INTERACTION ANALYSIS OF TRANSONIC SHOCK INDUCED SEPARATED FLOW INCLUDING NORMAL PRESSURE GRADIENTS

D. E. EDWARDS, J. E. CARTER (United Technologies Research Center, East Hartford, CT), and M. M. HAFEZ (Computer Dynamics, Inc., Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs

(Contract F49620-81-C-0041)

(AIAA PAPER 85-0371)

An analysis based on an Interacting Boundary Layer Theory is presented for the prediction of transonic shock-wave, boundary-layer interaction with emphasis on turbulent separated flow. In this analysis finite difference techniques are used to iteratively solve the viscous layer equations, expressed in a defect form, coupled to a stream function representation of the inviscid flow. Normal pressure gradients and imbedded shock effects are included in this analysis. Favorable comparisons which have been obtained with the separated flow data of Kooi demonstrate that for transonic shock induced separation the effect of displacement thickness interaction dominates over that produced by imbedded shock effects and normal pressure gradients. Calculations made with a modified algebraic turbulence model demonstrate that for separated flow cases the computed results are more sensitive to the turbulence model than to whether or not normal pressure gradients are included. Author

A85-19705#

NAVIER-STOKES COMPUTATIONS OF AXISYMMETRIC TRANSONIC FLOWS WITH A TWO-EQUATION MODEL OF TURBULENCE

J. SAHU (U.S. Army, Ballistics Research Laboratory, Aberdeen Proving Ground, MD) and J. E. DANBERG (Delaware, University, Newark, DE) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs

(AIAA PAPER 85-0373)

Computational techniques developed for describing the aerodynamics of artillery shell flight are presented. A two-equation turbulence model (TET) is introduced into a thin-layer azimuthally-invariant, time-dependent Navier-Stokes model which features the same implicit algorithm and generalized geometry. The TET, a kappa-epsilon model, is modified to fit a conformal coordinate system by adjusting the expressions for the turbulent kinetic energy and dissipation rate. Solutions are obtained with the Beam-Warning (1977) fully implicit, approximately factored finite difference technique after specifying boundary conditions at the wall. The results of sample calculations for an attached flow over an axisymmetric projectile and separated flow over an axisymmetric bump model are provided in terms of the surface pressures, velocity, turbulent kinetic energy, dissipation rate, and the Re'shear stress profiles. Comparisons with experimental data confirms that the kappa-epsilon model is valid for describing the wake or base flow behind a projectile. M.S.K.

A85-19708#

IS THE FREE FLIGHT/WIND TUNNEL EQUIVALENCE CONCEPT VALID FOR UNSTEADY VISCOUS FLOW?

L. E. ERICSSON (Lockheed Missiles and Space Co., Inc., Sunnyvale, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(AIAA PAPER 85-0378)

The extent to which unsteady flow has been numerically described in dynamic stall conditions around compressor and helicopter blades for which wind tunnel data are available is assessed. The stall behavior of the blades has normally been tested in wind tunnels after calculations have predicted the onset of stall at a specific angle of attack (AOA) and rate of change. It is noted that the nonuniform velocity distribution at a compressor inlet produces a continuously varying AOA at the blades. Separation on the lee side is then delayed when the free stream accelerates and is induced when the free stream decelerates. Separation delay is associated with a lift coefficient overshoot that is proportional to the blade plunging velocity, wherein a vortex is shed at the end of the upstroke and produces lift. Wind tunnel data for unsteady flow, obtained by accelerating the flow over the airfoils, does not provide data on the overshoot and therefore does not represent helicopter blade encounters with gusts. M.S.K.

A85-19730*# Ohio State Univ., Columbus.

DETAILED MEASUREMENTS OF THE FLOWFIELD IN THE VICINITY OF AN AIRFOIL WITH GLAZE ICE

M. B. BRAGG and W. J. COIRIER (Ohio State University, Columbus, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. NASA-supported research. refs

(AIAA PAPER 85-0409)

An experimental study has been conducted in the OSU subsonic tunnel to measure the characteristics of the separation bubble on an airfoil with glaze ice. A measured glaze ice accretion on a NACA 0012 airfoil was simulated in wood for this dry tunnel test. The 21 inch chord model was pressure belted and the ice shape internally tapped to obtain surface pressures, lift and moment coefficients. A wake survey probe was used to obtain airfoil drag. The separation bubble was explored by measuring the time averaged velocities using a split film probe. The probe was positioned using a computer controlled two-dimensional traversing system. In this paper, airfoil lift, drag, and moment coefficient data are compared for the airfoil with and without glaze ice. Velocity profiles in the separation bubble are presented for several chordwise stations at three angles of attack. The ice shape caused a severe lift and drag penalty. The velocity profiles show clearly the large bubble geometry, regions of reversed flow, and bubble reattachment. Author

A85-19731*# Akron Univ., Ohio.

PROGRESS IN DEVELOPMENT OF A NAVIER-STOKES SOLVER FOR EVALUATION OF ICED AIRFOIL PERFORMANCE

M. G. POTAPCZUK (Akron, University, Akron, OH) and P. M. GERHART (Evansville, University, Evansville, IN; Akron, University, Akron, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 19 p. refs

(Contract NAG3-416)

(AIAA PAPER 85-0410)

A method is being developed for evaluation of the flow field behavior about an airfoil with significant ice accretion on the leading edge. The computer code, being evaluated for this purpose, solves the Navier-Stokes equations in a body-fitted curvilinear coordinate system. This requires the use of a grid generation code to transform the x-y coordinates of the physical space into xi-eta coordinates of the computational space. Evaluation of the suitability of these two codes for predicting iced airfoil performance is presently being carried out in anticipation of use in an overall icing analysis effort. Results of this evaluation to date indicate good correlation with known information on clean airfoils. Preliminary results for rime and glaze, iced airfoil shapes are also presented. Author

A85-19732#

COMPUTATIONAL PARTICLE TRAJECTORY ANALYSIS ON A 3-DIMENSIONAL ENGINE INLET

J. J. KIM (Boeing Military Airplane Co., Wichita, KS) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. Research supported by the Boeing Military Airplane Co. refs (AIAA PAPER 85-0411)

The paper discusses a computational particle trajectory analysis code applied to the problem of water droplet impingement on a 3-dimensional engine inlet. The droplet equation of motion is solved numerically by a fourth order Adams predictor-corrector scheme. The method utilizes state-of-the-art parametric surface modeling techniques and computational fluid dynamics code to predict local impingement efficiency distribution on a representative 3-dimensional engine inlet configuration. Results are presented for a typical take-off power setting at two angles of attack. Comparison with test results for the classical problem of droplet impingement on a sphere is also presented. Author

A85-19733*# Atmospheric Science Associates, Bedford, Mass. THREE-DIMENSIONAL AIRFLOW AND HYDROMETEOR TRAJECTORY CALCULATION WITH APPLICATIONS

H. G. NORMENT (Atmospheric Science Associates, Bedford, MA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. Army-NASA-sponsored research. refs

(AIAA PAPER 85-0412)

Numerical codes developed to model potential flows about three-dimensional bodies and applied to examining the flowfields around aircraft nose probes for gathering hydrometeor data are described. The potential flow code accounts for lifting or nonlifting surfaces, the effects of lift vorticity, inlet flows, and compression effects. Particle trajectories are calculated using particle equations of motion, with note taken of conditions in both the far- and near-fields of the flow. Graphic projections of the trajectories can be made from any view angle using another code. The codes also contain routines for handling flow velocities around arrays of spatial locations, trajectory arrays, and the effects of flow distortion on the particle flux. M.S.K.

A85-19738#

BODY FLOW FIELD SIMULATION AND FORCE/MOMENT PREDICTION AT TRANSONIC SPEEDS

B. S. ROSEN (Grumman Aerospace Corp., Bethpage, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs (AIAA PAPER 85-0423)

Historically, investigators have devoted more attention to transonic wing-type flow simulations than to body-type flows. Full potential methods for 2-D axisymmetric flow have been developed, but have not been extended to treat the 3-D lifting case. Small disturbance methods for the inviscid treatment of bodies at incidence are available, but these impose boundary conditions on a constant cross-section shell which only approximates the true body shape. During a recent study, long-standing problems associated with the small disturbance/shell formulation were resolved when a grid which conforms to the true body shape was introduced. The resulting small disturbance/conformal grid computational method is described. Correlations with experimental data and 2-D full potential calculations are included. Author

A85-19740*# Grumman Aerospace Corp., Bethpage, N.Y. TRO-2D - A CODE FOR RATIONAL TRANSONIC AERODYNAMIC OPTIMIZATION

W. H. DAVIS, JR. (Grumman Aerospace Corp., Bethpage, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (Contract NAS1-17292)

(AIAA PAPER 85-0425)

Features and sample applications of the transonic rational optimization (TRO-2D) code are outlined. TRO-2D includes the airfoil analysis code FLO-36, the CONMIN optimization code and a rational approach to defining aero-function shapes for geometry modification. The program is part of an effort to develop an aerodynamically smart optimizer that will simplify and shorten the design process. The user has a selection of drag minimization and associated minimum lift, moment, and the pressure distribution, a choice among 14 resident aero-function shapes, and options on aerodynamic and geometric constraints. Design variables such as the angle of attack, leading edge radius and camber, shock strength and movement, supersonic pressure plateau control, etc., are discussed. The results of calculations of a reduced leading edge camber transonic airfoil and an airfoil with a natural laminar flow are provided, showing that only four design variables need be specified to obtain satisfactory results. M.S.K.

A85-19742#

COMPUTATIONAL AERODYNAMIC DESIGN OF THE GULFSTREAM IV WING

R. M. CHANDRASEKHARAN, W. R. MURPHY (Gulfstream Aerospace Corp., Savannah, GA), F. P. TAVERNA, and C. W. BOPPE (Grumman Aerospace Corp., Bethpage, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. (AIAA PAPER 85-0427)

A wing has been designed for the Gulfstream IV aircraft with the objective of improving upon the aerodynamic performance of the Gulfstream III. Computational methods capable of simulating the flow about this configuration, complete with nacelles and winglets, were implemented to enhance the probability that the desired effects would be verified by wind tunnel experimentation. Test results from the ARA Transonic Wind Tunnel at Bedford, England, confirmed all pre-test predictions. The aerodynamic improvements will result in a G-IV range increment of over 300 nautical miles.

A85-19746#

SHOCK INDUCED VORTICES ON ELLIPTIC CONES IN SUPERSONIC FLOW

F. MARCONI (Grumman Aerospace Research and Development Center, Bethpage, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs

(Contract F49620-84-C-0056)

(AIAA PAPER 85-0433)

A numerical study of the conical, supersonic, inviscid flow about elliptic cross section cones is presented. Although the flow is assumed inviscid, the vorticity produced by the shock system can cause the formation of vortices. The Euler equations are solved and all shock waves are fit as discrete discontinuities. This phenomenon has been shown to be a valid solution of the Euler equations. The production of vorticity by shock waves in the flow about wing-type bodies is studied. The vorticity in the flow field that may be shed from a separating boundary layer is not considered in this paper. The computed flow fields are compared with experimental data, full potential calculations and results from other Euler solvers.

A85-19747#

SPLIT-FLUX-VECTOR SOLUTIONS OF THE EULER EQUATIONS FOR THREE-DIMENSIONAL CONFIGURATIONS

J. E. DEESE (McDonnell Douglas Research Laboratories, St. Louis, MO) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. Research supported by the McDonnell Douglas Independent Research and Development Program. refs

(AIAA PAPER 85-0434)

A numerical solution method for the three-dimensional unsteady Euler equations is developed using flux-vector-splitting concepts. A finite-volume spatial discretization is applied to the equations written in body-conforming curvilinear coordinates. An explicit upwind predictor-corrector method is employed to integrate the spatially discretized equations in time. The resulting algorithm is second order in space and time, uses local time steps to accelerate convergence, and is stable for a Courant number of two. Results for wings in subsonic, transonic, and supersonic flow are compared with experimental data and the predictions of a central-difference, finite-volume Euler code where available. Author

A85-19748#

FINITE VOLUME SOLUTION OF THE TWO-DIMENSIONAL EULER EQUATIONS ON A REGULAR TRIANGULAR MESH

A. JAMESON and D. MAVRIPLIS (Princeton University, Princeton, NJ) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs (AIAA PAPER 85-0435)

Rectangular and triangular grids are compared for solution of the Euler equations for two-dimensional transonic flow around an airfoil. A Karman-Trefftz transformation is used to map the airfoil to a near-circle and a family of near-circles is then generated, together with radial lines to form a quadrilateral grid. Drawing diagonals in the resulting grid produces a triangular mesh. The Euler equations are then discretized to obtain the pressure, density, velocity, total energy, and total enthalpy. Extra dissipation terms are added to prevent decoupling between odd and even cells and the boundary and time-stepping schemes are defined. A multigrid treatment with high frequency error damping characteristics is applied to accelerate the convergence. Sample calculations for a NACA 0012 airfoil are provided. The accuracy is found to be comparable to that found with a quadrilateral grid.

M.S.K.

A85-19749*# Massachusetts Inst. of Tech., Cambridge. SOLUTION METHOD FOR A HOVERING HELICOPTER ROTOR USING THE EULER EQUATIONS

T. W. ROBERTS and E. M. MURMAN (MIT, Cambridge, MA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs (Contract NGT-22-009-901; NAG2-105; NAG2-275) (AIAA PAPER 85-0436)

A method for the calculation of the flow field of a helicopter rotor blade in hover is presented. The approach uses a finite volume solution of the three dimensional Euler equations for the blade near field. In the Euler solver the velocity field is decomposed into two parts. One is the induced velocity of the vortex wake extending below the blade, found from a free wake calculation procedure. The other part is the unknown additional velocity field of the rotor blade. This approach eliminates numerical diffusion of the rolled up wake vorticity due to truncation error and artificial viscosity. Also, the effects of the far wake are included in the limited computational domain. Solutions are presented for an isolated wing and a model helicopter rotor and compared to experiment.

A85-19755#

TRAPPING OF FREE VORTEX BY AIRFOILS WITH SURFACE SUCTION

C.-Y. CHOW (Colorado, University, Boulder, CO), M.-K. HUANG (Nanjing Aeronautical Institute, Nanjing, People's Republic of China; Colorado, University, Boulder, CO), and C.-L. CHEN American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p.

(Contract AF-AFOSR-84-0037) (AIAA PAPER 85-0446)

The free vortex on whose capture the augmentation of an airfoil's lift depends is unstable at most of its equilibrium positions, except at those in a narrow region above the trailing edge. It is presently reported that additional, stable positions may be established through the application of suction through the upper surface of the airfoil. In such cases, the strong vortex trapped above the airfoil is noted to be capable of generating much greater

lift than the airfoil without suction modification.

A85-19756#

VISUALIZATION OF THE SPANWISE VORTEX STRUCTURE IN THE STARTING FLOW BEHIND AN AIRFOIL

P. FREYMUTH, W. BANK, and F. FINAISH (Colorado, University, Boulder, CO) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(Contract AF-AFOSR-81-0027)

(AIAA PAPER 85-0447)

The smoke technique is presently used at moderate Reynolds number and at angles of attack beyond the static stall angle, in order to visualize spanwise vortical structure and development as they occur in accelerated flow around an airfoil starting from rest. Although leading and trailing edge vortical development starts out two-dimensionally, it passes through a complex series of three-dimensional stages until it reaches the turbulent state.

O.C.

O.C.

A85-19759# **EVALUATION OF VORTEX WAKE PREDICTIONS IN THE SWINT** CODE

M. I. ADIASOR and R. J. KRIEGER (McDonnell Douglas Astronautics Co., St. Louis, MO) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs (AIAA PAPER 85-0450)

Semi-empirical approaches are often used to model boundary layer separation effects in inviscid flowfield solutions based upon Euler's equations. In this paper, these approaches are described and the SWINT Euler code is used to investigate the sensitivity of flowfield predictions to the separation model. To assess the effects of the boundary layer separation model both a line integral and area integral for the circulation introduced into the flowfield were developed. Sensitivities of mass, moment and energy flux, circulation, pitching moment, normal force and pressure predictions to the boundary layer separation model are identified. A separation model based upon a control volume at separation is developed which allows the flow variables to satisfy the continuity, momentum and energy equations at separation and controls and amount of circulation introduced at separation. This model is recommended for inclusion in Euler codes when coupled to boundary layer solutions. Author

A85-19760# **CROSSFLOW DRAG OF FINITE-LENGTH RECTANGULAR** WING-BODIES

E. S. LARSON (Flygtekniska Forsoksanstalten, Bromma, Sweden) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. Research supported by the Forsvaret Materielverk. refs

(AIAA PAPER 85-0451)

The crossflow drag coefficient for finite-length cylinders with strakes in the form of slender rectangular wings has been constructed empirically from experimental results on the crossflow drag coefficient for cylinders with strakes in two-dimensional, subsonic-transonic flow by applying to the result crossflow drag proportionability factors empirically obtained also. The result is restricted to Mach numbers less than or equal to one. Experiments with straked finite-length cylinders are needed for a final quantification of a crossflow drag proportionality factor of interference type, at present estimated by a conjecture. Author

A85-19761*# McDonnell-Douglas Astronautics Co., St. Louis, Mo.

CORRELATION AND ANALYSIS OF OIL FLOW DATA FOR AN **AIR-BREATHING MISSILE MODEL**

S. L. STOY (McDonnell Douglas Astronautics Co., St. Louis, MO), J. L. DILLON (NASA, Langley Research Center, Hampton, VA), and A. P. ROMAN American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(AIAA PAPER 85-0452)

This paper will present the results of an oil flow investigation on an airbreathing missile model. This oil flow study examined the flow around the model, which can be configured with both axisymmetric and two-dimensional inlets. Flow visualization analyses were conducted for both types of geometries by examining the surface flow patterns made visible by the oil flows for Mach numbers of 2.5 and 3.95. The analysis has shown the extent of flow spillage around the inlet which has helped explain the force and moment data collected during previous testing of the model. The oil flow data has also been used to develop guidelines for modeling the location of the crossflow separation line along inlet fairings. Finally, the oil flow analysis has been used to identify unique features of the boattail flow. These boattail flow characteristics have been correlated with previous oil flow analysis of noncircular body models. This paper demonstrates the use of this type of oil flow analysis in developing missile flow field analysis and aerodynamic predictions ranging from impact angle methods through Navier-Stokes methods. Author

A85-19762*# Martin Marietta Aerospace, Orlando, Fla. **EXPERIMENTAL** STUDY OF FORWARD-LOCATED JET-INTERACTION NOZZLES

R. J. CAVALLERI, R. E. WITTMEYER, A. J. CIAPONI (Martin Marietta Aerospace, Orlando, FL), and J. W. KEYES (NASA, Langley Research Center, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. (AIAA PAPER 85-0454)

The effects of forward-mounted sonic jet-interaction nozzles with one, three equal, or one large and two small orifices on the transitional or turbulent boundary-layer flow over a biconic (9-deg-25-arcmin/6-deg) model at angle of attack -10 to the 15 deg and Reynolds number 8.10 x 10 to the 6th/ft are investigated experimentally using pressure taps, force measurements, oil-flow visualization, and schlieren photography in the 20-in. Mach-6 wind tunel at NASA Langley. The injection flow rates are 0.055 and 0.026 lbm/s, with stagnation pressure 500 psia, stagnation temperature 1000 R, and dynamic pressure 8.7 psia. The results are presented in diagrams, graphs, and photographs and characterized. Moment amplification factors of 1.0 or better (maximum 1.8 at angle of attack 15 deg and flow rate 0.055 lbm/s) are observed for all nozzle types, but the configuration with three unequal orifices is found to give improvements of 10 percent over the single-orifice nozzle at a given flow rate. T.K.

A85-19776#

TOMOGRAPHIC RECONSTRUCTION OF THREE-DIMENSIONAL FLOW OVER AIRFOILS

D. MODARRESS, H. TAN, J. D. TROLINGER (Spectron Development Laboratories, Inc., Aeromechanics Laboratory, Costa Mesa, CA), and Y. YU (U.S. Army, Army Aviation Research and Development Command, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs

(Contract DAAG29-83-C-0012)

(AIAA PAPER 85-0479)

New developments have led to the feasibility to conduct a quantitative analysis of three-dimensional density fields with the aid of tomographic methods. An important aerodynamic problem which requires use of this technology involves the three-dimensional flow field which occurs at the tip of a rotating airfoil depicting a helicopter rotor blade. This three-dimensional flow field is reconstructed using holographic interferometry. There are, however, a number of difficulties associated with the reconstruction of phase objects. Details regarding the tomographic reconstruction of flow over air foils are discussed, taking into account the experimental setup at the anechoic hover chamber, the digitization program, the iterative refinement of a least-squares solution of linear equations, numerical experimentation, and the reconstruction of experimental data. GR

A85-19777#

A COMPARATIVE STUDY BETWEEN AN IMPLICIT AND EXPLICIT ALGORITHM FOR TRANSONIC AIRFOILS

M. R. VISBAL and J. S. SHANG (USAF, Wright Aeronautical Laboratories, Wright-Patterson AFB, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs

(AIAA PAPER 85-0480)

A critical examination of several aspects of the numerical simulation of high Reynolds number transonic airfoil flows is presented. Subcritical and supercritical flow fields about an aft-cambered airfoil were generated by solving the mass-averaged Navier-Stokes equations with turbulence incorporated through an algebraic eddy viscosity model. The governing equations were solved on curvilinear body-fitted grids utilizing two different algorithms, i.e., MacCormack's explicit and Beam-Warming implicit. The numerical uncertainties associated with different schemes, grid resolution, artificial viscosity and far field boundary placement were investigated, and found to be of the same order of magnitude or less than the corresponding uncertainties in the available experimental data. Comparison of computed and experimental results showed good prediction of all the essential flow features. However, detailed comparison of velocity profiles pointed out deficiencies of the turbulence model downstream of the shock/boundary layer interaction in the airfoil cove and in the near-wake. Thin-layer and Navier-Stokes computed results were found in excellent agreement with each other. However, the Euler equations failed to provide a reasonable approximation of the flow due to the dramatic viscous-inviscid interaction effects for supercritical airfoils. Author

A85-19778#

A NEW SINGULAR INTEGRAL METHOD FOR COMPRESSIBLE POTENTIAL FLOW

D. E. WILSON (Texas, University, Austin, TX) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p.

(AIAA PAPER 85-0481)

The present investigation is concerned with a new singular integral technique for solving the full nonlinear potential flow equations describing the outer flow field about an arbitrary body. The only approximations employed are related to the usual potential flow boundary layer restrictions. The mathematical formulation is discussed, taking into account a symmetrical airfoil at some angle of attack with respect to a uniform free stream. A successive approximation technique is employed. The method involves the generation of a series of linear differential equations. The solution of the two-dimensional potential flow equations is reduced to a one-dimensional problem. G R

A85-19779*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va. EFFICIENT SELF-CONSISTENT

VISCOUS-INVISCID SOLUTIONS FOR UNSTEADY TRANSONIC FLOW

J. T. HOWLETT (NASA, Langley Research Center, Hampton, VA) American Institute of Aeronautics and Astronautics. Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs (AIAA PAPER 85-0482)

An improved method is presented for coupling a boundary layer code with an unsteady inviscid transonic computer code in a quasi-steady fashion. At each fixed time step, the boundary layer and inviscid equations are successively solved until the process converges. An explicit coupling of the equations is described which greatly accelerates the convergence process. Computer times for converged viscous-inviscid solutions are about 1.8 times the comparable inviscid values. Comparison of the results obtained with experimental data on three airfoils are presented. These demonstrate that the comparisons explicitly coupled viscous-inviscid solutions can provide efficient predictions of pressure distributions and lift for unsteady two-dimensional transonic flows. Author

A85-19781#

GRID ADAPTATION FOR THE 2-D EULER EQUATIONS

J. F. DANNENHOFFER, III and J. R. BARON (MIT. Cambridge, MA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs

(Contract AF-AFOSR-82-0136)

(AIAA PAPER 85-0484)

An adapted grid technique for accurate and efficient solutions of the steady, two-dimensional Euler equations is presented. Embedded meshes, which are coupled to a fixed global mesh via a multiple-grid technique, are employed. The effect of choosing various adaptation strategies is examined. Solutions are presented for isolated lifting airfoils in subcritical as well as transonic flow. The supersonic flow over a circular-arc cascade with a complex shock structure is also presented. In all cases, the adapted solution achieved the same accuracy as global refinement, but required a factor of between 5 and 7 less computer time and between 3 and 8 less storage. Author

A85-19783*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

A THREE-DIMENSIONAL ADAPTIVE GRID METHOD

K. NAKAHASHI and G. S. DEIWERT (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs

(AIAA PAPER 85-0486)

A three-dimensional solution-adaptive-grid scheme is described which is suitable for complex fluid flows. This method, using tension and torsion spring analogies, was previously developed and successfully applied for two-dimensional flows. In the present work, a collection of three-dimensional flow fields are used to demonstrate the feasibility and versatility of this concept to include an added dimension. Flow fields considered include: (1) supersonic flow past an aerodynamic afterbody with a propulsive jet at incidence to the free stream, (2) supersonic flow past a blunt fin mounted on a solid wall, and (3) supersonic flow over a bump. In addition to generating three-dimensional solution-adapted grids, the method can also be used effectively as an initial grid generator. The utility of the method lies in: (1) optimum distribution of discrete grid points, (2) improvement of accuracy, (3) improved computational efficiency, (4) minimization of data base sizes, and (5) simplified three-dimensional grid generation. Author

North Carolina State Univ., Raleigh. A85-19784*# APPLICATION OF A -VARIATIONAL METHOD FOR GENERATING ADAPTIVE GRIDS

R. I. KREIS, H. A. HASSAN (North Carolina State University, Raleigh, NC), and F. C. THAMES (NASA, Langley Research Center, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(AIAA PAPER 85-0487)

The application of variational methods for generating adaptive grids is not as straightforward as one is led to believe. Proper scaling, suitable weight functions and appropriate clustering on boundaries must be employed to obtain a satisfactory grid. This work, which is based on the framework developed by Brackbill and Saltzman, provides simple methods for determining scaling and investigates possible options for selecting the weight function and clustering points on the boundaries. The concepts developed here are applied to two two-dimensional problems: a model problem based on Burger's equation which contains two length scales and, transonic flow past airfoils using the Euler equations. Author

A85-19785*#

AN IMPLICIT, CONSERVATIVE, ZONAL-BOUNDARY SCHEME FOR EULER EQUATION CALCULATIONS

M. M. RAI (NASA, Ames Research Center, Moffett Field; Informatics General Corp., Palo Alto, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 23 p. refs (AIAA PAPER 85-0488)

A 'zonal', or 'patched-grid', approach is one in which the flow region of interest is divided into subregions which are then discretized independently, using existing grid generators. The equations of motion are integrated in each subregion in conjunction with zonal-boundary schemes which allow proper information transfer across interfaces that separate subregions. The zonal approach greatly simplifies the treatment of complex geometries and also the addition of grid points to selected regions of the flow. In this study a conservative, zonal-boundary condition that could be used with explicit schemes has been extended so that it can be used with existing second-order-accurate implicit integration schemes such as the Beam-Warming and Osher schemes. In the test case considered, the implicit schemes increased the rate of convergence considerably (by a factor of about 30 over that of the explicit scheme). Results demonstrating the time-accuracy of the zonal scheme and the feasibility of performing calculations on zones that move relative to each other are also presented.

Author

A85-19787#

LAMINAR BOUNDARY LAYER STABILITY EXPERIMENTS ON A CONE AT MACH 8. III - SHARP CONE AT ANGLE OF ATTACK

K. F. STETSON (USAF, Wright Aeronautical Laboratories, Wright-Patterson AFB, OH), E. R. THOMPSON (Arnold Engineering Development Center, Arnold AF Station, TN), J. C. DONALDSON, and L. G. SILER (ARVIN/CALSPAN Field Services, Inc., Arnold AF Station, TN) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 25 p. refs

(AIAA PAPER 85-0492)

The stability of the laminar boundary layer on a sharp, 7-degree half angle cone at free-stream M = 8 was experimentally investigated using hot-wire anemometry techniques. Angle of attack effects were obtained from measurements on the windward meridian at two and four degrees angle of attack and on the leeward meridian at two degrees angle of attack. Small angles of attack were found to make significant changes, compared to zero angle of attack, in the stability characteristics of the boundary layer. The experimentally detectable critical Reynolds number increased on the windward meridian and appeared to decrease on the leeward meridian. The amplification rates of second mode disturbances were not greatly affected by angle of attack; whereas, first mode disturbance growth was reduced on the windward

meridian. Higher frequency disturbance growth was delayed to higher local Reynolds numbers on the windward meridian and occurred at lower local Reynolds numbers on the leeward meridian. Windward meridian transition Reynolds numbers were larger than expected. Author

A85-19788*# Stanford Univ., Calif.

DISTURBANCE-WAVE INTERACTIONS IN FLOWS WITH CROSSFLOW

H. L. REED (Stanford University, Stanford, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs (Contract NAG1-402)

(AIAA PAPER 85-0494)

The leading-edge region of swept wings is dominated by the crossflow instability, resulting in vortices that all rotate in the same sense. The effect of these possibly unsteady vortices on the behavior of other disturbances is examined, and a strong interaction between these and disturbances of half the dominating crossflow wavelength is predicted. According to theory, the interaction is of crossflow-crossflow type. The effect explains the anomalies found in the experimental observations of Saric and Yeates. Visually, they observe vortices at the wavelength predicted by linear theory; however, in their hot-wire measurements they find that the superharmonic dominates disturbance growth, eventually having three times the amplitude of the primary wave. In this case, the usual transition prediction methods would fail, clearly indicating the importance of studying interactions of this sort. Author

A85-19798#

SIMULATION THREE-DIMENSIONAL OF TRANSONIC NACELLE/INLET FLOWFIELDS USING AN **EULER/NAVIER-STOKES ALGORITHM**

J. VADYAK (Lockheed-Georgia Co., Marietta, GA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 14 p. Research sponsored by the Lockheed Independent Research and Development Program. refs

(AIAA PAPER 85-0084)

An analysis is presented for calculating steady (or unsteady) three-dimensional aircraft inlet flowfields. This algorithm can compute the flowfield about axisymmetric or arbitrary asymmetric nacelle/inlet configurations with or without centerbodies at zero or nonzero incidence at subsonic, transonic, or supersonic free-stream speeds. The algorithm can solve either the Euler momentum equations for inviscid flow, the thin-shear-layer Navier-Stokes equations for viscous flow, or the full Navier-Stokes equations for viscous flow. The flowfield is determined on a body-fitted numerically-generated computational grid. A fully-implicit alternating-direction-implicit algorithm is employed for solution of the finite-difference equations. Numerical results and correlations with existing methods and experiment are presented to illustrate application of the analysis for cases at subsonic and transonic free-stream speeds. Author

A85-19821

VORTEX PATH IN THE SUPERSONIC WAKE OF A ROUGH EVEN PLATE (WIRBELSTRASSE IM UBERSCHALLNACHLAUF EINER RAUHEN EBENEN PLATTE]

Aachen, Rheinisch-Westfaelische Technische M.-Z. TANG Hochschule, Fakultaet fuer Mashinenwesen, Dr.-Ing. Dissertation, 1983, 96 p. In German. refs

The supersonic vortex path of a plate is described, and the influence of the boundary conditions of plate thickness, relative roughness, and plate trailing edge shape on the vortex path formation in the supersonic wake is investigated. The results are compared with ones obtained elsewhere for circular cylinders and profiles, and the relationship of the present results to those of Hermann (1972) on the interaction between a compression shock and a supersonic vortex path is addressed. Optical methods are used to determine fluctuations in velocity and density and the frequency of vortex shedding as well as their variations due to compression shock and the deformation of the shock caused by the vortex path wake. C.D.

A85-19844

COMPUTATION OF TRANSONIC INLET FLOWS [BERECHNUNG SCHALLNAHER EINLAUFSTROEMUNGEN]

U. GIESE Aachen, Rheinisch-Westfaelische Technische Hochschule, Fakultaet fuer Maschinenwesen, Dr.-Ing. Dissertation, 1983, 107 p. In German. refs

The compressible flow in a plane inlet is investigated analytically, applying a finite-difference scheme (in nonorthogonal curvilinear coordinates adapted to the wall geometry) to solve the full potential equations for the inviscid flow far from the wall and a factorization procedure to solve the discrete problem. The influence of the boundary conditions on the convergence of the solution is demonstrated; a linear relaxation technique is used in the integration of the differential equations for the stream function; the effect of the wall curvature radius on the solution of the boundary-layer problem is evaluated; and the core and wall flows are coupled via the displacement thickness. Numerical results for subsonic flow and supersonic regions are presented in graphs and compared with published experimental data. T.K.

A85-19848

CIRCULATION AROUND THICK WINGS WITH FREE VORTICES [UMSTROEMUNG VON DICKEN FLUEGELN MIT FREIEN WIRBELN]

P. ZHU Stuttgart, Universitaet, Fakultaet Verfahrenstechnik, Dr.-Ing. Dissertation, 1983, 129 p. In German. refs

The panel method is used to calculate the flow around three-dimensional thick wings with tip vortices. The wing tips from which vortices are shed are assumed to be sharp, i.e., the tips are the flow separation lines. Flat rectangular panels and panels composed of a parallelogram and four triangles are used for the wings. Each panel is covered with a dipole distribution of the second order, and the coefficients of the dipole distribution are determined using the least squares method. The position of the vortex layer and the dipole distribution are calculated simultaneously. The results are useful for research on vortex layers and for the aerodynamic design of aircraft. C.D.

A85-19851

A PROCEDURE FOR THE OPTIMIZATION OF THE AEROTHERMODYNAMIC DESIGN OF MULTISTAGE AXIAL COMPRESSORS [VERFAHREN ZUR OPTIMIERUNG DER AEROTHERMODYNAMISCHEN AUSLEGUNG MEHRSTUFIGER AXIALVERDICHTER]

A. BIAGOSCH Muenchen, Technische Universitaet, Fakultaet fuer Maschinenwesen, Dr.-Ing. Dissertation, 1984, 156 p. In German. refs

A reduction of fuel consumption is a very significant factor in decreasing costs of aircraft operation, because approximately 50 percent of the direct operating costs of an airliner are related to fuel costs. A reduction in engine fuel consumption can be obtained by achieving savings in the fuel consumption due to specific engine components. The present investigation is concerned with efficiency improvements in the case of axial compressors on the basis of an optimization of the aerothermodynamic design. For a number of reasons, a global solution is not possible, and partial solutions have to be considered. Attention is given to the optimal aerothermodynamic design for an operating point. The optimal partial solution takes into consideration as much as possible requirements related to other partial problems. A computational procedure is developed for optimizing the aerothermodynamic design parameters of multistage axial-flow compressors with the aid of numerical optimization strategies. G.R.

A85-19854

A SUBDOMAIN FINITE ELEMENT METHOD FOR SOLVING THE CONSERVATIVE FULL POTENTIAL EQUATION FOR TRANSONIC PROFILE FLOWS [EIN SUBDOMAIN-FINITE-ELEMENT-VERFAHREN AUR LOESUNG DER KONSERVATIVEN VOLLEN POTENTIALGLEICHUNG FUER TRANSSONISCHE PROFILSTROEMUNGEN]

C. W. LUCCHI Muenchen, Technische Universitaet, Fakultaet fuer Maschinenwesen, Dr.-Ing. Dissertation, 1984, 162 p. In German. refs

A subdomain finite element method for solving the conservative full potential equation for wing profiles in the transonic domain is developed along with a procedure for minimizing errors which occur in potential theory when bedded shocks are described. Pressure distributions on shocked objects are corrected using the Rankine-Hugoniot law at the shock and a simple formula behind the shock. The Kutta-Joukowsky downflow condition is transformed to take care of the flattening due to static pressure loss. The corrected pressure distribution fulfills the physical requirement that no jump in the corrected static pressure may occur at the trailing edge. The correction extensively ameliorates errors that commonly occur using the potential equation. These results are tested on two profiles and compared with results from conservatively and nonconservatively formulated potential methods and conservative Euler procedures, with excellent results. from C.D.

A85-20025

A NUMERICAL STUDY OF THREE-DIMENSIONAL RADIATION FIELDS IN PROBLEMS OF SUPERSONIC FLOW PAST SEGMENTAL BODIES [CHISLENNOE ISSLEDOVANIE TREKHMERNOGO RADIATSIONNOGO POLIA V ZADACHAKH GIPERZVUKOVOGO OBTEKANIIA SEGMENTAL'NYKH TEL]

A. A. KOSTUZIK and A. N. RUMYNSKII (Moskovskii Fiziko-Tekhnicheskii Institut, Moscow, USSR) Inzhenerno-Fizicheskii Zhurnal (ISSN 0021-0285), vol. 47, Dec. 1984, p. 941-945. In Russian. refs

A solution is presented to the problem of calculating a three-dimensional radiation field in a shock laver in three-dimensional hypersonic flow of an inviscid. non-heat-conducting, selectively radiating and absorbing gas past segmental bodies. The radiant energy transport is calculated with allowance for the curvature of the shock layer surface and the interaction between the radiation field and the flow field. The shape of the shock wave and distribution of the thermodynamic parameters of the gas in the shock layer are calculated using the Magomedov-Kholodov (1969) method. Numerical calculations of the effect of the multidimensionality of the radiation field on the radiative heat transfer are presented. VI.

A85-20074

SURVEY ON JET INSTABILITY THEORY

A. MICHALKE (Berlin, Technische Universitaet, Berlin, West Germany) Progress in Aerospace Sciences (ISSN 0376-0421), vol. 21, no. 3, 1984, p. 159-199. refs

Theoretical results concerning the instability of axisymmetric jets are reviewed. For inviscid parallel jet flow the various parameters affecting jet instability such as shear layer thickness, Mach number, temperature ratio, and external flow velocity are discussed. Furthermore, viscous and nonlinear effects are considered. Finally, the influences of flow divergence and of nozzle-jet interaction are discussed. Author

A85-20228#

MATRIX SOLUTION OF COMPRESSIBLE FLOW ON S(1) SURFACE THROUGH A TURBOMACHINE BLADE ROW WITH SPLITTER VANES OR TANDEM BLADES

B. WANG and C.-H. WU (Chinese Academy of Sciences, Institute of Engineering Thermophysics, Beijing, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, Feb. 1984, p. 18-26. In Chinese, with abstract in English. refs

The basic aerothermodynamic equations of turbomachine flow expressed with respect to nonorthogonal curvilinear coordinates and corresponding nonorthogonal velocity components are used to solve the compressible flow on S(1) surface in a turbomachine blade row with splitter vanes or tandem blades. The equation of stream function is solved by direct matrix method and the mass flow ratio and outlet flow angle are determined by applying the generalized Joukowski condition to the trailing edges of the main blade and the splitter vane. Typical examples are given to illustrate the effectiveness of the present method. Author

A85-20229#

A NEW APPROACH TO SOME HYBRID AERODYNAMIC PROBLEMS OF AIRFOIL CASCADES ON A GENERAL STREAMSHEET OF REVOLUTION. I

G. LIU (Shanghai Institute of Mechanical Engineering, Shanghai, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, Feb. 1984, p. 27-32. In Chinese, with abstract in English. refs

A novel universal method for solving the inverse problem and hybrid problem of types A, C, and D is proposed, and a new image plane xi-eta is introduced. The solution procedure for the type C hybrid problem, designing a cascade with prescribed profile thickness and suction surface velocity distribution, is illustrated in detail. In comparison with previous approaches, this one is capable of treating blunt nose profiles with higher accuracy and is very suitable for joint use with the optimization theory of cascades. Perhaps the most attractive feature of this approach is its extendability to the solution of the hybrid problem of fully 3-D flow. C.D.

A85-20230#

COMPLETE THREE-DIMENSIONAL FLOW SOLUTION OF A CASCADE INCORPORATING SPLITTER VANES OF ARBITRARY GEOMETRY

D. LIU (Chinese Academy of Sciences, Institute of Engineering Thermophysics, Beijing, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, Feb. 1984, p. 33-39. In Chinese, with abstract in English. refs

An approach to calculate the complete 3-D flow in a cascade incorporating splitter vanes is presented here. The splitter vanes have arbitrary shape to differ from the main vanes. In connection with some references published, this kind of cascade is discussed. The specification of the boundary conditions, the constitution of different solution regions, the accuracy of complete 3-D solution, and the determination of the flow split have been discussed. A model to calculate the flow split ratio is suggested. Author

A85-20231#

CALCULATION AND ANALYSIS OF THE THREE-DIMENSIONAL FLOW IN CENTRIFUGAL COMPRESSOR IMPELLERS

J. CHEN (Chinese Academy of Sciences, Institute of Engineering Thermophysics, Beijing, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, Feb. 1984, p. 40-46. In Chinese, with abstract in English. refs

An improved method for solving the 3-D flow in centrifugal impellers is presented. The method consists of an iterative calculation in two loops. The inner loop is an iterative solution of the aerothermodynamic equations along two sets of nonorthogonal stream surface coordinates. The outer loop is an iterative solution between two correlating flow fields. The 3-D solution is finally reached for the entire space region of the blade passage and its upstream and downstream extensions. The method can be applied to ordinary impellers and impellers with splitters or tandem blades. A comparison is made with measured data for 3-D flow fields.

C.D.

A85-20233# THE FUNDAMENTAL EQUATIONS OF 3-DIMENSIONAL TWO-PHASE PARTICULATE GAS FLOW AND A TWOFOLD STREAM SURFACES MODEL OF SOLUTION FOR PARTICULATE GAS FLOW IN TURBOMACHINES

Z. LING (Chinese Academy of Sciences, Institute of Engineering Thermophysics, Beijing, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, Feb. 1984, p. 51-54. In Chinese, with abstract in English.

ON THE VARIETY OF TYPE DISCRIMINATION CRITERIA OF EQUATIONS ON S1 AND S2 STREAM SURFACES IN TURBOMACHINE

H. CHEN (Chinese Academy of Sciences, Institute of Engineering Thermophysics, Beijing, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, May 1984, p. 135-141. In Chinese, with abstract in English. refs

This paper aims at solving the points at issue on the type discrimination of the partial differential equations of Wu (1952). Some confused understanding is clarified. The type discriminations for the stream-surface problems are correctly made. The relation between the types of the stream-function principal equations and of the systems of equations is found. The type-discrimination criteria of two-dimensional aerodynamic problems are characterized, and some knotty problems in regard to the physical meaning of the type criterion of the inverse problem of the stream surface are explained. Author

A85-20239#

A FAST ALGORITHM FOR SOLVING THE CONSERVATIVE TRANSONIC S1 FULL POTENTIAL EQUATION EMPLOYING NON-ORTHOGONAL CURVILINEAR COORDINATES AND NON-ORTHOGONAL VELOCITY COMPONENTS

J. ZHANG and C. WU (Chinese Academy of Sciences, Institute of Engineering Thermophysics, Beijing, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, May 1984, p. 142-147. In Chinese, with abstract in English. refs

A fast implicit AC-AF algorithm has been developed to solve the conservative, transonic, S1 full-potential equation. In the algorithm, the artificial density is introduced to the S1 full-potential equation, and the solution on S1 stream surface transonic flow field is obtained by solving the discreted algebraic equations according to the implicit approximate factorization scheme. Results obtained for several turbomachine cascades demonstrate both fast convergence speed and good coincidence agreement of calculated result with the experimental value or available analytic solution.

Author

A85-20240#

A STREAM FUNCTION RELAXATION METHOD FOR SOLVING TRANSONIC S1 STREAM SURFACE WITH RESPECT TO NON-ORTHOGONAL CURVILINEAR COORDINATES

M. GE (Chinese Academy of Sciences, Institute of Engineering Thermophysics, Beijing, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, May 1984, p. 148-153. In Chinese, with abstract in English. refs

The derived stream-function equation in nonorthogonal curvilinear coordinates can be used for solving problems on S1 or S2 stream surfaces (including plane, arbitrary-revolution, and twist surfaces). Stream-line coordinates and corresponding orthogonal coordinates are used, and the mixed-difference method is adopted in the numerical calculation for solving transonic S1 or S2 stream surface. Through the study of the method of solution for the density field in terms of stream function, a procedure for the predetermination of the density is presented. The calculated examples show satisfactory results.

A85-20241#

EFFECT OF INLET AND OUTLET FLOW CONDITIONS ON THE FLOW AND PERFORMANCE OF SUBSONIC TWO-DIMENSIONAL DIFFUSER

L. FANG and X. CHEN (Nanjing Aeronautical Institute, Nanjing, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, May 1984, p. 154-156. In Chinese, with abstract in English.

The effect of a change in inlet and outlet flow conditions on the flow in a two-dimensional diffuser has been studied experimentally in a small-aspect-ratio diffuser tunnel. The experimental result shows that the steady performance and separation point of the flow in the diffuser are substantially affected by the velocity distribution profiles in both directions at the inlet. The change in the exit geometry of the tested diffuser has only a small effect on the strength of separation region. Author

A85-20554

HYPERSONIC MULTICYCLE GAS JET WITH A STRONGLY UNDEREXPANDED STREAM AT THE NOZZLE SECTION [O GIPERZVUKOVOI MNOGOTSIKLOVOI STRUE GAZA S SIL'NYM NEDORASSHIRENIEM POTOKA NA SREZE SOPLA]

A. V. IVANOV, N. V. STANKUS, and S. F. CHEKMAREV Akademiia Nauk SSSR, Izvestiia, Mekhanika Zhidkosti i Gaza (ISSN 0568-5281), Nov.-Dec. 1984, p. 27-35. In Russian. refs

The method of unsteady analogy (i.e., the law of plane sections) is used to perform a theoretical analysis of a hypersonic multicycle jet with a strongly underexpanded stream at the nozzle section. An approximate flow model is developed, and an analytical solution is obtained for the location of the boundary of the multicycle jet. Also obtained is a numerical solution to the corresponding equivalent unsteady problem of the dispersion of a cylindrical gas cluster. It is shown that an experimentally observed decrease in cycle amplitude in the downstream direction is due to energy dissipation in shocks. Here, the cycle length is practically independent of dissipation and is almost constant. Also considered are the effects of heating or cooling, and the problem of a jet in a slightly inhomogeneous atmosphere.

A85-20557

CONICAL BODIES WITH A STAR-SHAPED TRANSVERSE CROSS SECTION, HAVING A RESERVE OF STATIC STABILITY [KONICHESKIE TELA SO ZVEZDOOBRAZNYM POPERECHNYM SECHENIEM, OBLADAIUSHCHIE ZAPASOM STATICHESKOI USTOICHIVOSTI]

N. A. OSTAPENKO (Moskovskii Gosudarstvennyi Universitet, Moscow, USSR) Akademiia Nauk SSSR, Izvestiia, Mekhanika Zhidkosti i Gaza (ISSN 0568-5281), Nov.-Dec. 1984, p. 84-92. In Russian.

The paper formulates and solves a variational problem concerning a conical body with a star-shaped transverse cross section, having a maximum reserve of static stability. The similarity law is formulated, and analyses are made of the reserves of static stability for a body with a skewed trailing edge and for a specified midsection area. L.M.

A85-20561

HYPERSONIC CHEMICALLY NONEQUILIBRIUM VISCOUS SHOCK LAYER ON WINGS WITH A CATALYTIC SURFACE [GIPERZVUKOVOI KHIMICHESKI NERAVNOVESNYI VIAZKII UDARNYI SLOI NA KRYL'IAKH S KATALITICHESKOI POVERKHNOST'IU]

E. A. GERSHBEIN, V. S. SHCHELIN, and S. A. IUNITSKII (Moskovskii Gosudarstvennyi Universitet, Moscow, USSR) Akademiia Nauk SSSR, Izvestiia, Mekhanika Zhidkosti i Gaza (ISSN 0568-5281), Nov.-Dec. 1984, p. 127-135. In Russian. refs

The theory of a hypersonic viscous shock layer is used to analyze flow past wings of infinite span with a blunt leading edge for different attack and slip angles. Conditions are imposed on the body which allow for first-order heterogeneous catalytic reactions. The flow conditions correspond to the motion of a body having lift force along an entry trajectory into the earth's atmosphere. Attention is given to the flight-altitude dependence of the surface equilibrium temperature along the critical line of the wing as well as to the temperature distribution along the surface of wings with parabolic and hyperbolic contours. It is shown that, for flow regimes with a relatively high degree of dissociation, the dependences of heat flux and surface temperature on the slip angle are nonmonotonic in cases when the fraction of atoms recombined on the surface is small. A85-20562

EFFECT OF THE ARRANGEMENT OF APERTURES ON THE GAIN COEFFICIENT DURING ASYMMETRIC GAS INJECTION INTO A LAVAL NOZZLE [VLIIANIE RASPOLOZHENIIA OTVERSTII NA KOEFFITSIENT USILENIIA PRI NESIMMETRICHNOM VDUVE GAZA V SOPLO LAVALIA]

V. V. ZELENTSOV, V. P. KREMNEV, A. A. NESTEROV, V. V. PORODENKO, and A. A. SHISHKOV Akademiia Nauk SSSR, Izvestiia, Mekhanika Zhidkosti i Gaza (ISSN 0568-5281), Nov.-Dec. 1984, p. 136-141. In Russian. refs

An experimental determination is made of the gain coefficient in the case of the injection of a transverse gas jet into the supersonic part of an axisymmetric nozzle for different arrangements of apertures along the nozzle and in the injection node for regimes characterized by perturbation propagation to the side of the nozzle opposite to the injection. It is shown that the working range of the injected-gas flowrate in which a sufficiently high efficiency of lateral-force generation is assured can be extended (as compared with injection through a single aperture) by the use of a system of subinjection apertures along with the main aperture. This situation is especially significant when the injection aperture is located deep within the nozzle and the required level of lateral force is sufficiently high. L.M.

A85-20744* United Technologies Corp., East Hartford, Conn. A LINEARIZED UNSTEADY AERODYNAMIC ANALYSIS FOR TRANSONIC CASCADES

J. M. VERDON and J. R. CASPAR (United Technologies Research Center, East Hartford, CT) Journal of Fluid Mechanics (ISSN 0022-1120); vol. 149, Dec. 1984, p. 403-429. refs (Contract NAS3-23696)

The unsteady airloads generated by the vibrations of turbomachine blades operating at transonic Mach numbers are predicted by a linearized potential flow analysis whose unsteady aerodynamics model encompasses the effects of blade geometry, nonzero mean pressure variation across the blade row, high frequency blade motion, and shock motion, all within the framework of a linearized frequency-domain formulation. A numerical solution for the entire unsteady flow field is determined by matching a solution covering an extended blade passage region to another covering, and extending beyond, the supersonic region(s) adjacent to a blade surface. Results are given for cascades of double circular arc and flat plate blades, in order to demonstrate the unsteady analysis and to partially illustrate the effects of blade geometry, inlet Mach number, vibration frequency and shock motion on unsteady response. O.C.

A85-20851*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

EULER COMPUTATIONS OF AGARD WORKING GROUP 07 AIRFOIL TEST CASES

T. H. PULLIAM and J. T. BARTON (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 34 p. refs

(AIAA PAPER 85-0018)

In an attempt to provide a set of accurate standard test problems for computational code developers, a series of inviscid airfoil test cases were chosen by the AGARD Working Group 07, a subpanel of the AGARD Fluid Dynamics Panel. The cases include three different airfoils at transonic to supersonic conditions. A large number of international experts responded in this effort with computations that have been contrasted for accuracy and consistency. This paper is a summary of the authors' contribution to this study. In particular, the important aspects of the solution process that made it possible to obtain the high level of accuracy needed in this study are stressed. Author

A85-20854# DRAG PREDICTION FOR PROJECTILES AND FINNED BODIES IN INCOMPRESSIBLE FLOW

والاستعادية والمتعادية

W. P. WOLFE and W. L. OBERKAMPF (Sandia National Laboratory, Albuquerque, NM) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs (Contract DE-AC04-76DP-00789)

(AIAA PAPER 85-0104)

A design method is presented for calculating the flow field and drag of bodies of revolution, with and without lifting surfaces, at zero angle of attack in incompressible flow. The body pressure distribution, viscous shear stress, and boundary layer separation point are calculated by a combination of a potential flow method and boundary layer techniques. The potential solution is obtained by modeling the body with an axial distribution of source/sink elements whose strengths vary linearly along their length. Both the laminar and turbulent boundary layer solutions use momentum integral techniques which have been modified to account for the effects of surface roughness. An existing technique for estimating the location of transition was also modified to include surface roughness. Empirical correlations are developed to estimate the base pressure coefficient on a wide variety of geometries. Body surface pressure distributions and drag predictions are compared with experimental data for artillery projectiles, concial bodies, bombs, and missiles. Very good agreement between the present method and experiment is obtained. Author

A85-20855*# Informatics General Corp., Palo Alto, Calif. NAVIER-STOKES COMPUTATIONS FOR EXOTIC AIRFOILS

T. J. BARTH (Informatics General Corp., Palo Alto, CA), T. H. PULLIAM, and P. G. BUNING (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 17 p. refs (AIAA PAPER 85-0109)

An efficient hyperbolic grid generator with improvements for handling sharp corners and concave surfaces is combined with an efficient and accurate Navier-Stokes flow solver. This combination is applied to some rather complex two-dimensional airfoil configurations. Steady separated flow about an iced leading edge of an airfoil is presented. Unsteady viscous separated flows past an airfoil at two angles of attack with a spoiler deployed at 60 degrees are presented and compared with experiment. The spoiler computations are performed with two different topological maps of the physical domain to the computational domain. Innovative graphical techniques for both the static and unsteady display of the flow fields are presented and discussed. Author

A85-20862#

AN EXPERIMENTAL INVESTIGATION OF THE MIXING OF **CO-ANNULAR SWIRLING FLOWS**

J. D. MATTINGLY (U.S. Air Force Academy, Colorado Springs, CO) and G. C. OATES (Washington, University, Seattle, WA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985, 10 p. refs. (Contract AF-AFOSR-80-0186G)

(AIAA PAPER 85-0186)

An extensive investigation of the mixing behavior of co-annular streams, with swirl present, has been carried out. A large blowdown facility was adapted to provide two streams of air at variable stagnation pressures, but equal stagnation temperatures. Conditions within the mixing region were essentially incompressible. The facility was constructed to provide swirl in the inner stream, and an inner and outer annulus could be provided if desired. In all cases considered, swirl was present in the inner, but not the outer stream, thereby leading to flow conditions unstable to the Rayleigh instability. Mean flow measurements, only, were obtained. A five hole probe was used to obtain the static pressure, stagnation pressure and three velocity components. Additional measurements included sidewall pressure measurements on the inner and outer annuli, as well as stream mass flow rates obtained from orifice plate meters. A variety of flow regimes were considered, including some without separated regions present. Where possible, the results were compared to the somewhat limited data available in the literature. Author

A85-20864#

FINITE ELEMENT SOLUTIONS OF EULER EQUATIONS FOR LIFTING AIRFOILS

H. U. AKAY, A. ECER, and P. G. WILLHITE (Purdue University, Indianapolis, IN) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs

(Contract F49620-83-K-0034)

(AIAA PAPER 85-0294)

A Clebsch formulation of Euler equations which includes the isentropic potential as well as the nonisentropic potential assumptions as special cases is reviewed. The applications to transonic flows around lifting airfoils are considered. The implementation of the Kutta condition at the sharp trailing edges for potential and Euler equations is presented. The differences for all three levels of approximations: isentropic potential, nonisentropic potential and full Euler, are demonstrated. Author

National Aeronautics and Space Administration. A85-20868*# Ames Research Center, Moffett Field, Calif.

RECENT IMPROVEMENTS IN EFFICIENCY, ACCURACY, AND CONVERGENCE FOR IMPLICIT APPROXIMATE FACTORIZATION ALGORITHMS

T. H. PULLIAM and J. L. STEGER (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 38 p. refs

(AIAA PAPER 85-0360)

In 1977 and 1978, general purpose centrally space differenced implicit finite difference codes in two and three dimensions have been introduced. These codes, now called ARC2D and ARC3D, can run either in inviscid or viscous mode for steady or unsteady flow. Since the introduction of the ARC2D and ARC3D codes, overall computational efficiency could be improved by making use of a number of algorithmic changes. These changes are related to the use of a spatially varying time step, the use of a sequence of mesh refinements to establish approximate solutions, implementation of various ways to reduce inversion work, improved numerical dissipation terms, and more implicit treatment of terms. The present investigation has the objective to describe the considered improvements and to quantify advantages and disadvantages. It is found that using established and simple procedures, a computer code can be maintained which is competitive with specialized codes. G.R.

A85-20869*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

NUMERICAL SIMULATION OF THE NFAC (NATIONAL FULL-SCALE AERODYNAMICS COMPLEX) OPEN-RETURN WIND TUNNEL INLET FLOW

U. K. KAUL (NASA, Ames Research Center, Moffett Field; Informatics General Corp., Palo Alto, CA), J. C. ROSS (NASA, Ames Research Center, Moffett Field, CA), and J. L. JACOCKS (Calspan Field Services, Inc., Arnold Air Force Station, TN) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 15 p. refs (AIAA PAPER 85-0437)

The flow into an open return wind tunnel inlet was simulated using Euler equations. An explicit predictor-corrector method was employed to solve the system. The calculation is time-accurate and was performed to achieve a steady-state solution. The predictions are in reasonable agreement with the experimental data. Wall pressures are accurately predicted except in a region of recirculating flow. Flow-field surveys agree qualitatively with laser velocimeter measurements. The method can be used in the design process for open-return wind tunnels. Author

National Aeronautics and Space Administration. A85-20870*# Ames Research Center, Moffett Field, Calif.

ARTIFICIAL DISSIPATION MODELS FOR THE EULER EQUATIONS

T. H. PULLIAM (Nasa, Ames Research Center, CFD Branch, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 23 p. refs

(AIAA PAPER 85-0438)

Various artificial dissipation models which are used with central difference algorithms for the Euler equations are analyzed for their effect on accuracy, stability and convergence rates. In particular, linear and nonlinear models are investigated using an implicit approximate factorization code (ARC2D) for transonic airfoils. Fully implicit application of the dissipation models is shown to improve robustness and convergence rates. The treatment of dissipation models at boundaries will be examined. It will be shown that accurate, error free solutions with sharp shocks can be obtained using a central difference algorithm coupled with an appropriate nonlinear artificial dissipation model. Author

A85-20873*# Arizona State Univ., Tempe. EXPERIMENTS ON THE STABILITY OF CROSSFLOW **VORTICES IN SWEPT-WING FLOWS**

W. S. SARIC (Arizona State University, Tempe, AZ) and L. G. YEATES (Lockheed-Georgia Co., Marietta, GA; Virginia Polytechnic Institute and State University, Blacksburg, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 14 p. refs (Contract NAG1-280)

(AIAA PAPER 85-0493)

Experiments are conducted which demonstrate the feasibility of creating crossflow vortices in a flat-plate flow. A swept leading edge and contoured wind-tunnel walls produce a strong pressure gradient and a typical swept-wing flow on the plate. Detailed three-dimensional measurements, made within the boundary layer using hot-wire anemometry, are supplemented with different flow-visualization techniques. Data are presented on the mean flow characteristics as well as on the behavior of the crossflow vortices. Comparisons are made with theoretical flow-field and stability calculations. Author

A85-20998#

DRAG OF THE FUNDAMENTAL SHAPES OF PARACHUTES

M. HAYASHI, S. ASO, S.-I. TENHIRO, and H. NAKAYA (Kyushu University, Fukuoka, Japan) Kyushu University, Technology Reports (ISSN 0023-2718), vol. 57, Aug. 1984, p. 463-470. In Japanese, with abstract in English.

To investigate the drag of the fundamental shapes of parachutes, two-dimensional and three-dimensional concave bodies with various skirts, various slits, or various vents are prepared. The drag of these models has been measured and the flow around them has been visualized with smoke-wire technique. From the experiments above, the following results are obtained. For the three-dimensional concave body, whose cross section is semi-circle, the drag decreases significantly when a skirt of height ratio, h/d, 0.4 is attached to the model. For the two-dimensional circular body with slit, the drag drops sharply at first and decreases linearly at the porosity, beta, of the slits increases. For the two-dimensional elliptic bodies, it is found that the slit around the top of the model is most effective to the drag of the model. For the three-dimensional concave bodies with slits and a vent the drag decreases more significantly with the porosity of the vent than with that of the slit. The results show that the drag of the parachute can be controlled to some degree by changing the porosity of the vent. Author

A85-21656

HARMONIC OSCILLATIONS OF A RECTANGULAR WING WITH CIRCULATION VARIABLE OVER THE SPAN **[GARMONICHESKIE KOLEBANIIA** PRIAMOUGOL'NOGO **KRYLA S TSIRKULIATSIEI PEREMENNOI PO RAZMAKHU**]

N. N. POLIAKHOV and Z. N. SHESTERNINA Leningradskii Universitet, Vestnik, Matematika, Mekhanika, Astronomiia (ISSN 0024-0850), Oct. 1984, p. 44-50. In Russian.

Birnbaum's vortex scheme is used to obtain a solution to the problem of the small harmonic oscillations of a slightly curved rectangular-planform wing in the translational flow of an ideal incompressible fluid. The problem is reduced to the solution of a Fredholm equation of the second kind. B.J.

A85-21827*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

INTRODUCTORY AEROTHERMODYNAMICS OF ADVANCED SPACE TRANSPORTATION SYSTEMS

J. T. HOWE (NASA, Ames Research Center, Moffett Field, CA) Journal of Spacecraft and Rockets (ISSN 0022-4650), vol. 22, Jan.-Feb. 1985, p. 19-26. Previously cited in issue 05, p. 585, Accession no. A83-16695. refs

A85-21830*# PEDA Corp., Palo Alto, Calif. REAL-GAS FLOWFIELDS ABOUT THREE-DIMENSIONAL CONFIGURATIONS

A. BALAKRISHNAN, C. K. LOMBARD (PEDA Corp., Palo Alto, CA), and W. C. DAVY (NASA, Ames Research Center, Moffett Field, CA) Journal of Spacecraft and Rockets (ISSN 0022-4650), vol. 22, Jan.-Feb. 1985, p. 46-53. Previously cited in issue 05, p. 591, Accession no. A83-17931, refs

A85-21841#

GROUND INTERFERENCE EFFECTS ON SUBSONIC DYNAMIC STALL IN PITCH AND PLUNGE

L. E. ERICSSON and J. P. REDING (Lockheed Missiles and Space Co., Inc., Sunnyvale, CA) (Structures, Structural Dynamics and Materials Conference, 24th, Lake Tahoe, NV, May 2-4, 1983, Collection of Technical Papers. Part 2, p. 266-276) Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. 1985, p. 109-116. Previously cited in issue 12, p. 1697, Accession no. A83-29836. refs

A85-21845#

ANALYSIS OF A SPLIT-FLOW INERTIAL PARTICLE SEPARATOR BY FINITE ELEMENTS

D. S. BREITMAN, E. G. DUECK (Pratt and Whitney Canada, Mississauga, Ontario, Canada), and W. G. HABASHI (Pratt and Whitney Čanada, Mississauga, Ontario; Concordia University, Montreal, Canada) (Numerical methods in laminar and turbulent flow; Proceedings of the Third International Conference, Seattle, WA, August 8-11, 1983, p. 477-488) Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. 1985, p. 135-140. Previously cited in issue 03, p. 255, Accession no. A84-13278. refs

A85-21848*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

EVALUATION OF A STALLED AIRFOIL ANALYSIS PROGRAM C. L. RUMSEY (NASA, Langley Research Center, Analytical Methods Branch, Hampton, VA) Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. 1985, p. 156, 157.

The Stalled Airfoil Analysis Program (SAAP) is a computer code for predicting the aerodynamic characteristics of an airfoil up to, and beyond, stall. SAAP is presently evaluated through comparisons with experiments and with two other theoretical methods over an extensive range of airfoils and Reynolds number conditions. SAAP modeled drag more accurately than either of the other methods, and at angles of attack below stall yielded a smoother lift variation with angle of attack. O.C.

A85-21849#

EXPERIMENTAL RESULTS FOR REYNOLDS NUMBER EFFECTS ON TRAILING VORTICES

H. LEE and J. A. SCHETZ (Virginia Polytechnic Institute and State University, Blacksburg, VA) Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. 1985, p. 158-160. Abridged. Previously cited in issue 17, p. 2458, Accession no. A83-38694.

A85-21851#

THE UNIVERSAL NATURE OF ZERO-CROSSING TIME AND VELOCITY SCALES IN TURBULENT SHEAR FLOWS

P. BANDYOPADHYAY (Systems and Applied Sciences Corp., Hampton, VA) and A. K. M. F. HUSSAIN (Houston, University, Houston, TX) AIAA Journal (ISSN 0001-1452), vol. 23, Feb. 1985, p. 161, 162.

Recent studies have shown that the turbulence production process in shear flows is not entirely random, but rather quasiperiodic in nature. Since the large eddies play a decisive role in these processes in all shear flows, it is instructive to see if they bear any common characteristics. The possible universal distributions of time and velocity scales (T, u sub p) in the low-frequency component of the turbulent signals (defined, respectively, as the interval between successive zero crossings and the intervening absolute peak value of the longitudinal velocity signal) have been explored in a number of flows. These include the self-preserving regions of a turbulent boundary layer, plane jet, circular jet, and plane mixing layer, and the initial mixing regions of a plane jet and circular jet. Both T and u sub p distributions show universal trends: T distributions agree well with the log normal distribution except in their extreme excursions, whereas u sub p distributions are intermediate between log normal and Gaussian distributions. Author

A85-21855#

MODES OF SHOCK-WAVE OSCILLATIONS ON SPIKE-TIPPED BODIES

W. CALARESE and W. L. HANKEY (USAF, Wright Aeronautical Laboratories, Wright-Patterson AFB, OH) AIAA Journal (ISSN 0001-1452), vol. 23, Feb. 1985, p. 185-192. Previously cited in issue 05, p. 587, Accession no. A83-16779. refs

A85-21856*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

SHOCK-FITTING SOLUTION OF THE SUPERSONIC FLOWFIELD IN A ROUNDED INTERNAL CORNER

J. A. MARTIN (NASA, Langley Research Center, Space Systems Div., Hampton, VA) AIAA Journal (ISSN 0001-1452), vol. 23, Feb. 1985, p. 193-200. Previously cited in issue 05, p. 578, Accession no. A83-16478. refs

A85-21857#

FLOWFIELD SCALING IN SHARP FIN-INDUCED SHOCK WAVE/TURBULENT BOUNDARY-LAYER INTERACTION

D. S. DOLLING (Texas, University, Austin, TX; Princeton University, Princeton, NJ) and W. B. MCCLURE (USAF, Aeronautical Systems Div., Wright-Patterson AFB, OH) AIAA Journal (ISSN 0001-1452), vol. 23, Feb. 1985, p. 201-206. Previously cited in issue 17, p. 2446, Accession no. A83-37227. refs (Contract F49620-81-K-0018)

A85-21859#

COMPUTATION OF CHOKED AND SUPERSONIC TURBOMACHINERY FLOWS BY A MODIFIED POTENTIAL METHOD

W. G. HABASHI (Concordia University, Montreal; Pratt and Whitney Canada, Lonqueuil, Quebec, Canada), M. M. HAFEZ (Computer Dynamics, Inc., Virginia Beach, VA; Pratt and Whitney Canada, Lonqueuil, Quebec, Canada), and P. L. KOTIUGA (Pratt and Whitney Canada, Lonqueuil, Quebec, Canada) AIAA Journal (ISSN 0001-1452), vol. 23, Feb. 1985, p. 214-220. Research supported by Pratt and Whitney Canada; Natural Sciences and Engineering Research Council of Canada. Previously cited in issue 16, p. 2296, Accession no. A83-36415. refs (Contract NSERC-A-3662)

A85-21864*# General Electric Co., Lynn, Mass. SHOCK-FREE TURBOMACHINERY BLADE DESIGN

P. P. BEAUCHAMP (General Electric Co., Lynn, MA) and A. R. SEEBASS (Colorado, University, Boulder, CO) AIAA Journal (ISSN 0001-1452), vol. 23, Feb. 1985, p. 249-253. NASA-USAF-Navy-supported research. refs

A computational method for designing shock-free. quasi-three-dimensional, transonic, turbomachinery blades is described. Shock-free designs are found by implementing Sobieczky's fictitious gas principle in the analysis of a baseline shape, resulting in an elliptic solution that is incorrect in the supersonic domain. Shock-free designs are obtained by combining the subsonic portion of this solution with a characteristic calculation of the correct supersonic flow using the sonic line data from the fictitious elliptic solution. This provides a new, shock-free blade design. Examples presented include the removal of shocks from two blades in guasi-three-dimensional flow and the development of a series of shock-free two-dimensional stators. The new designs all include modifications to the upper surface of an experimental stator blade developed at NASA Lewis Research Center. While the designs presented here are for inviscid flow, the same concepts have been successfully applied to the shock-free design of airfoils and three-dimensional wings with viscous effects. The extension of the present method to viscous flows is straightforward given a suitable analysis algorithm for the flow. Author

A85-22146

INVESTIGATIONS OF THE LONGITUDINAL FLOW IN CORNER CONFIGURATIONS IN THE HYPERSONIC REGIME. II -CORNERS BETWEEN SWEPT WEDGES [UNTERSUCHUNGEN AN LAENGSANGESTROEMTEN ECKENKONFIGURATIONEN IM HYPERSCHALLBEREICH. II - ECKEN ZWISCHEN GEPFEILTEN KEILEN]

W. MOELLENSTAEDT (IVM, Wolfsburg GmbH, West Germany) Zeitschrift fuer Flugwissenschaften und Weltraumforschung (ISSN 0342-068X), vol. 8, Nov.-Dec. 1984, p. 405-414. In German. Research supported by the Deutsche Forschungsgemeinschaft. refs

Hypersonic flight vehicles are exposed to considerable thermal stresses due to kinetic heating. High-level heat transfer processes occur also in corner regions of wing-fuselage junctions or propulsion system inlets. The present investigation is concerned with a systematic study of the longitudinal flow in such corner regions, taking into account a comprehensive experimental program initiated at a West German technical university a number of years ago. One part of this study has been discussed by Kipke and Hummel (1975). The second part provides the results of an investigation of the flow in swept corner configurations, giving attention to conditions involving a free-stream Mach number of 12.3 and a Reynolds number of 500,000. The characteristics of the corner flow are illustrated in a graph. The flowfield at a swept 90 deg corner is considered along with the effect of the leading edge sweep angle on the flow, and the effect of the corner angle on the flow. A leading edge sweep angle of 60 deg is found to lead to a significant reduction of the heat flux. GR

A85-22227#

FLIGHT TESTING OF A WING SECTION WITH LAMINAR FLOW CONTROL

R. B. DAMANIA (National Aeronautical Laboratory; Indian Institute of Science, Bangalore, India) and N. S. W. THOMAS (Lockheed-Georgia Co., Advanced Flight Sciences Dept., Marietta, GA) Aeronautical Society of India, Journal (ISSN 0001-9267), vol. 36, May 1984, p. 95-106. refs

Tests with a laminar flow control (LFC) wing glove over the using of a Caproni powered glide are discussed, with emphasis on the instrumentation and measurement methods used. The glove profile provided a pressure distribution resembling that on a large transonic LFC transport in the cruise condition; the five slots in the upper surface of the glove ensured Reynolds numbers less than 100. The techniques used included surface Preston tubes, surface microphones, boundary layer rakes, and naphthalene sprays for flow visualization. The Preston tube technique is noted to be the easiest in use and most repeatable. Boundary layer transition studies suggest that a greater shift in transition can be obtained if the suction is concentrated near the leading edge region rather than being distributed over the wing. L.T.

A85-22228#

DESIGN OF LIFTING SYMMETRIC SUPERCRITICAL AIRFOILS M. NANDANAN and M. A. RAMASWAMY (National Aeronautical

Laboratory, Bangalore, India) Aeronautical Society of India, Journal (ISSN 0001-9267), vol. 36, May 1984, p. 107-113. refs

The design of a symmetric supercritical airfoil (SSA), shock-free under lifting conditions, is feasible through an example of a modified NACA-0012 airfoil. Off-design performance comparison at a freestream Mach number of 0.752 and an incidence angle of 1.1 degrees indicates the superiority of the derivative over the original NACA-0012 airfoil. Zero camber of the airfoil eliminates the wave drag penalty at supersonic speeds, thus making possible the airfoil application to combat aircraft and helicopter rotors. A table containing NAL-114-36-00 SSA coordinates, and the comparison data of the buffet onset boundaries and pressure distribution are given. L.T.

A85-22308

FLOW BEHIND AN ATTACHED SHOCK WAVE IN A RADIATING GAS

L. P. SINGH, A. KUMAR, and R. SHYAM (Banaras Hindu University, Varanasi, India) Astrophysics and Space Science (ISSN 0004-640X), vol. 106, no. 1, Nov. 1984, p. 81-92. refs

A simple method is used to determine the curvature of an attached shock wave and the flow variable gradients behind the shock curve at the tip of a straight-edged wedge placed symmetrically in a supersonic flow of a radiating gas near the optically thin limit. The shock curvature and the flow variable gradients along the wedge at the tip are computed for a wide range of upstream flow Mach numbers and wedge angles. Several interesting results are noted; in particular, it is found that the effect of an increase in the upstream flow Mach number or the radiative flux is to enhance the shock wave curvature which, however, decreases with an increase in the specific heat ratio or the wedge angle.

A85-22364

ILL-POSED PROBLEMS IN PERTURBATION THEORY (ASYMPTOTIC METHODS OF MECHANICS) [NEKORREKTNYE ZADACHI TEORII VOZMUSHCHENII /ASIMPTOTICHESKIE METODY MEKHANIKI/]

A. N. PANCHENKOV, ED. Novosibirsk, Izdatel'stvo Nauka, 1984, 248 p. In Russian. For individual items see A85-22365 to A85-22374.

Papers are presented concerning the application of asymptotic methods to the study of various ill-posed problems of mechanics, with a particular emphasis on problems of aerohydrodynamics (i.e., sea surface effect vehicles). Consideration is given to the development of asymptotic algorithms in the Polet software package for the design of sea surface effect vehicles; the full-approximation method in the theory of transonic flows; approximation of solutions of the first extremum problem of a wing with constant sea surface effect; and the extremum problem of a wing with a maximum gradient of lift force. The extremum problem of the shape of a body of revolution in supersonic flow, the design of a STOL aircraft with jet assisted takeoff units, and the use of local functionals to construct a circumvention maneuver in game problems of evasion. B.J.

A85-22366

DEVELOPMENT OF ASYMPTOTIC ALGORITHMS IN THE POLET PACKAGE OF APPLICATIONS PROGRAMS [POSTROENIE ASIMPTOTICHESKIKH ALGORITMOV V PAKETE PRIKLADNYKH PROGRAMM 'POLET']

A. N. PANCHENKOV, IU. F. ORLOV, R. IU. SHLAUSTAS, M. N. BORISIUK, G. I. ANTOSHKINA, and V. D. MISHCHENKO IN: III-posed problems in perturbation theory (A85-22364 08-02). Novosibirsk, Izdatel'stvo Nauka, 1984, p. 44-102. In Russian. refs

The Polet (Flight) software package has been developed for the optimal design of sea surface effect vehicles. Polet is described with respect to the theory and methodology of optimal design, package structure and function, and the following basic asymptotic methods: theory of maximum correctness, theory of acceleration potential, theory of wings in bounded steady and unsteady flows, quadrupolar wing theory, and asymptotic programming. Particular attention is given to functional modules, the package languages, and general programs and schemes for the solution of large problems. B.J.

A85-22367

THE FULL-APPROXIMATION METHOD IN THE THEORY OF TRANSONIC FLOWS [METOD POLNOI APPROKSIMATSII V TEORII OKOLOZVUKOVYKH TECHENII]

G. F. SIGALOV IN: Ill-posed problems in perturbation theory (A85-22364 08-02). Novosibirsk, Izdatel'stvo Nauka, 1984, p. 102-147. In Russian. refs

The paper describes the distinctive features of the full-approximation method (FAM), an asymptotic method for the analysis of boundary value problems in the theory of transonic flows. The FAM is applied to the study of a number of aerodynamic problems in the subsonic and supersonic parts of the transonic region, including: the steady motions of profiles in bounded or unbounded flows; low-frequency harmonic oscillations of a profile; and flow past a wing of rectangular planform. The application of the FAM to certain ill-posed problems of transonic flow is considered; particular emphasis is placed on the shape optimization of thin bodies.

A85-22368

APPROXIMATE SOLUTION OF A NONLINEAR PROBLEM OF FLOW PAST A THIN AIRFOIL PROFILE NEAR A SUPPORT SURFACE [PRIBLIZHENNOE RESHENIE NELINEINOI ZADACHI OBTEKANIIA TONKOGO PROFILIA VBLIZI OPORNOI POVERKHNOSTI]

R. IU. SHLAUSTAS IN: III-posed problems in perturbation theory (A85-22364 08-02). Novosibirsk, Izdatel'stvo Nauka, 1984, p. 167-174. In Russian. refs

Asymptotic quadrupole wing theory is used to obtain an approximate equation for flow past a thin airfoil at small distances from a flat solid surface. An approximate analytical solution to this equation is obtained, and the results are compared with previous data, indicating a good agreement in a large range of distances between the airfoil and surface, and in a large range of angles of attack. It is shown that a large lift is achieved at small local angles of attack of the entering edge of the airfoil. B.J.

A85-22370 EXTREMUM PROBLEM CONCERNING A WING WITH A MAXIMUM GRADIENT OF LIFT FORCE [EKSTREMAL'NAIA ZADACHA O KRYLE S MAKSIMAL'NYM GRADIENTOM POD'EMNOI SILY]

L. V. ARSHINSKII IN: Ill-posed problems in perturbation theory (A85-22364 08-02). Novosibirsk, Izdatel'stvo Nauka, 1984, p. 187-193. In Russian.

The paper examines the problem of selecting the three-dimensional geometry of a lifting surface in such a way as to provide for a maximum value of the modulus of the lift-force gradient with respect to the distance between the wing and a screen. The wing is assumed to move at quadrupolar distance from the screen, and the lift coefficient is determined on the basis of the theory of moderate near-screen perturbations. An extremum is obtained which coincides with the Euler extremum everywhere but at singular edges. B.J.

A85-22371

AN EXTREMUM PROBLEM CONCERNING THE SHAPE OF A BODY OF REVOLUTION IN SUPERSONIC GAS FLOW [ODNA EKSTREMAL'NAIA ZADACHA O FORME TELA VRASHCHENIIA V SVERKHZVUKOVOM POTOKE GAZA]

A. V. DANEEV IN: Ill-posed problems in perturbation theory (A85-22364 08-02). Novosibirsk, Izdatel'stvo Nauka, 1984, p. 194-199. In Russian. refs

The method of sources is used to solve an ill-posed problem concerning the shape optimization of a closed thin body of revolution, assuring minimum wave drag in linearized supersonic flow. A formula is obtained for the wave drag coefficient in the Mach number range of 1.5 to 6.

N85-15687*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

GROUND-EFFECT ANALYSIS OF A JET TRANSPORT AIRPLANE

R. E. CURRY and A. H. BOWERS Jan. 1984 12 p refs Presented at the 23rd AIAA Aerospace Sci. Meeting, Reno, Nev., 14-17 Jan. 1985

(NASA-TM-85920; H-1273; NAS 1.15:85920; AIAA-85-0307) Avail: NTIS HC A02/MF A01 CSCL 01A

An analysis of the ground effect of a jet transport airplane has been made. Data were obtained from recent flight tests primarily using the constant angle-of-attack approach technique. Reasonable results were obtained for ground-effect pitching moment and lift increments. These were compared with data from other sources, including computations, wind tunnel, and previous flight test. A recommended ground-effect model was developed from the results. A brief simulator study was conducted to determine the sensitivity of a particular configuration to this ground-effect model and its associated uncertainty. Author

N85-15688*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

ANALYTICAL MODELING OF CIRCUIT AERODYNAMICS IN THE NEW NASA LEWIS WIND TUNNEL

C. E. TOWNE, L. A. POVINELLI, W. G. KUNIK, K. K. MURAMOTO, C. E. HUGHES, and R. LEVY (Scientific Research Associates) 1985 22 p refs Presented at the 23rd Aerospace Sci. Meeting, Reno, Nev., 14-17 Jan. 1985; sponsored by AIAA (NASA-TM-86912; E-2405; NAS 1.15:86912; AIAA-85-0380) Avail: NTIS HC A02/MF A01 CSCL 01A

Rehabilitation and extention of the capability of the altitude wind tunnel (AWT) was analyzed. The analytical modeling program involves the use of advanced axisymmetric and three dimensional viscous analyses to compute the flow through the various AWT components. Results for the analytical modeling of the high speed leg aerodynamics are presented; these include: an evaluation of the flow quality at the entrance to the test section, an investigation of the effects of test section bleed for different model blockages, and an examination of three dimensional effects in the diffuser due to reentry flow and due to the change in cross sectional shape of the exhaust scoop. E.A.K. **N85-15689*#** National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

UNSTEADY PRESSURE MEASUREMENTS ON A BICONVEX AIRFOIL IN A TRANSONIC OSCILLATING CASCADE

L. M. SHAW, D. R. BOLDMAN, A. E. BUGGELE, and D. H. BUFFUM (Purdue Univ.) 1985 18 p refs Proposed for presentation at the 30th Intern. Gas Turbine Conf. and Exhibit, Houston, Tex., 17-21 Mar. 1985; sponsored by the American Society of Mechanical Engineering

(NASA-TM-86914; E-2408; NAS 1.15:86914) Avail: NTIS HC A02/MF A01 CSCL 01A

Flush-mounted dynamic pressure transducers were installed on the center airfoil of a transonic oscillating cascade to measure the unsteady aerodynamic response as nine airfroils were simultaneously driven to provide 1.2 deg of pitching motion about the midchord. Initial tests were performed at an incidence and angle of 0 deg and A Mach number of 0.65 in order to obtain results in a shock-free compressible flowfield. Subsequent tests were performed at an incidence angle of 7 deg and Mach number of 0.8 in order to observe the surface pressures with an oscillating shock near the leading edge of the airfoil. Results are presented for interblade phase angles of 90 and -90 deg and at blade oscillatory frequencies of 200 and 500 Hz (semi-chord reduced frequencies up to about 0.5 at a Mach number of 0.8). Results from the zero-incidence cascade are compared with a classical unsteady flat-plate analysis. Flow visualization results depicting the shock motion on the airfoils in the high-incidence cascade are discussed. The airfoil pressure data are tabulated. Author

N85-15690*# Kansas Univ., Lawrence. Flight Research Lab. AN INVESTIGATION OF VORTEX-INDUCED AERODYNAMIC CHARACTERISTICS OF SUPERSONIC CRUISE CONFIGURATIONS Semiannual Status Report, 1 Jul. - 31 Dec. 1984

C. E. LAN 28 Jan. 1985 14 p refs

(Contract NSG-1629)

(NASA-CR-174299; NAS 1.26:174299) Avail: NTIS HC A02/MF A01 CSCL 01A

The linear lifting surface theory which predicts the life in supersonic flow, even though the drag is usually underpredicted, is described. A method for calculating the nonlinear wave drag was developed to remedy this deficiency. The calculated sectional drag is modified by adding the difference between the exact two dimensional (2-D) and the linear 2-D wave drag at the calculated sectional lift coefficient. Improvement in the supersonic drag prediction is shown. The VORCAM code was modified for the FORTRAN 77 language and its input stream was rearranged. The Boeing code was adapted to the computer system. All CDC special features in the code are replaced with standard FORTRAN algorithms. It is suggested that because of the nonlinearity the solution appears to be nonunique crowding of two vortices, a mechanism of vortex asymmetry, is investigated.

N85-15691*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

LOADS AND AEROELASTICITY DIVISION RESEARCH AND TECHNOLOGY ACCOMPLISHMENTS FOR FY 1984 AND PLANS FOR FY 1985

J. E. GARDNER and S. C. DIXON Jan. 1985 162 p refs (NASA-TM-86356; NAS 1.15:86356) Avail: NTIS HC A08/MF A01 CSCL 01A

The loads and aeroelasticity divisions research accomplishments are presented. The work under each branch or technical area, described in terms of highlights of accomplishments during the past year and highlights of plans for the current year as they relate to 5 year plans for each technical area. This information will be useful in program coordination with other government organizations and industry in areas of mutual interest. E.A.K.

N85-15692*# Kansas Univ. Center for Research, Inc., Lawrence. Flight Research Lab.

DESIGN STUDY OF TECHNOLOGY REQUIREMENTS FOR HIGH PERFORMANCE SINGLE-PROPELLER-DRIVEN BUSINESS AIRPLANES Final Report

D. L. KOHLMAN and J. HAMMER Washington NASA Jan. 1985 105 p refs

(NASA-CR-3863; NAS 1.26:3863; KU-FRL-487-1) Avail: NTIS HC A06/MF A01 CSCL 01A

Developments in aerodyamic, structural and propulsion technologies which influence the potential for significant improvements in performance and fuel efficiency of general aviation business airplanes are discussed. The advancements include such technolgies as natural laminar flow, composite materials, and advanced intermittent combustion engines. The design goal for this parameter design study is a range of 1300 nm at 300 knots true airspeed with a payload of 1200lbs at 35,000 ft cruise altitude. The individual and synergistic effects of various advanced technologies on the optimization of this class of high performance, single engine, propeller driven business airplanes are identified.

EAK

N85-15693*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

DOWNWASH IN THE PLANE OF SYMMETRY OF AN ELLIPTICALLY LOADED WING

J. D. PHILLIPS Jan. 1985 26 p refs (NASA-TP-2414; A-9871; NAS 1.60:2414) Avail: NTIS HC

A03/MF A01 CSCL 01A

A closed-form solution for the downwash in the plane of symmetry of an elliptically loaded line is given. This theoretical result is derived from Prandtl's lifting-line theory and assumes that: (1) a three-dimensional wing can be replaced by a straight lifting line, (2) this line is elliptically loaded, and (3) the trailing wake is a flat-sheet which does not roll up. The first assumption is reasonable for distances greater than about 1 chord from the wing aerodynamic center. The second assumption is satisfied by any combination of wing twist, spanwise camber variation, or planform that approximates elliptic loading. The third assumption is justified only for high-aspect-ratio wings at low lift coefficients and downstream distances less than about 1 span from the aerodynamic center. It is shown, however, that assuming the wake to be fully rolled up gives downwash values reasonably close to those of the flat-sheet solution derived in this paper. The wing can therefore be modeled as a single horseshoe vortex with the same lift and total circulation as the equivalent ellipticity loaded line, and the predicted downwash will be a close approximation independent of aspect ratio and lift coefficient. The flat-sheet equation and the fully rolled up wake equation are both one-line formulas that predict the upwash field in front of the wing, as well as the downwash field behind it. These formulas are useful for preliminary estimates of the complex aerodynamic interaction between two wings (i.e., canard, tandem wing, and conventional aircraft) including the effects of gap and stagger. Author

N85-15694*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

A COMPARATIVE STUDY OF THE NONUNIQUENESS PROBLEM OF THE POTENTIAL EQUATION

M. D. SALAS, A. JAMESON (Princeton Univ., N.J.), and R. E. MELNIK (Grumman Aerospace Corp., Bethpage, N.Y.) Jan. 1985 23 p refs

(NASA-TP-2385; L-15682; NAS 1.60:2385) Avail: NTIS HC A02/MF A01 CSCL 01A

The nonuniqueness problem occurring at transonic speeds with the conservative potential equation is investigated numerically. The study indicates that the problem is not an inviscid phenomenon, but results from approximate treatment of shock waves inherent in the conservative potential model. A new bound on the limit of validity of the conservative potential model is proposed. Author **N85-15695*#** National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

AILERON EFFECTIVENESS FOR A SUBSONIC TRANSPORT MODEL WITH A HIGH-ASPECT-RATIO SUPERCRITICAL WING P. F. JACOBS Dec. 1983 277 p refs

(NASA-TM-85674; L-15646; NAS 1.15:85674) Avail: NTIS HC A13/MF A01 CSCL 01A

Aileron effectiveness for a subsonc energy efficient transport (EET) model with a high aspect ratio supercritical wing was determined in the 8-foot transonic pressure tunnel. Data are presented for ailerons located at three positions along the wing span. The ailerons were designed as a preliminary active control concept with gust load alleviation, maneuver load alleviation, and flutter suppression systems. A linear variation of rolling moment coefficient with angle of attack for individual and multiple aileron deflections at Mach numbers up to 0.81 is indicated. For Mach numbers greater than 0.81, the rolling moment coefficient data become nonlinear with increasing angle of attack. At Mach numbers near the design value increased aileron effectiveness resulted from aft transition locations, which produced relatively thin boundary lavers and greater effective aileron deflections. Individual aileron deflections on the right wing panel produced only small effects on vawing moment and side force coefficients. E.A.K.

N85-15696*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

AN EXPLORATORY STUDY OF FINITE DIFFERENCE GRIDS FOR TRANSONIC UNSTEADY AERODYNAMICS

D. A. SEIDEL, R. M. BENNETT, and W. WHITLOW, JR. Dec. 1982 39 p refs Presented at the 21st AIAA Aerospace Sci. Meeting, Reno, Nev., 10-13 Jan. 1983

(NASA-TM-84583; NAS 1.15:84583; AIAA-83-0503) Avail: NTIS HC A03/MF A01 CSCL 01A

Unsteady aerodynamic forces are calculated by the XTRAN2L finite difference program which solves the complete two dimensional unsteady transonic small perturbation equation. The unsteady forces are obtained using a pulse transfer function technique which assumes the flow field behaves in a locally linear fashion about a mean condition. Forces are calculated for a linear flat plate using the default grids from the LTRAN2-NLR, LTRAN2-HI, and XTRAN3S programs. The forces are compared to the exact theoretical values for flat plate, and grid generated boundary and internal numerical reflections are observed to cause significant errors in the unsteady airloads. Grids are presented that alleviate the reflections while reducing computational time up to fifty-three percent and program size up to twenty-eight percent. Forces are presented for a six percent thick parabolic arc airfoil which demonstrate that the transform technique may be successfully applied to nonlinear transonic flows. Author

N85-15697*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

COMPARISON OF ANALYTICAL AND EXPERIMENTAL STEADYAND UNSTEADY-PRESSURE DISTRIBUTIONS AT MACH NUMBER 0.78 FOR A HIGH-ASPECT-RATIO SUPERCRITICAL WING MODEL WITH OSCILLATING CONTROL SURFACES

W. E. MCCAIN Jan. 1984 56 p refs

(NASA-TM-84589; NAS 1.15:84589) Avail: NTIS HC A04/MF A01 CSCL 01A

The unsteady aerodynamic lifting surface theory, the Doublet Lattice method, with experimental steady and unsteady pressure measurements of a high aspect ratio supercritical wing model at a Mach number of 0.78 were compared. The steady pressure data comparisons were made for incremental changes in angle of attack and control surface deflection. The unsteady pressure data comparisons were made at set angle of attack positions with oscillating control surface deflections. Significant viscous and transonic effects in the experimental aerodynamics which cannot be predicted by the Doublet Lattice method are shown. This study should assist development of empirical correction methods that may be applied to improve Doublet Lattice calculations of lifting surface aerodynamics. E.A.K.

02 AERODYNAMICS

Naval Air Development Center, Warminster, Pa. N85-15699# Aircraft and Crew Systems Technology Directorate.

ANALYSIS OF THE FLOW FIELD ABOUT A T-45 USING PANAIR **Final Report**

W. W. TSENG, R. LLORENS, and J. GARDNER May 1984 29

(AD-A146811; NADC-84077-60) Avail: NTIS HC A03/MF A01 CSCL 20D

It is the purpose of this report to document the work performed in utilizing the linear inviscid flow program called PANAIR on the analysis of the T-45 Hawk aircraft. This report summarizes the excellent agreement possible when using PANAIR to predict model pressure data in a wind tunnel at low Mach numbers. The Naval Air Development Center, under this IR program, is attempting to transition computational fluid dynamics research codes into practical and useful design/analysis tools. This report summarizes the work accomplished while utilizing PANAIR to predict the wing pressure distributions on the T-45 Hawk aircraft and then comparing these data to experimental wind tunnel results. The T-45 aircraft is part of a new Navy training system that will provide fixed wing jet flight training for intermediate and advanced phases of the Navy Integrated Flight Training System (NIFTS) to meet future pilot production requirements. Comparisons of the theoretical predictions obtained from PANAIR with experimental results show excellent agreement between the two data sets. GRA

N85-16240# Joint Publications Research Service, Arlington, Va. PARACHUTE EXPEDITION TO ARCTIC

N. SELIVANOR In its USSR Rept.: Earth Sci. (JPRS-UES-84-008) 13 Dec. 1984 Transl. into ENGLISH from Daily Rev. 106-108 (Moscow), v. 30, no. 131, 29 Jun. 1984 p 1-4 Avail: NTIS HC A06

The technique of parachuting people and heavy cargo onto an ice floe in the Arctic is described. The challenges of establishing a floating research facility are discussed. Particular emphasis is placed upon runway construction which permits heavy aircraft to land and deliver essential supplies. R.S.F.

N85-16772# British Aerospace Aircraft Group, Weybridge (England).

PROGRESS RECENT OF DEVELOPMENT AND UNDERSTANDING OF HIGH LIFT SYSTEMS

In AGARD Improvement of Aerodynamic D. J. BUTTER Performance Through Boundary Layer Control and High Lift Systems 26 p Aug. 1984 refs Avail: NTIS HC A18/MF A01

The mechanical high lift device as it is used for transport type aircraft is discussed. Current design approaches are reviewed along with progress on both the development of high lift device design and on the understanding of the related flow physics. Likely future developments and the fundamental research required to achieve them are also addressed. M.G.

N85-16773# Royal Aircraft Establishment, Farnborough (England). Aerodynamics Dept.

INVESTIGATIONS INTO THE EFFECTS OF SCALE AND COMPRESSIBILITY ON LIFT AND DRAG IN THE RAE 5M PRESSURIZED LOW-SPEED WIND TUNNEL

S. P. FIDDES, D. A. KIRBY, D. S. WOODWARD, and D. H. PECKHAM In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 7 p Aug. 1984 refs

Avail: NTIS HC A18/MF A01

Results obtained from experiments in the RAE 5m low speed pressurized wind tunnel are presented. The tunnel is capable of operation over a range of pressures (from one to three atmospheres) so that the effects of Mach and Reynolds number may be separated. This decoupling of scale and compressibility effects makes possible reliable extrapolation of test results to full-scale conditions (where this is necessary) as well as giving greater insight into the underlying flow mechanisms. The large size of the tunnel, combined with pressurization to three atmospheres, enabled some tests, on small combat/trainer aircraft

and on bomb-like stores, to be carried out at full scale. Three facets of the work of the 5m tunnel are described: work aimed at predicting or improving the high lift performance of specific aircraft; work of a more fundamental nature concerned particularly with the optimization of high-lift devices on generalized research models; and work on the drag of stores carried externally on combat aircraft. Author

N85-16774# National Aerospace Lab., Amsterdam (Netherlands).

RECENT ADVANCES IN COMPUTATIONAL METHODS TO SOLVE THE HIGH-LIFT MULTI-COMPONENT AIRFOIL PROBLEM

B. OSKAM, D. J. LAAN, and D. F. VOLKERS In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 31 p Aug. 1984 refs Avail: NTIS HC A18/MF A01

Recent advances made in the analysis of viscous flow over high-lift multi component airfoil configurations are described. The calculation of viscous wakes subjected to large adverse pressure gradients is considered. The local supersonic flow over the slat of a high-lift configuration, with a free stream Mach number of around 0.2, is also addressed. Development of a computational method for turbulent wakes in adverse pressure gradient, including strong inviscid-viscous interaction, has improved the understanding of such phenomena as the off-the-surface pressure recovery capability of viscous wakes. The example of a wing with double-slotted flap shows that the wake, flowing into a region of higher pressure, may play a critical role that has not been recognized before. Results of the transonic panel method, solving the full potential equation, and the experimental data both show high local velocities reaching Mach numbers up to 1.6 at a free stream Mach number of 0.225. R.S.F.

N85-16775# Office National d'Etudes et de Recherches Aerospatiales, Paris (France).

DETAILED STUDY OF THE FLOW AROUND A MULTI-ELEMENT AIRFOIL. COMPARISON WITH CALCULATIONS [ETUDE DETAILLEE DE L'ECOULEMWNT AUTOUR D'UN PROFIL HYPERSUSTENTE COMPARISONS AVEC LES CALCULS

B. PORCHERON and J. J. THIBERT In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems Aug. 1984 refs In FRENCH: 7 p **ENGLISH** summary

Avail: NTIS HC A18/MF A01

Results are discussed for studies using a theoretical method for computing the viscous incompressible flow around multi-element airfoils as well as an experimental study of the flow around such configurations. The velocity profiles and the turbulence measurements around a multi-element airfoil clearly show the interaction between boundary-layer and wakes even when these are not merging and they have been used to draw accurate maps of the flow. The computing method of the flow around these configurations is based upon a panel method (both sources and vortices) for the inviscid part of the flow and a method providing calculation and coupling for boundary layers and wakes, under strong viscous interaction conditions. This method has given quite good results even when there are several simultaneous separated flow regions. The comparisons between computation and experiment described underline the necessity of improving the computing method in the region located above the flap. A.R.H.

N85-16776# Manchester Univ. (England). Dept. of the Mechanics of Fluids.

INVISCID COMPRESSIBLE FLOW PAST A MULTI-ELEMENT AEROFOIL

I. M. HALL and A. SUDDHOO In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 15 p Aug. 1984 refs

Avail: NTIS HC A18/MF A01

A conformal transformation method is used to generate an orthogonal curvilinear grid for two and three-element airfoil configurations. The compressible potential flow equations are solved by finite difference methods. The solution could serve as a starting point for an iterative solution of the full viscous compressible flow case. R.S.F.

N85-16783# Office National d'Etudes et de Recherches Aerospatiales, Toulouse (France).

APPLICATION OF TWO AND THREE-DIMENSIONAL CRITERIA FOR CALCULATING TRANSITIONS AND BOUNDARY LAYERS **OVER SWEPT WINGS**

D. ARNAL and E. COUSTOLS In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 19 p Aug. 1984 refs In FRENCH; **ENGLISH** summary

Avail: NTIS HC A18/MF A01

The possible origins of turbulence on an infinite swept wing are examined. A method for calculating the beginning of transition, and the transition region itself, is suggested for the three dimensional flow. The influence of sweep angle on transition and on drag coefficient of the airfoil and the efficiency of wall suction are discussed. E.A.K.

N85-16784# Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West Germany).

THEORETICAL STUDY OF BOUNDARY-LAYER CONTROL

E. H. HIRSCHEL In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 11p Aug. 1984 refs Avail: NTIS HC A18/MF A01

The inviscid flow past the upswept rear part of a fuselage is directed beneath the fuselage. This leads to an accumulation of boundary layer material at the lower side of the fuselage which might be prone to separation. The cross sections of the rear end of a typical transport airplane fuselage were modified from the original circles to rounded triangles, in this way shifting downward the centers of gravity of the cross sections. The side view contour, the width of the fuselage and the volume remain unchanged. Three different configurations without wing and tail unit were studied, the original and two modified ones. The inviscid flow was computed with the MBB panel method, the boundary layer development with the integral method of Cousteix and Aupoix for three dimensional turbulent, compressible flow. It is shown that less boundary layer material is transported under the rear part of the fuselage in the modified cases. The tendency of the skin friction lines to converge is reduced. The whole flow pattern at the base is improved. In the frame of boundary layer theory, however, no statement can be made about possible pressure drag reductions. An improvement of the elevator performance appears to be probable. The study shows that the upsweep of the fuselage is the main factor in the boundary layer development. The addition of the wing and the tail unit will only modify the picture. E.A.K.

N85-16785# Bochum Univ. (West Germany). DRAG REDUCTION DUE TO BOUNDARY-LAYER CONTROL BY

COMBINED BLOWING AND SUCTION J. WIEDEMANN and K. GERSTEN In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 10p Aug. 1984 refs

Avail: NTIS HC A18/MF A01

The boundary control system of combined blowing and suction was investigated. Blowing is applied in the front part of the body where the pressure gradient is favorable, whereas suction is applied in the rear part of the body where adverse pressure gradients exist. To avoid the sink drag the volume rate of suction should be equal or smaller than the blowing volume rate. Theoretical investigations of laminar flows include optimization of the blowing velocity distribution and second order boundary layer effects such as pressure drag and displacement effects on friction drag. Experimental results of turbulent boundary layers with very strong blowing velocities near the stagnation point of a circular cylinder are used as a basis of a simple prediction method. Experiments on a circular cylinder show considerable drag reductions due to the combined blowing and suction boundary layer control system. E.A.K.

National Aeronautics and Space Administration. N85-16787*# Langley Research Center, Hampton, Va.

LAYER CONTROL ON SUBSONIC TRANSPORT AIRCRAFT

R. D. WAGNER, D. V. MADDALON, and M. C. FISCHER In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 13 p Aug. 1984 refs Previously announced in IAA as A84-33137

Avail: NTIS HC A18/MF A01 CSCL 01A

The development of laminar flow technology for commercial transport aircraft is discussed and illustrated in a review of studies undertaken in the NASA Aircraft Energy Efficiency (ACEE) program since 1976. The early history of laminar flow control (LFC) techniques and natural laminar flow (NLF) airfoil designs is traced, and the aims of ACEE are outlined. The application of slotted structures, composites, and electron beam perforated metals in supercritical LFC airfoils, wing panels, and leading edge systems is examined; wind tunnel and flight test results are summarized; studies of high altitude ice effects are described; and hybrid (LFC/NLF designs are characterized. Drawings and photographs are provided. (IAA)

N85-16788*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

TURBULENT DRAG REDUCTION RESEARCH

D. M. BUSHNELL, J. B. ANDERS, M. J. WALSH, and R. V. MCINVILLE (North Carolina State Univ.) In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 13 p Aug. 1984 refs Avail: NTIS HC A18/MF A01 CSCL 01A

Research in the area of turbulent drag reduction for attached flows is summarized. The most promising passive techniques utilize non-planar geometry. Of particular interest is the suitability of these devices for retrofit of existing vehicles. Five methods for reducing turbulent skin friction drag on bodies/fuselages are discussed. They are: (1) large-eddy breakup devices; (2) riblets; (3) slot injection optimization; (4) control of Emmons spot generation; and (5) relaminarization through massive suction. Except for the Emmons spot work these methods all indicate the possibility of sizable net reductions in skin friction for laboratory conditions. B.W.

Office National d'Etudes et de Recherches N85-16793# Aerospatiales, Paris (France).

INTEREST OF INTERNAL BLEED FOR A TWO-DIMENSIONAL AIR INTAKE OPERATING IN A WIDE MACH NUMBER RANGE (1.8-3 PLUS)

G. LARUELLE, C. SANS, and R. LEFEBVRE (Societe National Industrielle Aerospatiale, Chatillon, France) In AGARD Improvement of Aerodynamic Performance Through Boundary Laver Control and High Lift Systems 10 p Aug. 1984 refs In FRENCH; ENGLISH summary

Avail: NTIS HC A18/MF A01

٤,

From a two-dimensional air intake with an internal bleed and optimized for approximately Mach number 2, a new configuration is sought allowing still good performance up to Mach number 3 plus, but with the minimum of movable parts. The main geometrical parameters are: the slope of the external compression ramp; the internal section law of the diffuser; and the inlet section of the internal bleed. The internal bleed and the advantage of a variable geometry are discussed, as well as the model which was built at large scale and its equipment; motorizations, measurement devices, and internal visualizations. The tests were performed in a supersonic wind tunnel. A movie shows shadowgraphs of the flow in the air intake geometrical throat, where the internal bleed is located, for several configuration changes (external ramp or diffuser wall rotations, increases of Mach number or angle of attack), and variable internal obstruction. Some results obtained with this air-intake model are explained. The choice of two configurations allowing correct performance in the studied Mach number range, by optimization of the internal bleed geometry, is commented on. R.J.F.

N85-16795# Messerschmitt-Boelkow-Blohm G.m.b.H., Bremen (West Germany).

ACTIVE AND PASSIVE SHOCK/BOUNDARY LAYER INTERACTION CONTROL ON SUPERCRITICAL AIRFOILS THIEDE, P. KROGMANN (Deutsch Forschungs-Ρ. und Versuchsanstalt fuer Luft- und Raumfahrt, Goettingen, West Germany), and E. STANEWSKY (Deutsch Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Goettingen, West Germany) In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 13 p Aug. 1984 refs

Avail: NTIS HC A18/MF A01

Experimental investigations aiming at the improvement in the off-design performance of supercritical airfoils by active or passive control of the shock/boundary layer interaction (SBLI) through boundary layer suction in the shock region or ventilation respectively are presented. The experiments were carried out in a transonic wind tunnel using an advanced supercritical airfoil designed to have a largely fixed shock position at off-design conditions. The basic model was equipped with an exchangeable control device within the shock region of allow measurements with either surface clean, suction through a single slot, double slot or perforated strip, or ventilation through a double slot or perforated strip. The effectiveness of the different SBLI control methods is evaluated from surface pressure distribution, wake and boundary layer measurements, and Schlieren observations. It is shown that local boundary layer suction in the shock region mainly delays the shock-induced separation to greater shock strength and stabilizes the shock in its rearward position up to higher incidence, resulting in substantial improvements in the airfoil characteristics at off-design conditions. Without any suction a favorable passive effect is observed by boundary layer ventilation on the double slot and perforated strip configurations with a plenum underneath. A weakening of the shock wave results, offering a large potential for off-design drag reductions. R.J.F.

N85-16822 Illinois Univ., Urbana-Champaign.

AN OPTIMIZATION METHOD FOR THE PRELIMINARY DESIGN OF INTERPLANETARY AEROBRAKING MISSIONS Ph.D. Thesis

S. J. HOFFMAN 1984 161 p Avail: Univ. Microfilms Order No. DA8422080

The use of atmospheric drag to circularize spacecraft orbits, a concept referred to as aerobraking, can significantly increase the useful payload mass fraction for various types of missions. A procedure is devised which determines the optimal combination of aerobrake shielding area and initial orbit period to maximize the spacecraft mass in the final orbit. Two computer codes are constructed and the results from each are compared. The first simulation assumes only aerodynamic drag perturbations and uses simplified analytical expressions. The second is a detailed numerical integration including perturbations due to drag, atmospheric rotation, planet oblateness, third-body effects, and solar radiation pressure. Hypersonic aerodynamic heating rate equations for two different shield configurations are discussed and their performances are compared. Illustrative numerical examples for a Venus and a Mars mission are included. Dissert. Abstr.

N85-16823 Michigan Univ., Ann Arbor. SHOCK WAVES IN TRANSONIC FLOWS AT MODERATE REYNOLDS NUMBER Ph.D. Thesis J. L. MACE 1984 244 p

Avail: Univ. Microfilms Order No. DA8422281

The behavior of shock waves in transonic flow with varying Reynolds and Prandtl numbers was examined using analytical and numerical methods. The method of matched asymptotic expansions was used to provide analytical solutions for both an inviscid and a viscous, thermally-conducting flow moving at transonic speeds in a symmetric channel. Also, analytical solutions were obtained for the structure of a shock wave in a viscous, thermally-conducting flow moving at transonic speeds about an airfoil. Finally, a finite-volume numerical method was used to provide solutions to inviscid, transonic flows in a channel. It was shown that, to the accuracy desired, the location of the sonic line within the structure of a shock wave is independent of Reynolds number and, thus, coincident with the location of the corresponding discontinuous wave in the limit as Reynolds number tends to infinity. Also, in a numerical solution, truncation errors and artificial viscosity produce a smeared shock wave which is similar to that found in a flow at moderate Reynolds number. Dissert. Abstr.

N85-16825*# Atlanta Univ., Ga. RANDOM EQUATIONS IN AERODYNAMICS Semiannual Progress Report, 1 Oct. 1983 - 1 Apr. 1984 A. T. BHARUCHA-REID 1 Apr. 1984 3 p

(Contract NAG1-413)

(NASA-CR-174279; NAS 1.26:174279) Avail: NTIS HC A02/MF A01 CSCL 01A

Literature was reviewed to identify aerodynamic models which might be treated by probablistic methods. The numerical solution of some integral equations that arise in aerodynamical problems were investigated. On the basis of the numerical studies a qualitative theory of random integral equations was developed to provide information on the behavior of the solutions of these equations (in particular, boundary and asymptotic behavior, and stability) and their statistical properties without actually obtaining explicit solutions of the equations. B.G.

N85-16826*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

HELICOPTER MODEL ROTOR-BLADE VORTEX INTERACTION IMPULSIVE NOISE: SCALABILITY AND PARAMETRIC VARIATIONS

W. R. SPLETTSTOESSER (DFVLR, Brunswick), K. J. SCHULTZ (DFVLR, Brunswick), D. A. BOXWELL, and F. H. SCHMITZ Dec. 1984 31 p refs Prepared in cooperation with Army Research and Technology Labs., Moffett Field, Calif.

(NASA-TM-86007; A-9854; NAS 1.15:86007; TM-84-A-7) Avail: NTIS HC A03/MF A01 CSCL 01A

Acoustic data taken in the anechoic Deutsch-Niederlaendischer Windkanal (DNW) have documented the blade vortex interaction (BVI) impulsive noise radiated from a 1/7-scale model main rotor of the AH-1 series helicopter. Averaged model scale data were compared with averaged full scale, inflight acoustic data under similar nondimensional test conditions. At low advance ratios (mu = 0.164 to 0.194), the data scale remarkable well in level and waveform shape, and also duplicate the directivity pattern of BVI impulsive noise. At moderate advance ratios (mu = 0.224 to 0.270), the scaling deteriorates, suggesting that the model scale rotor is not adequately simulating the full scale BVI noise; presently, no proved explanation of this discrepancy exists. Carefully performed parametric variations over a complete matrix of testing conditions have shown that all of the four governing nondimensional parameters - tip Mach number at hover, advance ratio, local inflow ratio, and thrust coefficient - are highly sensitive to BVI noise radiation. Author

N85-16829*# Missouri Univ., Rolla. Dept. of Mechanical and Aerospace Engineering

AERODYNAMIC-STRUCTURAL STUDY OF CANARD WING. DUAL WING, AND CONVENTIONAL WING SYSTEMS FOR **GENERAL AVIATION APPLICATIONS Final Report**

B. P. SELBERG and D. L. CRONIN Feb. 1985 87 p refs (Contract NAG1-26)

(NASA-CR-172529; NAS 1.26:172529) Avail: NTIS HC A05/MF A01 CSCL 01A

An analytical aerodynamic-structural airplane configuration study was conducted to assess performance gains achievable through advanced design concepts. The mission specification was for 350 mph, range of 1500 st. mi., at altitudes between 30,000 and 40,000 ft. Two payload classes were studied - 1200 lb (6 passengers) and 2400 lb (12 passengers). The configurations analyzed included canard wings, closely coupled dual wings, swept forward - swept rearward wings, joined wings, and conventional wing tail arrangements. The results illustrate substantial performance gains possible with the dual wing configuration. These gains result from

weight savings due to predicted structural efficiencies. The need for further studies of structural efficiencies for the various advanced configurations was highlighted. Author

N85-16832# Nielsen Engineering and Research, Inc., Mountain View, Calif.

PREDICTION OF CRUCIFORM ALL-MOVABLE CONTROL CHARACTERISTICS AT TRANSONIC SPEEDS Final Technical Report, 1 Jan. 1983 - 31 Mar. 1984

J. N. NIELSEN, F. K. GOODWIN, and M. F. E. DILLENIUS Mar. 1984 258 p

(Contract N00014-81-C-0267; F41-411)

(AD-A147291; NEAR-TR-321) Avail: NTIS HC A12/MF A01 CSCL 20D

A study has been made of the feasibility of developing a transonic hinge-moment prediction method for cruciform all-movable controls by correlating an extensive data base using the equivalent angle of attack concept. Body vortex effects have been handled using a simplified vortex model. Existing data from the Army generalized missile have been studied to examine transonic nonlinearities including pitch-yaw coupling and fin-fin control interference. Data for an aspect ratio 3.53, taper ratio 0.06 canard fin have been successfully correlated on the basis of the equivalent angle-of-attack concept. Data for an aspect ratio 2 delta fin mounted aft on the triservice missile have also been studied for angle of attack to 20% for Mach numbers of 0.8 and 12. Methods of extending the range of applicability of a previous hinge-moment prediction method have been developed. Desirable future extensions have been pointed out. GRA

N85-16833# Aeronautical Research Labs., Melbourne (Australia).

CALCULATION OF THE VELOCITY FIELD GENERATED BY A HELICOPTER MAIN AND TAIL ROTORS IN HOVER

K. J. HAYMAN and K. R. REDDY Jul. 1984 19 p (AD-A147731; ARL-AERO-TM-366) Avail: NTIS HC A02/MF A01 CSCL 20D

A theory is presented to calculate the flow field due to main and tail rotors of a helicopter in hovering flight. To solve this complex flow problem, simple vortex rings are used to model main and tail rotor wakes. Preliminary numerical results are found to be encouraging. Author (GRA)

N85-16834# Rockwell International Corp., Los Angeles, Calif. North American Aircraft Operations.

JOINED WING TRANSONIC DESIGN AND TEST VALIDATION Final Report, 30 Sep. 1982 - 31 May 1984

J. A. CLYDE, E. BONNER, T. P. GOEBEL, and L. SPACHT 22 Jun. 1984 158 p

(Contract N00014-82-C-0601; NR PROJ. 212-276)

(AD-A148355; NA-84-1434) Avail: NTIS HC A08/MF A01 CSCL 20D

A tactical supercritical flow research model was designed to achieve high aerodynamic efficiency at Mach number 0.90 and lift coefficient 0.50 using numerical transonic design procedures. A wind tunnel model was built and tested in the Rockwell International Trisonic Wind Tunnel at Mach numbers of 0.40, 0.85, 0.90, 0.95. Lift-drag ratio at the design condition compared favorably with theoretical upper bound levels for the test arrangement and conditions. Six component force measurements for the joined wing are well behaved and near linear over an angle-of-attack range of -4< alpha <10 degrees. Stable stall is naturally achieved for the arrangement. Weak changes in longitudinal and lateral-directional stability and control with pitch angle exist. GRA

N85-16835# Naval Surface Weapons Center, White Oak, Md. Underwater Systems Dept.

A THEORETICAL VIEW ON THE STRESS ANALYSIS OF FULLY INFLATED PARACHUTE CANOPIES

W. P. LUDTKE 28 May 1984 72 p

(AD-A148387; NSWC/TR-84-204) Avail: NTIS HC A04/MF A01 CSCL 01C

This report describes a theoretical approach to the analysis of the force distribution in fully inflated parachute canopies based upon the inflated gore mainseam shape. Normal and tangential forces for any arbitrary point along the gore mainseam can be determined and the magnitude and location of the maximum normal force and cloth stress evaluated. Methods, criteria, and rationale for calculating the force distributions are presented. GRA

N85-16836# Analytical Methods, Inc., Redmond, Wash,

PREDICTION OF DYNAMIC STALL CHARACTERISTICS USING ADVANCED NON-LINEAR PANEL METHODS Final Report, 1

Nov. 1982 - 17 Apr. 1984 B. MASKEW and F. A. DVORAK 4 Apr. 1984 63 p (Contract F49620-82-C-0019)

(AD-A148453; AMI-8406; AFOSR-84-0975TR) Avail: NTIS HC

A04/MF A01 CSCL 20D

A surface singularity panel method was extended for modeling the dynamic interaction between a separated wake and a surface undergoing an unsteady motion. The method combines the capabilities of an unsteady, time-stepping code and a technique for modeling extensive separation using free vortex sheets. Routines were developed for treating the dynamic interaction between the separated wake and the solid boundary in an environment where the separation point is moving with time. The behavior of these routines is being examined in a parallel effort using a two-dimensional pilot version of the three-dimensional pilot version of the three-dimensional code. This allows refinements in the procedures to be quickly developed and tested prior to installation into the main code. The extended code was coupled with an unsteady integral boundary layer method to examine the prediction of dynamic stall characteristics. The boundary layer code is accessed during the time-step cycle and provides the separation locations as well as the boundary layer displacement effect: the latter is modelled in the potential flow code using the source transpiration technique. The preliminary results include basic unsteady test cases for both the potential flow and boundary layer routines. GRA

Dornier-Werke G.m.b.H., Friedrichshafen (West N85-16838# Germany). Abt. Theoretische Aerodynamik.

THEORETICAL CONTRIBUTIONS TO TRANSONIC FLOW ANALYSIS FOR TRANSPORT AIRCRAFT Final Report, Dec. 1982

W. FRITZ, S. LEICHNER, W. SCHMIDT, and H. W. STOCK Bonn Bundesministerium fuer Forschung und Technologie Oct. 1984 125 p refs In GERMAN; ENGLISH summary Sponsored by Bundesministerium fuer Forschung und Technologie (BMFT-FB-W-84-036; ISSN-0170-1339) Avail: NTIS HC A06/MF A01; Fachinformationszentrum, Karlsruhe, West Germany DM 26.50

Two and three dimensional computational methods were improved for the analysis of transonic aircraft. Viscous flow modeling and the analysis of unsteady transonic flow were emphasized. A fast method was developed for computation of viscous airfoil flow, and a finite volume method for general wing-body combinations, coupled with three-dimensional boundary-layer packages. Two and three-dimensional unsteady transonic flow solutions were derived for the analysis of flutter and active control devices. Author (ESA)

AIR TRANSPORTATION AND SAFETY

Includes passenger and cargo air transport operations; and aircraft accidents.

A85-19513#

SAFETY - METEOROLOGICAL DATA VITAL FOR SIMULATOR TRAINING

J. T. KLEHR (Singer Co., Link Flight Simulation Div., Binghamton, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs

(AIAA PAPER 85-0091)

Meteorological data and models currently in use in commercial transport aircraft simulators are reviewed and areas of possible improvements are indicated. Since modern simulators are computer-controlled and have six degrees of freedom in motion, the input of meteorological data such as that gathered during the JAWS experiment and with Doppler radar permits simulation of aircraft motion in response to wind shear and turbulence, provided sufficient computer power is available. The wind shear changes incorporate the effects of varying wind speed. The simulation attains higher realism when fed an input of high resolution meteorological numerical models, which also describe gusts and thunderstorm echoes. Further work and greater computer capacity is required to faithfully represent thunderstorm clouds, lightning strikes on and near aircraft, and icing hazards.

A85-19516#

THE LIGHTNING THREAT TO AEROSPACE VEHICLES

P. L. RUSTAN, JR. (USAF, Wright Aeronautical Laboratories, Wright-Patterson AFB, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985, 6 p. refs

(AIAA PAPER 85-0094)

During 1984 the United States Air Force Wright Aeronautical Laboratory and the Federal Aviation Administration conducted an inflight lightning measurement program using a CV-580 aircraft in the vicinity of the Kennedy Space Center, FL. The aircraft was flown in thunderclouds where the regions of precipitation did not exceed 40 dBz between 2,000 and 18,000 feet. The aircraft was instrumented to measure the current flow on the wing tips, the normal and horizontal component of current density on the fuselage and on the wings, the electrostatic field, and the VHF radiation during direct lightning attachment. The transient electromagnetic characteristics of the lightning attachment were recorded by using six Tektronix 7612D waveform digitizers with a sample rate of 5 ns and a Honeywell 101 analog recorder with a 2 MHz frequency response. Data from 21 direct strike lightning attachment were recorded in the CV-580 aircraft during the program. The maximum rate of rise of the electric and magnetic flux density measured at the aircraft during direct lightning attachments were 22 A/sq m and 2950 T/s, respectively. This paper presents the characteristics of these fast pulses and the overall characteristics of the lightning flashes. Author

A85-19679#

THE DEVELOPMENT OF MATHEMATICAL MODELLING TECHNIQUES FOR HELICOPTER ROTOR ICING

R. W. GENT and J. T. CANSDALE (Royal Aircraft Establishment, Farnborough, Hants., England) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs

(AIAA PAPER 85-0336)

Recent theoretical work at RAE on helicopter rotor icing and electrothermal deicing protection systems is presented. Mathematical models for the prediction of rotor ice accretion are described. These cover both droplet trajectories and the thermodynamic process of ice formation on an aerofoil in compressible flow. Details are given of the development stages from the initial 2-dimensional hover model with non-conducting surface, through the inclusion of structural heat conduction, to a complete transient model which includes the effects of cyclic airspeed and pitch appropriate to a helicopter in forward flight. Significant progress has been made in the prediction of glaze ice shapes. The development of mathematical models for the prediction of temperature transients in rotors protected with an electrothermal deicing system is also described. The various stages of complexity achieved with both one and two dimensional models are discussed. Results showing typical output from the models are included.

Author

A85-19680#

CORRELATION OF AIRFOIL ICING RELATIONSHIPS WITH TWO-DIMENSIONAL MODEL AND FULL SCALE ROTORCRAFT ICING TEST DATA

R. J. FLEMMING and D. A. LEDNICER (United Technologies Corp., Sikorsky Aircraft Div., Stratford, CT) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 16 p. refs

(AIAA PAPER 85-0337)

Tests have been conducted in a high-speed icing wind tunnel and a transonic airfoil facility to expand the data base on the performance of iced two-dimensional helicopter airfoils. It is found that generally, lift and drag increments vary linearly with liquid water content and icing time. Increasing Mach number has a greater effect on 12-pct-thick airfoils than on 9-pct-thick airfoils. The data have been generalized into a series of equations, providing predictions of ice thickness and force and moment coefficients with an accuracy of about 30 percent. The relationships have been incorporated into rotorcraft performance codes to give ice extent and torque rise information. V.L.

A85-19719#

EVALUATION OF AIRCRAFT INTERIOR PANELS UNDER FULL-SCALE CABIN FIRE TEST CONDITIONS

C. P. SARKOS and R. G. HILL (FAA, Technical Center, Atlantic City, NJ) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(AIAA PAPER 85-0393)

Realistic full-scale fire tests demonstrated the potential safety benefits of advanced interior panels in transport aircraft, and displayed the characteristics of cabin fire hazards. The tests were conducted in a C-133 airplane, modified to resemble a wide-body interior, under postcrash and in-flight fire scenarios. The safety benefit of the advanced panel ranged from a 2-minute delay in the onset of flashover when the cabin fire was initiated by a fuel fire adjacent to a fuselage rupture, to the elimination of flashover when the fuel fire was adjacent to a door opening or when an in-flight fire was started from a seat drenched in gasoline. Analysis of the cabin hazards measured during postcrash fire tests indicated that the greatest threat to passenger survival was cabin flashover, and that toxic gases did not reach hazardous levels unless flashover occurred.

A85-19720*# Jet Propulsion Lab., California Inst. of Tech., Pasadena.

MEASUREMENTS OF THE RESPONSE OF TRANSPORT AIRCRAFT CEILING PANELS TO FUEL POOL FIRES

C. P. BANKSTON and L. H. BACK (California Institute of Technology, Jet Propulsion Laboratory, Pasadena, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. NASA-supported research. refs

(AIAA PAPER 85-0394)

Tests were performed to characterize the responses of various aircraft ceiling panel configurations to a simulated post-crash fire. Attention was given to one currently used and four new ceiling configurations exposed to a fuel pool fire in a circulated air enclosure. The tests were controlled to accurately represent conditions in a real fire. The panels were constructed of

fiberglass-epoxy, graphite-phenolic resin, fiberglass-phenolic resin, Kevlar-epoxy, and Kevlar-phenolic resin materials. The phenolic resin-backed sheets performed the best under the circumstances, except when combined with Kevlar, which became porous when charred. M.S.K.

A85-19721#

THE THERMAL RESPONSE OF AIRCRAFT CABIN CEILING MATERIALS DURING A POST-CRASH, EXTERNAL FUEL-SPILL, **FIRE SCENARIO**

L. Y. COOPER (National Bureau of Standards, Center for Fire Research, Gaithersburg, MD) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. Research supported by the U.S. Department of Transportation and FAA. refs

(AIAA PAPER 85-0395)

Aircraft cabin ceiling temperatures were measured in full scale simulated post-crash fire conditions. A C133A cargo aircraft with the wings and tail surfaces removed was employed in the trials. which featured burning JP-4 fuel and data gathered with fluxmeters and thermocouples in a seat and in the ceiling. Eight tests were performed and numerical models were formulated for thermal radiation from the doorway, seat, ceiling, and far away sources, convective heat transfer, and heat transfer from the upper ceiling surface. The resulting algorithm was validated in comparison with data from tests with several seats within the cabin. The algorithm is recommended for evaluating seat material and ceiling configurations considered in terms of their contributions to the fire safety of the aircraft. M.S.K.

A85-19768#

A SUMMARY OF NASA'S RESEARCH ON THE FLUID ICE **PROTECTION SYSTEM**

A. E. ALBRIGHT (General Dynamics Corp., Fort Worth, TX) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 14 p. refs (AIAA PAPER 85-0467)

One of the primary objectives of the considered investigations is related to a study of minimum anti-ice flow rates required in general aviation deicing systems on contemporary airfoils, taking into account the times required for deicing. Another objective is the presentation of two methods of predicting anti-ice flow rates, and their comparison with the wind tunnel results. Attention is given to the icing research tunnel and the wing models, the fluid ice protection system, the test techniques and procedures, stainless steel and titanium wing-panel configurations, a comparison of the new laser drilled titanium panel with the old stainless steel panel, the ADS-4 anti-ice flow rate prediction method, and an analytical method of predicting anti-ice flow rates. GR

A85-19846

ANALYSIS OF FATAL ACCIDENTS INVOLVING LIGHT AIRCRAFT WEIGHING UP TO TWO TONS AND THEIR CAUSES IN THE CONTEXT OF FLIGHT MEDICINE [ANALYSE VON TOEDLICHEN UNFAELLEN MIT LEICHTFLUGZEUGEN BIS ZU ZWEI TONNEN UND DEREN URSACHEN UNTER FLUGMEDIZINISCHEN ASPEKTEN]

Muenchen, Technische Universitaet, Fakultaet fuer K. BAYER Medizin, Doktor der Medizin Dissertation, 1982, 85 p. In German. refs

All fatal accidents that occurred in the Federal Republic of Germany in aircraft weighing up to two tons during 1973-1977, a total of 104, have been evaluated in order to determine their causes. The human factor is emphasized, and the concepts of airflight medicine are used to probe the physiology of the sense organs of pilots and the parameters of competence to safely pilot an aircraft. Mechanical causes of accidents are also examined. the role of time of day and of flight phase in the generation of accidents. C.D.

A85-20148

WIND SHEAR - TAMING THE KILLER

D. BOYLE Interavia (ISSN 0020-5168), vol. 40, Jan. 1985, p. 65,

The possible consequences of wind shear, particularly microburst, phenomena are described, and prediction and avoidance techniques are recommended, based on research by the UK Royal Aircraft Establishment (RAE) and the US Joint Airport Weather Studies. A microburst, described as a collision of two masses of air traveling at different speeds, can be simulated using a mathematical three-dimensional model developed by RAE with the intensity of the down-draught controlled up to an unsurvivable speed of 85 km, whereas most events observed are in the region of 40-60 km. A set of instructions for pilots is developed, tested in a DC-10 simulator for take-off and landing procedures. Wind shear detection and effective avoidance, obstructed by the phenomenon's infrequency, localization, and short duration, can be achieved by Doppler radar (not yet deployed extensively) and the Low Level Wind Shear Alert System developed in the US, which uses an arrangement of remote anemometers spaced throughout an airport to detect wind direction and velocity. I T

A85-20872*# Wichita State Univ., Kans. ICING TUNNEL TESTS OF ELECTRO-IMPULSE DE-ICING OF AN ENGINE INLET AND HIGH-SPEED WINGS

G. W. ZUMWALT (Wichita State University, Wichita, KS) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs (Contract NAG3-284)

(AIAA PAPER 85-0466)

A brief review is given of four earlier tests in the NASA Lewis Icing Research Tunnel and of flight tests in NASA's Icing Research Aircraft and in a Cessna 206 airplane. Details are given of recent icing tunnel tests of thicker-skinned wings, a Gates Learjet, a composite leading edge, and a Boeing 767, and of a Falcon Fanjet engine inlet. These were tested at speeds from 87 to 220 knots, air temperatures from -2 to -15 C, LWC values of 0.6 to 2.4 grams/cu meter, and median droplet diameters from 12 to 20 microns. Energy requirements are reported, as well as conclusions from comparisons of several Electro-Impulse De-Icing coil system designs. Fundamental studies of the structural dynamics and ice shedding of a 12.7 cm (5 inch) diameter semicylinder are described. Some potential problem areas are discussed: fatigue of skin and coil mountings, system weight and cost, electro-magnetic interference and noise. Author

A85-21582#

JUDGMENT AND DISCIPLINE - RECIPE FOR SURVIVAL

J. R. GREENWOOD (Gates Learjet Corp., Tucson, AZ) IN: Symposium on Aviation Psychology, 2nd, Columbus, OH, April 25-28, 1983, Proceedings . Columbus, OH, Ohio State University, 1984, p. 393-400. refs

The major causes of aircraft accidents in the general aviation field are discussed in an anecdotal style, and with reference to National Traffic Safety Board (NTSB) statistics. It is shown that since 80 percent of the fatal aircraft accidents in the U.S. are caused by human factors, the exercise of better judgment and discipline on the part of professional pilots could reduce the number of fatalities significantly. It is recommended that future training courses for general aviation pilots place greater emphasis on developing judgment and discipline in the operation of commercial aircraft. I.H.

A85-21643

AN OVERVIEW OF HELICOPTER'S ENVIRONMENTAL CONSIDERATIONS

J. W. LEVERTON (Westland, Inc., Arlington, VA) Vertiflite (ISSN 0042-4455), vol. 31, Jan.-Feb. 1985, p. 14, 15.

Increasing helicopter rotor tip speeds for larger and heavier aircraft have tended to increase community awareness of noise levels, together with the dramatic increase in helicopter fleet size, over the last 10 years. The problems posed by this awareness are exacerbated by air traffic control practices which require flyover

03 AIR TRANSPORTATION AND SAFETY

altitudes of 500 ft or less. As part of a general consideration of the helicopter noise problem, the FAA and ICAO have undertaken detailed evaluations of noise-related helicopter design factors. In addition, the American Helicopter Society, in conjunction with NASA and helicopter manufacturers, formulated the National Rotorcraft Noise Reduction Program. Recommendations have also been made for routine helicopter operations and heliport design criteria.

0.C.

A85-21668

STRESS ANALYSIS AND SHAPING OF THE CANOPY OF A SQUARE PARACHUTE [ANALIZ NAPRIAZHENNOGO SOSTOIANIIA I FORMOOBRAZOVANIIA KUPOLA KVADRATNOGO PARASHIUTA]

M. V. DZHALALOVA Moskovskii Universitet, Vestnik, Seriia 1 -Matematika, Mekhanika (ISSN 0579-9368), Nov.-Dec. 1984, p. 93-96. In Russian. refs

A calculation method is developed for determining the shape of the meridional cross sections and the equatorial stresses of the fabric of the canopy of a square parachute in the case when Delta-p/q is a constant, where p is pressure and q is velocity head. It is assumed that there is a local similarity (i.e., a similarity of meridional cross sections) between the shapes of square and circular parachutes. The analysis is based on Rakhmatulin's equations for a circular parachute. B.J.

N85-15700 Department of the Air Force, Washington, D.C. **WINDBLAST LEG PROTECTOR ASSEMBLY Patent**

R. J. CUMMINGS, inventor (to Air Force) 14 Aug. 1984 8 p Supersedes AD-D010307

(AD-D011376; US-PATENT-4,465,250;

US-PATENT-APPL-SN-465230) Avail: US Patent and

Trademark Office CSCL 06Q

This patent is for a windblast leg protector assembly for use by an occupant of an open-type ejection seat of an aircraft. The assembly includes, for each leg of the seat occupant, a modification to the occupant's conventional anti-acceleration suit by way of a piece of nylon fabric (with concave configurated load spreading cuts, and with a ring captured thereon) attached to the thigh portion, and a similar piece of nylon fabric with a ring captured thereon attached to the calf portion, of each full length leg member of the anti-acceleration suit. Restraining-/retracting straps which are connected to, and which remain with the ejection seat, are also constituent components of the windblast leg protector assembly. Snap hooks, which are captured on the slack restraining/retracting straps, are releasably connected by the occupant, after sitting down in the ejection seat, to the captured rings on the thigh and the calf portions of the anti-acceleration suit being worn. During ejection, the slack restaining/retracting straps are automatically retracted and tensioned, thereby pulling downwardly on the captured rings, their retaining members, the leg members of the suit, and the legs of the occupant. As a result, the legs of the occupant are restrained, and thereby are prevented from being extended into the windblast. Although the thighs of the occupant are downwardly restrained during ejection, the calves of the seated occupant's legs move upwardly to relieve any tension load in the occupant's knees. GRA

N85-15701*# Jet Propulsion Lab., California Inst. of Tech., Pasadena.

FLOW OF NITROGEN-PRESSURIZED HALON 1301 IN FIRE EXTINGUISHING SYSTEMS

D. G. ELLIOTT, P. W. GARRISON, G. A. KLEIN, K. M. MORAN, and M. P. ZYDOWICZ 1 Nov. 1984 124 p refs

(Contract NAS7-918)

(NASA-CR-174271; JPL-PUBL-84-62; NAS 1.26:174271) Avail: NTIS HC A06/MF A01 CSCL 01C

Halon 1301 which is a halocarbon fire extinguishing agent (CBrF3) used by the U.S. Army for vehicle fire suppression is discussed. Halon 1301 is discharged under nitrogen pressure, and the Halon-nitrogen mixture is a two phase, two component mixture that obeys compressible fluid laws and exhibits choking effects. A computer model was developed to analyze the discharge of Halon

and nitrogen from a storage bottle through pipes and nozzles. The model agrees well with data from Halon 1301 discharge tests. The discharge time depends mainly on nozzle area and pipe volume, for given initial conditions. Graphs were developed for estimating discharge times. A nozzle employing multiple concentric converging/diverging nozzles was developed which gave hemispherical coverage. E.A.K.

N85-15702*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

THE UH-1H HELICOPTER ICING FLIGHT TEST PROGRAM: AN OVERVIEW

R. J. SHAW and G. P. RICHTER 1985 26 p refs Presented at the 23rd Aerospace Sci. Meeting, Reno, Nevada, 14-17 Jan. 1985; sponsored by AIAA, 14-17 Jan. 1985

(NASA-TM-86925; E-2421; NAS 1.15:86925; AIAA-85-0338) Avail: NTIS HC A03/MF A01 CSCL 01C

An ongoing joint NASA/Army program to study the effects of ice accretion on unprotected helicopter rotor aerodynamic performance is discussed. This program integrates flight testing, wind tunnel testing, and analytical modeling. Results are discussed for helicopter flight testing in the Canadian NRC hover spray rig facility to measure rotor aero performance degradation and document rotor ice accretion characteristics. The results of dry wind tunnel testing of airfoil sections with artificial ice accretions and predictions of rotor performance degradation using available rotor performance codes and the wind tunnel data are presented. An alternative approach to conducting future helicopter icing flight programs is discussed.

N85-15703# Imperial Coll. of Science and Technology, London (England). Dept. of Aeronautics.

PROCEEDINGS OF THE INTERNATIONAL CONFERENCE AND EXPOSITION ON STRUCTURAL IMPACT AND CRASHWORTHINESS Final Report

G. A. O. DAVIES and J. MORTON 26 Oct. 1984 15 p Proc. held in London, 16-20 Jul. 1984 Sponsored in part by Army (Contract AF-AFOSR-0329-83)

(AD-A147845; EOARD-TR-85-03) Avail: NTIS HC A02/MF A01 CSCL 20K

This report summarizes the main keynote papers and conference papers for the International Conference on Structural Impact and Crashworthiness, held at Imperial College of Science & Technology, London, U.K. Attendees had different interests in high and low velocity impact, low velocity crashworthiness of aircraft, trains, ships and helicopters, and high speed ballistic perforation. Most of the papers concerned metal impact in which plasticity and gross deformations control the energy absorbing process. There was one day devoted to composites (mostly glass and carbon/graphite) where energy absorption is guite different. Several full-scale tests were reported and filmed, including two U.K. crash tests reported for the first time in public: a nuclear fuel cell impacted at 100 mph by a complete train, and a drop test with a Lynx Helicopter. The Pending Boeing 720 crash test was reviewed. The growing reliability of numerical programs for predicting crash response was evident, but there is still a long way to go before computational programs become a design tool. It was clear that both in Europe and the U.S.A. the reliable use of finite element/finite difference codes for simulating crash cases is an urgent need, with an experimental validation used once only. GRA

N85-16840# Federal Aviation Administration, Atlantic City, N.J. PRELIMINARY EVALUATION OF AN IMPROVED FLAMMABILITY TEST METHOD FOR AIRCRAFT MATERIALS Final Report

C. P. SARKOS, R. A. FILIPCZAK, and A. ABRAMOWITZ Dec. 1984 48 p refs

(FAA-CT-84-22) Avail: NTIS HC A03/MF A01

Small-scale flammability test methods were evaluated by comparing data obtained on a series of interior honeycomb panels with fire test results obtained with a 1/4-scale cabin model. Generally, the vertical Bunsen burner, limiting oxygen index, and radiant panel test methods ranked the phenolic-faced panels higher (better performance) than the epoxy-faced panels. It appears as if these test methods, which employ relatively moderate exposure conditions, are reflecting the superior ignition resistance of the phenolics over the epoxies. Thus, these tests cannot predict the performance of materials that exhibit high burning rates when subjected to heating conditions above their ignition threshold. The heating conditions used in the Ohio State University (OSU) apparatus, however, can be set at higher levels. At 5 watts/sq cm, rank ordering materials based on peak heat release rate measured via oxygen depletion in the OSU apparatus agreed with materials ranking in the 1/4-scale model. The OSU apparatus operated at these conditions and employing oxygen depletion calorimetry is the recommended improved fire test method for interior panels. Author

N85-16842# Naval Air Development Center, Warminster, Pa. Aircraft and Crew Systems Technology Directorate.

S-3A BALLAST BLOCK FINAL DESIGN AND ENGINEERING **TESTS Final Report**

D. LORCH and J. QUARTUCCIO 22 Feb. 1984 50 p

(AD-A147685; NADC-84015-60) Avail: NTIS HC A03/MF A01 CSCL 01C

The S-3A aircraft has four ejection seats. Both the pilot and copilot have comand eject selector levers which allow them the option to eject all crewmembers or self eject. If one of the aft seats is unoccupied, and command eject is selected, the unoccupied seat will accelerate ahead of the occupied seat next to it. Two hazards exist: (1) the crewmember next to the unoccupied seat could be burned by the rocket plume from the empty seat which has a higher acceleration; (2) the empty seat could tumble into one of the other seats because the center of gravity and the center of rocket thrust are too far apart. To eliminate these hazards it is necessary to ballast the unoccupied seat. This is presently being done with anthropomorphic test dummies, if they can be obtained. Unfortunately these dummies have various weights and are usually damaged. There is no guarantee that the center of gravity is in the proper location to prevent tumbling. To correct this potentially dangerous situation the naval air systems command tasked the naval air development center to design a ballast block. After the initial prototype was developed and tested, references (1) and (2) recommended changes to be incorporated into the final design. All of these recommendations have been incorporated into the final design. The S-3A ballast block is a 169 pound assembly of four interlocking aluminum blocks. It is used to control the trajectory of an unoccupied 1E-1 ejection seat. Tests indicate that it meets all functional and structural requirements for use in the S-3A aircraft. GRA

N85-16844# Aerospace Medical Research Labs., Wright-Patterson AFB, Ohio. Biomedical Protection Branch. IMPACT TESTS OF AUTOMATIC LAP BELT CONFIGURATIONS Final Report, 10 Oct. 1981 - Jul. 1984

J. W. BRINKLEY and D. E. SCHIMMEL 2 Jul. 1984 104 p (Contract AF PROJ. 7231)

(AD-A148034; AFAMRL-TR-84-041) Avail: NTIS HC A06/MF A01 CSCL 06K

Sixteen impact tests of lap belt assemblies were performed to evaluate components for the HBU-X lap belt (now designated the HBU-12 lap belt). The lap belt assemblies were tested as part of a lap belt and shoulder harness configuration. Fifteen tests were conducted at a level of 40 G (mean = 40.2 G, S.D. = 0.898) with an average impact velocity of 105.7 ft/sec (S.D. 0.976), The impact vector was applied in the -G(sub x) direction. The primary purpose of the tests was to evaluate the effectiveness of two different types of webbing adjusters. The influence of nylon, polyester, and latex-impregnated polyester was also studied. The results of the impact tests and several modes of failure including belt slippage through the adjusters and fractures of the metal attachment link of the MB-6 shoulder harness are described. Revision of design and test conditions are recommended. GRA

N85-16845# Ketron, Inc., Warminister, Pa.

A GENERALIZED ESCAPE SYSTEM SIMULATION (GESS) COMPUTER PROGRAM. VOLUME 2: GESS PROGRAMMER'S **MANUAL, VERSION 2 Final Report**

L. A. DAULERIO (Naval Air Development Center, Warminster, Pa.) and D. A. FENDER Apr. 1984 349 p (Contract N62269-81-C-0206; NR PROJ. 630-194)

(AD-A148363; NADC-84068-60) Avail: NTIS HC A15/MF A01 CSCL 09B

The Generalized Escape System Simulation (GESS) program is a computerized mathematical model for dynamically simulating the performance of existing or developmental aircraft ejection seat systems. The program generates six-dimensional trajectory predictions of the aircraft, seat/occupant, occupant alone, and seat alone by calculating the forces and moments imposed on these elements by the seat catapults, rails, rockets, stabilization, and recovery systems included in most escape systems configurations. User options are provided to simulate the performance of all conventional escape system designs under most environmental conditions and aircraft attitudes or trajectories. This Gess Programmer's Manual, summarizes program conventions, lists the annotated FORTRAN IV program code, and represents the second of two volumes of GESS documentation. GRA

N85-16846# Civil Aeronautics Board, Washington, D.C. AIRPORT ACTIVITY STATISTICS OF CERTIFICATED ROUTE AIR CARRIERS Annual Report, period ending 31 Dec. 1983 31 Dec. 1983 365 p

(AD-A148472) Avail: NTIS HC A16/MF A01; also available SOD HC \$14.00 CSCL 01E

This report furnishes airport activity of the Certificated Route Air Carriers. Included in the data contained in Table 6 are passenger enplanements, tons of enplaned freight, express, and mail. Both scheduled and non-scheduled service, and domestic and international operations are included. These data are shown by aircraft and carrier. Table 7 includes departures by airport, carrier and type of operation, and type of aircraft. Author (GRA)

N85-16847# Army Concepts Analysis Agency, Bethesda, Md. UTILIZATION OF INCREASED AIRLIFT CAPABILITY (UIAC) STUDY Study Report, Apr. - Sep. 1984

J. A. SORENSON and J. DEPALMA Sep. 1984 272 p (AD-A148669; CAA-SR-84-29) Avail: NTIS HC A12/MF A01 CSCL 15E

This study examined the increases in peacetime airlift capacity due to the Military Airlift Command's fleet expansion, determined the impacts on the Army transportation system and developed a process to select the most suitable cargo and route combinations to use the additional capacity. The results of analysis indicated that transportation cost avoidances could be realized by diverting surface port-packed cargoes to airlift; however by increasing airlift resupply, potential cost savings could increase. Author (GRA)

N85-16848# Bundesanstalt fuer Flugsicherung, Frankfurt am Main (West Germany). Buero des Nachrichten fuer Luftfahrer. DIRECTIONS OF THE WEST GERMAN MINISTRY OF TRANSPORT FOR EDUCATION AND CONTROL OF AIRLINE PERSONNEL (SECTION 3, CHAPTERS 2 AND 12) [RICHTLINIEN DES BUNDESMINISTERS FUER VERKEHR FUER DIF AUSBILDUNG UND PRUEFUNG DES LUFTFAHRTPERSONALS, TEIL 2, KAPITEL 2 UND 12]

Mar. 1983 75 p In GERMAN

Avail: NTIS HC A04/MF A01

The education curriculum of second class pilots is described. It consists of a theoretical part and a pratical part. The subjects are: air regulation and laws, air traffic and safety, navigation, weather forecasts, engineering, and reactions in special situations. Author (ESA) **-N85-16849#** Bundesanstalt fuer Flugsicherung, Frankfurt am Main (West Germany). Buero der Nachrichten fuer Luftfahrer.

DIRECTIONS OF THE WEST GERMAN MINISTRY OF TRANSPORT FOR EDUCATION AND CONTROL OR AIRLINE PERSONNEL, REPORT 6; CHAPTERS 3/A AND 3/B [VERKEHRSFLUGZEUGFUEHRER, DIE DIE ERLAUBNIS FUER BUNDESMINISTERS FUER VERKEHR FUER DIE AUSBILDUNG UND PRUEFUNG DES LUFTFAHRTPERSONALS, HEFT 6; KAPITEL 3A UND 3/B]

Apr. 1984 212 p In GERMAN

Avail: NTIS HC A10/MF A01

The education curriculum of commercial aircraft captains is described. It consists of a theoretical part and a practical part. The subjects are: air regulations and laws, air traffic and safety, navigation, weather forecasts, engineering, and reactions in special situations. Author (ESA)

04

AIRCRAFT COMMUNICATIONS AND NAVIGATION

Includes digital and voice communication with aircraft; air navigation systems (satellite and ground based); and air traffic control.

A85-19183

SPEECH RECOGNITION MAKING PROGRESS - DIRECT VOICE INPUT IS A PROMISING INFANT

C. BULLOCH Interavia (ISSN 0020-5168), vol. 39, Dec. 1984, p. 1319-1321.

The potentialities of existing Direct Voice Input (DVI) speech recognition equipment on the airliner flight deck is investigated. RAE trials, based on analysis of the Marconi SR-128 speech recognizer and made with a variety of microphones, indicate that boom-type microphones scored best, oxygen-mask mikes next, and throat microphones came third. One of the jobs for RAE's speech recognizer is to select COM/NAV radio frequencies, a job which requires recognition of connected rather than isolated words. Since the Marconi system is user-dependent, a scatter of error rates between different individual pilots is a result of the RAE trials. The US Air Force Advanced Fighter Technology Integration program is discussed and in it the DVI units are programmed to recognize only numbers after enunciation of a command keyword such as frequency. A speech or voice interaction system involving speech recognition and speech synthesis techniques, used for both DVI confirmation and for providing warnings is being employed in the next phase of the AFTI program. DVI is being investigated for possible uses involving human interfacing with computer-based systems, CAD/CAM, and word processing as some of the nearer-term objectives. M.D.

A85-19275

NEW GENERATION MILITARY TACTICAL AIRBORNE COMMUNICATIONS SYSTEMS - THE INTEROPERABILITY CHALLENGE

R. C. SMITH (Rockwell International Corp., Collins Avionics Div., Cedar Rapids, IA) Defense Systems Review and Military Communications, vol. 2, Nov. 1984, p. 56-60.

The modern air battlefield is populated by a sophisticated assortment of enemy electronic jammers, direction finders, decoys, and weapon systems dedicated to the disruption or exploitation of airborne communications. These systems are collectively of sufficient disruptive power to render the standoff range 'smart' weapons of the F-14 impotent, and further threaten the destruction of the F-14 itself by homing on its communications emissions. A revolutionary response to these enemy capabilities is the Joint Tactical Information Distribution System (JTIDS), which provides secure, antijam, high data throughput command and control communications. The Global Positioning System will furnish user-passive, high precision dimensional position and time readings on a worldwide basis. TDMA and Distributed TDMA are both applicable to JTIDS. O.C.

A85-19620#

ATMOSPHERIC PROPAGATION LOSSES FOR LONG-RANGE AIRBORNE RADAR SYSTEMS ANALYSIS

C. J. PRUSZYNSKI (General Dynamics Corp., Fort Worth, TX) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs (AIAA PAPER 85-0267)

In determining the performance of very long range airborne radar systems, it is incumbent upon the radar systems analyst to take accurate account of atmospheric propagation losses. A simple model for predicting clear-air atmospheric attenuation in the microwave region (.1 to 35 GHz), based on the LOWTRAN atmospheric data base, is described and used to investigate the atmospheric propagation loss effects in several scenarios of interest. The results are then applied to the problem of selection of an optimal operating frequency for a hypothetical airborne radar system. Author

A85-19805

AVIATION RADAR [AVIATSIONNAIA RADIOLOKATSIIA]

P. S. DAVYDOV, A. A. SOSNOVSKII, and I. A. KHAIMOVICH Moscow, Izdatel'stvo Transport, 1984, 224 p. In Russian. refs

This handbook presents information concerning the design and characteristics of radar systems in civil aviation. Typical components of radar systems are examined, including antennas, transmitters, receivers, and digital processing devices. Attention is given to the parameters of ATC scanning radars, landing-system radars, and various airborne radar systems (meteorological, Doppler, and transponder). Also considered are the operational characteristics of radar systems, methods of failure diagnostics, and the organization of technical-support systems. B.J.

A85-20221

MILITARY AVIONICS - INCREASING INTEGRATION AT ALL LEVELS

G. WARWICK Flight International (ISSN 0015-3710), vol. 126, Dec. 15, 1984, p. 1635-1638, 1640, 1641.

Attention is given to the design features, performance capabilities and operational consequences of state-of-the-art military avionics systems that are being incorporated into such aircraft as the F-15E dual role fighter, the Tornado F.2, and the A-10. Representative of integrated avionics are the F-15's Joint Tactical Information Distribution System, which is a jam-resistant, high capacity voice and data link, the Navstar Global Positioning System, which establishes user position to within 15 m in three dimensions and user velocity to within 0.1 m/sec, voice-control systems for fighter cockpits, ring laser gyro inertial reference systems, and wide angle holographic head-up displays, which can also function as night vision aids. O.C.

A85-21459#

HARDWARE DESIGN TECHNIQUES

A. BARLOW (Smith Industries, PLC, London, England) IN: Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 . London, Royal Aeronautical Society, 1984, 9 p.

The physical design of avionics hardware and installation structures for civil and military aircraft is discussed in a historical review of the UK and U.S. development since the 1940s. Consideration is given to vibration problems in aircraft with reciprocating engines and/or guns, the vibration sensitivity of tube and solid-state components, the various standardized connection and rack systems, thermal-management integration, and the potential EMI problems posed by the increasing use of composite materials in military-aircraft structures. Photographs, drawings, and diagrams of typical installations are shown. T.K.

04 AIRCRAFT COMMUNICATIONS AND NAVIGATION

A85-21461# INTEGRATED NAVIGATION

R. N. PRIESTLEY (Ferranti, PLC, Cheadle, Ches., England) IN: Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3. 4, 1984 . London, Royal Aeronautical Society, 1984, 4 p. refs.

The integration of avionics navigation subsystems is projected to enhance accuracy, as well as redundancy, fault tolerance, and data display efficiency. The testing and maintenance of an integrated system may be easier if full use is made of self-checking and self-calibration capabilities that inhere in such systems. In conditions where subsystem performance has decayed, however, great difficulties may arise in the isolation of the subsystem. Integration is noted to make possible modes of operation which would be impossible to implement through independent subsystems, as in the rapid, at-sea and in-air alignment of an inertial navigation system. O.C.

A85-21462#

INTEGRATED COMMUNICATIONS - A DESIGNERS VIEW

W. E. BRIERLEY (Marconi Avionics, Ltd., Airadio Products Div., Basildon, Essex, England) IN: Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 . London, Royal Aeronautical Society, 1984, 7 p.

An integrated aircraft communications system should ensure high confidence levels for all phases of a task or mission, allow effective operation at the lowest possible crew workload, and be cost-effective with respect to equipment size, weight, power demand, reliability and maintainability. It is noted that while the technology for control and display system integration is available, the techniques required in common communication signal processing remain to be developed. Attention is given to the unique integration problems encountered in the man/machine interface of control and display systems, the acquisition and/or transmission of communication intelligence, and signal processing. O.C.

A85-21838#

NONLINEAR SIMULATION OF FLIGHT ALONG WIND COMPENSATING CURVED GLIDEPATHS

A. B. MARKOV (Defence Research Establishment Suffield, Ralston, Alberta, Canada) and L. D. REID (Toronto, University, Toronto, Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. Canada) 1985, p. 97, 98. refs

A technique for defining curved glidepath geometries that compensate for some of the undesirable effects of low altitude winds is described. This technique uses an a priori estimate of the wind conditions present at the time of the landing approach to define a suitable glidepath geometry. The results of closed-loop, six degree-of-freedom simulation of a two-engined STOL transport conducting landing approaches on such curved approaches are summarized, and a number of recommendations for future work are made. Author

N85-15706*# Research Triangle Inst., Research Triangle Park, N.C. Center for Systems Engineering.

EFFECTS OF AIRCRAFT AND FLIGHT PARAMETERS ON ENERGY-EFFICIENT PROFILE DESCENTS IN TIME-BASED **METERED TRAFFIC**

F. R. DEJARNETTE Nov. 1984 19 p refs (Contract NAS1-17023) (NASA-CR-172338-ADD; NAS 1.26:172338-ADD; RTI/2467)

Avail: NTIS HC A02/MF A01 CSCL 17G

The influence of several parameters on the time required to fly a nominal profile descent of a B-737 from an entry fix to a metering fix 75 n.mi. away was studied. The ground distance for the constant speed segment was adjusted in each case so that the aircraft would always arrive at the metering fix position at the completion of the five segments of the profile descent. The influence of eight parameters on the same nominal profile descent is outlined, but the method used for the off nominal cases was changed. The time calculated for the constant speed segment in the nominal case is used for all off nominal cases. This method

allows the aircraft to arrive at the metering fix before or after the profile descent is complete. It is shown that descent Mach number and wind speed have a large effect on the time error, whereas weight was a much smaller effect. E.A.K.

N85-15707# Engineering and Economics Research, Inc., Vienna, Va

NATIONAL AIRSPACE REVIEW: AIRPORT RADAR SERVICE AREA OPERATIONAL CONFIRMATION REPORT Final Report, Aug. 1983 - Oct. 1984

V. BHARTIYA, R. LEASURE, P. LU, M. J. ROLLS, and P. V. TAWARI Washington FAA Oct. 1984 201 p (Contract DTFA01-82-Y-30562)

(DOT/FAA/AT-84/2; AD-A150008) Avail: NTIS HC A10/MF A01

The airport radar service area (ARSA), a new concept in terminal airspace design and services to standarize the designation of controlled airspace services, rules, and procedures within which terminal radar traffic control is provided was confirmed. The operational confirmation assessed the accepability of the ARSA concept at two lead sites, Port Columbus International Airport, Columbus, Ohio, and Robert Muller Municipal Airport, Austin, Texas. The operational confirmation analysis of ARSA to determine its acceptance by users is presented. Data collection and analysis was geared towards two specific types: (1) opinion survey of local pilots, controller/staff, and supervisor/management at each of the facilities; and (2) lead site traffic activity profiles. It is concluded that ARSA is confirmed at Columbus, Ohio and Austin, Texas.

E.A.K.

N85-15709# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Brunswick (West Germany). Abt. Traegheitsortung und Navigation.

FLIGHT TESTING OF LITTON LASER GYRO STRAPDOWN SYSTEM LTN-90 FOR GENERAL AVIATION

H. J. HOTOP Jul. 1984 43 p refs in GERMAN; ENGLISH summary Translation is in process as (ESA-TT-904)

(DFVLR-MITT-84-16) Avail: NTIS HC A03/MF A01; DFVLR, Cologne DM 17

The instruments and data evaluation used for flight testing of

two Litton laser gyro strapdown navigation systems in a DO-28 aircraft are described. The reference data based on the platform navigation system CAROUSEL 4a are corrected by application of optimal smoothing techniques. Results of the LTN-90 flight tests are presented and graphs of one of the flight tests are discussed. Author (ESA)

N85-16802# Department of National Defence, Ottawa (Ontario). INTEGRATED DEVELOPMENT HELICOPTER OF A NAVIGATION SYSTEM

D. F. LIANG, W. R. CLUBINE, L. C. VALLOT (Honeywell Systems and Research Center, Minneapolis, Minn.), and J. K. MAHESH (Honeywell Systems and Research Center, Minneapolis, Minn.) In AGARD Helicopter Guidance and Control Systems for Battlefield Support 19 p Aug. 1984 refs

Avail: NTIS HC A13/MF A01

The Canadian Department of National Defence has initiated a project to develop and test a helicopter integrated navigation system (HINS) that is capable of satisfying all the operational requirements of shipborne, antisubmarine warfare helicopters. The HINS mission requirements, development plan and its basic hardware and software configurations are discussed. The integrated system is expected to bring forth vital benefits in mission reliability, operational efficiency and navigation accuracy. Additional benefits are in terms of the size, weight, height and cost, etc. In the current phase of this work, extensive simulation software packages have been generated to accurately represent the operational characteristics of various off-the-shelf candidate subsystems. An Integrated System Evaluation Program has been developed which takes into account the various characteristics of the navigation subsystems and the mission requirements to systematically evaluate a sequence of candidate configurations. . B.W.

N85-16804# Naval Air Development Center, Warminster, Pa. STANDARD ATTITUDE HEADING REFERENCE SYSTEM (SAHRS) FULL SCALE DEVELOPMENT PROGRAM

K. L. BACHMAN *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 12 p Aug. 1984 refs Avail: NTIS HC A13/MF A01

There is a recognized need within the military services for reliable, low cost-of-ownership Attitude Heading Reference Systems (AHRS) capable of operating for extended periods without the need for calibration or regularly scheduled maintenance. In recognition of this need, the military services have embarked upon a joint service full scale engineering development program to provide a Standard Attitude Heading Reference System (SAHRS) utilizing strapdown technology for a multiplicity of rotary and fixed wing platforms. System design concepts, and performance characteristics are described. Procurement and schedules are also discussed. B.W.

N85-16851# Committee on Commerce, Science, and Transportation (U. S. Senate). SATELLITE NAVIGATION

Washington GPO 1984 58 p Hearing on S. Con. Res. 69 before the Subcomm. on Aviation of the Comm. on Com., Sci. and Transportation, 98th Congr., 2d Sess., 23 May 1984

(S-HRG-98-856; GPO-35-977) Avail: Subcommittee on Aviation Legislation is discussed which proposes making the civilian version of the global positioning system available to domestic airlines as well as to the commercial airlines of those countries which strictly abide by the spirit and letter of the International Air Services Transit Agreement. It is recommended that user fees not be imposed for either foreign or domestic users. The need for aircraft surveillance by satellite is examined as well as the inadequancy of current technologies. A.R.H.

N85-16852# Engineering and Economics Research, Inc., Falls Church, Va.

NATIONAL AIRSPACE REVIEW ENHANCEMENT PLAN, REVISION 3

19 Dec. 1984 64 p

Avail: NTIS HC A04/MF A01

The National Airspace Review (NAR) Plan was retitled as the National Airspace Review Enhancement (NARE) Plan to reflect the expanded scope of this undertaking. The airspace allocation, procedural, and regulatory aspects of improvements scheduled under the National Airspace System (NAS) plan and the shift of program sponsorship from the Associate Administrator for Air Traffic to the Director of Management Systems are reviewed. B.G.

N85-16853# Royal Signals and Radar Establishment, Malvern (England).

AIR TRAFFIC MANAGEMENT CONCEPTS FOR THE UK IN THE 1990'S: A REVIEW OF RECENT RSRE WORK

S. N. MAGILL and G. ORD Jun. 1984 26 p refs Presented at Eurocontrol Specialist Panel on Conflict Detection and Resolution (SPACDAR), Brussels, 21-23 Sep. 1983 Sponsored by Civil Aviation Authority

(AD-A147850; RSRE-MEMO-3714; BR93171) Avail: NTIS HC A03/MF A01 CSCL 17G

Air traffic management and control in the United Kingdom in the 1990's is discussed. Metering of arriving traffic and departure management and control are considered. Author (ESA)

N85-16855# Federal Aviation Agency, Atlantic City, N.J. NATIONAL AIRSPACE REVIEW Interim Report

Jun. 1984 101 p

(AD-A147768) Avail: NTIS HC A06/MF A01 CSCL 17G

Since the summer of 1982, the Federal Aviation Administration (FAA) has been hosting task group working sessions of the National Airspace Review (NAR). The NAR is a cooperative venture by the aviation industry and government. The NAR is comprehensively reviewing current air traffic control procedures, flight regulations, and airspace for the purpose of validating the current system or identifying near-term changes which will promote greater efficiency. As a component of the National Airspace System Plan, the NAR will provide the operational framework for moving into the next generation National Airspace System (NAS). In the area of procedures, task groups have covered: terminal services, weather programs, traffic flow management, helicopter operations, separation standards and the National Flight Data System. GRA

N85-16860# Institut fuer Rundfunktechnik, Munich (West Germany).

 MEASUREMENT OF SIGNAL SEPARATION BETWEEN RADIO

 SERVICE
 AND
 AIR
 NAVIGATION
 SERVICE

 [SCHUTZABSTANDSMESSUNGEN
 ZWISCHEN

 RUNDFUNKDIENST UND FLUGNAVIGATIONSFUNK DIENST]

 E. J. MIELKE
 17 May 1982
 21 p
 refs
 In GERMAN

E. J. MIELKE 17 May 1982 21 p refs in GERMAN (IRT-TB-B-40/82) Avail: NTIS HC A02/MF A01

Interference between the frequency range for the air navigation service (108 to 112 MHz) and the VHF-FM-radio range 8, which was recently extended to 108 MHz, was studied. Pertubation of the Instrument Landing System was considered. The signal separation was measured with an aircraft ILS receiver. The required signal separation is presented as a function of the frequency distances of disturbing radio stations. Author (ESA)

05

AIRCRAFT DESIGN, TESTING AND PERFORMANCE

Includes aircraft simulation technology.

A85-19184

FROM AV-8B TO THE ASTOVL

B. SWEETMAN Interavia (ISSN 0020-5168), vol. 39, Dec. 1984, p. 1324-1327.

A runway-free future combat aircraft known as the ASTOVL (advanced short-take-off, vertical landing) and the AV-8B Harrier II which is, in operational terms, a stepping stone to ASTOVL are discussed. Although AV-8B meets its performance goals, it suffers from excessive drag at high speeds; without external stores, the AV-8B has a preducted maximum speed of 585 kn but the actual speed is in the region of 550-560 kn. The AV-8B program includes the development of a thermal imager and a multi-function display for a night-attack system which allows existing AV-8B to be used on clear nights and which is expected to increase production by 50 percent and of a radar system which requires a 10 percent thrust boost to 23,700 lbs. The AV-8 program points towards ASTOVL in two ways: through the development and use of the AV-8 across the entire spectrum of tactical roles and by generating a requirement for a new STOVL powerplant. US work on ASTOVL concepts is carried out by NASA-Ames. The program's objectives include improved stability augmentation and better flight guidance thus reducing excursions from the desired flightpath and the total reaction control system demand. M.D.

A85-19274

BOMB RACK TECHNOLOGY - KEEPING UP WITH ADVANCED WEAPONS

G. DE MOS (Western Gear Corp., Flight Structures Div., Lynwood, CA) Defense Systems Review and Military Communications, vol. 2, Nov. 1984, p. 40, 42-46.

The development and testing of a new advanced multiple stores ejection rack (MSER) are presented. MSER incorporates a dual dependent hydraulic ejection system, eliminating the effect of boundary layer reaction forces or of the store CG differentials, which is charged up from zero to 8000 psi in 70 milliseconds and ejects a 500 lb store at 20 ft/sec. A built-in-test capability provides a go/no go signal during the store loading operations and fault-isolates key circuits and a majority of the MSER components. The unit is adaptable to F-20, F-15, F-16, F-8, A-10, and AV-8B aircraft. The system is entirely modular, thereby cutting the

organizational maintenance time to under 10 min, and its ejector system requires no cleaning throughout its useful life. L.T.

A85-19457# ATMOSPHERIC ELECTRICITY HAZARDS TO AIRCRAFT OPERATION

R. C. PEAVIN, J. R. LIPPERT, and J. E. LAVOIE (USAF, Wright Aeronautical Laboratories, Wright-Patterson AFB, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p.

(AIAA PAPER 85-0013)

An advanced program for the development of effective atmospheric electricity hazards protection (AEHP) for military/transport aircraft is presented. The lightning threat parameters are defined for moderate and severe flashes (200 kA peak and 200 kA/microsecond rise rate), with particular attention to aircraft using large areas of composite materials. Protection concepts considered include circuit/system shielding, terminal protection, conducting floors, and cable protection. The demonstration testing will use modified F-14 fighter and YUH-61 helicopter airframes, with selected replacement of metal skin areas with composite and dielectric materials, together with test electronics consisting of digital processors and fiber-optics communication links, and is scheduled for May 1986. L.T.

A85-19459#

THE FEDERAL AVIATION ADMINISTRATION'S ENGINEERING AND DEVELOPMENT AIRCRAFT ICING PROGRAM

C. O. MASTERS (FAA, Technical Center, Atlantic City, NJ) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (AIAA PAPER 85-0015)

The goals and current status of the FAA Engineering and Development Aircraft Icing Program are described. Consideration is given to the identification of meteorological icing characteristics which can be used to determine flight risks for commercial fixed wing aircraft and helicopters. The development of ground deicing systems to permit certification for aircraft operating under icing conditions is also discussed. The use of computer simulations of the icing environment for certification tests is reviewed. A block diagram is provided which illustrates the organization of current FAA deicing E and D programs.

A85-19584#

MAXIMUM FINAL ENERGY CHANDELLE

I. MANSOUR (Purdue University, West Lafayette, IN; Military Technical College, Cairo, Egypt) and D. ANDRISANI, II (Purdue University, West Lafayette, IN) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs

(AIAA PAPER 85-0200)

Classical solution of the chandelle assumes exchange of kinetic and potential energies. The objective of this paper is to find an optimal load factor and bank angle control law such that the total energy of the airplane is maximized at the end of the maneuver. The maximum principle is used to find the necessary conditions of optimality. Then an ordinary gradient algorithm is used to solve this trajectory optimization problem. The obtained optimal control law is practical in the sense that it is easy for a pilot to perform. The gain in the final total energy is highly remarkable compared to the classical solution of the chandelle. The paper illustrates that the gradient algorithm is very efficient in this highly nonlinear trajectory optimization problem.

A85-19619#

THE AERODYNAMIC EFFECT OF SURFACE WETTING CHARACTERISTICS ON A LAMINAR FLOW AIRFOIL IN SIMULATED HEAVY RAIN

R. J. HANSMAN, JR. and M. F. BARSOTTI (MIT, Cambridge, MA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs (AIAA PAPER 85-0260)

Wind tunnel experiments have been conducted on a natural laminar flow airfoil in a simulated heavy rain of 440 mm/hr at a Reynolds number of 310,000 to assess the effect of surface wettability on the performance degradation due to rain. A significant loss of performance was observed for each of the three surfaces tested with the nonwettable, waxed, surface being the most degraded (75 percent reduction in maximum L/D) and the incompletely wettable epoxy gel coat being the least (45 percent reduction). Accompanying the L/D loss was an effective reduction in angle of attack of up to 2 deg resulting from a downward translation of the C(L) polar. In photographic observations, the runback water layer was found to bead on the wax surface and to sheet on the wettable surfaces. The strong dependence on surface wettability of both the airfoil performance and the water behavior indicates that the degradation due to heavy rain is primarily a result of the roughening of the airfoil surface by the runback water layer. The observed performance loss could only be partially emulated by causing premature transition from a laminar to turbulent boundary layer. Author

A85-19623#

INEXPENSIVE CALIBRATIONS FOR THE INFLUENCE FUNCTION METHOD USING THE INTERFERENCE DISTRIBUTED LOADS CODE

K. S. KEEN (Calspan Field Service, Inc., Arnold Air Force Station, TN) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 5 p. USAF-supported research. refs

(AIAA PAPER 85-0270)

Two engineering prediction methods for the calculation of store aerodynamic loads within the interference flow field of an aircraft have been integrated to produce a tool with capabilities beyond the range of either method individually. A reduction in computer cost of three-orders-of-magnitude has been realized in the theoretical determination of the influence response coefficient distributions of conventional store configurations. Additionally, nonlinear aerodynamic effects such as vortex downwash on the store afterbody were modeled. The integrated method has been incorporated into an interactive geometry modeling/input preparation system which allows a user with little or no familiarity with the related codes to derive the influence coefficient distributions with minimal effort. Predictions of store loads in an aircraft flow field using these influence coefficients have shown very good agreement with experimental data. Author

A85-19626*#

THE JOINED WING - AN OVERVIEW

J. WOLKOVITCH (ACA Industries, Inc., Torrance, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 27 p. refs (Contract NAS2-11255; NAS2-11725; N00014-79-C-0953; N00014-82-C-0607)

(AIAA PAPER 85-0274)

The joined wing is a new type of aircraft configuration which employs tandem wings arranged to form diamond shapes in plan view and front view. Wind-tunnel tests and finite-element structural analyses have shown that the joined wing provides the following advantages over a comparable wing-plus-tail system; lighter weight and higher stiffness, higher span-efficiency factor, higher trimmed maximum lift coefficient, lower wave drag, plus built-in direct lift and direct sideforce control capability. A summary is given of research performed on the joined wing. Calculated joined wing weights are correlated with geometric parameters to provide simple weight estimation methods. The results of low-speed and transonic wind-tunnel tests are summarized, and guidelines for design of joined-wing aircraft are given. Some example joined-wing designs are presented and related configurations having connected wings are reviewed. Author

A85-19627# The design and testing of several joined wing RPV's

J. N. PERKINS (North Carolina State University, Raleigh, NC), F. M. CHEATWOOD, R. J. VESS, and R. A. WAHLS American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. (AIAA PAPER 85-0275)

Attention is given to the design features and test performance results of five tip-joined wing configuration models which were subjected to wind tunnel and flight tests. The test results indicate that it is not possible to obtain all advantages claimed for joined wing configurations simultaneously. It is noted, on the basis of these results, that any future joined wing design should locate its ailerons outboard of the wingtip joining point, and that flaps should be located on the rear wing. The elevators would then be on the front wing, so that trimming movement yields increased lift for both wings. Canards should not be used for trimming purposes. It

A85-19677*# National Aeronautics and Space Administration. Flight Research Center, Edwards, Calif.

is important that there be no significant spanwise flow over the

GROUND-EFFECT ANALYSIS OF A JET TRANSPORT AIRPLANE

R. E. CURRY and A. H. BOWERS (NASA, Flight Research Center, Edwards, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(AIAA PAPER 85-0307)

front wing.

An analysis of the ground effect of a jet transport airplane has been made. Data were obtained from recent flight tests primarily using the constant angle-of-attack approach technique. Reasonable results were obtained for ground-effect pitching moment and lift increments. These were compared with data from other sources, including computations, wind tunnel, and previous flight tests. A recommended ground-effect model was developed from the results. A brief simulator study was conducted to determine the sensitivity of a particular configuration to this ground-effect model and its associated uncertainty. Author

A85-19684#

AERODYNAMIC CONFIGURED MISSILES - PROMISE AND FUTURE

R. J. KRIEGER (McDonnell Douglas Astronautics Co., St. Louis, MO) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs

(AIAA PAPER 85-0345)

The results of both the Air Force sponsored Aerodynamic Configured Missile (ACM) program, with the objective of exploiting the aerodynamic potential of supersonic cruise and maneuvering missiles, and the subsequent Low Cost Aerodynamic Configured Missile Demonstrator Program are summarized with emphasis on the impact of these studies on future missile concepts. The major uses of the programs, such as the points of departure concepts, direct prediction of aerodynamics, and evaluation of prediction techniques are discussed with regard to the use of the experimental data base. The Panair computer methods can be applied for Mach numbers up to 5. Wind tunnel testing showed significantly higher L/D ratios than for conventional circular missiles. Flight demonstrations are planned with a flight-proven ARIES solid fuel booster, including the ground launch scenario and the B52/ARIES scenario. L.T.

A85-19734*# Toledo Univ., Ohio.

FULL TWO-DIMENSIONAL TRANSIENT SOLUTIONS OF ELECTROTHERMAL AIRCRAFT BLADE DEICING

K. C. MASIULANIEC, T. G. KEITH, JR., K. J. DEWITT, and K. L. LEFFEL (Toledo, University, Toledo, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. NASA-supported research. refs

(AIAA PAPER 85-0413)

Two finite difference methods are presented for the analysis of transient, two-dimensional responses of an electrothermal de-icer pad of an aircraft wing or blade with attached variable ice layer thickness. Both models employ a Crank-Nicholson iterative scheme, and use an enthalpy formulation to handle the phase change in the ice layer. The first technique makes use of a 'staircase' approach, fitting the irregular ice boundary with square computational cells. The second technique uses a body fitted coordinate transform, and maps the exact shape of the irregular boundary into a rectangular body, with uniformally square computational cells. The numerical solution takes place in the transformed plane. Initial results accounting for variable ice layer thickness are presented. Details of planned de-icing tests at NASA-Lewis, which will provide empirical verification for the above two methods, are also presented. Author

A85-19739*# General Dynamics Corp., San Diego, Calif. NUMERICAL OPTIMIZATION DESIGN OF ADVANCED TRANSONIC WING CONFIGURATIONS

G. B. COSENTINO (General Dynamics Corp., Convair Div., San Diego, CA; Colorado, University, Boulder, CO) and T. L. HOLST (NASA, Ames Research Center, Applied Computational Aerodynamics Branch, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 15 p. Previously announced in STAR as N84-27718. refs

(AIAA PAPER 85-0424)

O.C.

A computationally efficient and versatile technique for use in the design of advanced transonic wing configurations has been developed. A reliable and fast transonic wing flow-field analysis program, TWING, has been coupled with a modified quasi-Newton method, unconstrained optimization algorithm, QNMDIF, to create a new design tool. Fully three-dimensional wing designs utilizing both specified wing pressure disributions and drag-to-lift ratio minimization as design objectives are demonstrated. Because of the high computational efficiency of each of the components of the design code, in particular the vectorization of TWING and the high speed of the Cray X-MP vector computer, the computer time required for a typical wing design is reduced by approximately an order of magnitude over previous methods. In the results presented here, this computed wave drag has been used as the quantity to be optimized (minimized) with great success, yielding wing designs with nearly shock-free (zero wave drag) pressure distributions and very reasonable wing section shapes. B.W.

A85-19741*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

POTENTIAL FLOW CALCULATIONS AND PRELIMINARY WING DESIGN IN SUPPORT OF AN NLF VARIABLE SWEEP TRANSITION FLIGHT EXPERIMENT

E. G. WAGGONER, P. S. PHILLIPS (NASA, Langley Research Center, Hampton, VA), J. K. VIKEN (Mandex, Inc., Falls Church, VA), and W. H. DAVIS (Grumman Aerospace Corp., Bethpage, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs

(AIAA PAPER 85-0426)

NASA Langley and NASA Ames-Dryden have defined a variable-sweep transition-flight experiment utilizing the F-14 aircraft to enhance understanding of the interaction of crossflow and Tollmien-Schlichting instabilities on a laminar-boundary-layer transition. The F-14 wing outer panel will be modified to generate favorable pressure gradients on the upper wing surface over a wide range of flight conditions. Extensive computations have been

performed using two-dimensional and three-dimensional transonic analysis codes. Flight-test and computational data are compared and shown to validate the applicability of the three-dimensional codes (WBPPW and TAWFIVE). In addition, results from two preliminary glove designs derived from two different approaches to the design problem are presented. Advantages and disadvantages of each approach are identified, and it is concluded that coupling an analysis code with an automated design procedure vields a powerful code with distinct advantages over a 'cut-and-dry' approach. Author

National Aeronautics and Space Administration. A85-19758*# Ames Research Center, Moffett Field, Calif.

ARRAYS FOR MINIMUM WAVE DRAG OF BODIES OF REVOLUTION

J. N. NIELSEN (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. (AIAA PAPER 85-0449)

The wave drag of two identical Sears-Haack bodies at transonic and supersonic speeds has been determined by using the supersonic area rule. The solution is found for these bodies displaced parallel to each other, both laterally and longitudinally. The results show that the drag of a pair of bodies can be either doubled, or nearly halved, depending upon the lateral and longitudinal spacings of the bodies. The magnitude of this drag is determined by the degree of mutual interference between the bodies. It is shown how reductions in wave drag can be obtained by proper spacing of external bodies. The regions of favorable mutual interference are delineated. It is also shown how to apply the two-body results to many-body arrays. Some remarks are made on applying the results to store-airframe interference and on further aspects of the store-airframe drag problem. Author

A85-19789#

INFLUENCE OF **PROPULSION/MISSION** PROFILE COMBINATIONS UPON GENERIC MISSILE PENETRATION OF A HYPOTHETICAL DEFENSE

M. M. BRIGGS and V. H. L. CHENG (Integrated Systems, Inc., Palo Alto, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs (AIAA PAPER 85-0495)

In the present standoff range guided missile design tradeoff study, the ability to penetrate enemy defenses is introduced as a measure-of-merit in the selection of missile airbreathing propulsion schemes. These propulsion schemes are associated with sets of mission profiles compatible with payload requirements and gross weight constraints, so that a unique mission profile may be identified which uses all available propellant in reaching the target while undertaking minimum exposure to enemy defenses. The three propulsion system types considered were an air-turboramiet. an integral rocket/ramjet, and an unaugmented turbojet. Simulations of the penetration mission were conducted in Monte Carlo fashion to determine average survival probabilities for the missiles. The air-turboramjet propulsion scheme yielded the highest survival rate, due to its high speed and cruise altitude. O.C.

A85-19790#

INTERACTIVE DESIGN TECHNIQUE FOR ARBITRARY SHAPED. AIRBREATHING MISSILE CONFIGURATIONS

R. J. KRIEGER (McDonnell Douglas Astronautics Co., St. Louis, MO) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p.

(AIAA PAPER 85-0496)

A computer-aided design procedure is described for use in conceptual design for sizing and shaping supersonic non-circular missiles with turbolet or ramlet propulsion systems. The theoretical basis for the method which uses a sensitivity derivative approach is developed. Avionics, structures, payload, inlet, engine, fuel, aerodynamic and performance models are described. Inlet/engine sizing, external moldline shaping and interactive graphics design

processes are presented. The synthesis procedure overcomes many of the major drawbacks of airbreathing missile synthesis. It has features such as: simple initial geometry setup for body, wings, tails and inlets; modeling of completely arbitrary missile shapes; non-circular subsystem packaging; non-circular and multiple inlet modeling; aerodynamic and performance shaping; low cost, short duration computer sessions; rapid convergence; and accurate aerodynamic predictions. Two example configuration shapings are provided to depict the sizing process. Author

A85-19836

FOR **EXPERIMENTAL** METHODS WIND-TUNNEL FLIGHT-MECHANICS INVESTIGATIONS USING DYNAMICALLY AIRCRAFT MODELS [BEITRAEGE SIMILAR ZUR VERSUCHSMETHODIK **FLUGMECHANISCHE** FUER UNTERSUCHUNGEN MIT DYNAMISCH **AEHNLICHEN** FLUGZEUGMODELLEN IM WINDKANAL]

H. SUBKE Braunschweig, Technische Universitaet, Fakultaet fuer Maschinenbau und Elektrotechnik, Dr.-Ing. Dissertation, 1984, 144 p. In German. refs

The aerodynamic response of lightweight а advanced-technology-wing aircraft based on the Do-28 is investigated using a computer simulation and a fixed dynamically scaled CFRP 1:8 wind-tunnel model with active control surfaces. The principles of wind-tunnel simulation are reviewed; the governing equations of a fixed model are derived; a model is constructed; and preliminary tests of the responses to elevator activation and to gusts are performed. The results are presented in graphs and tables and used to develop corrections to the dynamic derivatives of the model equations and to implement active-control systems which modify the natural dynamics of the wind-tunnel model to account for different profiles and mission requirements. Good agreement between computer and wind-tunnel results is obtained when the corrected control systems are employed. TK

A85-20058

TECHNOLOGY GAINS EXPECTED TO YIELD LHX SIZE. WEIGHT, COST REDUCTIONS

Aviation Week and Space Technology (ISSN 0005-2175), vol. 122, Jan. 14, 1985, p. 47, 49, 51, 55-57.

It is noted that technological advances in rotor design, composite structures, flight control systems, and cockpit automation, as well as their integration in helicopter configuraiations, suggest significant reductions in the size, weight, and life cycle costs of the U.S. Army's prospective family of light scout/utility/attack helicopters, designated 'LHX'. The emerging battlefield threats to be met by such rotorcraft have led to the stipulation of single pilot operation, and significant enhancement of survivability through radar, IR, visual and acoustic signature reductions. Ballistic and nuclear/biological/chemical warfare protection are also central to LHX specifications. Standoff range and multitarget engagement capabilities, and air-to-air defense systems, are to be incorporated. Attention is presently given to the development status of LHX flight controls, navigation aids, communications, cockpit displays, sensors, and weapons. 0.0

A85-20059

STRUCTURAL COMPONENTS, DESIGN OF TILT-ROTOR JVX NEAR COMPLETION

Aviation Week and Space Technology (ISSN 0005-2175), vol. 122, Jan. 14, 1985, p. 84-87.

The joint services vertical lift aircraft, designated 'JVX', is a twin-engine tilt-rotor vehicle that is expected to replace most of the existing medium lift helicopter fleet of U.S. military services during the 1990s. JVX will have a dash speed of 275 kt and a tactical range of 1400 nautical miles. These performance capabilities meet a variety of applications, such as combat assault for the Marine Corps, combat search and rescue for the Navy, and ground support activities for the Army. Attention is presently given to JVX nacelle and rotor tests, technological risk management, and the results of a weight management program.

A85-20142 AEROELASTIC CHARACTERISTICS OF THE AH-64 BEARINGLESS TAIL ROTOR

D. BANERJEE (Hughes Helicopters, Inc., Culver City, CA) (Integrated Technology Rotor Methodology Workshop, Moffett Field, CA, June 20, 21, 1983) Vertica (ISSN 0360-5450), vol. 8, no. 3, 1984, p. 263-287. refs

The results of a wind tunnel test program to determine the performance loads and dynamic characteristics of the Composite Flexbeam Tail Rotor (CFTR) for the AH-64 Advanced Attack Helicopter are reported. The CFTR uses an elastomeric shear attachment of the flexbeam to the hub to provide soft-inplane S-mode and stiff-inplane C-mode configuration. The properties of the elastomer were selected for proper frequency placement and scale damping of the inplane S-mode. Kinematic pitch-lag coupling was introduced to provide the first cyclic inplane C-mode damping at high collective pitch. The CFTR was tested in a wind tunnel over the full sideslip envelope of the AH-64. It is found that the rotor was aeroelastically stable throughout the complete collective pitch range and up to rotor speeds of 1403 rpm. The dynamic characteristics of the rotor were found to be satisfactory at all pitch angles and rotor speeds of the tunnel tests. The unique design characteristics of the rotor which permit the high performance characteristics are discussed. Several schematic drawings and photographs of the rotor are provided. LH.

A85-20146

FORWARD SWEEP - THE PROS AND CONS

B. R. A. BURNS (British Aerospace, PLC, Preston, Lancs., England) Interavia (ISSN 0020-5168), vol. 40, Jan. 1985, p. 39-41.

The swept-forward wing (SFW) design is analyzed as applied to modern fighter requirements, with reference to the X-29A experimental fighter. Due to lower sweep at all points forward of 70 percent chord the SFW has lower induced drag, higher lift slope, reduced pitch-up tendency, and smaller structural span, leading to reduced weight compared with equivalent SBW. An increased wave drag in the supersonic flight and more severe bending loads due to off-loading of the tips for a partially-stalled wing are noted. Maximum lift/drag ratios of the SFW and SBW are compared diagrammically for Mach numbers up to 1.6; the SFW is superior up to speeds of approximately 0.9 Mach. The comparison of fuel requirement in different missions shows a 10-percent benefit for the SFW for battlefield air-cover mission, and a 5-percent penalty for point intercept mission as compared to the SBW. L.T.

A85-20147

MI-28 - THE SOVIETS CREATE HAVOC

M. LAMBERT Interavia (ISSN 0020-5168), vol. 40, Jan. 1985, p. 44, 45.

A possible description of the Soviet Mi-28 Havoc antitank helicopter is given, and a comparison is made with the AH-64 Apache. The following estimates are given, with the corresponding AH-64 parameters in parentheses: fuel consumption of no less than 1200 lb/h (900 lb/h); two engines with take-off power of at least 1340 SHP (1688 SHP) each; combat weight 15,652 lbs (14,694 lbs) and empty weight 10,360 lbs (11,015 lbs); and hover ceiling IGE 12,000 ft (13,400 ft). The five-blade rotor, noted to improve the helicopter's low-speed performance, is of almost identical diameter as that of the AH-64, and is suggested to be an adaptation of the Mi-8 Hip rotor. The Mi-28 has direct optics, a nose-mounted 34 to 40 GHz pulse radar, and a supporting FLIR. It is armed with a millimetric-radar homing version of the AT-6 Spiral as antitank armament, a podded version of the SA-14 for air-to-air fighting, and a turret-mounted 23 mm gun. The paper concludes that the Mi-28 does not represent a significant advance on technology being used in the West, and that the Soviet Air Force appears to be adopting Western methods in antiarmor helicopters. L.T.

A85-20222

BOEING'S REJUVENATED TWIN JET

H. HOPKINS Flight International (ISSN 0015-3710), vol. 126, Dec. 29, 1984, p. 1708-1711.

The 737-300 variant of the 737 twin-engine airliner has been fitted with a 104-in fuselage stretch and 20,000-lb thrust CFM56-3B1 engines, which offer lower operating noise levels and fuel consumption. Hydraulic systems have also been substantially revised to yield greater capacity and flexibility. Attention is presently given to the flight handling characteristics of the 737-300, whose roll and yaw trim are electrically adjusted. The wing leading edge of this variant has been modified to achieve reduced cruise drag, and advanced avionics are incorporated.

A85-20469

LOADING CHARACTERISTICS OF VTOL AIRCRAFT AND THEIR EFFECT ON THE REMAINING LIFE OF THE AIRCRAFT [OSOBENNOSTI NAGRUZHENIIA SAMOLETA VERTIKAL'NOGO VZLETA I POSADKI I IKH VLIIANIE NA RASKHODOVANIE PROCHNOSTNOGO RESURSA]

V. V. NOVITSKII and V. F. PAVLENKO IN: Current problems in aviation science and technology . Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 164-172. In Russian, refs

The contributions of various types of loading to the diminution of the remaining life of VTOL aircraft are estimated. Particular attention is given to acoustic loading, vibrations, and pressure fluctuation in turbulent flow. As an example, a solution is presented to the problem of determining the life of a panel exposed to turbulent flow. V.L.

A85-20473

A FORMALISM FOR THE DESIGN PROBLEM OF AIRCRAFT SYSTEM UNIVERSALIZATION [FORMALIZATSIIA PROEKTNOI ZADACHI UNIVERSALIZATSII LETATEL'NYKH APPARATOV AVIATSIONNOI SISTEMY]

E. V. TARASOV and S. A. USTINOV IN: Current problems in aviation science and technology . Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 198-205. In Russian.

Various formulations of design problems based on a variety of universalization techniques are examined. A mathematical model for aircraft systems allowing for universalization on the basis of the building-block approach is proposed. A solution is presented to the problem of finding an optimal configuration for a hypothetic system of modular aircraft using basic modules of specified configurations. V.L.

A85-20875# STOL TECHNOLOGY FOR CONVENTIONAL FLIGHT ENHANCEMENT

J. P. LANDFIELD (Grumman Aerospace Corp., Bethpage, NY) and C. HENDERSON (U.S. Naval Air Development Center, Warminster, PA) AIAA, AHS, and ASEE, Aircraft Design Systems and Operations Meeting, San Diego, CA, Oct. 31-Nov. 2, 1984. 12 p. refs

(Contract N62269-83-C-0227)

(AIAA PAPER 84-2397)

Previous limited-scope investigations have identified promising extensions of STOL technologies into conventional flight regimes. A study was conducted to examine the design requirements and performance impact of integrating various aero/propulsive techniques into an advanced, supersonic carrier based tactical aircraft. Comparisons of takeoff, landing, combat maneuvering, and subsonic cruise characteristics were made with a CTOL baseline aircraft. A mission sizing evaluation was performed to quantify the iterative effects of installing a selected powered-lift technology suite. These investigations reaffirm that STOL capability adds weight and complexity to a high performance CTOL aircraft. However, the careful integration of powered lift technology compensated for the historical STOL penalty by offering unique operational and tactical advantages.

5

A85-21378

K747 COMPOSITE MAIN ROTOR BLADE MODIFICATION, ANALYSIS AND QUALIFICATION FOR NEW HIGH TEMPERATURE REQUIREMENTS

C. T. GUNSALLUS and M. A. BOWES (Kaman Aerospace Corp., IN: Composite structures; Proceedings of the Bloomfield, CT) National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983 . Washington, DC, American Helicopter Society, 1984, 9 p.

The K747 Composite Main Rotor Blade used on the Army AH-1S helicopter has undergone some redesign and analysis and has been qualified for use under extreme conditions of combined solar radiation and high ambient temperature. This environment has been shown to result in static blade material temperatures, approaching 220 F for black painted blades, well in excess of the previously accepted and specified extreme of 160 F. This problem was first recognized as a result of an in-service blade failure, which involved separation of the brass tip ballast weight from the blade during ground operation. This failure, which occurred in the desert in mid-summer, was duplicated through high temperature ground-air-ground fatigue testing which revealed that the original tip ballast weight retention design was not suitable for temperatures significantly above 160 F. Author

A85-21379

DESIGN, FABRICATION AND VERIFICATION OF COMPOSITE FLEXBEAM TAIL ROTOR FOR AH-64 APACHE HELICOPTER

S. TAHA (Hughes Helicopters, Inc., Culver City, CA) and S. WIESENBERG (U.S. Army, Aviation Research and Development Command, St. Louis, MO) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983 . Washington, DC, American Helicopter Society, 1984, 9 p.

A composite flexbeam tail rotor for the AH-64 Apache has been designed, fabricated and successfully subjected to structural and wind tunnel tests. The composite flexbeam tail rotor (CFTR) concept presented herein eliminates the use of pitch bearing, mechanical fastening and reduces the requirements for highly loaded structural joints. This has been accomplished by use of tailored, directed fiber structural flexbeams and efficient bonding of pitch control component to the blade assembly. Dynamically, the CFTR concept is soft in-plane for reactionless and collective boundary conditions and stiff in-plane for the cyclic case. Author

A85-21381

SIKORSKY COMPOSITE ROTOR HUB DEVELOPMENT

P. OGLE and G. WEHNERT (United Technologies Corp., Sikorsky Aircraft Div., Stratford, CT) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983 . Washington, DC, American Helicopter Society, 1984, 8 p.

While the current production S-76 and Black Hawk helicopter main rotor hubs are combined aluminum and titanium structures with two elastomeric bearings per blade, a combined glass fiber/graphite-reinforced structure is under development which will be interchangeable with existing hubs. The concept of this damage tolerant/safe life rotor hub combines an isotropic material with unidirectional glass fiber to yield a redundant structure with essentially infinite life, and very high resistance to cross structure cracking. 0.C

A85-21383* National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

GROUND TEST EXPERIENCE WITH LARGE COMPOSITE STRUCTURES FOR COMMERCIAL TRANSPORTS

H. L. BOHON, A. J. CHAPMAN, III, and H. A. LEYBOLD (NASA, Langley Research Center, Hampton, VA) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983 . Washington, DC, American Helicopter Society, 1984, 20 p. Previously announced in STAR as N83-29732. refs

The initial ground test of each component resulted in structural failure at less than ultimate design loads. While such failures represent major program delays, the investigation and analysis of each failure revealed significant lessons for effective utilization of composites in primary structure. Foremost among these are secondary loads that produce through-the-thickness forces which may lead to serious weaknesses in an otherwise sound structural design. The sources, magnitude, and effects of secondary loads need to be thoroughly understood and accounted for by the designers of composite primary aircraft structures. Author

A85-21384

STRUCTURAL ANALYSIS AND TESTING OF ACAP SUBCOMPONENTS

H. GAEBE and H. KEARNEY (United Technologies Corp., Sikorsky Aircraft Div., Stratford, CT) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983 . Washington, DC, American Helicopter Society, 1984, 14 p.

The Advanced Composite Airframe Program (ACAP) is a proprietary effort to demonstrate successful applications of such materials and their structural design concepts in airframe primary structures and landing gear. Attention is given to the results obtained to date by analyses and tests for ACAP structural subcomponents that include the windshield center post pultrusion, the empennage structure, and the cabin roof structure of the test helicopter. O.C.

A85-21386 CRASHWORTHINESS OF HELICOPTER COMPOSITE STRUCTURES

J. D. CRONKHITE (Bell Helicopter Textron, Fort Worth, TX) and L. T. BURROWS (U.S. Army, Applied Technology Laboratory, Fort Eustis, VA) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983. Washington, DC, American Helicopter Society, 1984, 16 p. refs

Two full scale composite-structure helicopter cabin sections derived from a preliminary design for the U.S. Army's Advanced Composite Airframe Program were subjected to crash testing which simulated zero- and 20-deg roll impact attitudes at a vertical impact velocity of 30 ft/sec. Test results indicate that structural deformation was restricted to areas designed to crush and absorb energy. In addition, two computer crash simulation programs for use in the design of crashworthy structures, designated KRASH and DYCAST, have been developed. 00

A85-21387

ADVANCED COMPOSITES - DESIGNED TO SURVIVE

N. CARAVASOS and J. P. DONNELLY (Boeing Vertol Co., Philadelphia, PA) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983 . Washington, DC, American Helicopter Society, 1984, 7 p. refs

In the modern battlefield scenarios contemplated for military aircraft, the inherent mechanical properties of composite materials offer improved damage tolerance over comparable metallic structures. Careful tailoring of the material both reduces overall weight and improves damage tolerance through redundancy and the presentation of minimum vulnerable areas. Upon sustaining damage from armor-piercing or high explosive munitions, composites can be more quickly returned to service by means of simple field repairs. Attention is given to military helicopter composite airframe structures and the damage that they typically sustain when hit by various types of 12.7 and 23 mm projectiles.

O.C.

A85-21388

ENVIRONMENTAL EFFECTS AND DURABILITY EVALUATION OF ADVANCED COMPOSITE FUSELAGE STRUCTURES

N. J. CALAPODAS (U.S. Army, Applied Technology Laboratory, Fort Eustis, VA) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983 Washington, DC, American Helicopter Society, 1984, 10 p.

An OH-58A helicopter tail section which comprises the tail boom and horizontal and vertical stabilizers has been used as a representative composite primary structure in a U.S. Army Applied Technology Laboratory program for evaluating composite helicopter structure desgn, fabriation and test methods. Of the 14 composite tail sections fabricated, 11 were subjected to high temperature and/or humidity environments over a period of two years. Three different reinforcing fibers were evaluated: graphite, kevlar, and

glass. Semiannual inspections have revealed no mechanical property degradation. O.C.

A85-21396* Sikorsky Aircraft, Stratford, Conn. COMPOSITE CURVED FRAMES FOR HELICOPTER FUSELAGE STRUCTURE

M. J. RICH and D. W. LOWRY (United Technologies Corp., Sikorsky Aircraft Div., Stratford, CT) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983 . Washington, DC, American Helicopter Society, 1984, 6 p. Army-supported research.

(Contract NAS1-16826)

This paper presents the results of analysis and testing of composite curved frames. A major frame was selected from the UH-60 Black Hawk helicopter and designed as a composite structure. The curved beam effects were expected to increase flange axial stresses and induce transverse bending. A NASTRAN finite element analysis was conducted and the results were used in the design of composite curved frame specimens. Three specimens were fabricated and five static tests were conducted. The NASTRAN analysis and test results are compared for axial, transverse, and Web strains. Results show the curved beam effects are closely predicted by a NASTRAN analysis and the effects increase with loading on the composite frames.

A85-21397

THE ALL-COMPOSITE AIRFRAMES

R. L. FOYE (U.S. Naval Postgraduate School, Monterey, CA) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983 . Washington, DC, American Helicopter Society, 1984, 9 p.

Although the concept of an all-composite airframe is over 60 years old an aerospace grade of composite material, clearly superior to aluminum, has only been available in commercial quantity for about 17 years. Since then (and even before that) there have been several serious efforts to build all-composite airframes. Discounting the gliders and home builts, there have been at least 24 different all-composite airframes built and flown in the last 25 years by established airframe fabricators. Some of these like the Lear Avia 2100, Windecker Eagle, and NASA AD-1 have received considerable publicity. Others have not. This paper reviews each of the all-composite designs that have flown. Most of them have been light airframes within the private aviation sector. There are also a number of recent European powered glider designs.

A85-21467#

THE IMPACT OF INTEGRATED SYSTEMS - THE HELICOPTER DESIGNER'S VIEWPOINT

S. D. ROY (Westland Helicopters, Ltd., Yeovil, Somerset, England) IN: Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 . London, Royal Aeronautical Society, 1984, 6 p.

An assessment is made of the benefits of avionics system integration in the case of helicopters. The systems under consideration are noted to be highly software-intensive, and require extensive validation testing in order to ascertain any unwanted interactions between the components and functions thus integrated. It is noted that generic integrating architectures are also required to provide a basis for subsequent hardware- and application-related innovations. O.C.

A85-21844*# Texas A&M Univ., College Station. EXPERIMENTAL AERODYNAMIC CHARACTERISTICS OF AN NACA 0012 AIRFOIL WITH SIMULATED ICE

K. D. KORKAN, E. J. CROSS, JR., and C. C. CORNELL (Texas A&M University, College Station, TX) Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. 1985, p. 130-134. Previously cited in issue 06, p. 719, Accession no. A84-17937. refs (Contract NAG3-242) A85-21847*# California Univ., Los Angeles.

COUPLED HELICOPTER ROTOR/BODY AEROMECHANICAL STABILITY COMPARISON OF THEORETICAL AND EXPERIMENTAL RESULTS

P. P. FRIEDMANN and C. VENKATESAN (California, University, Los Angeles, CA) Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. 1985, p. 148-155. refs (Contract NAG2-116)

This paper presents the results of an analytical study aimed at predicting the aeromechanical stability of a helicopter in ground resonance, with the inclusions of aerodynamic forces. The theoretical results are found to be in good agreement with the

experimental results, available in the literature, indicating that the coupled rotor/fuselage system can be represented by a reasonably simple mathmatical model. Author

A85-22005

OPTIMIZATION OF AIRPLANE WING STRUCTURES UNDER LANDING LOADS

S. S. RAO (San Diego State University, San Diego, CA) Computers and Structures (ISSN 0045-7949), vol. 19, no. 5-6, 1984, p. 849-863. refs

A considerable amount of work has been conducted regarding the optimization of aircraft structures subjected to flutter, natural frequency, and steady state stress constraints, while not much work has been reported with respect to the optimization of aircraft structures under landing loads. The present investigation provides a deterministic methodology for the optimum design of aircraft wing structures under landing loads. The methodology is presented for automated optimum design procedures. The considered optimization procedures are illustrated with the aid of two examples. The first example involves a hollow symmetric double-wedge airfoil, while the second example is concerned with a wing which has characteristics similar to that of the 707 aircraft. G.R.

A85-22081

BURBANK'S BLACKBIRDS

J. MILLER Air International (ISSN 0306-5634), vol. 28, Feb. 1985, p. 59-64, 84-87.

A development history is presented, together with design features and performance capabilities, for the 'Blackbird' series of aircraft that encompasses SR-71 reconnaissance platforms and YA-12/A-12 interceptor test bed aircraft. Aircraft of this type have been employed by NASA as flight test aircraft; their primary design mission, however, is optical, IR and radar reconnaissance in a flight regime in excess of Mach 3 and 100,000 ft, in order to elude detection. The Y-12 has achieved Mach 3.6 in level flight. The J58 'turboramjet', rated at 32,500 lb of static thrust, has been the standard powerplant, although J75 turbojets were used initially. Both single-seat and two-seat configurations have been employed, the latter in the case of reconnaissance-dedicated and training aircraft. O.C.

A85-22273

RENEGADE 250 - FLIGHT EVALUATION OR BOAT RIDE? [RENEGADE 250 - EVALUATION EN VOL OU PROMENADE EN BATEAU?]

H. JURION Air et Cosmos (ISSN 0044-6971), vol. 22, Jan. 12, 1985, p. 12, 13. In French.

The Renegade 250 Sea Wolf, a single-engine amphibian aircraft designed for marine reconnaissance and rescue operations, is characterized on the basis of a demonstration flight. Unusual features of the aircraft include a dorsally pylon-mounted 250-hp Lycoming C4B5 engine driving a three-blade constant-velocity curved-tip pusher propeller, a vertical tail fin with a notch giving wide clearance to the elevator, and a throttle mounted on the cockpit ceiling. The ground-takeoff characteristics, cruising performance at 250 km/h, and a marine landing and takeoff are described, and photographs are provided.

A85-22373

DESIGN OF A STOL AIRCRAFT WITH JET ASSISTED TAKEOFF UNITS (K PROEKTIROVANIIU SAMOLETA KOROTKOGO VZLETA I POSADKI S REAKTIVNYMI USKORITELIAMII

A. I. BAIDIN IN: III-posed problems in perturbation theory (A85-22364 08-02). Novosibirsk, Izdatel'stvo Nauka, 1984, p. 235-238. In Russian.

The present study describes a technique for reducing the length of the takeoff run of a STOL aircraft by means of starting jet assisted takeoff units (JATU), mounted at a certain angle to the horizontal. The optimal value of this angle is determined on the basis of known values for the thrust of the JATU and the thrust of the sustainer engine. B.L

N85-15665# Ministry of Defence, London (England). Materials and Structures Dept.

OPERATIONAL LOADS MEASUREMENT: A PHILOSOPHY AND ITS IMPLEMENTATION

D. M. HOLFORD and J. R. STURGEON In AGARD Operational Loads Data 22 p Aug. 1984 refs Avail: NTIS HC A14/MF A01

A philosophy of operational data acquisition, for structural objectives, within the general field of in-flight load measurement is reviewed, highlighting the constraints such activities place on the data acquisition system. One such system which can be tailored to perform a variety of tasks ranging from the collection of time histories of flight parameters or strain gauges to complex fatigue load analyses throughout the airframe is described. The system comprises a digital cassette recorder and a data acquisition unit within which a microprocessor is used for control of data acquisition and in-flight data analysis. System requirements in terms of accuracy, bandwidth and sampling rates are discussed for a range of aircraft types and operating conditions. The various modes of operation of the system are illustrated by examples drawn from operational experience with the system. These demonstrate the capability of the system to produce data suitable for automatic analysis in a variety of operational environments in both fixed and rotary wing aircraft. The examples clearly show the value of studying operational data in terms of fatigue life management, fatigue life monitoring, operational practices and design procedures. B.W.

N85-15666# McDonnell Aircraft Co., St. Louis, Mo. Structural Dynamics and Loads Dept.

THE F-15 FLIGHT LOADS TRACKING PROGRAM

J. T. JOHNSTON, R. E. PINCKERT, and R. A. MELLIERE In AGARD Operational Loads Data 7 p Aug. 1984 refs Avail: NTIS HC A14/MF A01

The F-15 flight loads tracking program is described. The tracking program consists of four phases: (1) data collection; (2) data reduction; (3) fatigue damage analysis; and (4) fleet management. Data collection is accomplished with a multi-channel recorder and a load factor (g) exceedance counter. Twenty percent of the fleet is equipped with the multi-channel recorder and every F-15 has a g exceedance counter installed. After the fleet data have been reduced by the Air Force it is sent to McDonnell Aircraft for conducting fatigue damage analyses. Quarterly Service Aircraft Fatigue Estimate (SAFE) reports inform the Air Force how much fatigue life has been expended on each aircraft. These reports are used for establishing inspections and aid in fleet management of the F-15 Eagles. This mature program, approaching, 1,000,000 flight hours, has been valuaable for solving in-service structural problems, understanding why the problems occurred, developing repairs, and for redesign. Future aircraft design will also benefit from this information. RW

N85-15667# National Amsterdam Aerospace Lab.. (Netherlands).

STRUCTURAL LOAD MEASUREMENTS ON A NORTHROP NF-5A

D. J. SPIEKHOUT In AGARD Operational Loads Data 15 p Aug. 1984

Avail: NTIS HC A14/MF A01

Load measurements were carried out on an NF-5A aircraft instrumented with a large number of strain gage bridges in the wing and the tail surfaces. Measurements included: (1) Specific stationary maneuvers; (2) Specific dynamic maneuver conditions; and (3) Complete mission segments typical for RNLAF-operational conditions. Using ground calibration results, recorded strains were converted to sectional loads and with flight parameters like V, H, acc. etc., stored in a structural load data base (15 flights covering 7 configurations and 715 measuring runs). By means of an interactive computer program the data stored in this data base are easily accessible. The results can be presented in tables or in graphical form. The Data Base may be used to evaluate the effect of changes in operational procedures, stores and store configurations on the fatigue load experience in various structural areas. A general description is given of the instrumentation used, the data handling and the flight conditions that were recorded. The possible use of the data base is illustrated by means of a number of examples. B.W.

N85-15668# Naval Air Development Center, Warminster, Pa. Airframe Engineering Branch.

NAVY OPERATIONAL LOADS DATA SOURCES AND SYSTEMS

A. H. JOHNSON and M. J. DUBBERLY (Naval Air Systems Command) In AGARD Operational Loads Data 20 p Aug. 1984

Avail: NTIS HC A14/MF A01

An overview of the Navy's total Aircraft Structural Life Surveillance Program is presented. Current Fatigue Monitoring Program operational achievements and costs are described. The loads data acquisition systems for the F-14, F-18, A-7, and A-3 aircraft are also described. Future expectations regarding operational features, results, and costs are discussed. Operational loads data from the Tactical Air Combat Training System for air combat training, and the 70 mm film system for landing loads, are also described. RW

N85-15669# Industrieanlagen-Betriebsgesellschaft m.b.H., Ottobrunn (West Germany).

OPERATIONAL LOADS DATA EVALUATION FOR INDIVIDUAL AIRCRAFT FATIGUE MONITORING

R. SCHUETZ and R. NEUNABER In AGARD Operational Loads Data 23 p Aug. 1984 refs

Avail: NTIS HC A14/MF A01

The utility of individual aircraft tracking (IAT) as an effective instrument for introducing the necessary maintenance activities which need to be adapted individually to each aircraft is examined. One of the most important activities within the IAT scope is the processing of operational loads data in order to calculate to consumed fatigue life of individual aircraft. The installed operational service load recording systems for military aircraft within the German Air Force include logforms, counting accelerometers and digital flight recorders. Under consideration are sytems for direct measurement of loads and damage. The main activities of individual aircraft tracking include: (1) loads and component data acquisition; (2) damage calculation; (3) calculation of allowable fatigue life; (4) prediction of maintenance actions; (5) derivation of standard load sequences or spectra; (6) cost effectiveness consideration; (7) verification of fatigue load monitoring; and (8) selection of load B.W. monitoring systems.

N85-15670# Messerschmitt-Boelkow-Blohm G.m.b.H., Toulouse (France). Airbus Program:

MEASUREMENT STRUCTURAL FLIGHT LOAD **DEMONSTRATION OF STRUCTURAL INTEGRITY**

E. RAUSCHER In AGARD Operational Loads Data 9 p Aug. 1984

Avail: NTIS HC A14/MF A01

Structural flight load testing is an important part of the certification of an aircraft. Calibration of strain gauges and bridge selection and evaluation of flight parameters for fatigue and static test problems are described. Procedures presented as an example here were used for flight testing on different types as fighters and military and civilian transport aircrafts. There are several evaluation methods for short and long flight periods to check design loads for static and fatigue criteria. The Maximum Likelihood method is used to investigate aerodynamic coefficients. Counting procedures are used for statistical purposes. B.W.

N85-15674# General Dynamics Corp., Fort Worth, Tex. F-16 Loads and Criteria Dept.

F-16 FORCE MANAGEMENT, YESTERDAY, TODAY AND TOMORROW

In AGARD Operational Loads Data 15 p R. L. CULP Aug. 1984 refs

Avail: NTIS HC A14/MF A01

United States Air Force regulations specify that a Force Management Program will be established for each aircraft system within its inventory. The approach taken by General Dynamics to fulfill the objectives of the Force Management Program for the F-16 aircraft is discussed. The methodology employed, the current status and the future plans for the F-16 Force Management Program in the areas of operational data acquisition, processing and airframe structural maintenance planning are discussed in detail. **BJF**

N85-15675# Army Research and Technology Labs., Fort Eustis, Va. Applied Technology Lab.

US ARMY HELICOPTER OPERATIONAL FLIGHT LOADS

D. J. MERKLEY and H. K. REDDICK, JR. In AGARD Operational Loads Data 26 p Aug. 1984 refs Avail: NTIS HC A14/MF A01

The findings from the Army's helicopter service usage programs and the Operational Loads Survey program are discussed. The development and capability of the Structural Integrity Recording System is described. R.J.F.

N85-15676# Westland Aircraft Ltd., Yeovil (England). HELICOPTER DATA ACQUISITION IN WHL

F. S. GRAINGER In AGARD Operational Loads Data 17 p Aug. 1984 refs

Avail: NTIS HC A14/MF A01

An approach to loads monitoring designed to fulfil two requirements is discussed. The first requirement is the elimination, as far as possible, of costly parts being thrown away because of overly conservative assumptions with respect to usage. The second requirement is to assure the assumed safety standards by knowledge of the in-service aircraft utilization. Specific problems appropriate to the helicopter make this task more difficult, but nevertheless the fundamental steps were taken to commence data acquisition. The nature of the task requires considerable aircraft management to ensure that as many role configurations are covered as possible. Since the data is acquired in real time, the acquisition of a statistically significant amount will be spread over the next few years. Nevertheless, early signs indicate that a considerable number of improvements will be accrued from even early data received. This approach also provides the ability to encompass new roles for an in-service aircraft type, in a much more rigorous way than current estimating methods. The methodology should also provide an information database against which to test loading theories (such as random load) and extend statistical scatter knowledge on times. R.J.F.

N85-15677# Messerschmitt-Boelkow-Blohm_G.m.b.H., Bremen (West Germany). Load Criteria Section. EVALUATION OF OPERATIONAL LOADS TO VERIFY STRUCTURAL DESIGN

H. STRUCK and H. BALKE In AGARD Operational Loads Data Aug. 1984 refs 16 p

Avail: NTIS HC A14/MF A01

A load evaluation method derived from operational maneuvers and the design requirements applied were presented. The method is based on the hypothesis that all maneuvers trained and flown by the Air Force can be standardized. Relevant parameters that are suitable to describe the maneuver time history with respect to load analysis were chosen. The standardization of maneuver parameters is demonstrated for two fighter aircraft and a few maneuver types. The correlated parameters necessary to derive structural loads, including control surface deflections can be determined, by standardized maneuvers. Operational loads on main structural components are evaluated by application of maneuver model. Extreme operational loads evaluated with the maneuver model and those determined by the design requirements are compared. E.A.K.

N85-15678# Canadair Ltd., Montreal (Quebec).

TUTOR (CL-41A) TAIL FLIGHT LOAD SURVEY

A. PAQUIN and J. SKOTNICKI (National Defence Headquarters) In AGARD Operational Loads Data 15 p Aug. 1984 refs Avail: NTIS HC A14/MF A01

An inflight structural failure of the Canadair Tutor aircraft horizontal tail fitting resulted in a flight load survey. An instrumented test aircraft was flown to the extremes of its structural envelope. and strains were recorded at 43 different locations on the rear fuselage and the empennage of the aircraft. The testinstrumentation, the calibration performed on the test article, and the resulting formulation of load equations for estimating shear, bending moment and torque at various locations on the rear fuselage, the vertical and the horizontal stabilizer are described. The various missions and maneuvers flown to gather the necessary data and the data acquisition, verification and reduction methods are discussed. E.A.K.

N85-15679# Avions Marcel Dassault, Saint-Cloud (France). AEROELASTIC ANALYSIS AND THE IDENTIFICATION OF FLIGHT LOADS {ANALYSE AEROELASTIQUE ET **IDENTIFICATION DES CHARGES EN VOL**

C. PETIAU and M. DELAVIGNE In AGARD Operational Loads Aug. 1984 refs In FRENCH Data 22 p Avail: NTIS HC A14/MF A01

A coupling procedure was developed for static analysis and load calculation in which pressure loads, obtained using aerodynamic theory, are transferred directly onto the finite element model. This sophisticated method singularly complicates the problem of smoothing models of the results of wind tunnel or flight tests. Processes of identification were studied with a view to easily reflecting the results of flight tests in complex aeroelastic models and to review, as rapidly as possible, the calculations justifying the structure and the static loads from ground tests.

Transl. by A.R.H.

N85-15710 Department of the Air Force, Washington, D.C. **POWERED ARTICULATED HEADREST SYSTEM Patent** A. B. MCDONALD and J. T. MANNIX, inventors (to Air Force)

21 Aug. 1984 7 p Supersedes AD-D009220 (AD-D011353; US-PATENT-4,466,662;

US-PATENT-APPL-SN-320893: US-PATENT-CLASS-297-406) Avail: US Patent and Trademark Office CSCL 01C

This patent is for a powered articulated headrest system for use with a seat structure having a backrest, such as the ejection seat of a high performance aircraft, e.g., a combat aircraft. The headrest system includes: a headrest assembly which is movably connected to the backrest; and, an electro-hydraulic actuator assembly for moving the headrest from an original (and normal) position above the backrest from an original (and normal) position above the backrest to any one of an infinite variety of positions which are rearward and downward of the headrest, and for moving the headrest from these other positions to the original position. The actuator assembly is controlled by the occupant of the seat, e.g., the pilot of the aircraft. When the headrest is moved rearwardly, unlike the prior art, the width of the headrest decreases thereby reducing any interference with aft visibility, and the height of the headrest also decreases thereby further reducing any interference with aft visibility and also eliminating any scrubbing action between the headrest and the head of the occupant of the seat. GRA

N85-15711 Department of the Air Force, Washington, D.C. AIRCRAFT THRUST CONTROL SCHEME FOR TERRAIN FOLLOWING SYSTEM Patent

W. C. KENDIG, inventor (to Air Force) 21 Aug. 1984 11 p Supersedes AD-D009357

(AD-D011387; US-PATENT-4,467,429;

US-PATENT-APPL-SN-339204; US-PATENT-CLASS-364-433) Avail: US Patent and Trademark Office CSCL 01C

This system permits speed variation within certain constraints. The minimum speed is derived from a stall avoidance or acceleration margin condition and the maximum speed may be the lower limit of the transonic region or other design limit. Assuming the throttle is set at or near a trim village, adjustments need only be made if the terrain following flight path is tending to drive the speed to one of the two velocity extremes. Velocity predictions are based on predicted kinetic energy being equal to the difference between the current kinetic energy and the potential energy to the profile extreme. The throttle is adjusted when the predicted velocity is outside the limits to add or remove the required amount of energy. Author (GRA)

N85-15712# Royal Aircraft Establishment, Farnborough (England).

THE EFFECT OF CHANGES IN THE ANGLE OF INCIDENCE IN THE EVENT OF A RICHOCHET AT A FLOAT STEP

B. E. PAVLIKEVICH Mar. 1984 11 p refs Transl. into ENGLISH from Gidromekhan. (USSR), v. 35, 1977 p 35-39 (RAE-TRANS-2120; BR93462) Avail: NTIS HC A02/MF A01

The results obtained by B. Milvitsky for the symmetrical impact of a seaplane when there is a significant change in the angle of incidence on contact with the water are examined. An expression is derived for a general dimensionless parameter which characterize the single degree-of-freedom motion. An analytical expression is derived which relates the immersion depth to the rate of immersion of the step. R.S.F.

N85-15713*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

F-8 REFUELING BOOM GROUND VIBRATION TEST Final Report

M. W. KAHOE Jan. 1985 50 p

(NASA-TM-84914; H-1194; NAS 1.15:84914) Avail: NTIS HC A03/MF A01 CSCL 01C

A ground vibration test was conducted on a simulated refueling boom mounted on an F-8 airplane. The ground vibration test was conducted to determine if the refueling boom modal frequencies were close to the airplane frequencies. The data presented in this report include modal frequencies, mode shape data, and structural damping coefficients. Author

N85-15714*# Boeing Commercial Airplane Co., Seattle, Wash. SYSTEMS STUDY FOR AN INTEGRATED DIGITAL-ELECTRIC AIRCRAFT (IDEA)

G. E. TAGGE, L. A. IRISH, and A. R. BAILEY Washington NASA Jan. 1985 206 p refs

(Contract NAS1-17528)

(NASA-CR-3840; NAS 1.26:3840; D6-52147) Avail: NTIS HC A10/MF A01 CSCL 01C

The results of the Integrated Digital/Electric Aircraft (IDEA) Study are presented. Airplanes with advanced systems were, defined and evaluated, as a means of identifying potential high payoff research tasks. A baseline airplane was defined for comparison, typical of a 1990's airplane with advanced active controls, propulsion, aerodynamics, and structures technology. Trade studies led to definition of an IDEA airplane, with extensive digital systems and electric secondary power distribution. This airplane showed an improvement of 3% in fuel use and 1.8% in DOC relative to the baseline configuration. An alternate configuration, an advanced technology turboprop, was also evaluated, with greater improvement supported by digital electric systems. Recommended research programs were defined for high risk, high payoff areas appropriate for implementation under NASA leadership. B.W.

N85-15715°# Hughes Helicopters, Culver City, Calif. STUDY TO ELIMINATE GROUND RESONANCE USING ACTIVE CONTROLS

F. K. STRAUB Oct. 1984 123 p refs

(Contract NAS2-11261)

(NASA-CR-166609; NAS 1.26:166609) Avail: NTIS HC A06/MF A01 CSCL 01C

The effectiveness of active control blade feathering in increasing rotor body damping and the possibility to eliminate ground resonance instabilities were investigated. An analytical model representing rotor flapping and lead-lag degrees of freedom and body pitch, roll, longitudinal and lateral motion is developed. Active control blade feathering is implemented as state variable feedback through a conventional swashplate. The influence of various feedback states, feedback gain, and weighting between the cyclic controls is studied through stability and response analyses. It is shown that blade cyclic inplane motion, roll rate and roll acceleration feedback can add considerable damping to the system and eliminate ground resonance instabilities, which the feedback phase is also a powerful parameter, if chosen properly, it maximizes augmentation of the inherent regressing lag mode damping. It is shown that rotor configuration parameters, like blade root hinge offset, flapping stiffness, and precone considerably influence the control effectiveness. It is found that active control is particularly powerful for hingeless and bearingless rotor systems. E.A.K.

N85-15716*# National Aeronautics and Space Administration, Washington, D. C.

INSTALLED NACELLE DRAG-IMPROVEMENT TESTS OF AN M = 0.8 TURBOPROP TRANSPORT CONFIGURATION

A. D. LEVIN and R. C. SMITH Jan. 1983 378 p refs (NASA-TM-84302; A-9127; NAS 1.15:84302) Avail: NTIS HC A17/MF A01 CSCL 01C

An unpowered semispan model of a representative turboprop configuration was tested to determine the effect of configuration modifications on the the nonmetric body and wing juncture. It is indicated that the jet off nacelle-installation drag can be approximately 25% of the cruise drag. However, the losses can be reduced to 17% by changes to the wing leading edge and nacelle intersection. Comparison of test results from a semispan nonmetric fuselage model with those from a full span metric fuselage show differences in angles of attack produced the same lift. It is found that the constant lift drag rise of the semispan model is higher because of the increased angle of attack to achieve the same lift. E.A.K.

N85-15717*# System Planning Corp., Arlington, Va. SPEED BENEFITS OF TILT-ROTOR DESIGNS FOR LHX Final Briefing Report, Feb. 1982

R. L. MCDANIEL, J. V. ADAMS, A. BALBERDE, S. P. DERESKA, C. J. GEARIN, and D. E. SHAW Jan. 1983 81 p

(Contract NAS2-11020)

.

(NASA-CR-166437; NÁS 1.26:166437; SPC-789) Avail: NTIS HC A05/MF A01 CSCL 01A

The merits of an advanced helicopter and a tilt rotor aircraft for light utility, scout, and attack roles in combat missions envisioned for the year 2000 and beyond were compared. It is demonstrated that speed has increasing value for 11 different mission classes broadly encompassing the intended LHX roles. Helicopter speeds beyond 250 knots are judged to have lower military worth. Since the tilt rotor concept offers a different cost
05 AIRCRAFT DESIGN, TESTING AND PERFORMANCE

speed relationship than that of helicopters, assessment of a tilt rotor LHX variant was warranted. The technical parameters of an advanced tilt rotor are stablished. Parameters of representative missions are identified, computed relative value of the tilt rotor LHX are compared to the baseline helicopter, a first-order life cycle estimate for the tilt rotor LHX is established, military worth of the alternative design is computed and the results are evaluated. It is suggested that the tilt rotor is the solution with the greatest capability for meeting the uncertainties of future needs. E.A.K.

N85-15718*# Lockheed-California Co., Burbank. INTEGRATED TECHNOLOGY WING STUDY (ORAL PRESENTATION)

8 Apr. 1981 188 p (Contract NAS1-16273)

(NASA-CR-169497; NAS 1.26:169497; LR-29801) Avail: NTIS HC A09/MF A01 CSCL 01C

The design of a plan for a commercial transport manufacturer to integrate advanced technology into a new wing for a derivative and/or new aircraft that could enter service in the late 1980s to early 1990s time period is proposed. The development of a new wing for a derivative or a new long range commercial aircraft and the incorporation of cost effective technologies are studied. The decision provides guidelines for the best allocation of research funds. E.A.K.

N85-15719# Army Aviation Engineering Flight Activity, Edwards AFB, Calif.

UH-60A EXTERNAL STORES SUPPORT SYSTEM FIXED PROVISION FAIRINGS DRAG DETERMINATION Final Report, 30 Aug. - 22 Sep. 1983

R. A. ŴILLIAMS, R. MACMULLIN, J. O. MIESS, R. M. BUCKANIN, and W. Y. ABBOTT May 1984 45 p

(AD-A147188; USAAEFA-82-15-1) Avail: NTIS HC A03/MF A01 CSCL 01C

A comparative performance evaluation of the UH-60A helicopter in the normal utility configuration and with the External Stores Support System (ESSS) fixed provision fairings configuration (ESSS wings removed) was conducted at Edwards AFB, Cal. A total of eight flights were flown between 30 August and 22 September 1983, for a total of 10.0 productive hours. The increase in equivalent flat plate area due to installation of the ESSS fixed provision fairings was 2.5 sq. ft. With the ESSS fixed provision fairings installed at the out-of-ground effect hover guarantee conditions of 95 percent intermediate rated power at 4700 feet pressure altitude on a 35 deg C day, the hover capability was reduced 466 pounds. Incorporating the weight of the airframe fixed provisions will reduce the payload by 596.6 pounds or the equivalent of eliminating two combat equipped troops and 117 pounds of fuel or equipment.

Author (GRA)

N85-15720# Research Inst. of National Defence, Stockholm (Sweden). Dept. 2.

NYKINM, A FURTHER DEVELOPMENT OF KINM 22

K. ANDÉRSSON Oct. 1984 37 p refs In SWEDISH; ENGLISH summary

(FOA-C-20559-D8(E3); ISSN-0347-3694) Avail: NTIS HC A03/MF A01

A simulation program of a robot attack against an aircraft, which can perform only one evasive action was developed. The robot is assumed to fulfill the proportional navigation condition all the time, its path is kinematic. Performance tests, input/output routines, and the mathematical relationship for the target path (and the robot path) are given. The simulation package makes it possible to integrate vectors. Author (ESA) N85-16766# Joint Publications, Research Service, Arlington, Va. TESTING SOLUTION FOR IL-76 BRAKING SYSTEM PROBLEM V. LAMZUTOV *In its* USSR Rept.: Transportation (JPRS-UTR-85-001) p 6-8 15 Jan. 1985 Transl. into ENGLISH from Vozdushnyy Transp. (Moscow), 30 Aug. 1984 p 3 Avail: NTIS HC A09/MF A01

Landing gear buffeting was noted on IL-76 aircraft returning with only a safe fuel reserve after having delivered cargo to the North. Experimental flights revealed that the automatic braking unit was at fault. Following adjustments to the braking unit, pilots were given instruction on how to fly the aircraft so as to avoid the buffeting and how to combat buffeting should it arise. One flight conducted to determine how the the unit behaves on a runway under various landing conditions and the kind of braking performance obtained is described. A.R.H.

N85-16768# Joint Publications Research Service, Arlington, Va. DESIGNER ON CIVIL AIRCRAFT DESIGN TRENDS IN USSR

S. YEGER *In its* USSR Rept.: Transportation (JPRS-UTR-85-001) p 14-17 15 Jan. 1985 Transl. into ENGLISH from Nedelya (Moscow), no. 33, 13-19 Aug. 1984 p 12-13 Avail: NTIS HC A09/MF A01

Further reduction in fuel consumption, weight, and drag are drivers affecting aircraft design in the coming decades. Technology needs include more economical engines; multi-bladed propellers; improved production techniques for cabin sealing and paint thickness distribution; and short takeoff and landing aircraft. Long range routes being flown by aircraft similar to the IL-86 are foreseen. Medium haul routes should see the appearance of aircraft capable of handling 180 to 200 passengers, with more economical engines, longer wingspans, and slightly wider fuselages. Short haul aircraft should have new generation turboprop or turbofan engines.

A.R.H.

N85-16777# National Aerospace Lab., Amsterdam (Netherlands).

DESIGN OF AN AIRFOIL LEADING EDGE SLAT USING AN INVERSE AERODYNAMIC CALCULATION METHOD

J. A. VANEGMOND and B. VANDENBERG *In* AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 11 p Aug. 1984 refs Avail: NTIS HC A18/MF A01

In order to evaluate the applicability of the design system MAD (multi-element airfoil design), a design study was performed for a two-dimensional wing with leading edge slat. The problem is representative for that of a transport airplane operating out of high altitude airfields requiring a high lift-to-drag ratio at takeoff. A two-dimensional high life configuration tested earlier in a low speed wind tunnel was selected as the starting configuration. The design system MAD is described briefly. The actual leading edge slat design is given. The new slat-wing configuration as tested in a wind tunnel and some of the test results are presented together with results of the baseline configuration. R.S.F.

N85-16780# Boeing Military Airplane Development, Seattle, Wash.

AERODYNAMIC ISSUES IN THE DESIGN OF HIGH-LIFT SYSTEMS FOR TRANSPORT AIRCRAFT

B. DILLNER, F. W. MAY, and J. H. MCMASTERS /n AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 22p Aug. 1984 refs Avail: NTIS HC A18/MF A01

The design of the high lift system has a profound effect on the sizing and total performance of transport aircraft, both civil and military. The fundamentals of high lift system design are reviewed along with the phenomena that govern their performance. The computational methods available to the high lift designer, with examples of their validity, are presented. New developments in flow diagnostic techniques are reviewed. Examples of several Boeing high lift design efforts are given. Emphasis is placed on the use of computational aerodynamic methods and the synergistic effect of using those methods in parallel with testing. A list of

05 AIRCRAFT DESIGN, TESTING AND PERFORMANCE

todays ten most important issues in high lift aerodynamics is presented. R.S.F.

N85-16781# De Havilland Aircraft Co. of Canada Ltd., Downsview (Ontario).

AN UPDATE OF THE CANADA/USA AUGMENTOR-WING PROJECT

D. C. WHITTLEY In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 8 p Aug. 1984 refs Avail: NTIS HC A18/MF A01

Following extensive tests of a half scale model in the NASA, Ames 40' x 80' wind tunnel, a minimum cost flight demonstrator was built based on the de Havilland Buffalo airframe. Following completion of the NASA trials in 1980, work has continued in Canada covering four main areas of interest using the augmenter wing powered lift concept: (1) additional flight trials on the demonstrator aircraft; (2) propulsion system technology development; (3) experimental investigation of a new compound supercritical airfoil; and (4) project definition studies. F.A.K.

N85-16782# Lockheed-Georgia Co., Marietta. Advanced Flight Sciences.

AIRCRAFT DRAG REDUCTION TECHNOLOGY

A. S. W. THOMAS In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and high Lift Systems 20p Aug. 1984 refs

Avail: NTIS HC A18/MF A01

The current techniques of aircraft viscous drag reduction and some of the more recent developments that have taken place in this technology are reviewed. The various sources and relative contributions of aircraft drag are described including skin friction drag, pressure drag, interference drag and lift induced drag. The physical processes that lead to these drag contributions are emphasized and methods of reducing the impact of these drag sources are discussed. It is shown how innovative and optimized aircraft configurations can lead to drag benefits. E.A.K.

N85-16786# Technische Hogeschool, Delft (Netherlands). Dept. of Aerospace Engineering.

DESIGN STUDIES OF THICK LAMINAR FLOW AIRFOILS FOR LOW SPEED FLIGHT EMPLOYING TURBULENT BOUNDARY LAYER SUCTION OVER THE REAR PART

J. L. VANINGEN, J. J. H. BLOM, and J. H. GOEI In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 19 p Aug. 1984 refs Avail: NTIS HC A18/MF A01

Computational tools, used to analyze and design airfoils for low speed flight (prediction of potential flow pressure distributions, laminar boundary layer flows, transition prediction using the e(n) method and Head's entrainment method for the calculation of turbulent boundary layers are described. These tools are used to design pressure distributions and corresponding airfoil shape producing long runs of natural laminar flow. Inevitably this results in airfoils with the maximum thickness far backwards, eventually leading to separation of the turbulent boundary layer over the rear part of the airfoil. This turbulent boundary layer separation is prevented by selecting a proper pressure distribution over the rear part and/or suction of the turbulent boundary layer through slots or distributed perforations. Design charts are presented which help to select the required pressure distributions for laminar and turbulent flow. B.W.

N85-16790*# Aeronautical Research Inst. of Sweden, Bromma. FULL SCALE EXPERIMENTS INTO THE USE OF LARGE EDDY BREAKUP DEVICES FOR DRAG REDUCTION ON AIRCRAFT

A. BERTELRUD In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 16 p Aug. 1984 refs

Avail: NTIS HC A18/MF A01

An experimental investigation in flight was performed to explore the feasibility of using LEBU (Large-Eddy-Breakup) devices to reduce the drag of aircraft. Two geometrical shapes of ribbons

were used, and the development of local skin friction was monitored downstream. The aircraft was a swept-wing attack aircraft, and the flights covered the entire subsonic regime from M=0.92 down to stall conditions; flight altitudes were 1, 4.5, 7 and 10 km to explore various combinations of angle of attack, Mach - and Revnolds numbers. Some information was obtained concerning the turbulence characteristics downstream, and a discussion of the downstream amplification due to the drag at the device is also presented. B.W.

N85-16791# Technische Hogeschool, Delft (Netherlands). PNEUMATIC TURBULATORS: A DEVICE FOR DRAG **REDUCTION AT REYNOLDS NUMBERS BELOW 5 MILLION**

K. H. HORSTMANN, A. QUAST, and L. M. M. BOERMANS In AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 19 p Aug. 1984 refs

Avail: NTIS HC A18/MF A01

At Reynolds numbers below 5 million, airfoils are affected by laminar separation bubbles which in many cases considerably increase the drag. By blowing air from a row of orifices at the beginning of the laminar separation bubble, the bubble can be prevented and the drag can be reduced substantially. This device is called a pneumatic turbulator. Free-stream total pressure is sufficient to provide the turbulator bleed air. The additional drag caused by the bleed air and the air jets is negligible. The low drag Reynolds number range of laminar airfoils can be extended by using pneumatic turbulators. B.J.F.

N85-16818# Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West Germany).

FLIGHT TESTS WITH A NEW HELICOPTER FORCE FEEL SYSTEM (FFS)

R. D. VONRETH, H. KOENIG, and G. TURCK In AGARD Helicopter Guidance and Control Systems for Battlefield Support Aug. 1984 refs 11 o

Avail: NTIŠ HC A13/MF A01

An artificial force feel system for the control of the pitch and roll axes of a Bo 105 helicopter was studied. Goals of the program were to investigate if the use of such an artificial force feel system for the helicopter control would increase flight safety, allow a more precise control of a flight path, increase stability, and reduce pilot workload. An experimental flight worthy system using the electro-hydraulic actuators for the pitch and roll axis respectively was implemented in the flying simulator Bo 105-53. A number of different force control laws were derived and flight tested. Although some contributions to the total control force were rated very differently by the various test pilots (e.g., contributions from the normal acceleration), as a general trend very favorable ratings were obtained. Two examples of these favorable ratings for highly dynamic maneuvers (slalom and dolphin) are an improved stability of the trim state and an improved flight path control in general.

M.G.

N85-16861*# Lockheed-California Co., Burbank.

INTEGRATED DIGITAL/ELECTRIC AIRCRAFT CONCEPTS STUDY Contractor Report, Oct. 1983 - Sep. 1984

M. J. CRONIN, A. P. HAYS, F. B. GREEN, N. A. RADOVCICH, C. W. HELSLEY, and W. L. RUTCHIK Washington NASA Jan. 1985 464 p refs

(Contract NAS1-17529)

(NASA-CR-3841; NAS 1.26:3841; LR-30704) Avail: NTIS HC A20/MF A01 CSCL 01C

The integrated digital/electrical aircraft (IDEA) is an aircraft concept which employs all electric secondary power systems and advanced digital flight control systems. After trade analysis, preferred systems were applied to the baseline configuration. An additional configuration, the alternate IDEA, was also considered. For this concept the design ground rules were relaxed in order to quantify additional synergistic benefits. It was proposed that an IDEA configuration and technical risks associated with the IDEA systems concepts be defined and the research and development required activities to reduce these risks be identified. The selected

subsystems -- include: --- power -- generation; -- power --- distribution; -actuators, environmental control system and flight controls systems. When the aircraft was resized, block fuel was predicted to decrease by 11,3 percent, with 7.9 percent decrease in direct operating cost. The alternate IDEA shows a further 3.4 percent reduction in block fuel and 3.1 percent reduction in direct operating cost.

R.S.F.

N85-16862*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

STUDY OF WINGLETS APPLIED TO BIPLANES

P. D. GALL and H. C. SMITH (Pennsylvania State Univ.) Jan. 1985 21 p refs Presented at the 23rd AIAA Aerospace Sci. Meeting, Reno, Nev., 14-17 Jan. 1985 Submitted for publication (NASA-TM-86350; NAS 1.15:86350; AIAA-85-0279) Avail: NTIS HC A02/MF A01 CSCL 01C

The possibility of improving the aerodynamic characteristics of a biplane configuration by adding winglets is examined both theoretically and experimentally. Theoretical calculations show good agreement with experiment in predicting inviscid drag due to lift. Theoretical and experimental results indicate that the addition of winglets to an optimized biplane configuration can increase the ideal efficiency factor by up to 13 percent, as well as increasing the lift curve slope and maximum lift coefficient. B.W.

N85-16864# Army Aviation Engineering Flight Activity, Edwards AFB, Calif.

AIRWORTHINESS AND FLIGHT CHARACTERISTICS TEST OF THE RC-12D GUARDRAIL V Final Report, 10 May - 1 Jun. 1984

G. M. YAMAKAWA, J. L. WEBRE, R. S. ADLER, and R. E. RATCLIFF Jul. 1984 73 p

(Contract AF PROJ. 8402)

(AD-A148046; AD-E850735; USAAEFA-84-02) Avail: NTIS HC A04/MF A01 CSCL 01B

The US Army Aviation Engineering Flight Activity conducted a limited Airworthiness and Flight Characteristics test of the RC-12D (Improved Guardrail V) aircraft with both standard and infrared (IR) suppressor exhaust stacks installed from 10 May though 1 June 1984 at Wichita, Kansas. During the test program, 12 flights were conducted for a total of 25.7 hours, of which 14.6 were productive. All tests were performed in a normal mission configuration ballasted to a maximum takeoff gross weight of 14,200 pounds and a center of gravity at fuselage station 190.1 (fwd). Test results were compared with data obtained during previous testing, and evaluated against military specification MIL-F-8785C. Takeoff and landing performance presented in the operator's manual were confirmed as was the Beech Aircraft Corporation provided drag polar plot of the standard stack configured aircraft. A slight degradation in performance was noted with IR suppressor exhaust stacks installed. The RC-12D aircraft has marginal climb performance capabilities with a combat ceiling below 24,000 feet density altitude. The handling qualities of the RC-12D with both standard and IR suppressor exhaust stacks installed were essentially unchanged from the standard C-12D aircraft with the exception of improved stall characteristics. GRA

N85-16865# Army Aviation Engineering Flight Activity, Edwards AFB, Calif.

PRELIMINARY AIRWORTHINESS EVALUATION AH-1S (MC) HELICOPTER WITH EXTERNAL FUEL TANKS INSTALLED Final Report, 17 Mar. - 27 Apr. 1984

J. J. NAGATA, J. S. VOSS, and R. A. WILLIAMS Jul. 1984 93

(AD-A148091; USAAEFA-84-09) Avail: NTIS HC A05/MF A01 CSCL 01C

The Preliminary Airworthiness Evaluation of the AH-1S Modernized Cobra, (S/N 69-16423) with the Kellett ferry tanks installed was conducted at Edwards Air Force Base, California (2302 feet) and Bakersfield, California (488 feet). Approximately 19 productive hours were flown during 24 flights between 17 March and 27 April 1984. The Kellett ferry tanks increased the equivalent flat plate area by 2.0 sq ft. One deficiency noted during the evaluation was the lack of crashworthiness of the external fuel tanks. Four shortcomings associated with the installation of the GRA external fuel tanks were found.

N85-16866# Air Force Inst. of Tech., Wright-Patterson AFB, Ohio. School of Systems and Logistics.

A DESCRIPTION OF A LOGISTICALLY IDEAL AIRCRAFT M.S. Thesis

J. O. CAMPBELL and J. D. CARLIN Sep. 1984 84 p

(AD-A148425; AFIT/GSM/LSY/84S-5) Avail: NTIS HC A05/MF A01 CSCL 01C

The purpose of this thesis was to develop a description of a logistics ideal aircraft. A survey was conducted of senior Air Force logisticians and distinguished civilian logisticians. The Delphi methodology was used to elicit expert opinion concerning major logistics problems in current generation aircraft and ways to avoid these problems in future generation aircraft. These problems and solutions were used to describe the logistics ideal aircraft. GRA

N85-16867# Air Force Wright Aeronautical Labs.. Wright-Patterson AFB, Ohio.

OPTIMUM PERFORMANCE PARAMETERS FOR SKI-JUMP OPERATIONS OF USAF FIGHTER AIRCRAFT

J. J. OLSEN Aug. 1984 42 p (Contract AF PROJ. 2401)

(AD-A148532; AFWAL-TM-84-217-FIB) Avail: NTIS HC A03/MF A01 CSCL 01B

This paper discusses the equations of motion which govern the aerodynamic performance of USAF fighter aircraft immediately after ski-jump takeoffs. By a careful selection of coordinate systems and independent and dependent variables, we eliminate the need for repetitive time-history integration of the nonlinear, coupled equations. This allows a relatively simple, but exact solution of the problem. Detailed results are presented for the F-4, A-10, F-15 and F-16 for two cases -- a nominal baseline for constant pitch attitude, and a best possible case which produces the lowest achievable takeoff speeds. Author (GRA)

06

AIRCRAFT INSTRUMENTATION

Includes cockpit and cabin display devices; and flight instruments.

A85-21555*# Lockheed-Georgia Co., Marietta. **PILOT'S DESK FLIGHT STATION**

G. A. SEXTON (Lockheed-Georgia Co., Marietta, GA) IN: Symposium on Aviation Psychology, 2nd, Columbus, OH, April 25-28, 1983, Proceedings . Columbus, OH, Ohio State University, 1984, p. 27-36.

(Contract NAS1-16199)

Aircraft flight station designs have generally evolved through the incorporation of improved or modernized controls and displays. In connection with a continuing increase in the amount of information displayed, this process has produced a complex and cluttered conglomeration of knobs, switches, and electromechanical displays. The result was often high crew workload, missed signals, and misinterpreted information. Advances in electronic technology have now, however, led to new concepts in flight station design. An American aerospace company in cooperation with NASA has utilized these concepts to develop a candidate conceptual design for a 1995 flight station. The obtained Pilot's Desk Flight Station is a unique design which resembles more an operator's console than today's cockpit. Attention is given to configuration, primary flight controllers, front panel displays, flight/navigation display, approach charts and weather display, head-up display, and voice command and response systems. G.R.

A85-21559#

THE COCKPIT DISPLAY OF TRAFFIC INFORMATION AND THE THREAT ALERT AND COLLISION AVOIDANCE SYSTEM INTEGRATION - A REVIEW

P. T. LESTER (San Jose State University, San Jose, CA) and E. E. QUAN, JR. (California, University, Berkeley, CA) IN: Symposium on Aviation Psychology, 2nd, Columbus, OH, April 25-28, 1983, Proceedings . Columbus, OH, Ohio State University, 1984, p. 69-75. refs

The Cockpit Display of Traffic Information (CDTI) and the Threat Alert and Collision Avoidance System (TCAS) integration will display traffic in the vicinity of an aircraft and issue maneuver commands to pilots to aid in the prevention of aircraft collisions. Discussed were the effects of adding more displays to an increasingly automated cockpit and the consequences of changing the design of aircraft from three to two man crews when using the CDTI/TCAS system. Studies were analyzed to find efficient display symbology for the CDTI, the problem of false alarms and their effect on pilot confidence in the CDTI/TCAS system, and the problem of pilot disagreement with TCAS commands. The authors suggest that the TCAS commands be closer to the pilot's maneuver of choice, and that additional studies are needed concerning the time a pilot must spend to utilize the CDTI and the effectiveness of the CDTI/TCAS system in areas with high air traffic densities.

Author

A85-21593#

CONTRAST SENSITIVITY PERFORMANCE ASSESSMENT OF HUD DISPLAY SYSTEMS

A. P. GINSBURG, W. L. MARTIN, and H. SELF (USAF, Aerospace Medical Research Laboratory, Wright-Patterson AFB, OH) IN: Symposium on Aviation Psychology, 2nd, Columbus, OH, April 25-28, 1983, Proceedings. Columbus, OH, Ohio State University, 1984, p. 473-480. refs

The contrast losses of three head-up displays (HUD) having either reflective or refractive optical systems were determined from contrast sensitivity measurements under laboratory and field conditions. Contrast sensitivity losses resulting from the HUD optics due to transmittance, glare and reflections were translated into detection range losses using previously collected field trial data that related differences in detection range of Air Force pilots to differences in their contrast sensitivity. Agreements in detection range loss penalties using this direct approach and traditional approaches are good. In general, these three quite different HUDs produce similar losses in detection range. Author

N85-15721 Department of the Air Force, Washington, D.C. BIODYNAMIC RESISTANT CONTROL STICK Patent

D. W. REPPERGER, inventor (to Air Force) 16 Oct. 1984 20 p Supersedes AD-D010034

(AD-D011380; US-PATENT-4,477,043;

US-PATENT-APPL-SN-449922; US-PATENT-CLASS-244-223)

Avail: US Patent and Trademark Office CSCL 01C This patent presents an improvement to an aircraft control

stick is disclosed. Movement of an aircraft may generate a force which undesirably causes the aircraft pilot to deflect the aircraft's control stick, which thereby results in the aircraft deviating from the desired flight path. The present invention includes a processor-based system which employs an algorithm that generates a signal for causing the control stick to resist such forces. The invention includes a spring and damper connected to the control stick so that the spring constant and damping ratio may be varied. GRA N85-15722# McDonnell Aircraft Co., St. Louis, Mo.

DISPLAY TECHNIQUES FOR ADVANCED CREW STATIONS (DTACS). PHASE 1: DISPLAY TECHNIQUES STUDY Final Technical Report, Apr. 1983 - Oct. 1984

E. C. ADAM, H. E. DILLARD, R. M. VELTEN, and J. GUENTHER Wright-Patterson AFB, Ohio AFWAL Mar. 1984 130 p (Contract F33615-83-C-1040)

(AD-A146922; AFWAL-TR-84-1016) Avail: NTIS HC A07/MF A01 CSCL 01C

The DTACS Final Report describes the study which explored advanced display techniques and their effect on future fighter/attack aircraft crew stations. The emphasis was placed on new and developing technology with applications to integrated avionics systems. Future mission requirements were reviewed, display requirements were established, display technologies were reviewed, an initial configuration of an advanced display was made and a plan for further development was also prepared. GRA

N85-16799# Ferranti Ltd., Edinburgh (Scotland). Navigation Systems Dept.

AUTOMATIC BRIEFING AND MISSION MANAGEMENT SYSTEMS FOR BATTLEFIELD SUPPORT

C. G. W. ROADS *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 6 p Aug. 1984 refs Avail: NTIS HC A13/MF A01

Mission planning and briefing systems were used for almost a decade to make the best use of advanced avionics fitted to high performance fixed-wing aircraft. As similar equipment is fitted to helicopters to enable them to perform on the battlefield the need for mission briefing systems will become apparent. How such a system might be used in the context of a hypothetical future operation is described and in doing so seeks to highlight some of the technical problems which will be encountered in developing and fielding such equipment. The interaction of the databases which could be exploited by such system are considered, and whether the equipment in service today is developing towards the future systems described.

N85-16800# Anacapa Sciences, Inc., Santa Barbara, Calif. A COMPUTER-GENERATED TOPOGRAPHIC DISPLAY SYSTEM FOR NAVIGATION AND MISSION PLANNING IN HELICOPTERS

S. P. ROGERS *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 11 p Aug. 1984 refs Avail: NTIS HC A13/MF A01

The Integrated Mission-Planning Station (IMPS) is a computer-generated topographic display system. The IMPS will provide not only a greatly enhanced navigation capability, but also a combination of dramatic improvements in cartographic support, map information content, and aviator-map interactions. The powerful computational capability of the IMPS can be used to present a shaded relief map, to display areas masked from visual or radar observation, to construct perspective views of key terrain, to support a self-contained terrain correlation navigation system, and to permit rapid solutions to problems of previously forbidding complexity. The tasks conducted to provide detailed human factors engineering specifications for the construction and programming are described. The outcome of these efforts is described in terms of an overview of system components and functions. Each of the major functions of the IMPS system is discussed, and the operational requirements, present deficiencies, and IMPS capabilities are identified. Author

N85-16801# Thomson-CSF, Issy les Moulineaux (France). MAP DISPLAY FOR HELICOPTERS

P. CHOLLE In AGARD Helicopter Guidance and Control Systems for Battlefield Support 16 p Aug. 1984 refs In ENGLISH and FRENCH

Avail: NTIS HC A13/MF A01

Modern combat helicopters have to be adapted to a context of constantly increasing crew work load. The electronic map display is a way to greatly reduce navigation tasks. Present position of the aircraft is continuously provided and allows for very fast

. •

06 AIRCRAFT INSTRUMENTATION

navigation-up-dating:-North-up-and Track-up modes are also possible. A continuous zoom is used to enlarge some details. A joystick is used to manually move the map for visualization of other zones. Different maps scales are available. If the helicopter's display system is powerful enough it is also possible to create an interactive console giving the crew the ability to memorize data on the map before the mission and in real time during the flight. Author

N85-16805# Racal Avionics Ltd., New Malden (England). INTEGRATED CONTROL AND DISPLAY SYSTEMS FOR HELICOPTER BATTLEFIELD MISSION MANAGEMENT

M. A. RICHARDSON *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 7 p Aug. 1984 Avail: NTIS HC A13/MF A01

The avionics requirements of an integrated crew station for battlefield helicopters are discussed. An example of the approach taken to equip a multi-role light attack helicopter is provided.

B.W.

N85-16806# Societe de Fabrication d'Instruments de Mesure, Massy (France).

A DIGITAL PILOTING SYSTEM FOR THE COMBAT HELICOPTER [SYSTEME NUMERIQUE DE PILOTAGE POUR HELICOPTERE DE COMBAT]

J. C. DERRIEN *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 13 p Aug. 1984 refs In FRENCH

Avail: NTIS HC A13/MF A01

For several years, SFIM has specialized in the development of digital systems for piloting the helicopter. A sophisticated environment for simulation for the design of future systems has been created and used in recent years for the design and adjustment of systems for complete in-flight evaluation on several types of helicopters. General methods for the design and integration of such systems, the PAN 1 digital piloting system coupled to the 26SH strap-down attitude unit, and an HCL coupling system for hovering which is itself, connected to the VENUS pointing system are discussed. The system being developed at SFIM which was completely adapted for the combat helicopter is examined.

Transl. by A.R.H.

N85-16808# Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West Germany).

EVALUATION OF NOSE, ROOF, AND MAST MOUNTED SENSOR PLATFORMS FOR PILOTING AND SIGHTING, INTEGRATED IN FUTURE COMBAT HELICOPTERS

H. D. V. BOEHM and R. D. V. RETH *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 16 p Aug. 1984 refs

Avail: NTIS HC A13/MF A01

The piloting and sighting tasks under day, night and adverse weather conditions for a combat helicopter are different. For sighting the helicopter needs a well adapted sensor package, which may consist of a high performance FLIR, a direct view glass optic, a TV-channel and a tracker with a boresighting module. For the piloting task it is possible to use a complex sensor system including a helmet mounted sight and display (HMS/D) and/or night vision goggles (NVG). Different aspects of nose-, roof-, and mast-mounted sights (NMS, RMS, NMS) for a gunner and present and future weapon systems are discussed. Advanced electro-optical systems with a high performance telescope, allowing an increased combat range are considered. An advanced multisensor approach where the more conventional systems are supplemented or partially replaced by a multimode imaging radar is examined. The sensor for piloting can be integrated with the sighting system or located in a position remote from the sight. The pilot needs a dedicated display in the form of either a head-down display (HDD) or a helmet mounted display (HMD). A superimposed symbology adapted to the phase of the mission e.g., cruise, transition or hover, is required in either case. E.A.K. -N85-16809# Crouzet Aerospace and Systems; Valence (France).

RECENT METHODS FOR CALIBRATING THE ANEMOMETRY OF HELICOPTERS AT LOW SPEEDS [NOVELLES METHODES D'ETALONNAGE DE L'ANEMOMETRIE DES HELICOPTERES AUX BASSES VITESSES]

J. MANDLE *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 12 p Aug. 1984 refs In FRENCH Avail: NTIS HC A13/MF A01

Improvements made by Crouzet to make classic methods of calibrating anemometry compatible with the flight domain of helicopters are discussed as well as proposed new material. The limitations of the classic methods are examined, the improvements defined, and equipment installed for these new methods at the Brittany Flight Test Center are described. Transl. by A.R.H.

N85-16811# Westland Helicopters Ltd., Yeovil (England). THE DESIGN AND DEVELOPMENT OF AN INTEGRATED CORE SYSTEM FOR BATTLEFIELD HELICOPTERS

S. D. ROY and P. L. SHILLITO *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 10 p Aug. 1984 refs

Avail: NTIS HC A13/MF A01

Integrated control systems for Lynx and Westland combat helicopters are discussed. Navigation, communications, and weapons systems integration is addressed, as well as an architecture which not only enables the crew to manage and control the systems and aircraft on the battlefield, but provides a means of extending the performance of the total system-crew, avionics, and aircraft. R.J.F.

N85-16812# Army Avionics Research and Development Activity, Fort Monmouth, N. J.

EVOLUTION TOWARD A MULTI-BUS. ARCHITECTURE FOR ARMY HELICOPTER AVIONIC SYSTEMS

J. A. DASARO *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 7 p Aug. 1984 refs Avail: NTIS HC A13/MF A01

An attempt to arrive at an architecture which fits the avionics technology available today and that which will be available in the near future is described. Current efforts to implement this technology in the U.S. Army Avionics Laboratory are using currently available microprocessors configured as a multiprocessor and an available Ada compiler. A procurement strategy evolved in parallel with this architecture that uses form, fit, function specifications and interface control documents so as not to restrict future procurements to today's technology. Certainly much work remains to be accomplished to evolve the concept presented here; however, it is fully expected that over the next several years, enough experience should be gained to achieve an architecture that should meet the needs for the demanding helicopter missions of the future. A.R.H.

N85-16813# Bell Helicopter Co., Fort Worth, Tex.

INTEGRATION OF SENSOR FUSION IN ADVANCED HELICOPTER COCKPIT DESIGN

G. L. COHILL, D. D. STROTHER, and H. B. HENDERSON (Texas Instruments, Dallas, Tex.) *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 9 p Aug. 1984 Avail: NTIS HC A13/MF A01

Effective operation and survival in the battlefield of the future can impose great demands on helicopter weapon systems and the crews who manage them. Among these are: time to detect and respond to threats and targets; ability to integrate many types of sensor data and assess the intelligence portrayed by these sensors; and requirements for highly trained systems management personnel who can process highly technical information while operating in the very demanding NOE environment. Helicopter cockpit designs for the future and how crew performance can be improved are discussed and subsystems are addressed which can improve human performance. Sensor fusion systems, related misconceptions and their proposed use are highlighted. It is shown that the fused system is more reliable, less costly, lighter, and has more performance potential. System fusion provides a way to unload the harried system operator and assure mission success at a cost/performance ratio that decreases proportionally with overall system complexity. A.R.H.

Deutsche Forschungs- und Versuchsanstalt fuer N85-16820# Luft- und Raumfahrt, Brunswick (West Germany). FLIGHT RESEARCH ON VISUSL AIDS AND NAVIGATION EQUIPMENT FOR HELICOPTER LOW-LEVEL FLIGHT AT NIGHT

R. BEYER In AGARD Helicopter Guidance and Control Systems for Battlefield Support 8 p Aug. 1984 refs

Avail: NTIS HC A13/MF A01

An avionic/optronic system comprising night goggles, electronic head down display and Doppler navigation was tested in a Bo 105 helicopter in low level flight at night. Particular emphasis was given to the assessment of system performance and pilot workload. The results obtained as well as the methods and procedures applied are discussed in a way that similar experiments in the future may benefit from the outcome. Author

N85-16821*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

DEVELOPMENT AND FLIGHT TEST OF A HELICOPTER COMPACT, PORTABLE, PRECISION LANDING SYSTEM CONCEPT

J. S. BULL, G. R. CLARY, T. J. DAVIS, and J. P. CHISHOLM (Sierra Nevada Corp., Reno) In AGARD Helicopter Guidance and Control Systems for Battlefield Support 8 p Aug. 1984 refs Previously announced as N84-24566

Avail: NTIS HC A13/MF A01 CSCL 01D

An airborne, radar based, precision approach concept is being developed and flight tested as a part of NASA's Rotorcraft All-Weather Operations Research Program. A transponder based beacon landing system (BLS) applying state of the art X band radar technology and digital processing techniques, has been built and is being flight tested to demonstrate the concept feasibility. The BLS airborne hardware consists of an add on microprocessor, installed in conjunction with the aircraft weather/mapping radar, which analyzes the radar beacon receiver returns and determines range, localizer deviation, and glide slope derivation. The ground station is an inexpensive, portable unit which can be quickly deployed at a landing site. Results from the flight test program show that the BLS concept has a significant potential for providing rotorcraft with low cost, precision instrument approach capability in remote areas. Author

N85-16868*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

REFERENCE ENERGY-ALTITUDE DESCENT GUIDANCE: SIMULATOR EVALUATION

K. H. ABBOT and C. E. KNOX Jan. 1985 39 p refs (NASA-TP-2383; L-15800; NAS 1.60:2383) Avail: NTIS HC A03/MF A01 CSCL 01D

Descent guidance was developed to provide a pilot with information to ake a fuel-conservative descent and cross a designated geographical waypoint at a preselected altitude and airspeed. The guidance was designed to reduce fuel usage during the descent and reduce the mental work load associated with planning a fuel-conservative descent. A piloted simulation was conducted to evaluate the operational use of this guidance concept. The results of the simulation tests show that the use of the guidance reduced fuel consumption and mental work load during the descent. Use of the guidance also decreased the airspeed error, but had no effect on the altitude error when the designated waypoint was crossed. Physical work load increased with the use of the guidance, but remained well within acceptable levels. The pilots found the guidance easy to use as presented and reported that it would be useful in an operational environment. Author N85-16869*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

A COCKPIT-DISPLAY CONCEPT FOR EXECUTING A MULTIPLE GLIDE-SLOPE APPROACH FOR WAKE-VORTEX AVOIDANCE T. S. ABBOTT Feb. 1984 44 p refs

(NASA-TP-2386; L-15852; NAS 1.60:2386) Avail: NTIS HC A03/MF A01 CSCL 01D

A piloted simulation study was undertaken to determine the feasibility of utilizing a forward-looking display to provide information that would enable aircraft to rredue their in-trail separation interval, and hence increase airport capacity, through the application of multiple glide-path approach techniques. The primary objective of this study was to determine whether information could be satisfactorily provided on a head-up display (HUD) format to permit the pilot to conduct a multiple glide-slope approach while maintaining a prespecified in-trail separation interval. The tests were conducted in a motion-base cockpit simulator configured as a current-generation transport aircraft and included dynamic effects of the vortices generated by the lead aircraft. The information provided on the HUD included typical aircraft guidance information and the current and past positions of the lead aircraft. Additionally, the displayed information provided self-separation cues that allowed the pilot to maintain separation on the lead aircraft. Performance data and pilot subjective ratings and comments were obtained during the tests. The results of this study indicate that multiple glide-slope approaches, procedurally designed for vortex avoidance, are possible while maintaining pilot work load and performance within operationally acceptable limits. In general, it would seem that multiple glide-slope approaches are possible even under reduced in-trail separation conditions if the pilot is provided with adequate situational information. Author

Roval Aircraft Establishment, Farnborough N85-16870# (England).

ON-BOARD PROCESSING FOR LINESCAN SENSORS IN MINIATURE UNMANNED AIRCRAFT

J. A. C. BEATTIE 10 Jan. 1984 21 p refs (RAE-TM-SPACE-327; BR91753) Avail: NTIS HC A02/MF A01 The characteristics of linescan imagery are identified, and for those suitable for on-board processing in unmanned aircraft, the parameters and limits of operation are shown. Bandwidth reduction and information extraction may be enhanced or supplemented by on-board processing to prefilter the data for target detection and target motion detection. Full use of automatic target detection can only be made in conjunction with a navigation system to give ground coordinates for the target data. Alternatively, navigation and air vehicle attitude data can be obtained from the on-board linescan image processor, given the appropriate sensor and Author (ESA) processing algorithms.

N85-16871# Rohde and Schwartz, Munich (West Germany). Unternehmensbereich Betriebsfunktechnik.

DEVELOPMENT, PRODUCTION AND TESTING OF CENTRAL CONTROL AND DISPLAY UNIT FOR HELICOPTERS Final Report, Dec. 1983

W. BRUECKNER Bonn Bundesministerium fuer Forschung und Technologie Oct. 1984 54 p In GERMAN; ENGLISH summary Sponsored by Bundesministerium fuer Forschung und Technologie

(BMFT-FB-W-84-039; ISSN-0170-1339) Avail: NTIS HC A04/MF A01; Fachinformationszentrum, Karlsruhe, West Germany DM 11

Central control of avionics systems is discussed. The individual control units monitoring avionics systems integrated in helicopters were replaced by a microprocessor controlled central control and display unit consisting of an alphanumeric display, a keypad for the entry of characters as well as softkeys for selecting the operating modes. A program was developed according to an operational philosophy complying with human engineering requirements. The unit was tested in flight and shows good Author (ESA) results.

N85-16872# VDO-Luftfahrtgeraete Werk Adolf Schindling G.m.b.H., Frankfurt (West Germany). Bereich Luftfahrt.

REALIZATION AND TESTING OF AN EXPERIMENTAL COLOR DISPLAY SYSTEM FOR GENERAL AVIATION HELICOPTERS AND AIRCRAFT Final Report, Apr. 1984

H. W. FISCHER, M. GROSSKOPF, and R. SCHOENNAGEL Bundesministerium fuer Forschung und Technologie Oct. Bonn 67 p In GERMAN; ENGLISH summary Sponsored by 1984 Bundesministerium fuer Forschung und Technologie

(BMFT-FB-W-84-042; ISSN-0170-1339) Avail: NTIS HC A04/MF A01; Fachinformationszentrum, Karlsruhe, West Germany DM 14

An experimental color display system, consisting of a 5 x 5 in monitor with cathode ray tube and a computer/symbol generator, was built and installed in a BO 105 helicopter for testing. The equipment was developed by modification of the cockpit components of the Airbus A 310 in order to reduce costs. For the tests all indicators required for flight were integrated in a compact and comprehensive way in one display. Owing to the good results of the tests with one display, the system was extended (hardware and software) by a second display for presenting all engine data. Author (ESA)

07 AIRCRAFT PROPULSION AND POWER

Includes prime propulsion systems and systems components, e.g., gas turbine engines and compressors; and on-board auxiliary power plants for aircraft.

A85-19453# ANALYSIS

OF COUNTER-ROTATING PROPELLER PERFORMANCE

F. J. DAVENPORT, J. L. COLEHOUR (Boeing Commercial Airplane Co., Seattle, WA), and J. S. SOKHEY (General Electric Co., Aircraft Engine Business Group, Evendale, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 14 p. refs

(AIAA PAPER 85-0005)

The paper discusses calculation of the performance of counter-rotating propellers, assuming quasi-steady interference effects between rotors. Both lifting-line ('strip theory') and three-dimensional rotating-coordinate Euler-equation methods are considered. It is argued that the much simpler strip-theory method can give useful results even for swept blades that are partially supersonic, by using 'synthetic' section data that implicitly include sweep and supersonic-flow effects. Calculations for a 5+5-blade counter-rotating propeller indicate 6 percent better efficiency at 35 percent higher design power loading than an 8-blade single-rotation rotor having similar planform and profiles. Euler-equation solutions of counter-rotating propeller flows are calculated by enforcing 'inlet' and 'exit' flow properties at a pair of mesh surfaces approximating the location of the interfering rotor. Stable and reasonable solutions are obtained, although loadings appear higher than would be expected for a given pitch setting. The difference is attributed to the neglect of viscosity. Author

262

A85-19509*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

COMPUTATIONAL THERMO-FLUID **DYNAMICS** CONTRIBUTIONS TO ADVANCED GAS TURBINE ENGINE DESIGN

R. W. GRAHAM, J. J. ADAMCZYK, and H. E. ROHLIK (NASA, Lewis Research Center, Cleveland, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. Previously announced in STAR as N85-10069. refs

(AIAA PAPER 85-0083)

The design practices for the gas turbine are traced throughout history with particular emphasis on the calculational or analytical methods. Three principal components of the gas turbine engine will be considered: namely, the compressor, the combustor and the turbine. B.W.

A85-19525#

ZONAL COMPUTATIONAL APPROACH TO THRUST AUGMENTOR OPTIMIZATION

T. S. LUND, D. A. TAVELLA, and L. ROBERTS (Stanford University, Stanford, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs

(AIAA PAPER 85-0110)

A viscous-inviscid interaction methodology based on a zonal description of the flowfield is developed as a means of predicting the performance of two-dimensional thrust augmenting ejectors. An inviscid zone comprising the irrotational flow about the device is patched together with a viscous zone containing the turbulent mixing flow. The inviscid region is computed by a higher order panel method, while an integral method is used for the description of the viscous part. A non-linear, constrained optimization study is undertaken for the design of the inlet region. In this study, the viscous-inviscid analysis is complemented with an algebraic penalty function to account for flow separation. The thrust-based Reynolds number as well as the free stream velocity are shown to be important parameters in the design of a thrust augmentor inlet.

Author

A85-19615#

REAL GAS EFFECTS IN ADVANCED TECHNOLOGY ENGINES W. E. SIMPKIN and C. A. CORBETT (LTV Aerospace and Defense American Institute of Aeronautics and Co., Dallas, TX) Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 6 p. refs

(AIAA PAPER 85-0252)

The results of cycle analyses of high temperature turbine and ramjet engines using several high energy density fuels show traditional engine performance computer programs can be misleading. Engine performance using heavy hydrocarbon or slurry fuels with 3500 F burner temperatures requires a direct evaluation of the thermodynamic properties of the combustion gases to adequately predict fuel consumption and specific thrust. A combustion thermochemistry routine was integrated into the engine cycle analysis routine to evaluate all hot gas properties. This approach accounts for gas species physical and chemical changes during the expansion process on equilibrium, frozen or partially frozen basis as appropriate. SFC error using heating value and conventional cycle analysis programs as great as 25 percent were observed. Specific thrust errors were as great as 10 percent.

Author

A85-19616#

AIRCRAFT TURBOJET ENGINE MODELING USING ARTIFICIAL INTELLIGENCE TECHNIQUES

R. RAJAGOPALAN (IBM Corp., Federal Systems Div., Houston, TX) and S. SIDDIQI (Embry-Riddle Aeronautical University, Daytona Beach, FL) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 14 p. refs

(AIAA PAPER 85-0253)

An attempt is made to demonstrate the feasibility of qualitatively modeling the operation of a turbojet engine. This falls under the area of qualitative reasoning in the field of artificial intelligence. The engine is qualitatively represented as a causal model consisting of pairs of operationally related engine parameters such as rpm, pressure ratio, etc. The computer simulation models the change from a given steady-state engine operation point due to changes in engine input parameters such as airspeed, fuel flow, etc. The simulation propagates only the sign of the derivative, not the quantity of the parameter. This is done using list-processing techniques developed in artificial intelligence. At the conclusion of the simulation, it is possible to predict whether there is an increase or decrease in thrust due to input change. The resulting state of the engine is checked to determine whether any operational limits may possibly have been exceeded. The model also possesses the capability to explain the results of the simulation, thus providing a training tool for engine operators. Author

A85-19671#

SFRJ SIMULATOR RESULTS - EXPERIMENT AND ANALYSIS IN COLD FLOW

J. RICHARDSON, W. A. DEGROOT, J. I. JAGODA, R. E. WALTERICK, J. E. HUBBARTT, and W. C. STRAHLE (Georgia Institute of Technology, Atlanta, GA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(Contract AF-AFOSR-83-0356)

(AIAA PAPER 85-0329)

This paper presents laser based experimental results and analytical results on two-dimensional backward facing step flows with mass injection from the bottom wall behind the step. The facility simulates the flowfield in the flame stabilization region of a solid fueled ramjet. Measured are two components of velocity and shear stress with and without secondary air injection. The same quantities are calculated for foreign gas injection. The most notable effect of blowing, both experimentally and analytically, is the appearance of a second recirculation zone. Analytically and experimentally, it is found that the general size of the main recirculatory region diminishes with increased blowing rate, and blowoff of the recirculation zone can occur at relatively low blowing rates. This indicates that flame stabilization may be strongly affected by the actual blowing rate in an SFRJ.

A85-19710#

BENEFITS AND COSTS OF POWERED ENGINE SIMULATION AT LOW SPEEDS

W. BURGSMUELLER and J. SZODRUCH (Messerschmitt-Boelkow-Blohm GmbH, Bremen, West Germany) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. Research supported by the Bundesministerium fuer Forschung und Technologie. refs

(AIAA PAPER 85-0381)

The applications and benefits of using a turbo-powered simulator (TPS) for studying low speed, one-engine-out flight are discussed. The TPS technique can be employed in a wind tunnel to examine conditions where jet interference effects are important. Comparisons may be made between predictions and experimental data on the mixing of the primary and secondary jets in the engine wake and the flow over the wing. The TPS method costs 75 percent more to perform than through flow nacelle tests. However, if a one percent drag reduction is obtained, then the TPS tests are paid back 2.5 times due to the high resolution of the data on drag increments. Likewise, a one percent hike in the mean take-off weight would return the TPS costs 3.5 times. M.S.K.

A85-19801*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

PREDICTED PERFORMANCE BENEFITS OF AN ADAPTIVE DIGITAL ENGINE CONTROL SYSTEM ON AN F-15 AIRPLANE F. W. BURCHAM, JR., L. P. MYERS, and R. J. RAY (NASA, Ames Research Center, Flight Research Facility, Edwards, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (AIAA PAPER 85-0255)

The highly integrated digital electronic control (HIDEC) program will demonstrate and evaluate the improvements in performance and mission effectiveness that result from integrating engine-airframe control systems. Currently this is accomplished on the NASA Ames Research Center's F-15 airplane. The two control modes used to implement the systems are an integrated flightpath management mode and an integrated adaptive engine control system (ADECS) mode. The ADECS mode is a highly integrated mode in which the airplane flight conditions, the resulting inlet distortion, and the available engine stall margin are continually computed. The excess stall margin is traded for thrust. The predicted increase in engine performance due to the ADECS mode is presented in this report.

A85-19877

MICROPROCESSOR CONTROL OF TURBOPROP ENGINES [RIZENI TURBOVRTULOVEHO MOTORU MIKROPROCESOROVYM REGULATOREM]

J. MUELLER Zpravodaj VZLU (ISSN 0044-5355), no. 4, 1984, p. 219-231. In Czech.

Results of tests conducted on a microprocessor controller for a turboprop engine are reported. The objective of the tests was to evaluate the potential of microprocessor control and to develop a basis for future design work. Results of the tests confirm that digital electronics provides an efficient means of engine control, with functional reliability remaining the principal problem. V.L.

A85-20060

ARMY, NASA RESEARCHING NEEDS FOR FUTURE ENGINE COMPONENTS

Aviation Week and Space Technology (ISSN 0005-2175), vol. 122, Jan. 14, 1985, p. 99, 103, 104.

Attention is given to the most promising alternatives under consideration in helicopter powerplant research programs being conducted by the U.S. Army's Aviation Systems Command and NASA. Basic engine designs under consideration are compound turbine-diesels and regenerative and recuperative cycle gas turbines. Component technology research is primarily concerned with high temperature materials, such as ceramics, and with variable area features for engine diffusers, nozzles, and inlet guide vanes. The compound turbine-diesel technology, although comparatively immature, promises very low specific fuel consumption, excellent partial power fuel economy, and lower exhaust temperatures, which minimize IR emissions in military helicopters. O.C.

A85-20061

EUROPEANS USING COMPOSITES, CERAMICS FOR ROTORCRAFT ENGINE IMPROVEMENTS

Aviation Week and Space Technology (ISSN 0005-2175), vol. 122, Jan. 14, 1985, p. 105-107, 110, 115.

An evaluation is made of French, West German, and British helicopter engine technology development trends. Typical of current efforts is the West German GNT 1 new technology gas generator for engines in the 1400-shp power class, which features a highly loaded, combined axial-centrifugal compressor, a reverse flow combustion chamber and a single stage transonic, cooled, compressor-driving turbine stage employing powder metallurgy-fabricated disks. Ceramic bearings are noted to be under investigation in both West Germany and Britain. In France, attention is being given to new materials for use in small turboshaft engines which will allow both higher operating temperatures and lower

•

production costs; ceramic components and coatings in engine hot sections are again prominent in these development programs.

0.C.

A85-20235#

SOME IMPROVEMENTS ON AN ANNULAR COMBUSTOR OF AI TYPE TURBOJET ENGINE

B. ZHANG, Y. HOU, and D. HUANG (Shenyang Aeroengine Co., Shenyang, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, Feb. 1984, p. 91-93. In Chinese, with abstract in English.

A85-20242#

DETERMINATION OF SURGING LINE OF TWO-SPOOL AXIAL FLOW COMPRESSOR WITH CROPPED FAN STAGES AT LOW SPEED BY USE OF PARALLEL COMPRESSOR THEORY

F. ZHONG and Z. LU (Jiaotong University, Shanghai, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, May 1984, p. 157-159. In Chinese, with abstract in English.

A85-20243#

EXPERIMENTAL INVESTIGATION OF BACKSWEPT CENTRIFUGAL COMPRESSOR IMPELLER. I

Z. DIAO, J. CHEN, X. CAO, Y. YU, E. WANG, and M. PANG (Chinese Academy of Sciences, Institute of Engineering Thermophysics, Beijing, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, May 1984, p. 160-163. In Chinese, with abstract in English. refs

Tests of an impeller with 25-deg backsweep were conducted to establish stage and impeller characteristics. Tip speed of 380 m/sec was attained. Compared with a radial-discharge impeller which has the same diameter and inducer-blade profile, the stage eficiency was increased by 4 percent, and the operating range was improved significantly. The effect of reaction on the stage performance is analyzed. Test data on the slip factor and the energy-transfer coefficient are given. Author

A85-20822

MODERN MILITARY ENGINES. II

M. HIRST Air International (ISSN 0306-5634), vol. 28, Jan. 1985, p. 24-30.

A discussion is conducted concerning the design features and performance characteristics of state-of-the-art turbojets and turbofans for advanced military aircraft such as the Mirage 2000, B-1B, Tornado, and AMX. Attention is given to the progressive reduction of engine size and weight for a given thrust output over the last 30 years, as evidenced by the equivalent thrust J-79 (old) and F-404 (new). Similar advances are noted for specific fuel consumption reduction. The development histories that are related trace the genealogies of several engines, answering requirements that differ widely with respct to total thrust and mission profile, from a single 'gas generator' core, as in the case of the F-101 bomber engine and its F-110 fighter engine derivative. O.C.

A85-20867*# Texas A&M Univ., College Station.

ANALYTICAL DETERMINATION OF PROPELLER PERFORMANCE DEGRADATION DUE TO ICE ACCRETION T. L. MILLER (Sverdrup Technology, Inc., Middleburg Heights, OH), K. D. KORKAN (Texas A&M University, College Station, TX), and R. J. SHAW (NASA, Lewis Research Center, Cleveland, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 42 p. refs (Contract NAG3-242)

(AIAA PAPER 85-0339)

It is pointed out that ice accretion on aircraft produces an adverse effect on aircraft performance in terms of decreased lift and increased drag of the lifting surface. Ice on the surface of a propeller may also cause a decrease in thrust, increase in the required power, and a resultant decrease in propeller efficiency. During the past years, a number of attempts have been made to analyze the effects of ice accretion on both fixed wings and propellers. The present investigation is concerned with the development of a single user-oriented computer code which makes it possible to calculate propeller performance degradation due to ice accretion for specified flight conditions, atmospheric conditions, and propeller geometry. This development is based on a combination of several of the codes and correlations considered in earlier studies. G.R.

A85-21420

AERONAUTICAL GAS TURBINES. III [LES TURBINES A GAZ AERONAUTIQUES. III]

Air et Cosmos (ISSN 0044-6971), vol. 22, Dec. 22, 1984, p. 19, 43. In French.

The performance levels and applications of the family of gas turbine engines manufactured by Pratt-Whitney are surveyed. The company has built about 62,000 engines since 1948, 2/3 having been used on military aircraft. The newest series, the JT9D-7R4, has achieved 1,000,000 flight hours, powers the 767-200, 747-300, A 310-200, and the A 300-600, and will be installed on the A 310-300. The engine delivers 48,000-56,000 lb. thrust and has featured a MTBF of 40,000 hr. The new PW2000 and PW4000 families of engines feature single-crystal blades and high rpm operation. PW is also participating in development of the 21,000-23,000 lb. thrust V2500 engine for near term transport aircraft. The F100 engine is used in the F15 and F16 fighters and is being upgraded. The PW1120 is being flight tested as a replacement engine for all F-4 engines. Three other engines, including the PW3005 for the JVX, are under development.

M.S.K.

A85-21466#

TRENDS IN DIGITAL ENGINE CONTROL - INTEGRATION OF PROPULSION CONTROL WITH FLIGHT CONTROL AND AVIONIC SYSTEMS IN FUTURE MILITARY AND COMMERCIAL AIRCRAFT

E. S. ECCLES (Dowty & Smith Industries Controls Ltd., Cheltenham, Glos., England) IN: Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 . London, Royal Aeronautical Society, 1984, 9 p. Research supported by the Ministry of Defence of England. refs

This paper discusses future trends in engine control and addresses the integration of flight control and propulsion control both in commercial and in future advanced military aircraft. Such aircraft may employ sustained supersonic cruise and maneuvering flight, thrust vectoring and extensive variable geometry features. The paper outlines the factors which force the integration of systems, the benefits hoped for and the status of current work. It discusses the effects of integration on inter-system and inter-organizational interfaces and the methods and technologies needed to achieve the ends being sought within anticipated timescales. Author

A85-21682

PREDICTION OF PERFORMANCE OF AIRCRAFT GAS TURBINES

L. L. DUNCKER Aeronautical Society of South Africa and South African Institute of Aeronautical Engineers, Journal (ISSN 0250-3786), vol. 5, no. 1, 1984, p. 46-51.

Attention is given to the means by which one can predict the steady state off-design performance of a single spool turbojet engine, using a computer simulation model. The performance characteristics of the individual components over a range of off-design conditions are generated through computerized analytical approaches, and can be verified by performing actual components tests. Components are linked together in such a way as to satisfy compatibility requirements. The determination of corresponding operating points on each component characteristic when the engine is running in equilibrium, at a specific off-design condition, is followed by consideration of equilibrium running lines and their change with flight altitude and Mach number.

A85-21839#

FLOWFIELD ANALYSIS OF LOW BYPASS RATIO TEST CELLS S. L. KROMER and D. A. DIETRICH (General Electric Co., Cincinnati, OH) Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. 1985, p. 99, 100. Abridged. Previously cited in Issue 06, p. 723, Accession no. A84-17999.

A85-21866*# Pennsylvania State Univ., University Park. EFFECTS OF FRICTION DAMPERS ON AERODYNAMICALLY UNSTABLE ROTOR STAGES

A. SINHA (Pennsylvania State University, University Park, PA) and J. H. GRIFFIN (Carnegie-Mellon University, Pittsburgh, PA) AIAA Journal (ISSN 0001-1452), vol. 23, Feb. 1985, p. 262-270. Previously cited in issue 14, p. 1976, Accession no. A83-32791. refs

(Contract NAG3-231)

A85-22231#

INFLUENCE OF BLOWING RATE AND INJECTION ANGLE ON THE PERFORMANCE OF A FILM-COOLED BLADE

G. N. RAO (Siddartha Engineering College, Vijayawada, India) and W. V. NABAR (Indian Institute of Technology, Bombay, India) Aeronautical Society of India, Journal (ISSN 0001-9267), vol. 36, May 1984, p. 129-135. refs

The effect of blowing rate and coolant injection angle on the efficiency of film-cooling of a turbine blade is studied experimentally, for constant values of the mainstream turbulence intensity, inlet Reynolds number, and the geometry and dimensions of the injection holes. Three rows of coolant-injection holes were cut on both sides of the blade. Coolant was injected at 30, 45, 90, and 30 x 45 (compound) degrees at blowing rates from 0.1 to 2.0. It is shown that the optimal value of the blowing rate, at which the cooling is most efficient, increases with the downstream distance, at a significantly higher rate of increase for the 45 and 30 x 45-degree injection angles. Surface curvature is also suggested to play an important role in cooling efficiency.

N85-15723 Department of the Air Force, Washington, D.C. MOUNTING CONSTRUCTION FOR TURBINE VANE ASSEMBLY Patent

D. S. WOLF, inventor (to Air Force) 16 Oct. 1984 4 p Supersedes AD-D009948

(AD-D011395; US-PATENT-4,477,222;

US-PATENT-APPL-SN-431435; US-PATENT-CLASS-415-138) Avail: US Patent and Trademark Office CSCL 21E

A turbine vane assembly of a gas turbine engine includes inner and outer shroud walls and a plurality of airfoil-shaped vanes extending between and connected at their opposite ends with the inner and outer shroud walls. The mounting construction of the vane ends to the respective shroud walls includes a plurality of recessed ledges defined in the shroud walls along respective ones of the ends of the vanes. Each ledge forms a gap between the respective wall and vane end extending from a trailing edge pressure side of the vane along the pressure side to a location approximately midway between the trailing and leading edges of the pressure side of the vane. The remainder of the vane end is rigidly connected to the respective shroud wall. Author (GRA)

N85-15724*# Tuskegee Inst., Ala. School of Engineering and Architecture.

AN IMPROVED COMPUTER MODEL FOR PREDICTION OF AXIAL GAS TURBINE PERFORMANCE LOSSES Final Report R. M. JENKINS Aug. 1984 119 p refs

(Contract NSG-3295)

(NASA-CR-174246; NAS 1.26:174246) Avail: NTIS HC A03/MF A01 CSCL 21E

The calculation model performs a rapid preliminary pitchline optimization of axial gas turbine annular flowpath geometry, as well as an initial estimate of blade profile shapes, given only a minimum of thermodynamic cycle requirements. No geometric parameters need be specified. The following preliminary design data are determined: (1) the optimum flowpath geometry, within mechanical stress limits; (2) initial estimates of cascade blade shapes; and (3) predictions of expected turbine performance. The model uses an inverse calculation technique whereby blade profiles are generated by designing channels to yield a specified velocity distribution on the two walls. Velocity distributions are then used to calculate the cascade loss parameters. Calculated blade shapes are used primarily to determine whether the assumed velocity loadings are physically realistic. Model verification is accomplished by comparison of predicted turbine geometry and performance with an array of seven NASA single-stage axial gas turbine configurations. B.W.

N85-15725*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

EFFECT OF STEADY-STATE TEMPERATURE DISTORTION ON INLET FLOW TO A HIGH-BYPASS-RATION TURBOFAN ENGINE

R. H. SOEDER, C. M. MEHALIC, and K. STANCIK (AFSC) Jan. 1985 32 p refs

(NASA-TM-86896; E-2369; NAS 1.15:86896) Avail: NTIS HC A03/MF A01 CSCL 21E

The effects of circumferential inlet temperature distortion on the flow characteristics between a distortion generator and a high bypass ratio turbofan engine and through its compression system were evaluated to support the effort to generate analytical models. The flow characteristics are defined by the inlet duct, the flow angles, and the total temperature, total pressure, and static pressure profiles in the inlet duct and through the fan and compressor. The effects of Reynolds number, rotor speed, and distortion extent are also considered. E.A.K.

N85-15729*# National Aeronautics and Space Administration. Hugh L. Dryden Flight Research Center, Edwards, Calif.

PREDICTED PERFORMANCE BENEFITS OF AN ADAPTIVE DIGITAL ENGINE CONTROL SYSTEM OF AN F-15 AIRPLANE Final Report

F. W. BURCHAM, JR., L. P. MYERS, and R. J. RAY Jan. 1985 11 p refs Prepared in cooperation with NASA, Ames Research Center

(NASA-TM-85916; H-1269; NAS 1.15:85916) Avail: NTIS HC A02/MF A01 CSCL 21E

The highly integrated digital electronic control (HIDEC) program will demonstrate and evaluate the improvements in performance and mission effectiveness that result from integrating engine-airframe control systems. Currently this is accomplished on the NASA Ames Research Center's F-15 airplane. The two control modes used to implement the systems are an integrated flightpath management mode and in integrated adaptive engine control system (ADECS) mode. The ADECS mode is a highly integrated mode in which the airplane flight conditions, the resulting inlet distortion, and the available engine stall margin are continually computed. The excess stall margin is traded for thrust. The predicted increase in engine performance due to the ADECS mode is presented in this report.

N85-15731# Pratt and Whitney Aircraft, West Palm Beach, Fla. Government Products Div.

IMPROVEMENT OF THE CORROSION RESISTANCE OF TURBINE ENGINE BEARINGS Interim Report, Aug. 1981 - Jul. 1983

J. H. MOHN, H. M. HODGENS, II, H. E. MUNSON (TRW, Inc., Jamestown, N.Y.), and W. E. POOLE Wright-Patterson AFB, Ohio AFWAL Feb. 1984 165 p Original contains color illustrations

(Contract F33615-81-C-2023)

(AD-A147430; PWA/GPD/FR-17952; AFWAL-TR-84-2014) Avail: NTIS HC A08/MF A01 CSCL 21E

This technical report encompasses the work accomplished in the first phase of a two-phase program aimed at developing an alternate material, fabrication technique, or material treatment for turbine engine mainshaft bearings with improved corrosion resistance compared to state of the art VIM-VAR M50. During Phase 1, five corrosion-resistant bearing candidates (armoloy-coated M50, nickel sputter-coated M50, wrought CRB7,

RSR565 and MRC2001) identified as the most promising were subjected to rolling contact fatigue, corrosion, hot hardness and wear screening tests. The phase concluded with selection of MCR2001 as the single most promising candidate for full-scale bearing fabrication and testing. In Phase 2 that candidate will be subjected to further full-scale bearing life and performance tests and a corrosion-resistant verification test. Author (GRA)

N85-15732# Naval Postgraduate School, Monterey, Calif. CONTROL SYSTEM DESIGN LANGUAGE IMPLEMENTATION OF A GAS TURBINE STARTING CONTROLLER M.S. Thesis R. P. RILEY Jun. 1984 124 p

(AD-A147896) Avail: NTIS HC A06/MF A01 CSCL 09B

This thesis investigates the feasibility and utility of the Computer System Design Language (CSDL) and its design environment. The primary purpose of this design system is to automatically design microprocessor-based controller prototypes given a description of the controller's behavior. CSDL is used to create a highly structured behavioral description which is used by the design environment to create a software and hardware listing. A generic gas turbine engine start malfunction controller is developed using CSDL and tested on a Prolog development system. GRA

N85-15733# Advisory Group for Aerospace Research and Development, Neuilly-Sur-Seine (France).

ENGINE CYCLIC DURABILITY BY ANALYSIS AND TESTING

Loughton, England Sep. 1984 271 p refs In ENGLISH and Conf. held in Lisse, Netherlands, 30 May - 1 Jun. FRENCH 1984

(AGARD-CP-368; ISBN-92-835-0362-7) Avail: NTIS HC A12/MF A01

Engine utilization and accelerated mission testing development; critical material characterization; life assessment methodologies; and component and engine cyclic testing are discussed. The current state-of-the-art in technolgical areas is related to improving engine life. The technical and economical problems of advanced cyclic testing in the development of engines are considered with focus on relationships between engine utilization and failure modes, accelerated mission testing development, critical material characteristics, component life assessment methods, recent results of component and engine cyclic testing, and future requirements.

N85-15735# Rolls-Royce Ltd., Bristol (England). MONITORING ENGINE THERMAL STRESSES

T. M. EDMUNDS and R. A. LAWRENCE In AGARD Eng. Cyclic Durability by Analysis and Testing 20 p Sep. 1984 refs Avail: NTIS HC A12/MF A01

The high performance and rapid response of modern military engines means that transient thermal stresses make a significant contribution to the fatigue life utilization of critical rotating components. This, coupled with the variability of actual usage, raises a requirement for calculating transient thermal stresses from flight recorded data. A computationally efficient procedure for meeting this requirement is described. The analysis is based on a simplified model of the heat transfer and mechanics of the engine that is tuned with results of more sophisticated finite difference and finite element computations. Applications to a engine disc are described using data collected by on-board recordings. The results are validated by comparisons with more detailed theoretical analyses - practical constraints preventing a direct measurement of in-flight stresses. The integration of the results into the overall lifting procedure is also briefly described. Author

N85-15736# Aeronautical Systems Div., Wright-Patterson AFB, Ohio.

ACCELERATED MISSION ENDURANCE TESTING (AMET)

W. R. TAYLOR In AGARD Eng. Cyclic Durability by Analysis and Testing 5 p Sep. 1984 refs Avail: NTIS HC A12/MF A01

The cost of ownership of gas turbine aircraft engines today makes it imperative that the development process produce a production engine that will minimize life cycle cost. This problem was recognized and one of the most significant changes that was made in the last 10 years is the incorporation of AMET into the development programs. In the past, engine designs were qualified for production release when it successfully completed a 150 hour model test. However, as these engines accumulated service time, problems arose that were not discovered in factory test. It was apparent that the durability of these engines were not well understood. In 1973, the US Air Force, Navy, and Detroit Diesel Allison incorporated a new test cycle in their TF41 engine development program that was representative of the ircraft usage. The success of this effort encouraged the incorporation test method into other engine development programs. Today, the US Air Force uses factory test cycles for design verification and qualification that were derived from known or projected aircraft usages. The background of mission related testing, test cycle derivation, data sources, key parameters, limitations and benefits will be discussed. Author

N85-15737# Turbomeca S. A. - Brevets Szydlowski, Bordes (France).

DESIGN AND TEST REQUIREMENTS FOR DEVELOPMENT OF **TODAY'S ENGINES [EXIGENCES DE CONCEPTION ET D'ESSAI** POUR DEVELOPPER LES MOTEURS D'AUJOURD'HUI]

J. FRESCO In AGARD Eng. Cyclic Durability by Analysis and Sep. 1984 In FRENCH Original language doc. Testing 14 p previously announced as N82-17205

Avail: NTIS HC A12/MF A01

To adapt to the ever greater safety and profitability requirements for transport aircraft, the engine must fulfill two functions which are often of an opposite nature: performance and durability. The combination of these two lines of force: performance (translated in terms of fuel consumption or power) and durability, lead to the final objective which is cost reduction. Today, from the beginning of a new engine, it is necessary to guarantee potentials that are of the same order, if not superior, to those of engines which have already accumulated thousands of flight hours. The different methods that permit achieving the durability objective are analyzed including how they are involved in engine design. Tests which best reproduce the damage phenomena are described, and some examples are given which relate particularly to small engines.

Transl. by A.R.H.

N85-15738# National Aerospace Lab. Amsterdam (Netherlands).

OVERVIEW OF THE AGARD SMP ACTIVITIES ON TURBINE ENGINE MATERIALS TECHNOLOGY IN THE 1972 - 1982 PERIOD

A. J. A. MOM In AGARD Eng. Cyclic Durability by Analysis and Testing 34 p Sep. 1984 refs

Avail: NTIS HC A12/MF A01

An overview of research on turbine engine technology over the last 10 years is given. These activities cover most of the material related aspects in gas turbine technology from the initial design stage up to the final retirement of components. The development and application of advanced materials; material properties and behavior; material processing and fabrication techniques; maintenance and repair; and life prediction methods are discussed. With respect to the advanced materials and fabrication techiques, attention is given to the directionally solidified in-situ composites, the ceramic materials and the powder metallurgy materials, and their different processing aspects. New fabrication techniques like hot isostatic pressing, superplastic forming and surface treatments are included. Furthermore the corrosion behavior and low cycle fatigue characteristics of engine materials, including methods to predict creep and fatigue behavior, e.g., the strain range partitioning method, are discussed. Finally, attention is given to maintenance, repair and life prediction of engine components. Emphasis is directed to the introduction of damage tolerance concepts to make a more economic use of inherently available component life than is presently done by the safe life philosphy. R.J.F.

N85-15741# Air Force Wright Aeronautical Labs., Wright-Patterson AFB, Ohio.

CUMULATIVE DAMAGE MODELING OF FATIGUE CRACK GROWTH

J. M. LARSEN and T. NICHOLAS *In* AGARD Eng. Cyclic Durability by Analysis and Testing 15 p Sep. 1984 refs Avail: NTIS HC A12/MF A01

Life predictions of turbine engine structural components utilize fracture mechanics principles to determine fatigue crack growth rates. Fatigue cracks grow under conditions of variable temperature, frequency, hold time, stress ratio, and stress level. At elevated temperatures, time dependent material behavior can play a significant role in the material behavior. Cumulative damage models must account for all these variables as well as interaction effects. The earliest modeling involved interaction schemes, and, primarily, time independent material behavior. More recent work focused on time dependence and creep fatigue interaction effects. A review of current modeling concepts and problems is presented. R.J.F.

N85-15742# National Aeronautical Establishment, Ottawa (Ontario). Structures and Materials Lab.

PROBLEMS AND POSSIBILITIES FOR LIFE EXTENSION IN GAS TURBINE COMPONENTS

A. K. KOUL, W. WALLACE, and R. THAMBURAJ (Carleton Univ., Ottawa) *In* AGARD Eng. Cyclic Durability by Analysis and Testing 32 p Sep. 1984 refs

Avail: NTIS HC A12/MF A01

Data showing the beneficial effects of hot isostatic processing on the stress rupture properties of new and service exposed Ni based superalloy turbine blades are presented. Creep design methods that are generally used to highlight the service induced degeneration effects are critically analyzed. A new life prediction method that systematically analyzes the creep degeneration effects with increasing service life is proposed. Results indicating the successful application of a damage tolerance based maintenance methodology in Canadian Forces J85 engine compressor and turbine discs are discussed. Possibilities of enhancing engine component durability through improved machining techniques and reheat treatments are also discussed.

N85-15743# Royal Aircraft Establishment, Farnborough (England). Materials and Engineering Research Div. DISC FATIGUE LIFE PREDICTIONS FOR GAS TURBINE

ENGINES W I EVANS M E E SMITH and C H H WILLIAMS //

W. J. EVANS, M. E. F. SMITH, and C. H. H. WILLIAMS In AGARD Eng. Cyclic Durability by Analysis and Testing 13 p Sep. 1984 refs

Avail: NTIS HC A12/MF A01

Safe cyclic lives for discs in gas turbine engines were determined. The current procedures which are based on a life-to-first-crack philosophy and, in Britain, require full scale component testing to establish a service safe life are reviewed. The limitations of this approach are highlighted. It is then suggested that an alternative method based on fatigue crack propagation should overcome some of the limitations. Before this alternative can be adopted, however, it is important to develop quantitative models for the types of crack that occur in engine discs. These cracks tend to be embedded, situated at stress concentration features and subjected to multiaxial stress fields. Some of the published work on such cracks is reviewed and the more relevant models detailed. An experimental program on the titanium alloy Ti-6-4 is then described in which the behavior of small cracks is evaluated for stress concentration features in bend specimens and model discs. R.S.F.

N85-15744*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

ENGINE CYCLIC DURABILITY BY ANALYSIS AND MATERIAL TESTING

A. KAUFMAN and G. R. HALFORD *In* AGARD Eng. Cyclic Durability by Analysis and Testing 12 p Sep. 1984 refs Previously announced as N84-18683

Avail: NTIS HC A12/MF A01 CSCL 21E

The problem of calculating turbine engine component durability is addressed. Nonlinear, finite-element structural analyses, cyclic constitutive behavior models, and an advanced creep-fatigue life prediction method called strainrange partitioning were assessed for their applicability to the solution of durability problems in hot-section components of gas turbine engines. Three different component or subcomponent geometries are examined: a stress concentration in a turbine disk; a louver lip of a half-scale combustor linear; and a squealer tip of a first-stage high-pressure turbine blade. Cyclic structural analyses were performed for all three problems. The computed strain-temperature histories at the critical locations of the combustor linear and turbine blade components were imposed on smooth specimens in uniaxial, strain-controlled, thermomechanical fatigue tests of evaluate the structural and life analysis methods. Author

N85-15745# Office National d'Etudes et de Recherches Aerospatiales, Paris (France).

LIFE PREDICTION AT HIGH TEMPERATURE UNDER MULTIAXIAL LOADING

G. CAILLETAUD and J. L. CHABOCHE In AGARD Eng. Cyclic Durability by Analysis and Testing Sep. 1984 refs Avail: NTIS HC A12/MF A01

The activities of ONERA concerning the life prediction of high temperature components are summarized. In the last few years, the viscoplastic finite element computer code EVPCYCL was developed which is suitable for any two-dimensional problem (plane stress or strain, axisymmetrical case). The code's main specificity is the choice of various possibilities concerning the consitiutive equations: cyclic calculations can be made with kinematic and isotropic hardening, with the introduction of a memory effect, etc. Graphic post-processors are available as well as a life prediction program that takes into account creep and fatigue damage.

Author

N85-15751# Pratt and Whitney Aircraft Group, West Palm Beach, Fla. Engineering Div.

VIEW OF FUTURE REQUIREMENTS FOR ENGINE CYCLIC DURABILITY BY ANALYSIS AND TESTING

T. E. FARMER *In* AGARD Eng. Cyclic Durability by Analysis and Testing 6 p Sep. 1984 refs

Avail: NTIŠ HC A12/MF A01

Future requirements of engine cyclic durability analysis and testing. These requirements must satisfy advancements in technology and configuration in a cost-effective manner. The importance are discussed of demonstrating engine durability is emphasized. It is essential that an integrated approach to durability verification be developed and involve component durability analysis, engine measured parameters, laboratory test and engine demonstrated capabilities. Automated analysis techniques must confidently relate test conditions to field operation; non-interference sensors and enhanced data acquisition systems are required for extended test periods; and engine testing must efficiently address sensitivities, operating limits and cyclic capabilities, Verified component durability prediction systems that are developed can reduce the number of required engine endurance tests. Through coordination of durability analysis, data acquisition and component demonstration testing, more complete knowledge of engine durability will be achieved in a cost-effective manner. B.W.

Massachusetts Inst. of Tech., Cambridge. Lab. N85-16873*# for Information and Decision Systems. MULTIVARIABLE FLIGHT CONTROL WITH TIME-SCALE

SEPARATION K. HAIGES May 1984 144 p refs

(Contract NGL-22-009-124)

(NASA-CR-174320; NAS 1.26:174320; LIDS-TH-1381) Avail: NTIS HC A07/MF A01 CSCL 20E

The design of a compensator to provide a multivariable closed-loop, feedback control system with bandwidth separated input-output groups is considered. The basic contribution is to analyze, improve, and illustrate the programmatically used closed-one-loop at-a-time design procedure and to investigate the attainable performance and robustness properties. The design example used is the AV-8A Harrier aircraft. The underlying philosophy employed in the Linear Quadratic Gaussian with Loop Transfer Recovery (LOG/LTR) design methodology. Author

Air Force Inst. of Tech., Wright-Patterson AFB, N85-16874# Ohio. School of Systems and Logistics.

THE APPLICATION OF A TECHNOLOGY INDEX TO AIRCRAFT TURBINE ENGINE COST ESTIMATING RELATIONSHIPS M.S. Thesis

W. P. SIMPSON, III and J. R. SIMS, JR. Sep. 1984 102 p (AD-A147701; AFIT/GSM/LSY/84S-25) Avail: NTIS HC A06/MF A01 CSCL 14A

This research attempts to develop a technological index based on selected characteristics of new products. The methodology employed to develop the index was adopted from the technological forecasting community, where it is accepted as a valid technique for quantifying technological change. Several indices were developed to measure the level of technology incorporated into the design and development of aircraft turbine engines. Each index was based on a different assumption about the expected time path of technological growth. The data set was restricted to the same engines used by Rand to develop a set of cost estimating relationships (CERs) for estimating the development cost to model qualification tests, production cost, and the total development cost of jet engines. Selected indices were then introduced into the Rand CERs to evaluate their impact as cost drivers and their relationship to the other variables in the equations. The application resulted in the technology indices being significant and valid cost drivers. GRA

N85-16875# Rolls-Royce Ltd., Derby (England). THE AIRCRAFT ENGINE OF THE FUTURE

J. F. COPLIN 10 Sep. 1984 37 p Presented at British Assoc. for the Adv. of Sci., Norwick, England 10-14 Sep. 1984 (PNR-90226) Avail: NTIS HC A03/MF A01

Quieter, simpler, and more efficient aircraft engines designed using computers, and built in automated factories, are predicted. Ceramic blades and mixed flow compressors are discussed.

Author (ESA)

08

AIRCRAFT STABILITY AND CONTROL

Includes aircraft handling gualities; piloting; flight controls; and autopilots.

A85-19498#

A LONGITUDINAL STABILITY AUGMENTATION SYSTEM FOR A TILT ROTOR AIRCRAFT

C. DABUNDO and M. D. NEARY (Drexel University, Philadelphia, PA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs (AIAA PAPER 85-0072)

The Army/NASA/Bell XV-15 is a twin engine, tilt-rotor aircraft that combines the VTOL capability of the helicopter with the cruise capability of a fixed wing aircraft. The tilt-rotor's unique use of helicopter rotors as opposed to fixed props allows for unconventional control stabilization in forward flight. The success of the tilt-rotor is directly related to its cost effectiveness, which can be improved by increasing its efficiency and payload capacity. The efficiency and payload capacity of the tilt-rotor can be increased by reducing the area of the horizontal stabilator which in effect reduces drag and weight. Drag can be further reduced by decreasing the aircraft's static margin. Unfortunately, these configuration changes render the aircraft's longitudinal dynamics unstable, and thus create a need for a longitudinal stability augmentation system. An iterative process is developed in which the aircraft and control system parameters are varied to yield an optimum configuration which maximizes efficiency and payload capacity while retaining acceptable flying qualities. Author

-

A85-19583*# Kansas Univ., Lawrence. THEORY OF WING ROCK

C.-H. HSU and C. E. LAN (Kansas, University, Lawrence, KS) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs (Contract NAG1-134)

(AIAA PAPER 85-0199)

Wing rock is one type of lateral-directional instabilities at high angles of attack. To predict wing rock characteristics and to design airplanes to avoid wing rock, parameters affecting wing rock characteristics must be known. A new nonlinear aerodynamic model is developed to investigate the main aerodynamic nonlinearities causing wing rock. In the present theory, the Beecham-Titchener asymptotic method is used to derive expressions for the limit-cycle amplitude and frequency of wing rock from nonlinear flight dynamics equations. The resulting expressions are capable of explaining the existence of wing rock for all types of aircraft. Wing rock is developed by negative or weakly positive roll damping, and sustained by nonlinear aerodynamic roll damping. Good agreement between theoretical and experimental results is obtained. Author

A85-19585*# Waterloo Univ. (Ontario).

TRANSIENT MOTION OF HYPERSONIC VEHICLES INCLUDING TIME HISTORY EFFECTS

W. H. HUI (Waterloo, University, Waterloo, Ontario, Canada) and H. J. VAN ROESSEL American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs (Contract NAGW-575)

(AIAA PAPER 85-0201)

An analytic method is developed for calculating the transient pitching motion of a wedge in hypersonic flow, taking into account fully the interaction between its motion and the unsteady air flow passing it. The effects of past motion history on the present state of motion are shown to be caused by the wave reflection from the bow shock. In the Newtonian limit they are equivalent to that of an added moment of inertia. The time history effects generally tend to decrease the damping, rendering the oscillatory motion more persistent. Numerical examples are given. Author

A85-19656*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

DESIGNING A PRIORITY DRIVEN MULTI-FRAME RATE FLIGHT EXECUTIVE

R. SMITH-TAYLOR (NASA, Langley Research Center, Analysis and Computation Div., Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs

(AIAA PAPER 85-0309)

The Advanced Transport Operating System (ATOPS) project is a NASA operational research flight project which is concerned with upgrading the new generation of flight computers. In connection with this work, it becomes also necessary to reassess the adequacy of the flight executive and flight software. In the present discussion, attention is given to the ATOPS project upgrade, the operating flight system, the design criteria for the new flight executive, the implementation of the executive, a sample

real-time execution, a real-time debug and test tool, and several experiences which could be useful to others considering a similar exercise. G.R.

A85-19685*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

HYPERSONIC CHARACTERISTICS OF AN ADVANCED AEROSPACE PLANE

R. S. MCCANDLESS and C. I. CRUZ (NASA, Langley Research Center, Space Systems Div., Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs

(AIAA PAPER 85-0346)

A series of hypersonic wind-tunnel tests have been conducted in the NASA Langley Hypersonic Facilities Complex to obtain the and lateral-directional static longitudinal aerodynamic characteristics of an advanced aerospace plane. Data were obtained at 0 to 20 deg angles of attack and -3 to 3 deg angles of sideslip at Mach numbers of 6 and 10 in air and 20 in helium. Results show that stable trim capability exists at angles of attack near maximum lift-drag ratio (L/D). Both performance and stability exhibited some Mach number dependency. The vehicle was longitudinally unstable at low angles of attack but stable at angles of attack near and above maximum L/D. It was directionally unstable with positive dihedral effect. The rudder showed an inability to provide lateral-directional control, and removing the vertical tail resulted in increased directional instability. Analytical predictions of the static longitudinal aerodynamic coefficients gave relatively good comparisons with the experimental data. Author

A85-19828

INVESTIGATIONS FOR THE USE OF AN ACTIVE CONTROL IN AIRCRAFT [UNTERSUCHUNGEN ZUM EINSATZ EINES AKTIVEN BEDIENELEMENTS IM FLUGZEUG]

H. GUENTHER Braunschweig, Technische Universitaet, Fakultaet fuer Maschinenbau und Elektrotechnik, Dr.-Ing. Dissertation, 1984, 124 p. In German. refs

The design, simulation, and flight testing of active controls (ACs) for aircraft are reported and illustrated with drawings, photographs, graphs, block diagrams, and tables of results. The AC uses digitally determined continuous displacement of the stick zero point and proportional increases in stick resistance to give the pilot accurate kinesthetic information on the control error to be corrected. Comparative tests with trained pilots in a flight simulator show that an electrohydraulic system which permits switching from an active stick (which forces the pilot to adopt the strategy of a fully automatic flight-control system) to a passive stick (fly-by-wire pilot control without synthetic kinesthetic information) is effective in improving flight-path accuracy in complex approach maneuvers. These findings are confirmed by flight tests using an experimental installation in a Do-28 aircraft.

A85-19876

CALCULATION OF THE MINIMUM-TIME LOOP MANEUVER FOR JET AIRCRAFT [VYPOCET CASOVE NEJKRATSIHO PREMETU PROUDOVEHO LETOUNU]

J. KUDRNA Zpravodaj VZLU (ISSN 0044-5355), no. 4, 1984, p. 209-217. In Czech.

A mathematical model is presented which makes it possible to determine optimum changes of angle of attack and engine thrust with time resulting in a minimum-time loop maneuver that ends at a specified altitude or a specified speed. The loop maneuver time and the required lift coefficient and engine thrust can be specified at the design stage. In the general case, the optimum path of an aircraft is shown to consist of three different arcs; the optimum values of the control variables are functions of stage variables and Lagrange multipliers. V.L.

A85-20143* National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif. APPLICATION OF AN ADAPTIVE BLADE CONTROL

APPLICATION OF AN ADAPTIVE BLADE CONTROL ALGORITHM TO A GUST ALLEVIATION SYSTEM

S. SAITO (NASA, Ames Research Center, Moffett Field, CA) (European Rotorcraft and Powered Lift Aircraft Forum, 9th, Stresa, Italy, Sept. 13-15, 1983) Vertica (ISSN 0360-5450), vol. 8, no. 3, 1984, p. 289-307. Previously announced in STAR as N84-10079. refs

The feasibility of an adaptive control system designed to alleviate helicopter gust induced vibration was analytically investigated for an articulated rotor system. This control system is based on discrete optimal control theory, and is composed of a set of measurements (oscillatory hub forces and moments), an identification system using a Kalman filter, a control system based on the minimization of the quadratic performance function, and a simulation system of the helicopter rotor. The gust models are step and sinusoidal vertical gusts. Control inputs are selected at the gust frequency, subharmonic frequency, and superharmonic frequency, and are superimposed on the basic collective and cyclic control inputs. The response to be reduced is selected to be that at the gust frequency because this is the dominant response compared with sub- and superharmonics. Numerical calculations show that the adaptive blade pitch control algorithm satisfactorily alleviates the hub gust response. Almost 100 percent reduction of the perturbation thrust response to a step gust and more than 50 percent reduction to a sinusoidal gust are achieved in the numerical simulations. Author

A85-21465#

TRENDS IN DIGITAL FLIGHT CONTROL SYSTEMS

K. W. ROSENBERG and A. R. HEAPS (Marconi Avionics, Ltd., Combat Aircraft Controls Div., Rochester, Kent, England) IN: Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 . London, Royal Aeronautical Society, 1984, 6 p.

Attention is given to current and projected trends in the design requirements of Digital Flight Control Systems which seek to enhance system capabilities through the electronic linking of the various automatic piloting aids. The piloting aids have, over years of development, reached high levels of complexity in order to meet the demands of both lower inherent stability in aircraft configurations and enhanced maneuvering degrees-of-freedom. A discussion is conducted concerning integrated system architecture, flight control computers, airborne sensors, and software design.

O.C.

A85-21679

CHARACTERISTIC MOTIONS FOR SIMULATION OF POST-STALL MANOEUVRES AND FLIGHT INSTABILITIES

M. E. BEYERS (National Research Council of Canada, Unsteady Aerodynamics Laboratory, Ottawa, Canada) Aeronautical Society of South Africa and South African Institute of Aeronautical Engineers, Journal (ISSN 0250-3786), vol. 5, no. 1, 1984, p. 20-34. refs

An approach to the problem of experimentally determining the aerodynamic characteristics of aircraft maneuvering in the nonlinear, post-stall flight regime is proposed. The importance of correctly representing the motion characteristics in unsteady aerodynamic measurements under these conditions is recognized; different approaches are indicated, depending on whether the flight is oscillatory or nonoscillatory (aperiodic) and nonplanar or near-planar. The requirements for captive-model experiments designed to yield the instantaneous dynamic-load histories of ramp-shaped intermittent motions and nonplanar oscillatory motions are discussed. The principle of 'orbital epicyclic motion' is introduced and an analysis of its potential for high-alpha nonplanar oscillatory experiments is presented. In the simulation of complex, nonplanar maneuvers an approach is suggested based on complementing the captive-model experiments with wind tunnel free-flight studies of models trimmed at high alpha. Author

A85-21681

A_GLOBAL_TECHNIQUE_FOR AIRCRAFT-STABILITY-AND CONTROL ANALYSIS

M. H. LOWENBERG (Council for Scientific and Industrial Research, National Institute for Aeronautics and Systems Technology, Pretoria, Republic of South Africa) Aeronautical Society of South Africa and South African Institute of Aeronautical Engineers, Journal (ISSN 0250-3786), vol. 5, no. 1, 1984, p. 41-45. refs

Bifurcation Analysis and Catastrophe Theory Methodology (BACTM) can both explain and predict the limit cycles, hysteresis effects, and discontinuous motion exhibited by high performance aircraft in their high angle-of-attack dynamics. BACTM yields quantitative global stability information, and can contribute to control system design, stability augmentation, dynamic stability envelope determination, aircraft dynamic model structure design, and safer piloting procedures. BACTM's complete, six-degree-of-freedom flight mechanics equations constitute an autonomous dynamical system which incorporates jump, hysteresis, and limit cycle behavior. O.C.

N85-15752*# National Aeronautics and Space Administration. Hugh L. Dryden Flight Research Center, Edwards, Calif.

MORE THAN YOU WANT TO KNOW ABOUT MAXIMUM LIKELIHOOD ESTIMATION Final Report

K. W. ILIFF and R. E. MAINE Jan. 1985 26 p refs Presented at AIAA Atmospheric Flight Mech. Conf., Seattle, 21-23 Aug. 1984 Prepared in cooperation with NASA, Ames Research Center

(NASA-TM-85905; H-1252; NAS 1.15:85905;

AIAA-PAPER-84-2070-CP) Avail: NTIS HC A03/MF A01 CSCL 01C

The maximum likelihood estimator has been used to extract stability and control derivatives from flight data for many years. Most of the literature on aircraft estimation concentrates on new developments and applications, assuming familiarity with basic estimation concepts. Some of these basic concepts are presented. The maximum likelihood estimator is briefly discussed and the aircraft equations of motion that the estimator uses. The basic concepts of minimization and estimation are examined for a simple computed aircraft example. The cost functions that are to be minimized during estimation are defined and discussed. Graphic representations of the cost functions are given to help illustrate the minimization process. Finally, the basic concepts are generalized, and estimation from flight data is discussed. Some of the major conclusions for the computed example are also developed for the analysis of flight data. B.W.

N85-15753# California Univ., Los Angeles. Dept. of Electrical Engineering.

FLUTTER CONTROL WITH UNSTEADY AERODYNAMIC MODELS Ph.D. Thesis

S. CHANG Oct. 1984 108 p

(Contract AF-AFOSR-0318-83)

(AD-A147858; AFOSR-84-1002TR) Avail: NTIS HC A06/MF A01 CSCL 20D

This dissertation deals with a generic problem for aircraft: control laws for flutter suppression. Until recently, the system frequency response was approximated by rational functions so that the finite-dimensional L-Q-R theory could be applied. However, discrepancies between theory and practice, especially in transient response, has led to renewed interest in the problem. It would appear the L-Q-R theory would need infinite dimensional state space models. In this research, we first develop a time-domain model for unsteady aerodynamic loads and then couple it with a lumped model for the structural dynamics. We show that the solutions to the resulting input-output system, characterized by integro-differential equations, can be endowed with a state space which is a reflexive Banach space, and the state equations have a unique semigroup solution. We go on to examine the input-output stability for such a system. We show that input-output stability need not imply stability of the states. By a suitable approximation of the Sears function near the origin, we show that infinite dimensional (L2) L-Q-R theory can be applied. We derive optimal

feedback control laws ensuring weak stability of the states, as well as input-output stability. GRA

N85-16048# Joint Publications Research Service, Arlington, Va. INVESTIGATION OF SEMIAUTOMATIC AIRCRAFT CONTROL PROCESSES EMPLOYING TIME REDUNDANCY IN ON-BOARD DIGITAL TRAJECTORY CONTROL COMPUTERS Abstract Only

S. M. FEDOROV, N. N. SUKHIKH, and M. Y. SMUROV In its USSR Rept.: Electron. and Elec. Eng. (JPRS-UEE-84-017) p 49 17 Dec. 1984 Transl. into ENGLISH from Izv. Vyssh. Ucheb. Zaved.: Priborostr. (Leningrad), v. 27, no. 8, Aug. 1984 p 20-24 Original language document previously announced in IAA as A85-10470

Avail: NTIS HC A06

Aircraft semiautomatic control processes are analyzed with allowance for the failure and recovery of the onboard computers using timer redundancy methods. The admissible time of computer recovery is estimated, and results of semifull scale simulation of the digital system are presented for different values of the discreteness period. B.J. (IAA)

N85-16814*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

A REVIEW OF US ARMY AIRCREW-AIRCRAFT INTEGRATION RESEARCH PROGRAMS

D. L. KEY and E. W. AIKEN *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 15 p Aug. 1984 refs

Avail: NTIS HC A13/MF A01 CSCL 01C

The desire of the Army for a one crew helicopter that can perform the scout and attack role is forcing the integration of handling qualities and mission management disciplines and concerns. Some recent studies and results in these disciplines are reviewed. The need for a more unified approach to support new helicopter development is described along with a plan to develop fundamental principles needed for efficient man machine interface design. R.S.F.

N85-16819# Rome Univ. (Italy).

HELICOPTER ACTIVE CONTROL WITH ROTOR BLADES RELAXATION

A. DANESI and A. DANESI *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 17 p Aug. 1984 refs

Avail: NTIS HC A13/MF A01

An active modal control for high performance combat helicopters in forward flight is presented. A gust alleviation control (G.A.C.) strategy based on the spectral data computed from the flexible blade structural mode of vibration measurements, is employed to relax, by appropriate longitudinal cyclic pitch modulation, the flat wise bending moments induced by environmental disturbances. The restoring cyclic pitch commands are derived processing the output data from an electro-optical laser sensor by means of a microprocessor performing the spectral power density real time computations; these data, obtained implementing a fast fourier transform algorithm and observed within a frequency window centered at the first bending mode frequency, are employed as a measure of the actual vibrational level existing on the blade. To reduce the helicopter rigid response sensitivity to the G.A.C. system actuators, its driving signals are applied to the longitudinal pitch decoupling unit making the helicopter attitude and vertical velocity component decoupled, the last one regulated by the collective pitch channel through a radioaltimeter closure. The effectiveness of the G.A.C. system is investigated by digital simulations. M.G.

N85-16876 Purdue Univ., Lafayette, Ind. TIME SERIES ANALYSIS OF CLOSED-LOOP PILOT VEHICLE DYNAMICS Ph.D. Thesis

D. J. BIEZAD 1984 275 p

Avail: Univ. Microfilms Order No. DA8423330

The off line development of linear discrete autoregressive models for man machine closed loop flight performance is presented. The development includes single input, single output (single channel) and multiple input, multiple output (multichannel) closed loop systems. Previous research is consolidated by extensive surveys of both single and multichannel closed loop modeling and is extended into a comprehensive joint autoregressive man machine identification process. In single channel closed loop tracking tasks, pilot manual control is modeled in terms of linear discrete transfer functions which are parsimonious and guaranteed staple. The transfer functions are found by applying a modified superposition time series generation technique to relatively short data records, approximately 25 seconds long. The resulting model is then validated and analyzed. Results from a piloted laboratory simulation of single and double integrator controlled elements (longitudinal axis) agree with previous research findings. The development of the multichannel identification process is also Dissert, Abstr. described.

N85-16877*# Systems Technology, Inc., Mountain View, Calif. MISSION-ORIENTED REQUIREMENTS FOR UPDATING MIL-H-8501. VOLUME 1: STI PROPOSED STRUCTURE Final Report

W. F. CLEMENT, R. H. HOH, S. W. FERGUSON, III, D. G. MITCHELL, I. L. ASHKENAS, and D. T. MCRUER Jan. 1985 150 p refs 2 Vol.

(Contract NAS2-11304)

(NASA-CR-177304-VOL-1: NAS 1.26:177304-VOL-1:

USAAVSCOM-TR-84-A-6; STI-TR-1194-1-1) Avail: NTIS HC A07/MF A01 CSCL 01C

The structure of a new flying and ground handling qualities specification for military rotorcraft is presented. This preliminary specification structure is intended to evolve into a replacement for specification MIL-H-8501A. The new structure is designed to accommodate a variety of rotorcraft types, mission flight phases, flight envelopes, and flight environmental characteristics and to provide criteria for three levels of flying qualities, a systematic treatment of failures and reliability, both conventional and multiaxis controllers, and external vision aids which may also incorporate synthetic display content. Existing and new criteria were incorporated into the new structure wherever they could be substantiated. R.S.F.

N85-16878*# Systems Technology, Inc., Mountain View, Calif. MISSION-ORIENTED REQUIREMENTS FOR UPDATING MIL-H-8501. VOLUME 2: STI BACKGROUND AND RATIONALE Final Report

W. F. CLEMENT, R. H. HOH, D. G. MITCHELL, and S. W. FERGUSON, III Jan. 1985 113 p refs 2 Vol.

(Contract NAS2-11304)

(NASA-CR-177304-VOL-2; NAS 1.26:177304-VOL-2;

USAAVSCOM-TR-84-A-6; STI-TR-1194-1-2) Avail: NTIS HC A06/MF A01 CSCL 01C

A supplement to the structure of a new flying and ground handling qualities specification for military rotorcraft structure is presented in order to explain the background and rationale for the specification structure, the proposed forms of criteria, and the status of the existing data base. Critical gaps in the data base for the new structure are defined, and recommendations are provided for the research required to address the most important of these gaps. R.S.F. N85-16879# Air Force Inst. of Tech., Wright-Patterson AFB, Ohio.

DESIGN OF A DIGITAL RIDE QUALITY AUGMENTATION SYSTEM FOR COMMUTER AIRCRAFT Ph.D. Thesis, Kansas Univ.

T. A. HAMMOND 1984 379 p

(AD-A148233; AFIT/CI/NR-84-84D) Avail: NTIS HC A17/MF A01 CSCL 01D

This project was initiated based on the goal of making the ride of the commuter aircraft as smooth as the ride experienced on the major commercial airliners. The objectives of this project were to design a digital, longitudinal mode ride quality augmentation system (RQAS) for a commuter aircraft, and to investigate the effect of selected parameters on those designs. The initial stage of this research was the development of an interactive control augmentation design (ICAD) program for use in the design and evaluation of the candidate RQASs. This computer aided design program included both optimal and classical design approaches for either continuous or digital systems, and provided data for analyses in both the time and frequency domains. Both optimal and classical RQAS designs were generated for the five flight conditions selected as representative of a typical commuter mission, using a Cessna 402B. These RQASs used direct lift flaps and the elevator for control of the longitudinal accelerations. The design parameters selected include the sample time, computation delay time, servo bandwidth, and the flap and elevator control power. Optimal and classical point designs, based on the nominal design parameters, are presented for all five flight conditions. Parametric analyses for all five flight conditions for both the optimal and classical designs are also presented. GRA

N85-16880# Naval Research Lab., Washington, D. C. USING THE CONTROL SYSTEM DESIGN ENVIRONMENT IN THE DESIGN OF A DATA LINK RECEIVER UNIT FOR THE COAST GUARD HH-65A HELICOPTER M.S. Thesis F.S. FOX Jun 1984 166 p

F. S. FOX Jun. 1984 166 p (AD-A148624) Avail: NTIS HC A08/MF A01 CSCL 17B

This thesis is an attempt to prove the value of the Control System Design Environment by designing a shipboard or ground-based data link receiver to communicate with the data link installed in the Coast Guard HH-65A helicopter. The Control System Design Environment was intended to allow a designer to use a high-level language to describe the required inputs and outputs of a system. This high-level language, the Control System Design Language (CSDL) is translated into a list of primitives by a Pascal program, CSDL.PAS. The primitive list is then compiled into assembly language by a FORTRAN program, NEWCSDL.FOR. The final output includes the hardware and software lists to build a controller that meets the designer's specifications. This particular project includes a project design much more ambitious than any previously attempted in the Control System Design Environment. Author (GRA)

N85-16881# Dornier-Werke G.m.b.H., Friedrichshafen (West Germany).

FLIGHT TEST OF THE OPEN LOOP GUST ALLEVIATION (OLGA) SYSTEM Final Report, Dec. 1983

H. BOEHRET, H. BUCHHOLZ, W. WAGNER, and H. WUENNENBERG Bonn Bundesministerium fuer Forschung und Technologie Oct. 1984 75 p refs In GERMAN; ENGLISH summary Sponsored by Bundesministerium fuer Forschung und Technologie

(BMFT-FB-W-84-038; ISSN-0170-1339) Avail: NTIS HC A04/MF A01; Fachinformationszentrum, Karlsruhe, West Germany DM 16

A gust alleviation system was applied to low wing loading and high aspect ratio aircraft in order to decrease gust induced vertical acceleration. An open loop gust alleviation system (OLGA) was realized. Gust angle is calculated from sensor signals and fed to the actuators which control the symmetric aileron as lift flaps and the horizontal stabilizer. Flight tests of the aileron rod control, for certification and parameter identification, for system optimization, and the demonstration of system efficiency show a substantial decrease in the gust induced vertical acceleration and pitch rate in the frequency range below 3 Hz. However, passenger comfort is far more determined by higher frequencies than expected. Problems are found by stimulating the natural frequencies of the aircraft structure. A fundamental improvement of system behavior is reached by implementation of specific notch filters.

Author (ESA)

09

RESEARCH AND SUPPORT FACILITIES (AIR)

Includes airports, hangars and runways; aircraft repair and overhaul facilities; wind tunnels; shock tube facilities; and engine test blocks.

A85-19270#

THE ACCURACY OF TRIALS WITH POWERED 1/2 MODELS IN THE S2MA WIND TUNNEL [PRECISION DES ESSAIS DE 1/2 MAQUETTES MOTORISEES A S2MA]

J. F. PIAT (ONERA, Centre d'Essais de Modane, Modane, Savoie, France) ONERA, TP, no. 1984-156, 1984, 22 p. In French. (ONERA, TP NO. 1984-156)

The fidelity of the scale-up of data gathered with compressed air turbo-powered simulations of commercial transport aircraft wing-nacelle configurations using a 1/2 model in the ONERA S2MA wind tunnel is assessed. The amount of drag induced on the wing is measured by a balance in the wall mount for the model and account can also be taken of the power produced by the jet and the pressure of the flow into the engine nacelle. It is found that the model faithfully causes flow-broadening behind the nacelle and jets. Defective data from short-term trials have been ameliorated by extending the trial duration to gather more data, although cross-checking is necessary for any conclusions to be drawn. The wind tunnel data are usually accurate to an average of 0.4 percent, with drag predictions being within 0.3 percent at a 76 percent level of certainty. M.S.K.

A85-19271#

TESTS OF AIR INLETS ON CIVIL AIRCRAFT [ESSAIS DE PRISES D'AIR D'AVION CIVIL]

P. WAGNER (ONERA, Centre d'Essais de Modane, Modane, Savoie, France) and J. C. RAYNAL (ONERA, Centre d'Essais de Fauga-Mauzac, Noe, Haute-Garonne, France) ONERA, TP, no. 1984-157, 1984, 55 p. In French. refs

(ONERA, TP NO. 1984-157)

The apparatus and techniques used in tests of turbojet air inlet configurations for engine nacelles on general aviation aircraft by ONERA are described. The trials are carried out to validate designs suitable for both landing and take-off flight at high angles of attack and for maximum efficiency cruise flight. Attention is given to disturbances in the flow once it enters the nacelle, the drag penalty imposed on the aircraft by the presence of the nacelle, limiting flow separation during low speed flight, and flow distortions caused by wind during low speed flight. The tests are performed in the S1MA and F1 wind tunnels. Up to 300 pressure sensors can be used in and around diffusers in the F1 tunnel, which is also equipped for investigations of separation occurrence in response to varying Re and Mach numbers up to 0.3. The S1MA wind tunnel permits velocity simulation up to Mach 0.9. The flow through a model nacelle is monitored with a rake within the inlet and before the compressor vanes. M.S.K.

-- . .

A85-19272#

TESTS, IN THE TRANSONIC REGIME, OF A MODEL MOTORIZED BY A BLOWING TURBINE 23 CM IN DIAMETER (9 INCHES) IN THE SIMA WIND TUNNEL [ESSAIS, DANS LE DOMAINE TRANSSONIQUE, DE MAQUETTE MOTORISEE PAR TPS DE 23 CM DE DIAMETRE /9 POUCES/ DANS LA SOUFFLERIE SIMA]

J. P. BECLE (ONERA, Centre d'Essais de Modane, Modane, Savoie, France) ONERA, TP, no. 1984-158, 1984, 12 p. In French.

(ONERA, TP NO. 1984-158)

The test apparatus and procedures employed with a 23 cm diam blowing turbine to characterize engine nacelle/wing interactions in the S1MA wind tunnel are outlined. The turbine is fed compressed air and is mounted on a balance to measure associated forces and inclinations in transonic and low speed, high Re flows at temperatures up to 80 C. Air at pressures up to 9 bar flows through the inlet. The blowing turbine is mounted on the wing of a half model with a fuselage 6.4 m long. Tests are performed in Mach 0.5-0.82 flows at angles of attack of 0-4 deg and turbine speeds of 10,000-34,000 rpm. The half-model, being held by a balance, furnishes engine nacelle drag data when tested with and without the engine in equivalent flows. M.S.K.

A85-19402#

THEORETICAL STUDY OF BLOCKAGE EFFECT OF WIND-TUNNEL WALL ON WAKE OF TWO-DIMENSIONAL FLAT PLATE NORMAL TO PLANE WALL

S. OKAMOTO (Shibaura Institute of Technology, Tokyo, Japan) and T. OKAMOTO (Tokyo Institute of Technology, Tokyo, Japan) Japan Society for Aeronautical and Space Sciences, Transactions (ISSN 0549-3811), vol. 27, Nov. 1984, p. 134-144. refs

A theoretical study was made of the blockage effect of an upper wall of wind-tunnel on the wake behind a two-dimensional flat plate normal to a ground wall. The flow studied was an incompressible potential flow past a normal plate having a closed wake region in which a stationary vortex exists. The streamlines and surface-pressure distribution were obtained. From these results it was found that the drag of a normal plate increases and the closed wake region is reduced with an increasing ratio of plate height (H) to tunnel height (h), and the blockage effect can be ignored so long as the ratio H/h is less than 0.05.

A85-19403#

EXPERIMENTAL INVESTIGATION OF BLOCKAGE EFFECT OF UPPER WALL OF WIND-TUNNEL OF WAKE OF TWO-DIMENSIONAL FLAT PLATE NORMAL TO PLANE BOUNDARY

S. OKAMOTO (Shibaura Institute of Technology, Tokyo, Japan) Japan Society for Aeronautical and Space Sciences, Transactions (ISSN 0549-3811), vol. 27, Nov. 1984, p. 145-154. refs

This paper describes an experimental investigation on the blockage effect of an upper wall of wind-tunnel on the wake of a two-dimensional flat plate normal to a plane boundary in a uniform stream. The experiment was carried out in a 40 cm x 40 cm NPL type wind-tunnel having the working section of 2 m long. The distributions of velocities and static pressures of the flow field, the recirculation region behind a flat plate, the surface pressure and the drag coefficient of a flat plate, and the shear flow near the wall in the wake were measured and the results were discussed in comparison with those of the existing investigations and the theory.

A85-19456*# National Aeronautics and Space Administration. Marshall Space Flight Center, Huntsville, Ala.

STATUS OF WARM FOG DISPERSAL RESEARCH

V. W. KELLER (NASA, Marshall Space Flight Center, Atmospheric Sciences Div., Huntsville, AL) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 4 p. NASA-supported research. refs (AIAA PAPER 85-0010)

A new concept for dispersing warm fog is presented. This brute force technique uses large volume recycled water sprays.

Energy requirements for this technique are an order of magnitude less than those to operate a thermo-kinetic system. An important side benefit is the considerable emergency fire extinguishing capability it provides along the runway. Tests conducted to provide drop spectra measurements and temperature response measurements of suitable water sprays are described. Three mobile firefighting modules capable of spraying up to 630 I/s (10,000 gpm) to a height in excess of 50 m were utilized. Periodic operation of two parallel rows of nozzles in a heavy fog resulted in downwind-correlated increases in the visual range measured with a forward scatter visibility meter. Author

A85-19483#

VARIABLE-TEMPERATURE WATER TUNNEL FOR HIGH **REYNOLDS NUMBERS**

W. H. STAHL (University of Petroleum and Minerals, Dhahran, Saudi Arabia) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(AIAA PAPER 85-0051)

The possibility of using a water tunnel with variable fluid temperature to achieve high Reynolds numbers for hydrodynamic and aerodynamic testing is investigated. Characteristics of such a water tunnel are compared to those of a low-speed wind tunnel operating at normal conditions, on the basis of the same Reynolds number in both tunnels. The advantages offered by the variable-temperature water tunnel with regard to tunnel dimensions, power requirements, and observation times led to a preliminary design of a small pilot water tunnel with heating and cooling of the fluid, which is presented. The problem of cavitation is considered and found to be not very restrictive for testing practical configurations. Author

A85-19485*# Air Force Inst. of Tech., Wright-Patterson AFB. Ohio.

FREQUENCY RESPONSE OF A JET ENGINE TEST FACILITY AIR SUPPLY SYSTEM

M. E. FRANKE (USAF, Institute of Technology, Wright-Patterson AFB, OH) and M. L. ROSS (NASA, Johnson Space Center, Houston, TX; USAF, Institute of Technology, Wright-Patterson AFB, American Institute of Aeronautics and Astronautics, OH) Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs

(AIAA PAPER 85-0053)

The frequency response of a laboratory scale model of a portion of the air supply system of an engine test facility is obtained both experimentally and using one-dimensional, small-signal, distributed parameter theory. The effects of line terminations and mean flow are considered. Good agreement between experiment and theory is obtained. Predictions are extended to a full scale test facility air supply system operating under several possible test conditions. Author

A85-19486#

MACH-10 HIGH REYNOLDS NUMBER DEVELOPMENT IN THE NSWC HYPERVELOCITY FACILITY

R. A. KAVETSKY and J. A. F. HILL (U.S. Navy, Naval Surface Weapons Center, Silver Spring, MD) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p.

(AIAA PAPER 85-0054)

In order to obtain higher boundary layer transition on reentry body models, the hypervelocity test facility presently treated has undergone a development program which resulted in the achievement of a maximum Reynolds number of 20 million at Mach 10. Predictions of natural transition were verified during development program testing, and altitude simulation range has been increased. It is noted that an ablative 'flow restrictor' used to mitigate expansion waves created by diaphragm had to be designed to meet severe operating requirements with respect to both operating time and temperature. O.C.

A85-19497#

A STUDY OF THE FLOW RECIRCULATION PROBLEMS WITHIN AN ANECHOIC HOVER CHAMBER

M. LESCAULT and F. VILLANUEVA (U.S. Military Academy, West American Institute of Aeronautics and Astronautics. Point, NY) Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs (AIAA PAPER 85-0071)

Problems have been observed with apparent recirculation in an anechoic hover chamber at the NASA/Ames Research Center during certain tests of model rotor blades. Tests were performed in a 1/7 scale model of the chamber to identify the problem and investigate possible causes. A flow visualization study was conducted on two model rotors with different aspect ratios to examine two theories concerning the cause of the recirculation. The first theory is that empty space beneath the collector floor induces turbulence to occur which creates a high pressure region, causing the flow to seep back through the collector. The second theory involves blade tip vortices produced by the rotor. These tip vortices induce a velocity in the dead air beneath the floor that causes the flow to recirculate back through the collector. Results show that the theories each have some validity and additively appear to cause the recirculation problem. Author

A85-19512#

ENVIRONMENTAL TEST CAPABILITIES OF THE AIR FORCE MCKINLEY CLIMATIC LABORATORY

C. W. DRAKE (USAF, Climatic Laboratory, Eglin AFB, FL) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs (AIAA PAPER 85-0089)

Aircraft testing capabilities of the Air Force's Climatic Laboratory are outlined. The facility has chambers large enough for full-size aircraft to eliminate discrepancies sometimes arising between laboratory and field tests. A 3.2 million cubic feet Main Chamber is equipped to simulate up to 15 in. of rainfall per hour, winds to 60 mph, snow, solar radiation, 10-95 percent humidity, and temperatures from -65 to +165 F. Aircraft engines can be run up to full afterburner during the tests, with the aircraft strapped down by steel cables and the exhaust funneled from the building. Icing tests with frame sprays can be performed in another chamber, as can controlled snowfall rates or direct snow ingestion. A sun, wind, rain and dust chamber allows examinations of dust penetration into aircraft at any simulated latitude. The chamber can also be used to test aircraft reactions to blown sand. Finally, a salt fog facility permits testing for electrochemical corrosion, electrical effects due to salt deposits, and physical effects caused by clogging or binding of moving parts. M.S.K.

A85-19515# LIGHTNING SIMULATION FACILITIES IN THE UNITED STATES AND EUROPE

L. C. WALKO and J. L. HEBERT (USAF, Wright Aeronautical Laboratories, Wright-Patterson AFB, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p.

(AIAA PAPER 85-0093)

The use of sophisticated avionics systems and non-metallic structures has enhanced aircraft susceptibility to, and the need for protection from, the lightning threat. Some of the lightning aspects may be simulated and this has established lightning simulation as a valuable aid in aircraft design. This paper describes the lightning threat and existing lightning simulation standards. It overviews lightning simulation facilities in the United States and Europe. Author

A85-19577#--

AUTOMATED VISIBILITY MEASUREMENTS FOR AIRPORTS

J. T. BRADLEY and S. M. IMBEMBO (NOAA, Test and Evaluation Div., Sterling, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs

(AIAA PAPER 85-0191)

An algorithm has been developed which, when used with the input from a visibility sensor, can provide a responsive and representative visibility observation for pilots and other users. The algorithm enables a continuous weather watch to be provided which responds better to varying and rapidly changing visibility conditions. In conjunction with proper sensor siting, the technique provides an observation which is specific for the airport touchdown zone and is general for airport environs. Various visibility sensors have been evaluated for use with the developed algorithm. Results of sensor comparisons show that each type of measurement technique (extinction, forward scatter, and backscatter) has a typical response in various types of weather phenomena, which may necessitate some minor tradeoffs between requirements and sensor performance capabilities.

A85-19601*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

GENERALIZED ADAPTIVE-WALL WIND TUNNELS

S. S. DAVIS (NASA, Ames Research Center, Aerodynamics Research Branch, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs

(AIAA PAPER 85-0225)

Adaptive-wall technology is being seriously considered for many aeronautical wind tunnel applications. A new degree of freedom is introduced into adaptive-wall wind tunnels. It is shown that the adaptive control system used to adjust wall boundary conditions may be used to select a wide variety of flow fields. These flow fields, in turn, maybe directly related to many useful unconfined or semiconfined flows. The generalized adaptive-wall concept is demonstrated for both two- and three-dimensional flows using simple analytical techniques. Author

A85-19602#

IMPROVEMENTS IN LOW REYNOLDS NUMBER TESTING IN THE NSWC HYPERVELOCITY WIND TUNNEL NO. 9

E. R. HEDLUND and W. C. RAGSDALE (U.S. Naval Surface Weapons Center, Silver Spring, MD) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(AIAA PAPER 85-0226)

This paper discusses recent developments in the low Reynolds number testing capability in the NSWC Hypervelocity Wind Tunnel No. 9. Through improvements to the vacuum system and modified heater operation, the tunnel's freestream Reynolds number has been lowered to 50,000/ft. Pressure and temperature surveys of the flow revealed adequate test core area for testing. This paper also describes some unique force testing hardware as well as a flow discharge flow visualization technique which has been recently implemented. Author

A85-19603*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

STUDIES OF CONDENSATION EFFECTS ON AIRFOIL TESTING IN A TRANSONIC CRYOGENIC TUNNEL

R. M. HALL (NASA, Langley Research Center, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs (AIAA PAPER 85-0229)

In the context of an overall development of transonic, cryogenic wind tunnel technology, NASA has been investigating the onset of condensation effects in nitrogen gas. The temperature at which condensation occurs determines the minimum operating temperature (MOT) of cryogenic tunnels. The apparatus and airfoils are discussed, taking into account a description of the 0.3-m Transonic Cryogenic Tunnel (TCT), the drag rake, the airfoils, and

the_technique_used_for_determining_the_onset_of_condensation_ effects. Attention is also given to the types of nucleation processes, the relative sensitivity of drag rake and surface pressure measurements, correlations between data and theory, the prediction of minimum operating temperatures for the 0.3-m TCT, and MOT's for different tunnels. G.R.

A85-19618*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

MEASUREMENTS OF WATER FILM CHARACTERISTICS ON AIRFOL SURFACES FROM WIND-TUNNEL TESTS WITH SIMULATED HEAVY RAIN

E. C. HASTINGS, JR. and G. S. MANUEL (NASA, Langley Research Center, Subsonic Aerodynamics Branch, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs (AIAA PAPER 85-0259)

This paper discusses some of the surface water characteristics obtained during recent simulated heavy rain experiments conducted at the Langley Research Center. Water film distributions and discrete film thickness measurements on several model wings are discussed. The water film distributions on the upper surfaces are shown in photographs from cameras mounted above the models, and film thickness data are presented which were obtained using resistance sensors mounted flush with the upper and lower wing model surfaces. The paper also discusses potential sources of performance decrements indicated by the data. Author

A85-19655*# Research Triangle Inst., Hampton, Va. THE MISSION ORIENTED TERMINAL AREA SIMULATION (MOTAS)

P. B. NAFTEL (Research Triangle Institute, Hampton, VA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs (Contract NAS1-15992)

(AIAA PAPER 85-0308)

A new simulation facility is described in which flight management and flight operations research studies can be conducted in a highly realistic terminal area environment. The historical evolution and justification of the facility is discussed, along with the design configuration of the system hardware and software. Details are provided on the traffic management features of the terminal area model as well as the human controller and multicockpit interface capabilities. The facility is currently operational with two cockpit simulators, two air traffic control (ATC) stations, four pseudo pilot stations (PPS), a metering and spacing system of traffic flow control management, and terminal area models providing two route structure environments: area navigation (ŘNAV) for advanced-equipped aircraft and vectoring for conventionally-equipped aircraft. Plans for future experiments utilizing the facility are discussed. Author

A85-19659#

MODULAR SIMULATORS, THEIR FEASIBILITY, DESIGN, AND PROCUREMENT

S. SEIDENSTICKER (Logicon, Inc., Tactical and Training Systems Div., San Diego, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p.

(AIAA PAPER 85-0312)

The concept of modularity has enjoyed popular support and various degrees of successful implementation. The basis benefits of modularity are related to flexibility, independent construction, and modification possibilities. The present investigation is concerned with questions regarding a utilization of the concept of modularity in the case of flight simulators. An important requirement regarding such a utilization is related to the definition of the modules, primarily by function, but also by constraints and restrictions. Standards governing the design and implementation of the modules and interfaces must be set up and adhered to. Attention is given to impact on cost and development time, implementation approaches, interfacing modules, potential impact on technology, the program structure, a cockpit procedures trainer,

a mini-aero model, a mini-propulsion model, a cockpit module, an operational flight trainer, and the motion system. G.R.

A85-19661*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

THE ALTITUDE WIND TUNNEL (AWT) - A UNIQUE FACILITY FOR PROPULSION SYSTEM AND ADVERSE WEATHER TESTING

R. CHAMBERLIN (NASA, Lewis Research Center, Cleveland, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs (AIAA PAPER 85-0314)

A need has arisen for a new wind tunnel facility with unique capabilities for testing propulsion systems and for conducting research in adverse weather conditions. New propulsion system concepts, new aircraft configurations with an unprecedented degree of propulsion system/aircraft integration, and requirements for aircraft operation in adverse weather dictate the need for a new test facility. Required capabilities include simulation of both altitude pressure and temperature, large size, full subsonic speed range, propulsion system operation, and weather simulation (i.e., icing, heavy rain). A cost effective rehabilitation of the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) will provide a facility with all these capabilities.

A85-19662#

DEVELOPMENT OF THE UTA HIGH REYNOLDS NUMBER TRANSONIC WIND TUNNEL

D. R. WILSON and S. Y. CHOU (Texas, University, Arlington, TX) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs (AIAA PAPER 85-0315)

The development history, operational theory, support systems, and results of test section calibration studies of the UTA High-Reynolds Number Transonic Wind Tunnel are presented. The facility, first operated in January 1984, is a Ludwieg tube tunnel. The test section measures 7.3 by 9.15 inches and is 25.4 inches long; the porous walls are of conventional design with the porosity varied manually from 3.5 to 10 percent for wave cancellation in supersonic flows, and for partially alleviating wall interference effects. The air supply system consists of a low-pressure compressor providing a flow rate of 84 cu ft/min at a maximum pressure of 200 psig, and a high-pressure compressor providing a flow rate of 44 cu ft/min at 1000 psig. During the calibration procedures 500 psi transducers were used, restricting the lower operating limit to static pressure levels of 40 psi or greater. With the current data acquisition system the pressure signals are measured to within + or - 0.25 percent. Schematic and block diagrams are included. I T

A85-19678*# National Aeronautics and Space Administration. Flight Research Center, Edwards, Calif.

THE WESTERN AERONAUTICAL TEST RANGE OF NASA AMES RESEARCH CENTER

A. L. MOORE (NASA, Flight Research Center, Edwards, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 16 p. (AIAA PAPER 85-0316)

An overview of the Western Aeronautical Test Range (WATR) of NASA Ames Research Center (ARC) is presented in this paper. The three WATR facilities are discussed, and three WATR elements - mission control centers, communications systems, real-time processing and display systems, and tracking systems - are reviewed. The relationships within the NASA WATR, with respect to the NASA aeronautics program, are also discussed. Author A85-19709*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

ANALYTICAL AND PHYSICAL MODELING PROGRAM FOR THE NASA LEWIS RESEARCH CENTER'S ALTITUDE WIND TUNNEL (AWT)

J. M. ABBOTT, J. H. DIEDRICH, J. F. GROENEWEG, L. A. POVINELLI, L. REID, J. J. REINMANN, and J. R. SZUCH (NASA, Lewis Research Center, Cleveland, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 13 p. refs (AIAA PAPER 85-0379)

An effort is currently underway at the NASA Lewis Research Center to rehabilitate and extend the capabilities of the Altitude Wind Tunnel (AWT). This extended capability will include a maximum test section Mach number of about 0.9 at an altitude of 55,000 ft and a -20 F stagnation temperature (octagonal test section, 20 ft across the flats). In addition, the AWT will include an icing and acoustic research capability. In order to insure a technically sound design, an AWT modeling program (both analytical and physical) was initiated to provide essential input to the AWT final design process. This paper describes the modeling program, including the rationale and criteria used in program definition, and presents some early program results.

A85-19711#

A UNIVERSAL TURBOSHAFT ENGINE TEST CELL - DESIGN CONSIDERATIONS AND MODEL TEST RESULTS

A. I. KARAMANLIS, W. HOELMER, D. C. BELLOMY (General Electric Co., Aircraft Engine Business Group, Cincinnati, OH), R. J. FREULER, and J. D. LEE (Ohio State University, Columbus, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p.

(AIAA PAPER 85-0382)

Studies to determine the influence of test cell operational parameters on test cell aerodynamics and engine performance have been made on a scale model of a universal Turboshaft Engine Test Cell. Two engine simulators with different inlet airflow and exhaust system configurations were evaluated and results are presented and discussed. Acceptable and unacceptable test cell aerodynamics were demonstrated qualitatively by flow visualization techniques and quantified by detailed flow measurements. Author

A85-19878

HISTORY OF THE DEVELOPMENT AND MANUFACTURE OF FLIGHT SIMULATORS IN CZECHOSLOVAKIA AND THE REST OF THE WORLD [HISTORIE VYVOJE A VYROBY PILOTNICH SIMULATORU VE SVETE A V CESKOSLOVENSKU]

J. POKORNY (Rudy Letov, Prague, Czechosolovakia) Zpravodaj VZLU (ISSN 0044-5355), no. 5, 1984, p. 269-271. In Czech.

The history of flight simulators, from simple pilot training aids used in the early days of aviation to sophisticated flight simulators made possible with the development of microelectronics and computer technology, is reviewed. In particular, attention is given to the development and production of flight simulators in Czechoslovakia and specific problems that the Czechoslovakian manufacturers have to deal with. The need for a closer cooperation between the supplier and the customer as well as between various specialized manufacturing plants is emphasized. V.L.

A85-20122

BIG WIND AT TULLAHOMA

N. B. BYARS (USAF, Washington, DC) Air Force Magazine (ISSN 0730-6784), vol. 68, Jan. 1985, p. 78-82.

The Air Force's new Aeropropulsion Systems Test Facility (ASTF), scheduled to achieve initial operational capability in September 1985, is described. The facility accommodates the full mission profile of an air-breathing propulsion system at simulated speeds of up to Mach 3.8, at thrust levels of 75,000 lbs, and at altitudes up to 100,000 feet. The facility is designed for both free-jet testing and direct-connect testing, and provides real-time, simultaneous data collection and display. Furthermore, the advantages of free-jet testing, such as the ability to test compatibility of an engine with a particular airframe before the production has begun, are discussed. The ASTF is adapted for competitive engine testing and will be used for Joint Advanced Fighter Engine testing. It is suggested that with the ASTF for a laboratory an Advanced Tactical Fighter could well be an affordable and reliable aircraft. L.T.

A85-21422

THE MOST SPECTACULAR EQUIPMENT - ETW [LE PLUS SPECTACULAIRE DES EQUIPEMENTS - ETW1

J. MORISSET Air et Cosmos (ISSN 0044-6971), vol. 22, Dec. 22, 1984, p. 55-57. In French.

The European Transonic Wind Tunnel (ETW) will be built in the next 10 yr as a cooperative effort of four countries and will serve for tests of fixed wing aircraft, helicopter and missile designs. Preliminary design work for the ETW, which will be constructed in Cologne-Porz, began in 1977. The final design features a 2.4 x 2 m test channel, a -183 to +40 C temperature range, a 1.25-4.5 atm. pressure range, Mach 0.15-1.3 flow velocities, a maximum Re of 50 million and a 61,000 hp blower. A cryogenic pressurized mode was chosen to faithfully reproduce flight conditions with scale models, which will be supported on a dynamic, mobile balance equipped with a sting. The flow will be provided by liquid nitrogen at rates up to 200 kg/sec. A smaller version of the ETW was completed in the spring of 1984 in Amsterdam and is serving in definition of the operational technques for the ETW. M.S.W.

A85-21644

ACOUSTICAL GUIDELINES FOR NEW HELIPORTS

J. LEVERTON (Westland Inc., Arlington, VA) Vertiflite (ISSN 0042-4455), vol. 31, Jan.-Feb. 1985, p. 48-52.

The Helicopter Association International (HAI) program for the development of acoustical guidelines for heliports had as its basis the concept that total sound exposure due to helicopter operations should not exceed, at the nearest residence or location of interest, a specified level of the existing ambient sound exposure level (whichever is higher). It is assumed that areas can be zoned, and therefore classified in acoustic terms, according to their use. In order to allow the proposed guideliness to be used without knowledge of actual helicopter noise data, generalized curves have been developed by HAI which associate noise levels with helicopters of a given class on the basis of vehicle weight and distance. O.C.

N85-15754 Department of the Navy, Washington, D. C. SYSTEM FOR RAPID REPAIR OF DAMAGED AIRFIELD **RUNWAYS** Patent

P. S. SPRINGSTON, inventor (to Navy) 13 Sep. 1983 5 p Supersedes AD-D009985

(AD-D011325; US-PATENT-4,404,244;

US-PATENT-APPL-SN-437092; US-PATENT-CLASS-428-109) Avail: US Patent and Trademark Office CSCL 01E

A membrane of fiberglass-reinforced polyester resin is used as a trafficable cover over a compacted backfilled crater and crushed stone base to impart strength to the repair and prevent foreign object damage to aircraft. The membrane cover is usually prefabricated from several fiberglass matting layers of chopped fiberglass strands chemically bonded to woven fiberglass roving and impregnated with a polyester resin; an anchoring system consisting of holes along the cover perimeter and torque set rock bolts are used in conjunction with special steel bushings to secure the cover to airfield pavement surrounding the crater. GRA DESCRIPTION OF THE INSULATION SYSTEM FOR THE LANGLEY 0.3-METER TRANSONIC CRYOGENIC TUNNEL Jan. 1985 P. L. LAWING, D. A. DRESS, and R. A. KILGORE

27 p refs

(NASA-TM-86274; L-15723; NAS 1.15:86274) Avail: NTIS HC A03/MF A01 CSCL 14B

The thermal insulation system of the Langley 0.3 Meter Transonic Cryogenic Tunnel is described. The insulation system is designed to operate from room temperature down to about 77.4 K, the temperature of liquid nitrogen at 1 atmosphere. A detailed description is given of the primary insulation sytem consists of glass fiber mats, a three part vapor barrier, and a dry positive pressure purge system. Also described are several secondary insulation systems required for the test section, actuators, and tunnel supports. An appendix briefly describes the original insulation system which is considered inferior to the one presently in place. The time required for opening and closing portions of the insulation system for modification or repair to the tunnel has been reduced, typically, from a few days for the original thermal insulating system to a few hours for the present system. Author

N85-15757*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

ANALYTICAL AND PHYSICAL MODELING PROGRAM FOR THE NASA LEWIS RESEARCH CENTER'S ALTITUDE WIND TUNNEL (AWT)

J. M. ABBOTT, J. H. DEIDRICH, J. F. GROENEWEG, L. A. POVINELLI, L. REID, J. J. REINMANN, and J. R. SZUCH 1985 21 p refs Presented at the 23rd Aerospace Sci. Meeting, Reno, Nevada, 14-17 Jan. 1985; sponsored by AIAA (NASA-TM-86919; E-2413; NAS 1.15:86919; AIAA-85-0379)

Avail: NTIS HC A02/MF A01 CSCL 14B An effort is currently underway at the NASA Lewis Research

Center to rehabilitate and extend the capabilities of the Altitude Wind Tunnel (AWT). This extended capability will include a maximum test section Mach number of about 0.9 at an altitude of 55,000 ft and a -20 F stagnation temperature (octagonal test section, 20 ft across the flats). In addition, the AWT will include an icing and acoustic research capability. In order to insure a technically sound design, an AWT modeling program (both analytical and physical) was initiated to provide essential input to the AWT final design process. This paper describes the modeling program, including the rationale and criteria used in program definition, and presents some early program results. Author

N85-15758*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio. THE NASA ALTITUDE WIND TUNNEL (AWT): ITS ROLE IN

ADVANCED ICING RESEARCH AND DEVELOPMENT

B. J. BLAHA and R. J. SHAW 1985 21 p refs Presented at the 23rd Aerospace Sci. Meeting, Reno, Nevada, 14-17 Jan. 1985; sponsored by AIAA

(NASA-TM-86920; E-2414; NAS 1.15:86920; AIAA-85-0090) Avail: NTIS HC A02/MF A01 CSCL 14B

Currently experimental aircraft icing research is severely hampered by limitations of ground icing simulation facilities. Existing icing facilities do not have the size, speed, altitude, and icing environment simulation capabilities to allow accurate studies to be made of icing problems occurring for high speed fixed wing aircraft and rotorcraft. Use of the currently dormant NASA Lewis Altitude Wind Tunnel (AWT), as a proposed high speed propulsion and adverse weather facility, would allow many such problems to be studied. The characteristics of the AWT related to adverse weather simulation and in particular to icing simulation are discussed, and potential icing research programs using the AWT are also included. Author

N85-15760# Illinois Univ., Urbana. Dept. of Civil Engineering. DEVELOPMENT OF A PRELIMINARY ALRS STABILIZED MATERIAL PAVEMENT ANALYSIS SYSTEM (SPAS) Final Report, Apr. 1982 - May 1983

B. J. DEMPSEY, D. JANSSEN, J. THOMAS, P. FREY, and A. **IOANNIDES** Tyndall AFB, Fla. AF Engineering and Services Center Aug. 1984 171 p

(Contract FY8952-82-60024)

(AD-A147116; AFESC/ESL-TR-83-34) Avail: NTIS HC A08/MF A01 CSCL 01E

This report is an analytical study of soil stabilization as used in Alternate Launch and Recovery Surface (ALRS) design. The study proposes that ALRS pavements can be designed using a mechanistic design approach and a stabilized pavement analysis system (SPAS) is proposed. Stabilized material properties (strength, modulus, fatigue), structural modeling and behavior concepts, and environmental factors (freeze-thaw, frost depth) are utilized in the SPAS development. Inputs required to establish a stabilized base thickness for an ALRS pavement (F-4 loading) are the field strength of the stabilized material and the E sub Ri (measure of resilient modulus) of the fine-grained subgrade. A properly designed ALRS pavement for F-4 loading can accommodate a limited number of C-130 and F-15 load applications. The SPAS thickness design concepts (based on an intact slab approach) are applicable to a broad range of cementitious-stabilized materials (soil-cement, lime-fly ash-aggregate, soil-lime mixtures, similar high strength and modulus SPAS F-4 thickness requirements appear reasonable. Further research and development activities are required to validate SPAS. Technical report ESL-TR-84-25, Response and Performance of Alternate Launch and Recovery Surfaces Containing Stabilized Material Layers, shall report on predicting structural responses for ALRS pavements using stabilized material. Validation of the research shall use information from Test Report ESL-TR-83-46, Performance Data for F-4 Load Cart Operations on Alternate Launch and Recovery Surfaces. GRA

N85-15761# Department of the Navy, Washington, D. C. **AIRCRAFT BARRICADE Patent Application**

P. DIGIOVANNIANTONIC and W. J. ZIMMER, inventors (to Navy) 1 Aug. 1983 17 p (AD-D011316; US-PATENT-APPL-SN-519421) Avail: NTIS HC

A02/MF A01 CSCL 01E

A webbing system is disclosed for use as an aircraft barricade wherein a plurality of rectangularly-shaped engaging loops are arranged in a alternating, muli-planar array and suspended across a landing area in the path of an approaching aircraft upon an assembly of support loops stretched between a pair of stanchoins and connected on either side to an energy absorbing device. Slidably connected along upper and lower horizontal components of the support loops, the engaging loops are free to move laterally along the support loops toward the longitudinal axis of the aircraft when penetrated by the fuselage so that the aircraft is ensnared about is wings by the loops with equalized loading and its forward motion arrested. GRA

N85-15762# Naval Civil Engineering Lab., Port Hueneme, Calif. HANGAR HEATING AND ENERGY CONSERVATION MANUAL Final Report, Oct. 1979 - Sep. 1983 J. L. ASHLEY Sep. 1984 110 p

(AD-A147893; AFESC/DEB-TR-84-01) Avail: NTIS HC A06/MF A01 CSCL 01E

Hangars and similar structures require large amounts of energy for space heating. Energy conservation survey techniques for hangars are defined and technical data sheets are included which provide: (1) procedures to identify energy conservation deficiencies; (2) methods to calculate annual energy losses; (3) recommended solutions; and (4) methods to calculate annual energy savings.

Author (GRA)

N85-15763# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Cologne (West Germany). Hauptabteilung Windkanaele.

EXPERIENCES WITH THE USE OF A SIDE-STRUT MODEL SUPPORT SYSTEM FOR HIGH ANGLES OF ATTACK IN THE TRINSONIK WIND TUNNEL TMK

May 1984 53 p refs In GERMAN; ENGLISH H. ESCH summary Translation is in process as (ESA-TT-895)

(DFVLR-MITT-84-09; ESA-TT-895) Avail: NTIS HC A04/MF A01; DFVLR, Cologne DM 22

Experience with a relatively simple model support system for high angles of attack in a blowdown wind tunnel are presented. The advantages of low production costs and low operational costs as compared to the standard system face the disadvantages of increased aerodynamic interference and asymmetrical deformations. Interference tests show the limitations of the use of this system. It can be used in the supersonic domain, especially for higher Mach numbers. It is only conditionally usable in the transonic domain. Author (ESA)

N85-16770# Joint Publications Research Service, Arlington, Va. AEROPROYEKT DEVELOPS IMPROVED RUNWAY SURFACING

In its USSR Rept.: A. VINOGRADOV Transportation (JPRS-UTR-85-001) p 20-21 15 Jan. 1985 Transl. into ENGLISH from Vozdushnyy Transp. (Moscow), 25 Sep. 1984 p 3 Avail: NTIS HC A09/MF A01

A framed pavement design for aircraft was developed. Prior to concreting, I-beams are placed on the prepared surface of a runway so that, after welding, they form frames. One frame cell covers an area of some 50 square meters. After concreting, each cell forms a finished plate framed by the metal form. The frame acts as a form during concreting and prevents edge creep. Later, as the concrete hardens, the frame becomes an excellent joint component. This type pavement was accepted for operational use at one airport. Work on all-weather pavement is progressing.

A.R.H.

N85-16815# Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West Germany).

ADVANCED FLIGHT SIMULATION FOR HELICOPTER DEVELOPMENT

H. HUBER, H. J. DAHL, and A. INGLSPERGER In AGARD Helicopter Guidance and Control Systems for Battlefield Support 14 p Aug. 1984 refs Avail: NTIS HC A13/MF A01

A simulation capability for both fixed wing and rotary wing aircraft has been developed. The fixed based simulator consists of interchangeable cockpit stations, a computer generated imagery (CGI) visual system, both coupled with the math model simulation computer. Specific integration rigs for avionics, flight controls, and weapon systems can be operated with the simulator. The simulation system is described including cockpit/interface hardware, visual display system, and mathematical modeling. The simulation validity is demonstrated by the verification of the mathematical model and by pilot judgments. Typical simulation tasks for future military applications are discussed. It is concluded that the existing simulator provides a valid tool for helicopter system development. R.S.F.

N85-16816# Centre d'Electronique de l'Armement, Bruz (France)

A SIMULATOR FOR STUDYING HELICOPTER WEAPONS SYSTEMS [UN SIMULATEUR D'ETUDES DE SYSTEMS D'ARMES HELICOPTERE]

M. HUON In AGARD Helicopter Guidance and Control Systems for Battlefield Support 12 p Aug. 1984 refs In FRENCH Avail: NTIS HC A13/MF A01

A simulator designed to study air to air missile and cannon fire against a helicopter is described. The pilot station is fixed and located in a sphere which serves as a screen on which a TITUS tube projects a synthetic image of the landscape defined by 10,000 facets (SOGITEC G I 10,000 processor). The field is covered from 80 degrees around and is completed by horizon projection. A 250 faceted projector generates the target. A transparent, symbolic sighting tube is projected on the sphere by a power tube. The pilot uses a helmet mounted display. The marksman's apparatus is offset and involves a main sighting tube with presentation of a G I 10,000 image and weapons control. Vibration seats are provided. Ambient noise is supplied by a programmable noise generator. The complete simulator is operated from a test direction station. A.R.H.

N85-16817# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

FIDELITY USING ASSESSMENT OF SIMULATION **MEASUREMENTS OF PILOTING TECHNIQUE IN FLIGHT**

W. F. CLEMENT (Systems Technology, Inc., Mountain View, Calif.), W. B. CLEVELAND, and D. L. KEY In AGARD Helicopter Guidance and Control Systems for Battlefield Support 12 p Aug. 1984 refs

Avail: NTIS HC A13/MF A01 CSCL 14B The U.S. Army and NASA joined together on a project to conduct a systematic investigation and validation of a ground based piloted simulation of the Army/Sikorsky UH-60A helicopter. Flight testing was an integral part of the validation effort. Nap-of-the-Earth (NOE) piloting tasks which were investigated included the bob-up, the hover turn, the dash/quickstop, the sidestep, the dolphin, and the slalom. Results from the simulation indicate that the pilot's NOE task performance in the simulator is noticeably and quantifiably degraded when compared with the task performance results generated in flight test. The results of the flight test and ground based simulation experiments support a unique rationale for the assessment of simulation fidelity: flight simulation fidelity should be judged quantitatively by measuring pilot's control strategy and technique as induced by the simulator. A quantitative comparison is offered between the piloting technique observed in a flight simulator and that observed in flight test for the same tasks performed by the same pilots. R.S.F.

N85-16882*# National Aeronautics and Space Administration, Washington, D. C.

RESULTS OF 55 CH TESTS WITH AN ARL (AEROSPACE RESEARCH LABORATORY) CASCADE

A. FOURMAUX Dec. 1984 34 p refs Transl. into ENGLISH of "Resultats d'essais a S5 CH d'une grille d'aubes ARL (Aerospace Research Laboratory)" rept. RT-5/3568-EN, Paris, Mar. 1984 31 p Transl. by Kanner (Leo) Associates, Redwood City, Calif. Original document prepared by ONERA, Paris

(Contract NASW-4005)

(NASA-TM-77510; NAS 1.15:77510; ONERA-RT-5/3568-EN)

Avail: NTIS HC A03/MF A01 CSCL 14B

As part of a research agreement between Iowa State University of Science and Technology (ISU) and ONERA, a blade cascade designed and already tested in the United States was manufactured and tested in France. The ONERA cascade wind tunnel and mock-up are described. Attention is focused on defining the upstream conditions of the cascade. Experimental results are presented, as well as comparisons with tests conducted by Detroit Diesel Allison (DDA) in the United States. B.W.

N85-16883*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

LANGLEY MACH 4 SCRAMJET TEST FACILITY

E. H. ANDREWS, JR., M. G. TORRENCE, G. Y. ANDERSON, G. B. NORTHAM, and E. A. MACKLEY Feb. 1985 56 p refs (NASA-TM-86277; L-15827; NAS 1.15:86277) Avail: NTIS HC A04/MF A01 CSCL 14B

An engine test facility was constructed at the NASA Langley Research Center in support of a supersonic combustion ramjet (scramjet) technology development program. Hydrogen combustion in air with oxygen replenishment provides simulated air at Mach 4 flight velocity, pressure, and true total temperature for an altitude range from 57,000 to 86,000 feet. A facility nozzle with a 13 in square exit produces a Mach 3.5 free jet flow for engine propulsion tests. The facility is described and calibration results are presented which demonstrate the suitability of the test flow for conducting scramjet engine research. Author

N85-16884# Oak Ridge National Lab., Tenn.

EVALUATION OF ARCTIC TEST OF IMPROVED TRITIUM RADIOLUMINESCENT LIGHTING Final Report, Nov. 1983 - Feb. 1984

K. W. HAFF, J. A. TOMPKINS, L. J. HULT, and C. L. BUPP Aug. 1984 73 p

(Contract AF PROJ. 2673)

(AD-A148215; AFESC/ESL-TR-84-19) Avail: NTIS HC A04/MF A01 CSCL 01E

This test was conducted to determine if the improved generation of tritium radioluminescent runway lighting could effectively support aircraft operations in the Alaskan winter environment. The lighting system was unidirectional and consisted of threshold and touchdown zone lights (each end), edge lights, and Visual Approach Slope Indicator (VASI) lights. The primary lighting layout tested was similar to that required by Military Airlift Command regulations for C-130 operations. Nearly all pilots rated the runway lights satisfactory for use at tactical operating locations. Visual acquisition range was 3 to 5 miles under dark conditions. This distance was decreased by ambient lighting conditions. Pilots landing into the twilight of a setting sun reported as little as 1 mile acquisition range. The VASI system was rated marginal by pilots. Increasing the number of radioluminescent panels used and the distance between the panels significantly improved acquisition and usable ranges. The tritium lights were extremely durable throughout the test. They required no maintenance except an occasional wipe off, and there were no failures or security violations. GRA

N85-16885# Weston (Roy F.), Inc., West Chester, Pa.

INSTALLATION RESTORATION PROGRAM. PHASE 2: STAGE PROBLEM CONFIRMATION STUDY, DULUTH AIRPORT DULUTH, MINNESOTA Final INTERNATIONAL Report

Oct. 1984 213 p Sponsored by Air Force

(AD-A148318; AD-E700012) Avail: NTIS HC A10/MF A01 CSCL 13B

The following are among the study's key conclusions: (1) Groundwater occurs under shallow water table conditions in and around all sites investigated. Lateral groundwater gradients typically average about 0.02. While the hydraulic driving force for groundwater contaminant migration is fairly large, the actual rate of movement of groundwater is slow due to the presence of low-permeability glacial till. (2) Regional water table flow is generally northerly. Locally, however, this regional gradient is modified by surface drainageways which intercept the upper few feet of water table flow. Discharge of shallow groundwater to these surface drainageways creates a potential for off-base migration of contaminants. (3) Such migration of contaminants is demonstrated by detection of solvent compounds in the surface drainageway adjacent to the DPDO Storage Area C and by observation of oily discharges in surface drainageways adjacent to the Fuel Storage Area. (4) Part-per-billion level concentrations of the pesticide DDD were found in the bottom sediments of the GMSDA (Goose Missile Site Disposal Area) but off-site migration appears to be negligible. A non-pesticide compound, tentatively identified as PCB, was detected in GMSDA sediments in the same general distribution as the pesticide. GRA

N85-16886# Clemson Univ., S.C. Dept. of Chemical Engineering.

LABORATORY SIMULATION OF SMOKE REDUCTION FROM AIRCRAFT ENGINE TEST CELL EXHAUST USING A FLUIDIZED BED FILTER Final Report, 1 Jun. 1983 - 31 Aug. 1984

R. W. RICE 22 Oct. 1984 37 p

(Contract AF-AFOSR-0147-83)

(AD-A148600; AFOSR-84-1078TR) Avail: NTIS HC A03/MF A01 CSCL 13B

The lowering of aircraft engine test cell exhaust opacity by fluidized bed filtration of soot was simulated in the laboratory. Smoke from a diesel burner was diluted with ambient air and passed through a 25 cm diameter cylindrical bed of either 500 or 1000 micron glass spheres. Bed depths ranging from 2.5 to 10 cm and superficial gas velocities of 2 to 60 cm/s were studied. Using separate light-sources and photocell detectors, the optical densities of the bed inlet and outlet gas streams were simultaneously monitored. From these data percentage opacity reduction (POR) values were determined as a function of time. This measure of filtration efficiency was found to increase with bed depth, ranging from roughly 50% for a 2.5 cm deep bed of 1100 micron glass beads to 99% for a 10 cm deep bed of 500 micron beads. No appreciable decline in effectiveness was observed for periods of up to 1.5 hours. Attempts were made to supplement POR results with gravimetric measurements of particle loading and size distribution made using a stack gas sampler (inertial impactor). **GB**

N85-16887# Arbeitsgemeinschaft Deutscher Verkehrsflughaefen, Stuttgart (West Germany). Abteilung Verkehr. ACTIVITIES REPORT ON WEST GERMAN CIVIL AIRPORTS.

PART 1: TEXT Annual Report, 1983 [VERKEHRSLEISTUNGEN DER DEUTSCHEN VERKEHRSFLUGHAEFEN. 1: TEXT) Jun. 1984 63 p refs in GERMAN 2 Vol. (ISBN-3-87977-055-7-PT-1) Avail: NTIS HC A04/MF A01

The 1983 traffic activity report is given for the 11 international and 29 regional West German airports, including West Berlin. Information on the major Austrian airports as well as Basel and Zurich airports and another 200 European and non-European airports is also given. Aircraft movements, passenger numbers, air freight quantities, air mail, commercial traffic figures, evolution graphs over 25 years and vocabulary definitions are included. Author (ESA)

N85-16888# Arbeitsgemeinschaft Deutscher Verkehrsflughaefen, Stuttgart (West Germany). Abteilung Verkehr.

ACTIVITIES REPORT FOR THE WEST GERMAN CIVIL AIRPORTS. PART 2: TABLES Annual Report, 1983 *(VERKEHRSLEISTUNGEN* DEUTSCHEN DER VERKEHRSFLUGHAEFEN. 2: TABELLEN] 1984 81 p refs In GERMAN 2 Vol. (ISBN-3-87977-055-7-PT-2) Avail: NTIS HC A05/MF A01

The 1983 traffic activity report for the 11 international and 29 regional West German airports, including West Berlin is summarized. Data on the major Austrian airports as well as Basel airport, Zurich airports and another 200 European and non-European airports is also given. Aircraft movements, passenger numbers, air freight quantities, air mail, commercial traffic figures. evolution graphs over 25 years and vocabulary definitions are presented. Author (ESA)

10

ASTRONAUTICS

Includes astronautics (general); astrodynamics; ground support systems and facilities (space); launch vehicles and space vehicles; space transportation; spacecraft communications, command and tracking; spacecraft design, testing and performance; spacecraft instrumentation; and spacecraft propulsion and power.

A85-19495#

THERMAL DESIGN OF ROTATABLE CRYOGENIC HEAT PIPE JOINTS

E. FRENCH (Rockwell International Corp., Seal Beach, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs (AIAA PAPER 85-0068)

A gas-filled, finned heat exchanger which couples independently sealed heat pipes has been found to be a promising approach to the design of rotatable thermal joints for space applications. Closed-form solutions for the thermal transport characteristics of such heat exchangers have been combined with heat pipe performance equations to obtain parametric estimates of overall joint capability. Interfin heat conduction is maintained by low-pressure (50 torr or less) helium gas sealed within the joint. In a related experimental study of cryogenic rotating seals, helium leak rates have been measured at room temperature and at 100 K. Preliminary results show at least one seal type which exhibits the very low leak rates consistent with multi-year operation in space. Author

A85-19791*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

THE APPLICATION OF SOME LIFTING-BODY REENTRY CONCEPTS TO MISSILE DESIGN

M. L. SPEARMAN (NASA, Langley Research Center, Hampton, American Institute of Aeronautics and Astronautics, VA) Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(AIAA PAPER 85-0497)

The aerodynamic characteristics of some lifting-body concepts are examined with a view to the applicability of such concepts to the design of missiles. A considerable amount of research has been done in past years with vehicle concepts suitable for manned atmospheric-entry and atmospheric flight. Some of the concepts appear to offer some novel design approaches for missiles for a variety of missions and flight profiles, including long-range orbital/reentry with transatmospheric operation for strategic penetration, low altitude penetration, and battlefield tactical. The concepts considered include right triangular pyramidal configurations, a lenticular configuration, and various 75-degree triangular planform configurations with variations in body camber and control systems. The aerodynamic features are emphasized but some observations are also made relative to other factors such as heat transfer, structures, carriage, observability, propulsion, and volumetric efficiency. Author

A85-19792#

A PARALLEL QUASI-LINEARIZATION ALGORITHM FOR AIR VEHICLE TRAJECTORY OPTIMIZATION

P. K. A. MENON and L. L. LEHMAN (Integrated Systems, Inc., Palo Alto, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs

(Contract F08635-83-C-0480)

(AIAA PAPER 85-0498)

Recent research on parallel computing architectures has generated a need for inherently parallel numerical algorithms to improve speed in 'compute bound' situations such as trajectory. optimization. In this paper, a parallel quasi-linearization algorithm is presented for the solution of nonlinear two-point-boundary-value problems arising in flight vehicle trajectory optimization. This approach uses the integrating matrix technique. Optimization of a boost-glide missile trajectory is given as an application example.

Author

A85-20226#

NEWTON ITERATION FORMULAS FOR CORRECTING TEMPERATURE AND PRESSURE IN THERMODYNAMIC CALCULATION OF ROCKET ENGINES

D. FANG (National University of Defense Technology, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, Feb. 1984, p. 1-7. In Chinese, with abstract in English.

In thermodynamic calculation of rocket engines, the method of interpolation is usually accepted for correcting temperature and pressure. But it is convenient for the correction of one variable only and its convergence of successive approximation is slower. In this paper, Newton iteration formulas for correcting temperature and pressure in thermodynamic calculation are deduced from Newton method and thermodynamic differential relationships. Thermodynamic calculation on any section of nozzle is accomplished with these iteration formulas. Examples are given in Author the paper.

A85-20909 AIR BREATHING SPACE TRANSPORT VEHICLES WITH WINGS [GEFLUEGELTE LUFTATMENDE RAUMTRANSPORTER]

U. M. SCHOETTLE (Stuttgart, Universitaet, Stuttgart, West Germany) (Hermann Oberth Gesellschaft, Symposium ueber gefluegelte Raumfahrzeuge, Hanover, West Germany, May 25, 1984) Astronautik (ISSN 0004-6221), vol. 21, no. 4, 1984, p. 108-113. In German. Sponsorship: Deutsche Forschungsgemeinschaft. refs

(Contract DFG-SFB-85)

It is pointed out that the currently available space transportation systems of the Western World will not be able to satisfy demands expected for the turn of the century. The development of new systems is, therefore, necessary. Studies of suitable concepts for space transportation systems have already been conducted. Key technologies for future space transportation systems are based on new structural and propulsion concepts. The present investigation is concerned with the employment of a combined rocket-ramjet engine in a single-stage vehicle with wings, taking into account vehicles with vertical or horizontal launching capabilities. Questions of feasibility are explored exclusively under considerations of technological implementation. The considered combined rocket-ramjet propulsion unit is compared with propulsion systems based entirely on the use of rockets. The propellants are liquid hydrogen and liquid oxygen. It is found that the single-stage rocket-ramjet engine vehicle is feasible on the basis of the technological assumptions discussed by Haefeli et al. (1977).

G.R.

N85-15778*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

EFFECT OF AERODYNAMIC AND ANGLE-OF-ATTACK UNCERTAINTIES ON THE MAY 1979 ENTRY FLIGHT CONTROL SYSTEM OF THE SPACE SHUTTLE FROM MACH 8 TO 1.5 H. W. STONE and R. W. POWELL Jan. 1985 137 p refs (NASA-TP-2365; L-15813; NAS 1.60:2365) Avail: NTIS HC A07/MF A01 CSCL 22B

A six degree of freedom simulation analysis was performed for the space shuttle orbiter during entry from Mach 8 to Mach 1.5 with realistic off nominal conditions by using the flight control systems defined by the shuttle contractor. The off nominal conditions included aerodynamic uncertainties in extrapolating from wind tunnel derived characteristics to full scale flight characteristics, uncertainties in the estimates of the reaction control system interaction with the orbiter aerodynamics, an error in deriving the angle of attack from onboard instrumentation, the failure of two of the four reaction control system thrusters on each side, and a lateral center of gravity offset coupled with vehicle and flow asymmetries. With combinations of these off nominal conditions, the flight control system performed satisfactorily. At low hypersonic speeds, a few cases exhibited unacceptable performances when errors in deriving the angle of attack from the onboard instrumentation were modeled. The orbiter was unable to maintain lateral trim for some cases between Mach 5 and Mach 2 and exhibited limit cycle tendencies or residual roll oscillations between Mach 3 and Mach 1. Piloting techniques and changes in some gains and switching times in the flight control system are suggested to help alleviate these problems. E.A.K. CHEMISTRY AND MATERIALS

Includes chemistry and materials (general); composite materials; inorganic and physical chemistry; metallic materials; nonmetallic materials; and propellants and fuels.

11.....

A85-20150

THE CHALLENGE FROM CERAMICS TO METALS IN THE GAS TURBINE AND RELATED AREAS

J. C. MOORE (Powder Metallurgy Group, Conference on Developments in Powder Metallurgy Materials, Processes, and Applications, Edinburgh, Scotland, Oct. 24-26, 1983) Powder Metallurgy (ISSN 0032-5899), vol. 27, no. 4, 1984, p. 229, 230.

A brief is made of the present competence in developing a ceramic gas turbine engine to replace the existing high temperature alloy systems, candidate materials are described and design and manufacturing problems are discussed. Author

A85-20545#

REVIEW OF THE ORIGIN OF JAPANESE INDUSTRIAL STANDARD

T. MORINAGA Japan Institute of Light Metals, Journal (ISSN 0451-5994), vol. 34, Oct. 1984, p. 607-617. In Japanese.

The historical background of the Japanese Industrial Standard (JIS) for AI and Mg alloys used in aircraft components is reviewed. The HD alloy (AI-Mg-Zn system containing Mn and Cr for inhibiting stress corrosion) developed for high strength aircraft components during World War II is described. The HD alloy has gained wide acceptance for commercial uses, currently is known as a three-dimensional AI alloy, and is also described in the JIS-7N01. The manufacturing methods of these AI and Mg alloys are outlined. The specifications and chemical composition of AI and Mg alloys used in aircraft components are listed.

A85-20758

DEVELOPMENT OF A FATIGUE CRACK PROPAGATION MODEL OF INCOLOY 901

B. J. SCHWARTZ, N. G. ENGSBERG, and D. A. WILSON (United Technologies Corp., Pratt and Whitney Group, West Palm Beach, FL) IN: Fracture mechanics . Philadelphia, PA, American Society for Testing and Materials, 1984, p. 218-241. refs

The present investigation is concerned with interpolative crack propagation models of Incoloy 901. The models were developed from data generated by an American aerospace company under a Navy contract. Attention is given to the experimental program for obtaining crack propagation data, aspects of mathematical model development, the effect of loading rate, the effect of positive stress ratio, the effect of negative stress ratio, the effect of temperature, prior plastic deformation, and the statistics of the model. The examined model is considered a highly accurate tool for describing the crack propagation rates in Incoloy 901 under constant peak amplitude loading. G.R.

A85-20759

FATIGUE CRACK GROWTH BEHAVIOR OF 7XXX ALUMINUM ALLOYS UNDER SIMPLE VARIABLE AMPLITUDE LOADING

P. E. BRETZ, A. K. VASUDEVAN, R. J. BUCCI, and R. C. MALCOLM (Aluminum Company of America, Alloy Technology Div., Alcoa Center, PA) IN: Fracture mechanics . Philadelphia, PA, American Society for Testing and Materials, 1984, p. 242-265. refs (Contract N00019-79-C-0258)

This investigation examines the influence of temper and purity on the fatigue crack growth (FCG) behavior of four 7XXX aluminum alloys (7075-T6, 7075-T7, 7050-T6, 7050-T7) tested using a periodic single overload spectrum at low stresses. The loading sequence consists of a periodic single overload spike occurring once every 800 constant amplitude cycles; the overload spike is 1.8 times the constant amplitude load peak. All tests have been performed in high humidity (greater than 90 percent relative humidity) air at a frequncy of 20 Hz and a constant amplitude load ratio of R = 0.33. The observed microstructural effects on transient (that is, spectrum) FCG behavior are contrasted with those for steady-state (constant load amplitude) fatigue performance. Author

A85-20790

INTERPRETATION OF FATIGUE CRACK GROWTH IN ALUMINIUM ALLOYS UNDER PROGRAMMED BLOCK LOADING

M. GABRA and C. BATHIAS (Complegne, Universite de Technologie, Complegne, France) Fatigue of Engineering Materials and Structures (ISSN 0160-4112), vol. 7, no. 4, 1984, p. 285-298. Research supported by the Direction des Recherches, Etudes et Techniques. refs

The effect of cycle ratio on the crack-propagation rate for two aluminum alloys is analyzed. Fatigue-crack growth under programmed block loading is presented and linear damage accumulation is established for some flight-simulation tests. Aspects covered include microscopic and fractographic observations. The incidence of crack closure is examined, and the concept of equivalent constant amplitude is applied. The agreement between predictions and test results is very promising. Author

A85-20865#

AN EXPERIMENTAL INVESTIGATION OF AN UNSTEADY COMBUSTING FLOW IN A PULSE COMBUSTOR

J. O. KELLER (Sandia National Laboratory, Livermore, CA) and K. SAITO (Toshiba Corp., Fuji, Japan) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. Research supported by the U.S. Department of Energy and Toshiba Corp. refs (AIAA PAPER 85-0322)

Pulse combustion devices exhibit exceedingly high thermal efficiency and very low pollutant emission when used in heating applications. Application of these heating devices has been limited, however, because of a lack of understanding of the fundamental controlling physical and chemical processes governing pulse combustors. An experimental research program has been initiated at Sandia National Laboratories to develop such insight. This paper reports the results of an experiment studying the effects of changing heat release and pressure pulsations on the fluid dynamics in the combustion chamber of a square pulse combustor. Using a two-color laser Doppler velocimeter (LDV) as a diagnostic tool, this study indicates that the fluid dynamics in the combustion chamber are strongly affected by pressure pulsations and are

weakly affected by a change in the heat release rate.

A85-20925

OXIDATION AND STABILIZATION OF JET FUELS [OKISLENIE | STABILIZATSIIA REAKTIVNYKH TOPLIV]

E. T. DENISOV and G. I. KOVALEV Moscow, Izdatel'stvo Khimiia, 1983, 270 p. In Russian. refs

The principal types of modern jet fuels are briefly reviewed, and problems associated with the oxidation of fuels during storage and use and the need for their stabilization are discussed. In particular, attention is given to the kinetics and mechanisms of the liquid-phase oxidation of hydrocarbons, kinetic methods of evaluating fuel oxidability, the mechanisms of oxidation inhibition, and the catalytic and inhibiting effects of structural materials on the oxidation of jet fuels. The relationship between the oxidability of fuels and their service-related properties is examined, and the efficiency of various oxidation inhibitors is assessed. V.L.

A85-21376

COMPOSITE STRUCTURES; PROCEEDINGS OF THE NATIONAL SPECIALISTS MEETING, PHILADELPHIA, PA, MARCH 23-25, 1983

Meeting sponsored by the American Helicopter Society. Washington, DC, American Helicopter Society, 1984, 335 p. For individual items see A85-21377 to A85-21398.

The present conference considers the design, fabrication and verification of a composite 'flexbeam' tail rotor, the development of a graphite/polyimide composite transmission housing, ground

test experience with large composite structures for commercial transport helicopters, advanced composite joints and fittings for primary structural components, the crashworthiness of helicopter composite structures, a flexible matrix composite hingeless rotor system, and recent filament-winding resin developments. Also discussed are the properties and advantages of Kevlar fiber reinforcement in airframe composites, the energy absorption characteristics of reinforced plastic tubes and composite materials, composite prototype and experimental aircraft, and the mechanical properties of magnaweave glass/epoxy composites. O.C.

A85-21380

DEVELOPMENT OF A GRAPHITE/POLYIMIDE COMPOSITE TRANSMISSION HOUSING

J. W. LENSKI, JR. (Boeing Vertol Co., Philadelphia, PA) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983. Washington, DC, American Helicopter Society, 1984, 11 p. Army-sponsored research. refs

Attention is given to the results of a development effort encompassing the design, fabrication, and testing of a high modulus composite transmission housing which will reduce helicopter mechanical drive system weight and cost while improving reliability and system performance. The composite transmission housing includes among its advantages corrosion resistance, thermal stability, and exceptional specific strength and stiffness by comparison to conventional cast magnesium housings. A filament winding fabrication procedure was selected to minimize production costs through the elimination of hand layups, multiple cure cycles, and secondary bonds. O.C.

A85-21389

FLEXIBLE MATRIX COMPOSITES APPLIED TO BEARINGLESS ROTOR SYSTEMS

A. J. HANNIBAL, B. P. GUPTA, J. A. AVILA, and C. H. PARR (Lord Corp., Mechanical Group, Erie, PA) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983. Washington, DC, American Helicopter Society, 1984, 34 p. refs

A new composite structure in which the typical epoxy matrix is replaced by an elastomer is introduced. Some of its properties, particularly its elastic constants, are discussed in terms of laminate angle, constituent properties and fiber fraction. Unidirectional flexible matrix composites are applied to the requirements of a bearingless rotor flexure. This is done by assessing load-deflection characteristics and strengths of test coupons in critical loading modes. Preliminary results indicate a short, lightweight, flexible matrix composite flexure is feasible. Flexible matrix composites are also applied to a pitch control tube of a typical 3000-kg helicopter. A full scale prototype was fabricated and tested both statically and dynamically. It endured 50 x 10 to the 6th cycles of combined bending and torsion loads with only a modest loss of properties.

A85-21390

Author

UTILIZATION OF ANALYTICAL EQUIPMENT IN DESIGN AND PROCESS PROBLEMS SOLUTION AND FAILURE ANALYSIS OF COMPOSITES

V. F. MAZZIO, R. R. IGNATUK, and H. R. LUZETSKY (Boeing Vertol Co., Philadelphia, PA) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983. Washington, DC, American Helicopter Society, 1984, 9 p.

The static and fatigue properties of epoxy/high strain graphite systems suitable for use in aircraft primary structures are presented, with attention to effects due to stress/strain, on the one hand, and those due to the surface and failure mechanism characteristics of the fibers, on the other. The results obtained for these high strain composite systems were compared to those for conventional graphite/epoxy. SEM and TEM were used to determine surface effects and evaluate failure mechanisms in tests conducted in 90-deg tension, compression, short beam shear, and in-plane shear.

11 CHEMISTRY AND MATERIALS

Excellent property improvements are noted for the high strain composite over standard materials. O.C.

A85-21392

KEVLAR ARAMID FIBERS VS OTHER FIBERS FOR REINFORCEMENT OF COMPOSITE STRUCTURES

P. R. LANGSTON (Du Pont de Nemours and Co., Wilmington, DE) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983. Washington, DC, American Helicopter Society, 1984, 22 p.

The physicomechanical properties of Kevlar 29 and Kevlar 49 fibers are reviewed, and the properties of Kevlar-reinforced composites are compared with those of other materials, such as graphite/epoxy, fiberglass/epoxy, boron/epoxy, cast iron, stainless steel, and aluminum. The properties discussed include tensile strength, specific modulus, flexural and compressive behavior, vibration dampening, fatigue strength, moisture pickup, and resistance to impact damage. The uses of Kevlar-reinforced composites in aerospace and aircraft structures are then examined.

A85-21393

ENERGY ABSORBING QUALITIES OF FIBER REINFORCED PLASTIC TUBES

C. M. KINDERVATER (Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Stuttgart, West Germany) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983. Washington, DC, American Helicopter Society, 1984, 14 p. refs

The fulfilment of crashworthiness requirements in helicopter composite primary structures has prompted the present parametric study of composite tubes. The investigation ranged over matrix/fiber material variations, the influence of foam fillers, different fiber orientations, and various failure-triggering mechanisms. Attention is given to axial crushing under quasi-static and impact loading. Typical load deflection curves and failure modes are presented, together with such performance indicators as specific energy, energy dissipation density, stroke efficiency, load uniformity, and crush stress. Results are correlated to the energy absorption performance of other structures, such as aluminum and paper honeycomb and thin walled steel and aluminum cvlinders. O.C.

A85-21482

V-378A, A NEW MODIFIED BISMALEIMIDE MATRIX RESIN FOR HIGH MODULUS GRAPHITE

S. W. STREET (United States Polymeric, HITCO Materials Div., Santa Ana, CA) IN: Polyimides: Synthesis, characterization, and applications. Volume 1 New York, Plenum Press, 1984, p. 77-98.

The characteristics of V-378A, a new modified bismaleimide matrix resin for high-modulus graphite, are discussed. The prepreg properties, lay-up and cure properties, mechanical and physical properties, and effects of prepreg aging, are described. The applications of V-378A are summarized. The resin exhibits significant advantages over previously available bismaleimides and 350 F curing epoxy resins. Its Tg is in excess of 700 F, it has excellent tack at ambient temperatures, and it is available at prepreg resin solids contents as low as 30 precent for 'net' resin cures. It can be cured under stnadard low autoclave pressure of 100 psi and temperatures of 350 F. It offers easy, epoxylike processing characteristics with no volatile condensation products given off during cure, as well as significant superior high-temperature strength retention after severe humidity aging.

A85-21483* National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

A THERMOPLASTIC POLYIMIDESULFONE

T. L. ST. CLAIR (NASA, Langley Research Center, Hampton, VA) and D. A. YAMAKI (NASA, Langley Research Center, Hampton, VA; Mobil Research and Development Corp., Paulsboro, NJ) IN: Polyimides: Synthesis, characterization, and applications. Volume 1. New York, Plenum Press, 1984, p. 99-116. Previously announced in STAR as N83-14273. refs

A polymer system has been prepared which has the excellent thermoplastic properties generally associated with polysulfones, and the solvent resistance and thermal stability of aromatic polyimides. This material, with improved processability over the base polyimide, can be processed in the 260-325 C range in such a manner as to yield high quality, tough unfilled moldings; strong, high-temperature-resistant adhesive bonds; and well consolidated, graphite-fiber-reinforced moldings (composites). The unfilled moldings have physical properties that are similar to aromatic polysulfones which demonstrates the potential as an engineering thermoplastic. The adhesive bonds exhibit excellent retention of initial strength levels even after thermal aging for 5000 hours at 232 C. The graphite-fiber-reinforced moldings have mechanical properties which makes this polymer attractive for the fabrication of structural composites. Author

A85-21520* National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio. PMR POLYIMIDE COMPOSITES FOR AEROSPACE

APPLICATIONS T. T. SERAFINI (NASA, Lewis Research Center, Cleveland, OH)

IN: Polyimides: Synthesis, characterization, and applications. Volume 2 . New York, Plenum Press, 1984, p. 957-975. refs

A novel class of addition-type polyimides has been developed in response to the need for high temperature polymers with improved processability. The new plastic materials are known as PMR (for in situ polymerization of monomer reactants) polyimides. The highly processable PMR polyimides have made it possible to realize much of the potential of high temperature resistant polymers. Monomer reactant combinations for several PMR polyimides have been identified. The present investigation is concerned with a review of the current status of PMR polyimides. Attention is given to details of PMR polyimide chemistry, the processing of composites and their properties, and aerospace applications of PMR-15 polyimide composites. G.R.

A85-21527

POLYIMIDE PROTECTIVE COATINGS FOR 700 DEG SERVICE R. J. JONES, G. E. CHANG, S. H. POWELL, and H. E. GREEN (TRW, Inc., TRW Energy Development Group, Redondo Beach, CA) IN: Polyimides: Synthesis, characterization, and applications. Volume 2, New York, Plenum Press, 1984, p. 1117-1137, refs

Volume 2 . New York, Plenum Press, 1984, p. 1117-1137. refs It has been discovered that partially fluorinated polyimide resins prepared grow from 2,2-bis/4-(4-aminophenoxy)-phenyl/hexafluoropropane (4-BDAF) possess great potential for long term service in highly oxidative

possess great potential for long term service in highly oxidative environments at temperatures up to and including 700 F. The new class of polyimides shows promise for use in applications involving advanced aircraft, engines, and missile designs in which higher temperatures are reached. The present investigation is concerned with the results of initial coating product applications studies. Attention is given to initial polyimide matrix resin studies and polyimide coating studies. It is concluded that the resins are amenable to a practical spray coating application technique. The resins are suitable for use as an oxidative barrier and/or corrosion inhibiting coating at temperatures up to a minimum of 700 F. A85-21650* National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

MICROSTRUCTURAL DEVELOPMENT OF PROTECTIVE AL203 SCALES

J. L. SMIALEK (NASA, Lewis Research Center, Cleveland, OH) IN: Electron Microscopy Society of America, Annual Meeting, 42nd, Detroit, MI, August 13-17, 1984. San Francisco, San Francisco Press, Inc., 1984, p. 594-597. refs

Microstructural characteristics of Al2O3 scales grown as protective coatings on NiCrAI alloys used in jet engines are described. The alloys were pure or doped with 0.3 percent Zr or Y and oxidized in 1 atm air at 1100 C for 0.1, 1 or 20.0 hr. The scales were then examined under a microscope. Transient epitaxial scales, formed during the 0.1 hr treatment and containing Ni, Cr and Al, consisted of a mosaic of subgrains and precipitates of different phases. The Y and Zr dopants had no effect on the nucleation site locations. The appearance of intergranular porosity at 0.1 hr was exacerbated after the 1 hr treatment. A bimodal void distribution appeared after 20 hr, when no porosity was evident. The detection of local areas of preferred orientation is taken as a spur to further studies of scale growth to gain control of the grain size or even to produce single crystal scales. MSK.

A85-21863#

SWIRLING FLOW IN A RESEARCH COMBUSTOR

J. I. RAMOS and H. T. SOMER (Carnegie-Mellon University, Pittsburgh, PA) AIAA Journal (ISSN 0001-1452), vol. 23, Feb. 1985, p. 241-248. Research supported by the Ford Motor Co. Previously cited in issue 05, p. 612, Accession no. A83-16644. refs

(Contract N00014-80-C-0400)

N85-15739# Motoren- und Turbinen-Union Muenchen G.m.b.H. (West Germany). Materials Lab.

COMPARISON BETWEEN PROPERTIES OF THE CONVENTIONAL WROUGHT AND POWDER METALLURGICAL ALLOYS FOR TURBINE DISC APPLICATIONS

G. W. KOENIG *In* AGARD Eng. Cyclic Durability by Analysis and Testing 11 p Sep. 1984 refs Avail: NTIS HC A12/MF A01

Mechanical properties of powder-metallurgical nickel-base superalloys (e.g., U700PM; Rene 95) were evaluated in order to predict the behavior of advanced aero-engine discs in comparison with conventional wrought nickel-base (e.g., Waspaloy; IN 718) discs. The assessment includes tensile strength, crack initiation and propagation fatigue life as well as the influence of mean stress. Special emphasis was put on the question about the scatter in fatigue lives resulting from defects in the material (e.g., oxide inclusions) and on the surface (e.g., grooves). The tolerance with respect to these defects was estimated on the basis of fracture mechanics methods. The potential of advanced nickel-base superalloys with respect to static strength and fatigue life is superior to that of currently used conventional wrought disc materials. It is shown that the most important requirement for the use of this fatique potential is a high quality standard which limits the maximum size of defects both in the material and on the surface. The now available knowledge of the variable influencing the reliability of disc materials enables an optimization to obtain improved service behavior. Furthermore, the strength and quality of materials as well as the manufacturing process can be fitted to the requirements of each type of component. R.J.F.

N85-15831# Research Inst. of National Defence, Stockholm (Sweden). Dept. 2.

IMPRESSIONS FROM A STUDY TOUR IN FINLAND **CONCERNING FIBER REINFORCED PLASTICS, JUNE 1984**

F. LARSSON Sep. 1984 11 p refs In SWEDISH; ENGLISH summary

(FOA-C-20552-D2(E4,F9); ISSN-0347-3694) Avail: NTIS HC A02/MF A01

The use of fiber reinforced plastics in high performance applications is outlined, including light plastic structures for aeronautical wings, sandwich structures, autoclaves and quenching ovens, and thermoplastic resins. Carbon and glass fibers, pultrusion combined with filament winding, ductility determination for plastic structures, and corrosion resistance are also discussed.

Author (ESA)

N85-15919# Michigan Univ., Ann Arbor. Dept. of Mechanical Engineering.

SOME CHARACTERISTICS OF AUTOMOTIVE GASOLINES AND THEIR PERFORMANCE IN A LIGHT AIRCRAFT ENGINE Final Report, Oct. 1982 - Mar. 1984

K. M. MORRISON, N. W. SUNG, and D. J. PATTERSON Atlantic City FAA Nov. 1984 101 p refs

(Contract DOT-FA79NA-6083)

(FAA-CT-84-12) Avail: NTIS HC A06/MF A01

The primary purpose of this extensive test effort was to observe real-time operational performance characteristics associated with automotive grade fuel utilized by piston engine powered light general aviation aircraft. In fulfillment of this effort, baseline engine operations were established with 100LL aviation grade fuel followed by four blends of automotive grade fuel. A comprehensive sea level - static test cell/flight test data collection and evaluation effort was conducted to review operational characteristics of a carbureted light aircraft piston engine as related to fuel volatility, fuel temperature, and fuel system pressure. Presented herein are results, data, and conclusions drawn from test cell engine operation as well as flight test operation on 100LL aviation grade fuel and various blends of automotive grade fuel. Sea-level-static test cell engine operations were conducted utilizing an AVCO Lycoming 0-320 engine connected to an eddy current dynamometer which facilitated data collection under various engine load conditions. Test cell instrumentation was utilized to obtain operational data (temperatures, pressures, flow rates, torque, horsepower, exhaust emissions, etc.) from idle through cruise to maximum power with fuel grades having Reid vapor pressures of 6.7, 8.0, 11.7, 14.0, Author and 14.4.

N85-15920# Boeing Military Airplane Development, Seattle, Wash.

AIRCRAFT WING FUEL TANK ENVIRONMENTAL SIMULATOR TESTS FOR EVALUATION OF ANTIMISTING FUELS Final Report, Sep. 1982 - Aug. 1984 P. M. MCCONNELL, F. F. TOLLE, and H. K. MEHTA Atlantic

City FAA Oct. 1984 107 p refs

(Contract DTFA03-83-C-00038)

(FAA-CT-84-15) Avail: NTIS HC A06/MF A01

The low temperature performance of antimisting kerosene (AMK) in airframe fuel systems and in certain engine fuel system components was studied and compared to Jet A fuel. Water vapor ingested into fuel tanks during simulation of repeated descents through clouds and rain had little effect on AMK. AMK retained antimisting properties during exposure to severe environmental flight simulations. Jet pump and boost pump operation had no discernable effect on AMK flammability. Jet pump performance with AMK was adversely affected. Main fuel boost pumps required up to 18 percent more power with AMK than with Jet A, and suction feed performance was lower with ambient and -20 C, but better than Jet A at -40 C. Boost pump performance was not affected by gel formations produced at low temperatures by the vapor removal return flow shearing of AMK. Aerodynamic heating and cooling of AMK in the fuel tank was similar to Jet A. A high pressure pump and needle valve used to degrade the AMK was inadequate, resulting in filter bypass at low temperatures. Author

N85-15921# Air Force Inst. of Tech., Wright-Patterson AFB, Ohio. School of Systems and Logistics.

DISTRIBUTION AND STORAGE OF AVIATION TURBINE FUEL FOR MILITARY OPERATIONS IN NORTHERN AUSTRALIA M.S. Thesis

D. A. WHITTY Sep. 1984 141 p

(AD-A147180; AD-E850744; AFIT/GLM/LSM/84S-63) Avail: NTIS HC A07/MF A01 CSCL 21D

In northern Australia, prospective economic development is unlikely to create a distributed network of aviation turbine fuel

11 CHEMISTRY AND MATERIALS

storages sufficient to support Australian Defence Force operations in an emergency, and Defence investment in fuel storage facilities and distribution resources might be required. This thesis project was an effort to identify the key relationships in the operational fuels system, and to create a decision support system capable of indicating broad relationships and tradeoffs between decision variables. To answer investigative questions arising from a broad system review, relevant literature was examined, indicating a need to focus on the distribution system with five key elements: (1) demand, (2) bulk seaboard storage facilities, (3) base storage, (4) transport resources, and (5) transport represent system dynamics for distribution from bulk to base storage. Subject to correcting of input statistics, the results could be used to inform Defence decisions on facilities construction, and investment in transport resources. With recommended enhancements, the model could potentially be used to inform Defence contributions to national and international policy considerations. GRA

N85-15922# Pratt and Whitney Aircraft, West Palm Beach, Fla. Government Products Div.

EVALUATION OF JET FUEL DEPOSIT KINETICS. LOT 4 Final Report, Mar. 1983 - Mar. 1984

W. J. PURVIS and R. J. MEEHAN Mar. 1984 48 p

(Contract N00140-80-C-0097)

(AD-A147196; PWA-FR-17658; NAPC-PE-107C) Avail: NTIS HC A03/MF A01 CSCL 21D

Four selected JP-5 type Navy jet fuels were investigated with regard to their rate of thermally induced deposition using two analytical techniques. A modified research Jet Fuel Thermal Oxidation Tester (JFTOT), using a quartz-enclosed heater section in combination with a photosensitive detector, was to monitor the buildup of thermally induced fuel deposits. Concurrent with the JFTOT, tests were conducted using the Experimental Coking Apparatus (ECA) in order to establish comparable deposition rate data. The resultant Arrhenius analyses have contributed to understanding the impact of an invariant oxygen concentration on the specific fuel deposition rate. An attempt to measure the hydrocarbon peroxide associated with each fuel and the buildup of organo-peroxide with fuel temperature was inconclusive due to the variation in peroxide potential analysis (ASTM D-3703). Originator-supplied key words include: Coking. GRA

N85-15931# Joint Publications Research Service, Arlington, Va. ALL-COMPOSITE AIRBUS EMPENNAGE Abstract Only

In its West Europe Rept.: Sci. and Technol. (JPRS-WST-84-039) p 4 18 Dec. 1984 Transl. into ENGLISH from Composites et Nouveaux Mater. (Paris), Sep. 1984 p 6

Avail: NTIS HC A04/MF A01

An all-composite Airbus empennage with a framework built entirely out of carbon fibers and epoxy resin in the form of two pre-impregnated fibredux units is discussed. It is suggested that the operating costs of a commercial airplane could be lowered without reducing its flight safety, by using support structures made of high performance composites. With 20% less weight, composite frames should be fully interchangeable with metal frames and meet the same navigability specifications. Their external geometry and attachment points to the fuselage, leading edge, and rudder should therefore be identical to those of metal structures. Moreover, their mass production has to be automated for economic reasons. When these requirements are met, five planes will be equipped with a composite empennage framework for flight tests. E.A.K.

N85-17048*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

ADVANCES IN COMPOSITES TECHNOLOGY

D. R. TENNEY and H. B. DEXTER Jan. 1985 33 p refs (NASA-TM-86353; NAS 1.15:86353) Avail: NTIS HC A03/MF A01 CSCL 11D

A significant level of research is currently focused on the development of tough resins and high strain fibers in an effort to gain improved damage tolerance. Moderate success has been achieved with the development of new resins such as PEEK and additional improvements look promising with new thermoplastic

resins. Development of innovative material forms such as 2-D and 3-D woven fabrics and braided structural subelements is also expected to improve damage tolerance and durability of composite hardware. The new thrust in composites is to develop low cost manufacturing and design concepts to lower the cost of composite hardware. Processes being examined include automated material placement, filament winding, pultrusion, and thermoforming. The factory of the future will likely incorporate extensive automation in all aspects of manufacturing composite components. B.W.

N85-17049*# Lockheed-California Co., Burbank. FLIGHT SERVICE EVALUATION OF ADVANCED COMPOSITE AILERONS ON THE L-1011 TRANSPORT AIRCRAFT Annual **Flight Service Report**

R. H. STONE Dec. 1984 10 p refs

(Contract NAS1-15069)

(NASA-CR-172483; NAS 1.26:172483; LR-30774; AFSR-2) Avail: NTIS HC A02/MF A01 CSCL 11D

A flight service evaluation of composite inboard ailerons on the L-1011 is discussed. This is the second annual report of the maintenance evaluation program, and covers the period from July 1983 when the first yearly inspections were completed, through July 1984. Four shipsets of graphite/epoxy composite ailerons were installed on L-1011 aircraft for this maintenance evaluation program. These include two Delta aircraft and two TWA aircraft. A fifth shipset of composite ailerons were installed in 1980 on Lockheed's flight test L-1011. A visual inspection was also conducted on these components. No visible damage was observed on any of the composite ailerons, and no maintenance action has occurred on any of the composite parts except for repainting of areas with paint loss. Flight hours on the airline components at the time of inspection ranged from 6318 to 6989 hours, after approximately 2 years of service. B.W.

N85-17057# Advisory Group for Aerospace Research and Development, Neuilly-Sur-Seine (France).

COMPOSITE STRUCTURE REPAIR, ADDENDUM

Loughton, England Aug. 1984 26 p refs Presented at the 58th Meeting of the Struct. and Mater. Panel, Sienna, Italy, 2-6 Apr. 1984 Addendum to AGARD-R-716; N84-31300 (AGARD-R-716-ADD; ISBN-92-835-1476-9) Avail: NTIS HC A03/MF A01

Programs are presented in which bonded and bolted composite repair techniques were validated. The repair of specific military and commercial aircraft components is addressed. Composite repair of flat laminates, integral stiffened panels, and honeycomb sandwich structures on aircraft is discussed.

N85-17058# Naval Air Development Center, Warminster, Pa. **REPAIR OF COMPOSITES**

T. M. DONNELLAN, E. L. ROSENZWEIG, R. E. TRABOCCO, and J. G. WILLIAMS (Aeronautical Research Labs., Melbourne) In AGARD Composite Struct. Repair, Addendum 10 p Aug. 1984 refs

Avail: NTIS HC A03/MF A01

Developments in composite repair technology are discussed. The planned use of composites in primary aircraft structure has necessitated the development of a specialized repair technology. The types of damage seen in composites differs from conventional materials. Delamination is the most serious composite defect since it can exist without causing surface damage. The two techniques used to repair composites are bonded and bolted approaches. A number of programs have been performed which have evaluated repair techniques under simulated operating conditions. Programs are discussed in which bonded and bolted repair techniques were validated. Generic repair development programs are described in which the repairs were performed with equipment and techniques possible in the service environment. The results of these studies show that the repairs restored the component structural integrity. Repair programs on specific military and commercial aircraft are also described. The components studied included an AHI rotor blade, a S-3A spoiler and a L-1011 fin. R.S.F.

N85-17059# Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West Germany).

COMPOSITE REPAIR OF AIRCRAFT STRUCTURES

J. W. VILSMEIER In AGARD Composite Struct. Repair, Addendum Aug. 1984 9 p

Avail: NTIS HC A03/MF A01

The repair of composite and metallic aircraft structures with composite materials has become a matter of world wide interest and activity. Activities in the field of composite repair of flat laminates, honeycomb sandwich structures, and integral stiffened panels are presented. Composite repair problems, aircraft battle damage repair, bonding on wet laminates, environmental effects, and problems associated with nondestructive testing of repaired structures and repair of joints are discussed. RSE

N85-17077# Department of the Air Force, Washington, D.C. HEATER BLOCK ASSEMBLY FOR USE IN THERMAL **OXIDATION TESTING OF JET FUEL Patent Application** R. A. HARVEY, inventor (to Air Force) 19 Sep. 1984 12 p (AD-D011430; US-PATENT-APPL-SN-651983) Avail: NTIS HC A02/MF A01 CSCL 21B

A heater block assembly for a jet fuel thermal oxidation test apparatus has back and front plates with a heater plate clamped therebetween. The heater plate has a flat surface which faces the front plate, while the front plate has a raised ledge with a channel formed therein which faces the flat surface of the heater plate. Also, inlet and outlet openings to opposite ends of the channel are formed through the front plate. When the back and front plates are clamped together with the heater plate therebetween the flat surface of the heater plate and the channel in the front plate together define a fuel sample flow passage. Thus, the fuel sample undergoing test is pumped through the inlet on the front plate into the flow passage where it flows along and in contact with the flat surface and then out through the outlet on the front plate. Heating rods disposed in the back plate raise the temperature of the back plate and thereby the heater plate and fuel sample, causing thermal decomposition deposits from the heated fuel to form on the flat surface of the heater plate. Author (GRA)

N85-17152# Rolls-Royce Ltd., Derby (England).

ROLLS-ROYCE EXPERIENCE WITH THERMAL BARRIER COATINGS

A. BENNETT 1 Aug. 1984 7 p Presented at British Ceramic Soc. Basic Sci. Section Meeting, London, 10-21 Dec. 1983 (PNR-90222) Avail: NTIS HC A02/MF A01

Technical and economic justifications for the use of thermal barrier coatings in aero engines are outlined. Zirconia-based ceramic coating materials are reviewed. The use of metallic and cermet bonding coats is described, particularly oxidation related failure mechanisms. Diagnostic analyses to explain failure mechanisms related to the stresses and strains encountered in major engine cycles are presented. This approach is valuable in clarifying the failure mechanisms and directing research towards effective material and processing improvements. Author (ESA)

N85-17153# SRI International Corp., Menlo Park, Calif. ANALYSIS OF MIDDLE DISTILLATE FUELS BY HIGH **RESOLUTION FIELD IONIZATION MASS SPECTROMETRY** Annual Report, 1 Jun. 1982 - 31 Aug. 1984 R. MALHOTRA, M. J. COGGIOLA, S. E. YOUNG, D. TSE, and S. E. BUTTRILL, JR. 29 Oct. 1984 40 p

(Contract N00014-81-K-2032; F65-511)

(AD-A147724) Avail: NTIS HC A03/MF A01 CSCL 21D

A method for the rapid and detailed chemical characterization of distillate fuels has been developed using high resolution field ionization mass spectrometric (HR-FIMS) techniques. A vintage AEI MS-9 mass spectrometer has been modified to house a volcano-style field ionizer and has been equipped with a high-temperature batch inlet system. Field ionization is particularly useful in this regard because it produces only molecular ions for most compounds and because different compound types do not differ in their ionization efficiencies by more than a factor of four. The mass spectrometer is operated at a resolution of 3000, which is adequate to resolve all the different types of hydrocarbons likely to be present in the fuel sample. Software has been written to present the mass spectrum intensities in a matrix where the various columns represent the different z-series of the hydrocarbons and the rows represent the number of carbon atoms in any given component. Analysis of a stable and an unstable jet fuel showed that the unstable fuel had a substantially higher naphthalene content. ĞRA

N85-17155# Virginia Polytechnic Inst. and State Univ., Blacksburg. Dept. of Chemistry.

GC-FTIR (FOURIÉR TRANSFORM INFRARED SPECTROMETRY) OF JET FUELS Final Report, 15 Jul. 1982 - 15 Aug. 1983 J. R. COOPER and L. T. TAYLOR Feb. 1984 156 p

(Contract F33615-82-C-2258)

(AD-A148272; AFWAL-TR-84-2007) Avail: NTIS HC A08/MF A01 CSCL 07D

The successful interfacing and utilization of fused silica capability gas chromatography (GC) columns with Fourier transform infrared spectrometry (FTIR) can introduce difficulties not usually encountered with lower efficiency (higher capacity) GC columns. Recognition of these difficulties, however, can lead to refinement of a GC-FTIR detection system which can analyze complete samples with low nanogram detection limits. Chromatography and spectrometric considerations include lightpipe temperature, choice of same introduction, column concentration dynamic range capability, infrared data acquisition rate and spectral S/N ratio. These parameters as they relate to capability GC-FTIR method development are discussed. GC-FTIR identification limits for sixteen model compounds which represent both polar and non-polar functionalities have been established employing optimized chromatographic-spectrometric parameters for complex mixture analysis. GRA

12

ENGINEERING

Includes engineering (general); communications; electronics and electrical engineering; fluid mechanics and heat transfer; instrumentation and photography; lasers and masers; mechanical engineering; quality assurance and reliability; and structural mechanics

A85-19491*# United Technologies Corp., East Hartford, Conn. CALCULATION OF CONFINED SWIRLING FLOWS

G. J. STURGESS and S. A. SYED (United Technologies Corp., Engineering Div., East Hartford, CT) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 16 p. refs

(Contract NAS3-235924; NAS3-23686)

(AIAA PAPER 85-0060)

Swirling jets are an important constituent flow of many types of combustion equipment. Flame size, shape, stability and combustion intensity are all favorably influenced by swirling some portion of the incoming air with the fuel. Fluid dynamics computer codes are being developed for the mathematical simulation of flows in practical combustors. It is important that these codes have the ability to accurately and reliably calculate swirling flows. Turbulent flow calculations with swirl can be inaccurate due to at least three major reasons: limitations of the turbulence modeling used, incorrect or inadequate specifications of inlet boundary conditions, and, error introduced through the numerics. These sources of error are described, and examples provided of each. The state-of-the-art in such calculations is reviewed. The controlling character of current numerics is demonstrated, and it is concluded that as a first priority, better numerics must be arrived at, and that an improved understanding of the discharge flow from swirl generators is essential as a second priority. When these priorities are satisfied an improved turbulence model is desirable. It is also concluded that an improved understanding of swirl-induced recirculation would be an asset. Author

A85-19520#

FLOW VISUALIZATION OF HIGH ANGLE OF ATTACK VORTEX WAKE STRUCTURES

R. C. NELSON (Notre Dame, University, Notre Dame, IN) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 11 p. refs (AIAA PAPER 85-0102)

Various flow visualization techniques and associated data on high angle of attack (AOA) aerodynamics are surveyed. Schlieren photography records density gradients in the flowfield when incident light is refracted by the gas to different degrees due to density variations. Three-dimensional vortex trajectory data are obtained by taking the photographs in two mutually orthogonal planes. Vortices and shocks are revealed by pumping a mist into the test channel flow and illuminating the resulting artificial fog with a thin sheet light beam, a technique called vapor screen photography. Low speed flow features can be recorded by introducing dye tracers into the mist. Substitution of smoke for the fog and using laser sheet light as the luminance source comprises the smoke streakline method, which yields images for characterizing vortex behavior and evolution. M.S.K.

A85-19575#

COMPUTATION OF RECIRCULATING COMPRESSIBLE FLOW IN AXISYMMETRIC GEOMETRIES

K. M. ISAAC (Missouri-Rolla, University, Rolla, MO) and A. S. NEJAD (USAF, Aero Propulsion Laboratory, Dayton, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (Contract F49620-82-C-0035)

(AIAA PAPER 85-0185)

A computational study of compressible, turbulent, recirculating flow in axisymmetric geometries is reported in this paper. The SIMPLE algorithm was used in the differencing scheme and the k-epsilon model for turbulence was used for turbulence closure. Special attention was given to the specification of the boundary conditions. The study revealed the significant influence of the boundary conditions on the solution. The eddy length scale at the inlet to the solution domain was the most uncertain parameter in the specification of the boundary conditions. The predictions were compared with the recent data based on laser velocimetry; the two are seen to be in good agreement. The present study underscores the need to have a more reliable means of specifying the inlet boundary conditions for the k-epsilon turbulence model.

Author

A85-19706#

EVALUATION OF LOW REYNOLDS NUMBER TURBULENCE MODELS FOR ATTACHED AND SEPARATED FLOWS

A. SUGAVANAM (Lockheed-Georgia Co., Marietta, GA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 12 p. refs (AIAA PAPER 85-0375)

Time-averaged Navier-Stokes and boundary layer computations have been performed to study the algebraic and the two-equation turbulence models in complex flows. Special attention is paid to the near-wall behavior of the low Reynolds number turbulence models of Jones-Launder and Chien. The mean flow and turbulence predictions are compared with reliable experimental data. Both the algebraic and the two-equation turbulence models are found to predict the mean flow characteristics very well. However, the Chien k-epsilon model is found to perform better than other models in predicting turbulence characteristics. Also this model is found to have fewer numerical problems compared to the other two-equation models included in the study.

ANALYSIS AND TESTING OF THE DIAMOND ONE WING ANTI-ICING SYSTEM

K. E. YEOMAN (KEY Industries Corp., San Antonio, TX) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs (AIAA PAPER 85-0414)

The Diamond One wing leading edge is protected against ice accretions by a bleed air anti-icing system. Three cross-sections selected for computer modeling considered the thermal mechanisms of convection, conduction, evaporation and sensible heating of impinged and runback water. With an instrumented aircraft, the model was refined using dry air and above freezing cloud flight test data. The refined model was exercised for wing surface temperature predictions for six critical icing conditions and found safe for natural icing flight testing. Measured natural icing test data was then inserted into the model to compare predicted vs. measured temperatures. Correlation was achieved and the system was accepted by FAA as safe for flight into known icing conditions.

A85-19754#

FREE SURFACE SCARS AND STRIATIONS DUE TO TRAILING VORTICES GENERATED BY A SUBMERGED LIFTING SURFACE

T. SARPKAYA (U.S. Naval Postgraduate School, Monterey, CA) and D. O. HENDERSON, JR. (U.S. Naval Postgraduate School, Monterey, CA; U.S. Navy, Charleston Naval Shipyard, Charleston, SC) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(AIAA PAPER 85-0445)

The characteristics of the surface signatures (scars and striations) resulting from the interaction of the ascending trailing vortices with the free surface have been investigated. The vortices were generated by towing horizontally various lifting surfaces (delta wings and rectangular foils of different shape and aspect ratio) well below the free surface at prescribed speeds, depths, anda negative angles of attack. The evolution of each type of surface signature has been expressed in terms of the governing parameters such as the depth of generation, mutual induction velocity, and the initial spacing of the vortex pair. It has been shown that the surface signatures are created and driven by trailing vortices and vortex rings. Two turbulent vortex models have been used to predict the apparent circulation of the vortices and the observed characteristics of the scar tracks.

A85-19769#

MEASUREMENT OF ICE ACCRETION USING ULTRASONIC PULSE-ECHO TECHNIQUES

R. J. HANSMAN, JR. and M. S. KIRBY (MIT, Cambridge, MA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. (AIAA PAPER 85-0471)

Results of tests to measure ice thickness using ultrasonic pulse-echo technique are presented. Tests conducted on simulated glaze and rime ice, and ice crystals are described. Additional tests on glaze and rime ice samples formed in the loing Research Tunnel at NASA Lewis are also described. The speed of propagation of the ultrasonic wave used for pulse-echo thickness measurement is found to be insensitive to the type of ice structure, and is determined to be 3.8 mm/microsec. An accuracy of + or - 0.5 mm is achieved for ice thickness measurement using this technique. Author

A85-19832

PRECALCULATION OF ROTATING STALL IN MULTISTAGE AXIAL COMPRESSORS [BEITRAG ZUR VORAUSBERECHNUNG DES ROTATING STALL IM MEHRUSTUFIGEN AXIALVERDICHTER]

D. TANG Aachen, Rheinisch-Westfaelische Technische Hochschule, Fakultaet fuer Maschinenwesen, Dr.-Ing. Disertation, 1983, 93 p. In German. refs

The present investigation is concerned with the development of a nonlinear model for predicting rotating stall. Previously, the nonlinear model could only be employed in cases involving a single stage. An analysis of the effects found in cases involving several stages makes it possible to adapt this model for a precalculation of the rotating stall in a multistage compressor. The boundary conditions in the model developed by Takata and Nagano (1972) and in the model reported by Orner (1979) make it impossible to consider the effects of a use of several stages. In the current investigation, an 'interface' is used to consider the influence of adjacent stages. The obtained nonlinear model is employed in the case of a single-stage design and a two-stage design. It was found possible to calculate the important data, including the beginning of rotating stall, the rotational frequency of the stall cells, and the left branch of the characteristic. A basic problem in the case of a nonlinear model of the rotating stall is related to the continuous increase in the amplitude of the stall cells. GR

A85-19837

REFLECTOR ANTENNAS WITH DIRECTIONAL EFFECT IN THE NEAR-FIELD CHARACTERISTICS AND APPLICATIONS [REFLEKTORANTENNEN MIT RICHTWIRKUNG IM NAHFELD -EIGENSCHAFTEN UND ANWENDUNGEN]

W. HOLZ Stuttgart, Universitaet, Dr.-Ing. Dissertation, 1983, 112 p. In German. refs

The present investigation is concerned with the characteristics and applications of reflector antennas with a radiation field which is focused on a point in the antenna near field. Scalar diffraction theory is employed to study apertures with a spherical phase front and a convergence of the radiation in the focus. Particular attention is given to the radiation field of the rectangular and circular focusing aperture. The radiation field of elliptical reflectors is studied with the aid of a vectorial approximate calculation. An application area of focusing antennas related to position finding is considered, taking into account the antenna of a radar for monitoring an aircraft landing field. In this radar system, the considered objects are partly or entirely in the antenna near field. Applications related to antenna measurement techniques are also discussed, taking into account focusing in the case of a parabolic reflector and the computation of radiation patterns. G.R.

A85-19886

THE HYDRAULIC AND ELECTROHYDRAULIC ELEMENTS USED IN FLIGHT SIMULATORS (HYDRAULICKE A ELEKTROHYDRAULICKE PRVKY PRO STAVBU LETECKYCH SIMULATORU]

P. BERGMANN (TST, Rakovnik, Czechoslovakia) Zpravodaj VZLU (ISSN 0044-5355), no. 5, 1984, p. 299-301. In Czech. refs

The advantages of using hydraulic and electrohydraulic components in flight simulators are reviewed. In particular, it is noted that hydraulic and electrohydraulic mechanisms afford simple implementation of rectilinear motion with high dynamic characteristics, simple overload protection, and high density of power transmission, providing for small size and weight. Data are presented on the components commercially available in Czechoslovakia that can be used in flight simulators. The principal trends in the development of hydraulic and electrohydraulic components abroad are reviewed.

A85-20232#

A METHOD FOR CALCULATING THE PERFORMANCE OF EJECTOR NOZZLES

H. QIAN, M. ZHANG, and G. YE Journal of Engineering Thermophysics, vol. 5, Feb. 1984, p. 47-50. In Chinese, with abstract in English.

The conventional assumption that secondary flow is a one-dimensional isentropic and that the pressure of both primary and secondary flow are equal has been modified in this paper. The pressure of primary and secondary is calculated by means of the relation between front and back parameters of the shock or Mach shock, and the ejector nozzle performance is determined using the equations between the inlet section and other characteristic sections. Calculation results of this paper have been verified by means of experimental data, and quite good agreement is obtained. Author

A85-20452

DETERMINATION OF THE OPTIMAL PARAMETERS OF AIRCRAFT STRUCTURAL ELEMENTS IN THE FORM OF SANDWICH PLATES AND SHALLOW SHELLS WITH A HONEYCOMB FILLER [OB OPREDELENII OPTIMAL'NYKH PARAMETROV ELEMENTOV AVIATSIONNYKH KONSTRUKTSII TIPA TREKHSLOINYKH PLASTIN I POLOGIKH OBOLOCHEK S SOTOVYM ZAPOLNITELEM]

A. IA. ALEKSANDROV and M. I. NAUMOVA IN: Current problems in aviation science and technology . Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 4-14. In Russian. refs

Graphic and iterative methods are used to determine the minimum-weight parameters of sandwich plates and shallow shells with honeycomb filler under uniform longitudinal compression and uniform heating. The analysis takes into account the effect of initial fabrication-related defects on the structural strength. Results are presented for plates with D16AT alloy layers and for a cylindrical panel.

A85-20454

THEORY OF VIBRATION CONDUCTION AS A METHOD FOR CALCULATING THE VIBRATION OF COMPLEX STRUCTURES [TEORIIA VIBROPROVODNOSTI KAK METOD RASCHETA VIBRATSII SLOZHNYKH KONSTRUKTSII]

A. K. BELIAEV and V. A. PALMOV IN: Current problems in aviation science and technology . Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 29-37. In Russian. refs

A vibration-conduction theory (VCT) is proposed which is a means to describe and analyze the high-frequency random vibration of complex dynamic objects (e.g., aircraft structures) by methods of heat-conduction theory. A differential equation of heat-conduction type is obtained, and methods for formulating the boundary and initial conditions are described. The parameters of the VCT are expressed through the mean mechanical characteristics of the object, e.g., the mean density, the mean stiffness, and the frequency-dependent parameter of vibration absorption by the structure. Temperature is represented as a linear function of the spectral densities of accelerations of points of the object in the direction of its orthotropy axes. The nonnegativity and uniqueness of the solution are proved.

A85-20459

CURRENT PROBLEMS IN THE THEORY OF PLATES AND SHELLS IN AIRCRAFT (SOVREMENNYE PROBLEMY TEORII PLASTINOK I OBOLOCHEK V LETATEL'NYKH APPARATAKH] A. S. VOLMIR IN: Current problems in aviation science and technology. Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 77-87. In Russian. refs

A survey is made of recent theoretical and experimental studies of plates and shells considered as elements of aircraft and their engines. Particular emphasis is placed on the application of finite-difference and finite-element methods, and attention is given to such examples as aircraft with large or small aspect-ratio wings, superelements for helicopter rotors, and the centrifugal wheel of a gas-turbine compressor. Also considered are problems of dynamic

stability and fracture mechanics. Finally, problems which will require study and solution in the 1980's and 1990's are discussed. B.L

A85-20460

SELECTION OF RATIONAL MODELS IN THE OPTIMAL PLANNING OF AEROMECHANICAL EXPERIMENTS [VYBOR RATSIONAL'NYKH MODELEI V ZADACHAKH OPTIMAL'NOGO PLANIROVANIJA **AEROMEKHANICHESKOGO** EKSPERIMENTA]

G. L. GRODZOVSKII IN: Current problems in aviation science and technology . Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 88-95. In Russian. refs

The paper describes an approach to the development of rational models for the statistical description of aeromechanical experiments involving balance measurements of aerodynamic forces and moments. The approach makes it possible to apply the maximum likelihood method, resulting in a rigorous solution to the inverse problem of mathematical statistics. B.J.

A85-20463

DESIGN OF LOAD-BEARING AIRCRAFT STRUCTURES PROEKTIROVANIE SILOVYKH SKHEM AVIATSIONNYKH KONSTRUKTSII)

V. A. KOMAROV IN: Current problems in aviation science and technology . Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 114-129. In Russian. refs

A method for the computer-aided design of load-bearing structures is proposed which is based on the determination of theoretically optimal structures using continuum models, followed by a graphic analysis of rational pathways of force transmission. Attention is given to the design characteristics of planar structures, wings, fuselages, and arbitrary three-dimensional elastic systems. The development of detailed finite-element methods is considered as the culminating stage in the design of the load-bearing structures. B.J.

A85-20472

AEROELASTIC STABILITY AND VIBRATION OF LAYERED PLATES AND CYLINDRICAL SHELLS [AEROUPRUGAIA USTOICHIVOST' I KOLEBANIIA SLOISTYKH PLASTIN I TSILINDRICHESKIKH OBOLOCHEK]

A. I. SMIRNOV IN: Current problems in aviation science and technology . Moscow, Izdatel'stvo Mashinostroenie, 1984, p. 190-197. In Russian. refs

Exact solutions have been obtained for boundary value problems concerning the vibration and supersonic flutter of sandwich plates and cylindrical shells. Results of parametric studies are presented which provide information on the effect of flow parameters, plate and shell material and geometry, median surface forces, and boundary conditions on the natural frequencies and modes of vibrations, both in vacuum and in gas flow. The mechanisms of flutter and divergence are discussed. VI

A85-20501

ADVANCES IN HEAT TRANSFER. VOLUME 16

J. P. HARTNETT, ED. (Illinois, University, Chicago, IL) and T. F. IRVINE, JR., ED. (New York, State University, Stony Brook, NY) Orlando, FL, Academic Press, Inc., 1984, 399 p. For individual items see A85-20502 to A85-20503.

The diffusion of turbulent buoyant jets is considered along with the boiling of multicomponent liquid mixtures, heat flow rates in saturated nucleate pool boiling, and a review of turbulent-boundary-layer heat transfer research at Stanford, 1958-1983. In connection with the boiling of mulitcomponent liquid mixtures, attention is given to the fundamentals of vapor-liquid phase equilibria, the inception of boiling, bubble growth, bubble departure, nucleate pool boiling heat transfer, prediction of nucleate boiling heat transfer coefficients, peak nucleate heat flux, film boiling, and convective boiling. A wide-ranging examination using reduced properties is conducted in the study of heat flow rates in saturated nucleate pool boiling. G.R.

288

A85-20800

ON THE EXCITATIONS DUE TO THE PERIODIC STRUCTURE OF TURBOMACHINES [UEBER DIE ERREGUNG INFOLGE DER PERIODISTITAET VON TURBOMASCHINENI

M. DUBAS (Sulter-Escher Wyss AG, Zurich, Switzerland) Ingenieur-Archiv (ISSN 0020-1154), vol. 54, no. 6, 1984, p. 413-426. In German. refs

In the present paper, the excitation caused by the periodical character of the rotor and the stator of turbomachines of any kind is investigated. The basic assumption is that, each time a runner blade passes a guide vane, a radial, a tangential and an axial load are produced. With the help of three simple mathematical models, the forces adn moments and especially their frequencies resulting from all these loads are determined. Depending on the position in time and space of each impulse and on the considered resultant, namely, that acting on the shaft, on a blade, or on the disk, these resultants have other properties. Furthermore, in the case of vibrations of shafts and disks, in addition to the known resonance condition, i.e., excitation frequency = natural frequency, an existence condition depending on the number of blades has to be taken into account. Author

A85-20828

OPTIMIZATION OF FLUTTER CHARACTERISTICS (OPTIMIZATSIIA FLATTERNYKH KHARAKTERISTIK)

A. P. SEIRANIAN and A. V. SHARANIUK (Akademiia Nauk SSSR, Institut Problem Mekhaniki, Moscow, USSR) Akademiia Nauk Armianskoi SSR, Izvestija, Mekhanika (ISSN 0002-3051), vol. 37, no. 5, 1984, p. 38-51. In Russian. refs

Nonconservative elastic stability problems in discrete systems are considered. Expressions are obtained for the derivatives of the critical stability parameters by means of a system of coupled equations. A number of problems connected with the optimization of flutter characteristics in a low aspect ratio wing in a gas flow are discussed as examples. Numerical results are presented.

I.H.

A85-20852#

APPLICATION OF DIGITAL INTERFEROGRAM EVALUATION TECHNIQUES то THE MEASUREMENT OF THREE-DIMENSIONAL FLOW FIELDS

F. BECKER and Y. H. YU (U.S. Army, Aeromechanics Laboratory, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 16 p. refs (AIAA PAPER 85-0037)

A system for digitally evaluating interferograms, based on an image-processing system connected to a host computer, has been implemented. The system supports one- and two-dimensional interferogram evaluations. Interferograms are digitized, enhanced, and then segmented. The fringe coordinates are extracted, and the fringes are represented as polygonal data structures. Fringe numbering and fringe interpolation modules are implemented. The system supports editing and interactive features, as well as graphic visualization. An application of the system to the evaluation of double-exposure interferograms from the transonic flow field around a helicopter blade and the reconstruction of the three-dimensional flow field is given. Author

A85-20874#

EXPERIMENTAL AND THEORETICAL ANALYSIS OF LAMINAR SEPARATION BUBBLES

E. WEIBUST, A. BERTELRUD, and S. O. RIDDER (Flygtekniska Forsoksanstalten, Bromma, Sweden) American Institute of Aeronautics and Astronautics, Applied Aerodynamics Conference, 2nd, Seattle, WA, Aug. 21-23, 1984. 12 p. Research sponsored by the Styrelsen for Teknisk Utveckling. refs (AIAA PAPER 84-2201)

Experimental and computational results from flow in and around laminar separation bubbles are given, with emphasis on the reattachment region. The experimental bubble parameters are correlated with existing formulae, utilizing a novel method of measuring with dense spacing in and behind the rear part of the

bubble. Removal of the separation bubble by means of a transition trip is discussed. Author

A85-20884

OFF-DESIGN POINT CHARACTERISTICS OF THE PRECOOLED GAS TURBINE CYCLE WITH LIQUEFIED HYDROGEN AS FUEL

Y. TSUJIKAWA and T. SAWADA (Osaka Prefecture, University, Sakai, Japan) International Journal of Hydrogen Energy (ISSN 0360-3199), vol. 9, no. 12, 1984, p. 1011-1017. refs

The off-design point performance of a precooled gas turbine cycle fueled with liquid hydrogen is analyzed. The gas turbine equips the precooler and hydrogen turbine in order that the cryogenic exergy (available energy) can be effectively converted to useful work. The design point is determined by using an estimating function, F. The thermodynamic analysis reveals that even at the off-design point working conditions the thermal efficiency of this cycle is also relatively high compared to that of conventional gas turbine cycle and the load factor decreases in keeping with the decrease in the temperature of the working fluid at the inlet of the gas turbine. Author

A85-20915#

RADAR CROSS SECTION LECTURES

A. E. FUHS (U.S. Naval Postgraduate School, Monterey, CA) New York, American Institute of Aeronautics and Astronautics, 1984, 132 n refs

A comprehensive account is given of the principles that can be applied in military aircraft configuration studies to minimize the radar cross section (RCS) that will be presented by the resulting design to advanced radars under various mission circumstances. It is noted that, while certain ECM techniques can be nullified by improved enemy electronics in a very short time, RCS reductions may require as much as a decade of radar development before prior levels of detectability can be reestablished by enemy defenses. Attention is given to RCS magnitude determinants, inverse scattering, the polarization and scattering matrix, the RCSs of flat plates and conducting cylinders, and antenna geometry and beam patterns. O Č

A85-21278#

A THEORETICAL STUDY OF STABILITY OF A RIGID ROTOR UNDER THE INFLUENCE OF DILUTE VISCOELASTIC LUBRICANTS

A. MUKHERJEE (Indian Institute of Technology, Kharagpur, India), R. BHATTACHARYYA, and A. M. RAO DASARY ASME. Transactions, Journal of Tribology (ISSN 0742-4787), vol. 107, Jan. 1985, p. 75-81. refs

(ASME PAPER 84-TRIB-17)

The present investigation is concerned with the determination of stable boundaries of a symmetrical horizontal rigid rotor supported by two identical short bearings using dilute viscoelastic fluids as lubricants. It has been found that the use of viscoelastic lubricants improves the bearing performances at high shear rates. Harnoy (1976) proposed a constitutive equation with a view to separate the contributions of relaxation and normal stress effects. The results presented in the current investigation are essentially dependent on the stress relaxation effect and may be qualitatively valid for a large class of fluids. Harnoy's constitutive equation is adopted only as it rationally permits the deletion of the Weissenberg effect in short bearings still retaining the objectivity of the constitutive equation. An evaluation is conducted of the dynamic performance of a short bearing using viscoelastic lubricants in the light of Harnov's ideas. G.R.

A85-21283#

EFFECTS OF TURBULENCE AND VISCOSITY VARIATION ON THE DYNAMIC COEFFICIENTS OF FLUID FILM JOURNAL BEARINGS

D. F. WILCOCK (Tribolock, Inc., Schenectady, NY) and O. PINKUS (Mechanical Technology, Inc., Latham, NY) American Society of Mechanical Engineers and American Society of Lubrication Engineers, Joint Lubrication Conference, San Diego, CA, Oct. 22-24, 1984. 6 p. refs (ASME PAPER 84-TRIB-8)

Many high-speed or large fluid film bearings operate in the turbulent regime. However, relatively little consideration has been given to the effects of turbulence and of the variation in viscosity on the dynamic stiffness and damping characteristics of the bearings. Since the dynamic behavior of the rotor supported on such bearings is often closely tied to the bearing dynamic coefficients, knowledge of them may be critical to both the design and the in-place correction of rotor instabilities. These effects are here considered in some detail on the basis of computer calculated analytical results, both in general dimensionless terms and with regard to a specific numerical example. Author

A85-21293*# Texas A&M Univ., College Station.

FOR ROTORDYNAMIC ANALYSIS AND TESTING COEFFICIENTS OF TURBULENT ANNULAR SEALS WITH DIFFERENT. **DIRECTIONALLY-HOMOGENEOUS** SURFACE-ROUGHNESS TREATMENT FOR ROTOR AND STATOR ELEMENTS

D. W. CHILDS and C.-H. KIM (Texas A & M University, College Station, TX) American Society of Mechanical Engineers and American Society of Lubrication Engineers, Joint Lubrication Conference, San Diego, CA, Oct. 22-24, 1984. 10 p. refs (Contract NAS8-33716)

(ASME PAPER 84-TRIB-31)

A combined analytical-computational method has been developed to calculate the transient pressure field and rotordynamic coefficients for high-pressure annular seals. The solution procedure applies to constant-clearance or the convergent tapered geometries of multistage centrifugal pumps which may have different surface roughness conditions on the stator and rotor seal elements. In experimental calculations with the method, the turbulent equations of Hirs (1973) are modified slightly to account for different surface roughness conditions, and a perturbation analysis is employed to develop zeroth and first order perturbation equations. Zeroth equations are also used to define both the leakage and circumferential flow due to shear stresses around the stator and rotor surfaces. The solution to analytical equations for four different surface roughnesses confirm the predicted net damping for the seals. A round-holed stator pattern yielded the highest net damping and lowest leakage of all the seals tested. IH.

A85-21296#

STABILITY OF SQUEEZE FILM DAMPED MULTI-MASS FLEXIBLE ROTOR BEARING SYSTEMS

E. J. HAHN (New South Wales, University, Kensington, Australia) and L. J. MCLEAN American Society of Mechanical Engineers and American Society of Lubrication Engineers, Joint Lubrication Conference, San Diego, CA, Oct. 22-24, 1984. 8 p. refs (ASME PAPER 84-TRIB-45)

A technique is presented for investigating the stability of and the degree of damping in the circular synchronous orbit equilibrium solutions pertaining to radially symmetric multi-mass flexible rotor bearing systems. It involves the analysis of appropriate linearized perturbation equations about the equilibrium solutions and is applicable to systems with several squeeze film dampers. For a system with a single damper, stability threshold maps, independent of unbalance distribution, may be found in terms of the same damper parameters and operating conditions as the equilibrium solutions, thereby allowing for damper design and performance monitoring. The technique is illustrated is illustrated for a simple symmetric four degree of freedom flexible rotor with an unpressurized damper. This example shows the utility of zero frequency stability maps for delineating multiple solution possibilities

and that for low (in this case of the order of 0.06 or lower) bearing parameters, the introduction of an unpressurized squeeze film damper may promote instability in an otherwise stable system.

Author

A85-21385

ADVANCED-COMPOSITE JOINTS AND FITTINGS FOR PRIMARY STRUCTURAL COMPONENTS

H. S. SALUJA (Boeing Vertol Co., Philadelphia, PA) IN: Composite structures; Proceedings of the National Specialists' Meeting, Philadelphia, PA, March 23-25, 1983. Washington, DC, American Helicopter Society, 1984, 3 p.

This paper discusses advanced-composite bonded and bolted joints and their applications for primary structural components. Also discussed are a bolted primary structural joint design for a composite longeron and the longeron itself made of T300/5209 graphite/epoxy caps supported by honeycomb core. Tension, compression, pin bearing, and combined tension and bearing coupon tests were performed on the longeron cap. Two designs for the composite longeron splice fitting were considered: a hairpin fitting and a T-fitting. The joint tests were successful in meeting ultimate design loads of 44,700 and 42,300 pounds in tension and compression, respectively. A conclusion was drawn from the test results regarding the effect of bearing stresses on the ultimate strength of the joint.

A85-21460#

PACKAGING AND INTERCONNECTION FOR AVIONICS

N. CHANDLER (General Electric Co., PLC, Research Laboratories, Chelmsford, Essex, England) IN: Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984. London, Royal Aeronautical Society, 1984, 7 p.

Following some examples of current equipment practice in avionics, future alternatives are discussed in terms of the various types of package and interconnection medium, particularly in relation to the increasing scale of integration on silicon. Assembly requirements are briefly addressed and a summary is given of trends in packaging and interconnection for avionics. Author

A85-21683

THE DEVELOPMENT OF A FINITE ELEMENT MODEL OF AN AIRCRAFT VERTICAL STABILIZER FOR VIBRATION ANALYSIS

R. J. MCKINNELL (Council for Scientific and Industrial Research, National Institute for Aeronautics and Systems Technology, Pretoria, Republic of South Africa) Aeronautical Society of South Africa and South African Institute of Aeronautical Engineers, Journal (ISSN 0250-3786), vol. 5, no. 1, 1984, p. 52-55. refs

A finite element idealization of the vertical stabilizer of a light transport aircraft was generated and a linear dynamic analysis of the structure was carried out using the ASKA software package. The structure was modeled using primarily normal-stress flange elements and plane-stress membrane elements. Ground vibration testing of the stabilizer was also used to find natural frequencies and modal response at resonance. The first five modes of vibration of the structure were investigated. Comparison of calculated and measured modal frequencies and modeshapes showed that the model generated could be successfully used in dynamic analysis, although some refinement would be necessary to increase accuracy. Author

A85-21846*# Purdue Univ., Lafayette, Ind.

VIBRATION TAILORING OF ADVANCED COMPOSITE LIFTING SURFACES

T. A. WEISSHAAR (Purdue University, West Lafayette, IN) and B. L. FOIST (Northrop Corp., Advanced Systems Div., Pico Rivera, CA) (Structures, Structural Dynamics and Materials Conference, 24th, Lake Tahoe, NV, May 2-4, 1983, Collection of Technical Papers. Part 2, p. 498-508) Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. 1985, p. 141-147. Navy-supported research. Previously cited in issue 12, p. 1744, Accession no. A83-29861. refs (Contract NAG1-157) A85-21875*# National Aeronautics and Space Administration... Langley Research Center, Hampton, Va.

NOÑRÉFLECTING BOUNDARY CONDITIONS FOR THE COMPLETE UNSTEADY TRANSONIC SMALL-DISTURBANCE EQUATION

W. WHITLOW, JR. and D. A. SEIDEL (NASA, Langley Research Center, Loads and Aeroelasticity Div., Hampton, VA) AIAA Journal (ISSN 0001-1452), vol. 23, Feb. 1985, p. 315-317. refs

Nonreflecting far-field boundary conditions that are consistent with the complete transonic small-disturbance (TSD) equations are derived. They are implemented in a new code for solving the complete TSD equation and are tested for a harmonically oscillating NACA 64A010 airfoil in transonic flow and for a flat-plate airfoil with a pulse in the angle of attack. Using the new boundary conditions on a relatively small grid, solutions for the airfoil that are obtained that agree with large-grid calculations, resulting in a 44 percent savings in computer time. Frequency responses for the flat plate show that most of the disturbances incident on the computational boundaries are absorbed by the boundary conditions. C.D.

A85-21985

AN OPTIMALITY CRITERION METHOD FOR STRUCTURES WITH STRESS, DISPLACEMENT AND FREQUENCY CONSTRAINTS

A. ZACHAROPOULOS, K. D. WILLMERT (Clarkson University, Potsdam, NY), and M. R. KHAN (Bechtel Corp., Power Div., San Francisco, CA) Computers and Structures (ISSN 0045-7949), vol. 19, no. 4, 1984, p. 621-629. refs

Presented in this paper is a procedure, based on optimality criterion methods, for the minimum weight design of structures subjected to stress, displacement and natural frequency constraints. The technique presented is a combination of a previously developed method for stress and displacement constraints alone and one for frequency limited structures. The method is applied to a delta-wing example, and the optimal designs obtained are compared to previously published results. The new method is capable of obtaining the optimal design in a small number of iterations, without significant calculations beyond a standard analysis. No approximate analyses or determination of large numbers of Lagrange multipliers are involved.

A85-22105

OPTIMAL CONTROL OF FLOW OF A VISCOUS INCOMPRESSIBLE FLUID [OB OPTIMAL'NOM UPRAVLENII POTOKOM VIAZKOI NESZHIMAEMOI ZHIDKOSTI]

M. A. BRUTIAN and P. L. KRAPIVSKII Prikladnaia Matematika i Mekhanika (ISSN 0032-8235), vol. 48, Nov.-Dec. 1984, p. 929-934. In Russian. refs

Flow of a viscous incompressible fluid past an arbitrary body, with tangential or normal velocity being controlled on its surface, is analyzed using Navier-Stokes equations. The necessary conditions for minimum energy dissipation rate are derived. Exact analytical solutions for the corresponding problems in the case of flow past an ellipsoid are obtained using the Stokes approximation. V.L.

A85-22113

CALCULATION OF THE HYDRODYNAMIC CHARACTERISTICS OF POLYPLANES [ROZRAKHUNOK GIDRODINAMICHNIKH KHARAKTERISTIK POLIPLANIV, SHCHO KOLIVAIUT'SIA]

O. A. SHCHIPTSOV (Akademiia Nauk Ukrains'koi RSR, Institut Gidromekhaniki, Kiev, Ukrainian SSR) Akademiia Nauk Ukrains'koi RSR, Dopovidi, Seriia A Fiziko-Matematichni ta Tekhnichni Nauki (ISSN 0002-3531), Nov. 1984, p. 46-48. In Ukrainian.

The problem of the oscillatory motion of a polyplane in an ideal incompressible fluid is solved in a linear formulation using the discrete vortex method. Results of numerical calculations are presented as plots of the coefficient of the longitudinal force component vs the dimensionless motion velocity. The results can be useful in evaluating the efficiency of various propulsion systems.

A85-22114

CALCULATION OF FRICTION AND HEAT TRANSFER IN TURBULENT FLOW OF A COMPRESSIBLE GAS IN A PLANE DUCT [RASCHET TRENIIA I TEPLOOBMENA PRI TURBULENTNOM TECHENII SZHIMAEMOGO GAZA V PLOSKOM KANALE]

IU. I. SHVETS, I. E. VIROZUB, V. F. VISHNIAK, N. M. KONDAK, V. N. PANCHENKO, and G. A. FROLOV (Akademiia Nauk Ukrainskoi SSR, Institut Tekhnicheskoi Teplofiziki, Kiev, Ukrainian SSR) Inzhenerno-Fizicheskii Zhurnal (ISSN 0021-0285), vol. 48, Jan. 1985, p. 19-23. In Russian. refs

Equations of turbulent flow of a compressible gas in a plane duct, with uniform velocity and temperature profiles at the inlet, are integrated numerically. It is assumed that the molecular viscosity coefficient is proportional to temperature, while the turbulent viscosity coefficient is determined on the basis of the Prandtl hypothesis with a damping multiplier. Calculations for the case of constant wall temperature during cooling are compared with experimental data. V.L.

A85-22168

EVALUATION OF THE FORWARD SCATTERING SPECTROMETER PROBE. I ELECTRONIC AND OPTICAL STUDIES

J. E. DYE and D. BAUMGARDNER (National Center for Atmospheric Research, Boulder, CO) Journal of Atmospheric and Oceanic Technology (ISSN 0739-0572), vol. 1, Dec. 1984, p. 329-344. refs

Laboratory studies of the Forward Scattering Spectrometer Probe (FSSP) were conducted to better understand the operation. to determine limitations and to define the measurement accuracy of the instrument for airborne cloud physics research. The studies included electronic checks of the instrument sensitivity to simulated particles of different sizes, airspeeds and arrival rates; measurement of important aspects of the optical configuration; and intercomparisons of six different FSSPs in a small wind tunnel with a droplet spray. The tests demonstrated measurement differences between various probes in several areas as well as areas in which there was reasonable agreement. Part of the differences can be attributed to different feature and design specifications of different probes as changes were made to improve the FSSP. Areas in which care needs to be taken in the calibration and processing of data from the FSSP are identified. Author

A85-22232#

UNIVERSAL MATRICES TO OBTAIN THERMAL LOAD VECTORS FOR THE FAMILY OF ANISOTROPIC PLANE TRIANGULAR FINITE ELEMENTS

C. RAMESH BABU and G. SUBRAMANIAN (Indian Institute of Technology, Madras, India) Aeronautical Society of India, Journal (ISSN 0001-9267), vol. 36, May 1984, p. 137-140.

Finite element techniques are applied to the thermal load analysis of aircraft and rocket structures subjected to kinetic heating conditions. Expressions are derived which define the universal matrices for anisotropic elements with temperatures prescribed at every node. Calculations are performed for E-glass/epoxy and carbon/epoxy plates with linear temperature variation from -50 to +50 C and the results are shown to agree well with previous isotropic calculations. Basic universal matrices for the CST, LST, and QST elements are given. The algorithm, easily adapted for computers, can be extended to three-dimensional tetrahedral elements.

A85-22240

CALCULATION OF THREE-DIMENSIONAL UNSTEADY INCOMPRESSIBLE FLOWS BY A VORTEX METHOD [CALCUL D'ECOULEMENTS TRIDIMENSIONNELS INSTATIONNAIRES INCOMPRESSIBLES PAR UNE METHODE PARTICULAIRE]

S. HUBERSON (CNRS, Laboratoire d'Informatique pour la Mecanique et les Sciences de l'Ingenieur, Orsay, Essonne, France) Journal de Mecanique Theorique et Appliquee (ISSN 0750-7240), vol. 3, no. 5, 1984, p. 805-819. In French. refs

A method derived from Rehbach's vortex method which permits the computation of three-dimensional flows of an incompressible fluid around an obstacle with arbitrary motion is presented. In Rehbach's method, the vortex field is discretized by means of turbulence particles. The flow is therefore described by two fields of discrete vectors: the vortex carried by each particle and a vector position characterizing the particle at each step of time. The method is applied to the flow around an oscillating flat plate placed in a uniform stream and is of interest in the study of the flow around complex configurations such as helicopter rotors, propellers, and wings with control surfaces. M.D.

A85-22281* Washington Univ., Seattle.

METALLURGICAL AND MECHANICAL PHENOMENA DUE TO RUBBING OF TITANIUM AGAINST SINTERED POWDER NICHROME

R. ZENAS, T. ARCHBOLD, J. WOLAK, A. F. EMERY, and S. ETEMAD (Washington, University, Seattle, WA) ASLE Transactions, vol. 28, Jan. 1985, p. 97-103. refs (Contract NAG3-7)

Metallurgical and mechanical changes occurring during high-speed rubbing of Ti-6AI-4V blade specimens against an abradable Nichrome aircraft engine seal material were studied using optical microscopy, electron microscopy, and microhardness techniques. Evidence of temperatures above the beta transus of Ti-6AI-4V (1000 C) and of thermal hardening was found on blade tips that exhibited undesirable abrading characteristics resulting in high forces of interaction, high temperatures, and smearing. The material within the layer of the corresponding seals was found to be work-hardened to a depth of about 0.1 mm and showed evidence of densification extending to a depth of about 0.5 mm below the rubbed surface. Wear particles produced by rub interactions that generated cleanly abraded seal surfaces were found to be several times larger than those produced during interactions which showed evidence of surface smearing and seal densification. Author

A85-22445#

A METHOD OF FORECASTING ACTIVE CONSTRAINT WITH THE APPLICATIONS TO STRUCTURAL OPTIMIZATION

Y. JIANG Chinese Society of Astronautics, Journal, no. 4, 1984, p. 44-54. In Chinese, with abstract in English. refs

A new approach to forecasting active constraint in an optimization problem is proposed. The constraints are chosen according to the projective direction, in which the objective function gradients project on the intersection of active constraints previously chosen. The number of active constraints is gradually increased until the cone, which is obtained by the gradient vector of these linearly independent constraints, can contain the objective function gradients. After establishing the explicit representation of the constraints, the method is applied to the DJY-2 structural optimization program similar to ACCESS 1. The high quality constrainat linearization and the precision of constraint forecasting of this method allow almost identical active constraints to be obtained in several adjacent iterations. A space truss, a box wing, and a delta wing are calculated with satisfactory results. It is shown that this method considerably improves computational efficiency. C.D.
N85-15671#----British--Aerospace Aircraft-Group;-Stockport (England). Structures Dept.

ADVANCED FATIGUE MONITORING ON SERVICE AIRCRAFT A. WALKDEN *In* AGARD Operational Loads Data 16 p Aug. 1984 refs

Avail: NTIS HC A14/MF A01

An exercise on a Royal Air Force aircraft where typical service data was collected to: (1) define the loading actions which should be included in a full scale wing fatigue test; (2) enable theoretical fatigue lives for wing, tailplane, fin and undercarriage to be calculated; and (3) define which parameters might be measured in a comprehensive fit of advanced fatigue meters so that the life of the main structural components of each aircraft could be accurately measured is described. R.J.F.

N85-15672# British Aerospace Aircraft Group, Preston (England).

EXPERIENCES OBTAINED FROM SERVICE FATIGUE MONITORING EXERCISES

A. P. WARD In AGARD Operational Loads Data 16 p Aug. 1984 refs

Avail: NTIS HC A14/MF A01

Two recent empennage fatigue load monitoring exercises involving the Jaguar and the Jet Provost aircraft are described. In each case digital recording technique were used and rainflow analysis techniques were employed to determine fatigue loading matrices. Problems were encountered in analysing the recorded data and these are enumerated. The more recent assessment of the Jet Provost provided a high rate of data recovery and benefited from experiences gained from the Jaguar exercise. The conventional method of assessing fin load spectra was found not to provide an adequate safeguard for the later Marks of Jet Provost where significant changes in operating patterns and speeds could not be taken into account adequately by theoretical methods.

R.J.F.

N85-15680# British Aerospace Aircraft Group, Preston (England).

TORNADO: STRUCTURAL USAGE MONITORING SYSTEM (SUMS)

A. P. WARD In AGARD Operational Loads Data 13 p Aug. 1984 refs

Avail: NTIS HC A14/MF A01

The background for the establishment of the tornado structural usage monitoring system (SUMS) is reviewed. The possible monitoring methods and the decision to opt for two approaches using flight parameters and load calibrated strain gauges are amplified. The calibration and instrumentation requirements are described and the use of SUMS data is discussed. E.A.K.

N85-15681# Advisory Group for Aerospace Research and Development, Neuilly-Sur-Seine (France).

KEEPING UP WITH OPERATIONAL LOADS IN THE FRENCH AIR FORCE: DEFINING NEW EQUIPMENT [SUIVI DES CHARGES EN SERVICE DANS L'ARMEE DE L'AIR FRANCAISE DEFINITION D'UN NOUVEAU MATERIEL]

L. BARANES and J. P. CORNAND In its Operational Loads Data 12 p Aug. 1984 In FRENCH

Avail: NTIS HC Å14/MF A01

To remedy the lacunae of present statistical accelerometers for following the operational loads of French Air Force aircraft a system was developed which offers the possibility of acquiring multiple parameters in association with a better data reduction logic. Topics covered include: (1) following real loads with emphasis on problems posed by using simple accelerocomputers; (2) defining the characteristics of the system developed and experience using the prototype; (3) a description of the series version of the prototype system for studying structural damage (SPEES); and (4) applications envisioned and future development considered for SPEES. Transl. by A.R.H. --- N85-15682#- -- Aeritalia · S.p.A., Torino · (Italy). - Gruppo - Velivoli · da Combattimento.

FLIGHT PARAMETERS RECORDING FOR STRUCTURE FATIGUE LIFE MONITORING

F. STAROPOLI In AGARD Operational Loads Data 7 p Aug. 1984 refs

Avail: NTIS HC A14/MF A01

The Tornado flight parameter recording system and its role in structure fatigue life monitoring are described. The system performs both on-board and on-ground recording and analysis functions. The fatigue analysis block program, data filtering subroutine, and damage calculation subroutine are described. The benefits of the system to fleet life management and safety are discussed.

E.A.K.

N85-15683# Aeronautical Systems Div., Wright-Patterson AFB, Ohio. Force Management Group. USAF APPROACH TO AIRBORNE STRUCTURAL DATA

USAF APPROACH TO AIRBORNE STRUCTURAL DATA RECORDING: AIRBORNE DATA ACQUISITION MULTIFUNCTION SYSTEM (ADAMS)

R. J. VELDMAN *In* AGARD Operational Loads Data 3 p Aug. 1984 refs

Avail: NTIS HC A14/MF A01

Current approaches to structural recording and considerations of future instrumentation systems are presented. The current state of the art of microprocessor technology lends itself to the development of airborne recording systems capable of onboard processing and data compression with solid state data storage. Such systems reduce supportability requirements because of increased reliability inherent to solid state electronics while providing processing and self diagnostic capability which were heretofore unachievable. These microprocessor based systems which record structural operational information are designated within the Air Force as the (ADAMS) airborne data acquisition multifunction system. E.A.K.

N85-15746# Brown Boveri Research Center, Baden (Switzerland).

EXPERIENCES WITH THE MATERIAL BEVAVIOUR AND HIGH TEMPERATURE LOW CYCLE FATIGUE LIFE PREDICTION OF THE IN 738 BLADING ALLOY

M. Y. NAZMY, H. WETTSTEIN, and A. WICKI (Brown, Boveri and Co. Ltd, Baden, Switzerland) *In* AGARD Eng. Cyclic Durability by Analysis and Testing 12 p Sep. 1984 refs Avail: NTIS HC A12/MF A01

The high temperature low cycle fatigue (HTLCF) behavior of the blading alloy IN 738 as studied in air at 850 C is studied. This aided in a basic understanding of the behavior of this alloy as well as the different methodologies used in life time prediction. Another part of the investigation was focused on the influence of different environmental effects on the (HTLCF) behavior. These environmental conditions were chosen to simulate as much as possible the actual conditions imposed on the gas turbine blades. Mainly sulfur containing environments were utilized for this purpose. Author

N85-15748# Air Force Wright Aeronautical Labs., Wright-Patterson AFB, Ohio. Turbine Engine Div. VERIFICATION OF LIFE PREDICTION THROUGH COMPONENT TESTING

R. J. HILL In AGARD Eng. Cyclic Durability by Analysis and Testing 9 p Sep. 1984

Avail: NTIS HC A12/MF A01

A status on report on the results of current rig and component testing being conducted under the life assessment testing (LAT) approach to turbine engine durability validation is given. Focus is the combination of using material of reduced life capability and creatin conditions of higher stress to produce short-time failure for cost effective validation of the tools and rules of life prediction. The three components discussed are combustors, compressor disks and turbine blades. B.W. N85-15940 Department of the Air Force, Washington, D.C. **VOICE COMMAND WEAPONS LAUNCHING SYSTEM Patent** H. E. BROWN, inventor (to Air Force) 14 Sep. 1984 7 o

Supersedes AD-D009839

(AD-D011378; US-PATENT-4,471.683:

US-PATENT-APPL-SN-411946: US-PATENT-CLASS-89-1A)

Avail: US Patent and Trademark Office CSCL 17B

This abstract discloses a voice-controlled weapons launching system for use by a pilot of an aircraft against a plurality of simultaneously appearing (i.e., existing) targets, such as two or more aggressor aircraft (or tanks, or the like) attacking more aggressor aircraft. The system includes, in combination, a voice controlled input device linked to and controlling a computer; apparatus (such as a television camera, receiver, and display), linked to and actuated by the computer by a voice command from the pilot, for acquiring and displaying an image of the multi-target area; a laser, linked to and actuated by the computer by a voice command from the pilot to point to (and to lock on to) any one of the plurality of targets, with the laser emitting a beam toward the designated (i.e., selected) target; and a plurality of laser beam-rider missiles, with a different missile being launched toward and attacking each different designated target by riding the laser beam to that target. Unlike the prior art, the system allows the pilot to use his hands full-time to fly and to control the aircraft, while also permitting him to launch each different missile in rapid sequence by giving a two-word spoken command after he has visually selected each target of the plurality of targets, thereby making it possible for the pilot of a single defender aircraft to prevail against the plurality of simultaneously attacking aircraft, or tanks, or the like. GRA

N85-15941 Department of the Air Force, Washington, D.C. EMI (ELECTROMAGNETIC INTERFERENCE) FILTER CAPACITOR UNIT Patent

G. W. MILLER and L. L. MCCLINTOCK, inventors (to Air Force) 7 Aug. 1984 7 p Supersedes AD-D010558 (AD-D011392; US-PATENT-4,464,702;

US-PATENT-APPL-SN-504183; US-PATENT-CLASS-361-328)

Avail: US Patent and Trademark Office CSCL 09E

The unit comprises several rolled capacitor elements in a single case, with a package concept that allows installation mounting and electrical interconnection on the same top plane. A U-shaped feedthrough bus in the form of a wide metal strip is routed from a top input terminal down the center of the case and up adjacent one wall to a top output terminal. The capacitor elements are in two sets on opposite sides of the center portion of the feedthrough bus, and connected thereto. A ground bus serving as an internal noise partition connected to the metal top is between the capacitor elements of one set and the outer portion of the feedthrough bus. A minimum of three units may be used with the variable speed constant frequency (VSCF) converter of the three-phase power supply system of an aircraft, for filtering and suppression of electromagnetic interference. The construction permits use of two input terminals bussed together, and two output terminals bussed together for handling large currents. Author (GRA)

N85-15949# Selenia S.p.A., Rome (Italy). Special System Design Dept.

EQUIPMENT FOR PREFLIGHT TEST OF AN ELECTRONIC COUNTERMEASURES (ECM) AVIONIC SYSTEM

V. BUONTEMPO In its Rivista Tec. Selenia, Vol. 9, No. 1 p 28-36 1984 refs Avail: NTIS HC A03/MF A01

Equipment used for the logistic support of the first level of maintenance of an ECM system is described. Design aspects such as mean time to repair and testability which give appreciable benefits to the readiness for the mission of the ECM system and the strike aircraft which carries it are outlined. Author (ESA)

N85-15954# Human Engineering Labs., Aberdeen Proving Ground, Md.

LITERATURE REVIEW OF VOICE RECOGNITION AND GENERATION TECHNOLOGY FOR ARMY HELICOPTER **APPLICATIONS Final Report**

K. A. CHRIST Aug. 1984 27 p (AD-A146878; HEL-TN-11-84) Avail: NTIS HC A03/MF A01 CSCL 17B

This report is a literature review on the topics of voice recognition and generation. Areas covered are: manual versus vocal data input, vocabulary, stress and workload, noise, protective masks, feedback, and voice warning systems. Results of the studies presented in this report indicate that voice data entry has less of an impact on a pilot's flight performance, during low-level flying and other difficult missions, than manual data entry. However, the stress resulting from such missions may cause the pilot's voice to change, reducing the recognition accuracy of the system. The noise present in helicopter cockpits also causes the recognition accuracy to decrease. Noise-cancelling devices are being developed and improved upon to increase the recognition performance in noisy environments. Future research in the fields of voice recognition and generation should be conducted in the areas of stress and workload, vocabulary, and the types of voice generation best suited for the helicopter cockpit. Also, specific tasks should be studied to determine whether voice recognition and generation can be effectively applied. GRA

N85-15993*# Boeing Commercial Airplane Co., Seattle, Wash. COST AND BENEFITS OPTIMIZATION MODEL FO FOR FAULT-TOLERANT AIRCRAFT ELECTRONIC SYSTEMS Final Report

Jan. 1983 298 p refs

(Contract NAS1-16669)

(NASA-CR-166043; NAS 1.26:166043) Avail: NTIS HC A13/MF A01 CSCL 09C

The factors involved in economic assessment of fault tolerant systems (FTS) and fault tolerant flight control systems (FTFCS) are discussed. Algorithms for optimization and economic analysis of FTFCS are documented. R.S.F.

Air Force Inst. of Tech., Wright-Patterson AFB, N85-16008# Ohio. School of Systems and Logistics.

A BIRD STRIKE HANDBOOK FOR BASE-LEVEL MANAGERS M.S. Thesis

R. P. PAYSON and J. D. VANCE Sep. 1984 223 p (AD-A147928: AFIT/GLM/LSM/84S-52) Avail: NTIS HC

A10/MF A01 CSCL 05A

To help develop more awareness about bird strikes and bird strike reduction techniques, this thesis compiled all relevant information through an extensive literature search, review of base-level documents, and personal interviews. The final product -- A Bird Strike Handbook for Base-Level Managers--provides information on bird strike statistics, methods to reduce the strike hazards, and means to obtain additional assistance. The handbook is organized for use by six major base agencies: Maintenance, Civil Engineering, Operations, Air Field Management, Safety, and Air Traffic Control. An appendix follows at the end. GRA

N85-16065*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

LAMINAR HEAT-TRANSFER DISTRIBUTIONS ON BICONICS AT INCIDENCE IN HYPERSONIC-HYPERVELOCITY FLOWS

C. G. MILLER, III, J. R. MICOL, and P. A. GNOFFO Jan. 1984 145 p refs

(NASA-TP-2213; L-15645; NAS 1.60:2213) Avail: NTIS HC A07/MF A01 CSCL 20D

Laminar heating distributions were measured at hypersonic-hypervelocity flow conditions on a 1.9-percent-scale model of an aeroassisted vehiclee proposed for missions to a number of planets. This vehicle is a spherically blunted, 12.84/7deg biconic with the fore-cone axis bent upward 7 deg relative to the aft-cone axis to provide selftrim capability. Also tested was a straight biconic (i.e., without nose bend) with the same nose radius

and half-angles as the bent-nose biconic. These measurements were made in the Langley Expansion Tube at free-stream velocities from 4.5 to 6.9 km/sec and Mach numbers from 6.0 to 9.0 with helium, nitrogen, air, and carbon dioxide test gases. The range of calculated thermochemical equilibrium normal-shock density ratios for these four test gases was 4 to 19. Angles of attack, referenced to the aft-cone, varied from 0 to 20 deg. Heating distributions predicted with a parabolized Navier-Stokes (PNS) code were compared with measurement for helium and air test gases. Measured windward and leeward heating levels were generally underpredicted by the PNS code for both test gases, and agreement was poorer on the leeward side than on the windward side. Author

N85-16067# Spectron Development Labs., Inc., Costa Mesa, Calif.

AERO-OPTICS EXPERIMENTAL TECHNIQUES Final Technical Report

W. C. ROSE Kirtland AFB, N. Mex. AFWL Jul. 1984 45 p Prepared in cooperation with Rose Engineering and Research Inc.

(Contract F29601-82-C-0013)

(AD-A146755; AFWL-TN-84-30) Avail: NTIS HC A03/MF A01 CSCL 20D

This report summarizes results of a study to determine the most appropriate aerodynamic experimental techniques for gathering data in aircraft boundary layer and shear layer turbulent flow, flow fields. It focuses on two primary techniques: hot-wire anemometry and five-hole pressure probes, and develops reduction equations for obtaining the desired aerodynamic parameters from raw data. It also presents comparison of hot-wire data using splitfilm probes and x-film probes collected during an airborne experiment. GRA

N85-16069# McDonnell-Douglas Corp., Long Beach, Calif. SOME IMPORTANT PROBLEMS IN UNSTEADY BOUNDARY LAYERS INCLUDING SEPARATION. 2: UNSTEADY BOUNDARY LAYERS CLOSE TO THE STAGNATION REGION OF SLENDER BODIES Annual Report, 15 Mar. 1983 - 14 Mar. 1984

T. CEBECI, K. STEWARTSON, and S. M. SCHIMKE Jun. 1984 39 p

(Contract F49620-82-C-0055)

(AD-A146964; MDC-J3527; AFOSR-84-0861TR) Avail: NTIS HC A03/MF A01 CSCL 20D

The evolution of unsteady boundary layers on the plane of symmetry of a slender prolate spheroid in uniform motion at constant angle of attack after an impulsive start has been studied for the case of prescribed pressure distribution. Calculated results have been obtained for angles of attack ranging from 30 degrees to 50 degrees and show, for example, that the unsteady-state solutions approach the steady-state solutions rapidly on the windward and leeward sides for alpha < and alpha sub c (approximately - 41 degrees). This is also so on the windward side for alpha > alpha sub c. On the leeward side for alpha > and alpha sub c, however, the unsteady boundary layer is initially unseparated but develops a region of reversed flow with increasing time. Subsequently, the streamwise displacement thickness develops a pronounced peak which leads to a singularity of the type observed by van Dommelen and Shen on a circular cylinder started impulsively from rest. Author (GRA)

N85-16070# Scientific Research Associates, Inc., Glastonbury, Conn.

DEVELOPMENT OF A NAVIER-STOKES ROTOR AND STATOR ANALYSIS Annual Report, 21 Jun. 1983 - 30 Jun. 1984

S. J. SHAMROTH, H. MCDONALD, B. C. WEINBERG, and D. V. ROSCOE Jun. 1984 39 p

(Contract F49620-83-C-0119)

(AD-A146967; SRA-R84-910004-1; AFOSR-84-0858TR) Avail: NTIS HC A03/MF A01 CSCL 20D

An important problem in axial flow turbomachinery is that of flow through a turbine or compressor stage in which interaction occurs between the rotor and the stator. Although several experimental efforts have focused upon this problem, relatively little analysis has been applied to this problem. The present effort applies a Navier-Stokes analysis to the rotor/stator problem. The effort consists of several tasks. These include assessment of an existing Navier-Stokes analysis for time-dependent flows, exploration of appropriate boundary conditions, development of an appropriate coordinate system and a demonstration calculation. The present annual report discusses the time-dependent assessment, exploration of boundary conditions and the coordinate system problem. GRA

N85-16073# Tennessee Univ. Space Inst., Tullahoma. Dept. of Aerospace and Mechanical Engineering.

CONTAMINATION AND DISTORTION OF STEADY FLOW FIELD INDUCED BY DISCRETE FREQUENCY IN AIRCRAFT GAS TURBINES Annual Report, 1 Jan. - 31 Dec. 1983

M. KUROSAKA 16 May 1984 20 p (Contract AF-AFOSR-0049-83)

(AD-A147092; AFOSR-84-0909TR) Avail: NTIS HC A02/MF A01 CSCL 20D

This annual technical report covers the first year. Phase 1 activity of a research program initiated in January 1, 1983. The main objective of the present program is to investigate the influence of Reynolds stresses of organized origin induced by discrete frequency disturbances - in deforming and affecting the steady internal flow of aircraft engines. In particular, attention of the present research is focused upon the effect of orderly disturbances such as: (1) the vortex whistle upon the Rangue-Hilsch effects, and (2) Karman vortex street in causing temperature separation within the wake of bodies. GRA

N85-16074# Massachusetts Inst. of Tech., Cambridge. Gas Turbine and Plasma Dynamics Lab.

IN TURBOMACHINERY CURRENT PROBLEMS FLUID DYNAMICS Semiannual Report, 1 Nov. 1983 - 30 Apr. 1984 E. M. GREITZER, J. L. KERREBROCK, W. T. TOMPKINS, JR., J. E. MCCUNE, and A. H. EPSTEIN Jun. 1984 106 p (Contract F49620-82-K-0002)

(AD-A147127; AFOSR-84-0859TR) Avail: NTIS HC A06/MF À01 CSCL 20D

A multi-investigator program on problems of current interest in turbomachinery fluid dynamics is being conducted at the MIT Gas Turbine and Plasma Dynamics Lab. Within the scope of this effort, four different tasks, encompassing both design and off-design problems, have been identified. These are: (1) Investigation of fan and compressor design point fluid dynamics (including formation of design procedures using current three-dimensional transonic codes and development of advanced measurement techniques for use in transonic fans); (2) Studies of basic mechanisms of compressor stability enhancement using compressor casing/hub treatment; (3) Fluid mechanics of inlet vortex flow distortions in gas turbine engines; and (4) Investigations of three-dimensional analytical and numerical computations of flows in highly loaded turbomachinery blading. GRA

N85-16087# McDonnell-Douglas Corp., Long Beach, Calif. SOME IMPORTANT PROBLEMS IN UNSTEADY BOUNDARY LAYERS INCLUDING SEPARATION. 1: NATURE OF SINGULARITY ON OSCILLATING AIRFOILS Annual Report T. CEBECI, A. A. KHATTAB, and S. M. SCHIMKE Apr. 1984

19 p

(Contract F49620-82-C-0055)

(AD-A147897; MDC-J2990; AFOSR-84-1066TR) Avail: NTIS HC A02/MF A01 CSCL 20D

Preliminary results are presented for the analysis of unsteady laminar boundary layers on oscillating airfoils. An examination of the evolution of the boundary layer near the nose of an oscillating airfoil has revealed that, when the reduced frequency is of the same order as in experiments on dynamic stall, the unsteady boundary layer ceases to behave in a smooth manner just downstream of separation and before one cycle is completed. As for the case of the implusively started circular cylinder, the irregular behavior signals the onset of a singularity in the solution of the

boundary layer equations. Numerical results for the method are compared with the numerical results of van Dommelen and Shen for the impulsively started circular cylinder, the irregular behavior signals the onset of a singularity in the solution of the boundary layer equations. Numerical results for the method are compared with the numerical results of van Dommelen and Shen for the impulsively started circular cylinder. GRA

N85-16096*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

HIGH TEMPERATURE THERMOCOUPLE AND HEAT FLUX GAUGE USING A UNIQUE THIN FILM-HARDWARE HOT JUNCTURE

C. H. LIEBERT, R. HOLANDA, S. A. HIPPENSTEELE, and C. A. ANDRACCHIO Dec. 1984 29 p refs Proposed for presentation at 30th Intern. Gas Turbine Conf. and Exhibition, Houston, Tex., 17-21 Mar. 1985; sponsored by ASME

(NASA-TM-86898; E-2365; NAS 1.15:86898) Avail: NTIS HC A03/MF A01 CSCL 14B

A special thin film-hardware material thermocouple (TC) and heat flux gauge concept for a reasonably high temperature and high flux flat plate heat transfer experiment was fabricated and tested to gauge temperatures of 911 K. This concept was developed for minimal disturbance of boundary layer temperature and flow over the plates and minimal disturbance of heat flux through the plates. Comparison of special heat flux gauge Stanton number output at steady-state conditions with benchmark literature data was good and agreement was within a calculated uncertainty of the measurement system. Also, good agreement of special TC and standard TC outputs was obtained and the results are encouraging. Oxidation of thin film thermoelements was a primary failure mode after about 5 of operation. Author

N85-16098*# ITT Aerospace/Optical Div., Fort Wayne, Ind. STEREO ELECTRO-OPTICAL TRACKING SYSTEM (SETS) Final Report

E. W. KOENIG et al. Sep. 1984 47 p

(Contract NAS1-16883)

(NASA-CR-172471; NAS 1.26:172471; REPT-61270-10) Avail: NTIS HC A03/MF A01 CSCL 14B

The SETS is a remote, non-contacting, high-accuracy tracking system for the measurement of deflection of models in the National Transonic Facility at Langley Research Center. The system consists of four electronically scanned image dissector trackers which locate the position of Light Emitting Diodes embedded in the wing or body of aircraft models. Target location data is recorded on magnetic tape for later 3-D processing. Up to 63 targets per model may be tracked at typical rates of 1280 targets per second and to precision of 0.02mm at the target under the cold (-193 C) environment of the NTF tunnel.

N85-16100*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

INTEGRATED EXHAUST GAS ANALYSIS SYSTEM FOR AIRCRAFT TURBINE ENGINE COMPONENT TESTING

R. L. SUMMERS and R. C. ANDERSON Jan. 1985 28 p refs (NASA-TP-2424; E-2302; NAS 1.60:2424) Avail: NTIS HC A03/MF A01 CSCL 14B

An integrated exhaust gas analysis system was designed and installed in the hot-section facility at the Lewis Research Center. The system is designed to operate either manually or automatically and also to be operated from a remote station. The system measures oxygen, water vapor, total hydrocarbons, carbon monoxide, carbon dioxide, and oxides of nitrogen. Two microprocessors control the system and the analyzers, collect data and process them into engineering units, and present the data to the facility computers and the system operator. Within the design of this system there are innovative concepts and procedures that are of general interest and application to other gas analysis tasks.

N85-16156 Department of the Air Force, Washington, D.C. TURBULENCE MEASUREMENT INTERFEROMETER APPARATUS Patent

J. M. GEARY, inventor (to Air Force) 14 Aug. 1984 6 p Supersedes AD-D009885

(AD-D011377; US-PATENT-4,465,372;

US-PATENT-APPL-SN-422429; US-PATENT-CLASS-356-359)

Avail: US Patent and Trademark Office CSCL 20E

Turbulence measurement interferometer apparatus includes a station having an entrance pupil and an aerodynamically stable boom connected to the station. The station houses an optical mirror arrangement defining an optical axis which extends through the entrance pupil. The boom has an end point spaced from the station but disposed on the optical axis. A laser generates a low power beam which is split into first and second portions. The first portion is guided to the boom end point and launched therefrom as a spherical wavefront through turbulence in front of the entrance pupil and toward the mirror arrangement, which in turn transforms it into an object collimated wavefront. The second portion of the beam is transformed into a second collimated reference wavefront which is combined with the first collimated wavefront and produces an interference pattern which is recorded on a medium, such as a photographic plate. The interference pattern provides information on the turbulence structure present at the entrance pupil of the station. GRA

N85-16180*# National Aeronautics and Space Administration, Washington, D. C.

CLEARANCE FLOW-GENERATED TRANSVERSE FORCES AT THE ROTORS OF THERMAL TURBOMACHINES Ph.D. Thesis -Technische Univ., 1975

K. URLICHS Oct. 1983 181 p refs Transl. into ENGLISH of "Durch Spaltstroemungen Hervorgerufene Querkraefte an den Laufern Thermischer Turbomaschinen", Munich p 1-159 Original language document was announced in IAA as A76-43249 Transl. by Scientific Translation Service, Santa Barbara, Calif.

(Contract NASW-3542)

(NASA-TM-77292; NAS 1.15:77292) Avail: NTIS HC A09/MF A01 CSCL 131

Self-excited rotor whirl represents a serious hazard in the operation of turbomachines. The reported investigation has, therefore, the objective to measure the lateral forces acting on the rotor and to determine the characteristic pressure distribution in the rotor clearance area. A description is presented of an approach for calculating the leakage flow in the case of an eccentric rotor position on the basis of empirical loss coefficients. The results are reported of an experimental investigation with a turbine stage, taking into account a variation of the clearance characteristics. The pressure data measured are consistent with the theoretical considerations. G.R. (IAA)

N85-16196# Air Force Human Resources Lab., Brooks AFB, Tex.

NONDESTRUCTIVE INSPECTION: IMPROVED CAPABILITIES OF TECHNICIANS Final Report

R. H. SUMMERS Oct. 1984 21 p

(AD-A147388; AFHRL-TP-83-63) Avail: NTIS HC A02/MF A01 CSCL 05I

This report covers two research and development (R&D) efforts relating to non-destructive inspection (NDI) in the Air Force. Recent surveys have found Air Force NDI capability to lack the precision and reliability necessary to ensure the structural integrity of aircraft. In one of these R&D efforts, specifications were developed for a trainer that would allow NDI technicians to learn and practice the ultrasonic NDI technique on the job. Functional specifications were developed first, based on technician-trainer interaction requirements, and then they were converted to engineering specifications for acquisition purposes. In the other R&D effort reported here, a study was made of relationships between personnel information on NDI technicians and their inspection abilities. The results from extensive eddy current and ultrasonic inspection tests were paired with data on experience, attitudes, and training. No significant relationships were found between NDI

12 ENGINEERING

abilities and selected personnel features. The specifications for the NDI trainer have potentially wide applicability throughout the military and civilian NDI communities. Results of the survey of personnel information, paired with NDI performance scores, holds interest for the personnel selection system. There is apparently little advantage to prior airframe or metals experience, and neither the volunteer nor the non-volunteer performs inspections with an edge in precision or reliability. The underlying conclusion seems to add weight to the premise that additional practice at the job site is the best approach to improving NDI capability. GRA

N85-16219# Fraunhofer-Inst. fuer Betriebsfestigkeit, Darmstadt (West Germany).

THE INFLUENCE OF FASTENER FLEXIBILITY ON LOAD TRANSFER AND FATIGUE LIFE PREDICTIONS FOR MULTIROW BOLTED AND RIVETED JOINTS

H. HUTH 1984 147 p refs In GERMAN; ENGLISH summary

(LBF-FB-172/84; ISSN-0721-5320) Avail: NTIS HC A07/MF A01 Karlsruhe, West Germany DM 90

A universal formula to calculate fastener flexibility was derived from load deformation measurements performed with a variety of commonly used types of single and double shear joints under quasi-static and flight-by-flight loading conditions. The improved accuracy of load transfer calculations is proved by comparative load transfer measurements with multirow joints. Load transfer mechanisms, especially under cyclic loading, are demonstrated, suggesting that fatigue life predictions based on local strains cannot be successful. A method for fatigue life estimation of multirow joints with shear-loaded fasteners is proposed. Author (ESA)

N85-16733# Naval Surface Weapons Center, Dahlgren, Va. JOINT SERVICE DESIGN FOR TESTABILITY PROGRAM

W. L. KEINER In AGARD Design for Tactical Avionics Maintainability 5 p Oct. 1984 refs

Avail: NTIS HC A13/MF A01

As electronics become more complex and more critical to weapon system operation, there is an acknowledge that new designs must be somehow constrained to be more easily tested or they may become completely unsupportable. As a result, design for testability is becoming increasingly important to the services. The Joint Logistics Commanders (JLC) Panel on Automatic Testing established a comprehensive program to coordinate the development of testing technology and its management within the military services. One important part of the program deals with the design aspects of the prime equipment which permit weapon systems to be more easily and confidently tested using automatic test resources. A JLC Testability Subpanel was established under the JPLC Panel to provide acquisition support tools and research and development programs in design for testability (DFT).

Author

N85-16736# Ferranti Ltd., Edinburgh (Scotland). Product Support Dept.

A PRACTICAL EXAMPLE OF REDUCING LIFE CYCLE COSTS AND INCREASED AVAILABILITY

R. P. F. LAUDER In AGARD Design for Tactical Avionics Maintainability 11 p Oct. 1984 refs

Avail: NTIS HC A13/MF A01

The principles underlying effective operational availability are explored and quantified. It is shown that although large sums of money are expended on producing reliable components, these are vitiated if the end equipment is not exposed to a reliability growth program, because only 10% of the calculated mean time between failures (MTBF) will be realised in practice. It is claimed that costs can be reduced by using common commercial components without loss of MTBF provided it is followed by a reliability growth program. A practical example is given of the expensive and time consuming steps which have to be taken in resucing a low MTBF radar, and increasing its availability. The steps and the methodology leading to them are described and the results shown. M.G. N85-16738# Dowty Electronics Ltd., London (England). Controls Div.

EXPERIENCE OF ONE UK ELECTRONIC EQUIPMENT SUPPLIER WITH BITE ON ENGINE/FLIGHT CONTROL SYSTEMS OVER THE PAST TEN YEARS

R. DEGAYE In AGARD Design for Tactical Avionics Maintainability 18 p Oct. 1984 refs

Avail: NTIS HC A13/MF A01

Early analogue electronic controllers for gas turbine control and A/C flight control applications were complex and poorly understood by A/C maintenance personnel - they were relatively easy to remove from their installation compared with the surrounding hydro-mechanical components. Both of these factors led to high unconfirmed defect rates, since these electronic black boxes were usually the first to be blamed for system problems. There was a clear need for some kind of built in fault identification system. The history of Dowty electronics involvement in BITE over the last ten years is traced. The techniques used, successes and failures, and customer reactions are described. A range of civil and military, analogue and digital applications are discussed and four civil applications described in detail. B.W.

N85-16765# Joint Publications Research Service, Arlington, Va. DESIGNER ON AEROFLOT AUTOMATED COMMO SYSTEM DEVELOPMENT

O. GONCHAROVA *In its* USSR Rept.: Transportation (JPRS-UTR-85-001) p 4-5 15 Jan. 1985 Transl. into ENGLISH from Vozdushnyy Transp. (Moscow), 17 Nov. 1984 p 3 Avail: NTIS HC A09/MF A01

Aeroflot digital communication collects and distributes data with a multilevel structure, each level of which is intended for preliminary processing of the data. On the first level, the airborne communications unit performs the initial collection and processing of flight performance information and transmits it to the ground communications center. On the second level, the data comes in from a group of aircraft accommodated by a given digital line. On the third level, the data coming in at the message switching center are processed and distributed among the civil aviation ground services. Capabilities of Aeroflot are compared with those of systems used in the United States and in Western European countries. A.R.H.

N85-16779# Naples Univ. (Italy). TURBULENT BUBBLES BEHIND AIRFOILS AND WINGS AT HIGH ANGLE OF ATTACK

V. LOSITO and G. TORELLA *In* AGARD Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems 13 p Aug. 1984 refs

Avail: NTIS HC A18/MF A01

More accurate inviscid and viscous flow models are needed for simulating the main features of the turbulent bubbles in the near wakes behind airfoils at high angles of attack. Descriptions of these flows are not sufficiently detailed to allow accurate modelling for the recirculating flow regions. Numerical and wind tunnel experiments are required to ensure convergence criteria and wake closure conditions at different Reynolds numbers. A simple relation was found which correlates the airfoils viscous lift loss with the location of the upper surface separation point and lift predicted in full attached flow conditions. This simple two-dimensional model was extended to three-dimensional wing flows with embedded turbulent bubbles after a set of wind tunnel experiments and oil-flow visualizations. A fast and efficient method is given for predicting spanwise load distribution and C sub L max for finite unswept wings. R.S.F.

N85-16807# Elmer, Rome (Italy). TACTICAL HF COMMUNICATION FOR MILITARY HELICOPTERS USING THE NVIS MODE

G. PUCCETTI and P. L. COMO *In* AGARD Helicopter Guidance and Control Systems for Battlefield Support 9 p Aug. 1984 refs

Avail: NTIS HC A13/MF A01

The use of loop antennas for tactical HF communications on board of military helicopters was investigated. The helo platform is considered for land or maritime scenarios. The experiments on the SH-3D helicopter compared the loop antennas and existing wire antennas. Groundwave radiated field at different azimuth angles were measured for the two antenna types, particularly at the lower end of the frequency range where the difference in the antenna geometry is more significant. A consistent better performance of the loop over the wire, typically a 16 dB to 8 dB improvement is indicated. Skywave propagation tests at different distances and altitude of the helicopter were conducted. It is found that the performance of the loop antenna is superior to the wire. It is concluded that the loop antenna is an ideal radiator for use onboard aircraft and helicopters because of its dimensions, increased efficiency, and radiation characteristics. E.A.K.

N85-16810# AEG-Telefunken, Ulm (West Germany).

LPI-RADAR FOR HELICOPTER OBSTACLE WARNING H. MEINEL, H. G. WIPPICH, B. REMBOLD, and W. F. X. FRANK In AGARD Helicopter Guidance and Control Systems for Battlefield Support 7 p Aug. 1984 refs

Avail: NTIS HC A13/MF A01

Employing the frequency range of maximum atmospheric attenuation around 60 GHz, a short range obstacle warning radar for helicopters was developed which can be operated under low probability of intercept conditions. Test flights with this noncoherent solid state radar showed that power cables as well as tall trees can be detected, even under adverse weather conditions. System considerations and test results are described. R.J.F.

N85-17159 Rolls-Royce Ltd., London (England).

FLEXIBLE MANUFACTURING SYSTEM FOR THE PRODUCTION OF AIRCRAFT PARTS

M. WECK et al. 13 Nov. 1984 16 p refs Transl. into ENGLISH from Ind. Anzeiger (West Germany), v. 10, no. 32, 20 Apr. 1979 p 42-46

(BLL-PNR-90237-(899.3153)) Avail: British Library Lending Div., Boston Spa, Engl.

The flexible manufacturing system for the machining of integral aircraft components not only comprises control functions for numerical control machines and material flow in the data management and distribution system but also includes a complex processing system for organization data. Especially important is the automatic data feedback from the production line, the prompt availability of data to the associated sectors of the firm contributing towards shorter planning and decision times. The deliberate creation of sub-systems which operate independently, and the material flow control and monitoring system for interlinked machines, also provides the condition which allows them to be used on their own in similar fields of application or as stages in a gradual expansion of a manufacturing system. B.G.

N85-17162# Air Force Inst. of Tech., Wright-Patterson AFB, Ohio. School of Systems and Logistics.

THE EFFECTS OF MANUFACTURING AUTOMATION ON THE SURGE AND MOBILIZATION CAPABILITIES OF THE GAS TURBINE ENGINE INDUSTRY M.S. Thesis

F. E. DRESSEL and V. F. GAUL Sep. 1984 101 p

(AD-A147295; AD-E500683; AFIT/GSM/LSY/84S-9) Avail: NTIS HC A06/MF A01 CSCL 05A

This thesis determines the effects of manufacturing automation on the surge and mobilization capabilities of the gas turbine engine industry. Five specific manufacturing characteristics are investigated: labor, flexibility, manufacturing inputs, equipment utilization, and lead time. The combined information showed mostly positive effects on surge and mobilization. Some areas showed no effect due to automation and the only negative effect was in one aspect of mobilization. Both companies reported an increased reliance on foreign suppliers for equipment and machinery, which would hamper their ability to expand their facilities during mobilization. Positive effects are anticipated for both surge and mobilization through increased flexibility, reduced labor requirements, and reduced manufacturing inputs requirements. Finally, the positive effects on these characteristics combined, are expected to significantly reduce the lead time required to deliver engine components and thereby for the engines themselves.

GRA

N85-17193# Joint Publications Research Service, Arlington, Va. FRG CERAMIC ENGINE COMPONENTS (PET) Abstract Only In its West Europe Rept.: Sci. and Technol. (JPRS-WST-85-001)

In its west Europe Rept.: Sci. and Technol. (JPRS-WST-85-001) p 6 2 Jan. 1985 Transl. into ENGLISH from Frankfurter Zeitung/Blick Durch die Wirtsch. (Frankfurt/Main), 1 Nov. 1984 p 7

Avail: NTIS HC A05/MF A01

Ceramic engine components for spark ignition and diesel engines for the development of ceramic rotors and ceramic-lined turbocharger housing are discussed. Ceramic port liners for thermal insulation of the exhaust gas channel in the cylinder head are cast into the cylinder head using improved manufacturing methods. Less heat would be given off by the cooling system, the exhaust temperatures would rise, hydrocarbon emissions would drop by 10% and catalytic treatment of the exhaust gases would be more favorable. The lining of the exhaust manifolds was investigated. It is difficult to manufacture the necessary shape while simultaneously adhering to close manufacturing tolerances. The ceramic lining of the combustion chamber still needs more development. Designs which lend themselves to ceramic linings, and the selection of suitable ceramic materials are emphasized. The objective of the development of ceramic engines is the reduction of fuel consumption by nerly 8% which is made possible by higher operating temperatures. Engine heat losses, however, must be minimized, and it is found that ceramics are suitable for this task. FAK

N85-17294*# Sunstrand Energy Systems, Rockford, III. DESIGN AND TEST OF A FOUR CHANNEL MOTOR FOR ELECTROMECHANICAL FLIGHT CONTROL ACTUATION Final Report

Dec. 1984 245 p

(Contract NAS9-16535)

(NASA-CR-171838; NÁS 1.26:171838; S8308-R1) Avail: NTIS HC A11/MF A01 CSCL 09A

To provide a suitable electromagnetic torque summing approach to flight control system redundancy, a four channel motor capable of sustaining full performance after any two credible failures was designed, fabricated, and tested. The design consists of a single samarium cobalt permanent magnet rotor with four separate three phase windings arrayed in individual stator quadrants around the periphery. Trade studies established the sensitivities of weight and performance to such parameters as design speed, winding pattern, number of poles, magnet configuration, and strength. The motor electromagnetically sums the torque of the individual channels on a single rotor and eliminate complex mechanical gearing arrangements. A.R.H.

N85-17298# Air Force Inst. of Tech., Wright-Patterson AFB, Ohio. School of Systems and Logistics.

LIFE CYCLE COST MODEL FOR VERY HIGH SPEED INTEGRATED CIRCUITS M.S. Thesis

E. A. LONG Sep. 1984 242 p

(AD-A147798; AFIT/GLM/LSM/84S-39) Avail: NTIS HC A11/MF A01 CSCL 14A

The Very High Speed Integrated Circuit (VHSIC) technology program is forecast to have a profound impact on performance, reliability, and cost of future avionics systems. An important question is: how do VHSIC design fabrication and support concepts impact life cycle cost (LCC) of a host system? To answer this question, an insertion model representative of future avionics systems is selected and LCCs are obtained for various chip designs and layout configurations which implement this model. This thesis then examines five factors affecting VHSIC chips with respect to LCC of a digital synthetic aperture radar processor. These factors are: (1) chip technology and design; (2) fabrication yields; (3) substrate type; (4) the degree to which computer-aided-design (CAD) methods are used; and (5) maintenance level. Of these factors, the greatest impact to LCC is chip fabrication yields. The least effect on LCC is the degree to which CAD methods are used. The remaining factors fall between these two. Originator-supplied keywords include: semiconductors, microcircuits and Chips(Electronics). GRA

N85-17351 Illinois Univ., Urbana-Champaign. THEORETICAL AND EXPERIMENTAL ANALYSES OF LASER ALTIMETERS FOR BAROMETRIC MEASUREMENTS OVER THE **OCEAN Ph.D. Thesis**

B. M. B. TSI 1984 214 p

Avail: Univ. Microfilms Order No. DA8422167

The optical path length from a satellite to the Earth's surface is strongly dependent on the atmospheric pressure along the propagation path. Surface pressure can be determined by measuring the difference between the round-trip propagation times of laser pulses that are transmitted simultaneously at two wavelengths. Although pressure measurements can be made over the ground and water, the application of this technique to pressure measurements over the ocean is considered. The statistical characteristics and the waveforms of the ocean reflected laser pulses are studied. The statistics of time-resolved speckle and its effects on the timing accuracy of the receiver are studied in the general context of laser altimetry. The data obtained from the first airborne two-color laser altimeter experiment are processed and analyzed. The results are used to verify the pressure measurement concept. Dissert. Abstr.

N85-17353*# Old Dominion Univ., Norfolk, Va. Dept. of Physics.

NASA THREE-LASER AIRBORNE DIFFERENTIAL ABSORPTION LIDAR SYSTEM ELECTRONICS Final Report, 15 Dec. 1979 -31 Dec. 1984

R. J. ALLEN and G. D. COPELAND Dec. 1984 85 p refs (Contract NCC1-32)

(NASA-CR-174293; NAS 1.26:174293; PTR-84-3) Avail: NTIS HC A05/MF A01 CSCL 20E

The system control and signal conditioning electronics of the NASA three laser airborne differential absorption lidar (DIAL) system are described. The multipurpose DIAL system was developed for the remote measurement of gas and aerosol profiles in the troposphere and lower stratosphere. A brief description and photographs of the majority of electronics units developed under this contract are presented. The precision control system; which includes a master control unit, three combined NASA laser control interface/guantel control units, and three noise pulse discriminator/pockels cell pulser units; is described in detail. The need and design considerations for precision timing and control are discussed. Calibration procedures are included. BSE

N85-17363*# National Aeronautics and Space Administration, Washington, D. C.

TURBO FLUID MACHINERY AND DIFFUSERS

T. SAKURAI Sep. 1984 220 p Transl. into ENGLISH of the book "Kikkan Kogyo Shinbunsha" Japan, 30 Sep. 1983 187 p Transl. by Scientific Translation Service, Santa Barbara, Calif. (Contract NASW-4004)

(NASA-TM-77467; NAS 1.15:77467) Avail: NTIS HC A10/MF A01 CSCL 131

The general theory behind turbo devices and diffusers is explained. Problems and the state of research on basic equations of flow and experimental and measuring methods are discussed. Conventional centrifugation-type compressor and fan diffusers are considered in detail. R.S.F.

N85-17369# Department of the Air Force, Washington, D.C. FLOW MEASUREMENT DEVICE Patent Application

T. C. CHANDLER, inventor (to Air Force) 17 Oct. 1984 18 p (AD-D011432; US-PATENT-APPL-SN-661834) Avail: NTIS HC A02/MF A01 CSCL 13G

A device is described for measuring fuel flow to a power plant such as a turbo fan engine with a very high degree of accuracy, for example, + or - 0.5%. A tubular flow loop having quick disconnect fittings for detachably connecting the loop between the aircraft fuel system outlet and the engine fuel inlet is disclosed. Two specially calibrated mass flow transmitters are arranged in series, each preceded by a straight section of piping having a preferred given length to diameter ratio. Preceding each of the two straight pipe sections is a honeycomb flow straightener and three in-series perforated plates for removing any effects of upstream flow characteristics from the transmitters. GRA

N85-17398# National Aerospace Lab., Amsterdam (Netherlands). Structures and Materials Div.

ENGINEERING PROPERTY COMPARISONS OF PM AND IM **ALUMINUM ALLOY FORGINGS**

R. J. H. WANHILL and L. SCHRA 23 Nov. 1983 23 p refs Presented at ASTM Symp. on Rapidy Solidified Powder Aluminum Alloys, Philadelphia, Apr. 1984

(AD-B0881466L; NLR-MP-83066-U) Avail: NTIS HC A02/MF A01

Strength, fracture toughness, fatigue strength, fatigue crack propagation resistance under constant amplitude and spectrum loading, stress corrosion crack initiation and propagation resistance, and exfoliation corrosion of the PM alloy 7091-T7E69 and the IM alloys 7075-T73, 7175-T736, 7010-T736 and 7050-T736 were compared. The PM alloy has a substantially better combination of strength and resistance to stress corrosion and exfoliation and higher notched fatigue strength at low mean stress levels and long lives. However, the fracture toughness is lower than (L-T orientation) or similar to (T-L orientation) that of the IM alloys, and the resistance to fatigue crack propagation under spectrum loading is greatly inferior. There are only minor differences in properties between the IM allovs. Author (ESA)

13

GEOSCIENCES

Includes geosciences (general); earth resources; energy production and conversion; environment pollution; geophysics; meteorology and climatology; and oceanography.

A85-19458*# Dayton Univ., Ohio.

CLEAR TURBULENCE FORECASTING - TOWARDS A UNION OF ART AND SCIENCE

J. L. KELLER (Dayton, University, Dayton, OH) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. NASA-NOAA-supported research. refs

(AIAA PAPER 85-0014)

The development of clear air turbulence (CAT) forecasting over the last several decades is reviewed in the context of empirical and theoretical research into the nature of nonconvective turbulence in the free atmosphere, particularly at jet stream levels. Various qualitative CAT forecasting techniques are examined, and prospects for an effective quantitative index to aid aviation meteorologists in jet stream level turbulence monitoring and forecasting are examined. Finally, the use of on-board sensors for short-term warning is discussed. V.L.

A85-19514#

RADAR FOR STORM FORECASTING AND WEATHER HAZARD WARNING

R. J. DOVIAK and J. T. LEE (NOAA, National Severe Storms Laboratory, Norman, OK) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. Sponsorship: U.S. Department of Transportation. refs

(Contract DOT-FA01-80-Y-10524)

(AIAA PAPER 85-0092)

The capabilities, probable applications and shortcomings of Doppler radar are discussed. A nationwide network of Doppler radars (NEXRAD) is planned for the late 1980s to replace the current incoherent WSR-57 weather radars. The NEXRAD system will detect mesoscale events from which aircraft hazards such as tornadoes can originate. The system will also identify hail, excessive water, wind shear and turbulence in proportion to their fields of reflectivity factor, which is estimated from echo power levels, range and radar calibration constants. The enhanced accuracy of the Doppler equipment will lend credibility to aircraft severe weather warnings and encourage pilots to stay the recommended 20 km from thunderstorms. Lead times up to 23 min have been achieved for hail forecasts, especially with dual polarization radars. It is noted that sidelobe levels are a critical factor for Doppler radar angular resolution, and range and velocity errors are inversely proportional to each other. Better resolution can be obtained with phased arrays, SAR or larger antennas. MSK

A85-21141 ICING CONDITIONS ENCOUNTERED BY A RESEARCH AIRCRAFT

W. R. SAND, W. A. COOPER, M. K. POLITOVICH, and D. L. VEAL (Wyoming, University, Laramie, WY) Journal of Climate and Applied Meteorology (ISSN 0733-3021), vol. 23, Oct. 1984, p. 1427-1440. NSF-NOAA-supported research; U.S. Bureau of Reclamation and U.S. Department of Transportation. refs (Contract USBR-7-07-83-V0001; DOT-FA03-81-C-00020)

The characteristics of clouds which have led to airframe icing on an instrumented Beechcraft Super King Air are summarized. The icing encounters occurred at altitudes from 0-8000 m MSL, in summer and winter, in stratiform and cumuliform clouds, and at temperatures from 0 to -30 C. The characteristics of icing encounters in different areas and in different seasons are compared. The fraction of measurements exceeding various threshold values of liquid water content, average liquid water content over a given distance, volume-median droplet diameter. droplet concentration, ice crystal concentration, and potential ice accumulation are given. The effects of these cloud characteristics on aircraft performance were measured by comparing the rate of climb of the aircraft with ice to the rate of climb for the clean aircraft under the same conditions. Most icing encounters led to a reduction in the rate of climb that increased linearly with the path integral of the supercooled liquid water content. The volume-median diameter had little correlation with changes in performance. Some potentially hazardous conditions, which decreased the rate of climb capability of this aircraft by 7-9 m/s, are also discussed. Author

A85-21843*# Arizona Univ., Tucson. IDENTIFICATION OF VORTEX-INDUCED CLEAR AIR TURBULENCE USING AIRLINE FLIGHT RECORDS

E. K. PARKS (Arizona, University, Tucson, AZ), R. C. WINGROVE, R. E. BACH, and R. S. MEHTA (NASA, Ames Research Center, Journal of Aircraft (ISSN 0021-8669), vol. 22, Moffett Field, CA) Feb. 1985, p. 124-129. Previously cited in issue 06, p. 798, Accession no. A84-17989. refs

N85-17435# Argonne National Lab., Ill. Air Resources Section. IMPACT OF AIRCRAFT EMISSIONS ON AIR QUALITY IN THE VICINITY OF AIRPORTS. VOLUME 3: AIR QUALITY AND **EMISSION MODELING NEEDS Final Report**

D. M. ROTE Jan. 1984 122 p Sponsored in part by AF 4 Vol.

(Contract DTFA01-83-4-10556)

(AD-A147951; FAA/EE-84-13; AFESC/ESL-TR-84-35) Avail:

NTIS HC A06/MF A01 CSCL 09B

The first part of this report addresses the status of the AVAP (Airport Vicinity Air Pollution) model and AQAM (Air Quality Assessment Model) from the perspective of the modeling requirements of users concerned with air-quality problems in civilian and military aviation. Brief descriptions of the types of problems likely to be encountered is followed by a detailed discussion of those characteristics of the problems that determine the technical requirements for the applicable computation procedures or models. This is followed by a discussion of the operational or user requirements of the models. Then a review and evaluation of the AVAP model and AQAM is given that includes a discussion of their intended uses, strengths, and weaknesses. The methods used by the two models to treat various aspects of the emission and dispersion are compared, and the best methods are selected, or alternatives are recommended where appropriate. The latter portion of the report addresses the future needs. Because of the number of interrelated problems and decisions required to meet these needs, a systematic approach to the problem in the form of a decision tree is presented. The final section contains an outline of a proposed new computational system that should alleviate at least some of the problems identified in earlier sections. Two objections were paramount in the new design: to make the model easier to use and to be able to implement the model on modern, small computers. GRA

IMPACT OF AIRCRAFT EMISSIONS ON AIR QUALITY IN THE VICINITY OF AIRPORTS. VOLUME 4. NITROGEN DIOXIDE AND HYDROCARBONS Final Report, Jul. 1980 - Apr. 1984 K. L. BRUBAKER, M. DAVE, R. J. WINGENDER, and R. D.

FLOTARD Apr. 1984 158 p

(Contract DTFA01-83-Y-10556)

(AD-A148253: FAA/EE-84-14; AFESC/ESL-TR-84-36) Avail: NTIS HC A08/MF A01 CSCL 13B

This report documents the results of three related studies conducted to assess the impact of aircraft emissions of nitrogen oxides (NOx) and hydrocarbons (Hc) on air quality. The first study consisted of a field program carried out at O'Hare International Airport and an associated model development program, the purposes of which were to assess the effect of aircraft NOx emissions on ambient 1-hour concentrations of nitrogen dioxide (NO2) and to provide a dispersion model suitable for the prediction of such concentrations. The second study involved the collection and laboratory analysis of samples of hydrocarbons in ambient air contaminated by jet aircraft exhaust, together with a determination of the type and relative amounts of the various hydrocarbons detected. The third study consisted of an analysis, based on available data in the literature, of the potential role of aircraft hydrocarbon emissions in the production of photochemical smog. The available literature dealing with the issue of aircraft contributions to photochemical smog has been reviewed and is discussed. At present, the available information is insufficient to evaluate the effect quantitatively. The requirements for further work that would enable a quantitative evaluation to be made are discussed. GRA

N85-17436# Argonne National Lab., III. Energy and Environmental Systems Div.

N85-17470# California Univ., Riverside: Statewide Air Pollution Research Center.

ATMOSPHERIC PHOTOCHEMICAL MODELING OF TURBINE ENGINE FUELS. PHASE 1: EXPERIMENTAL STUDIES. VOLUME 2: ENVIRONMENTAL CHAMBER DATA TABULATIONS Final Report, Jun. 1983 - Jun. 1984

W. P. L. CARTER, A. M. WINER, R. ATKINSON, M. C. DODD, and W. D. LONG Sep. 1984 576 p

(Contract F08635-80-C-0359)

(AD-A147786; AFESC/ESL-TR-84-32-VOL-2) Avail: NTIS HC A25/MF A01 CSCL 04A

This report documents the results of the first phase of a two-phase program aimed at developing for the U.S. Air. Force experimentally tested computer models to predict worst-case potentials for air quality degradation resulting from use of current and potential future turbine engine (jet) fuels. The development and testing of such models requires an adequate data base derived from appropriate environmental chamber experiments and laboratory studies. In Phase I of this two-phase program, a total of 131 environmental chamber experiments were carried out in a approx. 640000-liter, all Teflon indoor environmental chamber and several kinetic measurements were made in order to obtain data required for model development. The chamber experiments included 47 single component-NOx-air irradiations of various representative fuel constituents and potential future fuel impurities, 15 fuel-NOx-air irradiations of various representative fuel constituents and potential future fuel impurities, 15 fuel--NOx-air irradiations employing one whole and six synthetic surrogate fuels, and 69 control or characterizatin runs. Volume II contains a tabulation of the environmental chamber data gathered during the course of the experimental phase of this program. GRA

N85-17492# Naval Postgraduate School, Monterey, Calif. THE VISIBILITY CLIMATOLOGY OF MCMURDO SOUND-WILLIAMS FIELD, ANTARCTICA M.S. Thesis C. G. SOUDERS Mar. 1984 151 p

(AD-A148108) Avail: NTIS HC A08/MF A01 CSCL 04B

Accurate forecasting of visibility at McMurdo/Williams Field, Antarctica is essential for the air operations involving the resupply of United States bases and the conduct of research on the Antarctic continent. McMurdo, located at 77 deg 51' S 155 deg 40' E, receives all supplies destined for use by the United States Antarctic Research Program scientists. The Williams Field skiway and the adjacent ice runway are approximately 4.5 mi southeast of McMurdo. Weather observations are taken at both McMurdo and the operational airfield. The visibility climatology, August through March, for McMurdo (1956-1983) and Williams Field skiway/runway (1968-1983) was prepared using four operational visibility categories, as well as the seven important weather parameters which reduce visibility, namely, blowing snow, light snow, moderate to heavy snow, the three types of fog and ice crystals. A wind speed/direction climatology was also prepared because of its relation to both blowing snow and fog. GRA

N85-17494# New Mexico Inst. of Mining and Technology, Socorro.

A STUDY OF THE EFFECTS OF TRIGGERED LIGHTNING Final Report, 15 May 1982 - 31 Dec. 1983

C. B. MOORE and C. R. HOLMES Oct. 1984 40 p

(Contract AF-AFOSR-0206-82)

(AD-A148296; AFOSR-84-1024TR) Avail: NTIS HC A03/MF A01 CSCL 04A

The characteristics of lightning, artificially induced by wire-trailing rockets were measured in a cooperative program involving investigators from France, from the Flight Hazards Branch of Wright-Patterson Air Force Base and from New Mexico Institute of Mining & Technology. Lightning currents ranging from a few hundred amperes to a peak of 79 kA were measured. The waveforms of the electromagnetic signals produced by the lightning had associated magnetic field variations in excess of 10 T/s with rise times ranging from 40 ns to 1 microsecond. The development of an 11 cm radar was completed for a determination of the interaction between lightning and the surrounding atmosphere.

300

Preliminary data on lightning echoes have now been obtained with it. GRA

N85-17506# Department of the Navy, Washington, D. C. A METHOD FOR DETERMINING MESOSCALE DYNAMIC TOPOGRAPHY Patent Application

J. L. MITCHELL, inventor (to Navy) 22 Feb. 1984 13 p (AD-D011412; US-PATENT-APPL-SN-582412) Avail: NTIS HC A02/MF A01 CSCL 08J

A method for determining mesoscale dynamic topography places a satellite altimeter into a properly selected, exact repeating orbit. The proper mesoscale sampling strategy depends upon the nature of the frequency/wavenumber response of the mesoscale ocean which is different in different regions of the global ocean. The result is altimetry data completely free of geoid contamination and having an order of magnitude alleviation of the problem of temporal undersampling. Author (GRA)

15

MATHEMATICAL AND COMPUTER SCIENCES

Includes mathematical and computer sciences (general); computer operations and hardware; computer programming and software; computer systems; cybernetics; numerical analysis; statistics and probability; systems analysis; and theoretical mathematics.

A85-19586#

A GENERÂLIZED STABILITY CRITERION FOR NONLINEAR DYNAMIC SYSTEMS

M. N. WAGDI (Suez (Anal University, Port Said, Egypt) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 6 p. refs (AIAA PAPER 85-0202)

A novel method is introduced that results in a generalized nonlinear stability criterion. The present approach is completely different from those of Malkin's (1959) and Lyapunov's (1950). The basic concept of the present methodology is to discretize the given nonlinear continuous system via the fourth order Runge-Kutta scheme. Sensitivity analysis is performed and state disturbance propagation is obtained through defined matrices. A stability matrix is then derived which is the sum of a first order matrix and a second order matrix. The stability criterion reduces to that of determining the eigenvalues of the stability matrix. A general nonlinear autonomous system will be stable if all the eigenvalues of the stability matrix are confined within a unit central circle in the complex plane. The stability characteristics of a model aircraft performing a nonlinear rapid roll maneuver is investigated by the present method. Author

A85-19782*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

NONITERATIVE THREE-DIMENSIONAL GRID GENERATION USING PARABOLIC PARTIAL DIFFERENTIAL EQUATIONS

T. A. EDWARDS (NASA, Ames Research Center, Moffett Field, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 9 p. refs

(AIAA PAPER 85-0485)

A new algorithm for generating three-dimensional grids has been developed and implemented which numerically solves a parabolic partial differential equation (PDE). The solution procedure marches outward in two coordinate directions, and requires inversion of a scalar tridiagonal system in the third. Source terms have been introduced to control the spacing and angle of grid lines near the grid boundaries, and to control the outer boundary point distribution. The method has been found to generate grids about 100 times faster than comparable grids generated via solution of elliptic PDEs, and produces smooth grids for finite-difference flow calculations. Author

15 MATHEMATICAL AND COMPUTER SCIENCES

A85-19835

THREE-DIMENSIONAL KALMAN FILTER FOR SHORT Α OBSERVATION TIMES то EXTRAPOLATE FLIGHT TRAJECTORIES (EIN DREIDIMENSIONALES KALMANFILTER FUER KURZE BEOBACHTUNGSZEITEN ZUR EXTRAPOLATION VON FLUGBAHNEN]

D. URMANN Hamburg, Hochschule der Bundeswehr, Fachbereich Maschinenbau, Dr.-Ing. Dissertation, 1984, 130 p. In German. refs

The application of Kalman filters of the type described by Singer (1970) to the computer-guided radar tracking of aircraft is investigated analytically. A system model of the generalized Kalman filter is introduced; the equations for the three-dimensional filter are derived; problems are identified; and technical or mathematical approaches to their solution are developed. It is found that correcting for the coupling of the Cartesian coordinates gives only minimal improvements in accuracy at significant computation costs, whereas the use of velocity measurements (from appropriate sensors) improves performance and solves the initialization problem at all but very low target velocities. Best overall results are achieved using an initialization procedure based on linear least-squares fitting. T.K.

A85-20856#

DESIGN OF AERODYNAMIC BODIES USING ARTIFICIAL INTELLIGENCE/EXPERT SYSTEM TECHNIQUE

S. S. TONG (General Electric Co., Schenectady, NY) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 7 p. refs (AIAA PAPER 85-0112)

This paper introduces the concept of coupling artificial intelligence/expert system and computational fluid dynamics techniques for the design of aerodynamic bodies. A general design system architecture is presented with illustrations of the programming methodology. Applications, limitations, and software requirements are discussed. A simple axial cooling fan design is used to demonstrate that such a design system can solve problems as well as human experts, reduce labor costs by eliminating user intervention during design iterations, and has the potential of out-performing the experts by systematically examining many more cases than a human being is capable of examining. Author

A85-21457

SOFTWARE DESIGN METHODS

W. J. CULLYER (Royal Signals and Radar Establishment, Malvern, Worcs., England) IN: Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 . London, Royal Aeronautical Society, 1984, 10 p. refs

Contemporary civil and military aircraft avionics systems comprise a large number of different, interconnected computers for air data gathering, inertial navigation, automatic flight direction, flight management and stores management; the assembly of such systems involves both mutual understanding as to design methods, and agreement on avionics interface standards, among companies located throughout Western Europe and North America. Attention is presently given to the CORE and MENTOR methods for automated assessment and integration of complex avionics requirements, as well as to the difficulties anticipated in conversion to the Ada high level programming language for military avionics. O.C.

A85-21458#

A DESIGN METHODOLOGY FOR INTEGRATED AVIONIC SYSTEMS

A. O. WARD (British Aerospace, PLC, Warton Div., Preston, Lancs., England) IN: Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 . London, Royal Aeronautical Society, Research supported by the Royal Aircraft 1984, 9 p. Establishment.

The increasing use of computers and the growing sophistication of sensors and displays has led to a rapid expansion in the gathering, processing, and dissemination of information within airborne systems. The philosophy for the design of such systems has, moreover, been transformed from one of considering individual units to a comprehensive concern with information transfer and control architectures. Attention is presently given to the Controlled Requirements Expression (CORE) methodology, which consists of 11 logical steps for the generation of requirement decomposition according to system viewpoints, and their subsequent reconciliation. CORE has to date been applied to several small avionics-related projects in Britain. O.C.

A85-21548* College of William and Mary, Williamsburg, Va. OPTIMAL MAINTENANCE CENTER INVENTORIES FOR FAULT-TOLERANT REPAIRABLE SYSTEMS

S. H. LAWRENCE and M. K. SCHAEFER (Collage of William and Mary, Williamsburg, VA) Journal of Operations Management (ISSN 0272-6963), vol. 4, Feb. 1984, p. 175-181. Research supported by the College of William and Mary. refs (Contract NSG-1625)

A probabilistic approach is taken to determine the optimal repairable parts inventory for a maintenance center, servicing machines which contain several m-out-of-n systems of different parts, with a constraint on the total inventory investment. A model, based on the discrete Markov process, accounts for a typical ultrareliable avionics system, such as one presently being developed by NASA. The dynamic programming algorithm for minimizing the stockout and holding costs is applied to an exemplary maintenance center, and solutions for single-item and multi-item cases are given. The computational burden is noted to be reasonable and a computer program is used to generate optimal solutions. L.T.

A85-21791*# National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

COMPUTER FACILITY LARGE-SCALE FOR COMPUTATIONAL AERODYNAMICS

F. R. BAILEY and W. F. BALLHAUS, JR. (NASA, Ames Research Center, Moffett Field, CA) (Oak Ridge National Laboratory, NASA, NBS, et al., Nuclear Science Symposium, 31st, Orlando, FL, Oct. 31-Nov. 2, 1984) IEEE Transactions on Nuclear Science (ISSN 0018-9499), vol. NS-32, Feb. 1985, p. 202-208.

As a result of advances related to the combination of computer system technology and numerical modeling, computational aerodynamics has emerged as an essential element in aerospace vehicle design methodology. NASA has, therefore, initiated the Numerical Aerodynamic Simulation (NAS) Program with the objective to provide a basis for further advances in the modeling of aerodynamic flowfields. The Program is concerned with the development of a leading-edge, large-scale computer facility. This facility is to be made available to Government agencies, industry, and universities as a necessary element in ensuring continuing leadership in computational aerodynamics and related disciplines. Attention is given to the requirements for computational aerodynamics, the principal specific goals of the NAS Program, the high-speed processor subsystem, the workstation subsystem, the support processing subsystem, the graphics subsystem, the mass storage subsystem, the long-haul communication subsystem, the high-speed data-network subsystem, and software. G.R.

A85-21973* Stanford Univ., Calif. WRITING EXECUTABLE ASSERTIONS TO TEST FLIGHT SOFTWARE

A. MAHMOOD, D. M. ANDREWS, and E. J. MCCLUSKEY (Stanford University, Stanford, CA) Annual Asilomar Conference on Circuits, Systems, and Computers, 18th, Pacific Grove, CA, Nov. 5-7, 1984, Paper. 6 p. refs

(Contract NAG2-246)

.

(SU-CRC-TR-84-14; CSL-TN-84-256)

An executable assertion is a logical statement about the variables or a block of code. If there is no error during execution, the assertion statement results in a true value. Executable assertions can be used for dynamic testing of software. Thy can be employed for validation during the design phase, and exception and error detection during the operation phase. The present investigation-is-concerned-with-the-problem of writing executableassertions, taking into account the use of assertions for testing flight software. They can be employed for validation during the design phase, and for exception handling and error detection during the operation phase The digital flight control system and the flight control software are discussed. The considered system provides autopilot and flight director modes of operation for automatic and manual control of the aircraft during all phases of flight. Attention is given to techniques for writing and using assertions to test flight software, an experimental setup to test flight software, and language features to support efficient use of assertions. G.R.

A85-22274

ONERA - THE AERONAUTICS SUPERCOMPUTER IS PUT INTO SERVICE [ONERA - L'AERONAUTIQUE MET EN SERVICE SON SUPERCALCULATEUR]

R. NAZARETIAN Air et Cosmos (ISSN 0044-6971), vol. 22, Jan. 12, 1985, p. 27-29. In French.

The CRAY-1 S-2000 computer system recently installed by ONERA to meet the needs (increased by a factor of 60 over the last 10 years) of its own researchers and of its industrial contractors is characterized and illustrated with block diagrams and photographs. The factors evaluated in choosing the CRAY system over one based on the Cyber 205 are reviewed; the need for an aeronautics computer system to supplement ONERA's share in a CRAY system used by a number of French institutes is explained; and possible approaches to further expand ONERA computer capacity (since the present system has been used at nearly 100 percent of capacity since its activation) are considered. T.K.

A85-22374

THE USE OF LOCAL FUNCTIONALS TO CONSTRUCT A CIRCUMVENTION MANEUVER IN GAME PROBLEMS OF EVASION [PRIMENENIE LOKAL'NYKH FUNKTSIONALOV DLIA POSTROENIIA MANEVRA OBKHODA V IGROVYKH ZADACHAKH UKLONENIIA OT PEREKHVATA]

N. A. ZABOLONOVA IN: Ill-posed problems in perturbation theory (A85-22364 08-02). Novosibirsk, Izdatel'stvo Nauka, 1984, p. 238-243. In Russian. refs

A85-22449#

THE DEVELOPMENT OF DIGITAL ATTITUDE CONTROLLERS -ITS PAST, PRESENT AND FUTURE

Y. SHAN Chinese Society of Astronautics, Journal, no. 4, 1984, p. 90-97. In Chinese, with abstract in English. refs

The development of digital attitude controllers is analyzed, and the necessity for the transition from the linear to the nonlinear domains is shown. Using nonlinear methods, it is possible not only to shape the amplitude and phase characteristics of the controllers, but also successfully to achieve a new index of controllable performance. The key problems which remain to be solved in the future development of nonlinear controllers are indicated. C.D.

N85-16503# Bolt, Beranek, and Newman, Inc., Canoga Park, Calif.

NOISEMAP 4.4 COMPUTER PROGRAM UPDATE, OPERATOR'S MANUAL, ADDENDUM 1 Final Report

R. D. HORONJEFF Wright-Patterson AFB, Ohio AMRL Sep. 1984 16 p

(Contract F33615-82-C-0501)

(AD-A147091; BBN-5657; AFAMRL-TR-78-109-ADD-1) Avail: NTIS HC A02/MF A01 CSCL 09B

This report, an addendum to a previous document, describes new capabilities for the NOISEMAP program that allow calculation of the daily noise exposure at 20 user-specified locations. The program also produces a detailed listing of the aircraft flight and ground operations which are the greatest contributors to the daily noise exposure at each specified location. NOISEMAP is a general purpose digital computer program which creates noise exposure maps for land areas surrounding civil and military air installations. The programs have been written in FORTRAN IV and optimized for execution on Control Data Corporation (CDC) 6000, 7000, and Cyber 170 series computers. GRA

N85-16746# Pacific Missile Test Center, Point Mugu, Calif. Electronic Warfare Computer Resources Div.

EFFECTIVE LIFE CYCLE SOFTWARE SUPPORT: A STUDY IN DISCIPLINE AND VERSATILITY

G. H. SMITH In AGARD Design for Tactical Avionics Maintainability 7 p Oct. 1984

Avail: NTIS HC A13/MF A01

An effective life cycle software support capability that has evolved from emphasis being placed on a disciplined management process and a versatile set of laboratory facilities is characterized. The evolution of the capability described is still in progress. Much is yet to be accomplished in several areas. It is still very difficult to gain information in the early stages of the development cycle of a software system. Information that would enhance supportability and reduce eventual software support costs is elusive. Many of the configuration and data management functions are far too labor intensive. Great strides are possible in the automation and integration of data and documentation. As system complexities are certain to continually increase, so will the challenge to improve the approach to maintainability of the new generations of software. B.G.

N85-16747# Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West Germany).

EXPERIENCE IN USING ON-AIRCRAFT SOFTWARE FOR TESTING INTEGRATED SYSTEMS

K. NUMBERGER In AGARD Design for Tactical Avionics Maintainability 20 p Oct. 1984 refs

Avail: NTIS HC A13/MF A01

A need exists for test software capable of monitoring complex avionic systems during flight and delivering the collected information immediately after the mission for debriefing and maintenance, and testing complex avionic system with respect to correct functioning and integration status. It is very important that during the test run easy switching between the operational program without reloading is possible. The following feature of the co-resident program have proved the most useful input data display, in-flight moniter, and extended individual equipment/system tests. The highest priority is therefore given to optimizing the co-resident software, especially the Advanced Ground Test Facility (AGTR), while the priority for the External Ground Test Program (EGTP) refinement was downgraded. B.G.

N85-16749# International Business Machines Corp., Research Triangle Park, N.C.

INVESTIGATING VERSION DEPENDENCE IN FAULT-TOLERANT SOFTWARE

R. K. SCOTT, J. W. GAULT (ARO, Research Triangle Park, N.C.), D. F. MCALLISTER (North Carolina State Univ., Raleigh), and J. WIGGS (North Carolina State Univ., Raleigh) *In* AGARD Design for Tactical Avionics Maintainability 11 p Oct. 1984 refs Avail: NTIS HC A13/MF A01

The results are reported of an experiment conducted to validate the ability of several fault tolerant software reliability models to accurately predict system reliability. It was demonstrated that the dependent form of the model for the recovery block could predict reliability. The independent model failed to predict reliability due to version dependence. This dependence appeared to be due to the difficulty factor and not due to algorithmic dependence as might be expected. The recovery block does provide reliability gain over a single version of a program. It was demonstrated that the consensus recovery block approach to software fault tolerance was superior to the N version programming approach. R.S.F. N85-16750# Dowty Electronics Ltd., London (England). Controls Div.

THE EFFECT ON SOFTWARE DESIGN OF TESTING BY SYMBOLIC EXECUTION

D. A. RUTHERFORD and F. LAM /n AGARD Design for Tactical Avionics Maintainability 5 p Oct. 1984 Avail: NTIS HC A13/MF A01

Some special characteristics of real time software are addressed. The cost impact on applying symbolic execution is discussed. The results obtained in a symbolic test are more comprehensive as the conditions that lead to a particular path being executed are recorded as well as the final contents of variables. A symbolic value can represent a class of numeric values. This offers the advantages of time saving in test data preparation. In the extreme, test specifications can be eliminated completely which means that the maintenance cost for the associated text document is eliminated also. An unquantifiable advantage is that symbolic execution gives the programmer more insight into the working of the module under test and thus helps to check the specification of the routine. The test captures the philosophies behind both black and white box testing. R.S.F.

N85-16751# LABEN Space Instrumentation and Systems, Milan (Italy).

RELIABLE SOFTWARE DESIGN FOR AVIONICS AND SPACE APPLICATIONS

P. DONZELLI and G. GIANNINI *In* AGARD Design for Tactical Avionics Maintainability 11 p Oct. 1984 refs

Avail: NTIS HC A13/MF A01

The fundamental quality requirements of space software are the reliability and testability of software products. Only a structured methodology of software design can satisfy these pecularities producing software modules with low coupling and high strength. The production of software with these features becomes more complex when the work environment of software is a real time one. The first step toward the creation of reliable software is the introduction of a structured software design methodology properly devoted to real time applicatures. The software design methodology developed by LABEN to produce software for real time systems for space applications is discussed. R.S.F.

N85-17194# Joint Publications Research Service, Arlington, Va. DESCRIPTION OF MBB COMPUTERIZED DESIGN TECHNIQUES FOR A320

In its West Europe Rept.: Sci. and Technol. (JPRS-WST-85-001) p 7-9 2 Jan. 1985 Transl. into ENGLISH from VDI Nachr. (Dusseldorf), 28 Sep. 1984 p 26

Avail: NTIS HC A05/MF A01

The design of aircrafts by computerized design techniques is discussed. Picture screen, light marker, and computers are now exclusively the means by which the new Airbus A320 aircraft is built. Complete major structural parts, components, metal and synthetic material structures, down to the smallest sheet metal parts and connection elements are drawn on the picture screen, the drawing data are stored in computers, they are preserved on magnetic tape for use as construction documents, and they are reproduced on microfilm or they are printed out on paper. E.A.K.

N85-17578# Boeing Aerospace Co., Seattle, Wash. Engineering Technology Div.

SOFTWARE TEST HANDBOOK: SOFTWARE TEST GUIDEBOOK, VOLUME 2 Final Report, Mar. 1982 - Sep. 1983 E. PRESSON Griffiss AFB, N.Y. RADC Mar. 1984 281 p (Contract F30602-82-C-0059)

(AD-A147289; RADC-TR-84-53-VOL-2) Avail: NTIS HC A13/MF A01 CSCL 09B

The purpose of the Software Test Handbook effort was to provide Air Force software developers with guidelines and methodology for the effective use of higher order language (HOL) software testing techniques and for the selection of automated tools for the testing of computer programs. The effort resulted in a two volume final technical report. Volume 1, the Final Technical Report, describes the total contractual effort. This report, Volume 2 - Software Test Guidebook, contains the guidelines and methodology resulting from the effort. In addition, it contains the following: (1) summary descriptions of the testing techniques, (2) an extensive bibliography, (3) typical paragraphs that can be included in software development Statements of Work (SOW) to specify the use of advanced software testing techniques by the contractor during the testing and verification phases of a contracted software development, and (4) a cross-reference to government and commercially available catalogs listing automated test tools that support the various testing techniques. Author (GRA)

N85-17603*# Massachusetts Inst. of Tech., Cambridge. Lab. for Information and Decision Systems.

RESEARCH ON OPTIMAL CONTROL, STABILIZATION AND COMPUTATIONAL ALGORITHMS FOR AEROSPACE APPLICATIONS Final Report, 1966 - 1984

M. ATHANS Oct. 1984 64 p refs

(Contract NGL-22-009-124)

(NASA-CR-174318; NAS 1.26:174318; LIDS-FR-1418;

MIT-OSP-76265) Avail: NTIS HC A04/MF A01 CSCL 09B

The research carried out in the areas of optimal control and estimation theory and its applications under this grant is reviewed. A listing of the 257 publications that document the research results is presented.

N85-17613# Technion - Israel Inst. of Tech., Haifa. Faculty of Industrial and Mangement Engineering.

TAIL BEHAVIOUR FOR SUPREMA OF EMPIRICAL PROCESSES Technical Report

R. J. ADLER and L. D. BROWN Sep. 1984 54 p

(Contract AF-AFOSR-0068-83)

(AD-A147629; AFOSR-84-0937TR) Avail: NTIS HC A04/MF A01 CSCL 12A

This document considers multi-variate empirical processes with an empirical distribution function based on i.i.d. variables with certain distribution functions. GRA

16

PHYSICS

Includes physics (general); acoustics; atomic and molecular physics; nuclear and high-energy physics; optics; plasma physics; solid-state physics; and thermodynamics and statistical physics.

A85-19269#

NOISE OF AN AIRFOIL IN A FLOW [BRUIT D'UN PROFIL DANS UN ECOULEMENT]

P. GARCIA and P. GERARD (ONERA, Chatillon-sous-Bagneux, Hauts-de-Seine, France) (Colloque d'Acoustique Aeronautique, 9th, Compiegne, France, Nov. 14-16, 1984) ONERA, TP, no. 1984-155, 1984, 26 p. In French. refs

(ONERA, TP NO. 1984-155)

The results of measurements of the noise emitted from the trailing edge of a NACA 0012 airfoil embedded in a turbulent flow in an anechoic wind tunnel are reported. Pressure taps were set in the wall and on the extrados and intrados of the airfoils, which was kept at a 0.4 deg angle of attack. The sensors near the trailing edge were calibrated to relate pressure fluctuation data to acoustic resonance. A grid of 47 electrostatic polarized plastic membranes on the chord allowed determination of the acoustic profile. A theoretical model was devised to interpret the data and characterize the turbulence scales. The associated acoustic field was calculated according to a theory by Howe (1977), which depended on describing the boundary layer, a problem solved by spectral wavenumber and fluctuating pressure and pressure spectra and turbulence scale techniques. M.S.K.

A85-19505#

AN__EXPERIMENTAL -- STUDY--OF---SOUND -- ATTENUATION CHARACTERISTICS IN CIRCULAR DUCTS WITH LINED RADIAL BAFFLES

M. A. SHARAF (Dynatech R/D Co., Cambridge, MA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 8 p. refs (AIAA PAPER 85-0079)

Experimental data are reported to show that the insertion of acoustically treated radial baffles in circular ducts can attenuate airborne noise in the ducts. The tests covered five different liner materials with different thicknesses, including fiberglass and foam, compressed to 0.5 in. A sound driver sent pulses down lined ducts and data were taken on spectra, frequencies, and amplitudes before and after the liners, which were placed at varying angles to each other. High acoustic resistance (HAR) liners produced broad spectral attenuation, while low acoustic resistance (LAR) liners resulted in spectral peaks at several frequencies. Increasing the angles between the liners, but broadened the effectiveness of the LAR liners. Further studies are indicated on the effects of air flow in the duct and of point-reacting liners. M.S.K.

A85-19507*# Dynamics Technology, Inc., Torrance, Calif. INVESTIGATION OF NONLINEAR EFFECTS IN THE INSTABILITIES AND NOISE RADIATION OF SUPERSONIC JETS

S. I. JANJUA and D. K. MCLAUGHLIN (Dynamics Technology, Inc., Torrance, CA) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 10 p. refs

(Contract NAS1-17093)

(AIAA PAPER 85-0081)

The nonlinear interactions of fluctuating components which produce noise in supersonic jet flows were studied experimentally. Attention was given to spectral components interactions and the spectral effects of increasing Re. A jet exhausted in perfectly expanded conditions was monitored by microphones in the maximum noise emission direction. Trials were run at Mach 1.4 and 2.1 and the Re was varied from 5000-20,000 and 9000-25,000, respectively. Hot-wire data were gathered to examine the mode-mode interactions and a point glow discharge was used to excite the jets. The noise was found to exhibit discrete frequency components and a single tone instability at Re below 10,000. Mode interactions were found to weaken after the instabilities reached a crescendo and then decayed, leading to a nonlinear spectral broadening effect.

A85-19729#

RADIATIVE ENTROPY PRODUCTION

V. S. ARPACI (Michigan, University, Ann Arbor, MI) American Institute of Aeronautics and Astronautics, Aerospace Sciences Meeting, 23rd, Reno, NV, Jan. 14-17, 1985. 5 p. refs (AIAA PAPER 85-0408)

A radiative tensor is defined in terms of the specular moments of the radiative transfer equation and used to quantify radiative entropy production. The radiative stress is expressed in a manner similar to viscous stress as derived from elastic stress. Entropy production is considered in terms of radiation stress, conduction and friction effects in order to obtain its spatial distribution. A production minima is found to yield the least irreversible operating conditions when the production formula is applied to the case of aerodynamic heating. M.S.K.

A85-20236#

A LINEARLY CORRECTING METHOD OF DEVIATION FUNCTION FOR CONSIDERING THE INFLUENCE OF PRESSURE ON THE THERMODYNAMIC PROPERTIES OF COMBUSTION GAS

J. YAN, Y. YANG, and M. LIU (Harbin Institute of Science and Technology, Harbin, People's Republic of China) Journal of Engineering Thermophysics, vol. 5, May 1984, p. 111-118. In Chinese, with abstract in English. refs

A85-20650#

THE UNAMBIGUOUS IN-FLIGHT DETERMINATION OF PROPELLER ROTATIONAL NOISE IN AIRCRAFT WITH FOUR-CYCLE COMBUSTION ENGINES [DIE EINDEUTIGE ERMITTLUNG DES PROPELLERDREHKLANGS BEI FLUGZEUGEN MIT 4-TAKT-VERBRENNUNGSMOTOREN IM FLUG]

M. KALLERGIS (Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Institut fuer Entwurfs-Aerodynamik, Brunswick, West Germany) Deutsche Arbeitsgemeinschaft fuer Akustik, Meeting, Darmstadt, West Germany, Mar. 27-29, 1984, Paper. 4 p. In German.

A technique permitting the separation of motor noise from propeller rotation noise in light aircraft with four-cycle engines when the number of cylinders is a multiple of the number of propeller blades is demonstrated. Six condensor microphones are mounted on the leading edge of the wing of a Cessna T-207 equipped with a three-blade controllable-pitch propeller and a six-cylinder engine with output 212 kW at 2600 rpm, and an additional microphone is placed 20 cm from the exhaust outlet; the signals from all seven microphones are recorded simultaneously on a multiband magnetic tape and analyzed. A two-channel FFT analyzer is used to perform in-phase subtraction in time domain of the motor exhaust signal from the mixed signal recorded at each wing microphone (after appropriate amplitude correction). A similar FFT technique in frequency domain is also shown. T.K.

A85-21842*# Bionetics Corp., Hampton, Va.

FIELD-INCIDENCE NOISE TRANSMISSION LOSS OF GENERAL AVIATION AIRCRAFT DOUBLE-WALL CONFIGURATIONS

F. W. GROSVELD (Bionetics Corp., Hampton, VA) Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. 1985, p. 117-123. Previously cited in issue 06, p. 837, Accession no. A84-18133. refs

(Contract NAS1-16978)

A85-21858*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

SCĂLING OF AIRFOIL SELF-NOISE USING MEASURED FLOW PARAMETERS

T. F. BROOKS and M. A. MARCOLINI (NASA, Langley Research Center, Acoustics and Noise Reduction Div., Hampton, VA) AIAA Journal (ISSN 0001-1452), vol. 23, Feb. 1985, p. 207-213. refs

Data from an airfoil broadband self-noise study are reported. Attention here is restricted to two-dimensional models at zero angle of attack to the flow. The models include seven NACA 0012 airfoil sections and five flat plate sections with chordlengths ranging from 2.54 to 60.96 cm. Testing parameters include flow velocity to 71.3 m/s and boundary-layer turbulence through natural transition and by tripping. Detailed aerodynamic measurements are conducted in the near-wake of the sharp trailing edges. The noise spectra of the self-noise sources are determined by the use of a cross-spectral technique. The acoustic data are normalized using the measured aerodynamic parameters in order to evaluate a commonly used scaling law. An examination of the Reynolds number dependence of the normalized overall levels has revealed a useful scaling result. This result appears to quantify the transition between turbulent boundary-layer trailing-edge noise and laminar boundary-layer vortex shedding noise. Author

A85-22071

A PATH MODEL OF AIRCRAFT NOISE ANNOYANCE

S. M. TAYLOR (McMaster University, Hamilton, Ontario, Canada) Journal of Sound and Vibration (ISSN 0022-460X), vol. 96, Sept. 22, 1984, p. 243-260. refs

This paper describes the development and testing of a path model of aircraft noise annoyance by using noise and social survey data collected in the vicinity of Toronto International Airport. Path analysis is used to estimate the direct and indirect effects of seventeen independent variables on individual annoyance. The results show that the strongest direct effects are for speech interference, attitudes toward aircraft operations, sleep interruption and personal sensitivity to noise. The strongest indirect effects

خب خ

٠

are for aircraft Leq(24) and sensitivity. Overall the model explains 41 percent of the variation in the annoyance reported by the 673 survey respondents. The findings both support and extend existing statements in the literature on the antecedents of annoyance.

Author

N85-16586*# Old Dominion Univ., Norfolk, Va. Dept. of Electrical Engineering.

ULTRASOUND INSTRUMENTATION FOR THE 7 INCH MACH SEVEN TUNNEL Final Report, 28 Aug. - 31 Dec. 1984

D. S. MAZEL and R. R. MIELKE Jan. 1985 29 p refs

(Contract NAS1-17099)

(NASA-CR-174277; NAS 1.26:174277) Avail: NTIS HC A03/MF A01 CSCL 20A

The use of an Apple II + microcomputer to collect data during the operation of the 7 inch Mach Seven Tunnel is discussed. A method by which the contamination of liquid oxygen is monitored with sound speed techniques is investigated. The electrical equivalent of a transducer bonded to a high pressure fill plug is studied. The three areas are briefly explained and data gathered for each area are presented. B.G.

N85-16590*# Aeronautical Research Associates of Princeton, Inc., N. J.

ANALYSIS OF THE SURFACE LOAD AND RADIATED SOUND OF A VIBRATING AIRFOIL WITH APPLICATION TO THE EXPERIMENT OF BROOKS Final Report

J. E. YATES Washington NASA Jan. 1984 143 p refs (Contract NAS1-17003)

(NASA-CR-3864; NAS 1.26:3864; ARAP-508) Avail: NTIS HC A07/MF A01 CSCL 20A

A method is developed for calculating the surface load and radiated sound from a vibrating surface in a compressible viscous fluid. The method is applied to a thin two-dimensional elliptic cross-section. For large values of the viscous diffusion parameter, the surface load tends to an elliptic distribution in agreement with the results of inviscid theory when edge pressure continuity is enforced. For thin surfaces, the surface load is insensitive to variations in the thickness ratio. A three-dimensional spectral technique is developed to calculate the inviscid surface load and radiated sound from a thin vibrating airfoil. The inviscid theory predicts the correct form of the far field sound pressure and its phase. The actual levels are somewhat sensitive to the choice of theoretical spanwise surface pressure mode but are in better agreement with the experiment than the surface pressure. The comparison of theoretical and experimental surface pressure indicates that the viscous theory, used to validate the inviscid theory, is either inadequate or there is a source of experimental error. B.S.F.

N85-16593# Federal Aviation Administration, Washington, D.C. Office of Environment and Energy.

HELICOPTER NOISE SURVEY PERFORMED AT LAS VEGAS, NEVADA, 19-21 JANUARY, 1984

S. R. ALBERSHEIM 1984 49 p

(AD-A147392; FAA/EE-84-15) Avail: NTIS HC A03/MF A01 CSCL 20A

The FAA conducted a noise measurement survey of helicopter operations at Las Vegas during the Annual Helicopter Association International Convention. The survey was performed during the period of January 19-21, 1984. The purpose of this noise survey was to obtain additional noise data for a number of different helicopter models during normal operations in an urban environment. This survey was the first test program which measured sideline noise levels beyond 500 feet. The data collected are classified as survey type data, since the data obtained were from target of opportunity as apposed to controlled test data. GRA **N85-16595#** Federal Aviation Administration, Washington, D.C. Office of Environment and Energy. **NOISE MEASUREMENT FLIGHT TEST: DATA-ANALYSES**

AEROSPATIALE AS-355F TWINSTAR HELICOPTER J. S. NEWMAN, E. J. RICKLEY, K. R. BEATTIE, and T. L.

J. S. NEWMAN, E. J. RICKLEY, K. R. BEATTIE, and T. L. BLAND Aug. 1984 101 p (AD-A147497; AD-F300490; DOT/FAA/EE-84-04) Avail: NTIS

(AD-A14/49/; AD-F300490; DOT/FAA/EE-84-04) AVall: NTS HC A06/MF A01 CSCL 20A

This report documents the results of a Federal Aviation Administration (FAA) noise measurement flight test program with the TwinStar twin-jet helicopter. The report contains documentary sections describing the acoustical characteristics of the subject helicopter and provides analyses and discussions addressing topics ranging from acoustical propagation to environmental impact of helicopter noise. This test program was designed to address a series of objectives including: (1) acquisition of acoustical data for use in assessing heliport environmental impact, (2) documentation of directivity characteristics for static operation of helicopters, (3) establishment of ground-to-ground and air-to-ground acoustical propagation relationships for helicopters, (4) determination of noise event duration influences on energy dose acoustical metrics, (5) examination of the differences between noise measured by a surface mounted microphone and a microphone mounted at a height of four feet (1.2 meters), and (6) documentation of noise levels acquired using international helicopter noise certification test procedures. GRA

N85-17667*# Cleveland State Univ., Ohio.

INVESTIGATION ON EXPERIMENTAL TECHNIQUES TO DETECT, LOCATE AND QUANTIFY GEAR NOISE IN HELICOPTER TRANSMISSIONS Final Report

P. M. FLANAGAN and W. J. ATHERTON Washington NASA Jan. 1985 101 p refs Original contains color illustrations (Contract NAG3-315)

(NASA-CR-3847; E-2294; NAS 1.26:3847) Avail: NTIS HC A06/MF A01 CSCL 20A

A robotic system to automate the detection, location, and quantification of gear noise using acoustic intensity measurement techniques has been successfully developed. Major system components fabricated under this grant include an instrumentation robot arm, a robot digital control unit and system software. A commercial, desktop computer, spectrum analyzer and two microphone probe complete the equipment required for the Robotic Acoustic Intensity Measurement System (RAIMS). Large-scale acoustic studies of gear noise in helicopter transmissions cannot be performed accurately and reliably using presently available instrumentation and techniques. Operator safety is a major concern in certain gear noise studies due to the operating environment. The man-hours needed to document a noise field in situ is another shortcoming of present techniques. RAIMS was designed to reduce the labor and hazard in collecting data and to improve the accuracy and repeatability of characterizing the acoustic field by automating the measurement process. Using RAIMS a system operator can remotely control the instrumentation robot to scan surface areas and volumes generating acoustic intensity information using the two microphone technique. Acoustic intensity studies requiring hours of scan time can be performed automatically without operator assistance. During a scan sequence, the acoustic intensity probe is positioned by the robot and acoustic intensity data is collected, processed, and stored.

N85-17668*# Virginia Polytechnic Inst. and State Univ., Blacksburg.

AN IMPROVED SOURCE MODEL FOR AIRCRAFT INTERIOR NOISE STUDIES

J. R. MAHAN and C. R. FULLER Jan. 1985 30 p refs (Contract NAG1-493)

(NASA-CR-172517; NAS 1.26:172517) Avail: NTIS HC A03/MF A01 CSCL 20A

There is concern that advanced turboprop engines currently being developed may produce excessive aircraft cabin noise levels. This concern has stimulated renewed interest in developing aircraft interior noise reduction methods that do not significantly increase take off-weight. An existing analytical model for noise transmissioninto aircraft cabins was utilized to investigate the behavior of an improved propeller source model for use in aircraft interior noise studies. The new source model, a virtually rotating dipole, is shown to adequately match measured fuselage sound pressure distributions, including the correct phase relationships, for published data. The virtually rotating dipole is used to study the sensitivity of synchrophasing effectiveness to the fuselage sound pressure trace velocity distribution. Results of calculations are presented which reveal the importance of correctly modeling the surface pressure phase relations in synchrophasing and other aircraft interior noise studies. R.S.F.

N85-17669# Federal Aviation Administration, Washington, D.C. TEST OF DISPERSAL OF TURBOJET AIRCRAFT DEPARTURE TRACKS AT WASHINGTON NATIONAL AIRPORT (1983-84), VOLUME 1 REPORT Summary Report, 24 Oct. 1983 - 7 Jan. 1984

Oct. 1984 106 p 2 Vol.

(AD-A148111) Avail: NTIS HC A06/MF A01 CSCL 20A

This report is Volume 1 of a two-volume set describing the analysis of aircraft noise before, during and after the test of the so-called Scatter Plan, a dispersal of flight tracks for turbojet aircraft departing from Washington National Airport. The test, conducted by the Federal Aviation Administration (FAA) at the request of the Metropolitan Washington Council of Governments, took place from October 24, 1983, through January 7, 1984. Volume 1 presents analysis of data collected in the course of the test. Volume 2, the Technical Appendix, consists of a compilation of field sheets, survey forms, and details of the field noise measurement program and the community attitudinal survey. The purpose of this report is to present the data collected during the test for the information of and interpretation by the interested public. The report does not include conclusions or recommendations on maintaining or changing the flight paths at Washington National Airport. GRA

N85-17670# Federal Aviation Administration, Washington, D.C. Office of Environment and Energy.

NOISE MEASUREMENT FLIGHT TEST FOR BOEING VERTOL 234/CH 47-D HELICOPTER: DATA/ANALYSES

J. S. NEWMAN, T. L. BLAND, and K. R. BEATTIE Sep. 1984 195 p

(AD-A148172; FAA/EE-84-7) Avail: NTIS HC A09/MF A01 CSCL 20A

This report documents the results of a Federal Aviation Administration (FAA) noise measurement flight test program with the Boeing-Vertol CH-47D helicopter. The report contains documentary sections describing the acoustical characteristics of the subject helicopter and provides analyses and discussions addressing topics ranging from acoustical propagation to environmental impact of helicopter noise. This test program was designed to address a series of objectives including; (1) acquisition of acoustical data for use in assessing heliport environment impact, (2) documentation of directivity characteristics for static operations of helicopters, (3) establishment of ground-to-ground and air-to-ground acoustical propagation relationships for helicopters, (4) determination of noise event duration influences on energy dose acoustical metrics, (5) examination of the differences between noise measured by a surface mounted microphone and a microphone mounted at a height of four feet (1.2 meters), and (6) documentation of noise levels acquired using international helicopter noise certification test procedures. GRA

N85-17672# Federal Aviation Administration, Washington, D.C. Office of Environment and Energy.

NOISE MEASUREMENT FLIGHT TEST: DATA-ANALYSES AEROSPATIALE AS 350D ASTAR HELICOPTER

J. S. NEWMAN, E. J. RICKLEY, K. R. BEATTIE, and T. L. BLAND Sep. 1984 175 p

(AD-A148496; FAA/EE-84-05) Avail: NTIS HC A08/MF A01 CSCL 20A

This report documents the results of a Federal Aviation Administration (FAA) noise measurement flight test program with the-AStar-helicopter.-The-report-contains-documentary-sectionsdescribing the acoustical characteristics of the subject helicopter and provides analyses and discussions addressing topics ranging from acoustical propagation to environmental impact of helicopter noise. This program was designed to address a series of objectives including: (1) acquisition of acoustical data for use in assessing heliport environmental impact, (2) documentation of directivity characteristics for static operation of helicopters, (3) establishment of ground-to-ground and air-to-ground acoustical propagation relationships for helicopters, (4) determination of noise event duration influences on energy dose acoustical metrics, (5) examination of the differences between noise measured by a surface mounted microphone and a microphone mounted at a height of four feet (1.2 meters), and (6) documentation of noise levels acquired using international helicopter noise certification test procedures. GRA

N85-17673# Federal Aviation Administration, Washington, D.C. Office of Environment and Energy.

NOISE MEASUREMENT FLIGHT TEST: DATA-ANALYSES, SIKORSKY S-76A HELICOPTER

J. S. NEWMAN, E. J. RICKLEY, T. L. BLAND, and K. R. BEATTIE Sep. 1984 190 p

(AD-A148525; FAA/EE-84-6) Avail: NTIS HC A09/MF A01 CSCL 17A

This report documents the results of a FAA noise measurement flight test program with the Sikorsky S-76 helicopter. It contains documentary sections describing the acoustical characteristics of the subject helicopter and provides analyses and discussions addressing topics ranging from acoustic propagation to environmental impact of helicopter noise. This report is the sixth in a series of seven documenting the FAA helicopter noise measurement program conducted at Dulles International Airport during the summer of 1983. The S-76 test program involved the acquisition of detailed acoustic, position and meteorological data. This test program was designed to address a series of objectives including: (1) acquisition of acoustic data for use in assessing heliport environmental impact; (2) documentation of directivity characteristics for static operation of helicopters; (3) establishment of ground-to-ground and air-to-ground acoustic propagation relationships for helicopters; (4) determination of noise event duration influences on energy dose acoustical metrics; (5) examination of the differences between noise measured by a surface-mounted microphone and a microphone mounted at a height of four feet; and (6) documentation of noise levels acquired using international helicopter noise certification test procedures. GRA

N85-17677# Deutsche Forschungs- und Versuchsanstalt fuer Luft- und Raumfahrt, Brunswick (West Germany). Abt. Technische Akustik.

AEROACOUSTICS AT THE DFVLR BRUNSWICK RESEARCH CENTER: A SURVEY ON RECENT AND CURRENT ACTIVITIES

H. HELLER Aug. 1984 83 p refs Presented at 9th AAAF/GALF Colloq. d'Acoust. Aeron., Compiegne, France, 14-16 Nov. 1984 (DFVLR-MITT-84-14) Avail: NTIS HC A05/MF A01; DFVLR, Cologne DM 23.50

Basic and applied research and development projects pertaining to the noise of propeller driven planes and helicopters, to aeroacoustic specifics of wind tunnels, to airport noise and blast barriers, and to aerodynamically induced automobile noise are discussed. Planning of aeroacoustic projects is presented, and cooperation in national and international research and scientific committees is treated. Author (ESA)

SOCIAL SCIENCES

Includes social sciences (general); administration and management; documentation and information science; economics and cost analysis; law and political science; and urban technology and transportation.

A85-19826

THE DIVISION OF TASKS IN MODERN AIR TRANSPORT AND ITS EFFECT ON THE LIABILITY OF THE AIR CARRIER - THE CONCEPT 'AGENTS' IN THE SO-CALLED WARSAW CONVENTION [DIE ARBEITSTEILIGKEIT IM MODERNEN LUFTVERKEHR UND IHR EINFLUSS AUF DIE HAFTUNG DES LUFTFRACHTFUEHRERS - DER BEGRIFF 'LEUTE' IM SOG. WARSCHAUER ABKOMMEN]

R. SCHMID Frankfurt, Universitaet, Fachbereich Rechtswissenschaft, Doktor Dissertation, 1983, 286 p. In German. refs

The legal definition of air-carrier liability in paragraphs 17-20 of the Warsaw Convention of 1929 is investigated, with a focus on the French term 'preposes' in paragraph 20. Linguistic, comparative, historical, and logical analyses of the term as it has been incorporated into the legal codes of the signatories and in relevant passages of laws governing sea, rail, and road transportation are undertaken; and it is shown that both narrow interpretations (preposes = employees of the carrier) and broad interpretations (preposes = employees and independent contractors) have been or are currently in force. It is argued that the broad definition is correct but that the carrier is liable only for the acts or omissions of persons or firms performing directly-air-carriage-related functions. Legal language clarifying this relationship is proposed for eventual insertion in the Convention, and the effect of the present language, as interpreted, on each individual type of employee or contractor commonly involved in modern air transport is evaluated. TK

A85-21840#

SKIRT MATERIAL EFFECTS ON AIR CUSHION DYNAMIC HEAVE STABILITY

T. A. GRAHAM, P. A. SULLIVAN (Toronto, University, Downsview, Ontario, Canada), and M. J. HINCHEY (Newfoundland, Memorial University, St. John's; Toronto, University, Downsview, Ontario, Canada) Journal of Aircraft (ISSN 0021-8669), vol. 22, Feb. 1985, p. 101-108. Research supported by the Transportation Development Centre of Canada; Natural Sciences and Engineering Research Council of Canada. Previously cited in issue 05, p. 692, Accession no. A83-16675. refs (Contract NSERC-AS-3378)

A85-21942

REPORT FROM THE UNITED STATES OF AMERICA

J. E. MURDOCK, III (FAA, Washington, DC) Zeitschrift fuer Luftund Weltraumrecht (ISSN 0340-8329), vol. 33, Dec. 1984, p. 298-304.

Legal aspects of airport planning, construction, and expansion in the U.S. are surveyed. It is pointed out that the impetus for new airport construction or the enlargement of existing facilities comes from local or state governments or from citzen groups rather than from the Federal government, which enters the process (through the FAA) when funds from the Airport Improvement Program are applied for. Opponents mainly use the provisions of the National Environmental Policy Act of 1969 or its state or local analogs, challenging the sponsor or the FAA in Federal or state courts on the grounds that the detrimental environmental impact of the planned construction is not justified by the expected economic or traffic-flow benefits. Such actions have been effective in delaying or preventing construction, especially of new large-capacity commercial-carrier airports, so that most new capacity must come from expansion. Nevertheless, it is argued that local initiative and eventual local resolution of such conflicts is as effective an approach as centrally imposed planning. Data on the local economic benefits of airports and the timetable of a typical planning effort are provided in tables. T.K.

A85-21943

REPORT FROM THE UNITED KINGDOM

R. L. EVERITT (British Airports Authority, Gatwick, Sussex, England) Zeitschrift fuer Luft- und Weltraumrecht (ISSN 0340-8329), vol. 33, Dec. 1984, p. 305-316.

The legal procedures required for the planning and implementation of airport construction or expansion in the UK are reviewed, with a focus on recent major terminal developments undertaken at the three London airports by the British Airports Authority. The steps involved in obtaining a Development Order are characterized, including the Planning Application, preinquiry procedures, the public inquiry (justification of the development and evaluation of its impact), the role of the presiding Inspector, the postinguiry report to the Government Ministers and their ruling, implementation of the decision by local planning authorities, and court challenges to the decision of the Ministers by affected parties (on grounds of procedural errors or unreasonableness). It is found that the procedures are often very time-consuming, and that opponents are often successful in delaying construction or forcing the inclusion of environmental provisions such as curfews or noise barriers. T.K.

A85-21944

CONSTRUCTION AND EXTENSION OF AIRPORTS - LEGAL PROCEDURE AND PRACTICE IN CANADA

J.-L. MAGDELENAT (McGill University, Montreal, Canada) Zeitschrift fuer Luft- und Weltraumrecht (ISSN 0340-8329), vol. 33, Dec. 1984, p. 317-327. refs

A85-21945

CREATION AND EXTENSION OF AIRPORTS - PROCEDURES AND PRACTICE [CREATION ET EXTENSION D'AEROPORTS -PROCEDURES ET PRATIQUE]

J. DUTHEIL DE LA ROCHERE (Paris V, Universite, Paris, France) Zeitschrift fuer Luft- und Weltraumrecht (ISSN 0340-8329), vol. 33, Dec. 1984, p. 329-342. In French. refs

The legal procedures involved in the planning and construction of new airports or the expansion of existing airports in France are surveyed. Airports are classified according to technical criteria (following ICAO Annex 14), usage (private, public, or state), and sponsorship (state or nonstate); and the procedures required for the various classes are characterized. National and regional planning efforts begun in 1973 are shown to be in a waiting phase, since the growth of air traffic (by about 10 percent/yr) in the 1970s has slowed; realization of the plans in the 1990s is predicted. Problems involved in planning airport construction projects are discussed in detail, including land acquisition, safety, and noise, and a trend toward more transparent and publicly accessible planning and approval procedures is identified. T.K.

A85-21946 REPORT FROM SWEDEN

N. EDSTROM (Luftfartsverket, Stockholm, Sweden) Zeitschrift fuer Luft- und Weltraumrecht (ISSN 0340-8329), vol. 33, Dec. 1984, p. 343-358.

Legislation and legal procedures governing the planning and construction of airports and extensions to existing airports in Sweden are surveyed. Consideration is given to the Aviation Act of 1957 and possible conflicts between safety and environmental concerns arising under it, the National Building Act of 1947, the role of the Board of Civil Aviation (BCA) in operating 19 of the 220 Swedish airports and regulating the rest, the Environmental Protection Act of 1969, and proposals for environmental legislation in 1984. The formal procedures are shown to vary according to the initiating party (a private organization or the BCA) and to allow ample access to all concerned parties at open hearings, and the degree of cooperation in their implementation so far is judged as satisfactory. The findings of the Traffic Noise Committee of Parliament-on-aircraft-noise-(1975)-are-summarized-in-an-T.K. appendix.

A85-21947

CONSTRUCTION AND EXTENSION OF AIRPORTS - NATIONAL REPORT ON SWITZERLAND

W. GULDIMANN Zeitschrift fuer Luft- und Weltraumrecht (ISSN 0340-8329), vol. 33, Dec. 1984, p. 359-369; Discussion, p. 370, 371.

A85-21948

REPORT FROM JAPAN

T. SAKAMOTO (Japan Air Lines Co., Ltd., Tokyo, Japan) Zeitschrift fuer Luft- und Weltraumrecht (ISSN 0340-8329), vol. 33, Dec. 1984, p. 373-383. refs

Legal aspects of the planning and construction of airports and airport extensions in Japan are reviewed. Civil airports in Japan are operated exclusively under the authority of the Transport Ministry or local governments (except for the facility operated by the New Tokyo International Airport Authority), and improvements are carried out under a series of five-year plans (currently for 1981-1985). The application procedure, public notification requirements, airport-establishment and airport-expansion criteria. the public hearing process, and the rights of affected parties to challenge the decision of the Minister in court are characterized. The implications of the Supreme Court decision of 1981 (involving noise at Osaka airport) with regard to suspensions of takeoffs and landings, compensation for past and future damages, and assumption of risk by persons moving to the airport vicinity are discussed; and it is pointed out that the Osaka case, the only such case to reach the Supreme Court, was in litigation for more than 12 years. T.K.

A85-21949

NATIONAL REPORT - THE FEDERAL REPUBLIC OF GERMANY [LAENDERBERICHT - BUNDESREPUBLIK DEUTSCHLAND]

H. ACHTNICH (Arbeitsgemeinschaft Deutscher Verkehrsflughaefen, Stuttgart, West Germany) Zeitschrift fuer Luft- und Weltraumrecht (ISSN 0340-8329), vol. 33, Dec. 1984, p. 384-401; Discussion, p. 402, 403. In German.

The legal procedures involved in approving and implementing plans for airport construction or expansion in the FRG are reviewed. The FRG airport system is briefly characterized; the ongoing improvements are listed; and the two-stage formal process by which proposals are evaluated and approved (under air law and under the general planning law, at the level of the federal states of the FRG, but with review and approval by the federal Transportation Minister) is examined. Consideration is given to the broad range of parties admitted to the process, the criteria employed in the decision, and the jurisdictions available to opponents to contest the decision of the state transport ministry. The long duration of the approval process and subsequent litigation is illustrated with a timetable listing governmental and court decisions on the extension of Frankfurt airport over the period 1965-1984. ТΚ

N85-16667# RAND Corp., Santa Monica, Calif.

MANAGING RECOVERABLE AIRCRAFT COMPONENTS IN THE PPB AND RELATED PROCESSES: EXECUTIVE SUMMARY **Interim Report**

J. H. BIGELOW Jun. 1984 56 p

(Contract MDA903-81-C-0381)

(AD-A146806; RAND/R-3093-MIL) Avail: NTIS HC A04/MF A01 CSCL 15E

ORACLE (Oversight of Resources And Capability for Logistics Effectiveness) explores how the requirements to buy and repair aircraft components are related to the peacetime and planned wartime availability and flying activity of aircraft. It operates by producing a summary database from the Air Force's DO41 (Recoverable Consumption Item Requirements Computation System), a database from which one can estimate almost instantaneously and with remarkably little error how the complete DO41 computation, involving 150,000 separate components, would

have responded to a change in peacetime or wartime flying activity, aircraft availability, and a variety of other quantities. We feel that its primary use will be in the PPB process, to estimate budgetary consequences of changes in flying programs and the like. But it could also be used to help allocate funds during execution.

Author (GRA)

N85-16682# General Accounting Office, Washington, D. C. National Security and International Affairs Div. THE AIR FORCE CAN IMPROVE ITS FORECASTS OF AIRCRAFT SPARE PARTS REQUIREMENTS

19 Nov. 1984 27 p

(AD-A147911; GAO/NSIAD-85-2) Avail: NTIS HC A03/MF A01 CSCL 15E

The Air Force forecasts its aircraft spare parts requirements by calculating a ratio of future flying hours to past flying hours for the aircraft using a specific part and then applying this ratio to the historical demand for the part. GAO found that the process resulted in overstated estimates for some parts and understand estimates for others because: (1) The computer file which identifies the aircraft on which the individual parts are used contained inaccurate data. (2) The requirements were not computed on the basis off all the unique combinations of aircraft which use each part. (3) The time period used in calculating the ratios does not correspond to the time needed to obtain the part. GAO makes recommendations designed to correct these problems and improve the Air Force's forecasting process for aircraft spare parts. GRA

N85-16685# RAND Corp., Santa Monica, Calif.

ESTIMATING WARTIME SUPPORT RESOURCE REQUIREMENTS. STATISTICAL AND RELATED POLICY **ISSUES Interim Report**

L. B. EMBRY Jul. 1984 111 p

(Contract F49620-82-C-0018)

(AD-A147923; RAND/N-2163-AF) Avail: NTIS HC A06/MF A01 CSCL 15E

The Air Force spends several billion dollars annually to procure the spare parts and other resources need to support modern aircraft weapon systems. A large fraction of this investment is used to obtain assets for support of wartime operations. The assumptions used to project peacetime experience to wartime activity levels have important resource implications, but little has been done to test them empirically. Peacetime operational experiments, coupled with engineering projections of wartime failure rates, could be used to test these assumptions and provide an improved basis for resource requirements computations. This note addresses statistical and policy issues central to improving estimates of wartime support resource requirements. It uses the current problem of establishing the level of investment in spare engines for the C-5 aircraft to elucidate a number of these issues. The results should be of interest to policymakers concerned with logistics resource allocation, operational commanders whose wartime capabilities are affected by statistical assumptions and related policy decisions, and personnel responsible for producing requirements estimates. Originator-supplied keywords include: spare parts, failure, logistics planning, military aircraft and aircraft engines. GRA

N85-17732# Louisiana State Univ., Baton Rouge. Dept. of Quantitative Business Analysis.

PRODUCTION RATE VARIATIONS COST MODELS Final Report, 1 Jun. - 14 Aug. 1984 T. R. GULLEDGE, JR. 14 Aug. 1984 17 p

(Contract F49620-82-C-0035)

(AD-A147708) Avail: NTIS HC A02/MF A01 CSCL 14A

This research examines a model that may be used to estimate the cost impact of production rate changes on a timely and real world basis. Part 1 analyzes current models that are being implemented by Air Force Systems Command, and demonstrates that these models are deficient in their theoretical definition and empirical construction. Part 2 presents current status of the development of a more realistic rate variations model for the F-16 aircraft program. GRA

N85-17740*# National Aeronautics and Space Administration. Langley Research Center, Hampton, Va.

SCIENTIFIC AND TECHNICAL INFORMATION OUTPUT OF THE LANGLEY RESEARCH CENTER FOR CALENDAR YEAR 1984 Jan. 1985 247 p

(NASA-TM-86336; NAS 1.15:86336) Avail: NTIS HC A11/MF A01 CSCL 05B

The scientific and technical information that the Langley Research Center produced during the calendar year 1984 is compiled. Approximately 1650 citations are included comprising formal reports, quick-release technical memorandums, contractor reports, journal articles and other publications, meeting presentations, technical talks, computer programs, tech briefs, and patents. M.G.

19

GENERAL

N85-17928*# National Aeronautics and Space Administration. Lewis Research Center, Cleveland, Ohio.

RESEARCH AND TECHNOLOGY HIGHLIGHTS OF THE LEWIS RESEARCH CENTER Annual Report, 1984

1984 52 p

(NASA-TM-86899; NAS 1.15:86899) Avail: NTIS HC A04/MF A01 CSCL 05A

Highlights of research accomplishments of the Lewis Research Center for fiscal year 1984 are presented. The report is divided into four major sections covering aeronautics, space communications, space technology, and materials and structures. Six articles on energy are included in the space technology section. B.W.

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Supplement 187)

MAY 1985

Typical Subject Index Listing



The subject heading is a key to the subject content of the document. The title is used to provide a description of the subject matter. When the title is insufficiently descriptive of the document content, the title extension is added, separated from the title by three hyphens. The (NASA or AIAA) accession number and the page number are included in each entry to assist the user in locating the abstract in the abstract section. If applicable, a report number is also included as an aid in identifying the document. Under any one subject heading, the accession numbers are arranged in sequence with the AIAA accession numbers appearing first.

A-10 AIRCRAFT

Performance evaluation of A-10 aircraft mainteance units and aircraft using constrained facet analysis [AD-A146955] p 201 N85-15660

A-320 AIRCRAFT Description of MBB computerized design techniques for A320 p 303 N85-17194

ACCELEROMETERS

Keeping up with operational loads in the French Air Force: Defining new equipment p 292 N85-15681 ACCIDENT PREVENTION

- p 241 A85-20148 Wind shear - Taming the killer ACCIDENT PRONENESS p 241 A85-20148
- Wind shear Taming the killer ACCURACY
- Development of a Helicopter integrated navigation system p 245 N85-16802

ACOUSTIC ATTENUATION

An experimental study of sound attenuation characteristics in circular ducts with lined radial baffles [AIAA PAPER 85-0079] p 304 A85-19505 ACOUSTIC DUCTS

An experimental study of sound attenuation characteristics in circular ducts with lined radial baffles attenuation [AIAA PAPER 85-0079] p 304 A85-19505

ACOUSTIC MEASUREMENT

Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) [NASA-TM-86919] p 276 N85-15757

ACOUSTIC PROPERTIES

- Interaction of a turbulent vortex with a lifting surface [AIAA PAPER 85-0004] p 206 A85-19452 Noise measurement flight test: Data-analyses, Sikorsky
- S-76A helicopter [AD-A148525] p 306 N85-17673

ACOUSTICS

- Analysis of the surface load and radiated sound of a vibrating airfoil with application to the experiment of Brooks
- [NASA-CR-3864] p 305 N85-16590 ACTIVE CONTROL Investigations for the use of an active control in aircraft
- German thesis p 269 A85-19828 Study to eliminate ground resonance using active controls
- [NASA-CR-166609] p 255 N85-15715 Helicopter active control with rotor blades relaxation p 270 N85-16819
- ACTUATION Systems study for an Integrated Digital-Electric Aircraft
- (IDEA) [NASA-CR-3840] p 255 N85-15714 ACTUATORS
- Design and test of a four channel motor for electromechanical flight control actuation p 297 N85-17294 [NASA-CR-171838]
- ADAPTIVE CONTROL Generalized adaptive-wall wind tunnels
- p 274 A85-19601 [AIAA PAPER 85-0225] Predicted performance benefits of an adaptive digital engine control system on an F-15 airplane
- p 263 A85-19801 [AIAA PAPER 85-0255] Application of an adaptive blade control algorithm to a p 269. A85-20143 gust alleviation system Research on optimal control, stabilization and computational algorithms for aerospace applications

[NASA-CR-174318] p 303 N85-17603 ADHESIVES

A thermoplastic polyimidesulfone --- synthesis of processable and solvent resistant system p 282 A85-21483

- AEROACOUSTICS
- An experimental investigation of blade-vortex interaction at normal incidence
- [AIAA PAPER 85-0003] p 206 A85-19451 A study of the flow recirculation problems within an nechoic hover chamber
- p 273 A85-19497 [AIAA PAPER 85-0071] On boundary layer transition in high-subsonic and transonic flow under the influence of acoustic disturbances and free-stream turbulence
- p 210 A85-19508 [AIAA PAPER 85-0082] Loading characteristics of VTOL aircraft and their effect on the remaining life of the aircraft p 250 A85-20469 The unambiguous in-flight determination of propeller rotational noise in aircraft with four-cycle combustion

p 304 A85-20650 Aeroacoustics at the DFVLR Brunswick Research Center: A survey on recent and current activities

[DFVLR-MITT-84-14] p 306 N85-17677 AEROBRAKING

An optimization method for the preliminary design of interplanetary aerobraking missions p 238 N85-16822 AERODYNAMIC CHARACTERISTICS

- Aerodynamic studies linked to the development of aployable nozzles - for upper stage ballistic missiles [ONERA, TP NO. 1984-149] o 205 A85-19263 The design of airfoils at low Reynolds numbers
- [AIAA PAPER 85-0074] p 209 A85-19500 Solution of the unsteady Euler equations for fixed and rotor wing configurations
- [AIAA PAPER 85-01201 p 211 A85-19531 Numerical study on the dynamic stall process of a NACA 0012 airfoil
- [AIAA PAPER 85-0128] p 212 A85-19539 Circutation control airfoils - Past, present, future
- (AIAA PAPER 85-0204) p 215 A85-19588 Aerodynamic prediction of eliptically-shaped missile configurations using component build-up methodology [AIAA PAPER 85-0271] p 216 A85-19624 Study of winglets applied to biplanes
- (AIAA PAPER 85-0279) p 217 A85-19631 The computational treatment of supersonic wake flows
- in INCOREL [AIAA PAPER 85-0304] p 219 A85-19653

Hypersonic characteristics of an a	dvanced	aerospace
plane		
[AIAA PAPER 85-0346]	p 269	A85-19685
The influence of camber variation o	n the ae	rodynamics
of civil transport aircraft		
[AIAA PAPER 85-0353]	p 220	A85-19691
Progress in development of a Navi	er-Stoke	es solver for
evaluation of iced airfoil performance		
[AIAA PAPER 85-0410]	p 222	A85-19731
Computational aerodynamic design	n of the	Gulfstream
IV wing		
[AIAA PAPER 85-0427]	p 223	A85-19742
Tomographic reconstruction of thre	e-dime	nsional flow
over ainoils	- 005	405 40770
[AIAA PAPEH 85-0479]	p 225	A85-19776
Application of a variational method	ioo tor het ei rfe i	generaung //
AUAPUVO GIUS IOT GAS UVIAMICS PE	າວເອນ (Ol	A95.10784
[AIAA FAFEN 65-0467] The application of some lifting-box	1 220	A63-19704
to missile design	Jy reent	ry concepts
(AIAA PAPER 85-0497)	o 279	A85-19791
Selection of rational models in the	optimal	planning of
aeromechanical experiments	p 288	A85-20460
Conical bodies with a star-shape	d trans	verse cross
section, having a reserve of static sta	bility	
•	p 229	A85-20557
Euler computations of AGARD Wor	king Gro	oup 07 airfoil
test cases		
[AIAA PAPER 85-0018]	p 229	A85-20851
A large-scale computer facility	for co	mputational
aerodynamics	p 301	A85-21791
Analytical modeling of circuit aeroc	iynamici	s in the new
	0 224	NO5.15699
[NASA-IM-00912]	p 234	Noo-10000
characteristics of supersonic chilse of	onfigura	tions
[NASA-CR-174299]	n 234	N85-15690
Downwash in the plane of symme	try of a	n ellipticativ
loaded wing		
[NASA-TP-2414]	p 235	N85-15693
Aileron effectiveness for a subsonic	transpo	rt model with
a high-aspect-ratio supercritical wing	•	
[NASA-TM-85674]	p 235	N85-15695
Effect of aerodynamic and angle-of	-attack i	uncertainties
on the May 1979 entry flight control :	system o	of the Space
Shuttle from Mach 8 to 1.5		
[NASA-TP-2365]	p 280	N85-15778
Designer on civil aircraft design tre	nds in l	JSSR

p 256 N85-16768

Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems [AGARD-CP-365] p 204 N85-16771 technological Operational requirements VARSUS

capabilities p 204 N85-16798 Study of winglets applied to biplanes

- p 258 N85-16862 [NASA-TM-86350] Airworthiness and flight characteristics test of the RC-12D Guardrail V
- p 258 N85-16864 [AD-A148046] Optimum performance parameters for ski-jump
- operations of USAF fighter aircraft AD-A148532] p 258 N85-16867 **AERODYNAMIC COEFFICIENTS**
- Aerodynamics of an aspect ratio 8 wing at low Reynolds numbers
- p 217 A85-19630 (AIAA PAPER 85-0278) Correlation of airfoil icing relationships two-dimensional model and full scale rotorcraft icing test data
- [AIAA PAPER 85-0337] p 240 A85-19680 Determination of rarefied-flow aerodynamics of the Shuttle orbiter from flight measurements on STS-6 and STS-7
- p 219 A85-19686 [AIAA PAPER 85-0347] Analytical determination of propeller performance degradation due to ice accretion
- p 264 A85-20867 [AIAA PAPER 85-0339] Nonreflecting boundary conditions for the complete unsteady transonic small-disturbance equation
- p 290 A85-21875 Extremum problem concerning a wing with a maximum p 234 A85-22370 gradient of lift force

AERODYNAMIC CONFIGURATIONS

An investigation of vortex-induced aerodynamic characteristics of supersonic cruise configurations p 234 N85-15690 [NASA-CR-174299] **AERODYNAMIC CONFIGURATIONS**

Aerodynamics of an airfoil in ground effect with a jet suing from its undersurface

[AIAA PAPER 85-0019] p 207 A85-19461 Effects of covering configurations on ultralight wing aerodynamics

[AIAA PAPER 85-0277] p 217 A85-19629 Aerodynamic configured missiles - Promise and future p 248 A85-19684 [AIAA PAPER 85-0345]

Regarding parametric investigations of slender cone nose bluntness effects

[AIAA PAPER 85-0349] p 220 A85-19688 TRO-2D - A code for rational transonic aerodynamic optimization

[AIAA PAPER 85-0425] p 223 A85-19740 Design of aerodynamic bodies intelligence/expert system technique using artificial

[AIAA PAPER 85-0112] p 301 A85-20856 Optimal control of flow of a viscous incompressible fluid p 290 A85-22105 Systems study for an Integrated Digital-Electric Aircraft

(IDEA) [NASA-CR-3840] p 255 N85-15714

Aircraft drag reduction technology p 257 N85-16782 Theoretical study of boundary-layer control

p 237 N85-16784 Aerodynamic-structural study of canard wing, dual wing,

and conventional wing systems for general aviation applications p 238 N85-16829 [NASA-CR-172529]

Study of winglets applied to biplanes p 258 N85-16862 [NASA-TM-86350]

AERODYNAMIC DRAG Crossflow drag of finite-length rectangular wing-bodies [AIAA PAPER 85-0451] p 224 A85-19760

Drag prediction for projectiles and finned bodies in incompressible flow

[AIAA PAPER 85-0104] p 230 A85-20854 Drag of the fundamental shapes of parachutes p 231 A85-20998

Investigations into the effects of scale and compressibility on lift and drag in the RAE 5m pressurized p 236 N85-16773 low-speed wind tunnel An optimization method for the preliminary design of

interplanetary aerobraking missions p 238 N85-16822 AERODYNAMIC FORCES Body flow field simulation and force/moment prediction

at transonic speeds [AIAA PAPER 85-0423]

p 222 A85-19738 Calculation of the hydrodynamic characteristics of p 290 A85-22113 polyplanes An exploratory study of finite difference grids for

transonic unsteady aerodynamics p 235 N85-15696 [NASA-TM-84583]

AERODYNAMIC HEAT TRANSFER Investigations of the longitudinal flow in corner

configurations in the hypersonic regime. II - Corners p 232 · A85-22146 between swept wedges **AERODYNAMIC INTERFERENCE**

Theoretical study of blockage effect of wind-tunnel wall on wake of two-dimensional flat plate normal to plane p 272 A85-19402 wai Experimental investigation of blockage effect of upper wall of wind-tunnel of wake of two-dimensional flat plate p 272 A85-19403 normal to plane boundary

The use of panel methods for the development of low-subsonic wall interference and blockage corrections p 212 A85-19556 [AIAA PAPER 85-0159] Ground interference effects on subsonic dynamic stall in pitch and plunge p 231 A85-21841

AERODYNAMIC LOADS An improved version of the LTRAN2 for high frequency

p 205 A85-19401 domain Inexpensive calibrations for the influence function method using the interference distributed loads code --for prediction of store loads in aircraft flow fields

[AIAA PAPER 85-0270] p 247 A85-19623 Loading characteristics of VTOL aircraft and their effect on the remaining life of the aircraft p 250 A85-20469

A linearized unsteady aerodynamic analysis for transonic p 229 A85-20744 cascades Operational loads measurement: A philosophy and its

p 253 N85-15665 implementation Navy operational loads data sources and systems p 253 N85-15668

Operational loads data evaluation for individual aircraft p 253 N85-15669 fatigue monitoring Structural flight load measurement demonstration of p 254 N85-15670 structural integrity Aeroelastic analysis and the identification of flight loads p 254 N85-15679

--- Mirage 2000 aircraft

AERONAUTICS

Current problems in aviation science and technology p 199 A85-20451 Computers and progress in aviation

p 199 A85-20453 Research and technology highlights of the Lewis Research Center

[NASA-TM-86899] p 309 N85-17928 AEROSPACE ENGINEERING

PMR polyimide composites for aerospace applications - Polymerization of Monomer Reactants

p 282 A85-21520 Random equations in aerodynamics

p 238 N85-16825 [NASA-CR-174279] S-3A ballast block final design and engineering tests

[AD-A147685] p 243 N85-16842 Scientific and technical information output of the Langley Research Center for calendar year 1984

p 309 N85-17740 [NASA-TM-86336] AEROSPACE ENVIRONMENTS

Thermal design of rotatable cryogenic heat pipe joints - for heat exchangers in space applications

[AIAA PAPER 85-0068] p 279 A85-19495 AEROSPACE MEDICINE

weighing up to two tons and their causes in the context of flight medicine - German thesis p 241 A85-19846

AEROSPACE TECHNOLOGY TRANSFER Loads and Aeroelasticity Division research and

FY 1985 [NASA-TM-86356] p 234 N85-15691

AEROSPACE VEHICLES

p 212 A85-19539 Interrelated effects of pitch rate and pivot point on airfoil

dynamic stall [AIAA PAPER 85-0130] p 212 A85-19541

Keeping up with operational loads in the French Air

Loads and Aeroelasticity Division research and

Comparison of analytical and experimental steadyand

unsteady-pressure distributions at Mach number 0.78 for

a high-aspect-ratio supercritical wing model with oscillating

Speed benefits of tilt-rotor designs for LHX

Flutter control with unsteady aerodynamic models

Investigation of nonlinear effects in the instabilities and noise radiation of supersonic jets

Scaling of airfoil self-noise using measured flow

Characteristic motions for simulation of post-stall

Effects of friction dampers on aerodynamically unstable

Numerical study on the dynamic stall process of a NACA

Flutter control with unsteady aerodynamic models [AD-A147858] p 270 N85-1

p 234 N85-15691

p 235 N85-15697

p 255 N85-15717

0 270 N85-15753

p 304 A85-19507

p 304 A85-21858

p 288 A85-20828

p 269 A85-21679

p 265 A85-21866

p 270 N85-15753

Force: Defining new equipment _____p 292 __N85-15681

technology accomplishments for FY 1984 and plans for

FY 1985

[NASA-TM-863561

control surfaces

[AD-A147858]

parameters

rotor stages

0012 airfoil

[NASA-TM-84589]

[NASA-CR-166437]

AERODYNAMIĆ NOISE

[AIAA PAPER 85-0081]

AERODYNAMIC STABILITY

AERODYNAMIC STALLING

[AIAA PAPER 85-0128]

Optimization of flutter characteristics

manoeuvres and flight instabilities

Is the free flight/wind tunnel equivalence concept valid for unsteady viscous flow? [AIAA PAPER 85-0378] p 222 A85-19708

Determination of surging line of two-spool axial flow compressor with cropped fan stages at low speed by use of parallel compressor theory p 264 A85-20242

Characteristic motions for simulation of post-stall manoeuvres and flight instabilities p 269 A85-21679

Ground interference effects on subsonic dynamic stall p 231 A85-21841 in pitch and plunge Evaluation of a stalled airfoil analysis program

p 231 A85-21848

Prediction of dynamic stall characteristics using advanced non-linear panel methods p 239 N85-16836 [AD-A148453]

AERODYNAMICS Current status of numerical solutions of the

Navier-Stokes equations [AIAA PAPER 85-0032] p 207 A85-19469

A comparison between theoretical and experimental flow fields of an airfoil with deflected spoiler

p 216 A85-19622 [AIAA PAPER 85-0269] Ill-posed problems in perturbation theory (Asymptotic nethods of mechanics) p 233 A85-22364 methods of mechanics)

Circulation control: A bibliography of DTNSRDC research and selected outside references. Update p 201 N85-15661 [AD-A146966]

Aero-optics experimental techniques p 294 N85-16067 [AD-A146755]

Aeronautical Engineering: A continuing bibliography with indexes (supplement 182) [NASA-SP-7037(182)]

p 203 N85-16758 International aviation (selected articles) p 204 N85-16762 [AD-A148704] Aerodynamic issues in the design of high-lift systems

for transport aircraft o 256 N85-16780 Joined wing transonic design and test validation [AD-A148355] p 239 N85-16834

AÈROELASTICÍTY Aeroelastic characteristics of the AH-64 bearingless tail

rotor p 250 A85-20142 Forward sweep - The pros and cons

p 250 A85-20146 Aeroelastic stability and vibration of layered plates and p 288 A85-20472 cylindrical shells

Optimization of flutter characteristics p 288 A85-20828

Stress analysis and shaping of the canopy of a square p 242 A85-21668 parachute Aeroelastic analysis and the identification of flight loads

Mirage 2000 aircraft p 254 N85-15679 Stereo Electro-optical Tracking System (SETS)

[NASA-CR-172471] p 295 N85-16098 **AERONAUTICAL ENGINEERING**

ONERA - The aeronautics supercomputer is put into prvice p 302 A85-22274 service Aeronautical Engineering: A continuing bibliography with

indexes (supplement 182) [NASA-SP-7037(182)] p 203 N85-16758 Analysis of fatal accidents involving light aircraft

technology accomplishments for FY 1984 and plans for

The lightning threat to aerospace vehicles [AIAA PAPER 85-0094] p 240 p 240 A85-19516

AEROSPACEPLANES Hypersonic characteristics of an advanced aerospace

plane [AIAA PAPER 85-0346] p 269 A85-19685

AEROTHERMODYNAMICS

Application of axisymmetric analogue for calculating eating in three-dimensional flows

p 216 A85-19611 [AIAA PAPER 85-0245] optimization of the of multistage axial the Α procedure for aerothermodynamic design of

p 227 A85-19851 compressors --- German thesis Newton iteration formulas for correcting temperature and pressure in thermodynamic calculation of rocket engines

p 279 A85-20226 A new approach to some hybrid aerodynamic problems

of airfoil cascades on a general streamsheet of revolution. p 228 A85-20229

Calculation and analysis of the three-dimensional flow in centrifugal compressor impellers p 228 A85-20231

A linearly correcting method of deviation function for considering the influence of pressure on the thermodynamic properties of combustion gas

p 304 A85-20236 On the variety of type discrimination criteria of equations

on S1 and S2 stream surfaces in turbomachine p 228 A85-20238 Advances in heat transfer. Volume 16

p 288 A85-20501

Hypersonic chemically nonequilibrium viscous shock layer on wings with a catalytic surface p 229 A85-20561

Introductory aerothermodynamics of advanced space

p 231 A85-21827 transportation systems

Calculation of friction and heat transfer in turbulent flow of a compressible gas in a plane duct p 291 A85-22114

Analytical and physical modeling program for the NASA

p 220 A85-19692

p 204 N85-16764

p 250 A85-20142

p 251 A85-21379

p 200 A85-21382

p 235 N85-15695

p 284 N85-17049

Lewis Research Center's Altitude Wind Tunnel (AWT) [NASA-TM-86919] p 276 N85-15757

Aeroelastic characteristics of the AH-64 bearingless tail

Design, fabrication and verification of composite

Tooling problems in the manufacture of AH-64

Aileron effectiveness for a subsonic transport model with

Flight service evaluation of advanced composite ailerons

Afterbody drag reduction by vortex generators [AIAA PAPER 85-0354] p 220 A8

Director on institute's civil aviation projects

flexbeam tail rotor for AH-64 Apache helicopter

Composites Flexbearn Tail Rotor

on the L-1011 transport aircraft

a high-aspect-ratio supercritical wing

AFTERBODIES

AGRICULTURAL AIRCRAFT

AH-64 HELICOPTER

[NASA-TM-85674]

[NASA-CR-172483]

rotor

AILERONS

AIR BREATHING ENGINES

- Correlation and analysis of oil flow data for an air-breathing missile model [AIAA PAPER 85-0452] p 224 A85-19761
- Interactive design technique for arbitrary shaped, airbreathing missile configurations [AIAA PAPER 85-0496]
- p 249 A85-19790 Air breathing space transport vehicles with wings p 280 A85-20909
- AIR FLOW

Three-dimensional airflow and hydrometeor trajectory calculation with applications

[AIAA PAPER 85-0412] p 222 A85-19733 AIR INTAKES

- A sensor for detection of unsteady distortion maxima in air intakes
- [ONERA, TP NO. 1984-148] p 205 A85-19262 Tests of air inlets on civil aircraft
- [ONERA, TP NO. 1984-157] p 272 A85-19271 Frequency response of a jet engine test facility air supply mateva
- [AIAA PAPER 85-0053] p 273 A85-19485 Interest of internal bleed for a two-dimensional air intake

operating in a wide Mach number range (1.8-3 plus) p 237 N85 16793

AIR LAW

The division of tasks in modern air transport and its effect on the liability of the air carrier - The concept 'agents' in the so-called Warsaw Convention --- German thesis p 307 A85-19826 Report from the United States of America --- legal

- procedures for airport construction or expansion p 307 A85-21942
- Report from the United Kingdom --- legal procedures for airport construction or expansion
- p 307 A85-21943 Construction and extension of airports - Legal procedure nd practice in Canada p 307 A85-21944 Creation and extension of airports - Procedures and and practice in Canada p 307 A85-21945 practice Report from Sweden --- legal procedures for airport
- construction or expansion p 307 A85-21946 Construction and extension of airports - National report p 308 A85-21947 on Switzerland Report from Japan --- legal procedures for airport p 308 A85-21948 construction or expansion
- National report The Federal Republic of Germany ---legal procedures for airport construction or expansion p 308 A85-21949

AIR NAVIGATION Integrated navigation p 245 A85-21461

AIR POLI LITION Impact of aircraft emissions on air quality in the vicinity of airports. Volume 3: Air quality and emission modeling naarie

[AD-A147951] p 299 N85-17435 Atmospheric photochemical modeling of turbine engine fuels. Phase 1: Experimental studies. Volume 2: Environmental chamber data tabulations

p 300 N85-17470 [AD-A147786] AIR QUALITY

- Impact of aircraft emissions on air quality in the vicinity of airports. Volume 3: Air quality and emission modeling
- [AD-A147951] p 299 N85-17435 Impact of aircraft emissions on air quality in the vicinity of airports. Volume 4. Nitrogen dioxide and hydrocarbons
- p 299 N85-17436 [AD-A148253] Atmospheric photochemical modeling of turbine engine fuels. Phase 1: Experimental studies. Volume 2:
- Environmental chamber data tabulations p 300 N85-17470 [AD-A147786]
- AIR TRAFFIC The Cockpit Display of Traffic Information and the Threat
- Alert and Collision Avoidance System Integration A p 259 A85-21559 review FAA (Federal Aviation Administration) statistical
- handbook of aviation, calendar year 1983 [AD-A148171] p 203 N85-16760 Airport activity statistics of certificated route air
- carriers p 243 N85-16846 [AD-A148472] Air traffic management concepts for the UK in the 1990's:
- A review of recent RSRE work [AD-A147850] p 246 N85-16853
- AIR TRAFFIC CONTROL
- The Mission Oriented Terminal Area Simulation (MOTAS) p 274 A85-19655 [AIAA PAPER 85-0308]
- National airspace review: Airport radar service area operational confirmation report
- [DOT/FAA/AT-84/2] p 245 N85-15707 A bird strike handbook for base-level managers AD-A147928] p 293 N85-16008 [AD-A147928]

- Designer on Aeroflot automated COMMO system development p 296 N85-16765 National airspace review enhancement plan, revision 3 p 246 N85-16852
- Air traffic management concepts for the UK in the 1990's: A review of recent RSRE work
- [AD-A147850] p 246 N85-16853 National Airspace Review
- [AD-A147768] p 246 N85-16855 A cockpit-display concept for executing a multiple glide-slope approach for wake-vortex avoidance
- [NASA-TP-2386] p 261 N85-16869 Test of dispersal of turbojet aircraft departure tracks at washington National Airport (1983-84), volume 1
- report p 306 N85-17669 [AD-A148111] AIR TRANSPORTATION
- The division of tasks in modern air transport and its effect on the liability of the air carrier - The concept 'agents' in the so-called Warsaw Convention --- German thesis
- p 307 A85-19826 FAA (Federal Aviation Administration) statistical handbook of aviation, calendar year 1983
- p 203 N85-16760 [AD-A148171] Utilization of Increased Airlift Capability (UIAC) study [AD-A148669] p 243 N85-16847
- National Airspace Review AD-A1477681 p 246 N85-16855
- AIRBORNE EQUIPMENT USAF approach to airborne structural data recording:
- Airborne Data Acquisition Multifunction System (ADAMS) p 292 N85-15683 Realization and testing of an experimental color display
- system for general aviation helicopters and aircraft [BMFT-FB-W-84-042] p 262 N85p 262 N85-16872
- AIRBORNE RADAR APPROACH p 244 A85-19805 Aviation radar --- Russian book AIRBORNE SURVEILLANCE RADAR
- Atmospheric propagation losses for long-range airborne
- radar systems analysis [AIAA PAPER 85-0267] p 244 A85-19620 AIRBORNE/SPACEBORNE COMPUTERS
- Designing a priority driven multi-frame rate flight executive
- [AIAA PAPER 85-0309] p 268 A85-19656 Software design methods --- for civil and military aircraft avionics systems p 301 A85-21457
- A design methodology for integrated avionic systems p 301 A85-21458 Trends in digital flight control systems
- p 269 A85-21465
- Trends in digital engine control Integration of propulsion control with flight control and avionic systems in future military and commercial aircraft p 264 A85-21466 Investigation of semiautomatic aircraft control processes employing time redundancy in on-board digital trajectory control computers p 270 N85-16048
- Documentation and separate test program development is most important for test/maintenance
- p 203 N85-16745 Experience in using on-aircraft software for testing p 302 N85-16747 integrated systems The design and development of an integrated core system for battlefield helicopters p AIRCRAFT ACCIDENT INVESTIGATION p 260 N85-16811
- Analysis of fatal accidents involving light aircraft weighing up to two tons and their causes in the context of flight medicine --- German thesis p 241 A85-19846 AIRCRAFT ACCIDENTS
 - Judgment and discipline Recipe for survival
- p 241 A85-21582 FAA (Federal Aviation Administration) statistical handbook of aviation, calendar year 1983
- [AD-A148171] p 203 N85-16760 AIRCRAFT APPROACH SPACING
- National airspace review enhancement plan, revision 3 p 246 N85-16852
- AIRCRAFT COMMUNICATION generation tactical New military airborne communications systems - The interoperability challenge p 244 A85-19275 Integrated communications - A designers view --- for
- civil and military aircraft avionics p 245 A85-21462 Designer on Aeroflot automated COMMO system p 296 N85-16765 development Tactical HF communication for military helicopters using
- the NVIS mode p 297 N85-16807 AIRCRAFT COMPARTMENTS An improved source model for aircraft interior noise
- studies [NASA-CR-172517] p 305 N85-17668
- AIRCRAFT CONFIGURATIONS
- The joined wing An overview --- aircraft tandem wings in diamond configurations
- [AIAA PAPER 85-02741 p 247 A85-19626

Study of winglets applied to biplanes [AIAA PAPER 85-0279] p 217 A85-19631 Linearized potential flow analysis of complex aircraft configurations by HISSS, a higher order panel method p 217 A85-19632 [AIAA PAPER 85-0281] The influence of camber variation on the aerodynamics of civil transport aircraft [AIAA PAPER 85-0353] p 220 A85-19691 Afterbody drag reduction by vortex generators [AIAA PAPER 85-0354] p 220 A85-19692 Structural components, design of tilt-rotor JVX near p 249 A85-20059 completion A formalism for the design problem of aircraft system universalization p 250 A85-20473 Radar cross section lectures --- Book p 289 A85-20915 Design of an airfoil leading edge stat using an inverse p 256 N85-16777 aerodynamic calculation method Integrated digital/electric aircraft concepts study [NASA-CR-3841] p 257 N85-16861 AIRCRAFT CONSTRUCTION MATERIALS The thermal response of aircraft cabin ceiling materials during a post-crash, external fuel-spill, fire scenario [AIAA PAPER 85-0395] p 241 A85-19721 Europeans using composites, ceramics for rotorcraft engine improvements p 263 A85-20061 Review of the origin of Japanese Industrial Standard p 280 A85-20545 Interpretation of fatique crack growth in aluminium alloys under programmed block loading p 281 A85-20790 Kevlar aramid fibers vs other fibers for reinforcement of composite structures p 282 A85-21392 Energy absorbing qualities of fiber reinforced plastic p 282 A85-21393 tubes Preliminary evaluation of an improved flammability test method for aircraft materials [FAA-CT-84-22] p 242 N85-16840 Composite structure repair, addendum [AGARD-R-716-ADD] p 284 N85-17057 p 284 N85-17058 Repair of composites AIRCRAFT CONTROL Speech recognition making progress - Direct voice input is a promising infant p 244 A85-19183 Maximum final energy chandelle [AIAA PAPER 85-0200] p 247 A85-19584 Investigations for the use of an active control in aircraft p 269 A85-19828 --- German thesis Advanced technology - The key to European competitiveness --- in Airbus industry p 200 A85-21680 A global technique for aircraft stability and control p 270 A85-21681 analveie Aircraft thrust control scheme for terrain following system [AD-D011387] p 255 N85-15711 Investigation of semiautomatic aircraft control processes employing time redundancy in on-board digital trajectory control computers p 270 N85-16048 Integrated digital/electric aircraft concepts study [NASA-CR-3841] p 257 N85-16861 Time series analysis of closed-loop pilot vehicle mamics p 271 N85-16876 dvnamics AIRCRAFT DESIGN p 246 A85-19184 From AV-8B to the ASTOVL Bomb rack technology - Keeping up with advanced p 246 A85-19274 weapons A longitudinal stability augmentation system for a tilt rotor aircraft [AIAA PAPER 85-0072] p 268 A85-19498 The design of airfoils at low Reynolds numbers

- p 209 A85-19500 [AIAA PAPER 85-0074] A new iterative matrix solution procedure for three-dimensional panel methods
- [AIAA PAPER 85-0176] p 213 A85-19568 The joined wing - An overview --- aircraft tandem wings
- in diamond configurations [AIAA PAPER 85-0274] p 247 A85-19626 The design and testing of several joined wing RPV's 0 248 A85-19627
- Effects of covering configurations on ultralight wing
- aerodynamics [AIAA PAPER 85-0277] p 217 A85-19629
- Potential flow calculations and preliminary wing design in support of an NLF variable sweep transition flight p 248 A85-19741
- [AIAA PAPER 85-0426] Computational aerodynamic design of the Gulfstream IV wing
- [AIAA PAPER 85-0427] p 223 A85-19742 Combat aircraft: Flight vehicles, power plants, and their
- maintenance Russian book p 199 A85-19812 Structural components, design of tilt-rotor JVX near completion p 249 A85-20059
 - Forward sweep The pros and cons p 250 A85-20146
 - A-3

AIRCRAFT DESIGN

Nonlinear simulation of flight along wind compensating

AIRCRAFT LANDING

AIRCRAFT ENGINES

Current problems in aviation science and technology p 199 A85-20451 Training and research CAD system of the Moscow Aviation Institute and experience in its use p 199 A85-20455 Design of load-bearing aircraft structures p 288 A85-20463 A formalism for the design problem of aircraft system p 250 A85-20473 universalization STOL technology for conventional flight enhancement p 250 A85-20875 [AIAA PAPER 84-2397] Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 p 200 A85-21456 Hardware design techniques --- systems integration for civil and military aircraft avionics n 244 A85-21459 Integrated communications - A designers view -- for p 245 A85-21462 p 258 A85-21555 civil and military aircraft avionics Pilot's Desk Flight Station Advanced technology The key to European competitiveness --- in Airbus industry p 200 A85-21680 A large-scale computer facility for computational p 301 A85-21791 aerodynamics Burbank's Blackbirds encompassing SR-71 reconnaissance aircraft and YA-12/12-A interceptors p 252 A85-22081 A85-22226 Trends in civil aircraft design p 200 Design of lifting symmetric supercritical airfoils p 233 A85-22228 Design of a STOL aircraft with jet assisted takeoff p 253 A85-22373 units United States Air force aircraft modification process: A system dynamics analysis p 200 N85-15659 [AD-A146954] Design study of technology requirements for high performance single-propeller-driven business airplanes p 235 N85-15692 [NASA-CR-3863] Missions and vehicle concepts for modern, propelled, lighter-than-air vehicles p 203 N85-16757 [NASA-TM-86672] Computer sizing of fighter aircraft [NASA-TM-86351] p 203 N85-16759 International aviation (selected articles) N85-16762 (AD-A148704) p 204 Designer on civil aircraft design trends in USSR p 256 N85-16768 Recent progress of development and understanding of p 236 N85-16772 high lift systems Design of an airfoil leading edge slat using an inverse aerodynamic calculation method p 256 N85-16777 Aerodynamic issues in the design of high-lift systems for transport aircraft p 256 N85-16780 Design studies of thick laminar flow airfoils for low speed flight employing turbulent boundary layer suction over the rear part p 257 N85-16786 Technology developments for laminar boundary layer control on subsonic transport aircraft p 237 N85-16787 Integrated digital/electric aircraft concepts study p 257 N85 16861 [NASA-CR-3841] Study of winglets applied to biplanes [NASA-TM-86350] p 258 N85-16862 A description of a logistically ideal aircraft [AD-A148425] N85-16866 p 258 The aircraft engine of the future p 268 N85-16875 rPNR-902261 Description of MBB computerized design techniques for p 303 N85-17194 **4**320 AIRCRAFT ENGINES Aircraft turbojet engine modeling using artificial intelligence techniques [AIAA PAPER 85-0253] p 263 A85-19616 Benefits and costs of powered engine simulation at low shoon [AIAA PAPER 85-0381] p 263 A85-19710 Combat aircraft: Flight vehicles, power plants, and their maintenance -- Russian book p 199 A85-19812 Army, NASA researching needs for future engine p 263 A85-20060 components Europeans using composites, ceramics for rotorcraft p 263 A85-20061 engine improvements Big wind at Tullahoma --- USAF's new aeropropulsion p 275 A85-20122 test facility Modern military engines. II p 264 A85-20822 p 264 A85-21420 Aeronautical gas turbines. III Predicted performance benefits of an adaptive digital engine control system of an F-15 airplane [NASA-TM-85916] p 265 N85-15729 Monitoring engine thermal stresses p 266 N85-15735 Accelerated Mission Endurance Testing (AMET) p 266 N85-15736 Design and test requirements for development of today's engines p 266 N85-15737

Contamination and distortion of steady flow field induced by discrete frequency in aircraft gas turbines [AD-A147092] p 294 N85-16073 The aircraft engine of the future [PNR-90226] p 268 N85-16875 Rolls-Royce experience with thermal barrier coatings ---in aircraft engines [PNR-90222] p 285 N85-17152 Flow measurement device p 298 N85-17369 [AD-D011432] An improved source model for aircraft interior noise studies [NASA-CR-172517] p 305 N85-17668 AIRCRAFT EQUIPMENT Icing tunnel tests of Electro-Impulse De-Icing of an engine inlet and high-speed wings [AIAA PAPER 85-0466] p 241 A85-20872 Voice command weapons launching system p 293 N85-15940 [AD-D011378] cost and benefits optimization model for fault-tolerant aircraft electronic systems [NASA-CR-166043] p 293 N85-15993 Managing recoverable aircraft components in the PPB and related processes: Executive summary [AD-A146806] p 308 N85-16667 Design for Tactical Avionics Maintainability p 201 [AGARD-CP-361] N85-16731 Objectives in studying the maintainability of aircraft systems p 202 N85-16732 Joint service design for testability program N85-16733 p 296 Study and realisation of a 3rd level mainte ince center based on ATE systems utilization p 202 N85-16735 A practical example of reducing life cycle costs and increased availability p 296 N85-16736 Director on institute's civil aviation projects p 204 N85-16764 Impact tests of automatic lap belt configurations AD-A148034] p 243 N85-16844 [AD-A148034] NASA three-laser airborne differential absorption lidar system electronics [NASA-CR-174293] p 298 N85-17353 AIRCRAFT FUEL SYSTEMS Aircraft wing fuel tank environmental simulator tests for evaluation of antimisting fuels [FAA-CT-84-15] p 283 N85-15920 Flow measurement device [AD-D011432] p 298 N85-17369 AIRCRAFT FUELS Distribution and storage of aviation turbine fuel for military operations in northern Australia p 283 N85-15921 [AD-A147180] AIRCRAFT GUIDANCE Helicopter Guidance and Control Systems for Battlefield Support (AGARD-CP-359) p 204 N85-16797 AIRCRAFT HAZARDS Atmospheric electricity hazards to aircraft operation [AIAA PAPER 85-0013] p 247 A85-19457 The Federal Aviation Administration's Engineering and Development Aircraft Icing Program [AIAA PAPER 85-0015] p 247 A85-19459 Lightning simulation facilities in the United States and Europe [AIAA PAPER 85-0093] p 273 A85-19515 The lightning threat to aerospace vehicles p 240 A85-19516 [AIAA PAPER 85-00941 Evaluation of aircraft interior panels under full-scale abin fire test conditions [AIAA PAPER 85-0393] n 240 A85-19719 Measurements of the response of transport aircraft ceiling panels to fuel pool fires [AIAA PAPER 85-0394] p 240 A85-19720 Detailed measurements of the flowfield in the vicinity of an airfoil with glaze ice [AIAA PAPER 85-0409] p 222 A85-19730 p 241 A85-20148 Wind shear - Taming the killer A bird strike handbook for base-level mana p 293 N85-16008 [AD-A147928] A study of the effects of triggered lightning [AD-A148296] p 300 N85-17494 AIRCRAFT INDUSTRY Advanced technology key The to European competitiveness --- in Airbus industry p 200 A85-21680 The embedded test (BIT): Impact the total cost o p 202 N85-16734 nniezoszon AIRCRAFT INSTRUMENTS Measurement of ice accretion using ultrasonic oulse-echo techniques [AIAA PAPER 85-0471] p 286 A85-19769 p 244 Aviation radar --- Russian book A85-19805 Mi-28 - The Soviets create Havoc p 250 A85-20147 Military avionics - Increasing integration at all levels

p 244 A85-20221

p 245 A85-21838 curved glidepaths The effect of changes in the angle of incidence in the event of a richochet at a float step [RAE-TRANS-2120] p 255 N85-15712 Development of a preliminary ALRS stabilized material pavement analysis system (SPAS) [AD-A147116] p 277 N85-15760 Aircraft barricade [AD-D011316] n 277 N85-15761 Testing solution for IL-76 braking system problem p 256 N85-16766 Airport activity statistics of certificated route air carriers [AD-A148472] p 243 N85-16846 Evaluation of arctic test af improved tritium radioluminescent lighting [AD-A148215] p 278 N85-16884 AIRCRAFT MAINTENANCE Performance evaluation of A-10 aircraft mainteance units and aircraft using constrained facet analysis [AD-A146955] p 201 N85-15660 Parametric estimates of propulsion system maintenance manhours [AD-A147120] p 201 N85-15662 A Q-GERT network simulation model for examining pipeline time in the Navy's J-52 intermediate level jet engine repair cycle [AD-A147269] p 201 N85-15663 Operational Loads Data [AGARD-CP-375] p 201 N85-15664 F-16 force management, yesterday, p 254 today and N85-15674 tomorrow Managing recoverable aircraft components in the PPB and related processes: Executive summary [AD-A146806] p 308 N85-16667 Design for Tactical Avionics Maintainability [AGARD-CP-361] p 201 N85-16731 Objectives in studying the maintainability of aircraft N85-16732 systems p 202 Joint service design for testability program p 296 N85-16733 Study and realisation of a 3rd level maintenance center based on ATE systems utilization p 202 N85-16735 A practical example of reducing life cycle costs and increased availability p 296 N85-16736 Avionics fault tree analysis and artifical intelligence for p 203 N85-16755 future aircraft maintenance International projects, other work of Aeroproyekt p 204 N85-16767 Institute Composite structure repair, addendum [AGARD-R-716-ADD] p 284 N85-17057 Composite repair of aircraft structures p 285 N85-17059 AIRCRAFT MANEUVERS Maximum final energy chandelle [AIAA PAPER 85-0200] p 247 A85-19584 A generalized stability criterion for nonlinear dynamic systems --- modeling aircraft roll maneuvers [AIAA PAPER 85-0202] p 300 A85-19586 Calculation of the exchange ratio for the Adaptive Maneuvering Logic program p 199 A85-19658 [AIAA PAPER 85-0311] Calculation of the minimum-time loop maneuver for jet p 269 A85-19876 aircraft Characteristic motions for simulation of post-stall manoeuvres and flight instabilities p 269 A85-21679 The use of local functionals to construct a circumvention maneuver in game problems of evasion p 302 A85-22374 Evaluation of operational loads to verify structural p 254 N85-15677 design AIRCRAFT MODELS Experimental methods for wind-tunnel flight-mechanics investigations using dynamically similar aircraft models -German thesis p 249 A85-19836 Selection of rational models in the optimal planning of aeromechanical experiments p 288 A85-20460 AIRCRAFT NOISE Interaction of a turbulent vortex with a lifting surface [AIAA PAPER 85-0004] p 206 A85-19452 The unambiguous in-flight determination of propeller rotational noise in aircraft with four-cycle combustion enaines p 304 A85-20650 An overview of helicopter's environmental p 241 A85-21643 considerations Acoustical guidelines for new heliports p 276 A85-21644 Field-incidence noise transmission loss of general aviation aircraft double-wall configurations p 304 A85-21842 A path model of aircraft noise annoyance A85-22071 p 304

NOISEMAP 4.4 computer program update, operator's manual addendum 1

p 302 N85-16503 [AD-A147091] Helicopter noise survey performed at Las Vegas, Nevada, 19-21 January, 1984

p 305 N85-16593 [AD-A147392] Noise measurement flight test: Data-anatyses

aerospatiale AS-355F TwinStar helicopter p 305 N85-16595 [AD-A147497] Helicopter model rotor-blade vortex interaction impulsive

noise: Scalability and parametric variations p 238 N85-16826 [NASA-TM-86007]

An improved source model for aircraft interior noise studies [NASA-CR-172517] p.305 N85-17668

Test of dispersal of turboiet aircraft departure tracks at washington National Airport (1983-84), volume 1 report

[AD-A148111] p 306 N85-17669 Noise measurement flight test for Boeing Vertol 234/CH 47-d helicopter: Data/analyses

p 306 N85-17670 [AD-A148172] Noise measurement flight test: Data-analyses

Aerospatiale AS 350D AStar helicopter p 306 N85-17672 [AD-A1484961 Noise measurement flight test: Data-analyses, Sikorsky

S-76A helicopter p 306 N85-17673 [AD-A148525]

Aeroacoustics at the DFVLR Brunswick Research Center: A survey on recent and current activities [DFVLR-MITT-84-14] p 306 N85 p 306 N85-17677

AIRCRAFT PARTS

A thermoplastic polyimidesulfone --- synthesis of processable and solvent resistant system

p 282 A85-21483 US Army helicopter operational flight loads

p 254 N85-15675

Helicopter data acquisition in WHL p 254 N85-15676 All-composite Airbus empennage p 284 N85-15931

Managing recoverable aircraft components in the PPB and related processes: Executive summary

p 308 N85-16667 [AD-A146806] The Air Force can improve its forecasts of aircraft spare parts requirements

p 308 N85-16682 [AD-A147911] Estimating wartime support resource requirements. Statistical and related policy issues

[AD-A147923] p 308 N85-16685 AIRCRAFT PERFORMANCE

Scaling laws for testing of high lift airfoils under heavy rainfall

p 216 A85-19617 [AIAA PAPER 85-0257] Measurements of water film characteristics on airfol surfaces from wind-tunnel tests with simulated heavy

rain [AIAA PAPER 85-0259] p 274 · A85-19618 Benefits and costs of powered engine simulation at low

[AIAA PAPER 85-0381] p 263 A85-19710 A85-20222 Boeing's rejuvenated twin jet p 250 Renegade 250 - Flight evaluation or boat ride? p 252 A85-22273

Speed benefits of tilt-rotor designs for LHX p 255 N85-15717 [NASA-CR-166437] Missions and vehicle concepts for modern, propelled.

lighter-than-air vehicles [NASA-TM-86672] AIRCRAFT PILOTS p 203 N85-16757

Judgment and discipline - Recipe for survival p 241 A85-21582

AIRCRAFT PRODUCTION

Design, fabrication and verification of composite flexbeam tail rotor for AH-64 Apache helicopter p 251 A85-21379 Tooling problems in the manufacture of AH-64 p 200 A85-21382 Composites Flexbeam Tail Rotor

Fabrication and assembly of composite rear fuselage p 200 A85-21394 (CRF) tooling and manufacturing for helicopter AIRCRAFT RELIABILITY Atmospheric electricity hazards to aircraft operation

[AIAA PAPER 85-0013] p 247 A85-19457 Loading characteristics of VTOL aircraft and their effect on the remaining life of the aircraft p 250 A85-20469

Nondestructive inspection: Improved capabilities of technicians p 295 N85-16196 [AD-A147388]

Airworthiness and flight characteristics test of the RC-12D Guardrail V

[AD-A148046] p 258 N85-16864 Preliminary airworthiness evaluation AH-1S (MC) helicopter with external fuel tanks installed p 258 N85-16865 [AD-A148091]

AIRCRAFT SAFETY

Evaluation of aircraft interior panels under full-scale abin fire test conditions

(AIAA PAPER 85-03931 p 240 A85-19719 The thermal response of aircraft cabin ceiling materials during a post-crash, external fuel-spill, fire scenario

[AIAA PAPER 85-03951 p 241 A85-19721 Full two-dimensional solutions transient of electrothermal aircraft blade deicing

p 248 A85-19734 (ALAA PAPER 85-04131 Advanced composites - Designed to survive - helicopter safety in modern battlefield p 251 A85-21387

A bird strike handbook for base-level managers p 293 N85-16008 [AD-A147928]

AIRCRAFT STABILITY

Theory of wing rock [AIAA PAPER 85-0199]

p 268 A85-19583 Transient motion of hypersonic vehicles including time history effects [AIAA PAPER 85-0201]

p 268 A85-19585 A generalized stability criterion for nonlinear dynamic systems --- modeling aircraft roll maneuvers

[AIAA PAPER 85-0202] p 300 A85-19586 Characteristic motions for simulation of post-stall manoeuvres and flight instabilities p 269 A85-21679 A global technique for aircraft stability and control

p 270 A85-21681 The development of a finite element model of an aircraft

vertical stabilizer for vibration analysis p 290 A85-21683

Coupled helicopter rotor/body aeromechanical stability comparison of theoretical and experimental results

p 252 A85-21847 AIRCRAFT STRUCTURES

Measurements of the response of transport aircraft ceiling panels to fuel pool fires

[AIAA PAPER 85-0394] p 240 A85-19720 Current problems in aviation science and technology

p 199 A85-20451 Determination of the optimal parameters of aircraft structural elements in the form of sandwich plates and shallow shells with a honeycomb filler

p 287 A85-20452 Theory of vibration conduction as a method for

calculating the vibration of complex structures p 287 A85-20454 Current problems in the theory of plates and shells in

p 287 A85-20459 aircraft Design of load-bearing aircraft structures

p 288 A85-20463 Composite structures, Proceedings of the National

Specialists Meeting, Philadelphia, PA, March 23-25, p 281 A85-21376 1983

Sikorsky composite rotor hub development p 251 A85-21381

Tooling problems in the manufacture of AH-64 p 200 A85-21382 Composites Flexbeam Tail Rotor

Advanced-composite joints and fittings for primary p 290 A85-21385 structural components

Crashworthiness of helicopter composite structures p 251 A85-21386

Advanced composites - Designed to survive --- helicopter safety in modern battlefield p 251 A85-21387 Flexible matrix composites applied to bearingless rotor

p 281 A85-21389 systems Utilization of analytical equipment in design and process

problems solution and failure analysis of composites

p 281 A85-21390 Optimization of airplane wing structures under landing

p 252 A85-22005 loads Universal matrices to obtain thermal load vectors for

the family of anisotropic plane triangular finite elements p 291 A85-22232

- **Operational Loads Data**
- [AGARD-CP-375] p 201 N85-15664 Operational loads data evaluation for individual aircraft fatigue monitoring p 253 N85-15669 Structural flight load measurement demonstration of
- structural integrity p 254 N85-15670 Advanced fatigue monitoring on service aircraft

p 292 N85-15671 F-16 force management, yesterday, today and p 254 N85-15674 tomorrow

US Army helicopter operational flight loads p 254 N85-15675

Evaluation of operational loads to verify structural design p 254 N85-15677

Tomado: Structural Usage Monitoring System p 292 N85-15680 (SUMS) All-composite Airbus empennage p 284 N85-15931

The influence of fastener flexibility on load transfer and fatigue life predictions for multirow bolted and riveted joints - aircraft structures

[LBF-FB-172/84] p 296 N85-16219 Composite structure repair, addendum

[AGARD-R-716-ADD] p 284 N85-17057 Composite repair of aircraft structures

p 285 N85-17059 Flexible manufacturing system for the production of ircraft parts

AIRFOILS

[BLL-PNR-90237-(899.3153)] n 297 N85-17159 AIRCRAFT SURVIVABILITY

Advanced composites - Designed to survive - helicopter satety in modern battlefield p 251 A85-21387

F-16 force management, yesterday, today and pmorrow p 254 N85-15674 tomorrow AIRCRAFT WAKES Vortex research facility improvements and preliminary

density stratification effects on vortex wakes [AIAA PAPER 85-0050] p 209 A85-19482

Measurements of separating boundary layer and wake of an airfoil using laser Doppler velocimetry

[AIAA PAPER 85-0181] p 214 A85-19572 Numerical solution of the full-potential equation for rotors

and oblique wings using a new wake model (AIAA PAPER 85-0268) p 216 A85-19621 Experimental results for Reynolds number effects on

p 232 A85-21849 trailing vortices Recent advances in computational methods to solve

the high-lift multi-component airfoil problem p 236 N85-16774

AIRFOIL PROFILES

[AIAA PAPER 85-0167]

[AIAA PAPER 85-0171]

[AIAA PAPER 85-0203]

[AIAA PAPER 85-0205]

AIAA PAPER 85-02061

[AIAA PAPER 85-0207]

AIAA PAPER 85-02081

[AIAA PAPER 85-0293]

[AIAA PAPER 85-0410]

[AIAA PAPER 85-0446]

flows --- German thesis

[AIAA PAPER 85-0018]

[AIAA PAPER 85-0109]

[NASA-CR-172338-ADD]

Comparison with calculations

issuing from its undersurface

[AIAA PAPER 85-0019]

evaluation of iced airfoil performance

profiles on airfoils

Navier-Stokes solver

nassing vortex

airfoils

oradients

75 to .90

schemes

toet races

airfoils

traffie

AIRFOILS

Noise of an airfoil in a flow

- [ONERA, TP NO. 1984-155] p 303 A85-19269 An improved version of the LTRAN2 for high frequency p 205 A85-19401 domain
- An analysis of the flow past an S-shaped rotor by discrete vortex model n 206 A85-19405
- Calculation of compressible potential flow about multielement airfoils using a finite field-panel approach
- TAIAA PAPER 85-00381 n 207 A85-19473 Computational study of circulation control with suction

p 208 A85-19477 [AIAA PAPER 85-0042]

The design of airfoils at low Revnolds numbers p 209 A85-19500 [AIAA PAPER 85-0074]

Flows over low Reynolds number airfoils - Compressible Navier-Stokes numerical solutions [AIAA PAPER 85-0107] p 210 A85-19523

Numerical computation of viscous flowfields about multiple component airfoils

Analysis of circulation control airfoils using an implicit

Unsteady aerodynamics of an airfoil encountering a

Prediction of subsonic/transonic separated flow about

A class of airfoils having finite trailing edge pressure

Supercritical airfoil drag reduction by passive shock

A Fourier Transform method for calculating velocity

Multigrid solution of the Euler equations using implicit

Progress in development of a Navier-Stokes solver for

Trapping of free vortex by airfoils with surface suction

A subdomain finite element method for solving the

A new approach to some hybrid aerodynamic problems

Euler computations of AGARD Working Group 07 airfoil

Finite element solutions of Euler equations for lifting

[AIAA PAPER 85-0294] p 230 A85-20864 Effects of aircraft and flight parameters on

energy-efficient profile descents in time-based metered

Detailed study of the flow around a multi-element airfoil.

Aerodynamics of an airfoil in ground effect with a jet

conservative full potential equation for transonic profile

of airfoil cascades on a general streamsheet of revolution.

Navier-Stokes computations for exotic airfoils

wave/boundary layer control in the Mach number range

p 213 A85-19563

p 213 A85-19565

p 214 A85-19587

p 215 A85-19589

p 215 A85-19590

p 215 A85-19591

p 215 A85-19592

p 218 A85-19643

p 222 A85-19731

p 224 A85-19755

p 227 A85-19854

p 228 A85-20229

p 229 A85-20851

p 230 A85-20855

p 245 N85-15706

p 236 N85-16775

p 207 A85-19461

A-5

AIRFRAME MATERIALS

An experimental investigation of an airfoil undergoing arge amplitude pitching motions

[AIAA PAPER 85-00391 p 207 A85-19474 The interaction and merging of two turbulent line vortices

TAIAA PAPER 85-00461 p 208 A85-19480 Interrelated effects of pitch rate and pivot point on airfoil dvnamic stall

p 212 A85-19541 [AIAA PAPER 85-0130] Computation of unsteady shock-induced vortex separation

p 214 A85-19573 [AIAA PAPER 85-0183] Studies of condensation effects on airfoil testing in a transonic cryogenic tunnel

[AIAA PAPER 85-0229] p 274 A85-19603 Scaling laws for testing of high lift airfoils under heavy rainfall

y p 216 A85-19617 effect of surface [AIAA PAPER 85-0257] aerodynamic The characteristics on a laminar flow airfoil in simulated heavy rain

[AIAA PAPER 85-0260] p 247 A85-19619 A comparison between theoretical and experimental flow fields of an airfoil with deflected spoiler

[AIAA PAPER 85-0269] p 216 A85-19622 Application of continuous vorticity panels to general unsteady two-dimensional lifting flows

p 217 A85-19633 [AIAA PAPER 85-0282] Euler calculations for multielement airfoils using Cartesian orids

[AIAA PAPER 85-0291] p 218 A85-19641 Detailed measurements of the flowfield in the vicinity of an airfoil with glaze ice

[AIAA PAPER 85-0409] p 222 A85-19730 TRO-2D - A code for rational transonic aerodynamic optimization

[AIAA PAPER 85-0425] p 223 A85-19740 Visualization of the spanwise vortex structure in the starting flow behind an airfoil

[AIAA PAPER 85-04471 p 224 A85-19756 A summary of NASA's research on the fluid ice protection

system [AIAA PAPER 85-0467] p 241 A85-19768 A comparative study between an implicit and explicit

algorithm for transonic airfoils [AIAA PAPER 85-0480] p 225 A85-19777 Artificial dissipation models for the Euler equations AIAA PAPER 85-0438] p 231 A85-20870

[AIAA PAPER 85-0438] Evaluation of a stalled airfoil analysis program p 231 A85-21848

Scaling of airfoil self-noise using measured flow parameters p 304 A85-21858

Unsteady pressure measurements on a biconvex airfoil in a transonic oscillating cascade [NASA-TM-86914] p 234 N85-15689

Aircraft wing fuel tank environmental simulator tests for evaluation of antimisting fuels

[FAA-CT-84-15] p 283 N85-15920 Some important problems in unsteady boundary layers including separation. 1: Nature of singularity on oscillating airfaile

[AD-A147897] p 294 N85-16087 High temperature thermocouple and heat flux gauge using a unique thin film-hardware hot juncture [NASA-TM-86898] p 295

VASA-TM-86898] p 295 N85-16096 Analysis of the surface load and radiated sound of a vibrating airfoil with application to the experiment of Brooks [NASA-CR-3864] p 305 N85-16590

Recent advances in computational methods to solve the high-lift multi-component airfoil problem p 236 N85-16774

Inviscid compressible flow past a multi-element aerofoil p 236 N85-16776

Turbulent bubbles behind airfoils and wings at high angle of attack p 296 N85-16779 Design studies of thick laminar flow airfoils for low speed

flight employing turbulent boundary layer suction over the rear part p 257 N85-16786

Pneumatic turbulators: A device for drag reduction at p 257 N85-16791 Reynolds numbers below 5 million Results of S5 CH tests with an ARL (Aerospace

Research Laboratory) cascade p 278 N85-16882 [NASA-TM-77510] AIRFRAME MATERIALS

The all-composite airframes p 252 A85-21397 AIRFRAMES

Structural analysis and testing of ACAP subcomponents Advanced Composite Airframe Program

p 251 A85-21384 AIRPORT PLANNING Acoustical guidelines for new heliports

p 276 A85-21644 Report from the United States of America - legal procedures for airport construction or expansion p 307 A85-21942

Report from the United Kingdom -- legal procedures for airport construction or expansion p 307 A85-21943

Construction and extension of airports - Legal procedure p 307 A85-21944 and practice in Canada Creation and extension of airports - Procedures and

p 307 A85-21945 practice Report from Sweden --- legal procedures for airport construction or expansion p 307 A85-21946

Construction and extension of airports - National report p 308 A85-21947 on Switzerland

Report from Japan --- legal procedures for airport construction or expansion p 308 A85-21948 National report - The Federal Republic of Germany ---

legal procedures for airport construction or expansion p 308 A85-21949

AIRPORTS

Status of warm fog dispersal research [AIAA PAPER 85-0010]

p 272 A85-19456 Automated visibility measurements for airports p 274 A85-19577 [AIAA PAPER 85-0191]

FAA (Federal Aviation Administration) statistical handbook of aviation, calendar year 1983 [AD-A148171] p 203 N85-16760

International projects, other work of Aeroproyekt Institute p 204 N85-16767 Institute Activities report on West German civil airports. Part 1:

Text [ISBN-3-87977-055-7-PT-1] p 279 N85-16887

Activities report for the West German Civil Airports. Part 2: Tables [ISBN-3-87977-055-7-PT-2] p 279 N85-16888

Impact of aircraft emissions on air quality in the vicinity of airports. Volume 3: Air quality and emission modeling needs [AD-A147951]

p 299 N85-17435 Impact of aircraft emissions on air quality in the vicinity of airports. Volume 4. Nitrogen dioxide and hydrocarbons

[AD-A148253] p 299 N85-17436 Test of dispersal of turbojet aircraft departure tracks at washington National Airport (1983-84), volume 1 report

[AD-A148111] p 306 N85-17669 AIRSHIPS

Missions and vehicle concepts for modern, propelled, lighter-than-air vehicles

[NASA-TM-86672] p 203 N85-16757 AIRSPACE

National airspace review: Airport radar service area operational confirmation report

p 245 N85-15707 [DOT/FAA/AT-84/2] National airspace review enhancement plan, revision 3 p 246 N85-16852 National Airspace Review p 246 N85-16855

[AD-A147768] AIRSPEED

Recent methods for calibrating the anemometry of p 260 N85-16809 helicopters at low speeds ALGORITHMS

Accelerated convergence for incompressible flow calculations

[AIAA PAPER 85-0058] p 209 A85-19489 A comparative study between an implicit and explicit algorithm for transonic airfoils

(AIAA PAPER 85-0480) p 225 A85-19777 Application of an adaptive blade control algorithm to a

p 269 A85-20143 gust alleviation system Recent improvements in efficiency, accuracy, and convergence for implicit approximate factorization algorithms --- computational fluid dynamics

[AIAA PAPER 85-0360] p 230 A85-20868 Development of asymptotic algorithms in the Polet package of applications programs --- for sea surface effect p 233 A85-22366 vehicle design

cost and benefits optimization model for fault-tolerant aircraft electronic systems [NASA-CR-166043]

VASA-CR-166043] p 293 N85-15993 Research on optimal control, stabilization and computational algorithms for aerospace applications [NASA-CR-174318] p 303 N85-17603

ALL-WEATHER LANDING SYSTEMS

Development and flight test of a helicopter compact, portable, precision landing system concept p 261 N85-16821

ALTIMETERS Theoretical and experimental analyses of laser altimeters for barometric measurements over the ocean p 298 N85-17351

A method for determining mesoscale dynamic topography (AD-D011412) p 300 N85-17506

ALTITUDE

Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) p 276 N85-15757 [NASA-TM-86919]

[AIAA PAPER 85-0071] p 273 A85-19497

ALTITUDE SIMULATION

tructures

Laminar boundary layer stability experiments on a cone

Experiences with the use of a side-strut model support system for high angles of attack in the Trinsonik wind tunnel

[DFVLR-MITT-84-09] p 277 N85-15763 Effect of aerodynamic and angle-of-attack uncertainties on the May 1979 entry flight control system of the Space Shuttle from Mach 8 to 1.5

of a laminar circular jet under bi-modal excitation

An experimental investigation of the mixing of co-annular

[AIAA PAPER 85-0186] p 230 A85-20862

rbine performance losses

Field, Antarctica

near-field Characteristics and applications --- German p 287 A85-19837 thesis

the NVIS mode p 297 N85-16807

evaluation of antimisting fuels

p 245 N85-16802 system

glide-slope approach for wake-vortex avoidance [NASA-TP-2386] p 261 N85-16869

Nonlinear simulation of flight along wind compensating

Evaluation of arct	ic test	of	impro	ved	tritium
radioluminescent lightin	9		-		
[AD-A148215]			p 278	N85	-16884

The Altitude Wind Tunnel (AWT) - A unique facility for

propulsion system and adverse weather testing [AIAA PAPER 85-0314] p 275 A85-19661 [AIAA PAPER 85-0314] Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) [AIAA PAPER 85-0379] p 275 A85-19709 Analytical modeling of circuit aerodynamics in the new NASA Lewis wind tunnel [NASA-TM-86912] p 234 N85-15688 The NASA Altitude Wind Tunnel (AWT): Its role in advanced icing research and development [NASA-TM-86920] p 276 N85-15758 **ALUMINUM ALLOYS** Review of the origin of Japanese Industrial Standard p 280 A85-20545 Fatigue crack growth behavior of 7XXX aluminum alloys under simple variable amplitude loading p 280 A85-20759 Interpretation of fatigue crack growth in atuminium alloys under programmed block loading p 281 A85-20790 Engineering property comparisons of PM and IM aluminum alloy forgings [AD-B0881466L] p 298 N85-17398 ALUMINUM COATINGS Microstructural development of protective Al2O3 scales p 283 A85-21650 ALUMINUM OXIDES Microstructural development of protective AI2O3 scales p 283 A85-21650 AMPHIBIOUS AIRCRAFT Renegade 250 - Flight evaluation or boat ride? p 252 A85-22273 ANECHOIC CHAMBERS A study of the flow recirculation problems within an anechoic hover chamber ANGLE OF ATTACK Flow visualization of high angle of attack vortex wake p 286 A85-19520 [AIAA PAPER 85-0102] at Mach 8. III - Sharp cone at angle of attack [AIAA PAPER 85-0492] p 226 A85-19787 TMK [NASA-TP-2365] p 280 N85-15778 ANGLES (GEOMETRY) The effect of changes in the angle of incidence in the event of a richochet at a float step [RAE-TRANS-2120] p 255 N85-15712 ANNULAR FLOW The effect of phase-difference on the spreading rate p 208 A85-19479 [AIAA PAPER 85-0045] swirling flows An improved computer model for prediction of axial gas [NASA-CR-174246] p 265 N85-15724 ANTARCTIC REGIONS The visibility climatology of McMurdo Sound-Williams [AD-A148108] p 300 N85-17492 ANTENNA RADIATION PATTERNS Reflector antennas with directional effect in the Tactical HF communication for military helicopters using ANTIMISTING FUELS Aircraft wing fuel tank environmental simulator tests for [FAA-CT-84-15] p 283 N85-15920 ANTISUBMARINE WARFARE Development of a Helicopter integrated navigation APPROACH A cockpit-display concept for executing a multiple APPROACH CONTROL p 245 A85-21838 curved glidepaths APPROACH INDICATORS

APPROXIMATION

- A fast algorithm for solving the conservative transonic S1 full potential equation employing non-orthogonal curvilinear coordinates and non-orthogonal velocity components p 228 A85-20239
- The full-approximation method in the theory of transonic p 233 A85-22367 flows Approximate solution of a nonlinear problem of flow past
- a thin airfoil profile near a support surface p 233 A85-22368
- Multivariable flight control with time-scale separation [NASA-CR-174320] p 268 N85-16873
- **ARCHITECTURE (COMPUTERS)** Some problems in the development of CAD systems for design of minicomputer digital components
- p 200 A85-20466
- Trends in digital flight control systems p 269 A85-21465 Evolution toward a multi-bus architecture for Army
- p 260 N85-16812 helicopter avionic systems ARCTIC REGIONS
- p 236 N85-16240 Parachute expedition to Arctic ARMED FORCES (UNITED STATES)
- The Air Force stock fund and aircraft availability
- [AD-A148653] p 203 N85-16761 Utilization of Increased Airlift Capability (UIAC) study [AD-A148669] p 243 N85-16847
- ARRAYS Arrays for minimum wave drag of bodies of revolution [AIAA PAPER 85-0449] p 249 A85-19758 ARRESTING GEAR
- Aircraft barricade [AD-D011316] p 277 N85-15761 ARROW WINGS
- Subsonic pressure distributions near a wing-fin juncture on a supersonic arrow-wing configuration wing-mounted vertical fins with
- [AIAA PAPER 85-0276] p 217 A85-19628 ARTIFICIAL INTELLIGENCE
- Aircraft turbojet engine modeling using artificial intelligence techniques [AIAA PAPER 85-0253] p 263 A85-19616
- Design of aerodynamic bodies using artificial intelligence/expert system technique AIAA PAPER 85-01121 n 301 A85-20856
- Avionics fault tree analysis and artifical intelligence for future aircraft maintenance p 203 N85-16755 ASPECT RATIO
- Aerodynamics of an aspect ratio 8 wing at low Reynolds numbers
- AIAA PAPER 85-02781 p 217 A85-19630 ASYMPTOTIC METHODS
- Ill-posed problems in perturbation theory (Asymptotic p 233 A85-22364 methods of mechanics) Development of asymptotic algorithms in the Polet package of applications programs --- for sea surface effect
- p 233 A85-22366 vehicle design ATMOSPHERIC ATTENUATION Atmospheric propagation losses for long-range airborne
- radar systems analysis [AIAA PAPER 85-0267] p 244 A85-19620 ATMOSPHERIC CHEMISTRY
- Atmospheric photochemical modeling of turbine engine fuels. Phase 1: Experimental studies. Volume 2: Environmental chamber data tabulations
- p 300 N85-17470 FAD-A1477861 ATMOSPHERIC ELECTRICITY
- Atmospheric electricity hazards to aircraft operation [AIAA PAPER 85-0013] p 247 A85-19457 A study of the effects of triggered lightning [AD-A148296] p 300 N85-17494
- ATMOSPHERIC ENTRY A three-dimensional Navier-Stokes/Euler code for
- blunt-body flow computations [AIAA PAPER 85-0361] p 220 A85-19696
- ATMOSPHERIC HEATING
- Application of axisymmetric analogue for calculating heating in three-dimensional flows [AIAA PAPER 85-0245] p 216 A85-19611
- ATMOSPHERIC MODELS
- Atmospheric photochemical modeling of turbine engine fuels. Phase 1: Experimental studies. Volume 2: Environmental chamber data tabulations
- [AD-A147786] p 300 N85-17470 ATMOSPHERIC MOISTURE
- Three-dimensional airflow and hydrometeor trajectory calculation with applications
- [AIAA PAPER 85-0412] p 222 A85-19733 Icing conditions encountered by a research aircraft p 299 A85-21141
- ATMOSPHERIC PRESSURE
- Theoretical and experimental analyses of laser altimeters for barometric measurements over the ocean p 298 N85-17351

ATTACKING (ASSAULTING)

- NyKINM, a further development of KINM 22 -- simulation of a robot attack on an aircraft [FOA-C-20559-D8(E3)]
- p 256 N85-15720 ATTITUDE CONTROL
- The development of digital attitude controllers Its past, present and future p 302 A85-22449 AUGMENTATION
- An update of the Canada/USA augmentor-wing p 257 N85-16781 project
- AUTOMATIC CONTROL Investigation of semiautomatic aircraft control processes employing time redundancy in on-board digital trajectory p 270 N85-16048 control computers The effects of manufacturing automation on the surge
- and mobilization capabilities of the gas turbine engine industry [AD-A147295] p 297 N85-17162
- AUTOMATIC FLIGHT CONTROL Flight test of the Open Loop Gust Alleviation (OLGA) system
- [BMFT-FB-W-84-038] p 271 N85-16881 AUTOMATIC PILOTS
- A digital piloting system for the combat helicopter p 260 N85-16806
- AUTOMATIC TEST EQUIPMENT Design for Tactical Avionics Maintainability
- [AGARD-CP-361] p 201 N85-16731 Study and realisation of a 3rd level maintenance center p 202 based on ATE systems utilization N85-16735 ATE user's view on design for maintainability p 202 N85-16737 p 202 N85-16739 Built-in-test for first line testing
- Functional built-in-test in a pipelined image processor p 202 N85-16740 AUTOMOBILE ENGINES
- FRG ceramic engine components (PET) p 297 N85-17193
- AUTOMOBILE FUELS Some characteristics of automotive gasolines and their performance in a light aircraft engine
- [FAA-CT-84-12] p 283 N85-15919 AUTOREGRESSIVE PROCESSES
- Time series analysis of closed-loop pilot vehicle ynamics p 271 N85-16876 N85-16876 dynamics AVAILABILITY
- A practical example of reducing life cycle costs and p 296 N85-16736 increased availability AVIONICS
- Lightning simulation facilities in the United States and Europe
- p 273 A85-19515 [AIAA PAPER 85-0093] Military avionics - Increasing integration at all levels
- p 244 A85-20221 Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 p 200 A85-21456
- ondon, England, April 3, 4, 1904 p 200 noo 2112 Software design methods --- for civil and military aircraft vinnics systems p 301 A85-21457 avionics systems A design methodology for integrated avionic systems p 301 A85-21458
- Hardware design techniques --- systems integration for civil and military aircraft avionics p 244 A85-21459 Packaging and interconnection for avionics
- p 290 A85-21460 p 245 A85-21461 Integrated navigation Integrated communications - A designers view --- for
- p 245 A85-21462 civil and military aircraft avionics Trends in digital engine control - Integration of propulsion
- control with flight control and avionic systems in future military and commercial aircraft p 264 A85-21466 The impact of integrated systems - The helicopter
- p 252 A85-21467 designer's viewpoint Equipment for preflight test of an Countermeasures (ECM) avionic system Electronic
- p 293 N85-15949 Design for Tactical Avionics Maintainability
- p 201 N85-16731 [AGARD-CP-361] Objectives in studying the maintainability of aircraft
- p 202 N85-16732 systems Joint service design for testability program
- p 296 N85-16733 The embedded test (BIT): Impact on the total cost of
- p 202 N85-16734 possession Study and realisation of a 3rd level maintenance center
- based on ATE systems utilization p 202 N85-16735 ATE user's view on design for maintainability
- o 202 N85-16737 p 202 N85-16739 Built-in-test for first line testing Maintainability: An ILS effort to manipulate LCC
- p 202 N85-16743 Documentation and separate test program development
- is most important for test/maintenance p 203 N85-16745
- Effective life cycle software support: A study in discipline and versatility p 302 N85-16746

The effect on software design of testing by symbolic ecution p 303 N85-16750 execution. Reliable software design for avionics and space p 303 N85-16751 applications A weapon system design approach to diagnostics p 203 N85-16752 Avionics fault tree analysis and artifical intelligence for future aircraft maintenance p 203 N85-16755 Automatic briefing and mission management systems battlefield support p 259 N85-16799 Development of a Helicopter integrated navigation p 245 N85-16802 system Standard Attitude Heading Reference System (SAHRS) n 246 N85-16804 full scale development program Evolution toward a multi-bus architecture for Army p 260 N85-16812 helicopter avionic systems Integration of sensor fusion in advanced heliconter cockpit design p 260 N85-16813 Development, production and testing of central control and display unit for helicopters [BMFT-FB-W-84-039] p 261 N85-16871 Life cycle cost model for very high speed integrated circuits [AD-A147798] p 297 N85-17298 **AXIAL FLOW** Development of a Navier-Stokes rotor and stator analysis [AD-A146967] AXIAL FLOW TURBINES p 294 N85-16070 Precalculation of rotating stall in multistage axial p 287 A85-19832 compressors --- German thesis procedure for the optimization of the aerothermodynamic design multistage of axia p 227 A85-19851 compressors --- German thesis AXIAL LOADS On the excitations due to the periodic structure of p 288 A85-20800 turbomachines Life prediction at high temperature under multiaxial p 267 N85-15745 AXISYMMETRIC BODIES Optimized discrete-singularity representation of axisymmetric bodies --- for potential flo [AIAA PAPER 85-0284] p 218 A85-19635 AXISYMMETRIC FLOW Euler solution of axisymmetric flows about bodies of revolution using a multigrid method [AIAA PAPER 85-0017] p 206 A85-19460

- Computation of recirculating compressible flow in axisymmetric deometries
- [AIAA PAPER 85-0185] p 286 A85-19575 A simple analytical method for predicting axisymmetric turbulent jet flowfields in a freestream
- [AIAA PAPER 85-0251] p 216 A85-19614 Optimized discrete-singularity repr axisymmetric bodies --- for potential flow representation of
- p 218 A85-19635 [AIAA PAPER 85-0284] Navier-Stokes computations of axisymmetric transonic flows with a two-equation model of turbulence
- p 221 A85-19705 p 227 A85-20074 [AIAA PAPER 85-0373] Survey on jet instability theory Analytical modeling of circuit aerodynamics in the new NASA Lewis wind tunnel
 - p 234 N85-15688

В

BACKWARD FACING STEPS

[NASA-TM-86912]

- A study of compressible turbulent free shear layers using laser Doppler velocimetry
- [AIAA PAPER 85-0177] p 213 A85-19569 A study of the effects of numerical dissipation on the calculation of supersonic separated flows
- [AIAA PAPER 85-0301] p 219 A85-19650 BAFFLES
- An experimental study of sound attenuation characteristics in circular ducts with lined radial baffles p 304 A85-19505 [AIAA PAPER 85-0079]
- BALLISTIC MISSILES Aerodynamic studies linked to the development of deployable nozzles --- for upper stage ballistic missiles [ONERA, TP NO. 1984-149] p 205 A85-19263 p 205 A85-19263
- BANDWIDTH Multiveriable flight control with time-scale separation [NASA-CR-174320] p 268 N85-16873 p 268 N85-16873
- BARRIER LAYERS Rolls-Royce experience with thermal barrier coatings --in aircraft engines
- [PNR-90222] p 285 N85-17152 BEARINGLESS ROTORS
- Aeroelastic characteristics of the AH-64 bearingless tai p 250 A85-20142 rotor

BEARINGLESS ROTORS

p 302 N85-16747

p 302 N85-16749

Experience in using on-aircraft software for testing

Investigating version dependence in fault-tolerant

integrated systems

software

BEARINGS

Flexible matrix composites applied to bearingless rotor p 281 A85-21389 systems . BEARINGS

- Stability of squeeze film damped multi-mass flexible rotor bearing systems
- p 289 A85-21296 [ASME PAPER 84-TRIB-45] Improvement of the corrosion resistance of turbine engine bearings

p 265 N85-15731 [AD-A147430] BENDING MOMENTS

- Helicopter active control with rotor blades relaxation p 270 N85-16819 BIBLIOGRAPHIES
- Circulation control: A bibliography of DTNSRDC research and selected outside references: Update

p 201 N85-15661 [AD-A1469661 Loads and Aeroelasticity Division research and technology accomplishments for FY 1984 and plans for FY 1985

- [NASA-TM-86356] p 234 N85-15691 Aeronautical Engineering: A continuing bibliography with indexes (supplement 182)
- [NASA-SP-7037(182)] p 203 N85-16758 Software test handbook: Software test guidebook, volume 2
- [AD-A147289] p 303 N85-17578 Scientific and technical information output of the Langley Research Center for calendar year 1984 [NASA-TM-86336] p 309 N85-17740
- BIODYNAMICS
- Biodynamic resistant control stick [AD-D011380] p 259 N85-15721

BIPLANES Study of winglets applied to biplanes

- [AIAA PAPER 85-0279] p 217 A85-19631
- Study of winglets applied to biplanes [NASA-TM-86350] p p 258 N85-16862 **BIRD-AIRCRAFT COLLISIONS**
- A bird strike handbook for base-level managers p 293 N85-16008 [AD-A147928]
- BLADE SLAP NOISE An experimental investigation of blade-vortex interaction
- at normal incidence [AIAA PAPER 85-0003] p 206 A85-19451 Interaction of a turbulent vortex with a lifting surface
- p 206 A85-19452 [AIAA PAPER 85-0004] BLADE TIPS
- Interaction of a turbulent vortex with a lifting surface p 206 A85-19452 [AIAA PAPER 85-0004] Metallurgical and mechanical phenomena due to rubbing

of titanium against sintered powder Nichrome p 291 A85-22281

BLOWDOWN WIND TUNNELS

Experiences with the use of a side-strut model support system for high angles of attack in the Trinsonik wind tunnel тмк

[DFVLR-MITT-84-09]	p 277	N85-15763
BLOWING		

- Influence of blowing rate and injection angle on the performance of a film-cooled blade p 265 A85-22231 Drag reduction due to boundary-layer control by p 237 N85-16785 combined blowing and suction BLUNT BODIES
- Regarding parametric investigations of slender cone nose bluntness effects [AIAA PAPER 85-0349]

p 220 A85-19688 Passive control effects on flow separation around a protuberance at high subsonic speed --- for optical propagation quality enhancement to and from airborne platforms

[AIAA PAPER 85-0351] p 220 A85-19690 A three-dimensional Navier-Stokes/Euler code for blunt-body flow computations

- [AIAA PAPER 85-0361] p 220 A85-19696 BO-105 HELICOPTER
- Flight tests with a new helicopter Force Feel System p 257 N85-16818 (FFS)

Flight research on visusl aids and navigation equipment for helicopter low-level flight at night

p 261 N85-16820 BODIES OF REVOLUTION

- Euler solution of axisymmetric flows about bodies of revolution using a multigrid method [AIAA PAPER 85-0017] p 206 A85-19460
- Arrays for minimum wave drag of bodies of revolution p 249 A85-19758 [AIAA PAPER 85-0449]

A new approach to some hybrid aerodynamic problems of airfoil cascades on a general streamsheet of revolution. p 228 A85-20229

Drag prediction for projectiles and finned bodies in essible flow [AIAA PAPER 85-0104] p 230 A85-20854

An extremum problem concerning the shape of a body of revolution in supersonic gas flow p 234 A85-22371 BODY-WING AND TAIL CONFIGURATIONS

- Three-dimensional Euler solutions with grid embedding [AIAA PAPER 85-0121] p 211 A85-19532 Theoretical study of boundary-layer control
- p 237 N85-16784 Tail behaviour for suprema of empirical processes [AD-A147629] p 303 N85-17613
- BODY-WING CONFIGURATIONS Turbulent flow around a wing-fuselage type juncture
- p 208 A85-19475 [AIAA PAPER 85-0040] Numerical solution of the Euler equations for high-speed, blended wing-body configurations
- [AIAA PAPER 85-0123] p 211 A85-19534 Aerodynamic prediction of eliptically-shaped missile configurations using component build-up methodology [AIAA PAPER 85-0271] p 216 A85-19624
- Crossflow drag of finite-length rectangular wing-bodies [AIAA PAPER 85-0451] p 224 A85-19760 Drag reduction due to boundary-layer control by
- p 237 N85-16785 combined blowing and suction BOEING 737 AIRCRAFT p 250 A85-20222
- Boeing's rejuvenated twin let BOILING
- Advances in heat transfer. Volume 16 p 288 A85-20501
- BOMBING EQUIPMENT
- Bomb rack technology Keeping up with advanced p 246 A85-19274 weapons BOOMS (EQUIPMENT)
- F-8 refueling boom ground vibration test [NASA-TM-84914] p 253
- p 255 N85-15713 BOUNDARY LAYER CONTROL
- Supercritical airfoil drag reduction by passive shock wave/boundary layer control in the Mach number range .75 to .90
- [AIAA PAPER 85-0207] p 215 A85-19591 Optimal control of flow of a viscous incompressible
- p 290 A85-22105 fluid Flight testing of a wing section with laminar flow control p 233 A85-22227
- Circulation control: A bibliography of DTNSRDC research and selected outside references: Update
- p 201 N85-15661 [AD-A146966] Improvement of Aerodynamic Performance Through Boundary Layer Control and High Lift Systems
- [AGARD-CP-365] p 204 N85-16771 An update of the Canada/USA augmentor-wing project p 257 N85-16781
- Aircraft drag reduction technology p 257 N85-16782
- Theoretical study of boundary-layer control p 237 N85-16784
- Drag reduction due to boundary-layer control by p 237 N85-16785 combined blowing and suction Technology developments for laminar boundary layer control on subsonic transport aircraft
- p 237 N85-16787 Active and passive shock/boundary layer interaction phtrol on supercritical airfoils p 238 N85-16795 control on supercritical airfoils
- BOUNDARY LAYER EQUATIONS
- Drag prediction for projectiles and finned bodies in incompressible flow AIAA PAPER 85-01041 p 230 A85-20854
- BOUNDARY LAYER FLOW
- An experimental investigation of stator/rotor interaction influence on multistage compressor rotor flow [AIAA PAPER 85-0009] p 206 A85-19455
- Application of axisymmetric analogue for calculating heating in three-dimensional flows
- AIAA PAPER 85-02451 p 216 A85-19611 A relaxation approach to patched-grid calculations with the Euler equations
- AIAA PAPER 85-02951 p 218 A85-19644
- Nonreflecting boundary conditions for the complete unsteady transonic small-disturbance equation p 290 A85-21875
- Detailed study of the flow around a multi-element airfoil. Comparison with calculations p 236 N85-16775 Application of two and three-dimensional criteria for
- calculating transitions and boundary layers over swept p 237 N85-16783 wings BOUNDARY LAYER SEPARATION
- Some features of two-dimensional turbulent separated flows
- [AIAA PAPER 85-0178] p 214 A85-19570 Measurements of separating boundary layer and wake
- of an airfoil using laser Doppler velocimetry [AIAA PAPER 85-0181] p 214 o 214 A85-19572 Evaluation of vortex wake predictions in the SWINT
- code [AIAA PAPER 85-0450] p 224 A85-19759
- Experimental and theoretical analysis of laminar separation bubbles p 288 A85-20874 [AIAA PAPER 84-2201]

Some important problems in unsteady boundary layers including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies p 294 N85-16069

[AD-A146964] Some important problems in unsteady boundary layers including separation. 1: Nature of singularity on oscillating airfoils

[AD-A147897] p 294 N85-16087 Drag reduction due to boundary-layer control by ombined blowing and suction p 237 N85-16785 combined blowing and suction Pneumatic turbulators: A device for drag reduction at

Reynolds numbers below 5 million p 257 N85-16791 BOUNDARY LAYER STABILITY

- Critical layer concept relative to hypersonic boundary laver stability
- [AIAA PAPER 85-0303] p 219 A85-19652 Laminar boundary layer stability experiments on a cone

at Mach 8. III - Sharp cone at angle of attack [AIAA PAPER 85-0492] p 226 A85-19787 BOUNDARY LAYER TRANSITION

A comparison of flight test and analytical techniques for boundary layer transition on a sailplane

- p 210 A85-19501 [AIAA PAPER 85-0075] On boundary layer transition in high-subsonic and transonic flow under the influence of acoustic disturbances and free-stream turbulence
- [AIAA PAPER 85-0082] p 210 A85-19508

Some thoughts on the range/tunnel transition controvers [AIAA PAPER 85-0127]

AIAA PAPER 85-0127] p 211 A85-19538 Potential flow calculations and preliminary wing design in support of an NLF variable sweep transition flight

experiment [AIAA PAPER 85-0426] p 248 A85-19741

Application of two and three-dimensional criteria for calculating transitions and boundary layers over swept wings p 237 N85-16783

BOUNDARY LAYERS

Aero-optics experimental techniques [AD-A146755] p 294 N85-16067 Some important problems in unsteady boundary layers including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies

p 294 N85-16069 [AD-A146964] Active and passive shock/boundary layer interaction ontrol on supercritical airfoils p 238 N85-16795 control on supercritical airfoils

BOUNDARY VALUE PROBLEMS The full-approximation method in the theory of transonic p 233 A85-22367

flows BRAKING

BUBBLES

of attack

BUDGETING

[AD-A146806]

[AD-D011392]

C-130 AIRCRAFT

CALIBRATING

Tornado:

(SUMS)

CABINS

BYPASS RATIO

BUS CONDUCTORS

[NASA-TM-86896]

[AIAA PAPER 85-0354]

abin fire test conditions

[AIAA PAPER 85-0393]

[AIAA PAPER 85-0395]

[AIAA PAPER 85-0270]

Testing solution for IL-76 braking system problem p 256 N85-16766

Experimental and theoretical analysis of laminar

Turbulent bubbles behind airfoils and wings at high angle

Pneumatic turbulators: A device for drag reduction at

Managing recoverable aircraft components in the PPB

EMI (electromagnetic interference) filter capacitor unit

Effect of steady-state temperature distortion on inlet flow

С

Evaluation of aircraft interior panels under full-scale

The thermal response of aircraft cabin ceiling materials

Inexpensive calibrations for the influence function

method using the interference distributed loads code ---

during a post-crash, external fuel-spill, fire scenario

for prediction of store loads in aircraft flow fields

Structural Usage

Afterbody drag reduction by vortex generators

Reynolds numbers below 5 million p 257 N85-16791

and related processes: Executive summary

to a high-bypass-ration turbofan engine

p 246 N85-16860

p 288 A85-20874

p 296 N85-16779

p 308 N85-16667

p 293 N85-15941

p 265 N85-15725

p 220 A85-19692

p 240 A85-19719

p 241 A85-19721

p 247 A85-19623

Monitoring System p 292 N85-15680

BROADCASTING Measurement of signal separation between radio service

[IRT-TB-B-40/82]

separation bubbles

[AIAA PAPER 84-2201]

and air navigation service

SUB IECT INDEX

CAMBERED WINGS			
Subsonic pressure distributions ne	ar a wing	-fin junctu	116
wing-mounted vertical fins	comigur	anou m	iui
[AIĂA PAPER 85-0276]	p 217	A85-196	28
The influence of camber variation	on the ae	rodynam	ics
[AIAA PAPER 85-0353]	p 220	A85-196	91
CANARD CONFIGURATIONS	• • • •		
Aerodynamic-structural study of ca	nard wing	3, dual wi al aviati	ng,
applications	or gener	ai anau	
[NASA-CR-172529]	p 238	N85-168	29
Stress analysis and shaping of the	a canopy	of a sour	re
parachute	p 242	A85-216	68
A theoretical view on the stress an	alysis of	fully inflat	ed
[AD-A148387]	p 239	N85-168	35
CAPACITORS			
EMI (electromagnetic interference [AD-D011392]	n 293	N85-159	1011 141
CARBON FIBER REINFORCED PLAS	STICS		
Energy absorbing qualities of fit	er reinfo	rced plas	stic
	p 282	A65-213	93
All-composite Airbus empennage	p 284	N85-159	931
CASCADE FLOW Numerical solutions of viscous	transo	nic flow	in
turbomachinery cascades	0 0 0 1 3 0	10 100	
[AIAA PAPER 85-0007]	p 206	A85-194	154
in a non-uniform inlet flow	of an anni	llar casca	age
[AIAA PAPER 85-0174]	p 213	A85-195	567
Matrix solution of compressible through a turbomaching blade row	flow on a	S(1) surfa	ace
tandem blades	p 227	A85-202	228
A new approach to some hybrid a	erodynan	nic proble	ms
of airfoil cascades on a general strea	n 228	of revoluti A85-202	on. 229
Complete three-dimensional flow	solution of	of a casca	ade
incorporating splitter vanes of arbitration	ary geom	etry	
A linearized unsteady aerodynamic	p 220 analysis	for transc	nic
cascades	p 229	A85-20	744
Computation of choked and super flows by a modified potential metho	sonic turl d	omachin	ery
news by a meaned potential meane	p 232	A85-21	359
Unsteady pressure measurements	s on a bio	onvex ai	foil
[NASA-TM-86914]	p 234	N85-15	689
Results of S5 CH tests with	an ARL	(Aerosp	ace
Research Laboratory) cascade			
INASA. IM. 775101	n 278	N85-16	882
CASCADE WIND TUNNELS	p 278	N85-16	882
CASCADE WIND TUNNELS Results of S5 CH tests with	p 278 an ARL	N85-16	882 ace
[NASA-IM-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510]	р 278 an ARL р 278	N85-16 (Aerosp N85-16	882 ace 882
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY	p 278 an ARL p 278	N85-16 (Aerosp N85-16	882 ace 882
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft apothesis	p 278 an ARL p 278 t stability	N85-16 (Aerosp N85-16 and cor	882 ace 882 htrol
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CELLINGS (ARCHITECTURE)	p 278 an ARL p 278 t stability p 270	N85-164 (Aerosp N85-164 and cor A85-21	882 ace 882 htrol 681
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of	p 278 an ARL p 278 t stability p 270 cabin ceil	N85-16 (Aerosp N85-16 and cor A85-21 ing mater	882 ace 882 htrol 681 ials
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85:0395]	p 278 an ARL p 278 t stability p 270 cabin ceil cill, fire so p 241	N85-16 (Aerosp N85-16 and cor A85-21 ing mater cenario A85-19	882 ace 882 htrol 681 ials 721
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CELLINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS	p 278 an ARL p 278 t stability p 270 cabin ceil bill, fire so p 241	N85-16 (Aerosp N85-16 and cor A85-21 ing mater cenario A85-19	882 ace 882 htrol 681 rials 721
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CELLINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL	p 278 an ARL p 278 t stability p 270 cabin ceil cabin ceil cabin ceil cabin stabil RS stabil	N85-16 (Aerosp N85-16 and cor A85-21 ing mater cenario A85-19 ized mate	882 ace 882 htrol 681 tials 721 erial
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116]	p 278 an ARL p 278 t stability p 270 cabin ceil bill, fire sc p 241 RS stabil	N85-16 (Aerosp N85-16 and cor A85-21 ing mater cenario A85-19 ized mater	882 ace 882 htroi 681 ials 721 eria 760
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS	p 278 an ARL p 278 t stability p 270 cabin ceil bill, fire so p 241 RS stabil p 277	N85-16 (Aerosp N85-16 and cor A85-21 ing mater enario A85-19 ized mate N85-15	882 ace 882 htrol 681 rials 721 aria 760
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t	p 278 an ARL p 278 t stability p 270 cabin ceil bill, fire so p 241 RS stabil p 277 hree-drim	N85-16 (Aerosp N85-16 and cor A85-21 ing mater cenario A85-19 ized mater N85-15	882 ace 882 htrol 681 ials 721 3rials 721 8ria 760
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t in centrifugal compressor impellers Experimental investigation of ba	p 278 an ARL p 278 t stability p 270 cabin ceil jill, fire so p 241 RS stabil p 277 hree-dim p 228 ckswep	N85-16 (Aerosp N85-16 and cor A85-21 ing mater cenario A85-19 ized mater N85-15 ensional A85-20 centrift	882 ace 882 1trol 681 ials 721 37ia 760 flow 231 19a
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t in centrifugal compressor impellers.]	p 278 an ARL p 278 t stability p 270 cabin ceil pill, fire so p 241 RS stabil p 277 hree-dim p 228 ckswep p 264	N85-16i (Aerosp N85-16i and cor A85-21i ing mater cenario A85-19 ized mater N85-15 sensional i A85-20 i centrifi A85-20	882 ace 882 htrol 681 ials 721 aria 760 flow 231 uga 243
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t in centrifugal compressor impellers Experimental investigation of ba compressor impeller, I CENTRIFUGAL PUMPS Analysis and testing for rotorth	p 278 an ARL p 278 t stability p 270 cabin ceil pill, fire so p 241 RS stabil p 277 hree-dim p 228 ckswep p 264	N85-16i (Aerosp N85-16i and cor A85-21i ing mater cenario A85-19 ized mater N85-15 sensional i A85-20 centrific A85-20 centrific	882 ace 882 htrol 681 ials 721 3760 flow 231 98 243 243 243
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t in centrifugal compressor impellers Experimental investigation of ba compressor impeller. I CENTRIFUGAL PUMPS Analysis and testing for rotordy, turbulent annular seals	p 278 an ARL p 278 t stability p 270 cabin ceili jill, fire so p 241 RS stabil p 277 hree-dim p 228 ckswept p 228 ckswept p 228 ckswept p 228	N85-16i (Aerosp N85-16i and cor A85-21i ing mater cenario A85-19 ized mater N85-15 ensional 1 A85-20 centrific A85-20 centrific	882 ace 882 882 681 681 681 721 760 flow 231 233 243 243 8 o ent
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t in centrifugal compressor impellers Experimental investigation of ba compressor impeller. I CENTRIFUGAL PUMPS Analysis and testing for rotordy turbulent annular seals directionally-homogeneous surface	p 278 an ARL p 278 t stability p 270 cabin ceilio cill, fire so p 270 cabin ceilio p 270 cabin ceilio p 270 creation p 228 cckswepi p 228 cckswepi p 228 cckswepi p 228 cckswepi p 228 cckswepi p 228	N85-16i (Aerosp N85-16i and cor A85-21i ing mater cenario A85-19 ized mater N85-15 ensional i A85-20 centrific A85-20 centrific	882 ace 882 htroi 681 fials 721 sria 721 flow 231 iga 243 s or ent hen
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t in centrifugal compressor impellers. Experimental investigation of ba compressor impeller. I CENTRIFUGAL PUMPS Analysis and testing for rotordy turbulent annular seals directionally-homogeneous surface for rotor and stator elements [ASME PAPER 84-TRIB-311]	p 278 an ARL p 278 t stability p 270 cabin ceilio cill, fire so p 241 RS stabil p 277 hree-dim p 228 ckswepi p 264 mamic c with -roughne	N85-16i (Aerosp N85-16i and cor A85-21i ing mater penario A85-19 ized mater N85-15 ensional i A85-20 centrift A85-20 cefficient: differ ss treatm A85-21	882 ace 882 htrol 681 fals 721 aria 760 flow 231 iga 243 s of ent hen 293
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t in centrifugal compressor impellers. Experimental investigation of ba compressor impeller. I CENTRIFUGAL PUMPS Analysis and testing for rotordy turbulent annular seals directionally-homogeneous surface for rotor and stator elements [ASME PAPER 84-TRIB-31] CERAMIC COATINGS	p 278 an ARL p 278 t stability p 270 cabin ceilio p 270 cabin ceilio p 270 p 241 RS stabil p 277 hree-dimm p 228 ckswepi p 264 rnamic c with -roughne p 289	N85-16i (Aerosp N85-16i and cor A85-21i ing mater penario A85-19 ized mater N85-15 ensional i A85-20 centrifu A85-20 cefficient: differ ss treatm A85-21	882 ace 882 1trol 681 581 582 721 760 760 760 760 760 231 98 243 243 243 243 243 243 243 243
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t in centrifugal compressor impellers Experimental investigation of ba compressor impeller. I CENTRIFUGAL PUMPS Analysis and testing for rotordy turbulent annular seals directionally-homogeneous surface for rotor and stator elements [ASME PAPER 84-TRIB-31] CERAMIC COATINGS FRG ceramic engine components	p 278 an ARL p 278 t stability p 270 abin ceilibill, fire sc p 241 RS stabil p 277 hree-dim p 228 ckswepi p 264 rnamic c with -roughne p 289 s (PET)	N85-164 (Aerosp N85-16 and cor A85-21 ing mater cenario A85-19 ized mater N85-15 ansional i A85-20 centrift A85-20 centrift A85-21 differ s treatm A85-21	882 ace 882 htrol 681 ials 721 arials 760 flow 231 iga 243 s or ent ien 293
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t in centrifugal compressor impellers Experimental investigation of ba compressor impeller, I CENTRIFUGAL PUMPS Analysis and testing for rotordy turbulent annular seals directionally-homogeneous surface for rotor and stator elements [ASME PAPER 84-TRIB-31] CERAMIC COATINGS FRG ceramic engine components	p 278 an ARL p 278 t stability p 270 cabin ceil bill, fire sc p 241 RS stabil p 277 hree-dim p 228 ckswepi p 264 rnamic c with -roughne p 289 s (PET) p 297	N85-164 (Aerosp N85-16 and cor A85-21 ing mater cenario A85-19 ized mater N85-15 ansional i A85-20 centrift A85-20 centrift A85-20 centrift A85-21 N85-17	882 ace 882 htrol 681 ials 721 aria 721 aria 721 ga 243 ga 243 s or ent 193
[NASA-1M-/7510] CASCADE WIND TUNNELS Results of S5 CH tests with Research Laboratory) cascade [NASA-TM-77510] CATASTROPHE THEORY A global technique for aircraft analysis CEILINGS (ARCHITECTURE) The thermal response of aircraft of during a post-crash, external fuel-sp [AIAA PAPER 85-0395] CEMENTS Development of a preliminary AL pavement analysis system (SPAS) [AD-A147116] CENTRIFUGAL COMPRESSORS Calculation and analysis of the t in centrifugal compressor impellers Experimental investigation of ba compressor impeller. I CENTRIFUGAL PUMPS Analysis and testing for rotordy turbulent annular seals directionally-homogeneous surface for rotor and stator elements [ASME PAPER 84-TRIB-31] CERAMIC COATINGS FRG ceramic engine components	p 278 an ARL p 278 t stability p 270 cabin ceil bill, fire sy p 241 RS stabil p 277 hree-dim p 228 ckswepi p 264 rnamic c with -roughne p 289 s (PET) p 297 veranics	N85-164 (Aerosp N85-16 and cor A85-21 ing mater cenario A85-19 ized mater N85-15 ansional f A85-20 centrift A85-20 centrift A85-21 differ ss treatm A85-21 nstreatm	882 ace 882 htrol 681 ials 721 aria 721 aria 721 aria 231 233 243 s or ent 293 193 293

- The challenge from ceramics to metals in the gas turbine p 280 A85-20150 and related areas CESSNA 402B AIRCRAFT
- Design of a digital ride quality augmentation system for commuter aircraft [AD-A148233] p 271 N85-16879
- CH-47 HELICOPTER Noise measurement flight test for Boeing Vertol 234/CH 47-d helicopter: Data/analyses
- p 306 N85-17670 [AD-A148172]

Shock waves in transonic channel flows at moderate

[AIAA PAPER 85-03691 p 221 A85-19702 Shock waves in transonic flows at moderate Reynold p 238 N85-16823 Number CHANNELS (DATA TRANSMISSION) Systems study for an Integrated Digital-Electric Aircraft (IDÉA) [NASA-CR-3840] p 255 N85-15714 Evolution toward a multi-bus architecture for Army p 260 N85-16812 helicopter avionic systems Integration of sensor fusion in advanced helicopter p 260 N85-16813

cockoit desian CHECKOUT

CHANNEL FLOW

Reynolds number

Joint service design for testability program p 296 N85-16733

- CHEMICAL REACTIONS Spectral methods for modeling supersonic chemically
- reacting flow fields [AIAA PAPER 85-0302] p 219 A85-19651 CHIPS (ELECTRONICS)
- Life cycle cost model for very high speed integrated circuits p 297 N85-17298
- [AD-A147798] CIRCUIT BOARDS
 - Packaging and interconnection for avionics p 290 A85-21460
- **CIRCUIT PROTECTION** Atmospheric electricity hazards to aircraft operation [AIAA PAPER 85-0013] p 247 A85-19457 CIRCULAR TUBES
- An experimental study of sound attenuation characteristics in circular ducts with lined radial baffles p 304 A85-19505 [AIAA PAPER 85-0079] CIRCULATION
- Circulation control: A bibliography of DTNSRDC esearch and selected outside references: Update p 201 N85-15661 [AD-A146966]
- CIRCULATION CONTROL AIRFOILS Computational study of circulation control with suction [AIAA PAPER 85-0042] p 208 A85-19477
 - Analysis of circulation control airfoils using an implicit Navier-Stokes solver [AIAA PAPER 85-0171] p 213 A85-19565
 - Circulation control airfoils Past, present, future p 215 A85-19588 [AIAA PAPER 85-0204] A Navier-Stokes investigation of a circulation control
- airfoil [AIAA PAPER 85-0300] p 219 A85-19649 CIVIL AVIATION
 - The influence of camber variation on the aerodynamics of civil transport aircraft
- [AIAA PAPER 85-0353] p 220 A85-19691 p 244 A85-19805 Aviation radar --- Russian book The division of tasks in modern air transport and its effect on the liability of the air carrier - The concept 'agents'
- in the so-called Warsaw Convention --- German thesis p 307 A85-19826 Advanced helicopter technology - Industry girds for
- challenges of evolving operational needs p 199 A85-20057 Report from the United States of America --- legal
- procedures for airport construction or expansion p 307 A85-21942 Report from the United Kingdom --- legal procedures
- for airport construction or expansion p 307 A85-21943
- Construction and extension of airports Legal procedure p 307 and practice in Canada A85-21944 Creation and extension of airports - Procedures and
- p 307 A85-21945 practice Report from Sweden --- legal procedures for airport
- p 307 A85-21946 construction or expansion Construction and extension of airports - National report p 308 A85-21947 on Switzerland
- Report from Japan --- legal procedures for airport construction or expansion p 308 A85-21948 National report - The Federal Republic of Germany -
- legal procedures for airport construction or expansion p 308 A85-21949 Trends in civil aircraft design
- p 200 A85-22226 Design study of technology requirements for high performance single-propeller-driven business airplanes [NASA-CR-3863] p 235 N85-15692 FAA (Federal Aviation Administration) statistical
- handbook of aviation, calendar year 1983 [AD-A148171] p 203 N85-16760
- USSR report: Transportation [JPRS-UTR-85-001] p 204 N85-16763 Director on institute's civil aviation projects
- p 204 N85-16764 Designer on Aeroflot automated COMMO system p 296 N85-16765 development Testing solution for IL-76 braking system problem
 - p 256 N85-16766

International projects, other work of Aeroproyekt

- p 204 N85-16767 Institute Designer on civil aircraft design trends in USSR p 256 N85-16768 Airport activity statistics of certificated route air
- carriers p 243 N85-16846 [AD-A148472] Directions of the West German Ministry of Transport
- for education and control of airline personnel (section 3, p 243 N85-16848 chapters 2 and 12) Directions of the West German Ministry of Transport for education and control or airline personnel, Report 6;
- p 244 N85-16849 chapters 3/A and 3/B Satellite navigation
- [S-HRG-98-856] p 246 N85-16851 Activities report on West German civil airports. Part 1: Text
- [ISBN-3-87977-055-7-PT-1] p 279 N85-16887 Activities report for the West German Civil Airports. Part Tables
- p 279 N85-16888 [ISBN-3-87977-055-7-PT-2] **CL-41 AIRCRAFT**
- TUTOR (CL-41A) tail flight load survey p 254 N85-15678
- CLEAR AIR TURBULENCE Clear turbulence forecasting - Towards a union of art
- and science p 298 A85-19458 [AIAA PAPER 85-0014]
- Identification of vortex-induced clear air turbulence using airline flight records p 299 A85-21843 CLIMATOLOGY
- The visibility climatology of McMurdo Sound-Williams Field, Antarctica
- [AD-A148108] p 300 N85-17492 CLIMBING FLIGHT
 - Benefits and costs of powered engine simulation at low speeds
- [AIAA PAPER 85-0381] p 263 A85-19710 CLOUDS (METEOROLOGY)
- Icing conditions encountered by a research aircraft p 299 A85-21141
- COCKPIT SIMULATORS Advanced flight simulation for helicopter development p 277 N85-16815
- COCKPITS
- The Cockpit Display of Traffic Information and the Threat Alert and Collision Avoidance System Integration - A p 259 A85-21559 review
- Integration of sensor fusion in advanced helicopter p 260 N85-16813 cockpit design A cockpit-display concept for executing a multiple
- glide-slope approach for wake-vortex avoidance [NASA-TP-2386] p 261 N85-16869 COLD FLOW TESTS
- SFRJ simulator results Experiment and analysis in cold flow --- Solid Fuel RamJet
- TAIAA PAPER 85-03291 p 263 A85-19671 COLLISION AVOIDANCE
- The Cockpit Display of Traffic Information and the Threat Alert and Collision Avoidance System Integration - A p 259 A85-21559 review
- The use of local functionals to construct a circumvention maneuver in game problems of evasion
- p 302 A85-22374 A bird strike handbook for base-level managers p 293 N85-16008 [AD-A147928]
- COMBAT Calculation of the exchange ratio for the Adaptive
- Maneuvering Logic program [AIAA PAPER 85-0311] p 199 A85-19658 Computer sizing of fighter aircraft
- p 203 N85-16759 [NASA-TM-86351] Evaluation of nose, roof, and mast mounted sensor
- platforms for piloting and sighting, integrated in future p 260 N85-16808 combat helicopters The design and development of an integrated core system for battlefield helicopters p 260 N85-16811
- COMBUSTIBLE FLOW
- Examining the validity of a combustor flow model with LDV
- [AIAA PAPER 85-0055] p 209 A85-19487 Spectral methods for modeling supersonic chemically reacting flow fields
- p 219 A85-19651 [AIAA PAPER 85-0302] An experimental investigation of an unsteady
- combusting flow in a pulse combustor p 281 A85-20865 [AIAA PAPER 85-0322]
- COMBUSTION CHAMBERS Examining the validity of a combustor flow model with LDV
- [AIAA PAPER 85-0055] o 209 A85-19487 Calculation of confined swirting flows
- [AIAA PAPER 85-0060] p 285 A85-19491 Computation of recirculating compressible flow in axisymmetric geometries
 - p 286 A85-19575 [AIAA PAPER 85-0185]

p 205 A85-19401

p 205 A85-19404

p 206 A85-19405

p 206 A85-19439

p 206 A85-19454

p 206 A85-19460

solutions of

An improved version of the LTRAN2 for high frequency

Comparative study of various quadratures for subsonic

An analysis of the flow past an S-shaped rotor by discrete

Numerical solutions of viscous transonic flow in

Euler solution of axisymmetric flows about bodies of

Theoretical study on supersonic jet plumes

lifting surface chordwise integrals

revolution using a multigrid method [AIAA PAPER 85-0017]

turbomachinery cascades [AIAA PAPER 85-0007]

domain

vortex model

COMBUSTION PHYSICS

Some improvements on an annular combustor of AI type p 264 A85-20235 turboiet engine Swirling flow in a research combustor

p 283 A85-21863 Verification of life prediction through component p 292 N85-15748

COMBUSTION PHYSICS A linearly correcting method of deviation function for considering the influence of pressure on the

thermodynamic properties of combustion gas p 304 A85-20236 COMBUSTION PRODUCTS

Heater block assembly for use in thermal oxidation testing of jet fuel p 285 N85-17077

[AD-D011430] COMBUSTION STABILITY An experimental investigation of an unsteady

combusting flow in a pulse combustor p 281 A85-20865

- [AIAA PAPER 85-0322] COMMERCIAL AIRCRAFT Hardware design techniques --- systems integration for
- civil and military aircraft avionics p 244 A85-21459 Integrated communications - A designers view --- for civil and military aircraft avionics p 245 A85-21462 Airport activity statistics of certificated route air
- carriers [AD-A148472] p 243 N85-16846 Design of a digital ride quality augmentation system for
- commuter aircraft [AD-A148233] p 271 N85-16879
- COMMUNICATION NETWORKS tactical New generation military airborne communications systems - The interoperability challenge p 244 A85-19275
- COMMUNITIES
- Test of dispersal of turbojet aircraft departure tracks at washington National Airport (1983-84), volume 1 report
- [AD-A148111] p 306 N85-17669 COMPARISON Analysis of the flow field about a T-45 using PANAIR
- p 236 N85-15699 [AD-A146811] COMPENSATORS
- Multivariable flight control with time-scale separation [NASA-CR-174320] p 268 N85-16873 COMPLEX SYSTEMS
- Theory of vibration conduction as a method for calculating the vibration of complex structures p 287 A85-20454
- COMPONENT RELIABILITY Engine cyclic durability by analysis and material testing
- sting p 267 N85-15744 A practical example of reducing life cycle costs and increased availability p 296 N85-16736 COMPOSITE MATERIALS
- Europeans using composites, ceramics for rotorcraft p 263 A85-20061 engine improvements Fabrication and assembly of composite rear fuselage (CRF) tooling and manufacturing for the UH-60 p 200 A85-21394 helicopter Composite curved frames for helicopter fuselage p 252 A85-21396 structure
- The all-composite airframes p 252 A85-21397 Skirt material effects on air cushion dynamic heave p 307 A85-21840 stability All-composite Airbus empennage p 284 N85-15931
- Advances in composites technology p 284 N85-17048 [NASA-TM-86353] Composite structure repair, addendum
- p 284 N85-17057 (AGARD-R-716-ADD) p 284 N85-17058 Repair of composites Composite repair of aircraft structures
- p 285 N85-17059 COMPOSITE STRUCTURES
- Measurements of the response of transport aircraft
- ceiling panels to fuel pool fires [AIAA PAPER 85-0394] p 240 A85-19720 Composite structures; Proceedings of the National
- Specialists Meeting, Philadelphia, PA, March 23-25, 1983 p 281 A85-21376 K747 composite main rotor blade modification, analysis
- and qualification for new high temperature requirements p 251 A85-21378 Design, fabrication and verification of composite
- flexbeam tail rotor for AH-64 Apache helicopter p 251 A85-21379
- composite Development of a graphite/polyimide p 281 A85-21380 transmission housing Sikorsky composite rotor hub development p 251 A85-21381
- Tooling problems in the manufacture of AH-64 Composites Flexbeam Tail Rotor p 200 A85-21382 Ground test experience with large composite structures p 251 A85-21383 for commercial transports

Structural analysis and testing of ACAP subcomponents --- Advanced Composite Airframe Program p 251[°] A85-21384

- Advanced-composite joints and fittings for primary structural components p 290 A85-21385
- Crashworthiness of helicopter composite structures p 251 A85-21386
- Advanced composites Designed to survive --- helicopter safety in modern battlefield p 251 A85-21387 Environmental effects and durability evaluation of advanced composite fuselage structures
- p 251 A85-21388 Flexible matrix composites applied to bearingless rotor
- p 281 A85-21389 systems Utilization of analytical equipment in design and process problems solution and failure analysis of composites
- p 281 A85-21390 Kevlar aramid fibers vs other fibers for reinforcement p 282 A85-21392 of composite structures
- Universal matrices to obtain thermal load vectors for the family of anisotropic plane triangular finite elements p 291 A85-22232
- Composite structure repair, addendum [AGARD-R-716-ADD] p 284 N85-17057
- COMPRESSIBILITY Investigations into the effects of scale and compressibility on lift and drag in the RAE 5m pressurized p 236 N85-16773 low-speed wind tunnel
- COMPRESSIBLE FLOW An incremental block-line-Gauss-Seidel method for the
- Navier-Stokes equations [AIAA PAPER 85-0033] p 207 A85-19470 Calculation of compressible potential flow about
- multielement airfoils using a finite field-panel approach [AIAA PAPER 85-0038] p 207 A85-19473 Flows over low Reynolds number airfoils - Compressible
- Navier-Stokes numerical solutions [AIAA PAPER 85-0107] p 210 A85-19523
- Numerical solution of the Euler equations for high-speed, blended wing-body configurations [AIAA PAPER 85-0123] p 211 A85-19534
- Numerical solution of unsteady viscous flow past rotor sections
- [AIAA PAPER 85-0129] p 212 A85-19540 A study of compressible turbulent free shear layers using laser Doppler velocimetry
- [AIAA PAPER 85-0177] p 213 A85-19569 Computation of recirculating compressible flow in
- axisymmetric geometries [AIAA PAPER 85-0185] p 286 A85-19575
- A new singular integral method for compressible potential flow [AIAA PAPER 85-0481] p 225 A85-19778
- Computation of transonic inlet flows --- German thesis p 227 A85-19844
- Matrix solution of compressible flow on S(1) surface through a turbomachine blade row with splitter vanes or tandem blades p 227 A85-20228
- Flowfield analysis of low bypass ratio test cells p 265 A85-21839 Calculation of friction and heat transfer in turbulent flow
- of a compressible gas in a plane duct p 291 A85-22114
- Inviscid compressible flow past a multi-element aerofoil p 236 N85-16776 COMPRESSIBLE FLUIDS
- Analysis of the surface load and radiated sound of a vibrating airfoil with application to the experiment of Brooks [NASA-CR-3864]
- p 305 N85-16590 COMPRESSION LOADS
- The distortion of a supersonic turbulent boundary layer by bulk compression and surface curvature [AIAA PAPER 85-0299] p 218 A85-19648
- COMPRESSOR BLADES
- Calculation and analysis of the three-dimensional flow in centrifugal compressor impellers p 228 A85-20231 Experimental investigation of backswept centrifugal compressor impeller. I p 264 A85-20243
- COMPRESSOR ROTORS Problems and possibilities for life extension in gas turbine
- components p 267 N85-15742 COMPRESSORS
- Verification of life prediction through component p 292 N85-15748 testing Turbo fluid machinery and diffusers
- [NASA-TM-77467] p 298 N85-17363 COMPUTATION
- Numerical optimization design of advanced transonic ring configurations LAIAA PAPER 85-04241
- p 248 A85-19739 COMPUTATIONAL FLUID DYNAMICS
- Computation of three-dimensional flows for application to transonic compressors
- [ONERA, TP NO. 1984-146] p 204 A85-19260

Current status of numerical Navier-Stokes equations [AIAA PAPER 85-0032] p 207 A85-19469 An incremental block-line-Gauss-Seidel method for the Navier-Stokes equations [AIAA PAPER 85-0033] p 207 A85-19470 multistage time-stepping scheme for the Navier-Stokes equations [AIAA PAPER 85-0035] p 207 A85-19472 Calculation of compressible potential flow about multielement airfoils using a finite field-panel approach [AIAA PAPER 85-0038] p 207 A85-19473 Computational study of circulation control with suction [AIAA PAPER 85-0042] p 208 A85-19477 The effect of phase-difference on the spreading rate of a laminar circular jet under bi-modal excitation [AIAA PAPER 85-0045] p 208 A85-19479 Examining the validity of a combustor flow model with עמו p 209 A85-19487 [AIAA PAPER 85-0055] Calculation of confined swirling flows [AIAA PAPER 85-0060] p 285 A85-19491 Computational thermo-fluid dynamics contributions to advanced gas turbine engine design [AIAA PAPER 85-0083] p 262 A85-19509 A quasi-conservative lambda formulation --- for inviscid transonic flow simulation [AIAA PAPER 85-0088] o 210 A85-19511 Flows over low Reynolds number airfoils - Compressible Navier-Stokes numerical solutions [AIAA PAPER 85-0107] p 210 A85-19523 A zonal computational approach to thrust augmentor optimization [AIAA PAPER 85-0110] p 262 A85-19525 A comparison of Euler and Navier-Stokes solutions for supersonic flow over a conical delta wing [AIAA PAPER 85-0111] p 210 A85-19526 Solution of the unsteady Euler equations for fixed and rotor wing configurations [AIAA PAPER 85-0120] p 211 A85-19531 Three-dimensional Euler solutions with grid embedding NAA PAPER 85-0121] p 211 A85-19532 [AIAA PAPER 85-0121] A comparison of finite volume flux vector splittings for the Euler equations [AIAA PAPER 85-0122] p 211 A85-19533

- Numerical study on the dynamic stall process of a NACA 0012 airfoil [AIAA PAPER 85-0128] p 212 A85-19539
- Numerical solution of unsteady viscous flow past rotor sections
- [AIAA PAPER 85-0129] p 212 A85-19540 Calculation of viscous nozzle flows by the unsteady
- method of characteristics [AIAA PAPER 85-0131] p 212 A85-19542 The use of panel methods for the development of
- low-subsonic wall interference and blockage corrections [AIAA PAPER 85-0159] p 212 A85-19556 [AIAA PAPER 85-0159]
- A procedure for the calculation of supersonic flows with trong viscous-inviscid interaction
- p 213 A85-19562 [AIAA PAPER 85-0166] Numerical computation of viscous flowfields about
- multiple component airfoils p 213 A85-19563 [AIAA PAPER 85-0167]
- Analysis of circulation control airfoils using an implicit Navier-Stokes solver [AIAA PAPER 85-0171]
- p 213 A85-19565 A new iterative matrix solution procedure for three-dimensional panel methods
- [AIAA PAPER 85-0176] p 213 A85-19568
- Measurements of separating boundary layer and wake of an airfoil using laser Doppler velocimetry [AIAA PAPER 85-0181] p 214 p 214 A85-19572
- Computation of unsteady shock-induced vortex eparation
- [AIAA PAPER 85-0183] p 214 A85-19573 Computation of recirculating compressible flow in
- axisymmetric geometries [AIAA PAPER 85-0185] p 286 A85-19575
- Prediction of subsonic/transonic separated flow about airfaile [AIAA PAPER 85-0205]
 - p 215 A85-19589

A class of airfoils having finite trailing edge pressure oradients [AIAA PAPER 85-0206] p 215 A85-19590 Prediction of HiMAT RPRV component interference effects at transonic speeds [AIAA PAPER 85-0213] n 215 A85-19593 A simple analytical method for predicting axisymmetric turbulent jet flowfields in a freestream [AIAA PAPER 85-0251] p 216 A85-19614 Numerical solution of the full-potential equation for rotors and oblique wings using a new wake model [AIAA PAPER 85-0268] p 216 p 216 A85-19621 Linearized potential flow analysis of complex aircraft configurations by HISSS, a higher order panel method [AIAA PAPER 85-0281] p 217 A85-19632 Calculation of steady flow about propellers by means of a surface panel method [AIAA PAPER 85-0283] p 218 A85-19634 representation of Optimized discrete-singularity axisymmetric bodies --- for potential flow [AIAA PAPER 85-0284] p 218 A85-19635 Euler calculations for multielement airfoils using Cartesian grids [AIAA PAPER 85-0291] p 218 A85-19641 Numerical solution of the two-dimensional Euler equations by second-order upwind difference schemes [AIAA PAPER 85-0292] p 218 A85-19642 Multigrid solution of the Euler equations using implicit schemes [AIAA PAPER 85-0293] p 218 A85-19643 A relaxation approach to patched-grid calculations with the Euler equations [AIAA PAPER 85-0295] p 218 A85-19644 A Navier-Stokes investigation of a circulation control airfoil [AIAA PAPER 85-0300] p 219 A85-19649 A study of the effects of numerical dissipation on the calculation of supersonic separated flows p 219 A85-19650 [AIAA PAPER 85-0301] The computational treatment of supersonic wake flows in INCOREL [AIAA PAPER 85-0304] p 219 A85-19653 A three-dimensional Navier-Stokes/Euler code for blunt-body flow computations [AIAA PAPER 85-0361] p 220 A85-19696 A Navier-Stokes calculation of 3-D, turbulent flow near a propeller in a shear flow [AIAA PAPER 85-0365] p 220 A85-19698 Recent advances in computational transonic aerodynamics [AIAA PAPER 85-0366] p 221 A85-19699 The numerical simulation of steady transonic rotational flow using a dual potential formulation [AIAA PAPER 85-0368] p 221 A85-19701 Shock waves in transonic channel flows at moderate Revnolds number [AIAA PAPER 85-0369] p 221 A85-19702 Navier-Stokes computations of axisymmetric transonic flows with a two-equation model of turbulence [AIAA PAPER 85-0373] p 221 A85-19705 Evaluation of low Reynolds number turbulence models for attached and separated flows [AIAA PAPER 85-0375] p 286 A85-19706 Progress in development of a Navier-Stokes solver for evaluation of iced airfoil performance p 222 A85-19731 [AIAA PAPER 85-0410] Computational particle trajectory analysis on a 3-dimensional engine inlet [AIAA PAPER 85-0411] p 222 A85-19732 Three-dimensional airflow and hydrometeor trajectory calculation with applications [AIAA PAPER 85-0412] p 222 A85-19733 Shock induced vortices on elliptic cones in supersonic flow p 223 A85-19746 [AIAA PAPER 85-0433] Split-flux-vector solutions of the Euler equations for three-dimensional configurations p 223 A85-19747 [AIAA PAPER 85-0434] Solution method for a hovering helicopter rotor using the Euler equations [AIAA PAPER 85-0436] p 223 A85-19749 Trapping of free vortex by airfoils with surface suction [AIAA PAPER 85-0446] p 224 A85-19755 Evaluation of vortex wake predictions in the SWINT code [AIAA PAPER 85-0450] p 224 A85-19759 A comparative study between an implicit and explicit algorithm for transonic airfoils [AIAA PAPER 85-0480] p 225 A85-19777 A new singular integral method for compressible potential flow [AIAA PAPER 85-0481] p 225 A85-19778 Efficient self-consistent viscous-inviscid solutions for unsteady transonic flow [AIAA PAPER 85-0482] p 225 A85-19779

A three-dimensional adaptive grid method --- for computational fluid dynamics [AIAA PAPER 85-0486] p 225 A85-19783 Application of a variational method for generating adaptive grids --- for gas dynamics past airfoils [AIAA PAPER 85-0487] p 226 A85-19784 An implicit, conservative, zonal-boundary scheme for Euler equation calculations (AIAA PAPER 85-04881 p 226 A85-19785 Simulation of transonic three-dimensional nacelle/inlet flowfields using an Euler/Navier-Stokes algorithm [AIAA PAPER 85-0084] p 226 A85-19798 Computation of transonic inlet flows - German thesis p 227 A85-19844 Circulation around thick wings with free vortices p 227 A85-19848 German thesis A subdomain finite element method for solving the conservative full potential equation for transonic profile flows --- German thesis A85-19854 p 227 Matrix solution of compressible flow on S(1) surface through a turbomachine blade row with splitter vanes or p 227 A85-20228 tandem blades Complete three-dimensional flow solution of a cascade incorporating splitter vanes of arbitrary geometry p 228 A85-20230 Calculation and analysis of the three-dimensional flow in centrifugal compressor impellers p 228 A85-20231 A fast algorithm for solving the conservative transonic S1 full potential equation employing non-orthogonal curvilinear coordinates and non-orthogonal velocity p 228 A85-20239 components A stream function relaxation method for solving transonic S1 stream surface with respect to non-orthogonal curvilinear coordinates p 228 A85-20240 Hypersonic multicycle gas jet with a strongly underexpanded stream at the nozzle section p 229 A85-20554 Euler computations of AGARD Working Group 07 airfoil test cases [AIAA PAPER 85-0018] p 229 A85-20851 Navier-Stokes computations for exotic airfoils p 230 A85-20855 [AIAA PAPER 85-0109] Design of aerodynamic bodies using artificial intelligence/expert system technique [AIAA PAPER 85-0112] p 301 A85-20856 Recent improvements in efficiency, accuracy, and convergence for implicit approximate factorization algorithms --- computational fluid dynamics p 230 A85-20868 [AIAA PAPER 85-0360] A numerical simulation of the NFAC (National Full-scale Aerodynamics Complex) open-return wind tunnel inlet [AIAA PAPER 85-0437] p 230 A85-20869 Experimental and theoretical analysis of laminar separation bubbles [AIAA PAPER 84-2201] p 288 A85-20874 A large-scale computer facility for computational p 301 A85-21791 aerodynamics Real-oas flowfields about three-dimensional continurations p 231 A85-21830 Evaluation of a stalled airfoil analysis program p 231 A85-21848 Experimental results for Reynolds number effects on trailing vortices p 232 A85-21849 Shock-fitting solution of the supersonic flowfield in a p 232 A85-21856 rounded internal corner Computation of choked and supersonic turbomachinery flows by a modified potential method p 232 A85-21859 Shock-free turbomachinery blade design p 232 A85-21864 Calculation of three-dimensional unsteady incompressible flows by a vortex method p 291 A85-22240 Analysis of the flow field about a T-45 using PANAIR p 236 N85-15699 [AD-A146811] Current problems in turbomachinery fluid dynamics [AD-A147127] p 294 N85-16074 Detailed study of the flow around a multi-element airfoil. Comparison with calculations p 236 N85-16775 **COMPUTATIONAL GRIDS** Euler solution of axisymmetric flows about bodies of revolution using a multigrid method [AIAA PAPER 85-0017] p 206 A85-19460 Three-dimensional Euler solutions with grid embedding [AIAA PAPER 85-0121] p 211 A85-19532 Multigrid solution of the Euler equations using implicit [AIAA PAPER 85-0293] n 218 A85-19643

Grid adaptation for the 2-D Euler equations

parabolic partial differential equations

Noniterative three-dimensional grid generation using

(AIAA PAPER 85-0484)

AIAA PAPER 85-04851

p 225 A85-19781

p 300 A85-19782

COMPUTER PROGRAMS Finite volume solution of the two-dimensional Euler equations on a regular triangular mesh [AIAA PAPER 85-0435] p 223 A85-19748 Grid adaptation for the 2-D Euler equations p 225 A85-19781 [AIAA PAPER 85-0484] Noniterative three-dimensional grid generation using parabolic partial differential equations [AIAA PAPER 85-0485] p 300 A85-19782 A three-dimensional adaptive grid method --- for omputational fluid dynamics p 225 A85-19783 [AIAA PAPER 85-0486] Application of a variational method for generating adaptive grids --- for gas dynamics past airfoils [AIAA PAPER 85-0487] p 226 A85-19784 COMPUTER AIDED DESIGN Aircraft turbojet engine modeling using artificial intelligence techniques [AIAA PAPER 85-0253] p 263 A85-19616 TRO-2D - A code for rational transonic aerodynamic ontimization [AIAA PAPER 85-0425] p 223 A85-19740 Interactive design technique for arbitrary shaped. airbreathing missile configurations [AIAA PAPER 85-0496] p 249 A85-19790 Training and research CAD system of the Moscow Aviation Institute and experience in its use p 199 A85-20455 Design of load-bearing aircraft structures p 288 A85-20463 Some problems in the development of CAD systems --- for design of minicomputer digital components p 200 A85-20466 Design of aerodynamic bodies using artificial Intelligence/expert system technique [AIAA PAPER 85-0112] p 301 A85-20856 A large-scale computer facility for computational p 301 A85-21791 aerodynamics ONERA - The aeronautics supercomputer is put into p 302 A85-22274 service Development of asymptotic algorithms in the Polet package of applications programs --- for sea surface effect p 233 A85-22366 vehicle design A method of forecasting active constraint with the applications to structural optimization p 291 A85-22445 Control system design language implementation of a gas turbine starting controller p 266 N85-15732 [AD-A147896] Design of an airfoil leading edge slat using an inverse erodynamic calculation method p 256 N85-16777 aerodynamic calculation method Design of a digital ride quality augmentation system for commuter aircraft COMPUTER AIDED MANUFACTURING Fabrication and assembly of composite rear fuselage (CRF) tooling and manufacturing for the UH-60 helicopter p 200 A85-21394 COMPUTER COMPONENTS Some problems in the development of CAD systems --- for design of minicomputer digital components p 200 A85-20466 COMPUTER DESIGN Description of MBB computerized design techniques for A320 p 303 N85-17194 COMPUTER GRAPHICS A Computer-generated topographic display system for navigation and mission planning in helicopters p 259 N85-16800 Description of MBB computerized design techniques for A320 p 303 N85-17194 COMPUTER PROGRAMS An improved version of the LTRAN2 for high frequency omain p 205 A85-19401 domain Analytical determination of propeller performance degradation due to ice accretion [AIAA PAPER 85-0339] p 264 A85-20867 Software design methods --- for civil and military aircraft p 301 A85-21457 avionics systems Development of asymptotic algorithms in the Polet package of applications programs --- for sea surface effect vehicle design p 233 A85-22366 Analysis of the flow field about a T-45 using PANAIR p 236 N85-15699 [AD-A146811] NyKINM, a further development of KINM 22 --- simulation of a robot attack on an aircraft [FOA-C-20559-D8(E3)] p 256 N85-15720 NOISEMAP 4.4 computer program update, operator's manual, addendum 1 [AD-A147091] p 302 N85-16503

ATE user's view on design for maintainability p 202 N85-16303

Built-in-test for first line testing p 202 N85-16739 Development of a Helicopter integrated navigation system p 245 N85-16802

COMPUTER SYSTEMS DESIGN

SUBJECT INDEX

33	CORROSION RESISTANCE Improvement of the corrosion re	sistance	of turbine
bld	engine bearings		
97	[AD-A147430] COST ANALYSIS	p 265	N85-15731
	Integrated technology wing stud	ly (oral p	resentation)
ete	[NASA-CR-169497] More than you want to know about	p 256 It mavimu	N85-15718 m likelibood
05	estimation	it maximu	
	[NASA-TM-85905]	p 270	N85-15752
51	Integrated technology wing stud	ly (oral p	resentation)
SS	[NASA-CR-169497]	p 256	N85-15718
57	COST ESTIMATES Parametric estimates of propulsion	i system r	naintenance
57	manhours		
for	[AD-A147120] The application of a technology in	p 201 dex to air	N85-15662 craft turbine
26	engine cost estimating relationships		
nic	[AD-A147701]	p 268	N85-16874
46	A practical example of reducing	life cycle	e costs and
a	increased availability	p 296	N85-16736
56	The embedded test (BIT): Impac	t on the	total cost of
ed	possession	p 202	N85-16734
73	CRACK PROPAGATION Development of a fatigue crack	oronanati	on model of
//	Incoloy 901	p 280	A85-20758
E0	Fatigue crack growth behavior of a under simple variable amplitude los	7XXX alur	ninum alloys
-00		p 280	A85-20759
dar	Interpretation of fatigue crack grow	vth in alun	ninium alloys
53	Cumulative damage modeling of t	p 201 atigue cra	ack growth
	F eedback in the second secon	p 267	N85-15741
21	aluminum allov forgings	ons of F	'M and IM
	[AD-B0881466L]	p 298	N85-17398
igh	CHACKS Cumulative damage modeling of t	fatique cr	ack arowth
71		p 267	N85-15741
	Problems and possibilities for life e components	xtension i n 267	n gas turbine N85-15742
28	Disc fatigue life predictions for ga	is turbine	engines
ast,	CRASHWORTHINESS	p 267	N85-15743
149 the	Crashworthiness of helicopter co	mposite s	tructures
ard	Enormy sheathing qualities of fit	p 251	A85-21386
80	tubes	p 282	A85-21393
	Proceedings of the Internation	nal Conf	erence and
Ind	[AD-A147845]	p 242	N85-15703
603	CRAY COMPUTERS		
cal	Service	rcompute p 302	A85-22274
98	CREW STATIONS		
act	(DTACS). Phase 1: Display techni	aues stud	ew Stations
149	[AD-A146922]	p 259	N85-15722
fa	Pilot's Desk Flight Station	p 258	A85-21555
732	CRITICAL VELOCITY	P	
750	Optimization of flutter characteris	tics n 288	485-20828
vith	CROP DUSTING	p 200	7100-20020
ten	Director on institute's civil aviatio	n projects	N85-16764
01.	CROSS FLOW	p 204	1100-10704
raft	Turbulence structure of a three of	dimensior	nal impinging
577	[AIAA PAPER 85-0044]	p 208	A85-19478
low	Flow visualization of lateral jet i	injection	into swirling
189	[AIAA PAPER 85-0059]	p 209	A85-19490
ind	Crossflow drag of finite-length re	ctangular	wing-bodies
ion	[AIAA PAPER 85-0451] Disturbance-wave interactions in	p 224 flows w	A85-19760 ith crossflow
368	[AIAA PAPER 85-0494]	p 226	A85-19788
125	Experiments on the stability of swept-wing flows	crossflov	v vortices in
125	[AIAA PAPER 85-0493]	p 231	A85-20873
) of	CRUISE MISSILES Aerodynamic configured missiles	- Promis	a and future
155	[AIAA PAPER 85-0345]	p 248	A85-19684
lac	CRYOGENIC COOLING	aania ha	at nino ininte
rđe	for heat exchangers in space ap	plications	ar hiha loiuiz
524	TALAA DADED OF OOPOI		405 40405
		p 279	A85-19495
na	CRYOGENIC WIND TUNNELS Studies of condensation effects	p 2/9 on airfoi	testing in a
na 356	CRYOGENIC WIND TUNNELS Studies of condensation effects transonic cryogenic tunnel	p 2/9 on airfoi	A85-19495
n a 356 ner Iers	[AIAA PAPER 05-0006] CRYOGENIC WIND TUNNELS Studies of condensation effects transonic cryogenic tunnel [AIAA PAPER 85-0229] The most spectacular equipment	p 279 on airfoi p 274	A85-19495 I testing in a A85-19603

A Generalized Escape System Simulation (GESS) computer program. Volume 2: GESS programmer's manual, version 2 [AD-A148363] n 243 N85-16845

COMPUTER SYSTEMS DESIGN A design methodology for integrated avionic systems p 301 A85-21458

COMPUTER SYSTEMS PROGRAMS Designing a priority driven multi-frame rate flight evecutive

[AIAA PAPER 85-0309] p 268 A85-19656 Investigating version dependence in fault-tolerant p 302 N85-16749 software The effect on software design of testing by symbolic p 303 N85-16750 execution

Reliable software design for avionics and space o 303 N85-16751 applications Software test handbook: Software test guidebook, volume 2

[AD-A147289] p 303 N85-17578 COMPUTER TECHNIQUES

Computers and progress in aviation p 199 A85-20453

Computer sizing of fighter aircraft p 203 N85-16759 [NASA-TM-86351] Description of MBB computerized design techniques for A320 p 303 N85-17194

COMPUTERIZED SIMULATION Lightning simulation facilities in the United States and

Europe [AIAA PAPER 85-0093] p 273 A85-19515 Numerical solution of the Euler equations for high-speed,

lended wing-body configurations [AIAA PAPER 85-0123] p 211 A85-19534

Aircraft turbojet engine modeling using artificial intelligence techniques [AIAA PAPER 85-0253] p 263 A85-19616

Inexpensive calibrations for the influence function method using the interference distributed loads code --for prediction of store loads in aircraft flow fields

p 247 A85-19623 [AIAA PAPER 85-0270] Calculation of the exchange ratio for the Adaptive Maneuvering Logic program

[AIAA PAPER 85-0311] p 199 A85-19658 Body flow field simulation and force/moment prediction at transonic speeds

[AIAA PAPER 85-0423] p 222 A85-19738 Computational aerodynamic design of the Gulfstream N/ wind

[AIAA PAPER 85-0427] p 223 A85-19742 Experimental methods for wind-tunnel flight-mechanics investigations using dynamically similar aircraft models

p 249 A85-19836 German thesis Newton iteration formulas for correcting temperature and pressure in thermodynamic calculation of rocket engines p 279 A85-20226

Recent improvements in efficiency, accuracy, and convergence for implicit approximate factorization algorithms --- computational fluid dynamics [AIAA PAPER 85-0360] p 230 A85-20868

A numerical simulation of the NFAC (National Full-scale Aerodynamics Complex) open-return wind tunnel inlet flow

[AIAA PAPER 85-0437] p 230 A85-20869 Prediction of performance of aircraft gas turbines

p 264 A85-21682 A Q-GERT network simulation model for examining pipeline time in the Navy's J-52 intermediate level jet engine repair cycle

[AD-A147269] p 201 N85-15663 Computer sizing of fighter aircraft

p 203 N85-16759 [NASA-TM-86351] Development of a Helicopter integrated navigation p 245 N85-16802 system

A Generalized Escape System Simulation (GESS) computer program. Volume 2: GESS programmer manual, version 2

[AD-A148363] p 243 N85-16845 CONDENSATION

Studies of condensation effects on airfoil testing in a transonic cryogenic tunnel

[AIAA PAPER 85-0229] p 274 A85-19603 CONES

Laminar boundary layer stability experiments on a cone at Mach 8. III - Sharp cone at angle of attack [AIAA PAPER 85-0492] p 226 A85-19787

CONFERENCES Composite structures; Proceedings of the National

Specialists Meeting, Philadelphia, PA, March 23-25, 1983 p 281 A85-21376 Design and advanced concepts of avionics/weapons

system integration; Proceedings of the Symposium London, England, April 3, 4, 1984 p 200 A85-21456 Proceedings of the International Conference and Exposition on Structural Impact and Crashworthiness

[AD-A147845] p 242 N85-15703

Engine Cyclic Durability by Analysis and Testing [AGARD-CP-368] p 266 N85-157 Helicopter Guidance and Control Systems for Battlefie Support [AGARD-CP-359] p 204 N85-167

CONFORMAL MAPPING

An analysis of the flow past an S-shaped rotor by discre p 206 A85-194 vortex model CONGRESSIONAL REPORTS

Satellite navigation

(S-HBG-98-856) p 246 N85-168 CONICAL BODIES

Conical bodies with a star-shaped transverse cro section, having a reserve of static stability p 229 A85-205

CONICAL FLOW A comparison of Euler and Navier-Stokes solutions

supersonic flow over a conical delta wing [AIAA PAPER 85-0111] p 210 A85-195 Shock induced vortices on elliptic cones in superson

flow [AIAA PAPER 85-0433] p 223 A85-197

Shock-fitting solution of the supersonic flowfield p 232 A85-218 rounded internal corner CONTAMINATION

Contamination and distortion of steady flow field induc by discrete frequency in aircraft gas turbines p 294 N85-160 AD-A1470921

CONTRAROTATING PROPELLERS Analysis of counter-rotating propeller performance [AIAA PAPER 85-0005] p 262 A85-194

CONTROL

NASA three-laser airborne differential absorption lid system electronics [NASA-CR-174293]

CONTROL STICKS

Biodynamic resistant control stick FAD-D0113801 p 259 N85-157

Improvement of Aerodynamic Performance Throu Boundary Layer Control and High Lift Systems [AGARD-CP-365] p 204 p 204 N85-167

CONTROL SYSTEMS DESIGN Investigations for the use of an active control in aircr ---- German thesis n 269 A85-198

The development of digital attitude controllers - Its pa present and future p 302 A85-224

design of a data link receiver unit for the Coast Gu HH-65A helicopter

CONTROL THEORY

Research on optimal control, stabilization a computational algorithms for aerospace applications A-CR-174318] p 303 N85-176

CONTROLLABILITY Operational

p 204 N85-167 capal CONTROLLERS

The development of digital attitude controllers - Its pa p 302 A85-22 present and future Control system design language implementation o

[AD-A147896] p 266 N85-157

Flutter control with unsteady aerodynamic models [AD-A147858] p 270 N85-157

bite on engine/flight control systems over the past p 296 N85-16 years

Volume 1: STI proposed structure --- military rotorc [NASA-CR-177304-VOL-1] p 271 N85-166

Accelerated convergence for incompressible fi

[AIAA PAPER 85-0058] p 209 A85-19 Recent improvements in efficiency, accuracy, a convergence for implicit approximate factoriza

[AIAA PAPER 85-0360] p 230 A85-208

[NASA-CR-174279] p 238 N85-168 COPOLYMERS

GC-FTIR (Fourier Transform Infrared Spectrometry) jet fuels

[AD-A148272] p 285 N85-17 CORE FLOW

A theory for the core of a three-dimensional leading-ed

p 210 A85-19 CORNER FLOW

Shock-fitting solution of the supersonic flow rounded internal corner ounded internal corner p 232 A85-210 Investigations of the longitudinal flow in cor configurations in the hypersonic regime. II - Corn p 232 A85-22 between swept wedges

p 298 N85-173

CONTROL SURFACES

Using the control system design environment in t

[AD-A148624] p 271 N85-168

technoloa requirements versus

gas turbine starting controller

Experience of one UK electronic equipment supplier v

Mission-oriented requirements for updating MIL-H-85

CONVERGENCE

celculations

algorithms --- computational fluid dynamics

Random equations in aerodynamics

[AIAA PAPER 85-0108]

- Description of the insulation system for the Langley 0.3-Meter Transonic Cryogenic Tunnel [NASA-TM-86274] p 276 N85-15755
- CURVED BEAMS Composite curved frames for helicopter fuselage
- structure p 252 A85-21396 CUSHIONCRAFT GROUND EFFECT MACHINE
- Skirt material effects on air cushion dynamic heave p 307 A85-21840 stability CYCLES
- View of future requirements for engine cyclic durability y analysis and testing p 267 N85-15751 by analysis and testing

D DAMAGE The F-15 flight loads tracking program p 253 N85-15666 Cumulative damage modeling of fatigue crack growth p 267 N85-15741 Advances in composites technology [NASA-TM-86353] p 284 N85-17048 o 284 N85-17058 Renair of composites DATA ACQUISITION **Operational Loads Data** p 201 N85-15664 (AGARD-CP-375) Operational loads measurement: A philosophy and its p 253 N85-15665 implementation Navy operational loads data sources and systems p 253 N85-15668 Advanced fatigue monitoring on service aircraft p 292 N85-15671 Helicopter data acquisition in WHL p 254 N85-15676 USAF approach to airborne structural data recording: Airborne Data Acquisition Multifunction System (ADAMS) p 292 N85-15683 Noise measurement flight test: Data-analyses, Sikorsky S-76A helicopter AD-A1485251 p 306 N85-17673 DATA BASE MANAGEMENT SYSTEMS Flexible manufacturing system for the production of aircraft parts [BLL-PNR-90237-(899.3153)] p 297 N85-17159 DATA BASES

Managing recoverable aircraft components in the PPB and related processes: Executive summary

p 308 N85-16667 [AD-A146806] Mission-oriented requirements for updating MIL-H-8501. Volume 2: STI background and rationale --- military rotorcraft

INASA-CR-177304-VOL-21 p 271 N85-16878 DATA LINKS

Using the control system design environment in the design of a data link receiver unit for the Coast Guard HH-65A helicopter

p 271 N85-16880 AD-A148624 DATA PROCESSING

Literature review of voice recognition and generation technology for Army helicopter applications p 293 N85-15954 [AD-A1468781

DATA RECORDING Identification of vortex-induced clear air turbulence using p 299 A85-21843 airline flight records Operational loads measurement: A philosophy and its

p 253 N85-15665 implementation The F-15 flight loads tracking program p 253 N85-15666

Flight parameters recording for structure fatigue life p 292 N85-15682 monitoring USAF approach to airborne structural data recording:

Airborne Data Acquisition Multifunction System (ADAMS) p 292 N85-15683 DATA REDUCTION

Keeping up with operational loads in the French Air Force: Defining new equipment p 292 N85-15681 **DECISION MAKING**

Judgment and discipline - Recipe for survival p 241 A85-21582

- Performance evaluation of A-10 aircraft mainteance units and aircraft using constrained facet analysis p 201 N85-15660 [AD-A146955]
- Distribution and storage of aviation turbine fuel for military operations in northern Australia p 283 N85-15921 [AD-A147180]

DEFECTS p 202 N85-16739 Built-in-test for first line testing

DEFORMATION Stereo Electro-optical Tracking System (SETS)

p 295 N85-16098 [NASA-CB-172471] DEGREES OF FREEDOM

Effect of aerodynamic and angle-of-attack uncertainties on the May 1979 entry flight control system of the Space Shuttle from Mach 8 to 1.5 [NASA-TP-2365] p 280 N85-15778

DEICERS

A summary of NASA's research on the fluid ice protection

p 241 A85-19768 [AIAA PAPER 85-0467] Icing tunnel tests of Electro-Impulse De-Icing of an inlet and high-speed wings

[AIAA PAPER 85-0466] p 241 A85-20872 DEICING

The Federal Aviation Administration's Engineering and Development Aircraft Icing Program [AIAA PAPER 85-0015] p 247 A85-19459

two-dimensional Full transient solutions of electrothermal aircraft blade deicing

- (AIAA PAPER 85-0413) p 248 A85-19734 Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) [NASA-TM-86919] p 276 N85-15757
- DELPHI METHOD (FORECASTING)
- A description of a logistically ideal aircraft [AD-A148425] p 258 N85-16866 DELTA WINGS
- Three-dimensional effects on a pitching lifting surface [AIAA PAPER 85-0041] p 208 A85-19476 Flow visualization of high angle of attack vortex wake structures
- [AIAA PAPER 85-0102] p 286 A85-19520 A comparison of Euler and Navier-Stokes solutions for supersonic flow over a conical delta wing
- [AIAA PAPER 85-0111] p 210 A85-19526 Subsonic wing rock of slender delta wings [AIAA PAPER 85-0198] p 214
- p 214 A85-19582 An attached flow design of a noninterfering leading edge extension to a thick delta wing
- n 220 A85-19689 An optimality criterion method for structures with stress, displacement and frequency constraints
- A method of forecasting active constraint with the applications to structural optimization
- p 291 A85-22445
- Application of laser measurements in free jets interferometry to density p 206 A85-19406 Tomographic reconstruction of three-dimensional flow over airfoils
- DEPLOYMENT
- deployable nozzles --- for upper stage ballistic missiles [ONERA, TP NO. 1984-149] p 205 A85-19263 DEPOSITION
- Evaluation of jet fuel deposit kinetics. Lot 4 AD-A1471961 p 284 N85-15922
- DEPOSITS Evaluation of jet fuel deposit kinetics. Lot 4
- [AD-A147196] p 284 N85-15922 DESCENT
- of aircraft and flight parameters on Effects energy-efficient profile descents in time-based metered traffic
- [NASA-CR-172338-ADD] n 245 N85-15706 Reference energy-altitude descent guidance: Simulator evaluation --- aircraft descent and fuel conservation
- [NASA-TP-23831 p 261 N85-16868 DESIGN ANALYSIS
- Modular simulators, their feasibility, design, and procurement
- [AIAA PAPER 85-0312] p 274 A85-19659 TRO-2D - A code for rational transonic aerodynamic optimization
- [AIAA PAPER 85-0425] p 223 A85-19740 Design of aerodynamic bodies using artificial
- intelligence/expert system technique [AIAA PAPER 85-0112] p 301 A85-20856
- Shock-free turbomachinery blade design p 232 A85-21864
- Trends in civil aircraft design p 200 A85-22226 A description of a logistically ideal aircraft [AD-A148425] p 258 N85-16866
- DIESEL ENGINES
- FRG ceramic engine components (PET) p 297 N85-17193 DIFFERENCE EQUATIONS
- Numerical solution of the two-dimensional Euler equations by second-order upwind difference schemes AIAA PAPER 85-0292] p 218 A85-19642 DIFFUSERS
- Effect of inlet and outlet flow conditions on the flow and performance of subsonic two-dimensional diffuse p 228 A85-20241
- Turbo fluid machinery and diffusers [NASA-TM-77467] p 298 N85-17363 DIGITAL COMPUTERS
- Investigation of semiautomatic aircraft control processes employing time redundancy in on-board digital trajectory control computers p 270 N85-16048

DIGITAL NAVIGATION p 245 A85-21461 Integrated navigation Trends in digital flight control systems p 269 A85-21465 DIGITAL SYSTEMS Predicted performance benefits of an adaptive digital engine control system on an F-15 airplane [AIAA PAPER 85-0255] p 263 A85-19801 Systems study for an Integrated Digital-Electric Aircraft (IDEA) (NASA-CR-38401 o 255 N85-15714 Predicted performance benefits of an adaptive digital engine control system of an F-15 airplane [NASA-TM-85916] p 265 N85-15729 Experience of one UK electronic equipment supplier with bite on engine/flight control systems over the past ten p 296 N85-16738 vears A digital piloting system for the combat helicopter p 260 N85-16806 Integrated digital/electric aircraft concepts study p 257 N85-16861 [NASA-CR-3841] Design of a digital ride quality augmentation system for commuter aircraft [AD-A148233] p 271 N85-16879 DIGITAL TECHNIQUES Application of digital interferogram evaluation techniques to the measurement of three-dimensional flow fiolds [AIAA PAPER 85-0037] p 288 A85-20852 The development of digital attitude controllers - Its past, p 302 A85-22449 present and future **DIPOLE ANTENNAS** Tactical HF communication for military helicopters using p 297 N85-16807 the NVIS mode DIRECTIONAL ANTENNAS Reflector antennas with directional effect in the near-field Characteristics and applications --- German p 287 A85-19837 thesis DIRECTIONAL STABILITY Theory of wing rock [AIAA PAPER 85-0199] p 268 A85-19583 DISCIPLINING Judgment and discipline - Recipe for survival p 241 A85-21582 DISPLAY DEVICES The Cockpit Display of Traffic Information and the Threat Alert and Collision Avoidance System Integration - A A85-21559 p 259 Display Techniques for Advanced Crew Stations (DTACS). Phase 1: Display techniques study AD-A146922] p 259 N85-15722 p 202 N85-16739 Built-in-test for first line testing A Computer-generated topographic display system for navigation and mission planning in helicopters p 259 N85-16800 p 259 N85-16801 Map display for helicopters Integration of sensor fusion in advanced helicopter p 260 N85-16813 cockpit design Flight research on visusl aids and navigation equipment for helicopter low-level flight at night o 261 N85-16820 A cockpit-display concept for executing a multiple glide-slope approach for wake-vortex avoidance [NASA-TP-2386] p 261 No p 261 N85-16869 Realization and testing of an experimental color display system for general aviation helicopters and aircraft [BMFT-FB-W-84-042] p 262 N85p 262 N85-16872 DISTILLATION Analysis of middle distillate fuels by high resolution field ionization mass spectrometry [AD-A147724] p 285 N85-17153 DISTORTION Temperature distortion generator for turboshaft engine testina [NASA-TM-83748] p 200 N85-15658 Effect of steady-state temperature distortion on inlet flow to a high-bypass-ration turbofan engine p 265 N85-15725 [NASA-TM-86896]

Contamination and distortion of steady flow field induced

Test of dispersal of turbojet aircraft departure tracks

Experimental methods for wind-tunnel flight-mechanics

investigations using dynamically similar aircraft models

at washington National Airport (1983-84), volume 1

by discrete frequency in aircraft gas turbines

Tail behaviour for suprema of empirical proces

AD-A147092]

AD-A1476291

[AD-A148111]

DO-28 AIRCRAFT

German thesis

DOCUMENTATION

Built-in-test for first line testing

report

DISTRIBUTION FUNCTIONS

DISTRICT OF COLUMBIA

A-13

p 294 N85-16073

p 303 N85-17613

o 306 N85-17669

p 249 A85-19836

p 202 N85-16739

[AIAA PAPER 85-03501

p 290 A85-21985

DENSITY MEASUREMENT

[AIAA PAPER 85-0479] p 225 A85-19776

Aerodynamic studies linked to the development of

DOPPLER NAVIGATION

DOPPLER NAVIGATION

Flight research on visusl aids and navigation equipment for helicopter low-level flight at night

- p 261 N85-16820 DOPPLER RADAR Radar for storm forecasting and weather hazard
- warning [AIAA PAPER 85-0092] p 299 A85-19514 Aviation radar --- Russian book p 244 A85-19805
- DOWNWASH Downwash in the plane of symmetry of an elliptically
- loaded wing [NASA-TP-2414] p 235 N85-15693
- DRAG UH-60A external stores support system fixed provision
- fairings drag determination [AD-A147188] p 256 N85-15719
- DRAG CHUTES Drag of the fundamental shapes of parachutes
- p 231 A85-20998 DRAG COEFFICIENTS
- Crossflow drag of finite-length rectangular wing-bodies [AIAA PAPER 85-0451] p 224 A85-19760 p 224 A85-19760 DRAG REDUCTION
- A comparison of flight test and analytical techniques for boundary layer transition on a sailplane
- p 210 A85-19501 [AIAA PAPÉR 85-0075] Supercritical airfoil drag reduction by passive shock wave/boundary layer control in the Mach number range 75 to 90
- [AIAA PAPER 85-0207] p 215 A85-19591 Afterbody drag reduction by vortex generators [AIAA PAPER 85-0354] p 220 A85-19692
- Arrays for minimum wave drag of bodies of revolution p 249 A85-19758 [AIAA PAPER 85-0449]
- Installed nacelle drag improvement tests of an M = 0.8 turboprop transport configuration [NASA-TM-84302] p 255 N85-15716
- Aircraft drag reduction technology p 257 N85-16782
- Drag reduction due to boundary-layer control by p 237 N85-16785 combined blowing and suction Turbulent drag reduction research
- p 237 N85-16788 Full scale experiments into the use of large eddy breakup devices for drag reduction on aircraft
- p 257 N85-16790
- Pneumatic turbulators: A device for drag reduction at Reynolds numbers below 5 million p 257 N85-16791 Study of winglets applied to biplanes
- p 258 N85-16862 [NASA-TM-863501 DROPS (LIQUIDS)
- Computational particle trajectory analysis on a 3-dimensional engine inlet
- [AIAA PAPER 85-0411] p 222 A85-19732 Three-dimensional airflow and hydrometeor trajectory calculation with applications
- [AIAA PAPER 85-0412] p 222 A85-19733 DRY FRICTION
- Effects of friction dampers on aerodynamically unstable rotor stages p 265 A85-21866 Metallurgical and mechanical phenomena due to rubbing
- of titanium against sintered powder Nichrome p 291 A85-22281
- DUCTED FLOW
- Calculation of friction and heat transfer in turbulent flow of a compressible gas in a plane duct
- p 291 A85-22114 Shock waves in transonic flows at moderate Reynolds Number p 238 N85-16823 DURABILITY
- F-16 force management, yesterday, today p 254 N85-15674 tomorrow Design and test requirements for development of today's
- engines p 266 N85-15737 Overview of the AGARD SMP activities on turbine engine materials technology in the 1972 - 1982 period
- p 266 N85-15738 DUST COLLECTORS
- Analysis of a split-flow inertial particle separator by finite elements --- for helicopter gas turbine engine p 231 A85-21845
- DYNAMIC CHARACTERISTICS Prediction of dynamic stall characteristics using
- dvanced non-linear panel methods p 239 N85-16836 [AD-A148453] DYNAMIC CONTROL
- Aileron effectiveness for a subsonic transport model with high-aspect-ratio supercritical wing [NASA-TM-85674] p 235 N85-15695
- DYNAMIC LOADS Evaluation of operational loads to verify structural
- desian p 254 N85-15677 TUTOR (CL-41A) tail flight load survey
- p 254 N85-15678

- Structural Usage Monitoring System p 292 N85-15680 Tornado: (SUMS) Flight parameters recording for structure fatigue life p 292 N85-15682 monitoring USAF approach to airborne structural data recording:
- Airborne Data Acquisition Multifunction System (ADAMS) p 292 N85-15683 DYNAMIC MODELS
- Analytical modeling of circuit aerodynamics in the new NASA Lewis wind tunnel
- [NASA-TM-86912] p 234 N85-15688 DYNAMIC RESPONSE
- Flutter control with unsteady aerodynamic models p 270 N85-15753 [ATLA147858] DYNAMIC STABILITY
- Effects of turbulence and viscosity variation on the dynamic coefficients of fluid film journal bearings ASME PAPER 84-TRIB-81 p 289 A85-21283
- Analysis and testing for rotordynamic coefficients of turbulent annular seals with different directionally-homogeneous surface-roughness treatment for rotor and stator elements
- [ASME PAPER 84-TRIB-31] p 289 A85-21293 Skirt material effects on air cushion dynamic heave stability p 307 A85-21840
- DYNAMIC STRUCTURAL ANALYSIS
- Structural analysis and testing of ACAP subcomponents --- Advanced Composite Airframe Program
- D 251 A85-21384 Aeroelastic analysis and the identification of flight loads p 254 N85-15679 --- Mirage 2000 aircraft
- DYNAMICAL SYSTEMS A generalized stability criterion for nonlinear dynamic systems --- modeling aircraft roll maneuvers
- p 300 A85-19586 [AIAA PAPER 85-0202]

E

ECONOMIC ANALYSIS

- cost and benefits optimization model for fault-tolerant aircraft electronic systems
- p 293 N85-15993 [NASA-CR-166043] ECONOMIC IMPACT
- The embedded test (BIT): Impact on the total cost of p 202 N85-16734 noissession FICIENCY
- Numerical optimization design of advanced transonic wina configurations
- AA PAPER 85-0424] p 248 A85-19739 EJECTION SEATS
 - Windblast leg protector assembly
- [AD-D011376] p 242 N85-15700 Powered articulated headrest system p 254 N85-15710 [AD-D011353]
- S-3A ballast block final design and engineering tests [AD-A147685] p 243 N85-16842 A Generalized Escape System Simulation (GESS)
- computer program. Volume 2: GESS programmer's manual, version 2 p 243 N85-16845 [AD-A148363] EJECTORS
- A method for calculating the performance of ejector p 287 A85-20232 nozzles ELASTIC PLATES
- Aeroelastic stability and vibration of layered plates and p 288 A85-20472 cylindrical shells ELASTOHYDRODYNAMICS
- Calculation of the hydrodynamic characteristics of p 290 A85-22113 polyplanes ELASTOMERS
- Flexible matrix composites applied to bearingless rotor p 281 A85-21389 systems
- **ELÉCTRIC FIELD STRENGTH**
- The lightning threat to aerospace vehicles [AIAA PAPER 85-0094] p 240 p 240 A85-19516 ELECTRIC FILTERS
- EMI (electromagnetic interference) filter capacitor unit [AD-D011392] p 293 N85-15941 ELECTRIC MOTORS
- Design and test of a four channel motor for electromechanical flight control actuation
- [NASA-CR-171838] p 297 N85-17294 ELECTRICAL MEASUREMENT
- The lightning threat to aerospace vehicles p 240 A85-19516 [AIAA PAPER 85-0094] ELECTRO-OPTICS
 - Stereo Electro-optical Tracking System (SETS)
- [NASA-CR-172471] p 295 N85-16098 Evaluation of nose, roof, and mast mounted sensor platforms for piloting and sighting, integrated in future combat helicopters p 260 N85-16808
- EMI (electromagnetic interference) filter capacitor unit
- p 293 N85-15941 [AD-D011392]

ELECTROMECHANICAL DEVICES

The hydraulic and electrohydraulic elements used in p 287 A85-19886 flight simulators Systems study for an Integrated Digital-Electric Aircraft (IDÉA)

SUBJECT INDEX

p 255 N85-15714

p 277 N85-15762

p 277 N85-15762

p 247 A85-19584

p 205 A85-19264

p 275 A85-19661

p 265 N85-15729

p 263 A85-19801

p 263 A85-19877

p 264 A85-21466

p 262 A85-19509

p 210 A85-19510

p 262 A85-19615

p 263 A85-19616

p 227 Å85-19851

combustor of AI type

p 264 A85-20235

p 264 A85-20822

p 264 A85-21682

p 268 N85-16875

axial

optimization of the

multistage

- [NASA-CR-3840]
- Design and test of a four channel motor for electromechanical flight control actuation
- Electronic countermeasures
- Equipment for preflight test of an Electronic Countermeasures (ECM) avionic system
 - p 293 N85-15949
- ELECTRONIC EQUIPMENT cost and benefits optimization model for fault-tolerant aircraft electronic systems
- [NASA-CR-166043] p 293 N85-15993 Experience of one UK electronic equipment supplier with bite on engine/flight control systems over the past ten
- p 296 N85-16738 vears **ELECTRONIC EQUIPMENT TESTS**
- Equipment for preflight test of an Electronic Countermeasures (ECM) avionic system
- p 293 N85-15949 ELECTRONIC PACKAGING
- Hardware design techniques --- systems integration for p 244 A85-21459 civil and military aircraft avionics
- Packaging and interconnection for avionics p 290 A85-21460 FUIDTICITY
- Downwash in the plane of symmetry of an elliptically loaded wing
- p 235 N85-15693 [NASA TP.2414] EMBEDDED COMPUTER SYSTEMS
- Designing a priority driven multi-frame rate flight everitive [AIAA PAPER 85-0309] p 268 A85-19656
- The embedded test (BIT): Impact on the total cost of p 202 N85-16734 noiseession
- ENERGY ABSORPTION

[AD-A147893]

[AD-A147893]

ENERGY CONSUMPTION

ENERGY REQUIREMENTS

AIAA PAPER 85-02001

[NASA-TM-85916]

[AIAA PAPER 85-0255]

[AIAA PAPER 85-0083]

[AIAA PAPER 85-0086]

[AIAA PAPER 85-0252]

intelligence techniques

turbojet engine

[PNR-90226]

[AIAA PAPER 85-0253]

A procedure for

aerothermodynamic design

compressors --- German thesis

Modern military engines. II

Some improvements on an annular

The aircraft engine of the future

military and commercial aircraft

advanced gas turbine engine design

ENGINE CONTROL

ENGINE COOLANTS

ENGINE DESIGN

forced mivers

Maximum final energy chandelle

methods for modelling internal flows [ONERA, TP NO. 1984-150]

propulsion system and adverse weather testing [AIAA PAPER 85-0314] p 275 A

engine control system of an F-15 airplane

engine control system on an F-15 airplane

Microprocessor control of turboprop engines

ENGINE AIRFRAME INTEGRATION

Energy absorbing qualities of fiber reinforced plastic tubes p 282 A85-21393 ENERGY CONSERVATION Hangar heating and energy conservation manual

Hangar heating and energy conservation manual

A comparison of different three-dimensional singularity

The Altitude Wind Tunnel (AWT) - A unique facility for

Predicted performance benefits of an adaptive digital

Predicted performance benefits of an adaptive digital

Trends in digital engine control - Integration of propulsion

Influence of blowing rate and injection angle on the

Computational thermo-fluid dynamics contributions to

Three-dimensional inviscid flow analysis of turbofan

Aircraft turbojet engine modeling using artificial

the

Prediction of performance of aircraft gas turbines

of

Real gas effects in advanced technology engines

performance of a film-cooled blade p 265 A85-22231

control with flight control and avionic systems in future

ENGINE INLETS

- Computational particle trajectory analysis on a 3-dimensional engine inlet [AIAA PAPER 85-0411] p 222 A85-19732
- Icing tunnel tests of Electro-Impulse De-Icing of an engine inlet and high-speed wings
- [AIAA PAPER 85-0466] o 241 A85-20872 Analysis of a split-flow inertial particle separator by finite elements --- for helicopter gas turbine engine
- p 231 A85-21845 Effect of steady-state temperature distortion on inlet flow

to a high-bypass-ration turbofan engine [NASA-TM-86896] p 265 N85-15725 ENGINE NOISE

An experimental study of sound attenuation characteristics in circular ducts with lined radial baffles [AIAA PAPER 85-0079] p 304 A85-19505 ENGINE PARTS

- Army, NASA researching needs for future engine p 263 A85-20060 components The challenge from ceramics to metals in the gas turbine
- nd related areas p 280 A85-20150 Overview of the AGARD SMP activities on turbine engine and related areas materials technology in the 1972 - 1982 period
- p 266 N85-15738 Cumulative damage modeling of fatigue crack growth
- p 267 N85-15741 Problems and possibilities for life extension in gas turbine p 267 N85-15742

Disc fatigue life predictions for gas turbine engines p 267 N85-15743

Life prediction at high temperature under multiaxial ENGINE TESTING LABORATORIES

Frequency response of a jet engine test facility air supply system

- [AIAA PAPER 85-0053] p 273 A85-19485 The Altitude Wind Tunnel (AWT) - A unique facility for propulsion system and adverse weather testing
- [AIAA PAPER 85-0314] p 275 A85-19661 Flowfield analysis of low bypass ratio test cells p 265 A85-21839

ENGINE TESTS

- Benefits and costs of powered engine simulation at low speeds [AIAA PAPER 85-0381] p 263 A85-19710
- A universal turboshaft engine test cell Design considerations and model test results
- p 275 A85-19711 [AIAA PAPER 85-0382] Correlation and analysis of oil flow data for an air-breathing missile model
- [AIAA PAPER 85-0452] p 224 A85-19761 AIAA PAPEH 85-0492 j p 22-7 .000 Big wind at Tullahoma --- USAF's new aeropropulsion ast facility p 275 A85-20122 test facility Temperature distortion generator for turboshaft engine
- testing [NASA-TM-83748] p 200 N85-15658 Engine Cyclic Durability by Analysis and Testing
- p 266 N85-15733 FAGARD-CP-3681 Accelerated Mission Endurance Testing (AMET) p 266 N85-15736 Design and test requirements for development of today's
- p 266 N85-15737 engines Integrated exhaust gas analysis system for aircraft
- turbine engine component testing [NASA-TP-2424] p 295 N85-16100 Laboratory simulation of smoke reduction from aircraft
- engine test cell exhaust using a fluidized bed filter p 278 N85-16886 [AD-A148600]

ENTROPY Radiative entropy production [AIAA PAPER 85-0408] p 304 A85-19729

- ENVIRONMENT EFFECTS Installation restoration program. Phase 2: Stage 1 problem confirmation study, Duluth International Airport
- Duluth, Minnesota [AD-A148318] p 278 N85-16885 ENVIRONMENT SIMULATION
- The Altitude Wind Tunnel (AWT) A unique facility for propulsion system and adverse weather testing
- [AIAA PAPER 85-0314] p 275 A85-19661 ENVIRONMENTAL SURVEYS
- Helicopter noise survey performed at Las Vegas, Nevada, 19-21 January, 1984
- p 305 N85-16593 [AD-A147392] Noise measurement flight test: Data-analyses Aerospatiale AS 350D AStar helicopter
- p 306 N85-17672 (AD-A1484961 ENVIRONMENTAL TESTS
- Environmental test capabilities of the Air Force McKinley **Climatic Laboratory** (AIAA PAPER 85-0089) p 273 A85-19512
- EPOXY COMPOUNDS Preliminary evaluation of an improved flammability test
- method for aircraft materials (FAA-CT-84-22) p 242 N85-16840

EPOXY RESINS

- All-composite Airbus empennage p 284 N85-15931 EQUATIONS OF MOTION
- More than you want to know about maximum likelihood estimation
- [NASA-TM-85905] p 270 N85-15752 Optimum performance parameters for ski-jump operations of USAF fighter aircraft
- [AD-A148532] p 258 N85-16867 EQUATIONS OF STATE
- On the variety of type discrimination criteria of equations on S1 and S2 stream surfaces in turbomachine p 228 A85-20238
- EQUIPMENT SPECIFICATIONS
- Mi-28 The Soviets create Havoc p 250 A85-20147 ERROR ANALYSIS
- Calculation of confined swirling flows [AIAA PAPER 85-0060] p 285 A85-19491
- A linearly correcting method of deviation function for considering the influence of pressure on the thermodynamic properties of combustion gas p 304 A85-20236
- ESCAPE SYSTEMS
- A Generalized Escape System Simulation (GESS) computer program. Volume 2: GESS programmer's manual, version 2
- [AD-A148363] p 243 N85-16845 ESTIMATING
- Research on optimal control, stabilization and computational algorithms for aerospace applications [NASA-CR-174318] p 303 N85-1 p 303 N85-17603
- EULER EQUATIONS OF MOTION Euler solution of axisymmetric flows about bodies of revolution using a multigrid method
- AIAA PAPER 85-00171 p 206 A85-19460 A comparison of Euler and Navier-Stokes solutions for
- supersonic flow over a conical delta wing (AIAA PAPER 85-0111) p 210 A85-19526 Solution of the unsteady Euler equations for fixed and
- rotor wing configurations [AIAA PAPER 85-0120] o 211 A85-19531 Three-dimensional Euler solutions with grid embedding
- [AIAA PAPER 85-0121] p 211 A85-19532 A comparison of finite volume flux vector splittings for
- the Euler equations [AIAA PAPER 85-01221 p 211 A85-19533 Numerical solution of the Euler equations for high-speed,
- blended wing-body configurations p 211 A85-19534 [AIAA PAPER 85-0123] Euler calculations for multielement airfoils using
- Cartesian grids [AIAA PAPER 85-0291] p 218 A85-19641 Numerical solution of the two-dimensional Euler equations by second-order upwind difference schemes [AIAA PAPER 85-0292] p 218 A85-19642
- Multigrid solution of the Euler equations using implicit
- [AIAA PAPER 85-0293] p 218 A85-19643 A relaxation approach to patched-grid calculations with the Euler equations
- (AIAA PAPER 85-02951 p 218 A85-19644 A three-dimensional Navier-Stokes/Euler code for
- blunt-body flow computations [AIAA PAPER 85-0361] p 220 A85-19696
- Split-flux-vector solutions of the Euler equations for three-dimensional configurations [AIAA PAPER 85-0434] p 223 A85-19747
- Finite volume solution of the two-dimensional Euler equations on a regular triangular mesh [AIAA PAPER 85-0435]
- p 223 A85-19748 Solution method for a hovering helicopter rotor using
- the Euler equations [AIAA PAPER 85-0436] p 223 A85-19749 Evaluation of vortex wake predictions in the SWINT
- [AIAA PAPER 85-0450] p 224 A85-19759
- Grid adaptation for the 2-D Euler equations [AIAA PAPER 85-0484] p 225 A85-19781 An implicit, conservative, zonal-boundary scheme for
- Euler equation calculations [AIAA PAPER 85-0488] p 226 A85-19785 Simulation of transonic three-dimensional nacelle/inlet
- flowfields using an Euler/Navier-Stokes algorithm p 226 A85-19798 [AIAA PAPER 85-0084] Euler computations of AGARD Working Group 07 airfoil
- test cas [AIAA PAPER 85-0018] p 229 A85-20851 Finite element solutions of Euler equations for lifting
- airfoils p 230 A85-20864 [AIAA PAPER 85-0294]
- A numerical simulation of the NFAC (National Full-scale Aerodynamics Complex) open-return wind tunnel inlet flow
- [AIAA PAPER 85-0437] p 230 A85-20869 Artificial dissipation models for the Euler equations [AIAA PAPER 85-0438] p 231 A85-20870

A comparative study of the nonuniqueness problem of the potential equation [NASA-TP-2385]

FABRICATION

- p 235 N85-15694 EUROPEAN AIRBUS
- Advanced technology The key to European competitiveness --- in Airbus industry
- p 200 A85-21680 p 284 N85-15931 All-composite Airbus empennage
- EVALUATION Performance evaluation of A-10 aircraft mainteance units and aircraft using constrained facet analysis
- p 201 N85-15660 (AD-A1469551 Flight service evaluation of advanced composite ailerons
- on the L-1011 transport aircraft p 284 N85-17049 [NASA-CR-172483]
- EVASIVE ACTIONS The use of local functionals to construct a circumvention
- maneuver in game problems of evasion p 302 A85-22374
- EXHAUST EMISSION
 - Impact of aircraft emissions on air quality in the vicinity of airports. Volume 3: Air quality and emission modeling noode
- [AD-A147951] p 299 N85-17435 EXHAUST FLOW SIMULATION
 - A novel experimental facility for conducting jet impingement studies related to VTOL aircraft [AIAA PAPER 85-0052] p 209 A85-19484
- EXHAUST GASES Integrated exhaust gas analysis system for aircraft turbine engine component testing
- [NASA-TP-2424] p 295 N85-16100
- Laboratory simulation of smoke reduction from aircraft engine test cell exhaust using a fluidized bed filter p 278 N85-16886 [AD-A148600]
- Impact of aircraft emissions on air quality in the vicinity of airports. Volume 3: Air quality and emission modeling needs
- p 299 N85-17435 [AD-A147951] EXHAUST NOZZLES
 - A universal turboshaft engine test cell Design considerations and model test results
 - [AIAA PAPER 85-0382] D 275 A85-19711 Prediction of performance of aircraft gas turbines p 264 A85-21682
- EXPERIMENT DESIGN

weapons

[AD-A147188]

EXTERNAL TANKS

[AD-A148091] EXTREMUM VALUES

F-15 AIRCRAFT

gradient of lift force

[AIAA PAPER 85-0255]

(NASA-TM-85916)

F-16 AIRCRAFT

tomorrow

F-8 AIRCRAFT

FABRICATION

display systems

[NASA-TM-84914]

[NASA-TM-86353]

[AIAA PAPER 85-0270]

fairings drag determination

- Selection of rational models in the optimal planning of p 288 A85-20460 aeromechanical experiments EXPERT SYSTEMS
- Design of aerodynamic bodies using artificial intelligence/expert system technique [AIAA PAPER 85-0112] p 301 A85-20856
- **EXTERNAL STORES** Bomb rack technology - Keeping up with advanced

Inexpensive calibrations for the influence function

UH-60A external stores support system fixed provision

Preliminary airworthiness evaluation AH-1S (MC)

Extremum problem concerning a wing with a maximum

An extremum problem concerning the shape of a body

Predicted performance benefits of an adaptive digital

p 253 N85-15666 Predicted performance benefits of an adaptive digital

Contrast sensitivity performance assessment of HUD

F-16 force management, yesterday, today and

of revolution in supersonic gas flow p 234 A85-22371

F

method using the interference distributed loads code --

for prediction of store loads in aircraft flow fields

helicopter with external fuel tanks installed

ngine control system on an F-15 airplane

The F-15 flight loads tracking program

engine control system of an F-15 airplane

F-8 refueling boom ground vibration test

Advances in composites technology

p 246 A85-19274

p 247 A85-19623

p 256 N85-15719

p 258 N85-16865

p 234 A85-22370

p 263 A85-19801

p 265 N85-15729

p 259 A85-21593

p 254 N85-15674

p 255 N85-15713

p 284 N85-17048

A-15

FACTORIZATION

Investigation on experimental techniques to detect, locate and a quantify gear noise in helicopter transmissions

[NASA-CR-3847] p 305 N85-17667 FACTORIZATION

Recent improvements in efficiency, accuracy, and convergence for implicit approximate factorization algorithms — computational fluid dynamics [AIAA PAPER 85-0360] p 230 A85-20868

FAILURE ANALYSIS Utilization of analytical equipment in design and process problems solution and failure analysis of composites

p 261 A65-21390 Built-in-test for first line testing p 202 N85-16739

Advances in composites technology [NASA-TM-86353] p 284 N85-17048 FAIRINGS

Passive control effects on flow separation around a protuberance at high subsonic speed ---- for optical propagation quality enhancement to and from airborne platforms

[AIAA PAPER 85-0351] p 220 A85-19690 UH-60A external stores support system fixed provision fairings drag determination

[AD-Ă147188] p 256 N85-15719 FANS

Determination of surging line of two-spool axial flow compressor with cropped fan stages at low speed by use of parallel compressor theory p 264 A85-20242 FASTENERS

The influence of fastener flexibility on load transfer and fatigue life predictions for multirow bolted and riveted joints --- aircraft structures

- [LBF-FB-172/84] p 296 N85-16219 FATIGUE (MATERIALS) Operational Loads Data
- [AGARD-CP-375] p 201 N85-15664 Operational loads measurement: A philosophy and its implementation p 253 N85-15665
- The F-15 flight loads tracking program p 253 N85-15666 Structural load measurements on a Northrop NF-5A
- p 253 N85-15667 Operational loads data evaluation for individual aircraft fatigue monitoring p 253 N85-15669
- Monitoring engine thermal stresses p 266 N85-15735

FATIGUE LIFE

- Loading characteristics of VTOL aircraft and their effect on the remaining life of the aircraft p 250 A85-20469 Operational loads measurement: A philosophy and its implementation p 253 N85-15665
- The F-15 flight loads tracking program p 253 N85-15666
- Navy operational loads data sources and systems p 253 N85-15668 Structural flight load measurement demonstration of
- structural integrity p 254 N85-15670 Advanced fatigue monitoring on service aircraft p 292 N85-15671
- Flight parameters recording for structure fatigue life monitoring p 292 N85-15682 Disc fatigue life predictions for gas turbine engines
- p 267 N85-15743 Experiences with the material bevaviour and high temperature low cycle fatigue life prediction of the IN 738 blading alloy p 292 N85-15746 The influence of fastener flexibility on load transfer and
- fatigue life predictions for multirow bolted and riveted joints --- aircraft structures [LBF-FB-172/84] p 296 N85-16219
- FATIGUE TESTS Development of a fatigue crack propagation model of
- Incoloy 901 p 280 A85-20758 Fatigue crack growth behavior of 7XXX aluminum alloys under simple variable amplitude loading
- p 280 A85-20759 Interpretation of fatigue crack growth in aluminium alloys under programmed block loading p 281 A85-20790
- Advanced fatigue monitoring on service aircraft p 292 N85-15671 Design and test requirements for development of today's
- engines p 266 N85-15737 Engine cyclic durability by analysis and material testing p 267 N85-15744 FAULT TOLERANCE
- Optimal maintenance center inventories for fault-tolerant repairable systems p 301 A85-21548 cost and benefits optimization model for fault-tolerant
- aircraft electronic systems [NASA-CR-166043] p 293 N85-15993 Investigating version dependence in fault-tolerant software p 302 N85-16749 Research on optimal control, stabilization and
- computational algorithms for aerospace applications [NASA-CR-174318] p 303 N85-17603

A-16

FAULT TREES

- Avionics fault tree analysis and artifical intelligence for future aircraft maintenance p 203 N85-16755
 FEASIBILITY ANALYSIS
- Modular simulators, their feasibility, design, and procurement
- [AIAA PAPER 85-0312] p 274 A85-19659 FEATHERING
- Study to eliminate ground resonance using active controls
- [NASA-CR-166609] p 255 N85-15715 FEEDBACK CONTROL
 - Flutter control with unsteady aerodynamic models [AD-A147858] p 270 N85-15753
- Multivariable flight control with time-scale separation [NASA-CR-174320] p 268 N85-16873 Time series analysis of closed-loop pilot vehicle dynamics p 271 N85-16876
- Research on optimal control, stabilization and computational algorithms for aerospace applications [NASA-CR-174318] p 303 N85-17603
- FIBER COMPOSITES
- A thermoplastic polyimidesulfone --- synthesis of processable and solvent resistant system p 282 A85-21483
- FIBER OPTICS
- Helicopter Guidance and Control Systems for Battlefield Support
- [AGARD-CP-359] p 204 N85-16797 FIBER REINFORCED COMPOSITES
- Kevlar aramid fibers vs other fibers for reinforcement of composite structures p 282 A85-21392 System for rapid repair of damaged airfield runways (AD-D011325) p 276 N85-15754
- FIBER STRENGTH Keviar aramid fibers vs other fibers for reinforcement of composite structures p 282 A85-21392
- FIGHTER AIRCRAFT Bomb rack technology - Keeping up with advanced p 246 A85-19274 weapons military New generation tactical airborne communications systems - The interoperability challenge p 244 A85-19275 Combat aircraft: Flight vehicles, power plants, and their p 199 A85-19812 maintenance --- Russian book Forward sweep - The pros and cons p 250 A85-20146 Modern military engines. Il . p 264 A85-20822 STOL technology for conventional flight enhancement [AIAA PAPER 84-2397] p 250 A85-20875 A global technique for aircraft stability and control p 270 A85-21681 analysis Burbank's Blackbirds encompassing SR-71 reconnaissance aircraft and YA-12/12-A interceptors
- p 252 A85-22081 Operational Loads Data [AGARD-CP-375] p 201 N85-15664 Structural load measurements on a Northrop NF-5A p 253 N85-15667 Navy operational loads data sources and systems
- p 253 N85-15668 Structural flight load measurement demonstration of structural integrity p 254 N85-15670
- Display Techniques for Advanced Crew Stations (DTACS). Phase 1: Display techniques study [AD-A146922] p 259 N85-15722
- Computer sizing of fighter laircraft [NASA-TM-86351] p 203 N85-16759
- International aviation (selected articles) [AD-A148704] p 204 N85-16762 Full scale experiments into the use of large eddy breakup
- devices for drag reduction on aircraft p 257 N85-16790 Optimum performance parameters for ski-jump
- operations of USAF fighter aircraft [AD-A148532] p 258 N85-16867
- Advances in composites technology [NASA-TM-86353] p 284 N85-17048
- FILM COOLING Influence of blowing rate and injection angle on the
- performance of a film-cooled blade p 265 A85-22231 FILTRATION Laboratory simulation of smoke reduction from aircraft
- engine test cell exhaust using a fluidized bed filter [AD-A148600] p 278 N85-16886 FINITE DIFFERENCE THEORY
- Full two-dimensional transient solutions of electrothermal aircraft blade deicing
- [AIAA PAPER 85-0413] p 248 A85-19734 Evaluation of vortex wake predictions in the SWINT code
- [AIAA PAPER 85-0450] p 224 A85-19759 A stream function relaxation method for solving transonic S1 stream surface with respect to non-orthogonal curvilinear coordinates p 228 A85-20240

Recent improvements in efficiency, accuracy, and convergence for implicit approximate factorization algorithms -- computational fluid dynamics [AIAA PAPER 85-0360] p 230 A85-20868

An exploratory study of finite difference grids for transonic unsteady aerodynamics

[NASA-TM-84583] p 235 N85-15696 FINITE ELEMENT METHOD

A subdomain finite element method for solving the conservative full potential equation for transonic profile flows — German thesis p 227 A85-19854 Finite element solutions of Euler equations for lifting

airfoils [AIAA PAPER 85-0294] p 230 A85-20864 The development of a finite element model of an aircraft

- vertical stabilizer for vibration analysis p 290 A85-21683
- Computation of choked and supersonic turbomachinery flows by a modified potential method p 232 A85-21859
- Universal matrices to obtain thermal load vectors for the family of anisotropic plane triangular finite elements p 291 A85-22232
- FINITE VOLUME METHOD A multistage time-stepping scheme for the
- A multistage time-stepping scheme for the Navier-Stokes equations
- [AIAA PAPER 85-0035] p 207 A85-19472 A comparison of finite volume flux vector splittings for
- the Euler equations [AIAA PAPER 85-0122] p 211 A85-19533
- Euler calculations for multielement airfoils using Cartesian grids
- [AIAA PAPER 85-0291] p 218 A85-19641 Split-flux-vector solutions of the Euler equations for
- three-dimensional configurations [AIAA PAPER 85-0434] p 223 A85-19747 Finite volume solution of the two-dimensional Euler
- equations on a regular triangular mesh [AIAA PAPER 85-0435] p 223 A85-19748 Theoretical contributions to transonic flow analysis for transport aircraft
- [BMFT-FB-W-84-036] p 239 N85-16838 FINNED BODIES
- Drag prediction for projectiles and finned bodies in incompressible flow
- [AIAA PAPER 85-0104] p 230 A85-20854 FINS
- Subsonic pressure distributions near a wing-fin juncture on a supersonic arrow-wing configuration with wing-mounted vertical fins
- wing-mounted vertical fins [AIAA PAPER 85-0276] p 217 A85-19628
- Flowfield scaling in sharp fin-induced shock wave/turbulent boundary-layer interaction
- P 232 A85-21857 Repair of composites p 284 N85-17058
- Repair of composites p 284 N85-17058 FIRE CONTROL
- Voice command weapons launching system [AD-D011378] p 293 N85-15940
- FIRE EXTINGUISHERS Flow of nitrogen-pressurized Halon 1301 in fire
- extinguishing systems [NASA-CR-174271] p 242 N85-15701
- Evaluation of aircraft interior panels under full-scale cabin fire test conditions
- [AIAA PAPER 85-0393] p 240 A85-19719 FIRES
- Measurements of the response of transport aircraft ceiling panels to fuel pool fires
- [AIAA PAPER 85-0394] p 240 A85-19720 The thermal response of aircraft cabin ceiling materials
- during a post-crash, external fuel-spill, fire scenario [AIAA PAPER 85-0395] p 241 A85-19721

Solution of the unsteady Euler equations for fixed and

Analysis and testing of the Diamond One wing anti-icing

SFRJ simulator results - Experiment and analysis in cold

Preliminary evaluation of an improved flammability test

Theoretical study of blockage effect of wind-tunnel wall

Experimental investigation of blockage effect of upper

wall of wind-tunnel of wake of two-dimensional flat plate

on wake of two-dimensional flat plate normal to plane

p 211 A85-19531

p 286 A85-19735

p 263 A85-19671

p 242 N85-16840

p 272 A85-19402

p 272 A85-19403

FIXED WINGS

system

rotor wing configurations

[AIAA PAPER 85-0120]

[AIAA PAPER 85-0414]

flow --- Solid Fuel RamJet

method for aircraft materials

normal to plane boundary

[AIAA PAPER 85-0329]

FLAME STABILITY

FLAMMABILITY

FLAT PLATES

wall

[FAA-CT-84-22]

Critical layer concept	retative	to	hypersonic	boundary
layer stability				
TAIAA DADED 95,03031			n 210 /	85.10652

- Vortex path in the supersonic wake of a rough even p 226 A85-19821 plate --- German thesis
- Experiments on the stability of crossflow vortices in wept-wing flows
- [AIAA PAPER 85-0493] p 231 A85-20873 FLAT SURFACES
- Approximate solution of a nonlinear problem of flow past a thin airfoil profile near a support surface
- p 233 A85-22368 FLEXIBILITY
- The influence of fastener flexibility on load transfer and fatigue life predictions for multirow bolted and riveted joints
- aircraft structures [LBF-FB-172/84] p 296 N85-16219
- FLEXIBLE BODIES Stability of squeeze film damped multi-mass flexible rotor
- bearing systems [ASME PAPER 84-TRIB-45] p 289 A85-21296
- FLIGHT CHARACTERISTICS Effects of aircraft and flight parameters on energy-efficient profile descents in time-based metered
- traffic [NASA-CR-172338-ADD] o 245 N85-15706
- Airworthiness and flight characteristics test of the RC-12D Guardrail V
- [AD-A148046] p 258 N85-16864 Realization and testing of an experimental color display system for general aviation helicopters and aircraft
- p 262 N85-16872 [BMFT-FB-W-84-042]
- Time series analysis of closed-loop pilot vehicle ynamics p 271 N85-16876 dynamics FLIGHT CONDITIONS
- Clear turbulence forecasting Towards a union of art and science
- [AIAA PAPER 85-0014] o 298 A85-19458 Automated visibility measurements for airports
- p 274 A85-19577 [AIAA PAPER 85-0191] Scaling laws for testing of high lift airfoils under heavy rainfall
- p 216 A85-19617 [AIAA PAPER 85-0257] FLIGHT CONTROL
- Writing executable assertions to test flight software (SU-CRC-TR-84-14) p 301 A85-21973 Aircraft thrust control scheme for terrain following
- system [AD-D011387] p 255 N85-15711 Effect of aerodynamic and angle-of-attack uncertainties on the May 1979 entry flight control system of the Space
- Shuttle from Mach 8 to 1.5 [NASA-TP-2365] p 280 N85-15778
- Literature review of voice recognition and generation technology for Army helicopter applications
- [AD-A146878] p 293 N85-15954 cost and benefits optimization model for fault-tolerant aircraft electronic systems
- [NASA-CR-166043] p 293 N85-15993 Experience of one UK electronic equipment supplier with bite on engine/flight control systems over the past ten vears p 296 N85-16738
- Helicopter Guidance and Control Systems for Battlefield Support [AGARD-CP-359] p 204 N85-16797
- Integrated digital/electric aircraft concepts study p 257 N85-16861 [NASA-CR-3841]
- Reference energy-altitude descent guidance: Simulator evaluation --- aircraft descent and fuel conservation
- [NASA-TP-2383] p 261 N85-16868 Multivariable flight control with time-scale separation
- [NASA-CR-174320] p 268 N85-16873 Design and test of a four channel motor for electromechanical flight control actuation
- [NASA-CR-171838] p 297 N85-17294
- FLIGHT HAZARDS Status of warm fog dispersal research
- [AIAA PAPER 85-0010] p 272 A85-19456 The Federal Aviation Administration's Engineering and Development Aircraft Icing Program
- [AIAA PAPER 85-0015] p 247 A85-19459 Safety - Meteorological data vital for simulator training [AIAA PAPER 85-0091] p 240 A85-19513 Radar for storm forecasting and weather hazard
- warning [AIAA PAPER 85-0092] p 299 A85-19514 The development of mathematical modelling techniques
- for helicopter rotor icing IAIAA PAPER 85-03361 p 240 A85-19679 Experimental aerodynamic characteristics of an NACA
- 0012 airfoil with simulated ice p 252 A85-21844 FLIGHT INSTRUMENTS LPI-radar for helicopter obstacle warning
 - p 297 N85-16810

FLIGHT LOAD RECORDERS **Operational Loads Data**

- [AGARD-CP-375] p 201 N85-15664 Operational loads measurement: A philosophy and its
- p 253 N85-15665 implementation The F-15 flight loads tracking program

- p 253 N85-15666 Operational loads data evaluation for individual aircraft
- fatique monitoring p 253 N85-15669 US Army helicopter operational flight loads p 254 N85-15675
- Flight parameters recording for structure fatigue life p 292 N85-15682 monitoring USAF approach to airborne structural data recording:
- Airborne Data Acquisition Multifunction System (ADAMS) p 292 N85-15683
- FLIGHT MANAGEMENT SYSTEMS
- Speech recognition making progress Direct voice input is a promising infant p 244 A85-19183 The Mission Oriented Terminal Area Simulation (MOTAS)
- [AIAA PAPER 85-0308] p 274 A85-19655 Designing a priority driven multi-frame rate flight
- executive [AIAA PAPER 85-0309] p 268 A85-19656 Software design methods --- for civil and military aircraft
- avionics systems p 301 A85-21457 A design methodology for integrated avionic system:
- p 301 A85-21458 Trends in digital flight control systems
- p 269 A85-21465 Trends in digital engine control - Integration of propulsion control with flight control and avionic systems in future
- p 264 A85-21466 military and commercial aircraft FLIGHT MECHANICS
- Experimental methods for wind-tunnel flight-mechanics investigations using dynamically similar aircraft models p 249 A85-19836 German thesis Flight test of the Open Loop Gust Alleviation (OLGA)
- system (BMFT-FR-W-84-038) p 271 N85-16881
- FLIGHT OPTIMIZATION Maximum final energy chandelle
- p 247 A85-19584 AIAA PAPER 85-0200] FLIGHT PATHS
- A three-dimensional Kalman filter for short observation times to extrapolate flight trajectories --- German thesis
- p 301 A85-19835 of aircraft and flight parameters on Effects energy-efficient profile descents in time-based metered traffic
- [NASA-CR-172338-ADD] p 245 N85-15706 Predicted performance benefits of an adaptive digital engine control system of an F-15 airplane
- p 265 N85-15729 [NASA-TM-85916] Investigation of semiautomatic aircraft control processes employing time redundancy in on-board digital trajectory
- p 270 N85-16048 control computers FLIGHT RECORDERS Identification of vortex-induced clear air turbulence using
- airline flight records p 299 A85-21843 FLIGHT SAFETY
- A summary of NASA's research on the fluid ice protection system
- [AIAA PAPER 85-0467] p 241 A85-19768 FLIGHT SIMULATION
- Calculation of the exchange ratio for the Adaptive Maneuvering Logic program [AIAA PAPER 85-0311]
- p 199 A85-19658 Characteristic motions for simulation of post-stall manoeuvres and flight instabilities p 269 A85-21679 Nonlinear simulation of flight along wind compensating
- curved glidepaths p 245 A85-21838 NyKINM, a further development of KINM 22 --- simulation
- of a robot attack on an aircraft [FOA-C-20559-D8(E3)] p 256 N85-15720 Advanced flight simulation for helicopter development
- p 277 N85-16815 Assessment of simulation fidelity using measurements
- of piloting technique in flight p 278 N85-16817 FLIGHT SIMULATORS
- Safety Meteorological data vital for simulator training [AIAA PAPER 85-0091] p 240 A85-19513 Modular simulators, their feasibility, design, and nnocurement
- [AIAA PAPER 85-0312] p 274 A85-19659 History of the development and manufacture of flight
- simulators in Czechoslovakia and the rest of the world p 275 A85-19878 The hydraulic and electrohydraulic elements used in
- flight simulators p 287 A85-19886 Reference energy-altitude descent guidance: Simulator evaluation --- aircraft descent and fuel conservation
- [NASA-TP-2383] p 261 N85-16868

FLOW C	OEFFICIENTS
FLIGHT STABILITY TESTS Flight test of the Open Loop Gust	Alleviation (OLGA)
[BMFT-FB-W-84-038]	p 271 N85-16881
A comparison of flight test and a for boundary layer transition on a sail	nalytical techniques plane
[AIAA PAPER 85-0075]	p 210 A85-19501
The design and testing of several [AIAA PAPER 85-0275]	joined wing RPV's p 248 A85-19627
[AIAA PAPER 85-0307]	p 248 A85-19677
Analysis and testing of the Diamond system	One wing anti-icing
[AIAA PAPER 85-0414]	p 286 A85-19735
Writing executable assertions to [SU-CRC-TR-84-14]	p 250 A85-20222 test flight software p 301 A85-21973
Flight testing of a wing section	with laminar flow
Structural flight load measuremen	t demonstration of
structural integrity Ground-effect analysis of a jet tran	p 254 N85-15670 sport airplane
[NASA-TM-85920] The UH-1H helicopter icing flight	p 234 N85-15687 test program: An
overview [NASA-TM-86925]	p 242 N85-15702
Flight testing of Litton laser gyro LTN-90 for general aviation	strapdown system
[DFVLR-MITT-84-16]	p 245 N85-15709
Noise measurement flight tes aerospatiale AS-355F TwinStar helici	t: Data-analyses
[AD-A147497]	p 305 N85-16595
Built-in-test for first line testing	p 202 N85-16739
(FFS)	p 257 N85-16818
Development and flight test of a	helicopter compact,
ponable, precision landing system co	p 261 N85-16821
Airworthiness and flight charac RC-12D Guardrail V	teristics test of the
[AD-A148046] Preliminary airworthiness evaluated	p 258 N85-16864 Ntion AH-1S (MC)
[AD-A148091]	p 258 N85-16865
47-d helicopter: Data/analyses	oeing venoi 234/CH
[AD-A148172] Noise measurement flight tes	p 306 N85-17670 t: Data-analyses
Aerospatiale AS 350D AStar helicopt [AD-A148496]	er p 306 N85-17672
Noise measurement flight test: Dat	a-analyses, Sikorsky
S-76A helicopter [AD-A148525]	p 306 N85-17673
FLIGHT TIME Calculation of the minimum-time lo	op maneuver for jet
aircraft FLIGHT TRAINING	p 269 A85-19876
Directions of the West German M	Ainistry of Transport
for education and control of airline p chapters 2 and 12)	ersonnel (section 3, p 243 N85-16848
Directions of the West German N	linistry of Transport
for education and control or airline p	personnel, Report 6;
FLIGHT VEHICLES	p 244 1100-10040
A parallel quasi-linearization algoretraiectory optimization	rithm for air vehicle
[AIAA PAPER 85-0498]	p 279 A85-19792
Some features of two-dimensional	turbulent separated
TIOWS [AIAA PAPÉR 85-0178]	p 214 A85-19570
Measurements of water film cha surfaces from wind-tunnel tests wit	racteristics on airfol h simulated heavy
(AIAA PAPER 85-0259)	p 274 A85-19618
The distortion of a supersonic turb by bulk compression and surface cu	ulent boundary layer Ivature
[AIAA PAPER 85-0299]	p 218 A85-19648
Effect of inlet and outlet flow co	nations on the flow

- p 228 A85-20241 Scaling of airfoil self-noise using measured flow arameters p 304 A85-21858 parameters
- Analytical modeling of circuit aerodynamics in the new NASA Lewis wind tunnel [NASA-TM-86912] p 234 N85-15688
- Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems [NASA-CR-174271]
- p 242 N85-15701 FLOW COEFFICIENTS
- Effect of the arrangement of apertures on the gain coefficient during asymmetric gas injection into a Laval p 229 A85-20562 nozzle

FLOW DEFLECTION

FLOW DEFLECTION

- A comparison between theoretical and experimental flow fields of an airfoil with deflected spoiler p 216 A85-19622 [AIAA PAPER 85-0269]
- Approximate solution of a nonlinear problem of flow past a thin airfoil profile near a support surface
- p 233 A85-22368 FLOW DISTORTION

A sensor for detection of unsteady distortion maxima in air intakes

[ONERA, TP NO. 1984-148] p 205 A85-19262 Determination of surging line of two-spool axial flow compressor with cropped fan stages at low speed by use of parallel compressor theory p 264 A85-20242

- Effect of the arrangement of apertures on the gain coefficient during asymmetric gas injection into a Laval p 229 A85-20562 nozzle Flowfield analysis of low bypass ratio test cells
- p 265 A85-21839 FLOW DISTRIBUTION
- An analysis of the flow past an S-shaped rotor by discrete vortex model p 206 A85-19405 An experimental investigation of stator/rotor interaction influence on multistage compressor rotor flow
- p 206 A85-19455 [AIAA PAPER 85-0009] Aerodynamics of an airfoil in ground effect with a jet issuing from its undersurface
- p 207 A85-19461 [AIAA PAPER 85-0019] Turbulent flow around a wing-fuselage type juncture AIAA PAPER 85-0040] p 208 A85-19475 [AIAA PAPER 85-0040]
- Variable-temperature water tunnel for high Reynolds numbers [AIAA PAPER 85-0051] p 273 A85-19483
- Three-dimensional Euler solutions with grid embedding [AIAA PAPER 85-0121] p 211 A85-19532
- Interrelated effects of pitch rate and pivot point on airfoil dvnamic stall [AIAA PAPER 85-0130] p 212 A85-19541
- Three-dimensionality in unsteady flow about a wing p 212 A85-19543 [AIAA PAPER 85-0132] Numerical computation of viscous flowfields about
- multiple component airfoils [AIAA PAPER 85-0167] p 213 A85-19563
- Generalized adaptive-wall wind tunnels p 274 A85-19601 [AIAA PAPER 85-0225]
- Improvements in low Reynolds number testing in the NSWC hypervelocity wind tunnel No. 9 p 274 A85-19602 [AIAA PAPER 85-0226]
- Application of axisymmetric analogue for calculating heating in three-dimensional flows [AIAA PAPER 85-0245] p 216 A85-19611
- A comparison between theoretical and experimental flow fields of an airfoil with deflected spoiler
- [AIAA PAPER 85-0269] p 216 A85-19622 Euler calculations for multielement airfoils using Cartesian grids
- [AIAA PAPER 85-0291] p 218 A85-19641 Recent advances in computational transonic aerodynamics
- [AIAA PAPER 85-0366] p 221 A85-19699 Body flow field simulation and force/moment prediction at transonic speeds
- [AIAA PAPER 85-0423] p 222 A85-19738 Numerical optimization design of advanced transonic wing configurations
- p 248 A85-19739 [AIĂA PAPER 85-0424] Computational aerodynamic design of the Gulfstream IV wing
- p 223 A85-19742 [AIAA PAPER 85-0427] A stream function relaxation method for solving transonic S1 stream surface with respect to non-orthogonal
- p 228 A85-20240 curvilinear coordinates Hypersonic chemically nonequilibrium viscous shock layer on wings with a catalytic surface
- p 229 A85-20561 Application of digital interferogram evaluation techniques to the measurement of three-dimensional flow fields
- [AIAA PAPER 85-0037] p 288 A85-20852 Drag prediction for projectiles and finned bodies in incompressible flow
- [AIAA PAPER 85-0104] p 230 A85-20854 A numerical simulation of the NFAC (National Full-scale Aerodynamics Complex) open-return wind tunnel inlet
- flow p 230 A85-20869 [AIAA PAPER 85-0437] Real-cas flowfields about three-dimensional configurations p 231 A85-21830 Shock-fitting solution of the supersonic flowfield in a rounded internal corner Flowfield scaling in sharp p 232 A85-21856 fin-induced shock wave/turbulent boundary-layer interaction
- p 232 A85-21857 An exploratory study of finite difference grids for transonic unsteady aerodynamics [NASA-TM-84583] p 235 N85-15696

A-18

- Analysis of the flow field about a T-45 using PANAIR [AD-A146811] p 236 N85-15699 Aero-optics experimental techniques
- p 294 N85-16067 [AD-A146755] Contamination and distortion of steady flow field induced
- by discrete frequency in aircraft gas turbines p 294 N85-16073 [AD-A147092]
- Calculation of the velocity field generated by a helicopter main and tail rotors in hover [AD-A147731] p 239 N85-16833
- FLOW EQUATIONS
- Breakdown of the conservative potential equation --- for study of transonic flow [AIAA PAPER 85-0367] p 221 A85-19700
- A subdomain finite element method for solving the conservative full potential equation for transonic profile p 227 A85-19854 flows --- German thesis
- FLOW GEOMETRY
- The effect of phase-difference on the spreading rate of a laminar circular jet under bi-modal excitation
- p 208 A85-19479 [AIAA PAPER 85-0045] The distortion of a supersonic turbulent boundary layer by bulk compression and surface curvature
- p 218 A85-19648 [AIAA PAPER 85-0299]
- Complete three-dimensional flow solution of a cascade incorporating splitter vanes of arbitrary geometry p 228 A85-20230
- Flow behind an attached shock wave in a radiating p 233 A85-22308 gas
- An improved computer model for prediction of axial gas turbine performance losses [NASA-CR-174246]
- p 265 N85-15724 FLOW MEASUREMENT
- Examining the validity of a combustor flow model with I DV
- [AIAA PAPER 85-0055] p 209 A85-19487 Detailed measurements of the flowfield in the vicinity of an airfoil with glaze ice
- [AIAA PAPER 85-0409] p 222 A85-19730 An experimental investigation of the mixing of co-annular
- swirling flows [AIAA PAPER 85-0186] p 230 A85-20862
- Investigations of the longitudinal flow in corner configurations in the hypersonic regime. II Corners p 232 A85-22146 between swept wedges
- Turbulence measurement interferometer apparatus [AD-D011377] p 295 N85-16156 FLOW STABILITY
- The effect of phase-difference on the spreading rate of a laminar circular jet under bi-modal excitation
- p 208 A85-19479 [AIAA PAPER 85-0045] Investigation of nonlinear effects in the instabilities and noise radiation of supersonic jets
- [AIAA PAPER 85-0081]
- p 304 A85-19507 p 227 A85-20074 Survey on jet instability theory Experiments on the stability of crossflow vortices in ept-wing flows
- [AIAA PAPER 85-0493] p 231 A85-20873 Modes of shock-wave oscillations on spike-tipped p 232 A85-21855 dipa
- FLOW THEORY A theory for the core of a three-dimensional leading-edge
- [AIAA PAPER 85-0108] p 210 A85-19524 The full-approximation method in the theory of transonic
- p 233 A85-22367 FLOW VELOCITY
- An experimental investigation of an airfoil undergoing rge amplitude pitching motions
- [AIAA PAPER 85-0039] p 207 A85-19474 A Fourier Transform method for calculating velocity rofiles on airfoils
- **FAIAA PAPER 85-02081** p 215 A85-19592 p 227 A85-20074 Survey on jet instability theory A fast algorithm for solving the conservative transonic
- S1 full potential equation employing non-orthogonal curvilinear coordinates and non-orthogonal velocity p 228 A85-20239 components
- The universal nature of zero-crossing time and velocity ales in turbulent shear flows p 232 A85-21851 Optimal control of flow of a viscous incompressible
- fluid p 290 A85-22105 FLOW VISUALIZATION
- An experimental investigation of an airfoil undergoing large amplitude pitching motions
- [AIAA PAPER 85-0039] p 207 A85-19474 Flow visualization of lateral jet injection into swirling crossflow
- [AIAA PAPER 85-0059] p 209 A85-19490 A study of the flow recirculation problems within an anechoic hover chamber
- p 273 A85-19497 [AIAA PAPER 85-0071]
- A comparison of flight test and analytical techniques for boundary layer transition on a sailplane [AIAA PAPER 85-0075] p 210 A85-19501

- Flow visualization of high angle of attack vortex wake structures [AIAA PAPER 85-0102] p 286 A85-19520 Interrelated effects of pitch rate and pivot point on airfoil dvnamic stall
- [ÁIAA PAPER 85-0130] p 212 A85-19541 Three-dimensionality in unsteady flow about a wing [AIAA PAPER 85-0132] p 212 A85-19543 Improvements in low Reynolds number testing in the
- NSWC hypervelocity wind tunnel No. 9 [AIAA PAPER 85-0226] p p 274 A85-19602 Aerodynamics of an aspect ratio 8 wing at low Reynolds
- numbers [AIAA PAPER 85-0278] p 217 A85-19630
- Passive control effects on flow separation around a protuberance at high subsonic speed --- for optical propagation quality enhancement to and from airborne platforms
- p 220 A85-19690 AIAA PAPER 85-03511 Visualization of the spanwise vortex structure in the starting flow behind an airfoil
- [AIAA PAPER 85-0447] p 224 A85-19756 Correlation and analysis of oil flow data for an
- air-breathing missile model [AIAA PAPER 85-0452] p 224 A85-19761
- Unsteady pressure measurements on a biconvex airfoil in a transonic oscillating cascade [NASA-TM-86914] p 234 N85-15689
- FLOWMETERS
- Flow measurement device [AD-D011432] p 298 N85-17369
- FLUID DYNAMICS Analysis and testing for rotordynamic coefficients of
- turbulent annular seals with different, directionally-homogeneous surface-roughness treatment for rotor and stator elements ASME PAPER 84-TRIB-311 p 289 A85-21293
- FLUID FILMS
- Measurements of water film characteristics on airfol surfaces from wind-tunnel tests with simulated heavy rain
- [AIAA PAPER 85-0259] p 274 A85-19618
- Effects of turbulence and viscosity variation on the dynamic coefficients of fluid film journal bearings p 289 A85-21283 [ÁSME PAPER 84-TRIB-8]
- FLUID FILTERS

[AD-A147858]

surfaces

FOG DISPERSAL

FORECASTING

parts requirements

[AD-B0881466L]

[AD-A147091]

[AD-A148624]

manual, addendum 1

[AD-A147911]

FORGING

FORTRAN

FLY BY WIRE CONTROL

[AIAA PAPER 85-0010]

FLUTTER ANALYSIS

- Laboratory simulation of smoke reduction from aircraft engine test cell exhaust using a fluidized bed filter [AD-A148600] p 278 N85-16886
- FLUID MECHANICS An update of the Canada/USA augmentor-wing

Subsonic wing rock of slender delta wings (AIAA PAPER 85-0198) p 214

Optimization of flutter characteristics

vertical stabilizer for vibration analysis

Status of warm fog dispersal research

- p 257 N85-16781 project FLUID-SOLID INTERACTIONS
- Calculation of the hydrodynamic characteristics of p 290 A85-22113 polyplanes FLUIDIZED BED PROCESSORS
- Laboratory simulation of smoke reduction from aircraft ngine test cell exhaust using a fluidized bed filter
- p 278 N85-16886 [AD-A148600] FLUTTER Flutter control with unsteady aerodynamic models

The development of a finite element model of an aircraft

Vibration tailoring of advanced composite lifting

Integrated digital/electric aircraft concepts study [NASA-CR-3841] p 257 N85-16861

The Air Force can improve its forecasts of aircraft spare

Engineering property comparisons of PM and IM aluminum alloy forgings

NOISEMAP 4.4 computer program update, operator's

Using the control system design environment in the

design of a data link receiver unit for the Coast Guard HH-65A helicopter

p 270 N85-15753

p 214 A85-19582

p 288 A85-20828

p 290 A85-21683

p 290 A85-21846

p 272 A85-19456

p 308 N85-16682

p 298 N85-17398

p 302 N85-16503

p 271 N85-16880
FORWARD SCATTERING

- Evaluation of the forward scattering spectrometer probe. I Electronic and optical studies p 291 A85-22168 FOURIER TRANSFORMATION
- A Fourier Transform method for calculating velocity profiles on airfoils [AIAA PAPER 85-0208] p 215 A85-19592
- GC-FTIR (Fourier Transform Infrared Spectrometry) of jet fuels [AD-A148272] p 285 N85-17155
- FRACTURE MECHANICS
- Engine Cyclic Durability by Analysis and Testing [AGARD-CP-368] p 266 N85-15733 FRACTURE STRENGTH
- Engineering property comparisons of PM and IM aluminum alloy forgings
- AD-B0881466L] p 298 N85-17398 FRAMES
- Composite curved frames for helicopter fuselage structure p 252 A85-21396
- FREE FLIGHT Is the free flight/wind tunnel equivalence concept valid for unsteady viscous flow?
- (AIAA PAPER 85-0378) p 222 A85-19708 Characteristic motions for simulation of post-stall manoeuvres and flight instabilities p 269 A85-21679
- FREE FLOW A study of compressible turbulent free shear layers using
- laser Doppler velocimetry [AIAA PAPER 85-0177] p 213 A85-19569
- A simple analytical method for predicting axisymmetric turbulent jet flowfields in a freestream [AIAA PAPER 85-0251] p 216 A85-19614
- FREE JETS
- Application of laser interferometry to density measurements in free jets p 206 A85-19406 FRICTION FACTOR
- Calculation of friction and heat transfer in turbulent flow of a compressible gas in a plane duct

p 291 A85-22114

- Effects of friction dampers on aerodynamically unstable rotor stages p 265 A85-21866
- FUEL CONSUMPTION Mi-28 - The Soviets create Havoc p 250 A85-20147 Reference energy-altitude descent guidance: Simulator evaluation -- aircraft descent and fuel conservation
- [NASA-TP-2383] p 261 N85-16868 FUEL TANKS
- Aircraft wing fuel tank environmental simulator tests for evaluation of antimisting fuels
- [FAA-CT-84-15] p 283 N85-15920 Distribution and storage of aviation turbine fuel for military operations in northern Australia
- [AD-A147180] p 283 N85-15921 Preliminary airworthiness evaluation AH-1S (MC) helicopter with external fuel tanks installed
- [AD-A148091] p 258 N85-16865 FUNCTIONAL DESIGN SPECIFICATIONS
- Design study of technology requirements for high performance single-propeller-driven business airplanes [NASA-CR-3863] p 235 N85-15692 A digital piloting system for the combat helicopter
- p 260 N85-16806
- The use of local functionals to construct a circumvention maneuver in game problems of evasion
- p 302 A85-22374
- Turbulent flow around a wing-fuselage type juncture [AIAA PAPER 85-0040] p 208 A85-19475
- Environmental effects and durability evaluation of advanced composite fuselage structures p 251 A85-21388
- Fabrication and assembly of composite rear fuselage (CRF) tooling and manufacturing for the UH-60 heliconter p.200 A85-21394
- Composite curved frames for helicopter fuselage structure p 252 A85-21396 Field-incidence noise transmission loss of general
- aviation aircraft double-wall configurations p 304 A85-21842
 - Turbulent drag reduction research
 - p 237 N85-16788

G

- GAME THEORY
- The use of local functionals to construct a circumvention maneuver in game problems of evasion p 302 A85-22374
- GAS ANALYSIS
- Integrated exhaust gas analysis system for aircraft turbine engine component testing (NASA-TP-2424) p 295 N85-16100

- GAS CHROMATOGRAPHY
- GC-FTIR (Fourier Transform Infrared Spectrometry) of jet fuels
- [AD-A148272] p 285 N85-17155 GAS COOLING
- Some improvements on an annular combustor of Al type turbojet engine p 264 A85-20235 GAS DENSITY
- Application of laser interferometry to density measurements in free jets p 206 A85-19406 GAS DYNAMICS
- Calculation of friction and heat transfer in turbulent flow of a compressible gas in a plane duct
- p 291 A85-22114 GAS FLOW
- Euler solution of axisymmetric flows about bodies of revolution using a multigrid method [AIAA PAPER 85-0017] p 206 A85-19460
- [AIAA PAPER 85-0017] p 206 A85-19460 The fundamental equations of 3-dimensional two-phase particulate gas flow and a twofold stream surfaces model of solution for particulate gas flow in turbomachines p 228 A85-20233
- An extremum problem concerning the shape of a body of revolution in supersonic gas flow p 234 A85-22371 GAS INJECTION
- Effect of the arrangement of apertures on the gain coefficient during asymmetric gas injection into a Laval nozzle p 229 A85-20562 GAS_JETS
- Hypersonic multicycle gas jet with a strongly underexpanded stream at the nozzle section p 229 A85-20554
- GAS PRESSURE Newton iteration formulas for correcting temperature and
- pressure in thermodynamic calculation of rocket engines p 279 A85-20226
- A linearly correcting method of deviation function for considering the influence of pressure on the thermodynamic properties of combustion gas p 304 A85-20236
- GAS TEMPERATURE Newton iteration formulas for correcting temperature and
- pressure in thermodynamic calculation of rocket engines
 p 279 A85-20226
- GAS TURBINE ENGINES
- Computational thermo-fluid dynamics contributions to advanced gas turbine engine design
- [AIAA PAPER 85-0083] p 262 A85-19509 A procedure for the optimization of the aerothermodynamic design of multistage axial compressors -- German thesis p 227 A85-19851
- The challenge from ceramics to metals in the gas turbine and related areas p 280 A85-20150 A linearly correcting method of deviation function for considering the influence of pressure on the
- thermodynamic properties of combustion gas p 304 A85-20236 Off-design point characteristics of the precooled gas
- turbine cycle with liquefied hydrogen as fuel p 289 A85-20884 Aeronautical gas turbines. III p 264 A85-21420
- Prediction of performance of aircraft gas turbines p 264 A85-21682
- Analysis of a split-flow inertial particle separator by finite elements --- for helicopter gas turbine engine p 231 A85-21845
- Swirling flow in a research combustor p 283 A85-21863
- Effects of friction dampers on aerodynamically unstable rotor stages p 265 A85-21866 Influence of blowing rate and injection angle on the
- performance of a film-cocled blade p 265 A85-22231 Mounting construction for turbine vane assembly (AD-D011395) p 265 N85-15723
- [AD-D011395] p 265 N85-15723 Control system design language implementation of a gas turbine starting controller
- [AD-A147896] p 266 N85-15732 Overview of the AGARD SMP activities on turbine engine materials technology in the 1972 - 1982 period
- p 266 N85-15738 Comparison between the properties of conventional wrought and powder metallurgical alloys for turbine disc applications p 283 N85-15739
- Cumulative damage modeling of fatigue crack growth p 267 N85-15741 Disc fatigue life predictions for gas turbine engines
- p 267
 N85-15743

 Engine cyclic durability by analysis and material testing
 p 267

 N85-15744
 Life prediction at high temperature under multiaxial loading
 p 267

 N85-15745
 Experiences with the material bevaviour and high temperature low cycle fatigue life prediction of the IN 738

 blading alloy
 p 292

 Verification of life prediction through component testing
 p 292

- **GRAPHITE-EPOXY COMPOSITES**
- View of future requirements for engine cyclic durability by analysis and testing p 267 N85-15751 Current problems in turbornachinery fluid dynamics
- [AD-A147127] p 294 N85-16074 Integrated exhaust gas analysis system for aircraft
- turbine engine component testing (NASA-TP-2424) p 295 N85-16100
- The effects of manufacturing automation on the surge and mobilization capabilities of the gas turbine engine industry [AD-A147295] p 297 N85-17162
- GAS TURBINES
 - An improved computer model for prediction of axial gas turbine performance losses
 - [NASA-CR-174246] p 265 N85-15724 Accelerated Mission Endurance Testing (AMET)
 - p 266 N85-15736 Contamination and distortion of steady flow field induced by discrete frequency in aircraft gas turbines
 - [AD-A147092] p 294 N85-16073 Experience of one UK electronic equipment supplier with bite on engine/flight control systems over the past ten years p 296 N85-16738
- GASOLINE
- Some characteristics of automotive gasolines and their performance in a light aircraft engine [FAA-CT-84-12] p.283 N85-15919
- GENERAL AVIATION AIRCRAFT
- Analysis and testing of the Diamond One wing anti-icing system
- [AIAA PAPER 85-0414] p 286 A85-19735 A summary of NASA's research on the fluid ice protection system
- [AIAA PAPER 85-0467] p 241 A85-19768 Analysis of fatal accidents involving light aircraft
- weighing up to two tons and their causes in the context of flight medicine --- German thesis p 241 A85-19846 Field-incidence noise transmission loss of general
- aviation aircraft double-wall configurations p 304 A85-21842 Design study of technology requirements for high performance single-propeller-driven business airplanes
- [NASA-CR-3663] p 235 N85-15692 Some characteristics of automotive gasolines and their performance in a light aircraft engine
- [FAA-CT-84-12] p 283 N85-15919 Aerodynamic-structural study of canard wing, dual wing, and conventional wing systems for general aviation
- applications [NASA-CR-172529] p 238 N85-16829 GERT
- A Q-GERT network simulation model for examining pipeline time in the Navy's J-52 intermediate level jet engine repair cycle
- [AD-A147269] p 201 N85-15663 GLASS FIBER REINFORCED PLASTICS
- Energy absorbing qualities of fiber reinforced plastic tubes p 282 A85-21393 System for rapid repair of damaged airfield runways
- [AD-D011325] p 276 N85-15754 GLASS FIBERS Preliminary evaluation of an improved flammability test

Nonlinear simulation of flight along wind compensating

A cockpit-display concept for executing a multiple

A comparison of flight test and analytical techniques

Flight testing of a wing section with laminar flow

A weapon system design approach to diagnostics

A thermoplastic polyimidesulfone --- synthesis of

Utilization of analytical equipment in design and process

Flight service evaluation of advanced composite ailerons

problems solution and failure analysis of composites

glide-slope approach for wake-vortex avoidance

for boundary layer transition on a sailplane

The design of airfoils at low Reynolds numbers

p 242 N85-16840

p 245 A85-21838

p 261 N85-16869

p 209 A85-19500

p 210 A85-19501

p 233 A85-22227

p 246 N85-16851

p 203 N85-16752

p 282 A85-21483

p 281 A85-21390

p 284 N85-17049

A-19

method for aircraft materials [FAA-CT-84-22]

GLIDE PATHS

GUDERS

control

GRAPHITE

curved glidepaths

[NASA-TP-2386]

[AIAA PAPER 85-0074]

[AIAA PAPER 85-0075]

Satellite navigation

[S-HRG-98-856]

GLOBAL POSITIONING SYSTEM

GRAPHITE-EPOXY COMPOSITES

on the L-1011 transport aircraft

[NASA-CR-172483]

GOVERNMENT/INDUSTRY RELATIONS

processable and solvent resistant system

p 204 N85-16798

technological

vareus

Operational requirements

capabilities

GRAPHITE-POLYIMIDE COMPOSITES

GRAPHITE-POLYIMIDE COMPOSITES

- Development of a graphite/polyimide composite p 281 A85-21380 transmission housing V-378A, a new modified bismaleimide matrix resin for p 282 A85-21482 high modulus graphite
- PMR polyimide composites for aerospace applications --- Polymerization of Monomer Reactants p 282 A85-21520

GRIDS

- An exploratory study of finite difference grids for transonic unsteady aerodynamics p 235 N85-15696 (NASA-TM-84583)
- GROUND EFFECT (AERODYNAMICS) Aerodynamics of an airfoil in ground effect with a jet
- issuing from its undersurface o 207 A85-19461 (AIAA PAPER 85-00191
- A novel experimental facility for conducting jet impingement studies related to VTOL aircraft p 209 A85-19484 [AIAA PAPER 85-0052]
- Ground-effect analysis of a jet transport airplan p 248 A85-19677 [AIAA PAPER 85-0307]
- Ground interference effects on subsonic dynamic stall pitch and plunge p 231 A85-21841 in pitch and plunge
- Ground-effect analysis of a jet transport airplane p 234 N85-15687 [NASA-TM-85920] GROUND EFFECT MACHINES
- Skirt material effects on air cushion dynamic heave p 307 A85-21840 etability GROUND RESONANCE
- Study to eliminate ground resonance using active controls
- p 255 N85-15715 [NASA-CR-166609] GROUND SUPPORT FOUIPMENT
- The Western Aeronautical Test Range of NASA Ames Research Cente [AIAA PAPER 85-0316] p 275 A85-19678
- Equipment for preflight test of an Electronic Countermeasures (ECM) avionic system p 293 N85-15949
- GROUND TESTS
- Ground test experience with large composite structures p 251 A85-21383 for commercial transports GROUND WATER
- Installation restoration program. Phase 2: Stage 1 problem confirmation study, Duluth International Airport Duluth, Minnesota [AD-A148318] p 278 N85-16885
- GUIDANCE SENSORS
- Evaluation of nose, roof, and mast mounted sensor platforms for piloting and sighting, integrated in future combat helicopters p 260 N85-16808 GUIDE VANES
- Mounting construction for turbine vane assembly [AD-D011395] p 265 N85p 265 N85-15723 GUST ALLEVIATORS
- Application of an adaptive blade control algorithm to a p 269 A85-20143 gust alleviation system Helicopter active control with rotor blades relaxation
- p 270 N85-16819 Flight test of the Open Loop Gust Alleviation (OLGA)
- [BMFT-FB-W-84-038] p 271 N85-16881

Н

H-60 HELICOPTER

- Fabrication and assembly of composite rear fuselage (CRF) tooling and manufacturing for the UH-60 p 200 A85-21394 helicopter HALOCARBONS
- Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems
- [NASA-CR-174271] p 242 N85-15701 HANGARS
- Hangar heating and energy conservation manual [AD-A147893] p 277 N85-15762
- HARDENING (MATERIALS) Metallurgical and mechanical phenomena due to rubbing of titanium against sintered powder Nichrome
- p 291 A85-22281 HARDWARE
- ATE user's view on design for maintainability p 202 N85-16737
- HARMONIC OSCILLATION Harmonic oscillations of a rectangular wing with a circulation variable over the span p 231 A85-21656 HARNESSES
- Impact tests of automatic lap belt configurations p 243 N85-16844 [AD-A148034]
- HARRIER AIRCRAFT From AV-8B to the ASTOVL p 246 A85-19184
- Multivariable flight control with time-scale separation [NASA-CR-174320] p 268 N85-16873

HEAD (ANATOMY)

Powered articulated headrest system p 254 N85-15710 [AD-D011353]

- HEAD-UP DISPLAYS Contrast sensitivity performance assessment of HUD display systems p 259 A85-21593
- HEAT EXCHANGERS
- Thermal design of rotatable cryogenic heat pipe joints for heat exchangers in space applications [AIAA PAPER 85-0068] p 279 A85-19495 HEAT FLUX
- High temperature thermocouple and heat flux gauge using a unique thin film-hardware hot juncture p 295 N85-16096 [NASA-TM-868981
- HEAT PIPES Thermal design of rotatable cryogenic heat pipe joints
- for heat exchangers in space applications [AIAA PAPER 85-0068] n 279 A85-19495
- HEAT RESISTANT ALLOYS Microstructural development of protective Al2O3 p 283 A85-21650
- HEAT SHIELDING
- Improvements in low Reynolds number testing in the NSWC hypervelocity wind tunnel No. 9 p 274 A85-19602 AIAA PAPER 85-0226]
- HEAT TRANSFER Advances in heat transfer. Volume 16
- p 288 A85-20501 Engine Cyclic Durability by Analysis and Testing p 266 N85-15733
- [AGARD-CP-368] Monitoring engine thermal stresses p 266 N85-15735
- High temperature thermocouple and heat flux gauge using a unique thin film-hardware hot juncture [NASA-TM-86898] p 295 N85-16096
- HEAT TREATMENT Problems and possibilities for life extension in gas turbine
- components p 267 N85-15742 HEATERS Heater block assembly for use in thermal oxidation
- testing of jet fuel p 285 N85-17077 [AD-D011430]
- HELICOPTER CONTROL
- The design and development of an integrated core p 260 N85-16811 system for battlefield helicopters A review of US Army aircrew-aircraft integration research programs p 270 N85-16814
- Flight tests with a new helicopter Force Feel System (FFS) Helicopter active control with rotor blades relaxation
- p 270 N85-16819 Flight research on visusl aids and navigation equipment
- for helicopter low-level flight at night
- HELICOPTER DESIGN
- challenges of evolving operational needs
- Technology gains expected to yield LHX size, weight cost reductions
- Aeroelastic characteristics of the AH-64 bearingless tail rotor
- p 281 A85-21376 1983 K747 composite main rotor blade modification, analysis
- Design, fabrication and verification of composite
- flexbeam tail rotor for AH-64 Apache helicopter
- composite p 281 A85-21380 transmission housing Sikorsky composite rotor hub development
- p 251 A85-21381 Structural analysis and testing of ACAP subcomponents
- --- Advanced Composite Airframe Program p 251 A85-21384
- Environmental effects and durability evaluation of advanced composite fuselage structures p 251 A85-21388
- Flexible matrix composites applied to bearingless rotor stems p 281 A85-21389 systems
- Composite curved frames for helicopter fuselage structure p 252 A85-21396 p 245 A85-21461 Integrated navigation
- The impact of integrated systems The helicopte p 252 A85-21467 designer's viewpoint Analysis of a split-flow inertial particle separator by finite
- elements --- for helicopter gas turbine engine p 231 A85-21845 Coupled helicopter rotor/body aeromechanical stability
- comparison of theoretical and experimental results o 252 A85-21847
- Speed benefits of tilt-rotor designs for LHX p 255 N85-15717 [NASA-CR-166437]
- Integration of sensor fusion in advanced helicopter cockpit design p 260 N85-16813 Advanced flight simulation for helicopter development p 277 N85-16815 HELICOPTER PERFORMANCE The development of mathematical modelling techniques for helicopter rotor icing [AIAA PAPER 85-0336] p 240 A85-19679 Crashworthiness of helicopter composite structures p 251 A85-21386 Experimental aerodynamic characteristics of an NACA 0012 airfoil with simulated ice p 252 A85-21844 Preliminary airworthiness evaluation AH-1S (MC) helicopter with external fuel tanks installed p 258 N85-16865 [AD-A148091] HELICOPTER TAIL ROTORS Design fabrication and verification of composite flexbeam tail rotor for AH-64 Apache helicopter p 251 A85-21379 Tooling problems in the manufacture of AH-64 Composites Flexbeam Tail Rotor p 200 A85-21382 Calculation of the velocity field generated by a helicopter main and tail rotors in hover [AD-A147731] p 239 N85-16833 p 284 N85-17058 Repair of composites HELICOPTER WAKES Solution method for a hovering helicopter rotor using the Euler equations [AIAA PAPER 85-0436] p 223 A85-19749 HELICOPTERS Full two-dimensional transient solutions of electrothermal aircraft blade deicing [AIAA PAPER 85-0413] p 248 A85-19734 Application of an adaptive blade control algorithm to a gust alleviation system p 269 A85-20143 An overview of helicopter's 's environmental p 241 A85-21643 considerations **Operational Loads Data** p 201 N85-15664 [AGARD-CP-375] Helicopter data acquisition in WHL p 254 N85-15676 The UH-1H helicopter icing flight test program: An overview [NASA-TM-86925] p 242 N85-15702 Study to eliminate ground resonance using active controls p 255 N85-15715 [NASA-CR-166609] Literature review of voice recognition and generation technology for Army helicopter applications p 293 N85-15954 [AD-A146878] Helicopter noise survey performed at Las Vegas, Nevada, 19-21 January, 1984 p 305 N85-16593 [AD-A147392] Noise measurement flight test: Data-analyses aerospatiale AS-355F TwinStar helicopter p 305 N85-16595 [AD-A147497] Helicopter Guidance and Control Systems for Battlefield Support AGARD-CP-3591 p 204 N85-16797 Automatic briefing and mission management systems for battlefield support p 259 N85-16799 A Computer-generated topographic display system for navigation and mission planning in helicopters p 259 N85-16800 p 259 N85-16801 Map display for helicopters Development of a Helicopter integrated navigation p 245 N85-16802 system Standard Attitude Heading Reference System (SAHRS) p 246 N85-16804 full scale development program Integrated control and display systems for helicopter p 260 N85-16805 battlefield mission management Recent methods for calibrating the anemometry of p 260 N85-16809 helicopters at low speeds LPI-radar for helicopter obstacle warning p 297 N85-16810 Advanced flight simulation for helicopter development p 277 N85-16815 Development and flight test of a helicopter compact. portable, precision landing system concept p 261 N85-16821 Helicopter model rotor-blade vortex interaction impulsive noise: Scalability and parametric variations [NASA-TM-86007] p 238 N85-16826 Development, production and testing of central control
- and display unit for helicopters [BMFT-FB-W-84-039] p 261 N85-16871 Investigation on experimental techniques to detect,
- locate and quantify gear noise in helicopter transmissions [NASA-CR-3847] p 305 N85-17667
- Noise measurement flight test: Data-analyses Aerospatiale AS 350D AStar helicopter [AD-A148496]
 - p 306 N85-17672

- p 257 N85-16818
- p 261 N85-16820
- Advanced helicopter technology Industry girds for

- p 199 A85-20057 p 249 A85-20058
- p 250 A85-20142 Composite structures; Proceedings of the National Specialists Meeting, Philadelphia, PA, March 23-25,
- and qualification for new high temperature requirements p 251 A85-21378
- p 251 A85-21379
- Development of a graphite/polyimide

	Data-analyses	, SILUISKY
5-76A neikopter (AD-A148525)	0.306 N	85.17673
HELIPORTS	p + + + + + + + + + + + + + + + + + + +	
Acoustical guidelines for new	p 276 A	85-21644
Aileron effectiveness for a subs	onic transport r	nodel with
a high-aspect-ratio superchucal ([NASA-TM-85674]	p 235 N	85-15695
Comparison of analytical and	experimental s	steadyand
a high-aspect-ratio supercritical w	ing model with	oscillatino
control surfaces	0	
[NASA-TM-84589]	p 235 N	85-15697
HIGH FREQUENCIES	military bolicon	tore using
the NVIS mode HIGH REYNOLDS NUMBER	p 297 N	85-16807
Variable-temperature water t numbers	unnel for high	Reynolds
[AIAA PAPER 85-0051] Mach-10 high Reynolds numl	p 273 A ber developme	85-19483 Int in the
(ALAA PAPER 85-0054)	n 273 4	85.19486
Development of the UTA H	ligh Reynold:	Number
Transonic Wind Tunnel	n 275 d	85.10662
A comparative study betweet	n an implicit a	nd explicit
algorithm for transonic airfoils	n 205 d	95 10777
HIGH SPEED	P 220 P	
Numerical solution of the Euter	equations for hi	gh-speed,
[AIAA PAPER 85-0123]	p 211 A	85-19534
Life prediction at high tempe	rature under	multiaxial
loading	p267 N rial bevaviour	185-15745
temperature low cycle fatigue life	e prediction of	the IN 738
plading alloy	p 292 M	185-15746
KIGH TEMPERATURE TESTS	do modificatio	
and gualification for new high te	mperature requ	irements
.	p 251 /	85-21378
Polyimide protective coatings	for 700 deg se p 282 /	rvice \85-21527
HIGHLY MANEUVERABLE AIRC Prediction of HiMAT RPBV (RAFT	erference
	component int	
effects at transonic speeds	omponentint	195-19593
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET	p 215 / RY	\85-19593
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils	p 215 / P 215 / RY of three-dimens	185-19593
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479]	p 215 / P 215 / RY of three-dimens P 225 /	A85-19593 sional flow A85-19776
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in rechoiruse to the measurement	p 215 / P 215 / RY of three-dimens p 225 / terferogram of three-dimens	A85-19593 sional flow A85-19776 evaluation
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields	p 215 / P 215 / TRY of three-dimens p 225 / terferogram of three-dimens	A85-19593 sional flow A85-19776 evaluation sional flow
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037]	p 215 / P 215 / TRY of three-dimens p 225 / terferogram of three-dimens p 288 /	A85-19593 sional flow A85-19776 evaluation sional flow A85-20852
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES	p 215 / P 215 / PY of three-dimens p 225 / terferogram of three-dimens p 288 / p 288 /	A85-19593 sional flow A85-19776 evaluation sional flow A85-20852
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st	p 215 / FRY of three-dimens p 225 / terferogram of three-dimens p 288 / ructures p 285 /	A85-19593 sional flow A85-19776 evaluation sional flow A85-20852
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech	p 215 / Fry of three-dimens p 225 / tenferogram of three-dimens p 288 / ructures p 285 / ructures p 285 / niques	A85-19593 sional flow A85-19776 evaluation sional flow A85-20852
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS	p 215 / TRY of three-dimens p 225 / tenferogram of three-dimens p 288 / ructures p 288 / nuctures p 285 / niques p 294 /	A85-19593 sional flow A85-19776 evaluation sional flow A85-20852 A85-17059 A85-16067
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission brusion	p 215 / TRY of three-dimens p 225 / tenferogram of three-dimens p 288 / ructures p 288 / ructures p 285 / niques p 294 / te/polyimide	\85-19593 xional flow \85-19776 evaluation sional flow \85-20852 \85-17059 \85-16067 composite \85-2016
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircuit	p 215 / FRY of three-dimens p 225 / terferogram of three-dimens p 288 / ructures p 285 / iniques p 294 / te/polyimide p 281 / ation problems	A85-19593 ional flow A85-19776 evaluation sional flow A85-20852 A85-17059 A85-16067 composite A85-21380 within an
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircul anechoic hover chamber (AIAA DAPER 85-0011)	p 215 / TRY of three-dimens p 225 / terferogram of three-dimens p 288 / ructures p 285 / iniques p 294 / te/polyimide p 281 / ation problems	A85-19593 iional flow A85-19776 evaluation sional flow A85-20852 V85-17059 V85-16067 composite A85-21380 within an
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tect [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover	p 215 / TRY p 215 / terferogram p 225 / terferogram p 228 / ructures p 288 / ructures p 285 / iniques p 294 / te/polyimide p 281 / ation problems p 273 // ing helicopter (A85-19593 iional flow A85-19776 evaluation sional flow A85-20852 V85-17059 V85-16067 composite A85-21380 within an A85-19497 rotor using
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations	p 215 / RY of three-dimens p 225 / terferogram of three-dimens p 288 / ructures p 285 / ructures p 285 / iniques p 294 / te/polyimide p 281 / ation problems p 273 / ng helicopter /	A85-19593 sional flow A85-19776 evaluation sional flow A85-20852 A85-20852 A85-17059 A85-16067 composite A85-21380 within an A85-19497 rotor using
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tect [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0436] HUBS	p 215 / TRY of three-dimens p 225 / terferogram of three-dimens p 288 / ructures p 288 / ructures p 288 / tructures p 285 / niques p 294 / ter/polyimide p 281 / ation problems p 273 / ing helicopter (p 223 /	A85-19593 iional flow A85-19776 evaluation sional flow A85-20852 A85-17059 A85-16067 composite A85-16067 composite A85-19497 otor using A85-19749
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hoven the Euler equations [AIAA PAPER 85-0436] HUBS Sikorsky composite rotor hub	p 215 / P 215 / TRY of three-dimens p 225 / enferogram of three-dimens p 288 / ructures p 288 / ructures p 288 / ructures p 285 / endersity p 294 / te/polyimide p 281 / ation problems p 223 / development p 221 /	A85-19593 iional flow A85-19776 evaluation sional flow A85-20852 A85-17059 N85-16067 composite A85-21380 within an A85-19497 rotor using A85-19749 A85-21381
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft si HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0436] HUBS Sikorsky composite rotor hub	p 215 / P 215 / P 215 / P 215 / P 215 / P 225 / P 228 / ructures p 288 / p 281 / ation problems p 273 / ation problems p 223 / development p 251 / G G	A85-19593 sional flow A85-19776 evaluation sional flow A85-20852 A85-20852 A85-17059 A85-17059 A85-10667 composite A85-21380 within an A85-19497 rotor using A85-19749 A85-21381
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0436] HUBS Sikorsky composite rotor hub HUMAN FACTORS ENGINEERIN Biodynamic resistant control s [AD-D011380]	p 215 / P 215 / P 215 / P 215 / P 215 / P 225 / P 225 / P 288 / ructures P 288 / ructures P 288 / ructures P 281 / ation problems p 273 / ng helicopter / P 223 / development P 251 / G Stick P 259 /	A85-19593 iional flow A85-19776 evaluation sional flow A85-20852 A85-20852 A85-17059 A85-17059 A85-17059 within an A85-19497 rotor using A85-19749 A85-21381 V85-15721
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0436] HUBS Sikorsky composite rotor hub HUMAN FACTORS ENGINEERIN Biodynamic resistant control s [AD-D011380] Operational requirements	p 215 / P 215 / P 215 / P 215 / P 215 / P 215 / P 225 / P 228 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 281 / ation problems p 273 / ng helicopter / P 223 / development P 251 / G Stick P 259 / versus tech	A85-19593 isonal flow A85-19776 evaluation sional flow A85-20852 A85-20852 A85-20852 V85-16067 composite A85-21380 within an A85-19497 rotor using A85-19749 A85-21381 V85-15721 hnological
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0436] HUBS Sikorsky composite rotor hub HUMAN FACTORS ENGINEERIN Biodynamic resistant control s [AD-D011380] Operational requirements capabilities A Computer-generated topool	p 215 / P 215 / P 215 / P 215 / P 215 / P 215 / P 225 / P 228 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 281 / ation problems P 273 / development P 251 / G G stick P 259 i versus tec P 204 if tersus tec P 204 if ructures P 251 / development P 251 / G stick P 259 i versus tec P 204 if versus tec P 204 if P 204 if versus tec P 204 if versus tec P 204 if versus tec P 204 if Versus tec P 204 if Versus t	A85-19593 isonal flow A85-19776 evaluation sional flow A85-20852 A85-20852 A85-17059 A85-17059 A85-16067 composite A85-21380 within an A85-19497 rotor using A85-19749 A85-15721 hnological X85-16798 system for
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircul anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0436] HUBS Sikorsky composite rotor hub Biodynamic resistant control = [AD-D011380] Operational requirements capabilities A Computer-generated topog navigation and mission planning	p 215 / P 215 / P 215 / P 215 / P 215 / P 225 / P 225 / ructures p 288 / p 281 / ation problems p 273 / development p 223 / development p 221 / g 223 / development p 221 / g 224 / ructures p 225 / p 225 / p 225 / ructures p 273 / development p 223 / development p 225 / p 224 / ructures p 225 / p 255 /	A85-19593 isonal flow A85-19776 evaluation sional flow A85-20852 A85-17059 A85-17059 A85-17059 A85-16067 within an A85-19497 rotor using A85-19749 A85-21381 W85-16798 system for
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft si HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircul anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0436] HUBS Sikorsky composite rotor hub HUMAN FACTORS ENGINEERIN Biodynamic resistant control = [AD-011380] Operational requirements capabilities A Computer-generated topog navigation and mission planning	P 215 / P 215 / P 215 / P 215 / P 215 / P 225 / P 228 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 281 / ation problems P 273 / ation problems P 273 / ation problems P 273 / development P 251 / G versus tec P 259 / versus tec P 259 / ructurester P 250 / ructurester P	\u00e965-19593 \u00e965-19593 uional flow \u00e985-19776 evaluation sional flow \u00e985-20852 \u00e985-17059 \u00e985-16067 composite \u00e985-21380 within an \u00e985-19749 \u00e985-19749 \u00e985-15721 \u00e985-16788 \u00e95-16788 \u00e95-16788 \u00e95-16788 \u00e95-16788 \u00e95-16788 \u00e97-16788 \u00e97-16788 \u00e97-16788 \u00e97-16788 \u00e97-16788 \u00e97-16788 \u00e97-16788 \u00e97-16788 \u00e97-16788 \u00e98-16788 \u00e98-16788 \u00e98-16788 \u00e97-16788 \u00e98-16788 \u00e98-16788 \u00e98-16788 \u00e98-16788 \u00e98-16788 \u00e98-16788 \u00e98-16788
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircul anechoic hover chamber (AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0436] HUBS Sikorsky composite rotor hub HUMAN FACTORS ENGINEERIN Biodynamic resistant control [AD-D011380] Operational requirements capabilities A computer-generated topog navigation and mission planning A review of US Army aircrew-a programs	p 215 / P 215 / P 215 / P 215 / P 215 / P 215 / P 225 / P 228 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / ructures P 288 / P 281 / ation problems P 273 / development P 223 / development P 251 / P 251 / Rest P 259 / versus teo P 204 / P 251 / D 259 / versus teo P 204 / P 251 / P 251 / ructures P 259 / versus teo P 204 / P 251 / P	A85-19593 iional flow A85-19776 evaluation sional flow A85-20852 A85-20852 A85-17059 A85-17059 A85-16067 within an A85-19497 rotor using A85-19749 A85-21381 X85-15721 thnological X85-16798 system for N85-16800 m research
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft si HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircul anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0436] HUBS Sikorsky composite rotor hub HUMAN FACTORS ENGINEERIN Biodynamic resistant control = [AD-011380] Operational requirements capabilities A Computer-generated topog navigation and mission planning A review of US Army aircrew-a programs	p 215 / P 215 / P 215 / P 215 / P 215 / P 215 / P 225 / P 228 / P 288 / P 281 / P 281 / P 283 / P 284 / P 283 / P 283 / P 284 / P 284 / P 283 / P 284 / P 284 / P 284 / P 285 / P 284 / P 2	A85-19593 vional flow A85-19776 evaluation sional flow A85-19776 evaluation sional flow A85-20852 N85-17059 N85-16067 composite A85-21380 within an A85-19497 otor using A85-19749 A85-15721 xhab-16788 system for N85-16800 nr research N85-16804 wisb-16814 alabor
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0436] HUBS Sikorsky composite rotor hub HUMAN FACTORS ENGINEERIN Biodynamic resistant control : [AD-011380] Operational requirements capabilities A Computer-generated topog navigation and mission planning A review of US Army aircrew-a programs HUMAN PERFORMANCE Performance evaluation of A units and aircraft using constrai	p 215 / P 215 / P 215 / P 215 / P 215 / P 215 / P 225 / enferogram of three-dimens p 228 / ructures p 288 / ructures p 288 / ructures p 288 / P 288 / P 288 / ructures p 288 / P 288	A85-19593 vional flow A85-19776 evaluation sional flow A85-19776 evaluation sional flow A85-20852 N85-16067 composite A85-21380 within an A85-19497 otor using A85-21381 N85-15721 thological N85-16788 system for N85-16800 nresearch N85-16814 ainteance sis
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hoven the Euler equations [AIAA PAPER 85-0476] HUBS Sikorsky composite rotor hub HUMAN FACTORS ENGINEERIN Biodynamic resistant control [AD-0011380] Operational requirements capabilities A Computer-generated topog navigation and mission planning A review of US Army aircrew-a programs HUMAN PERFORMANCE Performance evaluation of A units and aircraft using constrai [AD-A146955]	p 215 / P 215 / P 215 / P 215 / P 215 / P 215 / P 225 / entercogram of three-dimens p 228 / ructures p 288 / ructures p 288 / P 288 / ructures p 288 / P 288	A85-19593 iional flow A85-19776 evaluation iional flow A85-20852 V85-17059 V85-17059 V85-16067 composite A85-21380 within an A85-19497 rotor using A85-19497 rotor using A85-15721 V85-16728 V85-16798 system for N85-16814 ainteance sis
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0476] HUBS Sikorsky composite rotor hub HUMAN FACTORS ENGINEERIN Biodynamic resistant control [AD-0011380] Operational requirements capabilities A Computer-generated topog navigation and mission planning A review of US Army aircrew-a programs HUMAN PERFORMANCE Performance evaluation of A units and aircraft using constrai [AD-A146955] Nondestructive inspection: technicians	p 215 / P 215 / P 215 / P 215 / P 215 / P 215 / P 225 / entercogram of three-dimens p 228 / ructures p 288 / ructures p 288 / P 288 / ructures p 288 / P 288	A85-19593 iional flow A85-19776 evaluation iional flow A85-20852 V85-17059 V85-17059 V85-16067 composite A85-21380 within an A85-19497 rotor using A85-19497 rotor using A85-15721 V85-16728 V85-16798 system for N85-16814 ainteance sis N85-15660 abilities of
effects at transonic speeds [AIAA PAPER 85-0213] HOLOGRAPHIC INTERFEROMET Tomographic reconstruction of over airfoils [AIAA PAPER 85-0479] Application of digital in techniques to the measurement fields [AIAA PAPER 85-0037] HONEYCOMB STRUCTURES Composite repair of aircraft st HOT-WIRE ANEMOMETERS Aero-optics experimental tech [AD-A146755] HOUSINGS Development of a graphi transmission housing HOVERING A study of the flow recircut anechoic hover chamber [AIAA PAPER 85-0071] Solution method for a hover the Euler equations [AIAA PAPER 85-0476] HUBS Sikorsky composite rotor hub HUMAN FACTORS ENGINEERIN Biodynamic resistant control [AD-0011380] Operational requirements capabilities A Computer-generated topog navigation and mission planning A review of US Army aircrew-a programs HUMAN PERFORMANCE Performance evaluation of A units and aircraft using constrai [AD-A146955] Nondestructive inspection: technicians [AD-A147388]	p 215 / P 215 / P 215 / P 215 / P 215 / P 215 / P 225 / enferogram of three-dimens p 228 / ructures p 288 / ructures p 288 / ructures p 288 / P 288 / P 288 / ructures p 288 / P 288	A85-19593 isonal flow A85-19776 evaluation isonal flow A85-20852 V85-17059 V85-17059 V85-17059 V85-17059 V85-16067 composite A85-21380 within an A85-19497 rotor using A85-19749 A85-15721 V85-16798 system for N85-16814 ainteance sis N85-15660 abilities of N85-16196

HUMAN REACTIONS A path model of aircraft noise annoyance p 304 A85-22071 HYDRAULIC CONTROL Powered articulated headrest system [AD-0011353] p 254 N85-15710 HYDRAULIC EQUIPMENT The hydraulic and electrohydraulic elements used in flight simulators p 287 A85-19886 HYDROCARBON FUELS Analysis of middle distillate fuels by high resolution field ionization mass spectrometry p 285 N85-17153 [AD-A147724] HYDROCARBONS Impact of aircraft emissions on air quality in the vicinity of airports. Volume 4. Nitrogen dioxide and hydrocarbons AD. A1482531 p 299 N85-17436 HYDROGEN FUELS Off-design point characteristics of the precooled gas turbine cycle with liquefied hydrogen as fuel p 289 A85-20884 HYPERSONIC BOUNDARY LAYER Critical layer concept relative to hypersonic boundary laver stability [AIAA PAPER 85-0303] p 219 A85-19652 HYPERSONIC FLIGHT Introductory aerothermodynamics of advanced space p 231 A85-21827 transportation systems HYPERSONIC FLOW Regarding parametric investigations of slender cone nose bluntness effects p 220 A85-19688 [AIAA PAPER 85-0349] Hypersonic multicycle gas jet with a strongly underexpanded stream at the nozzle section p 229 A85-20554 Hypersonic chemically nonequilibrium viscous shock layer on wings with a catalytic surface p 229 A85-20561 Investigations of the longitudinal flow in corner configurations in the hypersonic regime. II - Corners between swept wedges p 232 A85-22146 Laminar heat-transfer distributions on biconics at incidence in hypersonic-hypervelocity flows [NASA-TP-2213] p 293 N85-16065 HYPERSONIC HEAT TRANSFER A numerical study of three-dimensional radiation fields in problems of supersonic flow past segmental bodies p 227 A85-20025 HYPERSONIC VEHICLES Transient motion of hypersonic vehicles including time history effects [AIAA PAPER 85-0201] p 268 A85-19585 HYPERSONIC WIND TUNNELS Hypersonic characteristics of an advanced aerospace nian [AIAA PAPER 85-0346] p 269 A85-19685 HYPERVELOCITY Introductory aerothermodynamics of advanced space transportation systems p 231 A85-21827 HYPERVELOCITY FLOW Laminar heat-transfer distributions on biconics at incidence in hypersonic-hypervelocity flows p 293 N85-16065 [NASA-TP-2213]

[1745A-17-2213] p 293 N85-16065 HYPERVELOCITY WIND TUNNELS Mach-10 high Reynolds number development in the NSWC hypervelocity facility

[AIAA PAPER 85-0054] p 273 A85-19486 Improvements in low Reynolds number testing in the

NSWC hypervelocity wind tunnel No. 9 [AIAA PAPER 85-0226] p 274 A85-19602

ICE FLOES

Parachute expedition to Arctic p 236 N85-16240 ICE FORMATION

- The Federal Aviation Administration's Engineering and Development Aircraft Icing Program
- (AIAA PAPER 85-0015) p 247 A85-19459 The development of mathematical modelling techniques for helicopter rotor icing

[AIAA PAPER 85-0336] p 240 A85-19679 Correlation of airfoil icing relationships with two-dimensional model and full scale rotorcraft icing test data

[AIAA PAPER 85-0337] p 240 A85-19680 Detailed measurements of the flowfield in the vicinity of an airfoil with glaze ice

[AIAA PAPER 85-0409] p 222 A85-19730

Progress in development of a Navier-Stokes solver for evaluation of iced airfoil performance [AIAA PAPER 85-0410] p 222 A85-19731

INCOMPRESSIBLE FLOW

Three-dimensional airflow and hydrometeor trajectory calculation with applications [AIAA PAPER 85-0412] p 222 A85-19733 Measurement of ice accretion using ultrasonic nulso-echo techniques [AIAA PAPER 85-0471] p 286 A85-19769 Analytical determination of propeller performance degradation due to ice accretion IAIAA PAPER 85-03391 p 264 A85-20867 Icing tunnel tests of Electro-Impulse De-Icing of an engine inlet and high-speed wings [AIAA PAPER 85-0466] p 241 A85-20872 Icing conditions encountered by a research aircraft p 299 A85-21141 Experimental aerodynamic characteristics of an NACA 0012 airfoil with simulated ice p 252 A85-21844 The UH-1H helicopter icing flight test program: An [NASA-TM-86925] p 242 N85-15702 The NASA Altitude Wind Tunnel (AWT): Its role in advanced icing research and development [NASA-TM-86920] p 276 N85-15758 ICE PREVENTION Analysis and testing of the Diamond One wing anti-icing system [AIAA PAPER 85-0414] p 286 A85-19735 Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) [NASA-TM-86919] p 276 N85-15757 ILYUSHIN AIRCRAFT Testing solution for IL-76 braking system problem p 256 N85-16766 IMAGE CONTRAST Contrast sensitivity performance assessment of HUD solav systems p 259 A85-21593 IMAGE PROCESSING Application of digital interferogram evaluation techniques to the measurement of three-dimensional flow fields [AIAA PAPER 85-0037] n 288 A85-20852 Functional built-in-test in a pipelined image processor p 202 N85-16740 IMPACT STRENGTH Proceedings of the International Conference and Exposition on Structural Impact and Crashworthiness [AD-A147845] p 242 N85-15703 IMPACT TESTS Impact tests of automatic lap belt configurations [AD-A148034] p 243 N85p 243 N85-16844 INPELLERS Calculation and analysis of the three-dimensional flow in centrifugal compressor impellers p 228 A85-20231 Experimental investigation of backswept centrifugal compressor impeller. I IN-FLIGHT MONITORING p 264 A85-20243 The lightning threat to aerospace vehicles [AIAA PAPER 85-0094] p 240 AIAA PAPER 85-0094] p 240 A85-19516 Measurement of ice accretion using ultrasonic pulse-echo techniques p 286 A85-19769 [AIAA PAPER 85-0471] The unambiquous in-flight determination of propeller rotational noise in aircraft with four-cycle combustion engines p 304 A85-20650 Structural Usage Monitoring System p 292 N85-15680 Tornado: (SUMS) Flight parameters recording for structure fatigue life n 292 N85-15682 monitoring USAF approach to airborne structural data recording: Airborne Data Acquisition Multifunction System (ADAMS) p 292 N85-15683 INCIDENCE The effect of changes in the angle of incidence in the event of a richochet at a float step [RAE-TRANS-2120] p 255 N85-15712 INCOMPRESSIBLE FLOW An incremental block-line-Gauss-Seidel method for the Navier-Stokes equations p 207 A85-19470 [AIAA PAPER 85-0033] Computational study of circulation control with suction [AIAA PAPER 85-0042] p 208 A85-19477 Accelerated convergence for incompressible flow calculations [AIAA PAPER 85-0058] p 209 A85-19489 A Fourier Transform method for calculating velocity orofiles on airfoils p 215 A85-19592 p 227 A85-20074 [AIAA PAPER 85-0208] Survey on jet instability theory

Drag prediction for projectiles and finned bodies in incompressible flow

[AIAA PAPER 85-0104] p 230 A85-20854 An experimental investigation of the mixing of co-annular swirting flows

(AIAA PAPER 85-0186) p 230 A85-20862 Optimal control of flow of a viscous incompressible fluid p 290 A85-22105

INCONEL (TRADEMARK)

- Calculation of three-dimensional unsteady incompressible flows by a vortex method p 291 A85-22240
- Calculation of the velocity field generated by a helicopter main and tail rotors in hover
- [AD-A147731] p 239 N85-16833 INCONEL (TRADEMARK)
- Experiences with the material bevaviour and high temperature low cycle fatigue life prediction of the IN 738 p 292 N85-15746 blading alloy INDEPENDENT VARIABLES
- Optimum performance parameters for ski-jump operations of USAF fighter aircraft
- AD. 41495321 p 258 N85-16867 INDEXES (RATIOS)
- The application of a technology index to aircraft turbine engine cost estimating relationships p 268 N85-16874 [AD-A147701]
- INFINITE SPAN WINGS
- Hypersonic chemically nonequilibrium viscous shock layer on wings with a catalytic surface
- p 229 A85-20561 INFLATING A theoretical view on the stress analysis of fully inflated
- parachute canopies p 239 N85-16835 40.41483971
- INFLUENCE COEFFICIENT
- Inexpensive calibrations for the influence function method using the interference distributed loads code for prediction of store loads in aircraft flow fields
- [AIAA PAPER 85-0270] p 247 A85-19623 INFRARED SPECTROMETERS
- GC-FTIR (Fourier Transform Infrared Spectrometry) of iet fuels AD-41482721
- p 285 N85-17155 INFRARED SUPPRESSION
- Airworthiness and flight characteristics test of the RC-12D Guardrail V [AD-A148046] p 258 N85-16864
- INGESTION (ENGINES) Temperature distortion generator for turboshaft engine
- testina [NASA-TM-83748] p 200 N85-15658
- INGOTS
- Engineering property comparisons of PM and IM aluminum alloy forgings p 298 N85-17398 (AD-B0881466L)
- INLET FLOW A comparison of different three-dimensional singularity methods for modelling internal flows
- p 205 A85-19264 [ONERA, TP NO. 1984-150] Three dimensional aerodynamics of an annular cascade in a non-uniform inlet flow
- [AIAA PAPER 85-0174] p 213 A85-19567 A universal turboshaft engine test cell - Design
- nsiderations and model test results p 275 A85-19711 [AIAA PAPER 85-0382] Simulation of transonic three-dimensional nacelle/inlet
- flowfields using an Euler/Navier-Stokes algorithm [AIAA PAPER 85-00841 p 226 A85-19798
- Computation of transonic inlet flows --- German thesis p 227 A85-19844 Effect of inlet and outlet flow conditions on the flow
- and performance of subsonic two-dimensional diffuser p 228 A85-20241
- Determination of surging line of two-spool axial flow compressor with cropped fan stages at low speed by use p 264 A85-20242 of parallel compressor theory
- Effect of steady-state temperature distortion on inlet flow to a high-bypass-ration turbofan engine
- p 265 N85-15725 [NASA-TM-86896] Current problems in turbomachinery fluid dynamics [AD-A147127] p 294 N85-16074
- Interest of internal bleed for a two-dimensional air intake operating in a wide Mach number range (1.8-3 plus) p 237 N85-16793

INLET NOZZLES

A-22

- Interest of internal bleed for a two-dimensional air intake operating in a wide Mach number range (1.8-3 plus) p 237 N85-16793
- INSPECTION Nondestructive inspection: Improved capabilities of techniciane
- [AD-A147388] p 295 N85-16196 INSTRUMENT FLIGHT RULES
- National airspace review: Airport radar service area operational confirmation report
- [DOT/FAA/AT-84/2] p 245 N85-15707 INSTRUMENT LANDING SYSTEMS Measurement of signal separation between radio service
- and air navigation service (IRT-TB-B-40/82) p 246 N85-16860
- INTEGRATED CIRCUITS Packaging and interconnection for avionics
- p 290 A85-21460

- INTEGRATORS
- Integrated control and display-systems for helicopter battlefield mission management p 260 N85-16805 INTERACTIONAL AERODYNAMICS
- Tests, in the transonic regime, of a model motorized by a blowing turbine 23 cm in diameter (9 inches) in the S1MA wind tunnel
- [ONERA, TP NO. 1984-158] p 272 A85-19272 An experimental investigation of blade-vortex interaction en normal incidence
- [AIAA PAPER 85-0003] p 206 A85-19451 An experimental investigation of stator/rotor interaction
- influence on multistage compressor rotor flow p 206 A85-19455 [AIAA PAPER 85-0009] The interaction and merging of two turbulent line
- vortices [AIAA PAPER 85-0046]
- p 208 A85-19480 A zonal computational approach to thrust augmentor ootimization
- [AIAA PAPER 85-0110] p 262 A85-19525 Surface pressure fluctuations in a three-dimensional shock wave/turbulent boundary layer interaction
- [AIAA PAPER 85-0125] p 211 A85-19536 Three-dimensionality in unsteady flow about a wing p 212 A85-19543 [AIAA PAPER 85-0132]
- A procedure for the calculation of supersonic flows with strong viscous-inviscid interaction [AIAA PAPER 85-0166] p 213 A85-19562
- Transient motion of hypersonic vehicles including time history effects [AIAA PAPER 85-0201] p 268 A85-19585
- Unsteady aerodynamics of an airfoil encountering a passing vortex
- [AIAA PAPER 85-0203] p 214 A85-19587
- A class of airfoils having finite trailing edge pressure aradients [AIAA PAPER 85-0206] p 215 A85-19590
- Viscous/inviscid interaction analysis of transonic shock induced separated flow including normal pressure aradients
- [AIAA PAPER 85-0371] p 221 A85-19703 Experimental study of forward-located iet-interaction nozzles
- [AIAA PAPER 85-0454] p 224 A85-19762 Disturbance-wave interactions in flows with crossflow [AIAA PAPER 85-0494] p 226 A85-19788
- A linearized unsteady aerodynamic analysis for transonic p 229 A85-20744 cascades Evaluation of a stalled airfoil analysis program n 231 A85-21848
- Flowfield scaling in sharp fin-induced shock wave/turbulent boundary-layer interaction p 232 A85-21857
- INTERCEPTION LPI-radar for helicopter obstacle warning
- p 297 N85-16810 INTERFERENCE DRAG
- Installed nacelle drag-improvement tests of an M = 0.8 turboprop transport configuration
- [NASA-TM-84302] p 255 N85-15716 INTERFEROMETERS
- Turbulence measurement interferometer apparatus (AD-D011377) p 295 N85-16156 INTERNATIONAL COOPERATION
- International projects, other work of Aeroproyekt p 204 N85-16767 Institute INVENTORY MANAGEMENT
- Optimal maintenance center inventories for fault-tolerant
- repairable systems p 301 A85-21548 The Air Force stock fund and aircraft availability p 203 N85-16761 [AD-A148653]
- INVISCID FLOW
- Three-dimensional inviscid flow analysis of turbofan forced mixers
- [AIAA PAPER 85-0086] p 210 A85-19510 A quasi-conservative lambda formulation --- for inviscid transonic flow simulation
- [AIAA PAPER 85-0088] p 210 A85-19511 Shock waves in transonic channel flows at moderate
- Reynolds number [AIAA PAPER 85-0369] p 221 A85-19702
- Viscous/inviscid interaction analysis of transonic shock induced separated flow including normal pressure aradients
- p 221 A85-19703 [AIAA PAPER 85-0371] Finite volume solution of the two-dimensional Euler equations on a regular triangular mesh
- p 223 A85-19748 [AIAA PAPER 85-0435] Evaluation of vortex wake predictions in the SWINT code
- p 224 A85-19759 [AIAA PAPER 85-0450] Efficient self-consistent viscous-inviscid solutions for unsteady transonic flow
- p 225 A85-19779 [AIAA PAPER 85-0482]

three-dimensional Calculation of unsteady incompressible flows by a vortex method p 291 A85-22240 A comparative study of the nonuniqueness problem of the potential equation [NASA-TP-2385] p 235 N85-15694 Analysis of the flow field about a T-45 using PANAIR [AD-A1468111 p 236 N85-15699 Recent advances in computational methods to solve the high-lift multi-component airfoil problem p 236 N85-16774 Inviscid compressible flow past a multi-element aerofoil p 236 N85-16776 Theoretical study of boundary-layer control p 237 N85-16784 IONIZATION Analysis of middle distillate fuels by high resolution field ionization mass spectrometry [AD-A147724] p 285 N85-17153

A numerical study of three-dimensional radiation fields

Computation of choked and supersonic turbomachinery

in problems of supersonic flow past segmental bodies

Survey on jet instability theory

flows by a modified potential method

Shock-free turbomachinery blade design

SUBJECT INDEX

p 227 A85-20025 p 227 A85-20074

p 232 A85-21859

p 232 A85-21864

- **ITERATIVE SOLUTION** A new iterative matrix solution procedure for
- three-dimensional panel methods p 213 A85-19568 [AIAA PAPER 85-0176]
- Newton iteration formulas for correcting temperature and pressure in thermodynamic calculation of rocket engines p 279 A85-20226

J

J-52 ENGINE

- A Q-GERT network simulation model for examining pipeline time in the Navy's J-52 intermediate level jet enaine repair cycle
- [AD-A147269] p 201 N85-15663 LAS ENGINE
- Problems and possibilities for life extension in gas turbine p 267 N85-15742 ponents JAGUAR AIRCRAFT
- Experiences obtained from service fatique monitoring p 292 N85-15672
- JET AIRCRAFT

Ground-effect analysis of a jet transport airplane

- AIAA PAPER 85-0307] p 248 A85-19677 Calculation of the minimum-time loop maneuver for jet
- aircraft p 269 A85-19876 Design of a STOL aircraft with jet assisted takeoff
- unite p 253 A85-22373 Advanced fatique monitoring on service aircraft
- p 292 N85-15671 Ground-effect analysis of a jet transport airplane
- p 234 N85-15687 (NASA-TM-859201
- Analysis of the flow field about a T-45 using PANAIR p 236 N85-15699 140-41468111
- JET AMPLIFIERS

T ENGINE FUELS

testing of jet fuel [AD-D011430]

[AD-A148272]

[AD-A147786]

[AIAA PAPER 85-0053]

issuing from its undersurface

[AIAA PAPER 85-0019]

[AIAA PAPER 85-0045]

Survey on jet instability theory

JET ENGINES

JET EXHAUST

system

JET FLAPS

JET FLOW

iet fuels

Experimental study of forward-located jet-interaction nozzles [AIAA PAPER 85-0454] p 224 A85-19762

Oxidation and stabilization of jet fuels --- Russian book

Heater block assembly for use in thermal oxidation

GC-FTIR (Fourier Transform Infrared Spectrometry) of

Atmospheric photochemical modeling of turbine engine

Frequency response of a jet engine test facility air supply

Aerodynamics of an airfoil in ground effect with a jet

The effect of phase-difference on the spreading rate

fuels. Phase 1: Experimental studies. Volume 2:

Environmental chamber data tabulations

Theoretical study on supersonic jet plumes

of a laminar circular jet under bi-modal excitation

p 281 A85-20925

p 285 N85-17077

p 285 N85-17155

p 300 N85-17470

p 273 A85-19485

p 206 A85-19439

p 207 A85-19461

p 208 A85-19479

p 227 A85-20074

JET IMPINGEMENT

- Turbulence structure of a three dimensional impinging iet in a cross stream
- p 208 A85-19478 [AIAA PAPER 85-0044] A novel experimental facility for conducting jet
- impingement studies related to VTOL aircraft [AIAA PAPER 85-0052] p 209 A85-19484 JET MIXING FLOW
- A simple analytical method for predicting axisymmetric
- turbulent jet flowfields in a freestream [AIAA PAPER 85-0251] p 216 A85-19614 JET NOZZLES
- Experimental study of forward-located jet-interaction nozzies
- [AIAA PAPER 85-0454] p 224 A85-19762 JET PROVOST AIRCRAFT
- Experiences obtained from service fatigue monitoring p 292 N85-15672 exercises
- JOINTS (JUNCTIONS)
- Advanced-composite joints and fittings for primary tructural components p 290 A85-21385 structural components Aeroproyekt develops improved runway surfacing p 277 N85-16770
- JOURNAL BEARINGS
- A theoretical study of stability of a rigid rotor under the influence of dilute viscoelastic lubricants p 289 A85-21278 [ASME PAPER 84-TRIB-17]
- Effects of turbulence and viscosity variation on the dynamic coefficients of fluid film journal bearings [ASME PAPER 84-TRIB-8] p 289 A85-21283
- JP-5 JET FUEL Evaluation of jet fuel deposit kinetics. Lot 4
- [AD-A147196] p 284 N85-15922 JUDGMENTS
- Judgment and discipline Recipe for survival
- p 241 A85-21582

κ

KALMAN FILTERS

- A three-dimensional Kalman filter for short observation times to extrapolate flight trajectories --- German thesis n 301 A85-19835
- KEROSENE Aircraft wing fuel tank environmental simulator tests for evaluation of antimisting fuels
- [FAA-CT-84-15] p 283 N85-15920 KEVLAR (TRADEMARK)
- Kevlar aramid fibers vs other fibers for reinforcement p 282 A85-21392 of composite structures KINETICS
- Evaluation of jet fuel deposit kinetics. Lot 4 p 284 N85-15922 [AD-A147196]

L

L-1011 AIRCRAFT

- Flight service evaluation of advanced composite ailerons on the L-1011 transport aircraft [NASA-CR-172483] p 284 N85-17049
- LAMINAR BOUNDARY LAYER
- Critical layer concept relative to hypersonic boundary laver stability
- p 219 A85-19652 [AIAA PAPER 85-0303] Laminar boundary layer stability experiments on a cone at Mach 8. III - Sharp cone at angle of attack
- p 226 A85-19787 [AIAA PAPER 85-0492] Scaling of airfoil self-noise using measured flow arameters p 304 A85-21858 Some important problems in unsteady boundary layers parameters
- including separation. 1: Nature of singularity on oscillating airfoils
- p 294 N85-16087 [AD-A147897] Technology developments for laminar boundary layer control on subsonic transport aircraft
- p 237 N85-16787 LAMINAR FLOW
- The effect of phase-difference on the spreading rate
- of a laminar circular jet under bi-modal excitation p 208 A85-19479 [AIAA PAPER 85-0045] A comparison of flight test and analytical techniques
- for boundary layer transition on a sailplane [AIAA PAPER 85-0075] p 210 A85-19501 The aerodynamic effect of surface wetting characteristics on a laminar flow airfoil in simulated heavy
- nin [AIAA PAPER 85-0260] p 247 A85-19619
- Potential flow calculations and preliminary wing design in support of an NLF variable sweep transition flight experiment [AIAA PAPER 85-0426] p 248 A85-19741
- Flight testing of a wing section with laminar flow control p 233 A85-22227

- Aircraft drag reduction technology
- p 257 N85-16782 Design studies of thick laminar flow airfoils for low speed flight employing turbulent boundary layer suction over the p 257 N85-16786 rear part
- Pneumatic turbulators: A device for drag reduction at Reynolds numbers below 5 million p 257 N85-16791 LAMINAR FLOW AIRFOILS
- Experimental and theoretical analysis of laminar separation bubbles
- p 288 A85-20874 [AIAA PAPER 84-2201] LAMINAR HEAT TRANSFER
- Laminar heat-transfer distributions on biconics at incidence in hypersonic-hypervelocity flows [NASA-TP-2213] p 293 p 293 N85-16065
- LAMINAR WAKES
- Theoretical study of blockage effect of wind-tunnel wall on wake of two-dimensional flat plate normal to plane wall p 272 A85-19402
- Experimental investigation of blockage effect of upper wall of wind-tunnel of wake of two-dimensional flat plate p 272 A85-19403 normal to plane boundary AMINATES
- Aeroelastic stability and vibration of layered plates and cylindrical shells p 288 A85-20472
- Vibration tailoring of advanced composite lifting urfaces p 290 A85-21846 surfaces Composite repair of aircraft structures
- p 285 N85-17059 LANDING GEAR
- Testing solution for IL-76 braking system problem p 256 N85-16766
- LANDING LOADS Optimization of airplane wing structures under landing inads
- ads p 252 A85-22005 Development of a preliminary ALRS stabilized material avement analysis system (SPAS) n 277 N85-15760
- AD-A1471161 LARGE SPACE STRUCTURES
- Research and technology highlights of the Lewis Research Center [NASA-TM-86899] p 309 N85-17928
- LASER APPLICATIONS
- Theoretical and experimental analyses of laser altimeters for barometric measurements over the ocean p 298 N85-17351 NASA three-laser airborne differential absorption lidar
- system electronics p 298 N85-17353 [NASA-CR-174293]
- LASER DOPPLER VELOCIMETERS Examining the validity of a combustor flow model with
- p 209 A85-19487
- [AIAA PAPER 85-0055] Measurements of separating boundary layer and wake of an airfoil using laser Doppler velocimetry p 214 A85-19572
- [AIAA PAPER 85-0181] LASER GYROSCOPES
- Flight testing of Litton laser gyro strapdown system LTN-90 for general aviation [DFVLR-MITT-84-16] p 245 N85-15709
- LASER INTERFEROMETRY
- metry to density p 206 A85-19406 Application of laser interferometry measurements in free jets Turbulence measurement interferometer apparatus [AD-D011377] p 295 N85-16156
- LATERAL CONTROL Flight tests with a new helicopter Force Feel System
- (FFS) p 257 N85-16818 LATERAL OSCILLATION
- Clearance flow-generated transverse forces at the rotors of thermal turbomachines [NASA-TM-77292] p 295 N85-16180
- LATERAL STABILITY
- Theory of wing rock [AIAA PAPER 85-0199] p 268 A85-19583 Aileron effectiveness for a subsonic transport model with
- a high-aspect-ratio supercritical wing [NASA-TM-85674] p 235 N85-15695
- LATTICES (MATHEMATICS) Comparison of analytical and experimental steadyand
- unsteady-pressure distributions at Mach number 0.78 for a high-aspect-ratio supercritical wing model with oscillating control surfaces [NASA-TM-84589] p 235 N85-15697
- LAUNCHING Voice command weapons launching system
- [AD-D011378] p 293 N85-15940 LEADING EDGE SLATS
- Design of an airfoil leading edge slat using an inverse p 256 N85-16777 aerodynamic calculation method LEADING EDGES
- A theory for the core of a three-dimensional leading-edge
- [AIAA PAPER 85-0108] p 210 A85-19524

An attached flow design of a noninterfering leading edge extension to a thick delta wing

LIFT DRAG RATIO

- [AIAA PAPER 85-0350] p 220 A85-19689 Progress in development of a Navier-Stokes solver for evaluation of iced airfoil performance
- [AIAA PAPER 85-0410] p 222 A85-19731 Analysis and testing of the Diamond One wing anti-icing
- system p 286 A85-19735 [AIAA PAPER 85-0414] A summary of NASA's research on the fluid ice protection
- /stem [AIAA PAPER 85-0467] p 241 A85-19768
- LEAKAGE Clearance flow-generated transverse forces at the rotors
- of thermal turbomachines p 295 N85-16180 [NASA-TM-77292]
- LEAST SQUARES METHOD Parametric estimates of propulsion system maintenance manhours
- (AD-A147120) p 201 N85-15662 LIABILITIES
- The division of tasks in modern air transport and its effect on the liability of the air carrier - The concept 'agents' in the so-called Warsaw Convention -- German thesis
- p 307 A85-19826 LIFE (DURABILITY)
- Monitoring engine thermal stresses

by analysis and testing

and versatiility

circuits

rainfall

LIFT

[AD-A147798]

LIFE CYCLE COSTS

increased availability

full scale development program

[AIAA PAPER 85-0005]

[AIAA PAPER 85-0257]

[AIAA PAPER 85-0282]

[AGARD-CP-365]

high lift systems

of attack

oroiect

LIFT DEVICES

rain

high lift systems

LIFT DRAG RATIO

low-speed wind tunnel

for transport aircraft

LIFT AUGMENTATION

[AIAA PAPER 85-0446]

[AIAA PAPER 85-0260]

Comparison with calculations

unsteady two-dimensional lifting flows

Investigations into the effects

Study of winglets applied to biplanes [AIAA PAPER 85-0279]

The aerodynamic effect of

Forward sweep - The pros and cons

Boundary Layer Control and High Lift Systems

- p 266 N85-15735 Accelerated Mission Endurance Testing (AMET)
- p 266 N85-15736 Cumulative damage modeling of fatigue crack growth

p 267 N85-15751

p 266 N85-15736

p 296 N85-16736

p 246 N85-16804

p 297 N85-17298

p 262 A85-19453

p 216 A85-19617

p 217 A85-19633

p 204 N85-16771

p 236 N85-16772

p 236 N85-16773

p 236 N85-16775

p 296 N85-16779

p 257 N85-16781

p 217 A85-19631

p 224 A85-19755

p 236 N85-16772

surface wetting

p 247 A85-19619

p 250 A85-20146

A-23

- p 267 N85-15741 Problems and possibilities for life extension in gas turbine
- p 267 N85-15742 components Engine cyclic durability by analysis and material p 267 N85-15744
- testina Life prediction at high temperature under multiaxial p 267 N85-15745
- loading Verification of life prediction through component p 292 N85-15748 testing View of future requirements for engine cyclic durability

Effective life cycle software support: A study in discipline nd versatiility p 302 N85-16746

A practical example of reducing life cycle costs and

Standard Attitude Heading Reference System (SAHRS)

Life cycle cost model for very high speed integrated

Analysis of counter-rotating propeller performance

Scaling laws for testing of high lift airfoils under heavy

Application of continuous vorticity panels to general

Improvement of Aerodynamic Performance Through

Recent progress of development and understanding of

Investigations into the effects of scale and compressibility on lift and drag in the RAE 5m pressurized

Detailed study of the flow around a multi-element airfoil.

Turbulent bubbles behind airfoils and wings at high angle

Aerodynamic issues in the design of high-lift systems

An update of the Canada/USA augmentor-wise roject

Trapping of free vortex by airfoils with surface suction

Recent progress of development and understanding of

characteristics on a laminar flow airfoil in simulated heavy

Accelerated Mission Endurance Testing (AMET)

LIFTING BODIES

LIFTING BODIES

- Comparative study of various quadratures for subsonic lifting surface chordwise integrals p 205 A85-19404 Aerodynamic prediction of eliptically-shaped missile
- configurations using component build-up methodology [AIAA PAPER 85-0271] p 216 A85-19624 Finite element solutions of Euler equations for lifting
- airfoils [AIAA PAPER 85-0294] p 230 A85-20864 Vibration tailoring of advanced composite lifting surfaces p 290 A85-21846
- surfaces p 290 A85-21846 Extremum problem concerning a wing with a maximum gradient of lift force p 234 A85-22370
- An investigation of vortex-induced aerodynamic characteristics of supersonic cruise configurations [NASA-CR-174299] p 234 N85-15690
- Comparison of analytical and experimental steadyand unsteady-pressure distributions at Mach number 0.78 for a high-aspect-ratio supercritical wing model with oscillating control surfaces [NASA-TM-84589] p 235 N85-15697
- LIFTING REENTRY VEHICLES The application of some lifting-body reentry concepts
- to missile design [AIAA PAPER 85-0497] p 279 A85-19791
- LIGHT AIRCRAFT Experimental methods for wind-tunnel flight-mechanics
- German thesis p 249 A85-19836 Analysis of fatal accidents involving light aircraft
- weighing up to two tons and their causes in the context of flight medicine -- German thesis p 241 A85-19846 Technology gains expected to yield LHX size, weight, cost reductions p 249 A85-20058
- LIGHT TRANSMISSION
- Passive control effects on flow separation around a protuberance at high subsonic speed --- for optical propagation quality enhancement to and from airborne platforms (AIAA PAPER 85-0351) p 220 A85-19690
- [AIAA PAPER 85-0351] p 220 A85-19690 LIGHTING EQUIPMENT
- Evaluation of arctic test of improved tritium radioluminescent lighting [AD-A148215] p 278 N85-16884
- LIGHTNING Atmospheric electricity hazards to aircraft operation
- [AIAA PAPER 85-0013] p 247 A85-19457 A study of the effects of triggered lightning [AD-A148296] p 300 N85-17494
- LIGHTNING SUPPRESSION Lightning simulation facilities in the United States and
- Europe [AIAA PAPER 85-0093] p 273 A85-19515
- The lightning threat to aerospace vehicles [AIAA PAPER 85-0094] p 240 A85-19516 LINEARIZATION
- A parallel quasi-linearization algorithm for air vehicle trajectory optimization
- [AIAA PAPER 85-0498] p 279 A85-19792 LIQUID FUELS Off-design point characteristics of the precooled gas
- turbine cycle with liquefied hydrogen as fuel p 289 A85-20884
- LIQUID HYDROGEN
- Off-design point characteristics of the precooled gas turbine cycle with liquefied hydrogen as fuel p 289 A85-20884
- LIQUID OXYGEN Ultrasound instrumentation for the 7 inch Mach seven
- [NASA-CR-174277] p 305 N85-16586 LOAD DISTRIBUTION (FORCES)
- Evaluation of operational loads to verify structural design p 254 N85-15677 LOADING RATE
- Development of a fatigue crack propagation model of Incoloy 901 p 280 A85-20758 LOADS (FORCES)
- Operational Loads Data
- [AGARD-CP-375] p 201 N85-15664 Experiences obtained from service fatigue monitoring
- exercises p 292 N85-15672 US Army helicopter operational flight loads p 254 N85-15675
- Helicopter data acquisition in WHL p 254 N85-15676
- A theoretical view on the stress analysis of fully inflated parachute canopies [AD-A148387] p 239 N85-16835
- Distribution and storage of aviation turbine fuel for military operations in northern Australia [AD-A147180] p 283 N85-15921
- A description of a logistically ideal aircraft [AD-A148425] p 258 N85-16866

- LOGISTICS MANAGEMENT
- Managing recoverable aircraft components in the PPB and related processes: Executive summary [AD-A146806] p 308 N85-16667
- [AD-A146806] p 308 N85-16667 Utilization of Increased Airlift Capability (UIAC) study
- [AD-A148669] p 243 N85-16847 LONGERONS
- Advanced-composite joints and fittings for primary structural components p 290 A85-21385 LONGITUDINAL CONTROL
- Flight tests with a new helicopter Force Feel System (FFS) p 257 N85-16818 LONGITUDINAL STABILITY
- A longitudinal stability augmentation system for a tilt rotor aircraft
- [AIAA PAPER 85-0072] p 268 A85-19498 LOOP ANTENNAS
- Tactical HF communication for military helicopters using the NVIS mode p 297 N85-16807 LOSSES
- An improved computer model for prediction of axial gas turbine performance losses [NASA-CR-174246] p 265 N85-15724
- [NASA-CR-174246] p 265 N85-15724 LOW DENSITY FLOW Application of laser interferometry to density
- Application of laser interferometry to density measurements in free jets p 206 A85-19406 LOW REYNOLDS NUMBER
- The design of airfoils at low Reynolds numbers [AIAA PAPER 85-0074] p 209 A85-19500
- Flows over low Reynolds number airfoils Compressible Navier-Stokes numerical solutions
- [AIAA PAPER 85-0107] p 210 A85-19523 Improvements in low Reynolds number testing in the
- NSWC hypervelocity wind tunnel No. 9 [AIAA PAPER 85-0226] p 274 A85-19602
- Evaluation of low Reynolds number turbulence models for attached and separated flows [AIAA PAPER 85-0375] p 286 A85-19706
- LOW SPEED
- Benefits and costs of powered engine simulation at low speeds
- [AIAA PAPER 85-0381] p 263 A85-19710 Design studies of thick laminar flow airfoils for low speed flight employing turbulent boundary layer suction over the rear part p 257 N85-16786
- Recent methods for calibrating the anemometry of helicopters at low speeds p 260 N85-16809 LOW SPEED WIND TUNNELS
- A numerical simulation of the NFAC (National Full-scale Aerodynamics Complex) open-return wind tunnel inlet flow
- [AIAA PAPER 85-0437] p 230 A85-20869 Investigations into the effects of scale and compressibility on lift and drag in the RAE 5m pressurized low-speed wind tunnel p 236 N85-16773 LOW VISIBILITY
- Status of warm fog dispersal research
- [AIAA PAPER 85-0010] p 272 A85-19456 LUBRICANTS
- A theoretical study of stability of a rigid rotor under the influence of dilute viscoelastic lubricants [ASME PAPER 84-TRIB-17] p 289 A85-21278

M

- MACH NUMBER
- Comparison of analytical and experimental steadyand unsteady-pressure distributions at Mach number 0.78 for a high-aspect-ratio supercritical wing model with oscillating control surfaces
 - [NASA-TM-84589] p 235 N85-15697 Joined wing transonic design and test validation [AD-A148355] p 239 N85-16834
- MAGNESIUM ALLOYS Review of the origin of Japanese Industrial Standard
- p 280 A85-20545
- Design and test of a four channel motor for electromechanical flight control actuation [NASA-CR-171838] p 297 N85-17294
- MAINTAINABILITY Design for Tactical Avionics Maintainability
- [AGARD-CP-361]
 p 201
 N85-16731

 Objectives in studying the maintainability of aircraft systems
 p 202
 N85-16732
- Joint service design for testability program p 296 N85-16733 The embedded test (BIT): Impact on the total cost of
- possession p 202 N85-16734 ATE user's view on design for maintainability p 202 N85-16737
- Maintainability: An ILS effort to manipulate LCC p 202 N85-16743
- A description of a logistically ideal aircraft [AD-A148425] p 258 N85-16866

MAINTENANCE

Optimal maintenance center inventories for fault-tolerant repairable systems p 301 A85-21548 System for rapid repair of damaged airtield runways [AD-D011325] p 276 N85-15754 Managing recoverable aircraft components in the PPB

SUBJECT INDEX

- and related processes: Executive summary [AD-A146806] p 308 N85-16667
- Maintainability: An ILS effort to manipulate LCC p 202 N85-16743
- A weapon system design approach to diagnostics p 203 N85-16752
- Flight service evaluation of advanced composite ailerons on the L-1011 transport aircraft
- [NASA-CR-172483] p 284 N85-17049 Repair of composites p 284 N85-17058
- MAN MACHINE SYSTEMS
 - Trends in digital flight control systems p 269 A85-21465
- International aviation (selected articles) [AD-A148704] p 204 N85-16762
- Integrated control and display systems for helicopter battlefield mission management p 260 N85-16805
- A review of US Army aircrew-aircraft integration research programs p 270 N85-16814
- Time series analysis of closed-loop pilot vehicle dynamics p 271 N85-16876

MANAGEMENT

and versatiility

[AD-A147120]

MANUFACTURING

[BLL-PNR-90237-(899.3153)]

Map display for helicopters

Flow measurement device

ionization mass spectrometry [AD-A147724]

MARINE TRANSPORTATION

aircraft parts

[AD-A147295]

industry

MAPPING

MASS FLOW

[AD-D011432]

MASS SPECTROSCOPY

MATERIALS SCIENCE

Research Center

aircraft

[NASA-TM-86899]

MATHEMATICAL MODELS

[AIAA PAPER 85-0072]

for helicopter rotor icing

[AIAA PAPER 85-03361

[AIAA PAPER 85-0438]

universalization

manual, version 2

[AD-A148363]

[AD-A147708]

MANPOWER

manhours

- Distribution and storage of aviation turbine fuel for military operations in northern Australia [AD-A147180] p 283 N85-15921
- MANAGEMENT INFORMATION SYSTEMS
- National Airspace Review
- [AD-A147768] p 246 N85-16855 MANAGEMENT METHODS
- Performance evaluation of A-10 aircraft mainteance units and aircraft using constrained facet analysis [AD-A146955] p 201 N85-15660
- A Q-GERT network simulation model for examining pipeline time in the Navy's J-52 intermediate level jet engine repair cycle
- [AD-A147269] p 201 N85-15663 Effective life cycle software support: A study in discipline

Parametric estimates of propulsion system maintenance

Flexible manufacturing system for the production of

The effects of manufacturing automation on the surge

and mobilization capabilities of the gas turbine engine

Renegade 250 - Flight evaluation or boat ride?

Analysis of middle distillate fuels by high resolution field

Research and technology highlights of the Lewis

A longitudinal stability augmentation system for a tilt rotor

The development of mathematical modelling techniques

The fundamental equations of 3-dimensional two-phase

A formalism for the design problem of aircraft system

Artificial dissipation models for the Euler equations

A Generalized Escape System Simulation (GESS)

computer program. Volume 2: GESS programmer's

Production rate variations cost models

particulate gas flow and a twofold stream surfaces model

of solution for particulate gas flow in turbomachines

p 302 N85-16746

p 201 N85-15662

p 297 N85-17159

p 297 N85-17162

p 259 N85-16801

p 252 A85-22273

p 298 N85-17369

p 285 N85-17153

p 309 N85-17928

p 268 A85-19498

p 240 A85-19679

p 228 A85-20233

p 250 A85-20473

p 231 A85-20870

p 243 N85-16845

p 308 N85-17732

MATRICES (MATHEMATICS)

Matrix solution of compressible flow on S(1) surface through a turbomachine blade row with splitter vanes or tandem blades p 227 A85-20228 MATRIX MATERIALS

Flexible matrix composites applied to bearingless rotor systems p 281 A85-21389

MATRIX METHODS Universal matrices to obtain thermal load vectors for the family of anisotropic plane triangular finite elements p 291 A85-22232

MAXIMUM LIKELIHOOD ESTIMATES

More than you want to	s know about	maximum	likelihood
estimation			
[NASA-TM-85905]		p 270 N	185-15752

MEASURING INSTRUMENTS

Advanced fatigue monitoring on service aircraft p 292 N85-15671

High temperature thermocouple and heat flux gauge using a unique thin film-hardware hot juncture [NAŠA-TM-86898] 0 295 N85-16096

MECHANICAL PROPERTIES V-378A, a new modified bismaleimide matrix resin for

high modulus graphite p 282 A85-21482 **MECHANICS (PHYSICS)**

Ill-posed problems in perturbation theory (Asymptotic ethods of mechanics) p 233 A85-22364 methods of mechanics) MESOSCALE PHENOMENA

A method for determining mesoscale dynamic topography

[AD-D011412]	р 300	N85-17506
METAL FATIGUE		

Development of a fatigue crack propagation model of Incoloy 901 p 280 A85-20758 Fatigue crack growth behavior of 7XXX aluminum alloys under simple variable amplitude loading

p 280 A85-20759 Interpretation of fatigue crack growth in aluminium alloys under programmed block loading p 281 A85-20790

Cumulative damage modeling of fatigue crack growth p 267 N85-15741 METEOROLOGICAL INSTRUMENTS

- Evaluation of the forward scattering sp ctrometer probe. I Electronic and optical studies p 291 A85-22168 METEOROLOGICAL PARAMETERS
- The visibility climatology of McMurdo Sound-Williams Field, Antarctica

[AD-A148108] p 300 N85-17492 METEOROLOGICAL RADAR Radar for storm forecasting and weather hazard

[AIAA PAPER 85-0092] p 299 A85-19514

Aviation radar --- Russian book p 244 A85-19805 METEOROLOGICAL SERVICES

- Safety Meteorological data vital for simulator training [AIAA PAPER 85-0091] p 240 A85-19513 p 240 A85-19513 METHOD OF CHARACTERISTICS
- Theoretical study on supersonic jet plumes
- p 206 A85-19439 Calculation of viscous nozzle flows by the unsteady method of characteristics
- [AIAA PAPER 85-0131] p 212 A85-19542 METHODOLOGY

A design methodology for integrated avionic systems D 301 A85-21458

MICROCOMPUTERS

Control system design language implementation of a gas turbine starting controller [AD-A147896] p 266 N85-15732

Ultrasound instrumentation for the 7 inch Mach seven tunnei

[NASA-CB-174277] p 305 N85-16586 MICROPROCESSORS

- Microprocessor control of turboprop engines p 263 A85-19877 Control system design language implementation of a
- gas turbine starting controller [AD-A147896] p 266 N85-15732
- Functional built-in-test in a pipelined image processor p 202 N85-16740 MILITARY AIR FACILITIES
- Installation restoration program. Phase 2: Stage 1 problem confirmation study, Duluth International Airport
- Duluth, Minnesota [AD-A148318] p 278 N85-16885 MILITARY AIRCRAFT
- Environmental test capabilities of the Air Force McKinley Climatic Laboratory
- [AIAA PAPER 85-0089] p 273 A85-19512 Combat aircraft: Flight vehicles, power plants, and their maintenance — Russian book p 199 A85-19812 Army, NASA researching needs for future engine p 263 A85-20060 components
- Radar cross section lectures --- Book
 - p 289 A85-20915

Hardware design techniques --- systems integration for civil and military aircraft avionics p 244 A85-21459 Integrated communications - A designers view --- for p 245 A85-21462 civil and military aircraft avionics The Air Force stock fund and aircraft availability

p 203 N85-16761 [AD-A148653] Mission-oriented requirements for updating MIL-H-8501. Volume 1: STI proposed structure --- military rotorcraft [NASA-CR-177304-VOL-1] p 271 N85-16877 Mission-oriented requirements for updating MIL-H-8501. Volume 2: STI background and rationale --- military

rotorcraft [NASA-CR-177304-VOL-2] p 271 N85-16878 Using the control system design environment in the design of a data link receiver unit for the Coast Guard HH-65A helicopter

[AD-A148624] p 271 N85-16880 MILITARY AVIATION

Keeping up with operational loads in the French Air Defining new equipment p 292 N85-15681 MILITARY HELICOPTERS

- Advanced helicopter technology Industry girds for challenges of evolving operational needs
- p 199 A85-20057 Technology gains expected to yield LHX size, weight, cost reductions p 249 A85-20058 Mi-28 The Soviets create Havoc p 250 A85-20147 K747 composite main rotor blade modification, analysis and qualification for new high temperature requirements
- p 251 A85-21378 Advanced composites - Designed to survive --- helicopter p 251 A85-21387 safety in modern battlefield Environmental effects and durability evaluation of

advanced composite fuselage structures p 251 A85-21388

The impact of integrated systems - The helicopter designer's viewpoint p 252 A85-21467 US Army helicopter operational flight loads

p 254 N85-15675 Speed benefits of tilt-rotor designs for LHX p 255 N85-15717 [NASA-CR-166437]

A digital piloting system for the combat helicopter p 260 N85-16806

- Tactical HF communication for military helicopters using p 297 N85-16807 the NVIS mode Evaluation of nose, roof, and mast mounted sensor platforms for piloting and sighting, integrated in future p 260 N85-16808 combat helicopters
- The design and development of an integrated core system for battlefield helicopters p 260 N85-16811 Evolution toward a multi-bus architecture for Army p 260 N85-16812 helicopter avionic systems
- A review of US Army aircrew-aircraft integration research p 270 N85-16814 programs A simulator for studying helicopter weapons systems p 277 N85-16816
- Preliminary airworthiness evaluation AH-1S (MC) helicopter with external fuel tanks installed
- p 258 N85-16865 [AD-A148091] MILITARY OPERATIONS

Calculation of the exchange ratio for the Adaptive Maneuvering Logic program [AIAA PAPER 85-0311]

p 199 A85-19658 Distribution and storage of aviation turbine fuel for military operations in northern Australia

[AD-A147180] p 283 N85-15921 The Air Force can improve its forecasts of aircraft spare parts requirements

- [AD-A147911] p 308 N85-16682 Estimating wartime support resource requirements. Statistical and related policy issues p 308 N85-16685
- [AD-A147923] technological Operational requirements versus p 204 N85-16798 capabilities Automatic briefing and mission management systems
- for battlefield support p 259 N85-16799 Standard Attitude Heading Reference System (SAHRS)
- full scale development program p 246 N85-16804 Integrated control and display systems for helicopter p 260 N85-16805 battlefield mission management Evaluation of nose, roof, and mast mounted sensor platforms for piloting and sighting, integrated in future
- combat helicopters p 260 N85-16808 MILITARY TECHNOLOGY airborne
- New generation military tactical airborne communications systems The interoperability challenge p 244 A85-19275 Military avionics - Increasing integration at all levels
- p 244 A85-20221 Documentation and separate test program development
- is most important for test/maintenance p 203 N85-16745

Helicopter Guidance and Control Systems for Battlefield Support

[AGARD-CP-359] p 204 N85-16797 MINICOMPUTERS

Some problems in the development of CAD systems -- for design of minicomputer digital components p 200 A85-20466

MRCA AIRCRAFT

MINIMUM DRAG

Arrays for minimum wave drag of bodies of revolution (AIAA PAPER 85-0449) p 249 A85-19758 p 249 A85-19758 MIRAGE AIRCRAFT

Aeroelastic analysis and the identification of flight loads Mirage 2000 aircraft p 254 N85-15679 Map display for helicopters p 259 N85-16801

MISSILE BODIES

- Flow visualization of high angle of attack vortex wake structures [AIAA PAPER 85-0102]
- p 286 A85-19520 Correlation and analysis of oil flow data for an
- air-breathing missile model [AIAA PAPER 85-0452] p 224 A85-19761
- MISSILE COMPONENTS
- Aerodynamic prediction of eliptically-shaped missile configurations using component build-up methodology [AIAA PAPER 85-0271] p 216 A85-19624 p 216 A85-19624 **MISSILE CONFIGURATIONS**
- Aerodynamic prediction of eliptically-shaped missile configurations using component build-up methodology [AIAA PAPER 85-0271] p 216 A85-19624
- Aerodynamic configured missiles Promise and future p 248 A85-19684 [AIAA PAPER 85-0345]
- Interactive design technique for arbitrary shaped, airbreathing missile configurations [AIAA PAPER 85-0496] p 249 A85-19790
- **MISSILE CONTROL**

Prediction of cruciform all-movable control characteristics at transonic speeds

[AD-A147291] p 239 N85-16832 MISSILE DEFENSE

Influence of propulsion/mission profile combinations upon generic missile penetration of a hypothetical detense

[AIAA PAPER 85-0495] p 249 A85-19789 MISSILE DESIGN

Aerodynamic prediction of eliptically-shaped missile

Configurations using component build-up methodology [AIAA PAPER 85-0271] p 216 A85-19824 Influence of propulsion/mission profile combinations upon generic missile penetration of a hypothetical defense

[AIAA PAPER 85-0495] p 249 A85-19789 Interactive design technique for arbitrary shaped,

airbreathing missile configurations [AIAA PAPER 85-0496] p 249 A85-19790 The application of some lifting-body reentry concepts

- to missile design [AIAA PAPER 85-0497] p 279 A85-19791 MISSILE SIMULATORS
 - Influence of propulsion/mission profile combinations upon generic missile penetration of a hypothetical defense

AIAA PAPER 85-04951 p 249 A85-19789 MISSION PLANNING

Automatic briefing and mission management systems for battlefield support p 259 N85-16799 A Computer-generated topographic display system for

navigation and mission planning in helicopters p 259 N85-16800

MIXERS				
Three-dimensional	inviscid	flow	analysis	of turbofan
forced mixers				
[AIAA PAPER 85-008	6]		p 210	A85-19510

V-378A, a new modified bismaleimide matrix resin for

PMR polyimide composites for aerospace applications

Flight parameters recording for structure fatigue life

Study and realisation of a 3rd level maintenance center

Mounting construction for turbine vane assembly

Structural Usage Monitoring System p 292 N85-15680

Structural Usage Monitoring System

p 255 N85-15713

p 282 A85-21482

p 237 N85-16788

p 282 A85-21520

p 265 N85-15723

p 292 N85-15680

p 292 N85-15682

p 202 N85-16735

A-25

F-8 refueling boom ground vibration test [NASA-TM-84914] p 25

Turbulent drag reduction research

--- Polymerization of Monomer Reactants

based on ATE systems utilization

MODAL RESPONSE

MOMENTUM

MONITORS

(SUMS)

MONOMERS

MOUNTING

(SUMS)

monitoring

[AD-D011395]

MRCA AIRCRAFT

Tomado:

Tornado:

MOISTURE RESISTANCE

high modulus graphite

MULTIPROCESSING (COMPUTERS)

MULTIPROCESSING (COMPUTERS)

Evolution toward a multi-bus architecture for Army p 260 N85-16812 helicopter avionic systems MULTIVARIATE STATISTICAL ANALYSIS

Tail behaviour for suprema of empirical processes p 303 N85-17613 [AD-A147629]

Ν

- NACELLES
- A comparison of different three-dimensional singularity methods for modelling internal flows
- [ONERA, TP NO. 1984-150] p 205 A85-19264 Tests of air inlets on civil aircraft p 272 A85-19271 [ONERA, TP NO. 1984-157]
- Simulation of transonic three-dimensional nacelle/inlet flowfields using an Euler/Navier-Stokes algorithm [AIAA PAPER 85-0084] p 226 A85-19798
- installed nacelle drag-improvement tests of an M = 0.8turboprop transport configuration
- [NASA-TM-843021 p 255 N85-15716 NAP-OF-THE-EARTH NAVIGATION
- Assessment of simulation fidelity using measurements of piloting technique in flight p 278 N85-16817 NASA PROGRAMS
- The Western Aeronautical Test Range of NASA Ames Research Center p 275 A85-19678
- [AIAA PAPER 85-0316] Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) [AIAA PAPER 85-0379] p 275 A85-19709 Army, NASA researching needs for future engine
- p 263 A85-20060 components Scientific and technical information output of the Langley
- Research Center for calendar year 1984 p 309 N85-17740 [NASA-TM-86336] NASTRAN
- Composite curved frames for helicopter fuselage p 252 A85-21396 structure
- NATIONAL AVIATION SYSTEM Satellite navigation
- S-HRG-98-856] p 246 N85-16851 NAVIER-STOKES EQUATION
- Current status of numerical solutions of the Navier-Stokes equations
- [AIAA PAPER 85-00321 p 207 A85-19469 An incremental block-line-Gauss-Seidel method for the Navier-Stokes equations [AIAA PAPER 85-0033] p 207 A85-19470
- A multistage time-stepping for scheme the Navier-Stokes equations [AIAA PAPER 85-00351 p 207 A85-19472
- Accelerated convergence for incompressible flow calculations
- [AIAA PAPER 85-0058] p 209 A85-19489 Flows over low Reynolds number airfoils - Compressible Navier-Stokes numerical solutions
- [AIAA PAPER 85-0107] p 210 A85-19523 A comparison of Euler and Navier-Stokes solutions for supersonic flow over a conical delta wing
- p 210 A85-19526 AIAA PAPER 85-01111 Numerical solution of unsteady viscous flow past rotor sections
- [AIAA PAPER 85-0129] p 212 A85-19540 Analysis of circulation control airfoils using an implicit Navier-Stokes solver
- [AIAA PAPER 85-0171] p 213 A85-19565 A Navier-Stokes investigation of a circulation control airfoil
- p 219 A85-19649 [AIAA PAPER 85-0300] A three-dimensional Navier-Stokes/Euler code for
- blunt-body flow computations [AIAA PAPER 85-0361] p 220 A85-19696 A Navier-Stokes calculation of 3-D, turbulent flow near
- propeller in a shear flow [AIAA PAPER 85-0365] p 220 A85-19698
- Navier-Stokes computations of axisymmetric transonic flows with a two-equation model of turbulence
- p 221 A85-19705 [AIAA PAPER 85-0373] Progress in development of a Navier-Stokes solver for evaluation of iced airfoil performance
- [AIAA PAPER 85-0410] p 222 A85-19731 Simulation of transonic three-dimensional nacelle/inlet flowfields using an Euler/Navier-Stokes algorithm
- [AIAA PAPER 85-0084] p 226 A85-19798 Navier-Stokes computations for exotic airfoils
- [AIAA PAPER 85-0109] p 230 A85-20855 Development of a Navier-Stokes rotor and stator analysis
- [AD-A146967] p 294 N85-16070 NAVIGATION
- Map display for helicopters p 259 N85-16801 Development of a Helicopter integrated navigation system p 245 N85-16802

Standard Attitude Heading Reference System (SAHRS) p 246 N85-16804 full scale development program Integrated control and display systems for helicopter battlefield mission management p 260 N85-16805

NEAR FIELDS

Reflector antennas with directional effect in the near-field Characteristics and applications --- German p 287 A85-19837 thesis

NICHROME (TRADEMARK)

Metallurgical and mechanical phenomena due to rubbing of titanium against sintered powder Nichrome p 291 A85-22281

NICKEL

- Comparison between the properties of conventional wrought and powder metallurgical alloys for turbine disc p 283 N85-15739 applications NICKEL ALLOYS
- Development of a fatigue crack propagation model of Incoloy 901 p 280 A85-20758 Problems and possibilities for life extension in gas turbine p 267 N85-15742 components
- NIGHT FLIGHTS (AIRCRAFT) Flight research on visusl aids and navigation equipment
- for helicopter low-level flight at night p 261 N85-16820 NITROGEN
- Flow of nitrogen-pressurized Halon 1301 in fire
- extinguishing systems [NASA-CR-174271] p 242 N85-15701 NITROGEN OXIDES
- Impact of aircraft emissions on air quality in the vicinity Volume 4. of airports Nitrogen dioxide and hydrocarbons
- [AD-A148253] p 299 N85-17436 NOISE (SOUND)
- On boundary layer transition in high-subsonic and transonic flow under the influence of acoustic disturbances and free-stream turbulence
- [AIAA PAPER 85-0082] p 210 A85-19508 **NOISE INTENSITY**
- Investigation on experimental techniques to detect, locate and quantify gear noise helicopter in transmissions p 305 N85-17667 [NASA-CR-38471
- NOISE MEASUREMENT
- Noise of an airfoil in a flow [ONERA, TP NO. 1984-155]
- p 303 A85-19269 The unambiguous in-flight determination of propeller rotational noise in aircraft with four-cycle combustion enaines p 304 A85-20650
- Helicopter noise survey performed at Las Vegas, Nevada, 19-21 January, 1984 [AD-A147392] p 305 N85-16593
- Noise measurement flight test: Data-analyses aerospatiale AS-355F TwinStar helicopter p 305 N85-16595 [AD-A147497]
- Noise measurement flight test for Boeing Vertol 234/CH 47-d helicopter: Data/analyses
- p 306 N85-17670 [AD-A148172] Noise measurement flight test: Aerospatiale AS 350D AStar helicopter Data-analyses
- [AD-A148496] p 306 N85-17672 Noise measurement flight test: Data-analyses, Sikorsky S-76A helicopter
- [AD-A148525] p 306 N85-17673 **NOISE POLLUTION**
- overview Ал of helicopter's environmental considerations p 241 A85-21643 Acoustical guidelines for new heliports
 - p 276 A85-21644 A path model of aircraft noise annovance p 304 A85-22071
- NOISEMAP 4.4 computer program update, operator's manual, addendum 1
- AD-A1470911 p 302 N85-16503 NOISE PROPAGATION
- Investigation of nonlinear effects in the instabilities and noise radiation of supersonic jets
- [AIAA PAPER 85-0081] p 304 A85-19507 Field-incidence noise transmission loss of general aviation aircraft double-wall configurations
- p 304 A85-21842 NOISE REDUCTION
- An overview of helicopter's environmental considerations p 241 A85-21643 NOISE TOLERANCE
- A path model of aircraft noise annoyance
- p 304 A85-22071 NOISEMAP 4.4 computer program update, operators manual, addendum 1
- (AD-A1470911 p 302 N85-16503 NONDESTRUCTIVE TESTS
- Nondestructive inspection: Improved capabilities of technicians [AD-A147388] p 295 N85-16196

Approximate solution of a nonlinear problem of flow past a thin airfoil profile near a support surface

NONLINEAR SYSTEMS

NONLINEAR EQUATIONS

A generalized stability criterion for nonlinear dynamic systems --- modeling aircraft roll maneuvers

SUBJECT INDEX

p 233 A85-22368

p 300 A85-19586 [AIAA PAPER 85-0202] The development of digital attitude controllers - Its past, present and future p 302 A85-22449

NONLINEARITY

nozzie

NUMERICAL CONTROL

aircraft parts

military and commercial aircraft

[BLL-PNR-90237-(899.3153)]

[AIAA PAPER 85-0107]

(AIAA PAPER 85-0167)

[AIAA PAPER 85-0368]

[AIAA PAPER 85-0437]

NUMERICAL INTEGRATION

NUMERICAL STABILITY

[AIAA PAPER 85-0301]

[AIAA PAPER 85-0268]

OBSTACLE AVOIDANCE

OBLIQUE WINGS

lifting surface chordwise integrals

calculation of supersonic separated flows

and oblique wings using a new wake model

LPI-radar for helicopter obstacle warning

multiple component airfoils

NUMERICAL FLOW VISUALIZATION

Navier-Stokes numerical solutions

flow using a dual potential formulation

- An investigation of vortex-induced aerodynamic characteristics of supersonic cruise configurations p 234 N85-15690
- [NASA-CR-174299] p 234 N85-15690 Prediction of dynamic stall characteristics using advanced non-linear panel methods
- p 239 N85-16836 [AD-A148453]
- NONUNIFORM FLOW Three dimensional aerodynamics of an annular cascade
- in a non-uniform inlet flow [AIAA PAPER 85-0174] p 213 A85-19567 NOSE CONES
- Regarding parametric investigations of slender cone
- nose bluntness effects [AIAA PAPER 85-0349] p 220 A85-19688
- Laminar heat-transfer distributions on biconics at incidence in hypersonic-hypervelocity flows
- [NASA-TP-2213] p 293 N85-16065 NOZZLE DESIGN
- Aerodynamic studies linked to the development of deployable nozzles --- for upper stage ballistic missiles [ONERA, TP NO. 1984-149] p 205 A85-19263
- NOZZLE FLOW Calculation of viscous nozzle flows by the unsteady
- method of characteristics [AIAA PAPER 85-0131] p 212 A85-19542
- A method for calculating the performance of ejector ozzles p 287 A85-20232 Hypersonic multicycle gas jet with a strongly nozzles
- underexpanded stream at the nozzle section p 229 A85-20554
- Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems [NASA-CR-174271]
- p 242 N85-15701 NOZZLE GEOMETRY
- Aerodynamic studies linked to the development of deployable nozzles --- for upper stage ballistic missiles [ONERA, TP NO. 1984-149] p 205 A85-19263
- Experimental study of forward-located jet-interaction nozzles [AIAA PAPER 85-0454] p 224 A85-19762 Effect of the arrangement of apertures on the gain

coefficient during asymmetric gas injection into a Laval

Trends in digital engine control - Integration of propulsion

Flexible manufacturing system for the production of

Flows over low Reynolds number airfoils - Compressible

Numerical computation of viscous flowfields about

The numerical simulation of steady transonic rotational

A numerical simulation of the NFAC (National Full-scale

Comparative study of various quadratures for subsonic

A study of the effects of numerical dissipation on the

0

Numerical solution of the full-potential equation for rotors

Aerodynamics Complex) open-return wind tunnel inlet

control with flight control and avionic systems in future

Microprocessor control of turboprop engines

p 229 A85-20562

p 263 A85-19877

p 264 A85-21466

p 297 N85-17159

p 210 A85-19523

p 213 A85-19563

p 221 A85-19701

p 230 A85-20869

p 205 A85-19404

p 219 A85-19650

p 216 A85-19621

p 297 N85-16810

OCEANS

Theoretical and experimental analyses of laser altimeters for barometric measurements over the ocean p 298 N85-17351

- ONBOARD DATA PROCESSING Keeping up with operational loads in the French Air p 292 N85-15681 Force: Defining new equipment Designer on Aeroflot automated COMMO system
- development p 296 N85-16765 On-board processing for linescan sensors in miniature unmanned aircraft [RAE-TM-SPACE-327] p 261 N85-16870
- OPERATIONS
- Optimum performance parameters for ski-jump operations of USAF fighter aircraft [AD-A148532] p 258 N85-16867

OPTICAL EQUIPMENT

LPI-radar for helicopter obstacle warning p 297 N85-16810

OPTICAL RADAR

NASA three-laser airborne differential absorption lidar ystem electronics

[NASA-CB-174293] p 298 N85-17353 OPTIMAL CONTROL

Optimal control of flow of a viscous incompressible fluid p 290 A85-22105 Research on optimal control, stabilization and

computational algorithms for aerospace applications [NASA-CR-174318] p 303 N85-17603 OPTIMIZATION

TRO-2D - A code for rational transonic aerodynamic ontimization

[AIAA PAPER 85-0425] p 223 A85-19740 A procedure for optimization of the the aerothermodynamic design oí multistage

p 227 A85-19851 compressors --- German thesis Selection of rational models in the optimal planning of p 288 A85-20460 aeromechanical experiments

A formalism for the design problem of aircraft system universalization p 250 A85-20473 An improved computer model for prediction of axial gas

turbine performance losses p 265 N85-15724 [NASA-CR-174246] Predicted performance benefits of an adaptive digital

engine control system of an F-15 airplane p 265 N85-15729

[NASA-TM-85916] An optimization method for the preliminary design of interplanetary aerobraking missions p 238 N85-16822

ORBIT TRANSFER VEHICLES

Introductory aerothermodynamics of advanced space transportation systems p 231 A85-21827 ORBITS

An optimization method for the preliminary design of interplanetary aerobraking missions p 238 N85-16822 **ORIFICE FLOW**

Application of laser interferometry to density p 206 A85-19406 measurements in free jets **OSCILLATING CYLINDERS**

Some important problems in unsteady boundary layers including separation. 1: Nature of singularity on oscillating airfoils

[AD-A147897] p 294 N85-16087 **OSCILLATING FLOW**

Modes of shock-wave oscillations on spike-tipped hodies p 232 A85-21855 Calculation of three-dimensional unsteady incompressible flows by a vortex method

p 291 A85-22240 OUTLET FLOW

Effect of inlet and outlet flow conditions on the flow and performance of subsonic two-dimensional diffuse p 228 A85-20241

Oxidation and stabilization of jet fuels --- Russian book

OXIDATION RESISTANCE

p 281 A85-20925 Polyimide protective coatings for 700 deg service

p 282 A85-21527

Ρ

PANEL METHOD (FLUID DYNAMICS)

A comparison of different three-dimensional singularity methods for modelling internal flows

[ONERA, TP NO. 1984-150] p 205 A85-19264 Calculation of compressible potential flow about multielement airfoils using a finite field-panel approach multielement airfoils using a transformed p 207 A85-19473 [AIAA PAPER 85-0038] p 207 A85-19473 The use of panel methods for the development of low-subsonic wall interference and blockage corrections p 212 A85-19556 p 212 A85-19566 p 212 A85-19566 p 207 A85-19473

A new iterative matrix solution procedure for three-dimensional panel methods

[AIAA PAPER 85-0176] p 213 A85-19568

Linearized potential flow analysis of complex aircraft configurations by HISSS, a higher order panel method [AIAA PAPER 85-0281] p 217 A85-19632 Calcutation of steady flow about propellers by means of a surface panel method

[AIAA PAPER 85-0283] p 218 A85-19634 An attached flow design of a noninterfering leading edge extension to a thick delta wing

[AIAA PAPER 85-0350] p 220 A85-19689 Circulation around thick wings with free vortices --erman thesis p 227 A85-19848

German thesis Flowfield analysis of low bypass ratio test cells p 265 A85-21839

Prediction of dynamic stall characteristics using advanced non-linear panel methods

p 239 N85-16838 [AD-A148453] PANELS

Measurements of the response of transport aircraft ceiling panels to fuel pool fires [AIAA PAPER 85-0394]

p 240 A85-19720 Field-incidence noise transmission loss of general aviation aircraft double-wall configurations

p 304 A85-21842 Preliminary evaluation of an improved flammability test method for aircraft materials

[FAA-CT-84-22] p 242 N85-16840 Composite repair of aircraft structures

p 285 N85-17059 PARABOLIC DIFFERENTIAL EQUATIONS

- Noniterative three-dimensional grid generation using parabolic partial differential equations
- [AIAA PAPER 85-0485] p 300 A85-19782

PARACHUTE DESCENT Parachute expedition to Arctic PARACHUTES p 236 N85-16240

- Drag of the fundamental shapes of parachutes
- p 231 A85-20998
- Stress analysis and shaping of the canopy of a square parachute p 242 A85-21668 A theoretical view on the stress analysis of fully inflated
- parachute canopies AD-A148387] p 239 N85-16835
- PARALLEL PROCESSING (COMPUTERS) A parallel quasi-linearization algorithm for air vehicle

trajectory optimization [AIAA PAPER 85-0498] p 279 A85-19792

- PARAMETER IDENTIFICATION
- Aeroelastic analysis and the identification of flight loads --- Mirage 2000 aircraft p 254 N85-15679 More than you want to know about maximum likelihood
- estimation [NASA-TM-85905] p 270 N85-15752
- PARTICLE SIZE DISTRIBUTION
- Analysis of a split-flow inertial particle separator by finite elements --- for helicopter gas turbine engine p 231 A85-21845

PARTICLE TRAJECTORIES

- Computational particle trajectory analysis on a 3-dimensional engine inlet
- [AIAA PAPER 85-0411] p 222 A85-19732 Three-dimensional airflow and hydrometeor trajectory
- lculation with applications TAIAA PAPER 85-04121 p 222 A85-19733
- PASSENGER AIRCRAFT Evaluation of aircraft interior panels under full-scale cabin fire test conditions
- [AIAA PAPER 85-0393] p 240 A85-19719 PAVEMENTS
- System for rapid repair of damaged airfield runways [AD-D011325] p 276 N85-15754 Development of a preliminary ALRS stabilized material
- pavement analysis system (SPAS) [AD-A147116] p 277 N85-15760
- Aeroproyekt develops improved runway surfacing p 277 N85-16770
- PERFORMANCE
- Optimum performance parameters for ski-jump operations of USAF fighter aircraft
- p 258 N85-16867 [AD-A148532] PERFORMANCE PREDICTION
- Predicted performance benefits of an adaptive digital engine control system on an F-15 airplane [AIAA PAPER 85-0255] p 26 p 263 A85-19801
- A method for calculating the performance of ejector p 287 A85-20232
- Prediction of performance of aircraft gas turbines p 264 A85-21682 The influence of fastener flexibility on load transfer and
- fatigue life predictions for multirow bolted and riveted joints - aircraft structures [LBF-FB-172/84] p 296 N85-16219
- PERFORMANCE TESTS
- Analysis of counter-rotating propeller performance [AIAA PAPER 85-0005] p 262 A85-19453

A universal turboshaft engine test cell - Design considerations and model test results p 275 A85-19711 AIAA PAPER 85-03821 Experimental investigation of backswept centrifugal p 264 A85-20243 compressor impeller. I PERIODIC VARIATIONS The universal nature of zero-crossing time and velocity p 232 A85-21851 scales in turbulent shear flows PERSONNEL DEVELOPMENT Nondestructive inspection: Improved capabilities of technicians [AD-A147388] p 295 N85-16196 PERSONNEL MANAGEMENT Performance evaluation of A-10 aircraft mainteance units and aircraft using constrained facet analysis [AD-A146955] p 201 N85-15660 PERTURBATION THEORY Ill-posed problems in perturbation theory (Asymptotic p 233 A85-22364 methods of mechanics) PESTICIDES Installation restoration program. Phase 2: Stage 1 problem confirmation study, Duluth International Airport Duluth, Minnesota p 278 N85-16885 Preliminary evaluation of an improved flammability test method for aircraft materials [FAA-CT-84-22] p 242 N85-16840 PHOTOCHEMICAL REACTIONS Atmospheric photochemical modeling of turbine engine p 300 N85-17470 [AD-A147786] PHOTOSENSITIVITY Contrast sensitivity performance assessment of HUD p 259 A85-21593 PILOT ERROR Analysis of fatal accidents involving light aircraft PILOT PERFORMANCE Judgment and discipline - Recipe for survival p 241 A85-21582 Assessment of simulation fidelity using measurements p 278 N85-16817 Safety - Meteorological data vital for simulator training [AIAA PAPER 85-0091] p 240 A85-19513 p 240 A85-19513 History of the development and manufacture of flight simulators in Czechoslovakia and the rest of the world p 275 A85-19878 Analysis of the flow field about a T-45 using PANAIR [AD-A146811] AD-A146811] p 236 N85-15699 Directions of the West German Ministry of Transport for education and control of airline personnel (section 3, hapters 2 and 12) p 243 N85-16848 Directions of the West German Ministry of Transport chapters 2 and 12) for education and control or airline personnel, Report 6; p 244 N85-16849 chapters 3/A and 3/B PILOTLESS AIRCRAFT On-board processing for linescan sensors in miniature unmanned aircraft [RAE-TM-SPACE-327] p 261 N85-16870 PILOTS (PERSONNEL) Evaluation of arctic test of improved tritium radioluminescent lighting [AD-A148215] p 278 N85-16884 PIPE FLOW Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems NASA-CR-174271] p 242 N85-15701 PISTON ENGINES Some characteristics of automotive gasolines and their erformance in a light aircraft engine p 283 N85-15919 FAA-CT-84-121 PITCH (INCLINATION) Three-dimensional effects on a pitching lifting surface [AIAA PAPER 85-0041] p 208 A85-19476 Transient motion of hypersonic vehicles including time history effects [AIAA PAPER 85-0201] o 268 A85-19585 Ground interference effects on subsonic dynamic stall p 231 A85-21841 in pitch and plunge PITCHING MOMENTS An experimental investigation of an airfoil undergoing large amplitude pitching motions [AIAA PAPER 85-0039] p 207 A85-19474 PLANNING The Air Force can improve its forecasts of aircraft spare parts requirements [AD-A147911] p 308 N85-16682 PLATE THEORY

- [AD-A148318] PHENOLS

- fuels. Phase 1: Experimental studies. Volume 2: Environmental chamber data tabulations
- display systems

weighing up to two tons and their causes in the context of flight medicine --- German thesis p 241 A85-19846

of piloting technique in flight

PILOT TRAINING

PLUMES

PLUMES

- Theoretical study on supersonic jet plumes p 206 A85-19439
- PNELIMATIC FOUIPMENT Pneumatic turbulators: A device for drag reduction at
- Reynolds numbers below 5 million p 257 N85-16791 PODS (EXTERNAL STORES)
- Equipment for preflight test of an Electronic Countermeasures (ECM) avionic system p 293 N85-15949
- POLICIES
- National airspace review enhancement plan, revision 3 p 246 N85-16852 POLLUTION TRANSPORT
- Installation restoration program. Phase 2: Stage 1 problem confirmation study, Duluth International Airport Duluth, Minnesota
- [AD-A148318] p 278 N85-16885 POLYESTER RESINS
- System for rapid repair of damaged airfield runways [AD-D011325] p 276 N85-15754 POLYIMIDE RESINS
- V-378A, a new modified bismaleimide matrix resin for high modulus graphite p 282 A85-21482 Polyimide protective coatings for 700 deg service
- p 282 A85-21527 POLYMER CHEMISTRY
- PMR polyimide composites for aerospace applications - Polymerization of Monomer Reactants
- p 282 A85-21520 POLYMER MATRIX COMPOSITES
- PMR polyimide composites for aerospace applications -- Polymerization of Monomer Reactants
- p 282 A85-21520 POLYMERIC FILMS
- Polyimide protective coatings for 700 deg service p 282 A85-21527 POLYMERIZATION
- PMR polyimide composites for aerospace applications - Polymerization of Monomer Reactants
- p 282 A85-21520 POLYMERS
- A thermoplastic polyimidesulfone --- synthesis of processable and solvent resistant system p 282 A85-21483
- POTENTIAL FLOW
- Calculation of compressible potential flow about multielement airfoils using a finite field-panel approach p 207 A85-19473 AIAA PAPER 85-00381
- A class of airfoils having finite trailing edge pressure aradionte [AIAA PAPER 85-0206] p 215 A85-19590
- Numerical solution of the full-potential equation for rotors and oblique wings using a new wake mode p 216 A85-19621
- [AIAA PAPER 85-0268] Linearized potential flow analysis of complex aircraft configurations by HISSS, a higher order panel method p 217 A85-19632 [AIAĂ PAPER 85-0281]
- Optimized discrete-singularity representation of axisymmetric bodies --- for potential flow p 218 A85-19635 [AIAA PAPER 85-0284]
- Breakdown of the conservative potential equation --- for study of transonic flow
- [AIAA PAPER 85-0367] p 221 A85-19700 The numerical simulation of steady transonic rotational flow using a dual potential formulation
- [AIAA PAPER 85-0368] p 221 A85-19701 Potential flow calculations and preliminary wing design in support of an NLF variable sweep transition flight experiment
- [AIAA PAPER 85-0426] p 248 A85-19741 A new singular integral method for compressible potential flow
- p 225 A85-19778 AIAA PAPER 85-04811 A subdomain finite element method for solving the conservative full potential equation for transonic profile flows --- German thesis p 227 A85-19854
- A fast algorithm for solving the conservative transonic S1 full potential equation employing non-orthogonal curvilinear coordinates and non-orthogonal velocity p 228 A85-20239 components
- A linearized unsteady aerodynamic analysis for transonic cascades p 229 A85-20744 Drag prediction for projectiles and finned bodies in
- incompressible flow [AIAA PAPER 85-0104] n 230 A85-20854
- Finite element solutions of Euler equations for lifting airfoils
- [AIAA PAPER 85-0294] p 230 A85-20864 Computation of choked and supersonic turbomachinery flows by a modified potential method
- p 232 A85-21859 Inviscid compressible flow past a multi-element p 236 N85-16776 aerofoil

- POTENTIAL THEORY
- A comparative study of the nonuniqueness problem of the potential equation p 235 N85-15694 [NASA-TP-2385]
- POWDER METALLURGY
- Comparison between the properties of conventional wrought and powder metallurgical alloys for turbine disc applications p 283 N85-15739
- PRECIPITATION PARTICLE MEASUREMENT
- Evaluation of the forward scattering spectrometer probe I Electronic and optical studies p 291 A85-22168 PRECOOLING
- Off-design point characteristics of the precooled gas turbine cycle with liquefied hydrogen as fuel p 289 A85-20884
- PREDICTION ANALYSIS TECHNIQUES An improved version of the LTRAN2 for high frequency
- p 205 A85-19401 domain SFRJ simulator results - Experiment and analysis in cold flow --- Solid Fuel RamJet
- AIAA PAPER 85-03291 p 263 A85-19671
- Hypersonic characteristics of an advanced aerospace nland [AIAA PAPER 85-0346]
- p 269 A85-19685 Parametric estimates of propulsion system maintenance manhours
- [AD-A147120] p 201 N85-15662 Experiences with the material bevaviour and high temperature low cycle fatigue life prediction of the IN 738 p 292 N85-15746 blading allov
- View of future requirements for engine cyclic durability by analysis and testing p 267 N85-15751
- Prediction of cruciform all-movable control characteristics at transonic speeds
- p 239 N85-16832 [AD-A147291] Prediction of dynamic stall characteristics using advanced non-linear panel methods
- p 239 N85-16836 [AD-A148453] Atmospheric photochemical modeling of turbine engine fuels. Phase 1: Experimental studies. Volume 2:
- Environmental chamber data tabulations p 300 N85-17470 [AD-A147786]
- PREDICTIONS Prediction of cruciform all-movable control
 - characteristics at transonic speeds p 239 N85-16832 [AD-A147291]
 - Air traffic management concepts for the UK in the 1990's: A review of recent RSRE work
- [AD-A147850] p 246 N85-16853 PRESSURE
- Analysis of the surface load and radiated sound of a vibrating airfoil with application to the experiment of Brooks
- [NASA-CR-3864] p 305 N85-16590 PRESSURE DISTRIBUTION
- Subsonic pressure distributions near a wing-fin juncture on a supersonic arrow-wing configuration with wing-mounted vertical fins
- p 217 A85-19628 [AIAA PAPER 85-0276] Numerical optimization design of advanced transonic wing configurations
- [AIAA PAPER 85-0424] p 248 A85-19739 Analysis of the flow field about a T-45 using PANAIR [AD-A146811] p 236 N85-15699
- Some important problems in unsteady boundary layers including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies
- p 294 N85-16069 [AD-A146964]
- Analysis of the surface load and radiated sound of a vibrating airfoil with application to the experiment of Brooks
- [NASA-CR-3864] p 305 N85-16590 An improved source model for aircraft interior noise eninute
- [NASA-CR-172517] p 305 N85-17668 PRESSURE DRAG
- Theoretical study of blockage effect of wind-tunnel wall on wake of two-dimensional flat plate normal to plane p 272 A85-19402 wall
- Experimental investigation of blockage effect of upper wall of wind-tunnel of wake of two-dimensional flat plate normal to plane boundary p 272 A85-19403 PRESSURE EFFECTS
- A linearly correcting method of deviation function for considering the influence of pressure on the thermodynamic properties of combustion gas
- p 304 A85-20236 PRESSURE GRADIENTS A class of airfoils having finite trailing edge pressure
 - aradients [AIAA PAPER 85-0206] p 215 A85-19590
- Drag reduction due to boundary-layer control by p 237 N85-16785 combined blowing and suction

- PRESSURE MEASUREMENT Unsteady pressure measurements on a biconvex airfoil in a transonic oscillating cascade p 234 N85-15689 [NASA-TM-86914] PRESSURE OSCILLATIONS Surface pressure fluctuations in a three-dimensional shock wave/turbulent boundary layer interaction [AIAA PAPER 85-0125] p 211 A85-19536 PRESSURE PULSES An experimental investigation of an unsteady combusting flow in a pulse combustor [AIAA PAPER 85-0322] p 281 A85-20865 PRESSURE SENSORS A sensor for detection of unsteady distortion maxima n air intakes p 205 A85-19262 [ONERA, TP NO, 1984-148] Aero-optics experimental techniques p 294 N85-16067 [AD-A146755] Ultrasound instrumentation for the 7 inch Mach seven tunnel [NASA-CR-174277] p 305 N85-16586 PRODUCT DEVELOPMENT Aeronautical gas turbines. III Burbank's Blackbirds --p 264 A85-21420 encompassing SR-71 reconnaissance aircraft and YA-12/12-A interceptors p 252 A85-22081 **PRODUCTION COSTS** Production rate variations cost models p 308 N85-17732 (AD-A147708) PRODUCTIVITY Flexible manufacturing system for the production of aircraft parts [BLL-PNR-90237-(899.3153)] p 297 N85-17159 **PROGRAM VERIFICATION (COMPUTERS)** Writing executable assertions to test flight software [SU-CRC-TR-84-14] p 301 A85-21973 Investigating version dependence in fault-tolerant p 302 N85-16749 software Software test handbook: Software test guidebook, volume 2 [AD-A147289] p 303 N85-17578 **PROGRAMMING LANGUAGES** Control system design language implementation of a gas turbine starting controller [AD-A147896] p 266 N85-15732 PROJECT MANAGEMENT National airspace review enhancement plan, revision 3 p 246 N85-16852 PROPELLER BLADES Interaction of a turbulent vortex with a lifting surface [AIAA PAPER 85-0004] p 206 A85-19452 Calculation of steady flow about propellers by means of a surface panel method [AIAA PAPER 85-0283] p 218 A85-19634 A Navier-Stokes calculation of 3-D, turbulent flow near a propeller in a shear flow [AIAA PAPER 85-0365] p 220 A85-19698 PROPELLER DRIVE The unambiguous in-flight determination of propeller rotational noise in aircraft with four-cycle combustion p 304 A85-20650 enaines PROPELLER EFFICIENCY Analytical determination of propeller performance degradation due to ice accretion (AIAA PAPER 85-03391 p 264 A85-20867 PROPULSION SYSTEM CONFIGURATIONS Influence of propulsion/mission profile combinations upon generic missile penetration of a hypothetical defense [AIAA PAPER 85-0495] p 249 A85-19789 Parametric estimates of propulsion system maintenance manhours [AD-A147120] p 201 N85-15662 Installed nacelle drag-improvement tests of an M = 0.8 turboprop transport configuration [NASA-TM-84302] p 255 N85-15716 PROPULSION SYSTEM PERFORMANCE Real gas effects in advanced technology engines [AIAA PAPER 85-0252] p 262 A85-19615 Big wind at Tullahoma --- USAF's new aeropropulsion test facility p 275 A85-20122 Calculation of the hydrodynamic characteristics of polyplanes p 290 A85-22113 An update of the Canada/USA augmentor-wing relect p 257 N85-16781 project PROPULSIVE EFFICIENCY Design study of technology requirements for high performance single-propeller-driven business airplane [NASA-CR-3863] p 235 N85-15692 PROTECTIVE CLOTHING Windblast leg protector assembly [AD-D011376] p 242 N85-15700
- **PROTECTIVE COATINGS** Polyimide protective coatings for 700 deg service p 282 A85-21527

A-28

- Microstructural development of protective Al2O3 p 283 A85-21650 PROTECTORS
- Windblast leg protector assembly
- [AD-D011376] p 242 N85-15700 PULSE COMMUNICATION
- Designer on Aeroflot automated COMMO system p 296 N85-16765 development PUMP SEALS
- Analysis and testing for rotordynamic coefficients of turbulent annular seals with different, directionally-homogeneous surface-roughness treatment for rotor and stator elements
- [ASME PAPER 84-TRIB-31] p 289 A85-21293

Q

QUADRATURES

Comparative study of various guadratures for subsonic lifting surface chordwise integrals p 205 A85-19404 QUANTITATIVE ANALYSIS

- Impact of aircraft emissions on air quality in the vicinity of airports. Volume 4. Nitrogen dioxide and hydrocarbons
- p 299 N85-17436 [AD-A148253]

R

RADAR

LPI-radar for helicopter obstacle warning p 297 N85-16810

RADAR ANTENNAS

- Reflector antennas with directional effect in the near-field Characteristics and applications --- Germa p 287 A85-19837 thesis
- RADAR ATTENUATION Atmospheric propagation losses for long-range airborne radar systems analysis
- [AIAA PAPER 85-0267] p 244 A85-19620 RADAR BEACONS Development and flight test of a helicopter compact,
- portable, precision landing system concept p 261 N85-16821

RADAR CROSS SECTIONS

Radar cross section lectures		
	p 289	A85-20915
RADAR EQUIPMENT		

Aviation radar Russian book	p 244	A85-19805
RADAR NAVIGATION		

- National airspace review: Airport radar service area operational confirmation report
- [DOT/FAA/AT-84/2] n 245 N85-15707 RADAR TRACKING
- A three-dimensional Kalman filter for short observation times to extrapolate flight trajectories --- German thesis

p 301 A85-19835

RADIATION DISTRIBUTION

A numerical study of three-dimensional radiation fields in problems of supersonic flow past segmental bodies p 227 A85-20025

RADIATIVE HEAT TRANSFER

Radiative ent	ropy production		
AIAA PAPER 8	5-0408]	p 304	A85-19729
Flow behind	an attached sh	lock wave in	a radiating
gas		p 233	A85-22308
RADIO COMMUN	CATION		
Operational	requirements	versus te	echnological

Operational requirements versus p 204 N85-16798 capabilities RADIO FREQUENCY INTERFERENCE Measurement of signal separation between radio service

and air navigation service	-		
[IRT-TB-B-40/82]		p 246	N85-16860
RADIO NAVIGATION			

Measurement of signal separation betw	/een	radio	service
and air navigation service			

- [IRT-TB-B-40/82] p 246 N85-16860 RADIOACTIVITY Evaluation of arctic test of improved tritium radioluminescent lighting
- [AD-A148215] p 278 N85-16884 RAIN
- Scaling laws for testing of high lift airfoils under heavy rainfall
- [AIAA PAPER 85-0257] p 216 A85-19617 Measurements of water film characteristics on airfol surfaces from wind-tunnel tests with simulated heavy
- [AIAA PAPER 85-0259] p 274 A85-19618 The aerodynamic effect of surface wetting characteristics on a laminar flow airfoil in simulated heavy rein [AIAA PAPER 85-0260] p 247 A85-19619

Real gas effects in advanced technology engines [AIAA PAPER 85-0252] 0 262 A85-1 SFRJ simulator results - Experiment and analysis in cold flow --- Solid Fuel RamJet [AIAA PAPER 85-0329] RAREFIED GAS DYNAMICS Determination of rarefied-flow aerodynamics of the Shuttle orbiter from flight measurements on STS-6 and STS-7 [AIAA PAPER 85-0347] REAL GASES Real gas effects in advanced technology engines [AIAA PAPER 85-0252] Real-cas flowfields about configurations REAL TIME OPERATION

RAMJET ENGINES

Some characteristics of automotive gasolines and their performance in a light aircraft engine

p 262 A85-19615

p 263 A85-19671

p 219 A85-19686

p 262 A85-19615

three-dimensional

o 231 A85-21830

- p 283 N85-15919 [FAA-CT-84-12] The effect on software design of testing by symbolic p 303 N85-16750 execution Reliable software design for avionics and space
- applications p 303 N85-16751 RECEIVERS Using the control system design environment in the
- design of a data link receiver unit for the Coast Guard HH-65A helicopter [AD-A148624] p 271 N85-16880
- RECIRCULATIVE FLUID FLOW
- Calculation of confined swirling flows [AIAA PAPER 85-0060]
- p 285 A85-19491 A study of the flow recirculation problems within an anechoic hover chamber [AIAA PAPER 85-0071] p 273 A85-19497
- Computation of recirculating compressible flow in axisymmetric geometries
- [AIAA PAPER 85-0185] p 286 A85-19575 **RECONNAISSANCE AIRCRAFT**
- Burbank's Blackbirds encompassing SR-71 reconnaissance aircraft and YA-12/12-A interceptors p 252 A85-22081 Airworthiness and flight characteristics test of the
- RC-12D Guardrail V [AD-A148046] p 258 N85-16864
- RECONNAISSANCE SPACECRAFT A method for determining mesoscale dynamic
- topography [AD-D011412] p 300 N85-17506
- **RECTANGULAR WINGS** Three-dimensional effects on a pitching lifting surface
- [AIAA PAPER 85-0041] p 208 A85-19476 Crossflow drag of finite-length rectangular wing-bodies [AIAA PAPER 85-0451] p 224 A85-19760
- Harmonic oscillations of a rectangular wing with a p 231 A85-21656 circulation variable over the span
- **REDUNDANT COMPONENTS** Optimal maintenance center inventories for fault-tolerant
- repairable systems p 301 A85-21548 REENTRY VEHICLES
- Application of axisymmetric analogue for calculating heating in three-dimensional flows
- [AIAA PAPER 85-0245] p 216 A85-19611 REFLECTORS
- Reflector antennas with directional effect in the near-field Characteristics and applications --- German p 287 A85-19837 thesis REGRESSION ANALYSIS
- Parametric estimates of propulsion system maintenance manhours
- [AD-A147120] p 201 N85-15662 REINFORCED PLASTICS
- Impressions from a study tour in Finland concerning fiber einforced plastics, June 1984
- [FOA-C-20552-D2(E4,F9)] p 283 N85-15831 REINFORCING FIBERS
- Kevlar aramid fibers vs other fibers for reinforcement of composite structures p 282 A85-21392 Impressions from a study tour in Finland concerning fiber reinforced plastics, June 1984
- [FOA-C-20552-D2(E4,F9)] p 283 N85-15831 **RELAXATION METHOD (MATHEMATICS)**
- A relaxation approach to patched-orid calculations with the Euler equations
- p 218 A85-19644 [AIAA PAPER 85-0295] A stream function relaxation method for solving transonic S1 stream surface with respect to non-orthogonal
- curvilinear coordinates p 228 A85-20240 Theoretical contributions to transonic flow analysis for transport aircraft
- [BMFT-FB-W-84-036] p 239 N85-16838 RELIABILITY
- More than you want to know about maximum likelihood estimation
- [NASA-TM-85905] p 270 N85-15752

technicians		
[AD-A147388]	p 295	N85-16196
REMOTE SENSING		
Stereo Electro-optical Tracking S	System (SE	TS)
[NASA-CR-172471]	p 295	N85-16098
REMOTE SENSORS		
On-board processing for linesca	In sensors	in miniature
unmanned aircraft		
[RAE-TM-SPACE-327]	p 261	N85-16870
REMOTELY PILOTED VEHICLES		
The design of airfoils at low Rey	molds num	bers
[AIAA PAPER 85-0074]	p 209	A85-19500
Prediction of HiMAT RPRV c	omponent	interference
effects at transonic speeds		
[AIAA PAPER 85-0213]	p 215	A85-19593
The design and testing of sev	eral joined	wing RPV's
[AIAA PAPER 85-0275]	p 248	A85-19627
RENE 95		
Comparison between the prope	erties of c	onventional
wrought and powder metallurgical	alloys for	turbine disc
applications	p 283	N85-15739
REPORTS		
Research and technology hi	ghlights o	f the Lewis
Research Center		
[NASA-TM-86899]	p 309	N85-17928
REQUIREMENTS		
View of future requirements for	engine cyc	lic durability
by analysis and testing	p 267	N85-15751
Estimating wartime support re-	source ree	quirements.
Statistical and related policy issue	S	
[AD-A147923]	p 308	N85-16685
RESEARCH AIRCRAFT		
Icing conditions encountered by	a researci	h aircraft

Design and test requirements for development of today's

Nondestructive inspection: Improved capabilities of

RELIABILITY ENGINEERING

engines

Icing

- p 299 A85-21141 RESEARCH AND DEVELOPMENT
 - The Federal Aviation Administration's Engineering and Development Aircraft Icing Program [AIAA PAPER 85-0015] p 247 A85-19459

Training and research CAD system of the Moscow Aviation Institute and experience in its use p 199 A85-20455

- Fabrication and assembly of composite rear fuselage
- (CRF) tooling and manufacturing for the UH-60 p 200 A85-21394 p 258 A85-21555 helicopter Pilot's Desk Flight Station
- Technology developments for laminar boundary layer control on subsonic transport aircraft
- p 237 N85-16787 Aeroacoustics at the DFVLR Brunswick Research
- Center: A survey on recent and current activities p 306 N85-17677 [DFVLR-MITT-84-14]
- Research and technology highlights of the Lewis Research Center p 309 N85-17928 NASA-TM-868991
- RESEARCH FACILITIES
- The Western Aeronautical Test Range of NASA Arnes Research Center
- [AIAA PAPER 85-0316] p 275 A85-19678 Research and technology highlights of the Lewis Research Center
- [NASA-TM-86899] p 309 N85-17928 RÉSEARCH MANAGEMENT
- Integrated technology wing study (oral presentation) [NASA-CR-169497] p 256 N85-15718 p 256 N85-15718 RESIN MATRIX COMPOSITES
- V-378A, a new modified bismaleimide matrix resin for high modulus graphite p 282 A85-21482 System for rapid repair of damaged airfield runways
- p 276 N85-15754 (AD-D011325) RESONANT FREQUENCIES

An optimality criterion method for structures with stress, displacement and frequency constraints p 290 A85-21985

- RESOURCES MANAGEMENT
- Managing recoverable aircraft components in the PPB and related processes: Executive summary
- [AD-A146806] p 308 N85-16667 Estimating wartime support resource requirements. Statistical and related policy issues
- [AD-A147923] p 308 N85-16685 REVISIONS
- United States Air force aircraft modification process: A system dynamics analysis
- AD-A146954] p 200 N85-15659 REYNOLDS NUMBER
- Pneumatic turbulators: A device for drag reduction at Reynolds numbers below 5 million p 257 N85-16791 RIDING QUALITY
- Design of a digital ride quality augmentation system for

commuter ancrait		
[AD-A148233]	p 271	N85-16879

A-29

RIDING QUALITY

p 266 N85-15737

BIGID BOTORS

RIGID ROTORS

- A theoretical study of stability of a rigid rotor under the influence of dilute viscoelastic lubricants p 289 A85-21278 (ASME PAPER 84-TRIB-17)
- **RIGID STRUCTURES** Composite repair of aircraft structures
- p 285 N85-17059 **RIVETED JOINTS**
- The influence of fastener flexibility on load transfer and fatigue life predictions for multirow bolted and riveted joints -- aircraft structures
- p 296 N85-16219 [LBF-FB-172/84] RÓBOTICS
- Investigation on experimental techniques to detect, locate and quantify gear noise in helicopter transmissions
- [NASA-CR-3847] p 305 N85-17667 RÓBOTS
- NyKINM, a further development of KINM 22 --- simulation of a robot attack on an aircraft
- p 256 N85-15720 [FOA-C-20559-D8(E3)] ROBUSTNESS (MATHEMATICS)
- Artificial dissipation models for the Euler equations p 231 A85-20870 [AIAA PAPER 85-04381 ROCKET ENGINE DESIGN
- Newton iteration formulas for correcting temperature and pressure in thermodynamic calculation of rocket engines p 279 A85-20226

ROCKET EXHAUST

- Theoretical study on supersonic jet plumes p 206 A85-19439 ROCKET NOZZLES
- Aerodynamic studies linked to the development of
- deployable nozzles --- for upper stage ballistic missiles [ONERA, TP NO. 1984-149] p 205 A85-19263 ROTARY WING AIRCRAFT
- Mission-oriented requirements for updating MIL-H-8501. Volume 1: STI proposed structure --- military rotorcraft [NASA-CR-177304-VOL-1] p 271 N85-16877 Mission-oriented requirements for updating MIL-H-8501. Volume 2: STI background and rationale --- military rotorcraft
- [NASA-CR-177304-VOL-2] p 271 N85-16878 **RÖTARY WINGS**
- Solution of the unsteady Euler equations for fixed and rotor wind confidurations [AIAA PAPER 85-0120] p 211 A85-19531
- Numerical study on the dynamic stall process of a NACA 0012 airfoil
- [AIAA PAPER 85-0128] p 212 A85-19539 Numerical solution of unsteady viscous flow past rotor sections
- [AIAA PAPER 85-0129] p 212 A85-19540 Correlation of airfoil icing relationships with two-dimensional model and full scale rotorcraft icing test
- p 240 A85-19680 [AIAA PAPER 85-0337] Solution method for a hovering helicopter rotor using the Euler equations
- [AIAA PAPER 85-0436] p 223 A85-19749 Application of digital interferogram evaluation techniques to the measurement of three-dimensional flow fields
- [AIAA PAPER 85-0037] p 288 A85-20852 Sikorsky composite rotor hub development p 251 A85-21381
- Experimental aerodynamic characteristics of an NACA p 252 A85-21844 0012 airfoil with simulated ice Coupled helicopter rotor/body aeromechanical stability comparison of theoretical and experimental results
- p 252 A85-21847 Study to eliminate ground resonance using active controls
- [NASA-CR-1666091 p 255 N85-15715
- Helicopter active control with rotor blades relaxation p 270 N85-16819

ROTATING SPHERES

A-30

- Some important problems in unsteady boundary layers including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies
- p 294 N85-16069 [AD-A146964] **ROTATING STALLS**
- Precalculation of rotating stall in multistage axial p 287 A85-19832 compressors --- German thesis ROTOR AERODYNAMICS
- An analysis of the flow past an S-shaped rotor by discrete p 206 A85-19405 vortex model A study of the flow recirculation problems within an anechoic hover chamber
- [AIAA PAPER 85-0071] p 273 A85-19497 Effects of friction dampers on aerodynamically unstable rotor stages p 265 A85-21866 The UH-1H helicopter icing flight test program: An overview
- [NASA-TM-86925] p 242 N85-15702

Clearance flow-generated transverse forces at the rotors of thermal turbomachines p 295 N85-16180

[NASA-TM-772921 **ROTOR BLADES**

- Numerical solution of the full-potential equation for rotors
- and oblique wings using a new wake model [AIAA PAPER 85-0268] p 216 p 216 A85-19621 The development of mathematical modelling techniques
- for helicopter rotor icing [AIAA PAPER 85-0336] p 240 A85-19679
- Full two-dimensional transient solutions of electrothermal aircraft blade deicing
- p 248 A85-19734 [AIAA PAPER 85-0413] Solution method for a hovering helicopter rotor using the Euler equations
- [AIAA PAPER 85-0436] p 223 A85-19749 K747 composite main rotor blade modification, analysis
- and qualification for new high temperature requirements p 251 A85-21378 ROTOR BLADES (TURBOMACHINERY)
- An experimental investigation of stator/rotor interaction influence on multistage compressor rotor flow
- [AIAA PAPER 85-0009] p 206 A85-19455 Application of an adaptive blade control algorithm to a p 269 A85-20143 gust alleviation system Helicopter model rotor-blade vortex interaction impulsive
- noise: Scalability and parametric variations p 238 N85-16826 [NASA-TM-860071
- ROTOR BODY INTERACTIONS A relaxation approach to patched-grid calculations with
- the Euler equations [AIAA PAPER 85-0295] p 218 A85-19644 Coupled helicopter rotor/body aeromechanical stability
- comparison of theoretical and experimental results p 252 A85-21847
- ROTORCRAFT AIRCRAFT
- Correlation of airfoil icing relationships with two-dimensional model and full scale rotorcraft icing test data
- [AIAA PAPER 85-0337] p 240 A85-19680 Europeans using composites, ceramics for rotorcraft
- p 263 A85-20061 engine improvements ROTORS
- Analysis and testing for rotordynamic coefficients of annular with turbulent seals different. directionally-homogeneous surface-roughness treatment for rotor and stator elements
- [ASME PAPER 84-TRIB-31] p 289 A85-21293 Stability of squeeze film damped multi-mass flexible rotor bearing systems
- p 289 A85-21296 [ASME PAPER 84-TRIB-45] Development of a Navier-Stokes rotor and stator analysis
- AD-A1469671 p 294 N85-16070 **BUN TIME (COMPUTERS)**
- Inexpensive calibrations for the influence function nethod using the interference distributed loads code --for prediction of store loads in aircraft flow fields
- [AIAA PAPER 85-0270] p 247 A85-19623 A method of forecasting active constraint with the applications to structural optimization
- p 291 A85-22445 RUNGE-KUTTA METHOD
- A multistage time-stepping scheme for the Navier-Stokes equations
- [AIAA PAPER 85-0035] p 207 A85-19472 Spectral methods for modeling supersonic chemically reacting flow fields
- [AIAA PAPER 85-0302] p 219 A85-19651 RUNWAYS
- System for rapid repair of damaged airfield runways p 276 N85-15754 [AD-D011325] Development of a preliminary ALRS stabilized material pavement analysis system (SPAS)
- p 277 N85-15760 [AD-A147116] International projects, other work of Aeroproyekt
- p 204 N85-16767 Institute Aeroproyekt develops improved runway surfacing p 277 N85-16770

S

SAFETY DEVICES

- Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems [NASA-CR-174271] p 242 N85-15701
- Powered articulated headrest system [AD-D011353] p 254 N85-15710
- S-3A ballast block final design and engineering tests [AD-A147685] p 243 N85-16842 SANDWICH STRUCTURES
- Determination of the optimal parameters of aircraft structural elements in the form of sandwich plates and shallow shells with a honeycomb filler
 - p 287 A85-20452

Aeroelastic stability and vibration of layered plates and cylindrical shells p 288 A85-20472 Composite repair of aircraft structures p 285 N85-17059 SATELLITE NAVIGATION SYSTEMS Satellite navigation

SUBJECT INDEX

- p 246 N85-16851 [S-HRG-98-856] SCALE (CORROSION) Microstructural development of protective AI2O3
- p 283 A85-21650 SCALE EFFECT
- Flowfield scaling in sharp fin-induced shock wave/turbulent boundary-layer interaction
- p 232 A85-21857 Investigations into the effects of scale and compressibility on lift and drag in the RAE 5m pressurized low-speed wind tunnel p 236 N85-16773

SCALE MODELS

- The accuracy of trials with powered 1/2 models in the S2MA wind tunnel [ONERA, TP NO. 1984-156] p 272 A85-19270
- Frequency response of a jet engine test facility air supply
- p 273 A85-19485 [AIAA PAPER 85-0053] A universal turboshaft engine test cell - Design
- considerations and model test results [AIAA PAPER 85-0382] p 275 A85-19711
- SCALING LAWS Scaling laws for testing of high lift airfoils under heavy
- rainfall [AIAA PAPER 85-0257] p 216 A85-19617
- SCINTILLATION
- Unsteady pressure measurements on a biconvex airfoil in a transonic oscillating cascade [NASA-TM-86914] p 234 N85-15689
- SCREEN EFFECT
- Extremum problem concerning a wing with a maximum p 234 A85-22370 gradient of lift force SEALS (STOPPERS)
- Metallurgical and mechanical phenomena due to rubbing of titanium against sintered powder Nichrome p 291 A85-22281

SEADI ANES

- The effect of changes in the angle of incidence in the event of a richochet at a float step [RAE-TRANS-2120] p 255 N85-15712
- SEAT BELTS
- Impact tests of automatic lap belt configurations [AD-A148034] p 243 N85-16844

SECONDARY FLOW

of thermal turbomachines

Navier-Stokes equations

[AIAA PAPER 85-00331]

[AIAA PAPER 85-0108]

[AIAA PAPER 85-0178]

[AIAA PAPER 85-0179]

[AIAA PAPER 85-0205]

[AIAA PAPER 85-0301]

[AIAA PAPER 85-0351]

[AIAA PAPER 85-0371]

[AIAA PAPER 85-0375]

of an airfoil with glaze ice

[AIAA PAPER 85-04091

for attached and separated flows

SEMICONDUCTORS (MATERIALS)

A method for calculating the performance of ejector nozzles p 287 A85-20232

Life cycle cost model for very high speed integrated

An incremental block-line-Gauss-Seidel method for the

A theory for the core of a three-dimensional leading-edge

Some features of two-dimensional turbulent separated

Structure of the wall pressure fluctuations in a shock-induced separated turbulent flow

Prediction of subsonic/transonic separated flow about

A study of the effects of numerical dissipation on the

Passive control effects on flow separation around a

Viscous/inviscid interaction analysis of transonic shock

Evaluation of low Reynolds number turbulence models

Detailed measurements of the flowfield in the vicinity

induced separated flow including normal pressure

protuberance at high subsonic speed --- for optical propagation quality enhancement to and from airborne

calculation of supersonic separated flows

p 295 N85-16180

p 297 N85-17298

p 207 A85-19470

p 210 A85-19524

p 214 A85-19570

p 214 A85-19571

p 215 A85-19589

p 219 A85-19650

p 220 A85-19690

p 221 A85-19703

p 286 A85-19706

p 222 A85-19730

SELE EXCITATION Clearance flow-generated transverse forces at the rotors [NASA-TM-77292]

circuits

vortex

flows

airfoils

platforms

gradients

[AD-A147798]

SEPARATED FLOW

Experimental and theoretical analysis of laminar separation bubbles [AIAA PAPER 84-2201] p.288 AR5-20874
Turbulent bubbles behind airfoils and wings at high angle of attack p 296 N85-16779
SEPARATORS Analysis of a split-flow inertial particle separator by finite
elements for helicopter gas turbine engine p 231 A85-21845
Polyimide protective coatings for 700 deg service p 282 A85-21527
Structural flight load measurement demonstration of structural integrity p 254 N85-15670 US Army helicopter operational flight loads
p 254 N85-15675 Helicopter data acquisition in WHL
p 254 N85-15676 SERVOMOTORS
Design and test of a four channel motor for electromechanical flight control actuation
[NASA-CR-171838] p 297 N85-17294 SHAFTS (MACHINE ELEMENTS)
Improvement of the corrosion resistance of turbine engine bearings
[AĎ-A147430] p 265 N85-15731 SHALLOW SHELLS
Determination of the optimal parameters of aircraft structural elements in the form of sandwich plates and shallow shells with a honeycomb filler
p 287 A85-20452 SHAPES
Drag of the fundamental shapes of parachutes p 231 A85-20998
A Navier-Stokes calculation of 3-D, turbulent flow near a propeller in a shear flow
[AIAA PAPER 85-0365] p 220 A85-19698
scales in turbulent shear flows p 232 A85-21851 SHEAR LAYERS
A study of compressible turbulent free shear layers using laser Doppler velocimetry
[AIAA PAPER 85-0177] p 213 A85-19569 Aero-optics experimental techniques
[AD-A146755] p 294 N85-16067 SHELL STABILITY
cylindrical shells p 288 A85-20472 SHELL THEORY Current problems in the theory of plates and shells in
aircraft p 287 A85-20459 SHIPS
design of a data link receiver unit for the Coast Guard
[AD-A148624] p 271 N85-16880 SHOCK LAYERS
A numerical study of three-dimensional radiation fields in problems of supersonic flow past segmental bodies
p 227 A85-20025 Hypersonic chemically nonequilibrium viscous shock
layer on wings with a catalytic surface p 229 A85-20561
SHOCK WAVE INTERACTION Structure of the wall pressure fluctuations in a
shock-induced separated turbulent flow [AIAA PAPER 85-0179] p 214 A85-19571
Computation of unsteady shock-induced vortex separation
[AIAA PAPER 85-0183] p 214 A85-19573 Supercritical airfoil drag reduction by passive shock
wave/boundary layer control in the Mach number range .75 to .90
[AIAA PAPER 85-0207] p 215 A85-19591 Viscous/inviscid interaction analysis of transonic shock induced senarated flow including normal pressure
gradients (AIAA PAPER 85-0371) p 221 A85-19703
Flowfield scaling in sharp fin-induced shock wave/turbulent boundary-layer interaction
Active and passive shock/boundary layer interaction
SHOCK WAVE PROFILES Flow behind an attached shock wave in a radiating
gas p 233 A85-22308 SHOCK WAVE PROPAGATION
A quasi-conservative lambda formulation for inviscid transonic flow simulation
[AIAA PAPER 85-0088] p 210 A85-19511 SHOCK WAVES
Surface pressure fluctuations in a three-dimensional shock wave/turbulent boundary layer interaction

shock wave/turbulent boundary layer interaction [AIAA PAPER 85-0125] p 211 A85-19536

Shock waves in transonic channel flows at moderate Revnolds number [AIAA PAPER 85-0369] p 221 A85-19702 Shock induced vortices on elliptic cones in supersonic flow [AIAA PAPER 85-0433] p 223 A85-19746 Modes of shock-wave oscillations on spike-tipped bodies n 232 A85-21855 Shock-fitting solution of the supersonic flowfield in a p 232 A85-21856 rounded internal corner A comparative study of the nonuniqueness problem of the potential equation p 235 N85-15694 [NASA-TP-2385] Active and passive shock/boundary layer interaction p 238 N85-16795 control on supercritical airfoils Shock waves in transonic flows at moderate Reynolds Number p 238 N85-16823 SHORT TAKEOFF AIRCRAFT Aerodynamics of an airfoil in ground effect with a jet issuing from its undersurface [AIAA PAPER 85-0019] p 207 A85-19461 STOL technology for conventional flight enhancement [AIAA PAPER 84-2397] p 250 A85-20875 Design of a STOL aircraft with jet assisted takeoff p 253 A85-22373 unite Circulation control: A bibliography of DTNSRDC research and selected outside references: Update p 201 N85-15661 [AD-A146966] SIGNAL TO NOISE RATIOS Measurement of signal separation between radio service and air navigation service [IRT-TB-B-40/82] p 246 N85-16860 SIKORSKY AIRCRAFT Sikorsky composite rotor hub development p 251 A85-21381 SIMULATORS A simulator for studying helicopter weapons systems p 277 N85-16816 SINGULAR INTEGRAL EQUATIONS A new singular integral method for compressible potential flow [AIAA PAPER 85-0481] p 225 A85-19778 SINGULARITY (MATHEMATICS) A comparison of different three-dimensional singularity nethods for modelling internal flows p 205 A85-19264 [ONERA, TP NO. 1984-150] Optimized discrete-singularity rep axisymmetric bodies --- for potential flow representation of [AIAA PAPER 85-0284] p 218 A85-19635 SINTERED ALUMINUM POWDER Engineering property comparisons of PM and IM aluminum alloy forgings [AD-B0881466L] p 298 N85-17398 SIZE DETERMINATION Computer sizing of fighter aircraft [NASA-TM-86351] p 203 N85-16759 SKIN FRICTION Full scale experiments into the use of large eddy breakup devices for drag reduction on aircraft p 257 N85-16790 SLENDER BODIES Approximate solution of a nonlinear problem of flow past a thin airfoil profile near a support surface p 233 A85-22368 An extremum problem concerning the shape of a body of revolution in supersonic gas flow p 234 A85-22371 Some important problems in unsteady boundary layers including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies [AD-A146964] p 29 p 294 N85-16069 SLENDER CONES Regarding parametric investigations of slender cone nose hluntness effects [AIAA PAPER 85-0349] p 220 A85-19688 SLENDER WINGS Subsonic wing rock of slender delta wings TAIAA PAPER 85-01981 p 214 A85-19582 SMALL PERTURBATION FLOW Body flow field simulation and force/moment prediction at transonic speeds [AIAA PAPER 85-0423] p 222 A85-19738 SMOKE ABATEMENT Laboratory simulation of smoke reduction from aircraft engine test cell exhaust using a fluidized bed filter [AD-A148600] p 278 N85-16886 SOFTWARE ENGINEERING Software design methods --- for civil and military aircraft avionics systems p 301 A85-21457 Ultrasound instrumentation for the 7 inch Mach seven tunne

[NASA-CR-174277]

Built-in-test for first line testing

Functional built-in-test in a pipelined image processor p 202 N85-16740

p 202 N85-16739

Effective life cycle software support: A study in discipline and versatility p 302 N85-16746 Experience in using on-aircraft software for testing integrated systems p 302 N85-16747 Software test handbook: Software test guidebook, volume 2 [AD-A147289] p 303 N85-17578 SOFTWARE TOOLS Writing executable assertions to test flight software [SU-CRC-TR-84-14] p 301 A85-21973 p 301 A85-21973 SOIL MECHANICS Development of a preliminary ALRS stabilized material pavement analysis system (SPAS) p 277 N85-15760 [AD-A147116] SOILS Development of a preliminary ALRS stabilized material pavement analysis system (SPAS) [AD-A147116] p 277 N85-15760 SOLID PROPELLANT COMBUSTION SFRJ simulator results - Experiment and analysis in cold flow --- Solid Eucl Bam let IAIAA PAPER 85-0329) p 263 A85-19671 SOLVENTS A thermoplastic polyimidesulfone --- synthesis of processable and solvent resistant system p 282 A85-21483 SONIC NOZZLES Experimental study of forward-located jet-interaction nozzles [AIAA PAPER 85-0454] p 224 A85-19762 SOUND FIELDS Analysis of the surface load and radiated sound of a vibrating airfoil with application to the experiment of Brooke [NASA-CR-3864] p 305 N85-16590 SOUND PRESSURE An improved source model for aircraft interior noise studies [NASA-CR-172517] p 305 N85-17668 SOUND PROPAGATION An experimental study of sound attenuation characteristics in circular ducts with lined radial baffles p 304 A85-19505 [AIAA PAPER 85-0079] SOUND TRANSMISSION Field-incidence noise transmission loss of general aviation aircraft double-wall configurations p 304 A85-21842 SOUND-SOUND INTERACTIONS Investigation of nonlinear effects in the instabilities and noise radiation of supersonic jets [AIAA PAPER 85-0081] p 304 A85-19507 SPACE EXPLORATION Reliable software design for avionics and space p 303 N85-16751 applications SPACE HEATING (BUILDINGS) Hangar heating and energy conservation manual [AD-A147893] p 277 N85-15762 SPACE MISSIONS An optimization method for the preliminary design of interplanetary aerobraking missions p 238 N85-16822 SPACE SHUTTI E MISSION 31-B Determination of rarefied-flow aerodynamics of the Shuttle orbiter from flight measurements on STS-6 and STS.7 [AIAA PAPER 85-0347] p 219 A85-19686 SPACE SHUTTLE MISSION 31-C Determination of rarefied-flow aerodynamics of the Shuttle orbiter from flight measurements on STS-6 and STS-7 p 219 A85-19686 [AIAA PAPER 85-0347] SPACE SHUTTLE ORBITERS Determination of rarefied-flow aerodynamics of the Shuttle orbiter from flight measurements on STS-6 and STS-7 [AIAA PAPER 85-0347] p 219 A85-19686 Effect of aerodynamic and angle-of-attack uncertainties on the May 1979 entry flight control system of the Space Shuttle from Mach 8 to 1.5 p 280 N85-15778 (NASA-TP-23651 SPACE SHUTTLES Air breathing space transport vehicles with wings p 280 A85-20909 SPACE TRANSPORTATION SYSTEM FLIGHTS Introductory aerothermodynamics of advanced space transportation systems p 231 A85-21827 SPACEBORNE EXPERIMENTS A method for determining mesoscale dynamic topography p 305 N85-16586

[AD-D011412]	p 300	N85-17506
SPACECRAFT		

An optimization method for the preliminary design of interplanetary aerobraking missions p 238 N85-16822

SPACECRAFT

p 203 N85-16745

Documentation and separate test program development

is most important for test/maintenance

SPACECRAFT COMMUNICATION

SPACECRAFT COMMUNICATION

- Research and technology highlights of the Lewis
- [NASA-TM-86899] p 309 N85-17928 SPACECRAFT CONFIGURATIONS
- Air breathing space transport vehicles with wings p 280 A85-20909 SPACECRAFT PROPULSION
- Air breathing space transport vehicles with wings p 280 A85-20909
- SPACECRAFT RADIATORS Thermal design of rotatable cryogenic heat pipe joints
- --- for heat exchangers in space applications [AIAA PAPER 85-0068] p 279 A85-19495 SPACECRAFT REENTRY
- Effect of aerodynamic and angle-of-attack uncertainties on the May 1979 entry flight control system of the Space Shuttle from Mach 8 to 1.5
- [NASA-TP-2365] p 280 N85-15778 SPARE PARTS
- Managing recoverable aircraft components in the PPB and related processes: Executive summary [AD-A146806] p 308 N85-16667
- The Air Force can improve its forecasts of aircraft spare parts requirements
- [AD-A147911] p 308 N85-16682 Estimating wartime support resource requirements. Statistical and related policy issues
- [AD-A147923] p 308 N85-16685 SPARK [GNITION
- FRG ceramic engine components (PET) p 297 N85-17193
- SPECIFICATIONS Mission-oriented requirements for updating MIL-H-8501.
- Volume 1: STI proposed structure --- military rotorcraft [NASA-CR-177304-VOL-1] p 271 N85-18877 Mission-oriented requirements for updating MIL-H-8501. Volume 2: STI background and rationale --- military
- rotorcraft [NASA-CR-177304-VOL-2] p 271 N85-16878 Using the control system design environment in the
- SPECTRAL METHODS
- Spectral methods for modeling supersonic chemically reacting flow fields [AIAA PAPER 85-0302] p 219 A85-19651
- [AIAA PAPER 85-0302] p 219 A85-19651 SPECTROMETERS
- Evaluation of the forward scattering spectrometer probe. I Electronic and optical studies p 291 A85-22168 SPEECH RECOGNITION
- Speech recognition making progress Direct voice input is a promising infant p 244 A85-19183 Literature review of voice recognition and generation technology for Army helicopter applications
- [AD-A146878] p 293 N85-15954 SPIKES (AERODYNAMIC CONFIGURATIONS)
- Modes of shock-wave oscillations on spike-tipped bodies p 232 A85-21855
- SPOILERS A comparison between theoretical and experimental flow fields of an airfoil with deflected spoiler

[AIAA PAPER 85-0269]	p 216	A85-19622
Repair of composites	p 284	N85-17058
SQUEEZE FILMS		

- Stability of squeeze film damped multi-mass flexible rotor bearing systems [ASME PAPER 84-TRIB-45] p 289 A85-21296
- [ASME PAPER 84-TRIB-45] p 289 A85-21296 STABILITY AUGMENTATION
- A longitudinal stability augmentation system for a tilt rotor aircraft [AIAA PAPER 85-0072] p 268 A85-19498

[MMA FAFER 00-0072]	p 200	M00-19490
STABILITY DERIVATIVES		
O to a start of the start of th		

- Subsonic wing rock of slender delta wings [AIAA PAPER 85-0198] p 214 A85-19582 STABILIZATION
- Oxidation and stabilization of jet fuels --- Russian book p 281 A85-20925
- STABILIZED PLATFORMS

A-32

- Evaluation of nose, roof, and mast mounted sensor platforms for piloting and sighting, integrated in future combat helicopters p 260 N85-16808 STABIL/ZERS (FLUID DYNAMICS)
- The development of a finite element model of an aircraft vertical stabilizer for vibration analysis p 290 A85-21683
- TUTOR (CL-41A) tail flight load survey p 254 N85-15678
- STAGNATION FLOW
- Some important problems in unsteady boundary layers including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies [AD-A146964] p 294 N85-16069

- STARTING
- ...Control-system design-language-implementation of a gas turbine starting controller
- [AD-A147896] p 266 N85-15732 STATIC STABILITY
- Conical bodies with a star-shaped transverse cross section, having a reserve of static stability p 229 A85-20557
- STATISTICAL ANALYSIS
- Selection of rational models in the optimal planning of aeromechanical experiments p 288 A85-20460 FAA (Federal Aviation Administration) statistical handbook of aviation, calendar year 1983 [AD-A148171] p 203 N85-16760
- [AD-A148171] STATOR BLADES
- An experimental investigation of stator/rotor interaction influence on multistage compressor rotor flow [AIAA PAPER 85-0009] p 206 A85-19455
- STATORS Analysis and testing for rotordynamic coefficients of turbulent annular seals with different.
- turbulent annular seals with different, directionally-homogeneous surface-roughness treatment for rotor and stator elements [ASME PAPER 84-TRIB-31] p 289 A85-21293
- Development of a Navier-Stokes rotor and stator analysis
- [AD-A146967] p 294 N85-16070 STEADY FLOW
- Calculation of steady flow about propellers by means of a surface panel method
- [AIAA PAPER 85-0283] p 218 A85-19634 The numerical simulation of steady transonic rotational
- flow using a dual potential formulation [AIAA PAPER 85-0368] p 221 A85-19701
- Grid adaptation for the 2-D Euler equations [AIAA PAPER 85-0484] p 225 A85-19781
- Contamination and distortion of steady flow field induced by discrete frequency in aircraft gas turbines [AD-A147092] p 294 N85-16073
- STEADY STATE Effect of steady-state temperature distortion on inlet flow
- to a high-bypass-ration turbofan engine [NASA-TM-86896] p 265 N85-15725
- STORAGE STABILITY Oxidation and stabilization of jet fuels --- Russian book p 281 A85-20925
- STORMS (METEOROLOGY) Radar for storm forecasting and weather hazard
- warning [AIAA PAPER 85-0092] p 299 A85-19514
- STRAIN GAGE ACCELEROMETERS Navy operational loads data sources and systems
- STRAIN GAGES
- Structural load measurements on a Northrop NF-5A p 253 N85-15667 Tornado: Structural Usage Monitoring System (SUMS) p 292 N85-15680
- STRAIN MEASUREMENT Advanced fatigue monitoring on service aircraft p 292 N85-15671
- Experiences obtained from service fatigue monitoring exercises p 292 N85-15672
- STRAPDOWN INERTIAL GUIDANCE Flight testing of Litton laser gyro strapdown system LTN-90 for general aviation
- [DFVLR-MITT-84-16]) p 245 N85-15709
- Standard Attitude Heading Reference System (SAHRS) full scale development program p 246 N85-16804 STREAM FUNCTIONS (FLUIDS)
- On the variety of type discrimination criteria of equations on S1 and S2 stream surfaces in turbomachine
- p 228 A85-20238 A stream function relaxation method for solving transonic S1 stream surface with respect to non-orthogonal
- curvilinear coordinates p 228 A85-20240
 STRESS ANALYSIS
- Stress analysis and shaping of the canopy of a square parachute $p \, 242$ A85-21668 Universal matrices to obtain thermal load vectors for the family of anisotropic plane triangular finite elements
- p 291 A85-22232 A theoretical view on the stress analysis of fully inflated parachute canopies
- [AD-A148387] p 239 N85-16835 STRESS CONCENTRATION
- Disc fatigue life predictions for gas turbine engines p 267 N85-15743 STRESS CYCLES
- Fatigue crack growth behavior of 7XXX aluminum alloys under simple variable amplitude loading
- p 280 A85-20759
- Development of a fatigue crack propagation model of Incoloy 901 p 280 A85-20758

- Interpretation of fatigue crack growth in aluminium alloys under programmed block loading p 281 A85-20790 STRESS-STRAIN RELATIONSHIPS
- An optimality criterion method for structures with stress, displacement and frequency constraints
 - p 290 A85-21985

STRUCTURAL ANALYSIS Current problems in the theory of plates and shells in aircraft p 287 A85-20459

- Universal matrices to obtain thermal load vectors for the family of anisotropic plane triangular finite elements p 291 A85-22232
- Keeping up with operational loads in the French Air Force: Defining new equipment p 292 N85-15681
- USAF approach to airborne structural data recording: Airborne Data Acquisition Multifunction System (ADAMS) p 292 N85-15683
- Engine cyclic durability by analysis and material testing p 267 N85-15744 Flutter control with unsteady aerodynamic models
- Plutter control with unsteady aerodynamic models [AD-A147858] p 270 N85-15753 Advances in composite technology
- Advances in composites technology [NASA-TM-86353] p 284 N85-17048 STRUCTURAL DESIGN
- Current problems in aviation science and technology p 199 A85-20451
- Optimization of airplane wing structures under landing loads p 252 A85-22005
- Aeroproyekt develops improved runway surfacing p 277 N85-16770
- STRUCTURAL DESIGN CRITERIA
 - Design of load-bearing aircraft structures p 288 A85-20463 An optimality criterion method for structures with stress,
- displacement and frequency constraints p 290 A85-21985 A method of forecasting active constraint with the
- applications to structural optimization p 291 A85-22445
- Evaluation of operational loads to verify structural design p 254 N85-15677 STRUCTURAL FAILURE
- Utilization of analytical equipment in design and process problems solution and failure analysis of composites p 281 A85-21390 TUTOR (CL-41A) tail flight load survey

Coupled helicopter rotor/body aeromechanical stability

Experiences obtained from service fatigue monitoring

Flight parameters recording for structure fatigue life

Theory of vibration conduction as a method for

Aeroelastic stability and vibration of layered plates and

On the excitations due to the periodic structure of

Vibration tailoring of advanced composite lifting

Technology developments for laminar boundary layer

Comparative study of various quadratures for subsonic

Calculation of compressible potential flow about

On boundary layer transition in high-subsonic and

Prediction of subsonic/transonic separated flow about

Subsonic pressure distributions near a wing-fin juncture

Linearized potential flow analysis of complex aircraft

configurations by HISSS, a higher order panel method

on a supersonic arrow-wing configuration with

transonic flow under the influence of acoustic disturbances

multielement airfoils using a finite field-panel approach

comparison of theoretical and experimental results

Advanced fatigue monitoring on service aircraft

Structural Usage

calculating the vibration of complex structures

STRUCTURAL STABILITY

STRUCTURAL STRAIN

STRUCTURAL VIBRATION

exercises

(SUMS)

monitoring

cylindrical shells

turbomachines

SUBSONIC FLOW

SUBSONIC AIRCRAFT

control on subsonic transport aircraft

lifting surface chordwise integrals

[AIAA PAPER 85-0038]

and free-stream turbulence

[AIAA PAPER 85-0082]

[AIAA PAPER 85-02051

ving-mounted vertical fins

AIAA PAPER 85-02761

[AIAA PAPER 85-0281]

surfaces

airfoils

Tornado:

p 254 N85-15678

p 252 A85-21847

p 292 N85-15671

p 292 N85-15672

Monitoring System

p 292 N85-15680

p 292 N85-15682

p 287 A85-20454

p 288 A85-20472

p 288 A85-20800

p 290 A85-21846

p 237 N85-16787

p 205 A85-19404

p 207 A85-19473

p 210 A85-19508

p 215 A85-19589

p 217 A85-19628

p 217 A85-19632

Passive control effects on flow separation around a protuberance at high subsonic speed ---- for optical propagation quality enhancement to and from airborne platforms

[AIAA PAPER 85-0351] p 220 A85-19690 Effect of inlet and outlet flow conditions on the flow and performance of subsonic two-dimensional diffuser

p 228 A85-20241 Ground interference effects on subsonic dynamic stall in pitch and plunge p 231 A85-21841

SUBSONIC FLUTTER

Subsonic wing rock of slender delta wings [AIAA PAPER 85-0198] p 214 A85-19582

SUBSONIC SPEED Aileron effectiveness for a subsonic transport model with

a high-aspect-ratio supercritical wing [NASA-TM-85674] p 235 N85-15695

SUBSONIC WIND TUNNELS An experimental investigation of an airfoil undergoing large amplitude pitching motions

[AIAA PAPER 85-0039] p 207 A85-19474 The use of panel methods for the development of

Iow-subsonic wall interference and blockage corrections [AIAA PAPER 85-0159] p 212 A85-19556 The Altitude Wind Tunnel (AWT) - A unique facility for

propulsion system and adverse weather testing [AIAA PAPER 85-0314] p 275 A85-19661 Analytical modeling of circuit aerodynamics in the new NASA Lewis wind tunnel

[NASA-TM-86912] p 234 N85-15688 SUCTION

Computational study of circulation control with suction [AIAA PAPER 85-0042] p 208 A85-19477 Trapping of free vortex by airfoils with surface suction

 [AIAA PAPER 85-0446]
 p 224
 A85-19755

 Drag reduction due to boundary-layer control by combined blowing and suction
 p 237
 N85-16785

Design studies of thick laminar flow airfoils for low speed flight employing turbulent boundary layer suction over the

rear part p 257 N85-16786 Turbulent drag reduction research p 237 N85-16788

Active and passive shock/boundary layer interaction control on supercritical airfoils p 238 N85-16795 SULFONES

A thermoplastic polyimidesulfone --- synthesis of processable and solvent resistant system

p 282 A85-21483 SUPERCOMPUTERS

ONERA - The aeronautics supercomputer is put into service p 302 A85-22274 SUPERCRITICAL AIRFOILS

Measurements of separating boundary layer and wake of an airfoil using laser Doppler velocimetry

[AIAA PAPER 85-0161] p 214 A85-19572 Supercritical airfoil drag reduction by passive shock wave/boundary layer control in the Mach number range .75 to .90

[AIAA PAPER 85-0207] p 215 A85-19591 A comparative study between an implicit and explicit algorithm for transonic airfoils

[AIAA PAPER 85-0480] p 225 A85-19777 Design of lifting symmetric supercritical airfoils p 233 A85-22228

SUPERCRITICAL FLOW

Joined wing transonic design and test validation [AD-A148355] p 239 N85-16834

SUPERCRITICAL PRESSURES

Comparison of analytical and experimental steadyand unsteady-pressure distributions at Mach number 0.78 for a high-aspect-ratio supercritical wing model with oscillating control surfaces

[NASA-TM-84589] p 235 N85-15697 SUPERCRITICAL WINGS

Alleron effectiveness for a subsonic transport model with a high-aspect-ratio supercritical wing

[NASA-TM-85674] p 235 N85-15695 Comparison of analytical and experimental steadyand unsteady-pressure distributions at Mach number 0.78 for a high-aspect-ratio supercritical wing model with oscillating control surfaces

[NASA-TM-84589] p 235 N85-15697 Installed nacelle drag-improvement tests of an M = 0.8

turboprop transport configuration [NASA-TM-84302] p 255 N85-15716 Active and passive shock/boundary layer interaction

control on supercritical airfoils p 238 N85-16795 SUPERSONIC AIRFOILS Subsonic pressure distributions near a wing-fin juncture

on a supersonic arrow-wing configuration with wing-mounted vertical fins [AIAA PAPER 85-0276] p 217 A85-19628

SUPERSONIC COMBUSTION RAMJET ENGINES Spectral methods for modeling supersonic chemically

reacting flow fields [AIAA PAPER 85-0302] p 219 A85-19651 Langley Mach 4 scramjet test facility [NASA-TM-86277] p 278 N85-16883 SUPERSONIC FLIGHT

Aerodynamic configured missiles - Promise and future [AIAA PAPER 85-0345] p 248 A85-19684 SUPERSONIC FLOW

A comparison of Euler and Navier-Stokes solutions for supersonic flow over a conical delta wing

[AIAA PAPER 85-0111] p 210 A85-19526 A procedure for the calculation of supersonic flows with strong viscous-inviscid interaction

[AIAA PAPER 85-0166] p 213 A85-19562

A study of compressible turbulent free shear layers using laser Doppler velocimetry [AIAA PAPER 85-0177] p 213 A85-19569

Linearized potential flow analysis of complex aircraft configurations by HISSS, a higher order panel method (AIAA PAPER 85-0281) p 217 A85-19632

The distortion of a supersonic turbulent boundary layer by bulk compression and surface curvature [AIAA PAPER 85-0299] p 218 A85-19648

A study of the effects of numerical dissipation on the calculation of supersonic separated flows [AIAA PAPER 85-0301] p 219 A85-19650

Spectral methods for modeling supersonic chemically reacting flow fields [AIAA PAPER 85-0302] p 219 A85-19651

Shock induced vortices on elliptic cones in supersonic flow [AIAA PAPER 85-0433] p 223 A85-19746

A three-dimensional adaptive grid method --- for computational fluid dynamics

 [AIAA PAPER 85-0466]
 p 225 A85-19783

 Real-gas
 flowfields
 about

 configurations
 p 231 A85-21830

 Shock-fitting solution of the supersonic flowfield in a rounded internal corner
 p 232 A85-21856

 Computation of choked and supersonic turbomachinery flows by a modified potential method
 contact and supersonic turbomachinery

p 232 A85-21859 Shock-free turbomachinery blade design p 232 A85-21864 Flow behind an attached shock wave in a radiating

gas p 233 A85-22308 An extremum problem concerning the shape of a body of revolution in supersonic gas flow p 234 A85-22371 An investigation of vortex-induced aerodynamic

characteristics of supersonic cruise configurations [NASA-CR-174299] p 234 N85-15690 Recent advances in computational methods to solve

the high-lift multi-component airfoil problem p 236 N85-16774

SUPERSONIC JET FLOW

Theoretical study on supersonic jet plumes p 206 A85-19439

Investigation of nonlinear effects in the instabilities and noise radiation of supersonic jets [AIAA PAPER 85-0081] p 304 A85-19507

SUPERSONIC NOZZLES

Effect of the arrangement of apertures on the gain coefficient during asymmetric gas injection into a Laval nozzle p 229 A85-20562 SUPERSONIC SPEEDS

Analysis of counter-rotating propeller performance [AIAA PAPER 85-0005] p 262 A85-19453 SUPERSONIC WAKES

The computational treatment of supersonic wake flows in INCOREL

[AIAA PAPER 85-0304] p 219 A85-19653 Vortex path in the supersonic wake of a rough even

plate --- German thesis p 226 A85-19821 SUPPORT SYSTEMS

UH-60A external stores support system fixed provision fairings drag determination

- [AD-Ā147188] p 256 N85-15719 SURFACE EFFECT SHIPS
- Development of asymptotic algorithms in the Polet package of applications programs — for sea surface effect vehicle design p 233 A85-22366 SUBFACE GEOMETRY

Conical bodies with a star-shaped transverse cross section, having a reserve of static stability p 229 A85-20557

SURFACE LAYERS Aeroproyekt develops improved runway surfacing

p 277 N85-16770 SURFACE PROPERTIES

Measurements of water film characteristics on airfol surfaces from wind-tunnel tests with simulated heavy rain

[AIAA PAPER 85-0259] p 274 A85-19618 SURFACE ROUGHNESS EFFECTS

Vortex path in the supersonic wake of a rough even plate — German thesis p 226 A85-19821 [AD-A147116] p 277 N85-15760 SWEPT FORWARD WINGS Forward sweep - The pros and cons p 250 A85-20146 SWEPT WINGS Three-dimensional effects on a pitching lifting surface

Development of a preliminary ALRS stabilized material

SURFACE STABILITY

[AIAA PAPER 85-0041]

pavement analysis system (SPAS)

Disturbance-wave interactions in flows with crossflow [AIAA PAPER 85-0494] p 226 A85-19788 Experiments on the stability of crossflow vortices in rept-wing flows [AIAA PAPER 85-0493] p 231 A85-20873 Application of two and three-dimensional criteria for calculating transitions and boundary layers over swept p 237 N85-16783 wings Full scale experiments into the use of large eddy breakup devices for drag reduction on aircraft p 257 N85-16790 Joined wing transonic design and test validation

[AD-A148355] p 239 N85-16834 SWIRLING

Flow visualization of lateral jet injection into swirling crossflow

[AIAA PAPER 85-0059] p 209 A85-19490 Calculation of confined swirling flows

[AIAA PAPER 85-0060] p 285 A85-19491 An experimental investigation of the mixing of co-annular swirting flows

[AIAA PAPER 85-0186] p 230 A85-20862 Swirling flow in a research combustor

p 283 A85-21863

Downwash in the plane of symmetry of an elliptically loaded wing

[NASA-TP-2414] p 235 N85-15693 SYNCHROPHASING

An improved source model for aircraft interior noise studies

[NASA-CR-172517] p 305 N85-17668 SYSTEM EFFECTIVENESS

S-3A ballast block final design and engineering tests [AD-A147685] p 243 N85-16842

SYSTEMS ENGINEERING United States Air force aircraft modification process: A system dynamics analysis

[AD-A146954] p 200 N85-15659 Automatic briefing and mission management systems

for battlefield support p 259 N85-16799 Development and flight test of a helicopter compact,

portable, precision landing system concept p 261 N85-16821

SYSTEMS INTEGRATION

Military avionics - Increasing integration at all levels p 244 A85-20221 Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 p 200 A85-21456 Software design methods --- for civil and military aircraft p 301 A85-21457 avionics systems A design methodology for integrated avionic systems p 301 A85-21458 Hardware design techniques --- systems integration for civil and military aircraft avionics p 244 Packaging and interconnection for avionics p 244 A85-21459 p 290 A85-21460 p 245 A85-21461 Integrated navigation Integrated communications - A designers view -- for civil and military aircraft avionics p 245 A85-21462 Trends in digital flight control systems p 269 A85-21465 Trends in digital engine control - Integration of propulsion control with flight control and avionic systems in future military and commercial aircraft p 264 A85-21466 The impact of integrated systems - The helicopter p 252 A85-21467 designer's viewpoint p 252 A85-21467 The Cockpit Display of Traffic Information and the Threat Alert and Collision Avoidance System Integration - A p 259 A85-21559 review The design and development of an integrated core system for battlefield helicopters p 260 N85-16811 Evolution toward a multi-bus architecture for Army helicopter avionic systems p 260 N85-16812 Integration of sensor fusion in advanced helicopter p 260 N85-16813 cockpit design p 260 N85-16813 Development, production and testing of central control and display unit for helicopters [BMFT-FB-W-84-039] p 261 N85-16871 SYSTEMS SIMULATION

The Mission Oriented Terminal Area Simulation (MOTAS) [AIAA PAPER 85-0308] p 274 A85-19655

SYSTEMS SIMULATION

p 208 A85-19476

p 233 A85-22368

p 295 N85-16096

p 259 A85-21559

p 211 A85-19536

p 239 N85-16838

SYSTEMS STABILITY

SFRJ simulator results - Experiment and analysis in cold

flow ---- Solid Fuel RamJet [AIAA PAPER 85-0329] p 263 A85-19671 Analysis and testing of the Diamond One wing anti-icing

vsterr [AIAA PAPER 85-0414] p 286 A85-19735 A digital piloting system for the combat helicopter

p 260 N85-16806 A simulator for studying helicopter weapons systems p 277 N85-16816

SYSTEMS STABILITY

A generalized stability criterion for nonlinear dynamic systems --- modeling aircraft roll maneuvers p 300 A85-19586 [AIAA PAPER 85-0202]

Stability of squeeze film damped multi-mass flexible rotor bearing systems

p 289 A85-21296 ASME PAPER 84-TRIB-451

Т

- TAIL ASSEMBLIES
- Environmental effects and durability evaluation of advanced composite fuselage structures
- p 251 A85-21388 Experiences obtained from service fatigue monitoring p 292 N85-15672 exercises

TUTOR (CL-41A) tail flight load survey p 254 N85-15678 All-composite Airbus empennage p 284 N85-15931

TAIL ROTORS Aeroelastic characteristics of the AH-64 bearingless tail

p 250 A85-20142 rotor TAKEOFF

- Airport activity statistics of certificated route air carriers [AD-A148472] p 243 N85-16846
- Optimum performance parameters for ski-jump operations of USAF fighter aircraft [AD-A148532]
- p 258 N85-16867 TANDEM WING AIRCRAFT

The joined wing - An overview --- aircraft tandem wings in diamond configurations [AIAA PAPER 85-0274] p 247 A85-19626

TARGET RECOGNITION Contrast sensitivity performance assessment of HUD display systems p 259 A85-21593

TECHNOLOGICAL FORECASTING

Forward sweep - The pros and cons p 250 A85-20146 Trends in civil aircraft design p 200 A85-22226 The application of a technology index to aircraft turbine engine cost estimating relationships [AD-A147701] p 268 N85-16874 The aircraft engine of the future [PNR-90226] p 268 N85-16875

TECHNOLOGY ASSESSMENT Circulation control airfoils - Past, present, future [AIAA PAPER 85-0204] p 215 A85-19588

Advanced helicopter technology - Industry girds for challenges of evolving operational needs p 199 A85-20057

Technology gains expected to yield LHX size, weight, p 249 A85-20058 cost reductions Computers and progress in aviation

p 199 A85-20453 Review of the origin of Japanese Industrial Standard p 280 A85-20545

Modern military engines, II p 264 A85-20822 Advanced technology - The key to European competitiveness --- in Airbus industry p 200 A85-21680

The application of a technology index to aircraft turbine engine cost estimating relationships [AD-A147701] p 268 N85-16874

TECHNOLOGY UTILIZATION

Integrated technology wing study (oral presentation) (NASA-CR-1694971 p 256 N85-15718 Impressions from a study tour in Finland concerning fiber reinforced plastics, June 1984

p 283 N85-15831 [FOA-C-20552-D2(E4,F9)] TELESCOPES

Evaluation of nose, roof, and mast mounted sensor platforms for piloting and sighting, integrated in future combat helicopters p 260 N85-16808

TEMPERATURE GRADIENTS Temperature distortion generator for turboshaft engine

testing [NASA-TM-83748] p 200 N85-15658

TEMPERATURE INVERSIONS Effect of steady-state temperature distortion on inlet flow

to a high-bypass-ration turbofan engine [NASA-TM-86896] p 265 N85-15725 TEMPERING

Fatigue crack growth behavior of 7XXX aluminum alloys under simple variable amplitude loading p 280 A85-20759

TEST EQUIPMENT

Swirling flow in a research combustor

- p 283 A85-21863 Heater block assembly for use in thermal oxidation testing of jet fuel
- p 285 N85-17077 [AD-D011430] TEST FACILITIES
- Vortex research facility improvements and preliminary density stratification effects on vortex wakes p 209 A85-19482 [AIAA PAPER 85-0050]
- Environmental test capabilities of the Air Force McKinley Climatic Laboratory
- [AIAA PAPER 85-0089] p 273 A85-19512 Big wind at Tullahoma --- USAF's new aeropropulsion test facility p 275 A85-20122 Equipment for preflight test of an Electronic
- Countermeasures (ECM) avionic system p 293 N85-15949

Langley Mach 4 scramiet test facility [NASA-TM-86277] p 278 N85-16883 TEST RANGES

Some thoughts on the range/tunnel transition controversy

- [AIAA PAPER 85-0127] p 211 A85-19538 The Western Aeronautical Test Range of NASA Ames **Research Center**
- [AIAA PAPER 85-0316] p 275 A85-19678 TEST STANDS
- A universal turboshaft engine test cell Design considerations and model test results

[AIAA PAPER 85-0382] p 275 A85-19711 THERMAL ANALYSIS

The thermal response of aircraft cabin ceiling materials during a post-crash, external fuel-spill, fire scenario [AIAA PAPER 85-0395] p 241 A85p 241 A85-19721

- THERMAL BOUNDARY LAYER Advances in heat transfer. Volume 16
- p 288 A85-20501 THERMAL CONDUCTIVITY
- Theory of vibration conduction as a method for calculating the vibration of complex structures p 287 A85-20454
- THERMAL EATIGUE
- Cumulative damage modeling of fatigue crack growth p 267 N85-15741
- Engine cyclic durability by analysis and material p 267 N85-15744 testin THERMAL INSULATION

Description of the insulation system for the Langley 0.3-Meter Transonic Cryogenic Tunnel

- [NASA-TM-86274] p 276 N85-15755 FRG ceramic engine components (PET) p 297 N85-17193
- THERMAL PROTECTION Rolls-Royce experience with thermal barrier coatings ---
- in aircraft engines [PNR-90222] p 285 N85-17152 THERMAL STABILITY
- V-378A, a new modified bismaleimide matrix resin for high modulus graphite p 282 A85-21482 Heater block assembly for use in thermal oxidation testing of jet fuel
- [AD-D011430] p 285 N85-17077 THERMAL STRESSES
- Development of a fatigue crack propagation model of Incolov 901 p 280 A85-20758 Universal matrices to obtain thermal load vectors for
- the family of anisotropic plane triangular finite elements p 291 A85-22232
- Monitoring engine thermal stresses p 266 N85-15735 THERMOCHEMISTRY
- Laminar heat-transfer distributions on biconics at incidence in hypersonic-hypervelocity flows
- [NASA-TP-2213] p 293 N85-16065 **THERMOCOUPLES**

High temperature thermocouple and heat flux gauge using a unique thin film-hardware hot juncture [NASA-TM-86898] n 295 p 295 N85-16096

THERMODYNAMIC CYCLES Off-design point characteristics of the precooled gas

turbine cycle with liquefied hydrogen as fuel p 289 A85-20884 THERMODYNAMIC PROPERTIES

Real gas effects in advanced technology engines [AIAA PAPER 85-0252] p 262 A85-1 p 262 A85-19615 THERMOPLASTICITY

A thermoplastic polyimidesulfone --- synthesis of processable and solvent resistant system. p 282 A85-21483

parabolic partial differential equations

p 300 A85-19782 [AIAA PAPER 85-0485] A three-dimensional adaptive grid method --- for computational fluid dynamics

[AIAA PAPER 85-0486] p 225 A85-19783 Simulation of transonic three-dimensional nacelle/inlet flowfields using an Euler/Navier-Stokes algorithm

[AIAA PAPER 85-0084] p 226 A85-19798 A new approach to some hybrid aerodynamic problems of airfoil cascades on a general streamsheet of revolution.

p 228 A85-20229 Complete three-dimensional flow solution of a cascade incorporating splitter vanes of arbitrary geometry

p 228 A85-20230 Calculation and analysis of the three-dimensional flow

in centrifugal compressor impellers p 228 A85-20231 The fundamental equations of 3-dimensional two-phase particulate gas flow and a twofold stream surfaces model

of solution for particulate gas flow in turbomachines p 228 A85-20233

of digital interferogram evaluation Application techniques to the measurement of three-dimensional flow fields

[AIAA PAPER 85-0037] p 288 A85-20852

A-34

Computation of three-dimensional flows for application to transonic compressors [ONERA, TP NO. 1984-146] p 204 A85-19260 A comparison of different three-dimensional singularity methods for modelling internal flows [ONERA, TP NO. 1984-150] p 205 A85-19264 Three-dimensional effects on a pitching lifting surface

THIN AIRFOILS

THIN FILMS

review

[NASA-TM-868981

THREAT EVALUATION

[AIAA PAPER 85-0125]

[BMFT-FB-W-84-036]

THREE DIMENSIONAL FLOW

transport aircraft

[AIAA PAPER 85-0041] p 208 A85-19476 Turbulence structure of a three dimensional impinging jet in a cross stream

Approximate solution of a nonlinear problem of flow past

High temperature thermocouple and heat flux gauge

The Cockpit Display of Traffic Information and the Threat

Surface pressure fluctuations in a three-dimensional

Theoretical contributions to transonic flow analysis for

Alert and Collision Avoidance System Integration - A

a thin airfoil profile near a support surface

THREE DIMENSIONAL BOUNDARY LAYER

shock wave/turbulent boundary layer interaction

using a unique thin film-hardware hot juncture

- p 208 A85-19478 AIAA PAPER 85-00441 Three-dimensional inviscid flow analysis of turbofan forced mixers
- [AIAA PAPER 85-0086] p 210 A85-19510 A theory for the core of a three-dimensional leading-edge vortex

p 210 A85-19524 [AIAA PAPER 85-0108] Three-dimensional Euler solutions with grid embedding

p 211 A85-19532 [AIAA PAPER 85-0121] Numerical solution of the Euler equations for high-speed, blended wing-body configurations

[AIAA PAPER 85-0123] p 211 A85-19534 Three-dimensionality in unsteady flow about a wing

[AIAA PAPER 85-0132] p 212 A85-19543 A new iterative matrix solution procedure for

three-dimensional panel methods [AIAA PAPER 85-0176] p 213 A85-19568

Application of axisymmetric analogue for calculating heating in three-dimensional flows

[AIAA PAPER 85-0245] p 216 A85-19611 Aerodynamics of an aspect ratio 8 wing at low Reynolds numbers [AIAA PAPER 85-0278] p 217 A85-19630

A three-dimensional Navier-Stokes/Euler code for

A Navier-Stokes calculation of 3-D, turbulent flow near

Three-dimensional airflow and hydrometeor trajectory

Split-flux-vector solutions of the Euler equations for

Tomographic reconstruction of three-dimensional flow

Noniterative three-dimensional grid generation using

trajectory

p 220 A85-19696

p 220 A85-19698

analysis on a

p 222 A85-19732

p 222 A85-19733

p 223 A85-19747

p 225 A85-19776

blunt-body flow computations

[AIAA PAPER 85-0361]

a propeller in a shear flow

3-dimensional engine inlet

[AIAA PAPER 85-0411]

[AIAA PAPER 85-0412]

[AIAA PAPER 85-0434]

over airfoils [AIAA PAPER 85-0479]

Computational particle

calculation with applications

three-dimensional configurations

[AIAA PAPER 85-0365]

Experiments on the stability of crossflow vortices in swept-wing flows [AIAA PAPER 85-0493] p 231 A85-20873 Real-gas flowfields about three-dimensional p 231 A85-21830 configurations Flowfield analysis of low bypass ratio test cells p 265 A85-21839 Calculation of three-dimensional unsteady incompressible flows by a vortex method p 291 A85-22240 Turbulent bubbles behind airfoils and wings at high angle p 296 N85-16779 of attack Aerodynamic issues in the design of high-lift systems for transport aircraft p 256 N85-16780 Application of two and three-dimensional criteria for calculating transitions and boundary layers over swept p 237 N85-16783 wings THRUST AUGMENTATION A zonal computational approach to thrust augmentor optimization [AIAA PAPER 85-0110] p 262 A85-19525 THRUST CONTROL Aircraft thrust control scheme for terrain following system p 255 N85-15711 IAD-D0113871 TILT ROTOR AIRCRAFT A longitudinal stability augmentation system for a tilt rotor aircraft [AIAA PAPER 85-0072] p 268 A85-19498 Structural components, design of tilt-rotor JVX near Speed benefits of tilt-rotor designs for LHX completion [NASA-CR-166437] p 255 N85-15717 TILTING ROTORS Speed benefits of tilt-rotor designs for LHX [NASA-CR-166437] p 255 N85-15717 TIME MARCHING time-stepping scheme for the A multistage Navier-Stokes equations p 207 A85-19472 [AIAA PAPER 85-0035] TIME MEASUREMENT Effects of aircraft and flight parameters on energy-efficient profile descents in time-based metered traffic [NASA-CR-172338-ADD] p 245 N85-15706 TIME SERIES ANALYSIS Time series analysis of closed-loop pilot vehicle p 271 N85-16876 TIP SPEED Experimental investigation of backswept centrifugal compressor impeller. I p 264 A85-20243 TITANIUM ALLOYS Metallurgical and mechanical phenomena due to rubbing of titanium against sintered powder Nichrome n 291 A85-22281 Disc fatigue life predictions for gas turbine engines p 267 N85-15743 TOLERANCES (MECHANICS) Advances in composites technology [NASA-TM-86353] p 284 N85-17048 TOLLMEIN-SCHLICHTING WAVES Disturbance-wave interactions in flows with crossflow [AIAA PAPER 85-0494] p 226 A85-19788 TOMOGRAPHY Tomographic reconstruction of three-dimensional flow over airfoils TAIAA PAPER 85-04791 p 225 A85-19776 TOOLING Tooling problems in the manufacture of AH-64 Composites Flexbeam Tail Rotor p 200 A85-21382 TOPOGRAPHY A Computer-generated topographic display system for navigation and mission planning in helicopters p 259 N85-16800 A method for determining mesoscale dynamic topography [AD-D011412] p 300 N85-17506 TOXIC HAZARDS Evaluation of aircraft interior panels under full-scale cabin fire test conditions TAIAA PAPER 85-03931 p 240 A85-19719 TRACKING (POSITION) Stereo Electro-optical Tracking System (SETS) [NASA-CR-172471] p 295 N85-16098 TRACKING FILTERS A three-dimensional Kalman filter for short observation times to extrapolate flight trajectories --- German thesis p 301 A85-19835 TRAILING EDGES

A class of airfoils having finite trailing edge pressure gradients

 [AIAA PAPER 85-0206]
 p 215
 A85-19590

 Free surface scars and striations due to trailing vortices

 generated by a submerged lifting surface

 [AIAA PAPER 85-0445]
 p 286

 A85-19754

Experimental results for Reynolds number effects on p 232 A85-21849 trailing vortices Scaling of airfoil self-noise using measured flow aramet p 304 A85-21858 TRAINING AIRCRAFT Analysis of the flow field about a T-45 using PANAIR AD-A1468111 p 236 N85-15699 TRAINING SIMULATORS Modular simulators, their feasibility, design, and rocurement p 274 A85-19659 [AIAA PAPER 85-0312] History of the development and manufacture of flight simulators in Czechoslovakia and the rest of the world p 275 A85-19878 TRAJECTORIES A Generalized Escape System Simulation (GESS) computer program. Volume 2: GESS programmer's manual, version 2 [AD-A148363] n 243 N85-16845 TRAJECTORY ANALYSIS A three-dimensional Kalman filter for short observation times to extrapolate flight trajectories --- German thesis p 301 A85-19835 TRAJECTORY OPTIMIZATION Maximum finat energy chandelle [AIAA PAPER 85-0200] p 247 A85-19584 A parallel quasi-linearization algorithm for air vehicle trajectory optimization [AIAA PAPER 85-0498] p 279 A85-19792 Calculation of the minimum-time loop maneuver for jet p 269 A85-19876 aircraft TRANSDUCERS Unsteady pressure measurements on a biconvex airfoil in a transonic oscillating cascade [NASA-TM-86914] p 234 N85-15689 TRANSMISSION LOSS Atmospheric propagation losses for long-range airborne radar systems analysis [AIAA PAPER 85-0267] p 244 A85-19620 Field-incidence noise transmission loss of general aviation aircraft double-wall configurations p 304 A85-21842 TRANSMISSIONS (MACHINE ELEMENTS) Development of a graphite/polyimide composite transmission housing p 281 A85-21380 Investigation on experimental techniques to detect, locate and quantify gear noise in helicopter transmissions [NASA-CR-38471 p 305 N85-17667 TRANSONIC COMPRESSORS Computation of three-dimensional flows for application to transonic compressors [ONERA, TP NO. 1984-146] p 204 A85-19260 TRANSONIC FLIGHT TRO-2D - A code for rational transonic aerodynamic optimization [AIAA PAPER 85-0425] p 223 A85-19740 Joined wing transonic design and test validation [AD-A148355] p 239 N85-16834 TRANSONIC FLOW An improved version of the LTRAN2 for high frequency p 205 A85-19401 domain Numerical solutions of viscous transonic flow in turbornachinery cascades [AIAA PAPER 85-0007] p 206 A85-19454 On boundary layer transition in high-subsonic and transonic flow under the influence of acoustic disturbances and free-stream turbulence [AIAA PAPER 85-0082] p 210 A85-19508 A quasi-conservative lambda formulation --- for inviscid transonic flow simulation [AIAA PAPER 85-0088] p 210 A85-19511 Analysis of circulation control airfoils using an implicit Navier-Stokes solver [AIAA PAPER 85-0171] p 213 A85-19565 Computation of unsteady shock-induced vortex eparation [AIAA PAPER 85-0183] p 214 A85-19573 Prediction of subsonic/transonic separated flow about urfoils [AIAA PAPER 85-0205] p 215 A85-19589 Prediction of HiMAT RPRV component interference effects at transonic speeds [AIAA PAPER 85-0213] p 215 A85-19593 Multigrid solution of the Euler equations using implicit [AIAA PAPER 85-0293] p 218 A85-19643 Recent advances in computational transonic erodynamic [AIAA PAPER 85-0366] p 221 A85-19699 Breakdown of the conservative potential equation --- for study of transonic flow [AIAA PAPER 85-0367] p 221 A85-19700 The numerical simulation of steady transonic rotational

flow using a dual potential formulation [AIAA PAPER 85-0368] p 221 A85-19701

TRANSONIC WIND TUNNELS

Shock waves in transonic channel flows at moderate Revnolds number [AIAA PAPER 85-0369] p 221 A85-19702 Viscous/inviscid interaction analysis of transonic shock induced separated flow including normal pressure aradients [AIAA PAPER 85-0371] p 221 A85-19703 Navier-Stokes computations of axisymmetric transonic flows with a two-equation model of turbulence p 221 A85-19705 [AIAA PAPER 85-0373] Numerical optimization design of advanced transonic wing configurations [AIAA PAPER 85-0424] p 248 A85-19739 Finite volume solution of the two-dimensional Euler equations on a regular triangular mesh [AIAA PAPER 85-0435] p 223 A85-19748 A comparative study between an implicit and explicit algorithm for transonic airfoils p 225 A85-19777 [AJAA PAPER 85-0480] Efficient self-consistent viscous-inviscid solutions for unsteady transonic flow [AIAA PAPER 85-0482] p 225 A85-19779 Simulation of transonic three-dimensional nacelle/inlet flowfields using an Euler/Navier-Stokes algorithm p 226 A85-19798 TAIAA PAPER 85-00841 Computation of transonic inlet flows --- German thesis p 227 A85-19844 A subdomain finite element method for solving the conservative full potential equation for transonic profile p 227 A85-19854 flows --- German thesis A fast algorithm for solving the conservative transonic S1 full potential equation employing non-orthogonal curvilinear coordinates and non-orthogonal velocity components p 228 A85-20239 A stream function relaxation method for solving transonic S1 stream surface with respect to non-orthogonal p 228 A85-20240 curvilinear coordinates A linearized unsteady aerodynamic analysis for transonic cascades p 229 A85-20744 Finite element solutions of Euler equations for lifting airfoils [AIAA PAPER 85-0294] p 230 A85-20864 Shock-free turbomachinery blade design p 232 A85-21864 Nonreflecting boundary conditions for the complete unsteady transonic small-disturbance equation p 290 A85-21875 Design of lifting symmetric supercritical airfoils p 233 A85-22228 The full-approximation method in the theory of transonic p 233 A85-22367 flows A comparative study of the nonuniqueness problem of the potential equation [NASA-TP-2385] p 235 N85-15694 An exploratory study of finite difference grids for transonic unsteady aerodynamics [NASA-TM-84583] p 235 N85-15696 Shock waves in transonic flows at moderate Reynolds p 238 N85-16823 Number Theoretical contributions to transonic flow analysis for transport aircraft [BMFT-FB-W-84-036] p 239 N85-16838 TRANSONIC NOZZLES A quasi-conservative lambda formulation --- for inviscid transonic flow simulation AIAA PAPER 85-00881 p 210 A85-19511 TRANSONIC SPEED Body flow field simulation and force/moment prediction at transonic speeds [AIAA PAPER 85-0423] p 222 A85-19738 Artificial dissipation models for the Euler equations p 231 A85-20870 [AIAA PAPER 85-0438] Prediction of cruciform all-movable control characteristics at transonic speeds p 239 N85-16832 [AD-A147291] TRANSONIC WIND TUNNELS Tests, in the transonic regime, of a model motorized by a blowing turbine 23 cm in diameter (9 inches) in the S1MA wind tunnel [ONERA, TP NO. 1984-158] p 272 A85-19272 Supercritical airfoil drag reduction by passive shock wave/boundary layer control in the Mach number range 75 to .90 p 215 A85-19591 [AIAA PAPER 85-0207] Studies of condensation effects on airfoil testing in a transonic cryogenic tunnel [AIAA PAPER 85-0229] p 274 A85-19603 Development of the UTA High Reynolds Number Transonic Wind Tunnel p 275 A85-19662 [AIAA PAPER 85-0315]

(AIAA PAPER 65-0315) p 275 A65-19602 Correlation of airfoil icing relationships with two-dimensional model and full scale rotorcraft icing test data

[AIAA PAPER 85-0337] p 240 A85-19680

A-35

TRANSPORT AIRCRAFT

- Computational aerodynamic design of the Gulfstream IV wing [AIAA PAPER 85-0427] p 223 A85-19742
- The most spectacular equipment ETW p 276 A85-21422
- Description of the insulation system for the Langley 0.3-Meter Transonic Cryogenic Tunnel [NASA-TM-86274] p 276 N85-15755
- TRANSPORT AIRCRAFT The influence of camber variation on the aerodynamics
- of civil transport aircraft [AIAA PAPER 85-0353] p 220 A85-19691
- Measurements of the response of transport aircraft ceiling panels to fuel pool fires
- [AIAA PAPER 85-0394] p 240 A85-19720 The development of a finite element model of an aircraft vertical stabilizer for vibration analysis
- p 290 A85-21683 Ground-effect analysis of a jet transport airplane
- [NASA-TM-85920]
 p 234
 N85-15687

 Integrated technology wing study (oral presentation)
 [NASA-CR-169497]
 p 256
 N85-15718
- Design and test requirements for development of today's engines p 266 N85-15737
- Documentation and separate test program development is most important for test/maintenance
- p 203 N85-16745 Aerodynamic issues in the design of high-lift systems for transport aircraft p 256 N85-16780
- Technology developments for laminar boundary layer control on subsonic transport aircraft p 237 N85-16787
- Theoretical contributions to transonic flow analysis for transport aircraft
- [BMFT-FB-W-84-036] p 239 N85-16838 The visibility climatology of McMurdo Sound-Williams Field, Antarctica [AD-A149108] p 300 N85-17492
- TRANSPORTATION USSR report: Transportation
- [JPRS-UTR-85-001] p 204 N85-16763 TRAPPED VORTEXES
- Trapping of free vortex by airfoils with surface suction [AIAA PAPER 85-0446] p 224 A85-19755 TRUSSES
- A method of forecasting active constraint with the applications to structural optimization p 291 A85-22445

- Matrix solution of compressible flow on S(1) surface through a turbomachine blade row with splitter vanes or tandem blades p 227 A85-20228
- A new approach to some hybrid aerodynamic problems of airfoil cascades on a general streamsheet of revolution. 1 p 228 A85-20229
- Complete three-dimensional flow solution of a cascade incorporating splitter vanes of arbitrary geometry p 228 A85-20230
- The fundamental equations of 3-dimensional two-phase particulate gas flow and a twofold stream surfaces model of solution for particulate gas flow in turbomachines
- p 228 A85-20233 Influence of blowing rate and injection angle on the performance of a film-cooled blade p 265 A85-2231 Problems and possibilities for life extension in gas turbine components p 267 N85-15742 Experiences with the material bevaviour and high temperature low cycle fatigue life prediction of the IN 738
- blading alloy p 292 N85-15748 Verification of life prediction through component testing p 292 N85-15748
- TURBINE ENGINES
- Parametric estimates of propulsion system maintenance manhours
- [AD-A147120] p 201 N85-15662 Improvement of the corrosion resistance of turbine engine bearings
- [AD-A147430] p 265 N85-15731 Engine Cyclic Durability by Analysis and Testing
- [AGARD-CP-368] p 266 N85-15733 The application of a technology index to aircraft turbine engine cost estimating relationships
- [AD-A147701] p 268 N85-16874 TURBINE WHEELS
- Comparison between the properties of conventional wrought and powder metallurgical alloys for turbine disc applications p 283 N85-15739 Problems and possibilities for life extension in gas turbine components p 267 N85-15742
- Clearance flow-generated transverse forces at the rotors of thermal turbomachines [NASA-TM-77292] p 295 N85-16180

- TURBINES
- Tests, in the transonic regime, of a model motorized by a blowing turbine 23 cm in diameter (9 inches) in the S1MA wind tunnel
- [ONERA, TP NO. 1984-158] p 272 A85-19272 TURBOCOMPRESSORS
- Computation of three-dimensional flows for application to transonic compressors
- [ONERA, TP NO. 1984-146] p 204 A85-19260 An experimental investigation of stator/rotor interaction influence on multistage compressor rotor flow
- [AIAA PAPER 85-0009] p 206 A85-19455 Is the free flight/wind tunnel equivalence concept valid for unsteady viscous flow?
- [AIAA PAPER 85-0378] p 222 A85-19708
- Precalculation of rotating stall in multistage axial compressors --- German thesis p 287 A85-19832 A procedure for the optimization of the aerothermodynamic design of multistage axial compressors --- German thesis p 227 A85-19851
- Determination of surging line of two-spool axial flow compressor with cropped fan stages at low speed by use of parallel compressor theory p 264 A85-20242
- Current problems in turbomachinery fluid dynamics [AD-A147127] p 294 N85-16074
- TURBOFAN ENGINES Three-dimensional inviscid flow analysis of turbofan
- forced mixers [AIAA PAPER 85-0086] p 210 A85-19510
- Effect of steady-state temperature distortion on inlet flow to a high-bypass-ration turbofan engine
- [NASA-TM-86896] p 265 N85-15725 Flow measurement device
- [AD-D011432] p 298 N85-17369 TURBOJET ENGINES
- Aircraft turbojet engine modeling using artificial intelligence techniques
- [AIAA PAPER 85-0253]
 p 263
 A85-19616

 Some improvements on an annular combustor of AI type turbojet engine
 p 264
 A85-20235
- Prediction of performance of aircraft gas turbines p 264 A85-21682
- TURBOMACHINE BLADES Three dimensional aerodynamics of an annular cascade in a non-uniform inlet flow
- [AIAA PAPER 85-0174] p 213 A85-19567 A relaxation approach to patched-grid calculations with
- the Euler equations
- [AIAA PAPER 85-0295] p 218 A85-19644 Shock-free turbomachinery blade design p 232 A85-21864
- An improved computer model for prediction of axial gas turbine performance losses [NASA-CR-174246] p 265 N85-15724
- [NASA-CR-174246] p 265 N85-15724 TURBOMACHINERY
- Numerical solutions of viscous transonic flow in turbomachinery cascades [AIAA PAPER 85-0007] p 206 A85-19454
- (Altha FAFER 05-0007) p 200 A05-19454 On the variety of type discrimination criteria of equations on S1 and S2 stream surfaces in turbomachine
- p 228 A85-20238 On the excitations due to the periodic structure of turbomachines p 288 A85-20800
- Development of a Navier-Stokes rotor and stator analysis
- [AD-A146967] p 294 N85-16070 Clearance flow-generated transverse forces at the rotors of thermal turbomachines
- [NASA-TM-77292] p 295 N85-16180 Turbo fluid machinery and diffusers
- [NASA-TM-77467] p 298 N85-17363 TURBOPROP AIRCRAFT
- Installed nacelle drag-improvement tests of an M = 0.8 turboprop transport configuration [NASA-TM-84302] p 255 N85-15716
- TURBOPROP ENGINES
- Microprocessor control of turboprop engines p 263 A85-19877
- An improved source model for aircraft interior noise studies
- [NASA-CR-172517] p 305 N85-17668 TURBOSHAFTS
- A universal turboshaft engine test cell Design considerations and model test results
- [AIAA PAPER 85-0382] p 275 A85-19711 Temperature distortion generator for turboshaft engine testing
- [NASA-TM-83748] p 200 N85-15658 TURBULENCE
- Turbulence measurement interferometer apparatus [AD-D011377] p 295 N85-16156 Recent advances in computational methods to solve
- the high-lift multi-component airfoil problem p 236 N85-16774

- TURBULENCE EFFECTS
 - On boundary layer transition in high-subsonic and transonic flow under the influence of acoustic disturbances and free-stream turbulence
- [AIAA PAPER 85-0082] p 210 A85-19508 Effects of turbulence and viscosity variation on the dynamic coefficients of fluid film journal bearings
- (ASME PAPER 84-TRIB-8) p 289 A85-21283 Application of two and three-dimensional criteria for calculating transitions and boundary layers over swept wings p 237 N85-16783
- wings p 237 N85-16783 TURBULENT BOUNDARY LAYER Surface pressure fluctuations in a three-dimensional
- shock wave/turbulent boundary layer interaction [AIAA PAPER 85-0125] p 211 A85-19536
- Structure of the wall pressure fluctuations in a shock-induced separated turbulent flow
- [AIAA PAPER 85-0179] p 214 A85-19571 The distortion of a supersonic turbulent boundary layer by bulk compression and surface curvature
- [AIAA PAPER 85-0299] p 218 A85-19648 Viscous/inviscid interaction analysis of transonic shock induced separated flow including normal pressure gradients
- [AIAA PAPER 85-0371] p 221 A85-19703 Advances in heat transfer. Volume 16
- p 288 A85-20501 The universal nature of zero-crossing time and velocity scales in turbulent shear flows p 232 A85-21851 Flowfield scaling in sharp fin-induced shock wave/turbulent boundary-layer interaction
- Scaling of airfoil self-noise using measured flow parameters p 304 A85-21857
- parameters p 304 A85-21858 Design studies of thick laminar flow airfoils for low speed flight employing turbulent boundary layer suction over the
- rear part p 257 N85-16786 Full scale experiments into the use of large eddy breakup
- devices for drag reduction on aircraft p 257 N85-16790

TURBULENT FLOW

Noise of an airfoil in a flow [ONEBA, TP NO. 1984-155] p 303 A85-19269 Turbulent flow around a wing-fuselage type juncture p 208 A85-19475 [AIAA PAPER 85-0040] Turbulence structure of a three dimensional impinging jet in a cross stream p 208 A85-19478 [AIAA PAPER 85-0044] Accelerated convergence for incompressible flow calculations p 209 A85-19489 [AIAA PAPER 85-0058] Numerical computation of viscous flowfields about multiple component airfoils [AIAA PAPER 85-0167] p 213 A85-19563 A study of compressible turbulent free shear layers using laser Doppler velocimetry [AIAA PAPER 85-0177] p 213 A85-19569 Some features of two-dimensional turbulent separated flows [AIAA PAPER 85-0178] p 214 A85-19570 Structure of the wall pressure fluctuations in a shock-induced separated turbulent flow p 214 A85-19571 [AIAA PAPER 85-0179] Computation of unsteady shock-induced vortex separation [AIAA PAPER 85-0183] p 214 A85-19573 A Navier-Stokes investigation of a circulation control airfoil [AIAA PAPER 85-0300] p 219 A85-19649 A Navier-Stokes calculation of 3-D, turbulent flow near a propeller in a shear flow p 220 A85-19698 [AIAA PAPER 85-0365] Navier-Stokes computations of axisymmetric transonic flows with a two-equation model of turbulence [AIAA PAPER 85-0373] p 221 A85-19705 Evaluation of low Reynolds number turbulence models for attached and separated flows [AIAA PAPER 85-0375] p 286 A85-19706 The universal nature of zero-crossing time and velocity scales in turbulent shear flows p 232 A85-21851 Swirling flow in a research combustor p 283 A85-21863 Turbulence measurement interferometer apparatus [AD-D011377] p 295 N85-16156 Turbulent drag reduction research p 237 N85-16788 TURBULENT HEAT TRANSFER Calculation of friction and heat transfer in turbulent flow of a compressible gas in a plane duct p 291 A85-22114 TURBULENT JETS Flow visualization of lateral jet injection into swirling crossflow [AIAA PAPER 85-0059] p 209 A85-19490

Calculation of confined swirling flows
[AIAA PAPER 85-0060] p 285 A85-19491

SUBJECT INDEX A simple analytical method for predicting axisymmetric turbulent jet flowfields in a freestream p 216 A85-19614 [AIAA PAPER 85-0251] Advances in heat transfer. Volume 16 p 288 A85-20501 TURBULENT MIXING The interaction and merging of two turbulent line vortices p 208 A85-19480 [AIAA PAPER 85-0046] A simple analytical method for predicting axisymmetric turbulent jet flowfields in a freestream [AIAA PAPER 85-0251] p 216 A85-19614 An experimental investigation of the mixing of co-annular swirling flows [AIAA PAPER 85-0186] p 230 A85-20862 TURBULENT WAKES Vortex research facility improvements and preliminary density stratification effects on vortex wakes p 209 A85-19482 [AIAA PAPER 85-0050] Free surface scars and striations due to trailing vortices generated by a submerged lifting surface [AIAA PAPER 85-0445] p 286 A85-19754 TWO DIMENSIONAL BODIES Drag of the fundamental shapes of parachutes p 231 A85-20998 TWO DIMENSIONAL BOUNDARY LAYER Efficient self-consistent viscous-inviscid solutions for unsteady transonic flow [AIAA PAPER 85-0482] p 225 A85-19779 TWO DIMENSIONAL FLOW Theoretical study of blockage effect of wind-tunnel wall on wake of two-dimensional flat plate normal to plane p 272 A85-19402 wall An incremental block-line-Gauss-Seidel method for the Navier-Stokes equations [AIAA PAPER 85-00331 p 207 A85-19470 Computational study of circulation control with suction [AIAA PAPER 85-0042] p 208 A85-19477 Calculation of viscous nozzle flows by the unsteady method of characteristics p 212 A85-19542 [AIAA PAPER 85-0131] Analysis of circulation control airfoils using an implicit Navier-Stokes solver [AIAA PAPER 85-0171] p 213 A85-19565 Some features of two-dimensional turbulent separated flowe p 214 A85-19570 [AIAA PAPER 85-0178] Application of continuous vorticity panels to general unsteady two-dimensional lifting flows p 217 A85-19633 [AIAA PAPER 85-0282] Numerical solution of the two-dimensional Euler equations by second-order upwind difference schemes p 218 A85-19642 [AIAA PAPER 85-0292] Finite volume solution of the two-dimensional Euler equations on a regular triangular mesh p 223 A85-19748 [AIAA PAPER 85-04351 Grid adaptation for the 2-D Euler equations [AIAA PAPER 85-0484] p 225 A85-19781 On the variety of type discrimination criteria of equations on S1 and S2 stream surfaces in turbomachine p 228 A85-20238 Effect of inlet and outlet flow conditions on the flow and performance of subsonic two-dimensional diffuser p 228 A85-20241 **TWO PHASE FLOW** The fundamental equations of 3-dimensional two-phase particulate gas flow and a twofold stream surfaces model of solution for particulate gas flow in turbomachines p 228 A85-20233 Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems [NASA-CR-174271] p 242 N85-15701 TWO STAGE TURBINES Precalculation of rotating stall in multistage axial p 287 A85-19832 compressors --- German thesis U U.S.S.R. USSR report: Transportation p 204 N85-16763 [JPRS-UTR-85-001] Director on institute's civil aviation projects p 204 N85-16764 International projects, other work of Aeroproyekt Institute p 204 N85-16767 Designer on civil aircraft design trends in USSR p 256 N85-16768 UH-60A HELICOPTER UH-60A external stores support system fixed provision

fairings drag determination p 256 N85-15719 [AD-A1471881

Assessment of simulation fidelity using measurements p 278 N85-16817 of piloting technique in flight

ULTRALIGHT AIRCRAFT Effects of covering configurations on ultralight wing aerodynamics p 217 A85-19629 (AIAA PAPER 85-0277) ULTRASONIC TESTS Measurement of ice accretion using ultrasonic oulse-echo techniques [AIAA PAPER 85-0471] p 286 A85-19769 Nondestructive inspection: Improved capabilities of technicians [AD-A147388] p 295 N85-16196 UNIFORM FLOW Noise of an airfoil in a flow [ONERA, TP NO. 1984-155] p 303 A85-19269 UNITED KINGDOM Air traffic management concepts for the UK in the 1990's: A review of recent RSRE work (AD-A1478501 p 246 N85-16853 UNSTEADY FLOW A sensor for detection of unsteady distortion maxima air intakes [ONERA, TP NO. 1984-148] p 205 A85-19262 Comparative study of various guadratures for subsonic lifting surface chordwise integrals p 205 A85-19404 An experimental investigation of an airfoil undergoing large amplitude pitching motions p 207 A85-19474 [AIAA PAPER 85-0039] Solution of the unsteady Euler equations for fixed and rotor wing configurations [AIAA PAPER 85-0120] p 211 A85-19531 Numerical solution of unsteady viscous flow past rotor sections [AIAA PAPER 85-0129] p 212 A85-19540 Calculation of viscous nozzle flows by the unsteady method of characteristics [AIAA PAPER 85-0131] p 212 A85-19542 Three-dimensionality in unsteady flow about a wing [AIAA PAPER 85-0132] p 212 A85-19543 Unsteady aerodynamics of an airfoil encountering a passing vortex [AIAA PAPER 85-0203] p 214 A85-19587 A Fourier Transform method for calculating velocity profiles on airfoils [AIAA PAPER 85-0208] p 215 A85-19592 Application of continuous vorticity panels to general unsteady two-dimensional lifting flows [AIAA PAPER 85-0282] p 217 A85-19633 Recent advances in computational transonic aerodynamics [AIAA PAPER 85-0366] p 221 A85-19699 Is the free flight/wind tunnel equivalence concept valid for unsteady viscous flow? [AIAA PAPER 85-0378] p 222 A85-19708 Visualization of the spanwise vortex structure in the starting flow behind an airfoil [AIAA PAPER 85-0447] p 224 A85-19756 Efficient self-consistent viscous-inviscid solutions for unsteady transonic flow [AIAA PAPER 85-0482] p 225 A85-19779 Disturbance-wave interactions in flows with crossflow [AIAA PAPER 85-0494] p 226 A85-19788 A linearized unsteady aerodynamic analysis for transonic p 229 A85-20744 cascades An experimental investigation of an unsteady mbusting flow in a pulse combustor [AIAA PAPER 85-0322] p 281 A85-20865 Nonreflecting boundary conditions for the complete unsteady transonic small-disturbance equation p 290 A85-21875 Comparison of analytical and experimental steadyand unsteady-pressure distributions at Mach number 0.78 for a high-aspect-ratio supercritical wing model with oscillating control surfaces [NASA-TM-84589] p 235 N85-15697 Some important problems in unsteady boundary layers including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies p 294 N85-16069 [AD-A146964] UNSWEPT WINGS Turbutent bubbles behind airfoils and wings at high angle f attack p 296 N85-16779 of attack USER MANUALS (COMPUTER PROGRAMS) NOISEMAP 4.4 computer program update, operator's manual, addendum 1 [AD-A147091] p 302 N85-16503 USER REQUIREMENTS ATE user's view on design for maintainability p 202 N85-16737 V/STOL AIRCRAFT

From AV-8B to the ASTOVL

p 246 A85-19184

VISCOUS DAMPING

VANES

Matrix solution of compressible flow on S(1) surface through a turbomachine blade row with splitter vanes or tandem blades p 227 A85-20228 Complete three-dimensional flow solution of a cascade incorporating splitter vanes of arbitrary geometry

p 228 A85-20230 VARIABLE SWEEP WINGS Potential flow calculations and preliminary wing design in support of an NLF variable sweep transition flight

experiment [AIAA PAPER 85-0426] p 248 A85-19741 VARIATIONAL PRINCIPLES

Application of a variational method for generating adaptive grids --- for gas dynamics past airfoils [AIAA PAPER 85-0487] p 226 A85-19784

VELOCITY. Speed benefits of tilt-rotor designs for LHX [NASA-CR-166437] p 255 N85-15717

VELOCITY DISTRIBUTION A Fourier Transform method for calculating velocity

profiles on airfoils AIAA PAPER 85-02081 p 215 A85-19592 Calculation of the velocity field generated by a helicopter

main and tail rotors in hover o 239 N85-16833 [AD-A147731]

VENTILATION Active and passive shock/boundary layer interaction

p 238 N85-16795 control on supercritical airfoils VERTICAL LANDING

Loading characteristics of VTOL aircraft and their effect on the remaining life of the aircraft p 250 A85-20469 VERTICAL TAKEOFF AIRCRAFT

A novel experimental facility for conducting jet impingement studies related to VTOL aircraft

p 209 A85-19484 [AIAA PAPER 85-0052] Structural components, design of tilt-rotor JVX near completion p 249 A85-20059

Loading characteristics of VTOL aircraft and their effect on the remaining life of the aircraft p 250 A85-20469

Circulation control: A bibliography of DTNSRDC research and selected outside references: Update [AD-A146966] p 201 N85-15661

International aviation (selected articles) [AD-A148704] p 204 N85-16762

VHSIC (CIRCUITS) Life cycle cost model for very high speed integrated

circuits p 297 N85-17298 [AD-A147798]

VIBRATION F-8 refueling boom ground vibration test

p 255 N85-15713 [NASA-TM-84914] Analysis of the surface load and radiated sound of a vibrating airfoil with application to the experiment of Brooks

[NASA-CR-3864] p 305 N85-16590 VIBRATION DAMPING

F-8 refueling boom ground vibration test

[NASA-TM-84914] p 255 N85-15713 Study to eliminate ground resonance using active controls

[NASA-CR-166609] p 255 N85-15715 VIBRATION ISOLATORS

Stability of squeeze film damped multi-mass flexible rotor bearing systems [ASME PAPER 84-TRIB-45]

p 289 A85-21296 VIBRATION MODE

Modes of shock-wave oscillations on spike-tipped odies p 232 A85-21855 bodi **VIBRATION TESTS**

The development of a finite element model of an aircraft vertical stabilizer for vibration analysis

p 290 A85-21683

F-8 refueling boom ground vibration test [NASA-TM-84914] p 25 p 255 N85-15713 **VIBRATIONAL SPECTRA**

Investigation on experimental techniques to detect, locate and quantify gear noise in helicopter transmissions

p 305 N85-17667 [NASA-CR-3847] VISCOELASTICITY

A theoretical study of stability of a rigid rotor under the influence of dilute viscoelastic lubricants

[ASME PAPER 84-TRIB-17] p 289 A85-21278 Skirt material effects on air cushion dynamic heave

p 307 A85-21840 stability VISCOPLASTICITY

Life prediction at high temperature under multiaxial p 267 N85-15745 loading VISCOSITY

Effects of turbulence and viscosity variation on the dynamic coefficients of fluid film journal bearings ASME PAPER 84-TRIB-8) p 289 A85-21283 **VISCOUS DAMPING**

Effects of friction dampers on aerodynamically unstable p 265 A85-21866 rotor stages

VISCOUS DRAG

VISCOUS DRAG

- Aircraft drag reduction technology p 257 N85-16782
- VISCOUS FLOW Numerical solutions of viscous transonic flow in
- turbomachinery cascades [AIAA PAPER 85-0007] p 206 A85-19454 Numerical solution of unsteady viscous flow past rotor
- sections [AIAA PAPER 85-0129] p 212 A85-19540 Calculation of viscous nozzle flows by the unsteady
- method of characteristics [AIAA PAPER 85-0131] p 212 A85-19542
- Numerical computation of viscous flowfields about multiple component airfoils [AIAA PAPER 85-0167] p 213 A85-19563
- [AIAA PAPER 85-0167] p 213 A85-19563 Computation of unsteady shock-induced vortex separation
- [AIAA PAPER 85-0183] p 214 A85-19573 Recent advances in computational transonic aerodynamics
- [AIAA PAPER 85-0366] p 221 A85-19699 Viscous/inviscid interaction analysis of transonic shock induced separated flow including normal pressure gradients
- (AIAA PAPER 85-0371)
 p 221
 A85-19703

 Efficient self-consistent viscous-inviscid solutions for unsteady transonic flow
 p 225
 A85-19779

 (AIAA PAPER 85-0482)
 p 225
 A85-19779
- [AIAA PAPER 85-0482] p 225 A85-19779 Hypersonic chemically nonequilibrium viscous shock layer on wings with a catalytic surface
- p 229 A85-20561 Optimal control of flow of a viscous incompressible fluid p 290 A85-22105 Analytical modeling of circuit aerodynamics in the new
- NASA Lewis wind tunnel [NASA-TM-86912] p 234 N85-15688 Recent advances in computational methods to solve
- the high-lift multi-component airfoil problem p 236 N85-16774 Aerodynamic issues in the design of high-lift systems
- for transport aircraft p 256 N85-16780 VISCOUS FLUIDS Analysis of the surface load and radiated sound of a
- vibrating airfoil with application to the experiment of Brooks [NASA-CR-3864] p 305 N85-16590
- VISIBILITY Automated visibility measurements for airports
- [AIAA PAPER 85-0191] p 274 A85-19577 Evaluation of nose, roof, and mast mounted sensor platforms for piloting and sighting, integrated in future combat helicopters p 260 N85-16808 The visibility climatology of McMurdo Sound-Williams Field, Antarctica
- [AD-A148108] p 300 N85-17492 VISUAL FLIGHT
- Automated visibility measurements for airports [AIAA PAPER 85-0191] p 274 A85-19577 VISUAL FLIGHT RULES
- National airspace review: Airport radar service area operational confirmation report
- [DOT/FAA/AT-84/2] p 245 N85-15707 VOCODERS
- Literature review of voice recognition and generation technology for Army helicopter applications [AD-A146878] p 293 N85-15954
- VOICE COMMUNICATION Literature review of voice recognition and generation technology for Army helicopter applications
- [AD-A146878] p 293 N85-15954 VOICE CONTROL
- Speech recognition making progress Direct voice input is a promising infant p 244 A85-19183 Voice command weapons launching system (AD-D011378) p 293 N85-15940
- [AD-D011378] p 293 N85-15940 VORTEX BREAKDOWN
- Flow visualization of high angle of attack vortex wake structures [AIAA PAPER 85-0102] p 286 A85-19520
- A theory for the core of a three-dimensional leading-edge vortex
- [AIAA PAPER 85-0108] p 210 A85-19524 Turbulent drag reduction research p 237 N85-16788
- Full scale experiments into the use of large eddy breakup devices for drag reduction on aircraft p 257 N85-16790
- VORTEX GENERATORS Afterbody drag reduction by vortex generators
- [AIAA PAPER 85-0354] p 220 A85-19692 Identification of vortex-induced clear air turbulence using airline flight records p 299 A85-21843
- VORTEX SHEDDING An analysis of the flow past an S-shaped rotor by discrete
- vortex model p 206 A85-19405

A-38

- VORTEX STREETS
- Vortex path in the supersonic wake of a rough even plate -- German thesis p 226 A85-19821 VORTICES
- An experimental investigation of blade-vortex interaction at normal incidence
- [AIAA PAPER 85-0003] p 206 A85-19451 The interaction and merging of two turbulent line vortices
- [AIAA PAPER 85-0046] p 208 A85-19480 Vortex research facility improvements and preliminary
- density stratification effects on vortex wakes [AIAA PAPER 85-0050] p 209 A85-19482
- Interrelated effects of pitch rate and pivot point on airfoil dynamic stall [AIAA PAPER 85-0130] p 212 A85-19541
- Computation of unsteady shock-induced vortex separation
- [AIAA PAPER 85-0183] p 214 A85-19573 Unsteady aerodynamics of an airfoil encountering a passing vortex
- [AIAA PAPER 85-0203] p 214 A85-19587 Calculation of steady flow about propellers by means
- of a surface panel method [AIAA PAPER 85-0283] p 218 A85-19634
- The numerical simulation of steady transonic rotational flow using a dual potential formulation [AIAA PAPER 85-0368] p 221 A85-19701
- [AIAA PAPER 85-0368] p 221 A85-19701 Shock induced vortices on elliptic cones in supersonic flow
- [AIAA PAPER 85-0433] p 223 A85-19746 Free surface scars and striations due to trailing vortices generated by a submerged lifting surface
- [AIAA PAPER 85-0445] p 286 A85-19754 Visualization of the spanwise vortex structure in the starting flow behind an airfoil
- [AIAA PAPER 85-0447] p 224 A85-19756 Evaluation of vortex wake predictions in the SWINT
- code [AIAA PAPER 85-0450] p 224 A85-19759
- Experiments on the stability of crossflow vortices in swept-wing flows [AIAA PAPER 85-0493] p 231 A85-20873
- Harmonic oscillations of a rectangular wing with a circulation variable over the span p 231 A85-21656
- Experimental results for Reynolds number effects on trailing vortices p 232 A85-21849
- Calculation of three-dimensional unsteady incompressible flows by a vortex method
- p 291 A85-22240 An investigation of vortex-induced aerodynamic
- characteristics of supersonic cruise configurations [NASA-CR-174299] p 234 N85-15690
- Current problems in turbomachinery fluid dynamics [AD-A147127] p 294 N85-16074
- Full scale experiments into the use of large eddy breakup devices for drag reduction on aircraft p 257 N85-16790
- Helicopter model rotor-blade vortex interaction impulsive noise: Scalability and parametric variations
- [NASA-TM-86007] p 238 N85-16826 Prediction of dynamic stall characteristics using advanced non-linear panel methods [AD-A148453] p 239 N85-16836
- VORTICITY Application of continuous vorticity panels to general
- unsteady two-dimensional lifting flows [AIAA PAPER 85-0282] p 217 A85-19633

W

- WAKES
- Flow visualization of high angle of attack vortex wake structures
- [AIAA PAPER 85-0102] p 286 A85-19520 Calculation of steady flow about propellers by means of a surface panel method
- [AIAA PAPER 85-0283] p 218 A85-19634
- Evaluation of vortex wake predictions in the SWINT code [AIAA PAPER 85-0450] p 224 A85-19759
- [AIAA PAPER 85-0450] p 224 A85-19759 WALL FLOW
- Structure of the wall pressure fluctuations in a shock-induced separated turbulent flow [AIAA PAPER 85-0179] p 214 A85-19571
- [AIAA PAPER 85-0179] p 214 A85-19571 WALL PRESSURE
- Experimental investigation of blockage effect of upper wall of wind-tunnel of wake of two-dimensional flat plate normal to plane boundary p 272 A85-19403 Surface pressure fluctuations in a three-dimensional
- shock wave/turbulent boundary layer interaction [AIAA PAPER 85-0125] p 211 A85-19536
- Structure of the wall pressure fluctuations in a shock-induced separated turbulent flow
- [AIAA PAPER 85-0179] p 214 A85-19571

WALL TEMPERATURE

- High temperature thermocouple and heat flux gauge using a unique thin film-hardware hot juncture [NASA-TM-86898] p 295 N85-16096
- WARNING SYSTEMS The Cockpit Display of Traffic Information and the Threat
- Alert and Collision Avoidance System Integration A review p 259 A85-21559 LPI-radar for helicopter obstacle warning
- p 297 N85-16810 WATER TEMPERATURE
- Variable-temperature water tunnel for high Reynolds
- [AIAA PAPER 85-0051] p 273 A85-19483 WATER TUNNEL TESTS
- Vortex research facility improvements and preliminary density stratification effects on vortex wakes [AIAA PAPER 85-0050] p 209 A85-19482
- [AIAA PAPER 85-0050] p 209 A85-19482 Variable-temperature water tunnel for high Reynolds numbers
- [AIAA PAPER 85-0051] p 273 A85-19483 WAVE DRAG
- Arrays for minimum wave drag of bodies of revolution [AIAA PAPER 85-0449] p 249 A85-19758
- An extremum problem concerning the shape of a body of revolution in supersonic gas flow p 234 A85-22371 An investigation of vortex-induced aerodynamic
- characteristics of supersonic cruise configurations [NASA-CR-174299] p 234 N85-15690
- WAVE INTERACTION
- Disturbance-wave interactions in flows with crossflow [AIAA PAPER 85-0494] p 226 A85-19788 WAVEFORMS
- Theoretical and experimental analyses of laser altimeters for barometric measurements over the ocean p 298 N85-17351

WEAPON SYSTEMS

[AD-A147923]

and versatiility

WEAPONS DELIVERY

[AIAA PAPER 85-0091]

WEATHER FORECASTING

[AIAA PAPER 85-0014]

[AIAA PAPER 85-0092]

Field, Antarctica

Aircraft barricade

[AIAA PAPER 85-0201]

Advances in composites technology

shallow shells with a honeycomb filler

displacement and frequency constraints

[ISBN-3-87977-055-7-PT-1]

[ISBN-3-87977-055-7-PT-2]

[AD-A1481081

[AD-D011316]

history effects

WEIGHT (MASS)

WEST GERMANY

2: Tables

Text

(NASA-TM-863531

WEIGHT REDUCTION

WEDGE FLOW

....

WEBS (SHEETS)

weapons

and science

warning

WEATHER

- Design and advanced concepts of avionics/weapons system integration; Proceedings of the Symposium, London, England, April 3, 4, 1984 p 200 A85-21456 Packaging and interconnection for avionics
 - p 290 A85-21460

p 308 N85-16685

p 302 N85-16746

p 203 N85-16752

p 277 N85-16816

p 246 A85-19274

p 240 A85-19513

p 298 A85-19458

p 299 A85-19514

p 300 N85-17492

p 277 N85-15761

p 268 A85-19585

p 233 A85-22308

p 284 N85-17048

p 287 A85-20452

p 290 A85-21985

p 279 N85-16887

p 279 N85-16888

The impact of integrated systems - The helicopter designer's viewpoint p 252 A85-21467 Estimating wartime support resource requirements.

Effective life cycle software support: A study in discipline

A weapon system design approach to diagnostics

A simulator for studying helicopter weapons systems

Bomb rack technology - Keeping up with advanced

Safety - Meteorological data vital for simulator training

Clear turbulence forecasting - Towards a union of art

Radar for storm forecasting and weather hazard

The visibility climatology of McMurdo Sound-Williams

Transient motion of hypersonic vehicles including time

Flow behind an attached shock wave in a radiating

Determination of the optimal parameters of aircraft

An optimality criterion method for structures with stress,

Activities report on West German civil airports. Part 1:

Activities report for the West German Civil Airports. Part

structural elements in the form of sandwich plates and

Statistical and related policy issues

WETTING		
The aerodynamic effect of	surfa	ce wetting
characteristics on a laminar flow airfo	il in sim	ulated heavy
rain		
[AIAA PAPER 85-0260]	p 247	A85-19619
WIENER HOPF EQUATIONS		
Random equations in aerodynamic	s	
[NASA-CR-174279]	p 238	N85-16825
WIND EFFECTS		
Nonlinear simulation of flight along) wind c	ompensating
curved glidepaths	p 245	A85-21838
WIND MEASUREMENT		
Identification of vortex-induced clea	r air turb	ulence using
airline flight records	p 299	A85-21843
WIND PROFILES		
Aerodynamics of an aspect ratio 8	wing at l	ow Reynolds
[AIAA PAPER 85-0278]	p 217	A85-19630
WIND SHEAR		
, wind shear I aming the killer	p 241	A85-20148
WIND TUNNEL APPARATUS		
A sensor for detection of unstead	fy distor	tion maxima
IN AIT INTAKES	- 005	AOE 10000
[UNCHA, IP NU. 1984-148]	p 205	A85-19202
Analytical and physical modeling p	rogram i	of the NASA
(NASA-TM-86010)	WIND 1	UNDE (AVV)
The NACA Altitude Mind Turnel	P 2/0	No5-15/5/
advanced icino research and develo	(AVVI):	its fole if
INASA-TM-860201	n 276	N85-15758
WIND THINNEL CALIPRATION	p 210	100-10/00
Tests in the transpric regime of	ia mod	el motorizer
by a blowing turbine 23 cm in diame	ter (9 in	ches) in the
S1MA wind tunnel		
[ONERA, TP NO. 1984-158]	p 272	A85-19272
Langley Mach 4 scramiet test facil	litv	
[NASA-TM-86277]	p 278	N85-16883
WIND TUNNEL MODELS	•	
The accuracy of trials with powere	ed 1/2 n	nodels in the
S2MA wind tunnel		
[ONERA, TP NO. 1984-156]	p 272	A85-19270
Analytical and physical modeling p	rogram f	or the NASA
Lewis Research Center's Altitude	Wind T	unnel (AWT
[AIAA PAPER 85-0379]	p 275	A85-19709
Analysis of the flow field about a	T-45 u	sing PANAIF
[AD-A146811]	p 236	N85-15699
Experiences with the use of a side	e-strut m	odel suppor
system for high angles of attack in the	Trinsoni	k wind tunne

тмк [DFVLR-MITT-84-09] p 277 N85-15763

Joined wing transonic design and test validation AD-A148355) p 239 N85-16834 WIND TUNNEL TESTS

A sensor for detection of unsteady distortion maxima in air intakes

(ONERA, TP NO. 1984-148) p 205 A85-19262 Noise of an airfoil in a flow [ONERA, TP NO. 1984-155] p 303 A85-19269

The accuracy of trials with powered 1/2 models in the S2MA wind tunnel

p 272 A85-19270 [ONERA, TP NO. 1984-156] Tests of air inlets on civil aircraft [ONERA, TP NO. 1984-157] p 272 A85-19271

Tests, in the transonic regime, of a model motorized by a blowing turbine 23 cm in diameter (9 inches) in the S1MA wind tunnel

[ONERA, TP NO. 1984-158] p 272 A85-19272 Analysis of counter-rotating propeller performance

[AIAA PAPER 85-0005] p 262 A85-19453 Variable-temperature water tunnel for high Reynolds numbers

[AIAA PAPER 85-0051] p 273 A85-19483 Mach-10 high Reynolds number development in the NSWC hypervelocity facility

[AIAA PAPER 85-0054] p 273 A85-19486 Some thoughts on the range/tunnel transition controversy

[AIAA PAPER 85-0127] p 211 A85-19538 Structure of the wall pressure fluctuations in a shock-induced separated turbulent flow

[AIAA PAPER 85-0179] p 214 A85-19571

[Alcontrar Encourts] p 214 A85-195/1 Measurements of separating boundary layer and wake of an airfoil using laser Doppler velocimetry [AIAA PAPER 85-0181] p 214 A85-19572 Improvements in low Reynolds number testing in the NSWC burevelocide used baced be 0

NSWC hypervelocity wind tunnel No. 9 [AIAA PAPER 85-0226] p 274 A85-19602 Studies of condensation effects on airfoil testing in a

transonic cryogenic tunnel [AIAA PAPER 85-0229] p 274 A85-19603 effect of surface The aerodynamic wetting

characteristics on a laminar flow airfoil in simulated heavy rain . _ . _ .

85-19619

A comparison between theoretical and experimental flow fields of an airfoil with deflected spoiler

p 216 A85-19622 [AIAA PAPER 85-0269] The design and testing of several joined wing RPV's p 248 A85-19627 [AIAA PAPER 85-0275] Effects of covering configurations on ultralight wing

aerodynamics [AIAA PAPER 85-0277] p 217 A85-19629

Aerodynamics of an aspect ratio 8 wing at low Reynolds numbers [AIAA PAPER 85-0278] p 217 A85-19630

The distortion of a supersonic turbulent boundary layer by bulk compression and surface curvature

p 218 A85-19648 AIAA PAPER 85-02991 The Altitude Wind Tunnel (AWT) - A unique facility for propulsion system and adverse weather testing

p 275 Å85-19661 [AIAA PAPER 85-0314] Ground-effect analysis of a jet transport airplane

p 248 A85-19677 [AIAA PAPER 85-0307] AIAA PAPER 85-0307] p 248 A85-1 Correlation of airfoil icing relationships two-dimensional model and full scale rotorcraft icing test data

[AIAA PAPER 85-0337] p 240 A85-19680 Hypersonic characteristics of an advanced aerospace plane

[AIAA PAPER 85-0346] p 269 A85-19685

Afterbody drag reduction by vortex generators [AIAA PAPER 85-0354] p 220 A8 Recent advances in computational tr p 220 A85-19692 transonic aerodynamics [AIAA PAPER 85-0366] p 221 A85-19699

Is the free flight/wind tunnel equivalence concept valid for unsteady viscous flow?

p 222 A85-19708 [AIAA PAPER 85-0378] Benefits and costs of powered engine simulation at low speeds

[AIAA PAPER 85-0381] p 263 A85-19710 Detailed measurements of the flowfield in the vicinity of an airfoil with glaze ice

[AIAA PAPER 85-0409] p 222 A85-19730 Experimental study of forward-located jet-interaction nozzles

p 224 A85-19762 [AIAA PAPER 85-0454] Experimental methods for wind-tunnel flight-mechanics investigations using dynamically similar aircraft models ---German thesis p 249 A85-19836

Aeroelastic characteristics of the AH-64 bearingless tail p 250 A85-20142 The most spectacular equipment - ETW

p 276 A85-21422

Experimental results for Reynolds number effects on ailing vortices p 232 A85-21849 trailing vortices Analytical modeling of circuit aerodynamics in the new

NASA Lewis wind tunnel [NASA-TM-86912] p 234 N85-15688

Aileron effectiveness for a subsonic transport model with a high-aspect-ratio supercritical wing

[NASA-TM-85674] p 235 N85-15695 The UH-1H helicopter icing flight test program: An overview

[NASA-TM-86925] p 242 N85-15702 Installed nacelle drag-improvement tests of an M = 0.8 turboprop transport configuration

[NASA-TM-84302] p 255 N85-15716 Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT)

[NASA-TM-86919] p 276 N85-15757 The NASA Altitude Wind Tunnel (AWT): Its role in

advanced icing research and development p 276 N85-15758 [NASA-TM-869201

Stereo Electro-optical Tracking System (SETS) [NASA-CR-172471] p 295 N85-16098 Investigations into the effects of scale and

compressibility on lift and drag in the RAE 5m pressurized p 236 N85-16773 low-speed wind tunnel Results of S5 CH tests with an ARL (Aerospace

Research Laboratory) cascade p 278 N85-16882 [NASA-TM-77510]

WIND TUNNEL WALLS Theoretical study of blockage effect of wind-tunnel wall on wake of two-dimensional flat plate normal to plane wali p 272 A85-19402 Experimental investigation of blockage effect of upper

wall of wind-tunnel of wake of two-dimensional flat plate p 272 A85-19403 normal to plane boundary Some thoughts on the range/tunnel transition controvers

p 211 A85-19538 [AIAA PAPER 85-0127] The use of panel methods for the development of low-subsonic wall interference and blockage corrections [AIAA PAPER 85-0159] p 212 A85-19556

Generalized adaptive-wall wind tunnels p 274 A85-19601 (AIAA PAPER 85-0225)

WIND TUNNELS

Analytical and physical modeling program for the NASA ewis Research Center's Altitude Wind Tunnel (AWT) (AIAA PAPER 85-03791 o 275 A85-19709 Ultrasound instrumentation for the 7 inch Mach seven tunnel

[NASA-CR-174277] p 305 N85-16586 WIND VELOCITY MEASUREMENT

Recent methods for calibrating the anemometry of helicopters at low speeds p 260 N85-16809 WING CAMBER

The influence of camber variation on the aerodynamics of civil transport aircraft

[AIAA PAPER 85-0353] p 220 A85-19691 WING FLAPS

Recent progress of development and understanding of p 236 N85-16772 high lift systems WING FLOW METHOD TESTS

Three-dimensional effects on a pitching lifting surface [AIAA PAPER 85-0041] p 208 A85-19476 p 208 A85-19476 Vortex research facility improvements and preliminary

density stratification effects on vortex wakes [AIAA PAPER 85-0050] p 209 A85-19482

Free surface scars and striations due to trailing vortices generated by a submerged lifting surface p 286 A85-19754 AIAA PAPER 85-04451

Visualization of the spanwise vortex structure in the starting flow behind an airfoil

p 224 A85-19756 [AIAA PAPER 85-0447] Flight testing of a wing section with laminar flow

control p 233 A85-22227 WING LOADING

Optimization of airplane wing structures under landing p 252 A85-22005 loads Structural load measurements on a Northrop NF-5A

p 253 N85-15667 Downwash in the plane of symmetry of an elliptically

loaded wing p 235 N85-15693 [NASA-TP-2414] WING NACELLE CONFIGURATIONS

The accuracy of trials with powered 1/2 models in the S2MA wind tunnel

[ONERA, TP NO. 1984-156] p 272 A85-19270 Installed nacelle drag-improvement tests of an M = 0.8

turboprop transport configuration p 255 N85-15716 [NASA-TM-843021 WING OSCILLATIONS

Numerical study on the dynamic stall process of a NACA 0012 airfoil

[AIAA PAPER 85-0128] p 212 A85-19539 Interrelated effects of pitch rate and pivot point on airfoil dynamic stall

[AIAA PAPER 85-0130] p 212 A85-19541 Three-dimensionality in unsteady flow about a wing

[AIAA PAPER 85-0132] p 212 Subsonic wing rock of slender delta wings p 212 A85-19543

[AIAA PAPER 85-0198] p 214 A85-19582 Theory of wing rock

[AIAA PAPER 85-0199] p 268 A85-19583 Harmonic oscillations of a rectangular wing with a

p 231 A85-21656 circulation variable over the span Vibration tailoring of advanced composite lifting p 290 A85-21846 surfaces

Calculation of the hydrodynamic characteristics of polyplanes p 290 A85-22113

WING PANELS

A summary of NASA's research on the fluid ice protection system

[AIAA PAPER 85-0467] p 241 A85-19768 WING PLANFORMS

The joined wing - An overview --- aircraft tandem wings in diamond configurations

[AIAA PAPER 85-02741 p 247 A85-19626 An attached flow design of a noninterfering leading edge

extension to a thick delta wing [AIAA PAPER 85-0350] p 220 A85-19689

WING PROFILES Measurements of water film characteristics on airfol

surfaces from wind-tunnel tests with simulated heavy rain

p 274 A85-19618 [AJAA PAPER 85-0259] Effects of covering configurations on ultralight wing

aerodynamics p 217 A85-19629 AIAA PAPER 85-02771 Body flow field simulation and force/moment prediction

at transonic speeds [AIAA PAPER 85-0423] p 222 A85-19738

Numerical optimization design of advanced transonic wing configurations

p 248 A85-19739 [AIAA PAPER 85-0424] Computational aerodynamic design of the Gulfstream

wing [AIAA PAPER 85-0427] p 223 A85-19742 Split-flux-vector solutions of the Euler equations for

three-dimensional configurations [AIAA PAPER 85-0434] p 223 A85-19747

Extremum problem concerning a wing with a maximum gradient of lift force p 234 A85-22370 -Integrated technology- wing study (oral presentation) [NASA-CR-169497] p 256 N85-15718

WING SPAN Integrated technology wing study (oral presentation)

[NASA-CR-169497] WING TIP VORTICES p 256 N85-15718

Interaction of a turbulent vortex with a lifting surface [AIAA PAPER 85-0004] p 206 A85-19452 Numerical study on the dynamic stall process of a NACA 0012 airfoil

[AIAA PAPER 85-0128] p 212 A85-19539 Circulation around thick wings with free vortices ----Serman thesis p 227 A85-19848 German thesis WING TIPS

Analysis of counter-rotating propeller performance p 262 A85-19453 [AIAA PAPER 85-0005] Integrated technology wing study (oral presentation) [NASA-CR-169497] p 256 N85-15718 p 256 N85-15718 WINGED VEHICLES

Crossflow drag of finite-length rectangular wing-bodies [AIAA PAPER 85-0451] p 224 A85-19760 WINGLETS

Study of winglets applied to biplanes [AIAA PAPER 85-0279] p 217 A85-19631 [NASA-TM-86350] p Study of winglets applied to biplanes [NASA-TM-86350] p

p 258 .N85-16862 WINGS

Icing tunnel tests of Electro-Impulse De-Icing of an engine inlet and high-speed wings [AIAA PAPER 85-0466]

p 241 A85-20872 Recent progress of development and understanding of high lift systems p 236 N85-16772

Design of an airfoil leading edge stat using an inverse aerodynamic calculation method p 256 N85-16777

Aerodynamic issues in the design of high-fits systems or transport aircraft p 256 N85-16780 An update of the Canada/USA augmentor-wing for transport aircraft

project p 257 N85-16781 Aerodynamic-structural study of canard wing, dual wing, and conventional wing systems for general aviation

applications [NASA-CR-172529] p 238 N85-16829

A-40

PERSONAL AUTHOR INDEX

ANDRACCHIO, C. A.

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Supplement 187)

MAY 1985

.

Typical Personal Author Index Listina



Listings in this index are arranged alphabetically by personal author. The title of the document provides the user with a brief description of the subject matter. The report number helps to indicate the type of document listed (e.g., NASA report, translation, NASA contractor report). The page and accession numbers are located beneath and to the right of the title. Under any one author's name the accession numbers are arranged in sequence with the AIAA accession numbers appearing first.

Α

- ABBOT, K. H.
- Reference energy-altitude descent guidance: Simulator evaluation
- [NASA-TP-2383] p 261 N85-16868 ABBOTT, J. M.
- Analytical and physical modeling program for the NASA ewis Research Center's Altitude Wind Tunnel (AWT) p 275 A85-19709 [AIAA PAPER 85-0379]
- Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) p 276 N85-15757 [NASA-TM-86919] ABBOTT, T. S.
- A cockpit-display concept for executing a multiple glide-slope approach for wake-vortex avoidance [NASA-TP-2386] p 261 N85-16869
- ABBOTT, W. Y. UH-60A external stores support system fixed provision
- fairings drag determination p 256 N85-15719 [AD-A147188] ABRAMOWITZ A
- Preliminary evaluation of an improved flammability test method for aircraft materials
- [FAA-CT-84-22] p 242 N85-16840 ABTAHI, A. A.
- Aerodynamics of an aspect ratio 8 wing at low Reynolds number
- [AIAA PAPER 85-0278] p 217 A85-19630 ACHTNICH, H.
- National report The Federal Republic of Germany p 308 A85-21949
- ADAM, E. C.
- Display Techniques for Advanced Crew Stations (DTACS). Phase 1: Display techniques study (AD-A146922) p 259 N85-15722

ADAMCZYK, J. J.

- Computational thermo-fluid dynamics contributions to advanced gas turbine engine design [AIAA PAPER 85-0083] p 262 A85-19509
- ADAMS, J. V.
- Speed benefits of tilt-rotor designs for LHX [NASA-CR-166437] p 255 N85-15717

- ADAMSON, T. C., JR.
- Shock waves in transonic channel flows at moderate Reynolds number [AIAA PAPER 85-0369] p 221 A85-19702 ADDY, A. L
- A study of compressible turbulent free shear lavers using laser Doppler velocimetry p 213 A85-19569
- [AIAA PAPER 85-0177] ADIASOR, M. I.
- Evaluation of vortex wake predictions in the SWINT code
- p 224 A85-19759 [AIAA PAPER 85-0450] ADLER, J. N.
- Three-dimensionality in unsteady flow about a wing [AIAA PAPER 85-0132] p 212 A85-19543
- Tail behaviour for suprema of empirical processes
- ADLER, R. S. Airworthiness and flight characteristics test of the
- p 258 N85-16864 [AD-A148046]
- AGARWAL, R. K.
- Aerodynamics of an airfoil in ground effect with a jet issuing from its undersurface p 207 A85-19461
- [AIAA PAPER 85-0019] AHMADI, A. R.
- An experimental investigation of blade-vortex interaction at normal incidenc [AIAA PAPER 85-00031 p 206 A85-19451
- AIKEN, E. W. A review of US Army aircrew-aircraft integration research
- programs p 270 N85-16814 AKAY, H. U.
- Finite element solutions of Euler equations for lifting airfoils
- [AIAA PAPER 85-0294] p 230 A85-20864 ALBERSHEIM, S. R. Helicopter noise survey performed at Las Vegas.
- Nevada, 19-21 January, 1984 AD-A1473921 p 305 N85-16593
- ALBRIGHT, A. E. A summary of NASA's research on the fluid ice protection
- system [AIAA PAPER 85-0467] p 241 A85-19768 ALEKSANDROV, A. IA.
- Determination of the optimal parameters of aircraft structural elements in the form of sandwich plates and shallow shells with a honeycomb filler p 287 A85-20452
- ALLEN, R. J. NASA three-laser airborne differential absorption lidar
- system electronics [NASA-CR-174293] p 298 N85-17353
- ANDERS, J. B. Turbulent drag reduction research p 237 N85-16788
- ANDERSON, G. Y.
- Langley Mach 4 scramjet test facility [NASA-TM-86277] p 278 N85-16883
- ANDERSON, J. D., JR. Flows over low Reynolds number airfoils - Compressible Navier-Stokes numerical solutions
- p 210 A85-19523 [AIAA PAPER 85-0107] A study of the effects of numerical dissipation on the
- calculation of supersonic separated flows [AIAA PAPER 85-0301] p 219 A85-19650
- ANDERSON, R. C. Integrated exhaust gas analysis system for aircraft turbine engine component testing
- p 295 N85-16100 [NASA-TP-2424] ANDERSON, W. K.
- A comparison of finite volume flux vector splittings for the Euler equations [AIAA PAPER 85-0122] p 211 A85-19533
- ANDERSSON, K. NyKINM, a further development of KINM 22
- p 256 N85-15720 [FOA-C-20559-D8(E3)] ANDO. S.
- Comparative study of various quadratures for subsonic p 205 A85-19404 lifting surface chordwise integrals

righ temperature memocouple and near hux gauge
using a unique thin film-hardware hot juncture
[NASA-TM-86898] p 295 N85-16096
ANDREWS, D. M.
Writing executable assertions to test flight software
[SU-CBC-TB-84-14] 0 301 A85-21973
Langley Mach 4 scramjet test facility
[NASA-TM-86277] p 278 N85-16883
ANDRISANI, D., II
Maximum final energy chandelle
[AIAA PADER 95.0200] D 247 A95.19594
ANTUSHKINA, G. I.
Development of asymptotic algorithms in the Polet
package of applications programs p 233 A85-22366
AOKI, K.
Flow visualization of lateral let injection into swirling
eropeflow
[AIAA PAPEH 85-0059] p 209 A85-19490
APPLEGATE, C. A.
Circulation control: A bibliography of DTNSRDC
research and selected outside references. Undate
[AD A146966]
[AD-A140900] p 201 N05-15001
ARCHBOLD, T.
Metallurgical and mechanical phenomena due to rubbing
of titanium against sintered powder Nichrome
n 291 A85-22281
APDEMA M D
Missions and unkiels apprends for modern averalled
missions and venicle concepts for modern, propelled,
lighter-than-air vehicles
[NASA-TM-86672] p 203 N85-16757
ARNAL D.
Application of two and three-dimensional criteria for
estaulating transitions and hourdany layors aver averal
calculating transitions and boundary layers over swep
wings p 237 N85-16783
ARPACI, V. S.
Radiative entropy production
[AIAA PAPER 85-0408] 0 304 A85-19729
Extremum problem concerning a wing with a maximum
gradient of lift force p 234 A85-22370
ASAMI, K.
Comparative study of various guadratures for subsonio
lifting surface obordwise integrals p 205 A95-1940/
ACUMENAD LI
ASHKENAS, I. L.
Mission-oriented requirements for updating MIL-H-8501
Volume 1: STI proposed structure
[NASA-CR-177304-VOL-1] p 271 N85-1687
ASHLEY. J. L.
Honor bastics and anormy economistion manual
Hangar heating and energy conservation manual
[AD-A147893] p 277 N85-15762
ASO, S.
Drag of the fundamental shapes of parachutes
p 231 A85-2099
ATHANS M
Bososch en entimal central stabilization and
nesearch on optimal control, stabilization and
computational algorithms for aerospace applications
[NASA-CR-174318] p 303 N85-1760
ATHERTON, W. J.
Investigation on experimental techniques to detect
locate and quantify occur noise in holicente
transmission
uansinissions
[NASA-CR-3847] p 305 N85-1766
ATKINSON, R.
Atmospheric photochemical modeling of turbine engine
fuels Phase 1: Experimental studies Volume 2
Environmental chamber data tabulations

- [AD-A147786] p 300 N85-17470 AVILA. J. A.
- Flexible matrix composites applied to bearingless rotor systems p 281 Å85-21389

В

- BACH. R. E.
- Identification of vortex-induced clear air turbulence using airline flight records p 299 A85-21843 BACHMAN, K. L.
- Standard Attitude Heading Reference System (SAHRS) p 246 N85-16804 full scale development program

- ADLER, R. J.
- p 303 N85-17613 [AD-A147629]
- RC-12D Guardrail V

- BACK. L. H.
- Measurements of the response of transport aircraft ceiling panels to fuel pool fires
- p 240 A85-19720 TAIAA PAPER 85-03941 BAIDIN, A. I.
- Design of a STOL aircraft with jet assisted takeoff p 253 A85-22373 BAILEY, A. R.
- Systems study for an Integrated Digital-Electric Aircraft (IDEA)
- INASA-CR-38401 p 255 N85-15714 BAILEY, F. R.
- A large-scale computer facility for computational p 301 A85-21791 aerodynamics BAILEY. R.
- United States Air force aircraft modification process: A system dynamics analysis p 200 N85-15659 [AD-A146954]
- BÅKER. T. J.
- Three-dimensional Euler solutions with grid embedding p 211 A85-19532 [AIAA PAPER 85-0121] BALAKRISHNAN, A
- Real-gas flowfields about three-dimensional configurations p 231 A85-21830 BALBERDE, A.
- Speed benefits of tilt-rotor designs for LHX [NASA-CR-166437] p 255 N85-15717 BALKE, H.
- Evaluation of operational loads to verify structural p 254 N85-15677 sian BALLHAUS, W. F., JR.
- A large-scale computer facility for computational p 301 A85-21791 orodynamics
- BANDYOPADHYAY, P. The universal nature of zero-crossing time and velocity p 232 A85-21851 in turbulent shear flows
- BANEBJEE D. Aeroelastic characteristics of the AH-64 bearingless tail
- p 250 A85-20142 BANK. W Visualization of the spanwise vortex structure in the
- starting flow behind an airfoil [AIAA PAPER 85-0447] p 224 A85-19756
- BANKSTON, C. P. Measurements of the response of transport aircraft
- ceiling panels to fuel pool fires [AIAA PAPER 85-0394] p 240 A85-19720
- BARANES, L.
- Keeping up with operational loads in the French Air Force: Defining new equipment p 292 N85-15681 BARBER, T. J.
- Three-dimensional inviscid flow analysis of turbofan forced mixers p 210 A85-19510 [AIAA PAPER 85-0086]
- BARLOW. A. Hardware design techniques p 244 A85-21459
- BARNETT, M. A procedure for the calculation of supersonic flows with
- strong viscous-inviscid interaction [AIAA PAPER 85-0166] p 213 A85-19562 BARON, J. R.
- Grid adaptation for the 2-D Euler equations [AIAA PAPER 85-0484] p 225 A85-19781
- BARSOTTI, M. F. The aerodynamic effect of surface wetting characteristics on a laminar flow airfoil in simulated heavy rain
- [AIAA PAPER 85-0260] p 247 A85-19619 BARTH, R. L.
- Temperature distortion generator for turboshaft engine testing [NASA-TM-83748] p 200 N85-15658
- BARTH. T. J. Navier-Stokes computations for exotic airfoils
- [AIAA PAPER 85-0109] p 230 A85-20855 BARTON, J. T. Euler computations of AGARD Working Group 07 airfoil
- test cases [AIAA PAPER 85-0018] p 229 A85-20851
- BATHIAS, C. Interpretation of fatigue crack growth in aluminium alloys
- under programmed block loading p 281 A85-20790 BATTAGLIA, M.
- A weapon system design approach to diagnosti p 203 N85-16752 BAUMGARDNER, D.
- Evaluation of the forward scattering spectrometer probe p 291 A85-22168 Electronic and optical studies BAYER, K.
- Analysis of fatal accidents involving light aircraft weighing up to two tons and their causes in the context p 241 A85-19846 of flight medicine BEATTIE, J. A. C.
- On-board processing for linescan sensors in miniature unmanned aircraft
- [RAE-TM-SPACE-327] p 261 N85-16870
- B-2

- BEATTIE, K. R.
 - Noise measurement flight test: Data-analyses erospatiale AS-355F TwinStar helicopter p 305 N85-16595 AD-A1474971
 - Noise measurement flight test for Boeing Vertol 234/CH 47-d helicopter: Data/analyses
 - p 306 N85-17670 [AD-A148172] Noise measurement flight test: Data-analyses Aerospatiale AS 350D AStar helicopter
 - [AD-A148496] p 306 N85-17672 Noise measurement flight test: Data-analyses, Sikorsky S-76A helicopter
 - [AD-A148525] p 306 N85-17673 BEAUCHAMP. P. P.
 - Shock-free turbomachinery blade design p 232 A85-21864
 - BECKER, F. Application of digital interferogram evaluation techniques to the measurement of three-dimensional flow
 - p 288 A85-20852 TAIAA PAPER 85-00371
 - BECLE, J. P. Tests, in the transonic regime, of a model motorized by a blowing turbine 23 cm in diameter (9 inches) in the S1MA wind tunnel
- [ONERA, TP NO. 1984-158] p 272 A85-19272 BEHM W.R.H.
- Built-in-test for first line testing p 202 N85-16739 BELIAEV, A. K.
- Theory of vibration conduction as a method for calculating the vibration of complex structures p 287 A85-20454
- BELIAKOV. I. T. Training and research CAD system of the Moscow Aviation Institute and experience in its use
- p 199 A85-20455 BELLOMY, D. C.
- A universal turboshaft engine test cell Design considerations and model test results [AIAA PAPER 85-0382] p 275 A85-19711
- BELOTSERKOVSKII, S. M. Computers and progress in aviation
- p 199 A85-20453 BENNETT, A.
- Rolls-Royce experience with thermal barrier coatings [PNR-90222] p 285 N85-17152 BENNETT, R. M.
- An exploratory study of finite difference grids for transonic unsteady aerodynamics
- [NASA-TM-84583] p 235 N85-15696 BEREZIN, V.
- International projects, other work of Aeroproyekt p 204 N85-16767 Institute BERGMANN, P.
- The hydraulic and electrohydraulic elements used in p 287 A85-19886 flight simulators BERMAN, H. A.
- A Navier-Stokes investigation of a circulation control airfoil
- [AIAA PAPER 85-0300] p 219 A85-19649 BERTELRUD, A
- Experimental and theoretical analysis of laminar separation bubbles
- p 288 A85-20874 [AIAA PAPER 84-2201] Full scale experiments into the use of large eddy breakup devices for drag reduction on aircraft
- p 257 N85-16790 BEYER, R.
- Flight research on visusl aids and navigation equipment for helicopter low-level flight at night
- p 261 N85-16820 BEYERS, M. E.
- Characteristic motions for simulation of post-stall manoeuvres and flight instabilities p 269 A85-21679 BHARTIYA, V.
- National airspace review: Airport radar service area operational confirmation report
- [DOT/FAA/AT-84/2] p 245 NB5-15707 BHARUCHA-REID. A. T.
- Random equations in aerodynamics [NASA-CR-174279] p 238 N85-16825 BHATTACHARYYA, R.
- A theoretical study of stability of a rigid rotor under the influence of dilute viscoelastic lubricants
- [ASME PAPER 84-TRIB-17] p 289 A85-21278 BIAGOSCH, A.
- procedure for the Α optimization of the aerothermodynamic design of multistage avial compressors p 227 A85-19851 **BIESIADNY, T. J.**
- Temperature distortion generator for turboshaft engine testing
- [NASA-TM-83748] p 200 N85-15658 BIEZAD, D. J.
- Time series analysis of closed-loop pilot vehicle p 271 N85-16876 dynamics

BIGELOW, J. H.

BLOM, J. J. H.

rear part

BODAPATI, S.

BOEHM, H. D. V.

BOEHM, M.

BOEHRET, H

vstem

BOHON, H. L.

BONNER, E.

BOPPE, C. W.

BORISIUK, M. N.

BOWCUTT, K. G.

BOWERS, A. H.

IV wing

BOLDMAN, D. R.

[NASA-TM-86914]

[AIAA PAPER 85-0427]

[AIAA PAPER 85-0159]

[AIAA PAPER 85-0307]

[NASA-TM-85920]

package of applications programs

[AD-A148355]

combat helicopters

[BMFT-FB-W-84-038]

[AIAA PAPER 85-0125]

[AIAA PAPER 85-0179]

for commercial transports

in a transonic oscillating cascade

BOERMANS, L. M. M.

BOGDONOFF, S. M.

- Managing recoverable aircraft components in the PPB and related processes: Executive summary [AD-A146806] p 308 N85-16667
- BILANIN, A. J. Scaling laws for testing of high lift airfoils under heavy rainfall
- [AIAA PAPER 85-0257] p 216 A85-19617 BION, J. R.
- A sensor for detection of unsteady distortion maxima in air intakes
- [ONERA, TP NO, 1984-148] p 205 A85-19262 BIRCKELBAW. L. D.
- Numerical computation of viscous flowfields about multiple component airfoils
- p 213 A85-19563 (AIAA PAPER 85-01671 BLAHA, B. J.
- The NASA Altitude Wind Tunnel (AWT): Its role in advanced icing research and development p 276 N85-15758 [NASA-TM-86920]
- BLANCHARD R.C.
- Determination of rarefied-flow aerodynamics of the Shuttle orbiter from flight measurements on STS-6 and STS-7
- [AIAA PAPER 85-0347] p 219 A85-19686 BLAND. T. L.
- Noise measurement flight test: Data-analyses aerospatiale AS-355F TwinStar helicopter [AD-A147497] p 305 N85-16595
- Noise measurement flight test for Boeing Vertol 234/CH 47-d helicopter: Data/analyses
- [AD-A148172] p 306 N85-17670 Noise measurement flight test: Data-analyses Aerospatiale AS 350D AStar helicopter
- [AD-A148496] p 306 N85-17672 Noise measurement flight test: Data-analyses, Sikorsky
- S-76A helicopter [AD-A148525] p 306 N85-17673

Design studies of thick laminar flow airfoils for low speed

A comparison between theoretical and experimental flow

Evaluation of nose, roof, and mast mounted sensor

platforms for piloting and sighting, integrated in future

Flight test of the Open Loop Gust Alleviation (OLGA)

Pneumatic turbulators: A device for drag reduction at

Surface pressure fluctuations in a three-dimensional

Structure of the wall pressure fluctuations in a

Ground test experience with large composite structures

Unsteady pressure measurements on a biconvex airfoil

Computational aerodynamic design of the Gulfstream

Development of asymptotic algorithms in the Polet

The use of panel methods for the development of low-subsonic wall interference and blockage corrections

Ground-effect analysis of a jet transport airplane

Ground-effect analysis of a jet transport airplane

Joined wing transonic design and test validation

Reynolds numbers below 5 million p 257

shock-induced separated turbulent flow

shock wave/turbulent boundary layer interaction

Maintainability: An ILS effort to manipulate LCC

fields of an airfoil with deflected spoiler

[AIAA PAPER 85-0269]

p 257 N85-16786

p 216 A85-19622

p 260 N85-16808

p 202 N85-16743

p 271 N85-16881

p 211 A85-19536

p 214 A85-19571

p 251 A85-21383

p 234 N85-15689

p 239 N85-16834

p 223 A85-19742

p 233 A85-22366

p 212 A85-19556

p 248 A85-19677

p 234 N85-15687

N85-16791

flight employing turbulent boundary layer suction over the

PERSONAL AUTHOR INDEX

BOWES, M. A.

K747 composite main rotor blade modification, analysis and qualification for new high temperature requirements p 251 A85-21378

BOXWELL, D. A.

Helicopter model rotor-blade vortex interaction impulsive oise: Scalability and parametric variations [NASA-TM-86007] p 238 N85-16826

- BOYLE, D. Wind shear - Taming the killer p 241 A85-20148
- BOZZOLA, F. Study and realisation of a 3rd level maintenance center based on ATE systems utilization p 202 N85-16735
- BRADLEY, J. T. Automated visibility measurements for airports
- [AIAA PAPER 85-0191] p 274 A85-19577 BRADSHAW, P.
- Turbulence structure of a three dimensional impinging jet in a cross stream [AIAA PAPER 85-0044] p 208 A85-19478
- BRAGG, M. B. Detailed measurements of the flowfield in the vicinity
- of an airfoil with glaze ice [AIAA PAPER 85-0409] p 222 A85-19730 BREITMAN, D. S.
- Analysis of a split-flow inertial particle separator by finite p 231 A85-21845 elements BRETZ, P. E.
- Fatigue crack growth behavior of 7XXX aluminum alloys under simple variable amplitude loading
- p 280 A85-20759 BRIERLEY, W. E. Integrated communications - A designers view
- p 245 A85-21462 BRIGGS, M. M.
- Influence of propulsion/mission profile combinations upon generic missile penetration of a hypothetical defense
- [AIAA PAPER 85-0495] o 249 A85-19789 BRINKLEY, J. W. Impact tests of automatic lap belt configurations
- [AD-A148034] p 243 N85-16844 BROOKS, T. F.
- Scaling of airfoil self-noise using measured flow parame p 304 A85-21858 BROWN, H. E.
- Voice command weapons launching system [AD-D011378] p 293 N85-15940 BROWN, L. D.
- Tail behaviour for suprema of empirical processes [AD-A147629] p 303 N85-17613
- BRUBAKER, K. L. Impact of aircraft emissions on air quality in the vicinity Volume 4. Nitrogen dioxide and of airports. hydrocarbons
- [AD-A1482531 p 299 N85-17436 BRUECKNER, W.
- Development, production and testing of central control and display unit for helicopters p 261 N85-16871 [BMFT-FB-W-84-039]
- RRUTIAN M. A. Optimal control of flow of a viscous incompressible
- fluid p 290 A85-22105 BUCCI, R. J.
- Fatigue crack growth behavior of 7XXX aluminum alloys under simple variable amplitude loading p 280 A85-20759

BUCHHOLZ, H. Flight test of the Open Loop Gust Alleviation (OLGA)

- system [BMFT-FB-W-84-038] p 271 N85-16881
- BUCK. G. M. Determination of rarefied-flow aerodynamics of the Shuttle orbiter from flight measurements on STS-6 and STS-7
- [AIAA PAPER 85-0347] p 219 A85-19686 BUCKANIN, R. M. UH-60A external stores support system fixed provision
- fairings drag determination [AD-A147188] p 256 N85-15719
- BUFFUM, D. H.

Unsteady pressure measurements on a biconvex airfoil in a transonic oscillating cascade

- p 234 N85-15689 [NASA-TM-86914] BUGGELE, A. E.
- Unsteady pressure measurements on a biconvex airfoil in a transonic oscillating cascade
- [NASA-TM-86914] p 234 N85-15689 BULL, J. S.
- Development and flight test of a helicopter compact, portable, precision landing system concept
- p 261 N85-16821
- BULLOCH. C.
- Speech recognition making progress Direct voice input is a promising infant p 244 A85-19183

- BUNING, P. G.
 - Navier-Stokes computations for exotic airfoils [AIAA PAPER 85-0109] BUONTEMPO, V.
 - Equipment for preflight test of an Electronic Countermeasures (ECM) avionic system
 - p 293 N85-15949 BUPP, C. L.
 - Evaluation of arctic test of improved tritium radioluminescent lighting [AD-A148215] p 278 N85-16884
 - BURCHAM, F. W., JR.
 - Predicted performance benefits of an adaptive digital engine control system on an F-15 airplane [AIAA PAPER 85-0255] p 263 A85-19801
 - Predicted performance benefits of an adaptive digital engine control system of an F-15 airplane INASA-TM-859161 p 265 N85-15729
 - BURGSMUELLER, W. Benefits and costs of powered engine simulation at low
 - p 263 A85-19710 [AIAA PAPER 85-0381]
 - BURNS, B. R. A.
 - Forward sweep The pros and cons p 250 A85-20146 BURROWS, L. T.
 - Crashworthiness of helicopter composite structures p 251 A85-21386 BUSHNELL D. M.

 - Turbulent drag reduction research p 237 N85-16788 BUTTER, D. J.
 - Recent progress of development and understanding of high lift systems p 236 N85-16772 BUTTRILL, S. E., JR.
 - Analysis of middle distillate fuels by high resolution field ionization mass spectrometry [AD-A147724] p 285 N85-17153
 - BYARS, N. B. Big wind at Tullahoma p 275 A85-20122

С

- CAILLETAUD. G.
- Life prediction at high temperature under multiaxial Inading p 267 N85-15745 CALAPODAS, N. J.
- Environmental effects and durability evaluation of advanced composite fuselage structures p 251 A85-21388
- CALARESE, W.
- Afterbody drag reduction by vortex generators [AIAA PAPER 85-0354] p 220 A8 p 220 A85-19692
- Modes of shock-wave oscillations on spike-tipped p 232 A85-21855 bodies CAMPBELL, J. O.
- A description of a logistically ideal aircraft AD-A148425} p 258 N85-16866 CANSDALE, J. T.
- The development of mathematical modelling techniques for helicopter rotor icing
- [AIAA PAPER 85-0336] p 240 A85-19679 CAO, X.
- Experimental investigation of backswept centrifugal p 264 A85-20243 compressor impeller. I CARAVASOS. N.
- Advanced composites Designed to survive p 251 A85-21387
- CARLIN, J. D.
- A description of a logistically ideal aircraft [AD-A148425] p 258 p 258 N85-16866 CARTER, J. E.
- Viscous/inviscid interaction analysis of transonic shock induced separated flow including normal pressure aradients
- [AIAA PAPER 85-03711 p 221 A85-19703 CARTER, W. P. L
- Atmospheric photochemical modeling of turbine engine fuels. Phase 1: Experimental studies. Volume 2: Environmental chamber data tabulations [AD-A147786] p 300 N85-17470
- CASPAR, J. R. A linearized unsteady aerodynamic analysis for transonic
- cascades p 229 A85-20744 CAVALLERI, R. J.
- Experimental study of forward-located jet-interaction nozzles [AIAA PAPER 85-0454] p 224 A85-19762
- CEBECI. T.
- Some important problems in unsteady boundary layers including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies

p 294 N85-16069 [AD-A146964]

- Some important problems in unsteady boundary layers including separation. 1: Nature of singularity on oscillating airfoils [AD-A147897] p 294 N85-16087 CHABOCHE, J. L. Life prediction at high temperature under multiaxial ading p 267 N85-15745 CHADERJIAN, N. M. The numerical simulation of steady transonic rotational flow using a dual potential formulation p 221 A85-19701 [AIAA PAPER 85-0368] CHAMBERLIN, R. The Altitude Wind Tunnel (AWT) - A unique facility for propulsion system and adverse weather testing [AIAA PAPER 85-0314] o 275 A85-19661 CHANDLER, N. Packaging and interconnection for avionics p 290 A85-21460 CHANDLER, T. C. Flow measurement device [AD-D011432] p 298 N85-17369 CHANDRASEKHARAN, R. M. Computational aerodynamic design of the Gulfstream IV wing [AIAA PAPER 85-0427] p 223 A85-19742 CHANG. G. E. Polyimide protective coatings for 700 deg service p 282 A85-21527 CHANG, I.-C. Numerical solution of the full-potential equation for rotors and oblique wings using a new wake model [AIAA PAPER 85-0268] p 216 p 216 A85-19621 CHANG, S. Flutter control with unsteady aerodynamic models p 270 N85-15753 [AD-A147858] CHAPMAN, A. J., III Ground test experience with large composite structures for commercial transports p 251 A85-21383 CHEATWOOD, F. M. The design and testing of several joined wing RPV's [AIAA PAPER 85-0275] p 248 A85-19627 CHEKMAREV, S. F. Hypersonic multicycle gas jet with a strongly underexpanded stream at the nozzle section p 229 A85-20554 CHEN. C.-L. Trapping of free vortex by airfoils with surface suction [AIAA PAPER 85-0446] p 224 A85-19755 CHEN, F. L. Theoretical study on supersonic jet plumes p 206 A85-19439 CHEN H On the variety of type discrimination criteria of equations on S1 and S2 stream surfaces in turbomachine p 228 A85-20238 CHEN. J. Calculation and analysis of the three-dimensional flow in centrifugal compressor impellers p 228 A85-20231 Experimental investigation of backswept centrifugal compressor impeller. I p 264 A85-20243 CHEN X Effect of inlet and outlet flow conditions on the flow and performance of subsonic two-dimensional diffuse p 228 A85-20241 CHENG, V. H. L. Influence of propulsion/mission profile combinations upon generic missile penetration of a hypothetical
- dafaned [AIAA PAPER 85-0495] p 249 A85-19789
- CHIEN. L. C. Theoretical study on supersonic jet plumes
- p 206 A85-19439
- CHILDS, D. W. Analysis and testing for rotordynamic coefficients of turbulent annular with different. seals directionally-homogeneous surface-roughness treatment for rotor and stator elements
- [ASME PAPER 84-TRIB-31] p 289 A85-21293 CHISHOLM, J. P.
- Development and flight test of a helicopter compact, portable, precision landing system concept p 261 N85-16821
- CHOLLE, P.
- p 259 N85-16801 Map display for helicopters CHOU, D. C.
- Passive control effects on flow separation around a protuberance at high subsonic speed
- [AIAA PAPER 85-0351] p 220 A85-19690 CHOU, S. Y.
 - Development of the UTA High Reynolds Number Transonic Wind Tunnel p 275 A85-19662
- [AIAA PAPER 85-0315] CHOW, C .- Y.
- Trapping of free vortex by airfoils with surface suction [AIAA PAPER 85-0446] p 224 A85-19755

o 230 A85-20855

- Literature review of voice recognition and generation technology for Army helicopter applications [AD-A146878] p 293 p 293 N85-15954
- CHU, C.-W. A simple analytical method for predicting axisymmetric turbulent jet flowfields in a freestream
- p 216 A85-19614 [AIAA PAPER 85-0251]
- CIAPONI, A. J. Experimental study of forward-located jet-interaction nozzles
- p 224 A85-19762 [AIAA PAPER 85-0454] CLARK, R. W.
- A new iterative matrix solution procedure for three-dimensional panel methods p 213 A85-19568 [AIAA PAPER 85-0176]
- CLARKE, D. K.
- Euler calculations for multielement airfoils using Cartesian grids [AIAA PAPER 85-0291] p 218 A85-19641
- CLARY, G. R.
- Development and flight test of a helicopter compact, portable, precision landing system concept p 261 N85-16821
- CLAUS. R. W. Accelerated convergence for incompressible flow alculations
- (AIAA PAPER 85-0058) p 209 A85-19489 CLEMENT, W. F.
- Assessment of simulation fidelity using measurements p 278 N85-16817 of piloting technique in flight Mission-oriented requirements for updating MIL-H-8501. Volume 1: STI proposed structure
- p 271 N85-16877 [NASA-CB-177304-VOL-1] Mission-oriented requirements for updating MIL-H-8501. Volume 2: STI background and rationale p 271 N85-16878 [NASA-CR-177304-VOL-2]
- CLEVELAND, W. B. Assessment of simulation fidelity using measurements
- of piloting technique in flight p 278 N85-16817 CLUBINE, W. R.
- Development of a Helicopter integrated navigation p 245 N85-16802 evetom CLYDE, J. A.
- Joined wing transonic design and test validation p 239 N85-16834 [AD-A148355] COEN, P. G.
- Computer sizing of fighter aircraft [NASA-TM-86351] p 203 N85-16759
- COGGIOLA. M. J. Analysis of middle distillate fuels by high resolution field ionization mass spectrometry
- p 285 N85-17153 [AD-A147724] COHILL G. L.
- Integration of sensor fusion in advanced helicopte p 260 N85-16813 cockpit design COIRIER, W. J.
- Detailed measurements of the flowfield in the vicinity of an airfoil with glaze ice p 222 A85-19730 [AIAA PAPER 85-0409]
- COLEHOUR, J. L. Analysis of counter-rotating propeller performance
- p 262 A85-19453 [AIAA PAPER 85-00051 COMBET. M.
- A sensor for detection of unsteady distortion maxima in air intakes [ONERA, TP NO. 1984-148] p 205 A85-19262
- CÔMO, P. L Tactical HF communication for military helicopters using
- the NVIS mode p 297 N85-16807 COOPER J R
- GC-FTIR (Fourier Transform Infrared Spectrometry) of iet fuels [AD-A148272] p 285 N85-17155
- COOPER. L. Y.
- The thermal response of aircraft cabin ceiling materials during a post-crash, external fuel-spill, fire scenario p 241 A85-19721 [AIAA PAPER 85-03951
- COOPER. W. A. Icing conditions encountered by a research aircraft p 299 A85-21141
- COPELAND, G. D. NASA three-laser airborne differential absorption lidar
- system electronics p 298 N85-17353 [NASA-CR-174293] COPLIN. J. F.
- The aircraft engine of the future [PNR-90226] p 268 N85-16875 CORBETT, C. A.
- Real gas effects in advanced technology engines [AIAA PAPER 85-0252] p 262 A85-1 p 262 A85-19615
- CORNAND, J. P. Keeping up with operational loads in the French Air

B-4

Force: Defining new equipment p 292 N85-15681

- CORNELL, C. C.
- Experimental aerodynamic characteristics of an NACA 012 airfoil with simulated ice p 252 A85-21844 0012 COSENTINO, G. B.
- Numerical optimization design of advanced transonic wing configurations [AIAA PAPER 85-0424]
- p 248 A85-19739 COURTOIS M.
- Objectives in studying the maintainability of aircraft p 202 N85-16732 evetome COUSTOLS F
- Application of two and three-dimensional criteria for calculating transitions and boundary layers over swept p 237 N85-16783 winne COYLE. S.
- Operational requirements versus technological canabilities p 204 N85-16798 CRISLER, W. P.
- Afterbody drag reduction by vortex generators [AIAA PAPER 85-0354] p 220 A85-19692
- CRONIN, D. L. Aerodynamic-structural study of canard wing, dual wing, and conventional wing systems for general aviation
- applications [NASA-CR-172529] p 238 N85-16829
- CRONIN, M. J. Integrated digital/electric aircraft concepts study [NASA-CR-3841] p 257 N85-
- p 257 N85-16861 CRONKHITE, J. D.
- Crashworthiness of helicopter composite structures p 251 A85-21386 CROSS, E. J., JR.
- Experimental aerodynamic characteristics of an NACA 0012 airfoil with simulated ice p 252 A85-21844 CRUZ. C. I.
- Hypersonic characteristics of an advanced aerospace olane [AIAA PAPER 85-0346] p 269 A85-19685
- CULLYER, W. J. Software design methods p 301 A85-21457
- CULP. R. L. F-16 force management, yesterday, today and
- p 254 N85-15674 tomorrow CUMMINGS, R. J.
- Windblast leg protector assembly [AD-D011376] p 242 N85-15700 CURRY, R. E.
 - Ground-effect analysis of a jet transport airplane [AIAA PAPER 85-0307] p 248 A85-19677
- Ground-effect analysis of a jet tran sport airplane [NASA-TM-859201 p 234 N85 15687

D

- DABUNDO, C.
- A longitudinal stability augmentation system for a tilt rotor aircraft
- [AIAA PAPER 85-0072] p 268 A85-19498 DADONE, A.
- A quasi-conservative lambda formulation [AIAA PAPER 85-0088] p 210 A85-19511 DAHL H. J.
- Advanced flight simulation for helicopter development p 277 N85-16815
- DAMANIA, R. B. Flight testing of a wing section with laminar flow
- p 233 A85-22227 control 1 DANBERG, J. E.
- Navier-Stokes computations of axisymmetric transonic flows with a two-equation model of turbulence [AIAA PAPER 85-0373] p 221 A85-19705
- DANEEV. A. V. An extremum problem concerning the shape of a body
- of revolution in supersonic gas flow p 234 A85-22371 DANESI. A.
- Helicopter active control with rotor blades relaxation p 270 N85-16819
- Helicopter active control with rotor blades relaxation p 270 N85-16819
- DANNENHOFFER, J. F., III Grid adaptation for the 2-D Euler equations [AIAA PAPER 85-0484] p 225 A85-19781 DASARO, J. A.
- Evolution toward a multi-bus architecture for Army helicopter avionic systems p 260 N85-16812
- DAULERIO, L. A. A Generalized Escape System Simulation (GESS) computer program. Volume 2: GESS programmer's manual, version 2
- [AD-A148363] p 243 N85-16845 DAVE. M.
- Impact of aircraft emissions on air quality in the vicinity of airports. Volume 4. Nitrogen dioxide and hydrocarbons [AD-A148253] p 299 N85-17436

- DAVENPORT E J Analysis of counter-rotating propeller performance [AIAA PAPER 85-0005] p 262 A85-19453 DAVIES, G. A. O.
- Proceedings of the International Conference and Exposition on Structural Impact and Crashworthiness AD-A1478451 p 242 N85-15703
- DAVIS, R. T. A procedure for the calculation of supersonic flows with strong viscous-inviscid interaction
- [AIAA PAPER 85-0166] p 213 A85-19562 DAVIS. S. S.
- Generalized adaptive-wall wind tunnel p 274 A85-19601 TAIAA PAPER 85-02251
- DAVIS. T. J. Development and flight test of a helicopter compact. portable, precision landing system concept
- p 261 N85-16821 DAVIS, W. H.
 - Potential flow calculations and preliminary wing design in support of an NLF variable sweep transition flight [A]AA PAPER 85-04261 p 248 A85-19741
 - DAVIS, W. H., JR. TRO-2D A code for rational transonic aerodynamic optimization [AIAA PAPER 85-0425] p 223 A85-19740 DAVY. W. C. flowfields Real-oas three-dimensional about configurations p 231 A85-21830 DAVYDOV, P. S. p 244 A85-19805 Aviation radar DE JONCKHEERE, R. K. Passive control effects on flow separation around a protuberance at high subsonic speed AIAA PAPER 85-03511 n 220 A85-19690 DE MOS. G. Bomb rack technology - Keeping up with advanced p 246 A85-19274 weapons DEESE, J. E. Aerodynamics of an airfoil in ground effect with a jet issuing from its undersurface [AIAA PAPER 85-0019] p 207 A85-19461 Split-flux-vector solutions of the Euler equations for three-dimensional configurations [AIAA PAPER 85-0434] p 223 A85-19747 DEGAYE, R. Experience of one UK electronic equipment supplier with bite on engine/flight control systems over the past ten years p 296 N85-16738 DEGROOT, W. A. SFRJ simulator results - Experiment and analysis in cold flow [AIAA PAPER 85-0329] p 263 A85-19671 DEIDRICH, J. H. Analytical and physical modeling program for the NASA
 - Lewis Research Center's Altitude Wind Tunnel (AWT) [NASA-TM-86919] p 276 N85-15757 DEIWERT, G. S.
 - A three-dimensional adaptive grid method [AIAA PAPER 85-0486] p 225 A85-19783 DÈJARNETTE, F. R.
 - Application of axisymmetric analogue for calculating heating in three-dimensional flows
 - [AIAA PAPER 85-0245] p 216 A85-19611 Effects of aircraft and flight parameters on energy-efficient profile descents in time-based metered
 - traffi [NASA-CR-172338-ADD] n 245 N85-15706 DELAVIGNE, M.
 - Aeroelastic analysis and the identification of flight p 254 N85-15679 inads
 - DEMPSEY, B. J. Development of a preliminary ALRS stabilized material pavement analysis system (SPAS)
 - [AD-A147116] p 277 N85-15760 DENISOV, E. T.
 - Oxidation and stabilization of jet fuels p 281 A85-20925

Speed benefits of tilt-rotor designs for LHX

Full two-dimensional transient

Advances in composites technology

electrothermal aircraft blade deicing

A digital piloting system for the combat helicopter

p 243 N85-16847

p 255 N85-15717

p 260 N85-16806

of

solutions

p 248 A85-19734

p 284 N85-17048

DEPALMA, J. Utilization of Increased Airlift Capability (UIAC) study [AD-A148669]

[NASA-CR-166437]

[AIAA PAPER 85-0413]

[NASA-TM-86353]

DERESKA, S. P.

DERRIEN, J. C.

DEWITT, K. J.

DEXTER, H. B.

PERSONAL AUTHOR INDEX

DIACHENKO, A. A.

- Combat aircraft: Flight vehicles, power plants, and their maintenance p 199 A85-19812 DIAO, Z Experimental investigation of backswept centrifugal
- compressor impeller. I p 264 A85-20243 DIEDRICH, J. H.
- Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) [AIAA PAPER 85-0379] p 275 A85-19709 DIETRICH, D. A.
- Flowfield analysis of low bypass ratio test cells p 265 A85-21839

DIGIOVANNIANTONIC, P.

- Aircraft barricade [AD-D011316] p 277 N85-15761
- DILLARD, H. E. Display Techniques for Advanced Crew Stations (DTACS). Phase 1: Display techniques study
- p 259 N85-15722 [AD-A146922] DILLENIUS, M. F. E.
- cruciform all-movable control Prediction of characteristics at transonic speeds
- p 239 N85-16832 [AD-A147291] DILLNER, B. Aerodynamic issues in the design of high-lift systems
- for transport aircraft p 256 N85-16780 DILLON, J. L.
- Correlation and analysis of oil flow data for an air-breathing missile model [AIAA PAPER 85-0452]
- p 224 A85-19761 DIXON, S. C.
- Loads and Aeroelasticity Division research and technology accomplishments for FY 1984 and plans for FY 1985
- [NASA-TM-86356] p 234 N85-15691 DODD, M. C.
- Atmospheric photochemical modeling of turbine engine fuels. Phase 1: Experimental studies. Volume 2: Environmental chamber data tabulations p 300 N85-17470
- [AD-A147786] DOLLING, D. S. Flowfield scaling in sharp fin-induced shock wave/turbulent boundary-layer interaction
- p 232 A85-21857
- DONALDSON, J. C. Laminar boundary layer stability experiments on a cone
- at Mach 8. III Sharp cone at angle of attack [AIAA PAPER 85-0492] p 226 A85-19787
- DONNELLAN, T. M. Repair of composites p 284 N85-17058 DONNELLY, J. P.
- Advanced composites Designed to survive p 251 A85-21387
- DONZELLI, P.
- Reliable software design for avionics and space pplications p 303 N85-16751 applications DOVIAK, R. J.
- Radar for storm forecasting and weather hazard warning
- [AIAA PAPER 85-0092] p 299 A85-19514 DRAKE, C. W. Environmental test capabilities of the Air Force McKinley
- Climatic Laboratory [AIAA PAPER 85-0089] p 273 A85-19512
- DRESS, D. A. Description of the insulation system for the Langley
- 0.3-Meter Transonic Cryogenic Tunnel p 276 N85-15755 [NASA-TM-86274]
- DRESSEL, F. E. The effects of manufacturing automation on the surge
- and mobilization capabilities of the gas turbine engine industry [AD-A147295] p 297 N85-17162
- DRUMMOND, J. P.
- Spectral methods for modeling supersonic chemically reacting flow fields
- [AIAA PAPER 85-0302] p 219 A85-19651 DUBAS. M.
- On the excitations due to the periodic structure of turbomachines p 288 A85-20800 DUBBERLY, M. J.
- Navy operational loads data sources and systems p 253 N85-15668 DUECK, E. G.
- Analysis of a split-flow inertial particle separator by finite elements p 231 A85-21845 DUNCKER, L. L.
- Prediction of performance of aircraft gas turbines p 264 A85-21682
- DUSSAUGE, J.-P.
- Structure of the wall pressure fluctuations in a shock-induced separated turbulent flow [AIAA PAPER 85-0179] p 214 A85-19571

- DUTHEIL DE LA ROCHERE, J. Creation and extension of airports - Procedures and
 - p 307 A85-21945 oractico DVORAK F A Prediction of dynamic stall characteristics using
 - advanced non-linear panel methods o 239 N85-16836 [AD-A148453]
 - OVE I F
 - Evaluation of the forward scattering spectrometer probe. Electronic and optical studies p 291 A85-22168 DYER. R.
 - Supercritical airfoil drag reduction by passive shock wave/boundary layer control in the Mach number range .75 to .90
 - [AIAA PAPER 85-0207] p 215 A85-19591 DZHALALOVA, M. V.
 - Stress analysis and shaping of the canopy of a square p 242 A85-21668 parachute E

ECCLES, E. S.

- Trends in digital engine control Integration of propulsion control with flight control and avionic systems in future military and commercial aircraft p 264 A85-21466 ECER. Á. Finite element solutions of Euler equations for lifting
- airfoils [AIAA PAPER 85-0294] p 230 A85-20864
- EDMUNDS, T. M. Monitoring engine thermal stresses
- p 266 N85-15735 EDSTROM, N.
- Report from Sweden p 307 A85-21946 EDWARDS, D. E.
- Viscous/inviscid interaction analysis of transonic shock induced separated flow including normal pressure gradients AIAA PAPER 85-03711 p 221 A85-19703
- EDWARDS, T. A. Noniterative three-dimensional grid generation using
- parabolic partial differential equations [AIAA PAPER 85-0485] n 300 A85-19782
- ELLIOTT, D. G. Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems
- [NASA-CR-174271] p 242 N85-15701
- EMBRY, L. B. Estimating wartime support resource requirements. Statistical and related policy issues
- p 308 N85-16685 [AD-A147923] EMERY, A. F.
- Metallurgical and mechanical phenomena due to rubbing of titanium against sintered powder Nichrome p 291 A85-22281
- ENGLAR, R. J. Circulation control: A bibliography of DTNSRDC
- esearch and selected outside references: Update [AD-A146966] p 201 N85-15661 ENGSBERG, N. G.
- Development of a fatigue crack propagation model of p 280 A85-20758 Incolov 901
- EPSTEIN. A. H. Current problems in turbomachinery fluid dynamics [AD-A147127] p 294 N85-16074 ERICSSON, L. E.
- Some thoughts on the range/tunnel transition controversy
- [AIAA PAPER 85-0127] p 211 A85-19538 Regarding parametric investigations of slender cone nose hiuntness offects
- [AIAA PAPER 85-0349] p 220 A85-19688 is the free flight/wind tunnel equivalence concept valid for unsteady viscous flow?
- [AIAA PAPER 85-0378] p 222 A85-19708 Ground interference effects on subsonic dynamic stall p 231 A85-21841 in pitch and plunge
- ERZBERGER, H. Calculation of the exchange ratio for the Adaptive
- Maneuvering Logic program [AIAA PAPER 85-0311] p 199 A85-19658
- ESCH, H. Experiences with the use of a side-strut model support system for high angles of attack in the Trinsonik wind tunnel тмк
- [DEVLR-MITT-84-09] p 277 N85-15763 ETEMAD. S.
- Metallurgical and mechanical phenomena due to rubbing of titanium against sintered powder Nichrome p 291 A85-22281
- EVANS, W. J. Disc fatigue life predictions for gas turbine engines
- p 267 N85-15743 EVERITT, R. L.
 - Report from the United Kingdom p 307 A85-21943

F

FANG. D.

- Newton iteration formulas for correcting temperature and pressure in thermodynamic calculation of rocket engines p 279 A85-20226
- FANG 1 Effect of inlet and outlet flow conditions on the flow and performance of subsonic two-dimensional diffuser
- p 228 A85-20241 FARMER, T. E.
- View of future requirements for engine cyclic durability by analysis and testing p 267 N85-15751 p 267 N85-15751 FEDOROV, S. M.
- Investigation of semiautomatic aircraft control processes employing time redundancy in on-board digital trajectory control computers p 270 N85-16048
- FENDER D A A Generalized Escape System Simulation (GESS)
- computer program. Volume 2: GESS programmer manual, version 2 [AD-A148363] p 243 N85-16845
- FERGUSON, S. W., III
 - Mission-oriented requirements for updating MIL-H-8501. Volume 1: STI proposed structure
- [NASA-CR-177304-VOL-1] p 271 N85-16877 Mission-oriented requirements for updating MIL-H-8501. Volume 2: STI background and rationale
- [NASA-CR-177304-VOL-2] p 271 N85-16878 FERRELL G R
- Flow visualization of lateral jet injection into swirling crossflow
- p 209 A85-19490 FICARRA, R. V.
 - Supercritical airfoil drag reduction by passive shock wave/boundary layer control in the Mach number range 75 to .90

Investigations into the effects of scale and

Preliminary evaluation of an improved flammability test

Visualization of the spanwise vortex structure in the

Realization and testing of an experimental color display

Technology developments for laminar boundary layer

Investigation on experimental techniques to detect.

Three dimensional aerodynamics of an annular cascade

Correlation of airfoil icing relationships

two-dimensional model and full scale rotorcraft icing test

Impact of aircraft emissions on air quality in the vicinity

Vibration tailoring of advanced composite lifting

Linearized potential flow analysis of complex aircraft

configurations by HISSS, a higher order panel method (AIAA PAPER 85-0281) p 217 A85-19632

Results of S5 CH tests with an ARL (Aerospace

Subsonic pressure distributions near a wing-fin juncture

on a supersonic arrow-wing configuration with wing-mounted vertical fins

Volume 4. Nitrogen dioxide and

locate and quantify gear noise in helicopter

system for general aviation helicopters and aircraft [BMFT-FB-W-84-042] p 262 N85-

p 236 N85-16773

p 242 N85-16840

p 224 A85-19756

p 262 N85-16872

p 237 N85-16787

p 305 N85-17667

p 213 A85-19567

n 240 A85-19680

p 299 N85-17436

p 290 A85-21846

p 203 N85-16759

p 278 N85-16882

p 217 A85-19628

B-5

with

compressibility on lift and drag in the RAE 5m pressurized

[AIAA PAPER 85-0207] p 215 A85-19591 FIDDES, S. P.

low-speed wind tunnel

method for aircraft materials

starting flow behind an airfoil

control on subsonic transport aircraft

[AIAA PAPER 85-0447]

FILIPCZAK, R. A.

[FAA-CT-84-22]

FISCHER, H. W.

FISCHER. M. C.

FLANAGAN, P. M.

transmissions

FLEMMING, R. J.

FLOTARD. R. D.

of airports.

hydrocarbons

FOIST, B. L.

surfaces

FORNASIER 1

FOSS, W. E., JR.

FOURMAUX, A.

FOX, C. H., JR.

[NASA-TM-77510]

[AIAA PAPER 85-0276]

Computer sizing of fighter aircraft [NASA-TM-86351]

Research Laboratory) cascade

(AD-A148253)

FLEETER. S.

data

[NASA-CR-3847]

in a non-uniform inlet flow

AIAA PAPER 85-01741

[AIAA PAPER 85-0337]

FINAISH, F.

FOX, F. S.

FOX. F. S.

- Using the control system design environment in the design of a data link receiver unit for the Coast Guard HH-65A helicopter [AD-A148624] p 271 N85-16880
- FOYE. R. L. The all-composite airframes p 252 A85-21397
- FRANK, W. F. X. LPI-radar for helicopter obstacle warning
- p 297 N85-16810 FRANKE, M. E.
- Frequency response of a jet engine test facility air supply svstem [AIAA PAPER 85-0053] p 273 A85-19485
- FRENCH, E. Thermal design of rotatable cryogenic heat pipe joints
- p 279 A85-19495 [AIAA PAPER 85-0068] FRENCH. R. M. Effects of covering configurations on ultralight wing
- aerodynamics [AIAA PAPER 85-0277] p 217 A85-19629
- FRESCO, J. Design and test requirements for development of today's p 266 N85-15737 enaines
- FREULER, R. J. A universal turboshaft engine test cell - Design considerations and model test results p 275 A85-19711 [AIAA PAPER 85-0382]
- FREY. P. Development of a preliminary ALRS stabilized material
- pavement analysis system (SPAS) p 277 N85-15760 [AD-A147116] FREYMUTH, P.
- Visualization of the snanwise vortex structure in the starting flow behind an airfoil [AIAA PAPER 85-0447] p 224 A85-19756
- FRIEDMANN, P. P. Coupled helicopter rotor/body aeromechanical stability
- comparison of theoretical and experimental results p 252 A85-21847
- FRITZ. W. Theoretical contributions to transonic flow analysis for transport aircraft
- [BMFT-FB-W-84-036] p 239 N85-16838 FROLOV, G. A.
- Calculation of friction and heat transfer in turbulent flow of a compressible gas in a plane duct p 291 A85-22114
- FUHS. A. E. Radar cross section lectures p 289 A85-20915
- FULLER, C. R. An improved source model for aircraft interior noise studies
- [NASA-CR-172517] p 305 N85-17668 G

GABRA. M.

- Interpretation of fatigue crack growth in aluminium alloys p 281 A85-20790 under programmed block loading GAD-EL-HAK. M.
- Three-dimensional effects on a pitching lifting surface [AIAA PAPER 85-0041] p 208 A85-19476 GAEBE, H.
- sting of ACAP p 251 A85-21384 Structural analysis and testing subcomponents GALL, P. D.
- Study of winglets applied to biplanes p 217 A85-19631 [AIAA PAPER 85-0279] Study of winglets applied to biplanes
- [NASA-TM-86350] p 258 N85-16862 GARCIA, P. Noise of an airfoil in a flow
- [ONERA, TP NO. 1984-155] p 303 A85-19269
- GARDNER, J. Analysis of the flow field about a T-45 using PANAIR [AD-A146811] p 236 N85-15699
- GARDNER, J. E. Loads and Aeroelasticity Division research and technology accomplishments for FY 1984 and plans for FY 1985
- [NASA-TM-86356] p 234 N85-15691 GARRISON, P. W.
- Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems [NASA-CR-174271] p 242 N85-15701
- GAUL, V. F. The effects of manufacturing automation on the surge
- and mobilization capabilities of the gas turbine engine industry [AD-A147295] p 297 N85-17162
- GAULT, J. W.
- Investigating version dependence in fault-tolerant p 302 N85-16749 software

B-6

GE. M.

- A stream function relaxation method for solving transonic S1 stream surface with respect to non-orthogonal p 228 A85-20240 curvilinear coordinates GEARIN, C. J.
- Speed benefits of tilt-rotor designs for LHX [NASA-CR-166437] p 255 p 255 N85-15717
- GEARY, J. M. Turbulence measurement interferometer apparatus
- p 295 N85-16156 [AD-D011377] GENT, R. W.
- The development of mathematical modelling techniques for helicopter rotor icing [AIAA PAPER 85-0336] p 240 A85-19679
- GERARD, P.
- Noise of an airfoil in a flow [ONERA, TP NO. 1984-155] p 303 A85-19269 GERHART, P. M.
- Progress in development of a Navier-Stokes solver for evaluation of iced airfoil performance
- [AIAA PAPER 85-0410] p 222 A85-19731 GERSHBEIN, E. A.
- Hypersonic chemically nonequilibrium viscous shock layer on wings with a catalytic surface
- p 229 A85-20561 GERSTEN. K.
- Drag reduction due to boundary-layer control by combined blowing and suction p 237 N85-16785 GHAFFARI, F.
- An attached flow design of a noninterfering leading edge extension to a thick delta wing [AIAA PAPER 85-0350] p 220 A85-19689
- GIANNINI, G.
- Reliable software design for avionics and space p 303 N85-16751 applications GIESE, U. Computation of transonic inlet flows
- p 227 A85-19844 GINSBURG, A. P.
- Contrast sensitivity performance assessment of HUD display systems p 259 A85-21593 GNOFFO, P. A.
- Laminar heat-transfer distributions on biconics at incidence in hypersonic-hypervelocity flows [NASA-TP-2213] p 293 N85-16065
- GOEBEL, T. P. Joined wing transonic design and test validation
- [AD-A148355] p 239 N85-16834 GOEL J. H.
- Design studies of thick laminar flow airfoils for low speed flight employing turbulent boundary layer suction over the p 257 N85-16786 rear part GONCHAROVA, O.
- Designer on Aeroflot automated COMMO system development GONNERMAN, V. J. p 296 N85-16765
- Performance evaluation of A-10 aircraft mainteance units and aircraft using constrained facet analysis [AD-A1469551 p 201 N85-15660
- GOODWIN, F. K. Prediction of cruciform all-movable control characteristics at transonic speeds
- [AD-A147291] p 239 N85-16832 GRAHAM, R. W.
- Computational thermo-fluid dynamics contributions to advanced gas turbine engine design
- [AIAA PAPER 85-0083] p 262 A85-19509 GRAHAM, T. A.
- Skirt material effects on air cushion dynamic heave stability p 307 A85-21840 **GRAINGER, F. S.**
- Helicopter data acquisition in WHL p 254 N85-15676
- GREEN, F. B.
- Integrated digital/electric aircraft concepts study [NASA-CR-3841] p 257 N85p 257 N85-16861 GREEN. H. E.
- Polyimide protective coatings for 700 deg service p 282 A85-21527 GREENE. G. C.
- Vortex research facility improvements and preliminary density stratification effects on vortex wakes p 209 A85-19482 [AIAA PAPER 85-0050]
- GREENWOOD, J. R.
- Judgment and discipline Recipe for survival p 241 A85-21582 GREITZER, E. M.
- Current problems in turbomachinery fluid dynamics [AD-A147127] p 294 N85-16074 GRIFFIN, J. H.
- Effects of friction dampers on aerodynamically unstable p 265 A85-21866 rotor stages GRODZOVSKII, G. L.
- Selection of rational models in the optimal planning of p 288 A85-20460 aeromechanical experiments

GROENEWEG, J. F.

- Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) [AIAA PAPER 85-0379] p 275 A85-19709 Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT)
- [NASA-TM-86919] p 276 N85-15757 GROSSKOPF. M.
- Realization and testing of an experimental color display system for general aviation helicopters and aircraft [BMFT-FB-W-84-042] p 262 N85-16872
- GROSVELD, F. W. Field-incidence noise transmission loss of general
- aviation aircraft double-wall configurations p 304 A85-21842
- GUENTHER, H.
- Investigations for the use of an active control in p 269 A85-19828 aircraft **GUENTHER, J.**
- Display Techniques for Advanced Crew Stations (DTACS). Phase 1: Display techniques study
- [AD-A146922] p 259 N85-15722 GULDIMANN, W.
- Construction and extension of airports National report on Switzerland p 308 A85-21947 GULLEDGE, T. R., JR.
- Production rate variations cost models p 308 N85-17732 [AD-A147708]

GUMBERT, C. R.

- Breakdown of the conservative potential equation p 221 A85-19700 [AIAA PAPER 85-0367]
- GUNSALLUS, C. T. K747 composite main rotor blade modification, analysis and qualification for new high temperature requirement p 251 A85-21378
- GUPTA, B. P.

HAFEZ, M. M.

gradients

HAFF. K. W.

HÁHN, E. J.

HAIGES. K.

testing

HALL I. M.

aerofoil

HALL R. M.

HALSEY. N. D.

HAMILTON, H. H.

HAMMER, J.

HALFORD, G. R.

[AD-A148215]

bearing systems

[NASA-CR-174320]

[AIAA PAPER 85-0371]

radioluminescent lighting

[ASME PAPER 84-TRIB-45]

transonic cryogenic tunnel

[AIAA PAPER 85-0229]

[AIAA PAPER 85-0038]

(AIAA PAPER 85-0245)

[NASA-CR-3863]

heating in three-dimensional flows

flows by a modified potential method

- Flexible matrix composites applied to bearingless rotor p 281 A85-21389 svetems GUSMANN, B.
- Documentation and separate test program development is most important for test/maintenance
- p 203 N85-16745 GUSTAFSON, G. L.
- Afterbody drag reduction by vortex generators [AIAA PAPER 85-0354] p 220 A8 p 220 A85-19692

Н

HABASHI, W. G. Analysis of a split-flow inertial particle separator by finite p 231 A85-21845 elements Computation of choked and supersonic turbomachinery flows by a modified potential method

Viscous/inviscid interaction analysis of transonic shock

Computation of choked and supersonic turbomachinery

Evaluation of arctic test of improved tritium

Stability of squeeze film damped multi-mass flexible rotor

Multivariable flight control with time-scale separation

Engine cyclic durability by analysis and material

Inviscid compressible flow past a multi-element

Studies of condensation effects on airfoil testing in a

Calculation of compressible potential flow about

Application of axisymmetric analogue for calculating

Design study of technology requirements for high

performance single-propeller-driven business airplanes

multielement airfoils using a finite field-panel approach

induced separated flow including normal pressure

p 232 A85-21859

p 221 A85-19703

p 232 A85-21859

p 278 N85-16884

p 289 A85-21296

p 268 N85-16873

p 267 N85-15744

p 236 N85-16776

p 274 A85-19603

p 207 A85-19473

p 216 A85-19611

p 235 N85-15692

PERSONAL AUTHOR INDEX HAMMOND, T. A. Design of a digital ride quality augmentation system for commuter aircraft [AD-A148233] p 271 N85-16879 HANKEY, W. L. Modes of shock-wave oscillations on spike-tipped p 232 A85-21855 bodies HANKS, C. H. The Air Force stock fund and aircraft availability [AD-A148653] p 203 N85-16761 HANNIBAL, A. J. Flexible matrix composites applied to bearingless rotor p 281 A85-21389 evetere HANSMAN, R. J., JR. The aerodynamic effect of surface wetting characteristics on a laminar flow airfoil in simulated heavy rain [AIAA PAPER 85-0260] p 247 A85-19619 Measurement of ice accretion using ultrasonic pulse-echo techniques [AIAA PAPER 85-0471] p 286 A85-19769 HARRIS, M. E. Avionics fault tree analysis and artifical intelligence for p 203 N85-16755 future aircraft maintenance HARTNETT, J. P. Advances in heat.transfer. Volume 16 p 288 A85-20501 HARVEY R. A. Heater block assembly for use in thermal oxidation testing of jet fuel p 285 N85-17077 [AD-D011430] HASSAN, H. A. Euler calculations for multielement airfoils using Cartesian grids [AIAA PAPER 85-0291] p 218 A85-19641 Application of a variational method for generating adaptive grids [AIAA PAPER 85-0487] p 226 A85-19784 HASTINGS, E. C., JR. Measurements of water film characteristics on airfol surfaces from wind-tunnel tests with simulated heavy rain [AIAA PAPER 85-0259] p 274 A85-19618 HÂTAYAMA, E. An analysis of the flow past an S-shaped rotor by discrete vortex model p 206 A85-19405 HATHAWAY, M. D. An experimental investigation of stator/rotor interaction influence on multistage compressor rotor flow p 206 A85-19455 [AIAA PAPER 85-0009] HAYASHI, M. Drag of the fundamental shapes of parachutes p 231 A85-20998 HAYMAN, K. J. Calculation of the velocity field generated by a helicopter main and tail rotors in hover [AD-A147731] p 239 N85-16833 HAYS. A. P. Integrated digital/electric aircraft concepts study p 257 N85-16861 [NASA-CR-3841] HEAPS. A. R. Trends in digital flight control systems p 269 A85-21465 HEBERT, J. L. Lightning simulation facilities in the United States and Furone [AIAA PAPER 85-0093] p 273 A85-19515 HEDLUND, E. R. Improvements in low Reynolds number testing in the NSWC hypervelocity wind tunnel No. 9 [AIAA PAPER 85-0226] p p 274 A85-19602 HELIN, H. E. An experimental investigation of an airfoil undergoing large amplitude pitching motions [AIAA PAPER 85-0039] p 207 A85-19474 Interrelated effects of pitch rate and pivot point on airfoil dynamic stall [AIAA PAPER 85-0130] p 212 A85-19541 HELLER, H. Aeroacoustics at the DFVLR Brunswick Research Center: A survey on recent and current activities p 306 N85-17677 [DFVLR-MITT-84-14] HELSLEY, C. W. Integrated digital/electric aircraft concepts study [NASA-CR-3841] p 257 N85-16861 HENDERSON, C. STOL technology for conventional flight enhancement [AIAA PAPER 84-2397] p 250 A85-20875 HENDERSON, D. O., JR. Free surface scars and striations due to trailing vortices generated by a submerged lifting surface

[AIAA PAPER 85-0445] p 286 A85-19754 HENDERSON, H. B.

Integration of sensor fusion in advanced helicopter cockpit design p 260 N85-16813 HESS, J. L. HOWLETT, J. T. Calculation of steady flow about propellers by means Efficient of a surface panel method [AIAA PAPER 85-0283] p 218 A85-19634 HS HILL J. A. F. Mach-10 high Revnolds number development in the NSWC hypervelocity facility [AIAA PAPER 85-0054] p 273 A85-19486 HS HILL R. G. Evaluation of aircraft interior panels under full-scale cabin fire test conditions [AIAA PAPER 85-0393] HU p 240 A85-19719 HILL, R. J. Verification of life prediction through component нι p 292 N85-15748 testina HIMENO, R. Computational study of circulation control with suction [AIAA PAPER 85-0042] p 208 A85-19477 н p 208 A85-19477 HINCHEY, M. J. Skirt material effects on air cushion dynamic heave p 307 A85-21840 stability HIPPENSTEELE, S. A. High temperature thermocouple and heat flux gauge using a unique thin film-hardware hot juncture HI p 295 N85-16096 [NASA-TM-86898] HIRSCHEL, E. H. Theoretical study of boundary-layer control н p 237 N85-16784 HIRST. M. Modern military engines. II p 264 A85-20822 HO, C.-M. HL Three-dimensional effects on a pitching lifting surface [AIAA PAPER 85-0041] p 208 A85-19476 HODGENS, H. M., II Improvement of the corrosion resistance of turbine HI engine bearings [AD-A147430] p 265 N85-15731 HOELMER, W. A universal turboshaft engine test cell - Design HU considerations and model test results p 275 A85-19711 [AIAA PAPER 85-0382] HOFFMAN, J. D. Calculation of viscous nozzle flows by the unsteady н method of characteristics p 212 A85-19542 [AIAA PAPER 85-0131] HÖFFMAN, S. J. An optimization method for the preliminary design of н interplanetary aerobraking missions p 238 N85-16822 HOH. B. H. Mission-oriented requirements for updating MIL-H-8501. Volume 1: STI proposed structure [NASA-CR-177304-VOL-1] н p 271 N85-16877 Mission-oriented requirements for updating MIL-H-8501. ы Volume 2: STI background and rationale p 271 N85-16878 [NASA-CR-177304-VOL-2] HOLANDA, R. High temperature thermocouple and heat flux gauge using a unique thin film-hardware hot juncture [NASA-TM-86898] p 295 H p 295 N85-16096 HOLBROOK, G. T. Vortex research facility improvements and preliminary density stratification effects on vortex wakes [AIAA PAPER 85-0050] p 209 A85-19482 HOLFORD, D. M. Operational loads measurement: A philosophy and its implementation p 253 N85-15665 HOLMES. C. R. IG A study of the effects of triggered lightning AD-A148296] p 300 N85-17494 [AD-A148296] HOLST. T. L. Numerical optimization design of advanced transonic IL ring configurations [AIĂA PAPER 85-0424] p 248 A85-19739 HOLZ, W. Reflector antennas with directional effect in the (b) near-field Characteristics and applications p 287 A85-19837 HOPKINS, H. (). Boeing's rejuvenated twin jet HORONJEFF, R. D. p 250 A85-20222 NOISEMAP 4.4 computer program update, operator's 10 manual, addendum 1 [AD-A147091] p 302 N85-16503 HORSTMANN, K. H. Pneumatic turbulators: A device for drag reduction at IF Reynolds numbers below 5 million p 257 N85-16791 HOTOP, H. J. Flight testing of Litton laser gyro strapdown system LTN-90 for general aviation [DFVLR-MITT-84-16] p 245 N85-15709 1E HOU. Y. Some improvements on an annular combustor of Al type turbojet engine IS p 264 A85-20235 HOWE, J. T. Introductory aerothermodynamics of advanced space transportation systems p 231 A85-21827

ISAAC, K. M.

Efficient self-consistent viscous-inviscid solutions for
(AIAA PAPER 85-0482) p 225 A85-19779 SU, CH.
Theory of wing rock [AIAA PAPER 85-0199] p 268 A85-19583
Unsteady aerodynamics of an airfoil encountering a
passing vortex (AIAA PAPER 85-0203) p 214 A85-19587 J ANG, D.
Some improvements on an annular combustor of Al type turboiet engine p 264 A85-20235
JANG, MK.
[AIAA PAPER 85-0446] p 224 A85-19755 JBBARTT, J. E.
Turbulent flow around a wing-fuselage type juncture [AIAA PAPER 85-0040] p 208 A85-19475 SFRJ simulator results - Experiment and analysis in cold
flow [AIAA PAPER 85-0329] p 263 A85-19671
Advanced flight simulation for helicopter development p 277 N85-16815
UBERSON, S. Calculation of three-dimensional unsteady
incompressible flows by a vortex method
UFFMAN, J. K.
Subsonic pressure distributions near a wing-fin juncture on a supersonic arrow-wing configuration with
wing-mounted vertical fins [AIAA PAPER 85-0276] p 217 A85-19628
Analytical modeling of circuit aerodynamics in the new
NASA Lewis wind tunnel [NASA-TM-86912] p 234 N85-15688
Transient motion of hypersonic vehicles including time
history effects [AIAA PAPER 85-0201] p 268 A85-19585
ULT, L. J. Evaluation of arctic test of improved tritium
radioluminescent lighting [AD-A148215] p 278 N85-16884
A simulator for studying helicopter weapons systems
p 277 N85-16816
The universal nature of zero-crossing time and velocity scales in turbulent shear flows p 232 A85-21851 USSAINI. M. Y.
Spectral methods for modeling supersonic chemically reaction flow fields
[AIAA PAPER 85-0302] p 219 A85-19651 UTH, H.
The influence of fastener flexibility on load transfer and fatigue life predictions for multirow bolted and riveted ioints
[LBF-FB-172/84] p 296 N85-16219
I
NATUK, R. R.
Utilization of analytical equipment in design and process problems solution and failure analysis of composites p 281 A85-21390
JFF, K. W.
estimation
[NASA-TM-85905] p 270 N85-15752
Automated visibility measurements for airports
[AIAA PAPEH 85-0191] p 274 A85-19577 NGLSPERGER, A.
Advanced flight simulation for helicopter development p 277 N85-16815
DANNIDES, A. Development of a preliminary ALRS stabilized material pavement analysis system (SPAS)
[AD-A147116] p 277 N85-15760
AISH, L. A. Systems study for an Integrated Digital-Electric Aircraft
[NASA-CR-3840] p 255 N85-15714
AVINE, T. F., JR. Advances in heat transfer. Volume 16
SAAC, K. M.
Computation of recirculating compressible flow in axisymmetric geometries
[AIAA PAPER 85-0185] p 286 A85-19575

B-7

IUNITSKII, S. A.

IUNITSKII, S. A.

- ...Hypersonic..chemically..nonequilibrium..viscous..shock layer on wings with a catalytic surface p 229 A85-20561
- IVANOV, A. V. Hypersonic multicycle gas jet with a strongly underexpanded stream at the nozzle section
- p 229 A85-20554 IYER, V. Numerical solutions of viscous transonic flow in
- turbomachinery cascades [AIAA PAPER 85-0007] p 206 A85-19454

.

- JACARUSO, G.
- Fabrication and assembly of composite rear fuselage (CRF) tooling and manufacturing for the UH-60 helicopter p 200 A85-21394 JACOBS, P. F.
- Aileron effectiveness for a subsonic transport model with a high-aspect-ratio supercritical wing [NASA-TM-85674]
- p 235 N85-15695 JACOCKS. J. L.
- A numerical simulation of the NFAC (National Full-scale Aerodynamics Complex) open-return wind tunnel inlet flow p 230 A85-20869
- [AIAA PAPER 85-0437] JAGODA, J. I. SFRJ simulator results - Experiment and analysis in cold
- flow [AIAA PAPER 85-0329] p 263 A85-19671
- JAMESON, A. Three-dimensional Euler solutions with grid embedding [AIAA PAPER 85-0121] p 211 A85-19532
- Multigrid solution of the Euler equations using implicit scheme TAIAA PAPER 85-02931 p 218 A85-19643
- Finite volume solution of the two-dimensional Euler equations on a regular triangular mesh p 223 A85-19748 [AIAA PAPER 85-0435]
- A comparative study of the nonuniqueness problem of the potential equation p 235 N85-15694 INASA-TP-23851
- JANIKOWSKY, J. C. Optimized discrete-singularity representation of
- axisymmetric bodies [AIAA PAPER 85-0284] p 218 A85-19635 JANJUA, S. I.
- Investigation of nonlinear effects in the instabilities and noise radiation of supersonic jets
- [AIAA PAPER 85-0081] p 304 A85-19507 JANSSEN. D. Development of a preliminary ALRS stabilized material
- pavement analysis system (SPAS) p 277 N85-15760 [AD-A147116]
- JAYARAM, M. The distortion of a supersonic turbulent boundary layer
- by bulk compression and surface curvature [AIAA PAPER 85-0299] p 218 A85-19648 JENKINS, R. M.
- An improved computer model for prediction of axial gas turbine performance losses [NASA-CR-174246] p 265 N85-15724
- JIANG. Y. A method of forecasting active constraint with the
- applications to structural optimization p 291 A85-22445 JOHNSON, A. H.
- Navy operational loads data sources and systems p 253 N85-15668 JOHNSTON, J. T.
- The F-15 flight loads tracking program p 253 N85-15666
- JONES, R. J. Polyimide protective coatings for 700 deg service p 282 A85-21527
- JURION, H. Renegade 250 - Flight evaluation or boat ride? p 252 A85-22273

Κ

KAHOE, M. W.

B-8

- F-8 refueling boom ground vibration test [NASA-TM-84914] p 255 N85-15713 KALLERGIS. M.
- The unambiguous in-flight determination of propeller rotational noise in aircraft with four-cycle combustion p 304 A85-20650 enaines KARAMANLIS, A. I.
- A universal turboshaft engine test cell Design
- considerations and model test results [AIAA PAPER 85-0382] p 275 A85-19711

- KAUFMAN, A.
- Engine cyclic durability by analysis and material testing p 267 N85-15744 KAUL, Ü. K.
- A numerical simulation of the NFAC (National Full-scale Aerodynamics Complex) open-return wind tunnel inlet flow
- [AIAA PAPER 85-0437] p 230 A85-20869 KÁVETSKY, R. A.
- Mach-10 high Reynolds number development in the NSWC hypervelocity facility p 273 A85-19486
- [AIAA PAPER 85-0054] KAWAMURA, T.
- Computational study of circulation control with suction [AIAA PAPER 85-0042] p 208 A85-19477 KEARNEY. H.
- testina ACAP Structural analysis and of subcomponents p 251 A85-21384 KEEN. K. S.
- Inexpensive calibrations for the influence function method using the interference distributed loads code p 247 A85-19623 [AIAA PAPER 85-0270] KEHAN. Z.
- International aviation (selected articles)
- [AD-A148704] p 204 N85-16762 KEINER, W. L.
- Joint service design for testability program p 296 N85-16733
- KEITH, T. G., JR. Full two-dimensional transient solutions of electrothermal aircraft blade deicing
- [AIAA PAPER 85-0413] p 248 A85-19734 KELLER, J. L.
- Clear turbulence forecasting Towards a union of art and science
- [AIAA PAPER 85-0014] p 298 A85-19458 KELLER, J. O.
- An experimental investigation of an unsteady combusting flow in a pulse combustor [AIAA PAPER 85-0322] p 281 A85-20865
- KELLER. V. W.
- Status of warm fog dispersal research [AIAA PAPER 85-0010] p 2 p 272 A85-19456 KENDIG. W. C.
- Aircraft thrust control scheme for terrain following evetom
- [AD-D011387] p 255 N85-15711 KERREBROCK, J. L.
- Current problems in turbomachinery fluid dynamics [AD-A147127] p 294 N85-16074 KERVELLA, I. M.
- The embedded test (BIT): Impact on the total cost of possession p 202 N85-16734
- KEY. D. L.
- A review of US Army aircrew-aircraft integration research p 270 N85-16814 programs Assessment of simulation fidelity using measurements of piloting technique in flight p 278 N85-16817
- KEYES, J. W. Experimental study of forward-located iet-interaction [AIAA PAPER 85-0454] p 224 A85-19762
- KHAIMOVICH, I. A. Aviation radar p 244 A85-19805 KHAN. M. R.
 - An optimality criterion method for structures with stress, displacement and frequency constraints p 290 A85-21985
- KHATTAB. A. A.
- Some important problems in unsteady boundary layers including separation. 1: Nature of singularity on oscillating airfoils
- [AD-A147897] p 294 N85-16087 KILGORE, R. A.
- Description of the insulation system for the Langley 0.3-Meter Transonic Cryogenic Tunnel [NASA-TM-86274] p 276 N85-15755
- KIM, C.-H.
- Analysis and testing for rotordynamic coefficients of seals with turbulent annular different directionally-homogeneous surface-roughness treatment for rotor and stator elements [ASME PAPER 84-TRIB-31] p 289 A85-21293
- KIM. J. J.
- Computational particle trajectory analysis on a 3-dimensional engine inlet [AIAA PAPER 85-0411] p 222 A85-19732
- KIM, M. J.
- Application of continuous vorticity panels to general unsteady two-dimensional lifting flows [AIAA PAPER 85-0282] p 217 A85-19633
- KINDERVATER. C. M. Energy absorbing qualities of fiber reinforced plastic
- tubes p 282 A85-21393

KIRBY, D. A.

- Investigations into the effects of scale and compressibility on lift and drag in the RAE 5m pressurized p 236 N85-16773 low-speed wind tunnel KIRBY, M. S.
- Measurement of ice accretion using ultrasonic pulse-echo technique AIAA PAPER 85-04711 p 286 A85-19769
- KIRRMANN, C.
- A comparison of different three-dimensional singularity methods for modelling internal flows [ONERA, TP NO. 1984-150] p 205 A85-19264
- KLANN. G. A. Temperature distortion generator for turboshaft engine
- testing [NASA-TM-83748] p 200 N85-15658
- KLEHR, J. T. Safety Meteorological data vital for simulator training [AIAA PAPER 85-0091] p 240 A85-19513
- KLEIN, G. A. Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems
- [NASA-CR-174271] p 242 N85-15701 KNOX. C. E.
- Reference energy-altitude descent guidance: Simulator evaluation [NASA-TP-2383] p 261 N85-16868
- KOBAYASHI, H. to density
- Application of laser interferometry p 206 A85-19406 measurements in free jets KOENIG, E. W.
- Stereo Electro-optical Tracking System (SETS) [NASA-CR-172471] p 295 N85-16098 KÖENIG, G. W.
- Comparison between the properties of conventional wrought and powder metallurgical alloys for turbine disc p 283 N85-15739 applications
- KOENIG. H. Flight tests with a new helicopter Force Feel System
- (FFS) p 257 N85-16818 KOHLMAN, D. L. Design study of technology requirements for high
- performance single-propeller-driven business airplanes [NASA-CR-3863] o 235 N85-15692 KOLPAKOV. B. K
- Combat aircraft: Flight vehicles, power plants, and their p 199 A85-19812 maintenance KOMAROV, V. A.
- Design of load-bearing aircraft structures p 288 A85-20463

of a compressible gas in a plane duct

gradation due to ice accretion

Subsonic wing rock of slender delta wings

KONSTADINOPOULOS, P.

AIAA PAPER 85-0198]

[AIAA PAPER 85-0339]

0012 airfoil with simulated ice

Navier-Stokes numerical solutions

flows by a modified potential method

Oxidation and stabilization of jet fuels

TAIAA PAPER 85-01071

Calculation of friction and heat transfer in turbulent flow

Analytical determination of propeller performance

Experimental aerodynamic characteristics of an NACA

A numerical study of three-dimensional radiation fields

Flows over low Reynolds number airfoils - Compressible

Computation of choked and supersonic turbomachinery

Problems and possibilities for life extension in gas turbine

Examining the validity of a combustor flow model with

Optimal control of flow of a viscous incompressible

Application of a variational method for generating

Effect of the arrangement of apertures on the gain

coefficient during asymmetric gas injection into a Laval

in problems of supersonic flow past segmental bodies

p 291 A85-22114

p 214 A85-19582

p 264 A85-20867

p 252 A85-21844

p 227 A85-20025

p 210 A85-19523

p 232 A85-21859

p 267 N85-15742

p 281 A85-20925

p 209 A85-19487

p 290 A85-22105

p 226 A85-19784

p 229 A85-20562

KONDAK, N. M.

KORKAN, K. D.

KOSTUZIK, A. A.

KOTHARI, A. P.

KÔTIUGA. P. L.

KOUL, A. K.

components

KOVALEV, G. I.

KRAEMER, G. O.

KRAPIVSKII, P. L.

adaptive grids

KREMNEV, V. P.

[AIAA PAPER 85-0055]

[AIAA PAPER 85-0487]

LDV

fluid

KREIS. R. I.

nozzle

PERSONAL AUTHOR INDEX

KRIEGER, R. J.

- Aerodynamic configured missiles Promise and future [AIAA PAPER 85-0345] p 248 A85-19684 Evaluation of vortex wake predictions in the SWINT code
- [AIAA PAPER 85-0450] p 224 A85-19759 Interactive design technique for arbitrary shaped, airbreathing missile configurations [AIAA PAPER 85-0496]
- p 249 A85-19790 KROGMANN, P.
- Active and passive shock/boundary layer interaction p 238 N85-16795 control on supercritical airfoils KROMER, S. L.
- Flowfield analysis of low bypass ratio test cells p 265 A85-21839
- KROUTIL, J. C. A novel experimental facility for conducting jet impingement studies related to VTOL aircraft
- [AIAA PAPER 85-0052] p 209 A85-19484 KUBENDRAN, L. R. Turbulent flow around a wing-fuselage type juncture
- [AIAA PAPER 85-0040] p 208 A85-19475 KUBOTA, H.
- Computation of unsteady shock-induced vortex separation
- [AIAA PAPER 85-0183] p 214 A85-19573 KUDRNA, J.
- Calculation of the minimum-time loop maneuver for jet p 269 A85-19876 aircraft KUMAR. A.
- Flow behind an attached shock wave in a radiating p 233 A85-22308 nae
- KUMMER, R. P. The interaction and merging of two turbulent line vortices
- p 208 A85-19480 [AIAA PAPER 85-0046] KÜNIK, W. G.
- Analytical modeling of circuit aerodynamics in the new NASA Lewis wind tunnel
- [NASA-TM-86912] p 234 N85-15688 KÜROSAKA, M.
- Contamination and distortion of steady flow field induced by discrete frequency in aircraft gas turbines
- [AD-A147092] p 294 N85-16073 KÜRUVILA. G.

A study of the effects of numerical dissipation on the calculation of supersonic separated flows [AIAA PAPER 85-0301] p 219 A85-19650

KUWAHARA, K. Computational study of circulation control with suction

- [AIAA PAPER 85-0042] p 208 A85-19477 Computation of unsteady shock-induced vortex separation [AIAA PAPER 85-0183] p 214 A85-19573
 - L

LAAN, D. J.

- Recent advances in computational methods to solve the high-lift multi-component airfoil problem p 236 N85-16774
- LAIOSA, J.
- Prediction of HiMAT RPRV component interference effects at transonic speeds [AIAA PAPER 85-0213] p 215 A85-19593
- LAM. F.
- The effect on software design of testing by symbolic xecution p 303 N85-16750 execution LAMAR, J. E.
- An attached flow design of a noninterfering leading edge extension to a thick delta wing
- [AIAA PAPER 85-0350] p 220 A85-19689 LAMBERT. M.
- Mi-28 The Soviets create Havoc p 250 A85-20147 LAMZUTOV. V.
- Testing solution for IL-76 braking system problem p 256 N85-16766

p 268 A85-19583

LAN. C. E. Theory of wing rock

[AIAA PAPER 85-0199]

- An investigation of vortex-induced aerodynamic characteristics of supersonic cruise configurations
- [NASA-CR-174299] p 234 N85-15690 LANDAU, I. IA.
- Some problems in the development of CAD systems p 200 A85-20466 LANDFIELD, J. P.
- STOL technology for conventional flight enhancement [AIAA PAPER 84-2397] p 250 A85-20875 LANGSTON, P. R.
- Kevlar aramid fibers vs other fibers for reinforcement of composite structures p 282 A85-21392 LARSEN. J. M.
- Cumulative damage modeling of latigue crack growth p 267 N85-15741

- LARSON, E. S.
- Crossflow drag of finite-length rectangular wing-bodies [AIAA PAPER 85-0451] p 224 A85-19760 LARSSON, F.
- Impressions from a study tour in Finland concerning fiber reinforced plastics, June 1984 [FOA-C-20552-D2(E4,F9)]
- p 283 N85-15831 LARUELLE, G.
- Aerodynamic studies linked to the development of deployable nozzles
- [ONERA, TP NO. 1984-149] p 205 A85-19263 Interest of internal bleed for a two-dimensional air intake operating in a wide Mach number range (1.8-3 plus) p 237 N85-16793
- LAUDER, R. P. F.
- A practical example of reducing life cycle costs and increased availability p 296 N85-16736 LAVOIE, J. E.
- Atmospheric electricity hazards to aircraft operation p 247 A85-19457 [AIAA PAPER 85-0013] LAWING, P. L.
- Description of the insulation system for the Langley 0.3-Meter Transonic Cryogenic Tunnel
- p 276 N85-15755 [NASA-TM-86274] LAWRENCE, R. A.
- Monitoring engine thermal stresses p 266 N85-15735
- LAWRENCE, S. H. Optimal maintenance center inventories for fault-tolerant repairable systems p 301 A85-21548
- LE MEUR, A. Computation of three-dimensional flows for application to transonic compressors
- p 204 A85-19260 [ONERA, TP NO. 1984-146] LEASURE, R.
- National airspace review: Airport radar service area operational confirmation report p 245 N85-15707
- [DOT/FAA/AT-84/2] LEDNICER, D. A.
- Correlation of airfoil icing relationships with two-dimensional model and full scale rotorcraft icing test data [AIAA PAPER 85-0337] p 240 A85-19680
- LEE. C. S.
- A comparison between theoretical and experimental flow fields of an airfoil with deflected spoiler [AIAA PAPER 85-0269] p 216 A85-19622
- LEE, D. J. Interaction of a turbulent vortex with a lifting surface
- p 206 A85-19452 [AIAA PAPER 85-0004] LEE, D.-H.
- Comparative study of various quadratures for subsonic lifting surface chordwise integrals p 205 A85-19404 LEE, H.
- Experimental results for Reynolds number effects on p 232 A85-21849 trailing vortices LEE, J. D.
- A universal turboshaft engine test cell Design considerations and model test results
- p 275 A85-19711 [AIAA PAPER 85-0382] LEE. J. T.
- Radar for storm forecasting and weather hazard warning
- [AIAA PAPER 85-0092] p 299 A85-19514 LEFEBVRE, R.
- Interest of internal bleed for a two-dimensional air intake operating in a wide Mach number range (1.8-3 plus) p 237 N85-16793
- LEFFEL, K. L. Full two-dimensional transient solutions of electrothermal aircraft blade deicing
- [AIAA PAPER 85-0413] p 248 A85-19734
- LEHMAN, L. L. A parallel guasi-linearization algorithm for air vehicle ectory optimization
- p 279 A85-19792 [AIAA PAPER 85-0498] LEICHNER, S.
- Theoretical contributions to transonic flow analysis for transport aircraft
- [BMFT-FB-W-84-036] p 239 N85-16838 LEKOUDIS, S. G. Solution of the unsteady Euler equations for fixed and
- rotor wing configurations (AIAA PAPER 85-0120) p 211 A85-19531
- LENSKI, J. W., JR. Development of a graphite/polyimide composite
- p 281 A85-21380 transmission housing LESCAULT. M.
- A study of the flow recirculation problems within an nechoic hover chamber
- p 273 A85-19497 [AIAA PAPER 85-0071] LESTER P T
- The Cockpit Display of Traffic Information and the Threat Alert and Collision Avoidance System Integration - A review p 259 A85-21559

LEVERTON, J. Acoustical guidelines for new heliports p 276 A85-21644 LEVERTON, J. W. An overview of helicopter's considerations p environmental p 241 A85-21643 LEVIN, A. D. Installed nacelle drag-improvement tests of an $M\,=\,0.8$ turboprop transport configuration [NASA-TM-84302] p 255 N85-15716 LEVY. R. Analytical modeling of circuit aerodynamics in the new NASA Lewis wind tunnel p 234 N85-15688 (NASA-TM-869121 LEYBOLD, H. A. Ground test experience with large composite structures for commercial transports p 251 A85-21383 LI, C. P. A three-dimensional Navier-Stokes/Euler code for blunt-body flow computations [AIAA PAPER 85-0361] p 220 A85-19696 LIÀNG, D. F. Development of a Helicopter integrated navigation svstern LIANG. J. C. Theoretical study on supersonic jet plumes p 206 A85-19439 LIEBERT, C. H. High temperature thermocouple and heat flux gauge using a unique thin film-hardware hot juncture [NASA-TM-86898] p 295 N85-16096 LILLEY. D. G. Flow visualization of lateral jet injection into swirling crossflow [AIAA PAPER 85-0059] p 209 A85-19490 LING. Z. The fundamental equations of 3-dimensional two-phase particulate gas flow and a twofold stream surfaces model of solution for particulate gas flow in turbomachines p 228 A85-20233 LIPPERT, J. R. Atmospheric electricity hazards to aircraft operation [AIAA PAPER 85-0013] p 247 A85-19457 LIU, D. Complete three-dimensional flow solution of a cascade incorporating splitter vanes of arbitrary geometry p 228 A85-20230 LIU. G. A new approach to some hybrid aerodynamic problems of airfoil cascades on a general streamsheet of revolution. p 228 A85-20229 LIU, M. A linearly correcting method of deviation function for considering the influence of pressure on the thermodynamic properties of combustion gas p 304 A85-20236 LLORENS, R. Analysis of the flow field about a T-45 using PANAIR [AD-A146811] p 236 N85-15699 LOFLAND, R. A. Tooling problems in the manufacture of AH-64 Composites Flexbeam Tail Rotor p 200 A85-21382 LOMBARD, C. K. flowfields about three-dimensional Real-gas configurations p 231 A85-21830 LONG, E. A. Life cycle cost model for very high speed integrated circuits [AD-A147798] p 297 N85-17298 LONG. W. D. Atmospheric photochemical modeling of turbine engine fuels. Phase 1: Experimental studies. Volume 2: Environmental chamber data tabulations p 300 N85-17470 [AD-A147786] LORCH, D. S-3A ballast block final design and engineering tests p 243 N85-16842 [AD-A147685] LOSITO, V. Turbulent bubbles behind airfoils and wings at high angle of attack p 296 N85-16779 LOWENBERG, M. H. A global technique for aircraft stability and control analvsis p 270 A85-21681 LOWRY, D. W. Composite curved frames for helicopter fuselage p 252 A85-21396 structure LU. P. National airspace review: Airport radar service area operational confirmation report

- [DOT/FAA/AT-84/2] p 245 N85-15707 LU, Z.
- Determination of surging line of two-spool axial flow compressor with cropped fan stages at low speed by use of parallel compressor theory p 264 A85-20242

- p 245 N85-16802

LUCCHI, C. W.

LUCCHL C. W.

- A subdomain finite element method for solving the conservative full potential equation for transonic profile p 227 A85-19854 flows
- LUCKRING, J. M. A theory for the core of a three-dimensional leading-edge
- TAIAA PAPER 85-01081 p 210 A85-19524 LUDTKE, W. P.
- A theoretical view on the stress analysis of fully inflated parachute canopies
- p 239 N85-16835 AD-A148387 LUND. T. S.
- A zonal computational approach to thrust augmentor optimization [AIAA PAPER 85-0110] p 262 A85-19525
- LUTTGES, M. W. Three-dimensionality in unsteady flow about a wing
- [AIAA PAPER 85-0132] p 212 A85-19543 LUZETSKY, H. R.
- Utilization of analytical equipment in design and process problems solution and failure analysis of composites p 281 A85-21390

Μ

- MACCORMACK, R. W.
- Current status of numerical solutions of the Navier-Stokes equations [AIAA PAPER 85-0032] p 207 A85-19469
- MACE. J. Shock waves in transonic channel flows at moderate
- Revnolds number [AIAA PAPER 85-0369] p 221 A85-19702
- MACE. J. L. Shock waves in transonic flows at moderate Reynolds
- Number p 238 N85-16823 MACKLEY, E. A. Langley Mach 4 scramjet test facility
- [NASA-TM-86277] p 278 N85-16883 MACMULLIN, R.
- UH-60A external stores support system fixed provision fairings drag determination [AD-A147188] p 256 N85-15719
- MADDALON, D. V.
- Technology developments for laminar boundary layer control on subsonic transport aircraft p 237 N85-16787
- MAGDELENAT, J.-L. Construction and extension of airports - Legal procedure
- p 307 A85-21944 and practice in Canada MAGI. V.
- A guasi-conservative lambda formulation [AIAA PAPER 85-0088] p 210 A85-19511
- MAGILL, S. N. Air traffic management concepts for the UK in the 1990's: A review of recent RSRE work
- [AD-A147850] p 246 N85-16853 MAHAN, J. R.
- An improved source model for aircraft interior noise studies
- [NASA-CR-172517] p 305 N85-17668 MAHESH, J. K.
- Development of a Helicopter integrated navigation p 245 N85-16802 MAHMOOD, A.
- Writing executable assertions to test flight software [SU-CRC-TR-84-14] p 301 A85-21973 MAINE, R. E.
- More than you want to know about maximum likelihood estimation
- [NASA-TM-85905] p 270 N85-15752 MALCOLM, R. C. Fatigue crack growth behavior of 7XXX aluminum alloys
- under simple variable amplitude loading p 280 A85-20759
- MALHOTRA, R.
- Analysis of middle distillate fuels by high resolution field ionization mass spectrometry [AD-A147724] p 285 N85-17153
- MANDLE, J. Recent methods for calibrating the anemometry of
- helicopters at low speeds p 260 N85-16809 MANKBADI, R. R.
- The effect of phase-difference on the spreading rate of a laminar circular jet under bi-modal excitation [AIAA PAPER 85-0045] p 208 A85-19479 MANNIX, J. T.
- Powered articulated headrest system [AD-D011353] p 254 N85-15710
- MANSOUR. I. Maximum final energy chandelle
- [AIAA PAPER 85-0200] p 247 A85-19584

- Measurements of water film characteristics on airfol surfaces from wind-tunnel tests with simulated heavy rain [AIAA PAPER 85-0259]
- p 274 A85-19618 MANWARING, S. R. Three dimensional aerodynamics of an annular cascade
- in a non-uniform inlet flow p 213 A85-19567 [AIAA PAPER 85-0174]
- MARCHMAN, J. F., III Effects of covering configurations on ultralight wing erodynamics
- [AIAA PAPER 85-0277] p 217 A85-19629 Aerodynamics of an aspect ratio 8 wing at low Reynolds number
- [AIAA PAPER 85-0278] n 217 A85-19630 MARCOLINI, M. A.
- Scaling of airfoil self-noise using measured flow p 304 A85-21858 narameters MARCONI, F.
- Shock induced vortices on elliptic cones in supersonic flow
- [AIAA PAPER 85-0433] p 223 A85-19746 MARCUM. D. L.
- Calculation of viscous nozzle flows by the unsteady method of characteristics [AIAA PAPER 85-0131] p 212 A85-19542
- MARKOV, A. B. Nonlinear simulation of flight along wind compensating
- curved alidepaths p 245 A85-21838 MARRAFFA. L.
- Computation of three-dimensional flows for application to transonic compressors
- [ONERA, TP NO. 1984-146] p 204 A85-19260 MARTIN, J. A.
- Shock-fitting solution of the supersonic flowfield in a p 232 A85-21856 rounded internal corner MARTIN, W. L.
- Contrast sensitivity performance assessment of HUD display systems p 259 A85-21593 MASCARENHAS, J. M. G. B.
- ATE user's view on design for maintainability p 202 N85-16737
- MASIULANIEC, K. C. Full two-dimensional transient solutions of
- electrothermal aircraft blade deicing TAIAA PAPER 85-0413] p 248 A85-19734
- MASKEW, B. Prediction of dynamic stall characteristics using
- advanced non-linear panel methods [AD-A148453] p 239 N85-16836 MASTERS, C. O.
- The Federal Aviation Administration's Engineering and Development Aircraft Icing Program p 247 A85-19459 [AIAA PAPER 85-0015]
- MATTINGLY, J. D.
- swirling flows [AIAA PAPER 85-0186]
- MAUGHMER, M. D.
- oradients
- MAVRIPLIS, D.
- equations on a regular triangular mesh [AIAA PAPER 85-0435] p p 223 A85-19748
- Aerodynamic issues in the design of high-lift systems p 256 N85-16780 for transport aircraft
- tunnel
- [NASA-CR-174277] p 305 N85-16586 MAZZIO, V. F.
- Utilization of analytical equipment in design and process problems solution and failure analysis of composite p 281 A85-21390
- MCALLISTER, D. F.
- Investigating version dependence in fault-tolerant p 302 N85-16749 software MCCAIN, W. E.
- Comparison of analytical and experimental steadyand unsteady-pressure distributions at Mach number 0.78 for a high-aspect-ratio supercritical wing model with oscillating control surfaces [NASA-TM-84589] p 235 N85-15697
- MCCANDLESS, R. S.
- Hypersonic characteristics of an advanced aerospace nion [AIAA PAPER 85-0346] p 269 A85-19685
- MCCLINTOCK, L. L.
- EMI (electromagnetic interference) filter capacitor unit p 293 N85-15941 [AD-D0113921

MCCLURE, W. B.

Flowfield scaling ~ in sharp fin-induced shock wave/turbulent boundary-layer interaction p 232 A85-21857 MCCLUSKEY F. J. Writing executable assertions to test flight software [SU-CRC-TR-84-14] p 301 A85-21973 MCCONNELL, P. M. Aircraft wing fuel tank environmental simulator tests for evaluation of antimisting fuels p 283 N85-15920 [FAA-CT-84-15] MCCUNE, J. E. Current problems in turbomachinery fluid dynamics [AD-A147127] p 294 N85-16074 MCDANIEL R. L. Speed benefits of tilt-rotor designs for LHX [NASA-CR-166437] p 255 N85-15717 MCDONALD, A. B. Powered articulated headrest system [AD-D011353] p 254 N85-15710 MCDONALD, H. Development of a Navier-Stokes rotor and stator analycie [AD-A146967] p 294 N85-16070 MCINVILLE, R. V. Turbulent drag reduction research p 237 N85-16788 MCKINNELL, R. J. The development of a finite element model of an aircraft vertical stabilizer for vibration analysis p 290 A85-21683 MCLAUGHLIN, D. K. Investigation of nonlinear effects in the instabilities and noise radiation of supersonic jets p 304 A85-19507 [AIAA PAPER 85-0081] MCLEAN, L. J. Stability of squeeze film damped multi-mass flexible rotor bearing systems [ASME PAPER 84-TRIB-45] p 289 A85-21296 MCMAHON, H. M. Turbulent flow around a wing-fuselage type juncture [AIAA PAPER 85-0040] p 208 A85-19475 MCMASTERS, J. H. Aerodynamic issues in the design of high-lift systems for transport aircraft p 256 N85-16780 MCRUER, D. T. Mission-oriented requirements for updating MIL-H-8501. Volume 1: STI proposed structure p 271 N85-16877 [NASA-CR-177304-VOL-1] MEEHAN, R. J. Evaluation of jet fuel deposit kinetics. Lot 4 p 284 N85-15922 [AD-A147196] MEHALIC. C. M. Effect of steady-state temperature distortion on inlet flow to a high-bypass-ration turbofan engine p 265 N85-15725 [NASA-TM-86896] MEHTA, H. K. Aircraft wing fuel tank environmental simulator tests for evaluation of antimisting fuels [FAA-CT-84-15] p 283 N85-15920 MEHTA, R. S. Identification of vortex-induced clear air turbulence using airline flight records p 299 A85-21843 MEINEL H. LPI-radar for helicopter obstacle warning p 297 N85-16810 MELLIERE, R. A. The F-15 flight loads tracking program p 253 N85-15666 MELNIK, R. E. A comparative study of the nonuniqueness problem of the potential equation [NASA-TP-2385] p 235 N85-15694 MENON, P. K. A. A parallel quasi-linearization algorithm for air vehicle trajectory optimization [AIAA PAPER 85-0498] p 279 A85-19792 MERKLEY, D. J. US Army helicopter operational flight loads p 254 N85-15675 MICHALKE, A. Survey on jet instability theory p 227 A85-20074 MICOL J. R. Laminar heat-transfer distributions on biconics at incidence in hypersonic-hypervelocity flow p 293 N85-16065 [NASA-TP-2213] MIELKE, E. J. Measurement of signal separation between radio service and air navigation service [IRT-TB-B-40/82] p 246 N85-16860 MIELKE, R. R. Ultrasound instrumentation for the 7 inch Mach seven

tunnel [NASA-CR-174277] p 305 N85-16586

An experimental investigation of the mixing of co-annular p 230 A85-20862 A class of airfoils having finite trailing edge pressure

[AIAA PAPER 85-0206] p 215 A85-19590

- Finite volume solution of the two-dimensional Euler
- MAY, F. W.
- MAZEL, D. S.
- Ultrasound instrumentation for the 7 inch Mach seven

PERSONAL AUTHOR INDEX

MIESS. J. O. UH-60A external stores support system fixed provision fairings drag determination [AD-A147188] p 256 N85-15719 MILLER, C. G., III Laminar heat-transfer distributions on biconics at incidence in hypersonic-hypervelocity flows p 293 N85-16065 [NASA-TP-2213] MILLER, G. W. EMI (electromagnetic interference) filter capacitor unit [AD-D011392] p 293 N85-15941 MILLER. J. Burbank's Blackbirds p 252 A85-22081 MILLER, K. A comparison of flight test and analytical techniques for boundary layer transition on a sailplane p 210 A85-19501 [AIAA PAPER 85-0075] MILLER. T. L. Analytical determination of propeller performance degradation due to ice accretion [AIAA PAPER 85-0339] p 264 A85-20867 MISHCHENKO, V. D. Development of asymptotic algorithms in the Polet package of applications programs p 233 A85-22366 MITCHELL, D. G. Mission-oriented requirements for updating MIL-H-8501. Volume 1: STI proposed structure [NASA-CR-177304-VOL-1] p 271 N85-16877 Mission-oriented requirements for updating MIL-H-8501. Volume 2: STI background and rationale [NASA-CR-177304-VOL-2] p 271 N85-16878 MITCHELL, J. L. A method for determining mesoscale dynamic topography p 300 N85-17506 [AD-D011412] MIYAI, Y. An analysis of the flow past an S-shaped rotor by discrete p 206 A85-19405 vortex model MODARRESS, D. Tomographic reconstruction of three-dimensional flow over airfoils [AIAA PAPER 85-0479] p 225 A85-19776 MOELLENSTAEDT, W. Investigations of the longitudinal flow in corner configurations in the hypersonic regime. II - Corners between swept wedges p 232 A85-22146 MOHN J. H. Improvement of the corrosion resistance of turbine

engine bearings p 265 N85-15731 [AD-A147430] MOITRA, A.

Numerical solution of the Euler equations for high-speed, blended wing-body configurations [AIAA PAPER 85-0123]

p 211 A85-19534 MOM, A. J. A.

Overview of the AGARD SMP activities on turbine engine materials technology in the 1972 - 1982 period p 266 N85-15738

MONKEL A. Functional built-in-test in a pipelined image processo p 202 N85-16740

MOOK, D. T. Subsonic wing rock of slender delta wings p 214 A85-19582 [AIAA PAPER 85-0198] Application of continuous vorticity panels to general unsteady two-dimensional lifting flows

p 217 A85-19633 [AIAA PAPER 85-0282] MOORE, A. L. The Western Aeronautical Test Range of NASA Ames

Research Center [AIAA PAPER 85-0316] p 275 A85-19678

MOORE, C. B. A study of the effects of triggered lightning [AD-A148296] p 300 p 300 N85-17494

MOORE, J. C. The challenge from ceramics to metals in the gas turbine nd related areas p 280 A85-20150 and related areas

MORAN, K. M. Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems [NASA-CR-174271] p 242 N85-15701

MORINAGA. T. Review of the origin of Japanese Industrial Standard

p 280 A85-20545 MORISSET, J.

The most spectacular equipment - ETW p 276 A85-21422

MORRISON, K. M.

Some characteristics of automotive gasolines and their performance in a light aircraft engine p 283 N85-15919

[FAA-CT-84-12] MORTON, J.

Proceedings of the International Conference and Exposition on Structural Impact and Crashworthiness p 242 N85-15703 [AD-A147845]

MUCK. K. C.

Structure of the wall pressure fluctuations in a shock-induced separated turbulent flow p 214 A85-19571 [AIAA PAPER 85-0179]

MUELLER, J. Microprocessor control of turboprop engines

p 263 A85-19877 MUKHERJEE, A.

A theoretical study of stability of a rigid rotor under the influence of dilute viscoelastic lubricants [ASME PAPER 84-TRIB-17] p p 289 A85-21278

MULLER, G. L. Three-dimensional inviscid flow analysis of turbofan forced mixers

- [AIAA PAPER 85-0086] p 210 A85-19510 MUNSON, H. E.
- Improvement of the corrosion resistance of turbine ngine bearings [AD-A147430] p 265 N85-15731
- MURAMOTO, K. K. Analytical modeling of circuit aerodynamics in the new
- NASA Lewis wind tunnel [NASA-TM-86912] p 234 N85-15688 MURDOCK, J. E., III
- Report from the United States of America p 307 A85-21942
- MURMAN, E. M. Three-dimensional inviscid flow analysis of turbofan forced mixers
- [AIAA PAPER 85-0086] p 210 A85-19510 Solution method for a hovering helicopter rotor using the Euler equations [AIAA PAPER 85-0436] p 223 A85-19749
- MURPHY, W. R. Computational aerodynamic design of the Gulfstream
- IV wing [AIAA PAPER 85-0427] p 223 A85-19742
- MURTHY, S. V. On boundary layer transition in high-subsonic and
- transonic flow under the influence of acoustic disturbances and free-stream turbulence [AIAA PAPER 85-0082] p 210 A85-19508

MYERS, L. P. Predicted performance benefits of an adaptive digital

- engine control system on an F-15 airplane p 263 A85-19801 [AIAA PAPER 85-0255]
- Predicted performance benefits of an adaptive digital engine control system of an F-15 airplane

[NASA-TM-85916] p 265 N85-15729

Ν

NABAR, W. V.

- Influence of blowing rate and injection angle on the performance of a film-cooled blade p 265 A85-22231 NAFTEL. P. B.
- The Mission Oriented Terminal Area Simulation (MOTAS) [AIAA PAPER 85-0308] p 274 A85-19655
- NAGAMATSU, H. T.
- Supercritical airfoil drag reduction by passive shock wave/boundary layer control in the Mach number range .75 to .90
- [AIAA PAPER 85-0207] p 215 A85-19591 Critical layer concept relative to hypersonic boundary

laver stability [AIAA PAPER 85-0303] p 219 A85-19652 NAGATA, J. I.

Preliminary airworthiness evaluation AH-1S (MC) helicopter with external fuel tanks installed [AD-A148091] p 258 N85-16865 NAKAGAWA, T.

- Application of laser interferometry to density p 206 A85-19406 measurements in free jets NAKAHASHI, K.
- A three-dimensional adaptive grid method [AIAA PAPER 85-0486] p 225 p 225 A85-19783
- NAKAMICHI, J. An improved version of the LTRAN2 for high frequency
- domain p 205 A85-19401 NAKATANI H An analysis of the flow past an S-shaped rotor by discrete
- vortex model p 206 A85-19405 NAKAYA, H. Drag of the fundamental shapes of parachutes
- p 231 A85-20998
- NAKAYAMA, A. Measurements of separating boundary layer and wake of an airfoil using laser Doppler velocimetry [AIAA PAPER 85-0181] p 214 A85-19572
- NANDANAN, M. Design of lifting symmetric supercritical airfoils

p 233 A85-22228

An incremental block-line-Gauss-Seidel method for the Navier-Stokes equations [AIAA PAPER 85-0033] o 207 A85-19470 NÁUMOV, B. N. Some problems in the development of CAD systems p 200 A85-20466 NAUMOVA, M. I. Determination of the optimal parameters of aircraft structural elements in the form of sandwich plates and shallow shells with a honeycomb filler o 287 A85-20452 NAYFEH. A. H. Subsonic wing rock of slender delta wings [AIAA PAPER 85-0198] p 214 p 214 A85-19582 NAZARETIAN, R. ONERA - The aeronautics supercomputer is put into p 302 A85-22274 service NAZAROV. A. P. Combat aircraft: Flight vehicles, power plants, and their naintenance p 199 A85-19812 maintenance NAZMY. M. Y. Experiences with the material bevaviour and high temperature low cycle fatigue life prediction of the IN 738 blading alloy p 292 N85-15746 NEARY, M. D. A longitudinal stability augmentation system for a tilt rotor aircraft [AIAA PAPER 85-0072] p 268 A85-19498 NEELY, G. M. Accelerated convergence for incompressible flow calculations [AIAA PAPER 85-0058] p 209 A85-19489 NÈJAD. A. S.

NAPOLITANO, M.

Computation of recirculating compressible flow in axisymmetric geometries [AIAA PAPER 85-0185] p 286 A85-19575

NELSON, R. C. Flow visualization of high angle of attack vortex wake structures

[AIAA PAPER 85-0102] p 286 A85-19520 NESTEROV, A. A.

Effect of the arrangement of apertures on the gain coefficient during asymmetric gas injection into a Laval p 229 A85-20562 nozzie NEUHART, D.

Vortex research facility improvements and preliminary density stratification effects on vortex wakes p 209 A85-19482 [AIAA PAPER 85-0050]

NEUMAN, F.

Calculation of the exchange ratio for the Adaptive Maneuvering Logic program [AIAA PAPER 85-0311]

p 199 A85-19658 NEUMANN, G. W.

A weapon system design approach to diagnostics p 203 N85-16752

NEUNABER, R.

Operational loads data evaluation for individual aircraft fatigue monitoring p 253 N85-15669 NEWMAN, J. S.

- Noise measurement flight test: aerospatiale AS-355F TwinStar helicopter Data-analyses
- [AD-A147497] p 305 N85-16595 Noise measurement flight test for Boeing Vertol 234/CH 47-d helicopter: Data/analyses
- p 306 N85-17670 [AD-A148172] Noise measurement flight test: Data-analyses

Aerospatiale AS 350D AStar helicopter [AD-A148496] p 306 N85-17672

- Noise measurement flight test: Data-analyses, Sikorsky S-76A helicopter
- [AD-A148525] p 306 N85-17673 NEWSOME, R. W.
 - A comparison of Euler and Navier-Stokes solutions for supersonic flow over a conical delta wing [AIAA PAPER 85-0111] p 2 p 210 A85-19526
- NICHOLAS, T.

Cumulative damage modeling of fatigue crack growth p 267 N85-15741 NIELSEN, J. N.

- Circulation control airfoils Past, present, future
- [AIAA PAPER 85-0204] p 215 A85-19588 Arrays for minimum wave drag of bodies of revolution p 249 A85-19758 [AIAA PAPER 85-0449]
- Prediction of cruciform all-movable control characteristics at transonic speeds
- (AD-A147291) p 239 N85-16832 NISHIDA, M.
- Application of laser interferometry to density measurements in free jets p 206 A85-19406 NORMENT, H. G.

Three-dimensional airflow and hydrometeor trajectory alculation with applications

[AIAA PAPER 85-0412] p 222 A85-19733

NORTHAM, G. B.

NORTHAM, G. B.

- Langley Mach 4 scramjet test facility [NASA-TM-86277] p 278 N85-16883
- NOVITSKII, V. V. Loading characteristics of VTOL aircraft and their effect
- on the remaining life of the aircraft p 250 A85-20469 NUMBERGER, K.
- Experience in using on-aircraft software for testing integrated systems p 302 N85-16747

0

- OATES, G. C. An experimental investigation of the mixing of co-annular swirling flows
- swirling flows [AIAA PAPER 85-0186] p 230 A85-20862 OBAYASHI, S.
- Computation of unsteady shock-induced vortex separation [AIAA PAPER 85-0183] p 214 A85-19573
- OBERKAMPF, W. L. Drag prediction for projectiles and finned bodies in
- incompressible flow [AIAA PAPER 85-0104] p 230 A85-20854 OGLE. P.
- Sikorsky composite rotor hub development
- p 251 A85-21381 OKAMOTO. S.
- Theoretical study of blockage effect of wind-tunnel wall on wake of two-dimensional flat plate normal to plane wall p 272 A85-19402 Experimental investigation of blockage effect of upper
- wall of wind-tunnel of wake of two-dimensional flat plate normal to plane boundary p 272 A85-19403 OKAMOTO. T.
- Theoretical study of blockage effect of wind-tunnel wall on wake of two-dimensional flat plate normal to plane wall p 272 A85-19402 OKIISHI, T. H.
- An experimental investigation of stator/rotor interaction influence on multistage compressor rotor flow [AIAA PAPER 85-0009] p 206 A85-19455
- OLLIVIER, J. F. A sensor for detection of unsteady distortion maxima
- in air intakes [ONERA, TP NO. 1984-148] p 205 A85-19262 OLSEN. J. J.
- Optimum performance parameters for ski-jump operations of USAF fighter aircraft
- [AD-A148532] p 258 N85-16867 ONO, K.
- Numerical study on the dynamic stall process of a NACA 0012 airfoil [AIAA PAPER 85-0128] p 212 A85-19539
- ORD, G. Air traffic management concepts for the UK in the 1990's:
- A review of recent RSRE work [AD-A147850] p 246 N85-16853
- ORLINO, D. G. Fabrication and assembly of composite rear fuselage (CRF) tooling and manufacturing for the UH-60 helicopter p 200 A85-21394
- ORLOV, IU. F. Development of asymptotic algorithms in the Polet package of applications programs p 233 A85-22366 ORMSBEE, A. I.
- A class of airfoils having finite trailing edge pressure anatients
- [AIAA PAPER 85-0206] p 215 A85-19590 OSKAM, B.
- Recent advances in computational methods to solve the high-lift multi-component airfoit problem p 236 N85-16774
- OSTAPENKO, N. A. Conical bodies with a star-shaped transverse cross section, having a reserve of static stability p 229 A85-20557
 - Ρ
- PALMOV, V. A.

B-12

- Theory of vibration conduction as a method for calculating the vibration of complex structures p 287 A85-20454
- PANCHENKO, V. N. Calculation of friction and heat transfer in turbulent flow
- of a compressible gas in a plane duct p 291 A85-22114 PANCHENKOV. A. N.
- III-posed problems in perturbation theory (Asymptotic methods of mechanics) p 233 A85-22364 Development of asymptotic algorithms in the Polet package of applications programs p 233 A85-22366

- PANG, M.
- Experimental investigation of backswept centrifugal compressor impeller. 1 p 264 A85-20243 PAQUIN. A.
- TUTOR (CL-41A) tail flight load survey p 254 N85-15678 PARKS, E. K.
- Identification of vortex-induced clear air turbulence using airline flight records p 299 A85-21843
- PARR, C. H. Flexible matrix composites applied to bearingless rotor systems p 281 A85-21389
- PARTON, V. Z. Current problems in aviation science and technology
- p 199 A85-20451 PATTERSON, D. J.
- Some characteristics of automotive gasolines and their performance in a light aircraft engine [FAA-CT-84-12] p 283 N85-15919
- PAVLENKO, V. F. Combat aircraft: Flight vehicles, power plants, and their maintenance p 199 A85-19812
- Loading characteristics of VTOL aircraft and their effect on the remaining life of the aircraft p 250 A85-20469 PAVLIKEVICH, B. E.
- The effect of changes in the angle of incidence in the event of a richochet at a float step
- [RAE-TRANS-2120] p 255 N85-15712 PAYSON, R. P.
- A bird strike handbook for base-level managers [AD-A147928] p 293 N85-16008 PEAVIN. R. C.
- Atmospheric electricity hazards to aircraft operation [AIAA PAPER 85-0013] p 247 A85-19457 PECKHAM, D. H.
- Investigations into the effects of scale and compressibility on lift and drag in the RAE 5m pressurized low-speed wind tunnel p 236 N85-16773 PELLETIER, D. H.
- A Navier-Stokes calculation of 3-D, turbulent flow near a propeller in a shear flow [AIAA PAPER 85-0365] p 220 A85-19698
- PERKINS, J. N. The design and testing of several joined wing RPV's
- [AIAA PAPER 85-0275] p 248 A85-19627 PETIAU, C.
- Aeroelastic analysis and the identification of flight loads p 254 N85-15679 PETRIE, H. L.
- A study of compressible turbulent free shear layers using laser Doppler velocimetry [AIAA PAPER 65-0177] p 213 A85-19569
- [AIAA PAPER 85-0177] p 213 A85-19569 PHILLIPS, J. D. Downwash in the plane of symmetry of an elliptically
- loaded wing [NASA-TP-2414] p 235 N85-15693
- PHILLIPS, P. S. Potential flow calculations and preliminary wing design
- in support of an NLF variable sweep transition flight experiment [AIAA PAPER 85-0426] p 248 A85-19741
- PIAT, J. F.
 - The accuracy of trials with powered 1/2 models in the S2MA wind tunnel [ONERA, TP NO. 1984-156] p 272 A85-19270
 - PINCKERT, R. E. The F-15 flight loads tracking program
- p 253 N85-15666 PINKUS, O.
- Effects of turbulence and viscosity variation on the dynamic coefficients of fluid film journal bearings [ASME PAPER 84-TRIB-8] p 289 A85-21283
- [ÁSME PAPER 84-TRIB-8] p 289 Å85-21283 PLEIJSIER, A. Functional built-in-test in a pipelined image processor
- PUnctional built-in-test in a pipelined image processor p 202 N85-16740 POKORNY. J.
- History of the development and manufacture of flight simulators in Czechoslovakia and the rest of the world p 275 A85-19878
- POLIAKHOV, N. N.
 - Harmonic oscillations of a rectangular wing with a circulation variable over the span p 231 A85-21656 POLITOVICH, M. K.
 - Icing conditions encountered by a research aircraft p 299 A85-21141 POOLE, W. E.
 - Improvement of the corrosion resistance of turbine engine bearings
- [AD-A147430] p 265 N85-15731 PORCHERON, B. Detailed study of the flow around a multi-element airfoil.
- Comparison with calculations p 236 N85-16775 PORODENKO, V. V.
- Effect of the arrangement of apertures on the gain coefficient during asymmetric gas injection into a Laval nozzle p 229 A85-20562

POTAPCZUK, M. G.

- Progress in development of a Navier-Stokes solver for evaluation of iced airfoil performance [AIAA PAPER 85-0410] p 222 A85-19731 **POVINELLI, L. A.** Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) [AIAA PAPER 85-0379] p 275 A85-19709
- Analytical modeling of circuit aerodynamics in the new NASA Lewis wind tunnel
- [NASA-TM-86912]
 p 234
 N85-15688

 Analytical and physical modeling program for the NASA
 Lewis Research Center's Altitude Wind Tunnel (AWT)
 [NASA-TM-86919]
 p 276
 N85-15757
- POWELL, R. W.
- Effect of aerodynamic and angle-of-attack uncertainties on the May 1979 entry flight control system of the Space Shuttle from Mach 8 to 1.5 [NASA-TP-2365] p 280 N85-15778
- POWELL, S. H.
- Polylimide protective coatings for 700 deg service p 282 A85-21527 PRESSON. E.
- Software test handbook: Software test guidebook, volume 2
- [AD-A147289]
 p 303
 N85-17578

 PRIESTLEY, R. N.
 Integrated navigation
 p 245
 A85-21461

 PRUSZYNSKI, C. J.
 J.
 J.
 J.
- Atmospheric propagation losses for long-range airborne radar systems analysis
- [AIAA PAPER 85-0267] p 244 A85-19620 PUCCETTI, G.
- Tactical HF communication for military helicopters using the NVIS mode p 297 N85-16807 PIII LIAM T.H.
- Euler computations of AGARD Working Group 07 airfoil test cases
- [AIAA PAPER 85-0018] p 229 A85-20851 Navier-Stokes computations for exotic airfoils
- [AIAA PAPER 85-0109] p 230 A85-20855 Recent improvements in efficiency, accuracy, and convergence for implicit approximate factorization algorithms
- (AIAA PAPER 85-0360) p 230 A85-20868 Artificial dissipation models for the Euler equations (AIAA PAPER 85-0438) p 231 A85-20870 PURVIS. W. J.
 - Evaluation of jet fuel deposit kinetics. Lot 4
- [AD-A147196] p 284 N85-15922

Q

- QIAN, H. A method for calculating the performance of ejector nozzles p 287 A85-20232 QUAN E. E. JR.
- The Cockpit Display of Traffic Information and the Threat Alert and Collision Avoidance System Integration - A review p 259 A85-21559
- QUARTUCCIO, J. S-3A ballast block final design and engineering tests [AD-A147685] p 243 N85-16842 QUAST, A.

Pneumatic turbulators: A device for drag reduction at

Reynolds numbers below 5 million p 257 N85-16791

R

Integrated digital/electric aircraft concepts study

NSWC hypervelocity wind tunnel No. 9 [AIAA PAPER 85-0226] p

Improvements in low Reynolds number testing in the

A relaxation approach to patched-grid calculations with

An implicit, conservative, zonal-boundary scheme for

Aircraft turbojet engine modeling using artificial

Universal matrices to obtain thermal load vectors for

the family of anisotropic plane triangular finite elements

Design of lifting symmetric supercritical airfoils

p 257 N85-16861

p 274 A85-19602

p 218 A85-19644

p 226 A85-19785

p 263 A85-19616

p 233 A85-22228

p 291 A85-22232

RADOVCICH, N. A.

RÀGSDALE, W. C.

RAI, M. M.

[NASA-CR-38411

the Euler equations

RAJAGOPALAN, R.

RÀMASWAMY, M. A.

RAMESH BABU, C.

[AIAA PAPER 85-0295]

AIAA PAPER 85-0488]

intelligence technique

[AIAA PAPER 85-0253]

Euler equation calculations

PERSONAL AUTHOR INDEX

•		
RAMOS, J. I.		
Swirting flow in a research combus	itor	AGE 01000
RAMSAY S. M.	p 283	A00-21803
Three-dimensional inviscid flow	anatysis	of turbofan
forced mixers	,	
[AIAA PAPER 85-0086]	p 210	A85-19510
RAO DASARY, A. M.		
A theoretical study of stability of a	rigid roto	or under the
Influence of dilute viscoelastic lubrica	ints	405 04070
RAD G N	p 289	A85-212/8
Influence of blowing rate and init	action an	ale on the
performance of a film-cooled blade	p 265	A85-22231
RAO, S. S.	r	
Optimization of airplane wing strue	ctures un	ider landing
loads	p 252	A85-22005
RATCLIFF, R. E.		
Airworthiness and flight charai	teristics	test of the
HC-12D Guardrali V	- 050	NOE 10004
BAUSCHER F	þ 200	1405-10004
Structural flight load measurement	nt demor	stration of
structural integrity	p 254	N85-15670
RAY, R. J.	•	
Predicted performance benefits of	if an ada	ptive digital
engine control system on an F-15 ai	rplane	
[AIAA PAPER 85-0255]	p 263	A85-19801
Predicted performance benefits of	n an ada	ptive digital
INASA TM BEG161	plane	N85 15700
	P 205	100-10/29
Tests of air inlets on civil aircraft		
[ONERA, TP NO. 1984-1571	p 272	A85-19271
REDDICK, H. K., JR.		
US Army helicopter operational fli	ght loads	
	p 254	N85-15675
REDDY, K. R.		
Calculation of the velocity field gen	erated by	a helicopter
main and tail rotors in hover		
[AD-A14//31]	p 239	N85-16833
Ground interference effects on si	hoonio d	honomia stall
in pitch and plunge	n 221	AR5-218/1
REED. H. L.	P 201	A03-21041
Disturbance-wave interactions in	flows wi	th crossflow
[AIAA PAPER 85-0494]	p 226	A85-19788
REID, L.		
Analytical and physical modeling p	rogram f	or the NASA
Lowis Research Center's Altitude	-	
	Wind T	unnel (AWT)
[AIAA PAPER 85-0379]	Wind To p 275	unnel (AWT) A85-19709
[AIAA PAPER 85-0379] Analytical and physical modeling p	Wind To p 275 program fo Wind To	unnel (AWT) A85-19709 or the NASA
[AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA_TM_86910]	Wind To p 275 program fo Wind To p 276	unnel (AWT) A85-19709 or the NASA unnel (AWT)
[AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID. L. D.	Wind To p 275 program fo Wind To p 276	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757
[AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon	Wind To p 275 rogram fo Wind To p 276 g wind co	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757
[AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths	Wind To p 275 program f Wind To p 276 g wind co p 245	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838
[AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J.	Wind To p 275 program f Wind To p 276 g wind co p 245	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838
[AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p	Wind To p 275 rogram f Wind To p 276 g wind co p 245 rogram f	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA
[AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude	Wind To p 275 rogram fo Wind To p 276 g wind co p 245 wogram fo Wind To p 245	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT)
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] 	Wind Ti p 275 program f Wind Ti p 276 g wind ca p 245 wrogram f Wind T p 275	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] 	Wind Ti p 275 program f Wind Ti p 276 g wind ca p 245 word T p 275 program f Wind T	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-869191] 	Wind Tri p 275 rrogram f Wind Tr p 276 g wind cr p 245 rrogram f Wind T p 275 rrogram f Wind T p 275	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. 	Wind Tri p 275 program f Wind Tr p 276 g wind cri p 245 wogram f Wind T p 275 program f Wind T p 276	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) N85-15757
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of 	Wind Tri p 275 program fr Wind Tri p 276 g wind cri p 275 rrogram fr Wind T p 275 rrogram fr Wind T p 276 warning	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757
[AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of	Wind Tr p 275 program fr Wind Tr p 276 g wind ce p 245 rogram fr Wind T p 275 rogram fr Wind T p 276 warning p 297	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle w 	Wind Tr p 275 program fr Wind Tr p 276 g wind cr p 245 wogram fr Wind T p 275 rogram fr Wind T p 276 warning p 297	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle w REPPERGER, D. W. Biodynamic resistant control stick 	Wind Tr p 275 program fr Wind Tr p 276 g wind cc p 245 Wind T p 275 p 275 rrogram fr Wind T p 276 Wind T p 276	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) N85-15757 N85-16810
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] 	Wind Tr p 275 program f Wind Tr p 276 g wind cc p 245 wogram f Wind T p 275 rogram f Wind T p 276 varning p 297 p 259	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810
[AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle w Biodynamic resistant control stick [AD-D011380] RETH, R. D. V.	Wind Tr p 275 irogram fr Wind Tr p 276 g wind cr p 245 word an fr Wind T p 275 irogram fr Wind T p 276 wind g p 297 p 259	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle w REPPERGER, D. W. Biodynamic resistant control stick (AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n nelationes for pilotion and sighting 	Wind Ti p 275 rogram fi Wind Ti p 276 g wind Ci p 245 rogram fi Wind T p 276 rogram fi Wind T p 276 varning p 297 p 259 nast moore	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 inted sensor
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle w REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters 	Wind Tr p 275 rogram fr Wind Tr p 276 g wind or p 245 wogram fr Wind T p 275 rogram fr Wind T p 275 rogram fr Wind T p 275 p 259 p 259 hast mou integrat o 260	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 inted sensor ed in future
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle w REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters 	Wind Tr p 275 rogram fr Wind Tr p 276 g wind cr p 245 word Tr p 275 rogram fr Wind T p 275 rogram fr Wind T p 275 rogram fr Wind T p 275 p 259 p 259 p 259 nast mou integrat p 260	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 inted sensor ed in future N85-16808
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle to Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r 	Wind Ti p 275 rogram f Wind Ti p 276 g wind cc p 245 rogram f Wind T p 275 rogram f Wind T p 275 rogram f Wind T p 276 p 245 rogram f Wind T p 276 rogram f Wind T p 276 rogram f Wind T p 276 rogram f Wind T p 276 rogram f Wind Ti p 276 rogram f Wind C p 245 rogram f Wind Ti p 276 rogram f P 259 rogram f P 260 rogram f P 260 rogram f P 259 rogram f P 260 rogram f P	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 unted sensor ed in future N85-16808 from aircraft
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of Biodynamic resistant control stick [AD-011380] RETH, R. D. V. Evaluation of nose, roof, and m platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui 	Wind Ti p 275 rogram fi Wind Ti p 276 g wind cc p 245 rogram fi Wind T p 276 rogram fi Wind T p 276 rogram fi Wind T p 276 varning p 297 p 259 nast mou integrati p 259 eduction dized bee	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16808 N85-15721 unted sensor N85-15608 from aircraft d filter
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle w REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] 	Wind Ti p 275 rogram fi Wind Ti p 276 g wind cr p 245 wogram fi Wind T p 275 rogram fi Wind T p 275 rogram fi Wind T p 276 varning p 297 p 259 vast mou integrati p 260 eduction dized bec p 278	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 unted sensor ed in future N85-16886 from aircraft filter N85-16886
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of REPPERGER, D. W. Biodynamic resistant control stick (AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. 	Wind Tr p 275 rogram fr Wind Tr p 276 g wind cr p 245 wogram fr Wind T p 275 rogram fr Wind T p 275 rogram fr Wind T p 275 p 259 p 257 p 276 p 275 p 276 p 276 p 276 p 276 p 276 p 275 p 276 p 277 p 276 p 260 p 277 p 276 p 276 p 276 p 276 p 276 p 276 p 276 p 277 p 276 p 276 p 277 p 277 p 276 p 277 p 277 p 277 p 276 p 277 p 2777 p 277 p 277 p 277 p 277 p 277 p 277 p 277 p 277 p 277 p	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15770 N85-16810 N85-15721 unted sensor ed in future N85-16808 from aircraft d filter N85-16886
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for 	Wind Ti p 275 rogram f Wind Ti p 276 g wind cc p 245 rogram f Wind T p 275 rogram f Wind T p 275 rogram f Wind T p 275 rogram f Wind T p 276 varning p 297 p 259 nast mou integrat. p 260 eduction dized bec p 278 helicopi	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15757 N85-16810 N85-15721 unted sensor ed in future N85-16808 from aircraft d filter N85-16886 ter fuselage
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle to Biodynamic resistant control stick (AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and m platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure BICHARDSON - I 	Wind T: p 275 rogram f Wind Ti p 276 g wind cc p 245 rogram f Wind T p 276 rogram f Wind T p 275 rogram f Wind T p 276 varning p 297 p 259 p 250 p 259 p 250 p 276 p 277 p 276 p 277 p 276 p 276 p 276 p 276 p 276 p 252	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 inited sensor ed in future N85-15721 sensor ad in future N85-16808 from aircraft d filter N85-16886 ter fuselage A85-21396
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of Biodynamic resistant control stick (AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui (AD-A148600) RICH, M. J. Composite curved frames for structure RICHARDSON, J. 	Wind Ti p 275 rogram fr Wind Ti p 276 g wind cr p 245 wogram fr Wind T p 275 rogram fr Wind T p 275 rogram fr Wind T p 276 varning p 297 p 259 nast mou integrat p 260 eduction dized bec p 278 helicopp	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 N85-15721 N85-15721 or the sensor ed in future N85-16808 from aircraft d filter N85-16886 ter fuselage A85-21396
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle w REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow 	Wind Tr p 275 rogram fr Wind Tr p 276 g wind or p 245 wogram fr Wind T p 275 rogram fr P 297 p 259 rogram fr P 250 rogram fr P 250 rogram fr P 250 rogram fr P 250 rogram fr P 250 rogram fr P 250 rogram fr P 258 rogram fr P	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 inited sensor ed in future N85-16806 from aircraft filter N85-16886 ter fuselage A85-21396
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow [AIAA PAPER 85-0329] 	Wind Tri p 275 rogram fr Wind Tri p 276 g wind cri p 245 wogram fr Wind T p 275 rogram fr Wind T p 275 rogram fr Wind T p 275 p 259 p 259 p 259 p 259 p 259 p 259 p 250 eduction dized bec p 278 helicopi p 252 than and an p 263	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-16810 N85-16810 N85-15721 unted sensor ed in future N85-16808 from aircraft d filter N85-16886 ter fuselage A85-21396 alysis in cold A85-19671
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle to Biodynamic resistant control stick (AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow (AIAA PAPER 85-0329] RICHARDSON, M. A. 	Wind Ti p 275 rogram fi Wind Ti p 276 g wind cc p 245 rogram fi Wind T p 276 rogram fi Wind T p 275 rogram fi Wind T p 276 varning p 297 p 259 p 250 eduction dized bec p 278 helicopp p 252 nt and an p 253	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 N85-15721 inited sensor ed in future N85-16808 from aircraft d filter N85-16886 ter fuselage A85-21396 alysis in cold A85-19671
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of [NASA-TM-86919] REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and m platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow [AIAA PAPER 85-0329] RICHARDSON, M. A. Integrated control and display s 	Wind Ti p 275 rogram fr Wind Ti p 276 g wind cc p 245 wogram fr Wind T p 276 worgram fr Wind T p 275 rogram fr Wind T p 275 rogram fr Wind T p 276 varning p 297 p 259 nast mou integrati p 260 eduction dized bec p 278 helicopi p 252 nt and an p 263 ystems fr	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 N85-15721 N85-15721 or the unit of filter N85-16808 from aircraft f filter N85-16886 ter fuselage A85-21396 allysis in cold A85-19671 or helicopter
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of REPPERGER, D. W. Biodynamic resistant control stick (AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow [AIAA PAPER 85-0329] RICHARDSON, M. A. Integrated control and display s battlefield mission management 	Wind Tr p 275 rogram f Wind Tr p 276 g wind cr p 245 wogram f Wind T p 275 rogram f Wind T p 275 rogram f Wind T p 275 rogram f Wind T p 275 rogram f 275 p 259 nast mou integrat: p 260 eduction dized bec p 278 helicoppi p 252 nt and an p 263 ystems f p 260	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-15709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 inited sensor ed in future N85-16808 from aircraft filter N85-16886 ler fuselage A85-21396 ualysis in cold A85-19671 or helicopter N85-16805
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow [AIAA PAPER 85-0329] RICHARDSON, M. A. Integrated control and display s battlefield mission management RICHTER, G. P. 	Wind Tr p 275 rogram f Wind Tr p 276 g wind cc p 245 rogram f Wind T p 276 rogram f Wind T p 275 rogram f Wind T p 275 rogram f Wind T p 275 rogram f Wind T p 276 varning p 297 p 259 nast mou integrat p 260 eduction dized bec p 278 helicopi p 252 nt and an p 263 ystems f p 263	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15757 N85-16810 N85-15721 unted sensor ed in future N85-16808 from aircraft filter N85-16886 ter fuselage A85-21396 alysis in cold A85-19671 or helicopter N85-16805
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of Biodynamic resistant control stick (AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and m platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. SFRJ simulator results - Experime flow [AlAA PAPER 85-0329] RICHARDSON, M. A. Integrated control and display s battlefield mission management RICHARDSON, M. A. 	Wind Ti p 275 rogram f Wind Ti p 276 g wind cc p 245 rogram f Wind T p 276 rogram f Wind T p 275 rogram f Wind T p 276 varning p 297 p 259 p 259 p 259 p 259 p 259 p 259 p 259 p 259 contemp 260 eduction dized bec p 278 helicopp p 252 nt and an p 263 ystems f p 260 t test pr	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15770 N85-16810 N85-15721 inted sensor N85-15721 inted sensor N85-15721 inted sensor N85-15721 attract sensor N85-15721 inted sensor N85-15886 from aircraft d filter N85-15886 ter fuselage A85-21396 attract sensor N85-16805 intelicopter N85-16805 ogram: An
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle w REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow [AIAA PAPER 85-0329] RICHARDSON, M. A. Integrated control and display s battlefield mission management RICHTER, G. P. The UH-1H helicopter icing fligh overview [NAA.TMAR69251 	Wind Ti p 275 rogram fr Wind Ti p 276 g wind cc p 245 wogram fr Wind T p 276 word and T p 275 rogram fr Wind T p 275 rogram fr p 259 rogram fr p 250 rogram fr p 260 rogram	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 N85-15721 N85-15721 N85-15721 or the united sensor ed in future N85-15808 from aircraft d filter N85-16808 ter fuselage A85-21396 allysis in cold A85-19671 or helicopter N85-16805 ogram: An
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle v REPPERGER, D. W. Biodynamic resistant control stick (AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow [AIAA PAPER 85-0329] RICHARDSON, M. A. Integrated control and display s battlefield mission management RICHTER, G. P. The UH-11H helicopter icing fligh overview [NASA-TM-86925] BICKI Y F. J 	Wind Tr. p 275 rogram fr Wind Tr. p 276 g wind or p 276 g wind or p 275 rogram fr Wind Tr. p 276 varning p 259 hast moutintegrature p 260 eduction dized beck p 278 helicoppi p 263 ystems fr p 260 at test pr p 242	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-15729 N85-16810 N85-16810 N85-15721 Inted sensor ed in future N85-16810 N85-15721 or helicopter A85-21396 alysis in cold A85-19671 or helicopter N85-16805 ogram: An N85-15702
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Euatiation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure [AIAA PAPER 85-0329] RICHARDSON, J. SFRJ simulator results - Experime flow [AIAA PAPER 85-0329] RICHARDSON, M. A. Integrated control and display s battlefield mission management RICHTER, G. P. The UH-1H helicopter icing fligh overview [NASA-TM-86925] RICKLEY, E. J. Noise measurement flight for 	Wind Ti p 275 rogram f Wind Ti p 276 g wind cc p 245 rogram f Wind T p 276 g wind cc p 245 rogram f Wind T p 275 rogram f Wind T p 275 rogram f Wind T p 276 varning p 297 p 259 p 250 p 250 p 250 p 260 p 242 p 252 p 260 p 252 p 250 p 252 p 250 p 252 p 252 p 252 p 252 p 252 p 252 p 253 p 255 p 2	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15777 N85-16810 N85-15721 inted sensor ed in future N85-15721 inted sensor ed in future N85-16808 from aircraft filter N85-16886 ter fuselage A85-21396 ialysis in cold A85-19671 or helicopter N85-15702
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle of Biodynamic resistant control stick (AD-D011380] RETH, R. D. V. Biodynamic resistant control stick (AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui (AD-A148600) RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow (AIAA PAPER 85-0329) RICHARDSON, M. A. Integrated control and display s battlefield mission management RICHTER, G. P. The UH-11 helicopter icing fligh overview [NASA-TM-86925] RICKLEY, E. J. Noise measurement flight te aerospatiale AS-355F TwinStar heli 	Wind Ti p 275 rogram fi Wind Ti p 276 g wind cd p 245 rogram fi Wind T p 276 rogram fi Wind T p 275 rogram fi Wind T p 275 rogram fi Wind T p 277 p 259 p 259 theter fi p 260 theter fi p 260 theter fi p 260 theter fi p 260 theter fi p 242 theter fi p 260 theter fi p 242 theter fi p 260 theter fi p 242 theter fi p 260 theter fi p 245 theter fi p 260 theter fi p 245 theter fi p 260 theter fi p 245 theter fi p 260 theter fi p 242 theter fi p 245 theter fi p 260 theter fi p 260 theter fi p 260 theter fi p 245 theter fi p 260 theter fi p 245 theter fi p 260 theter fi p 245 theter fi p 260 theter fi p 245 theter fi p 260 theter fi p 245 theter fi p 245 theter fi p 245 theter fi p 245 theter fi fi fi fi fi fi fi fi fi fi fi fi fi f	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15770 N85-16810 N85-16810 N85-15721 unted sensor N85-15721 inted sensor N85-15721 atter fuselage A85-21396 alysis in cold A85-19671 or helicopter N85-16805 ogram: An N85-15702 bata-analyses
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle w REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow [AIAA PAPER 85-0329] RICHARDSON, M. A. Integrated control and display s battlefield mission management RICHTER, G. P. The UH-1H helicopter icing fligh overview [NASA-TM-86925] RICKLEY, E. J. Noise measurement flight te aerospatiale AS-355F TwinStar heli [AD-A147497] 	Wind Timp 275 rogram fr rogram fr Wind Cimp 276 g wind Cimp 276 g wind Cimp 245 worgram fr Wind Timp 276 worgram fr Wind Timp 276 worgram fr Wind Timp 276 worgram fr P 259 warning p 297 p 259 warning p 297 p 250 eduction dized bec dized bec p 250 nt and an p 260 wattest pr p 260 wattest pr p 261 st: p 242 st: p 242 st: p 200	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 N85-16810 N85-15721 N85-16808 from aircraft d filter N85-16808 from aircraft d filter N85-16808 ter fuselage A85-21396 alysis in cold A85-19671 or helicopter N85-16702 tata-analyses N85-16595
 [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REID, L. D. Nonlinear simulation of flight alon curved glidepaths REINMANN, J. J. Analytical and physical modeling p Lewis Research Center's Altitude [AIAA PAPER 85-0379] Analytical and physical modeling p Lewis Research Center's Altitude [NASA-TM-86919] REMBOLD, B. LPI-radar for helicopter obstacle v REPPERGER, D. W. Biodynamic resistant control stick [AD-D011380] RETH, R. D. V. Evaluation of nose, roof, and n platforms for piloting and sighting, combat helicopters RICE, R. W. Laboratory simulation of smoke r engine test cell exhaust using a flui [AD-A148600] RICH, M. J. Composite curved frames for structure RICHARDSON, J. SFRJ simulator results - Experime flow [AIAA PAPER 85-0329] RICHARDSON, M. A. Integrated control and display s battlefield mission management RICHTER, G. P. The UH-11H helicopter icing fligh overview [NASA-TM-86925] RICKLEY, E. J. Noise measurement flight te aerospatiale AS-355F TwinStar heli [AD-A147497] 	Wind Tr p 275 rogram fr Wind Tr p 276 g wind co p 245 wogram fr Wind T p 275 rogram fr p 259 rast mou integratic p 260 eduction dized bee p 278 helicopi p 252 nt and an p 263 ystems fr p 260 t test pr p 252 nt and an p 263 ystems fr p 260 t test pr p 252 nt and an p 263 ystems fr p 260 t test pr p 259 rogram fr p 250 rogram fr p 259 rogram fr p 250 rogram fr p 250 rogram fr p 250 rogram fr p 260 rogram fr p 260 rogra	unnel (AWT) A85-19709 or the NASA unnel (AWT) N85-15757 ompensating A85-21838 or the NASA unnel (AWT) N85-15777 N85-16810 N85-16810 N85-16810 N85-15721 Inted sensor ed in future N85-15721 State and a sensor ed in future N85-16805 from aircraft f filter N85-16886 ter fuselage A85-21396 alysis in cold A85-19671 or helicopter N85-16605 ogram: An N85-15702 sata-analyses N85-16595

Aerospatiale AS 350D AStar helicopter	
Noise measurement flight test: Data-analyses, Sikorsky	
S-76A helicopter	
[AD-A148525] p 306 N85-17673	
Experimental and theoretical analysis of laminar	
separation bubbles	
[AIAA PAPER 84-2201] p 288 A85-20874	
Control system design language implementation of a	
gas turbine starting controller	
[AD-A147896] p 266 N85-15732	
Automatic briefing and mission management systems	
for battlefield support p 259 N85-16799	
ROBERTS, L.	
[AIAA PAPER 85-0004] p 206 A85-19452	
A zonal computational approach to thrust augmentor	
Optimization	
ROBERTS, T. W.	
Solution method for a hovering helicopter rotor using	
the Euler equations	
ROGERS, S. P.	
A Computer-generated topographic display system for	
navigation and mission planning in helicopters	
ROHLIK, H. E.	
Computational thermo-fluid dynamics contributions to	
advanced gas turbine engine design	
ROLLS, M. J.	
National airspace review: Airport radar service area	
operational confirmation report (DOT/FAA/AT-84/2) p 245 N85-15707	
ROMAN, A. P.	
Correlation and analysis of oil flow data for an	
air-breathing Missile model [AIAA PAPER 85-0452] D 224 A85-19761	
ROMERO, M. N.	
A Q-GERT network simulation model for examining	
pipeline time in the Navy's J-52 intermediate level jet	
[AD-A147269] p 201 N85-15663	
ROSCOE, D. V.	
analysis	
[AD-A146967] p 294 N85-16070	
ROSE, W. C.	
[AD-A146755] p 294 N85-16067	
ROSEN, B. S.	
Body flow field simulation and force/moment prediction	
[AIAA PAPER 85-0423] p 222 A85-19738	
ROSENBERG, K. W.	
I rends in digital flight control systems	
ROSENZWEIG, E. L.	
Repair of composites p 284 N85-17058	
A numerical simulation of the NEAC (National Full-scale	
Aerodynamics Complex) open-return wind tunnel inlet	
ROSS, M, L.	
Frequency response of a jet engine test facility air supply	
SYSTEM [ALAA PADER 85-0053] D 273 A85-19485	
ROTE, D. M.	
Impact of aircraft emissions on air quality in the vicinity	
of airports. Volume 3: Air quality and emission modeling needs	
[AD-A147951] p 299 N85-17435	
ROY, S. D.	
ine impact of integrated systems - The helicopter designer's viewpoint n 252 ASS-21467	
The design and development of an integrated core	
system for battlefield helicopters - p 260 N85-16811	
RUMBET, U. L. Evaluation of a stalled airfoil analysis program	
p 231 A85-21848	
RUMYNSKII, A. N.	
in problems of supersonic flow past segmental hordies	
p 227 A85-20025	
RUSTAN, P. L., JR.	
AIAA PAPER 85-0094] D 240 A85-19516	
RUTCHIK, W. L.	
integrated digital/electric aircraft concepts study	
[NASA-CR-3841] n 257 NR5_16961	

Noise measurement flight test:

SCHAEFER, M. K.

BUTHEREORD, D. A.

Data-analyses

The effect on software design of testing by symbolic p 303 N85-16750 execution

S

SAHU, J.

Nav	ier-Stokes com	putations of axi	isymr	netri	c transonic
flows	with a two-equa	tion model of t	urbule	ence	1
[AIAA	PAPER 85-037	3]	p 2	21	A85-19705
SĂITO,	К.		•		
Ал	experimental	investigation	of	an	unsteady

combusting flow in a pulse combustor [AIAA PAPER 85-0322] p 281 A85-20865 SAITO, S.

Application of an adaptive blade control algorithm to a lust alleviation system p 269 A85-20143 gust alleviation system SAKACH, R.

Director on institute's civil aviation projects

	p 204	N85-16764
SAKAMOTO, T.		

p 308 A85-21948 Report from Japan SAKURAI, T.

Turbo fluid machinery and diffusers [NASA-TM-77467] p 298 N85-17363 SALAS, M. D.

Euler calculations for multielement airfoils using Cartesian grids [AIAA PAPER 85-0291]

- p 218 A85-19641 Breakdown of the conservative potential equation [AIAA PAPER 85-0367] p 221 A85-19700
- A comparative study of the nonuniqueness problem of the potential equation
- [NASA-TP-2385] p 235 N85-15694 SALUJA, H. S.
- Advanced-composite joints and fittings for primary p 290 A85-21385 structural components SAMIMY. M.

A study of compressible turbulent free shear layers using laser Doppler velocimetry [AIAA PAPER 85-0177]

p 213 A85-19569 SAND. W. R.

loing conditions encountered by a research aircraft p 299 A85-21141 SANDNER, N.

Documentation and separate test program development is most important for test/maintenance

- p 203 N85-16745 SANKAR, N. L. Solution of the unsteady Euler equations for fixed and
- rotor wing configurations [AIAA PAPER 85-0120] p 211 A85-19531
- Numerical solution of unsteady viscous flow past rotor sections
- [AIAA PAPER 85-0129] p 212 A85-19540 Unsteady aerodynamics of an airfoil encountering a passing vortex
- [AIAA PAPER 85-0203] p 214 A85-19587 SANS, C.

Interest of internal bleed for a two-dimensional air intake operating in a wide Mach number range (1.8-3 plus) p 237 N85-16793

SARIC, W. S. Experiments on the stability of crossflow vortices in swept-wing flows [AIAA PAPER 85-0493]

- p 231 A85-20873 SARIPALLI, K. R.
- A novel experimental facility for conducting jet impingement studies related to VTOL aircraft [AIAA PAPER 85-0052] p 209
- p 209 A85-19484 SARKOS, C. P. Evaluation of aircraft interior panels under full-scale
- cabin fire test conditions [AIAA PAPER 85-0393] p 240 A85-19719
- Preliminary evaluation of an improved flammability test method for aircraft materials
- p 242 N85-16840 [FAA-CT-84-22] SARPKAYA, T.
 - Optimized discrete-singularity representation of axisymmetric bodies
- [AIAA PAPER 85-0284] p 218 A85-19635 Free surface scars and striations due to trailing vortices
- generated by a submerged lifting surface [AIAA PAPER 85-0445] p 286 A85-19754

SATRAN, D. R. Vortex research facility improvements and preliminary

density stratification effects on vortex wakes

[AIAA PAPER 85-0050] p 209 A85-19482 SAWADA, T.

Off-design point characteristics of the precooled gas turbine cycle with liquefied hydrogen as fuel p 289 A85-20884

SCHAEFER, M. K.

Optimal maintenance center inventories for fault-tolerant repairable systems p 301 A85-21548

SCHETZ, J. A.

SCHETZ, J. A

A Navier-Stokes calculation of 3-D, turbulent flow near a propeller in a shear flow

- [AIAA PAPER 85-0365] p 220 A85-19698 Experimental results for Reynolds number effects on p 232 A85-21849
- trailing vortices SCHIMKE, S. M.
- Some important problems in unsteady boundary layers including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies
- p 294 N85-16069 [AD-A146964] Some important problems in unsteady boundary layers including separation. 1: Nature of singularity on oscillating airfoils
- p 294 N85-16087 AD-41478971 SCHIMMEL D. E. Impact tests of automatic lap belt configurations
- AD-A148034] p 243 N85-16844 SCHMID, R.
- The division of tasks in modern air transport and its effect on the liability of the air carrier - The concept 'agents' in the so-called Warsaw Convention
- p 307 A85-19826 SCHMIDT, W.
- Theoretical contributions to transonic flow analysis for transport aircraft [BMFT-FB-W-84-036]
- p 239 N85-16838 SCHMITZ, F. H.
- Helicopter model rotor-blade vortex interaction impulsive noise: Scalability and parametric variations [NASA-TM-86007] p 238 N85-16826
- SCHOENNAGEL, R. Realization and testing of an experimental color display
- system for general aviation helicopters and aircraft p 262 N85-16872 [BMFT-FB-W-84-042] SCHOETTLE, U. M.
- Air breathing space transport vehicles with wings p 280 A85-20909 SCHRA, L.
- Engineering property comparisons of PM and IM aluminum alloy forgings
- [AD-B0881466L] p 298 N85-17398 SCHUETZ, R. Operational loads data evaluation for individual aircraft
- fatioue monitoring p 253 N85-15669 SCHULTZ, K. J.
- Helicopter model rotor-blade vortex interaction impulsive noise: Scalability and parametric variations [NASA-TM-86007] p 238 N85-16826 SCHUSTER, D. M.
- Numerical computation of viscous flowfields about multiple component airfoils
- [AIAA PAPER 85-0167] p 213 A85-19563 SCHWARTZ, B. J.
- Development of a fatigue crack propagation model of p 280 A85-20758 Incoloy 901 SCOTT, R. K.
- Investigating version dependence in fault-tolerant p 302 N85-16749 oftware SEEBASS, A. R.
- Shock-free turbomachinery blade design
- p 232 A85-21864 SEIDEL, D. A.
- Nonreflecting boundary conditions for the complete unsteady transonic small-disturbance equation p 290 A85-21875
- An exploratory study of finite difference grids for transonic unsteady aerodynamics [NASA-TM-84583] p 235 N85-15696
- SEIDENSTICKER, S.
- Modular simulators, their feasibility, design, and procurement [AIAA PAPER 85-0312] p 274 A85-19659
- SEIRANIAN, A. P. Optimization of flutter characteristics
- p 288 A85-20828 SELBERG, B. P.
- Aerodynamic-structural study of canard wing, dual wing, and conventional wing systems for general aviation applications [NASA-CB-172529] p 238 N85-16829
- SELF. H.
- Contrast sensitivity performance assessment of HUD p 259 A85-21593 display systems SELIG, M. S.
- The design of airfoils at low Reynolds numbers [AIAA PAPER 85-0074] p 209 A85-19500 SELIVANOR, N.
- Parachute expedition to Arctic p 236 N85-16240 SELLIER. B.
- A sensor for detection of unsteady distortion maxima in air intakes
- [ONERA, TP NO. 1984-148] p 205 A85-19262 SERAFINI, T. T.

B-14

PMR polyimide composites for aerospace applications p 282 A85-21520

- SEXTON, G. A. Pilot's Desk Flight Station
- p 258 A85-21555 SHABAKA, I. M. M. A. Turbulence structure of a three dimensional impinging iet in a cross stream [AIAA PAPER 85-0044] p 208 A85-19478 SHAMROTH, S. J. Development of a Navier-Stokes rotor and stator analysis
- [AD-A146967] p 294 N85-16070 SHAN, Y.
- The development of digital attitude controllers Its past, resent and future p 302 A85-22449 SHANG, J. S.
- A comparative study between an implicit and explicit algorithm for transonic airfoils [AIAA PAPER 85-0480] p 225 A85-19777
- SHARAF. M. A. An experimental study of sound attenuation
- characteristics in circular ducts with lined radial baffles [AIAA PAPER 85-0079] p 304 A85-19505 SHARANIUK, A. V.
- Optimization of flutter characteristics p 288 A85-20828 SHARP, T. J.
- Parametric estimates of propulsion system maintenance manhours
- AD-A147120] p 201 N85-15662 SHAW. D. E.
- Speed benefits of tilt-rotor designs for LHX [NASA-CR-166437] p 255 N85-15717
- SHAW, L. M. Unsteady pressure measurements on a biconvex airfoil
- in a transonic oscillating cascade [NASA-TM-86914] p 234 N85-15689 SHAW, R. J.
- Analytical determination of propeller performance degradation due to ice accretion
- [AIAA PAPER 85-0339] p 264 A85-20867 The UH-1H helicopter icing flight test program: An overview
- [NASA-TM-86925] p 242 N85-15702 The NASA Altitude Wind Tunnel (AWT): Its role in advanced icing research and development
- [NASA-TM-86920] p 276 N85-15758 SHAYESTEH, M. V.
- Turbulence structure of a three dimensional impinging jet in a cross stream
- AIAA PAPER 85-0044] p 208 A85-19478 SHCHELIN V.S.
- Hypersonic chemically nonequilibrium viscous shock layer on wings with a catalytic surface p 229 A85-20561
- SHCHIPTSOV, O. A.
- Calculation of the hydrodynamic characteristics of p 290 A85-22113 polyplanes SHEER, R. E., JR.
- Critical layer concept relative to hypersonic boundary laver stability
- [AIAA PAPER 85-0303] p 219 A85-19652 SHESTERNINA, Z. N.
- Harmonic oscillations of a rectangular wing with a circulation variable over the span p 231 A85-21656 SHILLITO, P. L.
- The design and development of an integrated core system for battlefield helicopters p 260 N85-16811 SHISHKOV, A. A.
- Effect of the arrangement of apertures on the gain coefficient during asymmetric gas injection into a Laval p 229 A85-20562 nozzle
- SHLAUSTAS, R. IU. Development of asymptotic algorithms in the Polet package of applications programs p 233 A85-22366 Approximate solution of a nonlinear problem of flow past
- a thin airfoil profile near a support surface p 233 A85-22368
- SHREWSBURY, G. D. Analysis of circulation control airfoils using an implicit
- Navier-Stokes solver [AIAA PAPER 85-0171] p 213 A85-19565
- SHVETS, IU. I. Calculation of friction and heat transfer in turbulent flow
- of a compressible gas in a plane duct p 291 A85-22114
- SHYAM, R. Flow behind an attached shock wave in a radiating
- gas p 233 A85-22308 SICLARI, M. J.
- The computational treatment of supersonic wake flows in INCORFL [AIAA PAPER 85-0304] p 219 A85-19653
- SIDDIQI, S.
- Aircraft turbojet engine modeling using artificial intelligence techniques p 263 A85-19616 [AIAA PAPER 85-0253]

- SIGALOV, G. F.
- The full-approximation method in the theory of transonic p 233 A85-22367 flows SILER, L. G.
- Laminar boundary layer stability experiments on a cone at Mach 8. III - Sharp cone at angle of attack [AIAA PAPER 85-0492] p 226 A85-19787
- SIMPKIN, W. E. Real gas effects in advanced technology engine
- p 262 A85-19615 [AIAA PAPER 85-0252] SIMPSON, R. L.
- Some features of two-dimensional turbulent separated flows
- [AIAA PAPER 85-0178] p 214 A85-19570 SIMPSON, W. P., III
- The application of a technology index to aircraft turbine engine cost estimating relationships [AD-A147701] p 268 N85-16874
- SIMS, J. R., JR. The application of a technology index to aircraft turbine
- engine cost estimating relationships [AD-A147701] p 268 N85-16874
- SINGH. L. P. Flow behind an attached shock wave in a radiating p 233 A85-22308 aas
- SINHA, A. Effects of friction dampers on aerodynamically unstable
- p 265 A85-21866 rotor stages SKOTNICKI, J.
 - TUTOR (CL-41A) tail flight load survey

SMITH, G. H.

SMITH, H. C.

SMITH, M. E. F.

SMITH, P.

SMITH, R. C.

New

SMITS, A. J.

vortices

SNUROV. M. Y.

control computers

[NASA-TM-86896]

[AIAA PAPER 85-0005]

SNODGRASS, T. D.

SOEDER, R. H.

SOKHEY, J. S.

SOMER. H. T.

SORENSON, J. A.

[AD-A148669]

SÖSNOVSKII, Á. A.

Aviation radar

and versatiility

[AIAA PAPER 85-0279]

[NASA-TM-86350]

[NASA-TM-84302]

[AIAA PAPER 85-0046]

AIAA PAPER 85-0299]

future aircraft maintenance

to a high-bypass-ration turbofan engine

Swirting flow in a research combustor

- p 254 N85-15678 SMIALEK. J. L
- Microstructural development of protective Al2O3 p 283 A85-21650 scales SMIRNOV, A. I.
- Aeroelastic stability and vibration of layered plates and cylindrical shells p 288 A85-20472 SMITH-TAYLOR, R.
- Designing a priority driven multi-frame rate flight executive
- [AIAA PAPER 85-0309] p 268 A85-19656 SMITH, F. L.
- Passive control effects on flow separation around a protuberance at high subsonic speed p 220 A85-19690 [AIAA PAPER 85-0351]

Disc fatigue life predictions for gas turbine engines

military

communications systems - The interoperability challenge

Installed nacelle drag-improvement tests of an M = 0.8

The interaction and merging of two turbulent line

The distortion of a supersonic turbulent boundary layer

Investigation of semiautomatic aircraft control processes

Avionics fault tree analysis and artifical intelligence for

Effect of steady-state temperature distortion on inlet flow

Utilization of Increased Airlift Capability (UIAC) study

Analysis of counter-rotating propeller performance

employing time redundancy in on-board digital trajector

by bulk compression and surface curvature

Study of winglets applied to biplanes

Study of winglets applied to biplanes

Trends in civil aircraft design

generation

turboprop transport configuration

Effective life cycle software support: A study in discipline

p 302 N85-16746

p 217 A85-19631

p 258 N85-16862

p 267 N85-15743

p 200 A85-22226

p 244 A85-19275

p 255 N85-15716

p 208 A85-19480

p 218 A85-19648

p 270 N85-16048

p 203 N85-16755

p 265 N85-15725

p 262 A85-19453

p 283 A85-21863

p 243 N85-16847

p 244 A85-19805

airborne

tactical
PERSONAL AUTHOR INDEX

SOUDERS, C. G.
The visibility climatology of McMurdo Sound-Williams
Field, Antarctica
[AD-A148108] p 300 N85-17492
SOUTH, J. C., JR.
Recent advances in computational transonic
aerodynamics
[AIAA PAPER 85-0366] p 221 A85-19699
SPACHT, L
Joined wing transonic design and test validation
[AD-A148355] p 239 N85-16834
SPEARMAN, M. L
The application of some lifting-body reentry concepts
to missile design
[AIAA PAPER 85-0497] n 279 A85-19791
SPIEKHOUT D J.
Structural load measurements on a Northrop NE-5A
p 253 N85-15667
SPLETTSTOESSER, W. R.
Heliconter model rotor-blade vortex interaction impulsive
noise: Scalability and narametric variations
[NASA-TM-86007] 0 238 N85-16826
SPRINGSTON P S
System for rapid repair of damaged airfield norways
(AD-D011325) p 276 N95.1575/
ST CIAIR T I
A thermoniastic polyimidesulfone p 282 A85.21485
STANI W L
Variable temperature water tunnel for high Rounelds
oumbers
ETALCUB H E
Lipitod States Air force singraft medification presses /
Sustem dynamics analysis
[AD-A140934] p 200 N05-1505:
STANCIK, K.
Effect of steady-state temperature distortion on inlet flow
to a nigh-bypass-ration turbotan engine
[NASA-1M-86896] p 265 N85-1572
STANEWSKY, E.
Active and passive shock/boundary layer interaction
control on supercritical airtoils p 238 N85-1679
STANKUS, N. V.
Hypersonic multicycle gas jet with a strongh
underexpanded stream at the nozzle section
p 229 A85-20554
STABOPOLL F.
Flight narameters recording for structure fatique life
monitoring parameter in constant in 292 N85-1568/
STEGER 1
The humanical simulation of steady transactic rotations
flow using a dual potential formulation
Bosset improvements in 10-10-10
necent improvements in efficiency, accuracy, and

Recent improvements in	efficiency, accuracy, and
convergence for implicit	approximate factorization
algorithms	
[AIAA PAPER 85-0360]	p 230 A85-20868
STEINLE, F. W.	
On boundary layer transiti	ion in high-subsonic and
transonic flow under the influer	nce of acoustic disturbances
and from stream turbulance	

and nee-stream turbulence		
[AIAA PAPER 85-0082]	p 210	A85-19508
STEPHENSON, A.		
Trends in civil aircraft design	p 200	A85-22226

STETSON, K. F. Laminar boundary layer stability experiments on a cone

at Mach 8. III - Sharp cone at angle of attack [AIAA PAPER 85-0492] A85-19787 p 226 STEWARTSON, K.

Some important problems in unsteady boundary layers including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies

p 294 N85-16069 [AD-A146964] STOCK. H. W.

Theoretical contributions to transonic flow analysis for transport aircraft

[BMFT-FB-W-84-036]	p 239	N85-1683	
STONE, H. W.			

Effect of aerodynamic and angle-of-attack uncertainties on the May 1979 entry flight control system of the Space Shuttle from Mach 8 to 1.5 [NASA-TP-2365]

p 280 N85-15778 STONE, R. H.

- Flight service evaluation of advanced composite ailerons on the L-1011 transport aircraft
- [NASA-CR-172483] p 284 N85-17049 STOY, S. L. Correlation and analysis of oil flow data for an
- air-breathing missile model [AIAA PAPER 85-0452] p 224 A85-19761
- STRAHLE, W. C. SFRJ simulator results - Experiment and analysis in cold
- flow [AIAA PAPER 85-0329] p 263 A85-19671

STRAUB, F. K.

- Study to eliminate ground resonance using active controls
- [NASA-CR-1666091 p 255 N85-15715 STREET, S. W.
- V-378A, a new modified bismaleimide matrix resin for high modulus graphite p 282 A85-21482 STRICKLAND. J. H.
- An experimental investigation of an airfoil undergoing large amplitude pitching motions [AIAA PAPER 85-0039] p 207 A85-19474
- STROTHER, D. D.
- Integration of sensor fusion in advanced helicopter p 260 N85-16813 cockpit design STRUCK. H.
- Evaluation of operational loads to verify structural p 254 N85-15677 desian STURGEON, J. R.
- Operational loads measurement: A philosophy and its p 253 N85-15665 implementation STURGESS, G. J.
- Calculation of confined swirling flows p 285 A85-19491 [AIAA PAPER 85-0060] SUBKE, H.
- Experimental methods for wind-tunnel flight-mechanics investigations using dynamically similar aircraft model p 249 A85-19836
- SUBRAMANIAN, G. Universal matrices to obtain thermal load vectors for the family of anisotropic plane triangular finite elements p 291 A85-22232
- SUDDHOO, A. Inviscid compressible flow past a multi-element p 236 N85-16776 aerotoil
- SUGAVANAM, A Evaluation of low Reynolds number turbulence models
- for attached and separated flows p 286 A85-19706 [AIAA PAPER 85-0375]
- SÜKHIKH. N. N. Investigation of semiautomatic aircraft control processes employing time redundancy in on-board digital trajector p 270 N85-16048 control computers SULLIVAN, P. A.
- Skirt material effects on air cushion dynamic heave p 307 A85-21840 etahilit SUMMERS, R. H.
- Nondestructive inspection: Improved capabilities of technicians
- p 295 N85-16196 (AD-A147388) SUMMERS, R. L.
- Integrated exhaust gas analysis system for aircraft turbine engine component testing [NASA-TP-2424] p 295 N85-16100
- SUNG. N. W. Some characteristics of automotive gasolines and their performance in a light aircraft engine
- p 283 N85-15919 [FAA-CT-84-12] SWANSON, R. C.
- scheme multistage time-stepping for the Navier-Stokes equations [AIAA PAPER 85-0035] p 207 A85-19472
- SWEETMAN, B. p 246 A85-19184 From AV-88 to the ASTOVL
- SYED, S. A. Calculation of confined swirling flows [AIAA PAPER 85-0060] p 285 A85-19491
- SZODRUCH, J. The influence of camber variation on the aerodynamics
- of civil transport aircraft [AIAA PAPER 85-0353] p 220 A85-19691
- Benefits and costs of powered engine simulation at low sheeds
- [AIAA PAPER 85-0381] p 263 A85-19710 SZUCH. J. R.
- Analytical and physical modeling program for the NASA ewis Research Center's Altitude Wind Tunnel (AWT) p 275 A85-19709 [AIAA PAPER 85-0379] Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT)
- [NASA-TM-869191 p 276 N85-15757

Т

- TAGGE, G. E.
- Systems study for an Integrated Digital-Electric Aircraft (IDÉA)
- [NASA-CR-3840] p 255 N85-15714 TAHA, S.
- Design, fabrication and verification of composite flexbeam tail rotor for AH-64 Apache helicopter p 251 A85-21379
- TAN. D. K. M. Surface pressure fluctuations in a three-dimensional
- shock wave/turbulent boundary layer interaction p 211 A85-19536 [AIAA PAPER 85-0125]

TAN. H. Tomographic reconstruction of three-dimensional flow over airfoil [AIAA PAPER 85-0479] p 225 A85-19776 TĂNG D. Precalculation of rotating stall in multistage axial p 287 A85-19832 compressors TANG, M.-Z. Vortex path in the supersonic wake of a rough even olate p 226 A85-19821 TANG. W. Numerical solution of unsteady viscous flow past rotor sections [AIAA PAPER 85-0129] p 212 A85-19540 TARASOV, E. V. A formalism for the design problem of aircraft system universalization p 250 A85-20473 TAVELLA, D. A. A zonal computational approach to thrust augmentor optimization [AIAA PAPER 85-0110] p 262 A85-19525 TAVERNA. F. airfoils [AIAA PAPER 85-0205] p 215 A85-19589 TAVERNA. F. P. IV wing AIAA PAPER 85-0427] TAWARI P V National airspace review: Airport radar service area operational confirmation report [DOT/FAA/AT-84/2] TAYLOR, L. T. iet fuels [AD-A148272] p 285 N85-17155 TAYLOR, S. M. A path model of aircraft noise annoyance TAYLOR, W. R. Accelerated Mission Endurance Testing (AMET) TEDESCHI, W. J. profiles on airfoils [AIAA PAPER 85-0208] TENHIRO, S.-I. Drag of the fundamental shapes of parachutes TENNEY, D. R. Advances in composites technology [NASA-TM-86353] THAMBURAJ, R. components p 267 THAMES. F. C. adaptive grids [AIAA PAPER 85-0487] THIBERT. J. J. Comparison with calculations THIEDE, P. control on supercritical airfoils THOMAS, A. S. W. Aircraft drag reduction technology THOMAS, J. pavement analysis system (SPAS) [AD-A147116] THOMAS, J. K. W. Advanced technology The competitiveness THOMAS, J. L. the Euler equations (AIAA PAPER 85-0122) THOMAS, N. S. W. control THOMPSON, E. R. at Mach 8. III - Sharp cone at angle of attack [AIAA PAPER 85-0492] TIKHONRAVOV, V. A. Combat aircraft: Flight vehicles, power plants, and their

- p 199 A85-19812 maintenance TOLLE, F. F.
- Aircraft wing fuel tank environmental simulator tests for evaluation of antimisting fuels p 283 N85-15920 [FAA-CT-84-15]
 - **B-15**

Prediction of subsonic/transonic separated flow about Computational aerodynamic design of the Gulfstream p 223 A85-19742 n 245 N85-15707 GC-FTIR (Fourier Transform Infrared Spectrometry) of p 304 A85-22071 p 266 N85-15736 A Fourier Transform method for calculating velocity p 215 A85-19592 p 231 A85-20998 p 284 N85-17048 Problems and possibilities for life extension in gas turbine N85-15742 Application of a variational method for generating p 226 A85-19784 Detailed study of the flow around a multi-element airfoil. p 236 N85-16775 Active and passive shock/boundary layer interaction p 238 N85-16795 p 257 N85-16782 Development of a preliminary ALRS stabilized material p 277 N85-15760 key to European p 200 A85-21680 A comparison of finite volume flux vector solittings for p 211 A85-19533 Flight testing of a wing section with laminar flow p 233 A85-22227 Laminar boundary layer stability experiments on a cone p 226 A85-19787

TOMPKINS, J. A.

- TOMPKINS, J. A. Evaluation of arctic test of improved tritium radioluminescent lighting
- p 278 N85-16884 [AD-A148215] TOMPKINS, W. T., JR.
- Current problems in turbomachinery fluid dynamics [AD-A147127] p 294 N85-16074 TONG,
- International aviation (selected articles) p 204 N85-16762 [AD-A148704]
- TONG. S. S. Design of aerodynamic bodies using artificial intelligence/expert system technique
- [AIAA PAPER 85-0112] p 301 A85-20856 TORELLA. G.
- Turbulent bubbles behind airfoils and wings at high angle p 296 N85-16779 of attack TORRENCE, M. G.
- Langley Mach 4 scramjet test facility
- [NASA-TM-86277] p 278 N85-16883 TOWNE, C. E.
- Analytical modeling of circuit aerodynamics in the new NASA Lewis wind tunnel [NASA-TM-86912] p 234 N85-15688
- TRABOCCO, R. E. Repair of composites p 284 N85-17058
- TRAN, T. T. Surface pressure fluctuations in a three-dimensional shock wave/turbulent boundary layer interaction
- p 211 A85-19536 [AIAA PAPER 85-0125] TROLINGER, J. D.
- Tomographic reconstruction of three-dimensional flow over airfoils
- [AIAA PAPER 85-0479] p 225 A85-19776 TSE. D.
- Analysis of middle distillate fuels by high resolution field ionization mass spectrometry p 285 N85-17153 [AD-A147724]
- TSENG, W. W. Analysis of the flow field about a T-45 using PANAIR
- [AD-A146811] p 236 N85-15699 TSI, B. M. B. Theoretical and experimental analyses of laser
- altimeters for barometric measurements over the ocean p 298 N85-17351
- TSUJIKAWA, Y.
- Off-design point characteristics of the precooled gas turbine cycle with liquefied hydrogen as fuel p 289 A85-20884
- TUNG. C. Numerical solution of the full-potential equation for rotors and oblique wings using a new wake model ·p 216 A85-19621 [AIAA PAPER 85-0268]
- TURCK, G. Flight tests with a new helicopter Force Feel System p 257 N85-16818 (FFS)
- TURKEL, E. A multistage time-stepping scheme for the
- Navier-Stokes equations [AIAA PAPER 85-0035] p 207 A85-19472
- TWEEDT, D. L. An experimental investigation of stator/rotor interaction
- influence on multistage compressor rotor flow [AIAA PAPER 85-0009] p 206 A85-19455

U

- Clearance flow-generated transverse forces at the rotors of thermal turbomachines
- [NASA-TM-77292] p 295 N85-16180 URMANN, D.
- A three-dimensional Kalman filter for short observation times to extrapolate flight trajectories p 301 A85-19835
- USTINOV. S. A. A formalism for the design problem of aircraft system universalization p 250 A85-20473
 - ν
- VADYAK, J.

B-16

URLICHS. K.

- Simulation of transonic three-dimensional nacelle/inlet flowfields using an Euler/Navier-Stokes algorithm p 226 A85-19798 [AIAA PAPER 85-0084]
- VALAREZO, W. O. Calculation of steady flow about propellers by means of a surface panel method
- [AIAA PAPER 85-0283] p 218 A85-19634 VALLOT, L. C.
- Development of a Helicopter integrated navigation p 245 N85-16802 system

- VAN LEER. B.
- A comparison of finite volume flux vector splittings for the Euler equations
- [AIAA PAPER 85-0122] p 211 A85-19533 VAN ROESSEL H. J.
- Transient motion of hypersonic vehicles including time history effects [AIAA PAPER 85-0201] p 268 A85-19585
- VANCE. J. D. A bird strike handbook for base-level managers
- [AD-A147928] p 293 N85-16008 VANDENBERG, B.
- Design of an airfoil leading edge slat using an inverse erodynamic calculation method p 256 N85-16777 VANEGMOND, J. A.
- Design of an airfoil leading edge slat using an inverse aerodynamic calculation method p 256 N85-16777 VANINGEN SCHENAU, H. A.
- Functional built-in-test in a pipelined image processor p 202 N85-16740 VANINGEN, J. L.
- Design studies of thick laminar flow airfoils for low speed flight employing turbulent boundary layer suction over the p 257 N85-16786 ear part VASUDEVAN, A. K.
- Fatigue crack growth behavior of 7XXX aluminum alloys under simple variable amplitude loading 0 280 A85-20759
- VEAL D. L.
- Icing conditions encountered by a research aircraft p 299 A85-21141 VELDMAN, R. J.
- USAF approach to airborne structural data recording: Airborne Data Acquisition Multifunction System (ADAMS) p 292 N85-15683
- VELTEN, R. M.
- Display Techniques for Advanced Crew Stations (DTACS). Phase 1: Display techniques study p 259 N85-15722 [AD-A1469221 VENABLES. A.
- Aerodynamic studies linked to the development of deployable nozzles
- p 205 A85-19263 [ONERA, TP NO. 1984-149]
- VENKATESAN, C. Coupled helicopter rotor/body aeromechanical stability comparison of theoretical and experimental results
- p 252 A85-21847 VERDON, J. M.
- A linearized unsteady aerodynamic analysis for transonic cascades p 229 A85-20744 VERMELAND, R. E.
- Three-dimensional Euler solutions with grid embedding p 211 A85-19532 [AIAA PAPER 85-0121] VESS, R. J.
- The design and testing of several joined wing RPV's [AIAA PAPER 85-0275] p 248 A85-19627 VIKEN, J. K.
- Potential flow calculations and preliminary wing design in support of an NLF variable sweep transition flight experiment
- [AIAA PAPER 85-0426] p 248 A85-19741 VILLANUEVA, F.
- A study of the flow recirculation problems within an anechoic hover chamber (AIAA PAPER 85-0071) p 273 A85-19497
- VILSMEIER, J. W.
- Composite repair of aircraft structures p 285 N85-17059
- VINOGRADOV, A.
- Aeroproyekt develops improved runway surfacing p 277 N85-16770 VIROŽUB. I. E.
- Calculation of friction and heat transfer in turbulent flow of a compressible gas in a plane duct p 291 A85-22114
- VISBAL M. R. A comparative study between an implicit and explicit
- algorithm for transonic airfoils [A]AA PAPER 85-04801 p 225 A85-19777
- VISHNIAK, V. F. Calculation of friction and heat transfer in turbulent flow
- of a compressible gas in a plane duct p 291 A85-22114
- VOLKERS, D. F. Recent advances in computational methods to solve
- the high-lift multi-component airfoil problem p 236 N85-16774
- VOLMIR. A. S. Current problems in the theory of plates and shells in p 287 A85-20459 aircraft VON LAVANTE, E.
- Numerical solutions of viscous transonic flow in turbomachinery cascades [AIAA PAPER 85-0007] p 206 A85-19454

- VONRETH, R. D.
- Flight tests with a new helicopter Force Feel System (FFS) p 257 N85-16818 VOSS J. S.
- Preliminary airworthiness evaluation AH-1S (MC) helicopter with external fuel tanks installed [AD_A148091] p 258 N85-16865
- VUKELICH S. R. Aerodynamic prediction of eliptically-shaped missile
- configurations using component build-up methodology [AIAA PAPER 85-0271] p 216 A85-19624

W

- WAGDI, M. N.
- A generalized stability criterion for nonlinear dynamic evetame [AIAA PAPER 85-0202] p 300 A85-19586
- WAGGONER E G
- Potential flow calculations and preliminary wing design in support of an NLF variable sweep transition flight experiment
- [AIAA PAPER 85-0426] p 248 A85-19741 WAGNER, P.
- Tests of air inlets on civil aircraft
- [ONERA, TP NO. 1984-157] p 272 A85-19271 WAGNER, R. D.
- Technology developments for laminar boundary laver control on subsonic transport aircraft p 237 N85-16787
- WAGNER, W.
- Flight test of the Open Loop Gust Alleviation (OLGA) svstem (BMFT-FB-W-84-0381 p 271 N85-16881
- WAHLS, R. A. The design and testing of several joined wing RPV's
- [AIAA PAPER 85-0275] p 248 A85-19627 WAKE B.F.
- Solution of the unsteady Euler equations for fixed and rotor wing configurations AIAA PAPER 85-0120] p 211 A85-19531
- WALKDEN, A. Advanced fatigue monitoring on service aircraft

An experimental investigation of an airfoil undergoing

Interrelated effects of pitch rate and pivot point on airfoil

Lightning simulation facilities in the United States and

Problems and possibilities for life extension in gas turbine omponents p 267 N85-15742

SFRJ simulator results - Experiment and analysis in cold

An incremental block-line-Gauss-Seidel method for the

Matrix solution of compressible flow on S(1) surface

Experimental investigation of backswept centrifugal

Engineering property comparisons of PM and IM aluminum alloy forgings

A design methodology for integrated avionic systems

Experiences obtained from service fatigue monitoring

Structural Usage

Military avionics - Increasing integration at all levels

Theoretical study on supersonic jet plumes

through a turbomachine blade row with splitter vanes or

p 207 A85-19474

p 212 A85-19541

p 273 A85-19515

p 237 N85-16788

p 263 A85-19671

p 207 A85-19470

p 227 A85-20228

p 264 A85-20243

p 206 A85-19439

p 298 N85-17398

p 301 A85-21458

p 292 N85-15672 Monitoring

p 292 N85-15680

p 244 A85-20221

System

p 292 N85-15671 WALKER, J. M.

large amplitude pitching motions

Turbulent drag reduction research

[AIAA PAPER 85-0039]

[AIAA PAPER 85-0130]

[AIAA PAPER 85-0093]

[AIAA PAPER 85-0329]

Navier-Stokes equations

[AIAA PAPER 85-0033]

compressor impeller. I

dynamic stall

WALKO. L. C.

WALLACE, W.

components

WALTERICK, R. E.

WALTERS, R. W.

tandem blades

WANHILL, R. J. H.

[AD-B0881466L]

WALSH. M. J.

flow

WANG. B.

WANG, E.

WANG, T. C.

WARD. A. O.

WARD, A. P.

exercises

(SUMS)

WARWICK, G.

Tomado

Furope

PERSONAL AUTHOR INDEX

PERSONAL AUTHOR INDEX
WEBRE, J. L.
RC-12D Guardrail V
[AD-A148046] p 258 N85-16864 WECK, M.
Flexible manufacturing system for the production of eircraft parts
[BLL-PNR-90237-(899.3153)] p 297 N85-17159
Sikorsky composite rotor hub development
p 251 A85-21381 WEIBUST, E.
Experimental and theoretical analysis of laminar separation bubbles
[AIAA PAPER 84-2201] p 288 A85-20874
Application of axisymmetric analogue for calculating
[AIAA PAPER 85-0245] p 216 A85-19611
WEINBERG, B. C. Development of a Navier-Stokes rotor and stator
analysis [AD-A146967] p 294 N85-16070
WEISSHAAR, T. A. Vibration tailoring of advanced composite lifting
surfaces p 290 A85-21846 WETTSTEIN, H.
Experiences with the material bevaviour and high temperature low cycle fatigue life prediction of the IN 738
blading alloy p 292 N85-15746
Nonreflecting boundary conditions for the complete unsteady transonic small-disturbance equation
p 290 A85-21875
transonic unsteady aerodynamics
[NASA-1M-84583] p 235 N85-15696 WHITTLEY, D. C.
An update of the Canada/USA augmentor-wing project p 257 N85-16781
WHITTY, D. A. Distribution and storage of aviation turbine fuel for
military operations in northern Australia [AD-A147180] p 283 N85-15921
WICKI, A.
temperature low cycle fatigue life prediction of the IN 738 blading alloy p. 292 N85-15746
WIEDEMANN, J. Drag reduction due to boundary-layer control by
combined blowing and suction p 237 N85-16785 WIESENBERG, S.
Design, fabrication and verification of composite
p 251 A85-21379
Investigating version dependence in fault-tolerant
software p 302 N85-16749 WILCOCK, D. F.
Effects of turbulence and viscosity variation on the dynamic coefficients of fluid film journal bearings
[ASME PAPER 84-TRIB-8] p 289 A85-21283 WILLHITE, P. G.
Finite element solutions of Euler equations for lifting
[AIAA PAPER 85-0294] p 230 A85-20864
Disc fatigue life predictions for gas turbine engines
p 267 N85-15743 WILLIAMS, J. G.
Repair of composites p 284 N85-17058 WILLIAMS, R. A.
UH-60A external stores support system fixed provision fairings drag determination
[AD-A147188] p 256 N85-15719 Preliminary airworthiness evaluation AH-1S (MC)
helicopter with external fuel tanks installed
WILLMERT, K. D.
displacement and frequency constraints
p 290 A85-21985 WILSON, D. A.
Development of a fatigue crack propagation model of Incolog 901 p 280 A85-20758
A Fourier Transform method for calculating velocity
Profiles on alriculs [AIAA PAPER 85-0208] p 215 A85-19592
A new singular integral method for compressible potential flow
[AIAA PAPER 85-0481] p 225 A85-19778 WILSON, D. R.
Development of the UTA High Reynolds Number

Transonic Wind Tunnel [AIAA PAPER 85-0315] p 275 A85-19662 WINER, A. M.

- Atmospheric photochemical modeling of turbine engine fuels. Phase 1. Experimental studies. Volume 2: Environmental chamber data tabulations [AD-A147786] p 300 N85-17470
- WINGENDER, R. J. Impact of aircraft emissions on air quality in the vicinity of airports. Volume 4. Nitrogen dioxide and
- hydrocarbons [AD-A148253] p 299 N85-17436
- WINGROVE, R. C. Identification of vortex-induced clear air turbulence using
- airline flight records p 299 A85-21843 WIPPICH, H. G.
- LPI-radar for helicopter obstacle warning p 297 N85-16810
- WITTMEYER, R. E. Experimental study of forward-located jet-interaction
- [AIAA PAPER 85-0454] p 224 A85-19762
- WOAN, C. J. Euler solution of axisymmetric flows about bodies of
- revolution using a multigrid method [AIAA PAPER 85-0017] p 206 A85-19460
- WOLAK, J. Metallurgical and mechanical phenomena due to rubbing of titanium against sintered powder Nichrome
- p 291 A85-22281
- Mounting construction for turbine vane assembly [AD-D011395] p 265 N85-15723 WOLFE. W. P.
- Drag prediction for projectiles and finned bodies in incompressible flow
- [AIAA PAPER 85-0104] p 230 A85-20854 WOLKOVITCH, J.
- The joined wing An overview [AIAA PAPER 85-0274] p 247 A85-19626 WOOD, N. J.
- Circulation control airfoils Past, present, future [AIAA PAPER 85-0204] p 215 A85-19588
- WOODWARD, D. S. Investigations into the effects of scale and compressibility on lift and drag in the RAE 5m pressurized low-speed wind tunnel p 236 N85-16773 WU C.
- A fast algorithm for solving the conservative transonic S1 full potential equation employing non-orthogonal curvilinear coordinates and non-orthogonal velocity components p 228 A85-20239 WU.C.-H.
- Matrix solution of compressible flow on S(1) surface through a turbomachine blade row with splitter vanes or tandem blades p 227 A85-20228 WU.J.C.
- Unsteady aerodynamics of an airfoil encountering a passing vortex [AIAA PAPER 85-0203] p 214 A85-19587
- [AIAA PAPER 85-0203] p 214 A85-19587 WUENNENBERG, H.
- Flight test of the Open Loop Gust Alleviation (OLGA) system
- [BMFT-FB-W-84-038] p 271 N85-16881

Υ

- YAMAKAWA. G. M.
- Airworthiness and flight characteristics test of the RC-12D Guardrail V
- [AD-A148046] p 258 N85-16864 YAMAKI, D. A.
- A thermoplastic polyimidesulfone p 282 A85-21483 YAN, J.
- A linearly correcting method of deviation function for considering the influence of pressure on the thermodynamic properties of combustion gas p 304 A85-20236
- р 304 А85-2023 YANG, J. Y.
- Numerical solution of the two-dimensional Euler equations by second-order upwind difference schemes [AIAA PAPER 85-0292] p 218 A85-19642 YANG, Y.
- A linearly correcting method of deviation function for considering the influence of pressure on the thermodynamic properties of combustion gas p 304 A85-20236
- YATES, J. E. Analysis of the surface load and radiated sound of a
- vibrating airfoil with application to the experiment of Brooks [NASA-CR-3864] p 305 N85-16590 YE.Q.
- A method for calculating the performance of ejector nozzles p 287 A85-20232

YE, V	V.
-------	----

- International aviation (selected articles) [AD-A148704] p 204 N85-16762 YEATES, L. G.
- Experiments on the stability of crossflow vortices in swept-wing flows [AIAA PAPER 85-0493] p 231 A85-20873
- [AIAA PAPER 85-0493] p 231 A85-20873 YEGER, S.
- Designer on civil aircraft design trends in USSR p 256 N85-16768 YEOMAN. K. E.
- Analysis and testing of the Diamond One wing anti-icing system
- [AIAA PAPER 85-0414] p 286 A85-19735 YOON, S.
- Multigrid solution of the Euler equations using implicit schemes [AIAA PAPER 85-0293] p 218 A85-19643
- [AIAA PAPER 85-0293] p 218 A85-19643 YOUNG, S. E.
- Analysis of middle distillate fuels by high resolution field ionization mass spectrometry
- [AD-A147724] p 285 N85-17153 YU, Y.
 - Tomographic reconstruction of three-dimensional flow over airfoils
 - [AIAA PAPER 85-0479] p 225 A85-19776 Experimental investigation of backswept centrifugal compressor impeller. | p 264 A85-20243 YU. Y. H.
 - Application of digital interferogram evaluation techniques to the measurement of three-dimensional flow fields.
 - [AIAA PAPER 85-0037] p 288 A85-20852

Z

ZABOLONOVA, N. A.

- The use of local functionals to construct a circumvention maneuver in game problems of evasion
- p 302 A85-22374 ZACHAROPOULOS, A.
 - An optimality criterion method for structures with stress, displacement and frequency constraints p 290 A85-21985
 - ZANG, T. A.
 - Spectral methods for modeling supersonic chemically reacting flow fields [AIAA PAPER 85-0302] p 219 A85-19651
 - [AIAA PAPER 85-0302] p 219 A85-19651 ZELENTSOV, V. V.
 - Effect of the arrangement of apertures on the gain coefficient during asymmetric gas injection into a Laval nozzle p 229 A85-20562 ZENAS R.
 - ZENAS, R. Metallurgical and mechanical phenomena due to rubbing of titanium against sintered powder Nichrome
- p 291 A85-22281
- Some improvements on an annular combustor of Al type turbojet engine p 264 A85-20235 ZHANG, J.
- A fast algorithm for solving the conservative transonic S1 full potential equation employing non-orthogonal curvilinear coordinates and non-orthogonal velocity components p 228 A85-20239
- ZHANG, M. A method for calculating the performance of ejector nozzles p 287 A85-20232 ZHONG, F.
- Determination of surging line of two-spool axial flow compressor with cropped fan stages at low speed by use of parallel compressor theory p 264 A85-20242 ZHU, P.
- Circulation around thick wings with free vortices p 227 A85-19848 ZHULEV. V. I.
- Combat aircraft: Flight vehicles, power plants, and their maintenance p 199 A85-19812 ZIMMER, W. J.
- Aircraft barricade [AD-D011316] p 277 N85-15761 ZIQIAN, Z
- International aviation (selected articles) [AD-A148704] p 204 N85-16762 ZUMWALT, G. W.
- Ling tunnel tests of Electro-Impulse De-Icing of an engine inlet and high-speed wings
- [AIAA PAPER 85-0466] p 241 A85-20872 ZYDOWICZ, M. P.
 - Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems [NASA-CR-174271] p 242 N85-15701

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Supplement 187)

MAY 1985

Typical Corporate Source Index Listing



Listings in this index are arranged alphabetically by corporate source. The title of the document is used to provide a brief description of the subject matter. The page number and the accession number are included in each entry to assist the user in locating the abstract in the abstract section. If applicable, a report number is also included as an aid in identifying the document.

A

- Advisory Group for Aerospace Research and Development, Neuilly-Sur-Seine (France).
- Operational Loads Data [AGARD-CP-375] p 201 N85-15664 Keeping up with operational loads in the French Air
- Force: Defining new equipment p 292 N85-15681 Engine Cyclic Durability by Analysis and Testing [AGARD-CP-368] p 266 N85-15733
- [AGARD-CP-360]
 p 200
 Motor 13/33

 Design for Tactical Avionics Maintainability
 [AGARD-CP-361]
 p 201
 N85-16731

 Improvement of Aerodynamic Performance Through
 Participation
 Participation
 Participation
- Boundary Layer Control and High Lift Systems [AGARD-CP-365] p 204 N85-16771
- Helicopter Guidance and Control Systems for Battlefield Support
- [AGARD-CP-359]
 p 204
 N85-16797

 Composite structure repair, addendum
 [AGARD-R-716-ADD]
 p 284
 N85-17057
- AEG-Telefunken, Ulm (West Germany). Maintainability: An ILS effort to manipulate LCC
- p 202 N85-16743 LPI-radar for helicopter obstacle warning
- p 297 N85-16810 Aeritaila S.p.A., Torino (Italy).
- Flight parameters recording for structure fatigue life monitoring p 292 N85-15682 Study and realisation of a 3rd level maintenance center based on ATE systems utilization p 202 N85-16735
- Aeronautical Research Associates of Princeton, Inc., N. J.
- Analysis of the surface load and radiated sound of a vibrating airfoil with application to the experiment of Brooks
- [NASA-CR-3864] p 305 N85-16590 Aeronautical Research Inst. of Sweden, Bromma.
- Full scale experiments into the use of large eddy breakup devices for drag reduction on aircraft
 - p 257 N85-16790

- Aeronautical Research Labs., Melbourne (Australia). Calculation of the velocity field generated by a helicopter main and tail rotors in hover
- [AD-A147731] p 239 N85-16833 Aeronautical Systems Div., Wright-Patterson AFB,
- Ohlo. USAF approach to airborne structural data recording: Airborne Data Acquisition Multifunction System (ADAMS) p 292 N85-15683
- Accelerated Mission Endurance Testing (AMET) p 266 N85-15736
- Aerospace Engineering Test Establishment, Cold Lake
- (Alberta). Operational requirements versus technological
- capabilities p 204 N85-16798 Aerospace Medical Research Labs., Wright-Patterson AFB. Ohio.
- Impact tests of automatic lap belt configurations [AD-A148034] p 243 N85-168
- [AD-A148034] p 243 N85-16844 AIr Force Human Resources Lab., Brooks AFB, Tex. Nondestructive inspection: Improved capabilities of technicians
- [AD-A147388] p 295 N85-16196 Air Force inst. of Tech., Wright-Patterson AFB, Ohio. Frequency response of a jet engine test facility air supply
 - (AIAA PAPER 85-0053) p 273 A85-19485 United States Air force aircraft modification process: A
- system dynamics analysis [AD-A146954] p 200 N85-15659
- Performance evaluation of A-10 aircraft mainteance units and aircraft using constrained facet analysis [AD-A146955] p 201 N85-15660
- Parametric estimates of propulsion system maintenance manhours
- [AD-A147120] p 201 N85-15662 A Q-GERT network simulation model for examining pipeline time in the Navy's J-52 intermediate level jet engine repair cycle
- (AD-A147269) p 201 N85-15663 Distribution and storage of aviation turbine fuel for military operations in northern Australia
- [AD-A147180]
 p 283
 N85-15921

 A bird strike handbook for base-level managers
 [AD-A147928]
 p 293
 N85-16008
- [AD-A147928] p 293 N85-16008 A description of a logistically ideal aircraft
- [AD-A148425] p 258 N85-16866 The application of a technology index to aircraft turbine engine cost estimating relationships
- [AD-A147701] p 268 N85-16874 Design of a digital ride quality augmentation system for commuter aircraft

[AD-A148233] p 271 N85-16879 The effects of manufacturing automation on the surge and mobilization capabilities of the gas turbine engine industry

[AD-A147295] p 297 N85-17162 Life cycle cost model for very high speed integrated circuits

- [AD-A147798] p 297 N85-17298 AIr Force Systems Command, Wright-Patterson AFB, Ohio.
 - International aviation (selected articles)
- [AD-A148704] p 204 N85-16762 Air Force Wright Aeronautical Labs., Wright-Patterson
- AFB, Ohio. Cumulative damage modeling of fatigue crack growth p 267 N85-15741 Verification of life prediction through component testing p 292 N85-15748
- Optimum performance parameters for ski-jump operations of USAF fighter aircraft [AD-A148532] p 258 N85-16867
- Aix-Marseilles Univ. (France). Structure of the wall pressure fluctuations in a
- shock-induced separated turbulent flow [AIAA PAPER 85-0179] p 214 A85-19571 Akron Univ.. Ohio.
- Progress in development of a Navier-Stokes solver for evaluation of iced airfoil performance [AIAA PAPER 85-0410] p 222 A85-19731

Anacapa Sciences, Inc., Santa Barbara, Calif.

- A Computer-generated topographic display system for navigation and mission planning in helicopters p 259 N85-16800
- Analytical Methods, Inc., Redmond, Wash. Prediction of dynamic stall characteristics using
- advanced non-linear panel methods [AD-A148453] p 239 N85-16836 Arbeitsgemeinschaft Deutscher Verkehrsflughaefen,
- Stuttgart (West Germany). Activities report on West German civil airports. Part 1:
- Text [ISBN-3-87977-055-7-PT-1] p 279 N85-16887
- Activities report for the West German Civil Airports. Part 2: Tables
- [ISBN-3-87977-055-7-PT-2] p 279 N85-16888 Argonne National Lab., III.
- Impact of aircraft emissions on air quality in the vicinity of airports. Volume 3: Air quality and emission modeling needs
- [AD-A147951] p 299 N85-17435 Impact of aircraft emissions on air quality in the vicinity of airports. Volume 4. Nitrogen dioxide and
- hydrocarbons [AD-A148253] p 299 N85-17436
- Arizona State Univ., Tempe. Experiments on the stability of crossflow vortices in swept-wing flows
- [AIAA PAPER 85-0493] p 231 A85-20873 Artzona Univ., Tucson.
- Identification of vortex-induced clear air turbulence using airline flight records p 299 A85-21843
- Army Aviation Engineering Flight Activity, Edwards AFB, Calif.
- UH-60A external stores support system fixed provision fairings drag determination
- [AD-Ă147188] p 256 N85-15719 Airworthiness and flight characteristics test of the
- RC-12D Guardrail V [AD-A148046] p 258 N85-16864
- Preliminary airworthiness evaluation AH-1S (MC) helicopter with external fuel tanks installed
- [AD-A148091] p 258 N85-16865 Army Aviation Research and Development Command,
- Moffett Field, Calif. Numerical solution of the full-potential equation for rotors
- and oblique wings using a new wake model [AIAA PAPER 85-0268] p 216 A85-19621
- Army Avionics Research and Development Activity, Fort Monmouth, N. J.
- Evolution toward a multi-bus architecture for Army helicopter avionic systems p 260 N85-16812 Army Concepts Analysis Agency, Bethesda, Md.
- Utilization of Increased Airlift Capability (UIAC) study
- [AD-A148669] p 243 N85-16847 Army Research and Technology Labs., Fort Eustis, Va. US Army helicopter operational flight loads
- p 254 N85-15675 Army Research and Technology Labs., Moffett Field,
- Cain. Helicopter model rotor-blade vortex interaction impulsive noise: Scalability and parametric variations
- [NASA-TM-86007] p 238 N85-16826 Atlanta Univ., Ga.
- Random equations in aerodynamics [NASA-CR-174279] p 238 N85-16825
- Atmospheric Science Associates, Bedford, Mass. Three-dimensional airflow and hydrometeor trajectory
- calculation with applications [AIAA PAPER 85-0412] p 222 A85-19733
- Avions Marcel Dassault, Saint-Cloud (France). Aeroelastic analysis and the identification of flight loads p 254 N85-15679

- Bari Univ. (Italy).
- An incremental block-line-Gauss-Seidel method for the Navier-Stokes equations [AIAA PAPER 85-0033] p 207 A85-19470

В

C-1

Bell Helicopter Co., Fort Worth, Tex.

- Bell Helicopter Co., Fort Worth, Tex. Integration of sensor fusion in advanced helicopte
- p 260 N85-16813 cockpit design Bionetics Corp., Hampton, Va.
- Field-incidence noise transmission loss of general aviation aircraft double-wall configurations p 304 A85-21842
- Bochum Univ. (West Germany). Drag reduction due to boundary-layer control by combined blowing and suction p 237 N85-16785
- Boeing Aerospace Co., Seattle, Wash. Software test handbook: Software test guidebook, volume 2
- [AD-A147289] p 303 N85-17578 Boeing Commercial Airplane Co., Seattle, Wash.
- Systems study for an Integrated Digital-Electric Aircraft (IDÉA) p 255 N85-15714 [NASA-CR-3840]
- cost and benefits optimization model for fault-tolerant aircraft electronic systems p 293 N85-15993 [NASA-CR-166043]
- being Military Airplane Development, Seattle, Wash. B Aircraft wing fuel tank environmental simulator tests for evaluation of antimisting fuels p 283 N85-15920
- [FAA-CT-84-15] Aerodynamic issues in the design of high-lift systems for transport aircraft p 256 N85-16780 Bolt, Beranek, and Newman, Inc., Cambridge, Mass.
- An experimental investigation of blade-vortex interaction at normal incidence
- [AIAA PAPER 85-0003] p 206 A85-19451 Bolt, Beranek, and Newman, Inc., Canoga Park, Calif. NOISEMAP 4.4 computer program update, operator's manual, addendum 1
- [AD-A147091] p 302 N85-16503 Breguet-Avlation, Saint Cloud (France). Objectives in studying the maintainability of aircraft
- N85-16732 systems p 202 British Aerospace Aircraft Group, Preston (England).
- Experiences obtained from service fatigue monitoring p 292 N85-15672 exercises Tornado:
- Structural Usage Monitoring System p 292 N85-15680 (SUMS) British Aerospace Aircraft Group, Stockport (England).
- Advanced fatigue monitoring on service aircraft p 292 N85-15671 British Aerospace Alrcraft Group, Weybridge
- (England). Recent progress of development and understanding of
- p 236 N85-16772 high lift systems Brown Boverl Research Center, Baden (Switzerland).
- Experiences with the material bevaviour and high temperature low cycle fatigue life prediction of the IN 738 blading alloy p 292 N85-1574 Bundesanstalt fuer Flugsicherung, Frankfurt am Main p 292 N85-15746
- (West Germany). Directions of the West German Ministry of Transport
- for education and control of airline personnel (section 3, chapters 2 and 12) p 243 N85-16848
- Directions of the West German Ministry of Transport for education and control or airline personnel, Report 6; chapters 3/A and 3/B p 244 N85-16849

С

- California Univ., Los Angeles.
- Coupled helicopter rotor/body aeromechanical stability comparison of theoretical and experimental results p 252 A85-21847
- Flutter control with unsteady aerodynamic models p 270 N85-15753 [AD-A147858] California Univ., Riverside.
- Atmospheric photochemical modeling of turbine engine fuels. Phase 1: Experimental studies. Volume 2: Environmental chamber data tabulations
- [AD-A147786] p 300 N85-17470 Calspan Field Services, Inc., Arnold Air Force Station,
- Tenn. A numerical simulation of the NFAC (National Full-scale Aerodynamics Complex) open-return wind tunnel inlet flow
- [AIAA PAPER 85-0437] p 230 A85-20869 Canadair Ltd., Montreal (Quebec).
- TUTOR (CL-41A) tail flight load survey p 254 N85-15678
- Carnegie-Mellon Univ., Pittsburgh, Pa. Effects of friction dampers on aerodynamically unstable
- p 265 A85-21866 rotor stages Centre d'Electronique de l'Armement, Bruz (France). A simulator for studying helicopter weapons systems
- p 277 N85-16816 Cincinnati Univ., Ohio.
- A procedure for the calculation of supersonic flows with strong viscous-inviscid interaction
- p 213 A85-19562 [AIAA PAPER 85-0166]

C-2

- Civil Aeronautics Board, Washington, D.C.
- Airport activity statistics of certificated route air carriers
- [AD-A148472] p 243 N85-16846 Clemson Univ., S.C.
- Laboratory simulation of smoke reduction from aircraft engine test cell exhaust using a fluidized bed filter [AD-A148600] p 278 N85-16886
- Cleveland State Univ., Ohio. Investigation on experimental techniques to detect,
- locate and quantify gear noise in helicopter transmissions [NASA-CR-3847] p 305 N85-17667
- College of William and Mary, Williamsburg, Va. Optimal maintenance center inventories for fault-tolerant
- repairable systems p 301 A85-21548 Colorado Univ., Boulder.
- Numerical optimization design of advanced transonic wing configurations [AIAA PAPER 85-0424] p 248 A85-19739
- Shock-free turbomachinery blade design p 232 A85-21864
- Committee on Commerce, Science, and Transportation (U. S. Senate).
 - Satellite navigation [S-HRG-98-856]
- p 246 N85-16851 Continuum Dynamics, Inc., Princeton, N. J. Scaling laws for testing of high lift airfoils under heavy rainfall
- [AIAA PAPER 85-0257] p 216 A85-19617
- Crouzet Aerospace and Systems, Valence (France), Recent methods for calibrating the anemometry of helicopters at low speeds p 260 N85-16809

D

- Dayton Univ., Ohio.
- Clear turbulence forecasting Towards a union of art and science
- [AIAA PAPER 85-0014] p 298 A85-19458 De Havilland Aircraft Co. of Canada Ltd., Downsview (Ontario).
- An update of the Canada/USA augmentor-wing N85-16781 project p 257 Department of National Defence, Ottawa (Ontario).
- Development of a Helicopter integrated navigation p 245 N85-16802 system Department of the Air Force, Washington, D.C.
- Windblast leg protector assembly
- p 242 N85-15700 [AD-D011376] Powered articulated headrest system
- [AD-D011353] p 254 N85-15710
- Aircraft thrust control scheme for terrain following system p 255 N85-15711 [AD-D011387]
- Biodynamic resistant control stick [AD-D011380] p 259 N85-15721
- Mounting construction for turbine vane assembly [AD-D0113951 p 265 N85-15723
- Voice command weapons launching system p 293 N85-15940 [AD-D011378]
- EMI (electromagnetic interference) filter capacitor unit [AD-D011392] p 293 N85-15941
- Turbulence measurement interferometer apparatus [AD-D011377] p 295 N85-16156
- Heater block assembly for use in thermal oxidation testing of jet fuel p 285 N85-17077 [AD-D011430]
- Flow measurement device
- [AD-D011432] p 298 N85-17369 Department of the Navy, Washington, D. C.
- System for rapid repair of damaged airfield runways p 276 N85-15754 [AD-D011325] Aircraft barricade
 - [AD-D011316] p 277 N85-15761 A method for determining mesoscale dynamic
- topography [AD-D011412] p 300 N85-17506
- Deutsche Forschungs- und Versuchsanstalt fuer Luft-und Raumfahrt, Brunswick (West Germany).
- Flight testing of Litton laser gyro strapdown system LTN-90 for general aviation [DFVLR-MITT-84-16]
- p 245 N85-15709 Flight research on visusl aids and navigation equipment for helicopter low-level flight at night
- p 261 N85-16820 Aeroacoustics at the DEVLR Brunswick Research Center: A survey on recent and current activities [DFVLR-MITT-84-14] p 306 N85-17677
- Deutsche Forschungs- und Versuchsanstalt fuer Luftund Raumfahrt, Cologne (West Germany).
- Experiences with the use of a side-strut model support system for high angles of attack in the Trinsonik wind tunnel тмк
- [DFVLR-MITT-84-09] p 277 N85-15763

- Dornier-Werke G.m.b.H., Friedrichshafen (West
- Germany). Theoretical contributions to transonic flow analysis for transport aircraft

CORPORATE SOURCE

- [BMFT-FB-W-84-036] p 239 N85-16838 Flight test of the Open Loop Gust Alleviation (OLGA)
- system [BMFT-FB-W-84-038] p 271 N85-16881
- Dowty Electronics Ltd., London (England). Experience of one UK electronic equipment supplier with bite on engine/flight control systems over the past ten
- p 296 N85-16738 vears The effect on software design of testing by symbolic xecution p 303 N85-16750 execution
- Dynamics Technology, Inc., Torrance, Calif. Investigation of nonlinear effects in the instabilities and
- noise radiation of supersonic jets p 304 A85-19507 [AIAA PAPER 85-0081] E

Eimer, Rome (Italy).

- Tactical HF communication for military helicopters using p 297 N85-16807 the NVIS mode Engineering and Economics Research, Inc., Falls
- Church, Va. National airspace review enhancement plan, revision 3
- p 246 N85-16852 Engineering and Economics Research, Inc., Vienna, Va.
- National airspace review: Airport radar service area perational confirmation report p 245 N85-15707 [DOT/FAA/AT-84/2]

F

- Federal Aviation Administration, Atlantic City, N.J. Preliminary evaluation of an improved flammability test
- method for aircraft materials p 242 N85-16840 [FAA-CT-84-22] Federal Aviation Administration, Washington, D.C.
- Helicopter noise survey performed at Las Vegas, Nevada, 19-21 January, 1984
- Noise measurement flight test: Data-analycen arospatiale AS-3565 Test-50 [AD-A147392] arospatiale AS-355F TwinStar helicopter AD-A147497] p 305 N85-16595 FAA (Federal Aviation Administration) statistical [AD-A147497]

ND-A148171] p 203 N85-16760 Test of dispersal of turbojet aircraft departure tracks

Noise measurement flight test for Boeing Vertol 234/CH

Noise measurement flight test: Data-analyses, Sikorsky

A practical example of reducing life cycle costs and

Automatic briefing and mission management systems

(West Germany). The influence of fastener flexibility on load transfer and

fatigue life predictions for multirow bolted and riveted

G

tomorrow p 254 N85-15674 General Dynamics Corp., San Diego, Calif. Numerical optimization design of advanced transonic

The Air Force can improve its forecasts of aircraft spare

General Accounting Office, Washington, D. C.

General Dynamics Corp., Fort Worth, Tex.

F-16 force management, yesterday,

Shock-free turbomachinery blade design

Fraunhofer-Inst. fuer Betriebsfestigkeit, Darmstadt

p 306 N85-17669

p 306 N85-17670

p 306 N85-17672

p 306 N85-17673

p 246 N85-16855

p 296 N85-16736

p 259 N85-16799

p 296 N85-16219

p 308 N85-16682

today and

p 248 A85-19739

p 232 A85-21864

Data-analyses

at washington National Airport (1983-84), volume 1

handbook of aviation, calendar year 1983

47-d helicopter: Data/analyses

National Airspace Review

Ferranti Ltd., Edinburgh (Scotland).

Noise measurement flight test: Aerospatiale AS 350D AStar helicopter

Federal Aviation Agency, Atlantic City, N.J.

[AD-A148171]

[AD-A148111]

[AD-A148172]

[AD-A148496]

S-76A helicopter

[AD-A148525]

[AD-A147768]

ioints [LBF-FB-172/84]

increased availability

for battlefield support

parts requirements

ving configurations

[AIAA PAPER 85-0424]

General Electric Co., Lynn, Mass.

[AD-A147911]

report

CORPORATE SOURCE

Georgia Inst. of Tech., Atlanta.

- Turbulent flow around a wing-fuselage type juncture (AIAA PAPER 85-0040) p 208 A85-19475 Grumman Aerospace Corp., Bethpage, N.Y.
- Supercritical airfoil drag reduction by passive shock wave/boundary layer control in the Mach number range 75 to .90
- [AIAA PAPER 85-0207] p 215 A85-19591 Prediction of HiMAT RPRV component interference effects at transonic speeds
- [AIAA PAPER 85-0213] p 215 A85-19593 The computational treatment of supersonic wake flows in INCOREL
- [AIAA PAPER 85-0304] p 219 A85-19653 TRO-2D - A code for rational transonic aerodynamic optimization
- [AIAA PAPER 85-0425] p 223 A85-19740 Potential flow calculations and preliminary wing design in support of an NLF variable sweep transition flight
- experiment [AIAA PAPER 85-0426] p 248 A85-19741

H

Hughes Helicopters, Cuiver City, Calif.

- Study to eliminate ground resonance using active controls
- [NASA-CR-166609] p 255 N85-15715 Human Engineering Labs., Aberdeen Proving Ground,
 - Literature review of voice recognition and generation technology for Army helicopter applications
- [AD-A146878] p 293 N85-15954 I

Illinois Univ., Urbana.

A class of airfoils having finite trailing edge pressure oradients

- AIAA PAPER 85-02061 p 215 A85-19590 Development of a preliminary ALRS stabilized material
- pavement analysis system (SPAS) AD-A1471161 p 277 N85-15760 Illinois Univ., Urbana-Champaign.
- An optimization method for the preliminary design of interplanetary aerobraking missions p 238 N85-16822 Theoretical and experimental analyses of laser
- altimeters for barometric measurements over the ocean p 298 N85-17351 Imperial Coll. of Science and Technology, London
- (England).

Proceedings of the International Conference and Exposition on Structural Impact and Crashworthiness [AD-A147845] p 242 N85-15703

Industrieanlagen-Betriebsgesellschaft m.b.H., Ottobrunn (West Germany).

- Operational loads data evaluation for individual aircraft p 253 N85-15669 fatique monitoring Informatics General Corp., Palo Alto, Calif.
- Navier-Stokes computations for exotic airfoils [AIAA PAPER 85-0109] p 230 A
- p 230 A85-20855 A numerical simulation of the NFAC (National Full-scale Aerodynamics Complex) open-return wind tunnel inlet flow
- [AIAA PAPER 85-0437] p 230 A85-20869 Institut fuer Rundfunktechnik, Munich (West Germany). Measurement of signal separation between radio service
- and air navigation service [IRT-TB-B-40/82] p 246 N85-16860
- International Business Machines Corp., Research Triangle Park, N.C.
- Investigating version dependence in fault-tolerant p 302 N85-16749 software

ITT Aerospace/Optical Div., Fort Wayne, Ind.

Stereo Electro-optical Tracking System (SETS) [NASA-CR-172471] p 295 N8 p 295 N85-16098

J

Jet Propulsion Lab., California Inst. of Tech., Pasadena.

- Measurements of the response of transport aircraft ceiling panels to fuel pool fires
- [AIAA PAPER 85-0394] p 240 A85-19720 Flow of nitrogen-pressurized Halon 1301 in fire extinguishing systems
- [NASA-CR-174271] p 242 N85-15701 Joint Publications Research Service, Arlington, Va. All-composite Airbus empennage p 284 N85-15931
- Investigation of semiautomatic aircraft control processes employing time redundancy in on-board digital trajectory p 270 N85-16048 control computers Parachute expedition to Arctic p 236 N85-16240

- USSR report: Transportation
- [JPBS-UTB-85-001] p 204 N85-16763 Director on institute's civil aviation projects
- p 204 N85-16764 Designer on Aeroflot automated COMMO system development p 296 N85-16765
- Testing solution for IL-76 braking system problem p 256 N85-16766
- International projects, other work of Aeroproyekt Institute p 204 N85-16767 Designer on civil aircraft design trends in USSR
 - p 256 N85-16768 Aeroproyekt develops improved runway surfacing
- p 277 N85-16770 FRG ceramic engine components (PET)
- p 297 N85-17193 Description of MBB computerized design techniques for
- p 303 N85-17194 A320

Κ

Kansas Univ., Lawrence.

- Theory of wing rock
- p 268 A85-19583 [AIAA PAPER 85-0199] An investigation of vortex-induced aerodynamic characteristics of supersonic cruise configurations p 234 N85-15690 [NASA-CR-174299]
- Kansas Univ. Center for Research, Inc., Lawrence. Design study of technology requirements for high
- performance single-propeller-driven business airplanes [NASA-CR-3863] p 235 N85-15692 Kentron International, Inc., Hampton, Va.
- Vortex research facility improvements and preliminary density stratification effects on vortex wakes p 209 A85-19482 [AIAA PAPER 85-0050]
- Ketron, Inc., Warminister, Pa. A Generalized Escape System Simulation (GESS) computer program. Volume 2: GESS programmer's
- manual, version 2 [AD-A148363] p 243 N85-16845

L

- LABEN Space Instrumentation and Systems, Milan
- (Italy). Reliable software design for avionics and space applications p 303 N85-16751 LITEF, Freiburg (West Germany).
- Documentation and separate test program development is most important for test/maintenance
- p 203 N85-16745 Lockheed-California Co., Burbank.
- Integrated technology wing study (oral presentation) NASA-CR-169497] p 256 N85-15718 [NASA-CR-169497] Integrated digital/electric aircraft concepts study
- [NASA-CR-3841] p 257 N85-16861 Flight service evaluation of advanced composite allerons on the L-1011 transport aircraft
- [NASA-CR-172483] p 284 N85-17049 Lockheed-Georgia Co., Marietta.
- Experiments on the stability of crossflow vortices in swept-wing flows [AIAA PAPER 85-0493] p 231 A85-20873
- p 258 A85-21555 **Pilot's Desk Flight Station** Aircraft drag reduction technology
- p 257 N85-16782 Logistics Management Inst., Bethesda, Md.
- The Air Force stock fund and aircraft availability [AD-A148653] p 203 N85 p 203 N85-16761
- isiana State Univ., Baton Rouge. Production rate variations cost models
- [AD-A147708] p 308 N85-17732

Μ

Manchester Univ. (England).

- Inviscid compressible flow past a multi-element aerofoil p 236 N85-16776
- Martin Marletta Aerospace, Orlando, Fla. Experimental study of forward-located jet-interaction nozzies
- [AIAA PAPER 85-0454] p 224 A85-19762
- Maryland Univ., College Park. A study of the effects of numerical dissipation on the calculation of supersonic separated flows
- [AIAA PAPER 85-0301] p 219 A85-19650 Massachusetts Inst. of Tech., Cambridge.
- Three-dimensional inviscid flow analysis of turbofan forced mixers
- [AIAA PAPER 85-0086] p 210 A85-19510 Solution method for a hovering helicopter rotor using the Euler equations
- [AIAA PAPER 85-0436] p 223 A85-19749

Current problems in turbomachinery fluid dynamics p 294 N85-16074 [AD-A147127] p 294 N85-16074 Multivariable flight control with time-scale separation

- p 268 N85-16873 [NASA-CR-174320] Research on optimal control, stabilization and computational algorithms for aerospace applications
- [NASA-CR-174318] p 303 N85-17603 McDonnell Aircraft Co., St. Louis, Mo.
 - The F-15 flight loads tracking program

National Aeronautics and Space Administration, Washington, D. C.

- p 253 N85-15666 Display Techniques for Advanced Crew Stations (DTACS). Phase 1: Display techniques study AD-A146922] N85-15722 p 259
- Avionics fault tree analysis and artifical intelligence for p 203 N85-16755 future aircraft maintenance
- McDonnell-Douglas Astronautics Co., St. Louis, Mo. Correlation and analysis of oil flow data for an air-breathing missile model [AIAA PAPER 85-0452] p 224 A85-19761
- McDonnell-Douglas Corp., Long Beach, Calif. Some important problems in unsteady boundary layers
- including separation. 2: Unsteady boundary layers close to the stagnation region of slender bodies p 294 N85-16069 [AD-A146964]
- Some important problems in unsteady boundary layers including separation. 1: Nature of singularity on oscillating airfoils
- p 294 N85-16087 [AD-A147897] Messerschmitt-Boelkow-Blohm G.m.b.H., Bremen (West Germany).
- Evaluation of operational loads to verify structural desian esign p 254 N85-15677 Active and passive shock/boundary layer interaction
- p 238 N85-16795 control on supercritical airfoils p 238 N85-16795 Messerschmitt-Boelkow-Blohm G.m.b.H., Munich (West
- Germany). Built-in-test for first line testing
- p 202 N85-16739 Experience in using on-aircraft software for testing integrated systems p 302 N85-16747
- Theoretical study of boundary-layer control p 237 N85-16784 Evaluation of nose, roof, and mast mounted sensor
- platforms for piloting and sighting, integrated in future combat helicopters p 260 N85-16808
- Advanced flight simulation for helicopter development p 277 N85-16815 Flight tests with a new helicopter Force Feel System
- (FFS) p 257 N85-16818 Composite repair of aircraft structures p 285 N85-17059

Structural flight load measurement demonstration of

Some characteristics of automotive gasolines and their

Shock waves in transonic flows at moderate Reynolds

Operational loads measurement: A philosophy and its

Aerodynamic-structural study of canard wing, dual wing,

A thermoplastic polyimidesulfone p 282 A85-21483

Comparison between the properties of conventional

wrought and powder metallurgical alloys for turbine disc

Ν

Turbulent bubbles behind airfoils and wings at high angle

Problems and possibilities for life extension in gas turbine omponents p 267 N85-15742

installed nacelle drag-improvement tests of an M = 0.8

Clearance flow-generated transverse forces at the rotors

National Aeronautical Establishment, Ottawa (Ontarlo).

National Aeronautics and Space Administration,

and conventional wing systems for general aviation

Mobil Research and Development Corp., Paulsboro,

Motoren- und Turbinen-Union Muenchen G.m.b.H.

p 254 N85-15670

p 283 N85-15919

p 238 N85-16823

p 253 N85-15665

p 238 N85-16829

p 283 N85-15739

p 296 N85-16779

p 255 N85-15716

p 295 N85-16180

C-3

Messerschmitt-Boeikow-Biohm G.m.b.H., Toulouse

(France).

Number

structural integrity

[FAA-CT-84-12]

implementation

applications INASA-CR-1725291

N.J.

Missouri Univ., Rolla.

(West Germany).

Naples Univ. (Italy).

of attack

components

Washington, D. C.

[NASA-TM-84302]

[NASA-TM-77292]

of thermal turbomachines

turboprop transport configuration

applications

Michigan Univ., Ann Arbor.

performance in a light aircraft engine

Ministry of Defence, London (England).

Aeronautical Engineering: A continuing bibliography with indexes (supplement 182)

p 203 N85-16758 [NASA-SP-7037(182)] Results of S5 CH tests with an ARL (Aerospace

Research Laboratory) cascade [NASA-TM-77510] p 278 N85-16882 Turbo fluid machinery-and diffusers

p 298 N85-17363 [NASA-TM-77467] National Aeronautics and Space Administration. Ames Research Center, Moffett Field, Calif.

On boundary layer transition in high-subsonic and transonic flow under the influence of acoustic disturbances and free-stream turbulence

[AIAA PAPER 85-0082] p 210 A85-19508 Circulation control airfoils - Past, present, future [AIAA PAPER 85-0204] p 215 A85-19588

Generalized adaptive-wall wind tunnels [AIAA PAPER 85-0225] p 274 A85-19601

Numerical solution of the full-potential equation for rotors and oblique wings using a new wake model

[AIAA PAPER 85-0268] p 216 A85-19621 Numerical solution of the two-dimensional Euler quations by second-order upwind difference schemes AIAA PAPER 85-02921 p 218 A85-19642

A relaxation approach to patched-grid calculations with the Euler equations [AIAA PAPER 85-0295] p 218 A85-19644

Calculation of the exchange ratio for the Adaptive Maneuvering Logic program [AIAA PAPER 85-0311]

p 199 A85-19658 The numerical simulation of steady transonic rotational flow using a dual potential formulation

[AIAA PAPER 85-0368] p 221 A85-19701 Numerical optimization design of advanced transonic wing configurations

[AIĂA PAPER 85-0424] p 248 A85-19739 Arrays for minimum wave drag of bodies of revolution [AIAA PAPER 85-0449] p 249 A85-19758

Noniterative three-dimensional grid generation using parabolic partial differential equations

p 300 A85-19782 [AIAA PAPER 85-0485] A three-dimensional adaptive grid method

[AIAA PAPER 85-0486] p 225 A85-19783 Predicted performance benefits of an adaptive digital engine control system on an F-15 airplane

[AIAA PAPER 85-0255] p 263 A85-19801 Application of an adaptive blade control algorithm to a

p 269 A85-20143 gust alleviation system Euler computations of AGARD Working Group 07 airfoil test cases

[AIAA PAPER 85-0018] p 229 A85-20851 Navier-Stokes computations for exotic airfoils

p 230 A85-20855 [AIAA PAPER 85-0109] Recent improvements in efficiency, accuracy, and for implicit approximate factorization convergence algorithms

[AIAA PAPER 85-0360] p 230 A85-20868 A numerical simulation of the NFAC (National Full-scale Aerodynamics Complex) open-return wind tunnel inlet flow

[AIAA PAPER 85-0437] p 230 A85-20869 Artificial dissipation models for the Euler equations p 231 A85-20870 [AIAA PAPER 85-0438] A large-scale computer facility for computational aerodynamics p 301 A85-21791 Introductory aerothermodynamics of advanced space

p 231 A85-21827 transportation systems flowfields about Real-das three-dimensional configurations p 231 A85-21830 Identification of vortex-induced clear air turbulence using

airline flight records p 299 A85-21843 Ground-effect analysis of a jet transport airplane [NASA-TM-85920] p 234 N85-15687

Downwash in the plane of symmetry of an elliptically aded wing

[NASA-TP-2414] p 235 N85-15693 F-8 refueling boom ground vibration test

[NASA-TM-84914] NASA-TM-84914] p 255 N85-15713 Predicted performance benefits of an adaptive digital engine control system of an F-15 airplane

p 265 N85-15729 [NASA-TM-85916] More than you want to know about maximum likelihood estimation

p 270 N85-15752 [NASA-TM-85905] Missions and vehicle concepts for modern, propelled, lighter-than-air vehicles

[NASA-TM-86672] p 203 N85-16757 A review of US Army aircrew-aircraft integration research programs p 270 N85-16814

Assessment of simulation fidelity using measurements of piloting technique in flight p 278 N85-16817

Development and flight test of a helicopter compact, portable, precision landing system concept p 261 N85-16821

C-4

Helicopter model rotor-blade vortex interaction impulsive noise. Scalability and parametric variations p 238 N85-16826 [NASA-TM-86007]

National Aeronautics and Space Administration. Hugh L Dryden Flight Research Center, Edwards, Calif. Predicted performance benefits of an adaptive digital engine control system of an F-15 airplane

p 265 N85-15729 [NASA-TM-85916] More than you want to know about maximum likelihood estimation

[NASA-TM-85905] p 270 N85-15752 National Aeronautics and Space Administration. Flight Research Center, Edwards, Calif.

Ground-effect analysis of a jet transport airplane [AIAA PAPER 85-0307] p 248 A85-19677 The Western Aeronautical Test Range of NASA Ames

Research Center [AIAA PAPER 85-0316] p 275 A85-19678

National Aeronautics and Space Administration.

Lyndon B. Johnson Space Center, Houston, Tex. Frequency response of a jet engine test facility air supply system

[AIAA PAPER 85-0053] p 273 A85-19485 A three-dimensional Navier-Stokes/Euler code for blunt-body flow computations

p 220 A85-19696 [AIAA PAPER 85-0361] · National Aeronautics and Space Administration.

Langley Research Center, Hampton, Va. An incremental block-line-Gauss-Seidel method for the Navier-Stokes equations

[AIAA PAPER 85-0033] p 207 A85-19470 multistage time-stepping scheme for the Navier-Stokes equations

p 207 A85-19472 [AIAA PAPER 85-0035] Turbulent flow around a wing-fuselage type juncture

p 208 A85-19475 [AIAA PAPER 85-0040] Vortex research facility improvements and preliminary density stratification effects on vortex wakes

[AIAA PAPER 85-00501 p 209 A85-19482 A theory for the core of a three-dimensional leading-edge

[AIAA PAPER 85-0108] p 210 A85-19524

A comparison of Euler and Navier-Stokes solutions for supersonic flow over a conical delta wing [AIAA PAPER 85-0111] p 2

p 210 A85-19526 A comparison of finite volume flux vector splittings for the Euler equations

[AIAA PAPER 85-0122] p 211 A85-19533 Numerical solution of the Euler equations for high-speed,

blended wing-body configurations p 211 A85-19534 TAIAA PAPER 85-01231 Studies of condensation effects on airfoil testing in a

transonic cryogenic tunnel [AIAA PAPER 85-0229]

p 274 A85-19603 Application of axisymmetric analogue for calculating heating in three-dimensional flows

[AIAA PAPER 85-0245] p 216 A85-19611 Measurements of water film characteristics on airfol surfaces from wind-tunnel tests with simulated heavy rain

[AIAA PAPER 85-0259] p 274 A85-19618 Subsonic pressure distributions near a wing-fin juncture a supersonic arrow-wing configuration with OD. wing-mounted vertical fins

p 217 A85-19628 [AIÃA PAPER 85-0276] Study of winglets applied to biplanes

p 217 A85-19631 [AIAA PAPER 85-0279] Euler calculations for multielement airfoils using Cartesian grids

[AIAA PAPER 85-0291] p 218 A85-19641 Spectral methods for modeling supersonic chemically reacting flow fields

[AIAA PAPER 85-0302] p 219 A85-19651 Designing a priority driven multi-frame rate flight

executive [AIAA PAPER 85-0309] p 268 A85-19656 Hypersonic characteristics of an advanced aerospace

plane [AIAA PAPER 85-0346] p 269 A85-19685

Determination of rarefied-flow aerodynamics of the Shuttle orbiter from flight measurements on STS-6 and STS-7

[AIAA PAPER 85-0347] p 219 A85-19686 An attached flow design of a noninterfering leading edge extension to a thick delta wing

[AIAA PAPER 85-0350] p 220 A85-19689 Recent advances in computational transonic aerodynamics

[AIAA PAPER 85-0366] p 221 A85-19699 Breakdown of the conservative potential equation

[AIAA PAPER 85-0367] p 221 A85-19700 Potential flow calculations and preliminary wing design in support of an NLF variable sweep transition flight

p 248 A85-19741 [AIAA PAPER 85-0426]

Correlation and analysis of oil flow data for an air-breathing missile model p 224 A85-19761 [AIAA PAPER 85-0452]

Experimental study of forward-located jet-interaction nozzles

[AIAA PAPER 85-0454] p 224 A85-19762 Efficient self-consistent viscous-inviscid solutions for unsteady transonic flow

[AIAA PAPER 85-0482] p 225 A85-19779 Application of a variational method for generating

adaptive grids [AIAA PAPER 85-0487] p 226 A85-19784

The application of some lifting-body reentry concepts to missile design

[AIAA PAPER 85-0497] p 279 A85-19791 Ground test experience with large composite structures

r commercial transports p 251 A85-21383 A thermoplastic polyimidesulfone p 282 A85-21483 for commercial transports Evaluation of a stalled airfoil analysis program

p 231 A85-21848 Shock-fitting solution of the supersonic flowfield in a

p 232 A85-21856 rounded internal corner

Scaling of airfoil self-noise using measured flow arameters p 304 A85-21858 parameters Nonreflecting boundary conditions for the complete unsteady transonic small-disturbance equation

p 290 A85-21875 Loads and Aeroelasticity Division research and technology accomplishments for FY 1984 and plans for FY 1985

[NASA-TM-863561 p 234 N85-15691 A comparative study of the nonuniqueness problem of the potential equation

[NASA-TP-2385] p 235 N85-15694 Aileron effectiveness for a subsonic transport model with high-aspect-ratio supercritical wing

[NASA-TM-85674] p 235 N85-15695 An exploratory study of finite difference grids for ansonic unsteady aerodynamics

p 235 N85-15696 [NASA-TM-84583] Comparison of analytical and experimental steadyand unsteady-pressure distributions at Mach number 0.78 for a high-aspect-ratio supercritical wing model with oscillating

control surfaces [NASA-TM-84589] p 235 N85-15697 Description of the insulation system for the Langley

0.3-Meter Transonic Cryogenic Tunnel [NASA-TM-86274] p 276 N85-15755

Effect of aerodynamic and angle-of-attack uncertainties on the May 1979 entry flight control system of the Space Shuttle from Mach 8 to 1.5

p 280 N85-15778 [NASA-TP-2365] Laminar heat-transfer distributions on biconics at incidence in hypersonic-hypervelocity flows

p 293 N85-16065 [NASA-TP-2213] Computer sizing of fighter aircraft

p 203 N85-16759 [NASA-TM-86351] Technology developments for laminar boundary layer control on subsonic transport aircraft

p 237 N85-16787 Turbulent drag reduction research

p 237 N85-16788 Study of winglets applied to biplanes

p 258 N85-16862 [NASA-TM-86350] Reference energy-altitude descent guidance: Simulator avaluation

[NASA-TP-23831 p 261 N85-16868 A cockpit-display concept for executing a multiple

glide-slope approach for wake-vortex avoidance [NASA-TP-2386] p 261 N8 p 261 N85-16869

Langley Mach 4 scramjet test facility [NASA-TM-86277] p 278 N85-16883

Advances in composites technology [NASA-TM-86353] p 284 N85-17048 Scientific and technical information output of the Langley

National Aeronautics and Space Administration. Lewis

Accelerated convergence for incompressible flow

Computational thermo-fluid dynamics contributions to

The Altitude Wind Tunnel (AWT) - A unique facility for

Analytical and physical modeling program for the NASA

Analytical determination of propeller performance

PMR polyimide composites for aerospace applications

Lewis Research Center's Altitude Wind Tunnel (AWT)

propulsion system and adverse weather testing

p 309 N85-17740

p 209 A85-19489

p 262 A85-19509

p 275 A85-19661

p 275 A85-19709

p 264 A85-20867

p 282 A85-21520

Research Center for calendar year 1984

Research Center, Cleveland, Ohio.

advanced gas turbine engine design

[NASA-TM-86336]

[AIAA PAPER 85-0058]

(AIAA PAPER 85-00831

[AIAA PAPER 85-0314]

[AIAA PAPER 85-0379]

[AIAA PAPER 85-03391

degradation due to ice accretion

calculations

CORPORATE SOURCE

- Microstructural development of protective Al2O3 p 283 A85-21650 scales Temperature distortion generator for turboshaft engine
- testing [NASA-TM-83748] p 200 N85-15658 Analytical modeling of circuit aerodynamics in the new
- NASA Lewis wind tunnel [NASA-TM-869121 p 234 N85-15688 Unsteady pressure measurements on a biconvex airfoil
- in a transonic oscillating cascade [NASA-TM-86914] p 234 N85-15689 The UH-1H helicopter icing flight test program: An
- /erview [NASA-TM-86925] p 242 N85-15702
- Effect of steady-state temperature distortion on inlet flow to a high-bypass-ration turbofan engine p 265 N85-15725 [NASA-TM-868961
- Engine cyclic durability by analysis and material p 267 N85-15744 testing
- Analytical and physical modeling program for the NASA Lewis Research Center's Altitude Wind Tunnel (AWT) [NASA-TM-86919] p 276 N85-15757 The NASA Attitude Wind Tunnel (AWT): Its role in
- advanced icing research and development [NASA-TM-86920] p 276 N85-15758 High temperature thermocouple and heat flux gauge
- using a unique thin film-hardware hot juncture p 295 N85-16096 [NASA-TM-86898]
- Integrated exhaust gas analysis system for aircraft turbine engine component testing
- [NASA-TP-2424] p 295 N85-16100 Research and technology highlights of the Lewis **Research Center**
- [NASA-TM-86899] p 309 N85-17928 National Aeronautics and Space Administration.
- Marshall Space Flight Center, Huntsville, Ala.
- Status of warm fog dispersal research [AIAA PAPER 85-0010] p 2
- p 272 A85-19456 National Aerospace Lab., Amsterdam (Netherlands). Structural load measurements on a Northrop NF-5A p 253 N85-15667
- Overview of the AGARD SMP activities on turbine engine materials technology in the 1972 1982 period p 266 N85-15738
- Functional built-in-test in a pipelined image processor p 202 N85-16740
- Recent advances in computational methods to solve the high-lift multi-component airfoil problem
- p 236 N85-16774 Design of an airfoil leading edge slat using an inverse
- Engineering property comparisons of PM and IM aluminum alloy forgings [AD-B08814661]
- [AD-B0881466L] p 298 N8 Naval Air Development Center, Warminster, Pa. Navy operational loads data sources and systems
- p 253 N85-15668 Analysis of the flow field about a T-45 using PANAIR
- p 236 N85-15699 [AD-A146811] Standard Attitude Heading Reference System (SAHRS)
- p 246 N85-16804 full scale development program S-3A ballast block final design and engineering tests
- p 243 N85-16842 p 284 N85-17058 [AD-A147685] Repair of composites
- Naval Civil Engineering Lab., Port Hueneme, Calif.
- Hangar heating and energy conservation manual AD-A147893] p 277 N85-15762 [AD-A147893]
- Naval Electronic Systems Command, Washington, D. C.
- A weapon system design approach to diagnostics p 203 N85-16752
- Naval Postgraduate School, Monterey, Calif. Control system design language implementation of a
- gas turbine starting controller p 266 N85-15732 [AD-A147896] The visibility climatology of McMurdo Sound-Williams
- Field, Antarctica [AD-A148108] p 300 N85-17492
- Naval Research Lab., Washington, D. C. Using the control system design environment in the design of a data link receiver unit for the Coast Guard
- HH-65A helicopter [AD-A148624] p 271 N85-16880 Naval Ship Research and Development Center,
- Bethesda, Md. Circulation control: A bibliography of DTNSRDC
- research and selected outside references: Update [AD-A146966] p 201 N85-15661 [AD-A146966]
- Naval Surface Weapons Center, Dahlgren, Va. Joint service design for testability program
- p 296 N85-16733 Naval Surface Weapons Center, White Oak, Md.
- A theoretical view on the stress analysis of fully inflated parachute canopies p 239 N85-16835 AD-A1483871

- New Mexico Inst. of Mining and Technology, Socorro. A study of the effects of triggered lightning [AD-A148296] p 300 N85-17494
- Nielsen Engineering and Research, Inc., Mountain
- View, Calif. of crucitorm Prediction ali-movable control
- characteristics at transonic speeds p 239 N85-16832 [AD-A147291]
- North Carolina State Univ., Raleigh. Application of axisymmetric analogue for calculating eating in three-dimensional flows
- p 216 A85-19611 (AIAA PAPER 85-02451
- Euler calculations for multielement airfoils using Cartesian orids [AIAA PAPER 85-0291] p 218 A85-19641
- Application of a variational method for generating adaptive grids [AIAA PAPER 85-0487] n 226 A85-19784

Ο

- Oak Ridge National Lab., Tenn. Evaluation of arctic test of improved tritium radioluminescent lighting [AD-A148215] p 278 N85-16884
- Office National d'Etudes et de Recherches
- Aerospatiales, Parls (France). Life prediction at high temperature under multiaxial loading p 267 N85-15745
- Detailed study of the flow around a multi-element airfoil. Comparison with calculations omparison with calculations p 236 N85-16775 Interest of internal bleed for a two-dimensional air intake
- operating in a wide Mach number range (1.8-3 plus) p 237 N85-16793 Office National d'Etudes et de Recherches
- Aerospatiales, Toulouse (France). Application of two and three-dimensional criteria for calculating transitions and boundary layers over swep p 237 N85-16783 wings Ohio State Univ., Columbus.
- Detailed measurements of the flowfield in the vicinity of an airfoil with glaze ice [AIAA PAPER 85-0409]
- p 222 A85-19730 Okiahoma State Univ., Stillwater.
- Flow visualization of lateral jet injection into swirling crossflow [AIAA PAPER 85-0059]
- p 209 A85-19490 (AIAA PAPER 85-0059) p 209 A85-19490 Old Dominion Univ., Norfolk, Va. Ultrasound instrumentation for the 7 inch Mach seven
- tunnol [NASA-CR-174277] p 305 N85-16586
- NASA three-laser airborne differential absorption lidar system electronics
- [NASA-CR-174293] p 298 N85-17353

Ρ

- Pacific Missile Test Center, Point Mugu, Calif. Effective life cycle software support: A study in discipline and versatility p 302 N85-16746
- PEDA Corp., Palo Alto, Calif. three-dimensional
- Real-gas flowfields about configurations p 231 A85-21830 Pennsylvania State Univ., University Park.
- A class of airfoils having finite trailing edge pressure gradients
- [AIAA PAPER 85-0206] p 215 A85-19590 Study of winglets applied to biplanes [AIAA PAPER 85-0279] p 217 A85-19631
- Effects of friction dampers on aerodynamically unstable p 265 A85-21866 rotor stages Pratt and Whitney Aircraft, West Palm Beach, Fla.
- Improvement of the corrosion resistance of turbine engine bearings [AD-A147430]
- p 265 N85-15731 Evaluation of jet fuel deposit kinetics. Lot 4 [AD-A147196]
- p 284 N85-15922 Pratt and Whitney Aircraft Group, West Palm Beach, Fla
- View of future requirements for engine cyclic durability by analysis and testing p 267 N85-15751
- Princeton Univ., N. J. Structure of the wall pressure fluctuations in a shock-induced separated turbulent flow
- [AIAA PAPER 85-0179] p 214 A85-19571 The distortion of a supersonic turbulent boundary layer by bulk compression and surface curvature
- (ÁIAA PAPER 85-0299) p 218 A85-19648 Purdue Univ., Lafayette, Ind.
- Three dimensional aerodynamics of an annular cascade in a non-uniform inlet flow
- [AIAA PAPER 85-0174] p 213 A85-19567 Vibration tailoring of advanced composite lifting surfaces' p 290 A85-21846

Sikorsky Aircraft, Stratford, Conn.

Time series analysis of closed-loop pilot vehicle p 271 N85-16876 dynamics

R

- Racal Avionics Ltd., New Malden (England).
- Integrated control and display systems for helicopter battlefield mission management p 260 N85-16805 p 260 N85-16805 RAND Corp., Santa Monica, Calif.
- Managing recoverable aircraft components in the PPB and related processes: Executive summary
- [AD-A146806] p 308 N85-16667 Estimating wartime support resource requirements. Statistical and related policy issues
- p 308 N85-16685 [AD-A147923] Rensselaer Polytechnic Inst., Troy, N. Y. Supercritical airfoil drag reduction by passive shock
- vave/boundary layer control in the Mach number range 75 to .90 [AIAA PAPER 85-0207] p 215 A85-19591
- Research Inst. of National Defence, Stockholm (Sweden).
- NyKINM, a further development of KINM 22
- p 256 N85-15720 [FOA-C-20559-D8(E3)] p 256 N85-15720 Impressions from a study tour in Finland concerning fiber reinforced plastics, June 1984
- p 283 N85-15831 [FOA-C-20552-D2(E4,F9)] Research Triangle Inst., Hampton, Va. The Mission Oriented Terminal Area Simulation
- (MOTAS) [AIAA PAPER 85-0308] p 274 A85-19655
- Research Triangle Inst., Research Triangle Park, N.C. Effects of aircraft and flight parameters on energy-efficient profile descents in time-based metered
- [NASA-CR-172338-ADD] p 245 N85-15706 Rockwell International Corp., Los Angeles, Calif.
- Joined wing transonic design and test validation p 239 N85-16834 [AD-A148355] Rohde and Schwartz, Munich (West Germany).
- Development, production and testing of central control and display unit for helicopters [BMFT-FB-W-84-039]
- p 261 N85-16871 Rolls-Royce Ltd., Bristol (England). Monitoring engine thermal stresses

Rolls-Royce experience with thermal barrier coatings

Flexible manufacturing system for the production of

Helicopter active control with rotor blades relaxation

Rose Engineering and Research, Inc., Incline Village,

[AD-A146755] p 294 N85-16067 Royal Aircraft Establishment, Farnborough (England).

Disc fatigue life predictions for gas turbine engines

compressibility on lift and drag in the RAE 5m pressurized

On-board processing for linescan sensors in miniature

Air traffic management concepts for the UK in the 1990's:

S

Development of a Navier-Stokes rotor and stator

Selenia S.p.A., Rome (Italy). Equipment for preflight test of an Electronic Countermeasures (ECM) avionic system

Composite curved frames for helicopter fuselage

Scientific Research Associates, Inc., Glastonbury,

The effect of changes in the angle of incidence in the

Rolls-Royce Ltd., Derby (England).

The aircraft engine of the future [PNR-90226]

Rolls-Royce Ltd., London (England).

Nev. Aero-optics experimental techniques

event of a richochet at a float step

Investigations into the effects

Royal Signals and Radar Establishment, Malvern

[RAE-TRANS-2120]

low-speed wind tunnel

[RAE-TM-SPACE-327]

A review of recent RSRE work

Sikorsky Aircraft, Stratford, Conn

unmanned aircraft

(England).

Conn

analysis

structure

[AD-A146967]

[AD-A147850]

[BLL-PNR-90237-(899.3153)]

[PNR-902221]

aircraft parts

Rome Univ. (Italy).

p 266 N85-15735

p 268 N85-16875

p 285 N85-17152

p 297 N85-17159

p 270 N85-16819

p 255 N85-15712

p 267 N85-15743

of scale and

p 236 N85-16773

p 261 N85-16870

p 246 N85-16853

p 294 N85-16070

p 293 N85-15949

p 252 A85-21396

C-5

Societe de Fabrication d'Instruments de Mesure SFIM

Societe de Fabrication d'Instruments de Mesure,

- Massy (France). A digital piloting system for the combat helicopter p 260 N85-16806
- Spectron Development Labs., Inc., Costa Mesa, Calif. Aero-optics experimental techniques [AD-A146755] p 294 N85-16067
- SRI International Corp., Menio Park, Calif. Analysis of middle distillate fuels by high resolution field ionization mass spectrometry
- p 285 N85-17153 [AD-A147724] Stanford Univ., Calif.
- Circulation control airfoils Past, present, future [AIAA PAPER 85-0204] p 215 A85-19588
- Disturbance-wave interactions in flows with crossflow [AIAA PAPER 85-0494] p 226 A85-19788
- Writing executable assertions to test flight software [SU-CRC-TR-84-14] p 301 A85-21973 STTE, Paris (France). The embedded test (BIT): Impact on the total cost of
- p 202 N85-16734 possession ATE user's view on design for maintainability
- p 202 N85-16737 Sunstrand Energy Systems, Rockford, III. Design and test of a four channel motor for
- electromechanical flight control actuation [NASA-CR-171838] p 297 N85-17294
- System Planning Corp., Arlington, Va. Speed benefits of tilt-rotor designs for LHX [NASA-CR-166437]
- p 255 N85-15717 Systems and Applied Sciences Corp., Hampton, Va. Numerical solution of the Euler equations for high-speed,
- blended wing-body configurations [AIAA PAPER 85-0123] p 211 A85-19534 Systems Technology, Inc., Mountain View, Calif.
- Mission-oriented requirements for updating MIL-H-8501. Volume 1: STI proposed structure [NASA-CR-177304-VOL-1] p 271 N85-16877
- Mission-oriented requirements for updating MIL-H-8501. Volume 2: STI background and rationale
- p 271 N85-16878 [NASA-CR-177304-VOL-2]

Т

- Technion Israel Inst. of Tech., Haifa. Tail behaviour for suprema of empirical processe
- p 303 N85-17613 [AD-A147629] Technische Hogeschool, Delft (Netherlands).
- A comparison of finite volume flux vector splittings for the Euler equations p 211 A85-19533 [AIAA PAPER 85-0122]
- Design studies of thick laminar flow airfoils for low speed flight employing turbulent boundary layer suction over the rear part p 257 N85-16786
- Pneumatic turbulators: A device for drag reduction at Reynolds numbers below 5 million p 257 N85-16791 Tel-Aviv Univ. (Israel).
- multistage time-stepping scheme for the Navier-Stokes equations [AIAA PAPER 85-0035] p 207 A85-19472
- Tennessee Univ. Space Inst., Tullahoma.
- Contamination and distortion of steady flow field induced by discrete frequency in aircraft gas turbines [AD-A147092] p 294 N85-16073
- Texas A&M Univ., College Station, Analytical determination of propeller performance
- degradation due to ice accretion [AIAA PAPER 85-0339] p 264 A85-20867
- Analysis and testing for rotordynamic coefficients of turbulent annular seals with different, directionally-homogeneous surface-roughness treatment for rotor and stator elements
- [ASME PAPER 84-TRIB-31] p 289 A85-21293 Experimental aerodynamic characteristics of an NACA Texas Technological Univ., Lubbock.
- Flow visualization of lateral jet injection into swirling crossflow
- [AIAA PAPER 85-0059] p 209 A85-19490 Thomson-CSF, Issy les Moulineaux (France).
- p 259 N85-16801 Map display for helicopters Toledo Univ., Ohio.
- Full two-dimensional transient solutions of electrothermal aircraft blade deicing
- [AIAA PAPER 85-0413] p 248 A85-19734 Turbomeca S. A. - Brevets Szydlowski, Bordes (France).
- Design and test requirements for development of today's engines p 266 N85-15737 Tuskegee Inst., Ala.
- An improved computer model for prediction of axial gas turbine performance losses
- [NASA-CR-174246] p 265 N85-15724
- C-6

- United Technologies Corp., East Hartford, Conn. Calculation of confined swirling flows
 - p 285 A85-19491 [AIAA PAPER 85-0060] A linearized unsteady aerodynamic analysis for transonic cascades
- p 229 A85-20744 United Technologies Research Center, East Hartford, Conn.
- Three-dimensional inviscid flow analysis of turbofan forced mixers
- [AIAA PAPER 85-0086] p 210 A85-19510 A procedure for the calculation of supersonic flows with strong viscous-inviscid interaction
- [AIAA PAPER 85-0166] p 213 A85-19562

- VDO-Luftfahrtgeraete Werk Adolf Schindling G.m.b.H., Frankfurt (West Germany).
- Realization and testing of an experimental color display system for general aviation helicopters and aircraft [BMFT-FB-W-84-042] p 262 N85p 262 N85-16872
- Vigyan Research Associates, Inc., Hampton, Va. An attached flow design of a noninterfering leading edge extension to a thick delta wing
- [AIAA PAPER 85-0350] p 220 A85-19689 Virginia Polytechnic Inst. and State Univ., Blacksburg.
- Experiments on the stability of crossflow vortices in swept-wing flows [AIAA PAPER 85-0493] p 231 A85-20873
- GC-FTIR (Fourier Transform Infrared Spectrometry) of iet fuels
- [AD-A148272] o 285 N85-17155 An improved source model for aircraft interior noise studies
- [NASA-CR-172517] p 305 N85-17668

W

Washington Univ., Seattle.

- Metallurgical and mechanical phenomena due to rubbing of titanium against sintered powder Nichrome p 291 A85-22281
- Waterloo Univ. (Ontario). Transient motion of hypersonic vehicles including time
- history effects [AIAA PAPER 85-0201] p 268 A85-19585
- Westland Aircraft Ltd., Yeovil (England). Helicopter data acquisition in WHL
- p 254 N85-15676 Westland Helicopters Ltd., Yeovil (England). The design and development of an integrated core
- system for battlefield helicopters p 260 N85-16811 Weston (Roy F.), Inc., West Chester, Pa. Installation restoration program. Phase 2: Stage 1
 - problem confirmation study, Duluth International Airport Duluth, Minnesota
- [AD-A148318] p 278 N85-16885 Wichita State Univ., Kans.
- Icing tunnel tests of Electro-Impulse De-Icing of an ngine inlet and high-speed wings
- [AIAA PAPER 85-0466] p 241 A85-20872

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Supplement 187)

MAY 1985

Typical Foreign Technology Index

Listing



Listings in this index are arranged alphabetically by country of intellectual origin. The title of the document is used to provide a brief description of the subject matter. The page number and the accession number are included in each entry to assist the user in locating the citation in the abstract section.

Δ

AUSTRALIA

- Stability of squeeze film damped multi-mass flexible rotor bearing systems
- [ASME PAPER 84-TRIB-45] p 289 A85-21296 Calculation of the velocity field generated by a helicopter main and tail rotors in hover
- [AD-A147731] p 239 N85-16833

С

CANADA

- Transient motion of hypersonic vehicles including time history effects
- [AIAA PAPER 85-0201] n 268 A85-19585 Characteristic motions for simulation of post-stall anoeuvres and flight instabilities p 269 A85-21679
- Nonlinear simulation of flight along wind compensating p 245 A85-21838 curved glidepaths Skirt material effects on air cushion dynamic heave
- stability p 307 A85-21840 Analysis of a split-flow inertial particle separator by finite p 231 A85-21845 elements
- Computation of choked and supersonic turbomachinery flows by a modified potential method
- p 232 A85-21859 Construction and extension of airports - Legal procedure
- and practice in Canada p 307 A85-21944 A path model of aircraft noise annoyance
- p 304 A85-22071 TUTOR (CL-41A) tail flight load survey
- p 254 N85-15678 Problems and possibilities for life extension in gas turbine components p 267 N85-15742
- An update of the Canada/USA augmentor-wing p 257 N85-16781 project technological Operational requirements versus p 204 N85-16798 capabilities

Development of a Helicopter integrated navigation p 245 N85-16802 system CHINA, PEOPLE'S REPUBLIC OF

Newton iteration formulas for correcting temperature and pressure in thermodynamic calculation of rocket engines p 279 A85-20226

Matrix solution of compressible flow on S(1) surface through a turbomachine blade row with splitter vanes or p 227 A85-20228 tandem blades A new approach to some hybrid aerodynamic problems

- of airfoil cascades on a general streamsheet of revolution. p 228 A85-20229 Complete three-dimensional flow solution of a cascade
- incorporating splitter vanes of arbitrary geometry p 228 A85-20230
- Calculation and analysis of the three-dimensional flow in centrifugal compressor impellers p 228 A85-20231 A method for calculating the performance of ejector p 287 A85-20232 nozzles
- The fundamental equations of 3-dimensional two-phase particulate gas flow and a twofold stream surfaces model of solution for particulate gas flow in turbomachines
- p 228 A85-20233 Some improvements on an annular combustor of AI type turbojet engine p 264 A85-20235
- A linearly correcting method of deviation function for considering the influence of pressure on the thermodynamic properties of combustion gas
- p 304 A85-20236 On the variety of type discrimination criteria of equations
- on S1 and S2 stream surfaces in turbomachine p 228 A85-20238

A fast algorithm for solving the conservative transonic S1 full potential equation employing non-orthogonal curvilinear coordinates and non-orthogonal velocity p 228 A85-20239 components A stream function relaxation method for solving transonic

- **S1** stream surface with respect to non-orthogonal p 228 A85-20240 curvilinear coordinates Effect of inlet and outlet flow conditions on the flow
- and performance of subsonic two-dimensional diffuser p 228 A85-20241
- Determination of surging line of two-spool axial flow compressor with cropped fan stages at low speed by use p 264 A85-20242 of parallel compressor theory
- Experimental investigation of backswept centrifugal p 264 A85-20243 compressor impeller. I method of forecasting active constraint with the
- applications to structural optimization p 291 A85-22445 The development of digital attitude controllers - Its past,
- p 302 A85-22449 present and future International aviation (selected articles) AD-A148704] p 204 N85-16762
- **CZECHOSLOVAKIA** Calculation of the minimum-time loop maneuver for jet
- aircraft p 269 A85-19876 Microprocessor control of turboprop engines
- p 263 A85-19877 History of the development and manufacture of flight simulators in Czechoslovakia and the rest of the world
- p 275 A85-19878 The hydraulic and electrohydraulic elements used in
- p 287 A85-19886 flight simulators

F

FRANCE

- Computation of three-dimensional flows for application to transonic compressors
- [ONERA, TP NO. 1984-146] p 204 A85-19260 A sensor for detection of unsteady distortion maxima in air intakes
- [ONERA, TP NO. 1984-148] p 205 A85-19262 Aerodynamic studies linked to the development of deplovable nozzles

p 205 A85-19263 [ONERA, TP NO. 1984-149] A comparison of different three-dimensional singularity methods for modelling internal flows [ONERA, TP NO. 1984-150] p 205 A85-19264

Noise of an airfoil in a flow	- 000	
[UNEHA, TP NO. 1984-155] The accuracy of trials with powered	p 303 1/2 m-	A85-19269
S2MA wind tunnel	172 100	
[ONERA, TP NO. 1984-156]	p 272	A85-19270
Tests of air inlets on civil aircraft		
[ONERA, TP NO. 1984-157]	p 272	A85-19271
lests, in the transonic regime, of a	a model ar (9 inc	motorized
S1MA wind tunnel	a (5 nic	nesj ur ule
[ONERA, TP NO. 1984-158]	p 272.	A85-19272
Interpretation of fatigue crack growth	in alumi	nium alloys
under programmed block loading	p 281	A85-20790
The most spectacular equipment - F	p 264 FTW	A85-21420
	p 276	A85-21422
Creation and extension of airports	- Proc	edures and
practice	p 307	A85-21945
Calculation of three-dimens	anal	unsteady
moompressure nows by a voltex met	p 291	A85-22240
Renegade 250 - Flight evaluation or	boat rid	de?
	p 252	A85-22273
ONERA - The aeronautics superco	mputer	IS put into
Service Operational Loads Data	p 302	A65-222/4
[AGARD-CP-375]	p 201	N85-15664
Structural flight load measurement	demon	stration of
structural integrity	p 254	N85-15670
Aeroelastic analysis and the ide	n 254	on of flight NR5.16670
Keeping up with operational loads	in the	French Air
Force: Defining new equipment	p 292	N85-15681
Engine Cyclic Durability by Analysis	and Te	sting
[AGARD-CP-368]	p 266	N85-15733
Design and test requirements for dev	elopme	NOE 16727
life prediction at high temperate	µ∠00 Ire unde	r multiavial
loading	p 267	N85-15745
All-composite Airbus empennage	p 284	N85-15931
Design for Tactical Avionics Mainta	inability	
[AGARD-CP-361]	p 201	N85-16731
Objectives in studying the maintai	nability	of aircraft
systems	p 202	N85-16732
The embedded test (BIT): Impact	on the t n 202	OTAL COST OF
Improvement of Aerodynamic Pe	rformen	ce Through
Boundary Layer Control and High Lift	System	s S
[AGARD-CP-365]	p 204	N85-16771
Detailed study of the flow around a	multi-ele	ment airfoil.
Comparison with calculations	p 236	N85-16775
Application of two and three-dime	nsional	criteria for
calculating transitions and boundary winns	n 297	N85-16783
Interest of internal bleed for a two-di	mension	al air intake
operating in a wide Mach number ran	ge (1.8-	3 plus)
	p 237	N85-16793
Helicopter Guidance and Control Sy	sterns fo	or Battlefield
Support	- 204	NOS 46707
[AGARD-CP-359] Map display for bolissontem	p 204	N85.16801
A digital piloting system for the con	µ∠ə9 nhat hei	i uoo- 1000 l
~ aignal priviling system for the con	p 260	N85-16806
Recent methods for calibrating the	ne aner	nometry of
helicopters at low speeds	p 260	N85-16809
A simulator for studying helicopter	weapon	s systems
	n 277	N85_16816

- Results of S5 CH tests with an ARL (Aerospace Research Laboratory) cascade [NASA-TM-77510] p 278 N85-16882
- Composite structure repair, addendum [AGARD-R-716-ADD] p 284 N85-17057

G

GERMANY, FEDERAL REPUBLIC OF

Linearized potential flow analysis of complex aircraft configurations by HISSS, a higher order panel method p 217 A85-19632 [AIAĂ PAPER 85-0281]

INDIA

The influence of camber variation on the aerodynamics of civil transport aircraft p 220 A85-19691 [AIAA PAPER 85-0353] Renefits and costs of powered engine simulation at low

soreds [AIAA PAPER 85-0381] p 263 A85-19710

Vortex path in the supersonic wake of a rough even p 226 A85-19821 olate The division of tasks in modern air transport and its

effect on the liability of the air carrier - The concept 'agents' in the so-called Warsaw Convention p 307 A85-19826

Investigations for the use of an active control in p 269 A85-19828 aircraft Precalculation of rotating stall in multistage axial

p 287 A85-19832 compressors A three-dimensional Kalman filter for short observation

times to extrapolate flight trajectories p 301 A85-19835

Experimental methods for wind-tunnel flight-mechanics investigations using dynamically similar aircraft models p 249 A85-19836

Reflector antennas with directional effect in the near-field Characteristics and applications p 287 A85-19837

Computation of transonic inlet flows p 227 A85-19844

Analysis of fatal accidents involving light aircraft weighing up to two tons and their causes in the context of flight medicine p 241 A85-19846

Circulation around thick wings with free vortices p 227 A85-19848 procedure optimization of the

A procedure for the aerothermodynamic design of multistage axial p 227 Å85-19851 compressors A subdomain finite element method for solving the conservative full potential equation for transonic profile

p 227 A85-19854 p 227 A85-20074 flows Survey on jet instability theory

The unambiguous in-flight determination of propeller rotational noise in aircraft with four-cycle combustion endines p 304 A85-20650

Air breathing space transport vehicles with wings p 280 A85-20909

Energy absorbing qualities of fiber reinforced plastic p 282 A85-21393 tubes National report - The Federal Republic of Germany

p 308 A85-21949 Investigations of the longitudinal flow in corner configurations in the hypersonic regime. II - Corners p 232 A85-22146

between swept wedges Operational loads data evaluation for individual aircraft p 253 N85-15669 fatigue monitoring

Evaluation of operational loads to verify structural p 254 N85-15677 design Flight testing of Litton laser gyro strapdown system

LTN-90 for general aviation p 245 N85-15709 [DFVLR-MITT-84-16]

Comparison between the properties of conventional wrought and powder metallurgical alloys for turbine disc p 283 N85-15739 applications

Experiences with the use of a side-strut model support ystem for high angles of attack in the Trinsonik wind tunnel TMK

[DFVLR-MITT-84-09] p 277 N85-15763 Clearance flow-generated transverse forces at the rotors of thermal turbornachines

[NASA-TM-77292] p 295 N85-16180 The influence of fastener flexibility on load transfer and fatigue life predictions for multirow bolted and riveted ioints

[LBF-FB-172/84] p 296 N85-16219 p 202 N85-16739 Built-in-test for first line testing Maintainability. An ILS effort to manipulate LCC

p 202 N85-16743 Documentation and separate test program development is most important for test/maintenance

p 203 N85-16745 Experience in using on-aircraft software for testing p 302 N85-16747 integrated systems

Theoretical study of boundary-layer control p 237 N85-16784 Drag reduction due to boundary-layer control by combined blowing and suction p 237 N85-16785

Active and passive shock/boundary layer interaction control on supercritical airfoils p 238 N85-16795 Evaluation of nose, roof, and mast mounted sensor platforms for piloting and sighting, integrated in future

combat helicopters p 260 N85-16808 LPI-radar for helicopter obstacle warning p 297 N85-16810

Advanced flight simulation for helicopter development p 277 N85-16815

Flight tests with a new helicopter Force Feel System p 257 N85-16818 (FFS)

Flight research on visusl aids and navigation equipment for helicopter low-level flight at night

p 261 N85-16820 Theoretical contributions to transonic flow analysis for transport aircraft

[BMFT-FB-W-84-036] p 239 N85-16838 Directions of the West German Ministry of Transport for education and control of airline personnel (section 3

chapters 2 and 12) p 243 N85-16848 Directions of the West German Ministry of Transport for education and control or airline personnel, Report 6;

chapters 3/A and 3/B p 244 N85-16849 Measurement of signal separation between radio service and air navigation service

p 246 N85-16860 [IRT-TB-B-40/82] Development, production and testing of central control and display unit for helicopters

[BMFT-FB-W-84-039] p 261 N85-16871 Realization and testing of an experimental color display

system for general aviation helicopters and aircraft [BMFT-FB-W-84-042] p 262 N85-16872 Flight test of the Open Loop Gust Alleviation (OLGA)

system [BMFT-FB-W-84-038] p 271 N85-16881

Activities report on West German civil airports. Part 1: Text

[ISBN-3-87977-055-7-PT-1] p 279 N85-16887 Activities report for the West German Civil Airports. Part s Tables

[ISBN-3-87977-055-7-PT-2] p 279 N85-16888 Composite repair of aircraft structures

p 285 N85-17059 Flexible manufacturing system for the production of aircraft parts

[BLL-PNR-90237-(899.3153)] p 297 N85-17159 FRG ceramic engine components (PET)

p 297 N85-17193 Description of MBB computerized design techniques fo A320 p 303 N85-17194 Aeroacoustics at the DFVLR Brunswick Research

Center: A survey on recent and current activities [DFVLR-MITT-84-14] p 306 N85-17677

I

INDIA A theoretical study of stability of a rigid rotor under the influence of dilute viscoelastic lubricants

[ASME PAPER 84-TRIB-17] p 289 A85-21278 Flight testing of a wing section with laminar flow control p 233 A85-22227

Design of lifting symmetric supercritical airfoils p 233 A85-22228 Influence of blowing rate and injection angle on the

performance of a film-cooled blade p 265 A85-22231 Universal matrices to obtain thermal load vectors for

the family of anisotropic plane triangular finite elements p 291 A85-22232 Flow behind an attached shock wave in a radiating

n 233 A85-22308 das INTERNATIONAL ORGANIZATION

Advanced technology to Europear key competitiveness p 200 A85-21680 ISRAEL

Tail behaviour for suprema of empirical processes [AD-A147629] p 303 N85-17613 ITALY

A quasi-conservative lambda formulation

[AIAA PAPER 85-0088] p 210 A85-19511 Flight parameters recording for structure fatigue life monitoring p 292 N85-15682 Equipment for preflight test of an Electronic

Countermeasures (ECM) avionic system p 293 N85-15949

Study and realisation of a 3rd level maintenance center p 202 N85-16735 based on ATE systems utilization Reliable software design for avionics and space applications p 303 N85-16751

Turbulent bubbles behind airfoils and wings at high angle of attack p 296 N85-16779

Tactical HF communication for military helicopters using p 297 N85-16807 the NVIS mode Helicopter active control with rotor blades relaxation p 270 N85-16819

J

JAPAN

An improved version of the LTRAN2 for high frequency p 205 A85-19401 domain Theoretical study of blockage effect of wind-tunnel wall on wake of two-dimensional flat plate normal to plane wall p 272 A85-19402

FOREIGN TECHNOLOGY INDEX

Experimental investigation of blockage effect of upper wall of wind-tunnel of wake of two-dimensional flat plate p 272 A85-19403 normal to plane boundary Comparative study of various quadratures for subsonic lifting surface chordwise integrals p 205 A85-19404 An analysis of the flow past an S-shaped rotor by discrete vortex model p 206 A85-19405 Application of laser interferometry to density p 206 A85-19406 measurements in free jets Computational study of circulation control with suction [AIAA PAPER 85-0042] p 208 A85-19477 Numerical study on the dynamic stall process of a NACA 0012 airfoil [AIAA PAPER 85-0128] p 212 A85-19539 Computation of unsteady shock-induced vortex separation [AIAA PAPER 85-0183] p 214 A85-19573 Review of the origin of Japanese Industrial Standard p 280 A85-20545 Off-design point characteristics of the precooled gas turbine cycle with liquefied hydrogen as fuel p 289 A85-20884 Drag of the fundamental shapes of parachutes p 231 A85-20998 p 308 A85-21948 Report from Japan Turbo fluid machinery and diffusers p 298 N85-17363 [NASA-TM-77467]

Ν

NETHERLANDS

Structural load measurements on a Northrop NF-5A p 253 N85-15667 Overview of the AGARD SMP activities on turbine engine

materials technology in the 1972 - 1982 period p 266 N85-15738

Functional built-in-test in a pipelined image processor p 202 N85-16740

Recent advances in computational methods to solve the high-lift multi-component airfoil problem p 236 N85-16774

Design of an airfoil leading edge slat using an inverse

aerodynamic calculation method p 256 N85-16777 Design studies of thick laminar flow airfoils for low speed flight employing turbulent boundary layer suction over the p 257 N85-16786 rear part

Pneumatic turbulators: A device for drag reduction at Reynolds numbers below 5 million N85-16791 p 257 Engineering property comparisons of PM and IM

aluminum alloy forgings [AD-B0881466L]

p 298 N85-17398

P

PORTUGAL

ATE user's view on design for maintainability p 202 N85-16737

S

SAUDI ARABIA

Variable-temperature water tunnel for high Reynolds

[AIAA PAPER 85-0051] p 273 A85-19483 SOUTH AFRICA, REPUBLIC OF A global technique for aircraft stability and control

analysis p 270 A85-21681 Prediction of performance of aircraft gas turbines

p 264 A85-21682

The development of a finite element model of an aircraft vertical stabilizer for vibration analysis p 290 A85-21683

SWEDEN

Crossflow drag of finite-length rectangular wing-bodies (AIAA PAPER 85-0451) p 224 A85-19760 Experimental and theoretical analysis of laminar separation bubbles [AIAA PAPER 84-2201] p 288 A85-20874 Report from Sweden p 307 A85-21946 NyKINM, a further development of KINM 22 [FOA-C-20559-D8(E3)] p 256 N85-15720 Impressions from a study tour in Finland concerning fiber reinforced plastics, June 1984 [FOA-C-20552-D2(E4,F9)] p 283 N85-15831

Full scale experiments into the use of large eddy breakup devices for drag reduction on aircraft p 257 N85-16790

SWITZERLAND

	Speech recognizion making progress	- Direc	i voice iripu
8	a promising infant	p 244	A85-19183
	From AV-8B to the ASTOVL	p 246	A85-19184
	Mi-28 - The Soviets create Havoc	p 250	A85-20147
	Wind shear - Taming the killer	p 241	A85-20148
	•	•	

FOREIGN TECHNOLOGY INDEX

On the excitations due to the periodic structure of p 288 A85-20800 turbomachines Construction and extension of airports - National report p 308 A85-21947 on Switzerland Experiences with the material bevaviour and high temperature low cycle fatigue life prediction of the IN 738 blading alloy p 292 N85-15746

Т

TAIWAN

Theoretical study on supersonic jet plumes p 206 A85-19439

U U.S.S.R. p 244 A85-19805 Aviation radar Combat aircraft: Flight vehicles, power plants, and their p 199 A85-19812 maintenance A numerical study of three-dimensional radiation fields in problems of supersonic flow past segmental bodies p 227 A85-20025 Current problems in aviation science and technology p 199 A85-20451 Determination of the optimal parameters of aircraft structural elements in the form of sandwich plates and shallow shells with a honeycomb filler p 287 A85-20452 Computers and progress in aviation p 199 A85-20453 Theory of vibration conduction as a method for calculating the vibration of complex structures p 287 A85-20454 Training and research CAD system of the Moscow Aviation Institute and experience in its use p 199 A85-20455 Current problems in the theory of plates and shells in aircraft p 287 A85-20459 Selection of rational models in the optimal planning of p 288 A85-20460 aeromechanical experiments Design of load-bearing aircraft structures A85-20463 p 288 Some problems in the development of CAD systems p 200 A85-20466 Loading characteristics of VTOL aircraft and their effect on the remaining life of the aircraft p 250 A85-20469 Aeroelastic stability and vibration of layered plates and cylindrical shells p 288 A85-20472 A formalism for the design problem of aircraft system niversalization p.250 A85-20473 Hypersonic multicycle gas jet with a strongly universalization underexpanded stream at the nozzle section p 229 A85-20554 Conical bodies with a star-shaped transverse cross section, having a reserve of static stability p 229 A85-20557 Hypersonic chemically nonequilibrium viscous shock layer on wings with a catalytic surface p 229 A85-20561 Effect of the arrangement of apertures on the gain coefficient during asymmetric gas injection into a Laval nozzie p 229 A85-20562 Optimization of flutter characteristics p 288 A85-20828 Oxidation and stabilization of jet fuels p 281 A85-20925 Harmonic oscillations of a rectangular wing with a circulation variable over the span p 231 A85-21656 Stress analysis and shaping of the canopy of a square parachute p 242 A85-21668 Optimal control of flow of a viscous incompressible p 290 A85-22105 fluid Calculation of the hydrodynamic characteristics of potyplanes p 290 A85-22113 Calculation of friction and heat transfer in turbulent flow of a compressible gas in a plane duct D 291 A85-22114 Ill-posed problems in perturbation theory (Asymptotic p 233 A85-22364 methods of mechanics) Development of asymptotic algorithms in the Polet p 233 A85-22366 package of applications programs The full-approximation method in the theory of transonic flows p 233 A85-22367 Approximate solution of a nonlinear problem of flow past a thin airfoil profile near a support surface p 233 A85-22368 Extremum problem concerning a wing with a maximum p 234 A85-22370 gradient of lift force An extremum problem concerning the shape of a body of revolution in supersonic gas flow p 234 A85-22371 Design of a STOL aircraft with jet assisted takeoff p 253 A85-22373 units

The use of local functionals to construct a circumvention maneuver in game problems of evasion p 302 A85-22374

The effect of changes in the angle of incidence in the event of a richochet at a float step [RAE-TRANS-2120]

p 255 N85-15712 Investigation of semiautomatic aircraft control processes employing time redundancy in on-board digital trajectory p 270 N85-16048 control computers

Parachute expedition to Arctic p 236 N85-16240 USSR report: Transportation [JPRS-UTR-85-001] p 204 N85-16763

Director on institute's civil aviation projects p 204 N85-16764 Designer on Aeroflot automated COMMO system

p 296 N85-16765 development Testing solution for IL-76 braking system problem p 256 N85-16766 International projects, other work of Aeroproyekt

p 204 N85-16767 Institute

Designer on civil aircraft design trends in USSR p 256 N85-16768

Aeroproyekt develops improved runway surfacing p 277 N85-16770

UNITED ARAB REPUBLIC A generalized stability criterion for nonlinear dynamic systems

[AIAA PAPER 85-0202] p 300 A85-19586 UNITED KINGDOM Turbulence structure of a three dimensional impinging et in a cross stream p 208 A85-19478 [AIAA PAPER 85-0044] The development of mathematical modelling techniques for helicopter rotor icing [AIAA PAPER 85-0336] p 240 A85-19679 Forward sweep - The pros and cons p 250 A85-20146 The challenge from ceramics to metals in the gas turbine and related areas p 280 A85-20150 Military avionics - Increasing integration at all levels p 244 A85-20221 p 250 A85-20222 Boeing's rejuvenated twin jet Modern military engines. Il p 264 A85-20822 Design and advanced concepts of avionics/weapons

system integration; Proceedings of the Symposium, p 200 London, England, April 3, 4, 1984 A85-21456 Software design methods p 301 A85-21457 A design methodology for integrated avionic systems p 301 A85-21458

Hardware design techniques n 244 A85-21459 Packaging and interconnection for avionics p 290 A85-21460 p 245 A85-21461

Integrated navigation Integrated communications - A designers view

p 245 A85-21462 Trends in digital flight control systems p 269 A85-21465

Trends in digital engine control - Integration of propulsion control with flight control and avionic systems in future military and commercial aircraft p 264 A85-21466 The impact of integrated systems - The helicopter p 252 A85-21467 designer's viewpoint Report from the United Kingdom p 307 A85-21943 Burbank's Blackbirds p 252 A85-22081 Trends in civil aircraft design p 200 A85-22226 Operational loads measurement: A philosophy and its implementation p 253 N85-15665 Advanced fatigue monitoring on service aircraft p 292 N85-15671 Experiences obtained from service fatigue monitoring

p 292 N85-15672 exercises Helicopter data acquisition in WHL p 254 N85-15676

Structural Usage Tornado: Monitoring System p 292 N85-15680 (SUMS) Proceedings of the International Conference and Exposition on Structural Impact and Crashworthiness p 242 N85-15703 [AD-A147845] Monitoring engine thermal stresses

ó 266 N85-15735 Disc fatigue life predictions for gas turbine engines

p 267 N85-15743 A practical example of reducing life cycle costs and increased availability p 296 N85-16736 Experience of one UK electronic equipment supplier with bite on engine/flight control systems over the past ten p 296 N85-16738 The effect on software design of testing by symbolic execution p 303 N85-16750 Recent progress of development and understanding of high lift systems gh lift systems p 236 N85-16772 Investigations into the effects of scale and compressibility on lift and drag in the RAE 5m pressurized p 236 N85-16773 low-speed wind tunnel

Inviscid compressible flow past a multi-element aerofoil p 236 N85-16776

Automatic briefing and mission management systems p 259 N85-16799 for battlefield support Integrated control and display systems for helicopter

p 260 N85-16805 battlefield mission management The design and development of an integrated core rstem for battlefield helicopters p 260 N85-16811

system for battlefield helicopters Air traffic management concepts for the UK in the 1990's: A review of recent RSRE work

[AD-A147850] p 246 N85-16853 On-board processing for linescan sensors in miniature unmanned aircraft

[RAE-TM-SPACE-327] o 261 N85-16870 The aircraft engine of the future

(PNR-90226) p 268 N85-16875 Rolls-Royce experience with thermal barrier coatings [PNR-90222] p 285 N85-17152

CONTRACT NUMBER INDEX

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Supplement 187)

MAY 1985

Typical Contract Number Index Listing



Listings in this index are arranged alphanumerically by contract number. Under each contract number, the accession numbers denoting documents that have been produced as a result of research done under that contract are arranged in ascending order with the AIAA accession numbers appearing first. The accession number denotes the number by which the citation is identified in the abstract section. Preceding the accession number is the page number on which the citation may be found.

-	
p 258	N85-16867
p 278	N85-16884
p 243	N85-16844
p 258	N85-16864
p 294	N85-16073
p 303	N85-17613
p 278	N85-16886
р 300	N85-17494
p 270	N85-15753
p 242	N85-15703
p 230	A85-20862
p 224	A85-19756
p 212	A85-19543
p 214	A85-19587
p 225	A85-19781
p 207	A85-19469
p 263	A85-19671
p 224	A85-19755
p 213	A85-19569
p 214	A85-19587
p 225	A85-19776
p 213	A85-19569
p 230	A85-20854
p 280	A85-20909
b 588	A85-19514
p 299	A85-21141
p 283	N00-15919
p 245	NOS-15/0/
b 588	NOD-1/430
p 299	N65-1/435
p 283	N05-15920
p 2//	NOS-15/00
p 300	ARE 10702
p 2/ 8	N95 10792
p 294	NOS-10007
p 303	NO3-1/3/0
p 200	NRE 16502
0 302	NRE 17155
p 265	N95 16700
p 239	NRE 16922
p 200	A85.10703
0 211	A85.10526
0 232	A85.01857
- 009	NOS-21031
p 308	N05-10065
p 239	N85-16836
p 208	A85-19476
p 207	A85-19474
p 286	A85-19575
p 308	N85-17732
p 294	N85-16069
	p 258 p 270 p 233 p 243 p 294 p 2958 p 294 p 2970 p 270 p 242 p 212 p 214 p 224 p 212 p 214 p 212 p 214 p 212 p 214 p 224 p 212 p 214 p 224 p 230 p 241 p 230 p 245 p 245 p 245 p 230 p 231 p 232 p 233 p 233

	p 294	N85-16087
F49620-82-K-0002	p 294	N85-16074
F49620-83-C-0119	p 294	N85-16070
F49620-83-K-0023	p 206	A85-19455
F49620-83-K-0034	p 230	A85-20864
F49620-84-C-0056	p 223	A85-19746
F65-511	p 285	N85-17153
MDA903-81-C-0186	p 203	N85-16667
NAGW-240	p 214	A85-19571
·	p 218	A85-19648
NAGW-575	p 268	A85-19585
NAG1-134	p 200	A85-21846
NAG1-26	p 238	N85-16829
NAG1-280	p 231	A85-20873
NAG1-330	p 215	A85-19591
NAG1-402	p 220	A85-19788
NAG1-413	p 238	N85-16825
NAG1-493	p 305	N85-17668
NAG1-76	p 215	A85-19590
NAG2-105	p 223	A85-19749
NAG2-246	p 252	A85-21973
NAG2-275	p 223	A85-19749
NAG3-159	p 209	A85-19490
NAG3-231	p 265	A85-21866
NAG3-242	p 264	A85-20867
NAG3-284	p 252	A85-20872
NAG3-315	p 305	N85-17667
NAG3-416	p 222	A85-19731
NAG3-7	p 291	A85-22281
NASA UNDER L-71400-B	p 210	N85-16180
NASW-4004	p 298	N85-17363
NASW-4005	p 278	N85-16882
NAS1-15069	p 284	N85-17049
NAS1-15992	p 274	A85-19655
NAS1-16199	p 256	N85-15718
NAS1-16669	p 293	N85-15993
NAS1-16758	p 219	A85-19653
NAS1-16826	p 252 p 295	A85-21396 N85-16098
NAS1-16978	p 304	A85-21842
NAS1-17003	p 305	N85-16590
NAS1-17023	p 245	N85-15706
NAS1-17093	o 304	A85-19507
NAS1-17099	p 305	N85-16586
NAS1-17292	p 223	A85-19740
NAS1-17528	p 255	N85-15714
NAS2-11020	p 257	N85-15717
NAS2-11255	p 247	A85-19626
NAS2-11261	p 255	N85-15715
NAS2-11304	p 271	N85-16877
NAS2-11313	p 206	A85-19451
NAS2-11424	p 215	A85-19593
NAS2-11725	p 247	A85-19626
NAS3-23039	. p 210	A85-19510
NAS3-235924	. p.∠65 n.285	A85-19491
NAS3-23696	p 229	A85-20744
NAS7-918	. p 242	N85-15701
NAS8-33716	. p 289	A85-21293
NGA2-OB-130-101	. p 297	N85-17294
NCC1-22	p 218	A85-19641
NCC1-32	. p 298	N85-17353
NOC1-41	p 219	A85-19650
NGL-22-003-124	. p 268	N85-16873
NGT-22-009-901	. p 223	A85-19749
NGT-36-004-800	. p 213	A85-19562
NR PROJ. 630-194	p 243	N85-16845
NR PROJECT 061-201	. p 239	N85-16834
NSERC-A-3662	. p 232	A85-21859
NSERC-AS-3378	. p 307	A85-21840

NSF MEA-80-18565	p 207	A85-19473
NSG-1625	p 301	A85-21548
NSG-1629	p 234	N85-15690
NSG-3295	p 265	N85-15724
N00014-75-C-0381	p 214	A85-19582
N00014-76-C-0364	p 213	A85-19562
N00014-79-C-0953	p 247	A85-19626
N00014-80-C-0400	p 283	A85-21863
N00014-81-C-0267	p 239	N85-16832
N00014-81-K-2032	p 285	N85-17153
N00014-81-K-2037	p 210	A85-19523
N00014-82-C-0601	p 239	N85-16834
N00014-82-C-0607	p 247	A85-19626
N00014-82-K-0184	p 207	A85-19470
N00014-84-K-0181	D 210	A85-19523
N00019-79-C-0258	n 280	A85-20759
N00140-80-C-0097	n 284	N85-15922
N60921-83-C-0166	n 214	AR5-19571
N62269-81-C-0206	0 243	N85-16845
N62260-01-0-0200	0 240	485-20875
LICOD 7.07.92 V0001	p 200	A85-21141
EAE 21 02 01	P 233	N95 15604
505-31-03-01	p 235	N95 16009
505-31-05	p 295	NOD-10098
505-31-21	p 234	NOD-10007
505-31-23-07	p 235	NOD-10095
505-31-3A	p 234	N85-15689
505-31-53-10	p 2/6	N85-15755
505-32-6A	p 200	N85-15658
505-33-43-07	p 234	N85-15691
505-33-43-09	p 235	N85-15696
505-33-53	p 235	N85-15697
505-35-13	p 261	N85-16869
505-40-1B	p 295	N85-16100
505-40-42	p 305	N85-17667
505-40-74	p 234	N85-15688
•	p 265	N85-15725
	p 276	N85-15758
505-42-11	p 255	N85-15715
505-42-23-03	p 284	N85-17048
505-43-11	p 270	N85-15752
505-43-43-01	p 203	N85-16759
505-43-43	p 258	N85-16862
505-43-83	p 278	N85-16883
505-45-33	p 261	N85-16868
505-45-43	p 235	N85-15692
505-45-45	p 242	N85-15702
505-45-73-01	p 257	N85-16861
506-51-13	p 280	N85-15778
	p 293	N85-16065
532-01-11	p 235	N85-15693
532-06-11	p 203	N85-16757
533-02-21	p 265	N85-15729
533-04-1A	p 295	N85-16096
534-06-13	D 284	N85-17049
535-03-11	n 255	N85-15716

CONFRACE

E-1

REPORT NUMBER INDEX

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Supplement 187)

MAY 1985

Typical Report Number Index Listing



Listings in this index are arranged alphanumerically by report number. The page number indicates the page on which the citation is located. The accession number denotes the number by which the citation is identified. An asterisk (*) indicates that the item is a NASA report. A pound sign (#) indicates that the item is available on microfiche.

A-85077					p	203	N85-1	6757	٠	#
A-9127					Þ	255	N85-1	5716	٠	#
A-9854					b	238	N85-1	6826	٠	#
A-9871					ñ	235	N85-1	5693	٠	#
	•••••				۲	200	1100-1			n
AD-A146	755	•			0	294	N85-1	6067		#
AD-A146	806	, 			'n	308	N85-1	6667		#
AD-A146	811				'n	238	N85_1	5699		#
AD-A146	878				'n	293	N85-1	5954		#
AD-A146	922				2	259	N85.1	5722		#
AD-A146	954				h	200	N85.1	5659		#
AD-A146	055		••••••		2	201	N95.1	5660		#
AD-A146	06.4		·····		2	201	NOS 1	6060		#
	066				2	204	NO3-1	5661		#
	000		••••••	••••••	2	201	NO5-1	2001		#
AD-A147	1001	·····	•••••		2	284	NOC 1	6502		#
AD 6147	0000	••••••	••••••		P	302	N85-1	0003		77
AD: 6147	1110				P	284	N05-1	6073		#
AD A141	110	••••••			P	2//	N85-1	5/00		#
AD-A14/	120		•••••		P	201	N85-1	5662		Ŧ
AD-A147	127		•••••		р	294	N85-1	6074		#
AD-A147	160		••••••		Ρ	283	N85-1	5921		#
AD-A147	188		•••••	•••••	Ρ	256	N85-1	5719		#
AD-A147	196		•••••		Ρ	284	N85-1	5922		#
AU-A147	269		•••••	•••••	р	201	N85-1	5663		#
AD-A147	289		•••••		Ρ	303	N85-1	7578		#
AD-A147	291	•••••		•••••	P	239	N85-1	6832		#
AD-A147	7295				Ρ	297	N85-1	7162		#
AD-A147	7388				ρ	295	N85-1	6196		#
AD-A147	7392				р	305	N85-1	6593		#
AD-A147	/430				Ρ	265	N85-1	5731		#
AD-A147	497				р	305	N85-1	6595		#
AD-A147	629		•••••		Ρ	303	N85-1	7613		#
AD-A147	7685				p	243	N85-1	6842		#
AD-A147	701				Ρ	268	N85-1	6874		#
AD-A147	708				р	308	N85-1	7732		#
AD-A147	724				p	285	N85-1	17153		#
AD-A147	7731				p	239	N85-1	6833		Ħ
AD-A147	768				ρ	246	N85-1	6855		Ħ
AD-A147	786		•••••		p	300	N85-1	7470		#
AD-A147	798				P	297	N85-1	7298		#
AD-A147	845				Ρ	242	N85-1	5703		#
AD-A147	7850		•••••		р	246	N85-1	6853		#
AD-A147	7858				Ρ	270	N85-1	5753		#
AD-A147	7893				p	277	N85-1	5762		#
AD-A147	7896				p	266	N85-1	5732		#
AD-A147	7897				p	294	N85-1	16087		ŧ
AD-A147	7911				p	308	N85-1	6682		Ħ
AD-A147	923				P	308	N85-1	6685		#
AD-A147	7928		·····`		p	293	N85-1	6008		#
AD-A147	7951				P	299	N85-1	7435		#
AD-A148	3034				p	243	N85-1	6844		ŧ
AD-A14	3046				'n	258	N85-1	6864		#
AD-A144	2001				2	250	NOF	2000		4
AD 6140	100		••••••	••••••	P	200	1-00/1	0000		11
AD-A148	8010		•••••	••••••	p	300	N85-1	/492		Ħ
AD-A148	5111				D	306	N85-1	7669		Ħ

AD-A148171		p;	203	N85-16760	#
AD-A148172		D (306	N85-17670	#
AD A149216			279	N85-16884	#
AU-A140215		Ρ.		1103-10004	*
AD-A148233		p i	271	N85-16879	Ħ
AD-A148253		D	299	N85-17438	#
AD-A148272		5	285	N85-17155	
AD A440000		5	200	NOG 17404	7
AU-A146296	•••••••••••	P :	500	NOS-17484	#
AD-A148318		p	278	N85-16885	#
AD-A148355		p:	239	N85-16834	#
AD-A148363		D	243	N85-16845	#
AD-A148387		5	239	N85-16835	#
AD A140307		2	250	NGE 10000	<u>π</u>
AD-A140425		P	200	1003-10000	Ħ
AD-A148453		P:	239	N85-16836	#
AD-A148472		p:	243	N85-16846	#
AD-A148496		p;	306	N85-17672	#
AD-A148525		n:	306	N85-17673	#
AD A149522		5	258	N85-16967	<i>"</i> #
AD-A140332		2	230	NO5-10007	
AD-A146600		P	2/0	00001-000	Ŧ
AD-A148624		P.	271	N85-16880	#
AD-A148653 .		p	203	N85-16761	#
AD-A148669		'n	243	N85-16847	#
AD 4440704		2	204	NOE 10700	""
AU-A140704		P	204	1003-10702	#
AD-A150008		p :	245	N85-15707	Ħ
AD-B0881466L		D	298	N85-17398	#
			- · ·		
AD D011010		-	777	NOE 15701	4
AD-DU11316		P.	211	1403-15/01	Ħ
AD-D011325		p.	276	N85-15754	#
AD-D011353		p	254	N85-15710	#
AD-D011376		'n	242	N85-15700	#
AD D011977		5	205	N95 18156	"#
AD-D011377		P :	200	N05-10150	T,
AD-D011378		ρ.	293	1000-10940	Ħ
AD-D011380		Ρ	259	N85-15721	#
AD-D011387		ρ	255	N85-15711	#
AD-D011392		Ď.	293	N85-15941	#
AD-D011395		5	265	N85-15723	. H
AD D011410		2	200	NRE 17506	"
AD-DU11412 .		P.	300	N05-17500	#
AD-D011430 .		р	285	N85-17077	#
AD-D011432 .		Ρ	298	N85-17369	#
AD-E500683		п	297	N85-17162	#
AD E700010		2	279	N85 16885	"4
AD-E/00012		Ρ	2/0	C0001-C0M	#
AD-E850735		p	258	N85-16864	#
AD-E850744		р	283	N85-15921	#
AD-E200400		•	305	N85-16505	#
AD-1 300-450		۲	000	1100-10000	π
AERO-1291		Ρ	201	N85-15661	#
AFAMRI -TR-7	8-109-ADD-1	D	302	N85-16503	#
AEAAADI TO O	4 041	5	242	N95 16944	<i>"</i>
ALAWILFI H-04	4-04 I	μ	240	1403-10044	"
AFESC/DEB-T	R-84-01	р	277	N85-15762	Ħ
AFESC/ESI -TI	R-83-34	р	277	N85-15760	4
AFERC/ERL T	0.04.10	5	270	NR5 16004	"
AFEOU/EOL-1	H-04-19	Ρ	210	1403-10004	ti.
AFESC/ESL-T	R-84-32-VOL-2	Ρ	300	N85-1/4/0	Ħ
AFESC/ESL-TI	R-84-35	р	299	N85-17435	ŧ
AFESC/ESL-TI	R-84-36	P	299	N85-17436	ŧ
		ŕ			
ACHDI .TD.92	69	~	205	N85.16106	*
ALULTICADA		۲	205	1103-10180	"
AFIT/CI/NR-84	1-84D	p	271	N85-16879	f
AFIT/GLM/IS	M/84S-26	р	201	N85-15660	ŧ
AFIT/GI M/I SI	M/845.39	5	297	N85-17299	4
AFIT/OLA/		4	200	NIDE +0000	n,
ATTI/GLM/LS		~	20J	1103-10008	ħ
AFIT/GLM/LS	M/845-52	Ρ			
	M/845-52 M/84S-56	p	201	N85-15663	Ħ
AFIT/GLM/LSI	M/84S-52 M/84S-56 M/84S-57	P P P	201 201	N85-15663 N85-15662	7 7
AFIT/GLM/LSI AFIT/GLM/LSI	M/845-52 M/845-56 M/845-57 M/845-63	000	201 201 283	N85-15663 N85-15662 N85-15921	# #
AFIT/GLM/LSI AFIT/GLM/LSI	M/84S-52 M/84S-56 M/84S-57 M/84S-63	P P P P	201 201 283	N85-15663 N85-15662 N85-15921	节有有
AFIT/GLM/LSI	M/84S-52 M/84S-56 M/84S-57 M/84S-63 V/84S-25	. 444	201 201 283 268	N85-15663 N85-15662 N85-15921	8 8 8 8 8 8 8
AFIT/GLM/LSI	M/84\$-52 M/84\$-56 M/84\$-57 M/84\$-63 Y/84\$-25	5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	201 201 283 268	N85-15663 N85-15662 N85-15921 N85-16874	8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
AFIT/GLM/LSI AFIT/GLM/LSI AFIT/GSM/LS AFIT/GSM/LS	M/845-52 M/845-56 M/845-57 M/845-63 Y/845-25 Y/845-2	1000 1000 1000	201 201 283 268 200	N85-15663 N85-15662 N85-15921 N85-16874 N85-15659	***
AFIT/GLM/LSI AFIT/GLM/LSI AFIT/GSM/LSI AFIT/GSM/LSI AFIT/GSM/LSI	W/84S-52 W/84S-56 W/84S-57 M/84S-63 Y/84S-25 Y/84S-25 Y/84S-2 Y/84S-5	1000 000	201 201 283 268 200 258	N85-15663 N85-15662 N85-15921 N85-16874 N85-15659 N85-16866	***
AFIT/GLM/LSI AFIT/GLM/LSI AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS	W/84S-52 W/84S-56 W/84S-63 W/84S-63 Y/84S-25 Y/84S-2 Y/84S-5 Y/84S-9		201 201 283 268 200 258 297	N85-15663 N85-15662 N85-15921 N85-16874 N85-15659 N85-16866 N85-17162	***
AFIT/GLM/LS AFIT/GLM/LS AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS	W/845-52 W/845-56 W/845-57 W/845-63 Y/845-25 Y/845-2 Y/845-2 Y/845-9		201 203 283 268 200 258 297	N85-15663 N85-15662 N85-15921 N85-16874 N85-15659 N85-16866 N85-17162	***
AFIT/GLM/LSI AFIT/GLM/LSI AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LSI AFIT/GSM/LSI	W/845-52 W/845-56 W/845-57 W/845-63 Y/845-25 Y/845-25 Y/845-2 Y/845-5 Y/845-9	. 4444 444	201 201 283 268 200 258 297	N85-15663 N85-15662 N85-15921 N85-16874 N85-15659 N85-16866 N85-17162	***
AFIT/GLM/LSI AFIT/GLM/LSI AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS	W/845-52 W/845-56 W/845-57 W/845-63 Y/845-25 Y/845-2 Y/845-5 Y/845-9 W/845-9 W/845-9		201 201 283 268 200 258 297 294	N85-15663 N85-15662 N85-15921 N85-16874 N85-16874 N85-16866 N85-16866 N85-17162	***
AFIT/GLM/LSI AFIT/GLM/LSI AFIT/GSM/LSI AFIT/GSM/LSI AFIT/GSM/LSI AFOSR-84-085 AFOSR-84-085	W/845-52 W/845-56 W/845-57 W/845-63 Y/845-25 Y/845-2 Y/845-5 Y/845-9 W/845-9 SBTR		201 201 283 268 200 258 297 294 294	N85-15663 N85-15662 N85-15921 N85-16874 N85-15659 N85-16866 N85-17162 N85-16070 N85-16074	***
AFIT/GLM/LSI AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFOSR-84-085 AFOSR-84-085 AFOSR-84-085	W/845-52 W/845-56 W/845-57 W/845-63 Y/845-25 Y/845-2 Y/845-2 Y/845-5 W/845-9 W/845-9 W/845-9 W/845-9 W/845-9 W/845-9 W/845-9		201 201 283 268 200 258 297 294 294 294 294	N85-15663 N85-15662 N85-15921 N85-16874 N85-15659 N85-16866 N85-16070 N85-16070 N85-16074 N85-16069	***
AFIT/GLM/LSI AFIT/GSM/LSI AFIT/GSM/LSI AFIT/GSM/LSI AFIT/GSM/LSI AFOSR-84-085 AFOSR-84-085 AFOSR-84-085 AFOSR-84-085 AFOSR-84-085	W/845-52 W/845-57 W/845-57 W/845-63 Y/845-25 Y/845-2 Y/845-5 Y/845-5 W/845-9 W		201 201 283 268 200 258 297 294 294 294 294	N85-15663 N85-1562 N85-15921 N85-16874 N85-16866 N85-16866 N85-16070 N85-16079 N85-16079 N85-16073	***
AFIT/GLM/LSI AFIT/GLM/LSI AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFOSR-84-085 AFOSR-84-085 AFOSR-84-085 AFOSR-84-085 AFOSR-84-085	W/845-52 W/845-56 W/845-57 W/845-63 Y/845-25 Y/845-2 Y/845-2 Y/845-5 W/845-9 B6TR B6TR B6TR B1TR B1TR B1TR		201 201 283 268 200 258 297 294 294 294 294 303	N85-15663 N85-15621 N85-15921 N85-16874 N85-16876 N85-16866 N85-17162 N85-16070 N85-16074 N85-16073 N85-16073 N85-17613	***
AFIT/GLM/LSI AFIT/GLM/LSI AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFOSR-84-085 AFOSR-84-085 AFOSR-84-080 AFOSR-84-090 AFOSR-84-090	W/84S-52 W/84S-56 W/84S-63 W/84S-63 Y/84S-25 Y/84S-2 Y/84S-5 Y/84S-9 W		201 201 283 268 200 258 297 294 294 294 294 294 303 239	N85-15663 N85-15621 N85-15921 N85-16874 N85-16876 N85-16866 N85-17162 N85-16070 N85-16079 N85-16073 N85-16073 N85-17613	***
AFIT/GLM/LSI AFIT/GLM/LSI AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFIT/GSM/LS AFOSR-84-085 AFOSR-84-095 AFOSR-84-093 AFOSR-84-093 AFOSR-84-093	W/845-56 W/845-56 W/845-63 Y/845-25 Y/845-2 Y/845-5 Y/845-9 BITR BITR STR STR STR		201 201 283 268 200 258 297 294 294 294 294 303 239 239	N85-15663 N85-15621 N85-15921 N85-16874 N85-16876 N85-16866 N85-17162 N85-16070 N85-16073 N85-16073 N85-16073 N85-16836 N85-17613 N85-16836	***

AEOED 84 400470		NOC 47404	
AFU3R-04-10241H	p 300	N85-17494	Ŧ
AFOSR-84-1066TR	p 294	N85-16087	#
AFOSR-84-1078TR	p 278	N85-16886	#
AFSR-2	0.094	MR5 17040	• #
	p 204	1103-17048	π
AFWAL-IM-84-217-FIB	p 258	N85-16867	#
AFWAL-TR-84-1016	p 259	N85-15722	#
AFWAI -TR-84-2007	n 285	N85-17155	#
ADAVAL TE 84 2014	- 005	NOE 45704	
AFWAL-1H-04-2014	p 265	N85-15/31	₩
AFWL-TN-84-30	p 294	N85-16067	#
AGARD_CP.350	0.204	N95 18707	#
	p 204	1403-10787	
AGARD-CP-361	p 201	N85-16/31	#
AGARD-CP-365	p 204	N85-16771	#
AGARD-CP-368	p 266	N85-15733	#
AGARD-CP-375	n 201	N85-15684	#
	p 201	1100-10004	w
AGARD-R-/10-ADD	p 284	N85-17057	#
AIAA PAPER 84-2201	p 288	A85-20874	#
AIAA PAPER 84-2397	p 250	A85-20875	#
AIAA PAPER 85,0003	n 200	485 10451	• #
ALAA DADED DE AGO4	P 200	AOE 40475	11 ⁴
AIAA PAPER 85-0004	p 206	ABD-19452	#
AIAA PAPER 85-0005	p 262	A85-19453	#
AIAA PAPER 85-0007	p 206	A85-19454	#
AIAA PAPER 85.0000	n 20e	485.10455	
	P 200	AOE 10400	, П [*]
AIAA PAPER 65-0010	p 2/2	A83-19430	- #
AIAA PAPER 85-0013	p 247	A85-19457	#
AIAA PAPER 85-0014	p 298	A85-19458	• #
AIAA PAPER 85-0015	n 247	485-19459	#
ALAA DADED OF 0017	- 000	AOE 40460	
AIAA FAFER 60-0017	p 200	A65-19400	. #
AIAA PAPER 85-0018	p 229	A85-20851	•#
AIAA PAPER 85-0019	p 207	A85-19461	#
AIAA PAPER 85-0032	n 207	A85-19469	#
ALAA PAPER 85-0033	0 207	485-19470	• #
	- 007	AOE 40470	• 4
AIAA FAFER 05-0035	p 207	A65-19472	#
AIAA PAPEH 85-0037	p 288	A85-20852	#
AIAA PAPER 85-0038	p 207	A85-19473	#
AIAA PAPER 85-0039	p 207	A85-19474	#
AIAA PAPER 85-0040	n 208	A85-19475	• #
AIAA PAPER 85-0041	n 208	485-19476	#
AIAA PAPER 85 0042	- 209	A95 10477	"4
	p 200	A05-10477	11
AIAA PAPER 85-0044	p 208	A85-19478	Ŧ
AIAA PAPER 85-0045	p 208	A85-19479	#
AIAA PAPER 85-0046	p 208	A85-19480	#
AIAA PAPER 85-0050	p 209	A85-19482	• #
AIAA PAPER 85-0051	0 273	485-19483	. <i>#</i>
AIAA DAGED BE ODED	- 200	AGE 10404	
	p 208	A00-10404	. "
AIAA PAPEH 85-0053	p 2/3	A85-19485	- #
AIAA PAPER 85-0054	p 273	A85-19486	#
AIAA PAPER 85-0055	p 209	A85-19487	#
AIAA PAPER 85-0058	n 209	A85-19489	• #
AIAA PAPER 85-0059	n 200	485.19400	• #
	- 205	ADE 10401	• "
	P 200	A03-18491	#
AIAA PAPER 85-0068	p 279	A85-19495	#
AIAA PAPER 85-0071	p 273	A85-19497	#
AIAA PAPER 85-0072	p 268	A85-19498	#
AIAA PAPER 85-0074	6 200	485 10500	4 4
	p 203	105-10500	7
ANA PAPER 03-00/5	p 210	485-19501	Ħ
AIAA PAPEH 85-0079	p 304	A85-19505	#
AIAA PAPER 85-0081	p 304	A85-19507	•#
AIAA PAPER 85-0082	p 210	A85-19508	•#
AIAA PAPER 85.0082	0.262	ARE 10500	• #
AIAA DADED 65 0004	P 202	ADE 10009	Ħ,
AIAA PAPEH 85-0084	p 226	A85-19/98	Ħ
AIAA PAPEH 85-0086	p 210	A85-19510	*#
AIAA PAPER 85-0088	p 210	A85-19511	#
AIAA PAPER 85-0089	p 273	A85-19512	#
AIAA PAPER 85-0091	D 240	A85-19513	#
AIAA PAPER 85,0002	P	485,19514	4 1
	n 200	100-10014	tř
	p 299	ADE 40645	
AIAA PAPER 85-0093	p 299 p 273	A85-19515	#
AIAA PAPER 85-0093	p 299 p 273 p 240	A85-19515 A85-19516	# #
AIAA PAPER 85-0093 AIAA PAPER 85-0094 AIAA PAPER 85-0102	p 299 p 273 p 240 p 286	A85-19515 A85-19516 A85-19520	# #
AIAA PAPER 85-0093 AIAA PAPER 85-0094 AIAA PAPER 85-0102 AIAA PAPER 85-0104	p 299 p 273 p 240 p 286 p 230	A85-19515 A85-19516 A85-19520 A85-20854	# # # #
AIAA PAPER 85-0093 AIAA PAPER 85-0094 AIAA PAPER 85-0102 AIAA PAPER 85-0104	p 299 p 273 p 240 p 286 p 230 p 210	A85-19515 A85-19516 A85-19520 A85-20854 A85-19523	#####
AIAA PAPER 85-0093	p 299 p 273 p 240 p 286 p 230 p 210	A85-19515 A85-19516 A85-19520 A85-20854 A85-19523 A85-19523	###### •
AIAA PAPER 85-0093	p 299 p 273 p 240 p 286 p 230 p 210 p 210	A85-19515 A85-19516 A85-19520 A85-20854 A85-19523 A85-19523 A85-19524	#######
AIAA PAPER 85-0093 AIAA PAPER 85-0094 AIAA PAPER 85-0102 AIAA PAPER 85-0104 AIAA PAPER 85-0104 AIAA PAPER 85-0107 AIAA PAPER 85-0108 AIAA PAPER 85-0109	p 299 p 273 p 240 p 286 p 230 p 210 p 210 p 230	A85-19515 A85-19516 A85-19520 A85-20854 A85-19523 A85-19523 A85-19524 A85-20855	########
AIAA PAPER 85-0093 AIAA PAPER 85-0094 AIAA PAPER 85-0102 AIAA PAPER 85-0104 AIAA PAPER 85-0107 AIAA PAPER 85-0107 AIAA PAPER 85-0109 AIAA PAPER 85-0109 AIAA PAPER 85-0110	p 299 p 273 p 240 p 286 p 230 p 210 p 210 p 230 p 230 p 262	A85-19515 A85-19516 A85-19520 A85-20854 A85-19523 A85-19524 A85-20855 A85-19525	##########
AIAA PAPER 85-0093 AIAA PAPER 85-0094 AIAA PAPER 85-0102 AIAA PAPER 85-0104 AIAA PAPER 85-0104 AIAA PAPER 85-0108 AIAA PAPER 85-0109 AIAA PAPER 85-0110 AIAA PAPER 85-0111	p 299 p 273 p 240 p 286 p 230 p 210 p 210 p 230 p 262 p 262	A85-19515 A85-19516 A85-19520 A85-20854 A85-19523 A85-19524 A85-20855 A85-19525 A85-19525	<i>#########</i>
AIAA PAPER 85-0093 AIAA PAPER 85-0094 AIAA PAPER 85-0102 AIAA PAPER 85-0104 AIAA PAPER 85-0104 AIAA PAPER 85-0108 AIAA PAPER 85-0108 AIAA PAPER 85-0110 AIAA PAPER 85-0111 AIAA PAPER 85-0111	p 299 p 273 p 240 p 286 p 230 p 210 p 210 p 210 p 230 p 262 p 210	A85-19515 A85-19516 A85-19520 A85-20854 A85-19523 A85-19523 A85-19525 A85-19526 A85-19526	<i>###########</i>
AIAA PAPER 85-0093 AIAA PAPER 85-0094 AIAA PAPER 85-0102 AIAA PAPER 85-0102 AIAA PAPER 85-0103 AIAA PAPER 85-0107 AIAA PAPER 85-0108 AIAA PAPER 85-0109 AIAA PAPER 85-0109 AIAA PAPER 85-0109 AIAA PAPER 85-0110 AIAA PAPER 85-0111 AIAA PAPER 85-0112	p 299 p 273 p 240 p 286 p 230 p 210 p 210 p 230 p 262 p 210 p 262 p 210 p 301	A85-19515 A85-19516 A85-19520 A85-20854 A85-19523 A85-19524 A85-20855 A85-19525 A85-19526 A85-20856	<i>#####################################</i>

AIAA PAPER 85-0121

REPORT NUMBER INDEX

* * * * * * * * *

##

AIAA PAPER 85-0121 AIAA PAPER 85-0122	11 211	AOE 10507 #		- 000	405 40000 #
AIAA PAPER 85-0122		M00-18032 #	AIAA PAPER 60-0300	p 220	W02-18080 #
	p 211	A85-19533 * #	AIAA PAPER 85-0366	p 221	A85-19699 * #
AIAA PAPER 85-0123	p 211	A85-19534 * #	AIAA PAPEH 85-0367	p 221 -	A85-19700 # #
AIAA PAPER 85-0125	p 211	A85-19536 #	AIAA PAPER 85-0368	p 221	A85-19701 * #
AIAA PAPER 85-0127	p 211	A85-19538 #	AIAA PAPER 85-0369	p 221	A85-19702 #
AIAA PAPER 85-0128		A85-19539 #	AIAA PAPER 85-0371	p 221	A85-19703 #
AIAA PAPER 85-0129	p 212	A85-19540 #	AIAA PAPER 85-0373	p 221	A85-19705 #
AIAA PAPER 85-0130	n 212	495-19541 #	AIAA PAPER 85-0375	p 286	A85-19706 #
ALAA PAPER 85-0131	n 212	AR6.10542 #	AIAA PAPER 85-0378	0 222	A85-19708 #
AIAA DADER 85-0131	P 212	A05-10542 #	AIAA PAPER 85.0370	0 275	A85.10700 * #
AIAA PAPER 85-0132		A85-19543 #		P 213	APE 40740 #
AIAA PAPEH 85-0159	p 212	A85-19556 #	AIAA FAFER 03-0301	p 203	A05-19/10 #
AIAA PAPER 85-0166	p 213	A85-19562 * #	AIAA PAPER 85-0382	p 2/5	A85-19/11 #
AIAA PAPER 85-0167	p 213	A85-19563 #	AIAA PAPER 85-0393	ρ 240	A85-19719 #
AIAA PAPER 85-0171	p 213	A85-19565 #	AIAA PAPER 85-0394	p 240	A85-19720 * #
AIAA PAPER 85-0174	p 213	A85-19567 * #	AIAA PAPER 85-0395	p 241	A85-19721 #
AIAA PAPER 85-0176	0 213	A85-19568 #	AIAA PAPER 85-0408	p 304	A85-19729 #
AIAA PAPER 85-0177	p 213	A85-19569 #	AIAA PAPER 85-0409	0 222	A85-19730 * #
ALAA DADED 85.0179	0.214	A95-10570 #	AIAA PAPER 85-0410	0 222	A85-19731 * #
		A05 10571 1 #	AIAA PAPER 85.0411	0 222	A85.10722 #
AIAA PAPER 03-01/9		A65-19571 #		+ 200	AOC 40700 + #
AIAA PAPER 85-0181	ρ214	A85-19572 #	AIAA PAPER 85-0412	P 222	A05-19733 #
AIAA PAPER 85-0183	p 214	A85-19573 #	AIAA PAPER 85-0413	p 248	A85-19734 #
AIAA PAPER 85-0185	p 286	A85-19575 #	AIAA PAPER 85-0414	p 286	A85-19735 #
AIAA PAPER 85-0186	p 230	A85-20862 #	AIAA PAPER 85-0423	p 222	A85-19738 #
AIAA PAPER 85-0191		A85-19577 #	AIAA PAPER 85-0424	p 248	A85-19739 * #
AIAA PAPER 85-0198		A85-19582 #	AIAA PAPER 85-0425	p 223	A85-19740 * #
ALAA PAPER 85-0199	p 268	A85-19583 * #	AIAA PAPER 85-0426	0 248	A85-19741 * #
ALAA PAPER 85-0200	n 247	A85-19584 #	AIAA PAPER 85-0427	0 223	A85-19742 #
ALAA PAPER 85.0201	n 269	APE 10595 * #	AIAA PAPER 85-0433	0 223	A85-19746 #
		A96 10596 #	AIAA PAPER 85-0434	n 223	A85-19747 #
ALAA DADED OF OCO	p 300	A05-18000 #		P 220	A85.10740 #
AIAA PAPEH 85-0203	p 214	A80-1958/ #	AIAA DADED OF 0400	P 223	ADE 10740 #
AIAA PAPER 85-0204	p 215	A85-19588 *#	AIAA PAPEH 85-0435	p 223	A05-19/49 #
AIAA PAPER 85-0205	p 215	A85-19589 #	AIAA PAPER 85-0437	p 230	A85-20869 * #
AIAA PAPER 85-0206	p 215	A85-19590 * #	AIAA PAPER 85-0438	p 231	A85-20870 * #
AIAA PAPER 85-0207		A85-19591 * #	AIAA PAPER 85-0445	p 286	A85-19754 #
ALAA PAPER 85-0208	0.215	A85-19592 #	AIAA PAPER 85-0446	p 224	A85-19755 #
ALAA PAPER 85.0212	n 915	A85-19593 * #	AIAA PAPER 85-0447	p 224	A85-19756 #
ALAA DADED 85 0225		A95 10601 * #		n 249	A85-19758 * #
AIAA PAPER 03-0223		A00-19001 #	AIAA PAPER 85.0450	0 224	A95 10750 #
AIAA PAPER 05-0220		A65-19002 - #		- 204	A95 10760 #
AIAA PAPER 85-0229	p 2/4	A85-19603 #	AIAA PAPER 05-0451	p 224	A05-19700 #
AIAA PAPER 85-0245	p 216	A85-19611 * #	AIAA PAPEH 85-0452	p 224	A85-19761 * #
AIAA PAPER 85-0251	p 216	A85-19614 #	AIAA PAPEH 85-0454	p 224	A85-19762 #
AIAA PAPER 85-0252	p 262	A85-19615 #	AIAA PAPER 85-0466	p 241	A85-20872 * #
AIAA PAPER 85-0253	p 263	A85-19616 #	AIAA PAPER 85-0467	p 241	A85-19768 #
AIAA PAPER 85-0255	p 263	A85-19801 * #	AIAA PAPER 85-0471	p 286	A85-19769 #
AIAA PAPER 85-0257		A85-19617 * #	AIAA PAPER 85-0479	p 225	A85-19776 #
AIAA PAPER 85-0259	n 274	A85-19618 * #	AIAA PAPER 85-0480	p 225	A85-19777 #
ALAA DADED 85.0260	n 247	A96-10610 #	AIAA PAPER 85-0481	0 225	A85-19778 #
		A00-19019 #	AIAA PAPER 85.0482	n 225	A95.10770 * #
AIAA PAPER 05-0207		A05-19020 #		- 225	A95 10701 #
AIAA PAPEH 85-0268	p 216	A85-19621 #	AIAA DADED 05 0405	p 225	A05 40700 * #
AIAA PAPER 85-0269	p 216	A85-19622 #	AIAA PAPEH 85-0485	p 300	A85-19782 #
AIAA PAPER 85-0270	p 247	A85-19623 #	AIAA PAPEH 85-0486	p 225	A85-19783 * #
AIAA PAPER 85-0271	p 216	A85-19624 #	AIAA PAPER 85-0487	p 226	A85-19784 * #
AIAA PAPER 85-0274	p 247	A85-19626 * #	AIAA PAPER 85-0488	p 226	A85-19785 * #
AIAA PAPER 85-0275	p 248	A85-19627 #	AIAA PAPER 85-0492	p 226	A85-19787 #
AIAA PAPER 85-0275 AIAA PAPER 85-0276	р 248 р 217	A85-19627 # A85-19628 * #	AIAA PAPER 85-0492 AIAA PAPER 85-0493	p 226 p 231	A85-19787 # A85-20873 * #
AIAA PAPER 85-0275 AIAA PAPER 85-0276 AIAA PAPER 85-0277		A85-19627 # A85-19628 * # A85-19629 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494	p 226 p 231 p 226	A85-19787 # A85-20873 * # A85-19788 * #
AIAA PAPER 85-0275 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277		A85-19627 # A85-19628 * # A85-19629 # A85-19630 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494	p 226 p 231 p 226 p 249	A85-19787 # A85-20873 * # A85-19788 * # A85-19789 #
AIAA PAPER 85-0275 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0278	p 248 p 217 p 217 p 217 p 217 p 217	A85-19627 # A85-19628 * # A85-19629 # A85-19630 #	AIAA PAPER 85-0492 ' AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495	p 226 p 231 p 226 p 249 p 249	A85-19787 # A85-20873 * # A85-19788 * # A85-19789 # A85-19789 #
AIAA PAPER 85-0275 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0278 AIAA PAPER 85-0279	p 248 p 217 p 217 p 217 p 217 p 217 p 217 p 217	A85-19627 # A85-19628 * # A85-19629 # A85-19630 # A85-19631 * #	AIAA PAPER 85-0492 ' AIAA PAPER 85-0493 ' AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0495	p 226 p 231 p 226 p 249 p 249 p 249	A85-19787 # A85-20873 * # A85-19788 * # A85-19789 # A85-19790 #
AIAA PAPER 85-0275 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0279 AIAA PAPER 85-0281	p 248 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217	A85-19627 # A85-19628 * A85-19629 # A85-19630 # A85-19631 * A85-19632 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0496	p 226 p 231 p 226 p 249 p 249 p 249 p 279	A85-19787 # A85-20873 * # A85-19788 * # A85-19789 # A85-19790 # A85-19791 * #
AIAA PAPER 85-0275 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0270 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282	p 248 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217	A85-19627 # A85-19628 * A85-19629 # A85-19630 # A85-19630 # A85-19632 # A85-19633 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0496 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0497 AIAA PAPER 85-0498	p 226 p 231 p 226 p 249 p 249 p 249 p 279 p 279	A85-19787 # A85-20873 * # A85-19788 * # A85-19789 # A85-19790 # A85-19791 * # A85-19792 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0279 AIAA PAPER 85-0280 AIAA PAPER 85-0283 AIAA PAPER 85-0283	p 248 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 218	A85-19627 # A85-19628 * A85-19630 # A85-19630 # A85-19631 * A85-19632 # A85-19633 # A85-19634 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498	p 226 p 231 p 226 p 249 p 249 p 249 p 279 p 279	A85-19787 # A85-20873 * # A85-19788 * # A85-19789 # A85-19790 # A85-19791 * # A85-19792 #
AIAA PAPER 85-0275 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0283 AIAA PAPER 85-0283	p 248 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 218 p 218 p 218	A85-19627 # A85-19628 * A85-19629 # A85-19630 # A85-19631 * A85-19632 # A85-19633 # A85-19633 # A85-19634 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498	p 226 p 231 p 226 p 249 p 249 p 249 p 279 p 279 p 279	A85-19787 # A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19791 * A85-19792 # N85-15752 * #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0284 AIAA PAPER 85-0284 AIAA PAPER 85-0291	p 248 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 218 p 218 p 218 p 218	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19634 # A85-19631 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0497 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498	p 226 p 231 p 226 p 249 p 249 p 279 p 279 p 279	A85-19787 # A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19791 * A85-19792 # N85-15752 * #
AIAA PAPER 85-0275 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0279 AIAA PAPER 85-0280 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0291 AIAA PAPER 85-0291 AIAA PAPER 85-0292	p 248 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 218 p 218 p 218 p 218 p 218 p 218	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19635 # A85-19635 # A85-19641 * A85-19642 *	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498	p 226 p 231 p 226 p 249 p 249 p 279 p 279 p 270 p 270 p 235	A85-19787 # A85-20873 * A85-19788 * A85-19780 # A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15696 *
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0283 AIAA PAPER 85-0281 AIAA PAPER 85-0291 AIAA PAPER 85-0293 AIAA PAPER 85-0293	p 248 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 218 p 219	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19635 # A85-19642 * A85-19642 # A85-19643 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-PAPER-84-2070-CP AIAA-83-0503 AIAA-85-0090	p 226 p 231 p 226 p 249 p 249 p 279 p 279 p 279 p 270 p 270 p 235 p 276	A85-19787 # A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19791 * A85-19792 # N85-15752 * N85-15696 # N85-15758 *
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0284 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0292	p 248 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 217 p 218 p 219	A85-19627 # A85-19628 # A85-19630 # A85-19630 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19634 # A85-19635 # A85-19634 # A85-19641 # A85-19642 # A85-19644 # A85-19644 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0497 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0503 AIAA-85-0279	p 226 p 231 p 226 p 249 p 249 p 279 p 279 p 279 p 270 p 235 p 276 p 258	A85-19787 # A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15752 * N85-15756 * N85-15758 * M85-15758 *
AIAA PAPER 85-0275 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0279 AIAA PAPER 85-0280 AIAA PAPER 85-0280 AIAA PAPER 85-0280 AIAA PAPER 85-0290 AIAA PAPER 85-0290	p 248 p 217 p 217 p 217 p 217 p 217 p 217 p 218 p 219 p 219 p 219 p 217 p 218 p 228 p 230 p 218 p 230 p 218	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19634 # A85-19641 # A85-19642 # A85-19643 # A85-19644 # A85-19644 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-PAPER-84-2070-CP AIAA-85-0030 AIAA-85-0279 AIAA-85-0279 AIAA-85-0207	p 226 p 231 p 226 p 249 p 249 p 279 p 279 p 270 p 270 p 235 p 276 p 258 p 234	A85-19787 # A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15752 * N85-15758 * N85-16862 *
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0283 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294	p 248 p 217 p 218	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19635 # A85-19635 # A85-19635 # A85-19643 # A85-19643 # A85-19643 # A85-19643 # A85-19644 # A85-19644 # A85-19648 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-PAPER-84-2070-CP AIAA-85-0503 AIAA-85-0279 AIAA-85-0307 AIAA-85-0338	p 226 p 231 p 226 p 249 p 249 p 279 p 279 p 270 p 270 p 235 p 276 p 258 p 258 p 234 p 242	A85-19787 # A85-20873 # A85-19788 # A85-19789 # A85-19799 # A85-19791 # A85-19791 # A85-19792 # N85-15752 # N85-15758 # N85-15686 # N85-15687 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0284 AIAA PAPER 85-0291 AIAA PAPER 85-0292 AIAA PAPER 85-0295 AIAA PAPER 85-0295 AIAA PAPER 85-0295 AIAA PAPER 85-0295 AIAA PAPER 85-0295 AIAA PAPER 85-0295	p 248 p 217 p 218	A85-19627 # A85-19628 # A85-19630 # A85-19630 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19634 # A85-19641 # A85-19642 # A85-19644 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA-83-0503 AIAA-85-0279 AIAA-85-0307 AIAA-85-0378 AIAA-85-0379	p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 270 p 270 p 235 p 276 p 235 p 276 p 234 p 234 p 242 p 274	A85-19787 # A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15752 * N85-15686 * N85-15686 * N85-15757 *
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0279 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0293 AIAA PAPER 85-0293	p 248 p 217 p 218 p 219	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19634 # A85-19641 # A85-19644 # A85-19645 # A85-19646 # A85-19647 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0300 AIAA-85-0307 AIAA-85-0307 AIAA-85-0309 AIAA-85-0307 AIAA-85-0309	p 226 p 231 p 228 p 249 p 249 p 279 p 279 p 279 p 270 p 270 p 235 p 276 p 258 p 234 p 242 p 276 p 234	A85-19787 # A85-20873 * A85-19788 # A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15758 * N85-16862 * N85-15687 * N85-15702 * N85-15782 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0294 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0290 AIAA PAPER 85-0290 AIAA PAPER 85-0290 AIAA PAPER 85-0290 AIAA PAPER 85-0290 AIAA PAPER 85-0290 AIAA PAPER 85-0290	p 248 p 217 p 218 p 218 p 218 p 218 p 218 p 218 p 219 p 219	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19635 # A85-19635 # A85-19641 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19648 # A85-19649 # A85-19650 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-PAPER-84-2070-CP AIAA-85-0030 AIAA-85-0030 AIAA-85-0379 AIAA-85-0379 AIAA-85-0380	p 226 p 231 p 226 p 249 p 249 p 279 p 279 p 279 p 270 p 270 p 235 p 276 p 235 p 276 p 234 p 242 p 276 p 234	A85-19787 # A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15758 * N85-15758 * N85-15788 * N85-15686 * N85-15757 * N85-15757 *
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0284 AIAA PAPER 85-0291 AIAA PAPER 85-0292 AIAA PAPER 85-0295 AIAA PAPER 85-0295 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300	p 248 p 217 p 218 p 218 p 218 p 218 p 218 p 218 p 219 p 219	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19634 # A85-19643 # A85-19644 # A85-19649 # A85-19649 # A85-19650 # A85-19650 # A85-19650 # A85-19650 # A85-19650 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0497 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA-85-0503 AIAA-85-0307 AIAA-85-0379 AIAA-85-0379 AIAA-85-0379 AIAA-85-0379 AIAA-85-0379 AIAA-85-0378 AIAA-85-0378 AIAA-85-0378 AIAA-85-0378 AIAA-85-0378 AIAA-85-0378	p 226 p 231 p 228 p 249 p 279 p 279 p 270 p 270 p 235 p 276 p 235 p 276 p 234 p 234	A85-19787 # A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15752 * N85-15752 * N85-15686 * N85-15688 * N85-15688 * N85-15688 *
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0290 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300	p 248 p 217 p 218 p 219 p 219 p 219 p 219 p 219	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19643 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19648 # A85-19644 # A85-19648 # A85-19648 # A85-19648 # A85-19650 # A85-19650 # A85-19652 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-83-0503 AIAA-85-0279 AIAA-85-0377 AIAA-85-0380 AIAA-85-0380	p 226 p 231 p 228 p 249 p 249 p 279 p 279 p 270 p 270 p 235 p 276 p 258 p 276 p 258 p 276 p 258 p 242 p 276 p 234 p 234	A85-19787 # A85-20873 * A85-20873 * A85-19789 # A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15696 * N85-15687 * N85-15687 * N85-15688 * N85-15688 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0284 AIAA PAPER 85-0291 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300	p 248 p 217 p 218 p 219	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19635 # A85-19635 # A85-19643 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19649 # A85-19651 # A85-19652 # A85-19652 # A85-19652 # A85-19652 # A85-19652 # A85-19652 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0303 AIAA-85-0307 AIAA-85-0338 AIAA-85-0380 AIAA-85-0380 AIA-8406 AIAB 502	p 226 p 231 p 228 p 249 p 279 p 279 p 270 p 235 p 276 p 258 p 258 p 234 p 242 p 276 p 234 p 234	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15758 * N85-15686 * N85-15687 * N85-15688 * N85-15688 * N85-15688 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0284 AIAA PAPER 85-0294 AIAA PAPER 85-0295 AIAA PAPER 85-0296 AIAA PAPER 85-0296 AIAA PAPER 85-0296 AIAA PAPER 85-0301 AIAA PAPER 85-0301 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0304 AIAA PAPER 85-0304 AIAA PAPER 85-0304 AIAA PAPER 85-0304 AIAA PAPER 85-0304 AIAA PAPER 85-0304 AIAA PAPER 85-0304	p 248 p 217 p 218 p 219 p 219 </td <td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19645 # A85-19646 # A85-19650 # A85-19650 # A85-19650 # A85-19650 # A85-19650 # A85-19650 # A85-19653 #</td> <td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0303 AIAA-85-0279 AIAA-85-0379 AIAA-85-0380 AMI-8406 ARAP-508</td> <td>p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 270 p 235 p 276 p 258 p 276 p 258 p 234 p 234 p 234 p 239 p 239</td> <td>A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15696 * N85-15687 * N85-15687 * N85-15688 * N85-16836 # N85-16836 #</td>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19645 # A85-19646 # A85-19650 # A85-19650 # A85-19650 # A85-19650 # A85-19650 # A85-19650 # A85-19653 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0303 AIAA-85-0279 AIAA-85-0379 AIAA-85-0380 AMI-8406 ARAP-508	p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 270 p 235 p 276 p 258 p 276 p 258 p 234 p 234 p 234 p 239 p 239	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15696 * N85-15687 * N85-15687 * N85-15688 * N85-16836 # N85-16836 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0300 AIAA PAPER 85-0300	p 248 p 217 p 218 p 219 p 219 <tr tr=""> <tr tr=""></tr></tr>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19643 # A85-19643 # A85-19643 # A85-19643 # A85-19643 # A85-19643 # A85-19644 # A85-19645 # A85-19645 # A85-19645 # A85-19650 # A85-19651 # A85-19652 # A85-19652 # A85-19652 # A85-19655 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA-PAPER-84-2070-CP AIAA-85-030 AIAA-85-0307 AIAA-85-0338 AIAA-85-03380 AMI-8406 ARAP-508	p 226 p 231 p 228 p 249 p 279 p 279 p 279 p 270 p 235 p 276 p 236 p 234 p 234 p 234 p 239 p 239	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15758 * N85-15786 * N85-15686 * N85-15688 * N85-15688 # N85-16836 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0284 AIAA PAPER 85-0284 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0293 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0300 AIAA PAPER 85-0300	p 248 p 217 p 218 p 218 p 218 p 218 p 218 p 219 p 248 p 274 p 264 p 274	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19643 # A85-19644 # A85-19645 # A85-19644 # A85-19645 # A85-19644 # A85-19645 # A85-19645 # A85-19645 # A85-19650 # A85-19655 # A85-19655 # A85-19655 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA A5-0503 AIAA-85-0300 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 AIA-85-0380 AIA-85-0380 AIA-85-038 A	p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 270 p 270 p 270 p 270 p 235 p 276 p 234 p 242 p 276 p 234 p 234 p 239 p 305 p 239	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15757 * N85-15682 * N85-15687 * N85-15683 # N85-16836 # N85-16833 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0279 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0284 AIAA PAPER 85-0292 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0309 AIAA PAPER 85-0309	p 248 p 217 p 218 p 218 p 218 p 218 p 218 p 218 p 219 p 219 p 219 p 219 p 219 p 218 p 224 p 268 p 268 p 219	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19643 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19645 # A85-19646 # A85-19654 # A85-19655 # A85-19656 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0303 AIAA-85-0309 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366	p 226 p 231 p 226 p 249 p 249 p 279 p 270 p 235 p 270 p 235 p 276 p 258 p 234 p 234 p 234 p 239 p 305 p 305	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15686 * N85-15687 * N85-15687 * N85-15688 * N85-16836 # N85-16833 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0300 AIAA PAPER 85-0302 AIAA PAPER 85-0304 AIAA PAPER 85-0304 AIAA PAPER 85-0304 AIAA PAPER 85-0308 AIAA PAPER 85-0308 AIAA PAPER 85-0308 AIAA PAPER 85-0310 AIAA PAPER 85-0311 AIAA PAPER 85-0312	p 248 p 217 p 218 p 218 p 218 p 218 p 218 p 218 p 219 p 219 p 219 p 219 p 219 p 248 p 268 p 199 p 219	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19635 # A85-19635 # A85-19643 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19648 # A85-19650 # A85-19651 # A85-19652 # A85-19653 # A85-19655 # A85-19655 # A85-19656 # A85-19656 # A85-19656 # A85-19656 # A85-19655 # A85-19656 # A85-19656 # A85-19656 # A85-19656 # A85-19656 # A85-19656 # A85-196565 #	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA-B3-0503 AIAA-85-0030 AIAA-85-0379 AIAA-85-0380 AIA-85-0380 AMI-8406 ARAP-508 ARAL-AERO-TM-366 ASME PAPER 84-TRIB-17	p 226 p 231 p 226 p 249 p 249 p 279 p 279 p 279 p 270 p 235 p 276 p 235 p 236 p 234 p 242 p 276 p 234 p 239 p 239 p 305 p 239 p 239	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15758 * N85-15686 * N85-15687 * N85-15688 * N85-16836 # N85-16633 # A85-21278 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0284 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0295 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0310 AIAA PAPER 85-0311 AIAA PAPER 85-0314 AIAA PAPER 85-0314 AIAA PAPER 85-0314 AIAA PAPER 85-0314	p 248 p 217 p 218 p 219 p 219 p 219 p 219 p 219 p 218 p 219 p 218 p 219 p 218 p 219 p 219 p 219 p 219 p 219 p 218 p 219 </td <td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19634 # A85-19641 # A85-19643 # A85-19644 # A85-19645 # A85-19644 # A85-19645 # A85-19645 # A85-19650 # A85-19655 # A85-19655 # A85-19655 # A85-19656 # A8</td> <td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA A5-0503 AIAA-85-0300 AIAA-85-0379 AIAA-85-0380 AIAA-85-0380 AIA-85-0380 AIA-85-038 AI</td> <td>p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 235 p 270 p 235 p 258 p 234 p 234 p 234 p 234 p 239 p 239 p 305 p 239 p 239 p 239 p 239</td> <td>A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15757 * N85-15686 * N85-15687 * N85-15688 * N85-15688 * N85-16836 # N85-16833 # A85-21278 #</td>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19634 # A85-19641 # A85-19643 # A85-19644 # A85-19645 # A85-19644 # A85-19645 # A85-19645 # A85-19650 # A85-19655 # A85-19655 # A85-19655 # A85-19656 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA A5-0503 AIAA-85-0300 AIAA-85-0379 AIAA-85-0380 AIAA-85-0380 AIA-85-0380 AIA-85-038 AI	p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 235 p 270 p 235 p 258 p 234 p 234 p 234 p 234 p 239 p 239 p 305 p 239 p 239 p 239 p 239	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15757 * N85-15686 * N85-15687 * N85-15688 * N85-15688 * N85-16836 # N85-16833 # A85-21278 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0292 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0310 AIAA PAPER 85-03112 AIAA PAPER 85-03112 AIAA PAPER 85-0312 AIAA PAPER 85-0312	p 248 p 217 p 218 p 219 p 219 p 219 p 219 p 219 p 219 p 248 p 244 p 268 p 274 p 275 p 275	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19645 # A85-19645 # A85-19650 # A85-19652 # A85-19652 # A85-19652 # A85-19655 # A85-19656 # A85-19658 # A85-19658 # A85-19659 # A85-19659 # A85-19659 # A85-19659 # A85-19659 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-83-0503 AIAA-85-0300 AIAA-85-0307 AIAA-85-0307 AIAA-85-0338 AIAA-85-0338 AIAA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-35	p 226 p 231 p 226 p 249 p 249 p 279 p 279 p 270 p 235 p 276 p 235 p 276 p 234 p 249 p 249 p 279 p 279 p 270 p 235 p 276 p 234 p 249 p 249 p 249 p 249 p 249 p 249 p 279 p 270 p 235 p 270 p 235 p 249 p 249 p 279 p 276 p 279 p 276 p 276 p 279 p 276 p 276 p 279 p 276 p 276 p 279 p 279	A85-19787 # A85-20873 # A85-19788 # A85-19789 # A85-19799 # A85-19791 # A85-19792 # N85-15752 # N85-15758 # N85-15786 # N85-15686 # N85-15686 # N85-16836 # N85-16839 # N85-16833 # A85-21298 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0309 AIAA PAPER 85-0309 AIAA PAPER 85-0310 AIAA PAPER 85-0312 AIAA PAPER 85-0314 AIAA PAPER 85-0314	p 248 p 217 p 218 p 219 p 214 p 268 p 275 p 275 p <t< td=""><td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19634 # A85-19643 # A85-19643 # A85-19643 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19650 # A85-19651 # A85-19652 # A85-19655 # A85-19656 # A85-19655 # A85-19656 # A85-19655 # A85-19656 # A8</td><td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA-PAPER 85-0498 AIAA-PAPER 85-0498 AIAA-85-0303 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 AIA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31</td><td>p 226 p 231 p 226 p 249 p 249 p 279 p 270 p 270 p 270 p 270 p 270 p 276 p 276 p 276 p 276 p 276 p 276 p 234 p 234 p 234 p 239 p 239 p 239 p 289 p 289 p 289 p 289 p 289 p 289 p 289 p 289 p 289</td><td>A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15758 * N85-15757 * N85-15682 * N85-15688 * N85-16836 # N85-16836 # N85-16833 # A85-21278 # A85-21293 * A85-21293 #</td></t<>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19634 # A85-19643 # A85-19643 # A85-19643 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19650 # A85-19651 # A85-19652 # A85-19655 # A85-19656 # A85-19655 # A85-19656 # A85-19655 # A85-19656 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA-PAPER 85-0498 AIAA-PAPER 85-0498 AIAA-85-0303 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 AIA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31	p 226 p 231 p 226 p 249 p 249 p 279 p 270 p 270 p 270 p 270 p 270 p 276 p 276 p 276 p 276 p 276 p 276 p 234 p 234 p 234 p 239 p 239 p 239 p 289 p 289 p 289 p 289 p 289 p 289 p 289 p 289 p 289	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15758 * N85-15757 * N85-15682 * N85-15688 * N85-16836 # N85-16836 # N85-16833 # A85-21278 # A85-21293 * A85-21293 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0279 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0292 AIAA PAPER 85-0302 AIAA PAPER 85-0310 AIAA PAPER 85-0310 AIAA PAPER 85-0311 AIAA PAPER 85-0315 AIAA PAPER 85-0315 AIAA PAPER 85-0315 AIAA PAPER 85-0315 AIAA PAPER 85-0316 AIAA PAPER 85-0316	p 248 p 217 p 218 p 219 p 248 p 268 p 274 p 275 p 275	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19634 # A85-19641 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19645 # A85-19645 # A85-19645 # A85-19655 # A85-19655 # A85-19655 # A85-19656 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0303 AIAA-85-0307 AIAA-85-0307 AIAA-85-0308 AIAA-85-0380 AIAA-85-0380 AIA-85-0380 AIA-85-0380 AIA-85-0380 AIA-85-0380 AIA-85-0380 AIA-85-0380 AIA-85-0380 AIAA-85-0380 ABL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-45 ASME PAPER 84-TRIB-45 <td>p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 235 p 270 p 235 p 258 p 234 p 234 p 234 p 234 p 239 p 239 p 239 p 239 p 289 p 289 p 289 p 289 p 289 p 289 p 289</td> <td>A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15752 * N85-15686 * N85-15686 * N85-15688 * N85-15688 # N85-16833 # A85-21278 # A85-21293 #</td>	p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 235 p 270 p 235 p 258 p 234 p 234 p 234 p 234 p 239 p 239 p 239 p 239 p 289 p 289 p 289 p 289 p 289 p 289 p 289	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15752 * N85-15686 * N85-15686 * N85-15688 * N85-15688 # N85-16833 # A85-21278 # A85-21293 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0300 AIAA PAPER 85-0310 AIAA PAPER 85-0311 AIAA PAPER 85-0316 AIAA PAPER 85-0316	p 248 p 217 p 218 p 219 p 248 p 268 p 275 p 275 p 275 p <t< td=""><td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19643 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19645 # A85-19644 # A85-19650 # A85-19651 # A85-19652 # A85-19652 # A85-19652 # A85-19652 # A85-19655 # A85-19656 # A85-19658 # A85-19665 # A85-19665 # A85-19661 # A85-19662 # A85-19665 # A85-19667 # A85-19667 # A8</td><td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-83-0503 AIAA-85-0300 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-131 ASME PAPER 84-TRIB-81 ASME PAPER 84-TRIB-81</td><td>p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 279 p 270 p 235 p 276 p 258 p 258 p 258 p 258 p 234 p 249 p 249 p 279 p 270 p 235 p 258 p 234 p 249 p 249 p 279 p 276 p 278 p 276 p 276 p 278 p 276 p 276 p 276 p 276 p 276 p 276 p 276 p 276 p 276 p 278 p 276 p 278 p 276 p 278 p 278 p 276 p 278 p 299 p 289 p 289</td><td>A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15752 * N85-15758 * N85-15688 * N85-15688 * N85-15688 # N85-16833 # A85-21293 * A85-21293 # A85-21293 #</td></t<>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19643 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19645 # A85-19644 # A85-19650 # A85-19651 # A85-19652 # A85-19652 # A85-19652 # A85-19652 # A85-19655 # A85-19656 # A85-19658 # A85-19665 # A85-19665 # A85-19661 # A85-19662 # A85-19665 # A85-19667 # A85-19667 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-83-0503 AIAA-85-0300 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-131 ASME PAPER 84-TRIB-81	p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 279 p 270 p 235 p 276 p 258 p 258 p 258 p 258 p 234 p 249 p 249 p 279 p 270 p 235 p 258 p 234 p 249 p 249 p 279 p 276 p 278 p 276 p 276 p 278 p 276 p 276 p 276 p 276 p 276 p 276 p 276 p 276 p 276 p 278 p 276 p 278 p 276 p 278 p 278 p 276 p 278 p 299 p 289 p 289	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15752 * N85-15758 * N85-15688 * N85-15688 * N85-15688 # N85-16833 # A85-21293 * A85-21293 # A85-21293 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0271 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0284 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0300 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0310 AIAA PAPER 85-0314 AIAA PAPER 85-0314 AIAA PAPER 85-0316 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0316 AIAA PAPER 85	p 248 p 217 p 218 p 219 p 219 p 219 p 219 p 219 p 248 p 263 p 199 p 275 p 275 p 275 p 263 p 263 p 263	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19635 # A85-19643 # A85-19644 # A85-19645 # A85-19646 # A85-19648 # A85-19650 # A85-19651 # A85-19652 # A85-19652 # A85-19652 # A85-19655 # A85-19665 # A85-19665 # A85-19665 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0300 AIAA-85-0300 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 AIA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-8 BBN-5657	p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 270 p 275 p 276 p 258 p 258 p 258 p 234 p 239 p 239 p 239 p 239 p 239 p 239 p 289 p 289 p 289 p 289 p 289 p 289 p 289 p 289	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15757 * N85-156862 * N85-15687 * N85-15687 * N85-15683 # N85-16833 # A85-21278 # A85-21293 * A85-21293 # A85-21283 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0284 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0315 AIAA PAPER 85-0312 AIAA PAPER 85-0315 AIAA PAPER 85-0316 AIAA PAPER 85-0329 AIAA PAPER 85	p 248 p 217 p 218 p 218 p 218 p 218 p 218 p 219 p 240 p 274 p 275 p 275 p 281 p 263 p 2640	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19643 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19645 # A85-19644 # A85-19654 # A85-19652 # A85-19653 # A85-19652 # A85-19655 # A85-19655 # A85-19655 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19662 # A85-19678 # A85-19677 # A85-19677 # A85-19677 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0503 AIAA-85-0279 AIAA-85-0379 AIAA-85-0379 AIAA-85-0380 AMI-8406 ARA-8508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31	p 226 p 231 p 226 p 249 p 249 p 279 p 279 p 279 p 270 p 235 p 276 p 235 p 276 p 234 p 249 p 279 p 249 p 249 p 279 p 249 p 279 p 249 p 279 p 279 p 249 p 279 p 249 p 279 p 279 p 279 p 249 p 279 p 279 p 279 p 249 p 249 p 279 p 279 p 279 p 279 p 279 p 249 p 279 p 249 p 279 p 249 p 279 p 249 p 249 p 279 p 249 p 249 p 249 p 249 p 249 p 279 p 279 p 279 p 279 p 276 p 249 p 249 p 279 p 279 p 279 p 276 p 249 p 249 p 249 p 249 p 279 p 276 p 249 p 249	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15686 * N85-15686 * N85-15686 * N85-15688 * N85-15688 # N85-16833 # A85-21298 # A85-21296 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0294 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0310 AIAA PAPER 85-0314 AIAA PAPER 85-0314 AIAA PAPER 85-0316 AIAA PAPER 85-0336 AIAA PAPER 85-0336 AIAA PAPER 85-0336	p 248 p 217 p 218 p 219 p 248 p 263 p 263 p 240	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19635 # A85-19635 # A85-19643 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19648 # A85-19648 # A85-19650 # A85-19651 # A85-19652 # A85-19653 # A85-19655 # A85-19655 # A85-19655 # A85-19655 # A85-19656 # A85-19657 # A85-19662 # A85-19662 # A85-19665 # A85-19678 # A85-19678 # A85-19678 # A85-19679 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-B3-0503 AIAA-85-0300 AIAA-85-0379 AIAA-85-0380 AIAA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-131 ASME PAPER 84-TRIB-8 BBN-5667 BLL-PNR-90237-(899.3153)	p 226 p 231 p 226 p 249 p 279 p 270 p 270 p 270 p 270 p 270 p 270 p 276 p 258 p 276 p 258 p 234 p 249 p 258 p 234 p 249 p 249 p 258 p 234 p 249 p 249 p 258 p 258 p 249 p 249 p 270 p 276 p 276 p 249 p 270 p 276 p 276 p 276 p 249 p 279 p 276 p 276 p 249 p 249	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15758 * N85-15688 * N85-16862 * N85-16868 * N85-16839 # N85-16839 # A85-21298 # A85-21298 # A85-21298 # A85-21298 # A85-21298 # A85-21298 # A85-21298 # A85-21298 # A85-21298 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0271 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0284 AIAA PAPER 85-0284 AIAA PAPER 85-0292 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0302 AIAA PAPER 85-0310 AIAA PAPER 85-0310 AIAA PAPER 85-0310 AIAA PAPER 85-0310 AIAA PAPER 85-0310 AIAA PAPER 85-0310 AIAA PAPER 85-0311 AIAA PAPER 85-0310 AIAA PAPER 85-0310 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0322 AIAA PAPER 85-0329 AIAA PAPER 85-0339	p 248 p 217 p 218 p 219 p 274 p 275 p 275 p 275 p 240 p <t< td=""><td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19635 # A85-19644 # A85-19645 # A85-19644 # A85-19645 # A85-19645 # A85-19645 # A85-19655 # A85-19661 # A85-19662 # A85-19663 # A85-19665 # A85-19665 # A85-19665 # A85-19665 # A85-19665 # A8</td><td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0303 AIAA-85-0300 AIAA-85-0307 AIAA-85-0308 AIAA-85-0380 AIAA-85-0380 AIA-85-0380 AIAA-85-0380 ARAP-508 ARAP-508 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-8 BBN-5667 BLL-PNR-90237-(899.3153)</td><td>p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 235 p 276 p 258 p 234 p 234 p 234 p 234 p 234 p 234 p 234 p 239 p 239 p 289 p 289 p 289 p 289 p 289 p 289 p 289 p 289 p 289</td><td>A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19790 # N85-15752 * N85-15757 * N85-15682 * N85-15757 * N85-16826 * N85-16836 # N85-16836 # N85-16833 # A85-21288 # A85-21288 # N85-16503 # N85-17159 #</td></t<>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19633 # A85-19635 # A85-19644 # A85-19645 # A85-19644 # A85-19645 # A85-19645 # A85-19645 # A85-19655 # A85-19661 # A85-19662 # A85-19663 # A85-19665 # A85-19665 # A85-19665 # A85-19665 # A85-19665 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0303 AIAA-85-0300 AIAA-85-0307 AIAA-85-0308 AIAA-85-0380 AIAA-85-0380 AIA-85-0380 AIAA-85-0380 ARAP-508 ARAP-508 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-8 BBN-5667 BLL-PNR-90237-(899.3153)	p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 235 p 276 p 258 p 234 p 234 p 234 p 234 p 234 p 234 p 234 p 239 p 239 p 289 p 289 p 289 p 289 p 289 p 289 p 289 p 289 p 289	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19790 # N85-15752 * N85-15757 * N85-15682 * N85-15757 * N85-16826 * N85-16836 # N85-16836 # N85-16833 # A85-21288 # A85-21288 # N85-16503 # N85-17159 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0292 AIAA PAPER 85-0300 AIAA PAPER 85-0302 AIAA PAPER 85-0310 AIAA PAPER 85-03112 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0316 AIAA PAPER 85-0329 AIAA PAPER 85-0336 AIAA PAPER 85-0337 AIAA PAPER 85-0338 AIAA PAPER 85-0338	p 248 p 217 p 218 p 219 p 240 p 246 p 2463 p 2463 p 2464 p 2464 p 2464 p 2464 p 2464	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19643 # A85-19644 # A85-19643 # A85-19652 # A85-19652 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA-83-0503 AIAA-85-0300 AIAA-85-0307 AIAA-85-0307 AIAA-85-0308 AIAA-85-0380 AMI-8406 ARAP-508 ARAP-508 ARAP-508 ABL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-13 ASME PAPER 84-TRIB-85 BBN-5657 BLL-PNR-90237-(899.3153) BMFT-FE-W-84-036	p 226 p 231 p 226 p 249 p 249 p 279 p 270 p 275 p 276 p 235 p 276 p 235 p 276 p 234 p 249 p 249 p 279 p 249 p 279 p 249 p 249 p 279 p 270 p 235 p 270 p 249 p 279 p 270 p 270 p 235 p 276 p 249 p 249 p 279 p 270 p 235 p 249 p 249 p 279 p 249 p 279 p 249 p 249	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15758 * N85-15786 * N85-15686 * N85-15688 * N85-16839 # A85-21283 # A85-21283 # A85-21283 # N85-16503 # N85-16503 # N85-16503 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0283 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0304 AIAA PAPER 85-0314 AIAA PAPER 85-0314 AIAA PAPER 85-0314 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0314 AIAA PAPER 85-0316 AIAA PAPER 85-0326 AIAA PAPER 85-0337 AIAA PAPER 85-0337 AIAA PAPER 85-0337 AIAA PAPER 85-0336 AIAA PAPER 85-0337 AIAA PAPER 85-0337 AIAA PAPER 85-0337 AIAA PAPER 85-0345 AIAA PAPER 85-0345	p 248 p 217 p 218 p 218 p 218 p 218 p 218 p 218 p 219 p 248 p 263 p 264 p 240 p 2440 p <	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19632 # A85-19632 # A85-19632 # A85-19633 # A85-19634 # A85-19643 # A85-19643 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19650 # A85-19651 # A85-19652 # A85-19655 # A85-19655 # A85-19655 # A85-19655 # A85-19655 # A85-19656 # A85-19658 # A85-19658 # A85-19678 # A85-19678 # A85-19677 # A85-19677 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0303 AIAA-85-0307 AIAA-85-0380 AIAA-85-0380 AIAA-85-0380 AIA-85-0380 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-8 BBN-56657	p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 270 p 270 p 270 p 270 p 275 p 276 p 258 p 276 p 234 p 239 p 239 p 239 p 289 p 270 p 276 p 279 p 279 p 279 p 279 p 279 p 279 p 279 p 289 p 297 p 277 p 277 p 277 p 277 p 277 p 277 p 276 p 277 p 277 p 277 p 277	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15758 * N85-15758 * N85-15682 * N85-15682 * N85-16836 # N85-16833 # A85-21278 # A85-21283 # A85-21283 # N85-16503 # N85-16503 # N85-16533 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0279 AIAA PAPER 85-0279 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0292 AIAA PAPER 85-0302 AIAA PAPER 85-0312 AIAA PAPER 85	p 248 p 217 p 218 p 218 p 218 p 218 p 218 p 219 p 248 p 240 p 240 p 246 p <t< td=""><td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19644 # A85-19643 # A85-19644 # A85-19644 # A85-19644 # A85-19645 # A85-19654 # A85-19655 # A85-19656 # A85-19657 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19662 # A8</td><td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 84-2070-CP AIAA-85-0300 AIAA-85-0307 AIAA-85-0307 AIAA-85-0308 AIAA-85-0308 AIAA-85-0380 ARAP-508 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-18 BBN-5657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-036 BMFT-FB</td><td>p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 270 p 235 p 270 p 235 p 258 p 234 p 234 p 234 p 234 p 234 p 239 p 239 p 239 p 289 p 292 p 292 p 292 p 292 p 292 p 289 p 292 p 292</td><td>A85-19787 # A85-20873 # A85-20873 # A85-19788 # A85-19789 # A85-19790 # A85-19790 # A85-19792 # N85-15752 # N85-15757 # N85-15686 # N85-15687 # N85-16836 # N85-16833 # A85-21283 # A85-21293 # A85-16831 # N85-16831 #</td></t<>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19644 # A85-19643 # A85-19644 # A85-19644 # A85-19644 # A85-19645 # A85-19654 # A85-19655 # A85-19656 # A85-19657 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19662 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 84-2070-CP AIAA-85-0300 AIAA-85-0307 AIAA-85-0307 AIAA-85-0308 AIAA-85-0308 AIAA-85-0380 ARAP-508 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-18 BBN-5657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-036 BMFT-FB	p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 270 p 235 p 270 p 235 p 258 p 234 p 234 p 234 p 234 p 234 p 239 p 239 p 239 p 289 p 292 p 292 p 292 p 292 p 292 p 289 p 292 p 292	A85-19787 # A85-20873 # A85-20873 # A85-19788 # A85-19789 # A85-19790 # A85-19790 # A85-19792 # N85-15752 # N85-15757 # N85-15686 # N85-15687 # N85-16836 # N85-16833 # A85-21283 # A85-21293 # A85-16831 # N85-16831 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0299 AIAA PAPER 85-0300 AIAA PAPER 85-0310 AIAA PAPER 85-0312 AIAA PAPER 85-0320 AIAA PAPER 85-0330 AIAA PAPER 85-0330 AIAA PAPER 85-0330 AIAA PAPER 85-0330 AIAA PAPER 85-0340 AIAA PAPER 85	p 248 p 217 p 218 p 219 p 246 p 275 p 263 p 240 p 240 p 240 p 240 p 241 p 242 p 243 p 244 p 245 p 2463 p 2464 p 2464 p 2463 p 2464 p 2469 p 249 p 240	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19634 # A85-19635 # A85-19643 # A85-19652 # A85-19652 # A85-19655 # A85-19656 # A85-19658 # A85-19665 # A85-19665 # A85-19667 # A85-19667 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-83-0503 AIAA-85-0030 AIAA-85-0379 AIAA-85-0380 AIA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-13 ASME PAPER 84-TRIB-31 BBN-5657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-036 BMFT-FB-W-84-032 BMFT-FB-W-84-032 BMFT-FB-W-84-032	p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 270 p 275 p 276 p 258 p 258 p 258 p 258 p 258 p 258 p 234 p 249 p 270 p 258 p 258 p 249 p 249 p 279 p 249 p 279 p 270 p 270 p 270 p 249 p 270 p 270 p 249 p 270 p 249 p 270 p 249 p 270 p 249 p 270 p 249 p 249 p 279 p 249 p 279 p 249 p 249 p 279 p 249 p 249 p 279 p 249 p 249 p 249 p 279 p 249 p 249 p 249 p 249 p 249 p 249 p 249 p 249 p 270 p 249 p 249 p 249 p 270 p 249 p 249	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15752 * N85-15758 * N85-15686 * N85-16872 * N85-16833 # A85-21293 * A85-21293 * A85-21293 # A85-21293 # A85-21
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0284 AIAA PAPER 85-0284 AIAA PAPER 85-0284 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0302 AIAA PAPER 85-0314 AIAA PAPER 85-0314 AIAA PAPER 85-0314 AIAA PAPER 85-0312 AIAA PAPER 85-0314 AIAA PAPER 85-0322 AIAA PAPER 85-0322 AIAA PAPER 85-0336 AIAA PAPER 85-0339 AIAA PAPER 85-0339 AIAA PAPER 85-0347 AIAA PAPER 85-0347 AIAA PAPER 85-0347 AIAA PAPER 85-0347	p 248 p 217 p 218 p 219 p 274 p 263 p 264 p 263 p 240 p 240 p 241 p 264 p 264 </td <td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19635 # A85-19635 # A85-19644 # A85-19644 # A85-19644 # A85-19654 # A85-19654 # A85-19655 # A85-19652 # A85-19652 # A85-19652 # A85-19652 # A85-19655 # A85-19655 # A85-19655 # A85-19655 # A85-19655 # A85-19655 # A85-19658 # A85-19658 # A85-19665 # A85-19665 # A85-19671 # A85-19680 # A8</td> <td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-BAPER 85-0498 AIAA-85-0303 AIAA-85-0300 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 AIA-85-0380 AIAA-85-0380 AMI-8406 ARAP-508 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-8 BBN-5657 BLL-PNR-90237-(899.3153)</td> <td>p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 270 p 270 p 275 p 276 p 258 p 258 p 234 p 239 p 239 p 239 p 239 p 289 p 290 p 289 p 290 p 290</td> <td>A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15757 * N85-15686 * N85-15687 * N85-16826 * N85-16836 # N85-16833 # A85-21283 # A85-21293 * A85-21293 # A85-21293 # A85-21</td>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19633 # A85-19633 # A85-19635 # A85-19635 # A85-19644 # A85-19644 # A85-19644 # A85-19654 # A85-19654 # A85-19655 # A85-19652 # A85-19652 # A85-19652 # A85-19652 # A85-19655 # A85-19655 # A85-19655 # A85-19655 # A85-19655 # A85-19655 # A85-19658 # A85-19658 # A85-19665 # A85-19665 # A85-19671 # A85-19680 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-BAPER 85-0498 AIAA-85-0303 AIAA-85-0300 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 AIA-85-0380 AIAA-85-0380 AMI-8406 ARAP-508 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-8 BBN-5657 BLL-PNR-90237-(899.3153)	p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 270 p 270 p 275 p 276 p 258 p 258 p 234 p 239 p 239 p 239 p 239 p 289 p 290 p 289 p 290 p 290	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19790 # A85-19790 # A85-19792 # N85-15752 * N85-15757 * N85-15686 * N85-15687 * N85-16826 * N85-16836 # N85-16833 # A85-21283 # A85-21293 * A85-21293 # A85-21293 # A85-21
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0283 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0292 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0316 AIAA PAPER 85-0329 AIAA PAPER 85-0339 AIAA PAPER 85-0349 AIAA PAPER 85	p 248 p 217 p 218 p 218 p 218 p 218 p 218 p 218 p 219 p 240 p 268 p 275 p 275 p 275 p 240 p 240 p 240 p 240 p 240 p 241 p 242 p 243 p 244 p 249 p 240 p 248 </td <td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19643 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19645 # A85-19645 # A85-19650 # A85-19651 # A85-19655 # A85-19655 # A85-19655 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19668 # A85-19671 # A85-19671 # A85-19685 # A8</td> <td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-030 AIAA-85-0307 AIAA-85-0338 AIAA-85-0338 AIAA-85-0338 AIAA-85-0338 AIAA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-13 ASME PAPER 84-TRIB-8 BBN-5657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-039 BMFT-FB-W-84-039 BMFT-FB-W-84-042 BR91753</td> <td>p 226 p 231 p 226 p 249 p 249 p 279 p 270 p 235 p 276 p 235 p 276 p 234 p 242 p 234 p 249 p 269 p 289 p 297 p 297 p 297 p 297 p 297 p 297 p 297 p 269 p 297 p 269 p 297 p 269 p 297 p 269 p 297 p 269 p 269</td> <td>A85-19787 # A85-20873 # A85-20873 # A85-19788 # A85-19789 # A85-19790 # A85-19792 # N85-15752 # N85-15758 * N85-15758 * N85-15686 # N85-15686 # N85-16836 # N85-16839 # A85-21298 # A85-21298 # A85-21298 # A85-21298 # A85-21298 # N85-16503 # N85-16503 # N85-16503 # N85-166503 # N85-16838 # N85-16838 # N85-16838 # N85-16871 # N85-16871 #</td>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19643 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19644 # A85-19645 # A85-19645 # A85-19650 # A85-19651 # A85-19655 # A85-19655 # A85-19655 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19658 # A85-19668 # A85-19671 # A85-19671 # A85-19685 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-030 AIAA-85-0307 AIAA-85-0338 AIAA-85-0338 AIAA-85-0338 AIAA-85-0338 AIAA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-13 ASME PAPER 84-TRIB-8 BBN-5657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-039 BMFT-FB-W-84-039 BMFT-FB-W-84-042 BR91753	p 226 p 231 p 226 p 249 p 249 p 279 p 270 p 235 p 276 p 235 p 276 p 234 p 242 p 234 p 249 p 269 p 289 p 297 p 297 p 297 p 297 p 297 p 297 p 297 p 269 p 297 p 269 p 297 p 269 p 297 p 269 p 297 p 269 p 269	A85-19787 # A85-20873 # A85-20873 # A85-19788 # A85-19789 # A85-19790 # A85-19792 # N85-15752 # N85-15758 * N85-15758 * N85-15686 # N85-15686 # N85-16836 # N85-16839 # A85-21298 # A85-21298 # A85-21298 # A85-21298 # A85-21298 # N85-16503 # N85-16503 # N85-16503 # N85-166503 # N85-16838 # N85-16838 # N85-16838 # N85-16871 # N85-16871 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0299 AIAA PAPER 85-0300 AIAA PAPER 85-0310 AIAA PAPER 85-0314 AIAA PAPER 85-0314 AIAA PAPER 85-0316 AIAA PAPER 85-0320 AIAA PAPER 85-0330 AIAA PAPER 85-0330 AIAA PAPER 85-0346 AIAA PAPER 85-0340 AIAA PAPER 85	p 248 p 217 p 218 p 219 p 219 p 219 p 219 p 219 p 219 p 240 p 263 p 264 p 263 p 240 p 240 p 240 p 244 p 246 p 246 p 246 p <t< td=""><td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19632 # A85-19633 # A85-19632 # A85-19632 # A85-19633 # A85-19634 # A85-19643 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19648 # A85-19650 # A85-19651 # A85-19652 # A85-19655 # A85-19655 # A85-19656 # A85-19657 # A85-19665 # A85-19665 # A85-19665 # A85-19665 # A85-19665 # A85-19666 # A85-19678 # A85-19680 # A8</td><td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-B3-0503 AIAA-85-0279 AIAA-85-0379 AIAA-85-0380 AIAA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-131 ASME PAPER 84-TRIB-31 BBN-5667 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-039 BMFT-FB-W-84-034 BH931753 BR93171 </td><td>p 226 p 231 p 226 p 249 p 279 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 276 p 258 p 249 p 276 p 234 p 249 p 249 p 249 p 270 p 235 p 249 p 270 p 258 p 258 p 249 p 249 p 279 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 249 p 270 p 270 p 270 p 270 p 249 p 249 p 270 p 258 p 249 p 249 p 249 p 249 p 270 p 258 p 249 p 270 p 258 p 249 p 249</td><td>A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15757 * N85-15688 * N85-16862 * N85-16833 # A85-21298 # A85-21</td></t<>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19632 # A85-19633 # A85-19632 # A85-19632 # A85-19633 # A85-19634 # A85-19643 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19648 # A85-19650 # A85-19651 # A85-19652 # A85-19655 # A85-19655 # A85-19656 # A85-19657 # A85-19665 # A85-19665 # A85-19665 # A85-19665 # A85-19665 # A85-19666 # A85-19678 # A85-19680 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-B3-0503 AIAA-85-0279 AIAA-85-0379 AIAA-85-0380 AIAA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-131 ASME PAPER 84-TRIB-31 BBN-5667 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-039 BMFT-FB-W-84-034 BH931753 BR93171	p 226 p 231 p 226 p 249 p 279 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 276 p 258 p 249 p 276 p 234 p 249 p 249 p 249 p 270 p 235 p 249 p 270 p 258 p 258 p 249 p 249 p 279 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 270 p 249 p 270 p 270 p 270 p 270 p 249 p 249 p 270 p 258 p 249 p 249 p 249 p 249 p 270 p 258 p 249 p 270 p 258 p 249 p 249	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15757 * N85-15688 * N85-16862 * N85-16833 # A85-21298 # A85-21
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0279 AIAA PAPER 85-0279 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0292 AIAA PAPER 85-0302 AIAA PAPER 85-0302 AIAA PAPER 85-0310 AIAA PAPER 85-0312 AIAA PAPER 85-0322 AIAA PAPER 85-0322 AIAA PAPER 85-0322 AIAA PAPER 85-0330 AIAA PAPER 85-0330 AIAA PAPER 85-0346 AIAA PAPER 85-0346 AIAA PAPER 85-0346 AIAA PAPER 85-0346 AIAA PAPER 85-0350 AIAA PAPER 85	p 248 p 217 p 218 p 219 p 240 p 263 p 264 p 263 p 240 p 240 p 240 p 240 p 241 p 242 p 243 p 244 p 244 p 245 p 220 p 220 </td <td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19634 # A85-19643 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19645 # A85-19654 # A85-19655 # A85-19655 # A85-19655 # A85-19656 # A85-19658 # A85-19658 # A85-19658 # A85-19662 # A8</td> <td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0300 AIAA-85-0300 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 ARAP-508 ARAP-508 ARAP-508 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-18 BBN-5657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-036 BMFT-FB-W-84-038</td> <td>p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 279 p 279 p 279 p 270 p 235 p 258 p 234 p 234 p 239 p 239 p 239 p 239 p 289 p 290 p 289 p 289 p 290 p 290 p 290 p 290 p 289 p 290 p 200 p 200</td> <td>A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19790 # N85-15752 * N85-15757 * N85-15757 * N85-15682 * N85-16822 * N85-16833 # N85-16833 # A85-21283 # A85-21283 # A85-21283 # N85-16838 # N85-16837 # N85-16870 # N85-16870 # N85-16870 # N85-16870 #</td>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19634 # A85-19643 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19643 # A85-19644 # A85-19645 # A85-19654 # A85-19655 # A85-19655 # A85-19655 # A85-19656 # A85-19658 # A85-19658 # A85-19658 # A85-19662 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-85-0300 AIAA-85-0300 AIAA-85-0307 AIAA-85-0379 AIAA-85-0380 ARAP-508 ARAP-508 ARAP-508 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-18 BBN-5657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-036 BMFT-FB-W-84-038	p 226 p 231 p 226 p 249 p 279 p 279 p 279 p 279 p 279 p 279 p 270 p 235 p 258 p 234 p 234 p 239 p 239 p 239 p 239 p 289 p 290 p 289 p 289 p 290 p 290 p 290 p 290 p 289 p 290 p 200 p 200	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19790 # N85-15752 * N85-15757 * N85-15757 * N85-15682 * N85-16822 * N85-16833 # N85-16833 # A85-21283 # A85-21283 # A85-21283 # N85-16838 # N85-16837 # N85-16870 # N85-16870 # N85-16870 # N85-16870 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0292 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0310 AIAA PAPER 85-03112 AIAA PAPER 85-0312 AIAA PAPER 85-0312 AIAA PAPER 85-0316 AIAA PAPER 85-0320 AIAA PAPER 85-0330 AIAA PAPER 8	p 248 p 217 p 218 p 218 p 218 p 218 p 218 p 218 p 219 p 240 p 274 p 275 p 275 p 275 p 275 p 240 p 240 </td <td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19643 # A85-19644 # A85-19643 # A85-19645 # A85-19652 # A85-19655 # A85-19656 # A85-19658 # A85-19658 # A85-19659 # A85-19665 # A85-19665 # A8</td> <td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-83-0503 AIAA-85-0300 AIAA-85-0307 AIAA-85-0307 AIAA-85-0308 AIAA-85-0380 AMI-8406 ARAP-508 ARAP-508 ARAP-508 ARAP-508 ABL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-13 ASME PAPER 84-TRIB-8 BBN-5657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-036 BMFT-FB-W-84-036 BMFT-FB-W-84-032 BR91753 BR93171 BR93462</td> <td>p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 235 p 276 p 235 p 276 p 234 p 248 p 234 p 248 p 234 p 248 p 234 p 248 p 239 p 289 p 297 p 295 p 295</td> <td>A85-19787 # A85-20873 # A85-20873 # A85-19788 # A85-19789 # A85-19790 # A85-19792 # N85-15752 # N85-15752 # N85-15758 # N85-15786 # N85-15688 # N85-15688 # N85-16839 # A85-21293 # A85-21293 # A85-21293 # A85-21293 # N85-166503 # N85-166503 # N85-16871 # N85-16871 # N85-16871 # N85-16872 # N85-16872 # N85-16872 # N85-16872 # N85-16873 # N85-16873 # N85-16873 # N85-16873 #</td>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19630 # A85-19631 # A85-19632 # A85-19633 # A85-19634 # A85-19635 # A85-19642 # A85-19643 # A85-19644 # A85-19643 # A85-19645 # A85-19652 # A85-19655 # A85-19656 # A85-19658 # A85-19658 # A85-19659 # A85-19665 # A85-19665 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0494 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-83-0503 AIAA-85-0300 AIAA-85-0307 AIAA-85-0307 AIAA-85-0308 AIAA-85-0380 AMI-8406 ARAP-508 ARAP-508 ARAP-508 ARAP-508 ABL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-13 ASME PAPER 84-TRIB-8 BBN-5657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-036 BMFT-FB-W-84-036 BMFT-FB-W-84-032 BR91753 BR93171 BR93462	p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 235 p 276 p 235 p 276 p 234 p 248 p 234 p 248 p 234 p 248 p 234 p 248 p 239 p 289 p 297 p 295 p 295	A85-19787 # A85-20873 # A85-20873 # A85-19788 # A85-19789 # A85-19790 # A85-19792 # N85-15752 # N85-15752 # N85-15758 # N85-15786 # N85-15688 # N85-15688 # N85-16839 # A85-21293 # A85-21293 # A85-21293 # A85-21293 # N85-166503 # N85-166503 # N85-16871 # N85-16871 # N85-16871 # N85-16872 # N85-16872 # N85-16872 # N85-16872 # N85-16873 # N85-16873 # N85-16873 # N85-16873 #
AIAA PAPER 85-0276 AIAA PAPER 85-0276 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0277 AIAA PAPER 85-0278 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0281 AIAA PAPER 85-0282 AIAA PAPER 85-0282 AIAA PAPER 85-0294 AIAA PAPER 85-0294 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0293 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0300 AIAA PAPER 85-0310 AIAA PAPER 85-0314 AIAA PAPER 85-0314 AIAA PAPER 85-0316 AIAA PAPER 85-0336 AIAA PAPER 85-0336 AIAA PAPER 85-0336 AIAA PAPER 85-0336 AIAA PAPER 85-0336 AIAA PAPER 85-0346 AIAA PAPER 85-0346 AIAA PAPER 85-0346 AIAA PAPER 85-0346 AIAA PAPER 85-0350 AIAA PAPER 85	p 248 p 217 p 218 p 219 p 240 p 246 p <t< td=""><td>A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19632 # A85-19632 # A85-19632 # A85-19632 # A85-19633 # A85-19634 # A85-19643 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19648 # A85-19648 # A85-19650 # A85-19651 # A85-19652 # A85-19655 # A85-19655 # A85-19656 # A85-19657 # A85-19668 # A85-19678 # A85-19678 # A85-19678 # A85-19678 # A85-19680 # A85-19680 # A8</td><td>AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-B3-0503 AIAA-85-030 AIAA-85-0379 AIAA-85-0380 AIAA-85-0380 AIA-85-0380 AMI-8406 ARA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-8 BBN-56657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-038 BMFT-FB-W-84-036 BMFT-FB-W-84-038 BMFT-FB-W-84-038 BMFT-FB-W-84-036 BMFT-FB-W-84-032 BR93171 BR93171 BR93171 BR93462</td><td>p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 270 p 270 p 270 p 270 p 275 p 276 p 258 p 234 p 249 p 279 p 276 p 234 p 239 p 239 p 239 p 289 p 297</td><td>A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15757 * N85-15757 * N85-15688 * N85-16836 # N85-16838 # N85-16839 # A85-21296 # A85-21296 # A85-21296 # A85-21296 # N85-16503 # N85-16838 # N85-16838 # N85-16838 # N85-16837 # N85-16837 # N85-16838 # N85-16871 # N85-16872 # N85-16872 #</td></t<>	A85-19627 # A85-19628 # A85-19629 # A85-19630 # A85-19631 # A85-19632 # A85-19632 # A85-19632 # A85-19632 # A85-19632 # A85-19633 # A85-19634 # A85-19643 # A85-19643 # A85-19644 # A85-19648 # A85-19648 # A85-19648 # A85-19648 # A85-19650 # A85-19651 # A85-19652 # A85-19655 # A85-19655 # A85-19656 # A85-19657 # A85-19668 # A85-19678 # A85-19678 # A85-19678 # A85-19678 # A85-19680 # A85-19680 # A8	AIAA PAPER 85-0492 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0493 AIAA PAPER 85-0495 AIAA PAPER 85-0495 AIAA PAPER 85-0496 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA PAPER 85-0498 AIAA PAPER 85-0497 AIAA PAPER 85-0498 AIAA-B3-0503 AIAA-85-030 AIAA-85-0379 AIAA-85-0380 AIAA-85-0380 AIA-85-0380 AMI-8406 ARA-85-0380 AMI-8406 ARAP-508 ARL-AERO-TM-366 ASME PAPER 84-TRIB-17 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-31 ASME PAPER 84-TRIB-8 BBN-56657 BLL-PNR-90237-(899.3153) BMFT-FB-W-84-036 BMFT-FB-W-84-038 BMFT-FB-W-84-036 BMFT-FB-W-84-038 BMFT-FB-W-84-038 BMFT-FB-W-84-036 BMFT-FB-W-84-032 BR93171 BR93171 BR93171 BR93462	p 226 p 231 p 226 p 249 p 279 p 279 p 270 p 270 p 270 p 270 p 270 p 275 p 276 p 258 p 234 p 249 p 279 p 276 p 234 p 239 p 239 p 239 p 289 p 297	A85-19787 # A85-20873 * A85-20873 * A85-19788 * A85-19789 # A85-19790 # A85-19792 # N85-15752 * N85-15757 * N85-15757 * N85-15688 * N85-16836 # N85-16838 # N85-16839 # A85-21296 # A85-21296 # A85-21296 # A85-21296 # N85-16503 # N85-16838 # N85-16838 # N85-16838 # N85-16837 # N85-16837 # N85-16838 # N85-16871 # N85-16872 # N85-16872 #

CSL-TN-84-256	p 301	A85-21973 * #
DFVLR-MITT-84-09	p 277	N85-15763 #
DFVLR-MITT-84-14	p 306	N85-17677 #
UFVLH-MIT (-84-16	p 245	N85-15/09 #
DOT/FAA/AT-84/2	p 245	N85-15707 #
DOT/FAA/EE-84-04	p 305	N85-16595 #
DTNSRDC-84/052	p 201	N85-15661 #
06-52147	p 255	N85-15714 * #
-2197	n 200	N85-15658 * #
-2294	p 305	N85-17667 * #
E-2302	p 295	N85-16100 * #
E-2365	p 295	N85-16096 * #
E-2369	p 265	N85-15725 #
E-2408	n 234	N85-15689 * #
E-2413	p 276	N85-15757 * #
E-2414	p 276	N85-15758 * #
E-2421	p 242	N85-15702 * #
EOARD-TR-85-03	p 242	N85-15703 #
ESA-TT-895	p 277	N85-15763 #
AA-CT-84-12	p 283	N85-15919 #
FAA-CT-84-22	p 283	N85-15920 #
	p 242	1105-100-0 . #
FAA/EE-84-05	р́ 306	N85-17672 #
FAA/EE-84-13	p 299	N85-17435 #
FAA/EE-84-14	p 299	N85-17436 #
FAA/EE-04-15	p 305	N85-10093 #
FAA/FE-84-7	p 306	N85-17670 #
EQ4.C.20552-D2/E4 E9)	n 283	N85-15831 #
FOA-C-20559-D8(E3)	p 256	N85-15720 #
-TD-ID(RS)T-0969-84	p 204	N85-16762 #
GAO/NSIAD-85-2	p 308	N85-16682 #
GPO-35-977	p 246	N85-16851 #
H-1194	p 255	N85-15713 * #
H-1252	p 270	N85-15752 * #
H-1273	p 205 p 234	N85-15/29 #
HEL-TN-11-84	p 293	N85-15954 #
RT-TB-B-40/82	p 246	N85-16860 #
SBN-3-87977-055-7-PT-1	n 270	N85-16887 #
ISBN-3-87977-055-7-PT-2	p 279	N85-16888 #
ISBN-92-835-0358-9	p 204	N85-16771 #
ISBN-92-835-0362-7	p 266	N85-15733 #
ISBN-92-835-0363-5	p 201	N85-15664 #
ISBN-92-835-0365-1	p 204	N65-16/97 #
ISBN-92-835-1476-9	р 201 р 284	N85-17057 #
ISSN-0170-1339	p 239	N85-16838 #
ISSN-0170-1339	p 261	N85-16871 #
ISSN-0170-1339	p 262	N85-16872 #
ISSN-0170-1339	p 271	N85-16681 #
13314-0347-3694	p 256	N85-15220 #
ISSN-0721-5320	p 296	N85-16219 #
JPL-PUBL-84-62	p 242	N85-15701.* #
JPRS-UTR-85-001	p 204	N85-16763 #
KU-FRL-487-1	p 235	N85-15692 * #
L-15645	p 293	N85-16065 * #
L-15646	p 235	N85-15695 * #
L-15682	p 235	N85-15694 * #
L-15/23	p 276	N85-15755 #
L-15813	p 201	N85-16779 # 4
L-15827	D 278	N85-16883 #
L-15852	p 261	N85-16869 * #
LBF-FB-172/84	p 296	N85-16219 #
LIDS-FR-1418	p 303	N85-17603 * #
100 11 1001	- 000	NR5 16972 # #

F-2

REPORT NUMBER INDEX

	p 203	N85-16761 #
LR-29801 LR-30704 LR-30774	p 256 p 257 p 284	N85-15718 * # N85-16861 * # N85-17049 * #
MDC-J2990 MDC-J3527	р 294 р 294	N85-16087 # N85-16069 #
MIT-OSP-76265	p 303	N85-17603 * #
NA-84-1434	p 239	N85-16834 #
NADC-84015-60	p 243	N85-16842 #
NADC-84077-60	p 243 p 236	N85-15699 #
NAPC-PE-107C	p 284	N85-15922 #
NAS 1.15:77292 NAS 1.15:77467	p 295 p 298	N85-16180 * # N85-17363 * #
NAS 1.15:77510	p 278	N85-16882 * #
NAS 1.15:84302	p 255	N85-15716 * #
NAS 1.15:84583 NAS 1.15:84589	p 235	N85-15696 * #
NAS 1.15:84914	p 255	N85-15713 * #
NAS 1.15:85674 NAS 1.15:85905	p 235	N85-15695 * #
NAS 1.15:85916	p 265	N85-15729 * #
NAS 1.15:85920 NAS 1.15:86007	p 234	N85-15687 * #
NAS 1.15:86274	p 276	N85-15755 * #
NAS 1.15:86277 NAS 1.15:86336	p 278	N85-16883 * #
NAS 1.15:86350	p 258	N85-16862 #
NAS 1.15:86351	p 203	N85-12759 #
NAS 1.15:86356	p 234	N85-15691 * #
NAS 1.15:86672 NAS 1.15:86896	p 203 p 265	N85-16757 * #
NAS 1.15:86898	p 295	N85-16096 * #
NAS 1.15:86899	p 309 n 234	N85-17928 * #
NAS 1.15:86914	p 234	N85-15689 * #
NAS 1.15:86919 NAS 1.15:86920	p 276 p 276	N85-15757 * # N85-15758 * #
NAS 1.15:86925	p 242	N85-15702 * #
NAS 1.21:7037(182)	p 203 p 293	N85-16758 * # N85-15993 * #
NAS 1.26:166437	p 255	N85-15717 * #
NAS 1.26:169497	p 255 p 256	N85-15715 * # N85-15718 * #
NAS 1.26:171838	p 297	N85-17294 * #
NAS 1.26:172471	p 245 p 295	NOS-15/00 #
NAS 1.26:172483		No5-10090 #
NAS 1 26:172517	p 284	N85-17049 * #
NAS 1.26:172517	p 284 p 305 p 238	N85-17049 * # N85-17668 * # N85-16829 * #
NAS 1.26:172517 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271	p 284 p 305 p 238 p 265 p 242	N85-16096 # N85-17049 * # N85-17668 * # N85-16829 * # N85-15724 * #
NAS 1.26:172529	p 284 p 305 p 238 p 265 p 242 p 305	N85-16095 # N85-17668 * # N85-16829 * # N85-16829 * # N85-15724 * # N85-15701 * #
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174277 NAS 1.26:174279 NAS 1.26:174299	p 284 p 305 p 238 p 265 p 242 p 305 p 238 p 298	N85-16095 # N85-17668 * # N85-16629 * # N85-16629 * # N85-15724 * # N85-15721 * # N85-16625 * # N85-16625 * #
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174277 NAS 1.26:174279 NAS 1.26:174299 NAS 1.26:174299 NAS 1.26:174299	p 284 p 305 p 238 p 265 p 242 p 305 p 238 p 238 p 298 p 234	N85-17049 # N85-17668 # N85-17668 # N85-15724 # N85-15724 * N85-15701 * N85-16586 # N85-16586 # N85-16580 * N85-15690 * H85-15690 *
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174277 NAS 1.26:174279 NAS 1.26:174299 NAS 1.26:174299 NAS 1.26:174318 NAS 1.26:174318	p 284 p 305 p 238 p 265 p 242 p 305 p 238 p 238 p 298 p 234 p 303 p 268	N85-17049 # N85-17069 # N85-16629 # N85-15701 # N85-15701 * N85-16825 # N85-16825 # N85-16825 # N85-17603 * N85-17603 * M85-17603 *
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174277 NAS 1.26:174279 NAS 1.26:174279 NAS 1.26:174299 NAS 1.26:174318 NAS 1.26:174318 NAS 1.26:174320 NAS 1.26:177304-VOL-1 NAS 1.26:177304-VOL-2	p 284 p 305 p 238 p 265 p 242 p 305 p 238 p 298 p 234 p 303 p 268 p 271 p 271	N85-17049 # N85-17688 # N85-16829 * N85-15701 * N85-15701 * N85-16866 * N85-16865 * N85-16803 * N85-16803 * N85-16873 * N85-16877 * H85-16877 *
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174277 NAS 1.26:174279 NAS 1.26:174299 NAS 1.26:174299 NAS 1.26:174318 NAS 1.26:174318 NAS 1.26:174320 NAS 1.26:177304-VOL-1 NAS 1.26:177304-VOL-2 NAS 1.26:3840	p 284 p 305 p 238 p 265 p 242 p 305 p 238 p 238 p 238 p 238 p 238 p 239 p 234 p 303 p 268 p 271 p 271 p 255	N85-17049 # N85-17688 # N85-16629 # N85-15701 # N85-15701 # N85-16866 # N85-16805 # N85-15690 # N85-15697 # N85-16877 # N85-16878 #
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174277 NAS 1.26:174279 NAS 1.26:174299 NAS 1.26:174299 NAS 1.26:174318 NAS 1.26:174318 NAS 1.26:174320 NAS 1.26:177304-VOL-1 NAS 1.26:177304-VOL-2 NAS 1.26:3840 NAS 1.26:3841 NAS 1.26:3841	p 284 p 305 p 238 p 265 p 242 p 305 p 242 p 305 p 238 p 298 p 234 p 203 p 268 p 271 p 271 p 255 p 255 p 305	N85-17049 * N85-17049 * N85-17688 * N85-16829 * N85-16829 * N85-16868 * N85-16868 * N85-16868 * N85-16803 * N85-16873 * N85-16873 * N85-16878 * N85-16878 * N85-1687 *
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174277 NAS 1.26:174279 NAS 1.26:174293 NAS 1.26:174299 NAS 1.26:174299 NAS 1.26:174318 NAS 1.26:174318 NAS 1.26:177304-VOL-1 NAS 1.26:177304-VOL-2 NAS 1.26:3840 NAS 1.26:3841 NAS 1.26:3841 NAS 1.26:3847 NAS 1.26:3847	p 284 p 305 p 238 p 265 p 242 p 305 p 238 p 238 p 238 p 298 p 234 p 303 p 268 p 271 p 255 p 257 p 305 p 235	N85-17049 * N85-17049 * N85-17688 * N85-16829 * N85-16829 * N85-16868 * N85-16868 * N85-16868 * N85-16803 * N85-16873 * N85-16873 * N85-16878 * N85-16878 * N85-16878 * N85-16861 * N85-16892 *
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174277 NAS 1.26:174279 NAS 1.26:174299 NAS 1.26:174299 NAS 1.26:174318 NAS 1.26:174318 NAS 1.26:177304-VOL-1 NAS 1.26:177304-VOL-2 NAS 1.26:3840 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3844 NAS 1.26:3844 NAS 1.26:3844 NAS 1.26:3863 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:3864	p 284 p 305 p 238 p 265 p 242 p 305 p 238 p 238 p 238 p 238 p 238 p 233 p 268 p 271 p 257 p 257 p 257 p 257 p 257 p 205 p 235 p 235 p 235 p 235	N85-17049 * N85-17049 * N85-17688 * N85-16829 * N85-16829 * N85-16868 * N85-16868 * N85-16868 * N85-16803 * N85-16803 * N85-16873 * N85-16878 * N85-16878 * N85-16878 * N85-16877 * N85-16877 * N85-16695 *
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174277 NAS 1.26:174279 NAS 1.26:174299 NAS 1.26:174299 NAS 1.26:174318 NAS 1.26:174318 NAS 1.26:174318 NAS 1.26:174304-VOL-1 NAS 1.26:177304-VOL-1 NAS 1.26:3840 NAS 1.26:3840 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3863 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:3865 NAS 1.60:2213 NAS 1.60:2365	p 284 p 305 p 238 p 265 p 242 p 305 p 242 p 305 p 238 p 238 p 238 p 234 p 303 p 268 p 271 p 255 p 257 p 305 p 257 p 305 p 235 p 293 p 293 p 280	N85-17049 * N85-17049 * N85-17688 * N85-16829 * N85-16829 * N85-16828 * N85-16868 * N85-16808 * N85-16803 * N85-16803 * N85-16873 * N85-16873 * N85-16878 * N85-1687 * N85-1687 * N85-1687 * N85-1685 * N85-1685 * N85-1685 * N85-1685 * N85-1685 * N85-1685 *
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174277 NAS 1.26:174279 NAS 1.26:174299 NAS 1.26:174299 NAS 1.26:174299 NAS 1.26:174318 NAS 1.26:174304 NAS 1.26:174304 NAS 1.26:177304-VOL-1 NAS 1.26:3840 NAS 1.26:3841 NAS 1.26:3841 NAS 1.26:3842 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:285 NAS 1.60:2213 NAS 1.60:2385 NAS 1.60:2385	p 284 p 305 p 238 p 265 p 242 p 305 p 242 p 305 p 238 p 238 p 234 p 234 p 234 p 234 p 271 p 255 p 257 p 305 p 257 p 305 p 230 p 280 p 280 p 280 p 293 p 280 p 293 p 280 p 293 p 280 p 293 p 280 p 293 p 280 p 293 p 285 p 242 p 265 p 242 p 238 p 242 p 255 p 242 p 238 p 244 p 238 p 255 p 242 p 255 p 242 p 255 p 242 p 255 p 255 p 255 p 257 p 255 p 245 p 255 p 255 p 255 p 245 p 255 p 245 p 255 p 245 p 265 p 246 p 255 p 255 p 245 p 255 p 245 p 255 p 245 p 255 p 246 p 255 p 245 p 255 p 245 p 255 p 255 p 255 p 256 p 255 p 256 p 255 p 255 p 255 p 256 p 255 p 256 p 255 p 255 p 255 p 256 p 255 p 255 p 256 p 255 p 255	N85-17049 # N85-17049 # N85-17688 # N85-16829 # N85-16829 # N85-16828 # N85-16868 # N85-16803 # N85-16803 # N85-16873 # N85-16873 # N85-1687 # N85-1687 # N85-1687 # N85-1687 # N85-1687 # N85-1687 # N85-1686 # N85-1688 #
NAS 1,26:172529 NAS 1,26:172529 NAS 1,26:174246 NAS 1,26:174271 NAS 1,26:174277 NAS 1,26:174279 NAS 1,26:174279 NAS 1,26:174299 NAS 1,26:174299 NAS 1,26:174299 NAS 1,26:174318 NAS 1,26:174318 NAS 1,26:177304-VOL-1 NAS 1,26:177304-VOL-2 NAS 1,26:3840 NAS 1,26:3841 NAS 1,26:3847 NAS 1,26:3843 NAS 1,26:3864 NAS 1,26:3864 NAS 1,26:3864 NAS 1,26:3863 NAS 1,60:2365 NAS 1,60:2385 NAS 1,60:2385 NAS 1,60:2385 NAS 1,60:2385	p 284 p 305 p 238 p 265 p 242 p 305 p 248 p 238 p 298 p 298 p 238 p 298 p 234 p 303 p 268 p 271 p 257 p 257 p 257 p 305 p 257 p 305 p 257 p 305 p 242 p 305 p 258 p 257 p 205 p 257 p 257 p 257 p 257 p 257 p 257 p 235 p 257 p 257 p 235 p 257 p 235 p 257 p 257	N85-17049 # N85-17049 # N85-17688 # N85-16829 # N85-16829 # N85-16829 # N85-16868 # N85-16803 # N85-16803 # N85-16873 # N85-16873 # N85-16878 # N85-16878 # N85-16878 # N85-15892 # N85-16859 # N85-16868 # N85-16868 # N85-16869 #
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174271 NAS 1.26:174279 NAS 1.26:174279 NAS 1.26:174293 NAS 1.26:174318 NAS 1.26:174318 NAS 1.26:174318 NAS 1.26:177304-VOL-1 NAS 1.26:177304-VOL-2 NAS 1.26:3840 NAS 1.26:3841 NAS 1.26:3847 NAS 1.26:3847 NAS 1.26:3844 NAS 1.26:3843 NAS 1.26:3843 NAS 1.26:3843 NAS 1.26:385 NAS 1.60:2385 NAS 1.60:2385 NAS 1.60:2385 NAS 1.60:2385 NAS 1.60:2414 NAS 1.60:2424	p 284 p 305 p 238 p 265 p 242 p 305 p 242 p 303 p 238 p 238 p 238 p 238 p 234 p 233 p 268 p 271 p 255 p 257 p 305 p 235 p 235 p 280 p 281 p 293 p 281 p 295 p 295	N85-17049 # N85-17069 # N85-16629 # N85-16629 # N85-15701 # N85-15701 # N85-16805 # N85-16803 # N85-16803 # N85-16873 # N85-16873 # N85-16873 # N85-16861 # N85-16869 # N85-16668 # N85-16868 # N85-15693 # N85-16869 # N85-15693 # N85-16869 # N85-16809 # N85-16809 # N85-16809 # N85-16809 # N85-16809 # N85-16809 # N85-16809 # N85-16809 # N85-16809 #
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174271 NAS 1.26:174271 NAS 1.26:174279 NAS 1.26:174293 NAS 1.26:174299 NAS 1.26:174318 NAS 1.26:174304-VOL-1 NAS 1.26:177304-VOL-2 NAS 1.26:3840 NAS 1.26:3841 NAS 1.26:3843 NAS 1.26:3853 NAS 1.60:2385 NAS 1.60:2385 NAS 1.60:2424 NAS 1.60:2424	p 284 p 305 p 238 p 265 p 242 p 305 p 238 p 238 p 238 p 233 p 268 p 233 p 268 p 271 p 271 p 255 p 257 p 255 p 235 p 235 p 280 p 280 p 280 p 281 p 293 p 293	N85-10090 # N85-17069 # N85-17668 # N85-16629 # N85-16629 # N85-16626 # N85-16625 # N85-16673 # N85-16673 # N85-16673 # N85-16673 # N85-16673 # N85-16673 # N85-16676 # N85-16676 # N85-16690 # N85-16692 # N85-16692 # N85-16690 # N85-16688 # N85-16689 # N85-16689 # N85-16690 #
NAS 1,26:172529 NAS 1,26:172529 NAS 1,26:174246 NAS 1,26:174271 NAS 1,26:174271 NAS 1,26:174279 NAS 1,26:174293 NAS 1,26:174299 NAS 1,26:174299 NAS 1,26:174318 NAS 1,26:174318 NAS 1,26:17304-VOL-1 NAS 1,26:177304-VOL-2 NAS 1,26:3840 NAS 1,26:3841 NAS 1,26:3841 NAS 1,26:3841 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:385 NAS 1,26:385 NAS 1,26:385 NAS 1,26:385 NAS 1,26:385 NAS 1,26:385 NAS 1,26:2385 NAS 1,26:2385	p 284 p 305 p 238 p 265 p 242 p 305 p 238 p 238 p 238 p 233 p 268 p 233 p 271 p 271 p 271 p 271 p 271 p 271 p 271 p 271 p 235 p 235 p 235 p 265 p 235 p 235 p 265 p 235 p 235 p 235 p 255 p 235 p 235 p 255 p 235 p 235 p 255 p 235 p 255 p 235 p 255 p 235 p 255 p 235 p 255 p 235 p 255 p 255	N85-1049 # N85-17049 # N85-17688 # N85-16629 # N85-16629 # N85-1686 # N85-1686 # N85-16873 # N85-16873 # N85-16873 # N85-16873 # N85-16873 # N85-16878 # N85-16878 # N85-16878 # N85-16868 # N85-16869 # N85-16869 # N85-16877 # N85-16878 # N85-16878 # N85-16869 # N85-16869 # N85-16873 # N85-16868 # N85-16869 #
NAS 1,26:172517 NAS 1,26:172529 NAS 1,26:174246 NAS 1,26:174271 NAS 1,26:174271 NAS 1,26:174271 NAS 1,26:174279 NAS 1,26:174299 NAS 1,26:174299 NAS 1,26:174318 NAS 1,26:17304-VOL-1 NAS 1,26:177304-VOL-2 NAS 1,26:177304-VOL-2 NAS 1,26:3840 NAS 1,26:3841 NAS 1,26:3843 NAS 1,26:385 NAS 1,60:2385 NAS 1,60:2424 NAS 1,60:2424 NAS 1,60:2424 NAS 1,60:2424 NASA-CR-166437 NASA-CR-166437	p 284 p 305 p 238 p 265 p 242 p 305 p 265 p 238 p 238 p 238 p 238 p 233 p 268 p 271 p 271 p 271 p 271 p 271 p 271 p 271 p 271 p 235 p 235 p 280 p 280 p 280 p 280 p 280 p 285 p 285 p 285 p 295 p 255 p 255	N85-10049 # N85-17049 # N85-17688 # N85-16629 # N85-16629 # N85-16626 # N85-16868 # N85-16873 # N85-16873 # N85-16873 # N85-16873 # N85-16873 # N85-16878 # N85-16878 # N85-16868 # N85-16869 # N85-16868 # N85-16868 # N85-16868 # N85-16868 # N85-16868 # N85-16868 # N85-16869 # N85-16869 # N85-16869 # N85-1693 # N85-16100 #
NAS 1,26:172529 NAS 1,26:172529 NAS 1,26:174246 NAS 1,26:174271 NAS 1,26:174271 NAS 1,26:174279 NAS 1,26:174293 NAS 1,26:174299 NAS 1,26:174318 NAS 1,26:174318 NAS 1,26:174318 NAS 1,26:177304-VOL-1 NAS 1,26:177304-VOL-2 NAS 1,26:3840 NAS 1,26:3841 NAS 1,26:3841 NAS 1,26:3847 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:3843 NAS 1,26:385 NAS 1,60:2385 NAS 1,60:2424 NASA-CR-166437 NASA-CR-166497 NASA-CR-166497 NASA-CR-171839 NASA-CR-171838 ADD	p 284 p 305 p 238 p 238 p 265 p 305 p 242 p 305 p 235 p 238 p 238 p 238 p 238 p 238 p 238 p 233 p 257 p 255 p 235 p 235 p 280 p 280 p 280 p 280 p 280 p 280 p 285 p 235 p 285 p 235 p 255 p 235 p 285 p 235 p 235 p 255 p 235 p 255 p 235 p 255 p 235 p 265 p 235 p 235 p 235 p 235 p 235 p 235 p 235 p 257 p 235 p 255 p 255 p 235 p 255 p 256 p 256	N85-17049 * N85-17049 * N85-17688 * N85-17689 * N85-15701 * N85-15701 * N85-15701 * N85-16860 * N85-16873 * N85-16873 * N85-16873 * N85-16878 * N85-16878 * N85-16878 * N85-16878 * N85-16878 * N85-16869 * N85-16693 * N85-16693 * N85-16693 * N85-16693 * N85-16693 * N85-16693 * N85-16693 * N85-16778 * N85-15778 * N85-15718 * N85-15718 * N85-1778 *
NAS 1,26:172529 NAS 1,26:172529 NAS 1,26:174246 NAS 1,26:174271 NAS 1,26:174279 NAS 1,26:174279 NAS 1,26:174299 NAS 1,26:174299 NAS 1,26:174318 NAS 1,26:174318 NAS 1,26:177304-VOL-1 NAS 1,26:177304-VOL-2 NAS 1,26:177304-VOL-2 NAS 1,26:3840 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3848 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:385 NAS 1,60:2365 NAS 1,60:2385 NAS 1,60:2385 N	p 284 p 305 p 238 p 238 p 265 p 305 p 238 p 2398 p 2398 p 233 p 268 p 233 p 271 p 255 p 235 p 2305 p 2305 p 280 p 280 p 280 p 280 p 280 p 235 p 280 p 280 p 285 p 286 p 286 p 297 p 285 p 285 p 286 p 297 p 285 p 285 p 286 p 297 p 285 p 295 p 285 p 295 p 285 p 286 p 295 p 295 p 286 p 295 p 295	N85-17049 * N85-17049 * N85-17049 * N85-17688 * N85-15701 * N85-15701 * N85-15701 * N85-16860 * N85-16803 * N85-16803 * N85-16873 * N85-16873 * N85-16878 * N85-16878 * N85-16878 * N85-16878 * N85-16869 * N85-16692 * N85-16692 * N85-16693 * N85-15718 *
NAS 1,26:172529 NAS 1,26:172529 NAS 1,26:174246 NAS 1,26:174271 NAS 1,26:174279 NAS 1,26:174279 NAS 1,26:174299 NAS 1,26:174299 NAS 1,26:174318 NAS 1,26:174318 NAS 1,26:174304 VOL-1 NAS 1,26:174304 VOL-2 NAS 1,26:3840 NAS 1,26:3840 NAS 1,26:3841 NAS 1,26:3841 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3864 NAS 1,26:3864 NAS 1,26:385 NAS 1,60:2365 NAS 1,60:2385 NAS 1,60:2424 NASA-CR-166437 NASA-CR-166497 NASA-CR-169497 NASA-CR-172483 NASA-CR-172483 NASA-CR-172483 NASA-CR-172483 NASA-CR-172483	$ p \ 284 \\ p \ 305 \\ p \ 238 \\ p \ 238 \\ p \ 265 \\ p \ 305 \\ p \ 305 \\ p \ 238 \\ p \ 265 \\ p \ 305 \\ p \ 305 \\ p \ 238 \\ p \ 271 \\ p \ 255 \\ p \ 235 \\ p \ 255 \\ p \$	N85-17049 * N85-17049 * N85-17688 * N85-17689 * N85-15701 * N85-15701 * N85-15701 * N85-16800 * N85-16800 * N85-16803 * N85-16873 * N85-16873 * N85-16878 * N85-16878 * N85-16878 * N85-16869 * N85-16665 * N85-16665 * N85-16665 * N85-16669 * N85-16669 * N85-16669 * N85-16669 * N85-16669 * N85-16669 * N85-16669 * N85-15718 * N85-15717 * N85-15717 * N85-15717 * N85-15717 * N85-15717 * N85-15717 * N85-15718 * N85-15718 * N85-15718 * N85-15706 * N85-15708 * N85-17706 *
NAS 1,26:172529 NAS 1,26:172529 NAS 1,26:174246 NAS 1,26:174271 NAS 1,26:174279 NAS 1,26:174279 NAS 1,26:174299 NAS 1,26:174299 NAS 1,26:174318 NAS 1,26:174318 NAS 1,26:174304 NAS 1,26:174304 NAS 1,26:174304 NAS 1,26:174304 NAS 1,26:3840 NAS 1,26:3840 NAS 1,26:3841 NAS 1,26:3841 NAS 1,26:3847 NAS 1,26:3864 NAS 1,26:3864 NAS 1,26:3864 NAS 1,26:385 NAS 1,2	p 284 p 305 p 238 p 238 p 265 p 238 p 238 p 239 p 239 p 239 p 239 p 230 p 271 p 255 p 2305 p 2308 p 238 p 238 p 238 p 239 p 255 p 2305 p 2355 p 2355	N85-17049 * N85-17049 * N85-17688 * N85-16829 * N85-16829 * N85-16829 * N85-16826 * N85-16803 * N85-16803 * N85-16803 * N85-16873 * N85-16873 * N85-16878 * N85-16878 * N85-16878 * N85-16878 * N85-16878 * N85-16869 * N85-16869 * N85-16869 * N85-16869 * N85-15718 * N85-15715 * N85-15715 * N85-15715 * N85-15716 * N85-15706 * N85-15706 * N85-16088 * N85-16088 * N85-1608 * N85-1628 * N85
NAS 1,26:172529 NAS 1,26:172529 NAS 1,26:174246 NAS 1,26:174271 NAS 1,26:174279 NAS 1,26:174279 NAS 1,26:174293 NAS 1,26:174299 NAS 1,26:174318 NAS 1,26:174320 NAS 1,26:174304 VOL-1 NAS 1,26:174304 VOL-2 NAS 1,26:3840 NAS 1,26:3840 NAS 1,26:3840 NAS 1,26:3841 NAS 1,26:3847 NAS 1,26:3847 NAS 1,26:3864 NAS 1,26:3864 NAS 1,26:3864 NAS 1,26:385 NAS 1,60:2385 NAS 1,60:2424 NASA-CR-166437 NASA-CR-166437 NASA-CR-166437 NASA-CR-172338-ADD NASA-CR-172338 NASA-CR-172471 NASA-CR-172471 NASA-CR-172471 NASA-CR-17246 NASA-CR-17246 NASA-CR-174271	p 284 p 2305 p 238 p 2265 p 238 p 265 p 238 p 238 p 238 p 2398 p 2398 p 2398 p 2398 p 2398 p 2305 p 2355 p	N85-17049 * N85-17049 * N85-17688 * N85-16829 * N85-16829 * N85-16829 * N85-16826 * N85-16825 * N85-16803 * N85-16803 * N85-16873 * N85-16877 * N85-16878 * N85-16878 * N85-16878 * N85-16878 * N85-16878 * N85-16878 * N85-16869 * N85-16869 * N85-16869 * N85-16869 * N85-15718 * N85-15706 * N85-15
NAS 1.26:172529 NAS 1.26:172529 NAS 1.26:174246 NAS 1.26:174271 NAS 1.26:174279 NAS 1.26:174279 NAS 1.26:174299 NAS 1.26:174299 NAS 1.26:174318 NAS 1.26:174304 NAS 1.26:174304 NAS 1.26:174304 NAS 1.26:174304 NAS 1.26:174304 NAS 1.26:3840 NAS 1.26:3840 NAS 1.26:3841 NAS 1.26:3841 NAS 1.26:3847 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:3864 NAS 1.26:385 NAS 1.60:2385 NAS 1.60:2424 NASA-CR-166043 NASA-CR-166043 NASA-CR-1766043 NASA-CR-17283 NASA-CR-17283 NASA-CR-17283 NASA-CR-17283 NASA-CR-17283 NASA-CR-17283 NASA-CR-17287 NASA-CR-17287 NASA-CR-17287 NASA-CR-174271 NASA-CR-174271 NASA-CR-174271 NASA-CR-174271 NASA-CR-174271 NASA-CR-174271 NASA-CR-174271 NASA-CR-174271 NASA-CR-174271 NASA-CR-174277	$ p \ 284 \\ p \ 305 \\ p \ 238 \\ p \ 238 \\ p \ 265 \\ p \ 238 \\ p \ 265 \\ p \ 305 \\ p \ 238 \\ p \ 235 \\ p \$	N85-17049 * N85-17049 * N85-17688 * N85-16829 * N85-16829 * N85-16829 * N85-16826 * N85-16825 * N85-16803 * N85-16803 * N85-16873 * N85-16877 * N85-16877 * N85-16877 * N85-16877 * N85-16878 * N85-16869 * N85-16869 * N85-16869 * N85-16869 * N85-16869 * N85-15714 * N85-16869 * N85-16869 * N85-15717 * N85-15717 * N85-15716 * N85-15716 * N85-15716 * N85-15716 * N85-15716 * N85-15716 * N85-15716 * N85-15716 * N85-15706 * N85-15706 * N85-15706 * N85-15706 * N85-15706 * N85-15706 * N85-15706 * N85-15706 * N85-15706 * N85-15701 * N85-15701 * N85-15701 * N85-15701 * N85-15701 * N85-15701 *

NASA-UR-1/4293	p 200	1100-17000 #
NASA-CR-174299	p 234	N85-15690 * #
NASA-CR-174318	p 303	N85-17603 * #
NASA-CB-174320	n 268	N85-16873 * #
NASA CR 177204 VOL 1	0 271	NO5 10077 * #
NASA-OR-177304-VOL-1	p 271	N05-10077 #
NASA-CH-1//304-VOL-2	p 2/1	N85-168/8 * #
NASA-CR-3840	p 255	N85-15714 * #
NASA-CR-3841	p 257	N85-16861 * #
NASA-CR-3847	o 305	N85-17667 * #
NASA-CR-3863	p 235	N85-15692 * #
NASA-CR-3864	n 305	N85-16590 * #
	p 000	
NASA-SP-7037(182)	n 203	N85-16758 * #
	p 200	100-10/00 #
NASA.TM.77202	n 205	N85-16180 * #
NASA-TM-77467	p 200	N85.17262 * #
NASA-TM-77510	n 278	N85.16882 * #
NASA-TM-92748	200	N95 15859 * #
NASA-TM-84202	0 255	N85-15716 * #
NASA-TM-94583	n 235	N85-15696 * #
NASA-TM-84589	0 225	N95 15607 * #
NASA-TM-84914	n 255	N85-15713 * #
NASA-TM-85674	0 235	N85-15695 * #
NASA TH 05074	n 270	NO5-15035 #
VASA TM 95012	- 265	N95 15730 * #
NASA-TM-85810	p 200	N95 15697 * #
NASA TM 86007	p 204	N95 16926 * #
NASA THA 00074	p 230	NOS-10020 #
NASA TM 06077	p 270	N95 10000 * #
NASA TM 96226	p 200	N95 17740 * #
MASA TH 00050	p 309	NOS-17740 #
NASA-TM-80350	p 256	N05-10602 #
NASA-IM-86351	p 203	N85-16/59 #
NASA-IM-86353	p 284	N85-17048 #
NASA-1M-86356	p 234	N85-15691 #
NASA-IM-866/2	p 203	N85-16/5/ #
NASA-IM-86896	p 265	N85-15/25 #
NASA-IM-86898	p 295	N85-16096 #
NASA-IM-86899	p 309	N85-17928 #
NASA-1M-86912	p 234	N85-15688 #
NASA-1M-86914	p 234	N85-15689 #
NASA-IM-86919	p 276	N85-15/5/ #
NASA-1M-86920	p 276	N85-15758 #
NASA-1M-86925	p 242	N85-15/02 * #
NASA-1P-2213	p 293	N85-16065 #
NASA-TP-2365	p 280	N85-15//8 * #
NASA-1P-2383	p 261	N85-16868 * #
NASA-TP-2385	p 235	N85-15694 #
NASA-1P-2386	p 261	N85-16869 #
NASA-1P-2414	p 235	N00-10093 #
NASA-TP-2414	p 235 p 295	N85-16100 * #
NASA-TP-2414	p 235 p 295	N85-16100 * #
NASA-TP-2414	p 235 p 295 p 239	N85-16832 #
NASA-1P-2414	p 235 p 295 p 239	N85-16832 #
NASA-17-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U	p 235 p 295 p 239 p 239	N85-16832 # N85-16832 # N85-17398 #
NASA-1F-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U	p 235 p 295 p 239 p 239 p 298	N85-16832 # N85-16832 # N85-17398 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204	p 235 p 295 p 239 p 239 p 298 p 239	N85-16832 # N85-16832 # N85-17398 # N85-16835 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U	p 235 p 295 p 239 p 239 p 298 p 239	N85-16832 # N85-16832 # N85-17398 # N85-16835 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN	p 235 p 295 p 239 p 239 p 298 p 239 p 239 p 278	N85-16832 # N85-16832 # N85-17398 # N85-16835 # N85-16882 * #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 DNERA-RT-5/3568-EN	p 235 p 295 p 239 p 298 p 298 p 239 p 239 p 278	N85-16832 # N85-16832 # N85-17398 # N85-16835 # N85-16882 * #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146	p 235 p 295 p 239 p 298 p 298 p 239 p 239 p 278 p 278 p 204	N85-16832 # N85-16832 # N85-16835 # N85-16835 # N85-16832 * A85-19260 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 DNERA-RT-5/3568-EN DNERA, TP NO. 1984-146 DNERA, TP NO. 1984-148	p 235 p 295 p 239 p 298 p 298 p 239 p 239 p 278 p 204 p 205	N85-16832 # N85-16832 # N85-16835 # N85-16835 # N85-16882 * # A85-19260 # A85-19262 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NSWC/TR-83066-U ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-149	p 235 p 295 p 239 p 298 p 239 p 239 p 239 p 239 p 278 p 204 p 205 p 205	N85-16303 # N85-16100 * N85-16832 # N85-17398 # N85-16835 # N85-16882 * A85-19260 # A85-19263 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150	p 235 p 295 p 239 p 298 p 298 p 239 p 239 p 239 p 278 p 204 p 205 p 205 p 205	N85-15093 # N85-16100 # N85-16832 # N85-16835 # N85-16835 # N85-16832 * A85-19260 # A85-19263 # A85-19264 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-149 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155	p 235 p 295 p 239 p 298 p 298 p 239 p 239 p 239 p 278 p 204 p 205 p 205 p 205 p 205 p 303	N85-16100 * # N85-16100 * # N85-16832 # N85-16832 # N85-16835 # N85-16882 * # A85-19260 # A85-19262 # A85-19264 # A85-19269 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 NSWC/TR-84-204 ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-149 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155	p 235 p 295 p 239 p 239 p 298 p 239 p 239 p 239 p 239 p 278 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 205	N85-16100 * # N85-16100 * # N85-16832 # N85-17398 # N85-16835 # N85-16835 # N85-16882 * # A85-19260 # A85-19263 # A85-19264 # A85-19269 # A85-19269 # A85-19269 # A85-19269 # A85-19269 # A85-19270 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157	p 235 p 295 p 239 p 239 p 239 p 239 p 239 p 278 p 204 p 205 p 205 p 205 p 303 p 272 p 272	N85-15093 # N85-16100 # N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19260 # A85-19264 # A85-19264 # A85-19269 # A85-19270 # A85-19271 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA.TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-149 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-157	p 235 p 295 p 239 p 239 p 239 p 239 p 239 p 278 p 204 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 239	N85-16100 * # N85-16100 * # N85-16832 # N85-16832 # N85-16835 # N85-16882 * # A85-19260 # A85-19263 # A85-19264 # A85-1927 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158	p 235 p 295 p 239 p 239 p 239 p 239 p 239 p 278 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 272 p 272	N85-16100 * # N85-16100 * # N85-16832 # N85-16832 # N85-16835 # N85-16882 * # A85-19260 # A85-19264 # A85-19269 # A85-19269 # A85-19267 # A85-19269 # A85-19269 # A85-19270 # A85-19271 # A85-19272 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-149 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158	p 235 p 295 p 297 p 239 p 204 p 205 p 272 p 205 p 272 p 272 p 272 p 272 p 272 p 272 p 205 p 272 p 272	N85-15093 # N85-16100 * N85-16100 * N85-16832 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19263 # A85-19264 # A85-19265 # A85-19264 # A85-19270 # A85-19271 # A85-19272 # N85-17152 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158	p 235 p 295 p 297 p 298 p 298 p 298 p 298 p 298 p 298 p 204 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 272 p 272 p 272 p 272 p 278	N85-16100 * # N85-16100 * # N85-16832 # N85-16832 # N85-16835 # N85-16882 * # A85-19260 # A85-19263 # A85-19264 # A85-19264 # A85-19264 # A85-19264 # A85-19264 # A85-19264 # A85-1927 # A85-1927 # N85-16875 #
VRSA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-156 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158	p 235 p 295 p 239 p 238 p 238 p 238 p 238 p 278 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 272 p 272 p 272 p 272 p 272 p 285 p 268	N85-16100 * # N85-16100 * # N85-16832 # N85-16832 # N85-16835 # N85-16882 * # A85-19260 # A85-19262 # A85-19263 # A85-19264 # A85-19269 # A85-19267 # A85-19267 # A85-1927 # A85-1927 # N85-17152 # N85-16875 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158	p 235 p 295 p 297 p 298 p 298 p 298 p 298 p 278 p 204 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 272 p 272 p 272 p 272 p 278	N85-15093 # N85-16100 * N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19263 # A85-19264 # A85-19270 # A85-19271 # A85-19272 # N85-17152 # N85-17353 *
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 DNERA, TP NO. 1984-158	p 235 p 295 p 295 p 239 p 298 p 298 p 298 p 278 p 204 p 205 p 205 p 205 p 205 p 205 p 272 p 272 p 272 p 272 p 278 p 298 g 298 g 298	N85-16003 # N85-16100 * N85-16632 # N85-16832 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19264 # A85-19264 # A85-19264 # A85-19264 # A85-19271 # A85-19272 # N85-17152 # N85-17353 # N85-17353 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-149 ONERA, TP NO. 1984-149 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158	p 235 p 295 p 239 p 298 p 298 p 298 p 205 p 208 p 298 p 298 p 298 p 298	N85-16100 * # N85-16100 * # N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19272 # N85-17353 * # N85-17353 * # N85-15922 #
VRSA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA/GPD/EB 17952	p 235 p 295 p 239 p 204 p 205 p 205 p 205 p 205 p 205 p 209 p 200 p 202 p 200 p 200 p 202 p 202	N85-16100 * # N85-16100 * # N85-16832 # N85-16832 # N85-16835 # N85-16882 * # A85-19260 # A85-19262 # A85-19263 # A85-19264 # A85-19267 # A85-19267 # A85-19267 # A85-19271 # A85-19272 # N85-16875 # N85-16875 # N85-15922 # N85-15922 # N85-15924 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA/GPD/FR-17952	p 235 p 295 p 239 p 205 p 205 p 205 p 205 p 205 p 272 p 272 p 272 p 272 p 272 p 278 p 278 p 204 p 204 p 205 p 204 p 204 p 204 p 205 p 209 p 200 p 200 p 200 p 200 p 200 p 200 p 200 p 202 p 202	N85-15093 # N85-16100 * N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19263 # A85-19264 # A85-19270 # A85-19271 # A85-19272 # N85-17152 # N85-17353 * N85-15922 # N85-15731 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA/GPD/FR-17952 RADC-TR-84-53-VOL-2	p 235 p 295 p 239 p 204 p 205 p 205 p 205 p 205 p 205 p 272 p 265 p 265 p 272 p 272 p 272 p 265 p 265 p 265 p 272 p 272 p 272 p 268 p 272 p 268 p 272 p 268 p 272 p 268 p 272 p 268 p 272 p 272 p 258 p 268 p 272 p 258 p 272 p 258 p 258	N85-15093 # N85-16100 * N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19264 # A85-19264 # A85-19271 # A85-19272 # N85-17152 # N85-17333 * N85-17533 # N85-15731 # N85-17578 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-150 ONER	p 235 p 295 p 239 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 208 p 229 p 205 p 205	N85-15093 # N85-16100 * N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # N85-17353 # N85-17353 * N85-15731 # N85-15731 # N85-15737 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-149 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-159 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-150 ONER	p 235 p 295 p 239 p 205 p 205 p 205 p 205 p 205 p 205 p 239 p 239	N85-16000 # N85-16100 * N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19265 # A85-19264 # A85-19270 # A85-19271 # A85-19272 # N85-16875 # N85-15922 # N85-15922 # N85-15731 # N85-15737 # N85-16870 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-156 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA/GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TM-SPACE-327	p 235 p 295 p 239 p 205 p 205 p 205 p 205 p 205 p 207 p 272 p 272 p 272 p 272 p 278 p 278 p 204 p 205 p 204 p 205 p 204 p 205 p 204 p 205 p 204 p 205 p 204 p 205 p 205	N85-15093 # N85-16100 * N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19260 # A85-19264 # A85-19264 # A85-19270 # A85-19271 # A85-19272 # N85-17152 # N85-16875 # N85-15932 # N85-15731 # N85-15737 # N85-16870 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA-FR-17658 PWA/GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TM-SPACE-327 RAE-TRANS-2120	p 235 p 295 p 239 p 255 p 205 p 272 p 275 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 272 p 272 p 272 p 272 p 272 p 272 p 272 p 268 p 208 p 203 p 272 p 268 p 203 p 268 p 203 p 269 p 203 p 250 p 255 p 255	N85-16100 # N85-16600 # N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19264 # A85-19264 # A85-19264 # A85-19271 # A85-19272 # N85-17152 # N85-17353 * N85-17353 * N85-17573 # N85-17578 # N85-16870 # N85-16870 # N85-15712 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA/GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TR-84-53-VOL-2 RAE-TR-84-53-VOL-2 RAE-TR-84-53-VOL-2	p 235 p 295 p 239 p 205 p 205 p 205 p 205 p 205 p 205 p 205 p 209 p 205 p 205	N85-15093 # N85-16100 * N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # N85-17352 # N85-15731 # N85-15731 # N85-15731 # N85-15732 # N85-15712 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA/GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TR-SPACE-327 RAE-TR-SPACE-327 RAE-TRANS-2120 RAND/N-2163-AF	p 235 p 295 p 239 p 205 p 205 p 205 p 205 p 205 p 272 p 272 p 272 p 272 p 272 p 278 p 239 p 204 p 204 p 205 p 204 p 205 p 204 p 204 p 205 p 204 p 204 p 205 p 205	N85-16600 # N85-16600 # N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19263 # A85-19264 # A85-19270 # A85-19271 # A85-19272 # N85-15927 # N85-15922 # N85-15932 # N85-15731 # N85-15731 # N85-16870 # N85-16870 # N85-16870 # N85-16870 # N85-16685 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-157 ONER	p 235 p 295 p 239 p 205 p 205 p 205 p 205 p 207 p 272 p 272 p 272 p 278 p 278 p 208 p 209 p 200 p 200 p 200 p 200 p 200 p 200 p 202 p 203 p 202 p 203 p 202 p 203 p 203	N85-16600 # N85-16600 # N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19260 # A85-19260 # A85-19264 # A85-19270 # A85-19271 # A85-19272 # N85-17152 # N85-16875 # N85-15922 # N85-15733 # N85-15731 # N85-16870 # N85-16870 # N85-16870 # N85-16870 # N85-16870 # N85-16875 # N85-16855 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA/GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TM-SPACE-327 RAE-TRANS-2120 RAND/R-3093-MIL	p 235 p 295 p 239 p 204 p 205 p 272 p 272 p 272 p 272 p 278 p 278 p 278 p 278 p 279 p 272 p 272 p 278 p 278 p 205 p 272 p 272 p 272 p 278 p 205 p 272 p 272 p 275 p 206 p 272 p 205 p 272 p 272 p 275 p 206 p 272 p 205 p 272 p 272 p 275 p 203 p 272 p 276 p 205 p 272 p 272 p 276 p 205 p 272 p 272 p 275 p 203 p 272 p 276 p 205 p 203 p 272 p 272 p 275 p 203 p 272 p 205 p 203 p 272 p 205 p 203 p 272 p 205 p 203 p 272 p 205 p 203 p 205 p 203 p 205 p 203 p 205 p 203 p 205 p 203 p 205 p 203 p 205 p 205	N85-16600 # N85-16600 # N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19271 # N85-17152 # N85-17333 * N85-15731 # N85-15732 # N85-16870 # N85-15712 # N85-15712 # N85-16667 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-149 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-159 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-150 ONER	p 235 p 295 p 239 p 205 p 205 p 205 p 268 p 284 p 286 p 284 p 286 p 298 p 284 p 266 p 298 p 284 p 266 p 203 p 261 p 255 p 308 p 261 p 261 p 268 p 298 p 298 p 204 p 205 p 303 p 261 p 206 p 205 p 303 p 261 p 206 p 303 p 266 p 303 p 261 p 303 p 261 p 303 p 303 p 308 p 303 p 308 p 308 p 308 p 303 p 308 p 308 p 303 p 308 p 308 p 308 p 308 p 308 p 303 p 308 p 308	N85-16603 # N85-16100 * N85-16602 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19267 # A85-19271 # A85-19272 # N85-16875 # N85-15922 # N85-15922 # N85-15731 # N85-15737 # N85-16870 # N85-166870 # N85-16685 # N85-16667 # N85-16667 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-156 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA/GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TM-SPACE-327 RAE-TR-SPACE-327 RAE-TRANS-2120 RAND/R-2163-AF RAND/R-3093-MIL REPT-61270-10	p 235 p 295 p 239 p 205 p 205 p 205 p 205 p 205 p 207 p 272 p 272 p 272 p 272 p 278 p 278 p 208 p 209 p 200 p 200	N85-16600 # N85-16600 # N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19260 # A85-19264 # A85-19270 # A85-19271 # A85-19271 # A85-19271 # A85-19271 # N85-17152 # N85-15922 # N85-15733 # N85-15733 # N85-15731 # N85-16870 # N85-16870 # N85-16685 # N85-16685 # N85-16685 # N85-16685 # N85-16698 *
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA-GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TM-SPACE-327 RAE-TRANS-2120 RAND/N-2163-AF RAND/R-3093-MIL REPT-61270-10	p 235 p 295 p 239 p 204 p 205 p 205	N85-16093 # N85-16100 * N85-16632 # N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19271 # A85-19272 # N85-17333 # N85-17333 # N85-15731 # N85-16870 # N85-16670 # N85-16667 # N85-16098 # N85-16098 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-149 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-150 ONER	p 235 p 295 p 239 p 205 p 205 p 268 p 284 p 284 p 265 p 261 p 265 p 261 p 265 p 303 p 261 p 255 p 308 p 308 p 295 p 206	N85-16603 # N85-16100 * N85-16602 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19265 # A85-19264 # A85-19265 # A85-19270 # A85-19270 # A85-19271 # A85-19272 # N85-15922 # N85-15922 # N85-15922 # N85-16870 # N85-166870 # N85-16685 # N85-16667 # N85-16698 # N85-16698 # N85-16685 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-156 ONERA, TP NO. 1984-156 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90226 PTR-84-33 PWA-FR-17658 PWA/GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TM-SPACE-327 RAE-TRANS-2120 RAND/N-2163-AF RAND/R-3093-MIL REPT-61270-10 RSRE-MEMO-3714	p 235 p 295 p 239 p 205 p 205 p 205 p 205 p 205 p 207 p 272 p 272 p 272 p 278 p 288 p 298 p 298 p 298 p 298 p 298 p 298 p 298 p 298 p 278 p 204 p 205 p 303 p 261 p 265 p 303 p 255 p 308 p 208 p 209 p 200 p 200	N85-16003 # N85-16100 * N85-16603 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19264 # A85-19264 # A85-19264 # A85-19270 # A85-19271 # A85-19272 # N85-17152 # N85-15922 # N85-15733 # N85-15731 # N85-16870 # N85-16870 # N85-16687 # N85-16685 # N85-16667 # N85-16693 # N85-16653 #
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA-GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TM-SPACE-327 RAE-TRANS-2120 RAND/N-2163-AF RAND/N-2163-AF RAND/N-2163-AF RAND/R-3093-MIL REPT-61270-10 RSRE-MEMO-3714	p 235 p 295 p 239 p 239 p 239 p 239 p 239 p 239 p 239 p 239 p 235 p 235 p 205 p 205	N85-16000 # N85-16100 * N85-16632 # N85-16832 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19271 # A85-19272 # N85-17353 # N85-17353 # N85-17578 # N85-16870 # N85-16685 # N85-16667 # N85-16685 # N85-16098 * N85-16093 # N85-16093 # N85-16093 # N85-16093 # N8
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-149 ONERA, TP NO. 1984-150 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-156 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA/GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TM-SPACE-327 RAE-TR-SPACE-327 R	p 235 p 295 p 239 p 205 p 205 p 268 p 284 p 265 p 268 p 284 p 265 p 303 p 261 p 255 p 308 p 308 p 308 p 295 p 308 p 295	N85-16603 # N85-16100 * N85-16602 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19263 # A85-19264 # A85-19267 # A85-19271 # A85-19272 # N85-15922 # N85-15922 # N85-15731 # N85-15731 # N85-15732 # N85-16670 # N85-16685 # N85-16667 # N85-16698 # N85-16693 # N85-16693 # N85-16693 # N85-16693 # N85-16693 # N85-15706 *
NASA-TP-2414 NASA-TP-2424 NEAR-TR-321 NLR-MP-83066-U NSWC/TR-84-204 ONERA-RT-5/3568-EN ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-146 ONERA, TP NO. 1984-148 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-155 ONERA, TP NO. 1984-156 ONERA, TP NO. 1984-157 ONERA, TP NO. 1984-158 PNR-90222 PNR-90226 PTR-84-3 PWA-FR-17658 PWA/GPD/FR-17952 RADC-TR-84-53-VOL-2 RAE-TM-SPACE-327 RAE-TRANS-2120 RAND/N-2163-AF RAND/R-3093-MIL REPT-61270-10 RSRE-MEMO-3714 RTI/2467 S-HRG-98-856	p 235 p 295 p 239 p 205 p 205 p 205 p 205 p 205 p 205 p 207 p 272 p 272 p 272 p 272 p 278 p 278 p 204 p 205 p 204 p 205 p 208 p 298 p 298 p 298 p 278 p 204 p 205 p 205	N85-16000 # N85-16100 * N85-16600 # N85-16835 # N85-16835 # N85-16835 # N85-16835 # A85-19260 # A85-19260 # A85-19264 # A85-19265 # A85-19264 # A85-19270 # A85-19271 # N85-15922 # N85-15733 # N85-16870 # N85-166870 # N85-166851 # N85-166667 # N85-166853 # N85-166853 # N85-16853 # N85-16853 # N85-16853 #

USAAVSCOM-TR-84-C-12

SPC-789	p 255	N85-15717 * #
SRA-R84-910004-1	p 294	N85-16070 #
STI-TR-1194-1-1	D 271	N85-16877 * #
STI-TR-1194-1-2	p 271	N85-16878 * #
SU-CRC-TR-84-14	p 301	A85-21973 *#
S8308-R1	p 297	N85-17294 * #
TM-84-A-7	p 238	N85-16826 * #
US-PATENT-APPL-SN-320893	p 254	N85-15710 #
US-PATENT-APPL-SN-339204	p 255	N85-15711 #
US-PATENT-APPL-SN-411946	n 293	N85-15940 #
US-PATENT-APPL-SN-422429	0 295	N85-16156 #
US-PATENT-APPL-SN-431435	0 265	N85-15723 #
US-PATENT-APPL-SN-437092	n 276	N85-15754 #
US-PATENT-APPL-SN-449922	n 259	N85-15721 #
US-PATENT-APPL-SN-465230	n 242	N85-15700 #
US-PATENT-APPL-SN-504183	n 203	N85_15041 #
US-PATENT-APPI -SN-519421	n 277	N95-15761 #
US-PATENT-APPL-SN-582412	n 300	N85-17506 #
US-PATENT APPL SN 651083	n 285	N85-17077 #
LIS_PATENT_APPL_SN_661834	n 209	N95 17260 #
001 ATERIA T CON-001004	h 590	1103-17303 #
US-PATENT-CLASS-244-223	p 259	N85-15721 #
US-PATENT-CLASS-297-406	n 254	N85-15710 #
US-PATENT-CLASS-356-359	0 295	N85-16156 #
US-PATENT-CLASS-361-328	p 293	N85-15941 #
US-PATENT-CLASS-364-433	p 255	N85-15711 #
US-PATENT-CLASS-415-138	n 265	N85-15723 #
US-PATENT-CLASS-428-109	n 276	N85-15754 #
US-PATENT-CLASS-89-1A	n 293	N85-15940 #
	p 200	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
US-PATENT-4,404,244	p 276	N85-15754 #
US-PATENT-4,464,702	p 293	N85-15941 #
US-PATENT-4,465,250	p 242	N85-15700 #
US-PATENT-4,465,372	ρ 295	N85-16156 #
US-PATENT-4,466,662	p 254	N85-15710 #
US-PATENT-4,467,429	p 255	N85-15711 #
US-PATENT-4,471.683	p 293	N85-15940 #
US-PATENT-4,477.043	p 259	N85-15721 #
US-PATENT-4,477,222	p 265	N85-15723 #
USAAFFA-82-15-1	n 256	N95_15710 #
USAAFFA-84-02	n 259	N85_16864 #
LISAAFFA-84-09	p 250	N85_16865 #
	p 200	1100-10000 #
USAAVSCOM-TR-84-A-6	n 271	N85-16877 * #
USAAVSCOM-TB-84-A-6	0 271	N85-16878 #
LISAAVSCOM_TR-84_C-12	200	N95-15659 * #
	P 200	1403-10030 #

ACCESSION NUMBER INDEX

AERONAUTICAL ENGINEERING / A Continuing Bibliography (Supplement 187)

MAY 1985

Typical Accession Number Index Listing



Listings in this index are arranged alphanumerically by accession number. The page number listed to the right indicates the page on which the citation is located. An asterisk (*) indicates that the item is a NASA report. A pound sign (#) indicates that the item is available on microfiche.

A85-19183 #	p 244	A85-19505 #	p 304
A85-19184 #	p 246	A85-19507 *#	o 304
A85-19260 #	p 204	A85-19508 * #	0 210
A85-19262 #	p 205	ARE 10500 * #	- 160
A85-19263 #	p 205	A85-19509 #	p 202
A85-19264 #	p 205	A85-19510 *#	p 210
A85-19269 #	p 303	A85-19511 #	p 210
A85-19270 #	p 272	A85-19512 #	p 273
A85-19271 #	p 272	A85-19513 #	p 240
A85-19272 #	p 272	A85-19514 #	p 299
A85-19274 #	p 246	A85-19515 #	p 273
A85-19275 #	p 244	A85-19516 #	p 240
A85-19401 #	p 205	· A85-19520 #	p 286
A85-19402 #	p 272	A85-19523 #	p 210
A85-19403 #	p 272	A85-19524 *#	p 210
A85-19404 #	p 205	A85-19525 #	p 262
A85-19405 #	p 206	A85-19526 * #	p 210
A85-19406 #	p 206	A85-19531 #	p 211
A85-19439 #	p 206	A85-19532 #	p 211
A85-19451 *#	p 206	A85-19533 * #	p 211
A85-19452 #	p 206	A85-19534 #	p 211
A85-19453 #	p 262	A85-19536 #	p 211
A85-19454 #	p 206	A85-19538 #	p 211
A85-19455 #	p 206	A85-19539 #	p 212
A85-19456 * #	0 272	A85-19540 #	p 212
A85-19457 #	p 247	A85-19541 #	p 212
A85-19458 *#	p 298	A85-19542 #	p 212
A85-19459 #	p 247	A85-19543 #	p 212
A85-19460 #	n 206	A85-19556 #	p 212
A85-19461 #	0 207	A85-19562 * #	p 213
A85-19469 #	D 207	A85-19563 #	p 213
A85-19470 *#	0 207	A85-19565 #	p 213
A85-19472 *#	n 207	A85-19567 * #	p 213
A85-19473 #	n 207	A85-19568 #	p 213
A85-19474 #	n 207	A85-19569 #	p 213
A85-19475 *#	0.208	A85-19570 #	p 214
A85-19476 #	0.208	A85-19571 *#	p 214
A85-19477 #	0 208	A85-19572 #	p 214
A85-19478 #	0 208	A85-19573 #	p 214
A85-19479 #	n 208	A85-19575 #	p 286
A85-19480 #	n 208	A85-19577 #	p 274
A85-19482 *#	n 209	A85-19582 #	p 214
A85-19483 #	0 273	A85-19583 * #	p 268
A85-19484 #	0 209	A85-19584 #	p 247
A85-19485 *#	n 273	A85-19585 * #	p 268
A85-19486 #	0 273	A85-19586 #	p 300
A85-19487 #	n 209	A85-19587 #	p 214
A85-19489 *#	n 209	A85-19588 * #	p 215
A85-19490 *#	D 209	A85-19589 #	p 215
A85-19491 *#	n 285	A85-19590 * #	p 215
AR5-10405 4	0.270	A85-19591 * #	p 215
A05 40403 #	p 2/9	A85-19592 #	p 215
A65-1949/ #	p 2/3	A85-19593 *#	p 215
A85-19498 #	p 268	A85-19601 * #	p 274
A85-19500 #	p 209	A85-19602 #	p 274
A85-19501 #	p 210	A85-19603 * #	p 274

485.1	9611 * #	n 216
400-1 AOE 1	0614 #	p 210
400°I	0014 #	p 210
405-1	9015 #	p 202
485-1	9010 #	p 263
A85-1	9617 * #	p 216
A85-1	9618 * #	p 2/4
A85-1	9619 #	p 247
A85-1	9620 #	p 244
A85-1	9621 *#	p 216
A85-1	9622 #	p 216
A85-1	9623 #	p 247
A85-1	9624 #	p 216
A85-1	9626 * #	p 247
485-1	9627 #	0 248
485.1	9628 * #	0 217
A06 1	0620 #	0 217
AOC 1	0620 #	p 217
A05-1	9030 #	P 217
A03-1	9031 #	p 217
A85-1	9632 #	p 217
A85-1	9633 #	p 217
A85-1	9634 #	p 218
A85-1	9635 #	p 218
A85-1	9641 * #	p 218
A85-1	9642 * #	p 218
A85-1	9643 #	p 218
A85-1	9644 * #	p 218
A85-1	9648 * #	p 218
A85-1	9649 #	p 219
A85-1	9650 * #	0 219
A85.1	9651 * #	n 219
A85-1	9652 #	n 219
A95.4	0652 * #	n 210
A02-1	0655 * 4	p 274
A60-1	9000 #	p 2/4
A85-1	9000 #	p 268
A85-1	9658 - #	p 199
A85-1	9659 #	p 2/4
A85-1	9661 * #	p 275
A85-1	9662 #	p 275
A85-1	9671 #	p 263
A85-1	9677 * #	p 248
A85-1	9678 * #	p 275
A85-1	9679 #	p 240
A85-1	9680 #	p 240
A85-1	9684 #	p 248
485-1	9685 * #	p 269
A95.1	0696 * #	p 210
A05-1	10699 #	p 213
A05-1		p 220
A85-	9069 #	p 220
A85-1	19690 #	p 220
A85-1	9691 #	p 220
A85-1	19692 #	p 220
A85-1	9696 *#	p 220
A85-1	9698 #	p 220
A85-1	19699 *#	p 221
A85-1	19700 * #	p 221
A85-	19701 * #	p 221
A85-	19702 #	p 221
A85-	19703 #	D 221
ARA	19705 #	0 221
A85.	19706 #	0 286
495.	19709 4	p 200
A00-	10700 #	p 222
A00-	10710 #	P 2/3
A00-	19/10 #	p 263
A85-	19/11 #	p 2/5
A85-	19719 #	p 240
A85-	19720 *#	p 240
A85-	19721 #	p 241
A85-	19729 #	p 304
A85-	19730 *#	p 222
A85-1	19731 *#	p 222
A85-	19732 #	p 222
A85-	19733 ° #	p 222
A85-	19734 #	p 248
A85-	19735 #	p 286
A85	19738 #	p 200
486	19739 * #	n 249
200-	19740 * 4	p 290
A05-	10744 * "	P 223
A00-	10740 #	p 240
MOD-	13/42 #	p 223
A85-	19746 #	p 223
A85-	19747 #	p 223
A85-	19748 #	p 223
205	19740 * #	0 223
~00~	10140 H	y ces

A85-19754	#	p 286	
A85-19755	# #	p 224 n 224	
A85-19758	•#	p 249	
A85-19759	#	p 224	
A85-19760	# • #	p 224	
A85-19762	•#	p 224	
A85-19768	#	p 241	
A85-19769	# #	p 200 p 225	
A85-19777	#	p 225	
A85-19778 A85-19779	# *#	p 225 p 225	
A85-19781	#	p 225	
A85-19782	•# •#	p 300 p 225	
A85-19784	• #	p 226	
A85-19785	*#	p 226	
A85-19788	*#	p 226	
A85-19789	#	p 249	
A85-19790 A85-19791	*#	p 249 p 279	
A85-19792	#	p 279	
A85-19798 A85-19801	# •#	p 226 p 263	
A85-19805	#	p 244	
A85-19812	#	p 199 p 226	
A85-19826	#	p 307	
A85-19828	#	p 269	
A85-19835	# #	р 207 р 301	
A85-19836	#	p 249	
A85-19837 A85-19844	# #	p 287 p 227	
A85-19846	#	p 241	
A85-19848 A85-19851	# #	p 227 p 227	
A85-19854	#	p 227	
A85-19876 A85-19877	#	p 269 n 263	
A85-19878	#	p 275	
A85-19886 A85-20025	#	p 287 p 227	
A85-20057	#	p 199	
A85-20058	#	p 249	
A85-20059	#	p 243 p 263	
A85-20061	#	p 263	
A85-20074 A85-20122	# #	p 227 p 275	
A85-20142	#	p 250	
A85-20143 A85-20146	`# #	p 269 p 250	
A85-20147	#	p 250	
A85-20148	#	p 241 p 280	
A85-20221	#	p 244	
A85-20222	#	p 250 p 279	
A85-20228	#	p 227	
A85-20229	#	p 228	
A85-20230 A85-20231	#	p 228 p 228	
A85-20232	#	p 287	
A85-20233 A85-20235	#	р 228 р 264	
A85-20236	#	р 304	
A85-20238	#	p 228 n 228	
A85-20240	#	p 228	
A85-20241	#	p 228	
A85-20242	#	p 264	
A85-20451	#	p 199	
A85-20452	. #	p 199	
A85-20454	#	p 287	
A85-20455 A85-20459	#	p 199 p 287	
A85-20460	, <i>"</i> #	p 288	

		U 200
185-20466	#	p 200
A85-20469	#	p 250
485-20472	#	p 288
485-20473	#	p 250
485-20501	#	p 288
A85-20545	#	p 280
A85-20554	#	p 229
A85-20557	#	p 229
A85-20561	#	p 229
485-20562	#	p 229
A85-20650	#	p 304
A85-20744	•#	p 229
A85-20758	#	p 280
A85-20759	#	D 280
485-20790	#	p 281
A85-20800	#	p 288
A85-20822	#	р 264
A85-20828	#	p 288
A85-20851	•#	p 229
A85-20852	#	p 288
A85-20854	#	p 230
A85-20855	•#	D 230
A85-20856	#	p 301
A85-20862	#	p 230
A85-20864	#	p 230
A85-20865	#	p 281
A85-20867	•#	p 264
A85-20868	•#	p 230
A85-20869	•#	p 230
A85-20870	•#	D 231
A85-20872	•#	D 241
A85-20873	•#	D 231
A85-20874	#	p 288
A85-20875	#	p 250
A85-20884	#	p 289
A85-20909	#	p 280
A85-20915	#	p 289
A85-20925	#	p 281
A85-20998	#	p 231
A85-21141	#	p 299
A85-21278	#	0 289
A85-21283	#	p 289
A85-21293	•#	0 289
A85-21296	#	n 289
A85-21376	#	p 281
A85-21378	#	0 251
A85-21379	#	D 251
A85-21379 A85-21380	# #	p 251 p 281
A85-21379 A85-21380 A85-21381	# # #	p 251 p 281 p 251
A85-21379 A85-21380 A85-21381 A85-21382	# # # #	p 251 p 281 p 251 p 200
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383	####	p 251 p 281 p 251 p 200 p 251
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21384	######	p 251 p 281 p 251 p 200 p 251 p 251
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21384 A85-21385	#######	p 251 p 281 p 251 p 200 p 251 p 251 p 251
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21384 A85-21385 A85-21386	########	p 251 p 281 p 251 p 200 p 251 p 251 p 290 p 251
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21384 A85-21384 A85-21386 A85-21387	#########	p 251 p 281 p 251 p 200 p 251 p 251 p 290 p 251 p 251
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21384 A85-21385 A85-21386 A85-21387 A85-21388	###########	p 251 p 281 p 251 p 200 p 251 p 251 p 251 p 251 p 251 p 251
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21384 A85-21385 A85-21386 A85-21386 A85-21388 A85-21388 A85-21388	###########	p 251 p 281 p 251 p 200 p 251 p 251 p 251 p 251 p 251 p 251 p 251 p 251
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21384 A85-21385 A85-21386 A85-21387 A85-21388 A85-21389 A85-21389	############	p 251 p 281 p 251 p 250 p 251 p 251 p 251 p 251 p 251 p 251 p 251 p 281
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21385 A85-21385 A85-21385 A85-21385 A85-21389 A85-21389 A85-21392	#############	p 251 p 281 p 251 p 250 p 251 p 251 p 251 p 251 p 251 p 251 p 281 p 281 p 282
A85-21379 A85-21380 A85-21381 A85-21383 A85-21383 A85-21383 A85-21386 A85-21386 A85-21386 A85-21389 A85-21389 A85-21390 A85-21392	###############	p 251 p 281 p 251 p 200 p 251 p 282 p 282 p 282
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21385 A85-21386 A85-21386 A85-21388 A85-21388 A85-21388 A85-21390 A85-21392 A85-21392	################	p 251 p 281 p 250 p 251 p 251 p 251 p 251 p 251 p 251 p 251 p 251 p 281 p 282 p 282 p 282 p 282
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21385 A85-21386 A85-21386 A85-21387 A85-21388 A85-21387 A85-21390 A85-21393 A85-21393	################	p 251 p 251 p 251 p 250 p 251 p 251 p 251 p 251 p 251 p 251 p 251 p 282 p 282 p 282 p 282 p 282
A85-21379 A85-21380 A85-21381 A85-21383 A85-21383 A85-21385 A85-21385 A85-21385 A85-21385 A85-21386 A85-21389 A85-21393 A85-21393 A85-21394 A85-21394	<i>#####################################</i>	p 251 p 281 p 251 p 251 p 251 p 251 p 251 p 251 p 251 p 251 p 281 p 282 p 282 p 282 p 282 p 282 p 260 p 252 p 252
A85-21379 A85-21380 A85-21381 A85-21384 A85-21384 A85-21384 A85-21384 A85-21386 A85-21387 A85-21387 A85-21387 A85-21398 A85-21392 A85-21393 A85-21396 A85-21396 A85-21396	***	p 251 p 281 p 251 p 282 p 282 p 282 p 282 p 282 p 282 p 252 p 252 p 252
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21383 A85-21384 A85-21386 A85-21386 A85-21386 A85-21387 A85-21389 A85-21390 A85-21393 A85-21394 A85-21394 A85-21394 A85-21394 A85-21397 A85-21397	<i>#####################################</i>	p 251 p 281 p 282 p 282 p 282 p 264 p 252 p 264 p 254
A85-21379 A85-21380 A85-21380 A85-21381 A85-21381 A85-21383 A85-21384 A85-21386 A85-21386 A85-21386 A85-21386 A85-21388 A85-21392 A85-21394 A85-21	<i>#####################################</i>	p 251 p 281 p 251 p 282 p 282 p 282 p 282 p 262 p 252 p 252 p 254 p 252 p 252 p 254
A85-21379 A85-21380 A85-21381 A85-21382 A85-21382 A85-21383 A85-21385 A85-21386 A85-21386 A85-21388 A85-21388 A85-21392 A85-21392 A85-21393 A85-21394 A85-21394 A85-21397 A85-21420 A85-21420 A85-21456 A85-21456	<i>#####################################</i>	p 251 p 281 p 281 p 282 p 282 p 282 p 282 p 252 p 252 p 252 p 254 p 276 p 276
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21383 A85-21384 A85-21386 A85-21386 A85-21387 A85-21389 A85-21389 A85-21390 A85-21393 A85-21394 A85-21394 A85-21397 A85-21420 A85-21456 A85-21457	<i>#####################################</i>	p 251 p 281 p 251 p 251 p 251 p 251 p 251 p 251 p 251 p 251 p 281 p 281 p 281 p 282 p 282 p 260 p 252 p 262 p 252 p 264 p 276 p 276 p 200 p 251
A85-21379 A85-21380 A85-21380 A85-21381 A85-21383 A85-21383 A85-21384 A85-21386 A85-21386 A85-21386 A85-21386 A85-21387 A85-21392 A85-21392 A85-21394 A85-21396 A85-21396 A85-21420 A85-21420 A85-21420 A85-21458 A85-21458	<i>#####################################</i>	p 251 p 282 p 282 p 282 p 282 p 264 p 276 p 200 p 301 p 301 p 301
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21385 A85-21385 A85-21386 A85-21386 A85-21386 A85-21388 A85-21388 A85-21398 A85-21397 A85-21397 A85-21397 A85-21397 A85-21420 A85-21420 A85-21456 A85-21458 A85-21458 A85-21458	######################################	p 251 p 281 p 281 p 282 p 282 p 282 p 264 p 252 p 264 p 250 p 301 p 301 p 301 p 244 p 290
A85-21379 A85-21380 A85-21381 A85-21381 A85-21383 A85-21383 A85-21384 A85-21386 A85-21386 A85-21386 A85-21387 A85-21389 A85-21390 A85-21393 A85-21394 A85-21394 A85-21397 A85-21420 A85-21456 A85-21457 A85-21459 A85-21459 A85-21450 A85-21	######################################	p 251 p 252 p 254 p 250 p 254 p 251 p 252 p 252
A85-21379 A85-21380 A85-21380 A85-21381 A85-21383 A85-21384 A85-21384 A85-21386 A85-21386 A85-21386 A85-21386 A85-21387 A85-21389 A85-21390 A85-21394 A85-21394 A85-21394 A85-21420 A85-21457 A85-21459 A85-21450 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451 A85-21451	######################################	p 251 p 252 p 254 p 252 p 254 p 2554 p 25554 p 2554 p 2554 p 25554 p 25554 p 25554 p 255555555555555555
A85-21379 A85-21380 A85-21381 A85-21382 A85-21382 A85-21383 A85-21386 A85-21386 A85-21386 A85-21388 A85-21388 A85-21392 A85-21392 A85-21392 A85-21393 A85-21394 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450	***	p 251 p 252 p 264 p 252 p 252 p 252 p 252 p 252 p 254 p 276 p 252 p 254 p 250 p 251 p 252 p 254 p 255 p 255
A85-21379 A85-21380 A85-21381 A85-21381 A85-21383 A85-21383 A85-21383 A85-21384 A85-21386 A85-21387 A85-21389 A85-21389 A85-21390 A85-21393 A85-21393 A85-21393 A85-21394 A85-21450 A85-21	***	p 251 p 252 p 255 p 255
A85-21379 A85-21380 A85-21380 A85-21381 A85-21383 A85-21383 A85-21384 A85-21386 A85-21386 A85-21386 A85-21386 A85-21387 A85-21389 A85-21390 A85-21390 A85-21394 A85-21396 A85-21420 A85-21457 A85-21457 A85-21450 A85-21450 A85-21450 A85-21450 A85-21450 A85-21451 A85-21450 A85-21451 A85-21450 A85-2139 A85-21450 A85-	***	p 251 p 252 p 252
A85-21379 A85-21380 A85-21381 A85-21382 A85-21382 A85-21383 A85-21386 A85-21386 A85-21387 A85-21387 A85-21387 A85-21387 A85-21392 A85-21392 A85-21392 A85-21394 A85-21394 A85-21452 A85-21455 A85-21452 A85-21	***	p 251 p 252 p 252
A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21383 A85-21384 A85-21384 A85-21386 A85-21386 A85-21387 A85-21389 A85-21390 A85-21390 A85-21391 A85-21394 A85-21394 A85-21450 A85-21	***	p 251 p 252 p 252
A85-21379 A85-21380 A85-21380 A85-21381 A85-21383 A85-21384 A85-21384 A85-21386 A85-21386 A85-21386 A85-21386 A85-21387 A85-21389 A85-21390 A85-21390 A85-21396 A85-21490 A85-21450 A85-21247 A85-21	***	p 251 p 252 p 252 p 252 p 254 p 252 p 254 p 254 p 254 p 252 p 254 p 254 p 252 p 254 p 255 p 255
A85-21379 A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21386 A85-21386 A85-21387 A85-21387 A85-21387 A85-21387 A85-21387 A85-21392 A85-21392 A85-21392 A85-21392 A85-21392 A85-21452 A85-21	**	p 251 p 252 p 254 p 252 p 252 p 252 p 252 p 254 p 252 p 252 p 254 p 252 p 252 p 254 p 252 p 252 p 254 p 252 p 252 p 254 p 252 p 252 p 252 p 254 p 252 p 252
A85-21379 A85-21380 A85-21381 A85-21383 A85-21383 A85-21383 A85-21384 A85-21384 A85-21386 A85-21386 A85-21387 A85-21389 A85-21389 A85-21390 A85-21390 A85-21391 A85-21391 A85-21391 A85-21450 A85-21520 A85-21520 A85-21520 A85-21520	****	p 251 p 252 p 262 p 262 p 252 p 252
A85-21379 A85-21380 A85-21381 A85-21381 A85-21383 A85-21384 A85-21384 A85-21386 A85-21386 A85-21386 A85-21387 A85-21389 A85-21389 A85-21390 A85-21390 A85-21390 A85-21391 A85-21420 A85-21450 A85-21520 A85-21520 A85-21520	****	p 251 p 252 p 264 p 250 p 264 p 250 p 264 p 250 p 264 p 250 p 264 p 252 p 264 p 252 p 264 p 252 p 264 p 250 p 252 p 264 p 250 p 252 p 252 p 252 p 252 p 252 p 252 p 254 p 252 p 254 p 252 p 254 p 252 p 254 p 255 p 254 p 255 p 255
A85-21379 A85-21379 A85-21380 A85-21381 A85-21382 A85-21383 A85-21386 A85-21386 A85-21386 A85-21386 A85-21388 A85-21389 A85-21392 A85-21392 A85-21392 A85-21392 A85-21392 A85-21392 A85-21450 A85-21450 A85-21450 A85-21450 A85-21452 A85-21527 A85-21525	* * *	p 251 p 252 p 262 p 252 p 264 p 252 p 252 p 252 p 254 p 255 p 255

A85-21582

ACCESSION NUMBER INDEX

A85-21582	#	D 241	N85-15679 # n.24	a.
A85-21593	#	0 259	N85-15680 # p 2	2
A85-21643	#	n 241	N85-15681 # p 29	2
A85-21644	#	n 276	N85-15682 # p 29	2
A85-21650 *	#	0 283	N85-15683 # p 29	2
A85-21656	#	p 231	N85-15687 * # p 23	14
A85-21668	#	p 242	N85-15688 * # ρ 23	14
A85-21679	#	p 269	N85-15689 *# p 23	4
A85-21680	#	p 200	N85-15690 # p 23	14
A85-21681	#	p 270	N85-15691 *# p 2	4
A85-21682	#	p 264	N05-15092 # p 23	
A85-21683	#	p 290	N85-15693 # 0.23	5
A85-21791 *	#	p 301	N85-15695 *# n 23	15
A85-21827 *	#	p 231	N85-15696 *# p 20	15
A85-21830 *	Ħ.	p 231	N85-15697 * # p 23	15
A85-21838	#	p 245	N85-15699 # p 23	6
A85-21839	#	p 205	N85-15700 # p 24	2
A00-21040	#	p 307	N85-15701 * # p 24	2
A85.21842 *	# #	0 304	N85-15702 * # p 24	2
A85-21843	#	p 299	N85-15703 # p 24	2
A85-21844 *	#	p 252	N85-15706 * # p 24	15
A85-21845	#	p 231	N85-15707 # p 24	5
A85-21846 *	#	p 290	N85-15/09 # p 24	5
A85-21847 *	#	p 252	N65-15/10 # p 2:	24 E
A85-21848 *	#	p 231	N85-15712 # o.26	5
A85-21849	#	p 232	N85-15713 *# n 25	5
A85-21851	ŧ.	p 232	N85-15714 * # n 25	5
A85-21855	#	p 232	N85-15715 *# 0.25	5
A85-21856	#	p 232	N85-15716 * # p 25	5
A05-2105/	7	p 232	N85-15717 * # p 25	5
A05-21050	7	p 304	N85-15718 * # p 25	6
A05-21059 :	#	p 202	N85-15719 # p 25	6
A85-21864 *	7 #	n 232	N85-15720 # p 25	6
A85-21866 *	#	p 265	N85-15721 # p 25	9
A85-21875 *	#	p 290	N85-15722 # p 25	9
A85-21942	#	p 307	N85-15723 # p 26	5
A85-21943	#	p 307	N85-15/24 # p 2t	5
A85-21944	#	p 307	N65-15725 # p 20	
A85-21945	#	p 307	N85-15729 # D20	5
A85-21946	#	p 307	N85-15732 # p.20	5
A85-21947	#	p 308	N85-15733 # n 26	6
A85-21948	#	p 308	N85-15735 # p.20	6
A85-21949	#	p 308	N85-15736 # p 26	6
A85-219/3	F.	p 301	N85-15737 # p 26	6
A00-21980	7	p 290	N85-15738 # p 26	6
A85-22005	# #	p 202	N85-15739 # p 28	3
A85-22081	#	p 252	N85-15741 # p 26	57
A85-22105	#	p 290	N85-15742 # p 26	7
A85-22113	#	p 290	N85-15743 # p 20	57
A85-22114	#	p 291	N85-15744 * # p 20	57
A85-22146	#	p 232	N85-15/45 # p20	97 20
A85-22168	#	p 291	N03-15740 # p 28	2
A85-22226	#	p 200	N85-15751 # p 20	7
A85-22227	#	p 233	N85-15752 * # n 27	0
A85-22228	#	p 233	N85-15753 # p 2	70
A85-22231	#	p 265	N85-15754 # p 2	6
A85-22232	# #	p 291	N85-15755 *# p 2	6
A85.22240	π #	0 252	N85-15757 * # p 23	6
A85-22274	#	p 302	N85-15758 * # p 23	'6
A85-22281 *	#	p 291	N85-15760 # p 2	7
A85-22308	#	p 233	N85-15761 # p2	7
A85-22364	#	p 233	N65-15/62 # P2	7
A85-22366	#	p 233	N85-15779 *# ~ 2	
A85-22367	#	p 233	N85-15831 # 0.2	33
A85-22368	#	p 233	N85-15919 # D 2	33
A00-223/U	#	p 234	N85-15920 # p 2	13
A85-22373	17 #	p 234	N85-15921 # p 2	33
A85-22374	а #	p 302	N85-15922 # p 2	34
A85-22445	 #	p 291	N85-15931 # p 2	34
A85-22449	#	p 302	N85-15940 # p 2	33
			N85-15941 # p 2	13
N85-15658 *			N85-15949 # p21	13
	#	p 200		20
N85-15659	# #	р 200 р 200	N85-15954 # p 29	93
N85-15659 N85-15660	###	p 200 p 200 p 201	N85-15954 # p 2 N85-15993 * # p 2 N85-16008 # ~ ~	93 93 93
N85-15659 N85-15660 N85-15661	####	p 200 p 200 p 201 p 201	N85-15954 # p2 N85-15993 * # p2 N85-16008 # p2 N85-16048 # p2	93 93 93 70
N85-15659 N85-15660 N85-15661 N85-15662	######	p 200 p 200 p 201 p 201 p 201	N85-15954 # p 2 N85-15993 *# p 2 N85-16008 # p 2 N85-16048 # p 2 N85-16048 # p 2	93 93 93 93 70 93
N85-15659 N85-15660 N85-15661 N85-15662 N85-15663	#######	p 200 p 200 p 201 p 201 p 201 p 201 p 201	N85-15954 # p 2 N85-15993 *# p 2 N85-16008 # p 2 N85-16048 # p 2 N85-16045 *# p 2 N85-16065 *# p 2	93 93 93 93 93 93 94
N85-15659 N85-15660 N85-15661 N85-15662 N85-15663 N85-15664 N85-15664	#########	p 200 p 200 p 201 p 201 p 201 p 201 p 201 p 201	N85-15954 # p 2 N85-15993 *# p 2 N85-16008 # p 2 N85-16048 # p 2 N85-16065 *# p 2 N85-16067 # p 2 N85-16069 # p 2	33 33 33 33 33 34 34
N85-15659 N85-15660 N85-15661 N85-15662 N85-15663 N85-15664 N85-15665	##########	p 200 p 200 p 201 p 201 p 201 p 201 p 201 p 201 p 201 p 253 p 253	N85-15954 # p2 N85-15993 * p2 N85-16008 # p2 N85-16048 # p2 N85-16065 * p2 N85-16067 # p2 N85-16069 # p2 N85-16070 # p2	93 93 93 93 93 93 94 94 94
N85-15659 N85-15660 N85-15661 N85-15662 N85-15663 N85-15664 N85-15665 N85-15666 N85-15666	###########	p 200 p 200 p 201 p 201 p 201 p 201 p 201 p 201 p 201 p 253 p 253 p 253	N85-15954 # p 2 N85-15993 * p 2 N85-16008 # p 2 N85-16048 # p 2 N85-16046 * p 2 N85-16067 # p 2 N85-16069 # p 2 N85-16070 # p 2 N85-16073 # p 2	33 33 33 33 33 33 34 44 34
N85-15659 N85-15660 N85-15661 N85-15662 N85-15663 N85-15664 N85-15665 N85-15667 N85-15667 N85-15667	############	p 200 p 200 p 201 p 201 p 201 p 201 p 201 p 201 p 201 p 253 p 253 p 253 p 253	N85-15954 # p 2' N85-15993 # p 2' N85-16008 # p 2' N85-16048 # p 2' N85-16048 # p 2' N85-16065 # p 2' N85-16065 # p 2' N85-16067 # p 2' N85-16067 # p 2' N85-16067 # p 2' N85-16070 # p 2' N85-16073 # p 2' N85-16073 # p 2' N85-16074 # p 2'	33 33 33 33 33 34 34 44 34 34
N85-15659 N85-15660 N85-15661 N85-15662 N85-15663 N85-15664 N85-15665 N85-15667 N85-15667 N85-15668 N85-15669	#############	p 200 p 200 p 201 p 201 p 201 p 201 p 201 p 201 p 201 p 253 p 253 p 253 p 253 p 253	N85-15954 # p 2 N85-15993 # p 2 N85-16008 # p 2 N85-16048 # p 2 N85-16068 # p 2 N85-16065 # p 2 N85-16067 # p 2 N85-16067 # p 2 N85-16070 # p 2 N85-16073 # p 2 N85-16074 # p 2 N85-16087 # p 2	33 33 33 33 33 33 33 34 44 44 44
N85-15659 N85-15660 N85-15661 N85-15662 N85-15663 N85-15664 N85-15666 N85-15666 N85-15667 N85-15669 N85-15669 N85-15670	################	p 200 p 200 p 201 p 201 p 201 p 201 p 201 p 201 p 253 p 253 p 253 p 253 p 253	N85-15954 # p 22 N85-15993 # p 22 N85-16008 # p 22 N85-16048 # p 22 N85-16065 # p 22 N85-160667 # p 22 N85-16067 # p 22 N85-16067 # p 22 N85-16067 # p 22 N85-16070 # p 22 N85-16073 # p 22 N85-16074 # p 22 N85-16075 # p 22 N85-16076 # p 22 N85-16076 # p 22 N85-16087 # p 22 N85-16096 # p 24	33 33 33 70 70 94 94 94 94 94 94 95
N85-15659 N85-15660 N85-15661 N85-15662 N85-15663 N85-15665 N85-15666 N85-15666 N85-15666 N85-15668 N85-15668 N85-15669 N85-15670 N85-15671	##################	p 200 p 200 p 201 p 201 p 201 p 201 p 201 p 201 p 203 p 253 p 253 p 253 p 253 p 253 p 253 p 254 p 292	N85-15954 # p 2 N85-15993 # p 2 N85-16008 # p 2' N85-16048 # p 2' N85-16048 # p 2' N85-16065 # p 2' N85-16066 # p 2' N85-16067 # p 2' N85-16069 # p 2' N85-16070 # p 2' N85-16073 # p 2' N85-16074 # p 2' N85-16075 # p 2' N85-16076 # p 2' N85-16096 # p 2' N85-16098 # p 2'	33 33 33 33 33 33 34 34 34 34 34 34 35 35
N85-15659 N85-15661 N85-15661 N85-15662 N85-15662 N85-15663 N85-15665 N85-15665 N85-15668 N85-15668 N85-15669 N85-15670	####################	p 200 p 200 p 201 p 201 p 201 p 201 p 201 p 201 p 203 p 253 p 253 p 253 p 253 p 253 p 254 p 292 p 292	N85-15954 # p 2 N85-15993 # p 2 N85-16048 # p 2' N85-16048 # p 2' N85-16048 # p 2' N85-16065 # p 2' N85-16067 # p 2' N85-16067 # p 2' N85-16067 # p 2' N85-16070 # p 2' N85-16073 # p 2' N85-16074 # p 2' N85-16087 # p 2' N85-16098 # p 2' N85-16100 # p 2' N85-16100 # p 2' N85-16098 # p 2'	33 33 33 33 33 33 33 34 34 34 34 34 34 3
N85-15659 N85-15661 N85-15661 N85-15662 N85-15663 N85-15665 N85-15665 N85-15665 N85-15668 N85-15669 N85-15679 N85-15672 N85-15674	######################################	p 200 p 200 p 201 p 201 p 201 p 201 p 201 p 253 p 253 p 253 p 253 p 253 p 254 p 292 p 292 p 254	N85-15954 # p 2 N85-15993 # p 2 N85-16048 # p 2' N85-16048 # p 2' N85-16048 # p 2' N85-16065 # p 2' N85-16067 # p 2' N85-16067 # p 2' N85-16070 # p 2' N85-16073 # p 2' N85-16074 # p 2' N85-16087 # p 2' N85-16096 # p 2' N85-16097 # p 2' N85-16074 # p 2' N85-16096 # p 2' N85-16097 # p 2' N85-16096 # p 2' N85-16097 # p 2' N85-16098 # p 2' N85-16100 # p 2' N85-16105 # p 2'	33 33 33 30 70 33 34 34 34 34 34 35 35 35 35 35
N85-15659 N85-15661 N85-15661 N85-15662 N85-15664 N85-15664 N85-15665 N85-15667 N85-15667 N85-15670 N85-15670 N85-15671 N85-15674 N85-15675	######################################	p 200 p 200 p 201 p 201 p 201 p 201 p 201 p 201 p 253 p 253 p 253 p 253 p 253 p 253 p 253 p 254 p 292 p 292 p 254 p 254 p 254	N85-15954 # p 2 N85-15993 # p 2 N85-16008 # p 2 N85-16048 # p 2 N85-16048 # p 2 N85-16048 # p 2 N85-16047 # p 2 N85-16069 # p 2 N85-16070 # p 2 N85-16073 # p 2 N85-16074 # p 2 N85-16075 # p 2 N85-16074 # p 2 N85-16075 # p 2 N85-16076 # p 2 N85-16096 # p 2 N85-16098 # p 2 N85-16100 # p 2	93 93 93 93 93 93 93 94 94 94 94 95 95 95 95 95 95
N85-15659 N85-15660 N85-15661 N85-15662 N85-15664 N85-15664 N85-15665 N85-15666 N85-15667 N85-15668 N85-15669 N85-15670 N85-15671 N85-15675 N85-15675 N85-15675	#####################	p 200 p 201 p 201 p 201 p 201 p 201 p 201 p 253 p 253 p 253 p 253 p 253 p 253 p 253 p 254 p 292 p 254 p 254 p 254	N85-15954 # p 2' N85-15993 # p 2' N85-16008 # p 2' N85-16048 # p 2' N85-16048 # p 2' N85-16065 # p 2' N85-16067 # p 2' N85-16067 # p 2' N85-16070 # p 2' N85-16073 # p 2' N85-16074 # p 2' N85-16087 # p 2' N85-16098 # p 2' N85-16098 # p 2' N85-16098 # p 2' N85-16100 # p 2' N85-16156 # p 2' N85-16156 # p 2' N85-16169 # p 2' N85-16196 # p 2' N85-16196 # p 2'	33 333 330 330 330 333 344 344 344 345 355 355 355 355 355
N85-15659 N85-15660 N85-15661 N85-15662 N85-15662 N85-15663 N85-15665 N85-15665 N85-15666 N85-15668 N85-15668 N85-15676 N85-15671 N85-15677 N85-15677 N85-15676 N85-15676	并并并并并并并并并并并并并并并并并并并	p 200 p 200 p 201 p 201 p 201 p 201 p 253 p 253 p 253 p 253 p 253 p 254 p 292 p 254 p 254 p 254	N85-15954 # p 2 N85-15993 # p 2 N85-16008 # p 2 N85-16048 # p 2 N85-16048 # p 2 N85-16065 # p 2 N85-16067 # p 2 N85-16067 # p 2 N85-16067 # p 2 N85-16073 # p 2 N85-16074 # p 2 N85-16087 # p 2 N85-16086 # p 2 N85-16196 # p 2	33 33 33 30 30 30 33 34 34 34 34 34 34 34 35 35 35 35 35 36

N95	6503 #	• •	302
NRE	10500 m		305
NOS	16500 * 4		205
NOS-	10000 7		205
1980-	10393 #	. P	305
N85-	16595 #	, P	305
NOS-	1000/ #		200
NO5-	16685 #	· •	308
N85	16731 ±	. p	201
N85.	16732 #		202
N85	6733 #	5 0	296
N85-	6734 #	: 6	202
N85-	6735 #	Εp	202
N85-	6736 #	ŧ p	296
N85-1	16737 #	Εp	202
N85-	16738 #	t p	296
N85-1	6739 #	t p	202
N85-	6740 #	E p	202
N85-	16743 #	F P	202
N85-	16745 #	t p	203
N85-	16/46 #	r p	302
N85-	10/4/ #	E P	302
N85-	10/49 👭	, p	302
NO5	10/30 #	, p	202
NRS.	10/51 #		203
N85	16755 #	· •	203
N95.1	16757 * #		203
N85-1	6758 *#		203
N85-1	6759 * #	5	203
N85-1	6760 #	. 5	203
N85-1	6761 #	5	203
N85-	6762 #	ιĎ	204
N85-1	6763 #	i p	204
N85-1	6764 #	t p	204
N85-1	6765 #	E p	296
N85-1	6766 #	F p	256
N85-1	16767 #	P P	204
N85-1	16768 #	t p	256
N85-1	6770 #	Еp	277
N85-1	16771 #	P	204
N85-	6772 #	р р	236
N85-	6773 #	t p	236
N85-	16774 #	; p	236
N85-	16775 #	P	236
N85-1	0777 #	P	230
N85-	10/// #	P	200
NOD-	10//9 #		280
N95.1	10700 // 16781 ±	· P	257
N85.	16782 #	t p	257
N85-	16783 #	÷δ	237
N85-	16784 #	ŧõ	237
N85-	16785 #	ŧ p	237
N85-	16786 #	t p	257
N85-	16787 * #	⊧ p	237
N85-	16788 * #	ŧ p	237
N85-	16790 * #	ŧ p	257
N85-	16791 #	t p	257
N85-	16793 🕺	¢ p	237
N85-	16795 #	ŧ p	238
N85-	16797 #	ŧ P	204
N85-	16798 #	ŧ p	204
N85-	16799 #	F P	259
N85-	16800 #	f p	259
N85-	10001 # 16900 -	P	209
N85-	16804 1	r y ŧ n	245
N85	16805 1	r p f n	260
N85-	16806	+ D	260
N85-	16807 #	ŧ 0	297
N85-	16808 #	ŧ 0	260
N85-	16809 #	≠ ṕ	260
N85-	16810 #	≠ p	297
N85-	16811 ∦	* p	260
N85-	16812 #	ŧ ρ	260
N85-	16813 #	∮ Ρ	260
N85-	16814 *#	₹ P	270
N85-	10815 #	r p	2/7
N85-		ŗρ	211
1185-	1001/ # 16819 -	, p	210
NRE	16810 /	, μ έ κ	270
N85	16820 4	≠ π	261
N85-	16821 *	, p	261
N85-	16822	ŧ 0	238
N85-	16823	ŧ 0	238
N85-	16825 🕯	≠ p	238
N85-	16826 * #	≠ p	238
N85-	16829 * #	∮ P	238
N85-	16832 #	ŧ p	239
N85-	16833 #	ţΡ	239
N85-	16834 #	F P	239
N85-	16835 #	F P	239
N85-	10836 #	, p	233
ALC: N	10070 -		

1100-	00-0	π	P 242
N85-	16842	#	p 243
N85-	6844	#	p 243
N85-1	16845	#	p 243
N85-1	16846	#	p 243
N85-1	16847	#	p 243
N85-1	16848	#	p 243
N85-1	16849	#	D 244
N85-	16851	#	D 246
NOC -	10001	<i>"</i>	0 246
NOS-	10052	7	p 240
-COVI	10000	#	p 240
N85-	16835	Ŧ	p 246
N85-1	16860	#	p 246
N85-1	16861	•#	p 257
N85-1	16862	*#	p 258
N85-1	16864	#	p 258
N85-1	16865	#	p 258
N85-	16866	#	p 258
N85-	16867	#	n 258
NRE	16969	• #	p 261
NOS	16060	• #	n 261
NOC-	10009	#	p 201
-C6/1	16870	Ŧ	p 261
N85-	168/1	#	p 261
N85-1	16872	#	p 262
N85-1	16873	•#	p 268
N85-1	16874	#	p 268
N85-1	16875	#	p 268
N85-1	6876	#	p 271
N85-	6877	•#	0 271
N85-	6878	• #	n 271
NQ5.	6970	#	D 271
NOC 1	0079	<i>#</i>	p 271
-COVI	0000	#	p 2/1
N85-1	16881	Ŧ	p 2/1
N85-1	6882	•#	p 278
N85-1	16883	•#	p 278
N85-1	16884	#)	p 278
N85-1	16885	#	p 278
N85-1	16886	#	p 278
N85-1	16887	#	p 279
N85-1	16888	#	p 279
N85-	17048	•#	p 284
N85-	7049	•#	n 284
N85	17067	<i>"</i> #	p 284
N95	17050	#	p 204
NOU-	17050	#	p 204
100-	17039	#	p 200
N85-	1/0//	Ħ	p 285
N85-1	7152	#	p 285
N85-1	17153	#	p 285
N85-1	17155	#	p 285
N85-1	17159	#	p 297
N85-1	17162	#	p 297
N85-	17193	#	p 297
N85-	17194	#	n 303
NRS	17204	+ #	n 202
NIGE	17200	#	0 207
NO5-	17200	#	p 201
1100-	17331	# * #	h 596
N85-	17353	- <i>#</i>	p 285
N85-	1/363	#	p 298
N85-	17369	#	p 298
N85-	17398	#,	, p 298
N85-	17435	#)	p 299
N85-	17436	#、	p 299
N85-1	17470	#	p 300
N85-	17492	#	p 300
N85-	17494	#	0 300
NR5	17506	#	p 300
NRS	17579	#	0.300
NRE	17602	•#	P 303
1100-	17640	1f 	p 303
N85-	17013	#	p 303
N85-	1/667	#	p 305
N85-	17668	#	p 305
N85-	17669	#	p 306
N85-	17670	#	p 306
N85-	17672	#	p 306
N85-	17673	#	p 306
N85-	17677	#	p 304
N85			~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~
1100-	17732	#	n 309
NRF	17732	#	p 308
N85-	17732	# •#	p 308 p 309
N85- N85-	17732 17740 17928	•# •#	p 308 p 309 p 309

NOE 10040

G-2

1. Report No. NASA-SP-7037 (187)	2. Government Access	ion No.	3. Recipient's Catalog	No.	
4. Title and Subtitle	· · · · · · · · · · · · · · · · · · ·		5. Report Date		
Aeronautical Engineering	Ļ	May 1985			
A Continuing Bibliography (Su	6. Performing Organization Code				
7. Author(s)			8. Performing Organiz	ation Report No.	
			10. Work Unit No.		
9. Performing Organization Name and Address		L			
National Aeronautics and Space		11. Contract or Grant	No.		
wasnington, DC 20546					
	13. Type of Report and Period Covered				
12. Sponsoring Agency Name and Address					
			14. Sponsoring Agency	Code	
15. Supplementary Notes		1			
			'n		
	······				
16. Abstract					
This bit	oliography lists	725 reports, arti	icles and other		
document	ts introduced in	to the NASA scient	ific and		
technica	al information s	ystem in April 198	35.		
			~		
			2		
		ę			
17. Key Words (Suggested by Author(s))	18. Distribution Statement				
Aeronautical Engineering	Unclassified - Unlimited				
Aeronautics			UNITER CON		
Bibliographies					
19. Security Classif (of this report)					
	20. Security Classif. (o	t this page)	21. No. of Pages	22. Price*	

.

For sale by the National Technical Information Service, Springfield, Virginia 22161 NASA-Langley, 1985

FEDERAL DEPOSITORY LIBRARY PROGRAM

The Federal Depository Library Program provides Government publications to designated libraries throughout the United States. The Regional Depository Libraries listed below receive and retain at least one copy of nearly every Federal Government publication, either in printed or microfilm form, for use by the general public. These libraries provide reference services and inter-library loans; however, they are *not* sales outlets. You may wish to ask your local library to contact a Regional Depository to help you locate specific publications, or you may contact the Regional Depository yourself.

ARKANSAS STATE LIBRARY One Capitol Mall Little Rock, AR 72201 (501) 371-2326

AUBURN UNIV. AT MONTGOMERY LIBRARY Documents Department

Montgomery, AL 36193 (205) 279-9110, ext. 253

UNIV. OF ALABAMA LIBRARY Documents Dept.—Box S University, AL 35486 (205) 348-7369

DEPT. OF LIBRARY, ARCHIVES AND PUBLIC RECORDS Third Floor-State Cap. 1700 West Washington Phoenix, AZ 85007 (602) 255-4121

UNIVERSITY OF ARIZONA LIB. Government Documents Dept. Tucson, AZ 85721 (602) 626-5233

CALIFORNIA STATE LIBRARY Govt. Publications Section P.O. Box 2037 Sacramento, CA 95809 (916) 322-4572

UNIV. OF COLORADO LIB. Government Pub. Division Campus Box 184 Boulder, CO 80309 (303) 492-8834

DENVER PUBLIC LIBRARY Govt. Pub. Department 1357 Broadway Denver, CO 80203 (303) 571-2131

CONNECTICUT STATE LIBRARY Government Documents Unit 231 Capitol Avenue Hartford, CT 06106 (203) 566-4971

UNIV. OF FLORIDA LIBRARIES Library West Documents Department Gainesville, FL 32611 (904) 392-0367

UNIV. OF GEORGIA LIBRARIES Government Reference Dept. Athens. Ga 30602 (404) 542-8951

UNIV. OF HAWAII LIBRARY Govt Documents Collection 2550 The Mall Honolulu, HI 96822 (808) 948-8230

UNIV. OF IDAHO LIBRARY Documents Section Moscow, ID 83843 (208) 885-6344 ILLINOIS STATE LIBRARY Information Services Branch Centennial Building Springfield, IL 62706 (217) 782-5185

INDIANA STATE LIBRARY Serials Documents Section 140 North Senate Avenue Indianapolis, IN 46204 (317) 232-3686

UNIV. OF IOWA LIBRARIES Govt. Documents Department Iowa City, IA 52242 (319) 353-3318

1i

ł,

UNIVERSITY OF KANSAS Doc. Collect--Spencer Lib. Lawrence, KS 66045 (913) 864-4662

UNIV. OF KENTUCKY LIBRARIES Govt. Pub. Department Lexington, KY 40506 (606) 257-3139

LOUISIANA STATE UNIVERSITY Middleton Library Govt. Docs. Dept. Baton Rouge, LA 70803 (504) 388-2570

LOUISIANA TECHNICAL UNIV. LIBRARY Documents Department Ruston, LA 71272

(318) 257-4962 UNIVERSITY OF MAINE Raymond H. Fogler Library Tri-State Regional Documents Depository Orono, ME 04469 (207) 581-1680

UNIVERSITY OF MARYLAND McKeldin Lib.—Doc. Div. College Park, MD 20742 (301) 454-3034

BOSTON PUBLIC LIBRARY Government Docs. Dept. Boston, MA 02117 (617) 536-5400 ext. 226

DETROIT PUBLIC LIBRARY Sociology Department 5201 Woodward Avenue Detroit, Mi 48202 (313) 833-1409

MICHIGAN STATE LIBRARY P O. Box 30007 Lansing. MI 48909 (517) 373-0640

UNIVERSITY OF MINNESOTA Government Pubs Division 409 Wilson Library 309 19th Avenue South Minneapolis, MN 55455 (612) 373-7813 UNIV. OF MISSISSIPPI LIB. Documents Department University, MS 38677 (601) 232-5857

UNIV. OF MONTANA Mansfield Library Documents Division Missoula, MT 59812 (406) 243-6700

NEBRASKA LIBRARY COMM.

Federal Documents 1420 P Street Lincoln, NE 68508 (402) 471-2045 In cooperation with University of Nebraska-Lincoln

UNIVERSITY OF NEVADA LIB. Govt. Pub. Department Reno, NV 89557 (702) 784-6579

NEWARK PUBLIC LIBRARY 5 Washington Street Newark, NJ 07101 (201) 733-7812

UNIVERSITY OF NEW MEXICO Zimmerman Library Government Pub. Dept. Albuquerque, NM 87131 (505) 277-5441

NEW MEXICO STATE LIBRARY Reference Department 325 Don Gaspar Avenue Santa Fe, NM 87501 (505) 827-2033, ext. 22

NEW YORK STATE LIBRARY Empire State Plaza Albany, NY 12230 (518) 474-5563

UNIVERSITY OF NORTH CAROLINA AT CHAPEL HILL Wilson Library BA SS Documents Division Chapel Hill, NC 27515 (919) 962-1321

UNIVERSITY OF NORTH DAKOTA Chester Fritz Library Documents Department Grand Forks, ND 58202 (701) 777-2617, ext. 27 (In cooperation with North Dakota State Univ. Library)

STATE LIBRARY OF OHIO

Documents Department 65 South Front Street Columbus, OH 43215 (614) 462-7051 OKLAHOMA DEPT. OF LIB. Government Documents 200 NE 18th Street Oklahoma City, OK 73105 (405) 521-2502

OKLAHOMA STATE UNIV. LIB. Documents Department Stillwater, OK 74078 (405) 624-6546

PORTLAND STATE UNIV. LIB. Documents Department P.O. Box 1151 Portland, OR 97207 (503) 229-3673

STATE LIBRARY OF PENN.

Government Pub. Section P.O. Box 1601 Harrisburg, PA 17105 (717) 787-3752

TEXAS STATE LIBRARY Public Services Department P.O. Box 12927—Cap. Sta. Austin, TX 78753 (512) 471-2996

TEXAS TECH UNIV. LIBRARY Govt. Documents Department Lubbock, TX 79409 (806) 742-2268

UTAH STATE UNIVERSITY Merrill Library, U M.C. 30 Logan, UT 84322 (801) 750-2682

UNIVERSITY OF VIRGINIA Alderman Lib.—Public Doc. Charlottesville, VA 22901 (804) 924-3133

WASHINGTON STATE LIBRARY Documents Section Olympia, WA 98504 (206) 753-4027

WEST VIRGINIA UNIV. LIB. Documents Department Morgantown, WV 26506 (304) 293-3640

MILWAUKEE PUBLIC LIBRARY 814 West Wisconsin Avenue Milwaukee, Wł 53233 (414) 278-3000

ST. HIST LIB. OF WISCONSIN Government Pub Section 816 State Street Madison. WI 53706 (608) 262-4347

WYOMING STATE LIBRARY Supreme Ct & Library Bld Cheyenne, WY 82002

(307) 777-6344

National Aeronautics and Space Administration

SPECIAL FOURTH CLASS MAIL BOOK Postage and Fees Paid National Aeronautics and Space Administration NASA-451



Washington, D.C. 20546

Official Business Penalty for Private Use, \$300

> 4 I SP-7037, 850521 S90569ASR850630 NASA SCIEN & TECH INFO FACILITY ATTN: ACCESSIONING DEPT P O BOX 8757 BWI ARPRT BALTIMORE MD 21240

NASA

POSTMASTER:

ĩ . 4 If Undeliverable (Section 158 Postal Manual) Do Not Return