

## General Disclaimer

### One or more of the Following Statements may affect this Document

adata, citation and similar papers at [core.ac.uk](https://core.ac.uk)

brought to you by

provided by NASA Technical Re

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

Contract No. NAS 3-22498

(NASA-CR-174268) THE 20 GHZ  
PROOF-OF-CONCEPT TEST MODEL RESULTS FOR A  
MULTIPLE SCAN BEAM DUAL REFLECTOR ANTENNA  
(Ford Aerospace and Communications Corp.)  
15 P HC A02/NF A01

N85-15944

Unclas  
13678

CSCI 17B G3/32

20GHZ PROOF-OF-CONCEPT TEST MODEL RESULTS FOR A  
MULTIPLE SCAN BEAM DUAL REFLECTOR ANTENNA

BY

T. Roberts, A. Smoll, H. Luh, E. W. Matthews, W. G. Scott

FORD AEROSPACE & COMMUNICATIONS CORPORATION  
WESTERN DEVELOPMENT LABORATORIES

PALO ALTO, CALIFORNIA 94303

Presented at: IEEE Antenna  
Propagation Symposium  
Houston, Texas  
May 23 - 27, 1983


8/83

12/21/83  
5/11/83  
K...


#### ABSTRACT

Under Contract NAS 3-22498, NASA Lewis Research Center, we have designed, fabricated, and are testing a full scale 20 GHz antenna model. The model is intended to test the low side-lobe beam scanning capability of a new class of an offset dual reflector and feed array configuration. The offset main reflector and subreflector surfaces were custom shaped by a computer synthesis procedure. The optics so derived results in beam scan loss under 1 db over the  $\pm 12.3$  beamwidths by  $\pm 5.8$  beamwidths scan volume while maintaining low sidelobes. The preliminary test results indicate that the measured and computed patterns are in good agreement.

# CLUSTER EXCITATION FOR THREE BEAM POSITIONS IN CONUS FEED ARRAY



# NASA 30/20 GHz REFLECTORS AND FEED CONFIGURATION



 Ford Aerospace &  
Communications Corporation

## KEY FEATURES

### Shaped-Surface Cassegrain Reflector System

- Minimal ( 0.5 dB) gain loss over  $\pm 12$  beamwidths (0.3° of scan)
- Preservation of low sidelobes at wide scan angles ( 30 dB scan beam isolation)
- Development of antenna synthesis and analysis computer programs (including GTD)


### Unique Beamforming/Switching Feed Networks

- Utilizes multi-element clusters to minimize cross-polarization and sidelobes
- Beam selection performed by variable power dividers and ferrite switches
- Fast switching time,  $< 6.0 \mu\text{s}$




Ford Aerospace &  
Communications Corporation

# POC MODEL MBA




Ford Aerospace &  
Communications Corporation



Ford Aerospace &  
Communications Corporation


ORIGINAL PAGE IS  
OF POOR QUALITY






Ford Aerospace &  
Communications Corporation


ORIGINAL PAGE IS  
OF POOR QUALITY




 Ford Aerospace &  
Communications Corporation

ORIGINAL PAGE IS  
OF POOR QUALITY


# NASA 30/20 GHz SCAN BEAM PRIMARY PATTERN SINGLE AND 7-ELEMENT E-PLANE 19.1 GHz



# NASA 30/20 GHz SCAN BEAM PRIMARY PATTERN SINGLE AND 7-ELEMENT H-PLANE 19.1 GHz



# NASA 30/20 GHz SCAN BEAM PRIMARY PATTERN SINGLE AND 7-ELEMENT 45° PLANE 19.1 GHz




WASA 30 20 002 USA  
Dist = 109  
 $V_p = 0, Y_p = 0$   
Measured AZ Pattern


10


20 (dB)

ORIGINAL PAGE IS  
OF POOR QUALITY

30







ORIGINAL PAGE IS  
OF POOR QUALITY