

*1984-140 p12*

DOE/NASA/0084-1  
NASA CR-168292

NASA-CR-168292  
19840011117

# Optimization Methods Applied to Hybrid Vehicle Design

John F. Donoghue and James H. Burghart  
Department of Electrical Engineering  
Cleveland State University

**June 1983**

**LIBRARY COPY**

MAR 8 1984

LANGLEY RESEARCH CENTER  
LIBRARY, NASA  
HAMPTON, VIRGINIA

Prepared for  
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION  
Lewis Research Center  
Under Grant NAG 3-84

for  
**U.S. DEPARTMENT OF ENERGY**  
**Conservation and Renewable Energy**  
**Office of Vehicle and Engine R&D**

## DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Printed in the United States of America

Available from

National Technical Information Service  
U.S. Department of Commerce  
5285 Port Royal Road  
Springfield, VA 22161

NTIS price codes<sup>1</sup>

Printed copy: A09

Microfiche copy: A01

<sup>1</sup>Codes are used for pricing all publications. The code is determined by the number of pages in the publication. Information pertaining to the pricing codes can be found in the current issues of the following publications, which are generally available in most libraries: *Energy Research Abstracts (ERA)*; *Government Reports Announcements and Index (GRA and I)*; *Scientific and Technical Abstract Reports (STAR)*; and publication, NTIS-PR-360 available from NTIS at the above address.

14

1

1 RN/NASA-CR-168292

DISPLAY 14/2/1

84N19185\*\* ISSUE 9 PAGE 1406 CATEGORY 85 RPT#: NASA-CR-168292  
DOE/NASA-0084/1 NAS 1.26:168292 CNT#: MAG3-84 DE-AI01-77CS-51044  
83/06/00 180 PAGES UNCLASSIFIED DOCUMENT

UTTL: Optimization methods applied to hybrid vehicle design TLSP: Final Report

AUTH: A/DONOGHUE, J. F.; B/BURGHART, J. H.

CORP: Cleveland State Univ., Ohio. CSS: (Dept. of Electrical Engineering.)

AVAIL.NTIS SAP: HC A09/MF A01

MAJS: /\*ELECTRIC MOTOR VEHICLES/\*HYBRID PROPULSION/\*OPTIMIZATION

MINS: / DESIGN ANALYSIS/ PROPULSION SYSTEM CONFIGURATIONS/ RUN TIME (COMPUTERS)

ABA: Author

ABS: The use of optimization methods as an effective design tool in the design of hybrid vehicle propulsion systems is demonstrated. Optimization techniques were used to select values for three design parameters (battery weight, heat engine power rating and power split between the two on-board energy sources) such that various measures of vehicle performance (acquisition cost, life cycle cost and petroleum consumption) were optimized. The approach produced designs which were often significant improvements over hybrid designs already reported on in the literature. The principal conclusions are as follows. First, it was found that the strategy used to split the required power between the two on-board energy sources can have a significant effect on life cycle cost and petroleum consumption. Second, the optimization program should be constructed so

ENTER:

---

DOE/NASA/0084-1  
NASA CR-168292

## **Optimization Methods Applied to Hybrid Vehicle Design**

John F. Donoghue and James H. Burghart  
Department of Electrical Engineering  
Cleveland State University  
Cleveland, Ohio

June 1983

Prepared for  
National Aeronautics and Space Administration  
Lewis Research Center  
Cleveland, Ohio 44135  
Under Grant NAG 3-84

for  
U.S. DEPARTMENT OF ENERGY  
Conservation and Renewable Energy  
Office of Vehicle and Engine R&D  
Washington, D.C. 20545  
Under Interagency Agreement DE-AI01-77CS51044

N84-19185#



TABLE OF CONTENTS

	Page
1.0 SUMMARY . . . . .	1
2.0 INTRODUCTION . . . . .	4
2.1 Research Objectives . . . . .	4
2.2 Previous Work . . . . .	5
2.3 Major Tasks . . . . .	6
2.4 Report Organization . . . . .	7
3.0 VEHICLE DESCRIPTION AND OPERATION. . . . .	8
3.1 Propulsion System . . . . .	8
3.2 Vehicle Operation and Ratio Selection . . . . .	10
3.3 Power Split Strategy. . . . .	11
4.0 VEHICLE DRIVING REQUIREMENTS . . . . .	13
5.0 ENERGY AND COST CALCULATIONS . . . . .	16
5.1 Yearly Electrical Energy Consumption. . . . .	16
5.2 Yearly Petroleum Consumption. . . . .	17
5.3 Life Cycle Cost Calculation . . . . .	18
6.0 VEHICLE SIMULATION . . . . .	22
6.1 General Computational Procedure and Trip Characteristics Design . . . . .	22
6.2 Simulation Time Increment Selection . . . . .	25
6.3 Power Overload . . . . .	25
6.4 Other Features of the Simulation . . . . .	28
7.0 OPTIMIZATION AS A DESIGN TECHNIQUE . . . . .	30

	Page
8.0 THE VEHICLE DESIGN PROBLEM AS AN OPTIMIZATION PROBLEM. . . . .	33
9.0 SELECTION OF OPTIMIZATION METHOD . . . . .	37
10.0 IMPLEMENTATION OF THE GRG PROGRAM FOR VEHICLE DESIGN PROBLEMS. . . . .	39
11.0 RESULTS AND DISCUSSIONS OF RESULTS . . . . .	43
11.1 Vehicle Power Source Sizing for Minimum Life Cycle Cost. . . . .	43
11.2 Vehicle Power Source Sizing for Changing Petroleum Costs . . . . .	46
11.3 Vehicle Power Source Sizing to Minimize Total Petroleum Consumption. . . . .	48
11.4 Power Split Optimization . . . . .	52
11.4.1 Parameterized AiResearch Power Split Function. . . . .	54
11.4.2 Polynomial Power Split Function . . . . .	55
11.5 Summary of Results . . . . .	57
12.0 CONCLUSIONS. . . . .	59
APPENDIX A - DICTIONARY OF VARIABLES . . . . .	62
APPENDIX B - CALCULATION OF VEHICLE MASS . . . . .	83
APPENDIX C - CALCULATION OF MANUFACTURING, MAINTENANCE AND REPAIR COSTS . . . . .	86
APPENDIX D - CALCULATION OF ACQUISITION COST . . . . .	90
APPENDIX E - VEHICLE SIMULATION . . . . .	91



	Page
E.1 Component Models. . . . .	91
E.2 Calculation of Power Required at the Axle During the Acceleration and Cruise Phases of the STC and During Highway Driving. . . . .	98
E.3 Drive Train Power Calculations for Acceleration and Cruise Phases of STC and for Highway Driving. . . . .	99
E.4 Calculation for Coasting Phase of the STC . . . . .	103
E.5 Calculation of Drive Train Power Regeneration During the Braking Phase of the STC . . . . .	103
APPENDIX F - BATTERY MODEL . . . . .	106
F.1 Scaling the Battery Model . . . . .	106
F.2 Calculation of Battery Voltage and State of Charge During Discharge in Highway Driving and in the Acceleration and Cruise Phases of an STC . . . . .	106
F.3 Battery Charging at End of Trip . . . . .	110
F.4 Calculation of Battery Voltage and State of Charge During Regeneration in the Braking Phase of an STC. . . . .	112
APPENDIX G - CVT RATIO SELECTION PROCEDURE . . . . .	114
APPENDIX H - AIRESEARCH POWER SPLIT STRATEGY . . . . .	121
APPENDIX I - COMPUTER PROGRAMS . . . . .	122
REFERENCES . . . . .	172



## 1.0 SUMMARY

The overall objective of this work was to demonstrate the use of optimization methods as an effective design tool in the design of hybrid vehicle propulsion systems.

Specifically, optimization techniques were used to select values for three design parameters (battery weight, heat engine power rating and a parameter through which the required wheel power at each time instant was split between the two on-board energy sources) such that various measures of vehicle performance were optimized. The performance measures considered were acquisition cost, life cycle cost, petroleum consumption, or various weighted combinations of these. For specific values of the design parameters, vehicle performance was determined using a vehicle simulation. The optimization was carried out by coupling the simulation to a sophisticated, nonlinear programming code (GRG2) and running the two in combination.

The optimization approach was successful in coming up with designs which were often significant improvements over hybrid designs already reported on in the literature. Furthermore, it was found that the strategy used to split the required wheel power between the two on-board energy sources can have a significant effect on life cycle cost and petroleum consumption. More importantly, however, the work showed that it is quite feasible to couple a complex optimization program to a vehicle simulation program for the purpose of propulsion system design. It was also found that the optimization program should be constructed so that performance measures and/or design variables can be easily changed; in the conduct of the research it was often desirable to compare, say, the minimum life cycle cost design to the minimum petroleum

consumption design.

Another area in which important results were obtained was in understanding the effect the vehicle simulation program design has on both the computer run time of the overall optimization program and on the ability of the optimization program to even arrive at a meaningful solution. First, it was found that the computer run time could be significantly reduced by proper design of the types of trips the vehicle takes in a one year period. Specifically, if a trip consists of a combination of test cycles (accelerate-cruise-coast-brake cycles) and highway driving, then it is important that all the test cycles precede the highway driving, and that the same number of cycles are at the front end of each trip, no matter how long the trip.

Second, it was found that care must be taken in designing the cost and constraint expressions which are being used in the optimization so that they are relatively smooth functions of the design variables. Otherwise, the function surfaces may be severely distorted and create many local minima which will prevent the program from even approaching the global minimum. This is particularly true with regard to how the battery replacement cost is handled.

Finally, it was found that proper handling of constraints on battery weight and heat engine rating is particularly important for the success of an optimization study. These design variables cannot be allowed to be reduced to the point where the combined on-board power cannot meet the power demanded at the wheels. It was found that the way in which this "overload" constraint is handled strongly influences whether an optimization run gets "hung-up" at a non-optimal solution or finds the constrained, global optimum.

The principal conclusion reached from this research is that optimization methods provide a practical tool for carrying out the design of the

propulsion system of a hybrid vehicle. Once the optimization program and the vehicle simulation are combined and operating, it is relatively easy to change objective functions and/or design variables so that designs based on different performance criteria (e.g. minimum life cycle cost design v.s. minimum petroleum consumption design) or different driving conditions, component characteristics or propulsion system configurations can be quickly carried out and compared. Use of optimization methods also force designers to make explicit their objective functions and constraints; thus designs carried out by different researchers are more readily and meaningfully compared.

This work has also lead to the conclusion that the way in which the demanded power at any instant of time is split between the two on-board power sources has a significant impact on vehicle cost and petroleum consumption. Although some preliminary results in this area are presented in this report, it would appear that future hybrid vehicle work should look at this question of power split on a more systematic basis.

## 2.0 INTRODUCTION

The energy crisis, dramatized by the oil embargo of 1973, has become one of the most serious long-term problems confronting the United States. In response to this crisis there has been a significant increase in the research and development of electric and hybrid vehicles in an attempt to reduce our dependence on foreign oil. The work discussed in this report is a part of that on-going effort.

### 2.1 RESEARCH OBJECTIVES

The primary objective of this work was to study the use of optimization methods for the design of propulsion systems for hybrid vehicles. The term hybrid vehicle as used in this report means a vehicle which contains a heat engine and gas tank as well as an electric motor and batteries. The configuration used here was a parallel hybrid with a continuously variable transmission. Of particular interest in this work was determining the ease or difficulty with which a sophisticated, nonlinear programming algorithm could be coupled to a vehicle simulation program for purposes of optimally designing the vehicle propulsion system. The design variables were heat engine power rating, the weight of the on-board batteries, and a parameter through which the power required at the wheels at each time instant was split between the two on-board power sources. The study considered optimizing various vehicle performance measures to determine how different performance measures influenced the final propulsion system design. The performance measures used were acquisition cost, life cycle cost, and petroleum consumption.

## 2.2 PREVIOUS WORK

There have been no studies reported in the literature which attempt a vehicle propulsion system design using optimization methods. Two recent studies [1,2] have looked at different aspects of the design of various types of hybrid vehicles. In each case, however, a final design is arrived at using a sound, but nevertheless ad hoc, selection process. Furthermore, the performance measure used to guide the selection is often not clearly stated, is modified or changed in the middle of a study, or is quite different from study to study. These factors combine to make it difficult to compare the results of one study to those of another. In contrast to this, use of optimization methods force standardization by requiring a designer to explicitly state the performance measure to be used, and to maintain the same measure in effect throughout the process of selecting final values for the design variables. Furthermore, with an optimization approach the selection process itself is standardized, and it also generally identifies the "best" values for the design variables so that the performance measure used is optimized (maximized or minimized, whichever is appropriate).

From the perspective of previous work on the problem of hybrid vehicle propulsion system design therefore, the work reported here represents the first time an attempt has been made to apply optimization methods to the design problem in order to come up with what may be considered the best or "optimal" design.

### 2.3 MAJOR TASKS

The conduct of the research fell naturally into a group of major tasks which are listed below:

1. Development of a vehicle simulation to be used to predict petroleum and electrical energy consumption as the vehicle is driven over the specified driving pattern. These consumptions provide a basis for computing overall performance measures such as life cycle cost.
2. Selection of a nonlinear programming algorithm (and associated program) which will be used to perform the optimization calculations.
3. Coupling the vehicle simulation program to the optimization program to allow optimal propulsion system designs to be carried out. In carrying out an optimal design calculation, the optimization program must run the simulation repeatedly. Consequently, a good deal of the work involved in coupling the two programs is in tailoring the vehicle simulation so that it runs efficiently, and so that vehicle performance is a smooth function of the design variables.
4. Translating various design goals into optimization problems. For each design goal this would include specifying (i) the system performance measure to be optimized, (ii) the design variables, and (iii) the proper constraints.



5. Generation and analysis of results using the combined optimization/vehicle simulation program.

In the sections which follow, each of the major task areas outlined above will be considered in depth.

## 2.4 REPORT ORGANIZATION

The report is organized as follows. Sections 3 through 6 present detailed information about the vehicle and its simulation. In particular, Sections 3 and 4 describe the vehicle and its propulsion system as well as the vehicle's basic method of operation along with the driving requirements it must meet over a ten year period. Section 5 details the way in which the various vehicle performance measures (life cycle cost, etc.) are calculated, while Section 6 describes the vehicle simulation.

The optimization design approach as it relates to hybrid vehicles is covered in Sections 7 through 9. Section 7 presents a general discussion of optimization methods which is useful background for subsequent sections. Section 8 deals with formulating hybrid vehicle design problems as optimization problems, while Section 9 describes some of the features of the actual optimization algorithm used in the study, as well as the reasons for its selection.

Section 10 discusses how the vehicle simulation program and optimization program were combined, and Section 11 presents and discusses particular vehicle design problems and the results obtained using the optimization approach; conclusions are presented in Section 12.

### 3.0 VEHICLE DESCRIPTION AND OPERATION

The vehicle selected to be studied in this research was essentially the same as the vehicle studied in [1]; it is a five-passenger sedan with a test mass of 2,049 kg. The details of the vehicle weight calculations are given in Appendix B.

#### 3.1 PROPULSION SYSTEM

The propulsion system is a parallel hybrid configuration as shown in Figure 3-1. The traction motor is a brushless, DC, permanent-magnet motor operating from a battery voltage of 168 V. The motor is rated at 20 kw and has a top speed of 14,000 rpm. The output of the motor is connected to the transmission input through a gear which provides a 3.5:1 reduction of the motor speed.

The heat engine is assumed to be a four cylinder engine. Since in the optimization work the kilowatt rating of the engine is a design parameter which is varied, no specific rating for the engine is given. However, in the optimization studies that were conducted, the heat engine would normally start out at a rating of 65 kw. The output of the heat engine is directly connected to the input of the transmission (no speed reduction).

The transmission is a continuously variable transmission (CVT) which provides a range of ratios (input/output) from a 0.3:1 overdrive to a 3.33:1 speed reduction. The output of the CVT feeds the differential through a 12:1 speed reducer. The differential is assumed to have a ratio of 1:1. Thus, if the traction motor was running at its maximum speed of 14,000 rpm, and the CVT ratio was 0.3:1, the differential input would have a speed of 1,111 rpm.




Figure 3-1. Propulsion System Configuration

The batteries are assumed to be lead-acid batteries with a system voltage of 168 V. In the optimization runs in which the battery weight was varied it was assumed that the system voltage remained the same and that a variation in battery weight meant the plate area of the battery cells was increased or decreased. A detailed description of the battery model used in the vehicle simulation is given in Appendix F.

Finally, it was assumed that a clutch existed between the heat engine and the CVT input to allow the heat engine to be decoupled from the system when it was not supplying power.

Section 6 and Appendix E (Vehicle Simulation) provide a detailed description of the simulation and the models used for all of the components in the propulsion system. Reference to that section and that appendix can give the reader a more thorough understanding of the components, their interrelationships, and how typical power consumption calculations were made.

### 3.2 VEHICLE OPERATION AND RATIO SELECTION

In order to avoid engine stalling, it was assumed that when the vehicle was starting from rest all power was supplied by the traction motor until the vehicle speed reached 4.82 km/hr (3.0 mph).

Whenever the vehicle was to brake to slow down, it was assumed that regenerative braking was used to the extent possible. If the maximum power rating of a component limited the fraction of the available power which could be regenerated, then it was assumed that normal braking was used to dissipate the excess energy.

In the early stages of the work, the CVT ratio was selected such that as the vehicle speed changed, the traction motor always ran at its most

efficient operating speed. The disadvantage of this approach in the hybrid propulsion system studied is that the heat engine speed is also determined by the CVT ratio, and a ratio that operates the traction motor most efficiently often operates the heat engine very inefficiently. In fact, it was found that the traction motor efficiency is always in the 90% or above range independent of the ratio, whereas the heat engine efficiency can often be substantially improved by proper choice of the ratio. For this reason the CVT ratio was always selected to maximize the heat engine efficiency (except when the heat engine was not delivering any power). We note that a better approach might have been to base the ratio selection on the amount of power each source is delivering, as well as on the relative efficiency improvement possible from each source. A detailed description of the ratio selection procedure, along with the engine and traction motor data used, is given in Appendix G.

### 3.3 POWER SPLIT STRATEGY

In order to operate a hybrid propulsion system it is necessary to specify a strategy for splitting the required wheel power between the two power sources. The power split strategy must operate continuously, deciding at each instant of time how the total power is to be split. A realistic strategy generally is a function of vehicle velocity and acceleration, and battery state of charge.

An important part of this research was to use optimization methods to identify "optimal" strategies, or to select optimal values for parameters in a given strategy based on common sense. An example of a common-sense strategy which has been reported in the literature is the strategy proposed

by AiResearch [1]. The AiResearch (AR) strategy is often used in the work discussed in the following sections; for this reason it is described in detail in Appendix H.

#### 4.0 VEHICLE DRIVING REQUIREMENTS

In order to compute petroleum or electrical energy consumption (important factors in themselves, but also important factors in computing life cycle cost) it is necessary to specify how the vehicle is to be driven over its ten year life. Table 4-1 lists the lengths of eight different trip types for the vehicle, as well as the number of times the vehicle takes each trip type in one year.

Some portion of every trip is composed of Special Test Cycle (STC) driving. The STC is shown in Figure 4-1 and is a modified SAE J227A, D cycle; it contains a 14 second constant power acceleration period, followed by a 50 second, 72 km/hr (45 mph) cruise period, a 10 second coast period, and a 9 second braking period. Referring to Table 4-1, trips 1, 2 and 3 (trips less than 80 km in length) are made up of just a sequence of STC's, while trips 4 through 8 are made up of a combination of STC's and highway driving. Each of these latter trips consists of 28 STC's followed by enough highway driving to reach the total trip length. Highway driving is constant speed driving at 90 km/hr (56 mph).

The structuring of the longer trips to consist of a fixed number of STC's followed by varying lengths of highway driving had a big impact on reducing the computer run time of the overall vehicle simulation/optimization program. This is discussed in detail in Section 6 which deals with the vehicle simulation.

Table 4-1

Yearly Distribution of Trips

<u>Trip Length</u>		<u>Number of Trips</u>
<u>Km</u>	<u>Mi</u>	<u>Per Year</u>
10	6.2	130
30	18.6	85
50	31.1	57
80	49.7	54
130	80.8	12
160	99.4	7
500	311.0	3
800	497.0	1






Figure 4-1. Special Test Cycle

## 5.0 ENERGY AND COST CALCULATIONS

This section details the methods used to calculate the yearly electrical energy consumption, yearly petroleum consumption and life cycle cost.

### 5.1 YEARLY ELECTRICAL ENERGY CONSUMPTION

The yearly electrical energy consumption calculation is based on first determining the total ampere-hours out of the battery for each of the trip types described in the previous section. The battery charging characteristic is then used to determine the energy required to replace those amp-hours (including a charging efficiency). Each of these results is multiplied by the number of such trips each year for each trip type, and the results then added to produce the total yearly electrical energy consumption. The details of the calculation are given below.

As explained in Section 6 on the vehicle simulation, it is necessary when calculating the electrical energy and petroleum consumptions for a particular trip to calculate the powers delivered by the battery and the heat engine at each time instant throughout the entire trip; it is not reliable, in general, to do it for just a few STC's and a segment of highway driving and then extrapolate the results for the entire trip. In the simulation, a small time step size is used and, for the electrical energy calculation, at each time increment in the trip the battery model is used to determine the battery voltage, current and state of charge for the power that must be delivered to the motor in that time increment (the calculation takes into account the chopper/inverter efficiency). In this way a total net amp-hours out of the battery for each trip type is determined: the total net amp-hours

out includes the effect of regenerating capacity back into the battery during the braking phase of each STC. This total net capacity removed, together with an assumed charging current of 25 amps, is used to determine an average charging voltage from the battery charging characteristic (Appendix F). The average charging voltage is then multiplied by the total net capacity removed to determine the total energy that must be restored to the battery to bring it to a fully charged condition. Finally, to determine the total wall-plug energy, the above total energy is divided by a charger efficiency factor. This calculation is done for each trip type. The total, yearly electrical energy consumed is finally calculated by multiplying the energy consumed for each trip type by the number of such trips per year, and then adding these results.

If we let  $AH_i$ ,  $i=1, \dots, 8$ , be the net amp-hours out of the battery for trip type  $i$ ,  $V_i$  be average charging voltage to fully charge the battery after delivering  $AH_i$  amp-hours,  $EFF$  be the charger efficiency,  $N_i$  be the number of trips of type  $i$  made in one year, then the total, yearly electrical energy consumed,  $E_{TOT}$ , in megajoules, is given as

$$E_{TOT} = (3600/10^6) \sum_{i=1}^8 (N_i AH_i V_i / EFF) \quad (5-1)$$

## 5.2 YEARLY PETROLEUM CONSUMPTIONS

As noted above, when calculating electrical energy and petroleum consumptions it is necessary to calculate the powers delivered by the battery and heat engine at each time instant throughout the entire trip. In the simulation, the power delivered by the heat engine, the engine speed and the

torque at each time instant are determined. The heat engine map (Appendix E) is then used to determine the fuel flow rate into the heat engine; multiplying this flow rate by the simulation time increment gives the fuel consumed over that time increment.

The procedure used to calculate the total, yearly petroleum consumption parallels the one used for electrical energy consumption: the total petroleum consumed for each trip type is determined by adding the fuel consumed over each time increment in the trip, these are multiplied by the number of trips of each trip type made per year, and the results then summed to produce the total petroleum consumption per year.

### 5.3 LIFE CYCLE COST CALCULATION

The life cycle cost is the sum of the vehicle acquisition cost, the petroleum, electrical energy, maintenance and repair, and battery replacement costs over a ten year period, minus the salvage value of the battery, the vehicle body and the power train.

It is assumed that the costs of petroleum and electricity increase in a linear fashion from year one to year ten. The arrays containing this information are GASCST(I) and KWCST(I); the particular values used are given in Appendix A.

Life cycle cost is computed in 1976 dollars, and it is assumed that there is no inflation. The cost for a future year is discounted to a present value using a discount factor (DISCNT in Appendix A).

The salvage value of the vehicle body and power train is taken to be 10% of the marked-up manufacturing cost, i.e. 10% of the difference between the acquisition cost and the list price of the battery ( $0.1*(ACQCST-BTLIST)$ ), see

Appendix A for definitions of variables).

The years in which a battery replacement is required depend upon the battery weight and the way in which the battery and heat engine are used. In calculating battery life it was assumed that there were 840 deep discharges in the lifetime of a battery [1], where a deep discharge is defined to be a discharge to 20% state of charge or below. The calculation procedure was to determine how far the battery was discharged when the vehicle made each of the trips defined in Section 4 (this was determined during the simulation of the vehicle to determine petroleum and electrical energy consumptions). If the battery state of charge dropped to only, say, 40% at the end of a particular short trip, then that trip represented 75% of a deep discharge. In this way the total number of deep discharges of the battery per year was determined and used to calculate the number of years in the battery life. If the battery state of charge fell below 20% during the part of a trip in which STC driving was being performed, regeneration back into the battery and subsequent use of the battery until its state of charge again fell below 20% was allowed, but only one deep discharge was attributed to that trip. The battery replacement cost had a mark-up factor which was twice that used in calculating the initial cost of the battery. The expression used to determine the replacement cost is

$$\text{BTCOST} = \text{BATCST} * (1.0 + 2.0 * \text{BTMKUP}) \quad (5-2)$$

where

$$\text{BATCST} = \text{BATCER} * \text{WGBATT} \quad (5-3)$$

and where (see Appendix A) WGBATT, BATCER, BATCST, BTMKUP and BTCOST are battery weight, cost estimating ratio (CER), manufacturing cost, mark-up

factor and replacement cost, respectively. The way in which the battery replacement cost was used in calculating life cycle cost was influenced by the method used to handle battery salvage value. In particular, battery salvage value was taken to be the cost of the last battery replacement multiplied by the ratio of the number of years left in the battery (at the end of the ten year vehicle lifetime) to the number of years in the battery life. Furthermore, instead of adding the total battery replacement cost to the year in which the replacement took place, each replacement cost was evenly distributed over the ten years in the lifetime of the vehicle. Although this is not quite representative of what would actually take place, it was necessary in order to produce a life cycle cost expression for the optimization studies which was a relatively smooth function of battery replacement cost. Furthermore, if it is assumed that the vehicle owner meets the battery replacement cost by borrowing money which is paid back over several years, then the above approach begins to more closely approximate reality. Based on the above discussion, the battery replacement cost assigned to each year in the ten year lifetime of the vehicle is given by

$$\text{BATRYR} = \{[10.0/\text{BATLFE})-1.0\}*\text{BTCOST}/10.0 \quad (5-4)$$

where

$$\text{BATLFE} = \text{DISLFE}/\text{DEEP} \quad (5-5)$$

where  $\text{BTCOST}$  is as calculated above, and where  $\text{BATRYR}$ ,  $\text{BATLFE}$ ,  $\text{DISLFE}$  and  $\text{DEEP}$  are battery cost assigned to each year, battery lifetime, number of deep discharges in the battery lifetime, and the number of deep discharges per year, respectively.

Based on the discussion above, in Sections 5.1 and 5.2 and in Appendices C and D, the total yearly cost for operating the vehicle in year  $i$  is (see Appendix A for complete definitions of the variables)

$$\begin{aligned} \text{VHCOST}_i = & E_{\text{TOT}} * \text{KWCST}_i + P_{\text{TOT}} * \text{GASCST}_i + \text{BATRYR} \\ & + \text{MAINT} + \text{REPAIR} \end{aligned} \quad (5-6)$$

where  $E_{\text{TOT}}$  and  $P_{\text{TOT}}$  are the yearly electrical energy and petroleum consumed, respectively,  $\text{KWCST}_i$  and  $\text{GASCST}_i$  are the cost factors, and MAINT and REPAIR are the maintenance and repair costs, respectively. Letting the salvage value of the vehicle body and power train be (see above)

$$\text{SALVGE} = 0.1 * (\text{ACQCST} - \text{BTLIST}) \quad (5-7)$$

and the discount factor for year  $i$  be

$$D_i = (1.0 + \text{DISCNT})^{(i-1)} \quad (5-8)$$

where DISCNT is the discount rate, the life cycle cost is given as

$$\text{LCCOST} = \text{ACQCST} + \sum_{i=1}^{10} (\text{VHCOST}_i / D_i) - (\text{SALVGE} / D_{11}) \quad (5-9)$$

## 6.0 VEHICLE SIMULATION

In the optimization studies the vehicle simulation was used primarily to calculate the electrical energy and petroleum consumed by the vehicle in a one year period. Appendix E presents a detailed description of the modeling of the vehicle (the vehicle is described in general terms in Section 3) and of the way in which the petroleum and the electrical energy consumption was determined at each instant of time in the simulation interval. Section 5 describes the way in which these individual consumptions were used to calculate the yearly consumptions. The objective of this section is to discuss a number of features of the vehicle simulation effort (other than vehicle modeling) which were considered to have a significant impact on the simulation run time, on the outcome of optimization runs, or which represented particular features of vehicle operation which should be made explicit.

### 6.1 GENERAL COMPUTATIONAL PROCEDURE AND TRIP CHARACTERISTICS DESIGN

The purpose of this subsection is to describe the overall computational procedure used to calculate the fuel and energy consumptions for each trip in Table 4-1, and then to discuss how the structuring of these trips (STC and highway driving) can have a significant impact on simulation run time.

As discussed in Section 4, each trip to be simulated is either a sequence of just STC's or a combination of 28 STC's followed by varying lengths of highway driving. Since in this study the power split was allowed to vary with battery state of charge and/or vehicle acceleration, the power supplied by either on-board energy source could vary significantly from one part of a trip to another, particularly on those trips which depleted the



battery. In the case of a depleted battery, the electrical energy supplied over the final STC would be zero, whereas that supplied over the first STC would be non-zero. Because of this, it was necessary to simulate the vehicle over the entire trip length for all trips: the fuel and energy consumption could not be calculated for one STC and a segment of highway driving, and then multiplied by appropriate factors to arrive at trip totals.

The calculation procedure used is as follows. The longest all STC trip is 35 consecutive STC's. The simulation was therefore run for 35 consecutive STC's, and the "state" of the vehicle at the end of each STC was saved. By "state" is meant all the vehicle quantities necessary to resume the calculation from that point forward in time (petroleum consumed, battery amp-hours out and regenerated, state of charge, voltage, instantaneous and average currents, and whether the battery has discharged by the end of that STC). Knowing these quantities at the end of each STC, the fuel and energy consumption for trips consisting of just STC's (trips 1, 2, 3 in Table 4-1) can be calculated from simulating just the longest all-STC trip (trip 3).

To calculate the consumptions for trips involving highway driving, the simulation was initialized by the information saved at the end of the 28th STC, and highway driving was begun (in this way the 28 STC's preceeding highway driving need not be resimulated). At each time step in highway driving a test was made to determine if the shortest STC and highway trip had been completed; if so, the consumptions for that trip were computed and highway driving resumed until the next trip in Table 4-1 was completed. In this way, consumptions for all trips consisting of STC's and highway driving can be calculated by simulating just the longest trip (trip 8, Table 4-1).

The above calculation procedure where fuel and energy consumptions for all highway trips can be calculated from the longest trip depends on all highway trips having all of their STC's in the front of the trip, and all having the same number of STC's up front. If either of these conditions is changed, it would become necessary to simulate each trip separately. This could represent a significant increase in simulation run time. For example, the time step size in simulating STC driving is 1 second, and that used in simulating highway driving is 60 seconds (see Section 6.2). Since each STC is 83 seconds long, and there are 35 STC's in the longest all-STC trip, the total number of drive train power calculations required for trips 1, 2 and 3 in Table 4.1 is  $(1 \times 83 \times 35) = 2,905$ . The longest highway trip is 759 km of highway driving, driven at 90 km/hr, or a highway driving time duration of 8.44 hrs. A 60 second simulation time step would therefore require 506 additional power train calculations for all of the highway trips (trips 4 through 8), yielding a total of 3,411 calculations. If each highway trip had to be simulated separately (including the 28 STC's since they could be split differently between the beginning and end of each trip), the 28 STC's for the 5 highway trips would require a total of  $(5 \times 28 \times 83) = 2,324$  computations, and the highway parts of trips 4 through 8 would require 26, 60, 80, 306, and 506 computations, respectively. The total number of computations would therefore be  $(26 + 60 + 80 + 306 + 506 + 2,324 + 2,905) = 6,207$ . Compared to the above total of 3,411, it is seen that the number of drive train power computations has almost doubled. Since these computations are by far the major computational burden of the simulation, and since the computation time is large to begin with, it is important to design the driving pattern so that computational efficiencies can be achieved.

## 6.2 SIMULATION TIME INCREMENT SELECTION

Another important factor in determining the length of time it takes the simulation to run is the time step size used in STC and highway driving. Since in a typical optimization run the yearly fuel and energy consumptions are computed 30 to 50 times, the choice of the time step size has a significant effect on overall computer run time.

Separate time step sizes were used for STC driving and highway driving: since highway driving is at a constant velocity, it was felt that a larger step size could be used without missing significant changes in the vehicle state (e.g. battery state of charge).

The time step sizes were selected by trying various values and observing the effects on petroleum consumption, electrical energy consumption and life cycle cost. In particular, the time step sizes were increased until a meaningful change in any of the above three quantities was observed; the values selected were set just below the values that produced a change. The STC time step size used was one second, and the time step size for highway driving was 60 seconds.

## 6.3 POWER OVERLOAD

One of the most frequent optimization problems studied was to choose battery weight and heat engine rating to minimize life cycle cost. Without constraints on this problem the answer would be to set both design variables to zero. Of course, the vehicle would then not be able to meet the yearly driving requirements. In this research, the condition in which both power sources were reduced in size to the point where they could not supply the power required at the wheels was called power overload. This condition could

occur at any time in the yearly driving pattern, and it could occur for various combinations of heat engine rating and battery weight. The overload condition was handled in the optimization work by incorporating it as a constraint: combinations of battery weight and heat engine rating which produced overload were considered infeasible.

One method (which did not work) of handling this constraint was to set a flag if an overload condition occurred anywhere in the yearly driving patterns. This flag would indicate to the optimization scheme that the current choices for the design variables were infeasible, and new values would be tried. The problem with this method was that the constraint was a discontinuous (step) function of the design variables, and if it was violated the optimization method (GRG2) would attempt to find exactly where, in the current search direction (see Section 7), the constraint was just satisfied. This attempt (using Newton's Method for finding the roots of an equation) would fail and the optimization scheme could not determine a useful, new search direction to locate the optimum.

In an attempt to visualize the shape of the constraint in the battery weight/heat engine rating plane, a series of simulation runs were made in the region of the constraint boundary (varying battery weight and heat engine rating for each run, and using the AiResearch power split (see Section 3.3 and Appendix H)). The result is shown in Figure 6-1 where it is seen that the constraint boundary is highly irregular. Even if the optimization method could find the boundary (for a particular search direction), once it began to move along the boundary it would get hung up at one of the many local minima.




Figure 6-1. Overload Constraint Boundary

The method finally adopted for handling the constraint was to approximate it with two smooth curves as shown in Figure 6-1. For these smooth constraint functions the optimization scheme can easily find the location of the constraint boundary in a given search direction, and it can also move easily along the constraint boundary in search of the optimum. If we let  $x_1$  = battery weight (kg), and  $x_2$  = heat engine rating (kw), then the constraint equations are given as

$$P_{HE} > 37.0 - 0.02564 W_B \quad (W_B < 273) \quad (6-1)$$

$$P_{HE} > 77.23 - 0.2268 W_B + 1.982 \times 10^{-4} W_B^2 \quad (W_B > 273) \quad (6-2)$$

The justification for using this approximate constraint boundary is that in any optimization study which chooses battery weight and heat engine rating to minimize life cycle cost, the objective is not necessarily to arrive at a design which just borders on overload. Having the small "cushion" above overload that use of the approximate constraint produces could be beneficial.

#### 6.4 OTHER FEATURES OF THE SIMULATION

Several features of the simulation which should be mentioned are listed below.

First, since a clutch existed between the heat engine and the CVT, the heat engine could be decoupled from the drive train when it was not being used. Hence it was assumed that there was zero fuel consumption by the heat engine during idling.

A second feature was that no matter how the power split strategy split the CVT input power, the heat engine was not allowed to deliver any power if the vehicle velocity was below 3 mph. This came into play as the vehicle started from rest at the beginning of a STC.

A third feature (which is detailed in Appendix E) was that if either the battery or the heat engine could not deliver the power called for by the power split, the unmet power was assigned to the other power source and both the electrical and heat engine calculations were repeated.

## 7.0 OPTIMIZATION AS A DESIGN TECHNIQUE

It is now appropriate to consider optimization as a technique which can be used with the vehicle simulation previously described to obtain desired design results. It will become apparent in the discussion below that the role of optimization is that of systematically changing design parameters for use with the vehicle simulation until design objectives are met. Optimization techniques are based on a particular methodology and formalism which must be adapted to the design problem at hand. The purpose of this section is to define the terminology of optimization, briefly summarize the optimization problem mathematically, and discuss the general nature of solutions to such problems.

Each optimization problem has an objective function (or criterion function),  $f(x)$ , which is an algebraic function of the  $n$  components of the vector  $x$ , and which is to be minimized (or maximized). The objective function in a design problem provides a measure of the quality of the design such that its minimum value occurs for a value of  $x$  which represents the best design.

The components of  $x$  may be subject to upper and lower bounds,

$$x_{r \min} \leq x_r \leq x_{r \max} \quad (7-1)$$

where, for a given variable  $x_r$ , one, neither or both of these bounds may be present. Variables often are given bounds for reasons of physical realizability; e.g., both battery weight and heat engine power rating must be positive, and the percentage of power delivered from one source must be between 0 and 100.



In addition to bounds which apply to the variables themselves, we must consider constraints, functions of these variables which also must be maintained within limits. An optimization problem might contain  $m$  constraints

$$g_{j_{\min}} < g_j(x) < g_{j_{\max}} \quad (j = 1, 2, \dots, m) \quad (7-2)$$

where one or both of the limiting values on a particular constraint  $g_j(x)$  may apply. The designer uses such constraint functions to calculate design characteristics which must be kept within upper or lower limits. A vehicle designer, for example, might want to place a lower limit on accelerating ability, or an upper limit on acquisition cost.

Since the objective functions and constraint functions applicable to hybrid vehicle design are generally nonlinear functions of  $x$ , we have a nonlinear optimization problem. Converting the scalar variables in equations 7-1 and 7-2 to vectors allows us to state the nonlinear optimization problem in a precise mathematical form:

$$\begin{aligned} & \min_x f(x) \\ & \text{subject to} \\ & x_{\min} < x < x_{\max} \end{aligned} \quad (7-3)$$

and

$$g_{\min} < g(x) < g_{\max} \quad (7-4)$$

The notation  $\min_x f(x)$  means that  $f(x)$  is to be minimized with respect to  $x$ . Equations 7-3 and 7-4 are the vector versions of equations 7-1 and 7-2, respectively, and include all desired bounds and constraint relationships.

Nonlinear optimization problems such as the one stated above have been well known for some time, and many techniques have been developed for finding

their solutions. Since  $f(x)$  and  $g(x)$  are assumed to be nonlinear, the techniques for solution of the problem are called nonlinear programming algorithms. Many of these have been developed over the past 25 years to provide a means of obtaining digital computer solutions to these problems [6,7,8,9] Some of these methods are discussed in Section 9.

Techniques for solution generally begin with an initial estimate,  $x_0$ , of the solution vector, which is feasible in that all bounds and constraints are satisfied, and proceed in an attempt to satisfy all of the necessary conditions for minimum  $f(x)$  while maintaining  $x$  feasible. The process terminates when these conditions are met, or when no further progress is possible.

Each nonlinear programming method has its own set of assumptions regarding the mathematical properties of  $f(x)$  and  $g(x)$ . Although there are small differences from method to method, it is usually necessary for both  $f(x)$  and the elements of  $g(x)$  to be continuous, differentiable functions of  $x$ , with continuous first partial derivatives with respect to the components of  $x$ . These restrictions have important implications on the specifications of the objective and constraint functions for a design problem, as well as the development of simulation programs for optimization.

## 8.0 THE VEHICLE DESIGN PROBLEM AS AN OPTIMIZATION PROBLEM

Having considered a general description of an optimization problem in Section 7, it is now possible to consider application of optimization methods to the design of the hybrid vehicle described earlier in this report. This involves formulating the vehicle design problem in terms of vehicle design parameters which will become the variables of the optimization problem, defining any bounds or constraint functions associated with these variables, and selecting an objective function which represents the designer's primary goal in a mathematical fashion. The key to successful formulation of a vehicle design problem as an optimization problem is in specifying all of the needed ingredients for the optimization problem (variables, objective function, bounds and constraints) in a way which meaningfully includes all important aspects of the design problem.

The primary design variables for the hybrid vehicle design problem discussed here are the two power-sizing parameters, heat engine power rating (in kilowatts) and battery weight (in kilograms). Additional design parameters are introduced later (see Section 11) as part of a decision rule which is used on an instantaneous basis to decide how much power is to be used from each of the two on-board power sources.

Lower bounds of at least zero must be specified for both the heat engine power and the battery weight. This is because the optimization method will consider all possible values of the design parameters, even those which are physically meaningless, unless such bounds are imposed. From a designer's point of view, a hybrid vehicle which has a very low heat engine power rating

or negligible battery weight is a single-power-source vehicle and not a hybrid vehicle; thus lower bounds were imposed to insure that the solution of the design problem by optimization produced a vehicle with both sources. The values of the lower bounds used in this study were 15 kw for the heat engine power rating and 60 kg for the battery weight.

Two primary objectives were considered in this study: life cycle cost (\$) and life cycle petroleum consumption (liters). Both of these can be calculated using the calculation procedure discussed in Section 5, and the vehicle simulation discussed in Section 6.

The principal constraint function used in this study is the power overload constraint discussed in Section 6. It was necessary to impose this constraint in order to ensure that the designs resulting from the use of optimization represent vehicles which can produce sufficient power to successfully complete all the specified driving regimes. Other constraint functions can also be used for particular design problems, using as a constraint a function which could be an objective function for another design; for example, the design might call for the hybrid vehicle which has the minimum life cycle cost subject to the constraint that its total petroleum consumption be less than some prespecified amount.

There are many vehicle design problems which may be stated and solved as optimization problems. Listed below are several sample optimization problems for hybrid vehicle design. These same problems were solved as part of this study and are discussed later in this report where results are presented. In the statement of these problems,  $C_{LC}$  is the life cycle cost (in \$),  $V_p$  is the total petroleum volume (in liters) used over a life cycle,  $P_{HE}$  is the heat engine power rating (in kilowatts),  $W_B$  is the battery weight (in kilograms)

and  $P_O$  is the power overload function ( $> 0$  when no overload occurs).

Sample Design Optimization Problem No. 1

Choose  $P_{HE}$  and  $W_B$  to minimize  $C_{LC}(P_{HE}, W_B)$   
subject to  $P_{HE} > P_{HE_{min}}$   
 $W_B > W_{B_{min}}$   
 $P_O > 0$

Sample Design Optimization Problem No. 2

Choose  $P_{HE}$  and  $W_B$  to minimize  $V_P(P_{HE}, W_B)$   
subject to  $P_{HE} > P_{HE_{min}}$   
 $W_B > W_{B_{min}}$   
 $P_O > 0$

Sample Design Optimization Problem No. 3

Choose  $P_{HE}$  and  $W_B$  to minimize  $V_P(P_{HE}, W_B)$   
subject to  $P_{HE} > P_{HE_{min}}$   
 $W_B > W_{B_{min}}$   
 $P_O > 0$   
 $C_{LC} < C_{LC_{max}}$

These three problems are typical of many which were considered in this study. All three are essentially vehicle power-sizing problems, where it is

desired to find the proper values of the heat engine power rating and the battery weight. They vary according to their objective functions and, in problem No. 3, the imposition of an additional constraint besides the power overload constraint.

Other design problems considered later in this report involve constraining the total petroleum volume in the minimization of  $C_{LC}$ , examining the effect of petroleum pricing on design results, and parameterizing the power split decision rule. These problems are discussed with the results in Section 11.

## 9.0 SELECTION OF OPTIMIZATION METHOD

Several methods including variable metric and conjugate gradient methods [6, 7, 8, 9] are available for direct solution of nonlinear programming problems such as the type stated in Section 7 and applicable to the hybrid vehicle design problem. Indirect methods such as those based on the Newton-Raphson method are also available, but this class of methods was rejected because of the likelihood of divergence with a poor initial estimate of the solution. Most direct methods such as gradient and modified gradient method were originally developed for unconstrained optimization problems (no bounds or constraints) and must be modified to include constraints.

One proven method for successfully incorporating bounds and constraints into a direct search method was developed by Abadie and Carpentier [8]. The method, called the Generalized Reduced Gradient Method (GRG), uses linearized constraints, defines new variables which are normal to some of the constraints, and transforms the gradient to a new basis.

Lasdon and Waren, et. al. [10] have developed an extensively refined code (computer program) for general purpose implementation of the GRG optimization method. The code which is now called GRG2, has been successfully tried on test problems in competition with other nonlinear programming codes, and has consistently ranked high in the primary characteristics desired of such a code (accuracy, efficiency, reliability, and ease of use) [11, 12]. GRG2 easily incorporates bounds on the variables and a variety of constraints. It provides great flexibility which includes a choice of search method, a variety of stopping criteria, provisions for scaling of variables and constraint functions, and several options regarding the amount of detail

provided in the printed output.

The designer who wishes to use GRG2 for optimization results must provide [13]:

1. a subroutine which computes the objective function and all of the constraint functions, given the optimization variables.
2. a data file which includes an initial point for the search, upper and lower bounds on variables and constraints (as applicable), and names for all variables and functions.

The designer may provide:

1. a subroutine for computing derivatives for gradients (otherwise the program uses finite difference approximations)
2. a subroutine for reporting needed output information which is not directly related to the optimization calculations
3. a file containing scale factors for the variables and constraints, and control parameters which specify how the detailed operation of the optimization search is to be carried out (e.g., search direction method, stopping criteria, constraint tolerances)

After a vehicle design problem has been properly formulated as an optimization problem, it is a fairly straight-forward procedure to write the subroutines and determine the data files indicated above. The most difficult part of this task is in writing the subroutine which computes the objective and constraint functions from the design parameters, since this normally involves the entire vehicle simulation as well as the computation of various vehicle costs.



## 10.0 IMPLEMENTATION OF THE GRG PROGRAM FOR VEHICLE DESIGN PROBLEMS

It was desired to combine the GRG2 optimization program with the hybrid vehicle simulation program in a way which would provide flexibility regarding specification of objective function, constraint functions, variables and bounds, so that a variety of hybrid vehicle design problems could be studied merely by changing a data file in the program.

This goal was accomplished by defining five functions of  $P_{HE}$  and  $W_B$  which would suffice for the calculation of all possible objective and constraint functions which were anticipated at the time the computer program was written. These functions are:

1. life cycle cost (\$)
2. acquisition cost (\$)
3. total petroleum volume in life cycle (liters)
4. linear combination of above three functions
5. power overload function

The fourth function was included to provide a weighted sum of three objective functions for the designer who wishes to compromise and not select a single objective from among the first three functions listed.

As described in Section 6.3, the power overload function was developed by simulating the hybrid vehicle for various pairs of values of the parameters ( $P_{HE}, W_B$ ) using a particular power split strategy developed by AiResearch Manufacturing Co. [1,5]. Regions where the hybrid vehicle was not able to meet the power demanded by the driving regime were identified and the power overload boundary was seen to be an irregular surface (Fig. 6-1)

which was not amenable to treatment by nonlinear programming techniques; these techniques normally require a smooth, differentiable function for each constraint. In order to meet this requirement in at least an approximate way, the overload constraint boundary function,  $P_O(P_{HE}, W_B)$ , was approximated by two polynomial functions as follows:

$$P_{HE} > 37.0 - 0.02564 W_B \quad (W_B < 273) \quad (6-1)$$

$$P_{HE} > 77.23 - 0.2268 W_B + 1.982 \times 10^{-4} W_B^2 \quad (W_B > 273) \quad (6-2)$$

These functions were used with GRG2 for determining solutions to optimization problems which included the power overload constraint.

For examination of the power flow or power split strategy problem, where we are trying to find the parameters of a decision rule which specifies how much power comes from each on-board power source at each instant of time, the GRG/simulation program was provided with three different ways to determine the power split between the heat engine and the electric propulsion system:

1. the AiResearch algorithm [1]
2. a polynomial function
3. a parameterized version of the AiResearch algorithm

More detail on the particular functions involved will be provided in Section 11.

Further flexibility in the program was provided by defining a data file which could be used to specify which type of vehicle design problem was to be solved with a particular optimization run: (1) vehicle sizing, (2) power split optimization, or a combination of the two.

The overall organization of the vehicle design computer program involves an interaction between the GRG2 optimization program and the hybrid vehicle simulation program discussed in Section 6. The interconnection is illustrated in Figure 10-1. The reader should note that the GRG2 program selects values of the parameter vector,  $x$ , for simulation in the Hybrid Vehicle Simulation Program, and receives the calculated values of the five functions (which may be the objective function or constraint functions) from it. GRG2 then systematically adjusts  $x$  in such a way as to minimize the objective function while satisfying bounds and constraints. The REPORT subroutine in GRG2 is used to calculate and print output information about the hybrid vehicle which is not essential to the GRG2 program.

The next section discusses particular problems which were attempted using this program, and the results which were obtained.




Figure 10-1 Interconnection of Optimization and Simulation Programs

## 11.0 RESULTS AND DISCUSSIONS OF RESULTS

Four different design problems were solved using the optimization approach discussed previously. Each of these problems is discussed in a separate subsection where the problem is defined and results are presented for that particular problem.

The two major problem areas considered were those of vehicle power source sizing and power split parameter optimization. The first three design problems deal with the sizing problem, including various design objectives and constraints, and the final design problem is concerned with optimizing the power split decision rule.

### 11.1 VEHICLE POWER SOURCE SIZING FOR MINIMUM LIFE CYCLE COST

The design objective here was to determine the proper power source sizing parameters, heat engine power (kw) and battery weight (kg), so that the life cycle cost of the hybrid vehicle is minimized and the final vehicle is able to meet all driving requirements as specified by the annual trip requirements and reflected in the vehicle simulation.

The optimization problem for this design problem is very similar to Sample Problem No. 1 in Section 8 of this report:

$$\text{Min } C_{LC}(P_{HE}, W_B) \quad (11-1)$$

$$\text{subject to } P_{HE} > 15 \quad (11-2)$$

$$W_B > 60 \quad (11-3)$$

$$P_O(P_{HE}, W_B) > 0 \quad (11-4)$$

and the AiResearch power split function which is specified in Appendix H.

Several initial estimates for the solution were tried, and all led to the same result:

$$\text{Min}_{P_{HE}, W_B} C_{LC}(P_{HE}, W_B) = C_{LC}(35.5, 60.0) = \$17,100 \quad (11-5)$$

This point is at the intersection of the overload constraint boundary and the lower bound for  $W_B$ . See Figure 11-1, which shows the optimization as it proceeded from the design parameters recommended by AiResearch [1],  $P_{HE} = 65$  kw and  $W_B = 386$  kg. Although this point was reached in two iterations, it should be noted that each iteration included many evaluations of the objective function for the various pairs of  $(P_{HE}, W_B)$  values which were being considered. During the first iteration, the search proceeded in the negative gradient direction until the overload constraint boundary was reached, using longer and longer steps until the boundary was encountered. During the second iteration, the search moved along the overload constraint boundary until the lower bound on  $W_B$  was reached; several intermediate points were used along the constraint before the iteration was completed. The overall result is a reduction in life cycle cost from \$20,796 to \$17,100.

It is not surprising that the optimal design in this case occurred on the overload constraint boundary, since any point above this boundary would correspond to higher value of  $P_{HE}$ ,  $W_B$  or both, leading to a higher life cycle cost, and any point below this boundary, although yielding a lower life cycle cost, would correspond to a vehicle not able to meet the specified driving requirements. It is also not surprising that the optimal solution occurs at the minimum value of  $W_B$ , since the nominal petroleum pricing used for this problem (See Section 5.3) makes it desirable to use as little electric power




Figure 11-1 Power Source Sizing for Optimum Life Cycle Cost  
(Petroleum Usage Unconstrained)

as possible if minimum life cycle cost is the objective.

A modified version of this problem was solved after including an additional constraint,

$$V_p < r V_p^* \quad (11-6)$$

to the optimization problem specified in equations 11-1 through 11-4.  $V_p^*$  is the petroleum volume, 9,814 liters, associated with the solution to the original optimization problem, and  $r$  ( $0 < r < 1$ ) specifies a certain fraction of that amount. The purpose of this design problem was to investigate how the optimal power sizing parameters would change, and how the life cycle cost would increase in the case where less and less total petroleum volume is available for the life of the vehicle. This is a situation which could be quite realistic as world petroleum resources are depleted or when foreign supplies become unavailable.

The results for this modified problem are shown in Figure 11-2 for various values of  $r$ , from  $r = 1.0$  to  $r = 0.60$ . The results show a steady increase of  $C_{LC}$  as  $r$  is decreased, rising from \$17,100 at  $r = 1.0$  to \$18,679 at  $r = 0.60$ . These results demonstrate the utility of a hybrid vehicle when petroleum supplies are strictly limited, and more reliance must be placed on the electrical propulsion system.

## 11.2 VEHICLE POWER SOURCE SIZING FOR CHANGING PETROLEUM COSTS

The design problem considered here is similar to that of the last section, where life cycle cost is to be minimized, but where the price of petroleum is varied and its effect on the results is observed. The price of petroleum was varied by introducing a gas factor,  $\gamma$ , which scales all of the






Figure 11-2 Power Source Sizing for Optimum Life Cycle Cost  
(Petroleum Usage Constrained)

petroleum costs,  $\gamma > 1.0$  ( $\gamma$  multiplies the array GASCST(I)).

The optimization problem for this design is:

$$\text{Min}_{P_{HE}, W_B} C_{LC}(P_{HE}, W_B, \gamma) \quad (11-7)$$

subject to equations 11-2, 11-3 and 11-4. The AiResearch power split function (see Appendix H) is again used and the value of  $\gamma$  is held constant during the optimization, so that this problem represents a family of optimization problems, each corresponding to a fixed value of  $\gamma$ .

The several optimization problems all used the same starting point,  $P_{HE} = 65$  kw and  $W_B = 368$  kg. The results are shown in Figure 11-3 for  $\gamma = \{1.00, 1.25, 1.50, 1.75, 2.00, 2.50, 3.00, 5.00\}$ . All results are on the boundary of the overload constraint function, with higher values of  $\gamma$  yielding designs which rely more and more on the electrical propulsion system. The life cycle costs associated with these results are listed in Table 11-1. It is clear from these results that the nominal petroleum pricing ( $\gamma = 1.0$ ) which was used for much of this study is too low to justify a hybrid vehicle on the basis of life cycle cost; the optimization would yield  $W_B = 0$  if this were permitted. Higher gas factors, however, show designs which have a much greater reliance on the electrical propulsion system.

### 11.3 VEHICLE POWER SOURCE SIZING TO MINIMIZE TOTAL PETROLEUM CONSUMPTION

The design problem considered here differs from the problems discussed in the last two sections in that the design objective was to minimize the total volume of petroleum used over the expected life of the vehicle. The rationale for this objective was that very low availability of petroleum could




Figure 11-3 Power Source Sizing for Optimum Life Cycle Cost  
(Various Petroleum Costs)

Table 11-1

Optimum Life Cycle Cost For Various Gas Factors

Gas Factor, $\gamma$	Optimum		
	$C_{LC}$ (\$)	$P_{HE}$ (kw)	$W_B$ (kg)
1.00	17,100	35.46	60.00
1.25	18,112	35.46	60.00
1.50	19,123	35.46	60.00
1.75	19,956	33.98	117.86
2.00	21,046	25.98	309.96
2.50	22,334	25.97	310.10
3.00	23,495	23.34	336.74
5.00	27,926	16.46	428.40

make a hybrid vehicle whose petroleum consumption was minimal very attractive, even at a somewhat higher price. Thus this problem, at least in its initial formulation, did not take costs into account explicitly.

The design optimization problem here is:

$$\text{Min}_{P_{HE}, W_B} V_p(P_{HE}, W_B) \quad (11-8)$$

subject to equations 11-2, 11-3 and 11-4, with the Airesearch power split function and  $\gamma = 1.0$ .

The result for this problem involving no costs was a hybrid vehicle with  $P_{HE} = 15.0$  kw, and  $W_B = 457$  kg. This design point is on the overload constraint boundary and sets the heat engine power at its lower limit, yielding total petroleum usage of 5,209 liters (compared to 9,814 when life cycle cost is minimized) and a life cycle cost of \$19,337 (compared to \$17,100 when life cycle cost is minimized). The results illustrate the trade off that occurs when the objective is low petroleum usage rather than minimum cost: the petroleum consumption decreases and the cost increases.

These results motivated another design optimization problem which was defined, starting with the problem above, by adding an additional constraint,

$$C_{LC}(P_{HE}, W_B) < 18,000 \quad (11-9)$$

This in effect asks for petroleum consumption which is superior to (lower than) that of the minimum-life-cycle-cost petroleum consumption, but which limits the cost increase. The result, as expected, was intermediate to the previous results for minimum life cycle cost and minimum petroleum consumption, with petroleum consumption of 7,2061 liters and a life cycle cost of

\$17,963. The design variables for this result were  $P_{HE} = 31.2$  kw and  $W_B = 226$  kg, a point on the overload constraint boundary.

The addition of this constraint illustrates the great flexibility of the optimization approach to hybrid vehicle design. It is easy for a designer to add such a constraint and repeat the optimization procedure in order to gain the desired result.

A summary of the results for the two problems discussed in this section as well as the minimum life cycle cost results are listed in Table 11-2.

Table 11-2  
Summary of Optimization Results

<u>Function Minimized</u>	<u>Constraint</u>	<u><math>P_{HE}</math>(kw)</u>	<u><math>W_B</math>(kg)</u>	<u><math>V_p</math>(l)</u>	<u><math>C_{LC}</math>(\$)</u>
$C_{LC}$	none	35.5	60	9,814	17,100
$V_p$	$C_{LC} < 18,000$	31.2	226	7,206	17,963
$V_p$	none	15.0	457	5,209	19,337

#### 11.4 POWER SPLIT OPTIMIZATION

This section discusses some particular problems which are in a class which may be described as power flow strategy problems. The general problem could include any number of on-board power sources, including storage devices, and is directed toward specifying the direction and amount of power flow for each power source at each instant of time. The result of solving the problem is called the power flow strategy because it is to be expressed

as a set of strategy algorithms, or decision rules, dependent on some of the vehicle dynamic variables and internal variables, which permit calculation of each power flow as these variables change with time.

For the particular case of a hybrid vehicle considered here, with the two on-board power sources, the power flow strategy problem reduces to that of determining, at each instant of time, how much of the wheel power is supplied by the electric propulsion system, and how much by the heat engine. Battery charging during regeneration is handled as a separate consideration (see Appendix F). The power flow strategy then amounts to determining the power split between heat engine power and battery power, and so the problem was defined using a power split function,  $s(t)$ ,  $0 < s(t) < 1$ , where the extremes correspond to all-petroleum ( $s = 0$ ) and all-electric ( $s = 1$ ) power.

It is important to recognize the infeasibility of finding  $s(t)$  as the solution to an optimization problem. This would be possible only if we were to define a dynamic optimization problem with a prescribed vehicle driving regime (speed vs. time) for the entire life of the vehicle. This is unrealistic from two points of view: (1) the time interval involved would be so long that the computations could not be performed efficiently, and (2) it is not possible to predict the exact, second by second driving velocity of a vehicle realistically for the entire life of the vehicle, and for a substantial number of vehicles.

Thus the approach taken here was based on the parameterization of a strategy function or decision rule, with the power split strategy expressed in terms of variables likely to influence the ideal power split function, and using parameters whose values could be obtained using the same methodology and computer programs used to determine optimal vehicle sizing parameters.

This part of the project included two different approaches concerning the parameterization of the power split function,  $s(t)$ . The first involved the parameterization of the AiResearch power split function, and the second involved the use of polynomial functions to represent  $s(t)$ .

#### 11.4.1 PARAMETERIZED AIRESEARCH POWER SPLIT FUNCTION

The power split function, previously discussed and used in the study by AiResearch Corporation [1] (also see Appendix H), contains several constants which could be treated as parameters. One of these, which was thought to be one of the most critical, is the value of the power split function during acceleration,  $s_a$ , which was given the value 0.3 in the AiResearch study. An optimization problem was formed with  $s_a$  as a parameter:

$$\text{Min } C_{LC}(s_a) \quad (11-10)$$

$$\text{subject to } P_{HE} = 65 \text{ kw} \quad (11-11)$$

$$W_B = 386 \text{ kg} \quad (11-12)$$

$$0 < s_a < 1.0 \quad (11-13)$$

and the remainder of the AiResearch power split algorithm. Equations 11-11 and 11-12 specify vehicle power sizing parameters which correspond to those of the AiResearch hybrid vehicle design; since this vehicle is easily able to meet the power demanded by the driving regime, it was not necessary to include the power overload function as a constraint for this problem.

This optimization problem was solved repeatedly for several values of the gas factor,  $\gamma$ , which was discussed in Section 11.2. Results, which are listed in Table 11-3, show that no electric power should be used during acceleration for the lowest values of the gas factor, and that the power split



rises to 0.264 with  $\gamma = 5.0$ . The optimal life cycle costs rises correspondingly with the gas factor, as expected. These results show that the optimal distribution of power between the two sources is strongly dependent upon the petroleum price, and that a power split value of 0.3 could be justified only for a very large value of the gas factor.

Table 11-3  
Optimal Power Split During Acceleration

Gas Factor, $\gamma$	Power Split, $s_a$	Life Cycle Cost, $C_{LC}(\$)$
1.0	0.000	20,000
1.5	0.000	21,886
2.0	0.114	23,303
2.5	0.194	24,669
3.0	0.231	26,021
4.0	0.248	28,702
5.0	0.264	31,364

#### 11.4.2 POLYNOMIAL POWER SPLIT FUNCTION

Another approach to expressing the power split function in parameterized form is to use a simple polynomial function of vehicle variables with parameters to be determined through optimization. This leads to a problem of constraining  $s(t)$  to its specified range,  $0 < s(t) < 1$ , since any polynomial

function of vehicle variables is likely to exceed this range during at least part of the driving regime. This problem cannot be treated directly through constraints on  $s(t)$  because that involves a dynamic optimization problem which is unrealistic in this application as discussed earlier.

The power split function was constrained through the use of limiting. Let  $s_p(t)$  be the value of the power split polynomial function. Then

$$s(t) = \begin{cases} 0, & s_p(t) < 0 \\ s_p(t), & 0 < s_p(t) < 1 \\ 1, & s_p(t) > 1 \end{cases} \quad (11-14)$$

The polynomial function chosen for investigation involved two key vehicle variables, battery state of charge,  $c(t)$  and vehicle acceleration,  $a(t)$ . Several polynomial functions were tried starting with the linear polynomial

$$s_p(t) = \alpha_0 + \alpha_1 c(t) + \alpha_2 a(t) \quad (11-15)$$

and later including higher-degree polynomial functions.

The search procedures of GRG2 did not produce worthwhile results with this approach. Typically, the search started with an initial estimate of the  $\alpha$  parameters and failed to improve the objective function in several iterations, finally stopping because of lack of progress at a point very close to the initial estimate. Our conclusion about this is that it was not due to any deficiency in GRG2, but was due to a fundamental problem with the approach, in particular the limiting process defined by equation (11-14). The limiting apparently led to erroneous values of the gradient so that the search directions determined by GRG2 were not effective. It seems as if the changes used for the parameters had little or no effect because the value of

$s_p(t)$  calculated from the polynomial such as that in equation (11-15) was promptly and frequently overridden by the limiting action as the vehicle simulation was carried out. Approaches like the one described in Section 11.4.1, where a proven and acceptable power split function was parameterized, seem much more promising. The main reason for this is that such an approach allows incorporation of bounds on the parameters themselves in a direct manner, rather than the indirect approach used in the limiting of the polynomial function.

### 11.5 SUMMARY OF RESULTS

This section has treated the application of an optimization technique based on nonlinear programming to the design of hybrid vehicles. Four different design problems were solved using the digital computer program which combined the optimization algorithm with the hybrid vehicle simulation.

The method was successfully applied to vehicle power source sizing problems for a variety of design goals and specifications. It was found that all solutions were on the power overload constraint boundary such that, in each case, any reduction in the battery weight or heat engine power rating would yield a vehicle which would not be able to meet the power demands of the specified driving regime.

Two methods were considered for parameterizing the power split function which specifies, at each instant of time, what fraction of the total power demand is supplied by the electric propulsion system, and what fraction by the heat engine. The parameterization of the AiResearch power split function was found to be much more successful than using a polynomial power split function with limiting.

The use of optimization as a systematic approach to a variety of hybrid vehicle design problems was shown by these results to be very effective.

## 12.0 CONCLUSIONS

This study has led to several conclusions regarding the effective use of an optimization technique for hybrid vehicle design.

Efficient and effective use of an optimization technique for hybrid vehicle design depends heavily on a vehicle simulation program which is designed for this purpose. One of the main necessary features of such a simulation is that it must permit continuous variation of the power plant sizing parameters, battery weight and heat engine power rating.

Another area demanding attention in such a simulation is the way the specified driving pattern, including standard test cycles and highway driving, are incorporated into the simulation; this has impact both on computer run time, which must be minimized, and on the ability to accurately simulate long trips involving a declining state of charge for the batteries, since this state of charge affects the power split. One cannot get accurate results by merely simulating one standard test cycle and extrapolating the results.

Attention must be paid to the simulation time step sizes used in the simulation. They must be small enough to provide sufficient accuracy in the calculation of vehicle variables and costs, while remaining as large as possible for the purpose of minimizing computer run time; this is particularly important when the simulation is used in optimization, since the optimization program must run the simulation program dozens of times during the completion of one design problem.

Since the main purpose of the simulation program is to calculate functions which are used as the objective or constraint functions for the

optimization program, the simulation program must be designed to produce these functions as smooth functions of the design parameters. Otherwise the optimization program is likely to calculate search directions which will not yield a successful result because of functional discontinuities, or the optimization is likely to stall at a false local minimum.

This research demonstrated that the handling of the power overload function is critical to obtaining successful results for power-sizing design problems. Design results for this problem are very likely to lie on the power overload constraint boundary, since the region above it represents increased life cycle cost and petroleum consumption, while the region below it represents a vehicle which will not be able to meet the power demand associated with the specified driving regime. The exact location of the power overload constraint boundary need not be determined; it is more important that this constraint be a smooth function so that the optimization program can work efficiently.

It is important to choose the optimization program and to carefully design the interface between the simulation program and the optimization program in order to provide considerable flexibility to the designer in the choice of the design objective, constraints and variables for a variety of design problems. This project demonstrated that this can be done successfully.

Standard procedures for improving the efficiency of the optimization program, including scaling of the design variables and functions, were used and were judged to be effective. Gradient calculations by finite differences required the use of double-precision arithmetic. These are points which the designer must keep in mind when developing optimization program applications.

The two methods of parameterizing the power split algorithm, which specifies how much electric power and heat engine power is used at any time, demonstrated the feasibility of this parameterization. The polynomial power split function which was limited in value did not produce useful results because the optimization program did not have a free hand in varying the power split function due to the limiting. The parameterization of the AiResearch algorithm was much more effective, and this general area of parameterizing an established algorithm is a promising area for future research. Optimization of the power split function, in particular, is a research area which should be pursued.

Optimization has been shown to be a useful tool for systematic design of hybrid vehicles. This research showed that it is possible to couple a sophisticated, general purpose optimization program to a complex hybrid vehicle simulation and produce a successful hybrid vehicle design using a reasonable amount of computer time.

APPENDIX A - DICTIONARY OF VARIABLES

```

FIN4,L
PROGRAM HVPOP
C
C*****
C***          PROGRAM HVPOP = HYBRID VEHICLE PERFORMANCE EVALUATION PROGRAM      ***
C***          *****
C
C
C*****
C***          DICTIONARY OF VARIABLES          *****
C***          *****
C*****
C
C
C VARIABLE          DESCRIPTION          UNITS          SOURCE          VALUE
C
C*****
C AACTL          ACTUAL CAPACITY WITHDRAWN          AMP-HOURS          CALC          *****
C                FROM BATTERY
C
C AACVC          MAP OF AVERAGE CHARGING VOLTAGE          VOLTS          CSU          HAVE
C (AACTL/MC) VS ACTUAL CAPACITY REMOVED (FOR
C                A 25 AMP CHARGE RATE)
C
C ACCEL          AVERAGE ACCELERATION OVER ONE          METERS PER          CALC          *****
C                DRIVING CYCLE TIME INCREMENT          SECOND SQUARED
C
C ACQST          ACQUISITION COST OF VEHICLE          DOLLARS          CALC          *****
C
C ACR          ARRAY OF CAPACITY REMOVED (USED          AMP-HOURS          NASA          HAVE
C                IN CALCULATING THE AVERAGE          PER KILOGRAM
C                CHARGING VOLTAGE)
C
C ALLETA(I)      ARRAY OF ELECTRIC ENERGY,          MEGAJOULS          CALC          *****
C                COMPUTED BY SUMMING THE CURRENT
C                OUT OF THE BATT, IN THE VARIOUS
C                TRIPS (FOR PRINTING)
C
C ALLETP(I)      ARRAY OF ELECTRIC ENERGY,          MEGAJOULS          CALC          *****
C                COMPUTED BY SUMMING THE POWER
C                OUT OF THE BATT, IN THE VARIOUS
C                TRIPS (FOR PRINTING)
C
C AESPED(1)      ARRAY OF ENGINE SPEEDS USED IN          RAD/SEC          NASA          HAVE
C                HC MAP INTERPOLATION
C

```



C AHCHG	AMP-HRS INTO BATTERY FROM HE CHARGING	AMP-HOURS	CALC	*****
C				
C				
C AHEKW(I)	ARRAY CONTAINING HE POWER RATINGS (USED IN FUEL RATE CALCULATIONS)	KILOWATTS	NASA	T AHEKW(I) 1 37. 2 56. 3 75. 4 112.
C				
C				
C				
C AHOUT	BATTERY AMP-HOURS OUT	AMP-HOURS	CALC	*****
C				
C ALLSTC	LENGTH OF LONGEST TRIP WHICH USES JUST STC'S (NO HIGHWAY DRIVING)	METERS	NASA	50,001.0
C				
C				
C ALPHA1	WEIGHTING PARAMETER FOR LIFE CYCLE COST IN OBJECTIVE FUNCTION	-	CSU	VARIES
C				
C				
C ALPHA2	WEIGHTING PARAMETER FOR PETROLEUM COST IN OBJECTIVE FUNCTION	-	CSU	VARIES
C				
C				
C ALPHA3	WEIGHTING PARAMETER FOR ACQUISITION COST IN OBJECTIVE FUNCTION	-	CSU	VARIES
C				
C				
C APETT(I)	ARRAY OF PETROLEUM USED IN THE VARIOUS TRIPS (FOR PRINTING)	LITERS	CALC	*****
C				
C				
C AREGEN	AMP-HOURS REGENERATED	AMP-HOURS	CALC	*****
C				
C ASMCER	CONSTANT USED TO CALC. THE ASSEMBLY COST	DOLLARS PER KILOGRAM	NASA	0.1984
C				
C				
C ASMCST	VEHICLE ASSEMBLY COST	DOLLARS	CALC	*****
C				
C ATORQ(I)	ARRAY OF TORQUES CORRESPONDING TO THE STANDARD 75 KW ENGINE USED TO COMPUTE THE SCALED ARRAY OF TORQUES USED FOR A DIFFERENT SIZED ENGINE	NM	NASA	HAVE
C				
C				
C BATCER	CONSTANT USED TO CALCULATE COST OF BATTERIES	DOLLARS PER KILOGRAM	NASA	1.87
C				
C				
C BATCST	MANUFACTURING COST OF BATTERIES	DOLLARS	CALC	*****
C				
C				
C BATLFE	NO. OF YEARS IN BATTERY LIFE	YEARS	CALC	*****
C				
C				
C BATRPL	NO. OF BATTERY REPLACEMENTS IN VEHICLE LIFE	-	CALC	*****
C				
C				

C	BATSAL	SALVAGE VALUE OF BATTERY	DOLLARS	CALC	*****
C					
C	BENRGY	BATTERY ENERGY USED FOR THIS INCREMENT IN THE DRIVING CYCLE	JOULES	CALC	*****
C					
C	BET(I)	GRADE ANGLE ARRAY FOR COMPLETE DRIVING CYCLE	DEGREES	CSU/NASA	ALL 0.
C					
C	BETA	GRADE ANGLE AT THIS POINT IN THE DRIVING CYCLE	DEGREES	CALC	*****
C					
C	BSFC	CONSTANT USED TO CALC MOST EFFICIENT ENGINE SPEED FOR A GIVEN PERCENT OUTPUT OF HE	RAD/SEC ----- % RATED POWER	CSU/NASA	4.2
C					
C	BTCOST	COST OF BATTERY REPLACEMENT DURING VEHICLE LIFE	DOLLARS	CALC	*****
C					
C	DTLIST	LIST COST OF BATTERIES	DOLLARS	CALC	*****
C					
C	BTMAIN	BATTERY MAINTENANCE COST	DOLLARS PER KILOMETER	CALC	*****
C					
C	BTMKUP	BATTERY MARKUP FACTOR (A CONSTANT BETWEEN 0 AND 1)	-	NASA	0.3
C					
C	CAPCTY	CELL CAPACITY	AMP-HOURS	CALC	*****
C					
C	CAPKG	CAPACITY OF A BATTERY CELL PER KILOGRAM	AMP-HOURS/KG	CALC	*****
C					
C	CDA	DRAG COEFFICIENT TIMES VEHICLE FRONTAL AREA	METERS SQUARED	NASA	0.6
C					
C	CHARGE(I)	ARRAY WHICH SAVES AT THE END OF EACH STC THE TOTAL AMP-HRS INTO THE BATTERY FROM HE CHARGING	AMP-HOURS	CALC	*****
C					
C	CHGGER	CONSTANT USED TO CALCULATE COST OF CHARGER	DOLLARS PER KILOGRAM	NASA	5.89
C					
C	CHGCST	COST OF BATTERY CHARGER	DOLLARS	CALC	*****
C					
C	CHGEFF	BATTERY CHARGER EFFICIENCY	-	NASA	0.85
C					
C	CHGRC1	CONSTANT USED IN CALCULATING MASS OF CHARGER	KILOGRAMS PER WATT	NASA	0.0
C					
C	CHGRKW	POWER RATING OF CHARGER	KILOWATTS	NASA	14.5
C					

C	CHICI	CONSTANT USED IN CALCULATING MASS OF CHOPPER INVERTER	KILOGRAMS PER KW	NASA	0.91
C	CHICER	CONSTANT USED TO CALCULATE CHOPPER INVERTER COST	DOLLARS PER KILOGRAM	NASA	14.00
C	CHICST	COST OF CHOPPER INVERTER	DOLLARS	CALC	*****
C	CHIKW	POWER RATING OF CHOPPER INVERTER	KILOWATTS	NASA	40.0
C	CHIMAN	CHOPPER INVERTER MAINTENANCE COST	DOLLARS PER KILOMETER	CALC	*****
C	CHOOSE	IF EQUAL TO 1, ELECTRICITY COST COMPUTED FROM ELECVR(I). IF EQUAL TO 0, ELEC(I) REPLACES ELECVR(I)	-	CSU	0.0
C	CLTCR	CONSTANT USED TO CALCULATE THE COST OF THE CLUTCH	DOLLARS PER KILOGRAM	NASA	0.0
C	CLTCST	COST OF CLUTCH FOR VEHICLE	DOLLARS	CALC	*****
C	COUNT	VARIABLE USED IN DETERMINING WHICH YEARS BATT. REPLACEMENT COSTS ARE ADDED	-	CALC	*****
C	CR	CONSTANT IN ROLLING RESISTANCE FORCE CALCULATION	-	CALC	*****
C	CVTCI	CONSTANT USED TO CALCULATE CVT MASS	KILOGRAMS PER KILOWATT	NASA	1.07
C	CVTCR	CONSTANT USED TO CALCULATE CVT COST	DOLLARS PER KILOGRAM	NASA	1.42
C	CVTCST	COST OF CVT	DOLLARS	CALC	*****
C	CVTKW	POWER RATING OF CVT	KILOWATTS	NASA	90.0
C	CVTMAN	CVT MAINTENANCE COST	DOLLARS PER KILOMETER	CALC	*****
C	CX(I)	ARRAY CONTAINING POWER SPLIT PARAMETERS	MIXED	CALC	*****
C	DEEP	NO. OF DEEP DISCHARGES OF BATTERY DURING VEHICLE LIFE	-	CALC	*****
C	DELR	INCREMENT FOR DECREASING CVT	-	CSU	0.1

C	RATIO TO PREVENT MOTOR FROM				
C	STALLING				
C					
C	DELSYC	FRACTION OF AN STC USED	-	CALC	*****
C		IN CURRENT TRIP			
C					
C	DELT	SIMULATION TIME STEP SIZE	SECONDS	CALC	*****
C					
C	DELTW	SIMULATION TIME INCREMENT FOR	SECONDS	CSU	60.0
C		HIGHWAY DRIVING			
C					
C	DELV	VEHICLE VELOCITY DECREASE PER	KILOMETERS	CALC	*****
C		TIME INCREMENT DURING BREAKING	PER SECOND		
C		PHASE OF STC			
C					
C	DIGRkW	POWER RATING OF GEAR BETWEEN	KILOWATTS	NASA	90.0
C		DIFFERENTIAL AND CVT (SEE ALSO			
C		PGRATE)			
C					
C	DHEKW	WHEN RUN21=2, THE AMOUNT HEKW	KILOWATTS	ARB	
C		IS INCREMENTED FOR NEXT GCOMP CALL			
C		WHEN RUN21=1 THE TOLERANCE ON HEKW			
C					
C	DIFCER	CONSTANT USED TO CALCULATE	DOLLARS PER	NASA	2.42
C		COST OF A DIFFERENTIAL	KILOGRAM		
C					
C	DIFCST	COST OF DIFFERENTIAL	DOLLARS	CALC	*****
C					
C	DIFFC1	CONSTANT USED IN CALCULATING	KILOGRAMS	NASA	0.66
C		MASS OF DIFFERENTIAL	PER KW		
C					
C	DIFFKW	POWER RATING OF DIFFERENTIAL	KILOWATTS	NASA	90.0
C		(ALSO SEE PDRATE)			
C					
C	DISCH(I)	ARRAY CONTAINING THE NUMBER	-	CALC	*****
C		OF BATTERY DISCHARGES PER YEAR			
C		FOR THIS PARTICULAR TRIP TYPE			
C					
C	DISCHG(	BATTERY DISCHARGE CURVE	VOLTS/CELL	NASA	HAVE
C	SUC, I(OFF)				
C					
C	DISCNT	DOLLAR DISCOUNT RATE	-	NASA	0.02
C					
C	DISEFF	FACTOR USED DURING DISCHARGE	-	CALC	*****
C		TO CONVERT BATTERY TERMINAL			
C		ENERGY TO INTERNAL ENERGY			
C					
C	DISFAC	THE AMOUNT OF BATTERY DISCHARGE	-	CALC	*****
C		DURING ONE TRIP OF THIS			
C		PARTICULAR TRIP TYPE			

C				
C	DISLFE	NO. OF DEEP DISCHARGES IN BATTERY LIFE	--	NASA 840.
C				
C	DLTSTC	SIMULATION TIME STEP SIZE FOR STC DRIVING	SECONDS	CSU/NASA 1.0
C				
C	DWGBAT	WHEN RUN21=1, OR 2 THE AMOUNT WGBAT IS INCREMENTED FOR NEXT GCOMP CALL	KILOGRAMS	ARB
C				
C	EBTOT	TOTAL BATTERY ENERGY USED SINCE START OF TRIP	MEGAJOULES	CALC *****
C				
C	EBTOTL(I)	ARRAY WHICH SAVES AT THE END OF EACH STC THE TOTAL BATTERY ENERGY USED SINCE THE START OF ALL STC'S	MEGAJOULES	CALC *****
C				
C	EFF(KW, RATIO)	CVT EFFICIENCY MAP (A NUMBER BETWEEN 0 AND 1)	-	NASA HAVE
C				
C	EFFBC	COMBINED BATTERY CHARGER EFF. AND BATTERY TURNAROUND EFF.	-	NASA 0.75
C				
C	EFFMTR(PERCENT RATED PWR, SPEED)	MOTOR EFFICIENCY MAP	--	NASA HAVE
C				
C	ELEC(I)	ARRAY CONTAINING WALL PLUG ELECTRICAL ENERGY (COMPUTED ON AMP-HR BASIS) REQUIRED TO MEET ELECTRICAL ENERGY CONSUMPTION FOR THIS PARTICULAR TRIP TYPE FOR ONE YEAR	MEGAJOULES	CALC *****
C				
C	ELECST(I)	ARRAY CONTAINING ELECT. COST FOR YEAR I	DOLLARS	CALC *****
C				
C	ELECYR(I)	ARRAY CONTAINING WALL PLUG ELECTRICAL ENERGY (COMPUTED ON POWER BASIS) REQUIRED TO MEET ELECTRICAL ENERGY CONSUMPTION FOR THIS PARTICULAR TRIP TYPE FOR ONE YEAR	MEGAJOULES	CALC *****
C				
C	ENELEC	ELECTRICAL ENERGY CONSUMED IN CURRENT TRIP (BASED ON POWER)	MEGAJOULES	CALC *****
C				
C	ENRGY	ELECTRICAL ENERGY CONSUMED	MEGAJOULES	CALC *****

```

C      IN CURRENT TRIP (BASED ON
C      ANP-HRS)
C
C FA      VEHICLE ACCELERATION FORCE      NEWTONS      CALC      *****
C
C FD      VEHICLE DRAG FORCE              NEWTONS      CALC      *****
C
C FFHEKW(I)  ARRAY CONTAINING PENALTY/
C           IMPROVEMENT FACTORS FOR
C           VARIOUS HE POWER RATINGS
C           (USED IN FUEL RATE
C           CALCULATIONS)
C                                     -      NASA      I FFHEKW(I)
C                                     1 1.09718
C                                     2 1.05
C                                     3 1.
C                                     4 .954545
C
C FGR      GRADE FORCE                    NEWTONS      CALC      *****
C
C FR      ROLLING RESISTANCE FORCE        NEWTONS      CALC      *****
C
C FRSCLE    FACTOR DEPENDENT ON HEKW ONLY
C           USED IN MAKING DIFFERENT SIZED
C           HE MAPS FROM A 75 KW HE MAP
C                                     -      CALC      *****
C
C FUELRT    HEAT ENGINE FUEL RATE        LITERS PER   CALC      *****
C                                     SECOND
C
C G(I)      ARRAY CONTAINING WEIGHTED OBJECTIVE
C           AND CONSTRAINT FUNCTIONS
C                                     1      CALC      *****
C
C GASCST(I)  ARRAY CONTAINING PRICE OF
C           PETROLEUM FOR EACH YEAR
C                                     DOLLARS      NASA      I GASCST(I)
C                                     PER LITER
C                                     1 0.32
C                                     2 0.35
C                                     3 0.38
C                                     4 0.41
C                                     5 0.44
C                                     6 0.47
C                                     7 0.50
C                                     8 0.53
C                                     9 0.56
C                                     10 0.59
C
C GRAY      ACCELERATION OF GRAVITY      METERS PER   CSU      9.807
C                                     SECOND
C                                     SQUARED
C
C GRCG      CONSTANT USED IN CALCULATING
C           MASS OF GEAR
C                                     KILOGRAMS PER NASA      0.5
C                                     KILOWATT
C
C GRCEB      CONSTANT USED TO CALCULATE
C           COST OF A GEAR
C                                     DOLLARS PER   NASA      2.43
C                                     KILOGRAM
C
C GRCST      COST OF GEAR BETWEEN
C                                     DOLLARS      CALC      *****

```

```

D DIFFERENTIAL AND CVT
C
C GRFF(PERCENT GEARS AND DIFFERENTIAL - NASA HAVE
C POWER,PERCENT EFFICIENCY MAP,(A
C SPEED) CONSTANT BETWEEN ZERO
C AND 1.0)
C
C GRMCST COST OF GEAR BETWEEN ELECTRIC DOLLARS CALC *****
C MOTOR AND CVT
C
C HEC1 CONSTANT USED IN CALCULATING KILOGRAMS PER NASA 0.6
C MASS OF ENGINE KW SQUARED
C
C HEC2 CONSTANT USED IN CALCULATING KILOGRAMS NASA 2.84
C MASS OF ENGINE PER KW
C
C HECER CONSTANT USED TO CALCULATE DOLLARS PER NASA 1.43
C HEAT ENGINE COST KILOGRAM
C
C HECOST COST OF HEAT ENGINE DOLLARS CALC *****
C
C HEKW POWER RATING OF HEAT ENGINE KILOWATTS NASA 65.0
C STARTING VALUE OF HEKW WHEN
C RUN21=2
C
C HEMAIN HEAT ENGINE MAINTENANCE COST DOLLARS PER CALC *****
C KILUMETER
C
C HEMAP( HEAT ENGINE MAP LITERS PER NASA HAVE
C TORQUE,SPEED) SECOND
C
C HOUT(1) ARRAY WHICH SAVES AT THE END OF AMP-HOURS CALC *****
C EACH STC THE AMP HOURS OUT OF THE
C BATTERY SINCE THE START OF THE STC'S
C
C HWYVEL HIGHWAY VELOCITY FOR VEHICLE METERS PER NASA 25.0
C SECOND
C
C I80DDO BATTERY DISCHARGE FLAG - CALC *****
C (EQUALS 1 MEANS BATTERY IS AT OR
C BELOW 80% DEPTH OF DISCHARGE)
C
C IAVE AVERAGE BATTERY CURRENT SINCE AMPS CALC *****
C START OF STC DRIVING
C
C IBATT BATTERY OUTPUT CURRENT AMPS CALC *****
C
C IBMAX BATTERY MAX. CHARGING CURRENT AMPS NASA 200.0
C
C IRTOLD OLD VALUE OF BATTERY CURRENT AMPS CALC *****

```

C				
C	IDOD(I)	ARRAY WHICH SAVES STATE OF DEPTH OF DISCHARGE FLAG AT END OF EACH STC	-	CALC *****
C				
C	IEFF	BATTERY CELL CURRENT (ACCOUNTS FOR CHANGE IN CELL RESISTANCE DUE TO CHANGE IN CELL MASS)	AMPS	CALC *****
C				
C	IEFFMX	MAX VALUE OF BATTERY EFFECTIVE CURRENT	AMPS	CSU 700.
C				
C	IIELEC	ELECTRICAL PATH CALC. FLAG (EQUALS 1 IF ELECTRICAL PATH CALC WAS MADE THIS ITERATION)	-	CALC *****
C				
C	IIFILL	BATTERY CURRENT NEEDED TO CHARGE BATTERY TO SOC OF 1.0	AMPS	CALC *****
C				
C	IIFLLBK	COUNTS NUMBER OF TIMES ACTUAL POWER SPLIT IS CHANGED FROM SPLIT DETERMINED BY SPLIT FUNCTION	-	CALC *****
C				
C	IINECHG	BATTERY CHARGING FLAG (EQUAL TO 1 MEANS BATTERY IS BEING CHARGED BY HE)	-	CALC *****
C				
C	IINHWY	HIGHWAY DRIVING FLAG (EQUALS 1 IF DRIVING ON HIGHWAY RATHER THAN STC)	-	CALC *****
C				
C	IJJCHG	COUNTS ITERATIONS IN ATTEMPTING TO MATCH CALCULATED BATTERY VOLTAGE TO BATTERY VOLTAGE ASSUMED IN MAKING A HE CHARGING OF THE BATTERY CALCULATION	-	CALC *****
C				
C	IITER	COUNTS ITERATIONS IN ATTEMPTING TO MATCH CALCULATED BATTERY VOLTAGE TO BATTERY VOLTAGE ASSUMED IN MAKING A BATTERY DISCHARGE CALCULATION	-	CALC *****
C				
C	IIREGN	COUNTS ITERATIONS IN ATTEMPTING TO MATCH CALCULATED BATTERY VOLTAGE TO BATTERY VOLTAGE ASSUMED IN MAKING A POWER REGENERATION CALCULATION	-	CALC *****
C				
C	INAX	NUMBER OF POWER SPLIT PARAMETERS	-	CSU *****
C				
C	INUCHG	HE CHARGING INHIBIT FLAG (=1 FOR NO HE CHARGING)	-	CSU 0
C				



```

C
C INDELE FLAG WHICH INHIBITS FURTHER USE -- CALC *****
C OF BATTERIES IF SOC FALLS BELOW
C 0.2 DURING HIGHWAY DRIVING
C (=1 FOR INHIBIT)
C
C IOVRLD POWER OVERLOAD FLAG (COUNTS NO. -- CALC *****
C OF TIMES BATTERIES AND HEAT ENGINE
C CANNOT MEET POWER REQUIRED BY VEHICLE)
C
C ISWICH POWER SWITCH FLAG (EQUALS 1 WHEN WE -- CALC *****
C HAVE ALREADY ATTEMPTED TO SWITCH
C EXCESS HEAT ENGINE POWER TO
C ELECTRIC MOTOR)
C
C ITERMX MAX NUMBER OF ITERATIONS ALLOWED -- CSU/NASA 10
C IN ATTEMPTING TO MATCH CALCULATED
C BATTERY VOLTAGE TO BATTERY VOLTAGE
C ASSUMED IN MAKING THE CALCULATION
C
C IVESTC(I) ARRAY WHICH SAVES AT THE END OF AMPS CALC *****
C EACH STC THE AVERAGE CURRENT OUT
C OF THE BATTERY SINCE THE START
C OF THE STC'S
C
C IYEAR INDEX INDICATING PRESENT YEAR IN -- CALC *****
C LIFE CYCLE COST CALCULATIONS
C
C JTRIP INDEX INDICATING PRESENT TRIP IN -- CALC *****
C LIFE CYCLE COST CALCULATIONS
C
C KMPYR KILOMETERS TRAVELED PER YEAR KILOMETERS NASA 16,000.
C
C KWGST(I) ARRAY CONTAINING PRICE OF DOLLARS PER NASA I KWGST(I)
C ELECTRICITY FOR EACH YEAR MEGAJOULE 1 .0111
C 2 .0125
C 3 .0139
C 4 .0153
C 5 .0167
C 6 .0181
C 7 .0194
C 8 .0208
C 9 .0222
C 10 .0236
C
C LCCOST LIFE CYCLE COST DOLLARS CALC *****
C
C LENGTH LENGTH OF THE CURRENT TRIP METERS CALC *****
C
C LINCOM LINEAR COMBINATION OF LIFE DOLLARS CALC *****

```

C	CYCLE COST, PETROLEUM COST				
C	AND ACQUISITION COST				
C					
C	MAINTC	VEHICLE MAINTENANCE COST	DOLLARS	CALC	*****
C		FOR ONE YEAR			
C					
C	MARKUP	DEALER MARKUP FACTOR	-	CALC	*****
C					
C	MC	MASS OF A BATTERY CELL	KILOGRAMS	CALC	*****
C					
C	MCSTND	MASS OF THE BATTERY CELL USED	KILOGRAMS	NASA	9.83
C		IN DEVELOPING THE BATTERY			
C		DISCHARGE CURVE			
C					
C	MNFCS	MANUFACTURING COST FOR VEHICLE	DOLLARS	CALC	*****
C					
C	MT	TOTAL MASS OF VEHICLE AND	KILOGRAMS	CALC	*****
C		PROPULSION SYSTEM			
C					
C	MTGRKW	POWER RATING OF GEAR BETWEEN	KILOWATTS	NASA	40.0
C		ELECTRIC MOTOR AND CVT (ALSO			
C		SEE PMGRTE)			
C					
C	MTKWP	ELECTRIC MOTOR PEAK KILOWATT	KILOWATTS	NASA	40.0
C		RATING (ALSO SEE PMTMAX)			
C					
C	MTMAIN	ELECTRIC MOTOR MAINTENANCE COST	DOLLARS PER	CALC	*****
C			KILOMETER		
C					
C	MTRC1	CONSTANT USED IN CALCULATING	KILOGRAMS	NASA	0.6
C		MASS OF ELECTRIC MOTOR	PER KW		
C					
C	MTRCR	CONSTANT USED TO CALCULATE	DOLLARS PER	NASA	15.95
C		THE COST OF THE ELECTRIC MOTOR	KILOGRAM		
C					
C	MTRCST	COST OF ELECTRIC MOTOR	DOLLARS	CALC	*****
C					
C	MTRKW	POWER RATING OF ELECTRIC MOTOR	KILOWATTS	NASA	20.0
C		(ALSO SEE PMTRTD)			
C					
C	MTRSPD	AN ARRAY SPECIFYING MAXIMUM	RADIANS PER	NASA	HAVE
C	(PMTPCT)	EFFICIENCY MOTOR SPEED FOR A	SECOND		
C		GIVEN OUTPUT POWER			
C					
C	NC	NUMBER OF SERIES CONNECTED	-	NASA	84
C		BATTERY CELLS NECESSARY TO			
C		REACH SYSTEM VOLTAGE			
C					
C	NCORE	DIMENSION OF GRG ARRAY Z	-	CSU	6900
C					

C NCYCLE	NUMBER OF STO CYCLES ALREADY SIMULATED	-	CALC	*****
C				
C NCYLMX	MAX NUMBER OF STO'S IN ANY PARTICULAR TRIP	-	NASA	35
C				
C NHEKW	(WHEN RUN21 = 2) THE NO. OF DIFFERENT HEKW VALUES USED	-	CSU	VARIES
C				
C NOSTD	TRUNCATED VALUE OF STOND	-	CALC	*****
C				
C NN	NUMBER OF VARIABLE PARAMETERS FOR URG	-	CSU	VARIES
C				
C NSTDR	NUMBER OF STO'S IN THE FRONT OF EACH TRIP REQUIRING HIGHWAY DRIVING	-	NASA	28
C				
C NTINE	INTEGER INDICATING NUMBER OF TIME INCREMENTS OF DRIVING CYCLE ALREADY SIMULATED	-	CALC	*****
C				
C NTRIP	INDEX INDICATING WHICH TRIP IS BEING USED	-	CALC	*****
C				
C NTRIPX	MAXIMUM NUMBER OF TRIP TYPES	-	NASA	8
C				
C PAXLE	POWER REQUIRED AT AXLE	WATTS	CALC	*****
C				
C PCHMAX	BATTERY MAX CHARGING POWER	WATTS	NASA	33,600.
C				
C PCHOUT	BATTERY OUTPUT POWER	WATTS	CALC	*****
C				
C PCHG	HEAT ENGINE POWER USED TO CHARGE BATTERIES	WATTS	CALC	*****
C				
C PCVT	POWER REQUIRED AT CVT INPUT	WATTS	CALC	*****
C				
C PCVTMAX	MAXIMUM POWER RATING OF CVT	WATTS	NASA	90,000.
C				
C PDPOCT	DIFFERENTIAL OUTPUT POWER AS A PERCENT OF DIFFERENTIAL RATED POWER	PERCENT	CALC	*****
C				
C PDPRATE	DIFFERENTIAL RATED POWER (ALSO SEE DIFFKW)	WATTS	NASA	90,000.
C				
C PDRIIVE	POWER REQUIRED AT DRIVE SHAFT	WATTS	CALC	*****
C				

C PELEC	ELECTRIC POWER REQUIRED AT	WATTS	CALC	*****
C	INPUT TO CVT			
C				
C PLTCST(I)	ARRAY CONTAINING PETROLEUM	DOLLARS	CALC	*****
C	COSTS FOR YEAR I			
C				
C PETROL	PETROLEUM VOLUME USED	LITERS	CALC	*****
C	IN CURRENT TRIP			
C				
C PETSTC(I)	ARRAY WHICH SAVES AT THE END	LITERS	CALC	*****
C	OF EACH STC THE TOTAL PETROLEUM			
C	VOLUME USED SINCE THE START OF			
C	ALL STC'S			
C				
C PETYR(I)	ARRAY WHICH CONTAINS THE YEARLY	LITERS	CALC	*****
C	PETROLEUM CONSUMPTION FOR THIS			
C	PARTICULAR TRIP			
C				
C PGEAR	POWER REQUIRED AT INPUT TO GEAR	WATTS	CALC	*****
C	BETWEEN CVT AND DIFFERENTIAL			
C				
C PGPCY	OUTPUT POWER OF GEAR BETWEEN	PERCENT	CALC	*****
C	CVT AND DIFFERENTIAL AS A			
C	PERCENT OF GEAR RATED POWER			
C				
C PGRATE	RATED POWER FOR GEAR BETWEEN	WATTS	NASA	99,000.
C	CVT AND DIFFERENTIAL (SEE ALSO			
C	DFGRKW)			
C				
C PHE	HEAT ENGINE POWER REQUIRED AT	WATTS	CALC	*****
C	INPUT TO CVT			
C				
C PHEMAX	MAX OUTPUT POWER OF HEAT ENGINE	WATTS	CALC	*****
C				
C PHEST	ESTIMATED OUTPUT POWER OF HE	WATTS	CALC	*****
C	USED IN DETERMINING CVT RATIO			
C				
C PLOSS	INVERTER POWER LOSS	WATTS	CALC	*****
C				
C PINV	POWER REQUIRED AT OUTPUT OF	WATTS	CALC	*****
C	INVERTER			
C				
C PINVMX	MAX OUTPUT POWER OF INVERTER	WATTS	NASA	40,000.
C				
C PPGPCY	POWER AT OUTPUT OF GEAR BETWEEN	PERCENT	CALC	*****
C	MOTOR AND CVT AS A PERCENT OF			
C	GEAR RATED OUTPUT POWER			
C				
C PPGRTE	RATED OUTPUT POWER FOR GEAR	WATTS	NASA	40,000.
C	BETWEEN MOTOR AND CVT (ALSO			
C				

C	SEE MTRKW)			
C				
C	PNOTOR	ELECTRIC MOTOR OUTPUT POWER	WATTS	CALC *****
C				
C	PMT	ESTIMATED OUTPUT POWER OF MOTOR	WATTS	CALC *****
C		USED IN DETERMINING THE CVT RATIO		
C				
C	PMTMAX	ELECTRIC MOTOR MAX OUTPUT POWER	WATTS	NASA 40,000.
C		(ALSO SEE MMAX AND MTKWPK)		
C				
C	PMPCT	MOTOR OUTPUT POWER AS A PERCENT	PERCENT	CALC *****
C		OF RATED POWER (USED FOR RATIO		
C		CALC)		
C				
C	PNTRD	RATED POWER OF MOTOR (SEE ALSO	WATTS	NASA 20,000.
C		MTRKW)		
C				
C	POVRD	ACCUMULATION OF SQUARED VALUES	WATTS	CALC *****
C		OF PSHORT	SQUARED	
C				
C	PREGEN	POWER AVAILABLE FOR REGENERATION	WATTS	CALC *****
C		AFTER ROAD LOSSES		
C				
C	PROAD	VEHICLE POWER LOSS DUE TO ROAD	WATTS	CALC *****
C		LOSSES DURING BREAKING PHASE OF		
C		STC		
C				
C	PSHORT	DIFFERENCE BETWEEN DEMANDED POWER	WATTS	CALC *****
C		AND POWER PROPULSION SYSTEM CAN		
C		SUPPLY		
C				
C	PUKRT(CURRENT/KG)	PEUKERT CURVE	AMP-HOURS/KG	NASA HAVE
C				
C	PVBATT	VARIABLE USED TO PRINT VBATT	VOLTS	CALC *****
C		AND VBCHG		
C				
C	PWRSTP	TOTAL POWER AVAILABLE FOR	WATTS	CALC *****
C		REGENERATION DURING THIS TIME		
C		INCREMENT IN THE BREAKING		
C		PHASE OF THE STC		
C				
C	RCVT	CVT RATIO (OUTPUT SPEED	-	CALC *****
C		DIVIDED BY INPUT SPEED)		
C				
C	RCVTMN	MINIMUM ALLOWABLE CVT RATIO	-	NASA 0.0
C				
C	RCVTMX	MAX ALLOWABLE CVT RATIO	-	NASA 3.4
C				
C	RDIFF	GEAR RATIO OF DIFFERENTIAL (AXLE	-	NASA 1.0
C		SPEED DIVIDED BY SHAFT SPEED)		

C					
C	REGEFF	REGENERATIVE EFFICIENCY	-	CALC	*****
C					
C	REGEN(I)	ARRAY WHICH SAVES AT THE END OF EACH STC THE AMP HOURS REGENERATED INTO THE BATTERY SINCE THE START OF ALL STC'S	AMP-HOURS	CALC	*****
C					
C	REGNIN	MINIMUM POWER WORTH REGENERATING	WATTS	NASA	1,000.
C					
C	REPAIR	VEHICLE REPAIR COST FOR ONE YEAR	DOLLARS	CALC	*****
C					
C	REPCHT	CHOPPER INVERTER REPAIR COST	DOLLARS PER KILOMETER	CALC	*****
C					
C	REPCVT	CVT REPAIR COST	DOLLARS PER KILOMETER	CALC	*****
C					
C	REPMTN	ELECTRIC MOTOR REPAIR COST	DOLLARS PER KILOMETER	CALC	*****
C					
C	REPRHE	HEAT ENGINE REPAIR COST	DOLLARS PER KILOMETER	CALC	*****
C					
C	RGEAR	RATIO OF GEAR BETWEEN CVT AND DIFFERENTIAL (DRIVE SHAFT SPEED DIVIDED BY CVT OUTPUT SPEED)	-	NASA	0.0833
C					
C	RGRN	RATIO OF GEAR BETWEEN ELECTRIC MOTOR AND CVT (CVT INPUT SPEED DIVIDED BY ELEC. MOTOR SPEED)	-	NASA	0.2857
C					
C	RHO	AIR WEIGHT DENSITY	KILOGRAMS PER CUBIC METER	CSU	1.225
C					
C	RUN21	A VARIABLE READ IN:		ARB	
C		0 FOR 1 GCOMP CALL (WITH ONLY A SUMMARY SHEET PRINTED)			
C		1 FOR 1 GCOMP CALL (WITH B9 & A8 & SUMMARY SHEET PRINTED)			
C		2 FOR MAKING A LCCOST GRID WITH HEKW AND WGBATT AS THE AXIS			
C		3 FOR MAKING POWER SPLIT VS CONSUMPTION DATA			
C					
C	RTIRE	TIRE RADIUS	METERS	NASA	0.30
C					
C	SALVGE	SALVAGE VALUE OF VEHICLE	DOLLARS	CALC	*****
C					
C	SATORQ(I)	ARRAY OF SCALED TORQUES USED IN FUEL RATE CALC	NM	CALC	*****
C					
C					

C SFG(I)	ARRAY OF WEIGHTING FACTORS FOR ARRAY G	-	CSU	VARIES
C				
C SFX(I)	ARRAY OF WEIGHTING FACTORS FOR PARAMETERS OPTIMIZED BY GRG	-	CSU	VARIES
C				
C SOC	STATE OF CHARGE	-	CALC	*****
C				
C SOCL	THE MINIMUM STATE OF CHARGE ATTAINED BY THE BATTERY DURING ACCELERATION	-	CALC	*****
C				
C SOCMAX	MAXIMUM STATE OF CHARGE TO WHICH HE CHARGES BATTERY	-	NASA	0.3
C				
C SOCSTC(I)	ARRAY WHICH SAVES THE STATE OF CHARGE OF THE BATTERY AT THE END OF EACH STC	-	CALC	*****
C				
C STALL(WMT)	A FUNCTION WHICH GIVES THE MAX POWER FROM MOTOR FOR A GIVEN SPEED	% RATED POWER	NASA	HAVE
C				
C STCDIS	DISTANCE OF ONE STC	METERS	NASA	1,450.0
C				
C STCNO	NUMBER OF STC'S IN CURRENT TRIP	-	CALC	*****
C				
C TACCEL	TIME AT WHICH ACCELERATION PHASE OF STC ENDS	SECONDS	NASA	14.0
C				
C TAXLE	AXLE TORQUE	NEWTON METERS	CALC	*****
C				
C TBRAKE	TIME AT WHICH BRAKING PHASE OF STC IS REACHED	SECONDS	NASA	74.0
C				
C TCGAST	TIME AT WHICH COAST PHASE OF STC IS REACHED	SECONDS	NASA	64.0
C				
C TCVT	TORQUE AT INPUT TO CVT	NEWTON METERS	CALC	*****
C				
C TCYCLE	TIME REQUIRED TO DRIVE ONE DRIVING CYCLE (INCLUDING IDLING)	SECONDS	NASA	108.0
C				
C TORIVE	DRIVE SHAFT TORQUE	NEWTON METERS	CALC	*****
C				
C TGEAR	TORQUE AT INPUT TO GEAR BETWEEN CVT AND DIFFERENTIAL	NEWTON METERS	CALC	*****
C				
C THE	HEAT ENGINE OUTPUT TORQUE	NEWTON METERS	CALC	*****
C				

C	TIME	SIMULATION TIME	SECONDS	CALC	*****
C					
C	T MOTOR	OUTPUT TORQUE OF ELECTRIC MOTOR	NEWTON METERS	CALC	*****
C					
C	TOTBAT	FIRST YEAR EQUIVALENT TOTAL BATTERY REPLACEMENT COST (SEE TOTILE)	DOLLARS	CALC	*****
C					
C	TOTBS	FIRST YEAR EQUIVALENT BATTERY SALVAGE VALUE (THE AMOUNT OF MONEY INVESTED IN THE FIRST YEAR NECESSARY TO OBTAIN THE AMOUNT THE BATTERIES WOULD BE SOLD FOR IN THE TENTH YEAR)	DOLLARS	CALC	*****
C					
C	TOTELE	FIRST YEAR EQUIVALENT TOTAL ELECTRICAL ENERGY COSTS, OBTAINED BY COMPUTING THE SUM OF THE FIRST YEAR EQUIVALENT YEARLY COSTS, FOR ALL TEN YEARS, WHICH ARE AMOUNTS, WHICH IF INVESTED IN THE FIRST YEAR AT A FIXED INTEREST RATE, YIELD THE COST OF ELECTRICAL ENERGY FOR THE GIVEN YEAR	DOLLARS	CALC	*****
C					
C	TOTPET	FIRST YEAR EQUIVALENT TOTAL PETROLEUM COST USED DURING LIFE CYCLE (SEE TOTELE)	DOLLARS	CALC	*****
C					
C	TOTSAL	FIRST YEAR EQUIVALENT VEHICLE SALVAGE VALUE (SEE TOTBS)	DOLLARS	CALC	*****
C					
C	TRIPLN(I)	ARRAY WHICH CONTAINS THE LENGTH OF ALL THE REQUIRED TRIPS	METERS	NASA	I TRIPLN(I) 1 10,000.0 2 30,000. 3 50,000. 4 80,000. 5 130,000. 6 160,000. 7 500,000. 8 800,000.
C					
C	TRIPNO(I)	ARRAY CONTAINING NUMBER OF EACH OF THE INDIVIDUAL TRIPS PER YEAR	-	NASA	I TRIPNO(I) 1 130 2 85 3 57 4 54 5 12 6 7
C					



C				7	3
C				8	1
C					
C	TRIPM	TIME IT TAKES TO MAKE A PARTICULAR TRIP	SECONDS	CALC	*****
C					
C	TRIPYR	NUMBER OF TRIPS OF A PARTICULAR TYPE PER YEAR	-	CALC	*****
C					
C	TSTOP	TIME AT WHICH VEHICLE MUST STOP AT END OF STC	SECONDS	NASA	83.0
C					
C	V(I)	DRIVING CYCLE VELOCITY ARRAY (ENTRIES CALCULATED IN PROGRAM)	METERS PER SECOND	CALC	*****
C					
C	V1	VELOCITY AT END OF SIMULATION TIME STEP	METERS PER SECOND	CALC	*****
C					
C	V2	VELOCITY AT BEGINNING OF SIMULATION TIME STEP	METERS PER SECOND	CALC	*****
C					
C	VAVE	AVERAGE VELOCITY OVER ONE DRIVING CYCLE TIME INCREMENT	METERS PER SECOND	CALC	*****
C					
C	VBATT	BATTERY VOLTAGE DURING DISCHARGE	VOLTS	CALC	*****
C					
C	VBCHG	BATTERY VOLTAGE DURING CHARGING	VOLTS	CALC	*****
C					
C	VBOLD	VALUE OF BATTERY VOLTAGE FROM PREVIOUS ITERATION	VOLTS	CALC	*****
C					
C	VCELL	BATTERY CELL VOLTAGE (WHEN CELL IS FULLY CHARGED)	VOLTS	NASA	2.05
C					
C	VCHG(	BATTERY CELL CHARGE CURVE (AMP-HRS/KG, CURRENT)	CELL VOLTS	NASA	HAVE
C					
C	VDELT	MAX ALLOWABLE DIFFERENCE BETWEEN BATTERY VOLTAGE FROM LAST ITERATION AND PRESENT CALCULATED BATTERY VOLTAGE	VOLTS	CSU	1.0
C					
C	VELO	VELOCITY AT CURRENT TIME DURING COAST PHASE OF STC	METERS PER SECOND	CALC	*****
C					
C	VHCOST(I)	ARRAY CONTAINING YEARLY COST OF OPERATING VEHICLE	DOLLARS	CALC	*****
C					
C	VHMBTT	VALUE OF BATTERY VOLTAGE AT END	VOLTS	CALC	*****

C	OF STC'S PRECEEDING ALL HIGHWAY				
C	TRIPS				
C					
C	VINT	BATTERY INTERNAL VOLTAGE	VOLTS	CALC	*****
C					
C	VMINHE	VEHICLE VELOCITY BELOW WHICH	METERS PER	NASA	1.34
C		NO HEAT ENGINE POWER CAN BE	SECOND		
C		DEVELOPED			
C					
C	VNEXT	VELOCITY VEHICLE HAS COASTED TO	METERS PER	CALC	*****
C		AT END OF CURRENT TIME INCREMENT	SECOND		
C		DURING COAST PHASE OF STC			
C					
C	VOLTOT	TOTAL HEAT ENGINE FUEL VOLUME	LITERS	CALC	*****
C		USED SINCE START OF TRIP			
C					
C	WAXLE	ANGULAR SPEED OF AXLE	RADIANS PER	CALC	*****
C			SECOND		
C					
C	WCONST	CONSTANT TERM IN MASS FORMULA	KILOGRAMS	CALC	*****
C		FOR VEHICLE			
C					
C	WCURB	CURB MASS OF VEHICLE	KILOGRAMS	CALC	*****
C					
C	WCVT	SPEED AT INPUT TO CVT	RADIANS PER	CALC	*****
C			SECOND		
C					
C	WDRTE	DIFFERENTIAL RATED OUTPUT	RADIANS PER	NASA	116.35
C		SPEED	SECOND		
C					
C	WDPCT	DIFFERENTIAL OUTPUT SPEED AS	PERCENT	CALC	*****
C		A PERCENT OF DIFFERENTIAL			
C		RATED OUTPUT SPEED			
C					
C	WDRIVE	ANGULAR SPEED OF DRIVE SHAFT	RADIANS PER	CALC	*****
C			SECOND		
C					
C	WF	VEHICLE FIXED MASS	KILOGRAMS	NASA	510.0
C					
C	WFCER	CONSTANT USED TO CALCULATE	DOLLARS PER	NASA	3.13
C		THE COST OF THE FIXED WEIGHT	KILOGRAM		
C		OF THE VEHICLE			
C					
C	WFCOST	COST OF FIXED WEIGHT OF	DOLLARS	CALC	*****
C		VEHICLE			
C					
C	WGBATT	MASS OF BATTERIES	KILOGRAMS	NASA	386.0
C		WHEN RUN21=1 OR 2 = STARTING			
C		VALUE OF WGBATT			
C					

C	WGCHGR	MASS OF THE BATTERY CHARGER	KILOGRAMS	CALC	*****
C					
C	WGCHI	MASS OF THE CHOPPER INVERTER	KILOGRAMS	CALC	*****
C					
C	WGCLT	MASS OF CLUTCH	KILOGRAMS	NASA	0.0
C					
C	WGCVT	MASS OF THE CVT	KILOGRAMS	CALC	*****
C					
C	WGDIFF	MASS OF THE DIFFERENTIAL	KILOGRAMS	CALC	*****
C					
C	WGEAR	ANGULAR SPEED AT INPUT TO GEAR BETWEEN CVT AND DIFFERENTIAL	RADIANS PER SECOND	CALC	*****
C					
C	WGENG	MASS OF THE ENGINE	KILOGRAMS	CALC	*****
C					
C	WGEXTR	MASS OF EXTRA COMPONENTS IN VEHICLE PROPULSION SYSTEM	KILOGRAMS	NASA	0.0
C					
C	WGRDF	MASS OF THE GEAR BETWEEN THE DIFFERENTIAL AND THE CVT	KILOGRAMS	CALC	*****
C					
C	WGGRM	MASS OF THE GEAR BETWEEN THE ELECTRIC MOTOR AND THE CVT	KILOGRAMS	CALC	*****
C					
C	WGNTR	MASS OF THE ELECTRIC MOTOR	KILOGRAMS	CALC	*****
C					
C	WGORTE	RATED OUTPUT SPEED FOR GEAR BETWEEN CVT AND DIFFERENTIAL	RADIANS PER SECOND	NASA	116.35
C					
C	WGPCT	OUTPUT SPEED OF GEAR BETWEEN CVT AND DIFFERENTIAL AS A PERCENT OF RATED OUTPUT SPEED	PERCENT	CALC	*****
C					
C	WHE	HEAT ENGINE ANGULAR SPEED	RADIANS PER SECOND	CALC	*****
C					
C	WHEFF	MOST EFFICIENT ENGINE SPEED FOR A SPECIFIED POWER OUTPUT	RADIANS PER SECOND	CALC	*****
C					
C	WHEMN	MIN ENGINE SPEED	RAD/SEC	CSU/NASA	104.72
C					
C	WHORTE	RATED OUTPUT SPEED FOR GEAR BETWEEN MOTOR AND CVT	RADIANS PER SECOND	NASA	419.0
C					
C	WNOTOR	ELECTRIC MOTOR ANGULAR SPEED	RADIANS PER SECOND	CALC	*****
C					
C	WNT	MOTOR SPEED COMPUTED IN RATIO SUBROUTINE	RADIANS PER SECOND	CALC	*****
C					
C					

C	WTRMX	MAX SPEED OF MOTOR	RAD PER SEC	CSU	1,675.5
C					
C	WP	POWER TRAIN WEIGHT	KILOGRAMS	CALC	*****
C					
C	WPL	MAXIMUM DESIGN PAYLOAD FOR VEHICLE	KILOGRAMS	NASA	415.0
C					
C	WPROP	MASS OF VEHICLE PROPULSION SYSTEM	KILOGRAMS	CALC	*****
C					
C	WS	MASS OF STRUCTURE AND CHASSIS FOR VEHICLE	KILOGRAMS	CALC	*****
C					
C	WSCER	CONSTANT USED TO CALCULATE THE COST OF THE STRUCTURE AND CHASSIS FOR THE VEHICLE	DOLLARS PER KILOGRAM	NASA	3.00
C					
C	WSCOST	COST OF STRUCTURE AND CHASSIS FOR VEHICLE	DOLLARS	CALC	*****
C					
C	WT	TOTAL MASS OF VEHICLE AND PROPULSION SYSTEM	KILOGRAMS	CALC	*****
C					
C	WTL	TEST PAYLOAD FOR VEHICLE	KILOGRAMS	NASA	207.0
C					
C	XX	ARRAY OF PARAMETERS OPTIMIZED BY GRG	MIXED	CALC	*****
C					
C	Z	OVERALL GRG LARGE MAIN ARRAY	-	CALC	*****
C					
	STOP				
	END				
	END				

## APPENDIX B - CALCULATION OF VEHICLE MASS

This appendix details the method used to calculate the vehicle mass. The variable names used below correspond to the names used in the dictionary in Appendix A and also in the computer program. To obtain actual values used for any constants, refer to Appendix A. The overall vehicle mass formula is the same as that used in [1, 2]. The component mass formulas and the values for constants used in those formulas substantially agree with those found in [1, 5]. In the following, all masses are in kg.

### Total Mass Calculation

If we let

WCONST = constant term in the total mass formula

WF = fixed mass of the vehicle (510 kg)

WPL = design payload (415 kg)

WPROP = mass of propulsion system

WT = total mass of vehicle

WTL = test payload (207 kg)

then

$$WCONST = WTL + \frac{0.23 (WPL) + WF}{0.77} \quad (B-1)$$

and

$$WT = WCONST + \frac{WPROP}{0.77} \quad (B-2)$$

The mass of the propulsion system, WPROP, is calculated below.

### Propulsion System Mass Calculation

We let (where the masses are in kg, and the component power ratings are in kw):

WGBATT = battery mass	WGENG = engine mass
WGCHGR = battery charger mass	WGGRM = mass of gear between motor and CVT
WGCLT = clutch mass	CVTKW = power rating of CVT
WGCVT = CVT Mass	HEKW = power rating of heat engine
WGMOTR = traction motor mass	DIFFKW = power rating of differential
WGRDF = mass of gear between differential and CVT	MTGRKW = power rating of gear between motor and CVT
MTRKW = power rating of traction motor	DFGRKW = power rating of gear between CVT and differential
CHIKW = power rating of chopper/inverter	CHGRKW = power rating of battery charger
WGCHI = chopper/inverter mass	
WGDIFF = differential mass	

The quantities CVTC1, HEC2, MTRC1, CHIC1, DIFFC1, GRC1, CHGRC1 are all constants used below in the mass formulas; their values are given in Appendix A.

Using the quantities defined above, the component masses and the propulsion system mass are given by

$$WGCVT = CVTC1 * CVTKW \quad (B-3)$$

$$WGENG = HEC2 * HEKW \quad (B-4)$$

$$WGMOTR = MTRC1 * MTRKW \quad (B-5)$$

$$WGCHI = CHIC1 * CHIKW \quad (B-6)$$

$$WGDIFF = DIFFC1 * DIFFKW \quad (B-7)$$

$$WGGRM = GRC1 * MTGRKW \quad (B-8)$$

$$WGRDF = GRC1 * DFGRKW \quad (B-9)$$

$$WGCHGR = CHGRC1 * CHGRKW \quad (B-10)$$

and

$$\begin{aligned} WPROP = & WGCVT + WGENG + WGMOTR + WGCHI + WGDIF + WGGRM \\ & + WGRDF + WGCHGR + WGBATT + WGCLT \end{aligned} \quad (B-11)$$

In addition, the curb mass, WCURB, and the power train mass, WP, are given by

$$WCURB = WT - WTL \quad (B-12)$$

and

$$WP = WPROP - WGBATT \quad (B-13)$$

APPENDIX C - CALCULATION OF MANUFACTURING,  
MAINTENANCE, AND REPAIR COSTS

This appendix details the methods used to calculate the vehicle manufacturing, maintenance and repair costs. The variable names used below correspond to the names used in the dictionary in Appendix A and also in the computer program. To obtain actual values used for any of the constants, refer to Appendix A. The formulas and values for the constants used in these calculations are taken from [1, 4]. The component masses used below are calculated in Appendix B.

Manufacturing Costs

We let (where the masses are in kg)

WF = vehicle fixed mass	WGENG = engine mass
WGCVT = CVT mass	WGCHGR = battery charger mass
WGCHI = chopper/inverter mass	WGGRM = mass of gear between motor & CVT
WGDIFF = mass of differential	WGGRDF = mass of gear between differential and CVT
WS = structure and chassis mass	WGMOTR = mass of motor
WCURB = curb mass	WGCLT = mass of clutch

In addition, HECER, CVTCER, CHGCER, CHICER, GRCER, DIFCER, WFCER, WSCER, MTRCER, CLTCER and ASMCER are the various component cost estimating ratios (CER's) in \$/kg. The component costs are then calculated as

$$\text{HECOST} = \text{HECER} * \text{WGENG} \quad (\text{C-1})$$

$$\text{CVTCST} = \text{CVTCER} * \text{WGCVT} \quad (\text{C-2})$$

$$\text{CHGCST} = \text{CHGCER} * \text{WGCHGR} \quad (\text{C-3})$$

$$\text{CHICST} = \text{CHICER} * \text{WGCHI} \quad (\text{C-4})$$



$$\begin{aligned} \text{GRMCST} &= \text{GRCER} * \text{WGGRM} && \text{(C-5)} \\ \text{GRDCST} &= \text{GRCER} * \text{WGGRDF} && \text{(C-6)} \\ \text{DIFCST} &= \text{DIFCER} * \text{WGDIFF} && \text{(C-7)} \\ \text{WFCOST} &= \text{WFCER} * \text{WF} && \text{(C-8)} \\ \text{WS} &= 0.3 * (\text{WPL} + \text{WPROP} + \text{WF}) && \text{(C-9)} \\ \text{WSCOST} &= \text{WSCER} * \text{WS} && \text{(C-10)} \\ \text{MTRCST} &= \text{MTRCER} * \text{WGMOTR} && \text{(C-11)} \\ \text{CLTCST} &= \text{CLTCER} * \text{WGCLT} && \text{(C-12)} \\ \text{ASMCST} &= \text{ASMCER} * \text{WCURB} && \text{(C-13)} \end{aligned}$$

The manufacturing cost is then the sum of these twelve component costs. Note that the battery cost is handled separately and is not included in the manufacturing cost (it is included in the calculation of acquisition cost in Section 5). Note also that the above manufacturing cost includes (in addition to the component costs) an assembly cost (ASMCST), a structure/chassis cost (WSCOST), and a fixed weight cost (WFCOST).

#### Maintenance Costs

It is assumed that maintenance is performed on the heat engine, motor, battery and chopper/inverter. HEMAIN, MTMAIN, BTMAIN, CVTMAN and CHIMAN are component maintenance costs (\$/km), HEKW and MTKWPK are component power ratings (kw), BTLIST, BATCST and BTMKUP are battery list price, battery cost and battery markup factor, respectively, WGBATT and WGCHI are the weights of the battery and the chopper/inverter (kg), respectively, and BATCER and KMPYR are the battery CER and the kilometers driven per year, respectively. With these definitions, the total yearly maintenance cost, MAINT, in dollars, is given as

$$\text{MAINT} = \text{KMPYR} * (\text{HEMAIN} + \text{MTMAIN} + \text{BTMAIN} + \text{CVTMAN} + \text{CHIMAN}) \quad (\text{C-14})$$

where

$$\text{HEMAIN} = [0.18 + 0.005 * (\text{HEKW} / 0.746)] / 160.93 \quad (\text{C-15})$$

$$\text{MTMAIN} = [0.06 + 0.002 * (\text{MTKWPK} / 0.746)] / 160.93 \quad (\text{C-16})$$

$$\text{BATCST} = \text{BATCER} * \text{WGBATT} \quad (\text{C-17})$$

$$\text{BTLIST} = \text{BATCST} * (1.0 + \text{BTMKUP}) \quad (\text{C-18})$$

$$\text{BTMAIN} = (0.004 * \text{BTLIST}) / 160.93 \quad (\text{C-19})$$

$$\text{CVTMAN} = 0.063 / 160.93 \quad (\text{C-20})$$

$$\text{CHIMAN} = [(36.83 / 2.0) * \text{SQRT}(\text{WGCHI})] / (10.0 * \text{KMPYR}) \quad (\text{C-21})$$

Most of the above expressions are taken from [4]. However, the chopper/inverter maintenance cost is taken from [1], but with the modification that half of the cost is assigned to maintenance and half to repair.

#### Repair Costs

It is assumed that repair is performed on the heat engine, motor, chopper/inverter and CVT. The yearly repair cost, REPAIR, in dollars, is given as

$$\text{REPAIR} = \text{KMPYR} * (\text{REPRHE} + \text{REPMTR} + \text{REPCVT} + \text{REPCHI}) \quad (\text{C-22})$$

where REPRHE, REPMTR, REPCVT and REPCHI are the component repair costs (\$/km) calculated from (HEKW, MTKWPK, WGCHI and KMPYR are all defined above)

$$\text{REPRHE} = [0.28 + 0.008 * (\text{HEKW} / 0.746)] / 160.93 \quad (\text{C-23})$$

$$\text{REPMTR} = [0.09 + 0.002 * (\text{MTKWPK} / 0.746)] / 160.93 \quad (\text{C-24})$$

$$\text{REPCVT} = [0.05 + 0.0013 * (\text{MTKWPK} / 0.746)] / 160.93 \quad (\text{C-25})$$

$$\text{REPCHI} = [(36.83 / 2.0) * \text{SQRT}(\text{WGCHI})] / (10.0 * \text{KMPYR}) \quad (\text{C-26})$$

## APPENDIX D - CALCULATION OF ACQUISITION COST

The acquisition cost is a combination of the manufacturing cost of the vehicle drive train and body and the cost of the batteries. The vehicle acquisition cost, ACQCST, in dollars, is given as

$$ACQCST = MARKUP * MNFCST + BATCST * (1.0 + BTMKUP) \quad (D-1)$$

where MARKUP is the manufacturing cost markup factor, MNFCST is the manufacturing cost (calculated in Appendix C), BATCST is the battery cost, and BTMKUP is the battery markup factor. BATCST and MARKUP are calculated from (the ex-pression for MARKUP is taken from [4])

$$BATCST = BATCER * WGBATT \quad (D-2)$$

$$MARKUP = (29.176 * 10^{-5}) * MNFCST + 1.40833 \quad (D-3)$$

and where WGBATT is the battery weight, and BATCER is the battery cost estimating ratio (CER).

## APPENDIX E - VEHICLE SIMULATION

For each choice of the design variables (battery weight, heat engine rating and power split strategy) it is necessary to simulate the vehicle as it is driven over the specified yearly driving requirements (Section 4) in order to calculate yearly electrical energy and petroleum consumptions, the number of deep discharges of the battery per year, and whether at any point in any of the trips the on-board energy is insufficient to meet the power required at the wheels. This appendix gives the details of how that simulation was carried out. It includes a description of how each component in the power train was modeled as well as a description of the overall computational procedure used to determine the power required from each of the on-board energy sources at each instant of time in driving an STC or in highway driving. Reference should be made to Section 3.1 and Figure 3-1 for a description and diagram of the overall propulsion system and how the various components described below are interconnected.

### E.1 COMPONENT MODELS

In this part of the appendix we describe the methods used to model each of the components in the drive train. It should be noted that this is a simulation of the steady state rather than the dynamic behavior of the vehicle: the component models are therefore steady state rather than dynamic models.

Battery Model: Of all the component models, the battery model is the most complex. Because of this complexity it is described in depth in its own appendix, Appendix F.


Heat Engine Model: The heat engine model used was a heat engine map [1] which plotted fuel flow rate (liters/sec) against engine speed (rad/sec) for a given engine torque (Nm). The map consisted of a set of such curves

for different torques as shown in Figure E-1. The map was used to determine fuel flow rate corresponding to a known engine output torque and speed. The maps were stored as arrays, and double variable linear interpolation was used. The actual maps used in this study were the same as those used in [1], but with an added degree of complexity. In this study the heat engine rating was continually changed in a smooth fashion as the optimization algorithm searched for the optimum. Consequently, maps for any rating between a maximum and minimum rating had to be easily generated to carry out the optimization. From interpolation studies using the three maps given in [1] for ratings of 56 kw, 75 kw and 112 kw, it was found that the other maps could be generated from the 75 kw map by leaving the engine speed axis alone, and multiplying the fuel flow rate ordinate and the torque corresponding to each curve by a factor equal to the rating of the engine whose map is sought divided by 75. Thus, at the beginning of each simulation run, the map array for the given heat engine used for that simulation run would be generated and stored. Then at each simulation time increment, that array would be used with a double variable linear interpolation scheme to determine the fuel flow rate during that time increment.

Chopper/Inverter: The characteristic of the chopper/inverter that required modeling for the instantaneous power calculations was the power loss in the device. The model used was the same as that used in [1,2] and is given as

$$PILOSS = 3.0*(PINV/VBATT) + 0.035*PINV \quad (E-1)$$

where PINV and VBATT are the chopper/inverter output power and battery voltage, respectively. The ratio (PINV/VBATT) is an estimate of the current

Figure E-1 Heat Engine Map

being drawn from the battery.

Electric Motor: The traction motor was a brushless, DC, permanent-magnet motor operating from a battery voltage of 168 V. It was rated at 20 kw and had a top speed of 14,000 rpm. The model for the motor was taken from [1] and is an efficiency map with motor efficiency plotted against percent rated output power (see PMTRTD and PMTPCT in dictionary) for a given motor speed. The map is shown in Figure E-2. However, in using the map it must be recognized that there is a stall-out speed for each percent rated output power: for the given output power the motor cannot be run below this speed without stalling. The stall-out map is used in selecting the CVT ratio; the stall-out map actually used for this motor is given in Appendix G where the ratio selection is discussed.

Continuously Variable Transmission (CVT): The CVT provides a range of ratios (input speed/output speed) which vary continuously from a 0.3:1 overdrive to a 3.33:1 speed reduction. The CVT model [1] is an efficiency map as shown in Figure E-3 where efficiency is plotted against output power for a given ratio.

Gears and Differential: The differential (with a speed ratio of 1:1) and the gears between the electric motor and the CVT input (providing a speed reduction from motor to CVT of 3.5:1) and between the CVT output and the differential input (providing a speed reduction of 12:1 from CVT to differential) were all modeled by the same efficiency map shown in Figure E-4 where gear efficiency is plotted against percent rated output power for a given percent rated input speed. The rated powers and speeds for the different gears are PDRATE, WDORTE, PMGRTE, WMORTE, PGRATE and WGORTE, and are found in the dictionary in Appendix A.






Figure E-2. Electric Motor Efficiency Map




Figure E-3. CVT Efficiency Map




Figure E-4 Gear Efficiency Map

## E.2 CALCULATION OF POWER REQUIRED AT THE AXLE DURING THE ACCELERATION AND CRUISE PHASES OF THE STC AND DURING HIGHWAY DRIVING

The power required at the axle is determined by summing the forces acting on the vehicle and multiplying this by the average velocity over the present simulation time increment. In particular, if the simulation time increment is  $\Delta$  and current time is  $t$ , then the average velocity over the current simulation time interval is

$$V_a = (1/2) [v(t) + v(t+\Delta)] \quad (E-2)$$

where  $v(t)$  is the vehicle velocity at time  $t$ . The required acceleration over this time interval is

$$a(t) = [v(t+\Delta) - v(t)]/\Delta \quad (E-3)$$

If  $F_D$ ,  $F_R$ ,  $F_A$  and  $F_G$  are the drag force, rolling resistance force, acceleration force and grade angle force, respectively, then

$$F_D = C_d A \rho (V_a^2/2) \quad (E-4)$$

$$F_R = C_R M_T g \quad (E-5)$$

$$C_R = [10.0 + 0.01V_a + (8 \times 10^{-5}) V_a^2] \times 10^{-3} \quad (E-6)$$

$$F_A = (1.1) M_T V_a \quad (E-7)$$

$$F_G = M_T g \sin (\beta) \quad (E-8)$$

where all the forces are in newtons,  $g$  is the acceleration of gravity,  $M_T$  is the vehicle mass (kg),  $\beta$  is the grade angle at the current simulation time,  $C_d A$  is the aerodynamic drag coefficient multiplied by the vehicle frontal area ( $C_d A = 0.6 \text{ m}^2$ ) and  $\rho$  is the air weight density ( $\rho = 1.225 \text{ kg/m}^3$ ). The factor of 1.1 in the expression for  $F_A$  takes into account accelerating the rotating inertias in the vehicle drive train. The power required at the axle at the current time is therefore given as

$$P_A = (F_D + F_R + F_A + F_G) V_a \quad (E-9)$$

The axle torque and speed,  $T_A$  and  $W_A$ , are obtained from

$$W_A = V_a/R_T \quad (E-10)$$

$$T_A = P_A/W_A \quad (E-11)$$

where  $R_T$  is the tire radius.

### E.3 DRIVE TRAIN POWER CALCULATIONS FOR ACCELERATION AND CRUISE PHASES OF STC AND FOR HIGHWAY DRIVING

At each time step in the simulation a calculation is made to determine the petroleum and electrical energy consumed in that time step. This is done by moving the power required at the axle (see Section E.2) back through each component in the drive train. In the following discussion reference should be made to the component models given in Section E.1. It should be noted that the maps used in the calculations consist of data arrays, and a double variable or single variable linear interpolation routine (whichever is appropriate) is used to locate points not in the arrays.

Knowing the power, speed and torque at the axle, the differential efficiency map and ratio is used to determine the power, speed and torque at the input to the differential. The same exact calculation is then made to determine the power, speed and torque at the input to the gear between the CVT and the differential. At this point in the power train calculation the CVT ratio is determined so that the heat engine is run at its most efficient speed for the heat engine's current power level (this method of ratio selection is discussed in detail in Appendix G). Once the CVT ratio is known, along with the CVT output power, speed and torque, the CVT efficiency map and ratio can be used to determine the power, speed and torque at the input to the CVT. This CVT input power is then split between the heat engine and the electric motor

and batteries using the power split strategy currently in force in the simulation; no matter what power split strategy is in use, the outcome is an allocation of a fraction of the total CVT input power to the heat engine and the remainder to the motor and batteries. There is a maximum allowable heat engine power, and the simulation off loads any excess to the electrical leg if the power split calls for more than the heat engine can deliver.

Once the heat engine output power and speed are known (the heat engine is directly connected to the CVT input so that its speed is the same as the CVT input speed), the heat engine output torque can be calculated (power/speed) and used in conjunction with the speed to determine the fuel flow rate from the heat engine map. This fuel flow rate is then multiplied by the simulation time step size to determine the fuel consumption for the present simulation time increment. The computation of the total yearly fuel consumption using these fuel increments is discussed in Section 5.

The electrical leg computation proceeds by first calculating the power, torque and speed at the input to the gear between the motor and CVT by using the gear output power (from the power split) and speed in conjunction with the gear map and the known gear ratio. The motor input power can then be calculated using this output power and speed and the motor efficiency map. This establishes the power which must be supplied by the chopper/inverter.

The loss in the chopper/inverter is modeled by an equation requiring the chopper/inverter output power, which is known, and the battery current, which is not known at this point in the calculation. However, it is reasonable to assume that (i) if the simulation time step is small, the battery voltage does not change significantly from one simulation time step to the next, and (ii) the losses in the chopper/inverter are small. Under these assumptions,

the battery current for the present time increment (for use in the chopper/inverter loss equation) can be estimated by dividing the battery voltage at the last simulation increment into the present chopper/inverter output power and using this result in the chopper/inverter loss equation. This procedure allows calculation of the required battery output power.

To calculate the battery voltage, current and state of charge requires use of the battery model and an iterative procedure. An iteration procedure is required because the present battery current is not known, yet this current is required in order to use the battery model to calculate battery voltage and state of charge. At this point in the calculation, the only battery quantities which are known are the battery present output power, and the battery current, voltage and state of charge which existed at the last simulation time increment. The iterative procedure used to arrive at present values for these last three quantities is to guess at the present battery voltage (using the value from the last simulation time step; at start-up the battery is fully charged and the first value is the system voltage) and divide this into the known output power to obtain an estimate of the battery current. Knowing the output current, the battery model (Appendix F) is used to calculate a battery state of charge and voltage. This new battery voltage is then compared to the assumed value: if it differs by less than a specified limit (VDELT in Appendix A) the calculation is completed; if the difference is greater, the new voltage is assumed to be the battery voltage, a new current is computed and the process is repeated. An upper limit on the number of such iterations was used, but the process always converged in three or less iterations.

At this point the drive train power calculation is complete and the sim-

ulation moves to the next time interval. However, there are a number of special features in the drive train power calculation related to limiting which should be mentioned.

First, there are limits on the heat engine power and the electrical energy available at any instant of time in the simulation. If the power required at the CVT input is split in such a way that either the electrical leg or the heat engine leg cannot meet the demand, a calculation is made to determine the maximum power available from the limiting leg, this is moved through any components between the source and the CVT input, and the other leg's demand is increased by the appropriate amount (with the other leg's power calculation redone if necessary). If a situation arises in which both power sources together cannot meet the total demand, the vehicle is considered to be overloaded. The topic of overload is discussed in detail in Section 6.

In the battery calculation it is important to make sure the battery current does not exceed a maximum value (this limit must be scaled each time the battery mass is changed). As described above, the battery current is computed by dividing the battery voltage into the battery output power. If this current turns out to be excessive (at low battery voltages) when the battery calculation is finished, the available power from the battery must be estimated (by multiplying the maximum allowable current by the battery voltage just calculated), the battery calculation redone, this new battery output power moved through the electrical leg components to the CVT input, and the difference between the total power and the available electrical power made up by increasing the heat engine required power and redoing the heat engine leg computation.



#### E.4 CALCULATIONS FOR COASTING PHASE OF THE STC

In the coasting phase of the STC the vehicle simply coasts for ten seconds (see Section 4). The coasting phase always begins at the same cruise velocity of 72 km/hr, but the velocity the vehicle has at the end of the coast period (and hence the amount of energy available for regeneration) depends upon the battery weight and heat engine rating (the rating determines the engine weight); consequently the coast phase final velocity changes during a simulation run and the coast period must be simulated for each STC.

The velocity at the end of the coast phase was computed as follows. For each time step in the coast phase the current values for the drag, rolling resistance and grade forces (using the vehicle velocity at the beginning of the time step) were computed (see Section E.2). Adding these, dividing by the vehicle mass and multiplying by the time step size (DELTA) yielded the decrease in vehicle velocity over the current simulation step. This was repeated for each time step in the coast phase to determine the vehicle velocity at the end of the coast phase.

#### E.5 CALCULATION OF DRIVE TRAIN POWER REGENERATION DURING THE BRAKING PHASE OF THE STC

In regenerating power back into the battery it was assumed that if the power available at any time fell below some minimum (REGMIN), regeneration would stop and the vehicle would come to rest through normal braking. Also, if in the drive train calculation the regenerated power at the input to any component exceeded that component's maximum rating, the power passed on was assumed to be equal to that maximum, and the difference was assumed to be dissipated by normal braking.

The first step in the calculation in each simulation time increment is to determine the regenerative power available at the axle for that time increment. Knowing the velocity at the start of the braking phase, and the length of time allowed for braking, the velocity decrease and the average velocity for each simulation time step can be determined. The velocity decrease over the time step is used to calculate the decrease in kinetic energy the vehicle must undergo in that time step; dividing this by the time step yields the vehicle total power reduction over that time interval. The average velocity is used to compute the drag, rolling resistance and grade forces, and these are then added and multiplied by the average velocity to obtain the power lost to the road in the time interval. The difference between these two powers is the power available for regeneration. The calculation then proceeds in a manner similar to that used in the drive train power calculation during acceleration and cruise (Section E.3): the power is moved through each component (differential, gear, CVT, gear, motor, and chopper/inverter), but with the difference that the component efficiencies multiply the output power to obtain the input power, rather than divide it as was the case earlier. When the battery is finally reached, the battery input power is known, but the current and voltage are not known. An iterative scheme is therefore again needed which guesses a battery voltage, uses that to calculate a battery current, and then uses this current with the battery charging model to calculate a battery voltage and state of charge. If the assumed and calculated voltages do not agree, the calculated value is used as a new starting point and the process repeated. This scheme was also found to converge rapidly (less than three iterations). Care must be taken to check that

battery input power and current do not exceed maximums (which change with changing battery mass).

## APPENDIX F - BATTERY MODEL

The model used for the battery is based on the model described in [3]. The batteries are assumed to be lead-acid batteries with a system voltage of 168 volts, a cell voltage of 2.0 volts and 84 cells connected in series.

### F.1 SCALING THE BATTERY MODEL

In the optimization studies the battery mass is continually changed. This change is interpreted as a change in the mass of each cell; the number of cells in the battery is assumed to be constant at 84. To handle this situation, all of the battery maps (discussed in the next subsection) were scaled (where necessary) so that they represented a battery comprised of one-kilogram cells. Calculations were therefore carried out on a per kilogram basis, and the results then scaled back up to the actual mass of each cell. The actual mass of each cell is equal to the total battery mass divided by 84. The way in which the maps were scaled should be clear from the discussions in the following subsections.

### F.2 CALCULATION OF BATTERY VOLTAGE AND STATE OF CHARGE DURING DISCHARGE IN HIGHWAY DRIVING AND IN THE ACCELERATION AND CRUISE PHASES OF AN STC

Using the battery model given in [3], the battery voltage and state of charge at any time instant in the simulation are calculated as follows. First, the average current since the start of the trip (assuming a fully charged battery at the start of the trip) is calculated as

$$I_A = (1/T) \int_0^T i(t) dt \quad (F-1)$$

where  $T$  is the length of time into the trip, and  $i(t)$  is the current at any time  $t \in [0, T]$ . In the simulation,  $I_A$  was actually computed by dividing the ampere-hours (amp-hrs) out of the battery by  $T$  (ignoring regeneration). The current out of each cell (and out of the battery since the cells are in series) on a per kilogram basis is  $(I_A/M_C)$ , where  $M_C$  is the mass of a cell, i.e.  $M_C = M_B/N_C$  where  $M_B$  is the battery mass and  $N_C$  the number of cells. This average battery output current per cell kilogram is then used in conjunction with the scaled Peukert curve, Figure F-1, to determine the capacity per kilogram (amp-hrs/kilogram),  $AH_1$ , available from each cell in the battery (and hence the capacity per kilogram available from the battery) if the battery is discharged at a current equal to the average current per kilogram computed above. The total capacity from a battery with cells of mass  $M_C$  is then  $AH_2 = M_C AH_1$ . Next, the net amp-hours out of the battery since the start of the trip is computed as

$$AH_3 = TI_A - AH_R \quad (F-2)$$

where  $T$  and  $I_A$  are as defined above, and  $AH_R$  is the total amp-hrs regenerated into the battery (since the start of the trip) during the braking phases of the STC's. The battery state of charge, SOC, at the current time is, then,

$$SOC = 1 - (AH_3/AH_2) \quad (F-3)$$

The battery voltage is obtained from the battery discharge characteristic shown in Figure F-2. This discharge characteristic gives cell voltage as a function of both state of charge and cell current for a cell of a given




Figure F-1. Scaled Peukert Curve




Figure F-2 Battery Discharge Characteristic

mass. Since the batteries are not used if the SOC drops below 0.2, the cell voltage is assumed constant below this SOC. If the mass of the cell changes, the internal resistance will change (increasing cell mass is interpreted to mean more plate area, hence a smaller interval resistance). This is handled by multiplying the battery current by  $(M_{STND}/M_C)$  where  $M_C$  is the cell mass and  $M_{STND}$  is the mass of the standard cell (taken to be 9.83 kg) used in generating the discharge curve in Figure F-2. This scaled current is then used with the state of charge to enter the discharge characteristic and determine the cell voltage. Finally, the battery voltage is obtained by multiplying the cell voltage by the number of cells in the battery.

### F.3 BATTERY CHARGING AT END OF TRIP

This section presents the details of the calculations involved in determining the wall plug electrical energy required to charge the battery to a fully charged condition after a trip is completed. Calculations for regeneration back into the battery during the braking phase of an STC is covered in Section F.4. At the end of a trip the net amp-hours out of the battery is known; net amp-hours is the difference between total amp-hours out and amp-hours put back from regeneration during the braking phases of STC's driven in the trip. If  $AH_N$  is this net amp-hours out, then the amp-hours delivered per kilogram for a cell is  $AH_N/M_C$ , where  $M_C$  is the mass of a cell. Assuming a charging current of 25 amps, the charging characteristic for a cell (on a per kilogram basis) shown in Figure F-3 can be entered at  $AH_N/M_C$  and an average charging voltage for a cell can be determined; multiplying this by the number of cells gives an average charging voltage for the battery. In the actual simulation, an additional map (AACV in Appendix A) was generated from the






Figure F-3. Battery Cell Charging Characteristic

charge characteristic which gave the average charging voltage (for a charging current of 25 amps) as a function of  $AH_N/M_C$ . Multiplying this average battery charging voltage by the net amp-hours out determines the electrical energy needed from the charger to recharge the battery. Finally, dividing this energy figure by the charger efficiency yields the total wall plug energy required to recharge the batteries.

#### F.4 CALCULATION OF BATTERY VOLTAGE AND STATE OF CHARGE DURING REGENERATION IN THE BRAKING PHASE OF AN STC

Appendix E covers the details of the calculation procedure used to determine how much of the vehicle power at the wheels available for regeneration during the braking phase of an STC actually arrives at the battery terminals at each time increment in the simulation (taking into account efficiencies and maximum power levels of the drive train components). This section explains how that power alters the battery voltage and state of charge. As explained in Appendix E, at each time step in the simulation the regenerated power calculation determines a regenerated power at the battery terminals (PBOUT) and a battery current (IEFF). The current and power to be regenerated must be limited by the maximum current and power that the battery can handle, and these limits must be scaled each time the battery mass is changed by the ratio of the present battery mass to a standard battery mass. At this point in the regeneration calculation, the calculation of the battery SOC is carried out; this calculation is exactly the same as described in Section F.2, with the exception that the most recent current increment in the calculation of  $I_A$  is negative (current is now into the battery) or, if amp-hours are used to calculate  $I_A$ , the regenerated amp-hrs are increased for the most

recent simulation increment, the net amp-hours out of the battery is computed (total out minus regenerated) and  $I_A$  calculated from these net amp-hrs out.

The battery voltage is calculated from the charge characteristic given in Figure F-3. Specifically, the net amp-hours used in calculating  $I_A$  above is divided by the cell mass to determine the net amp-hrs per kilogram for a battery cell. Then, using both the effective battery current (IEFF) mentioned above and this cell net amp-hrs per kilogram in conjunction with the battery charge characteristic in Figure F-3, a cell charging voltage is determined. Multiplying this by the number of cells in the battery yields a battery voltage for the present simulation time increment. In the actual battery calculation an iteration scheme is required because the current (IEFF) is not really known a priori to allow determination of the battery voltage from the charging characteristic (see Appendix E for a description of this iterative procedure).

## APPENDIX G - CVT RATIO SELECTION PROCEDURE

In this study the CVT ratio was selected (at each time step in the simulation) such that the heat engine was operated at its most efficient speed. The reason for employing this approach rather than the approach used in [1] in which the ratio was selected to operate the traction motor at its most efficient speed was that the traction motor efficiency was always in the range of 90% or above (Appendix E) whereas the heat engine efficiency could be substantially improved by proper choice of the ratio.

The most efficient heat engine speed for a given engine output power was determined from the Brake Specific Fuel Consumption (BSFC) map for a 75 kw engine shown in Figure G-1. Each characteristic on the map is engine BSFC (in grams/sec of petroleum flow rate per megawatt of output power) as a function of engine output power (in percent of rated power) with engine speed held constant. For example, if the engine speed is held constant at 104.7 rad/sec, the BSFC decreases as the engine output power increases from zero to 25% of rated output power (more power output from the engine requires a higher engine speed; the characteristic essentially stops at 25% of rated power). Also, for a given output power, the speed corresponding to the characteristic with the lowest BSFC represents the most efficient operating speed since for that output power that particular speed produces the lowest fuel flow rate. For example, for output powers below 30%, the most fuel efficient engine speed is 104.7 rad/sec; at 50% it is 209.4 rad/sec; at 75% it is 314.12 rad/sec; at 100% it is 418.9 rad/sec. For intermediate output powers linear interpolation was used to determine the most fuel efficient speed for each heat engine output power. The result is shown in Figure G-2.

At each time increment in the simulation the CVT output power is calculated (Appendix E). To continue the drive train power calculation and




Figure G-1 Brake Specific Fuel Consumption (BSFC) Map  
for a 75 Kilowatt Engine




Figure G-2 Most Fuel-Efficient Engine Speed vs. Engine Output Power

determine the CVT input power, the CVT ratio must be known in order to determine the CVT efficiency. However, selecting the ratio to run the engine at its most fuel efficient speed requires knowledge of the engine output power. Since this is not known, the calculation procedure estimates it with the value which existed at the previous simulation time increment. Since the drive train power and power split are not changing rapidly from one time increment to the next, the heat engine output power should not change much either. Consequently, the calculation procedure is as follows: after the CVT output power is calculated, the previous heat engine output power and Figure G-2 are used to determine the best engine speed; this speed and the CVT output speed determine a CVT ratio (which is checked and limited to upper and lower bounds as appropriate). Knowing the CVT ratio, the CVT input power can be calculated and split between the heat engine and traction motor, and the calculation proceeds as described in Appendix E.

Modifications to the above approach occur under several conditions. First, if in the previous iteration the heat engine power was zero, the ratio is selected to run the traction motor at its most efficient speed. The map used for this purpose is shown in Figure G-3. This handles the case where the power split calls for all of the CVT input power to be met by the traction motor. Second, each time the ratio is selected to run the engine most efficiently, a check must be made to make sure this ratio doesn't call for a traction motor speed which, at the present traction motor output power level, would cause the motor to stall. The stall out curve is shown in Figure G-4: for a given percent rated output power the curve yields the minimum motor speed to avoid stalling the motor. If the selected ratio would result in motor stall, the ratio is decremented by small steps until the stall-out con-




Figure G-3. CVT Ratio for Most Efficient Electric Motor Speed






Figure G-4. Traction Motor Stall-Out Curve

dition no longer exists. Finally, if the ratio selected to run the engine most efficiently calls for a motor speed which is excessive, then the ratio is changed to run the motor at its maximum speed.

A copy of the ratio selection program is given in Appendix I.

## APPENDIX H - AIRESEARCH POWER SPLIT STRATEGY

Since the AiResearch power split strategy [1] was used in parts of this study it is worthwhile including it here for reference. A listing of the program is given in Appendix I. The decision of how much of the CVT input power to assign to the heat engine and how much to the traction motor depends on the battery state of charge and whether or not the vehicle is accelerating. If the acceleration is zero, the state of charge above 20%, and the vehicle is not in a hill climb (CVT input power is  $< 20$  kw), the power split is 100% electric. If the vehicle is in a hill climb, the split is 30% electric, 70% heat engine. If the acceleration is zero but the battery state of charge is below 20% (independent of hill climb), the split is 100% heat engine.

If the vehicle is accelerating (independent of whether the battery is above or below 20% state of charge), the split is 30% electric and 70% heat engine. However, this split is modified if the CVT input power exceeds 80% of the maximum rating of the heat engine: in this latter case the heat engine power is set to the CVT input power or its maximum rating, whichever is smaller, and the remaining required power is delivered by the traction motor.

APPENDIX I - COMPUTER PROGRAMS

```

FTN4,L
C ADDING THE D OPTION WILL PRINTOUT DATA (LCCOST,POVRLD,SOCL) TO
C FILE A8 FOR RUN21=3 (VALUES OVER A SPECIFIED RANGE OF HEKW AND
C WGBATT). THE TWO WRITE STATEMENTS FOLLOWING STATEMENT #109 MUST
C ALSO BE COMMENTED ( C ).
      PROGRAM HVPOP(3,100)
C HYBRID VEHICLE PERFORMANCE OPTIMIZATION PROGRAM
C*****
C
C THIS MAIN PROGRAM READS IN INITIAL VALUES, SETS UP THE DRIVING CYCLE
C ARRAYS (VELOCITY AND GRADE ANGLE), SCALES THE GRG2 VARIABLES, AND
C CALLS THE OPTIMIZATION PROGRAM.
C
C*****
      LOGICAL SOVRLD,SMOTC,SMOOTH
      REAL KMPYR
      INTEGER RUN21
      COMMON RUN21
      COMMON/ALPHA/ALPHA1,ALPHA2,ALPHA3
      COMMON/CC/CDA,RDIFF,RGEAR,RGRM,RTIRE
      COMMON/MAP/DISCHG(101,6),EFFMTR(81,7),HEMAP(6,6),
&GREFF(101,11),VCHG(13,12),ATORQ(6),AESPED(6),ARATIO(10)
      COMMON/OMISC/CHOOSE,SMOOTH
      COMMON/SCALE/SFX(17),SFG(20),NN
      COMMON/STC/V(831),BET(831),TRIPLN(8),TRIPNO(8)
      COMMON/TIMEC/DLTSTC,DELTHW,TACCEL,TCOAST,TBRAKE,TSTOP,TCYCLE
      COMMON/VARY/ WTL,INOCHG
      COMMON/YEARC/PETYR(15),ELECTYR(15),ELEC(15),DISCH(15)
      COMMON GF
      DIMENSION G(20),XX(17),AVELA(15)
      DIMENSION IBUF(98)
      DIMENSION HE(3),LINEO(161),LINES(161)
      DATA HEKW/65./, WGBATT/386./, XX(3)/.7/, XX(4)/0./, XX(5)/0./
      DATA AVELA/0.,3.2777,5.8611,7.9166,9.9722,11.333,12.583,13.722,
&14.805,15.777,16.75,17.639,18.5,19.333,20.111/
      CALL LGBUF(IBUF,98)
C
C READING INITIAL VALUES OF OPTIMIZATION PARAMETERS
      1 READ(5,*) NN,(XX(I),I=3,NN),HEKW,WGBATT,DHEKW,DWGBAT,NHEKW,NWGBAT
      2 READ(5,*) DLTSTC,DELTHW,WTL,CHOOSE,INOCHG,RUN21,GF
      3 READ(5,7) SMOOTH
      7 FORMAT(L1)
      WRITE(6,2000) XX(3),XX(4),XX(5)
2000 FORMAT(
&' CONSTANT TERM IN POWER SPLIT FUNCTION=',F8.3,/
&'     TERM USED TO WEIGHT ACCELERATION=',F8.3,/
&'     TERM USED TO WEIGHT STATE OF CHARGE=',F8.4)
      WRITE(6,2005)HEKW,WGBATT
2005 FORMAT(/,
&'     HEKW=',F8.4,/

```

```

& WGBATT=',F8.4,/)
  IF(SMOOTH) WRITE(6,2006)
2006 FORMAT('          SMOOTH=TRUE')
  IF(.NOT.SMOOTH) WRITE(6,2007)
2007 FORMAT('          SMOOTH=FALSE')
  WRITE(6,2008) GF
2008 FORMAT('///      GAS FACTOR (GF)=',F7.3,/)
  WRITE(6,2010) DLTSTC,DELTHW,CHOOSE
2010 FORMAT(
&
&          STC TIME INCREMENT (DLTSTC)=',F8.2,/
&          HIGHWAY TIME INCREMENT (DELTHW)=',F8.1,/
&(CHOOSE=0 FOR ELECST COMPUTATIONS BASED ON ',
&'ELEC(I) & ENRGY) CHOOSE=',F2.0)
  XX(1)=HEKW
  XX(2)=WGBATT
C SCALING OF OPTINIZATION PARAMETERS
  DO 10 I=1,NN
10  XX(I)=XX(I)/SFX(I)
C SET UP SAE DRIVING CYCLE.
  IMAX=IFIX(TACCEL/DLTSTC)+1
  IDEL=1
  IF(DLTSTC.GT.1.) IDEL=DLTSTC
  DO 20 I=1,IMAX
C FIND DRIVING CYCLE VEL. AND STORE IN V(I)
  T=FLOAT(I-1)*DLTSTC
  TMIN=INT(T)
  TMAX=TMIN+FLOAT(IDEL)
  IBOT=INT(TMAX)+1-IDEL
  ITOP=IBOT+IDEL
  IF(ITOP.LE.15) GOTO 20
  IRUP=15
  IBOT=15-IDEL
  TMAX=14.
  TMIN=TMAX-FLOAT(IDEL)
20  V(I)=((T-TMIN)*AVELA(ITOP)+(TMAX-T)*AVELA(IBOT))/(TMAX-TMIN)
  K=I-1
  IMAX=K+IFIX((TCOAST-TACCEL)/DLTSTC)+1
  DO 30 I=K,IMAX
30  V(I)=20.
C DO 40 I=1,IMAX
C T=DLTSTC*FLOAT(I-1)
C40 WRITE(1,2030) I,V(I)
2030 FORMAT('T=',F5.2,3X,'V(I)=',F9.5)
  IMAX=IFIX(TSROP/DLTSTC)+1
  DO 50 I=1,IMAX
50  BET(I)=0.
C CALL GRG(Z,NCORE)
  IRUN21=RUN21+1
  GO10 (101,151,202,303,404,505),IRUN21
101 CALL GCOMP(G,XX)

```

```

        WRITE(8,2040)
2040 FORMAT(' HEKW   WGBATT   LCCOST   POVRLD   SOCL ')
        WRITE(8,2050) XX(1),XX(2),G(1),G(5),G(13)
2050 FORMAT(F9.4,1X,F9.3,1(1X,F9.2),1X,G11.4,1X,F9.7,1X,F9.1)
        IF(SMOOTH) WRITE(8,106)
        IF (.NOT.SMOOTH) WRITE(8,107)
106  FORMAT('  SMOOTH=TRUE')
107  FORMAT('  SMOOTH=FALSE')
        WRITE(8,883) G(2)
883  FORMAT(/,' TO1PET=',F9.3)
        STOP 101
C-----
C---
151  CALL GCOMP(G,XX)
        STOP 151
C---
C=====
C UDH = 1  WHEN OVERLOAD REGION LIES BELOW CURRENT HEKW OVERLOAD THRESHOLD
C         CURVE (SEARCH FOR FIRST ADMISSIBLE RUN, THEN GET CURVE
C   =-1  WHEN OVERLOAD REGION LIES ABOVE CURRENT HEKW OVERLOAD THRESHOLD
C         CURVE (SEARCH FOR FIRST OVERLOAD, THEN GET CURVE)
C UDW = 1  WHEN WGBATT INCREASES IN THE SEARCH
C   =-1  WHEN WGBATT DECREASES IN THE SEARCH
C SOVRLD = TRUE TO SEARCH FOR AN OVERLOAD AFTER WGBATT HAS BEEN CHANGED
C SNOTC  = TRUE TO SEARCH FOR A NEW OVERLOAD THRESHOLD CURVE
202  TWGBAT=WGBATT+DWGBAT*FLOAT(NWGBAT-1)
        BWGBAT=WGBATF
        WRITE(8,2060)
2060 FORMAT(' HEKW   WGBATT   LCCOST   POVRLD   SOCL ')
        UOW=1
        UDH=-1
        SNOTC=.FALSE.
        SOVRLD=.FALSE.
        DO 190 K=1,5
            I=1
60    CONTINUE
        WRITE(1,2060)
        WRITE(9,2060)
C
C SEARCH FOR NEXT OVERLOAD AT WGBATT=300
        IF(K.EQ.1) GOTO 90
        J=K-2
        IF(J/2*2.EQ.J) UDH=-UDH
        IF(K.GE.3) UDW=-UDW
        WGBATT=300.
        XR=HE(3)
        SNOTC=.TRUE.
        SOVRLD=.FALSE.
        IF(K/2*2.EQ.K) GOTO 70
        SNOTC=.FALSE.

```

```

        GOTO 90
C
C SEARCH FOR FIRST NEW OVERLOAD CURVE WITH CONSTANT STEP SIZE
70  XR=XR-DELX*UDH
    GOTO 150
80  IF(G(5).LE.0.) GOTO 70
    SNOTC=.FALSE.
C
C INCREMENT BATTERY WEIGHT & TEST IF ITS OUT OF RANGE
90  XX(2)=WGBATT+OWGBAT*FLUAT(I-1)*UDW
    IF(XX(2).LE.TWGBAT) GOTO 100
    I=NWGBAT
    GOTO 180
100 IF(XX(2).GE.BWGBAT) GOTO 110
    I=NWGBAT
    GOTO 180
110 IF(SNOTC.OR.K.NE.1) GOTO 150
    IF(I.NE.1) GOTO 130
    SOVRD=.FALSE.
    DELX=2.
    UDH=1
    XR=15.
    GOTO 140
C
C SEARCH FOR OVERLOADS & DOUBLE STEP SIZE WITH FAILURE
120 IF(G(5).LE.0.) GOTO 130
    SOVRD=.FALSE.
    GOTO 160
C
C DOUBLE STEP SIZE
130 DELX=DELX*2.
    XR=XR-DELX*UDH
    SOVRD=.TRUE.
    GOTO 150
140 CONTINUE
150 XX(1)=XR
    CALL GCOMP(G,XX)
    WRITE(1,2070) XX(1),XX(2),G(1),G(5)
    WRITE(9,2070) XX(1),XX(2),G(1),G(5)
2070 FORMAT(F9.3,1X,F9.3,1(X,F9.2),1X,G11.4,1X,F9.7,1X,F9.1)
    IF(SOVRD) GOTO 120
    IF(SNOTC) GOTO 80
    IF(G(5).LE.0..AND.DELX.LE.DHEKW) GOTO 170
    IF(G(5).GT.0.) GOTO 160
    DELX=AINT(DELX*.5.)/10.
    IF(DELX.LE.0.) DELX=DHEKW/2.
    XR=XL+DELX*UDH
    GOTO 140
160 XL=XR
    XR=XR+DELX*UDH

```

```

        GO TO 150
170 CONTINUE
    WRITE(8,2070) XX(1),XX(2),G(1),G(5),G(13)
    IF(XX(2).EQ.100.) HE(1)=XX(1)
    IF(XX(2).EQ.200.) HE(2)=XX(1)
    IF(XX(2).EQ.300.) HE(3)=XX(1)
180 I=I+1
    IF(I.LE.NWGBAT) GO TO 60
190 CONTINUE
    STOP 202

C=====
C+++++++
303 CONTINUE
D WRITE(8,2090)
D2090 FORMAT(' HEKW WGBATT LCCOST POVRLD SOCL ')
    DO 108 I=1,NHEKW
    XX(1)=HEKW-DHEKW*FLOAT(I-1)
    DO 109 J=1,NWGBAT
    XX(2)=WGBATT+DWGBAT*FLOAT(J-1)
    CALL GCOMP(G,XX)
D WRITE(8,3000) XX(1),XX(2),G(1),G(5),G(13)
D3000 FORMAT(F9.3,1X,F9.3,1(1X,F9.2),1X,G11.4,1X,F9.7,1X,F9.1)
    WRITE(8,3003) XX(1),XX(2),G(2),G(1)
3003 FORMAT(F9.3,3(5X,F9.3))
C LINEO(J)=1H.
C IF(G(5).GT.0.) LINEO(J)=1H@
C IF(G(2).GT.1072.) LINEO(J)=1H@
C LINES(J)=1H^
C IF(G(13).LT.2) LINES(J)=1H+
109 CONTINUE
C WRITES POVRLD GRID. COMMENT IF USING D OPTION (DATA PRINTOUT).
C WRITE(8,3005) (LINEO(J),J=1,NWGBAT)
C WRITES SOCL GRID. COMMENT IF USING D OPTION (DATA PRINTOUT).
C WRITE(9,3005) (LINES(J),J=1,NWGBAT)
C WRITE(9,3005) (LINEO(J),J=1,NWGBAT)
3005 FORMAT(17X,161A1)
108 CONTINUE
C WRITE(6,320)
320 FORMAT(' FILE A8 CONTAINS THE POVRLD GRID:',/
&,' FOR NO OVERLOAD (POVRLD.LE.0)',/
&,' @ WHEN AN OVERLOAD OCCURS (POVRLD.GT.0)',/
&,' FILE B7 CONTAINS THE SOCL GRID:',/
&,' ^ WHEN ELECTRIC POWER IS AVAILABLE DURING ACCELERATION',/
&,' + WHEN ELEC. POWER IS NOT AVAILABLE DURING ACCELERATION')
    STOP 303

C+++++++
C*****
404 DO 409 I=1,21
    XX(3)=.05*FLOAT(I-1)
409 CALL GCOMP(G,XX)

```



```

      STOP 404
C*****
C#####
  505 CONTINUE
      DO 510 I=1,481
      XX(2)=WGBATT+1.0*FLUAT(I-1)
      IF(XX(2).LE.273.) XX(1)=37.0-0.02564*XX(2)
      IF(XX(2).GT.273.) XX(1)=77.2334-0.2267756*XX(2)
      &+1.9819E-04*XX(2)*XX(2)
      CALL GCOMP(G,XX)
      WRITE(8,520) XX(1),XX(2),G(1),G(7),G(8),G(9)
  520  FORMAT(F9.4,5(3X,F9.4))
  510 CONTINUE
      STOP 505
C#####
      END
      END

```

```

      CTR4,L
      SUBROUTINE GCOMP(G,XX)
      C*****
      C
      C THIS EVALUATES THE CONSTRAINT AND OBJECTIVE FUNCTIONS FOR GRG2 GIVEN THE
      C THE GRG2 PARAMETERS, WHICH ARE POWER RATING OF THE HEAT ENGINE, BATTERY
      C WEIGHT, AND THE POWER SPLIT PARAMETERS.
      C
      C*****
      REAL MT,MNFCST,KMPRYR,MTKWPK,LCCOST,MAINTC,LINCOM
      DIMENSION G(20),XX(17)
      INTEGER RUN21
      COMMON RUN21
      COMMON GF
      COMMON/ALPHA/ALPHA1,ALPHA2,ALPHA3
      COMMON/MOTOR/MTKWPK
      COMMON/RSPLT/ACCEL,SOC,PCVT,CX(15),VAVE,PHEMAX,PHE,PELEC
      COMMON/SCALE/SFX(17),SFG(20),NN
      COMMON/YEARC/PETYR(15),ELECTYR(15),ELEC(15),DISCH(15)
      COMMON BTCOST,BATRYR,BATLFE
      DIMENSION ELECST(10),PETCST(10)
      DATA KMPRYR/16000./,WP/20./
      C
      C THIS PROGRAM TAKES VALUES FOR THE IC ENGINE SIZE, BATTERY WEIGHT
      C AND POWER SPLIT FUNCTION PARAMETERS, AND COMPUTES THE VALUES OF
      C THE OBJECTIVE AND CONSTRAINT FUNCTIONS
      C
      HEKW=XX(1)*SFX(1)
      WGBATT=XX(2)*SFX(2)
      IMAX=NN-2
      DO 115 I=1,IMAX
115  CX(I)=XX(I+2)*SFX(I+2)
      C CX IS VECTOR OF UNSCALED POWER FLOW PARAMETERS
      CALL WGTG(HEKW,WGBATT,WT,MT,WGCHI,WP)
      CALL MFCST(WGBATT,WGCHI,MNFCST)
      CALL ACQST(MNFCST,WGBATT,BATCST,ACQST)
      CALL MAINTC(HEKW,MTKWPK,BATCST,KMPRYR,WP,WGCHI,BTLIST,MAINTC)
      CALL REPAIR(HEKW,MTKWPK,WP,WGCHI,KMPRYR,REPAIR)
      C TRAVL USES POWER FLOW PARAMETERS
      CALL TRAVL(HEKW,WGBATT,MT,PETYR,ELECTYR,ELEC,DISCH,POVRD,PETV10,
      &SOC,L,BGPCVT)
      IF(RUN21.LE.1) WRITE(6,425) MT,WGBATT,WP,MNFCST,ACQST,MAINTC,
      &REPAIR,HEKW,POVRD
425  FORMAT(/'***** SUMMARY DATA *****',/
      &'          TOTAL MASS (MT) =',F9.3,/
      &'          BATTERY MASS (WGBATT) =',F9.3,/
      &'          POWER TRAIN WEIGHT (WP) =',F9.3,/
      &'          MANUFACTURING COST (MNFCST) =',F9.3,/
      &'          ACQUISITION COST (ACQST) =',F9.3,/
      &'          YEARLY MAINTENANCE COST (MAINTC) =',F9.3,/

```

```

&'          YEARLY REPAIR COST (REPAIR) =',F9.3,/
&'          HE POWER RATING (HEKW) =',F8.3,/
&'SUM OF POWER OVERLOAD SQUARED (POVRLD) =',F8.3)
CALL LIFE(PETYR,ELECYR,ELEC,DISCH,BTLIST,ACQCST,MAINTC,REPAIR,
&BATCST, LCCOST,PETCST,ELECST,TOTPET)

```

```

C
C MY CONVENTION IS TO SEPARATE GIVEN AND RETURNED VALUES BY A BLANK
C AND TO COMMUNICATE CALC VALUES BY ARGUMENT LIST AND MAPS BY COMMON
C STATEMENTS

```

```

C
LINCOM=ALPHA1*LCCOST+ALPHA2*TOTPET+ALPHA3*ACQCST
G(1)=LCCOST*SFG(1)
G(2)=TOTPET*SFG(2)
G(3)=ACQCST*SFG(3)
G(4)=LINCOM*SFG(4)
G(5)=POVRLD*SFG(5)
G(7)=BTCOST
G(8)=BATRYR
G(9)=BATLFE
G(13)=SOCL
G(14)=BGPCVT
RETURN
RETURN

```

```

SUBROUTINE TRAVL(HEKW,WGBATT,MT, PETYR,ELECYR,ELEC,DISCH,POVRLD,
&PETV10,SOC1,BGPCVT)
C*****
C
C THIS SIMULATES BOTH STC AND HIGHWAY DRIVING FOR THE VEHICLE.
C IT CALCULATES THE YEARLY FUEL CONSUMPTION, ELECTRICITY USAGE, AND
C THE NUMBER OF DEEP DISCHARGES OF THE BATTERY.
C
C*****
LOGICAL SMOOTH
INTEGER RUN21
REAL INTEQ,INTN0
REAL MT,IAVE,IBATT,IVESTC,KMPYR,IBMAX,IEFFMX,IBTOLD
REAL KWCST,LENGTH,MT,MTGRKW,MTKWPX,MC,NC,IEFF,MCSTND
DIMENSION PETYR(15),ELECYR(15),ELEC(15),DISCH(15)
DIMENSION EAKWHR(15),AEKHA(15),AEKHP(15)
DIMENSION AHEKW(4),FFHEKW(4),SATURQ(6)
COMMON RUN21
COMMON/CC/CDA,RDIFF,RGEAR,RGRN,RTIRE
COMMON/CHARG/AACV(8),ACR(8)
COMMON/EFCVT/APCVT(8),ARCVT(7),EFF(8,7)
COMMON/LIMIT/ NTRIPX, ITERMX
COMMON/MAP/DISCHG(101,6),EFFMTR(81,7),HEMAP(6,6),
&SREFF(101,11),VCHG(13,12),ATORQ(6),AESPED(6),ARATIO(10)
COMMON/DMISC/CHOOSE,SMOOTH
COMMON/PHY/GRAV,RHO
COMMON/PRINT/APETT(15),AELETA(15),AELETP(15)
COMMON/KRATU/NTIME,WGEAR,RCVT,PMOTOR,PMTRTD,PGEAR
COMMON/RSPLT/ACCEL,SOC,PCVT,CX(15),VAVE,PHEMAX,PHE,PELEC
COMMON/STC/V(831),BET(831),TRIPLN(8),TRIPNO(8)
COMMON/TIMEC/DLTSTC,DELTHW,TACCEL,TCOAST,TBRAKE,TSTOP,TCYCLE
COMMON/TRIP/CHARGE(36),EBTOTL(36),HOUT(36),IDDD(36),
&IVESTC(36),PETSTC(36),SOCSTC(36),REGEN(36)
COMMON/VARY/ WTL,INUCHC
DATA AHEKW/37.,56.,75.,112./
DATA FFHEKW/1.09718,1.05,1.,0.954545/
DATA ALLSTC/50001./, HWYVEL/25.0/, STCDIS/1450.0/, CHGEFF/0.85/
DATA NC/84./,WMORTE/116.35/,WGORTE/116.35/,WMORTE/419./
DATA NSTCFR/28/, PCVTMX/90000./, NCYLMX/35/
DATA PDORATE/90000./, PINVMX/40000./
DATA PGRATE/90000./, PMGRTE/40000./, REGMIN/1000./
DATA PMTHAX/40000./, SOCMAX/.3/, VCELL/2.05/
DATA VDELT/1./, MCSTND/9.83/, PBMAX/33600./, IBMAX/200./
DATA EFFBC/.75/, IEFFMX/.700./
C CALCULATE THE MASS OF A BATTERY CELL
MC=WGBATT/NC
C INITIALIZE VARIABLES
IB000D=0
AHOUT=0.
AREGEN=0.

```

```

SOC=1.0
SUCL=1.0
IGPCVT=0.
POVRD=0.
)NOELE=0
IHWY=0
ISWTCH=0
NTIME=1
VBCHG=200.
VOLTOT=0.
AHCHG=0.
IOVRD=0
)FLLBK=0
EOTOT=0.
VBATT=NC*VCELL
C SET TIME, TIME STEP AND CYCLE COUNTER FOR DRIVING A SEQUENCE OF STC'S
TIME=0.
NCYCLE=1
DELT=DLTSTC
PHEMAX=1000.*HEKW
FRSCL=HEKW/75.*SVINT(FFHEKW,HEKW,AHEKW,4)
D) 5 I=1,6
5 SATORQ(I)=ATORQ(I)*(HEKW/75.)
C-----
C----- ACCELERATION AND CRUISE PHASE -----
C----- AND HIGHWAY DRIVING -----
C-----
C CALC. AVERAGE VELOCITY AND ACCELERATION OVER CURRENT TIME STEP
10 V1=V(NTIME+1)
V2=V(NTIME)
VAVE=(V1+V2)/2.
ACCEL=(V1-V2)/DELT
BETA=BET(NTIME)
C CALC DRAG FORCE OF VEHICLE
20 FD=CDA*RHU*VAVE*VAVE/2.
C CALC ROLLING RESISTANCE FORCE
CR=(10.+0.01*VAVE+0.00008*VAVE*VAVE)/1000.
FR=CR*MT*GRAV
C INITIALIZE POWER SWITCH FLAG
ISWTCH=0
C CALC. GRADE FORCE
FGR=MT*GRAV*SIN(BETA)
C CALCULATE VEHICLE ACCELERATION FORCE
FA=1.1*MT*ACCEL
C CALC. POWER REQ'D AT AXLE
PAXLE=(FD+FR+FGR+FA)*VAVE
C CALC. AXLE SPEED AND TORQUE
WAXLE=VAVE/RTIRE
TAXLE=PAXLE/WAXLE
C CALC. DIFFERENTIAL INPUT SPEED, TORQUE, POWER

```

```

WDRIVE=WAXLE/ROIFF
PDPCT=(PAXLE/PDRATE)*100.
WDPCT=(WAXLE/WDORTE)*100.
PDRIVE=PAXLE/INTEQ(GREFF,PDPCT,WDPCT,100.,100.,
&1.,-1.,10.,-10.,101,11)
TDRIVE=PDRIVE/WDRIVE
C CALC. TORQUE, SPEED, POWER AT INPUT TO GEAR BETWEEN CVT AND DIFFERENTIAL
WGEAR=WDRIVE/RGEAR
PGPCT=(PDRIVE/PGRATE)*100.
WGPCT=(WDRIVE/WGORTE)*100.
PGEAR=PDRIVE/INTEQ(GREFF,PGPCT,WGPCT,100.,100.,
&1.,-1.,10.,-10.,101,11)
TGEAR=PGEAR/WGEAR
C DETERMINE CVT RATIO (RCVT)
CALL RATIO
C CALC. TORQUE, SPEED, POWER AT CVT INPUT
PCVT=(PGEAR)/(INTQ(EFF,(PGEAR/1000.),RCVT,100.,3.4,
&APCVT,ARCVT,8,7))
IF(PCVT.GT.8GPCVT) BGPCVT=PCVT
WCVT=WGEAR/RCVT
TCVT=PCVT/WCVT
C DETERMINE POWER SPLIT (RESULT IS PHE AND PELEC)
CALL SPLIT
C IS USE OF BATTERIES PROHIBITED
IF(INOELE.NE.1) GOTO 33
PELEC=0.
PHE=PCVT
C IS ELECTRIC POWER NEGLIGIBLE
33 IF(PELEC.LT.50.) GOTO 31
C IS BATTERY 80% DISCHARGED
IF(SOC.GE.0.2) GO TO 32
31 PHE=PHE+PELEC
IF(PELEC.GT.0.) IFLLBK=IFLLBK+1
PELEC=0.
PMOTOR=0.
PINV=0.
PBOUT=0.
IBATT=0.
IELEC=0
GO TO 80
32 IF(SOC.GE.SOCNAX) GOTO 30
IF(IHECHG.NE.1) GOTO 30
GOTO 31
C CALC. INPUT QUANTITIES TO GEAR BETWEEN MOTOR AND CVT
30 IELEC=1
WMOTOR=WCVT/RGRN
PMGPCT=(PELEC/PMGRTE)*100.
WNGPCT=(WCVT/WMORTE)*100.
PMOTOR=PELEC/INTEQ(GREFF,PMGPCT,WNGPCT,100.,100.,
&1.,-1.,10.,-10.,101,11)

```

```

      (FG1=PELEC/PMOTOR
      TMOTOR=PMOTOR/WMOTOR
C   DOES MOTOR OUTPUT POWER EXCEED PEAK
      IF(PMOTOR.LE.PMGMAX) GOTO 50
C   SET MOTOR POWER AT MAX
      PMOTOR=PMGMAX
C   CALC. NEW MOTOR TORQUE
      TMOTOR=PMOTOR/WMOTOR
C   CALC. NEW ELECTRIC POWER AT CVT INPUT
40  PMGPCT=(PMOTOR/PMGRTE)*100.
      PELEC=PMOTOR*INTEQ(GREFF,PMGPCT,WMGPCT,100.,100.,
      &1.,-1.,10.,-10.,101,11)
      EFG2=PELEC/PMOTOR
      )FLLBK=IFLLBK+1
C   SET ENGINE POWER TO MEET TOTAL REQ'D POWER
      PHE=PCVT-PELEC
C   CALC MOTOR INPUT (INVERTER OUTPUT) POWER
50  PMTPCT=(PMOTOR/PMTRTD)*100.
      PINV=PMOTOR/INTEQ(EFFMTR,PMTPCT,WMOTOR,200.,1466.,
      &2.5,-2.5,146.61,439.82,81,7)
      EFM1=PMOTOR/PINV
C   DOES INVERTER OUTPUT POWER EXCEED MAX
      IF(PINV.LE.PINVMAX) GOTO 55
C   SET INVERTER POWER AT MAX AND COMPUTE NEW MOTOR OUTPUT POWER
      PINV=PINVMX
      PMTPCT=(PINV/PMTRTD)*100.
      PMOTOR=PINV*INTEQ(EFFMTR,PMTPCT,WMOTOR,200.,1466.,
      &2.5,-2.5,146.61,439.82,81,7)
      EFM1=PMOTOR/PINV
C   COMPUTE NEW ELECTRIC POWER AT CVT INPUT
      PMGPCT=(PMOTOR/PMGRTE)*100.
      PELEC=PMOTOR*INTEQ(GREFF,PMGPCT,WMGPCT,100.,100.,
      &1.,-1.,10.,-10.,101,11)
C   COMPUTE NEW HEAT ENGINE POWER
      PHE=PCVT-PELEC
      )FLLBK=IFLLBK+1
C   CALC INVERTER LOSSES AND INPUT POWER USING OLD VALUE OF BATTERY VOLTAGE,
C   AND RESET ITERATION COUNTER
55  PLOSS=3.0*(PINV/VBATT)+0.035*PINV
      PBOUT=PINV+PLOSS
      IITER=0

C-----
C----- DISCHARGING BATTERY VOLTAGE LOOP -----
C-----
C   CALCULATE BATTERY CURRENT USING BATTERY VOLTAGE FROM LAST ITERATION
41  IBATT=PBOUT/VBATT
C   SAVE OLD VALUE OF BATTERY VOLTAGE
      VBTOLD=VBATT
      PVBATT=VBATT
      )BTOLD=IBATT

```

```

C  CALC BATTERY AMP-HRS OUT
  AHOUT=AHOUT+(IBATT*DELTA/3600.)
C  IS THIS HIGHWAY DRIVING
  IF(IHWY.NE.1.) GOTO 57
C  CALC AVERAGE BATT CURRENT FOR STC AND HIGHWAY DRIVING
  IAVE=(3600.*AHOUT)/(TIME+DELTA)
  GOTO 58
C  CALC AVERAGE BATT CURRENT SINCE START OF STC DRIVING
57  IAVE=(3600.*AHOUT)/((TIME+DELTA)+FLOAT(NCYCLE-1)*STOP)
C  FIND CELL CAPACITY PER KILOGRAM
58  CAPKG=PUKRT(IAVE/MC)
C  CALC AMP-HRS PER CELL
  CAPCTY=CAPKG*MC
C  CALC ACTUAL CAPACITY WITHDRAWN AND STATE OF CHARGE
  AACLT=AHOUT-AREGEN-AHCHG
  SOC=1.-(AACLT/CAPCTY)
  IF(SOC.LE.SOCL.AND.ACCEL.NE.0.) SOCL=SOC
C  CHANGE CELL CURRENT TO ACCOUNT FOR CHANGE IN CELL RESISTANCE
  IEFF=IBATT*(MCSTND/MC)
C  CALC BATTERY VOLTAGE FROM DISCHARGE CURVE
  VBATT=MC*INTEQ(DISCHG,SOC,IEFF,1.,IEFFMX,.01,-.01,100.,-100.,
&101,6)
C  DOES CALCULATED BATTERY VOLTAGE EQUAL BATT VOLTAGE ASSUMED AT START OF CALC
  IF(ABS(VBATT-VBTOLD).GT.VDELTA) GOTO 59
  GOTO 71
C  HAVE WE ITERATED THE MAX NO. OF TIMES
59  IF(IITER.GE.ITERMX) GOTO 60
C  RESET AMP-HRS OUT OF BATT. AND INCREMENT ITERATION COUNTER
  AHOUT=AHOUT-(IBATT*DELTA/3600.)
  IITER=IITER+1
  GOTO 41
C  SET BATTERY VOLTAGES AND CURRENTS TO OLD VALUES
60  VBATT=VBTOLD
  IBATT=IBTOLD
  IEFF=IBATT*(MCSTND/MC)
C  WAS THE EFFECTIVE BATTERY CURRENT ABOVE ITS MAX
71  IF(IEFF.LE.IEFFMX) GOTO 70
C  COMPUTE BATTERY CURRENT CORRESPONDING TO MAX EFFECTIVE CURRENT
  IBATT=IEFFMX*(MC/MCSTND)
C  COMPUTE NEW BATTERY OUTPUT POWER
  PBOUT=IBATT*VBATT
C  ESTIMATE NEW INVERTER OUTPUT POWER
  PINV=PBOUT-3.0*IBATT-0.035*(PBOUT-PILOSS)
C  ESTIMATE MOTOR OUTPUT POWER AND ELECTRIC POWER AT CVT INPUT
  PMTPCT=((PINV*0.9)/PMTRFD)*100.
  PMOTOR=PINV*INTEQ(EFFMTR,PMTPCT,WMOTOR,200.,1466.,
&2.5,-2.5,146.61,439.82,81,7)
  PMGPCT=(PMOTOR/PMGRTE)*100.
  PELEC=PMOTOR*INTEQ(GREFF,PMGPCT,WMGPCT,100.,100.,
&1.,-1.,10.,-10.,101,11)

```



```

      IFLLBK=IFLLBK+1
C  CALC NEW HE POWER
      PHE=PCVT-PELEC
C  IF BATT IS DISCHARGED SET 80% DOD FLAG
70   IF(SOC.LT.0.2) I80DOD=1
C  CALC. BATT. ENERGY USAGE FOR THIS INCREMENT
      BENRGY=(PBOUT*DELT)/1.E+06
C  CALC BATT INTERNAL VOLTAGE AND ENERGY WEIGHTING FACTOR
      VINT=NC*INTEQ(DISCNG,SOC,0.,1.,IEFFMX,.01,-.01,100.,-100.,101,6)
      DISEFF=VINT/VBATT
C  CALC. TOTAL BATT ENERGY USAGE SINCE START OF TRIP
      EBTOT=EBTOT+BENRGY*DISEFF
C-----
C----- HE CHARGING COMPUTATIONS -----
C-----
C  IS HE CHARGING INHIBITED
80   IF(INOCHG.EQ.1) GOTO 101
C  IS BATT DISCHARGED
      IF(SOC.LT.0.2) GO TO 90
C  IS BATT PRESENTLY BEING CHARGED
      IF(IHECHG.NE.1) GOTO 101
C  IS BATT BELOW MAX CHARGING LEVEL
      IF(SOC.LT.SOCMAX) GOTO 90
C STOP CHARGING
      IHECHG=0
      GOTO 101
C  IS THIS HIGHWAY DRIVING
90   IF(IHWY-1) 102,103,103
C  INHIBIT ALL FURTHER USE OF BATTERIES
103  INOCHG=1
      GOTO 105
C  IS THIS THE CRUISE PHASE OF THE STC
102  IF(TIME.LT.TCOAST.AND.TIME.GE.TACCEL) GOTO 105
101  PCHG=0.
      GOTO 140
C  SET BATT CHARGING FLAG
105  IHECHG=1
C  IS POWER SPLIT BEING CHANGED
      IF(PELEC .GT. 0.) IFLLBK=IFLLBK+1
C  SET HE POWER TO TOTAL
      PHE=PHE+PELEC
      PBOUT=0.
      PLEEC=0.
      PMOTOR=0.
      PINV=0.
C  HAS ELECTRIC POWER BEEN CHARGED TO BATT THIS ITERATION
      IF(IELEC.NE.1) GOTO 106
C  RESET BATTERY QUANTITIES
      AHUUF=AHUUF-(IBATT*DELT/3600.)
      IHTOT=EBTOT-BENRGY*DISEFF

```

```

      IBATT=0.
C  CALC CHARGING POWER
106  PCHG=PHEMAX-PHE
      IF(PCHG .GE. 0.) GO TO 100
      PCHG=0.
      GOTO 140
C  CALC POWER SUPPLIED TO ELECTRIC MOTOR
100  WMPCT=(WCV1/WMORTE)*100.
      PMGPCT=(PCHG/PMGRTE)*100.
      PMOTOR=PCHG*INTEQ(GREFF,PMGPCT,WMPCT,100.,100.,
&1.,-1.,10.,-10.,101,11)
C  IS THE CHARGING POWER GREATER THAN THE MAX MOTOR POWER
      IF(PMOTOR.LE.PMTMAX) GOTO 110
C  SET POWER AT MAX AND CORRECT POWER CHARGED TO HE
      PMOTOR=PMTMAX
      PMGPCT=(PMOTOR/PMGRTE)*100.
      PCHG=PMTMAX/INTEQ(GREFF,PMGPCT,WMPCT,100.,100.,
&1.,-1.,10.,-10.,101,11)
C  CALC POWER FROM GENERATOR TO INVERTER
110  WMOTOR=WCVT/RGRM
      PMTPCT=(PMOTOR/PMTRTD)*100.
      PINV=PMOTOR*INTEQ(EFFMTR,PMTPCT,WMOTOR,200.,1466.,
&2.5,-2.5,146.61,439.82,81,7)
C  IS INVERTER POWER TOO GREAT
      IF(PINV.LE.PINVX) GOTO 120
C  SET POWER AT MAX AND CORRECT POWER CHARGED TO HE
      PINV=PINVX
      PMTPCT=(PINV/PMTRTD)*100.
      PCHG=PINV/(INTEQ(EFFMTR,PMTPCT,WMOTOR,200.,1466.,
&2.5,-2.5,146.61,439.82,81,7)
& *INTEQ(GREFF,PMGPCT,WMPCT,100.,100.,1.,-1.,10.,-10.,101,11))
C  INITIALIZE ITERATION FLAG
120  IICHG=0
      EFMI=PINV/PMOTOR
C-----
C----- HE CHARGING BATTERY LOOP -----
C-----
C  CALCULATE BATT INPUT POWER AND CURRENT
123  PBOUT=-PINV+3.0*(PINV/VBCHG)+0.035*PINV
      IBATT=PBOUT/VBCHG
      PVBATT=VBCHG
C  IS CHARGING POWER TOO GREAT
      IF(PBMAX*(MC/MCSTND)+PBOUT.GE.0.) GOTO 121
C  SET CHARGING POWER AT MAX AND CALC NEW BATT CURRENT
      PBOUT=-PBMAX*(MC/MCSTND)
      IBATT=PBOUT/VBCHG
C  IS CHARGING CURRENT TOO LARGE
121  IF(IBMAX+IBATT.GE.0.) GOTO 122
C  SET BATT CURRENT AT MAX AND RECALCULATE CHARGING POWER
      IBATT= -IBMAX

```

```

      PBOUT=IBATT*VBCHG
C   SAVE OLD VALUE OF BATTERY VOLTAGE
122  VBTOLD=VBCHG
C   CALC. CHARGING AMP-HRS AND ACTUAL AMP-HRS
      AHCHG=AHCHG-(IBATT*DELTA/3600.)
      AACTL=AHOUT-AHCHG-AREGEN
C   CALC AVER BATT CURRENT FOR STC AND HIGHWAY DRIVING
      IF(INHWY.NE.1) GOTO 125
      IAVE=3600.*AHOUT/(TIME+DELTA)
      GOTO 130
C   CALC AVER BATT CURRENT SINCE START OF STC DRIVING
125  IAVE=(3600.*AHOUT)/((TIME+DELTA)+FLOAT(NCYCLE-1)*(STOP))
C   CALCULATE STATE OF CHARGE AND BATTERY VOLTAGE DURING CHARGING
130  CAPKG=PUKRT(IAVE/MC)
      CAPCTY=CAPKG*MC
      SOC=1.0-(AACTL/CAPCTY)
      IEFF=-IBATT*(MCSTND/MC)
      VBCHG=NC*INTEQ(VCHG,(AACTL/MC),IEFF,15.,300.,1.,0.,25.,0.,13,12)
      KLEFF=NC*INTEQ(DISCHG,SOC,0.,1.,IEFFMX,.01,-.01,100.,-100.,
&101,6)
      &/VBCHG
C   DOES CALC VOLTAGE EQUAL VOLTAGE ASSUMED
      IF(ABS(VBCHG-VBTOLD).LE.VDELTA) GO TO 133
C   HAVE WE ITERATED MAXIMUM NUMBER OF TIMES
      IF(IICHG.GE.ITERMX) GO TO 134
C   INCREMENT ITERATION COUNTER AND RESET CHARGING AMP-HRS INTO BATT
      IICHG=IICHG+1
      AHCHG=AHCHG+(IBATT*DELTA/3600.)
      GO TO 123
C   SET BATTERY VOLTAGE TO OLD VALUE
134  VBCHG=VBTOLD
C   LIMIT SOC TO MAX
133  IF(SOC.GT.1.0) SOC=1.
C   STOP CHARGING IF BATTERY HAS REACHED MAX CHARGING LEVEL
131  IF(SOC.GE.SOCMAX) ICHG=0
C   CALC TOTAL BATT ENERGY USED SO FAR ON THIS TRIP OR FROM START OF STC'S
      EBOUT=EBOUT+((PBOUT*DELTA)/1.E+06)*REGEFF
C   INCREASE REQ'D HE POWER TO INCLUDE CHARGING POWER
      PHE=PHE+PCHG
C   IS HE POWER TOO LARGE
140  IF(PHE.LE.PHEMAX) GOTO 160
C   IS BATT DISCHARGED
      IF(SOC.GE.0.2) GOTO 141
      IOVRD=IOVRD+1
      PSHORT=PCVT-PHEMAX-PELEC
      IF(PSHORT) 136,136,137
136  WRITE(7,1072) PSHORT
1072 FORMAT(" AN ERROR HAS OCCURED IN COMPUTING THE",
&" SUM OF THE SQUARED POWER OVERLOAD (POVRD=",F9.2,")")
      GOTO 160

```

```

137 POVRLO=POVRLO+PSHORT*PSHORT
    GOTO 160
C HAVE WE ATTEMPTED TO SWITCH MORE POWER TO ELECTRIC MOTOR
141 IF (ISWCH.NE.1) GOTO 142
    IOVRLO=IOVRLO+1
    PSHORT=PCVT-PHEMAX-PELEC
    IF (PSHORT) 136,136,137
C SET SWITCH FLAG
142 ISWCH=1
C DID WE USE ELECTRIC POWER IN THIS INCREMENT
    IF (PELEC.LE.0.) GOTO 150
C RESET AMP HOURS OUT OF BATT
    AHOUT=AHOUT-(IBATT*DELT/3600.)
    EBTOT=EBTOT-ENRGY*DISEFF
C SWITCH EXCESS POWER TO ELECTRIC MOTOR
150 PHE=PHEMAX
    PELEC=PCVT-PHE
    IFLLBK=IFLLBK+1
    GOTO 30
C CALC THE TORQUE, SPEED, FUEL FLOW RATE
160 WHE=WCVT
    THE=PHE/WHE
    FUELRT=INTND(CHEMAP, THE, WHE, PHEMAX/200., 840.0, SATORQ, AESPED, 6, 6)
    & *FRSCLE
    BSFC1=FUELRT/PHE*4178722.1
C CALC THE FUEL VOLUME USED SINCE START OF TRIP
    VOLTOT=VOLTOT+(FUELRT*DELT)
C INCREMENT TIME
    TIME=TIME+DELT
    NTIME=NTIME+1
C*
C HIGHWAY PRINTOUT
    IF (IA.EQ.1A/57*57.AND.RUN21.EQ.1) WRITE(8,401)
    IA=IA+1
401 FORMAT('1', 'NCYCLE   TIME   VAVE   WDRIVE   WGEAR   WCVT   ',
& ' WHE   THE   WMOTOR   IAVE   IBODD   IFLLBK   IOVRLO ',
& ' ISWCH   IITER   IHECHG   IICHG   IIREGN')
    IF (RUN21.EQ.1) WRITE(8,500) NCYCLE, TIME, VAVE, WDRIVE, WGEAR, WCVT,
& WHE, THE, WMOTOR,
& IAVE, IBODD, IFLLBK, IOVRLO, ISWCH, IITER, IHECHG, IICHG, IIREGN
500 FORMAT(I4, 2X, F8.0, 1X, F8.2, 1X, F8.3, 1X, F8.2, 1X, F8.3, 1X, F8.3, 1X,
& F8.2, 1X, F8.2, 1X, F8.3, 1X, 8(18, 1X))
    IF (IB.EQ.1B/57*57.AND.RUN21.EQ.1) WRITE(9,402)
402 FORMAT('1', 'NCYCLE   TIME   PAXLE   PDRIVE   PGEAR   PCVT   ',
& ' PCVT   PHE   PCHG   PELEC   PMOTOR   PINV   ',
& ' PBOUT   IBATT   VBATT   SOC   PROAD   PREGN   ',
& ' BSFC', 4X, 'FUELRT', 5X, 'EFM1')
    IB=IB+1
    IF (RUN21.EQ.1) WRITE(9,501) NCYCLE, TIME, PAXLE, PDRIVE, PGEAR,
& PCVT, PCVT, PHE, PCHG,

```

```

&PELEC,PMOTOR,PINV,PROUT,IBATT,PVBATT,SOC,PROAD,PREGEN,
&BSFC1,FUELRT,EFM1
5010 FORMAT(I4,2X,F8.0,1X,F8.1,1X,F8.1,1X,F8.1,1X,F8.1,1X,F8.3,1X,
&F8.1,1X,F8.2,1X,F8.1,1X,F8.1,1X,F8.2,1X,F8.2,1X,F8.2,1X,
&F8.2,1X,F8.4,1X,F8.2,1X,F8.2,1X,F9.4,1X,F10.8,1X,F7.6)
C*
C IS THIS HIGHWAY DRIVING
  IF(IHWY.EQ.1) GOTO 170
C HAS THE 'COAST' PHASE OF THE STC BEEN REACHED
  IF((TIME-TCOAST) 10,180,180)
C HAS HIGHWAY DRIVING BEEN COMPLETED FOR THIS TRIP
  170 CONTINUE
C
  IF((TIME-TRIPM) 20,300,300)
C-----
C----- COAST PHASE -----
C-----
C SET HEAT ENGINE CHARGING POWER TO ZERO
180 PCHG=0.
  IITER=0
  )ICHG=0
  PVBATT=NC*INTEQ(DISCHG,SOC,0.,1.,IEFFMX,.01,-.01,100.,-100.,
&101,6)
C CALC CURRENT VELOCITY
  VELO=V(NTIME)
C CALC VEHICLE DRAG FORCE
190 FD=CDA*RHU*VELO*VELO/2.
C CALC ROLLING RESISTANCE FORCE
  FR=MT*GRAV*(10.+0.01*VELO+0.00008*VELO*VELO)/1000.
C CALC GRADE FORCE
  BETA=BET(NTIME)
  FGR=MT*GRAV*SIN(BETA)
C CALC VEHICLE VELOCITY AT END OF TIME INCREMENT
  VNEXT=VELO-(DELT*(FGR+FD+FR)/MT)
C CALC AVERAGE CURRENT AND VELOCITY
  IAVE=(3600.*AHOUT)/(TIME+FLOAT(NCYCLE-1)*TSTOP)
  VAVE=.5*(VELO+VNEXT)
C ZERO ALL DRIVE TRAIN POWERS, ETC
  PAXLE=0.
  PDRIVE=0.
  PGEAR=0.
  PCV1=0.
  PELEC=0.
  PHE=0.
  PMOTOR=0.
  PINV=0.
  PLOSS=0.
  IBATT=0.
  PROUT=0.
  THE=0.

```

```

C  CALC DRIVE SHAFT SPEEDS
    WHE=0.
    WDRIVE=VAVE/(RTIRE*RDIFF)
    WGEAR=WDRIVE/RGEAR
    WCVT=WGEAR/RCVT
    WMOTOR=WCVT/RGRM
C  INCREMENT TIME
    TIME=TIME+DELT
    NTIME=NTIME+1
    FUELRT=0.
C#
    IF(IA.EQ. IA/57*57.AND.RUN21.EQ.1) WRITE(8,401)
    IA=IA+1
    IF(RUN21.EQ.1) WRITE(8,5000) NCYCLE,TIME,VAVE,WDRIVE,WGEAR,
    &WCVT,WHE,THE,WMOTOR,
    &IAVE,IBODOD,IFLLBK,IOVRLD,ISWTCH,IITER,IHECHG,IICHG,IIREGN
    IF(IB.EQ. IB/57*57.AND.RUN21.EQ.1) WRITE(9,402)
    IB=IB+1
    IF(RUN21.EQ.1) WRITE(9,5010) NCYCLE,TIME,PAXLE,PDRIVE,PGEAR,
    &PCVT,RCVT,PHE,PCHG,
    &PELEC,PMOTOR,PINV,PBOUT,IBATT,PVBATT,SOC,PROAD,PREGEN,
    &BSFC1,FUELRT,EFM1
C#
C  SAVE VELOCITY
    V(NTIME)=VNEXT
C  HAS THE BRAKING PART OF THE STC BEEN REACHED
    IF(TIME.GE.TBRAKE) GOTO 195
C  INITIALIZE VELOCITY FOR NEXT TIME INCREMENT
    VELO=VNEXT
    GOTO 190
-----
C----- BRAKING PHASE -----
-----
C  CALC VEL DECREASE PER TIME INCREMENT DURING BRAKING
195  DELV=(VNEXT*DELT)/(TSTOP-TBRAKE)
C  CALC THE AVERAGE VELOCITY OVER THE NEXT TIME INCREMENT
200  V1=V(NTIME)
    V2=V1-DELV
    VAVE=(V1+V2)/2.
C  CALC POWER LOST DUE TO ROAD LOSSES FOR THIS INCREMENT
    FO=CDA*RHO*VAVE*VAVE/2.
    FR=MT*GRAV*(10.+0.01*VAVE+0.00008*VAVE*VAVE)/1000.
    BETA=BET(NTIME)
    FGR=MT*GRAV*SIN(BETA)
    PROAD=(FGR+FR+FO)*VAVE
C  CALC THE POWER DUE TO VEHICLE ENERGY CHANGE
    PWRSTP=(MT*1.1/2.)*((V1*V1)-(V2*V2))/DELT
C  CALC POWER AVAILABLE FOR REGENERATION
    PREGEN=PWRSTP-PROAD
C  IS REGEN POWER ABOVE MIN

```

```

        IF(PREGEN-REGMIN) 230,230,231
C  SET REGENERATED POWERS TO ZERO
230  PAXLE=0.
      PDRIVE=0.
      PGEAR=0.
      PCVT=0.
      PMOTOR=0
      PINV=0.
      PLOSS=0.
      PBLUT=0.
      PHE=0.
      IBATT=0.
      PELEC=0.
      GOTO 235
C  IS BATTERY FULLY CHARGED
231  IF(SOC.GE.1.0) GOTO 230
C  CALC AXLE SPEED AND TORQUE
      WAXLE=VAVE/RTIRE
      TAXLE=PREGEN/WAXLE
      PAXLE=PREGEN
C  CALC DRIVE SHAFT TORQUE, SPEED, POWER
      WDRIVE=WAXLE/RDIFF
      PDPCT=(PREGEN/PDRATE)*100.
      WDPCT=(WAXLE/WDRATE)*100.
      PDRIVE=PREGEN*INTEQ(GREFF,PDPCT,WDPCT,100.,100.,
&1.,-1.,10.,-10.,101,11)
      YDRIVE=PDRIVE/WDRIVE
C  CALC QUANTITIES AT DIFF'L SIDE OF CVT
      WGEAR=WDRIVE/RGEAR
      PGPCCT=(PDRIVE/PCRATE)*100.
      WGPCCT=(WDRIVE/WGRATE)*100.
      PGEAR=PDRIVE*INTEQ(GREFF,PGPCCT,WGPCCT,100.,100.,
&1.,-1.,10.,-10.,101,11)
      TGEAR=PGEAR/WGEAR
C  CALC CVT RATIO
      PHE=0.
      CALL RATIO
C  CALC QUANTITIES ON ENGINE SIDE OF CVT
      WCVT=WGEAR/RCVT
      PCVT=(PGEAR)*(INTNO(EFF,(PGEAR/1000.),RCVT,100.,3.4,
&APCVT,ARCVT,8,7))
      TCVT=PCVT/WCVT
C  LIMIT CVT POWER TO MAX
      IF(PCVT.GT.PCVTMX) PCVT=PCVTMX
      PELEC=PCVT
C  CALC POWER AT MOTOR SIDE OF MOTOR GEAR REDUCER
      WMOTOR=WCVT/RGRM
      PMGPCT=(PCVT/PMGRATE)*100.
      WMPCT=(WCVT/WMGRATE)*100.
      PMOTOR=PCVT*INTEQ(GREFF,PMGPCT,WMPCT,100.,100.,

```

```

&1.,-1.,10.,-10.,101,11)
  WMOTOR=PMOTOR/WMOTOR
C IF REGENERATION POWER IS GREATER THAN MAX MOTOR POWER SET POWER AT MAX
  IF(PMOTOR.GT.PMTMAX) PMOTOR=PMTMAX
C CALC POWER FROM GENERATOR TO INVERTER
  PMTPCT=(PMOTOR/PMTRTD)*100.
  PINV=PMOTOR*
  &INTEQ(EFFMTR,PMTPCT,WMOTOR,200.,1466.,2.5,-2.5,146.61,439.82,81,7)
C INITIALIZE ITERATION COUNTER
  IIREGN=0
C IF INVERTER POWER IS TOO GREAT SET POWER AT MAX
  IF(PINV.GT.PINVMX) PINV=PINVMX
  IFM1=PINV/PMOTOR
C CALC BATTERY INPUT POWER AND CURRENT
C-----
C----- REGENERATIVE BATTERY VOLTAGE LOOP -----
C-----
245 PBOUT=-PINV+3.0*(PINV/VBCHG)+0.035*PINV
  IBATT=PBOUT/VBCHG
  PV8ATT=VBCHG
C IS CHARGING POWER TOO LARGE
  IF(P8MAX*(MC/MCSTND)+PBOUT.GE.0.) GOTU 237
C SET POWER AT MAX AND RECALCULATE BATT CURRENT
  PBOUT=-P8MAX*(MC/MCSTND)
  IBATT=PBOUT/VBCHG
C IS CHARGING CURRENT TOO LARGE
239 IF(IBMAX+IBATT.GE.0.) GOTU 241
C SET CURRENT AT MAX AND RECALCULATE CHARGING POWER
  IBATT=-IBMAX
  PBOUT=IBATT*VBCHG
C SAVE OLD VALUE OF BATT VOLTAGE
241 VBTOLD=VBCHG
C CALC BATT AMP-HRS OUT AND AVER BATT CURRENT SINCE START OF STC'S
  AREGEN=AREGEN-(IBATT*DEL T/3600)
  AACTL=AHOUT-AREGEN-AHCHG
  IAVE=(3600.*AHOUT)/(TIME+FLOAT(MCYCLE-1)*TSTOP)
C CALC STATE OF CHARGE AND BATTERY VOLTAGE DURING REGENERATION
  CAPCTY=MC*PUKRT(IAVE/MC)
  SOC=1.0-(AACTL/CAPCTY)
  IEFF=-IBATT*(MCSTND/MC)
  VBCHG=NC*INTEQ(VCHG,(AACTL/MC),IEFF,15.,300.,1.,0.,25.,0.,13,12)
  REGEFF=NC*INTEQ(0ISCHG,SOC,0.,1.,IEFFMX,.01,-.01,100.,-100.,
&101,6)
  A/VBCHG
C DOES CALC BATTERY VOLTAGE EQUAL ASSUMED VOLTAGE
  IF(ABS(VBCHG-VBTOLD) .LE. VDEL T) GOTU 243
C HAVE WE ITERATED THE MAX NO OF TIMES
  IF(IIREGN.GE.ITERMX) GOTU 244
C INCREMENT ITERATION COUNTER AND RESET A-H INTO BATT
  IIREGN=IIREGN+1

```



```

AREGEN=AREGEN+(IBATT*DELTA/3600.)
GOTO 245
C SET BATT VOLTAGE TO OLD VALUE
244 VBCHG=VBTOLD
C LIMIT SOC TO MAX
243 IF(SOC.LE.1.0) GOTO 242
SOC=1.0
C CALC BATTERY CURRENT REQUIRED TO FULLY CHARGE BATTERY
AREGEN=AREGEN+(IBATT*DELTA/3600.)
IFILL=3600./DELTA*(AHOUT-AREGEN-AHCHG)
IBATT=-IFILL
AREGEN=AREGEN-(IBATT*DELTA/3600.)
AACTL=AHOUT-AREGEN-AHCHG
IEFF=-IBATT*(MCSTND/MC)
VBCHG=NC*INTEQ(VCHG,(AACTL/MC),IEFF,15.,300.,1.,0.,25.,0.,13,12)
REGEFF=NC*INTEQ(DISCHG,SOC,0.,1.,IEFFMX,.01,-.01,100.,-100.,
&101,6)
&/VBCHG
PBOU=VBCHG*IBATT
PVBATT=VBCHG
C SET TOTAL ENERGY OUT OF BATTERY TO ZERO
EBTOT=0.
GO TO 235
242 CONTINUE
C CALC TOTAL BATT ENERGY USED ON THIS TRIP OR FROM START OF STC'S
EBTOT=EBTOT+((PBOU*DELTA)/1.E+06)*REGEFF
C INCREMENT TIME
235 TIME=TIME+DELTA
NTIME=NTIME+1
C$
IF(IA.EQ.1A/57*57.AND.RUN21.EQ.1) WRITE(8,401)
IA=IA+1
IF(RUN21.EQ.1) WRITE(8,5000) NCYCLE,TIME,VAVE,WDRIVE,WGEAR,
&WCVT,WHE,THE,W MOTOR,
&IAVE,I80DD,IFLLBK,IOVRLD,ISWCH,IITER,IHECHG,IICHG,IIREGN
IF(IB.EQ.1B/57*57.AND.RUN21.EQ.1) WRITE(9,402)
IB=IB+1
IF(RUN21.EQ.1) WRITE(9,5010) NCYCLE,TIME,PAXLE,PDRIVE,PGEAR,
&PCVT,RCVT,PHE,PCHG,
&PELEC,P MOTOR,PINV,PBOU,IBATT,PVBATT,SOC,PROAD,PREGEN,
&BSFC1,FUELRT,EFM1
C$
C HAVE WE REACHED THE STOP PHASE OF THE STC
IF(TIME.GE.TSTOP) GOTO 236
V(NTIME)=V2
GO TO 200
C CALC AVER CURRENT FOR ALL STC'S
236 IAVE=(AHOUT*3600.)/(FLOAT(NCYCLE)*TSTOP)
C AT END OF THIS STC, SAVE: BATT SOC, AVERAGE CURRENT,PETROLEUM VOLUME,
C ELECTRICAL ENERGY, AMP-HRS OUT, AMP-HRS REGEN AND BATT. STATE-

```

```

C ALL SINCE START OF STC'S
  IDDD(NCYCLE)=I8DDDD
  IVESTC(NCYCLE)=IAVE
  HOUT(NCYCLE)=AHOUT
  REGEN(NCYCLE)=AREGEN
  EBTOTL(NCYCLE)=EBTOT
  PETSTC(NCYCLE)=VOLTOT
  SOCSTC(NCYCLE)=SOC
  CHARGE(NCYCLE)=ACHG
C#
  I6=I6+1
  IF(I6/NCYLX*NCYLX.EQ.I6.AND.RUN21.LE.1) WRITE(6,404)
  &(I,EBTOTL(I),HOUT(I),IDDD(I),IVESTC(I),PETSTC(I),REGEN(I),
  &SOCSTC(I),CHARGE(I),I=1,NCYCLE)
404  FORMAT(' ',/1X,' I',5X,'EBTOTL(I)',4X,'HOUT(I)',4X,'IDDD(I)',
  &4X,'IVEST(I)',3X,'PETSTC(I)',3X,'REGEN(I)',2X,'SOCSTC(I)',3X,
  &'CHARGE(I)',/36(12,3X,2X,F9.5,2X,F9.5,3X,18,3X,F9.5,
  &4(2X,F9.5)/))
C#
C IS THIS THE END OF THE STC WHICH PRECEEDS ALL HIGHWAY DRIVING?
  IF (NCYCLE-NSTCFR) 238,237,238
C SAVE PRESENT VALUE OF BATTERY VOLTAGE
237  VHWBTT=VBATT
C INITIALIZE POWER REGENERATION VARIABLES
238  PREGEN=0.
  PROAD=0.
  IIREGN=0
C HAVE WE GONE THE MAX NO OF STC'S
  IF(NCYCLE-NCYLX) 240,250,250
C INCREMENT CYCLE COUNTER AND INITIALIZE TIME
240  NCYCLE=NCYCLE+1
  TIME=0.
  NTIME=1
  GOTO 10
C INITIALIZE TRIP CONSUMPTION VARIABLES
250  PETROL=0.
  IHWY=0
  ENEELEC=0.
  NTRIP=1
C DETERMINE LENGTH OF CURRENT TRIP
260  LENGTH=TRIPLN(NTRIP)
C IS TRIP ALL STC'S
  IF(LENGTH.GT.ALLSTC) GOTO 290
C CALC NUMBER OF STC'S IN TRIP
  STCNO=LENGTH/STCDIS
  NOSTC=STCNO
  DELSTC=STCNO-FLOAT(NOSTC)
C CALC AMP-HRS FOR THIS TRIP
  AACTL1=HOUT(NOSTC)-REGEN(NOSTC)-CHARGE(NOSTC)
  AACTL2=HOUT(NOSTC+1)-REGEN(NOSTC+1)-CHARGE(NOSTC+1)

```

```

      AACTL=AACTL1+(AACTL2-AACTL1)*DELSTC
C   CALC PETROL CONSUMPTION FOR THIS TRIP
      PETROL=PETSTC(NOSTC)+DELSTC*(PETSTC(NOSTC+1)-PETSTC(NOSTC))
      APETP(NTRIP)=PETROL
C   CALC ELEC ENERGY CONSUMPTION FOR THIS TRIP USING POWER AND USING AMP-HRS
      ENELEC=EBTOTL(NOSTC)+DELSTC*(EBTOTL(NOSTC+1)-EBTOTL(NOSTC))
      AELETP(NTRIP)=ENELEC
      ENRGY=NC*AACTL*3.6E-03*SVINT(AACV,AACTL/MC,ACR,8)
      AELETA(NTRIP)=ENRGY

C#
C%
C   DETERMINE NO OF SUCH TRIPS/YEAR
      TRIPYR=TRIPNO(NTRIP)
C   DETERMINE YEARLY PETROL AND ELECT CONSUMPTION FOR THIS TRIP
      PETYR(NTRIP)=TRIPYR*PETROL
      ELECYR(NTRIP)=TRIPYR*ENELEC
      ELEC(NTRIP)=TRIPYR*ENRGY
C   WAS THE BATT DISCHARGED SOMETIME DURING THIS TRIP
      IF(IGD(NOSTC).NE.1) GOTO 265
      DISFAC=1
      GOTO 267
265  DISFAC=(1.-SOCSTC(NOSTC))/0.8
C   CALC NO OF DISCHARGES PER YEAR FOR THIS TRIP TYPE
267  DISCH(NTRIP)=DISFAC*TRIPYR
C   IS THIS THE LAST TRIP TYPE
270  IF(NTRIP.GE.NTRIPX) GOTO 271
      NTRIP=NTRIP+1
      GO TO 260
C   DETERMINE WALL PLUG ENERGY REQ'D TO MEET ELECT. ENERGY CONSUMPTION
271  DO 280 I=1,NTRIPX
      ELEC(I)=ELEC(I)/CHGEFF
      AELETA(I)=AELETA(I)/CHGEFF
      AELETP(I)=AELETP(I)/EFFBC
280  ELECVR(I)=ELECVR(I)/EFFBC
      IF(RUN21.LE.1) WRITE(6,126)
126  FORMAT(1X,' I',7X,'DISCH(I)',3X,'PETYR(I)',3X,'ELECVR(I)',
&5X,'ELEC(I)',5X,'TRIPNO(I)',3X,'TRIPLN(I)',10X,
&3X,'PETROL',6X,'ENELEC',6X,'ENRGY')
      DO 6579 I=1,8
6579  IF(RUN21.LE.1) WRITE(6,408) I,DISCH(I),PETYR(I),ELECVR(I),
&AELEC(I),TRIPNO(I),TRIPLN(I),APETP(I),AELETP(I),AELETA(I)
408  FORMAT(1X,I2,5X,F9.4,2X,F9.4,3X,F9.4,6X,F9.4,3X,F6.0,4X,F9.0,10X,
&4,1X,F10.4,2X,F10.4,2X,F10.4)
C+*****
      SUMA=0.
      EAKHY=0.
      SUMP=0.
      PLTVY=0.
      PETV=0.
      DO 83341 I=1,8

```

```

      EAKWHR(I)=ELEC(I)/3.6
      AEKHA(I)=AELETA(I)/3.6
      AEKHP(I)=AELETP(I)/3.6
      PETV=PETV+APETT(I)
      PETVY=PETVY+PETYR(I)
      SUMA=SUMA+AEKHA(I)
      SUMP=SUMP+AEKHP(I)
83341 EAKHY=EAKHY+EAKWHR(I)
      IF(RUN21.NE.4) GOTO 323
      IF(CX(1).NE.0.) GOTO 33244
      WRITE(7,3346)
      IF(RUN21.EQ.4) WRITE(8,3346)
      IF(RUN21.EQ.4) WRITE(9,3346)
      WRITE(10,3346)
3346 FORMAT(2X,'PS',10X,'1',11X,'2',11X,'3',11X,'4',11X,'5',11X,
&'6',11X,'7',11X,'8',10X,'SUM',/'***')
83244 CONTINUE
      WRITE(7,3432) CX(1),(AEKHA(I),I=1,8),SUMA
      WRITE(8,3432) CX(1),(APETT(I),I=1,8),PETV
      WRITE(9,3432) CX(1),(AEKHP(I),I=1,8),SUMP
      WRITE(10,3432) CX(1),(EAKWHR(I),I=1,8),EAKHY
3432 FORMAT(1X,F4.2,1X,8(F11.5,1X),F11.5)
323 CONTINUE
C+++++
      IF(RUN21.LE.1) WRITE(6,3431) IOVRLO,POVRLO,PETVY,EAKHY,INCHG
3431 FORMAT('IOVRLO=',I5,2X,'POVRLO=',G13.7,2X,'TOTAL PETROLEUM ',
&'VOLUME PER YEAR (PETVY)=' ,F9.2,' LITERS/YEAR',5X,
&'TOTAL ELECTRIC ENERGY CONSUMPTION PER YEAR (EAKHY)=' ,F9.2,
&' KILOWATT HOURS/YEAR',5X,'INCHG=' ,I1)
      PETV10=PETVY*10.
      RETURN
C CALC TIME IT TAKES TO MAKE THIS TRIP
290 TRIPTE=FLUAT(NSTCFR)*TSTOP+((LENGTH-FLUAT(NSTCFR)*STCDIS)/HWYVEL)
C IS THIS THE FIRST TRIP REQUIRING HIGHWAY DRIVING
IF(IHWY.NE.0) GOTO 20
C INITIALIZE BATT MODEL AND FUEL CONSUMPTIONS
C VBAIT=VHWBTT
  AHOUT=HOUT(NSTCFR)
  IJDDDD=IDDD(NSTCFR)
  JAVE=IVESTC(NSTCFR)
  VOLTOT=PETSTC(NSTCFR)
  LRTOT=EBTOTL(NSTCFR)
  AREGEN=REGEN(NSTCFR)
  ANCHG=CHARGE(NSTCFR)
C SET VELOCITY, ACCELERATION AND GRADE FOR HIGHWAY DRIVING
  VAVE=HWYVEL
  ACCEL=0.
  BETA=0.
C INITIALIZE TIME TO START OF HIGHWAY DRIVING
  TIME=FLUAT(NSTCFR)*TSTOP

```

```

C  INITIALIZE BATTERY MODEL QUANTITIES FOR START OF HIGHWAY DRIVING
   CAPCTY=MC*PKRT(IAVE/MC)
   AACTL=AHOUT-AREGEN-AHCHG
   SUC=1.0-(AACTL/CAPCTY)
C  SET HIGHWAY FLAG TO HIGHWAY DRIVING CONDITION
   CHWY=1
C  SET HWY DRIVING TIME INCREMENT
   DELT=DELTHW
   GOTO 20
C  CALC YEARLY PETROL CONSUMPTION FOR THIS TRIP TYPE
300  TRIPYR=TRIPND(NTRIP)
   PETYR(NTRIP)=TRIPYR*VOLTOT
   PETROL=VOLTOT
   APETT(NTRIP)=PETROL
C  CALC YEARLY ELEC ENERGY CONSUMPTION FOR THIS TRIP TYPE
   ELECYR(NTRIP)=TRIPYR*EBTOT
   ENELEC=EBTOT
   AELETP(NTRIP)=ENELEC
   ELEC(NTRIP)=TRIPYR*NC*AACTL*3.6E-03*SVINT(AACV,AACTL/MC,ACR,0)
   ENRGY=ELEC(NTRIP)/TRIPYR
   ALETA(NTRIP)=ENRGY
C  SET DISCHG FACTOR TO FULL DISCHG IF BATT WAS DISCHARGED DURING THIS TRIP
   IF(I80000.NE.1) GOTO 310
   DISFAC=1.
   GOTO 320
C  CALC DISCHG FACTOR
310  DISFAC=(1.-SUC)/0.3
C  CALC NO OF YEARLY DISCHARGES FOR THIS TRIP TYPE
320  DISCH(NTRIP)=DISFAC*TRIPYR
   GOTO 270
   END
   END

```

SUBROUTINE RATIO

```

C*****
C
C THIS DETERMINES RATIO OF THE CONTINUOUSLY VARIABLE TRANSMISSION BASED ON
C THE LAST VALUE OF THE GEAR POWER. AT VEHICLE START UP TIME THE VALUE
C IS SET TO A MINIMUM OF .3. THE RATIO VALUE IS LIMITED TO PREVENT
C EXCESSIVE MOTOR SPEED. THE MAXIMUM VALUE IS 3.4.
C
C*****
      REAL MTRSPD(5),APRP(5),AWMT(6),STALL(6)
      COMMON/CC/CDA,RDIFF,RGEAR,RGRM,RTIRE
      COMMON/RRATU/RCVME,WGEAR,RCVT,PMOTOR,PMTRTD,PGEAR
      COMMON/RSPLT/ACCEL,SOC,PCVT,CX(15),VAVE,PHEMAX,PHE,PELEC
      DATA RCVTMX/3.4,RCVTMN/0.3,WMTMX/1675.5,DELR/0.1/
      DATA BSFC/4.2/,WHEMN/104.72/
      DATA MTRSPD/586.431,879.646,1172.86,1319.47,1466.08/
      DATA AWMT/0.,586.431,879.646,1172.86,1319.47,1466.08/
      DATA STALL/0.,50.,75.84,109.57,129.79,200./
      DATA APRP/19.4,36.7,64.3,75.5,101./
C IS VEHICLE JUST STARTING UP
      IF(NTIME.NE.1) GO TO 10
C SET RATIO AT MINIMUM
      RCVT=RCVTMN
      RETURN
C WAS HE POWER USED IN THE LAST ITERATION
10 IF(PHE.GT.0.) GO TO 20
C PICK RATIO TO MAXIMIZE MOTOR EFF
      PMT=PGEAR/(0.93*0.98)
C COMPUTE MOTOR POWER IN PERCENT OF RATED POWER
      PMTPCT=(PMT/PMTRTD)*100.
      RCVT=WGEAR/(SVINT(MTRSPD,PMTPCT,APRP,5)*RGRM)
C LIMIT RATIO SO MOTOR SPEED IS NOT EXCESSIVE
      WMT=WGEAR/(RCVT*RGRM)
      IF(WMT.LE.WMTMX) GO TO 40
      WMT=WMTMX
      RCVT=WGEAR/(WMT*RGRM)
      GO TO 40
C ESTIMATE A HE OUTPUT POWER FOR THIS ITERATION
20 PHEST=(PHE/(PHE+PELEC))*(PGEAR/0.93)
C CALC MOST EFFICIENT HE SPEED
      WHEFF=BSFC*(PHEST/PHEMAX)*100.
      IF(WHEFF.LT.WHEMN) WHEFF=WHEMN
C CAL RATIO
      RCVT=WGEAR/WHEFF
C CAL MOTOR SPEED
      WMT=WGEAR/(RCVT*RGRM)
C CALC REQUIRED MOTOR POWER AT THIS SPEED
      PMT=(PGEAR/0.93)-PHEST
      PMTPCT=(PMT/PMTRTD)*100.
C CAN MOTOR DELIVER THIS POWER AT THIS SPEED

```

```
30 IF(PMT/PCF.LT.SVINT(STALL,WMT,AWMT,6)) GO TO 40
C DECREASE RATIO TO INCREASE MOTOR SPEED
  RCVT=RCVT-DELR
  WMT=WGEAR/(RCVT*RGRR)
  IF(RCVT.GT.RCVTMN) GO TO 30
C IS RATIO ABOVE UPPER LIMIT
40 IF(RCVT.GT.RCVTMX) RCVT=RCVTMX
  IF(RCVT.LT.RCVTMN) RCVT=RCVTMN
  RETURN
END
END
```

```

FTN4,L
SUBROUTINE SPLIT
C*****
C
C THIS DETERMINES THE POWER SPLIT BETWEEN THE HEAT ENGINE AND THE
C ELECTRIC MOTOR. IT IS A FUNCTION OF THE ACCELERATION AND THE STATE
C OF CHARGE OF THE BATTERY.
C
C*****
COMMON/RSPLIT/ACCEL,SOC,PCVT,CX(15),VAVE,PHIEMAX, PHE,PELEC
C PS =0 WHEN ONLY HEAT ENGINE USED
C PS =1 WHEN ONLY BATTERIES USED
DATA VMINHE/1.34/
C IS VEHICLE VELOCITY BELOW MIN
IF(VAVE-VMINHE) 10,10,20
10 PS=1.0
GOTO 30
20 PS=CX(1)+CX(2)*ACCEL+CX(3)*SOC
IF(PS.GT.1.) PS=1.
IF(PS.LT.0.) PS=0.
30 PELEC=PCVT*PS
PHE=PCVT*(1.0-PS)
RETURN
END
END

```



FTN4,L

SUBROUTINE SPLIT

C\*\*\*\*\*

C

C THIS DETERMINES THE POWER SPLIT BETWEEN THE HEAT ENGINE AND THE  
C ELECTRIC MOTOR. IT IS A FUNCTION OF THE ACCELERATION AND THE STATE  
C OF CHARGE OF THE BATTERY. (AIRESEARCH POWER SPLIT)

C

C\*\*\*\*\*

COMMON/RSPLOT/ACCEL,SOC,PCVT,CX(15),VAVE,PHEMAX, PHE,PELEC

C PS =0 WHEN ONLY HEAT ENGINE USED

C PS =1 WHEN ONLY BATTERIES USED

DATA VMINHE/1.34/

C IS VEHICLE VELOCITY BELOW MIN

IF(VAVE-VMINHE) 10,10,20

10 PS=1.0

GOTO 80

20 IF(ACCEL.NE.0.) GOTO 40

IF(SOC.LE.2) GOTO 70

C IS THIS A HILL CLIMB

IF(PCVT.GE.20000.) GOTO 30

PS=1.

GOTO 80

30 PS=.3

GOTO 80

C IS REQUIRED POWER TOO LARGE

40 IF(PCVT.GE. .8\*PHEMAX) GOTO 50

PS=.3

GOTO 80

50 PHE=PCVT

IF(PHE.LE.PHEMAX) GOTO 60

PHE=PHEMAX

PELEC=PCVT-PHEMAX

PS=PELEC/PCVT

RETURN

60 PHE=PCVT

PELEC=0.

PS=0.

RETURN

70 PS=0.

80 PELEC=PCVT\*PS

PHE=PCVT\*(1.0-PS)

RETURN

END

END

```

      REAL FUNCTION PUKRT(IAVE)
C*****
C
C CALCULATES CAPACITY PER KILOGRAM OF BATTERY BASED ON THE AVERAGE
C CURRENT PER KILOGRAM OUT OF THE BATTERY. IT IS LIMITED TO A
C MINIMUM OF 0.5.
C
C*****
      REAL IAVE
      IF(IAVE.LT.10.173) GOTO 10
      PUKRT=22.38811 - 3.796948*ALOG(IAVE)
      IF(PUKRT.LT. .5) PUKRT=.5
      RETURN
10  PUKRT=16.98881-.3806714*IAVE
      RETURN
      END

```

```

      FUNCTION SVINT(ARRAY,X,XARRAY,IDIM)
C*****
C
C SINGLE VARIABLE INTERPOLATION SUBROUTINE. SPACING BETWEEN DATA
C POINTS OF THE INDEPENDENT VARIABLE NEED NOT BE EQUAL.
C
C*****
      DIMENSION ARRAY(IDIM),XARRAY(IDIM)
      IDM1=IDIM-1
      DO 5 IMAX=2,IDM1
      IF(X.LE.XARRAY(IMAX)) GO TO 7
5   CONTINUE
7   IMIN=IMAX-1
      SVINT=((X-XARRAY(IMIN))*ARRAY(IMAX)+
&(XARRAY(IMAX)-X)*ARRAY(IMIN))/(XARRAY(IMAX)-XARRAY(IMIN))
      RETURN
      END
      END

```

```

      REAL FUNCTION INTNQ(ARRAY,XX,YY,XTOP,YTOP,XARRAY,YARRAY,IDIM,JDIM)
C*****
C
C DOUBLE VARIABLE INTERPOLATION SUBROUTINE. BOTH VARIABLES NEED NOT
C HAVE EQUAL SPACING BETWEEN DATA POINTS.
C
C*****
C THIS LINEAR INTERPOLATION MUST TAKE INTO ACCOUNT VALUES OF X AND Y LYING
C ABOVE AND BELOW THE MAXIMUM AND MINIMUM VALUES IN THE ARRAY
      DIMENSION XARRAY(IDIM),YARRAY(JDIM),ARRAY(IDIM,JDIM)
      X=XX
      Y=YY
      IF(X.GT.XTOP) X=XTOP
      IF(Y.GT.YTOP) Y=YTOP
C FIND INDICES ON X ARRAY
      IDM1=IDIM-1
      DO 5 IMA=2,IDM1
      IF(X.LE.XARRAY(IMA)) GO TO 7
5      CONTINUE
7      IMIN=IMA-1
C FIND THE INDICES OF THE VALUES IN THE YARRAY WHICH BRACKET THE
C ACTUAL Y VALUE
      JDM1=JDIM-1
      DO 15 JMA=2,JDM1
      IF(Y.LE.YARRAY(JMA)) GO TO 17
15     CONTINUE
17     JMIN=JMA-1
C INTERPOLATE TO FIND THE ARRAY VALUES CORRESPONDING TO THE
C BRACKETING X VALUES AND THE ACTUAL Y VALUES
      ALOWY=((X-XARRAY(IMIN))*ARRAY(IMA,JMIN)+
      &(XARRAY(IMA)-X)*ARRAY(IMIN,JMIN))/(XARRAY(IMA)-XARRAY(IMIN))
      AHIGHY=((X-XARRAY(IMIN))*ARRAY(IMA,JMAX)+
      &(XARRAY(IMA)-X)*ARRAY(IMIN,JMAX))/(XARRAY(IMA)-XARRAY(IMIN))
C INTERPOLATE BETWEEN THE ABOVE ARRAY VALUES TO FIND THE ARRAY VALUE
C CORRESPONDING TO THE ACTUAL Y VALUE
      INTNQ=((Y-YARRAY(JMIN))*AHIGHY+(YARRAY(JMAX)-Y)*ALOWY)/
      &(YARRAY(JMAX)-YARRAY(JMIN))
      RETURN
      END
      END

```

```

      REAL FUNCTION INTEQ(ARRAY,XX,YY,XTOP, YTOP,
      &XCON1,XCON2,YCON1,YCON2, IDIM,JDIM)
C*****
C
C DOUBLE VARIABLE INTERPOLATION SUBROUTINE. BOTH VARIABLES MUST HAVE
C EQUAL SPACING BETWEEN THE DATA POINTS.
C
C*****
      DIMENSION ARRAY(IDIM,JDIM)
C
      X=XX
      Y=YY
      IF(X.GT.XTOP) X=XTOP
      IF(Y.GT.YTOP) Y=YTOP
C X=FLOAT(I)*XCON1+XCON2
C Y=FLOAT(J)*YCON1+YCON2
C
C FIND THE INDICE OF THE X VALUE WHICH BRACKETS THE ACTUAL X VALUE
      IMIN=(X-XCON2)/XCON1
      IF(IMIN.LT.1) IMIN=1
      IF(IMIN.GE.IDIM) IMIN=IDIM-1
      IMAX=IMIN+1
      XMIN=FLOAT(IMIN)*XCON1+XCON2
      XMAX=XMIN+XCON1
C FIND THE INDICE OF THE Y VALUE WHICH BRACKETS THE ACTUAL Y VALUE
      JMIN=(Y-YCON2)/YCON1
      IF(JMIN.LT.1) JMIN=1
      IF(JMIN.GE.JDIM) JMIN=JDIM-1
      JMAX=JMIN+1
      YMIN=FLOAT(JMIN)*YCON1+YCON2
      YMAX=YMIN+YCON1
C INTERPOLATE TO FIND THE ARRAY VALUE CORRESPONDING TO THE BRACKETING
C X VALUES AND THE ACTUAL X VALUES
      ALOWY=((X-XMIN)*ARRAY(IMAX,JMIN)+
      &(XMAX-X)*ARRAY(IMIN,JMIN))/(XMAX-XMIN)
      AHIGHY=((X-XMIN)*ARRAY(IMAX,JMAX)+
      1(XMAX-X)*ARRAY(IMIN,JMAX))/(XMAX-XMIN)
C INTERPOLATE TO FIND THE ARRAY VALUE CORRESPONDING TO THE ACTUAL
C Y VALUE
      INTEQ=((Y-YMIN)*AHIGHY+(YMAX-Y)*ALOWY)/(YMAX-YMIN)
      RETURN
      END
      ENO

```

```

      SUBROUTINE WGH1(HEKW,WGBATT, WT,MT,WGCHI,WP)
C*****
C
C THIS CALCULATES THE TOTAL MASS AND CURB MASS OF THE VEHICLE.
C
C*****
      REAL MT,MTRC1,MTRKW,MTGRKW
      INTEGER RUN21
      COMMON RUN21
      COMMON/KILOG/WGENG,WGCVT,WGCHGR,WGGRM,WGGRDF
      &,WGDIF,WF,WPL,WPROP,WS,WGMOTR,WGCLT,WCURB
      COMMON/VARY/ WTL,INCHG
      DATA CVTC1/1.07/, CVTKW/90.0/, HEC1/0.0/, HEC2/2.84/
      DATA MTRC1/0.6/, MTRKW/20.0/, CHIC1/0.91/, CHIKW/40.0/
      DATA WGEXTR/0.0/
      DATA DIFFC1/0.66/, DIFFKW/90.0/, GRC1/0.3/, MTGRKW/40.0/
      DATA DFGRKW/90.0/, CHGRC1/0.0/, CHGRKW/14.5/
C COMPUTE CONSTANT TERM IN VEHICLE WEIGHT FORMULA
C (FROM MTI,APPENDIXB)
      WCONST=((0.23*WPL+WF)/0.77)+WTL
C CALC. PROPULSION SYST. COMPONENT WEIGHTS
C CVT
      WGCVT=CVTC1*CVTKW
C HE
      WGENG=(HEC1*HEKW+HEC2)*HEKW
C MOTOR
      WGMOTR=MTRC1*MTRKW
C CHOPPER/INV.
      WGCHI=CHIC1*CHIKW
C DIFF'L
      WGDIF=DIFFC1*DIFFKW
C GEAR BETWEEN MOTOR AND CVT
      WGGRM=GRC1*MTGRKW
C GEAR BETWEEN DIFF & CVT
      WGGRDF=GRC1*DFGRKW
C CHARGER
      WGCHGR=CHGRC1*CHGRKW
C CALCULATE PROPULSION SYSTEM WEIGHT
      WPROP=WGENG+WGCVT+WGMOTR+WGCHI+WGDIF+WGGRM+WGGRDF+WGCHGR
      &+WGEXTR+WGBATT+WGCLT
C CALCULATE VEHICLE TOTAL WEIGHT
      WT=WCONST + WPROP/0.77
C CALCULATE VEHICLE TOTAL MASS
      MT=WT
C CALCULATE CURB MASS OF VEHICLE
      WCURB=WT-WTL
C CALC. POWER TRAIN WEIGHT
      WP=(WPROP-WGBATT)
      A=WGCVT+WGGRM+WGGRDF+WGDIF
      IF(RUN21.LE.1) WRITE(6,2001) WCURB,WF,WGBATT,WGCHGR,WGCHI,WGCLT,

```

```

& WGCVT,WGDIFF,WGENG,WGEXTR,WGGRDF,WGGRM,WGMOTR,WP,WPL,WPROP,
&WT,WTL,A
2001 FORMAT(/'***** VEHICLE MASSES *****',/
&'
&' CURB MASS OF VEHICLE (WCURB)=' ,F9.3,/
&' FIXED VEHICLE MASS (WF)=' ,F9.3,/
&' BATTERY WEIGHT (WGBATT)=' ,F9.3,/
&' CHARGER MASS (WGCHGR)=' ,F9.3,/
&' CHOPPER INVERTER MASS (WGCHI)=' ,F9.3,/
&' CLUTCH MASS (WGCLT)=' ,F9.3,/
&' CVT MASS (WGCVT)=' ,F9.3,/
&' DIFFERENTIAL MASS (WGDIFF)=' ,F9.3,/
&' ENGINE MASS (WGENG)=' ,F9.3,/
&' EXTRA VEHICLE PROPULSION COMPONENT MASS (WGEXTR)=' ,F9.3,/
&' MASS OF GEAR BETWEEN CVT & DIFFERENTIAL (WGGRDF)=' ,F9.3,/
&' MASS OF GEAR BETWEEN MOTOR & CVT (WGGRM)=' ,F9.3,/
&' ELECTRIC MOTOR MASS (WGMOTR)=' ,F9.3,/
&' POWER TRAIN MASS (WP)=' ,F9.3,/
&' MAXIMUM PAYLOAD MASS (WPL)=' ,F9.3,/
&' PROPULSION SYSTEM MASS (WPROP)=' ,F9.3,/
&' TOTAL MASS (WT)=' ,F9.3,/
&' TEST PAYLOAD MASS (WTL)=' ,F9.3,/
&' WGCVT+WGGGRM+WGGGRDF+WGDIFFF=' ,/
&' TRANSMISSION & DRIVE TRAIN WEIGHT=' ,F9.3)
RETURN
END
END

```

```

SUBROUTINE MFCST(WGBATT,WGCHI, MNFCST)
C*****
C
C THIS DETERMINES THE MANUFACTURING COST OF THE VEHICLE AS A FUNCTION
C OF THE VARIOUS MASSES.
C
C*****
REAL MNFCST,MTRCER,MTRCST
INTEGER RUN21
COMMON RUN21
COMMON/KILOG/WGENG,WGCVT,WGCHGR,WGGRM,WGGRDF
&,WGDIFF,WF,WPL,WPROP,WS,WGMOTR,WGCLT,WCURB
DATA HECER/1.43/, CVTCER/1.42/, CHGCER/5.89/
DATA CHICER/14.0/, GRCCER/2.43/, DIFCER/2.42/, WFCER/3.13/
DATA WSCER/3./, MTRCER/15.95/, CLTCER/0.0/
DATA ASMCER/0.1284/
C CALCULATES MANUFACTURING COSTS FOR PROPULSION SYSTEM COMPONENTS
C
HECOST=HECER*WGENG
CVTCST=CVTCER*WGCVT
CHGCST=CHGCER*WGCHGR
CHICST=CHICER*WGCHI
GRMCST=GRCCER*WGGRM
GRDCST=GRCCER*WGGRDF
DIFCST=DIFCER*WGDIFF
WFCOST=WFCER*WF
WS=0.3*(WPL+WPROP+WF)
WGCOST=WSCER*WS
MTRCST=MTRCER*WGMOTR
CLTCST=CLTCER*WGCLT
ASMCST=ASMCER*WCURB
C CALCULATE TOTAL MANUFACTURING COST
A=CVTCST+GRMCST+GRDCST+DIFCST+CLTCST
MNFCST=HECOST+CVTCST+CHGCST+CHICST+GRMCST+GRDCST
&+DIFCST+WFCOST+WGCOST+MTRCST+CLTCST+ASMCST
IF(RUN21.LE.1) WRITE(6,1900) WS
1900 FORMAT(
&'          STRUCTURE & CHASSIS MASS (WS)=' ,F9.3)
IF(RUN21.LE.1) WRITE(6,2000) ASMCST,CHGCST,CHICST,CLTCST,CVTCST,
&DIFCST,GRDCST,GRMCST,HECOST,MNFCST,MTRCST,WFCOST,WGCOST,A
2000 FORMAT(/"***** MANUFACTURING COSTS FOLLOW *****"/
&'          ASSEMBLY COST (ASMCST)=' ,F9.3,/
&'          CHARGER COST (CHGCST)=' ,F9.3,/
&'          CHOPPER INVERTER COST (CHICST)=' ,F9.3,/
&'          CLUTCH COST (CLTCST)=' ,F9.3,/
&'          CVT COST (CVTCST)=' ,F9.3,/
&'          DIFFERENTIAL COST (DIFCST)=' ,F9.3,/
&'          GEAR BETWEEN DIFF & CVT COST (GRDCST)=' ,F9.3,/
&'          GEAR BETWEEN MOTOR & CVT COST (GRMCST)=' ,F9.3,/
&'          HEAT ENGINE COST (HECOST)=' ,F9.3,/

```

```
&'      TOTAL MANUFACTURING COST (MFCST)='F9.3,/
&'      ELECTRIC MOTOR COST (MTRCST)='F9.3,/
&'      COST OF VEHICLE FIXED WEIGHT (WFCOST)='F9.3,/
&'      COST OF STRUCTURE & CHASSIS (WSCOST)='F9.3,/
&'      CVTCST+GRMCST+GRDCST+DIFCST+CLTCST='F9.3)
RETURN
END
END
```



```

SUBROUTINE MAINT(HEKW,MTKWPK,BATCST,KMPYR,WP,WGCHI,BTLIST,MAINTC)
C*****
C
C THIS CALCULATES THE YEARLY MAINTENANCE COST OF THE VEHICLE AS A FUNCTION
C OF HEAT ENGINE, BATTERY, AND VEHICLE MAINTENANCE, AND ANNUAL DRIVING
C DISTANCE.
C
C*****
REAL KWCST,MTKWPK,KMPYR,MAINTC,MTMAIN
INTEGER RUN21
COMMON RUN21
COMMON/BATT/BTKUP
COMMON/COST/GASCST(10),KWCST(10)
C CALCULATE COMPONENT MAINTENANCE COSTS ($/KM)
HEMAIN=(0.18+0.005*(HEKW/0.746))/160.93
MTMAIN=(0.06+0.002*(MTKWPK/0.746))/160.93
BTLIST=BATCST*(1.+BTKUP)
BTMAIN=(0.0004*BTLIST)/160.93
CVTMAN=0.063/160.93
C (AR-H P. 78) 1/2 MAINTENANCE 1/2 REPAIR
CHIMAN=((36.83/2)*SQRT(WGCHI))/(10.*KMPYR)
C CALCULATE MAINTENANCE COST FOR ONE YEAR
MAINTC=(HEMAIN+MTMAIN+BTMAIN+CVTMAN+CHIMAN)*KMPYR
IF(RUN21.LE.1) WRITE(6,2020) BTLIST
2020 FORMAT(' LIST COST OF BATTERIES (BTLIST)=' ,F9.3)
IF(RUN21.LE.1) WRITE(6,2030) BTMAIN,CVTMAN,CHIMAN,HEMAIN,
&MAINTC,MTMAIN
2030 FORMAT('/***** MAINTENANCE COSTS FOLLOW *****/, /
&' BATTERY MAINTENANCE COST PER KILOMETER (BTMAIN)=' ,F9.8, /
&' CVT MAINTENANCE COST PER KILOMETER (CVTMAN)=' ,F9.8, /
&' CHOPPER INVERTER MAINTENANCE COST PER KILOMETER (CHIMAN)=' ,F9.8, /
&' HEAT ENGINE MAINTENANCE COST PER KILOMETER (HEMAIN)=' ,F9.8, /
&' TOTAL MAINTENANCE COST (MAINTC)=' ,F9.8, /
&' ELECTRIC MOTOR MAINTENANCE COST PER KILOMETER (MTMAIN)=' ,F9.8)
RETURN
END
END

```

```

      SUBROUTINE REPAR(HEKW,MTKWPK,WP,WGCHI,KMPYR, REPAIR)
C*****
C
C THIS CALCULATES THE YEARLY VEHICLE REPAIR COST AS A FUNCTION OF THE
C ANTICIPATED REPAIR COSTS FOR THE HEAT ENGINE, MOTOR, CVT, POWER TRAIN,
C AND CHOPPER INVERTER.
C
C*****
      REAL KMPYR,MTKWPK
      INTEGER RUN21
      COMMON RUN21
      REPRHE=(0.28+0.008*(HEKW/0.746))/160.93
      REPMTR=(0.09+0.002*(MTKWPK/0.746))/160.93
      REPCVT=(0.05+0.0013*(MTKWPK/0.746))/160.93
      REPCHI=((36.83/2.)*SQRT(WGCHI))/(10.*KMPYR)
C CALCULATE YEARLY REPAIR COST
      REPAIR=(REPRHE+REPMTR+REPCVT+REPCHI)*KMPYR
      IF(RUN21.LE.1) WRITE(6,2020) REPAIR,REPCHI,REPCVT,REPMTR,REPRHE
2020 FORMAT(/'***** REPAIR COSTS FOLLOW *****',/
&'          TOTAL REPAIR COST (REPAIR)=' ,F9.3,/
&'CHOPPER INVERTER REPAIR COST PER KILOMETER (REPCHI)=' ,F9.8,/
&'          CVT REPAIR COST PER KILOMETER (REPCVT)=' ,F9.8,/
&' ELECTRIC MOTOR REPAIR COST PER KILOMETER (REPMTR)=' ,F9.8,/
&'          HE REPAIR COST PER KILOMETER (REPRHE)=' ,F9.8)
      RETURN
      END
      END

```

```

SUBROUTINE ACQCST(MNFCST,WGBATT, BATCST,ACQCST)
C*****
C
C THIS DETERMINES THE ACQUISITION COST OF THE VEHICLE AS A FUNCTION OF THE
C MANUFACTURING COST, BATTERY MANUFACTURING COST, AND THE MARKUP FACTOR.
C
C*****
REAL MARKUP,MNFCST
INTEGER RUN21
COMMON RUN21
COMMON/BATT/BTKUP
DATA BATCER/1.87/
C CALCULATE THE MARKUP FACTOR
MARKUP=(29.176E-5)*MNFCST+1.40833
C CALCULATE BATTERY COST
BATCST=BATCER*WGBATT
C CALCULATE ACQUISITION COST (COST TO CONSUMER)
ACQCST=MARKUP*MNFCST+BATCST*(1.+BTKUP)
IF(RUN21.LE.1) WRITE(6,101) BATCST,MARKUP
101 FORMAT(
&'MANUFACTURING COST OF BATTERIES (BATCST)='&,F9.3,/&
&40X,'@@ @@ @@ DEALER MARKUP FACTOR (MARKUP)='&,G11.5)
RETURN
END
END

```

```

FIN4,L
      SUBROUTINE LIFE(PETYR,ELECYR,ELEC,DISCH,BTLIST,ACQCST,MAINTC,
      &REPAIR,BATCST,LCCOST,PETCST,ELECST,TOTPEF)
C*****
C
C THIS CALCULATES THE LIFE CYCLE COST OF THE VEHICLE BASED ON TEN YEARS
C USAGE. IT IS A FUNCTION OF THE ACQUISITION, MAINTENANCE, REPAIR,
C BATTERY, FUEL, AND ELECTRICITY COSTS OVER THAT PERIOD.
C
C*****
      LOGICAL SMOOTH
      REAL KWCST,MAINTC,LCCOST
      INTEGER RUN21
      COMMON RUN21
      COMMON GF
      COMMON/BATT/BTKUP
      COMMON/COST/GASCST(10),KWCST(10)
      COMMON/LIMIT/NTRIPX,ITERMX
      COMMON/CHOOSE/CHOOSE,SMOOTH
      COMMON BTCOST,BATRYR,BATLFE
      DIMENSION PETYR(15),ELECYR(15),ELEC(15),DISCH(15),
      &PETCST(10),ELECST(10)
      DIMENSION VHCOST(10)
      DATA DISCNT/0.02/,DISLFE/840./
C CALC PETROL AND ELEC COSTS: INITIALIZE YEAR INDEX AND TOTAL COSTS
      DO 5 IYEAR=1,10
        PETCST(IYEAR)=0.
5      ELECST(IYEAR)=0.
        DO 10 JTRIP=1,NTRIPX
C ADD COSTS FOR THIS TRIP TO TOTAL COSTS
          PETCST(IYEAR)=PETCST(IYEAR)+PETYR(JTRIP)*GASCST(IYEAR)*GF
10      ELECST(IYEAR)=ELECST(IYEAR)+(CHOOSE*ELECYR(JTRIP)+
          &(1.-CHOOSE)*ELEC(JTRIP))*KWCST(IYEAR)
C CALC NO. OF DEEP DISCHARGES OF BATT. DURING ONE YEAR
          DEEP=0.
          DO 20 JTRIP=1,NTRIPX
20      DEEP=DEEP+DISCH(JTRIP)
C CALC NO. OF YEARS IN BATT LIFE
          BATLFE=DISLFE/DEEP
C CALC BATT REPLACEMENT COST
          BTCOST=BATCST*(1.+2.*BTKUP)
C CALC TOTAL VEHICLE COST FOR ONE YEAR
          COUNT=1.
          TOTBAT=0.
          BATRYR=(((10./BATLFE)-1.)*BTCOST)/10.
          DO 40 IYEAR=1,10
            VHCOST(IYEAR)=PETCST(IYEAR)+MAINTC+ELECST(IYEAR)+REPAIR
            IF(.NOT.SMOOTH) GOTO 35
            VHCOST(IYEAR)=VHCOST(IYEAR)+BATRYR
          35
        40
      50
    END

```

```

        TOTBAT=TOTBAT+BATYR/(DISCNT+1.)**(IYEAR-1)
        GO TO 40
C   IS THIS A YEAR FOR BATT REPLACEMENT
35  IF(FLOAT(IYEAR).LE.COUNT*BATLFE) GOTO 40
C   ADD IN BATT REPLACEMENT COST
        VHCOST(IYEAR)=VHCOST(IYEAR)+0.9*BTCOST
        TOTBAT=TOTBAT+BTCOST/((DISCNT+1.)**(IYEAR-1))
        COUNT=COUNT+1.
40  CONTINUE
C   CALC VEHICLE AND POWER TRAIN AND BATT SALVAGE VALUE
        SALVGE=0.1*(ACQCST-BTLIST)
        BATSAL=0.5*BTLIST*(COUNT-(10./BATLFE))
        IF(SMOOTH) BATSAL=0.
C   CALC LIFE CYCLE COST
        LCCOST=0.
        TOTPET=0.
        DO 50 IYEAR=1,10
            TOTPET=TOTPET+PETCST(IYEAR)/((DISCNT+1.)**(IYEAR-1))
50    LCCOST=LCCOST+VHCOST(IYEAR)/((DISCNT+1.)**(IYEAR-1))
C   SUBTRACT SALVAGE VALUES
        LCCOST=LCCOST-(SALVGE+BATSAL)/((DISCNT+1.)**10)
C   ADD IN AQUISITION COST
        LCCOST=LCCOST+ACQCST
        IF(RUN21.LE.1) WRITE(6,131) BATLFE,BATSAL,LCCOST,BTCOST,SALVGE
131  FORMAT(
&'          BATTERY LIFE (BATLFE) =',F9.3,/
&'          BATTERY SALVAGE VALUE (BATSAL) =',F9.3,/
&'          LIFE CYCLE COST (LCCOST) =',F9.3,/
&'          BATTERY REPLACEMENT COST (BTCOST) =',F9.3,/
&'          SALVAGE VALUE (SALVGE) =',F9.3)
        IF(RUN21.LE.1)
&WRITE(6,404) (I,PETCST(I),ELECST(I),VHCOST(I),I=1,10)
404  FORMAT(' ',/1X,'YEAR',5X,'PETROLEUM COST',3X,
&'ELECTRICITY COST',3X,'VEHICLE COST',/
&' I',10X,'PETCST(I)',8X,'ELECST(I)',8X,'VHCOST(I)',
&/10(1X,I2,2X,3(8X,F9.5)/))
        RETURN
        END
        END

```

```

      BLOCK DATA
C*****
C
C   BLOCK DATA
C
C*****
      LOGICAL SMOOTH
      REAL KWCS1,MTKWPK,IVESTC
      COMMON/ALPHA/ALPHA1,ALPHA2,ALPHA3
      COMMON/BATT/BTMKUP
      COMMON/CC/CDA,RDIFF,RGEAR,RGRM,RTIRE
      COMMON/COST/GASCST(10),KWCS1(10)
      COMMON/EFCVT/APCVT(8),ARCVT(7),EFF(8,7)
      COMMON/KILOG/WGENG,WGCVT,WGCHGR,WGGRM,WGGRDF
      &,WGDIFF,WFWPL,WPROP,WS,WGMOTR,WGCLT,WCURB
      COMMON/LIMIT/NTRIPX,ITERMX
      COMMON/MAP/DISCHG(101,6),EFFMTR(81,7),HEMAP(6,6),
      &GREFF(101,11),VCHG(13,12),ATORQ(6),AESPED(6),ARATIO(10)
      COMMON/UNISC/CHOOSE,SMOOTH
      COMMON/MOTOR/MTKWPK
      COMMON/PHY/GRAV,RHD
      COMMON/PRINT/APETT(15),AELETA(15),AELETP(15)
      COMMON/RRATIO/NRIME,WGEAR,RCVT,PMOTOR,PMTRFD,PGEAR
      COMMON/RSPLT/ACCEL,SOC,PCVT,CX(15),VAVE,PHEMAX,PHE,PELEC
      COMMON/SCALE/SFX(17),SFG(20),NN
      COMMON/STC/V(831),BET(831),TRIPLN(8),TRIPNO(8)
      COMMON/CHARG/AACV(8),ACR(8)
      COMMON/TIMEC/PLTSTC,DELTHW,TACCEL,TCOAST,TBRAKE,TSTOP,TCYCLE
      COMMON/TRIP/CHARGE(36),EBFOIL(36),HOUT(36),IDOD(36),
      &IVESTC(36),PETSTC(36),SOCSTC(36),REGEN(36)
      COMMON/VARY/ WFL,INCHG
      COMMON/YEARC/PETYR(15),ELECVR(15),ELEC(15),DISCH(15)
C
C ALPHA
      DATA ALPHA1/1./,ALPHA2/0./,ALPHA3/0./
C BATT
      DATA BTMKUP/.3/
C CC
      DATA CDA/.6/,RDIFF/1./,RGEAR/.08333333/,RGRM/0.2857/
      DATA RTIRE/.3/
C COST
      DATA GASCST/0.32,0.35,0.38,0.41,0.44,0.47,0.5,0.53,0.56,0.59/
      DATA KWCS1/.0111,.0125,.0139,.0153,.0167,.0181,.0194,
      &.0208,.0222,.0236/
C KILOG
      DATA WFW510./,WGCLT/0./,WPL/415./
C LIMIT
      DATA ITERMX/5/,NTRIPX/8/
C MOTOR
      DATA MTKWPK/40./

```

C OMISC  
   DATA CHOOSE/0./,SMOOTH/.TRUE./  
 C PHY  
   DATA GRAV/9.807/, RHO/1.225/  
 C RRATIO  
   DATA PMTRID/20000./  
 C SCALE  
   DATA SFX/20\*1./, NN/5/  
   DATA SFG/20\*1./  
 C STC  
   DATA RET/830%0./  
   DATA TRIPLN/10000.,30000.,50000.,80000.,130000.,160000.,  
   &500000.,800000./  
   DATA TRIPNO/130.,85.,57.,54.,12.,7.,3.,1./  
 C TEST  
   DATA AACV/2.265,2.2225,2.1993,2.1827,2.1702,2.1607,2.1524,2.1455/  
   DATA ACR/0.,1.017,2.034,3.052,4.069,5.086,6.104,7.121/  
 C TIMEC  
   DATA DLTSTC/1./, DELTHW/30./  
   DATA TACCEL/14.0/, TCOAST/64.0/, TBRAKE/74.0/, TSTOP/83./  
   DATA TCYCLE/108./  
 C VARY  
   DATA WTL/207./, INOCHG/1/  
 C  
   DATA DISCHG/1.30,1.30,1.30,1.30,1.30,1.30,1.30,1.30,  
   &1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
   &1.3000,1.3000,1.3000,1.3000,1.3000,1.6800,1.7400,1.7570,  
   &1.7670,1.7800,1.7930,1.8015,1.8100,1.8190,1.8295,1.8393,  
   &1.8490,1.8585,1.8640,1.8715,1.8790,1.8845,1.8900,1.8955,  
   &1.9010,1.9048,1.9085,1.9123,1.9160,1.9197,1.9235,1.9272,  
   &1.9310,1.9349,1.9388,1.9426,1.9465,1.9504,1.9542,1.9581,  
   &1.9620,1.9645,1.9670,1.9695,1.9720,1.9745,1.9770,1.9795,  
   &1.9820,1.9845,1.9870,1.9895,1.9920,1.9942,1.9964,1.9986,  
   &2.0008,2.0030,2.0052,2.0074,2.0096,2.0118,2.0140,2.0159,  
   &2.0178,2.0197,2.0217,2.0236,2.0255,2.0274,2.0293,2.0313,  
   &2.0332,2.0351,2.0370,2.0382,2.0394,2.0406,2.0418,2.0430,  
   &2.0442,2.0454,2.0466,2.0478,2.0490,  
   &1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
   &1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
   &1.3000,1.3000,1.3000,1.3000,1.3000,1.5200,1.6320,1.6870,  
   &1.7190,1.7420,1.7570,1.7685,1.7800,1.7883,1.7965,1.8047,  
   &1.8130,1.8185,1.8240,1.8295,1.8350,1.8395,1.8440,1.8485,  
   &1.8530,1.8565,1.8600,1.8635,1.8670,1.8705,1.8740,1.8775,  
   &1.8810,1.8834,1.8858,1.8881,1.8905,1.8929,1.8953,1.8976,  
   &1.9000,1.9020,1.9040,1.9060,1.9080,1.9100,1.9120,1.9140,  
   &1.9160,1.9180,1.9200,1.9220,1.9240,1.9260,1.9280,1.9300,  
   &1.9320,1.9340,1.9360,1.9380,1.9400,1.9420,1.9440,1.9453,  
   &1.9465,1.9478,1.9490,1.9503,1.9515,1.9528,1.9540,1.9553,  
   &1.9565,1.9578,1.9590,1.9598,1.9606,1.9614,1.9622,1.9630,  
   &1.9638,1.9646,1.9654,1.9662,1.9670,

&1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.4800,1.5530,1.6080,  
 &1.6300,1.6610,1.6750,1.6855,1.6960,1.7025,1.7070,1.7155,  
 &1.7220,1.7273,1.7325,1.7378,1.7430,1.7473,1.7515,1.7557,  
 &1.7600,1.7625,1.7650,1.7675,1.7700,1.7725,1.7750,1.7775,  
 &1.7800,1.7825,1.7850,1.7875,1.7900,1.7925,1.7950,1.7975,  
 &1.8000,1.8017,1.8035,1.8052,1.8070,1.8088,1.8105,1.8123,  
 &1.8140,1.8158,1.8175,1.8193,1.8210,1.8229,1.8248,1.8267,  
 &1.8286,1.8305,1.8324,1.8343,1.8362,1.8381,1.8400,1.8400,  
 &1.8417,1.8425,1.8433,1.8442,1.8450,1.8458,1.8467,1.8475,  
 &1.8483,1.8492,1.8500,1.8510,1.8520,1.8530,1.8540,1.8550,  
 &1.8560,1.8570,1.8580,1.8590,1.8600,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.4130,1.4600,1.4830,  
 &1.5030,1.5210,1.5370,1.5485,1.5600,1.5698,1.5795,1.5893,  
 &1.5990,1.6050,1.6110,1.6170,1.6230,1.6277,1.6325,1.6372,  
 &1.6420,1.6463,1.6505,1.6547,1.6590,1.6633,1.6675,1.6718,  
 &1.6760,1.6790,1.6820,1.6850,1.6880,1.6910,1.6940,1.6970,  
 &1.7000,1.7026,1.7052,1.7077,1.7103,1.7129,1.7155,1.7181,  
 &1.7207,1.7233,1.7258,1.7284,1.7310,1.7326,1.7342,1.7358,  
 &1.7374,1.7390,1.7406,1.7422,1.7438,1.7454,1.7470,1.7486,  
 &1.7490,1.7500,1.7510,1.7520,1.7530,1.7540,1.7550,1.7560,  
 &1.7570,1.7580,1.7590,1.7598,1.7606,1.7614,1.7622,1.7630,  
 &1.7638,1.7646,1.7654,1.7662,1.7670,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.3670,1.4000,1.4180,  
 &1.4330,1.4530,1.4660,1.4765,1.4870,1.4935,1.5000,1.5065,  
 &1.5130,1.5180,1.5230,1.5280,1.5330,1.5380,1.5430,1.5480,  
 &1.5530,1.5571,1.5612,1.5654,1.5695,1.5736,1.5778,1.5819,  
 &1.5860,1.5894,1.5927,1.5961,1.5995,1.6029,1.6062,1.6096,  
 &1.6130,1.6154,1.6178,1.6202,1.6227,1.6251,1.6275,1.6299,  
 &1.6323,1.6347,1.6372,1.6396,1.6420,1.6445,1.6470,1.6495,  
 &1.6520,1.6545,1.6570,1.6595,1.6620,1.6645,1.6670,1.6686,  
 &1.6702,1.6718,1.6733,1.6749,1.6765,1.6781,1.6797,1.6813,  
 &1.6828,1.6844,1.6860,1.6878,1.6896,1.6914,1.6932,1.6950,  
 &1.6968,1.6986,1.7004,1.7022,1.7040,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,1.3000,  
 &1.3000,1.3000,1.3000,1.3000,1.3000,1.3160,1.3310,1.3430,  
 &1.3540,1.3660,1.3720,1.3810,1.3900,1.3965,1.4030,1.4095,  
 &1.4160,1.4205,1.4250,1.4295,1.4340,1.4388,1.4435,1.4483,  
 &1.4530,1.4565,1.4600,1.4635,1.4670,1.4705,1.4740,1.4775,  
 &1.4810,1.4839,1.4868,1.4896,1.4925,1.4954,1.4983,1.5011,  
 &1.5040,1.5064,1.5088,1.5112,1.5137,1.5161,1.5185,1.5209,  
 &1.5233,1.5258,1.5282,1.5306,1.5330,1.5354,1.5378,1.5402,  
 &1.5426,1.5450,1.5474,1.5498,1.5522,1.5546,1.5570,1.5594,  
 &1.5612,1.5633,1.5653,1.5674,1.5695,1.5716,1.5737,1.5758,



&1.5778,1.5799,1.5820,1.5845,1.5870,1.5895,1.5920,1.5945,  
 &1.5970,1.5995,1.6020,1.6045,1.6070/  
 DATA ATORQ/0.,19.,47.,94.,140.,178./  
 DATA AESPED/0.,207.439,261.797,314.159,366.519,418.879/  
 DATA EFFMTR/0.,.8094,.91,.9175,.9250,.9280,.9310,.9315,.9320,  
 &.9295,.9270,.9240,.9210,.9175,.9140,.9085,.9030,.8980,  
 &.8930,.8860,.8790,.8720,.8650,.8580,.8510,.8442,.8375,  
 &.8308,.8240,.8170,.8100,.8030,.7960,.7890,.7820,.7750,  
 &.7680,.7610,.7540,.7470,.7400,.7332,.7265,.7198,.7130,  
 &.7060,.6990,.6920,.6850,.6780,.6710,.6640,.6570,.6500,  
 &.6430,.6360,.6290,.6222,.6155,.6087,.6020,.5950,.5880,  
 &.5810,.5740,.5670,.5600,.5530,.5460,.5390,.5320,.5250,  
 &.5180,.5112,.5045,.4977,.4910,.4840,.4770,.4700,.4630,  
 &  
 &0.000,.7761,.8870,.8983,.9095,.9158,.9220,.9253,.9285,  
 &.7293,.9300,.7295,.9290,.9275,.9260,.9230,.9200,.9173,  
 &.9145,.9108,.9070,.9026,.8983,.8939,.8895,.8846,.8798,  
 &.8747,.8700,.8640,.8595,.8543,.8490,.8438,.8385,.8333,  
 &.8280,.8227,.8175,.8123,.8070,.8020,.7970,.7920,.7870,  
 &.7817,.7765,.7713,.7660,.7607,.7555,.7502,.7450,.7398,  
 &.7345,.7292,.7240,.7189,.7138,.7086,.7035,.6982,.6930,  
 &.6877,.6825,.6774,.6723,.6671,.6620,.6568,.6515,.6463,  
 &.6410,.6359,.6308,.6256,.6205,.6152,.6100,.6048,.5995,  
 &  
 &0.000,.7428,.8646,.8790,.8940,.9035,.9130,.9190,.9250,  
 &.9290,.9330,.9350,.9370,.9375,.9380,.9375,.9370,.9365,  
 &.9360,.9355,.9350,.9333,.9315,.9298,.9280,.9250,.9220,  
 &.9190,.9160,.9125,.9090,.9055,.9020,.8985,.8950,.8915,  
 &.8880,.8845,.8810,.8775,.8740,.8707,.8675,.8642,.8610,  
 &.8575,.8540,.8505,.8470,.8435,.8400,.8365,.8330,.8295,  
 &.8260,.8225,.8190,.8155,.8120,.8085,.8050,.8015,.7980,  
 &.7945,.7910,.7870,.7845,.7813,.7780,.7745,.7710,.7675,  
 &.7640,.7605,.7570,.7535,.7500,.7465,.7430,.7395,.7360,  
 &  
 &0.000,.6862,.8165,.8400,.8635,.8765,.8895,.8980,.9065,  
 &.9130,.9195,.9230,.9265,.9288,.9310,.9323,.9335,.9345,  
 &.9350,.9350,.9350,.9344,.9338,.9331,.9325,.9309,.9293,  
 &.9276,.9260,.9240,.9220,.9200,.9180,.9156,.9133,.9109,  
 &.9085,.9056,.9028,.8999,.8970,.8943,.8915,.8888,.8860,  
 &.8830,.8800,.8770,.8740,.8709,.8678,.8646,.8615,.8585,  
 &.8555,.8525,.8495,.8464,.8433,.8401,.8370,.8340,.8310,  
 &.8280,.8250,.8220,.8190,.8160,.8130,.8100,.8070,.8040,  
 &.8010,.7979,.7948,.7916,.7885,.7855,.7825,.7795,.7765,  
 &  
 &0.000,.6295,.7690,.8010,.8330,.8495,.8660,.8770,.8880,  
 &.8970,.9060,.9110,.9160,.9200,.9240,.9270,.9300,.9320,  
 &.9340,.9345,.9350,.9355,.9360,.9365,.9370,.9368,.9365,  
 &.9362,.9360,.9355,.9350,.9345,.9340,.9328,.9315,.9302,  
 &.9290,.9268,.9245,.9222,.9200,.9178,.9155,.9132,.9110,  
 &.9085,.9060,.9035,.9010,.8983,.8955,.8928,.8900,.8875,

&.8850, .8825, .8800, .8773, .8745, .8718, .8690, .8665, .8640,  
 &.8615, .8590, .8563, .8535, .8508, .8480, .8455, .8430, .8405,  
 &.8380, .8353, .8325, .8298, .8270, .8245, .8220, .8195, .8170,  
 &  
 &0.000, .6275, .7690, .8010, .8330, .8495, .8660, .8755, .8850,  
 &.8920, .8990, .9035, .9080, .9115, .9150, .9180, .9210, .9225,  
 &.9240, .9255, .9270, .9280, .9290, .9300, .9310, .9310, .9310,  
 &.9310, .9310, .9310, .9310, .9310, .9310, .9305, .9300, .9295,  
 &.9290, .9282, .9275, .9267, .9260, .9247, .9235, .9222, .9210,  
 &.9197, .9185, .9173, .9160, .9148, .9135, .9122, .9110, .9095,  
 &.9080, .9065, .9050, .9035, .9020, .9005, .8990, .8975, .8960,  
 &.8945, .8930, .8917, .8905, .8892, .8880, .8865, .8850, .8835,  
 &.8820, .8805, .8790, .8775, .8760, .8745, .8730, .8715, .8700,  
 &  
 &0.000, .4946, .6520, .7055, .7590, .7845, .8100, .8245, .8390,  
 &.8530, .8670, .8745, .8820, .8890, .8960, .9010, .9060, .9095,  
 &.9130, .9160, .9190, .9210, .9230, .9250, .9270, .9280, .9290,  
 &.9300, .9310, .9315, .9320, .9325, .9330, .9332, .9335, .9338,  
 &.9340, .9343, .9345, .9347, .9350, .9347, .9345, .9342, .9340,  
 &.9332, .9325, .9317, .9310, .9302, .9295, .9287, .9280, .9267,  
 &.9255, .9242, .9230, .9217, .9205, .9192, .9180, .9162, .9145,  
 &.9127, .9110, .9090, .9070, .9050, .9030, .9010, .8990, .8970,  
 &.8950, .8927, .8905, .8882, .8860, .8835, .8810, .8785, .8760/  
 DATA APCVT/0., 2.05, 4.42, 9.32, 60., 80., 90., 100. /  
 DATA ARCVT/ .333, .667, .5, 1., 1.49, 2., 2.5 /  
 DATA EFF/0., .904, .931, .944, .945, .937, .929, .918,  
 &0., .904, .911, .923, .922, .919, .914, .905,  
 &0., .904, .917, .920, .931, .925, .921, .911,  
 &0., .904, .92, .932, .931, .925, .921, .911,  
 &0., .904, .927, .94, .939, .937, .934, .927,  
 &0., .904, .931, .944, .945, .944, .942, .939,  
 &0., .904, .933, .949, .949, .949, .949, .949 /  
 DATA GREFF/ 9, .948, .9667, .978, .9815, .9827, .9842, .9851, .9857, .9861,  
 &.9865, .9867, .9868, .9870, .9872, .9873, .9874, .9876, .9877, .9879,  
 &.9880, .9881, .9881, .9882, .9882, .9883, .9883, .9884, .9884, .9885,  
 &.9885, .9885, .9886, .9886, .9887, .9887, .9888, .9888, .9889, .9889,  
 &.9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890,  
 &.9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890,  
 &.9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890,  
 &.9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890, .9890,  
 &.9890,  
 &.9000, .9325, .9502, .9640, .9757, .9783, .9803, .9814, .9822, .9828,  
 &.9834, .9838, .9842, .9845, .9848, .9851, .9853, .9856, .9858, .9860,  
 &.9862, .9863, .9864, .9866, .9867, .9868, .9869, .9870, .9871, .9872,  
 &.9873, .9874, .9874, .9875, .9876, .9876, .9877, .9878, .9879, .9880,  
 &.9881, .9881, .9881, .9881, .9881, .9882, .9882, .9882, .9882, .9882,  
 &.9883, .9883, .9883, .9883, .9883, .9883, .9884, .9884, .9884, .9884,  
 &.9885, .9885, .9885, .9885, .9885, .9885, .9885, .9886, .9886, .9886,

&.9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886,  
 &.9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886,  
 &.9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886, .9886,  
 &.9885,  
 &.9000, .9170, .9337, .9500, .9700, .9739, .9764, .9777, .9787, .9795,  
 &.9803, .9809, .9815, .9821, .9824, .9828, .9832, .9835, .9838, .9840,  
 &.9843, .9845, .9847, .9849, .9852, .9854, .9855, .9857, .9858, .9860,  
 &.9861, .9862, .9863, .9864, .9865, .9866, .9867, .9868, .9869, .9870,  
 &.9871, .9871, .9872, .9872, .9873, .9873, .9873, .9874, .9874, .9875,  
 &.9875, .9875, .9876, .9876, .9877, .9877, .9877, .9878, .9878, .9879,  
 &.9879, .9879, .9880, .9880, .9880, .9881, .9881, .9881, .9881, .9882,  
 &.9882, .9882, .9882, .9882, .9882, .9882, .9882, .9882, .9882, .9882,  
 &.9882, .9882, .9882, .9882, .9882, .9882, .9882, .9882, .9882, .9882,  
 &.9882, .9882, .9882, .9881, .9881, .9881, .9881, .9881, .9880, .9880,  
 &.9880,  
 &.9000, .9085, .9228, .9364, .9543, .9622, .9684, .9713, .9732, .9745,  
 &.9757, .9766, .9774, .9782, .9789, .9795, .9802, .9807, .9812, .9817,  
 &.9821, .9824, .9827, .9830, .9833, .9836, .9838, .9840, .9841, .9843,  
 &.9845, .9846, .9848, .9849, .9851, .9852, .9853, .9854, .9855, .9856,  
 &.9857, .9858, .9858, .9859, .9860, .9860, .9861, .9862, .9862, .9863,  
 &.9864, .9864, .9865, .9865, .9866, .9867, .9867, .9868, .9868, .9869,  
 &.9870, .9870, .9870, .9871, .9871, .9872, .9872, .9873, .9873, .9874,  
 &.9874, .9874, .9874, .9875, .9875, .9875, .9875, .9875, .9876, .9876,  
 &.9876, .9876, .9876, .9876, .9876, .9876, .9876, .9876, .9876, .9876,  
 &.9877, .9877, .9877, .9877, .9877, .9877, .9877, .9877, .9877, .9877,  
 &.9877,  
 &.9000, .9000, .9120, .9227, .9386, .9504, .9604, .9649, .9677, .9694,  
 &.9711, .9722, .9733, .9744, .9753, .9762, .9771, .9779, .9786, .9793,  
 &.9800, .9804, .9807, .9811, .9814, .9818, .9820, .9822, .9825, .9827,  
 &.9829, .9831, .9833, .9835, .9837, .9839, .9840, .9841, .9841, .9842,  
 &.9843, .9844, .9845, .9846, .9847, .9848, .9848, .9849, .9850, .9851,  
 &.9852, .9853, .9854, .9854, .9855, .9856, .9857, .9858, .9858, .9859,  
 &.9860, .9861, .9861, .9862, .9862, .9863, .9864, .9864, .9865, .9865,  
 &.9866, .9866, .9867, .9867, .9868, .9868, .9868, .9869, .9869, .9870,  
 &.9870, .9870, .9870, .9870, .9870, .9871, .9871, .9871, .9871, .9871,  
 &.9871, .9871, .9871, .9872, .9872, .9872, .9872, .9872, .9873, .9873,  
 &.9873,  
 &.9000, .9000, .9060, .9169, .9313, .9423, .9525, .9579, .9615, .9639,  
 &.9662, .9677, .9691, .9705, .9716, .9727, .9738, .9748, .9756, .9764,  
 &.9771, .9776, .9780, .9784, .9788, .9793, .9796, .9798, .9801, .9804,  
 &.9807, .9809, .9812, .9814, .9817, .9819, .9821, .9823, .9825, .9826,  
 &.9828, .9829, .9831, .9832, .9833, .9834, .9836, .9837, .9838, .9839,  
 &.9841, .9842, .9843, .9844, .9845, .9846, .9847, .9848, .9849, .9850,  
 &.9851, .9852, .9853, .9853, .9854, .9855, .9855, .9856, .9857, .9857,  
 &.9858, .9858, .9859, .9859, .9860, .9860, .9860, .9861, .9861, .9862,  
 &.9862, .9862, .9863, .9863, .9864, .9864, .9864, .9865, .9865, .9866,  
 &.9866, .9866, .9866, .9866, .9866, .9867, .9867, .9867, .9867, .9867,  
 &.9867,  
 &.9000, .9000, .9000, .9110, .9240, .9342, .9445, .9508, .9554, .9584,  
 &.9614, .9631, .9649, .9666, .9679, .9692, .9705, .9716, .9725, .9734,

&.9743,.9748,.9753,.9758,.9763,.9768,.9771,.9774,.9777,.9781,  
 &.9784,.9787,.9790,.9793,.9797,.9800,.9802,.9805,.9808,.9810,  
 &.9813,.9815,.9816,.9818,.9819,.9821,.9823,.9824,.9826,.9827,  
 &.9829,.9830,.9832,.9833,.9835,.9836,.9837,.9839,.9840,.9842,  
 &.9843,.9844,.9844,.9845,.9846,.9847,.9847,.9848,.9849,.9849,  
 &.9850,.9850,.9851,.9851,.9852,.9852,.9852,.9853,.9853,.9854,  
 &.9854,.9855,.9855,.9856,.9857,.9857,.9858,.9859,.9860,.9860,  
 &.9861,.9861,.9861,.9861,.9861,.9861,.9861,.9861,.9861,  
 &.9861,  
 &.9000,.9000,.9000,.9000,.9133,.9225,.9330,.9404,.9461,.9503,  
 &.9545,.9569,.9594,.9617,.9634,.9651,.9668,.9681,.9692,.9703,  
 &.9714,.9720,.9727,.9733,.9739,.9745,.9750,.9755,.9759,.9764,  
 &.9768,.9772,.9775,.9779,.9782,.9786,.9789,.9791,.9794,.9797,  
 &.9800,.9801,.9803,.9804,.9806,.9807,.9808,.9810,.9811,.9813,  
 &.9814,.9815,.9816,.9817,.9818,.9820,.9821,.9822,.9823,.9824,  
 &.9825,.9826,.9827,.9828,.9829,.9831,.9832,.9833,.9834,.9835,  
 &.9836,.9837,.9837,.9838,.9837,.9839,.9840,.9841,.9842,.9842,  
 &.9843,.9844,.9844,.9845,.9846,.9847,.9847,.9848,.9849,.9849,  
 &.9850,.9850,.9851,.9851,.9852,.9852,.9852,.9853,.9853,.9854,  
 &.9854,  
 &.9000,.9000,.9000,.9000,.9000,.9094,.9216,.9314,.9385,.9425,  
 &.9464,.9492,.9519,.9546,.9563,.9581,.9599,.9616,.9632,.9648,  
 &.9664,.9674,.9683,.9693,.9703,.9712,.9719,.9725,.9731,.9737,  
 &.9743,.9747,.9751,.9755,.9760,.9764,.9767,.9770,.9773,.9776,  
 &.9779,.9781,.9784,.9786,.9789,.9791,.9793,.9796,.9798,.9801,  
 &.9803,.9805,.9806,.9807,.9809,.9811,.9812,.9814,.9815,.9817,  
 &.9818,.9819,.9820,.9821,.9822,.9823,.9825,.9826,.9827,.9828,  
 &.9829,.9829,.9830,.9830,.9831,.9832,.9832,.9833,.9833,.9833,  
 &.9834,.9835,.9835,.9836,.9836,.9837,.9837,.9837,.9838,.9839,  
 &.9839,.9839,.9840,.9840,.9841,.9841,.9841,.9842,.9842,.9843,  
 &.9843,  
 &.9000,.9000,.9000,.9000,.9000,.9000,.9107,.9207,.9284,.9339,  
 &.9375,.9429,.9462,.9494,.9517,.9539,.9561,.9581,.9598,.9616,  
 &.9633,.9643,.9652,.9662,.9672,.9681,.9688,.9694,.9701,.9707,  
 &.9714,.9719,.9724,.9729,.9734,.9739,.9742,.9746,.9750,.9753,  
 &.9757,.9760,.9762,.9765,.9768,.9771,.9773,.9776,.9779,.9781,  
 &.9784,.9786,.9788,.9789,.9791,.9793,.9795,.9797,.9798,.9800,  
 &.9802,.9803,.9805,.9806,.9808,.9809,.9810,.9812,.9813,.9815,  
 &.9816,.9817,.9818,.9819,.9820,.9821,.9821,.9822,.9823,.9824,  
 &.9825,.9825,.9826,.9826,.9827,.9827,.9828,.9828,.9829,  
 &.9829,.9830,.9830,.9831,.9832,.9833,.9833,.9834,.9835,.9835,  
 &.9836,  
 &.9000,.9000,.9000,.9000,.9000,.9000,.9072,.9150,.9210,  
 &.9271,.9314,.9356,.9397,.9427,.9457,.9487,.9512,.9533,.9554,  
 &.9575,.9589,.9603,.9617,.9631,.9645,.9653,.9662,.9670,.9678,  
 &.9686,.9692,.9697,.9703,.9708,.9714,.9717,.9721,.9725,.9728,  
 &.9732,.9735,.9738,.9741,.9744,.9746,.9749,.9752,.9755,.9758,  
 &.9761,.9763,.9766,.9769,.9771,.9773,.9776,.9779,.9781,.9783,  
 &.9786,.9787,.9789,.9790,.9792,.9793,.9794,.9796,.9797,.9799,  
 &.9800,.9801,.9802,.9803,.9804,.9806,.9807,.9808,.9809,.9810,

.9811, .9812, .9813, .9814, .9815, .9816, .9817, .9818, .9819, .9820,  
.9821, .9822, .9823, .9824, .9825,  
.9825/

DATA HEMAP/0., 0., 0., 0., 0., 0.,  
80., 9.714E-04, 1.371E-03, 2.171E-03, 3.15E-03, 3.943E-03,  
60., 1.2E-03, 1.714E-03, 2.686E-03, 3.966E-03, 5.038E-03,  
80., 1.486E-03, 2.057E-03, 3.267E-03, 4.871E-03, 6.16E-03,  
60., 1.714E-03, 2.366E-03, 3.911E-03, 5.829E-03, 7.275E-03,  
80., 1.929E-03, 2.686E-03, 4.714E-03, 6.857E-03, 8.873E-03/

DATA VCHG/2.180, 2.154, 2.134, 2.121, 2.114, 2.104,  
82.098, 2.088, 2.079, 2.069, 2.057, 2.045, 2.030,  
82.188, 2.171, 2.156, 2.144, 2.134, 2.128,  
82.118, 2.109, 2.099, 2.089, 2.079, 2.067, 2.054,  
82.256, 2.225, 2.204, 2.189, 2.179, 2.171,  
82.160, 2.152, 2.142, 2.132, 2.122, 2.112, 2.101,  
82.324, 2.279, 2.251, 2.234, 2.224, 2.214,  
82.202, 2.194, 2.185, 2.175, 2.165, 2.158, 2.148,  
82.421, 2.365, 2.323, 2.295, 2.276, 2.260,  
82.246, 2.236, 2.226, 2.217, 2.209, 2.205, 2.198,  
82.519, 2.452, 2.394, 2.356, 2.327, 2.306,  
82.290, 2.278, 2.267, 2.259, 2.254, 2.251, 2.247,  
82.617, 2.539, 2.466, 2.416, 2.379, 2.352,  
82.335, 2.320, 2.308, 2.301, 2.293, 2.297, 2.297,  
82.715, 2.626, 2.538, 2.477, 2.431, 2.397,  
82.379, 2.362, 2.349, 2.343, 2.343, 2.344, 2.346,  
82.788, 2.719, 2.645, 2.582, 2.525, 2.480,  
82.450, 2.429, 2.415, 2.409, 2.407, 2.408, 2.411,  
82.861, 2.812, 2.753, 2.688, 2.619, 2.563,  
82.522, 2.496, 2.482, 2.474, 2.471, 2.472, 2.475,  
82.910, 2.873, 2.823, 2.762, 2.697, 2.643,  
82.599, 2.567, 2.544, 2.526, 2.517, 2.512, 2.515,  
82.959, 2.934, 2.892, 2.837, 2.775, 2.722,  
82.676, 2.638, 2.605, 2.578, 2.563, 2.553, 2.554/

END  
END

## REFERENCES

1. Norrup, L. V. and A. T. Lintz, Advanced Propulsion Systems for Hybrid Vehicles, AiResearch Manufacturing Co. of California, Report No. AiResearch 79-16430 (DOE/NASA/0091-80/1, NASA CR-159771), January 1980.
2. Bhate, S., H. Chen and G. Dochat, Advanced Propulsion System Concept for Hybrid Vehicles, Mechanical Technology, Inc., Report No. MTI 80TR25 (DOE/NASA/0092-80/1, NASA CR-159772), December 1980.
3. Bozek, J. M., An Averaging Battery Model for a Lead-Acid Battery Operating in an Electric Car, NASA Lewis Research Center, Report No. DOE/NASA/1044-79/5, NASA TM-79321, December 1979.
4. Schwartz, H. J. and A. L. Gordan, Impact of Propulsion System R&D on Electric Vehicle Performance and Cost, NASA Lewis Research Center, Report No. DOE/NASA/1044-9, NASA TM-81548, May 1980.
5. Raynard, A. E. and F. E. Forbes, Advanced Electric Propulsion System Concept for Electric Vehicles, AiResearch Manufacturing Co. of California, Report No. AiResearch 79-16182 (DOE/NASA/0081-79/1, NASA CR-159651), August 1979.
6. Fletcher, R., "A New Approach to Variable Metric Algorithms", Computer Journal, Vol. 13, 1970, pp 317-322.
7. Fletcher, R., "An Ideal Penalty Function for Constrained Optimization, Journal of the Institute of Mathematical Applications", Vol. 15, 1975, 319-342.

8. Abadie, J. and J. Carpentier, "Generalization of the Wolfe Reduced Gradient Method to the Case of Nonlinear Constraints", in Optimization, R. Fletcher, Editor, Academic Press, New York, 1969, pp 37-47.
9. Powell, M. J. D., "A New Algorithm for Unconstrained Optimization", in Nonlinear Programming, O. L. Mangasarian and K. Ritter, Editors, Academic Press, New York, 1970.
10. Lasdon, L. S., Waren, A. D., Jain, A. and M. Ratner, "Design and Testing of a Generalized Reduced Gradient Code for Nonlinear Programming", ACM Transactions on Mathematical Science, Vol. 4, No. 1, March 1978, pp 34-50.
11. Schittkowski, K., Nonlinear Programming Codes - Information, Tests, Performance, Internal Report, Institute for Angewandte Mathematik und Statistik, Universitat Wurzburg, AmHubland, D-87, Wurzburg, West Germany, 1980.
12. Sarma, P.V.L.M. and G. V. Reklaitis, "Optimization of a Complex Chemical Process Using an Equation Oriented Model", presented at 10th International Symposium on Mathematical Programming, Montreal, Aug. 1979.
13. Lasdon, L., Waren, A.D. and M. W. Ratner, GRG User's Guide, Department of Computer and Information Science, Cleveland State University, Cleveland, Ohio, October 1978.

1. Report No. NASA CR-168292		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle  Optimization Methods Applied to Hybrid Vehicle Design				5. Report Date June 1983	
				6. Performing Organization Code 778-36-06	
7. Author(s)  John F. Donoghue and James H. Burghart				8. Performing Organization Report No.	
				10. Work Unit No.	
9. Performing Organization Name and Address Department of Electrical Engineering Cleveland State University Cleveland, Ohio				11. Contract or Grant No. NAG 3-84	
				13. Type of Report and Period Covered Contractor Report	
12. Sponsoring Agency Name and Address U.S. Department of Energy Office of Vehicle and Engine R&D Washington, D.C. 20545				14. Sponsoring Agency Code Report No. DOE/NASA/0084-1	
15. Supplementary Notes Final report. Prepared under Interagency Agreement DE-AI01-77CS51044. Project Manager, Raymond F. Beach, Space Power Technology Division, NASA Lewis Research Center, Cleveland, Ohio 44135.					
16. Abstract  This work demonstrates the use of optimization methods as an effective design tool in the design of hybrid vehicle propulsion systems. Optimization techniques were used to select values for three design parameters (battery weight, heat engine power rating and power split between the two on-board energy sources) such that various measures of vehicle performance (acquisition cost, life cycle cost and petroleum consumption) were optimized. The approach produced designs which were often significant improvements over hybrid designs already reported on in the literature. The principal conclusions are as follows. First, it was found that the strategy used to split the required power between the two on-board energy sources can have a significant effect on life cycle cost and petroleum consumption. Second, the optimization program should be constructed so that performance measures and design variables can be easily changed. Third, the vehicle simulation program has a significant effect on the computer run time of the overall optimization program; run time can be significantly reduced by proper design of the types of trips the vehicle takes in a one year period. Fourth, care must be taken in designing the cost and constraint expressions which are used in the optimization so that they are relatively smooth functions of the design variables. Fifth, proper handling of constraints on battery weight and heat engine rating, variables which must be large enough to meet power demands, is particularly important for the success of an optimization study. Finally, the principal conclusion is that optimization methods provide a practical tool for carrying out the design of a hybrid vehicle propulsion systems.					
17. Key Words (Suggested by Author(s)) Optimization Hybrid vehicles Electric vehicles			18. Distribution Statement Unclassified - unlimited STAR Category 85 DOE Category UC-96		
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of pages 180	22. Price* A09





