



---

# Acoustic Measurements of a Full-Scale, Coaxial, Hingeless Rotor Helicopter

---

Randall L. Peterson and Marianne Mosher

---

(NASA-TM-84349) ACOUSTIC MEASUREMENTS OF A  
FULL-SCALE COAXIAL HINGELESS ROTOR  
HELICOPTER (NASA) 127 P HC A07/MF A01

N83-28986

CSC 20A

G3/71

Unclas  
28075

---

# Acoustic Measurements of a Full-Scale, Coaxial, Hingeless Rotor Helicopter

---

Randall L. Peterson  
Marianne Mosher, Ames Research Center, Moffett Field, California



National Aeronautics and  
Space Administration

Ames Research Center  
Moffett Field, California 94035

# TABLE OF CONTENTS

## Page

SYMBOLS . . . . .	111
SUMMARY . . . . .	1
INTRODUCTION . . . . .	1
EXPERIMENT . . . . .	2
DATA ACQUISITION AND REDUCTION . . . . .	2
RESULTS AND DISCUSSION . . . . .	3
CONCLUDING REMARKS . . . . .	5
APPENDIX A . . . . .	6
APPENDIX B . . . . .	22
APPENDIX C . . . . .	42
REFERENCES . . . . .	70
TABLES . . . . .	71
FIGURES . . . . .	73

## SYMBOLS

A	coefficient in background noise curve fit
B	coefficient in background noise curve fit
$C_{LR/\sigma,R}$	isolated rotor lift coefficient, $CLR/S,R, L/\rho(\Omega R)^2S$
$C_{P/\sigma}$	rotor power coefficient, $CP/S, P/\rho(\Omega R)^3S$
c	speed of sound, m/sec
$\bar{c}$	blade chord at 75% radius, m
dB	sound pressure level, $20 \log(P_{rms}/P_{ref})$
dB <sub>B</sub>	background sound pressure level, $20 \log(P_{rms}/P_{ref})$
dBAC	A-weighted dB corrected for background noise
dB <sub>AU</sub>	A-weighted dB not corrected for background noise
DBC	sound pressure level corrected for background noise
DBU	sound pressure level not corrected for background noise
J THRUST	total thrust of J60 auxiliary propulsion engine, N
L	isolated rotor lift, N
M	wind tunnel Mach number, $V/c$
$M_{at}$	advancing tip Mach number, $MAT, (1 + \mu)M_{tip}$
$M_{tip}$	rotor rotational Mach number, $MTIP, \Omega R/c$
N	total number of blades
P	rotor power, W
P <sub>MAX</sub>	maximum pressure in time history sample, $N/m^2$
P <sub>MIN</sub>	minimum pressure in time history sample, $N/m^2$
P <sub>N</sub> dB <sub>C</sub>	perceived noise level corrected for background noise
P <sub>N</sub> dB <sub>U</sub>	perceived noise level not corrected for background noise
$P_{ref}$	reference pressure ( $0.00002 N/m^2$ )
$P_{rms}$	root-mean-square sound pressure, $N/m^2$
R	rotor radius, m

RPM rotor rotational speed, rev/min  
 r distance to microphone from midway between rotor hubs, m  
 S reference area,  $S = N\bar{c}R$ , m<sup>2</sup>  
 V wind tunnel speed, knots or m/sec  
 x distance upstream from rotor center, m  
 y distance left from rotor center looking upstream, m  
 z distance up from midway between hubs, m  
 %RPM J1 auxiliary engine rotational speed expressed as percent of nominal value.  
 RPM J1/16,000  
 %RPM J2 auxiliary engine rotational speed expressed as percent of nominal value.  
 RPM J2/16,000  
 $\alpha$  angle of attack of rotor shaft, ALPHA, deg  
 $\Delta\theta$  upper rotor blade collective pitch minus lower rotor blade collective  
 pitch, deg  
 $\mu$  rotor advance ratio,  $\mu$ ,  $V/\Omega R$   
 $\rho$  air density, kg/m<sup>3</sup>  
 $\sigma$  solidity,  $S/\pi R^2$   
 $\theta$  rotor blade collective pitch, deg  
 $\phi$  angle below rotor plane,  $\tan^{-1}(-z/r)$ , deg  
 $\psi$  azimuth angle from downstream,  $\tan^{-1}(-y/-x)$ , deg  
 $\Omega$  rotor rotational speed, rad/sec

## SUMMARY

Acoustic data were obtained during a full-scale test of the XH-59A Advancing Blade Concept Technology Demonstrator in the 40- by 80-Foot Wind Tunnel. The XH-59A is a research helicopter with two coaxial rotors and hingeless blades. Performance, vibration, and noise at various forward speeds, rotor lift coefficients and rotor shaft angles of attack were investigated. The noise data were acquired over an isolated rotor lift coefficient range of 0.024 to 0.162, an advance ratio range of 0.23 to 0.45 corresponding to tunnel wind speeds of 89 to 160 knots, and angles of attack from 0° to 10°. Acoustic data are presented for seven microphone locations for all run conditions where the model noise is above the background noise. Model test configuration and performance information are also listed. Acoustic waveforms, dBA, and 1/3-octave spectra as functions of operating condition for selected data points and microphones are presented. In general, the noise level is shown to increase with rotor lift coefficient except under certain operating conditions where significant impulsive blade/vortex interactions increase noise levels. The impulsivity appears to depend upon how the lift is distributed between the two rotors.

## INTRODUCTION

In the design and development of new helicopters, noise, as well as performance, handling qualities, and stability and control must be considered. This report describes the acoustic results from a recent full-scale test of an advanced technology rotorcraft. Under U.S. Army sponsorship, Sikorsky Aircraft built two XH-59A Advancing Blade Concept Technology Demonstrator helicopters that utilize two counter-rotating coaxial hingeless rotors to improve high-speed performance and increase cruise efficiency. On a conventional helicopter in forward flight, the rotor blades operate at a low lift coefficient on the advancing side because the rotor must produce no roll moment in level flight. The use of two counter-rotating rigid rotors allows each individual rotor to have a high lift coefficient on the advancing side while the aircraft has no total roll moment. The full-scale XH-59A Advancing Blade Concept (ABC) aircraft tested in the Ames 40- by 80-Foot Wind Tunnel is shown in figure 1. For additional information pertaining to the ABC concept, see references 1 through 3.

The ABC aircraft is significantly different from a conventional helicopter; therefore, one would expect the noise produced by this aircraft to differ from noise produced by a conventional helicopter. This aircraft has a slow rotational tip speed ( $M_{tip} = 0.52$  to  $0.58$ ) which may reduce the overall noise since all sources and convective amplification increase with increasing Mach number. Also, the high speed impulsive noise may be less than that of a conventional helicopter at a given forward speed because of the slower tip speed. However, high speed noise will still become a problem because this aircraft is designed to fly at faster speeds than a conventional rotorcraft. Also, under certain flight conditions, one would expect some impulsive blade slap due to the interaction of tip vortices from the upper rotor with the lower rotor.

This report presents the noise data of a full-scale ABC aircraft as measured in the Ames 40- by 80-Foot Wind Tunnel. Noise data were measured over an advance ratio range of 0.23 to 0.45 (89 knots to 160 knots) with the rotor on and from 60 to 180 knots with the rotor off. The rotor-on testing was conducted over an angle of attack range of  $0^\circ$  to  $10^\circ$ , and the auxiliary propulsion engines were operated at flight idle for all noise data runs.

## EXPERIMENT

The ABC aircraft (shown installed in the Ames 40- by 80-Foot Wind Tunnel in fig. 1) has two rotors, each containing three 5.5 m radius blades. General specifications for the ABC rotor system are listed in table 1. The midpoint between these two rotors was 1.5 m above the tunnel centerline. Viewed from above, the upper rotor of the model rotates in the counter-clockwise direction, and the lower rotor rotates in the clockwise direction. Collective, lateral cyclic, and longitudinal cyclic for each rotor were independently operated by six rotor controls, thereby allowing the rotors to independently apply trim forces and moments to the aircraft. The rotors were powered by two 552,000 W PT6T-3 turboshaft engines. Auxiliary propulsive force is provided by two nacelle-mounted J60-P3A turbojet engines which produce 13,300 N of thrust each. For a more detailed description of the aircraft, see Felker (ref. 3).

Performance, loads, and noise data for the full-scale ABC aircraft were measured in the Ames 40- by 80-Foot Wind Tunnel. Table 2 shows the flight conditions where data were taken. During testing, the rotor speed was adjusted to give the desired tip Mach number,  $M_{tip}$ , then the tunnel speed was adjusted to obtain the desired advance ratio,  $\mu$ . Noise data were then acquired for a matrix of isolated rotor lift coefficients,  $C_{LR/G,R}$ , and shaft angles,  $\alpha$ . The rotor-on testing was conducted over an isolated rotor lift coefficient range of 0.024 to 0.162 and an angle of attack range of  $0^\circ$  to  $10^\circ$ . The auxiliary propulsion engines were operated at flight idle for all noise data runs. For this test, the background wind tunnel noise was recorded at 60, 90, 120, and 180 knots with the model installed in the wind tunnel, the rotor blades off, the rotor head rotating, and the auxiliary engines operating at flight idle. A more detailed description of the test can be found in reference 3.

## DATA ACQUISITION AND REDUCTION

The acoustic data for this test were acquired using seven 1.3-cm condenser microphones equipped with nose cones to reduce wind-induced noise. Four of these microphones were located upstream of the model, and three microphones were located near the model. Three of the seven microphones were flush mounted on plates near the floor while the remaining four were mounted on stands at various heights below the midpoint between the two rotors. The microphone locations are given in table 3 and shown in figure 2; the coordinate system used is also shown. Signal conditioners were used to control the gain of the acoustic signal and to power the microphones. The acoustic signals were recorded on tape using a 14-track frequency-modulated (FM) tape recorder running at 15 ips. This gave a bandwidth of 10 kHz. All microphones were calibrated at the start and end of each day using a 124-dB, 250 Hz signal from a pistonphone. At each data point, a 50-sec sample of acoustic data was recorded for later analysis. In order to assure a maximum signal-to-noise ratio, the gain of the acoustic signal was adjusted in 10-dB intervals. A schematic of the data acquisition system is shown in figure 3.

Initially, the acoustic data were reduced and analyzed off-line on a minicomputer time series data system. Figure 4 shows a flow chart of the equipment used for data reduction. Data are digitized at a sample rate of 20 kHz while being played back through a low pass filter with a cutoff frequency of 10 kHz to prevent aliasing. From the digitized data, the minicomputer generated 1/3-octave spectra from 1-Hz spectra in the range of 10 to 200 Hz, and from 10-Hz spectra in the range of 250 Hz to 10 kHz. The minicomputer also computed dB, dBA, and PNdB from the 1/3-octave spectra and the first 10 blade passage harmonics from the 1-Hz, narrow-band spectra. The computed acoustic data were then transferred into a computer containing the data base with all of the measured test parameters. Background noise corrections, obtained with all the propulsion systems operating but rotor blades removed, were applied to the 1/3-octave spectra in the following manner. Background noise measurements were fitted to a linear regression of the form

$$dBB = A + B * \log(V)$$

and then subtracted from the measured spectra on a power basis for each 1/3-octave,

$$dBC = 10 \log[10^{dB/10} - 10^{dBB/10}]$$

Graphs and tables were then constructed from this data base. The background noise levels used for corrections on microphones 1 through 7 are tabulated in appendix A. Appendix A also contains 1/3-octave plots of the averaged background noise measurements used at 89, 106, 142, and 160 knots, and plots of dBA as a function of velocity for each microphone. The effect of these corrections is to remove the jet noise as well as the background noise from the noise data.

## RESULTS AND DISCUSSION

Acoustic data for the XH-59A model are presented in appendix B. Performance and global acoustic measurements are listed for all of the microphones. The data are for rotor-on configurations at forward speeds of 89, 106, 142, and 160 knots and angles of attack from 0° to 10°.

Figures 5 through 10 show the general trends in the acoustic data with airspeed and shaft angle. Data from microphones 2, 4, and 7 are shown as a function of isolated rotor lift coefficient,  $C_{LR}/\sigma R$ . Figures 5, 6, and 7 display the corrected dBA as a function of isolated rotor lift coefficient for tunnel wind speeds of 89, 106, and 142 knots, respectively. Data are grouped by shaft angle of attack (2.5°, 5.0°, and 7.5°) for each curve on each figure. Figures 8, 9, and 10 show the corrected dBA as a function of isolated rotor lift coefficient for angles of attack of 2.5°, 5.0°, and 7.5°, respectively. Data are grouped by tunnel wind speed (89, 106, and 142 knots) for each curve on each plot. In general, these figures (5 to 10) show an increase in noise level with increasing rotor lift coefficient. There are some exceptions to these trends and it is believed that this is due to impulsive blade/vortex interaction noise.

Blade/vortex interactions appear to depend on the control settings. Noise levels for a number of points in figure 10 are listed in table 4 with some control settings. Data are shown for shaft angle of attack of 7.5° and wind velocities of 89 and 106 knots. For each wind velocity, the data are listed in increasing order of rotor lift coefficient. The collective pitch,  $\theta$ , and the differential collective pitch,  $\Delta\theta$ , are included in the table. In the data at 106 knots, the noise levels



appear to depend on  $\Delta\theta$  as well as the rotor lift coefficient. Noise levels are higher for negative values of  $\Delta\theta$  than for positive values of  $\Delta\theta$  for some data with nearly identical rotor lift coefficients. Other data does not show this trend so no definitive conclusions can be made. Dependence of blade/vortex interaction upon lift distribution is a reasonable hypothesis; lift distribution effects the strength and location of the shed tip vortex and therefore would be expected to directly affect the blade/vortex interactions and impulsive noise.

Detailed acoustic data for selected data points are presented in appendix C. These data are for various wind speeds and angles of attack from microphones 2, 4, and 7. The tabulated data in appendix C shows 1/3-octave spectra, 1/3-octave spectra corrected for background noise, and the first 10 blade passage harmonic sound levels (dB).

Figures 11 through 17 show corrected 1/3-octave spectra as functions of isolated rotor lift coefficient. Each figure is for a specific tunnel wind speed, shaft angle of attack, and microphone. Data for microphones 2, 4, and 7 are shown for tunnel wind speeds of 89, 106, and 142 knots and for angles of attack of 2.5°, 5.0°, and 7.5°. Except for the frequency range 50 to 1600 Hz, the 1/3-octave spectra for all data are nearly the same. In this mid-frequency range, the sound pressure levels vary from point to point. The mid-frequency sound pressure levels follow the same trend seen in the dBA in figures 5 through 7. At 89 knots the mid-frequency noise levels increase as the rotor lift coefficient increases, and at the other wind tunnel speeds the noise levels are more sporadic. The curves also show that the energy in the high frequency range has been removed due to background noise corrections. This is because the noise of the auxiliary propulsive engines was included in the background noise measurements.

Figures 18 through 26 show typical time histories from the above 1/3-octave curves. Averaged time histories were obtained from the recorded microphone signals. A 1-per-revolution trigger signal was utilized to synchronize the microphone data, allowing constructive averaging of the coherent signal and destructive averaging of the random signal. Time histories are shown for data from microphone 4 located under the rotor. Each figure contains several time history plots for several isolated rotor lift coefficients at a fixed velocity and shaft angle. Velocities of 89, 106, and 142 knots and shaft angles of 2.5°, 5.0°, and 7.5° are used for the plots. The periodicity of the noise signals is very evident in these figures; all show a complicated time history with much high frequency harmonic noise. Some of the figures contain impulses from blade vortex interaction noise.

The time histories (figs. 18 to 20) for data taken at 89 knots show only a small amount of impulsive noise. The most impulsive data are for  $\alpha = 2.5^\circ$  and  $C_{LR/\sigma,R} = 0.150$  which are also the data points with the highest noise level in figure 5b.

The time histories (figs. 21 to 23) for data taken at 106 knots show a mixture of impulsive and nonimpulsive noise. Some data are nonimpulsive and have low noise levels in figure 6b. Those points are identified with the following settings:  $\alpha = 5.0^\circ$  and  $C_{LR/\sigma,R} = 0.114$ ;  $\alpha = 7.5^\circ$  and  $C_{LR/\sigma,R} = 0.067, 0.116, \text{ and } 0.131$ . Some data are impulsive and have high noise levels in figure 6b. Those points can be identified with the following settings:  $\alpha = 7.5^\circ$  and  $C_{LR/\sigma,R} = 0.093 \text{ and } 0.106$ . The other time histories shown for 106 knots have moderate impulsive character and low to moderate noise levels in figure 6b.

The time histories (figs. 24 to 26) for some of the data taken at 142 knots show very little impulsive character except for the two points (fig. 24a  $\alpha = 7.5^\circ$ ,  $CLR/\sigma_R = 0.079$ ; and fig. 26a  $\alpha = 7.5^\circ$ ,  $CLR/\sigma_R = 0.090$ ) with slight impulsivity. The corresponding data in figure 7b have moderate noise levels with the two points mentioned above having higher noise levels than average.

In general, the time histories with a distinct impulsive nature correspond to data with high overall noise levels. The presence of this impulsive noise is not a simple function of the basic parameters of forward speed, isolated rotor lift coefficient, and angle of attack.

#### CONCLUDING REMARKS

Acoustic measurements of the XH-59A ABC Technology Demonstrator helicopter were obtained from a full-scale test in the NASA Ames 40- by 80-Foot Wind Tunnel. General noise measurements at all microphone locations and specific detailed noise measurements for three representative microphones are presented. From analysis of these test results, the following conclusions may be drawn:

1. Under certain operating conditions the rotor experienced significant blade/vortex interactions. How the lift was distributed between the upper and lower rotor may have a large influence on the impulsivity of the noise. Unfortunately, accurate measurements of all the control settings are not available; therefore, the effect of the controls on the noise cannot be quantified.
2. When impulses are not present, the noise level increases as the lift coefficient increases and as the angle of attack approaches  $0^\circ$  as in a typical rotor.

## APPENDIX A

The following tables and dB and dBA plots (figs. A1-A14) present the XH-59A ABC background noise data. The background noise data are presented in terms of 1/3-octave center frequencies, 1/3-octave spectra, and as a function of tunnel velocity (knots) for microphones 1 through 7.

Background noise data in terms of 1/3-octave center frequencies are presented first in tabular form for each microphone. One-third-octave spectra are presented next for tunnel wind speeds of 89, 106, 142, and 160 knots for each microphone. Lastly, the background noise at each microphone is presented as a function of tunnel velocity (knots).

### SYMBOLS

A	coefficient in background noise curve fit
B	coefficient in background noise curve fit
DB	background sound pressure level
MIC	microphone number
PT	point number
RUN	run number
V	wind tunnel speed, knots

BACKGROUND NOISE CURVE FIT  
 $DB = A + B * LOG(V)$

1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 1		MICROPHONE 2	
	A	B	A	B
10.0	16.74	32.34	39.98	19.34
12.5	27.28	26.22	40.98	18.35
16.0	58.27	13.54	47.45	17.93
20.0	46.27	21.93	35.32	25.68
25.0	17.94	33.74	-5.07	45.03
31.5	35.66	26.29	16.98	35.00
40.0	31.71	30.46	31.48	30.93
50.0	-13.01	54.52	-3.53	48.14
63.0	38.19	28.96	32.27	30.95
80.0	-6.15	51.57	22.68	37.04
100.0	20.82	38.85	29.44	34.46
125.0	42.34	28.04	54.97	21.90
160.0	38.35	30.09	45.81	26.05
200.0	26.07	25.99	22.48	37.65
250.0	22.61	36.67	18.00	38.94
315.0	27.19	29.24	36.37	29.41
400.0	54.74	20.75	53.39	21.30
500.0	56.28	19.83	54.10	20.79
630.0	46.41	24.32	44.04	25.31
800.0	59.51	18.66	55.22	20.28
1000.0	67.62	15.48	64.45	16.19
1250.0	40.30	29.07	59.25	19.15
1600.0	66.15	16.36	71.80	13.31
2000.0	48.29	22.59	50.19	21.40
2500.0	68.55	13.96	71.54	12.05
3150.0	74.70	12.13	82.59	8.16
4000.0	64.35	14.30	67.23	13.55
5000.0	112.09	-5.91	97.33	-0.33
6300.0	73.74	12.19	96.00	1.93
8000.0	103.33	-1.65	100.23	-1.45

ORIGINAL PAGE IS  
 OF POOR QUALITY

BACKGROUND NOISE CURVE FIT  
 $DE = A + B * \text{LOG}(V)$

ORIGINAL PAGE IS  
 OF POOR QUALITY

1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 3		MICROPHONE 4	
	A	B	A	B
10.0	23.46	30.15	21.66	30.59
12.5	27.06	26.65	23.53	28.19
16.0	49.89	17.66	47.40	19.50
20.0	47.60	22.37	37.80	26.83
25.0	-0.49	43.22	-20.95	54.16
31.5	26.30	30.93	1.30	43.54
40.0	42.71	25.93	32.10	30.27
50.0	-2.98	48.71	0.53	46.65
63.0	34.13	30.52	32.98	31.20
80.0	22.37	37.27	24.69	37.55
100.0	37.08	31.51	27.72	35.58
125.0	51.12	23.98	40.55	29.63
160.0	43.16	27.87	36.53	31.15
200.0	23.49	37.49	24.93	36.62
250.0	24.04	36.06	24.26	36.12
315.0	27.94	28.83	39.55	28.45
400.0	56.23	19.84	58.74	19.17
500.0	54.88	20.37	60.64	18.29
630.0	47.55	23.62	46.75	23.55
800.0	59.18	18.50	7.63	19.31
1000.0	68.50	14.41	16.54	16.08
1250.0	52.22	22.37	23.26	36.92
1600.0	72.53	12.61	75.58	12.37
2000.0	58.24	17.69	49.64	22.30
2500.0	74.21	11.24	58.52	18.37
3150.0	51.17	4.78	86.07	6.95
4000.0	74.87	10.56	73.05	11.47
5000.0	100.76	-1.28	74.34	10.52
6300.0	104.92	-1.60	87.04	6.58
8000.0	105.99	-2.57	92.89	2.43

ORIGINAL PAGE IS  
OF POOR QUALITY

BACKGROUND NOISE CURVE FIT  
DB = A + B \* LOG(V)

4

1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 5		MICROPHONE 6	
	A	B	A	B
10.0	21.90	31.60	29.58	31.53
12.5	25.62	29.62	29.99	30.59
16.0	28.07	30.56	21.46	37.31
20.0	35.90	28.58	24.58	37.35
25.0	13.76	38.82	0.54	49.19
31.5	32.13	30.93	24.14	38.90
40.0	29.13	34.05	15.72	44.04
50.0	0.80	48.41	14.78	44.49
63.0	39.68	29.40	13.99	45.00
80.0	30.66	35.12	18.99	43.36
100.0	46.97	27.51	24.45	40.68
125.0	46.91	27.92	28.55	38.73
160.0	44.90	29.38	23.09	41.29
200.0	28.74	37.27	20.33	42.74
250.0	32.66	35.00	21.71	41.55
315.0	40.75	31.47	28.72	38.56
400.0	47.01	28.43	39.13	33.31
500.0	45.85	29.07	37.31	34.02
630.0	37.39	33.12	30.60	37.15
800.0	38.18	32.78	36.16	34.36
1000.0	40.75	31.61	40.48	32.35
1250.0	43.21	30.36	40.85	32.05
1600.0	50.50	26.85	46.27	29.49
2000.0	25.83	37.12	18.17	41.53
2500.0	48.76	26.04	44.93	28.88
3150.0	67.33	17.74	50.46	25.63
4000.0	62.86	17.66	50.08	24.43
5000.0	95.88	0.95	88.90	6.70
6300.0	98.47	1.80	62.68	18.36
8000.0	202.22	-0.53	46.13	7.27

BACKGROUND NOISE CURVE FIT  
 $DB = A + B * LOG(V)$

ORIGINAL PAGE IS  
 OF POOR QUALITY

1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 7	
	A	B
10.0	20.17	39.15
12.5	3.65	41.44
16.0	27.26	32.3
20.0	23.97	36.16
25.0	6.65	44.40
31.5	11.56	43.21
40.0	25.68	37.91
50.0	17.90	41.92
63.0	20.12	41.27
80.0	14.13	44.55
100.0	15.93	43.89
125.0	21.14	41.31
160.0	21.82	40.94
200.0	18.73	42.73
250.0	21.49	41.00
315.0	36.20	34.43
400.0	38.42	33.13
500.0	43.14	30.93
630.0	21.72	36.32
800.0	22.00	35.99
1000.0	40.07	32.31
1250.0	30.62	36.30
1600.0	33.39	34.90
2000.0	11.53	44.08
2500.0	20.60	39.17
3150.0	39.11	30.10
4000.0	37.42	29.89
5000.0	49.73	23.67
6300.0	57.14	20.00
8000.0	57.75	19.10

GEOPHONIC LEVELS  
OF POOR QUALITY




Figure A1.- Background 1/3-octave spectrum for microphone 1.



ORIGINAL PAGE IS  
OF POOR QUALITY




Figure A2.- Background 1/3-octave spectrum for microphone 2.

ORIGINAL RECORDS  
OF FOUR QUALITY




Figure A3.- Background 1/3-octave spectrum for microphone 3.

ORIGINAL PAGE IS  
OF POOR QUALITY




Figure A4.- Background 1/3-octave spectrum for microphone 4.

ORIGINAL PAGE IS  
OF POOR QUALITY




Figure A5.- Background 1/3-octave spectrum for microphone 5.

ORIGINAL PAGE IS  
OF POOR QUALITY




Figure A6.- Background 1/3-octave spectrum for microphone 6.

ORIGINAL PAGE IS  
OF POOR QUALITY




Figure A7.- Background 1/3-octave spectrum for microphone 7.




Figure A8.- A-weighted background sound pressure level for microphone 1.




Figure A9.- A-weighted background sound pressure level for microphone 2.




Figure A10.- A-weighted background sound pressure level for microphone 3.




Figure A11.- A-weighted background sound pressure level for microphone 4.



ORIGINAL PAGE IS  
OF POOR QUALITY




Figure A12.- A-weighted background sound pressure level for microphone 5.




Figure A13.- A-weighted background sound pressure level for microphone 6.




Figure A14.- A-weighted background sound pressure level for microphone 7.

APPENDIX B

The following tables present acoustic and performance data for the XH-59A ABC model. Acoustic data are presented for microphones 1 through 7. The run/point number sequence used is based on tunnel velocity (knots), shaft angle of attack (ALPHA), and isolated rotor lift coefficient (CLR/S,R). The run/point numbers are ordered in terms of increasing isolated rotor lift coefficient at each tunnel velocity and shaft angle of attack.

SYMBOLS

ALPHA	model pitch, positive up, deg
CLR/S,R	isolated rotor lift coefficient
CP/S	rotor power coefficient
DBAC	dBA corrected for background noise
DBAU	dBA not corrected for background noise
DBC	dB corrected for background noise
DBU	dB not corrected for background noise
J THRUST	total auxiliary engine thrust, N
MAT	advancing tip Mach number
MTIP	rotor tip Mach number
MTUN	tunnel Mach number
MU	advance ratio
PMAX	maximum pressure in time history sample, $N/m^2$
PMIN	minimum pressure in time history sample, $N/m^2$
PNDBC	PNdB corrected for background noise
PNDBU	PNdB not corrected for background noise
PT	point number
RPM	rotor rotational speed, rev/min
RUN	run number
VELOCITY	tunnel velocity, knots
VTIP	rotor tip velocity, m/sec

%RPM J1 auxiliary engine rotational speed expressed as percent of nominal value,  
RPM J1/16,000

%RPM J2 auxiliary engine rotational speed expressed as percent of nominal value,  
RPM J2/16,000

Acoustic data are presented in the following order:

RUN/PT	VELOCITY	ALPHA	CLR/S,R
21/16	90.2	10.0	0.068
21/17	91.1	10.0	.080
29/7	88.7	10.0	.108
21/11	89.8	7.5	.074
21/12	90.0	7.5	.074
21/13	90.0	7.5	.090
29/6	88.4	7.5	.099
21/14	90.1	7.5	.119
29/10	87.9	7.5	.124
21/15	90.0	7.5	.141
29/11	88.4	7.5	.162
21/7	89.4	5.0	.072
21/18	90.1	5.0	.074
21/8	90.0	5.0	.093
29/5	88.6	5.0	.093
30/7	88.2	5.0	.104
29/9	88.1	5.0	.116
21/9	89.8	5.0	.121
30/6	88.0	5.0	.128
29/8	88.2	5.0	.133
21/10	89.9	5.0	.134
28/6	88.3	2.5	.082
28/7	88.6	2.5	.109
28/8	88.8	2.5	.150
21/6	89.3	0.0	.026
25/6	106.2	7.5	.067
23/12	106.8	7.5	.093
25/7	104.7	7.5	.106
25/5	105.3	7.5	.107
25/8	104.8	7.5	.116
23/14	107.0	7.5	.117
23/13	107.0	7.5	.131
25/9	104.3	7.5	.138
21/19	108.5	5.0	.069
23/9	105.6	5.0	.114
23/10	106.1	5.0	.135
23/11	106.4	5.0	.145
23/15	107.8	2.5	.085
23/7	105.0	0.0	.025
23/8	105.8	0.0	.083
24/9	142.4	7.5	.090
24/6	140.9	5.0	.079
24/7	140.9	5.0	.113
24/8	141.2	5.0	.125
23/16	143.0	2.5	.079

ORIGINAL PAGE IS  
OF POOR QUALITY

RUN/PT	VELOCITY	ALPHA	CLR/S,R
23/18	143.2	2.5	0.093
23/17	143.0	2.5	.110
30/8	141.9	2.5	.110
30/9	142.1	2.5	.113
24/12	160.6	2.5	.085
24/11	160.6	2.5	.085

ORIGINAL PAGE IS  
OF POOR QUALITY

XH-50A ACOUSTIC DATA

RUN PT	MIC	VELOCITY MTUN		CLK/S.P CP/S	ALPHA MU	PPM MAT		VTIP MTIP	J THRUST	XRPM J1 XPPM J2	PMAK
		FBAC	DBAC			DBU	DEC				
21	16	50.2	0.1210	0.068552	10.0	0.2424	23.1	0.5405	004.3	45.2	42.0
	1	110.4		100.3	118.2		117.7	124.0	118.6	-59.4	43.8
	2	110.1		107.7	117.8		117.2	124.6	118.7	-37.7	42.9
	3	110.8		108.2	119.0		118.5	125.8	119.0	-53.2	43.7
	4	110.7		108.4	118.5		118.3	125.0	119.2	-40.1	52.3
	5	114.5		111.0	121.7		120.8	127.9	121.0	-66.0	84.5
	6	114.8		111.1	121.6		120.2	127.7	120.3	-75.5	66.1
	7	116.0		114.2	122.4		121.6	128.4	122.8	-111.5	72.2
21	17	91.1	0.1223	0.080190	10.0	0.2266	360.2	206.9	945.3	45.2	42.5
	1	113.4		112.3	121.1		120.8	126.7	122.6	-70.7	85.4
	2	112.4		111.1	121.1		120.9	126.6	122.7	-58.7	66.0
	3	112.5		111.1	120.2		119.8	126.3	121.7	-65.9	54.6
	4	113.4		112.2	122.5		122.7	128.0	124.2	-72.9	88.8
	5	116.2		114.1	122.6		121.8	129.5	124.1	-69.4	81.6
	6	116.8		114.6	124.5		124.2	130.0	125.2	-95.5	70.6
	7	117.5		116.3	123.0		122.3	129.5	125.9	-71.5	80.0
29	7	88.7	0.1211	0.108137	10.0	0.2485	210.2	183.4	875.4	43.7	43.7
	1	111.4		105.2	112.2		117.8	126.1	120.6	-454.1	58.0
	2	110.7		108.5	115.8		119.5	125.0	119.8	-481.4	50.8
	3	112.1		105.2	116.4		118.8	127.5	122.3	-465.0	51.5
	4	111.7		105.8	120.5		120.1	126.7	120.9	-50.0	62.0
	5	115.3		112.5	122.9		122.3	128.8	123.2	-79.5	88.3
	6	114.8		110.9	122.1		120.9	128.3	121.5	-86.5	75.9
	7	116.0		114.2	124.4		124.0	129.1	126.0	-494.1	97.7

ORIGINAL PAGE IS  
OF POOR QUALITY

XH-59A ACOUSTIC DATA

VELOCITY		CLS/S.F.	ALPHA	RPM	VTIP	J THRUST	TKPM J1	PMAX
MTUN		CP/S	MU	MAT	MTIP	J THRUST	TKPM J2	
LBAU		DBAC	DPU	DPC	PDRUC	FRDRC	PMIN	
PUN 21	89.8	0.073677	7.5	323.7	186.0	977.3	48.7	
PT 11	0.1206	0.000804	0.2485	0.6564	0.5257		42.9	
MIC 1	111.7	110.1	120.0	119.6	125.6	121.2	-58.2	47.0
MIC 2	100.9	107.4	117.7	117.2	123.9	118.4	-47.0	34.6
MIC 3	111.1	106.8	118.0	117.3	126.1	119.3	-55.5	47.0
MIC 4	111.2	109.3	119.4	118.9	125.1	120.3	-67.0	71.9
MIC 5	114.9	112.1	121.5	120.5	128.1	121.6	-69.4	78.9
MIC 6	114.8	111.0	121.9	120.5	128.2	121.5	-65.0	68.8
MIC 7	115.3	113.2	122.5	121.8	128.1	123.3	-87.4	88.3
RUN 21	90.0	0.073647	7.5	323.8	186.0	967.0	48.7	
PT 12	0.1209	0.000871	0.2490	0.6568	0.5259		42.8	
MIC 1	111.6	109.9	120.2	119.8	125.8	121.4	-46.2	64.8
MIC 2	110.1	107.8	118.2	117.7	123.9	119.0	-46.0	37.7
MIC 3	121.0	108.5	116.0	117.3	125.9	119.6	-56.0	44.9
MIC 4	111.1	109.0	119.6	119.1	125.2	120.1	-75.3	73.4
MIC 5	114.7	111.3	121.4	120.4	128.1	121.5	-60.6	72.8
MIC 6	114.6	110.5	122.3	121.0	128.1	120.6	-73.5	74.6
MIC 7	115.4	113.2	123.4	121.6	128.4	123.4	-55.6	74.2
FUN 21	90.0	0.089785	7.5	323.8	186.0	977.0	48.8	
PT 13	0.1209	0.001027	0.2489	0.6568	0.5259		42.0	
MIC 1	112.1	110.5	120.8	120.4	126.1	121.0	-60.8	61.5
MIC 2	111.1	106.4	119.9	118.5	125.3	121.3	-55.4	44.8
MIC 3	110.5	109.1	118.5	117.0	124.7	118.9	-59.7	42.8
MIC 4	112.1	110.4	120.7	120.4	126.4	122.1	-87.7	71.4
MIC 5	114.7	111.4	121.0	121.1	128.5	121.2	-78.0	73.5
MIC 6	115.6	112.6	122.9	121.6	128.9	122.9	-87.0	62.2
MIC 7	115.1	112.9	123.9	122.3	128.2	123.8	-80.0	79.2

XN-59A ACOUSTIC DATA

	VELOCITY FT/SEC	CLK/S.P CP/S	ALPHA DU	KFM MAT	VTIP HTIP	J THRUST	ZRPM J1 ZRPM J2	PMAX
	DCAU	DIAC	PPU	DEC	PI:DBU	PNDPC	PPIN	
RUN 29 PT 6	88.4 0.1107	0.005471 0.004665	7.5 0.2490	318.0 0.6557	132.7 0.5246	885.4	43.9 43.6	
MIC 1	110.6	108.1	117.3	116.5	125.0	118.7	-450.9	37.0
MIC 2	110.4	106.2	119.7	116.3	124.5	110.7	-464.1	51.1
MIC 3	110.8	107.3	118.1	117.4	125.7	118.8	-455.0	43.2
MIC 4	111.2	109.0	118.6	116.4	126.2	121.0	-50.2	40.8
MIC 5	115.3	112.1	122.3	122.1	129.7	123.6	-70.6	73.7
MIC 6	114.8	111.0	121.4	119.9	128.1	121.8	-67.2	86.5
MIC 7	115.7	113.8	125.2	124.8	128.9	125.2	-88.3	102.6
RUN 21 PT 14	50.1 0.1303	0.118578 0.002092	7.5 0.2499	322.7 0.6545	185.4 0.5236	967.1	48.7 42.8	
MIC 1	111.5	109.6	120.8	120.5	125.6	120.6	-59.7	67.2
MIC 2	111.5	109.0	120.1	119.8	125.4	120.9	-56.6	58.0
MIC 3	111.5	109.5	120.2	119.8	125.7	120.2	-66.4	51.6
MIC 4	112.8	111.5	123.1	122.9	127.5	123.6	-70.0	93.0
MIC 5	115.4	112.8	125.4	122.8	129.2	123.5	-77.8	87.3
MIC 6	115.9	113.1	124.0	123.2	129.6	123.6	-82.8	80.8
MIC 7	116.4	114.9	125.4	125.0	129.0	125.9	-104.0	100.5
RUN 29 PT 10	87.6 0.1305	0.123751 0.004230	7.5 0.2480	217.4 0.6569	182.4 0.5264	1115.3	50.1 43.0	
MIC 1	111.8	110.1	119.3	118.0	125.8	121.5	-458.5	60.2
MIC 2	111.5	109.8	121.4	121.1	126.2	121.6	-63.8	48.7
MIC 3	112.0	109.5	119.6	119.1	127.2	122.1	-65.7	63.3
MIC 4	112.3	110.9	121.2	120.9	126.1	122.2	-62.0	64.3
MIC 5	115.9	113.5	123.6	123.0	130.1	124.7	-92.0	80.0
MIC 6	115.5	112.6	122.6	121.5	129.4	124.1	-70.6	55.4
MIC 7	116.6	115.1	126.5	126.2	129.8	127.0	-143.0	122.1

ORIGINAL PAGE IS  
OF POOR QUALITY



XH-59A ACOUSTIC DATA

	VFLOCITY MTUN	CLP/S.R CP/S	ALPHA MU	FPM MAT	VTIP MTIP	J THRUST	ZRPM J1 ZPPM J2	PMAX
	DBAU	CBAC	DBU	DBL	PMDBU	PNPBC	PMIN	
FUN 21	98.0	0.140575	7.5	323.7	196.0	977.1	48.7	
PT 15	0.1204	0.003825	0.2400	0.6561	0.5253		42.8	
MIC 1	112.5	111.2	121.4	121.1	126.7	122.8	-82.8	62.7
MIC 2	113.9	110.5	121.6	121.7	126.2	122.0	-70.8	64.4
MIC 3	113.6	112.4	122.6	122.4	128.0	124.6	-87.7	73.6
MIC 4	112.7	112.0	124.0	123.8	127.0	124.1	-62.1	106.9
MIC 5	115.3	113.4	124.3	123.8	129.9	124.4	-86.6	119.6
MIC 6	116.1	113.5	124.3	123.6	129.6	124.6	-128.9	101.1
MIC 7	117.8	116.7	126.8	126.5	131.4	128.6	-120.8	125.8

ORIGINAL PAGE IS  
OF POOR QUALITY

8	FUN 29	95.4	0.161634	7.5	315.7	181.4	50.0	
	PT 11	0.1710	0.005362	0.2507	0.6536	0.5226	64.2	
MIC 1	115.2	114.4	123.8	123.6	120.0	126.2	-80.2	97.2
MIC 2	114.2	113.3	123.0	122.8	127.8	124.5	-66.6	68.7
MIC 3	114.7	113.4	124.2	124.0	129.4	126.3	-106.1	95.7
MIC 4	116.3	115.7	125.5	125.4	130.0	127.6	-113.4	156.1
MIC 5	119.0	117.9	126.0	125.7	132.2	129.0	-118.7	124.6
MIC 6	118.3	116.8	125.4	124.9	131.8	128.2	-118.3	120.8
MIC 7	120.3	119.8	130.5	130.4	133.8	131.9	-147.9	170.3
FUN 21	89.4	0.071956	5.0	319.8	183.7	1017.8	47.5	
PT 7	0.1209	0.001602	0.2504	0.6525	0.5227		43.1	
MIC 1	110.5	109.1	118.7	118.2	124.9	119.5	-46.9	52.2
MIC 2	110.0	107.8	119.0	118.6	124.5	120.2	-47.2	42.5
MIC 3	110.2	108.0	118.3	117.7	124.5	119.1	-43.6	53.4
MIC 4	110.3	107.9	119.5	119.0	124.6	119.4	-52.3	55.2
MIC 5	114.5	111.4	121.3	120.3	128.1	121.8	-58.0	59.8
MIC 6	114.6	110.5	122.2	121.0	128.8	121.7	-67.6	56.1
MIC 7	114.6	112.1	122.7	122.0	127.8	122.4	-71.9	68.8

CRITICAL POINTS  
OF POOR QUALITY

24-SEA ACOUSTIC DATA

	VELOCITY M/TUP	CL - /S.F C/P/S	ALPHA MU	FRM MAT	VTIP MTIP	J THRUST PNDRAC	ZPPM JJ ZOPM JJ	PMAX
	MPAU	DBAC	GRU	DBC	PHURU	PNDRAC	P.MIN	PMAX
FUR 21 PT 15	90.1 5.1394	0.074942 0.001672	5.0 0.2497	323.0 0.6550	185.6 0.5241	959.6	48.6 42.7	
MIC 1	110.6	109.4	119.6	116.1	124.3	118.8	-45.3	50.0
MIC 2	110.2	109.1	119.2	118.5	124.2	119.2	-47.6	54.7
MIC 3	110.2	107.1	117.6	116.0	125.2	117.6	-48.5	44.7
MIC 4	110.5	107.9	119.0	118.5	125.0	110.2	-44.0	62.6
MIC 5	114.4	110.7	121.1	120.1	128.2	120.8	-61.5	58.1
MIC 6	114.7	110.8	121.7	120.2	128.4	121.4	-78.4	68.6
MIC 7	115.4	113.4	122.8	122.1	128.2	122.5	-104.1	79.5
PUR 21 PT 9	90.0 0.1214	0.092162 0.002323	5.0 0.2511	320.5 0.6550	184.4 0.5235	1020.3	47.3 42.9	
MIC 1	111.5	109.6	120.1	115.8	125.7	121.1	-57.6	56.0
MIC 2	111.0	109.4	120.5	120.2	125.4	121.0	-463.3	56.0
MIC 3	110.6	107.9	118.0	118.3	125.5	119.2	-42.6	52.5
MIC 4	111.2	109.4	122.0	121.8	125.9	121.7	-53.7	90.9
MIC 5	115.2	112.3	122.4	121.7	128.8	123.1	-67.0	83.1
MIC 6	115.6	112.8	124.1	123.3	129.1	123.2	-124.6	70.4
MIC 7	115.8	114.0	124.7	124.2	129.3	124.6	-105.3	111.9
FUR 23 PT 5	88.6 0.1211	0.052200 0.004822	5.0 0.2497	317.1 0.6500	182.5 0.5240	872.0	43.6 43.5	
MIC 1	112.2	110.7	119.0	110.5	125.8	121.5	-468.2	64.2
MIC 2	112.4	111.3	121.1	120.8	126.0	122.1	-475.0	54.7
MIC 3	112.5	110.5	119.1	118.6	126.5	121.8	-75.1	50.2
MIC 4	112.4	110.9	119.7	119.2	126.1	122.2	-465.6	60.2
MIC 5	116.4	114.2	123.4	123.0	129.6	124.9	-110.0	103.8
MIC 6	116.2	113.6	121.0	120.5	129.2	123.9	-476.2	63.2
MIC 7	117.0	115.7	125.7	125.3	130.0	126.8	-84.5	93.1

YH-50A ACOUSTIC DATA

	VFLUCLTY BTUN	CLP/S,P CP/S	ALPH* MU	KAP KAT	VTIP MTIP	J THRUST	XPPM J1 XPPM J2	PMAZ
	DBAU	DBAC	DBU	DBL	PNDPU	PND3C	PMIN	
FUN 30 PT 7	80.2 0.1312	0.103501 0.004512	5.0 0.2501	215.7 0.6557	181.6 0.5245	1246.7	50.4 47.2	
MIC 1	112.8	111.4	120.2	119.9	127.1	122.2	-471.3	57.7
MIC 2	112.7	111.5	121.5	121.3	127.2	123.2	-471.0	48.4
MIC 3	112.7	110.6	119.3	118.7	127.8	123.0	-45.7	53.1
MIC 4	112.9	111.6	121.2	120.9	126.5	122.7	-470.4	43.1
MIC 5	116.3	114.1	123.1	122.5	130.1	125.1	-101.0	85.3
MIC 6	117.0	115.1	123.6	122.8	131.6	127.8	-496.1	64.1
MIC 7	118.1	117.1	126.6	126.3	130.7	128.4	-525.2	133.0
FUN 29 PT 5	88.1 0.1308	0.115752 0.004681	5.0 0.2490	316.7 0.6560	182.0 0.5252	1102.5	49.8 43.9	
MIC 1	112.5	111.1	120.5	120.2	126.2	122.3	-51.1	61.1
MIC 2	112.5	111.2	121.9	121.7	126.7	122.7	-48.7	57.3
MIC 3	112.7	110.7	120.0	119.5	127.8	123.2	-466.4	58.9
MIC 4	113.1	111.6	122.3	122.0	127.2	123.7	-76.6	87.4
MIC 5	116.9	115.1	126.0	123.5	130.6	126.6	-494.2	85.8
MIC 6	116.2	113.6	124.4	123.7	129.9	125.5	-93.1	94.0
MIC 7	117.0	115.8	126.7	126.4	130.1	127.2	-95.2	140.0
FUN 21 PT 9	80.8 0.1311	0.120763 0.003662	5.0 0.2507	320.7 0.6548	184.2 0.5227	956.8	47.9 42.8	
MIC 1	112.9	111.6	122.5	122.3	127.1	123.7	-56.5	80.7
MIC 2	112.9	111.8	121.9	121.7	126.8	122.9	-62.7	76.3
MIC 3	113.5	112.4	123.0	122.8	127.7	123.7	-72.2	92.1
MIC 4	113.2	112.0	124.3	124.2	127.6	123.9	-82.1	109.8
MIC 5	116.4	114.4	123.9	123.4	130.1	125.4	-83.2	55.8
MIC 6	117.2	115.3	126.3	125.9	130.5	126.1	-214.0	117.7
MIC 7	116.7	115.2	126.5	126.3	130.0	126.4	-147.8	120.8

ORIGINAL PAGE IS  
OF POOR QUALITY

XH-59A ACOUSTIC DATA

VELOCITY FT/UN		CLR/S.R CP/S	ALPHA MU	RPM MAT	VTIP MTIP	J TIPUST	ZRPM J1 ZRPM J2	P4MAX
DEAU	DBAC	DBU	D9C	P4DBU	P4DEC			
RUN 30 PT 5	88.0 0.1311	0.127927 0.004719	5.0 0.2500	314.0 0.6548	180.4 0.5227	1244.2	50.2 47.3	
MIC 1	113.8	112.8	122.2	122.0	127.5	124.1	-470.7	83.6
MIC 2	113.3	112.2	122.0	121.8	127.3	124.1	-466.6	72.8
MIC 3	113.6	112.1	122.0	121.7	129.2	125.5	-480.6	63.2
MIC 4	114.1	113.2	124.0	123.9	128.4	125.1	-477.0	139.0
MIC 5	117.4	115.9	124.5	124.0	130.5	126.2	-513.3	80.2
MIC 6	117.6	116.1	124.6	124.0	131.0	127.4	-534.5	84.3
MIC 7	117.6	116.5	127.7	127.4	131.0	128.4	-577.2	129.0
RUN 29 PT 8	86.2 0.1312	0.132203 0.005012	5.0 0.2504	315.5 0.6549	181.3 0.5237	1109.5	49.7 43.9	
MIC 1	115.5	114.8	123.1	122.9	128.7	125.9	-61.1	82.7
MIC 2	115.2	114.6	123.4	123.3	128.6	125.4	-479.9	83.5
MIC 3	114.7	113.6	122.5	122.2	128.7	125.3	-70.6	87.3
MIC 4	115.3	114.6	124.5	124.4	128.9	125.9	-82.3	138.4
MIC 5	119.2	118.2	126.2	125.9	132.4	129.2	-522.1	117.4
MIC 6	114.2	118.1	126.4	126.0	132.7	129.5	-270.9	104.0
MIC 7	118.9	118.1	127.6	127.4	131.5	128.9	-529.7	119.5
RUN 21 PT 10	89.9 0.1308	0.138755 0.007045	5.0 0.2498	322.2 0.6546	185.1 0.5238	954.7	48.4 47.6	
MIC 1	115.8	115.2	124.3	124.2	129.4	126.5	-101.2	99.5
MIC 2	115.9	115.4	124.6	124.5	129.7	127.3	-66.7	107.8
MIC 3	115.6	114.9	123.9	123.7	129.7	126.8	-85.8	94.4
MIC 4	115.0	114.1	125.2	125.1	129.0	125.9	-84.2	99.1
MIC 5	118.4	117.2	126.0	125.6	131.7	128.6	-113.5	128.0
MIC 6	119.8	118.8	128.4	128.1	133.0	130.1	-351.2	110.2
MIC 7	118.9	118.1	127.2	127.1	132.2	129.7	-93.8	147.0

OF FOUR QUALITY

XH-59A ACOUSTIC DATA

RUN	PT	VELOCITY MTUN	CLR/S,F CP/S	ALPHA MIJ	RPM MAT	VTIP MTIP	J THRUST	XRPM J1 XRPM J2	PMAX
		DBAU	DBAC	LDU	DBC	PNDRU	PNDBC	PMIN	
28	6	88.3	0.031592	2.5	316.6	191.0	982.8	48.8	
		0.1711	0.002004	0.2406	0.6561	0.5251		42.0	
MIC	1	112.2	117.0	121.1	120.8	126.8	122.9	-402.2	95.0
MIC	2	112.2	111.0	120.6	120.3	126.0	122.3	-472.7	58.9
MIC	3	111.5	108.9	119.7	118.0	126.1	122.2	-478.0	54.2
MIC	4	112.0	110.5	122.6	122.2	126.6	123.0	-467.8	87.1
MIC	5	116.8	114.9	123.9	123.4	124.9	125.4	-522.1	76.8
MIC	6	117.7	116.1	126.8	124.1	131.2	126.3	-563.1	91.8
MIC	7	115.7	114.0	124.6	124.2	128.6	123.0	-523.1	110.3

ORIGINAL PAGE IS  
OF POOR QUALITY

32

28	7	83.5	0.109912	2.5	315.7	181.4	976.1	48.8	
		0.1213	0.004381	0.2516	0.6534	0.5229		42.6	
MIC	1	115.5	114.7	123.2	123.0	129.7	125.3	-496.1	91.5
MIC	2	114.6	114.0	122.5	122.3	127.0	125.0	-488.2	103.6
MIC	3	113.0	112.5	122.0	121.7	128.4	124.9	-480.5	79.4
MIC	4	113.3	112.3	122.5	123.4	127.2	124.0	-470.1	127.6
MIC	5	118.1	116.7	125.1	124.7	131.1	127.4	-512.8	102.9
MIC	6	118.4	118.4	125.7	126.3	133.1	129.7	-613.2	116.4
MIC	7	118.2	117.2	127.5	127.3	130.8	127.9	-551.5	114.6
29	3	88.8	0.149022	2.5	317.3	182.2	1020.0	50.4	
		0.1309	0.009279	0.2305	0.6538	0.5228		42.4	
MIC	1	118.4	118.1	127.1	127.0	132.1	130.2	-127.0	129.1
MIC	2	117.6	117.2	126.8	126.8	131.4	129.4	-507.6	105.7
MIC	3	117.4	116.8	125.4	125.2	131.2	129.4	-505.1	87.2
MIC	4	117.5	117.1	127.4	127.4	131.4	129.3	-576.2	124.6
MIC	5	120.0	119.2	127.5	127.3	133.2	130.9	-144.4	144.4
MIC	6	121.1	120.2	129.0	128.7	134.0	131.3	-146.0	175.0
MIC	7	122.2	122.0	131.1	131.0	136.5	135.1	-663.6	184.0

XH-59A ACOUSTIC DATA

ORIGINAL DATA IS  
OF POOR QUALITY

	VELOCITY MTUN	CLR/S.F CF/S	ALPHA MU	PPM MST	VTIP HTIP	J THRUST	ZPPM J1 ZPPM J2	PMIN	PMAX
	DBAU	DBAC	DBU	DBC	PNDDBU	PNDPC			
FUN 21 PT 6	86.2 0.1309	0.025602 0.002247	0.0 0.2585	321.2 0.6570	184.6 0.5261	995.4	47.2 47.8		
MIC 1	100.3	105.2	116.5	115.6	123.1	116.7	-38.6	43.5	
MIC 2	100.8	107.1	116.7	115.3	124.2	118.8	-40.7	44.7	
MIC 3	100.4	106.2	116.6	115.8	123.0	116.5	-37.0	39.2	
MIC 4	110.1	107.3	118.1	117.5	124.4	118.4	-36.7	40.9	
MIC 5	114.0	110.4	119.8	118.4	127.0	119.9	-67.7	40.0	
MIC 6	114.4	110.0	120.2	118.1	127.8	119.8	-61.5	55.9	
MIC 7	114.7	112.2	121.2	120.2	127.5	122.4	-61.5	43.2	
FUN 25 PT 5	106.2 0.1581	0.066537 0.000632	7.5 0.2017	315.1 0.6820	181.0 0.5230	1017.3	49.9 43.5		
MIC 1	111.5	105.2	120.2	119.6	125.3	110.8	-58.7	52.5	
MIC 2	111.7	105.8	120.1	115.6	125.5	120.2	-47.5	63.6	
MIC 3	111.7	105.8	119.8	119.2	125.2	110.6	-55.6	57.0	
MIC 4	111.5	105.2	120.8	120.2	125.0	119.9	-64.6	59.8	
MIC 5	116.4	112.2	126.5	124.2	129.6	122.8	-84.8	92.8	
MIC 6	116.5	111.7	126.5	122.1	120.1	122.0	-129.1	90.7	
MIC 7	117.2	114.6	124.5	123.5	129.9	124.6	-123.7	134.6	
FUN 23 PT 12	106.8 0.1570	0.093217 0.001055	7.5 0.3002	318.6 0.6830	183.0 0.5230	001.4	47.7 43.4		
MIC 1	115.6	115.0	126.5	126.3	120.4	127.4	-113.0	106.1	
MIC 2	118.4	115.0	126.1	125.0	131.5	120.2	-62.1	107.8	
MIC 3	117.3	117.2	124.4	124.2	130.7	127.0	-50.1	107.1	
MIC 4	117.2	116.6	126.8	124.6	130.0	126.9	-134.2	50.2	
MIC 5	120.5	119.2	122.1	127.7	133.8	130.1	-175.4	168.2	
MIC 6	120.7	116.4	120.8	120.4	134.2	130.2	-277.5	170.8	
MIC 7	120.6	119.4	125.2	127.8	132.2	120.6	-112.4	206.2	

XH-50A ACOUSTIC DATA

	VELOCITY WTUN	CLP/S.F CF/S	ALPHA MU	RPM MAT	V TIP P TIP	J THRUST	TRPM J1 TRPM J2	P MAX
	DBAU	DEAC	DRU	DPC	PLCDBU	PHDRC	P MIN	
FUN 25	104.7	0.105915	7.5	313.0	179.8	1959.4	40.7	
PT 7	0.1558	0.0002266	0.2994	0.6757	0.5195		44.7	
MIC 1	115.8	115.0	125.2	125.1	129.6	126.5	-83.4	96.4
MIC 2	117.4	117.0	125.6	125.4	130.6	128.2	-111.6	100.0
MIC 3	117.0	116.4	124.7	124.5	130.1	126.6	-106.6	108.6
MIC 4	116.5	115.8	125.4	125.3	130.2	127.1	-116.5	111.6
MIC 5	118.5	117.3	127.5	127.2	132.2	128.2	-121.4	119.4
MIC 6	110.4	117.7	128.4	127.9	132.9	128.9	-163.5	143.0
MIC 7	110.8	118.6	128.4	128.3	132.3	128.0	-158.8	212.8
FUN 25	105.2	0.107211	7.5	315.0	181.0	1930.8	49.9	
PT 5	0.1570	0.001613	0.2994	0.6812	0.5242		43.4	
MIC 1	116.2	115.5	126.4	126.3	130.3	127.1	-106.0	123.7
MIC 2	117.2	116.7	125.8	125.7	130.9	128.3	-141.5	93.8
MIC 3	115.9	115.1	124.2	124.1	129.5	126.0	-85.4	103.9
MIC 4	115.6	114.8	124.6	124.4	129.2	126.0	-115.6	79.5
MIC 5	110.4	118.0	128.0	127.7	132.6	128.2	-155.9	158.6
MIC 6	120.5	119.1	129.7	129.3	134.1	130.2	-297.4	156.8
MIC 7	110.6	118.4	128.7	128.4	132.8	128.7	-141.5	177.4
FUN 25	104.8	0.116004	7.5	314.0	180.4	1964.5	49.0	
PT 9	0.1557	0.001886	0.2998	0.6768	0.5211		44.6	
MIC 1	114.7	113.6	124.7	124.5	128.6	124.9	-85.0	96.0
MIC 2	115.5	114.8	124.2	124.0	129.5	126.1	-73.0	84.4
MIC 3	114.9	113.9	123.6	123.4	128.6	124.7	-72.0	81.1
MIC 4	114.6	113.5	124.6	124.5	128.7	125.1	-86.4	97.7
MIC 5	118.4	116.5	127.5	127.2	131.4	127.0	-125.2	145.4
MIC 6	110.5	117.7	127.3	126.7	132.4	128.5	-101.5	108.0
MIC 7	119.5	118.2	128.8	128.5	132.4	128.2	-134.1	153.3

ORIGINAL PAGE  
OF POOR QUALITY

XH-59A ACOUSTIC DATA

ORIGINAL PAGE IS  
OF POOR QUALITY

VELOCITY		CLR/S.F	ALPHA	KPM	VTIP	J THPUS	ZPPM J1	PMAX
MTUN		CP/S	MU	NAT	MTIP	PNDR	TPPM J2	
CHAU	DEAC	DBU	DBC	PNDBU	PNDR			
MUN 23	107.0	0.117986	7.5	320.5	184.1	976.4	48.0	
PT 14	6.1567	0.004506	0.2686	0.6896	0.5247		43.7	
MIC 1	116.7	116.0	127.1	127.0	130.6	128.0	-119.9	125.5
MIC 2	118.2	117.8	127.8	127.7	132.2	129.9	-175.7	102.4
MIC 3	116.9	116.2	125.1	124.9	130.0	127.1	-55.5	115.2
MIC 4	116.3	115.6	125.9	125.7	130.0	126.0	-100.1	123.1
MIC 5	120.2	118.9	129.0	128.7	133.8	129.8	-118.1	173.2
MIC 6	121.5	120.4	131.1	130.8	135.7	131.9	-305.9	179.4
MIC 7	120.4	119.2	129.2	129.0	133.7	129.5	-127.6	187.2
MUN 23	107.0	0.131272	7.5	316.2	183.4	988.9	47.9	
PT 13	0.1572	0.007816	0.3002	0.6807	0.5235		43.2	
MIC 1	119.9	119.6	123.5	128.4	133.5	131.4	-126.1	151.1
MIC 2	115.2	118.8	127.8	127.7	132.8	130.6	-153.7	108.4
MIC 3	118.1	117.6	126.2	126.2	131.2	128.8	-67.2	112.7
MIC 4	117.9	117.4	126.9	126.9	131.8	129.3	-112.5	143.9
MIC 5	122.8	122.2	130.8	130.6	136.2	133.5	-202.8	167.9
MIC 6	124.8	124.2	133.6	133.5	138.5	136.3	-488.4	236.2
MIC 7	121.5	120.6	131.3	131.1	135.0	132.2	-173.9	215.1
MUN 25	104.3	0.137698	7.5	317.1	182.7	1052.6	50.0	
PT 9	0.1550	0.001653	0.2946	0.6813	0.5262		44.4	
MIC 1	113.7	112.4	123.7	123.5	127.5	123.2	-70.5	102.6
MIC 2	114.1	112.0	122.7	122.4	127.8	123.8	-95.1	79.8
MIC 3	114.4	113.4	124.0	123.7	125.4	124.5	-68.6	74.0
MIC 4	114.4	112.3	124.5	124.3	128.1	124.2	-73.8	142.5
MIC 5	118.0	115.0	127.1	126.7	131.7	127.1	-125.6	141.0
MIC 6	119.5	116.3	126.5	125.6	131.7	126.3	-117.2	120.3
MIC 7	119.5	118.7	129.1	128.8	133.0	128.0	-157.3	152.7



ORIGINAL PAGE IS  
OF POOR QUALITY

YH-50A ACOUSTIC DATA

	VELOCITY MTUN	CLR/S.P CF/S	ALPHA MU	FPM MAT	VTIP MTIP	J THRUST	ZRPM J1 ZRPM J2	PMIN	PMAX
	DBAU	CBAC	DPU	LRC	PND8U	PNCRC			
RUN 21	108.5	0.06927P	5.0	323.5	185.9	645.6			
PT 19	0.1576	0.001245	0.2902	0.6825	0.524C		48.6	42.0	
MIC 1	112.2	110.1	121.2	120.7	126.2	120.7	-70.2	-70.2	67.7
MIC 2	111.3	108.1	118.5	118.2	125.0	119.8	-57.0	-57.0	63.2
MIC 3	111.7	109.6	120.6	120.0	125.5	120.2	-70.8	-70.8	50.9
MIC 4	111.5	108.8	120.7	120.2	125.8	120.3	-62.5	-62.5	71.0
MIC 5	115.9	111.8	122.7	121.5	125.4	121.9	-58.6	-58.6	88.7
MIC 6	116.6	111.9	123.9	122.2	129.4	121.6	-113.8	-113.8	95.8
MIC 7	118.4	116.6	125.0	124.1	130.9	126.0	-85.1	-85.1	113.9
RUN 23	105.6	0.114256	5.0	316.6	182.1	635.7	48.5	43.2	
PT 9	0.1560	0.004235	0.2985	0.6810	0.524F				
MIC 1	113.8	112.5	123.3	123.0	127.9	123.7	-79.2	-79.2	79.2
MIC 2	113.1	111.8	122.4	122.1	127.2	123.3	-101.0	-101.0	82.7
MIC 3	113.2	111.6	121.6	121.2	128.1	123.4	-68.7	-68.7	66.6
MIC 4	113.7	112.3	122.9	122.6	127.9	123.7	-73.6	-73.6	76.1
MIC 5	117.9	115.6	126.0	125.5	131.2	125.7	-118.4	-118.4	158.2
MIC 6	117.0	115.2	127.0	126.3	132.0	126.6	-158.5	-158.5	115.9
MIC 7	118.0	115.9	127.2	126.8	131.4	126.8	-135.5	-135.5	116.0
RUN 23	106.1	0.135245	5.0	316.9	182.1	937.7	48.7	43.1	
PT 10	0.1571	0.006703	0.2998	0.6811	0.5240				
MIC 1	115.1	114.2	124.8	124.7	129.1	125.6	-93.6	-93.6	97.7
MIC 2	114.6	113.7	124.2	124.1	128.5	125.4	-100.0	-100.0	74.0
MIC 3	114.4	113.5	123.2	122.9	128.1	124.5	-68.4	-68.4	80.4
MIC 4	115.2	114.1	123.9	123.6	129.1	125.9	-40.9	-40.9	85.7
MIC 5	118.7	116.7	123.2	122.9	132.4	128.1	-112.2	-112.2	200.4
MIC 6	120.1	116.4	129.2	128.8	133.6	128.5	-149.1	-149.1	144.3
MIC 7	119.6	118.2	129.2	129.0	132.7	120.0	-148.5	-148.5	205.0

XH-30A ACOUSTIC DATA

VELOCITY MTUN		CLR/S·P CP/S	ALPHA MU	RPV MAT	VTIP MTIP	J THRUST	ZRPM J1 ZRPM J2	P MAX
DRAU		DRAC	DBU	DEC	PNJABU	PNIDBC	PMIN	
RUN 23	106.4	0.145552	5.0	317.3	182.2	986.4	47.5	
PT 11	0.1569	0.0099078	0.2002	0.6797	0.5227		43.1	
MIC 1	116.4	115.6	125.5	125.3	130.0	127.1	-95.2	86.2
MIC 2	115.8	115.1	125.2	125.1	129.0	127.1	-101.0	76.5
MIC 3	115.6	114.7	124.2	124.0	129.0	125.7	-90.7	94.7
MIC 4	116.6	116.0	127.0	126.9	130.5	127.8	-114.8	139.4
MIC 5	110.5	118.1	128.7	128.4	133.2	129.2	-123.2	146.6
MIC 6	110.4	117.4	129.8	129.4	133.2	128.7	-221.5	145.6
MIC 7	120.9	120.0	130.7	130.5	134.5	131.7	-151.4	213.7
PUN 23	107.8	0.084788	2.5	322.2	185.1	938.8	47.2	
PT 15	0.1577	0.007807	0.2005	0.6842	0.5265		42.7	
MIC 1	112.0	105.8	121.3	120.9	126.2	120.6	-68.2	64.2
MIC 2	111.6	109.5	120.0	119.5	125.8	120.4	-53.1	50.2
MIC 3	111.5	105.7	118.0	118.1	125.7	120.1	-58.7	53.9
MIC 4	112.3	110.5	121.7	121.3	126.0	121.2	-66.1	66.2
MIC 5	116.4	112.0	123.5	122.6	129.7	123.7	-73.3	85.7
MIC 6	117.4	113.8	126.0	125.0	130.4	124.6	-125.1	106.5
MIC 7	117.5	115.3	126.1	125.4	130.4	125.4	-93.6	96.7
FUN 23	105.0	0.074990	0.0	314.1	180.5	988.0	47.0	
PT 7	0.1566	0.002093	0.2992	0.6798	0.5232		43.4	
MIC 1	110.7	107.6	117.5	116.4	124.4	117.6	-40.6	48.3
MIC 2	110.7	108.1	117.5	116.6	124.8	118.2	-32.9	50.3
MIC 3	110.6	107.6	117.2	116.2	124.7	117.7	-40.9	33.1
MIC 4	111.0	108.5	118.4	117.5	124.6	118.9	-40.9	44.8
MIC 5	115.4	111.0	121.2	119.6	128.5	120.2	-60.2	61.9
MIC 6	115.8	110.4	122.1	119.5	128.5	119.4	-72.3	73.3
MIC 7	118.3	114.5	124.2	123.2	130.9	126.8	-92.3	71.6

ORIGINAL PAGE IS  
OF POOR QUALITY

XH-59A ACOUSTIC DATA

VELOCITY		CLP/S,R	ALPHA	RPM	VTIP	J THRUST	XRPM J1	P MAX
MTUN		CP/S	MU	MAT	MTIF	PNDRB	XRPM J2	
DRAU		CRAC	DRU	DHC	PNDRU	PNDRB	P MIN	
PUN 23	115.8	0.082525	0.0	314.7	180.8	988.9	47.5	
PT 8	0.1572	0.003572	0.5010	0.6705	0.5223		42.9	
MIC 1	111.5	105.1	122.7	120.3	125.6	119.1	-77.7	50.3
MIC 2	111.2	108.8	115.1	118.5	125.6	119.3	-62.3	47.5
MIC 3	111.1	108.6	119.9	119.3	125.6	119.4	-53.2	54.9
MIC 4	112.3	110.5	121.8	121.4	126.3	121.5	-85.0	92.1
MIC 5	116.2	112.6	122.0	122.0	128.8	122.0	-82.0	77.8
MIC 6	116.4	111.5	125.1	123.8	129.8	121.6	-109.0	116.3
MIC 7	118.4	116.7	126.2	125.6	131.3	126.8	-134.1	116.2
RUN 24	142.4	0.070290	7.5	316.5	183.0	774.1	51.6	
PT 9	0.2388	0.000919	0.4004	0.7302	0.5214		43.7	
MIC 1	119.8	115.3	127.8	127.6	133.2	130.9	-170.9	137.4
MIC 2	117.0	116.1	124.9	124.5	130.2	126.9	-97.8	87.6
MIC 3	117.5	116.7	124.2	125.9	130.2	127.9	-102.7	86.0
MIC 4	116.8	115.6	126.2	125.9	130.2	126.2	-88.7	126.1
MIC 5	123.5	122.1	132.2	129.7	136.5	133.4	-231.1	168.8
MIC 6	124.4	122.7	131.6	130.8	137.4	133.7	-335.7	299.9
MIC 7	121.5	119.0	127.9	126.5	133.7	128.8	-114.0	159.3
RUN 24	140.9	0.078550	5.0	313.5	180.1	770.1	50.8	
PT 6	0.2079	0.002754	0.4026	0.7244	0.5165		43.7	
MIC 1	115.0	118.3	127.7	127.5	132.2	129.3	-151.1	126.8
MIC 2	118.4	117.8	126.1	125.8	131.4	128.2	-116.0	109.9
MIC 3	117.3	116.5	125.6	125.3	130.6	127.1	-110.2	90.4
MIC 4	116.9	115.8	127.2	127.0	129.9	127.0	-110.3	93.7
MIC 5	122.7	121.1	129.6	129.1	135.4	131.7	-152.4	242.0
MIC 6	123.6	121.7	132.5	131.9	136.9	132.1	-245.8	331.9
MIC 7	121.8	119.4	129.4	128.5	134.7	130.3	-164.7	193.5

ORIGINAL PAGE IS  
OF POOR QUALITY

ORIGINAL PAGE IS  
OF POOR QUALITY

XH-593 ACOUSTIC DATA

VELOCITY PTUR:		CLR/S.S. (P/S)	ALPHA MU	KPM MAT	VTIP MTIP	J THRUST	XRPM J1 XRPM J2	PMAX
TBAU		DBAC	DBU	DRC	PNDRU	PNDRC	PMIN	
FUN 24	140.5	0.113114	5.0	320.3	184.0	765.3	50.9	
PT 7	0.2071	0.003184	0.3040	0.7329	0.5254		43.6	
MIC 1	115.3	112.7	124.8	124.4	129.4	124.7	-108.7	76.9
MIC 2	114.1	112.4	124.7	124.3	128.7	124.1	-79.8	84.8
MIC 3	114.4	112.6	124.4	124.0	129.3	125.0	-120.7	86.7
MIC 4	115.0	112.2	125.1	125.7	129.2	124.7	-94.6	121.8
MIC 5	110.0	116.1	127.1	126.1	132.5	127.8	-120.6	135.2
MIC 6	120.2	114.2	124.2	126.3	133.1	125.0	-150.0	181.5
MIC 7	121.1	118.2	128.7	127.6	133.4	128.4	-146.2	146.0
FUN 24	141.2	0.125296	5.0	319.2	183.4	774.1	50.9	
PT 3	0.2073	0.004110	0.3060	0.7308	0.5235		43.6	
MIC 1	116.0	114.7	126.1	125.8	130.1	126.4	-115.3	124.6
MIC 2	114.5	112.9	124.6	124.2	128.7	124.8	-86.4	89.5
MIC 3	114.7	112.1	124.1	123.7	128.8	125.0	-99.3	81.2
MIC 4	116.2	114.9	127.2	127.0	131.0	127.3	-107.3	118.4
MIC 5	120.5	117.3	128.1	127.3	133.5	128.6	-120.8	167.6
MIC 6	120.7	115.8	129.2	127.7	133.4	126.2	-142.0	145.4
MIC 7	120.9	118.0	128.7	127.6	133.6	128.4	-118.8	183.8
RUN 23	143.0	0.079327	2.5	320.6	184.2	599.9	47.8	
PT 16	0.2000	0.002045	0.3092	0.7325	0.5235		43.3	
MIC 1	114.3	112.1	124.2	123.7	128.7	123.8	-89.1	80.0
MIC 2	113.0	110.4	122.1	121.5	126.9	121.8	-66.0	85.8
MIC 3	112.4	109.4	122.1	121.3	126.7	120.9	-64.0	65.4
MIC 4	114.0	111.7	123.3	122.6	127.9	122.9	-91.0	69.4
MIC 5	115.8	115.6	125.4	124.0	132.2	125.9	-100.4	89.9
MIC 6	120.1	113.2	127.1	124.2	133.4	123.8	-140.8	158.5
MIC 7	120.3	115.5	127.4	126.9	132.8	126.5	-141.4	144.0

XH-59A ACOUSTIC DATA

VELOCITY		CLR/S,R	ALPHA	PPM	VTIP	J THRUST	XPPM J1	PHMAX
4TUN		CP/S	MU	MAT	MTIP	PNDRC	XPPM J2	
DEAU	CRAC	PRU	D4C	PNDPU	PMIN			
RUN 23	143.2	0.0926JR	2.5	321.2	184.5	592.7	47.8	
PT 18	0.2086	0.003449	0.3992	0.7212	0.5226		43.1	
MIC 1	114.8	112.8	123.8	173.2	128.5	123.4	-103.4	64.5
MIC 2	113.5	111.3	122.2	171.5	127.3	122.9	-71.3	91.0
MIC 3	112.6	109.7	121.3	170.4	126.8	120.8	-69.1	72.6
MIC 4	114.3	112.0	123.5	172.8	128.0	122.8	-95.0	78.0
MIC 5	115.8	115.5	125.4	173.6	132.4	125.8	-89.6	105.2
MIC 6	120.2	113.6	127.5	175.0	133.1	123.0	-173.6	143.3
MIC 7	120.4	116.5	127.9	176.4	133.0	126.6	-114.6	165.3

40

ORIGINAL PAGE IS  
OF POOR QUALITY

RUN 23	143.2	0.109872	2.5	320.8	184.2	592.7	47.6	
PT 17	0.2087	0.004461	0.3992	0.7314	0.5229		43.1	
MIC 1	115.2	113.6	124.7	174.2	129.2	124.6	-98.4	83.8
MIC 2	114.0	112.1	122.9	172.3	127.8	123.3	-62.5	63.9
MIC 3	113.8	111.7	122.3	171.6	127.7	122.5	-64.0	64.1
MIC 4	115.3	113.6	124.5	174.0	129.1	124.6	-86.6	83.8
MIC 5	120.2	116.6	126.3	175.0	132.7	127.0	-96.2	155.1
MIC 6	120.5	115.1	128.2	176.1	133.6	125.5	-195.0	171.4
MIC 7	120.8	117.3	128.5	177.3	133.4	127.9	-109.7	168.2
RUN 30	141.5	0.110322	2.5	312.8	179.7	1389.3	61.6	
PT 8	0.2107	0.004529	0.4062	0.7294	0.5187		47.3	
MIC 1	115.0	113.0	122.7	171.5	129.0	124.1	-60.3	80.8
MIC 2	114.8	112.2	124.3	173.9	129.4	125.8	-473.1	87.4
MIC 3	114.5	112.6	123.3	172.7	130.7	126.9	-491.8	61.0
MIC 4	115.7	114.0	125.0	175.5	130.2	126.6	-491.2	171.9
MIC 5	120.0	116.4	127.1	176.0	132.0	127.6	-115.7	102.8
MIC 6	120.3	114.5	127.6	175.3	133.1	124.1	-126.5	123.1
MIC 7	121.8	119.3	128.0	177.9	134.2	120.6	-157.9	183.9

XH-59A ACOUSTIC DATA

VELOCITY		CLR/S.R	ALPHA	RPM	VTIP	J THRUST	SRPM J1	PMAX
MTUN		CP/S	MJ	MAT	MTIP	PNDBC	SRPM J2	PMIN
DBAU		DBAC	DBU	DBC	PHDBU			
RUN 30	142.1	0.112681	2.5	316.0	181.6	1379.9	61.7	
PT 4	0.2104	0.003485	0.4027	0.7330	0.5226		47.2	
MIC 1	115.4	113.7	124.7	124.3	129.2	124.9	-109.2	86.1
MIC 2	115.7	114.5	125.4	125.1	129.7	126.5	-85.6	83.6
MIC 3	114.0	113.0	124.2	123.7	130.3	126.5	-106.1	65.5
MIC 4	116.0	115.3	127.6	127.4	130.9	127.2	-130.8	109.0
MIC 5	120.9	118.0	128.8	128.1	133.7	129.2	-176.4	127.7
MIC 6	120.4	115.8	123.5	128.2	124.1	126.3	-213.6	129.7
MIC 7	122.2	120.0	130.1	129.3	135.0	131.1	-178.2	191.1
RUN 24	160.6	0.084655	2.5	321.6	184.8	528.1	50.7	
PT 12	0.2742	0.003623	0.4471	0.7580	0.5238		43.4	
MIC 1	116.2	114.4	124.5	126.0	129.9	125.8	-143.6	04.5
MIC 2	114.6	112.6	123.9	123.3	128.5	123.9	-79.3	78.6
MIC 3	115.2	113.4	124.0	123.3	128.8	124.3	-101.1	115.4
MIC 4	116.3	114.4	126.2	125.7	130.0	125.6	-113.6	129.6
MIC 5	121.7	119.0	128.5	127.9	134.2	128.9	-176.9	149.0
MIC 6	123.0	118.5	130.8	125.1	125.6	129.3	-166.0	185.8
MIC 7	121.7	117.4	129.0	127.3	134.1	126.9	-154.2	147.3
RUN 24	160.6	0.084656	2.5	320.3	194.0	528.1	50.8	
PT 11	0.2342	0.002551	0.4489	0.7559	0.5217		43.3	
MIC 1	115.7	115.1	126.5	126.1	130.2	126.3	-123.4	106.0
MIC 2	115.0	113.1	123.8	124.3	129.0	124.7	-107.4	72.7
MIC 3	115.7	114.1	123.9	123.2	129.0	124.5	-89.7	71.2
MIC 4	116.4	114.5	126.0	125.5	130.2	126.1	-112.4	100.4
MIC 5	121.5	117.6	123.2	127.1	123.9	128.5	-151.7	160.1
MIC 6	122.2	118.0	130.4	128.4	135.5	128.7	-210.4	245.2
MIC 7	122.5	118.9	123.4	127.8	134.8	120.1	-152.5	172.6

ORIGINAL PAGE IS  
OF POOR QUALITY

The following tables present detailed XH-59A ABC acoustic data of selected points. Data are presented for microphones 2, 4, and 7. The run/point number sequence used is based on tunnel velocity (knots), shaft angle of attack (ALPHA), and isolated rotor lift coefficient (CLR/S,R). The run/point numbers are ordered in terms of increasing isolated rotor lift coefficient at each tunnel velocity and shaft angle of attack.

## SYMBOLS

ALPHA model pitch, positive up, deg  
 CLR/S,R isolated rotor lift coefficient  
 DBC dB corrected for background noise  
 DBU dB not corrected for background noise  
 MU advance ratio  
 PT point number  
 RUN run number  
 VELOCITY tunnel velocity, knots

Acoustic data for the selected points are presented in the following order:

RUN/PT	VELOCITY	ALPHA	CLR/S,R
28/6	88.3	2.5	0.082
28/7	88.6	2.5	.109
28/8	88.8	2.5	.150
21/7	89.4	5.0	.072
30/7	88.2	5.0	.104
30/6	88.0	5.0	.128
21/11	89.8	7.5	.074
21/14	90.1	7.5	.119
29/11	88.4	7.5	.162
23/15	107.8	2.5	.085
21/19	108.5	5.0	.069
23/9	105.6	5.0	.114
23/10	106.1	5.0	.135
23/11	106.4	5.0	.145
25/6	106.2	7.5	.067
23/12	106.8	7.5	.093
25/8	104.8	7.5	.116
23/13	107.0	7.5	.131
25/9	104.3	7.5	.134
23/16	143.0	2.5	.079
23/17	143.0	2.5	.110
30/9	142.1	2.5	.113

ORIGINAL PART I.  
OF POOR QUALITY

RUN/PT	VELOCITY	ALPHA	CLR/S.R
24/6	140.9	5.0	0.079
24/7	140.9	5.0	.113
24/8	141.2	5.0	.125
24/9	142.4	7.5	.090



XH-59A ACOUSTIC DATA

ORIGINAL PAGE IS  
OF POOR QUALITY

RUN 28	POINT 6	VELOCITY 88.3	ALPHA 2.5	CLR/S,R 0.081592	MU 0.2496	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	79.0	73.4	83.6	79.9	88.6	84.7
12.5	75.9	0.0	81.8	79.2	83.1	0.0
16.0	107.1	107.1	114.0	114.0	114.3	114.3
20.0	97.9	97.7	103.8	103.6	104.2	103.7
25.0	80.1	0.0	89.3	87.6	89.2	0.0
31.5	106.8	106.8	100.6	100.4	118.6	118.6
40.0	90.0	0.0	95.6	93.7	98.1	0.0
50.0	110.5	110.5	92.3	85.4	114.3	114.2
63.0	109.8	109.7	109.1	109.0	113.3	113.1
80.0	103.1	102.4	113.9	113.8	105.2	103.2
100.0	105.2	104.6	106.1	105.5	109.4	108.7
125.0	111.7	111.5	113.2	113.1	109.9	109.2
160.0	112.7	112.6	115.9	115.8	109.1	108.3
200.0	109.3	109.1	113.5	113.4	110.6	110.0
250.0	108.8	108.7	107.7	107.5	114.7	114.5
315.0	110.4	110.3	107.2	106.9	113.8	113.4
400.0	107.7	107.5	106.8	106.4	111.3	110.6
500.0	106.4	106.1	104.9	104.3	110.0	110.1
630.0	103.3	102.8	102.3	101.5	107.8	106.4
800.0	99.8	98.2	99.1	96.0	104.2	100.2
1000.0	99.0	98.0	100.3	96.7	104.2	98.3
1250.0	100.6	98.4	98.8	96.4	104.5	101.7
1600.0	96.6	0.0	96.8	0.0	100.8	0.0
2000.0	94.7	91.5	94.4	88.7	97.2	0.0
2500.0	96.9	92.4	95.8	90.5	96.2	0.0
3150.0	96.7	0.0	96.7	0.0	96.0	0.0
4000.0	91.8	0.0	93.2	0.0	93.5	0.0
5000.0	91.2	0.0	90.4	0.0	91.3	0.0
6300.0	90.3	0.0	92.3	0.0	88.7	0.0
8000.0	88.8	0.0	89.7	0.0	88.0	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	107.5	114.3	114.7
2	106.7	100.5	118.6
3	110.4	87.4	114.1
4	109.5	108.9	112.8
5	102.7	113.7	102.0
6	104.5	104.6	107.5
7	103.5	106.5	108.3
8	110.7	111.5	96.5
9	109.8	112.3	98.2
10	107.8	110.5	104.6

XH-59A ACOUSTIC DATA

ORIGINAL 17.000  
OF POOR QUALITY

RUN 28	POINT 7	VELOCITY 88.6	ALPHA 2.5	CLR/S,R 0.108912	MU 0.2514	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	79.7	75.5	79.8	0.0	82.6	0.0
12.5	76.0	0.0	77.2	0.0	81.4	0.0
16.0	104.9	104.9	113.8	113.8	113.7	113.7
20.0	96.0	95.6	103.3	103.1	103.9	103.4
25.0	81.0	0.0	83.6	0.0	93.9	84.1
31.5	106.1	106.1	105.5	105.4	123.1	123.1
40.0	90.7	0.0	92.6	87.3	100.9	95.3
50.0	110.5	110.5	104.7	104.5	117.8	117.7
63.0	108.9	108.8	111.5	111.4	115.7	115.6
80.0	99.5	97.7	116.3	116.2	113.0	112.7
100.0	112.4	112.3	110.3	110.1	105.7	103.7
125.0	114.1	114.0	115.1	115.0	108.8	107.9
160.0	111.0	110.8	114.4	114.3	114.2	114.0
200.0	113.7	113.6	112.5	112.4	113.2	112.9
250.0	113.4	113.4	111.6	111.5	114.7	114.5
315.0	111.9	111.8	111.2	111.1	115.4	115.1
400.0	111.7	111.6	107.1	106.7	115.5	115.3
500.0	108.4	108.2	106.9	106.5	113.2	112.7
630.0	107.2	107.0	105.8	105.5	111.8	111.3
800.0	102.6	101.8	101.1	99.4	107.3	105.7
1000.0	101.3	99.8	101.1	98.3	107.3	105.3
1250.0	101.9	100.4	99.6	97.7	105.2	102.9
1600.0	98.2	86.4	98.0	0.0	102.3	95.2
2000.0	95.6	93.2	95.0	90.5	98.9	93.6
2500.0	96.7	91.8	96.6	92.7	98.8	94.3
3150.0	95.9	0.0	94.6	0.0	96.6	0.0
4000.0	92.0	0.0	93.1	0.0	93.7	0.0
5000.0	92.2	0.0	90.4	0.0	91.4	0.0
6300.0	89.0	0.0	93.2	0.0	89.3	0.0
8000.0	89.2	0.0	89.7	0.0	87.5	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	105.3	114.2	114.0
2	106.0	105.4	123.1
3	110.4	104.6	117.7
4	108.7	111.3	115.5
5	96.5	116.2	112.8
6	112.0	110.0	101.3
7	108.1	110.2	106.1
8	112.7	112.9	90.7
9	102.2	107.5	106.4
10	105.9	111.5	110.5

XH-59A ACOUSTIC DATA ORIGINAL PAGE IS  
OF POOR QUALITY

RUN 28	POINT 8	VELOCITY 88.8	ALPHA 2.5	CLR/S,R 0.149922	MU 0.2505	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	83.4	82.1	83.6	79.8	88.8	85.0
12.5	76.6	0.0	75.4	0.0	84.5	68.6
16.0	104.6	104.6	114.2	114.2	113.2	113.2
20.0	96.4	96.0	105.4	105.3	105.2	104.8
25.0	86.7	84.5	93.6	93.0	97.2	94.8
31.5	106.4	106.4	99.1	98.9	117.8	117.8
40.0	94.4	91.0	95.7	93.9	100.9	95.2
50.0	110.7	110.7	109.4	109.3	122.5	122.5
63.0	116.2	116.2	115.0	115.0	122.1	122.1
80.0	115.2	115.2	120.8	120.8	118.0	117.9
100.0	113.9	113.8	115.7	115.6	114.7	114.5
125.0	119.8	119.8	118.3	118.3	113.4	113.1
160.0	117.0	117.0	118.5	116.5	116.5	118.8
200.0	118.4	118.4	118.2	118.2	120.4	120.3
250.0	118.1	118.1	114.5	114.5	117.3	117.2
315.0	115.4	115.4	115.7	115.7	124.2	124.2
400.0	112.7	112.6	112.5	112.4	121.6	121.5
500.0	110.6	110.5	110.5	110.3	117.1	116.9
630.0	109.0	108.9	110.3	110.2	113.1	112.7
800.0	105.9	105.6	106.4	106.0	111.3	110.7
1000.0	103.7	102.9	105.0	104.1	110.3	109.4
1250.0	103.4	102.4	103.7	103.0	107.5	106.3
1600.0	100.9	98.1	102.1	98.4	106.1	104.3
2000.0	98.5	97.4	100.5	99.6	104.0	102.9
2500.0	98.3	95.6	97.7	95.0	102.0	100.4
3150.0	97.3	0.0	97.1	0.0	99.8	95.6
4000.0	93.1	0.0	94.8	0.0	97.1	91.6
5000.0	93.1	0.0	91.5	0.0	94.6	0.0
6300.0	90.4	0.0	92.5	0.0	91.4	0.0
8000.0	87.7	0.0	88.5	0.0	88.0	0.0

BLADE PASSAGE HARMONICS	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	105.1	114.7	113.7
2	106.4	98.9	117.7
3	110.5	109.7	122.4
4	116.0	114.8	122.0
5	115.0	120.7	117.7
6	113.6	115.1	113.0
7	115.0	117.4	107.7
8	117.8	108.9	110.7
9	112.9	112.6	113.1
10	110.8	114.6	113.9

ORIGINAL REPORT  
OF POOR QUALITY

XH-59A ACOUSTIC DATA

RUN 21	POINT 7	VELOCITY 89.4	ALPHA 5.0	CLR/S,K 0.071956	MU 0.2504	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	72.6	0.0	81.8	71.8	85.7	0.0
12.5	66.4	0.0	80.0	74.6	76.6	0.0
16.0	99.4	99.3	105.1	105.1	109.4	109.3
20.0	91.8	90.7	97.9	97.1	102.7	102.0
25.0	74.0	0.0	83.7	0.0	96.3	93.0
31.5	105.5	105.5	102.1	102.0	98.2	94.4
40.0	92.1	79.9	86.0	0.0	101.7	97.4
50.0	99.6	99.0	99.7	99.0	114.5	114.4
63.0	111.1	111.0	111.1	111.0	115.2	115.0
80.0	103.3	102.6	112.0	111.8	109.1	108.4
100.0	109.4	109.2	100.4	97.6	102.8	96.7
125.0	109.0	108.7	106.3	105.5	105.7	103.5
160.0	110.8	110.6	112.6	112.5	106.8	105.2
200.0	110.9	110.8	109.7	109.5	114.3	114.0
250.0	104.2	103.6	106.8	106.5	111.8	111.4
315.0	107.4	107.2	106.9	106.6	113.0	112.5
400.0	104.8	104.3	105.1	104.5	110.5	109.6
500.0	102.4	101.6	102.9	101.8	108.8	107.3
630.0	99.1	97.7	100.4	99.0	105.1	101.6
800.0	96.9	92.7	97.5	91.3	103.8	98.6
1000.0	97.0	90.0	98.4	88.5	103.9	96.1
1250.0	98.6	94.2	98.3	95.3	102.8	97.0
1600.0	95.6	0.0	96.5	0.0	100.5	0.0
2000.0	93.4	87.9	93.1	0.0	97.4	0.0
2500.0	96.3	90.3	94.5	79.1	95.9	0.0
3150.0	95.8	0.0	97.2	0.0	96.1	0.0
4000.0	91.2	0.0	92.3	0.0	92.5	0.0
5000.0	91.2	0.0	90.3	0.0	91.1	0.0
6300.0	93.9	0.0	94.0	0.0	88.7	0.0
8000.0	88.8	0.0	87.9	0.0	85.8	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	99.6	105.6	110.2
2	105.5	102.0	96.2
3	98.8	99.1	114.4
4	111.0	111.0	115.0
5	102.2	111.7	108.3
6	109.2	92.5	95.0
7	105.9	93.2	96.4
8	104.3	104.2	96.8
9	101.8	110.7	93.7
10	109.1	106.9	104.3

ORIGINAL PAGE IS  
OF POOR QUALITY

XH-59A ACOUSTIC DATA

RUN 30	POINT 7	VELOCITY 88.2	ALPHA 5.0	CLR/S,R 0.103501	MU 0.2501	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	78.1	68.4	80.7	0.0	85.1	0.0
12.5	76.4	0.0	79.3	72.2	78.6	0.0
15.0	105.8	105.8	111.2	111.2	113.5	113.5
20.0	96.3	95.9	101.1	100.7	103.8	103.3
25.0	88.8	87.6	88.1	85.7	95.0	90.1
31.5	107.6	107.6	100.4	100.2	121.1	121.1
40.0	95.9	93.9	92.2	86.1	102.2	98.9
50.0	112.9	112.9	104.6	104.4	113.2	113.0
63.0	110.1	110.0	113.3	113.3	117.2	117.1
80.0	111.6	111.5	110.3	110.1	111.5	111.1
100.0	109.4	109.2	107.6	107.2	109.9	109.3
125.0	114.3	114.2	111.0	110.8	112.1	111.7
160.0	107.8	107.5	110.6	110.4	107.4	106.1
200.0	108.6	108.4	111.3	111.2	114.8	114.6
250.0	110.2	110.1	108.7	108.5	115.9	115.7
315.0	109.7	109.6	109.5	109.3	115.3	115.0
400.0	107.8	107.6	109.3	109.1	114.2	113.9
500.0	106.5	106.2	106.5	106.1	113.6	113.2
630.0	104.7	104.4	104.7	104.3	110.7	110.0
800.0	101.3	100.2	102.0	100.7	107.5	106.1
1000.0	100.5	98.6	101.3	98.7	106.7	104.4
1250.0	100.5	98.3	101.0	99.7	105.4	103.3
1600.0	98.6	91.4	98.6	0.0	103.2	98.7
2000.0	96.4	94.5	96.6	94.1	100.6	97.9
2500.0	94.7	0.0	94.9	86.3	99.2	95.5
3150.0	100.6	96.5	97.0	0.0	99.5	94.9
4000.0	92.8	0.0	94.5	0.0	95.9	84.5
5000.0	89.3	0.0	90.9	0.0	93.4	0.0
6300.0	92.6	0.0	89.8	0.0	91.1	0.0
8000.0	87.9	0.0	89.1	0.0	89.0	0.0

BLADE PASSAGE HARMONICS	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	106.2	111.6	113.9
2	107.5	100.3	121.1
3	112.7	104.3	113.0
4	109.7	113.1	117.1
5	111.3	109.2	110.6
6	108.2	106.3	106.7
7	112.3	105.7	109.9
8	109.2	108.3	99.2
9	95.1	105.6	95.6
10	106.0	103.2	101.2

ORIGINAL PAGE IS  
OF POOR QUALITY

XH-59A ACOUSTIC DATA

KUN 30	POINT 6	VELOCITY 88.0	ALPHA 5.0	CLR/S.R 0.127927	MU 0.2508	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	74.8	0.0	82.7	77.5	87.7	82.1
12.5	72.9	0.0	80.4	76.2	71.2	0.0
16.0	102.6	102.6	112.4	112.4	115.6	115.6
20.0	90.2	88.5	100.2	99.8	103.3	102.7
25.0	86.7	84.6	82.2	0.0	98.6	97.1
31.5	110.1	110.1	105.3	105.2	122.8	122.8
40.0	95.6	93.4	90.3	0.0	99.3	0.0
50.0	111.3	111.3	105.4	105.2	118.5	118.4
63.0	109.3	109.2	110.0	109.9	116.8	116.7
80.0	104.8	104.4	115.3	115.2	112.8	112.5
100.0	111.6	111.5	112.0	111.9	109.2	108.4
125.0	114.7	114.6	115.4	115.3	111.5	111.0
160.0	111.4	111.3	116.5	116.4	115.7	115.5
200.0	111.8	111.7	114.4	114.3	114.4	114.2
250.0	111.7	111.6	114.6	114.6	110.7	110.2
315.0	109.6	109.5	111.1	111.0	116.4	116.2
400.0	111.4	111.3	107.0	106.6	114.1	113.8
500.0	106.1	105.8	107.7	107.4	112.7	112.2
630.0	103.2	102.7	105.3	104.9	109.7	108.8
800.0	101.3	100.2	101.8	100.4	107.2	105.6
1000.0	100.0	97.8	100.6	97.4	106.3	103.7
1250.0	99.8	97.1	100.2	98.6	104.7	102.1
1600.0	98.7	91.9	97.9	0.0	103.1	98.5
2000.0	95.3	92.7	95.7	92.4	99.9	96.5
2500.0	94.1	0.0	94.5	82.1	98.5	93.7
3150.0	98.7	86.0	99.0	0.0	98.5	91.1
4000.0	93.2	0.0	93.7	0.0	95.6	76.6
5000.0	89.7	0.0	90.7	0.0	93.1	0.0
6300.0	92.2	0.0	90.6	0.0	90.9	0.0
8000.0	88.1	0.0	89.3	0.0	89.0	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	102.7	112.6	115.8
2	110.0	105.2	122.7
3	111.2	105.0	118.4
4	109.1	109.9	116.5
5	103.5	115.1	112.3
6	110.9	109.2	100.6
7	106.7	113.5	110.7
8	113.3	111.8	103.3
9	99.1	113.6	99.5
10	101.0	111.0	111.6

XH-59A ACOUSTIC DATA

RUN	POINT	VELOCITY	ALPHA	CLR/S.R	MU
21	11	89.8	7.5	0.073627	0.2485

1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	69.8	0.0	74.4	0.0	85.8	0.0
12.5	71.2	0.0	74.9	0.0	84.1	0.0
16.0	100.3	100.2	107.8	107.8	107.4	107.3
20.0	95.7	95.3	104.2	104.0	104.4	103.9
25.0	82.0	0.0	87.8	84.7	89.1	0.0
31.5	104.6	104.5	98.0	97.7	109.6	109.4
40.0	93.1	81.0	91.1	0.0	98.3	0.0
50.0	103.3	103.1	92.3	83.7	110.5	110.1
63.0	102.2	106.0	111.4	111.3	108.0	107.1
80.0	99.5	97.6	109.4	109.1	114.2	114.0
100.0	108.3	105.8	102.1	100.4	109.1	108.2
125.0	110.8	110.6	106.3	105.5	109.4	108.6
160.0	109.3	109.1	108.8	108.5	107.6	106.3
200.0	108.9	108.7	112.0	111.9	112.8	112.4
250.0	102.6	101.9	106.9	106.6	111.8	111.4
315.0	104.4	104.0	108.4	108.2	112.3	111.7
400.0	104.9	104.4	105.3	104.7	111.9	111.3
500.0	102.7	101.9	104.1	103.3	110.6	109.6
630.0	100.3	99.3	103.4	102.8	107.9	106.4
800.0	99.3	97.4	98.8	95.1	104.4	100.2
1000.0	98.6	95.0	100.4	96.7	103.6	93.3
1250.0	99.1	95.4	100.1	98.3	103.2	98.2
1600.0	96.0	0.0	97.9	0.0	100.9	0.0
2000.0	93.2	87.1	93.0	0.0	97.9	85.5
2500.0	94.9	0.0	93.8	0.0	95.8	0.0
3150.0	96.0	0.0	95.9	0.0	95.6	0.0
4000.0	91.7	0.0	92.4	0.0	93.2	0.0
5000.0	91.4	0.0	90.0	0.0	91.3	0.0
6300.0	95.6	0.0	93.8	0.0	89.4	0.0
8000.0	87.3	0.0	86.7	0.0	85.3	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	101.3	109.4	109.0
2	104.5	97.8	109.6
3	102.9	90.8	110.2
4	106.1	111.3	107.1
5	97.8	108.6	114.0
6	105.7	98.1	107.8
7	105.0	98.1	99.5
8	109.0	105.0	107.2
9	102.5	104.8	89.3
10	107.5	103.8	104.0

XH-59A ACOUSTIC DATA

RUN 21	POINT 14	VELOCITY 90.1	ALPHA 7.5	CLR/S,R 0.118578	MU 0.2499	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBJ	DBC	DBU	DBC	DBU	DBC
10.0	80.8	77.8	80.0	0.0	77.5	0.0
12.5	78.9	74.7	73.5	0.0	88.3	85.8
16.0	105.6	105.6	113.7	113.7	113.0	113.0
20.0	100.3	100.2	108.8	108.7	108.2	108.0
25.0	61.9	0.0	85.0	67.9	95.9	91.8
31.5	109.5	109.5	105.2	105.1	115.1	115.0
40.0	90.0	0.0	92.2	85.0	97.9	0.0
50.0	105.8	105.7	102.9	102.6	116.6	116.5
63.0	110.4	110.3	110.2	110.1	117.9	117.8
80.0	99.5	97.5	114.1	114.0	109.0	108.2
100.0	112.2	112.1	109.1	108.8	110.1	109.4
125.0	110.3	110.1	108.7	108.3	106.8	105.1
160.0	108.5	108.2	117.6	117.6	112.2	111.8
200.0	109.5	109.3	113.2	113.1	115.3	115.1
250.0	107.4	107.2	109.4	109.2	110.4	109.8
315.0	109.3	109.2	111.5	111.4	116.0	115.7
400.0	108.1	107.9	107.8	107.5	113.7	113.3
500.0	105.3	104.9	105.2	104.6	110.5	109.5
630.0	102.2	101.6	102.4	101.6	108.3	106.9
800.0	98.4	95.9	99.4	96.4	105.2	102.0
1000.0	98.3	94.3	99.7	94.9	104.7	99.3
1250.0	99.6	96.5	98.9	96.3	102.8	96.7
1600.0	96.6	0.0	97.2	0.0	101.1	0.0
2000.0	94.4	90.7	93.9	85.5	98.2	88.6
2500.0	95.1	71.5	94.2	0.0	97.3	82.1
3150.0	96.9	0.0	98.1	0.0	96.4	0.0
4000.0	92.1	0.0	92.9	0.0	93.6	0.0
5000.0	91.2	0.0	90.3	0.0	91.6	0.0
6300.0	95.0	0.0	94.7	0.0	89.0	0.0
8000.0	87.9	0.0	89.1	0.0	86.2	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	106.6	114.9	114.2
2	109.5	105.1	115.0
3	105.5	101.8	116.2
4	110.2	110.0	117.8
5	95.9	114.0	106.8
6	112.1	108.6	109.1
7	107.6	106.0	102.2
8	105.8	102.3	93.5
9	98.6	116.7	100.9
10	103.7	108.6	110.6



XH-59A ACOUSTIC DATA

ORIGINAL PAGE IS  
OF POOR QUALITY

RUN 29	POINT 11	VELOCITY 88.4	ALPHA 7.5	CLR/S.R 0.161634	MU 0.2507	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	80.6	77.5	78.9	0.0	89.8	87.2
12.5	78.4	73.5	80.6	76.6	92.2	92.1
16.0	98.3	98.2	110.2	110.2	116.1	116.1
20.0	91.7	90.6	98.3	97.6	106.9	106.7
25.0	88.1	86.7	93.3	92.7	92.7	0.0
31.5	110.2	110.2	104.8	104.7	125.1	125.1
40.0	94.8	91.9	90.3	0.0	103.6	101.5
50.0	110.6	110.6	107.9	107.8	121.0	121.0
63.0	112.4	112.4	108.6	108.5	121.4	121.4
80.0	102.9	102.2	119.9	119.9	116.2	116.1
100.0	113.0	112.9	111.1	110.9	104.4	104.8
125.0	116.5	116.4	117.3	117.2	114.4	114.2
160.0	112.7	112.6	115.6	115.5	115.1	114.9
200.0	110.4	110.2	115.0	114.9	118.1	118.0
250.0	112.1	112.0	111.6	111.5	119.1	119.0
315.0	112.1	112.0	115.2	115.2	120.4	120.3
400.0	110.2	110.1	112.8	112.7	116.7	116.5
500.0	108.2	108.0	111.4	111.3	114.8	114.5
630.0	105.9	105.7	108.7	108.5	112.0	111.5
800.0	102.7	102.0	103.5	102.6	108.7	107.6
1000.0	100.7	98.9	102.0	99.9	107.4	105.5
1250.0	101.3	99.5	101.7	100.6	105.9	104.1
1600.0	99.5	94.8	99.9	87.2	103.5	99.5
2000.0	96.6	94.6	97.8	96.0	101.6	99.6
2500.0	94.8	0.0	96.2	91.7	99.8	96.7
3150.0	98.0	0.0	99.8	86.3	99.0	93.1
4000.0	93.0	0.0	94.4	0.0	96.7	90.2
5000.0	89.9	0.0	91.0	0.0	94.3	0.0
6300.0	93.7	0.0	92.2	0.0	91.4	0.0
8000.0	88.8	0.0	89.3	0.0	88.8	0.0

BLADE PASSAGE HARMONICS	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	98.3	110.0	116.5
2	110.1	104.4	125.1
3	110.4	107.6	120.9
4	112.1	107.8	121.3
5	101.4	119.8	116.0
6	112.6	110.4	96.4
7	108.6	115.7	100.6
8	115.3	111.6	113.5
9	110.7	112.9	108.5
10	96.0	109.7	110.9

ORIGINAL PAGE IS  
OF POOR QUALITY

XH-59A ACOUSTIC DATA

NON 23	POINT 15	VELOCITY 107.8	ALPHA 2.5	CLR/S,R 0.084788	MU 0.2995	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	75.4	0.0	82.1	0.0	91.1	85.4
12.5	82.5	80.4	79.9	0.0	92.7	91.0
16.0	96.4	96.1	95.1	94.4	109.5	109.4
20.0	93.9	92.8	91.9	0.0	105.1	104.3
25.0	83.9	0.0	86.3	0.0	102.8	101.4
31.5	101.8	101.6	107.2	107.1	115.3	115.2
40.0	91.1	0.0	93.1	0.0	102.8	84.6
50.0	104.7	104.3	100.9	99.5	117.9	117.8
63.0	111.1	111.0	111.9	111.8	116.0	115.7
80.0	102.8	101.1	115.7	115.5	119.0	118.8
100.0	112.4	112.2	104.8	103.0	108.0	104.8
125.0	110.1	109.7	114.7	114.5	109.6	107.7
160.0	111.4	111.2	109.8	109.3	109.0	106.8
200.0	110.3	110.0	110.9	110.6	112.0	110.9
250.0	107.3	106.9	109.2	108.9	114.5	114.0
315.0	108.2	107.9	109.2	108.9	115.5	115.0
400.0	106.6	106.1	106.7	106.1	113.9	113.2
500.0	105.6	105.0	107.4	106.9	112.5	111.4
630.0	102.8	101.9	104.8	104.1	110.0	108.1
800.0	100.4	98.2	101.6	99.2	107.7	104.2
1000.0	96.6	92.6	99.8	90.7	106.7	99.7
1250.0	99.4	97.3	98.9	90.0	105.6	99.4
1600.0	97.3	0.0	97.3	0.0	102.5	0.0
2000.0	92.7	0.0	93.6	0.0	99.8	0.0
2500.0	97.0	90.1	95.1	0.0	98.7	0.0
3150.0	96.4	0.0	97.1	0.0	96.5	0.0
4000.0	91.4	0.0	92.4	0.0	93.9	0.0
5000.0	92.5	0.0	90.0	0.0	91.4	0.0
6300.0	90.4	0.0	89.6	0.0	88.8	0.0
8000.0	87.7	0.0	88.5	0.0	87.2	0.0

BLADE PASSAGE HARMONICS	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	98.1	95.9	110.6
2	101.8	107.1	115.2
3	104.5	100.4	117.7
4	111.0	111.5	115.2
5	101.5	115.4	118.7
6	111.9	102.7	102.0
7	102.5	103.6	107.0
8	108.4	113.7	96.6
9	102.0	102.1	103.2
10	109.8	107.6	98.6

ORIGINAL PAGE IS  
OF POOR QUALITY

XH-59A ACOUSTIC DATA

RUN 21	POINT 19	VELOCITY 108.5	ALPHA 5.0	CLR/S,R 0.069378	MU 0.3002		
1/3 OCTAVE CENTER FREQUENCY		MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC	
10.0	79.7	68.6	85.0	78.5	85.9	0.0	
12.5	72.3	0.0	83.5	80.0	84.8	0.0	
16.0	97.7	97.5	107.1	107.1	106.8	106.6	
20.0	91.5	89.2	104.7	104.4	102.7	101.1	
25.0	88.0	82.5	88.9	0.0	93.6	0.0	
31.5	106.0	105.9	101.0	100.6	114.8	114.7	
40.0	93.9	0.0	95.0	89.1	100.9	0.0	
50.0	107.2	107.0	102.5	101.5	115.7	115.4	
63.0	99.3	97.1	111.7	111.6	111.9	111.1	
80.0	103.8	102.4	111.0	110.5	112.8	112.0	
100.0	106.2	107.6	104.1	101.9	107.4	103.3	
125.0	112.3	112.1	113.7	113.5	110.9	109.5	
160.0	107.8	107.2	110.0	109.5	109.9	108.1	
200.0	108.1	107.5	111.3	111.0	113.1	112.7	
250.0	107.8	107.4	106.5	105.9	113.6	113.0	
315.0	108.1	107.8	107.9	107.5	116.5	116.1	
400.0	107.1	106.7	108.7	108.3	114.7	114.1	
500.0	104.5	103.8	105.7	104.9	114.4	113.7	
630.0	102.2	101.1	103.2	102.1	110.8	109.3	
800.0	100.6	98.5	101.8	99.5	108.1	104.9	
1000.0	98.8	93.2	99.4	83.9	107.6	102.9	
1250.0	99.9	94.9	98.7	87.0	106.6	102.4	
1600.0	97.3	0.0	97.4	0.0	103.9	0.0	
2000.0	93.6	0.0	94.8	0.0	100.6	0.0	
2500.0	97.8	93.0	94.4	0.0	99.0	0.0	
3150.0	95.4	0.0	95.1	0.0	96.9	0.0	
4000.0	92.3	0.0	92.5	0.0	94.4	0.0	
5000.0	92.1	0.0	90.2	0.0	92.6	0.0	
6300.0	94.9	0.0	95.4	0.0	89.6	0.0	
8000.0	86.1	0.0	88.2	0.0	86.7	0.0	

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	98.6	109.0	108.1
2	106.0	100.7	114.8
3	106.3	98.1	115.4
4	95.6	111.3	111.0
5	101.7	110.7	112.5
6	107.7	101.4	94.0
7	106.6	109.4	106.9
8	110.4	111.1	100.8
9	105.0	107.9	100.1
10	95.7	102.7	104.6

XH-59A ACOUSTIC DATA

RUN 23	POINT 9	VELOCITY 105.6	ALPHA 5.0	CLR/S.R 0.114356	MU 0.2985	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	77.4	0.0	78.0	0.0	95.2	93.9
12.5	72.1	0.0	79.8	0.0	93.7	92.5
16.0	101.6	101.5	96.7	96.2	111.8	111.7
20.0	93.0	91.6	91.7	0.0	103.1	101.8
25.0	86.6	77.2	88.5	0.0	99.1	95.2
31.5	109.2	109.2	105.3	105.2	114.8	114.7
40.0	94.1	72.6	92.0	0.0	105.1	101.7
50.0	109.0	108.9	102.4	101.5	120.2	120.1
63.0	107.9	107.7	108.2	107.9	119.0	118.9
80.0	107.9	107.5	112.0	111.7	116.6	116.3
100.0	114.2	114.1	102.8	99.9	108.4	105.9
125.0	116.2	116.1	119.1	119.0	117.1	116.8
160.0	113.1	112.0	109.0	108.5	112.5	111.7
200.0	111.4	111.2	114.2	114.1	114.6	114.1
250.0	107.0	106.6	109.5	109.2	116.4	116.1
315.0	111.5	111.4	113.3	113.2	115.9	115.4
400.0	109.8	109.6	108.8	108.5	113.3	112.5
500.0	106.8	106.4	105.8	105.1	111.1	109.6
630.0	103.6	102.9	103.5	102.6	110.3	108.7
800.0	100.3	98.1	102.7	101.0	107.9	104.9
1000.0	99.5	95.6	100.3	94.2	107.1	102.1
1250.0	100.8	97.5	99.6	94.5	106.2	102.0
1600.0	98.2	0.0	98.2	0.0	103.8	0.0
2000.0	93.9	83.3	94.9	79.5	101.2	91.1
2500.0	97.2	91.3	94.5	0.0	99.6	0.0
3150.0	96.3	0.0	98.6	0.0	98.3	0.0
4000.0	92.9	0.0	93.8	0.0	95.1	0.0
5000.0	92.8	0.0	90.1	0.0	92.8	0.0
6300.0	94.1	0.0	93.3	0.0	90.6	0.0
8000.0	89.1	0.0	89.2	0.0	87.7	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	102.1	97.4	112.3
2	109.1	105.1	114.8
3	108.6	100.2	120.1
4	107.2	107.7	118.9
5	107.2	111.4	115.9
6	113.8	93.2	104.4
7	114.8	112.1	108.5
8	109.7	118.0	115.9
9	106.1	103.8	105.5
10	110.5	99.0	108.4

XH-59A ACOUSTIC DATA

RUN 23	POINT 10	VELOCITY 106.1	ALPHA 5.0	CLR/S,R 0.135245	MU 0.2998	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBJ	DBC	DBU	DBC	DBU	DBC
10.0	80.3	73.9	83.5	0.0	94.5	92.9
12.5	76.2	0.0	82.4	77.6	94.7	93.8
16.0	99.4	99.3	102.0	101.9	115.3	115.3
20.0	90.5	87.6	97.7	96.3	105.8	105.2
25.0	89.4	86.6	94.1	92.6	99.5	96.0
31.5	110.0	110.0	102.1	101.9	120.6	120.6
40.0	95.8	90.8	95.3	90.7	104.8	101.0
50.0	111.5	111.4	100.8	99.5	121.2	121.1
63.0	109.1	108.9	100.8	99.0	122.2	122.1
80.0	105.6	104.8	115.8	115.7	117.4	117.2
100.0	116.8	116.7	105.8	104.5	107.8	104.7
125.0	118.0	117.9	117.5	117.4	116.1	115.8
160.0	116.1	116.0	114.3	114.1	115.5	115.1
200.0	113.2	113.0	116.8	116.7	115.9	115.5
250.0	109.8	109.6	110.8	110.6	116.5	116.2
315.0	113.0	112.9	112.6	112.5	117.5	117.2
400.0	109.8	109.6	111.4	111.2	116.2	115.8
500.0	107.3	106.9	108.0	107.6	113.9	113.2
630.0	107.3	107.0	106.5	106.0	113.0	112.2
800.0	102.4	101.2	104.2	103.1	109.5	107.6
1000.0	101.4	99.3	102.8	100.4	107.7	103.7
1250.0	102.1	99.9	101.2	98.3	105.9	101.1
1600.0	98.9	84.1	98.9	0.0	104.1	78.7
2000.0	95.7	91.6	96.5	91.6	101.8	94.8
2500.0	97.3	91.6	95.9	81.5	100.1	85.3
3150.0	96.4	0.0	100.5	89.4	99.4	0.0
4000.0	92.9	0.0	94.0	0.0	96.4	0.0
5000.0	91.6	0.0	90.8	0.0	93.4	0.0
6300.0	94.3	0.0	94.6	0.0	90.8	0.0
8000.0	88.5	0.0	88.4	0.0	87.0	0.0

ELADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	94.6	103.0	115.7
2	109.9	101.8	120.6
3	111.3	100.2	120.9
4	108.2	97.1	122.0
5	104.0	115.5	116.7
6	116.6	102.5	93.4
7	117.5	108.8	100.6
8	104.5	116.5	115.4
9	112.6	100.7	108.2
10	111.7	108.9	111.4

XH-59A ACOUSTIC DATA

RUN 23	POINT 11	VELOCITY 106.4	ALPHA 5.0	CLR/S,K 0.145052	MU 0.3092	
1/2 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	70.9	0.0	84.0	72.9	90.3	82.5
12.5	72.1	0.0	72.4	0.0	80.7	0.0
16.0	99.8	99.7	99.5	99.3	115.4	115.4
20.0	92.7	91.2	94.6	90.9	106.3	105.7
25.0	90.6	88.6	87.7	0.0	95.3	0.0
31.5	110.9	110.9	97.6	96.9	120.6	120.6
40.0	95.9	91.1	99.7	98.5	107.0	105.1
50.0	114.2	114.2	101.4	100.2	122.3	122.3
63.0	111.4	111.3	114.4	114.3	124.9	124.9
80.0	109.7	109.4	121.2	121.2	118.2	118.0
100.0	115.4	119.4	108.9	108.3	114.1	113.5
125.0	117.2	117.1	120.5	120.5	115.1	114.7
160.0	113.0	112.8	119.8	119.8	115.9	115.5
200.0	112.8	112.6	116.5	116.4	113.5	112.6
250.0	113.0	112.9	111.4	111.2	119.0	118.8
315.0	115.1	115.0	113.5	113.4	121.1	121.0
400.0	111.3	111.2	113.0	112.9	118.3	118.1
500.0	109.3	109.1	111.2	111.0	115.3	114.8
630.0	107.8	107.5	107.6	107.3	111.4	110.2
800.0	104.8	104.1	105.4	104.6	109.6	107.8
1000.0	103.3	102.1	103.3	101.2	108.5	105.4
1250.0	102.0	101.3	102.3	100.2	107.2	104.2
1600.0	99.5	91.4	100.0	0.0	104.8	96.4
2000.0	97.1	94.6	98.3	95.7	103.0	98.9
2500.0	98.2	94.3	96.4	87.8	101.0	94.1
3150.0	95.0	0.0	97.2	0.0	99.3	0.0
4000.0	93.1	0.0	94.1	0.0	96.7	0.0
5000.0	91.5	0.0	91.3	0.0	93.9	0.0
6300.0	94.0	0.0	91.4	0.0	90.9	0.0
8000.0	87.7	0.0	88.2	0.0	87.4	0.0

BLADE PASSAGE HARMONICS	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	100.4	99.9	115.8
2	110.9	97.1	120.6
3	114.1	100.4	122.3
4	110.6	114.0	124.7
5	108.3	121.1	117.8
6	119.3	106.6	113.5
7	112.8	109.1	107.6
8	114.5	119.9	113.2
9	106.1	115.8	111.8
10	107.0	116.8	110.9

XH-59A ACOUSTIC DATA

RUN 25	POINT 6	VELOCITY 106.2	ALPHA 7.5	CLR/S,R 0.066537	MU 0.3017	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	71.7	0.0	85.4	80.7	95.5	94.2
12.5	70.3	0.0	80.5	0.0	94.1	93.0
16.0	108.0	108.0	114.9	114.9	106.2	106.0
20.0	96.3	97.9	105.7	105.5	96.1	0.0
25.0	86.9	78.8	90.7	86.2	97.9	91.0
31.5	103.8	103.7	100.5	100.1	112.6	112.4
40.0	88.2	0.0	90.9	0.0	103.8	98.0
50.0	109.7	109.6	95.9	88.5	117.1	116.9
63.0	99.0	96.7	107.0	106.6	115.7	115.4
80.0	99.9	95.8	112.9	112.6	109.0	107.2
100.0	111.4	111.1	102.7	99.6	107.3	103.6
125.0	107.9	107.2	109.4	108.8	108.5	106.1
160.0	113.7	113.6	110.3	109.9	111.4	110.3
200.0	109.0	108.6	110.6	110.3	111.0	109.6
250.0	108.8	108.5	108.6	108.3	114.0	113.5
315.0	107.7	107.4	108.0	107.6	114.9	114.3
400.0	107.4	107.0	105.1	104.3	112.4	111.4
500.0	104.9	104.3	105.3	104.5	111.1	109.6
630.0	103.1	102.3	103.2	102.2	110.6	109.1
800.0	100.2	97.9	101.9	99.8	108.0	105.1
1000.0	99.5	95.6	99.9	92.0	107.1	102.0
1250.0	100.5	96.8	99.3	93.3	106.5	102.7
1600.0	97.1	0.0	97.7	0.0	103.0	0.0
2000.0	93.5	0.0	94.9	77.5	99.6	0.0
2500.0	95.4	0.0	94.0	0.0	97.4	0.0
3150.0	97.4	0.0	96.1	0.0	98.3	0.0
4000.0	91.7	0.0	93.2	0.0	94.1	0.0
5000.0	92.5	0.0	89.8	0.0	92.1	0.0
6300.0	93.7	0.0	90.8	0.0	90.0	0.0
8000.0	87.8	0.0	86.3	0.0	87.0	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	108.4	115.3	106.3
2	103.6	100.3	112.4
3	109.5	92.7	116.9
4	97.2	105.7	115.2
5	90.6	117.4	106.3
6	110.8	99.4	101.6
7	106.3	106.8	100.4
8	98.8	103.0	103.9
9	109.7	107.1	99.4
10	109.6	94.9	105.8

XH-59A ACCUSTIC DATA

FOI 23	POINT 12	VELOCITY 106.8	ALPHA 7.5	CLK/S,R 0.093217	MU 0.3002	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	78.1	0.0	83.0	0.0	84.3	0.0
12.5	84.1	62.8	83.9	81.1	84.5	0.0
16.0	95.7	99.6	99.4	99.1	110.7	110.6
20.0	93.4	92.1	87.6	0.0	107.5	107.1
25.0	86.9	78.1	86.9	0.0	97.8	90.0
31.5	107.2	107.1	95.1	93.6	115.7	115.6
40.0	93.9	0.0	97.5	95.3	102.5	0.0
50.0	107.9	107.7	97.8	94.4	120.3	120.2
63.0	111.4	111.3	106.9	106.4	117.1	116.9
80.0	107.4	106.9	114.2	114.0	113.1	112.5
100.0	113.7	113.5	102.9	99.7	111.4	110.3
125.0	119.0	119.0	118.4	118.3	117.3	117.0
160.0	117.7	117.6	111.8	111.5	112.8	112.0
200.0	113.0	112.8	117.7	117.6	114.4	113.8
250.0	117.6	117.6	113.9	113.8	119.2	119.0
315.0	117.7	117.7	116.3	116.2	120.2	120.0
400.0	114.9	114.8	113.6	113.5	115.7	115.3
500.0	112.1	112.0	113.0	112.9	115.6	115.1
630.0	111.0	110.9	107.7	107.4	112.9	112.1
800.0	106.9	106.5	105.9	105.2	110.8	109.5
1000.0	104.6	103.7	103.7	101.8	109.0	106.3
1250.0	104.7	103.6	102.4	100.4	106.1	101.5
1600.0	101.4	97.9	98.9	0.0	103.4	0.0
2000.0	97.1	94.5	96.1	90.0	99.6	0.0
2500.0	97.4	91.9	94.8	0.0	98.5	0.0
3150.0	97.1	0.0	97.9	0.0	97.2	0.0
4000.0	93.4	0.0	93.3	0.0	94.1	0.0
5000.0	93.7	0.0	90.1	0.0	90.9	0.0
6300.0	94.7	0.0	90.8	0.0	89.0	0.0
8000.0	87.9	0.0	88.3	0.0	85.7	0.0

BLADE PASSAGE HARMONICS	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	100.2	99.5	112.1
2	107.1	94.3	115.7
3	107.5	95.1	120.3
4	111.1	106.5	116.8
5	106.8	113.9	112.4
6	113.2	99.5	108.4
7	118.7	111.0	106.3
8	102.8	117.3	116.4
9	112.2	107.6	108.3
10	115.8	104.9	101.1



XH-59A ACOUSTIC DATA

RJN 25	POINT 8	VELOCITY 104.8	ALPHA 7.5	CLR/S,R 0.116004	MU 0.2988	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	75.9	0.0	85.5	81.3	93.8	91.9
12.5	79.6	74.4	77.8	0.0	90.2	87.0
16.0	101.7	101.6	109.7	109.7	110.5	110.4
20.0	92.1	90.4	100.4	99.7	95.8	0.0
25.0	82.9	0.0	84.6	0.0	96.0	0.0
31.5	109.0	109.0	99.8	99.4	117.7	117.6
40.0	89.2	0.0	96.9	94.4	101.3	0.0
50.0	111.9	111.8	99.1	97.1	122.5	122.5
63.0	105.9	105.5	113.7	113.6	122.5	122.4
80.0	111.0	110.8	119.6	119.5	114.8	114.4
100.0	116.0	115.9	111.3	111.0	108.6	106.4
125.0	108.9	108.4	115.0	114.8	112.9	112.2
160.0	117.0	116.9	113.8	113.6	113.1	112.5
200.0	112.3	112.1	113.6	113.4	116.4	116.1
250.0	117.0	117.0	113.1	113.0	115.6	115.3
315.0	113.7	113.6	113.9	113.8	117.7	117.4
400.0	111.6	111.7	110.6	110.4	115.4	114.9
500.0	108.4	108.1	107.9	107.5	115.7	115.3
630.0	106.2	105.8	104.1	103.3	112.4	111.5
800.0	103.5	102.6	103.7	102.5	109.1	107.1
1000.0	101.6	99.7	101.7	98.3	108.1	104.8
1250.0	101.7	99.3	99.7	95.1	106.4	102.7
1600.0	98.2	0.0	98.2	0.0	103.8	0.0
2000.0	94.6	88.4	95.2	85.6	100.2	0.0
2500.0	95.4	0.0	93.9	0.0	98.3	0.0
3150.0	96.4	0.0	98.7	0.0	98.1	0.0
4000.0	92.5	0.0	93.2	0.0	94.9	0.0
5000.0	89.1	0.0	89.7	0.0	91.8	0.0
6300.0	94.0	0.0	90.8	0.0	89.8	0.0
8000.0	87.9	0.0	87.7	0.0	86.7	0.0

ELADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	102.1	110.1	110.5
2	109.0	99.6	117.5
3	111.7	96.8	122.5
4	105.3	113.5	122.4
5	110.7	119.4	114.3
6	115.8	109.3	99.8
7	106.4	111.6	110.9
8	102.9	112.6	108.0
9	112.6	108.4	109.1
10	113.7	99.2	102.4

XH-59A ACOUSTIC DATA

ORIGINAL DATA IS  
OF FOOT COUNTRY

RUN	POINT	VELOCITY	ALPHA	CLR/S.R	MU
23	13	107.0	7.5	0.131272	0.3003

1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	87.4	86.7	90.2	89.1	97.8	97.1
12.5	84.3	83.1	74.9	0.0	97.8	97.3
16.0	105.7	105.7	105.9	105.8	114.8	114.8
20.0	99.6	99.3	99.7	98.8	107.8	107.4
25.0	90.3	89.1	86.6	0.0	103.3	102.1
31.5	109.5	104.5	105.0	104.9	117.4	117.3
40.0	91.5	0.0	94.3	86.3	106.1	103.5
50.0	113.1	113.0	104.4	103.8	125.8	125.8
63.0	115.6	115.6	111.9	111.8	123.8	123.8
80.0	107.6	107.1	120.2	120.1	118.2	118.0
100.0	120.8	120.8	112.6	112.4	115.6	115.2
125.0	116.8	116.7	117.2	117.1	117.1	116.8
160.0	118.2	118.2	119.2	119.2	116.0	115.6
200.0	114.3	114.2	115.6	115.5	119.4	119.2
250.0	120.0	120.0	116.5	116.4	117.0	117.7
315.0	119.5	119.5	118.7	118.7	120.8	120.7
400.0	115.4	115.3	113.3	113.2	118.3	118.1
500.0	111.4	111.3	110.5	110.3	116.1	115.7
630.0	109.8	109.6	108.5	108.2	114.2	113.6
800.0	107.7	107.4	106.4	105.8	109.8	108.0
1000.0	104.9	104.1	104.4	102.8	109.3	106.9
1250.0	104.5	103.4	103.2	101.6	107.5	104.7
1600.0	101.6	98.4	100.2	0.0	105.9	101.0
2000.0	98.2	96.3	98.0	95.1	103.1	98.9
2500.0	98.5	94.9	96.5	88.2	101.3	95.1
3150.0	98.2	0.0	97.7	0.0	99.8	0.0
4000.0	92.9	0.0	94.1	0.0	96.6	0.0
5000.0	94.0	0.0	90.7	0.0	93.6	0.0
6300.0	94.6	0.0	91.2	0.0	91.1	0.0
8000.0	87.2	0.0	88.2	0.0	87.7	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	106.6	106.8	115.5
2	109.4	104.9	117.2
3	113.0	103.7	125.8
4	115.5	111.2	123.8
5	106.4	120.1	117.7
6	120.7	111.7	114.6
7	114.9	110.9	105.5
8	110.8	115.6	115.1
9	113.0	117.3	109.6
10	115.9	113.8	106.8

XH-59A ACCUSTIC DATA

RUN 25	PLINT 9	VELOCITY 104.3	ALPHA 7.5	CLR/S,R 0.137698	MU 0.2946	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	75.4	68.6	86.0	82.5	93.0	90.7
12.5	76.4	0.0	83.3	80.1	83.3	0.0
16.0	107.8	107.8	115.9	115.9	117.8	117.8
20.0	96.5	96.0	104.6	104.4	109.4	109.1
25.0	84.6	0.0	87.5	0.0	99.8	97.0
31.5	111.7	111.7	101.6	101.3	118.9	118.9
40.0	95.2	89.3	96.8	94.3	106.2	104.0
50.0	110.1	110.0	104.8	104.4	121.4	121.3
63.0	101.6	100.6	111.4	111.3	119.1	119.0
80.0	104.0	102.9	116.5	116.4	118.4	118.2
100.0	112.3	112.1	108.7	108.1	106.1	100.9
125.0	115.2	115.1	116.6	116.5	113.0	113.4
160.0	113.0	112.8	116.4	116.3	113.0	112.3
200.0	110.3	110.0	112.7	112.5	117.0	116.7
250.0	112.4	112.3	111.9	111.8	119.2	119.1
315.0	113.4	113.3	112.2	112.1	119.1	118.9
400.0	111.5	111.4	110.9	110.7	117.2	116.9
500.0	106.8	106.4	108.3	107.9	113.7	113.0
630.0	105.7	103.1	105.3	104.7	111.8	110.8
800.0	101.4	99.9	103.0	101.5	108.9	106.9
1000.0	100.2	97.3	100.3	94.4	107.0	102.2
1250.0	101.4	98.8	100.0	96.0	106.0	101.8
1600.0	97.7	0.0	98.1	0.0	103.7	0.0
2000.0	94.2	86.5	95.1	85.0	99.8	0.0
2500.0	95.2	0.0	94.3	0.0	98.1	0.0
3150.0	99.0	0.0	98.4	0.0	98.5	0.0
4000.0	92.7	0.0	93.2	0.0	94.5	0.0
5000.0	89.2	0.0	89.6	0.0	92.4	0.0
6300.0	93.6	0.0	90.1	0.0	90.0	0.0
8000.0	87.9	0.0	87.2	0.0	87.3	0.0

BLADE PASSAGE HARMONICS	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	108.1	116.2	118.3
2	111.7	101.2	118.8
3	109.8	104.2	121.3
4	99.2	111.1	118.9
5	101.9	116.5	118.2
6	111.9	108.0	100.0
7	113.5	112.2	109.4
8	108.7	114.0	110.3
9	110.9	115.8	106.1
10	104.7	98.0	103.8

XH-59A ACOUSTIC DATA

ORIGINAL DATA  
OF FOUR (2) 1.7

RUN	PLINT	VELOCITY	ALPHA	CLR/S,R	MU
23	16	143.0	2.5	0.079327	0.3993

1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBJ	DBC	DBL	DBC	DBU	DBC
10.0	76.3	0.0	88.9	83.1	92.1	0.0
12.5	75.5	0.0	85.3	78.5	98.6	97.2
16.0	100.2	100.0	105.6	105.5	113.5	113.4
20.0	99.8	99.2	105.7	105.3	106.8	105.1
25.0	97.1	95.5	102.6	101.6	104.9	101.0
31.5	102.5	102.1	105.6	105.2	116.0	115.7
40.0	103.0	101.3	96.7	0.0	106.7	0.0
50.0	98.2	0.0	100.2	0.0	116.9	116.3
63.0	116.5	116.4	115.3	115.2	114.8	113.5
80.0	109.7	108.8	113.4	112.6	118.7	118.0
100.0	111.7	110.9	112.3	111.5	113.0	109.4
125.0	112.9	112.5	117.2	117.0	114.1	111.8
160.0	109.5	108.7	112.6	112.0	113.3	110.5
200.0	112.4	111.8	110.2	109.1	118.0	117.1
250.0	111.1	110.5	110.1	109.3	115.4	114.0
315.0	110.0	109.6	110.2	109.7	116.5	115.3
400.0	107.1	106.3	109.2	108.6	116.4	115.3
500.0	105.8	104.8	105.9	104.6	112.6	109.4
630.0	103.2	101.4	103.1	100.6	111.5	106.4
800.0	100.1	93.6	101.6	95.9	110.6	105.1
1000.0	102.1	98.8	107.0	105.7	110.0	98.4
1250.0	101.7	95.4	101.4	0.0	109.4	100.1
1600.0	99.8	0.0	100.2	0.0	107.3	0.0
2000.0	97.0	88.7	97.9	84.4	105.0	0.0
2500.0	97.0	0.0	96.9	0.0	102.6	0.0
3150.0	98.8	0.0	98.1	0.0	100.7	0.0
4000.0	93.0	0.0	94.4	0.0	96.9	0.0
5000.0	91.5	0.0	91.8	0.0	93.2	0.0
6300.0	91.5	0.0	91.3	0.0	90.5	0.0
8000.0	86.4	0.0	87.7	0.0	88.3	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	100.9	106.5	113.9
2	102.4	105.6	115.7
3	88.8	95.8	116.2
4	116.4	115.1	113.1
5	98.6	112.4	117.2
6	110.3	110.2	106.1
7	107.1	108.2	101.1
8	110.4	116.1	105.7
9	101.6	107.5	103.9
10	98.4	102.4	109.1

XH-59A ACOUSTIC DATA

ORIGINAL PAGE IS  
OF POOR QUALITY

RUN 23	PLINT 17	VELOCITY 143.0	ALPHA 2.5	CLR/S,R 0.109872	MU 0.3992	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	79.3	0.0	91.8	89.7	89.5	0.0
12.5	81.5	74.5	83.9	0.0	96.6	94.1
16.0	101.4	101.3	99.5	99.0	115.6	115.5
20.0	98.7	98.0	104.4	103.8	112.6	112.2
25.0	98.2	97.0	102.5	101.5	107.5	105.8
31.5	105.8	105.6	109.7	109.5	118.5	118.3
40.0	102.7	100.8	96.1	0.0	109.5	105.3
50.0	100.3	82.3	101.0	0.0	118.5	118.1
63.0	115.5	115.4	116.0	115.9	113.5	111.6
80.0	105.3	102.0	110.4	108.6	120.1	119.6
100.0	114.3	113.0	115.0	114.6	113.3	110.0
125.0	112.9	112.5	118.6	118.4	114.9	113.1
160.0	112.6	112.2	112.4	111.8	114.2	112.1
200.0	113.3	112.8	113.0	112.4	117.3	116.2
250.0	112.7	112.3	113.4	113.1	116.9	115.9
315.0	112.1	111.8	112.0	111.7	117.6	116.7
400.0	110.2	109.8	111.2	110.9	116.6	115.6
500.0	105.7	104.7	107.3	106.4	114.1	112.1
630.0	104.1	102.7	105.2	103.8	112.4	108.8
800.0	101.0	96.8	103.2	100.1	110.9	105.1
1000.0	101.6	97.7	107.4	106.2	110.7	103.8
1250.0	101.8	95.8	102.7	0.0	109.9	103.1
1600.0	100.4	0.0	100.4	0.0	109.0	98.3
2000.0	96.9	87.9	98.2	88.5	106.1	0.0
2500.0	96.7	0.0	96.9	0.0	103.1	0.0
3150.0	98.8	0.0	98.8	0.0	101.0	0.0
4000.0	92.6	0.0	94.3	0.0	97.4	0.0
5000.0	93.5	0.0	91.9	0.0	94.2	0.0
6300.0	91.7	0.0	91.8	0.0	91.0	0.0
8000.0	86.2	0.0	88.4	0.0	88.2	0.0

BLADE PASSAGE HARMONICS	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	102.3	100.7	117.1
2	105.6	109.5	118.0
3	97.0	95.1	117.8
4	115.4	115.8	111.3
5	102.4	108.4	119.4
6	113.8	114.4	107.4
7	110.7	109.1	107.9
8	107.8	117.7	104.3
9	106.4	105.6	95.5
10	99.9	106.5	102.0

XH-59A ACOUSTIC DATA

RUN 30	POINT 9	VELOCITY 142.1	ALPHA 2.5	CLR/S.R 0.112681	MU 0.4027	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	84.5	81.4	88.8	82.9	93.0	0.0
12.5	76.4	0.0	85.8	80.7	90.9	0.0
16.0	117.7	117.7	122.9	122.9	115.0	114.9
20.0	107.6	107.5	114.5	114.4	109.6	108.8
25.0	95.4	92.9	106.1	105.7	107.2	105.4
31.5	108.4	108.3	100.8	99.5	121.0	120.9
40.0	104.3	103.1	102.9	101.5	109.8	106.2
50.0	114.0	113.8	112.7	112.4	110.8	107.4
63.0	114.0	112.9	117.7	117.6	124.5	124.4
80.0	110.6	109.9	119.1	118.9	117.5	116.6
100.0	113.8	113.4	110.4	109.2	115.2	113.4
125.0	116.4	116.2	113.1	112.5	114.3	112.2
160.0	115.4	115.2	113.9	113.5	114.4	112.5
200.0	113.1	112.6	116.9	116.7	117.4	116.3
250.0	114.1	113.8	112.6	112.2	116.6	115.6
315.0	114.1	113.9	111.7	111.3	120.3	119.8
400.0	111.5	111.2	112.5	112.2	117.4	116.6
500.0	106.4	107.9	109.0	108.4	116.9	116.0
630.0	107.3	106.7	108.0	107.3	113.2	110.5
800.0	103.5	101.7	104.4	102.3	112.6	109.7
1000.0	102.5	99.7	107.8	106.7	111.6	107.3
1250.0	102.1	97.0	103.9	97.6	112.1	109.4
1600.0	101.1	92.6	102.0	0.0	109.8	103.9
2000.0	96.3	94.0	100.1	96.5	106.3	0.0
2500.0	96.8	0.0	97.5	0.0	102.6	0.0
3150.0	97.7	0.0	97.2	0.0	100.7	0.0
4000.0	101.6	100.0	104.2	103.1	102.7	95.5
5000.0	91.6	0.0	93.9	0.0	96.4	0.0
6300.0	90.2	0.0	91.1	0.0	92.1	0.0
8000.0	90.3	0.0	96.0	0.0	90.0	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	118.1	123.2	115.5
2	106.4	100.4	121.0
3	113.5	112.5	109.6
4	113.4	117.6	124.2
5	108.9	118.7	116.5
6	112.1	108.7	113.4
7	106.5	105.8	106.3
8	114.7	108.7	109.8
9	109.8	109.2	102.0
10	110.9	109.0	107.4

ORIGINAL PAGE IS  
OF POOR QUALITY

XH-59A ACOUSTIC DATA

RUN 24	POINT 6	VELOCITY 140.9	ALPHA 5.0	CLR/S,R 0.078550	MU 0.4026	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	79.4	0.0	89.3	84.8	90.4	0.0
12.5	73.3	0.0	88.7	86.8	94.1	88.5
16.0	108.2	108.2	117.8	117.8	118.3	118.3
20.0	99.3	98.7	107.8	107.5	108.2	107.1
25.0	95.6	92.3	102.1	101.0	103.1	95.0
31.5	100.7	100.0	99.6	97.8	121.3	121.2
40.0	104.5	103.4	94.1	0.0	108.9	104.1
50.0	104.6	102.8	112.3	112.0	117.4	116.9
63.0	109.9	109.5	120.7	120.7	116.4	115.6
80.0	104.2	99.7	118.2	118.0	115.6	114.2
100.0	114.8	114.5	107.0	103.8	115.0	113.2
125.0	112.9	112.5	115.5	115.2	115.3	113.8
160.0	119.1	119.0	117.6	117.4	115.2	113.7
200.0	114.8	114.5	115.9	115.6	118.9	118.2
250.0	118.3	118.2	115.0	114.8	118.2	117.6
315.0	118.4	118.3	116.6	116.5	120.5	120.1
400.0	117.0	116.9	113.2	113.0	117.1	116.2
500.0	111.7	111.5	108.5	107.8	115.6	114.3
630.0	107.4	106.8	107.0	106.2	113.6	111.3
800.0	104.1	102.6	103.7	101.2	111.1	106.3
1000.0	103.3	101.1	107.4	106.2	111.2	106.3
1250.0	101.5	94.9	102.3	0.0	110.3	105.3
1600.0	99.8	0.0	101.1	0.0	109.3	102.1
2000.0	97.9	92.0	98.0	87.8	106.2	0.0
2500.0	96.3	0.0	96.3	0.0	102.0	0.0
3150.0	99.5	0.0	98.8	0.0	100.6	0.0
4000.0	92.6	0.0	94.5	0.0	97.6	0.0
5000.0	90.6	0.0	91.4	0.0	94.4	0.0
6300.0	94.3	0.0	91.7	0.0	91.2	0.0
8000.0	87.1	0.0	87.9	0.0	88.0	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	108.4	118.0	118.6
2	100.4	98.4	121.2
3	103.2	112.1	117.0
4	109.4	120.6	115.6
5	94.3	117.7	114.3
6	112.7	102.5	103.5
7	113.8	101.1	110.6
8	101.4	114.9	112.0
9	110.2	113.3	107.0
10	118.0	110.7	111.5

XH-59A ACOUSTIC DATA

RUN 24	POINT 7	VELOCITY 140.9	ALPHA 5.0	CLR/S,R 0.113114	MU 0.3940	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	84.0	80.3	92.8	91.3	99.7	98.2
12.5	71.0	0.0	89.9	88.6	94.9	90.9
16.0	107.0	107.0	110.1	110.1	115.1	115.0
20.0	102.6	102.3	105.6	105.2	110.8	110.2
25.0	98.2	97.2	102.7	101.8	104.7	100.9
31.5	105.3	105.1	110.5	110.4	119.3	119.2
40.0	106.0	105.3	97.1	0.0	110.9	108.5
50.0	106.0	104.8	106.7	105.4	118.1	117.7
63.0	119.7	119.7	118.1	118.0	116.9	116.2
80.0	106.9	105.1	119.3	119.1	118.4	117.7
100.0	115.3	115.0	117.0	116.8	113.7	111.1
125.0	116.1	115.9	116.8	116.6	114.6	112.8
160.0	111.6	111.1	116.8	116.6	115.6	114.3
200.0	114.4	114.0	111.5	110.7	118.8	118.1
250.0	113.5	113.2	111.7	111.2	116.4	115.4
315.0	112.1	111.8	111.7	111.3	117.0	116.0
400.0	106.9	106.1	110.6	110.2	115.8	114.6
500.0	106.5	105.7	107.1	106.2	115.4	114.1
630.0	104.5	103.3	104.8	103.3	112.7	109.7
800.0	102.3	99.7	102.3	98.2	111.8	108.2
1000.0	103.0	100.6	106.5	105.0	111.7	107.7
1250.0	101.5	94.9	101.5	0.0	110.2	105.0
1600.0	100.2	0.0	100.4	0.0	109.3	102.1
2000.0	97.4	91.3	98.0	87.8	105.7	0.0
2500.0	95.3	0.0	96.3	0.0	102.7	0.0
3150.0	98.6	0.0	99.3	0.0	100.3	0.0
4000.0	92.9	0.0	94.5	0.0	97.4	0.0
5000.0	91.6	0.0	91.7	0.0	94.6	0.0
6300.0	92.7	0.0	91.9	0.0	91.0	0.0
8000.0	86.6	0.0	88.2	0.0	87.8	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	108.0	110.9	115.7
2	105.0	110.3	119.2
3	104.6	106.4	117.9
4	119.7	118.0	115.8
5	90.5	118.9	116.5
6	114.6	116.9	107.4
7	97.2	106.2	111.0
8	115.7	115.9	102.2
9	102.5	110.2	103.9
10	102.4	114.9	113.7



XH-59A ACOUSTIC DATA

RUN 24	POINT 8	VELOCITY 141.2	ALPHA 5.0	CLR/S,R 0.125296	MU 0.3960	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBL	DBC	DBU	DBC
10.0	82.8	76.7	74.6	0.0	94.0	0.0
12.5	74.8	0.0	88.3	86.2	95.0	91.1
16.0	101.6	101.5	101.0	100.7	115.2	115.1
20.0	97.6	96.6	105.3	104.8	108.8	107.9
25.0	96.8	95.2	103.3	102.5	104.3	99.8
31.5	108.7	106.6	110.2	110.1	117.9	117.7
40.0	104.2	103.0	99.3	95.2	108.4	102.3
50.0	106.1	104.9	108.6	107.8	117.4	116.9
63.0	118.5	118.5	118.3	118.2	117.2	116.5
80.0	110.4	109.7	118.4	118.2	120.8	120.4
100.0	116.8	116.6	115.0	114.6	113.0	109.7
125.0	115.2	115.0	122.3	122.2	114.0	111.8
160.0	112.3	111.9	117.3	117.1	114.7	113.0
200.0	114.5	114.1	113.4	112.9	117.8	116.9
250.0	113.5	113.2	115.1	114.9	118.5	117.9
315.0	111.4	111.1	112.5	112.2	116.5	115.3
400.0	109.2	108.7	111.8	111.5	116.9	116.0
500.0	107.1	106.4	107.5	106.7	113.8	111.7
630.0	105.3	104.3	105.8	104.7	113.2	110.6
800.0	102.6	100.2	104.1	101.9	111.0	106.0
1000.0	103.2	101.0	106.9	105.6	111.1	106.0
1200.0	101.8	96.1	102.2	0.0	110.8	106.7
1600.0	100.9	91.2	100.8	0.0	108.5	91.3
2000.0	97.7	92.4	98.3	90.1	105.1	0.0
2500.0	96.7	0.0	96.7	0.0	102.6	0.0
3150.0	99.7	0.0	97.7	0.0	99.9	0.0
4000.0	94.1	0.0	94.7	0.0	97.6	0.0
5000.0	92.6	0.0	91.9	0.0	94.2	0.0
6300.0	93.3	0.0	91.2	0.0	90.9	0.0
8000.0	86.6	0.0	87.5	0.0	87.9	0.0

BLADE PASSAGE HARMONICS	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	102.3	101.6	116.0
2	108.6	110.0	117.9
3	105.0	108.2	117.0
4	118.5	118.3	116.7
5	109.8	118.0	120.5
6	116.2	114.5	109.4
7	110.3	109.5	111.4
8	113.0	121.8	105.8
9	106.3	115.7	105.3
10	108.0	109.8	105.2

XH-59A ACOUSTIC DATA

ORIGINAL PAGE IS  
OF FOUR QUALITY

RUN 24	POINT 9	VELOCITY 142.4	ALPHA 7.5	CLR/S.R 0.090290	MU 0.4004	
1/3 OCTAVE CENTER FREQUENCY	MICROPHONE 2		MICROPHONE 4		MICROPHONE 7	
	DBU	DBC	DBU	DBC	DBU	DBC
10.0	79.6	0.0	86.6	0.0	87.6	0.0
12.5	82.0	76.6	82.7	0.0	91.2	0.0
16.0	112.6	112.6	119.2	119.2	115.0	114.9
20.0	105.2	105.0	111.2	111.1	108.4	107.3
25.0	98.4	97.3	100.1	98.1	101.3	0.0
31.5	106.8	106.6	102.7	101.9	113.4	112.8
40.0	100.4	96.6	100.6	97.9	110.6	107.8
50.0	108.5	107.8	112.1	111.7	116.4	115.7
63.0	114.9	114.8	114.7	114.5	111.3	107.4
80.0	102.9	92.8	117.2	116.9	116.3	115.1
100.0	114.4	114.0	113.5	112.9	116.3	115.0
125.0	111.2	110.6	115.9	115.6	114.9	113.2
160.0	117.7	117.6	114.6	114.2	113.6	111.1
200.0	114.6	114.2	112.2	111.5	115.3	113.4
250.0	111.3	110.8	114.8	114.6	117.8	117.1
315.0	116.1	116.0	114.7	114.5	118.4	117.7
400.0	113.3	113.1	113.9	113.7	117.5	116.7
500.0	111.8	111.6	110.2	109.8	116.2	115.1
630.0	108.3	107.8	107.2	106.4	114.2	112.2
800.0	106.8	106.0	104.5	102.5	111.6	107.4
1000.0	104.2	102.5	108.2	107.2	111.4	106.6
1250.0	103.9	101.2	103.2	93.0	110.7	106.2
1600.0	101.1	92.5	100.9	0.0	108.9	97.8
2000.0	98.2	93.7	98.2	88.8	105.3	0.0
2500.0	97.0	0.0	96.3	0.0	102.2	0.0
3150.0	98.9	0.0	100.7	0.0	100.2	0.0
4000.0	93.1	0.0	94.0	0.0	97.0	0.0
5000.0	91.4	0.0	91.8	0.0	94.0	0.0
6300.0	94.1	0.0	91.2	0.0	91.0	0.0
8000.0	85.8	0.0	86.4	0.0	87.4	0.0

BLADE  
PASSAGE  
HARMONICS

	MICROPHONE 2	MICROPHONE 4	MICROPHONE 7
1	113.3	119.8	115.8
2	106.8	107.6	113.0
3	107.7	111.7	116.1
4	114.7	114.0	108.0
5	96.3	115.5	114.8
6	113.8	112.5	112.3
7	104.9	109.9	109.9
8	108.1	113.7	109.5
9	113.4	111.2	101.8
10	112.4	107.6	104.7

## REFERENCES

1. Ruddell, Andrew J., "Advancing Blade Concept (ABC)<sup>TM</sup> Development, Paper No. 1012, Presented at the 32nd AHS National Forum, Washington, D.C., May 1976.
2. Ruddell, Andrew J. and Macrino, John A., "Advancing Blade Concept (ABC)<sup>TM</sup> High Speed Development," Paper No. 80-57, presented at the 36th AHS National Forum, Washington, D.C., May 1980.
3. Felker, Fort F., "Performance and Loads Data from a Wind Tunnel Test of a Full-Scale, Coaxial, Hingeless Rotor Helicopter," NASA TM 81329, October 1981.

ORIGINAL PAGE IS  
OF POOR QUALITY

TABLE 1.- DESCRIPTION OF ABC ROTOR

Item	Specification
Rotor radius, R	5.5 m
Number of rotors	2
Blades per rotor	3
Rotor separation	0.76 m
Blade tip chord	0.29 m
Blade taper ratio	2:1
Blade twist (nonlinear)	-10°
Solidity, $\sigma$	0.13
Reference area, S	12.0 m <sup>2</sup>
Blade precone angle	3°
Blade prelag angle	1.4°
Shaft tilt	0°

ORIGINAL PAGE IS  
OF POOR QUALITY

TABLE 2.- OPERATING CONDITIONS

Parameter	Rotor-on	Rotor-off
$\Omega R$ , m/sec	180 to 206	---
$M_{tip}$	0.52 to 0.58	---
V, knots	89 to 160	60 to 180
$\mu$	0.23 to 0.45	---
$M_{at}$	0.65 to 0.76	---
$\alpha$ , deg	0 to 10	-10 to 10
$C_{LR}/\sigma R$	0.024 to 0.162	---
$C_p/\sigma$	0.0002 to 0.0093	---

TABLE 3.- MICROPHONE LOCATIONS AS REFERENCED  
FROM MIDWAY BETWEEN HUBS

Microphone	x, m	y, m	z, m	r, m	$\phi$ , deg	$\psi$ , deg
1	15.9	-5.5	-3.9	17.3	13.0	160.0
2	15.9	0.0	-3.9	16.4	13.7	180.0
3	15.9	5.5	-3.9	17.3	13.0	200.0
4	5.6	5.2	-4.8	9.0	32.3	223.0
5	17.8	-3.0	-7.3	19.4	22.0	170.3
6	5.1	-4.9	-7.3	10.2	45.9	136.3
7	-3.1	7.0	-7.3	10.6	43.5	294.0

TABLE 4.- EFFECT OF CONTROL POSITIONS ON NOISE

Run/pt	$\theta$ , deg	$\Delta\theta$ , deg	$C_{LR/\sigma, R}$	Mic 2, dBA	Mic 4, dBA	Mic 7, dBA
89 knots, $\alpha = 7.5^\circ$						
21/11	7.63	0.75	0.074	107.4	109.3	113.2
21/12	7.65	.75	.074	107.8	109.0	113.2
21/13	8.98	.70	.090	109.4	110.4	112.9
21/14	11.46	.36	.119	109.9	111.5	114.9
21/15	13.54	-.01	.141	110.5	112.0	116.7
106 knots, $\alpha = 7.5^\circ$						
25/6	7.79	2.44	0.067	109.8	109.2	114.9
23/12	10.01	-.69	.093	118.0	116.6	119.4
25/7	12.23	.37	.106	117.0	115.8	118.6
25/5	11.69	-1.30	.107	116.7	114.8	118.4
25/8	12.26	.36	.116	114.8	113.5	118.3
23/14	13.23	-.27	.117	117.8	115.6	119.3
23/13	15.06	-1.52	.131	118.8	117.4	120.6
25/9	12.35	.39	.138	113.0	113.3	118.7




Figure 1.- ABC Rotor installed in 40- by 80-Foot Wind Tunnel.

ORIGINAL PAGE IS  
OF POOR QUALITY




Figure 2.- Microphone locations.

ORIGINAL PAGE IS  
OF POOR QUALITY




Figure 3.- Schematic of data acquisition set-up.






Figure 4.- Schematic of data reduction set-up.






(a) In front of the rotor, microphone 2.



(b) Under the rotor, microphone 4.


Figure 5.- Corrected sound pressure level as a function of isolated rotor lift coefficient, velocity = 89 knots.

ORIGINAL PAGE IS  
OF POOR QUALITY



(c) Under the rotor, microphone 7.


Figure 5.- Concluded.




(a) In front of the rotor, microphone 2.

Figure 6.- Corrected sound pressure level as a function of isolated rotor lift coefficient, velocity = 106 knots.

ORIGINAL PAGE IS  
OF POOR QUALITY




(b) Under the rotor, microphone 4.




(c) Under the rotor, microphone 7.

Figure 6.- Concluded.




(a) In front of the rotor, microphone 2.



(b) Under the rotor, microphone 4.


Figure 7.- Corrected sound pressure level as a function of isolated rotor lift coefficient, velocity = 142 knots.

ORIGINAL PAGE IS  
OF POOR QUALITY



(c) Under the rotor, microphone 7.


Figure 7.- Concluded.




(a) In front of the rotor, microphone 2.

Figure 8.- Corrected sound pressure level as a function of isolated rotor lift coefficient,  $\alpha = 2.5^\circ$ .

ORIGINAL PAGE IS  
OF POOR QUALITY




(b) Under the rotor, microphone 4.




(c) Under the rotor, microphone 7.

Figure 8.- Concluded.




(a) In front of the rotor, microphone 2.




(b) Under the rotor, microphone 4.

Figure 9.- Corrected sound pressure level as a function of isolated rotor lift coefficient,  $\alpha = 5.0^\circ$ .



(c) Under the rotor, microphone 7.


Figure 9.- Concluded.




(a) In front of the rotor, microphone 2.

Figure 10.- Corrected sound pressure level as a function of isolated rotor lift coefficient,  $\alpha = 7.5^\circ$ .






(b) Under the rotor, microphone 4.



(c) Under the rotor, microphone 7.

Figure 10.- Concluded.

ORIGINAL PAGE IS  
OF POOR QUALITY



(a) In front of the rotor, microphone 2.

Figure 11.- One-third octave spectra as a function of isolated rotor lift coefficient, velocity = 89 knots,  $\alpha = 2.5^\circ$ .

ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA


CORRECTED DATA  
SYMBOL

CLR/ $\sigma$ , R

RUN	28	PT	6	MIC	4
RUN	28	PT	7	MIC	4
RUN	28	PT	8	MIC	4

□
○
△


0.082
0.109
0.150



(b) Under the rotor, microphone 4.

Figure 11.- Continued.

ORIGINAL PAGE IS  
OF POOR QUALITY



(c) Under the rotor, microphone 7.

Figure 11.- Concluded.


ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA

RUN	21	PT	18	MIC	2
RUN	29	PT	9	MIC	2
RUN	30	PT	6	MIC	2
RUN	21	PT	10	MIC	2

CORRECTED DATA  
SYMBOL

$C_{LR}/\sigma \cdot R$
0.093
0.116
0.128
0.139



(a) In front of the rotor, microphone 2.

Figure 12.- One-third octave spectra as a function of isolated rotor lift coefficient, velocity = 89 knots,  $\alpha = 5.0^\circ$ .


ORIGINAL SOURCE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA

CORRECTED DATA  
SYMBOL

CLR/a, R

RUN	21	PT	18	MIC	4	□	0.093
RUN	29	PT	9	MIC	4	○	0.116
RUN	30	PT	6	MIC	4	△	0.128
RUN	21	PT	10	MIC	4	•	0.139



(b) Under the rotor, microphone 4.


Figure 12.- Continued.

1/3 OCTAVE SPECTRA

CORRECTED DATA  
SYMBOL


CLR/σ, R

RUN	21	PT	18	MIC	7	□	0.093
RUN	29	PT	9	MIC	7	○	0.116
RUN	30	PT	6	MIC	7	△	0.128
RUN	21	PT	10	MIC	7	+	0.139



(c) Under the rotor, microphone 7.

Figure 12.- Concluded.




(a) In front of the rotor, microphone 2.

Figure 13.- One-third octave spectra as a function of isolated rotor lift coefficient, velocity = 89 knots,  $\alpha = 7.5^\circ$ .



ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA				CORRECTED DATA		C <sub>LR/a</sub> R
RUN	PT	PT	MIC	SYMBOL		
RUN 21	PT 12	MIC 4	□	0.074		
RUN 29	PT 6	MIC 4	○	0.099		
RUN 29	PT 10	MIC 4	△	0.124		
RUN 29	PT 11	MIC 4	+	0.162		



(b) Under the rotor, microphone 4.

Figure 13.- Continued.


ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA

CORRECTED DATA  
SYMBOL

$C_{LR/\sigma, R}$   
0.074  
0.099  
0.124  
0.162

RUN	21	PT	12	MIC	7	□
RUN	29	PT	6	MIC	7	○
RUN	29	PT	1C	MIC	7	△
RUN	29	PT	11	MIC	7	•



(c) Under the rotor, microphone 7.

Figure 13.- Concluded.

C-2


ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA

CORRECTED DATA  
SYMBOL

$C_{LH}/\sigma \cdot R$

RUN	21	PT	19	MIC	2	□	0.069
RUN	23	PT	9	MIC	2	○	0.114
RUN	23	PT	10	MIC	2	△	0.135
RUN	23	PT	11	MIC	2	+	0.145



(a) In front of the rotor, microphone 2.

Figure 14.- One-third octave spectra as a function of isolated rotor lift coefficient, velocity = 106 knots,  $\alpha = 5.0^\circ$ .


ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA

RUN	21	PT	19	MIC	4
RUN	23	PT	9	MIC	4
RUN	23	PT	10	MIC	4
RUN	23	PT	11	MIC	4

CORRECTED DATA  
SYMBOL


□	0.089
○	0.114
△	0.135
•	0.145



(b) Under the rotor, microphone 4.

Figure 14.- Continued.

ORIGINAL PAGE IS  
OF POOR QUALITY



(c) Under the rotor, microphone 7.

Figure 14.- Concluded.


ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA

CORRECTED DATA  
SYMBOL

CLR/ $\sigma$ , R

RUN	25	PT	6	MIC	2	□	0.067
RUN	23	PT	12	MIC	2	○	0.093
RUN	23	PT	13	MIC	2	△	0.131
RUN	25	PT	9	MIC	2	*	0.138



(a) In front of the rotor, microphone 2.

Figure 15.- One-third octave spectra as a function of isolated rotor lift coefficient, velocity = 106 knots,  $\alpha = 7.5^\circ$ .

ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA

CORRECTED DATA  
SYMBOL

CLR/ $\sigma$ , R

RUN	25	PT	6	MIC	4
RUN	23	PT	12	MIC	4
RUN	23	PT	13	MIC	4
RUN	25	PT	9	MIC	4

○

0.067

○


0.093

△

0.131

+

0.138



(b) Under the rotor, microphone 4.

Figure 15.- Continued.


ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA

CORRECTED DATA  
SYMBOL

$C_{LR/\sigma, R}$

RUN	25	PT	6	MIC	7	□	0.067
RUN	23	PT	12	MIC	7	○	0.093
RUN	23	PT	13	MIC	7	△	0.131
RUN	25	PT	9	MIC	7	+	0.138




(c) Under the rotor, microphone 7.

Figure 15.- Concluded.



ORIGINAL PAGE IS  
OF POOR QUALITY



(a) In front of the rotor, microphone 2.

Figure 16.- One-third octave spectra as a function of isolated rotor lift coefficient, velocity = 142 knots,  $\alpha = 2.5^\circ$ .


ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA

CORRECTED DATA  
SYMBOL

CLR/a. R


RUN	23	PT	16	MIC	4	□	0.079
RUN	23	PT	17	MIC	4	○	0.110
RUN	23	PT	18	MIC	4	△	0.093
RUN	30	PT	9	MIC	4	•	0.113



(b) Under the rotor, microphone 4.

Figure 16.- Concluded.

ORIGINAL PAGE IS  
OF POOR QUALITY



(a) In front of the rotor, microphone 2.

Figure 17.- One-third octave spectra as a function of isolated rotor lift coefficient, velocity = 142 knots,  $\alpha = 5.0^\circ$ .

ORIGINAL PAGE IS  
OF POOR QUALITY

1/3 OCTAVE SPECTRA


CORRECTED DATA  
SYMBOL

$C_{LR}/\sigma_R$

RUN	24	PT	6	MIC	4
RUN	24	PT	7	MIC	4
RUN	24	PT	8	MIC	4

□
○
△

0.079
0.113
0.125



(b) Under the rotor, microphone 4.

Figure 17.- Continued.


ORIGINAL  
OF POOR QUALITY

1/3 OCTAVE SPECTRA

CORRECTED DATA  
SYMBOL


$C_{LR/a, R}$

RUN	24	PT	6	MIC	7	□	0.079
RUN	24	PT	7	MIC	7	○	0.113
RUN	24	PT	8	MIC	7	△	0.125




(c) Under the rotor, microphone 7.

Figure 17.- Concluded.



RUN - 28 POINT - 6 MICROPHONE - 4

(a)  $C_{LR/\sigma,R} = 0.082.$




RUN - 28 POINT - 7 MICROPHONE - 4

(b)  $C_{LR/\sigma,R} = 0.109.$

Figure 18.- Averaged time histories, velocity = 89 knots,  $\alpha = 2.5^\circ$ .


ORIGINAL PAGE IS  
OF POOR QUALITY



RUN = 28 POINT = 8 MICROPHONE = 4


(c)  $C_{LR/\sigma, R} = 0.150.$

Figure 18.- Concluded.



RUN - 21 POINT - 7 MICROPHONE - 4

(a)  $C_{LR/\sigma,R} = 0.072.$




RUN - 21 POINT - 8 MICROPHONE - 4

(b)  $C_{LR/\sigma,R} = 0.093.$


Figure 19.- Averaged time histories, velocity = 89 knots,  $\alpha = 5.0^\circ$ .





RUN = 30 POINT = 7 MICROPHONE = 4

(c)  $C_{LR/\sigma,R} = 0.104.$




RUN = 28 POINT = 8 MICROPHONE = 4

(d)  $C_{LR/\sigma,R} = 0.133.$

Figure 19.- Continued.

ORIGINAL PAGE 13  
OF POOR QUALITY




RUN = 21 POINT = 10 MICROPHONE = 4

(e)  $C_{LR/\sigma,R} = 0.139$ .


Figure 19.- Concluded.

ORIGINAL PAGE IS  
OF POOR QUALITY



RUN = 21 POINT = 11 MICROPHONE = 4

(a)  $C_{LR/\sigma, R} = 0.074$ .




RUN = 21 POINT = 13 MICROPHONE = 4

(b)  $C_{LR/\sigma, R} = 0.090$ .


Figure 20.- Averaged time histories, velocity = 89 knots,  $\alpha = 7.5^\circ$ .

ORIGINAL PAGE IS  
OF POOR QUALITY



RUN - 21 POINT - 15 MICROPHONE - 4

(c)  $C_{LR/\sigma,R} = 0.141.$




RUN - 29 POINT - 11 MICROPHONE - 4

(d)  $C_{LR/\sigma,R} = 0.162.$


Figure 20.- Concluded.

ORIGINAL PAGE IS  
OF POOR QUALITY



RUN - 23 POINT - 15 MICROPHONE - 4

Figure 21.- Averaged time histories, velocity = 106 knots,  $\alpha = 2.5^\circ$ ,  $C_{LR/\sigma,R} = 0.085$ .




RUN - 23 POINT - 9 MICROPHONE - 4

(a)  $C_{LR/\sigma,R} = 0.114$ .

Figure 22.- Averaged time histories, velocity = 106 knots,  $\alpha = 5.0^\circ$ .

ORIGINAL PAGE IS  
OF POOR QUALITY


TIME HISTORY  
18 AVERAGES



RUN - 23 POINT - 10 MICROPHONE - 4

(b)  $C_{LR/\sigma,R} = 0.135.$

TIME HISTORY  
17 AVERAGES




RUN - 23 POINT - 11 MICROPHONE - 4

(c)  $C_{LR/\sigma,R} = 0.145$

Figure 22.- Concluded.


TIME HISTORY  
30 AVERAGES



RUN - 26 POINT - 6 MICROPHONE - 4

(a)  $C_{LR/\sigma,R} = 0.066.$

TIME HISTORY  
15 AVERAGES




RUN - 23 POINT - 12 MICROPHONE - 4

(b)  $C_{LR/\sigma,R} = 0.093.$

Figure 23.- Averaged time histories, velocity = 106 knots,  $\alpha = 7.5^\circ$ .

ORIGINAL PAGE IS  
OF POOR QUALITY


TIME HISTORY  
30 AVERAGES



RUN - 25 POINT - 7 MICROPHONE - 4

(c)  $C_{LR/\sigma, R} = 0.106.$

TIME HISTORY  
30 AVERAGES




RUN - 25 POINT - 8 MICROPHONE - 4

(d)  $C_{LR/\sigma, R} = 0.116.$

Figure 23.- Continued.



ORIGINAL PAGE IS  
OF POOR QUALITY




RUN = 23 POINT = 13 MICROPHONE = 4

(e)  $C_{LR/\sigma,R} = 0.131.$


Figure 23.- Concluded.

ORIGINAL PAGE IS  
OF POOR QUALITY



RUN - 23 POINT - 18 MICROPHONE - 4

(a)  $C_{LR/\sigma,R} = 0.079$ .




RUN - 23 POINT - 18 MICROPHONE - 4

(b)  $C_{LR/\sigma,R} = 0.093$ .

Figure 24.- Averaged time histories, velocity = 142 knots,  $\alpha = 2.5^\circ$ .

ORIGINAL PAGE IS  
OF POOR QUALITY




RIJN - 30 POINT - 8 MICROPHONE - 4

(c)  $C_{LR/\sigma,R} = 0.110$ .


Figure 24.- Concluded.

ORIGINAL RECORDS  
OF POOR QUALITY



RUN - 24 POINT - 6 MICROPHONE - 4

(a)  $C_{LR/\sigma,R} = 0.079.$




RUN - 24 POINT - 7 MICROPHONE - 4

(b)  $C_{LR/\sigma,R} = 0.113.$

Figure 25.- Averaged time histories, velocity = 142 knots,  $\alpha = 5.0^\circ.$

ORIGINAL PAGE 10  
OF POOR QUALITY




RUN = 24 POINT = 8 MICROPHONE = 4

(c)  $C_{LR/\sigma,R} = 0.125$ .


Figure 25.- Continued.

ORIGINAL PAGE IS  
OF POOR QUALITY



RUN - 24 POINT - 9 MICROPHONE - 4

(a)  $C_{LR}/\sigma_R = 0.090.$



RUN - 24 POINT - 9 MICROPHONE - 4

(b)  $C_{LR}/\sigma_R = 0.90.$

Figure 26.- Averaged time histories, velocity = 142 knots,  $\alpha = 7.5^\circ$ .