# ΝΟΤΙCΕ

THIS DOCUMENT HAS BEEN REPRODUCED FROM MICROFICHE. ALTHOUGH IT IS RECOGNIZED THAT CERTAIN PORTIONS ARE ILLEGIBLE, IT IS BEING RELEASED IN THE INTEREST OF MAKING AVAILABLE AS MUCH INFORMATION AS POSSIBLE



VPI-Aero-125

## FINAL REPORT

1

l

11

I

Į

Nov. 14, 1980 - Nov. 15, 1981

NASA Langley Research Center Research Grant NAG-1-80

Computational Methods of Robust Controller Design for Aerodynamic Flutter Suppression

L. R. Anderson, Principal Investigator Department of Aerospace and Ocean Engineering Virginia Polytechnic Institute and State University Blacksburg, Virginia 24061

The NASA Technical Officer for this grant is Jerry R. Newson, Structures and Dynamics Division, NASA Langley Research Center

## Acknowledgements

i

Γ

Sincere thanks is due to Professor Dennis Brewer for the elegant mathematical proof in the second paper of this report, to my very capable graduate research assistants Mr. Rasim Baykan and Mr. Alok Das for their major contribution to this work, and to Mrs. Mary Moore and Miss Sherry Layman for their fine typing of drafts and final papers.

## TABLE OF CONTENTS

+ ; ;

i :

l

].

l

I

I

ľ

		Page	
Ι.	Introduction	4	
II.	Pole Placement and Order Reduction in Two-Time-Scale		
	Control Systems through Riccati Iteration		
	by L. R. Anderson	5	
III.	Numerical Solution of the Symmetric Riccati Equation		
	through Riccati Iteration		
	by L. R. Anderson		
	D. M. Brewer		
	A. R. Baykan	17	
IV.	A Literature Review of Robust Controller Design Methods		
	by A. Das	44	
۷.	Robust Controller Design for Large Parameter Variations		
	by L. R. Anderson	69	
VI.	Appendix A - Additional References on Robust Controller		
	Design Methods	73	

#### Introduction

The major focus of this research work has been the continuing development of "Riccati Iteration," a new numerical tool for the design and analysis of linear control systems. This report is arranged into four chapters consisting of two research papers, an extensive literature review, and a viewgraph summary of directions for future research work. The Masters degree thesis "Comparison of Algebraic Riccati Equation solvers" by Mr. Rasim Baykan was also supported by this research grant. An apology must be made for the fact that the numerical examples in chapters II and III are taken from other aerospace applications and computer-generated random cases rather than aerodynamic flutter models as originally proposed in this research effort.

ļ

į

#### POLE PLACEMENT AND ORDER REDUCTION IN TWO-TIME-SCALE CONTROL SYSTEMS THROUGH RICCATI ITERATION

Leonard R. Anderson\*

#### Abstract

A transformation of variables taken from singular perturbations may be applied to two-time-scale linear systems in state space form to reduce the system to block-diagonal form with slow and fast modes decoupled. The transformation is easily computed by applying the new "Riccati Iteration." The iteration yields a solution to the nonsymmetric algebraic Riccati equation obtained by partitioning the original system matrix A. The numerical procedure is initiated with the trivial iterate Lo = 0, and is <u>globally</u> convergent to the desired unique time scale decoupling solution.

After transformation, the decoupled system may be used in controller design to achieve exact clused-loop pole placement in the slow subsystem without altering the poles of the fast subsystem. The decoupled form may also be used to reduce system order by sitting a small parameter to zero. Provided the fast subsystem is stable, the order reduction can be expected to yield a good approximation to the original system. These methods are demonstrated using the 16th order linear model of a turbofan engine.

This paper was presented at the 3rd International Conference on Mathematical Conference, University of Southern California, July 29-31, 1981 and has been accepted for publication in <u>Mathematical Modeling</u>.

\* Assist. Prof., Aerospace and Ocean Eng. Dept., VPI & SU

#### 1. INTRODUCTION

100

5

「こうちんなから」というないのであるというないないないないというというでもないできたないというない

Large scale linear control systems are encountered frequently in engineering problems such as the design of high performance aircraft<sup>1,2</sup>, large space structures<sup>3</sup>, or power systems<sup>4</sup>. A recurring theme in such problems is the need to reduce the originally high order of the system to facilitate simulation, eigenanalysis, or control system design studies. The question of order reduction has been widely researched and many order reduction schemes have been proposed<sup>5,6</sup>. The method presented here is related to the familiar eigenspace analysis of linear multivariable systems, but is particularly well suited to direct numerical implementation for large scale systems, and systems with "stiff" dynamics.

Consider the linear control system

$$x = Ax + Bu$$
(1)  
$$w = Cx + Du$$

where x, u and w are state, control and output variables of dimension n, m and l, respectively. As proposed by Chow and Kokotovic<sup>7</sup>, system (1) will be classified as <u>two-time-scale</u> if the eigenvalue spectrum of the A matrix, represented as  $\lambda(A)$ , can be separated by absolute values into nonempty sets S and F with n<sub>1</sub> and n<sub>2</sub> = n - n<sub>1</sub> elements, respectively, such that

 $|s_i| \ll |f_j|$  for all  $s_i$  in S, and  $f_j$  in F. (2)

A naturally occurring system <u>small parameter</u> is the eigenvalue ratio

$$\mu = \frac{\max_{i} |s_{i}|}{\min_{j} |f_{j}|} << 1.$$
(3)

This parameter provides a measure of the system's time scale separation and identifies (1) as a singular perturbations problem. This particular small parameter was also proposed by Kelley<sup>8</sup>.

More refined partitioning of the spectrum  $\lambda(A)$  yielding three or more time scales (i.e., eigenvalue groups) may also be considered with two or more small parameters analogous to (3). The technique described below may be applied repeatedly for such cases. Only the two-time-scale case will be considered here.

#### 2. THE LK TRANSFORMATION

Such two-time-scale systems may be conveniently transformed into decoupled subsystems by a two step transformation to new variables  $y = T_2T_1 x = T_x$  with

$$T_{I} = \begin{bmatrix} I & 0 \\ L & I \end{bmatrix}$$
(4)

$$T_{2} = \begin{bmatrix} I & K \\ 0 & I \end{bmatrix}$$
(5)  
$$T = \begin{bmatrix} I + KL & K \end{bmatrix}$$
(6)

where the I are identity matrices of dimension  $n_1$  and  $n_2$ . If the original system (1) is partitioned as

$$\begin{bmatrix} \dot{x}_1 \\ \dot{x}_2 \end{bmatrix} = \begin{bmatrix} A_{11} & A_{12} \\ A_{21} & A_{22} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} + \begin{bmatrix} B_1 \\ B_2 \end{bmatrix} u$$
(7)

I

where  $A_{11}$  is  $n_1 \times n_1$ , etc., then the new system defined by transformation (4) will be block-triangular provided the  $n_2 \times n_1$  matrix L satisfies the nonsymmetric algebraic Riccati equation (ARE)

$$LA_{11} - A_{22}L - LA_{12}L + A_{21} = 0.$$
 (8)

If, in addition the  $n_1 \ge n_2$  matrix K satisfies the Lyapunov equation

 $\tilde{KA}_{22} - \tilde{A}_{11}K + A_{12} = 0$  (9)

where  $A_{11} = A_{12}$  -  $A_{12}$ L,  $A_{22} = A_{22} + LA_{12}$ , then (7) is transformed to the block-diagonal form

$$\begin{bmatrix} y_1 \\ y_2 \end{bmatrix} = \begin{bmatrix} \tilde{A}_{11} & 0 \\ 0 & \tilde{A}_{22} \end{bmatrix} \begin{bmatrix} y_1 \\ y_2 \end{bmatrix} + \begin{bmatrix} \tilde{B}_1 \\ \tilde{B}_2 \end{bmatrix} u$$
(10)

where  $\tilde{B}_{1} = (I+KL) B_{1} + KB_{2}, \tilde{B}_{2} = LB_{1} + B_{2}$ .

Such transformations have appeared in singular perturbations work  $^{9,10,11}$  and were introduced into the controls literature by Kokotovic<sup>12</sup>. One attractive feature of transformation T is that it is always nonsingular and has the explicit inverse

T-1	×	ſ	-ĸ ]	
		L-L	I+LK	

Since  $\tilde{A}$  is similar to matrix A, the eigenvalues of A become the eigenvalues of  $\tilde{A}_{11}$  and  $\tilde{A}_{22}$ , i.e.

$$\lambda(A) = \lambda(\tilde{A}_{11}) \cup \lambda(\tilde{A}_{22}).$$

It is well known that ARE has many solutions  $^{13,14}$ . If we express the A matrix in spectral form as A = MJQ where M is a modal matrix, J is diagonal (assuming A nondefective), and Q=M<sup>-1</sup>, then solutions to ARE can be expressed

in terms of partitions of M. MJQ is partitioned conformably with (7) so that M<sub>1</sub>], J<sub>1</sub> and Q<sub>11</sub> have dimensions n<sub>1</sub> x n<sub>1</sub>, etc. It can be shown by matrix algebra that L is a solution to ARE if

1) M<sub>11</sub> is nonsingular

2) 
$$L = -M_{21}M_{11}^{-1} = Q_{22}^{-1}Q_{21}$$
 (11)

Also, if L satisfies (11), then  $A_{11} = M_{11}J_{1}M_{11}^{-1}$ . In general there will be one solution to ARE corresponding to each partition of the eigenvalues of A into  $A_{11}$  and  $A_{22}$ .

The solution L of particular interest in two-time-scale systems is the unique solution to ARE which yields

$$\lambda(\tilde{A}_{11}) = S, \quad \lambda(\tilde{A}_{22}) = F$$
 (12)

and from here on it is assumed that L satisfies ARE and (12). The Lyapunov equation (9) will have a unique solution<sup>15</sup> provided  $\tilde{A}_{11}$  and  $\tilde{A}_{22}$  have no common eigenvalues, which is guaranteed by (12). The solution K of (9) can also be expressed in terms of the modal matrix M as

 $K = M_{11}Q_{12} = -M_{12}Q_{22}$ One method of computing L is to compute n<sub>1</sub> eigenvectors  $\begin{bmatrix}
M_{11} \\
M_{21}
\end{bmatrix}$ spanning the

slow eigenspace and apply (11). However, as recently shown, 13, 16, L can be computed as the limit of the <u>Riccati Iteration</u><sup>18</sup> algorithm

$$L_{i+1} = (A_{22} + L_i A_{12})^{-1} (L_i A_{11} + A_{21})$$

initialized with  $L_0 = 0$  which is globally convergent to the desired decoupling L. If we define the residual

 $R_i = L_i A_{11} - A_{22}L_i - L_i A_{12}L_i + A_{21}$ 

then in the limit as  $i + \infty$ ,  $\frac{||R_{i+1}||}{||R_i||} + \mu$ .

Thus L is readily computed for strongly two-time-scale systems (i.e. those with very small  $\mu$ ).

#### 3. ORDER REDUCTION

The original system (1) can therefore be considered as the decoupled subsystems

$$\dot{y}_{1} = \tilde{A}_{11}y_{1} + \tilde{B}_{1}u$$
 (13a)

$$\dot{y}_2 = \tilde{A}_{22}y_2 + \tilde{B}_2 u$$
 (13b)

which model the system slow and fast dynamic parts, respectively. The appropriate initial condition for (13a, b) is y(0) = Tx(0). The decoupled form can yield a saving in simulation studies since only the fast subsystem (13b) need by integrated with a small time step. If the original system (1) is integrated directly, then one must treat the entire n<sup>th</sup> order system as fast to obtain accurate numerical solutions.

As noted above, order reduction is often required in the study of large scale systems, and this may be conveniently done using decoupled subsystems (13a, b). Using the spectral norm,



so we can write (13a, b) in the standard singularly perturbed form

$$\dot{y}_1 = \hat{A}_{11}y_1 + \hat{B}_1 u$$
 (14)  
 $\mu \dot{y}_2 = \hat{A}_{22}y_2 + \hat{B}_2 u$ 

where  $A_{22} = \mu A_{22}$  and  $B_2 = \mu B_2$ . The zeroth order approximation to (14) obtained by setting the small parameter to zero is then

$$y_1 = \tilde{A}_{11}y_1 + \tilde{B}_1 u$$
 (15a)

$$\hat{y}_2 \equiv -\hat{A}_{22}^{-1} \hat{B}_2^{-1} u$$
 (15b)

with initial condition

$$y_1(0) = (I+KL)x_1(0) + K x_2(0)$$
 (15c)

and the approximation x to the original state x is given by

$$\hat{x} \equiv \begin{bmatrix} I \\ -L \end{bmatrix} y_1 + \begin{bmatrix} -K \\ I + LK \end{bmatrix} \hat{y}_2.$$
(15d)

If the fast subsystem (13b) has eigenvalues with large negative real part, i.e.

$$\operatorname{Re}(f_j) << -\max_i |s_i| \quad \text{for all } f_j \text{ in } F \qquad (16)$$

then the  $n_1$ th order approximation x can be expected to yield a good approximation for x outside of an initial boundary layer where fast, stable dynamics may predominate.

Note that if one is primarily interested in output variables w rather than state variables x, the reduced order model (15) may be written in a compact matrix form similar to (1). Transform and partition the output matrix as

$$[\tilde{c}_1 \ \tilde{c}_2] = \tilde{c} = cT^{-1}$$

to yield

$$\dot{y}_{1} = \tilde{A}_{11} y_{1} + \tilde{B}_{1} u$$
 (17)  
 $w = \tilde{C}_{1} y_{1} + \tilde{D} u$ 

where

$$\tilde{D} = D - \tilde{C}_2 \tilde{A}_{22}^{-1} \tilde{B}_2.$$

This order reduction method has been shown to compare favorably with other standard methods<sup>17</sup>.

#### 4. POLE PLACEMENT

Dynamic systems are often modeled as linear control systems for the purpose of designing a feedback controller to achieve specific closed-loop eigenvalue locations. Through application of the LK transformation, an n-dimensional eigenvalue placement problem can be reduced to separate eigenvalue placement problems of dimension  $n_1$  and  $n_2$ .

It is well known that if a constant linear control system is <u>controllable</u>, i.e.

then there exists at least one real m x n dimensional feedback matrix H such that the closed-loop eigenvalues given by

 $\lambda$ (A+BH)

can be placed arbitrarily (as long as complex eigenvalues appear in conjugate pairs). If the original system (1) is controllable, it can be shown by linear algebra that the slow and fast subsystems (13a, b) are also controllable. Transfer of observability from the original system to the decoupled subsystems follows by a dual argument.

The design of a feedback matrix H to achieve a specific closed-loop eigenvalue location then follows directly. Suppose it is desired to relocate the  $n_1$  slow open-loop eigenvalues S to  $n_1$  new eigenvalue locations S'. If one can find an m x  $n_1$  feedback matrix  $\tilde{H}_1$  which satisfies

 $(\tilde{A}_{11} + \tilde{B}_1 \tilde{H}_1) = S',$  (19)

then system (13a, b) with feedback  $u = H_1y_1$  becomes

$$\begin{bmatrix} \dot{y}_1 \\ \dot{y}_2 \end{bmatrix} \begin{bmatrix} \tilde{A}_{11} + \tilde{B}_1 \tilde{H}_1 & 0 \\ \tilde{B}_2 \tilde{H}_1 & \tilde{A}_{22} \end{bmatrix} \begin{bmatrix} y_1 \\ y_2 \end{bmatrix} .$$
(20)

Thus the fast eigenvalues F are unchanged and the corresponding feedback matrix for (1) is given by

 $H = [\tilde{H}_1 \quad 0] T.$  (21)

If in addition to relocating the slow mode eigenvalues S it is also necessary to relocate the fast open-loop eigenvalues F to closed-loop values F' then this can be done as follows. After solving for feedback matrix H<sub>1</sub> in (19) find the unique (assuming S' and F have no common eigenvalues)  $n_2 \times n_1$  matrix P satisfying the Lyapunov equation

 $P(\tilde{A}_{11}+\tilde{B}_{1}\tilde{H}_{1}) - \tilde{A}_{22}P + \tilde{B}_{2}\tilde{H}_{1} = 0.$ 

The block-triangular system (20) can then be transformed to a new blockdiagonal form

$$\begin{bmatrix} \dot{\mathbf{y}}_1 \\ \dot{\mathbf{y}}_2 \end{bmatrix} = \begin{bmatrix} \tilde{\tilde{A}}_{11} & 0 \\ 0 & \tilde{A}_2 \end{bmatrix} \begin{bmatrix} \mathbf{y}_1 \\ \tilde{\mathbf{y}}_2 \end{bmatrix} + \begin{bmatrix} \tilde{B}_1 \\ \tilde{B}_2 \end{bmatrix} \tilde{\mathbf{u}}$$
(22)

where  $\bar{y}_2 = Py_1 + \bar{y}_2$ ,  $\bar{A}_{11} = \bar{A}_{11} + \bar{B}_1\bar{H}_1$ , and  $\bar{B}_2 = P\bar{B}_1 + \bar{B}_2$  and  $\bar{u} = u - \bar{H}_1y_1$ .

Now relocate fast eigenvalues F to new values F' by finding an m x  $n_2$  feedback matrix  $\rm H_2$  satisfying

$$\lambda(\tilde{A}_{22} + \tilde{\tilde{B}}_{2}\tilde{H}_{2}) = F'.$$
 (23)

The appropriate gain matrix for the original system (1) is then given by

$$u = Hx$$
,  $H = \left[ (\tilde{H}_1 + \tilde{H}_2 P) \tilde{H}_2 \right] T.$  (24)

Thus, the block-decoupling transformation T can be used to exactly relocate both slow and fast eigenvalues via state feedback.

Many variations of this approach are possible to facilitate the feedback matrix design task. For example, by repeated application of the block-decoupling transformation either of the decoupled subsystems (13a, b) could be further transformed into block-diagonal form and a complete eigenvalue relocation could be achieved in three consecutive design steps analogous to the above two design steps (19) and (23). In many practical applications, the fast modes are all stable and well damped so only the slow eigenvalues need be relocated.

#### 5. A TURBOFAN EXAMPLE

•

The example considered here is the 16th order model of a turbofan engine which was the theme problem for a recent conference on control of linear multivariable systems<sup>1</sup>. This model is the linearization of a detailed nonlinear simulation (at the sea level maximum non-afterburner thrust point). The state variables consist of shaft speeds, temperatures and pressures; the five control inputs are fuel flow, nozzle area, two vane positions and compressor bleed; and the five output variables are net thrust, total airflow, a temperature and two stall margins. For  $n_1 = 15$ , 5 and 3, the resulting small parameters are 0.304, 0.371 and 0.383. Since these values are not particularly small relative to one, we might call this system weakly two-tim2-scale.

Selecting  $n_1 = 5$ , the L and K matrices were computed as described in Anderson<sup>13</sup>. The response of the full 16th order system and reduced 5th order system containing the slow dynamics are compared in Figures 1 and 2. The response of

total thrust and fan speed to step inputs in fuel flow rate and inlet guide vane position demonstrate that good agreement is achieved between full and reduced order response except during an initial boundary layer transient where fast dynamics are significant. The response to a guide vane step input provides a severe test of the reduced order model since this control variable is located at the front of the engine and some time is required for its effects to propagate to the net thrust.

Pole placement for this example was carried out with the goal of increasing the speed of the thrust response. Applying the methods of the previous section, the three slowest modes -0.65, -1.90 and -2.62 were relocated to approximately -6.6. Since there are five control inputs in this example and B<sub>1</sub> is nonsingular, it was possible to shift the above three poles and leave the eigenvectors of the slow subsystem unchanged. Let the slow subsystem have spectral form

$$A_{11} = M_{11}J_1 M_{11}^{-1}$$

where  $J_1 = diag(-0.65, -1.90, -2.62, -6.72 \pm 3.31)$ .

Then feedback matrix H<sub>1</sub> was chosen as

$$\tilde{H}_{1} = \tilde{B}_{1}^{-1} M_{11} \Delta M_{11}^{-1}$$

where  $\Delta = \text{diag}(-6, -5, -4, 0, 0)$  and the model response for the resulting H (c.f. equation (21)) is illustrated in Figure 3. As expected, the response is much quicker with this feedback.

#### 6. CONCLUSIONS

į

· ·

ł .

A method of time scale separation based on the block-decoupling LK transformation is proposed. Methods of applying this transformation to order reduction and pole placement design tasks are described and demonstrated for a turbofan engine example. As previously shown, the L and K matrices are easily computed for large scale systems, particularly those systems with large time scale separation and correspondingly small  $\mu_c$ 





13

Figure 1

L

1

E





Figure 2

!





Figure 3

:

1 5

į

REFERENCES

- M. K. Sain, J. L. Peczkowski and J. L. Melsa, (ed's) <u>Alternatives for</u> <u>Linear Multivariable Control</u>, National Engineering Consortium, Chicago, 1978.
- 2. C. A. Harvey and R. E. Pope, "Synthesis Techniques for Insensitive Aircraft Control Systems," Proceedings, 1976 IEEE Decision and Control Conference, Clearwater, Florida, pp. 990-1001.
- L. Meirovitch (ed.), <u>Proceedings of the First VPI/AIAA Symposium on</u> <u>Dynamics and Control of Large Flexible Spacecraft</u>, June 1977, Blacksburg, VA.
- 4. J. R. Winkelman, J. H. Chow, J. J. Allemong and P. V. Kokotovic, "Multiple-Time-Scale Analysis of a Power System," IFAC Symposium on Computer Applications in Large Scale Systems, New Delhi, India, Aug. 16-18, 1979.
- 5. R. Genesio and M. Milanese, "A Note on the Derivation and Use of Reduced-Order Models" IEEE Trans on Automatic Control. Vol. 21, 1976, pp. 118-122.
- Order Models" <u>IEEE Trans on Automatic Control</u>, Vol. 21, 1976, pp. 118-122. 6. N. K. Sinha, "Reduction of High-Order Systems: A Critical Survey," Proceedings of the 21st Midwest Symposium on Circuits and Systems, Ames, Iowa, 1978, pp. 573-577.
- 7. J. H. Chow and P. V. Kokotovic, "Eigenvalue Placement in Two-Time-Scale Systems," Large Scale Systems Theory and Applications, G. Guardabassi and A. Locatelli, Ed's., IFAC Symposium, Udine, Italy, 1976, pp. 321-326.
- H. J. Kelley, "Aircraft Maneuver Optimization by Reduced-Order Approximation," <u>Advances in Control Theory and Applications</u>, C. T. Leondes, Ed., Vol. 10, 1973, pp. 131-178.
- 9. W. Wasow, <u>Asymptotic Expansions of Ordinary Differential Equations</u>, Wiley-Interscience, New York, 1965.
- R. E. O'Malley, Jr., "Boundary Value Problems for Linear Systems of Ordinary Differential Equations Involving Many Small Parameters," J. Math. and Mech., Vol. 18, 1969, p. 835-855.
- 11. W. A. Harris, Jr., "Singularly Perturbed Boundary Value Problems Revisited," Lecture Notes in Math, Vol. 312, Springer-Verlag, Berlin, 1973, pp. 54-64.
- P. V. Kokotovic, "A Riccati Equation for Block-Diagonalization of Ill-Conditioned Systems," <u>IEEE Trans. on Automatic Control</u>, Vol. 20, 1975, pp. 812-814.
- L. Anderson, "Decoupling of Two-Time-Scale Linear Systems," Proceedings, 1978 Joint Automatic Controls Conference, Philadelphia, Vol. 4, pp. 153– 163.
- 14. J. Medanic, "Geometric Properties and Invariant Manifolds of the Riccati Equation," preprint, Coordinated Sciences Laboratory, University of Illinois, Urbana, 1979.
- 15. R. Bellman, Introduction to Matrix Analysis, McGraw-Hill, New York, 1970.
- 16. B. Avramovic, "Subspace Iteration Approach to the Time Scale Separation," Proceedings of the 18th IEEE Conference on Decision and Control, Fort Lauderdale; Florida, 1979.
- L. Anderson, "Decoupling and Order Reduction of Two-Time-Scale Control Systems," <u>Information Linkage Between Applied Mathematics and Industry II</u>, A. L. Schoemstadt Et. Al., Editors, Academic Press, 1980, p. 197-213.
- L. R. Anderson and W. L. Hallauer, Jr., "A Method of Order Reduction for Structural Dynamics based on Riccati Iteration," <u>AIAA Journal</u> (to appear in May or June, 1981).

Numerical Solution of the Symmetric Riccati Equation through Riccati Iteration

Leonard R. Anderson\* Dennis W. Brewer\*\* A. Rasim Baykan\*\*\*

#### Abstract

This research paper presents a new numerical method for solving the symmetric algebraic Riccati equation from optimal control. This algorithm employs the "Riccati iteration" which has been successfully used to solve time-scale decoupling problems in structural vibrations. The algorithm is related to the subspace iteration method, and the rate of convergence to the solution is governed by the relative separation between the stable and unstable eigenvalues in the Hamiltonian system of equations. Provided there is adequate eigenvalue separation and ignoring roundoff error, the algorithm is globally convergent to the desired Riccati solution. The method is demonstrated for a set of 8th order random examples. Preliminary accuracy and timing comparisons with other standard methods of solving the symmetric Riccati equations are presented.

Submitted for presentation at the 1982 American Control Conference, Arlington, Virginia and for publication in the <u>IEEE Transactions on Automatic Control</u>.

\*Assist. Prof., Aerospace and Ocean Eng. Dept., VPI & SU. \*\*Assist. Prof., Mathematics Dept., Univ. of Arkansas. \*\*\*Graduate Research Assistant, Aerospace and Ocean Eng. Dept., VPI & SU.

This research work was sponsored by NASA research grant NAG-1-80.

I. Introduction

1 1

It is well known that in order to solve the infinite-time regulator problem [1,2] with linear system

$$\hat{\mathbf{x}} = \mathbf{A}\mathbf{x} + \mathbf{B}\mathbf{u} \tag{1}$$

and quadratic performance index (the LQR problem)

$$J = 1/2 \int_{0}^{\infty} (x^{T}Qx + u^{T}Ru) dt$$
 (2)

one must compute the unique positive definite solution S to the symmetric algebraic Riccati equation

$$\mathbf{O} = \mathbf{S}\mathbf{A} + \mathbf{A}^{\mathsf{T}}\mathbf{S} - \mathbf{S}\mathbf{B}\mathbf{R}^{-1}\mathbf{B}^{\mathsf{T}}\mathbf{S} + \mathbf{Q} \,. \tag{3}$$

Here x is an n-dimensional state vector, u is an m-dimensional control vector, A and B are constant matrices Q and R are positive semi-definite and positive definite, respectively. Also it is assumed that the matrix pair (A,B) is controllable, and the pair (A,Q<sup>1/2</sup>) is observable and that B has full rank. Then assuming that any constraints on the size of u(t) are not violated, the linear feedback control law which minimizes the performance index J is given by -1 T.

$$u = Kx \text{ where } K = -R^{-1}B^{T}S.$$
(4)

Algebraic Riccati equations similar to (3) also play a fundamental roll in discrete-time optimal control problems, in optional estimation problems, and is many other areas of applied mathematics [3-7]. See Jones [8] for basic necessary and sufficient conditions for solutions of equations of this type.

Among the most widely used solution methods for solving algebraic Riccati equations are the Schur vector method described by Laub [9], methods employing eigenvectors of the Hamiltonian system [1,2,10,11] and Newton-Raphson

methods [1,2,12]. The Riccati iteration method differs from these methods in that neither eigenvalue computation nor solution of equations of the Lyapunov-type are required. The algorithm is suprisingly simple, requiring only repetitive solution of linear equations of order n. However, caution must be exercised when applying the method to LQR problems with nearly zero eigenvalues, or eigenvalues with large imaginary part.

II. The eigenvector solution to the algebraic Riccati equation

Ł

Ľ

11

Given the linear system (1) and performance index (2), we can form the control Hamiltonian and apply the necessary conditions for optimal control to obtain the Hamiltonian system of equations

$$\begin{bmatrix} \mathbf{x} \\ \mathbf{y} \end{bmatrix} = \begin{bmatrix} \mathbf{A} & -\mathbf{B}\mathbf{R}^{-1}\mathbf{B}^{\mathsf{T}} \\ -\mathbf{Q} & -\mathbf{A}^{\mathsf{T}} \end{bmatrix} \begin{bmatrix} \mathbf{x} \\ \mathbf{y} \end{bmatrix} \equiv \mathbf{H} \begin{bmatrix} \mathbf{x} \\ \mathbf{y} \end{bmatrix}, \qquad (5)$$

where y is an n-dimensional vector of costate or adjoint variables. The 2n x 2n matrix H has symmetric eigenvalues. That is, if  $\lambda$  is an eigenvalue of H then  $-\lambda$  is also an eigenvalue of H.

If matrix H is represented in spectral form

where the matrices are partitioned conformally with (5), and  $\Lambda_1$  contains all the eigenvalues with positive real part ordered as

 $\Lambda_{1} = \text{diag} (\lambda_{1}, \lambda_{2}, \dots, \lambda_{n}) \text{ with } |\lambda_{i}| \leq |\lambda_{i+1}|, i = 1, 2, \dots n-1, (6)$ then the desired solution, S, to the Riccati equation is given by

- - -

$$SM_{11} = M_{21} \text{ or } Q_{22} S = -Q_{21}$$
 (7)

To demonstrate this fact, apply the similarity transformation

$$T = \begin{bmatrix} I & 0 \\ \\ \\ -S & I \end{bmatrix}, T^{-1} = \begin{bmatrix} I & 0 \\ \\ \\ S & I \end{bmatrix}$$
(8)

to the Hamiltonian system to obtain

$$\hat{H} = THT^{-1} = \begin{bmatrix} A - BR^{-1}B^{T}S & -BR^{-1}B^{T} \\ -SA - A^{T}S + SBR^{-1}B^{T}S - Q & -A^{T} + SBR^{-1}B^{T} \end{bmatrix}, \quad (9)$$

or in spectral form

i

$$\hat{H} = \begin{bmatrix} I & 0 \\ -M_{21}M_{11}^{-1} & I \end{bmatrix} \begin{bmatrix} M_{11} & M_{12} \\ M_{21} & M_{22} \end{bmatrix} \begin{bmatrix} -\Lambda_{1} & 0 \\ 0 & \Lambda_{1} \end{bmatrix} \begin{bmatrix} Q_{11} & Q_{12} \\ Q_{21} & Q_{22} \end{bmatrix} \begin{bmatrix} I & 0 \\ -Q_{22}^{-1}Q_{21} & I \end{bmatrix}$$
$$= \begin{bmatrix} -M_{11} & \Lambda_{1} & M_{11}^{-1} \\ 0 & Q_{22}^{-1} & \Lambda_{1} & Q_{22} \end{bmatrix}$$
(10)

Since the closed-loop system for feedback law (4) is

$$\dot{x} = Ax + Bu = (A - BR^{-1}B^{T}S)x$$
(11)  
$$\equiv \tilde{A}x$$

the eigenvalues  $-\Lambda_{\eta}$  become the eigenvalues  $\lambda(\tilde{A})$  of the closed-loop system. Given efficient eigenanalysis software such as EISPACK [13], one can directly compute the eigenvalues and eigenvectors of the Hamiltonian system (5) and solve the appropriate system of linear equations (7) for the Riccati solution S. If  $-\Lambda_1$  includes complex conjugate eigenvalues  $\lambda_j$ ,  $\overline{\lambda_j}$  with corresponding complex conjugate eigenvectors  $u_j = \alpha + i\beta$ ,  $\overline{u_j} = \alpha - i\beta$ , then complex arithmetic can be avoided in the set of linear equations (7) by replacing  $u_j$  with  $\alpha$  and  $\overline{u_j}$  with  $\beta$ .

As an alternative to computing eigenvectors  $\begin{bmatrix} M_{11} \\ M_{21} \end{bmatrix}$ , one can compute the n Schur vectors [9] spanning the stable eigenspace and solve (7) with  $M_{11}$ ,  $M_{21}$  replaced by corresponding Schur vectors. Schur vectors are defined as follows. Given any nxn matrix C with eigenvalues  $\lambda_1, \ldots, \lambda_n$  there exists a unitary matrix V such that V<sup>H</sup>CV is upper triangular with diagonal elements  $\lambda_1, \ldots, \lambda_n$ . The columns of V are the Schur vectors of C, possibly complex, corresponding to this particular ordering of eigenvalues.

If some of the eigenvalues  $\lambda_i$  are complex, then one can avoid complex Schur vectors by employing a (real) orthogonal matrix  $\tilde{V}$  such that  $\tilde{V}^T A \tilde{V}$  is real and nearly upper triangular. The only nonzero subdiagonal elements in  $\tilde{V}^T A \tilde{V}$  will be due to real 2x2 diagonal blocks corresponding to complex eigenvalues  $\lambda_i$ . This is termed the real Schur form of C, and the columns of  $\tilde{V}$  are real Schur vectors.

To return to the problem of computing the solution (7) to the symmetric Riccati equation (3), one can compute the 2n real Schur vectors

 $\tilde{\mathbf{v}} = \begin{bmatrix} \tilde{\mathbf{v}}_{11} & \tilde{\mathbf{v}}_{12} \\ \\ \\ \tilde{\mathbf{v}}_{21} & \tilde{\mathbf{v}}_{22} \end{bmatrix}$ (12)

of the 2nx2n matrix H so that  $\begin{bmatrix} v_{11} \\ v_{21} \end{bmatrix}$  provides a basis for the eigenspace corresponding to stable eigenvalues  $-\Lambda_1$ .

The computation is best performed using the subroutine HQR3 [14] with small modifications. In its standard form, HQR3 orders the eigenvalues of H

by modulus with  $|\lambda_1| \le |\lambda_2| \le ...$  on the diagonal of  $\forall^T H \dot{\forall}$ . The ordering statements in HQR3 may be modified so that either

- 1) all stable (negative real part) eigenvalues are placed in the upper left diagonal block of  $\hat{V}^T H \hat{V}$  and unstable eigenvalues are placed in the lower right block, with no regard to ordering within each block, or
- 2) the eigenvalues of H are ordered along the diagonal of  $\tilde{V}^T H \tilde{V}$  by real part from most negative to most positive.

Only modification (2) is implemented in the numerical examples which follow.

III. Riccati iteration solution to the algebraic Riccati equation

Before proceeding to the solution of the symmetric Riccati equation (3), we will first describe in detail the solution of the closely related timescale decoupling problem using Riccati iteration [15,16], and then extend these results to (3).

The time-scale decoupling problem can be stated as follows. Given an nxn diagonalizable matrix C with eigenvalues

 $s_1, s_2, \ldots, s_{n_1}, f_1, f_2, \ldots, f_{n_2}$ 

not necessarily distinct and satisfying

$$|s_{1}| \leq |s_{2}| \leq \cdots \leq |s_{n_{1}}| < |f_{1}| \leq |f_{2}| \leq \cdots \leq |f_{n_{2}}|,$$
  
with  $\mu = \frac{|s_{n_{1}}|}{|f_{1}|},$  (13)

if parameter  $\underline{u}$  is small relative to one, we say that the matrix is two-timescale [17,18]. Let the diagonalization of C be given by C = EJF where  $F=E^{-1}$  and J is diagonal with diagonal entries

 $s_1, s_2, \ldots, s_{n_1}, f_1, f_2, \ldots, f_{n_2}.$ 

۱,

Ŀ

li

Partition the matrices C, E, F and J as

ł.

[]

[.

$$C = \begin{bmatrix} c_{11} & c_{12} \\ c_{21} & c_{22} \end{bmatrix} , E = \begin{bmatrix} E_{11} & E_{12} \\ E_{21} & E_{22} \end{bmatrix}$$
$$F = \begin{bmatrix} F_{11} & F_{12} \\ F_{21} & F_{22} \end{bmatrix} , J = \begin{bmatrix} J_1 & 0 \\ 0 & J_2 \end{bmatrix}$$

where  $C_{11}, E_{11}, F_{11}, J_1$  are  $n_1 \times n_1$ , etc. For k = 0, 1, 2, ... partition the matrix  $C^k$  similarly as

$$C^{k} = \begin{bmatrix} S_{k} & T_{k} \\ & \\ U_{k} & V_{k} \end{bmatrix}$$

The Riccati iteration and its convergence properties for the time-scale decoupling problem [19] are introduced through

<u>Theorem 1.</u> Given  $\mu < 1$  and  $V_k$  nonsingular for k = 1, 2, 3, ..., the iteration

$$L_{0} = 0$$

$$L_{k+1} = (C_{22} + L_{k}C_{12})^{-1}(L_{k}C_{11} + C_{21})$$

$$k = 0, 1, 2, ...$$
(14)

is well defined and

$$L_k \longrightarrow F_{22}^{-1}F_{21}$$
 as  $k \longrightarrow \infty$ 

with convergence in the sense of matrix norm. For any ixj matrix B, ||B||

11

where  $||\cdot||_1$ ,  $||\cdot||_1$  denote convenient norms on  $R^1$  and  $R^j$ .

The proof of Theorem 1 is presented in the Appendix.

Furthermore, the rate of convergence of  $L_k$  to  $F_{22}^{-1}F_{21}$  is controlled by the small parameter  $\mu$  as shown in the Appendix. Convergence would be expected to be unreasonably slow for  $\mu$  close to one.

To apply the Riccati iteration to the symmetric Riccati equation (3) we need to shift the Hamiltonian matrix (5) as

$$\hat{H} = H + \lambda_{s} I$$
(15)

so that the stable, left half-plane eigenvalues  $-\lambda_1$ ,  $-\lambda_2$ , ...,  $-\lambda_n$  of H become the slow or small eigenvalues of H analogous to  $s_1$ ,  $s_2$ , ...,  $s_{n_1}$ .

We can now state the formal conditions for convergence of the Riccati iteration for the symmetric Riccati equation (3) as

<u>Theorem 2.</u> Given the Hamiltonian system (5) and given shift distance  $\lambda_s$  satisfying<sup>1</sup>

<sup>1</sup>Note, this redefines  $\mu$  for the sequel, cf. (13).

$$\mu = \frac{\max_{i=1,...,n} |-\lambda_i + \lambda_s|}{\min_{i=1,...,n} |\lambda_i + \lambda_s|} < 1$$
(16)

the Riccati Iteration

t :

1

Li

11

11

----

ì

ł

$$S_{0} = 0$$

$$S_{1+1} = (-A^{T} + \lambda_{s} I - S_{1}BR^{-1}B^{T})^{-1}(S_{1}(A + \lambda_{s}I) - Q)$$
(17)

converges to solution (7) with asymptotic rate

 $||s_{f} + Q_{22}^{-1}Q_{21}|| \le c\mu^{k}$ 

where the matrix norm is as in Theorem 1, and constant c is independent of k. The proof of Theorem 2 follows directly from the proof of Theorem 1 in the Hamiltonian setting.

The key practical difficulty in implementing iteration (17) is the estimation of the shift distance  $\lambda_s$ . Two choices for the shift distance are proposed, namely

$$\lambda_{s} \stackrel{\gamma}{=} \max_{i=1,\dots,n} |\lambda_{i}|$$
(18)

or

$$\lambda_{s} \stackrel{\sim}{=} \frac{\max}{\substack{i=1,\ldots,n}} \frac{|\lambda_{i}| + \min}{\frac{j \leq 1,\ldots,n}{2}}$$
(19)

The shifting strategy (19) will in general yield higher rates of convergence since the stable eigenvalues of H become nearly centered about the origin in A. Shift strategy (18) is recommended for symmetric Riccati equations with eigenvalues having large imaginary part, since this minimizes the chances of no convergence, or convergence to a solution other than the desired solution (7). Both shifting strategies can be implemented numerically in approximate form.

The computational algorithm for the symmetric Riccati equation is therefore <u>Algorithm 1.</u>

1) Form the Hamiltonian matrix

1

$$H = \begin{bmatrix} A & -BR^{-1}B^{T} \\ \\ -Q & -A^{T} \end{bmatrix}$$

2) Beginning with the 2n vector

 $x_0 = (2n)^{-1/2} [1 \ 1... \ 1]^T$ 

perform a few power steps (five or more)

$$\hat{x}_{i+1}^{T} = x_i^{T} H$$
  
 $x_{i+1} = \hat{x}_{i+1} / ||\hat{x}_{i+1}||, i = 0, 1, ...5$ 

where ||-|| is the Euclidean or Frobenius norm.

3) Obtain an initial estimate of the shift distance  $\alpha_{1} = ||\tilde{x}_{1}||$   $\alpha_{i+1} = \frac{\alpha_{i} + ||\tilde{x}_{i+1}||}{2}$ , i = 1, 2, ..., 5 $\lambda_{s,0} = \alpha_{6}$ . 4) Estimate a limit for  $\lambda_{max}$ 

 $\lambda_{1imit} = 1.5 \lambda_{s,0}$ 

and partition the vector  $\boldsymbol{x}_6$  as

$$x_6 = [u_0 \ u_0]^T$$

1

•

with  $u_0$  of dimension n.

5) Initialize  $S_0 = 0$ , j = 0, and form the inverse power vector  $v_0 = (n)^{-1/2} [1 \ 1 \dots 1]^T$ of dimension n.

$$H_{22,j} = -A^{T} + \lambda_{s,j}I - S_{j}BR^{-1}B^{T}$$
$$G_{j} = S_{j}(A + \lambda_{s,j}I) - Q.$$

7) Perform a power step and estimate 
$$\lambda_{max}$$
.

$$\hat{u}_{j+1}^{T} = u_{j}^{T} H_{22,j}$$

$$\lambda_{max,j} = max (0, min (\lambda_{limit}, ||\hat{u}_{j+1}|| - \lambda_{s,j}))$$

$$u_{j+1} = \hat{u}_{j+1} / ||\hat{u}_{j+1}||$$

8) Solve the linear system for 
$$S_{j+1}$$
 and  $\tilde{v}_{j+1}$   
 $H_{22,j} [S_{j+1} \tilde{v}_{j+1}] = [G_j v_j]$ 
(20)

9) If 
$$j \ge 1$$
, find the relative change in  $S_j$ .  
 $\delta_j = ||S_{j+1} - S_j||/||S_j||$ 

and terminate the iteration if  $\delta_j$  is less than or equal to some specified convergence tolerance  $\epsilon$ , or has reached a minimum value.

10) Normalize the inverse power vector 
$$\hat{V}_{j+1}$$
 and estimate  $\lambda_{\min}$ .  
 $\lambda_{\min,j} = \max (0, \min (\lambda_{\max,j}, \frac{1}{||\tilde{V}_{j+1}||} - \lambda_{s,j}))$   
 $v_{j+1} = \hat{V}_{j+1}/||\hat{V}_{j+1}||.$ 

11) Update the shift distance by either

$$\lambda_{s,j+1} = \frac{3\lambda_{s,j} + \lambda_{max,j}}{4}$$
(21)

or

$$\hat{\lambda}_{s,j+1} = \frac{6\lambda_{s,j} + \lambda_{\max,j} + \lambda_{\min,j}}{8}$$
(22)

12) Increase j by one and go to step 6.

Obviously, if one computes the updated shift distance by the more conservative (21), then one need not include the inverse power vector  $v_j$  in the iteration. The power and inverse power estimates of  $\lambda_{\min} = |\lambda_1|$  and  $\lambda_{\max} = |\lambda_n|$  are based on the fact that the eigenvalue spectrum of H<sub>22,j</sub> converges to the eigenvalues  $\Lambda_1$  increased by  $\lambda_{s,j}$ .

This iterative technique for solving the symmetric Riccati equation has similarities to one proposed by Farrar and DiPietro [20]. The methods differ in that their method is initialized using eigenvectors, and employs iterative improvement requiring solution of a Lyapunov-type equation at each step.

### IV. Numerical examples

Į,

The eigenvector and Schur vector solution methods and the Riccati iteration method were evaluated in a limited comparative test. The test consisted of

sets of linear-quadratic-regulator problems generated as follows. The elements of the A and B matrices of system (1) were chosen as random integers from a uniform distribution over the internal [-10, +10], with 25% of the elements set arbitrarily to zero. The order n of the system was varied between 5 and 20, and the control dimension m was held at one. The positive semidefinite weighting matrix Q was constructed from a Choleski factorization

$$0 = PP^{I}$$

where P is upper-triangular. The upper-triangular elements of P are also integers chosen uniformly from the internal [-10, +10], with 25% of these elements set to zero. In all cases the R matrix, a scalar, had a value of 2.

All methods were either obtained or coded in the FORTRAN language in double precision, and executed in batch mode on the VPI&SU IBM 370/158 computer.

Table 1 presents the results for a set of ten random cases of order eight generated as described above and solved by Algorithm 1. The table includes the theoretical rate of convergence  $\mu$  for each of the shift strategies (18) and (19), the value of the Riccati residual  $||R_i||$  where

$$R_{i} = S_{i}A + A^{T}S_{i} - S_{i}BR^{-1}B^{T}S_{i} + Q$$
 (23)

for the converged solution  $S_i$ , the maximum relative error between the eigenvalues of the closed-loop system (11) and the stable eigenvalues of the Hamiltonian system (5), the number of iterations in Algorithm 1 to reach a minimum value of  $\delta_i$ , and the corresponding central processor execution time in seconds. As noted earlier, the shift strategy (18), (21) is significantly slower in convergence than (19), (22). However, the faster method (19), (22) fails to converge for case 8 as expected since  $\mu > 1$ .

To further describe the convergence characteristics of the Riccati iteration, the values of  $\log_{10} ||R_1||$  and  $\log_{10} ||\delta_1||$  versus iteration

number are plotted in Figures 1 and 2. These figures correspond to cases 2 and 9, and represent the most rapid and the slowest convergence of the ten cases, respectively. As shown, the theoretical limit  $\mu$ , cf. (15), accurately predicts the true rate of convergence of the algorithm for each of the two shifting strategies. The specific A, B, Q and R matrices for cases 2 and 9 are listed in Tables 2 and 3.

For comparison purposes, the symmetric Riccati equation for these ten cases is also solved by the eigenvector and Schur vector methods. This data is listed in Table 4. As in Table 1, we specify the value of the norm of the Riccati residual ||R|| corresponding to the computed solution S, the maximum relative error between the eigenvalues of the closed-loop system and the Hamiltonian system, and the execution time in seconds. The execution times include both the time to compute eigenvectors or Schur vectors and the time to solve the linear system (7). The numerical method used to solve both the linear systems (7) and (20) in this study was LU decomposition with partial pivoting without iterative improvement of accuracy. Specifically, the Fortran subroutines DECOMP and SOLVE were used, but not the subroutine IMPRUV from the widely used Forsythe and Moler text [21].

For the eigenvector solution method, all eigenvalues and eigenvectors of the Hamiltonian matrix were computed using EISPACK subroutines ELMHES, ELTRAN and HQR2. Then eigenvectors corresponding to stable eigenvalues were selected to form the real  $\begin{bmatrix} M_{11} \\ M_{21} \end{bmatrix}$  matrix. For the Schur vector solution method, the real Schur vectors  $\begin{bmatrix} V_{11} \\ V_{21} \end{bmatrix}$  spanning the stable eigenspace were computed using EISPACK subroutines ORTHES and ORTRAN, and Stewart's subroutines HQR3 and EXCHNG. The HQR3 subroutine was modified [22] so that the eigenvalues  $\widehat{V}$  H $\widehat{V}$  are ordered along the diagonal from most negative to most positive real part.

As shown in comparison of Tables 1 and 4, the Riccati iteration is able to

produce final Riccati residuals two orders of magnitude smaller on the average than the eigenvector and Schur vector methods. However, the Riccati iteration execution times are slower than the eigenvector and Schur vector methods by a factor of ten, on the average.

The choice of method clearly depends on both the parameter  $\mu$  for the class of problems under consideration, and the relative importance of minimizing computer execution time versus software simplicity. In general, as the order n of the LQR problem increases, the parameter  $\mu$  increases and approaches or exceeds one. Therefore, the eigenvector/Schur vector algorithms would still be the method of choice for problems of large order.

V. Conclusions

i

Ŀ

A new numerical algorithm for solving the symmetric Riccati equation from the linear-quadratic-regulator problem has been presented and compared with standard methods. A formal proof of convergence for the Riccati iteration is presented, and numerical examples confirm the theoretical rate of convergence. The strengths of this new algorithm are its simplicity, accuracy and theoretically transparent basis. Riccati iteration may be particularly useful for low order adaptive control algorithms or control system design studies where one must update the Riccati solution as system matrices or performance index weighting matrices slowly change. The primary weakness of this method is that it is slower than standard methods as shown here, and the rate of convergence is dependent on sufficient stable/unstable eigenvalue separation in the Hamiltonian system.

Future research tasks include:

- finding an appropriate conformal transformation for the Hamiltonian system to increase stable/unstable eigenvalue separation and/or decrease the imaginary component of eigenvalues.
- Applying a doubling algorithm [23] to this method to increase rate of convergence.

j,

## Appendix - Proof of Theorem 1

To prove theorem 1 the following lemma will be useful.

<u>Lemma</u>: For k = 0, 1, 2, ... $L_{\nu} = V_{\nu}^{-1}U_{\nu}.$ 

<u>Proof</u>: We proceed by induction on k:

For k = 0 $L_0 = V_0^{-1}U_0 = I \cdot 0 = 0$ 

as required. Note that partitioning the product

$$c^{k}c = c^{k+1}$$

yields :

$$U_k C_{11} + V_k C_{21} = U_{k+1}$$
  
 $U_k C_{12} + V_k C_{22} = V_{k+1}$ 

Assuming the induction hypothesis,

 $(c_{22} + L_k c_{12}) = c_{22} + v_k^{-1} u_k c_{12} = v_k^{-1} v_{k+1}$ 

which is nonsingular by hypothesis.

Therefore 
$$L_{k+1} = (C_{22} + L_k C_{12})^{-1} (L_k C_{11} + C_{21})$$
  
=  $(V_{k+1}^{-1} V_k) (V_k^{-1} U_k C_{11} + C_{21})$   
=  $V_{k+1}^{-1} V_k V_k^{-1} U_{k+1} = V_{k+1}^{-1} U_{k+1}$ .

This completes the proof of the lemma.

## Proof of Theorem 1

Since C = EJF, where  $F=E^{-1}$ , we have  $C^{k} = (EJF)^{k} = EJ^{k}F$ . Partitioning the product  $EJ^kF$  yields

$$U_{k} = E_{21}J_{1}^{k}F_{11} + E_{22}J_{2}^{k}F_{21}$$
  
$$V_{k} = E_{21}J_{1}^{k}F_{12} + E_{22}J_{2}^{k}F_{22}$$

where  $J_1$  and  $J_2$  are diagonal matrices with diagonal entries  $s_1$ ,  $s_2$ , ...,  $s_{n_1}$ and  $f_1, f_2, \ldots, f_n$  respectively. Therefore, by the lemma

$$\mathbf{F}_{k} = (\mathbf{E}_{21}\mathbf{J}_{1}^{\mathbf{F}}\mathbf{F}_{12} + \mathbf{E}_{22}\mathbf{J}_{2}^{\mathbf{F}}\mathbf{F}_{22})^{-1}(\mathbf{E}_{21}\mathbf{J}_{1}^{\mathbf{F}}\mathbf{F}_{11} + \mathbf{E}_{22}\mathbf{J}_{2}^{\mathbf{F}}\mathbf{F}_{21})$$

for k = 0, 1, 2, ...

For brevity let

$$D_{k} = (E_{21}J_{1}^{k}F_{12} + E_{22}J_{2}^{k}F_{22}).$$

An easy computation shows that

$$D_{k}^{-1} = (I - D_{k}^{-1} (E_{21}J_{1}^{k}F_{12}))(E_{22}J_{2}^{k}F_{22})^{-1},$$

therefore

$$L_{k} = (I - D_{k}^{-1}E_{21}J_{1}^{k}F_{12})(E_{22}J_{2}^{k}F_{22})(E_{21}J_{1}^{k}F_{11} + E_{22}J_{2}^{k}F_{21})$$
  
= (I - D\_{k}^{-1}E\_{21}J\_{1}^{k}F\_{12})(F\_{22}^{-1}J\_{2}^{-k}E\_{22}^{-1}E\_{21}J\_{1}^{k}F\_{11} + F\_{22}^{-1}F\_{21}).

Hence,

SO

•

$$\begin{split} L_{k} &= F_{22}^{-1}F_{21} = F_{22}^{-1}J_{2}^{-k}E_{22}^{-1}E_{21}J_{1}^{-k}F_{11} \\ &= (D_{k}^{-1}E_{21}J_{1}^{-k}F_{12})(F_{22}^{-1}J_{2}^{-k}E_{22}^{-1}E_{21}J_{2}^{-k}F_{11}) \\ &= (D_{k}^{-1}E_{21}J_{1}^{-k}F_{12})(F_{22}^{-1}F_{21}). \end{split}$$
Note that  $||J_{1}|| \leq |s_{n_{1}}|$  and  $||J_{2}^{-1}|| \leq \frac{1}{|f_{1}|},$   
so  $||J_{2}^{-k}|| ||J_{1}^{-k}|| \leq \frac{|s_{n_{1}}|^{k}}{|f_{1}|^{k}} = \mu^{k}.$ 

Furthermore,

$$\begin{split} \mathbb{D}_{k}^{-1}\mathbb{E}_{21}J_{1}^{k}F_{12} &= (\mathbb{E}_{21}J_{1}^{k}F_{12} + \mathbb{E}_{22}J_{2}^{k}F_{22})^{-1}\mathbb{E}_{21}J_{1}^{k}F_{12} \\ &= F_{22}^{-1}J_{2}^{-1}\mathbb{E}_{21}^{-1}(1 + \mathbb{E}_{21}J_{1}^{k}F_{12}F_{22}^{-1}J_{2}^{-k}\mathbb{E}_{22}^{-1})^{-1}\mathbb{E}_{21}J_{1}^{k}F_{12} \\ \text{Now } ||(I + T)^{-1}|| &\leq (1 - ||T||)^{-1} \text{ if } ||T|| < 1, \\ \text{so } ||\mathbb{D}_{k}^{-1}\mathbb{E}_{21}J_{1}^{k}F_{12}|| &\leq \frac{a\mu^{k}}{1 - a\mu^{k}} \\ \text{for sufficiently large } k, \\ \text{where } a &= ||F_{22}^{-1}|| ||\mathbb{E}_{22}^{-1}|| ||\mathbb{E}_{21}|| ||F_{12}||. \\ \text{Combining these estimates yields} \\ &||\mathbb{L}_{k}^{-}F_{22}^{-1}F_{21}|| &\leq \frac{b\mu^{k}}{1 - a\mu^{k}} + \frac{a\mu^{k}}{1 - a\mu^{k}} ||F_{22}^{-1}F_{21}|| \end{split}$$

where  $b = a||F_{11}||/||F_{12}||$ .

Since  $\mu < 1$ ,  $\mu^k \longrightarrow 0$  as  $k \longrightarrow \infty$ . This estimate completes the proof.
Table 1 Summary of Riccati Iteration Performance for ten 8th order random examples

1

L.;

<u>|</u>,

I

•

•

	×	$= 1 \lambda_{\text{MB}, \text{X}} + \frac{1}{2}$	λ <u>min</u> , cf. (19)	, (21)			λ <sub>s</sub> = [.	λ <sub>max</sub>  . cf. (18).	(20)	
case	a		max. rel. e-value error	iterations	tine (sec)	h#	R   <sub>mfn</sub>	max. rel. e-value error	iterations	time (sec)
-	0.656	4.0 X 10 <sup>-5</sup>	2.4 X 10 <sup>-7</sup>	85	3.2	0.792	4.3 X 10 <sup>-5</sup>	4.5 X 10 <sup>-7</sup>	144	5.5
2	0.613	2.5 X 10 <sup>-6</sup>	1.8 X 10 <sup>-9</sup>	86	3.2	0.730	4.1 X 10 <sup>-7</sup>	2.9 X 10 <sup>-9</sup>	137	5.2
m	0.704	2.0 X 10 <sup>-4</sup>	3.8 X 10 <sup>-8</sup>	92	3.4	0.826	1.6 X 10 <sup>-4</sup>	5.5 X 10 <sup>-8</sup>	146	5.4
4	0.730	01-01 X 8.7	1.3 X 10 <sup>-12</sup>	106	4.1	0.838	8.7 X 10 <sup>-10</sup>	1.2 X 10 <sup>-12</sup>	181	6.8
5	0.692	6.8 X 10 <sup>-10</sup>	1.7 X 10 <sup>-12</sup>	16	3.5	0.818	0.0 X 10 <sup>-10</sup>	3.0 X 10 <sup>-12</sup>	159	6.0
9	0.913	9.0 X 10 <sup>-9</sup>	2.2 X 10 <sup>-12</sup>	160	6.1	0.760	9.7 X 10 <sup>-10</sup>	1.9 X 10 <sup>-13</sup>	127	4.8
7	0.768	4.6 X 10 <sup>-10</sup>	9.8 X 10 <sup>-12</sup>	136	5.3	0.868	6.6 X 10 <sup>-5</sup>	6.4 X 10 <sup>-11</sup>	146	5.6
80	1.106	no convergen	Ce la			0.930	7.2 X 10 <sup>-5</sup>	2.1 X 10 <sup>-9</sup>	343	13.3
6	0.927	8.7 X 10 <sup>-11</sup>	2.7 X 10 <sup>-13</sup>	452	17.0	0.962	8.2 X 10 <sup>-11</sup>	3.5 X 10 <sup>-13</sup>	893	33.8
01	0.716	5.5 X 10 <sup>-13</sup>	4.1 X 10 <sup>-14</sup>	106	4.2	0.825	7.3 X 10 <sup>-13</sup>	1.8 X 10 <sup>-4</sup>	180	6.9

ł

	<del>8</del> - ]	-8	6	-4	-7	4	0	0
	-2	-10	-6	-4	0	-3	1	1
	-5	9	2	5	-6	8	0	-7
A -	-7	-4	-4	10	5	2	0	-3
~ -	3	5	-1	2	1	-10	0	6
	-8	2	-7	-9	-8	4	-8	0
	-7	-1	-6	9	-10	-8	-6	7
	4	7	0	4	0	6	-1	2
β <sup>T</sup> =	[0	-7	-7	5	· 6	-7	-2	o .]
	<b>48</b>	18	7	-3	-5	-10	6	-9
	18	27	-10	11	-1	3	0	0
	7	-10	30	-6	1	-5	0	0
	-3	11	-6	33	0	2	0	0
Q,=	-5	-1	٦	0	6	-3	-4	6
	-10	3	-5	2	-3	10	0	0
	6	0	0	0	-4	0	4	-6
	9	0	0	0	6	0	-6	[ و

	<b>8-</b> ]	-8	-7	0	-4	10	-9	0	
	4	-9	-6	-4	7	0	-4	-7	
	1	7	-10	-1	-3	0	10	-2	
	0	6	10	0	0	9	2	-10	
A 🛥	0	0	0	0	0	0	3	0	
	7	-2	-3	2	-4	-6	2	0	
	8	-8	8	0	0	0	0	-8	
	5	0	0	0	-2	-1	-5	-6	
8 <sup>T</sup> =	[0	5	8	6	0	0	0	-6	]
	<b>4</b> 4	7	-6	15	17	-7	-12	6	]
	7	20	8	7	7	-11	-4	-2	
	-6	8	21	6	-4	-4	4	-4	
-	15	7	6	29	11	-7	-6	4	
Q =	17	7	-4	11	14	-7	-10	4	
	-7	-11	-4	-7	-7	17	2	4	
	-12	-4	4	-6	-10	2	8	-4	
	6	-2	-4	4	4	4	-4	4	J

R = 2

:

L

ł

. **\*** 

Table 4 Summary of eigenvector and Schur vector solution performance for ten 8th order random examples

l

1

t

1

	eigenvector	solution (EISPACI	Ŷ	Schur vector	<ul><li>solution (HQR3)</li></ul>	
case	R   <sub>min</sub>	max. rel. e-value error	time (sec)	R   <sub>mfn</sub>	max. rel. e-value error	time (sec)
-	1.3 X 10 <sup>-2</sup>	5.9 X 10 <sup>-8</sup>	0.40	4.0 X 10 <sup>-3</sup>	5.9 X 10 <sup>-8</sup>	0.62
~	2.8 X 10 <sup>-4</sup>	4.8 X 10 <sup>-11</sup>	0.45	7.6 X 10 <sup>-5</sup>	11-01 X 1.3	0.63
e	2.3 X 10 <sup>-2</sup>	3.8 X 10 <sup>-9</sup>	0.46	6.4 X 10 <sup>-5</sup>	1.4 X 10 <sup>-9</sup>	0.55
4	1.6 X 10 <sup>-8</sup>	2.6 X 10 <sup>-12</sup>	0.47	2.0 X 10 <sup>-8</sup>	3.1 X 10 <sup>-12</sup>	0.63
S	1.8 X 10 <sup>-8</sup>	2.1 X 10 <sup>-12</sup>	0.46	1.9 X 10 <sup>-8</sup>	6.6 X 10 <sup>-13</sup>	0.57
9	2.2 X 10 <sup>-8</sup>	2.0 X 10 <sup>-11</sup>	0.40	1.3 X 10 <sup>-8</sup>	2.8 X 10 <sup>-12</sup>	0.57
~	2.5 X 10 <sup>-8</sup>	2.0 X 10 <sup>-12</sup>	0.42	1.1 X 10 <sup>-8</sup>	1.2 X 10 <sup>-12</sup>	0.61
æ	2.0 X 10 <sup>-4</sup>	1.2 X 10 <sup>-10</sup>	0.47	3.9 X 10 <sup>-5</sup>	3.8 X 10 <sup>-11</sup>	0.56
6	5.8 X 10 <sup>-4</sup>	1.6 X 10 <sup>-12</sup>	0.42	3.1 X 10 <sup>-9</sup>	3.8 X 10 <sup>-13</sup>	0.56
10	6.5 X 10 <sup>-11</sup>	1.1 X 10 <sup>-13</sup>	0.41	2.4 X 10 <sup>-11</sup>	6.2 X 10 <sup>-14</sup>	0.59



Fig. 1 The Convergence of Case #2

----

i

Ì



Fig. 2 The Convergence of Case #9

1

1

ì

## References

- B. D. O. Anderson and J. B. Moore, <u>Linear Optimal Control</u>, Prentice Hall, Englewood Cliffs, N. J., 1971.
- H. Kwakernaak and R. Sivan, <u>Linear Optimal Control Systems</u>, Wiley-Interscience, New York, 1972.
- 3) W. M. Wonham, "On a matrix Riccati equation of stochastic control," <u>SIAM Contr.</u>, Vol. 6, pp. 681-697, 1968.
- 4) W. T. Reid, <u>Riccati Differential Equations</u>, Academic Press, New York, 1972.
- 5) J. C. Willems, "Least squares stationary optimal control and the algebraic Riccati equation," <u>IEEE Trans. Automat. Contr.</u>, Vol. AC-16, pp. 621-634, 1971.
- L. M. Silverman, "Discrete Riccati equations: Alternative algorithms, asymptotic properties, and system theory interpretations," in <u>Advances</u> <u>in Control Systems</u>, Vol. 12, Leondes, ed., Academic Press, New York, pp. 313-386, 1976.
- 7) D. G. Lainiotis, "Partitional Riccati solutions and integration-free doubling algorithms," <u>IEEE Trans. Automat. Contr.</u>, Vol. AC-21, pp. 677-689, 1976.
- J. Jones, Jr., "Solution of certain matrix equations," <u>Proc. of the</u> <u>Am. Math. Soc.</u>, Vol. 31, pp. 333-339, 1972.
- 9) A. J. Laub, "A Schur methoid for solving algebraic Riccati equations," <u>IEEE Trans. Auto. Contr.</u>, Vol. AC-24, pp. 913-921, 1979.
- J. E. Potter, "Matrix quadratic solutions," <u>SIAM J. Appl. Math.</u>, Vol. 14, pp. 496-501, 1966.
- W. E. Holley and S. Y. Wei, "Improved methods for solving the algebraic Riccati equation," <u>AIAA J. Guidance and Contr.</u>, Vol. 3, pp. 190-192, 1980.

- 12) D. L. Kleinman, "On an iterative technique for Riccati equation computation," <u>IEEE Trans. Auto. Contr.</u>, Vol. AC-13, pp. 114-115, 1968.
- 13) B. T. Smith, et. al., "Matrix eigensystem routines EISPACK guide," 2nd Ed., <u>Lecture Notes in Computer Science</u>, Vol. 6, Springer Verlag, New York, 1976.

- 14) G. W. Stewart, "HQR3 and EXCHNG: Fortran subroutines for calculating and ordering the eigenvalues of a real upper Hessenberg matrix," <u>ACM Trans. Math. Software</u>, Vol. 2, pp. 275-280, 1976.
- 15) L. R. Anderson, "Decoupling and reduced order modeling of two-time-scale control systems," Ph.D. dissertation, University of Arizona, Tucson, 1979.
- 16) L. R. Anderson and W. L. Hallauer, Jr., "A method of order reduction for structural dynamics based on Riccati iteration," <u>AIAA Journal</u>, Vol. 19, pp. 796-800, 1981.
- 17) J. H. Chow and P. V. Kokotovic, "Eigenvalue placement in two-time-scale systems," in <u>Large Scale Systems Theory and Applications</u>, G. Guardabassi and A. Locatelli, eds., proc. of an IFAC symposium on Large Scale Systems, Udine, Italy, pp. 321-326, 1976.
- 18) L. R. Anderson, "Decoupling of two-time-scale linear systems," <u>Proc.</u> <u>1978 Joint Auto. Contr. Conf</u>., Vol. 4, Philadelphia, Pa., pp. 153-164, Oct. 1978.
- 19) B. Avramovic, "Subspace iterations approach to the time scale separation," <u>Proc. 18th IEEE Conference on Decision and Control</u>, Fort Lauderdale, Fla., pp. 684-687, Dec. 1979.
- 20) F. A. Farrar and R. C. DiPietro, "Comparative evaluation of numerical methods for solving the algebraic matrix Riccati equation," <u>Proc. 1977</u> <u>Joint Auto. Contr. Conf</u>., San Francisco, Ca., pp. 1543-1548, June 1977.

- G. Forsythe and C. B. Moler, <u>Computer Solution of Linear Algebraic Systems</u>, Prentice-Hall, Englewood Cliffs, New Jersey, 1967.
- 22) A. R. Baykan, "Comparison of algebraic Riccati equation solvers," M. S. Thesis, Aerospace and Ocean Eng. Dept., Va. Poly. Inst. and State Univ., 1981.

23) B. D. O. Anderson, "Second-order convergent algorithms for the steadystate Riccati equation," <u>Int. J. Control</u>, Vol. 28, pp. 295-306, 1978.

# A Literature Review of Robust Controller Design Methods

# Alok Das\*

### Abstract

This paper presents a literature survey on the methods available for designing robust controllers. A number of methods for reducing the trajectory/ performance index sensitivity in linear regulators are described. It is shown with the help of an example that decrease in system sensitivity to variation in parameters is obtained at the cost of a higher value for the performance index. A method for reducing the eigenvalue sensitivity is also discussed.

\* Graduate Research Assistant, Aerospace & Ocean Eng. Dept., VPI & SU

## Introduction

2

1

1.

Į i

1

The design of a controller for a system requires a mathematical model of the system. In most cases some of the parameters of the system will change with time. The changes in the parameters could occur due to a variety of reasons for example, aging of components, environmental changes, etc. It has been found that for some systems even small changes in certain key parameters could appreciably degrade the performance of the control system. Hence, it is very important to estimate the effect of changes in the system parameters on its overall performance and to use controllers which minimize this degradation in performance.

The problem then is, given a specified structure of the controller, to find the particular controller which yields a system with minimum sensitivity to variation in system parameters. Such controllers are usually called robust or insensitive controllers. The robust controllers with constant feedback gain matrix will be considered. Adaptive controllers provide an attractive alternative to the problem of varying system parameters. We will not discuss adaptive controllers here.

A large amount of literature is available on robust controller design using both classical and modern control theories. A brief literature survey is presented here and some of the more important methods are described. In the analysis, the system parameters are assumed to take an unknown but constant value around their known nominal value.

Appendix A contains a bibliography on robust controllers containing 173 references. The bibliography covers the following journals and conference proceedings from 1970 to 1980.

Allerton Conference on Circuit and System Theory IEEE Transactions on Automatic Control International Journal of Control Joint Automatic Control Conference IEEE Decision and Control Conference IFAC Symposium on System Stability and Adaptivity (1968, 1973) Automatica Some other important references are also included.

### Parameter Sensitivity Reduction in Linear Regulators:

A considerable amount of work has been done on the parameter sensitivity reduction in linear regulators. Most of the literature on this topic falls in one of the following catagories:

a) Trajectory sensitivity reduction

-----

1

i l

1

l

į

1:

1

1

b) Performance index sensitivity reduction

In both of these approaches to sensitivity reduction, the main objective is to achieve a trade off between optimality in the nominal performance and sensitivity to small parameter variations. In a recent paper Yedavalli and Skelton [1] treat the problem of trajectory sensitivity and performance index sensitivity in a unified way. We will now discuss the trajectory sensitivity reduction and combined trajectory and performance sensitivity reduction.

<u>Trajectory sensitivity reduction</u>. In this approach a quadratic trajectory sensitivity term is included in the integrand of the performance index. One of the initial papers on this is by Kahne [2]. This paper served as a starting point for a number of research efforts. Kahne implements the control in an open loop manner.

Let the linear time invariant system be given by:

$$\dot{x}(t) = Ax(t) + Bu(t), x(o) = x_o$$
 (1)

where x(t) is the state vector of dimension n

u(t) is the control vector of dimension m

A and B are the state and control matrices of appropriate dimensions.  $\alpha$  is a time invariant parameter of the system x, A may depend on  $\alpha$ . B and u are taken to be independent of  $\alpha$ .

In the linear regulator problem we determine the optimal control vector  $u^{*}(t)$  which minimizes the performance index (subject to system eq. (1)).

$$J = \frac{1}{2} x^{T}(T) F_{X}(T) + \frac{1}{2} \int_{0}^{1} [x^{T}(t) Q(t) x(t) + u^{T}(t) R(t) u(t)] dt \qquad (2)$$
(2)

where T is the final time.

Ι.

1:

11

F and Q(t) are positive semidefinite nxn matrices

and R(t) is positive definite mxm matrix.

To incorporate the trajectory sensitivity into the design, consider the <u>trajectory sensitivity vector</u>

$$\sigma = \frac{\partial x}{\partial \alpha} \bigg|_{\alpha} = \alpha \text{ nominal}$$

Differentiating (1) with respect to  $\alpha$  gives

$$\dot{\sigma} = A\sigma + A_{\alpha} x, \sigma(o) = o \qquad (3)$$

where  $A_{\alpha} = \frac{\partial A}{\partial \alpha}$ 

A trajectory sensitivity term is incorporated in the performance index and the problem becomes:

find u(t) that minimizes

$$J = \frac{1}{2} x^{T}(T)Fx(T) + \frac{1}{2} \int_{0}^{T} \{x^{T}Qx + u^{T}Ru + \sigma^{T}s\sigma\} dt$$
(4)

subject to

$$\dot{x} = Ax + Bu, x(o) = x_0$$
  
 $\dot{\sigma} = A\sigma + A_{\sigma}x, \sigma(o) = o$ 
(5)

Kahne solved this problem in the standard way.

This method has two major drawbacks:

 For each parameter considered the order of the system of equations to be solved increases by n. Kahne showed that this order could be somewhat reduced by using the fact that the feedback matrix obtained in symmetric. 2) The more important problem is that in a closed loop implementation, as is usually the case,  $\sigma(t)$  no longer represents the trajectory sensitivity. This was pointed out by Kreindler [3].

We will now formulate the problem for a closed loop implementation. In this case u and B will depend on the parameter  $\alpha$ . Then eq. (1) gives

$$\dot{\sigma} = A_{\alpha} + A\sigma + B_{\alpha}u + B \frac{\partial u}{\partial \alpha} \sigma(o) = 0$$
 (6)

Using the linear feedback law

$$u = K_{1}(t)_{X} + K_{2}(t)\sigma \qquad (7)$$

we get

$$\frac{\partial u}{\partial \alpha} = K_1 \sigma + K_2 \frac{\partial \sigma}{\partial \alpha}$$
(8)

Substituting in eq. (6),

$$\dot{\sigma} = (A_{\alpha} + B_{\alpha} K_{1}) \times + (A + B_{\alpha} K_{2} + BK_{1}) \sigma + BK_{2} \frac{\partial \sigma}{\partial \alpha}, \sigma(\sigma) = 0 \qquad (9)$$

The second order derivative  $\frac{\partial \sigma}{\partial \alpha}$  is neglected because the only way it can be obtained is by differentiating eq. (9) with respect to  $\alpha$ , this introduces  $\frac{\partial^2 \sigma}{\partial \alpha^2}$  term and so on. The solution of eq. (9) with  $\frac{\partial \sigma}{\partial \alpha}$  neglected will provide an <u>approximate trajectory sensitivity vector p(t)</u>.

If p(t) is used in the feedback law, then  $u = K_1 + K_2 p$  (10) and substituting in eq. (1) we get

$$\dot{x} = (A + BK_1)x + BK_2p, x(o) = x_0$$
 (11)

Differentiating (11) with respect to a (neglecting  $\frac{\partial p}{\partial \alpha}$  and letting  $\frac{\partial x}{\partial \alpha} = p$ ) gives

$$\dot{p} = (A_{\alpha} + B_{\alpha}K_{1})x + (A + BK_{1} + B_{\alpha}K_{2})p, p(o) = o$$
 (12)

Exact differentiation of (11) yields

$$\dot{\sigma} = (A_{\alpha} + B_{\alpha}K_{1})x + B_{\alpha}K_{2}p + (A + BK_{1})\sigma + BK_{2}\frac{\partial p}{\partial \alpha}, p(o) = 0$$
(13)

where  $\frac{\partial p}{\partial \alpha}$  can be obtained from

$$\frac{\partial \dot{p}}{\partial \alpha} = (A_{\alpha} + B_{\alpha} K_{1})\sigma + (A + BK_{1} + B_{\alpha} K_{2}) \frac{\partial p}{\partial \alpha}, \frac{\partial p}{\partial \alpha} (o) = o \qquad (14)$$

The difference between p and  $\sigma$  can be reduced by taking  $u = \hat{K}_1 \times + \hat{K}_2 p$ where  $\hat{K}_1$  and  $\hat{K}_2$  are chosen so as to reduce the difference between p and  $\sigma$ . Then,

$$\dot{x} = (A + B\hat{K}_1) x + B\hat{K}_2 p$$
 (15)

$$\dot{p} = (A_{\alpha} + B_{\alpha} \tilde{K}_{1})x + (A + B\tilde{K}_{1} + B_{\alpha} \tilde{K}_{2})p, p(o) = o$$
 (16)

and 
$$\frac{\partial \dot{p}}{\partial \alpha} = (A_{\alpha} + B_{\alpha} \tilde{K}_{1})\sigma + (A + B\tilde{K}_{1} + B_{\alpha}\tilde{K}_{2}) \frac{\partial p}{\partial \alpha}, \frac{\partial p(o)}{\partial \alpha} = 0$$
 (17)

A number of authors have used this formulation to solve the problem of closed loop trajectory sensitivity. Some of the important works will now be discribed.

Kreindler [3] used the approximate trajectory sensitivity vector p(t) in his formulation. Using equations (1) and (16) he constructed an augmented system of order 2n.

Take 
$$Z = \begin{bmatrix} x \\ p \end{bmatrix}$$
  
then  
 $\dot{Z} = \overline{A}Z + \overline{B}u, Z(o) = Z_0$  (18)  
where  $\overline{A} = \begin{bmatrix} A & 0 \\ (A_{\alpha} + B_{\alpha} \hat{K}_{1}) & (A + B\hat{K}_{1} + B_{\alpha} \hat{K}_{2}) \end{bmatrix}, \overline{B} = \begin{bmatrix} B \\ 0 \end{bmatrix}$   
and  $Z_{0} = \begin{bmatrix} X \\ 0 \end{bmatrix}$   
also  $u = [\hat{K}_{1} \hat{K}_{2}]Z$ 

The augmented problem solved by Kreindler was to find  $\hat{K}_1$  and  $\hat{K}_2$  so as to minimize

$$J = \int_{0}^{T} (Z^{T} \overline{Q}Z + u^{T}Ru)dt$$
 (19)

subject to (18)

## Where

1

$$\overline{\mathbf{Q}} = \begin{bmatrix} \mathbf{Q} & \mathbf{0} \\ \mathbf{0} & \mathbf{s} \end{bmatrix}$$

Q and S are positive semidefinite nxn matrices and R is a positive definite mxm matrix.

This is now a standard linear regulator problem and the solution is given by:

$$K = [K_1 \ K_2] = -R^{-1} \ \overline{B}^T \overline{P}_1$$
(20)

where  $\overline{R}$  is the solution of the matrix Riccati eq.

$$-\hat{R} = \bar{A}^{T}\bar{R} + \bar{P}\bar{A} - \bar{R}\bar{B}\bar{R}^{-1}\bar{B}^{T}\bar{R} + \bar{Q}, \bar{R}(T) = 0$$
(21)

As an initial estimate for  $\hat{K}_1$  and  $\hat{K}_2$ , Kreindler takes them to be  $K_1$  and  $K_2$ , but then eq. (21) is no longer one of the Riccati type because  $\overline{A}$  depends on  $K_1$ . for wortheless he chooses  $K_1$  and  $K_2$  to satisfy eqs. (20) and (21).

This approach works well as long as p does not differ much from the true trajectory sensitivity vector  $\sigma$ .

Rao and Soudack [4] modified the above procedure so that one can get a better approximation for  $\sigma$ . They also use p in the cost functional but use a generalized version of Eq.(16).

$$\dot{p} = C_x + D_p, p(o) = o$$
 (22)

Matrices C and D contain as many parameters as one may consider necessary to get a close approximation for  $\sigma$  by the procedure described below. From eq. (22) we get

$$\frac{\partial \dot{p}}{\partial \alpha} = C\sigma + D \frac{\partial p}{\partial \alpha}, \frac{\partial p}{\partial \alpha} \begin{pmatrix} 0 \end{pmatrix} = 0$$
(23)

In this case the augmented system of equations are

$$\dot{Z} = \overline{A}Z + \overline{B}u, Z(o) = Z_o$$
 (24)

where

$$\overline{A} = \begin{bmatrix} A & 0 \\ C & D \end{bmatrix}, \ \overline{B} = \begin{bmatrix} B \\ 0 \end{bmatrix} \text{ and } Z_0 = \begin{bmatrix} x_0 \\ 0 \end{bmatrix}$$

The procedure is to choose a set of values for the parameters in C and D and with the new expression for  $\overline{A}$  to find a K by solving eqns. (20) and (21). This will minimize J given by (19). With this K, the parameters in C and D are varied so as to minimize  $J_2 = \int_{-1}^{1} ||p - \sigma||^2 dt$ 

For this, eqns (11), (13), (22) and (23), have to be integrated simultaneously for  $\alpha = \alpha_{nominal}$ . The new values of C and D are used to again solve the Riccati equation to get a new K. This procedure is repeated until J<sub>2</sub> reduces to an acceptable level.

This procedure may give better results than Kreindler's procedure, but its computational complexity is far greater than that of the latter.

Fleming and Newmann [5] use the exact trajectory sensitivity vector o in the performance index but use the approximate trajectory sensitivity vector p in the feedback law. They define the augmented state vector Z as



Using eqns. (11), (12), (13) and (14) the augmented eqns can be written as (of order 4n)

ż

$$= \overline{A}Z, Z(0) = Z_{0}$$
 (25)

where

$$A = \begin{bmatrix} A + BK_{1} & BK_{2} & 0 & 0 \\ A_{\alpha} + B_{\alpha} K_{1} & A + BK_{1} + B_{\alpha} K_{2} & 0 & 0 \\ A_{\alpha} + B_{\alpha} K_{1} & B_{\alpha} K_{2} & A + BK_{1} & BK_{2} \\ 0 & 0 & A_{\alpha} + B_{\alpha} K_{1} & A + BK_{1} + B_{\alpha} K_{2} \end{bmatrix}$$

and 
$$Z_0 = \begin{bmatrix} x_0 \\ 0 \\ 0 \\ 0 \end{bmatrix}$$

The performance index is

$$J = \int_0^T (x^T Q x + \sigma^T s \sigma + u^T R u) dt$$

This can be written as

$$J = \int_{0}^{T} Z^{T} (\overline{Q} + E^{T} K^{T} RKE) Z dt$$
 (26)

where

Ŀ

L

$$\overline{Q} = \begin{bmatrix} Q & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 3 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix}, E = \begin{bmatrix} I_{2n} & 0_{2n} \end{bmatrix} \text{ and } K = \begin{bmatrix} K_1 & K_2 \end{bmatrix}$$

The problem then becomes to choose K so as to minimize J subject to (25). Clearly this is not a linear regulator problem in its standard form and the authors describe a few computational methods of solving it.

In the three approaches given till now, one either neglects the second order derivative term  $\frac{\partial \sigma}{\partial \alpha}$  or uses successive minimization techniques. In an interesting correspondence Byrne and Burke [6] use a slightly different approach. They use the optimal control for the regulator problem without sensitivity constraints as an initial approximation to the optimal control with sensitivity constraints. Let the optimal control for the problem without trajectory constraints be

where K is given by

$$K = -R^{-1}B^{T}P_{1}$$
 (28)

and  ${\ensuremath{\mathtt{R}}}$  is the solution of the Riccati eq.

$$\dot{P} + PA + A^{T}P + Q - PBR^{-1}B^{T}P = 0, P(T) = 0$$
 (29)

Differentiating u with respect to parameter a gives

$$\frac{\partial u}{\partial \alpha} = K_{\sigma} + K_{\alpha} x \qquad (30)$$

where  $K_{\alpha} = \partial K / \partial \alpha$ 

and differentiating (28) with respect to  $\alpha$  gives

$$K_{\alpha} = -R^{-1}B^{T}\sum_{\alpha} -R^{-1}B_{\alpha}^{T}P_{1}$$
(31)  
where  $\sum_{\alpha} = \frac{\partial P_{1}}{\partial \alpha}$ 

Differentiating (29) with respect to  $\alpha$ 

$$\sum + \sum (A - BR^{-1}B^{T}P_{1}) + (A - BR^{-1}B^{T}P_{1})^{T}\sum + (PA_{\alpha} + A_{\alpha}^{T}P_{1})$$
  
-P\_{1}(B\_{\alpha} R^{-1}B^{T} + BR^{-1}B\_{\alpha}^{T}) P\_{1} = 0, \sum(0) = 0 (32)

This equation is solved to give  $\sum$ . Substituting eq. (30) in eq. (6), we get

$$\dot{\sigma} = (A + BK) \sigma + (A_{\sigma} + BK_{\sigma}) x + B_{\alpha}u, \sigma(o) = o$$
 (33)

Then using the augmented vector Z =  $\begin{bmatrix} x \\ \sigma \end{bmatrix}$ , the augmented system becomes

$$\dot{z} = \overline{A}Z + \overline{B}u, Z(o) = Z_o$$
 (34)

where

$$\overline{A} = \begin{bmatrix} A & 0 \\ \\ \\ A_{\alpha} + BK_{\alpha} & A + BK \end{bmatrix}, \quad \overline{B} = \begin{bmatrix} B \\ \\ B_{\alpha} \end{bmatrix}, \quad Z_{0} = \begin{bmatrix} x_{0} \\ \\ 0 \end{bmatrix}$$

The problem is now to minimize the performance index given by (19) subject to (34). This is a standard regulator problem and the solution is

$$u = -R^{-1}\overline{B}^{T}\overline{P}Z$$
 (35)

where  $\overline{P}_1$  is the solution of the equation

١.,

t

ł

$$\dot{P}_{I} + P_{I}\overline{A} + \overline{A}^{T}P_{I} + \overline{Q} - P_{I}\overline{B}\overline{R}^{-1}\overline{B}^{T}\overline{P}_{I} = 0, P_{I}(T) = 0$$
 (36)

A number of comparisons have been made between these methods and the results of these depend very much on the problem at hand. But if one was to use a comparison index of some sort composed of reduction in sensitivity per unit increase in cost and the numerical effort required, then the routine of Kreindler and Byrne and Burke would probably come out whead.

<u>Combined trajectory and performance index sensitivity reduction</u>: The parameter sensitivity of the performance index is important because the optimal control is obtained by minimizing the given performance index. Yahagi [7] worked on this problem and gave necessary conditions for an optimal output feedback control with reduced performance index sensitivity.

Yedavalli and Skelton [1] established relationship between the trajectory and performance index sensitivities. They exploit this relationship to present a unified way of reducing trajectory (output or state) sensitivity and performance index sensitivity. Their method also considers control sensitivity, something which is ignored by most authors. Although Yedavalli and Skelton developed their method for the general case of r parameters, we will describe it for the case of one parameter only. This somewhat reduces the notational complexity.

Using the notation developed earlier, the linear time invariant system is

$$\dot{x} = Ax + Bu, x(o) = x_0$$
 (37)

$$y = C_X \tag{38}$$

where

y is a k dimensional output vector and C is the output matrix.

The performance index of the unperturbed problem is

$$J = \int_{0}^{\infty} (y^{T}Qy + u^{T}Ru)dt$$
 (39)

where

L

Q and R are symmetric positive definite matrices. The standard solution of this is

$$u = Kx$$
(40)

where  $K = -R^{-1}B^{T}P_{1}$  (41)

and  $P_l$  is the unique positive definite solution of the matrix Riccati equation

$$P_{I}A + A^{T}P_{I} - P_{I}BR^{-1}B^{T}P_{I} + C^{T}QC = 0$$
 (42)

Let  $\alpha$  be the uncertain parameter and A, B, C,  $\times$  and y are continuous functions of  $\alpha$ . The sensitivity vectors are

State trajectory sensitivity vector  $\sigma = \frac{\partial x}{\partial \alpha}$ Output trajectory sensitivity vector  $y_{\alpha} = \frac{\partial y}{\partial \alpha}$ Control trajectory sensitivity vector  $u_{\alpha} = \frac{\partial u}{\partial \alpha}$ and performance index sensitivity  $J_{\alpha} = \frac{\partial J}{\partial \alpha}$ 

From equations (37) and (38) we get  $\dot{\sigma} = A_{\alpha}x + A\sigma + B_{\alpha}u + Bu_{\alpha}, \sigma(o) = o$  (43)  $y_{\alpha} = C_{\alpha}x + C\sigma$  (44)

Where the subscript  $\alpha$  denotes partial derivative with respect to  $\alpha$ 

Using 
$$Z = \begin{bmatrix} x \\ \sigma \end{bmatrix}$$
 and  $W = \begin{bmatrix} y \\ y_{\alpha} \end{bmatrix}$  the augmented system is  
 $\dot{Z} = \bar{A}Z + \bar{B}u + \hat{B} u_{\alpha}, Z(o) = Z_{0}$ 
(45)  
 $W = \bar{C}Z$ 
(46)

where

$$\bar{A} = \begin{bmatrix} A & 0 \\ A_{\alpha} & A \end{bmatrix}, \quad \bar{B} = \begin{bmatrix} B \\ B_{\alpha} \end{bmatrix}, \quad \hat{B} = \begin{bmatrix} 0 \\ B \end{bmatrix}$$
$$\bar{C} = \begin{bmatrix} C & 0 \\ C_{\alpha} & C \end{bmatrix} \quad \text{and} \quad Z_{0} = \begin{bmatrix} x_{0} \\ 0 \end{bmatrix}$$

The authors define a new performance index which in addition to the output sensitivity term also contains control sensitivity term.

$$J_{s} = \int_{0}^{\infty} \left\{ y^{T}Qy + y^{T}_{\alpha}Q_{1}y_{\alpha} + u^{T}_{\alpha}R_{1}u_{\alpha} + u^{T}Ru \right\} dt$$
(47)

where  $Q_1$  and  $R_1$  are positive definite matrices.

The norms  $y_{\alpha}^{T} Q_{T} y_{\alpha}$ ,  $u_{\alpha}^{T} R_{T} u_{\alpha}$  and  $|kJ_{\alpha}|$  are functions of time. They showed that  $J_{s}$  is an upper bound to these three norms. where

 $\boldsymbol{k}_1$  is a nonzero scalar such that the matrix

 $S_{c} = \begin{bmatrix} S & \pm \alpha s \\ \\ \pm \alpha s^{T} & \overline{s} \end{bmatrix}$  is positive definite

with S = block diagonal [Q, R]  $\bar{S}$  = block diagonal [Q<sub>1</sub>,R<sub>1</sub>]

They also showed that if  $\frac{\partial^2 y}{\partial \alpha^2}$  and  $\frac{\partial^2 u}{\partial \alpha^2}$  are zero, then,

$$\int_{0}^{\infty} (y_{\alpha}^{T} Q_{\gamma} y_{\alpha} + u_{\alpha}^{T} R_{\gamma} u_{\alpha}) dt = \frac{1}{2} \beta \frac{\partial^{2} J}{\partial \alpha^{2}}$$
(48)

This relates the trajectory sensitivity terms  $y_{\alpha}^{T} Q_{1} y_{\alpha}$  and  $u_{\alpha}^{T} R_{1} u_{\alpha}$  in (47) with the performance index sensitivity  $J_{\alpha}$ .

All this implies that minimization of J<sub>s</sub> achieves a trade-off between

unperturbed optimal cost J and the sensitivities (output, control and performance index). Although  $J_{\alpha}$  is not included in the performance index  $J_{s}$ , performance index sensitivity reduction is obtained as a "byproduct".

Using equation (38) and (44)

$$y^{T} Qy + y^{T}_{\alpha} Q_{1}y_{\alpha} = x^{T}C^{T}QCx + (x^{T}C^{T}_{\alpha} + \sigma^{T}C^{T})Q (C_{\alpha}x + C\sigma)$$

then  $\boldsymbol{J}_{\boldsymbol{S}}$  becomes

$$J_{s} = \int_{0}^{\infty} \left\{ \begin{bmatrix} x^{T} \sigma^{T} \end{bmatrix} \begin{bmatrix} (c^{T}Qc + c_{\alpha}^{T}Q_{1}c_{\alpha}) & c_{\alpha}^{T}Q_{1}c \\ \\ c^{T}Q_{1}c_{\alpha} & c^{T}Q_{1}c \end{bmatrix} \begin{bmatrix} x \\ \sigma \end{bmatrix} + \begin{bmatrix} u^{T}u_{\alpha}^{T} \end{bmatrix} \begin{bmatrix} R & 0 \\ \\ 0 & R \end{bmatrix} \begin{bmatrix} u \\ u_{\alpha} \end{bmatrix} \right\} dt$$

$$(49)$$

The above expression requires  $u_{\alpha}$ . Since the desired control law

$$u = k_1 x + k_2 \sigma$$
 (50)

is not available, the authors use the control for the unperturbed problem (given by eqs. (40), (41) and (42)) to obtain an approximate  $u_{\alpha}$ .

Then the approximate control sensitivity  $u_{\alpha a}$  is given by

$$u_{\alpha a} = kp$$
 (51)

where p is the approximate trajectory sensitivity.

Substituting equation (51) in eq. (43),

$$\dot{p} = A_{\alpha} x + (A + BK)p + B_{\alpha} u$$
(52)
Defining  $Z_a = \begin{bmatrix} x \\ p \end{bmatrix}$ , we get
$$\dot{Z}_a = A_1 Z_a + B_1 u, Z_a(o) = Z_{ao}$$
(53)
$$u_{\alpha_a} = \hat{K} Z_a$$
(54)

where

$$A_{1} = \begin{bmatrix} A & 0 \\ \\ \\ A_{\alpha} & (A + BK) \end{bmatrix}, B_{1} = \begin{bmatrix} B \\ \\ \\ B_{\alpha} \end{bmatrix}, Z_{a_{0}} = \begin{bmatrix} x_{0} \\ \\ \\ 0 \end{bmatrix} \text{ and } \hat{K} = [0 \ K]$$

The performance index  $J_{s}$  becomes (using  $u_{\alpha a}$  for  $u_{\alpha})$ 

$$J_{s} = \int_{0}^{\infty} (Z_{a}^{T} U_{a} Z_{a} + u^{T} R u) dt$$
(55)
where  $U_{a} = \begin{bmatrix} (c^{T} Q c + c_{\alpha}^{T} Q_{1} C_{\alpha}) & c_{\alpha}^{T} Q_{1} C \\ c^{T} Q_{1} C_{\alpha} & (c^{T} Q_{1} C + K^{T} R_{1} K) \end{bmatrix}$ 

The problem is to minimize  $J_s$  subject to equation (53). This is a standard regulator problem and the solution is

$$u = \bar{K} Z_a = \bar{K}_1 x + \bar{K}_2 p$$
 (56)

where 
$$\bar{K} = -R^{-1}B_1^T \bar{P}_1$$
 (57)

 $\overline{\textbf{P}}_{l}$  is the positive definite solution of the Riccati equation

$$\vec{P}_{1} + A_{1}^{T}\vec{P}_{1} - \vec{P}_{1}B_{1}R^{-1}B_{1}^{T}\vec{P}_{1} + U_{a} = 0$$
(58)

So the steps in the Yedavalli and Skelton procedure are

- (a) Compute K given by eqns. (41) and (42)
- (b) Form the matrices  $A_1$ ,  $B_1$  and  $U_a$

(c) The desired control is given by equations (56), (57) and (58).

As pointed earlier, results of comparisons between the various methods depends on the problem used. Keeping this in mind we will now use a first order example for the comparison of the methods described above. This example has been used by a number of authors for this purpose. The first order plant is

$$\dot{x} = \alpha^2 x + u, x(0) = 1$$

where  $\alpha$  is the parameter with a nominal value of 1. The objective is to minimize the trajectory sensitivity.

The performance index is given by

$$J = \int_{0}^{\infty} (x^{2} + u^{2}) dt$$

To aid in the comparison of the various methods, the sensitivity integral, S, is also evaluated along with J for each of the methods. S is given by

$$S = \int_{0}^{\infty} \sigma^2 dt$$

The results of this are given in table 1. Clearly for all the algorithms a comparison with the simple regulator reveals that the decrease in sensitivity measured by S is obtained at the expense of a higher cost given by J. The best method would be the one which for the least increase in J will give the maximum decrease in S. The method of Byrne and Burke is the best for this example. The methods of Rao and Saudack and Fleming and Newman require much more computation than the other methods.

## Eigenvalue Sensitivity

Besides the trajectory and performance index (cost) sensitivities there is another important means of estimating the sensitivity of the system to variations in its parameters. This is through the use of eigenvalue/eigenvector sensitivity. It should be mentioned here that eigenvalue/eigenvector sensitivity provides a less direct measure of the system sensitivity than trajectory or cost sensitivity. Designers working with classical design techniques tend to use eigenvalue sensitivity.

Crossby and Porter [8] developed expressions for eigenvalue and eigenvector sensitivities for linear time invariant systems. Reddy [9] also worked on the problem of determining the effects of variation in system parameters on eigenvalues. Although they provided explicit expressions for the sensitivity, these authors do not suggest a method of reducing the eigenvalue/eigenvector sensitivity. In an interesting paper Gourishankar and Ramar [10] combine the problems of reducing eigenvalue sensitivity and closed loop eigenvalues (pole) placements for a linear time invariant multivariable system. We will now discuss their approach in some detail.

It has been known for a long time that using complete state feedback the closed loop poles can be assigned to any desired location. It is also known that for multiinput systems a number of feedback matrices give the desired closed loop pole locations. These controllers will in general give different time responses. Designers usually use this freedom to obtain other desired characteristics in the system response. Gourishankar and Ramar use this freedom to minimize the sensitivity of the closed loop eigenvalues to the variation in the system parameters without effecting their desired location. In the following development, the closed-loop poles are taken to be distinct.

Using the notation of the previous chapter, the linear time invariant system is given by

$$\dot{\mathbf{x}} = \mathbf{A}\mathbf{x} + \mathbf{B}\mathbf{u} \tag{1}$$

and the feedback law is

where K is mxn time invariant feedback matrix.

The closed loop system is then given by

$$\dot{\mathbf{x}} = (\mathbf{A} + \mathbf{B}\mathbf{K})\mathbf{x} \tag{3}$$

Keeping in mind that n elements of the mxn feedback matrix are sufficient to place the n closed loop poles to their desired location, we subdivide the feedback matrix into two parts as follows

$$\bar{\mathbf{K}} = [\mathbf{k}_1^{\mathsf{T}} \ \mathbf{k}_2^{\mathsf{T}} \ ---\mathbf{k}_{i-1}^{\mathsf{T}} \ \mathbf{k}_{i+1}^{\mathsf{T}} \ ---\mathbf{k}_m^{\mathsf{T}}]^{\mathsf{T}}$$

and  $\hat{k} = k_i$ 

and

where  $k_j$  is the jth row of the K matrix, j = 1, 2, --m

The vector  $\hat{k}$  is used to obtain the desired pole locations while the elements of the matrix  $\bar{K}$  are chosen to reduce the eigenvalue sensitivity. Define

$$\vec{u} = \begin{bmatrix} u_1 & u_2 & \cdots & u_{i-1} & u_{i+1} & \cdots & u_m \end{bmatrix}^T$$
and  $\hat{u} = u_i$ 
Eq. (2) becomes
$$\vec{u} = \vec{k}x$$
(4)
$$\hat{u} = \hat{k}x$$
(5)

We can now write eq. (1) as

$$\dot{\mathbf{x}} = (\mathbf{A} + \mathbf{B}\,\mathbf{\bar{K}})\mathbf{x} + \mathbf{\hat{b}}\,\mathbf{\hat{u}} \tag{6}$$

where

 $\hat{B} = [b_1 \ b_2 \ ----b_{i-1} \ b_{i+1} \ ----b_m]$  and  $\hat{b} = b_i$ 

 $b_i$ 's being the columns of the matrix B.

Eq. (6) represents a single input system  $(\hat{u} = u_i)$  and the feedback vector  $\hat{k}$  in eq. (5) can be designed to place the closed loop poles in their specified location. This can always be done as long as the pair  $(A + \bar{B} \bar{K}, \hat{b})$  is completely controllable. Since  $A + \bar{B} \bar{K}$  depends on  $\bar{K}$ , care has to be taken while selecting  $\bar{K}$  so as to maintain the above mentioned pair completely controllable. The authors have mentioned that this is not a serious limitation as almost any  $\bar{K}$  satisfies this requirement.

Substituting eq. (5) in (6) yields the closed loop system

$$\dot{\mathbf{x}} = (\mathbf{A} + \mathbf{B} \,\mathbf{\bar{K}} + \mathbf{\hat{b}} \,\mathbf{\hat{k}})\mathbf{x}$$
(7)

It is to be noted that the feedback vector  $\hat{k}$  depends on A +  $\bar{B}$   $\bar{K}$  and hence on  $\bar{K}.$ 

Morgan [11] gave the expression for the sensitivity of the closed loop eigenvalues to the variations in the elements of the system matrix A.

$$S_{j\ell}^{i} = \frac{\partial S_{i}}{\partial a_{j\ell}} = \frac{1}{(\partial g(s)/\partial s)/s=s_{i}} \operatorname{trace} \left[R(S_{i}) \frac{\partial A}{\partial a_{j\ell}}\right]$$
 (8)

where

Ŀ

 $S_{j\mathcal{L}}^{i}$  is the sensitivity of the eigenvalue  $S_{i}$  to a small variation in the element  $a_{j\mathcal{L}}$  of the system matrix A, g(s) is the characteristic polynamial of the closed loop system,  $R(S_{i}) = adjoint (S_{i} I - \hat{A})$ and  $\hat{A} = A + \bar{B} \bar{K} + \hat{b} \hat{k}$  The authors choose the elements of the matrix  $\bar{K}$  so as to minimize the performance index

$$J = \sum_{i=1}^{n} \sum_{j=1}^{n} \sum_{\ell=1}^{n} (S_{j\ell}^{i})^{2}$$
(9)

If only the  $a_{jl}$  element is changing, the performance index becomes

$$J = \sum_{i=1}^{n} (S_{j\ell}^{i})^{2}$$
(10)

The authors mention that transforming to phase-variable form facilitates in the minimization of J.

The procedure can be summarized as follows

- (a) Choose  $\bar{K}$  so as to minimize J
- (b) With this value of  $\bar{K}$  find k which assigns the closed loop poles to the desired location.

Any row of matrix  $\bar{k}$  can be used as  $\hat{k}$ . One could take the rows of  $\bar{k}$  as  $\hat{k}$  one at a time and calculate  $J_{\min n}$  each time. Then choose that row of  $\bar{k}$  as  $\hat{k}$  for which the lowest  $J_{\min n}$  was obtained. This is usually not done as the amount of computation increases enormously

The design procedure is illustrated by the following linear time invariant second-order system with two inputs and two outputs,

$$\dot{x} = Ax + Bu$$
(11)

where

ł

1:

1

$$A = \begin{bmatrix} a_{11} & a_{12} \\ \\ a_{21} & a_{22} \end{bmatrix} , B = \begin{bmatrix} 1 & 1 \\ \\ 0 & 1 \end{bmatrix}$$

The nominal values of  $a_{11}$ ,  $a_{12}$ ,  $a_{21}$  and  $a_{22}$  are 0, 1, 0 and 0 respectively.

Only  $a_{21}$  varies from its nominal value. The desired location for the closed loop poles is  $S_1 = -2$  and  $S_2 = -3$ . The feedback matrix is

 $K = \begin{bmatrix} k_{11} & k_{12} \\ k_{21} & k_{22} \end{bmatrix} = \begin{bmatrix} \hat{k} \\ R \end{bmatrix}$ 

then

1.

Ì

ł

i...

-

i

ļ.

I

Ľ

$$B = [\hat{b} \ \bar{B}]$$
  
and  $\hat{A} = \begin{bmatrix} 0 & 1 \\ a_{21} & 0 \end{bmatrix} + \begin{bmatrix} 1 \\ 1 \end{bmatrix} \begin{bmatrix} k_{21} & k_{22} \end{bmatrix} + \begin{bmatrix} 1 \\ 0 \end{bmatrix} \begin{bmatrix} k_{11} & k_{12} \end{bmatrix}$ 
$$= \begin{bmatrix} (k_{11} + k_{21}) & (1 + k_{12} + k_{22}) \\ (a_{21} + k_{21}) & k_{22} \end{bmatrix}$$

This gives

$$\frac{\partial \dot{A}}{\partial a_{21}} = \begin{bmatrix} 0 & 0 \\ 0 \\ 1 & 0 \end{bmatrix}$$

and R(s) = Adjoint 
$$\begin{bmatrix} (s - k_{11} - k_{21}) & -(1 + k_{12} + k_{22}) \\ - (a_{21} + k_{21}) & (s - k_{22}) \end{bmatrix}$$
$$= \begin{bmatrix} (s - k_{22}) & (1 + k_{12} + k_{22}) \\ (a_{21} + k_{21}) & (s - k_{11} - k_{21}) \end{bmatrix}$$

Now trace R(s) 
$$\frac{\partial \lambda}{\partial a_{21}} = \text{tre } e_{21} \begin{bmatrix} (1 + k_{12} + k_{22}) & 0 \\ (s - k_{11} - k_{21}) & 0 \end{bmatrix}$$
  
=  $(1 + k_{12} + \frac{1}{22})$   
g(s) =  $(s - k_{11} - k_{21}) (s - k_{22}) - (1 + k_{12} + k_{22}) (a_{21} + k_{21})$   
 $\therefore \frac{\partial g(s)}{\partial s} = 2s - (k_{11} + k_{21} + k_{22})$   
The eq. (8) now gives  
 $s_{21}^{-1} = \frac{\partial s}{\partial a_{21}} \Big|_{s = -2} = \frac{-(1 + k_{12} + k_{22})}{(k_{11} + k_{21} + k_{22} + 4)}$ 

$$S_{21}^{2} = \frac{\partial S}{\partial a_{21}} \bigg|_{S = -3} = \frac{-(1 + k_{12} + k_{22})}{(k_{11} + k_{21} + k_{22} + 6)}$$

The performance index becomes

ŧ

1

í ķ

$$J = (S_{21}^{1})^{2} + (S_{21}^{2})^{2}$$
  
=  $(1 + k_{12} + k_{22})^{2} \left\{ \frac{1}{(k_{11} + k_{21} + k_{22} + 4)^{2}} + \frac{1}{(k_{11} + k_{21} + k_{22} + 6)^{2}} \right\}$ 

We have to choose  $\bar{K}$  so as to minimize J. J takes its minimum value 0 if

 $k_{22} = -(1 + k_{12})$   $k_{11} + k_{21} + k_{22} + 4 \neq 0$ and  $k_{11} + k_{21} + k_{22} + 6 \neq 0$ 

Take 
$$k_{21} = 0$$
  
For  $a_{21} = 0$ , we get  
 $g(s) = s^2 - s(k_{11} + k_{21} + k_{22}) + k_{11} k_{22} - k_{21} - k_{12} k_{21}$   
Substituting the values of  $k_{21}$  and  $k_{22}$  in the above expression,  
 $g(s) = s^2 - s(k_{11} - k_{12} - 1) - k_{11} (1 + k_{12})$   
 $k_{11}, k_{12}$  have to be chosen so as to get the desired characteristic polynomial  
 $(s + 2) (s + 3) = s^2 + 5s + 6$   
Equating the two polynomials, we get  
 $k_{11} - k_{12} - 1 = -5$   
and  $k_{11} (1 + k_{12}) = -6$   
Solving for  $k_{12}$ ,  
 $(k_{12} - 4) (1 + k_{12}) = -6$   
or  $k_{12}^2 - 3 k_{12} + 2 = 0$   
or  $(k_{12} - 2) (k_{12} - 1) = 0$   
 $\therefore k_{12} = 2, 1$   
 $k_{11} = -2, -3$   
 $k_{22} = -3, -2$   
 $k_{21} = 0$   
This gives the desired feedback matrix as  
 $K = \begin{bmatrix} -2 & 2 \\ 0 & -3 \end{bmatrix}$  or  $\begin{bmatrix} -3 & 1 \\ 0 & -2 \end{bmatrix}$ 

í

Į

Į

{

### References

1

Ì

- 1. Yedavalli, R., and Skelton, R. E., "Controller Design for Parameter Sensitivity Reduction in Linear Regulators", 18th Allerton Conference on Circuit and System Theory, 1980, pp. 414-423.
- Kahne, S. J., "Low-Sensitivity Design of Optima! Linear Control Systems", IEEE Transactions on Aerospace and Electronic Systems, Vol. AES-4, No. 3, 1968, pp. 374-379.
- 3. Kreindler, E., "On Minimization of Trajectory Sensitivity", International Journal of Control, Vol. 8, No. 1, 1968, pp. 89-96.
- 4. Rao, S. G., and Soudack, A. C., "Synthesis of Optimal Control System with Near Sensitivity Feedback", IEEE Transaction on Automatic Control, Vol. AC-16, 1971, pp. 194-196.
- 5. Flemming, P. J., and Newmann, M. M., "Trajectory Sensitivity Reduction in the Optimal Linear Regulator", Recent Mathematical Developments in Control, Bell, D. J., Editor, Academic, 1973, pp. 137-151.
- Byrne, P. C., and Burke, M., "Optimization with Trajectory Sensitivity Considerations", IEEE Transactions on Automatic Control, Vol. AC-21, 1976, pp. 282-283.
- 7. Yahagi, T., "Optimal Output Feedback Control with Reduced Performance Index Sensitivity", International Journal of Control, Vol. 25, 1977, pp. 769-783.
- 8. Crossley, T. R., and Porter, B., "Eigenvalue and Eigenvector Sensitivities in Linear Systems Theory", International Journal of Control, Vol. 10, 1969, pp. 163-170.
- Reddy, D. C., "Eigenfunction Sensitivity and the Parameter Variation Problem", International Journal of Control, Vol. 9, 1969, pp. 561-568.
- Gaurishankar, V., and Ramar, K., "Pole Assignment with Minimum Eigenvalue Sensitivity to Plant Parameter Variations", International Journal of Control, Vol. 23, 1976, pp. 493-504.
- Morgan, S. B., "Sensitivity Analysis and Synthesis of Multivariable Systems", IEEE Transactions on Automatic Control, Vol. 11, 1966, pp. 506-512.

# ROBUST CONTROLLER DESIGN FOR LARGE PARAMETER VARIATIONS

#### Leonard R. Anderson\*

### ASSUMPTIONS

- 1) The physical process depends on a <u>few</u> key parameters  $\alpha_1$ , ...,  $\alpha_N$ . (For wing flutter suppression these would be dynamic pressure, fuel load in wings, etc). N would not typically be larger than 2 or 3.
- These N parameters vary c or limits that are either <u>specified</u>, or <u>to</u> <u>be determined</u> in the design process.

$$\alpha_{i} \leq \alpha_{i} \leq \alpha_{i} \quad i = 1, ..., N$$
  
min max

The range of each parameter is divided into a grid of a small number of equally spaced points, e.g., 3-7 points.

$$\begin{bmatrix} \alpha_{i_{\min}}; \alpha_{i_{\max}} \end{bmatrix} = \begin{bmatrix} \alpha_{i_{1}}; \alpha_{i_{2}}; \dots; \alpha_{i_{Mi}} \end{bmatrix}$$

with  $\alpha_{i_{\min}} = \alpha_{i_{1}}; \alpha_{i_{\max}} = \alpha_{i_{Mi}}$ 

The set of  $\Sigma_{\alpha}$  of possible parameter values, therefore has  $N_{\alpha} = M_1 \cdot M_2 \cdots M_N$  elements.

3) For each element  $\overline{\alpha} \in \Sigma_{\alpha}$  the physical process can be modeled by a system of linear constant coefficient O.D.E.'s. For example, consider a wing flutter model.

\*Assist. Prof., Aerospace and Ocean Eng. Dept., VPI & SU.



Typical Parameters that would vary might be

Actuators: Gain, Phase Error Vehicle : Dynamic Pressure, Geometry Sensors : Gain, Offset Error

 4) The structure of the control law is specified, but values of constants in the control law are to be determined in the design process.
 For example, suppose the sensor signals consist of accelerations, y<sub>i</sub>, measured at various points on the vehicle/wing, and the control law is:

$$\begin{bmatrix} \dot{z}_{1i} \\ \dot{z}_{2i} \end{bmatrix} = \begin{bmatrix} 0 & 1 \\ c_{1i} & c_{2i} \end{bmatrix} \begin{bmatrix} z_{1i} \\ z_{2i} \end{bmatrix} + \begin{bmatrix} 0 \\ 1 \end{bmatrix} y_{i}, i = 1, \dots p$$
$$\vec{u} = K_{1} \vec{z} + K_{2} \vec{y}$$

Let the elements of matrices  $K_1$ ,  $K_2$  and  $C_{11}$ ,  $C_{21}$ ,  $C_{12}$ ,  $C_{22}$ , ... be represented by the <u>design vector</u>  $\vec{k}$ .

5) If we choose a parameter vector  $\vec{a}$  and a design vector  $\vec{k}$ , we have a well defined closed-loop linear system

$$\begin{bmatrix} \vec{x} \\ \vdots \\ \vec{z} \end{bmatrix} = \tilde{A} (\vec{k}, \vec{\alpha}) \begin{bmatrix} \vec{x} \\ \vec{z} \end{bmatrix} + \begin{bmatrix} G \\ 0 \end{bmatrix} \vec{w} + \begin{bmatrix} 0 \\ I \end{bmatrix} \vec{v}$$
6) For one design point  $\overline{k}$  there are  $N_{\alpha}$  closed-loop system matrices

$$\tilde{A}(\vec{k},\vec{a}_1), \ldots, \tilde{A}(\vec{k},\vec{a}_N)$$

corresponding to the possible discrete values of the parameters  $\bar{\alpha}_1, \bar{\alpha}_2, \ldots, \bar{\alpha}_{N_{\alpha}}$ 

We can compute the eigenvalues of each of these  $N_{\alpha}$  closed-loop system matrices as

$$\lambda$$
 ( $\tilde{A}(\tilde{k}, \tilde{\alpha}_{i})$ )

and collect them all into one set that depends only on the design point  $\vec{k}$  as

$$\Lambda (\vec{k}) = \{\lambda(\tilde{A}(\vec{k},\vec{a}_{1})), \ldots, \lambda(\tilde{A}(\vec{k},\vec{a}_{N_{a}}))\}$$

7) Also, for specified initial state and noise covariance matrices, we can compute the RMS values of actuator signals, structural degrees of freedom, or other linearly related parameters for any given closed loop system  $\tilde{A}(\vec{k},\vec{a})$ .

If the number  $N_{\alpha}$  were not unreasonably large, we could find the <u>maximum</u> RMS values of these variables for the  $N_{\alpha}$  closed-loop systems

$$\hat{A}(\vec{k},\vec{a}_1), \ldots, A(\vec{k},\vec{a}_{N_{\alpha}})$$

8) Then, applying either random pattern search strategy (Bekey '81) or nonlinear programming without gradient evaluation, we can search over the space  $\Sigma_{\vec{k}}$  of possible design points to achieve any of the following design objectives:

 $\Lambda(\vec{k})$  to remain in some favorable region of the complex plane.

b) maximize the range  $\alpha_{i \text{ min}}$ ,  $\alpha_{i \text{ max}}$  while constraining both RMS values of actuator signals, and location of  $\Lambda(\vec{k})$  in the complex plane.

c) for specified limits on actuator signals and parameter ranges, move  $\Lambda(\vec{k})$  as far to the left in the complex plane as possible.

## IMPLEMENTATION PROBLEMS:

1

ĺ

- 1) One must be able to effectively generate the linear models A(a), B(a), G(a) corresponding to the specified parameter ranges. This is probably not possible on-line, but will require these arrays of arrays be stored on disk before the controller design study is initiated.
- 2) It may be difficult to avoid local minima in the search for an optimal  $\vec{k}$ , and alternate starting points should be considered.
- 3) One must religiously avoid the curse of dimensionality and reduce the number of parameter points  $N_{\alpha}$  to an absolute minimum (i.e., 9 or 15).
- 4) Care must be taken to construct a well-posed problem in which none of the design variables  $\vec{k}$  may go to infinity.
  - REF: G. A. Bekey, "Modeling and Identification of Nonlinear Systems with Hysteresis", 3rd Int. Conf. on Math. Modeling, U.C.L.A., July 29-31, 1981.

## Appendix A

Additional References on Robust Controller Design Methods

 Ackerman, J. E., "A Robust Control System Design", 1979 Joint Automatic Control Conference, pp. 877-883.

;

- Ackermann, J. E., "A Robust Control System Design", U. Ill. report, 1979, AD-A071162 N79-33909.
- 3. Ackermann, J. E., "Parameter Space Design of Robust Control Systems", IEEE Transactions on Automatic Control, Vol. 25, No. 6, 1980, pp. 1058-1071.
- Arbel, A., and Gupta, N. K., "Robust Colocated Control for Large Flexible Space Structures", 1980 Joint Automatic Control Conference, Vol. II, FPI-E.
- 5. Astrom, K. J., "Robustness of a Design Method Based on Assignment of Poles and Zeros", IEEE Transactions on Automatic Control, Vol. AC-25, 1980, pp. 588-591.
- 6. Barmish, B. R., "Robust Solutions of Perturbed Linear Equations", IEEE Transactions on Automatic Control, Vol. AC-22, 1977, pp. 123-124.
- 7. Barmish, B. R., Blume, L. E., and Chikte, S. D., "On a Class of Nonlinear Robustness Problems", 17th Allerton Conference on Circuit and System Theory, 1979, pp. 555-561.
- 8. Barmish, B. R., "Robust Solutions of Perturbed Dynamical Equations from within a Convex Restraint Set", IEEE Transactions on Automatics Control, Vol. AC-24, 1979, pp. 921-926.
- 9. Barnett, S., "Insensitivity of Optimal Linear Discrete-Time Regulators", International Journal of Control, Vol. 21, 1975, pp. 843-848.
- Barrett, M. F., "Conservatism with Robustness Tests for Linear Feedback Control Systems", IEEE Decision and Control Conference, 1980, Vol. II, pp. 885-890.
- Basuthakur, S., and Knapp, C. H., "Output Feedback for Linear Multivariable Systems with Parameter Uncertainty", 1973 Joint Automatic Control Conference, pp. 661-665.
- 12. Basuthakur, S., and Knapp, C. H., "Minimax Control in Substate Space of a System with Process Uncertainty", Automatica, Vol. 10, 1974, pp. 37-47.
- Becker, N., "A Note on Performance Index Sensitivity of Time Optimal Control Systems", IEEE Transactions on Automatic Control, Vol. AC-25, 1980, pp. 819-821.
- Berger, C. S. and Roberts, J. D., "Design of a Linear Control System with Insensitivity to Plant Variations", 2nd IFAC Symposium on System Stability and Adaptivity, 1968, pp. E 41- E 51.

15. Bhattacharyya, S. P., "The Structure of Robust Observers", IEEE Transactions on Automatic Control, Vol. AC-21, 1976, pp. 581-588.

- Bobrovsky, B. Z., and Graupe, D., "Analysis of Optimal-Cost Sensitivity to Parameter Changes", IEEE Transactions on Automatic Control, Vol. AC-16, 1971, pp. 487-488.
- Bongiorno, Jr., J. J., "On the Design of Observers for Insensitivity to Plant Parameter Variations", International Journal of Control, Vol. 18, 1973, pp. 597-606.
- 18. Bonivento, C., Guidorzi, R., and Marro, G., "Parametric Insensitivity and Controlled Invariance", 3rd IFAC Symposium on Sensitivity, Adaptivity and Optimality, 1973, pp. 177-182.
- 19. Brandt, A. J., "Sensitivity Functions in the Design of Optimal Regulators", IEEE Transactions on Automatic Control, Vol. AC-13, 1968, pp. 110-111.
- 20. Brown, W. A., "Suboptimal Compensator Design for the Linear Regulator via Second-Order Sensitivity", 9th Allerton Conference on Circuit and System Theory, 1971, pp. 595-603.
- Bux, D., "A New Closed Solution Design of Constant Feedback Control for Systems with Large Parameter Variations", 3rd IFAC Symposium on Sensitivity, Adaptivity and Optimality, 1973, pp. 225-235.
- 22. Callier, F. M., "On the Characterization of Minimal Order Robust Servocompensator", IEEE Decision and Control Conference, 1978, pp. 21-24, also in International Journal of Control, Vol. 30, 1979, pp. 379-385.
- 23. Chang, S. S. L., and Peng, T. K. C., "Adaptive Guaranteed Cost Control of Systems with Uncertain Parameters", 1971 Joint Automatic Control Conference, pp. 686-691.
- Chiang, S., and Shih, Y., "Low-Sensitivity Feedback Control of Non-Linear Discrete Systems", International Journal of Control, Vol. 14, 1971, pp. 659-668.
- 25. Chizeck, H. J. and Willsky, A. S., "Towards Fault-Tolerant Optimal Control", IEEE Decision and Control Conference, 1978, pp. 19-20.
- Connor, M. A., "Minimization of Performance Sensitivity for Time-Lag Systems", IEEE Transactions on Automatic Control, Vol. AC-16, 1971, pp. 496-497.
- 27. Courtin, P., "Performance Index Sensitivity of Minimum-Fuel Systems", Automatica, Vol. 7, 1971, pp. 755-759.
- Courtin, P., and Rootenberg, J., "Performance Index Sensitivity of Optimal Control Systems", IEEE Transactions on Automatic Control, Vol. AC-16, 1971, pp. 275-277.

- 29. Cruz, Jr., J. B., and Perkins, W. R., "A New Approach to the Sensitivity Problem in Multivariable Feedback System Design", Coordinated Science Lab; University of Illinois, Rept. No. R-177, 1963.
- 30. Cruz, Jr., J. B. and Perkins, W. R., "A New Approach to the Sensitivity Problem in Multivariable Feedback System Design", IEEE Transactions on Automatic Control, Vol. AC-9, 1964, pp. 216-223.
- 31. Cruz, Jr., Freudenberg, J. S., and Looze, D. P., "A Relationship Between Sensitivity and Stability of Multivariable Feedback Systems", 1980 Joint Automatic Control Conference, Vol. IM WP8-C.
- 32. D'Angelo, H., Moe, M. L., and Hendricks, T. C., "Trajectory Sensitivity of an Optimal Control Systems", 4th Allerton Conference on Circuit and System Theory, 1966, pp. 489-498.
- 33. Davison, E. J., "The Output Control of Linear Time-Invariant Multivariable Systems with Unmeasurable Arbitrary Disturbances", 1972 Joint Automatic Control Conference, pp. 146-157.
- 34. Davison, E. J., and Goldenberg, A., "Robust Control of a General Servomechanism Problem: The Servo Compensator", Automatica, Vol. 11, 1975, pp. 461-471.
- 35. Davison, E. J., "Multivariable Tuning Regulators: The Feedforward and Robust Control of a General Servomechanism Problem", IEEE Decision and Control Conference, 1975, pp. 180-187, also in IEEE Transactions on Automatic Control, Vol. AC-21, 1976, pp. 35-47.
- Davison, E. J., "The Robust Decentralized Control of a General Servomechanism Problem", IEEE Decision and Control Conference, 1975, pp. 815-821, also in IEEE Transactions on Automatic Control, Vol. AC-21, 1976, pp. 14-24.
- 37. Davison, E. J., "Decentralized Robust Control of Unknown Systems using Tuning Regulators", 14th Allerton Conference on Circuit and System Theory, 1976, pp. 339-348.
- 38. Davison, E. J., "The Robust Control of a Servomechanism Problem for Linear Time-Invariant Multivariable Systems", IEEE Transactions on Automatic Control, Vol. AC-21, 1976, pp. 25-34.
- 39. Davison, E. J., "The Robust Decentralized Servomechanism Problem with Extra Stabilizing Agents", IEEE Transactions on Automatic Control, Vol. AC-22, 1977, pp. 256-258.
- 40. Davison, E. J., "Decentralized Robust Control of Unknown Systems Using Tuning Regulators", IEEE Transactions on Automatic Control, Vol. AC-23, 1978, pp. 276-289.
- 41. Davison, E. J., "The Robust Decentralized Control of a Servomechanism Problem for Composite Systems with Input-Output Interconnections", IEEE Transactions on Automatic Control, Vol. AC-24, 1979, pp. 325-327.

- 42. Davison, E. J., and Ozguner, U., "Decentralized Synthesis of the Decentralized Robust Servomechanism Problem", 1980 Joint Automatic Control Conference, Vol. I, WAI-A.
- Davison, E. J., and Ferguson, I. J., "The Design of Controllers for the Multivariable Robust Servomechanism Problem Using Parameter Optimization Methods", IEEE Decision and Control Conference, 1980, Vol. II, pp. 871-877.
- 44. De Oliveira, C., "Eigenvalue Sensitivity of Some Transfer Function Realizations", IEEE Transactions on Automatic Control, Vol. AC-20, 1975, pp. 276-278.
- 45. De Santis, R. M., and Conan, J., "Practical Sensitivity Reduction for Linear and Nonlinear Systems", 13th Allerton Conference on Circuit and System Theory, 1975, pp. 612-621.
- 46. De Santis, R. M., and Lefebvre, S., "Comparative Sensitivity and Absolute Invariant Compensators with Application to a DC-AC Converter", 14th Allerton Conference on Circuit and System Theory, 1976, pp. 964-973.
- 47. De Santis, R. M., and Lefebvre, S., "A Frequency Design Technique for Model Matching and Sensitivity Reduction", 16th Allerton Conference on Circuit and System Theory, 1978, pp. 914-922.
- 48. Desoer, C. A., and Wang, Y. T., "The Robust Nonlinear Servomechanism Problem", IEEE Decision and Control Conference, 1978, pp. 7-11, also in International Journal of Control, Vol. 29, 1979, pp. 803-828.
- 49. Desoer, C. A., Callier, F. M., and Chan, W. S., "Robustness of Stability Conditions for Linear Time-Invariant Feedback Systems", IEEE Transactions on Automatic Control, Vol. AC-22, 1977, pp. 586-590.
- Desoer, C. A., and Wang, Y. T., "On the Minimum Order of a Robust Servocompensator", IEEE Transactions on Automatic Control, Vol. AC-23, 1978, pp. 70-73.
- 51. Desoer, C. A., Callier, F. M., and Chan, W. S., "Robustness of Stability Conditions for Linear Time-Invariant Feedback Systems", 1977 Joint Automatic Control Conference, pp. 601-607.
- 52. Dias, R. J., and Bhattacharyya, S. P., "Disturbance Rejection Control of Linear Systems with Variations in the System Parameters", 1977 Joint Automatic Control Conference, pp. 1647-1649.
- Dompe, R. J., and Dorf, R. C., "The Design of Optimal Low Sensitivity Linear Control Systems", Allerton Conference on Circuit and System Theory, 1967.
- 54. Dorato, P., "On Sensitivity in Optimal Control Systems", IEEE Transactions on Automatic Control, Vol. AC-8, 1963, pp. 256-257.
- 55. Dougherty, H. J., Lee, I., and DeRusso, P. M., "Synthesis of Optimal Feedback Control Systems Subject to Parameter Variations", Joint Automatic Control Conference, 1967, pp. 125-133.

- 56. Doyle, J. C., and Stein, G., "Robustion with Observers", IEEE Decision and Control Conference, 1978, pp. 1-6, also in IEE Transactions on Automatic Control, Vol. AC-24, 1979, pp. 607-611.
- 57. Doyle, J. C., "Robustness of Multiloop Linear Feedback Systems", IEEE Decision and Control Conference, 1978, pp. 12-18.
- 58. El-Hodiri, M., "Sensitivity Analysis for an Optimal Control Problem", IEEE Transactions on Automatic Control, Vol. AC-20, 1975, pp. 251-252.
- 59. Elmetwally, M. M., and Rao, N. D., "Design of Near-Zero Sensitivity Optimal Control Systems", International Journal of Control, Vol. 18, 1973, pp. 353-357.
- 60. Elmentwally, M. M., and Rao, N. D., "Design of Low Sensitivity Optimal Regulators for Synchronous Machines", International Journal of Control, Vol. 19, 1974, pp. 593-607.
- 61. Elrazaz, Z., and Sinha, N. K., "Decentralized Stabilization of Large-Scale Systems Using Modal Control and Eigenvalue Sensitivities", 16th Allerton Conference on Circuit and System Theory, 1978, pp. 762-769.
- Eslami, M., and Marleau, R. S., "On Sensitivity Minimization with an Adaptive Controller", 1978 Joint Automatic Control Conference, Vol. 4, pp. 219-228.
- 63. Fleming, P. J., and Newmann, M. M., "Design Algorithms for a Sensitivity Constrained Suboptimal Regulators", International Journal of Control, Vol. 25, 1977, pp. 965-978.
- 64. Fleming, P. J., "Desensitizing Constant Gain Feedback Linear Regulators", IEEE Transactions on Automatic Control, Vol. AC-23, 1978, pp. 933-936.
- 65. Ferreira, P. M. G., "Robustness and Partial Robustness in the Servo Problem", International Journal of Control, Vol. 32, 1980, pp. 891-898.
- 66. Gajendran, F., "Design of Servo Systems with Low Sensitivity A New Approach", 1977 Joint Automatic Control Conference, pp. 1498-1503.
- 67. Goldenberg, A., and Davison, E. J., "On the Robust Control of a Time Delay Servomechanism Problem", 14th Allerton Conference on Circuit and System Theory, 1976, pp. 983-997.
- 68. Gomathi, K., Prabhu, S. S., and Pai, M. A., "A Suboptimal Controller for Minimum Sensitivity of Closed Loop Eigenvalues to Parameter Variations", IEEE Transactions on Automatic Control, Vol. AC-25, 1980, pp. 587-588.
- 69. Gori-Giorgi, C., and Grasselli, O. M., "A New Approach to the Study of Parameter Insensitivity", Automatica, Vol. 11, 1975, pp. 181-188.
- 70. Grubel, G., and Kreisselmier, G., "A Generalized Comparison Sensitivity Concept for Sensitivity Reduction in Control System Design", 1974 Joint Automatic Control Conference, pp. 328-332.

71. Guardabassi, G., Locatelli, A., and Rinaldi, S., "On the Optimization of Continuous Linear Systems with Sensitivity Constraints", 2nd IFAC Symposium on System Stability and Adaptivity, 1968, pp. E25-E40.

ł

ł

l

ļ

ŧ.

- 72. Guardabassi, G., Locatelli, A., and Rinaldi, S., "The Role of Controllability in some Sensitivity Problems", International Journal of Control, Vol. 19, 1974, pp. 57-64.
- 73. Gupta, N. K., "New Structures for Parameter Insensitive Controllers", IEEE Decision and Control Conference, 1978, pp. 25-30.
- 74. Haddad, A. H., Cruz, Jr., J. B., and Kakotovic, P. V., "Design of Control Systems with Random Parameters", International Journal of Control, Vol. 13, 1971, pp. 981-992.
- 75. Hanafy, A. A. R., "Two Level Optimization Technique to Minimize Trajectory Sensitivity", 1976 Joint Automatic Control Conference, pp. 568-575.
- 76. Harvey, C. A., and Pope, R. E., "Synthesis Techniques for Insensitive Aircraft Control Systems", IEEE Decision and Control Conference, 1976, pp. 990-1001.
- 77. Hendricks, T. C., and D'Angelo, H., "An Optimal Fixed Control Structure Design with Minimal Sensitivity for a Large Elastic Booster", Allerton Conference on Circuit and System Theory, 1967.
- 78. Horowitz, I. M., and Rolnik, J. A., "Feedback Control Systems for Plants With Large Parameter Variations", 2nd IFAC Symposium on System Stability and Adaptivity, 1968, pp. El-El2.
- 79. Hontoir, Y., and Cruz, Jr., J. B., "Sensitivity Reduction in Linear Systems", Automatica, Vol. 8, 1972, pp. 445-449.
- Hontoir, Y., and Cruz, Jr., J. B., "Minimum Trajectory Sensitivity Design of Systems with Random Parameters", International Journal of Control, Vol. 20, 1974, pp. 353-362.
- 81. Hontoir, Y., and Cruz, Jr., J. B., "A Probabilistic Likelihood Approach to Trajectory Sensitivity", Automatica, Vol. 10, 1974, pp. 49-60.
- Hontoir, Y., and Cruz, Jr., J. B., "Trajectory Sensitivity Reduction Through Exponentially Stable Feedback", IEEE Decision and Control Conference, 1974, pp. 319-324.
- 83. Horowitz, I., and Sidi, M., "Synthesis of Cascaded Multiple-Loop Feedback Systems with Large Plant Parameter Ignorance", Automatica, Vol. 9, 1973, pp. 589-600.
- 84. Huseyin, O., Sezer, M. E., and Siljak, D. D., Robust Decentralized Control Using Output Feedback", 18th Allerton Conference on Circuit and System Theory, 1980, pp. 900-908.

- 85. Inoue, K., Akashi, H., Ogino, K., and Sawaragi, Y., "Sensitivity Approaches to Optimization of Linear Systems with Time Delay", Automatica, Vol. 7, 1971, pp. 671-679.
- Kahne, S. J., and Lamont, G. B., "Time Domain Sensitivity Comparison", IEEE Transactions on Aerospace and Electronic Systems, Vol. AES-5, 1969, pp. 142-151.

- 87. Kamiya, Y., "Construction of a Low Parameter and Disturbance Sensitivity System by a Model - Following Method", International Journal of Control, Vol. 23, 1976, pp. 515-524.
- 88. Kang, H. S., "Minimum Sensitivity Design of M. V. Systems", International Journal of Control", Vol. 11, 1970, pp. 791-801.
- 89. Karlin, A., Locatelli, A., and Zanardini, C., "On the Synthesis of Trajectory Insensitive Linear Systems", 3rd IFAC Symposium on Sensitivity, Adaptivity and Optimality, 1973, pp. 183-189.
- 90. Karlin, A., Locatelli, A., and Zanardin, C., "Trajectory Insensitivity via Feedback", Automatica, Vol. 10, 1974, pp. 517-524.
- 91. Khalil, H. K., "On the Robustness of Output Feedback Control Methods to Modeling Errors", 18th Allerton Conference on Circuit and System Theory, 1980, pp. 405-413.
- 92. Kiendl, H. D., "Synthesis of parameter and State Insensitive Faedback Systems with Constraints Based on Piecewise Constant Linear Control Laws", 3rd IFAC Symposium on Sensitivity, Adaptivity and Optimality, 1973, pp. 236-238.
- Kleinman, D. L., and Rao, P. K., "An Information Matrix Approach for Aircraft Parameter - Insensitive Control", IEEE Decision and Control Conference, 1977, pp. 316-325.
- 94. Kokotovic, P., Heller, J., and Sannuti, P., "Sensitivity Comparison of Optimal Controls", International Journal of Control, Vol. 9, 1969, pp. 111-117.
- 95. Kreindler, E., "On the Definition and Application of the Sensitivity Function", Journal of Franklin Institute, Vol. 285, 1968, pp. 26-36.
- 96. Kriendler, E., "Formulation of the Minimum Trajectory Sensitivity Problem", IEEE Transactions on Automatic Control, Vol. AC-14, 1969, pp. 206-207.
- 97. Kreindler, E., and Jameson, A., "On Sensitivity Reduction in Non-Linear Feedback Systems", 3rd IFAC Symposium on Sensitivity, Adaptivity and Optimality, 1973, pp. 131-136.
- 98. Krishnan, K. R., and Cruickshanks. A., 'Frequency-Domain Design of Feedback Systems for Specified Insensitivity of Time-Domain Response to Parameter Variation", 13th Allerton Conference on Circuit and System Theory, 1975, pp. 859-866.

99. Krishnan, K. R., and Brzezawski, S., "Design of Robust Linear Regulator with Prescribed Trajectory Insensitivity to Parameter Variations", IEEE Transactions on Automatic Control, Vol. AC-23, 1978, pp. 474-478.

| | | | |

ł

ć

١

ţ,

- 100. Kroogh, B., and Cruz Jr., J. B., "Design of Sensitivity-Reducing Compensators Using Observers", IEEE Transactions on Automatic Control, Vol. AC-23, 1978, pp. 1058-1062.
- 101. Kwakernaak, H., "Optimal Low-Sensitivity Linear Feedback Systems", 2nd IFAC Symposium on System Stability and Adaptivity, 1968, pp. E13-E24.
- 102. Kwakernaak, H., "Design of Robust Controllers by Linear Optimal Control Theory", TW-Memorandum No. 317, Twente University of Technology, The Netherlands, 1980.
- 103. Kwatny, H. G., and Kalnitsky, K. C., "On Alternative Methodologies for the Design of Robust Linear Multivariable Regulators", IEEE Transactions on Automatic Control, Vol. AC-23, 1978, pp. 930-933.
- 104. Lamont, G. B., and Kahne, S. J., "Time Domain Sensitivity Comparison", Allerton Conference on Circuit and System Theory, 1967.
- 105. Lehtomaki, N. A., et. al., "Robust Control of Multiterminal DC/AC Systems", IEEE Decision and Control Conference, 1979, Vol. II, pp. 886-896.
- 106. Leondes, C. T., and Pezet, P., "Sensitivity Requirements for Suboptimal Controllers", IEEE Transactions on Automatic Control, Vol. AC-20, 1975, pp. 426-428.
- 107. Liberty, S. R., Maynard, R. A., and Mielke, R. R., "Design of a Turbojet Engine Controller Via Eigenvalue/Eigenvector Assignment: A New Sensitivity Formulation", 1979 Joint Automatic Control Conference, pp. 359.
- 108. Locatelli, A., and Schiavoni, N., Further Results on Trajectory Insensitivity", Automatica, Vol. 12, 1976, pp. 285-288.
- 109. Mahalanabis, A. K., Kang, H. S., and Vaish, P. C., "Minimum Sensitivity, Minimum Variance Control of Stochastic Systems", 1971 Joint Automatic Control Conference, pp. 111-115.
- 110. Malek-Zavarei, M., and Jamshid, M., "Sensitivity of Linear Time-Delay Systems to Parameter Variations", Automatica, Vol. 11, 1975, pp. 315-319.
- 111. Missaghie, M. M. and Fairman, F. W., "Sensitivity Reducing Observers for Optimal Feedback Control", IEEE Transacticas on Automatic Control, Vol. AC-22, 1977, pp.
- 112. Naeije, W. J., and Bosgra, N. B., "Comparison Sensitivity Design of Multivariable Output Feedback Systems", 4th IFAC Symposium on Multivariable Technological Systems, 1977, pp. 127-135.
- 113. Newmann, M. M., "On Attempts to Reduce the Sensitivity of the Optimal Regulator to a Parameter Change", International Journal of Control, Vol. 11, 1970, pp. 1079-1084.

114. Nuzman, D. W., and Sandell, Jr., N. R., "An Inequality Arising in Robustness Analysis of Multivariable Systems", IEEE Transactions on Automatic Control, Vol. AC-24, 1979, pp. 492-493.

Ľ

- 115. O'Reilly, J., "Low Sensitivity Feedback Controllers for Linear Systems with Incomplete State Information", International Journal of Control, Vol. 29, 1979, pp. 1047-1058.
- 116. Ohta, H., and Sugiura, I., "Optimal Landing Flare Control of Aircrafts with Sensitivity Consideration", 3rd IFAC Symposium on Sensitivity, Adaptivity and Optimality, 1973, pp. 251-259.
- 117. Orbach, A., and Fischi, R., "Performance Index Sensitivity of Optimal Control of First Order in Time-and-Space-Distributed Parameter Systems", IEEE Transactions on Automatic Control, Vol. AC-25, 1980, pp. 314-316.
- 118. Palsson, T., and Whitaker, H. P., "Parameter Uncertainties in Control System Design", 1972 Joint Automatic Control Conference, pp. 248-254.
- 119. Patel, R. V., Toda, M., and Sridhar, B., "Robustness of Linear Quadratic State Feedback Designs in the Presence of System Uncertainty", 1977 Joint Automatic Control Conference, pp. 1668-1673, also in IEEE Transactions on Automatic Control, Vol. AC-22, 1977, pp. 945-949.
- 120. Patel, R. V., and Toda, M., "Quantitative Measures of Robustness for Multivariable Systems", 1980 Joint Automatic Control Conference, Vol. II, TP8-A.
- 121. Pearson, J. B., Shields, R. W., and Staats, Jr., P. W., "Robust Solutions to Linear Multivariable Control Problems", 1974 Joint Automatic Control Conference, pp. 172-176, also in IEEE Transactions on Automatic Control, Vol. AC-19, 1974, pp. 508-517.
- 122. Perkins, W. R., and Cruz, Jr., J. B., "The Parameter Variation Problem in State Feedback Control Systems", Journal of Basic Engineering, Trans. ASME, Series D, Vol. 87, 1965, pp. 120-124.
- 123. Perlis, H. J., and Duckworth, Jr., E. M., "Trajectory Sensitivity Profiles in a Class of Distributed Optimal Water Quality Control Systems", 1972 Joint Automatic Control Conference, pp. 358-365.
- 124. Platzman, L., and Athans, M., Explicit Cost Sensitivity Analysis for Linear Systems with Quadratic Criteria", IEEE Transactions on Automatic Control, Vol. AC-20, 1975, pp. 252-254.
- 125. Pohjolainen, S., and Koivo, H., "On Robust Eigenvalue/Eigenvector Assignment", 16th Allerton Conference on Circuit and System Theory, 1978, pp. 744-753.
- 126. Porter, B., "Eigenvalue Sensitivity of Modal Control Systems to Loop-Gain Variations", International Journal of Control, Vol. 10, 1969, pp. 159-162.
- 127. Porter, W. A., "Partial Inverses for Parameter Sensitivity Reduction", International Journal of Control, Vol. 29, 1979, pp. 949-961.

- 128. Quintana, V. H., "Low-Sensitivity Dynamic Compensation for Linear Stochastic Systems with Random Parameters", International Journal of Control, Vol. 28, 1978, pp. 621-634.
- 129. Ramnath, R. V., and Radovsky, S., "Parameter Sensitivity in Time Varying Linear Systems, with an Application to the Dynamics of VTOL Aircraft", 1979 Joint Automatic Control Conference, pp. 509-616.
- 130. R111ings, J. H., and Roy, R. J., "Analog Sensitivity Design of Saturn V Launch Vehicle", IEEE Transactions on Automatic Control, Vol. AC-15, 1970, pp. 437-442.

l

ł

- 131. Rootenberg, J., and Courtin, P., "Sensitivity of Optimal Control Systems with Bang-Bang Control", International Journal of Control, Vol. 18, 1973, pp. 537-544.
- 132. Rushing, A. J., "Sensitivity Analysis and Optimal Control Theory Applied to Corona Charging of Electrophotographic Films", 1980 Joint Automatic Control Conference, Vol. I, WAIO-A.
- 133. Russell, D. L., "Response Variation Weighting Methods for Cost Sensitivity Reduction", Honeywell Report MR12497, 1978.
- 134. Russell, D. L., "Cont Sensitivity Reduction", Mathematics of Finite-Dimensional Control Systems, Marcel Dekker Inc., 1979, pp. 492-512.
- 135. Safonov, M. G., and Athans, M., "Robustness and Computational Aspects of Nonlinear Stochastic Estimators and Regulators", IEEE Decision and Control Conference, 1977, pp. 1229-1238.
- 136. Safonov, M. G., "Frequency-Domain Design of Multivariable Control Systems for Insensitivity to Large Plant Modeling Errors", IEEE Decision and Control Conference, 1979, Vol. I, pp. 247-249.
- 137. Sain, M. K., Schafer, R. M., and Dudek, K. P., "An Application of Total Synthesis to Robust Coupled Design", 18th Allerton Conference on Circuit and System Theory, 1980, pp. 386-395.
- 138. Sain, M. K., and Ma, A., "Multivariable Synthesis with Reduced Comparison Sensitivity", 1980 Joint Automatic Control Conference, Vol. I, WP8-B.
- 139. Salmon, D. M., "Minimax Controller Design", IEEE Transactions on Automatic Control, Vol. AC-13, 1968, pp. 369-376.
- 140. Sandell, N. R., "Robust Stability of Multivariable Feedback Systems", 16th Allerton Conference on Circuit and System Theory, 1978, pp. 471-479.
- 141. Sannuti, P., and Cruz, Jr., J. B., "A Note on Trajectory Sensitivity of Optimal Control Systems", IEEE Transactions on Automatic Control, Vol. AC-13, 1968, pp. 111-113.
- 142. Sarma, I. G., Hole, K. E., and Prasad, U. R., "Minimum Trajectory Sensitivity Design of Optimal Control Systems", 3rd IFAC Symposium on Sensitivity, Adaptivity and Optimality, 1973, pp. 260-266.

143. Sawan, M. E., and Cruz, Jr., J. B., "Optimal Control Systems With Low Sensitivity to Small Time Delays", IEEE Decision and Control Conference, 1979, Vol. I, pp. 45-48.

.

12

11

ţ.

- 144. Sawaragi, Y., Inoue, K., and Asai, K., "Optimal Control Synthesis by Sensitivity Considerations", 2nd IFAC Symposium on System Stability and Adaptivity, 1968, pp. E52-E63.
- 145. Sesak, J. R., "Sensitivity Constrained Linear Optimal Control, Analysis and Synthesis", Ph.D. Thesis, University of Wisconsin, 1974.
- 146. Sesak, J. R., "Sensitivity-Constrained Linear Optimal Control via Forced Singular Perturbation Model Reduction", IEEE Decision and Control Conference, 1978, pp. 1145-1146.
- 147. Sezer, M. E., and Siljak, D. D., "Robustness of Suboptimal Control: Gain and Phase Margin", IEEE Decision and Control Conference, 1980, Vol. II, pp. 878-884.
- 148. Shaked, U., Horowitz, I. and Gold, S., "Synthesis of Multivariable, Basically Non-Interacting Systems with Significant Plant Uncertainty", Automatica, Vol. 12, 1976, pp. 61-71.
- 149. Sibul, L. H., "Sensitivity Analysis of Linear Control Systems with Random Plant Parameters", IEEE Transactions on Automatic Control, Vol. AC-15, 1970, pp. 459-462.
- 150. Sinha, N. K., and Dai, S.-H., "Reduction of the Sensitivity of an Optimal Control System to Plant Parameter Variations", IEEE Transactions on Automatic Control, Vol. AC-15, 1970, pp. 589-590.
- 151. Sinha, N. K., and Dai, S., "Sensitivity Reduction in Optimal Control Systems", 8th Allerton Conference on Circuit and System Theory, 1970, pp. 545-551.
- 152. Sinha, N. K., "Reduction of the Sensitivity of Optimal Control System by Using Two Degree of Freedom", 3rd IFAC Symposium on Sensitivity, Adaptivity and Optimality, 1973, pp. 267-270.
- 153. Sinha, N. K., and Elrazaz, Z., "Eigenvalue Sensitivity of Aggregated Models", 15th Allerton Conference on Circuit and System Theory, 1977, pp. 305-313.
- 154. Sirisena, H. R., and Chai, S. S., "Pole Placement in Output Feedback Control Systems for Minimum Sensitivity to Plant Parameters Variations", International Journal of Control, Vol. 22, 1975, pp. 129-140.
- 155. Staats, P. W., and Pearson, J. B., "Robust Solution of the Linear Servomechanism Problem", Automatica, Vol. 13, 1977, pp. 125-138.
- 156. Stavroulakis, P., "Implementation of a Low Sensicivity Control of Distributed Parameter Systems via an Observer", IEEE Decision and Control Conference, 1974, pp. 891-896.

157. Stavroulakis, P., and Sarachik, P. E., "Low Sensitivity Feedback Gains for Deterministic and Stochastic Control Systems", international Journal of Control, Vol. 19, 1974, pp. 15-31.

----

ŧ

i.

1.

- 158. Strintzis, M. G., and Liu, B., "Sensitivity Minimization in the Design of Linear Multivariable Feedback Systems", 8th Allerton Conference on Circuit and System Theory, 1970, pp. 163-172.
- 159. Subbayyan, R., et. al., "An Approach for Sensitivity Reduced Design of Linear Regulators", International Journal of Systems Sciences, Vol. 9, 1978, pp. 65-75.
- 160. Subbayyan, R., and Vaithilingam, M. C., "Sensitivity-Reduced Design of Linear Regulators", International Journal of Control, Vol. 29, 1979, pp. 435-440.
- 161. Sundararajan, N., and Cruz, Jr., J. B., "Trajectory Insensitivity of Optimal Feedback Systems", IEEE Transactions on Automatic Control, Vol. AC-15, 1970, pp. 663-665.
- 162. Toda, M., Patel, R., and Sridhar, B., "Closed-Loop Stability of Linear Quadratic Optimal Systems in the Presence of Modelling Errors", 14th Allerton Conference on Circuit and System Theory, 1976, pp. 974-982.
- 163. Tse, E., and Bar-Shalom, Y., "An Activity Adaptive Control for Linear Systems with Random Parameters via the Dual Control Approach", IEEE Decision and Control Conference, 1972, pp. 623-627.
- 164. Tuel, W., Lee, I., and De Russo, P., "Synthesis of Optimal Control Systems with Sensitivity Constraints", 3rd IFAC Congress, 1966.
- 165. Vandelinde, V. D., "Robust Properties of Solutions to Linear-Quadratic Estimation and Control Problems", IEEE Transactions on Automatic Control, Vol. AC-22, 1977, pp. 138-139.
- 166. Wang, S. H., and Davison, E. J., "On the Stabilization of Decentralized Control Systems", IEEE Transactions on Automatic Control, Vol. AC-18, 1973, pp. 473-478.
- 167. Winsor, C. A., and Roy, R. J., "The Application of Specific Optimal Control to the Design of Desensitized Model Following Control Systems", 1970 Joint Automatic Control Conference, pp. 271-277, IEEE Transactions on Automatic Control, Vol. AC-15, 1970, pp. 326-333.
- 168. Wu, Y. W., and Chang, S. S. L., "Guaranteed Cost Control and Guaranteed Error Estimation of Stochastic Systems with Uncertain Parameters", IEEE Decision and Control Conference, 1974, pp. 214-219.
- 169. Yanushevsky, R. T., "Design of Optimal Low-Sensitivity Feedback Control Systems", 3rd IFAC Symposium on Sensitivity, Adaptivity and Optimality, 1973, pp. 271-275.
- 170. Yedavalli, R., "Control Design for Parameter Sensitivity Reduction in Linear Regulators: Application to Large Space Structures", Ph.D. Thesis, Purdue University, 1980.

171. Zames, G., "Cptimal Sensitivity and Feedback; Weighted Seminorms, Approximate Inverses, and Plant Invariant Schemes", 17th Allerton Conference on Circuit and System Theory, 1979, pp. 744-752.

3 L.

ł.

- 172. Zames, G., and El-Sakkary, A., "Unstable Systems and Feedback: The Gap Metric", 18th Allerton Conference on Circuit and System Theory, 1980, pp. 380-385.
- 173. Zinober, A. S. I., and Fuller, A. T., "The Sensitivity of Nominally Time-Optimal Control Systems to Parameter Variations", International Journal of Control, Vol. 17, 1973, pp. 673-703.