ΝΟΤΙCΕ

THIS DOCUMENT HAS BEEN REPRODUCED FROM MICROFICHE. ALTHOUGH IT IS RECOGNIZED THAT CERTAIN PORTIONS ARE ILLEGIBLE, IT IS BEING RELEASED IN THE INTEREST OF MAKING AVAILABLE AS MUCH INFORMATION AS POSSIBLE

NWC Technical Memorandum 3667

NASA CR-160359

AIRBORNE MEASUREMENTS OF CLOUD FORMING NUCLEI AND AEROSOL PARTICLES AT KENNEDY SPACE CENTER, FLORIDA

by

Lawrence F. Padke Atmospheric Sciences Department University of Washington Seattle, Washington 98195

Gerhard Langer Convective Storms Division National Center for Atmospheric Research Boulder, Colorado 80307

and

Edward E. Hindman, II Research Department Naval Weapons Center China Lake, California 93555

December 1978

. Approved for public release; distribution unlimited. This is an informal report of the Naval Weapons Center and is not part of the permanent records of the Department of Defense.

> NAVAL WEAPONS CENTER China Lake, California 93555

(MASA-CR-160354) ATRBORNE MEASUPEMENTS OF CLOUD FOFMING NUCLEI AND AFROSOL PARTICLES AT KENNEDY SPACE CENTER, FLORIDA (Naval Weapons Center, China Lake, Calif.) 33 p Unclas CSCL 04B G3/47 46039 HC A03/MF A01

N80-11716

ABSTRACT

Results of airborne measurements of the sizes and concentrations of aerosol particles, ice nuclei, and cloud condensation nuclei that were taken at Kennedy Space Center, Florida are presented along with a detailed description of the instrumentation and measuring capabilities of the University of Washington airborne measuring facility (Douglas B-23). Airborne measurements made at Ft. Collins, Colorado and Little Rock, Arkansas during the ferry of the B-23 are presented.

The particle concentrations differed significantly between the clean air over Ft. Collins and the hazy air over Little Rock and Kennedy Space Center. The concentrations of cloud condensation nuclei over Kennedy Space Center were typical of polluted eastern seaboard air.

Three different instruments were used to measure ice nuclei: one used filters to collect the particles, and the others used optical and acoustical methods to detect ice crystals grown in portable cloud chambers. A comparison of the ice nucleus counts, which are in good agreement, is presented.

4

CONTENTS

Airborne Measurement Facility
Aerosol Instrumentation
Cloud Physics Instrumentation
Measurements, Results, and Discussion
Conclusions
References
Appendix: A. Specifications of Research Instruments on the B-23 Aircraft

F

INTRODUCTION

Airborne measurements of ice nuclei (IN), cloud condensation nuclei (CCN), liquid and solid aerosol particles, and cloud volumes were made in stabilized ground clouds (SGCs) produced by Titan III launches at Kennedy Space Center (KSC) on 20 August and 5 September 1977.¹ The IN measurements, which were the focus of the flights, were not conclusive because counts from the portable counters and those using filters were inconsistent. It was recommended that laboratory studies of the various portable counters and filters be conducted to prepare them to monitor the SGC from the Titan III launch at KSC in March 1978.² The results of the laboratory investigations are reported by Hindman and others.³

The primary emphasis of the airborne measurements reported here was to study the ice nucleating properties of the effluents from the Titan III solid rocket motors. We planned to measure the structure of the SGC produced by the launch and the aerosol size distributions and CCN in the effluents. The Titan III launch was plagued by repeated postponements of the scheduled 13 March launch. The measurement aircraft (University of Washington) had other contractual obligations and had to return to Seattle before the launch finally cook place on 25 March (due to malfunction, the rocket and payload were destroyed 8 minutes after blastoff). Therefore, the measurements reported here were obtained in air unaffected by rocket effluents during project flights in the vicinity of KSC. Data obtained during ferry flights from Ft. Collins, Colorado to Patr.ck AFB, Florida are presented for comparison purposes. The measurements obtained at KSC will be useful for comparisons with measurements from future flights at KSC.

AIRBORNE MEASUREMENT FACILITY

The University of Washington Douglas B-23 is ideal for aerosol and cloud physics research and has been used in a wide variety of atmospheric research projects since 1970. It is a heavy (12,000 kg), twin-engine plane and can carry a crew of seven and more than 1,000 kg of equipment. It is an all-weather plane (equipped for instrument operations, all leading edges and propellers de-iced), has a service ceiling of 8,000 m, and has excellent maneuverability at all altitudes. At speeds between 35 and 85 m s⁻¹, it provides a stable sampling platform (normal sampling

PTECEDING PAGE PLANK NOT IT TAR

speed 60 m s⁻¹), and its low cruising speed minimizes problems associated with small-particle sampling. The specialized instrumentation is described in the following section.

DATA SYSTEM AND BASIC PARAMETERS

One of the most important characteristics of the B-24 research system is that, despite its extent and complexity, an adequate crew can be carried aboard to ensure its reliable operation. Moreover, the crew is provided with sufficient real-time data so that project goals can be adjusted in-flight to take advantage of unique situations.

Data syntheses are orchestrated by the Flight Data Engineer interacting with a minicomputer (16-bit word, 16K-word capacity coupled to twin, 100K-word floppy disks). The engineer can provide the research crew with any recorded or computed parameter via 20 digital and electromechanical displays, a hard-copy digital printer, and a six-channel, high speed, strip-chart recorder.

Data are recorded on both magnetic tape and disk media via serial digital, IRIG FM and direct recording. The disk record allows a detailed flight summary to be compiled immediately after landing at the airport using the small, onboard computer.

For this mission, the aircraft was configured for both cloud physics and aerosol research; the instrumentation layout is shown in Figure 1. Instruments for measuring basic parameters (temperature, dew point, pressure altitude, altitude above terrain, true airspeed, vertical and horizontal winds, aircraft altitude and rate of climb, turbulence and solar irradiance) are located primarily in the forward portion of the aircraft and are a permanent installation. A history of the aircraft flight path is provided by an x-y plotter which is driven by the aircraft navigational system; this provides a tracing of the aircraft position on a sectional map.

AEROSOL INSTRUMENTATION

A schematic of the layout and ducting for the aerosol instrumentation is shown in Figure 2. The most complex portion is the aerosol sizing system which consists of four instruments:

- 1. The condensation nucleus counter (CNC)
- 2. The electrical aerosol analyzer (EAA)
- 3. Two optical particle counters (OPCs)

The instruments, completely integrated and controlled by the onboard computer, provide size spectral measurements of atmospheric aerosol from



5



148. 1 Accartions of a research fastriments on the University of Mashington's Douglas 3-23 altrends.

わ

Ŧ

- UB-DE slaved position plotter; research power pased (3 LM 110W 45) Rz;
 1.5 Km 110W 450 Mar; 350 anys 28 450.
 1.5 Km 110W 450 Mar; 350 anys 28 450.
 1.5 Km 110W 450 Mar; 350 anys 28 450.
 1.5 Km 110W 450 Mar; 360 anys 28 450.
 1.5 Km 110W 450 Mar; 360 anys 28 450.
 1.5 Km 110W 450 Mar; 360 anys 28 450.
 1.5 Km 110W 450 Mar; 360 anys 28 450.
 1.5 Km 110W 450 Mar; 360 anys 28 450.
 1.5 Km 110W 450 Mar; 360 anys 28 450.
 1.5 Km 110W 450 Mar; 360 anys 28 450.
 1.5 Km 110W 450 Mar; 360 and 37 450 Mar; 4150 Mar; 450 Mar; 45 5 Acrosof Retrievention Monitor I 6 Flight Scientist 7 Aerosol Instrumentation Monitor II 5-ca grostabilized scather radar. Resecuent airspeel, pressure altitude and total temperature probek. Rel-tendulence probe and electronics, J-4 ligaid water probe. angle of attask sensor. URE-PME slaved position plotter; research power pamel (3 RM 1100 63) filter aal eorpfilet Observer Instrumentation Engloeer
- The mainly scattering sportoweter (cwalt droplet proke), vertically mowated Deeb ank bard puint saitable for scall fastrement pols. Untermaintus towater (KAR). Unterheat (r. scasse.)
- Electric field call scatter (vertical and herizontal field). Reverse field call scatter appears Automatic free particle compare and metal full hydrometeor lapacter. Net continueus particle traiterior. Frace Picturian protechant rack (52 tom calts). Frace protechant vark (52 tom calts).

- Kalar repeater, side viewing antomatic capera. Kelar altimeter, 3-D elettic field all wiettenive, 20-thannel telemetry
- transmitter. Internet term system (varialiss of aik high-variality rature pumps connected normer ted fuiltuiduilly to the abin).
- aaiskinetu large vulmee atosol samjke. 185 optial artev prospination seerikusi 115 optial attev elead dr.µku probe 186 omblev enater (Aka), ke omblev filtera, su 8 uS anaitu.



. s.

States of the second second







(b) SIDE VIEW

FIGURE 2. Plan and Side Views of Aerosol Instrumentation on the University of Washington's Research Aircraft.

0.01 to 65 μ m in diameter over a concentration range of 10^{-6} to 10^7 cm⁻³. These instruments have been extensively modified in the laboratory at the University of Washington to provide optimum performance and they are regularly calibrated. A description of the CNC, EAA, and OPCs and their installation in the B-23 has been given by Hobbs and others.⁴

The sampling system as show in Figure 2 is configured for measuring transient deviations in aerosols (such as those encountered in plumes or clouds). Consequently, air samples are taken in rapidly and automatically by a "grab-bag" sampling system. In addition to the grab-bag sampling (which is not completely isokinetic), an isokinetic sampling system is used. Both sampling systems condition the aerosol to a nearly constant relative humidity (<60%). [OPC I, EAA, and mass monitor sample is dried by a diffusion drier; OPC II and nephelometer sample is drawn from the 30 & heated chamber.]

A general index of the air pollution is obtained using an integrating nephelometer, 4 the automatic CNC, and an oscillating crystal mass monitor.⁵

Since the major interests in this study were the concentrations of atmospheric IN and CCN, some modifications were made to expand the B-23 capabilities in this portion of the instrumentation. An NCAR IN counter was installed aft of its usual location, allowing room for an operator. The Naval Weapons Center (NWC) Mee IN counter was installed where normally the University of Washington automatic CCN counter is mounted. The automatic CCN counter was replaced with a manual NCAR CCN counter. In addition, a multi-filter manifold was added for measuring IN by the Millipore filter method. The IN counters, the NCAR CCN counter, and the filters were calibrated in the laboratory prior to the flight.³

CLOUD PHYSICS INSTRUMENTATION

The cloud physics instrumentation on the B-23 is designed to provide comprehensive measurements of the sizes, spatial distributions, and physical characteristics of solid and liquid cloud and precipitation particles. This information is provided by seven different instruments:

1. Data on solid hydrometer characteristics (e.g. crystal type, degree of rimming and aggregation) are provided by impaction and Formvar plastic replication.⁶

2. Similar information for mm-size solid and liquid particles is provided by impact markings on the thin, metal foil of the foil sampler.⁷

3. The size spectra (concentration versus maximum particle dimensions) of cloud and precipitation particles over the size range 3 to 4500 μ m are provided by three Particle Measuring Systems (PMS) laser probes.⁸ Unlike the impaction devices the PMS data are processed and

displayed in real-time in the aircraft by the computer. Computed values of the effective radar reflectivity and precipitation rate (assuming spherical particles) are also calculated and displayed.

4. Cloud liquid water content is measured directly by a hot-wire sensor (Johnson-Williams device) and is also computed from the PMS data.

5. Ice crystal concentrations are measured by a laser depolarization device developed at the University of Washington.

An overall view of the spatial distribution of precipitation is provided by a 5-cm gyrostabilized weather radar.

The specifications of all the instrumentation for the aircraft is given in Appendix A (some of the instrumentation listed was not aboard during this experiment).

MEASUREMENTS, RESULTS, AND DISCUSSION

Descriptions of all of the flights for this project are given in Table 1. During portions of the ferry and project flights, measurements were made of the ambient aerosol. These measurements illustrate both the capabilities of the research system aboard the B-23 and provide some information on the "background" aerosol over the Florida peninsula during periods when the region was experiencing a rather polluted northern continental air mass. A few measurements were also made in the smoke plumes from a number of brush fires in the area of KSC.

AEROSOL PARTICLE AND CCN MEASUREMENTS

Figure 3 shows the aerosol size distribution near Ft. Collins on 15 March 1978 taken during the test flight of the NCAR and Mee IN counters. Sampling at 800 m above ground level (AGL) (777 mb), the total particle concentration was rather high (~10⁶ cm⁻³), indicating the presence of either fresh anthropogenic aerosol or gas-to-particle conversion products. However, particle concentrations decreased rapidly with increasing particle size. The rather good visibility which was observed is reflected in the low concentrations of 0.1 to 1 μ m particles. The large expanse of exposed soil in the area produced significant numbers of particles as large as ~8 μ m in diameter (strong northerly winds and dust devils were observed during the flight).

On the flight from Little Rock to Patrick AFB on 16 March 1978 measurements were taken near Little Rock at an altitude of 500 m AGL (957 mb) in visually polluted air. Figure 4 shows that the concentrations

f FARMER

<u>ن</u>

Date	Destination	Mission
13 March 1978	Ft. Collins, Colo.	Ferry aircraft from Seattle.
15 March 1978	Loveland, Colo.	Test flight to check out NCAR and Mee IN counters (installed in Ft. Collins).
15 March 1978	Little Rock, Ark.	Ferry aircraft from Loveland.
16 March 1978	Patrick AFB, Fla.	Ferry aircraft from Little Rock. Heavily polluted air mass, some en route sampling.
17 March 1978	Patrick AFB, Fla.	Pre-launch test flight. Inter- esting "background" data taken as well as samples from brush fire plumes.
23 March 1978	Patrick AFB, Fla.	"Background" aerosol data in vicinity of KSC.
24 March 1978	Boulder, Colo.	Ferry from Patrick AFB. Instruments returned to NCAR and NWC.
25 March 1978	Seattle, Wash.	Ferry from Boulder, Colo.

TABLE 1. B-23 Flight Operations.

ŧ.



of the particles in the optically important size range (0.1 to 1 µm) were more than 2 orders of magnitude greater than those measured at Ft. Collins, but the larger micron-sized particles were present in concentrations similar to those measured at Ft. Collins.

Later on 16 March 1978 (1328 EST), approaching Patrick AFB in bright, midday sunshine, the particle measurements made at 2,000 m AGL (787 mb) show possible effects of photochemistry (Figure 5). The concentrations of the smallest aerosol (~ 10^{-2} µm) were an order of magnitude greater than those measured near Little Rock, but the size distribution of the remainder of the aerosol was similar to that measured at Little Rock. The larger concentrations of the 10^{-2} µm particles may have been due to gas-to-particle conversion in air, rich in trace gases, flowing from the northwest across the continental United States (Figure 6).

One of the characteristics of such a polluted, aged air mass can be seen in Figure 7 where the data from Figure 5 are replotted as a particle volume distribution. It can be seen that this plot is distinctly trimodal. Such a distribution is normally interpreted as follows: the particles in the smallest size mode (0.01 to 0.1 µm) represent particle production by either gas-to-particle conversion or by fresh high-temperature combustion processes; the particles in the middle size mode (0.1 to 1 µm, often called the "accumulation mode") are a mixture of long-lived, directly-emitted particles in the large size mode (>1 µm, called the "coarse particle mode") are mostly short-lived aerosol produced directly from the earth's surface by mechanical processes.

The following day (17 March 1978), while practicing aircraft prelaunch procedures in the vicinity of KSC, measurements were taken in the same polluted air mass that was sampled on 16 March as well as in smoke plumes from trush fires. The size distributions of the aerosol samples from the polluted air mass (Figures 8 and 9) taken at 1,000 m AGL (917 mb) are similar to the measurements taken on 16 March. Measurements of the CCN concentrations from the polluted air mass on 17 March are shown in Figure 10. The CCN measurements were fitted to an expression of the form:

 $N = cS^k$

×.

where N is the CCN concentration (cm^{-3}) , c and k are empirical constants, and S the supersaturation in percent. For the measurements shown in Figure 10 the values of c and k were 3,000 cm⁻³ and 1.1, respectively. These values are typical for measurements in polluted air masses in the eastern United States as reported by Radke and Hobbs.⁹ The remainder of the CCN data are given in Table 2. The CCN concentration reported here are greater than those measured in background air at KSC in August, September 1977.¹





FLGURE 7. The Aerosol Volume Distribution Corresponding to Figure 5 Showing a Trimodal Character.





Space Center.

NWC TM 3667

ŧ

1

借



	16 Mar	ch 1978			17 Mai	ch 1978	
I	Flight to	Patrick	AFB		Flight	at KSC	
Time (EST)	s ^a (%)	N (cm ⁻³)	Remarks ^b	Time (EST)	s ^a (%)	N (cm ⁻³)	Remarks ^b
1309 1310 1320 1324 1327 1330 1333 1336 1338 1355 1357 1401 1405 1414 1408 1422	.21 .23 .22 .31 .57 .70 .58 .38 .26 .20 .21 .40 .58 .39 .38 .40	1680 1650 1090 0396 0264 0429 0495 0363 0561 0561 0396 0495 1390 0462 2010 1980	Free-stream Free-stream Bag Free-stream Free-stream Free-stream Free-stream Free-stream Free-stream Free-stream Free-stream Free-stream Free-stream	1544 1548 1553 1617 1618 1620 1628	.23 .40 .56 .23 .40 .56 .46	1350 1390 2140 0660 0825 1848 2310	Free-stream Free-stream Bag ^C Free-stream ^C Free-stream ^C Free-stream

TABLE 2. CCN Data.

a S means supersaturation with respect to water. b Free-stream sample means the CCN instrument was sampling outside air, bag sample means outside air was grab-sampled with a bag and then monitored with the instrument. C Plotted in Figure 10.

¥. ..

. . .

2

4

đ

1

F

Measurements in the smoke plumes from brush fires on 17 March were made also at 1,000 m altitude. A typical set of measurements from the integrating nephelometer and from the rate meter on OPC I is shown in Figure 11. The measured particle size distribution for this smoke sample (Figure 12) shows that the concentrations of particles 0.3 to 1 μ m in size were about an order of magnitude greater than in the "background" air (see Figure 8) and that particles ~10⁻² μ m in diameter were also present in large concentrations. Such high concentrations of 10⁻² μ m particles are somewhat surprising from a presumably low-temperature fire. However, as we have previously observed in smokes from woody, biomass fires, most of the aerosol volume (mass) is contained in the accumulation mode. The measurements on 17 March (Figure 13) are consistent with this observation.

During our stay in Florida we made no cloud particle measurements. However, to demonstrate the B-23 capabilities in this area, Figure 14 illustrates the cloud particle size distribution measured in a precipitating, marine cumulus near Seattle.

IN MEASUREMENTS

Airborne measurements of 17 and 23 March and ground measurements of 22 March from the membrane filters are summarized in Table 3. Measurements were made at -20, -16, and -12C at a supersaturation (with respect to water) of approximately 6%. Similar concentrations were obtained with both the Sartorius and Millipore filters

Figures 15 and 16 show the counts plotted as a function of temperature. The IN activity dropped only an order of magnitude from -20 to -12C (ordinarily a change of 2 orders of magnitude would be expected, but the validity of the rule on which this assumption is based is not well founded). The IN concentration reported in Figures 15 and 16 are consistent with IN concentrations measured in background air at KSC in August, September 1977.¹

The counts were relatively high for a number of samples; in fact, they are not much lower than ice crystal concentrations observed on FACE (Florida Area Cumulus Experiment) by Sax.¹⁰ The low counts of 17 March were collected in air over land, while the high counts of 22 March were taken on the ground near the beach in a steady breeze from the ocean. The 23 March samples (Figure 16) show both high and low counts. Further analysis may reveal that these relate to the altitudes at which the samples were obtained and to the source of the air (over land versus over water).

Figures 17 and 18 show a comparison of the filter counts with those from the NCAR and Mee counters (continuous counts). The 23 March filter counts are in good agreement with the continuous counts, even on an



NWC TM 3667

17

100 AN 1 AN





C 2.5	$\begin{array}{c} \operatorname{Conc} \\ (\mathfrak{X}^{-1}) \end{array}$	0	0.01	0	0.09	0.07	0.02	0.27	0.15	2.80	0.80	0.12	0.07	0.06	0	0	0.41	1.11	0.06	0.06	0.01	0
-12 ΔT =	Count	0	4	0	32	∞	4	36	48	84	56	16	4	4	0	0	77	60	ß	ω	~ s t	0
с 3С	$Conc(x^{-1})$	0.06	0.05	0.04	0.07	0.15	0.48	0.48	0.31	4.27	1.09	0.06	0	0.35	0.03	0.10	1.44	3.56	0.18	0.21	0.19	0.29
-16 AT =	Count	24	16	24	24	16	104	76	100	128	76	∞.	0	24	4	4	156	192	24	28	52	12
)c = 3c	$conc (\ell^{-1})$	0.10	0.06	0.04	0.19	1.00	1.65	3.45	2.19	7.07	1.31	0.59	0.44	0.53	0.32	0.88	4.67	8.22	0.76	0.53	1.24	0.29
-2(ΔT =	Count	42	20	20	68	108	356	552	200	212	92	80	24	36	44	36	504	444	104	72	336	20
	Vol (L)	420	350	560	350	108	216	160	320	30	70	136	54	68	136	4T	108	54	136	136	272	68
	Time (EST)	1520-1630	1520-1630	1520-1630	1520-1630	1559-1609	1609-1629	1630-1640	1642-1702	1626-1636	1626-1636	1637-1647	1647-1651	1658-1703	1704-1714	1717-1720	1723-1733	1734-1739	1807-1817	1818-1828	1844-1904	1913-1918
	Type/no.	SA 1	SA 2	HA P2	HA P4	64 3 64	SA 4	HA A	HA B	SA 5	SA 6	HA 6	HA 7	HA 8	HA 9	HA 10	SA 8	SA 9	SA 11	SA 12	SA 12A	SA 13
	Date	3-17	3-17	3-17	3-17	3-22	3-22	3-22	3-22	3-23	3-23	3-23	3-23	3-23	3-23	3-23	3-23	3-23	3-23	3-23	3-23	3-23

19

Florida Membrane Filter Data. TABLE 3.

1

ters cale with the first

SA = Filters from SUNYA made by Sartorius. HA = Filters from UW Supply made by Millipore, 0.45 μ gridded. NOTE:

54 j

NWC TM 3667



FIGURE 16. Membrane Filter Ice Nucleus Data for 23 March 1978 Flight Along the Coast. **





FIGURE 18. Correlation Between Ice Nucleus Counts From Membranes and NCAR Counter.

.*

absolute basis. However, in the 17 March data, the filter counts are much lower than those from the NCAR counter. In this flight only four parallel filter samples were taken for the entire period, resulting in large sample volumes and the possibility that some of the nuclei may have been suppressed by the concurrently collected aerosol particles. The fact that both the highest and lowest counts were from the smallest volume appears to discount the possible adverse effect of large sample volume (see Table 3). Further, during Project FACE, hundreds of membrane filter samples were taken over the peninsula and these invariably gave much lower counts than the NCAR counter. It can be speculated that for the 17 March sampling over land, the NCAR counter was not influenced by the apparent "suppression effect" as was the membrane filter.

Using Figure 17, the counts from the NCAR and Mee instruments can be compared. During the early part of the flights, the two instruments gave similar counts, but as the flights progressed, the Mee counts became lower than the NCAR counts. An examination of the operating variables of the Mee counter (given in Table 4) may explain this decrease. The chamber temperature (T_{sump}) remained constant throughout the flight (except when it was cooling), but the inlet air temperature (T_{inlet}) decreased significantly. When T_{iniet} was high, the trigger level also had to be set high to avoid counting cloud droplets. When T_{inlet} was low, the trigger level could be set low and not count droplets. This indicates that the moisture content of the cloud decreased with decreasing T_{inlet} . A decrease in moisture would have inhibited ice crystal formation and growth and would have led to suppressed IN counts in the Mee counter.

A few tests with the NCAR IN counter were performed on the ground at Patrick AFB. The IN counter remained in the aircraft. Milligramsized pieces of Shuttle solid propellant were burned in a small container. Very little activity at -20C was observed in contrast to the tests at Colorado State University.³ Recently similar pieces were tested at the NCAR. Some pieces showed a lack of activity and some showed considerable activity. Clearly, much more research should be carried out in the laboratory on the properties of the propellant as a source of IN.

CONCLUSIONS

The airborne measurement facility was used to obtain aerosol particle sizes and concentrations at Ft. Collins, Little Rock, and in the vicinity of Kennedy Space Center (KSC); IN and CCN measurements were made in the vicinity of KSC. Significant differences in particle concentrations were measured between clean air over Ft. Collins and considerably dirtier air over Little Rock and KSC. The air mass over KSC originated in the high plains region 3 days earlier. The air over Ft. Collins was probably

Remarks	Chamber cooling &่งนก	Inlet air temper- ature slowly chang-	ing; trigger level adjusted as cloud	gensity decreased.					an a	Note trigger level change		minin
Trigger level) (mv)	10.0 11.0 13.0	13.0 13.0 14.0	13.0	11.0	10.0 10.0	10.0 8.0		10.0	10.01	11.0	11.0	0.11
Flow (% min ⁻¹	10 10	10	10	10	10	10		1 01	10	10	10	10
Tfulet (C)	28.0 26.8 27.4	23.7 23.3 23.5	22.2	20.7	19.0 18.2	18.0 17.6		21.1	19.9			
T _{sump} (C)	-11.0 -18.0 -19.0	-20.4 -20.5	-20.4 -20.9	-20.4	-20.5 -20.6	-20.8 -20.2		-19.8	-20.1	-20.6	-20.7	-20.8
Average Conc. (ℓ^{-1})	6.6 5.7 2.3	0.63 0.45 0.10	0.08 0.20	0.20	0.18 0.06	0.03 0.10		4.0	4.8	0.084	0.080	0.10
Time Interval (EST)	1626-1536 1637-1647 1647-1651	1658-1709 1709-1714 1717-1720	1723–1733 1734–1739	1740-1750 1801-1806	1807–1817 1818–1828	1844-1904 1913-1918	1520-1530	1540-1550	1550-1600	1600-1610	1610-1620	1620-1630
Date	3-23 3-23 3-23	3-23 3-23 3-23	3-23 3-23	3-23 3-23	3-23 3-23	3-23 3-23	3-17	3-17	3-17	3-17	3-17	3-17

TABLE 4. Data From the Mee Ice Nucleus Counter.

Ľ,

23

NWC TM 3667

representative of the air in the high plains region and became increasingly dirtier as it flowed south-eastward toward KSC due to numerous sources of natural and man-made particles. The CCN measurements at KSC were typical of polluted eastern seaboard air. The CCN concentrations were greater than the CCN concentrations obtained KSC in August, September 1977.

IN concentrations were measured using NCAR and Mee portable IN counters and filter devices. The data from the NCAR and filter devices correlated satisfactorily. The data from the NCAR and Mee counters correlated satisfactorily until the Mee counter inlet air cooled significantly. The concentrations of IN detected with the filters are similar to concentrations measured at KSC in August, September 1977. Filter derived IN concentrations reported here were systematically lower over the land and higher over the sea. This difference in IN concentrations may be related to the source of the air and warrants further investigation.

REFERENCES

- Naval Weapons Center. Airborne Measurements of Cloud-Forming Nuclei and Aerosol Farticles in Stabilized Ground Clouds Produced by Solid Rocket Booster Firings, by E. E. Hindman II, G. G. Lala, F. P. Parungo, P. T. Willis, R. J. Bendura and D. C. Woods. China Lake, Calif., NWC, October 1978. 76 pp. (NWC TM 3589, publication UNCLASSIFIED.)
- 2. E. E. Hindman. "Ice Nuclei Measurements From Solid Rocket Motor Effluents," submitted to Proceedings Shuttle Environmental Effects Program Review, 21-22 March 1978, NASA/KSC, Florida.
- Naval Weapons Center. Laboratory Investigations of Cloud Formity. Nuclei and Aerosol Particles From Unpressourised Burns of Space Shuttle Propellant, by E. E. Hindman II, D. Garvey, G. Langer, F. K. Odencrantz, F. P. Parungo and G. L. Gregory. China Lake, Calif., NWC, December 1978. 88 pp. (NWC TM 3666, publication UNCLASSIFIED.)
- P. V. Hobbs, Z. W. Radke and E. E. Hindman II. "An Integrating Airborne Particle-Measuring Facility and Its Preliminary Use in Atmospheric Aerosol Studies," *Aerosol Set.*, Vol. 7 (1976), pp. 195-211.
- P. S. Daley and D. A. Lundgren. "The Performance of Piezoelectric Crystal Sensors Used to Determine Aerosol Mass Concentration," J. Am. Ind. Hyg. Assoc., Vol. 36 (1975), p. 518.
- P. B. MacCready, Jr. and C. J. Todd. "Continuous Particle Sampler," J. Appl. Metr. r., Vol. 3 (1964), pp. 450-460.
- R. M. Schecter and R. G. Russ. "The Relationship Between Imprint Size and Drop Diameter for an Airborne Drop Sampler," J. App?. Meteor., Vol. 9 (1970), pp. 123-126.
- 8. R. G. Knollenberg. "Three New Instruments for Cloud Physics Measurements," in *Preprints International Conference on Cloud Physics, 26-30 July 1976.* Boston, Mass., American Meteorological Society, 1976. Pp. 554-561.
- L. F. Radke and P. V. Hobbs. "Cloud Condensation Nuclei on the Atlantic Seaboard of the United States," *Science*, Vol. 139 (1976), pp. 999-1002.
- R. I. Sax, J. Thomas, M. Bonebrake and J. Hallett. "Difference in Evolution of Ice Within Seeded and Nonseeded Florida Cumuli as a Function of Nucleating Agent," in Preprints of the Sixth Conference on Planned and Inadvertant Weather Modification, 10-13 October 1977, Champaign, Ill. Bostom, Mass., American Meteorological Society, 1977. Pp. 202-205.

.*

.,

Appendix A

SPECIFICATIONS OF RESEARCH INSTRUMENTS ON THE B-23 AIRCRAFT

PRECEDING PAGE BLANK NOT PU MON

	AIRCRAFT
	-73
	S
	IGTON
	VIHS
	N L
	Σ
	VERS
V	IN
ABLE	Ħ
H	NO S
	ÉNT:
	TRU
	No.
	ARCH
	RESE
	8
	IONS
	ICAT
	E F
	a's

E,

Parameter	instrument Type	Manufacturer and Model No.	Range	Error	l ime Constant	Un-Board Recorded?	rower Requirements	CN I PHILID
Total air Temperature (T _{TOT})	Platinum wire resistance	Rosemont Eng. Co. 102CY2CG +414 L Bridge	-100 to +200°C	=±0.1°C (Manuf. Spec.)	≓l sec	Yes	1.44/28vDC	Hodified to give 0-5V output
Static Air Temperature (T _{STAT})	Platinum wire resistance	In House	-100 to +100°C	±0.5°C	=] sec	Yes	6W/28VDC	Minco resistance element in reverse flow housing (S1083) Recovery coefficient) =0.2-0.3 Unreliable under icing conditions
Dewpoint	Dew condensation type	Cambridge Model 880	-46 to +50°C	=+1°C (Manuf. Spec.)	2°C/sec	Yes	50W/IISVAC	Modified to give 0-5V output for linear output over -40 to +10°C
Pressure Altitude	Absolute capacitance pressure	Rosemont Eng. Co. Model 830 BA	0-15 psi	≃±0.2% full scale (Manuf. Spec.)	No specs	Yes	3w/28vDC	
True Air Speed (TAS)	Differential capacitance pressure sensor	Rosemont Eng. Co. Model 831 BA	0-±1 psi	=±0.2% full scale (Manuf. Spec.)	No specs	Yes	34/28vDC	TAS derived by means of on-board in-house built analog computer
Air Turbulence	Differential pressure sensor Model 1120	Meteorology Research Inc.	0-10 cm ^{2/3} sec ⁻¹	≈±10\$	3 sec	Yes .	204/28VDC	

NWC TM 3667

PDECEDING PAGE BLANK NOT FURS

					I F H H A CA				
Parameter	l nstrument Type	Manufacturer and Model No.	Range Er	ror	Time Constant	0n-Board Recorded7	Power Requirements	Remarks	
Liquid Water	Hot wire resistance	Johnson Williams	0-2 -3 No gm m 3 0-6 -3 gm m -3	specs	No specs	Yes	1 104/1 15V/400Hz 4204/28VDC		
Electric Field in Vertical Plane	Rotary field mill	Meteorology Research Inc. Model 611	0-±100kV ±1 m-1	\$0	0.2 sec	Yes	201/1 1 5V/400Hz 1 204/ 28VDC	Modified for 0-5V output and calibration circuitry added for ±20kV m ⁻¹	
Hydrometeor Sampler	Metal foil impactor	Meteorology Research Inc. Model 1220A	Particles greater than 250 µm in size				3004/28VDC		
Cloud Particle Sampler	Continuous particle replicator	Meteorology Research Inc. Model 12030	8	specs		Yes	300W/28VDC		
lce Crystal Counter	Optical polarization technique	In house	0-1000 No particles per liter	specs	lmrediate	Yes	1804/28vDC 504/115v 160Hz	50 µm diameter minimum detected crystal size	
Cloud Condensation Nuclei	Optical counting by light scattering	In house	0-5,000 ±1 cloud conden- sation nuclei/ cm3	80 0	l Cycle per 15 sec	Yes	5004 (Max) / 1 1 5V/ 60Hz		

TABLE A-I (continued)

NWC TM 3667

ŧ

1

€,

Parameter	lnstrument Type	Manufacturer and Model No.	Range	Error	ïime Constant	<u> </u>	Power Requirements	Remarks
lce Nucleus Concentrations	NCAR acoustical counter	E. Bollay Assoc. (modified in house)	0.01-500 counts per liter	No specs	20 sec rise time several minutes delay	Yes	250W/115V/60Hz	Hodified humidity control and aerosol generator. Compressor converted to 28VDC
lce Mucleus Concentrations	Fast response polarizing technique	Mee Indust.	0.1-10000 counts per liter	No specs	10 sec	Yes	1754/28VDC	
Sodium Particle Counter	Flame spectrometer	In house	0-10,000 per liter	81 11	lmmediate response	Yes	604/115V/60Hz	Detects NaCl particles larger than 0.05 µm in diameter
Altitude above Terrain	Radar altimeter	AN/APN22	0-20,000 ft.	±5% of indicated value	No specs	Yes	36W/28VDC 120W/115V/400Hz	
Weather Radar	5 cm gyro stabilized	Radio Corp. America AVQ-10	50 nautical miles	No specs		No		Addition monitor at position U
Aircraft Position and Course Plotter	Works off DME and VOR	In house	80 miles	²l mile	10 sec	Yes	30W/28VDC	Gives real time plot on sectional map of area of position of aircraft
Time	Time code generator	Systron Donner Model 8220	hrs, min, sec, (IRIG B code)	l part in 10 ⁵		Yes ,	12W/115V/60Hz	Modified for 28VDC operation. Hr, min, sec, display

TABLE A-1 (continuez)

đ 1

NWC TM 3667

TABLE A-1(continued)

Parameter	Instrument Type	Manufacturer and Model No.	Range	Error	Time Constant	0n-Board Recorded?	Pover Requirements	Requirements
Time	Radio WW	Gertsch RHF 1	ain			Yes	1W/18236	2.5, 5, 10, 15 mHz Voice announcements are recorded on tape
Ground Communication	FN transceiver	Motorola	approx. 100 miles			No	Internal batteries	150 MHz band
lntegrating Nephelometer	Optical Light Scattering	Meteorology Research, Inc. Model 1567	0 to42.5 x10 ⁻⁴ 0 to10 x10 ⁻⁴	±10%	10 sec	Yes .	200W/115V/60Hz	
Dew Point	.Dew condensation type	Cambridge Systems Model TH73-244	-40°C to +40°C		2°C/sec	Yes	55W/115VAC/ 400Hz	Switch selectable ranges for -40° to +10°C and -10° to +40°C
Heading	Gyro-compass	Sperry Model C-2	0-360°	+2°	200°/sec	Yes	1004/115VAC/ 400Hz	Slaved to navigation compass through synero-Digital converter
Ground Speed and Drift Angle	Doppler Navigator	Bendix Model DRA-12	0-20,000 ft.	No specs	No specs	Yes	2004/115vAC/ 400Hz	Basic sensor for computing horizontal wind direction and velocity.
Jltra-violet Radiation	Barrier- layer photo- electric cell	Eppley Laboratory, r Inc. #14042 r	0-100 -2 mcal_cm ⁻² min_1	5% full scale	0.1 sec	Yes	14/28v	

NWC TM 3667

٤

6

			IA	BLE A-1(con	tinued)			
Parameter	instrument Type	Manufacturer and Model No.	Range	Error	Time Constarit	0n-Board Recorded7	Power Requïrements	Remarks
Angle of Attack	Potentio- meter	Rosemount 861	±23°	±0.5°	0.1 sec	Yes	1W/28V	
Photographs	35-mm time- lapse camera	Automax Model GS-2D-111	ł	ł	l sec to 10 min	1	754/28v	Automatic recording of time of day, flight number and aircraft heading on each frame.
Total Gaseous Sulfur	FPD flame photometric detector	Heloy 285	mqd [-0	±l0 ppb	0, 1, 1 0 sec	Yes	200W/115V/60Hz	
0zone	Chemilumin- escence (C ₂ H ₄)	Monitor Labs 8410'A	0-5 ppm	qád L∓	د کal sec dependent on range	Yes	2504/115V/60Hz	
ИО, ИО ₂ , ИО _х	Chemilumin- escence (0 ₃)	Monitor Labs 8440	0-5 ррт	4qq T±	2 l sec dependent on range	Yes	2004/115v/60Hz	
Aerosol Particles	Mobility analysis	TSI 3030	1.3×10 ⁻² - 4.2×10 ⁻¹ ^{µm}	- 12	120 sec	Yes	20W/117V/60Hz	
Aerosol Particles	90°light scattering	ROYCO 202 (modified)	0.3-10µm	~ 🖂	6 sec	Yes	20W/117V/60Hz	

33

-X0

유 도

*

Ŧ

ž N = number of measurements

NWC TM 3667

- s

ι.

Parameter	l ns trument Type	Manufacturer and Model No.	Range	Error	Time Constant	On-Board Recurded?	Power Requirements	Remarks
Aerosol Particles	Forward 1 ight- scattering	Royco 225 (modified)	1.7-39µm	- K	6 sec ⁺	Yes	40W/117V/60 Hz	
Aerosol Particles and Cloud Particles	Forward light- scattering	PMS ASSP100	2.8-66µm	- 🕅	6 sec [†]	Yes	604/117V/60 Hz 1004/28V DC	
Cloud Particles	Diode occultation	PMS 0AP-200X	20-300µm	- 14	6 sec [†]	Yes	60W/117V/400 Hz 100W/28V DC	
Precipitation Particles	Diode occul tation	PMS 0AP-200Y	300-4500 µ ^m	- 1	6 sec [†]	Yes	60W/117V/400 Hz 100W/28V DC	
Aitken Nuclei	Light transmission	General Electr CNCII (modified)	ic >0.002µm	- 14	1.5 sec	Yes	200/117V/60 Hz	
Aerosol Particles	Direct impaction	Glass slides	5-100µm					
lce Nuclei	FILTRATION	Nucleopore/ Millipore	0.2-200µm				150W/28V DC	
Aerosol Particles Mass	Electro- static deposition	TSI Model 3021	0.2-2 ₁ m		120 sec	Yes	1004/117v/60 Hz	
Aitken Nuclei	Rapid expansion chamber	Gardner Type CN	0-2 х 10 ⁵ /си < 0.002µm	-				
[†] Limited by me	thod of record	1 îng						

34

TABLE A-1(continued)

NWC TM 3667