

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

NASA CONTRACTOR REPORT 141435

Deep Sea Tides Determination From GEOS-3

George A. Maul
and
Alan Yanaway

{NASA-CR-141435} DEEP SEA TIDES
DETERMINATION FROM GEOS-3 Final Report
(National Oceanic and Atmospheric
Administration) 27 p HC A03/MF A01 CSCL 08C

N78-18661

Unclas
G3/48 06610

February 1978

NASA

National Aeronautics and
Space Administration

Wallops Flight Center
Wallops Island, Virginia 23337
AC 804 824-3411



NASA CONTRACTOR REPORT 141435

Deep Sea Tides Determination From GEOS-3

George A. Maul
and
Alan Yanaway

National Oceanic and Atmospheric Administration
Atlantic Oceanographic and Meteorological Laboratories
Miami, Florida 33149

Prepared under Purchase Order No. P-57579 (G)



National Aeronautics and
Space Administration

Wallops Flight Center

Wallops Island, Virginia 23337
AC 804 824-3411

Table of Contents

	Page
Introduction	1
Data Management and Processing	6
Data Analysis	9
Results	14
Conclusions	19
References	22

Introduction

One of the outstanding problems of geophysics is the global determination of the oceanic tide. The coastal tide can be markedly different from the oceanic tide due to the influence of bottom topography (Redfield, 1958). Many measurements exist of the coastal tide, but few are known in the deep sea. If a radar altimeter on a satellite could adequately detect deep-sea tides (NASA, 1969), the need for sea-floor pressure gages could be significantly reduced. Zetler and Maul (1971) showed that it was possible to retrieve the most important tidal amplitudes and phases from a simulated satellite altimeter in the presence of noise which was larger than the signal. A practical test of this concept was performed using the GEOS-3 altimeter data and is reported herein.

Geometry of the measurements is shown in Figure 1. Height of the spacecraft above the ellipsoid and the corrected altitude measurement are provided by the NASA Wallops Flight Center; details of the tracking techniques and microwave propagation corrections are given in Leitao, et al. (1975). For the purposes of this report, the oceanic tide will be considered the temporal variability of the sea-surface height at a particular location in certain tidal frequencies (see again Fig. 1). Perturbations in the sea-surface height due to wind waves, swell, quasi-geostrophic currents and eddies, and to steric changes are considered along with tracking and propagation inaccuracies, to be noise.

Test site for this experiment is the GEOS-3 calibration area off the east coast of the United States. Surface truth for the




Figure 1. Schematic of the measurement geometry. Height of the spacecraft above the reference ellipsoid is determined from tracking data; altitude measurement is from the corrected radar altimeter data. Note that the ellipsoid, the geoid, and the sea-surface vary independently of each other.

ORIGINAL PAGE IS
OF POOR QUALITY

observation of oceanic tides does not require concurrent measurements if the amplitude and phase of the tidal constituents are well known. For the GEOS-3 calibration area, Mofjeld (1975) developed an empirical tidal prediction model; development of that model was part of this contract. Mofjeld's model, when compared with a deep-sea tide gage within the GEOS-3 calibration area, had a standard deviation of ± 3 cm. The amplitude of the tide in this area is approximately 60 cm. Signal to noise ratio due to inaccuracies in the model is 20:1, which is adequate for this analysis.

To analyze altimeter data for tides, the calibration area was divided into $1^\circ \times 1^\circ$ squares of latitude and longitude. Referring again to Figure 1, consider a $1^\circ \times 1^\circ$ square centered on the vertical line connecting to the center of mass. An altimeter measurement of the sea surface taken at another point along the curve of the ellipsoid within the $1^\circ \times 1^\circ$ square will be subject to a difference due to the combination of the slope of the geoid and the slope of the tidal wave. It is desired to relate each measurement within the $1^\circ \times 1^\circ$ square to the center; this can most simply be accomplished by neglecting geoid and tidal effects, if they are small enough.

Mofjeld's (1975) model shows that for an area even as large as $5^\circ \times 5^\circ$, the error due to assuming a uniform areal rise and fall is less than ± 5 cm in the GEOS-3 calibration zone. Marsh and Vincent's (1974) gravimetric geoid shows a broad minimum in the vicinity of 30°N , 70°W (Fig. 2); geoidal variance is about ± 1 m in a $5^\circ \times 5^\circ$ square here, and this variance is within the noise range that Zetler and Maul (1971)

GODDARD SPACE FLIGHT CENTER DETAILED GRAVIMETRIC GEOID




Figure 2. NASA's Goddard Space Flight Center detailed gravimeter geoid based on the work of Marsh and Vincent (1974). Center of the analysis region used herein is marked by a rectangle near 29.5°N , 70.5°W (289.5°E).

ORIGINAL PAGE IS
OF POOR QUALITY

successfully retrieved the tides. Bottom topography (Bush, 1976) is quite uniform in this region (known as the Hatteras Abyssal Plain), which supports Marsh and Vincent's calculations. Finally, a deep-sea tide gage (Zetler, et al., 1975) was located at $28^{\circ}08'N$, $69^{\circ}45'W$, and the amplitudes and phases of the tidal constituents are well known. Based on these facts, the $5^{\circ} \times 5^{\circ}$ square centered on $29.5^{\circ}N$, $70.5^{\circ}W$ was chosen for the analysis, and to first order, it is assumed that the tides and geoid are uniform.

Data Management and Processing

Initially GEOS-C data were received in one of two formats: the 7-track binary packed decimal, and the 7-track card image BCD. These formats existed until January, 1977 when the binary 7-track format was replaced by the binary 9-track format. The 7-track BCD formatted tape was eliminated. Seventy-one (71) 9-track tapes were received. The final mailing of 20 tapes was received in late August, 1977. Nine more tapes were received on 29 September, 1977. These had been sent to an incorrect address and were forwarded by the recipient.

These 71 tapes were difficult to read and necessitated the option that parity and frame count errors be ignored on reading. On reading a record, the format indicator was unpacked to determine the data rate. This determined which number was a valid altimeter status word for that record. All status words were then compared to this standard, and for all data rates each sample had to be valid in order for that record to be acceptable.

The latitude and longitude were then unpacked and, if in the calibration area, were accepted. The various parameters were then unpacked. All these data were arranged chronologically and ready for analysis.

The summary report computer printout distributed by Wallops Flight Center indicates that 357 days of data were acquired and distributed. These data varied from one to ten orbit segments per day; the elapsed time between the first and last data tape is 18 months. There are then no data for one third of the time these tapes cover. The elapsed

time in that portion of the calibration area represented by the $5^{\circ} \times 5^{\circ}$ shaded box (Fig. 3), is 498 days. There are 97 days for which data are available in this area and a total of 148 separate data points within the 97 days. These points are scattered throughout the $5^{\circ} \times 5^{\circ}$ area.

Both high and low intensity mode data were used in this study in order to have adequate samples. Whenever a pass crossed any $1^{\circ} \times 1^{\circ}$ box, all altimeter values in that pass were averaged, and that single averaged value was considered a measurement of the sea-surface height (see Fig. 1). Each average includes an error due to variations in the tides and the geoid across each $1^{\circ} \times 1^{\circ}$ box. Maximum range of the geoid in any $1^{\circ} \times 1^{\circ}$ box in the $5^{\circ} \times 5^{\circ}$ area (Fig. 3) is 1 meter, the average value being approximately 0.2 meters. In summary, the error introduced by averaging a pass across a $1^{\circ} \times 1^{\circ}$ box (tidal and geoid), is no more than ± 0.5 m, and for the most part is ± 0.15 m.




Figure 3. $1^{\circ} \times 1^{\circ}$ squares of latitude and longitude in the GEOS-3 calibration area. Analysis region used herein is lightly shaded. The deep-sea tide gage used as surface truth was located in box number 20.

Data Analysis

Analysis of the GEOS-3 altimeter data for ocean tides was performed using two independent methods, both of which are least squares techniques. The methods of Zetler et al. (1965) have been applied to a simulation of this problem (Zetler and Maul, 1971) and require no further verification. Another technique derived by Vanicek (1971) is also applied, but since it is not well known to the oceanographic community, it was tested with simulated tidal data.

Consider a time series of the form

$$H(t) = H_0 + \sum_i A_i \cos (w_i t - \phi_i) \quad (1)$$

where the height (H) of the tide at time (t), is the sum of the mean value (H_0) plus a series (i) of cosine terms with amplitude (A), frequency (w), and phase (ϕ). From well known trigonometric identities equation (1) may be written

$$H(t) = H_0 + \sum_i C_i \cos (w_i t) + \sum_i S_i \sin (w_i t) \quad (2)$$

where $A^2 = C^2 + S^2$ and $\phi = \tan^{-1} (S/C)$.

A time series using equation (1) was generated for the M_2 , S_2 , N_2 , O_1 , and K_1 tides, and C , S , and ϕ given in equation (2), and the variance spectra were calculated by Vanicek's (1971) method using the program of Wells and Vanicek (1977). In order to simulate randomly acquired

data, a random number generator (R) on the interval (0,1) was used to degrade the data generated by equation (1) progressively until 100%, 90%, 80%...10% (R = 1, 0.9, 0.8,...,0.1) of the original data remained. Results of those calculations are given in Table 1.

Listed at the top of Table 1 are the original input values for the five constituents and the mean value. Record length is 2160 hours (3 months), and $\phi = 0$ for all inputs. The least squares analysis is within a few tenths of a percent of the input data when 100% of the original data are used (row 1.0). Even when only 10% of the original data are input (row 0.1), the maximum error in amplitude is 0.6% and the maximum error in phase is 3° . Thus, for a geophysical process where the frequency is well known, randomly spaced gappy data sampled without regard to the Nyquist theorem can be successfully analyzed.

If the frequencies are unknown, Vanicek's (1971) technique is still useful. Figure 4 is a variance spectrum for the semi-diurnal species input as before (Table 1). The ordinate in Figure 4 is the percentage variance, defined as

$$\frac{A_i^2}{\sum_i A_i^2} \quad (3)$$

and the abscissa is the period. It is clear that the spectrum using 100% of the data (dotted line) and the spectrum computed from 10% of the data (solid line) are quite similar. There are no errors in period, and the maximum error in percentage variance is 5% which occurs

Table 1

$$H(t) = H_0 + \sum_1^3 C_1 \cos \omega_1 t + \sum_1^3 S_1 \sin \omega_1 t$$

$\Sigma t = 2150 \text{ hrs}$

O_1 (25.82^h) K_1 (23.93^h) N_2 (12.66^h) M_2 (12.42^h) S_2 (12.00^h)

Run. No.	H_0		O_1		K_1		N_2		M_2		S_2	
	C	S	C	S	C	S	C	S	C	S	C	S
Input	100	0	1	0	3	0	7	0	10	0	5	0
1.0	99.999	0.999	0.999	0.051	2.998	-0.113	7.003	0.013	10.000	-0.080	4.996	-0.007
0.9	100.000	0.999	0.999	0.051	2.998	-0.113	7.003	0.013	10.001	-0.080	4.996	-0.007
0.8	99.999	0.999	0.999	0.050	2.998	-0.113	7.003	0.013	9.999	-0.080	4.998	-0.008
0.7	99.998	0.997	0.997	0.050	2.998	-0.113	7.002	0.014	9.999	-0.079	4.993	-0.007
0.6	99.999	1.000	1.000	0.049	2.997	-0.113	7.003	0.013	10.001	-0.080	4.994	-0.007
0.5	100.000	0.999	0.999	0.053	2.996	-0.112	7.002	0.013	9.999	-0.078	4.996	-0.007
0.4	100.002	1.002	1.002	0.048	2.997	-0.112	7.001	0.015	10.003	-0.079	4.997	-0.006
0.3	99.999	0.998	0.998	0.048	3.002	-0.115	7.001	0.011	10.003	-0.081	4.995	-0.007
0.2	99.998	0.992	0.992	0.051	2.998	-0.117	7.001	0.013	10.004	-0.080	5.003	-0.010
0.1	100.000	0.999	0.999	0.054	3.000	-0.120	7.004	0.014	9.996	-0.077	4.994	-0.006




Figure 4. Comparison of the variance spectrum for the semi-diurnal constituents using least squares analysis. Dotted line used 2160 hourly values; solid line used 10% of the 2160 values randomly chosen. Theoretical values of the percentage variance are given below their identifying constituent abbreviation.

ORIGINAL PAGE 44
OF POOR QUALITY

in the M_2 constituent. Thus, if the signal to noise is low (there being no noise in this example), it appears that an unknown period can be detected, and then once detected, its amplitude and phase calculated.

The analysis techniques tested above were applied to the GEOS-3 data in the calibration zone. It should be noted that the calibration zone is typical of oceanic regions, and imposes a reasonable test. The number of observations would be increased by using a higher latitude site; the signal to noise would also be impaired by choosing an area with large tidal range. The intent herein is to question the applicability of GEOS-3 data for determining the global tide, rather than a proof of concept.

Results

Table 2 summarizes the calculations using the methods of Vanicek (1971) and Zetler et al. (1965); the known tidal constituents from Zetler et al. (1975) are listed at the bottom of the table. Tabulated are the amplitudes in meters, and the phases in degrees (relative to 0000 GMT, 1 March, 1975). The number of samples in each area size is based on 18 months of data. The average number of samples is 1.5 per month in each $1^{\circ} \times 1^{\circ}$ square (Zetler and Maul (1971) used more than 9 samples per month in their analysis which was based on different orbital parameters). Sparsity of samples undoubtedly contributes to the poor agreement between predicted values and observed in the GEOS-C data.

In most cases (Table 2) the GEOS-C derived amplitude is an order of magnitude more than the values reported by Zetler, et al. (1975). The phase calculations are equally uncorrelated. Comparisons of the two analysis methods (see $5^{\circ} \times 5^{\circ}$ rows) show some consistency in the calculation of amplitude (within 93%), but the phases are poorly related.

The correlation is graphically displayed in Figure 5. Observed sea-level heights from GEOS-3 are plotted along the ordinate, and the values predicted due to ocean tides by Mofjeld's (1975) model are along the abscissa. The range of the tide (signal) is at best an order of magnitude less than the measurement variability (signal + noise). Thus, the tidal signal to noise ratio is approximately 0.1, which is seven times smaller than assumed by Zetler and Maul (1971) in their successful theoretical analysis. Table 3 summarizes the

Table 2

vanicek (1971)

<u>Area Size</u>	<u>No. Samples</u>	<u>S₂</u>	<u>M₂</u>	<u>N₂</u>	<u>K₁</u>	<u>O₁</u>
		<u>Ampl./Phase</u>				
1°x1°	26	1.92/75.9	1.55/32.2	1.59/27.6	2.02/81.5	1.25/36.9
2°x2°	58	0.46/12.1	1.52/294.4	0.37/327.6	2.05/75.9	1.0/42.4
3°x3°	92	0.98/69.3	1.67/347.1	0.739/3.2	2.11/85.8	.96/337.2
4°x4°	119	1.24/42.5	1.83/1.7	0.577/29.8	2.16/280.0	.476/338.8
5°x5°	148	.81/20.6	1.35/315.5	0.75/18.8	1.86/303.4	.91/86.4

Zetler et al.
(1965)

<u>Area Size</u>	<u>No. Samples</u>	<u>S₂</u>	<u>M₂</u>	<u>N₂</u>	<u>K₁</u>	<u>O₁</u>
		<u>Ampl./Phase</u>				
1°x1°	26	.49/166.8	1.21/330.2	1.39/133.7	1.98/99.5	1.43/132.4
2°x2°	58	.48/354.6	1.49/279.1	.39/209.3	2.25/94.7	.96/179.6
3°x3°	92	1.01/309.6	1.63/228.4	.71/310.0	2.11/89.0	.95/249.0
4°x4°	119	1.20/335.4	1.85/215.4	.37/277.5	2.13/78.1	.49/251.1
5°x5°	148	.78/337.8	1.31/231.8	.62/307.8	2.01/70.2	.96/271.6

Zetler et al.
(1975)

<u>S₂</u>	<u>M₂</u>	<u>N₂</u>	<u>K₁</u>	<u>O₁</u>
<u>Ampl./Phase</u>				
0.071/30.8	0.345/0.6	0.080/339.8	0.077/194.7	0.061/197.6

ORIGINAL PAGE IS
OF POOR QUALITY




Figure 5. Comparison of tidal height observed by the GEOS-3 altimeter versus computed tides (Mofjeld, 1975) in the $5^{\circ} \times 5^{\circ}$ calibration area. Observed values are corrected for atmospheric effects but not for spatial variation in the geoid.

variance of sea-level height above the ellipsoid from the GEOS-3 altimeter in the $5^{\circ} \times 5^{\circ}$ square shaded in Figure 3. Mean height of sea-level in this $5^{\circ} \times 5^{\circ}$ square is 50.7 (± 1.3) meters below the ellipsoid. The low standard deviation is in agreement with the Marsh and Vincent (1974) gravimeter geoid (cf. Fig. 2), and confirms that geoid variability does not significantly contribute to the inability of the GEOS-3 data to discriminate the oceanic tide.

However, to further insure that geoid variability is not important, the calculations summarized in Table 2 were repeated after subtracting the Marsh and Vincent (1974) geoid. That is, the Vanicek (1971) and Zetler et al. (1965) techniques were applied to the temporal term

$$H(t) = h_{ss} - h_g \quad (4)$$

where h_{ss} is the GEOS-3 determined height of the sea-surface above the ellipsoid, and h_g is the height of the Marsh and Vincent $5' \times 5'$ geoid. The results of those calculations were essentially identical to the results summarized above, leading to the conclusion that the GEOS-3 data, in the form provided, is not useful for observing ocean tides.

As a final test of using GEOS-3 altimeter data to study temporal variability of the sea-surface, the percentage variance spectrum (cf. Equation 3) was computed for the $5^{\circ} \times 5^{\circ}$ calibration area. Tidal frequencies have been removed in this application of Vanicek's (1971) least squares technique. Because of the signal to noise analysis above, it is difficult to have a great deal of confidence in this spectrum. However, some

Table 3

Mean and standard deviation of the GEOS-3 height of sea-level above the ellipsoid in the 5°x5° calibration area (see Fig. 3).

1°x1° Box	Number of Points	Mean (Meters)	Std Dev (Meters)
10	24	-48.6	±3.9
11	24	-50.9	±6.8
12	22	-51.1	±7.1
13	28	-49.6	±7.1
14	34	-49.7	±2.8
17	36	-50.6	±5.9
18	33	-51.3	±6.1
19	26	-52.0	±3.3
20	26	-50.9	±3.3
21	31	-51.2	±3.7
27	27	-51.1	±2.7
28	35	-51.3	±3.2
29	33	-51.5	±3.6
30	28	-51.8	±3.8
31	24	-52.4	±3.5
38	30	-51.2	±3.9
39	32	-51.7	±3.1
40	35	-51.5	±3.8
41	32	-51.3	±4.0
42	28	-50.7	±4.7
52	31	-51.4	±4.2
53	31	-51.6	±4.3
54	29	-50.3	±3.5
55	31	-47.6	±7.2
56	34	-47.2	±9.6

ORIGINAL PAGE IS
OF POOR QUALITY

features are common to a similar analysis of Gulf Stream meanders made from infrared measurements by Maul, deWitt, Yanaway, and Baig (in preparation). The numerous spectral peaks with a period of a fortnight or so and less are commonly reported in the oceanographic literature. At 38 days, a strong peak (Fig. 6) is evident, which is probably due to the 37 day cycle in the GEOS-3 orbit. The most intriguing peak, however, is at 56 days. Hansen (1970) noted that the average periods of Gulf Stream meanders is about 14 months, which is close to 56 days, and Maul et al. noted this too in their spectra of meanders. This raises the interesting possibility that sea-level in the Sargasso Sea pumps up-and-down in response to the meanders, as well as to other forcing.

Conclusions

The GEOS-3 altimeter data as processed by the NASA Wallops Flight Center were analyzed for deep-sea tides in the calibration area of the western North Atlantic Ocean. It was found that the signal to-noise ratio of the data was about 0.1, and that only one observation every four days was available in a $5^{\circ} \times 5^{\circ}$ latitude & longitude area for the 18 months analyzed. Using two independent methods, the tides could not be resolved. Tidal variability will not detract from geoid determination if data averaging is used, however, other error sources such as orbit determination, altimeter correction, or mean (steric) sea level will influence the accuracy of the marine geoid.

The consistency of the calculated tidal amplitudes (Table 2) raises the question of tidal frequency errors in the tracking of GEOS-3. If there are undetectable errors of these frequencies in the data, it may never be possible to do deep-sea tide determinations with




Figure 6. Percentage variance of sea-surface heights in the $5^{\circ} \times 5^{\circ}$ calibration area as a function of period in hours. Note the variance at 38 days.

ORIGINAL PAGE IS
OF POOR QUALITY

future vehicles such as SEASAT-A. The average of the standard deviations given in Table 3 is ± 0.5 m of which can be attributed to variations of the geoid and oceans tides. SEASAT-A's radial orbit determination error is specified as ± 2 m; unless that can be improved upon by a factor of at least 2, it does not seem possible to extract tides from that data either, unless a refined approach is taken.

Refinement of the approach used herein forms the basis for suggestions for further research. From conversations held at the GEOS-3 Principal Investigator's Meeting (November, 1977) it appears that better orbit determinations would give the most marked improvement in the signal to noise ratio. Thus, a new analysis of the spectrum of variability (cf. Fig. 6) would identify known periods, such as the 37 day cycle, which could be filtered out. If filtering etc. increases the signal to noise by half an order of magnitude, it is reasonable to expect that the ocean tides would be observed. Success does not seem possible with these GEOS-3 data, but with improvements in the orbit determinations, SEASAT-A is still a viable contender.

References

- Bush, P. A. (1976). Bathymetry of the MODE-1 region. Deep-Sea Res., 23, pp. 1105-1113.
- Hansen, D. V. (1970). Gulf Stream Meanders between Cape Hatteras and the Grand Banks. Deep-Sea Res., 17, pp. 495-511.
- Leitao, C. D., C. L. Purdy, and R. L. Brooks (1975). Wallops GEOS-C altimeter preprocessing report. NASA Technical Memorandum, NASA TM X-69357, Wallops Flight Center, Wallops Island, Va. 68 pgs.
- Marsh, J. G., and S. Vincent (1974). Global detailed geoid computation and model analysis. Geophys. Surveys, 1, pp. 481-511.
- Mofjeld, H. O. (1975). Empirical model for tides in the western North Atlantic Ocean. NOAA Technical Report ERL 340-AOML 19, Boulder, Co. 27 pgs.
- National Aeronautics and Space Administration (1969). The terrestrial environment, solid earth and ocean physics; application of space and astronautic techniques. Report of a study at Willimstown, Mass.
- Redfield, A. C. (1958). The influence of the continental shelf on the tides of the Atlantic Coast of the United States. J. Mar. Res., 17, pp. 432-448.
- Vanicek, P. (1971). Further development and properties of the spectral analysis by least squares. Astrophys. and Space Phys., 12, pp. 10-33.
- Wells, D. E., and P. Vanicek (1977). Least squares spectral analysis. Submitted to Computers and Geosciences.

Zetler, B. D., M. D. Schuldt, R. W. Whipple, and S. D. Hicks (1965).

Harmonic analysis of tides from data randomly spaced in time.

J. Geophys. Res., 70, pp. 2805-2811.

Zetler, B. D., and G. A. Maul (1971). Precision requirements for a

spacecraft tide program. J. Geophys. Res., 76(27), pp. 6601-6605.

Zetler, B. D., W. Munk, H. Mofjeld, W. Brown, and F. Dormer (1975).

MODE tides. J. Phys. Oceano., 5, pp. 430-441.

1. Report No. NASA CR-141435		2. Government Accession No.		3. Recipient's Catalog No.	
4. Title and Subtitle DEEP SEA TIDES DETERMINATION FROM GEOS-3				5. Report Date February 1978	
				6. Performing Organization Code	
7. Author(s) George A. Maul and Alan Yanaway				8. Performing Organization Report No.	
9. Performing Organization Name and Address National Oceanic and Atmospheric Administration Atlantic Oceanographic and Meteorological Laboratories Miami, Florida 33149				10. Work Unit No.	
				11. Contract or Grant No. P57,579(G)	
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Wallops Flight Center Wallops Island, Virginia 23337				13. Type of Report and Period Covered Final Report	
				14. Sponsoring Agency Code	
15. Supplementary Notes					
16. Abstract <p>GEOS-3 altimeter data in a 5°x5° square centered at 30°N, 70°W were analyzed to evaluate deep-sea tide determination from a spacecraft. The signal to noise ratio of known tidal variability to altimeter measurement of sea level above the ellipsoid was 0.1. A sample was obtained in a 5°x5° area approximately once every four days. The randomly spaced time-series was analyzed using two independent least squares techniques, but it was not possible to retrieve the amplitude and phase of the M₂, S₂, N₂, O₁, or K₁ constituents.</p>					
17. Key Words (Suggested by Author(s)) GEOS-3 ocean tides			18. Distribution Statement Unclassified - unlimited STAR Category - 42,47,48		
19. Security Classif. (of this report) Unclassified		20. Security Classif. (of this page) Unclassified		21. No. of Pages 26	22. Price*