

## General Disclaimer

### One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.



NASA CR  
131630

January 1978

SC577.51AR

INTERNAL FRICTION Q FACTOR MEASUREMENTS

IN LUNAR ROCKS

ANNUAL REPORT NO. 4

For Period 01/01/77 thru 12/31/77

Contract No. NAS9-13846

General Order No. 577

Prepared for:

National Aeronautics and Space Administration  
Lyndon B. Johnson Space Center  
Science and Applications Directorate  
Houston, Texas 77058

by:

*B. R. Tittmann*  
B. R. Tittmann  
Principal Investigator



This work was sponsored by the National Aeronautics and Space Administration. Reproduction in whole or in part is permitted for any purpose of the United States Government.



(NASA-CR-151630) INTERNAL FRICTION Q FACTOR MEASUREMENTS IN LUNAR ROCKS Annual Report, 1 Jan. - 31 Dec. 1977 (Rockwell International Corp., Thousand Oaks) 6 p  
EC AC2/MF A01  
CSCI 03B 03/91  
Unclas  
05340  
N78-17977

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) INTERNAL FRICTION Q FACTOR MEASUREMENTS IN LUNAR ROCKS - ANNUAL REPORT NO. 4		5. TYPE OF REPORT & PERIOD COVERED Annual Report 01/01/77 thru 12/31/77
		6. PERFORMING ORG. REPORT NUMBER SC577.51AR
7. AUTHOR(s) B.R. Tittmann		8. CONTRACT OR GRANT NUMBER(s) NAS9-13846
9. PERFORMING ORGANIZATION NAME AND ADDRESS Science Center, Rockwell International 1049 Camino Dos Rios Thousand Oaks, CA 91360		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS National Aeronautics and Space Administration Lyndon B. Johnson Space Center Houston, Texas 77058		12. REPORT DATE January 1978
		13. NUMBER OF PAGES 5
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report)  UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)  Reproduction in whole or in part is permitted for any purpose of the United States Government.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Quality factor Q, confining pressure, basalt, volatiles, attenuation, seismic waves, terrestrial analog, absorbed H <sub>2</sub> O, internal friction, damping, elastic modulus, absorption, vacuum, outgassing		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) In order to better interpret recently reported values for the variation of seismic Q as a function of depth below the lunar surface, we have developed apparatus and made laboratory measurements of Q as a function of hydrostatic pressure, temperature and frequency. Our measurements of the Q associated with shear deformations at pressures up to 2.5 kbar at room temperature have demon- strated that the large difference in Q between well outgassed and volatile-rich rocks persists to pressures corresponding to a depth of at least 50 km. Here we report new measurements of Q as a function of temperature, on the development		

of techniques to measure the  $Q$  associated with extensional deformations under hydrostatic pressure, on the derivation of theoretical relations between our laboratory  $Q$  values and the attenuation coefficient of seismic waves, and on the development of a model for the mechanism of adsorption.

UNCLASSIFIED



INTERNAL FRICTION AND MODULUS MEASUREMENTS IN LUNAR AND LUNAR ANALOG  
ROCKS, B.R. Tittmann, H. Nadler, J. Curnow, and J.M. Richardson  
Science Center, Rockwell International Thousand Oaks, CA 91360

In order to aid in the interpretation of the recently reported seismic Q versus depth profiles<sup>(1,2)</sup> we have begun laboratory Q measurements as a function of hydrostatic pressure, temperature, and frequency. We have already reported<sup>(3)</sup>  $Q_s$  (shear wave) measurements up to 2.5 kbar at room temperature and demonstrated that the dramatic differences in Q between thoroughly out-gassed and volatile-rich rock persist to confining pressures corresponding to a depth of at least 50 km. Here we report on measurements of Q as a function of temperature, on the development of techniques to measure  $Q_p$  (longitudinal wave) under hydrostatic pressure, on the derivation of theoretical relations between laboratory Q and seismic attenuation, and on the development of a model for the absorption mechanism.

(1) Temperature Dependence

Q measurements were performed in the temperature range -100 to 450°C on lunar rock 70215.85 and on analogs of lunar basalt at a frequency of about 50 Hz. The measurements were carried out at  $2 \times 10^{-7}$  Torr with our low frequency flexural apparatus<sup>(4)</sup> modified for the admission of dry N<sub>2</sub> cooled to -100°C into a Cu tube surrounding the furnace and sample. The system was calibrated with a sample of fused silica which gave a background (apparatus) Q well above the values measured for the rock samples. A conspicuous feature of the rock data is the systematic increase in Q as the temperature is lowered to -100°C. This feature has been observed by us also in the 10 kHz range and aside from the detailed structure of the curves is qualitatively repeatable from run to run, and sample to sample. The result suggests that the cool ( $\sim -40^\circ\text{C}$ ) dry near-surface regions of the lunar crust should also give high Q values. Table I summarizes the results at high temperatures and shows that except for a moderate increase in Q at 100-200°C, the high Q values are observed to at least 450°C.

(2) Measurements of  $Q_p$  Under Hydrostatic Pressure

The measurement of Q for a bar vibrating in the extensional mode is straightforward under ambient conditions but becomes apparently meaningless at high confining pressures when the radiative losses into the pressure medium become excessive. (The Q of a metal rod decreases by a factor of 3 when subjected to a He pressure of only 0.8 kbar.) We have overcome this difficulty by rounding the end pieces of the vibrating bar to an aerodynamically low drag shape and have been able to obtain similarly high Q ( $Q \approx 1.0 \times 10^4$ ) on a polycrystalline Mo bar at 1 kbar as at ambient pressure. Since the rock samples are clad in a Cu sheath the measured modulus must be corrected for the cladding and we have derived the formulae to calculate the Young's modulus of the rock itself. Measurements carried out in the extensional mode for a well-outgassed analog of lunar basalt show roughly the same Q values as those obtained for the torsional mode over the hydrostatic pressure range studied (0-1.6 kbar).



## INT. FRICTION &amp; MODULUS MEASUREMENTS IN LUNAR &amp; LUNAR ANALOG ROCKS

B.R. TITTMANN

(3) Relationship between Laboratory Q and Seismic Q

In an effort to establish a quantitative relationship between the seismic data obtained for plane traveling waves and the laboratory data obtained in vibrating bars at resonance, we have derived the necessary theoretical expressions for both shear and longitudinal waves. Assumptions made in the derivation are that the strain amplitudes are small so that only linear processes are involved, that the internal friction is small ( $Q > 10$ ) and that the microstructure and the processes associated with it have characteristic scales short compared with the wavelengths, so that the Lamé constants  $\mu$  and  $\lambda$  may be expressed as complex functions of frequency. Under these assumptions and measurements of the density, the torsional and extensional modulus and the corresponding Q values, we are now able to calculate  $Q_p$ ,  $Q_s$ ,  $v_p$ , and  $v_s$  for seismic waves.

(4) Model for Absorption Mechanism

The results presented here and in previous reports have provided valuable clues to the mechanism by which an elastic wave is damped in a volatile-rich rock, and we summarize here the principal features of the absorption model which these clues suggest. Our observed increases in Q from  $Q \approx 50$  in laboratory air to as high as  $Q \approx 4800$ <sup>(5)</sup> in vacuum after strong outgassing demonstrate that the removal of trace amounts of adsorbed volatiles play the dominant role in the absorption mechanism. The Q measurements under hydrostatic pressures to 2.5 kbar<sup>(3)</sup> show that the absorption mechanism caused by adsorbed volatiles is not inhibited by the partial closing of fractures under confining pressure, and probably involves active sites at grain boundaries throughout the rock. The experiments with a great variety of volatiles<sup>(6)</sup> show that adsorbed H<sub>2</sub>O is by far the most effective volatile in reducing Q, most likely because of the well known strong bonding between H<sub>2</sub>O and SiO<sub>2</sub> molecules. The results of ellipsometric experiments<sup>(3)</sup> demonstrate that the strong absorption of H<sub>2</sub>O onto the rock surface does not lead to a uniformly covering layer of H<sub>2</sub>O many tens or hundreds of monolayers thick. Rather the H<sub>2</sub>O molecules must absorb preferentially onto active surface sites and diffuse into the interior of the rock. Depending on the specific nature of the fracture system of the rock and the influence of H<sub>2</sub>O on the cracks and pores, the H<sub>2</sub>O can reside as molecular water in sites favoring capillary condensation or as adsorbed species on grain and crack boundaries. The systematic increase in Q with decreasing temperature (without a discontinuous jump at 0°C) represents the immobilization of any traces of H<sub>2</sub>O still present after the long term outgassing treatment. These results prompt us to propose a model for the absorption mechanism which involves changes in the bonding, structure, and coverage of the molecular, physisorbed, and chemisorbed H<sub>2</sub>O at the crack and grain boundaries. We present the details of the model and a theoretical approach to describe the processes involved.

ORIGINAL PAGE  
OF POOR QUALITY

## INT. FRIC. &amp; MOD. MEAS. IN LUNAR &amp; LUNAR ANALOG ROCKS

B.R. TITTMANN

TABLE I

 Temperature Dependence of Q at 56 Hz  
 for a Terrestrial Analog of Lunar Basalt

T (°C)	Q	Conditions
450	900	In vacuum
350	950	of $10^{-7}$ Torr
250	900	after strong
150	700	outgassing
50	1000	

## References

- (1) Dainty A.M., Toksöz M.N. and Stein S. (1976), Proc. Lunar Sci. Conf. 7th, p. 3057.
- (2) Nakamura &, Latham G.V., Dorman H.J., and Duennebier F.K. (1976), Proc. Lunar Sci. Conf. 7th, p. 3113.
- (3) Tittmann B.R., Ahlberg L., Nadler H., Curnow J., Smith T. and Cohen E.R. (1977), Proc. Lunar Sci. Conf. 8th, p. 1209.
- (4) Tittmann B.R. and Curnow J. (1976), Rev. Sci. Instr. 47, p. 1516.
- (5) Tittmann B.R. (1977), Phil. Trans. Roy. Soc. London., A285, 475-479.
- (6) Tittmann B.R., Ahlberg L., and Curnow J. (1976), Proc. Lunar Sci. Conf. 7th, p. 3123.