General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

Produced by the NASA Center for Aerospace Information (CASI)

Application of Remote Sensing in the Determination of Water Quality in Nebraska Reservoirs

(NASA-CR	-14	776) APPLICATION O	F REMOTE	N76-30633
SENSING	IN	HE DETERMINATION OF	WATER	
QUALITY	IN	EBRASKA RESERVOIRS		
Univ.)	11	HC \$3.50	CSCL (Unclas 01766

Project Completion Report

Gary L. Hergenrader School of Life Sciences University of Nebraska-Lincoln July 22, 1976



Introduction

The purpose of this project has been to determine the feasibility of detecting and quantifying selected water quality parameters in Nebraska reservoirs which are useful for indicating their trophic status. The bulk of the results obtained over the last three years in this project was transmitted earlier to NASA in the form of a Masters' thesis by Mr. Kelly White. The data contained therein will not be duplicated here. One result reported in the thesis and which forms the basis for the present report was that CCT's from Landsat correlated very well with the water quality parameters chlorophyll, turbidity, and suspended solids. However, because the tape of only one overflight with concurrent ground truth was available, it was necessary to collect additional data in order to determine the usefulness of Landsat for measuring specific water quality parameters.

Methods

In June, July, and August, 1975 ground truth was collected from Lake McConaughy, a 35,000 acre reservoir in western Nebraska, coincident with the overflights of Landsat. Water samples were collected on six different dates and analyzed for turbidity, suspended solids, and chlorophyll, parameters which from our earlier work had correlated well with CCT reflectances. However, on three of the dates for which ground truth was collected the satellites were not operating when they passed over Lake McConaughy, the study site. Consequently the correlations and regressions reported below were derived from data obtained on only three of the six sampling dates.

The three CCT's corresponding to the ground truth were processed by the University of Nebraska's IBM 360 computer. The radiance values from each of the four spectral bands were printed out in the form of a map of Lake McConaughy. Reflectances in the various bands were then obtained from the map at the appropriate sampling sites. Following our previous protocol, the dependent variables chlorophyll, suspended solids, and turbidity were compared to the independent variables - reflectances in the four bands - by regression analysis. Both multiple and univariate regressions were examined. In order for a regression to be deemed significant we chose the same significance values used in our previous work; a coefficient of determination of .43 for univariate regressions and .60 for multivariate regressions, and a probability of less than 0.05 that the F value would exceed the tabular F value.

Results

The input data collected from ground truth and CCT reflectances are given in Table 1. The range of suspended solids measured (3-184 mg/1) and the distribution of values within this range are such to allow meaningful regressions. The range of turbidity and chlorophyll concentration is more restricted and is confined to the low end of the scale. Although useful statistics can be derived from the observations it would be desirable to have data of wider scope. The chlorophyll values less than 4 mg/m³ and turbidity values less than 2 FTU, because

	Ref	lectance	(mW/cm ²)	Chloro- Suspended phyll solids	Turbidity	
Date	Band 4	Band 5	Band 6	Band 7	(mg/m^3)	(mg/1)	(FTU)
6/19/75							
East	13.5	8.5	7.5	.5	.001	35	.80
Middle	15.0	9.5	5.0	.3	.27	16	1.40
West	18.5	14.5	5.5	1.0	4.07	99	5.10
7/7/75							
East	14.5	10.0	5.5	.5	.03	8	.90
Middle	17.5	12.0	6.5	1.0	.40	18	1.50
West	24.0	20.0	10.0	1.0	5.47	183	11.30
7/25/75							
East	13.5	9.0	5.0	.53	1.24	3	1.1
Middle	15.5	10.0	4.8	.01	1.54	3	1.6
West	23.5	19.5	10.0	.5	11.49	184	14.0

Table 1.	CCT reflectances and chlorophyll, suspended solids, and tur-	
	bidity from three stations in Lake McConaughy, summer, 1975.	

of the wide confidence limits associated with their measurement, are not very useful in the regressions we have developed. The chlorophyll concentrations measured in Lake McConaughy are typical of oligotrophic lakes even though Lake McConaughy is eutrophic by other parameters.

Table 2 shows the correlation coefficient "r" between the water quality parameters and reflectances in the different spectral bands. In every case band 7 (infra-red) proved to have lower correlation between chlorophyll, suspended solids, and turbidity than did the remaining three bands. In fact, in no instance was the derived regression equation with band 7 reflectances significant by the previous levels of significance we had adopted. On the other hand, the correlations between bands 4, 5, 6, and turbidity and suspended solids are very high indeed. The correlation between these bands and chlorophyll, although not as high, is still very strong. At this point the results would suggest that bands 4, 5, 6 from Landsat CCT would be exceedingly useful for detecting the parameters chlorophyll, suspended solids, and turbidity in lakes and reservoirs. Table 3 gives the univariate regression statistics for significant water quality - band reflectance relationships. The equations in the table will give the value of the parameter in water if reflectance from the appropriate spectral band is inserted at the appropriate place in the equation.

Multiple regression statistics were developed to examine the simultaneous interaction between dependent variables and reflectances in all four spectral bands. To be significant the regressions had to have a coefficient of determination of at least 0.6. Table 4 presents

Reflectance		Parameter					
source	Suspended solids	Turbidity	Chlorophy11				
Band 4	.9420	.9515	.8569				
Band 5	.9629	.9643	.8757				
Band 6	.8747	.8549	.7386				
Band 7	.4522	.3178	.1819				

Table 2.	Correlation coefficients	(r)	between CCT :	reflectances	and	
	water quality parameters.					

				Coeficient of	
Water parameter	Band	F value	Prob. > F	determination	Line Equations*
Chlorophy11	4	19.3438	.0032	.7343	0.8089(X) - 11.2527
	5	23.0197	.0020	.7668	0.7471(X) - 6.6568
	6	8.4004	.0230	.5455	1.3497(X) - 6.2445
Suspended Solids	4	55,0984	.0001	.8873	17.6271(X) -243.5568
	5	89.1447	.0001	.9272	16.2854(X) -143.4724
	6	22.7916	.0020	.7650	31.6867(X) -149.5407
Turbidity	4	67.0242	.0001	.9054	1.1835(X) - 16.2603
	5	92.9259	.0001	.9299	1.0840(X) - 9.4220
	6	19.0050	.0033	.7308	2.0585(X) - 9.4887

Table 3. Univariate regression statistics for significant reflectance - water quality relationships

* $X = reflectance, mW/cm^2$, from CCT.

Water parameter	Band	F value	Prob. > F	Coefficient of determination	Line Equations*
Chlorophy11	4,5,6,7	7.6570	0.0389	.8845	$-1.3756(x_4)+2.1153(x_5)+0.0789(x_6)-4.2372(x_7)+1.9216$
Suspended Solids	4,5,6,7	29.3317	0.0052	.9670	$-21.5186(x_4)+32.4514(x_5)+9.6019(x_6)-14.1302(x_7)-30.0667$
Turbidity	4,5,6,7	66.8495	.0019	.9853	-1.0194(x ₄)+1.9656(x ₅)+0.4358(x ₆)-3.4647(x ₇)-3.7173

Table 4. Multivariate regression statistics for significant reflectance - water quality relationships

* X_4 , X_5 , X_6 , X_7 are reflectances (mW/cm²) from bands 4,5,6,7

the statistics for these regressions. All four spectral bands were used in the multiple regression even though band 7 contributes little to it. The reflectances from band 7 could be eliminated with no loss in accuracy or precision.

Discussion

The objective of the research was to confirm our earlier observations that reflectance data from Landsat CCT's correlate very well with certain water quality parameters, especially suspended solids, turbidity, and chlorophyll concentration. The additional data we collected have resulted in even stronger correlations than we reported earlier. However, an unfortunate aspect is that the confidence intervals associated with the regression equations are extremely broad, suggesting that even though the parameters can be detected and measured by remote sensing, the accuracy of the measurements is questionable. Table 5 compares the confidence intervals of our regressions from the Salt Valley Lakes of eastern Nebraska with those developed more recently from Lake McConaughy. The confidence intervals of our most recent data are broader than these we reported earlier. Part of the reason is owing to the uncertainty associated with measuring very low values of chlorophyll and turbidity. For example, depending upon the spectral band, the confidence intervals for chlorophyll vary between 38 and 56% of the value predicted by the regression equation. However, if all chlorophyll values less than 4 mg/m³ are eliminated, the confidence intervals are reduced to a maximum of $\pm 59\%$ of the value predicted by

		Salt Vall	Les Lakes	Lake	McConaughy	
		x	Range	x	Range	
Turbi	ldity (FTU)	20	8-32	4	0.8-14	
	cophyll (mg/m ³)	76	45-109	3	<.01-11	
	ended solids (mg/l)	41	23-58	61	3 - 184	
		Confidence	intervals	for the	spectral bands	
		Chlore	ophyll	Cł	nlorophy11	
Band	4	15-	38%		41-400%	
Band	5	25-63%		38-434%		
Band	6	16-	16-31% 61-560			
		Suspended	Solids	Suspe	ended Solids	
Band	4	23-	52%		22-119%	
Band	5	23-	85%		19-188%	
Band	6	16-	29%		36-452%	
		Turbi	dity	T	urbidity	
Band	4	23-	75%		21-178%	
Band	5	33-	115%		18-437%	
Band	6	13-	31%		39-355%	

Table 5. Mean, range, and confidence interval for selected water quality parameters detected in different spectral bands the regression equation. Thus, concentrations above 4 mg/m^3 can be predicted with an accuracy of ±38-59% of the value calculated with our regression equation. Similarly, the confidence intervals for turbidity vary between 18 and 437% of the predicted value but if those observations less than 2 FTU are eliminated the interval narrows to ±18-138%. Moreover, if band 6 and 7 reflectances are not considered the confidence interval becomes ±18-24% of the predicted value. The data suggest that the smail values at the lowermost part of the measured range are seriously affecting the accuracy with which the water quality parameters can be quantified. Thus the lower limits of meaningful detection would appear in our reservoirs to be 4 mg/m^3 chlorophyll, 2FTU turbidity, and about 3-5 mg/l suspended solids. The data from the Sait Valley Reservoirs (Table 5) indicate that in concentrations up to 109 mg/m^3 chlorophyll. 32 FTU turbidity, and 58 mg/l suspended solids can be measured with fair accuracy. As the concentrations increase the confidence intervals become narrower.

Given the above considerations we conclude that CCT's from Landsat can be used to detect and quantify the water quality parameters suspended solids, turbidity, and chlorophyll. The measurements thus obtained are not precise enough to detect subtle changes in the trophic status of 'a lake or reservoir or to allow categorization of groups of lakes closely placed along the trophic spectrum. They can, however, be used with confidence we believe, to distinguish between and classify lakes at the ends of the trophic spectrum from oligotrophic to eutrophic.