



**EVALUATION PROGRAM**  
**for**  
**SECONDARY SPACECRAFT CELLS**

INITIAL EVALUATION TESTS  
OF  
EAGLE - PICHER INDUSTRIES, INCORPORATED  
6.0 AMPERE-HOUR, NICKEL-CADMIUM SPACECRAFT CELLS  
FOR

SEPARATOR MATERIAL EVALUATION

prepared for  
GODDARD SPACE FLIGHT CENTER

CONTRACT S-23404-G

(NASA-CR-141231) EVALUATION PROGRAM FOR  
SECONDARY SPACECRAFT CELLS: INITIAL  
EVALUATION TESTS OF EAGLE-PICHER INDUSTRIES,  
INCORPORATED 6.0 AMPERE-HOUR, NICKEL-CADMIUM  
SPACECRAFT CELLS FOR SEPARATOR (Nava1  
g3/44 10270  
N75-17789  
Unclass

WEAPONS QUALITY ENGINEERING CENTER  
NAVAL AMMUNITION DEPOT, CRANE, INDIANA

WEAPONS QUALITY ENGINEERING CENTER  
NAVAL AMMUNITION DEPOT  
CRANE, INDIANA 47522

EVALUATION PROGRAM  
FOR  
SECONDARY SPACECRAFT CELLS  
  
INITIAL EVALUATION TESTS  
OF  
EAGLE-PICHER INDUSTRIES  
6.0 AMPERE-HOUR NICKEL-CADMIUM SPACECRAFT CELLS  
FOR  
SEPARATOR MATERIAL EVALUATION

WQEC/C 75-32

17 JANUARY 1975

PREPARED BY

*J. D. Harkness*

J. D. HARKNESS

PREPARED UNDER THE DIRECTION OF

*D. E. Mains*

D. E. MAINS, Manager  
Space Satellite Cell Program Branch

APPROVED

*D. G. Miley*

D. G. MILEY  
By direction

Enclosure (1)

REPORT BRIEF  
INITIAL EVALUATION TESTS  
OF  
EAGLE-PICHER INDUSTRIES  
6.0 AMPERE-HOUR NICKEL-CADMIUM SPACECRAFT CELLS  
FOR  
SEPARATOR MATERIAL EVALUATION

Ref: (a) NASA Purchase Order S-23404-G  
(b) Initial Evaluation Test Procedure for Nickel-Cadmium  
Sealed Space Cells: NADC 3053-TP324 of 10 Apr 73

## I. TEST ASSIGNMENT BRIEF

A. The purpose of this evaluation test program is to insure that all cells put into the life cycle program are of high quality by the screening of cells found to have electrolyte leakage, internal shorts, low capacity, or inability of any cell to recover its open-circuit voltage above 1.150 volts during the internal short test.

B. The 66 cells, comprising 10 groups, were manufactured for the National Aeronautics and Space Administration, Goddard Space Flight Center, under NASA contract number NAS-5-17806, by Eagle-Picher Industries, Joplin, Missouri. They were manufactured to Goddard Space Flight Center's specification number S-716-P-6. All the cells had auxiliary electrodes, but these electrodes were not evaluated since the purpose of this test was to evaluate various separator materials. The cells were identified by Eagle-Picher's type number, RSN-6B, and serial numbers 1 to 70, non-inclusive. Two groups of cells had nylon separator material and the other groups had polypropylene. These cells are rated at 6.0 ampere-hours, contain double ceramic seals, and two cells in each group were fitted with pressure gauge assemblies prior to testing. Testing was funded in accordance with reference (a).

C. Test limits specify those values in which a cell is to be terminated from a particular charge or discharge. Requirements are referred to as normally expected values based on past performance of aerospace nickel-cadmium cells with demonstrated life characteristics. A requirement does not constitute a limit for discontinuance from test.

## II. SUMMARY OF RESULTS

A. One cell, S/N 46, with Hercules separator material, would not charge. Its initial resistance was 10 milliohms.

B. Only those cells with the PP-Canadian separator material and those with the N-Pellon material (groups R and F respectively) completed their initial charge without exceeding any test limits.

C. No group of cells completed their second charge, c/10 for 24 hours, without having any cell exceed a test limit.

D. Group R cells, with the PP-Canadian separator material, averaged the highest ampere-hours out (8.3) during the first capacity test, whereas Group O, PP-Grace material, averaged the lowest (5.8). Two cells each, from Groups O and N (PP-Grace material) did not deliver the rated capacity of 6.0 ampere-hours following this charge.

E. Group F cells, with the II-Pellon material, exhibited the highest average ampere-hours out (7.6) during the second capacity test. Group II cells averaged the lowest, 5.6 ampere-hours, in which five cells did not deliver rated capacity. Two cells each, from Groups L and O, and five cells from Group M did not deliver rated capacity. These groups have the PP-Grace type material.

F. During the charge efficiency test, only one cell each, from Groups R and F, failed to deliver the minimum capacity out requirement of 55 percent of capacity in, whereas Groups O and S had one cell each to pass this requirement.

### III. RECOMMENDATIONS

A. It is recommended that these cells be placed into the life cycling program for comparison of performance of the various types of separator material.

B. As of 14 November 1974, 10 battery packs, one made up of cells from each group, were on life cycle test.

RESULTS OF  
INITIAL EVALUATION TESTS  
OF  
EAGLE-PICHER INDUSTRIES  
6.0 AMPERE-HOUR NICKEL-CADMIUM SPACECRAFT CELLS  
FOR  
SEPARATOR MATERIAL EVALUATION

I. TEST CONDITIONS AND PROCEDURE

A. All evaluation tests were performed at room ambient (RA) pressure and temperature ( $25^{\circ} + 2^{\circ}$  C), with discharges at the 2-hour rate, and in accordance with reference (b), and consisted of the following:

1. Phenolphthalein leak tests (2).
2. Two capacity tests, with internal resistance measurement following the second discharge.
3. Internal short test.
4. Charge efficiency test.
5. Phenolphthalein leak test.

(See Appendix I for summary of test procedure.)

II. CELL IDENTIFICATION AND DESCRIPTION

A. The 66 cells were manufactured with 10 various types of separator material. The cells were identified by the manufacturer type number, RSN-6B, and by serial numbers. Following is a listing of the serial numbers, type separator, group and test pack number.

<u>Group</u>	<u>Separator Material*</u>	<u>Cell S/N</u>	<u>Test Pack</u>
L	PP-Grace 3073-23	1-7	9L
M	PP-Grace 3073-35	8-14	9M
N	PP-Grace 3074-18	15-17,19-21	9K
O	PP-Grace 1972-31W	22-26,28	9O
P	PP-Grace 3073-32W	29-35	9P
Q	PP-WEX 1242 RAI	36-42	9Q
J	PP-Hercules 2711-55	44-47,49	9J
R	PP-Canadian WEX-ISIS	50-55	9R
F	N-Pellon 2505 (Control)	56-63	9F
S	N-Grace Extracted	64-70	9S

\* PP - Polypropylene  
N - Nylon

Each group had two cells fitted with pressure gauge assemblies prior to testing.

B. The 6.0 ampere-hour cell is rectangular with an average weight and physical dimensions as follows:

<u>Weight (g)</u>	<u>Height (In)</u>	<u>Length (In)</u>	<u>Width (In)</u>
291.0	3.795	.852	2.100

Individual cell measurements are listed in Table 1.

C. The cell containers and covers are made of stainless steel. The positive and negative terminals are insulated from the cell cover by ceramic seals and protrude through the cover as solder-type terminals.

(See Appendix II for detailed cell description.)

III. RESULTS--The following was condensed from Tables I through III.

A. One cell, S/N 46, with Hercules separator material, would not charge. Its internal resistance was 10 milliohms.

B. Three cells, S/N's 8, 10 and 32, initially indicated leaks at the base of their fill tube, but did not indicate leaks after high vacuum or following test.

C. Only two groups of cells (R and F), with PP-Canadian and H-Pellon separator material, completed the initial charge without having any cells removed from charge due to high cell voltage (1.520 volts) or high pressure (100 psia).

D. No group of cells completed the second charge, c/10 for 24 hours, without having any cells removed because of high voltage or pressure.

E. Group R cells, with the PP-Canadian separator material, averaged the highest ampere-hours out (8.3) during the first capacity test, whereas Group O, PP-Grace material, averaged the lowest (5.8). Two cells each, from Groups O and N, did not deliver the rated capacity of 6.0 ampere-hours following this charge.

F. Group F cells, with the H-Pellon material, exhibited the highest average ampere-hours out (7.6) during the second capacity test. Group H cells averaged the lowest, 5.6 ampere-hours, in which five cells did not deliver rated capacity. Two cells each, from Groups L and O, and five cells from Group M did not deliver rated capacity. These groups have the PP-Grace type material.

G. During the charge efficiency test, only one cell each, from Groups R and F, failed to deliver the minimum capacity out requirement of 55 percent of capacity in, whereas Groups O and S had one cell each to pass this requirement.

H. All cells exceeded 1.200 volts at the end of 24 hours, following a 16-hour short period, during the internal short test.

I. The internal resistance of cells S/N 28, of Group 0, was 9.4 milliohms, whereas the resistance of all the other cells was  $4.0 \pm .8$  milliohms.



APPENDIX I

## APPENDIX I

## I. TEST PROCEDURE

## A. Phenolphthalein Leak Tests:

1. This test is a determination of the condition of the welds and ceramic seals on receipt of the cells and following the last discharge of the cells (Cycle #3).

2. The cells were initially checked with a one-half of one percent phenolphthalein solution applied with a cotton swab and then placed in a vacuum chamber and exposed to a vacuum of 40 microns of mercury or less for 24 hours. Upon removal they were rechecked for leaks and then received a final check following test completion. The requirement is no red or pink discoloration which indicates a leak.

## B. Capacity Tests:

1. The capacity test is a determination of the cell's capacity at the  $c/2$  discharge rate to 0.75 volt per cell, where  $C$  is the manufacturer's rated capacity. This type discharge follows all charges of this evaluation test.

2. The charges for the capacity tests are as follows:

a.  $c/20$ , 48 hours, room ambient (RA), Cycle 0, with a test limit of 1.52 volts or pressure of 100 psia.

b.  $c/10$ , 24 hours, RA, Cycle 1, with a test limit of 1.52 volts or 100 psia pressure and a requirement of maximum voltage (1.48) or pressure (65 psia).

## C. Internal Resistance:

1. Measurements are taken across the cell terminals following the discharge of Cycle 2. These measurements were made with a Hewlett-Packard milliohmmeter (Model 4328A).

## D. Internal Short Test:

1. This test is a means of detecting slight shorting conditions which may exist because of imperfections in the insulating materials, or damage to element in handling or assembly.

2. Following completion of the second capacity discharge, the cells are shunted with an 0.5 ohm, 3-watt resistor for 16 hours. At the end of the 16 hours the resistors are removed and the cells stand on open-circuit-voltage (OCV) for 24 hours. A minimum voltage of 1.15 is required at the end of 24 hours.

E. Charge Efficiency Test, 25° C:

1. This test is a measurement of the cells' charge efficiency when charged at a low current rate.

2. The cells are charged at c/40 for 20 hours with a test limit of 1.52 volts or 100 psia pressure. They are then discharged and the requirement is that the minimum capacity out equals 55 percent of capacity in during the preceding charge.

## APPENDIX II

Cell Design  
Eagle-Picher RSN-6 Separator  
Cells

1. Cell Case: The cell case is drawn from 304L stainless steel with a wall thickness of 0.025.
2. Cell Header: The cell cover is fabricated from 304L stainless steel and contains two alumina ceramic seals with nickel iron (alloy 42) stress relief collars. The terminal posts are nickel. The brazing alloy used is silver, copper, indium alloy per MIL-B-15395A. The header assembly has a 0.187 O.D. stainless steel fill tube welded to the cover.
3. Positive plates: Each cell contains ten positive plates. The nominal dimension of the plate, not including the tab, are 2.50 in. high, 1.75 in. wide and 0.025 in. thick. A nickel tab is welded to the plate. Plate edges are coined 0.031 in. The capacity of the positive plate is 0.7 ampere hours.
4. Negative Plates: Each cell contains eleven negative plates. The nominal dimensions of the plate, not including the tab, are 2.50 in. high, 1.75 in. wide and 0.028 in. thick. A nickel tab is spot welded to the plate. Plate edges are coined 0.031 in. The capacity of the negative plate is 1.14 ampere hours.
5. Separators: The separators in the cell are listed in the attached table. The electrode/separator assembly is not insulated from the cell case. A jacket, made of the same material as the cell separator, surrounds the electrode/separator assembly.
6. Electrolyte: The electrolyte used in each cell is 31 percent KOH. Electrolyte adjustments during the manufacturer's processing are shown in the attached table.

SEPARATOR MATERIAL	CELL S/N	SEPARATOR COMMENTS (PAB. & ASS'Y.)	KOH (GMS) RETAINED AFTER ACCELERATION	KOH ADDED PRIOR TO 1ST VENTED CYCLE	1ST VENTED CYCLE CAPACITY (APPROX. MIN.)	KOH ADDED (GMS) AFTER 1ST V CYCLE	2ND VENTED CYCLE CAPACITY (APPROX. MIN.)	KOH ADDED AFTER 2ND V CYCLE (GMS)	3RD VENTED CYCLE CAPACITY (APPROX. MIN.)	KOH ADDED AFTER 3RD VENTED CYCLE (GMS)	SEALED CYCLE CAPACITY (APPROX. MIN.)	FINAL KOH ADDITION (GMS)
POLYPROPYLENE GRACE #3073-23	1		33.9								115	2.5
	2		24.4								115	3.0
	3		22.1								115	3.0
	4		22.2								115	3.5
	5		21.6								115	2.5
	6		23.4								115	2.5
	7		21.1								115	3.5
POLYPROPYLENE GRACE #3073-35	8		20.8								120	3.0
	9		19.9								120	3.5
	10		19.4								120	3.5
	11		20.4								120	3.0
	12		19.0								120	3.5
	13		19.6								120	3.5
	14		20.6								120	3.0
POLYPROPYLENE GRACE #3074-18	15		18.9								90	5.0
	16		17.9								90	3.5
	17		18.9								90	3.0
	18		18.1	+5	50	+4	70		80	+3	90	3.0
	19		19.5								90	5.0
	20		19.1								90	3.0
	21		19.7								90	3.0
POLYPROPYLENE GRACE #1972-31W	22		20.5								120	4.0
	23		21.4								120	3.5
	24		21.4								120	3.5
	25		21.7		75	+6	135		130	+3	120	3.5
	26		22.2								120	3.5
	27		21.5								120	3.5
	28		21.8								120	4.0
POLYPROPYLENE GRACE #3073-32W	29		23.3								118	4.0
	30		23.2								118	4.0
	31		22.8								118	4.5
	32		22.3								118	4.0
	33		23.3								118	4.0
	34		23.8								118	4.0
	35		22.9								118	4.5
HERCULES MICRO FIBER #2711-55	36		19.5								130	4.0
	37		19.7								130	4.0
	38		19.9								130	4.0
	39		18.3		105				145		130	5.0
	40		20.3								130	3.5
	41		19.4								130	4.0
	42		19.1								130	4.0
CARADIAN BATTERY HRC. HEX ISIS (6 Cells Only)	43		26.8								125	0.0
	44		24.8								125	3.0
	45		24.6								125	3.0
	46		30.0		110						125	0.0
	47		26.5								125	1.0
	48		26.8								125	3.0
	49		25.1								125	2.0
PRILON #2303 (6 Cells)	50		19.0								132	3.0
	51		18.2								132	3.5
	52		18.3		130						132	3.5
	53		19.8								132	3.0
	54		19.0								132	3.0
	55		19.1								132	3.0
	56		20.7								130	4.0
GRACE NYLON (EXTRACTED)	57		20.6								130	4.0
	58		20.9								130	4.0
	59		20.0		125						130	4.0
	60		18.8								130	4.0
	61		21.2								130	3.0
	62		19.9								130	4.0
	63		20.0								130	4.0
GRACE NYLON (EXTRACTED)	64		29.6		130						120	3.0
	65		29.6								120	3.0
	66		31.3								120	1.0
	67		29.9								120	3.0
	68		29.7								120	2.0
	69		29.4								120	3.0
	70		29.4								120	3.0

CELL TYPE RSN 6B

SUMMARY OF SEPARATOR MATERIAL COMMENTS AND ABBREVIATED PERFORMANCE DATA

TABLE I

SERIAL NUMBER	WEIGHT (Grams)	HEIGHT (Inches)	LENGTH (Inches)	WIDTH (Inches)	PHENOLPHTHALEIN LEAK TESTS															
					Initial				Following Hi Vac				Following Test Completion							
					Terminals		Fill Tube	Other	Terminals		Fill Tube	Other	Terminals		Fill Tube	Other				
+	-			+	-			+	-											
1	294.3	3.794	.841	2.103																
2	295.7	3.807	.851	2.096																
3	290.6	3.794	.846	2.098																
4	291.3	3.790	.833	2.103																
5	290.5	3.790	.851	2.097																
6	291.6	3.770	.844	2.095																
7	292.4	3.813	.854	2.096																
8	292.1	3.790	.851	2.097																
9	292.5	3.792	.855	2.107																
10	290.4	3.765	.861	2.104																
11	292.6	3.815	.855	2.104																
12	289.7	3.804	.835	2.094																
13	293.8	3.804	.827	2.095																
14	291.9	3.785	.854	2.100																
15	288.9	3.766	.855	2.102																
16	290.4	3.804	.852	2.095																
17	287.4	3.785	.840	2.105																
19	289.3	3.811	.842	2.096																
20	287.1	3.814	.834	2.095																
21	289.9	3.807	.828	2.106																
22	295.3	3.801	.857	2.103																
23	294.9	3.790	.857	2.104																
24	292.9	3.804	.846	2.096																
25	290.6	3.813	.844	2.099																
26	292.8	3.808	.854	2.097																
28	295.1	3.797	.866	2.102																

10

↑

No Leaks

No Leaks

✓

✓

↓

↓

MOEC/C 75-32

TABLE I

SERIAL NUMBER	WEIGHT (Grams)	HEIGHT (Inches)	LENGTH (Inches)	WIDTH (Inches)	PHENOLPHTHALEIN LEAK TESTS															
					Initial				Following H1 Vac				Following Test Completion							
					Terminals		Fill Tube	Other	Terminals		Fill Tube	Other	Terminals		Fill Tube	Other				
					+	-			+	-			+	-						
29	290.5	3.800	.852	2.103																
30	290.1	3.788	.856	2.104																
31	289.1	3.809	.864	2.097																
32	290.9	3.795	.846	2.107																
33	288.9	3.786	.839	2.100																
34	289.4	3.817	.837	2.097																
35	290.7	3.792	.866	2.108																
36	286.0	3.768	.852	2.099																
37	289.7	3.778	.841	2.096																
38	291.9	3.792	.868	2.097																
39	290.9	3.785	.852	2.106																
40	292.3	3.787	.859	2.098																
41	290.2	3.790	.843	2.097																
42	292.6	3.785	.859	2.106																
44	294.8	3.790	.861	2.097																
45	290.3	3.805	.845	2.100																
46	289.7	3.802	.867	2.104																
47	294.7	3.808	.857	2.103																
49	293.7	3.797	.851	2.097																
50	286.0	3.806	.836	2.092																
51	286.9	3.792	.856	2.096																
52	283.9	3.806	.853	2.096																
53	286.7	3.795	.852	2.092																
54	287.4	3.790	.861	2.102																
55	284.9	3.768	.852	2.092																

11





ORIGINAL PAGE IS  
OF POOR QUALITY

TABLE II  
CAPACITY AND CHARGE EFFICIENCY DATA

SERIAL NUMBER	CAPACITY TEST 1						CAPACITY TEST 2						CHARGE EFFICIENCY					
	END-OF-CHARGE			END-OF-DISCHARGE			END-OF-CHARGE			END-OF-DISCHARGE			END-OF-CHARGE			END-OF-DISCHARGE		
	CELL (Volts)	AUX ELECT (Volts)	PRESS (PSIA)	CAPACITY (ah)	AUX ELECT (Volts)	PRESS (PSIA)	CELL (Volts)	AUX ELECT (Volts)	PRESS (PSIA)	CAPACITY (ah)	AUX ELECT (Volts)	PRESS (PSIA)	CELL (Volts)	AUX ELECT (Volts)	PRESS (PSIA)	CAPACITY (ah)	AUX ELECT (Volts)	PRESS (PSIA)
1	10.8*	N/A	37	7.1	N/A	25	10.5*	N/A	96	6.2	N/A	77	1.371	N/A	50	1.25	N/A	50
2	11.7*			7.1			11.2*			6.7			1.370			1.20		
3	11.1*		45	6.6		22	10.8*		77	6.7		61	1.370		37	1.25		36
4	11.5*			7.2			10.9*			6.7			1.371			1.25		
5	11.1*			6.9			9.1*			5.1			1.372			1.25		
6	10.3*			6.9			9.2*			6.0			1.372			1.25		
7	10.4*			6.5			9.0*			5.8			1.373			1.30		
8	10.2*			7.2			9.0*			5.8			1.370			1.46		
9	10.3*		41	7.1		19	9.0*		59	5.6		32	1.369		24	1.46		24
10	10.4*			6.8			9.3*			6.0			1.369			1.40		
11	10.6*			7.1			9.3*			5.6			1.368			1.40		
12	11.1*		43	7.5		23	9.7*		70	5.8		56	1.368		34	1.40		34
13	10.8*			7.4			9.4*			5.7			1.369			1.40		
14	10.5*			7.1			9.3*			5.7			1.371			1.46		
15	1.489		33	6.1		33	1.519/137		100	5.5		37	1.364		22	1.35		21
16	1.504			4.8			11.2*			5.8			1.367			1.37		
17	1.500		46	5.8		38	1.507/114		100	5.8		80	1.364		56	1.44		55
19	12.1*			6.7			10.5*			6.0			1.368			1.49		
20	1.472			5.8			1.505			5.2			1.366			1.37		
21	12.0*			6.8			1.518			5.4			1.364			1.44		
22	13.0*		77	5.7			1.519/99		100	5.7		57	1.373		41	1.58		41
23	1.508			6.5			10.9*			6.5			1.371			1.69		
24	1.459		80	6.1			1.477/10.7		100	6.1		46	1.371		32	1.53		31
25	1.464			6.1			12.9*			6.1			1.371			1.53		
26	1.494			6.1			11.1*			6.1			1.372			1.58		
28	11.7*			4.1			8.2*			4.1			1.381			1.53		

9ND-RADC (SP 11/73) \* Cells removed from charge due to high voltage (1.52 volts), value indicates AH input when removed.  
 □ - Only 2 cells in each group have pressure gauges. \*\* - Removed from charge due to high pressure.

ORIGINAL PAGE IS  
OF POOR QUALITY

TABLE II  
CAPACITY AND CHARGE EFFICIENCY DATA

SERIAL NUMBER	CAPACITY TEST 1						CAPACITY TEST 2						CHARGE EFFICIENCY					
	END-OF-CHARGE			END-OF-DISCHARGE			END-OF-CHARGE			END-OF-DISCHARGE			END-OF-CHARGE			END-OF-DISCHARGE		
	CELL (Volts)	AUX ELECT (Volts)	PRESS (PSIA)	CAPACITY (ah)	AUX ELECT (Volts)	PRESS (PSIA)	CELL (Volts)	AUX ELECT (Volts)	PRESS (PSIA)	CAPACITY (ah)	AUX ELECT (Volts)	PRESS (PSIA)	CELL (Volts)	AUX ELECT (Volts)	PRESS (PSIA)	CAPACITY (ah)	AUX ELECT (Volts)	PRESS (PSIA)
29	13.1*	N/A	31	7.5	N/A	19	11.0*	N/A	61	6.8	N/A	37	1.369	N/A	32	1.51	N/A	31
30	1.455			7.5			1.451			7.5			1.371			1.45		
31	1.450		31	7.3		23	11.5*		55	6.6		31	1.371		26	1.45		25
32	1.469			7.6			1.452			7.3			1.371			1.45		
33	1.495			7.9			1.458			7.5			1.370			1.51		
34	1.447			7.0			1.437			7.0			1.371			1.43		
35	1.478			7.6			10.8*			6.8			1.372			1.57		
36	1.464		23	7.7		15	1.472		40	7.3		28	1.370		28	1.51		27
37	12.0*			7.8			10.0*			7.1			1.372			1.58		
38	1.461		27	7.6		21	1.450		36	7.3		27	1.371		23	1.51		23
39	1.510			8.0			11.1*			7.0			1.371			1.58		
40	1.456			8.0			1.454			7.5			1.371			1.58		
41	1.514			8.1			1.498			7.7			1.371			1.55		
42	1.464			7.8			1.451			7.5			1.370			1.51		
44	12.2*		42	7.8			9.8*		58	6.9		35	1.372		20	1.52		19
45	11.6*			7.4			9.5*			6.3			1.372			1.42		
46	N/A		N/A	N/A		N/A	N/A		N/A	N/A		N/A	N/A		N/A	N/A		N/A
47	11.7*			6.8			9.5*			6.3			1.374			1.42		
49	1.488			7.7			11.0*			6.8			1.372			1.47		
50	1.457		23	8.4			11.8*		48	7.1		23	1.376		34	1.72		33
51	1.441			8.3			1.468			7.6			1.375			1.65		
52	1.438		21	8.3			1.480		31	7.6		23	1.375		25	1.68		25
53	1.443			8.2			1.473			7.6			1.375			1.70		
54	1.438			8.2			1.454			7.5			1.375			1.65		
55	1.445			8.2			1.474			7.5			1.376			1.61		

\* - Cells Removed from charge due to High Voltage (1.52 volts), value indicates AH input when removed  
 □ - Only 2 cells in each group have pressure gauges. N/A - Not applicable

TABLE II  
CAPACITY AND CHARGE EFFICIENCY DATA

SERIAL NUMBER	CAPACITY TEST 1						CAPACITY TEST 2						CHARGE EFFICIENCY					
	END-OF-CHARGE			END-OF-DISCHARGE			END-OF-CHARGE			END-OF-DISCHARGE			END-OF-CHARGE			END-OF-DISCHARGE		
	CELL (Volts)	AUX ELECT (Volts)	PRESS (PSIA)	CAPACITY (ah)	AUX ELECT (Volts)	PRESS (PSIA)	CELL (Volts)	AUX ELECT (Volts)	PRESS (PSIA)	CAPACITY (ah)	AUX ELECT (Volts)	PRESS (PSIA)	CELL (Volts)	AUX ELECT (Volts)	PRESS (PSIA)	CAPACITY (ah)	AUX ELECT (Volts)	PRESS (PSIA)
56	1.481	N/A	22	8.1	N/A	17	11.4 *	N/A	26	7.5	N/A	21	1.373	N/A	21	1.82	N/A	21
57	1.459			8.1			1.468			7.4			1.373			1.71		
58	1.500		25	8.1		19	10.7 *		33	7.7		21	1.375		17	1.85		17
59	1.463			8.2			1.498			7.7			1.374			1.71		
60	1.517			8.4			10.5 *			7.8			1.373			1.85		
61	1.465			8.0			1.469			7.3			1.373			1.61		
62	1.498			8.1			11.0 *			7.7			1.373			1.85		
63	1.478			8.1			11.4 *			7.8			1.373			1.85		
64	11.9 *		65	7.1		34	10.1 *		55	6.7		43	1.373		33	1.75		35
65	1.447			7.1			1.446			6.7			1.375			1.47		
66	1.471		26	7.5		21	1.504		38	7.5		27	1.373		25	1.52		27
67	1.455			7.1			1.464			7.0			1.375			1.47		
68	1.463			7.2			1.501			7.1			1.375			1.52		
69	1.464			7.1			1.491			6.9			1.373			1.52		
70	1.490			7.2			10.9 *			6.6			1.375			1.52		
	* - Cells Removed. Seam change due to High Voltage (6.2 volts), value indicates attempt when removed.																	
	□ - Only 2 cells in each group have pressure gauges. N/A - not applicable.																	

Group F

Group S

TABLE III  
INTERNAL RESISTANCE AND SHORT TEST DATA

9ND-NADC (SP 11/73)

SERIAL NUMBER	INTERNAL RESISTANCE (MILLIOHMS)			INTERNAL SHORT TEST		
	END-OF-CHARGE	ONE HOUR AFTER START-OF-DISCHARGE	TWO HOURS AFTER START-OF-DISCHARGE *	AFTER 16 HR SHORT	AFTER 24 HOUR OCV STAND	
				CELL	CELL	PRESS <sup>□</sup>
1	N/A	N/A	3.9	.031	1.213	45
2			4.2	.032	1.214	
3			4.0	.034	1.206	16
4			4.4	.028	1.232	
5			4.3	.034	1.214	
6			4.6	.040	1.222	
7			4.6	.061	1.227	
8			4.2	.029	1.214	
9			3.9	.010	1.232	14
10			4.2	.022	1.203	
11			3.9	.027	1.211	
12			4.0	.028	1.207	30
13			4.0	.028	1.210	
14			4.6	.024	1.212	
15			4.3	.024	1.240	14
16			4.0	.003	1.229	
17			4.0	.027	1.238	51
19			3.9	.025	1.239	
20			4.5	.058	1.238	
21			4.0	.038	1.240	
22			4.5	.027	1.245	33
23			4.0	.085	1.253	
24			4.2	.095	1.238	21
25			4.5	.044	1.253	
26			4.3	.086	1.257	
28			9.4	.031	1.249	
29			4.4	.030	1.248	29
30			4.4	.040	1.240	
31			4.4	.047	1.250	21
32			4.4	.047	1.260	
33			4.1	.026	1.248	
34			4.4	.046	1.243	
35			4.3	.055	1.252	
* - Following discharge						
N/A - not applicable      □ - Only 2 cells in each group w/gauges						

TABLE III  
INTERNAL RESISTANCE AND SHORT TEST DATA

9ND-NADC (SP 11/73)

SERIAL NUMBER	INTERNAL RESISTANCE (MILLIOHMS)			INTERNAL SHORT TEST		
	END-OF-CHARGE	ONE HOUR AFTER START-OF-DISCHARGE	TWO HOURS AFTER START-OF-DISCHARGE *	AFTER 16 HR SHORT	AFTER 24 HOUR OCV STAND	
				CELL	CELL	PRESS <sup>□</sup>
36	N/A	N/A	4.3	.037	1.246	20
37			3.9	.018	1.246	
38			4.2	.050	1.256	17
39			4.2	.047	1.247	
40			4.4	.030	1.247	
41			4.7	.032	1.244	
42			4.7	.038	1.249	
44			4.7	.032	1.238	17
45			4.7	.037	1.237	
46			10.0 **	N/A	N/A	
47			4.6	.041	1.221	
49			4.8	.040	1.237	
50			3.5	.038	1.251	32
51			3.6	.029	1.250	
52			3.4	.033	1.248	21
53			3.5	.021	1.249	
54			3.6	.040	1.252	
55			3.6	.036	1.254	
56			3.7	.058	1.258	19
57			4.0	.049	1.254	
58			3.9	.051	1.255	17
59			3.9	.048	1.253	
60			3.9	.051	1.253	
61			4.1	.050	1.257	
62			4.2	.052	1.257	
63			4.0	.050	1.256	
64			3.6	.043	1.254	33
65			3.8	.045	1.261	
66			4.0	.039	1.251	26
67			3.9	.042	1.256	
68			4.0	.040	1.251	
69			3.9	.054	1.256	
70			4.0	.051	1.257	
	* -	Following discharge	** -	Beginning of Test		
	N/A -	Not Applicable	□ -	Only 2 cells in each group w/gauges		

## DISTRIBUTION LIST

National Aeronautics and Space Administration, Goddard Space Flight Center (Code 711.2, Mr. T. J. Hennigan), Greenbelt, Maryland 20771 (12 copies)

National Aeronautics and Space Administration (Code RPP, Mr. Ernst M. Cohn), Washington, D. C. 20546

National Aeronautics and Space Administration (Code ES, Mr. Simon Manson), Washington, D. C. 20546

National Aeronautics and Space Administration, Scientific and Technical Information Center; Input, P. O. Box 33, College Park, Maryland 20740 (3 copies)

National Aeronautics and Space Administration (Code KT, Dr. E. N. Case), Washington, D. C. 20546

National Aeronautics and Space Administration (Code RF, Mr. R. D. Ginter), Washington, D. C. 20546

National Aeronautics and Space Administration, Goddard Space Flight Center (Code 711.2, Mr. Gerald Halpert), Greenbelt, Maryland 20771

National Aeronautics and Space Administration, Goddard Space Flight Center (Code 711.2, Mr. William Webster), Greenbelt, Maryland 20771

National Aeronautics and Space Administration, Goddard Space Flight Center (Code 711.2, Mr. Floyd Ford), Greenbelt, Maryland 20771

National Aeronautics and Space Administration, Goddard Space Flight Center (Code 251.2, Ms. Virginia Kendall), Greenbelt, Maryland 20771

National Aeronautics and Space Administration, Langley Research Center (MS-488, Mr. James Bene), Hampton, Virginia 23365

National Aeronautics and Space Administration, Lewis Research Center (MS 309-1, Mr. John Bozek), 21000 Brookpark Road, Cleveland, Ohio 44135

National Aeronautics and Space Administration, Lewis Research Center (MS 302-1, Dr. Louis Rosenblum), 21000 Brookpark Road, Cleveland, Ohio 44135

National Aeronautics and Space Administration, Lewis Research Center (MS 309-1, Mr. Harvey Schwartz), 21000 Brookpark Road, Cleveland, Ohio 44135

National Aeronautics and Space Administration, Lewis Research Center (MS 309-1, Dr. J. Stuart Fordyce), 21000 Brookpark Road, Cleveland, Ohio 44135

National Aeronautics and Space Administration, George C. Marshall Space Flight Center (EC-11, Mr. Charles B. Graff), Huntsville, Alabama 35812

National Aeronautics and Space Administration, Johnson Space Center (EP-5, Mr. Barry Trout), Houston, Texas 77058

National Aeronautics and Space Administration, Ames Research Center (M.S. 244-8, Mr. Jon A. Rubenzer), Moffett Field, California 94035

Jet Propulsion Laboratory (M.S. 198-220, Mr. Daniel Runkle), 4800 Oak Grove Drive, Pasadena, California 91103

Jet Propulsion Laboratory (M.S. 198-220, Mr. Aiji Uchiyama), 4800 Oak Grove Drive, Pasadena, California 91103

Jet Propulsion Laboratory (M.S. 198-220, Dr. R. Lutwack), 4800 Oak Grove Drive, Pasadena, California 91103

Jet Propulsion Laboratory (M.S. 198-220, Mr. Sam Bogner), 4800 Oak Grove Drive, Pasadena, California 91103

Commanding General, U. S. Army Electro Technology Lab, Energy Conversion Research Division (MERDC/STSTFB-EE, Dr. James R. Huff), Fort Belvoir, Virginia 22060

Commanding General, Picatinny Arsenal (Engineering Science, Div. 350, Mr. Max R. Merriman), Dover, New Jersey 07801

Commanding General, U. S. Army Electronics Command (AMSEL-TL-P), Fort Monmouth, New Jersey 07703

Commanding General, U. S. Army Electronics Command (AMSEL-MA-DM, Mr. A. Frink), Fort Monmouth, New Jersey 07703

Officer-In-Charge, Warrenton Training Center (Mr. Stanley Kazen), Box 700, Warrenton, Virginia 22186

Harry Diamond Laboratories, Room 300, Building 92 (Branch 910, Mr. Nathan Kaplan), Connecticut Ave. & Van Ness Street, N.W., Washington, D. C. 20438

National Bureau of Standards (272.0, Mr. Ramon Jesch), Boulder, Colorado 80302

Chief of Naval Research (Code 473, Director, Power Program), Department of the Navy, Arlington, Virginia 22217

Chief of Naval Research (Code 472, Dr. George A. Neece), Department of the Navy, 800 N. Quincy Street, Arlington, Virginia 22217

Director, Naval Research Laboratory (Code 6160, Mr. A. C. Simon), 4555 Overlook Avenue, S. W., Washington, D. C. 20375

Director, Naval Research Laboratory (Code 6160, Mr. S. Schuldiner), 4555 Overlook Avenue, S.W., Washington, D. C. 20375

Director, Naval Research Laboratory (Code 7045, Mr. Fred Betz), 4555 Overlook Avenue, S.W., Washington, D. C. 20375

Officer In Charge, Annapolis Division, Naval Ship Research & Development Center (Code 2724, Mr. J. A. Woerner), Annapolis, Maryland 21402

Commander, Naval Air Systems Command (AIR-53643, Mr. E. Wright), Department of the Navy, Washington, D. C. 20360

Commander, Naval Ordnance Laboratory, White Oak (Dr. A. Hellfritzsch), Silver Spring, Maryland 20910

Commander, Mare Island Naval Shipyard (Code 134.7, Mr. Donald O. Newton, Chemical Laboratory), Vallejo, California 94592

Commander, Naval Ship Engineering Center (Code 6157D, Mr. Albert Himy), Center Building, Prince George Center, Hyattsville, Maryland 20782

Superintendent, Naval Observatory (NISC, Mr. E. H. Fuskie), 4301 Suitland Road, Suitland, Maryland 20390

Commander, Naval Sea Systems Command (Code 03523, Mr. Bernard B. Rosenbaum), Department of the Navy, Washington, D. C. 20360

Commander, AFAPL (POE-1, Dr. D. Pickett), Wright-Patterson Air Force Base, Ohio 45433

Commander, AFAPL (POE-1, Mr. R. L. Kerr), Wright-Patterson Air Force Base, Ohio 45433

Rome Air Development Center (Code TUGG, Mr. Frank J. Mollura), Griffiss Air Force Base, New York 13441

Headquarters, SAMSO (SMTAE, Lt. R. Ballard), Los Angeles Air Force Station, Los Angeles, California 90045



Commander, SAMSO/DYE, P. O. Box 92960, Worldway Postal Center,  
Los Angeles, California 90009

Defence Research Establishment, Power Sources Division  
(Dr. Joseph Lackner), Shirley Bay, Ottawa, Ontario, Canada

Aerospace Corporation (Library Acquisition Group), P. O. Box 95085,  
Los Angeles, California 90045

Aerospace Corporation (Mr. Larry Gibson), P. O. Box 95085,  
Los Angeles, California 90045

American University, Chemistry Department (Dr. R. T. Foley),  
Massachusetts & Nebraska Avenues, N. W., Washington, D. C. 20016

Artech, Inc. (Dr. Frank Swindells), 2816 Fallfax Drive,  
Falls Church, Virginia 22042

Battelle Memorial Institute (Mr. Paul W. Cover), 505 King Avenue,  
Columbus, Ohio 43201

Bell Telephone Labs, Inc. (Mr. D. O. Feder), Murray Hill,  
New Jersey 07974

Bell Telephone Laboratories (Mr. R. L. Beauchamp), Murray Hill,  
New Jersey 07974

The Boeing Company (MS BE-37, Mr. Sidney Gross), P. O. Box 3999,  
Seattle, Washington 98124

Burgess Battery Division, Gould, Inc. (Mr. M. E. Wilke, Chief  
Engineer), Freeport, Illinois 61032

C & D Batteries, Division of Eltra Corporation (Mr. A. Howard),  
3043 Walton Road, Plymouth Meeting, Pennsylvania 19462

Calvin College (Prof. T. P. Dirkse), 3175 Burton Street, S. E.,  
Grand Rapids, Michigan 49506

Catalyst Research Corporation (Mr. F. Tepper), 1421 Clarkview Road,  
Baltimore, Maryland 21209

Cermaseal, Inc. (Mr. Robert Turner), New Lebanon Center,  
New York 12126

Chrysler Corporation, Space Division (Mr. C. E. Thomas),  
P. O. Box 29200, New Orleans, Louisiana 70129

Comsat Laboratories (Mr. James Dunlop), P. O. Box 115, Clarksburg,  
Maryland 20734

Cryptanalytic Computer Sci. Inc., 499 Cooper Landing Road,  
Cherry Hill, New Jersey 08034

Cubic Corporation (Librarian), 9233 Balboa Avenue, San Diego,  
California 92123

Delco-Remy Division, General Motors Corporation (Mr. J. A. Keralla),  
2401 Columbus Avenue, Anderson, Indiana 46011

Eagle-Picher Industries, Inc., Couples Department (Mr. E. P.  
Broglio), P. O. Box 47, Joplin, Missouri 64801

Eagle-Picher Industries, Inc., Electronics Division (Mr. William  
Harsch), Couples Department, P. O. Box 47, Joplin, Missouri 64801

E. I. du Pont DeNemours & Company, Engineering Materials Laboratory,  
Experimental Station, Bldg 304 (Dr. K. B. Keating), Wilmington,  
Delaware 19898

ESB, Inc., Carl F. Norberg Research Center (Dr. A. J. Salkind),  
19 West College Avenue, Yardley, Pennsylvania 19067

Energy Research Corporation (Mr. Martin Klein), 15 Durant Avenue,  
Bethel, Connecticut 06801

Exxon Research & Engineering Company (Mr. Robert P. Hamlen),  
P. O. Box 45, Bldg. 25, Linden, New Jersey 07036

Dr. Arthur Fleischer, 466 South Center Street, Orange,  
New Jersey 07050

General Dynamics/Convair (Dept. 623-2, Mr. R. P. Mikkelson),  
P. O. Box 80847, San Diego, California 92138

General Electric Company, Research and Development Laboratory  
(Dr. F. Will), P. O. Box 43, Schenectady, New York 12301

General Electric Company, Missile and Space Division (Mr. H.  
Thierfelder), P. O. Box 8555, Philadelphia, Pennsylvania 19101

General Electric Company, Missile and Space Division (Mr. Aaron Kirpich, Room M-2614), P. O. Box 8555, Philadelphia, Pennsylvania 19101

General Electric Company, Battery Business Section (Mr. P. R. Voyentzie), P. O. Box 114, Gainesville, Florida 32601

General Electric Company (Mr. Guy Rampel), P. O. Box 114, Gainesville, Florida 32601

General Electric Company (Mr. David F. Schmidt), 777 Leesburg Pike, Falls Church, Virginia 22043

General Electric Company (Whitney Library), P. O. Box 8, Schenectady, New York 12301

Globe-Union, Inc. (Dr. R. Goodman), 5757 N. Green Bay Avenue, Milwaukee, Wisconsin 53201

Gould Ionics, Inc. (Dr. B. B. Owens), P. O. Box 3140, St. Paul, Minnesota 55165

Gould, Inc. (Lab Director), P. O. Box 3140, St. Paul, Minnesota 55165

Grumman Aerospace Corporation (Plant 35, Dept 533, Mr. Steve J. Gaston), Bethpage, Long Island, New York 11714

Gulton Industries, Battery & Power Sources Division, 212 Durham Avenue, Metuchen, New Jersey 08840

Heliotek (Dr. Harvey N. Seiger), 12500 Gladstone Avenue, Sylmar, California 91342

Honeywell, Inc., Livingston Electronic Laboratory (Librarian), Montgomeryville, Pennsylvania 18936

P. L. Howard Associates, Inc. (Dr. Paul L. Howard), Millington, Maryland 21651

Hughes Aircraft Corporation, Commercial Systems Division (M. S. 9515, Bldg. 373, Mr. Robert A. Steinhauer), P. O. Box 92919, Los Angeles, California 90009

Idaho State University, Department of Chemistry (Dr. G. Myron Arcand), Pocatello, Idaho 83201

University of Illinois (306E Talbot Laboratory, Prof. Will J. Worley), Urbana, Illinois 61801

Institute for Defense Analyses (Mr. R. Hamilton), 400 Army-Navy Drive, Arlington, Virginia 22202

International Nickel Company (Mr. N. A. Matthews), 1000-16th Street, N.W., Washington, D. C. 20036

Invention Talents, Inc. (Dr. John McCallum), 1149 Chesapeake Avenue, Columbus, Ohio 24312

Johns Hopkins University, Applied Physics Laboratory (Mr. Richard C. Evans), 8621 Georgia Avenue, Silver Spring, Maryland 20910

Mr. E. Kantner, 13 Stephens Drive, E. Brunswick, New Jersey 08816

Kendall Fiber Products Company (Mr. G. C. Anderson), Walpole, Massachusetts 02081

Arthur D. Little, Inc. (Dr. James D. Birkett), Acorn Park, Cambridge, Massachusetts 02140

Life Systems, Inc. (Dr. Richard A. Wynveen, Pres.), 23715 Mercantile Road, Cleveland, Ohio 44122

Lockheed Missiles & Space Company (Bldg. 151, Dept 62-25, Mr. Robert E. Corbett), P. O. Box 504, Sunnyvale, California 94088

Lockheed Missiles & Space Company (Bldg. 151, Dept 62-25, Mr. M. G. Gandel), P. O. Box 504, Sunnyvale, California 94088

Mallory Battery Company (Mr. S. J. Angelovich, Director of Engineering, So. Broadway, Tarrytown, New York 10591

P. R. Mallory and Co., Inc. (Dr. Per Bro), Northwest Industrial Park, Burlington, Massachusetts 01801

P. R. Mallory and Co., Inc. (Library), P. O. Box 706, Indianapolis, Indiana 46206

Marathon Battery Company (Mr. Lou Belove), P. O. Box 8233, Waco, Texas 76710

Martin-Marietta Corporation (M.S. C8801, Mr. M. S. Imamura), P. O. Box 179, Denver, Colorado 80201

Martin-Marietta Corporation (M.S. 0455, Mr. John Sanders), P. O. Box 179, Denver, Colorado 80201

Martin-Marietta Corporation (M.S. 0455, Mr. Charles Bolton), P. O. Box 179, Denver, Colorado 80201

Maryland University, Department of Mechanical Engineering (Dr. Frederick Morse), College Park, Maryland 20742

McDonnell Douglas Astronautics Company (Bldg 13-3, Mr. A. D. Tonelli), 5301 Bolsa Avenue, Huntington Beach, California 92647

Motorola, Inc. (Dr. Robert C. Shair), 8000 West Sunrise Boulevard, Ft. Lauderdale, Florida 33313

National Science Foundation, Rann Program (Dr. Leonard Topper), Washington, D. C. 20550

National Center for Energy Management and Power, 113 Town Building, University of Pennsylvania, Philadelphia, Pennsylvania 19104

Philco-Ford Corporation, Power and Control Engineering Department (M.S. R-26, Mr. D. C. Briggs), 3939 Fabian Way, Palo Alto, California 94303

Power Information Center, University City Science Institute, Room 2210, 3401 Market Street, Philadelphia, Pennsylvania 19104

RAI Research Corporation, 225 Marcus Boulevard, Hauppauge, New York 11787

Rockwell International, Autonetics Division (Mr. R. F. Fogle), P. O. Box 4192, GF 40, 3370 Miraloma Avenue, Anaheim, California 92803

Rockwell International, Atomic International Division (Mr. H. L. Recht), 8900 DeSota Avenue, Canoga Park, California 91304

RCA, Astro Electronics Division (Mr. Joel Bacher), P. O. Box 800, Princeton, New Jersey 08540

SAFT Corporation of America (Mr. D. Verrier), 50 Rockefeller Plaza, New York, New York 10020

Standard Scientific Systems (Mr. M. J. Milden), 703A Arroyo Street, Sylmar, California 91340

Southwest Research Institute (Library), P. O. Drawer 28510, San Antonio, Texas 78228

Stanford Research Institute (Library), 333 Ravenswood Avenue,  
Menlo Park, California 94025

TRW Systems, Inc. (Dr. Willard R. Scott, M-1/1208), One Space Park,  
Redondo Beach, California 90278

TRW Systems, Inc. (Dr. Herbert P. Silverman, R-1/2094), One Space  
Park, Redondo Beach, California 90278

TRW, Inc. (Librarian, TIM 3417), 23555 Euclid Avenue, Cleveland,  
Ohio 44117

Unican Security Systems Ltd. (Dr. Carl Berger), 5795 De Gaspe Avenue,  
Montreal H25 2X3, Quebec, Canada

Union Carbide Corporation, Consumer Products Division, (Dr. Ralph  
Brodd), P. O. Box 6116, Cleveland, Ohio 44101

Union Carbide Corporation, Development Laboratory (Mr. C. M. Foecking),  
P. O. Box 6056, Cleveland, Ohio 44101

Union Carbide Corporation, Battery Products Division (Dr. Robert  
Powers), P. O. Box 6116, Cleveland, Ohio 44101

Utah Research and Development Co., Inc. (Mr. William Boyd),  
1820 South Industrial Road, Salt Lake City, Utah 84104

United Aircraft Corporation (Library), 400 Main Street, East Hartford,  
Connecticut 06108

Director (Dr. E. Y. Weissman), Inorganic-Electrolytic R&D,  
Wyandotte Corporation, Wyandotte, Michigan 48192

Yardney Electric Corporation, Power Sources Division (Mr. J. E. Smith),  
3850 Olive Street, Denver, Colorado 80207

Yardney Electric Corporation (Mr. William Ryder), 82 Mechanic Street,  
Pawcatuck, Connecticut 02891

Mr. Robert H. Park, Main Street, Brewster, Massachusetts 02631