

Temperature insensitive hysteresis free highly sensitive polymer optical fiber Bragg grating humidity sensor - DTU Orbit (08/11/2017)

Temperature insensitive hysteresis free highly sensitive polymer optical fiber Bragg grating humidity sensor

The effect of humidity on annealing of poly (methyl methacrylate) (PMMA) based microstructured polymer optical fiber Bragg gratings (mPOFBGs) and the resulting humidity responsivity are investigated. Typically annealing of PMMA POFs is done in an oven without humidity control around 80°C and therefore at low humidity. We demonstrate that annealing at high humidity and high temperature improves the performances of mPOFBGs in terms of stability and sensitivity to humidity. PMMA POFBGs that are not annealed or annealed at low humidity level will have a low and highly temperature dependent sensitivity and a high hysteresis in the humidity response, in particular when operated at high temperature. PMMA mPOFBGs annealed at high humidity show higher and more linear humidity sensitivity with negligible hysteresis. We also report how annealing at high humidity can blue-shift the FBG wavelength more than 230 nm without loss in the grating strength

General information

State: Published

Organisations: Department of Photonics Engineering, Fiber Sensors and Supercontinuum Generation

Authors: Woyessa, G. (Intern), Nielsen, K. (Intern), Stefani, A. (Intern), Markos, C. (Intern), Bang, O. (Intern)

Pages: 1206-1213

Publication date: 2016

Main Research Area: Technical/natural sciences

Publication information

Journal: Optics Express

Volume: 24

Issue number: 2

ISSN (Print): 1094-4087

Ratings:

BFI (2017): BFI-level 2

Web of Science (2017): Indexed yes

BFI (2016): BFI-level 2

Scopus rating (2016): CiteScore 3.48 SJR 1.487 SNIP 1.589

Web of Science (2016): Indexed yes

BFI (2015): BFI-level 2

Scopus rating (2015): SJR 1.976 SNIP 1.755 CiteScore 3.78

Web of Science (2015): Indexed yes

BFI (2014): BFI-level 2

Scopus rating (2014): SJR 2.349 SNIP 2.166 CiteScore 4.18

Web of Science (2014): Indexed yes

BFI (2013): BFI-level 2

Scopus rating (2013): SJR 2.358 SNIP 2.226 CiteScore 4.38

ISI indexed (2013): ISI indexed yes

Web of Science (2013): Indexed yes

BFI (2012): BFI-level 2

Scopus rating (2012): SJR 2.587 SNIP 2.145 CiteScore 3.85

ISI indexed (2012): ISI indexed yes

Web of Science (2012): Indexed yes

BFI (2011): BFI-level 2

Scopus rating (2011): SJR 2.579 SNIP 2.606 CiteScore 4.04

ISI indexed (2011): ISI indexed yes

Web of Science (2011): Indexed yes

BFI (2010): BFI-level 2

Scopus rating (2010): SJR 2.943 SNIP 2.466

Web of Science (2010): Indexed yes

BFI (2009): BFI-level 2

Scopus rating (2009): SJR 3.092 SNIP 2.669

Web of Science (2009): Indexed yes

BFI (2008): BFI-level 2

Scopus rating (2008): SJR 3.195 SNIP 2.393

Web of Science (2008): Indexed yes
Scopus rating (2007): SJR 3.27 SNIP 2.032
Web of Science (2007): Indexed yes
Scopus rating (2006): SJR 3.233 SNIP 2.326
Web of Science (2006): Indexed yes
Scopus rating (2005): SJR 3.334 SNIP 2.379
Web of Science (2005): Indexed yes
Scopus rating (2004): SJR 2.833 SNIP 2.499
Web of Science (2004): Indexed yes
Scopus rating (2003): SJR 2.688 SNIP 2.193
Web of Science (2003): Indexed yes
Scopus rating (2002): SJR 1.547 SNIP 1.673
Web of Science (2002): Indexed yes
Scopus rating (2001): SJR 1.442 SNIP 1.39
Web of Science (2001): Indexed yes
Scopus rating (2000): SJR 1.246 SNIP 0.714
Web of Science (2000): Indexed yes
Scopus rating (1999): SJR 1.381 SNIP 0.838

Original language: English

Electronic versions:

Temperature_insensitive_hysteresis_free_highly_sensitive_polymer_optical_fiber_Bragg_gating_humidity_sensor.pdf
DOIs:

10.1364/OE.24.001206

Source: PublicationPreSubmission

Source-ID: 120985233

Publication: Research - peer-review › Journal article – Annual report year: 2016