

promoting access to White Rose research papers



Universities of Leeds, Sheffield and York
<http://eprints.whiterose.ac.uk/>

White Rose Research Online URL for this paper:

<http://eprints.whiterose.ac.uk/8578/>

Conference paper

Mara, D.D. (2008) *Sanitation options in rural and urban areas: best practices*. In: Aquatech Amsterdam 2008: International Conference on the Millennium Development Goals on Sanitation, 30th Sept - 1st October 2008, Amsterdam.

Sanitation Options in Rural and Urban Areas: Best Practices

D. D. Mara

School of Civil Engineering, University of Leeds, Leeds LS2 9JT, Leeds, UK
(E-mail: d.d.mara@leeds.ac.uk)

Abstract

Suitable low-cost sanitation systems for use in poor rural and urban areas are described. For dispersed rural areas Arborloos generally represent the 'best' choice. As the density increases other options may be used, including alternating twin-pit or twin-vault systems providing they can be desludged by the users. In poor urban areas the choice is normally between simplified sewerage, low-cost combined sewerage and community-managed sanitation blocks.

Keywords

Arborloos; biogas toilets; simplified sewerage; low-cost combined sewerage; community-managed sanitation blocks

INTRODUCTION

In 2004 there were around 2.6 billion people without improved sanitation and, to meet the Millennium Development Goals sanitation target, some 1.6 billion people will have to be provided with improved sanitation by the end of 2015. How is this going to be achieved? This is a hugely important question for these 1.6 billion people. Part of the answer is the correct selection of sanitation technologies. Fortunately there are not many options, but they need to be fully understood by local sanitation engineers and planners so that they and the intended beneficiaries can make informed choices about which system may be the most appropriate in any given situation.

SANITATION OPTIONS IN RURAL AREAS

Low-density dispersed areas

In low-density rural areas individual-household on-site sanitation systems, including some simple means of greywater management, are commonly viable options. Such systems include:

- 1) single-pit ventilated improved pit latrines (Morgan and Mara, 1982; Mara, 1985a),
- 2) urine-diverting alternating twin-vault ventilated improved vault latrines (WIN-SA, 2006),
- 3) single-pit pour-flush toilets (Roy et al., 1984; Mara, 1985b),
- 4) biogas toilets (Mara, 2007), and
- 5) Arborloos (Morgan, 2007a,b; Simpson-Hébert, 2007).

Of these five options probably the one that is most likely to be the most appropriate in many, if not all, dispersed rural areas is the Arborloo as it provides not only sanitation but also agroforestry benefits and so actively helps to alleviate rural poverty (IFAD, 2008).

All the above options have to be complemented with a simple greywater-management system such as disposal in a stone-filled soakaway or used for irrigation of a “greywater garden” or the fruit or medicinal trees planted in full Arborloo pits (Ridderstolpe, 2004; Morel and Diener, 2006).

Higher-density nucleated areas

As the density increases (e.g., in large villages), options 2, 4 and 5 above are still viable. Although, as the density increases and the availability of space for sanitation facilities thus decreases, there would be a limit on the number of ‘Arborloo trees’ that could be grown. Options 1 and 3 would be better changed to alternating twin-pit VIP latrines, and alternating twin-pit pour-flush toilets, respectively (van Nostrand and Wilson, 1983; Mara, 1985a,b). Greywater management options would now also include modified stormwater drains (Kalbermatten et al., 1982b).

There is also a further option which has been successfully used in villages in the state of Ceará in northeast Brazil (Sarmiento, 2001): simplified sewerage (see below).

SANITATION OPTIONS IN URBAN AREAS

In high-density low-income urban areas, often termed ‘periurban’ areas, the most relevant sanitation systems are (i) simplified (also called ‘condominial’) sewerage (Sinnatamby, 1986; Mara et al., 2001; Melo, 2005), similar to ‘slum networking’ in India (Diacon, 1997; Parikh et al., 2002), (ii) low-cost combined sewerage (Guimarães and de Souza, 2004; Beauséjour and Nguyen, 2007; Beauséjour, 2008), and (iii) in periurban slums community-managed sanitation blocks (Burra et al., 2003).

In areas with existing septic tanks (i.e., mainly non-poor areas) which are malfunctioning due to the inability of the local soil to absorb the tank effluent, options are the installation of in-house water-saving plumbing fixtures (to reduce the quantity of wastewater generated to the level that the soil is again able to absorb the septic tank effluent) (Mara, 1989), and/or settled sewerage (also called ‘solids-free’ sewerage) (Otis and Mara, 1985).

There are two sanitation options that are *not* applicable in poor urban areas: these are conventional sewerage which is excluded on grounds of excessively high costs (Kalbermatten et al., 1982a), and ecological sanitation, especially its multi-sewer variant, which is also excluded for reasons of very high costs (SEI, 2005; Oldenburg et al., 2007), but also because it is not yet sufficiently well developed for large-scale application in urban areas (Otterpohl, 2008).

SELECTION CRITERIA

In any one location the most appropriate sanitation option has to be chosen from those mentioned above, with ‘appropriate’ being understood to refer to social acceptability, financial affordability, institutional acceptance and physical feasibility. As almost all those to be provided with improved sanitation facilities by 2015 and beyond are the poor and the very poor, cost is generally the most important selection criterion. Thus in dispersed rural areas Arborloos ‘win’ because not only are they very cheap to build (costing around USD 10–20, Simpson-Hébert, 2007), but they also generate an income for very many years. Similarly in

high-density periurban areas simplified sewerage generally wins as the monthly charge is very low (Mara, 2008).

REFERENCES

- Beauséjour, J. (2008). *Alternatives à l'Assainissement Centralisé dans les Pays en Développement: Le Cas des Zones Périurbaines sur Vietnam (Alternatives to Centralized Sanitation: Case Study of Periurban Areas in Vietnam)* (Thèse de doctorat/PhD thesis). Montréal: Université de Montréal.
- Beauséjour, J. and Nguyen, V. A. (2007). Decentralized sanitation implementation in Vietnam: a peri-urban case study. *Water Science & Technology* **56** (5), 133–139.
- Burra, S., Patel, S. and Kerr, T. (2003). Community-designed built and managed toilet blocks in Indian cities. *Environment & Urbanization* **15** (2), 11–32.
- Diacon, D. (1997). *Slum Networking: An Innovative Approach to Urban Development in India*. Coalville: Building and Social Housing Foundation.
- Guimarães, A. S. P. and de Souza, A. P. (2004). *Projetos de Pequenos Sistemas Unitários de Esgotamento (Design of Small Combined Sewerage Systems)*. Brasília: Caixa Econômica Federal.
- IFAD (2008). Tree domestication programme in Africa helps families out of poverty, web-page at: www.ruralpovertyportal.org/english/regions/africa/cmr/voices/tree.htm. Rome: International Fund for Agricultural Development
- Kalbermatten, J. M., Julius, D. S. and Gunnerson, C. G. (1982a). *Appropriate Sanitation Alternatives: A Technical and Economic Appraisal* (World Bank Studies in Water Supply and Sanitation No. 1). Baltimore, MD: Johns Hopkins University Press.
- Kalbermatten, J. M., Julius, D. S., Gunnerson, C. G. and Mara, D. D. (1982b). *Appropriate Sanitation Alternatives: A Planning and Design Manual* (World Bank Studies in Water Supply and Sanitation No. 2). Baltimore, MD: Johns Hopkins University Press.
- Mara, D. D. (1985a). *The Design of Ventilated Improved Pit Latrines* (TAG Technical Note No. 13). Washington, DC: The World Bank.
- Mara, D. D. (1985b). *The Design of Pour-Flush Latrines* (TAG Technical Note No. 15). Washington, DC: The World Bank.
- Mara, D. D. (1989). *The Conservation of Drinking-water Supplies: Techniques for Low-income Settlements*. Nairobi: United Nations Centre for Human Settlements.
- Mara, D. D. (2007). *Good Sanitation Practice No. 5: Biogas Toilets*, available at: www.personal.leeds.ac.uk/~cen6ddm/SanitationPracticeBoxes/GoodPractice5_Biogas%20toilets.pdf.
- Mara, D. D. (2008). Simplified/condominial sewerage – 2. Blog, dated 24 January, available at: duncanmarasanitation.blogspot.com/2008/01/simplifiedcondominial-sewerage-2.html.
- Mara, D. D., Sleight, P. A. and Tayler, K. (2001). *PC-based Simplified Sewer Design*. Leeds: School of Civil Engineering, University of Leeds.
- Melo, J. C. (2005). *The Experience of Condominial Water and Sewerage Systems in Brazil: Case Studies from Brasília, Salvador and Parauapebas*. Lima: Water and Sanitation Program Latin America.
- Morel, A. and Diener, S. (2006). *Greywater Management in Low- and Middle-Income Countries*. Dübendorf: Sandec/EAWAG.
- Morgan, P. R. (2007a). *Toilets that Make Compost: Low-cost Sanitary Toilets that Produce Valuable Compost for Crops in an African Context*. Stockholm: EcoSanRes Programme, Stockholm Environment Institute.

- Morgan, P. R. (2007b). EcoSan at low cost – with the potential for upgrading. *Waterlines* **26** (2), 6–7.
- Morgan, P. R. and Mara, D. D. (1982). *Ventilated Improved Pit Latrines: Recent Developments in Zimbabwe* (Technical Paper No. 3). Washington, DC: The World Bank.
- Oldenburg, M., Peter-Fröhlich, A., Dlabacs, C., Pawlowski, L. and Bonhomme, A. (2007). EU demonstration project for separate discharge and treatment of urine, faeces and greywater – Part II: Cost comparison of different sanitation systems. *Water Science & Technology* **56** (5), 251–257.
- Otis, R. J. and Mara, D. D. (1985). *The Design of Small-bore Sewers* (TAG Technical Note No. 14). Washington, DC: The World Bank.
- Otterpohl, R. (2008). Pathways for future developments in sanitation. Presentation at the International Conference ‘Sanitation Challenge: New Sanitation Concepts and Models of Governance’. Wageningen: Wageningen University, 19–21 May.
- Parikh, H., Surkar, D. and Zanders, M. O. (2002). Sustainable infrastructure development for slums and villages. Paper presented at the 28th WEDC Conference ‘Sustainable Environmental Sanitation and Water Services’, Kolkata.
- Ridderstolpe, P. (2004). *Introduction to Greywater Management*. Stockholm: Stockholm Environment Institute.
- Roy, A. K., Chatterjee, P. K., Gupta, K. N., Khare, S. T., Rau, B. B. and Singh, R. S. (1984). *Manual on the Design, Construction and Maintenance of Low-cost Pour-flush Waterseal Latrines* (TAG Technical Note No. 10). Washington, DC: The World Bank.
- Sarmiento, V. de B. A. (2001). *Low-cost Sanitation Improvements in Poor Communities: Conditions for Physical Sustainability* (PhD thesis). Leeds: University of Leeds.
- SEI (2005). *Sustainable Pathways to Attain the Millennium Development Goals – Assessing the Role of Water, Energy and Sanitation*. Stockholm: Stockholm Environment Institute.
- Simpson-Hébert, M. (2007). Low-cost Arborloo offers Ethiopians health and agriculture benefits. *Waterlines* **26** (2), 12–14.
- Sinnatamby, G. S. (1986). *The Design of Shallow Sewer Systems*. Nairobi: United Nations Centre for Human Settlements.
- van Nostrand, J. and Wilson, J. G. (1983). *The Ventilated Improved Double Pit Latrine: A Construction Manual for Botswana* (TAG Technical Note No. 3). Washington, DC: The World Bank.
- WIN-SA (2006). *eThekweni's Water & Sanitation Programme*. Pretoria: Water Information Network – South Africa.