



University of HUDDERSFIELD

University of Huddersfield Repository

Opoz, Tahsin Tecelli and Chen, Xun

Material removal phases in single abrasive grain grinding

Original Citation

Opoz, Tahsin Tecelli and Chen, Xun (2010) Material removal phases in single abrasive grain grinding. In: AMPT 2010, October 24-27, Paris. (Unpublished)

This version is available at <http://eprints.hud.ac.uk/9775/>

The University Repository is a digital collection of the research output of the University, available on Open Access. Copyright and Moral Rights for the items on this site are retained by the individual author and/or other copyright owners. Users may access full items free of charge; copies of full text items generally can be reproduced, displayed or performed and given to third parties in any format or medium for personal research or study, educational or not-for-profit purposes without prior permission or charge, provided:

- The authors, title and full bibliographic details is credited in any copy;
- A hyperlink and/or URL is included for the original metadata page; and
- The content is not changed in any way.

For more information, including our policy and submission procedure, please contact the Repository Team at: E.mailbox@hud.ac.uk.

<http://eprints.hud.ac.uk/>

MATERIAL REMOVAL PHASES IN SINGLE ABRASIVE GRAIN GRINDING

Tahsin Tecelli Öpöz and Xun Chen

Centre for Precision Technologies, University of Huddersfield, Huddersfield, UK

Key words: Finite Element Analysis, single grain abrasive, grinding

In this research basic material removal characteristics with single abrasive grain is explored by using Finite Element Analysis (FEA). Material properties of Cubic Boron Nitride (CBN) and Steel are used for abrasive grain and workpiece part in FEA simulation, respectively. ABAQUS/CAE is used as a computational environment. Transition between material removal phases are observed. Different indentation depths and different size grain with a defined sliding path are simulated to investigate the effect of depth of cut in transition of material removal generally called as rubbing, ploughing and cutting phenomenon. Friction coefficient is also involved to the model by using penalty friction formulation in Abaqus. The most important thing to get good results from simulation is the satisfaction of meshing size with plastic deformation. To provide good contact conformity between two surfaces without using computational resource excessively, a remeshing strategy is built up in contact area where the high plastic deformation subjected to work material. The FEA simulation is highly strong tool to predict the grinding outcomes and results physically. The paper presents the results of rubbing and ploughing phase of grinding as shown in Figure 1. In the literature this type of model was named as micro-scale model dealing with individual grain interaction with workpiece [1, 2]. Micro-scale modelling of grinding still requires many developments for fully understanding of grinding material removal. The grinding action of a single grain including rubbing, ploughing and cutting phases was first put forth by Hahn [3] and was called as a prevailing rubbing hypothesis. Recent investigation on three dimensional finite element model of rubbing and ploughing phases in single-grain grinding has performed by Doman et al [4] by considering the elastoplastic material characteristics.




Figure 1 Example of (a) remeshed part and (b) single grain scratch groove

References

- [1] Brinksmeier E, Aurich JC, Govekar E, Heinzel C, Hoffmeister H-W, Klocke F, Peters J, Rentsch R, Stephenson DJ, Uhlmann E, Weinert K, Wittmann M, (2006) Advances in Modeling and Simulation of Grinding Processes. *Annals of the CIRP* 55(2):667–696
- [2] Doman DA, Warkentin A, Bauer R, (2009) Finite element modeling approaches in grinding. *International Journal of Machine Tools & Manufacture* 49:109-116
- [3] Hahn RS, (1962) On the nature of the grinding process. In *Proceeding of the 3rd International Conference On Machine tool design and research*, Birmingham, UK, pp:129-154
- [4] Doman DA, Bauer R, Warkentin A, (2009) Experimentally validated finite element model of the rubbing and ploughing phases in scratch tests. *Proc. IMechE Part B: J. Engineering Manufacture* 223:1519-1527