

NASA TECHNICAL NOTE



NASA TN D-3718

c. 1




NASA TN D-3718

**LOAN COPY: RETURN TO
AFWL (WLIL-2)
KIRTLAND AFB, N MEX**

SUBSONIC LONGITUDINAL AERODYNAMIC CHARACTERISTICS OF A 40° SEMIAPEX ANGLE CONICAL REENTRY CONFIGURATION

*by W. Pelham Phillips
Langley Research Center
Langley Station, Hampton, Va.*





SUBSONIC LONGITUDINAL AERODYNAMIC CHARACTERISTICS OF A
40° SEMIAPEX ANGLE CONICAL REENTRY CONFIGURATION

By W. Pelham Phillips

Langley Research Center
Langley Station, Hampton, Va.

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

For sale by the Clearinghouse for Federal Scientific and Technical Information
Springfield, Virginia 22151 - Price \$1.00

SUBSONIC LONGITUDINAL AERODYNAMIC CHARACTERISTICS OF A 40° SEMIAPEX ANGLE CONICAL REENTRY CONFIGURATION

By W. Pelham Phillips
Langley Research Center

SUMMARY

A wind-tunnel investigation has been made to determine the subsonic longitudinal aerodynamic characteristics of a 40° semiapex angle conical reentry configuration having several nose-to-base radii bluntness ratios. The longitudinal center-of-pressure locations near zero angle of attack were aft of the base for all nose bluntness ratios over the subsonic Mach number range investigated. The only notable effect of increasing nose bluntness for a given Mach number was a slight rearward movement of the center-of-pressure location relative to that of the sharp apex configuration.

INTRODUCTION

Considerable aerodynamic research has been conducted by the National Aeronautics and Space Administration and others on low-fineness-ratio bodies of varying shapes and bluntness having applications as possible manned or unmanned reentry configurations. (See, for example, refs. 1 to 6.) Blunted conical shapes of very low fineness ratio (that is, 0.5 to 1.0) are particularly desirable as unmanned reentry vehicles since increases in cone angle and nose bluntness result in considerable reductions in total entry heating and the associated higher deceleration levels are acceptable for payload instrumentation.

The present investigation was made to provide the subsonic longitudinal aerodynamic characteristics for a 40° semiapex angle conical reentry configuration having nose-to-base radii bluntness ratios of 0, 0.2, and 0.4. The investigation was conducted in the Langley high-speed 7- by 10-foot tunnel at angles of attack from approximately -2° to 47° over a Mach number range from 0.200 to 0.583.

SYMBOLS

The data presented herein were computed about the body axis system and nondimensionalized with respect to the maximum cross-sectional area and maximum diameter of the cone. The moment reference point was located at the intersection of the axis of symmetry with the plane of maximum cross section.

C_A	axial-force coefficient, $\frac{\text{Axial force}}{qS}$
$C_{A,0}$	axial-force coefficient at $\alpha = 0^\circ$
C_m	pitching-moment coefficient, $\frac{\text{Pitching moment}}{qSd}$
$C_{m\alpha}$	longitudinal stability parameter, per degree
C_N	normal-force coefficient, $\frac{\text{Normal force}}{qS}$
$C_{N\alpha}$	normal-force-curve slope, per degree
d	base diameter, 0.4064 meter
l	cone length (measured from apex to station for maximum cross section), 0.2426 meter
M	Mach number
N_{Re}	Reynolds number, $\frac{\rho V l}{\mu}$
q	free-stream dynamic pressure, newtons/meter ²
r	nose radius, meters
R	base radius, 0.2032 meter
S	base area (cross sectional), 0.1297 meter ²
V	free-stream velocity, meters/second
$\frac{x_{cp}}{l}$	longitudinal center-of-pressure location expressed in body lengths from nose ($\alpha \approx 2^\circ$), $1 - \frac{C_{m\alpha}(d)}{C_{N\alpha}(l)}$
α	angle of attack, degrees

ρ density of air, kilograms/meter³

μ viscosity of air, $\frac{\text{kilograms}}{\text{meter-second}}$

MODEL

The wind-tunnel model of the present investigation was a right circular cone having a semiapex angle of 40° and a sharp-edged slightly convex base. Model drawings and a photograph are included in figures 1 and 2, respectively.

The base cap of the model was formed by a spherical segment having a radius of 0.9144 meter. Nose-to-base radii bluntness ratios (referred to cross-section radius at base) of 0, 0.2, and 0.4 were made possible by the use of replaceable nose caps.

TESTS AND CORRECTIONS

The present investigation was conducted in the Langley high-speed 7- by 10-foot tunnel at Mach numbers from 0.200 to 0.583. Average test Reynolds numbers are shown as a function of Mach number in figure 3. The model was tested at angles of attack from approximately -2° to 47° and utilized a sting-mounted, six-component strain-gage balance to provide force and moment measurements. A differential pressure transducer was used to measure pressure differences between the central region of the spherical base cap and the sting cavity.

Jet boundary and blockage corrections have been applied to the data (where applicable) in accordance with the methods outlined in references 7 and 8, respectively. The angle-of-attack data have also been corrected to account for sting and balance deflection under load. No corrections to the axial-force data were made to account for pressure differences across the region of the spherical base cap containing the sting cavity since pressure measurements indicated only insignificant corrections. Total axial-force data (including base drag) are presented herein since the model represents an unpowered reentry configuration. No attempt was made to fix transition during the wind-tunnel investigation.

RESULTS

The longitudinal aerodynamic characteristics for the 40° semiapex angle conical reentry configuration are presented in figure 4 for the various nose bluntness ratios over the Mach number range investigated.

The positive values of C_m noted at $\alpha = 0$ are equivalent to a 0.0203-meter vertical displacement of the axial-force vector relative to the balance moment reference point. This discrepancy is attributed to possible errors in model-balance construction and/or wind-tunnel installation. The discrepancies noted in C_A and C_m at $\alpha \approx 24^\circ$ are indicative of sting support interference on model base pressures for the sting knuckle setting visible in figure 2. This knuckle setting was required to obtain aerodynamic data at the high angles of attack (24° to 47°) of the investigation. Variations of the aerodynamic parameters x_{cp}/l , $C_{N\alpha}$, and $C_{A,0}$ are shown in figure 5 as a function of Mach number.

The most forward center-of-pressure location ($\alpha \approx 2^\circ$) for the 40° semiapex angle cone was found to occur at 0.13*l* aft of the maximum cross section for the sharp apex configuration ($r/R = 0$) at a Mach number of 0.583. (See fig. 5.) Center-of-pressure locations aft of the configuration base are desirable for unmanned reentry configurations in that they allow uncomplicated longitudinal payload balancing to achieve acceptable static longitudinal stability levels in nose-forward flight attitudes.

Increasing the nose-to-base radii bluntness ratio from the sharp apex conditions to a value of 0.4 produced slight rearward movements in center of pressure throughout the Mach number range investigated with no appreciable effect on $C_{N\alpha}$ and $C_{A,0}$. Increasing test Mach numbers from 0.200 to 0.583 produced increases in $C_{N\alpha}$ and $C_{A,0}$ and a slight forward movement of the center of pressure.

CONCLUSIONS

An investigation has been made in the Langley high-speed 7- by 10-foot tunnel to determine the subsonic longitudinal aerodynamic characteristics of a 40° semiapex angle conical reentry configuration having several nose-to-base radii bluntness ratios. Investigation results may be summarized by the following observations:

1. The longitudinal center-of-pressure locations near zero angle of attack were aft of the base for all nose bluntness ratios over the subsonic Mach number range investigated.
2. The only notable effect of increasing nose bluntness for a given Mach number was a slight rearward movement of the center-of-pressure location relative to that of the sharp apex configuration.

Langley Research Center,
National Aeronautics and Space Administration,
Langley Station, Hampton, Va., August 25, 1966,
124-07-03-05-23.

REFERENCES

1. Witcofski, Robert D.; and Woods, William C.: Static Stability Characteristics of Blunt Low-Fineness-Ratio Bodies of Revolution at a Mach Number of 24.5 in Helium. NASA TN D-2282, 1964.
2. Penland, Jim A.: A Study of the Stability and Location of the Center of Pressure on Sharp, Right Circular Cones at Hypersonic Speeds. NASA TN D-2283, 1964.
3. Armstrong, William O.: Hypersonic Aerodynamic Characteristics of Several Series of Lifting Bodies Applicable to Reentry Vehicle Design. NASA TM X-536, 1961.
4. Brooks, Cuyler W., Jr.; and Trescot, Charles D., Jr.: Transonic Investigation of the Effects of Nose Bluntness, Fineness Ratio, Cone Angle, and Base Shape on the Static Aerodynamic Characteristics of Short, Blunt Cones at Angles of Attack to 180° . NASA TN D-1926, 1963.
5. Hayes, William C., Jr.; and Henderson, William P.: Some Effects of Nose Bluntness and Fineness Ratio on the Static Longitudinal Aerodynamic Characteristics of Bodies of Revolution at Subsonic Speeds. NASA TN D-650, 1961.
6. Spencer, Bernard, Jr.; and Phillips, W. Pelham: Transonic Aerodynamic Characteristics of a Series of Bodies Having Variations in Fineness Ratio and Cross-Sectional Ellipticity. NASA TN D-2622, 1965.
7. Gillis, Clarence L.; Polhamus, Edward C.; and Gray, Joseph L., Jr.: Charts for Determining Jet-Boundary Corrections for Complete Models in 7- by 10-Foot Closed Rectangular Wind Tunnels. NACA WR L-123, 1945. (Formerly NACA ARR L5G31.)
8. Herriot, John G.: Blockage Corrections for Three-Dimensional-Flow Closed-Throat Wind Tunnels, With Consideration of the Effect of Compressibility. NACA Rept. 995, 1950. (Supersedes NACA RM A7B28.)




Figure 1.- Geometric characteristics of model tested. All dimensions are in meters unless otherwise specified.




Figure 2.- Three-quarter side view of 80° cone model having $r/R = 0$.

L-64-6413





Figure 3.- Variation of average test Reynolds number (based on model length) with Mach number.



(a) Variation of C_N with α .

Figure 4.- Effect of nose-to-base radii bluntness ratio on the longitudinal aerodynamic characteristics for the configuration.



(b) Variation of C_A with α .

Figure 4.- Continued.



(c) Variation of C_m with α .

Figure 4.- Concluded.




Figure 5.- Summary of aerodynamic parameters x_{cp}/l , $C_{N\alpha}$, and $C_{A,0}$ for various nose bluntness ratios and Mach numbers.

"The aeronautical and space activities of the United States shall be conducted so as to contribute . . . to the expansion of human knowledge of phenomena in the atmosphere and space. The Administration shall provide for the widest practicable and appropriate dissemination of information concerning its activities and the results thereof."

—NATIONAL AERONAUTICS AND SPACE ACT OF 1958

NASA SCIENTIFIC AND TECHNICAL PUBLICATIONS

TECHNICAL REPORTS: Scientific and technical information considered important, complete, and a lasting contribution to existing knowledge.

TECHNICAL NOTES: Information less broad in scope but nevertheless of importance as a contribution to existing knowledge.

TECHNICAL MEMORANDUMS: Information receiving limited distribution because of preliminary data, security classification, or other reasons.

CONTRACTOR REPORTS: Technical information generated in connection with a NASA contract or grant and released under NASA auspices.

TECHNICAL TRANSLATIONS: Information published in a foreign language considered to merit NASA distribution in English.

TECHNICAL REPRINTS: Information derived from NASA activities and initially published in the form of journal articles.

SPECIAL PUBLICATIONS: Information derived from or of value to NASA activities but not necessarily reporting the results of individual NASA-programmed scientific efforts. Publications include conference proceedings, monographs, data compilations, handbooks, sourcebooks, and special bibliographies.

Details on the availability of these publications may be obtained from:

SCIENTIFIC AND TECHNICAL INFORMATION DIVISION
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
Washington, D.C. 20546