Int J Ind Chem (2016) 7:223-229 DOI 10.1007/s40090-016-0076-x



RESEARCH

Influence of ZnO doping and calcination temperature of nanosized CuO/MgO system on the dehydrogenation reactions of methanol

S. A. El-Molla¹ · Sh. M. Ibrahim^{1,2} · M. M. Ebrahim¹

Received: 31 July 2015/Accepted: 23 February 2016/Published online: 8 March 2016 © The Author(s) 2016. This article is published with open access at Springerlink.com

Pure and doped catalysts were prepared with ZnO dopant concentration (0.04–0.08 mol) by impregnation method followed by calcination 350-650 °C. The prepared solids were characterized by X-ray diffraction, N₂-adsorption at −196 °C and the methanol conversion as the catalytic probe reaction. The results revealed that the crystallite size and ordering of CuO phase decrease by ZnO-doping for samples calcined at 350-550 °C. Opposite trends were observed by increasing ZnO amount to 0.08 mol (i.e. 9.21 wt%). The specific surface area (S_{BET}) and the catalytic activity of pure catalyst increase by increasing the calcination temperature to 550 °C and/or increasing the amounts of ZnO up to certain extent reaching to a maximum at 7.07 wt% ZnO; above this concentration catalytic activity of doped samples decreases. But at calcination temperature above 550 °C, the catalytic activity and selectivity decrease. The prepared catalysts are selective towards formaldehyde and methyl formate formation.

Keywords ZnO-doping · CuO/MgO system · Methanol dehydrogenation · Conversion · Selectivity

Introduction

Methanol has been considered as an important raw material in the synthesis of various chemicals. Dehydrogenation of methanol was expected as a promising process to synthesize formaldehyde and methyl formate [1]. Formaldehyde is an industrial chemical that is widely used to manufacture numerous household products [2]. Formaldehyde and methyl formate are produced in large quantity by the coal chemical industry and natural gas chemical industry [3], both of them are important organic chemical materials usually used as the raw material of medicines [4]. Methanol is also considered as a candidate for the chemical carrier to transport hydrogen [5]. Copper-based catalysts appeared to be active towards the dehydrogenation of methanol. The activity and selectivity of catalyst were strongly influenced by both reaction conditions and surface structure. On reduced copper surface, CH₃O species decomposed near 370 K to form formaldehyde and methyl formate [6]. Over the past two decades, there has been considerable interest in the adsorption and decomposition mechanism of methanol over solid surfaces such as Cu, Pt, Ni, TiO_2 and other oxides [7–11].

Improving the catalytic activity and selectivity of metal oxides employed in some important industrial reactions is achieved using suitable support, exposure to radiation and doping with certain foreign cations [12, 13]. Doping of single or multicomponent metal or metal oxide system with certain foreign oxides was efficient approach for bringing about significant modifications in their thermal stability, electrical, optical, magnetic, surface and catalytic properties [14]. The addition of small amounts of certain foreign cations such as Li+, Zr4+ and K+ to CuO/MgO has influenced the mutual solid-solid interaction between constituents [15, 16]. This influence may be accompanied by



Sh. M. Ibrahim shiemaa 332003@yahoo.com

Department of Chemistry, Faculty of Education, Ain Shams University, Roxy, Cairo 11757, Egypt

Present Address: Department of Chemistry, Faculty of Science, Al-Qassim University, Al-Qassim, Buraidah 51452, Saudi Arabia

significant changes in the catalytic and physicochemical properties of the doped catalysts [14]. Doping CuO/MgO system with K₂O decreased the degree of ordering of CuO and MgO phases [16]. Li₂O-doping of CuO/MgO solid enhanced its catalytic activity towards conversion of isopropanol [15, 17]. ZnO is a well-known dopant for many catalytic systems such as NiO and Co₃O₄, in which ZnO brought about measurable changes in their specific surface areas and the crystallite sizes of their phases [18]. Doping Ni-Al₂O₃ system with ZnO affected on the range of reduction temperature of NiO due to formation of ZnAl₂O₄ spinel-liked structure [19]. It was reported that the reactivity of Fe_2O_3 to interact with MO (M = Mg, Ni, Co and Mn) yielding the corresponding MFe₂O₄ had been found to be much stimulated by doping with ZnO [20, 21]. Zn²⁺ had a high activity to diffuse into Co₃O₄ and Fe₂O₃ solids at about 600 °C [22]. Doping CuO/TiO2 with ZnO brought about a measurable decrease in the crystallite size of both anatase and CuO phases to an extent proportional to the amount of dopant added [23].

The present work aimed at studying the role of calcination temperature and ZnO doping of CuO/MgO system was prepared by impregnation method on its structural, surface characteristics, catalytic activity and selectivity. The techniques employed were X-ray-diffraction, N_2 -adsorption at $-196\,^{\circ}\text{C}$.

Experimental

Materials

A known amount of magnesium hydroxide (previously prepared [24]) was impregnated with a solution containing a known amount of copper nitrate dissolved in the least amount of distilled water. The CuO content in all solid samples was fixed at 23 mol%. The solutions prepared contained different proportions of Zn (NO₃)₂·6H₂O. The obtained pastes were dried at 110 °C and then calcined at 350–650 °C for 4 h. The amount of zinc oxide expressed in mole was 0.04, 0.05, 0.06 and 0.08. The undoped sample was nominated as CuMgO, but doped solids were determined and nominated as 0.04, 0.05, 0.06, 0.08 ZnO-doped CuMgO.

Techniques

X-Ray diffractograms of various prepared solids were determined using a Bruker diffractometer (Bruker D8 Advance). The scanning rate was fixed at 8° in 2θ /min and 0.8° in 2θ /min for phase identification and line broadening analysis, respectively. The patterns were run with $CuK\alpha1$ with secondly monochromator, $\lambda = 0.15005$ nm at 40 kV

and 40 mA. The crystallite size of the phases present was calculated using Scherrer equation [25].

The specific surface areas of the solid catalyst samples were determined from nitrogen adsorption desorption isotherms measured at $-196\,^{\circ}\mathrm{C}$ using a Quanta chrome NOVA 2000 automated gas-sorption apparatus model 7.11. All samples were degassed at 200 $^{\circ}\mathrm{C}$ for 2 h under a reduced pressure of 10^{-5} Torr before undertaking such measurements.

The catalytic activities of pure and variously ZnO doped-CuMgO solid catalyst samples towards methyl alcohol dehydrogenation were determined at reaction temperatures 125-275 °C, the catalytic reaction being conducted in a flow reactor under atmospheric pressure. Thus, a 50 mg catalyst sample was held between two glass wool plugs in a Pyrex glass reactor tube 20 cm long and 1 cm internal diameter packed with quartz fragments 2-3 mm length. The temperature of the catalyst bed was regulated and controlled to within ±1 °C. Argon gas was used as the diluents and the methyl alcohol vapor was introduced into the reactor through an evaporator/saturator containing the liquid reactant at constant temperature 26 °C. The flow rate of the carrier gas was maintained at 15 ml/min. Before carrying out such catalytic activity measurements, each catalyst sample was activated by heating at 300 °C in a current of argon for 1 h then cooled to the catalytic reaction temperature. The injection time of the reaction products and the unreacted methyl alcohol was fixed after 15 min, and GC control at t = constant was performed until achieving a steady state process. The reaction products in the gaseous phase were analyzed chromatographically using Perkin-Elmer Auto System XL Gas Chromatograph fitted with a flame ionization detector. Stainless steel chromatographic columns were used, 4 m length, packed with 10 % squalane supported on chromosorp. The reaction products were analyzed at a column temperature of 40 °C in all conversion runs. Detector temperature was kept at 250 °C.

Results and discussion

XRD investigation of pure ZnO-doped CuMgO solids calcined at different temperatures

X-Ray diffractograms of pure and variously ZnO-doped solids precalcined at 350–650 °C were determined and illustrated in Figs. 1 and 2. The values of crystallite sizes of different phases were calculated using Scherrer equation [25], are given in Table 1. Inspection of Figs. 1 and 2 and Table 1 revealed that: (1) all investigated solids precalcined at 350, 550 °C consisted of MgO as a major phase, CuO as a minor thereof together with Cu₂O phase in





nanocrystalline nature. The presence of $\mathrm{Cu_2O}$ phase was evidenced from the brown color of the calcined solids beside presence of diffraction line at d=2.44~Å (at $I/I>10~\mathrm{C/O}$). (2) Doping CuMgO system with 0.06 mol ZnO (i.e. 7.07 wt%) brought about a measurable decrease in both of ordering and crystallite sizes of MgO and CuO phases, further increase in ZnO amount to 0.08 mol (i.e.




Fig. 1 XRD diffractograms of pure and ZnO doped CuMgO solids precalcined at 550 °C. *Lines 1* refer to MgO, *lines 2* refer to CuO phases, *lines 3* refer to Cu₂O phase




Fig. 2 XRD diffractograms of pure and ZnO-doped CuMgO solids precalcined at 350 and 650 °C. *Lines 1* refer to MgO, *lines 2* refer to CuO phases, *lines 3* refer to Cu₂O phase

Table 1 Intensity count, crystallite sizes of various phases present in pure and ZnOdoped CuMgO solids calcined at 350, 550 and 650 °C

MgO phase. (3) Calcination at 350 and 550 °C of the doped
solids resulted in the formation of nanocrystalline ZnO
phase, its crystallite size increases with increasing ZnO
content. (4) The rise in calcination temperature of pure and
ZnO-doped solids to 650 °C causes decreasing the degree
of ordering of CuO, MgO and ZnO phases, but led to
increasing the crystallite size of CuO (4.7–25 nm).
These obtained results can be explained in the role of
ZnO-doping in increasing the degree of dispersion of active
phase [26, 27] via decreasing its crystallite sizes. The
mechanism of this action had been tentatively attributed to

9.21 wt%) resulted in an increase in the degree of ordering

of CuO phase while opposite result was found in case of

Inese obtained results can be explained in the role of ZnO-doping in increasing the degree of dispersion of active phase [26, 27] via decreasing its crystallite sizes. The mechanism of this action had been tentatively attributed to coating the copper oxide crystallites by ZnO film that may hinder the particle adhesion of the doped oxide solids [26]. The re-increase of degree of crystallinity of CuO phase in the highly doped sample (0.08 mol) at 550 °C could be due to the presence of maximum limit for ZnO to hinder the grain growth of CuO. Increasing ZnO content to 0.06 mol at 650 °C led to dissolving ZnO in MgO and forms solid solution; this interaction led the finally divided CuO crystallites to grow on the top surface layer of MgO. This speculation was based on the effective increase in the crystallite size of CuO as shown in Table 1.

Specific surface areas of pure and ZnO-doping CuMgO calcined at different temperatures

The surface characteristics of pure adsorbent sample and those treated with small amounts of ZnO precalcined in air at 550 and 650 °C were determined from nitrogen adsorption isotherms conducted at -196 °C. The dopant concentrations were 0.06 and 0.08 mol ZnO per mol MgO corresponding to 7.07 and 9.21 wt%, respectively. The surface characteristics, namely $S_{\rm BET}$, $V_{\rm p}$ "total pore volume" and r^- "mean pore radius" calculated for various adsorbents are listed in Table 2. Inspection of the results in Table 2 shows that (1) addition of ZnO resulted in a progressive increase in the specific surface areas of the treated solids. The maximum increase in the $S_{\rm BET}$ due to treatment with 0.06 and 0.08 mol ZnO attained about 33 and 52 %

Solid	Calcination temp. (°C)	Intensity count (a.u.)			Crystallite size (nm)			I/Io
		MgO	CuO	ZnO	MgO	CuO	ZnO	Cu_2O
Pure solid	350	131	52	_	17	11	_	27
0.06 ZnO	350	81	36	36	13	4.7	4.7	39
Pure solid	550	114	43	_	12	14.6	_	31
0.06 ZnO	550	109	30	30	12.4	8.7	8.7	30
0.08 ZnO	550	73	61	45	8.6	16.5	13.6	55
Pure solid	650	93	32	_	14	21	_	23
0.06 ZnO	650	94	25	-	14	25	-	33



Table 2 The specific surface areas of pure and ZnO-doped 0.3CuO/MgO adsorbents precalcined at 550 and 650 °C


Moles of ZnO	Calcination temp. (°C)	$S_{\rm BET}~({\rm m}^2/{\rm g})$	$V_{\rm p}~({\rm cm}^3/{\rm g})$	r- (Å)
0	550	21	0.108	103
0.06	550	28	0.109	78
0.08	550	32	0.102	64
0	650	16	0.052	65
0.06	650	22	0.048	44

for the solids calcined at 550 °C. The observed increase in the specific surface areas of ZnO-doped solids may be attributed to formation of new pores. The formation of these pores may be due to liberation of gaseous nitrogen oxides in the course of the heat treatment of zinc nitrate added. (2) Increasing the calcination temperature from 550 to 650 °C decreases the specific surface areas of the treated solids. The decrease in the S_{BET} by increasing calcination temperature to 650 °C attained 24 and 21 % for pure and doped solid with 0.06 mol ZnO, respectively. This decrease in specific surface areas of the treated solids may be attributed to collapse of the pore structure and/or the particle adhesion process (grain growth). In fact, the BETsurface area of CuMgO treated with 0.06 mol ZnO conducted at 650 °C measured 22 m²/g while the ZnO-free sample calcined at the same temperature measured 16 m²/g. These findings might suggest that ZnO acted as convenient stabilizer against thermal sintering process of the treated solids.

The extension in the surface area due to ZnO-doping is expected to be accompanied by a corresponding improvement in their catalytic activity.

Catalytic activity and selectivity of the pure and ZnO-doped CuMgO systems towards methanol dehydrogenation reactions

Doping with small amounts of ZnO affected both structural and surface properties of the investigated CuMgO system. The changes in structure and/or the surface can reflect the catalytic properties of these solid catalysts. The effect of ZnO-doping (0.04-0.08 mol)corresponding (4.83-9.21 wt%) of CuMgO followed by calcinations at 350-650 °C on the catalytic activity and selectivity was investigated at different reaction temperatures (125–275 °C) as shown in Figs. 3 and 4 and Tables 3 and 4. The reaction proceeded via dehydrogenation to give both methyl formate and formaldehyde [28]. Examination of Figs. 3 and 4 and Tables 3 and 4 shows the following: (1) the catalytic activity of investigated solids (expressed as conversion of methanol) increases with increasing reaction temperature in the range of 125–175 °C. Further increase in the reaction temperature is followed by a small decrease in the catalytic activity (above this temperature the activity tends to be stable).






Fig. 3 Total conversion of methanol as a function of reaction temperature over **(a)** CuMgO **(b)** 0.06 mol ZnO-doped CuMgO sample at different calcination temperatures

(2) Doping CuMgO solid with ZnO from 0.04 to 0.06 mol in the range of 125–175 °C led to increasing the conversion and selectivity of both formaldehyde and methyl formate. But increasing reaction temperature above 175 °C led to small increase in the conversion of methanol. (3) Further increase in ZnO content to (0.08 mol) decreases the conversion of methanol. (4) The catalytic activity and selectivity of pure and ZnO-doped solids increased with increasing the calcination temperature from 350 to 550 °C, but above this temperature the catalytic activity and selectivity decrease. (5)The investigated solids are selective to formaldehyde (S_F %) at low temperature, this selectivity decreases with increasing reaction temperature from 125 to 275 °C. The selectivity towards methyl formate (S_m %) was more pronounced at high reaction temperature.





Fig. 4 Total conversion of methanol at reaction temperature 125 and 150 °C over pure CuMgO and those variously ZnO-doped samples calcined at 550 °C




Table 3 Effect of ZnO-doping on the selectivity of CuMgO solids calcined at 550 $^{\circ}$ C towards methanol dehydrogenation (with reference to formaldehyde ($S_{\rm f}$ %) and methyl formate ($S_{\rm m}$ %)

The solids	Selectivities (%)	150 °C	175 °C	200 °C	225 °C	250 °C	275 °C
0.3CuMgO	$S_{ m m}$	17	43	46	48	53	59
	$S_{ m f}$	83	57	54	52	47	41
0.04ZnO/0.3CuMgO	$S_{ m m}$	17	47	50	52	55	57
	$S_{ m f}$	83	53	50	48	45	43
0.05ZnO/0.3CuMgO	$S_{ m m}$	18	47	50	53	55	57
	$S_{ m f}$	82	53	50	47	45	43
0.06ZnO/0.3CuMgO	$S_{ m m}$	23	42	48	50	52	52
	$S_{ m f}$	77	58	52	50	48	48
0.08ZnO/0.3CuMgO	$S_{ m m}$	16	42	45	50	51	58
	$S_{ m f}$	84	58	55	51	49	42

The results mentioned above can be explained in the light of: (1) the investigated CuMgO system is dehydrogenation catalyst. The prepared catalysts are selective to formaldehyde formation due to the presence of dehydrogenation sites (copper species) [15, 29–31]. (2) The observed increase in the catalytic activity and selectivity of solid samples doped with ZnO (0.06 mol) 7.07 wt% may be attributed to an affective increase in the concentration of active sites involved in the catalytic reaction via decreasing the crystallite size of CuO and MgO phase (as shown in "XRD" section), beside increasing the $S_{\rm BET}$ as shown in Table 2 and the presence of ZnO as dehydrogenation catalyst.

(3) Decreasing the catalytic activity and selectivity of doped solids above 0.06 mol% ZnO may be due to decreasing the ability of ZnO to hinder the grain growth of CuO and small amount of ZnO dissolves in MgO matrix. These effects yielded big crystallites of CuO (as shown in "XRD" section). (4) The observed increase in the catalytic activity by increasing the calcination temperature from 350 to 550 °C can be explained in the light of possible completeness of thermal decomposition of Mg(OH)₂ and also formation of new active sites responsible for increasing the catalytic activity, beside increasing the $S_{\rm BET}$ as shown in Table 2. (5) Beside the possible dissolution of ZnO in both CuO and MgO



The Solids	Calcination temperature (°C)	Selectivities (%)	125 °C	150 °C	175 °C	200 °C	225 °C	250 °C	275 °C
0.3CuMgO	350	$S_{ m m}$	100	12	42	50	54	56	58
		$S_{ m f}$	0	88	58	50	46	45	42
0.06ZnO/0.3CuMgO	350	$S_{ m m}$	74	14	38	48	52	55	57
		$S_{ m f}$	26	86	62	52	48	45	43
0.3CuMgO	650	$S_{ m m}$	100	9	41	49	54	57	58
		$S_{ m f}$	0	92	59	51	46	44	42
0.06ZnO/0.3CuMgO	650	$S_{ m m}$	65	11	41	45	52	56	58
		$S_{ m f}$	35	90	59	55	48	44	42

Table 4 Effect of calcination temperature of pure 0.3CuMgO and ZnO-doped solids on their selectivities in the course of methanol dehydrogenation with respect to formaldehyde (S_f %) and methyl formate (S_m %)

lattice yielding various solid solutions [32], the obtained decrease in the catalytic activity as a result of increasing the calcination temperature above 550 °C may be attributed to an effective increase in the crystallite size of copper oxides in pure and doped solids (as shown in "XRD" section), which was evidenced also, by decreasing the $S_{\rm BET}$ as shown in Table 2. The portion of CuO and/or ZnO involved in solid solution should have very small catalytic activity.

Conclusions

In conclusion, the physicochemical and catalytic properties of CuMgO system are affected by ZnO-doping and calcination temperature. The results revealed that:

- The crystallite size and ordering of CuO phase decrease to (4 nm) by ZnO-doping (<0.08 mol) for samples calcined at 350–550 °C. Opposite trends was observed by increasing ZnO amount to 0.08 mol (i.e. 9.21 wt%).
- The BET surface area and catalytic activity of CuMgO catalyst increase by increasing the calcination temperature from 350 to 550 °C and/or by increasing the amounts of ZnO up to certain extent reaching to a maximum at 7.07 wt% ZnO.
- In the pure and doped samples, increasing the calcination temperature to 650 °C led to increasing the crystallite size of CuO, decreasing the catalytic activity and selectivity.
- 4. The prepared catalysts were selective towards formaldehyde and methyl formate formation.

Open Access This article is distributed under the terms of the Creative Commons Attribution 4.0 International License (http://creative commons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons license, and indicate if changes were made.

References

- Guerrero-Ruiz A, Rodriguez-Ramos I, Fierro JLG (1991) Dehydrogenation of methanol to methyl formate over supported copper catalysts. Appl Catal 72:119
- Thorud S, Gjolstad M, Ellingsen DG, Molander P (2005) Air formaldehyde and solvent concentrations during surface coating with acid-curing lacquers and paints in the woodworking and furniture industry. J Environ Monit 7:586
- 3. Lee JS, Kim JC, Kim YG (1990) Methyl formate as a new building block in C₁ chemistry. Appl Catal 57:1
- Lee YS, Kim JC, Lee JS, Kim YG (1993) Carbonylation of formaldehyde over ion exchange resin catalysts. Ind Eng Chem Res 32:253
- Adamson K, Pearson P (2000) Hydrogen and methanol: a comparison of safety, economics, efficiencies and emissions. J Power Sources 86:548
- Fu SS, Somorjai GA (1992) Roles of chemisorbed oxygen and zinc oxide islands on copper(110) surfaces for methanol decomposition. J Phys Chem 96:4542
- Hsu WD, Ichihashi M, Kondow T, Sinnott SB (2007) Ab initio molecular dynamics study of methanol adsorption on copper clusters. J Phys Chem A 111:441
- Spendelow JS, Goodpaster JD, Kenis PJA, Wieckowski A (2006) Methanol dehydrogenation and oxidation on Pt(111) in alkaline solutions. Langmuir 22:10457
- Wang GC, Zhou YH, Morikawa Y, Nakamura J, Cai ZS, Zhao XZ (2005) Kinetic mechanism of methanol decomposition on Ni(111) surface: a theoretical study. J Phys Chem B 109:12431
- Gong XQ, Selloni A, Vittadini A (2006) Density functional theory study of formic acid adsorption on anatase TiO₂(001): geometries, energetics, and effects of coverage, hydration, and reconstruction. J Phys Chem B 110:2804
- Branda MM, Collins SE, Castellani NJ, Baltanas MA, Bonivardi AL (2006) Methanol adsorption on the beta-Ga₂O₃ surface with oxygen vacancies: theoretical and experimental approach. J Phys Chem B 110:11847
- El-Molla SA, Ismail SA, Ibrahim MM (2011) Effects of γ-irradiation and ageing on Surface and catalytic properties of nano-sized CuO/MgO system. J Mex Chem Soc 55(3): 154–163
- Ibrahim SM, Badawy AA, El-Shobaky GA, Mohamed HA (2014) Structural, surface and catalytic properties of pure and ZrO₂doped nanosized cobalt–manganese mixed oxides. Can J Chem Eng 92:676–684
- 14. Rossignol S, Kappenstein C (2001) Effect of doping elements on the thermal stability of transition alumina. Int J Inorg Mater 3:51





- El-Molla SA (2006) Dehydrogenation and condensation in catalytic conversion of iso-propanol over CuO/MgO system doped with Li₂O and ZrO₂. Appl Catal A 298:103
- El-Molla SA, El-Shobaky GA, Amin NH, Hammed MN, Sultan SN (2013) Catalytic properties of pure and K-doped CuO/MgO system towards 2-propanol conversion. J Mex Chem Soc 57(1):36
- Diez VK, Apesteguia CR, Dicosimo JI (2000) Acid-base properties and active site requirements for elimination reactions on alkali-promoted MgO catalysts. Catal Today 63:53
- El-Shobaky GA, Ghozza AM (2004) Effect of ZnO doping on surface and catalytic properties of NiO and Co₃O₄ solids. Mater Lett 58:699
- Chen J, Qiao Y, Li Y (2008) Promoting effects of doping ZnO into coprecipitated Ni–Al₂O₃ catalyst on methane decomposition to hydrogen and carbon nanofibers. Appl Catal A 337:148
- 20. El-Shobaky GA, Radwan NRE, Radwan FM (2001) Investigation of solid–solid interactions between pure and $\text{Li}_2\text{O-doped}$ magnesium and ferric oxides. Thermochim Acta 380:27
- Radwan NRE, El-Shobaky HG (2001) Solid–solid interactions between ferric and cobalt oxides as influenced by Al₂O₃-doping. Thermochim Acta 360:147
- 22. Zhou J-p, He H-c, Lin Y-h (2006) Effect of ZnO doping on the reaction between Co and Fe oxides. Mater Lett 60:1542
- El-Shobaky HG, Ahmed AS, Radwan NRE (2006) Effect of γirradiation and ZnO-doping of CuO/TiO₂ system on its catalytic activity in ethanol and isopropanol conversion. Colloids Surf A 274:138

- El-Molla SA, Abdel-all SM, Ibrahim MM (2009) Influence of precursor of MgO and preparation conditions on the catalytic dehydrogenation of iso-propanol over CuO/MgO catalysts. J Alloys Compd 484:280
- Klug HP, Alexander LE (1966) X-ray diffraction procedures for polycrystalline and amorphous materials. Wiley, New York, p 491
- Dohiem MM, El-Boohy HA, Mokhater M, El-Shobaky GA (2001) Surface and catalytic properties of the γ-irradiated ZnOtreated Co₃O₄/Al₂O₃ system. Adsorpt Sci Technol 19:721
- El-Shobaky GA, Amin NH, Deras NM, El-Molla SA (2001)
 Decomposition of H₂O₂ on pure and ZnO-treated Co₃O₄/Al₂O₃ solids. Adsorpt Sci Technol 19(1):45–58
- Zaza P, Randall H, Dopper R, Renken A (1994) Dynamic kinetics of catalytic dehydrogenation of methanol to formaldehyde. Catal Today 20:325
- Wojciechowska M, Haber J, Lomnicki S, Stoch J (1999) Structure and catalytic activity of double oxide system: Cu–Cr–O supported on MgF₂. J Mol Catal A 141:155
- Pepe F, Angeletti C, Rossi S, Jacono ML (1985) Catalytic behavior and surface chemistry of copper/alumina catalysts for isopropanol decomposition. J Catal 91:69
- Henrich VE, Cox PA (1994) The surface science of metal oxides.
 Cambridge University Press, Cambridge
- El-Shobaky GA, Mostafa AA (2003) Solid-solid interactions in Fe₂O₃/MgO system doped with aluminium and zinc oxides. Thermochim Acta 408:75

