



Results of the material screening program of the NEXT experiment

T. Dafni^{a,b,*}, V. Álvarez^c, I. Bandac^a, A. Bettini^{a,d}, F.I.G.M. Borges^e, M. Camargo^f, S. Cárcel^c, S. Cebrián^{a,b}, A. Cervera^c, C.A.N. Conde^e, J. Díaz^c, R. Esteve^g, L.M.P. Fernandes^e, M. Fernández^h, P. Ferrario^c, A.L. Ferreiraⁱ, E.D.C. Freitas^e, V.M. Gehman^j, A. Goldschmidt^j, H. Gómez^{a,b}, J.J. Gómez-Cadenas^c, D. González-Díaz^{a,b}, R.M. Gutiérrez^f, J. Hauptman^k, J.A. Hernando Morata^l, D.C. Herrera^{a,b}, F.J. Iguaz^{a,b}, I.G. Irastorza^{a,b}, L. Labarga^m, A. Laing^c, I. Liubarsky^c, D. Lorca^c, M. Losada^f, G. Luzón^{a,b}, A. Marí^g, J. Martín-Albo^c, A. Martínez^c, G. Martínez-Lema^l, T. Miller^j, F. Monrabal^c, M. Monserrate^c, C.M.B. Monteiro^c, F.J. Mora^g, L.M. Moutinhoⁱ, J. Muñoz Vidal^c, M. Nebot-Guino^c, D. Nygren^j, C.A.B. Oliveira^j, J. Pérezⁿ, J.L. Pérez Aparicio^o, J. Renner^j, L. Ripoll^p, A. Rodríguez^{a,b}, J. Rodríguez^c, F.P. Santos^e, J.M.F. dos Santos^e, L. Seguí^{a,b}, L. Serra^c, D. Shuman^j, A. Simón^c, C. Sofka^q, M. Sorel^c, J.F. Toledo^g, J. Torrent^p, Z. Tsamalaidze^r, J.F.C.A. Velosoⁱ, J.A. Villar^{a,b}, R.C. Webb^q, J.T. White^q, N. Yahlali^c

^aLaboratorio Subterneo de Canfranc, 22880 Canfranc Estacin, Huesca, Spain

^bLaboratorio de Física Nuclear y Astropartículas, Universidad de Zaragoza, 50009 Zaragoza, Spain

^cInstituto de Física Corpuscular (IFIC), CSIC & Universitat de València, 46980 Paterna, Valencia, Spain

^dPadua University and INFN Section, Dipartimento di Fisica G. Galilei, 35131 Padova, Italy

^eDepartamento de Física, Universidade de Coimbra, 3004-516 Coimbra, Portugal

^fCentro de Investigaciones en Ciencias Básicas y Aplicadas, Universidad Antonio Nariño, Bogotá, Colombia

^gInstituto de Instrumentación para Imagen Molecular (I3M), U. Politècnica de València, 46022 Valencia, Spain

^hCentro de Investigaciones Energéticas, Medioambientales y Tecnológicas (CIEMAT), 28040 Madrid, Spain

ⁱInstitute of Nanostructures, Nanomodelling and Nanofabrication (i3N), U. de Aveiro, 3810-193 Aveiro, Portugal

^jLawrence Berkeley National Laboratory (LBNL), Berkeley, California 94720, USA

^kDepartment of Physics and Astronomy, Iowa State University, Ames, Iowa 50011-3160, USA

^lInstituto Gallego de Física de Altas Energías (IGFAE), U. de Santiago de Compostela, 15782 Santiago de Compostela, Spain

^mDepartamento de Física Teórica, Universidad Autónoma de Madrid, 28049 Madrid, Spain

ⁿInstituto de Física Teórica (IFT), UAM/CSIC, 28049 Madrid, Spain

^oDpto. de Mecánica de Medios Continuos y Teoría de Estructuras, U. Politècnica de València, 46071 Valencia, Spain

^pEscola Politècnica Superior, Universitat de Girona, 17071 Girona, Spain

^qDepartment of Physics and Astronomy, Texas A&M University, Texas 77843-4242, USA

^rJoint Institute for Nuclear Research (JINR), 141980 Dubna, Russia

Abstract

The Neutrino Experiment with a Xenon TPC (NEXT), intended to investigate neutrinoless double beta decay, requires extremely low background levels. An extensive material screening and selection process to assess the radioactivity of components is underway combining several techniques, including germanium γ -ray spectrometry performed at the Canfranc Underground Laboratory; recent results of this material screening program are presented here.

Keywords: Double beta decay, Radiopurity, Germanium gamma spectrometry

1. Introduction

The NEXT experiment [1] will operate at the Laboratorio Subterneo de Canfranc (LSC), Spain, a high-

pressure xenon time projection chamber (TPC) to search for neutrinoless double beta decay events of ^{136}Xe using 100 kg of enriched xenon at 90%. As in any experiment investigating rare event phenomena, ultra-low background conditions are a must and materials used in

*Attending speaker

the set-up have to be carefully selected. A thorough material screening program was undertaken to evaluate the radioactivity of all the relevant components of NEXT [2, 3]; new results are presented here.

This screening program is mainly based on germanium γ -ray spectrometry using ultra-low background detectors from the Radiopurity Service of LSC (in particular, those named GeOroel, GeAnayet, GeTobazo, GeLataca) operated at a depth of 2450 m.w.e.. Detectors are p-type close-end coaxial 2.2-kg High Purity germanium detectors, from Canberra France. For the measurements presented here, shield consisted of 5 cm of copper in the inner part surrounded by 20 cm of low activity lead, with nitrogen flush to avoid airborne radon intrusion. Detection efficiency is estimated for each sample by GEANT4 simulation. Complementing germanium spectrometry results, measurements based on Glow Discharge Mass Spectrometry (GDMS) and Inductively Coupled Plasma Mass Spectrometry (ICPMS) have been also carried out. GDMS is performed by Evans Analytical Group in France, providing concentrations of U, Th and K. An ICPMS measurement was made at CIEMAT (Unidad de Espectrometria de Masas) in Spain.

2. Results

Materials analyzed deal with the shielding, pressure vessel, field cage and electroluminescence (EL) components and the energy and tracking readout planes. Results obtained after those presented in [2, 3] are summarized in table 1 and described in the following; for germanium measurements, reported errors correspond to 1σ uncertainties and upper limits are given at 95% C.L.. Uncertainties for GDMS results are typically of 20%.

Lead and copper from different suppliers to be used as shielding were studied [2, 3]. Finally, refurbished lead from the OPERA experiment with 80 Bq/kg of ^{210}Pb will be used for external shielding (#1-2) and CuAl (or ETP) copper will be used for inner shield (#3-4). For the pressure vessel, several samples of 316Ti Stainless Steel were initially screened with germanium detectors: 10-mm-thick for body, 15-mm-thick for end-caps, 50-mm-thick for flanges. Now, complementary results have been obtained from GDMS analysis (#5-7).

Concerning the field cage and EL region, several types of plastics [2, 3] and High Density Polyethylene (PE500) for field cage (#8) have been screened; HD polyethylene has been analyzed also by ICPMS (#9). In addition, results for silver epoxy (CW2400) (#10) and

ETP copper for field cage, in rod (#11) and sheet (#12), have been obtained.

The tracking readout in NEXT is based on SiPMs in kapton Printed Circuit Boards (PCB). PCB boards (made of cuflon [2, 3] or kapton and copper (#13)) and different electronic components (capacitors, resistors, connectors, solder paste [2], NTC temperature sensors (#14) and blue LEDs (#15)) have been screened with germanium detectors. Plexiglas sheets which could be placed in front of boards have been also considered (#16). At the opposite side of the vessel, the energy readout is based on photomultipliers (PMTs); 34 (out of 60) Hamamatsu R11410-10 PMTs have been already screened in 3-unit groups (#17) showing equivalent activity. Shappire windows [3] and copper have been studied: CuAl (or ETP) for PMT cans (#3-4) and CuCl (or OF) for plates (#18). Several components for PMT bases have been also analyzed: capacitors (#19), resistors (#20), pin receptacles (#21) and thermal epoxy (#22).

In summary, complementary activity measurements based on ICPMS, GDMS and germanium spectrometry performed at LSC have been carried out to help both in the design of the set-up and in the construction of the background model of the NEXT experiment. Radiopure enough samples of copper for inner shielding, stainless steel for pressure vessel and polyethylene for field cage have been found: expected contributions from $^{214}\text{Bi}+^{208}\text{Tl}$ at the region of interest are 9.7, 2.9 and $9.4 \cdot 10^{-5} \text{ keV}^{-1} \text{ kg}^{-1} \text{ y}^{-1}$ respectively. An extensive work has been carried out, but the screening program is still going on and SiPMs and shielding structure components are now under analysis.

Acknowledgments

The NEXT Collaboration acknowledges funding support from: the MINECO of Spain under Grants CONSOLIDER-Ingenio 2010 CSD2008-0037 (CUP), FPA2009-13697-C04-04, and FIS2012-37947-C04; the Director, Office of Science, Office of Basic Energy Sciences of the US DoE under Contract no. DE-AC02-05CH11231; and the Portuguese FCT and FEDER through the program COMPETE, Projects PTDC/FIS/103860/2008 and PTDC/FIS/112272/2009.

References

- [1] J. J. Gomez Cadenas et al, *Advances in High Energy Physics* vol. 2014 907067.
- [2] V. Alvarez et al, *JINST* 8 (2013) T01002.
- [3] V. Alvarez et al, *AIP Conf. Proc.* 1549 (2013) 46.

Material	Supplier	Technique	units	^{238}U	^{226}Ra	^{232}Th	^{228}Th	^{235}U	^{40}K	^{60}Co	^{137}Cs
1 Pb	Britannia	Ge	mBq/kg		<0.83		<0.48		<1.3	<0.08	
2 Pb	Britannia	GDMS	mBq/kg	0.35		0.094			0.12		
3 Cu	Lugand Aciers	Ge	mBq/kg	<4.1	<0.16	<0.15	<0.13	<0.17	<0.37	0.04±0.01	<0.04
4 Cu	Lugand Aciers	GDMS	mBq/kg	<0.012		<0.004			0.062		
5 316Ti SS, 10mm	Nironit	GDMS	mBq/kg	<5.0		<0.12			<0.16		
6 316Ti SS, 15mm	Nironit	GDMS	mBq/kg	<9.9		<0.41			<0.12		
7 316Ti SS, 50mm	Nironit	GDMS	mBq/kg	<7.4		<0.12			<0.09		
8 Polyethylene	In2Plastics	Ge	mBq/kg	<18	<0.88	<0.81	<0.70	<0.4	<3.4	<0.14	<0.14
9 Polyethylene	Simona	ICPMS	mBq/kg	<0.062		<0.021					
10 Silver epoxy	Circuit Works	Ge	mBq/kg	<1.0 10 ³	13.6±2.8	<18	< 16	<4.5	<52	<1.9	<2.2
11 Cu, rod	Lumetalplastics	GDMS	mBq/kg	0.66±0.09		0.45±0.08			0.16		
12 Cu, sheet	Lumetalplastics	GDMS	mBq/kg	0.041±0.007		0.014±0.002			0.031		
13 Kapton-Cu PCB	Flexiblecircuits	Ge	mBq/unit	<1.3	0.031±0.004	0.027±0.008	0.042±0.004		12.1±1.2	<0.01	<0.01
14 NTC sensors	Murata	Ge	mBq/unit	<96	<1.5	<1.6	<1.3	<0.3	<2.9	<0.2	<0.2
15 LEDs	Osram Ge		mBq/unit	<90	1.4±0.2	3.5±0.4	3.0±0.3	<0.6	<4.0	<0.2	<0.3
16 Plexiglas/PMMA	Evonik	Ge	mBq/kg	<208	<2.2	<3.9	<3.4	<1.1	<8.1	<0.4	<0.6
17 PMTs	Hamamatsu	Ge	mBq/unit	<87	<0.96	<2.5	0.69±0.35	0.4±0.2	11.5±2.1	3.7±0.3	<0.3
18 Cu	Lugand Aciers	GDMS	mBq/kg	0.025±0.005		0.015±0.004			0.19		
19 Capacitors	AVX	Ge	mBq/unit	<360	72±3	749±3	32±2		71±9	<1	<1
20 Resistors	Finechem	Ge	mBq/unit	85±23	4.1±0.3	5.6±0.5	4.4±0.3		83.6±8.7	< 0.2	104±11
21 Pin receptacles	Farnell	Ge	mBq/unit	217±42	<1.1	5.6±0.5	4.5±0.4	6.1±0.5	20.5±2.4	<0.3	<0.2
22 Thermal epoxy	Electrolube	Ge	mBq/kg	(1.0±0.2)10 ³	169.4±7.9	52.1±3.7	54.4±3.2		105±12	<1.1	<1.3

Table 1: Activities measured in relevant materials for NEXT following different techniques. GDMS and ICPMS results were derived from U, Th and K concentrations. Germanium γ -ray spectrometry results reported for ^{238}U and ^{232}Th correspond to the upper part of the chains (derived from ^{234m}Pa and ^{228}Ac emissions) and those of ^{226}Ra and ^{228}Th give activities of the lower parts.