

Available online at www.sciencedirect.com**ScienceDirect**

Procedia Computer Science 83 (2016) 203 – 211

Procedia
Computer ScienceThe 7th International Conference on Ambient Systems, Networks and Technologies
(ANT 2016)

Literature Review of Advancements in Adaptive Ramp Metering

Khaled Shaaban^{a*}, Muhammad Asif Khan^a, Rida Hamila^a^a*Qatar University, PO Box 2713, Doha, Qatar*

Abstract

Over a period spanning more than 30 years, several ramp metering algorithms have been developed to improve the operation of freeways. Many of these algorithms were deployed in several regions of the world, and field evaluations have shown their significance to improve traffic conditions on freeways and ramps. Previous reviews of ramp metering algorithms focused more on the research outcomes and evaluations of traditional metering algorithms developed in the early stage of ramp metering research. The purpose of this paper is to cover the more recent developments in ramp metering in relation to the traditional metering strategies. Several local and coordinated ramp metering algorithms were reviewed. In summary, Asservissement Linéaire d'Entrée Autoroutière (ALINEA) was found to be the most widely deployed local ramp metering strategy. The algorithm is simple and implementation costs less than other strategies. It also guarantees the targeted performance goals provided that the on-ramp has sufficient storage. Several extensions were proposed in the literature to fine-tune its performance. Among the coordinated metering strategies, zone based metering is simple to implement and easy to re-configure. System-wide adaptive ramp metering (SWARM) algorithm is more sensitive to calibrate for accurate prediction of traffic states. Heuristic ramp-metering coordination (HERO) algorithm can be useful if both local and coordinated control are desired particularly if the local control is using ALINEA. Fuzzy logic based algorithms are gaining popularity because of the simplicity and the fast re-configuration capability. Advanced real time metering system (ARMS) seems theoretically promising because of its proactive nature to prevent congestion; however, its performance is highly dependent upon accurate predictions. Finally, some guidelines were proposed for future research to develop new proposals and to extend the existing algorithms for guaranteed performance solutions.

© 2016 The Authors. Published by Elsevier B.V. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

Peer-review under responsibility of the Conference Program Chairs

Keywords: freeway operation; signal control; queue management; congestion management; algorithms; coordination strategy; traffic control

* Corresponding author. Tel.: +974-4403-4185; fax: +974-4403-4172.
E-mail address: kshaaban@qu.edu.qa

1. Introduction

Ramp metering is a ramp management strategy to control the number of vehicles entering a freeway using a traffic signal. They are programmed with a much shorter cycle time to allow a single vehicle or a small platoon of vehicles (usually two or three) per green phase. The metering rate is based on the traffic volume and speed on the freeway. On freeways, the goal is to increase throughput, speed, and capacity to maintain the optimum operation of the freeway. Ramp meters are usually employed to control vehicles at the on-ramp to enter the freeway (mainline) to mitigate the impact of the ramp traffic on the mainline flow. However, ramp meters can also be used to control traffic flow from the freeway to freeway and arterial to ramp and freeway. The selection of appropriate ramp metering strategy is based on the needs and goals of the regional transportation agency.

The simplest form of ramp meters works based on pre-set metering rates. The metering rates are either fixed or variable rates that are assigned on a defined schedule based on some historical traffic data. Fixed time or pre-timed metering addresses the recurring congestion problem but fails in case of non-recurring congestion. A better approach to ramp metering is adaptive or traffic responsive ramp metering where variable metering rates are allocated to ramps in response to actual traffic conditions. Traffic responsive metering uses present traffic conditions to adjust its metering rate. Traffic data is collected using loop detectors or any other detection system in real time. The metering rate is either calculated based on some algorithms or selected from a pre-defined matrix. Traffic responsive control can be implemented in both local and coordinated fashion.

This paper is divided into two main sections. The first section presents a review of the adaptive ramp metering systems developed in the earlier stage and their evaluations. The second section provides a review of the recent developments in ramp metering strategies.

2. Traditional Ramp Metering Algorithms

This section describes the traffic responsive algorithms that were developed in the early stages. The working principles and control logics of these algorithms are explained and compared in several aspects in Table 1.

2.1. *Asservissement Linéaire d'Entrée Autoroutière (ALINEA)*

ALINEA is a local traffic responsive feedback control algorithm for ramp metering developed by Papageorgiou et al.¹. The algorithm takes freeway occupancy as input and computes the metering rate as a control variable that varies in response to changes in occupancy. ALINEA uses a single detector per lane of the freeway installed downstream at a distance of 40 meters or 400 meters. The downstream detectors measure the occupancy rate and send to the controller at regular intervals usually 40 seconds. The controller computes the difference between desired occupancy threshold and measured occupancy and determines the metering rate for the next interval (40 seconds). The algorithm also considers the previous interval metering rate while computing the metering rate for the next interval to avoid major variations in the metering rates for smooth operation. The goal of ALINEA is to set the metering rate at which the flow will not exceed the freeway capacity.

ALINEA performs well in maintaining a desired flow at the freeway. However, it creates long queues at the on-ramp that causes bottlenecks. Zhang et al.² proposed an extension to basic ALINEA to avoid the ramp traffic to exceed the capacity. Smaragdis and Papageorgiou³ proposed three more modifications FL-ALINEA, UP-ALINEA and X-ALINEA/Q to the standard version for improving the performance in various scenarios.

FL-ALINEA uses the mainline flow from the downstream detectors instead of occupancy while UP-ALINEA uses occupancy values from the upstream detectors when the downstream detectors are not available. X-ALINEA/Q addresses the problem of long queue formation on the ramp when the freeway is saturated that causes restricted metering rates. Smaragdis et al.⁴ proposed another extension AD-ALINEA, which addresses the issue of constant desired occupancy value that might change in real time due to weather conditions or traffic compositions.

Several field studies evaluate the performance of ALINEA. Chu et al.⁵ evaluated ALINEA in a simulation environment over a stretch of the I-405 freeway in California where ALINEA shows good performance under both recurrent and non-recurrent congestion scenarios. Caglar and Hilmi⁶ used ALINEA on Bosphorus Strait crossing bridges on State Road D100 and Europe Route E80 between Europe and Turkey. Field results showed that ALINEA

regulates the ramp flow and keeps the mainline flow under capacity in the stable mode to prevent congestion. Zheng et al.⁷ evaluated ALINEA on Shanghai Urban Expressway and successfully increased the mainline speed and reduced downstream congestion.

2.2. METALINE

METALINE¹¹ is an extension of ALINEA for coordinated control of ramp meters, proposed by Papageorgiou et al. (1990). The algorithm computes the metering rates using the list of occupancy values from several detectors on different ramps. The algorithm is similar to ALINEA in its response to the difference in the occupancy in two successive time intervals making it more sensitive to traffic variations. The disadvantage of METALINE is the complex calibration of the algorithm for multiple ramps. METALINE was deployed in Paris, France (1991)¹¹ on the three on-ramps of a six-kilometer freeway in Boulevard Périphérique. The results showed an increase in the mainline speed. In Milwaukee¹⁰, METALINE was used on several freeways and showed improved performance in traffic. A field evaluation of METALINE in Netherlands, Amsterdam was conducted. However, the results are not published for organizational reasons.⁹

2.3. Bottleneck Algorithm

The algorithm was first developed by Washington State Department of Transportation by Jacobson et al.¹². The algorithm works at both local and system-wide levels. At the local level, the algorithm compares the free demand at upstream of the ramp and capacity at the downstream of the ramp and thus optimum metering rates are computed that ensure that demand does not exceed capacity. At the coordinated level, the control algorithm is activated when the occupancy at a potential bottleneck area exceeds the threshold and the area upstream of the bottleneck is storing vehicles. The coordinated control determines the metering rates for all meters in the area or zone to reduce the volume of vehicles entering from the ramps to the bottleneck area equal to the volume in the upstream queue on the mainline. Once the two metering rates are computed for each ramp using local and coordinated control, the more restrictive rate is applied.

2.4. Zone Algorithm

Zone algorithms^{13, 14} divide the freeway into multiple zones of various lengths from 3-6 miles with several metered and non-metered ramps. The algorithm maintains the density on mainline below a certain threshold by controlling the inflow and outflow in the zone. The collective metering rate is computed from the inflow and outflow values and then distributed among all ramp meters using the pre-defined ramp factor. One of the variants of zone metering is Stratified Zone metering¹⁷ that uses density inputs obtained at real time on upstream of on-ramps, at mainline off-ramps, and on the mainline. The goal is to control the total volume of a segment of a freeway called a “zone”. The increase in the mainline density is balanced by lowering the metering rates in the particular zone.

2.5. HELPER Algorithm

Lipp et al.¹⁸ proposed a local traffic-responsive algorithm with the added feature of central override control for system-wide implementation over the entire freeway corridor. All the on-ramps are divided into six groups. Six metering rates are defined that can be selected by individual ramp meters on the basis of local traffic conditions. If the queue on a ramp exceeds a specified threshold value for three consecutive time intervals, the central override feature is activated that reduce the metering rate by one level. This process continues until the problem is solved. If the queue persists, all the upstream ramps will be overridden and will operate with more restrictive metering levels.

The algorithm was first deployed in the Denver area, Colorado in 1981 on I-10 freeway¹⁹. A comprehensive evaluation showed the significance of the central override feature in congestion reduction for low speeds (less than 90 km/hr) while less or no significance of the centralized control for speed greater than 90 km/hr.

2.6. System-Wide Adaptive Ramp Metering (SWARM) Algorithm

SWARM was developed by Paesani et al.²² uses traffic forecasting to determine the metering rates. The algorithm works in two operational levels, a coordinated control (SWARM1) and local control (SWARM2). In SWARM1, traffic data is collected, and future state of traffic density is estimated using linear regression. For the non-linear relations between the data set, Kalman Filter is applied. The coordinated metering rates are computed using current

and desired density values. In SWRAM2, metering rates are calculated based on density values computed locally from the distance headway measurements. Then the more restrictive metering rate (calculated in SWARM1 or SWARM2) is applied.

2.7. Fuzzy Logic Algorithm

The fuzzy logic algorithm is deployed in Seattle freeway by Taylor and Meldrum^{24, 25, 26, 27}. This kind of control algorithms is well suited to situations where the accurate system model is not available. The fuzzy logic used in this algorithm takes real time measured values from detectors and convert them to different textual values based on the values of measured inputs. This is called fuzzification of inputs. Based on these fuzzified inputs the controller logic determines the control actions that are finally defuzzified to determine the real value of metering rates.

Table 1: Summary of Traditional Ramp Metering Algorithms

Algorithm	Year	Authors	Type	Control Inputs	Evaluations		
					Authors	Simulation	Field
ALINEA 1, 3, 4, 6, 7, 8, 11	1997	Papageorgiou et al.	Local w/Feedback	Occupancy	Papageorgiou et al. ^{1,7}	✓	✓
					Chu et al. ⁵	✓	X
					Zheng et al. ⁵⁵	✓	X
					Caglar and Hilmi ⁵⁶	✓	X
METALINE7 ^{9,10,11}	1990	Papageorgiou et al.	Coordinated w/Feedback	Occupancy	Papageorgiou et al. ¹¹	✓	✓
					H.Talee et al. ⁹	✓	✓
					JHK Associates ¹⁰	✓	X
Bottleneck ¹²	1989	Jacobsen et al.,	Coordinated	Occupancy	WDOT, 1981 ¹²	✓	X
Zone Algorithm 13, 14, 15, 16, 17	1989	Stephanedes,	Local or Coordinated	Flow rate	Minnesota DOT, 1989 ¹⁴	✓	✓
HELPER 18, 19, 20, 21	1991	Lipp et al.	Coordinated	Occupancy	Corcoran et al., 1989 ¹⁹	✓	X
					Colorado DOT, 1983 ²⁰	✓	X
SWARM 22, 23	1997	Paesani et al.	Coordinated (Prediction)	Density	Planned in California and Los Angeles ²³	✓	X
FUZZY 24, 25, 26, 27	1998	Taylor and Meldrum	Coordinated	Multiple	WDOT, 1995 ²⁷	✓	✓
Linear Programming ^{28, 29}	1995	Yoshino et al.	Coordinated	Not specified	Yoshino et al. ²⁸	✓	X
Dynamic Ramp Metering ³⁰	1997	Chen et al.	Coordinated	Multiple	O Chen et al., 1997	✓	X
ARMS 31, 32, 33	1993	Liu et al.	Coordinated	Flow rate	Planned for Texas ³³	✓	X
COMPASS ^{34, 35}	1975	Canada DoT	Coordinated	Occupancy	Carroll et al., 1993	✓	X
Linked Algorithm ^{36, 37, 38, 39}	1998	Taylor et al.	Coordinated w/Feedback	Occupancy and flow	Banks, 1993 ^{37, 38}	✓	X

2.8. Linear Programming

The algorithm was first developed and implemented by Yoshino et al.²⁸ on the Hanshin Expressway in Japan. The algorithm used detectors on all on and off ramps. The algorithm does not require any communication between ramp meters. The metering rates for all ramps are computed using complex functions.

2.9. Dynamic Ramp Metering

Dynamic control model of ramp metering was first proposed by Chen et al.³⁰ that include both local and coordinated control of ramps. The coordinated control is a kind of strategic control that uses a rolling horizon based predictive algorithm to minimize system travel time. The local control is a tactical control that sets its metering rates to maintain the traffic conditions that are provided by system-wide or coordinated control.

2.10. Advanced Real Time Metering System (ARMS)

ARMS, developed by Liu et al.^{32,34} at Texas Transportation Institute, is a proactive metering algorithm that is designed to mitigate the risk of congestion. The algorithm predicts the traffic conditions and potential bottlenecks and resolves it using real time mainline flow information. ARMS is more complex relative to other ramp metering algorithms. However, the features are more appealing.

2.11. COMPASS

The Compass algorithm was first developed in Toronto Canada (1975). The details of this algorithm are explained in Michael et al.³⁴. The metering algorithm allows both manual and automatic control of metering rates. The automated control function calculates metering rates at regular intervals of 30 seconds based on local mainline occupancy, downstream mainline occupancy, and upstream mainline occupancy. Each measured value of occupancy is compared to thresholds values stored in a look-up table to find the metering rates. If metering rates from the table for each parameter are different, the most restrictive rate is applied. The algorithm uses queue spillback detection to prevent queue formation on ramps.

2.12. Linked Algorithm

The algorithm, first developed by Tayler et al.²⁴, is based on the non-minimal state space (NMSS) approach of control design. The author proposed the use of proportional integral-plus linear quadratic (PIP-LQ) type of adaptive optimal controllers. The controller computes the metering rates as output by minimizing a linear-quadratic function. The inputs to the control function are ramp flows, occupancy values from detectors from the entire control area.

3. Recent Advancements in Ramp Metering

The main research challenge in ramp metering is to design a metering strategy that can maintain a good balance between two inversely proportionally parameters: freeway congestion and ramp queue⁵⁴. This section presents the most-recent research trends in the development of ramp metering for local and coordinated control to overcome this challenge. These algorithms are explained and compared in several aspects in Table 2.

3.1. Heuristic Ramp-Metering Coordination (HERO)

The HERO algorithm was first developed by Papamichail et al.⁴⁰ and deployed at Monash Freeway in Australia. HERO is the extended version of ALINEA algorithm for coordinated ramp control. In HERO, the critical occupancy is measured at merge area of ramps. Each on-ramp is independently controlled using ALINEA, but all ramps are connected to each other via a central controller. When a bottleneck occurs on the mainstream near an on-ramp (queue length on an on-ramp (master) reaches a predefined threshold value), the central controller recruits the on-ramp in bottleneck segment as Master ramp and some of its upstream on-ramps as Slaves. The algorithms now try to increase the capacity of the master on-ramp.

3.2. Proportional Integral ALINEA (PI-ALINEA)

The PI-ALINEA proposed by Wang et al.⁴² is an extended version of ALINEA to overcome one of its shortcomings. Basic ALINEA operates to reduce the mainline congestion at most a few hundred meters downstream

of the merge point. However, if the bottleneck occurs further downstream from the location of ALINEA occupancy detectors, ALINEA will be unable to detect and thus respond to the congestion that can increase with time to form a bottleneck. Simulations study⁴⁴ shows improved performance of PI-ALINEA as compared to ALINEA in both local and distant bottlenecks.

3.3. ALINEA with Speed Discovery

Rui et al.⁴⁵ proposed this algorithm to address the inherited problem with ALINEA with restricted metering rates that leads to longer queue at the on-ramp. Using queue management override feature with ALINEA, the queue can be discharged, but it again creates bottlenecks at merge area. Rui et al. proposed the concept of a mainline speed recovery with suspending queue management temporarily. However, when a potential breakdown is identified at the mainline, the algorithm gives control of the metering rate back to the standard ALINEA module. The study suggests that the mainline speed should be less than 45 Km/hr and suspension time 300 seconds for optimum operation of the control. Simulation results in AIMSUN showed the improved speed and reduced travel time on mainline as compared to standard ALINEA.

3.4. Zippered Control Strategy (ZCS)

The ZCS proposed by Huadong et al.⁴⁶ used cellular automata based capacity model simulated in microsimulation software PTV VISSIM. The objective of the proposed strategy is to increase the capacity of the on-ramp junction. The model is based on a fair distribution of road priority between the mainline traffic and on-ramp traffic. The model has no field evaluations, and not enough details about simulation data are provided.

3.5. Genetic Fuzzy Logic Control (GFLC)

The idea of adaptive fuzzy logic control based on genetic algorithm was proposed by Amir et al.⁴⁷. The fuzzy controller is used with the additional implementation of variable speed limits (VSLs) to control congestion and regulate the freeway traffic flow. The results of the fuzzy controller with and without VSLs were compared with no control and standard ALINEA implementation on the same network with same base conditions. The results showed that the genetic fuzzy logic based ramp metering results in smooth traffic states. The comparisons showed an increase in TTS (5% Without Using VSLs and 15.5% With VSLs) as compared to ALINEA. Fang et al.⁴⁸ proposed a genetic algorithm (GA) based tuning for the fuzzy logic controller for the isolated ramp. The GA-based tuning is repeated after 5 min intervals for any change in flow density on the on-ramp. The algorithm was tested in AIMSUN's based simulation and the results showed improvement in total travel time as compared to the fuzzy logic controller without using the GA. In Jianxin et al.⁴⁹, the fuzzy logic controller is used with particle swarm optimization method to minimize the weighted total-time-spent (WTTS) on the freeway and ramp. The controlled logic was used for local ramp control and simulation results from microsimulation software PARAMICS showed a good balance between freeway and on-ramp traffic.

3.6. Dual Heuristic Programming Control (DHPC)

Dongbin et al.⁵⁰ proposed a DHPC method to solve recurrent and non-recurrent congestion using neural networks. The proposed algorithms were tested using mathematical models on a hypothetical freeway segment. The results of DHPC compared to ALINEA shows convincing improvements in freeway operation. The authors emphasized on the evaluation of DHPC method in microsimulation environments.

3.7. Iterative Local Control (ILC)

Zhongsheng et al.⁵¹ proposed ILC based ramp metering control strategy that according to the authors has a simple learning approach, effective, inter-operable with ALINAE and other feedback-based control logics. The algorithm also requires less historical data as compared to fuzzy logic and neural networks based control algorithms. The use of ILC as an add-on to basic ALINEA is described as a complementary modularized approach to enhance the performance of ALINAE and ILC using a macroscopic simulation of the local ramp and freeway.

3.8. Additive Increase Multiplicative Decrease (AIMD)Algorithm

The AIMD algorithm is a coordinated ramp metering algorithm developed by Yin Hai et al.⁵² at Washington. The algorithm is inspired by the computer networks congestion control strategy. The algorithm reduces the on-ramp flow only to a fraction of ramp demand by limiting metering rates when congestion occurs and then gradually increase the metering rates avoid queue spillover. The algorithm was evaluated using VISSIM simulation of Seattle's I-5 and I-90 freeways. The results compared with the fuzzy logic algorithm show a 28.2% reduction in travel time⁵².

Table 2: Comparison of Recent Ramp Metering Algorithms

Algorithm	Year	Author	Type	Evaluation Methods	Description
HERO ^{40, 41}	2010	Papamichail et al.	Local and Coordinated,	Field Implementation in Monash Highway, Australia	ALINEA based coordinated control metering, with master and slave on-ramps during congestion.
PI-ALINEA ^{42, 43, 44}	2014	Wang et al.	Local / Feedback-based	Simulation ^{42, 44} METANET ⁴³	ALINEA extension for efficient detection and elimination of distant downstream congestion
ALINEA with Speed Recovery ⁴⁵	2012	Rui et al.	Local	Simulation/AIMSUN	Mainline speed recovery with suspending queue management temporarily.
ZCS ⁴⁶	2013	Huadong et al.	Local	Simulation/VISSIM	Cellular automata based capacity model for fair distribution of priority between mainline and ramp traffic
GFLC ^{47, 48, 49}	2012	X.F. Yu et al.	Local or Coordinated	mathematical model ⁴⁷ AIMSUN ⁴⁸ PARAMICS ⁵¹	Fuzzy Logic controller based on GA ^{47, 48} and swarm optimization ⁴⁹
DHPC ⁵⁰	2011	Dongbin et al.	Coordinated	mathematical model	Neural network based dual heuristic programming model to solve recurrent and non-recurrent congestion
ILC ⁵¹	2011	Zhongsheng et al.	Coordinated	mathematical model	Iterative control of isolated ramp and integration with ALINEA for improved performance
AIMD ⁵²	2008	Yin Hai et al.	Coordinated w/Feedback	Simulation/ VISSIM	Using computer networks congestion control policy to control congestion while preventing ramp queues

4. Discussion and Future Directions

In this paper, several local and coordinated ramp metering algorithms are discussed. Based on simulation results and field evaluations^{1, 5 7 55, 56}, ALINEA showed to be widely deployed local ramp metering strategy. Several extensions^{3, 4, 42, 43, 44, 45} were proposed to fine-tune its performance in the diverse road and traffic conditions. Among the coordinated metering strategies, zone based metering is simple to implement and easy to re-configure. SWARM is more sensitive to calibrate for accurate prediction of traffic states. HERO algorithm can be useful if both local and coordinated control are desired particularly if local control is using ALINEA. Fuzzy logic based algorithms are gaining popularity because of simplicity, the fast re-configuration capability, and the integration of neural networks and genetic algorithms with fuzzy logic^{47, 48, 49}. ARMS seems theoretically a promising algorithm because of its proactive nature to prevent congestion. Some guidelines are proposed for future research either to develop new proposals or to extend the existing algorithms for guaranteed performance solutions:

- The feedback based algorithms (e.g. ALINEA) eliminate downstream congestion if properly configured despite the distance from the on-ramp. However, it cannot detect upstream initiated congestion. The UP-ALINEA can detect upstream congestion only to a certain level. Future research should consider more fine-tuning of ALINEA. Some useful guidelines for configuring ALINEA can be found in Papageorgiou et al⁵⁷.
- The success of achieving local ramp metering goals depends on the sufficient length of the on-ramp to store vehicles in the time of congestion on the freeway. If the ramp has limited storage, the queues on ramps will

extend to the arterial upstream. One possible approach to avoid this is the coordination of upstream traffic signal and ramp meter⁵⁹. However, many ramp metering algorithms have not addressed this phenomenon.

- c. Online simulation based metering can provide more realistic results, but the operational cost and acquisition of real-time traffic data in this method are a barrier for such implementations.
- d. The genetic fuzzy logic metering algorithms has the potential to be the future choice for ramp metering. However, these algorithms usually require more inputs than any other method. The probe vehicle approach⁵⁴ based on cellular phones' data (e.g. speed, location) of road users should be considered to reduce the cost of traffic data acquisition in real time.

References

1. Papageorgiou, M. , Hadj-Salem, H. and Blosseville, J.M., 1991," ALINEA: A Local Feedback Control Law for On-ramp Metering", Transportation Research Record, No. 1320, Transportation Research Board, Washington, D.C., pp. 58 – 64
2. Zhang, M., Kim, T., Nie, X., Jin, W., Chu, L., & Recker, W. (2001). Evaluation of on-ramp control algorithms. California Partners for Advanced Transit and Highways (PATH).
3. Smargdis, E. , Papageorgiou, M. and Kosmatopoulos, E., 2004,"A flow-maximizing adaptive local ramp metering strategy ", Journal of Transportation. Research., vol. 38, pp. 251 - 270.
4. Smaragdis, E. and Papageorgiou, M., 2003, "A series of new local ramp metering strategies", 82nd Annual Meeting of the Transportation Research Board, Washington DC, Paper No. 03 3171
5. Chu, L., Liu, H.X., Recker W., Zhang, M. (2004), Performance Evaluation of ITS Strategies Using Microscopic Simulation, ASCE Journal of Transportation Engineering, 130 (3).
6. Demiral, C., & Celikoglu, H. B. (2011). Application of ALINEA ramp control algorithm to freeway traffic flow on approaches to Bosphorus strait crossing bridges. *Procedia-Social and Behavioral Sciences*, 20, 364-371
7. Papageorgiou, M., Hadj-Salem, H., Middelham, F. ,1997, "ALINEA Local Ramp Metering – Summary of Field Results", Transportation Research Record 1603, Transportation Research Board, Washington, D.C.
8. "Eurocor and A10-West Coordinated Ramp Metering Near Amsterdam", F. Middelham, W.J. Schouten, J. Chrisoulakis, M. Papageorgiou, H. Haj-Salem, Proceedings of the 1st World Congress on Applications of Transport Telematics and IVHS, ERTICO, 1994.
9. "Design of a coordinated Ramp Metering System near Amsterdam", H. Taale, W.J.J.P. Schouten, 7th International Conference on Road Traffic Monitoring and Control, 1994.
10. "Milwaukee Monitor FTMS Software Design Report", JHK & Associates, 1998.
11. Papageorgiou, M., Blosseville, J. M., and Hadj Salem, H. ,1990, " Modeling and Real-time Control of Traffic Flow on the Southern Part of Boulevard Peripherique in Paris: Part II: Coordinated On-ramp Metering." Transportation Research. Vol. 24A, No. 5, pp. 361-370.
12. Jacobson, L. N., Henry, K. C., & Mehyar, O. (1989). Real-time metering algorithm for centralized control (No. 1232).
13. "Implementation of on-line Zone Control Strategies for optimal Ramp Metering in the Minneapolis Ring Road", Yorgos Stephanedes, 7th International Conference on Road Traffic Monitoring and Control, 1994.
14. "Ramp Metering by Zone - The Minnesota Algorithm", Richard Lau, Minnesota Department of Transportation, Revised in June 1997.
15. "Trunk Highway 169 Dynamic Ramp Metering Evaluation", Research Report 1998-14, Minnesota Department of Transportation, 1998
16. "Ramp up the Volume: Sophisticated Ramp Metering Techniques Promise to Alleviate Highway Congestion in Minnesota", ITS International, Issue No. 13, November-December 1997.
17. Lau R. (2001) Minnesota Department of Transportation: Stratified Metering Algorithm. Internal report. Minnesota Department of Transportation, Minneapolis
18. Louis Lipp, Lawrence Corcoran, and Gordon Hickman (1991) Benefits of Central Computer Control for the Denver Ramp Metering System, Transportation Research Board Record 1320
19. "Freeway Ramp Metering Effects in Denver", Corcoran, Lawrence and Gordon Hickman, 59th Annual Meeting of the Institute of Transportation Engineers, San Diego, Compendium of Technical Papers, 1989.
20. "I-25 Ramp Metering: Final Evaluation Report", Colorado Department of Transportation, District VI, November 1983.
21. "Bay Area Traffic Operations System – Ramp Metering Algorithm Report"; JHK and Associates, 1989.
22. Gordon Paesani, James Kerr, Pat Perovich, Edward Khosravi (1997) System Wide Adaptive Ramp Metering In Southern California, ITS America 7th Annual Meeting
23. "System Wide Adaptive Ramp Metering Algorithm - High Level Design" Final Report, Prepared by NET for Caltrans and FHWA, March 1996.
24. Taylor, C., D. Meldrum, and L. Jacobson, 1998. "Fuzzy Ramp Metering: Design Overview and Simulation Results," Transportation Research Record: Journal of the Transportation Research Board, 1634:10-18.
25. Taylor, C. and D. Meldrum, 2000a. "Algorithm Design, User Interface, and Optimization Procedure for a Fuzzy Logic Ramp Metering Algorithm: A Training Manual for Freeway Operations Engineers," Washington State Department of Transportation, Report WA-RD 481.1.
26. Taylor, C. and D. Meldrum, 2000b. "Evaluation of a Fuzzy Logic Ramp Metering Algorithm: A Comparative Study among Three Ramp Metering Algorithms Used in the Greater Seattle Area." Washington State Department of Transportation, Report WA-RD 481.2.

27. "Freeway Traffic Data Prediction using Artificial Neural Networks and Development of a Fuzzy Logic Ramp Metering Algorithm", Dieder Meldrum, Cynthia Taylor; Final Technical Report, Washington State Dept. of Transportation Report No. WA-RD 365.1, Washington 1995
28. "The Traffic Control System on the Hanshin Expressway"; Tsuyoshi Yoshino, Tsuna Sasaki, Toshiharu Hasegawa; Interfaces Magazine, Jan/Feb. 1995.
29. "Dynamic Traffic Control System for Urban Expressway with Constraint of Off-Ramp Queue Length"; Xiao-Guang Yang, Yasanori Iida, Nobuhiro Uno, Pi-Yun Yang; ITS World Conference Proceedings, Seoul 1996
30. O. Chen, A. Hotz and M. Ben-Akiva, Development and evaluation of a dynamic metering control model, IFAC Transportation Systems; Chania, Greece, 1997.
31. "A Successful Return To Ramp Metering - The Houston Experience", John M. Gaynor, Darrell Borchardt, ITS America 7th Annual Meeting, 1997.
32. "An Advanced Real Time Metering System (ARMS): The System Concept", Jyh-Charn Liu, Junguk Kim, Yiloeng Chen, Ying Hao, Sojung Lee, Taeyoung Kim, Michael Thomadakis, Texas Department of Transportation Report Number 1232-24, 1993.
33. "Advanced Freeway System Ramp Metering Strategies for Texas", Carroll Messer; Texas Department of Transportation Report Number 1232-23, 1993.
34. Jyh-Charn Liu, Junguk Kim, Yiloeng Chen, Ying Hao, Sojung Lee, Taeyoung Kim, Michael Thomadakis (1993) An Advanced Real Time Metering System (ARMS): The System Concept, Texas Department of Transportation Report Number 1232-24
35. "Mississauga FTMS System - Ramp Metering Algorithm", Ontario Ministry of Transportation, undated.
36. Notes on San Diego Ramp Metering System operations, From Don Day, Caltrans District 11.
37. "Effect of Response Limitations on Traffic-Responsive Ramp Metering", James Banks, TRB Record 1394, 1993.
38. "Evaluation of The Two-Capacity Phenomenon As A Basis For Ramp Metering", James Banks, December 1990.
39. "The History of Ramp Metering In California", S.H. Harvey, Caltrans District 11, July 1990.
40. Papamichail, I., M.Papageorgiou, V. Vong, & J. Gaffney (2010) Heuristic Ramp-Metering Coordination Strategy Implemented at Monash Freeway, Australia, Research Record: Journal of the Transportation Research Board, No. 2178, 2010, pp. 10–20.
41. Papamichail, I., & Papageorgiou, M. (2008). Traffic-responsive linked ramp-metering control. *Intelligent Transportation Systems, IEEE Transactions on*,9(1), 111-121.
42. Wang, Y., Kosmatopoulos, E.B., Papageorgiou, M., Papamichail, I., 2014. Local ramp metering in the presence of a distant downstream bottleneck: Theoretical analysis and simulation study. *IEEE Trans. Intell. Transp. Syst.*, 1–16.
43. Carlson, R. C., Papamichail, I., & Papageorgiou, M. (2014). Integrated feedback ramp metering and mainstream traffic flow control on motorways using variable speed limits. *Transportation research part C: Emerging technologies*, 46, 209-221.
44. Wang, Y., Kan, Y., Papageorgiou, M., & Papamichail, I. (2014, October). Local ramp metering with distant downstream bottlenecks: A comparative study. In *Intelligent Transportation Systems (ITSC), 2014 IEEE 17th International Conference on* (pp. 768-773). IEEE.
45. Jiang, R., Chung, E., & Lee, J. B. (2012). Local on-ramp queue management strategy with mainline speed recovery. *Procedia-Social and Behavioral Sciences*, 43, 201-209.
46. Tan, H., Yang, X., & Wu, A. (2013). The optimization of On-ramp Junction Capacity based on Zippered Control Strategy. *Procedia-Social and Behavioral Sciences*, 96, 1764-1773.
47. Ghods, A. H., Kian, A. R., & Tabibi, M. (2009). Adaptive freeway ramp metering and variable speed limit control: a genetic-fuzzy approach. *Intelligent Transportation Systems Magazine, IEEE*, 1(1), 27-36.
48. Yu, X. F., Xu, W. L., Alam, F., Potgieter, J., & Fang, C. F. Genetic fuzzy logic approach to local ramp metering control using microscopic traffic simulation. In *Mechatronics and Machine Vision in Practice, 2012 19th International Conference* (pp. 290-297). IEEE
49. Xu, J., Zhao, X., & Srinivasan, D. (2013). On optimal freeway local ramp metering using fuzzy logic control with particle swarm optimisation. *IET Intelligent Transport Systems*, 7(1), 95-104.
50. Zhao, D., Bai, X., Wang, F. Y., Xu, J., & Yu, W. (2011). DHP method for ramp metering of freeway traffic. *Intelligent Transportation Systems, IEEE Transactions on*, 12(4), 990-999.
51. Hou, Z., Xu, X., Yan, J., Xu, J. X., & Xiong, G. (2011). A complementary modularized ramp metering approach based on iterative learning control and ALINEA. *Intelligent Transportation Systems, IEEE Transactions on*, 12(4), 1305-1318.
52. Wang, Y., Perrine, K. A., & Lao, Y. (2008). Developing an area-wide system for coordinated ramp meter control (No. TNW2008-11). University of Washington, Transportation Northwest (TransNow).
53. Bogenberger K. and May, A.D.,1999, "Advanced Coordinated Traffic Responsive Ramp Metering Strategies", California PATH Paper UCB-ITS-PWP-99-19
54. Kattan, L., & Saidi, M. S. (2011). Design and Evaluation of Adaptive Coordinated Ramp Control Strategies on Deerfoot Trail Using Paramics Microsimulation.
55. Zheng, F., Du, Y., Sun, L. (2009). ALINEA-Based Urban Expressway On-ramp Local Metering Strategy. *ICCTP 2009: Critical Issues in Transportation Systems Planning, Development, and Management, 2009*, ASCE press
56. Demiral, C., & Celikoglu, H. B. (2011). Application of ALINEA ramp control algorithm to freeway traffic flow on approaches to Bosphorus strait crossing bridges. *Procedia-Social and Behavioral Sciences*, 20, 364-371.
57. Papageorgiou, M., Kosmatopoulos, E., Papamichail, I., & Wang, Y. (2008). A misapplication of the local ramp metering strategy ALINEA. *Intelligent Transportation Systems, IEEE Transactions on*, 9(2), 360-365.
58. Tian, Zongzhong. Development and Evaluation of Operational Strategies for Providing an Integrated Diamond Interchange Ramp-Metering Control System. Ph.D. Dissertation, Department of Civil Engineering, Texas A&M University, College Station, Texas, May 2004
59. Pooran, F., and R. Summer. Coordinated Operation of Ramp Metering and Adjacent Traffic Signal Control Systems. Report FHWA-RD-95-130. Federal Highway Administration, Washington, D.C., 1996.