

## Queues with Non-Stationary Input Stream

Tomasz Rolski, *Wrocław University, Wrocław, Poland*

We consider a single server system with general independent inter-arrival times and doubly stochastic Poisson arrivals. In this talk I shall survey the following issues:

- (i) ergodic properties for such queues and their stationary representations [5],
- (ii) bounds for the characteristics ([2] and references therein, [3], [6]),
- (iii) periodic Poisson queues as a special case of interest with emphasis on
  - inequalities and identities between queueing characteristics [1],
  - evaluation of characteristics.

## References

- [1] J.M. Harrison and A.J. Lemoine, Limit theorems for periodic queues, *J. Appl. Prob.* 14 (1977) 568–576.
- [2] T. Rolski, Comparison theorems for queues with dependent inter-arrival times, in: F. Baccelli and G. Fayolle, eds., *Modelling and Performance Evaluation Methodology*, Lecture Notes in Control and Information Sciences 60 (Springer-Verlag, Berlin, 1984), 42–67.
- [3] T. Rolski, Upper bounds for single server queues with doubly stochastic Poisson arrivals, *Math. Oper. Res.* 11 (1986) 442–450.
- [4] T. Rolski, Approximation of periodic queues, *J. Appl. Prob.* (1987, to appear).
- [5] T. Rolski, Ergodic properties of almost periodic Poisson processes, *Mathematical Institute, University of Wrocław*, preprint No. 71 (1986).
- [6] S.M. Ross, Average delay in queues with non-stationary Poisson arrivals, *J. Appl. Prob.* 15 (1978) 602–609.

## Probabilistic and Worst Case Analyses of Classical Problems of Combinatorial Optimization in Euclidean Space

J. Michael Steele, *Princeton University, Princeton, NJ, USA*

The classical problems which are considered are the traveling salesman problem (TSP), minimal spanning tree (MST), minimal matching, greedy matching, and minimal triangulation. Each of these problems is studied for finite sets of points in  $\mathbb{R}^d$ , and the feature of principal interest is the asymptotic behavior of the value of the associated objective function.

## Algebraic Duality of Markov Processes

Wim Vervaat, *Catholic University of Nijmegen, The Netherlands*

Let  $\eta = (\eta_t)_{t \geq 0}$  and  $\zeta = (\zeta_t)_{t \geq 0}$  be Markov processes with state spaces  $Y$  and  $Z$ . Following Liggett (1985) we say that  $\eta$  and  $\zeta$  are dual with respect to a function  $H: Y \times Z \rightarrow \mathbb{R}$  or  $\mathbb{C}$  if

$$E_{\eta_0=y} H(\eta_t, z) = E_{\zeta_0=z} H(y, \zeta_t)$$

for  $t \geq 0$  and  $(y, z) \in Y \times Z$ . It turns out that in all cases studied so far  $Y$  and  $Z$  are commutative semigroups and  $H$  is a homomorphism from  $Y \times Z$  into  $\mathbb{R}$  or  $\mathbb{C}$  with multiplication:

$$H(y_1 + y_2, z) = H(y_1, z)H(y_2, z),$$

$$H(y, z_1 + z_2) = H(y, z_1)H(y, z_2);$$

$H$  is said to be a duality between the semigroups  $Y$  and  $Z$ .

Examples of semigroups in duality will be discussed. A simple one is:  $Y = [0, 1]$  with  $+$  = supremum;  $Z = [0, 1]$  with  $+$  = infimum;  $H(y, z) = 1$  if  $y \leq z$ , 0 elsewhere.

A general class of Markov processes in duality will be presented in this context. Both  $\eta$  and  $\zeta$  are random walks with state-dependent clock, stopping at the zeros of the semigroups  $Y$  and  $Z$ , so that these zeros are absorbing states. The clock speed of one random walk is the logarithm of the characteristic function of the steps of the other random walk. The special case of the groups  $Y = Z^d$ ,  $Z = (\mathbb{R}/\mathbb{Z})^d$  with  $+$  = addition and  $H(y, z) = e^{2\pi i y z}$  has been considered by Holley and Stroock (1979).

## References

- [1] R. Holley and D. Stroock, Dual processes and their application to infinite interacting systems, *Advances in Mathematics* 32 (1979) 149–174.
- [2] T.M. Liggett, *Interacting Particle Systems* (Springer-Verlag, Berlin, 1985).

## Quick Simulations of Networks of GI/GI/1 Queues

Jean Walrand, *University of California, Berkeley, CA, USA*

A heuristic to speed up simulations of large backlogs in networks of GI/GI/1 queues is proposed. We use an importance sampling technique where the change of measure is based on large deviation estimates.

The change of measure is performed so that the modified system is again a network of GI/GI/1 queues. The service times and interarrival times (or the independent renewal arrival processes) are modified by an exponential change of measure. The routing probabilities are also modified. The calculations required for finding the new measures depend only on the number of queues, not on the backlog level to be investigated. Also, the necessary likelihood ratio calculations are recursive and inexpensive.

We present simulation results (in the case of Jackson networks, for simplicity) that demonstrate significant speed-ups.