

Available online at www.sciencedirect.com

SCIENCE @ DIRECT®

Applied Mathematics Letters 18 (2005) 833–841

**Applied
Mathematics
Letters**www.elsevier.com/locate/aml

A posteriori discontinuous Galerkin error estimates for transient convection–diffusion equations

Alexandre Ern^a, Jennifer Proft^{a,b,*}^aCERMICS, École Nationale des Ponts et Chaussées, 6/8 avenue Blaise Pascal, F-77455 Marne-la-Vallée cedex 2, France^bLAMA, CNRS UMR 8050, Université Marne-la-Vallée, 5 boulevard Descartes, F-77454 Marne-la-Vallée cedex 2, France

Received 12 May 2004; accepted 21 May 2004

Abstract

A posteriori error estimates are derived for unsteady convection–diffusion equations discretized with the non-symmetric interior penalty and the local discontinuous Galerkin methods. First, an error representation formula in a user specified output functional is derived using duality techniques. Then, an $L^2_t(L^2_x)$ a posteriori estimate consisting of elementwise residual-based error indicators is obtained by eliminating the dual solution. Numerical experiments are performed to assess the convergence rates of the various error indicators on a model problem.

© 2005 Elsevier Ltd. All rights reserved.

Keywords: A posteriori error estimates; Duality techniques; Non-symmetric interior penalty; Local discontinuous Galerkin; Convection–diffusion equations

1. Introduction

Adaptive finite element methods based on discontinuous approximation spaces have been under rapid development recently, notably because of their flexibility in both local mesh subdivision and local polynomial degree variation. The inherent flexibility of discontinuous Galerkin (DG) methods allows for the general construction of temporal and spatial non-uniformities, more so than conventional continuous finite element techniques, though at a higher computational expense. Furthermore, they are locally conservative, allow for nonconforming grids, and successfully handle the difficulties associated with

* Corresponding author at: Université Marne-la-Vallée, 5 boulevard Descartes, F-77454 Marne-la-Vallée cedex 2, France.
E-mail address: jennifer@ices.utexas.edu (J. Proft).

high gradient solutions. Cockburn et al. [1] contains a thorough survey of modern implementations in various applications.

While an extensive body of work with a priori error analysis exists for these methods applied to transient convection–diffusion equations (see [1–5] and references therein), their a posteriori error analysis and implementation is significantly less developed. A posteriori estimators rely on the derivation of computable bounds on the error and may be used to signify where refinement in spatial quantities or polynomial degree may be adaptively modified. They can be particularly useful in applications where solution gradients vary in orders of magnitude across spatial domains, such as those arising in convection-dominated transport.

A posteriori error estimators for DG methods have focused primarily on steady-state equations of elliptic and hyperbolic type. Recent work by Becker et al. [6] and Karakashian and Pascal [7] establishes energy norm estimates for elliptic equations. Houston et al. [8] derive computable upper bounds on a natural DG energy norm for incompressible Stokes flows. We mention work by Rivière and Wheeler [9] who utilize a standard elliptic duality technique to derive L^2 estimates. The use of a duality argument also extends to hyperbolic problems for deriving estimates of functional quantities of interest, leading to adaptivity based on more physically meaningful quantities than the energy or L^2 norm. Such error bounds for first order hyperbolic problems were derived by Larson and Barth in [10]. Süli and collaborators [11,12] also derive and implement various error bounds for general linear and nonlinear target functionals of the solution within an adaptive framework.

There are considerably fewer papers that are concerned with a posteriori error estimation for DG methods applied to transient problems. Adjerid et al. [13] and Flaherty et al. [14] exploit superconvergence results to construct asymptotically correct estimates of spatial discretization errors for unsteady linear and nonlinear hyperbolic conservation laws. This application was also explored by Hartmann and Houston [15] where they employ duality techniques to derive estimates based on functional quantities of interest and demonstrate that “weighted” a posteriori error indicators can lead to sharper bounds and more efficient meshes than corresponding “unweighted” indicators: estimates based on the elimination of the dual solution in the analysis. Results for transient convection–diffusion operators remain sparse; we mention the work of Sun and Wheeler [16], where an explicit $L^2(L^2)$ and target functional estimates are derived for a symmetric discretization of the diffusion operator. Formal $L^2(L^2)$ and target functional estimates of a non-symmetric interior penalty formulation and the related “local” discontinuous Galerkin formulation remain unexplored in the literature.

In this work, we focus our attention on the derivation of an explicit error estimator for the transient convection–diffusion problem

$$\phi \partial_t c + \nabla \cdot (uc - D\nabla c) = \phi f \quad \text{on } \Omega, \quad t \geq 0, \quad (1)$$

$$(uc - D\nabla c) \cdot n = (u\hat{g}) \cdot n \quad \text{on } \partial\Omega_{\text{in}}, \quad t \geq 0, \quad (2)$$

$$(-D\nabla c) \cdot n = 0 \quad \text{on } \partial\Omega_{\text{out}}, \quad t \geq 0, \quad (3)$$

$$c(x, 0) = c_0(x) \quad \text{on } \Omega, \quad (4)$$

defined on the polygonal bounded domain $\Omega \in \mathbb{R}^d$, $d = 2$ or 3 , with unit outward normal n to Lipschitz boundary $\partial\Omega$. Let $\partial\Omega = \partial\Omega_{\text{in}} \cup \partial\Omega_{\text{out}}$ be partitioned into disjoint inflow and outflow boundary portions: $\partial\Omega_{\text{in}} = \{x \in \partial\Omega : u \cdot n < 0\}$ and $\partial\Omega_{\text{out}} = \{x \in \partial\Omega : u \cdot n \geq 0\}$, respectively. In typical porous media applications, $c(x, t)$ represents the concentration of some chemical component, $\phi(x)$ is the effective porosity of the medium and is bounded above and below by positive constants, $u(x, t)$ is the Darcy velocity, $D(x, u, t)$ is a diffusion/dispersion tensor assumed to be uniformly positive definite (but not

necessarily symmetric), and $f(x, t)$ is a source term. We will assume that the Darcy velocity field vector u is given and satisfies the continuity equation $\nabla \cdot u = 0$.

Our approach to deriving a posteriori error estimates is based on the use of a duality argument and Galerkin orthogonality and is similar to techniques used by Rivière and Wheeler in [9] for elliptic equations. The particular non-symmetric discontinuous Galerkin method (NIPG) that we consider for discretizing the diffusion operator was originally developed by Oden et al. in [17], and extended by Rivière et al. by adding interior penalty terms in the formulation to weakly enforce inner element continuity; see [18] and references therein. We also consider the local discontinuous Galerkin method (LDG) developed by Cockburn and Shu [2].

2. Non-symmetric interior penalty Galerkin (NIPG) formulation

Let $\{T_h\}_{h>0}$ denote a family of finite element subdivisions of domain Ω partitioned into open disjoint elements Ω_e such that $\bar{\Omega} = \cup_{\Omega_e \in T_h} \bar{\Omega}_e$. We denote by $H^s(\Omega)$ the standard Sobolev spaces equipped with the usual norms $\|\cdot\|_{H^s(\Omega)}$. For a time–space function u , the notation $u \in L^2_t(H^s_x)$ (resp. $u \in C^k_t(H^s_x)$) means that the function $t \mapsto u(t, \cdot) \in H^s(\Omega)$ is in $L^2(0, T)$ (resp. $C^k(0, T)$) where T is given. Define $\mathbb{P}^k(\Omega_e)$ to be the set of polynomials of degree less than or equal to k on Ω_e and consider the finite element space $V_h = \{v \in L^2(\Omega) : \forall \Omega_e \in T_h, v|_{\Omega_e} \in \mathbb{P}^k(\Omega_e)\}$.

We will use the standard L^2 inner product notation $(\cdot, \cdot)_R$ for domains $R \in \mathbb{R}^d$, and the notation $\langle \cdot, \cdot \rangle_R$ to denote integration over $(d - 1)$ -dimensional manifolds. Let F_h be the set of faces belonging to elements $\Omega_e \in T_h$ and partition F_h into $F^i \cup F^{\partial}_{in} \cup F^{\partial}_{out}$, where F^i denotes the set of interior faces, F^{∂}_{in} the set of those located on $\partial\Omega_{in}$, and F^{∂}_{out} the set of those located on $\partial\Omega_{out}$. For a face $F \in F^i$ shared by elements Ω_{e1} and Ω_{e2} with respective unit outward normals n_1 and n_2 , define the average and (vector-valued) jump of $v \in V_h$ as $\{v\} = \frac{1}{2}(v_1 + v_2)$ and $[v] = (v_1 n_1 + v_2 n_2)$, respectively, where $v_1 = v|_{\Omega_{e1}}$ and $v_2 = v|_{\Omega_{e2}}$. Define the upwind value $v^\uparrow = v_1$ when $u \cdot n_1 > 0$, else $v^\uparrow = v_2$. Similarly, for a function $w \in [V_h]^d$, define the average and (scalar-valued) jump as $\{w\} = \frac{1}{2}(w_1 + w_2)$ and $[w] = (w_1 \cdot n_1 + w_2 \cdot n_2)$, respectively.

The NIPG formulation consists of seeking $u_h \in C^1_t(V_h)$ such that $\forall v \in V_h$ and $\forall t \geq 0$,

$$(\phi \partial_t c_h, v)_\Omega + a_{\text{NIPG}}(c_h, v) = (\phi f, v)_\Omega - (u \hat{g} \cdot n, v)_{\partial\Omega_{in}}, \tag{5}$$

with the initial condition $(c_0 - c_h(0, \cdot), v)_\Omega = 0, \forall v \in V_h$. The bilinear form a_{NIPG} is given by

$$\begin{aligned} a_{\text{NIPG}}(c_h, v) = & - \sum_{\Omega_e \in T_h} (uc_h - D\nabla c_h, \nabla v)_{\Omega_e} + \sum_{F \in F^{\partial}_{out}} \langle uc_h \cdot n, v \rangle_F \\ & + \sum_{F \in F^i} (\langle uc_h^\uparrow, [v] \rangle_F - \langle \{D\nabla c_h\}, [v] \rangle_F + \langle \{D\nabla v\}, [c_h] \rangle_F + \langle \sigma_F [c_h], [v] \rangle_F), \end{aligned} \tag{6}$$

where $\sigma_F = \frac{\sigma_0}{|F|}$, σ_0 is a positive constant, and $|F|$ the $(d - 1)$ -dimensional measure of F . Let the error in the solution be defined as $e_c = c - c_h$. Our goal is to control the error in the functional

$$\Psi(e_c) = \int_0^T (\psi_1(e_c), e_c)_\Omega dt + (\psi_2(e_c(T, \cdot)), e_c(T, \cdot))_\Omega, \tag{7}$$

where ψ_1 and ψ_2 are user specified functions. Let ξ satisfy the adjoint equation

$$\phi \partial_t \xi + \nabla \cdot (u \xi + D^T \nabla \xi) = \psi_1(e_c) \quad \text{on } \Omega, \quad t \leq T, \tag{8}$$

$$(u\xi + D^T \nabla \xi) \cdot n = 0 \quad \text{on } \partial\Omega_{\text{out}}, \quad t \leq T, \quad (9)$$

$$(-D^T \nabla \xi) \cdot n = 0 \quad \text{on } \partial\Omega_{\text{in}}, \quad t \leq T, \quad (10)$$

$$\xi(x, T) = -\psi_2(e_c(T, \cdot)) \quad \text{on } \Omega. \quad (11)$$

We first derive an error representation formula.

Theorem 2.1. *Assume that the solution c to (1)–(4) and the solution ξ to (8)–(11) are both in $L_t^2(H_x^2) \cap C_t^0(L_x^2)$. Assume the diffusion/dispersion tensor D to be continuous. Then,*

$$\begin{aligned} \Psi(e_c) = & - \int_0^T (R_{\text{eqn}}, \xi - \xi^*)_{\Omega} dt - (R_{t=0}, (\xi - \xi^*)(0, \cdot))_{\Omega} \\ & + \int_0^T \left(\sum_{F \in F_{\text{in}}^{\partial}} \langle R_{\text{in}}, \xi - \xi^* \rangle_F + \sum_{F \in F_{\text{out}}^{\partial}} \langle R_{\text{out}}, \xi - \xi^* \rangle_F \right) dt \\ & + \int_0^T \sum_{F \in F^i} (\langle R_{[c_h]}, D^T \nabla \xi + D \nabla \xi^* \rangle_F - \langle R_{[D \nabla c_h]} - u \cdot R_{[c_h]}, \xi - \xi^* \rangle_F) dt, \end{aligned} \quad (12)$$

where ξ^* is arbitrary in $V_h \cap C^0(\overline{\Omega})$ and where we have introduced the residuals

$$R_{\text{eqn}} = \phi f - \phi \partial_t c_h + \nabla \cdot (u c_h - D \nabla c_h), \quad (13)$$

$$R_{[c_h]} = [c_h], \quad R_{[D \nabla c_h]} = [D \nabla c_h], \quad (14)$$

$$R_{\text{in}} = u \hat{g} \cdot n - (u c_h - D \nabla c_h) \cdot n, \quad R_{\text{out}} = -D \nabla c_h \cdot n, \quad (15)$$

$$R_{t=0} = c_0 - c_{h,0}. \quad (16)$$

Proof. Using (7), (8), and (11), we infer

$$\Psi(e_c) = - \int_0^T (\phi \partial_t e_c, \xi)_{\Omega} dt - (R_{t=0}, \xi(0, \cdot))_{\Omega} + \int_0^T (\nabla \cdot (u \xi + D^T \nabla \xi), e_c)_{\Omega} dt.$$

Integrate by parts the diffusion contribution to the last term and use (10) to obtain

$$\begin{aligned} (\nabla \cdot (D^T \nabla \xi), e_c)_{\Omega} = & - \sum_{\Omega_e \in T_h} (\nabla \xi, D \nabla e_c)_{\Omega_e} + \sum_{F \in F^i} \langle D^T \nabla \xi, [e_c] \rangle_F \\ & + \sum_{F \in F_{\text{out}}^{\partial}} \langle D^T \nabla \xi \cdot n, e_c \rangle_F. \end{aligned}$$

Let ξ^* be arbitrary in $V_h \cap C^0(\overline{\Omega})$. Using Galerkin orthogonality, we obtain

$$\begin{aligned} \Psi(e_c) = & - \int_0^T (\phi \partial_t e_c, \xi - \xi^*)_{\Omega} dt - (R_{t=0}, (\xi - \xi^*)(0, \cdot))_{\Omega} \\ & + \int_0^T \sum_{\Omega_e \in T_h} (u e_c - D \nabla e_c, \nabla (\xi - \xi^*))_{\Omega_e} dt \\ & + \int_0^T \left(\sum_{F \in F^i} \langle D^T \nabla \xi, [e_c] \rangle_F + \sum_{F \in F_{\text{out}}^{\partial}} \langle D^T \nabla \xi \cdot n, e_c \rangle_F \right) dt \end{aligned}$$

$$+ \int_0^T \left(\sum_{F \in F^i} \langle \{D\nabla \xi^*\}, [e_c] \rangle_F + \sum_{F \in F_{out}^\partial} \langle ue_c \cdot n, \xi^* \rangle_F \right) dt.$$

Integrate by parts the term in the second line of the above equation to infer

$$\begin{aligned} \sum_{\Omega_e \in T_h} (ue_c - D\nabla e_c, \nabla(\xi - \xi^*))_{\Omega_e} &= - \sum_{\Omega_e \in T_h} (\nabla \cdot (ue_c - D\nabla e_c), \xi - \xi^*)_{\Omega_e} \\ &+ \sum_{F \in F^i} \langle [ue_c - D\nabla e_c], \xi - \xi^* \rangle_F + \sum_{F \in F_{in}^\partial \cup F_{out}^\partial} \langle (ue_c - D\nabla e_c) \cdot n, \xi - \xi^* \rangle_F. \end{aligned}$$

Using (9), we readily deduce the error representation formula (12). \square

From the error representation formula (12), it is possible to infer a residual-based a posteriori error estimate where the dual solution has been eliminated using the Cauchy–Schwarz inequality, local approximation properties of the finite element space V_h , and a global stability result for the dual problem. Set $\psi_1(e_c) = e_c$ and $\psi_2(e_c) = 0$ so that $\Psi(e_c) = \|e_c\|_{L^2_t(L^2_x)}$. Assume that the resulting dual problem (8)–(11) satisfies the stability estimate

$$\max_{0 \leq t \leq T} \|\xi(\cdot, t)\|_{\Omega}^2 + \int_0^T \|\xi\|_{H^2(\Omega)}^2 dt \leq C \int_0^T \|e_c\|_{L^2(\Omega)}^2 dt. \tag{17}$$

Furthermore, assume that the following approximation properties proven in [19] for $d = 2$ also hold for $d = 3$. For element Ω_e in T_h and $\phi \in H^s(\Omega_e)$, there exists a constant C depending on s but independent of ϕ , k , and element diameter h_e and a sequence $\phi_h^* \in \mathbb{P}^k(\Omega_e)$, such that for $0 \leq q \leq s$ and for $\mu = \min(k + 1, s)$,

$$\|\phi - \phi_h^*\|_{H^q(\Omega_e)} \leq C \frac{h_e^{\mu-q}}{k^{s-q}} \|\phi\|_{H^s(\Omega_e)} \quad s \geq 0, \tag{18}$$

$$\|\phi - \phi_h^*\|_{H^r(\partial\Omega_e)} \leq C \frac{h_e^{\mu-r-1/2}}{k^{s-r-1/2}} \|\phi\|_{H^s(\Omega_e)} \quad s > \frac{1}{2} + \delta, \delta = 0, 1. \tag{19}$$

Corollary 2.1. *With the above assumptions, an $L^2_t(L^2_x)$ a posteriori error estimate holds for the formulation (5) of the form*

$$\|e_c\|_{L^2_t(L^2_x)}^2 \leq C \int_0^T \sum_{\Omega_e \in T_h} \eta_e^2 dt, \tag{20}$$

with elementwise error indicators

$$\begin{aligned} \eta_e^2 &= \frac{h_e^4}{k^4} \|R_{eqn}\|_{L^2(\Omega_e)}^2 + \frac{h_e^4}{k^4} \|R_{t=0}\|_{L^2(\Omega_e)}^2 \\ &+ \sum_{F \in \partial\Omega_e \cap \Omega} \left(\frac{\tilde{h}_e^3}{k^3} \|R_{[D\nabla c_h]} + u \cdot R_{[c_h]}\|_{L^2(F)}^2 + \frac{\tilde{h}_e^2}{k^2} \|D\|_{L^\infty} \|R_{[c_h]}\|_{L^2(F)}^2 \right. \\ &\left. + \|D\|_{L^\infty}^2 \|R_{[c_h]}\|_{L^2(F)}^2 \right) + \sum_{F \in \partial\Omega_e \cap \partial\Omega_{in}} \frac{\tilde{h}_e^3}{k^3} \|R_{in}\|_{L^2(F)}^2 + \sum_{F \in \partial\Omega_e \cap \partial\Omega_{out}} \frac{\tilde{h}_e^3}{k^3} \|R_{out}\|_{L^2(F)}^2, \end{aligned} \tag{21}$$

for \tilde{h}_e the maximal element diameter over all elements with the common face F and C a constant independent of h_F .

Proof. Use the error representation formula (12) together with the stability estimate (17) and the approximation results (18) and (19). The only term requiring special attention is the first one in the third line of (12). Writing $D^T \nabla \xi + D \nabla \xi^* = (D + D^T) \nabla \xi - D \nabla (\xi - \xi^*)$, the second term yields the last term in the second line of (21). The quantity $\|\nabla \xi\|_F$ is estimated by $\|\xi\|_{H^2(\Omega_e)}$ where Ω_e is an element to which F belongs. Using the stability estimate (17), this yields the first term in the third line of (21). \square

Convergence orders of the various contributions to (21) are assessed numerically in Section 4. Note also that with some additional algebra, it is possible to derive an error representation formula and an a posteriori error estimate when the diffusion tensor is discontinuous across mesh interfaces.

3. Local discontinuous Galerkin (LDG) formulation

The LDG method consists of seeking $c_h, \tilde{z}_h, z_h \in C_t^1(V_h)$ such that $\forall v \in V_h, \forall w \in [V_h]^d, \forall \tilde{w} \in [V_h]^d$, and $\forall t \geq 0$,

$$\begin{aligned} & (\phi \partial_t c_h, v)_\Omega - \sum_{\Omega_e \in \mathcal{T}_h} (uc_h + z_h, \nabla v)_{\Omega_e} + \sum_{F \in F^i} \langle uc_h^\uparrow + \{z_h\}, [v] \rangle_F \\ & + \sum_{F \in F_{\text{out}}^\partial} \langle uc_h \cdot n, v \rangle_F = (\phi f, v)_\Omega - (u \hat{g} \cdot n, v)_{\partial \Omega_{\text{in}}}, \end{aligned} \quad (22)$$

$$(\tilde{z}_h, w)_\Omega - \sum_{\Omega_e \in \mathcal{T}_h} (c_h, \nabla \cdot w)_{\Omega_e} + \sum_{F \in F^i} \langle \{c_h\}, [w] \rangle_F + (c_h, w \cdot n)_{\partial \Omega} = 0, \quad (23)$$

$$(D \tilde{z}_h, \tilde{w})_\Omega - (z_h, \tilde{w})_\Omega = 0, \quad (24)$$

with the same initial condition as before. Again, let ξ satisfy the dual problem (8)–(11).

Theorem 3.1. Assume that the solution c to (1)–(4) and the solution ξ to (8)–(11) are both in $L_t^2(H_x^2) \cap C_t^0(L_x^2)$. Assume the diffusion/dispersion tensor D to be continuous and piecewise linear in space. Then,

$$\begin{aligned} \Psi(e_c) = & - \int_0^T (R_{\text{eqn}}, \xi - \xi^*)_\Omega \, dt - (R_{t=0}, (\xi - \xi^*)(0, \cdot))_\Omega \\ & + \int_0^T \left(\sum_{F \in F_{\text{in}}^\partial} \langle R_{\text{in}}, \xi - \xi^* \rangle_F + \sum_{F \in F_{\text{out}}^\partial} \langle R_{\text{out}}, \xi - \xi^* \rangle_F \right) dt \\ & + \int_0^T \sum_{F \in F^i} \left(\langle R_{[c_h]}, D^T \nabla \xi \rangle_F - \langle R_{[D \nabla c_h]} - u \cdot R_{[c_h]}, \xi - \xi^* \rangle_F \right) dt, \end{aligned} \quad (25)$$

where ξ^* is arbitrary in $V_h \cap C^0(\bar{\Omega})$ and where the residuals $R_{\text{eqn}}, R_{[c_h]}, R_{[D \nabla c_h]}, R_{\text{in}}, R_{\text{out}}$, and $R_{t=0}$ are defined in (13)–(16).

Proof. The proof is similar to that of [Theorem 2.1](#). The main difference is that Galerkin orthogonality now yields

$$\begin{aligned} \Psi(e_c) &= - \int_0^T (\phi \partial_t e_c, \xi - \xi^*)_{\Omega} dt - (R_{t=0}, (\xi - \xi^*)(0, \cdot))_{\Omega} \\ &+ \int_0^T \left(\sum_{\Omega_e \in T_h} (ue_c, \nabla(\xi - \xi^*))_{\Omega_e} - (D \nabla e_c, \nabla \xi)_{\Omega_e} - (e_z, \nabla \xi^*)_{\Omega_e} \right) dt \\ &+ \int_0^T \left(\sum_{F \in F^i} \langle D^T \nabla \xi, [e_c] \rangle_F + \sum_{F \in F_{out}^{\partial}} \langle D^T \nabla \xi \cdot n, e_c \rangle_F + \sum_{F \in F_{out}^{\partial}} \langle ue_c \cdot n, \xi^* \rangle_F \right) dt, \end{aligned}$$

where $e_z = z - z_h$ and $z = -D \nabla c$. Similarly, set $e_{\tilde{z}} = \tilde{z} - \tilde{z}_h$ where $\tilde{z} = -\nabla c$. Owing to the assumption on D , we infer $D^T \nabla \xi^* \in [V_h]^d$ and hence

$$(e_z, \nabla \xi^*)_{\Omega_e} = (e_{\tilde{z}}, D^T \nabla \xi^*)_{\Omega_e} = -(\nabla e_c, D^T \nabla \xi^*)_{\Omega_e} = -(D \nabla e_c, \nabla \xi^*)_{\Omega_e},$$

whence the error representation formula (25) readily follows. \square

Corollary 3.1. *With the assumptions of [Corollary 2.1](#), an $L^2_t(L^2_x)$ a posteriori error estimate holds for the formulation (22)–(24) of the form (20) with elementwise error indicators given by (21).*

4. Numerical results

In this section we present numerical results to illustrate the convergence order of the various terms in the a posteriori error estimates. For the sake of brevity, we consider the NIPG error estimates (21). As a model problem, consider a 1D convection–diffusion equation posed over domain $\Omega = (0, 4\pi)$ with initial data $u_0(x) = \sin(x)$, source term $f = 0$, inflow data $\hat{g}(t) = -e^{-Dt} \sin(ut)$, diffusion coefficient $D = 1$, and advection velocity $u = 1$. The simulation time is set to $T = 0.5$. Since the diffusion length scale can be estimated as $\delta = (DT)^{\frac{1}{2}} = 0.7$, we infer that the restriction of the solution to the interval $(0, 2\pi)$ is approximately given by $c(t, x) = e^{-Dt} \sin(x - ut)$.

Numerical experiments are performed on two series of meshes: a series of uniform meshes with step size $h = 2^{-p} \frac{\pi}{8}$ ($0 \leq p \leq 3$) and a series of non-uniform meshes which are constructed from the uniform meshes by setting the step size alternatively to $\frac{h}{2}$ and $\frac{3h}{2}$ for adjacent cells. Problem (5) is discretized in time using an explicit Euler method and a time step of 2.5×10^{-5} . Results are presented in [Tables 1](#) and [2](#). We evaluate the quantities

$$\begin{aligned} T_1 &= \left(\sum_{x_j \in (0, 2\pi)} [c_h(x_j)]^2 \right)^{\frac{1}{2}}, & T_2 &= \left(\sum_{x_j \in (0, 2\pi)} [c'_h(x_j)]^2 \right)^{\frac{1}{2}}, \\ T_3 &= R_{in}(t = T, x = 0), & T_4 &= \left(\sum_{\Omega_e \in (0, 2\pi)} \|R_{t=0}\|_{L^2(\Omega_e)}^2 \right)^{\frac{1}{2}}, \end{aligned}$$

where the x_j 's denotes the mesh vertices. On the uniform meshes, superconvergence is obtained so that the upper bound in (21) scales as h^2 . On the non-uniform mesh, the first term in the third equation of

Table 1
Convergence tests on uniform meshes

p	T_1	Order	T_2	Order	T_3	Order	T_4	Order
0	2.98e-2	–	7.73e-1	–	2.53e-2	–	7.18e-3	–
1	1.79e-2	2.2	5.51e-1	.49	5.97e-3	2.1	1.80e-3	2.0
2	3.36e-3	2.4	3.90e-1	.50	1.22e-3	2.3	4.50e-3	2.0
3	6.07e-4	2.5	2.76e-1	.50	2.03e-4	2.6	1.13e-3	2.0

Table 2
Convergence tests on non-uniform meshes

p	T_1	Order	T_2	Order	T_3	Order	T_4	Order
0	4.94e-2	–	7.84e-1	–	5.78e-2	–	1.40e-2	–
1	1.95e-2	1.3	5.54e-1	.49	1.37e-2	2.1	3.51e-3	2.0
2	7.82e-3	1.3	3.92e-1	.50	3.30e-3	2.1	8.79e-4	2.0
3	1.04e-3	1.4	2.78e-1	.50	7.29e-4	2.2	2.20e-4	2.0

(21) dominates the upper bound, yielding a convergence order of $h^{\frac{3}{2}}$ approximately. This estimate is compatible with standard a priori estimates for convection–diffusion equations.

Acknowledgements

This work was supported in part by the GdR MoMaS program (CNRS-2439, ANDRA, BRGM, CEA, EdF). The authors thank Prof. Béatrice Rivière for valuable suggestions.

References

- [1] B. Cockburn, G. Karniadakis, C. Shu, The development of discontinuous Galerkin methods, in: B. Cockburn, G. Karniadakis, C. Shu (Eds.), *Discontinuous Galerkin Methods*, Springer-Verlag, Berlin, 2000.
- [2] B. Cockburn, C.-W. Shu, The local discontinuous Galerkin method for time-dependent convection–diffusion systems, *SIAM J. Numer. Anal.* 35 (1998).
- [3] C.E. Baumann, J.T. Oden, A discontinuous hp finite element method for convection–diffusion problems, *Comput. Meth. Appl. Mech. Engrg.* 175 (3–4) (1999) 311–341.
- [4] C. Dawson, J. Proft, A priori error estimates for interior penalty versions of local discontinuous Galerkin methods applied to transport equations, *Numer. Methods Partial Differential Equations* 17 (6) (2001) 545–564.
- [5] P. Castillo, B. Cockburn, D. Schotzau, C. Schwab, An optimal a priori error estimate for the hp-version of the local discontinuous Galerkin method for convection–diffusion problems, *Math. Comp.* 71 (238) (2002) 455–478.
- [6] R. Becker, P. Hansbo, M.G. Larson, Energy norm a posteriori error estimation for discontinuous Galerkin methods, *Comput. Methods Appl. Mech. Engrg.* 192 (2003) 723–733.
- [7] O.A. Karakashian, F. Pascal, A posteriori error estimates for a discontinuous Galerkin approximation of second order elliptic problems, *SIAM J. Numer. Anal.* 41 (6) (2003) 2374–2399.
- [8] P. Houston, I. Perugia, D. Schotzau, Energy norm a posteriori error estimation for mixed discontinuous Galerkin approximations of the Maxwell operator, *Comput. Methods Appl. Mech. Engrg.* 194 (2005) 499–510.
- [9] B. Rivière, M.F. Wheeler, A posteriori error estimates and mesh adaptation strategy for discontinuous Galerkin methods applied to diffusion problems, *Comput. Math. Appl.* 46 (1) (2003) 141–163.
- [10] M. Larson, T. Barth, A posteriori error estimation for adaptive discontinuous Galerkin approximations of hyperbolic systems, in: B. Cockburn, G. Karniadakis, C. Shu (Eds.), *Discontinuous Galerkin Methods*, Springer-Verlag, Berlin, 2000.

- [11] E. Süli, C. Schwab, P. Houston, hp-dgfem for partial differential equations with non-negative characteristic form, in: B. Cockburn, G. Karniadakis, C. Shu (Eds.), *Discontinuous Galerkin Methods*, Springer-Verlag, Berlin, 2000.
- [12] P. Houston, B. Senior, E. Süli, hp-Discontinuous Galerkin finite element methods for hyperbolic problems: Error analysis and adaptivity, *Internat. J. Numer. Methods Fluids* 40 (1–2) (2002) 153–169.
- [13] S. Adjerid, K. Devine, J. Flaherty, L. Krivodonova, A posteriori estimation for discontinuous Galerkin solutions of hyperbolic problems, *Comput. Methods Appl. Mech. Engrg.* 191 (11–12) (2002) 1097–1112.
- [14] J. Flaherty, L. Krivodonova, J.-F. Remacle, M. Shephard, Aspects of discontinuous Galerkin methods for hyperbolic conservation laws, *Finite Elem. Anal. Des.* 38 (10) (2002) 889–908.
- [15] R. Hartmann, P. Houston, Adaptive discontinuous Galerkin finite element methods for nonlinear hyperbolic conservation laws, *SIAM J. Sci. Comput.* 24 (2002) 979–1004.
- [16] S. Sun, M.F. Wheeler, A posteriori error analysis for symmetric discontinuous Galerkin approximations of reactive transport problems, 2003 (submitted for publication).
- [17] J.T. Oden, I. Babuška, C. Baumann, A discontinuous finite element method for diffusion problems, *J. Comput. Phys.* 146 (1998) 491–519.
- [18] B. Rivière, M.F. Wheeler, V. Girault, A priori error estimates for finite element methods based on discontinuous approximation spaces for elliptic problems, *SIAM J. Numer. Anal.* 39 (3) (2001) 902–931.
- [19] I. Babuška, M. Suri, The optimal convergence rate of the p-version of the finite element method, *SIAM J. Numer. Anal.* 24 (1987) 750–776.