ing Saud University

Journal of King Saud University - Science (2012) 24, 63-67



King Saud University Journal of King Saud University – Science

www.ksu.edu.sa www.sciencedirect.com

ORIGINAL ARTICLE

Travelling waves solution for MHD aligned flow of a second grade fluid with heat transfer: A symmetry independent approach

Najeeb Alam Khan^{a,*}, Asmat Ara^a, Muhammad Jamil^{b,c}, Ahmet Yildirim^d

^a Department of Mathematics, University of Karachi, Karachi 75270, Pakistan

^b Abdul Salam School of Mathematical Science, GC University, Lahore, Pakistan

^c Department of Mathematics, NED University of Engineering & Technology, Karachi 75270, Pakistan

^d Department of Mathematics, Faculty of Science, Ege University, 35100 Bornova-Izmir, Turkey

Received 22 June 2010; accepted 26 August 2010 Available online 6 September 2010

KEYWORDS

Travelling waves; Heat transfer; Second grade fluid; Aligned flows **Abstract** In this work, an approach is implemented for finding exact solutions of an incompressible MHD aligned flow with heat transfer in a second grade fluid. This approach based on travelling wave phenomenon. The partial differential equations (PDEs) are reduced to ordinary differential equations (ODEs) by using wave parameter. The methodology used in this work is independent of perturbation, symmetry consideration and other restrictive assumption. Comparison is made with the results obtained previously.

© 2010 King Saud University. Production and hosting by Elsevier B.V. All rights reserved.

1. Introduction

2.01

ELSEVIER

It is an established fact that the flow characteristics of non-Newtonian fluids are quite different when compared with the

* Corresponding author. Tel.: +92 2135040516.

E-mail addresses: njbalam@yahoo.com (N.A. Khan), jqrza26@ yahoo.com (M. Jamil), ahmet.yildirim@ege.edu.tr (A. Yildirim).

1018-3647 © 2010 King Saud University. Production and hosting by Elsevier B.V. All rights reserved.

Peer review under responsibility of King Saud University. doi:10.1016/j.jksus.2010.08.014

Production and hosting by Elsevier

viscous fluids. Therefore, the well-known Navier-Stokes equations (Berker, 1963; Chandna et al., 1982; Chandna and Oku-Ukpong, 1994a; Hui, 1987; Naeem and Jamil, 2006) are inappropriate for the non-Newtonion fluids. There are numerous models of fluids are mainly classified in the literature. The flows of non-Newtonion fluids (Khan et al., 2009; Fetecau et al., 2008; Fetecau et al., 2006) are mainly classified into differential, integral and rate type fluids. Amongst these, the flows of differential type fluids have attracted the mathematician, computer programmers and numerical solvers. The constitutive equations of differential type fluids are very complex. Several authors in fluid dynamics are engaged with equations of motion of second grade fluid (Hayat et al., 2005; Siddiqui et al., 1985; Labropulu, 2003; Siddiqui, 1990; Rajagopal, 1980; Rajagopal and Gupta, 1984; Kaloni and Huschilt, 1984; Siddiqui and Kaloni, 1986; Mohyuddin et al., 2005; Ali and Hasan, 2007; Ali et al., 2007).

Ting (1963) has studied unsteady flows of a second grade fluid in a bounded region. He studied that the solution exists only if the coefficient of the higher order derivative in the governing equation positive. In 1994, Chandna and Oku-Ukpong (Chandna and Oku-Ukpong, 1994b) studied MHD aligned flow of a second grade fluid by assuming the prescribed form of vorticity. By taking the vorticity to be proportional to the stream function perturbed by a uniform stream, Lin and Tobak (Lin and Tobak, 1986), Benharbit and Siddiqui (Benharbit and Siddiqui, 1992), Labropulu (Labropulu, 2000), they investigated the exact solutions for second grade fluid. Under the slow motion assumption Dolapçi and Pakdemirli (Dolapçi and Pakdemirli, 2004) found the exact solution by Lie group method. Yürüsoy (Yürüsoy, 2004) found exact solutions of steady creeping flow of a second grade fluid with heat transfer via Lie group. Recently, for creeping flow Afify (Afify, 2009) studied the Lie group analysis approach and found the exact solutions for steady MHD aligned second grade fluid with heat transfer.

In this work, the MHD aligned unsteady flow of a second grade fluid with heat transfer is studied. The study of flow for an electrically conducting fluid has applications in many engineering problems such as MHD generators, plasma studied, geothermal energy extractions and electromagnetic propulsion. The electromagnetic propulsion system is closely associated with magneto chemistry, requires a complete understanding of the equation of state and transport properties such as diffusion, stress-shear rate relationship, thermal conductivity and radiation. The investigations of the travelling wave solution of nonlinear equations play an important role in the study of nonlinear physical phenomena. Travelling wave phenomenon, that appears in many areas such as physics (El-Wakil and Abdou, 2008; Yildirim and Gülkanat, 2010), mathematical biology (Mohyud-Din et al., 2010), chemical kinetics, fiber optics, fluid mechanics, etc.

To the best of our knowledge only few studies, which deal with the flows of MHD aligned second grade fluid available in the literature. For the present paper, the method adopted is as follows. In Section 2, we put forward the statement of the problem. A theoretical development of Section 3 is illustrated by solution of the equations of motion of MHD aligned second grade fluid with heat transfer in Section 4. Section 5 synthesis the concluding remarks.

2. Flow development

The equations of motion of an unsteady MHD aligned flow of a second grade fluid with heat transfer is governed by

$$\rho_t + div(\rho V) = 0 \quad \text{(Continuity)} \tag{1}$$

$$\rho \frac{dV}{dt} = div\tau + \Lambda(Curl \ H) \times H + \rho r_1 \quad \text{(Linear momentum) (2)}$$

$$divH = 0 \quad (\text{Solenoidal}) \tag{3}$$

$$H_{t} = Curl(V \times H) - \frac{1}{\Lambda\delta}Curl(Curl \ H) \quad (\text{Diffusion}) \tag{4}$$

$$\rho \frac{dL}{dt} = \tau L - div \ q + \rho r_2 \quad \text{(Energy)} \tag{5}$$

The constitutive equations for the stress of a second grade fluid given by Coleman and Noll (Coleman and Noll, 1960)

$$\tau = -pI + \mu L_1 + \alpha_1 L_2 + \alpha_2 L_1^2 \tag{6}$$

$$L_1 = (grad \ V) + (grad \ V)^* \tag{7}$$

$$L_{2} = \frac{dL_{1}}{dt} + L_{1}(grad \ V) + (grad \ V)^{*}L_{1}$$
(8)

Here V is the velocity, p is the fluid pressure function, ρ the density, μ the constant viscosity, grad the gradient operator, '*' the transpose, $\frac{d}{dt}$ the material time derivative, α_1, α_2 are the constant normal stress moduli, L_1 and L_2 are the first two Rivlin–Ericksen tensors, r_1 the body force per unit mass, r_2 is the radiant heating (assumed to be zero), $E = C_p T$ is the specific internal energy, C_p is the specific heat and T is the temperature, $q = -k\nabla T$ is the heat flux vector, k is the constant thermal conductivity.

If an incompressible fluid of second grade is to have motions that are compatible with thermodynamics in the sense of the Clausius–Duhem inequality and the condition that the Helmholtz free energy be a minimum when the fluid is at rest, then the following must be satisfied (Dunn and Fosdick, 1974)

$$\mu \ge 0, \quad \alpha_1 \ge 0, \quad \alpha_1 + \alpha_2 = 0$$

$$\tag{9}$$

In this paper, we shall consider a second grade fluid which under goes isochoric motion in a plane and body force is negligible, we take V = (u(x, y, t), v(x, y, t), 0), p = $p(x, y, t)H = (H_1(x, y, t), H_2(x, y, t), 0)$ and T = T(x, y, t) so that our flow Eqs. (1)–(5) takes the form

$$\frac{\partial u}{\partial x} = -\frac{\partial v}{\partial y}$$
(10)
$$\frac{\partial u}{\partial t} + u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y}$$

$$= -\frac{1}{\rho} \frac{\partial p}{\partial x} + v \nabla^2 u + \beta \left[\frac{\partial}{\partial t} \left(\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} \right) \right.$$

$$+ 5 \frac{\partial u}{\partial x} \frac{\partial^2 u}{\partial x^2} + \frac{\partial u}{\partial x} \frac{\partial^2 u}{\partial y^2} + u \frac{\partial^3 u}{\partial x^3} + v \frac{\partial^3 u}{\partial y^3} + u \frac{\partial^3 u}{\partial x \partial y^2}$$

$$+ 2 \frac{\partial v}{\partial x} \frac{\partial^2 v}{\partial x^2} + \frac{\partial u}{\partial y} \frac{\partial^2 u}{\partial x \partial y} + \frac{\partial u}{\partial y} \frac{\partial^2 v}{\partial x^2} + v \frac{\partial^3 u}{\partial y \partial x^2} \right]$$
(10)

$$\frac{\partial v}{\partial t} + u \frac{\partial v}{\partial x} + v \frac{\partial v}{\partial y}$$

$$= -\frac{1}{\rho} \frac{\partial p}{\partial y} + v \nabla^2 v + \beta \left[\frac{\partial}{\partial t} \left(\frac{\partial^2 v}{\partial x^2} + \frac{\partial^2 v}{\partial y^2} \right) + 5 \frac{\partial u}{\partial x} \frac{\partial^2 u}{\partial x \partial y} - \frac{\partial u}{\partial x} \frac{\partial^2 v}{\partial x^2} - v \frac{\partial^3 u}{\partial x \partial y^2} + u \frac{\partial^3 v}{\partial x^3} - v \frac{\partial^3 u}{\partial x^3} + 2 \frac{\partial u}{\partial y} \frac{\partial^2 u}{\partial y^2} - \frac{\partial v}{\partial x} \frac{\partial^2 u}{\partial x^2} + \frac{\partial v}{\partial x} \frac{\partial^2 u}{\partial y^2} - u \frac{\partial^3 u}{\partial x^2 \partial y} \right]$$
(12)

$$\frac{\partial H_1}{\partial x} + \frac{\partial H_2}{\partial y} = 0 \tag{13}$$

$$\frac{\partial}{\partial t} \left(\frac{\partial H_2}{\partial x} - \frac{\partial H_1}{\partial y} \right) = \nabla^2 \left[\frac{1}{A\delta} \left(\frac{\partial H_2}{\partial x} - \frac{\partial H_1}{\partial y} \right) + vH_1 - uH_2 \right]$$
(14)

$$\begin{split} \rho C_p \left(\frac{\partial I}{\partial t} + u \frac{\partial I}{\partial x} + v \frac{\partial I}{\partial y} \right) \\ &= k \nabla^2 T + \mu \left[\left(\frac{\partial u}{\partial y} \right)^2 + 2 \left(\frac{\partial v}{\partial y} \right)^2 + \left(\frac{\partial v}{\partial x} \right)^2 + 2 \left(\frac{\partial u}{\partial x} \right)^2 + 2 \frac{\partial u}{\partial y} \frac{\partial v}{\partial x} \right] \\ &+ \alpha_1 \left[\frac{\partial u}{\partial y} \frac{\partial^2 u}{\partial t \partial y} + 2 \frac{\partial v}{\partial y} \frac{\partial^2 v}{\partial t \partial y} + 2 v \frac{\partial v}{\partial y} \frac{\partial^2 v}{\partial y^2} + \frac{\partial v}{\partial x} \frac{\partial^2 v}{\partial t \partial y} + v \frac{\partial v}{\partial x} \frac{\partial^2 v}{\partial y^2} \\ &+ 2 \frac{\partial u}{\partial x} \frac{\partial^2 u}{\partial t \partial x} + \frac{\partial u}{\partial y} \frac{\partial^2 v}{\partial t \partial x} + \frac{\partial v}{\partial x} \frac{\partial^2 v}{\partial t \partial x} + u \frac{\partial u}{\partial y} \frac{\partial^2 u}{\partial x \partial y} + v \frac{\partial u}{\partial x} \frac{\partial^2 u}{\partial y^2} \right] \end{split}$$
(15)

3. Travelling waves

Let Lx be a linear form of the independent variables.

$$Lx = L_{\bar{a}} x_{\bar{a}} \tag{16}$$

The representation of a solution is assumed in the form

$$\vartheta(x) = \upsilon(Lx) \tag{17}$$

where the function $v(\zeta)$ depends on one independent variable ζ . The value of ζ is called a phase of the wave. Fixing the phase $\zeta = Lx$, one obtains the front of the wave, where the values of the dependent variables are constant. Hence, the front of the wave is a plane propagating in the space R^n .

A solution $u(x_1, x_2, ..., x_n)$ is called an *r*-multiple travelling wave, if it has the representation

$$\vartheta(x) = \upsilon(Lx) \tag{18}$$

where Lx be a vector, which coordinates are linear forms of independent variables

$$(Lx)_i = L_{i\bar{\alpha}} x_{\bar{\alpha}}, \quad i = 1, 2, \dots r, \ r < n \tag{19}$$

The variables $\overline{\zeta} = Lx \in R^r$ are called parameters of the wave. It is note that for an *r*-multiple travelling wave the rank of the Jacobi matrix of the dependent variables with respect to the independent variables is less or equal then *r*.

4. Solution

Without loss of generality one can assume that the travelling wave type solution has the representation

$$u = u(\xi), \quad v = v(\xi), \quad p = p(\xi), \quad T = T(\xi),$$

$$H_1 = H_1(\xi), \quad H_2 = H_2(\xi)$$
(20)

where $\xi = bx + ay + Ct$ is the wave parameter b, a are constants and C is the constant phase velocity.

On substituting the representation of the solution (20) into (10)–(14), we have

$$= -\frac{1}{\rho}p + v(a + b')a + \beta \left[(C + bu + av)(a^2 + b^2)a''' + \frac{2b}{a^2}(a^2 + b^2)^2a'a'' \right] - \eta H_2(bH'_2 - aH'_1)$$
(22)

$$= -\frac{a}{\rho}p' + v(a^{2} + b^{2})v'' + \beta \left[-(C + bu + av) \left(\frac{a^{2} + b^{2}}{a}\right)bu''' + \frac{2}{a}(a^{2} + b^{2})^{2}u'u'' \right] + \eta H_{2}(bH'_{2} - aH'_{1})$$
(23)
$$bH'_{1} + aH'_{2} = 0$$
(24)

$$C(bH_1'' - aH_1'')$$

$$= (a^{2} + b^{2}) \left[\frac{1}{\Lambda \delta} (bH_{2}^{'''} - aH_{1}^{'''}) + vH_{1}^{''} - uH_{2}^{''} + H_{1}v^{''} - H_{2}u^{''} \right]$$
(25)

$$(C + bu + av)T' = \frac{k}{\rho C_p} (a^2 + b^2)T'' + \frac{\mu}{\rho C_p} (a^2 + b^2)u'^2 + \frac{\alpha_1}{\rho C_p} \left[a^2 (bu + av) + \frac{C}{a^2} (a^2 + b^2)^2 \right] u'u''(26)$$

where $u = \frac{\mu}{\rho}$ and $\beta = \frac{\alpha_1}{\rho}$ are kinematical viscosity and non-Newtonian parameter respectively and $\eta = \frac{\Lambda}{\rho}$

On integrating the Eqs. (21) and (24), we have

$$bu + av = m_1 \tag{27}$$

$$bH_1 + aH_2 = m_2 \tag{28}$$

where m_1, m_2 are arbitrary constants. Here we assumed $m_2 = 0$

On utilizing Eqs. (27) and (28) in Eqs. (21), (22), (25) and (26), we have

$$(C+m_{1})u' = -\frac{b}{\rho}p' + v(a^{2}+b^{2})u'' + \beta \left[(C+m_{1})(a^{2}+b^{2})u''' + \frac{2b}{a^{2}}(a^{2}+b^{2})^{2}u'u'' \right] + \eta \frac{(a^{2}+b^{2})}{b}H_{1}H'_{1}$$
(29)
$$(C+m_{1})v' = -\frac{a}{\rho}p' + v(a^{2}+b^{2})v''$$

$$+ \beta \left[-(C+m_1) \left(\frac{a^2+b^2}{a} \right) b u''' + \frac{2}{a} (a^2+b^2)^2 u' u'' \right]$$
$$- \eta \frac{(a^2+b^2)}{b} H_2 H_2'$$
(30)

$$(a^2 + b^2)H_1''' - CH_1'' = 0 \tag{31}$$

$$\begin{aligned} (C+m_1)T' &= \frac{k}{\rho C_p} (a^2 + b^2) T'' + \frac{\mu}{\rho C_p} (a^2 + b^2)^2 u'^2 \\ &+ \frac{\alpha_1}{\rho C_p} \left[\frac{U(a^2 + b^2) + a^4 m_1}{a^2} \right] u' u'' \end{aligned}$$
(32)

On eliminating pressure p from Eqs. (29) and (30), we get

$$u''' - Mu'' - Nu' = 0 (33)$$

where

$$M = rac{\mu}{lpha_1(C+m_1)}, \quad N = rac{
ho}{lpha_1(a^2+b^2)}$$

The components of velocity are

$$u(\xi) = m_3 e^{n_1 \xi} + m_4 e^{n_2 \xi} - \frac{m_5}{N}$$
(34)

$$v(\xi) = \frac{m_1}{a} - \frac{b}{a} \left(m_3 e^{n_1 \xi} + m_4 e^{n_2 \xi} - \frac{m_5}{N} \right)$$
(35)

where n_1, n_2 are the roots of the equation $n^2 - Mn - N = 0$ From Eq. (31), the components of magnetic field are

From Eq. (51), the components of magnetic field are

$$H_1(\xi) = m_6 e^{\overline{(a^2 + b^2)}^{\xi}} + m_7 \xi + m_8$$
(36)

$$H_2(\xi) = -\frac{b}{a} \left(m_6 e^{\left(\frac{a^2 + b^2}{a^2 + b^2} \right)^{\xi}} + m_7 \xi + m_8 \right)$$
(37)

Substituting Eqs. (34) and (36) into Eq. (29), we obtain

$$p(\xi) = M_1 e^{n_1 \xi} + M_2 e^{n_2 \xi} + M_3 e^{2n_1 \xi} + M_4 e^{2n_2 \xi} + M_5 e^{(n_1 + n_2)\xi} + M_6 \left(m_6 e^{\frac{C}{(n^2 + \rho^2)}\xi} + m_7 \xi + m_8 \right)^2 + M_7$$
(38)

Where
$$n_1, n_2$$
 are the roots of the equation

$$M_{1} = \frac{m_{3} \left[-\rho(c+m_{1}) + \left(a^{2}+b^{2}\right) \left\{\mu m_{1} + \alpha_{1} m_{4} n_{1}^{2}(C+m_{1})\right\}\right]}{b}$$
$$M_{2} = \frac{m_{4} \left[-\rho(c+m_{1}) + \left(a^{2}+b^{2}\right) \left\{\mu m_{2} + \alpha_{1} m_{4} n_{2}^{2}(C+m_{1})\right\}\right]}{b}$$
$$M_{3} = \frac{\alpha_{1} n_{1}^{2} m_{3}^{2} \left(a^{2}+b^{2}\right)^{2}}{a^{4}}$$
$$M_{4} = \frac{\alpha_{1} n_{2}^{2} m_{4}^{2} \left(a^{2}+b^{2}\right)^{2}}{a^{4}}$$

$$M_{5} = \frac{2\alpha_{1}m_{3}m_{4}n_{1}n_{2}(a^{2} + b^{2})}{a^{4}}$$
$$M_{6} = \frac{\Lambda(a^{2} + b^{2})}{2b^{2}}$$
$$M_{7} = \frac{bNm_{9} + \rho m_{5}(C + m_{1})}{bN}$$

Utilizing Eqs. (27) and (34) in Eq. (26) and integrating, we obtain

$$T(\xi) = M_9 e^{2n_1\xi} + M_{10} e^{2n_2\xi} + M_{11} e^{(n_1+n_2)\xi} + m_{10} e^{M_8\xi} - \frac{m_9}{M_8}$$
(39)

$$M_8 = \frac{\rho C_p (C+m_1)}{k(a^2+b^2)}$$

$$M_9 = \frac{-n_1 \lambda_2^2 (a^2+b^2)}{k(2n_1-A_7)} \left[\mu(a^2+b^2) + \frac{n_1 \alpha_1 \{ U(a^2+b^2) + a^4 \lambda_1 \} }{2(a^2+b^2)} \right]$$

$$M_{10} = \frac{-n_2 \lambda_3^2 (a^2+b^2)}{k(2n_2-A_7)} \left[\mu(a^2+b^2) + \frac{n_2 \alpha_1 \{ U(a^2+b^2) + a^4 \lambda_1 \} }{2(a^2+b^2)} \right]$$

$$M_{11} = \frac{-2\lambda_2 \lambda_3 n_1 n_2 (a^2+b^2)}{k(n_1+n_2-A_7)} \left[\frac{\mu(a^2+b^2)}{(n_1+n_2)} + \frac{\alpha_1 \{ U(a^2+b^2) + a^4 \lambda_1 \} }{2(a^2+b^2)} \right]$$

The velocity components, pressure, temperature and magnetic field components in the original variables are

$$u(x, y, t) = m_3 e^{n_1(bx+ay+Ct)} + m_4 e^{n_2(bx+ay+Ct)} - \frac{m_5}{N}$$
(40)

$$v(x, y, t) = \frac{m_1}{a} - \frac{b}{a} \left(m_3 e^{n_1(bx+ay+Ct)} + m_4 e^{n_2(bx+ay+Ct)} - \frac{m_5}{N} \right)$$
(41)

$$p(x, y, t) = M_1 e^{n_1(bx+ay+Ct)} + M_2 e^{n_2(bx+ay+Ct)} + M_3 e^{2n_1(bx+ay+Ct)} + M_4 e^{2n_2(bx+ay+Ct)} + M_5 e^{(n_1+n_2)(bx+ay+Ct)} + M_6 \left(m_6 e^{\frac{C}{(a^2+b^2)}(bx+ay+Ct)} + m_7(bx+ay+Ct) + m_8 \right)^2 + M_7$$
(42)

$$T(x, y, t) = A_8 e^{2n_1(bx+ay+Ct)} + A_9 e^{2n_2(bx+ay+Ct)} + A_9 e^{(n_1+n_2)(bx+ay+Ct)} + (\lambda_2(bx+ay+Ct) + \lambda_2)e^{2A_2(bx+ay+Ct)}$$
(43)

$$H_1(x, y, t) = m_6 e^{\frac{C}{(a^2 + b^2)}(bx + ay + Ct)} + m_4(bx + ay + Ct) + m_8$$
(44)

$$H_2(x, y, t) = -\frac{b}{a} \left(m_6 e^{\frac{C}{(a^2 + b^2)}(bx + ay + Ct)} + m_4(bx + ay + Ct) + m_8 \right)$$
(45)

5. Concluding remarks

The goal to obtain exact solution of an incompressible MHD aligned flow with heat transfer of a second grade fluid. The methodology (Meleshko, 2004) used in this work is easy for linearizing the flow equations by considering travelling wave phenomenon. The method was used in a direct way without transformation, symmetry consideration and restrictive assumptions. It is observed that exponential type solution have been obtained. Finally, compared the velocity and magnetic field in our work by Ali and Mahmood (Ali and Mahmood, 2005) the results are found to be excellent. This guarantees the correctness of the mathematical calculation.

Acknowledgement

The author M. Jamil highly thankful and grateful to the Abdus Salam School of Mathematical Sciences, GC University, Lahore, Pakistan; Department of Mathematics, NED University of Engineering & Technology, Karachi-75270, Pakistan and also Higher Education Commission of Pakistan for supporting and facilitating this research work.

References

- Afify, A.A., 2009. Some new exact solutions for MHD aligned creeping flow and heat transfer in second-grade fluid by using Lie group analysis. Nonlinear Analysis: Theory, Methods and Applications 70 (9), 3298–3306.
- Ali, A., Mahmood, A., 2005. Symmetry reduction of unsteady MHD aligned second grade flow equations. Mathematical and Computational Applications 10 (3), 395–402.
- Ali, M., Hasan, M., 2007. A different approach to exact solutions in non-Newtonian second-grade of creeping fluid. Applied Mathematics and Computation 191, 484–490.
- Ali, S.A., Ara, A., Khan, N.A., 2007. Martin's method applied to steady plane flow of a second grade fluid. International Journal of Applied Mathematics and Mechanics 3 (3), 71–81.
- Benharbit, A.M., Siddiqui, A.M., 1992. Certain solutions of the equations of the planar motion of a second grade fluid for steady and unsteady cases. Acta Mechanica 94, 85–96.
- Berker, R., 1963. Intégration des equations du movement d'un fluide visqueux incompressible, Handbuch der physic, Bd VIII/2. Springer, Berlin, pp. 1–384.
- Chandna, O.P., Oku-Ukpong, E.O., 1994a. Flows for chosen vorticity functions exact solutions of the Navier–Stokes equations. International Journal of Mathematics and Mathematical Sciences 17 (1), 155–164.
- Chandna, O.P., Oku-Ukpong, O.P., 1994b. Unsteady second grade aligned MHD fluid flow. Acta Mechanica 107, 77–91.
- Chandna, O.P., Barron, R.M., Smith, A.C., 1982. Rotational plane flows of a viscous fluid. SIAM Journal of Applied Mathematics 42 (6), 1323–1336.
- Coleman, B.D., Noll, W., 1960. An approximation theorem for functionals with applications in continuum mechanics. Archive of Rational Mechanics Analysis 6, 355–370.
- Dolapçi, Í.T., Pakdemirli, M., 2004. Approximate symmetries of creeping flow equations of a second grade fluids. International Journal of Nonlinear Mechanics 39, 1603–1619.
- Dunn, J.E., Fosdick, R.L., 1974. Thermodynamic stability and boundedness of fluid complexity 2 and fluids of second grade. Archive of Rational Mechanics Analysis 56, 191–252.
- El-Wakil, S.A., Abdou, M.A., 2008. New exact traveling wave solutions of two non-linear physical models. Nonlinear Analysis: Theory, Methods and Applications 68, 235–245.
- Fetecau, C., Corina, Fetecau, 2006. Starting solutions for the motion of a second grade fluid due to longitudinal and torsional oscillations of a circular cylinder. International Journal of Engineering Sciences 44, 788–796.
- Fetecau, C., Mahmood, A., Corina, Fetecau, Vieru, D., 2008. Some exact solutions for the helical flow of a generalized Oldroyd-B fluid in a circular cylinder. Computer and Mathematics with Applications 56, 3096–3108.
- Hayat, T., Mohyuddin, M.R., Asgher, S., 2005. Some inverse solutions for unsteanian fluid. Tamsui Oxford Journal of Mathematical Sciences 2, 1–20.
- Hui, W.H., 1987. Exact solutions of the unsteady Navier–Stokes equation. Journal of Applied Mathematics and Physics 38, 689–702.
- Kaloni, P.N., Huschilt, K., 1984. Semi inverse solutions of a non-Newtonian fluid. International Journal of Nonlinear Mechanics 19, 373–381.
- Khan, N.A., Ara, A., Jamil, M., 2009. Travelling waves solution of a micropolar fluid. International Journal of Nonlinear Science and Numerical Simulation 10 (9), 1121–1125.

- Labropulu, F., 2000. Exact solutions of non-Newtonian fluid flows with prescribed vorticity. Acta Mechanica 141, 11–20.
- Labropulu, F., 2003. D' Alembert motions for non-Newtonian second grade fluid. International Journal of Nonlinear Mechanics 38, 1027–1036.
- Lin, S.P., Tobak, M., 1986. Reversed flow above a plate with suction. AIAA Journal 24 (2), 334–335.
- Meleshko, S.V., 2004. Methods for Constructing Exact Solutions of Partial Differential Equations. Springer.
- Mohyuddin, M.R., Hayat, T., Mohamed, F.M., Asgher, S., Siddiqui, A.M., 2005. On Solutions for non-linear differential equations arising in Newtonian and non-Newtonian fluids. Nonlinear Dynamics 35, 237–262.
- Mohyud-Din, S.T., Yildirim, A., Gülkanat, Y., 2010. Analytic solution of Volterra's population model. Journal of King Saud University Science 22 (4), 247–250.
- Naeem, R.K., Jamil, M., 2006. On plane study plane flows of an incompressible fluid with variable viscosity. International Journal of Applied Mathematics and Mechanics 2 (3), 32–51.
- Rajagopal, K.R., 1980. On decay of vortices in a second grade fluid. Meccanica 9, 185–188.

- Rajagopal, K.R., Gupta, A.S., 1984. On a class of exact solutions to the equations of motion of a second grade fluid. International Journal of Engineering Sciences 19, 373–381.
- Siddiqui, A.M., 1990. Some more inverse solutions of a non-Newtonian fluid. Mechanics Research Communication 17, 157–163.
- Siddiqui, A.M., Kaloni, P.N., 1986. Certain-inverse solutions of a non-Newtonian fluid. International Journal of Nonlinear Mechanics 21, 459–473.
- Siddiqui, A.M., Kaloni, P.N., Chandna, O.P., 1985. Hodograph transformation methods in non-Newtonion fluids. Journal of Engineering Mathematics 19, 203–216.
- Ting, T.W., 1963. Certain nonsteady flows of second-order fluids. Archive of Rational Mechanics Analysis 14 (1963), 1–26.
- Yildirim, A., Gülkanat, Y., 2010. Analytical approach to fractional Zakharov–Kuznetsov equations by He's homotopy perturbation method. Communications in Theoretical Physics 53 (6), 1005– 1010.
- Yürüsoy, M., 2004. Similarity solutions for creeping flow and heat transfer of a second grade fluids. International Journal of Nonlinear Mechanics 39, 665–672.