


NOT SUPPLIES
NASA CR-72541

GESP-237
NASA-CR-72541



**CASE FILE
COPY**

**DETERMINATION OF BIAXIAL CREEP STRENGTH
OF T-111 TANTALUM ALLOY**

SEMI-ANNUAL REPORT
Period September 8, 1968 to March 8, 1969

by
L. B. Engel, Jr.

prepared for
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

NASA Lewis Research Center
Contract NAS 3-9437
Robert L. Davies, Project Manager

NUCLEAR SYSTEMS PROGRAMS
SPACE SYSTEMS
GENERAL ELECTRIC
CINCINNATI, OHIO 45215

NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the National Aeronautics and Space Administration (NASA), nor any person acting on behalf of NASA:

- A.) Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
- B.) Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method or process disclosed in this report.

As used above, "person acting on behalf of NASA" includes any employee or contractor of NASA, or employee of such contractor, to the extent that such employee or contractor of NASA, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with NASA, or his employment with such contractor.

Requests for copies of this report should be referred to:

National Aeronautics and Space Administration
Scientific and Technical Information Division
Attention: USS-A
Washington, D.C. 20546

SEMI-ANNUAL REPORT

DETERMINATION OF BIAXIAL CREEP STRENGTH
OF T-111 TANTALUM ALLOY

prepared by
L. B. Engel, Jr.

approved by
R. W. Harrison

NUCLEAR SYSTEMS PROGRAMS
MISSILE AND SPACE DIVISION
GENERAL ELECTRIC COMPANY
Cincinnati, Ohio 45215

prepared for
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

Period September 8 to March 8, 1969
June 17, 1969

CONTRACT NAS 3-9437

NASA Lewis Research Center
Cleveland, Ohio
Robert L. Davies, Project Manager
Materials Section

TABLE OF CONTENTS

	<u>PAGE NO.</u>
I. INTRODUCTION	1
II. SUMMARY	3
III. PROGRAM STATUS	5
A. T-111 Alloy Test Capsule Manufacture	5
B. Biaxial Creep Capsule Testing	6
C. Preliminary Uniaxial Creep Testing	13
D. 5000 Hour Uniaxial Creep Testing	17
IV. FUTURE PLANS	19

LIST OF ILLUSTRATIONS

<u>Figure No.</u>		<u>Page No.</u>
1	T-111 Alloy Biaxial Creep Capsule Test Facility	7
2	Equivalent Uniaxial Creep in the Liquid Zone of Biaxial Creep Capsule I	9
3	Equivalent Uniaxial Creep in the Condensing Zone of Biaxial Creep Capsule I	10
4	Equivalent Uniaxial Creep Rate in the Liquid Zone of Biaxial Creep Capsule I	11
5	Equivalent Uniaxial Creep Rate in the Condensing Zone of Biaxial Creep Capsule I	12
6	Conventional T-111 Alloy Uniaxial Creep Test Specimen Prior to Testing	14
7	Special Uniaxial Creep Test Specimen Made from Seamless T-111 Alloy Tubing. The Contour of the Specimen is Identical to the Biaxial Creep Capsule Contour in the Test Section and Stress Attenuating Fillets and is a Quarter Section of the Tube	15
8	Uniaxial Creep of T-111 Alloy Tested at 2300 ^o F with a 12,500 psi Stress in a Vacuum of $<1 \times 10^{-8}$ Torr. The Special Specimen was Machined from the Seamless Tube (Preliminary Uniaxial Test No. 4)	16

DETERMINATION OF BIAXIAL CREEP STRENGTH
OF T-111 TANTALUM ALLOY

I. INTRODUCTION

This report covers the period from September 8, 1968 to March 8, 1969, of a program to document the creep behavior of seamless and welded and reworked T-111 alloy tubing under a biaxial state of stress, and to evaluate the effects of stress on the corrosion behavior of T-111 alloy with potassium. Potassium refluxing capsules of seamless and welded and reworked T-111 alloy tubing are being tested under conditions which will result in one to five percent equivalent uniaxial strain during a 5000-hour exposure. The capsule test temperature is 2200°F. The capsule walls are reduced in the potassium liquid region and in the vapor condensing region to provide gauge sections where the extent of creep can be measured. The testing is being done in a manner similar to that developed under an earlier NASA contract. ⁽¹⁾

⁽¹⁾Harrison, R. W., "The Compatibility of Biaxially Stressed D-43 Alloy with Refluxing Potassium," NASA CR-807, June, 1967.

II. SUMMARY

Machining and ultrasonic inspection of a test capsule from the welded and reworked T-111 alloy tube has been completed. The capsule is now ready for postweld annealing.

Testing of Biaxial Creep Capsule I, fabricated from seamless T-111 alloy tubing, was initiated. As of March 8, 1969, 3635 hours of testing have been completed with the capsule at 2200°F. At that time the equivalent uniaxial creep was 0.98% in the liquid zone and 0.93% in the condensing zone.

The fourth preliminary uniaxial test has been completed.

The first 5000-hour uniaxial creep test was initiated at 2200°F with a stress of 8100 psi. As of March 8, 1969, 1914 hours of testing have been completed.

III. PROGRAM STATUS

A. T-111 ALLOY TEST CAPSULE MANUFACTURE

As a result of the cracking and lack of straightness in the finished, welded and reworked T-111 alloy tube, there is only sufficient material to make one test capsule from this tube. Manufacture of a second capsule from the welded and reworked T-111 alloy tube would require significant reductions of the capsule's dimensional tolerances.

Honing of the ID of the welded and reworked T-111 alloy tubing to be used in making the test capsule was completed at Delta Tool Inc., Warren, Michigan. Ultrasonic inspection of the tubing after honing indicated one small defect near the ID of the tube and 1.5 inches in from one end of the tube. This location places the defect within the stress attenuating fillet at a point where the wall thickness will be approximately 0.027 inch thick. A defect of significant size in this area could influence the creep behavior of the adjacent test section. Therefore to more accurately determine the size and location of the defect, a reference mark was placed on the capsule for locating the defect area after machining and the OD fillet contours were machined into the test capsule. Following machining, the defect area was re-examined using ultrasonic techniques to determine in more detail the nature of the defect. No defect was observed in the area where a defect had been detected in the inspection prior to final machining.

Pretest dimensioning and assembly of the test capsule has been completed in the same manner as that used for Biaxial Creep Capsule I, made from the seamless T-111 alloy tube.⁽²⁾ The test capsule, Biaxial Creep Capsule II, made from the welded and reworked T-111 alloy tube, is now ready for postweld annealing.

⁽²⁾ Engel, L. B., "Determination of Biaxial Creep Strength of T-111 Tantalum Alloy," Semi-annual Report, NASA-CR-72528, General Electric Company, NSP, NASA Contract NAS 3-9437, Period March 9, 1968, to September 8, 1968.

B. BIAXIAL CREEP CAPSULE TESTING

Biaxial Creep Capsule I, made from the seamless T-111 alloy tube, was installed in the test facility as shown in Figure 1. The linear variable differential transformers (LVDT's) were calibrated prior to installation and their precision was found to be approximately ± 0.0001 -inch. The 18-inch diameter, getter-ion pumped, vacuum chamber was sealed and evacuated to approximately 5×10^{-7} torr before bakeout was initiated. The chamber was baked out at 500°F for 12 hours. During this time the argon gas pressure system which is connected to the potassium pressure transducer was also evacuated and baked out at approximately 500°F. Following bakeout, the gas pressure system was filled with argon and evacuated three times before final filling to a pressure of approximately 5 psia.

On October 2, 1968, heating of the test capsule was initiated. When the test capsule temperature reach 1000°F, power was applied to the boiling nucleator heater and the nucleator temperature was maintained between 100 and 150°F above the test capsule temperature during subsequent capsule heat up. Slightly less uniform boiling was noted in the capsule when the capsule reached approximately 1300°F but this condition subsided at approximately 1500°F. When the test capsule temperature reached 1800°F, the power to the boiling nucleator was turned off and no changes in boiling stability were observed. During capsule heat up the argon gas pressure in the pressure transducer gas system was increased so as to produce a minimum pressure differential on the transducer diaphragm. The capsule reached the 2200°F test temperature on October 7, 1968. The maximum chamber pressure reached during capsule heat up was 7×10^{-7} torr. As of March 8, 1969, 3635 hours of testing of the planned 5000 hours have been completed. The vacuum chamber pressure at that time was 5.9×10^{-9} torr.

The average potassium pressure in the test capsule at this time is 267.0 psia and results in average equivalent uniaxial stresses in the test sections of 8229 psi in the liquid zone and 8106 psi in the condensing zone.




Figure 1. T-111 Alloy Biaxial Creep Capsule Test Facility. (P68-9-45B)

The equivalent uniaxial creep data for Biaxial Creep Capsule I in the liquid zone and condensing zone are shown in Figures 2 and 3, respectively. The data for the liquid zone was computed from capsule diameter measurements obtained with LVDT's. The data for the condensing zone was computed from capsule diameter measurements obtained with an optical extensometer. The LVDT's being used in the condensing zone became inoperative during testing and could not be used. The scatter in the data for the condensing zone is the result of not being able to accurately locate the sides of the capsule with the optical extensometer. The curves shown in Figures 2 and 3 were developed by iterative least squares solutions⁽³⁾ of the Garofalo creep-time equation:⁽⁴⁾

$$\epsilon = \epsilon_0 + \epsilon_t(1 - e^{-rt}) + \dot{\epsilon}_s t$$

where:

ϵ = strain at time t

ϵ_0 = strain observed upon loading

ϵ_t = limiting transient creep strain

r = ratio of transient creep rate to transient creep strain

$\dot{\epsilon}_s$ = secondary creep rate.

The derivatives of the curves in Figures 2 and 3, which yield the creep rates for the tests, are shown in Figures 4 and 5, respectively, and indicate that secondary creep was established after approximately 2000 hours of testing. An extrapolation of the Garofalo equation to 5000 hours predicts that approximately 1.3 percent creep should be obtained in the capsule in 5000 hours of testing.

(3) Deming, W. E., Statistical Adjustment of Data, Dover Publications, Inc., New York (1964).

(4) Garofalo, F., Fundamentals of Creep and Creep-Rupture in Metals, The Macmillan Company, New York, p. 16-17 (1965).




Figure 2. Equivalent Uniaxial Creep in the Liquid Zone (2220° F) of Biaxial Creep Capsule I.




Figure 3. Equivalent Uniaxial Creep in the Condensing Zone (2200°F) of Biaxial Creep Capsule I.




Figure 4. Equivalent Uniaxial Creep Rate in the Liquid Zone (2220°F) of Biaxial Creep Capsule I.




Figure 5. Equivalent Uniaxial Creep Rate in the Condensing Zone (2200°F) of Biaxial Creep Capsule I.

C. PRELIMINARY UNIAXIAL CREEP TESTING

Preliminary uniaxial creep tests are being used to obtain baseline creep data for the final selection of test conditions for the 5000-hour tests and to evaluate a special uniaxial creep test specimen design which more closely resembles the biaxial capsule test section design.

In the three previously completed preliminary uniaxial tests, a more conventional test specimen, shown in Figure 6, was utilized. From the results of these tests, a test temperature of 2200°F was selected for the 5000-hour biaxial creep capsule test.⁽⁵⁾ Presently, a fourth preliminary uniaxial creep test has been completed using the special uniaxial test specimen shown in Figure 7. As mentioned earlier, this specimen more closely resembles the biaxial capsule test section in that it has a similar reduced wall test section with stress attenuating fillets. The fourth preliminary uniaxial creep test was conducted at the same test conditions as the third preliminary test, i.e., 2300°F at a stress of 12,500 psi in a vacuum of $<1 \times 10^{-8}$ torr. From the least squares linear correlation of the data plotted in Figure 8, one percent creep was found to occur in 58.6 hours. A similar treatment of the data from the third test showed one percent creep to occur in 84.1 hours. The creep rates were found to be 1.052×10^{-4} in/in/hr and 1.173×10^{-4} in/in/hr for the third and fourth tests respectively. Possible explanation of the differences in the test results because of test specimen design are not straight forward since a statistical treatment of the data shows the creep rate for the third test to be $1.052 \times 10^{-4} \pm 0.043 \times 10^{-4}$ in/in/hr, and for the fourth test $1.172 \times 10^{-4} \pm 0.146 \times 10^{-4}$ in/in/hr using a 95 percent confidence level. Although the creep rate for the fourth test appears larger than that for the third test, consideration of the error limits indicates that the creep rates may not be significantly different. More tests of longer duration would be needed to improve the evaluation.

⁽⁵⁾ Engel, L. B., "Determination of Biaxial Creep Strength of T-111 Tantalum Alloy," Semiannual Report, NAS-CR-72528, General Electric Company, NSP, NASA Contract NAS 3-9437, Period March 9, 1968, to September 8, 1968.




Figure 6. Conventional T-III Alloy Uniaxial Creep Test Specimen Prior to Testing. (C68050719)




Figure 7. Special Uniaxial Creep Test Specimen Made from Seamless T-111 Alloy Tubing. The Contour of the Specimen is Identical to the Biaxial Creep Capsule Contour in the Test Section and Stress Attenuating Fillets and is a Quarter Section of the Tube. (C680719170)




Figure 8. Uniaxial Creep of T-111 Alloy Tested at 2300° F with a 12,500 psi Stress in a Vacuum of $<1 \times 10^{-8}$ Torr. The Special Specimen was Machined from the Seamless Tube (Preliminary Uniaxial Test No. 4).

D. 5000-HOUR UNIAXIAL CREEP TESTING

In the present program, two 5000-hour uniaxial tests are scheduled. Because of the preliminary uniaxial creep test results it has been decided to test one conventional design specimen and one special design specimen. The first 5000-hour uniaxial creep test was initiated on December 18, 1968. The test specimen is the special test specimen shown previously in Figure 7.

Prior to loading the test specimen, it was annealed at 2400°F for one hour in the creep facility at pressures of less than 4×10^{-8} torr as were the previous preliminary uniaxial tests. This heat treatment gives the uniaxial test specimens the same thermal history as the biaxial creep capsule which was postweld annealed at 2400°F for one hour. Following the anneal the specimen temperature was reduced to 2200°F and loaded to a stress of 8100 psi. The test conditions for the uniaxial test are therefore approximately the same as those for the biaxial creep capsule. As of March 8, 1969, 1914 hours of testing have been completed. The vacuum chamber pressure at that time was 4.7×10^{-9} torr. Analysis of the test data is now in progress.

IV. FUTURE PLANS

- A. Preparation of the test capsule from the welded and reworked T-111 tube will be completed and the capsule will be put on test.
- B. Biaxial Creep Capsule I will complete 5000 hours of testing at 2200°F on May 4, 1969.
- C. The first uniaxial creep test will complete 5000 hours of testing at 2200°F on July 14, 1969.
- D. The second uniaxial creep test will be initiated.

DISTRIBUTION LIST - SEMI-ANNUAL REPORT

CONTRACT NAS 3-9437

NASA
Washington, D. C. 20546
ATTN: Arvin Smith (RNW)
S. V. Manson (RNP)
George C. Deutsch (RR)
Dr. Fred Schulman (RNP)

NASA - Lewis Research Center
21000 Brookpark Road
Cleveland, Ohio 44135
ATTN: Librarian MS 3-7
Dr. B. Lubarsky MS 500-201
G. M. Ault MS 105-1
R. L. Davies MS 500-201
J. E. Dilley MS 500-309
M. Sabala MS 3-19
T. A. Moss MS 500-201
Coulson Scheuermann (106-1)
Report Control Office MS 5-5
V. F. Hlavin MS 3-14

NASA
Scientific & Technical Infor. Fac.
P. O. Box 33
College Park, Maryland 20740
ATTN: Acquisitions Branch
(SQT-34054) (2 + Repro.)

NASA
Goddard Space Flight Center
Greenbelt, Maryland 20771
ATTN: Librarian

NASA
Langley Research Center
Hampton, Virginia 23365
ATTN: Librarian

NASA
Manned Spacecraft Center
Houston, Texas 77001
ATTN: Librarian

NASA
George C. Marshall Space Flight Center
Huntsville, Alabama 35812
ATTN: Librarian

Jet Propulsion Laboratory
California Institute of Technology
4800 Oak Grove Drive
Pasadena, California 91103
ATTN: Librarian

National Bureau of Standards
Washington, D. C. 20225
ATTN: Librarian

Flight Vehicle Power Branch
Air Force Aero-Propulsion Lab
Wright Patterson AFB, Ohio 45433
ATTN: Charles Armbruster ASRPP-10
T. Cooper
Librarian
George E. Thompson APIP-1
George Sherman API
George Glenn

Army Ordnance Frankford Arsenal
Bridesburg Station
Philadelphia, Pennsylvania 19137
ATTN: Librarian

Bureau of Mines
Albany, Oregon
ATTN: Librarian

Bureau of Ships
Department of the Navy
Washington, D. C. 20225
ATTN: Librarian

Bureau of Weapons
Research and Engineering
Materials Division
Washington, D. C. 20225
ATTN: Librarian

U.S. Atomic Energy Commission
Technical Reports Library
Washington, D. C. 20545
ATTN: J. M. O'Leary (2)

U. S. Atomic Energy Commission
Germantown, Maryland 20767
ATTN: K. E. Horton

NAS 3-9437

U. S. Atomic Energy Commission
Technical Information Service Ext.
P. O. Box 62
Oak Ridge, Tennessee 27831 (3)

U. S. Atomic Energy Commission
Washington, D. C. 20545
ATTN: M. J. Whitman

Office of Naval Research
Power Division
Washington, D. C. 20225
ATTN: Librarian

U. S. Naval Research Laboratory
Washington, D. C. 20225
ATTN: Librarian

AiResearch Manufacturing Company
Sky Harbor Airport
402 South 36th Street
Phoenix, Arizona 85034
ATTN: Librarian
E. A. Kovacevich
John Dannan

AiResearch Manufacturing Company
9851-9951 Sepulveda Boulevard
Los Angeles, California 90045
ATTN: Librarian

Argonne National Laboratory
9700 South Cross Avenue
Argonne, Illinois 60440
ATTN: Librarian

Atomics International
8900 DeSoto Avenue
Canoga Park, California 91303
ATTN: Librarian
Harry Pearlman

AVCO
Research & Advanced Development Prog.
201 Lowell Street
Wilmington, Massachusetts 01800
ATTN: Librarian

Babcock & Wilcox Company
Research Center
Alliance, Ohio 44601
ATTN: Librarian

Battelle Memorial Institute
505 King Avenue
Columbus, Ohio 43201
ATTN: Dr. E. M. Simmons
Librarian

The Bendix Corporation
Research Laboratories Division
Southfield, Michigan 48200
ATTN: Librarian

The Boeing Company
Seattle, Washington 98100
ATTN: Librarian

Brookhaven National Laboratory
Upton, Long Island, New York 11973
ATTN: Librarian

Chance Vought Aircraft, Inc.
P. O. Box 5907
Dallas, Texas 75222
ATTN: Librarian

Clevite Corporation
Mechanical Research Division
540 East 105th Street
Cleveland, Ohio 44108
ATTN: N. C. Beerli

Convair Astronautics
5001 Kerry Villa Road
San Diego, California 92111
ATTN: Librarian

Curtiss-Wright Corporation
Research Division
Quehanna, Pennsylvania
ATTN: Librarian

Eitel McCullough, Inc.
301 Industrial Way
San Carlos, California
ATTN: M. Parkman

Electro-Optical Systems, Inc.
Advanced Power Systems Division
Pasadena, California 91100
ATTN: Librarian

NAS 3-9437

Lawrence Radiation Laboratory
Livermore, California
ATTN: Librarian (2)

Allis Chalmers
Atomic Energy Division
Milwaukee, Wisconsin
ATTN: Librarian

Allison-General Motors
Energy Conversion Division
Indianapolis, Indiana
ATTN: Librarian

AMF Atomics
140 Greenwich Avenue
Greenwich, Connecticut
ATTN: Librarian

American Machine And Foundry Company
Alexandria Division
1025 North Royal Street
Alexandria, Virginia
ATTN: Librarian

Douglas Aircraft Company, Inc.
Missile & Space Systems Division
3000 Ocean Park Boulevard
Santa Monica, California
ATTN: Librarian

Climax Molybdenum Company of Michigan
1600 Huron Parkway
Ann Arbor, Michigan 48105
ATTN: Librarian
Dr. M. Semchyshen

Fansteel Metallurgical Corporation
North Chicago, Illinois
ATTN: Librarian

National Research Corporation
405 Industrial Place
Newton, Massachusetts
ATTN: Librarian

Universal Cyclops Steel Corporation
Refractomet Division
Bridgeville, Pennsylvania
ATTN: C. P. Mueller

Los Alamos Scientific Laboratory
University of California
Los Alamos, New Mexico
ATTN: Librarian

Lockheed Georgia Company
Division, Lockheed Aircraft Company
Marietta, Georgia
ATTN: Librarian

Sandia Corporation
Div. 9333
P. O. Box 5800
Albuquerque, New Mexico 87115
ATTN: James Jacobs