

General Disclaimer

One or more of the Following Statements may affect this Document

metadata, citation and similar papers at core.ac.uk

brought to you by

provided by NASA Technical Re

much information as possible.

- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

N69-24881

(ACCESSION NUMBER)	(THRU)
11	
(PAGES)	(CODE)
66-100817	32
(NACA CR OR TRS OR AD NUMBER)	(CATEGORY)

FAGILITY FORM 602

THE EFFECT OF EXTERNAL DAMPING
ON THE STABILITY OF BECK'S COLUMN¹

by

R. H. Plaut

Assistant Professor of Applied Mathematics (Research)
Center for Dynamical Systems
Division of Applied Mathematics
Brown University
Providence, Rhode Island 02912

¹This research was supported in part by the National Aeronautics and Space Administration under Grant No. NGL-40-002-015, in part by the United States Army, Durham, under Contract No. DA-31-124-ARO-D-270, and in part by the Air Force Office of Scientific Research, under Grant No. AF-AFOSR 67-0693A.

ABSTRACT

The stability of a cantilevered column subjected to a constant follower load in the presence of external damping is investigated. It is shown that the buckling load increases with increasing damping from the value $20.05 EI/L^2$ at zero damping to the limiting value $37.7 EI/L^2$ for infinite damping.

THE EFFECT OF EXTERNAL DAMPING
ON THE STABILITY OF BECK'S COLUMN

The influence of damping on the stability of nonconservative elastic systems has been a subject of recent interest (see [1] for references). The presence of damping has a "stabilizing" effect in some cases and a "destabilizing" effect in others. This note considers the case of Beck's column, a linear elastic cantilevered column subjected to a constant follower load at its free end. External damping of a linear viscous nature is assumed to be present. An approximate expression for the critical load of the column will be derived, and it will be seen that an increase in the damping coefficient causes an increase in the critical load. Contrary to what one might expect, however, the critical load does not become unbounded for large damping.

In nondimensional form, the equation of motion for the lateral displacement $w(x,t)$ of the column is assumed to be

$$\frac{\partial^2 w}{\partial t^2} + \frac{\partial^4 w}{\partial x^4} + p \frac{\partial^2 w}{\partial x^2} + 2\xi \frac{\partial w}{\partial t} = 0, \quad 0 < x < 1, \quad t \geq 0. \quad (1)$$

Here the x -axis lies along the straight equilibrium shape of the column with $x = 0$ at the built-in end and $x = 1$ at the free end. The time is denoted by t , and $\xi (> 0)$ is the coefficient of damping. The compressive force p is applied at the free end in such a manner that it remains tangential to the column during motion. The boundary conditions are given by

$$w(0,t) = \frac{\partial w}{\partial x}(0,t) = \frac{\partial^2 w}{\partial x^2}(1,t) = \frac{\partial^3 w}{\partial x^3}(1,t) = 0, \quad t \geq 0, \quad (2)$$

while the initial displacement $w(x,0)$ and initial velocity $\frac{\partial w}{\partial t}(x,0)$ are allowed to be arbitrary.

If one considers a solution of the form

$$w(x,t) = a(t)f(x), \quad (3)$$

then (1) separates into the two equations

$$\frac{d^2 a}{dt^2} + 2\xi \frac{da}{dt} + \lambda a = 0 \quad (4)$$

and

$$\frac{d^4 f}{dx^4} + p \frac{d^2 f}{dx^2} - \lambda f = 0 \quad (5)$$

where λ is a constant. Nontrivial solutions of (5) which satisfy the boundary conditions (2) are given by

$$f(x) = \cosh \gamma x - \cos \eta x + \mu(\gamma \sin \eta x - \eta \sinh \gamma x) \quad (6)$$

where

$$\mu = (\gamma^2 \cosh \gamma + \eta^2 \cos \eta) / (\eta \gamma^2 \sinh \gamma + \eta^2 \gamma \sin \eta), \quad (7)$$

$$\gamma = \left\{ -\frac{p}{2} + \sqrt{\lambda + \frac{p^2}{4}} \right\}^{1/2}, \quad (8)$$

$$\eta = \left\{ \frac{p}{2} + \sqrt{\lambda + \frac{p^2}{4}} \right\}^{1/2}, \quad (9)$$

and λ satisfies the frequency equation

$$2\lambda \cos \eta \cosh \gamma + p \lambda \sin \eta \sinh \gamma + 2\lambda + p^2 = 0. \quad (10)$$

As p increases in value from zero, the two lowest roots λ of (10) approach each other. According to Beck [2] these two roots merge when $p = 20.05$ (slightly different values are given in [3] and [4]). For higher values of p these roots form a complex conjugate pair which shall be denoted by

$$\lambda = \alpha \pm i\beta. \quad (11)$$

Substitution of (11) into (10) yields a complex equation, and setting the real and imaginary parts equal to zero then leads to two transcendental equations in α and β . These equations will not be listed here, but it is noted that they are extremely complicated and untractable. Only the following solution for the special case $\alpha = 0$ has been calculated by the author:

$$\alpha = 0, \beta = 191 \text{ when } p = 37.7. \quad (12)$$

However, one can easily obtain approximate values for α and β .
For example, Deineko and Leonov [3] derived the approximate frequency equation

$$\lambda^2 + (13.36p - 53.34\pi^2)\lambda + 12.14p^2 + 25.75\pi^2 p + 65.38\pi^4 = 0 \quad (13)$$

with the use of the assumption

$$w(x,t) = \phi(t)y_1(x) + \psi(t)y_2(x) \quad (14)$$

where

$$\begin{aligned} y_1(x) &= 5 - \cos 2\pi x - 4 \cos \pi x, \\ y_2(x) &= 28 - \cos \frac{3\pi x}{2} - 27 \cos \frac{\pi x}{2}. \end{aligned} \quad (15)$$

With $\lambda = \alpha \pm i\beta$, solution of (13) yields

$$\begin{aligned} \alpha &= 26.67\pi^2 - 6.68p, \\ \beta &= [-32.48p^2 + 382.05\pi^2 p - 645.97\pi^4]^{1/2} \end{aligned} \quad (16)$$

when $p > 20.23$.

Now recall the differential equation (4) for $a(t)$, with solution

$$a(t) = c_1 e^{\Omega_1 t} + c_2 e^{\Omega_2 t} \quad (17)$$

where

$$\Omega_{1,2} = -\xi \pm \sqrt{\xi^2 - \lambda}. \quad (18)$$

If $\lambda = \alpha \pm i\beta$, then

$$\Omega_{1,2} = -\xi \pm \sqrt{\xi^2 - \alpha - i\beta} \quad \text{or} \quad \Omega_{1,2} = -\xi \pm \sqrt{\xi^2 - \alpha + i\beta}. \quad (19)$$

The column is asymptotically stable (i.e., $w(x,t) \rightarrow 0$ as $t \rightarrow \infty$) if the real part of each Ω is negative. For Ω of the form in (19), this stability condition is equivalent to the inequality

$$\alpha > \frac{\beta^2}{4\xi^2} \quad (20)$$

(see [5]). The column is unstable (i.e., $w(x,t)$ can become unbounded as $t \rightarrow \infty$) if the real part of at least one Ω is positive, that is, if

$$\alpha < \frac{\beta^2}{4\xi^2}. \quad (21)$$

The critical load (or buckling load) p_{cr} is defined such that the column is stable if $p < p_{cr}$ and unstable if $p > p_{cr}$. It follows from (20) and (21) that p_{cr} is the minimum solution p of the equation

$$\alpha = \frac{\beta^2}{4\xi^2} \quad (22)$$

where α and β are functions of p . With the use of the approximate values of α and β given by (16), one obtains

$$26.67\pi^2 - 6.68p_{cr} = \frac{1}{4\xi^2}(-32.48p_{cr}^2 + 382.05\pi^2 p_{cr} - 645.97\xi^4). \quad (23)$$

Solving for p_{cr} gives

$$p_{cr} = 5.88\pi^2 + 0.41\xi^2 - \sqrt{14.71\pi^4 + 1.55\pi^2 \xi^2 + 0.17\xi^4}. \quad (24)$$

This result is depicted in Figure 1.

A comparison of the approximate expression (24) with the exact critical load may be made for the extreme cases of zero damping and infinite damping. For $\xi = 0$ the column is unstable whenever the frequency equation (10) has complex roots, that is, when $p > 20.05$. The expression (24) yields $p_{cr} = 20.23$ for $\xi \rightarrow 0$, a value 1% higher than the exact buckling load.

For the case $\xi \rightarrow \infty$, it is seen from (22) that the exact buckling load corresponds to a solution $\alpha = 0$ of the frequency equation (10), and from (12) it then follows that this load is given by $p = 37.7$. According to stability condition (24), $p_{cr} \rightarrow 39.4$ as $\xi \rightarrow \infty$ (see the dashed line in Figure 1), so that the approximate critical load p_{cr} is $4\frac{1}{2}\%$ higher than the exact value as $\xi \rightarrow \infty$.

In conclusion, it is noted again that the presence of

linear viscous external damping has a "stabilizing" effect on Beck's column. The buckling load increases monotonically with increasing damping but does not approach infinity for infinite damping. In fact, the lower and upper bounds on the buckling load are, respectively, $p = 20.05$ (corresponding to zero damping) and $p = 37.7$ (corresponding to infinite damping).

REFERENCES

- [1] G. HERRMANN, Stability of equilibrium of elastic systems subjected to nonconservative forces, Appl. Mech. Rev. 20, 103 (1967).
- [2] M. BECK, Die Knicklast des einseitig eingespannten, tangential gedrückten Stabes, Z. angew. Math. Phys. 3, 225 and 476 (1952).
- [3] K. S. DEINEKO and M. IA. LEONOV, Dynamic method of investigation of stability of a compressed bar (in Russian), Prikl. matem. i mekh. 19, 738(1955).
- [4] S. P. TIMOSHENKO and J. M. GERE, Theory of Elastic Stability, second edition, McGraw-Hill Book Company (1961).
- [5] H. LEIPHOLZ, "Über den Einfluss der Dämpfung bei nichtkonservativen Stabilitätsproblemen elastischer Stäbe, Ingen. - Arch. 33, 308 (1964).

LEGEND FOR FIGURE

Figure 1. Critical load for Beck's column

