

MECHANICAL TECHNOLOGY INCORPORATED
968 Albany-Shaker Road
Latham, New York 12110

MTI-67TR14

A SEMI-IMPLICIT NUMERICAL METHOD
FOR TREATING THE TIME TRANSIENT
GAS LUBRICATION EQUATION

by

V. Castelli
C. H. Stevenson

March, 1967

TECHNICAL REPORT

**A SEMI-IMPLICIT NUMERICAL METHOD
FOR TREATING THE TIME TRANSIENT
GAS LUBRICATION EQUATION**

Vittorio Castelli *Charles H. Stevenson*

Author (s)

John W. John
Approved

Charles H. T. Parn
Approved

Prepared under

Contract Nonr-3730(00)
Task NR 062-317/4-7-66

Prepared for

DEPARTMENT OF DEFENSE
ATOMIC ENERGY COMMISSION
NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

Administered by

OFFICE OF NAVAL RESEARCH
Department of the Navy

**Reproduction in Whole or in Part is Permitted
for any purpose of the U.S. Government**

MTI
MECHANICAL TECHNOLOGY INCORPORATED
MTI

968 ALBANY - SHAKER ROAD - LATHAM, NEW YORK - PHONE 785-0922

ABSTRACT

This report presents a numerical method for treating the time transient Reynolds equation which has the numerical stability properties of implicit schemes and the speed of execution of explicit methods. These advantages make this method quite suitable for both steady-state and transient calculations.

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION-----	1
TREATMENT OF REYNOLDS EQUATION-----	3
NUMERICAL STABILITY ANALYSIS-----	6
General treatment-----	6
Simplified criteria-----	10
NUMERICAL EXAMPLE-----	14
REFERENCES-----	16
NOMENCLAUTRE-----	17

INTRODUCTION

The research presented in this paper has been motivated by two classes of problems commonly encountered in gas lubrication technology:

- 1) Dynamic response and stability calculations for gas bearing systems are best solved by time transient integration of Reynolds equation in combination with the appropriate dynamic equations of motion of the system components (Ref. 1).
- 2) Steady-state data for extreme operating conditions such as high values of the bearing number Λ and eccentricity ratio ϵ are often obtained with great numerical difficulty by steady-state methods (Refs. 2 and 3) but can be easily obtained by time transient calculations starting from physically reasonable initial conditions and diffusing to the final answer.

Two basic approaches can be used in the time integration of Reynolds equation; they are commonly called the "explicit" and implicit" methods (Ref. 1).

By the explicit method the time derivative of pressure is evaluated from the rest of Reynolds equation taken at time T . The value of the pressure at time $T + \Delta T$ is then obtained by direct extrapolation.

By the implicit method both the value of pressure in the time diffusion term and the highest space derivatives of pressure are taken at time $T + \Delta T$ and solved in terms of the rest of the terms of Reynolds equation taken at time T .

In the explicit method each grid value of pressure at time $T + \Delta T$ is obtained by one explicit algebraic equation.

In the implicit method, due to the inclusion of derivatives of the pressure at time $T + \Delta T$, a system of algebraic equations connecting all grid pressures must be solved. Consequently, integration over one time step requires much

more computation time by the implicit method than by the explicit one.

However, the numerical stability characteristics of the explicit method severely limit the size of the time step that can be utilized, while the stability characteristics of the implicit method are much better and allow much larger values of the time step ΔT .

In conclusion, the explicit method is of fast execution per time step but is limited to short time interval while the implicit method is of slow execution per time step but can utilize a long time interval.

Since it is in the interest of most problems to integrate over a certain time interval, it is obvious that a technique which combines the speed of execution of the explicit method and the numerical stability of the implicit method is quite desirable.

In what follows, one such method is exposed.

TREATMENT OF REYNOLDS EQUATION

Consider the following form of Reynolds equation:

$$\Lambda \frac{\partial \psi}{\partial T} = \left[H\psi \frac{\partial^2 \psi}{\partial X^2} - \psi^2 \frac{\partial^2 H}{\partial X^2} + H \left(\frac{\partial \psi}{\partial X} \right)^2 - \psi \frac{\partial \psi}{\partial X} \frac{\partial H}{\partial X} - \Lambda \frac{\partial \psi}{\partial X} + \right. \\ \left. + H\psi \frac{\partial^2 \psi}{\partial Y^2} - \psi^2 \frac{\partial^2 H}{\partial Y^2} + H \left(\frac{\partial \psi}{\partial Y} \right)^2 - \psi \frac{\partial \psi}{\partial Y} \frac{\partial H}{\partial Y} \right] \quad (1)$$

where all variables are dimensionless and X is the direction of motion.

Let the quantity $H\psi$ be arbitrarily split in the following manner.

$$H\psi = (H\psi)_{0x} + (H\psi)_{1x} = (H\psi)_{0y} + (H\psi)_{1y} \quad (2)$$

and

$$\frac{\partial \psi}{\partial T} = \frac{\psi(T + \Delta T) - \psi(T)}{\Delta T} \quad (3)$$

Equation (1) can now be written as:

$$\frac{\Lambda}{\Delta T} \psi(T + \Delta T) = (H\psi)_{0x} \frac{\partial^2 \psi(T + \Delta T)}{\partial X^2} + (H\psi)_{0y} \frac{\partial^2 \psi(T + \Delta T)}{\partial Y^2} + \\ + \left[(H\psi)_{1x} \frac{\partial^2 \psi}{\partial X^2} - \psi^2 \frac{\partial^2 H}{\partial X^2} + H \left(\frac{\partial \psi}{\partial X} \right)^2 - \psi \frac{\partial \psi}{\partial X} \frac{\partial H}{\partial X} - \Lambda \frac{\partial \psi}{\partial X} + \right. \\ \left. + \frac{\Lambda}{\Delta T} \psi + (H\psi)_{1y} \frac{\partial^2 \psi}{\partial Y^2} - \psi^2 \frac{\partial^2 H}{\partial Y^2} + H \left(\frac{\partial \psi}{\partial Y} \right)^2 - \psi \frac{\partial \psi}{\partial Y} \frac{\partial H}{\partial Y} \right]_T \quad (4)$$

Equation (4) is a general formulation which contains both the explicit method by setting

$$(H\psi)_{0x} = (H\psi)_{0y} = 0$$

and the implicit method by setting

$$(\psi H)_{1x} = (\psi H)_{1y} = 0.$$

By numerically approximating all derivatives of ψ in equation (4) by central differences and considering that the ψ distribution at time T is known, the numerical problem reduces to

$$\begin{bmatrix} \mathbf{L} \end{bmatrix} \left\{ \psi(T + \Delta T) \right\} = \left\{ \mathbf{R} \right\} \quad (5)$$

The solution of equation (5) is

$$\psi(T + \Delta T) = \begin{bmatrix} \mathbf{L} \end{bmatrix}^{-1} \left\{ \mathbf{R} \right\} \quad (6)$$

For the explicit method $\begin{bmatrix} \mathbf{L} \end{bmatrix}$ is diagonal with constant members $\frac{\Delta}{\Delta T}$. Its inverse is also diagonal with constant members $\frac{\Delta T}{\Delta}$ and equation (6) is of simple numerical execution.

For the implicit case $\begin{bmatrix} \mathbf{L} \end{bmatrix}$ is not diagonal and its members vary with ψ from time step to time step. Therefore the inverse $\begin{bmatrix} \mathbf{L} \end{bmatrix}^{-1}$ must be obtained at each time step at the expense of calculation time. (It should be pointed out that the columnwise inversion method of references 2 and 3 is applicable to the solution of equation (5) thus reducing the inversion time considerably but not to the level of the explicit method).

A great improvement over this situation is afforded by the choice

$$(\psi H)_{0x} \text{ and } (\psi H)_{0y} \text{ independent of } T. \quad (7)$$

Indeed, equation (4) has not suffered in accuracy since

$$(\psi H)_{1x} = \psi H - (\psi H)_{0x} \text{ and } (\psi H)_{1y} = \psi H - (\psi H)_{0y}$$

compensate for any difference between the true ψH distribution at time T and the $(\psi H)_{0x}$ and $(\psi H)_{0y}$ distributions, and the operator $\begin{bmatrix} \mathbf{L} \end{bmatrix}$ and its inverse $\begin{bmatrix} \mathbf{L} \end{bmatrix}^{-1}$ do not change with time. Therefore all changes in ψ from time step to time step are reflected in changes of the members of the right hand side $\left\{ \mathbf{R} \right\}$.

The fact that the inversion $[L]^{-1}$ is not performed at each time step reduces the amount of computation to the level of the explicit method.

The necessary condition for the usefulness of the above proposed semi-implicit method is that it be numerically more stable than the explicit method.

NUMERICAL STABILITY ANALYSISGeneral treatment:

Let equation (4) be written with the aid of the following definitions

$$F_1 = \frac{\partial}{\partial \psi} \left(\frac{\partial \psi}{\partial T} \right) \quad (8)$$

$$F_2 = \frac{\partial}{\partial \left(\frac{\partial \psi}{\partial X} \right)} \left(\frac{\partial \psi}{\partial T} \right) \quad (9)$$

$$F_3 = \frac{\partial}{\partial \left(\frac{\partial^2 \psi}{\partial X^2} \right)} \left(\frac{\partial \psi}{\partial T} \right) = F_{30} + F_{31} = \frac{1}{\Lambda} \left[(\psi H)_{0x} + (\psi H)_{1x} \right] \quad (10)$$

$$F_4 = \frac{\partial}{\partial \left(\frac{\partial \psi}{\partial Y} \right)} \left(\frac{\partial \psi}{\partial T} \right) \quad (11)$$

$$F_5 = \frac{\partial}{\partial \left(\frac{\partial^2 \psi}{\partial Y^2} \right)} \left(\frac{\partial \psi}{\partial T} \right) = F_{50} + F_{51} = \frac{1}{\Lambda} \left[(\psi H)_{0y} + (\psi H)_{1y} \right] \quad (12)$$

By standard central difference formulae, equation (4) becomes

$$\begin{aligned} \frac{\psi_{ik}^{j+1} - \psi_{ik}^j}{\Delta T} &= F_1 \psi_{i,k}^j + \frac{F_2}{2\Delta X} (\psi_{i+1,k}^j - \psi_{i-1,k}^j) + \\ &+ \frac{F_4}{2\Delta Y} (\psi_{i,k+1}^j - \psi_{i,k-1}^j) + \frac{F_{30}}{(\Delta X)^2} (\psi_{i+1,k}^{j+1} - 2\psi_{i,k}^{j+1} + \psi_{i-1,k}^{j+1}) + \\ &+ \frac{F_{31}}{(\Delta X)^2} (\psi_{i+1,k}^j - 2\psi_{i,k}^j + \psi_{i-1,k}^j) + \frac{F_{50}}{(\Delta Y)^2} (\psi_{i,k+1}^{j+1} - 2\psi_{i,k}^{j+1} + \psi_{i,k-1}^{j+1}) + \\ &+ \frac{F_{51}}{(\Delta Y)^2} (\psi_{i,k+1}^j - 2\psi_{i,k}^j + \psi_{i,k-1}^j) \end{aligned} \quad (13)$$

Where

- a) The F's are evaluated somewhere in the interval according to the mean value theorem and are considered to vary much slower than the solution components causing numerical instability.
- b) i is the grid index in the X direction
 k is the grid index in the Y direction
 j is the time grid index

Letting

$$\psi_{i,k}^j = \Psi_{i,k}^j + \epsilon_{i,k}^j \tag{14}$$

where $\Psi_{i,k}^j$ are the exact solution to equations (13) and $\epsilon_{i,k}^j$ the deviations of the actual solution $\psi_{i,k}^j$ from it, equations (13) can be transformed into equations for the deviations $\epsilon_{i,k}^j$. Such equations are identical in form to equations (13) with $\epsilon_{i,k}^j$ in place of $\psi_{i,k}^j$ and shall not be written. (This is due to the linearity of equation (13)).

The equations for $\epsilon_{i,k}^j$ can be satisfied by

$$\epsilon(X,Y,T) = \sum_{n=1}^N A_n e^{a_n T + \sqrt{-1} (b_n X + c_n Y)} \tag{15}$$

where every term represents a solution.

Substituting one typical term of (15) into the equations for $\epsilon_{i,k}^j$ and dividing by

$$\frac{e^{a_n T + \sqrt{-1} (b_n X + c_n Y)}}{\Delta T} \text{ yields:}$$

$$\begin{aligned}
 e_n^{a\Delta T} - 1 &= F_1\Delta T + \\
 &+ \frac{F_2\Delta T}{2\Delta X} \left[e^{\sqrt{-1} b_n \Delta X} - e^{-\sqrt{-1} b_n \Delta X} \right] + \frac{F_4\Delta T}{2\Delta Y} \left[e^{\sqrt{-1} c_n \Delta Y} - e^{-\sqrt{-1} c_n \Delta Y} \right] + \\
 &+ \frac{F_{30}\Delta T}{(\Delta X)^2} \left[e^{a_n \Delta T + \sqrt{-1} b_n \Delta X} - 2e^{a_n \Delta T} + e^{a_n \Delta T - \sqrt{-1} b_n \Delta X} \right] + \\
 &+ \frac{F_{31}\Delta T}{(\Delta X)^2} \left[e^{\sqrt{-1} b_n \Delta X} - 2 + e^{-\sqrt{-1} b_n \Delta X} \right] + \\
 &+ \frac{F_{50}\Delta T}{(\Delta Y)^2} \left[e^{a_n \Delta T + \sqrt{-1} c_n \Delta Y} - 2e^{a_n \Delta T} + e^{a_n \Delta T - \sqrt{-1} c_n \Delta Y} \right] + \\
 &+ \frac{F_{51}\Delta T}{(\Delta Y)^2} \left[e^{\sqrt{-1} c_n \Delta Y} - 2 + e^{-\sqrt{-1} c_n \Delta Y} \right] \tag{16}
 \end{aligned}$$

Collecting terms and using the definition of complex exponentials

$$\begin{aligned}
 &- e_n^{a\Delta T} \left\{ -1 - 4F_{30} \frac{\Delta T}{(\Delta X)^2} \sin^2 \frac{b_n \Delta X}{2} - 4F_{50} \frac{\Delta T}{(\Delta Y)^2} \sin^2 \frac{c_n \Delta Y}{2} \right\} = \\
 &= 1 + F_1\Delta T + F_2 \frac{\Delta T}{\Delta X} \sqrt{-1} \sin b_n \Delta X + F_4 \frac{\Delta T}{\Delta Y} \sqrt{-1} \sin c_n \Delta Y + \\
 &- 4F_{31} \frac{\Delta T}{(\Delta X)^2} \sin^2 \frac{b_n \Delta X}{2} - 4F_{51} \frac{\Delta T}{(\Delta Y)^2} \sin^2 \frac{c_n \Delta Y}{2} \tag{17}
 \end{aligned}$$

$e_n^{a\Delta T}$ is the error growth ratio in a time step ΔT . A sufficient condition for numerical stability is that

$$\left| e^{a_n \Delta T} \right| \leq 1 \quad (18)$$

or

$$\left| \frac{+ 1 - 4 \left[F_{31} \frac{\Delta T}{(\Delta X)^2} \sin^2 \frac{b_n \Delta X}{2} + F_{51} \frac{\Delta T}{(\Delta Y)^2} \sin^2 \frac{c_n \Delta Y}{2} \right] + 0(\Delta T)}{+ 1 + 4 \left[F_{30} \frac{\Delta T}{(\Delta X)^2} \sin^2 \frac{b_n \Delta X}{2} + F_{50} \frac{\Delta T}{(\Delta Y)^2} \sin^2 \frac{c_n \Delta Y}{2} \right] + 0(\Delta T)} \right| \leq 1 \quad (19)$$

Writing equation (19) as

$$\left| \frac{1 - 4A}{1 + 4B} \right| < 1 \quad (20)$$

and using the fact that $B > 0$, the stability limits are given by

$$- B < A < 1/2 + B \quad (21)$$

But, since $A + B > 0$, the left limit is always satisfied and it must be that

$$A - B < 1/2$$

or

$$\frac{1}{\Delta T} > \frac{2}{\Lambda} \left[\frac{(\psi H)_{1x} - (\psi H)_{0x}}{(\Delta X)^2} + \frac{(\psi H)_{1y} - (\psi H)_{0y}}{(\Delta Y)^2} \right] \quad (22)$$

Obviously, when the quantity in parenthesis is negative the numerical stability condition is always satisfied. Condition (22) yields

a) the well known explicit stability limit

$$\frac{1}{\Delta T} > \frac{2}{\Lambda} \left[\frac{1}{(\Delta X)^2} + \frac{1}{(\Delta Y)^2} \right] (\psi H)$$

when

$$(\psi H)_{0x} = (\psi H)_{0y} = 0,$$

b) the unconditional stability of the implicit method

when

$$(\psi H)_{1x} = (\psi H)_{1y} = 0.$$

Simplified criteria

1) Equal treatment in both directions

Let

$$(\psi H)_{1x} = (\psi H)_{1y} = (\psi H)_1 \quad \text{and}$$

$$(\psi H)_{0x} = (\psi H)_{0y} = (\psi H)_0 .$$

Then

$$\frac{1}{\Delta T} > \frac{2}{\Lambda} \left[\frac{1}{(\Delta X)^2} + \frac{1}{(\Delta Y)^2} \right] \left[(\psi H)_1 - (\psi H)_0 \right] \quad (23)$$

The simplest way to use this criterion is to have

$$(\psi H)_1 < (\psi H)_0 \quad (24)$$

Thus by selecting $(\psi H)_0$ to be the highest thinkable value of ψH (easily done especially with bearings possessing a "leading edge") it is possible to keep the correction $(\psi H)_1$ always negative and the process always numerically stable.

The question of numerical accuracy remains unchanged, and in true dynamic transient calculations it is important to bear in mind that very large values of the time interval ΔT give erroneous results especially in self-excited whirl threshold evaluations. For the case of steady-state calculations transient accuracy is not important, and since the accuracy of the steady-state answer is not affected by the selection of time interval ΔT , this selection should be made on the basis of expediency. Indeed the rapidity with which the transient settled to the steady-state pressure distribution depends on the time step ΔT . For small values of ΔT the true transient is followed and larger values of ΔT mean longer times to reach steady-state. Typically the pressure at each point is approached asymptotically from one side. For larger values of ΔT the true transient is not followed, the solution tends to the steady-state more rapidly overshooting it and then oscillating about it. As the value of ΔT is raised further the overshoot increases and the number of time steps spent in oscillations increases. Beyond a certain value of ΔT the oscillations become so violent that the solution could be called numerically unstable. The numerical stability analysis presented above does not predict this limit because its validity is limited to small values of the errors while in this case the errors even after one time step are very large.

In conclusion, for the most economical evaluation of steady-state pressure profiles the optimum value of ΔT lies in the region where it produces an incorrect transient which just overshoots the steady-state solution. This depends on the actual geometry under investigation and on the range of running conditions. A few numerical experiments are useful in determining the most economical production value of ΔT .

2) Implicit in one direction only. It may be of great interest to use

$$(\psi H)_{0y} = 0$$

$$(\psi H)_{1y} = \psi H$$

so that the only implicit operator is

$$(\psi H)_{0x} \frac{\partial^2 \psi}{\partial X^2} - \frac{\Lambda}{\Delta T} \psi \quad . \quad (25)$$

Approximating this operator by three point central difference formulae it becomes a three point operator (rather than five point as in the case of $(\psi H)_{0y} \neq 0$).

This affords the great advantage that each X-row of points forms an independent three-diagonal problem. If i denotes an X-row (that is, i runs in the Y direction), the problem can be represented as

$$\sum_j \left[A_{k,j} \right]_i \psi_{i,j} = R_{i,k}; \quad i = 1, M$$

where each matrix $[A]_i$ is tridiagonal and therefore of extremely easy inversion.

The storage problem is also greatly relieved in comparison with the full "columnwise influence coefficients" method.

Analysis of the numerical stability of this particular technique starting from the general formula (22) yields

$$\frac{1}{\Delta T} > \frac{2}{\Lambda} \frac{\psi H}{(\Delta Y)^2} \quad (26)$$

which is the numerical stability limit for one dimensional explicit methods. Therefore, the one direction which is not treated implicitly falls back into the explicit method limitations. However, it should be noticed that

$$\frac{1}{(\Delta Y)^2} < \frac{1}{(\Delta Y)^2} + \frac{1}{(\Delta X)^2}$$

and, by selecting Y so that

$$\Delta Y > \Delta X$$

improvements over the explicit method in the allowable value of ΔT by factors of 4 or 5 are easily obtained. Indeed if

$$\Delta Y = \alpha \Delta X,$$

the improvement over the explicit method stability limit is given by

$$\Delta T = (1 + \alpha^2) \Delta T_{\text{(explicit)}}$$

NUMERICAL EXAMPLE

The results for a numerical example are shown in Figure 1. The case presented is the solution for a one dimensional slider bearing whose particular geometry is shown on the figure. The data plotted are load/steady state load versus the iteration number, with ΔT showing the parametric study. For all cases the initial pressure distribution is set equal to the ambient pressure. From these data, the effect of changing the value of ΔT can be readily seen. For small values of ΔT , the load approaches the steady state solution from one side behaving as a normal physical transient. For the higher values of ΔT , the load overshoots the steady state result and oscillates about it, decaying into the steady state. The higher the value of ΔT , the more violent the oscillation appeared. It should be mentioned here that for this particular analysis, the threshold of stability for the explicit method is $\Delta T < .001$.




FIGURE 1

REFERENCES

1. V. Castelli and H. G. Elrod, "Solution of the Stability Problem for the 360° Gas-Lubricated Journal Bearing", Transactions of the ASME, Journal of Basic Engineering, March, 1965, pp 199-212.
2. V. Castelli and J. Pirvics, "Equilibrium Characteristics of the Axial Groove Gas-Lubricated Bearing", ASME Paper No. 65-LUB-16.
3. V. Castelli and W. Shapiro, "Improved Method for Numerical Solutions of the General Incompressible Fluid Film Lubrication Problem", ASME Paper No. 66-LubS-14.

NOMENCLATURE

c = reference clearance

H = h/c

h = local clearance

L = reference length

P = p/p_a

p = local pressure

p_a = ambient pressure

T = $\frac{tU}{2L}$

t = time

U = effective surface speed

X = $\frac{x}{L}$

x,y = dimensional coordinates on bearing surface

Y = $\frac{y}{L}$

Λ = $6\mu UL / (p_a c^2)$

μ = absolute viscosity

ψ = PH

APPROVED DISTRIBUTION LISTS FOR UNCLASSIFIED TECHNICAL REPORTS
ISSUED UNDER

GAS LUBRICATED BEARINGS CONTRACTS

Contract Nonr 3730(00) NR 062-317

(ONR-4)

Chief of Naval Research Department of the Navy Washington 25, D.C. 20360 Attn: Code 438 429 463	(3)	Commander Naval Ship Systems Command Washington, D.C. 20360 Attn: 6644 C (R. M. Petros)	Commanding General U.S. Army Material Command Research & Development Directorate Research Division Washington, D.C. 20315 Attn: Mr. Norman L. Klein	Mr. Lukasiewicz Chief, Gas Dynamics Facility Arnold Air Force Station Tennessee 37389
Commanding Officer Office of Naval Research Branch Office 495 Summer Street Boston, Massachusetts 02110		Department of the Navy Naval Air Systems Command Washington, D.C. 20360 Attn: (S. M. Collegeman) (H. R. Walters)	Chief of Research and Development Office of Chief of Staff Department of the Army The Pentagon, Washington, D.C. 20310	Mr. Clarence E. Miller, Jr. Division of Reactor Development & Technology U.S. Atomic Energy Commission Washington, D.C. 20545 (2)
Commanding Officer Office of Naval Research Branch Office 279 South Dearborn Street Chicago, Illinois 60604		Director Naval Research Laboratory Washington, D.C. Attn: Code 2027 5230 (6)	Commanding General U.S. Army Engineer R & D Laboratories Fort Belvoir, Virginia 22060 Attn: W. M. Crim, Field Office Technical Documents Center	Mr. N. Grossman, Chief Engineering Development Branch Reactor Development Division U.S. Atomic Energy Commission Washington, D.C. 20545 (2)
Commanding Officer Office of Naval Research Branch Office 207 West 24th Street New York, New York 10011		Special Projects Office Department of the Navy Washington 25, D.C. Attn: Code SP230 (D. Gold) SP001 (Dr. J. P. Craven)	Redstone Scientific Information Center Attn: Chief, Document Section U.S. Army Missile Command Redstone Arsenal, Alabama 35809	Headquarters Library U.S. Atomic Energy Commission Washington, D.C. 20545
Commanding Officer Office of Naval Research Branch Office Box 59 Fleet Post Office New York, New York 09510	(25)	Commanding Officer and Director U.S. Navy Marine Engineering Laboratory Annapolis, Maryland Attn: Code 800 Code 852 (Watt V. Smith)	Commanding Officer U.S. Army Research Office ESD - AROD Box CH, Duke Station Durham, North Carolina 27706	U.S. Atomic Energy Commission Oak Ridge Operations Office P.O. Box E Oak Ridge, Tennessee 37831 Attn: Charles A. Keller
Commanding Officer Office of Naval Research Branch Office 1030 East Green Street Pasadena, California 91101		Superintendent U.S. Naval Postgraduate School Monterrey, California Attn: Library	Chief of Staff U.S. Air Force The Pentagon Washington, D.C. 20330 Attn: AFRDR-AS/M	U.S. Atomic Energy Commission Portsmouth Area Office Pikeon, Ohio 45661 Attn: Dr. Malone
Commanding Officer Office of Naval Research Branch Office 1076 Mission Street San Francisco, California 94103		Commanding Officer U.S. Naval Avionics Facility Indianapolis 18, Indiana Attn: J. G. Weir RDM-4	Commander Air Force Office of Scientific Research Washington, D.C. 20333 Attn: SRHM	Chief, Division of Engineering Maritime Administration 441 G Street, N.W. Washington, D.C. 20235
Defense Documentation Center Cameron Station Alexandria, Virginia 22314	(20)	Dr. W. A. Gross Ampex Corporation 401 Broadway Redwood City, California 94063 (2)	Commander, R & T Division Air Force Systems Command Attn: L.M. Medgepeth (APIP-1) R.W. McAduy (AVNE) Wright-Patterson AFB, Ohio 45433	Cryogenic Data Center National Bureau of Standards Boulder, Colorado 80302
NASA Lewis Research Center Attn: Library MS 60-3 21000 Brookpark Road Cleveland, Ohio 44135		Mr. Stanley L. Zedekar Department 244-2, Building 71 Autonetics P. O. Box 4181 Anaheim, California 92803	AF Flight Dynamics Laboratory Attn: Mr. W. C. Buzzard (PDFM) Wright-Patterson AFB, Ohio 45433	Director, Lewis Research Center National Aeronautics & Space Administration Attn: Mr. E. E. Bisson Cleveland, Ohio 44871
Mr. P. H. Broussard, Jr. Guidance and Control Division National Aeronautics and Space Administration George C. Marshall Space Flight Center Huntsville, Alabama 35812		C. C. Flanigan Director of Engineering Lycoming Division, Avco Corporation Stratford, Connecticut 06497	Air Force Aero Propulsion Laboratory Attn: APFL (Mr. John L. Morris) Wright-Patterson AFB, Ohio 45433	NASA Scientific & Technical Information Facility Attn: Acquisitions Branch (SAK/DL) P. O. Box 33 College Park, Maryland 20740
United States Atomic Energy Commission Div. of Technical Info. Extension P. O. Box 62 Oak Ridge, Tennessee 37830		Dr. Russell Dayton Battelle Memorial Institute 505 King Avenue Columbus, Ohio 43201	Robert H. Josephson, Manager Clevis Corporation Mechanical Research Division 540 East 105th Street Cleveland, Ohio 44108	Professor D. D. Fuller Laboratories for Research and Development The Franklin Institute Philadelphia, Pennsylvania 19104 (3)
Aerojet-General Nucleonics P. O. Box 86 San Ramon, California 94583		Walt Tucker Nuclear Engineering Department Brookhaven National Laboratory Upton, Long Island, New York 11973	Professor V. Castelli Department of Mechanical Engineering Columbia University New York, New York 10027	Mr. Jerry Glaser Senior Project Engineer (Dept 37) AirResearch Manufacturing Division The Garrett Corporation 9851 S. Sepulveda Boulevard Los Angeles, California 90009
Aerospace Corporation P. O. Box 95085 Los Angeles, California 90045 Attn: Library, Reports Acquisitions Group		Jet Propulsion Laboratory California Institute of Technology 4800 Oak Grove Avenue Pasadena, California 91103 Attn: Library	Professor H. Elrod Department of Mechanical Engineering Columbia University New York, New York 10027 (2)	Library General Atomic Division General Dynamics Corporation P. O. Box 608 San Diego, California 92112
AiResearch Manufacturing Company P. O. Box 5217 Phoenix, Arizona 85010 Attn: Mrs. J.F. Mackenzie, Librarian		Dr. F. Osterle Mechanical Engineering Department Carnegie Institute of Technology Pittsburgh, Pennsylvania 15213	Mr. Gerald B. Speen Division Manager Conductron P. O. Box 844 Northridge, California 91324	Mr. G. R. Fox Research and Development Center General Electric Company P. O. Box 8 Schenectady, New York 12381
American Institute of Aeronautics and Astronautics Technical Information Service 750 Third Avenue New York, New York 10017		Professor M. C. Shaw, Head Department of Mechanical Engineering Carnegie Institute of Technology Pittsburgh, Pennsylvania 15213	Mr. J. W. Lower, Chief Engineer-Inertial Components Honeywell Aero Division 2600 Ridgeway Road Minneapolis, Minnesota 55455	Mr. C. C. Moore, Specialist Advanced Bearing & Seal Technology General Electric Company Flight Propulsion Division Cincinnati, Ohio 45215
American Society of Lubrication Engineers 838 Busse Highway Park Ridge, Illinois 60068		Dr. W. T. Sawyer Department of Mechanical Engineering Catholic University Washington, D.C. 20017	Mr. J. Levine Ford Instrument Company 31-10 Thomson Avenue Long Island City, New York 11101	Mr. E. Roland Maki Mechanical Development Department General Motors Corporation 12 Mile and Mound Roads Warren, Michigan 48090
Otto Decker, Manager Friction & Lubrication Lab Franklin Institute 20th and Parkway Philadelphia, Pennsylvania 19103		Mr. George H. Pedersen Curtiss-Wright Corporation Wright Aeronautical Division Woodridge, New Jersey 07075	Engineering Societies Library 345 East 47th Street New York, New York 10017	Mr. Richard J. Matt, Manager Bearing Development & Contract New Departure Division General Motors Corporation Milwaukee, Wisconsin 53201
			Library & Information Services General Dynamics-Convair P. O. Box 1128 San Diego, California 92112	Mr. Howard F. Traeder Instruments Engineering Department AC Electronics Division General Motors Corporation Milwaukee, Wisconsin 53201
			Dr. John E. Mayer, Jr. Research and Engineering Center Ford Motor Company P. O. Box 2053 Dearborn, Michigan 48123	Mr. Walter Carow Kearfott Division General Precision Incorporated 1150 McBride Avenue Little Falls, New Jersey 07425

W. David Craig, Jr.
Mechanical Design Section
Grumman Aircraft Engineering Corporation
Bethpage, Long Island, New York 11714

Mr. P. Eisenberg, President
Hydraulics, Incorporated
Pindell School Road
Howard County
Laurel, Maryland 20810

Professor L. N. Tao
Illinois Institute of Technology
Chicago, Illinois 60616

Mr. Stanley Abramovitz, Director
Industrial Tectonics, Inc.
Fluid Film Bearing Division
New South Road and Commercial Street
Hicksville, Long Island, New York 11803

The Johns Hopkins University
Applied Physics Laboratory
8621 Georgia Avenue
Silver Spring, Maryland 20910
Attn: Fenton L. Kennedy
Document Library

Lockheed Missiles and Space Company
Technical Information Center
3251 Hanover Street
Palo Alto, California 94301

Dr. J. S. Ausman
Litton Systems, Inc.
5500 Canoga Avenue
Woodland Hills, California 91364 (2)

Mr. Don Moors
Litton Systems
5500 Canoga Avenue
Woodland Hills, California 91364 (2)

Library
The Marquardt Corporation
16555 Saticoy
Van Nuys, California 91409

Massachusetts Institute of Technology
Instrumentation Laboratory
68 Albany Street
Cambridge, Massachusetts 02139
Attn: Library, ILL-109

Mr. Sherrill Hisaw
The LaFleur Corporation
16659 South Gramercy Place
Torrance, California

Mr. Edgar J. Gunter, Jr.
University of Virginia
School of Engineering and Applied Science
Charlottesville, Virginia 22903

Mr. J. Licht
Department of Mechanical Engineering
Columbia University
New York, New York 10027

Mr. R. A. Minard
Assistant Product Manager
Gas Bearing Technology Division
MPB Incorporated
Precision Products Division
Keene, New Hampshire

Professor J. Modrey
Department of Mechanical Engineering
Purdue University
Lafayette, Indiana

Mr. J. W. Kannel
Battelle Memorial Institute
505 King Avenue
Columbus, Ohio 43201

Professor Herbert H. Richardson
Room 3-461
Massachusetts Institute of Technology
Cambridge, Massachusetts 02139

McDonnell Aircraft Corporation
Post Office Box 516
St. Louis, Missouri 63166
Attn: Library, Dept. 718

Dr. Beno Sternlicht
Mechanical Technology Incorporated
968 Albany-Shaker Road
Latham, New York 12110

Mr. Carl F. Graesser, Jr.
Director of Research
New Hampshire Ball Bearings, Inc.
Peterborough, New Hampshire 03458

Professor A. Charnes
The Technological Institute
Northwestern University
Evanston, Illinois 60201

Mr. E. L. Swinson, Chief of Research
Precision Products Department
Nortronics
A Division of Northrop Corporation
100 Morse Street
Norwood, Massachusetts 02062

Northrop Norair
3901 West Broadway
Hawthorne, California 90250
Attn: Tech. Info. 3343-32

Professor P. R. Trumpler
Towne School of Civil and Mechanical
Engineering
University of Pennsylvania
Philadelphia, Pennsylvania 19104

Pratt & Whitney Aircraft
Division of UAC - CANEL
P. O. Box 611
Middletown, Connecticut
Attn: Librarian

Radio Corporation of America
Camden, New Jersey 01802
Attn: Library, Building 10-2-5

Mr. Robert S. Siegler
Rocketdyne
Nucleonics Subdivision
6633 Canoga Avenue
Canoga Park, California 91304 (1)

Mrs. Florence Turnbull
Engineering Librarian
Sperry Gyroscope Company
Great Neck, New York 11020

W. G. Wing
Sperry Gyroscope Company
2T120
Great Neck, New York 11020

R. G. Jordan
Oak Ridge Gaseous Diffusion Pl.
Union Carbide Corp. Nuclear Div.
P. O. Box P
Oak Ridge, Tennessee 37830

Ralph F. DeAngelias, Technical Librarian
Norden Division of United Aircraft
Corporation
Helen Street
Norwalk, Connecticut 06852

Mr. J. M. Gruber, Ch. Engrg.
Waukesha Bearings Corporation
P. O. Box 798
Waukesha, Wisconsin 53186

John Boyd
Westinghouse Research Laboratories
Churchill Boro
Pittsburgh, Pennsylvania 15235

Mr. H. Walter
Vice President - Research & Development
Worthington Corporation
Harrison, New Jersey 07029

Dr. Galus G. Goetzl, D/52-30
Bldg. 201, Plant 2, Palo Alto
Lockheed Missiles & Space Company
P. O. Box 504
Sunnyvale, California 94086

Mr. Philip J. Mullan
Staff Engineer - Advanced Tapes
IBM Data Systems Division
Development Laboratory - Box 390
Poughkeepsie, New York 12602

Science & Technology Division
Library of Congress
Washington, D. C. 20540

Admiralty Compass Observatory
Ditton Park
Slough, Bucks, England
Attn: Mr. Henri J. Elwertowski

The University of Southampton
Department of Mechanical Engineering
Southampton, England
Attn: Dr. H. S. Grassam

The Bunker-Ramo Corporation
Attn: Technical Library
8433 Fallbrook Avenue
Canoga Park, California 91804

Research Committee in Information
The American Society of Mechanical
Engineers
345 East 47th Street
New York, New York 10017

Supervisor, Tech. Library Section
Thiokol Chemical Corporation
Wasatch Division
Brigham City, Utah 84302

Mr. Alfonso Alcedan L., Director
Laboratorio Nacional De Hydraulics
Ant iguo Cameno A. Ancon
Casilla Jostal 682
Lima, Peru

National Research Council
Aeronautical Library
Attn: Miss O. M. Leach, Librarian
Montreal Road
Ottawa 7, Canada

Professor J. K. Lunde
Skipsmodelltanken
Trondheim, Norway

Dr. Charles C. W. Ng
IIT Research Institute
10 West 35th Street
Chicago, Illinois 60616

Mr. I. C. Weymouth
Massachusetts Institute of Technology
Instrumentation Laboratory
275 Massachusetts Avenue
Cambridge, Massachusetts 02139

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Mechanical Technology Incorporated 968 Albany-Shaker Road Latham, New York 12110		2a. REPORT SECURITY CLASSIFICATION Unclassified	
		2b. GROUP None	
3. REPORT TITLE A Semi-Implicit Numerical Method For Treating The Time Transient Gas Lubrication Equation			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Technical Report			
5. AUTHOR(S) (Last name, first name, initial) Castelli, Vittorio Stevenson, Charles H.			
6. REPORT DATE March, 1967		7a. TOTAL NO. OF PAGES 17	7b. NO. OF REFS 3
8a. CONTRACT OR GRANT NO. Nonr-3730(00)		9a. ORIGINATOR'S REPORT NUMBER(S) MTI-67TR14	
b. PROJECT NO. Task NR 062-317/4-7-66		9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
c.		d.	
10. AVAILABILITY/LIMITATION NOTICES Copies may be obtained by qualified requestors from DDC			
11. SUPPLEMENTARY NOTES NONE		12. SPONSORING MILITARY ACTIVITY Office of Naval Research	
13. ABSTRACT This report presents a numerical method for treating the time transient Reynolds equation which has the numerical stability properties of implicit schemes and the speed of execution of explicit method. These advantages make this method quite suitable for both steady-state and transient calculations.			

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Transient Reynolds Equation Explicit numerical method Implicit numerical method						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.
- 2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.
- 2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.
3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.
4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.
5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.
6. **REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.
- 7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.
- 7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.
- 8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.
- 8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.
- 9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.
- 9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).
10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.
12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.
13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.